**VALIDATION OF SCALE 4.0 — CSAS25 MODULE AND THE
27-GROUP ENDF/B-IV CROSS-SECTION LIBRARY
FOR LOW-ENRICHED URANIUM SYSTEMS**

W. C. Jordan
Computing and Telecommunications Division
at Oak Ridge National Laboratory
P.O. Box 2008
Oak Ridge, TN 37831-6370

Date Published—February 1993

NOTICE This document contains information of a preliminary nature.
It is subject to revision or correction and therefore does not represent a
final report.

MARTIN MARIETTA ENERGY SYSTEMS, INC.
managing the
Oak Ridge National Laboratory Oak Ridge Y-12 Plant
Oak Ridge K-25 Plant Paducah Gaseous Diffusion Plant
under Contract No. DE-AC05-84OR21400
for the
U.S. DEPARTMENT OF ENERGY

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

CONTENTS

	<u>Page</u>
LIST OF FIGURES	iv
LIST OF TABLES	v
ABSTRACT	vii
1. INTRODUCTION	1
2. DESCRIPTION OF THE CODE PACKAGE	2
2.1 CSAS25 CONTROL SEQUENCE (Version 1.4)	2
2.2 BONAMI-S (Version 1.3)	3
2.3 NITAWL-S (Version 1.3)	3
2.4 KENO V.a (Version 1.5)	4
2.5 THE 27-GROUP NEUTRON CROSS-SECTION LIBRARY (Rev. 2 created 1/27/89, updated 10/12/89)	4
3. CALCULATIONAL PROCEDURE	6
4. PROBLEM DESCRIPTION AND RESULTS	7
5. DISCUSSION AND CONCLUSIONS	14
REFERENCES	18
APPENDIX A. CSAS25 INPUT DATA USE FOR VALIDATION	23
APPENDIX B. CALCULATED RESULTS AND EXPERIMENTAL PARAMETERS	115
APPENDIX C. STATISTICAL ANALYSIS OF VALIDATION RESULTS	117

LIST OF FIGURES

<u>Figure</u>	<u>Page</u>
1. k_{eff} vs AEG low-enriched experiments	15
2. k_{eff} vs AEG high- and low-enriched experiments	16

LIST OF TABLES

<u>Table</u>	<u>Page</u>
1. KENO V.a calculated k_{eff} for experimentally critical low-enriched uranium systems	8
2. KENO V.a calculated k_{eff} for experimentally critical highly enriched uranium systems .	13
3. Average k_{eff}	14

ABSTRACT

A version of KENO V.a and the 27-group library in SCALE-4.0 were validated for use in evaluating the nuclear criticality safety of low-enriched uranium systems. A total of 59 critical systems were analyzed. A statistical analysis of the results was performed, and subcritical acceptance criteria are established.

1. INTRODUCTION

The purpose of this report is to present the results of validation/reverification calculations using KENO V.a¹ in SCALE 4.0.² This validation is limited primarily to low-enriched uranium systems and is intended to demonstrate the ability of KENO V.a in the CSAS25 module³ to accurately calculate systems similar to those encountered at a low-enrichment Gaseous Diffusion Plant (GDP) and in the proposed Atomic Vapor Laser Isotope Separation (AVLIS) facility.

This validation was accomplished by performing calculations on critical systems for which the effective multiplication value, k_{eff} , was known to be very close to 1.0. A statistical analysis was performed on the results of these calculations to determine a lower tolerance band that encompasses the range of calculated k_{eff} values which belong to a group of critical systems.⁴ The statistical treatment provides a high degree of confidence that a calculation that yields a value of k_{eff} below the lower tolerance band is not of a critical system. This lower tolerance band is then used as an upper safety limit for subcriticality.

A total of 59 critical systems were analyzed in this validation. The models of 51 critical systems were selected from a previous validation of KENO V.a reported in ORNL/CSD/TM-238.⁵ Eleven of these 51 models were of highly enriched systems included to demonstrate the ability of the codes to accurately calculate systems over the full enrichment range and to validate the ²³⁵U cross sections. Forty of the models were of low-enriched uranium systems which allow the demonstration of the ability to accurately calculate a broad range of low-enriched systems. Models of 9 low-enriched reactor lattices previously analyzed by H. R. Dyer were included to allow testing the adequacy of the code and cross sections for heterogeneous systems.⁶

A description of the CSAS25 sequence and the major changes that have been made in the various programs are given in Sect. 2. The calculational procedure is given in Sect. 3, and problem descriptions and results are given in Sect. 4.

Section 5 presents a discussion of the results of the calculation. A statistical analysis of the results is presented, and subcriticality acceptance criteria are established.

2. DESCRIPTION OF THE CODE PACKAGE

This report documents the validation of SCALE 4.0 on the ORNL IBM-3090 computer as it existed in November 1990. This version is under configuration management plan SCALE-CMP-001, Rev. 1.⁷ The programs in SCALE 4.0 are not strictly "frozen"; however, they are under stringent configuration change control. This control allows elimination of code errors in a timely manner while introducing minimal concerns for the ability of the programs to perform their prescribed functions. The following subsections give a brief description of the program modules that were validated. The version number of each program is included in the following discussions. The version numbers of the program modules should be checked when calculations are performed to verify that the validated versions are being used. If a code version changes, the nature of the modifications should be reviewed and check cases should be run to see if complete revalidation is warranted.

2.1 CSAS25 SEQUENCE (VERSION 1.4)

This report documents only the CSAS25 control sequence of the CSAS4 control module in SCALE 4.0. The CSAS25 control sequence reads user-specified data, which include the required cross-section library, specifications for mixtures, information for resonance region cross-section processing of nuclides (size, geometry, and temperature), and a detailed geometry model for KENO V.a. Physical and neutronics information not supplied explicitly but required by the functional modules (such as theoretical density, molecular weights, average resonance region background cross sections) is supplied by the Standard Composition Library⁸ and calculated by the Material Information Processor Library (MIPLIB).⁹ These data are used by CSAS25 to set up the input for BONAMI-S,¹⁰ NITAWL-S,¹¹ and KENO V.a. Several significant modifications and enhancements have been developed for the CSAS25 control sequence in SCALE 4.0, compared with earlier versions. These modifications and their impact are described below.

Modifications were made to MIPLIB, called by CSAS25, which impact the input data for NITAWL. An approximation was incorporated into MIPLIB which treats all admixed moderators in a mixture. This modification eliminated a 1.5% positive bias for a series of low-enriched green block experiments, but had little effect on other unbiased low- and high-enriched systems.

Modifications were made to MIPLIB when calculating the Dancoff factor for lattices. The modifications apply a conservative adjustment to the Dancoff factor, eliminating a 50% negative bias for systems in which the mean-free path of the neutron is large with respect to the lattice spacing. This correction has little effect on typical reactor lattices.

Modifications were made to MIPLIB in order to implement an annular treatment in NITAWL. The addition of the annular geometry treatment into NITAWL and the CSAS25 module represents a significant code enhancement. This treatment is implemented automatically for LATTICECELL and MULTIREGION calculations. The annular option may be invoked specifically in LATTICECELL calculations by specifying one of the annular geometries; however, the annular treatment is used in all LATTICECELL geometry specifications. Similarly, the annular geometry treatment is used for all MULTIREGION calculations. The external moderator indices that flag the type of treatment to be used in MULTIREGION calculations are optional input data in SCALE 4.0.

In the annular geometry implementation, an inward and outward transmission probability are calculated. These probabilities are used to obtain the Dancoff factor for the region being treated. Each geometry region is treated independently. A "reasonable" resonance correction is performed for every region. In previous versions of SCALE, certain assumptions had been made about where

the resonance absorbers were located and how they would be treated. These assumptions had the potential of causing a significant error in the resonance correction applied to resonance absorbers that were modeled in a region which had not been anticipated (for example, in the clad region or moderator region of LATTICECELL problems).

Modifications were made to MIPLIB to improve the estimation of the specific gravity of uranyl nitrate solutions. An option was added to allow the specific gravity or density to be entered for any of the solutions or materials in the Standard Composition Library.

2.2 BONAMI-S (VERSION 1.3)

BONAMI-S performs resonance shielding through the application of the Bondarenko shielding factor method. BONAMI-S reads the master-format cross-section library and applies the Bondarenko correction to all nuclides that have Bondarenko data. Input to BONAMI-S, set up by the CSAS25 control sequence, includes information relating to the physical characteristics (composition of material, size, geometry, temperature) of the system being calculated. BONAMI-S produces a Bondarenko-corrected master-format library that is read by NITAWL-S. For the 27-group master cross-section library used in this validation, the primary purpose of the BONAMI functional module is to select the required material cross sections and to create a smaller master cross-section library to be processed by NITAWL-S. No data processing is performed in BONAMI for the 27-group cross-section library.

2.3 NITAWL-S (VERSION 1.3)

NITAWL-S applies the Nordheim Integral Treatment to perform neutron cross-section processing in the resolved resonance range for nuclides that have single-level Breit-Wigner (SLBW) resonance parameter data. This technique involves the numerical integration of SLBW resonance parameters using a calculated flux distribution that is based on the collision density across each resonance and subsequent weighting of the cross-section to the desired broad-group structure. Input data to NITAWL-S, automatically set up by the CSAS25 control sequence, include information relating to the physical and neutronic characteristics of the system being calculated. NITAWL-S uses these data to complete the processing of the problem-dependent master library from BONAMI-S. NITAWL-S assembles the group-to-group transfer arrays from the elastic and inelastic scattering components and performs other tasks to produce a problem-dependent, working format cross-section library that can be used by KENO V.a. The analyst specifies the input resonance data based on the available options. The options include (1) a homogeneous medium treatment that treats the resonance region of the fissile mixture as if it were an infinite homogeneous media and (2) a finite lump treatment that treats the resonance region as if the fissile mixture were a discrete lump with a $1/E$ return flux at the boundary. This latter option is for problems where the system is substantially heterogeneous or where reflector effects are important. These options are automatically invoked in the CSAS25 control sequence according to the keywords INFHOMMEDIUM, LATTICECELL, or MULTIREGION. The INFHOMMEDIUM option treats the fissile mixture as an infinite homogeneous medium. The LATTICECELL option uses a multiple repeated cell for the resonance self-shielding correction. With the MULTIREGION option, a single-cell resonance self-shielding calculation is made.

Several modifications have been made to NITAWL-S. These include the addition of the ability to more accurately treat annular geometry and the ability to read and use the new AMPX¹² master-format libraries. Previous AMPX master libraries had the resonance region cross sections referenced to background cross sections such that the contribution from the resonances calculated by NITAWL was added to the background to obtain the shielded values. In the SCALE 4.0 AMPX master-format libraries, the cross sections are referenced to infinite dilution cross sections so the contribution from the resonances calculated by NITAWL is subtracted from the infinite dilution values to obtain the shielded values. This change was made to decouple the resonance region cross-section reconstruction from the codes used to generate the cross-section data (in this case, XLACS¹³). As a result of these changes, a larger correction is required for pure uranium metal systems than for dilute uranium mixtures. The NITAWL annular treatment is discussed in Sect. 2.1.

2.4 KENO V.a (VERSION 1.5)

KENO V.a is a multigroup Monte Carlo code used to determine k_{eff} . KENO V.a is a substantial revision of KENO IV and includes an enhanced geometry package that allows modeling of a wide variety of complex three-dimensional (3-D) geometries. The geometry package allows nested arrays and "holes" to be placed in the geometry model. The code permits the use of reflector options, including mirror reflection, differential albedo reflection, and an automatic reflector; the latter has the capability of using reflector region-weighting functions that are based on one-dimensional (1-D) adjoint calculations. The reflector options simplify geometry data input and/or reduce the running time of a specific problem. Cross-section input and atom-density input are handled by the CSAS25 module. Most of the major KENO parameters have defaults that work for a wide variety of problems, but can be overridden if the problem or analyst dictates.

There have been many minor changes to the KENO V.a code, most of which are invisible to the user. When a code problem arises in KENO, the run typically terminates. Several changes to the data checking performed by KENO and to program logic involved in the treatment of computer round-off error during tracking have been made.

Changes have also been made in the manner in which KENO handles inadequate Legendre transfer cross-section expansions. Inadequate Legendre expansions may be caused by a number of problems including poor cross-section data, inadequate or incompatible processing of the base data, and/or roundoff of the data. When inadequate Legendre expansions are encountered by KENO, they are corrected by the smallest amount required to make them usable.

2.5 THE 27-GROUP NEUTRON CROSS-SECTION LIBRARY

(Rev. 2 created January 27, 1989, updated October 12, 1989)

The 27-group ENDF/B-IV master cross-section library¹⁴ in SCALE is activated in the CSAS25 control sequence by specifying 27GROUPNDF4 (27GR) as the cross-section library name. The 27-group library is the broad-group companion library to the 218-group Criticality Safety Reference Library. The Criticality Safety Reference Library master library, which is based on ENDF/B-IV data, was generated as a pseudo-problem-independent fine-group structure library for use in general criticality safety analysis and shipping cask calculations. The 27-group library was collapsed from the 218-group library using a characteristic fission-(1/E)-Maxwellian spectral flux shape. Explicit ENDF/B-IV resonance parameters are carried for resonance nuclides in both the 27-group and 218-group master libraries. These resonance parameters are used by NITAWL-S in

the CSAS25 control sequence for calculating problem-dependent, self-shielded resonance region cross sections.

The original 27-group library was processed into the new AMPX master-library format using CORECTOL.¹⁵ In addition, all SCALE-4.0 nuclides were processed with PERFUME.¹⁶ The cross sections distributed with SCALE 4.0 are not compatible with previous versions of SCALE.

3. CALCULATIONAL PROCEDURE

In the KENO V.a validation process, many of the available options in CSAS25 and KENO V.a were exercised. These options include the automatic atomic density generation features, the various treatments in NITAWL, and the geometry and reflector options in KENO V.a. This procedure was followed in order to validate the mechanics and capabilities of the code for a broad spectrum of problems. The majority of the calculations repeat calculations that were modeled by different people at different times. Usually there are multiple ways that a problem may be specified, all of which are equally correct. The original input data were left substantially unchanged in order to allow testing for discrepancies or bias that might have been caused by the differences in analysts' problem specifications. A complete listing of the input data has been included in Appendix A.

The resonance treatment used was the one that appeared to most accurately fit the problem specifications. All problems were run for 103 generations of 600 neutrons per generation. Some problems were run using the adjoint reflector weighting (bias ID), whereas others were run using full neutron tracking in the reflector in order to test for bias which might be caused by one or the other treatment.

With KENO V.a, there is no single k_{eff} that is "the answer" for the problem. The code starts with an initial neutron distribution and calculates the effective multiplication for a generation of neutrons. The next generation uses a starting distribution based on the fission points of the previous generation and calculates the effective multiplication for the current generation. Because 103 generations were run, there are 103 different answers. In the ideal situation, once the source has converged and the original (and usually arbitrary) starting distribution has decayed, the difference in the batch-to-batch k_{eff} may be attributed to the statistical nature of the Monte Carlo calculation, and the "best" answer should be the average of the remaining calculations. The common practice in KENO V.a is to tabulate the average k_{eff} as a function of the number of generations skipped. Considerable judgment is then required in determining the answer. Many calculations do not approach the ideal situation. For example, undersampling may exist where the number of neutrons per generation is not sufficient to sustain a proper source distribution, or the number of generations is insufficient to converge the source distribution. In order to remove the element of judgment from the interpretation of the results and to mechanize the process of validating and comparing results with previous validation, the average k_{eff} by generation skipped with the lowest calculated standard deviation is reported here. This number appears in the plot of average k_{eff} by generation skipped in the KENO V.a output.

In each calculation, the optional parameter NTR was set to "yes" in KENO V.a, so the program would calculate and print the average energy group of the neutron-causing fission. This parameter has been frequently used in past validations because of trends that have been observed and appear to be correlated.

4. PROBLEM DESCRIPTION AND RESULTS

A brief problem description and results are presented in Tables 1 and 2. The majority of the models used in this validation were taken from ORNL/CSD/TM-238. The descriptions in Tables 1 and 2 are organized in a manner to refer back to the tables in ref. 5.

The experiments analyzed were chosen to validate KENO V.a in SCALE 4.0 for low-enriched uranium systems similar to those encountered at the GDP and in the proposed AVLIS facility.

The experiments described in Table I, Section A, are 4.89% ^{235}U enriched uranium systems from Table 1 in ref. 5. The descriptions of the models for the 4.89% uranium metal rod experiments were obtained from the original data notebooks. Geometries modeled include single-unit spheres and slabs and arrays of cylinders. The fissile compounds considered were UO_2F_2 , U metal, and U_3O_8 . Moderating materials were water, sterotex, and UO_2F_2 solution.

The experimental models used to generate Table 1, Sect. B, are from low-enriched uranium experiments obtained from Table 2 in ref. 5. These experiments are formally undocumented experiments for 3.85% enriched uranium metal rods in water. The heterogeneous systems consist of large-diameter rods that are water moderated. In some cases, the rods have an internal hole which is also water moderated. The critical experiments were modeled in detail from descriptions in the experiment logbook. Extensive detail was included in these calculations in order to thoroughly test the KENO V.a geometry package.

Table 1, Sect. C, includes models from Table 3 in ref. 5 which were used for the validation of Y12CSG for the Oak Ridge Gaseous Diffusion Plant (ORGDP). The validation considered single-unit criticals, both reflected and unreflected, at several enrichments ranging from 1.4 to 4.98%. The first 14 experiments are UF_4 /paraffin-moderated systems and UO_2F_2 solution systems at various moderation levels. The last 10 experiments are 4.46% enriched damp-oxide experiments performed at Rocky Flats. These later experiments test the code's ability to handle both intermixed and interstitial moderation. Several of the damp oxide experiments, which were driven by highly enriched uranium systems, were added to the series.

Table 1, Sect. D, models were taken from ref. 6. These experiments are arrays of 2.459 wt % ^{235}U UO_2 fuel pins in array of arrays with borated water as the moderator. These experiments were chosen because (1) they test the ability of the codes and cross sections to calculate systems with a harder neutron spectrum and (2) they had exhibited a bias in the past.

Several highly enriched uranium experiments were included in the validation. These models, taken from Tables 4 and 5 in ref. 5, were included to check the code's ability to properly calculate resonance cross sections for low-moderated and unmoderated systems. Several deficiencies in the early implementation of NITAWL-II were discovered when calculating highly enriched systems. The deficiencies were related to correcting infinite dilute cross sections ($\sigma_p = \infty$) to near pure material values ($\sigma_p = \sigma_r$).

Table 1. KENO V.a calculated k_{eff} for experimentally critical low-enriched uranium systems

Case	Experimental description	Reference	$k_{\text{eff}} \pm \sigma$
A) Ref. 5, Table 1 cases			
CAA01	Experiment 1A. 401-4.89% U rods, 0.762-cm diam, 30-cm long, 1.3-cm pitch, H ₂ O moderated and reflected	17	0.9894 ± 0.0040
CAA04	Experiment 6A. 203-4.89% U rods, 0.762-cm diam, 30-cm long, 2.05-cm pitch, H ₂ O moderated and reflected	17	0.9893 ± 0.0032
CAA07	Experiment 23B. 400-4.89% U rods, 0.762-cm diam, 30-cm long, 1.3-cm pitch, H ₂ O moderated, H ₂ O top reflector, Plexiglas bottom reflector, Pb reflected 4 faces	17	0.9806 ± 0.0032
CAA12	Experiment 32S. 11 × 12 array of 4.89% U rods in ~300 g U/L UO ₂ F ₂ solution, 0.762-cm diam, 2.05-cm pitch, in 95.88-cm-diam tank	17	0.9793 ± 0.0025
CAA14	Experiment 36S. 9 × 10 array of 4.89% U rods in ~300 g U/L UO ₂ F ₂ solution, 0.762-cm-diam, 2.453-cm pitch, in 95.88-cm-diam tank	17	0.9893 ± 0.0032
CAA19	4.89% U ₃ O ₈ - Sterotex blocks, 55.5 g ²³⁵ U/L, unreflected	18	0.9913 ± 0.0037
CAA21	4.89% U ₃ O ₈ - Sterotex blocks, 22.1 g ²³⁵ U/L (H/X = 757.0), unreflected	18	0.9997 ± 0.0033
CAA25	4.89% U ₃ O ₈ - Sterotex blocks, 81.1 g ²³⁵ U/L (H/X = 396.7), paraffin top reflector, H ₂ O-reflected bottom and sides	18	0.9999 ± 0.0032
CAA27	4.89% U ₃ O ₈ - Sterotex blocks, 81.1 g ²³⁵ U/L (H/X = 146.8), paraffin top reflector, H ₂ O-reflected bottom and sides	18	0.9873 ± 0.0034
CAA29	4.89% U ₃ O ₈ - Sterotex blocks, 33.3 g ²³⁵ U/L (H/X = 504.1), paraffin top reflector, H ₂ O-reflected bottom and sides	18	0.9860 ± 0.0031
CAA33	4.89% UO ₂ F ₂ solution 24.04 g ²³⁵ U/L (H/X = 1002) in a 27.3-in.-diam aluminum sphere, unreflected	18	0.9916 ± 0.0024
CAA38	4.89% UO ₂ F ₂ solution 22.11 g ²³⁵ U/L (H/X = 991) in a 27.3-in.-diam aluminum sphere, H ₂ O reflected	18	1.0000 ± 0.0025

Table 1 (continued)

Case	Experimental description	Reference	$k_{\text{eff}} \pm \sigma$
B) Ref. 5, Table 2 cases			
CAB03	(EBJ.3X) lattice 8. 24-3.85% U rods, 7.2-in.-diam $\times$ 30-in.-long square lattice, 8.70 in. center to center, 75.0-cm water height	19	0.9925 ± 0.0024
CAB08	(EBJ.5X) lattice 9. 7-3.85% U rods, 7.2 in. diam $\times$ 30 in. long in triangular lattice, 8.20 in. center to center, 53.1 cm water height	19	0.9932 ± 0.0030
CAB11	(EBJ.9) lattice 6. 16-3.85% U rods, 7.2 in. OD $\times$ 2.6 in. ID $\times$ 30 in. long in square lattice, 8.70 in. center to center, 49.2 cm water height	19	1.0017 ± 0.0027
CAB15	(EBJ.13) lattice 9. 15-3.85% U rods, 2.5 in. diam $\times$ 30 in. long in square lattice, 3.25 in. center to center, 64.8 cm water height	19	1.0050 ± 0.0029
C) Ref. 5, Table 3 cases			
CAS04	An unreflected rectangular parallelepiped of homogeneous $\text{U}(1.4)\text{F}_4$ and paraffin with an $\text{H}/^{235}\text{U}$ atomic ratio of 421.8; 93.1 cm $\times$ 93.0 cm $\times$ 123.8 cm	20	0.9854 ± 0.0023
CAS06	An unreflected rectangular parallelepiped of homogeneous $\text{U}(1.4)\text{F}_4$ and paraffin with an $\text{H}/^{235}\text{U}$ atomic ratio of 421.8; 130.7 cm $\times$ 130.6 cm $\times$ 74.2 cm	20	0.9861 ± 0.0020
CAS11	A reflected rectangular parallelepiped of homogeneous $\text{U}(2)\text{F}_4$ and paraffin with an $\text{H}/^{235}\text{U}$ atomic ratio of 195.2; 56.22 cm $\times$ 56.22 cm $\times$ 112.88 cm, reflected with 15.2 cm of paraffin on top and sides and 15.2 cm of Plexiglas on the bottom	20	0.9945 ± 0.0027
CAS16	A reflected rectangular parallelepiped of homogeneous $\text{U}(2)\text{F}_4$ and paraffin with an $\text{H}/^{235}\text{U}$ atomic ratio of 495.9; 46.00 cm $\times$ 46.00 cm $\times$ 96.57 cm, reflected with 15.2 cm of paraffin on top and sides of 15.2 cm of Plexiglas on the bottom	21	0.9898 ± 0.0025
CAS17	A reflected rectangular parallelepiped of homogeneous $\text{U}(2)\text{F}_4$ and paraffin with an $\text{H}/^{235}\text{U}$ atomic ratio of 613.6; 56.32 cm $\times$ 61.29 cm $\times$ 54.08 cm, reflected with 15.2 cm of polyethylene on top and sides and 15.2 cm of Plexiglas on the bottom	21	0.9885 ± 0.0027

Table 1 (continued)

Case	Experimental description	Reference	$k_{\text{eff}} \pm \sigma$
CAS21	A reflected rectangular parallelepiped of homogeneous $\text{U}(3)\text{F}_4$ and paraffin with an $\text{H}/^{235}\text{U}$ atomic ratio of 133.4; 51.14 cm $\times$ 51.14 cm $\times$ 51.27 cm, reflected with 15.2 cm of paraffin on top and sides and 15.2 cm of Plexiglas on the bottom	21	1.0066 ± 0.0031
CAS23	A reflected rectangular parallelepiped of homogeneous $\text{U}(3)\text{F}_4$ and paraffin with an $\text{H}/^{235}\text{U}$ atomic ratio of 133.4; 46.02 cm $\times$ 46.02 cm $\times$ 67.57 cm, reflected with 15.2 cm of paraffin on top and sides and 15.2 cm of Plexiglas on the bottom	21	1.0124 ± 0.0032
CAS26	An unreflected rectangular parallelepiped of homogeneous $\text{U}(3)\text{F}_4$ and paraffin with an $\text{H}/^{235}\text{U}$ atomic ratio of 133.4; 56.47 cm $\times$ 56.47 cm $\times$ 86.64 cm	21	1.0072 ± 0.0028
CAS29	A reflected rectangular parallelepiped of homogeneous $\text{U}(3)\text{F}_4$ and paraffin with an $\text{H}/^{235}\text{U}$ atomic ratio of 276.9; 40.81 cm $\times$ 40.80 cm $\times$ 39.49 cm, reflected with 15.2 cm of polyethylene on top and sides and 15.2 cm of Plexiglas on the bottom	21	1.0070 ± 0.0032
CAS31	An unreflected rectangular parallelepiped of homogeneous $\text{U}(3)\text{F}_4$ and paraffin with an $\text{H}/^{235}\text{U}$ atomic ratio of 276.9; 48.59 cm $\times$ 51.14 cm $\times$ 48.53 cm	21	1.0043 ± 0.0029
CAS33	A composite cadmium/steel/water side reflected stainless steel cylinder of 0.079-cm wall thickness and 19.545-cm IR filled to a height of 54.45 cm with $\text{U}(4.98)\text{O}_2\text{F}_2$ solution at an $\text{H}/^{235}\text{U}$ atomic ratio of 488	22	0.9934 ± 0.0028
CAS34	A composite 1-in. steel/water side reflected steel cylinder of 0.079-cm wall thickness and 16.51-cm IR filled to a height of 143 cm with $\text{U}(4.98)\text{O}_2\text{F}_2$ solution at an $\text{H}/^{235}\text{U}$ atomic ratio of 488	22	0.9915 ± 0.0031
CAS36	An unreflected stainless steel cylinder of 0.07874 cm wall thickness and a 19.55-cm IR filled to a height of 101.7 cm with $\text{U}(4.98)\text{O}_2\text{F}_2$ solution at an $\text{H}/^{235}\text{U}$ atomic ratio of 496	23	0.9955 ± 0.0032
CAR01	Experiment 1. 4.46% enriched U_3O_8 , $\text{H}/\text{U} = 0.77$, 42 fuel cans with 2.44 cm interstitial moderation, plastic reflected	24	1.0126 ± 0.0031

Table 1 (continued)

Case	Experimental description	Reference	$k_{\text{eff}} \pm \sigma$
CAR04	Experiment 13. 4.46%-enriched U_3O_8 , $\text{H}/\text{U} = 0.77$, 40 fuel cans with 2.44-cm interstitial moderation, concrete reflected	24	1.0116 ± 0.0032
CAR07	4.46%-enriched U_3O_8 , $\text{H}/\text{U} = 0.77$, driven by high concentration (14.844 kg 351.18 g/L) fuel cans, plastic reflected	25	1.0158 ± 0.0037
CAR08	4.46%-enriched U_3O_8 , $\text{H}/\text{U} = 0.77$, driven by low concentration (12.871 kg 86.42 g/L) 93.17% enriched $\text{UO}_2(\text{NO}_3)_2$, 119 + 2S fuel cans, plastic reflected	25	1.0017 ± 0.0035
CAR11	Experiment A. 4.46%-enriched U_3O_8 $\text{H}/\text{U} = 1.25$, 38 fuel cans with 2.44-cm interstitial moderation, plastic reflected	26	1.0070 ± 0.0033
CAR13	Experiment C. 4.46%-enriched U_3O_8 $\text{H}/\text{U} = 1.25$, 80 fuel cans with 0.929-cm interstitial moderation, plastic reflected	26	1.0081 ± 0.0030
CAR15	4.46%-enriched U_3O_8 $\text{H}/\text{U} = 1.25$, driven by high concentration (12.400 kg 351.65 gU/L), 93.17% enriched $\text{UO}_2(\text{NO}_3)_2$, 119 + 2S fuel cans, plastic reflected	26	0.9995 ± 0.0030
CAR16	4.46%-enriched U_3O_8 $\text{H}/\text{U} = 1.25$, driven by low concentration (10.836 kg p 86.60 gU/L), 93.17% enriched $\text{UO}_2(\text{NO}_3)_2$, 119 + 2S fuel cans, plastic reflected	26	1.0090 ± 0.0034
CAR18	Experiment G. 4.46%-enriched U_3O_8 $\text{H}/\text{U} = 2.03$, 30 fuel cans with 2.44-cm interstitial moderation, plastic reflected	27	1.0087 ± 0.0031
CAR20	Experiment E. 4.46%-enriched U_3O_8 $\text{H}/\text{U} = 2.03$, driven by 93.12% enriched hollow uranium metal sphere (12.786 kg), 120 + 4S fuel cans, plastic reflected	27	1.0036 ± 0.0026

Table 1 (continued)

Case	Experimental description	Reference	$k_{\text{eff}} \pm \sigma$
D) Ref. 6			
CLT01	BAW-1645-4 Exp. 2452, 2.459%-enriched UO_2 pins in triangular-pitched lattice, 1.86-cm pitch, 435 ppm boron	6	0.9830 ± 0.0035
CLT02	BAW-1645-4 Exp. 2457, 2.439%-enriched UO_2 pins in triangular-pitched lattice, 1.86-cm pitch, 335 ppm boron	6	0.9772 ± 0.0038
CLT03	BAW-1645-4 Exp. 2464, 2.459%-enriched UO_2 pins in triangular-pitched lattice, 2.62-cm pitch, 361 ppm boron	6	0.9818 ± 0.0031
CLT04	BAW-1645-4 Exp. 2472, 2.459%-enriched UO_2 pins in triangular-pitched lattice, 3.39-cm pitch, 121 ppm boron	6	0.9968 ± 0.0043
CLT05	BAW-1645-4 Exp. 2485, 2.459%-enriched UO_2 pins in square-pitched lattice, 1.778-cm pitch, 886 ppm boron	6	0.9864 ± 0.0031
CLT06	BAW-1645-4 Exp. 2491, 2.459%-enriched UO_2 pins in square-pitched lattice, 1.778-cm pitch, 746 ppm boron	6	0.9873 ± 0.0034
CLT07	BAW-1645-4 Exp. 2500, 2.459%-enriched UO_2 pins in square open-pitched lattice, 1.792-cm pitch, 1156 ppm boron	6	1.0019 ± 0.0030
CLT08	BAW-1645-4 Exp. 2505, 2.459%-enriched UO_2 pins in square open-pitched lattice, 1.792-cm pitch, 1068 ppm boron	6	0.9928 ± 0.0037

Table 2. KENO V.a calculated k_{eff} for experimentally critical highly enriched uranium systems

Case	Experimental description	Reference	$k_{\text{eff}} \pm \sigma$
A) Ref. 5, Table 4 cases			
CAA14	U(93.2)O ₂ (NO ₃) ₂ solution 54.89 g U/L, 33.01-cm-diam cylinder, unreflected	28	1.0141 $\pm$ 0.0039
B) Ref. 5, Table 5 cases			
CAS02	Y-12 validation case A-10. 97.67% U metal sphere, H ₂ O reflected	29	1.0114 $\pm$ 0.0031
CAS06	Y-12 validation case A-4. 93.18% UO ₂ (NO ₃) ₂ solution, 20.12 g U/L, in Al sphere, unreflected	30	1.0162 $\pm$ 0.0022
CAS07	Y-12 validation case A-5. 93.5% U metal hemispherical shell, H ₂ O reflected	31	1.0140 $\pm$ 0.0031
CAS11	Y-12 validation case A-9. 93.1% U metal hemispherical shell, steel center and oil reflected	32	0.9956 $\pm$ 0.0032
CAS18	Y-12 validation case B-15. 92.6% UO ₂ (NO ₃) ₂ solution, 415 g U/L, in Plexiglas cylinders, 3 $\times$ 3 $\times$ 3 array, Plexiglas reflected (see also problem U4R27G1F)	33	1.0080 $\pm$ 0.0040
CAS28	Y-12 validation case B-8. 93.2% U metal cylinders each in a Plexiglas box, 2 $\times$ 2 $\times$ 2 array of these units unreflected	34	1.0133 $\pm$ 0.0031
CAS32	Problem S333SP1. 93.2% UO ₂ F ₂ solution, 81.8 g U/L, in Al slabs, 3 7.62-cm slabs in 3 $\times$ 1 array, 2.54-cm separation, unreflected, cylindrical tank, floor, and walls in experiment room included	35	0.9731 $\pm$ 0.0034
CAS52	Problem S63SP6. 93.2% UO ₂ F ₂ solution, 81.8 g U/L, in Al slabs. One slab is made up from two 7.62-cm slabs snugly fit together, the other is 7.62 cm, 2 $\times$ 1 array, 15.24-cm separation, unreflected	35	0.9883 $\pm$ 0.0036
CAS60	Problem U2B271F. 92.6% UO ₂ (NO ₃) ₂ solution, 279 g U/L, in Plexiglas cylinders, 3 $\times$ 3 $\times$ 3 array, unreflected, walls, floor, and tank in experiment room included	33	1.0027 $\pm$ 0.0044
CAS74	Problem U4R27I1F. 92.6% UO ₂ (NO ₃) ₂ solution, 415 g U/L, in Plexiglas cylinders, 3 $\times$ 3 $\times$ 3 array, reflected, 15.24-cm paraffin all faces	33	1.0254 $\pm$ 0.0044

5. DISCUSSION AND CONCLUSIONS

The experiments modeled were parameterized such that a trend analysis could be performed. Table B.1 (Appendix B) is a relisting of the calculated results of the validation experiments. The mean k_{eff} and standard deviation for the calculations are presented in Table 3, treating the data for low-enriched and highly enriched experiments separately and combined. The mean value of k_{eff} is in excellent agreement with the experiments.

Table 3. Average k_{eff}

	N	Mean	Standard deviation	Minimum value	Maximum value
Low enriched (from Table 1)	48	0.99628	0.00993	0.9772	1.0158
Highly enriched (from Table 2)	11	1.0043	0.01447	0.9731	1.0254
Combined	59	0.99778	0.01224	0.9731	1.0254

The combined data were tested for correlation of variability to k_{eff} . The results indicate that k_{eff} is correlated to the average energy group causing fission (AEG) and to the class-variable FUEL. The variation of k_{eff} with AEG is not as large if the data are separated into low-enriched and highly enriched calculations. It is thought that the variation of calculated k_{eff} as a function of fuel type is related to the same factors that contribute to the variation of k_{eff} with AEG.

Figures 1 and 2 present scatter plots of k_{eff} as a function of AEG for low-enriched calculations, and low-enriched and highly enriched combined. Also presented in the figures are a linear-least-squares fit through the data, a linear uniform width band that encompasses the 95% confidence band for a single future calculation, and the 95% closed interval, uniform-width lower tolerance band on 99.9% proportion of the population.

For these figures, the "bias" is defined as the difference between the least-squares fit and a $k_{eff} = 1.0$ for the critical experiments. The general trend is that there is a positive bias of about 0.8% for the lowest AEG, decreasing to a negative bias of about 0.5% at the highest AEG.

The bias observed is consistent with two factors that affect calculations performed with 27-group ENDF/B-IV library in SCALE: (1) the unresolved resonance region cross sections for ^{235}U and ^{238}U were processed at a $\sigma_p = 50,000$; and (2) few groups are in the fast range of the 27-group library. The effect of the fixed unresolved resonance region cross sections is that resonance fission for ^{235}U is too high and resonance absorption for ^{238}U is too high. The positive bias at low AEG can be attributed, in part, to few fast groups and an overestimation of ^{235}U fission for the highly enriched systems. The effect of few fast groups is that the cross sections are not independent of the collapsing spectrum used to generate them and this spectrum is not optimal for all systems. Other factors that may contribute to the observed bias include inadequacies in the base data for ENDF/B-IV cross sections.

Fig. 1. k_{eff} vs AEG low-enriched experiments

Fig. 2. k_{eff} vs AEG high- and low-enriched experiments.

The negative bias at high AEG may be attributed, in part, to few fast groups and over-estimation of the ^{238}U unresolved resonance region capture for the low-enriched systems. Not all low-enriched systems are sensitive to the unresolved resonance region cross sections. Systems that are more likely to be sensitive are undermoderated lattices and poisoned systems. The experiments in Table 1, Sect. D, exhibit a sensitivity to the unresolved resonance region processing. These are low-enriched UO_2 fuel-pin-lattice experiments performed by Babcock and Wilcox Company³⁶ (B&W) as modeled in ref. 6. A comparison of the validation results for these experiments with ref. 6 indicates that SCALE 4.0 calculates about 0.5% higher than previous versions of SCALE. This is attributed to the modifications made to the code system to more correctly treat annular geometry.

The linear uniform-width band that encompasses the 95% confidence band on a single future calculation may be interpreted as the k_{eff} value that, for a critical system similar to those validated, one would calculate above for a single future estimate of k_{eff} at 95% confidence. Any calculated k_{eff} above this band is considered critical.

The 95% closed-interval, uniform-width, lower tolerance band on 99.9% proportion of the population is used as the calculation acceptance criteria. The values of k_{eff} represented by this band may be interpreted as the k_{eff} value that, for a critical system similar to those validated, one would expect to calculate above for 99.9% of the estimates of k_{eff} at 95% confidence. Any calculated k_{eff} below this band is considered to be of the group of systems that is not critical. The difference between the two confidence bands is taken to be the margin of calculated subcriticality. For the low-enriched systems, this margin is $0.0298 \Delta k$.

Based on the results of the validation and on the statistical analysis of the data for low-enriched uranium systems, a calculated k_{eff} , including the uncertainty in k_{eff} ($k_{\text{eff}} + 2\sigma$), that is less than 0.945 may be considered safely subcritical for systems similar to those validated, and provided the AEG is within the range from about 15.5 to 24.75. The calculational limit may be increased slightly at lower values of AEG, as indicated in Fig. 1.

REFERENCES

1. L. M. Petrie and N. F. Landers, "KENO V.a: An Improved Monte Carlo Criticality Program with Supergrouping," Sect. F11 of *SCALE: A Modular Code System for Performing Standardized Computer Analyses for Licensing Evaluation*, NUREG/CR-0200, Rev. 4 (ORNL/NUREG/CSD-2/R4), Vols. 1, 2, and 3 (draft February 1990). Available from Radiation Shielding Information Center as CCC-545.
2. *SCALE: A Modular Code System for Performing Standardized Computer Analyses for Licensing Evaluation*, NUREG/CR-0200, Rev. 4 (ORNL/NUREG/CSD-2/R4), Vols. 1, 2, and 3 (draft February 1990). Available from Radiation Shielding Information Center as CCC-545.
3. N. F. Landers and L. M. Petrie, "CSAS4: An Enhanced Criticality Safety Analysis Module with an Optimum Pitch Search Option," Sect. C4 of *SCALE: A Modular Code System for Performing Standardized Computer Analyses for Licensing Evaluation*, NUREG/CR-0200, Rev. 4 (ORNL/NUREG/CSD-2/R4), Vols. 1, 2, and 3 (draft February 1990). Available from Radiation Shielding Information Center as CCC-545.
4. H. R. Dyer et al., *A Technique for Code Validation for Criticality Calculations*, TANSO 63-1-464, p. 238, 1991.
5. W. C. Jordan, N. F. Landers, and L. M. Petrie, *Validation of KENO V.a Comparison with Critical Experiments*, ORNL/CSD/TM-238, Martin Marietta Energy Systems, Inc., Oak Ridge Natl. Lab., December 1986.
6. H. R. Dyer and R. M. Westfall, *KENO V.a Validation of Fuel Pin Experiments*, TANSO 55-1-760, p. 382, 1987.
7. S. M. Bowman, *Configuration Management Plan for the SCALE Code System*, SCALE-CMP-001, Rev. 1, ORNL Internal Report issued by Nuclear Engineering Applications Department of Computing and Telecommunications Division, Oak Ridge National Laboratory, September 1990.
8. J. R. Knight, L. M. Petrie, and C. V. Parks, "Standard Composition Library," Sect. M8 of *SCALE: A Modular Code System for Performing Standardized Computer Analyses for Licensing Evaluation*, NUREG/CR-0200, Rev. 4 (ORNL/NUREG/CSD-2/R4), Vols. 1, 2, and 3 (draft February 1990). Available from Radiation Shielding Information Center as CCC-545.
9. N. F. Landers, L. M. Petrie, and J. A. Bucholz, "The Material Information Processor for SCALE," Sect. M7 of *SCALE: A Modular Code System for Performing Standardized Computer Analyses for Licensing Evaluation*, NUREG/CR-0200, Rev. 4 (ORNL/NUREG/CSD-2/R4), Vols. 1, 2, and 3 (draft February 1990). Available from Radiation Shielding Information Center as CCC-545.

10. N. M. Greene, "BONAMI-S: Resonance Self-Shielding by the Bondarenko Method," Sect. F1 of *SCALE: A Modular Code System for Performing Standardized Computer Analyses for Licensing Evaluation*, NUREG/CR-0200, Rev. 4 (ORNL/NUREG/CSD-2/R4), Vols. 1, 2, and 3 (draft February 1990). Available from Radiation Shielding Information Center as CCC-545.
11. N. M. Greene, L. M. Petrie, and R. M. Westfall, "NITAWL-II: SCALE System Module for Performing Resonance Shielding and Working Library Production," Sect. F2 of *SCALE: A Modular Code System for Performing Standardized Computer Analyses for Licensing Evaluation*, NUREG/CR-0200, Rev. 4 (ORNL/NUREG/CSD-2/R4), Vols. 1, 2, and 3 (draft February 1990). Available from Radiation Shielding Information Center as CCC-545.
12. N. M. Greene, W. E. Ford, III, L. M. Petrie, and J. W. Arwood, *AMPX-77: A Modular Code System for Generating Coupled Multigroup Neutron-Gamma Cross-Section Libraries from ENDF/B-IV and/or ENDF/B-V*, ORNL/CSD/TM-283, Martin Marietta Energy Systems, Inc., Oak Ridge Natl. Lab., October 1992.
13. N. M. Greene et al., "3. XLACS — Module to Produce Group-Averaged Neutron Cross-Section Libraries on an AMPX Master Library," Section from *AMPX-77: A Modular Code System for Generating Coupled Multigroup Neutron-Gamma Cross-Section Libraries From ENDF/B-IV and/or ENDF/B-V*, ORNL/CSD/TM-283, Martin Marietta Energy Systems, Inc., Oak Ridge Natl. Lab. (to be published).
14. W. C. Jordan, "SCALE Cross-Section Libraries," Sect. M4 of *SCALE: A Modular Code System for Performing Standardized Computer Analyses for Licensing Evaluation*, NUREG/CR-0200, Rev. 4 (ORNL/NUREG/CSD-2/R4), Vols. 1, 2, and 3 (draft February 1990). Available from Radiation Shielding Information Center as CCC-545.
15. N. M. Greene et al., "3. CORECTOL — Module to Convert Pre-AMPX-77 Master Libraries to the AMPX-77 Form," Section from *AMPX-77: A Modular Code System for Generating Coupled Multigroup Neutron-Gamma Cross-Section Libraries From ENDF/B-IV and/or ENDF/B-V*, ORNL/CSD/TM-283, Martin Marietta Energy Systems, Inc., Oak Ridge Natl. Lab. (to be published).
16. N. M. Greene et al., "3. PERFUME — Module to Correct Legendre Polynomial Fits to Scattering Matrices," Section from *AMPX-77: A Modular Code System for Generating Coupled Multigroup Neutron-Gamma Cross-Section Libraries From ENDF/B-IV and/or ENDF/B-V*, ORNL/CSD/TM-283, Martin Marietta Energy Systems, Inc., Oak Ridge Natl. Lab. (to be published).
17. L. M. Petrie and J. T. Thomas, *Assessment of Computational Performance in Nuclear Criticality*, ORNL/CSD/TM-224, Martin Marietta Energy Systems, Inc., Oak Ridge Natl. Lab., January 1985.
18. D. F. Cronin, *Critical Mass Studies, Part X*, ORNL-2968, Union Carbide Corp., Nucl. Div., Oak Ridge Natl. Lab., 1960.

19. E. B. Johnson, *The Criticality of Large Uranium Metal Units of Low Enrichment in U-235*, ORNL-6310, Martin Marietta Energy Systems, Inc., Oak Ridge Natl. Lab. (to be published).
20. F. Abbey, comp., *Handbook of Experimental Criticality Data*, AHSB(s) Handbook 5, 1968.
21. S. J. Raffety and J. T. Mihalczo, *Homogenized Critical Assemblies of 2 and 3% Enriched Uranium in Paraffin*, Y-DR-14, Union Carbide Corp., Nucl. Div., Oak Ridge Y-12 Plant, 1969.
22. E. B. Johnson, "Effect of Steel-Water Reflectors on the Criticality of Low Enriched Uranyl Fluoride Solution," p. 47 in *Neutron Physics Division Annual Progress Report for Period Ending May 31, 1968*, ORNL-4280, Union Carbide Corp., Nucl. Div., Oak Ridge Natl. Lab., 1968.
23. J. W. Webster and E. B. Johnson, *Criticality of a Single Unit of Aqueous Uranyl Fluoride Solution Enriched to 5% in U-235*, ORNL/TM-1195, Union Carbide Corp., Nucl. Div., Oak Ridge Natl. Lab., 1965.
24. R. E. Rothe et al., *Critical Experiments with Interstitially Moderated Arrays of Low Enriched Uranium Oxide*, NUREG/CR-1071, RFP-3008, U.S. Nuclear Regulatory Commission, 1980.
25. G. Tuck and I. Oh, *Benchmark Critical Experiments on Low Enriched Uranium Oxide Systems with H/U = 0.77*, NUREG/CR-0674, U.S. Nuclear Regulatory Commission, 1979.
26. G. R. Goebel et al., *Critical Experiments on Low-Enriched Uranium Oxide Systems with H/U = 1.25*, NUREG/CR-1653, RFP-3129, U.S. Nuclear Regulatory Commission, 1980.
27. R. E. Rothe and G. R. Goebel, *Critical Experiments on Low-Enriched Uranium Oxide Systems with H/U = 2.03*, NUREG/CR-2500, RFP-3277, U.S. Nuclear Regulatory Commission, 1982.
28. R. E. Rothe, *Benchmark Critical Experiments on High Enriched Uranyl Nitrate Solution Systems*, NUREG/CR-0041, RFP-2710, U.S. Nuclear Regulatory Commission, 1978.
29. C. C. Byers, J. J. Koelling, G. E. Hansen, D. R. Smith, and H. R. Dyer, "Critical Measurements of a Water-Reflected Enriched Uranium Sphere," *Trans. Am. Nucl. Soc.* **27**, 412 (1977).
30. R. Gwin and D. W. Magnuson, *Nucl. Sci. Eng.* **12**, 364 (1962).
31. H. C. Paxton, *Los Alamos Critical Mass Data*, LAMS-3067, Los Alamos National Laboratory, Los Alamos, New Mexico, 1964.
32. G. Tuck, "Critical Masses of Spherical and Hemispherical Enriched Uranium Assemblies," *J. Nucl. Energy* **23**, 663 (1969).

33. J. T. Thomas, *Critical Three-Dimensional Arrays of Neutron-Interacting Units*, ORNL/TM-719, Union Carbide Corp., Nucl. Div., Oak Ridge Natl. Lab., 1963.
34. J. T. Thomas, *Critical Three-Dimensional Arrays of Neutron-Interacting Units, Part II - U(93.2) Metal*, ORNL/TM-868, Union Carbide Corp., Nucl. Div., Oak Ridge Natl. Lab., 1964.
35. J. K. Fox and L. W. Gilley, *Preliminary Report of Critical Experiments in Slab Geometry*, ORNL/CF-56-7-148, Union Carbide Corp., Nucl. Div., Oak Ridge Natl. Lab., 1956.
36. G. S. Hoovler et al., *Critical Experiments Supporting Underwater Storage of Lightly Packed Configurations of Spent Fuel Pins*, BAW-1645-4, Babcock and Wilcox Company, 1981.

APPENDIX A. CSAS25 INPUT DATA USE FOR VALIDATION

```

VALIDATION CASE (CAA01 )
=CSAS25
LIBBY EXP. 4.89% RODS 30 CM LONG, .762 CM DIAM, 1.3 CM PITCH
27GROUPNDF4 LATTICECELL
URANIUM 1 .9995 293 92235 4.89 92238 95.11 END
H2O 2 1 END
PLEXIGLASS 3 1 END
END COMP
SQUAREPITCH 1.3 .762 1 2 END
LIBBY EXP. 4.89% RODS 30 CM LONG, .762CM DIAM, 1.3CM PITCH
READ PARAM NPG=600 NUB=YES FDN=YES END PARAM
READ GEOM
UNIT 1
CYLINDER 1 1 .381 5.08 0
CUBOID 2 1 4P.65 5.08 0
UNIT 2
CYLINDER 1 1 .381 1.27 0
CUBOID 3 1 4P.65 1.27 0
UNIT 3
CYLINDER 1 1 .381 17.935 0
CUBOID 2 1 4P.65 17.935 0
UNIT 4
CYLINDER 1 1 .381 .635 0
CUBOID 3 1 4P.65 .635 0
UNIT 5
CUBOID 2 1 4P.65 5.08 0
UNIT 6
CYLINDER 2 1 .381 1.27 0
CUBOID 3 1 4P.65 1.27 0
UNIT 7
CUBOID 2 1 4P.65 17.935 0
UNIT 8
CYLINDER 2 1 .381 .635 0
CUBOID 3 1 4P.65 .635 0
CORE 0 1 3R0
REFLECTOR 3 1 5R0 3.81 1
REFLECTOR 2 2 5R3 0 1
REFLECTOR 2 3 5R3 2 19 1
REFLECTOR 2 4 4R3 3.2 3 1
REFLECTOR 2 5 4R3 0 3 2
END GEOM
READ ARRAY NUX=20 NUY=21 NUZ=5 FILL
19R5 401R1 19R6 401R2 19R7 401R3 19R8 401R4 19R5 401R1
END FILL END ARRAY
READ BIAS ID=500 2 6 END BIAS
END DATA
END

```

```

VALIDATION CASE (CAA04 )
=CSAS25
LIBBY EXP. 4.89% RODS 30 CM LONG, .762 CM DIAM, 2.05 CM PITCH
27GROUPNDF4 LATTICECELL
URANIUM 1 .9995 293 92235 4.89 92238 95.11 END
H2O 2 1 END
PLEXIGLASS 3 1 END
END COMP
SQUAREPITCH 2.05 .762 1 2 END
LIBBY H2O REFL. CASE 6A
READ PARAM NPG=600 NUB=YES FDN=YES END PARAM
READ GEOM
UNIT 1
CYLINDER 1 1 .381 30 0
CUBOID 2 1 4P1.025 30 0
UNIT 2
CUBOID 2 1 4P1.025 30 0
CORE 0 1 3R0
REFLECTOR 2 2 6R3 3
REFLECTOR 2 5 4R3 .3 3 1
REFLECTOR 2 6 4R3 0 3 1
END GEOM
READ ARRAY NUX=14 NUY=15 NUZ=1 FILL
7R1 7R2 F1
END FILL END ARRAY
READ BIAS ID=500 2 6 END BIAS
END DATA
END

```

VALIDATION CASE (CAA07)
 =CSAS25
 LIBBY EXP. 4.89% RODS 30 CM LONG, .762 CM DIAM, 1.3 CM PITCH
 27GROUPNDF4 LATTICECELL
 URANIUM 1 .9995 293 92235 4.89 92238 95.11 END
 H2O 2 1 END
 PLEXIGLASS 3 1 END
 PB 4 1 END
 END COMP
 SQUAREPITCH 1.3 .762 1 2 END
 LIBBY H2O REFL. CASE 238 PB 4 FACES
 READ PARAM NPG=600 NUB=YES PLT=NO FDN=YES END PARAM
 READ GEOM
 UNIT 1
 CYLINDER 1 1 .381 27 0
 CUBOID 2 1 4P.65 27 0
 UNIT 2
 CUBOID 2 1 4P.65 27 0
 UNIT 7
 CYLINDER 1 1 .381 3 0
 CUBOID 0 1 4P.65 3 0
 UNIT 8
 CUBOID 0 1 4P.65 3 0
 UNIT 3
 ARRAY 1 3R0
 REFLECTOR 2 1 4R3.221 2R0 1
 UNIT 9
 ARRAY 4 3R0
 REFLECTOR 0 1 4R3.221 2R0 1
 UNIT 10
 ARRAY 5 3R0
 UNIT 4
 CUBOID 4 1 2P10.16 2P16.871 25.4 0
 REFLECTOR 0 1 4R0 1.425 0 1
 REFLECTOR 3 2 5R0 3.175 1
 UNIT 5
 ARRAY 2 3R0
 UNIT 6
 CUBOID 4 1 2P37.191 2P10.16 25.4 0
 REFLECTOR 0 1 4R0 1.425 0 1
 REFLECTOR 3 2 5R0 3.175 1
 ARRAY 3 3R0
 REFLECTOR 3 2 5R0 3 4
 REFLECTOR 3 6 5R0 1.97 1
 END GEOM
 READ ARRAY ARA=1 NUX=21 NUY=21 NUZ=1 FILL
 10R1 2 10R1 9Q21 21R2 10R1 2 10R1 9Q21
 END FILL
 ARA=4 NUX=21 NUY=21 NUZ=1 FILL
 10R7 8 10R7 9Q21 21R8 10R7 8 10R7 9Q21
 END FILL
 ARA=2 NUX=3 NUY=1 NUZ=1 FILL 4 10 4 END FILL
 ARA=3 NUX=1 NUY=3 NUZ=1 FILL 6 5 6
 END FILL
 ARA=5 NUX=1 NUY=1 NUZ=2 FILL 3 9
 END FILL END ARRAY
 READ BIAS ID=500 2 6 END BIAS
 READ PLOT TTL='X-Y' PIC=MIX
 XUL=0 YUL=75 ZUL=15 XLR=75 YLR=0 ZLR=15
 UAX=1 VDN=-1 MAX=125 END
 TTL='X-Y' PIC=WTS END
 TTL='Y-Z' PIC=MIX
 XUL=33 YUL=0 ZUL=31 XLR=33 YLR=75 ZLR=-14.1
 VAX=1 WDN=-1 UAX=0 VDN=0 MAX=125 END
 TTL='Y-Z' PIC=WTS END
 END PLOT
 END DATA
 END

VALIDATION CASE (CAA12)
 =CSAS25
 LIBBY EXP. 4.89% RODS 30 CM LONG, .762 CM DIAM, 2.05 CM PITCH IN UO2F2 SOLN
 27GROUPNDF4 LATTICECELL
 URANIUM 1 .9995 293 92235 4.89 92238 95.11 END
 SOLNUO2F2 2 295.54 0 1 293 92235 4.89 92238 95.11 END
 PLEXIGLASS 3 1 END
 AL 4 1 END
 SOLNUO2F2 5 295.54 0 1 293 92235 4.89 92238 95.11 END
 END COMP
 SQUAREPITCH 2.05 .762 1 2 END
 LIBBY RODS IN UO2F2 SOLN CASE 32S
 READ PARAM NPG=600 NUB=YES FDN=YES END PARAM
 READ GEOM
 UNIT 1
 CYLINDER 1 1 .381 5.08 0
 CUBOID 5 1 4P1.025 5.08 0
 UNIT 2

```

CYLINDER 1 1 .381 1.27 0
CUBOID 3 1 4P1.025 1.27 0
UNIT 3
CYLINDER 1 1 .381 17.935 0
CUBOID 5 1 4P1.025 17.935 0
UNIT 4
CYLINDER 1 1 .381 .635 0
CUBOID 3 1 4P1.025 .635 0
UNIT 5
CUBOID 2 1 4P1.025 5.08 0
UNIT 6
CYLINDER 2 1 .381 1.27 0
CUBOID 3 1 4P1.025 1.27 0
UNIT 7
CUBOID 2 1 4P1.025 17.935 0
UNIT 8
CYLINDER 2 1 .381 .635 0
CUBOID 3 1 4P1.025 .635 0
CORE 0 1 -11.275 -12.3 0
REFLECTOR 3 1 5R0 3.81 1
CYLINDER 5 1 47.94 30.1 -7.4
CYLINDER 4 1 48.26 30.1 -7.72
END GEOM
READ ARRAY NUX=11 NUY=12 NUZ=5 FILL
132R1 132R2 132R3 132R4 132R1
END FILL END ARRAY
END DATA
END

```

```

VALIDATION CASE (CAA14 )
=CSAS25
LIBBY EXP. 4.89 RODS 30 CM LONG, .762 CM DIAM, 2.05 CM PITCH
27GROUPNDF4 LATTICECELL
URANIUM 1 .9995 293 92235 4.89 92238 95.11 END
H2O 2 1 END
PLEXIGLASS 3 1 END
END COMP
SQUAREPITCH 2.05 .762 1 2 END
LIBBY H2O REFL. CASE 6A
READ PARAM NPG=600 NUB=YES FDN=YES END PARAM
READ GEOM
UNIT 1
CYLINDER 1 1 .381 30 0
CUBOID 2 1 4P1.025 30 0
UNIT 2
CUBOID 2 1 4P1.025 30 0
CORE 0 1 3R0
REFLECTOR 2 2 6R3 3
REFLECTOR 2 5 4R3 .3 3 1
REFLECTOR 2 6 4R3 0 3 1
END GEOM
READ ARRAY NUX=14 NUY=15 NUZ=1 FILL
7R1 7R2 F1
END FILL END ARRAY
READ BIAS ID=500 2 6 END BIAS
END DATA
END

```

```

VALIDATION CASE (CAA19 )
=CSAS25
4.89% GREEN BLOCKS H/U-235=244.6 55.5G U-235/L
27GROUPNDF4 MULTIREGION
U-234 1 0 5.8000-7 END
U-235 1 0 1.4220-4 END
U-238 1 0 2.7302-3 END
H 1 0 3.4782-2 END
C 1 0 1.8023-2 END
O 1 0 9.5585-3 END
AL 2 1 END
END COMP
SPHERICAL END
1 28 NOEXTERMOD END ZONE
4.89% GREEN BLOCKS UNREFLECTED CASE 1
READ PARAM NPG=600 NUB=YES FDN=YES END PARAM
READ GEOM
UNIT 1
CUBE 1 1 2P10.16
UNIT 2
CUBOID 1 1 4P10.16 2P6.604
END GEOM
READ ARRAY NUX=3 NUY=3 NUZ=3 FILL 18R1 9R2 END FILL END ARRAY
END DATA
END

```

```

VALIDATION CASE (CAA21 )
=CSAS25
4.89% GREEN BLOCKS H/U-235=757.0 22.1 G U-235/L

```

```

27GROUPNDF4 MULTIREGION
U-234 1 0 2.3000-7 END
U-235 1 0 5.6624-5 END
U-238 1 0 1.0872-3 END
H 1 0 4.2864-2 END
C 1 0 2.2212-2 END
O 1 0 5.3889-3 END
AL 2 1 END
END COMP
SPHERICAL END
1 28 NOEXTERMOD END ZONE
4.89% GREEN BLOCKS UNREFLECTED CASE 3
READ PARAM NPG=600 NUB=YES FDN=YES END PARAM
READ GEOM
CUBOID 1 1 71.12 0 71.12 0 70.358 0
END GEOM
END DATA
END

```

```

VALIDATION CASE (CAA25 )
=CSAS25
4.89% GREEN BLOCKS H/U-235=396.7 40.6 G U-235/L
27GROUPNDF4 MULTIREGION
U-234 1 0 4.3000-7 END
U-235 1 0 1.0402-4 END
U-238 1 0 1.9972-3 END
H 1 0 4.1265-2 END
C 1 0 2.1383-2 END
O 1 0 7.8552-3 END
AL 2 1 END
H2O 3 1 END
PARA(H2O) 4 1 END
END COMP
SPHERICAL END
1 20 ONEEXTERMOD 3 38 NOEXTERMOD END ZONE
4.89% GREEN BLOCKS REFLECTED CASE 3
READ PARAM NPG=600 NUB=YES FDN=YES END PARAM
READ GEOM
CUBOID 1 1 40.64 0 40.64 0 57.658 0
REFLECTOR 4 8 4R0 3.048 0 5
REFLECTOR 3 2 4R3 0 3 6
END GEOM
READ BIAS ID=500 2 7 ID=400 8 12 END BIAS
END DATA
END

```

```

VALIDATION CASE (CAA27 )
=CSAS25
4.89% GREEN BLOCKS H/U-235=146.8 81.1 G U-235/L
27GROUPNDF4 MULTIREGION
U-234 1 0 8.5000-7 END
U-235 1 0 2.0779-4 END
U-238 1 0 3.9896-3 END
H 1 0 3.0504-2 END
C 1 0 1.5807-2 END
O 1 0 1.2859-2 END
AL 2 1 END
H2O 3 1 END
'ARAFFIN 4 1 END
PARA(H2O) 4 1 END
END COMP
SPHERICAL END
1 22 ONEEXTERMOD 3 40 NOEXTERMOD END ZONE
4.89% GREEN BLOCKS REFLECTED CASE 5
READ PARAM NPG=600 NUB=YES FDN=YES END PARAM
READ GEOM
CUBOID 1 1 50.8 0 50.8 0 42.164 0
REFLECTOR 4 8 4R0 3.048 0 5
REFLECTOR 3 2 4R3 0 3 6
END GEOM
READ BIAS ID=500 2 7 ID=400 8 12 END BIAS
END DATA
END

```

```

VALIDATION CASE (CAA29 )
=CSAS25
4.89% GREEN BLOCKS H/U-235=504.1 33.3 G U-235/L
27GROUPNDF4 MULTIREGION
U-234 1 0 3.5000-7 END
U-235 1 0 8.5320-5 END
U-238 1 0 1.6381-3 END
H 1 0 4.3010-2 END
C 1 0 2.2287-2 END
O 1 0 6.9427-3 END
AL 2 1 END
H2O 3 1 END
PARA(H2O) 4 1 END

```

```

END COMP
SPHERICAL END
1 29 ONEEXTERMOD 3 47 NOEXTERMOD END ZONE
4.89% GREEN BLOCKS REFLECTED CASE 7
READ PARAM NPG=600 NUB=YES FDN=YES END PARAM
READ GEOM
CUBOID 1 1 50.8 0 50.8 0 41.148 0
REFLECTOR 4 8 4R0 3.048 0 5
REFLECTOR 3 2 4R3 0 3 6
END GEOM
READ BIAS ID=500 2 7 ID=400 8 12 END BIAS
END DATA
END

```

VALIDATION CASE (CAA33)

```

=CSAS25
4.89% UO2F2 H/U-235=1002
27GROUPNDF4 MULTIREGION
SOLNUO2F2 1 491.6 0 1 293 92234 .02 92235 4.89
92238 95.09 END
AL 2 1 END

```

```

END COMP
SPHERICAL END
1 34.6 NOEXTERMOD 2 34.76 NOEXTERMOD END ZONE
4.89% UO2F2 27.3 IN DIAM AL SPHERE BARE 4
READ PARAM NPG=600 NUB=YES FDN=YES END PARAM
READ GEOM
HEMISPHE-Z 1 1 34.6 CHORD 30.
SPHERE 0 1 34.6
SPHERE 2 1 34.759
END GEOM
END DATA
END

```

VALIDATION CASE (CAA38)

```

=CSAS25
4.89% UO2F2 H/U-235=1099
27GROUPNDF4 MULTIREGION
SOLNUO2F2 1 452.1 0 1 293 92234 .02 92235 4.89
92238 95.09 END
AL 2 1 END
H2O 3 1 END

```

```

END COMP
SPHERICAL END
1 34.6 ONEEXTERMOD 2 34.76 NOEXTERMOD 3 52.76 NOEXTERMOD END ZONE
4.89% UO2F2 27.3 IN DIAM AL SPHERE REFL 4
READ PARAM NPG=600 NUB=YES FDN=YES END PARAM
READ GEOM
HEMISPHE-Z 1 1 34.6 CHORD 27.9
SPHERE 0 1 34.6
SPHERE 2 1 34.759
REFLECTOR 3 2 3.6
END GEOM
READ BIAS ID=500 2 7 END BIAS
END DATA
END

```

VALIDATION CASE (CAB03)

```

=CSAS25
CASE EBJ.3X ( U(3.85) 24 @ 7.2"/0"/1.5"/75.0CM, SQUARE)
27GROUPNDF4 INFHOMMEDIUM

```

```

' U(3.85) METAL
U-235 1 0. 1.8643E-3 END
U-238 1 0. 4.5971E-2 END

```

```

' FULL DENSITY WATER MODERATOR/REFLECTOR
H2O 2 1.0 END

```

```

' FIR TIMBER MODEL
C 3 0. 1.06802E-2 END
H 3 0. 2.21713E-2 END
O 3 0. 1.10850E-2 END

```

```

' STEEL FOR GRATING, TANK WALLS AND FLOOR
CARBONSTEEL 4 1.0 END

```

```

' STAINLESS STEEL LINING FOR TANK
SS304 5 1.0 END

```

```

END COMP
CASE EBJ.3X
READ PARAM
NPG=600 NUB=YES PLT=NO FDN=YES TME=90 TBA=2 FLX=YES
END PARAM
READ GEOM

```

```

UNIT 1
COM=* FIR TIMBER 7.25" X 72" X 7.25" *
CUBOID 3 1 182.88 0. 18.415 0. 18.415 0.

UNIT 2
COM=* WATER GAP 3.5" X 72" X 7.25" BETWEEN TIMBERS *
CUBOID 2 1 182.88 0. 8.89 0. 18.415 0.

UNIT 3
COM=* ARRAY OF TIMBERS 72" X 72" X 7.25" PLUS 12" H2O *
ARRAY 1 3*0.0
REPLICATE 2 1 2R0. 2R0.3175 2R0. 1
REPLICATE 2 1 4R30.48 2R0. 1

UNIT 4
COM=* SECTION OF STEEL GRATING *
CUBOID 4 1 2.778125 .238125 .396875 -.396875 3.175 2.38125
CUBOID 2 1 2.778125 .238125 4.524375 -4.524375 3.175 0.
CUBOID 4 1 3.01625 0. 4.524375 -4.524375 3.175 0.

UNIT 5
COM=* ARRAY OF STEEL GRATING PLUS 12" H2O *
ARRAY 2 3*0.0
REPLICATE 2 1 4R0.9525 2R0.0 1
REPLICATE 2 1 4R30.48 2R0.0 1

UNIT 6
COM=* U(3.85) ANNULUS WITH INSERT (75.0 CM H) *
CYLINDER 1 1 3.175 75.0 0.
CYLINDER 2 1 3.302 75.0 0.
CYLINDER 1 1 9.144 75.0 0.
CUBOID 2 1 4P11.049 75.0 0.

UNIT 7
COM=* WATER CUBOID TO COMPLETE ANNULI ARRAY (75.0 CM H) *
CUBOID 2 1 4P11.049 75.0 0.

UNIT 8
COM=* ARRAY OF 24 ANNULI WITH U(3.85) INSERTS (75.0 CM H) *
ARRAY 3 3*0.0
REPLICATE 2 1 4R36.195 2R0. 1
REPLICATE 2 1 4R30.48 2R0.0 1

UNIT 9
COM=* U(3.85) ANNULUS WITH INSERT (1.2 CM H) *
CYLINDER 1 1 3.175 1.2 0.
CYLINDER 0 1 3.302 1.2 0.
CYLINDER 1 1 9.144 1.2 0.
CUBOID 0 1 4P11.049 1.2 0.

UNIT 10
COM=* VOID CUBOID TO COMPLETE ANNULI ARRAY (1.2 CM H) *
CUBOID 0 1 4P11.049 1.2 0.

UNIT 11
COM=* ARRAY OF 24 ANNULI WITH U(3.85) INSERTS (1.2 CM H) *
ARRAY 4 3*0.0
REPLICATE 0 1 4R36.195 2R0.0 1
REPLICATE 0 1 4R30.48 2R0.0 1

CORE 5 1 -121.92 -121.92 0.
REPLICATE 5 1 5R0.0 0.1905 1
REPLICATE 4 1 5R0.0 2.54 1
END GEOM
READ ARRAY
ARA=1 NUX=1 NUY=13 NUZ=1
FILL 1 2 5Q2 1 END FILL
ARA=2 NUX=60 NUY=20 NUZ=1
FILL F4 END FILL
ARA=3 NUX=5 NUY=5 NUZ=1
LOOP 6 1 5 1 1 5 1 1 1 1
7 5 5 1 1 1 1 1 1 1 END LOOP
ARA=4 NUX=5 NUY=5 NUZ=1
LOOP 9 1 5 1 1 5 1 1 1 1
10 5 5 1 1 1 1 1 1 1 1 END LOOP
GBL=5
ARA=5 NUX=1 NUY=1 NUZ=4
FILL 3 5 8 11 END FILL
END ARRAY
READ START
NST=1
XSM=-55.245 XSP=55.245 YSM=-55.245 YSP=55.245 ZSM=21.59 ZSP=97.79
END START
READ PLOT

```


TTL="PLAN VIEW 1/6 SCALE OF PALLET, Z=MIDLEVEL OF ANNULI/INSERTS"
 XUL=-91.44 YUL=91.44 ZUL=59.69
 XLR=91.44 YLR=-91.44 ZLR=59.69
 UAX=1. VDN=-1. DLX=1.524 NCH=* U.WGSC* END

TTL="PLAN VIEW 1/6 SCALE OF PALLET, Z=MIDLEVEL OF GRATING"
 XUL=-91.44 YUL=91.44 ZUL=20.0025
 XLR=91.44 YLR=-91.44 ZLR=20.0025
 UAX=1. VDN=-1. DLX=1.524 NCH=* U.WGSC* END

TTL="PLAN VIEW 1/6 SCALE OF PALLET, Z=MIDLEVEL OF FIR TIMBERS"
 XUL=-91.44 YUL=91.44 ZUL=9.2075
 XLR=91.44 YLR=-91.44 ZLR=9.2075
 UAX=1. VDN=-1. DLX=1.524 NCH=* U.WGSC* END

TTL="PLAN VIEW 1/10 SCALE OF MOCKUP, Z=MIDLEVEL OF U UNITS"
 XUL=-137. YUL=137. ZUL=59.69
 XLR=137. YLR=-137. ZLR=59.69
 UAX=1. VDN=-1. DLX=2.54 NCH=* U.WGSC* END

TTL="PLAN VIEW 2X SCALE OF SINGLE U UNIT, Z=MIDLEVEL OF UNIT"
 XUL=-11.049 YUL=11.049 ZUL=59.69
 XLR=11.049 YLR=-11.049 ZLR=59.69
 UAX=1. VDN=-1. DLX=0.127 NCH=* U.WGSC* END

TTL="CROSS SECTION OF PALLET 1/6 SCALE, Y=0.0"
 XUL=-91.44 YUL=0.0 ZUL=113.
 XLR=91.44 YLR=0.0 ZLR=-18.
 UAX=1. VDN=-1. DLX=1.524 NCH=* U.WGSC* END

TTL="CROSS SECTION OF MOCKUP 1/10 SCALE, Y=0.0"
 XUL=-137. YUL=0.0 ZUL=113.
 XLR=137. YLR=0.0 ZLR=-18.
 UAX=1. VDN=-1. DLX=2.54 NCH=* U.WGSC* END

TTL="CROSS SECTION OF FLOOR/GRATING/FIR TIMBERS, FULL SCALE"
 XUL=0. YUL=0. ZUL=24.13
 XLR=25.4 YLR=0. ZLR=-5.4
 UAX=1. VDN=-1. DLX=.254 NCH=* U.WGSC* END

TTL="PLAN VIEW OF GRATING THRU TIEBARS, FULL SCALE"
 XUL=0. YUL=25.4 ZUL=21.193
 XLR=25.4 YLR=0. ZLR=21.193
 UAX=1. VDN=-1. DLX=.254 NCH=* U.WGSC* END

TTL="PLAN VIEW OF GRATING @ GRATING MIDLEVEL, FULL SCALE"
 XUL=0. YUL=25.4 ZUL=20.0025
 XLR=25.4 YLR=0. ZLR=20.0025
 UAX=1. VDN=-1. DLX=.254 NCH=* U.WGSC* END

TTL="PLAN VIEW OF TIMBERS @ TIMBER MIDLEVEL, FULL SCALE"
 XUL=0. YUL=25.4 ZUL=9.2075
 XLR=25.4 YLR=-25.4 ZLR=9.2075
 UAX=1. VDN=-1. DLX=.254 NCH=* U.WGSC* END

TTL="CROSS SECTION AT TOP OF UNITS, 2X SCALE"
 XUL=-11.049 YUL=0. ZUL=105.
 XLR=11.049 YLR=0. ZLR=90.
 UAX=1. VDN=-1. DLX=.127 NCH=* U.WGSC* END
 END PLOT
 END DATA
 END

VALIDATION CASE (CAB08)
 =CSAS25
 CASE EBJ.5X (U(3.85) 7 @ 7.2"/0"/1.0"/53.1CM, TRIANGULAR)
 27GROUPNDF4 INFHOMMEDIUM

/ U(3.85) METAL
 U-235 1 0. 1.8643E-3 END
 U-238 1 0. 4.5971E-2 END

/ FULL DENSITY WATER MODERATOR/REFLECTOR
 H2O 2 1.0 END

/ FIR TIMBER MODEL
 C 3 0. 1.06802E-2 END
 H 3 0. 2.21713E-2 END
 O 3 0. 1.10850E-2 END

/ STEEL FOR GRATING, TANK WALLS AND FLOOR
 CARBONSTEEL 4 1.0 END

/ STAINLESS STEEL LINING FOR TANK
 SS304 5 1.0 END

END COMP
CASE EBJ.5X
READ PARM
TBA=3 NPG=600 NUB=YES PLT=NO FDN=YES TME=90
END PARM
READ GEOM

UNIT 1
COM=* FIR TIMBER 7.25" X 72" X 7.25" *
CUBOID 3 1 182.88 0. 18.415 0. 18.415 0.

UNIT 2
COM=* WATER GAP 3.5" X 72" X 7.25" BETWEEN TIMBERS *
CUBOID 2 1 182.88 0. 8.89 0. 18.415 0.

UNIT 3
COM=* ARRAY OF TIMBERS 72" X 72" X 7.25" *
ARRAY 1 3*0.0
REPLICATE 2 1 2R0. 2R0.3175 2R0. 1
REPLICATE 2 1 4R30.48 2R0.0 1

UNIT 4
COM=* SECTION OF STEEL GRATING *
CUBOID 4 1 2.778125 .238125 .396875 -.396875 3.175 2.38125
CUBOID 2 1 2.778125 .238125 4.524375 -4.524375 3.175 0.
CUBOID 4 1 3.01625 0. 4.524375 -4.524375 3.175 0.

UNIT 5
COM=* ARRAY OF STEEL GRATING *
ARRAY 2 3*0.0
REPLICATE 2 1 4R0.9525 2R0.0 1
REPLICATE 2 1 4R30.48 2R0.0 1

UNIT 6
COM=* U(3.85) UNIT, FLOODED, H=1.905, LEVELS 1 AND 3 *
CYLINDER 1 1 3.175 1.905 0.
CYLINDER 2 1 3.302 1.905 0.
CYLINDER 1 1 9.144 1.905 0.

UNIT 7
COM=* ARRAY OF 7 UNITS, FLOODED, H=1.905, LEVELS 1 AND 3 *
CUBOID 3 1 4P91.44 1.905 0.
HOLE 6 0.0 0.0 0.0
HOLE 6 -20.828 0.0 0.0
HOLE 6 -10.414 18.037577 0.0
HOLE 6 10.414 18.037577 0.0
HOLE 6 20.828 0.0 0.0
HOLE 6 10.414 -18.037577 0.0
HOLE 6 -10.414 -18.037577 0.0
REPLICATE 2 1 4R30.48 2R0.0 1

UNIT 8
COM=* U(3.85) UNIT, FLOODED, H=35.2425, LEVEL 2 *
CYLINDER 1 1 3.175 35.2425 0.
CYLINDER 2 1 3.302 35.2425 0.
CYLINDER 1 1 9.144 35.2425 0.

UNIT 9
COM=* ARRAY OF 7 UNITS, FLOODED, H=35.2425, LEVEL 2 *
CUBOID 2 1 4P91.44 35.2425 0.
HOLE 8 0.0 0.0 0.0
HOLE 8 -20.828 0.0 0.0
HOLE 8 -10.414 18.037577 0.0
HOLE 8 10.414 18.037577 0.0
HOLE 8 20.828 0.0 0.0
HOLE 8 10.414 -18.037577 0.0
HOLE 8 -10.414 -18.037577 0.0
REPLICATE 2 1 4R30.48 2R0.0 1

UNIT 10
COM=* U(3.85) UNIT, FLOODED, H=14.0475, LEVEL 4 *
CYLINDER 1 1 3.175 14.0475 0.
CYLINDER 2 1 3.302 14.0475 0.
CYLINDER 1 1 9.144 14.0475 0.

UNIT 11
COM=* ARRAY OF 7 UNITS, FLOODED, H=14.0475, LEVEL 4 *
CUBOID 2 1 4P91.44 14.0475 0.
HOLE 10 0.0 0.0 0.0
HOLE 10 -20.828 0.0 0.0
HOLE 10 -10.414 18.037577 0.0
HOLE 10 10.414 18.037577 0.0
HOLE 10 20.828 0.0 0.0
HOLE 10 10.414 -18.037577 0.0
HOLE 10 -10.414 -18.037577 0.0
REPLICATE 2 1 4R30.48 2R0.0 1

```

UNIT 12
COM=* U(3.85) UNIT, DRY, H=11.9875, LEVEL 5 *
CYLINDER 1 1 3.175 11.9875 0.
CYLINDER 0 1 3.302 11.9875 0.
CYLINDER 1 1 9.144 11.9875 0.

UNIT 13
COM=* ARRAY OF 7 UNITS, DRY, H=11.9875, LEVEL 5 *
CUBOID 0 1 4P91.44 11.9875 0.
HOLE 12 0.0 0.0 0.0
HOLE 12 -20.828 0.0 0.0
HOLE 12 -10.414 18.037577 0.0
HOLE 12 10.414 18.037577 0.0
HOLE 12 20.828 0.0 0.0
HOLE 12 -10.414 -18.037577 0.0
HOLE 12 -10.414 -18.037577 0.0
REPLICATE 0 1 4R30.48 2R0.0 1

UNIT 14
COM=* U(3.85) UNIT, DRY, H=1.905, LEVEL 6 *
CYLINDER 1 1 3.175 1.905 0.
CYLINDER 0 1 3.302 1.905 0.
CYLINDER 1 1 9.144 1.905 0.

UNIT 15
COM=* ARRAY OF 7 UNITS, DRY, H=1.905, LEVEL 6 *
CUBOID 3 1 4P91.44 1.905 0.
HOLE 14 0.0 0.0 0.0
HOLE 14 -20.828 0.0 0.0
HOLE 14 -10.414 18.037577 0.0
HOLE 14 10.414 18.037577 0.0
HOLE 14 20.828 0.0 0.0
HOLE 14 -10.414 -18.037577 0.0
HOLE 14 -10.414 -18.037577 0.0
REPLICATE 0 1 4R30.48 2R0.0 1

UNIT 16
COM=* U(3.85) UNIT, DRY, H=9.2075, LEVEL 7 *
CYLINDER 1 1 3.175 9.2075 0.
CYLINDER 0 1 3.302 9.2075 0.
CYLINDER 1 1 9.144 9.2075 0.

UNIT 17
COM=* ARRAY OF 7 UNITS, DRY, H=9.2075, LEVEL 7 *
CUBOID 0 1 4P91.44 9.2075 0.
HOLE 16 0.0 0.0 0.0
HOLE 16 -20.828 0.0 0.0
HOLE 16 -10.414 18.037577 0.0
HOLE 16 10.414 18.037577 0.0
HOLE 16 20.828 0.0 0.0
HOLE 16 -10.414 -18.037577 0.0
HOLE 16 -10.414 -18.037577 0.0
REPLICATE 0 1 4R30.48 2R0.0 1

CORE 3 1 -121.92 -121.92 0.
REPLICATE 5 1 5R0.0 0.1905 1
REPLICATE 4 1 5R0.0 2.54 1
END GEOM
READ ARRAY
ARA=1 NUX=1 NUY=13 NUZ=1
FILL 1 2 5Q2 1 END FILL
ARA=2 NUX=60 NUY=20 NUZ=1
FILL F4 END FILL
GBL=3
ARA=3 NUX=1 NUY=1 NUZ=9
FILL 3 5 7 9 7 11 13 15 17 END FILL
END ARRAY
READ START
NST=1
XSM=-20.828 XSP=20.828
YSM=-20.828 YSP=20.828
ZSM= 21.59 ZSP=74.69
END START
READ PLOT

TTL="PLAN VIEW 1/6 SCALE OF CORE, Z=MIDLEVEL OF ANNULI/INSERTS"
XUL=-100. YUL=100. ZUL=59.69
XLR=100. YLR=-100. ZLR=59.69
UAX=1. VDN=-1. DLX=1.524 NCH=* U.WGSC* END

TTL="PLAN VIEW 1/6 SCALE OF CORE, Z=MIDLEVEL OF GRATING"
XUL=-100. YUL=100. ZUL=20.0025
XLR=100. YLR=-100. ZLR=20.0025
UAX=1. VDN=-1. DLX=1.524 NCH=* U.WGSC* END

TTL="PLAN VIEW 1/6 SCALE OF CORE, Z=MIDLEVEL OF FIR TIMBERS"
XUL=-100. YUL=100. ZUL=9.2075

```

```

XLR=100. YLR=-100. ZLR=9.2075
UAX=1. VDN=-1. DLX=1.524 NCH=* U.WGSC* END

TTL="PLAN VIEW 1/10 SCALE OF MOCKUP, Z=MIDLEVEL OF U UNITS"
XUL=-130. YUL=130. ZUL=59.69
XLR=130. YLR=-130. ZLR=59.69
UAX=1. VDN=-1. DLX=2.54 NCH=* U.WGSC* END

TTL="PLAN VIEW, FULL SCALE AT CENTER OF ARRAY, Z=MIDLEVEL "
XUL=-16.75 YUL=16.75 ZUL=59.69
XLR=16.75 YLR=-16.75 ZLR=59.69
UAX=1. VDN=-1. DLX=0.254 NCH=* U.WGSC* END

TTL="CROSS SECTION OF CORE 1/6 SCALE,Y=0.0"
XUL=-100. YUL=0.0 ZUL=102.
XLR=100. YLR=0.0 ZLR=0.
UAX=1. VDN=-1. DLX=1.524 NCH=* U.WGSC* END

TTL="CROSS SECTION OF MOCKUP 1/10 SCALE,Y=0.0"
XUL=-130. YUL=0.0 ZUL=105.
XLR=130. YLR=0.0 ZLR=-65.
UAX=1. VDN=-1. DLX=2.54 NCH=* U.WGSC* END

TTL="CROSS SECTION OF GRATING/FIR TIMBERS, FULL SCALE"
XUL=0. YUL=0. ZUL=24.13
XLR=25.4 YLR=0. ZLR=-5.0
UAX=1. VDN=-1. DLX=.254 NCH=* U.WGSC* END

TTL="PLAN VIEW OF GRATING THRU TIEBARS, FULL SCALE"
XUL=0. YUL=25.4 ZUL=21.193
XLR=25.4 YLR=0. ZLR=21.193
UAX=1. VDN=-1. DLX=.254 NCH=* U.WGSC* END

TTL="PLAN VIEW OF GRATING @ GRATING MIDLEVEL, FULL SCALE"
XUL=0. YUL=25.4 ZUL=20.0025
XLR=25.4 YLR=0. ZLR=20.0025
UAX=1. VDN=-1. DLX=.254 NCH=* U.WGSC* END

TTL="PLAN VIEW OF TIMBERS @ TIMBER MIDLEVEL, FULL SCALE"
XUL=0. YUL=25.4 ZUL=9.2075
XLR=25.4 YLR=-25.4 ZLR=9.2075
UAX=1. VDN=-1. DLX=.254 NCH=* U.WGSC* END

TTL="CROSS SECTION OF CENTRAL UNIT, 2X SCALE"
XUL=0.0 YUL=0.0 ZUL=102.
XLR=15.24 YLR=0.0 ZLR=-5.
UAX=1. VDN=-1. DLX=0.127 NCH=* U.WGSC* END

END PLOT
END DATA
END

VALIDATION CASE (CAB11 )
=CSAS25
CASE EBJ.9 U(3.85) 16 @ 7.2"/2.6"/1.50"/49.2CM, SQUARE
27GROUPNDF4 INFHOMMEDIUM

' U(3.85) METAL
U-235 1 0. 1.8643E-3 END
U-238 1 0. 4.5971E-2 END

' FULL DENSITY WATER MODERATOR/REFLECTOR
H2O 2 1.0 END

' FIR TIMBER MODEL
C 3 0. 1.06802E-2 END
H 3 0. 2.21713E-2 END
O 3 0. 1.10850E-2 END

' STEEL FOR GRATING, TANK WALLS AND FLOOR
CARBONSTEEL 4 1.0 END

' STAINLESS STEEL LINING FOR TANK
SS304 5 1.0 END

END COMP
CASE EBJ.9 U(3.85) 16 @ 7.2"/2.6"/1.50"/49.2CM, SQUARE
READ PARM
NPG=600 NUB=YES PLT=NO FDN=YES TME=90 TBA=2
END PARM
READ GEOM

UNIT 1
COM=* FIR TIMBER 7.25" X 72" X 7.25" *
CUBOID 3 1 182.88 0. 18.415 0. 18.415 0.

```

UNIT 2
COM=* WATER GAP 3.5" X 72" X 7.25" BETWEEN TIMBERS *
CUBOID 2 1 182.88 0. 8.89 0. 18.415 0.

UNIT 3
COM=* ARRAY OF TIMBERS 72" X 72" X 7.25" *
ARRAY 1 3*0.0
REPLICATE 2 1 2R0. 2R0.3175 2R0. 1
REPLICATE 2 1 4R30.48 2R0. 1

UNIT 4
COM=* SECTION OF STEEL GRATING *
CUBOID 4 1 2.778125 .238125 .396875 -.396875 3.175 2.38125
CUBOID 2 1 2.778125 .238125 4.524375 -4.524375 3.175 0.
CUBOID 4 1 3.01625 0. 4.524375 -4.524375 3.175 0.

UNIT 5
COM=* ARRAY OF STEEL GRATING *
ARRAY 2 3*0.0
REPLICATE 2 1 4R0.9575 2R0.0 1
REPLICATE 2 1 4R30.48 2R0. 1

UNIT 6
COM=* U(3.85) ANNULUS, H=49.2, SUBMERGED, ON CORNER *
CYLINDER 2 1 3.302 49.2 0.
CYLINDER 1 1 4.614139 49.2 0.
CYLINDER 1 1 5.628264 49.2 0.
CYLINDER 1 1 6.485710 49.2 0.
CYLINDER 1 1 7.242341 49.2 0.
CYLINDER 1 1 7.927079 49.2 0.
CYLINDER 1 1 8.557199 49.2 0.
CYLINDER 1 1 9.144000 49.2 0.
CUBOID 2 1 4P11.049 49.2 0.

UNIT 7
COM=* U(3.85) ANNULUS, H=49.2, SUBMERGED, ON SIDE *
CYLINDER 2 1 3.302 49.2 0.
CYLINDER 1 1 4.614139 49.2 0.
CYLINDER 1 1 5.628264 49.2 0.
CYLINDER 1 1 6.485710 49.2 0.
CYLINDER 1 1 7.242341 49.2 0.
CYLINDER 1 1 7.927079 49.2 0.
CYLINDER 1 1 8.557199 49.2 0.
CYLINDER 1 1 9.144000 49.2 0.
CUBOID 2 1 4P11.049 49.2 0.

UNIT 8
COM=* U(3.85) ANNULUS, H=49.2, SUBMERGED, IN MIDDLE *
CYLINDER 2 1 3.302 49.2 0.
CYLINDER 1 1 4.614139 49.2 0.
CYLINDER 1 1 5.628264 49.2 0.
CYLINDER 1 1 6.485710 49.2 0.
CYLINDER 1 1 7.242341 49.2 0.
CYLINDER 1 1 7.927079 49.2 0.
CYLINDER 1 1 8.557199 49.2 0.
CYLINDER 1 1 9.144000 49.2 0.
CUBOID 2 1 4P11.049 49.2 0.

UNIT 9
COM=* U(3.85) ANNULUS, H=27.0, DRY, ON CORNER *
CYLINDER 0 1 3.302 27.0 0.
CYLINDER 1 1 4.614139 27.0 0.
CYLINDER 1 1 5.628264 27.0 0.
CYLINDER 1 1 6.485710 27.0 0.
CYLINDER 1 1 7.242341 27.0 0.
CYLINDER 1 1 7.927079 27.0 0.
CYLINDER 1 1 8.557199 27.0 0.
CYLINDER 1 1 9.144000 27.0 0.
CUBOID 0 1 4P11.049 27.0 0.

UNIT 10
COM=* U(3.85) ANNULUS, H=27.0, DRY, ON SIDE *
CYLINDER 0 1 3.302 27.0 0.
CYLINDER 1 1 4.614139 27.0 0.
CYLINDER 1 1 5.628264 27.0 0.
CYLINDER 1 1 6.485710 27.0 0.
CYLINDER 1 1 7.242341 27.0 0.
CYLINDER 1 1 7.927079 27.0 0.
CYLINDER 1 1 8.557199 27.0 0.
CYLINDER 1 1 9.144000 27.0 0.
CUBOID 0 1 4P11.049 27.0 0.

UNIT 11
COM=* U(3.85) ANNULUS, H=27.0, DRY, IN MIDDLE *
CYLINDER 0 1 3.302 27.0 0.
CYLINDER 1 1 4.614139 27.0 0.
CYLINDER 1 1 5.628264 27.0 0.

CYLINDER 1 1 6.485710 27.0 0.
 CYLINDER 1 1 7.242341 27.0 0.
 CYLINDER 1 1 7.927079 27.0 0.
 CYLINDER 1 1 8.557199 27.0 0.
 CYLINDER 1 1 9.144000 27.0 0.
 CUBOID 0 1 4P11.049 27.0 0.

UNIT 12
 COM=* ARRAY OF 16 ANNULI, H=49.2, SUBMERGED *
 ARRAY 3 3*0.0
 REPLICATE 2 1 4R47.244 2R0. 1
 REPLICATE 2 1 4R30.48 2R0. 1

UNIT 13
 COM=* ARRAY OF 16 ANNULI, H=27.0, DRY *
 ARRAY 4 3*0.0
 REPLICATE 0 1 4R47.244 2R0. 1
 REPLICATE 0 1 4R30.48 2R0. 1

CORE 5 1 -121.92 -121.92 0.
 REPLICATE 5 1 5R0.0 0.1905 1
 REPLICATE 4 1 5R0.0 2.54 1
 END GEOM
 READ ARRAY
 ARA=1 NUX=1 NUY=13 NUZ=1
 FILL 1 2 5Q2 1 END FILL
 ARA=2 NUX=60 NUY=20 NUZ=1
 FILL F4 END FILL
 ARA=3 NUX=4 NUY=4 NUZ=1
 FILL 6 7 7 6 7 8 8 7 7 8 8 7 6 7 7 6 END FILL
 ARA=4 NUX=4 NUY=4 NUZ=1
 FILL 9 10 10 9 10 11 11 10 10 11 11 10 9 10 10 9 END FILL
 GBL=5
 ARA=5 NUX=1 NUY=1 NUZ=4
 FILL 3 5 12 13 END FILL
 END ARRAY
 READ START
 NST=1
 XSM=-44.196 XSP=44.196
 YSM=-44.196 YSP=44.196
 ZSM=21.59 ZSP=70.79
 END START
 READ PLOT

TTL="PLAN VIEW 1/6 SCALE OF CORE, Z=MIDLEVEL OF ANNULI/INSERTS"
 XUL=-91.44 YUL=91.44 ZUL=59.69
 XLR=91.44 YLR=-91.44 ZLR=59.69
 UAX=1. VDN=-1. DLX=1.524 NCH=* U.WGS* END

TTL="PLAN VIEW 1/6 SCALE OF CORE, Z=MIDLEVEL OF GRATING"
 XUL=-91.44 YUL=91.44 ZUL=20.0025
 XLR=91.44 YLR=-91.44 ZLR=20.0025
 UAX=1. VDN=-1. DLX=1.524 NCH=* U.WGS* END

TTL="PLAN VIEW 1/6 SCALE OF CORE, Z=MIDLEVEL OF FIR TIMBERS"
 XUL=-91.44 YUL=91.44 ZUL=9.2075
 XLR=91.44 YLR=-91.44 ZLR=9.2075
 UAX=1. VDN=-1. DLX=1.524 NCH=* U.WGS* END

TTL="PLAN VIEW 1/10 SCALE OF MOCKUP, Z=MIDLEVEL OF U UNITS"
 XUL=-135. YUL=135. ZUL=59.69
 XLR=135. YLR=-135. ZLR=59.69
 UAX=1. VDN=-1. DLX=2.54 NCH=* U.WGS* END

TTL="PLAN VIEW 2X SCALE OF SINGLE U UNIT, Z=MIDLEVEL OF UNIT"
 XUL=0.0 YUL=22.098 ZUL=59.69
 XLR=22.098 YLR=0. ZLR=59.69
 UAX=1. VDN=-1. DLX=0.127 NCH=* U.WGS* END

TTL="CROSS SECTION OF CORE 1/6 SCALE, Y=11.049"
 XUL=-91.44 YUL=11.049 ZUL=110.
 XLR=91.44 YLR=11.049 ZLR=-10.
 UAX=1. WDN=-1. DLX=1.524 NCH=* U.WGS* END

TTL="CROSS SECTION OF MOCKUP 1/10 SCALE, Y=11.049"
 XUL=-135. YUL=11.049 ZUL=125.
 XLR=135. YLR=11.049 ZLR=-10.
 UAX=1. WDN=-1. DLX=2.54 NCH=* U.WGS* END

TTL="CROSS SECTION OF GRATING/FIR TIMBERS, FULL SCALE"
 XUL=0. YUL=0. ZUL=24.13
 XLR=25.4 YLR=0. ZLR=-3.0
 UAX=1. WDN=-1. DLX=.254 NCH=* U.WGS* END

TTL="PLAN VIEW OF GRATING THRU TIEBARS, FULL SCALE"
 XUL=0. YUL=25.4 ZUL=21.193
 XLR=25.4 YLR=0. ZLR=21.193

```

UAX=1. VDN=-1. DLX=.254 NCH=* U.WGS* END

TTL="PLAN VIEW OF GRATING @ GRATING MIDLEVEL, FULL SCALE"
XUL=0. YUL=25.4 ZUL=20.0025
XLR=25.4 YLR=0. ZLR=20.0025
UAX=1. VDN=-1. DLX=.254 NCH=* U.WGS* END

TTL="PLAN VIEW OF TIMBERS @ TIMBER MIDLEVEL, FULL SCALE"
XUL=0. YUL=25.4 ZUL=9.2075
XLR=25.4 YLR=-25.4 ZLR=9.2075
UAX=1. VDN=-1. DLX=.254 NCH=* U.WGS* END

TTL="CROSS SECTION OF CENTRAL UNIT, FULL SCALE,Y=11.049"
XUL=0.0 YUL=22.098 ZUL=110.
XLR=22.098 YLR=0.0 ZLR=-10.
UAX=1. VDN=-1. DLX=.254 NCH=* U.WGS* END

END PLOT
END DATA
END

VALIDATION CASE (CAB15 )
=CSAS25
CASE EBJ.13 U(3.85) 15 @ 2.5"/0.0"/0.75"/64.8CM, SQUARE
27GROUPNDF4 INFHOMMEDIUM

/ U(3.85) METAL
U-235 1 0. 1.8643E-3 END
U-238 1 0. 4.5971E-2 END

/ FULL DENSITY WATER MODERATOR/REFLECTOR
H2O 2 1.0 END

/ FIR TIMBER MODEL
C 3 0. 1.06802E-2 END
H 3 0. 2.21713E-2 END
O 3 0. 1.10850E-2 END

/ STEEL FOR GRATING, TANK WALLS AND FLOOR
CARBONSTEEL 4 1.0 END

/ STAINLESS STEEL LINING FOR TANK
SS304 5 1.0 END

END COMP
CASE EBJ.13 U(3.85) 15 @ 2.5"/0.0"/0.75"/64.8CM, SQUARE
READ PARM
NPG=600 NUB=YES PLT=NO FDN=YES TME=90 TBA=2
END PARM
READ GEOM

UNIT 1
COM=* FIR TIMBER 7.25" X 72" X 7.25" *
CUBOID 3 1 182.88 0. 18.415 0. 18.415 0.

UNIT 2
COM=* WATER GAP 3.5" X 72" X 7.25" BETWEEN TIMBERS *
CUBOID 2 1 182.88 0. 8.89 0. 18.415 0.

UNIT 3
COM=* ARRAY OF TIMBERS 72" X 72" X 7.25" *
ARRAY 1 3*0.0
REPLICATE 2 1 2R0. 2R0.3175 2R0. 1
REPLICATE 2 1 4R30.48 2R0. 1

UNIT 4
COM=* SECTION OF STEEL GRATING *
CUBOID 4 1 2.778125 .238125 .396875 -.396875 3.175 2.38125
CUBOID 2 1 2.778125 .238125 4.524375 -4.524375 3.175 0.
CUBOID 4 1 3.01625 0. 4.524375 -4.524375 3.175 0.

UNIT 5
COM=* ARRAY OF STEEL GRATING *
ARRAY 2 3*0.0
REPLICATE 2 1 4R0.9525 2R0.0 1
REPLICATE 2 1 4R30.48 2R0. 1

UNIT 6
COM=* U(3.85) ROD, H=64.8, SUBMERGED *
CYLINDER 1 1 1.419903 64.8 0.
CYLINDER 1 1 2.008046 64.8 0.
CYLINDER 1 1 2.459344 64.8 0.
CYLINDER 1 1 2.839806 64.8 0.
CYLINDER 1 1 3.175000 64.8 0.
CUBOID 2 1 4P4.1275 64.8 0.

```

```

UNIT 7
COM=* WATER CUBOID TO COMPLETE ARRAY 3 *
CUBOID 2 1 4P4.1275 64.8 0.

UNIT 8
COM=* U(3.85) ROD H=11.4, DRY *
CYLINDER 1 1 1.419903 11.4 0.
CYLINDER 1 1 2.008046 11.4 0.
CYLINDER 1 1 2.459344 11.4 0.
CYLINDER 1 1 2.839806 11.4 0.
CYLINDER 1 1 3.175000 11.4 0.
CUBOID 0 1 4P4.1275 11.4 0.

UNIT 9
COM=* VOID CUBOID TO COMPLETE ARRAY 4 *
CUBOID 0 1 4P4.1275 11.4 0.

UNIT 10
COM=* U(3.85) ROD ARRAY, H=64.8, SUBMERGED *
ARRAY 3 3*0.0
REPLICATE 2 1 4R74.93 2R0. 1
REPLICATE 2 1 4R30.48 2R0. 1

UNIT 11
COM=* ARRAY OF 15 RODS, H=11.4, DRY *
ARRAY 4 3*0.0
REPLICATE 0 1 4R74.93 2R0. 1
REPLICATE 0 1 4R30.48 2R0. 1

CORE 5 1 -121.92 -121.92 0.
REPLICATE 5 1 5R0.0 0.1905 1
REPLICATE 4 1 5R0.0 2.54 1
END GEOM
READ ARRAY
ARA=1 NUX=1 NUY=13 NUZ=1
FILL 1 2 5Q2 1 END FILL
ARA=2 NUX=60 NUY=20 NUZ=1
FILL F4 END FILL
ARA=3 NUX=4 NUY=4 NUZ=1
FILL 3R6 7 12R6 END FILL
ARA=4 NUX=4 NUY=4 NUZ=1
FILL 3R8 9 12R8 END FILL
GBL=5
ARA=5 NUX=1 NUY=1 NUZ=4
FILL 3 5 10 11 END FILL
END ARRAY
READ START
NST=1
XSM=-16.51 XSP=16.51
YSM=-16.51 YSP=16.51
ZSM=21.59 ZSP=86.39
END START
READ PLOT

TTL="PLAN VIEW 1/6 SCALE OF CORE, Z=MIDLEVEL OF ANNULI/INSERTS"
XUL=-91.44 YUL=91.44 ZUL=59.69
XLR=91.44 YLR=-91.44 ZLR=59.69
UAX=1. VDN=-1. DLX=1.524 NCH=* U.WGS* END

TTL="PLAN VIEW FULL SCALE OF ARRAY, Z=MIDLEVEL OF UNITS"
XUL=-16.51 YUL=16.51 ZUL=59.69
XLR=16.51 YLR=-16.51 ZLR=59.69
UAX=1. VDN=-1. DLX=.254 NCH=* U.WGS* END

TTL="PLAN VIEW 1/6 SCALE OF CORE, Z=MIDLEVEL OF GRATING"
XUL=-91.44 YUL=91.44 ZUL=20.0025
XLR=91.44 YLR=-91.44 ZLR=20.0025
UAX=1. VDN=-1. DLX=1.524 NCH=* U.WGS* END

TTL="PLAN VIEW 1/6 SCALE OF CORE, Z=MIDLEVEL OF FIR TIMBERS"
XUL=-91.44 YUL=91.44 ZUL=9.2075
XLR=91.44 YLR=-91.44 ZLR=9.2075
UAX=1. VDN=-1. DLX=1.524 NCH=* U.WGS* END

TTL="PLAN VIEW 1/10 SCALE OF MOCKUP, Z=MIDLEVEL OF U UNITS"
XUL=-135. YUL=135. ZUL=59.69
XLR=135. YLR=-135. ZLR=59.69
UAX=1. VDN=-1. DLX=2.54 NCH=* U.WGS* END

TTL="PLAN VIEW 2X SCALE OF SINGLE U UNIT, Z=MIDLEVEL OF UNIT"
XUL=0.0 YUL=8.255 ZUL=59.69
XLR=8.255 YLR=0.0 ZLR=59.69
UAX=1. VDN=-1. DLX=0.127 NCH=* U.WGS* END

TTL="CROSS SECTION OF CORE 1/6 SCALE,Y=4.1275"
XUL=-91.44 YUL=4.1275 ZUL=110.
XLR=91.44 YLR=4.1275 ZLR=-10.

```


UAX=1. WDN=-1. DLX=1.524 NCH=* U.WGS* END

TTL="CROSS SECTION OF MOCKUP 1/10 SCALE,Y=4.12;3"
XUL=-135. YUL=4.1275 ZUL=125.
XLR=135. YLR=4.1275 ZLR=-10.
UAX=1. WDN=-1. DLX=2.54 NCH=* U.WGS* END

TTL="CROSS SECTION OF GRATING/FIR TIMBERS, FULL SCALE"
XUL=0. YUL=0. ZUL=24.13
XLR=25.4 YLR=0. ZLR=-3.0
UAX=1. WDN=-1. DLX=.254 NCH=* U.WGS* END

TTL="PLAN VIEW OF GRATING THRU TIEBARS, FULL SCALE"
XUL=0. YUL=25.4 ZUL=21.193
XLR=25.4 YLR=0. ZLR=21.193
UAX=1. VDN=-1. DLX=.254 NCH=* U.WGS* END

TTL="PLAN VIEW OF GRATING @ GRATING MIDLEVEL, FULL SCALE"
XUL=0. YUL=25.4 ZUL=20.0025
XLR=25.4 YLR=0. ZLR=20.0025
UAX=1. VDN=-1. DLX=.254 NCH=* U.WGS* END

TTL="PLAN VIEW OF TIMBERS @ TIMBER MIDLEVEL, FULL SCALE"
XUL=0. YUL=25.4 ZUL=9.2075
XLR=25.4 YLR=-25.4 ZLR=9.2075
UAX=1. VDN=-1. DLX=.254 NCH=* U.WGS* END

TTL="CROSS SECTION OF CENTRAL UNIT, 2X SCALE,Y=4.1275"
XUL=0.0 YUL=4.1275 ZUL=110.
XLR=8.255 YLR=4.1275 ZLR=-10.
UAX=1. WDN=-1. DLX=.127 NCH=* U.WGS* END

END PLOT
END DATA
END

VALIDATION CASE (CAR01)
=CSAS25
ROCKY FLATS CRITICALS NUREG/CR-1071 EXPERIMENT NUMBER 1 (27 GROUP)
' 48 FUEL CANS 2.44 CM MODERATOR GEE.HU77.DATA(OPT1)
27GROUPNDF4 LATTICECELL
U308 1 5.4078E-1 293.0 92234 0.03 92235 4.46 92236 0.08 92238 95.43 END
H2O 1 8.9514E-2 END
ARBH-BAGGIE 1.0 3 0 0 0 1001 14.01 6012 84.9 8016 1.20 1 1.9134E-2
END
ARBH-AL1100 1.0 3 0 0 1 13027 99.18 26000 0.5 29000 0.2 2 9.5390E-1
END
ARBH-TAPE(VINYL) 1.0 7 0 0 0 1001 5.92 6012 45.91 8016 10.82 17000
25.73 20000 6.9 22000 1.6 82000 1.1 2 1.1115E-2 END
ARBH-TAPE(MYLAR) 1.0 3 0 0 0 1001 6.83 6012 65.50 8016 27.02 2
1.7491E-2 END
ARBH-MODERATOR 1.185 3 0 0 0 1001 7.83 6012 59.49 8016 32.48 3 END
ARBH-PLEX(REG) 1.0 3 0 0 0 1001 7.84 6012 59.59 8016 32.23 4
1.1773 END
ARBH-PLEX(PAPER) 1.0 3 0 0 0 1001 6.48 6012 42.17 8016 49.5 4
3.7534E-3 END
ARBH-PLEX(GLUE) 1.0 3 0 0 0 1001 11.67 6012 86.29 8016 1.20 4
1.1648E-3 END
ARBH-PLEX(TRIS) 1.0 8 0 0 1 1001 7.16 6012 52.03 7014 0.16 8016 29.82
15031 1.02 17000 1.81 35079 4.260 35081 2.840 5 1.2757 END
ARBH-PLEX(PAPER) 1.0 3 0 0 0 1001 6.48 6012 42.17 8016 49.5 5
3.7534E-3 END
ARBH-PLEX(GLUE) 1.0 3 0 0 0 1001 11.67 6012 86.29 8016 1.20 5
1.1648E-3 END
ARBH-FILLER 1.185 3 0 0 0 1001 7.83 6012 59.49 8016 32.48 6 .88 END
' THIS MATERIAL IS ACTUALLY MODERATOR ADJUSTED FOR THE VOLUME
' FRACTION OF THE VOID FILLED BETWEEN CORE AND REFLECTOR.
END COMP
SPHTRIANGP 19.9462 18.5857 1 3 18.9579 2 END
ROCKY FLATS CRITICALS NUREG/CR-1071 EXPERIMENT NUMBER 1 (27 GROUP)
' 48 FUEL CANS 2.44 CM MODERATOR GEE.HU77.DATA(OPT1)
READ PARM RUN=YES NPG=600
NUB=YES FDN=YES PLT=NO
END PARM
READ GEOM
UNIT 1
COM='FUEL BOX 15.28 CM ON A SIDE WITH .15 CM WALLS .05CM STACKING VOID'
CUBOID 1 1 6P7.49
CUBOID 2 1 6P7.64
CUBOID 0 1 6P7.6650
UNIT 2
COM='X-FACE INTERSTITIAL MODERATOR'
CUBOID 3 1 2P1.2200 4P7.665
UNIT 3
COM='Y-FACE INTERSTITIAL MODERATOR'
CUBOID 3 1 2P7.665 2P1.2200 2P7.665

```

UNIT 4
COM='Z-FACE INTERSTITIAL MODERATOR'
CUBOID 3 1 4P7.665 2P1.2200
UNIT 5
COM='MORE X-FACE MODERATOR'
CUBOID 3 1 4P1.2200 2P7.665
UNIT 6
COM='MORE Y-FACE MODERATOR'
CUBOID 3 1 2P7.665 4P1.2200
UNIT 7
COM='MORE Z-FACE MODERATOR'
CUBOID 3 1 2P1.2200 2P7.665 2P1.2200
UNIT 8
COM='LAST OF INTERSTITIAL MODERATOR'
CUBOID 3 1 6P1.2200
UNIT 9
COM='NORTH SPLIT TABLE CORE'
ARRAY 1 3*0.0
UNIT 10
COM='SOUTH SPLIT TABLE CORE'
ARRAY 2 3*0.0
UNIT 11
COM='PLEXIGLASS REFLECTOR SHEET WITHOUT TRIS, NORTH BOTTOM REFLECTOR'
CUBOID 4 1 2P16.5500 2P38.7500 2P0.6150
UNIT 12
COM='PLEXIGLASS REFLECTOR SHEET WITH TRIS, NORTH BOTTOM REFLECTOR'
CUBOID 5 1 2P16.5500 2P38.7500 2P0.6150
UNIT 13
COM='UPPER PORTION NORTH BOTTOM REFLECTOR WITH TRIS'
CUBOID 5 1 2P16.550 2P38.75 2P8.24
UNIT 14
COM='LOWER PORTION NORTH BOTTOM REFLECTOR WITH TRIS'
CUBOID 5 1 2P16.550 2P38.75 2P3.69
UNIT 15
COM='NORTH BOTTOM REFLECTOR INCLUDES REGULAR AND TRIS'
ARRAY 3 3*0.0
UNIT 16
COM='PLEXIGLAS SHEET BOTTOM SOUTH REFLECTOR WITHOUT TRIS'
CUBOID 0 1 2P5.1 2P2.55 2P0.615
CUBOID 4 1 44.3 -5.1 2P38.75 2P0.615
UNIT 17
COM='PLEXIGLAS SHEET BOTTOM SOUTH REFLECTOR WITH TRIS'
CUBOID 0 1 2P5.1 2P2.55 2P0.615
CUBOID 5 1 44.3 -5.1 2P38.75 2P0.6150
UNIT 18
COM='LOWER PORTION SOUTH BOTTOM REFLECTOR WITH TRIS'
CUBOID 0 1 2P5.1 2P2.55 2P8.855
CUBOID 5 1 44.3 -5.1 2P38.75 2P8.855
UNIT 19
COM='SOUTH BOTTOM REFLECTOR WITH REGULAR AND TRIS'
ARRAY 4 3*0.0
UNIT 20
COM='EAST AND WEST REFLECTORS FOR NORTH REFLECTOR WITH TRIS'
CUBOID 5 1 2P16.550 2P12.65 2P54.2825
UNIT 21
COM='ARRAY FOR EAST AND WEST REFLECTORS FOR NORTH REFLECTOR'
ARRAY 5 3*0.0
UNIT 22
COM='EAST AND WEST REFLECTORS FOR SOUTH REFLECTOR WITH TRIS'
CUBOID 5 1 2P24.700 2P12.65 2P54.2825
UNIT 23
COM='ARRAY FOR EAST AND WEST REFLECTORS FOR SOUTH REFLECTOR'
ARRAY 6 3*0.0
UNIT 24
COM='NORTH TOP REFLECTOR WITH TRIS'
CUBOID 5 1 2P29.100 2P64.05 2P12.15
UNIT 25
COM='ARRAY FOR NORTH TOP REFLECTOR'
ARRAY 7 3*0.0
UNIT 26
COM='SOUTH TOP REFLECTOR WITH TRIS'
CUBOID 0 1 2P5.1 2P2.55 2P12.15
CUBOID 5 1 69.4 -5.1 2P64.05 2P12.15
UNIT 27
COM='ARRAY FOR SOUTH TOP REFLECTOR'
ARRAY 8 3*0.0
UNIT 28
COM='NORTH END REFLECTOR 9.8CM PORTION WITHOUT TRIS'
CUBOID 4 1 2P4.9000 2P64.0500 2P54.2825
UNIT 29
COM='NORTH END REFLECTOR 5.2 CM PORTION WITH TRIS'
CUBOID 5 1 2P2.6 2P64.0500 2P54.2825
UNIT 30
COM='NORTH END REFLECTOR 10.1 CM PORTION WITHOUT TRIS'
CUBOID 4 1 2P5.05 2P64.05 2P54.2825

```

```

UNIT 31
COM='ARRAY FOR NORTH END REFLECTOR'
ARRAY 9 3*0.0
UNIT 32
COM='SOUTH END REFLECTOR'
CUBOID 5 1 2P12.55 2P64.05 2P54.2825
UNIT 33
COM='ARRAY FOR SOUTH END REFLECTOR'
ARRAY 10 3*0.0
UNIT 34
COM='BOTTOM MODERATING PLASTIC NORTH CORE'
CUBOID 6 1 2P16.550 2P38.7500 2P13.0500
UNIT 35
COM='TOP MODERATING PLASTIC NORTH CORE'
CUBOID 6 1 2P16.550 2P38.7500 2P3.2525
UNIT 36
ARRAY 11 3*0.0
UNIT 37
ARRAY 12 3*0.0
UNIT 38
COM='NORTH CORE WITH BOTTOM REFLECTOR'
ARRAY 13 3* 0.0
UNIT 39
COM='NORTH CORE WITH EAST AND WEST REFLECTOR'
ARRAY 14 3*0.0
UNIT 40
COM='NORTH CORE WITH END REFLECTOR'
ARRAY 15 3*0.0
UNIT 41
COM='NORTH SPLIT TABLE FACEPLATE'
CUBOID 3 1 2P0.6150 2P64.0500 2P66.4325
UNIT 42
COM='NORTH CORE WITH TOP REFLECTOR'
ARRAY 16 3*0.0
UNIT 43
COM='NORTH CORE WITH FACEPLATE'
ARRAY 17 3*0.0
UNIT 44
COM='12.95 CM THICK MODERATOR SOUTH CORE'
CUBOID 6 1 2P23.924 2P6.475 2P40.183
UNIT 45
COM='2.95 THICK MODERATOR SOUTH CORE'
CUBOID 6 1 2P23.924 2P38.5285 2P1.475
UNIT 46
COM='COMBINATION OF CORE WITH 12.95 THICK MODERATOR'
ARRAY 18 3*0.0
UNIT 47
COM='COMBINATION OF CORE WITH 2.95 THICK MODERATOR'
ARRAY 19 3*0.0
UNIT 48
COM='SOUTH CORE WITH EAST WEST REFLECTORS'
ARRAY 20 3*0.0
UNIT 49
COM='SOUTH CORE WITH EAST WEST REFLECTORS'
ARRAY 21 3*0.0
UNIT 50
COM='SOUTH CORE END REFLECTOR'
ARRAY 22 3*0.0
UNIT 51
COM='FACEPLATE FOR SOUTH SPLIT TABLE'
CUBOID 3 1 2P0.4620 2P64.0500 2P66.4325
UNIT 52
COM='SOUTH CORE WITH TOP REFLECTOR'
ARRAY 23 3*0.0
UNIT 53
COM='SOUTH CORE WITH FACEPLATE'
ARRAY 24 3*0.0
UNIT 54
COM='AIR GAP'
CUBOID 0 1 2P0.1550 2P64.0500 2P66.4325
GLOBAL
UNIT 55
COM='TOTAL'
ARRAY 25 3*0.0
UNIT 56
COM='EMPTY FUEL LOCATION'
CUBOID 0 1 6P7.6650
UNIT 57
COM='SIDE MODERATOR'
CUBOID 6 1 2P16.550 2P4.4300 2P25.4350
UNIT 58
COM='END MODERATOR'
CUBOID 6 1 2P8.1500 2P38.7500 2P25.4350
UNIT 59
COM='SOUTH CORE BOTTOM MODERATING PLASTIC'
CUBOID 6 1 2P24.7000 2P38.7500 2P13.0500

```

```

UNIT 60
COM='SOUTH CORE TOP MODERATING PLASTIC'
CUBOID 6 1 2P24.7000 2P38.7500 2P3.2525
UNIT 61
COM='Y-FACE MODERATOR VOID'
CUBOID 0 1 2P7.665 2P1.2200 2P7.665
END GEOMETRY
READ ARRAY
ARA=1 NUX=3 NUY=7 NUZ=5
COM='NORTH SPLIT TABLE CORE'
FILL 1 2 1 3 5 3 2Q6 1 2 1
      4 7 4 6 8 6 2Q6 4 7 4
      1Q42
      56 2 1 3 5 3 1 2 1 3 5 3 1Q6 56 2 1 END FILL
ARA=2 NUX=3 NUY=7 NUZ=5
COM='SOUTH SPLIT TABLE CORE'
FILL 1 2 1 3 5 3 2Q6 1 2 1
      4 7 4 6 8 6 2Q6 4 7 4
      1Q42
      1 2 56 3 5 61 2Q6 1 2 56 END FILL
ARA=3 NUX=1 NUY=1 NUZ=3
COM='NORTH BOTTOM REFLECTOR'
FILL 14 11 13 END FILL
ARA=4 NUX=1 NUY=1 NUZ=7
COM='SOUTH BOTTOM REFLECTOR'
FILL 18 16 17 16 16 17 17 END FILL
ARA=5 NUX=1 NUY=1 NUZ=1
COM='EAST AND WEST WALLS OF NORTH REFLECTOR'
FILL 20 END FILL
ARA=6 NUX=1 NUY=1 NUZ=1
COM='EAST AND WEST WALLS OF SOUTH REFLECTOR'
FILL 22 END FILL
ARA=7 NUX=1 NUY=1 NUZ=1
COM='ARRAY FOR NORTH TOP REFLECTOR'
FILL 24 END FILL
ARA=8 NUX=1 NUY=1 NUZ=1
COM='ARRAY FOR SOUTH TOP REFLECTOR'
FILL 26 END FILL
ARA=9 NUX=3 NUY=1 NUZ=1
COM='ARRAY FOR NORTH END REFLECTOR'
FILL 28 29 30 END FILL
ARA=10 NUX=1 NUY=1 NUZ=1
COM='ARRAY FOR SOUTH END REFLECTOR'
FILL 32 END FILL
ARA=11 NUX=1 NUY=2 NUZ=1
COM='COMBINARION OF CORE WITH SIDE MODERATOR'
FILL 9 57 END FILL
ARA=12 NUX=1 NUY=1 NUZ=3
COM='COMBINATION OF PREVIOUS ARRAY WITH TOP AND BOTTOM MODERATOR'
FILL 34 36 35 END FILL
ARA=13 NUX=1 NUY=1 NUZ=2
COM='COMBINATION OF NORTH CORE WITH BOTTOM REFLECTOR'
FILL 15 37 END FILL
ARA=14 NUX=1 NUY=3 NUZ=1
COM='NORTH CORE WITH SIDE REFLECTORS'
FILL 21 38 21 END FILL
ARA=15 NUX=2 NUY=1 NUZ=1
COM='NORTH CORE WITH END REFLECTOR'
FILL 31 39 END FILL
ARA=16 NUX=1 NUY=1 NUZ=2
COM='NORTH CORE WITH TOP REFLECTOR'
FILL 40 25 END FILL
ARA=17 NUX=2 NUY=1 NUZ=1
COM='NORTH CORE WITH FACEPLATE'
FILL 42 41 END FILL
ARA=18 NUX=1 NUY=2 NUZ=1
COM='COMBINATION OF S. CORE WITH SIDE MODERATOR'
FILL 10 57 END FILL
ARA=19 NUX=2 NUY=1 NUZ=1
COM='COMBINATION OF CORE WITH END MODERATOR'
FILL 46 58 END FILL
ARA=20 NUX=1 NUY=1 NUZ=4
COM='SOUTH CORE WITH BOTTOM MODERATOR AND REFLECTOR'
FILL 19 59 47 60 END FILL
ARA=21 NUX=1 NUY=3 NUZ=1
COM='SOUTH CORE WITH EAST WEST REFLECTORS'
FILL 23 48 23 END FILL
ARA=22 NUX=2 NUY=1 NUZ=1
COM='SOUTH CORE WITH END REFLECTOR'
FILL 49 33 END FILL
ARA=23 NUX=1 NUY=1 NUZ=2
COM='COMBINATION OF CORE WITH TOP REFLECTOR'
FILL 50 27 END FILL
ARA=24 NUX=2 NUY=1 NUZ=1
COM='SOUTH CORE WITH FACEPLATE'
FILL 51 52 END FILL
ARA=25 NUX=3 NUY=1 NUZ=1

```

```

COM='TOTAL'
FILL 43 54 53 END FILL
END ARRAY
READ PLOT TTL='XZ SLICE OF RFP1 SHOWING MATERIAL REGIONS'
XUL=-2 YUL=64.05 ZUL=136
XLR=137 YLR=64.05 ZLR=-2
UAX=1 WDN=-1 MAX=130 NCH='0123456'END
TTL='YZ SLICE OF NORTH CORE SECOND ROW'
XUL=28 YUL=-2 ZUL=136
XLR=28 YLR=136 ZLR=-2
VAX=1 WDN=-1 MAX=130 NCH='0123456'END
TTL='YZ SLICE OF SOUTH CORE SECOND ROW'
XUL=80 YUL=-2 ZUL=136
XLR=80 YLR=136 ZLR=-2
VAX=1 WDN=-1 MAX=130 NCH='0123456'
END PLOT
END DATA
END

VALIDATION CASE (CAR04 )
=CSAS25
ROCKY FLATS CRITICALS NUREG/CR-1071 EXPERIMENT NUMBER 13 (27 GROUP)
27GROUPNDF4 LATTICECELL
U308 1 5.4078E-1 293.0 92234 0.03 92235 4.46 92236 0.08 92238 95.43 END
H2O 1 8.9514E-2 END
ARBM-BAGGIE 1.0 3 0 0 0 1001 14.01 6012 84.9 8016 1.20 1 1.9134E-2
END
ARBM-AL1100 1.0 3 0 0 1 13027 99.18 26000 0.5 29000 0.2 2 9.5390E-1
END
ARBM-TAPE(VINYL) 1.0 7 0 0 0 1001 5.92 6012 45.91 8016 10.82 17000
25.73 20000 6.9 22000 1.6 82000 1.1 2 1.1115E-2 END
ARBM-TAPE(MYLAR) 1.0 3 0 0 0 1001 6.83 6012 65.50 8016 27.02 2
1.7491E-2 END
ARBM-MODERATOR 1.185 3 0 0 0 1001 7.83 6012 59.49 8016 32.48 3 END
RFCONCRETE 5 1.0 END
END COMP
SPHTRIANGP 19.9462 18.5857 1 3 18.9579 2 END
ROCKY FLATS CRITICALS NUREG/CR-1071 EXPERIMENT NUMBER 13 (27 GROUP)
READ PARM RUN=YES NPG=600
PLT=NO FDN=YES NUB=YES
END PARM
READ GEOM
UNIT 1
COM='FUEL BOX 15.28 CM ON A SIDE WITH .15 CM WALLS .05CM STACKING VOID'
CUBOID 1 1 6P7.49
CUBOID 2 1 6P7.64
CUBOID 0 1 6P7.6650
UNIT 2
COM='X-FACE INTERSTITIAL MODERATOR'
CUBOID 3 1 2P1.2200 4P7.665
UNIT 3
COM='Y-FACE INTERSTITIAL MODERATOR'
CUBOID 3 1 2P7.665 2P1.2200 2P7.665
UNIT 4
COM='Z-FACE INTERSTITIAL MODERATOR'
CUBOID 3 1 4P7.665 2P1.2200
UNIT 5
COM='MORE X-FACE MODERATOR'
CUBOID 3 1 4P1.2200 2P7.665
UNIT 6
COM='MORE Y-FACE MODERATOR'
CUBOID 3 1 2P7.665 4P1.2200
UNIT 7
COM='MORE Z-FACE MODERATOR'
CUBOID 3 1 2P1.2200 2P7.665 2P1.2200
UNIT 8
COM='LAST OF INTERSTITIAL MODERATOR'
CUBOID 3 1 6P1.2200
UNIT 9
COM='NORTH SPLIT TABLE CORE'
ARRAY 1 -33.1 2*0.0
CUBOID 5 1 0.0 -33.6 76.2 0.0 50.87 -30.5
CUBOID 0 1 0.0 -33.6 77.5 0.0 52.70 -30.5
CUBOID 5 1 0.0 -33.6 103.0 -25.5 78.2 -56.0
CUBOID 0 1 0.0 -34.3 103.0 -25.5 78.2 -56.0
CUBOID 5 1 0.0 -59.9 103.0 -25.5 78.2 -56.0
UNIT 10
COM='SOUTH SPLIT TABLE CORE'
ARRAY 2 3*0.0
CUBOID 5 1 44.4 0.0 76.2 0.0 50.87 -30.5
CUBOID 0 1 47.5 0.0 77.5 0.0 52.70 -30.5
CUBOID 5 1 73.0 0.0 103.0 -25.5 78.2 -56.0
HOLE 11 0.0 38.75 -56.0
HOLE 11 0.0 38.75 52.7
UNIT 11
CUBOID 0 1 10.2 0.0 2P2.55 25.5 0.0

```

```

UNIT 12
COM='NORTH SPLIT TABLE FACEPLATE'
CUBOID 3 1 2P0.6150 2P64.2500 2P67.1
UNIT 13
COM='FACEPLATE FOR SOUTH SPLIT TABLE'
CUBOID 3 1 2P0.6150 2P64.2500 2P67.1
UNIT 14
COM='AIR GAP'
CUBOID 0 1 2P0.2850 2P64.2500 2P67.1
GLOBAL
UNIT 15
COM='TOTAL'
ARRAY 3 3*0.0
UNIT 56
COM='EMPTY FUEL LOCATION'
CUBOID 0 1 6P7.6650
UNIT 61
COM='Y-FACE MODERATOR VOID'
CUBOID 0 1 2P7.665 2P1.2200 2P7.665
END GEOMETRY
READ ARRAY
ARA=1 NUX=3 NUY=7 NUZ=5
COM='NORTH SPLIT TABLE CORE'
FILL 1 2 1 3 5 3 2Q6 1 2 1
      4 7 4 6 8 6 2Q6 4 7 4
      1Q42
      56 2 1 61 5 3 2Q6 56 2 1 END FILL
ARA=2 NUX=3 NUY=7 NUZ=5
COM='SOUTH SPLIT TABLE CORE'
FILL 1 2 1 3 5 3 2Q6 1 2 1
      4 7 4 6 8 6 2Q6 4 7 4
      1Q42
      1 2 56 3 5 61 2Q6 1 2 56 END FILL
ARA=3 NUX=5 NUY=1 NUZ=1
COM='TOTAL'
FILL 9 12 14 13 10 END FILL
END ARRAY
READ PLOT TTL='XZ SLICE OF RFP1 SHOWING MATERIAL REGIONS'
XUL=-2 YUL=64.05 ZUL=136
XLR=137 YLR=64.05 ZLR=-2
UAX=1 WDN=-1 NAX=130 NCH='0123456'END
TTL='YZ SLICE OF NORTH CORE SECOND ROW'
XUL=28 YUL=-2 ZUL=136
XLR=28 YLR=136 ZLR=-2
VAX=1 WDN=-1 NAX=130 NCH='0123456'END
TTL='YZ SLICE OF SOUTH CORE SECOND ROW'
XUL=80 YUL=-2 ZUL=136
XLR=80 YLR=136 ZLR=-2
VAX=1 WDN=-1 NAX=130 NCH='0123456'
END PLOT
READ START NST=1
XSM=15 XSP=122 YSM=15 YSP=122 ZSM=30 ZSP=122 END START
END DATA
END

```

```

VALIDATION CASE (CAR07 )
=CSAS25
ROCKY FLATS CRITICALS NUREG/CR-0674 EXPERIMENT NUMBER ? (27 GROUP MODEL)
' FUEL CUBE 15.28 CM, U(4.46)308 @ H/U=0.77, HI CONC. SOLUTION DRIVEN
27GROUPPND4 INFHOMMEDIUM
U308 1 5.4078E-1 293.0 92234 0.03 92235 4.46 92236 0.08 92238 95.43 END
H2O 1 8.9514E-2 END
ARBM-BAGGIE 1.0 3 0 0 0 1001 14.01 6012 84.9 8016 1.20 1 1.9134E-2
END
ARBM-AL1100 1.0 3 0 0 1 13027 99.18 26000 0.5 29000 0.2 2 9.5390E-1
END
ARBM-TAPE(VINYL) 1.0 7 0 0 0 1001 5.92 6012 45.91 8016 10.82 17000
25.73 20000 6.9 22000 1.6 82000 1.1 2 1.1115E-2 END
ARBM-TAPE(MYLAR) 1.0 3 0 0 0 1001 6.83 6012 65.50 8016 27.02 2
1.7491E-2 END
ARBM-MODERATOR 1.185 3 0 0 0 1001 7.83 6012 59.49 8016 32.48 3 END
ARBM-PLEX(REG) 1.0 3 0 0 0 1001 7.84 6012 59.59 8016 32.23 4
1.1773 END
ARBM-PLEX(PAPER) 1.0 3 0 0 0 1001 6.48 6012 42.17 8016 49.5 4
3.7534E-3 END
ARBM-PLEX(GLUE) 1.0 3 0 0 0 1001 11.67 6012 86.29 8016 1.20 4
1.1648E-3 END
ARBM-PLEX(TRIS) 1.0 8 0 0 1 1001 7.16 6012 52.03 7014 0.16 8016 29.82
15031 1.02 17000 1.81 35079 4.260 35081 2.840 5 1.2757 END
ARBM-PLEX(PAPER) 1.0 3 0 0 0 1001 6.48 6012 42.17 8016 49.5 5
3.7534E-3 END
ARBM-PLEX(GLUE) 1.0 3 0 0 0 1001 11.67 6012 86.29 8016 1.20 5
1.1648E-3 END
ARBM-FILLER 1.185 3 0 0 0 1001 7.83 6012 59.49 8016 32.48 6 0.7 END
' THIS MATERIAL IS ACTUALLY MODERATOR ADJUSTED FOR THE VOLUME
' FRACTION OF THE VOID FILLED BETWEEN CORE AND REFLECTOR.
ARBM-AL1100 1.0 3 0 0 1 13027 99.18 26000 0.5 29000 0.2 7 2.715 END

```

SOLNU02(N03)2 8 351.18 0.549 1.0 293.0 92234 1.022 92235 93.172
 92236 0.434 92238 5.372 END
 SS304 9 1.0 END
 END COMP
 ROCKY FLATS CRITICALS NUREG/CR-0674 EXPERIMENT NUMBER ? (27 GROUP MODEL)
 ' FUEL CUBE 15.28 CM, U(4.46)308 @ H/U=0.77, HI CONC. SOLUTION DRIVEN
 READ PARM NPG=600 NUB=YES FDN=YES PLT=NO END PARM
 READ GEOM
 UNIT 1
 COM='FUEL BOX WITH VOID AND PART OF AL BOX'
 CUBOID 0 1 9.80 0.0 3.75 0.0 14.98 0.0
 CUBOID 2 1 9.95 0.0 3.90 -0.15 14.98 0.0
 CUBOID 1 1 14.98 0.0 9.365 -5.615 14.98 0.0
 UNIT 2
 COM='FRONT OF FUEL BOX'
 CUBOID 2 1 0.15 0.0 5.615 0.0 14.98 0.0
 CUBOID 0 1 0.15 0.0 9.365 0.0 14.98 0.0
 CUBOID 2 1 0.15 0.0 14.98 0.0 14.98 0.0
 UNIT 3
 COM='REAR OF FUEL BOX'
 CUBOID 2 1 0.15 0.0 14.98 0.0 14.98 0.0
 UNIT 4
 COM='ARRAY TO ASSEMBLE PART OF BOX'
 ARRAY 26 3*0
 UNIT 5
 COM='TOP AND BOTTOM OF BOX'
 CUBOID 0 1 9.80 0.0 3.750 0.0 0.15 0.0
 CUBOID 2 1 15.28 0.0 9.365 -5.615 0.15 0.0
 GLOBAL
 UNIT 6
 COM='ARRAY TO ASSEMBLE TOP AND BOTTOM'
 ARRAY 27 3*0
 CUBOID 2 1 15.28 0.0 15.13 -0.15 15.28 0.0
 CUBOID 0 1 15.305 -0.025 15.155 -0.175 15.305 -0.025
 UNIT 7
 COM='FUEL BOX 15.28 CM ON A SIDE WITH .15 CM WALLS .05CM STACKING VOID'
 CUBOID 1 1 6P7.49
 CUBOID 2 1 6P7.64
 CUBOID 0 1 6P7.6650
 UNIT 34
 COM='ALUMINUM WEIGHT DISTRIBUTION PLATE FOR SPECIAL BOX'
 CUBOID 0 1 9.80 0.0 3.750 0.0 0.16 0.0
 CUBOID 7 1 15.33 0.0 9.54 -5.79 0.16 0.0
 UNIT 35
 COM='ALUMINUM WEIGHT DISTRIBUTION PLATE FOR BOXES'
 CUBOID 7 1 4P7.665 0.16 0.0
 UNIT 9
 COM='NORTH SPLIT TABLE CORE'
 ARRAY 1 3*0.0
 CUBOID 0 1 30.66 -0.94 77.5 0.0 83.475 0.0
 UNIT 10
 COM='SOUTH SPLIT TABLE CORE'
 ARRAY 2 3*0.0
 CUBOID 0 1 49.4 0.0 77.5 0.0 83.475 0.0
 UNIT 11
 COM='PLEXIGLASS REFLECTOR SHEET WITHOUT TRIS, NORTH BOTTOM REFLECTOR'
 CUBOID 4 1 2P15.8000 2P38.7500 2P0.6150
 UNIT 12
 COM='PLEXIGLASS REFLECTOR SHEET WITH TRIS, NORTH BOTTOM REFLECTOR'
 CUBOID 5 1 2P15.8000 2P38.7500 2P0.6150
 UNIT 13
 COM='UPPER PORTION NORTH BOTTOM REFLECTOR WITH TRIS'
 CUBOID 5 1 2P15.8 2P38.75 2P8.24
 UNIT 14
 COM='LOWER PORTION NORTH BOTTOM REFLECTOR WITH TRIS'
 CUBOID 5 1 2P15.8 2P38.75 2P3.69
 UNIT 15
 COM='NORTH BOTTOM REFLECTOR INCLUDES REGULAR AND TRIS'
 ARRAY 3 3*0.0
 UNIT 16
 COM='PLEXIGLAS SHEET BOTTOM SOUTH REFLECTOR WITHOUT TRIS'
 CUBOID 0 1 2P5.1 2P2.5 2P0.6150
 CUBOID 4 1 44.3 -5.1 2P38.75 2P0.615
 UNIT 17
 COM='PLEXIGLAS SHEET BOTTOM SOUTH REFLECTOR WITH TRIS'
 CUBOID 0 1 2P5.1 2P2.5 2P0.6150
 CUBOID 5 1 44.3 -5.1 2P38.75 2P0.6150
 UNIT 18
 COM='LOWER PORTION SOUTH BOTTOM REFLECTOR WITH TRIS'
 CUBOID 0 1 2P5.1 2P2.5 2P8.855
 CUBOID 5 1 44.3 -5.1 2P38.75 2P8.855
 UNIT 19
 COM='SOUTH BOTTOM REFLECTOR WITH REGULAR AND TRIS'
 ARRAY 4 3*0.0
 UNIT 20
 COM='EAST AND WEST REFLECTORS FOR NORTH REFLECTOR WITH TRIS'
 CUBOID 5 1 2P15.8 2P12.65 2P54.2825

```

UNIT 21
COM='ARRAY FOR EAST AND WEST REFLECTORS FOR NORTH REFLECTOR'
ARRAY 5 3*0.0
UNIT 22
COM='EAST AND WEST REFLECTORS FOR SOUTH REFLECTOR WITH TRIS'
CUBOID 5 1 2P24.700 2P12.65 2P54.2825
UNIT 23
COM='ARRAY FOR EAST AND WEST REFLECTORS FOR SOUTH REFLECTOR'
ARRAY 6 3*0.0
UNIT 24
COM='NORTH TOP REFLECTOR WITH TRIS'
CUBOID 5 1 2P28.35 2P64.05 2P12.15
UNIT 25
COM='ARRAY FOR NORTH TOP REFLECTOR'
ARRAY 7 3*0.0
UNIT 26
COM='SOUTH TOP REFLECTOR WITH TRIS'
CUBOID 0 1 2P5.1 2P2.5 2P12.15
CUBOID 5 1 69.4 -5.1 2P64.05 2P12.15
UNIT 27
COM='ARRAY FOR SOUTH TOP REFLECTOR'
ARRAY 8 3*0.0
UNIT 28
COM='NORTH END REFLECTOR 9.8CM PORTION WITHOUT TRIS'
CUBOID 4 1 2P4.9000 2P64.0500 2P54.2825
UNIT 29
COM='NORTH END REFLECTOR 5.2 CM PORTION WITH TRIS'
CUBOID 5 1 2P2.6 2P64.0500 2P54.2825
UNIT 30
COM='NORTH END REFLECTOR 10.1 CM PORTION WITHOUT TRIS'
CUBOID 4 1 2P5.05 2P64.05 2P54.2825
UNIT 31
COM='ARRAY FOR NORTH END REFLECTOR'
ARRAY 9 3*0.0
UNIT 32
COM='SOUTH END REFLECTOR'
CUBOID 5 1 2P12.55 2P64.05 2P54.2825
UNIT 33
COM='ARRAY FOR SOUTH END REFLECTOR'
ARRAY 10 3*0.0
UNIT 38
COM='NORTH CORE WITH BOTTOM REFLECTOR'
ARRAY 13 3* 0.0
UNIT 39
COM='NORTH CORE WITH EAST AND WEST REFLECTOR'
ARRAY 14 3*0.0
UNIT 40
COM='NORTH CORE WITH END REFLECTOR'
ARRAY 15 3*0.0
UNIT 42
COM='NORTH CORE WITH TOP REFLECTOR'
ARRAY 16 3*0.0
UNIT 48
COM='SOUTH CORE WITH BOTTOM REFLECTORS'
ARRAY 20 3*0.0
UNIT 49
COM='SOUTH CORE WITH EAST WEST REFLECTORS'
ARRAY 21 3*0.0
UNIT 50
COM='SOUTH CORE END REFLECTOR'
ARRAY 22 3*0.0
UNIT 52
COM='SOUTH CORE WITH TOP REFLECTOR'
ARRAY 23 3*0.0
UNIT 54
COM='AIR GAP'
CUBOID 0 1 0.942 0.0 64.475 -63.625 69.13 -63.735
GLOBAL
UNIT 55
COM='TOTAL'
ARRAY 25 3*0.0
UNIT 56
COM='COMBINATION OF TWO REGULAR FUEL BOXES'
ARRAY 28 3*0.0
UNIT 57
COM='COMBINATION OF REGULAR FUEL BOX AND SPECIAL FUEL BOX'
ARRAY 29 3*0.0
UNIT 58
COM='COMBINATION OF TWO REGULAR WEIGHT DISTRIBUTION PLATES'
ARRAY 30 3*0.0
UNIT 59
COM='COMBINATION OF REGULAR AND SPECIAL WEIGHT DISTRIBUTION PLATES'
ARRAY 31 3*0.0
UNIT 60
COM='NORTH CORE SOLUTION DRIVER'
CUBOID 8 1 2P7.5 2P14.9 3.710 -7.5
CUBOID 0 1 2P7.5 2P14.9 2P7.5

```



```

CUBOID 9 1 2P7.65 2P15.05 2P7.65
CUBOID 0 1 2P7.665 2P15.33 2P7.665
UNIT 61
COM='NORTH CORE SOLUTION DRIVER'
CUBOID 8 1 2P7.5 2P14.9 3.630 -7.5
CUBOID 0 1 2P7.5 2P14.9 2P7.5
CUBOID 9 1 2P7.65 2P15.05 2P7.65
CUBOID 0 1 2P7.665 2P15.33 2P7.665
END GEOMETRY
READ ARRAY
ARA=1 NUX=2 NUY=4 NUZ=9
COM='NORTH SPLIT TABLE CORE'
FILL 2R7 2R56 4R7
      2R35 2R58 4R35
      2R7 2R56 4R7
      2R35 2R58 4R35
      2R7 56 60 4R7
      2R35 2R58 4R35
      2R7 2R56 4R7
      2R35 2R58 4R35
      2R7 2R56 4R7
END FILL
ARA=2 NUX=3 NUY=4 NUZ=9
COM='SOUTH SPLIT TABLE CORE'
FILL 3R7 3R56 6R7
      3R35 3R58 6R35
      3R7 3R56 6R7
      3R35 3R58 6R35
      3R7 61 56 56 6R7
      3R35 3R58 6R35
      3R7 57 56 56 6R7
      3R35 59 58 58 6R35
      3R7 57 56 56 6R7
END FILL
ARA=3 NUX=1 NUY=1 NUZ=3
COM='NORTH BOTTOM REFLECTOR'
FILL 14 11 13 END FILL
ARA=4 NUX=1 NUY=1 NUZ=7
COM='SOUTH BOTTOM REFLECTOR'
FILL 18 16 17 16 16 17 17 END FILL
ARA=5 NUX=1 NUY=1 NUZ=1
COM='EAST AND WEST WALLS OF NORTH REFLECTOR'
FILL 20 END FILL
ARA=6 NUX=1 NUY=1 NUZ=1
COM='EAST AND WEST WALLS OF SOUTH REFLECTOR'
FILL 22 END FILL
ARA=7 NUX=1 NUY=1 NUZ=1
COM='ARRAY FOR NORTH TOP REFLECTOR'
FILL 24 END FILL
ARA=8 NUX=1 NUY=1 NUZ=1
COM='ARRAY FOR SOUTH TOP REFLECTOR'
FILL 26 END FILL
ARA=9 NUX=3 NUY=1 NUZ=1
COM='ARRAY FOR NORTH END REFLECTOR'
FILL 28 29 30 END FILL
ARA=10 NUX=1 NUY=1 NUZ=1
COM='ARRAY FOR SOUTH END REFLECTOR'
FILL 32 END FILL
ARA=13 NUX=1 NUY=1 NUZ=2
COM='COMBINATION OF NORTH CORE WITH BOTTOM REFLECTOR'
FILL 15 9 END FILL
ARA=14 NUX=1 NUY=3 NUZ=1
COM='NORTH CORE WITH SIDE REFLECTORS'
FILL 21 38 21 END FILL
ARA=15 NUX=2 NUY=1 NUZ=1
COM='NORTH CORE WITH END REFLECTOR'
FILL 31 39 END FILL
ARA=16 NUX=1 NUY=1 NUZ=2
COM='NORTH CORE WITH TOP REFLECTOR'
FILL 40 25 END FILL
ARA=20 NUX=1 NUY=1 NUZ=2
COM='SOUTH CORE WITH BOTTOM REFLECTOR'
FILL 19 10 END FILL
ARA=21 NUX=1 NUY=3 NUZ=1
COM='SOUTH CORE WITH EAST WEST REFLECTORS'
FILL 23 48 23 END FILL
ARA=22 NUX=2 NUY=1 NUZ=1
COM='SOUTH CORE WITH END REFLECTOR'
FILL 49 33 END FILL
ARA=23 NUX=1 NUY=1 NUZ=2
COM='COMBINATION OF CORE WITH TOP REFLECTOR'
FILL 50 27 END FILL
ARA=25 NUX=3 NUY=1 NUZ=1
COM='TOTAL'
FILL 42 54 52 END FILL
ARA=26 NUX=3 NUY=1 NUZ=1
COM='ASSEMBLY OF FUEL BOX FRONT AND REAR'

```

```

FILL 2 1 3 END FILL
ARA=27 NUX=1 NUY=1 NUZ=3
COM='ASSEMBLY OF FUEL BOX TOP AND BOTTOM'
FILL 5 4 5 END FILL
ARA=28 NUX=1 NUY=2 NUZ=1
COM='COMBINATION OF TWO FUEL BOXES'
FILL 7 7 END FILL
ARA=29 NUX=1 NUY=2 NUZ=1
COM='COMBINATION OF SPECIAL AND REGULAR FUEL BOXES'
FILL 7 6 END FILL
ARA=30 NUX=1 NUY=2 NUZ=1
COM='COMBINATION OF TWO WEIGHT DISTRIBUTION PLATES'
FILL 35 35 END FILL
ARA=31 NUX=1 NUY=2 NUZ=1
COM='COMBINATION OF SPECIAL AND REGULAR WEIGHT DISTRIBUTION PLATES'
FILL 35 34 END FILL
END ARRAY
READ PLOT TTL='YZ SLICE OF SOUTH CORE FIRST ROW'
XUL=64.319 YUL=40.000 ZUL=72.000
XLR=64.319 YLR=72.000 ZLR=56.000
VAX=1 WDN=-1 MAX=130 NCH='012345678'END
TTL='XZ SLICE OF SPHERE CUBOID'
XUL=56.0 YUL=63.625 ZUL=71.735
XLR=72.0 YLR=63.625 ZLR=55.735
UAX=1 WDN=-1 MAX=130 NCH='012345678'
END PLOT
READ START NST=1 XSM=41.37 XSP=72.894 YSM=40.63 YSP=71.29
ZSM=56.071 ZSP=71.4 END START
END DATA
END

```

```

VALIDATION CASE (CAR08 )
=CSAS25
ROCKY FLATS CRITICALS NUREG/CR-0674 EXPERIMENT NUMBER ? (27 GROUP MODEL)
' FUEL CUBE 15.28 CM, U(4.46)308 @ H/U=0.77, LOW CONC. SOLUTION DRIVEN
27GROUPNDF4 INFHOMMEDIUM
U308 1 5.4078E-1 293.0 92234 0.03 92235 4.46 92236 0.08 92238 95.43 END
H2O 1 8.9514E-2 END
ARBM-BAGGIE 1.0 3 0 0 0 1001 14.01 6012 84.9 8016 1.20 1 1.9134E-2
END
ARBM-AL1100 1.0 3 0 0 1 13027 99.18 26000 0.5 29000 0.2 2 9.5390E-1
END
ARBM-TAPE(VINYL) 1.0 7 0 0 0 1001 5.92 6012 45.91 8016 10.82 17000
25.73 20000 6.9 22000 1.6 82000 1.1 2 1.1115E-2 END
ARBM-TAPE(MYLAR) 1.0 3 0 0 0 1001 6.83 6012 65.50 8016 27.02 2
1.7491E-2 END
ARBM-MODERATOR 1.185 3 0 0 0 1001 7.83 6012 59.49 8016 32.48 3 END
ARBM-PLEX(REG) 1.0 3 0 0 0 1001 7.84 6012 59.59 8016 32.23 4
1.1773 END
ARBM-PLEX(PAPER) 1.0 3 0 0 0 1001 6.48 6012 42.17 8016 49.5 4
3.7534E-3 END
ARBM-PLEX(GLUE) 1.0 3 0 0 0 1001 11.67 6012 86.29 8016 1.20 4
1.1648E-3 END
ARBM-PLEX(TRIS) 1.0 8 0 0 1 1001 7.16 6012 52.03 7014 0.16 8016 29.82
15031 1.02 17000 1.81 35079 4.260 35081 2.840 5 1.2757 END
ARBM-PLEX(PAPER) 1.0 3 0 0 0 1001 6.48 6012 42.17 8016 49.5 5
3.7534E-3 END
ARBM-PLEX(GLUE) 1.0 3 0 0 0 1001 11.67 6012 86.29 8016 1.20 5
1.1648E-3 END
ARBM-FILLER 1.185 3 0 0 0 1001 7.83 6012 59.49 8016 32.48 6 0.7 END
' THIS MATERIAL IS ACTUALLY MODERATOR ADJUSTED FOR THE VOLUME
' FRACTION OF THE VOID FILLED BETWEEN CORE AND REFLECTOR.
ARBM-AL1100 1.0 3 0 0 1 13027 99.18 26000 0.5 29000 0.2 7 2.715 END
SOLNUO2(NO3)2 8 86.42 0.149 1.0 293.0 92234 1.022 92235 93.172
92236 0.434 92238 5.372 END
SS304 9 1.0 END
END COMP
ROCKY FLATS CRITICALS NUREG/CR-0674 EXPERIMENT NUMBER ? (27 GROUP MODEL)
' FUEL CUBE 15.28 CM, U(4.46)308 @ H/U=0.77, LOW CONC. SOLUTION DRIVEN
READ PARM NPG=600 NUB=YES FDN=YES PLT=NO END PARM
READ GEOM
UNIT 1
COM='FUEL BOX WITH VOID AND PART OF AL BOX'
CUBOID 0 1 9.80 0.0 3.75 0.0 14.98 0.0
CUBOID 2 1 9.95 0.0 3.90 -0.15 14.98 0.0
CUBOID 1 1 14.98 0.0 9.365 -5.615 14.98 0.0
UNIT 2
COM='FRONT OF FUEL BOX'
CUBOID 2 1 0.15 0.0 5.615 0.0 14.98 0.0
CUBOID 0 1 0.15 0.0 9.365 0.0 14.98 0.0
CUBOID 2 1 0.15 0.0 14.98 0.0 14.98 0.0
UNIT 3
COM='REAR OF FUEL BOX'
CUBOID 2 1 0.15 0.0 14.98 0.0 14.98 0.0
UNIT 4
COM='ARRAY TO ASSEMBLE PART OF BOX'
ARRAY 26 3*0

```

```

UNIT 5
COM='TOP AND BOTTOM OF BOX'
CUBOID 0 1 9.80 0.0 3.750 0.0 0.15 0.0
CUBOID 2 1 15.28 0.0 9.365 -5.615 0.15 0.0
GLOBAL
UNIT 6
COM='ARRAY TO ASSEMBLE TOP AND BOTTOM'
ARRAY 27 3*0
CUBOID 2 1 15.28 0.0 15.13 -0.15 15.28 0.0
CUBOID 0 1 15.305 -0.025 15.155 -0.175 15.305 -0.025
UNIT 7
COM='FUEL BOX 15.28 CM ON A SIDE WITH .15 CM WALLS .05CM STACKING VOID'
CUBOID 1 1 6P7.49
CUBOID 2 1 6P7.64
CUBOID 0 1 6P7.6650
UNIT 34
COM='ALUMINUM WEIGHT DISTRIBUTION PLATE FOR SPECIAL BOX'
CUBOID 0 1 9.80 0.0 3.750 0.0 0.16 0.0
CUBOID 7 1 15.33 0.0 9.54 -5.79 0.16 0.0
UNIT 35
COM='ALUMINUM WEIGHT DISTRIBUTION PLATE FOR BOXES'
CUBOID 7 1 4P7.665 0.16 0.0
UNIT 9
COM='NORTH SPLIT TABLE CORE'
ARRAY 1 3*0.0
CUBOID 0 1 30.66 -0.94 77.5 0.0 83.475 0.0
UNIT 10
COM='SOUTH SPLIT TABLE CORE'
ARRAY 2 3*0.0
CUBOID 0 1 49.4 0.0 77.5 0.0 83.475 0.0
UNIT 11
COM='PLEXIGLASS REFLECTOR SHEET WITHOUT TRIS, NORTH BOTTOM REFLECTOR'
CUBOID 4 1 2P15.8000 2P38.7500 2P0.6150
UNIT 12
COM='PLEXIGLASS REFLECTOR SHEET WITH TRIS, NORTH BOTTOM REFLECTOR'
CUBOID 5 1 2P15.8000 2P38.7500 2P0.6150
UNIT 13
COM='UPPER PORTION NORTH BOTTOM REFLECTOR WITH TRIS'
CUBOID 5 1 2P15.8 2P38.75 2P8.24
UNIT 14
COM='LOWER PORTION NORTH BOTTOM REFLECTOR WITH TRIS'
CUBOID 5 1 2P15.8 2P38.75 2P3.69
UNIT 15
COM='NORTH BOTTOM REFLECTOR INCLUDES REGULAR AND TRIS'
ARRAY 3 3*0.0
UNIT 16
COM='PLEXIGLAS SHEET BOTTOM SOUTH REFLECTOR WITHOUT TRIS'
CUBOID 0 1 2P5.1 2P2.5 2P0.6150
CUBOID 4 1 44.3 -5.1 2P38.75 2P0.615
UNIT 17
COM='PLEXIGLAS SHEET BOTTOM SOUTH REFLECTOR WITH TRIS'
CUBOID 0 1 2P5.1 2P2.5 2P0.6150
CUBOID 5 1 44.3 -5.1 2P38.75 2P0.6150
UNIT 18
COM='LOWER PORTION SOUTH BOTTOM REFLECTOR WITH TRIS'
CUBOID 0 1 2P5.1 2P2.5 2P8.855
CUBOID 5 1 44.3 -5.1 2P38.75 2P8.855
UNIT 19
COM='SOUTH BOTTOM REFLECTOR WITH REGULAR AND TRIS'
ARRAY 4 3*0.0
UNIT 20
COM='EAST AND WEST REFLECTORS FOR NORTH REFLECTOR WITH TRIS'
CUBOID 5 1 2P15.8 2P12.65 2P54.2825
UNIT 21
COM='ARRAY FOR EAST AND WEST REFLECTORS FOR NORTH REFLECTOR'
ARRAY 5 3*0.0
UNIT 22
COM='EAST AND WEST REFLECTORS FOR SOUTH REFLECTOR WITH TRIS'
CUBOID 5 1 2P24.700 2P12.65 2P54.2825
UNIT 23
COM='ARRAY FOR EAST AND WEST REFLECTORS FOR SOUTH REFLECTOR'
ARRAY 6 3*0.0
UNIT 24
COM='NORTH TOP REFLECTOR WITH TRIS'
CUBOID 5 1 2P28.35 2P64.05 2P12.15
UNIT 25
COM='ARRAY FOR NORTH TOP REFLECTOR'
ARRAY 7 3*0.0
UNIT 26
COM='SOUTH TOP REFLECTOR WITH TRIS'
CUBOID 0 1 2P5.1 2P2.5 2P12.15
CUBOID 5 1 69.4 -5.1 2P64.05 2P12.15
UNIT 27
COM='ARRAY FOR SOUTH TOP REFLECTOR'
ARRAY 8 3*0.0

```

```

UNIT 28
COM='NORTH END REFLECTOR 9.8CM PORTION WITHOUT TRIS'
CUBOID 4 1 2P4.9000 2P64.0500 2P54.2825
UNIT 29
COM='NORTH END REFLECTOR 5.2 CM PORTION WITH TRIS'
CUBOID 5 1 2P2.6 2P64.0500 2P54.2825
UNIT 30
COM='NORTH END REFLECTOR 10.1 CM PORTION WITHOUT TRIS'
CUBOID 4 1 2P5.05 2P64.05 2P54.2825
UNIT 31
COM='ARRAY FOR NORTH END REFLECTOR'
ARRAY 9 3*0.0
UNIT 32
COM='SOUTH END REFLECTOR'
CUBOID 5 1 2P12.55 2P64.05 2P54.2825
UNIT 33
COM='ARRAY FOR SOUTH END REFLECTOR'
ARRAY 10 3*0.0
UNIT 38
COM='NORTH CORE WITH BOTTOM REFLECTOR'
ARRAY 13 3* 0.0
UNIT 39
COM='NORTH CORE WITH EAST AND WEST REFLECTOR'
ARRAY 14 3*0.0
UNIT 40
COM='NORTH CORE WITH END REFLECTOR'
ARRAY 15 3*0.0
UNIT 42
COM='NORTH CORE WITH TOP REFLECTOR'
ARRAY 16 3*0.0
UNIT 48
COM='SOUTH CORE WITH BOTTOM REFLECTORS'
ARRAY 20 3*0.0
UNIT 49
COM='SOUTH CORE WITH EAST WEST REFLECTORS'
ARRAY 21 3*0.0
UNIT 50
COM='SOUTH CORE END REFLECTOR'
ARRAY 22 3*0.0
UNIT 52
COM='SOUTH CORE WITH TOP REFLECTOR'
ARRAY 23 3*0.0
UNIT 54
COM='AIR GAP'
CUBOID 0 1 0.912 0.0 64.475 -63.625 69.13 -63.735
GLOBAL
UNIT 55
COM='TOTAL'
ARRAY 25 3*0.0
UNIT 56
COM='COMBINATION OF TWO REGULAR FUEL BOXES'
ARRAY 28 3*0.0
UNIT 57
COM='COMBINATION OF REGULAR FUEL BOX AND SPECIAL FUEL BOX'
ARRAY 29 3*0.0
UNIT 58
COM='COMBINATION OF TWO REGULAR WEIGHT DISTRIBUTION PLATES'
ARRAY 30 3*0.0
UNIT 59
COM='COMBINATION OF REGULAR AND SPECIAL WEIGHT DISTRIBUTION PLATES'
ARRAY 31 3*0.0
UNIT 60
COM='NORTH CORE SOLUTION DRIVER'
CUBOID 8 1 2P7.5 2P14.9 5.374 -7.5
CUBOID 0 1 2P7.5 2P14.9 2P7.5
CUBOID 9 1 2P7.65 2P15.05 2P7.65
CUBOID 0 1 2P7.665 2P15.33 2P7.665
UNIT 61
COM='NORTH CORE SOLUTION DRIVER'
CUBOID 8 1 2P7.5 2P14.9 5.328 -7.5
CUBOID 0 1 2P7.5 2P14.9 2P7.5
CUBOID 9 1 2P7.65 2P15.05 2P7.65
CUBOID 0 1 2P7.665 2P15.33 2P7.665
END GEOMETRY
READ ARRAY
ARA=1 NUX=2 NUY=4 NUZ=9
COM='NORTH SPLIT TABLE CORE'
FILL 2R7 2R56 4R7
      2R35 2R58 4R35
      2R7 2R56 4R7
      2R35 2R58 4R35
      2R7 56 60 4R7
      2R35 2R58 4R35
      2R7 2R56 4R7
      2R35 2R58 4R35
      2R7 2R56 4R7
END FILL

```

```

ARA=2  NUX=3  NUY=4  NUZ=9
COM='SOUTH SPLIT TABLE CORE'
FILL  3R7  3R56  6R7
      3R35 3R58  6R35
      3R7  3R56  6R7
      3R35 3R58  6R35
      3R7  61 56 56 6R7
      3R35 3R58  6R35
      3R7  57 56 56 6R7
      3R35 59 58 58 6R35
      3R7  57 56 56 6R7
END FILL
ARA=3  NUX=1  NUY=1  NUZ=3
COM='NORTH BOTTOM REFLECTOR'
FILL  14 11 13  END FILL
ARA=4  NUX=1  NUY=1  NUZ=7
COM='SOUTH BOTTOM REFLECTOR'
FILL  18 16 17 16 16 17 17  END FILL
ARA=5  NUX=1  NUY=1  NUZ=1
COM='EAST AND WEST WALLS OF NORTH REFLECTOR'
FILL  20  END FILL
ARA=6  NUX=1  NUY=1  NUZ=1
COM='EAST AND WEST WALLS OF SOUTH REFLECTOR'
FILL  22  END FILL
ARA=7  NUX=1  NUY=1  NUZ=1
COM='ARRAY FOR NORTH TOP REFLECTOR'
FILL  24  END FILL
ARA=8  NUX=1  NUY=1  NUZ=1
COM='ARRAY FOR SOUTH TOP REFLECTOR'
FILL  26  END FILL
ARA=9  NUX=3  NUY=1  NUZ=1
COM='ARRAY FOR NORTH END REFLECTOR'
FILL  28 29 30  END FILL
ARA=10 NUX=1  NUY=1  NUZ=1
COM='ARRAY FOR SOUTH END REFLECTOR'
FILL  32  END FILL
ARA=13 NUX=1  NUY=1  NUZ=2
COM='COMBINATION OF NORTH CORE WITH BOTTOM REFLECTOR'
FILL  15 9  END FILL
ARA=14 NUX=1  NUY=3  NUZ=1
COM='NORTH CORE WITH SIDE REFLECTORS'
FILL  21 38 21  END FILL
ARA=15 NUX=2  NUY=1  NUZ=1
COM='NORTH CORE WITH END REFLECTOR'
FILL  31 39  END FILL
ARA=16 NUX=1  NUY=1  NUZ=2
COM='NORTH CORE WITH TOP REFLECTOR'
FILL  40 25  END FILL
ARA=20 NUX=1  NUY=1  NUZ=2
COM='SOUTH CORE WITH BOTTOM REFLECTOR'
FILL  19 10  END FILL
ARA=21 NUX=1  NUY=3  NUZ=1
COM='SOUTH CORE WITH EAST WEST REFLECTORS'
FILL  23 48 23  END FILL
ARA=22 NUX=2  NUY=1  NUZ=1
COM='SOUTH CORE WITH END REFLECTOR'
FILL  49 33  END FILL
ARA=23 NUX=1  NUY=1  NUZ=2
COM='COMBINATION OF CORE WITH TOP REFLECTOR'
FILL  50 27  END FILL
ARA=25 NUX=3  NUY=1  NUZ=1
COM='TOTAL'
FILL  42 54 52  END FILL
ARA=26 NUX=3  NUY=1  NUZ=1
COM='ASSEMBLY OF FUEL BOX FRONT AND REAR'
FILL  2 1 3  END FILL
ARA=27 NUX=1  NUY=1  NUZ=3
COM='ASSEMBLY OF FUEL BOX TOP AND BOTTOM'
FILL  5 4 5  END FILL
ARA=28 NUX=1  NUY=2  NUZ=1
COM='COMBINATION OF TWO FUEL BOXES'
FILL  7 7  END FILL
ARA=29 NUX=1  NUY=2  NUZ=1
COM='COMBINATION OF SPECIAL AND REGULAR FUEL BOXES'
FILL  7 6  END FILL
ARA=30 NUX=1  NUY=2  NUZ=1
COM='COMBINATION OF TWO WEIGHT DISTRIBUTION PLATES'
FILL  35 35  END FILL
ARA=31 NUX=1  NUY=2  NUZ=1
COM='COMBINATION OF SPECIAL AND REGULAR WEIGHT DISTRIBUTION PLATES'
FILL  35 34  END FILL
END ARRAY
READ PLOT TTL='YZ SLICE OF SOUTH CORE FIRST ROW'
XUL=64.319 YUL=40.000 ZUL=72.000
XLR=64.319 YLR=72.000 ZLR=56.000
VAX=1  WDN=-1  MAX=130  NCH='012345678' END
TTL='XZ SLICE OF SPHERE CUBOID'

```

```

XUL=56.0 YUL=63.625 ZUL=71.735
XLR=72.0 YLR=63.625 ZLR=55.735
UAX=1 WDN=-1 NAX=130 NCH='012345678'
END PLOT
READ START NST=1 XSM=41.37 XSP=72.894 YSM=40.63 YSP=71.29
ZSM=56.071 ZSP=71.4 END START
END DATA
END

VALIDATION CASE (CAR11 )
=CSAS25
ROCKY FLATS CRITICALS NUREG/CR-1653 EXPERIMENT A (27 GROUP)
' 48 FUEL CANS 2.44 CM MODERATOR GEE.HU125.DATA(OPT)
27GROUPNDF4 LATTICECELL
U308 1 5.4078E-1 293.0 92234 0.03 92235 4.46 92236 0.08 92238 95.43 END
H2O 1 1.5627E-1 END
ARB-M-BAGGIE 1.0 3 0 0 0 1001 14.01 6012 84.9 8016 1.20 1 1.9134E-2
END
ARB-M-AL1100 1.0 3 0 0 1 13027 99.18 26000 0.5 29000 0.2 2 9.5390E-1
END
ARB-M-TAPE(VINYL) 1.0 7 0 0 0 1001 5.92 6012 45.91 8016 10.82 17000
25.73 20000 6.9 22000 1.6 82000 1.1 2 1.1115E-2 END
ARB-M-TAPE(MYLAR) 1.0 3 0 0 0 1001 6.83 6012 65.50 8016 27.02 2
1.7491E-2 END
ARB-M-MODERATOR 1.185 3 0 0 0 1001 7.83 6012 59.49 8016 32.48 3 END
ARB-M-PLEX(REG) 1.0 3 0 0 0 1001 7.84 6012 59.59 8016 32.23 4
1.1773 END
ARB-M-PLEX(PAPER) 1.0 3 0 0 0 1001 6.48 6012 42.17 8016 49.5 4
3.7534E-3 END
ARB-M-PLEX(GLUE) 1.0 3 0 0 0 1001 11.67 6012 86.29 8016 1.20 4
1.1648E-3 END
ARB-M-PLEX(TRIS) 1.0 8 0 0 1 1001 7.16 6012 52.03 7014 0.16 8016 29.82
15031 1.02 17000 1.81 35079 4.260 35081 2.840 5 1.2757 END
ARB-M-PLEX(PAPER) 1.0 3 0 0 0 1001 6.48 6012 42.17 8016 49.5 5
3.7534E-3 END
ARB-M-PLEX(GLUE) 1.0 3 0 0 0 1001 11.67 6012 86.29 8016 1.20 5
1.1648E-3 END
ARB-M-FILLER 1.185 3 0 0 0 1001 7.83 6012 59.49 8016 32.48 6 .888 END
' THIS MATERIAL IS ACTUALLY MODERATOR ADJUSTED FOR THE VOLUME
' FRACTION OF THE VOID FILLED BETWEEN CORE AND REFLECTOR.
END COMP
SPHTRIANGP 19.9462 18.5857 1 3 18.9579 2 END
ROCKY FLATS CRITICALS NUREG/CR-1653 EXPERIMENT A (27 GROUP)
' 48 FUEL CANS 2.44 CM MODERATOR GEE.HU125.DATA(OPT)
READ PARM RUN=YES NPG=600 FDN=YES NUB=YES PLT=NO END PARM
READ GEOM
UNIT 1
COM='FUEL BOX 15.28 CM ON A SIDE WITH .15 CM WALLS .05CM STACKING VOID'
CUBOID 1 1 6P7.49
CUBOID 2 1 6P7.64
CUBOID 0 1 6P7.6650
UNIT 2
COM='X-FACE INTERSTITIAL MODERATOR'
CUBOID 3 1 2P1.2200 4P7.665
UNIT 3
COM='Y-FACE INTERSTITIAL MODERATOR'
CUBOID 3 1 2P7.665 2P1.2200 2P7.665
UNIT 4
COM='Z-FACE INTERSTITIAL MODERATOR'
CUBOID 3 1 4P7.665 2P1.2200
UNIT 5
COM='MORE X-FACE MODERATOR'
CUBOID 3 1 4P1.2200 2P7.665
UNIT 6
COM='MORE Y-FACE MODERATOR'
CUBOID 3 1 2P7.665 4P1.2200
UNIT 7
COM='MORE Z-FACE MODERATOR'
CUBOID 3 1 2P1.2200 2P7.665 2P1.2200
UNIT 8
COM='LAST OF INTERSTITIAL MODERATOR'
CUBOID 3 1 6P1.2200
UNIT 9
COM='NORTH SPLIT TABLE CORE'
ARRAY 1 3*0.0
UNIT 10
COM='SOUTH SPLIT TABLE CORE'
ARRAY 2 3*0.0
UNIT 11
COM='PLEXIGLASS REFLECTOR SHEET WITHOUT TRIS, NORTH BOTTOM REFLECTOR'
CUBOID 4 1 2P16.5500 2P38.7500 2P0.6150
UNIT 12
COM='PLEXIGLASS REFLECTOR SHEET WITH TRIS, NORTH BOTTOM REFLECTOR'
CUBOID 5 1 2P16.5500 2P38.7500 2P0.6150
UNIT 13
COM='UPPER PORTION NORTH BOTTOM REFLECTOR WITH TRIS'
CUBOID 5 1 2P16.550 2P38.75 2P8.24

```

```

UNIT 14
COM='LOWER PORTION NORTH BOTTOM REFLECTOR WITH TRIS'
CUBOID 5 1 2P16.550 2P38.75 2P3.69
UNIT 15
COM='NORTH BOTTOM REFLECTOR INCLUDES REGULAR AND TRIS'
ARRAY 3 3*0.0
UNIT 16
COM='PLEXIGLAS SHEET BOTTOM SOUTH REFLECTOR WITHOUT TRIS'
CUBOID 0 1 2P5.1 2P2.55 2P0.615
CUBOID 4 1 44.3 -5.1 2P38.75 2P0.615
UNIT 17
COM='PLEXIGLAS SHEET BOTTOM SOUTH REFLECTOR WITH TRIS'
CUBOID 0 1 2P5.1 2P2.55 2P0.615
CUBOID 5 1 44.3 -5.1 2P38.75 2P0.6150
UNIT 18
COM='LOWER PORTION SOUTH BOTTOM REFLECTOR WITH TRIS'
CUBOID 0 1 2P5.1 2P2.55 2P8.855
CUBOID 5 1 44.3 -5.1 2P38.75 2P8.855
UNIT 19
COM='SOUTH BOTTOM REFLECTOR WITH REGULAR AND TRIS'
ARRAY 4 3*0.0
UNIT 20
COM='EAST AND WEST REFLECTORS FOR NORTH REFLECTOR WITH TRIS'
CUBOID 5 1 2P16.550 2P12.65 2P54.2825
UNIT 21
COM='ARRAY FOR EAST AND WEST REFLECTORS FOR NORTH REFLECTOR'
ARRAY 5 3*0.0
UNIT 22
COM='EAST AND WEST REFLECTORS FOR SOUTH REFLECTOR WITH TRIS'
CUBOID 5 1 2P24.700 2P12.65 2P54.2825
UNIT 23
COM='ARRAY FOR EAST AND WEST REFLECTORS FOR SOUTH REFLECTOR'
ARRAY 6 3*0.0
UNIT 24
COM='NORTH TOP REFLECTOR WITH TRIS'
CUBOID 5 1 2P29.100 2P64.05 2P12.15
UNIT 25
COM='ARRAY FOR NORTH TOP REFLECTOR'
ARRAY 7 3*0.0
UNIT 26
COM='SOUTH TOP REFLECTOR WITH TRIS'
CUBOID 0 1 2P5.1 2P2.55 2P12.15
CUBOID 5 1 69.4 -5.1 2P64.05 2P12.15
UNIT 27
COM='ARRAY FOR SOUTH TOP REFLECTOR'
ARRAY 8 3*0.0
UNIT 28
COM='NORTH END REFLECTOR 9.8CM PORTION WITHOUT TRIS'
CUBOID 4 1 2P4.9000 2P64.0500 2P54.2825
UNIT 29
COM='NORTH END REFLECTOR 5.2 CM PORTION WITH TRIS'
CUBOID 5 1 2P2.6 2P64.0500 2P54.2825
UNIT 30
COM='NORTH END REFLECTOR 10.1 CM PORTION WITHOUT TRIS'
CUBOID 4 1 2P5.05 2P64.05 2P54.2825
UNIT 31
COM='ARRAY FOR NORTH END REFLECTOR'
ARRAY 9 3*0.0
UNIT 32
COM='SOUTH END REFLECTOR'
CUBOID 5 1 2P12.55 2P64.05 2P54.2825
UNIT 33
COM='ARRAY FOR SOUTH END REFLECTOR'
ARRAY 10 3*0.0
UNIT 34
COM='BOTTOM MODERATING PLASTIC NORTH CORE'
CUBOID 6 1 2P16.550 2P38.7500 2P13.0500
UNIT 35
COM='TOP MODERATING PLASTIC NORTH CORE'
CUBOID 6 1 2P16.550 2P38.7500 2P3.2525
UNIT 36
ARRAY 11 3*0.0
UNIT 37
ARRAY 12 3*0.0
UNIT 38
COM='NORTH CORE WITH BOTTOM REFLECTOR'
ARRAY 13 3*0.0
UNIT 39
COM='NORTH CORE WITH EAST AND WEST REFLECTOR'
ARRAY 14 3*0.0
UNIT 40
COM='NORTH CORE WITH END REFLECTOR'
ARRAY 15 3*0.0
UNIT 41
COM='NORTH SPLIT TABLE FACEPLATE'
CUBOID 3 1 2P0.6150 2P64.0500 2P66.4325

```

```

UNIT 42
COM='NORTH CORE WITH TOP REFLECTOR'
ARRAY 16 3*0.0
UNIT 43
COM='NORTH CORE WITH FACEPLATE'
ARRAY 17 3*0.0
UNIT 44
COM='12.95 CM THICK MODERATOR SOUTH CORE'
CUBOID 6 1 2P23.924 2P6.475 2P40.183
UNIT 45
COM='2.95 THICK MODERATOR SOUTH CORE'
CUBOID 6 1 2P23.924 2P38.5285 2P1.475
UNIT 46
COM='COMBINATION OF CORE WITH 12.95 THICK MODERATOR'
ARRAY 18 3*0.0
UNIT 47
COM='COMBINATION OF CORE WITH 2.95 THICK MODERATOR'
ARRAY 19 3*0.0
UNIT 48
COM='SOUTH CORE WITH EAST WEST REFLECTORS'
ARRAY 20 3*0.0
UNIT 49
COM='SOUTH CORE WITH EAST WEST REFLECTORS'
ARRAY 21 3*0.0
UNIT 50
COM='SOUTH CORE END REFLECTOR'
ARRAY 22 3*0.0
UNIT 51
COM='FACEPLATE FOR SOUTH SPLIT TABLE'
CUBOID 3 1 2P0.4620 2P64.0500 2P66.4325
UNIT 52
COM='SOUTH CORE WITH TOP REFLECTOR'
ARRAY 23 3*0.0
UNIT 53
COM='SOUTH CORE WITH FACEPLATE'
ARRAY 24 3*0.0
UNIT 54
COM='AIR GAP'
CUBOID 0 1 2P0.1550 2P64.0500 2P66.4325
GLOBAL
UNIT 55
COM='TOTAL'
ARRAY 25 3*0.0
UNIT 56
COM='EMPTY FUEL LOCATION'
CUBOID 0 1 6P7.6650
UNIT 57
COM='SIDE MODERATOR'
CUBOID 5 1 2P16.550 2P4.4300 2P25.4350
UNIT 58
COM='END MODERATOR'
CUBOID 6 1 2P8.1500 2P38.7500 2P25.4350
UNIT 59
COM='SOUTH CORE BOTTOM MODERATING PLASTIC'
CUBOID 6 1 2P24.7000 2P38.7500 2P13.0500
UNIT 60
COM='SOUTH CORE TOP MODERATING PLASTIC'
CUBOID 6 1 2P24.7000 2P38.7500 2P3.2525
UNIT 61
COM='Y-FACE MODERATOR VOID'
CUBOID 0 1 2P7.665 2P1.2200 2P7.665
UNIT 62
COM='X-FACE MODERATOR VOID'
CUBOID 0 1 2P1.2200 4P7.665
END GEOMETRY
READ ARRAY
ARA=1 NUX=3 NUY=7 NUZ=5
COM='NORTH SPLIT TABLE CORE'
FILL 1 2 1 3 5 3 2Q6 1 2 1
      4 7 4 6 8 6 2Q6 4 7 4
      1Q42
      56 2 1 61 5 3 56 2 1 61 5 3 1Q6 56 62 56 END FILL
ARA=2 NUX=3 NUY=7 NUZ=5
COM='SOUTH SPLIT TABLE CORE'
FILL 1 2 1 3 5 3 2Q6 1 2 1
      4 7 4 6 8 6 2Q6 4 7 4
      1Q42
      1 2 56 3 5 61 2Q6 56 62 56 END FILL
ARA=3 NUX=1 NUY=1 NUZ=3
COM='NORTH BOTTOM REFLECTOR'
FILL 14 11 13 END FILL
ARA=4 NUX=1 NUY=1 NUZ=7
COM='SOUTH BOTTOM REFLECTOR'
FILL 18 16 17 16 16 17 17 END FILL
ARA=5 NUX=1 NUY=1 NUZ=1
COM='EAST AND WEST WALLS OF NORTH REFLECTOR'
FILL 20 END FILL

```



```

ARA=6 NUX=1 NUY=1 NUZ=1
COM='EAST AND WEST WALLS OF SOUTH REFLECTOR'
FILL 22 END FILL
ARA=7 NUX=1 NUY=1 NUZ=1
COM='ARRAY FOR NORTH TOP REFLECTOR'
FILL 24 END FILL
ARA=8 NUX=1 NUY=1 NUZ=1
COM='ARRAY FOR SOUTH TOP REFLECTOR'
FILL 26 END FILL
ARA=9 NUX=3 NUY=1 NUZ=1
COM='ARRAY FOR NORTH END REFLECTOR'
FILL 28 29 30 END FILL
ARA=10 NUX=1 NUY=1 NUZ=1
COM='ARRAY FOR SOUTH END REFLECTOR'
FILL 32 END FILL
ARA=11 NUX=1 NUY=2 NUZ=1
COM='COMBINARION OF CORE WITH SIDE MODERATOR'
FILL 9 57 END FILL
ARA=12 NUX=1 NUY=1 NUZ=3
COM='COMBINATION OF PREVIOUS ARRAY WITH TOP AND BOTTOM MODERATOR'
FILL 34 36 35 END FILL
ARA=13 NUX=1 NUY=1 NUZ=2
COM='COMBINATION OF NORTH CORE WITH BOTTOM REFLECTOR'
FILL 15 37 END FILL
ARA=14 NUX=1 NUY=3 NUZ=1
COM='NORTH CORE WITH SIDE REFLECTORS'
FILL 21 38 21 END FILL
ARA=15 NUX=2 NUY=1 NUZ=1
COM='NORTH CORE WITH END REFLECTOR'
FILL 31 39 END FILL
ARA=16 NUX=1 NUY=1 NUZ=2
COM='NORTH CORE WITH TOP REFLECTOR'
FILL 40 25 END FILL
ARA=17 NUX=2 NUY=1 NUZ=1
COM='NORTH CORE WITH FACEPLATE'
FILL 42 41 END FILL
ARA=18 NUX=1 NUY=2 NUZ=1
COM='COMBINATION OF S. CORE WITH SIDE MODERATOR'
FILL 10 57 END FILL
ARA=19 NUX=2 NUY=1 NUZ=1
COM='COMBINATION OF CORE WITH END MODERATOR'
FILL 46 58 END FILL
ARA=20 NUX=1 NUY=1 NUZ=4
COM='SOUTH CORE WITH BOTTOM MODERATOR AND REFLECTOR'
FILL 19 59 47 60 END FILL
ARA=21 NUX=1 NUY=3 NUZ=1
COM='SOUTH CORE WITH EAST WEST REFLECTORS'
FILL 23 48 23 END FILL
ARA=22 NUX=2 NUY=1 NUZ=1
COM='SOUTH CORE WITH END REFLECTOR'
FILL 49 33 END FILL
ARA=23 NUX=1 NUY=1 NUZ=2
COM='COMBINATION OF CORE WITH TOP REFLECTOR'
FILL 50 27 END FILL
ARA=24 NUX=2 NUY=1 NUZ=1
COM='SOUTH CORE WITH FACEPLATE'
FILL 51 52 END FILL
ARA=25 NUX=3 NUY=1 NUZ=1
COM='TOTAL'
FILL 43 54 53 END FILL
END ARRAY
READ PLOT TTL='XZ SLICE OF RFP1 SHOWING MATERIAL REGIONS'
XUL=-2 YUL=64.05 ZUL=136
XLR=137 YLR=64.05 ZLR=-2
UAX=1 WDN=-1 NAX=130 NCH='0123456'END
TTL='YZ SLICE OF NORTH CORE FIRST ROW'
XUL=48 YUL=-2 ZUL=136
XLR=48 YLR=136 ZLR=-2
VAX=1 WDN=-1 NAX=130 NCH='0123456'END
TTL='YZ SLICE OF NORTH CORE SECOND ROW'
XUL=28 YUL=-2 ZUL=136
XLR=28 YLR=136 ZLR=-2
VAX=1 WDN=-1 NAX=130 NCH='0123456'END
TTL='YZ SLICE OF SOUTH CORE FIRST ROW'
XUL=62 YUL=-2 ZUL=136
XLR=62 YLR=136 ZLR=-2
VAX=1 WDN=-1 NAX=130 NCH='0123456'END
TTL='YZ SLICE OF SOUTH CORE SECOND ROW'
XUL=80 YUL=-2 ZUL=136
XLR=80 YLR=136 ZLR=-2
VAX=1 WDN=-1 NAX=130 NCH='0123456'END
END PLOT
END DATA
END

```

```

VALIDATION CASE                      (CAR13 )
=CSAS25
ROCKY FLATS CRITICALS NUREG/CR-1653 EXPERIMENT C (27 GROUP)
' 80 FUEL CANS 0.929 CM MODERATOR GEE.HU125.DATA(UND2)
27GROUPNDF4 LATTICECELL
U308 1 5.4078E-1 293.0 92234 0.03 92235 4.46 92236 0.08 92238 95.43 END
H2O 1 1.5627E-1 END
ARBM-BAGGIE 1.0 3 0 0 0 1001 14.01 6012 84.9 8016 1.20 1 1.9134E-2
END
ARBM-AL1100 1.0 3 0 0 1 13027 99.18 26000 0.5 29000 0.2 2 9.5390E-1
END
ARBM-TAPE(VINYL) 1.0 7 0 0 0 1001 5.92 6012 45.91 8016 10.82 17000
25.73 20000 6.9 22000 1.6 82000 1.1 2 1.1115E-2 END
ARBM-TAPE(MYLAR) 1.0 3 0 0 0 1001 6.83 6012 65.50 8016 27.02 2
1.7491E-2 END
ARBM-MODERATOR 1.185 3 0 0 0 1001 7.83 6012 59.49 8016 32.48 3 END
ARBM-PLEX(REG) 1.0 3 0 0 0 1001 7.84 6012 59.59 8016 32.23 4
1.1773 END
ARBM-PLEX(PAPER) 1.0 3 0 0 0 1001 6.48 6012 42.17 8016 49.5 4
3.7534E-3 END
ARBM-PLEX(GLUE) 1.0 3 0 0 0 1001 11.67 6012 86.29 8016 1.20 4
1.1648E-3 END
ARBM-PLEX(TRIS) 1.0 8 0 0 1 1001 7.16 6012 52.03 7014 0.16 8016 29.82
15031 1.02 17000 1.81 35079 4.260 35081 2.840 5 1.2757 END
ARBM-PLEX(PAPER) 1.0 3 0 0 0 1001 6.48 6012 42.17 8016 49.5 5
3.7534E-3 END
ARBM-PLEX(GLUE) 1.0 3 0 0 0 1001 11.67 6012 86.29 8016 1.20 5
1.1648E-3 END
ARBM-FILLER 1.185 3 0 0 0 1001 7.83 6012 59.49 8016 32.48 6 .854 END
' THIS MATERIAL IS ACTUALLY MODERATOR ADJUSTED FOR THE VOLUME
' FRACTION OF THE VOID FILLED BETWEEN CORE AND REFLECTOR.
END COMP
SPHTRIANGP 19.00 18.5857 1 3 18.9579 2 END
ROCKY FLATS CRITICALS NUREG/CR-1653 EXPERIMENT C (27 GROUP)
' 80 FUEL CANS 0.929 CM MODERATOR GEE.HU125.DATA(UND2)
READ PARM RUN=YES NPG=600 FDN=YES NUB=YES PLT=NO END PARM
READ GEOM
UNIT 1
COM='FUEL BOX 15.28 CM ON A SIDE WITH .15 CM WALLS .05CM STACKING VOID'
CUBOID 1 1 6P7.49
CUBOID 2 1 6P7.64
CUBOID 0 1 6P7.6650
UNIT 2
COM='X-FACE INTERSTITIAL MODERATOR'
CUBOID 3 1 2P0.4645 4P7.665
UNIT 3
COM='Y-FACE INTERSTITIAL MODERATOR'
CUBOID 3 1 2P7.665 2P0.4645 2P7.665
UNIT 4
COM='Z-FACE INTERSTITIAL MODERATOR'
CUBOID 3 1 4P7.665 2P0.4645
UNIT 5
COM='MORE X-FACE MODERATOR'
CUBOID 3 1 4P0.4645 2P7.665
UNIT 6
COM='MORE Y-FACE MODERATOR'
CUBOID 3 1 2P7.665 4P0.4645
UNIT 7
COM='MORE Z-FACE MODERATOR'
CUBOID 3 1 2P0.4645 2P7.665 2P0.4645
UNIT 8
COM='LAST OF INTERSTITIAL MODERATOR'
CUBOID 3 1 6P0.4645
UNIT 9
COM='NORTH SPLIT TABLE CORE'
ARRAY 1 3*0.0
UNIT 10
COM='SOUTH SPLIT TABLE CORE'
ARRAY 2 3*0.0
UNIT 11
COM='PLEXIGLASS REFLECTOR SHEET WITHOUT TRIS, NORTH BOTTOM REFLECTOR'
CUBOID 4 1 2P15.8000 2P38.7500 2P0.6150
UNIT 12
COM='PLEXIGLASS REFLECTOR SHEET WITH TRIS, NORTH BOTTOM REFLECTOR'
CUBOID 5 1 2P15.8000 2P38.7500 2P0.6150
UNIT 13
COM='UPPER PORTION NORTH BOTTOM REFLECTOR WITH TRIS'
CUBOID 5 1 2P15.8 2P38.75 2P8.24
UNIT 14
COM='LOWER PORTION NORTH BOTTOM REFLECTOR WITH TRIS'
CUBOID 5 1 2P15.8 2P38.75 2P3.69
UNIT 15
COM='NORTH BOTTOM REFLECTOR INCLUDES REGULAR AND TRIS'
ARRAY 3 3*0.0

```

```

UNIT 16
COM='PLEXIGLAS SHEET BOTTOM SOUTH REFLECTOR WITHOUT TRIS'
CUBOID 0 1 2P5.1 2P2.55 2P0.615
CUBOID 4 1 44.3 -5.1 2P38.75 2P0.615
UNIT 17
COM='PLEXIGLAS SHEET BOTTOM SOUTH REFLECTOR WITH TRIS'
CUBOID 0 1 2P5.1 2P2.55 2P0.615
CUBOID 5 1 44.3 -5.1 2P38.75 2P0.6150
UNIT 18
COM='LOWER PORTION SOUTH BOTTOM REFLECTOR WITH TRIS'
CUBOID 0 1 2P5.1 2P2.55 2P8.855
CUBOID 5 1 44.3 -5.1 2P38.75 2P8.855
UNIT 19
COM='SOUTH BOTTOM REFLECTOR WITH REGULAR AND TRIS'
ARRAY 4 3*0.0
UNIT 20
COM='EAST AND WEST REFLECTORS FOR NORTH REFLECTOR WITH TRIS'
CUBOID 5 1 2P15.8 2P12.65 2P54.2825
UNIT 21
COM='ARRAY FOR EAST AND WEST REFLECTORS FOR NORTH REFLECTOR'
ARRAY 5 3*0.0
UNIT 22
COM='EAST AND WEST REFLECTORS FOR SOUTH REFLECTOR WITH TRIS'
CUBOID 5 1 2P24.700 2P12.65 2P54.2825
UNIT 23
COM='ARRAY FOR EAST AND WEST REFLECTORS FOR SOUTH REFLECTOR'
ARRAY 6 3*0.0
UNIT 24
COM='NORTH TOP REFLECTOR WITH TRIS'
CUBOID 5 1 2P28.35 2P64.05 2P12.15
UNIT 25
COM='ARRAY FOR NORTH TOP REFLECTOR'
ARRAY 7 3*0.0
UNIT 26
COM='SOUTH TOP REFLECTOR WITH TRIS'
CUBOID 0 1 2P5.1 2P2.55 2P12.15
CUBOID 5 1 69.4 -5.1 2P64.05 2P12.15
UNIT 27
COM='ARRAY FOR SOUTH TOP REFLECTOR'
ARRAY 8 3*0.0
UNIT 28
COM='NORTH END REFLECTOR 9.8CM PORTION WITHOUT TRIS'
CUBOID 4 1 2P4.9000 2P64.0500 2P54.2825
UNIT 29
COM='NORTH END REFLECTOR 5.2 CM PORTION WITH TRIS'
CUBOID 5 1 2P2.6 2P64.0500 2P54.2825
UNIT 30
COM='NORTH END REFLECTOR 10.1 CM PORTION WITHOUT TRIS'
CUBOID 4 1 2P5.05 2P64.05 2P54.2825
UNIT 31
COM='ARRAY FOR NORTH END REFLECTOR'
ARRAY 9 3*0.0
UNIT 32
COM='SOUTH END REFLECTOR'
CUBOID 5 1 2P12.55 2P64.05 2P54.2825
UNIT 33
COM='ARRAY FOR SOUTH END REFLECTOR'
ARRAY 10 3*0.0
UNIT 34
COM='12.95 THICK MODERATING PLASTIC NORTH CORE'
CUBOID 6 1 2P15.7945 2P6.4750 2P32.0535
UNIT 35
COM='2.95 THICK MODERATING PLASTIC NORTH CORE'
CUBOID 6 1 2P15.7945 2P38.5285 2P1.475
UNIT 36
ARRAY 11 3*0.0
UNIT 37
ARRAY 12 3*0.0
REPLICATE 0 1 0.0 0.011 0.443 0.0 0.1590 0.0 1
UNIT 38
COM='NORTH CORE WITH BOTTOM REFLECTOR'
ARRAY 13 3* 0.0
UNIT 39
COM='NORTH CORE WITH EAST AND WEST REFLECTOR'
ARRAY 14 3*0.0
UNIT 40
COM='NORTH CORE WITH END REFLECTOR'
ARRAY 15 3*0.0
UNIT 41
COM='NORTH SPLIT TABLE FACEPLATE'
CUBOID 3 1 2P0.6150 2P64.0500 2P66.4325
UNIT 42
COM='NORTH CORE WITH TOP REFLECTOR'
ARRAY 16 3*0.0
UNIT 43
COM='NORTH CORE WITH FACEPLATE'
ARRAY 17 3*0.0

```

```

UNIT 44
COM='12.95 CM THICK MODERATOR SOUTH CORE'
CUBOID 6 1 2P23.924 2P6.475 2P32.0535
UNIT 45
COM='2.95 THICK MODERATOR SOUTH CORE'
CUBOID 6 1 2P23.924 2P38.5285 2P1.475
UNIT 46
COM='COMBINATION OF CORE WITH 12.95 THICK MODERATOR'
ARRAY 18 3*0.0
UNIT 47
COM='COMBINATION OF CORE WITH 2.95 THICK MODERATOR'
ARRAY 19 3*0.0
REPLICATE 0 1 1.552 0.0 0.4430 0.0 0.159 0.0 1
UNIT 48
COM='SOUTH CORE WITH EAST WEST REFLECTORS'
ARRAY 20 3*0.0
UNIT 49
COM='SOUTH CORE WITH EAST WEST REFLECTORS'
ARRAY 21 3*0.0
UNIT 50
COM='SOUTH CORE END REFLECTOR'
ARRAY 22 3*0.0
UNIT 51
COM='FACEPLATE FOR SOUTH SPLIT TABLE'
CUBOID 3 1 2P0.4620 2P64.0500 2P66.4325
UNIT 52
COM='SOUTH CORE WITH TOP REFLECTOR'
ARRAY 23 3*0.0
UNIT 53
COM='SOUTH CORE WITH FACEPLATE'
ARRAY 24 3*0.0
UNIT 54
COM='AIR GAP'
CUBOID 0 1 2P0.7805 2P64.0500 2P66.4325
GLOBAL
UNIT 55
COM='TOTAL'
ARRAY 25 3*0.0
UNIT 56
COM='NORTH BOTTOM MODERATOR'
CUBOID 6 1 2P15.8000 2P38.7500 2P8.1295
UNIT 57
COM='BOTTOM SOUTH MODERATOR'
CUBOID 6 1 2P24.700 2P38.75 2P8.1295
UNIT 58
COM='SOUTH REAR MODERATOR'
CUBOID 3 1
END GEOMETRY
READ ARRAY
ARA=1 NUX=3 NUY=7 NUZ=7
COM='NORTH SPLIT TABLE CORE'
FILL 1 2 1 3 5 3 2Q6 1 2 1
      4 7 4 6 8 6 2Q6 4 7 4
      2Q42
      1 2 1 3 5 3 2Q6 1 2 1 END FILL
ARA=2 NUX=5 NUY=7 NUZ=7
COM='SOUTH SPLIT TABLE CORE'
FILL 1 2 1 2 1 3 5 3 5 3 2Q10 1 2 1 2 1
      4 7 4 7 4 6 8 6 8 6 2Q10 4 7 4 7 4
      2Q70
      1 2 1 2 1 3 5 3 5 3 2Q10 1 2 1 2 1 END FILL
ARA=3 NUX=1 NUY=1 NUZ=4
COM='NORTH BOTTOM MODERATOR AND REFLECTOR'
FILL 14 11 13 56 END FILL
ARA=4 NUX=1 NUY=1 NUZ=8
COM='SOUTH BOTTOM MODERATOR AND REFLECTOR'
FILL 18 16 17 16 16 17 17 57 END FILL
ARA=5 NUX=1 NUY=1 NUZ=1
COM='EAST AND WEST WALLS OF NORTH REFLECTOR'
FILL 20 END FILL
ARA=6 NUX=1 NUY=1 NUZ=1
COM='EAST AND WEST WALLS OF SOUTH REFLECTOR'
FILL 22 END FILL
ARA=7 NUX=1 NUY=1 NUZ=1
COM='ARRAY FOR NORTH TOP REFLECTOR'
FILL 24 END FILL
ARA=8 NUX=1 NUY=1 NUZ=1
COM='ARRAY FOR SOUTH TOP REFLECTOR'
FILL 26 END FILL
ARA=9 NUX=3 NUY=1 NUZ=1
COM='ARRAY FOR NORTH END REFLECTOR'
FILL 28 29 30 END FILL
ARA=10 NUX=1 NUY=1 NUZ=1
COM='ARRAY FOR SOUTH END REFLECTOR'
FILL 32 END FILL
ARA=11 NUX=1 NUY=2 NUZ=1
COM='COMBINARION OF CORE WITH 12.95CM THICK MODERATOR'

```

```

FILL 9 34 END FILL
ARA=12 NUX=1 NUY=1 NUZ=2
COM='COMBINATION OF PREVIOUS ARRAY WITH 2.95CM THICK MODERATOR'
FILL 36 35 END FILL
ARA=13 NUX=1 NUY=1 NUZ=2
COM='COMBINATION OF NORTH CORE WITH BOTTOM REFLECTOR'
FILL 15 37 END FILL
ARA=14 NUX=1 NUY=3 NUZ=1
COM='NORTH CORE WITH SIDE REFLECTORS'
FILL 21 38 21 END FILL
ARA=15 NUX=2 NUY=1 NUZ=1
COM='NORTH CORE WITH END REFLECTOR'
FILL 31 39 END FILL
ARA=16 NUX=1 NUY=1 NUZ=2
COM='NORTH CORE WITH TOP REFLECTOR'
FILL 40 25 END FILL
ARA=17 NUX=2 NUY=1 NUZ=1
COM='NORTH CORE WITH FACEPLATE'
FILL 42 41 END FILL
ARA=18 NUX=1 NUY=2 NUZ=1
COM='COMBINATION OF S. CORE WITH 12.95 CM THICK MODERATOR'
FILL 10 44 END FILL
ARA=19 NUX=1 NUY=1 NUZ=2
COM='COMBINATION OF CORE WITH 2.95 CM THICK MODERATOR'
FILL 46 45 END FILL
ARA=20 NUX=1 NUY=1 NUZ=2
COM='SOUTH CORE WITH BOTTOM REFLECTOR'
FILL 19 47 END FILL
ARA=21 NUX=1 NUY=3 NUZ=1
COM='SOUTH CORE WITH EAST WEST REFLECTORS'
FILL 23 48 23 END FILL
ARA=22 NUX=2 NUY=1 NUZ=1
COM='SOUTH CORE WITH END REFLECTOR'
FILL 49 33 END FILL
ARA=23 NUX=1 NUY=1 NUZ=2
COM='COMBINATION OF CORE WITH TOP REFLECTOR'
FILL 50 27 END FILL
ARA=24 NUX=2 NUY=1 NUZ=1
COM='SOUTH CORE WITH FACEPLATE'
FILL 51 52 END FILL
ARA=25 NUX=3 NUY=1 NUZ=1
COM='TOTAL'
FILL 43 54 53 END FILL
END ARRAY
READ PLOT TTL='XZ SLICE OF RFP3 SHOWING MATERIAL REGIONS'
XUL=-1 YUL=64.05 ZUL=135
XLR=136 YLR=64.05 ZLR=-2
UAX=1 WDN=-1 NAX=130 NCH='0123456'END
TTL='YZ SLICE OF NORTH CORE SECOND ROW'
XUL=28 YUL=-2 ZUL=136
XLR=28 YLR=136 ZLR=-2
VAX=1 WDN=-1 NAX=130 NCH='0123456'END
TTL='YZ SLICE OF SOUTH CORE SECOND ROW'
XUL=80 YUL=-2 ZUL=136
XLR=80 YLR=136 ZLR=-2
VAX=1 WDN=-1 NAX=130 NCH='0123456'
END PLOT
END DATA
END

```

```

VALIDATION CASE (CAR15 )
=CSAS25
ROCKY FLATS CRITICALS NUREG/CR-1653 EXPERIMENT NUMBER ? (27 GROUP MODEL)
' FUEL CUBE 15.28 CM, U(4.46)308 @ H/U=1.25, HI CONC. SOLUTION DRIVEN
27GROUPNDF4 INFHOMMEDIUM
U308 1 5.4078E-1 293.0 92234 0.03 92235 4.46 92236 0.08 92238 95.43 END
H2O 1 1.5627E-1 END
ARBM-BAGGIE 1.0 3 0 0 0 1001 14.01 6012 84.9 8016 1.20 1 1.9134E-2
END
ARBM-AL1100 1.0 3 0 0 1 13027 99.18 26000 0.5 29000 0.2 2 9.5390E-1
END
ARBM-TAPE(VINYL) 1.0 7 0 0 0 1001 5.92 6012 45.91 8016 10.82 17000
25.73 20000 6.9 22000 1.6 82000 1.1 2 1.1115E-2 END
ARBM-TAPE(MYLAR) 1.0 3 0 0 0 1001 6.83 6012 65.50 8016 27.02 2
1.7491E-2 END
ARBM-MODERATOR 1.185 3 0 0 0 1001 7.83 6012 59.49 8016 32.48 3 END
ARBM-PLEX(REG) 1.0 3 0 0 0 1001 7.84 6012 59.59 8016 32.23 4
1.1773 END
ARBM-PLEX(PAPER) 1.0 3 0 0 0 1001 6.48 6012 42.17 8016 49.5 4
3.7534E-3 END
ARBM-PLEX(GLUE) 1.0 3 0 0 0 1001 11.67 6012 86.29 8016 1.20 4
1.1648E-3 END
ARBM-PLEX(TRIS) 1.0 8 0 0 1 1001 7.16 6012 52.03 7014 0.16 8016 29.82
15031 1.02 17000 1.81 35079 4.260 35081 2.840 5 1.2757 END
ARBM-PLEX(PAPER) 1.0 3 0 0 0 1001 6.48 6012 42.17 8016 49.5 5
3.7534E-3 END

```

```

ARBM-PLEX(GLUE) 1.0 3 0 0 0 1001 11.67 6012 86.29 8016 1.20 5
1.164BE-3 END
ARBM-FILLER 1.185 3 0 0 0 1001 7.83 6012 59.49 8016 32.48 6 0.7 END
/ THIS MATERIAL IS ACTUALLY MODERATOR ADJUSTED FOR THE VOLUME
/ FRACTION OF THE VOID FILLED BETWEEN CORE AND REFLECTOR.
ARBM-AL1100 1.0 3 0 0 1 13027 99.18 26000 0.5 29000 0.2 7 2.715 END
SOLNUO2(NO3)2 8 351.18 0.549 1.0 293.0 92234 1.022 92235 93.172
92236 0.434 92238 5.372 END
SS304 9 1.0 END
END COMP
ROCKY FLATS CRITICALS NUREG/CR-1653 EXPERIMENT NUMBER ? (27 GROUP MODEL)
/ FUEL CUBE 15.28 CM, U(4.46)308 @ H/U=1.25, HI CONC. SOLUTION DRIVEN
READ PARM NPG=600 NUB=YES FDN=YES PLT=NO END PARM
READ GEOM
UNIT 1
COM='FUEL BOX WITH VOID AND PART OF AL BOX'
CUBOID 0 1 9.80 0.0 3.75 0.0 14.98 0.0
CUBOID 2 1 9.95 0.0 3.90 -0.15 14.98 0.0
CUBOID 1 1 14.98 0.0 9.365 -5.615 14.98 0.0
UNIT 2
COM='FRONT OF FUEL BOX'
CUBOID 2 1 0.15 0.0 5.615 0.0 14.98 0.0
CUBOID 0 1 0.15 0.0 9.365 0.0 14.98 0.0
CUBOID 2 1 0.15 0.0 14.98 0.0 14.98 0.0
UNIT 3
COM='REAR OF FUEL BOX'
CUBOID 2 1 0.15 0.0 14.98 0.0 14.98 0.0
UNIT 4
COM='ARRAY TO ASSEMBLE PART OF BOX'
ARRAY 26 3*0
UNIT 5
COM='TOP AND BOTTOM OF BOX'
CUBOID 0 1 9.80 0.0 3.750 0.0 0.15 0.0
CUBOID 2 1 15.28 0.0 9.365 -5.615 0.15 0.0
GLOBAL
UNIT 6
COM='ARRAY TO ASSEMBLE TOP AND BOTTOM'
ARRAY 27 3*0
CUBOID 2 1 15.28 0.0 15.13 -0.15 15.28 0.0
CUBOID 0 1 15.305 -0.025 15.155 -0.175 15.305 -0.025
UNIT 7
COM='FUEL BOX 15.28 CM ON A SIDE WITH .15 CM WALLS .05CM STACKING VOID'
CUBOID 1 1 6P7.49
CUBOID 2 1 6P7.64
CUBOID 0 1 6P7.6650
UNIT 34
COM='ALUMINUM WEIGHT DISTRIBUTION PLATE FOR SPECIAL BOX'
CUBOID 0 1 9.80 0.0 3.750 0.0 0.16 0.0
CUBOID 7 1 15.33 0.0 9.54 -5.79 0.16 0.0
UNIT 35
COM='ALUMINUM WEIGHT DISTRIBUTION PLATE FOR BOXES'
CUBOID 7 1 4P7.665 0.16 0.0
UNIT 9
COM='NORTH SPLIT TABLE CORE'
ARRAY 1 3*0.0
CUBOID 0 1 30.66 -0.94 77.5 0.0 83.475 0.0
UNIT 10
COM='SOUTH SPLIT TABLE CORE'
ARRAY 2 3*0.0
CUBOID 0 1 49.4 0.0 77.5 0.0 83.475 0.0
UNIT 11
COM='PLEXIGLASS REFLECTOR SHEET WITHOUT TRIS, NORTH BOTTOM REFLECTOR'
CUBOID 4 1 2P15.8000 2P38.7500 2P0.6150
UNIT 12
COM='PLEXIGLASS REFLECTOR SHEET WITH TRIS, NORTH BOTTOM REFLECTOR'
CUBOID 5 1 2P15.8000 2P38.7500 2P0.6150
UNIT 13
COM='UPPER PORTION NORTH BOTTOM REFLECTOR WITH TRIS'
CUBOID 5 1 2P15.8 2P38.75 2P8.24
UNIT 14
COM='LOWER PORTION NORTH BOTTOM REFLECTOR WITH TRIS'
CUBOID 5 1 2P15.8 2P38.75 2P3.69
UNIT 15
COM='NORTH BOTTOM REFLECTOR INCLUDES REGULAR AND TRIS'
ARRAY 3 3*0.0
UNIT 16
COM='PLEXIGLAS SHEET BOTTOM SOUTH REFLECTOR WITHOUT TRIS'
CUBOID 0 1 2P5.1 2P2.5 2P0.6150
CUBOID 4 1 44.3 -5.1 2P38.75 2P0.615
UNIT 17
COM='PLEXIGLAS SHEET BOTTOM SOUTH REFLECTOR WITH TRIS'
CUBOID 0 1 2P5.1 2P2.5 2P0.6150
CUBOID 5 1 44.3 -5.1 2P38.75 2P0.6150
UNIT 18
COM='LOWER PORTION SOUTH BOTTOM REFLECTOR WITH TRIS'
CUBOID 0 1 2P5.1 2P2.5 2P8.855
CUBOID 5 1 44.3 -5.1 2P38.75 2P8.855

```

```

UNIT 19
COM='SOUTH BOTTOM REFLECTOR WITH REGULAR AND TRIS'
ARRAY 4 3*0.0
UNIT 20
COM='EAST AND WEST REFLECTORS FOR NORTH REFLECTOR WITH TRIS'
CUBOID 5 1 2P15.8 2P12.65 2P54.2825
UNIT 21
COM='ARRAY FOR EAST AND WEST REFLECTORS FOR NORTH REFLECTOR'
ARRAY 5 3*0.0
UNIT 22
COM='EAST AND WEST REFLECTORS FOR SOUTH REFLECTOR WITH TRIS'
CUBOID 5 1 2P24.700 2P12.65 2P54.2825
UNIT 23
COM='ARRAY FOR EAST AND WEST REFLECTORS FOR SOUTH REFLECTOR'
ARRAY 6 3*0.0
UNIT 24
COM='NORTH TOP REFLECTOR WITH TRIS'
CUBOID 5 1 2P28.35 2P64.05 2P12.15
UNIT 25
COM='ARRAY FOR NORTH TOP REFLECTOR'
ARRAY 7 3*0.0
UNIT 26
COM='SOUTH TOP REFLECTOR WITH TRIS'
CUBOID 0 1 2P5.1 2P2.5 2P12.15
CUBOID 5 1 69.4 -5.1 2P64.05 2P12.15
UNIT 27
COM='ARRAY FOR SOUTH TOP REFLECTOR'
ARRAY 8 3*0.0
UNIT 28
COM='NORTH END REFLECTOR 9.8CM PORTION WITHOUT TRIS'
CUBOID 4 1 2P4.9000 2P64.0500 2P54.2825
UNIT 29
COM='NORTH END REFLECTOR 5.2 CM PORTION WITH TRIS'
CUBOID 5 1 2P2.6 2P64.0500 2P54.2825
UNIT 30
COM='NORTH END REFLECTOR 10.1 CM PORTION WITHOUT TRIS'
CUBOID 4 1 2P5.05 2P64.05 2P54.2825
UNIT 31
COM='ARRAY FOR NORTH END REFLECTOR'
ARRAY 9 3*0.0
UNIT 32
COM='SOUTH END REFLECTOR'
CUBOID 5 1 2P12.55 2P64.05 2P54.2825
UNIT 33
COM='ARRAY FOR SOUTH END REFLECTOR'
ARRAY 10 3*0.0
UNIT 38
COM='NORTH CORE WITH BOTTOM REFLECTOR'
ARRAY 13 3*0.0
UNIT 39
COM='NORTH CORE WITH EAST AND WEST REFLECTOR'
ARRAY 14 3*0.0
UNIT 40
COM='NORTH CORE WITH END REFLECTOR'
ARRAY 15 3*0.0
UNIT 42
COM='NORTH CORE WITH TOP REFLECTOR'
ARRAY 16 3*0.0
UNIT 48
COM='SOUTH CORE WITH BOTTOM REFLECTORS'
ARRAY 20 3*0.0
UNIT 49
COM='SOUTH CORE WITH EAST WEST REFLECTORS'
ARRAY 21 3*0.0
UNIT 50
COM='SOUTH CORE END REFLECTOR'
ARRAY 22 3*0.0
UNIT 52
COM='SOUTH CORE WITH TOP REFLECTOR'
ARRAY 23 3*0.0
UNIT 54
COM='AIR GAP'
CUBOID 0 1 0.732 0.0 64.475 -63.625 69.13 -63.735
GLOBAL
UNIT 55
COM='TOTAL'
ARRAY 25 3*0.0
UNIT 56
COM='COMBINATION OF TWO REGULAR FUEL BOXES'
ARRAY 28 3*0.0
UNIT 57
COM='COMBINATION OF REGULAR FUEL BOX AND SPECIAL FUEL BOX'
ARRAY 29 3*0.0
UNIT 58
COM='COMBINATION OF TWO REGULAR WEIGHT DISTRIBUTION PLATES'
ARRAY 30 3*0.0

```

```

UNIT 59
COM='COMBINATION OF REGULAR AND SPECIAL WEIGHT DISTRIBUTION PLATES'
ARRAY 31 3*0.0
UNIT 60
COM='NORTH CORE SOLUTION DRIVER'
CUBOID 8 1 2P7.5 2P14.9 1.863 -7.5
CUBOID 0 1 2P7.5 2P14.9 2P7.5
CUBOID 9 1 2P7.65 2P15.05 2P7.65
CUBOID 0 1 2P7.665 2P15.33 2P7.665
UNIT 61
COM='SOUTH CORE SOLUTION DRIVER'
CUBOID 8 1 2P7.5 2P14.9 1.794 -7.5
CUBOID 0 1 2P7.5 2P14.9 2P7.5
CUBOID 9 1 2P7.65 2P15.05 2P7.65
CUBOID 0 1 2P7.665 2P15.33 2P7.665
END GEOMETRY
READ ARRAY
ARA=1 NUX=2 NUY=4 NUZ=9
COM='NORTH SPLIT TABLE CORE'
FILL 2R7 2R56 4R7
      2R35 2R58 4R35
      2R7 2R56 4R7
      2R35 2R58 4R35
      2R7 56 60 4R7
      2R35 2R58 4R35
      2R7 2R56 4R7
      2R35 2R58 4R35
      2R7 2R56 4R7
END FILL
ARA=2 NUX=3 NUY=4 NUZ=9
COM='SOUTH SPLIT TABLE CORE'
FILL 3R7 3R56 6R7
      3R35 3R58 6R35
      3R7 3R56 6R7
      3R35 3R58 6R35
      3R7 61 56 56 6R7
      3R35 3R58 6R35
      3R7 57 56 56 6R7
      3R35 59 58 58 6R35
      3R7 57 56 56 6R7
END FILL
ARA=3 NUX=1 NUY=1 NUZ=3
COM='NORTH BOTTOM REFLECTOR'
FILL 14 11 13 END FILL
ARA=4 NUX=1 NUY=1 NUZ=7
COM='SOUTH BOTTOM REFLECTOR'
FILL 18 16 17 16 16 17 17 END FILL
ARA=5 NUX=1 NUY=1 NUZ=1
COM='EAST AND WEST WALLS OF NORTH REFLECTOR'
FILL 20 END FILL
ARA=6 NUX=1 NUY=1 NUZ=1
COM='EAST AND WEST WALLS OF SOUTH REFLECTOR'
FILL 22 END FILL
ARA=7 NUX=1 NUY=1 NUZ=1
COM='ARRAY FOR NORTH TOP REFLECTOR'
FILL 24 END FILL
ARA=8 NUX=1 NUY=1 NUZ=1
COM='ARRAY FOR SOUTH TOP REFLECTOR'
FILL 26 END FILL
ARA=9 NUX=3 NUY=1 NUZ=1
COM='ARRAY FOR NORTH END REFLECTOR'
FILL 28 29 30 END FILL
ARA=10 NUX=1 NUY=1 NUZ=1
COM='ARRAY FOR SOUTH END REFLECTOR'
FILL 32 END FILL
ARA=13 NUX=1 NUY=1 NUZ=2
COM='COMBINATION OF NORTH CORE WITH BOTTOM REFLECTOR'
FILL 15 9 END FILL
ARA=14 NUX=1 NUY=3 NUZ=1
COM='NORTH CORE WITH SIDE REFLECTORS'
FILL 21 38 21 END FILL
ARA=15 NUX=2 NUY=1 NUZ=1
COM='NORTH CORE WITH END REFLECTOR'
FILL 31 39 END FILL
ARA=16 NUX=1 NUY=1 NUZ=2
COM='NORTH CORE WITH TOP REFLECTOR'
FILL 40 25 END FILL
ARA=20 NUX=1 NUY=1 NUZ=2
COM='SOUTH CORE WITH BOTTOM REFLECTOR'
FILL 19 10 END FILL
ARA=21 NUX=1 NUY=3 NUZ=1
COM='SOUTH CORE WITH EAST WEST REFLECTORS'
FILL 23 48 23 END FILL
ARA=22 NUX=2 NUY=1 NUZ=1
COM='SOUTH CORE WITH END REFLECTOR'
FILL 49 33 END FILL
ARA=23 NUX=1 NUY=1 NUZ=2

```



```

COM='COMBINATION OF CORE WITH TOP REFLECTOR'
FILL 50 27 END FILL
ARA=25 NUX=3 NUY=1 NUZ=1
COM='TOTAL'
FILL 42 54 52 END FILL
ARA=26 NUX=3 NUY=1 NUZ=1
COM='ASSEMBLY OF FUEL BOX FRONT AND REAR'
FILL 2 1 3 END FILL
ARA=27 NUX=1 NUY=1 NUZ=3
COM='ASSEMBLY OF FUEL BOX TOP AND BOTTOM'
FILL 5 4 5 END FILL
ARA=28 NUX=1 NUY=2 NUZ=1
COM='COMBINATION OF TWO FUEL BOXES'
FILL 7 7 END FILL
ARA=29 NUX=1 NUY=2 NUZ=1
COM='COMBINATION OF SPECIAL AND REGULAR FUEL BOXES'
FILL 7 6 END FILL
ARA=30 NUX=1 NUY=2 NUZ=1
COM='COMBINATION OF TWO WEIGHT DISTRIBUTION PLATES'
FILL 35 35 END FILL
ARA=31 NUX=1 NUY=2 NUZ=1
COM='COMBINATION OF SPECIAL AND REGULAR WEIGHT DISTRIBUTION PLATES'
FILL 35 34 END FILL
END ARRAY
READ PLOT TTL='YZ SLICE OF SOUTH CORE FIRST ROW'
XUL=64.319 YUL=40.000 ZUL=72.000
XLR=64.319 YLR=72.000 ZLR=56.000
VAX=1 WDN=-1 NAX=130 NCH='012345678' END
TTL='XZ SLICE OF SPHERE CUBOID'
XUL=56.0 YUL=63.625 ZUL=71.735
XLR=72.0 YLR=63.625 ZLR=55.735
UAX=1 WDN=-1 NAX=130 NCH='012345678'
END PLOT
/ READ START NST=1 XSM=41.37 XSP=72.894 YSM=40.63 YSP=71.29
/ ZSM=56.071 ZSP=71.4 END START
READ START NST=1 END START
END DATA
END

```

```

VALIDATION CASE (CAR16 )
=CSAS25
ROCKY FLATS CRITICALS NUREG/CR-1653 EXPERIMENT NUMBER ? (27 GROUP MODEL)
/ FUEL CUBE 15.28 CM, U(4.46)308 @ H/U=1.25, LOW CONC. SOLUTION DRIVEN
27GROUPPNDFF4 INFHOMMEDIUM
U308 1 5.4078E-1 293.0 92234 0.03 92235 4.46 92236 0.08 92238 95.43 END
H2O 1 1.5627E-1 END
ARBM-BAGGIE 1.0 3 0 0 0 1001 14.01 6012 84.9 8016 1.20 1 1.9134E-2
END
ARBM-AL1100 1.0 3 0 0 1 13027 99.18 26000 0.5 29000 0.2 2 9.5390E-1
END
ARBM-TAPE(VINYL) 1.0 7 0 0 0 1001 5.92 6012 45.91 8016 10.82 17000
25.73 20000 6.9 22000 1.6 82000 1.1 2 1.1115E-2 END
ARBM-TAPE(MYLAR) 1.0 3 0 0 0 1001 6.83 6012 65.50 8016 27.02 2
1.7491E-2 END
ARBM-MODERATOR 1.185 3 0 0 0 1001 7.83 6012 59.49 8016 32.48 3 END
ARBM-PLEX(REG) 1.0 3 0 0 0 1001 7.84 6012 59.59 8016 32.23 4
1.1773 END
ARBM-PLEX(PAPER) 1.0 3 0 0 0 1001 6.48 6012 42.17 8016 49.5 4
3.7534E-3 END
ARBM-PLEX(GLUE) 1.0 3 0 0 0 1001 11.67 6012 86.29 8016 1.20 4
1.1648E-3 END
ARBM-PLEX(TRIS) 1.0 8 0 0 1 1001 7.16 6012 52.03 7014 0.16 8016 29.82
15031 1.02 17000 1.81 35079 4.260 35081 2.840 5 1.2757 END
ARBM-PLEX(PAPER) 1.0 3 0 0 0 1001 6.48 6012 42.17 8016 49.5 5
3.7534E-3 END
ARBM-PLEX(GLUE) 1.0 3 0 0 0 1001 11.67 6012 86.29 8016 1.20 5
1.1648E-3 END
ARBM-FILLER 1.185 3 0 0 0 1001 7.83 6012 59.49 8016 32.48 6 0.7 END
/ THIS MATERIAL IS ACTUALLY MODERATOR ADJUSTED FOR THE VOLUME
/ FRACTION OF THE VOID FILLED BETWEEN CORE AND REFLECTOR.
ARBM-AL1100 1.0 3 0 0 1 13027 99.18 26000 0.5 29000 0.2 7 2.715 END
SOLNUO2(NO3)2 8 86.42 0.149 1.0 293.0 92234 1.022 92235 93.172
92236 0.434 92238 5.372 END
SS304 9 1.0 END
END COMP
ROCKY FLATS CRITICALS NUREG/CR-1653 EXPERIMENT NUMBER ? (27 GROUP MODEL)
/ FUEL CUBE 15.28 CM, U(4.46)308 @ H/U=1.25, LOW CONC. SOLUTION DRIVEN
READ PARM NPG=600 NUB=YES FDN=YES PLT=YES END PARM
READ GEOM
UNIT 1
COM='FUEL BOX WITH VOID AND PART OF AL BOX'
CUBOID 0 1 9.80 0.0 3.75 0.0 14.98 0.0
CUBOID 2 1 9.95 0.0 3.90 -0.15 14.98 0.0
CUBOID 1 1 14.98 0.0 9.365 -5.615 14.98 0.0

```

```

UNIT 2
COM='FRONT OF FUEL BOX'
CUBOID 2 1 0.15 0.0 5.615 0.0 14.98 0.0
CUBOID 0 1 0.15 0.0 9.365 0.0 14.98 0.0
CUBOID 2 1 0.15 0.0 14.98 0.0 14.98 0.0
UNIT 3
COM='REAR OF FUEL BOX'
CUBOID 2 1 0.15 0.0 14.98 0.0 14.98 0.0
UNIT 4
COM='ARRAY TO ASSEMBLE PART OF BOX'
ARRAY 26 3*0
UNIT 5
COM='TOP AND BOTTOM OF BOX'
CUBOID 0 1 9.80 0.0 3.750 0.0 0.15 0.0
CUBOID 2 1 15.28 0.0 9.365 -5.615 0.15 0.0
GLOBAL
UNIT 6
COM='ARRAY TO ASSEMBLE TOP AND BOTTOM'
ARRAY 27 3*0
CUBOID 2 1 15.28 0.0 15.13 -0.15 15.28 0.0
CUBOID 0 1 15.305 -0.025 15.155 -0.175 15.305 -0.025
UNIT 7
COM='FUEL BOX 15.28 CM ON A SIDE WITH .15 CM WALLS .05CM STACKING VOID'
CUBOID 1 1 6P7.49
CUBOID 2 1 6P7.64
CUBOID 0 1 6P7.6650
UNIT 34
COM='ALUMINUM WEIGHT DISTRIBUTION PLATE FOR SPECIAL BOX'
CUBOID 0 1 9.80 0.0 3.750 0.0 0.16 0.0
CUBOID 7 1 15.33 0.0 9.54 -5.79 0.16 0.0
UNIT 35
COM='ALUMINUM WEIGHT DISTRIBUTION PLATE FOR BOXES'
CUBOID 7 1 4P7.665 0.16 0.0
UNIT 9
COM='NORTH SPLIT TABLE CORE'
ARRAY 1 3*0.0
CUBOID 0 1 30.66 -0.94 77.5 0.0 83.475 0.0
UNIT 10
COM='SOUTH SPLIT TABLE CORE'
ARRAY 2 3*0.0
CUBOID 0 1 49.4 0.0 77.5 0.0 83.475 0.0
UNIT 11
COM='PLEXIGLASS REFLECTOR SHEET WITHOUT TRIS, NORTH BOTTOM REFLECTOR'
CUBOID 4 1 2P15.8000 2P38.7500 2P0.6150
UNIT 12
COM='PLEXIGLASS REFLECTOR SHEET WITH TRIS, NORTH BOTTOM REFLECTOR'
CUBOID 5 1 2P15.8000 2P38.7500 2P0.6150
UNIT 13
COM='UPPER PORTION NORTH BOTTOM REFLECTOR WITH TRIS'
CUBOID 5 1 2P15.8 2P38.75 2P8.24
UNIT 14
COM='LOWER PORTION NORTH BOTTOM REFLECTOR WITH TRIS'
CUBOID 5 1 2P15.8 2P38.75 2P3.69
UNIT 15
COM='NORTH BOTTOM REFLECTOR INCLUDES REGULAR AND TRIS'
ARRAY 3 3*0.0
UNIT 16
COM='PLEXIGLAS SHEET BOTTOM SOUTH REFLECTOR WITHOUT TRIS'
CUBOID 0 1 2P5.1 2P2.5 2P0.6150
CUBOID 4 1 44.3 -5.1 2P38.75 2P0.615
UNIT 17
COM='PLEXIGLAS SHEET BOTTOM SOUTH REFLECTOR WITH TRIS'
CUBOID 0 1 2P5.1 2P2.5 2P0.6150
CUBOID 5 1 44.3 -5.1 2P38.75 2P0.6150
UNIT 18
COM='LOWER PORTION SOUTH BOTTOM REFLECTOR WITH TRIS'
CUBOID 0 1 2P5.1 2P2.5 2P8.855
CUBOID 5 1 44.3 -5.1 2P38.75 2P8.855
UNIT 19
COM='SOUTH BOTTOM REFLECTOR WITH REGULAR AND TRIS'
ARRAY 4 3*0.0
UNIT 20
COM='EAST AND WEST REFLECTORS FOR NORTH REFLECTOR WITH TRIS'
CUBOID 5 1 2P15.8 2P12.65 2P54.2825
UNIT 21
COM='ARRAY FOR EAST AND WEST REFLECTORS FOR NORTH REFLECTOR'
ARRAY 5 3*0.0
UNIT 22
COM='EAST AND WEST REFLECTORS FOR SOUTH REFLECTOR WITH TRIS'
CUBOID 5 1 2P24.700 2P12.65 2P54.2825
UNIT 23
COM='ARRAY FOR EAST AND WEST REFLECTORS FOR SOUTH REFLECTOR'
ARRAY 6 3*0.0
UNIT 24
COM='NORTH TOP REFLECTOR WITH TRIS'
CUBOID 5 1 2P28.35 2P64.05 2P12.15

```

```

UNIT 25
COM='ARRAY FOR NORTH TOP REFLECTOR'
ARRAY 7 3*0.0
UNIT 26
COM='SOUTH TOP REFLECTOR WITH TRIS'
CUBOID 0 1 2P5.1 2P2.5 2P12.15
CUBOID 5 1 69.4 -5.1 2P64.05 2P12.15
UNIT 27
COM='ARRAY FOR SOUTH TOP REFLECTOR'
ARRAY 8 3*0.0
UNIT 28
COM='NORTH END REFLECTOR 9.8CM PORTION WITHOUT TRIS'
CUBOID 4 1 2P4.9000 2P64.0500 2P54.2825
UNIT 29
COM='NORTH END REFLECTOR 5.2 CM PORTION WITH TRIS'
CUBOID 5 1 2P2.6 2P64.0500 2P54.2825
UNIT 30
COM='NORTH END REFLECTOR 10.1 CM PORTION WITHOUT TRIS'
CUBOID 4 1 2P5.05 2P64.05 2P54.2825
UNIT 31
COM='ARRAY FOR NORTH END REFLECTOR'
ARRAY 9 3*0.0
UNIT 32
COM='SOUTH END REFLECTOR'
CUBOID 5 1 2P12.55 2P64.05 2P54.2825
UNIT 33
COM='ARRAY FOR SOUTH END REFLECTOR'
ARRAY 10 3*0.0
UNIT 38
COM='NORTH CORE WITH BOTTOM REFLECTOR'
ARRAY 13 3* 0.0
UNIT 39
COM='NORTH CORE WITH EAST AND WEST REFLECTOR'
ARRAY 14 3*0.0
UNIT 40
COM='NORTH CORE WITH END REFLECTOR'
ARRAY 15 3*0.0
UNIT 42
COM='NORTH CORE WITH TOP REFLECTOR'
ARRAY 16 3*0.0
UNIT 48
COM='SOUTH CORE WITH BOTTOM REFLECTORS'
ARRAY 20 3*0.0
UNIT 49
COM='SOUTH CORE WITH EAST WEST REFLECTORS'
ARRAY 21 3*0.0
UNIT 50
COM='SOUTH CORE END REFLECTOR'
ARRAY 22 3*0.0
UNIT 52
COM='SOUTH CORE WITH TOP REFLECTOR'
ARRAY 23 3*0.0
UNIT 54
COM='AIR GAP'
CUBOID 0 1 0.570 0.0 64.475 -63.625 69.13 -63.735
GLOBAL
UNIT 55
COM='TOTAL'
ARRAY 25 3*0.0
UNIT 56
COM='COMBINATION OF TWO REGULAR FUEL BOXES'
ARRAY 28 3*0.0
UNIT 57
COM='COMBINATION OF REGULAR FUEL BOX AND SPECIAL FUEL BOX'
ARRAY 29 3*0.0
UNIT 58
COM='COMBINATION OF TWO REGULAR WEIGHT DISTRIBUTION PLATES'
ARRAY 30 3*0.0
UNIT 59
COM='COMBINATION OF REGULAR AND SPECIAL WEIGHT DISTRIBUTION PLATES'
ARRAY 31 3*0.0
UNIT 60
COM='NORTH CORE SOLUTION DRIVER'
CUBOID 8 1 2P7.5 2P14.9 3.332 -7.5
CUBOID 0 1 2P7.5 2P14.9 2P7.5
CUBOID 9 1 2P7.65 2P15.05 2P7.65
CUBOID 0 1 2P7.665 2P15.33 2P7.665
UNIT 61
COM='SOUTH CORE SOLUTION DRIVER'
CUBOID 8 1 2P7.5 2P14.9 3.292 -7.5
CUBOID 0 1 2P7.5 2P14.9 2P7.5
CUBOID 9 1 2P7.65 2P15.05 2P7.65
CUBOID 0 1 2P7.665 2P15.33 2P7.665
END GEOMETRY
READ ARRAY
ARA=1 NUX=2 NUY=4 NUZ=9
COM='NORTH SPLIT TABLE CORE'

```

```

FILL 2R7 2R56 4R7
      2R35 2R58 4R35
      2R7 2R56 4R7
      2R35 2R58 4R35
      2R7 56 60 4R7
      2R35 2R58 4R35
      2R7 2R56 4R7
      2R35 2R58 4R35
      2R7 2R56 4R7
END FILL
ARA=2 NUX=3 NUY=4 NUZ=9
COM='SOUTH SPLIT TABLE CORE'
FILL 3R7 3R56 6R7
      3R35 3R58 6R35
      3R7 3R56 6R7
      3R35 3R58 6R35
      3R7 61 56 56 6R7
      3R35 3R58 6R35
      3R7 57 56 56 6R7
      3R35 59 58 58 6R35
      3R7 57 56 56 6R7
END FILL
ARA=3 NUX=1 NUY=1 NUZ=3
COM='NORTH BOTTOM REFLECTOR'
FILL 14 11 13 END FILL
ARA=4 NUX=1 NUY=1 NUZ=7
COM='SOUTH BOTTOM REFLECTOR'
FILL 18 16 17 16 17 17 END FILL
ARA=5 NUX=1 NUY=1 NUZ=1
COM='EAST AND WEST WALLS OF NORTH REFLECTOR'
FILL 20 END FILL
ARA=6 NUX=1 NUY=1 NUZ=1
COM='EAST AND WEST WALLS OF SOUTH REFLECTOR'
FILL 22 END FILL
ARA=7 NUX=1 NUY=1 NUZ=1
COM='ARRAY FOR NORTH TOP REFLECTOR'
FILL 24 END FILL
ARA=8 NUX=1 NUY=1 NUZ=1
COM='ARRAY FOR SOUTH TOP REFLECTOR'
FILL 26 END FILL
ARA=9 NUX=3 NUY=1 NUZ=1
COM='ARRAY FOR NORTH END REFLECTOR'
FILL 28 29 30 END FILL
ARA=10 NUX=1 NUY=1 NUZ=1
COM='ARRAY FOR SOUTH END REFLECTOR'
FILL 32 END FILL
ARA=13 NUX=1 NUY=1 NUZ=2
COM='COMBINATION OF NORTH CORE WITH BOTTOM REFLECTOR'
FILL 15 9 END FILL
ARA=14 NUX=1 NUY=3 NUZ=1
COM='NORTH CORE WITH SIDE REFLECTORS'
FILL 21 38 21 END FILL
ARA=15 NUX=2 NUY=1 NUZ=1
COM='NORTH CORE WITH END REFLECTOR'
FILL 31 39 END FILL
ARA=16 NUX=1 NUY=1 NUZ=2
COM='NORTH CORE WITH TOP REFLECTOR'
FILL 40 25 END FILL
ARA=20 NUX=1 NUY=1 NUZ=2
COM='SOUTH CORE WITH BOTTOM REFLECTOR'
FILL 19 10 END FILL
ARA=21 NUX=1 NUY=3 NUZ=1
COM='SOUTH CORE WITH EAST WEST REFLECTORS'
FILL 23 48 23 END FILL
ARA=22 NUX=2 NUY=1 NUZ=1
COM='SOUTH CORE WITH END REFLECTOR'
FILL 49 33 END FILL
ARA=23 NUX=1 NUY=1 NUZ=2
COM='COMBINATION OF CORE WITH TOP REFLECTOR'
FILL 50 27 END FILL
ARA=25 NUX=3 NUY=1 NUZ=1
COM='TOTAL'
FILL 42 54 52 END FILL
ARA=26 NUX=3 NUY=1 NUZ=1
COM='ASSEMBLY OF FUEL BOX FRONT AND REAR'
FILL 2 1 3 END FILL
ARA=27 NUX=1 NUY=1 NUZ=3
COM='ASSEMBLY OF FUEL BOX TOP AND BOTTOM'
FILL 5 4 5 END FILL
ARA=28 NUX=1 NUY=2 NUZ=1
COM='COMBINATION OF TWO FUEL BOXES'
FILL 7 7 END FILL
ARA=29 NUX=1 NUY=2 NUZ=1
COM='COMBINATION OF SPECIAL AND REGULAR FUEL BOXES'
FILL 7 6 END FILL
ARA=30 NUX=1 NUY=2 NUZ=1
COM='COMBINATION OF TWO WEIGHT DISTRIBUTION PLATES'

```

```

FILL 35 35 END FILL
ARA=31 NUX=1 NUY=2 NUZ=1
COM='COMBINATION OF SPECIAL AND REGULAR WEIGHT DISTRIBUTION PLATES'
FILL 35 34 END FILL
END ARRAY
READ PLOT TTL='YZ SLICE OF SOUTH CORE FIRST ROW'
XUL=64.319 YUL=40.000 ZUL=72.000
XLR=64.319 YLR=72.000 ZLR=56.000
VAX=1 WDN=-1 MAX=130 NCH='012345678'END
TTL='XZ SLICE OF SPHERE CUBOID'
XUL=56.0 YUL=63.625 ZUL=71.735
XLR=72.0 YLR=63.625 ZLR=55.735
UAX=1 WDN=-1 MAX=130 NCH='012345678'
END PLOT
READ START NST=1 XSM=41.37 XSP=72.894 YSM=40.63 YSP=71.29
ZSM=56.071 ZSP=71.4 END START
END DATA
END

VALIDATION CASE (CAR18 )
=CSAS25
ROCKY FLATS CRITICALS NUREG/CR-2500 EXPERIMENT G (27 GROUP)
' 30 FUEL CANS 2.44 CM MODERATOR GEE.HU203.DATA(OPTUM)
27GROUPNDF4 LATTICECELL
U308 1 5.4078E-1 293.0 92234 0.03 92235 4.46 92236 0.08 92238 95.43 END
H2O 1 2.6356E-1 END
ARBM-BAGGIE 1.0 3 0 0 0 1001 14.01 6012 84.9 8016 1.20 1 1.9134E-2
END
ARBM-AL1100 1.0 3 0 0 1 13027 99.18 26000 0.5 29000 0.2 2 9.5390E-1
END
ARBM-TAPE(VINYL) 1.0 7 0 0 0 1001 5.92 6012 45.91 8016 10.82 17000
25.73 20000 6.9 22000 1.6 82000 1.1 2 1.1115E-2 END
ARBM-TAPE(MYLAR) 1.0 3 0 0 0 1001 6.83 6012 65.50 8016 27.02 2
1.7491E-2 END
ARBM-MODERATOR 1.185 3 0 0 0 1001 7.83 6012 59.49 8016 32.48 3 END
ARBM-PLEX(REG) 1.0 3 0 0 0 1001 7.84 6012 59.59 8016 32.23 4
1.1773 END
ARBM-PLEX(PAPER) 1.0 3 0 0 0 1001 6.48 6012 42.17 8016 49.5 4
3.7534E-3 END
ARBM-PLEX(GLUE) 1.0 3 0 0 0 1001 11.67 6012 86.29 8016 1.20 4
1.1648E-3 END
ARBM-PLEX(TRIS) 1.0 8 0 0 1 1001 7.16 6012 52.03 7014 0.16 8016 29.82
15031 1.02 17000 1.81 35079 4.260 35081 2.840 5 1.2757 END
ARBM-PLEX(PAPER) 1.0 3 0 0 0 1001 6.48 6012 42.17 8016 49.5 5
3.7534E-3 END
ARBM-PLEX(GLUE) 1.0 3 0 0 0 1001 11.67 6012 86.29 8016 1.20 5
1.1648E-3 END
ARBM-FILLER 1.185 3 0 0 0 1001 7.83 6012 59.49 8016 32.48 6 1.0 END
' THIS MATERIAL IS ACTUALLY MODERATOR ADJUSTED FOR THE VOLUME
' FRACTION OF THE VOID FILLED BETWEEN CORE AND REFLECTOR.
END COMP
SPHTRIANGP 19.00 18.5857 1 3 18.9579 2 END
ROCKY FLATS CRITICALS NUREG/CR-2500 EXPERIMENT G (27 GROUP)
' 30 FUEL CANS 2.44 CM MODERATOR GEE.HU203.DATA(OPTUM)
READ PARM RUN=YES NPG=600 FDN=YES NUB=YES PLT=NO
END PARM
READ GEOM
UNIT 1
COM='FUEL BOX 15.28 CM ON A SIDE WITH .15 CM WALLS .05CM STACKING VOID'
CUBOID 1 1 6P7.49
CUBOID 2 1 6P7.64
CUBOID 0 1 6P7.6650
UNIT 2
COM='X-FACE INTERSTITIAL MODERATOR'
CUBOID 3 1 2P1.2200 4P7.665
UNIT 3
COM='Y-FACE INTERSTITIAL MODERATOR'
CUBOID 3 1 2P7.665 2P1.2200 2P7.665
UNIT 4
COM='Z-FACE INTERSTITIAL MODERATOR'
CUBOID 3 1 4P7.665 2P1.2200
UNIT 5
COM='MORE X-FACE MODERATOR'
CUBOID 3 1 4P1.2200 2P7.665
UNIT 6
COM='MORE Y-FACE MODERATOR'
CUBOID 3 1 2P7.665 4P1.2200
UNIT 7
COM='MORE Z-FACE MODERATOR'
CUBOID 3 1 2P1.2200 2P7.665 2P1.2200
UNIT 8
COM='LAST OF INTERSTITIAL MODERATOR'
CUBOID 3 1 6P1.2200
UNIT 9
COM='NORTH SPLIT TABLE CORE'
ARRAY 1 3*0.0
UNIT 10

```

```

COM='SOUTH SPLIT TABLE CORE'
ARRAY 2 3*0.0
UNIT 11
COM='PLEXIGLASS REFLECTOR SHEET WITHOUT TRIS, NORTH BOTTOM REFLECTOR'
CUBOID 4 1 2P16.5500 2P38.7500 2P0.6150
UNIT 12
COM='PLEXIGLASS REFLECTOR SHEET WITH TRIS, NORTH BOTTOM REFLECTOR'
CUBOID 5 1 2P16.5500 2P38.7500 2P0.6150
UNIT 13
COM='UPPER PORTION NORTH BOTTOM REFLECTOR WITH TRIS'
CUBOID 5 1 2P16.5500 2P38.75 2P8.24
UNIT 14
COM='LOWER PORTION NORTH BOTTOM REFLECTOR WITH TRIS'
CUBOID 5 1 2P16.5500 2P38.75 2P3.69
UNIT 15
COM='NORTH BOTTOM REFLECTOR INCLUDES REGULAR AND TRIS'
ARRAY 3 3*0.0
UNIT 16
COM='PLEXIGLAS SHEET BOTTOM SOUTH REFLECTOR WITHOUT TRIS'
CUBOID 0 1 2P5.1 2P2.55 2P0.615
CUBOID 4 1 44.3 -5.1 2P38.75 2P0.615
UNIT 17
COM='PLEXIGLAS SHEET BOTTOM SOUTH REFLECTOR WITH TRIS'
CUBOID 0 1 2P5.1 2P2.55 2P0.615
CUBOID 5 1 44.3 -5.1 2P38.75 2P0.6150
UNIT 18
COM='LOWER PORTION SOUTH BOTTOM REFLECTOR WITH TRIS'
CUBOID 0 1 2P5.1 2P2.55 2P8.855
CUBOID 5 1 44.3 -5.1 2P38.75 2P8.855
UNIT 19
COM='SOUTH BOTTOM REFLECTOR WITH REGULAR AND TRIS'
ARRAY 4 3*0.0
UNIT 20
COM='EAST AND WEST REFLECTORS FOR NORTH REFLECTOR WITH TRIS'
CUBOID 5 1 2P16.5500 2P12.65 2P52.7825
UNIT 21
COM='ARRAY FOR EAST AND WEST REFLECTORS FOR NORTH REFLECTOR'
ARRAY 5 3*0.0
UNIT 22
COM='EAST AND WEST REFLECTORS FOR SOUTH REFLECTOR WITH TRIS'
CUBOID 5 1 2P24.700 2P12.65 2P52.7825
UNIT 23
COM='ARRAY FOR EAST AND WEST REFLECTORS FOR SOUTH REFLECTOR'
ARRAY 6 3*0.0
UNIT 24
COM='NORTH TOP REFLECTOR WITH TRIS'
CUBOID 5 1 2P29.1 2P64.05 2P12.15
UNIT 25
COM='ARRAY FOR NORTH TOP REFLECTOR'
ARRAY 7 3*0.0
UNIT 26
COM='SOUTH TOP REFLECTOR WITH TRIS'
CUBOID 0 1 2P5.1 2P2.55 2P12.15
CUBOID 5 1 69.4 -5.1 2P64.05 2P12.15
UNIT 27
COM='ARRAY FOR SOUTH TOP REFLECTOR'
ARRAY 8 3*0.0
UNIT 28
COM='NORTH END REFLECTOR 9.8CM PORTION WITHOUT TRIS'
CUBOID 4 1 2P4.9000 2P64.0500 2P52.7825
UNIT 29
COM='NORTH END REFLECTOR 5.2 CM PORTION WITH TRIS'
CUBOID 5 1 2P2.6 2P64.0500 2P52.7825
UNIT 30
COM='NORTH END REFLECTOR 10.1 CM PORTION WITHOUT TRIS'
CUBOID 4 1 2P5.05 2P64.05 2P52.7825
UNIT 31
COM='ARRAY FOR NORTH END REFLECTOR'
ARRAY 9 3*0.0
UNIT 32
COM='SOUTH END REFLECTOR'
CUBOID 5 1 2P12.55 2P64.05 2P52.7825
UNIT 33
COM='ARRAY FOR SOUTH END REFLECTOR'
ARRAY 10 3*0.0
UNIT 34
COM='12.95 THICK MODERATING PLASTIC NORTH CORE'
CUBOID 0 1 2P16.5500 2P13.315 2P25.4350
UNIT 35
COM='2.95 THICK MODERATING PLASTIC NORTH CORE'
CUBOID 6 1 2P16.5500 2P38.75 2P1.7525
UNIT 36
ARRAY 11 3*0.0
UNIT 37
ARRAY 12 3*0.0

```

```

UNIT 38
COM='NORTH CORE WITH BOTTOM REFLECTOR'
ARRAY 13 3* 0.0
UNIT 39
COM='NORTH CORE WITH EAST AND WEST REFLECTOR'
ARRAY 14 3*0.0
UNIT 40
COM='NORTH CORE WITH END REFLECTOR'
ARRAY 15 3*0.0
UNIT 41
COM='NORTH SPLIT TABLE FACEPLATE'
CUBOID 3 1 2P0.61 2P64.0500 2P64.9325
UNIT 42
COM='NORTH CORE WITH TOP REFLECTOR'
ARRAY 16 3*0.0
UNIT 43
COM='NORTH CORE WITH FACEPLATE'
ARRAY 17 3*0.0
UNIT 44
COM='12.95 CM THICK MODERATOR SOUTH CORE'
CUBOID 0 1 2P16.5500 2P13.315 2P25.4350
UNIT 45
COM='2.95 THICK MODERATOR SOUTH CORE'
CUBOID 6 1 2P16.5500 2P38.75 2P1.7525
UNIT 46
COM='COMBINATION OF CORE WITH 12.95 THICK MODERATOR'
ARRAY 18 3*0.0
UNIT 47
COM='COMBINATION OF CORE WITH 2.95 THICK MODERATOR'
ARRAY 19 3*0.0
UNIT 48
COM='SOUTH CORE WITH EAST WEST REFLECTORS'
ARRAY 20 3*0.0
UNIT 49
COM='SOUTH CORE WITH EAST WEST REFLECTORS'
ARRAY 21 3*0.0
UNIT 50
COM='SOUTH CORE END REFLECTOR'
ARRAY 22 3*0.0
UNIT 51
COM='FACEPLATE FOR SOUTH SPLIT TABLE'
CUBOID 3 1 2P0.610 2P64.0500 2P64.9325
UNIT 52
COM='SOUTH CORE WITH TOP REFLECTOR'
ARRAY 23 3*0.0
UNIT 53
COM='SOUTH CORE WITH FACEPLATE'
ARRAY 24 3*0.0
UNIT 54
COM='AIR GAP'
CUBOID 0 1 2P0.2850 2P64.0500 2P64.9325
GLOBAL
UNIT 55
COM='TOTAL'
ARRAY 25 3*0.0
UNIT 56
COM='NORTH BOTTOM MODERATOR'
CUBOID 6 1 2P16.5500 2P38.7500 2P13.05
UNIT 57
COM='BOTTOM SOUTH MODERATOR'
CUBOID 6 1 2P24.700 2P38.75 2P13.05
UNIT 58
COM='REAR FILLER'
CUBOID 6 1 2P8.1500 2P38.75 2P27.1875
UNIT 59
COM='COMBINATION OF SOUTH CORE WITH REAR FILLER'
ARRAY 26 3*0.0
UNIT 60
COM='NORTH CORE REAR FILLER'
CUBOID 6 1 2P0.0 2P38.75 2P27.1875
UNIT 61
COM='COMBINATION OF NORTH CORE WITH REAR FILLER'
ARRAY 27 3*0.0
UNIT 62
COM='EMPTY FUEL LOCATION'
CUBOID 0 1 6P7.6650
UNIT 63
COM='Y-FACE MODERATOR VOID'
CUBOID 0 1 2P7.665 2P1.22 2P7.665
END GEOMETRY
READ ARRAY
ARA=1 NUX=3 NUY=5 NUZ=5
COM='NORTH SPLIT TABLE CORE'
FILL 1 2 1 3 5 3 1Q6 1 2 1
      4 7 4 6 8 6 1Q6 4 7 4
      1Q30
      62 2 1 63 5 3 1Q6 62 2 1 END FILL

```

```

ARA=2  NUX=3  NUY=5  NUZ=5
COM='SOUTH SPLIT TABLE CORE'
FILL  1 2 1 3 5 3 166 1 2 1
      4 7 4 6 8 6 106 4 7 4
      1030
      1 2 62 3 5 63 106 1 2 62  END FILL
ARA=3  NUX=1  NUY=1  NUZ=4
COM='NORTH BOTTOM MODERATOR AND REFLECTOR'
FILL  14 11 13 56  END FILL
ARA=4  NUX=1  NUY=1  NUZ=8
COM='SOUTH BOTTOM MODERATOR AND REFLECTOR'
FILL  18 16 17 16 16 17 17 57  END FILL
ARA=5  NUX=1  NUY=1  NUZ=1
COM='EAST AND WEST WALLS OF NORTH REFLECTOR'
FILL  20  END FILL
ARA=6  NUX=1  NUY=1  NUZ=1
COM='EAST AND WEST WALLS OF SOUTH REFLECTOR'
FILL  22  END FILL
ARA=7  NUX=1  NUY=1  NUZ=1
COM='ARRAY FOR NORTH TOP REFLECTOR'
FILL  24  END FILL
ARA=8  NUX=1  NUY=1  NUZ=1
COM='ARRAY FOR SOUTH TOP REFLECTOR'
FILL  26  END FILL
ARA=9  NUX=3  NUY=1  NUZ=1
COM='ARRAY FOR NORTH END REFLECTOR'
FILL  28 29 30  END FILL
ARA=10 NUX=1  NUY=1  NUZ=1
COM='ARRAY FOR SOUTH END REFLECTOR'
FILL  32  END FILL
ARA=11 NUX=1  NUY=2  NUZ=1
COM='COMBINATION OF CORE WITH 12.95CM THICK MODERATOR'
FILL  9 34  END FILL
ARA=12 NUX=1  NUY=1  NUZ=2
COM='COMBINATION OF PREVIOUS ARRAY WITH 2.95CM THICK MODERATOR'
FILL  36 35  END FILL
ARA=13 NUX=1  NUY=1  NUZ=2
COM='COMBINATION OF NORTH CORE WITH BOTTOM REFLECTOR'
FILL  15 61  END FILL
ARA=14 NUX=1  NUY=3  NUZ=1
COM='NORTH CORE WITH SIDE REFLECTORS'
FILL  21 38 21  END FILL
ARA=15 NUX=2  NUY=1  NUZ=1
COM='NORTH CORE WITH END REFLECTOR'
FILL  31 39  END FILL
ARA=16 NUX=1  NUY=1  NUZ=2
COM='NORTH CORE WITH TOP REFLECTOR'
FILL  40 25  END FILL
ARA=17 NUX=2  NUY=1  NUZ=1
COM='NORTH CORE WITH FACEPLATE'
FILL  42 41  END FILL
ARA=18 NUX=1  NUY=2  NUZ=1
COM='COMBINATION OF S. CORE WITH 12.95 CM THICK MODERATOR'
FILL  10 44  END FILL
ARA=19 NUX=1  NUY=1  NUZ=2
COM='COMBINATION OF CORE WITH 2.95 CM THICK MODERATOR'
FILL  46 45  END FILL
ARA=20 NUX=1  NUY=1  NUZ=2
COM='SOUTH CORE WITH BOTTOM REFLECTOR'
FILL  19 59  END FILL
ARA=21 NUX=1  NUY=3  NUZ=1
COM='SOUTH CORE WITH EAST WEST REFLECTORS'
FILL  23 48 23  END FILL
ARA=22 NUX=2  NUY=1  NUZ=1
COM='SOUTH CORE WITH END REFLECTOR'
FILL  49 33  END FILL
ARA=23 NUX=1  NUY=1  NUZ=2
COM='COMBINATION OF CORE WITH TOP REFLECTOR'
FILL  50 27  END FILL
ARA=24 NUX=2  NUY=1  NUZ=1
COM='SOUTH CORE WITH FACEPLATE'
FILL  51 52  END FILL
ARA=25 NUX=3  NUY=1  NUZ=1
COM='TOTAL'
FILL  43 54 53  END FILL
ARA=26 NUX=2  NUY=1  NUZ=1
COM='COMBINATION OF SOUTH CORE WITH REAR FILLER'
FILL  47 58  END FILL
ARA=27 NUX=2  NUY=1  NUZ=1
COM='COMBINATION OF NORTH CORE WITH REAR FILLER'
FILL  37 60  END FILL
END ARRAY
READ PLOT TTL='XZ SLICE OF RFPG SHOWING MATERIAL REGIONS'
XUL=-1  YUL=64.05  ZUL=135
XLR=136  YLR=64.05  ZLR=-2
UAX=1  WDN=-1  NAX=130  NCH='0123456'END
TTL='YZ SLICE OF NORTH CORE FIRST ROW'

```



```

XUL=48 YUL=-2 ZUL=136
XLR=48 YLR=136 ZLR=-2
VAX=1 WDN=-1 NAX=130 NCH='0123456'END
TTL='YZ SLICE OF NORTH CORE SECOND ROW'
XUL=28 YUL=-2 ZUL=136
XLR=28 YLR=136 ZLR=-2
VAX=1 WDN=-1 NAX=130 NCH='0123456'END
TTL='YZ SLICE OF SOUTH CORE FIRST ROW'
XUL=62 YUL=-2 ZUL=136
XLR=62 YLR=136 ZLR=-2
VAX=1 WDN=-1 NAX=130 NCH='0123456'END
TTL='TOP VIEW OF SOURCE SLOT'
XUL=-2 YUL=136 ZUL=125
XLR=138 YLR=-2 ZLR=125
UAX=1 VDN=-1 NAX=130 NCH='0123456'END
TTL='TOP VIEW OF TOP LAYER'
XUL=-2 YUL=136 ZUL=95
XLR=138 YLR=-2 ZLR=95
UAX=1 VDN=-1 NAX=130 NCH='0123456'
END PLOT
READ START NST=1
XSP=100.0 XSM=10.0
YSP=100.0 YSM=10.0
ZSP=117.0 ZSM=60.0
END DATA
END

```

```

VALIDATION CASE (CAR20 )
=CSAS25
ROCKY FLATS CRITICALS NUREG/CR-2500 EXPERIMENT NUMBER ? (27 GROUP MODEL)
' FUEL CUBE 15.28 CM, U(4.46)308 @ H/U=2.03, HI ENRICHED SPHERE DRIVEN
27GROUPNDF4 INFHOMMEDIUM
U308 1 5.4078E-1 293.0 92234 0.03 92235 4.46 92236 0.08 92238 95.43 END
H2O 1 2.6356E-1 END
ARBM-BAGGIE 1.0 3 0 0 0 1001 14.01 6012 84.9 8016 1.20 1 1.9134E-2
END
ARBM-AL1100 1.0 3 0 0 1 13027 99.18 26000 0.5 29000 0.2 2 9.5390E-1
END
ARBM-TAPE(VINYL) 1.0 7 0 0 0 1001 5.92 6012 45.91 8016 10.82 17000
25.73 20000 6.9 22000 1.6 82000 1.1 2 1.1115E-2 END
ARBM-TAPE(MYLAR) 1.0 3 0 0 0 1001 6.83 6012 65.50 8016 27.02 2
1.7491E-2 END
ARBM-MODERATOR 1.185 3 0 0 0 1001 7.83 6012 59.49 8016 32.48 3 END
ARBM-PLEX(REG) 1.0 3 0 0 0 1001 7.84 6012 59.59 8016 32.23 4
1.1773 END
ARBM-PLEX(PAPER) 1.0 3 0 0 0 1001 6.48 6012 42.17 8016 49.5 4
3.7534E-3 END
ARBM-PLEX(GLUE) 1.0 3 0 0 0 1001 11.67 6012 86.29 8016 1.20 4
1.1648E-3 END
ARBM-PLEX(TRIS) 1.0 8 0 0 1 1001 7.16 6012 52.03 7014 0.16 8016 29.82
15031 1.02 17000 1.81 35079 4.260 35081 2.840 5 1.2757 END
ARBM-PLEX(PAPER) 1.0 3 0 0 0 1001 6.48 6012 42.17 8016 49.5 5
3.7534E-3 END
ARBM-PLEX(GLUE) 1.0 3 0 0 0 1001 11.67 6012 86.29 8016 1.20 5
1.1648E-3 END
ARBM-FILLER 1.185 3 0 0 0 1001 7.83 6012 59.49 8016 32.48 6 0.7 END
' THIS MATERIAL IS ACTUALLY MODERATOR ADJUSTED FOR THE VOLUME
' FRACTION OF THE VOID FILLED BETWEEN CORE AND REFLECTOR.
ARBM-AL1100 1.0 3 0 0 1 13027 99.18 26000 0.5 29000 0.2 7 2.715 END
URANIUM 8 0.9483 293.0 92234 1.0 92235 93.19 92236 0.4 92238 5.41 END
ARBM-PJ 0.816 2 0 0 0 1001 85.1 6012 14.9 8 0.0089 END
SS304 9 1.0 END
END COMP
ROCKY FLATS CRITICALS NUREG/CR-2500 EXPERIMENT NUMBER ? (27 GROUP MODEL)
' FUEL CUBE 15.28 CM, U(4.46)308 @ H/U=2.03, HI ENRICHED SPHERE DRIVEN
READ PARM MPG=600 NUB=YES FDN=YES PLT=NO END PARM
READ GEOM
UNIT 1
COM='FUEL BOX WITH VOID AND PART OF AL BOX'
CUBOID 0 1 9.80 0.0 3.75 0.0 14.98 0.0
CUBOID 2 1 9.95 0.0 3.90 -0.15 14.98 0.0
CUBOID 1 1 14.98 0.0 9.365 -5.615 14.98 0.0
UNIT 2
COM='FRONT OF FUEL BOX'
CUBOID 2 1 0.15 0.0 5.615 0.0 14.98 0.0
CUBOID 0 1 0.15 0.0 9.365 0.0 14.98 0.0
CUBOID 2 1 0.15 0.0 14.98 0.0 14.98 0.0
UNIT 3
COM='REAR OF FUEL BOX'
CUBOID 2 1 0.15 0.0 14.98 0.0 14.98 0.0
UNIT 4
COM='ARRAY TO ASSEMBLE PART OF BOX'
ARRAY 26 3*0
UNIT 5
COM='TOP AND BOTTOM OF BOX'
CUBOID 0 1 9.80 0.0 3.750 0.0 0.15 0.0
CUBOID 2 1 15.28 0.0 9.365 -5.615 0.15 0.0

```

```

GLOBAL
UNIT 6
COM='ARRAY TO ASSEMBLE TOP AND BOTTOM'
ARRAY 27 3*0
CUBOID 2 1 15.28 0.0 15.13 -0.15 15.28 0.0
CUBOID 0 1 15.305 -0.025 15.155 -0.175 15.305 -0.025
UNIT 7
COM='FUEL BOX 15.28 CM ON A SIDE WITH .15 CM WALLS .05CM STACKING VOID'
CUBOID 1 1 6P7.49
CUBOID 2 1 6P7.64
CUBOID 0 1 6P7.6650
UNIT 8
COM='BOX FOR DRIVER'
CYLINDER 9 1 0.3175 2P2.318
SPHERE 0 1 2.34
SPHERE 8 1 5.67
HOLE 36 0.0 0.0 2.3401
HOLE 100 0.0 0.0 -2.3401
CUBOID 0 1 8.71 -6.62 2P7.665 7.365 -7.965
HOLE 37 0.0 0.0 -7.965
UNIT 34
COM='ALUMINUM WEIGHT DISTRIBUTION PLATE FOR SPECIAL BOX'
CUBOID 0 1 9.80 0.0 3.750 0.0 0.16 0.0
CUBOID 7 1 15.33 0.0 9.54 -5.79 0.16 0.0
UNIT 35
COM='ALUMINUM WEIGHT DISTRIBUTION PLATE FOR BOXES'
CUBOID 7 1 4P7.665 0.16 0.0
UNIT 36
COM='DRIVER SUPPORT'
CYLINDER 9 1 0.3175 3.32 0.0
UNIT 100
COM='DRIVER SUPPORT'
CYLINDER 9 1 0.3175 0.0 -3.32
UNIT 37
COM='DRIVER MOUNT'
CYLINDER 9 1 1.56 2.2 0.0
UNIT 9
COM='NORTH SPLIT TABLE CORE'
ARRAY 1 3*0.0
CUBOID 0 1 30.66 -0.94 77.5 0.0 83.475 0.0
UNIT 10
COM='SOUTH SPLIT TABLE CORE'
ARRAY 2 3*0.0
CUBOID 0 1 49.4 0.0 77.5 0.0 83.475 0.0
UNIT 11
COM='PLEXIGLASS REFLECTOR SHEET WITHOUT TRIS, NORTH BOTTOM REFLECTOR'
CUBOID 4 1 2P15.8000 2P38.7500 2P0.6150
UNIT 12
COM='PLEXIGLASS REFLECTOR SHEET WITH TRIS, NORTH BOTTOM REFLECTOR'
CUBOID 5 1 2P15.8000 2P38.7500 2P0.6150
UNIT 13
COM='UPPER PORTION NORTH BOTTOM REFLECTOR WITH TRIS'
CUBOID 5 1 2P15.8 2P38.75 2P8.24
UNIT 14
COM='LOWER PORTION NORTH BOTTOM REFLECTOR WITH TRIS'
CUBOID 5 1 2P15.8 2P38.75 2P3.69
UNIT 15
COM='NORTH BOTTOM REFLECTOR INCLUDES REGULAR AND TRIS'
ARRAY 3 3*0.0
UNIT 16
COM='PLEXIGLAS SHEET BOTTOM SOUTH REFLECTOR WITHOUT TRIS'
CUBOID 0 1 2P5.1 2P2.5 2P0.6150
CUBOID 4 1 44.3 -5.1 2P38.75 2P0.615
UNIT 17
COM='PLEXIGLAS SHEET BOTTOM SOUTH REFLECTOR WITH TRIS'
CUBOID 0 1 2P5.1 2P2.5 2P0.6150
CUBOID 5 1 44.3 -5.1 2P38.75 2P0.6150
UNIT 18
COM='LOWER PORTION SOUTH BOTTOM REFLECTOR WITH TRIS'
CUBOID 0 1 2P5.1 2P2.5 2P8.855
CUBOID 5 1 44.3 -5.1 2P38.75 2P8.855
UNIT 19
COM='SOUTH BOTTOM REFLECTOR WITH REGULAR AND TRIS'
ARRAY 4 3*0.0
UNIT 20
COM='EAST AND WEST REFLECTORS FOR NORTH REFLECTOR WITH TRIS'
CUBOID 5 1 2P15.8 2P12.65 2P54.2825
UNIT 21
COM='ARRAY FOR EAST AND WEST REFLECTORS FOR NORTH REFLECTOR'
ARRAY 5 3*0.0
UNIT 22
COM='EAST AND WEST REFLECTORS FOR SOUTH REFLECTOR WITH TRIS'
CUBOID 5 1 2P24.700 2P12.65 2P54.2825
UNIT 23
COM='ARRAY FOR EAST AND WEST REFLECTORS FOR SOUTH REFLECTOR'
ARRAY 6 3*0.0

```

```

UNIT 24
COM='NORTH TOP REFLECTOR WITH TRIS'
CUBOID 5 1 2P28.35 2P64.05 2P12.15
UNIT 25
COM='ARRAY FOR NORTH TOP REFLECTOR'
ARRAY 7 3*0.0
UNIT 26
COM='SOUTH TOP REFLECTOR WITH TRIS'
CUBOID 0 1 2P5.1 2P2.5 2P12.15
CUBOID 5 1 69.4 -5.1 2P64.05 2P12.15
UNIT 27
COM='ARRAY FOR SOUTH TOP REFLECTOR'
ARRAY 8 3*0.0
UNIT 28
COM='NORTH END REFLECTOR 9.8CM PORTION WITHOUT TRIS'
CUBOID 4 1 2P4.9000 2P64.0500 2P54.2825
UNIT 29
COM='NORTH END REFLECTOR 5.2 CM PORTION WITH TRIS'
CUBOID 5 1 2P2.6 2P64.0500 2P54.2825
UNIT 30
COM='NORTH END REFLECTOR 10.1 CM PORTION WITHOUT TRIS'
CUBOID 4 1 2P5.05 2P64.05 2P54.2825
UNIT 31
COM='ARRAY FOR NORTH END REFLECTOR'
ARRAY 9 3*0.0
UNIT 32
COM='SOUTH END REFLECTOR'
CUBOID 5 1 2P12.55 2P64.05 2P54.2825
UNIT 33
COM='ARRAY FOR SOUTH END REFLECTOR'
ARRAY 10 3*0.0
UNIT 38
COM='NORTH CORE WITH BOTTOM REFLECTOR'
ARRAY 13 3* 0.0
UNIT 39
COM='NORTH CORE WITH EAST AND WEST REFLECTOR'
ARRAY 14 3*0.0
UNIT 40
COM='NORTH CORE WITH END REFLECTOR'
ARRAY 15 3*0.0
UNIT 42
COM='NORTH CORE WITH TOP REFLECTOR'
ARRAY 16 3*0.0
UNIT 48
COM='SOUTH CORE WITH BOTTOM REFLECTORS'
ARRAY 20 3*0.0
UNIT 49
COM='SOUTH CORE WITH EAST WEST REFLECTORS'
ARRAY 21 3*0.0
UNIT 50
COM='SOUTH CORE END REFLECTOR'
ARRAY 22 3*0.0
UNIT 52
COM='SOUTH CORE WITH TOP REFLECTOR'
ARRAY 23 3*0.0
UNIT 54
COM='AIR GAP'
CUBOID 0 1 1.49 0.0 64.475 -63.625 69.13 -63.735
GLOBAL
UNIT 55
COM='TOTAL'
ARRAY 25 3*0.0
END GEOMETRY
READ ARRAY
ARA=1 NUX=2 NUY=5 NUZ=9
COM='NORTH SPLIT TABLE CORE'
FILL 10R7
      10R35
      10R7
      10R35
      10R7
      10R35
      10R7
      10R35
      10R7 END FILL
ARA=2 NUX=3 NUY=5 NUZ=9
COM='SOUTH SPLIT TABLE CORE'
FILL 6R7 6 8R7
      6R35 34 8R35
      6R7 6 8R7
      6R35 34 8R35
      6R7 8 8R7
      6R35 34 8R35
      6R7 6 8R7
      6R35 34 8R35
      6R7 6 8R7 END FILL
ARA=3 NUX=1 NUY=1 NUZ=3

```

```

COM='NORTH BOTTOM REFLECTOR'
FILL 14 11 13 END FILL
ARA=4 NUX=1 NUY=1 NUZ=7
COM='SOUTH BOTTOM REFLECTOR'
FILL 18 16 17 16 16 17 17 END FILL
ARA=5 NUX=1 NUY=1 NUZ=1
COM='EAST AND WEST WALLS OF NORTH REFLECTOR'
FILL 20 END FILL
ARA=6 NUX=1 NUY=1 NUZ=1
COM='EAST AND WEST WALLS OF SOUTH REFLECTOR'
FILL 22 END FILL
ARA=7 NUX=1 NUY=1 NUZ=1
COM='ARRAY FOR NORTH TOP REFLECTOR'
FILL 24 END FILL
ARA=8 NUX=1 NUY=1 NUZ=1
COM='ARRAY FOR SOUTH TOP REFLECTOR'
FILL 26 END FILL
ARA=9 NUX=3 NUY=1 NUZ=1
COM='ARRAY FOR NORTH END REFLECTOR'
FILL 28 29 30 END FILL
ARA=10 NUX=1 NUY=1 NUZ=1
COM='ARRAY FOR SOUTH END REFLECTOR'
FILL 32 END FILL
ARA=13 NUX=1 NUY=1 NUZ=2
COM='COMBINATION OF NORTH CORE WITH BOTTOM REFLECTOR'
FILL 15 9 END FILL
ARA=14 NUX=1 NUY=3 NUZ=1
COM='NORTH CORE WITH SIDE REFLECTORS'
FILL 21 38 21 END FILL
ARA=15 NUX=2 NUY=1 NUZ=1
COM='NORTH CORE WITH END REFLECTOR'
FILL 31 39 END FILL
ARA=16 NUX=1 NUY=1 NUZ=2
COM='NORTH CORE WITH TOP REFLECTOR'
FILL 40 25 END FILL
ARA=20 NUX=1 NUY=1 NUZ=2
COM='SOUTH CORE WITH BOTTOM REFLECTOR'
FILL 19 10 END FILL
ARA=21 NUX=1 NUY=3 NUZ=1
COM='SOUTH CORE WITH EAST WEST REFLECTORS'
FILL 23 48 23 END FILL
ARA=22 NUX=2 NUY=1 NUZ=1
COM='SOUTH CORE WITH END REFLECTOR'
FILL 49 33 END FILL
ARA=23 NUX=1 NUY=1 NUZ=2
COM='COMBINATION OF CORE WITH TOP REFLECTOR'
FILL 50 27 END FILL
ARA=25 NUX=3 NUY=1 NUZ=1
COM='TOTAL'
FILL 42 54 52 END FILL
ARA=26 NUX=3 NUY=1 NUZ=1
COM='ASSEMBLY OF FUEL BOX FRONT AND REAR'
FILL 2 1 3 END FILL
ARA=27 NUX=1 NUY=1 NUZ=3
COM='ASSEMBLY OF FUEL BOX TOP AND BOTTOM'
FILL 5 4 5 END FILL
END ARRAY
READ PLOT TTL='YZ SLICE OF SOUTH CORE FIRST ROW'
XUL=64.319 YUL=55.625 ZUL=71.735
XLR=64.319 YLR=71.625 ZLR=55.735
VAX=1 WDN=-1 NAX=130 NCH='012345678'END
TTL='XZ SLICE OF SPHERE CUBOID'
XUL=56.0 YUL=63.625 ZUL=71.735
XLR=72.0 YLR=63.625 ZLR=55.735
UAX=1 WDN=-1 NAX=130 NCH='012345678'
END PLOT
/ READ START NST=6 TFX=65 TFY=63.625 TFZ=63.735 LNU=300 END START
READ START NST=1 XSM=56.981 XSP=71.649 YSM=56.219 YSP=70.959
ZSM=56.401 ZSP=71.069 END START
END DATA
END

```

```

VALIDATION CASE (CAS04 )
=CSAS25
BRITISH HANDBOOK OF CRITICALITY SAFETY U(1.42)F4 & PARAFFIN (CASE 04)
27GROUPNDF4 INFHOMMEDIUM
UF4 1 0.4903 293 92235 1.4023 92238 98.5977 END
/ NOTE: THE ENRICHMENT GIVEN IN THE REFERENCE IS NOT WEIGHT PERCENT
PARA(H2O) 1 0.4572 END
END COMP
BRITISH HANDBOOK OF CRITICALITY SAFETY U(1.42)F4 & PARAFFIN (CASE 04)
READ PARM NPG=600 NUB=YES FDN=YES END PARM
READ GEOM
CUBOID 1 1 2P46.55 2P46.50 2P61.9
END GEOM
END DATA
END

```

```

VALIDATION CASE                      (CAS06 )
=CSAS25
BRITISH HANDBOOK OF CRITICALITY SAFETY U(1.42)F4 & PARAFFIN (CASE 06)
27GROUPNDF4 INFHOMMEDIUM
UF4 1 0 0.4903 293 92235 1.4023 92238 98.5977 END
/ NOTE: THE ENRICHMENT GIVEN IN THE REFERENCE IS NOT WEIGHT PERCENT
PARA(H2O) 1 0.4572 END
END COMP
BRITISH HANDBOOK OF CRITICALITY SAFETY U(1.42)F4 & PARAFFIN (CASE 06)
READ PARM NPG=600 NUB=YES FDN=YES END PARM
READ GEOM
CUBOID 1 1 2P65.35 2P65.3 2P37.1
END GEOM
END DATA
END

```

```

VALIDATION CASE                      (CAS11 )
=CSAS25
RAFFETY AND MILHALCZO U(2)F4-1 REFLECTED (CASE 11)
27GROUPNDF4 INFHOMMEDIUM
U-235 1 0 1.5811E-4 END
U-238 1 0 7.6467E-3 END
H 1 0 3.0864E-2 END
C 1 0 1.4839E-2 END
F 1 0 3.1219E-2 END
PARA(H2O) 2 1.0 END
PLEXIGLASS 3 0.918 END
AL 3 0.062 END
END COMP
RAFFETY AND MALHALCZO U(2)F4-1 REFLECTED (CASE 11)
READ PARM RUN=YES NPG=600 NUB=YES FDN=YES END PARM
READ GEOM
UNIT 1
CUBOID 1 1 4P28.110 2P56.44
REPLICATE 2 2 5*3.048 0.0 5
UNIT 2
CUBOID 3 1 4P28.110 2*0.0
REPLICATE 3 2 4*3.048 0.0 3.048 5
END GEOM
READ ARRAY
NUX=1 NUY=1 NUZ=2
FILL 2 1 END FILL
END ARRAY
READ BIAS ID=400 2 6 END BIAS
END DATA
END

```

```

VALIDATION CASE                      (CAS13 )
=CSAS25
RAFFETY AND MILHALCZO U(2)F4-2 REFLECTED (CASE 13) NO BIASING
27GROUPNDF4 INFHOMMEDIUM
U-235 1 0 1.3303E-4 END
U-238 1 0 6.4370E-3 END
H 1 0 3.9097E-2 END
C 1 0 1.8797E-2 END
F 1 0 2.6280E-2 END
PARA(H2O) 2 1.0 END
PLEXIGLASS 3 0.918 END
AL 3 0.062 END
END COMP
RAFFETY AND MALHALCZO U(2)F4-2 REFLECTED (CASE 13) NO BIASING
READ PARM RUN=YES NPG=600 NUB=YES FDN=YES END PARM
READ GEOM
UNIT 1
CUBOID 1 1 4P25.555 2P36.935
REPLICATE 2 2 5*3.048 0.0 5
UNIT 2
CUBOID 3 1 4P25.555 2*0.0
REPLICATE 3 2 4*3.048 0.0 3.048 5
END GEOM
READ ARRAY
NUX=1 NUY=1 NUZ=2
FILL 2 1 END FILL
END ARRAY
/ READ BIAS ID=400 2 6 END BIAS
END DATA
END

```

```

VALIDATION CASE                      (CAS16 )
=CSAS25
RAFFETY AND MILHALCZO U(2)F4-4 REFLECTED (CASE 16)
27GROUPNDF4 INFHOMMEDIUM
U-235 1 0 0.9924E-4 END
U-238 1 0 4.7998E-3 END
H 1 0 4.9212E-2 END
C 1 0 2.3660E-2 END
F 1 0 1.9596E-2 END

```

```

'PARAFFIN 2 1.0 END
PARA(H2O) 2 1.0 END
PLEXIGLASS 3 0.918 END
AL 3 0.062 END
END COMP
RAFFETY AND MALHALCZO U(2)F4-4 REFLECTED (CASE 16)
READ PARM RUN=YES NPG=600 NUB=YES FDN=YES END PARM
READ GEOM
UNIT 1
CUBOID 1 1 4P23.000 2P48.285
REPLICATE 2 2 5*3.048 0.0 5
UNIT 2
CUBOID 3 1 4P23.000 2*0.0
REPLICATE 3 2 4*3.048 0.0 3.048 5
END GEOM
READ ARRAY
NUX=1 NUY=1 NUZ=2
FILL 2 1 END FILL
END ARRAY
READ BIAS ID=400 2 6 END BIAS
END DATA
END

```

```

VALIDATION CASE (CAS17 )
=CSAS25
RAFFETY AND MILHALCZO U(2)F4-5 REFLECTED (CASE 17)
27GROUPNDF4 INFHOMMEDIUM
U-235 1 0 0.8667E-4 END
U-238 1 0 4.1941E-3 END
H 1 0 5.3187E-2 END
C 1 0 2.5570E-2 END
F 1 0 1.7123E-2 END
POLY(H2O) 2 1.0 END
PLEXIGLASS 3 0.918 END
AL 3 0.062 END
END COMP
RAFFETY AND MALHALCZO U(2)F4-5 REFLECTED (CASE 17)
READ PARM RUN=YES NPG=600 NUB=YES FDN=YES END PARM
READ GEOM
UNIT 1
CUBOID 1 1 2P28.160 2P30.645 2P27.040
REPLICATE 2 2 5*3.048 0.0 5
UNIT 2
CUBOID 3 1 2P28.160 2P30.645 2*0.0
REPLICATE 3 2 4*3.048 0.0 3.048 5
END GEOM
READ ARRAY
NUX=1 NUY=1 NUZ=2
FILL 2 1 END FILL
END ARRAY
READ BIAS ID=400 2 6 END BIAS
END DATA
END

```

```

VALIDATION CASE (CAS21 )
=CSAS25
RAFFETY AND MILHALCZO U(3)F4-1 REFLECTED (CASE 21) NO BIAS
27GROUPNDF4 INFHOMMEDIUM
U-235 1 0 2.3494E-4 END
U-238 1 0 7.4999E-3 END
H 1 0 3.1341E-2 END
C 1 0 1.5067E-2 END
F 1 0 3.0939E-2 END
PARA(H2O) 2 1.0 END
PLEXIGLASS 3 0.918 END
AL 3 0.062 END
END COMP
RAFFETY AND MILHALCZO U(3)F4-1 REFLECTED (CASE 21) NO BIAS
READ PARM RUN=YES NPG=600 NUB=YES FDN=YES END PARM
READ GEOM
UNIT 1
CUBOID 1 1 2P25.57 2P25.57 2P25.635
REPLICATE 2 2 5*3.048 0.0 5
UNIT 2
CUBOID 3 1 2P25.57 2P25.57 2*0.0
REPLICATE 3 2 4*3.048 0.0 3.048 5
END GEOM
READ ARRAY
NUX=1 NUY=1 NUZ=2
FILL 2 1 END FILL
END ARRAY
' READ BIAS ID=400 2 6 END BIAS
END DATA
END

```

```

VALIDATION CASE (CAS23 )
=CSAS25
RAFFETY AND MILHALCZO U(3)F4-1 REFLECTED (CASE 23)
27GROUPNDF4 INFHOMMEDIUM
U-235 1 0 2.3494E-4 END
U-238 1 0 7.4999E-3 END
H 1 0 3.1341E-2 END
C 1 0 1.5067E-2 END
F 1 0 3.0939E-2 END
PARA(H2O) 2 1.0 END
PLEXIGLASS 3 0.918 END
AL 3 0.062 END
END COMP
RAFFETY AND MALHALCZO U(3)F4-1 REFLECTED (CASE 23)
READ PARM RUN=YES NPG=600 NUB=YES FDN=YES END PARM
READ GEOM
UNIT 1
CUBOID 1 1 2P23.010 2P23.010 2P33.785
REPLICATE 2 2 5*3.048 0.0 5
UNIT 2
CUBOID 3 1 2P23.010 2P23.010 2*0.0
REPLICATE 3 2 4*3.048 0.0 3.048 5
END GEOM
READ ARRAY
NUX=1 NUY=1 NUZ=2
FILL 2 1 END FILL
END ARRAY
READ BIAS ID=400 2 6 END BIAS
END DATA
END

```

```

VALIDATION CASE (CAS26 )
=CSAS25
RAFFETY AND MILHALCZO U(3)F4-1 UNREFLECTED (CASE 26)
27GROUPNDF4 INFHOMMEDIUM
U-235 1 0 2.3494E-4 END
U-238 1 0 7.4999E-3 END
H 1 0 3.1341E-2 END
C 1 0 1.5067E-2 END
F 1 0 3.0939E-2 END
END COMP
RAFFETY AND MALHALCZO U(3)F4-1 UNREFLECTED (CASE 26)
READ PARM NPG=600 NUB=YES FDN=YES END PARM
READ GEOM
CUBOID 1 1 28.235 -28.235 28.235 -28.235 43.32 -43.32
END GEOM
END DATA
END

```

```

VALIDATION CASE (CAS29 )
=CSAS25
RAFFETY AND MILHALCZO U(3)F4-2 REFLECTED (CAS29)
27GROUPNDF4 INFHOMMEDIUM
U-235 1 0 1.6709E-4 END
U-238 1 0 5.3355E-3 END
H 1 0 4.6262E-2 END
C 1 0 2.2241E-2 END
F 1 0 2.2011E-2 END
POLY(H2O) 2 1.0 END
PLEXIGLASS 3 0.918 END
AL 3 0.062 END
END COMP
RAFFETY AND MALHALCZO U(3)F4-2 REFLECTED (CAS29)
READ PARM RUN=YES NPG=600 NUB=YES FDN=YES END PARM
READ GEOM
UNIT 1
CUBOID 1 1 2P20.405 2P20.400 2P19.745
REPLICATE 2 2 5*3.048 0.0 5
UNIT 2
CUBOID 3 1 2P20.405 2P20.400 2*0.0
REPLICATE 3 2 4*3.048 0.0 3.048 5
END GEOM
READ ARRAY
NUX=1 NUY=1 NUZ=2
FILL 2 1 END FILL
END ARRAY
READ BIAS ID=400 2 6 END BIAS
END DATA
END

```

```

VALIDATION CASE (CAS31 )
=CSAS25
RAFFETY AND MILHALCZO U(3)F4-2 UNREFLECTED (CASE 31)
27GROUPNDF4 INFHOMMEDIUM
U-235 1 0 1.6709E-4 END
U-238 1 0 5.3355E-3 END
H 1 0 4.6262E-2 END

```

```

C      1 0 2.2241E-2 END
F      1 0 2.2011E-2 END
END COMP
RAFFETY AND MALHALCZO U(3)F4-2 UNREFLECTED (CASE 31)
READ PARM RUN=YES NPG=600 NUB=YES FDN=YES END PARM
READ GEOM
CUBOID 1 1 2P24.295 2P25.570 2P24.265
END GEOM
END DATA
END

```

```

VALIDATION CASE (CAS33 )
=CSAS25
CRITICAL REFLECTED CYLINDER OF AQUEOUS U(4.98)O2F2 (CASE 33)
27GROUPNDF4 INFHOMMEDIUM
SOLNUO2F2 1 910.36 0.0 1 298 92235 4.98 92238 95.02 END
SS304 2 1.0 END
H2O 3 1.0 END
CD 4 1.0 END
END COMP
CRITICAL REFLECTED CYLINDER OF AQUEOUS U(4.98)O2F2 (CASE 33)
READ PARM RUN=YES NPG=600 NUB=YES FDN=YES END PARM
READ GEOM
UNIT 1
CYLINDER 1 1 19.545 2P27.225
CYLINDER 0 1 19.545 78.975 -27.225
CYLINDER 2 1 19.624 79.054 -27.304
CYLINDER 4 1 19.705 79.054 -27.304
CYLINDER 2 1 22.245 79.054 -27.304
CYLINDER 3 1 45.000 79.054 -27.304
CUBOID 0 1 4P45.000 79.054 -27.304
END GEOM
END DATA
END

```

```

VALIDATION CASE (CAS34 )
=CSAS25
CRITICAL REFLECTED CYLINDER OF AQUEOUS U(4.98)O2F2 (CASE 34)
27GROUPNDF4 INFHOMMEDIUM
SOLNUO2F2 1 910.36 0.0 1 298 92235 4.98 92238 95.02 END
U-235 1 0 1.1599E-4 END
U-238 1 0 2.1852E-3 END
F 1 0 4.6024E-3 END
H 1 0 5.6605E-2 END
O 1 0 3.2904E-2 END
SS304 2 1.0 END
H2O 3 1.0 END
END COMP
CRITICAL REFLECTED CYLINDER OF AQUEOUS U(4.98)O2F2 (CASE 34)
READ PARM RUN=YES NPG=600 NUB=YES FDN=YES END PARM
READ GEOM
UNIT 1
CYLINDER 1 1 16.510 2P71.500
CYLINDER 0 1 16.510 172.400 -71.500
CYLINDER 2 1 16.589 172.479 -71.579
CYLINDER 2 1 19.129 172.479 -71.579
CYLINDER 3 1 45.000 172.479 -71.579
CUBOID 0 1 4P45.000 172.479 -71.579
END GEOM
END DATA
END

```

```

VALIDATION CASE (CAS36 )
=CSAS25
CRITICAL CYLINDER OF AQUEOUS U(4.98)O2F2 (CASE 36)
27GROUPNDF4 INFHOMMEDIUM
SOLNUO2F2 1 910.36 0.0 1 298 92235 4.98 92238 95.02 END
SS304 2 1.0 END
END COMP
CRITICAL CYLINDER OF AQUEOUS U(4.98)O2F2 (CASE 36)
READ PARM RUN=YES NPG=600 NUB=YES FDN=YES END PARM
READ GEOM
UNIT 1
CYLINDER 1 1 19.5500 2P50.85
CYLINDER 0 1 19.5500 74.16 -50.85
CYLINDER 2 1 19.6287 74.16 -50.9287
CUBOID 0 1 4P19.6287 74.16 -50.9287
END GEOM
END DATA
END

```

```

VALIDATION CASE (CLT01 )
=CSAS25
BAW-1645-4, EXP/MT-2452, CASE C-2-C, DANCOFF FACTOR FOR EACH FUEL PIN
27GROUPNDF4 LATTICECELL
AL 1 1.0 295.5 END
AL 2 1.0 295.5 END

```



```

H2O 3 1.0 295.5 END
BORON 3 1.7129-4 295.5 END
H2O 4 0.75 295.5 END
BORON 4 1.2847-4 295.5 END
AL 4 0.25 295.5 END
CARBONSTEEL 5 1.0 295.5 END
UO2 13 0.9325 295.5 92235 2.459 92238 97.541 END
UO2 14 0.9325 295.5 92235 2.459 92238 97.541 END
UO2 15 0.9325 295.5 92235 2.459 92238 97.541 END
UO2 16 0.9325 295.5 92235 2.459 92238 97.541 END
UO2 23 0.9325 295.5 92235 2.459 92238 97.541 END
UO2 24 0.9325 295.5 92235 2.459 92238 97.541 END
UO2 25 0.9325 295.5 92235 2.459 92238 97.541 END
UO2 26 0.9325 295.5 92235 2.459 92238 97.541 END
END COMP
TRIANGPITCH 1.2093 1.0300 16 3 1.2060 1 1.0440 0 END
MORE DATA RES=13 CYLINDER 0.5150 DAN(13)=0.37809
RES=14 CYLINDER 0.5150 DAN(14)=0.50536
RES=15 CYLINDER 0.5150 DAN(15)=0.63264
RES=23 CYLINDER 0.5150 DAN(23)=0.46920
RES=24 CYLINDER 0.5150 DAN(24)=0.63217
RES=25 CYLINDER 0.5150 DAN(25)=0.79514
RES=26 CYLINDER 0.5150 DAN(26)=0.97782 END MORE
BAW-1645-4, EXP'MT-2452, CASE C-2-C, DANC OFF FACTOR FOR EACH FUEL PIN
READ PARAM TME=40 FDN=YES NUB=YES END PARAM
READ GEOM

UNIT 1
ZHEMICYL-Y 2 1 0.6030 143.9600 -0.3180
UNIT 2
ZHEMICYL-Y 2 1 0.6030 156.1220 143.9600
UNIT 3
ZHEMICYL+Y 2 1 0.6030 143.9600 -0.3180
UNIT 4
ZHEMICYL+Y 2 1 0.6030 156.1220 143.9600

UNIT 5
ZHEMICYL-Y 13 1 0.5150 143.9600 0.0
ZHEMICYL-Y 0 1 0.5220 143.9600 0.0
ZHEMICYL-Y 1 1 0.6030 143.9600 -0.3180
UNIT 6
ZHEMICYL-Y 23 1 0.5150 153.3400 143.9600
ZHEMICYL-Y 0 1 0.5220 155.8040 143.9600
ZHEMICYL-Y 1 1 0.6030 156.1220 143.9600
UNIT 7
ZHEMICYL-Y 14 1 0.5150 143.9600 0.0
ZHEMICYL-Y 0 1 0.5220 143.9600 0.0
ZHEMICYL-Y 1 1 0.6030 143.9600 -0.3180
UNIT 8
ZHEMICYL-Y 24 1 0.5150 153.3400 143.9600
ZHEMICYL-Y 0 1 0.5220 155.8040 143.9600
ZHEMICYL-Y 1 1 0.6030 156.1220 143.9600
UNIT 9
ZHEMICYL-Y 16 1 0.5150 143.9600 0.0
ZHEMICYL-Y 0 1 0.5220 143.9600 0.0
ZHEMICYL-Y 1 1 0.6030 143.9600 -0.3180
UNIT 10
ZHEMICYL-Y 26 1 0.5150 153.3400 143.9600
ZHEMICYL-Y 0 1 0.5220 155.8040 143.9600
ZHEMICYL-Y 1 1 0.6030 156.1220 143.9600

UNIT 11
ZHEMICYL+Y 13 1 0.5150 143.9600 0.0
ZHEMICYL+Y 0 1 0.5220 143.9600 0.0
ZHEMICYL+Y 1 1 0.6030 143.9600 -0.3180
UNIT 12
ZHEMICYL+Y 23 1 0.5150 153.3400 143.9600
ZHEMICYL+Y 0 1 0.5220 155.8040 143.9600
ZHEMICYL+Y 1 1 0.6030 156.1220 143.9600
UNIT 13
ZHEMICYL+Y 14 1 0.5150 143.9600 0.0
ZHEMICYL+Y 0 1 0.5220 143.9600 0.0
ZHEMICYL+Y 1 1 0.6030 143.9600 -0.3180
UNIT 14
ZHEMICYL+Y 24 1 0.5150 153.3400 143.9600
ZHEMICYL+Y 0 1 0.5220 155.8040 143.9600
ZHEMICYL+Y 1 1 0.6030 156.1220 143.9600
UNIT 15
ZHEMICYL+Y 16 1 0.5150 143.9600 0.0
ZHEMICYL+Y 0 1 0.5220 143.9600 0.0
ZHEMICYL+Y 1 1 0.6030 143.9600 -0.3180
UNIT 16
ZHEMICYL+Y 26 1 0.5150 153.3400 143.9600
ZHEMICYL+Y 0 1 0.5220 155.8040 143.9600
ZHEMICYL+Y 1 1 0.6030 156.1220 143.9600

```

```

UNIT 17
ZHEMICYL-X 14 1 0.5150 143.9600 0.0
ZHEMICYL-X 0 1 0.5220 143.9600 0.0
ZHEMICYL-X 1 1 0.6030 143.9600 -0.3180
UNIT 18
ZHEMICYL-X 24 1 0.5150 153.3400 143.9600
ZHEMICYL-X 0 1 0.5220 155.8040 143.9600
ZHEMICYL-X 1 1 0.6030 156.1220 143.9600
UNIT 19
ZHEMICYL-X 15 1 0.5150 143.9600 0.0
ZHEMICYL-X 0 1 0.5220 143.9600 0.0
ZHEMICYL-X 1 1 0.6030 143.9600 -0.3180
UNIT 20
ZHEMICYL-X 25 1 0.5150 153.3400 143.9600
ZHEMICYL-X 0 1 0.5220 155.8040 143.9600
ZHEMICYL-X 1 1 0.6030 156.1220 143.9600
UNIT 21
ZHEMICYL-X 16 1 0.5150 143.9600 0.0
ZHEMICYL-X 0 1 0.5220 143.9600 0.0
ZHEMICYL-X 1 1 0.6030 143.9600 -0.3180
UNIT 22
ZHEMICYL-X 26 1 0.5150 153.3400 143.9600
ZHEMICYL-X 0 1 0.5220 155.8040 143.9600
ZHEMICYL-X 1 1 0.6030 156.1220 143.9600

UNIT 23
ZHEMICYL+X 14 1 0.5150 143.9600 0.0
ZHEMICYL+X 0 1 0.5220 143.9600 0.0
ZHEMICYL+X 1 1 0.6030 143.9600 -0.3180
UNIT 24
ZHEMICYL+X 24 1 0.5150 153.3400 143.9600
ZHEMICYL+X 0 1 0.5220 155.8040 143.9600
ZHEMICYL+X 1 1 0.6030 156.1220 143.9600
UNIT 25
ZHEMICYL+X 15 1 0.5150 143.9600 0.0
ZHEMICYL+X 0 1 0.5220 143.9600 0.0
ZHEMICYL+X 1 1 0.6030 143.9600 -0.3180
UNIT 26
ZHEMICYL+X 25 1 0.5150 153.3400 143.9600
ZHEMICYL+X 0 1 0.5220 155.8040 143.9600
ZHEMICYL+X 1 1 0.6030 156.1220 143.9600
UNIT 27
ZHEMICYL+X 16 1 0.5150 143.9600 0.0
ZHEMICYL+X 0 1 0.5220 143.9600 0.0
ZHEMICYL+X 1 1 0.6030 143.9600 -0.3180
UNIT 28
ZHEMICYL+X 26 1 0.5150 153.3400 143.9600
ZHEMICYL+X 0 1 0.5220 155.8040 143.9600
ZHEMICYL+X 1 1 0.6030 156.1220 143.9600

UNIT 29
COM='CUBOID BUILT AROUND UNIT 1'
ZHEMICYL-Y 2 1 0.6030 143.9600 -0.3180
CUBOID 3 1 2P0.6047 0.0 -0.6047 143.9600 -0.3180
UNIT 30
COM='CUBOID BUILT AROUND UNIT 2'
ZHEMICYL-Y 2 1 0.6030 156.1220 143.9600
CUBOID 0 1 2P0.6047 0.0 -0.6047 156.1220 143.9600
UNIT 31
COM='CUBOID BUILT AROUND UNIT 3'
ZHEMICYL+Y 2 1 0.6030 143.9600 -0.3180
CUBOID 3 1 2P0.6047 0.6047 0.0 143.9600 -0.3180
UNIT 32
COM='CUBOID BUILT AROUND UNIT 4'
ZHEMICYL+Y 2 1 0.6030 156.1220 143.9600
CUBOID 0 1 2P0.6047 0.6047 0.0 156.1220 143.9600

UNIT 33
ZHEMICYL-Y 13 1 0.5150 143.9600 0.0
ZHEMICYL-Y 0 1 0.5220 143.9600 0.0
ZHEMICYL-Y 1 1 0.6030 143.9600 -0.3180
CUBOID 3 1 2P0.6047 0.0 -0.6047 143.9600 -0.3180
UNIT 34
ZHEMICYL-Y 23 1 0.5150 153.3400 143.9600
ZHEMICYL-Y 0 1 0.5220 155.8040 143.9600
ZHEMICYL-Y 1 1 0.6030 156.1220 143.9600
CUBOID 0 1 2P0.6047 0.0 -0.6047 156.1220 143.9600
UNIT 35
ZHEMICYL-Y 14 1 0.5150 143.9600 0.0
ZHEMICYL-Y 0 1 0.5220 143.9600 0.0
ZHEMICYL-Y 1 1 0.6030 143.9600 -0.3180
CUBOID 3 1 2P0.6047 0.0 -0.6047 143.9600 -0.3180
UNIT 36
ZHEMICYL-Y 24 1 0.5150 153.3400 143.9600
ZHEMICYL-Y 0 1 0.5220 155.8040 143.9600
ZHEMICYL-Y 1 1 0.6030 156.1220 143.9600
CUBOID 0 1 2P0.6047 0.0 -0.6047 156.1220 143.9600

```

```

UNIT 37
ZHEMICYL+Y 13 1 0.5150          143.9600 0.0
ZHEMICYL+Y 0 1 0.5220          143.9600 0.0
ZHEMICYL+Y 1 1 0.6030          143.9600 -0.3180
CUBOID      3 1 2P0.6047 0.6047 0.0 143.9600 -0.3180
UNIT 38
ZHEMICYL+Y 23 1 0.5150          153.3400 143.9600
ZHEMICYL+Y 0 1 0.5220          155.8040 143.9600
ZHEMICYL+Y 1 1 0.6030          156.1220 143.9600
CUBOID      0 1 2P0.6047 0.6047 0.0 156.1220 143.9600
UNIT 39
ZHEMICYL+Y 14 1 0.5150          143.9600 0.0
ZHEMICYL+Y 0 1 0.5220          143.9600 0.0
ZHEMICYL+Y 1 1 0.6030          143.9600 -0.3180
CUBOID      3 1 2P0.6047 0.6047 0.0 143.9600 -0.3180
UNIT 40
ZHEMICYL+Y 24 1 0.5150          153.3400 143.9600
ZHEMICYL+Y 0 1 0.5220          155.8040 143.9600
ZHEMICYL+Y 1 1 0.6030          156.1220 143.9600
CUBOID      0 1 2P0.6047 0.6047 0.0 156.1220 143.9600

UNIT 41
COM='CUBOID BUILT AROUND UNIT 3 WITH UNITS 5 & 17 ADDED AS HOLES'
ZHEMICYL+Y 2 1 0.6030 143.9600 -0.3180 ORIGIN 0.0 -1.0473
CUBOID      3 1 2P0.6047 2P1.0473 143.9600 -0.3180
HOLE        5      0.0 1.0473 0.0
HOLE        17     0.6047 0.0 0.0
UNIT 42
COM='CUBOID BUILT AROUND UNIT 4 WITH UNITS 6 & 18 ADDED AS HOLES'
ZHEMICYL+Y 2 1 0.6030 156.1220 143.9600 ORIGIN 0.0 -1.0473
CUBOID      0 1 2P0.6047 2P1.0473 156.1220 143.9600
HOLE        6      0.0 1.0473 0.0
HOLE        18     0.6047 0.0 0.0
UNIT 43
COM='CUBOID BUILT AROUND UNIT 11 WITH UNITS 9 21 & 23 ADDED AS HOLES'
ZHEMICYL+Y 13 1 0.5150 143.9600 0.0000 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 143.9600 0.0000 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 143.9600 -0.3180 ORIGIN 0.0 -1.0473
CUBOID      3 1 2P0.6047 2P1.0473 143.9600 -0.3180
HOLE        9      0.0 1.0473 0.0
HOLE        21     0.6047 0.0 0.0
HOLE        23     -0.6047 0.0 0.0
UNIT 44
COM='CUBOID BUILT AROUND UNIT 12 WITH UNITS 10 22 & 24 ADDED AS HOLES'
ZHEMICYL+Y 23 1 0.5150 153.3400 143.9600 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 155.8040 143.9600 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 156.1220 143.9600 ORIGIN 0.0 -1.0473
CUBOID      0 1 2P0.6047 2P1.0473 156.1220 143.9600
HOLE        10     0.0 1.0473 0.0
HOLE        22     0.6047 0.0 0.0
HOLE        24     -0.6047 0.0 0.0
UNIT 45
COM='CUBOID BUILT AROUND UNIT 13 WITH UNITS 9 21 & 27 ADDED AS HOLES'
ZHEMICYL+Y 14 1 0.5150 143.9600 0.0000 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 143.9600 0.0000 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 143.9600 -0.3180 ORIGIN 0.0 -1.0473
CUBOID      3 1 2P0.6047 2P1.0473 143.9600 -0.3180
HOLE        9      0.0 1.0473 0.0
HOLE        21     0.6047 0.0 0.0
HOLE        27     -0.6047 0.0 0.0
UNIT 46
COM='CUBOID BUILT AROUND UNIT 14 WITH UNITS 10 22 & 28 ADDED AS HOLES'
ZHEMICYL+Y 24 1 0.5150 153.3400 143.9600 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 155.8040 143.9600 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 156.1220 143.9600 ORIGIN 0.0 -1.0473
CUBOID      0 1 2P0.6047 2P1.0473 156.1220 143.9600
HOLE        10     0.0 1.0473 0.0
HOLE        22     0.6047 0.0 0.0
HOLE        28     -0.6047 0.0 0.0
UNIT 47
COM='CUBOID BUILT AROUND UNIT 11 WITH UNITS 9 17 & 27 ADDED AS HOLES'
ZHEMICYL+Y 13 1 0.5150 143.9600 0.0000 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 143.9600 0.0000 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 143.9600 -0.3180 ORIGIN 0.0 -1.0473
CUBOID      3 1 2P0.6047 2P1.0473 143.9600 -0.3180
HOLE        9      0.0 1.0473 0.0
HOLE        17     0.6047 0.0 0.0
HOLE        27     -0.6047 0.0 0.0
UNIT 48
COM='CUBOID BUILT AROUND UNIT 12 WITH UNITS 10 18 & 28 ADDED AS HOLES'
ZHEMICYL+Y 23 1 0.5150 153.3400 143.9600 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 155.8040 143.9600 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 156.1220 143.9600 ORIGIN 0.0 -1.0473
CUBOID      0 1 2P0.6047 2P1.0473 156.1220 143.9600

```

HOLE 10 0.0 1.0473 0.0
HOLE 18 0.6047 0.0 0.0
HOLE 28 -0.6047 0.0 0.0

UNIT 49

COM='CUBOID BUILT AROUND UNIT 3 WITH UNITS 5 & 23 ADDED AS HOLES'

ZHEMICYL+Y 2 1 0.6030 143.9600 -0.3180 ORIGIN 0.0 -1.0473
CUBOID 3 1 2P0.6047 2P1.0473 143.9600 -0.3180
HOLE 5 0.0 1.0473 0.0
HOLE 23 -0.6047 0.0 0.0

UNIT 50

COM='CUBOID BUILT AROUND UNIT 4 WITH UNITS 6 & 24 ADDED AS HOLES'

ZHEMICYL+Y 2 1 0.6030 156.1220 143.9600 ORIGIN 0.0 -1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 143.9600
HOLE 6 0.0 1.0473 0.0
HOLE 24 -0.6047 0.0 0.0

UNIT 51

COM='CUBOID BUILT AROUND UNIT 11 WITH UNITS 5 & 19 ADDED AS HOLES'

ZHEMICYL+Y 13 1 0.5150 143.9600 0.0 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 143.9600 0.0 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 143.9600 -0.3180 ORIGIN 0.0 -1.0473
CUBOID 3 1 2P0.6047 2P1.0473 143.9600 -0.3180
HOLE 5 0.0 1.0473 0.0
HOLE 19 0.6047 0.0 0.0

UNIT 52

COM='CUBOID BUILT AROUND UNIT 12 WITH UNITS 6 & 20 ADDED AS HOLES'

ZHEMICYL+Y 23 1 0.5150 153.3400 143.9600 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 155.8040 143.9600 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 156.1220 143.9600 ORIGIN 0.0 -1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 143.9600
HOLE 6 0.0 1.0473 0.0
HOLE 20 0.6047 0.0 0.0

UNIT 53

COM='CUBOID BUILT AROUND UNIT 15 WITH UNITS 9 21 & 25 ADDED AS HOLES'

ZHEMICYL+Y 16 1 0.5150 143.9600 0.0000 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 143.9600 0.0000 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 143.9600 -0.3180 ORIGIN 0.0 -1.0473
CUBOID 3 1 2P0.6047 2P1.0473 143.9600 -0.3180
HOLE 9 0.0 1.0473 0.0
HOLE 21 0.6047 0.0 0.0
HOLE 25 -0.6047 0.0 0.0

UNIT 54

COM='CUBOID BUILT AROUND UNIT 16 WITH UNITS 10 22 & 26 ADDED AS HOLES'

ZHEMICYL+Y 26 1 0.5150 153.3400 143.9600 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 155.8040 143.9600 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 156.1220 143.9600 ORIGIN 0.0 -1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 143.9600
HOLE 10 0.0 1.0473 0.0
HOLE 22 0.6047 0.0 0.0
HOLE 26 -0.6047 0.0 0.0

UNIT 55

COM='CUBOID BUILT AROUND UNIT 15 WITH UNITS 9 21 & 27 ADDED AS HOLES'

ZHEMICYL+Y 16 1 0.5150 143.9600 0.0000 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 143.9600 0.0000 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 143.9600 -0.3180 ORIGIN 0.0 -1.0473
CUBOID 3 1 2P0.6047 2P1.0473 143.9600 -0.3180
HOLE 9 0.0 1.0473 0.0
HOLE 21 0.6047 0.0 0.0
HOLE 27 -0.6047 0.0 0.0

UNIT 56

COM='CUBOID BUILT AROUND UNIT 16 WITH UNITS 10 22 & 28 ADDED AS HOLES'

ZHEMICYL+Y 26 1 0.5150 153.3400 143.9600 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 155.8040 143.9600 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 156.1220 143.9600 ORIGIN 0.0 -1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 143.9600
HOLE 10 0.0 1.0473 0.0
HOLE 22 0.6047 0.0 0.0
HOLE 28 -0.6047 0.0 0.0

UNIT 57

COM='CUBOID BUILT AROUND UNIT 15 WITH UNITS 9 19 & 27 ADDED AS HOLES'

ZHEMICYL+Y 16 1 0.5150 143.9600 0.0000 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 143.9600 0.0000 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 143.9600 -0.3180 ORIGIN 0.0 -1.0473
CUBOID 3 1 2P0.6047 2P1.0473 143.9600 -0.3180
HOLE 9 0.0 1.0473 0.0
HOLE 19 0.6047 0.0 0.0
HOLE 27 -0.6047 0.0 0.0

UNIT 58

COM='CUBOID BUILT AROUND UNIT 16 WITH UNITS 10 20 & 28 ADDED AS HOLES'

ZHEMICYL+Y 26 1 0.5150 153.3400 143.9600 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 155.8040 143.9600 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 156.1220 143.9600 ORIGIN 0.0 -1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 143.9600

HOLE 10 0.0 1.0473 0.0
HOLE 20 0.6047 0.0 0.0
HOLE 28 -0.6047 0.0 0.0

UNIT 59

COM='CUBOID BUILT AROUND UNIT 11 WITH UNITS 5 & 25 ADDED AS HOLES'

ZHEMICYL+Y 13 1 0.5150 143.9600 0.0 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 143.9600 0.0 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 143.9600 -0.3180 ORIGIN 0.0 -1.0473
CUBOID 3 1 2P0.6047 2P1.0473 143.9600 -0.3180
HOLE 5 0.0 1.0473 0.0
HOLE 25 -0.6047 0.0 0.0

UNIT 60

COM='CUBOID BUILT AROUND UNIT 12 WITH UNITS 6 & 26 ADDED AS HOLES'

ZHEMICYL+Y 23 1 0.5150 153.3400 143.9600 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 155.8040 143.9600 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 156.1220 143.9600 ORIGIN 0.0 -1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 143.9600
HOLE 6 0.0 1.0473 0.0
HOLE 26 -0.6047 0.0 0.0

UNIT 61

COM='CUBOID BUILT AROUND UNIT 1 WITH UNITS 11 & 17 ADDED AS HOLES'

ZHEMICYL-Y 2 1 0.6030 143.9600 -0.3180 ORIGIN 0.0 1.0473
CUBOID 3 1 2P0.6047 2P1.0473 143.9600 -0.3180
HOLE 11 0.0 -1.0473 0.0
HOLE 17 0.6047 0.0 0.0

UNIT 62

COM='CUBOID BUILT AROUND UNIT 2 WITH UNITS 12 & 18 ADDED AS HOLES'

ZHEMICYL-Y 2 1 0.6030 156.1220 143.9600 ORIGIN 0.0 1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 143.9600
HOLE 12 0.0 -1.0473 0.0
HOLE 18 0.6047 0.0 0.0

UNIT 63

COM='CUBOID BUILT AROUND UNIT 5 WITH UNITS 15 21 & 23 ADDED AS HOLES'

ZHEMICYL-Y 13 1 0.5150 143.9600 0.0000 ORIGIN 0.0 1.0473
ZHEMICYL-Y 0 1 0.5220 143.9600 0.0000 ORIGIN 0.0 1.0473
ZHEMICYL-Y 1 1 0.6030 143.9600 -0.3180 ORIGIN 0.0 1.0473
CUBOID 3 1 2P0.6047 2P1.0473 143.9600 -0.3180
HOLE 15 0.0 -1.0473 0.0
HOLE 21 0.6047 0.0 0.0
HOLE 23 -0.6047 0.0 0.0

UNIT 64

COM='CUBOID BUILT AROUND UNIT 6 WITH UNITS 16 22 & 24 ADDED AS HOLES'

ZHEMICYL-Y 23 1 0.5150 153.3400 143.9600 ORIGIN 0.0 1.0473
ZHEMICYL-Y 0 1 0.5220 155.8040 143.9600 ORIGIN 0.0 1.0473
ZHEMICYL-Y 1 1 0.6030 156.1220 143.9600 ORIGIN 0.0 1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 143.9600
HOLE 16 0.0 -1.0473 0.0
HOLE 22 0.6047 0.0 0.0
HOLE 24 -0.6047 0.0 0.0

UNIT 65

COM='CUBOID BUILT AROUND UNIT 7 WITH UNITS 15 21 & 27 ADDED AS HOLES'

ZHEMICYL-Y 14 1 0.5150 143.9600 0.0000 ORIGIN 0.0 1.0473
ZHEMICYL-Y 0 1 0.5220 143.9600 0.0000 ORIGIN 0.0 1.0473
ZHEMICYL-Y 1 1 0.6030 143.9600 -0.3180 ORIGIN 0.0 1.0473
CUBOID 3 1 2P0.6047 2P1.0473 143.9600 -0.3180
HOLE 15 0.0 -1.0473 0.0
HOLE 21 0.6047 0.0 0.0
HOLE 27 -0.6047 0.0 0.0

UNIT 66

COM='CUBOID BUILT AROUND UNIT 8 WITH UNITS 16 22 & 28 ADDED AS HOLES'

ZHEMICYL-Y 24 1 0.5150 153.3400 143.9600 ORIGIN 0.0 1.0473
ZHEMICYL-Y 0 1 0.5220 155.8040 143.9600 ORIGIN 0.0 1.0473
ZHEMICYL-Y 1 1 0.6030 156.1220 143.9600 ORIGIN 0.0 1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 143.9600
HOLE 16 0.0 -1.0473 0.0
HOLE 22 0.6047 0.0 0.0
HOLE 28 -0.6047 0.0 0.0

UNIT 67

COM='CUBOID BUILT AROUND UNIT 5 WITH UNITS 15 17 & 27 ADDED AS HOLES'

ZHEMICYL-Y 13 1 0.5150 143.9600 0.0000 ORIGIN 0.0 1.0473
ZHEMICYL-Y 0 1 0.5220 143.9600 0.0000 ORIGIN 0.0 1.0473
ZHEMICYL-Y 1 1 0.6030 143.9600 -0.3180 ORIGIN 0.0 1.0473
CUBOID 3 1 2P0.6047 2P1.0473 143.9600 -0.3180
HOLE 15 0.0 -1.0473 0.0
HOLE 17 0.6047 0.0 0.0
HOLE 27 -0.6047 0.0 0.0

UNIT 68

COM='CUBOID BUILT AROUND UNIT 6 WITH UNITS 16 18 & 28 ADDED AS HOLES'

ZHEMICYL-Y 23 1 0.5150 153.3400 143.9600 ORIGIN 0.0 1.0473
ZHEMICYL-Y 0 1 0.5220 155.8040 143.9600 ORIGIN 0.0 1.0473
ZHEMICYL-Y 1 1 0.6030 156.1220 143.9600 ORIGIN 0.0 1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 143.9600

HOLE 16 0.0 -1.0473 0.0
 HOLE 18 0.6047 0.0 0.0
 HOLE 28 -0.6047 0.0 0.0

UNIT 69
 COM='CUBOID BUILT AROUND UNIT 1 WITH UNITS 11 & 23 ADDED AS HOLES'
 ZHEMICYL-Y 2 1 0.6030 143.9600 -0.3180 ORIGIN 0.0 1.0473
 CUBOID 3 1 2P0.6047 2P1.0473 143.9600 -0.3180
 HOLE 11 0.0 -1.0473 0.0
 HOLE 23 -0.6047 0.0 0.0

UNIT 70
 COM='CUBOID BUILT AROUND UNIT 2 WITH UNITS 12 & 24 ADDED AS HOLES'
 ZHEMICYL-Y 2 1 0.6030 156.1220 143.9600 ORIGIN 0.0 1.0473
 CUBOID 0 1 2P0.6047 2P1.0473 156.1220 143.9600
 HOLE 12 0.0 -1.0473 0.0
 HOLE 24 -0.6047 0.0 0.0

UNIT 71
 COM='FUEL MODULE W/O AL SIDE PLATES, BELOW WATER'
 ARRAY 1 -9.0705 -8.9832 -0.3180
 CUBOID 3 1 2P9.5250 2P9.5250 143.9600 -0.3180
 CUBOID 4 1 2P9.5250 2P9.5250 143.9600 -1.3848
 CUBOID 2 1 2P9.5250 2P9.5250 143.9600 -3.1755
 CUBOID 3 1 2P9.9595 2P9.9556 143.9600 -3.1755

UNIT 72
 COM='FUEL MODULE W/O AL SIDE PLATES, ABOVE WATER'
 ARRAY 2 -9.0705 -8.9832 143.9600
 CUBOID 0 1 2P9.5250 2P9.5250 156.1220 143.9600
 CUBOID 2 1 2P9.5250 2P9.5250 157.7095 143.9600
 CUBOID 0 1 2P9.9595 2P9.9556 157.7095 143.9600

UNIT 73
 COM='FUEL MODULE WITH AL SIDE PLATES, BELOW WATER'
 ARRAY 1 -9.0705 -8.9832 -0.3180
 CUBOID 3 1 2P9.0705 2P9.3957 143.9600 -0.3180
 CUBOID 2 1 2P9.0705 2P9.5250 143.9600 -0.3180
 CUBOID 3 1 2P9.5250 2P9.5250 143.9600 -0.3180
 CUBOID 4 1 2P9.5250 2P9.5250 143.9600 -1.3848
 CUBOID 2 1 2P9.5250 2P9.5250 143.9600 -3.1755
 CUBOID 3 1 2P9.9595 2P9.9556 143.9600 -3.1755

UNIT 74
 COM='FUEL MODULE WITH AL SIDE PLATES, ABOVE WATER'
 ARRAY 2 -9.0705 -8.9832 143.9600
 CUBOID 0 1 2P9.0705 2P9.3957 156.1220 143.9600
 CUBOID 2 1 2P9.0705 2P9.5250 156.1220 143.9600
 CUBOID 0 1 2P9.5250 2P9.5250 156.1220 143.9600
 CUBOID 2 1 2P9.5250 2P9.5250 157.7095 143.9600
 CUBOID 0 1 2P9.9595 2P9.9556 157.7095 143.9600

UNIT 75
 COM='5X5X1 ARRAY OF FUEL MODULES, BELOW WATER'
 ARRAY 3 -49.7975 -49.7780 -3.1755
 CUBOID 3 1 2P60.9600 2P60.9600 143.9600 -3.1755
 CUBOID 2 1 2P60.9600 2P60.9600 143.9600 -11.8115
 CYLINDER 3 1 137.1600 143.9600 -14.6815
 CYLINDER 5 1 138.1600 143.9600 -15.6815
 CUBOID 0 1 4P138.1600 143.9600 -30.9215

UNIT 76
 COM='5X5X1 ARRAY OF FUEL MODULES, ABOVE WATER'
 ARRAY 4 -49.7975 -49.7780 143.9600
 CUBOID 0 1 2P60.9600 2P60.9600 157.7095 143.9600
 CYLINDER 0 1 137.1600 157.7095 143.9600
 CYLINDER 5 1 138.1600 157.7095 143.9600
 CUBOID 0 1 4P138.1600 157.7095 143.9600

GLOBAL
 UNIT 77
 COM='STACK UNIT 76 ATOP UNIT 75'
 ARRAY 5 -138.1600 -138.1600 -30.9215
 END GEOM

READ ARRAY
 ARA=1 NUX=15 NUY=10 NUZ=1
 COM='FUEL MODULE ARRAY, BELOW WATER'
 FILL 29 33 11R35 33 29
 41 43 11R45 47 49
 51 53 11R55 57 59 5Q15
 61 63 11R65 67 69
 31 37 11R39 37 31 END FILL
 ARA=2 NUX=15 NUY=10 NUZ=1
 COM='FUEL MODULE ARRAY, ABOVE WATER'
 FILL 30 34 11R36 34 30
 42 44 11R46 48 50
 52 54 11R56 58 60 5Q15
 62 64 11R66 68 70
 32 38 11R40 38 32 END FILL

ARA=3 NUX=5 NUY=5 NUZ=1
COM='ARRAY OF FUEL MODULES BELOW WATER'
FILL

5R71
71 3R73 71
5R71
71 3R73 71
5R71 END FILL

ARA=4 NUX=5 NUY=5 NUZ=1
COM='ARRAY OF FUEL MODULES ABOVE WATER'
FILL

5R72
72 3R74 72
5R72
72 3R74 72
5R72 END FILL

ARA=5 NUX=1 NUY=1 NUZ=2
COM='STACKING ABOVE WATER UNIT ATOP BELOW WATER UNIT'
FILL 75 76 END FILL
END ARRAY

READ MIXT EPS=1. END MIXT
READ BOUNDS -ZB=CONC8 END BOUNDS
READ START NST=1 END START
END DATA
END

VALIDATION CASE (CLT02)

=CSAS25
BAW-1645-4, EXP'MT-2457, CASE C-2-C, DANC OFF FACTOR FOR EACH FUEL PIN
27GROUPNDF4 LATTICECELL

AL	1	1.0	296.0	END
AL	2	1.0	296.0	END
H2O	3	1.0	296.0	END
BORON	3	1.3191-4	296.0	END
H2O	4	0.75	296.0	END
BORON	4	0.9894-4	296.0	END
AL	4	0.25	296.0	END
CARBONSTEEL	5	1.0	296.0	END
UO2	13	0.9325	296.0	92235 2.459 92238 97.541 END
UO2	14	0.9325	296.0	92235 2.459 92238 97.541 END
UO2	15	0.9325	296.0	92235 2.459 92238 97.541 END
UO2	16	0.9325	296.0	92235 2.459 92238 97.541 END
UO2	23	0.9325	296.0	92235 2.459 92238 97.541 END
UO2	24	0.9325	296.0	92235 2.459 92238 97.541 END
UO2	25	0.9325	296.0	92235 2.459 92238 97.541 END
UO2	26	0.9325	296.0	92235 2.459 92238 97.541 END

END COMP
TRIANGPITCH 1.2093 1.0300 16 3 1.2060 1 1.0440 0 END

MORE DATA RES=13 CYLINDER 0.5150 DAN(13)=0.37809
RES=14 CYLINDER 0.5150 DAN(14)=0.50536
RES=15 CYLINDER 0.5150 DAN(15)=0.63264
RES=23 CYLINDER 0.5150 DAN(23)=0.46920
RES=24 CYLINDER 0.5150 DAN(24)=0.63217
RES=25 CYLINDER 0.5150 DAN(25)=0.79514
RES=26 CYLINDER 0.5150 DAN(26)=0.97782 END MORE

BAW-1645-4, EXP'MT-2457, CASE C-2-C, DANC OFF FACTOR FOR EACH FUEL PIN
READ PARAM TME=40 FDN=YES NUB=YES END PARAM
READ GEOM

UNIT 1
ZHEMICYL-Y 2 1 0.6030 104.8200 -0.3180
UNIT 2
ZHEMICYL-Y 2 1 0.6030 156.1220 104.8200
UNIT 3
ZHEMICYL+Y 2 1 0.6030 104.8200 -0.3180
UNIT 4
ZHEMICYL+Y 2 1 0.6030 156.1220 104.8200

UNIT 5
ZHEMICYL-Y 13 1 0.5150 104.8200 0.0
ZHEMICYL-Y 0 1 0.5220 104.8200 0.0
ZHEMICYL-Y 1 1 0.6030 104.8200 -0.3180
UNIT 6
ZHEMICYL-Y 23 1 0.5150 153.3400 104.8200
ZHEMICYL-Y 0 1 0.5220 155.8040 104.8200
ZHEMICYL-Y 1 1 0.6030 156.1220 104.8200
UNIT 7
ZHEMICYL-Y 14 1 0.5150 104.8200 0.0
ZHEMICYL-Y 0 1 0.5220 104.8200 0.0
ZHEMICYL-Y 1 1 0.6030 104.8200 -0.3180
UNIT 8
ZHEMICYL-Y 24 1 0.5150 153.3400 104.8200
ZHEMICYL-Y 0 1 0.5220 155.8040 104.8200
ZHEMICYL-Y 1 1 0.6030 156.1220 104.8200

```

UNIT 9
ZHEMICYL-Y 16 1 0.5150 104.8200 0.0
ZHEMICYL-Y 0 1 0.5220 104.8200 0.0
ZHEMICYL-Y 1 1 0.6030 104.8200 -0.3180
UNIT 10
ZHEMICYL-Y 26 1 0.5150 153.3400 104.8200
ZHEMICYL-Y 0 1 0.5220 155.8040 104.8200
ZHEMICYL-Y 1 1 0.6030 156.1220 104.8200
UNIT 11
ZHEMICYL+Y 13 1 0.5150 104.8200 0.0
ZHEMICYL+Y 0 1 0.5220 104.8200 0.0
ZHEMICYL+Y 1 1 0.6030 104.8200 -0.3180
UNIT 12
ZHEMICYL+Y 23 1 0.5150 153.3400 104.8200
ZHEMICYL+Y 0 1 0.5220 155.8040 104.8200
ZHEMICYL+Y 1 1 0.6030 156.1220 104.8200
UNIT 13
ZHEMICYL+Y 14 1 0.5150 104.8200 0.0
ZHEMICYL+Y 0 1 0.5220 104.8200 0.0
ZHEMICYL+Y 1 1 0.6030 104.8200 -0.3180
UNIT 14
ZHEMICYL+Y 24 1 0.5150 153.3400 104.8200
ZHEMICYL+Y 0 1 0.5220 155.8040 104.8200
ZHEMICYL+Y 1 1 0.6030 156.1220 104.8200
UNIT 15
ZHEMICYL+Y 16 1 0.5150 104.8200 0.0
ZHEMICYL+Y 0 1 0.5220 104.8200 0.0
ZHEMICYL+Y 1 1 0.6030 104.8200 -0.3180
UNIT 16
ZHEMICYL+Y 26 1 0.5150 153.3400 104.8200
ZHEMICYL+Y 0 1 0.5220 155.8040 104.8200
ZHEMICYL+Y 1 1 0.6030 156.1220 104.8200
UNIT 17
ZHEMICYL-X 14 1 0.5150 104.8200 0.0
ZHEMICYL-X 0 1 0.5220 104.8200 0.0
ZHEMICYL-X 1 1 0.6030 104.8200 -0.3180
UNIT 18
ZHEMICYL-X 24 1 0.5150 153.3400 104.8200
ZHEMICYL-X 0 1 0.5220 155.8040 104.8200
ZHEMICYL-X 1 1 0.6030 156.1220 104.8200
UNIT 19
ZHEMICYL-X 15 1 0.5150 104.8200 0.0
ZHEMICYL-X 0 1 0.5220 104.8200 0.0
ZHEMICYL-X 1 1 0.6030 104.8200 -0.3180
UNIT 20
ZHEMICYL-X 25 1 0.5150 153.3400 104.8200
ZHEMICYL-X 0 1 0.5220 155.8040 104.8200
ZHEMICYL-X 1 1 0.6030 156.1220 104.8200
UNIT 21
ZHEMICYL-X 16 1 0.5150 104.8200 0.0
ZHEMICYL-X 0 1 0.5220 104.8200 0.0
ZHEMICYL-X 1 1 0.6030 104.8200 -0.3180
UNIT 22
ZHEMICYL-X 26 1 0.5150 153.3400 104.8200
ZHEMICYL-X 0 1 0.5220 155.8040 104.8200
ZHEMICYL-X 1 1 0.6030 156.1220 104.8200
UNIT 23
ZHEMICYL+X 14 1 0.5150 104.8200 0.0
ZHEMICYL+X 0 1 0.5220 104.8200 0.0
ZHEMICYL+X 1 1 0.6030 104.8200 -0.3180
UNIT 24
ZHEMICYL+X 24 1 0.5150 153.3400 104.8200
ZHEMICYL+X 0 1 0.5220 155.8040 104.8200
ZHEMICYL+X 1 1 0.6030 156.1220 104.8200
UNIT 25
ZHEMICYL+X 15 1 0.5150 104.8200 0.0
ZHEMICYL+X 0 1 0.5220 104.8200 0.0
ZHEMICYL+X 1 1 0.6030 104.8200 -0.3180
UNIT 26
ZHEMICYL+X 25 1 0.5150 153.3400 104.8200
ZHEMICYL+X 0 1 0.5220 155.8040 104.8200
ZHEMICYL+X 1 1 0.6030 156.1220 104.8200
UNIT 27
ZHEMICYL+X 16 1 0.5150 104.8200 0.0
ZHEMICYL+X 0 1 0.5220 104.8200 0.0
ZHEMICYL+X 1 1 0.6030 104.8200 -0.3180
UNIT 28
ZHEMICYL+X 26 1 0.5150 153.3400 104.8200
ZHEMICYL+X 0 1 0.5220 155.8040 104.8200
ZHEMICYL+X 1 1 0.6030 156.1220 104.8200
UNIT 29
COM='CUBOID BUILT AROUND UNIT 1'
ZHEMICYL-Y 2 1 0.6030 104.8200 -0.3180
CUBOID 3 1 2P0.6047 0.0 -0.6047 104.8200 -0.3180

```



```

UNIT 30
COM='CUBOID BUILT AROUND UNIT 2'
ZHEMICYL-Y 2 1 0.6030 156.1220 104.8200
CUBOID 0 1 2P0.6047 0.0 -0.6047 156.1220 104.8200
UNIT 31
COM='CUBOID BUILT AROUND UNIT 3'
ZHEMICYL+Y 2 1 0.6030 104.8200 -0.3180
CUBOID 3 1 2P0.6047 0.6047 0.0 104.8200 -0.3180
UNIT 32
COM='CUBOID BUILT AROUND UNIT 4'
ZHEMICYL+Y 2 1 0.6030 156.1220 104.8200
CUBOID 0 1 2P0.6047 0.6047 0.0 156.1220 104.8200
UNIT 33
ZHEMICYL-Y 13 1 0.5150 104.8200 0.0
ZHEMICYL-Y 0 1 0.5220 104.8200 0.0
ZHEMICYL-Y 1 1 0.6030 104.8200 -0.3180
CUBOID 3 1 2P0.6047 0.0 -0.6047 104.8200 -0.3180
UNIT 34
ZHEMICYL-Y 23 1 0.5150 153.3400 104.8200
ZHEMICYL-Y 0 1 0.5220 155.8040 104.8200
ZHEMICYL-Y 1 1 0.6030 156.1220 104.8200
CUBOID 0 1 2P0.6047 0.0 -0.6047 156.1220 104.8200
UNIT 35
ZHEMICYL-Y 14 1 0.5150 104.8200 0.0
ZHEMICYL-Y 0 1 0.5220 104.8200 0.0
ZHEMICYL-Y 1 1 0.6030 104.8200 -0.3180
CUBOID 3 1 2P0.6047 0.0 -0.6047 104.8200 -0.3180
UNIT 36
ZHEMICYL-Y 24 1 0.5150 153.3400 104.8200
ZHEMICYL-Y 0 1 0.5220 155.8040 104.8200
ZHEMICYL-Y 1 1 0.6030 156.1220 104.8200
CUBOID 0 1 2P0.6047 0.0 -0.6047 156.1220 104.8200
UNIT 37
ZHEMICYL+Y 13 1 0.5150 104.8200 0.0
ZHEMICYL+Y 0 1 0.5220 104.8200 0.0
ZHEMICYL+Y 1 1 0.6030 104.8200 -0.3180
CUBOID 3 1 2P0.6047 0.6047 0.0 104.8200 -0.3180
UNIT 38
ZHEMICYL+Y 23 1 0.5150 153.3400 104.8200
ZHEMICYL+Y 0 1 0.5220 155.8040 104.8200
ZHEMICYL+Y 1 1 0.6030 156.1220 104.8200
CUBOID 0 1 2P0.6047 0.6047 0.0 156.1220 104.8200
UNIT 39
ZHEMICYL+Y 14 1 0.5150 104.8200 0.0
ZHEMICYL+Y 0 1 0.5220 104.8200 0.0
ZHEMICYL+Y 1 1 0.6030 104.8200 -0.3180
CUBOID 3 1 2P0.6047 0.6047 0.0 104.8200 -0.3180
UNIT 40
ZHEMICYL+Y 24 1 0.5150 153.3400 104.8200
ZHEMICYL+Y 0 1 0.5220 155.8040 104.8200
ZHEMICYL+Y 1 1 0.6030 156.1220 104.8200
CUBOID 0 1 2P0.6047 0.6047 0.0 156.1220 104.8200
UNIT 41
COM='CUBOID BUILT AROUND UNIT 3 WITH UNITS 5 & 17 ADDED AS HOLES'
ZHEMICYL+Y 2 1 0.6030 104.8200 -0.3180 ORIGIN 0.0 -1.0473
CUBOID 3 1 2P0.6047 2P1.0473 104.8200 -0.3180
HOLE 5 0.0 1.0473 0.0
HOLE 17 0.6047 0.0 0.0
UNIT 42
COM='CUBOID BUILT AROUND UNIT 4 WITH UNITS 6 & 18 ADDED AS HOLES'
ZHEMICYL+Y 2 1 0.6030 156.1220 104.8200 ORIGIN 0.0 -1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 104.8200
HOLE 6 0.0 1.0473 0.0
HOLE 18 0.6047 0.0 0.0
UNIT 43
COM='CUBOID BUILT AROUND UNIT 11 WITH UNITS 9 21 & 23 ADDED AS HOLES'
ZHEMICYL+Y 13 1 0.5150 104.8200 0.0000 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 104.8200 0.0000 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 104.8200 -0.3180 ORIGIN 0.0 -1.0473
CUBOID 3 1 2P0.6047 2P1.0473 104.8200 -0.3180
HOLE 9 0.0 1.0473 0.0
HOLE 21 0.6047 0.0 0.0
HOLE 23 -0.6047 0.0 0.0
UNIT 44
COM='CUBOID BUILT AROUND UNIT 12 WITH UNITS 10 22 & 24 ADDED AS HOLES'
ZHEMICYL+Y 23 1 0.5150 153.3400 104.8200 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 155.8040 104.8200 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 156.1220 104.8200 ORIGIN 0.0 -1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 104.8200
HOLE 10 0.0 1.0473 0.0
HOLE 22 0.6047 0.0 0.0
HOLE 24 -0.6047 0.0 0.0

```

```

UNIT 45
COM='CUBOID BUILT AROUND UNIT 13 WITH UNITS 9 21 & 27 ADDED AS HOLES'
ZHEMICYL+Y 14 1 0.5150 104.8200 0.0000 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 104.8200 0.0000 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 104.8200 -0.3180 ORIGIN 0.0 -1.0473
CUBOID 3 1 2P0.6047 2P1.0473 104.8200 -0.3180
HOLE 9 0.0 1.0473 0.0
HOLE 21 0.6047 0.0 0.0
HOLE 27 -0.6047 0.0 0.0
UNIT 46
COM='CUBOID BUILT AROUND UNIT 14 WITH UNITS 10 22 & 28 ADDED AS HOLES'
ZHEMICYL+Y 24 1 0.5150 153.3400 104.8200 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 155.8040 104.8200 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 156.1220 104.8200 ORIGIN 0.0 -1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 104.8200
HOLE 10 0.0 1.0473 0.0
HOLE 22 0.6047 0.0 0.0
HOLE 28 -0.6047 0.0 0.0
UNIT 47
COM='CUBOID BUILT AROUND UNIT 11 WITH UNITS 9 17 & 27 ADDED AS HOLES'
ZHEMICYL+Y 13 1 0.5150 104.8200 0.0000 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 104.8200 0.0000 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 104.8200 -0.3180 ORIGIN 0.0 -1.0473
CUBOID 3 1 2P0.6047 2P1.0473 104.8200 -0.3180
HOLE 9 0.0 1.0473 0.0
HOLE 17 0.6047 0.0 0.0
HOLE 27 -0.6047 0.0 0.0
UNIT 48
COM='CUBOID BUILT AROUND UNIT 12 WITH UNITS 10 18 & 28 ADDED AS HOLES'
ZHEMICYL+Y 23 1 0.5150 153.3400 104.8200 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 155.8040 104.8200 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 156.1220 104.8200 ORIGIN 0.0 -1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 104.8200
HOLE 10 0.0 1.0473 0.0
HOLE 18 0.6047 0.0 0.0
HOLE 28 -0.6047 0.0 0.0
UNIT 49
COM='CUBOID BUILT AROUND UNIT 3 WITH UNITS 5 & 23 ADDED AS HOLES'
ZHEMICYL+Y 2 1 0.6030 104.8200 -0.3180 ORIGIN 0.0 -1.0473
CUBOID 3 1 2P0.6047 2P1.0473 104.8200 -0.3180
HOLE 5 0.0 1.0473 0.0
HOLE 23 -0.6047 0.0 0.0
UNIT 50
COM='CUBOID BUILT AROUND UNIT 4 WITH UNITS 6 & 24 ADDED AS HOLES'
ZHEMICYL+Y 2 1 0.6030 156.1220 104.8200 ORIGIN 0.0 -1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 104.8200
HOLE 6 0.0 1.0473 0.0
HOLE 24 -0.6047 0.0 0.0
UNIT 51
COM='CUBOID BUILT AROUND UNIT 11 WITH UNITS 5 & 19 ADDED AS HOLES'
ZHEMICYL+Y 13 1 0.5150 104.8200 0.0 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 104.8200 0.0 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 104.8200 -0.3180 ORIGIN 0.0 -1.0473
CUBOID 3 1 2P0.6047 2P1.0473 104.8200 -0.3180
HOLE 5 0.0 1.0473 0.0
HOLE 19 0.6047 0.0 0.0
UNIT 52
COM='CUBOID BUILT AROUND UNIT 12 WITH UNITS 6 & 20 ADDED AS HOLES'
ZHEMICYL+Y 23 1 0.5150 153.3400 104.8200 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 155.8040 104.8200 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 156.1220 104.8200 ORIGIN 0.0 -1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 104.8200
HOLE 6 0.0 1.0473 0.0
HOLE 20 0.6047 0.0 0.0
UNIT 53
COM='CUBOID BUILT AROUND UNIT 15 WITH UNITS 9 21 & 25 ADDED AS HOLES'
ZHEMICYL+Y 16 1 0.5150 104.8200 0.0000 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 104.8200 0.0000 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 104.8200 -0.3180 ORIGIN 0.0 -1.0473
CUBOID 3 1 2P0.6047 2P1.0473 104.8200 -0.3180
HOLE 9 0.0 1.0473 0.0
HOLE 21 0.6047 0.0 0.0
HOLE 25 -0.6047 0.0 0.0
UNIT 54
COM='CUBOID BUILT AROUND UNIT 16 WITH UNITS 10 22 & 26 ADDED AS HOLES'
ZHEMICYL+Y 26 1 0.5150 153.3400 104.8200 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 155.8040 104.8200 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 156.1220 104.8200 ORIGIN 0.0 -1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 104.8200
HOLE 10 0.0 1.0473 0.0
HOLE 22 0.6047 0.0 0.0
HOLE 26 -0.6047 0.0 0.0

```

UNIT 55
 COM='CUBOID BUILT AROUND UNIT 15 WITH UNITS 9 21 & 27 ADDED AS HOLES'
 ZHEMICYL+Y 16 1 0.5150 104.8200 0.0000 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 0 1 0.5220 104.8200 0.0000 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 1 1 0.6030 104.8200 -0.3180 ORIGIN 0.0 -1.0473
 CUBOID 3 1 2P0.6047 2P1.0473 104.8200 -0.3180
 HOLE 9 0.0 1.0473 0.0
 HOLE 21 0.6047 0.0 0.0
 HOLE 27 -0.6047 0.0 0.0

UNIT 56
 COM='CUBOID BUILT AROUND UNIT 16 WITH UNITS 10 22 & 28 ADDED AS HOLES'
 ZHEMICYL+Y 26 1 0.5150 153.3400 104.8200 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 0 1 0.5220 155.8040 104.8200 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 1 1 0.6030 156.1220 104.8200 ORIGIN 0.0 -1.0473
 CUBOID 0 1 2P0.6047 2P1.0473 156.1220 104.8200
 HOLE 10 0.0 1.0473 0.0
 HOLE 22 0.6047 0.0 0.0
 HOLE 28 -0.6047 0.0 0.0

UNIT 57
 COM='CUBOID BUILT AROUND UNIT 15 WITH UNITS 9 19 & 27 ADDED AS HOLES'
 ZHEMICYL+Y 16 1 0.5150 104.8200 0.0000 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 0 1 0.5220 104.8200 0.0000 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 1 1 0.6030 104.8200 -0.3180 ORIGIN 0.0 -1.0473
 CUBOID 3 1 2P0.6047 2P1.0473 104.8200 -0.3180
 HOLE 9 0.0 1.0473 0.0
 HOLE 19 0.6047 0.0 0.0
 HOLE 27 -0.6047 0.0 0.0

UNIT 58
 COM='CUBOID BUILT AROUND UNIT 16 WITH UNITS 10 20 & 28 ADDED AS HOLES'
 ZHEMICYL+Y 26 1 0.5150 153.3400 104.8200 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 0 1 0.5220 155.8040 104.8200 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 1 1 0.6030 156.1220 104.8200 ORIGIN 0.0 -1.0473
 CUBOID 0 1 2P0.6047 2P1.0473 156.1220 104.8200
 HOLE 10 0.0 1.0473 0.0
 HOLE 20 0.6047 0.0 0.0
 HOLE 28 -0.6047 0.0 0.0

UNIT 59
 COM='CUBOID BUILT AROUND UNIT 11 WITH UNITS 5 & 25 ADDED AS HOLES'
 ZHEMICYL+Y 13 1 0.5150 104.8200 0.0 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 0 1 0.5220 104.8200 0.0 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 1 1 0.6030 104.8200 -0.3180 ORIGIN 0.0 -1.0473
 CUBOID 3 1 2P0.6047 2P1.0473 104.8200 -0.3180
 HOLE 5 0.0 1.0473 0.0
 HOLE 25 -0.6047 0.0 0.0

UNIT 60
 COM='CUBOID BUILT AROUND UNIT 12 WITH UNITS 6 & 26 ADDED AS HOLES'
 ZHEMICYL+Y 23 1 0.5150 153.3400 104.8200 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 0 1 0.5220 155.8040 104.8200 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 1 1 0.6030 156.1220 104.8200 ORIGIN 0.0 -1.0473
 CUBOID 0 1 2P0.6047 2P1.0473 156.1220 104.8200
 HOLE 6 0.0 1.0473 0.0
 HOLE 26 -0.6047 0.0 0.0

UNIT 61
 COM='CUBOID BUILT AROUND UNIT 1 WITH UNITS 11 & 17 ADDED AS HOLES'
 ZHEMICYL-Y 2 1 0.6030 104.8200 -0.3180 ORIGIN 0.0 1.0473
 CUBOID 3 1 2P0.6047 2P1.0473 104.8200 -0.3180
 HOLE 11 0.0 -1.0473 0.0
 HOLE 17 0.6047 0.0 0.0

UNIT 62
 COM='CUBOID BUILT AROUND UNIT 2 WITH UNITS 12 & 18 ADDED AS HOLES'
 ZHEMICYL-Y 2 1 0.6030 156.1220 104.8200 ORIGIN 0.0 1.0473
 CUBOID 0 1 2P0.6047 2P1.0473 156.1220 104.8200
 HOLE 12 0.0 -1.0473 0.0
 HOLE 18 0.6047 0.0 0.0

UNIT 63
 COM='CUBOID BUILT AROUND UNIT 5 WITH UNITS 15 21 & 23 ADDED AS HOLES'
 ZHEMICYL-Y 13 1 0.5150 104.8200 0.0000 ORIGIN 0.0 1.0473
 ZHEMICYL-Y 0 1 0.5220 104.8200 0.0000 ORIGIN 0.0 1.0473
 ZHEMICYL-Y 1 1 0.6030 104.8200 -0.3180 ORIGIN 0.0 1.0473
 CUBOID 3 1 2P0.6047 2P1.0473 104.8200 -0.3180
 HOLE 15 0.0 -1.0473 0.0
 HOLE 21 0.6047 0.0 0.0
 HOLE 23 -0.6047 0.0 0.0

UNIT 64
 COM='CUBOID BUILT AROUND UNIT 6 WITH UNITS 16 22 & 24 ADDED AS HOLES'
 ZHEMICYL-Y 23 1 0.5150 153.3400 104.8200 ORIGIN 0.0 1.0473
 ZHEMICYL-Y 0 1 0.5220 155.8040 104.8200 ORIGIN 0.0 1.0473
 ZHEMICYL-Y 1 1 0.6030 156.1220 104.8200 ORIGIN 0.0 1.0473
 CUBOID 0 1 2P0.6047 2P1.0473 156.1220 104.8200
 HOLE 16 0.0 -1.0473 0.0
 HOLE 22 0.6047 0.0 0.0
 HOLE 24 -0.6047 0.0 0.0

UNIT 65
COM='CUBOID BUILT AROUND UNIT 7 WITH UNITS 15 21 & 27 ADDED AS HOLES'
ZHEMICYL-Y 14 1 0.5150 104.8200 0.0000 ORIGIN 0.0 1.0473
ZHEMICYL-Y 0 1 0.5220 104.8200 0.0000 ORIGIN 0.0 1.0473
ZHEMICYL-Y 1 1 0.6030 104.8200 -0.3180 ORIGIN 0.0 1.0473
CUBOID 3 1 2P0.6047 2P1.0473 104.8200 -0.3180
HOLE 15 0.0 -1.0473 0.0
HOLE 21 0.6047 0.0 0.0
HOLE 27 -0.6047 0.0 0.0

UNIT 66
COM='CUBOID BUILT AROUND UNIT 8 WITH UNITS 16 22 & 28 ADDED AS HOLES'
ZHEMICYL-Y 24 1 0.5150 153.3400 104.8200 ORIGIN 0.0 1.0473
ZHEMICYL-Y 0 1 0.5220 155.8040 104.8200 ORIGIN 0.0 1.0473
ZHEMICYL-Y 1 1 0.6030 156.1220 104.8200 ORIGIN 0.0 1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 104.8200
HOLE 16 0.0 -1.0473 0.0
HOLE 22 0.6047 0.0 0.0
HOLE 28 -0.6047 0.0 0.0

UNIT 67
COM='CUBOID BUILT AROUND UNIT 5 WITH UNITS 15 17 & 27 ADDED AS HOLES'
ZHEMICYL-Y 13 1 0.5150 104.8200 0.0000 ORIGIN 0.0 1.0473
ZHEMICYL-Y 0 1 0.5220 104.8200 0.0000 ORIGIN 0.0 1.0473
ZHEMICYL-Y 1 1 0.6030 104.8200 -0.3180 ORIGIN 0.0 1.0473
CUBOID 3 1 2P0.6047 2P1.0473 104.8200 -0.3180
HOLE 15 0.0 -1.0473 0.0
HOLE 17 0.6047 0.0 0.0
HOLE 27 -0.6047 0.0 0.0

UNIT 68
COM='CUBOID BUILT AROUND UNIT 6 WITH UNITS 16 18 & 28 ADDED AS HOLES'
ZHEMICYL-Y 23 1 0.5150 153.3400 104.8200 ORIGIN 0.0 1.0473
ZHEMICYL-Y 0 1 0.5220 155.8040 104.8200 ORIGIN 0.0 1.0473
ZHEMICYL-Y 1 1 0.6030 156.1220 104.8200 ORIGIN 0.0 1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 104.8200
HOLE 16 0.0 -1.0473 0.0
HOLE 18 0.6047 0.0 0.0
HOLE 28 -0.6047 0.0 0.0

UNIT 69
COM='CUBOID BUILT AROUND UNIT 1 WITH UNITS 11 & 23 ADDED AS HOLES'
ZHEMICYL-Y 2 1 0.6030 104.8200 -0.3180 ORIGIN 0.0 1.0473
CUBOID 3 1 2P0.6047 2P1.0473 104.8200 -0.3180
HOLE 11 0.0 -1.0473 0.0
HOLE 23 -0.6047 0.0 0.0

UNIT 70
COM='CUBOID BUILT AROUND UNIT 2 WITH UNITS 12 & 24 ADDED AS HOLES'
ZHEMICYL-Y 2 1 0.6030 156.1220 104.8200 ORIGIN 0.0 1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 104.8200
HOLE 12 0.0 -1.0473 0.0
HOLE 24 -0.6047 0.0 0.0

UNIT 71
COM='FUEL MODULE W/O AL SIDE PLATES, BELOW WATER'
ARRAY 1 -9.0705 -8.9832 -0.3180
CUBOID 3 1 2P9.5250 2P9.5250 104.8200 -0.3180
CUBOID 4 1 2P9.5250 2P9.5250 104.8200 -1.3848
CUBOID 2 1 2P9.5250 2P9.5250 104.8200 -3.1755
CUBOID 3 1 2P9.9595 2P9.9556 104.8200 -3.1755

UNIT 72
COM='FUEL MODULE W/O AL SIDE PLATES, ABOVE WATER'
ARRAY 2 -9.0705 -8.9832 104.8200
CUBOID 0 1 2P9.5250 2P9.5250 156.1220 104.8200
CUBOID 2 1 2P9.5250 2P9.5250 157.7095 104.8200
CUBOID 0 1 2P9.9595 2P9.9556 157.7095 104.8200

UNIT 73
COM='FUEL MODULE WITH AL SIDE PLATES, BELOW WATER'
ARRAY 1 -9.0705 -8.9832 -0.3180
CUBOID 3 1 2P9.0705 2P9.3957 104.8200 -0.3180
CUBOID 2 1 2P9.0705 2P9.5250 104.8200 -0.3180
CUBOID 3 1 2P9.5250 2P9.5250 104.8200 -0.3180
CUBOID 4 1 2P9.5250 2P9.5250 104.8200 -1.3848
CUBOID 2 1 2P9.5250 2P9.5250 104.8200 -3.1755
CUBOID 3 1 2P9.9595 2P9.9556 104.8200 -3.1755

UNIT 74
COM='FUEL MODULE WITH AL SIDE PLATES, ABOVE WATER'
ARRAY 2 -9.0705 -8.9832 104.8200
CUBOID 0 1 2P9.0705 2P9.3957 156.1220 104.8200
CUBOID 2 1 2P9.0705 2P9.5250 156.1220 104.8200
CUBOID 0 1 2P9.5250 2P9.5250 156.1220 104.8200
CUBOID 2 1 2P9.5250 2P9.5250 157.7095 104.8200
CUBOID 0 1 2P9.9595 2P9.9556 157.7095 104.8200

UNIT 75
COM='5X5X1 ARRAY OF FUEL MODULES, BELOW WATER'
ARRAY 3 -49.7975 -49.7780 -3.1755
CUBOID 3 1 2P60.9600 2P60.9600 104.8200 -3.1755

```

CUBOID 2 1 2P60.9600 2P60.9600 104.8200 -11.8115
CYLINDER 3 1 137.1600 104.8200 -14.6815
CYLINDER 5 1 138.1600 104.8200 -15.6815
CUBOID 0 1 4P138.1600 104.8200 -30.9215
UNIT 76
COM='5X5X1 ARRAY OF FUEL MODULES, ABOVE WATER'
ARRAY 4 -49.7975 -49.7780 104.8200
CUBOID 0 1 2P60.9600 2P60.9600 157.7095 104.8200
CYLINDER 0 1 137.1600 157.7095 104.8200
CYLINDER 5 1 138.1600 157.7095 104.8200
CUBOID 0 1 4P138.1600 157.7095 104.8200

```

```

GLOBAL
UNIT 77
COM='STACK UNIT 76 ATOP UNIT 75'
ARRAY 5 -138.1600 -138.1600 -30.9215
END GEOM

```

```

READ ARRAY
ARA=1 NUX=15 NUY=10 NUZ=1
COM='FUEL MODULE ARRAY, BELOW WATER'
FILL 29 33 11R35 33 29
41 43 11R45 47 49
51 53 11R55 57 59 5Q15
61 63 11R65 67 69
31 37 11R39 37 31 END FILL
ARA=2 NUX=15 NUY=10 NUZ=1
COM='FUEL MODULE ARRAY, ABOVE WATER'
FILL 30 34 11R36 34 30
42 44 11R46 48 50
52 54 11R56 58 60 5Q15
62 64 11R66 68 70
32 38 11R40 38 32 END FILL

```

```

ARA=3 NUX=5 NUY=5 NUZ=1
COM='ARRAY OF FUEL MODULES BELOW WATER'
FILL 5R71
71 3R73 71
5R71
71 3R73 71
5R71 END FILL

```

```

ARA=4 NUX=5 NUY=5 NUZ=1
COM='ARRAY OF FUEL MODULES ABOVE WATER'
FILL 5R72
72 3R74 72
5R72
72 3R74 72
5R72 END FILL

```

```

ARA=5 NUX=1 NUY=1 NUZ=2
COM='STACKING ABOVE WATER UNIT ATOP BELOW WATER UNIT'
FILL 75 76 END FILL
END ARRAY

```

```

READ MIXT EPS=1. END MIXT
READ BOUNDS -ZB=CONC8 END BOUNDS
READ START NST=1 END START
END DATA
END

```

```

VALIDATION CASE (CLT03 )
=CSAS25
BAW-1645-4, EXP'MT-2464, CASE C-2-C, DANC OFF FACTOR FOR EACH FUEL PIN
27GROUPNDF4 LATTICECELL
AL 1 1.0 293.0 END
AL 2 1.0 293.0 END
H2O 3 1.0 293.0 END
BORON 3 1.4215-4 293.0 END
H2O 4 0.75 293.0 END
BORON 4 1.0663-4 293.0 END
AL 4 0.25 293.0 END
CARBONSTEEL 5 1.0 293.0 END
UO2 13 0.9325 293.0 92235 2.459 92238 97.541 END
UO2 14 0.9325 293.0 92235 2.459 92238 97.541 END
UO2 15 0.9325 293.0 92235 2.459 92238 97.541 END
UO2 16 0.9325 293.0 92235 2.459 92238 97.541 END
UO2 23 0.9325 293.0 92235 2.459 92238 97.541 END
UO2 24 0.9325 293.0 92235 2.459 92238 97.541 END
UO2 25 0.9325 293.0 92235 2.459 92238 97.541 END
UO2 26 0.9325 293.0 92235 2.459 92238 97.541 END
END COMP
TRIANGPITCH 1.2093 1.0300 16 3 1.2060 1 1.0440 0 END
MORE DATA RES=13 CYLINDER 0.5150 DAN(13)=0.37808
RES=14 CYLINDER 0.5150 DAN(14)=0.50536
RES=15 CYLINDER 0.5150 DAN(15)=0.63264
RES=23 CYLINDER 0.5150 DAN(23)=0.46920
RES=24 CYLINDER 0.5150 DAN(24)=0.63217

```

RES=25 CYLINDER 0.5150 DAN(25)=0.79514
 RES=26 CYLINDER 0.5150 DAN(26)=0.97782 END MORE
 BAW-1645-4, EXP'MT-2464 CASE C-2-C, DANCOFF FACTOR FOR EACH FUEL PIN
 READ PARAM TME=40 FDN=YES NUB=YES END PARAM
 READ GEOM

UNIT 1
 ZHEMICYL-Y 2 1 0.6030 142.5400 -0.3180
 UNIT 2
 ZHEMICYL-Y 2 1 0.6030 156.1220 142.5400
 UNIT 3
 ZHEMICYL+Y 2 1 0.6030 142.5400 -0.3180
 UNIT 4
 ZHEMICYL+Y 2 1 0.6030 156.1220 142.5400

UNIT 5
 ZHEMICYL-Y 13 1 0.5150 142.5400 0.0
 ZHEMICYL-Y 0 1 0.5220 142.5400 0.0
 ZHEMICYL-Y 1 1 0.6030 142.5400 -0.3180

UNIT 6
 ZHEMICYL-Y 23 1 0.5150 153.3400 142.5400
 ZHEMICYL-Y 0 1 0.5220 155.8040 142.5400
 ZHEMICYL-Y 1 1 0.6030 156.1220 142.5400

UNIT 7
 ZHEMICYL-Y 14 1 0.5150 142.5400 0.0
 ZHEMICYL-Y 0 1 0.5220 142.5400 0.0
 ZHEMICYL-Y 1 1 0.6030 142.5400 -0.3180

UNIT 8
 ZHEMICYL-Y 24 1 0.5150 153.3400 142.5400
 ZHEMICYL-Y 0 1 0.5220 155.8040 142.5400
 ZHEMICYL-Y 1 1 0.6030 156.1220 142.5400

UNIT 9
 ZHEMICYL-Y 16 1 0.5150 142.5400 0.0
 ZHEMICYL-Y 0 1 0.5220 142.5400 0.0
 ZHEMICYL-Y 1 1 0.6030 142.5400 -0.3180

UNIT 10
 ZHEMICYL-Y 26 1 0.5150 153.3400 142.5400
 ZHEMICYL-Y 0 1 0.5220 155.8040 142.5400
 ZHEMICYL-Y 1 1 0.6030 156.1220 142.5400

UNIT 11
 ZHEMICYL+Y 13 1 0.5150 142.5400 0.0
 ZHEMICYL+Y 0 1 0.5220 142.5400 0.0
 ZHEMICYL+Y 1 1 0.6030 142.5400 -0.3180

UNIT 12
 ZHEMICYL+Y 23 1 0.5150 153.3400 142.5400
 ZHEMICYL+Y 0 1 0.5220 155.8040 142.5400
 ZHEMICYL+Y 1 1 0.6030 156.1220 142.5400

UNIT 13
 ZHEMICYL+Y 14 1 0.5150 142.5400 0.0
 ZHEMICYL+Y 0 1 0.5220 142.5400 0.0
 ZHEMICYL+Y 1 1 0.6030 142.5400 -0.3180

UNIT 14
 ZHEMICYL+Y 24 1 0.5150 153.3400 142.5400
 ZHEMICYL+Y 0 1 0.5220 155.8040 142.5400
 ZHEMICYL+Y 1 1 0.6030 156.1220 142.5400

UNIT 15
 ZHEMICYL+Y 16 1 0.5150 142.5400 0.0
 ZHEMICYL+Y 0 1 0.5220 142.5400 0.0
 ZHEMICYL+Y 1 1 0.6030 142.5400 -0.3180

UNIT 16
 ZHEMICYL+Y 26 1 0.5150 153.3400 142.5400
 ZHEMICYL+Y 0 1 0.5220 155.8040 142.5400
 ZHEMICYL+Y 1 1 0.6030 156.1220 142.5400

UNIT 17
 ZHEMICYL-X 14 1 0.5150 142.5400 0.0
 ZHEMICYL-X 0 1 0.5220 142.5400 0.0
 ZHEMICYL-X 1 1 0.6030 142.5400 -0.3180

UNIT 18
 ZHEMICYL-X 24 1 0.5150 153.3400 142.5400
 ZHEMICYL-X 0 1 0.5220 155.8040 142.5400
 ZHEMICYL-X 1 1 0.6030 156.1220 142.5400

UNIT 19
 ZHEMICYL-X 15 1 0.5150 142.5400 0.0
 ZHEMICYL-X 0 1 0.5220 142.5400 0.0
 ZHEMICYL-X 1 1 0.6030 142.5400 -0.3180

UNIT 20
 ZHEMICYL-X 25 1 0.5150 153.3400 142.5400
 ZHEMICYL-X 0 1 0.5220 155.8040 142.5400
 ZHEMICYL-X 1 1 0.6030 156.1220 142.5400

UNIT 21
 ZHEMICYL-X 16 1 0.5150 142.5400 0.0
 ZHEMICYL-X 0 1 0.5220 142.5400 0.0
 ZHEMICYL-X 1 1 0.6030 142.5400 -0.3180

UNIT 22
 ZHEMICYL-X 26 1 0.5150 153.3400 142.5400

ZHEMICYL-X 0 1 0.5220 155.8040 142.5400
 ZHEMICYL-X 1 1 0.6030 156.1220 142.5400

UNIT 23

ZHEMICYL+X 14 1 0.5150 142.5400 0.0
 ZHEMICYL+X 0 1 0.5220 142.5400 0.0
 ZHEMICYL+X 1 1 0.6030 142.5400 -0.3180

UNIT 24

ZHEMICYL+X 24 1 0.5150 153.3400 142.5400
 ZHEMICYL+X 0 1 0.5220 155.8040 142.5400
 ZHEMICYL+X 1 1 0.6030 156.1220 142.5400

UNIT 25

ZHEMICYL+X 15 1 0.5150 142.5400 0.0
 ZHEMICYL+X 0 1 0.5220 142.5400 0.0
 ZHEMICYL+X 1 1 0.6030 142.5400 -0.3180

UNIT 26

ZHEMICYL+X 25 1 0.5150 153.3400 142.5400
 ZHEMICYL+X 0 1 0.5220 155.8040 142.5400
 ZHEMICYL+X 1 1 0.6030 156.1220 142.5400

UNIT 27

ZHEMICYL+X 16 1 0.5150 142.5400 0.0
 ZHEMICYL+X 0 1 0.5220 142.5400 0.0
 ZHEMICYL+X 1 1 0.6030 142.5400 -0.3180

UNIT 28

ZHEMICYL+X 26 1 0.5150 153.3400 142.5400
 ZHEMICYL+X 0 1 0.5220 155.8040 142.5400
 ZHEMICYL+X 1 1 0.6030 156.1220 142.5400

UNIT 29

COM='CUBOID BUILT AROUND UNIT 1'
 ZHEMICYL-Y 2 1 0.6030 142.5400 -0.3180
 CUBOID 3 1 2P0.6047 0.0 -0.6047 142.5400 -0.3180

UNIT 30

COM='CUBOID BUILT AROUND UNIT 2'
 ZHEMICYL-Y 2 1 0.6030 156.1220 142.5400
 CUBOID 0 1 2P0.6047 0.0 -0.6047 156.1220 142.5400

UNIT 31

COM='CUBOID BUILT AROUND UNIT 3'
 ZHEMICYL+Y 2 1 0.6030 142.5400 -0.3180
 CUBOID 3 1 2P0.6047 0.6047 0.0 142.5400 -0.3180

UNIT 32

COM='CUBOID BUILT AROUND UNIT 4'
 ZHEMICYL+Y 2 1 0.6030 156.1220 142.5400
 CUBOID 0 1 2P0.6047 0.6047 0.0 156.1220 142.5400

UNIT 33

ZHEMICYL-Y 13 1 0.5150 142.5400 0.0
 ZHEMICYL-Y 0 1 0.5220 142.5400 0.0
 ZHEMICYL-Y 1 1 0.6030 142.5400 -0.3180
 CUBOID 3 1 2P0.6047 0.0 -0.6047 142.5400 -0.3180

UNIT 34

ZHEMICYL-Y 23 1 0.5150 153.3400 142.5400
 ZHEMICYL-Y 0 1 0.5220 155.8040 142.5400
 ZHEMICYL-Y 1 1 0.6030 156.1220 142.5400
 CUBOID 0 1 2P0.6047 0.0 -0.6047 156.1220 142.5400

UNIT 35

ZHEMICYL-Y 14 1 0.5150 142.5400 0.0
 ZHEMICYL-Y 0 1 0.5220 142.5400 0.0
 ZHEMICYL-Y 1 1 0.6030 142.5400 -0.3180
 CUBOID 3 1 2P0.6047 0.0 -0.6047 142.5400 -0.3180

UNIT 36

ZHEMICYL-Y 24 1 0.5150 153.3400 142.5400
 ZHEMICYL-Y 0 1 0.5220 155.8040 142.5400
 ZHEMICYL-Y 1 1 0.6030 156.1220 142.5400
 CUBOID 0 1 2P0.6047 0.0 -0.6047 156.1220 142.5400

UNIT 37

ZHEMICYL+Y 13 1 0.5150 142.5400 0.0
 ZHEMICYL+Y 0 1 0.5220 142.5400 0.0
 ZHEMICYL+Y 1 1 0.6030 142.5400 -0.3180
 CUBOID 3 1 2P0.6047 0.6047 0.0 142.5400 -0.3180

UNIT 38

ZHEMICYL+Y 23 1 0.5150 153.3400 142.5400
 ZHEMICYL+Y 0 1 0.5220 155.8040 142.5400
 ZHEMICYL+Y 1 1 0.6030 156.1220 142.5400
 CUBOID 0 1 2P0.6047 0.6047 0.0 156.1220 142.5400

UNIT 39

ZHEMICYL+Y 14 1 0.5150 142.5400 0.0
 ZHEMICYL+Y 0 1 0.5220 142.5400 0.0
 ZHEMICYL+Y 1 1 0.6030 142.5400 -0.3180
 CUBOID 3 1 2P0.6047 0.6047 0.0 142.5400 -0.3180

UNIT 40

ZHEMICYL+Y 24 1 0.5150 153.3400 142.5400
 ZHEMICYL+Y 0 1 0.5220 155.8040 142.5400
 ZHEMICYL+Y 1 1 0.6030 156.1220 142.5400
 CUBOID 0 1 2P0.6047 0.6047 0.0 156.1220 142.5400

```

UNIT 41
COM='CUBOID BUILT AROUND UNIT 3 WITH UNITS 5 & 17 ADDED AS HOLES'
ZHEMICYL+Y 2 1 0.6030 142.5400 -0.3180 ORIGIN 0.0 -1.0473
CUBOID 3 1 2P0.6047 2P1.0473 142.5400 -0.3180
HOLE 5 0.0 1.0473 0.0
HOLE 17 0.6047 0.0 0.0
UNIT 42
COM='CUBOID BUILT AROUND UNIT 4 WITH UNITS 6 & 18 ADDED AS HOLES'
ZHEMICYL+Y 2 1 0.6030 156.1220 142.5400 ORIGIN 0.0 -1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 142.5400
HOLE 6 0.0 1.0473 0.0
HOLE 18 0.6047 0.0 0.0
UNIT 43
COM='CUBOID BUILT AROUND UNIT 11 WITH UNITS 9 21 & 23 ADDED AS HOLES'
ZHEMICYL+Y 13 1 0.5150 142.5400 0.0000 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 142.5400 0.0000 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 142.5400 -0.3180 ORIGIN 0.0 -1.0473
CUBOID 3 1 2P0.6047 2P1.0473 142.5400 -0.3180
HOLE 9 0.0 1.0473 0.0
HOLE 21 0.6047 0.0 0.0
HOLE 23 -0.6047 0.0 0.0
UNIT 44
COM='CUBOID BUILT AROUND UNIT 12 WITH UNITS 10 22 & 24 ADDED AS HOLES'
ZHEMICYL+Y 23 1 0.5150 153.3400 142.5400 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 155.8040 142.5400 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 156.1220 142.5400 ORIGIN 0.0 -1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 142.5400
HOLE 10 0.0 1.0473 0.0
HOLE 22 0.6047 0.0 0.0
HOLE 24 -0.6047 0.0 0.0
UNIT 45
COM='CUBOID BUILT AROUND UNIT 13 WITH UNITS 9 21 & 27 ADDED AS HOLES'
ZHEMICYL+Y 14 1 0.5150 142.5400 0.0000 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 142.5400 0.0000 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 142.5400 -0.3180 ORIGIN 0.0 -1.0473
CUBOID 3 1 2P0.6047 2P1.0473 142.5400 -0.3180
HOLE 9 0.0 1.0473 0.0
HOLE 21 0.6047 0.0 0.0
HOLE 27 -0.6047 0.0 0.0
UNIT 46
COM='CUBOID BUILT AROUND UNIT 14 WITH UNITS 10 22 & 28 ADDED AS HOLES'
ZHEMICYL+Y 24 1 0.5150 153.3400 142.5400 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 155.8040 142.5400 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 156.1220 142.5400 ORIGIN 0.0 -1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 142.5400
HOLE 10 0.0 1.0473 0.0
HOLE 22 0.6047 0.0 0.0
HOLE 28 -0.6047 0.0 0.0
UNIT 47
COM='CUBOID BUILT AROUND UNIT 11 WITH UNITS 9 17 & 27 ADDED AS HOLES'
ZHEMICYL+Y 13 1 0.5150 142.5400 0.0000 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 142.5400 0.0000 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 142.5400 -0.3180 ORIGIN 0.0 -1.0473
CUBOID 3 1 2P0.6047 2P1.0473 142.5400 -0.3180
HOLE 9 0.0 1.0473 0.0
HOLE 17 0.6047 0.0 0.0
HOLE 27 -0.6047 0.0 0.0
UNIT 48
COM='CUBOID BUILT AROUND UNIT 12 WITH UNITS 10 18 & 28 ADDED AS HOLES'
ZHEMICYL+Y 23 1 0.5150 153.3400 142.5400 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 155.8040 142.5400 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 156.1220 142.5400 ORIGIN 0.0 -1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 142.5400
HOLE 10 0.0 1.0473 0.0
HOLE 18 0.6047 0.0 0.0
HOLE 28 -0.6047 0.0 0.0
UNIT 49
COM='CUBOID BUILT AROUND UNIT 3 WITH UNITS 5 & 23 ADDED AS HOLES'
ZHEMICYL+Y 2 1 0.6030 142.5400 -0.3180 ORIGIN 0.0 -1.0473
CUBOID 3 1 2P0.6047 2P1.0473 142.5400 -0.3180
HOLE 5 0.0 1.0473 0.0
HOLE 23 -0.6047 0.0 0.0
UNIT 50
COM='CUBOID BUILT AROUND UNIT 4 WITH UNITS 6 & 24 ADDED AS HOLES'
ZHEMICYL+Y 2 1 0.6030 156.1220 142.5400 ORIGIN 0.0 -1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 142.5400
HOLE 6 0.0 1.0473 0.0
HOLE 24 -0.6047 0.0 0.0
UNIT 51
COM='CUBOID BUILT AROUND UNIT 11 WITH UNITS 5 & 19 ADDED AS HOLES'
ZHEMICYL+Y 13 1 0.5150 142.5400 0.0 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 142.5400 0.0 ORIGIN 0.0 -1.0473

```


ZHEMICYL+Y 1 1 0.6030 142.5400 -0.3180 ORIGIN 0.0 -1.0473
 CUBOID 3 1 2P0.6047 2P1.0473 142.5400 -0.3180
 HOLE 5 0.0 1.0473 0.0
 HOLE 19 0.6047 0.0 0.0

UNIT 52

COM='CUBOID BUILT AROUND UNIT 12 WITH UNITS 6 & 20 ADDED AS HOLES'

ZHEMICYL+Y 23 1 0.5150 153.3400 142.5400 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 0 1 0.5220 155.8040 142.5400 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 1 1 0.6030 156.1220 142.5400 ORIGIN 0.0 -1.0473
 CUBOID 0 1 2P0.6047 2P1.0473 156.1220 142.5400
 HOLE 6 0.0 1.0473 0.0
 HOLE 20 0.6047 0.0 0.0

UNIT 53

COM='CUBOID BUILT AROUND UNIT 15 WITH UNITS 9 21 & 25 ADDED AS HOLES'

ZHEMICYL+Y 16 1 0.5150 142.5400 0.0000 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 0 1 0.5220 142.5400 0.0000 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 1 1 0.6030 142.5400 -0.3180 ORIGIN 0.0 -1.0473
 CUBOID 3 1 2P0.6047 2P1.0473 142.5400 -0.3180
 HOLE 9 0.0 1.0473 0.0
 HOLE 21 0.6047 0.0 0.0
 HOLE 25 -0.6047 0.0 0.0

UNIT 54

COM='CUBOID BUILT AROUND UNIT 16 WITH UNITS 10 22 & 26 ADDED AS HOLES'

ZHEMICYL+Y 26 1 0.5150 153.3400 142.5400 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 0 1 0.5220 155.8040 142.5400 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 1 1 0.6030 156.1220 142.5400 ORIGIN 0.0 -1.0473
 CUBOID 0 1 2P0.6047 2P1.0473 156.1220 142.5400
 HOLE 10 0.0 1.0473 0.0
 HOLE 22 0.6047 0.0 0.0
 HOLE 26 -0.6047 0.0 0.0

UNIT 55

COM='CUBOID BUILT AROUND UNIT 15 WITH UNITS 9 21 & 27 ADDED AS HOLES'

ZHEMICYL+Y 16 1 0.5150 142.5400 0.0000 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 0 1 0.5220 142.5400 0.0000 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 1 1 0.6030 142.5400 -0.3180 ORIGIN 0.0 -1.0473
 CUBOID 3 1 2P0.6047 2P1.0473 142.5400 -0.3180
 HOLE 9 0.0 1.0473 0.0
 HOLE 21 0.6047 0.0 0.0
 HOLE 27 -0.6047 0.0 0.0

UNIT 56

COM='CUBOID BUILT AROUND UNIT 16 WITH UNITS 10 22 & 28 ADDED AS HOLES'

ZHEMICYL+Y 26 1 0.5150 153.3400 142.5400 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 0 1 0.5220 155.8040 142.5400 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 1 1 0.6030 156.1220 142.5400 ORIGIN 0.0 -1.0473
 CUBOID 0 1 2P0.6047 2P1.0473 156.1220 142.5400
 HOLE 10 0.0 1.0473 0.0
 HOLE 22 0.6047 0.0 0.0
 HOLE 28 -0.6047 0.0 0.0

UNIT 57

COM='CUBOID BUILT AROUND UNIT 15 WITH UNITS 9 19 & 27 ADDED AS HOLES'

ZHEMICYL+Y 16 1 0.5150 142.5400 0.0000 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 0 1 0.5220 142.5400 0.0000 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 1 1 0.6030 142.5400 -0.3180 ORIGIN 0.0 -1.0473
 CUBOID 3 1 2P0.6047 2P1.0473 142.5400 -0.3180
 HOLE 9 0.0 1.0473 0.0
 HOLE 19 0.6047 0.0 0.0
 HOLE 27 -0.6047 0.0 0.0

UNIT 58

COM='CUBOID BUILT AROUND UNIT 16 WITH UNITS 10 20 & 28 ADDED AS HOLES'

ZHEMICYL+Y 26 1 0.5150 153.3400 142.5400 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 0 1 0.5220 155.8040 142.5400 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 1 1 0.6030 156.1220 142.5400 ORIGIN 0.0 -1.0473
 CUBOID 0 1 2P0.6047 2P1.0473 156.1220 142.5400
 HOLE 10 0.0 1.0473 0.0
 HOLE 20 0.6047 0.0 0.0
 HOLE 28 -0.6047 0.0 0.0

UNIT 59

COM='CUBOID BUILT AROUND UNIT 11 WITH UNITS 5 & 25 ADDED AS HOLES'

ZHEMICYL+Y 13 1 0.5150 142.5400 0.0 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 0 1 0.5220 142.5400 0.0 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 1 1 0.6030 142.5400 -0.3180 ORIGIN 0.0 -1.0473
 CUBOID 3 1 2P0.6047 2P1.0473 142.5400 -0.3180
 HOLE 5 0.0 1.0473 0.0
 HOLE 25 -0.6047 0.0 0.0

UNIT 60

COM='CUBOID BUILT AROUND UNIT 12 WITH UNITS 6 & 26 ADDED AS HOLES'

ZHEMICYL+Y 23 1 0.5150 153.3400 142.5400 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 0 1 0.5220 155.8040 142.5400 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 1 1 0.6030 156.1220 142.5400 ORIGIN 0.0 -1.0473
 CUBOID 0 1 2P0.6047 2P1.0473 156.1220 142.5400
 HOLE 6 0.0 1.0473 0.0
 HOLE 26 -0.6047 0.0 0.0

```

UNIT 61
COM='CUBOID BUILT AROUND UNIT 1 WITH UNITS 11 & 17 ADDED AS HOLES'
ZHEMICYL-Y 2 1 0.6030 142.5400 -0.3180 ORIGIN 0.0 1.0473
CUBOID 3 1 2P0.6047 2P1.0473 142.5400 -0.3180
HOLE 11 0.0 -1.0473 0.0
HOLE 17 0.6047 0.0 0.0

UNIT 62
COM='CUBOID BUILT AROUND UNIT 2 WITH UNITS 12 & 18 ADDED AS HOLES'
ZHEMICYL-Y 2 1 0.6030 156.1220 142.5400 ORIGIN 0.0 1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 142.5400
HOLE 12 0.0 -1.0473 0.0
HOLE 18 0.6047 0.0 0.0

UNIT 63
COM='CUBOID BUILT AROUND UNIT 5 WITH UNITS 15 21 & 23 ADDED AS HOLES'
ZHEMICYL-Y 13 1 0.5150 142.5400 0.0000 ORIGIN 0.0 1.0473
ZHEMICYL-Y 0 1 0.5220 142.5400 0.0000 ORIGIN 0.0 1.0473
ZHEMICYL-Y 1 1 0.6030 142.5400 -0.3180 ORIGIN 0.0 1.0473
CUBOID 3 1 2P0.6047 2P1.0473 142.5400 -0.3180
HOLE 15 0.0 -1.0473 0.0
HOLE 21 0.6047 0.0 0.0
HOLE 23 -0.6047 0.0 0.0

UNIT 64
COM='CUBOID BUILT AROUND UNIT 6 WITH UNITS 16 22 & 24 ADDED AS HOLES'
ZHEMICYL-Y 23 1 0.5150 153.3400 142.5400 ORIGIN 0.0 1.0473
ZHEMICYL-Y 0 1 0.5220 155.8040 142.5400 ORIGIN 0.0 1.0473
ZHEMICYL-Y 1 1 0.6030 156.1220 142.5400 ORIGIN 0.0 1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 142.5400
HOLE 16 0.0 -1.0473 0.0
HOLE 22 0.6047 0.0 0.0
HOLE 24 -0.6047 0.0 0.0

UNIT 65
COM='CUBOID BUILT AROUND UNIT 7 WITH UNITS 15 21 & 27 ADDED AS HOLES'
ZHEMICYL-Y 14 1 0.5150 142.5400 0.0000 ORIGIN 0.0 1.0473
ZHEMICYL-Y 0 1 0.5220 142.5400 0.0000 ORIGIN 0.0 1.0473
ZHEMICYL-Y 1 1 0.6030 142.5400 -0.3180 ORIGIN 0.0 1.0473
CUBOID 3 1 2P0.6047 2P1.0473 142.5400 -0.3180
HOLE 15 0.0 -1.0473 0.0
HOLE 21 0.6047 0.0 0.0
HOLE 27 -0.6047 0.0 0.0

UNIT 66
COM='CUBOID BUILT AROUND UNIT 8 WITH UNITS 16 22 & 28 ADDED AS HOLES'
ZHEMICYL-Y 24 1 0.5150 153.3400 142.5400 ORIGIN 0.0 1.0473
ZHEMICYL-Y 0 1 0.5220 155.8040 142.5400 ORIGIN 0.0 1.0473
ZHEMICYL-Y 1 1 0.6030 156.1220 142.5400 ORIGIN 0.0 1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 142.5400
HOLE 16 0.0 -1.0473 0.0
HOLE 22 0.6047 0.0 0.0
HOLE 28 -0.6047 0.0 0.0

UNIT 67
COM='CUBOID BUILT AROUND UNIT 5 WITH UNITS 15 17 & 27 ADDED AS HOLES'
ZHEMICYL-Y 13 1 0.5150 142.5400 0.0000 ORIGIN 0.0 1.0473
ZHEMICYL-Y 0 1 0.5220 142.5400 0.0000 ORIGIN 0.0 1.0473
ZHEMICYL-Y 1 1 0.6030 142.5400 -0.3180 ORIGIN 0.0 1.0473
CUBOID 3 1 2P0.6047 2P1.0473 142.5400 -0.3180
HOLE 15 0.0 -1.0473 0.0
HOLE 17 0.6047 0.0 0.0
HOLE 27 -0.6047 0.0 0.0

UNIT 68
COM='CUBOID BUILT AROUND UNIT 6 WITH UNITS 16 18 & 28 ADDED AS HOLES'
ZHEMICYL-Y 23 1 0.5150 153.3400 142.5400 ORIGIN 0.0 1.0473
ZHEMICYL-Y 0 1 0.5220 155.8040 142.5400 ORIGIN 0.0 1.0473
ZHEMICYL-Y 1 1 0.6030 156.1220 142.5400 ORIGIN 0.0 1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 142.5400
HOLE 16 0.0 -1.0473 0.0
HOLE 18 0.6047 0.0 0.0
HOLE 28 -0.6047 0.0 0.0

UNIT 69
COM='CUBOID BUILT AROUND UNIT 1 WITH UNITS 11 & 23 ADDED AS HOLES'
ZHEMICYL-Y 2 1 0.6030 142.5400 -0.3180 ORIGIN 0.0 1.0473
CUBOID 3 1 2P0.6047 2P1.0473 142.5400 -0.3180
HOLE 11 0.0 -1.0473 0.0
HOLE 23 -0.6047 0.0 0.0

UNIT 70
COM='CUBOID BUILT AROUND UNIT 2 WITH UNITS 12 & 24 ADDED AS HOLES'
ZHEMICYL-Y 2 1 0.6030 156.1220 142.5400 ORIGIN 0.0 1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 142.5400
HOLE 12 0.0 -1.0473 0.0
HOLE 24 -0.6047 0.0 0.0

UNIT 71
COM='FUEL MODULE W/O AL SIDE PLATES, BELOW WATER'
ARRAY 1 -9.0705 -8.9832 -0.3180
CUBOID 3 1 2P9.5250 2P9.5250 142.5400 -0.3180

```

```

CUBOID 4 1 2P9.5250 2P9.5250 142.5400 -1.3848
CUBOID 2 1 2P9.5250 2P9.5250 142.5400 -3.1755
CUBOID 3 1 2P10.3400 2P10.3367 142.5400 -3.1755
UNIT 72
COM='FUEL MODULE W/O AL SIDE PLATES, ABOVE WATER'
ARRAY 2 -9.0705 -8.9832 142.5400
CUBOID 0 1 2P9.5250 2P9.5250 156.1220 142.5400
CUBOID 2 1 2P9.5250 2P9.5250 157.7095 142.5400
CUBOID 0 1 2P10.3400 2P10.3367 157.7095 142.5400

UNIT 73
COM='FUEL MODULE WITH AL SIDE PLATES, BELOW WATER'
ARRAY 1 -9.0705 -8.9832 -0.3180
CUBOID 3 1 2P9.0705 2P9.3957 142.5400 -0.3180
CUBOID 2 1 2P9.0705 2P9.5250 142.5400 -0.3180
CUBOID 3 1 2P9.5250 2P9.5250 142.5400 -0.3180
CUBOID 4 1 2P9.5250 2P9.5250 142.5400 -1.3848
CUBOID 2 1 2P9.5250 2P9.5250 142.5400 -3.1755
CUBOID 3 1 2P10.3400 2P10.3367 142.5400 -3.1755
UNIT 74
COM='FUEL MODULE WITH AL SIDE PLATES, ABOVE WATER'
ARRAY 2 -9.0705 -8.9832 142.5400
CUBOID 0 1 2P9.0705 2P9.3957 156.1220 142.5400
CUBOID 2 1 2P9.0705 2P9.5250 156.1220 142.5400
CUBOID 0 1 2P9.5250 2P9.5250 156.1220 142.5400
CUBOID 2 1 2P9.5250 2P9.5250 157.7095 142.5400
CUBOID 0 1 2P10.3400 2P10.3367 157.7095 142.5400

UNIT 75
COM='5X5X1 ARRAY OF FUEL MODULES, BELOW WATER'
ARRAY 3 -51.7000 -51.6880 -3.1755
CUBOID 3 1 2P60.9600 2P60.9600 142.5400 -3.1755
CUBOID 2 1 2P60.9600 2P60.9600 142.5400 -11.8115
CYLINDER 3 1 137.1600 142.5400 -14.6815
CYLINDER 5 1 138.1600 142.5400 -15.6815
CUBOID 0 1 4P138.1600 142.5400 -30.9215
UNIT 76
COM='5X5X1 ARRAY OF FUEL MODULES, ABOVE WATER'
ARRAY 4 -51.7000 -51.6880 142.5400
CUBOID 0 1 2P60.9600 2P60.9600 157.7095 142.5400
CYLINDER 0 1 137.1600 157.7095 142.5400
CYLINDER 5 1 138.1600 157.7095 142.5400
CUBOID 0 1 4P138.1600 157.7095 142.5400

GLOBAL
UNIT 77
COM='STACK UNIT 76 ATOP UNIT 75'
ARRAY 5 -138.1600 -138.1600 -30.9215
END GEOM

READ ARRAY
ARA=1 NUX=15 NUY=10 NUZ=1
COM='FUEL MODULE ARRAY, BELOW WATER'
FILL 29 33 11R35 33 29
      41 43 11R45 47 49
      51 53 11R55 57 59 5Q15
      61 63 11R65 67 69
      31 37 11R39 37 31 END FILL
ARA=2 NUX=15 NUY=10 NUZ=1
COM='FUEL MODULE ARRAY, ABOVE WATER'
FILL 30 34 11R36 34 30
      42 44 11R46 48 50
      52 54 11R56 58 60 5Q15
      62 64 11R66 68 70
      32 38 11R40 38 32 END FILL

ARA=3 NUX=5 NUY=5 NUZ=1
COM='ARRAY OF FUEL MODULES BELOW WATER'
FILL 5R71
      71 3R73 71
      5R71
      71 3R73 71
      5R71 END FILL
ARA=4 NUX=5 NUY=5 NUZ=1
COM='ARRAY OF FUEL MODULES ABOVE WATER'
FILL 5R72
      72 3R74 72
      5R72
      72 3R74 72
      5R72 END FILL

ARA=5 NUX=1 NUY=1 NUZ=2
COM='STACKING ABOVE WATER UNIT ATOP BELOW WATER UNIT'
FILL 75 76 END FILL
END ARRAY

READ MIXT EPS=1. END MIXT

```

READ BOUNDS -ZB=CONC8 END BOUNDS
 READ START NST=1 END START
 END DATA
 END

VALIDATION CASE

(CLT04)

=CSAS25

BAW-1645-4, EXP'MT-2472, CASE C-2-C, DANC OFF FACTOR FOR EACH FUEL PIN

27GROUPNDF4 LATTICECELL

AL 1 1.0 291.5 END
 AL 2 1.0 291.5 END
 H2O 3 1.0 291.5 END
 BORON 3 4.7646-5 291.5 END
 H2O 4 0.75 291.5 END
 BORON 4 3.5735-5 291.5 END
 AL 4 0.25 291.5 END
 CARBONSTEEL 5 1.0 291.5 END
 UO2 13 0.9325 291.5 92235 2.459 92238 97.541 END
 UO2 14 0.9325 291.5 92235 2.459 92238 97.541 END
 UO2 15 0.9325 291.5 92235 2.459 92238 97.541 END
 UO2 16 0.9325 291.5 92235 2.459 92238 97.541 END
 UO2 23 0.9325 291.5 92235 2.459 92238 97.541 END
 UO2 24 0.9325 291.5 92235 2.459 92238 97.541 END
 UO2 25 0.9325 291.5 92235 2.459 92238 97.541 END
 UO2 26 0.9325 291.5 92235 2.459 92238 97.541 END

END COMP

TRIANGPITCH 1.2093 1.0300 16 3 1.2060 1 1.0440 0 END

MORE DATA RES=13 CYLINDER 0.5150 DAN(13)=0.37813

RES=14 CYLINDER 0.5150 DAN(14)=0.50543

RES=15 CYLINDER 0.5150 DAN(15)=0.63273

RES=23 CYLINDER 0.5150 DAN(23)=0.46920

RES=24 CYLINDER 0.5150 DAN(24)=0.63217

RES=25 CYLINDER 0.5150 DAN(25)=0.79514

RES=26 CYLINDER 0.5150 DAN(26)=0.97782 END MORE

BAW-1645-4, EXP'MT-2472, CASE C-2-C, DANC OFF FACTOR FOR EACH FUEL PIN

READ PARAM TME=40 FDN=YES NUB=YES END PARAM

READ GEOM

UNIT 1

ZHEMICYL-Y 2 1 0.6030 145.6400 -0.3180

UNIT 2

ZHEMICYL-Y 2 1 0.6030 156.1220 145.6400

UNIT 3

ZHEMICYL+Y 2 1 0.6030 145.6400 -0.3180

UNIT 4

ZHEMICYL+Y 2 1 0.6030 156.1220 145.6400

UNIT 5

ZHEMICYL-Y 13 1 0.5150 145.6400 0.0

ZHEMICYL-Y 0 1 0.5220 145.6400 0.0

ZHEMICYL-Y 1 1 0.6030 145.6400 -0.3180

UNIT 6

ZHEMICYL-Y 23 1 0.5150 153.3400 145.6400

ZHEMICYL-Y 0 1 0.5220 155.8040 145.6400

ZHEMICYL-Y 1 1 0.6030 156.1220 145.6400

UNIT 7

ZHEMICYL-Y 14 1 0.5150 145.6400 0.0

ZHEMICYL-Y 0 1 0.5220 145.6400 0.0

ZHEMICYL-Y 1 1 0.6030 145.6400 -0.3180

UNIT 8

ZHEMICYL-Y 24 1 0.5150 153.3400 145.6400

ZHEMICYL-Y 0 1 0.5220 155.8040 145.6400

ZHEMICYL-Y 1 1 0.6030 156.1220 145.6400

UNIT 9

ZHEMICYL-Y 16 1 0.5150 145.6400 0.0

ZHEMICYL-Y 0 1 0.5220 145.6400 0.0

ZHEMICYL-Y 1 1 0.6030 145.6400 -0.3180

UNIT 10

ZHEMICYL-Y 26 1 0.5150 153.3400 145.6400

ZHEMICYL-Y 0 1 0.5220 155.8040 145.6400

ZHEMICYL-Y 1 1 0.6030 156.1220 145.6400

UNIT 11

ZHEMICYL+Y 13 1 0.5150 145.6400 0.0

ZHEMICYL+Y 0 1 0.5220 145.6400 0.0

ZHEMICYL+Y 1 1 0.6030 145.6400 -0.3180

UNIT 12

ZHEMICYL+Y 23 1 0.5150 153.3400 145.6400

ZHEMICYL+Y 0 1 0.5220 155.8040 145.6400

ZHEMICYL+Y 1 1 0.6030 156.1220 145.6400

UNIT 13

ZHEMICYL+Y 14 1 0.5150 145.6400 0.0

ZHEMICYL+Y 0 1 0.5220 145.6400 0.0

ZHEMICYL+Y 1 1 0.6030 145.6400 -0.3180

UNIT 14

ZHEMICYL+Y 24 1 0.5150 153.3400 145.6400

ZHEMICYL+Y 0 1 0.5220 155.8040 145.6400

```

ZHEMICYL+Y 1 1 0.6030 156.1220 145.6400
UNIT 15
ZHEMICYL+Y 16 1 0.5150 145.6400 0.0
ZHEMICYL+Y 0 1 0.5220 145.6400 0.0
ZHEMICYL+Y 1 1 0.6030 145.6400 -0.3180
UNIT 16
ZHEMICYL+Y 26 1 0.5150 153.3400 145.6400
ZHEMICYL+Y 0 1 0.5220 155.8040 145.6400
ZHEMICYL+Y 1 1 0.6030 156.1220 145.6400

UNIT 17
ZHEMICYL-X 14 1 0.5150 145.6400 0.0
ZHEMICYL-X 0 1 0.5220 145.6400 0.0
ZHEMICYL-X 1 1 0.6030 145.6400 -0.3180
UNIT 18
ZHEMICYL-X 24 1 0.5150 153.3400 145.6400
ZHEMICYL-X 0 1 0.5220 155.8040 145.6400
ZHEMICYL-X 1 1 0.6030 156.1220 145.6400
UNIT 19
ZHEMICYL-X 15 1 0.5150 145.6400 0.0
ZHEMICYL-X 0 1 0.5220 145.6400 0.0
ZHEMICYL-X 1 1 0.6030 145.6400 -0.3180
UNIT 20
ZHEMICYL-X 25 1 0.5150 153.3400 145.6400
ZHEMICYL-X 0 1 0.5220 155.8040 145.6400
ZHEMICYL-X 1 1 0.6030 156.1220 145.6400
UNIT 21
ZHEMICYL-X 16 1 0.5150 145.6400 0.0
ZHEMICYL-X 0 1 0.5220 145.6400 0.0
ZHEMICYL-X 1 1 0.6030 145.6400 -0.3180
UNIT 22
ZHEMICYL-X 26 1 0.5150 153.3400 145.6400
ZHEMICYL-X 0 1 0.5220 155.8040 145.6400
ZHEMICYL-X 1 1 0.6030 156.1220 145.6400

UNIT 23
ZHEMICYL+X 14 1 0.5150 145.6400 0.0
ZHEMICYL+X 0 1 0.5220 145.6400 0.0
ZHEMICYL+X 1 1 0.6030 145.6400 -0.3180
UNIT 24
ZHEMICYL+X 24 1 0.5150 153.3400 145.6400
ZHEMICYL+X 0 1 0.5220 155.8040 145.6400
ZHEMICYL+X 1 1 0.6030 156.1220 145.6400
UNIT 25
ZHEMICYL+X 15 1 0.5150 145.6400 0.0
ZHEMICYL+X 0 1 0.5220 145.6400 0.0
ZHEMICYL+X 1 1 0.6030 145.6400 -0.3180
UNIT 26
ZHEMICYL+X 25 1 0.5150 153.3400 145.6400
ZHEMICYL+X 0 1 0.5220 155.8040 145.6400
ZHEMICYL+X 1 1 0.6030 156.1220 145.6400
UNIT 27
ZHEMICYL+X 16 1 0.5150 145.6400 0.0
ZHEMICYL+X 0 1 0.5220 145.6400 0.0
ZHEMICYL+X 1 1 0.6030 145.6400 -0.3180
UNIT 28
ZHEMICYL+X 26 1 0.5150 153.3400 145.6400
ZHEMICYL+X 0 1 0.5220 155.8040 145.6400
ZHEMICYL+X 1 1 0.6030 156.1220 145.6400

UNIT 29
COM='CUBOID BUILT AROUND UNIT 1'
ZHEMICYL-Y 2 1 0.6030 145.6400 -0.3180
CUBOID 3 1 2P0.6047 0.0 -0.6047 145.6400 -0.3180
UNIT 30
COM='CUBOID BUILT AROUND UNIT 2'
ZHEMICYL-Y 2 1 0.6030 156.1220 145.6400
CUBOID 0 1 2P0.6047 0.0 -0.6047 156.1220 145.6400
UNIT 31
COM='CUBOID BUILT AROUND UNIT 3'
ZHEMICYL+Y 2 1 0.6030 145.6400 -0.3180
CUBOID 3 1 2P0.6047 0.6047 0.0 145.6400 -0.3180
UNIT 32
COM='CUBOID BUILT AROUND UNIT 4'
ZHEMICYL+Y 2 1 0.6030 156.1220 145.6400
CUBOID 0 1 2P0.6047 0.6047 0.0 156.1220 145.6400

UNIT 33
ZHEMICYL-Y 13 1 0.5150 145.6400 0.0
ZHEMICYL-Y 0 1 0.5220 145.6400 0.0
ZHEMICYL-Y 1 1 0.6030 145.6400 -0.3180
CUBOID 3 1 2P0.6047 0.0 -0.6047 145.6400 -0.3180
UNIT 34
ZHEMICYL-Y 23 1 0.5150 153.3400 145.6400
ZHEMICYL-Y 0 1 0.5220 155.8040 145.6400
ZHEMICYL-Y 1 1 0.6030 156.1220 145.6400
CUBOID 0 1 2P0.6047 0.0 -0.6047 156.1220 145.6400

```

```

UNIT 35
ZHEMICYL-Y 14 1 0.5150      145.6400  0.0
ZHEMICYL-Y 0 1 0.5220      145.6400  0.0
ZHEMICYL-Y 1 1 0.6030      145.6400 -0.3180
CUBOID      3 1 2P0.6047  0.0 -0.6047 145.6400 -0.3180
UNIT 36
ZHEMICYL-Y 24 1 0.5150      153.3400 145.6400
ZHEMICYL-Y 0 1 0.5220      155.8040 145.6400
ZHEMICYL-Y 1 1 0.6030      156.1220 145.6400
CUBOID      0 1 2P0.6047  0.0 -0.6047 156.1220 145.6400
UNIT 37
ZHEMICYL+Y 13 1 0.5150      145.6400  0.0
ZHEMICYL+Y 0 1 0.5220      145.6400  0.0
ZHEMICYL+Y 1 1 0.6030      145.6400 -0.3180
CUBOID      3 1 2P0.6047  0.6047  0.0 145.6400 -0.3180
UNIT 38
ZHEMICYL+Y 23 1 0.5150      153.3400 145.6400
ZHEMICYL+Y 0 1 0.5220      155.8040 145.6400
ZHEMICYL+Y 1 1 0.6030      156.1220 145.6400
CUBOID      0 1 2P0.6047  0.6047  0.0 156.1220 145.6400
UNIT 39
ZHEMICYL+Y 14 1 0.5150      145.6400  0.0
ZHEMICYL+Y 0 1 0.5220      145.6400  0.0
ZHEMICYL+Y 1 1 0.6030      145.6400 -0.3180
CUBOID      3 1 2P0.6047  0.6047  0.0 145.6400 -0.3180
UNIT 40
ZHEMICYL+Y 24 1 0.5150      153.3400 145.6400
ZHEMICYL+Y 0 1 0.5220      155.8040 145.6400
ZHEMICYL+Y 1 1 0.6030      156.1220 145.6400
CUBOID      0 1 2P0.6047  0.6047  0.0 156.1220 145.6400
UNIT 41
COM='CUBOID BUILT AROUND UNIT 3 WITH UNITS 5 & 17 ADDED AS HOLES'
ZHEMICYL+Y 2 1 0.6030      145.6400 -0.3180  ORIGIN 0.0 -1.0473
CUBOID      3 1 2P0.6047  2P1.0473 145.6400 -0.3180
HOLE        5      0.0 1.0473  0.0
HOLE       17      0.6047  0.0 0.0
UNIT 42
COM='CUBOID BUILT AROUND UNIT 4 WITH UNITS 6 & 18 ADDED AS HOLES'
ZHEMICYL+Y 2 1 0.6030      156.1220 145.6400  ORIGIN 0.0 -1.0473
CUBOID      0 1 2P0.6047  2P1.0473 156.1220 145.6400
HOLE        6      0.0 1.0473  0.0
HOLE       18      0.6047  0.0 0.0
UNIT 43
COM='CUBOID BUILT AROUND UNIT 11 WITH UNITS 9 21 & 23 ADDED AS HOLES'
ZHEMICYL+Y 13 1 0.5150      145.6400  0.0000  ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220      145.6400  0.0000  ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030      145.6400 -0.3180  ORIGIN 0.0 -1.0473
CUBOID      3 1 2P0.6047  2P1.0473 145.6400 -0.3180
HOLE        9      0.0 1.0473  0.0
HOLE       21      0.6047  0.0 0.0
HOLE       23     -0.3047  0.0 0.0
UNIT 44
COM='CUBOID BUILT AROUND UNIT 12 WITH UNITS 10 22 & 24 ADDED AS HOLES'
ZHEMICYL+Y 23 1 0.5150      153.3400 145.6400  ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220      155.8040 145.6400  ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030      156.1220 145.6400  ORIGIN 0.0 -1.0473
CUBOID      0 1 2P0.6047  2P1.0473 156.1220 145.6400
HOLE       10      0.0 1.0473  0.0
HOLE       22      0.6047  0.0 0.0
HOLE       24     -0.6047  0.0 0.0
UNIT 45
COM='CUBOID BUILT AROUND UNIT 13 WITH UNITS 9 21 & 27 ADDED AS HOLES'
ZHEMICYL+Y 14 1 0.5150      145.6400  0.0000  ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220      145.6400  0.0000  ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030      145.6400 -0.3180  ORIGIN 0.0 -1.0473
CUBOID      3 1 2P0.6047  2P1.0473 145.6400 -0.3180
HOLE        9      0.0 1.0473  0.0
HOLE       21      0.6047  0.0 0.0
HOLE       27     -0.6047  0.0 0.0
UNIT 46
COM='CUBOID BUILT AROUND UNIT 14 WITH UNITS 10 22 & 28 ADDED AS HOLES'
ZHEMICYL+Y 24 1 0.5150      153.3400 145.6400  ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220      155.8040 145.6400  ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030      156.1220 145.6400  ORIGIN 0.0 -1.0473
CUBOID      0 1 2P0.6047  2P1.0473 156.1220 145.6400
HOLE       10      0.0 1.0473  0.0
HOLE       22      0.6047  0.0 0.0
HOLE       28     -0.6047  0.0 0.0
UNIT 47
COM='CUBOID BUILT AROUND UNIT 11 WITH UNITS 9 17 & 27 ADDED AS HOLES'
ZHEMICYL+Y 13 1 0.5150      145.6400  0.0000  ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220      145.6400  0.0000  ORIGIN 0.0 -1.0473

```

```

ZHEMICYL+Y 1 1 0.6030 145.6400 -0.3180 ORIGIN 0.0 -1.0473
CUBOID 3 1 2P0.6047 2P1.0473 145.6400 -0.3180
HOLE 9 0.0 1.0473 0.0
HOLE 17 0.6047 0.0 0.0
HOLE 27 -0.6047 0.0 0.0
UNIT 48
COM='CUBOID BUILT AROUND UNIT 12 WITH UNITS 10 18 & 28 ADDED AS HOLES'
ZHEMICYL+Y 23 1 0.5150 153.3400 145.6400 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 155.8040 145.6400 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 156.1220 145.6400 ORIGIN 0.0 -1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 145.6400
HOLE 10 0.0 1.0473 0.0
HOLE 18 0.6047 0.0 0.0
HOLE 28 -0.6047 0.0 0.0
UNIT 49
COM='CUBOID BUILT AROUND UNIT 3 WITH UNITS 5 & 23 ADDED AS HOLES'
ZHEMICYL+Y 2 1 0.6030 145.6400 -0.3180 ORIGIN 0.0 -1.0473
CUBOID 3 1 2P0.6047 2P1.0473 145.6400 -0.3180
HOLE 5 0.0 1.0473 0.0
HOLE 23 -0.6047 0.0 0.0
UNIT 50
COM='CUBOID BUILT AROUND UNIT 4 WITH UNITS 6 & 24 ADDED AS HOLES'
ZHEMICYL+Y 2 1 0.6030 156.1220 145.6400 ORIGIN 0.0 -1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 145.6400
HOLE 6 0.0 1.0473 0.0
HOLE 24 -0.6047 0.0 0.0
UNIT 51
COM='CUBOID BUILT AROUND UNIT 11 WITH UNITS 5 & 19 ADDED AS HOLES'
ZHEMICYL+Y 13 1 0.5150 145.6400 0.0 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 145.6400 0.0 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 145.6400 -0.3180 ORIGIN 0.0 -1.0473
CUBOID 3 1 2P0.6047 2P1.0473 145.6400 -0.3180
HOLE 5 0.0 1.0473 0.0
HOLE 19 0.6047 0.0 0.0
UNIT 52
COM='CUBOID BUILT AROUND UNIT 12 WITH UNITS 6 & 20 ADDED AS HOLES'
ZHEMICYL+Y 23 1 0.5150 153.3400 145.6400 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 155.8040 145.6400 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 156.1220 145.6400 ORIGIN 0.0 -1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 145.6400
HOLE 6 0.0 1.0473 0.0
HOLE 20 0.6047 0.0 0.0
UNIT 53
COM='CUBOID BUILT AROUND UNIT 15 WITH UNITS 9 21 & 25 ADDED AS HOLES'
ZHEMICYL+Y 16 1 0.5150 145.6400 0.0000 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 145.6400 0.0000 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 145.6400 -0.3180 ORIGIN 0.0 -1.0473
CUBOID 3 1 2P0.6047 2P1.0473 145.6400 -0.3180
HOLE 9 0.0 1.0473 0.0
HOLE 21 0.6047 0.0 0.0
HOLE 25 -0.6047 0.0 0.0
UNIT 54
COM='CUBOID BUILT AROUND UNIT 16 WITH UNITS 10 22 & 26 ADDED AS HOLES'
ZHEMICYL+Y 26 1 0.5150 153.3400 145.6400 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 155.8040 145.6400 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 156.1220 145.6400 ORIGIN 0.0 -1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 145.6400
HOLE 10 0.0 1.0473 0.0
HOLE 22 0.6047 0.0 0.0
HOLE 26 -0.6047 0.0 0.0
UNIT 55
COM='CUBOID BUILT AROUND UNIT 15 WITH UNITS 9 21 & 27 ADDED AS HOLES'
ZHEMICYL+Y 16 1 0.5150 145.6400 0.0000 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 145.6400 0.0000 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 145.6400 -0.3180 ORIGIN 0.0 -1.0473
CUBOID 3 1 2P0.6047 2P1.0473 145.6400 -0.3180
HOLE 9 0.0 1.0473 0.0
HOLE 21 0.6047 0.0 0.0
HOLE 27 -0.6047 0.0 0.0
UNIT 56
COM='CUBOID BUILT AROUND UNIT 16 WITH UNITS 10 22 & 28 ADDED AS HOLES'
ZHEMICYL+Y 26 1 0.5150 153.3400 145.6400 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 155.8040 145.6400 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 1 1 0.6030 156.1220 145.6400 ORIGIN 0.0 -1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 145.6400
HOLE 10 0.0 1.0473 0.0
HOLE 22 0.6047 0.0 0.0
HOLE 28 -0.6047 0.0 0.0
UNIT 57
COM='CUBOID BUILT AROUND UNIT 15 WITH UNITS 9 19 & 27 ADDED AS HOLES'
ZHEMICYL+Y 16 1 0.5150 145.6400 0.0000 ORIGIN 0.0 -1.0473
ZHEMICYL+Y 0 1 0.5220 145.6400 0.0000 ORIGIN 0.0 -1.0473

```

ZHEMICYL+Y 1 1 0.6030 145.6400 -0.3180 ORIGIN 0.0 -1.0473
 CUBOID 3 1 2P0.6047 2P1.0473 145.6400 -0.3180
 HOLE 9 0.0 1.0473 0.0
 HOLE 19 0.6047 0.0 0.0
 HOLE 27 -0.6047 0.0 0.0
 UNIT 58
 COM='CUBOID BUILT AROUND UNIT 16 WITH UNITS 10 20 & 28 ADDED AS HOLES'
 ZHEMICYL+Y 26 1 0.5150 153.3400 145.6400 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 0 1 0.5220 155.8040 145.6400 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 1 1 0.6030 156.1220 145.6400 ORIGIN 0.0 -1.0473
 CUBOID 0 1 2P0.6047 2P1.0473 156.1220 145.6400
 HOLE 10 0.0 1.0473 0.0
 HOLE 20 0.6047 0.0 0.0
 HOLE 28 -0.6047 0.0 0.0
 UNIT 59
 COM='CUBOID BUILT AROUND UNIT 11 WITH UNITS 5 & 25 ADDED AS HOLES'
 ZHEMICYL+Y 13 1 0.5150 145.6400 0.0 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 0 1 0.5220 145.6400 0.0 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 1 1 0.6030 145.6400 -0.3180 ORIGIN 0.0 -1.0473
 CUBOID 3 1 2P0.6047 2P1.0473 145.6400 -0.3180
 HOLE 5 0.0 1.0473 0.0
 HOLE 25 -0.6047 0.0 0.0
 UNIT 60
 COM='CUBOID BUILT AROUND UNIT 12 WITH UNITS 6 & 26 ADDED AS HOLES'
 ZHEMICYL+Y 23 1 0.5150 153.3400 145.6400 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 0 1 0.5220 155.8040 145.6400 ORIGIN 0.0 -1.0473
 ZHEMICYL+Y 1 1 0.6030 156.1220 145.6400 ORIGIN 0.0 -1.0473
 CUBOID 0 1 2P0.6047 2P1.0473 156.1220 145.6400
 HOLE 6 0.0 1.0473 0.0
 HOLE 26 -0.6047 0.0 0.0
 UNIT 61
 COM='CUBOID BUILT AROUND UNIT 1 WITH UNITS 11 & 17 ADDED AS HOLES'
 ZHEMICYL-Y 2 1 0.6030 145.6400 -0.3180 ORIGIN 0.0 1.0473
 CUBOID 3 1 2P0.6047 2P1.0473 145.6400 -0.3180
 HOLE 11 0.0 -1.0473 0.0
 HOLE 17 0.6047 0.0 0.0
 UNIT 62
 COM='CUBOID BUILT AROUND UNIT 2 WITH UNITS 12 & 18 ADDED AS HOLES'
 ZHEMICYL-Y 2 1 0.6030 156.1220 145.6400 ORIGIN 0.0 1.0473
 CUBOID 0 1 2P0.6047 2P1.0473 156.1220 145.6400
 HOLE 12 0.0 -1.0473 0.0
 HOLE 18 0.6047 0.0 0.0
 UNIT 63
 COM='CUBOID BUILT AROUND UNIT 5 WITH UNITS 15 21 & 23 ADDED AS HOLES'
 ZHEMICYL-Y 13 1 0.5150 145.6400 0.0000 ORIGIN 0.0 1.0473
 ZHEMICYL-Y 0 1 0.5220 145.6400 0.0000 ORIGIN 0.0 1.0473
 ZHEMICYL-Y 1 1 0.6030 145.6400 -0.3180 ORIGIN 0.0 1.0473
 CUBOID 3 1 2P0.6047 2P1.0473 145.6400 -0.3180
 HOLE 15 0.0 -1.0473 0.0
 HOLE 21 0.6047 0.0 0.0
 HOLE 23 -0.6047 0.0 0.0
 UNIT 64
 COM='CUBOID BUILT AROUND UNIT 6 WITH UNITS 16 22 & 24 ADDED AS HOLES'
 ZHEMICYL-Y 23 1 0.5150 153.3400 145.6400 ORIGIN 0.0 1.0473
 ZHEMICYL-Y 0 1 0.5220 155.8040 145.6400 ORIGIN 0.0 1.0473
 ZHEMICYL-Y 1 1 0.6030 156.1220 145.6400 ORIGIN 0.0 1.0473
 CUBOID 0 1 2P0.6047 2P1.0473 156.1220 145.6400
 HOLE 16 0.0 -1.0473 0.0
 HOLE 22 0.6047 0.0 0.0
 HOLE 24 -0.6047 0.0 0.0
 UNIT 65
 COM='CUBOID BUILT AROUND UNIT 7 WITH UNITS 15 21 & 27 ADDED AS HOLES'
 ZHEMICYL-Y 14 1 0.5150 145.6400 0.0000 ORIGIN 0.0 1.0473
 ZHEMICYL-Y 0 1 0.5220 145.6400 0.0000 ORIGIN 0.0 1.0473
 ZHEMICYL-Y 1 1 0.6030 145.6400 -0.3180 ORIGIN 0.0 1.0473
 CUBOID 3 1 2P0.6047 2P1.0473 145.6400 -0.3180
 HOLE 15 0.0 -1.0473 0.0
 HOLE 21 0.6047 0.0 0.0
 HOLE 27 -0.6047 0.0 0.0
 UNIT 66
 COM='CUBOID BUILT AROUND UNIT 8 WITH UNITS 16 22 & 28 ADDED AS HOLES'
 ZHEMICYL-Y 24 1 0.5150 153.3400 145.6400 ORIGIN 0.0 1.0473
 ZHEMICYL-Y 0 1 0.5220 155.8040 145.6400 ORIGIN 0.0 1.0473
 ZHEMICYL-Y 1 1 0.6030 156.1220 145.6400 ORIGIN 0.0 1.0473
 CUBOID 0 1 2P0.6047 2P1.0473 156.1220 145.6400
 HOLE 16 0.0 -1.0473 0.0
 HOLE 22 0.6047 0.0 0.0
 HOLE 28 -0.6047 0.0 0.0
 UNIT 67
 COM='CUBOID BUILT AROUND UNIT 5 WITH UNITS 15 17 & 27 ADDED AS HOLES'
 ZHEMICYL-Y 13 1 0.5150 145.6400 0.0000 ORIGIN 0.0 1.0473
 ZHEMICYL-Y 0 1 0.5220 145.6400 0.0000 ORIGIN 0.0 1.0473


```

ZHEMICYL-Y 1 1 0.6030 145.6400 -0.3180 ORIGIN 0.0 1.0473
CUBOID 3 1 2P0.6047 2P1.0473 145.6400 -0.3180
HOLE 15 0.0 -1.0473 0.0
HOLE 17 0.6047 0.0 0.0
HOLE 27 -0.6047 0.0 0.0
UNIT 68
COM='CUBOID BUILT AROUND UNIT 6 WITH UNITS 16 18 & 28 ADDED AS HOLES'
ZHEMICYL-Y 23 1 0.5150 153.3400 145.6400 ORIGIN 0.0 1.0473
ZHEMICYL-Y 0 1 0.5220 155.8040 145.6400 ORIGIN 0.0 1.0473
ZHEMICYL-Y 1 1 0.6030 156.1220 145.6400 ORIGIN 0.0 1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 145.6400
HOLE 16 0.0 -1.0473 0.0
HOLE 18 0.6047 0.0 0.0
HOLE 28 -0.6047 0.0 0.0

UNIT 69
COM='CUBOID BUILT AROUND UNIT 1 WITH UNITS 11 & 23 ADDED AS HOLES'
ZHEMICYL-Y 2 1 0.6030 145.6400 -0.3180 ORIGIN 0.0 1.0473
CUBOID 3 1 2P0.6047 2P1.0473 145.6400 -0.3180
HOLE 11 0.0 -1.0473 0.0
HOLE 23 -0.6047 0.0 0.0
UNIT 70
COM='CUBOID BUILT AROUND UNIT 2 WITH UNITS 12 & 24 ADDED AS HOLES'
ZHEMICYL-Y 2 1 0.6030 156.1220 145.6400 ORIGIN 0.0 1.0473
CUBOID 0 1 2P0.6047 2P1.0473 156.1220 145.6400
HOLE 12 0.0 -1.0473 0.0
HOLE 24 -0.6047 0.0 0.0

UNIT 71
COM='FUEL MODULE W/O AL SIDE PLATES, BELOW WATER'
ARRAY 1 -9.0705 -8.9832 -0.3180
CUBOID 3 1 2P9.5250 2P9.5250 145.6400 -0.3180
CUBOID 4 1 2P9.5250 2P9.5250 145.6400 -1.3848
CUBOID 2 1 2P9.5250 2P9.5250 145.6400 -3.1755
CUBOID 3 1 2P10.9740 2P10.4711 145.6400 -3.1755
UNIT 72
COM='FUEL MODULE W/O AL SIDE PLATES, ABOVE WATER'
ARRAY 2 -9.0705 -8.9832 145.6400
CUBOID 0 1 2P9.5250 2P9.5250 156.1220 145.6400
CUBOID 2 1 2P9.5250 2P9.5250 157.7095 145.6400
CUBOID 0 1 2P10.9740 2P10.4711 157.7095 145.6400

UNIT 73
COM='FUEL MODULE WITH AL SIDE PLATES, BELOW WATER'
ARRAY 1 -9.0705 -8.9832 -0.3180
CUBOID 3 1 2P9.0705 2P9.3957 145.6400 -0.3180
CUBOID 2 1 2P9.0705 2P9.5250 145.6400 -0.3180
CUBOID 3 1 2P9.5250 2P9.5250 145.6400 -0.3180
CUBOID 4 1 2P9.5250 2P9.5250 145.6400 -1.3848
CUBOID 2 1 2P9.5250 2P9.5250 145.6400 -3.1755
CUBOID 3 1 2P10.9740 2P10.4711 145.6400 -3.1755
UNIT 74
COM='FUEL MODULE WITH AL SIDE PLATES, ABOVE WATER'
ARRAY 2 -9.0705 -8.9832 145.6400
CUBOID 0 1 2P9.0705 2P9.3957 156.1220 145.6400
CUBOID 2 1 2P9.0705 2P9.5250 156.1220 145.6400
CUBOID 0 1 2P9.5250 2P9.5250 156.1220 145.6400
CUBOID 2 1 2P9.5250 2P9.5250 157.7095 145.6400
CUBOID 0 1 2P10.9740 2P10.4711 157.7095 145.6400

UNIT 75
COM='5X5X1 ARRAY OF FUEL MODULES, BELOW WATER'
ARRAY 3 -54.8700 -52.3555 -3.1755
CUBOID 3 1 2P60.9600 2P60.9600 145.6400 -3.1755
CUBOID 2 1 2P60.9600 2P60.9600 145.6400 -11.8115
CYLINDER 3 1 137.1600 145.6400 -14.6815
CYLINDER 5 1 138.1600 145.6400 -15.6815
CUBOID 0 1 4P138.1600 145.6400 -30.9215
UNIT 76
COM='5X5X1 ARRAY OF FUEL MODULES, ABOVE WATER'
ARRAY 4 -54.8700 -52.3555 145.6400
CUBOID 0 1 2P60.9600 2P60.9600 157.7095 145.6400
CYLINDER 0 1 137.1600 157.7095 145.6400
CYLINDER 5 1 138.1600 157.7095 145.6400
CUBOID 0 1 4P138.1600 157.7095 145.6400

GLOBAL
UNIT 77
COM='STACK UNIT 76 ATOP UNIT 75'
ARRAY 5 -138.1600 -138.1600 -30.9215
END GEOM

READ ARRAY
ARA=1 NUX=15 NUY=10 NUZ=1
COM='FUEL MODULE ARRAY, BELOW WATER'
FILL 29 33 11R35 33 29
41 43 11R45 47 49

```

```

51 53 11R55 57 59 5Q15
61 63 11R65 67 69
31 37 11R39 37 31 END FILL
ARA=2 NUX=15 NUY=10 NUZ=1
COM='FUEL MODULE ARRAY, ABOVE WATER'
FILL 30 34 11R36 34 30
42 44 11R46 48 50
52 54 11R56 58 60 5Q15
62 64 11R66 68 70
32 38 11R40 38 32 END FILL

```

```

ARA=3 NUX=5 NUY=5 NUZ=1
COM='ARRAY OF FUEL MODULES BELOW WATER'
FILL 5R71
71 3R73 71
5R71
71 3R73 71
5R71 END FILL

```

```

ARA=4 NUX=5 NUY=5 NUZ=1
COM='ARRAY OF FUEL MODULES ABOVE WATER'
FILL 5R72
72 3R74 72
5R72
72 3R74 72
5R72 END FILL

```

```

ARA=5 NUX=1 NUY=1 NUZ=2
COM='STACKING ABOVE WATER UNIT ATOP BELOW WATER UNIT'
FILL 75 76 END FILL
END ARRAY

```

```

READ MIXT EPS=1. END MIXT
READ BOUNDS -ZB=CONC8 END BOUNDS
READ START NST=1 END START
END DATA
END

```

```

VALIDATION CASE (CLT05 )
=CSAS25
BAW-1645-4, EXP/MT-2485, CASE C-2-C, DANC OFF FACTOR FOR EACH FUEL PIN
27GROUPNDF4 LATTICECELL
AL 1 1.0 294.0 END
AL 2 1.0 294.0 END
H2O 3 1.0 294.0 END
BORON 3 3.4888-4 294.0 END
H2O 4 0.75 294.0 END
BORON 4 2.6166-4 294.0 END
AL 4 0.25 294.0 END
CARBONSTEEL 5 1.0 294.0 END
UO2 14 0.9325 294.0 92235 2.459 92238 97.541 END
UO2 15 0.9325 294.0 92235 2.459 92238 97.541 END
UO2 17 0.9325 294.0 92235 2.459 92238 97.541 END
UO2 18 0.9325 294.0 92235 2.459 92238 97.541 END
UO2 24 0.9325 294.0 92235 2.459 92238 97.541 END
UO2 25 0.9325 294.0 92235 2.459 92238 97.541 END
UO2 27 0.9325 294.0 92235 2.459 92238 97.541 END
UO2 28 0.9325 294.0 92235 2.459 92238 97.541 END
END COMP
SQUAREPITCH 1.2093 1.0300 18 3 1.2060 1 1.0440 0 END
MORE DATA RES=14 CYLINDER 0.5150 DAN(14)=0.30655
RES=15 CYLINDER 0.5150 DAN(15)=0.43008
RES=17 CYLINDER 0.5150 DAN(17)=0.58330
RES=24 CYLINDER 0.5150 DAN(24)=0.47740
RES=25 CYLINDER 0.5150 DAN(25)=0.63128
RES=27 CYLINDER 0.5150 DAN(27)=0.85323
RES=28 CYLINDER 0.5150 DAN(28)=0.97931 END MORE
BAW-1645-4, EXP/MT-2485, CASE C-2-C, DANC OFF FACTOR FOR EACH FUEL PIN
READ PARAM FDN=YES NUB=YES END PARAM
READ GEOM

```

```

UNIT 1
COM='AL PIN BELOW WATER'
CYLINDER 2 1 0.6030 145.0000 -0.3180
CUBOID 3 1 4P0.6047 145.0000 -0.3180
UNIT 2
COM='AL PIN ABOVE WATER'
CYLINDER 2 1 0.6030 156.1220 145.0000
CUBOID 0 1 4P0.6047 156.1220 145.0000

```

```

UNIT 3
COM='FUEL PIN BELOW WATER SURROUNDED BY 4 PINS'
CYLINDER 14 1 0.5150 145.0000 0.0
CYLINDER 0 1 0.5220 145.0000 0.0
CYLINDER 1 1 0.6030 145.0000 -0.3180
CUBOID 3 1 4P0.6047 145.0000 -0.3180

```

```

UNIT 4
COM='FUEL PIN ABOVE WATER,SURROUNDED BY 4 PINS'
CYLINDER 24 1 0.5150 153.3400 145.0000
CYLINDER 0 1 0.5220 155.8040 145.0000
CYLINDER 1 1 0.6030 156.1220 145.0000
CUBOID 0 1 4P0.6047 156.1220 145.0000
UNIT 5
COM='FUEL PIN BELOW WATER,SURROUNDED BY 5 PINS'
CYLINDER 15 1 0.5150 145.0000 0.0
CYLINDER 0 1 0.5220 145.0000 0.0
CYLINDER 1 1 0.6030 145.0000 -0.3180
CUBOID 3 1 4P0.6047 145.0000 -0.3180
UNIT 6
COM='FUEL PIN ABOVE WATER,SURROUNDED BY 5 PINS'
CYLINDER 25 1 0.5150 153.3400 145.0000
CYLINDER 0 1 0.5220 155.8040 145.0000
CYLINDER 1 1 0.6030 156.1220 145.0000
CUBOID 0 1 4P0.6047 156.1220 145.0000
UNIT 7
COM='FUEL PIN BELOW WATER,SURROUNDED BY 7 PINS'
CYLINDER 17 1 0.5150 145.0000 0.0
CYLINDER 0 1 0.5220 145.0000 0.0
CYLINDER 1 1 0.6030 145.0000 -0.3180
CUBOID 3 1 4P0.6047 145.0000 -0.3180
UNIT 8
COM='FUEL PIN ABOVE WATER,SURROUNDED BY 7 PINS'
CYLINDER 27 1 0.5150 153.3400 145.0000
CYLINDER 0 1 0.5220 155.8040 145.0000
CYLINDER 1 1 0.6030 156.1220 145.0000
CUBOID 0 1 4P0.6047 156.1220 145.0000
UNIT 9
COM='FUEL PIN BELOW WATER,SURROUNDED BY 8 PINS'
CYLINDER 18 1 0.5150 145.0000 0.0
CYLINDER 0 1 0.5220 145.0000 0.0
CYLINDER 1 1 0.6030 145.0000 -0.3180
CUBOID 3 1 4P0.6047 145.0000 -0.3180
UNIT 10
COM='FUEL PIN ABOVE WATER,SURROUNDED BY 8 PINS'
CYLINDER 28 1 0.5150 153.3400 145.0000
CYLINDER 0 1 0.5220 155.8040 145.0000
CYLINDER 1 1 0.6030 156.1220 145.0000
CUBOID 0 1 4P0.6047 156.1220 145.0000
UNIT 11
COM='FUEL MODULE W/O AL SIDE PLATE, BELOW WATER'
ARRAY 1 -9.0705 -9.0705 -0.3180
CUBOID 3 1 4P9.5250 145.0000 -0.3180
CUBOID 4 1 4P9.5250 145.0000 -1.3848
CUBOID 2 1 4P9.5250 145.0000 -3.1755
CUBOID 3 1 4P9.9595 145.0000 -3.1755
UNIT 12
COM='FUEL MODULE W/O AL SIDE PLATE, ABOVE WATER'
ARRAY 2 -9.0705 -9.0705 145.0000
CUBOID 0 1 4P9.5250 156.1220 145.0000
CUBOID 2 1 4P9.5250 157.7095 145.0000
CUBOID 0 1 4P9.9595 157.7095 145.0000
UNIT 13
COM='FUEL MODULE W AL SIDE PLATE, BELOW WATER'
ARRAY 1 -9.0705 -9.0705 -0.3180
CUBOID 3 1 2P9.0705 2P9.3957 145.0000 -0.3180
CUBOID 2 1 2P9.0705 2P9.5250 145.0000 -0.3180
CUBOID 3 1 4P9.5250 145.0000 -0.3180
CUBOID 4 1 4P9.5250 145.0000 -1.3848
CUBOID 2 1 4P9.5250 145.0000 -3.1755
CUBOID 3 1 4P9.9595 145.0000 -3.1755
UNIT 14
COM='FUEL MODULE W AL SIDE PLATE, ABOVE WATER'
ARRAY 2 -9.0705 -9.0705 145.0000
CUBOID 0 1 2P9.0705 2P9.3957 156.1220 145.0000
CUBOID 2 1 2P9.0705 2P9.5250 156.1220 145.0000
CUBOID 0 1 4P9.5250 156.1220 145.0000
CUBOID 2 1 4P9.5250 157.7095 145.0000
CUBOID 0 1 4P9.9595 157.7095 145.0000
UNIT 15
COM='5X5 ARRAY OF FUEL MODULES,BELOW WATER'
ARRAY 3 -49.7975 -49.7975 -3.1755
CUBOID 3 1 4P60.9600 145.0000 -3.1755
CUBOID 2 1 4P60.9600 145.0000 -11.8115
CYLINDER 3 1 137.1600 145.0000 -14.6815
CYLINDER 5 1 138.1600 145.0000 -15.6815
CUBOID 0 1 4P138.1600 145.0000 -30.9215
UNIT 16
COM='5X5 ARRAY OF FUEL MODULES,ABOVE WATER'
ARRAY 4 -49.7975 -49.7975 145.0000
CUBOID 0 1 4P60.9600 157.7095 145.0000

```

CYLINDER 0 1 137.1600 157.7095 145.0000
 CYLINDER 5 1 138.1600 157.7095 145.0000
 CUBOID 0 1 4P138.1600 157.7095 145.0000

GLOBAL
 UNIT 17
 COM='STACK UNIT 16 ATOP UNIT 15'
 ARRAY 5 -138.1600 -138.1600 -30.9215
 END GEOM

READ ARRAY
 ARA=1 NUX=15 NUY=15 NUZ=1
 COM='FUEL MODULE PIN ARRAY, BELOW WATER'
 FILL 1 3 11R5 3 1
 3 7 11R9 7 3
 5 13R9 5 10Q15
 3 7 11R9 7 3
 1 3 11R5 3 1 END FILL
 ARA=2 NUX=15 NUY=15 NUZ=1
 COM='FUEL MODULE PIN ARRAY, ABOVE WATER'
 FILL 2 4 11R6 4 2
 4 8 11R10 8 4
 6 13R10 6 10Q15
 4 8 11R10 8 4
 2 4 11R6 4 2 END FILL
 ARA=3 NUX=5 NUY=5 NUZ=1
 COM='5X5 ARRAY OF FUEL MODULES, BELOW WATER'
 FILL 5R11
 11 3R13 11
 5R11
 11 3R13 11
 5R11 END FILL
 ARA=4 NUX=5 NUY=5 NUZ=1
 COM='5X5 ARRAY OF FUEL MODULES, BELOW WATER'
 FILL 5R12
 12 3R14 12
 5R12
 12 3R14 12
 5R12 END FILL
 ARA=5 NUX=1 NUY=1 NUZ=2
 FILL 15 16 END FILL
 END ARRAY
 READ BOUNDS -ZB=CONC8 END BOUNDS
 READ START NST=1 END START
 END DATA
 END

VALIDATION CASE

(CLT06)

=CSAS25
 BAW-1645-4, EXP'MT-2491, CASE C-2-C, DANCOFF FACTOR FOR EACH FUEL PIN
 27GROUPNDF4 LATTICECELL
 AL 1 1.0 295.0 END
 AL 2 1.0 295.0 END
 H2O 3 1.0 295.0 END
 BORON 3 2.9375-4 295.0 END
 H2O 4 0.75 295.0 END
 BORON 4 2.2031-4 295.0 END
 AL 4 0.25 295.0 END
 CARBONSTEEL 5 1.0 295.0 END
 UO2 14 0.9325 295.0 92235 2.459 92238 97.541 END
 UO2 15 0.9325 295.0 92235 2.459 92238 97.541 END
 UO2 17 0.9325 295.0 92235 2.459 92238 97.541 END
 UO2 18 0.9325 295.0 92235 2.459 92238 97.541 END
 UO2 24 0.9325 295.0 92235 2.459 92238 97.541 END
 UO2 25 0.9325 295.0 92235 2.459 92238 97.541 END
 UO2 27 0.9325 295.0 92235 2.459 92238 97.541 END
 UO2 28 0.9325 295.0 92235 2.459 92238 97.541 END
 END COMP
 SQUAREPITCH 1.2093 1.0300 18 3 1.2060 1 1.0440 0 END
 MORE DATA RES=14 CYLINDER 0.5150 DAN(14)=0.30659
 RES=15 CYLINDER 0.5150 DAN(15)=0.43013
 RES=17 CYLINDER 0.5150 DAN(17)=0.58337
 RES=24 CYLINDER 0.5150 DAN(24)=0.47740
 RES=25 CYLINDER 0.5150 DAN(25)=0.63128
 RES=27 CYLINDER 0.5150 DAN(27)=0.85323
 RES=28 CYLINDER 0.5150 DAN(28)=0.97931 END MORE
 BAW-1645-4, EXP'MT-2491, CASE C-2-C, DANCOFF FACTOR FOR EACH FUEL PIN
 READ PARAM FDN=YES NUB=YES END PARAM
 READ GEOM
 UNIT 1
 COM='AL PIN BELOW WATER'
 CYLINDER 2 1 0.6030 100.2400 -0.3180
 CUBOID 3 1 4P0.6047 100.2400 -0.3180
 UNIT 2
 COM='AL PIN ABOVE WATER'
 CYLINDER 2 1 0.6030 156.1220 100.2400
 CUBOID 0 1 4P0.6047 156.1220 100.2400

```

UNIT 3
COM='FUEL PIN BELOW WATER, SURROUNDED BY 4 PINS'
CYLINDER 14 1 0.5150 100.2400 0.0
CYLINDER 0 1 0.5220 100.2400 0.0
CYLINDER 1 1 0.6030 100.2400 -0.3180
CUBOID 3 1 4P0.6047 100.2400 -0.3180
UNIT 4
COM='FUEL PIN ABOVE WATER, SURROUNDED BY 4 PINS'
CYLINDER 24 1 0.5150 153.3400 100.2400
CYLINDER 0 1 0.5220 155.8040 100.2400
CYLINDER 1 1 0.6030 156.1220 100.2400
CUBOID 0 1 4P0.6047 156.1220 100.2400
UNIT 5
COM='FUEL PIN BELOW WATER, SURROUNDED BY 5 PINS'
CYLINDER 15 1 0.5150 100.2400 0.0
CYLINDER 0 1 0.5220 100.2400 0.0
CYLINDER 1 1 0.6030 100.2400 -0.3180
CUBOID 3 1 4P0.6047 100.2400 -0.3180
UNIT 6
COM='FUEL PIN ABOVE WATER, SURROUNDED BY 5 PINS'
CYLINDER 25 1 0.5150 153.3400 100.2400
CYLINDER 0 1 0.5220 155.8040 100.2400
CYLINDER 1 1 0.6030 156.1220 100.2400
CUBOID 0 1 4P0.6047 156.1220 100.2400
UNIT 7
COM='FUEL PIN BELOW WATER, SURROUNDED BY 7 PINS'
CYLINDER 17 1 0.5150 100.2400 0.0
CYLINDER 0 1 0.5220 100.2400 0.0
CYLINDER 1 1 0.6030 100.2400 -0.3180
CUBOID 3 1 4P0.6047 100.2400 -0.3180
UNIT 8
COM='FUEL PIN ABOVE WATER, SURROUNDED BY 7 PINS'
CYLINDER 27 1 0.5150 153.3400 100.2400
CYLINDER 0 1 0.5220 155.8040 100.2400
CYLINDER 1 1 0.6030 156.1220 100.2400
CUBOID 0 1 4P0.6047 156.1220 100.2400
UNIT 9
COM='FUEL PIN BELOW WATER, SURROUNDED BY 8 PINS'
CYLINDER 18 1 0.5150 100.2400 0.0
CYLINDER 0 1 0.5220 100.2400 0.0
CYLINDER 1 1 0.6030 100.2400 -0.3180
CUBOID 3 1 4P0.6047 100.2400 -0.3180
UNIT 10
COM='FUEL PIN ABOVE WATER, SURROUNDED BY 8 PINS'
CYLINDER 28 1 0.5150 153.3400 100.2400
CYLINDER 0 1 0.5220 155.8040 100.2400
CYLINDER 1 1 0.6030 156.1220 100.2400
CUBOID 0 1 4P0.6047 156.1220 100.2400
UNIT 11
COM='FUEL MODULE W/O AL SIDE PLATE, BELOW WATER'
ARRAY 1 -9.0705 -9.0705 -0.3180
CUBOID 3 1 4P9.5250 100.2400 -0.3180
CUBOID 4 1 4P9.5250 100.2400 -1.3848
CUBOID 2 1 4P9.5250 100.2400 -3.1755
CUBOID 3 1 4P9.9595 100.2400 -3.1755
UNIT 12
COM='FUEL MODULE W/O AL SIDE PLATE, ABOVE WATER'
ARRAY 2 -9.0705 -9.0705 100.2400
CUBOID 0 1 4P9.5250 156.1220 100.2400
CUBOID 2 1 4P9.5250 157.7095 100.2400
CUBOID 0 1 4P9.9595 157.7095 100.2400
UNIT 13
COM='FUEL MODULE W AL SIDE PLATE, BELOW WATER'
ARRAY 1 -9.0705 -9.0705 -0.3180
CUBOID 3 1 2P9.0705 2P9.3957 100.2400 -0.3180
CUBOID 2 1 2P9.0705 2P9.5250 100.2400 -0.3180
CUBOID 3 1 4P9.5250 100.2400 -0.3180
CUBOID 4 1 4P9.5250 100.2400 -1.3848
CUBOID 2 1 4P9.5250 100.2400 -3.1755
CUBOID 3 1 4P9.9595 100.2400 -3.1755
UNIT 14
COM='FUEL MODULE W AL SIDE PLATE, ABOVE WATER'
ARRAY 2 -9.0705 -9.0705 100.2400
CUBOID 0 1 2P9.0705 2P9.3957 156.1220 100.2400
CUBOID 2 1 2P9.0705 2P9.5250 156.1220 100.2400
CUBOID 0 1 4P9.5250 156.1220 100.2400
CUBOID 2 1 4P9.5250 157.7095 100.2400
CUBOID 0 1 4P9.9595 157.7095 100.2400
UNIT 15
COM='5X5 ARRAY OF FUEL MODULES, BELOW WATER'
ARRAY 3 -49.7975 -49.7975 -3.1755
CUBOID 3 1 4P60.9600 100.2400 -3.1755
CUBOID 2 1 4P60.9600 100.2400 -11.8115
CYLINDER 3 1 137.1600 100.2400 -14.6815

```

```

CYLINDER 5 1 138.1600 100.2400 -15.6815
CUBOID 0 1 4P138.1600 100.2400 -30.9215
UNIT 16
COM='5X5 ARRAY OF FUEL MODULES, ABOVE WATER'
ARRAY 4 -49.7975 -49.7975 100.2400
CUBOID 0 1 4P60.9600 157.7095 100.2400
CYLINDER 0 1 137.1600 157.7095 100.2400
CYLINDER 5 1 138.1600 157.7095 100.2400
CUBOID 0 1 4P138.1600 157.7095 100.2400

```

```

GLOBAL
UNIT 17
COM='STACK UNIT 16 ATOP UNIT 15'
ARRAY 5 -138.1600 -138.1600 -30.9215
END GEOM

```

```

READ ARRAY
ARA=1 NUX=15 NUY=15 NUZ=1
COM='FUEL MODULE PIN ARRAY, BELOW WATER'
FILL 1 3 11R5 3 1
      3 7 11R9 7 3
      5 13R9 5 10Q15
      3 7 11R9 7 3
      1 3 11R5 3 1      END FILL
ARA=2 NUX=15 NUY=15 NUZ=1
COM='FUEL MODULE PIN ARRAY, ABOVE WATER'
FILL 2 4 11R6 4 2
      4 8 11R10 8 4
      6 13R10 6 10Q15
      4 8 11R10 8 4
      2 4 11R6 4 2      END FILL
ARA=3 NUX=5 NUY=5 NUZ=1
COM='5X5 ARRAY OF FUEL MODULES, BELOW WATER'
FILL 11 3R13 11
      5R11
      11 3R13 11
      5R11      END FILL
ARA=4 NUX=5 NUY=5 NUZ=1
COM='5X5 ARRAY OF FUEL MODULES, BELOW WATER'
FILL 12 3R14 12
      5R12
      12 3R14 12
      5R12      END FILL
ARA=5 NUX=1 NUY=1 NUZ=2
FILL 15 16      END FILL
END ARRAY
READ BOUNDS -ZB=CONC8 END BOUNDS
READ START NST=1 END START
END DATA
END

```

```

VALIDATION CASE (CLT07 )
=CSAS25
BAW-1645-4, EXP'MT-2500, CASE C-2-C, DANCOFF FACTOR FOR EACH FUEL PIN
27GROUPNDF4 LATTICECELL
AL 1 1.0 294.0 END
AL 2 1.0 294.0 END
H2O 3 1.0 294.0 END
BORON 3 4.5520-4 294.0 END
H2O 4 0.75 294.0 END
BORON 4 3.4140-4 294.0 END
AL 4 0.25 294.0 END
CARBONSTEEL 5 1.0 294.0 END
UO2 14 0.9325 294.0 92235 2.459 92238 97.541 END
UO2 15 0.9325 294.0 92235 2.459 92238 97.541 END
UO2 17 0.9325 294.0 92235 2.459 92238 97.541 END
UO2 18 0.9325 294.0 92235 2.459 92238 97.541 END
UO2 24 0.9325 294.0 92235 2.459 92238 97.541 END
UO2 25 0.9325 294.0 92235 2.459 92238 97.541 END
UO2 27 0.9325 294.0 92235 2.459 92238 97.541 END
UO2 28 0.9325 294.0 92235 2.459 92238 97.541 END
END COMP
SQUAREPITCH 1.4097 1.0300 18 3 1.2060 1 1.0440 0 END
MORE DATA RES=14 CYLINDER 0.5150 DAN(14)=0.17297
RES=15 CYLINDER 0.5150 DAN(15)=0.24270
RES=17 CYLINDER 0.5150 DAN(17)=0.32913
RES=24 CYLINDER 0.5150 DAN(24)=0.46465
RES=25 CYLINDER 0.5150 DAN(25)=0.59972
RES=27 CYLINDER 0.5150 DAN(27)=0.79067
RES=28 CYLINDER 0.5150 DAN(28)=0.98155      END MORE
BAW-1645-4, EXP'MT-2500, CASE C-2-C, DANCOFF FACTOR FOR EACH FUEL PIN
READ PARAM FDN=YES NUB=YES END PARAM
READ GEOM

```

```

UNIT 1
COM='AL PIN BELOW WATER'
CYLINDER 2 1 0.6030 144.8500 -0.3180
CUBOID 3 1 4P0.7049 144.8500 -0.3180
UNIT 2
COM='AL PIN ABOVE WATER'
CYLINDER 2 1 0.6030 156.1220 144.8500
CUBOID 0 1 4P0.7049 156.1220 144.8500
UNIT 3
COM='FUEL PIN BELOW WATER, SURROUNDED BY 4 PINS'
CYLINDER 14 1 0.5150 144.8500 0.0
CYLINDER 0 1 0.5220 144.8500 0.0
CYLINDER 1 1 0.6030 144.8500 -0.3180
CUBOID 3 1 4P0.7049 144.8500 -0.3180
UNIT 4
COM='FUEL PIN ABOVE WATER, SURROUNDED BY 4 PINS'
CYLINDER 24 1 0.5150 153.3400 144.8500
CYLINDER 0 1 0.5220 155.8040 144.8500
CYLINDER 1 1 0.6030 156.1220 144.8500
CUBOID 0 1 4P0.7049 156.1220 144.8500
UNIT 5
COM='FUEL PIN BELOW WATER, SURROUNDED BY 5 PINS'
CYLINDER 15 1 0.5150 144.8500 0.0
CYLINDER 0 1 0.5220 144.8500 0.0
CYLINDER 1 1 0.6030 144.8500 -0.3180
CUBOID 3 1 4P0.7049 144.8500 -0.3180
UNIT 6
COM='FUEL PIN ABOVE WATER, SURROUNDED BY 5 PINS'
CYLINDER 25 1 0.5150 153.3400 144.8500
CYLINDER 0 1 0.5220 155.8040 144.8500
CYLINDER 1 1 0.6030 156.1220 144.8500
CUBOID 0 1 4P0.7049 156.1220 144.8500
UNIT 7
COM='FUEL PIN BELOW WATER, SURROUNDED BY 7 PINS'
CYLINDER 17 1 0.5150 144.8500 0.0
CYLINDER 0 1 0.5220 144.8500 0.0
CYLINDER 1 1 0.6030 144.8500 -0.3180
CUBOID 3 1 4P0.7049 144.8500 -0.3180
UNIT 8
COM='FUEL PIN ABOVE WATER, SURROUNDED BY 7 PINS'
CYLINDER 27 1 0.5150 153.3400 144.8500
CYLINDER 0 1 0.5220 155.8040 144.8500
CYLINDER 1 1 0.6030 156.1220 144.8500
CUBOID 0 1 4P0.7049 156.1220 144.8500
UNIT 9
COM='FUEL PIN BELOW WATER, SURROUNDED BY 8 PINS'
CYLINDER 18 1 0.5150 144.8500 0.0
CYLINDER 0 1 0.5220 144.8500 0.0
CYLINDER 1 1 0.6030 144.8500 -0.3180
CUBOID 3 1 4P0.7049 144.8500 -0.3180
UNIT 10
COM='FUEL PIN ABOVE WATER, SURROUNDED BY 8 PINS'
CYLINDER 28 1 0.5150 153.3400 144.8500
CYLINDER 0 1 0.5220 155.8040 144.8500
CYLINDER 1 1 0.6030 156.1220 144.8500
CUBOID 0 1 4P0.7049 156.1220 144.8500
UNIT 11
COM='FUEL MODULE W/O AL SIDE PLATE, BELOW WATER'
ARRAY 1 -9.1637 -9.1637 -0.3180
CUBOID 3 1 4P9.5250 144.8500 -0.3180
CUBOID 4 1 4P9.5250 144.8500 -1.3848
CUBOID 2 1 4P9.5250 144.8500 -3.1755
CUBOID 3 1 4P9.9578 144.8500 -3.1755
UNIT 12
COM='FUEL MODULE W/O AL SIDE PLATE, ABOVE WATER'
ARRAY 2 -9.1637 -9.1637 144.8500
CUBOID 0 1 4P9.5250 156.1220 144.8500
CUBOID 2 1 4P9.5250 157.7095 144.8500
CUBOID 0 1 4P9.9578 157.7095 144.8500
UNIT 13
COM='FUEL MODULE W AL SIDE PLATE, BELOW WATER'
ARRAY 1 -9.1637 -9.1637 -0.3180
CUBOID 3 1 2P9.1637 2P9.3957 144.8500 -0.3180
CUBOID 2 1 2P9.1637 2P9.5250 144.8500 -0.3180
CUBOID 3 1 4P9.5250 144.8500 -0.3180
CUBOID 4 1 4P9.5250 144.8500 -1.3848
CUBOID 2 1 4P9.5250 144.8500 -3.1755
CUBOID 3 1 4P9.9578 144.8500 -3.1755
UNIT 14
COM='FUEL MODULE W AL SIDE PLATE, ABOVE WATER'
ARRAY 2 -9.1637 -9.1637 144.8500
CUBOID 0 1 2P9.1637 2P9.3957 156.1220 144.8500
CUBOID 2 1 2P9.1637 2P9.5250 156.1220 144.8500
CUBOID 0 1 4P9.5250 156.1220 144.8500

```

CUBOID 2 1 4P9.5250 157.7095 144.8500
CUBOID 0 1 4P9.9578 157.7095 144.8500

UNIT 15
COM='5X5 ARRAY OF FUEL MODULES, BELOW WATER'
ARRAY 3 -49.7890 -49.7890 -3.1755
CUBOID 3 1 4P60.9600 144.8500 -3.1755
CUBOID 2 1 4P60.9600 144.8500 -11.8115
CYLINDER 3 1 137.1600 144.8500 -14.6815
CYLINDER 5 1 138.1600 144.8500 -15.6815
CUBOID 0 1 4P138.1600 144.8500 -30.9215

UNIT 16
COM='5X5 ARRAY OF FUEL MODULES, ABOVE WATER'
ARRAY 4 -49.7890 -49.7890 144.8500
CUBOID 0 1 4P60.9600 157.7095 144.8500
CYLINDER 0 1 137.1600 157.7095 144.8500
CYLINDER 5 1 138.1600 157.7095 144.8500
CUBOID 0 1 4P138.1600 157.7095 144.8500

GLOBAL
UNIT 17
COM='STACK UNIT 16 ATOP UNIT 15'
ARRAY 5 -138.1600 -138.1600 -30.9215
END GEOM

READ ARRAY
ARA=1 NUX=13 NUY=13 NUZ=1
COM='FUEL MODULE PIN ARRAY, BELOW WATER'
FILL 1 3 9R5 3 1
3 7 9R9 7 3
5 11R9 5 8Q13
3 7 9R9 7 3
1 3 9R5 3 1 END FILL
ARA=2 NUX=13 NUY=13 NUZ=1
COM='FUEL MODULE PIN ARRAY, ABOVE WATER'
FILL 2 4 9R6 4 2
4 8 9R10 8 4
6 11R10 6 8Q13
4 8 9R10 8 4
2 4 9R6 4 2 END FILL
ARA=3 NUX=5 NUY=5 NUZ=1
COM='5X5 ARRAY OF FUEL MODULES, BELOW WATER'
FILL 5R11
11 3R13 11
5R11
11 3R13 11
5R11 END FILL
ARA=4 NUX=5 NUY=5 NUZ=1
COM='5X5 ARRAY OF FUEL MODULES, BELOW WATER'
FILL 5R12
12 3R14 12
5R12
12 3R14 12
5R12 END FILL
ARA=5 NUX=1 NUY=1 NUZ=2
FILL 15 16 END FILL
END ARRAY
READ BOUNDS -ZB=CONC8 END BOUNDS
READ START NST=1 END START
END DATA
END

VALIDATION CASE (CLT08)
=CSAS25
BAW-1645-4, EXP/MT-2505, CASE C-2-C, DANC OFF FACTOR FOR EACH FUEL PIN
27GROUPNDF4 LATTICECELL
AL 1 1.0 296.0 END
AL 2 1.0 296.0 END
H2O 3 1.0 296.0 END
BORON 3 4.2055-4 296.0 END
H2O 4 0.75 296.0 END
BORON 4 3.1541-4 296.0 END
AL 4 0.25 296.0 END
CARBONSTEEL 5 1.0 296.0 END
UO2 14 0.9325 296.0 92235 2.459 92238 97.541 END
UO2 15 0.9325 296.0 92235 2.459 92238 97.541 END
UO2 17 0.9325 296.0 92235 2.459 92238 97.541 END
UO2 18 0.9325 296.0 92235 2.459 92238 97.541 END
UO2 24 0.9325 296.0 92235 2.459 92238 97.541 END
UO2 25 0.9325 296.0 92235 2.459 92238 97.541 END
UO2 27 0.9325 296.0 92235 2.459 92238 97.541 END
UO2 28 0.9325 296.0 92235 2.459 92238 97.541 END
END COMP
SQUAREPITCH 1.4097 1.0300 18 3 1.2060 1 1.0440 0 END
MORE DATA RES=14 CYLINDER 0.5150 DAN(14)=0.17297
RES=15 CYLINDER 0.5150 DAN(15)=0.24270
RES=17 CYLINDER 0.5150 DAN(17)=0.32913


```

RES=24 CYLINDER 0.5150 DAN(24)=0.46465
RES=25 CYLINDER 0.5150 DAN(25)=0.59972
RES=27 CYLINDER 0.5150 DAN(27)=0.79067
RES=28 CYLINDER 0.5150 DAN(28)=0.98155      END MORE
BAW-1645-4, EXP'MT-2505, CASE C-2-C, DANC OFF FACTOR FOR EACH FUEL PIN
READ PARAM FDN=YES NUB=YES END PARAM
READ GEOM

```

```

UNIT 1
COM='AL PIN BELOW WATER'
CYLINDER 2 1 0.6030 101.8100 -0.3180
CUBOID 3 1 4P0.7049 101.8100 -0.3180
UNIT 2
COM='AL PIN ABOVE WATER'
CYLINDER 2 1 0.6030 156.1220 101.8100
CUBOID 0 1 4P0.7049 156.1220 101.8100

```

```

UNIT 3
COM='FUEL PIN BELOW WATER, SURROUNDED BY 4 PINS'
CYLINDER 14 1 0.5150 101.8100 0.0
CYLINDER 0 1 0.5220 101.8100 0.0
CYLINDER 1 1 0.6030 101.8100 -0.3180
CUBOID 3 1 4P0.7049 101.8100 -0.3180

```

```

UNIT 4
COM='FUEL PIN ABOVE WATER, SURROUNDED BY 4 PINS'
CYLINDER 24 1 0.5150 153.3400 101.8100
CYLINDER 0 1 0.5220 155.8040 101.8100
CYLINDER 1 1 0.6030 156.1220 101.8100
CUBOID 0 1 4P0.7049 156.1220 101.8100

```

```

UNIT 5
COM='FUEL PIN BELOW WATER, SURROUNDED BY 5 PINS'
CYLINDER 15 1 0.5150 101.8100 0.0
CYLINDER 0 1 0.5220 101.8100 0.0
CYLINDER 1 1 0.6030 101.8100 -0.3180
CUBOID 3 1 4P0.7049 101.8100 -0.3180

```

```

UNIT 6
COM='FUEL PIN ABOVE WATER, SURROUNDED BY 5 PINS'
CYLINDER 25 1 0.5150 153.3400 101.8100
CYLINDER 0 1 0.5220 155.8040 101.8100
CYLINDER 1 1 0.6030 156.1220 101.8100
CUBOID 0 1 4P0.7049 156.1220 101.8100

```

```

UNIT 7
COM='FUEL PIN BELOW WATER, SURROUNDED BY 7 PINS'
CYLINDER 17 1 0.5150 101.8100 0.0
CYLINDER 0 1 0.5220 101.8100 0.0
CYLINDER 1 1 0.6030 101.8100 -0.3180
CUBOID 3 1 4P0.7049 101.8100 -0.3180

```

```

UNIT 8
COM='FUEL PIN ABOVE WATER, SURROUNDED BY 7 PINS'
CYLINDER 27 1 0.5150 153.3400 101.8100
CYLINDER 0 1 0.5220 155.8040 101.8100
CYLINDER 1 1 0.6030 156.1220 101.8100
CUBOID 0 1 4P0.7049 156.1220 101.8100

```

```

UNIT 9
COM='FUEL PIN BELOW WATER, SURROUNDED BY 8 PINS'
CYLINDER 18 1 0.5150 101.8100 0.0
CYLINDER 0 1 0.5220 101.8100 0.0
CYLINDER 1 1 0.6030 101.8100 -0.3180
CUBOID 3 1 4P0.7049 101.8100 -0.3180

```

```

UNIT 10
COM='FUEL PIN ABOVE WATER, SURROUNDED BY 8 PINS'
CYLINDER 28 1 0.5150 153.3400 101.8100
CYLINDER 0 1 0.5220 155.8040 101.8100
CYLINDER 1 1 0.6030 156.1220 101.8100
CUBOID 0 1 4P0.7049 156.1220 101.8100

```

```

UNIT 11
COM='FUEL MODULE W/O AL SIDE PLATE, BELOW WATER'
ARRAY 1 -9.1637 -9.1637 -0.3180
CUBOID 3 1 4P9.5250 101.8100 -0.3180
CUBOID 4 1 4P9.5250 101.8100 -1.3848
CUBOID 2 1 4P9.5250 101.8100 -3.1755
CUBOID 3 1 4P9.9578 101.8100 -3.1755

```

```

UNIT 12
COM='FUEL MODULE W/O AL SIDE PLATE, ABOVE WATER'
ARRAY 2 -9.1637 -9.1637 101.8100
CUBOID 0 1 4P9.5250 156.1220 101.8100
CUBOID 2 1 4P9.5250 157.7095 101.8100
CUBOID 0 1 4P9.9578 157.7095 101.8100

```

```

UNIT 13
COM='FUEL MODULE W AL SIDE PLATE, BELOW WATER'
ARRAY 1 -9.1637 -9.1637 -0.3180
CUBOID 3 1 2P9.1637 2P9.3957 101.8100 -0.3180
CUBOID 2 1 2P9.1637 2P9.5250 101.8100 -0.3180
CUBOID 3 1 4P9.5250 101.8100 -0.3180
CUBOID 4 1 4P9.5250 101.8100 -1.3848

```

```

CUBOID 2 1 4P9.5250 101.8100 -3.1755
CUBOID 3 1 4P9.9578 101.8100 -3.1755
UNIT 14
COM='FUEL MODULE W AL SIDE PLATE, ABOVE WATER'
ARRAY 2 -9.1637 -9.1637 101.8100
CUBOID 0 1 2P9.1637 2P9.3957 156.1220 101.8100
CUBOID 2 1 2P9.1637 2P9.5250 156.1220 101.8100
CUBOID 0 1 4P9.5250 156.1220 101.8100
CUBOID 2 1 4P9.5250 157.7095 101.8100
CUBOID 0 1 4P9.9578 157.7095 101.8100

```

```

UNIT 15
COM='5X5 ARRAY OF FUEL MODULES, BELOW WATER'
ARRAY 3 -49.7890 -49.7890 -3.1755
CUBOID 3 1 4P60.9600 101.8100 -3.1755
CUBOID 2 1 4P60.9600 101.8100 -11.8115
CYLINDER 3 1 137.1600 101.8100 -14.6815
CYLINDER 5 1 138.1600 101.8100 -15.6815
CUBOID 0 1 4P138.1600 101.8100 -30.9215

```

```

UNIT 16
COM='5X5 ARRAY OF FUEL MODULES, ABOVE WATER'
ARRAY 4 -49.7890 -49.7890 101.8100
CUBOID 0 1 4P60.9600 157.7095 101.8100
CYLINDER 0 1 137.1600 157.7095 101.8100
CYLINDER 5 1 138.1600 157.7095 101.8100
CUBOID 0 1 4P138.1600 157.7095 101.8100

```

GLOBAL

```

UNIT 17
COM='STACK UNIT 16 ATOP UNIT 15'
ARRAY 5 -138.1600 -138.1600 -30.9215
END GEOM

```

```

READ ARRAY
ARA=1 NUX=13 NUY=13 NUZ=1
COM='FUEL MODULE PIN ARRAY, BELOW WATER'
FILL 1 3 9R5 3 1
      3 7 9R9 7 3
      5 11R9 5 8Q13
      3 7 9R9 7 3
      1 3 9R5 3 1 END FILL
ARA=2 NUX=13 NUY=13 NUZ=1
COM='FUEL MODULE PIN ARRAY, ABOVE WATER'
FILL 2 4 9R6 4 2
      4 8 9R10 8 4
      6 11R10 6 8Q13
      4 8 9R10 8 4
      2 4 9R6 4 2 END FILL
ARA=3 NUX=5 NUY=5 NUZ=1
COM='5X5 ARRAY OF FUEL MODULES, BELOW WATER'
FILL 5R11
      11 3R13 11
      5R11
      11 3R13 11
      5R11 END FILL
ARA=4 NUX=5 NUY=5 NUZ=1
COM='5X5 ARRAY OF FUEL MODULES, BELOW WATER'
FILL 5R12
      12 3R14 12
      5R12
      12 3R14 12
      5R12 END FILL
ARA=5 NUX=1 NUY=1 NUZ=2
FILL 15 16 END FILL
END ARRAY
READ BOUNDS -ZB=CONC8 END BOUNDS
READ START NST=1 END START
END DATA
END

```

```

VALIDATION CASE (HCAA14 )
=CSAS25
ROCKY FLATS UO2(NO3)2 SOLN 54.89 G U/L
27GROUPNDF4 MULTIREGION
SOLNUO2(NO3)2 1 54.89 0.105 1 293 92234 1.022 92235 93.172 92236 .434
92238 5.372 END
AL 2 1 END
END COMP
CYLINDRICAL END
1 16.5 NOEXTERMOD 2 16.8 NOEXTERMOD END ZONE
ROCKY FLATS UO2(NO3)2 SOLN 33.01 CM DIAM BARE 3
READ PARAM NPG=600 NUB=YES FDN=YES END PARAM
READ GEOM
CYLINDER 1 1 16.505 39.48 0
CYLINDER 2 1 16.825 39.48 -.32
END GEOM
END DATA
END

```

VALIDATION CASE (HCAS02)
 =CSAS25
 KENO-5 VALIDATION CASE A-10
 27GROUPNDF4 MULTIREGION
 URANIUM 1 .9866 293 92235 97.67 92238 2.33 END
 H2O 2 END
 PLEXIGLASS 3 END
 END COMP
 SPHERICAL END
 1 6.55 ONEEXTERMOD 2 12.7 NOEXTERMOD END ZONE
 KENO-5 VALIDATION CASE A-10
 READ PARAM TME=60 NPG=600 FDN=YES NUB=YES END PARAM
 READ GEOM
 BOX TYPE 1
 SPHERE 1 1 6.5537
 CUBOID 2 1 12.7 -12.7 12.7 -12.7 6.5537 -6.5537
 BOX TYPE 2
 CYLINDER 2 1 4.1275 1.27 -1.27
 CYLINDER 3 1 12.7 1.27 -1.27
 CUBOID 2 1 12.7 -12.7 12.7 -12.7 1.27 -1.27
 CORE 0 1 -12.7 -12.7 -7.8237
 CYLINDER 2 1 30.48 24.3337 -39.5737
 END GEOM
 READ ARRAY NUX=1 NUY=1 NUZ=2 LOOP
 1 1 1 1 1 1 2 2 1
 2 1 1 1 1 1 1 1 1
 END ARRAY
 END DATA
 END

VALIDATION CASE (HCAS06)
 =CSAS25
 KENO-5 VALIDATION CASE A-4
 27GROUPNDF4 MULTIREGION
 SOLNUO2(NO3)2 1 20.15 .139 1 293 92235 93.18 92238 6.82 END
 AL 2 END
 END COMP
 SPHERICAL END
 1 34.6 ONEEXTERMOD 2 34.92 NOEXTERMOD END ZONE
 KENO-5 VALIDATION CASE A-4
 READ PARAM NPG=600 FDN=YES NUB=YES END PARAM
 READ GEOM
 SPHERE 1 1 34.6
 SPHERE 2 1 34.92
 CUBE 0 1 35.0 -35.0
 END GEOM
 END DATA
 END

VALIDATION CASE (HCAS07)
 =CSAS25
 KENO-5 VALIDATION CASE A-5
 27GROUPNDF4 MULTIREGION
 URANIUM 1 .9848 283 92235 93.5 92238 6.5 END
 H2O 2 END
 END COMP
 SPHERICAL END
 1 12.7 ONEEXTERMOD 2 31. NOEXTERMOD END ZONE
 KENO-5 VALIDATION CASE A-5
 READ PARAM TME=60 NPG=600 FDN=YES NUB=YES END PARAM
 READ GEOM
 HEMISPHERE 2 1 12.7
 HEMISPHERE 1 1 15.24
 CUBOID 2 1 31.00 -31.00 31.00 -31.00 31.00 -16.
 END GEOM
 END DATA
 END

VALIDATION CASE (HCAS11)
 =CSAS25
 KENO-5 VALIDATION CASE A-9
 27GROUPNDF4 MULTIREGION
 ARBMOIL .88 3 0 0 0 6012 86.82 1001 13.16 16000 .02 1 END
 URANIUM 2 .9528 293 92235 93.1 92238 6.9 END
 ARBMPJEL .024 2 0 0 0 6012 85 1001 15 2 END
 CARBONSTEEL 3 END
 END COMP
 SPHERICAL END
 2 8.2 ONEEXTERMOD 1 40.5 NOEXTERMOD END ZONE
 KENO-5 VALIDATION CASE A-9
 READ PARAM
 TME=60 NPG=600 FDN=YES NUB=YES END PARAM
 READ GEOM
 HEMISPHERE 3 1 6.012
 HEMISPHERE 2 1 10.488
 SPHERE 1 1 40.438
 CUBE 0 1 41.0 -41.0

END GEOM
END DATA
END

VALIDATION CASE (HCAS18)
=CSAS25
KENO-5 VALIDATION CASE B-15
27GROUPNDF4 MULTIREGION
SOLNUO2(NO3)2 1 415 0 1 293 92235 92.6 92238 7.4 END
PLEXIGLASS 2 1 END
END COMP
CYLINDRICAL END
1 9.52 ONEEXTERMOD 2 10.16 NOEXTERMOD END ZONE
KENO-5 VALIDATION CASE B-15
READ PARAM TME=60 NPG=600 FDN=YES NUB=YES END PARAM
READ GEOM
CYLINDER 1 1 9.52 8.7804 -8.7804
CYLINDER 0 1 9.52 8.9896 -8.7804
CYLINDER 2 1 10.16 9.6296 -9.4204
CUBOID 0 1 14.54 -14.54 14.54 -14.54 14.0096 -13.8004
CORE 0 1 -43.62 -43.62 -41.715
CUBOID 2 1 44.89 -44.89 44.89 -44.89 42.985 -42.985
END GEOM
READ ARRAY NUX=3 NUY=3 NUZ=3 END ARRAY
END DATA
END

VALIDATION CASE (HCAS28)
=CSAS25
KENO-5 VALIDATION CASE B-8
27GROUPNDF4 MULTIREGION
URANIUM 1 .9848 293 92235 93.2 92238 6.8 END
PLEXIGLASS 2 1 END
END COMP
CYLINDRICAL END
1 5.753 NOEXTERMOD END ZONE
KENO-5 VALIDATION CASE B-8
READ PARAM NPG=600 FDN=YES NUB=YES END PARAM
READ GEOM
BOX TYPE 1
CYLINDER 1 1 5.753 5.3825 -5.3825
CUBOID 0 1 7.68 -7.68 7.68 -7.68 7.33 -7.33
CUBOID 2 1 8.95 -8.95 8.95 -8.95 8.6 -8.6
CUBOID 0 1 9.0599 -9.0599 9.0599 -9.0599 8.6975 -8.6975
END GEOM
READ ARRAY NUX=2 NUY=2 NUZ=2 END ARRAY
END DATA
END

VALIDATION CASE (HCAS32)
=CSAS25
93.2% UO2F2 H/U-235=337
27GROUPNDF4 MULTIREGION
SOLNUO2F2 1 81.845 0 1 293 92235 93.2
92238 6.8 END
AL 2 1 END
CARBONSTEEL 3 1 END
PLEXIGLASS 4 1 END
ARBMWOOD .640525 3 0 0 0 6012 44.435 1001 6.2639 8016 49.301 5 END
REG-CONCRETE 6 END
END COMP
SLAB END
1 3.81 NOEXTERMOD 2 4.12 NOEXTERMOD END ZONE
93.2% UO2F2 3 IN AL SLAB 3X1X1 ARRAY 1 IN SEP ROOM
READ PARAM NPG=600 FDN=YES NUB=YES END PARAM
READ GEOM
CUBOID 1 1 2P3.81 2P60.325 34.44 0
REFLECTOR 2 1 4R.318 0 .318 1
CUBOID 0 1 2P5.398 2P65. 150. -1.
CORE 0 1 -15.194 -65. -1.
CYLINDER 0 1 142.8 212. -60.
CYLINDER 3 1 144.8 212. -62.
CUBOID 0 1 275.5 -638.9 475. -744.2 588. -62.
REFLECTOR 4 1 5R0 .32 1
REFLECTOR 5 1 5R0 1.27 1
REFLECTOR 3 1 5R0 .64 1
REFLECTOR 0 1 5R0 365 1
REFLECTOR 6 2 6R3 10
REFLECTOR 6 12 0 3 4R0 10
END GEOM
READ BIAS ID=301 2 21 END BIAS
READ ARRAY NUX=3 NUY=1 NUZ=1 END ARRAY
END DATA
END

VALIDATION CASE (HCAS52)
 =CSAS25
 93.2% UO2F2 H/U-235=337
 27GROUPNDF4 MULTIREGION
 SOLNUO2F2 1 81.845 0 1 293 92235 93.2
 92238 6.8 END
 AL 2 1 END
 END COMP
 SLAB END
 1 7.62 NOEXTERMOD 2 7.94 NOEXTERMOD END ZONE
 93.2% UO2F2 6 & 3 IN AL SLABS 2X1X1 ARRAY 6 IN SEP
 READ PARAM NPG=600 FDN=YES NUB=YES END PARAM
 READ GEOM
 UNIT 1
 CUBOID 1 1 2P3.81 2P60.325 45.03 0
 REFLECTOR 2 1 4R.318 0 .318 1
 CUBOID 0 1 2P4.128 2P65. 150. -1.
 UNIT 2
 CUBOID 2 1 2P.318 2P60.325 45.03 0
 CUBOID 1 1 2P7.938 2P60.325 45.03 0
 REFLECTOR 2 1 4R.318 0 .318 1
 CUBOID 0 1 2P8.574 2P65. 150. -1.
 UNIT 3
 CUBOID 0 1 15.24 0 2P65. 150. -1.
 END GEOM
 READ ARRAY NUX=3 NUY=1 NUZ=1 FILL 2 3 1 END FILL END ARRAY
 END DATA
 END

VALIDATION CASE (HCAS60)
 =CSAS25
 UO2(NO3)2 279 G U/L
 27GROUPNDF4 MULTIREGION
 SOLNUO2(NO3)2 1 279 0 1 293 92235 92.6 92238 7.4 END
 PLEXIGLASS 2 1 END
 ARBMWOOD .640525 3 0 0 0 6012 44.435 1001 6.2639 8016 49.301 3 END
 CARBONSTEEL 4 END
 REG-CONCRETE 5 END
 END COMP
 CYLINDRICAL END
 1 9.52 ONEEXTERMOD 2 10.16 NOEXTERMOD END ZONE
 UO2(NO3)2 279 G U/L 3X3X3 ARRAY UNREFL. WALLS, TANK, & FLOOR
 READ PARAM NPG=600 FDN=YES NUB=YES PLT=NO END PARAM
 READ GEOM
 UNIT 1
 CYLINDER 1 1 9.52 17.5609 0.
 CYLINDER 0 1 9.52 17.77 0.
 CYLINDER 2 1 10.16 18.41 -.64
 CUBOID 0 1 4P13.36 21.61 -3.84
 UNIT 2
 ARRAY 1 2R-40.08 0.
 CUBOID 0 1 4P200. 250. -50.
 UNIT 3
 CYLINDER 0 1 142.8 224. -48.
 CYLINDER 4 1 144.8 224. -50.
 CUBOID 0 1 218.1 -181.9 215. -185. 250. -50.
 ARRAY 2 3R0
 REFLECTOR 0 1 57.4 57. 260. 559.2 400. 0. 1
 REFLECTOR 2 1 5R0 .32 1
 REFLECTOR 3 1 5R0 1.27 1
 REFLECTOR 4 1 5R0 .64 1
 REFLECTOR 0 1 5R0 365 1
 REFLECTOR 5 2 6R3 10
 REFLECTOR 5 12 0 3 4R0 10
 END GEOM
 READ START XSM=160 XSP=240 YSM=160 YSP=240 ZSM=50 ZSP=127 END START
 READ BIAS ID=301 2 21 END BIAS
 READ ARRAY ARA=1 NUX=3 NUY=3 NUZ=3 FILL F1 END FILL
 ARA=2 NUX=2 NUY=1 NUZ=1 FILL 2 3 END FILL END ARRAY
 READ PLOT PLT=NO
 XUL=113.2 YUL=286.8 ZUL=60. XLR=286.8 YLR=113.2 ZLR=60.
 UAX=1 VDN=-1 NAX=125 END
 XUL=437.1 YUL=329.8 ZUL=60. XLR=726.7 YLR=40.2 ZLR=60. END
 END PLOT
 END DATA
 END

VALIDATION CASE (HCAS74)
 =CSAS25
 UO2(NO3)2 415 G U/L
 27GROUPNDF4 MULTIREGION
 SOLNUO2(NO3)2 1 415 0 1 293 92235 92.6 92238 7.4 END
 PLEXIGLASS 2 1 END
 PARA(H2O) 3 1 END
 END COMP
 CYLINDRICAL END
 1 9.52 ONEEXTERMOD 2 10.16 NOEXTERMOD END ZONE

```
U02(N03)2 415 G U/L 3X3X3 ARRAY 15.24 CM PARAFFIN REFL.  
READ PARAM NPG=600 FDN=YES NUB=YES END PARAM  
READ GEOM  
CYLINDER 1 1 9.52 17.5609 0.  
CYLINDER 0 1 9.52 17.77 0.  
CYLINDER 2 1 10.16 18.41 -.64  
CUBOID 0 1 4P18.425 26.675 -8.905  
CORE 0 1 3R0.  
REFLECTOR 3 2 6R3 4  
REFLECTOR 3 6 6R3.24 1  
END GEOM  
READ BIAS ID=400 2 6 END BIAS  
READ ARRAY NUX=3 NUY=3 NUZ=3 END ARRAY  
END DATA  
END
```

APPENDIX B. CALCULATED RESULTS AND EXPERIMENTAL PARAMETERS

In order to analyze the data from the validation calculations, the experiments were parameterized. The results could then be categorized in a number of ways to test for trends and bias. Table B.1 contains the parameters which were used for data analysis for each experiment.

Key terms are as follows:

RUN	- Sequential number assigned to experiments.
MEMB	- Case number which corresponds to Tables 1-6.
KEFF	- KENO calculated k.
SDM	- KENO calculated standard deviation.
AEG	- Average energy group of neutron causing fission.
ENRLEV	- Enrichment level (high, intermediate, low).
ASSAY	- Fuel enrichment.
REFLCOND	- Reflection condition (reflected, partially reflected, unreflected).
REFL	- Reflector material.
SYSGEOM	- Overall system geometry (array, single unit).
UNITGEOM	- Principal geometry of unit (cylinder, slab, sphere).
FUELMIX	- Indicator as to whether the system was considered primarily heterogeneous or homogeneous.
FUEL	- Primary form of fissile material.
FMATL	- Principal fissile nuclide in fuel.
REF	- Reference number for reference which describes the critical experiment.

New Data-----Nov. 13, 1990

MEMB	KEFF	SDM	AEG	ENRLEV	ASSAY	REFLCOND	REFL	SYSGEOM	UNITGEOM	FUELMIX	FUEL	FMATL
CAA01	0.98944	0.00396	21.1691	L	4.89	R	H2O	A	CY	HET	METAL	U235
CAA04	0.98931	0.00319	23.1187	L	4.89	R	H2O	A	CY	HET	METAL	U235
CAA07	0.98055	0.00315	21.3937	L	4.89	R	PB	A	CY	HET	METAL	U235
CAA12	0.97925	0.00253	24.0354	L	4.89	R	UO2F2	A	CY	HET	METAL	U235
CAA14	0.98931	0.00319	23.1187	L	4.89	R	UO2F2	A	CY	HET	METAL	U235
CAA19	0.99127	0.00356	23.3604	L	4.89	U		S	SL	HOM	U308	U235
CAA21	0.99969	0.00331	24.5658	L	4.89	U		S	SL	HOM	U308	U235
CAA25	0.99988	0.00324	24.1875	L	4.89	U	H2O	S	SL	HOM	U308	U235
CAA27	0.98726	0.00340	22.8547	L	4.89	U	H2O	S	SL	HOM	U308	U235
CAA29	0.98595	0.00310	24.3732	L	4.89	U	H2O	S	SL	HOM	U308	U235
CAA33	0.99157	0.00241	24.7165	L	4.89	U		S	SP	HOM	UO2F2	U235
CAA38	1.00000	0.00254	24.7870	L	4.89	R	H2O	S	SP	HOM	UO2F2	U235
CAB03	0.99246	0.00239	16.7469	L	3.85	R	H2O	A	CY	HET	METAL	U235
CAB08	0.99321	0.00295	15.5959	L	3.85	R	H2O	A	CY	HET	METAL	U235
CAB11	1.00168	0.00270	17.1817	L	3.85	R	H2O	A	CY	HET	METAL	U235
CAB15	1.00502	0.00294	18.5659	L	3.85	R	H2O	A	CY	HET	METAL	U235
CAS04	0.98537	0.00225	23.2734	L	1.40	U		S	SL	HOM	UF4	U235
CAS06	0.98605	0.00202	23.2791	L	1.40	U		S	SL	HOM	UF4	U235
CAS11	0.99445	0.00270	22.4849	L	2.00	R	PARA	S	SL	HOM	UF4	U235
CAS13	0.99878	0.00278	23.2174	L	2.00	R	PARA	S	SL	HOM	UF4	U235
CAS16	0.98975	0.00250	23.9037	L	2.00	R	PARA	S	SL	HOM	UF4	U235
CAS17	0.98853	0.00272	24.1057	L	2.00	R	PARA	S	SL	HOM	UF4	U235
CAS21	1.00663	0.00307	22.2061	L	3.00	R	PARA	S	SL	HOM	UF4	U235
CAS23	1.01240	0.00315	22.2218	L	3.00	R	PARA	S	SL	HOM	UF4	U235
CAS26	1.00723	0.00282	21.7608	L	3.00	U		S	SL	HOM	UF4	U235
CAS29	1.00697	0.00324	23.5224	L	3.00	R	POLY	S	SL	HOM	UF4	U235
CAS31	1.00426	0.00292	23.2732	L	3.00	U		S	SL	HOM	UF4	U235
CAS33	0.99340	0.00275	24.2199	L	4.98	R	COMP	S	CY	HOM	UO2F2	U235
CAS34	0.99148	0.00305	24.2248	L	4.98	R	COMP	S	CY	HOM	UO2F2	U235
CAS36	0.99546	0.00316	24.2270	L	4.98	U		S	CY	HOM	UO2F2	U235
CAR01	1.01259	0.00308	21.3757	L	4.46	R	PLEX	S	SL	HET	U308	U235
CAR04	1.01155	0.00320	21.1831	L	4.46	R	CONC	S	SL	HET	U308	U235
CAR07	1.01583	0.00366	18.3377	L	4.46	R	PLEX	S	SL	HOM	U308	U235
CAR08	1.00169	0.00352	19.2762	L	4.46	R	PLEX	S	SL	HOM	U308	U235
CAR11	1.00698	0.00325	21.5422	L	4.46	R	PLEX	S	SL	HET	U308	U235
CAR13	1.00808	0.00296	20.1769	L	4.46	R	PLEX	S	SL	HET	U308	U235
CAR15	0.99945	0.00302	18.5301	L	4.46	R	PLEX	S	SL	HOM	U308	U235
CAR16	1.00896	0.00342	19.3123	L	4.46	R	PLEX	S	SL	HOM	U308	U235
CAR18	1.00868	0.00312	21.8624	L	4.46	R	PLEX	S	SL	HET	U308	U235
CAR20	1.00356	0.00263	18.3286	L	4.46	R	PLEX	S	SL	HOM	U308	U235
CLT01	0.98300	0.00352	19.2219	L	2.459	R	H2O	A	CY	HET	UO2	U235
CLT02	0.97715	0.00375	19.1577	L	2.459	R	H2O	A	CY	HET	UO2	U235
CLT03	0.98178	0.00310	19.7538	L	2.459	R	H2O	A	CY	HET	UO2	U235
CLT04	0.99676	0.00429	20.2683	L	2.459	R	H2O	A	CY	HET	UO2	U235
CLT05	0.98644	0.00306	19.8747	L	2.459	R	H2O	A	CY	HET	UO2	U235
CLT06	0.98733	0.00340	19.7891	L	2.459	R	H2O	A	CY	HET	UO2	U235
CLT07	1.00191	0.00304	21.5533	L	2.459	R	H2O	A	CY	HET	UO2	U235
CLT08	0.99282	0.00370	21.4604	L	2.459	R	H2O	A	CY	HET	UO2	U235
HCAA14	1.01405	0.00391	24.5715	H	93.20	U		S	CY	HOM	NITRATE	U235
HCAS02	1.01136	0.00309	8.5257	H	97.67	R	H2O	S	SP	HOM	METAL	U235
HCAS06	1.00162	0.00224	24.9967	H	93.20	U		S	SP	HOM	NITRATE	U235
HCAS07	1.01401	0.00307	11.7440	H	93.50	R	H2O	S	SP	HET	METAL	U235
HCAS11	0.99561	0.00319	9.4317	H	93.10	R	OIL	S	SP	HET	METAL	U235
HCAS18	1.00797	0.00388	21.5727	H	92.60	R	PLEX	A	CY	HOM	NITRATE	U235
HCAS28	1.01331	0.00305	7.7109	H	93.20	U		A	CY	HET	METAL	U235
HCAS32	0.97311	0.00341	24.2583	H	93.20	U		A	SL	HOM	UO2F2	U235
HCAS52	0.98831	0.00360	24.2576	H	93.20	U		A	SL	HOM	UO2F2	U235
HCAS60	1.00268	0.00436	22.5067	H	92.60	U		A	CY	HOM	NITRATE	U235
HCAS74	1.02539	0.00439	22.1205	H	92.60	R	PARA	A	CY	HOM	NITRATE	U235

APPENDIX C. STATISTICAL ANALYSIS OF VALIDATION RESULTS

```

0      input to statistical treatment
0      KENOV.a Validation 1-15-91. Low Enriched Experiments
0      proportion of the population = .999
      confidence of fit = .950
      confidence on proportion = .950
      number of observations = 48
      minimum value of closed band = .00
      maximum value of closed band = .00
      estimated sample deviation = 3.10199E-03
0      independent      dependent      independent      dependent      deviation
      variable - x      variable - y      in y      variable - x      variable - y      in y
      2.11690E+01      9.89440E-01      3.96000E-03      2.17610E+01      1.00720E+00      2.82000E-03
      2.31190E+01      9.89310E-01      3.19000E-03      2.35220E+01      1.00700E+00      3.24000E-03
      2.13940E+01      9.80550E-01      3.15000E-03      2.32730E+01      1.00430E+00      2.92000E-03
      2.40350E+01      9.79250E-01      2.53000E-03      2.42200E+01      9.93400E-01      2.75000E-03
      2.31190E+01      9.89310E-01      3.19000E-03      2.42250E+01      9.91480E-01      3.05000E-03
      2.33600E+01      9.91270E-01      3.56000E-03      2.42270E+01      9.95460E-01      3.16000E-03
      2.45660E+01      9.99690E-01      3.31000E-03      2.13760E+01      1.01260E+00      3.08000E-03
      2.41880E+01      9.99880E-01      3.24000E-03      2.11830E+01      1.01150E+00      3.20000E-03
      2.28550E+01      9.87260E-01      3.40000E-03      1.83380E+01      1.01580E+00      3.66000E-03
      2.43730E+01      9.85950E-01      3.10000E-03      1.92760E+01      1.00170E+00      3.52000E-03
      2.47160E+01      9.91570E-01      2.41000E-03      2.15420E+01      1.00700E+00      3.25000E-03
      2.47870E+01      1.00000E+00      2.54000E-03      2.01770E+01      1.00810E+00      2.96000E-03
      1.67470E+01      9.92460E-01      2.39000E-03      1.85300E+01      9.99450E-01      3.02000E-03
      1.55960E+01      9.93210E-01      2.95000E-03      1.93120E+01      1.00900E+00      3.42000E-03
      1.71820E+01      1.00170E+00      2.70000E-03      2.18620E+01      1.00870E+00      3.12000E-03
      1.85660E+01      1.00500E+00      2.94000E-03      1.83290E+01      1.00360E+00      2.63000E-03
      2.32730E+01      9.85370E-01      2.25000E-03      1.92220E+01      9.83000E-01      3.52000E-03
      2.32790E+01      9.86050E-01      2.02000E-03      1.91580E+01      9.77150E-01      3.75000E-03
      2.24850E+01      9.94450E-01      2.70000E-03      1.97540E+01      9.81780E-01      3.10000E-03
      2.32170E+01      9.98780E-01      2.78000E-03      2.02680E+01      9.96760E-01      4.29000E-03
      2.39040E+01      9.89750E-01      2.50000E-03      1.98750E+01      9.86440E-01      3.06000E-03
      2.41060E+01      9.88530E-01      2.72000E-03      1.97890E+01      9.87330E-01      3.40000E-03
      2.22060E+01      1.00660E+00      3.07000E-03      2.15530E+01      1.00190E+00      3.04000E-03
      2.22220E+01      1.01240E+00      3.15000E-03      2.14600E+01      9.92820E-01      3.70000E-03
1      intermediate calculation results
0      KENOV.a Validation 1-15-91. Low Enriched Experiments
      Student t = 1.680E+00 for 46 dof's and P = .950 .

      subroutine fit
      xbar = 2.1598E+01, standard deviation in xbar = 2.3617E+00
      ybar = 9.9628E-01, standard deviation in ybar = 9.9289E-03
      sigmaxx = 2.6215E+02, sigmayy = 4.6334E-03, sigmaxy = -1.6518E-01
      root mean square error of fit = 9.9229E-03
      r squared of fit = 2.2464E-02
      standard variance of the fit = 9.84642E-05
      estimated sample variance = 9.62236E-06
      estimated total variance = 1.08087E-04
      estimated total standard error = 1.03965E-02

      Student t = 1.679E+00 for 47 dof's and P = .950 .
      Student t = 3.090E+00 for 150 dof's and P = .999 .

      estimate of lower 95.000 percent confidence
      bound on 99.900 percent proportion of the
      population for the data treated as a single group
      osc = 9.5685E-01

      subroutine fnorm
      bin tallies 11.0 12.0 3.0 10.0 12.0
      WARNING *** the test for normal may be unreliable
      chi = 5.9583 compared to 9.49. The data tests normal
      Student t = 3.690E+00 for 150 dof's and P = .999 .
      Chi**2 = 2.920E+01 for 46 dof's and P = .025 .

      subroutine conf
      g = .3978, h = .2442, rho = -.5372

      subroutine dcalc
      gamma = .050, A = .6139, n = 48, rho = .53718
      d = 1.00, ans = .3439, nof = 1089
      d = 10.00, ans = 1.0000, nof = 2145

      d1      d      d2      a1      ans      a2
      -----
      1.0000  10.0000  10.0000  .3439  .9500  1.0000
      1.0000  5.5000  5.5000  .3439  .9500  .9985
      3.2500  3.2500  5.5000  .9469  .9500  .9985
      3.2500  4.3750  4.3750  .9469  .9500  .9899

```

```

3.2500 3.8125 3.8125 .9469 .9500 .9761
3.2500 3.5313 3.5313 .9469 .9500 .9641
3.2500 3.3906 3.3906 .9469 .9500 .9562
3.2500 3.3203 3.3203 .9469 .9500 .9518
3.2852 3.2852 3.3203 .9494 .9500 .9518
3.2852 3.3027 3.3027 .9494 .9500 .9506
Jumped out, n = 10

```

```

subroutine conf
Selected D value = 3.294E+00

```

```

k = cstar + zsubp * sqrt( (n-2) / chisq )
k = 8.0436E-01 + 3.0900E+00 * sqrt( 46 / 2.9200E+01 )
k = 4.6827E+00

```

```

ksigma = k * sigma
ksigma = 4.6827E+00 * 1.0396E-02
ksigma = 4.8684E-02

```

```
1 output from statistical treatment
```

```
KENOV.a Validation 1-15-91. Low Enriched Experiments
```

```
0 linear least squares fit to data
```

```

y = b0 + x * b1
y = 1.0099E+00 + x * -6.3011E-04

```

```
(T for H0: b1 = 0.) = -1.0281E+00
```

```
0 95.0 percent confidence of the fit (not plotted)
```

```

ys = b0 - cstar * sigma + x * b1
ys = 1.0099E+00 - 8.0436E-01 * 1.0396E-02 + x * -6.3011E-04
ys = 1.0099E+00 - 8.3625E-03 + x * -6.3011E-04
ys = 1.0015E+00 + x * -6.3011E-04

```

```
0 one-sided, uniform-width, lower 95.0 percent confidence band for a single future calculation
```

```

ys = b0 - st * sigma * sfc + x * b1
ys = 1.0099E+00 - 1.6801E+00 * 1.0396E-02 * 1.0762E+00 + x * -6.3011E-04
ys = 1.0099E+00 - 1.8798E-02 + x * -6.3011E-04
ys = 9.9109E-01 + x * -6.3011E-04

```

```
0 lower tolerance bound for
```

```
95.0 percent confidence on 99.9 percent of the population
```

```

yc = b0 - ksigma + x * b1
yc = 1.0099E+00 - 4.8684E-02 + x * -6.3011E-04
yc = 9.6120E-01 + x * -6.3011E-04

```

```
0 margin between the confidence band for a single
```

```
future calculation and the lower tolerance bound 2.9885E-02
```

```
0 95.0 percent confidence on a single future calculation (not plotted)
```

```

yf = b0 - w3 + x * b1
w3 = st * sigma * sqrt(1 + 1/ n + (x - xb)**2/ sxx )
w3 = 1.6801E+00 * .01040 * sqrt(1 + 1/ 48 + (x - 2.1598E+01)**2/ 2.6215E+02)

```

```

minimum value of closed band = 1.5596E+01
maximum value of closed band = 2.4787E+01
minimum value of y = 9.7715E-01
maximum value of y = 1.0158E+00

```

```
0 input to statistical treatment
```

```
0 KENOV.a Validation 1-15-91. High Enriched Experiments
```

```
0 proportion of the population = .999
```

```
confidence of fit = .950
```

```
confidence on proportion = .950
```

```
number of observations = 11
```

```
minimum value of closed band = .00
```

```
maximum value of closed band = .00
```

```
estimated sample deviation = 3.52500E-03
```

```
0 independent dependent deviation
```

```
variable - x variable - y in y
```

```

2.45720E+01 1.01410E+00 3.91000E-03
8.52570E+00 1.01140E+00 3.09000E-03
2.49970E+01 1.00160E+00 2.24000E-03
1.17440E+01 1.01400E+00 3.07000E-03
9.43170E+00 9.95610E-01 3.19000E-03
2.15730E+01 1.00800E+00 3.88000E-03
7.71090E+00 1.01330E+00 3.05000E-03
2.42580E+01 9.73110E-01 3.41000E-03
2.42580E+01 9.88310E-01 3.60000E-03
2.25070E+01 1.00270E+00 4.36000E-03
2.21210E+01 1.02540E+00 4.39000E-03

```

```
1 intermediate calculational results
```

```
0 KENOV.a Validation 1-15-91. High Enriched Experiments
```

```
Student t = 1.833E+00 for 9 dof's and P = .950 .
```

```
subroutine fit
```

```

xbar = 1.8336E+01, standard deviation in xbar = 7.2627E+00
ybar = 1.0043E+00, standard deviation in ybar = 1.4472E-02

```

```

sigmaxx = 5.2747E+02, sigmayy = 2.0943E-03, sigmaxy = -3.0295E-01
root mean square error of fit = 1.4607E-02
r squared of fit = 8.3080E-02
standard variance of the fit = 2.13367E-04
estimated sample variance = 1.24256E-05
estimated total variance = 2.25793E-04
estimated total standard error = 1.50264E-02

```

```

Student t = 1.812E+00 for 10 dof's and P = .950 .
Student t = 3.090E+00 for 150 dof's and P = .999 .

```

```

estimate of lower 95.000 percent confidence
bound on 99.900 percent proportion of the
population for the data treated as a single group
osc = 9.2524E-01

```

```

subroutine fnorm
bin tallies 2.0 1.0 2.0 5.0 1.0
WARNING *** the test for normal may be unreliable
chi = 4.9091 compared to 9.49. The data tests normal
Student t = 3.090E+00 for 150 dof's and P = .999 .
Chi**2 = 2.700E+00 for 9 dof's and P = .025 .

```

```

subroutine conf
g = .5522, h = .4184, rho = -.1873

```

```

subroutine dcalc
gamma = .050, A = 1.3200, n = 11, rho = .18727
d = 1.00, ans = .5282, nof = 1063
d = 10.00, ans = 1.0009, nof = 1217

```

d1	d	d2	a1	ans	n2
1.0000	10.0000	10.0000	.5282	.9500	1.0009
1.0000	5.5000	5.5000	.5282	.9500	.9993
1.0000	3.2500	3.2500	.5282	.9500	.9883
2.1250	2.1250	3.2500	.9210	.9500	.9883
2.1250	2.6875	2.6875	.9210	.9500	.9699
2.1250	2.4063	2.4063	.9210	.9500	.9513
2.2656	2.2656	2.4063	.9380	.9500	.9513
2.3359	2.3359	2.4063	.9450	.9500	.9513
2.3711	2.3711	2.4063	.9482	.9500	.9513

Jumped out, n = 9

```

subroutine conf
Selected D value = 2.389E+00

```

```

k = cstar + zsubp * sqrt( (n-2) / chisq )
k = 1.3191E+00 + 3.0900E+00 * sqrt( 9 / 2.7000E+00 )
k = 6.9606E+00

```

```

ksigma = k * sigma
ksigma = 6.9606E+00 * 1.5026E-02
ksigma = 1.0459E-01

```

```
1 output from statistical treatment
```

```
KEMOV.a Validation 1-15-91. High Enriched Experiments
```

```
0 linear least squares fit to data
```

```

y = b0 + x * b1
y = 1.0149E+00 + x * -5.7434E-04

```

```
(T for H0: b1 = 0.) = -9.0303E-01
```

```
0 95.0 percent confidence of the fit (not plotted)
```

```

ys = b0 - cstar * sigma + x * b1
ys = 1.0149E+00 - 1.3191E+00 * 1.5026E-02 + x * -5.7434E-04
ys = 1.0149E+00 - 1.982E-02 + x * -5.7434E-04
ys = 9.9503E-01 + x * -5.7434E-04

```

```
0 one-sided, uniform-width, lower 95.0 percent confidence band for a single future calculation
```

```

ys = b0 - st * sigma * sfc + x * b1
ys = 1.0149E+00 - 1.8330E+00 * 1.5026E-02 * 1.1423E+00 + x * -5.7434E-04
ys = 1.0149E+00 - 3.1464E-02 + x * -5.7434E-04
ys = 9.8339E-01 + x * -5.7434E-04

```

```
0 lower tolerance bound for
```

```
95.0 percent confidence on 99.9 percent of the population
```

```

yc = b0 - ksigma + x * b1
yc = 1.0149E+00 - 1.0459E-01 + x * -5.7434E-04
yc = 9.1026E-01 + x * -5.7434E-04

```

```
0 margin between the confidence band for a single
```

```
future calculation and the lower tolerance bound 7.3129E-02
```

```
0 95.0 percent confidence on a single future calculation (not plotted)
```

```

yf = b0 - w3 + x * b1
w3 = st * sigma * sqrt(1 + 1/n + (x - xb)**2/sxx)
w3 = 1.8330E+00 * 1.01503 * sqrt(1 + 1/11 + (x - 1.8336E+01)**2/ 5.2747E+02)

```

```

minimum value of closed band = 7.7109E+00
maximum value of closed band = 2.4997E+01
minimum value of y = 9.7311E-01
maximum value of y = 1.0254E+00

```

```

0      input to statistical treatment
0 KENOV.a Validation 1-15-91. High and Low Enriched Experiments

```

```

0 proportion of the population = .999
confidence of fit = .950
confidence on proportion = .950
number of observations = 59
minimum value of closed band = .00
maximum value of closed band = .00
estimated sample deviation = 3.18512E-03

```

independent variable - x	dependent variable - y	deviation in y	independent variable - x	dependent variable - y	deviation in y
2.11690E+01	9.89440E-01	3.96000E-03	2.13760E+01	1.01260E+00	3.08000E-03
2.31190E+01	9.89310E-01	3.19000E-03	2.11830E+01	1.01150E+00	3.20000E-03
2.13940E+01	9.80550E-01	3.15000E-03	1.83380E+01	1.01580E+00	3.66000E-03
2.40350E+01	9.79250E-01	2.53000E-03	1.92760E+01	1.00170E+00	3.52000E-03
2.31190E+01	9.89310E-01	3.19000E-03	2.15420E+01	1.00700E+00	3.25000E-03
2.33600E+01	9.91270E-01	3.56000E-03	2.01770E+01	1.00810E+00	2.96000E-03
2.45660E+01	9.99690E-01	3.31000E-03	1.85300E+01	9.99450E-01	3.02000E-03
2.41880E+01	9.99880E-01	3.24000E-03	1.93120E+01	1.00900E+00	3.42000E-03
2.28550E+01	9.87260E-01	3.40000E-03	2.18620E+01	1.00870E+00	3.12000E-03
2.43730E+01	9.85950E-01	3.10000E-03	1.83290E+01	1.00360E+00	2.63000E-03
2.47160E+01	9.91570E-01	2.41000E-03	1.92220E+01	9.83000E-01	3.52000E-03
2.47870E+01	1.00000E+00	2.54000E-03	1.91580E+01	9.77150E-01	3.75000E-03
1.67470E+01	9.92460E-01	2.39000E-03	1.97540E+01	9.81780E-01	3.10000E-03
1.55960E+01	9.93210E-01	2.95000E-03	2.02680E+01	9.96760E-01	4.29000E-03
1.71820E+01	1.00170E+00	2.70000E-03	1.98750E+01	9.86440E-01	3.06000E-03
1.85660E+01	1.00500E+00	2.94000E-03	1.97890E+01	9.87330E-01	3.40000E-03
2.32730E+01	9.85370E-01	2.25000E-03	2.15530E+01	1.00190E+00	3.04000E-03
2.32790E+01	9.86050E-01	2.02000E-03	2.14600E+01	9.92820E-01	3.70000E-03
2.24850E+01	9.94450E-01	2.70000E-03	2.45720E+01	1.01410E+00	3.91000E-03
2.32170E+01	9.98780E-01	2.78000E-03	8.52570E+00	1.01140E+00	3.09000E-03
2.39040E+01	9.89750E-01	2.50000E-03	2.49970E+01	1.00160E+00	2.24000E-03
2.41060E+01	9.88530E-01	2.72000E-03	1.17440E+01	1.01400E+00	3.07000E-03
2.22060E+01	1.00660E+00	3.07000E-03	9.43170E+00	9.95610E-01	3.19000E-03
2.22220E+01	1.01240E+00	3.15000E-03	2.15730E+01	1.00800E+00	3.88000E-03
2.17610E+01	1.00720E+00	2.82000E-03	7.71090E+00	1.01330E+00	3.05000E-03
2.35220E+01	1.00700E+00	3.24000E-03	2.42580E+01	9.73110E-01	3.41000E-03
2.32730E+01	1.00430E+00	2.92000E-03	2.42580E+01	9.88310E-01	3.60000E-03
2.42200E+01	9.93400E-01	2.75000E-03	2.25070E+01	1.00270E+00	4.36000E-03
2.42250E+01	9.91480E-01	3.05000E-03	2.21210E+01	1.02540E+00	4.39000E-03
2.42270E+01	9.95460E-01	3.16000E-03			

```

1      intermediate calculational results
0 KENOV.a Validation 1-15-91. High and Low Enriched Experiments
Student t = 1.673E+00 for 57 dof's and P = .950 .

```

```

subroutine fit
xbar = 2.0990E+01, standard deviation in xbar = 3.9059E+00
ybar = 9.9778E-01, standard deviation in ybar = 1.1224E-02
sigmaxx = 8.8483E+02, sigmayy = 7.3069E-03, sigmaxy = -7.0295E-01
root mean square error of fit = 1.0881E-02
r squared of fit = 7.6429E-02
standard variance of the fit = 1.18394E-04
estimated sample variance = 1.01450E-05
estimated total variance = 1.28539E-04
estimated total standard error = 1.13375E-02

```

```

Student t = 1.672E+00 for 58 dof's and P = .950 .
Student t = 3.090E+00 for 150 dof's and P = .999 .

```

```

estimate of lower 95.000 percent confidence
bound on 99.900 percent proportion of the
population for the data treated as a single group
osc = 9.5455E-01

```

```

subroutine fnorm
bin tallies 13.0 13.0 8.0 12.0 13.0
chi = 1.5932 compared to 9.49. The data tests normal

```

```

Student t = 3.090E+00 for 150 dof's and P = .999 .
Chi**2 = 3.814E+01 for 57 dof's and P = .025 .

```

```

subroutine conf
g = .4650, h = .1873, rho = -.4958

```

```

suroutine dcalc
gamma = .050 , A = .4029, n = 59, rho = .49577

```

d = 1.00 , ans = .2322, nof = 1089
d = 10.00 , ans = .9998, nof = 2145

d1	d	d2	a1	ans	a2
1.0000	10.0000	10.0000	.2322	.9500	.9998
1.0000	5.5000	5.5000	.2322	.9500	.9693
3.2500	3.2500	5.5000	.8037	.9500	.9693
4.3750	4.3750	5.5000	.9167	.9500	.9693
4.9375	4.9375	5.5000	.9485	.9500	.9693
4.9375	5.2188	5.2188	.9485	.9500	.9601
4.9375	5.0781	5.0781	.9485	.9500	.9546
4.9375	5.0078	5.0078	.9485	.9500	.9517
Jumped out, n = 8					

subroutine conf
Selected D value = 4.973E+00

k = cstar + zsubp * sqrt((n-2) / chisq)
k = 9.3159E-01 + 3.0900E+00 * sqrt(57 / 3.8140E+01)
k = 4.7091E+00

ksigma = k * sigma
ksigma = 4.7091E+00 * 1.1338E-02
ksigma = 5.3389E-02

1 output from statistical treatment

KENOV.a Validation 1-15-91. High and Low Enriched Experiments

0 linear least squares fit to data

y = b0 + x * b1
y = 1.0145E+00 + x * -7.9445E-04

(T for H0: b1 = 0.) = -2.1719E+00

0 95.0 percent confidence of the fit (not plotted)

ys = b0 - cstar * sigma + x * b1
ys = 1.0145E+00 - 9.3159E-01 * 1.1338E-02 + x * -7.9445E-04
ys = 1.0145E+00 - 1.0562E-02 + x * -7.9445E-04
ys = 1.0039E+00 + x * -7.9445E-04

0 one-sided, uniform-width, lower 95.0 percent confidence band for a single future calculation

ys = b0 - st * sigma * sfc + x * b1
ys = 1.0145E+00 - 1.6730E+00 * 1.1338E-02 * 1.1028E+00 + x * -7.9445E-04
ys = 1.0145E+00 - 2.0917E-02 + x * -7.9445E-04
ys = 9.9353E-01 + x * -7.9445E-04

0 lower tolerance bound for

95.0 percent confidence on 99.9 percent of the population

0 yc = b0 - ksigma + x * b1

yc = 1.0145E+00 - 5.3389E-02 + x * -7.9445E-04
yc = 9.6106E-01 + x * -7.9445E-04

0 margin between the confidence band for a single future calculation and the lower tolerance bound 3.2472E-02

0 95.0 percent confidence on a single future calculation (not plotted)

yf = b0 - w3 + x * b1
w3 = st * sigma * sqrt(1 + 1/n + (x - xb)**2/sxx)
w3 = 1.6730E+00 * .01134 * sqrt(1 + 1/59 + (x - 2.0990E+01)**2/ 8.8483E+02)

minimum value of closed band = 7.7109E+00

maximum value of closed band = 2.4997E+01

minimum value of y = 9.7311E-01

maximum value of y = 1.0254E+00

INTERNAL DISTRIBUTION

1. T. A. Angelelli	36. J. P. Little, Jr.
2. D. Baltimore	37. S. K. Martin
3. E. J. Barber	38. D. S. Milewski
4. S. M. Bowman	39. R. L. Newvahner
5. W. R. Brock	40. L. F. Norris
6. L. D. Charles	41. M. G. Otey
7. W. K. Crowley	42-43. C. V. Parks
8-10. D. M. D'Aquila	44. A. J. Saraceno
11. J. C. Dean	45-46. C. H. Shappert
12-13. H. R. Dyer	47. J. N. Sumner
14. D. A. Dyslin	48. C. A. Sweet
15. D. L. English	49. R. G. Taylor
16. P. A. Haas	50. D. A. Walker
17. H. F. Hartman	51. B. G. Warriner
18-20. T. W. Hines	52. R. M. Westfall
21. J. A. Hoffmeister	53. G. E. Whitesides
22. J. C. Ingram III	54. D. W. Wilson
23-32. W. C. Jordan	55-56. Laboratory Records Dept.
33. R. A. Just	57. Laboratory Records, ORNL-RC
34. M. R. Lambert	58. ORNL Y-12 Research Library
35. P. D. Lassiter	Document Reference Section
	59. Central Research Library
	60. ORNL Patent Section

EXTERNAL DISTRIBUTION

61. Office of the Assistant Manager for Energy Research and Development, U.S. Department of Energy Field Office, Oak Ridge, (DOE-OR), P.O. Box 2001, Oak Ridge, TN 37831
- 62-63. Office of Scientific and Technical Information, U.S. Department of Energy, P.O. Box 62, Oak Ridge, TN 37831

END

DATE
FILMED
5/05/93