FLOWTRAN-TF v1.2 Source Code (U)

**S. E. Aleman, R. E. Cooper, G. P. Flach, L. L. Hamm, S. Lee,
F. G. Smith III**

Publication Date: February, 1993

MASTER

**Westinghouse Savannah River Company
Savannah River Site
Aiken, SC 29808**

TASK NUMBER: 89-021-1
DOCUMENT TITLE: FLOWTRAN-TF v1.2 Source Code (U)
DOCUMENT NUMBER: WSRC-TR-93-086
REVISION NUMBER: 0

APPROVALS

2/18/93

G. P. FLACH, TASK LEADER DATE

2/24/93

D. A. CROWLEY, NES CODE DEVELOPMENT GROUP MANAGER DATE

2/24/93

A. J. GARRETT, NES MANAGER DATE

Acknowledgements

The FLOWTRAN-TF code development effort was initiated in early 1989. Several members of the Code Development Group have contributed to FLOWTRAN-TF development as summarized alphabetically below:

Contributor	Principal Contributions
Sebastian Aleman	Axial wall drag, neutronic power distribution, splines, code architecture, documentation, coding, graphics, testing
Roger Cooper	Coding, graphics
Greg Flach	Program leadership, interfacial drag, axial wall drag, phase transition logic, fluid finite-differencing and solution methods, equations of state, documentation, coding, testing, benchmarking
Larry Hamm	Program concept, initiation and leadership, all aspects of physical model development and computational implementation, interfacial heat and mass transfer, code architecture, coding, testing, benchmarking
Andrea Kielpinski	Interfacial heat and mass transfer coefficients, flow regime map, documentation
Larry Koffman	Documentation
Si Young Lee	Channel inlet void distribution, CCFL correlation, inter-subchannel mixing, interfacial heat and mass transfer coefficients, rib void model, equations of state, documentation, coding, testing, benchmarking
Andy Shadday	Azimuthal wall drag, documentation, testing
Frank Smith	Solid heat conduction, neutronic power distribution, wall heat transfer, interfacial heat and mass transfer, fluid finite differencing and solution methods, code architecture and I/O, documentation, coding, testing, benchmarking

The developers are grateful to the many technical reviewers of FLOWTRAN-TF. These include Ken Moore, Garry Gose, Ken Katsma and M. Paulsen of Computer Simulation & Analysis, Inc. and Steve Hensel and Jeff Jerrell of WSRC. The helpful suggestions of the DOE Independent Review Panel (DIRP) are also appreciated.

The developers also appreciate the support of the DOE, former WSRC Nuclear Engineering Section manager Ken Huffman and present manager Al Garrett, and former Code Development Group managers Larry Hamm and Bill Horton and current manager Dave Crowley.

This page intentionally left blank

Table of Contents

CODE ARCHITECTURE.....	1
SOURCE CODE LISTING.....	7
TFMAIN.....	7
ACCCHK.....	9
AIR.....	13
AVEC1.....	13
AVECB.....	18
AVECT.....	20
AVECX.....	23
AVECZ.....	27
AXIALP.....	32
BOUND.....	35
COFCN.....	38
CDENS.....	39
CHEN.....	40
CHF.....	44
CHLSKI.....	46
CHP.....	47
CIA.....	48
CLEAR.....	49
CLEAR1.....	49
CONDLQ.....	49
CONDT.....	50
CONLAW.....	51
CONST.....	53
CPGS.....	59
CPLQ.....	60
CRIT.....	61
CYLNDR.....	68
DMPPLT.....	70
DONORB.....	75
DONORM.....	78
DONORT.....	82
EOSSLD.....	85
EXPL1D.....	87
EXPL2D.....	91
EXPLCT.....	98
EXPLPL.....	103
EXPLTB.....	108
FILMB.....	112
FWALLX.....	115
FWALLZ.....	117
GAJOR.....	119
GAMMAA.....	121
GAMMAI.....	122
GEOFLD.....	126
GEOSLD.....	136
HCONV.....	139
HFIA.....	141

HFIB	142
HFIS	144
HFLUID	145
HFSAT	145
HGIA	146
HGIB	147
HGIS	148
HSSAT	150
HSTEAM	150
INBOND	151
INDPWR	154
INITFD	163
INITL	169
INITSD	173
INNER	174
INOPTS	182
INPOWER	189
INPUT	193
INSPLN	194
INTARA	197
JACOB	201
JACOB	207
JACOB	213
MIKIC	219
MOVE	225
NEWTON	225
PDIST	229
PNORM	235
POINT	237
POWER	245
PROPCK	247
PRTFLD	251
PRTPOW	260
PRTSLD	263
PRTSRN	265
PSAT	269
QWALL	269
RADSH	276
READIN	279
RESET	281
RESTR	283
RING	288
ROFSAT	292
RSTEAM	293
SCMSLB	293
SETSLD	294
SOLID	297
SPLINE	300
SRLHTC	301
STATE	303
STORE	306
SURTEN	310
TIMSTP	310
TRANS	314

TRIDAG	322
TSAT	324
TURBX	324
UPDATP	328
UPDATV	347
VISGS	350
VISLQ	351
VRIB	351
YVALU	352
KNOBS.INC	353
PARAMS.INC	353
POINTS.INC	353

This page intentionally left blank

Code Architecture

Figure 1 illustrates the architecture of FLOWTRAN-TF v1.2.

Figure 1a

Figure 1d

Source Code Listing

The FORTRAN coding for FLOWTRAN-TF v1.2 is listed below. The listing starts with the main program followed by subroutines in alphabetical order. Three INCLUDE files complete the listing.

TFMAIN

```

      program tfmain
c
c      *****
c      *
c      *   PROGRAM tfmain
c      *
c      *   MAIN DRIVER FOR FLOWTRAN-TF CODE
c      *
c      *****
      implicit real (a-h,o-z), integer(i-n)
      logical iquit
c
      parameter (icmax=5, ipmax=20)
c
      dimension critr(icmax,ipmax), lcrit(3,icmax,ipmax),
&          tcrit(icmax,ipmax)
      common /iounit/ ninp, nout, ndmp, ntmp, nrsti, nrsto
      common /pltfil/ mapnam
      common /pltrec/ nrec
c
      include 'params.inc'
      include 'points.inc'
c
      character filnam * 16,
&          mapnam * 16,
&          buf1 * 9,
&          buf2 * 8
c
      data iquit /.false./
c
      SET I/O/UNITS AND MAXIMUM ARRAY SIZES
c
      ntmp = 5
      nout = 11
      ninp = 7
      ndmp = 8
      nrsti = 9
      nrsto = 10
c
      maxa = 200000
      maxia = 10000
c
      OPEN FILE AT UNIT ninp TO HOLD MODIFIED INPUT DATA,
      READ INPUT DATA FROM UNIT ntmp AND CREATE INPUT FILE
c
      open (unit=ninp, status='scratch')
      call readin
      close (unit=ntmp)
c
      WRITE CODE CONFIGURATION MANAGEMENT HEADER
c
      call scmslb (nout)
      call scmslb (20)

```

```

C
C   READ INPUT FILES
C
  call input (icmax,ipmax)
  close (unit=ninp)
C
C   SET UP PLOTTING DUMP FILE
C
  if (dtpdmp.le.runsec) then
    nrecl = max(11*nzt+10,nzp2*nxmax+17,nz*na+17,11*nzb+10)
    nrecl = (iword**3)*nrecl
    if(iword .eq. 1) then
      call date(buf1)
      call time(buf2)
      filnam = 'plt_//buf1(1:2)//buf1(4:6)//'.',
&             buf2(1:2)//buf2(4:5)//buf2(7:8)
      mapnam = 'map_//filnam(5:16)
    elseif(iword .eq. 2) then
      call date(buf1)
      call clock(buf2)
      filnam = 'plt_//buf1(1:2)//buf1(4:5)//'_',
&             buf2(1:2)//buf2(4:5)//buf2(7:8)
      mapnam = 'map_//filnam(4:14)
    endif
    open (unit=ndmp, file=filnam, access='direct',
&        recl=nrecl, form='unformatted', status='new')
    nrec = 1
  end if
C
C   INITIALIZE POWER ITERATION VARIABLES.
C
  ip = 0
  call clear (critr,ncrit*maxpi)
C
C   POWER ITERATIONS
C
100 continue
  iredo = 0
  ip = ip + 1
C
C   INITIALIZE VARIABLES
C
  call init1
C
C   PERFORM TRANSIENT CALCULATION
C
  call trans (critr(1,ip),tcrit(1,ip),lcrit(1,1,ip),iredo)
C
C   PERFORM INTERPOLATION TO OBTAIN A NEW ESTIMATE
C   FOR THE PRE-INCIDENT ASSEMBLY POWER
C
  call power (asypwr,tolpow,critr,tcrit,lcrit,ia(lichkc),
&            iredo,ncrit,maxpi,icmax,ipmax,ip,iquit,nout)
C
  if (iquit) goto 200
  if (iredo.eq.1) ip = ip - 1
  nrec = 1
  goto 100
C
C   CLOSE DATA FILES
C
200 close (unit=ndmp)
  close (unit=nout)
  close (unit=nrsti)

```

```

      close (unit=nrsto)
c
      stop
      end

```

ACCCHK

```

      subroutine accchk(pt ,alpt ,tgt ,tft ,xat ,rogt ,roft ,hgt ,hft ,
&      p ,alp ,tg ,tf ,xa ,rog ,rof ,hg ,hf ,
&      pb ,alpb ,tgb ,tgb ,xab ,rogb ,rofb ,hgb ,hfb ,
&      ptn ,alptn ,tgt ,tft ,xatn ,rogt ,roft ,hgt ,hft ,
&      pn ,alpn ,tgn ,tfn ,xan ,rogn ,rofn ,hgn ,hfn ,
&      pbn ,alpb ,tgb ,tgb ,xab ,rogb ,rofb ,hgb ,hfb ,
&      volt ,volc ,volb ,tsurf ,tsrfn ,
&      nsurf ,na ,nz ,nzt ,nzp1 ,nzp2 ,nxmax ,nchn ,nx ,nzb ,
&      ierr ,istdy ,tol ,tolss ,nstdy ,delt ,tsec ,
&      dif ,difp ,difalp ,diftg ,diftf ,difxa ,difts ,delhm ,
&      steady)
c
c *****
c
c DESCRIPTION:
c Subroutine accchk is an accuracy checking subroutine. When any of
c the physical variables P, alpha, Tg, Tf, or Xa change by more than
c a prescribed amount compared to a reference quantity, accchk
c returns ierr=3. This causes the time step to be repeated with a
c smaller step size. The assumption is that if any of the variables
c change by a large amount then the time truncation error is probably
c large as well.
c
c GLOSSARY: I=input, O=output
c The symbol "_" after a variable denotes either a blank or an "n".
c * * * A trailing "n" means "old" time value * * *
c * * * No trailing "n" means "new" time value * * *
c
c ---General---
c O ierr = 'error' indicator (ierr=3 denotes insufficient accuracy)
c O dif = maximum of difp, difalp, diftg, diftf, difxa over
c the entire grid
c
c ---Top Section---
c I nzt = number of cells in the top section
c I pt_ (nzt) = top section pressure
c I alpt_ (nzt) = top section alpha
c I tgt_ (nzt) = top section gas temp.
c I tft_ (nzt) = top section liquid temp.
c I xat_ (nzt) = top section air mass fract.
c
c ---Middle Section---
c I nz = number of axial cells in the middle section
c I nzp1 = nz + 1
c I nzp2 = nz + 2
c I nxmax = maximum number of x-direction cells in middle section
c I nchn = number of channels in middle section
c I nx(nchn) = number of x-direction cells in a channel
c I p_ (nzp2,nxmax,nchn) = middle section pressure
c I alp_ (nzp2,nxmax,nchn) = middle section alpha
c I tg_ (nzp2,nxmax,nchn) = middle section gas temp.
c I tf_ (nzp2,nxmax,nchn) = middle section liquid temp.
c I xa_ (nzp2,nxmax,nchn) = middle section air mass fract.
c
c ---Bottom Section---
c I nzb = number of cells in the bottom section
c I pb_ (nzb) = bottom section pressure
c I alpb_ (nzb) = bottom section alpha
c I tgb_ (nzb) = bottom section gas temp.

```

```

c I tfb_ (nzb) = bottom section liquid temp.
c I xab_ (nzb) = bottom section air mass fract.
c *****
c
c      implicit real (a-h,o-z), integer (i-n)
c      logical steady
c
c      parameter (zero=0.0, one=1.0, hundrd=100.0, ctok=273.15)
c
c      dimension nx(nchn), dhxdt(10)
c
c      TOP SECTION ARRAYS
c
c      dimension pt (nzt), ptn (nzt), volt(nzt),
&      alpt(nzt), alptn(nzt),
&      tgt (nzt), tgtn (nzt),
&      tft (nzt), tftn (nzt),
&      xat (nzt), xatn (nzt),
&      rogt(nzt), rogtn(nzt),
&      roft(nzt), roftn(nzt),
&      hgt (nzt), hgtn (nzt),
&      hft (nzt), hftn (nzt)
c
c      MIDDLE SECTION ARRAYS
c
c      dimension p (nzp2,nxmax,nchn), pn (nzp2,nxmax,nchn),
&      alp(nzp2,nxmax,nchn), alpn(nzp2,nxmax,nchn),
&      tg (nzp2,nxmax,nchn), tgn (nzp2,nxmax,nchn),
&      tf (nzp2,nxmax,nchn), tfn (nzp2,nxmax,nchn),
&      xa (nzp2,nxmax,nchn), xan (nzp2,nxmax,nchn),
&      rog(nzp2,nxmax,nchn), rogn(nzp2,nxmax,nchn),
&      rof(nzp2,nxmax,nchn), rofn(nzp2,nxmax,nchn),
&      hg (nzp2,nxmax,nchn), hgn (nzp2,nxmax,nchn),
&      hf (nzp2,nxmax,nchn), hfn (nzp2,nxmax,nchn),
&      volc(nzp2,nxmax,nchn)
c
c      BOTTOM SECTION ARRAYS
c
c      dimension pb (nzb), pbn (nzb), volb(nzb),
&      alpb(nzb), alpbn(nzb),
&      tgb (nzb), tgbn (nzb),
&      tfb (nzb), tfbn (nzb),
&      xab (nzb), xabn (nzb),
&      rogb(nzb), rogbn(nzb),
&      rofb(nzb), rofbn(nzb),
&      hgb (nzb), hgbn (nzb),
&      hfb (nzb), hfbn (nzb)
c
c      SURFACE TEMPERATURES
c
c      dimension tsurf(nsurf,na,nz), tsrfrn(nsurf,na,nz)
c
c      data allow /0.001/, alhigh /0.999/
c      data ipass/0/, iset/5/
c
c      INITIALIZE
c
c      ierr = 0
c      dif = zero
c      difp = zero
c      difalp = zero
c      diftg = zero
c      diftf = zero
c      difxa = zero

```

```

difts = zero
sumv = zero
sumdh = zero
c
c COMPUTE MAXIMUM CHANGE IN TOP SECTION FLUID VARIABLES
c
do 100 jc=1,nzt
  difp = max(difp ,abs(( pt(jc) - ptn(jc))/ptn(jc)))
  difalp = max(difalp,abs (alpt(jc) - alptn(jc)))
  if (alpt(jc).lt.alhigh .and. alptn(jc).lt.alhigh) then
    diftf = max(diftf ,abs((tft(jc) - tftn(jc))/tftn(jc)))
  end if
  if (alpt(jc).gt.allow .and. alptn(jc).gt.allow) then
    diftg = max(diftg ,abs((tgt(jc) - tgtn(jc))/tgtn(jc)))
    difxa = max(difxa ,abs (xat(jc) - xatn(jc)))
  end if

  arg = alpt(jc)*rogt(jc)
  arf = (one - alpt(jc))*roft(jc)
  hmix = (arg*hgt(jc) + arf*hft(jc))/(arg + arf)

  argn = alptn(jc)*rogtn(jc)
  arfn = (one - alptn(jc))*roftn(jc)
  hmixn = (argn*hgt(jc) + arfn*hftn(jc))/(argn + arfn)

  vdelh = volt(jc)*(hmix - hmixn)
  sumdh = sumdh + vdelh*vdelh
  sumv = sumv + volt(jc)
100 continue
c
c COMPUTE MAXIMUM CHANGE IN MIDDLE SECTION FLUID VARIABLES
c
do 220 k=1,nchn
  do 210 i=1,nx(k)
    do 200 jc=2,nzpl
      difp = max(difp ,abs((p(jc,i,k) - pn(jc,i,k))/
& pn(jc,i,k)))
      difalp = max(difalp,abs (alp(jc,i,k) - alpn(jc,i,k)))
      if (alp(jc,i,k).lt.alhigh .and. alpn(jc,i,k).lt.alhigh) then
        diftf = max(diftf ,abs((tf(jc,i,k) - tfn(jc,i,k))/
& tfn(jc,i,k)))
      end if
      if (alp(jc,i,k).gt.allow .and. alpn(jc,i,k).gt.allow) then
        diftg = max(diftg ,abs((tg(jc,i,k) - tgn(jc,i,k))/
& tgn(jc,i,k)))
        difxa = max(difxa ,abs (xa(jc,i,k) - xan(jc,i,k)))
      end if

      arg = alp(jc,i,k)*rog(jc,i,k)
      arf = (one - alp(jc,i,k))*rof(jc,i,k)
      hmix = (arg*hg(jc,i,k) + arf*hf(jc,i,k))/(arg + arf)

      argn = alpn(jc,i,k)*rogn(jc,i,k)
      arfn = (one - alpn(jc,i,k))*rofn(jc,i,k)
      hmixn = (argn*hgn(jc,i,k) + arfn*hfn(jc,i,k))/(argn + arfn)

      vdelh = volc(jc,i,k)*(hmix - hmixn)
      sumdh = sumdh + vdelh*vdelh
      sumv = sumv + volc(jc,i,k)
200 continue
210 continue
220 continue
c
c COMPUTE MAXIMUM CHANGE IN MIDDLE SECTION SURFACE TEMPERATURES.

```

```

c
  do 250 isrf = 2,nsurf
    do 240 ia = 1,na
      do 230 jc = 2,nzpl
        js = jc - 1
        difts = max(difts, abs((tsurf(isrf,ia,js)-tsrfn(isrf,ia,js))
          &          / (tsrfn(isrf,ia,js) + ctok)))
230      continue
240      continue
250      continue
c
c    COMPUTE MAXIMUM CHANGE IN BOTTOM SECTION FLUID VARIABLES
c
  do 300 jc=1,nzb
    difp = max(difp ,abs(( pb(jc) - pbn(jc))/pbn(jc)),
    difalp = max(difalp,abs (alpb(jc) - alpbn(jc)))
    if (alpb(jc).lt.alhigh .and. alpbn(jc).lt.alhigh) then
      diftf = max(diftf ,abs((tfb(jc) - tfbn(jc))/tfbn (jc)))
    end if
    if (alpb(jc).gt.allow .and. alpbn(jc).gt.allow) then
      diftg = max(diftg ,abs((tgb(jc) - tgbn(jc))/tgbn (jc)))
      difxa = max(difxa ,abs (xab(jc) - xabn(jc)))
    end if
c
    arg = alpb(jc)*rogb(jc)
    arf = (one - alpb(jc))*rofb(jc)
    hmix = (arg*hgb(jc) + arf*hfb(jc))/(arg + arf)
c
    argn = alpbn(jc)*rogbn(jc)
    arfn = (one - alpbn(jc))*rofbn(jc)
    hmixn = (argn*hgbn(jc) + arfn*hfbn(jc))/(argn + arfn)
c
    vdelh = volb(jc)*(hmix - hmixn)
    sumdh = sumdh + vdelh*vdelh
    sumv = sumv + volb(jc)
300  continue
c
c    CHECK FOR LARGE MAX CHANGE
c
    dif = max(difp,difalp,diftg,diftf,difxa,difts)
    if (dif.gt. tol) then
      ierr = 3
cc    write(*,900) hundrd*difp ,hundrd*difalp,hundrd*diftg,
cc    &          hundrd*diftf,hundrd*difxa,hundrd*difts
    end if
c
c    CHECK FOR A STEADY STATE SOLUTION
c    BASED ON CHANGE IN MIXTURE ENTHALPY
c
    if (istdy.gt.0) then
      ipass = ipass + 1
c    CHECK IF MAXIMUM NUMBER OF STEADY STATE ITERATIONS EXCEEDED
c    FOR OPTIONS istdy = 2 or istdy = 3
c
      if ((istdy.gt.1) .and. (ipass.gt.nstdy)) then
        write (*,1000) istdy
        stop
      end if
      index = ipass - iset*((ipass-1)/iset)
      delhm = sqrt(sumdh)/(delt*sumv)
cc    write (30,350) tsec, delhm
cc350    format (1x,f10.5,5x,g12.5)
      dhxdt(index) = delhm
      if (ipass.ge.iset) then

```



```

      do 400 ic=1,iset
        if (dhxdt(ic).gt.tolss) return
400    continue
        steady = .true.
      end if
    end if
  c
900  format(/,' Time step reduction requested by accchk',/,
        &      ' % dif: ',f6.1,' p ',f6.1,' alp ',f6.1,' tg ',
        &      ' f6.1,' tf ',f6.1,' xa ',f6.1,' ts')
1000 format(/,' Maximum number of steady-state iterations exceeded',
        &      /,' for istdy = ',il)
  c
    return
  end

```

AIR

```

subroutine air(p,t,roa,droadp,droadt,ha,dhadp,dhadt)
  c
  c *****
  c *
  c * INPUT:
  c *   p = PARTIAL PRESSURE OF AIR, Pa
  c *   t = MIXTURE GAS TEMPERATURE, K
  c *
  c * OUTPUT:
  c *   roa = DENSITY OF AIR, kg/m^3
  c *   droadp = DERIVATIVE OF roa W.R.T. p AT CONSTANT t
  c *   droadt = DERIVATIVE OF roa W.R.T. t AT CONSTANT p
  c *   ha = ENTHALPY OF AIR, J/kg
  c *   dhadp = DERIVATIVE OF ha WRT TOTAL PRESSURE AT CONSTANT t
  c *   dhadt = DERIVATIVE OF ha WRT t AT CONSTANT TOTAL PRESSURE
  c *
  c * RANGE:
  c *   275K < t < 700K
  c *   'low' pressure
  c *
  c *****
  c
  parameter (zero=0.0, one=1.0, two=2.0, three=3.0)
  data ra/287.0/, tref/375.0/, haref/375.7e+3/
  data c1/1005.9/, c2/-8.6140e-2/, c3/2.6295e-4/
  c
  c AIR DENSITY AND ITS DERIVATIVES
  c
    roa = p/(ra*t)
    droadp = one/(ra*t)
    droadt = -roa/t
  c
  c AIR ENTHALPY AND ITS DERIVATIVES
  c
    ha = haref + (c1 + ((c2/two) + (c3/three)*t)*t)*t -
    &      (c1 + ((c2/two) + (c3/three)*tref)*tref)*tref
    dhadp = zero
    dhadt = c1 + (c2 + c3*t)*t
  c
    return
  end

```

AVEC1

```

subroutine avecl (advz,avgak,acz,azz,aratz,uz,alpn,rhon,
  &      acin,uin,alpin,rhoin,acex,uex,alpex,rhoex,
  &      vminz,jz,jmod,nz,nin,nex,liquid)

```

```

C *****
C *
C * SUBROUTINE avecl
C *
C * SUBROUTINE TO CALCULATE THE EXPLICIT ADVECTION TERMS IN
C * THE ONE DIMENSIONAL AXIAL MOMENTUM EQUATIONS FOR THE TOP
C * AND BOTTOM SECTIONS. ONE CALL IS MADE FOR EACH PHASE PER
C * MOMENTUM CELL.
C *
C * ARGUMENTS (O=Output, I=Input):
C *
C * O advz = MOMENTUM ADVECTION TERM NOT INCLUDING 1/Vc FACTOR
C * O avgak = AVERAGE PHASIC AREA
C *
C * I acz = MASS CELL FACE AREAS
C * I azz = MOMENTUM CELL FACE AREAS
C * I aratz = RATIO OF LOCAL MASS FACE AREA TO AVERAGE CELL AREA
C * I uz - PHASE VELOCITY IN AXIAL DIRECTION
C * I alpn = VOID FRACTION
C * I rhon = PHASE DENSITY
C * I acin = INLET FACE AREAS
C * I uin = PHASE VELOCITIES AT INLET FACES
C * I alpin = VOID FRACTIONS AT SECTION INLET BOUNDARY
C * I rhoiin = PHASE DENSITIES AT SECTION INLET BOUNDARY
C * I acex = OUTLET FACE AREAS
C * I uex = PHASE VELOCITIES AT OUTLET FACES
C * I alpex = VOID FRACTIONS AT SECTION OUTLET BOUNDARY
C * I rhoeex = PHASE DENSITIES AT SECTION OUTLET BOUNDARY
C * I vminz = MINIMUM VELOCITY FOR FULL DONORING
C * I jz = AXIAL MOMENTUM CELL INDEX
C * I jmod = OFFSET BETWEEN MOMENTUM AND MASS CELL INDICES
C * jmod = 0 FOR TOP SECTION
C * jmod = 1 FOR BOTTOM SECTION
C * I nz = ARRAY DIMENSION
C * I nin = ARRAY DIMENSION
C * I nex = ARRAY DIMENSION
C * I liquid = PHASE SELECTOR (.true.==>liquid, .false.==>gas)
C *
C * CELL NOTATION:
C *
C *      |-----|
C *      |         |
C *      |   jcm    | UPPER MASS CELL
C *      |         |
C *      |-----jft-----|
C *      |         |
C *      |   jc     | MASS CELL FORMING
C *      |         | PART OF MOMENTUM CELL
C *      |         |
C *      |-----jfb-----|
C *      |         |
C *      |   jcp    | LOWER MASS CELL
C *      |         |
C *      |-----|
C *
C *****
C
C implicit real (a-h,o-z), integer (i-n)
C logical liquid

```

```

c      dimension acz(nz),  uz(nz), aratz(nz),
&          azz(nz), alpn(nz), rhon(nz)
c
c      dimension acin(nin), uin(nin), acex(nex), uex(nex),
&          alpin(nin), rhoin(nin), alpex(nex), rhoex(nex)
c
c      dimension aaavg(2)
c
c      parameter (zero=0.0, half=0.5, one=1.0, two=2.0)
c      data epsalp/1.0e-4/
c
c      INITIALIZATIONS
c
c      aaavg(1) = zero
c      aaavg(2) = zero
c      advz = zero
c      signt = -one
c
c      LOOP OVER TWO AXIAL MASS CELLS FORMING THE MOMENTUM CELL
c
c      do 100 mcell=1,2
c          signt = (-one)*signt
c
c          SET LOCAL CELL POINTERS:
c          jz = MOMENTUM CELL INDEX
c          jc = MASS CELL INDEX
c          jcm = MASS CELL ABOVE jc
c          jcp = MASS CELL BELOW jc
c          jft = INDEX FOR TOP FACE OF MASS CELL jc
c          jfb = INDEX FOR BOTTOM FACE OF MASS CELL jc
c
c          jc = jz + jmod + mcell - 2
c          jcm = jc - 1
c          jcp = jc + 1
c          jft = jc - jmod
c          jfb = jft + 1
c
c          alpc = alpn(jc)
c          rhoc = rhon(jc)
c
c          CALCULATE VOLUME AVERAGE VELOCITY FOR MOMENTUM CELL
c
c          ujz = uz(jz)
c          uavg = ujz*aratz(jz)
c
c----- FOR TOP FACE: CALCULATE AREA(Acz), PHASIC AREA(Acz*alpk), ----
c          (Acz*alpk*rhok), MASS FLOWRATE(Acz*alpk*rhok*uk) &
c          MOMENTUM(Acz*alpk*rhok*uk*uk)
c
c          if (jc .eq. 1) then
c
c              SINGLE (Top Section) OR MULTIPLE (Bottom Section) INLET(S)
c
c              alptmx = zero
c              at = zero
c              aat = zero
c              aart = zero
c              aarut = zero
c              aaruut = zero
c              do 10 k=1,nin
c                  uztop = uin(k)
c                  if (abs(uztop) .ge. vminz) then
c                      wt = sign(half, uztop)

```

```

        else
            wt = half*uztop/vminz
        end if
        wtm = half + wt
        wtp = half - wt
        alpt = wtm*alpin(k) + wtp*alpc
        rhot = wtm*rhoin(k) + wtp*rhoc
        if (liquid) alpt = one - alpt
        alptmx = max(alpt, alptmx)
        temp = acin(k)*alpt
c
        at = at + acin(k)
        aat = aat + temp
        aart = aart + temp*rhot
        aarut = aarut + temp*rhot*uztop
        aaruut = aaruut + temp*rhot*uztop*uztop
10    continue
c
    else
c
c        SINGLE INLET ONLY
c
        uztop = uz(jft)
        if (abs(uztop) .ge. vminz) then
            wt = sign(half, uztop)
        else
            wt = half*uztop/vminz
        end if
        wtm = half + wt
        wtp = half - wt
        alpt = wtm*alpn(jcm) + wtp*alpc
        rhot = wtm*rhon(jcm) + wtp*rhoc
        if (liquid) alpt = one - alpt
        alptmx = alpt
c
        at = acz(jft)
        aat = at*alpt
        aart = aat*rhot
        aarut = aart*uztop
        aaruut = aarut*uztop
c
    end if
c
c----- FOR BOTTOM FACE: CALCULATE AREA(Acz), PHASIC AREA(Acz*alpk),
c                        (Acz*alpk*rhok), MASS FLOWRATE(Acz*alpk*rhok*uk) &
c                        MOMENTUM(Acz*alpk*rhok*uk*uk)
c
    if (jc .eq. nz) then
c
c        SINGLE (Bottom Section) OR MULTIPLE (Top Section) INLET(S)
c
        alpbmx = zero
        ab = zero
        aab = zero
        aarb = zero
        aarub = zero
        aaruub = zero
        do 20 k=1,nex
            uzbot = uex(k)
            if (abs(uzbot) .ge. vminz) then
                wt = sign(half, uzbot)
            else
                wt = half*uzbot/vminz
            end if

```

```

        wtm = half + wt
        wtp = half - wt
        alpb = wtm*alpc + wtp*alpex(k)
        rhob = wtm*rhoc + wtp*rhoex(k)
        if (liquid) alpb = one - alpb
        alpbmx = max(alpb, alpbmx)
        temp = acex(k)*alpb
c
        ab = ab + acex(k)
        aab = aab + temp
        aarb = aarb + temp*rhob
        aarub = aarub + temp*rhob*uzbot
        aaruub = aaruub + temp*rhob*uzbot*uzbot
20      continue
c
      else
c
c        SINGLE INLET ONLY
c
        uzbot = uz(jfb)
        if (abs(uzbot) .ge. vminz) then
          wt = sign(half, uzbot)
        else
          wt = half*uzbot/vminz
        end if
        wtm = half + wt
        wtp = half - wt
        alpb = wtm*alpc + wtp*alpn(jcp)
        rhob = wtm*rhoc + wtp*rhon(jcp)
        if (liquid) alpb = one - alpb
        alpbmx = alpb
c
        ab = acz(jfb)
        aab = ab*alpb
        aarb = aab*rhob
        aarub = aarb*uzbot
        aaruub = aarub*uzbot
c
      end if
c
c----- CALCULATE CONTRIBUTION TO MOMENTUM ADVECTION IN AXIAL -----
c          DIRECTION FROM VELOCITY COMPONENT IN AXIAL DIRECTION &
c          AVERAGE AREA FOR mcell
c
        alpmx = max(alptmx, alpbmx)
        if (alpmx .ge. epsalp) then
          uc = (aarut*at + aarub*ab)/((aart + aarb)*azz(jc))
          if (abs(uc) .ge. vminz) then
            wt = sign(half, uc)
          else
            wt = half*uc/vminz
          end if
          wtm = half + wt
          wtp = half - wt
          aaru = wtm*aarut + wtp*aarub
          aaruu = wtm*aaruut + wtp*aaruub
          advz = advz + signt*(aaruu - aaru*uavg)
c
          aavg(mcell) = two*aat*aab/(aat + aab)
c
        end if
c
100  continue
c

```

```

c----- CALCULATE AVERAGE PHASIC AREA <alp*k*Ac> -----
c
      if (abs(ujz) .ge. vminz) then
        wt = sign(half, ujz)
      else
        wt = half*ujz/vminz
      end if
      wtm = half + wt
      wtp = half - wt
      avgak = wtm*aaavg(1) + wtp*aaavg(2)
c
      return
end

```

AVECB

```

      subroutine avecb (advz,avgak,
6         alpb2,rhob2,          acb2,uzb2,
6         alpbl,rhobl,azbl,acbl,uzbl,aratbl,
6         alptb,rhotb,
6         vminz,liquid)
C
C *****
C *
C SUBROUTINE avecb
C *
C SUBROUTINE TO CALCULATE THE EXPLICIT ADVECTION TERMS IN
C THE ONE DIMENSIONAL AXIAL MOMENTUM EQUATIONS FOR THE OUTLET
C (TANK BOTTOM) BOUNDARY CELL. ONE CALL IS MADE FOR EACH PHASE
C *
C ARGUMENTS (O=Output, I=Input):
C *
C O    advz = MOMENTUM ADVECTION TERM NOT INCLUDING 1/Vc FACTOR
C O    avgak = AVERAGE PHASIC AREA
C *
C I    alpb2 = BOTTOM SECTION CELL nzb-1 VOLUME FRACTION
C I    rhob2 = BOTTOM SECTION CELL nzb-1 PHASIC DENSITY
C I    alpbl = BOTTOM SECTION CELL nzb VOLUME FRACTION
C I    rhobl = BOTTOM SECTION CELL nzb PHASIC DENSITY
C I    azbl = BOTTOM SECTION CELL nzb CELL CENTER AREA
C I    alptb = TANK BOTTOM VOLUME FRACTION
C I    rhotb = TANK BOTTOM PHASIC DENSITY
C I    acb2 = BOTTOM SECTION FACE nzb-1 AREA
C I    uzb2 = BOTTOM SECTION FACE nzb-1 VELOCITY
C I    acbl = BOTTOM SECTION FACE nzb AREA
C I    uzbl = BOTTOM SECTION FACE nzb VELOCITY
C I    aratbl = BOTTOM SECTION FACE nzb AREA RATIO
C I    vminz = MINIMUM VELOCITY FOR FULL DONORING
C I    liquid = PHASE SELECTOR (.true.==>liquid, .false.==>gas)
C *
C CELL NOTATION:
C *
C * -----
C |               |
C |   BOTTOM SECT.   |
C |           *       |   alpb2, rhob2
C |   CELL nzb-1     |
C |               |
C |-----|        |   acb2, uzb2
C |               |
C |   BOTTOM SECT.   |
C --->|- - - *- - - |   alpbl, rhobl, azbl
C |               |   CELL nzb
C |               |
C * BOUNDARY MOMENTUM |   |-----|   acbl, uzbl, aratbl
C * CELL              |   |

```

```
C      *          | TANK BOTTOM |          *
C      *          --->| - - * - - | alptb, rhotb
C      *          | CELL        |
C      *          |             |
C      *          -----
C      *
C      *****
C
C      implicit real (a-h,o-z), integer (i-n)
C      logical liquid
C
C      parameter (zero=0.0, half=0.5, one=1.0, two=2.0)
C      data epsalp/1.0e-4/
C
C      INITIALIZATIONS
C
C      aaavgv = zero
C      advz = zero
C
C      CALCULATE VOLUME AVERAGE VELOCITY FOR MOMENTUM CELL
C
C      uavg = uzbl*aratbl
C
C----- CALCULATE MOMENTUM CONTRIBUTION FROM BOTTOM SECTION CELL nzb -----
C
C      FOR TOP FACE: CALCULATE PHASIC AREA(Acz*alpk),
C                    (Acz*alpk*rhok), MASS FLOWRATE(Acz*alpk*rhok*uk) &
C                    MOMENTUM(Acz*alpk*rhok*uk*uk)
C
C      if (abs(uzb2) .ge. vminz) then
C         wt = sign(half, uzk2)
C      else
C         wt = half*uzb2/vminz
C      end if
C      wtm = half + wt
C      wtp = half - wt
C      alpt = wtm*alpb2 + wtp*alpb1
C      rhot = wtm*rhob2 + wtp*rhob1
C      if (liquid) alpt = one - alpt
C
C      aat = ach2*alpt
C      aart = aat*rhot
C      aarut = aart*uzb2
C      aaruuc = aarut*uzb2
C
C      FOR BOTTOM FACE: CALCULATE PHASIC AREA(Acz*alpk),
C                      (Acz*alpk*rhok), MASS FLOWRATE(Acz*alpk*rhok*uk) &
C                      MOMENTUM(Acz*alpk*rhok*uk*uk)
C
C      if (abs(uzb1) .ge. vminz) then
C         wt = sign(half, uzb1)
C      else
C         wt = half*uzb1/vminz
C      end if
C      wtm = half + wt
C      wtp = half - wt
C      alpb = wtm*alpb1 + wtp*alptb
C      rhob = wtm*rhob1 + wtp*rhotb
C      if (liquid) alpb = one - alpb
C
C      aab = acb1*alpb
C      aarb = aab*rhob
C      aarub = aarb*uzb1
C      aaruub = aarub*uzb1
```

```

c
c  CALCULATE CONTRIBUTION TO MOMENTUM ADVECTION IN AXIAL
c  DIRECTION FROM VELOCITY COMPONENT IN AXIAL DIRECTION
c
  alpmx = max(alpt, alpb)
  if (alpmx .ge. epsalp) then
    uc = (aarut*acb2 + aarub*acb1)/((aart + aarb)*azb1)
    if (abs(uc) .ge. vminz) then
      wt = sign(half, uc)
    else
      wt = half*uc/vminz
    end if
    wtm = half + wt
    wtp = half - wt
    aaru = wtm*aarut + wtp*aarub
    aaruu = wtm*aaruut + wtp*aaruub
    advz = aaruu - aaru*uavg
  c
    aaavg = two*aat*aab/(aat + aab)
  end if
c----- CALCULATE MOMENTUM CONTRIBUTION FROM TANK BOTTOM CELL -----
c
c  FOR TOP FACE: USE PREVIOUSLY COMPUTED VALUES
c
  alpt = alpb
  aat = aab
  aart = aarb
  aarut = aarub
  aaruut = aaruub
c
c  FOR BOTTOM FACE: SET ALL QUANTITIES EQUAL TO TOP FACE VALUES
c  (DONE IMPLICITLY)
c
c  CALCULATE CONTRIBUTION TO MOMENTUM ADVECTION IN AXIAL
c  DIRECTION FROM VELOCITY COMPONENT IN AXIAL DIRECTION
c
  advz = advz - (aaruut - aarut*uavg)
  aaavgb = aat
c----- CALCULATE AVERAGE PHASIC AREA <alpk*Acz> -----
c
  if (abs(uzb1) .ge. vminz) then
    wt = sign(half, uzb1)
  else
    wt = half*uzb1/vminz
  end if
  wtm = half + wt
  wtp = half - wt
  avgak = wtm*aaavg + wtp*aaavgb
c
  return
end

```

AVECT

```

  subroutine avect (advz,avgak,
&                  alpl,rhopl,
&                  alpt1,rhot1,azt1,act1,uzt1,aratt1,
&                  alpt2,rhot2,      act2,uzt2,
&                  vminz,liquid)
c
c  *****
c  *
c  * SUBROUTINE avect
c  *

```



```

c
c   FOR TOP FACE:      SET ALL QUANTITIES EQUAL TO BOTTOM FACE VALUES
c                       (DONE IMPLICITLY)
c   FOR BOTTOM FACE:  CALCULATE PHASIC AREA(Acz*alpk),
c                       (Acz*alpk*rhok), MASS FLOWRATE(Acz*alpk*rhok*uk) &
c                       MOMENTUM(Acz*alpk*rhok*uk*uk)
c
c   if (abs(uzt1) .ge. vminz) then
c       wt = sign(half, uzt1)
c   else
c       wt = half*uzt1/vminz
c   end if
c   wtm = half + wt
c   wtp = half - wt
c   alpb = wtm*alpt1 + wtp*alpt1
c   rhob = wtm*rhop1 + wtp*rhot1
c   if (liquid) alpb = one - alpb
c
c   aab = act1*alpb
c   aarb = aab*rhob
c   aarub = aarb*uzt1
c   aaruub = aarub*uzt1
c
c   CALCULATE CONTRIBUTION TO MOMENTUM ADVECTION IN AXIAL
c   DIRECTION FROM VELOCITY COMPONENT IN AXIAL DIRECTION
c
c   advz = aaruub - aarub*uavg
c   aaavgz = aab
c
c----- CALCULATE MOMENTUM CONTRIBUTION FROM TOP SECTION CELL 1 -----
c
c   FOR TOP FACE:  USE PREVIOUSLY COMPUTED VALUES
c
c   alpt = alpb
c   aat = aab
c   aart = aarb
c   aarut = aarub
c   aaruut = aaruub
c
c   FOR BOTTOM FACE:  CALCULATE PHASIC AREA(Acz*alpk),
c                       (Acz*alpk*rhok), MASS FLOWRATE(Acz*alpk*rhok*uk) &
c                       MOMENTUM(Acz*alpk*rhok*uk*uk)
c
c   if (abs(uzt2) .ge. vminz) then
c       wt = sign(half, uzt2)
c   else
c       wt = half*uzt2/vminz
c   end if
c   wtm = half + wt
c   wtp = half - wt
c   alpb = wtm*alpt1 + wtp*alpt2
c   rhob = wtm*rhop1 + wtp*rhot2
c   if (liquid) alpb = one - alpb
c
c   aab = act2*alpb
c   aarb = aab*rhob
c   aarub = aarb*uzt2
c   aaruub = aarub*uzt2
c
c   CALCULATE CONTRIBUTION TO MOMENTUM ADVECTION IN AXIAL
c   DIRECTION FROM VELOCITY COMPONENT IN AXIAL DIRECTION
c
c   alpmax = max(alpt, alpb)
c   if (alpmax .ge. epsalp) then

```

```

      uc = (aarut*act1 + aarub*act2)/((aart + aarb)*azt1)
      if (abs(uc) .ge. vminz) then
        wt = sign(half, uc)
      else
        wt = half*uc/vminz
      end if
      wtm = half + wt
      wtp = half - wt
      aaru = wtm*aarut + wtp*aarub
      aaruu = wtm*aaruut + wtp*aaruub
      advz = advz - (aaruu - aaru*uavg)
c
      aaavgb = two*aat*aab/(aat + aab)
    end if
c
c---- CALCULATE AVERAGE PHASIC AREA <alpk*Acz> -----
c
      if (abs(uzt1) .ge. vminz) then
        wt = sign(half, uzt1)
      else
        wt = half*uzt1/vminz
      end if
      wtm = half + wt
      wtp = half - wt
      avgak = wtm*aaavgt + wtp*aaavgb
c
    return
  end

```

AVECX

```

      subroutine avecx (advx,avgax,acx,acz,axx,aratx,wx,uz,alpn,
&                      rhon,vminz,vminx,ix,k,icc,nzpl,nzp2,nzp3,
&                      nxmax,nchn,liquid)
c
c *****
c *
c * SUBROUTINE avecx
c *
c * SUBROUTINE TO CALCULATE THE EXPLICIT ADVECTION TERMS IN THE
c * AZIMUTHAL MOMENTUM EQUATIONS FOR THE MIDDLE SECTION. ONE
c * CALL IS MADE FOR EACH PHASE PER AXIAL STRIPE OF MOM. CELLS
c *
c * ARGUMENTS (O=Output, I=Input):
c *
c * O advx = AZIMUTHAL MOM. ADVECTION TERM NOT INCLUDING 1/Vc
c * O avgax = AVERAGE AZIMUTHAL PHASIC AREA
c *
c * I acx = MASS CELL FACE AREAS IN THE AZIMUTHAL DIRECTION
c * I acz = MASS CELL FACE AREAS IN THE AXIAL DIRECTION
c * I axx = MOMENTUM CELL FACE AREAS IN AZIMUTHAL DIRECTION
c * I aratx = RATIO OF LOCAL MASS FACE AREA TO AVERAGE CELL AREA
c * I wx = PHASE VELOCITY IN AZIMUTHAL DIRECTION
c * I uz = PHASE VELOCITY IN AXIAL DIRECTION
c * I alpn = VOLUME FRACTION
c * I rhon = PHASE DENSITY
c * I vminz = MINIMUM AXIAL VELOCITY FOR FULL DONORING
c * I vminx = MINIMUM AZIMUTHAL VELOCITY FOR FULL DONORING
c * I ix = MOMENTUM CELL AZIMUTHAL INDEX
c * I k = MOMENTUM CELL CHANNEL INDEX
c * I icc = POINTER TO ADJACENT AZIMUTHAL CELLS
c * I nzpl = ARRAY DIMENSION
c * I nzp2 = ARRAY DIMENSION
c * I nzp3 = ARRAY DIMENSION
c * I nxmax = ARRAY DIMENSION

```



```

c      icp = MASS CELL TO RIGHT OF CELL ic
c      ifl = INDEX FOR LEFT FACE OF CELL ic
c      ifr = INDEX FOR RIGHT FACE OF CELL ic
c      jft = INDEX FOR TOP FACE OF CELL ic
c      jfb = INDEX FOR BOTTOM FACE OF CELL ic
c
c      jzm = jz - 1
c      jzp = jz + 1
c      ixm = icc(1,ix,k)
c      ic = ixm + (mcell - 1)*(ix - ixm)
c      icm = icc(1,ic,k)
c      icp = icc(2,ic,k)
c      ifl = ic
c      ifr = icp
c      jft = jz
c      jfb = jzp
c
c      alpc = alpn(jz,ic,k)
c      rhoc = rhon(jz,ic,k)
c
c      CALCULATE VOLUME AVERAGE VELOCITIES FOR MOMENTUM
c      CELL AND MOMENTUM CELLS ABOVE AND BELOW CELL
c
c      wxix = wx(jz,ix,k)
c      wavg = wxix*aratx(jz,ix,k)
c      wxtop = wx(jzm,ix,k)*aratx(jzm,ix,k)
c      wxbot = wx(jzp,ix,k)*aratx(jzp,ix,k)
c
c----- AZIMUTHAL MOMENTUM CONTRIBUTION FROM AZIMUTHAL VELOCITIES -----
c
c      FOR LEFT FACE: CALCULATE AREA(Acx), PHASIC AREA(Acx*alpk),
c                      (Acx*alpk*rhok), MASS FLOWRATE(Acx*alpk*rhok*uk) &
c                      MOMENTUM(Acx*alpk*rhok*uk*uk)
c
c      wxlft = wx(jz,ifl,k)
c      if (abs(wxlft) .ge. vminx) then
c          wt = sign(half, wxlft)
c      else
c          wt = half*wxlft/vminx
c      end if
c      wtm = half + wt
c      wtp = half - wt
c      alpl = wtm*alpn(jz,icm,k) + wtp*alpc
c      alpl = vrib(alpl)
c      rhol = wtm*rhon(jz,icm,k) + wtp*rhoc
c      if (liquid) alpl = one - alpl
c
c      al = acx(jz,ifl,k)
c      aal = al*alpl
c      aarl = aal*rhol
c      aarwl = aarl*wxlft
c      aarwl = aarwl*wxlft
c
c      FOR RIGHT FACE: CALCULATE AREA(Acx), PHASIC AREA(Acx*alpk),
c                      (Acx*alpk*rhok), MASS FLOWRATE(Acx*alpk*rhok*uk) &
c                      MOMENTUM(Acx*alpk*rhok*uk*uk)
c
c      wxrqt = wx(jz,ifr,k)
c      if (abs(wxrqt) .ge. vminx) then
c          wt = sign(half, wxrqt)
c      else
c          wt = half*wxrqt/vminx
c      end if
c      wtm = half + wt

```

```

      wtp = half - wt
      alpr = wtm*alpc + wtp*alpn(jz,icp,k)
      alpr = vrib(alpr)
      rhor = wtm*rhoc + wtp*rhon(jz,icp,k)
      if (liquid) alpr = one - alpr
c
      ar = acx(jz,ifr,k)
      aar = ar*alpr
      aarr = aar*rhor
      aarwr = aarr*wxrgt
      aarwrr = aarwr*wxrgt
c
c      CALCULATE CONTRIBUTION TO MOMENTUM ADVECTION IN AZIMUTHAL
c      DIRECTION FROM VELOCITY COMPONENT IN AZIMUTHAL DIRECTION &
c      AVERAGE AREA FOR mcell
c
      alpmax = max(alpl, alpr)
      if (alpmax .ge. epsalp) then
        wc = (aarwl*al + aarwr*ar)/((aarl + aarr)*axx(jz,ic,k))
        if (abs(wc) .ge. vminx) then
          wt = sign(half, wc)
        else
          wt = half*wc/vminx
        end if
        wtm = half + wt
        wtp = half - wt
        aarw = wtm*aarwl + wtp*aarwr
        aarww = wtm*aarwrl + wtp*aarwrr
        advx(jz) = advx(jz) + signt*(aarww - aarw*wavg)
c
        aaavg(mcell,jz) = two*aal*aar/(aal + aar)
      end if
c
c----- AZIMUTHAL MOMENTUM CONTRIBUTION FROM AXIAL VELOCITIES -----
c
c      FOR TOP FACE:  CALCULATE AZIMUTHAL VELOCITY FOR LATERAL MOM.
c                     TRANSPORT <w>i-1/2 left(1st pass) or right
c                     (2nd pass) & MASS FLOWRATE(Acx*alpk*rhoc*uk)
c
      uztop = uz(jft,ic,k)
      if (abs(uztop) .ge. vminz) then
        wt = sign(half, uztop)
      else
        wt = half*uztop/vminz
      end if
      wtm = half + wt
      wtp = half - wt
      alpt = wtm*alpn(jzm,ic,k) + wtp*alpc
      rhot = wtm*rhon(jzm,ic,k) + wtp*rhoc
      if (liquid) alpt = one - alpt
c
      wxt = wtm*wxtop + wtp*wavg
      aarut = acz(jft,ic,k)*alpt*rhot*uztop
c
c      FOR BOTTOM FACE:  CALCULATE AZIMUTHAL VELOCITY FOR LATERAL MOM.
c                     TRANSPORT <w>i-1/2 left(1st pass) or right
c                     (2nd pass) & MASS FLOWRATE(Acx*alpk*rhoc*uk)
c
      uzbot = uz(jfb,ic,k)
      if (abs(uzbot) .ge. vminz) then
        wt = sign(half, uzbot)
      else
        wt = half*uzbot/vminz
      end if

```

```

      wtm = half + wt
      wtp = half - wt
      alpb = wtm*alpc + wtp*alpn(jzp,ic,k)
      rhob = wtm*rhoc + wtp*rhon(jzp,ic,k)
      if (liquid) alpb = one - alpb
c
      wxb = wtm*wavg + wtp*wxbot
      aarub = acz(jfb,ic,k)*alpb*rhob*uzbot
c
c      CALCULATE CONTRIBUTION TO MOMENTUM ADVECTION IN AZIMUTHAL
c      DIRECTION FROM VELOCITY COMPONENT IN AXIAL DIRECTION
c
      advx(jz) = advx(jz) + half*(aarut*(wxt - wavg)
&                - aarub*(wxb - wavg))
c
c 100 continue
c
c 200 continue
c
c----- CALCULATE AVERAGE PHASIC AREA <alpk*Acx> -----
c
      do 300 jz=2,nzpl
        if (abs(wxix) .ge. vminx) then
          wt = sign(half, wxix)
        else
          wt = half*wxix/vminx
        end if
        wtm = half + wt
        wtp = half - wt
        avgax(jz) = wtm*aaavg(1,jz) + wtp*aaavg(2,jz)
300 continue
c
      return
      end

```

AVECZ

```

      subroutine avecz (advz,avgaz,acx,acz,azz,aratz,wx,uz,alpn,
&                    rhon,alpin,rhoi,alpex,rhoex,vminz,vminx,ix,
&                    k,icc,nzp2,nzp3,nxmax,nchn,liquid)
c
c *****
c *
c * SUBROUTINE avecz
c *
c * SUBROUTINE TO CALCULATE THE EXPLICIT ADVECTION TERMS IN THE
c * AXIAL MOMENTUM EQUATIONS FOR THE MIDDLE SECTION. ONE CALL
c * IS MADE FOR EACH PHASE PER AXIAL STRIPE OF MOMENTUM CELLS
c *
c * ARGUMENTS (O=Output, I=Input):
c *
c * O advz = AXIAL MOMENTUM ADVECTION TERM NOT INCLUDING 1/Vc
c * O avgaz = AVERAGE AXIAL PHASIC AREA
c *
c * I acx = MASS CELL FACE AREAS IN THE AZIMUTHAL DIRECTION
c * I acz = MASS CELL FACE AREAS IN THE AXIAL DIRECTION
c * I azz = MOMENTUM CELL FACE AREAS IN AXIAL DIRECTION
c * I aratz = RATIO OF LOCAL MASS FACE AREA TO AVERAGE CELL AREA
c * I wx = PHASE VELOCITY IN AZIMUTHAL DIRECTION
c * I uz = PHASE VELOCITY IN AXIAL DIRECTION
c * I alpn = VOLUME FRACTION
c * I rhon = PHASE DENSITY
c * I alpin = VOLUME FRACTION IN TOP SECTION CELL nzt-1
c * I rhoi = PHASE DENSITY IN TOP SECTION CELL nzt-1
c * I alpex = VOLUME FRACTION IN BOTTOM SECTION CELL 2

```

```

C      * I rhoex = PHASE DENSITY IN BOTTOM SECTION CELL 2
C      * I vminz = MINIMUM AXIAL VELOCITY FOR FULL DONORING
C      * I vminx = MINIMUM AZIMUTHAL VELOCITY FOR FULL DONORING
C      * I ix = MOMENTUM CELL AZIMUTHAL INDEX
C      * I k = MOMENTUM CELL CHANNEL INDEX
C      * I icc = POINTER TO ADJACENT AZIMUTHAL CELLS
C      * I nzp2 = ARRAY DIMENSION
C      * I nzp3 = ARRAY DIMENSION
C      * I nxmax = ARRAY DIMENSION
C      * I nchn = ARRAY DIMENSION
C      * I liquid = PHASE SELECTOR (.true.==>liquid, .false.==>gas)
C
C      * CELL NOTATION:
C
C      *
C      *          |-----|
C      *          |         |
C      *          |       jcm       | UPPER MASS CELL
C      *          |         |
C      *          |-----jft-----|
C      *          |             |
C      *          |   ixm   ifl   jc   ifr   ixp   | MASS CELL
C      *          |             | FORMING PART
C      *          |             | OF AXIAL
C      *          |             | MOMENTUM
C      *          |             | CELL
C      *          |-----jfb-----|
C      *          |         |
C      *          |       jcp       | LOWER MASS CELL
C      *          |         |
C      *          |-----|
C
C      *****
C      implicit real (a-h,o-z), integer (i-n)
C      logical liquid
C
C      dimension acx(nzp2,nxmax,nchn),    acz(nzp3,nxmax,nchn),
C      &          wx(nzp2,nxmax,nchn),    uz(nzp3,nxmax,nchn),
C      &          alpn(nzp2,nxmax,nchn), aratz(nzp3,nxmax,nchn),
C      &          rhon(nzp2,nxmax,nchn),
C      &          azz(nzp2,nxmax,nchn),
C      &          icc(2,nxmax,nchn)
C
C      dimension advz(nzp2), avgaz(nzp2), aaavg(2,100)
C
C      parameter (zero=0.0, half=0.5, one=1.0, two=2.0)
C      data epsalp/1.0e-4/
C
C      INITIALIZATIONS
C
C      call clear (aaavg,200)
C      call clear (advz,nzp2)
C      signt = -one
C
C      SET LOCAL POINTERS TO ADJACENT AZIMUTHAL CELLS
C
C      ixm = icc(1,ix,k)
C      ixp = icc(2,ix,k)
C
C      LOOP OVER TWO AXIAL MASS CELLS FORMING THE MOMENTUM CELL
C
C      do 200 mcell=1,2

```



```

      signt = (-one)*signt
c
      do 100 jz=2,nzp2
c
c         SET LOCAL POINTERS TO ADJACENT CELLS AND CELL FACES:
c         jz = MOMENTUM CELL INDEX (AXIAL FACE AT CELL CENTER)
c         jc = MASS CELL INDEX
c         jcm = MASS CELL ABOVE CELL jc
c         jcp = MASS CELL TO BELOW CELL jc
c         jft = INDEX FOR TOP FACE OF CELL jc
c         jfb = INDEX FOR BOTTOM FACE OF CELL jc
c         ifl = INDEX FOR LEFT FACE OF CELL jc
c         ifr = INDEX FOR RIGHT FACE OF CELL jc
c
c         jc = jz - 2 + mcell
c         jcm = jc - 1
c         jcp = jc + 1
c         jft = jc
c         jfb = jc + 1
c         ifl = ix
c         ifr = ixp
c
c         alpc = alpn(jc,ix,k)
c         rhoc = rhon(jc,ix,k)
c
c         CALCULATE VOLUME AVERAGE VELOCITIES FOR MOMENTUM
c         CELL AND MOMENTUM CELLS TO LEFT AND RIGHT
c
c         uzjz = uz(jz,ix,k)
c         uavg = uzjz*aratz(jz,ix,k)
c         uzlft = uz(jz,ixm,k)*aratz(jz,ixm,k)
c         uzrgt = uz(jz,ixp,k)*aratz(jz,ixp,k)
c
c----- AXIAL MOMENTUM CONTRIBUTION FROM AXIAL VELOCITIES -----
c
c         FOR TOP FACE: CALCULATE AREA(Acz), PHASIC AREA(Acz*alpk),
c                     (Acz*alpk*rhok), MASS FLOWRATE(Acz*alpk*rhok*uk) &
c                     MOMENTUM(Acz*alpk*rhok*uk*uk)
c
c         uztop = uz(jft,ix,k)
c         if (abs(uztop) .ge. vminz) then
c             wt = sign(half, uztop)
c         else
c             wt = half*uztop/vminz
c         end if
c         wtm = half + wt
c         wtp = half - wt
c         if (jcm .lt. 1) then
c             if (nchn .ne. 3) then
c                 alpm = alpin
c             else
c                 alpm = alpn(jc,ix,k)
c             end if
c             alpt = wtm*alpm + wtp*alpc
c             rhot = wtm*rhoin + wtp*rhoc
c         else
c             alpt = wtm*alpn(jcm,ix,k) + wtp*alpc
c             rhot = wtm*rhon(jcm,ix,k) + wtp*rhoc
c         end if
c         if (liquid) alpt = one - alpt
c
c         at = acz(jft,ix,k)
c         aat = at*alpt
c         aart = aat*rhot

```

```

      aarut = aart*uztop
      aaruut = aarut*uztop
c
c      FOR BOTTOM FACE: CALCULATE AREA(Acz), PHASIC AREA(Acz*alpk),
c                      (Acz*alpk*rhok), MASS FLOWRATE(Acz*alpk*rhok*uk) &
c                      MOMENTUM(Acz*alpk*rhok*uk*uk)
c
      uzbot = uz(jfb,ix,k)
      if (abs(uzbot) .ge. vminz) then
         wt = sign(half, uzbot)
      else
         wt = half*uzbot/vminz
      end if
      wtm = half + wt
      wtp = half - wt
      if (jcp .gt. nzp2) then
         alpb = wtm*alpc + wtp*alpex
         rhob = wtm*rhoc + wtp*rhoex
      else
         alpb = wtm*alpc + wtp*alpn(jcp,ix,k)
         rhob = wtm*rhoc + wtp*rhon(jcp,ix,k)
      end if
      if (liquid) alpb = one - alpb
c
      ab = acz(jfb,ix,k)
      aab = ab*alpb
      aarb = aab*rhob
      aarub = aarb*uzbot
      aaruub = aarub*uzbot
c
c      MODIFY ABOVE RESULTS FOR ENTRANCE/EXIT FICTITIOUS CELLS
c      IF 1) PHASE EXISTS
c          2) VELOCITIES ARE IN SAME DIRECTION
c          3) MIDDLE SECTION IS NOT 1-D
c
      alphas = alpt
      alphab = alpb
c
      if (jft .eq. 1) then
         if ((alpt .ge. epsalp) .and. (uztop*uzbot .gt. zero)
           & .and. (nchn*nxmax .ne. 1)) then
            at = aarub/(alpt*rhot*uztop)
            aat = at*alpt
            aart = aat*rhot
            aarut = aart*uztop
            aaruut = aarut*uztop
            alphas = alpb
         end if
      end if
c
      if (jfb .eq. nzp3) then
         if ((alpb .ge. epsalp) .and. (uztop*uzbot .gt. zero)
           & .and. (nchn*nxmax .ne. 1)) then
            ab = aarut/(alpb*rhob*uzbot)
            aab = ab*alpb
            aarb = aab*rhob
            aarub = aarb*uzbot
            aaruub = aarub*uzbot
            alphab = alpt
         end if
      end if
c
c      CALCULATE CONTRIBUTION TO MOMENTUM ADVECTION IN AXIAL
c      DIRECTION FROM VELOCITY COMPONENT IN AXIAL DIRECTION &

```

```

c      AVERAGE AREA FOR mcell
c
      alpmax = max(alphat, alphab)
      if (alpmax .ge. epsalp) then
        uc = (aarut*at + aarub*ab)/((aart + aarb)*azz(jc,ix,k))
        if (abs(uc) .ge. vminz) then
          wt = sign(half, uc)
        else
          wt = half*uc/vminz
        end if
        wtm = half + wt
        wtp = half - wt
        aaru = wtm*aarut + wtp*aarub
        aaruu = wtm*aaruut + wtp*aaruub
        advz(jz) = advz(jz) + signt*(aaruu - aaru*uavg)
c
        aaavg(mcell,jz) = two*aat*aab/(aat + aab)
      end if
c
c----- AXIAL MOMENTUM CONTRIBUTION FROM AZIMUTHAL VELOCITIES -----
c
c      FOR LEFT FACE:  CALCULATE AXIAL VELOCITY FOR LATERAL MOMENTUM
c                      TRANSPORT <u>i-1/2 upper(1st pass) or lower
c                      (2nd pass) & MASS FLOWRATE(Acz*alp*rhok*wk)
c
      wxlft = wx(jc,ifl,k)
      if (abs(wxlft) .ge. vminx) then
        wt = sign(half, wxlft)
      else
        wt = half*wxlft/vminx
      end if
      wtm = half + wt
      wtp = half - wt
      alpl = wtm*alpn(jc,ixm,k) + wtp*alpc
      alpl = vrib(alpl)
      rhol = wtm*rhon(jc,ixm,k) + wtp*rhoc
      if (liquid) alpl = one - alpl
c
      uzl = wtm*uzlft + wtp*uavg
      aarwl = acx(jc,ifl,k)*alpl*rhol*wxlft
c
c      FOR RIGHT FACE:  CALCULATE AXIAL VELOCITY FOR LATERAL MOMENTUM
c                      TRANSPORT <u>i+1/2 upper(1st pass) or lower
c                      (2nd pass) & MASS FLOWRATE(Acz*alp*rhok*wk)
c
      wxrgt = wx(jc,ifr,k)
      if (abs(wxrgt) .ge. vminx) then
        wt = sign(half, wxrgt)
      else
        wt = half*wxrgt/vminx
      end if
      wtm = half + wt
      wtp = half - wt
      alpr = wtm*alpc + wtp*alpn(jc,ixp,k)
      alpr = vrib(alpr)
      rhor = wtm*rhoc + wtp*rhon(jc,ixp,k)
      if (liquid) alpr = one - alpr
c
      uzr = wtm*uavg + wtp*uzrgt
      aarwr = acx(jc,ifr,k)*alpr*rhor*wxrgt
c
c      CALCULATE CONTRIBUTION TO MOMENTUM ADVECTION IN AXIAL
c      DIRECTION FROM VELOCITY COMPONENT IN AZIMUTHAL DIRECTION
c

```

```

      advz(jz) = advz(jz) + half*(aarwl*(uzl - uavg)
      &          - aarwr*(uzr - uavg))
c
100  continue
c
200  continue
c
c---- CALCULATE AVERAGE PHASIC AREA <alp*Acz> -----
c
      do 300 jz=2,nzp2
        if (abs(uzjz) .ge. vminz) then
          wt = sign(half, uzjz)
        else
          wt = half*uzjz/vminz
        end if
        wtm = half + wt
        wtp = half - wt
        avgaz(jz) = wtm*aaavg(1,jz) + wtp*aaavg(2,jz)
300  continue
c
      return
      end

```

AXIALP

```

      subroutine axialp (axial,axalo,itimex,itime,timet,tsec,rdz,nz,
      &                  iaxlp,ntp,intp,itype,xtp,ytp,ztp,ntpmax,ntptot,
      &                  nsplin,nout,izht,izhb)
c
c *****
c *
c *   THIS ROUTINE CALCULATES THE NORMALIZED AXIAL POWER
c *   PROFILE AT THE SPECIFIED TIME tsec.  VARIOUS SNAPSHOTS
c *   OF THE AXIAL PROFILE ARE GIVEN IN A SPLINE FIT FORM
c *   WHERE THE DESIRED PROFILE IS OBTAINED FROM THIS SET
c *   BY LINEAR INTERPOLATION OVER TIME.  THE SNAPSHOTS WERE
c *   OBTAINED FROM A SEPARATE CODE WHICH PERFORMED 1-D SPACE
c *   AND TIME DIFFUSION THEORY (TWO-GROUP) CALCULATIONS AND
c *   ACCOUNT FOR SAFETY ROD INSERTION EFFECTS.
c *
c *   THIS ROUTINE IS ENTERED AT TIME 0.0 TO INITIALIZE,
c *   THEN AT LATER TIMES TO GENERATE CURRENT AXIAL SHAPE.
c *
c *   A SET OF 'itime' SNAPSHOT TIMES 'time' ARE SPECIFIED
c *   IN THE INPUT SET OF ctp COEFFICIENTS, DATA IS
c *   SPECIFIED FOR 11 AXIAL POSITIONS AT 9 SNAPSHOT
c *   TIMES THROUGH INPUT.
c *
c *   AXIAL      SNAPSHOT
c *   PROFILE    TIME          AXIAL PROFILE
c *
c *   FIRST      itimex-1      LOWER TIME PROFILE
c *   SECOND      itimex        UPPER TIME PROFILE
c *   THIRD      INTERPOLATED   INTERPOLATED PROFILE
c *
c *****
c=====
c  CALCULATE NORMALIZED AXIAL POWER PROFILE AT TIME tsec
c=====
c
c  ARGUMENTS:
c  O axial - AXIAL POWER SHAPE
c  O axalo - AXIAL POWER SHAPE AT TIME 0.0
c  O itimex - LATEST AXIAL PROFILE SNAPSHOT COUNTER
c
c  I itime - NUMBER OF SNAPSHOTS FOR AXIAL POWER SHAPE

```

```

c I timet - SNAPSHOT TIMES AT WHICH AXIAL SHAPES ARE INPUT
c I tsec  - CURRENT TIME, sec
c I rdz   - AXIAL MESH SPACINGS NORMALIZED TO UNIT LENGTH OVER
c         HEATED SECTION
c I nz    - NUMBER OF AXIAL LEVELS
c I iaxlp - ARRAY OF POINTERS TO AXIAL POWER SHAPE PROFILES
c I ntp   - ARRAY CONTAINING NUMBER OF DATA POINTS IN SPLINE FITS
c I intp  - ARRAY OF POINTERS TO START OF DATA SETS
c I itype - ARRAY CONTAINING TYPE OF SPLINE
c I xtp   - ABSCISSA VALUES FOR SPLINE DATA
c I ytp   - ORDINATE VALUES FOR SPLINE DATA
c I ztp   - SPLINE COEFFICIENTS
c I ntpmax - MAXIMUM NUMBER OF POINTS IN A SPLINE
c I ntptot - TOTAL NUMBER OF SPLINE DATA POINTS
c I nspln  - NUMBER OF SPLINES USED
c I nout   - WRITE FILE UNIT NUMBER
c I izht   - TOP AXIAL CELL THAT IS HEATED
c I izhb   - BOTTOM AXIAL CELL THAT IS HEATED
c

```

```

c -----
c
c      implicit real (a-h,o-z), integer (i-n)
c      parameter (zero=0.0, half=0.5, one=1.0)
c
c      dimension axial(nz,3), axial0(nz), rdz(nz)
c
c      dimension xtp(ntptot), ytp(ntpmax,nspln), ztp(ntpmax,nspln),
c      &          intp(nspln), itype(nspln), ntp(nspln),
c      &          iaxlp(itime), timet(itime)
c
c      INITIALIZE THE SNAPSHOTS OF THE AXIAL PROFILE ON FIRST CALL
c
c      if (tsec .eq. zero) then
c          itime = 1
c          ispln = iaxlp(1)
c
c      LOOP OVER DESIRED AXIAL POSITIONS AND CALCULATE PROFILE
c
c          ntps = ntp(ispln)
c          ityp = itype(ispln)
c          inx = intp(ispln)
c          asum = zero
c          zsum = zero
c
c          do 20 iz=izht,izhb
c              zval = zsum + half*rdz(iz)
c              axial(iz,1) = yvalu(ityp,ntps,xtp(inx),ytp(1,ispln),
c      &              ztp(1,ispln),zval)
c              asum = asum + axial(iz,1)
c              zsum = zsum + rdz(iz)
c
c          20 continue
c          asumi = one/asum
c
c      NORMALIZE AXIAL PROFILES
c
c          do 30 iz=izht,izhb
c              axial(iz,1) = asumi*axial(iz,1)
c              axial(iz,2) = axial(iz,1)
c              axial(iz,3) = axial(iz,1)
c              axial0(iz) = axial(iz,1)
c          30 continue
c
c      end if
c

```

```
c      CHECK CURRENT SNAPSHOT TIME INTERVAL WITH CURRENT TIME tsec,
c      IF tsec OUTSIDE RANGE UPDATE TIME INTERVAL PRIOR TO DOING
c      THE LINEAR INTERPOLATION IN TIME
c
c      if (itimex.gt.1 .and. tsec.le.timet(itimex)) goto 800
500  continue
c
c      PLACE SECOND PROFILE INTO THE FIRST PROFILE ARRAY
c
c      do 600 iz=izht,izhb
c          axial(iz,1) = axial(iz,2)
600  continue
c
c      if (itimex.eq.itime) then
c          slope = zero
c          goto 825
c      else
c          itimex = itimex + 1
c          isplne = iaxlp(itimex)
c      end if
c
c      CALCULATE NORMALIZED PROFILE FOR SECOND PROFILE ARRAY
c
c      LOOP OVER DESIRED AXIAL POSITIONS AND CALCULATE PROFILE
c
c      ntps = ntp(isplne)
c      ityp = itype(isplne)
c      inx = intp(isplne)
c      asum = zero
c      zsum = zero
c      do 670 iz=izht,izhb
c          zval = zsum + half*rdz(iz)
c          axial(iz,2) = yvalu(ityp,ntps,ctp(inx),ytp(1,isplne),
c              &          ztp(1,isplne),zval)
c          asum = asum + axial(iz,2)
c          zsum = zsum + rdz(iz)
670  continue
c      asumi = one/asum
c
c      NORMALIZE SECOND AXIAL PROFILE
c
c      do 700 iz=izht,izhb
c          axial(iz,2) = asumi*axial(iz,2)
700  continue
c
c      IF TIME STILL EXCEEDS SNAP-SHOT RANGE CONTINUE STEPPING
c
c      if (tsec.gt.timet(itimex)) goto 500
c
c      PERFORM LINEAR INTERPOLATION IN TIME FOR CURRENT PROFILE,
c      IF ALL SNAPSHOT TIMES HAVE BEEN EXCEEDED, HOLD THE AXIAL
c      POWER PROFILE CONSTANT USING THE FINAL ENTERED SHAPE
c
c      800  continue
c      slope = (tsec - timet(itimex-1))/
c      &      (timet(itimex) - timet(itimex-1))
c
c      825  asum = zero
c          zsum = zero
c          do 850 iz=izht,izhb
c              axial(iz,3) = axial(iz,1) +
c              &          slope*(axial(iz,2) - axial(iz,1))
c              asum = asum + axial(iz,3)
c              zsum = zsum + rdz(iz)
```

```

850  continue
      asumi = one/asum
c
c    NORMALIZE THIRD AXIAL PROFILE
c
      do 900 iz=izht,izhb
          axial(iz,3) = asumi*axial(iz,3)
900  continue
c
c    PRINT AXIAL PROFILE (NORMALLY OFF)
c
cc    write (nout,1100) tsec
cc    write (nout,1200) (axial(i,1), axial(i,2), axial(i,3), i=1,nz)
1100  format (//,' axial power shape profiles 1, 2, and 3 at time ',
&          g12.5,' seconds'/)
1200  format (1x,3(g15.4,2x))
c
      return
      end

```

BOUND

```

      subroutine bound (xtp,ytp,ztp,ntp,intp,itype,nspln,
&                    ntpmax,ntptot,tsec,
&                    ppl,alpp1,tgpl,tfpl,xapl,rogpl,rofpl,hgpl,hfpl,
&                    ptb,alptb,tgtb,tftb,xatb,rogtb,roftb,hgtb,hftb,
&                    ppl0,alpp10,tgpl0,tfpl0,xapl0,
&                    ptb0,alptb0,tgtb0,tftb0,xatb0,
&                    qfin,qgin,qfin0,qgin0,
&                    ippl,ialpl,itgpl,itfpl,ixapl,
&                    iptb,ialtb,itgtb,itftb,ixatb,
&                    iqfin,iqgin,factor,ilq)
c
c *****
c *
c * SUBROUTINE bound
c *
c * SUBROUTINE TO FIND THERMODYNAMIC STATE PROPERTIES WITHIN THE
c * THE PLENUM AND TANK BOTTOM BOUNDARY CELLS AT TIME tsec
c *
c * INPUT ARGUMENTS:
c *
c *      xtp - ABSCISSA VALUES IN TRANSIENT PROFILE
c *      ytp - ORDINATE VALUES FOR SPLINE DATA
c *      ztp - SPLINE COEFFICIENTS
c *      ntp - NUMBER OF SPLINE INTERVALS IN TRANSIENT PROFILE
c *      intp - POINTER TO SPLINE COEFFICIENT AND DATA WITHIN
c *            THE ARRAYS xtp AND ztp
c *      nspln - NUMBER OF SPLINE PROFILES USED
c *      ntpmax - MAXIMUM NUMBER OF POINTS IN A SPLINE
c *      ntptot - CUMULATIVE NUMBER OF SPLINE POINTS FOR ALL PROFILES
c *      tsec - TIME AT WHICH SPLINES ARE TO BE EVALUATED
c *      factor - LIQUID COMPRESSIBILITY FACTOR
c *      ilq - LIQUID IDENTIFIER (1=H2O, 2=D2O)
c *
c * Spline multiplication coefficients:
c *      ppl0 - PLENUM PRESSURE
c *      alpp10 - PLENUM VOID FRACTION
c *      tgpl0 - PLENUM GAS TEMPERATURE
c *      tfpl0 - PLENUM FLUID TEMPERATURE
c *      xapl0 - PLENUM AIR MASS FRACTION
c *      qfin0 - INLET LIQUID FLOW RATE
c *      qgin0 - INLET GAS FLOW RATE
c *      ptb0 - TANK BOTTOM PRESSURE
c *      alptb0 - TANK BOTTOM VOID FRACTION

```

```

c      *      tgtb0 - TANK BOTTOM GAS TEMPERATURE      *
c      *      tftb0 - TANK BOTTOM FLUID TEMPERATURE    *
c      *      xatb0 - TANK BOTTOM AIR MASS FRACTION    *
c      *
c      *      OUTPUT ARGUMENTS:
c      *
c      *      Primary thermodynamic state variables:
c      *      ppl - PLENUM PRESSURE
c      *      alppl - PLENUM VOID FRACTION
c      *      tfpl - PLENUM FLUID TEMPERATURE
c      *      tgpl - PLENUM GAS TEMPERATURE
c      *      xapl - PLENUM AIR MASS FRACTION
c      *      qfin - INLET LIQUID FLOW RATE
c      *      qgin - INLET GAS FLOW RATE
c      *      ptb - TANK BOTTOM PRESSURE
c      *      alptb - TANK BOTTOM VOID FRACTION
c      *      tftb - TANK BOTTOM FLUID TEMPERATURE
c      *      tgtb - TANK BOTTOM GAS TEMPERATURE
c      *      xatb - TANK BOTTOM AIR MASS FRACTION
c      *
c      *      Auxiliary state variables:
c      *      rogpl - PLENUM GAS DENSITY
c      *      rofpl - PLENUM FLUID DENSITY
c      *      hgpl - PLENUM GAS ENTHALPY
c      *      hfpl - PLENUM FLUID ENTHALPY
c      *      rogtb - TANK BOTTOM GAS DENSITY
c      *      roftb - TANK BOTTOM FLUID DENSITY
c      *      hgtb - TANK BOTTOM GAS ENTHALPY
c      *      hftb - TANK BOTTOM FLUID ENTHALPY
c      *
c      *      INPUT ARGUMENTS HAVING THE OUTPUT VARIABLE NAMES PRECEDED
c      *      BY THE PREFIX i ARE POINTERS USED TO INDICATE THE TRANSIENT
c      *      PROFILE TO BE USED TO DETERMINE THE VARIABLE TIME HISTORY
c      *
c      *      *****
c      implicit real (a-h,o-z), integer (i-n)
c      parameter (convt=273.15)
c
c      dimension xtp(ntptot), ytp(ntpmax,nspln), ztp(ntpmax,nspln),
c      &          intp(nspln), itype(nspln), ntp(nspln)
c
c      dimension drogdp(1), drogdt(1), drgdx(1),
c      &          dhgdp(1), dhgdt(1), dhgdx(1),
c      &          drofdp(1), drofdt(1),
c      &          dhfdp(1), dhfdt(1)
c
c      EVALUATE PLENUM CONDITIONS AT TIME tsec
c
c      inx = intp(ippl)
c      ityp = itype(ippl)
c      ntps = ntp(ippl)
c      ppl = ppl0*yvalu(ityp,ntps,xtp(inx),ytp(1,ippl),
c      &          ztp(1,ippl),tsec)
c
c      inx = intp(ialpl)
c      ityp = itype(ialpl)
c      ntps = ntp(ialpl)
c      alppl = alppl0*yvalu(ityp,ntps,xtp(inx),ytp(1,ialpl),
c      &          ztp(1,ialpl),tsec)
c
c      inx = intp(itfpl)
c      ityp = itype(itfpl)
c      ntps = ntp(itfpl)
c      tfpl = tfpl0*yvalu(ityp,ntps,xtp(inx),ytp(1,itfpl),

```



```

      &          ztp(1,itfpl),tsec) + convt
c
      inx = intp(itgpl)
      ityp = itype(itgpl)
      ntps = ntp(itgpl)
      tgpl = tgpl0*yvalu(ityp,ntps,xtp(inx),ytp(1,itgpl),
      &          ztp(1,itgpl),tsec) + convt
c
      inx = intp(ixapl)
      ityp = itype(ixapl)
      ntps = ntp(ixapl)
      xapl = xapl0*yvalu(ityp,ntps,xtp(inx),ytp(1,ixapl),
      &          ztp(1,ixapl),tsec)
c
c      DETERMINE DENSITY AND ENTHALPY AT PLENUM
c
      call state (ppl,tgpl,tfpl,xapl,factor,ilq,
      &          1,1,1,1,1,1,1,
      &          rogpl,drogdp,drogdt,drqdx,
      &          hqpl,dhqdp,dhqdt,dhqdx,
      &          rofpl,drofdp,drofdt,
      &          hfpl,dhfdp,dhfdt)
c
c      EVALUATE LIQUID AND GAS INLET FLOWS:
c      (These values are always used for flow initialization purposes
c      regardless of B.C. option selected)
c
      inx = intp(iqfin)
      ityp = itype(iqfin)
      ntps = ntp(iqfin)
      qfin = qfin0*yvalu(ityp,ntps,xtp(inx),ytp(1,iqfin),
      &          ztp(1,iqfin),tsec)
c
      inx = intp(iqgin)
      ityp = itype(iqgin)
      ntps = ntp(iqgin)
      qgin = qgin0*yvalu(ityp,ntps,xtp(inx),ytp(1,iqgin),
      &          ztp(1,iqgin),tsec)
c
c      EVALUATE TANK BOTTOM CONDITIONS AT TIME tsec
c
      inx = intp(iptb)
      ityp = itype(iptb)
      ntps = ntp(iptb)
      ptb = ptb0*yvalu(ityp,ntps,xtp(inx),ytp(1,iptb),
      &          ztp(1,iptb),tsec)
c
      inx = intp(ialtb)
      ityp = itype(ialtb)
      ntps = ntp(ialtb)
      alptb = alptb0*yvalu(ityp,ntps,xtp(inx),ytp(1,ialtb),
      &          ztp(1,ialtb),tsec)
c
      inx = intp(itftb)
      ityp = itype(itftb)
      ntps = ntp(itftb)
      tftb = tftb0*yvalu(ityp,ntps,xtp(inx),ytp(1,itftb),
      &          ztp(1,itftb),tsec) + convt
c
      inx = intp(itgtb)
      ityp = itype(itgtb)
      ntps = ntp(itgtb)
      tgtb = tgtb0*yvalu(ityp,ntps,xtp(inx),ytp(1,itgtb),
      &          ztp(1,itgtb),tsec) + convt

```

```

c
  inx = intp(ixatb)
  ityp = itype(ixatb)
  ntps = ntp(ixatb)
  xatb = xatb0*yvalu(ityp,ntps,xtp(inx),ytp(1,ixatb),
&                  ztp(1,ixatb),tsec)
c
c   DETERMINE DENSITY AND ENTHALPY AT TANK BOTTOM
c
  call state (ptb,tgtb,tftb,xatb,factor,ilq,
&            1,1,1,1,1,1,1,
&            rogtb,drogdp,drogdt,drqdx,
&            hgtb,dhgdp,dhgdt,dhgdx,
&            roftb,drofdp,drofdt,
&            hftb,dhfdp,dhfdt)
c
  return
end

```

C0FCN

```

  subroutine c0fcn(alp,c0b,c0s,c0,cg,ann)
c
c   *****
c   * SUBROUTINE c0fcn                                     *
c   * *                                                    *
c   * This routine computes the distribution coefficient, C0, the *
c   * coefficient of ug in the relative velocity, Cg, and the *
c   * fraction of the two-phase flow in the annular regime, ann. *
c   * Consult TF-23 for more information.                   *
c   * *                                                    *
c   * ARGUMENTS (I=Input, O=Output):                      *
c   * *                                                    *
c   * I alp = void fraction                                *
c   * I c0b = bubbly regime C0                             *
c   * I c0s = slug regime C0                               *
c   * *                                                    *
c   * O c0 = distribution coefficient C0                   *
c   * O cg = coefficient of ug in ur expression           *
c   * O ann = fraction of flow in annular regime          *
c   * *                                                    *
c   * COMMON VARIABLES:                                    *
c   * *                                                    *
c   * I alb2 = bubbly-slug transition point                *
c   * I als2 = pure slug point                             *
c   * I ala2 = slug-annular transition point               *
c   * *                                                    *
c   *****
c
  implicit real (a-h,o-z), integer (i-n)
  parameter (zero=0.0, one=1.0)
c
  include 'knobs.inc'
c
  APPLY FLOW REGIME LOGIC
c
  if (alp .le. alb2) then
c
    ann = zero
    c0 = c0b
    cg = (one - c0*alp)/(one - alp)
c
  else if (alp .le. als2) then
c
    albl = alb2*((als2 - alp)/(als2 - alb2))**expbs

```

```

      als = (alp - alb1)/(one - alb1)
      alb = alp - als
c
      ann = zero
      c0 = (alb/alp)*c0b + (one - alb/alp)*c0s
      cg = (one - c0*alp)/(one - alp)
c
      else if (alp .le. ala2) then
c
        ala1 = ala2*((alp - als2)/(ala2 - als2))**expsa
        als = (alp - ala1)/(one - ala1)
        ala = alp - als
c
        ann = ala/alp
        c0 = (one - ann)*c0s + ann
        cg = (one - c0*alp)/(one - alp)
c
      else
c
        ann = one
        c0 = one
        cg = one
c
      end if
c
      return
      end

```

CDENS

```

      subroutine cdens (qg,dqgdt,vapor,hfc,twalk,tsat,uliq,ugas,
&                      rhog,rhog,condl,cpl,visl,visg,dhy,hfg,
&                      tgas,alfa,docond)
c
c *****
c *
c * SUBROUTINE cdens
c *
c * SUBROUTINE TO CALCULATE CONDENSATION REGIME HEAT FLUXES
c *
c * OUTPUT ARGUMENTS:
c *   qg - SURFACE HEAT FLUX TO GAS, W/m**2
c *   dqgdt - DERIVATIVE OF GAS HEAT FLUX WITH RESPECT TO
c *           WALL TEMPERATURE
c *   vapor - VAPOR GENERATION RATE, kg/m**2-s
c *   hcon - HEAT TRANSFER COEFFICIENT
c *
c * INPUT ARGUMENTS:
c *   twalk - WALL TEMPERATURE, K
c *   uliq - liquid phasic velocity, m/sec
c *   ugas - gas phasic velocity, m/sec
c *   alfa - void fraction
c *   rhog - LIQUID DENSITY, kg/m**3
c *   rhog - GAS DENSITY, kg/m**3
c *   condl - LIQUID THERMAL CONDUCTIVITY, W/m-C
c *   cpl - LIQUID HEAT CAPACITY, J/kg-C
c *   cpg - GAS HEAT CAPACITY, J/kg-C
c *   visl - LIQUID VISCOSITY, kg/m-s
c *   visg - GAS VISCOSITY, kg/m-s
c *   dhy - CELL HYDRAULIC DIAMETER, m
c *   hfg - LATENT HEAT OF VAPORIZATION, J/kg
c *   docond - LOGICAL FLAG TO INDICATE CALCULATION OF TERMS
c *            IN CORRELATION THAT ARE CONSTANT FOR FLUID CELL
c *
c *****

```

```

      implicit real (a-h,o-z), integer (i-n)
      real jl, jg, jlmin, jgmin

c
      parameter (one=1.0, g=9.80665)

c
c      CORRELATION PARAMETERS
c
      parameter (coef1=1.1025, coef2=0.3333, jlmin=0.0001)
      parameter (coef3=0.0430, coef4=0.0396, jgmin=0.0001)

c
      logical docond
      save hcon

c
c      CALCULATE CONSTANT VALUES FOR FLUID CELL
c
      if (docond) then
         jl = max(abs((one - alfa)*uliq), jlmin)
         term = g*(rho1 - rhog)/(dhy*jl*visl)
         hcon1 = coef1*condl*(term**coef2)

c
         jg = max(abs(alfa*ugas), jgmin)
         prl = cpl*visl/condl
         reg = dhy*jg*rhog/visg
         tau = coef4*rhog*jg*jg/sqrt(sqrt(reg))
         hcon2 = coef3*condl*sqrt(rhol*prl*tau)/visl

c
         hcon = max(hcon1,hcon2)
         docond = .false.
      end if

c
c      CALCULATE TOTAL HEAT FLUXES AND DERIVATIVES
c
      qfc = hfc*(twalk - tgas)
      qcon = hcon*(twalk - tsat)
      qg = qcon + qfc
      dqgdt = hcon + hfc
      vapor = qcon/hfg

c
      return
      end

```

CHEN

```

      subroutine chen (qflux,dqdtw,vapor,qchf,tchf,hfc,twall,tliq,
&                    tgas,tsat,pres,alfa,beta,xair,gliq,ggas,rhol,
&                    rhog,visl,visg,condl,cpl,dhy,hfg,hlsat,hgsat,
&                    sigma,dochen,dochf,ichf,ilq)

c
c      *****
c      *
c      * SUBROUTINE chen
c      *
c      * SUBROUTINE TO CALCULATE NUCLEATE BOILING AND SUBCOOLED
c      * NUCLEATE BOILING SURFACE HEAT FLUXES USING THE CHEN
c      * CORRELATION
c      *
c      * OUTPUT ARGUMENTS:
c      *   qflux - SURFACE HEAT FLUX, W/m**2
c      *   dqdtw - DERIVATIVE OF HEAT FLUX WITH RESPECT TO WALL
c      *             TEMPERATURE
c      *   vapor - VAPOR GENERATION AT WALL, kg/m**2-s
c      *   qchf - CRITICAL HEAT FLUX, W/m**2
c      *   tchf - TEMPERATURE WHERE qchf IS REACHED, K
c      *   hfc - FORCED CONVECTION OR SINGLE PHASE LIQUID
c      *             HEAT TRANSFER COEFFICIENT, W/m**2-K
c      *
c      *****

```

```

C      *
C      * INPUT ARGUMENTS:
C      *      twall - WALL TEMPERATURE, K
C      *      tliq - LIQUID TEMPERATURE, K
C      *      tgas - GAS TEMPERATURE, K
C      *      tsat - SATURATION TEMPERATURE, K
C      *      pres - CELL PRESSURE, Pa
C      *      gliq - LIQUID MASS FLUX, kg/m**2-s
C      *      ggas - GAS MASS FLUX, kg/m**2-s
C      *      rho1 - LIQUID DENSITY, kg/m**3
C      *      rho2 - GAS DENSITY, kg/m**3
C      *      vis1 - LIQUID VISCOSITY, kg/m-s
C      *      vis2 - GAS VISCOSITY, kg/m-s
C      *      cond1 - LIQUID THERMAL CONDUCTIVITY, W/m-C
C      *      cpl - LIQUID SPECIFIC HEAT, J/kg-C
C      *      dhy - CELL HYDRAULIC DIAMETER, m
C      *      hfg - LATENT HEAT OF VAPORIZATION, J/kg
C      *      sigma - SURFACE TENSION, N/m
C      *
C      *****
C      implicit real (a-h,o-z), integer (i-n)
C      logical dochen, dochf
C
C      parameter (zero=0.0, one=1.0, oneh=100.0, toler=1.0)
C      parameter (rg=8314.0, rnul=4.0)
C      parameter (tcmin=273.15, tcmax=647.15)
C
C      SINGLE PHASE HEAT TRANSFER PARAMETERS
C
C      parameter (cdb=0.023, pt8=0.80, pt4=0.40)
C
C      CHEN CORRELATION PARAMETERS
C
C      parameter ( xml=0.900,  xm2=0.100)
C      parameter ( cf1=2.351,  xf1=0.736,  cnb=1.22e-3)
C      parameter ( cf2=0.213,  xf2=1.250,  cre=1.00e-4)
C      parameter ( cs1=0.120,  xs1=1.140,  retp1=32.5)
C      parameter ( cs2=0.420,  xs2=0.780,  retp2=50.9)
C      parameter (xnb1=0.240, xnb2=0.210,  xnb3=0.750, xnb4=1.240)
C
C      dimension ws(2)
C      data wa/28.97/, ws(1)/18.016/, ws(2)/20.034/
C      data itmax/10/
C
C      if (gliq.eq.zero .or. twall.eq.tliq) return
C
C      if (dochen) then
C
C      CALCULATE FLUID CELL PROPERTIES
C
C          re = gliq*dhy/vis1
C          pr = cpl*vis1/cond1
C          rhor = rho1/rho2
C
C      CALCULATE INVERSE MARTINELLI FACTOR
C
C          xtti = ((ggas/gliq)**xm1)*sqrt(rhor)*((vis2/vis1)**xm2)
C          xtti = min(xtti,oneh)
C
C      DETERMINE REYNOLDS NUMBER FACTOR
C
C          if (tliq.lt.tsat) then
C              f = one
C              retp = re

```

```

      else if (xtti.lt.xm2) then
        f = one
        retp = cre*re
      else
        f = cf1*((xtti + cf2)**xf1)
        retp = cre*re*(f**xf2)
      end if

c
c   DETERMINE SUPPRESSION FACTOR
c
      if (retp.lt.retp1) then
        s = one/(one + cs1*(retp**xs1))
      else if (retp.lt.retp2) then
        s = one/(one + cs2*(retp**xs2))
      else
        s = xm2
      end if

c
c   COLLECT TERMS OF LIKE POWERS IN CHEN CORRELATION
c   (EVALUATE FLUID PROPERTIES AT SATURATION CONDITIONS)
c
      if (tliq.lt.tsat) then
        xstm = one - xair
        pstm = pres*xstm*wa/(xstm*wa + xair*ws(ilq))
        pair = pres - pstm

c
        call rsteam (pstm,tsat,ilq,rhos,dx,dx)
        call rofsat (tsat,ilq,rhols,dx)
        call surten (tsat,sigmas)
        call cond1q (tsat,ilq,condls,dx)
        call vis1q (tsat,ilq,visls,dx)
        call cplq (tsat,ilq,cpls)

c
        rhoa = pair*wa/(rg*tsat)
        rhogs = rhoa + rhos

c
        term1 = cpls*rhols/(hfg*rhogs)
        term2 = sqrt(rhols)/(visls*sigmas)
        cond = condls
        prn = cpls*visls/condls
      else
        term1 = cpl*rhor/hfg
        term2 = sqrt(rhol)/(visl*sigma)
        cond = condl
        prn = pr
      end if

c
c   CALCULATE HEAT TRANSFER COEFFICIENTS
c
      rnut = cdb*f*(re**pt8)*(pr**pt4)
      rnu = max(rnut,rnul)
      hfc = condl*rnu/dhy
      hlnb = cnb*s*cond*(term1**xnb1)*(prn**xnb2)*sqrt(term2)

c
c   CALCULATE ROUHANI EVAPORATION PARAMETER
c
      call hfluid (pres,tliq,hlsat,dx,hf,dx,dx)
      evap = hfg/(hfg + rhor*(hlsat - hf))

c
      call psat (tsat,ilq,pssat,dpsdt)

c
      dochen = .false.
    end if

```

```

        iter = -1
        tsurf = twall
c
10      iter = iter + 1
c
c      DETERMINE CELL PROPERTIES
c
        call psat (tsurf, ilq, pwsat, dpsdt)
        delp = pwsat - pssat
        delt = tsurf - tsat
c
c      CALCULATE SINGLE PHASE AND NUCLEATE BOILING
c      SURFACE HEAT FLUXES
c
        qspl = hfc*(tsurf - tliq)
        if (qspl.le.zero .or. delt.le.zero) then
            qnb = zero
            dqnb = zero
        else
            qnb = hlnb*(delt**xnb4)*(delp**xnb3)
            dqnb = qnb*(xnb4/delt + xnb3*dpsdt/delp)
        end if
c
        qsurf = qspl + qnb
        dqsurf = hfc + dqnb
c
c      ON FIRST PASS, SAVE TOTAL SURFACE HEAT FLUX, DERIVATIVE WITH
c      RESPECT TO WALL TEMPERATURE, AND VAPOR GENERATION RATE
c
        if (iter.eq.0) then
            qflux = qsurf
            dqdtw = dqsurf
            vapor = evap*qnb/hfg
            if (qflux.le.zero) return
        end if
c
c      COMPUTE qchf ONCE FOR EACH FLUID CELL
c
        if (dochf) then
            call chf (qchf, tliq, tgas, tsat, pres, alfa, beta, ggass, gliq,
&                  rho1, rhog, visl, visg, cond1, cpl, xair, dhy, hfg,
&                  hlsat, hgsat, sigma, ichf, ilq)
            dochf = .false.
        end if
c
c      HAVING FOUND qflux, ITERATIVELY SOLVE FOR tchf
c
        tchf = tsurf + (qchf - qsurf)/dqsurf
        tchf = min(tchf, tcmax)
        tchf = max(tchf, tcmin)
c
        dtchf = abs(tchf - tsurf)
        if (dtchf.le.toler) then
            return
        else if (iter.lt.itmax) then
            tsurf = tchf
            goto 10
        end if
c
        write (*,20) itmax, toler, dtchf
20      format (/, ' newton iteration failed to find tchf',
&            ' within ', i3, ' iterations', /,
&            ' tolerance = ', g12.5, ' error = ', g12.5)
c

```

```

return
end

```

CHF

```

subroutine chf (qchf,tliq,tgas,tsat,pres,alfa,beta,qgas,
6          gliq,rhol,rhog,visl,visg,condl,cpl,xair,
6          dhy,hfg,hlsat,hgsat,sigma,ichf,ilq)
C
C *****
C *
C * SUBROUTINE chf
C *
C * SUBROUTINE TO CALCULATE CRITICAL HEAT FLUX USING BIASI
C * AND MODIFIED ZUBER CORRELATIONS
C *
C * OUTPUT ARGUMENT:
C *   qchf - CRITICAL HEAT FLUX, W/m**2
C *
C * INPUT ARGUMENTS:
C *   tliq - LIQUID TEMPERATURE, K
C *   tgas - GAS TEMPERATURE, K
C *   tsat - SATURATION TEMPERATURE, K
C *   pres - CELL PRESSURE, Pa
C *   alfa - CELL VOID FRACTION
C *   beta - (1.0 - alfa)
C *   qgas - GAS MASS FLUX, kg/m**2-s
C *   gliq - LIQUID MASS FLUX, kg/m**2-s
C *   rhol - LIQUID DENSITY, kg/m**3
C *   rhog - GAS DENSITY, kg/m**3
C *   visl - LIQUID VISCOSITY, kg/m-s
C *   visg - GAS VISCOSITY, kg/m-s
C *   condl - LIQUID THERMAL CONDUCTIVITY, W/m-C
C *   cpl - LIQUID SPECIFIC HEAT, J/kg-C
C *   xair - MASS FRACTION AIR IN GAS PHASE
C *   dhy - CELL HYDRAULIC DIAMETER, m
C *   hfg - LATENT HEAT OF VAPORIZATION, J/kg
C *   hlsat - SATURATED LIQUID ENTHALPY, J/kg
C *   hgsat - SATURATED VAPOR ENTHALPY, J/kg
C *   sigma - SURFACE TENSION, N/m
C *
C *****
C implicit real (a-h,o-z), integer (i-n)
C
C parameter (zero=0.0, one=1.0, ten=10.0, cent=100.0)
C parameter (g=9.8066, convp=1.0e-5)
C parameter (glow=300.0, gmin=200.0)
C
C CRITICAL HEAT FLUX CORRELATION PARAMETERS
C
C parameter (cb1=1.883e7, xb1=1.0/6.0)
C parameter (cb2=3.780e7, xb2=0.600)
C parameter (fp1=0.7249, fp2=0.099, fp3=0.032)
C parameter (hp1=1.1590, hp2=0.149, hp3=0.019, hp4=8.99)
C parameter (xn1=0.4000, xn2=0.600, czb=0.1178)
C
C SRS CORRELATION PARAMETERS
C
C parameter (cs1=5.264e+5, cv1=0.476, ct1=0.031)
C parameter (cs2=2.021e+6, cv2=0.169)
C
C dimension ws(2)
C data wa/28.97/, ws(1)/18.016/, ws(2)/20.034/
C
C BIASI CORRELATION PRESSURE FUNCTION STATEMENTS

```



```

c      fp(p) = +fp1 + p*(fp2*exp(-fp3*p))
c      hp(p) = -hp1 + p*(hp2*exp(-hp3*p) + hp4/(ten + p*p))
c
c      if (ichf.eq.1) then
c          gmix = gliq
c      else
c          gmix = gliq + ggas
c      end if
c
c      FOR LOW FLOWS, USE MODIFIED ZUBER POOL BOILING DNB CORRELATION
c
c      if (gmix.lt.glow) then
c          qchf = czb*beta*hfg*sqrt(rhog*sqrt(g*sigma*(rho1 - rhog)))
c          if (gmix.le.gmin) return
c          qzubr = qchf
c      end if
c
c      FORCED CONVECTION DNB CORRELATIONS
c
c      flow = max(gliq,glow)
c      if (ichf.eq.1) then
c
c          USE SRS CRITICAL HEAT FLUX CORRELATIONS
c
c          vliq = flow/rho1
c          delt = tsat - tliq
c          qsrs1 = cs1*(one + cv1*vliq)*(one + ct1*delt)
c          qsrs2 = cs2*(one + cv2*vliq)
c          qchf = max(qsrs1,qsrs2)
c      else
c
c          USE BIASI FORCED-CONVECTION DNB CORRELATION:
c          CALCULATE PARTIAL PRESSURE OF AIR
c
c          xstm = one - xair
c          pair = pres*xair/(xair + xstm*wa/ws(ilq))
c
c          EVALUATE AIR, STEAM, AND LIQUID ENTHALPIES (hair, hstm, hf)
c
c          call air (pair,tgas,roa,dx,dx,hair,dx,dx)
c          call hsteam (tgas,tsat,dx,hgsat,dx,ilq,hstm,dx,dx)
c          call hfluid (pres,tliq,hlsat,dx,hf,dx,dx)
c
c          CALCULATE EQUILIBRIUM QUALITY
c
c          hgas = xair*hair + xstm*hstm
c          alrg = alfa*rhog
c          alrl = beta*rho1
c          hmix = (alrg*hgas + alrl*hf)/(alrg + alrl)
c          xe = (hmix - hlsat)/hfg
c
c          dhcm = cent*dhy
c          if (dhcm.ge.one) then
c              xde = xn1
c          else
c              xde = xn2
c          end if
c
c          pbar = convp*pres
c          gcgs = flow/ten
c
c          gl6 = one/(r,cgs**xb1)
c          rden = one/(dhcm**xde)

```

```

      qchf1 = cb1*rden*(fp(pbar)*g16 - xe)*g16
      qchf2 = cb2*rden*(hp(pbar)*(one - xe)/(gcgs**xb2))
      qchf = max(qchf1,qchf2)
    end if
  c
    if (gmix.lt.glow) then
  c
  c    INTERPOLATE BETWEEN HIGH AND LOW FLOW CORRELATIONS
  c
      qchf = qzubr + (gmix - gmin)*(qchf - qzubr)/(glow - gmin)
    end if
  c
    return
  end

```

CHLSKI

```

      subroutine chlski (amat,nr,nr1,bvct)
  c
  c *****
  c *
  c *          SUBROUTINE chlski:
  c *
  c *          SOLVES AC=X FOR C BY THE CHOLESKY'S METHOD
  c *          WHERE THE SOLUTION VECTOR, C, IS PLACED IN
  c *          THE VECTOR X ON RETURN.
  c *
  c *****
  c
    implicit real (a-h,o-z), integer (i-n)
    parameter (zero=0.0, maxp=25, maxpl=maxp+1)
    dimension amat(maxp,maxpl), bvct(maxp)
  c
  c    CALCULATE FIRST ROW OF UPPER UNIT TRIANGULAR MATRIX.
  c
    do 3 j=2,nr1
      amat(1,j) = amat(1,j)/amat(1,1)
3    continue
  c
  c    CALCULATE OTHER ELEMENTS OF U AND L MATRICES.
  c
    do 8 i=2,nr
      j = 1
      do 5 ii=j,nr
        sum = zero
        jml = j - 1
        do 4 k=1,jml
          sum = sum + amat(ii,k)*amat(k,j)
4        continue
        amat(ii,j) = amat(ii,j) - sum
5      continue

      ipl = i + 1
      do 7 jj=ipl,nr1
        sum = zero
        iml = i - 1
        do 6 k=1,iml
          sum = sum + amat(i,k)*amat(k,jj)
6        continue
        amat(i,jj) = (amat(i,jj) - sum)/amat(i,i)
7      continue
8    continue

    SOLVE FOR bvct(i) BY BACK SUBSTITUTION.
  c
  c
  c

```

```

      bvct(nr) = amat(nr,nr+1)
      l = nr - 1
      do 10 nn=1,l
        sum = zero
        i = nr - nn
        ipl = i + 1
        do 9 j=ipl,nr
          sum = sum + amat(i,j)*bvct(j)
        9 continue
        bvct(i) = amat(i,nr1) - sum
      10 continue
c
      return
      end

```

CHP

```

      subroutine chp(x,x1,x2,y,dydx)
c
c *****
c * Cubic Hermitian Polynomial Subroutine *
c * - - - - - *
c * *
c * The function below smoothly transitions between 0 and 1. The *
c * function and first derivative are continuous (C1 continuity). *
c * The mid-portion of the composite function is a cubic *
c * Hermitian polynomial. *
c * *
c * { 0 x <= x1 *
c * { 2 x1 < x < x2 *
c * { 3 ( x - x1 ) ( x - x1 ) *
c * y = { 3(-----) - 2(-----) *
c * { ( x2 - x1 ) ( x2 - x1 ) *
c * { 1 x >= x2 *
c * *
c * { 0 x <= x1 *
c * { *
c * dy { ( x - x1 ) ( x - x1 ) *
c * -- = { 6(-----) [1 - (-----)] x1 < x < x2 *
c * dx { ( x2 - x1 ) ( x2 - x1 ) *
c * { *
c * { 0 x >= x2 *
c *****
c
      implicit real (a-h,o-z), integer (i-n)
      parameter (zero=0.0, one=1.0, two=2.0, three=3.0, six=6.0)
c
      if (x .ge. x2) then
        y = one
        dydx = zero
c
      else if (x .gt. x1) then
        arg = (x - x1)/(x2 - x1)
        y = three*(arg)**2 - two*(arg)**3
        dydx = six*arg*(one - arg)
c
      else
        y = zero
        dydx = zero
c
      end if
c
      return

```

end

CIA

```

real function cia(aia,alpha,del,flowa,pia,rhog,urabs,visg)

c
c *****
c *
c * FUNCTION cia
c *
c * THIS FUNCTION COMPUTES THE GENERALIZED INTERFACIAL
c * FRICTION COEFFICIENT FOR THE ANNULAR FLOW REGIME.
c *
c * ARGUMENTS (O=Output, I=Input):
c *
c * O cia - generalized interfacial friction coefficient,
c *       A      1
c *       -i * f * - * rhog      (kg/m^4)
c *       V      i 2
c *
c * I aia - interfacial area per unit volume (m^-1)
c * I alpha - void fraction
c * I del - film thickness (m)
c * I flowa - flow area (m^2)
c * I pia - interfacial perimeter (m)
c * I rhog - gas density (kg/m^3)
c * I urabs - absolute relative velocity (m/s)
c * I visg - gas dynamic viscosity
c *
c *****
c
implicit real (a-h,o-z), integer (i-n)
real mgplus
parameter (zero=0.0, half=0.5, one=1.0, two=2.0, four=4.0)
parameter (c1=0.046, c2=-0.20, c3=0.045, c4=5.9, regmin=0.01)

c
c PRODUCT OF HALF THE GAS DENSITY AND INTERFACIAL AREA
c
factor=half*rhog*aia

c
c COMPUTE THE GAS PHASE FRICTION FACTOR FOR A SMOOTH PIPE
c
reg=four*alpha*flowa*rhog*urabs/visg/pia
if (reg .ge. regmin) then
  fs = c1*reg**c2
else
  cia = factor*(c1*regmin**c2)
  return
end if

c
c COMPUTE THE FILM REYNOLDS NUMBER
c
rem = del*rhog*urabs/visg

c
c SOLVE QUADRATIC EQUATION FOR sqrt(fr)
c
b = -c3*rem/sqrt(two)*fs
c = -(one - c3*c4)*fs
sqrtfr = half*(-b + sqrt(b**2 - four*c))

c
c DETERMINE IF fr IS IN SMOOTH OR RIPPLE REGIME
c
mgplus = rem/sqrt(two)*sqrtfr
fr = fs*max(one, one + c3*(mgplus - c4))
cia = factor*fr

```

```

c
      return
      end

```

CLEAR

```

      subroutine clear (ax,nx)

c
c *****
c *
c *   subroutine clear
c *
c *   ROUTINE TO SET ALL VALUES IN A REAL ARRAY TO ZERO
c *
c *   INPUT ARGUMENTS:
c *       ax = REAL ARRAY TO BE CLEARED
c *       nx = DIMENSION OF x
c *
c *****
      implicit real (a-h,o-z), integer (i-n)
      parameter (zero=0.0)
      dimension ax(nx)

c
      do 10 ix=1,nx
         ax(ix) = zero
10    continue
c
      return
      end

```

CLEAR1

```

      subroutine clear1 (ax,nx)

c
c *****
c *
c *   subroutine clear1
c *
c *   ROUTINE TO SET ALL VALUES IN A REAL ARRAY TO ONE
c *
c *   INPUT ARGUMENTS:
c *       ax = REAL ARRAY TO BE CLEARED
c *       nx = DIMENSION OF x
c *
c *****
      implicit real (a-h,o-z), integer (i-n)
      parameter (one=1.0)
      dimension ax(nx)

c
      do 10 ix=1,nx
         ax(ix) = one
10    continue
c
      return
      end

```

CONDLQ

```

      subroutine condlq(t,l,condl,dcdt)

c
c *****
c *
c *   INPUT:
c *       t = TEMPERATURE IN K
c *       l = IDENTIFIER (l=1 FOR H2O, l=2 FOR D2O)
c *
c *****

```

```

c      * OUTPUT:
c      *      cond1 = THERMAL CONDUCTIVITY OF SATURATED LIQUID (W/m-K)
c      *      dcdt = DERIVATIVE OF THERMAL CONDUCTIVITY WITH RESPECT TO
c      *              TEMPERATURE
c      *
c      *      RANGE:
c      *      10C < t < 300C
c      *
c      *****
c
c      parameter (tconv=273.15)
c      dimension c1(2), c2(2), c3(2), c4(2), c3x2(2), c4x3(2)
c
c      H2O PROPERTIES
c
c      data c1(1)/ 0.57032432e+0/, c2(1)/0.17996615e-2/,
c      *      c3(1)/-0.72881959e-5/, c4(1)/0.32412245e-8/
c      data c3x2(1)/-1.45763918e-5/, c4x3(1)/0.97236735e-8/
c
c      D2O PROPERTIES
c
c      data c1(2)/ 0.56340135e+0/, c2(2)/0.14504443e-2/,
c      *      c3(2)/-0.79650470e-5/, c4(2)/0.71584948e-8/
c      data c3x2(2)/-1.59300940e-5/, c4x3(2)/2.14754844e-8/
c
c      tinc = t - tconv
c      cond1 = c1(1) + (c2(1) + (c3(1) + c4(1)*tinc)*tinc)*tinc
c      dcdt = c2(1) + (c3x2(1) + c4x3(1)*tinc)*tinc
c
c      return
c      end

```

COND T

```

function cond t (mat,t,wtpc)
c
c      *****
c      *
c      *      FUNCTION COND T:  THIS FUNCTION RETURNS THERMAL CONDUCTIVITY
c      *                          OF THE MATERIAL INDICATED BY mat AT THE
c      *                          TEMPERATURE t IN UNITS OF W/m-K.
c      *                          FOR ALLOYS, WTPC GIVES EITHER
c      *                          THE WEIGHT PERCENT LITHIUM IN ALUMINUM OR
c      *                          THE WEIGHT PERCENT URANIUM IN ALUMINUM
c      *
c      *      THE FOLLOWING MATERIALS ARE AVAILABLE:
c      *          1 - URANIUM
c      *          2 - ALUMINUM
c      *          3 - 304L STAINLESS STEEL
c      *          4 - LITHIUM-ALUMINUM ALLOY
c      *          5 - URANIUM-ALUMINUM ALLOY
c      *          6 - ALUMINUM 6063
c      *          7 - MACOR
c      *          8 - INCONEL 600
c      *          9 - FLAME SPRAYED OXIDE
c      *
c      *****
c
c      implicit real(a-h,o-z), integer(i-n)
c      parameter (one=1.0)
c      dimension coef(36), clial(2), cual(3)
c
c      include 'knobs.inc'
c
c      THERMAL CONDUCTIVITY COEFFICIENTS (BTU/FT-S-F)

```

```

C
      data coef/4.3348290e-03,3.1175360e-06, 8.8954201e-10,0.000000e-00,
&      3.7868370e-02,1.0550300e-05,-4.8345810e-08,3.531802e-11,
&      2.3722218e-03,2.4960340e-06,-5.9524200e-10,0.000000e-00,
&      7.5633460e-03,0.0000000e-00, 0.0000000e-00,0.000000e-00,
&      3.5700000e-02,5.3000000e-06,-2.2000000e-08,0.000000e-00,
&      0.0322      ,0.0      , 0.0      ,0.0      ,
&      2.7e-4      ,0.0      , 0.0      ,0.0      ,
&      2.38e-3     ,0.0      , 0.0      ,0.0      ,
&      3.4e-4      ,0.0      , 0.0      ,0.0      /

C
C      ALLOY WEIGHT PERCENT COEFFICIENTS
C
      data clial/ 3.130461e-02, 1.281840e-00/
      data cual/-5.69000e-04, 4.500000e-06, 1.90000e-07/

C
C      CONVERSION FACTOR FOR THERMAL CONDUCTIVITY TO SI UNITS
C
      data csik/6.230645e+03/

C
C      CALCULATE THERMAL CONDUCTIVITY IN ENGLISH UNITS
C
      mf = 4*mat - 3
      cond = coef(mf) + (coef(mf+1) + (coef(mf+2) + coef(mf+3)*t)*t)*t

C
C      INCLUDE FUNCTIONS OF WEIGHT PERCENT ALUMINUM FOR ALLOYS
C
      if (mat.eq.4) then
        cond = cond + clial(1)/(one + clial(2)*wtpc)
      else if (mat.eq.5) then
        cond = cond + (cual(1) + cual(2)*wtpc + cual(3)*t)*wtpc
      end if

C
C      CONVERT THERMAL CONDUCTIVITY TO SI UNITS
C      NOTE: xkmet IS A SENSITIVITY MULTIPLIER
C
      cond = xkmet*csik*cond

C
      return
      end

```

CONLAW

```

      subroutine conlaw (p,tg,tf,xa,l,n,nz,visg,cpg,condg,diffm,
&      visl,cpl,condl,sigma)

C
C      *****
C      *
C      * INPUT:
C      *   p = MIXTURE PRESSURE IN Pa
C      *   tg = GAS TEMPERATURE IN K
C      *   tf = LIQUID TEMPERATURE IN K
C      *   xa = MASS FRACTION OF AIR IN MIXTURE
C      *   l = IDENTIFIER (l=1 FOR H2O, l=2 FOR D2O)
C      *
C      * OUTPUT:
C      *   visg = DYNAMIC VISCOSITY OF AIR-STEAM GAS MIXTURE IN Pa-s
C      *   cpg = SPECIFIC HEAT OF AIR-STEAM GAS MIXTURE IN J/kg-K
C      *   condg = THERMAL CONDUCTIVITY OF AIR-STEAM GAS MIXTURE IN W/m-K*
C      *   diffm = BINARY A-B MASS DIFFUSIVITY, m^2/s,
C      *           WHERE A IS WATER VAPOR AND B IS AIR
C      *   visl = DYNAMIC VISCOSITY OF SATURATED LIQUID H2O OR D2O
C      *           IN Pa-s
C      *   cpl = SPECIFIC HEAT OF SATURATED LIQUID H2O OR D2O IN J/kg-K*
C      *   condl = THERMAL CONDUCTIVITY OF SATURATED LIQUID H2O OR D2O

```

```

C      *          IN W/m-K                      *
C      *  sigma = SURFACE TENSION OF LIQUID H2O OR D2O IN N/m  *
C      *                                                         *
C      *****
C
C      parameter (one=1.0, two=2.0, tconv=273.15)
C
C      dimension  p(nz),  tg(nz),  tf(nz),  xa(nz),
&               visg(nz), cpg(nz), condg(nz), diffm(nz),
&               visl(nz), cpl(nz), condl(nz), sigma(nz)
C
C      dimension  rs(2), cs1(2), cs2(2), cs3(2), cs4(2), cs5(2), cs6(2),
&               cs7(2), cs8(2), ds1(2), ds2(2), ds3(2), ds4(2), c1(2),
&               c2(2), c3(2), c7(2), c8(2), c9(2), c10(2), c11(2),
&               c12(2)
C
C----- AIR PROPERTIES:
C
C      AIR VISCOSITY, HEAT CAPACITY, & CONDUCTIVITY DATA (RESPECTIVELY)
C      data ca1/145.8e-8/, ca2/110.4/
C      data ca4/1005.9/, ca5/-8.6140e-2/, ca6/2.6295e-4/
C      data da1/3.3350e-3/, da2/8.0021e-5/, da3/-1.8975e-8/
C
C----- H2O PROPERTIES:
C
C      data rs(1)/461.0/
C
C      STEAM VISCOSITY, HEAT CAPACITY & CONDUCTIVITY DATA (RESPECTIVELY)
C      data cs1(1)/8.04e-6/,  cs2(1)/4.07e-8/,
&      cs3(1)/1.858e-7/,  cs4(1)/5.9e-10/
C      data cs5(1)/1901.4/,  cs6(1)/-0.62129/,
&      cs7(1)/1.9538e-3/,  cs8(1)/-1.0083e-6/
C      data ds1(1)/1.76e-2/,  ds2(1)/5.87e-5/,
&      ds3(1)/1.04e-7/,  ds4(1)/-4.51e-11/
C
C      LIQUID VISCOSITY, HEAT CAPACITY & CONDUCTIVITY DATA (RESPECTIVELY)
C      data c1(1)/2.41277e-5/, c2(1)/574.268/, c3(1)/139.16/
C      data c7(1)/3960.2/, c8(1)/0.36868/
C      data c9(1)/ 0.57032432e+0/, c10(1)/0.17996615e-2/,
&      c11(1)/-0.72881959e-5/, c12(1)/0.32412245e-8/
C
C----- D2O PROPERTIES:
C
C      data rs(2)/415.0/
C
C      STEAM VISCOSITY, HEAT CAPACITY & CONDUCTIVITY DATA (RESPECTIVELY)
C      data cs1(2)/8.3224e-6/,  cs2(2)/4.1550e-8/,
&      cs3(2)/0.0/,  cs4(2)/0.0/
C      data cs5(2)/1611.4/,  cs6(2)/3.6681e-3/,
&      cs7(2)/1.3023e-3/,  cs8(2)/-6.6266e-7/
C      data ds1(2)/1.7880e-2/,  ds2(2)/5.1209e-5/,
&      ds3(2)/1.1218e-7/,  ds4(2)/0.0/
C
C      LIQUID VISCOSITY, HEAT CAPACITY & CONDUCTIVITY DATA (RESPECTIVELY)
C      data c1(2)/3.34625e-5/, c2(2)/490.126/, c3(2)/157.884/
C      data c7(2)/4340.2/, c8(2)/-0.20733/
C      data c9(2)/ 0.56340135e+0/, c10(2)/0.14504443e-2/,
&      c11(2)/-0.79650470e-5/, c12(2)/0.71584948e-8/
C
C----- COMMON PROPERTIES TO H2O & D2O
C
C      SURFACE TENSION (SAME FOR H2O & D2O)
C      data c13/+0.75743910e-1/, c14/-0.14302481e-3/,
&      c15/-0.29108772e-6/, c16/+0.28387790e-9/

```



```

C
C   DIFFUSIVITY PARAMETERS (ASSUMED SAME FOR H2O & D2O)
C   data convrt/1.01325e-4/, al/0.187/, sl/2.072/, ah/2.75/, sh/1.632/
C
C   do 100 j = n,nz
C
C   AIR TRANSPORT PROPERTIES
C
C       visa = cal*(sqrt(tg(j)))*3/(tg(j) + ca2)
C       conda = dal + (da2 + da3*tg(j))*tg(j)
C       cpa = ca4 + (ca5 + ca6*tg(j))*tg(j)
C
C   STEAM TRANSPORT PROPERTIES
C
C       ros = p(j)/(rs(1)*tg(j))
C       tinc = tg(j) - tconv
C       viss = cs1(1) + cs2(1)*tinc - ros*(cs3(1) - cs4(1)*tinc)
C       conds = (dsl(1) + (ds2(1) + (ds3(1) + ds4(1)*tinc)*tinc)*tinc)
C       cps = cs5(1) + (cs6(1) + (cs7(1) + cs8(1)*tg(j))*tg(j))*tg(j)
C
C   GAS TRANSPORT PROPERTIES - WEIGHT BY MASS FRACTION
C
C       xs = one - xa(j)
C       visg(j) = xa(j)*visa + xs*viss
C       condg(j) = xa(j)*conda + xs*conds
C       cpj(j) = xa(j)*cpa + xs*cps
C
C   LIQUID TRANSPORT PROPERTIES
C
C       tinc = tf(j) - tconv
C       visl(j) = c1(1)*exp(c2(1)/(tf(j) - c3(1)))
C       cpl(j) = c7(1) + two*c8(1)*tf(j)
C       condl(j) = c9(1) + (c10(1) + (c11(1) + c12(1)*tinc)*tinc)*tinc
C
C   SURFACE TENSION
C
C       sigma(j) = c13 + (c14 + (c15 + c16*tinc)*tinc)*tinc
C
C   MASS DIFFUSIVITY
C
C       diffm(j) = min(al*(tg(j)**sl)*convrt/p(j),
C   &               ah*(tg(j)**sh)*convrt/p(j))
C
C   100 continue
C
C   return
C   end

```

CONST

```

subroutine const (ptn,alptn,tgtn,tftn,xatn,rogt,roftn,volt,
&                pn ,alpn ,tgn ,tfn ,xan ,rogn ,rofn ,volc,
&                pbn,alpbn,tgbn,tfbn,xabn,rogbn,rofbn,volb,
&                ugt,uft,act,defft,dht,cost,fldmt,fldct,
&                c0bt,c0st,ckbt,ckst,
&                ugz,ufz,acz,deffz,dhz,cosz,fldmz,fldcz,
&                c0bz,c0sz,ckbz,cksz,
&                ugb,ufb,acb,deffb,dhb,cosb,fldmb,fldcb,
&                c0bb,c0sb,ckbb,cksb,
&                hgit,hfit,akgit,ysit,citn,
&                hgl ,hfl ,akgl ,ysl ,cizn,cixn,
&                hgib,hfib,akgib,ysib,cibn,
&                ppln,alppln,tgpln,tfpln,xapln,
&                rogpln,rofpln,volpl,
&                ptbn,alptbn,tgtbn,tftbn,xatbn,

```

```

&          rogtbn, roftbn, voltb, cidamp,
&          nzt, nzp1, nzp2, nzp3, nxmax, nx, nchn, nzb, dtprev, ilq)
C
C *****
C * Interfacial Constitutive Laws *
C * *
C * *
C *****
C implicit real (a-h,o-z), integer (i-n)
C parameter (zero=0.0, half=0.5, one=1.0, two=2.0)
C include 'knobs.inc'
C
C TOP SECTION ARRAYS
C
C dimension ptn(nzt), alptn(nzt),
&          tgtn(nzt), tftn(nzt), xatn(nzt),
&          rogtn(nzt), roftn(nzt), volt(nzt)
C dimension ugt(nzt), uft(nzt), act(nzt), cost(nzt),
&          defft(nzt), dht(nzt), citn(nzt),
&          hgit(nzt), hfit(nzt), akgit(nzt),
&          fldmt(nzt), fldct(nzt), ysit(nzt),
&          c0bt(nzt), c0st(nzt), ckbt(nzt), ckst(nzt)
C
C MIDDLE SECTION ARRAYS
C
C dimension nx(nchn)
C dimension pn(nzp2,nxmax,nchn), alpn(nzp2,nxmax,nchn),
&          tgn(nzp2,nxmax,nchn), tfn(nzp2,nxmax,nchn),
&          rogn(nzp2,nxmax,nchn), rofn(nzp2,nxmax,nchn),
&          volc(nzp2,nxmax,nchn), xan(nzp2,nxmax,nchn)
C dimension ugz(nzp3,nxmax,nchn), ufz(nzp3,nxmax,nchn),
&          acz(nzp3,nxmax,nchn), deffz(nzp3,nxmax,nchn),
&          dhz(nzp3,nxmax,nchn), fldmz(nzp3,nxmax,nchn),
&          fldcz(nzp3,nxmax,nchn), cosz(nzp3,nxmax,nchn)
C dimension cizn(nzp3,nxmax,nchn), cixn(nzp3,nxmax,nchn),
&          hqi(nzp2,nxmax,nchn), hfi(nzp2,nxmax,nchn),
&          akqi(nzp2,nxmax,nchn), ysi(nzp2,nxmax,nchn),
&          c0bz(nzp3,nxmax,nchn), c0sz(nzp3,nxmax,nchn),
&          ckbz(nzp3,nxmax,nchn), cksz(nzp3,nxmax,nchn)
C
C BOTTOM SECTION ARRAYS
C
C dimension pbn(nzb), alpbn(nzb),
&          tgbn(nzb), tfbn(nzb), xabn(nzb),
&          rogbn(nzb), rofbn(nzb), volb(nzb)
C dimension ugb(nzb), ufb(nzb), acb(nzb), cosb(nzb),
&          deffb(nzb), dhb(nzb), cibn(nzb),
&          hgib(nzb), hfib(nzb), akgib(nzb),
&          fldmb(nzb), fldcb(nzb), ysib(nzb),
&          c0bb(nzb), c0sb(nzb), ckbb(nzb), cksc(nzb)
C
C LOCAL VARIABLES
C
C parameter ( mxnz = 100 )
C dimension pz (mxnz), alpz (mxnz), tgz (mxnz),
&          tfz (mxnz), xaz (mxnz), rogz (mxnz),
&          rofz (mxnz), visg (mxnz), cpg (mxnz),
&          condg (mxnz), visf (mxnz), cpf (mxnz),
&          condf (mxnz), diffm (mxnz), sigma (mxnz),
&          ai (mxnz), vol (mxnz), ysiz (mxnz)
C
C DAMPING FACTORS

```

```

      decay1 = two**(-dtprev/abs(cidamp))
      decay2 = one - decay1
c
c   TOP SECTION Z-MOMENTUM CELLS
c
      do 100 jz=1,nzt
        jzm = jz - 1
c
        if (jz .eq. 1) then
          volm = volpl
          pm = ppln
          alpm = alppln
          tgm = tgpln
          tfm = tfpln
          xam = xapln
          rogm = rogpln
          rofm = rofpln
          ysim = ysit(1)
        else
          volm = volt(jzm)
          pm = ptn(jzm)
          alpm = alptn(jzm)
          tgm = tgtn(jzm)
          tfm = tftn(jzm)
          xam = xatn(jzm)
          rogm = rogtn(jzm)
          rofm = roftn(jzm)
          ysim = ysit(jzm)
        end if
c
        sumv = volm + volt(jz)
        vol(jz) = half*sumv
        fm = volm / sumv
        fp = volt(jz)/sumv
c
c   COMPUTE MOMENTUM CELL VOLUME AVERAGE PROPERTIES
c
        pz(jz) = fm* pm + fp* ptn(jz)
        alpz(jz) = fm*alpm + fp*alptn(jz)
        tgz(jz) = fm* tgm + fp* tgtn(jz)
        tfz(jz) = fm* tfm + fp* tftn(jz)
        xaz(jz) = fm* xam + fp* xatn(jz)
        rogz(jz) = fm*rogm + fp*rogtn(jz)
        rofz(jz) = fm*rofm + fp*roftn(jz)
        ysiz(jz) = fm*ysim + fp* ysit(jz)
c
100    continue
c
      call conlaw (pz,tgz,tfz,xaz,ilq,1,nzt,visg,cpg,condg,
&               diffm,visf,cpf,condf,sigma)
c
      do 105 jz=1,nzt
        jzm = jz - 1
c
        call intara (ai(jz),citemp,akgin,hgin,hfin,
&                  alpz(jz),defft(jz),fldmt(jz),fldct(jz),
&                  c0bt(jz),c0st(jz),ckbt(jz),ckst(jz),
&                  dht(jz),vol(jz),act(jz),cost(jz),rofz(jz),
&                  rogz(jz),sigma(jz),uft(jz),ugt(jz),visf(jz),
&                  visg(jz),pz(jz),tgz(jz),cpf(jz),cpg(jz),
&                  condf(jz),condg(jz),diffm(jz),ysiz(jz),xaz(jz))
c
        citemp = -min(cizfac,zero) + max(cizfac,zero)*citemp
        if (cidamp .ge. zero) then

```

```

      citn(jz) = decay1*citn(jz) + decay2*citemp
    else
      citn(jz) = max(min(citemp,citn(jz)/decay1),citn(jz)*decay1)
    end if

c
    if (jz .gt. 1) then
      hfit(jzm) = hfit(jzm) + half* hfin
      hgit(jzm) = hgit(jzm) + half* hgin
      akgit(jzm) = akgit(jzm) + half*akgin
c
      if (cidamp .ge. zero) then
        hfit(jzm) = decay1* hftop + decay2* hfit(jzm)
        hgit(jzm) = decay1* hgtop + decay2* hgit(jzm)
        akgit(jzm) = decay1*akgtop + decay2*akgit(jzm)
      else
        hfit(jzm) = max(min( hfit(jzm), hftop/decay1),
c          hftop*decay1)
        hgit(jzm) = max(min( hgit(jzm), hgtop/decay1),
c          hgtop*decay1)
        akgit(jzm) = max(min(akgit(jzm),akgtop/decay1),
c          akgtop*decay1)
      end if
    end if

c
    hftop = hfit(jz)
    hgtop = hgit(jz)
    akgtop = akgit(jz)

c
    hfit(jz) = half* hfin
    hgit(jz) = half* hgin
    akgit(jz) = half*akgin

c
105 continue
c
    hfbot = hfib(1)
    hgbot = hgib(1)
    akgbot = akgib(1)

c
c MIDDLE SECTION 2-MOMENTUM CELLS
c
do 220 ic=1,nchn
  nsub = nx(ic)
  do 210 ix=1,nsub
    ysi( 1,ix,ic) = ysit(nzt)
    ysi(nzp2,ix,ic) = ysib(1)
    do 200 jz=2,nzp2
      jzm = jz - 1

c
      sumv = volc(jzm,ix,ic) + volc(jz,ix,ic)
      vol(jz) = half*sumv
      fm = volc(jzm,ix,ic)/sumv
      fp = volc(jz ,ix,ic)/sumv

c
c COMPUTE MOMENTUM CELL VOLUME AVERAGE PROPERTIES
c
      pz(jz) = fm* pn(jzm,ix,ic) + fp* pn(jz,ix,ic)
      alpz(jz) = fm*alpn(jzm,ix,ic) + fp*alpn(jz,ix,ic)
      tqz(jz) = fm* tgn(jzm,ix,ic) + fp* tgn(jz,ix,ic)
      tfz(jz) = fm* tfn(jzm,ix,ic) + fp* tfn(jz,ix,ic)
      xaz(jz) = fm* xan(jzm,ix,ic) + fp* xan(jz,ix,ic)
      rogz(jz) = fm*rogn(jzm,ix,ic) + fp*rogn(jz,ix,ic)
      rofz(jz) = fm*rofn(jzm,ix,ic) + fp*rofn(jz,ix,ic)
      ysiz(jz) = fm* ysi(jzm,ix,ic) + fp* ysi(jz,ix,ic)
c

```

```

200 continue
c
  call conlaw (pz,tgz,tfz,xaz,ilq,2,nzp2,visg,cpg,condg,
  & diffm,visf,cpf,condf,sigma)
c
  do 205 jz=2,nzp2
    jzm = jz - 1
  c
    call intara (ai(jz),citemp,akgin,hgin,hfin,
  & alpz(jz),deffz(jz,ix,ic),fldmz(jz,ix,ic),
  & fldcz(jz,ix,ic),c0bz(jz,ix,ic),c0sz(jz,ix,ic),
  & ckbz(jz,ix,ic),cksz(jz,ix,ic),dhz(jz,ix,ic),
  & vol(jz),acz(jz,ix,ic),cosz(jz,ix,ic),rofz(jz),
  & rogz(jz),sigma(jz),ufz(jz,ix,ic),ugz(jz,ix,ic),
  & visf(jz),visg(jz),pz(jz),tgz(jz),cpf(jz),cpg(jz),
  & condf(jz),condg(jz),diffm(jz),ysiz(jz),xaz(jz))
  c
    citemp = -min(cizfac,zero) + max(cizfac,zero)*citemp
    if (cidamp .ge. zero) then
      cizn(jz,ix,ic) = decay1*cizn(jz,ix,ic) + decay2*citemp
    else
      cizn(jz,ix,ic) = max(min(citemp,cizn(jz,ix,ic)/decay1),
  & cizn(jz,ix,ic)*decay1)
    end if
    cixn(jz,ix,ic) = max(cixfac,zero)
  & - min(cixfac,zero)*cizn(jz,ix,ic)
  c
    hfi(jzm,ix,ic) = hfi(jzm,ix,ic) + half* hfin
    hgi(jzm,ix,ic) = hgi(jzm,ix,ic) + half* hgin
    akgi(jzm,ix,ic) = akgi(jzm,ix,ic) + half*akgin
  c
    if (cidamp .ge. zero) then
      hfi(jzm,ix,ic) = decay1* hfmid + decay2* hfi(jzm,ix,ic)
      hgi(jzm,ix,ic) = decay1* hgmid + decay2* hgi(jzm,ix,ic)
      akgi(jzm,ix,ic) = decay1*akgmid + decay2*akgi(jzm,ix,ic)
    else
      hfi(jzm,ix,ic) = max(min( hfi(jzm,ix,ic), hfmid/decay1),
  & hfmid*decay1)
      hgi(jzm,ix,ic) = max(min( hgi(jzm,ix,ic), hgmid/decay1),
  & hgmid*decay1)
      akgi(jzm,ix,ic) = max(min(akgi(jzm,ix,ic),akgmid/decay1),
  & akgmid*decay1)
    end if
  c
    hfmid = hfi(jz,ix,ic)
    hgmid = hgi(jz,ix,ic)
    akgmid = akgi(jz,ix,ic)
  c
    hfi(jz,ix,ic) = half* hfin
    hgi(jz,ix,ic) = half* hgin
    akgi(jz,ix,ic) = half*akgin
  c
    if (jz .eq. 2) then
      wght = half*volc(1,ix,ic)/volt(nzt)
      hfit(nzt) = hfit(nzt) + wght* hfin
      hgit(nzt) = hgit(nzt) + wght* hgin
      akgit(nzt) = akgit(nzt) + wght*akgin
    c
    else if (jz .eq. nzp2) then
      wght = half*volc(nzp2,ix,ic)/volb(1)
      hfib(1) = wght* hfin
      hgib(1) = wght* hgin
      akgib(1) = wght*akgin
    end if

```

```

c
205    continue
210    continue
220    continue
c
    if (cidamp .ge. zero) then
        hfit(nzt) = decay1* hftop + decay2* hfit(nzt)
        hgit(nzt) = decay1* hgtop + decay2* hgit(nzt)
        akgit(nzt) = decay1*akgtop + decay2*akgit(nzt)
    else
        hfit(nzt) = max(min( hfit(nzt), hftop/decay1),
        &                    hftop*decay1)
        hgit(nzt) = max(min( hgit(nzt), hgtop/decay1),
        &                    hgtop*decay1)
        akgit(nzt) = max(min(akgit(nzt), akgtop/decay1),
        &                    akgtop*decay1)
    end if
c
c    BOTTOM SECTION Z-MOMENTUM CELLS
c
do 300 jz=1,nzb
    jzp = jz + 1
c
    if (jz .eq. nzb) then
        volp = voltb
        pp = ptbn
        alpp = alptbn
        tgp = tgtbn
        tfp = tftbn
        xap = xatbn
        rogp = rogtbn
        rofp = roftbn
        ysip = ysib(nzb)
    else
        volp = volb(jzp)
        pp = pbn(jzp)
        alpp = alpbn(jzp)
        tgp = tgbn(jzp)
        tfp = tfbn(jzp)
        xap = xabn(jzp)
        rogp = rogbn(jzp)
        rofp = rofbn(jzp)
        ysip = ysib(jzp)
    end if
c
    sumv = volb(jz) + volp
    vol(jz) = half*sumv
    fm = volb(jz)/sumv
    fp = volp /sumv
c
c    COMPUTE MOMENTUM CELL VOLUME AVERAGE PROPERTIES
c
    pz(jz) = fm* pbn(jz) + fp* pp
    alpz(jz) = fm*alpbn(jz) + fp*alpp
    tgz(jz) = fm* tgbn(jz) + fp* tgp
    tfz(jz) = fm* tfbn(jz) + fp* tfp
    xaz(jz) = fm* xabn(jz) + fp* xap
    rogz(jz) = fm*rogbn(jz) + fp*rogp
    rofz(jz) = fm*rofbn(jz) + fp*rofp
    ysiz(jz) = fm* ysib(jz) + fp*ysip
c
300    continue
c
    call conlaw (pz,tgz,tfz,xaz,ilq,1,nzb,visg,cpg,condg,

```

```

      diffm,visf,cpf,condf,sigma)
c
      do 305 jz=1,nzb
        jzp = jz + 1
c
        call intara (ai(jz),citemp,akgin,hgin,hfin,
      & alpz(jz),deffb(jz),fldmb(jz),fldcb(jz),
      & c0bb(jz),c0sb(jz),ckbb(jz),cksb(jz),
      & dhb(jz),vol(jz),acb(jz),cosb(jz),rofz(jz),
      & rogz(jz),sigma(jz),ufb(jz),ugb(jz),visf(jz),
      & visg(jz),pz(jz),tgz(jz),cpf(jz),cpg(jz),
      & condf(jz),condg(jz),diffm(jz),ysiz(jz),xaz(jz))
c
        citemp = -min(cizfac,zero) + max(cizfac,zero)*citemp
        if (cidamp .ge. zero) then
          cibn(jz) = decay1*cibn(jz) + decay2*citemp
        else
          cibn(jz) = max(min(citemp,cibn(jz)/decay1),cibn(jz)*decay1)
        end if
c
        hfib(jz) = hfib(jz) + half* hfin
        hgib(jz) = hgib(jz) + half* hgin
        akgib(jz) = akgib(jz) + half*akgin
c
        if (cidamp .ge. zero) then
          hfib(jz) = decay1* hfbot + decay2* hfib(jz)
          hgib(jz) = decay1* hgbot + decay2* hgib(jz)
          akgib(jz) = decay1*akgbot + decay2*akgib(jz)
        else
          hfib(jz) = max(min( hfib(jz), hfbot/decay1), hfbot*decay1)
          hgib(jz) = max(min( hgib(jz), hgbot/decay1), hgbot*decay1)
          akgib(jz) = max(min(akgib(jz),akgbot/decay1),akgbot*decay1)
        end if
c
        if (jz.lt.nzb) then
          hfbot = hfib(jzp)
          hgbot = hgib(jzp)
          akgbot = akgib(jzp)
c
          hfib(jzp) = half* hfin
          hgib(jzp) = half* hgin
          akgib(jzp) = half*akgin
        end if
c
305   continue
c
      return
      end

```

CPGS

```

      subroutine cpgs(t,xa,l,cpg)
c
c *****
c *
c * INPUT:
c *   t = TEMPERATURE IN K
c *   xa = MASS FRACTION OF AIR IN MIXTURE
c *   l = IDENTIFIER (l=1 FOR H2O, l=2 FOR D2O)
c *
c * OUTPUT:
c *   cpg = SPECIFIC HEAT OF AIR-STEAM GAS MIXTURE IN J/kg-K
c *
c * RANGE:
c *   275K < t < 700K
c *****

```

```

c      *      0 < xa < 1
c      *      'low' pressure
c      *
c      *****
c
c      parameter (one=1.0)
c      dimension cs1(2), cs2(2), cs3(2), cs4(2)
c
c      AIR PROPERTIES
c
c      data ca1/1005.9/, ca2/-8.6140e-2/, ca3/2.6295e-4/
c
c      H2O PROPERTIES
c
c      data cs1(1)/1901.4/,      cs2(1)/-0.62129/,
c      &      cs3(1)/1.9538e-3/, cs4(1)/-1.0083e-6/
c
c      D2O PROPERTIES
c
c      data cs1(2)/1611.4/,      cs2(2)/3.6681e-3/,
c      &      cs3(2)/1.3023e-3/, cs4(2)/-6.6266e-7/
c
c      cpa = ca1 + (ca2 + ca3*t)*t
c      cps = cs1(1) + (cs2(1) + (cs3(1) + cs4(1)*t)*t)*t
c
c      WEIGHT BY MASS FRACTION
c
c      cpg = xa*cpa + (one - xa)*cps
c
c      return
c      end

```

CPLQ

```

      subroutine cplq(t,l,cpl)
c
c      *****
c      *
c      *      INPUT:
c      *      t = TEMPERATURE IN K
c      *      l = IDENTIFIER (l=1 FOR H2O, l=2 FOR D2O)
c      *
c      *      OUTPUT:
c      *      cpl = SPECIFIC HEAT OF SATURATED LIQUID H2O
c      *              OR D2O IN J/kg-K
c      *
c      *      RANGE:
c      *      273K < t < 453K
c      *
c      *****
c
c      parameter (two=2.0)
c      dimension c1(2), c2(2)
c
c      H2O PROPERTIES
c
c      data c1(1)/3960.2/, c2(1)/0.36868/
c
c      D2O PROPERTIES
c
c      data c1(2)/4340.2/, c2(2)/-0.20733/
c
c      cpl = c1(1) + two*c2(1)*t
c
c      return

```


end

CRIT

```

subroutine crit (critr,tcrit,termax,lcrit,icrit,ncrit,pkfac,
&               tsec,tsurf,p,tf,ugz,ufz,pt,tft,ugt,uft,pb,
&               tfb,ugb,ufb,tfpl,tsupw,ichks,ichkc,nx,
&               iazl,nazc,nchn,nxmax,nz,nzp1,nzp2,nzp3,nzt,
&               nzb,nsurf,na,napl,icent,iredo,nout,defft,deffz,
&               deffb,fldmt,fldmz,fldmb,fldct,fldcz,fldcb,
&               dxm,dhz,vminz,alpln,rogpln,rofpn,alptn,
&               rogt,roftn,alpn,rogn,rofn,alpb,rogbn,rofbn,
&               alptbn,rogtbn,roftbn,twinst,twhid,ntwhid,
&               ilq)
c
c *****
c *
c * SUBROUTINE crit
c *
c * COMPUTES THE FOLLOWING CRITERION RATIOS:
c *
c * #1 BULK FLUID TEMPERATURE
c * #2 INSTANTANEOUS SURFACE TEMPERATURE (MIDDLE SECTION)
c * #3 TIME-AVERAGED SURFACE TEMPERATURE (MIDDLE SECTION)
c * #4 CCFL
c *
c *****
c
c implicit real (a-h,o-z), integer (i-n)
c real jgstar, jfstar, jgavg, jfavg
c parameter (zero=0.0, half=0.5, one=1.0, ctok=273.15, grav=9.80665)
c
c CRITERIA ARRAYS
c
c dimension critr(ncrit), tcrit(ncrit), ichkc(ncrit),
& lcrit(3,ncrit), pkfac(ncrit)
c
c SURFACE ARRAYS
c
c dimension tsurf(nsurf,na,nz), twhld(nsurf,na,nz), ichks(nsurf),
& iazl(nxmax,nchn), nazc(nxmax,nchn)
c
c FLUID ARRAYS
c
c dimension alptn(nzt), rogt(nzt), roftn(nzt),
& alpb(nzb), rogb(nzb), rofb(nzb)
c
c dimension alpn(nzp2,nxmax,nchn), rogn(nzp2,nxmax,nchn),
& rofn(nzp2,nxmax,nchn)
c
c dimension pt(nzt), tft(nzt), ugt(nzt), uft(nzt),
& pb(nzb), tfb(nzb), ugb(nzb), ufb(nzb)
c
c dimension p(nzp2,nxmax,nchn), tf(nzp2,nxmax,nchn),
& ugz(nzp3,nxmax,nchn), ufz(nzp3,nxmax,nchn),
& nx(nchn)
c
c dimension defft(nzt), fldmt(nzt), fldct(nzt),
& deffb(nzb), fldmb(nzb), fldcb(nzb),
& deffz(nzp3,nxmax,nchn), fldmz(nzp3,nxmax,nchn),
& fldcz(nzp3,nxmax,nchn), dhz(nzp3,nxmax,nchn), dxm(nchn)
c
c data cron/1.0/, croff/100.0/
c
c----- INITIALIZE FLAG INDICATING POWER LEVEL IS TOO LARGE -----

```

```
c
      iredo = 0
      twinst = zero

c
c      DO CRITERIA CHECKING IF CURRENT TIME GREATER THAN
c      CRITICAL SPECIFIED TIME; CONTINUE INITIALIZING
c
      if (tsec .lt. tcmax) return

c
      critr(3) = zero
      ntwhld = ntwhld + 1

c
c      IF CRITERIA CHECKING FOR WALL SATURATION IS ON, LIMIT THE
c      FLUID SATURATION RATIO < 1 TO ACCELERATE ITERATIONS
c
      if (ichkc(2) .eq. 1) then
        crmax = cron
      else
        crmax = croff
      end if

c
c----- TOP SECTION -----
c
      do 10 jz=1,nzt

c
c        COMPUTE CRITERION RATIO #1 (BULK FLUID TEMPERATURE)
c
        tbulk = tft(jz)
        call tsat (pt(jz),ilq,tfsat,xjunk)

c
        ratio = pkfac(1)*(tbulk - tfpl)/(tfsat - tfpl)

c
        if (ratio .gt. critr(1)) then
          tcrit (1) = tsec
          critr (1) = ratio
          lcrit(1,1) = 0
          lcrit(2,1) = 1
          lcrit(3,1) = jz
        end if

c
c        PRINT BULK FLUID TEMPERATURE AND SATURATION TEMPERATURE
c        IF CRITERIA PRINT IS REQUESTED AND CRITERION EXCEEDED
c
        if (lcrit.eq.1 .and. ratio.gt.one) then
          write (nout,15) tsec, jz, tfsat-ctok, tbulk-ctok
          write (*,15) tsec, jz, tfsat-ctok, tbulk-ctok
        end if

c
c        IF CRITERION #1 EXCEEDED,
c        STOP TRANSIENT CALCULATIONS (IF CRITERION #2 CHECKED)
c
        if (ratio .ge. crmax) then
          iredo = 1
          return
        end if

c
c        COMPUTE CRITERION RATIO #4 (CCFL)
c
        jzm = jz - 1
        if (jz .eq. 1) then
          alpm = alppln
          rogm = rogpln
          rofm = rofpln
        else
```

```

      alpm = alptn(jzm)
      rogm = rogtm(jzm)
      rofm = roftn(jzm)
    end if
    facg = sign(half, ugt(jz))
    facf = sign(half, uft(jz))
    if (abs(ugt(jz)) .lt. vminz) facg = half*ugt(jz)/vminz
    if (abs(uft(jz)) .lt. vminz) facf = half*uft(jz)/vminz
    wtgm = half + facg
    wtfm = half + facf
    wtgp = one - wtgm
    wtfp = one - wtfm
    walpg = wtgm*alpm + wtgp*alptn(jz)
    walpf = wtfm*alpm + wtfp*alptn(jz)
    wrog = wtgm*rogm + wtgp*rogtm(jz)
    wrof = wtfm*rofm + wtfp*roftn(jz)

C
    drogd = (wrof - wrog)*grav*defft(jz)
    jgstar = walpg *ugt(jz)*sqrt(wrog/drogd)
    jfstar = (one-walpf)*uft(jz)*sqrt(wrof/drogd)
    if (jfstar.gt. zero .and. jgstar .lt. zero) then
      cn = sqrt(abs(jgstar)) + fldmt(jz)*sqrt(abs(jfstar))
    else
      cn = zero
    end if

C
    ratio = pkfac(4)*cn/fldct(jz)

C
    if (ratio.gt. critr(4)) then
      tcrit (4) = tsec
      critr (4) = ratio
      lcrit(1,4) = 0
      lcrit(2,4) = 1
      lcrit(3,4) = jz
    end if

C
C PRINT NONDIMENSIONAL SUPERFICIAL VELOCITIES
C IF CRITERIA PRINT IS REQUESTED AND CRITERION EXCEEDED
C
    if (lcrit.eq.1 .and. ratio.gt.one) then
      write (nout,25) tsec, jz, jgstar, jfstar
      write (*,25) tsec, jz, jgstar, jfstar
    end if

C
10 continue

C----- MIDDLE SECTION -----
C
do 60 ic=1,nchn
  isrfi = 2*ic - 1 + icent
  isrfo = isrfi + 1
  nsub = nx(ic)

C
do 50 ix=1,nsub
  iazf = iazl(ix,ic)
  iazl = iazf + nazc(ix,ic) - 1

C
do 40 jz=2,nzpl
  jzl = jz - 1

C
C COMPUTE CRITERION RATIO #1 (BULK FLUID TEMPERATURE)
C
  tbulk = tf(jz,ix,ic)
  call tsat (p(jz,ix,ic),ilq,tfsat,xjunk)

```

```

c
      ratio = pkfac(1)*(tbulk - tfpl)/(tfsat - tfpl)
c
      if (ratio.gt.critr(1)) then
        tcrit (1) = tsec
        critr (1) = ratio
        lcrit(1,1) = ic
        lcrit(2,1) = ix
        lcrit(3,1) = jz1
      end if
c
c      PRINT BULK FLUID TEMPERATURE AND SATURATION TEMPERATURE
c      IF CRITERIA PRINT IS REQUESTED AND CRITERION EXCEEDED
c
      if (icrit.eq.1 .and. ratio.gt.one) then
        write (nout,35) tsec, ic, ix, jz1, tfsat-ctok, tbulk-ctok
        write (*,35) tsec, ic, ix, jz1, tfsat-ctok, tbulk-ctok
      end if
c
c      IF CRITERION #1 EXCEEDED,
c      STOP TRANSIENT CALCULATIONS (IF CRITERION #2 CHECKED)
c
      if (ratio .ge. crmax) then
        iredo = 1
        return
      end if
c
c      COMPUTE CRITERION RATIO #4 (CCFL)
c
      if (ix.eq.1 .and. jz.gt.2) then
c
        jgavg = zero
        jfavg = zero
        do 1111 ix=1, nsub
          jzm = jz - 1
          facg = sign(half, ugz(jz,ix,ic))
          facf = sign(half, ufz(jz,ix,ic))
          if (abs(ugz(jz,ix,ic)) .lt. vminz)
            & facg = half*ugz(jz,ix,ic)/vminz
          if (abs(ufz(jz,ix,ic)) .lt. vminz)
            & facf = half*ufz(jz,ix,ic)/vminz
          wtgm = half + facg
          wtfm = half + facf
          wtgp = one - wtgm
          wtfp = one - wtfm
          walpg = wtgm*alpn(jzm,ix,ic) + wtgp*alpn(jz,ix,ic)
          walpf = wtfm*alpn(jzm,ix,ic) + wtfp*alpn(jz,ix,ic)
          wrog = wtgm*rogn(jzm,ix,ic) + wtgp*rogn(jz,ix,ic)
          wrof = wtfm*rofn(jzm,ix,ic) + wtfp*rofn(jz,ix,ic)
          jgavg = jgavg + walpg *ugz(jz,ix,ic)
          jfavg = jfavg + (one-walpf)*ufz(jz,ix,ic)
1111 continue
c
        drogd = (wrof - wrog)*grav*deffz(jz,ix,ic)
        jgstar = jgavg/float(nsub)*sqrt(wrog/drogd)
        jfstar = jfavg/float(nsub)*sqrt(wrof/drogd)
        if (jfstar .gt. zero .and. jgstar .lt. zero) then
          cn = sqrt(abs(jgstar)) + fldmz(jz,ix,ic)*sqrt(abs(jfstar))
        else
          cn = zero
        end if
c
c      ratio = pkfac(4)*cn/fldcz(jz,ix,ic)
c

```

```

      if (ratio .gt. critr(4)) then
        tcrit (4) = tsec
        critr (4) = ratio
        lcrit(1,4) = ic
        lcrit(2,4) = ix
        lcrit(3,4) = jz1
      end if

c
c      PRINT NONDIMENSIONAL SUPERFICIAL VELOCITIES
c      IF CRITERIA PRINT IS REQUESTED AND CRITERION EXCEEDED
c
      if (icrit.eq.1 .and. ratio.gt.one) then
        write (nout,45) tsec, ic, ix, jz1, jgstar, jfstar
        write      (*,45) tsec, ic, ix, jz1, jgstar, jfstar
      end if

c
      end if

c
c      COMPUTE CRITERIA RATIOS #2 AND 3 (WALL TEMPERATURES)
c
      twcrt = tfsat + tsupw

c
c      (LOOP OVER INNER AND OUTER SURFACES IN CONTACT WITH FLUID CELL)
c
      do 30 isrf=isrfi,isrfo

c
c        (LOOP OVER AZIMUTHAL SECTORS ON SURFACE)
c
        do 20 iaz=iazf,iazl
          ia = iaz - na*(iaz/napl)
          twall = tsurf(isrf,ia,jz1) + ctok

c
c          COMPUTE CRITERION RATIO #2 (INST. WALL TEMP.)
c
          if (twall .gt. tbulk) then
            ratio = (twall - tfpl)/(twcrt - tfpl)
            twinst = max(ratio,twinst)
            if (ratio .gt. critr(2)) then
              tcrit (2) = tsec
              critr (2) = ratio
              lcrit(1,2) = isrf
              lcrit(2,2) = ia
              lcrit(3,2) = jz1
            end if

c
c          COMPUTE CRITERION RATIO #3 (AVG. WALL TEMP.)
c
            twhld(isrf,ia,jz1) = twhld(isrf,ia,jz1) + twall
            twavg = twhld(isrf,ia,jz1)/float(nthwld)
            ratio = (twavg - tfpl)/(twcrt - tfpl)
            if (ratio .gt. critr(3)) then
              tcrit (3) = tsec
              critr (3) = ratio
              lcrit(1,3) = isrf
              lcrit(2,3) = ia
              lcrit(3,3) = jz1
            end if

c
c          PRINT WALL TEMPERATURE AND SATURATION TEMPERATURE
c          IF CRITERIA PRINT IS REQUESTED AND CRITERION EXCEEDED
c
            if (icrit.eq.1 .and. ratio.gt.one) then
              write (nout,55) tsec, isrf, ia, jz1,
                twall-ctok, tfsat-ctok

```

```

        write      (*,55) tsec, isrf, ia, jz1,
        twall-ctok, tfsat-ctok
    6      end if
        end if
20      continue
30      continue
40      continue
50      continue
60      continue
c
c----- BOTTOM SECTION -----
c
c      do 70 jz=1,nzb
c
c          COMPUTE CRITERION RATIO #1 (BULK FLUID TEMPERATURE)
c
c          tbulk = tfb(jz)
c          call tsat(pb(jz),ilq,tfsat,xjunk)
c
c          ratio = pkfac(1)*(tbulk - tfpl)/(tfsat - tfpl)
c
c          if (ratio .gt. critr(1)) then
c              tcrit (1) = tsec
c              critr (1) = ratio
c              lcrit(1,1) = 0
c              lcrit(2,1) = 2
c              lcrit(3,1) = jz
c          end if
c
c          PRINT BULK FLUID TEMPERATURE AND SATURATION TEMPERATURE
c          IF CRITERIA PRINT IS REQUESTED AND CRITERION EXCEEDED
c
c          if (icrit.eq.1 .and. ratio.gt.one) then
c              write (nout,65) tsec, jz, tfsat-ctok, tbulk-ctok
c              write      (*,65) tsec, jz, tfsat-ctok, tbulk-ctok
c          end if
c
c          IF CRITERION #1 EXCEEDED,
c          STOP TRANSIENT CALCULATIONS (IF CRITERION #2 CHECKED)
c
c          if (ratio .ge. crmax) then
c              iredo = 1
c              return
c          end if
c
c          COMPUTE CRITERION RATIO #4 (CCFL)
c
c          jzp = jz + 1
c          if (jz .eq. nzb) then
c              alpp = alptbn
c              rogp = rogtbn
c              rofp = roftbn
c          else
c              alpp = alpbn(jzp)
c              rogp = rogbn(jzp)
c              rofp = rofbn(jzp)
c          end if
c          facg = sign(half, ugb(jz))
c          facf = sign(half, ufb(jz))
c          if (abs(ugb(jz)) .lt. vminz) facg = half*ugb(jz)/vminz
c          if (abs(ufb(jz)) .lt. vminz) facf = half*ufb(jz)/vminz
c          wtgm = half + facg
c          wtfm = half + facf
c          wtgp = one - wtgm

```

```

      wtfp = one - wtfm
      walpg = wtgm*alpbm(jz) + wtgp*alpp
      walpf = wtfm*alpbm(jz) + wtfp*alpp
      wrog = wtgm*rogbm(jz) + wtgp*rogp
      wrof = wtfm*rofbm(jz) + wtfp*rofp
c
      drogd = (wrof - wrog)*grav*deffb(jz)
      jgstar = walpg *ugb(jz)*sqrt(wrog/drogd)
      jfstar = (one-walpf)*ufb(jz)*sqrt(wrof/drogd)
      if (jfstar .gt. zero .and. jgstar .lt. zero) then
         cn = sqrt(abs(jgstar)) + fldmb(jz)*sqrt(abs(jfstar))
      else
         cn = zero
      end if
c
      ratio = pkfac(4)*cn/fldcb(jz)
c
      if (ratio .gt. critr(4)) then
         tcrit (4) = tsec
         critr (4) = ratio
         lcrit(1,4) = 0
         lcrit(2,4) = 2
         lcrit(3,4) = jz
      end if
c
c      PRINT NONDIMENSIONAL SUPERFICIAL VELOCITIES
c      IF CRITERIA PRINT IS REQUESTED AND CRITERION EXCEEDED
c
      if (icrit.eq.1 .and. ratio.gt.one) then
         write (nout,75) tsec, jz, jgstar, jfstar
         write (*,75) tsec, jz, jgstar, jfstar
      end if
70  continue
c
c----- FORMATS -----
c
15  format (' time = ',g12.5,' s',/
&         ' tsat criterion exceeded in top section cell # ',i2,/
&         ' tsat = ',f6.2,' C tbulk = ',f6.2,' C')
c
25  format (' time = ',g12.5,' s',/
&         ' CCFL criterion exceeded in top section cell # ',i2,/
&         ' jgstar = ',f8.3,2x,' jfstar = ',f8.3)
c
35  format (' time = ',g12.5,' s',/
&         ' tsat criterion exceeded in middle section at',
&         ' channel # ',i2,' theta # ',i2,' axial # ',i2,/
&         ' tsat = ',f6.2,' C tbulk = ',f6.2,' C')
c
45  format (' time = ',g12.5,' s',/
&         ' CCFL criterion exceeded in middle section at',
&         ' surface # ',i2,' theta # ',i2,' axial # ',i2,/
&         ' jgstar = ',f8.3,2x,' jfstar = ',f8.3)
c
55  format (' time = ',g12.5,' s',/
&         ' twall criterion #2 exceeded in middle section at',
&         ' surface # ',i2,' theta # ',i2,' axial # ',i2,/
&         ' twall = ',f6.2,' C tsat = ',f6.2,' C')
c
65  format (' time = ',g12.5,' s',/
&         ' tsat criterion exceeded in bottom section cell # ',i2,/
&         ' tsat = ',f6.2,' C tbulk = ',f6.2,' C')
c
75  format (' time = ',g12.5,' s',/

```

```

&      ' CCFL criterion exceeded in bottom section cell # ',i2,/
&      ' jgstar = ',f8.3,2x,' jfstar = ',f8.3)
C
      return
      end

```

CYLNR

```

      subroutine cylndr (ts,tsn,pows,tsurf,tsrfrn,radc,ar,dr,zfacm,
&                      vols,hcap,cond,rhs,diag,cra,crc,ca,cb,trhs,
&                      d,cri,cro,rhsi,rhso,rf,cmdag,cmrhs,cma,
&                      cmb,cmd,rdelt,da,dz,nr,nrp,nrmax,nrmxp,na,
&                      nsurf,nz,ncyln,icyln,wss,icent,qwf,qwg,
&                      dqfdw,dqgdw,iaxial,ncms)
C
C      *****
C      *
C      *   SUBROUTINE cylndr:  THIS SUBROUTINE SOLVES THE HEAT
C      *   CONDUCTION EQUATION FOR A SINGLE
C      *   CYLINDER
C      *
C      *****
C
      implicit real (a-h,o-z), integer (i-n)
      parameter (zero=0.0, one=1.0, two=2.0)
C
      dimension vols(nrmax,nz), zfacm(nr), dr(nr),
&              ar(nrmxp,nz), radc(nr), dz(nz)
C
      dimension tsurf(nsurf,na,nz), tsrfrn(nsurf,na,nz),
&              qwf(nsurf,na,nz), dqfdw(nsurf,na,nz),
&              qwg(nsurf,na,nz), dqgdw(nsurf,na,nz),
&              ts(nrmax,na,nz), tsn(nrmax,na,nz),
&              pows(nrmax,na,nz), hcap(nr,na,nz),
&              cond(nr,na,nz)
C
      dimension rhs(nr,na), trhs(na),
&              diag(nr,na), d(nr),
&              ca(nr,na), cri(na),
&              cb(nr,na), cro(na),
&              cra(nr,na), rhsi(na),
&              crc(nr,na), rhso(na)
C
      dimension cmrhs(na), cmdag(nr,na),
&              cma(na), cmb(na),
&              cmd(na), rf(na)
C
      if (iaxial.eq.1) then
         zo = two
      else
         zo = zero
      end if
      wssm = one - wss
C
C      SOLVE FOR TOP AXIAL LEVEL
C
      iz = 1
      izp = iz + 1
      do 10 ia=1,na
      do 10 ir=1,nr
         c1 = cond(ir,ia,iz)/dz(iz)
         c2 = cond(ir,ia,izp)/dz(izp)
         cb(ir,ia) = zo*zfacm(ir)*c1*c2/(c1 + c2)
         rhs(ir,ia) = rdelt*vols(ir,iz)*hcap(ir,ia,iz)*ts(ir,ia,iz)
&              + wssm*cb(ir,ia)*(tsn(ir,ia,izp) - tsn(ir,ia,iz))

```



```

      + wss*cb(ir,ia)*ts(ir,ia,izp) + pows(ir,ia,iz)
      diag(ir,ia) = rdelt*vols(ir,iz)*hcap(ir,ia,iz) + wss*cb(ir,ia)
10  continue
c
      call ring (ts(1,1,iz),tsurf(1,1,iz),tsrfn(1,1,iz),
      &          dr,cond(1,1,iz),radc,ar(1,iz),rhs,diag,cra,crc,ca,
      &          trhs,cmdag,cmrhs,cma,cmb,cmd,cri,cro,d,rhsi,rhso,rf,
      &          ncms,da,dz(iz),nr,nrp,nrmax,na,nz,nsurf,ncyln,icyln,
      &          icent,qwf(1,1,iz),qwg(1,1,iz),dqfdw(1,1,iz),
      &          dqgdw(1,1,iz))
c
c      LOOP OVER INTERMEDIATE AXIAL LEVELS
c
      do 100 iz=2,nz-1
      izp = iz + 1
      izm = iz - 1
c
      do 50 ia=1,na
      do 50 ir=1,nr
          ct = cb(ir,ia)
          c1 = cond(ir,ia,iz)/dz(iz)
          c2 = cond(ir,ia,izp)/dz(izp)
          cb(ir,ia) = zo*zfacm(ir)*c1*c2/(c1 + c2)
          rhs(ir,ia) = rdelt*vols(ir,iz)*hcap(ir,ia,iz)*ts(ir,ia,iz)
      &          + wssm*(ct*(tsn(ir,ia,izm) - tsn(ir,ia,iz)) +
      &          cb(ir,ia)*(tsn(ir,ia,izp) - tsn(ir,ia,iz)))
      &          + wss*(ct*ts(ir,ia,izm) +
      &          cb(ir,ia)*ts(ir,ia,izp)) + pows(ir,ia,iz)
          diag(ir,ia) = rdelt*vols(ir,iz)*hcap(ir,ia,iz) +
      &          wss*(ct + cb(ir,ia))
50  continue
c
      call ring (ts(1,1,iz),tsurf(1,1,iz),tsrfn(1,1,iz),
      &          dr,cond(1,1,iz),radc,ar(1,iz),rhs,diag,cra,crc,ca,
      &          trhs,cmdag,cmrhs,cma,cmb,cmd,cri,cro,d,rhsi,rhso,rf,
      &          ncms,da,dz(iz),nr,nrp,nrmax,na,nz,nsurf,ncyln,icyln,
      &          icent,qwf(1,1,iz),qwg(1,1,iz),dqfdw(1,1,iz),
      &          dqgdw(1,1,iz))
c
100  continue
c
c      SOLVE FOR BOTTOM AXIAL LAYER
c
      iz = nz
      izm = iz - 1
      do 150 ia=1,na
      do 150 ir=1,nr
          rhs(ir,ia) = rdelt*vols(ir,iz)*hcap(ir,ia,iz)*ts(ir,ia,iz)
      &          + wssm*cb(ir,ia)*(tsn(ir,ia,izm) - tsn(ir,ia,iz))
      &          + wss*cb(ir,ia)*ts(ir,ia,izm) + pows(ir,ia,iz)
          diag(ir,ia) = rdelt*vols(ir,iz)*hcap(ir,ia,iz) + wss*cb(ir,ia)
150  continue
c
      call ring (ts(1,1,iz),tsurf(1,1,iz),tsrfn(1,1,iz),
      &          dr,cond(1,1,iz),radc,ar(1,iz),rhs,diag,cra,crc,ca,
      &          trhs,cmdag,cmrhs,cma,cmb,cmd,cri,cro,d,rhsi,rhso,rf,
      &          ncms,da,dz(iz),nr,nrp,nrmax,na,nz,nsurf,ncyln,icyln,
      &          icent,qwf(1,1,iz),qwg(1,1,iz),dqfdw(1,1,iz),
      &          dqgdw(1,1,iz))
c
      return
      end

```

DMPPLT

```

      subroutine dmpplt (ts,tsurf,qwf,qwg,
      &      pt,alpt,xat,rogt,roft,hgt,hft,tgt,tft,
      &      p ,alp ,xa ,rog ,rof ,hg ,hf ,tg ,tf ,
      &      pb,alpb,xab,rogb,rofb,hgb,hfb,tgb,tfb,
      &      ugt,uft,wgx,wfx,ugz,ufz,ugb,ufb,
      &      ppl,alppl,tgpl,tfpl,xapl,rogpl,rofpl,hgpl,hfpl,
      &      ptb,alptb,tgtb,tftb,xatb,rogtb,roftb,hgtb,hftb,
      &      tsec,nx,nr,nzp1,nzp2,nzp3,nxmax,nchn,
      &      nsubc,nzt,nzb,nrmax,na,nz,ncyln,nsurf)
c
c      *****
c      *
c      *   SUBROUTINE dmpplt
c      *
c      *   SUBROUTINE TO WRITE FLUID VARIABLE ARRAYS TO BE USED FOR
c      *   DATA PLOTTING TO DUMP FILE AT UNIT ndmp
c      *
c      *****
      implicit real (a-h,o-z), integer (i-n)
      parameter (one=1.0, hundrd=100.0, ckilo=0.001, ctemp=-273.15)
c
      integer recl, rcl
      logical first
      character*12 units (7)
      character*16 mapnam
c
c      SOLID PARAMETERS
c
      dimension tsurf(nsurf,na,nz), ts(nrmax,na,nz,ncyln),
      &      qwf(nsurf,na,nz),          nr(ncyln),
      &      qwg(nsurf,na,nz)
c
c      MIDDLE SECTION PHYSICAL PARAMETERS
c
      dimension          nx(nchn),      p(nzp2,nxmax,nchn),
      &      alp(nzp2,nxmax,nchn),      xa(nzp2,nxmax,nchn),
      &      rog(nzp2,nxmax,nchn),      rof(nzp2,nxmax,nchn),
      &      hg(nzp2,nxmax,nchn),      hf(nzp2,nxmax,nchn),
      &      tg(nzp2,nxmax,nchn),      tf(nzp2,nxmax,nchn),
      &      ugz(nzp3,nxmax,nchn),      ufz(nzp3,nxmax,nchn),
      &      wx(nzp2,nxmax,nchn),      wf(nzp2,nxmax,nchn)
c
c      TOP SECTION PHYSICAL PARAMETERS
c
      dimension      pt(nzt), alpt(nzt), xat(nzt),
      &      rogt(nzt), roft(nzt),
      &      hgt(nzt), hft(nzt),
      &      tgt(nzt), tft(nzt),
      &      ugt(nzt), uft(nzt)
c
c      BOTTOM SECTION PHYSICAL PARAMETERS
c
      dimension      pb(nzb), alpb(nzb), xab(nzb),
      &      rogb(nzb), rofb(nzb),
      &      hgb(nzb), hfb(nzb),
      &      tgb(nzb), tfb(nzb),
      &      ugb(nzb), ufb(nzb)
c
      common /lounit/ ninp, nout, ndmp, ntmp, nrsti, nrsto
      common /pltfil/ mapnam
      common /pltrec/ nrec
      save first
c

```

```

      data first /.true./
      data n0, n1, n2, n3, n4/0, 1, 2, 3, 4/
c
      data units / '   deg C   ',
&                '   W/m^2   ',
&                '   kPa     ',
&                '   %       ',
&                '   kg/m^3   ',
&                '   kJ/kg    ',
&                '   cm/s     ' /
c
c      OPEN A DIRECT ACCESS FILE IN THE CALLING PROGRAM USING THE FOLLOWING
c      PARAMETERS.  COMPUTE A RECL PARAMETER AS THE LARGEST OF THE PRODUCTS
c      (nzp2 * nxmax) OR (nz * na)
c
c      open ( unit   = ndmp,
c      1      file    = '?????.???' ,
c      1      access  = 'direct' ,
c      1      recl    = ?????,
c      1      form    = 'unformatted',
c      1      status  = 'unknown' )
c
c      ON FIRST PASS THROUGH SUBROUTINE, SAVE GEOMETRIC PARAMETERS
c
      map = 15
c
      if(first) then
         open(unit = map,
&           file = mapnam,
&           status = 'new')
         inquire(ndmp,recl=recl)
         write(map,'(1X,A,I5)') ' Max record length = ',recl
         write(map,'(A)') ' '
         write(map,'(i5,a)') nrec,' Geometry Specs '
         write(ndmp,rec=nrec) nzt, nz, nzb, nchn, ncyl,
&           na, nxmax, nrmax,
&           nsurf, (nx(ichn), ichn=1,nchn),
&           (nr(icyl), icyl=1,ncyl)
      end if
c
      nrec = nrec + 1
      if(first) then
         write(map,'(i5,a)') nrec,' Elapsed time, sec '
         write(map,'('' ''')')
      endif
      write(ndmp,rec=nrec) n0,tsec
c
c      WRITE SOLID TEMPERATURE
c
      scaler = one
      do 10 icyl=1,ncyl
         nri = nr(icyl)
         do 10 ir = 1, nri
            nrec = nrec + 1
            if(first) write(map,'(i5,a,i2,a,i4)') nrec,
&              ' Solid Temperatures, Radius # ',ir,' Cylinder # ',icyl
            write(ndmp,rec=nrec) n1, ' SOLID TEMPS ',
&              units(1),scaler,icyl,
&              (ts(ir,ia,iz,icyl), iz=1,nz),ia=1,na)
10        continue
c
      if(first) write(map,'('' ''')')
c
c      WRITE SURFACE TEMPERATURE AND HEAT FLUX

```

```

c
  do 11 isurf = 2, nsurf
    nrec = nrec + 1
    if(first) write(map,'(i5,a,i2)') nrec,
& ' Temperatures, Surface #', isurf
    write(ndmp,rec=nrec) n1, ' SURFACE TEMPS ',
& units(1), scaler, isurf,
& ((tsurf(isurf,ia,iz), iz=1,nz), ia=1,na)
11 continue
c
  if(first) write(map,'('' '')')
c
  scaler = one
  do 12 isurf = 2, nsurf
    nrec = nrec + 1
    if(first) write(map,'(i5,a,i2)') nrec,
& ' Liq Heat Flx, Surface #', isurf
    write(ndmp,rec=nrec) n1, ' SURF HEAT FLUX',
& units(2), scaler, isurf,
& ((qwf(isurf,ia,iz), iz=1,nz), ia=1,na)
12 continue
c
  if(first) write(map,'('' '')')
c
  scaler = one
  do 13 isurf = 2, nsurf
    nrec = nrec + 1
    if(first) write(map,'(i5,a,i2)') nrec,
& ' Gas Heat Flx, Surface #', isurf
    write(ndmp,rec=nrec) n1, ' SURF HEAT FLUX',
& units(2), scaler, isurf,
& ((qwg(isurf,ia,iz), iz=1,nz), ia=1,na)
13 continue
c
  if(first) write(map,'('' '')')
c
  WRITE LOCAL PRESSURE, VOID FRACTION, AIR MASS FRACTION,
  GAS TEMPERATURE, FLUID TEMPERATURE, GAS DENSITY,
  FLUID DENSITY, GAS ENTHALPY, FLUID ENTHALPY, AND
  GAS AND FLUID VELOCITIES
c
  TOP SECTION
c
  nrec = nrec + 1
  if(first) write(map,'(i5,a/,a)') nrec,
& ' pt, alpt, xat, tgt, tft, rogt, roft, hgt, hft, ugt, uft,',
& ' ppl,alppl,xapl,tgpl,tfpl,rogpl,rofpl,hgpl,hfpl '
  write (ndmp,rec=nrec) n2, (pt(jz), alpt(jz), xat(jz),
& tgt(jz), tft(jz),
& rogt(jz), roft(jz),
& hgt(jz), hft(jz),
& ugt(jz), uft(jz), jz=1,nzt),
& ppl,alppl,xapl,tgpl,tfpl,rogpl,rofpl,hgpl,hfpl
c
  if(first) write(map,'('' '')')
c
  MIDDLE SECTION
c
  scaler = ckilo
  do 20 ic=1,nchn
    nrec = nrec + 1
    nsub = nx(ic)
    if(first) write(map,'(i5,a,i2)') nrec,
& ' Pressure, Mid Section, Channel # ',ic

```

```

        write(ndmp,rec=nrec) n3, '    PRESSURE    ',
        &      units(3),scaler,ic,
        &      ((p(jz,ix,ic),ix=1,nsup),jz=1,nzp2)
20  continue
c
    if(first) write(map,(' ' ' '))
c
    scaler = hundrd
    do 21 ic=1,nchn
        nrec = nrec + 1
        nsup = nx(ic)
        if(first) write(map,('i5,a,i2')) nrec,
        &      ' Alpha,          Mid Section,   Channel # ',ic
        write(ndmp,rec=nrec) n3, '    VOID FRAC    ',
        &      units(4),scaler,ic,
        &      ((alp(jz,ix,ic),ix=1,nsup),jz=1,nzp2)
21  continue
c
    if(first) write(map,(' ' ' '))
c
    scaler = hundrd
    do 22 ic=1,nchn
        nrec = nrec + 1
        nsup = nx(ic)
        if(first) write(map,('i5,a,i2')) nrec,
        &      ' Air Mass,          Mid Section,   Channel # ',ic
        write(ndmp,rec=nrec) n3, '    AIR MASS FRAC ',
        &      units(4),scaler,ic,
        &      ((xa(jz,ix,ic),ix=1,nsup),jz=1,nzp2)
22  continue
c
    if(first) write(map,(' ' ' '))
c
    scaler = ctemp
    do 23 ic=1,nchn
        nrec = nrec + 1
        nsup = nx(ic)
        if(first) write(map,('i5,a,i2')) nrec,
        &      ' Temp, Gas,          Mid Section,   Channel # ',ic
        write(ndmp,rec=nrec) n3, '    VAPOR TEMPS ',
        &      units(1),scaler,ic,
        &      ((tg(jz,ix,ic),ix=1,nsup),jz=1,nzp2)
23  continue
c
    if(first) write(map,(' ' ' '))
c
    scaler = ctemp
    do 24 ic=1,nchn
        nrec = nrec + 1
        nsup = nx(ic)
        if(first) write(map,('i5,a,i2')) nrec,
        &      ' Temp, Fluid,          Mid Section,   Channel # ',ic
        write(ndmp,rec=nrec) n3, '    FLUID TEMPS ',
        &      units(1),scaler,ic,
        &      ((tf(jz,ix,ic),ix=1,nsup),jz=1,nzp2)
24  continue
c
    if(first) write(map,(' ' ' '))
c
    scaler = one
    do 25 ic=1,nchn
        nrec = nrec + 1
        nsup = nx(ic)
        if(first) write(map,('i5,a,i2')) nrec,

```

```

      & ' Density, Gas,      Mid Section,   Channel # ',ic
      write(ndmp,rec=nrec) n3, ' VAPOR DENSITY ',
      &      units(5),scaler,ic,
      &      ((rog(jz,ix,ic),ix=1,nsup),jz=1,nzp2)
25  continue
c
      if(first) write(map,(' ' ' '))
c
      scaler = one
      do 26 ic=1,nchn
         nrec = nrec + 1
         nsup = nx(ic)
         if(first) write(map,('i5,a,i2')) nrec,
      & ' Density, Fluid,      Mid Section,   Channel # ',ic
      write(ndmp,rec=nrec) n3, ' FLUID DENSITY ',
      &      units(5),scaler,ic,
      &      ((rof(jz,ix,ic),ix=1,nsup),jz=1,nzp2)
26  continue
c
      if(first) write(map,(' ' ' '))
c
      scaler = ckilo
      do 27 ic=1,nchn
         nrec = nrec + 1
         nsup = nx(ic)
         if(first) write(map,('i5,a,i2')) nrec,
      & ' Enthalpy, Gas,      Mid Section,   Channel # ',ic
      write(ndmp,rec=nrec) n3, ' VAPOR ENTHALPY ',
      &      units(6),scaler,ic,
      &      ((hg(jz,ix,ic),ix=1,nsup),jz=1,nzp2)
27  continue
c
      if(first) write(map,(' ' ' '))
c
      scaler = ckilo
      do 28 ic=1,nchn
         nrec = nrec + 1
         nsup = nx(ic)
         if(first) write(map,('i5,a,i2')) nrec,
      & ' Enthalpy Fluid,      Mid Section,   Channel # ',ic
      write(ndmp,rec=nrec) n3, ' FLUID ENTHALPY ',
      &      units(6),scaler,ic,
      &      ((hf(jz,ix,ic),ix=1,nsup),jz=1,nzp2)
28  continue
c
      if(first) write(map,(' ' ' '))
c
      scaler = hundrd
      do 29 ic=1,nchn
         nrec = nrec + 1
         nsup = nx(ic)
         if(first) write(map,('i5,a,i2')) nrec,
      & ' W-velocity, Gas,      Mid Section,   Channel # ',ic
      write(ndmp,rec=nrec) n4, ' VAPOR W-VEL ',
      &      units(7),scaler,ic,
      &      ((wgx(jz,ix,ic),ix=1,nsup),jz=1,nzp2)
29  continue
c
      if(first) write(map,(' ' ' '))
c
      scaler = hundrd
      do 30 ic=1,nchn
         nrec = nrec + 1
         nsup = nx(ic)
```

```

        if(first) write(map,'(i5,a,i2)') nrec,
&      ' W-velocity, Fluid, Mid Section, Channel # ',ic
        write(ndmp,rec=nrec) n4, ' FLUID W-VEL ',
&          units(6),scaler,ic,
&          ((wfx(jz,ix,ic),ix=1,nsub),jz=1,nzp2)
30      continue
c
        if(first) write(map,'('' '')')
c
        scaler = hundrd
        do 31 ic=1,nchn
            nrec = nrec + 1
            nsub = nx(ic)
            if(first) write(map,'(i5,a,i2)') nrec,
&          ' U-velocity, Gas, Mid Section, Channel # ',ic
            write(ndmp,rec=nrec) n4, ' VAPOR VELOCITY ',
&          units(6),scaler,ic,
&          ((ugz(jz,ix,ic),ix=1,nsub),jz=1,nzp2)
31      continue
c
        if(first) write(map,'('' '')')
c
        scaler = hundrd
        do 32 ic=1,nchn
            nrec = nrec + 1
            if(first) write(map,'(i5,a,i2)') nrec,
&          ' U-velocity, Fluid, Mid Section, Channel # ',ic
            write(ndmp,rec=nrec) n4, ' FLUID VELOCITY ',
&          units(1),scaler,ic,
&          ((ufz(jz,ix,ic),ix=1,nsub),jz=1,nzp2)
32      continue
c
        if(first) write(map,'('' '')')
c
        BOTTOM SECTION
c
        nrec = nrec + 1
        if(first) then
            write(map,'(i5,a/,a)') nrec,
&          ' pb, alpb, xab, tgb, tfb, rogb, rofb, hgb, hfb, ugb, ufb,',
&          ' ptb,alptb,xatb,tgtb,tftb,rogtb,roftb,hgtb,hftb '
            close (map)
        endif
        write (ndmp,rec=nrec) n2, (pb(jz), alpb(jz), xab(jz),
&          tgb(jz), tfb(jz),
&          rogb(jz), rofb(jz),
&          hgb(jz), hfb(jz),
&          ugb(jz), ufb(jz), jz=1,nzb),
&          ptb,alptb,xatb,tgtb,tftb,rogtb,roftb,hgtb,hftb
c
        first = .false.
c
        return
    end

```

DONORB

```

        subroutine donorb(alpbn ,xabn ,rogbn ,rofbn ,hgbn ,hfbn,
&          alptbn,xatbn,rogtbn,roftbn hgtbn,hftbn,
&          ugb,ufb,bgb,cgb,bfb,cfb,
&          acb,advbb,advcb,vminz,
&          nzb)
c
c *****
c *
c *

```

[illegible]


```
C          INTERPOLATION IS EMPLOYED.  FOR VELOCITIES GREATER
C          THAN vminz IN MAGITUDE FULL DONORING IS EMPLOYED
C
      facg = sign(half, vgb)
      facf = sign(half, vfb)
      if (abs(vgb) .lt. vminz) facg = half*vgb/vminz
      if (abs(vfb) .lt. vminz) facf = half*vfb/vminz
      wtgm = half + facg
      wtfm = half + facf
      wtgp = one - wtgm
      wtfp = one - wtfm
C
C      SET CELL PROPERTIES FOR jcp MASS CELL
C
      if (jz .eq. nzb) then
        alpp = alptbn
        rogp = rogtbn
        rofp = roftbn
        xap  = xatbn
        hgp  = hgtbn
        hfp  = hftbn
      else
        alpp = alpbn(jcp)
        rogp = rogbn(jcp)
        rofp = rofbn(jcp)
        xap  = xabn(jcp)
        hgp  = hgbn(jcp)
        hfp  = hfbn(jcp)
      endif
C
C      COMPUTE DONORED (GAS MIXTURE) VOID FRACTION
C      FOR BOTH GAS AND LIQUID PHASE DONORING
C
      walpg = wtgm * alpbn(jc) + wtgp * alpp
      walpf = wtfm * alpbn(jc) + wtfp * alpp
C
C      COMPUTE DONORED (MIXTURE) GAS DENSITY
C
      wrg = wtgm * rogbn(jc) + wtgp * rogp
C
C      COMPUTE DONORED LIQUID DENSITY
C
      wrf = wtfm * rofbn(jc) + wtfp * rofp
C
C      COMPUTE DONORED (MIXTURE) GAS ENTHALPY
C
      whg = wtgm * hgbn(jc) + wtgp * hgp
C
C      COMPUTE DONORED LIQUID ENTHALPY
C
      whf = wtfm * hfbn(jc) + wtfp * hfp
C
C      COMPUTE DONORED (GAS MIXTURE) AIR MASS FRACTION
C
      wxa = wtgm * xabn(jc) + wtgp * xap
C
C      GROUP COMMON ADVECTIVE QUANTITIES
C
      c1 = arb * walpg * wrg
      c2 = arb * (one - walpf) * wrf
      c3 = c1 * whg
      c4 = c2 * whf
      c5 = c1 * wxa
C
```

```

c      COMPUTE DONORED ADVECTIVE QUANTITIES FOR CELL FACE jz
c
      advbb(jz,1) = c1 * bgl(jz)
      advcb(jz,1) = c1 * cgb(jz)
      advbb(jz,2) = c2 * bfb(jz)
      advcb(jz,2) = c2 * cfb(jz)
      advbb(jz,3) = c3 * bgb(jz)
      advcb(jz,3) = c3 * cgb(jz)
      advbb(jz,4) = c4 * bfb(jz)
      advcb(jz,4) = c4 * cfb(jz)
      advbb(jz,5) = c5 * bgb(jz)
      advcb(jz,5) = c5 * cgb(jz)
c
c 10      continue
c
      return
      end

```

DONORM

```

      subroutine donorm(alpn , xan , rogn , rofn , hgn , hfn,
&                      ugz,ufz,bgz,cgz,bfz,cfz,
&                      wgx,wfx,dgx,egx,dfx,efx,
&                      acz,acx,advbz,advbz,advdx,advex,vminz,vminx,
&                      nzp1,nzp2,nzp3,nchn,nxmax,nx,icc)
c
c *****
c *
c * Subroutine Name: DONORM
c *
c * Function: DONORM computes the time-step dependent advective
c * donored quantities that are used in the JACOBM module to
c * construct the jacobian matrix within the NEWTON iterations.
c * These variables are set up according to a donoring scheme
c * described in the FLOWTRAN_TF report.
c *
c *****
c
      parameter (zero=0.0, half=0.5, one=1.0)
      include 'knobs.inc'
c
      ARGUMENT ARRAYS
c
      dimension
&          alpn (nzp2,nxmax,nchn),      acx (nzp2,nxmax,nchn),
&          acz (nzp3,nxmax,nchn),      icc (2,nxmax,nchn),
&          advbz (nzp3,nxmax,nchn,5),  advcz (nzp3,nxmax,nchn,5),
&          advdx (nzp2,nxmax,nchn,5),  advex (nzp2,nxmax,nchn,5),
&          bfz (nzp3,nxmax,nchn),      cfz (nzp3,nxmax,nchn),
&          dfx (nzp2,nxmax,nchn),      efx (nzp2,nxmax,nchn),
&          bgz (nzp3,nxmax,nchn),      cgz (nzp3,nxmax,nchn),
&          dgx (nzp2,nxmax,nchn),      egx (nzp2,nxmax,nchn),
&          hfn (nzp2,nxmax,nchn),      hgn (nzp2,nxmax,nchn),
&          rofn (nzp2,nxmax,nchn),     rogn (nzp2,nxmax,nchn),
&          wfx (nzp2,nxmax,nchn),      ufz (nzp3,nxmax,nchn),
&          wgx (nzp2,nxmax,nchn),      ugz (nzp3,nxmax,nchn),
&          xan (nzp2,nxmax,nchn),      nx (nchn)
c
c      INTERNAL ARRAYS
c
      dimension ija(2),arb(2),vfb(2),vgb(2)
c
      data ija /-1,0/
c
      LOOP OVER EACH FLOW ANNULUS (CHANNEL) WITHIN ASSEMBLY (CORE)

```

[illegible]

```

C      *      |      |      |      |      |      |      jc=jx
C      *      |      |      |      |      |      |
C      *      |      |      |      |      |      |
C      * nz+1 -----|-----|-----|-----|-----|
C      *      |      |      |      |      |      |
C      *      |      |      |      |      |      |      nz+1
C      *      |      |      |      |      |      |
C      * nz+2 -----|-----|-----|-----|-----| <--- Connects to
C      *      |      |      |      |      |      |      bottom section
C      *      |      |      |      |      |      |      nz+2 (Fictitious cells
C      *      |      |      |      |      |      |      overlapping top
C      * nz+3 -----|-----|-----|-----|-----|      cell of bottom
C      *      1      2      ix      nx(k)   (1)      section)
C      *
C      *****
C
C      COMPUTE DONOR CELL QUANTITIES
C
C      FACE AREA BETWEEN c AND CELL m
C      SET HORIZONTAL AND VERTICAL FACE AREAS, LIQUID AND
C      MIXTURE GAS VELOCITIES
C
C      HORIZONTAL FACE:
C      arb(1) = acz(jz,i,k)
C      vgb(1) = ugz(jz,i,k)
C      vfb(1) = ufz(jz,i,k)
C
C      VERTICAL FACE:
C      arb(2) = acx(jx,i,k)
C      vgb(2) = wgx(jx,i,k)
C      vfb(2) = wfx(jx,i,k)
C
C      m = 1
C
C      SET ia AND ja INDEXES ACCORDING TO WHICH FACE
C      BEING PROCESSED
C
C      ja = jc + ija(m)
C      ia = i
C
C      COMPUTE DONORING WEIGHTS FOR MASS/ENERGY CELLS ABOVE AND
C      BELOW GIVEN MOMENTUM FACE. A POSITIVE VELOCITY IMPLIES
C      INCOMING FLOW INTO GIVEN MASS/ENERGY CELL (jc,i,k)
C
C      NOTE THAT: FOR VELOCITIES OF MAGNITUDE LESS THAN vmin
C                  LINEAR INTERPOLATION IS EMPLOYED. FOR
C                  VELOCITIES GREATER THAN vmin IN MAGNITUDE
C                  FULL DONORING IS EMPLOYED
C
C      facg = sign(half, vgb(m))
C      facf = sign(half, vfb(m))
C      if (abs(vgb(m)) .lt. vminz) facg = half*vgb(m)/vminz
C      if (abs(vfb(m)) .lt. vminz) facf = half*vfb(m)/vminz
C      wtgm = half + facg
C      wtfm = half + facf
C      wtgp = one - wtgm
C      wtfp = one - wtfm
C
C      COMPUTE DONORED (GAS MIXTURE) VOID FRACTION
C      FOR BOTH GAS AND LIQUID PHASE DONORING
C
C      alpc = alpn(jc, i,k)
C      alpa = alpn(ja,ia,k)
C      walpg = wtgp * alpc + wtgm * alpa

```

```

c      walpf = wtfp * alpc + wtfm * alpa
c
c      COMPUTE DONORED (MIXTURE) GAS DENSITY PER UNIT CELL VOL.
c
c      wrg = wtgp * rogn(jc,i,k) + wtgm * rogn(ja,ia,k)
c
c      COMPUTE DONORED LIQUID DENSITY PER UNIT CELL VOLUME
c
c      wrf = wtfp * rofn(jc,i,k) + wtfm * rofn(ja,ia,k)
c
c      COMPUTE DONORED (MIXTURE) GAS ENTHALPY
c
c      whg = wtgp * hgn(jc,i,k) + wtgm * hgn(ja,ia,k)
c
c      COMPUTE DONORED LIQUID ENTHALPY
c
c      whf = wtfp * hfn(jc,i,k) + wtfm * hfn(ja,ia,k)
c
c      COMPUTE DONORED (GAS MIXTURE) AIR MASS FRACTION
c
c      wxa = wtgp * xan(jc,i,k) + wtgm * xan(ja,ia,k)
c
c      GROUP COMMON ADVECTIVE QUANTITIES FOR HORIZONTAL SURF.
c
c      c1 = arb(m) * walpg * wrg
c      c2 = arb(m) * (one - walpf) * wrf
c      c3 = c1 * whg
c      c4 = c2 * whf
c      c5 = c1 * wxa
c      advbz(jc,i,k,1) = c1 * bgz(jc,i,k)
c      advcz(jc,i,k,1) = c1 * cgz(jc,i,k)
c      advbz(jc,i,k,2) = c2 * bfz(jc,i,k)
c      advcz(jc,i,k,2) = c2 * cfz(jc,i,k)
c      advbz(jc,i,k,3) = c3 * bgz(jc,i,k)
c      advcz(jc,i,k,3) = c3 * cgz(jc,i,k)
c      advbz(jc,i,k,4) = c4 * bfz(jc,i,k)
c      advcz(jc,i,k,4) = c4 * cfz(jc,i,k)
c      advbz(jc,i,k,5) = c5 * bgz(jc,i,k)
c      advcz(jc,i,k,5) = c5 * cgz(jc,i,k)
c
c      m = 2
c
c      SET ia AND ja INDEXES ACCORDING TO WHICH FACE
c      BEING PROCESSED
c
c      ja = jc + ija(m)
c      ia = icc(1,i,k)
c
c      COMPUTE DONORING WEIGHTS FOR MASS/ENERGY CELLS ABOVE AND
c      BELOW GIVEN MOMENTUM FACE.  A POSITIVE VELOCITY IMPLIES
c      INCOMING FLOW INTO GIVEN MASS/ENERGY CELL (jc,i,k)
c
c      NOTE THAT: FOR VELOCITIES OF MAGITUDE LESS THAN vmin
c      LINEAR INTERPOLATION IS EMPLOYED.  FOR
c      VELOCITIES GREATER THAN vmin IN MAGNITUDE
c      FULL DONORING IS EMPLOYED
c
c      facg = sign(half, vgb(m))
c      facf = sign(half, vfb(m))
c      if (abs(vgb(m)) .lt. vminx) facg = half*vgb(m)/vminx
c      if (abs(vfb(m)) .lt. vminx) facf = half*vfb(m)/vminx
c      wtgm = half + facg
c      wtfm = half + facf
c      wtgp = one - wtgm

```

```

      wtfp = one - wtfm
c
c      COMPUTE DONORED (GAS MIXTURE) VOID FRACTION
c      FOR BOTH GAS AND LIQUID PHASE DONORING
c
      alpc = alpn(jc, i, k)
      alpa = alpn(ja, ia, k)
      walpg = wtgp * alpc + wtgm * alpa
      walpf = wtfp * alpc + wtfm * alpa
c
c      COMPUTE DONORED (MIXTURE) GAS DENSITY PER UNIT CELL VOL.
c
      wrg = wtgp * rogn(jc, i, k) + wtgm * rogn(ja, ia, k)
c
c      COMPUTE DONORED LIQUID DENSITY PER UNIT CELL VOLUME
c
      wrf = wtfp * rofn(jc, i, k) + wtfm * rofn(ja, ia, k)
c
c      COMPUTE DONORED (MIXTURE) GAS ENTHALPY
c
      whg = wtgp * hgn(jc, i, k) + wtgm * hgn(ja, ia, k)
c
c      COMPUTE DONORED LIQUID ENTHALPY
c
      whf = wtfp * hfn(jc, i, k) + wtfm * hfn(ja, ia, k)
c
c      COMPUTE DONORED (GAS MIXTURE) AIR MASS FRACTION
c
      wxa = wtgp * xan(jc, i, k) + wtgm * xan(ja, ia, k)
c
c      GROUP COMMON ADVECTIVE QUANTITIES FOR VERTICAL SURFACES
c
      if(jx .gt. nzpl) go to 10
c
      arib = vrib(walpg)
      c1 = arb(m) * arib * wrg
      c2 = arb(m) * (one - arib) * wrf
      c3 = c1 * whg
      c4 = c2 * whf
      c5 = c1 * wxa
      advdx(jc, i, k, 1) = c1 * dgx(jc, i, k)
      advex(jc, i, k, 1) = c1 * egx(jc, i, k)
      advdx(jc, i, k, 2) = c2 * dfx(jc, i, k)
      advex(jc, i, k, 2) = c2 * efx(jc, i, k)
      advdx(jc, i, k, 3) = c3 * dgx(jc, i, k)
      advex(jc, i, k, 3) = c3 * egx(jc, i, k)
      advdx(jc, i, k, 4) = c4 * dfx(jc, i, k)
      advex(jc, i, k, 4) = c4 * efx(jc, i, k)
      advdx(jc, i, k, 5) = c5 * dgx(jc, i, k)
      advex(jc, i, k, 5) = c5 * egx(jc, i, k)
c
10      continue
20      continue
30      continue
40      continue
c
      return
      end

```

DONORT

```

      subroutine donort(alptn , xatn , rogn , rofn , hgn , hfn,
4          alppln, xapln, rogpln, rofpln, hgpln, hfpln,
4          ugt, uft, bgt, cgt, bft, cft,
4          act, advbt, advct, vminz,

```

```

      &          nzt)
C
C *****
C *
C * Subroutine Name: DONORT
C *
C * Function: DONORT computes the time-step dependent advective
C * donored quantities that are used in the JACOBT module to
C * construct the jacobian matrix within the NEWTON iterations.
C * These variables are set up according to a donating scheme
C * described in the FLOWTRAN_TF report.
C *****
C
C parameter (zero=0.0, half=0.5, one=1.0)
C
C ARGUMENT ARRAYS
C
C dimension
C
C      alptn (nzt),      act (nzt),
C      advbt (nzt,5),    advct(nzt,5),
C      bft (nzt),        cft (nzt),
C      bgt (nzt),        cgt (nzt),
C      hftn (nzt),       hgtn (nzt),
C      roftn (nzt),      rogtn(nzt),
C      uft (nzt),        ugt (nzt),
C      xatn (nzt)
C
C LOOP OVER ALL AXIAL MOMENTUM CELLS
C
C do 10 jz = 1, nzt
C   jc = jz
C   jcm = jc - 1
C
C SET DONOR CELL QUANTITIES FOR DIVERGENCE TERMS IN MASS/ENERGY
C EQUATIONS
C
C *****
C *
C * Numbering convention for Top Section cells and faces
C *
C * Z
C * Direction
C *
C * |
C * |           | jc-1 | <--- Cell jcm
C * |           |     |
C * |           |_____| <--- Face jz
C * |           | v   |
C * |           | jc  | <--- Cell jc
C * |           |     |
C * |           |_____|
C * v
C *****
C
C COMPUTE DONOR CELL QUANTITIES
C
C SET FACE AREA, LIQUID AND MIXTURE GAS VELOCITIES
C
C art = act(jz)
C vft = uft(jz)
C vgt = ugt(jz)

```

```
c      COMPUTE DONORING WEIGHTS FOR MASS/ENERGY CELLS ABOVE AND BELOW
c      GIVEN MOMENTUM FACE (I.E. jc AND jcm)
```

```
c      NOTE THAT: FOR VELOCITIES OF MAGITUDE LESS THAN vminz LINEAR
c      INTERPOLATION IS EMPLOYED. FOR VELOCITIES GREATER
c      THAN vminz IN MAGITUDE FULL DONORING IS EMPLOYED.
```

```
c
c      facg = sign(half, vgt)
c      facf = sign(half, vft)
c      if (abs(vgt) .lt. vminz) facg = half*vgt/vminz
c      if (abs(vft) .lt. vminz) facf = half*vft/vminz
c      wtgm = half + facg
c      wtfm = half + facf
c      wtgp = one - wtgm
c      wtfp = one - wtfm
```

```
c      SET CELL PROPERTIES FOR jcm MASS CELL
```

```
c
c      if (jz .eq. 1) then
c         alpm = alppln
c         rogm = rogpln
c         rofm = rofpln
c         xam = xapln
c         hgm = hgpln
c         hfm = hfpln
c      else
c         alpm = alptn(jcm)
c         rogm = rogtm(jcm)
c         rofm = roftn(jcm)
c         xam = xatn(jcm)
c         hgm = hgtm(jcm)
c         hfm = hftn(jcm)
c      endif
```

```
c      COMPUTE DONORED (GAS MIXTURE) VOID FRACTION
c      FOR BOTH GAS AND LIQUID PHASE DONORING
```

```
c
c      walpg = wtgm * alpm + wtgp * alptn(jc)
c      walpf = wtfm * alpm + wtfp * alptn(jc)
```

```
c      COMPUTE DONORED (MIXTURE) GAS DENSITY
```

```
c
c      wrg = wtgm * rogm + wtgp * rogtm(jc)
```

```
c      COMPUTE DONORED LIQUID DENSITY
```

```
c
c      wrf = wtfm * rofm + wtfp * roftn(jc)
```

```
c      COMPUTE DONORED (MIXTURE) GAS ENTHALPY
```

```
c
c      whg = wtgm * hgm + wtgp * hgtm(jc)
```

```
c      COMPUTE DONORED LIQUID ENTHALPY
```

```
c
c      whf = wtfm * hfm + wtfp * hftn(jc)
```

```
c      COMPUTE DONORED (GAS MIXTURE) AIR MASS FRACTION
```

```
c
c      wxa = wtgm * xam + wtgp * xatn(jc)
```

```
c      GROUP COMMON ADVECTIVE QUANTITIES
```

```
c
c      c1 = art * walpg * wrg
c      c2 = art * (one - walpf) * wrf
```



```

      c3 = c1 * whg
      c4 = c2 * whf
      c5 = c1 * wxa

c
c      COMPUTE DONORED ADVECTIVE QUANTITIES FOR CELL FACE jz
c
      advbt(jz,1) = c1 * bgt(jz)
      advct(jz,1) = c1 * cgt(jz)
      advbt(jz,2) = c2 * bft(jz)
      advct(jz,2) = c2 * cft(jz)
      advbt(jz,3) = c3 * bgt(jz)
      advct(jz,3) = c3 * cgt(jz)
      advbt(jz,4) = c4 * bft(jz)
      advct(jz,4) = c4 * cft(jz)
      advbt(jz,5) = c5 * bgt(jz)
      advct(jz,5) = c5 * cgt(jz)

c
10  continue
c
      return
      end

```

EOSSLD

```

      subroutine eossld (hcap,cond,mat,ts,wtpc,nr,na,nz,nrmax)

c
c      *****
c      *
c      * SUBROUTINE eossld: THIS ROUTINE COMPUTES THE HEAT CAPACITY
c      * AND THERMAL CONDUCTIVITY OF THE SOLID
c      * CELLS AS A FUNCTION OF THE MATERIAL AND
c      * TEMPERATURE
c      *
c      * FUNCTION rhocv: THIS FUNCTION RETURNS THE HEAT CAPACITY
c      * OF THE MATERIAL INDICATED BY mat AT
c      * TEMPERATURE t
c      *
c      * DENSITY IN kg/m**3
c      * HEAT CAPACITY IN J/kg-K
c      *
c      * FOR ALLOYS, WTPC GIVES EITHER
c      * THE WEIGHT PERCENT LITHIUM IN ALUMINUM OR
c      * THE WEIGHT PERCENT URANIUM IN ALUMINUM
c      *
c      * FUNCTION condct: THIS FUNCTION RETURNS THERMAL CONDUCTIVITY
c      * OF THE MATERIAL INDICATED BY mat AT THE
c      * TEMPERATURE t IN UNITS OF W/m-K.
c      * FOR ALLOYS, WTPC GIVES EITHER
c      * THE WEIGHT PERCENT LITHIUM IN ALUMINUM OR
c      * THE WEIGHT PERCENT URANIUM IN ALUMINUM
c      *
c      * THE FOLLOWING MATERIALS ARE AVAILABLE:
c      * 1 - URANIUM
c      * 2 - ALUMINUM
c      * 3 - 304L STAINLESS STEEL
c      * 4 - LITHIUM-ALUMINUM ALLOY
c      * 5 - URANIUM-ALUMINUM ALLOY
c      * 6 - ALUMINUM 6063
c      * 7 - MACOR
c      * 8 - INCONEL 600
c      * 9 - FLAME SPRAYED OXIDE
c      *
c      *****

c
c      implicit real (a-h,o-z), integer (i-n)

```

```

      parameter (oneh=0.01, one=1.0)
c
      include 'knobs.inc'
c
      dimension hcap(nr,na,nz), ts(nrmax,na,nz),
&      cond(nr,na,nz), mat(nrmax,nz)
c
      LOCAL COEFFICIENT ARRAYS
c
      dimension coef1(18), coef2(9), coef3(27)
c
      DENSITY ALLOY WEIGHT PERCENT COEFFICIENTS
c
      data coef1/0.0      , 0.0      ,
&      0.0      , 0.0      ,
&      0.0      , 0.0      ,
&      -2.358601, 0.0      ,
&      0.351305, 1.963374,
&      0.0      , 0.0      ,
&      0.0      , 0.0      ,
&      0.0      , 0.0      ,
&      0.0      , 0.0      /
c
      DENSITY TEMPERATURE COEFFICIENTS (LBM/FT**3 AT 20 C)
c
      data coef2 /1186.7700,
&      168.8400,
&      500.4400,
&      168.6200,
&      171.6500,
&      168.0      ,
&      157.0      ,
&      525.0      ,
&      254.0      /
c
      HEAT CAPACITY TEMPERATURE COEFFICIENTS (BTU/LBM-F)
c
      data coef3/2.778114e-02, 1.043055e-05, 3.096700e-08,
&      2.103620e-01, 7.021134e-05, 8.219068e-08,
&      1.099500e-01, 6.754000e-05, -2.645100e-08,
&      8.267500e-01, 7.855900e-04, 1.394300e-06,
&      2.778114e-02, 1.043055e-05, 3.096700e-08,
&      0.218      , 0.0      , 0.0      ,
&      0.2      , 0.0      , 0.0      ,
&      0.105     , 0.0      , 0.0      ,
&      0.208     , 0.0      , 0.0      /
c
      CONVERSION FACTORS FOR THERMAL CONDUCTIVITY, DENSITY,
      AND HEAT CAPACITY FROM ENGLISH (SRS) UNITS TO SI UNITS
c
      data csik/6.230645e+03/, csid/16.01846/, csic/4.18400e+03/
c
      do 100 ia=1,na
      do 100 ir=1,nr
      do 100 iz=1,nz
c
         tsld = ts(ir,ia,iz)
         nsld = mat(ir,iz)
         rho0 = coef2(nsld)
c
         mf = 2*nsld - 1
         mfl = mf + 1
         wtf = oneh*wtpc
         fact = one + (coef1(mf) + coef1(mfl)*wtf)*wtf

```

```

C
      mf = 3*nsld - 3
      mf1 = mf + 1
      c1 = coef3(mf1)*wtf + coef3(4)*(one - wtf)
      mf2 = mf + 2
      c2 = coef3(mf2)*wtf + coef3(5)*(one - wtf)
      mf3 = mf + 3
      c3 = coef3(mf3)*wtf + coef3(6)*(one - wtf)
C
C      CALCULATE DENSITY AND HEAT CAPACITY AND CONVERT TO SI UNITS
C
      rho = csld*fact*rho0
      cv = csic*(c1 + (c2 + c3*tsld)*tsld)
C
      hcap(ir,ia,iz) = xcvmet*rho*cv
C
C      CALCULATE THERMAL CONDUCTIVITY IN SI UNITS
C
      cond(ir,ia,iz) = condt(nsld,tsld,wtpc)
C
100 continue
C
      return
      end

```

EXPL1D

```

      subroutine expl1d (bgz,bfz,cgz,cfz,
&                      acz,aratz,dhz,cosz,dzm,ugz,ufz,
&                      absrz,fmltz,formz,frez,cizn,c0bz,c0sz,
&                      azz,volc,pn,alpn,tgn,tfn,xan,rogn,rofn,
&                      acin,ugin,ufin,alpin,rogin,rofin,
&                      acex,ugex,ufex,alpex,rogex,rofex,
&                      rdelt,vminz,
&                      nz,nin,nex,jstrt,jend,jmod,ierr,msgld,ilq)
C
C      *****
C      *
C      * SUBROUTINE expl1d
C      *
C      * THIS ROUTINE COMPUTES THE NEW TIME STEP FLUID VELOCITIES
C      * AT EACH CELL FACE AS A LINEAR FUNCTION OF THE NEW TIME
C      * STEP PRESSURE DIFFERENCE ACROSS THE CELL FACE FOR THE ONE
C      * DIMENSIONAL TOP AND BOTTOM SECTIONS OF THE ASSEMBLY. THE
C      * COEFFICIENTS FORMING THESE LINEAR EXPRESSIONS ARE FUNCTIONS
C      * OF OLD TIME STEP QUANTITIES; THEREFORE, THIS CALCULATION
C      * IS ONLY DONE ONCE AT THE BEGINNING OF EACH TIME STEP.
C      * THE EXPRESSIONS HAVE THE FOLLOWING FORM:
C      *
C      * FOR GAS PHASE:
C      *
C      *      
$$u_{g,j+1/2}^{n+1} = B_{g,j+1/2}^n + C_{g,j+1/2}^n * (P_j^{n+1} - P_{j+1}^{n+1})$$

C      *
C      * FOR LIQUID PHASE:
C      *
C      *      
$$u_{f,j+1/2}^{n+1} = B_{f,j+1/2}^n + C_{f,j+1/2}^n * (P_j^{n+1} - P_{j+1}^{n+1})$$

C      *
C      * WHERE: B = bgz (Z-DIRECTION)
C      *          g
C      *          B = biz (Z-DIRECTION)
C      *          f
C      *          C = cgz (Z-DIRECTION)
C      *          g

```

```

c      *      C = cfz(Z-DIRECTION)
c      *      f
c      *
c      * ARGUMENTS (O=Output, I=Input):
c      *
c      * O   bgz = SEE ABOVE; GAS PHASE CONSTANT TERM
c      * O   bfz = SEE ABOVE; LIQUID PHASE CONSTANT TERM
c      * O   cgz = SEE ABOVE; GAS PHASE PRESSURE COEFFICIENT
c      * O   cfz = SEE ABOVE; LIQUID PHASE PRESSURE COEFFICIENT
c      *
c      * I   acz = FACE AREA
c      * I   aratz = RATIO OF LOCAL FACE AREA TO AVERAGE CELL AREA
c      * I   dhz = FACE HYDRAULIC DIAMETER
c      * I   cosz = FACE cos*g
c      * I   dzm = MOMENTUM CELL LENGTH
c      * I   ugz = FACE GAS VELOCITY
c      * I   ufz = FACE LIQUID VELOCITY
c      * I   absrz = FACE ABSOLUTE ROUGHNESS
c      * I   fmltz = FACE FRICTION MULTIPLIER
c      * I   formz = FACE FORM LOSS COEFFICIENT
c      * I   frez = FACE HYDRAULIC DIAMETER CORRECTION FACTOR, Kh
c      * I   cizn = FACE GENERALIZED INTERFACIAL DRAG COEFFICIENT
c      * I   c0bz = BUBBLE REGIME DISTRIBUTION COEFFICIENT
c      * I   c0sz = SLUG REGIME DISTRIBUTION COEFFICIENT
c      * I   azz = CELL (CENTER) AREA
c      * I   volc = CELL VOLUME
c      * I   pn = CELL PRESSURE
c      * I   alp = CELL VOID FRACTION
c      * I   tgn = CELL GAS TEMPERATURE
c      * I   tfn = CELL LIQUID TEMPERATURE
c      * I   xan = CELL AIR MASS FRACTION
c      * I   rogn = CELL GAS DENSITY
c      * I   rofn = CELL LIQUID DENSITY
c      * I   acin = SECTION INLET FACE AREA
c      * I   ugin = SECTION INLET FACE GAS VELOCITY
c      * I   ufin = SECTION INLET FACE LIQUID VELOCITY
c      * I   alpin = SECTION INLET CELL VOID FRACTION
c      * I   rogin = SECTION INLET CELL GAS DENSITY
c      * I   rofin = SECTION INLET CELL LIQUID DENSITY
c      * I   acex = SECTION OUTLET FACE AREA
c      * I   uge = SECTION OUTLET FACE GAS VELOCITY
c      * I   ufe = SECTION OUTLET FACE LIQUID VELOCITY
c      * I   alpex = SECTION OUTLET CELL VOID FRACTION
c      * I   roge = SECTION OUTLET CELL GAS DENSITY
c      * I   rofe = SECTION OUTLET CELL LIQUID DENSITY
c      * I   rdelt = RECIPROCAL dt
c      * I   vminz = MINIMUM VELOCITY FOR FULL DONORING
c      * I   nz = ARRAY DIMENSION
c      * I   nin = ARRAY DIMENSION
c      * I   nex = ARRAY DIMENSION
c      * I   jstrt = STARTING FACE NUMBER FOR 1-D SECTION
c      * I   jend = ENDING FACE NUMBER FOR 1-D SECTION
c      * I   jmod = OFFSET BETWEEN FACE AND CELL INDICES
c      *      (jmod = 0 FOR TOP SECTION; jmod = 1 FOR BOTTOM SEC.
c      * I   ierr = ERROR FLAG
c      * I   msgld = CHARACTER VARIABLE HOLDING SECTION LABEL
c      * I   ilq = LIQUID IDENTIFIER (.true.==>liquid, .false.==>gas)
c      *
c      *****
c      implicit real (a-h,o-z), integer (i-n)
c      logical liquid
c      character*6 msgld
c
c      dimension bgz(nz), bfz(nz),

```

```

      &          cgz(nz), cfz(nz)
c
      dimension acz(nz), aratz(nz), dhz(nz), cosz(nz), dzm(nz),
      &          ugz(nz), ufz(nz), absrz(nz), fmltz(nz), formz(nz),
      &          frez(nz), cizn(nz), c0bz(nz), c0sz(nz)
c
      dimension azz(nz), volc(nz), pn(nz), alpn(nz), tgn(nz),
      &          tfn(nz), xan(nz), rogn(nz), rofn(nz)
c
      dimension acin(nin), acex(nex),
      &          ugin(nin), ugex(nex),
      &          ufin(nin), ufex(nex),
      &          alpin(nin), alpex(nex),
      &          rogin(nin), rogex(nex),
      &          rofin(nin), rofex(nex)
c
      parameter (zero=0.0, half=0.5, one=1.0, two=2.0, three=3.0)
c
      data epsv/0.001/, eps1/0.001/, eps2/0.01/, epsdet/1.0e-20/
c
      LOOP OVER AXIAL CELLS IN TOP OR BOTTOM SECTION
c
      do 100 jz=jstrt,jend
c
c          SET POINTERS TO MASS CELLS FORMING TOP (jzt)
c          AND BOTTOM (jzb) OF MOMENTUM CELL;
c          jmod = 0 FOR TOP SECTION
c          jmod = 1 FOR BOTTOM SECTION
c
c          jzb = jz + jmod
c          jzt = jzb - 1
c
c          ug = ugz(jz)
c          uf = ufz(jz)
c
c          COMPUTE VOLUME FRACTIONS FOR TOP AND BOTTOM CELLS
c
c          rvolz = two/(volc(jzt) + volc(jzb))
c          ft = volc(jzt)/(volc(jzt) + volc(jzb))
c          fb = one - ft
c
c          CALCULATE VOLUME AVERAGED PROPERTIES
c
c          pc = ft*pn(jzt) + fb*pn(jzb)
c          tgc = ft*tgn(jzt) + fb*tgn(jzb)
c          tfc = ft*tfn(jzt) + fb*tfn(jzb)
c          xac = ft*xan(jzt) + fb*xan(jzb)
c
c          alpg = ft*alpn(jzt) + fb*alpn(jzb)
c          rhog = ft*rogn(jzt) + fb*rogn(jzb)
c          arog = ft*alpn(jzt)*rogn(jzt) + fb*alpn(jzb)*rogn(jzb)
c
c          alpf = one - alpg
c          rhof = ft*rofn(jzt) + fb*rofn(jzb)
c          arof = ft*(one - alpn(jzt))*rofn(jzt) +
      &          fb*(one - alpn(jzb))*rofn(jzb)
c
c          CALCULATE ADVECTION TERMS
c
c          liquid = .false.
c          call avecl (advq,avgag,acz,azz,aratz,ugz,alpn,rogn,
      &          acin,ugin,alpin,rogin,acex,ugex,alpex,rogex,
      &          vminz,jz,jmod,nz,nin,nex,liquid)
c

```

```

      liquid = .true.
      call avecl (advf,avgaf,acz,azz,aratz,ufz,alpn,rofn,
&               acin,ufin,alpin,rofin,acex,ufex,alpex,rofex,
&               vminz,jz,jmod,nz,nin,nex,liquid)
C
C      EVALUATE ADVECTION TERM CUT-OFF FUNCTIONS
C
      phig = min(one, max(zero, (alpg-eps1)/(eps2-eps1)))
      phif = min(one, max(zero, (alpf-eps1)/(eps2-eps1)))
C
C      COMPUTE C0, Cg & ANNULAR FRACTION ann
C
      call c0fcn(alpg,c0bz(jz),c0sz(jz),c0,cg,ann)
C
C      COMPUTE GAS AND LIQUID WALL DRAG AND DERIVATIVES
C
      theta = phif
      alpgdz = avgag*rvolz
      alpfdz = avgaf*rvolz
C
      call fwallz (fwg,fwf,dfgdug,dffdug,
&               dhz(jz),theta,fmltz(jz),formz(jz),absrz(jz),
&               frez(jz),ug,uf,alpgdz,alpfdz,
&               pc,tgc,tfc,xac,rhog,rhof,ilq)
C
C      ADD FALLING FILM CORRECTION TERM TO LIQUID WALL DRAG
C      IF LIQUID FLOW IS DOWNWARD (NOT USED CURRENTLY!)
C
      cosg = cosz(jz)*max(zero, sign(one, cosz(jz)*uf))
      fwf = fwf + theta*ann*alpf*(rhof-rhog)*cosg
&         *(one - two*alpf/(three*frez(jz)))
C
C      COMPUTE INTERFACIAL DRAG AND DERIVATIVES
C
      urel = cg*ug - c0*uf
      fidz = cizn(jz)*(abs(urel) + epsv)*urel
      dfddug = cizn(jz)*cg*(two*abs(urel) + epsv)
      dffdug = -cizn(jz)*c0*(two*abs(urel) + epsv)
C
      alpmin = min(alpn(jzt), alpn(jzb))
      phiw = min(one, max(zero, (alpmin-eps1)/(eps2-eps1)))
      coef = (one - ann)*alpg*phiw
      fiwz = coef*(fwg + fwf)
      dfwdug = coef*dfgdug
      dfwduf = coef*dffdug
C
      fi = fidz + fiwz
      dfidug = dfddug + dfwdug
      dfiduf = dfdduf + dfwduf
C
C      CALCULATE 2X2 SYSTEM GAS MOMENTUM EQUATION COEFFICIENTS
C
      dtz = rdelt*aratz(jz)
      fiterm = fi - dfidug*ug - dfiduf*uf
C
      az11 = dtz*arog + dfgdug + dfidug
      az12 = dfiduf
      cz1 = alpgdz
      bz1 = advg*rvolz*phig + arog*dtz*ug
&         + rhog*cosz(jz)*alpgdz*dzm(jz)
&         - (fwg - dfgdug*ug) - fiterm
C
C      CALCULATE 2X2 SYSTEM LIQUID MOMENTUM EQUATION COEFFICIENTS

```

```

      az21 = -dfidug
      az22 = dtz*arof + dffduf - dfiduf
      cz2 = alpfdz
      bz2 = advf*rvolz*phif + arof*dtz*uf
      &      + rhof*cosz(jz)*alpfdz*dzm(jz)
      &      - (fwf - dffduf*uf) + fiterm
c
c      SOLVE FOR PRESSURE EQUATION COEFFICIENTS
c
      det = az11*az22 - az12*az21
      if (det .le. epsdet) then
        ierr = 2
        write(*,910) jz,msgld
        return
      end if
      rdet = one/det
      bgz(jz) = (az22*bz1 - az12*bz2)*rdet
      bfz(jz) = (az11*bz2 - az21*bz1)*rdet
      cgz(jz) = (az22*cz1 - az12*cz2)*rdet
      cfz(jz) = (az11*cz2 - az21*cz1)*rdet
c
100 continue
c
c      FORMATS
c
910 format(/,' 2x2 determinant is nearly zero for jz = ',i3,
      &      ' in explld',/, ' in the ',a,' section')
c
      return
end

```

EXPL2D

```

      subroutine expl2d (bgz,bfz,cgz,cfz,dgx,dfx,egx,efx,
      &      acz,aratz,dhz,cosz,dzm,ugz,ufz,absrz,fmltz,
      &      formz,frez,cizn,cixn,c0bz,c0sz,
      &      acx,aratx,dhx,cosx,dxm,wgx,wfx,absrx,fmltx,
      &      formx,frex,
      &      azz,axx,volc,pn,alpn,tgn,tfn,xan,rogn,rofn,
      &      theta,txg,txf,
      &      alpin,rogin,rofin,alpex,rogex,rofex,
      &      rdelt,vminz,vminx,
      &      icc,nx,nxmax,nchn,nzpl,nzp2,nzp3,ierr,ilq)
c
c      *****
c      *
c      * SUBROUTINE expl2d
c      *
c      * THIS ROUTINE COMPUTES THE NEW TIME STEP FLUID VELOCITIES
c      * AT EACH CELL FACE AS A LINEAR FUNCTION OF THE NEW TIME
c      * STEP PRESSURE DIFFERENCE ACROSS THE CELL FACE FOR THE TWO
c      * DIMENSIONAL MIDDLE SECTION OF THE ASSEMBLY. COEFFICIENTS
c      * FORMING THESE LINEAR EXPRESSIONS ARE FUNCTIONS OF OLD TIME
c      * STEP QUANTITIES; THEREFORE, THIS CALCULATION IS ONLY DONE
c      * ONCE AT THE BEGINING OF EACH TIME STEP.
c      * THE EXPRESSIONS HAVE THE FOLLOWING FORM:
c      *
c      * FOR GAS PHASE:
c      *
c      *      n+1      n      n      n+1      n+1
c      *      u      = B      + C      *(P      - P      )
c      *      g,j+1/2      g,j+1/2      g,j+1/2      j      j+1
c      *
c      *      n+1      n      n      n+1      n+1
c      *      w      = D      + E      *(P      - P      )
c      *      g,i+1/2      g,i+1/2      g,i+1/2      i      i+1
c      *

```

```

C      *
C      *   FOR LIQUID PHASE:
C      *
C      *       n+1      n      n      n+1      n+1
C      *       u      = B      + C      *(P      - P      )
C      *       f,j+1/2    f,j+1/2    f,j+1/2    j      j+1
C      *
C      *       n+1      n      n      n+1      n+1
C      *       w      = D      + E      *(P      - P      )
C      *       f,i+1/2    f,i+1/2    f,i+1/2    i      i+1
C      *
C      *   WHERE:   B = bgz      D = dgx
C      *             g          g
C      *             B = bfz      D = dfx
C      *             f          f
C      *             C = cgz      E = egx
C      *             g          g
C      *             C = cfz      E = efx
C      *             f          f
C      *
C      *   ARGUMENTS (O=Output, I=Input):
C      *
C      *   O   bgz = SEE ABOVE; GAS PHASE CONSTANT TERM; Z-DIRECTION
C      *   O   bfz = SEE ABOVE; LIQUID PHASE CONSTANT TERM; Z-DIRECTION
C      *   O   cgz = SEE ABOVE; GAS PHASE PRESSURE COEFFICIENT; Z-DIR.
C      *   O   cfz = SEE ABOVE; LIQUID PHASE PRESSURE COEFFICIENT; Z-DIR
C      *   O   dgx = SEE ABOVE; GAS PHASE CONSTANT TERM; X-DIRECTION
C      *   O   dfx = SEE ABOVE; LIQUID PHASE CONSTANT TERM; X-DIRECTION
C      *   O   egx = SEE ABOVE; GAS PHASE PRESSURE COEFFICIENT; X-DIR.
C      *   O   efx = SEE ABOVE; LIQUID PHASE PRESSURE COEFFICIENT; X-DIR
C      *
C      *   Z-FACE:
C      *   I   acz = AREA
C      *   I   aratz = RATIO OF LOCAL FACE AREA TO AVERAGE CELL AREA
C      *   I   dhz = HYDRAULIC DIAMETER
C      *   I   cosz = cos*g
C      *   I   dzm = MOMENTUM CELL LENGTH
C      *   I   ugz = GAS VELOCITY
C      *   I   ufz = LIQUID VELOCITY
C      *   I   absrz = ABSOLUTE ROUGHNESS
C      *   I   fmltz = FRICTION MULTIPLIER
C      *   I   formz = FORM LOSS COEFFICIENT
C      *   I   frez = HYDRAULIC DIAMETER CORRECTION FACTOR, Kh
C      *   I   cizn = GENERALIZED INTERFACIAL DRAG COEFFICIENT; AXIAL
C      *   I   cixn = GENERALIZED INTERFACIAL DRAG COEFFICIENT; AZIMUTHAL
C      *   I   c0bz = BUBBLE REGIME DISTRIBUTION COEFFICIENT
C      *   I   c0sz = SLUG REGIME DISTRIBUTION COEFFICIENT
C      *
C      *   X-FACE:
C      *   I   acx = AREA
C      *   I   aratx = RATIO OF LOCAL FACE AREA TO AVERAGE CELL AREA
C      *   I   dhx = HYDRAULIC DIAMETER
C      *   I   cosx = cos*g
C      *   I   dxm = MOMENTUM CELL LENGTH
C      *   I   wgx = GAS VELOCITY
C      *   I   wfx = LIQUID VELOCITY
C      *   I   absrx = ABSOLUTE ROUGHNESS
C      *   I   fmltx = FRICTION MULTIPLIER
C      *   I   formx = FORM LOSS COEFFICIENT
C      *   I   frex = HYDRAULIC DIAMETER CORRECTION FACTOR, Kh
C      *
C      *   CELL:
C      *   I   azz = AREA; Z-DIR.
C      *   I   axx = AREA; X-DIR.
C      *   I   volc = VOLUME

```



```

c      * I      pn = PRESSURE
c      * I      alpn = VOID FRACTION
c      * I      tgn = GAS TEMPERATURE
c      * I      tfn = LIQUID TEMPERATURE
c      * I      xan = AIR MASS FRACTION
c      * I      rogn = GAS DENSITY
c      * I      rofn = LIQUID DENSITY
c      * I      theta = FRACTION OF WALL WETTED BY LIQUID
c      * I      txg = INTER-SUBCHANNEL TURBULENT EXCHANGE - GAS
c      * I      txf = INTER-SUBCHANNEL TURBULENT EXCHANGE - LIQUID
c      * I      alpin = VOID FRACTION IN TOP SECTION nzt-1 OR PLENUM CELL
c      * I      rogin = GAS DENSITY IN TOP SECTION nzt-1 OR PLENUM CELL
c      * I      rofin = LIQUID DENSITY IN TOP SECTION nzt-1 OR PLENUM CELL
c      * I      alpex = VOID FRACTION IN BOTTOM SECTION 2 OR T.B. CELL
c      * I      rogex = GAS DENSITY IN BOTTOM SECTION 2 OR T.B. CELL
c      * I      rofex = LIQUID DENSITY IN BOTTOM SECTION 2 OR T.B. CELL
c      *
c      * OTHER:
c      * I      rdelt = RECIPROCAL dt
c      * I      vminz = MINIMUM Z-VELOCITY FOR FULL DONORING
c      * I      vminx = MINIMUM X-VELOCITY FOR FULL DONORING
c      * I      icc = POINTER TO ADJACENT AZIMUTHAL CELLS
c      * I      nx = NUMBER OF SUBCHANNELS WITHIN A CHANNEL
c      * I      nxmax = ARRAY DIMENSION
c      * I      nchn = ARRAY DIMENSION
c      * I      nzp1 = ARRAY DIMENSION
c      * I      nzp2 = ARRAY DIMENSION
c      * I      nzp3 = ARRAY DIMENSION
c      * I      ierr = ERROR FLAG
c      * I      ilq = LIQUID IDENTIFIER (.true.==>liquid, .false.==>gas)
c      *
c      *****
c
c      implicit real (a-h,o-z), integer (i-n)
c      logical liquid
c
c      dimension bgz(nzp3,nxmax,nchn), dgx(nzp2,nxmax,nchn),
c      &          bfz(nzp3,nxmax,nchn), dfx(nzp2,nxmax,nchn),
c      &          cgz(nzp3,nxmax,nchn), egx(nzp2,nxmax,nchn),
c      &          cfz(nzp3,nxmax,nchn), efx(nzp2,nxmax,nchn)
c
c      dimension acz(nzp3,nxmax,nchn), aratz(nzp3,nxmax,nchn),
c      &          dhz(nzp3,nxmax,nchn), cosz(nzp3,nxmax,nchn), dzm(nzp3),
c      &          ugz(nzp3,nxmax,nchn), ufz(nzp3,nxmax,nchn),
c      &          absrz(nzp3,nxmax,nchn), fmltz(nzp3,nxmax,nchn),
c      &          formz(nzp3,nxmax,nchn), frez(nzp3,nxmax,nchn),
c      &          cizn(nzp3,nxmax,nchn), cixn(nzp3,nxmax,nchn),
c      &          c0bz(nzp3,nxmax,nchn), c0sz(nzp3,nxmax,nchn)
c
c      dimension acx(nzp2,nxmax,nchn), aratx(nzp2,nxmax,nchn),
c      &          dhx(nzp2,nxmax,nchn), cosx(nzp2,nxmax,nchn), dxm(nchn),
c      &          wgx(nzp2,nxmax,nchn), wfx(nzp2,nxmax,nchn),
c      &          absrx(nzp2,nxmax,nchn), fmltx(nzp2,nxmax,nchn),
c      &          formx(nzp2,nxmax,nchn), frex(nzp2,nxmax,nchn)
c
c      dimension azz(nzp2,nxmax,nchn), axx(nzp2,nxmax,nchn),
c      &          volc(nzp2,nxmax,nchn), pn(nzp2,nxmax,nchn),
c      &          alpn(nzp2,nxmax,nchn), tgn(nzp2,nxmax,nchn),
c      &          tfn(nzp2,nxmax,nchn), xan(nzp2,nxmax,nchn),
c      &          rogn(nzp2,nxmax,nchn), rofn(nzp2,nxmax,nchn),
c      &          theta(nzp2,nxmax,nchn),
c      &          txg(4,nzp2,nxmax,nchn), txf(4,nzp2,nxmax,nchn),
c      &          icc(2,nxmax,nchn), nx(nchn)

```

```

      parameter (mxnz=100)
      dimension avgagx(mxnz), avgafx(mxnz),
&          avgagz(mxnz), avgafz(mxnz),
&          advgx(mxnz), advfx(mxnz),
&          advgz(mxnz), advfz(mxnz)

c
      parameter (zero=0.0, half=0.5, one=1.0, two=2.0, three=3.0)
c
      data epsv/0.001/, eps1/0.001/, eps2/0.01/, epsdet/1.0e-20/
c
c----- LOOP OVER EACH FLOW CHANNEL -----
c
      do 300 k=1,nchn
         nsub = nx(k)
         if (nsub .gt. 1) then
c
c----- SOLVE X-MOMENTUM BALANCE -----
c
            do 100 ix=1,nsub
c
c              CALCULATE X-MOMENTUM ADVECTION TERMS
c
               liquid = .false.
               call avecx (advgx,avgagx,acx,acz,axx,aratx,wgx,ugz,alpn,
&                   rogn,vminz,vminx,ix,k,icc,nzpl,nzp2,nzp3,
&                   nxmax,nchn,liquid)
c
               liquid = .true.
               call avecx (advfx,avgafx,acx,acz,axx,aratx,wfx,ufz,alpn,
&                   rofn,vminz,vminx,ix,k,icc,nzpl,nzp2,nzp3,
&                   nxmax,nchn,liquid)
c
            do 100 jz=2,nzpl
c
c              SET LOCAL POINTERS TO MASS CELLS FORMING THE
c              LEFT (ixl) AND RIGHT (ixr) PARTS OF MOMENTUM CELL
c
               ixl = icc(1,ix,k)
               ixr = ix
c
               wgix = wxg(jz,ix,k)
               wfix = wfx(jz,ix,k)
c
c              CALCULATE VOLUME FRACTIONS FOR LEFT AND RIGHT CELLS
c
               rvolx = two/(volc(jz,ixl,k) + volc(jz,ixr,k))
               fl = volc(jz,ixl,k)/(volc(jz,ixl,k) + volc(jz,ixr,k))
               fr = one - fl
c
c              CALCULATE VOLUME AVERAGED PROPERTIES
c
               pc = fl*pn(jz,ixl,k) + fr*pn(jz,ixr,k)
               tgc = fl*tgn(jz,ixl,k) + fr*tgn(jz,ixr,k)
               tfc = fl*tfn(jz,ixl,k) + fr*tfn(jz,ixr,k)
               xac = fl*xan(jz,ixl,k) + fr*xan(jz,ixr,k)
c
               alpg = fl*alpn(jz,ixl,k) + fr*alpn(jz,ixr,k)
               rhog = fl*rogn(jz,ixl,k) + fr*rogn(jz,ixr,k)
               arog = fl*alpn(jz,ixl,k)*rogn(jz,ixl,k) +
&                   fr*alpn(jz,ixr,k)*rogn(jz,ixr,k)
c
               alpf = one - alpg
               rhof = fl*rofn(jz,ixl,k) + fr*rofn(jz,ixr,k)
               arof = fl*(one - alpn(jz,ixl,k))*rofn(jz,ixl,k) +

```

```

      &      fr*(one - alpn(jz,ixr,)))*rofn(jz,ixr,k)
c
      thetax = fl*theta(jz,ixl,k) + fr*theta(jz,ixr,k)
c
c      EVALUATE ADVECTION TERM CUT-OFF FUNCTIONS
c
      phig = min(one, max(zero, (alpg-eps1)/(eps2-eps1)))
      phif = min(one, max(zero, (alpf-eps1)/(eps2-eps1)))
c
c      COMPUTE GAS AND LIQUID WALL DRAG AND DERIVATIVES
c
      alpgdx = avgagx(jz)*rvolx
      alpfdx = avgafx(jz)*rvolx
c
      call fwallx(fwg,fwf,dfgdwg,dfdfwf,
&              dhx(jz,ix,k),thetax,fm1tx(jz,ix,k),formx(jz,ix,k),
&              absrx(jz,ix,k),frex(jz,ix,k),wgix,wfix,
&              alpgdx,alpfdx,pc,tgc,tfc,xac,rhog,rhof,ilq)
c
c      COMPUTE INTERFACIAL DRAG AND DERIVATIVES
c
      cixl = half*(cixn(jz,ixl,k) + cixn(jz+1,ixl,k))
      cixr = half*(cixn(jz,ixr,k) + cixn(jz+1,ixr,k))
      cixavg = fl*cixl + fr*cixr
      wrel = wgix - wfix
c
      fi = cixavg*(abs(wrel) + epsv)*wrel
      dfidwg = cixavg*(two*abs(wrel) + epsv)
      dfidwf = -dfidwg
c
c      CALCULATE 2X2 SYSTEM GAS MOMENTUM EQUATION COEFFICIENTS
c
      dtx = rdelt*aratx(jz,ix,k)
      fiterm = fi - dfidwg*wgix - dfidwf*wfix
c
      ax11 = dtx*arog + dfgdwg + dfidwg
      ax12 = dfidwf
      ex1 = alpgdx
      dx1 = advgx(jz)*rvolx*phig + arog*dtx*wgix
&          + rhog*cosx(jz,ix,k)*alpgdx*dxm(k)
&          - (fwg - dfgdwg*wgix) - fiterm
c
c      CALCULATE 2X2 SYSTEM LIQUID MOMENTUM EQUATION COEFFICIENTS
c
      ax21 = -dfidwg
      ax22 = dtx*arof + dfdfwf - dfidwf
      ex2 = alpfdx
      dx2 = advfx(jz)*rvolx*phif + arof*dtx*wfix
&          + rhof*cosx(jz,ix,k)*alpfdx*dxm(k)
&          - (fwf - dfdfwf*wfix) + fiterm
c
c      SOLVE FOR PRESSURE EQUATION COEFFICIENTS
c
      det = (ax11*ax22 - ax12*ax21)
      if (det .le. epsdet) then
        ierr = 2
        write (*,900) jz,ix,k
        return
      end if
      rdet = one/det
      dgx(jz,ix,k) = (ax22*dx1 - ax12*dx2)*rdet
      dfx(jz,ix,k) = (ax11*dx2 - ax21*dx1)*rdet
      egx(jz,ix,k) = (ax22*ex1 - ax12*ex2)*rdet
      efx(jz,ix,k) = (ax11*ex2 - ax21*ex1)*rdet

```

```

100    continue
      end if
c
c----- SOLVE Z-MOMENTUM BALANCE -----
c
      do 200 ix=1,nsub
c
c      CALCULATE Z-MOMENTUM ADVECTION TERMS
c
        liquid = .false.
        call avecz (advgz,avgagz,acx,acz,azz,aratz,wgx,ugz,alpn,
&                  rogn,alpin,rogin,alpex,rogex,vminz,vminx,ix,
&                  k,icc,nzp2,nzp3,nxmax,nchn,liquid)
c
        liquid = .true.
        call avecz (advfz,avgafz,acx,acz,azz,aratz,wfx,ufz,alpn,
&                  rofn,alpin,rofin,alpex,rofex,vminz,vminx,ix,
&                  k,icc,nzp2,nzp3,nxmax,nchn,liquid)
c
      do 200 jz=2,nzp2
c
c      SET LOCAL POINTERS TO MASS CELLS FORMING THE
c      TOP (jzt) AND BOTTOM (jzb) PARTS OF MOMENTUM CELL
c
        jzt = jz - 1
        jzb = jz
c
        ugjz = ugz(jz,ix,k)
        ufjz = ufz(jz,ix,k)
c
c      COMPUTE VOLUME FRACTIONS FOR TOP AND BOTTOM CELLS
c
        rvolz = two/(volc(jzt,ix,k) + volc(jzb,ix,k))
        ft = volc(jzt,ix,k)/(volc(jzt,ix,k) + volc(jzb,ix,k))
        fb = one - ft
c
c      CALCULATE VOLUME AVERAGED PROPERTIES
c
        pc = ft*pn(jzt,ix,k) + fb*pn(jzb,ix,k)
        xac = ft*xan(jzt,ix,k) + fb*xan(jzb,ix,k)
        tgc = ft*tgn(jzt,ix,k) + fb*tgn(jzb,ix,k)
        tfc = ft*tfn(jzt,ix,k) + fb*tfn(jzb,ix,k)
c
        alpg = ft*alpn(jzt,ix,k) + fb*alpn(jzb,ix,k)
        rhog = ft*rogn(jzt,ix,k) + fb*rogn(jzb,ix,k)
        arog = ft*alpn(jzt,ix,k)*rogn(jzt,ix,k) +
&             fb*alpn(jzb,ix,k)*rogn(jzb,ix,k)
c
        alpf = one - alpg
        rhof = ft*rofn(jzt,ix,k) + fb*rofn(jzb,ix,k)
        arof = ft*(one - alpn(jzt,ix,k))*rofn(jzt,ix,k) +
&             fb*(one - alpn(jzb,ix,k))*rofn(jzb,ix,k)
c
        thetaz = ft*theta(jzt,ix,k)+fb*theta(jzb,ix,k)
c
        txgjz = ft*txg(3,jzt,ix,k) + fb*txg(3,jzb,ix,k)
        txfjz = ft*txf(3,jzt,ix,k) + fb*txf(3,jzb,ix,k)
c
c      EVALUATE ADVECTION TERM CUT-OFF FUNCTIONS
c
        phig = min(one, max(zero, (alpg-eps1)/(eps2-eps1)))
        phif = min(one, max(zero, (alpf-eps1)/(eps2-eps1)))
c
c      COMPUTE C0, Cg & ANNULAR FRACTION ann

```

```

C      call c0fcn(alpg,c0bz(jz,ix,k),c0sz(jz,ix,k),c0,cg,ann)
C
C      COMPUTE GAS AND LIQUID PHASE WALL DRAG AND DERIVATIVES
C
      alpgdz = avgagz(jz)*rvolz
      alpfdz = avgafz(jz)*rvolz
C
      call fwallz (fwg,fwf,dfgdug,dffduf,
&                dhz(jz,ix,k),thetaz,fmltz(jz,ix,k),formz(jz,ix,k),
&                absrz(jz,ix,k),frez(jz,ix,k),ugjz,ufjz,
&                alpgdz,alpfdz,pc,tgc,tfc,xac,rhog,rhof,ilq)
C
C      ADD FALLING FILM CORRECTION TERM TO LIQUID WALL DRAG
C      IF LIQUID FLOW IS DOWNWARD (NOT USED CURRENTLY!)
C
      cosg = cosz(jz,ix,k)*max(zero, sign(one, cosz(jz,ix,k)*ufjz))
      fwf = fwf + thetaz*ann*alp*(rhof-rhog)*cosg
&          *(one - two*alp/(three*frez(jz,ix,k)))
C
C      COMPUTE INTERFACIAL DRAG AND DERIVATIVES
C
      urel = cg*ugjz - c0*ufjz
      fidz = cizn(jz,ix,k)*(abs(urel) + epsv)*urel
      dfddug = cizn(jz,ix,k)*cg*(two*abs(urel) + epsv)
      dffduf = -cizn(jz,ix,k)*c0*(two*abs(urel) + epsv)
C
      alpmin = min(alpn(jzt,ix,k) , alpn(jzb,ix,k))
      phiw = min(one, max(zero, (alpmin-eps1)/(eps2-eps1)))
      coef = (one - ann)*alpg*phiw
      fiwz = coef*(fwg + fwf)
      dfwdug = coef*dfgdug
      dfwduf = coef*dffduf
C
      fi = fidz + fiwz
      dfidug = dfddug + dfwdug
      dfiduf = dffduf + dfwduf
C
C      CALCULATE 2X2 SYSTEM GAS MOMENTUM EQUATION COEFFICIENTS
C
      dtz = rdelt*aratz(jz,ix,k)
      fiterm = fi - dfidug*ugjz - dfiduf*ufjz
C
      az11 = dtz*arog + dfgdug + dfidug
      az12 = dfiduf
      cz1 = alpgdz
      bz1 = advgz(jz)*rvolz*phig + arog*dtz*ugjz
&          + rhog*cosz(jz,ix,k)*alpgdz*dzm(jz)
&          - (fwg - dfgdug*ugjz) - fiterm - txgjz
C
C      CALCULATE 2X2 SYSTEM LIQUID MOMENTUM EQUATION COEFFICIENTS
C
      az21 = -dfidug
      az22 = dtz*arof + dffduf - dfiduf
      cz2 = alpfdz
      bz2 = advfz(jz)*rvolz*phif + arof*dtz*ufjz
&          + rhof*cosz(jz,ix,k)*alpfdz*dzm(jz)
&          - (fwf - dffduf*ufjz) + fiterm - txfjz
C
C      SOLVE FOR PRESSURE EQUATION COEFFICIENTS
C
      det = (az11*az22 - az12*az21)
      if (det .le. epsdet) then
        ierr = 2

```

```

        write(*,910) jz,ix,k
        return
    end if
    rdet = one/det
    bgz(jz,ix,k) = (az22*bz1 - az12*bz2)*rdet
    bfz(jz,ix,k) = (az11*bz2 - az21*bz1)*rdet
    cgz(jz,ix,k) = (az22*cz1 - az12*cz2)*rdet
    cfz(jz,ix,k) = (az11*cz2 - az21*cz1)*rdet
c
200    continue
c
300    continue
c
c----- FORMATS -----
c
900    format(/,' X mom. 2x2 determinant is nearly zero for',/,
        &      ' jz = ',i3,' ix = ',i3,' k = ',i3,' in expl2d',/,
        &      ' in the middle section')
c
910    format(/,' Z mom. 2x2 determinant is nearly zero for',/,
        &      ' jz = ',i3,' ix = ',i3,' k = ',i3,' in expl2d',/,
        &      ' in the middle section')
c
        return
    end

```

EXPLCT

```

subroutine explct (bgz,bfz,cgz,cfz,dgx,dfx,egx,efx,
&                acz,aratz,dhz,cosz,ugz,ufz,absrz,fmltz,formz,
&                frez,dzm,cizn,cixn,c0bz,c0sz,
&                acx,aratx,dhx,cosx,wgx,wfx,absrx,fmltx,formx,
&                frex,dxm,
&                azz,axx,volc,pn,alpn,tgn,tfn,xan,rogn,rofn,
&                theta,txf,txg,
&                act,aratt,dht,cost,dzmt,ugt,uft,absrt,fmltt,
&                formt,fret,citn,c0bt,c0st,
&                azt,volt,ptn,alptn,tgtn,tftn,xatn,rogn,roftn,
&                bgt,bft,cgt,cft,
&                acb,aratb,dhb,cosb,dzmb,ugb,ufb,absrb,fmltb,
&                formb,freb,cibn,c0bb,c0sb,
&                azb,volb,pbn,alpb,tn,tgbn,tfbn,xabn,rogn,rofbn,
&                bgb,bfb,cgb,cfb,
&                acin,ugin,ufin,alpin,rogin,rofin,
&                acex,ugex,ufex,alpex,rogex,rofex,
&                nx,icc)
c
c *****
c *
c * SUBROUTINE explct
c *
c * SUBROUTINE TO PERFORM EXPLICIT FLUID CALCULATIONS FOR EACH
c * TIME STEP
c *
c *****
c
implicit real (a-h,o-z), integer (i-n)
character*6 msgld(2)
c
c MIDDLE SECTION ARRAYS
c
dimension acz(nzp3,nxmax,nchn), acx(nzp2,nxmax,nchn),
&          aratz(nzp3,nxmax,nchn), aratx(nzp2,nxmax,nchn),
&          dhz(nzp3,nxmax,nchn), dhx(nzp2,nxmax,nchn),
&          cosz(nzp3,nxmax,nchn), cosx(nzp2,nxmax,nchn),
&          ugz(nzp3,nxmax,nchn), wxg(nzp2,nxmax,nchn),

```

```

&      ufz(nzp3,nxmax,nchn),    wfx(nzp2,nxmax,nchn),
&      absrz(nzp3,nxmax,nchn),  absrx(nzp2,nxmax,nchn),
&      fmltz(nzp3,nxmax,nchn),  fmltx(nzp2,nxmax,nchn),
&      formz(nzp3,nxmax,nchn),  formx(nzp2,nxmax,nchn),
&      frez(nzp3,nxmax,nchn),   frex(nzp2,nxmax,nchn),
&      dzm(nzp3),               dxm(nchn),
&      cizn(nzp3,nxmax,nchn),
&      cixn(nzp3,nxmax,nchn),
&      c0bz(nzp3,nxmax,nchn),
&      c0sz(nzp3,nxmax,nchn)
C
dimension  azz(nzp2,nxmax,nchn),  axx(nzp2,nxmax,nchn),
&          volc(nzp2,nxmax,nchn),  pn(nzp2,nxmax,nchn),
&          alpn(nzp2,nxmax,nchn),  tgn(nzp2,nxmax,nchn),
&          tfn(nzp2,nxmax,nchn),   xan(nzp2,nxmax,nchn),
&          rogn(nzp2,nxmax,nchn),  rofn(nzp2,nxmax,nchn),
&          theta(nzp2,nxmax,nchn),
&          txg(4,nzp2,nxmax,nchn), txf(4,nzp2,nxmax,nchn),
&          icc(2,nxmax,nchn),      nx(nchn)
C
dimension  bgz(nzp3,nxmax,nchn),  dgx(nzp2,nxmax,nchn),
&          bfz(nzp3,nxmax,nchn),  dfx(nzp2,nxmax,nchn),
&          cgz(nzp3,nxmax,nchn),  egx(nzp2,nxmax,nchn),
&          cfz(nzp3,nxmax,nchn),  efz(nzp2,nxmax,nchn)
C
C      TOP SECTION ARRAYS
C
dimension  act(nzt),  aratt(nzt),  dht(nzt),  cost(nzt),
&          dzmt(nzt),  ugt(nzt),   uft(nzt),  absrt(nzt),
&          fmltt(nzt),  formt(nzt),  fret(nzt),  citn(nzt),
&          c0bt(nzt),  c0st(nzt)
C
dimension  azt(nzt),  volt(nzt),  ptn(nzt),  alptn(nzt),
&          tgtn(nzt),  tftn(nzt),  xatn(nzt),  rogtm(nzt),
&          roftn(nzt)
C
dimension  bgt(nzt),  bft(nzt),  cgt(nzt),  cft(nzt)
C
C      BOTTOM SECTION ARRAYS
C
dimension  acb(nzb),  aratb(nzb),  dnb(nzb),  cosb(nzb),
&          dzmb(nzb),  ugb(nzb),   ufb(nzb),  absrb(nzb),
&          fmltb(nzb),  formb(nzb),  freb(nzb),  cibn(nzb),
&          c0bb(nzb),  c0sb(nzb)
C
dimension  azb(nzb),  volb(nzb),  pbn(nzb),  alpbn(nzb),
&          tgbn(nzb),  tfbn(nzb),  xabn(nzb),  rogbn(nzb),
&          rofbn(nzb)
C
dimension  bgb(nzb),  bfb(nzb),  cgb(nzb),  cfb(nzb)
C
C      ARRAYS TO HOLD INLET AND OUTLET PARAMETERS
C
dimension  acin(nsubc),  acex(nsubc),
&          ugin(nsubc),  ugex(nsubc),
&          ufin(nsubc),  ufex(nsubc),
&          alpin(nsubc),  alpex(nsubc),
&          rogin(nsubc),  rogex(nsubc),
&          rofin(nsubc),  rofex(nsubc)
C
include 'params.inc'
C
parameter (zero=0.0, half=0.5, one=1.0)
data msgld(1)/'top  '/,

```

```

      msgld(2)='bottom'/
      data eps1/0.001/, eps2/0.01/
c
c  INITIALIZATIONS
c
      ierr = 0
c
c----- INLET (PLENUM) FACE -----
c
      call explpl (bgt(1),bft(1),cgt(1),cft(1),
&                act(1),aratt(1),dht(1),cost(1),dzmt(1),ugt(1),uft(1),
&                absrt(1),fmltt(1),formt(1),fret(1),citrn(1),c0bt(1),
&                c0st(1),qgin,qfin,act(2),ugt(2),uft(2),
&                volpl,ppln,alppln,tgpln,tfpln,xapln,rogpln,rofpln,
&                azt(1),volt(1),ptn(1),alptn(1),tgtn(1),tftn(1),
&                xatn(1),rogtn(1),rofn(1),alptn(2),rogtn(2),roftn(2),
&                rdelt,vminz,ptmp,iupp,
&                ibond,ierr,ilq)
      if (ierr .eq. 2) return
      if (iupp .eq. 1) then
        ppl=ptmp
      end if
c
c----- TOP SECTION FACES -----
c
c  SETUP INLET BOUNDARY ARRAYS
c
      acin(1) = act(1)
      ugin(1) = ugt(1)
      ufin(1) = uft(1)
      alpin(1) = alppln
      rogin(1) = rogpln
      rofin(1) = rofpln
c
c  SETUP OUTLET BOUNDARY ARRAYS
c
      isub = 0
      do 30 ic=1,nchn
        nsub = nx(ic)
        do 20 ix=1,nsub
          isub = isub + 1
          acex(isub) = acz(2,ix,ic)
          ugex(isub) = ugz(2,ix,ic)
          ufex(isub) = ufz(2,ix,ic)
          alpex(isub) = alpn(2,ix,ic)
          rogex(isub) = rogn(2,ix,ic)
          rofex(isub) = rofn(2,ix,ic)
20      continue
30      continue
c
c  PERFORM EXPLICIT CALCULATIONS FOR TOP SECTION
c
      nin = 1
      jstrt = 2
      jend = nzt
      jmod = 0
      call explld (bgt,bft,cgt,cft,
&                act,aratt,dht,cost,dzmt,ugt,uft,
&                absrt,fmltt,formt,fret,citrn,c0bt,c0st,
&                azt,volt,ptn,alptn,tgtn,tftn,xatn,rogtn,roftn,
&                acin,ugin,ufin,alpin,rogin,rofin,
&                acex,ugex,ufex,alpex,rogex,rofex,
&                rdelt,vminz,
&                nzt,nin,isub,jstrt,jend,jmod,ierr,msgld(1),ilq)

```



```

      if (ierr .eq. 2) return
c
c----- MIDDLE SECTION FACES -----
c
c      DEFINE WETTED WALL PARAMETER FOR FICTICIOUS CELLS
c
      alpft = one - alptn(nzt)
      alpfb = one - alpbn(1)
      phift = min(one, max(zero, (alpft-eps1)/(eps2-eps1)))
      phifb = min(one, max(zero, (alpfb-eps1)/(eps2-eps1)))
c
      do 35 ic=1,nchn
      do 35 ix=1,nx(ic)
         theta( 1,ix,ic) = phift
         theta(nzp2,ix,ic) = phifb
35      continue
c
c      DEFINE WETTED WALL PARAMETER FOR MIDDLE SECTION CELL
c      IF NO SOLID CALCULATIONS ARE BEING PERFORMED
c
      if (isolid .eq. 0) then
         do 36 ic=1,nchn
         do 36 ix=1,nx(ic)
         do 36 jz=2,nzpl
            alpf = one - alpn(jz,ix,ic)
            theta(jz,ix,ic) = min(one, max(zero,
4            (alpf-eps1)/(eps2-eps1)))
36      continue
         end if
c
c      SETUP BOUNDARY PARAMETERS
c
      if (nzt .eq. 1) then
         alpi = alppln
         rogi = rogpln
         rofi = rofpln
      else
         alpi = alptn(nzt-1)
         rogi = rogtn(nzt-1)
         rofi = roftn(nzt-1)
      end if
c
      if (nzb .eq. 1) then
         alpx = alptbn
         rogx = rogtbn
         rofx = roftbn
      else
         alpx = alpbn(2)
         rogx = rogbn(2)
         rofx = rofbn(2)
      end if
c
c      PERFORM EXPLICIT CALCULATIONS FOR MIDDLE SECTION
c
c      call expl2d (bgz,bfz,cgz,cfz,dgx,dfx,egx,efx,
4      acz,aratz,dhz,cosz,dzm,ugz,ufz,absrz,fmltz,
4      formz,frez,cizn,cixn,c0bz,c0sz,
4      acx,aratx,dhx,cosx,dxm,wgx,wfx,absrx,fmltx,
4      formx,frex,
4      azz,axx,volc,pn,alpn,tgn,tfn,xan,rogn,rofn,
4      theta,txg,txf,
4      alpi,rogi,rofi,alpx,rogx,rofx,
4      rdelt,vminz,vminx,
4      icc,nx,nxmax,nchn,nzp1,nzp2,nzp3,ierr,ilq)

```

```

      if (ierr .eq. 2) return
c
c----- BOTTOM SECTION FACES -----
c
c      SETUP INLET BOUNDARY ARRAYS
c
      isub = 0
      do 50 ic=1,nchn
        nsub = nx(ic)
        do 40 ix=1,nsub
          isub = isub + 1
          acin(isub) = acz(nzp2,ix,ic)
          ugin(isub) = ugz(nzp2,ix,ic)
          ufin(isub) = ufz(nzp2,ix,ic)
          alpin(isub) = alpn(nzpl,ix,ic)
          rogin(isub) = rogn(nzpl,ix,ic)
          rofin(isub) = rofn(nzpl,ix,ic)
40      continue
50      continue
c
c      SETUP OUTLET BOUNDARY ARRAYS
c
      acex(1) = acb(nzb)
      uge(1) = ugb(nzb)
      ufex(1) = ufb(nzb)
      alpex(1) = alptbn
      roge(1) = rogtbn
      rofex(1) = roftbn
c
c      PERFORM EXPLICIT CALCULATIONS FOR BOTTOM SECTION
c
      nex = 1
      jstrt = 1
      jend = nzb - 1
      jmod = 1
      call explld (bgb,bfb,cgb,cfb,
&                acb,aratb,dhb,cosb,dzmb,ugb,ufb,
&                absr,bfmltb,formb,freb,cibn,c0bb,c0sb,
&                azb,volb,pbn,alpb,tgbn,tfbn,xabn,rogbn,rofbn,
&                acin,ugin,ufin,alpin,rogin,rofin,
&                acex,uge,ufex,alpex,roge,rofex,
&                rdelt,vminz,
&                nzb,isub,nex,jstrt,jend,jmod,ierr,msgld(2),ilq)
      if (ierr .eq. 2) return
c
c----- OUTLET (TANK BOTTOM) FACE -----
c
      l = nzb
      m = nzb - 1
      call expltb (bgb(1),bfb(1),cgb(1),cfb(1),
&                acb(1),aratb(1),dhb(1),cosb(1),dzmb(1),
&                ugb(1),ufb(1),absrb(1),fmltb(1),formb(1),
&                freb(1),cibn(1),c0bb(1),c0sb(1),
&                acb(m),ugb(m),ufb(m),
&                volb,ptbn,alptbn,tgtbn,tftbn,xatbn,rogtbn,roftbn,
&                azb(1),volb(1),pbn(1),alpb(1),tgbn(1),tfbn(1),
&                xabn(1),rogbn(1),rofbn(1),alpb(m),rogbn(m),rofbn(m),
&                rdelt,vminz,
&                ierr,ilq)
      if (ierr .eq. 2) return
c
      return
      end

```

EXPLPL

```

subroutine explpl(bgz,bfz,cgz,cfz,
&               act1,aratt1,dhz,cosz,dzm,ugt1,uft1,
&               absr,fmlt,form,fre,cizn,c0b,c0s,qg,qf,
&               act2,               ugt2,uft2,
&               volpl,ppl,alpp1,tgpl,tfpl,xapl,rogpl,rofpl,
&               azt1,volt1,pt1,alpt1,tgt1,tft1,xat1,rogt1,roft1,
&               alpt2,               rogt2,roft2,
&               rdelt,vminz,ptmp,lupp,
&               ibond,ierr,ilq)

```

```

C *****
C *
C * SUBROUTINE explpl
C *
C * THIS ROUTINE COMPUTES THE NEW TIME STEP FLUID VELOCITIES
C * AT THE PLENUM CELL FACE AS A LINEAR FUNCTION OF THE NEW
C * TIME STEP PRESSURE DIFFERENCE ACROSS THE CELL FACE FOR THE
C * TOP BOUNDARY OF THE ASSEMBLY. THE COEFFICIENTS
C * FORMING THESE LINEAR EXPRESSIONS ARE FUNCTIONS OF OLD TIME
C * STEP QUANTITIES; THEREFORE, THIS CALCULATION IS ONLY DONE
C * ONCE AT THE BEGINING OF EACH TIME STEP.
C * THE EXPRESSIONS HAVE THE FOLLOWING FORM:
C *
C * FOR GAS PHASE:
C *
C *      n+1      n      n      n+1      n+1
C *      u      = B      + C      * (P      - P      )
C *      g,j+1/2  g,j+1/2  g,j+1/2  j      j+1
C *
C * FOR LIQUID PHASE:
C *
C *      n+1      n      n      n+1      n+1
C *      u      = B      + C      * (P      - P      )
C *      f,j+1/2  f,j+1/2  f,j+1/2  j      j+1
C *
C * WHERE:  B = bgz (Z-DIRECTION)
C *          g
C *          B = bfz (Z-DIRECTION)
C *          f
C *          C = cgz (Z-DIRECTION)
C *          g
C *          C = cfz (Z-DIRECTION)
C *          f
C *
C * ARGUMENTS (O=Output, I=Input):
C *
C * O  bgz = SEE ABOVE; GAS PHASE CONSTANT TERM
C * O  bfz = SEE ABOVE; LIQUID PHASE CONSTANT TERM
C * O  cgz = SEE ABOVE; GAS PHASE PRESSURE COEFFICIENT
C * O  cfz = SEE ABOVE; LIQUID PHASE PRESSURE COEFFICIENT
C *
C * TOP SECTION FACE #1:
C * I  act1 = AREA
C * I  aratt1 = RATIO OF LOCAL FACE AREA TO AVERAGE CELL AREA
C * I  dhz = HYDRAULIC DIAMETER
C * I  cosz = cos*g
C * I  dzm = MOMENTUM CELL LENGTH
C * I  ugt1 = GAS VELOCITY
C * I  uft1 = LIQUID VELOCITY
C * I  absr = ABSOLUTE ROUGHNESS
C * I  fmlt = FRICTION MULTIPLIER
C * I  form = FORM LOSS COEFFICIENT
C * I  fre = HYDRAULIC DIAMETER CORRECTION FACTOR, Kh
C * I  cizn = GENERALIZED INTERFACIAL DRAG COEFFICIENT

```

```

c      * I   c0b = BUBBLE REGIME DISTRIBUTION COEFFICIENT      *
c      * I   c0s = SLUG REGIME DISTRIBUTION COEFFICIENT      *
c      * I   qg = GAS FLOWRATE (USED FOR PRESCRIBED GAS FLOWRATE) *
c      * I   qf = LIQUID FLOWRATE (USED FOR PRESCRIBED GAS FLOWRATE) *
c      *                                           *
c      * TOP SECTION FACE #2:                               *
c      * I   act2 = AREA                                       *
c      * I   ugt2 = GAS VELOCITY                               *
c      * I   uft2 = LIQUID VELOCITY                           *
c      *                                           *
c      * PLENUM CELL:                                         *
c      * I   volpl = VOLUME                                     *
c      * I   ppl = PRESSURE                                     *
c      * I   alpp1 = VOID FRACTION                             *
c      * I   tgpl = GAS TEMPERATURE                           *
c      * I   tfpl = LIQUID TEMPERATURE                         *
c      * I   xapl = AIR MASS FRACTION                           *
c      * I   rogpl = GAS DENSITY                               *
c      * I   rofpl = LIQUID DENSITY                           *
c      *                                           *
c      * TOP SECTION CELL #1:                                  *
c      * I   azt1 = AREA                                       *
c      * I   volt1 = VOLUME                                     *
c      * I   pt1 = PRESSURE                                     *
c      * I   alpt1 = VOID FRACTION                             *
c      * I   tgt1 = GAS TEMPERATURE                           *
c      * I   tft1 = LIQUID TEMPERATURE                         *
c      * I   xat1 = AIR MASS FRACTION                           *
c      * I   rogt1 = GAS DENSITY                               *
c      * I   roft1 = LIQUID DENSITY                           *
c      *                                           *
c      * TOP SECTION CELL #2:                                  *
c      * I   alpt2 = VOID FRACTION                             *
c      * I   rogt2 = GAS DENSITY                               *
c      * I   roft2 = LIQUID DENSITY                           *
c      *                                           *
c      * OTHER:                                                *
c      * I   rdelt = RECIPROCAL dt                             *
c      * I   vminz = MINIMUM VELOCITY FOR FULL DONORING       *
c      * I   ibond = BOUNDARY CONDITION OPTION                 *
c      *           1 ==> Prescribed pressure                   *
c      *           2 ==> Prescribed Qf                         *
c      *           3 ==> Prescribed Qg                         *
c      *           4 ==> Prescribed Qf and Qg                   *
c      * I   ierr = ERROR FLAG                                  *
c      * I   ilq = LIQUID IDENTIFIER (.true.==>liquid, .false.==>gas) *
c      *                                           *
c      *****
c      implicit real (a-h,o-z), integer (i-n)
c      logical liquid
c
c      include 'knobs.inc'
c
c      parameter (zero=0.0, half=0.5, one=1.0, two=2.0, three=3.0,
c      6          grav=9.80665)
c
c      data epsv/0.001/, eps1/0.001/, eps2/0.01/, epsdet/1.0e-20/,
c      6          eps/0.00001/
c
c      iupp = 0
c
c      ----- PRELIMINARY CALCULATIONS -----
c
c      COMPUTE VOLUME FRACTIONS FOR TOP(pl) AND BOTTOM(tl) CELLS

```

```

c
  rvolz = two/(volpl + volt1)
  ft = volpl/(volpl + volt1)
  fb = one - ft

c
c  CALCULATE VOLUME AVERAGED PROPERTIES
c
  pc = ft*ppl + fb*pt1
  tgc = ft*tgpl + fb*tgt1
  tfc = ft*tfpl + fb*ttf1
  xac = ft*xapl + fb*xatl

c
  alpg = ft*alpp1 + fb*alpt1
  rhog = ft*rogpl + fb*rogt1
  arog = ft*alpp1*rogpl + fb*alpt1*rogt1

c
  alpf = one - alpg
  rhof = ft*rofpl + fb*roft1
  arof = ft*(one - alpp1)*rofpl + fb*(one - alpt1)*roft1

c
c  CALCULATE ADVECTION TERMS
c
  liquid = .false.
  call avect (advf,avgag,
    &          alpp1,rogpl,
    &          alpt1,rogt1,azt1,act1,ugt1,aratt1,
    &          alpt2,roft2,      act2,ugt2,
    &          vminz,liquid)

c
  liquid = .true.
  call avect (advf,avgaf,
    &          alpp1,rofpl,
    &          alpt1,roft1,azt1,act1,uft1,aratt1,
    &          alpt2,roft2,      act2,uft2,
    &          vminz,liquid)

c
c  EVALUATE ADVECTION TERM CUT-OFF FUNCTIONS
c
  phig = min(one, max(zero, (alpg-eps1)/(eps2-eps1)))
  phif = min(one, max(zero, (alpf-eps1)/(eps2-eps1)))

c
c  SET INTERFACIAL DRAG PARAMETERS AND FORM LOSS COEFFICIENT
c
  if (cosz.eq.zero .and. plnht.ne.zero
    & .and. alpp1.ge.atl(alphs)) then
    call c0fcn(one,c0b,c0s,c0,cg,ann)
    ci = cipln
    formpl = formhs
  else
    call c0fcn(alpg,c0b,c0s,c0,cg,ann)
    ci = cizn
    formpl = form
  end if

c
c  COMPUTE GAS AND LIQUID WALL DRAG AND DERIVATIVES
c
  theta = phif
  alpgdz = avgag*rvolz
  alpfdz = avgaf*rvolz

c
  call fwallz (fwg,fwf,dfgdug,dffduf,
    &          dhz,theta,fmlt,formpl,absr,fre,ugt1,uft1,
    &          alpgdz,alpfdz,pc,tgc,tfc,xac,rhog,rhof,ilq)

```

```

c      ADD FALLING FILM CORRECTION TERM TO LIQUID WALL DRAG
c      IF LIQUID FLOW IS DOWNWARD (NOT USED CURRENTLY!)
c
c      cosg = cosz*max(zero, sign(one, cosz*uft1))
c      fwf = fwf + theta*ann*alf*(rhoF-rhog)*cosg
c      &      *(one - two*alf/(three*fre))
c
c      COMPUTE INTERFACIAL DRAG AND DERIVATIVES
c
c      urel = cg*ugt1 - c0*uft1
c      fidz = ci*(abs(urel) + epsv)*urel
c      dfddug = ci*cg*(two*abs(urel) + epsv)
c      dfdduf = -ci*c0*(two*abs(urel) + epsv)
c
c      alpmin = min(alppl, alpt1)
c      phiw = min(one, max(zero, (alpmin-eps1)/(eps2-eps1)))
c      coef = (one - ann)*alpg*phiw
c      fiwz = coef*(fwg + fwf)
c      dfwdug = coef*dfgdug
c      dfwduf = coef*dfdduf
c
c      fi = fidz + fiwz
c      dfidug = dfddug + dfwdug
c      dfiduf = dfdduf + dfwduf
c
c      COMPUTE VOID GRADIENT TERM FOR HORIZONTAL STRATIFIED FLOW
c
c      sinz = sqrt(grav**2 - cosz**2)
c      if (alphs .ge. zero) then
c          alweir = alpt1
c      else
c          if (alpt1 .gt. alppl) then
c              alweir = one
c          else
c              alweir = alpt1
c          end if
c      end if
c      strat = (rofpl - rogpl)*sinz*plnht*alppl*(one - alppl)
c      &      *(alweir - alppl)*act1*rvolz
c
c      MISC.
c
c      dtz = rdelt*aratt1
c      fiterm = fi - dfidug*ugt1 - dfiduf*uft1
c
c----- CALCULATE 2X2 SYSTEM GAS COEFFICIENTS -----
c
c      if (ibond.eq.3 .or. ibond.eq.4) then
c
c          USE SPECIFIED GAS FLOW
c
c          qm = act1*alppl*vminz
c          qp = -act1*alpt1*vminz
c          if (qg .ge. qm) then
c              az11 = act1*alppl
c              bz1 = qg
c          else if (qg .le. qp) then
c              az11 = act1*alpt1
c              bz1 = qg
c          else
c              if (abs(alppl - alpt1) .lt. eps) then
c                  az11 = act1*half*(alppl + alpt1)
c                  bz1 = qg
c              else

```

```

      az11 = (act1/vminz)*(alpl1 - alpt1)
      b2m4ac = (act1*half*(alpl1 + alpt1))**2
      + two*act1*(alpl1 - alpt1)/vminz*qg
c      (TAKE ABS. VALUE IN CASE OF SLIGHTLY NEGATIVE b2m4ac)
      bz1 = -act1*half*(alpl1 + alpt1) + sqrt(abs(b2m4ac))
      end if
    end if
    az12 = zero
    cz1 = zero
    if (az11 .lt. eps) then
      ierr = 2
      write (*,900)
      return
    end if
c
c  else
c
c    SOLVE GAS PHASE MOMENTUM EQUATION
c
    az11 = dtz*arog + dfgdug + dfidug
    az12 = dfiduf
    cz1 = alpgdz
    bz1 = advg*rvolz*phiq + arog*dtz*ugt1
    + rhog*cosz*alpgdz*dzm
    - (fwg - dfgdug*ugt1) - fiterm - strat
  end if
c
c----- CALCULATE 2X2 SYSTEM LIQUID COEFFICIENTS -----
c
c  if (ibond.eq.2 .or. ibond.eq.4) then
c
c    USE SPECIFIED FLUID FLOW
c
    alpl1f = one - alpl1
    alpt1f = one - alpt1
    qm = act1*alpl1f*vminz
    qp = -act1*alpt1f*vminz
    if (qf .ge. qm) then
      az22 = act1*alpl1f
      bz2 = qf
    else if (qf .le. qp) then
      az22 = act1*alpt1f
      bz2 = qf
    else
      if (abs(alpl1f - alpt1f) .lt. eps) then
        az22 = act1*half*(alpl1f + alpt1f)
        bz2 = qf
      else
        az22 = (act1/vminz)*(alpl1f - alpt1f)
        b2m4ac = (act1*half*(alpl1f + alpt1f))**2
        + two*act1*(alpl1f - alpt1f)/vminz*qf
c      (TAKE ABS. VALUE IN CASE OF SLIGHTLY NEGATIVE b2m4ac)
        bz2 = -act1*half*(alpl1f + alpt1f) + sqrt(abs(b2m4ac))
      end if
    end if
    az21 = zero
    cz2 = zero
    if (az22 .lt. zero) then
      ierr = 2
      write(*,901)
      return
    end if
c
c  UPDATE PLENUM PRESSURE USING LIQUID MOMENTUM BALANCE

```

```

c      if (lppu.eq.1 .or. (lppu.eq.2 .and. (alpl1.lt.abs(alphs))))
c      then
c          a21 = -dfidug
c          a22 = dtz*arof + dffduf - dfiduf
c          c2 = alpfdz
c          b2 = advf*rvolz*phif + arof*dtz*uft1
c          + rhof*cosz*alpfdz*dzm
c          - (fwf - dffduf*uft1) + fiterm + strat
c          ptmp = pt1 + (a21*ugt1+a22*uft1-b2)/c2
c          iupp = 1
c          end if
c
c      else
c
c          SOLVE FLUID PHASE MOMENTUM EQUATION
c
c          az21 = -dfidug
c          az22 = dtz*arof + dffduf - dfiduf
c          cz2 = alpfdz
c          bz2 = advf*rvolz*phif + arof*dtz*uft1
c          + rhof*cosz*alpfdz*dzm
c          - (fwf - dffduf*uft1) + fiterm + strat
c          end if
c
c----- SOLVE FOR PRESSURE EQUATION COEFFICIENTS -----
c
c      det = (az11*az22 - az12*az21)
c      if (det .le. epsdet) then
c          ierr = 2
c          write(*,910)
c          return
c      end if
c      rdet = one/det
c      bgz = (az22*bz1 - az12*bz2)*rdet
c      bfz = (az11*bz2 - az21*bz1)*rdet
c      cgz = (az22*cz1 - az12*cz2)*rdet
c      cfz = (az11*cz2 - az21*cz1)*rdet
c
c----- FORMATS -----
c
c      900 format(/,' Area*alpha is nearly zero in explpl',/,
c          &      ' for prescribed gas flow')
c      901 format(/,' Area*(1-alpha) is nearly zero in explpl',/,
c          &      ' for prescribed fluid flow')
c      910 format(/,' 2x2 determinant is nearly zero in explpl')
c
c      return
c      end

```

EXPLTB

```

subroutine expltb(bgz,bfz,cgz,cfz,
c      acb1,aratb1,dhz,cosz,dzm,ugb1,ufb1,
c      absr,fmlt,form,fre,cizn,c0b,c0s,
c      acb2,                                ugb2,ufb2,
c      voltb,ptb,alptb,tgtb,tftb,xatb,rogtb,roftb,
c      azb1,volb1,pb1,alpb1,tgb1,tfb1,xab1,rogb1,rofb1,
c      alpb2,                                rogb2,rofb2,
c      rdelt,vminz,
c      ierr,ilq)
c
c      *****
c      *
c      * SUBROUTINE expltb
c      *
c      *****

```



```

C      *
C      * THIS ROUTINE COMPUTES THE NEW TIME STEP FLUID VELOCITIES
C      * AT THE TANK BOTTOM CELL FACE AS A LINEAR FUNCTION OF THE NEW
C      * TIME STEP PRESSURE DIFFERENCE ACROSS THE CELL FACE FOR THE
C      * BOTTOM BOUNDARY OF THE ASSEMBLY. THE COEFFICIENTS
C      * FORMING THESE LINEAR EXPRESSIONS ARE FUNCTIONS OF OLD TIME
C      * STEP QUANTITIES; THEREFORE, THIS CALCULATION IS ONLY DONE
C      * ONCE AT THE BEGINING OF EACH TIME STEP.
C      * THE EXPRESSIONS HAVE THE FOLLOWING FORM:
C      *
C      * FOR GAS PHASE:
C      *
C      *      n+1      n      n      n+1      n+1
C      *      u      = B      + C      *(P      - P      )
C      *      g,j+1/2  g,j+1/2  g,j+1/2  j      j+1
C      *
C      * FOR LIQUID PHASE:
C      *
C      *      n+1      n      n      n+1      n+1
C      *      u      = B      + C      *(P      - P      )
C      *      f,j+1/2  f,j+1/2  f,j+1/2  j      j+1
C      *
C      * WHERE:  B = bgz (Z-DIRECTION)
C      *          g
C      *          B = bfz (Z-DIRECTION)
C      *          f
C      *          C = cgz (Z-DIRECTION)
C      *          g
C      *          C = cfz (Z-DIRECTION)
C      *          f
C      *
C      * ARGUMENTS (O=Output, I=Input):
C      *
C      * O  bgz = SEE ABOVE; GAS PHASE CONSTANT TERM
C      * O  bfz = SEE ABOVE; LIQUID PHASE CONSTANT TERM
C      * O  cgz = SEE ABOVE; GAS PHASE PRESSURE COEFFICIENT
C      * O  cfz = SEE ABOVE; LIQUID PHASE PRESSURE COEFFICIENT
C      *
C      * BOTTOM SECTION FACE #nzb (TERMED 'b1' IN THIS SUBROUTINE):
C      * I  acb1 = AREA
C      * I  aratb1 = RATIO OF LOCAL FACE AREA TO AVERAGE CELL AREA
C      * I  dhz = HYDRAULIC DIAMETER
C      * I  cosz = cos*g
C      * I  dzm = MOMENTUM CELL LENGTH
C      * I  ugb1 = GAS VELOCITY
C      * I  ufb1 = LIQUID VELOCITY
C      * I  absr = ABSOLUTE ROUGHNESS
C      * I  fmlt = FRICTION MULTIPLIER
C      * I  form = FORM LOSS COEFFICIENT
C      * I  fre = HYDRAULIC DIAMETER CORRECTION FACTOR, Kh
C      * I  cizn = GENERALIZED INTERFACIAL DRAG COEFFICIENT
C      * I  cob = BUBBLE REGIME DISTRIBUTION COEFFICIENT
C      * I  cos = SLUG REGIME DISTRIBUTION COEFFICIENT
C      *
C      * BOTTOM SECTION FACE #nzb-1 (TERMED 'b2' IN THIS SUBROUTINE):
C      * I  acb2 = AREA
C      * I  ugb2 = GAS VELOCITY
C      * I  ufb2 = LIQUID VELOCITY
C      *
C      * TANK BOTTOM CELL:
C      * I  voltb = VOLUME
C      * I  ptb = PRESSURE
C      * I  alptb = VOID FRACTION
C      * I  tgtb = GAS TEMPERATURE
C      * I  tftb = LIQUID TEMPERATURE

```

```

c      * I  xatb = AIR MASS FRACTION
c      * I  rogtb = GAS DENSITY
c      * I  roftb = LIQUID DENSITY
c      *
c      * BOTTOM SECTION CELL #nzb (TERMED 'b2' IN THIS SUBROUTINE):
c      * I  azb1 = AREA
c      * I  volb1 = VOLUME
c      * I  pbl = PRESSURE
c      * I  alpb1 = VOID FRACTION
c      * I  tgb1 = GAS TEMPERATURE
c      * I  tfb1 = LIQUID TEMPERATURE
c      * I  xab1 = AIR MASS FRACTION
c      * I  rogb1 = GAS DENSITY
c      * I  rofb1 = LIQUID DENSITY
c      *
c      * BOTTOM SECTION CELL #nzb-1:
c      * I  alpb2 = VOID FRACTION
c      * I  rogb2 = GAS DENSITY
c      * I  rofb2 = LIQUID DENSITY
c      *
c      * OTHER:
c      * I  rdelt = RECIPROCAL dt
c      * I  vminz = MINIMUM VELOCITY FOR FULL DONORING
c      * I  ierr = ERROR FLAG
c      * I  ilq = LIQUID IDENTIFIER (.true.==>liquid, .false.==>gas)
c      *
c      *****
c      implicit real (a-h,o-z), integer (i-n)
c      logical liquid
c
c      parameter (zero=0.0, half=0.5, one=1.0, two=2.0, three=3.0,
c      & grav=9.80665)
c
c      data epsv/0.001/, eps1/0.001/, eps2/0.01/, epsdet/1.0e-20/,
c      & eps/0.00001/
c
c      COMPUTE VOLUME FRACTIONS FOR TOP(b1) AND BOTTOM(tb) CELLS
c
c      rvolz = two/(volb1 + voltb)
c      ft = volb1/(volb1 + voltb)
c      fb = one - ft
c
c      CALCULATE VOLUME AVERAGED PROPERTIES
c
c      pc = ft* pbl + fb* ptb
c      tgc = ft*tgb1 + fb*tgtb
c      tfc = ft*tfb1 + fb*tftb
c      xac = ft*xab1 + fb*xatb
c
c      alpg = ft*alpb1 + fb*alptb
c      rhog = ft*rogb1 + fb*rogtb
c      arog = ft*alpb1*rogb1 + fb*alptb*rogtb
c
c      alpf = one - alpg
c      rhof = ft*rofb1 + fb*roftb
c      arof = ft*(one - alpb1)*rofb1 + fb*(one - alptb)*roftb
c
c      CALCULATE ADVECTION TERMS
c
c      liquid = .false.
c      call avecb (advb,avgag,
c      & alpb2,rogb2, acb2,ugb2,
c      & alpb1,rogb1,azb1,acb1,ugb1,aratb1,
c      & alptb,rogtb,

```

```

      &          vminz,liquid)
C
      liquid = .true.
      call avecb (advf,avgaf,
      &          alpb2,rofb2,      acb2,ufb2,
      &          alpb1,rofb1,azb1,acb1,ufb1,aratb1,
      &          alptb,roftb,
      &          vminz,liquid)
C
C      EVALUATE ADVECTION TERM CUT-OFF FUNCTIONS
C
      phig = min(one, max(zero, (alpg-eps1)/(eps2-eps1)))
      phif = min(one, max(zero, (alpf-eps1)/(eps2-eps1)))
C
C      COMPUTE C0, Cg, & ANNULAR FRACTION ann
C
      call c0fcn(alpg,c0b,c0s,c0,cg,ann)
C
C      COMPUTE GAS AND LIQUID WALL DRAG AND DERIVATIVES
C
      theta = phif
      alpgdz = avgag*rvolz
      alpfdz = avgaf*rvolz
C
      call fwallz (fwg,fwf,dfgdug,dffdug,
      &          dhz,theta,fmlt,form,absr,fre,ugb1,ufb1,
      &          alpgdz,alpfdz,pc,tgc,tfc,xac,rhog,rhof,ilq)
C
C      ADD FALLING FILM CORRECTION TERM TO LIQUID WALL DRAG
C      IF LIQUID FLOW IS DOWNWARD (NOT USED CURRENTLY!)
C
      cosg = cosz*max(zero, sign(one, cosz*ufb1))
      fwf = fwf + theta*ann*alpf*(rhof-rhog)*cosg
      &          *(one - two*alpf/(three*fre))
C
C      COMPUTE INTERFACIAL DRAG AND DERIVATIVES
C
      urel = cg*ugb1 - c0*ufb1
      fidz = cizn*(abs(urel) + epsv)*urel
      dfddug = cizn*cg*(two*abs(urel) + epsv)
      dfdduf = -cizn*c0*(two*abs(urel) + epsv)
C
      alpmin = min(alpb1, alptb)
      phiw = min(one, max(zero, (alpmin-eps1)/(eps2-eps1)))
      coef = (one - ann)*alpg*phiw
      fiwz = coef*(fwg + fwf)
      dfwdug = coef*dfgdug
      dfwduf = coef*dffdug
C
      fi = fidz + fiwz
      dfidug = dfddug + dfwdug
      dfiduf = dfdduf + dfwduf
C
C      CALCULATE 2X2 SYSTEM GAS MOMENTUM COEFFICIENTS
C
      dtz = rdelt*aratb1
      fiterm = fi - dfidug*ugb1 - dfiduf*ufb1
C
      azl1 = dtz*arog + dfgdug + dfidug
      azl2 = dfiduf
      czl = alpgdz
      bz1 = advg*rvolz*phig + arog*dtz*ugb1
      &          + rhog*cosz*alpgdz*dzm
      &          - (fwg - dfgdug*ugb1) - fiterm

```

```

C
C      CALCULATE 2X2 SYSTEM LIQUID MOMENTUM COEFFICIENTS
C

```

```

      az21 = -dfidug
      az22 = dtz*arof + dffduf - dfiduf
      cz2 = alpfdz
      bz2 = advf*rvolz*phif + arof*dtz*ufb1
      + rhof*cosz*alpfdz*dzm
      - (fwf - dffduf*ufb1) + fiterm

```

```

C
C      SOLVE FOR PRESSURE EQUATION COEFFICIENTS
C

```

```

      det = (az11*az22 - az12*az21)
      if (det .le. epsdet) then
        ierr = 2
        write(*,910)
        return
      end if
      rdet = one/det
      bgz = (az22*bz1 - az12*bz2)*rdet
      bfz = (az11*bz2 - az21*bz1)*rdet
      cgz = (az22*cz1 - az12*cz2)*rdet
      cfz = (az11*cz2 - az21*cz1)*rdet

```

```

C
C      FORMATS
C

```

```

900  format(/,' Area*alpha is nearly zero in expltb',/,
      &      ' for prescribed gas flow')
901  format(/,' Area*(1-alpha) is nearly zero in expltb',/,
      &      ' for prescribed fluid flow')
910  format(/,' 2x2 determinant is nearly zero in expltb')
C
      return
      end

```

FILMB

```

      subroutine filmb (qf,dqfdt,qg,dqgdt,vapor,wet,qchf,tchf,twalk,
      &                  tliq,tgas,tsat,pres,alfa,beta,xa,uliq,ugas,
      &                  rhof,rhog,condg,cpg,visg,dhy,hfg,hlsat,hgsat,
      &                  sigma,dofilm,ilq)

```

```

C
C      *****
C      *
C      *      SUBROUTINE filmb
C      *
C      *      SUBROUTINE TO CALCULATE FILM BOILING AND TRANSITION BOILING
C      *      HEAT FLUXES USING BROMLEY-POMERANZ CORRELATION FOR LIQUID,
C      *      FORSLUND-ROHSENOW DROP IMPINGEMENT CORRELATION FOR LIQUID,
C      *      AND DOUGALL-ROHSENOW CORRELATION FOR GAS
C      *
C      *      OUTPUT ARGUMENTS:
C      *      qf - SURFACE HEAT FLUX TO LIQUID, W/m**2
C      *      dqfdt - DERIVATIVE OF LIQUID HEAT FLUX WITH RESPECT TO
C      *              WALL TEMPERATURE
C      *      qg - SURFACE HEAT FLUX TO GAS, W/m**2
C      *      dqgdt - DERIVATIVE OF GAS HEAT FLUX WITH RESPECT TO
C      *              WALL TEMPERATURE
C      *      vapor - VAPOR GENERATION RATE, kg/m**2-s
C      *      wet - FRACTION OF SURFACE AREA THAT IS WETTED
C      *
C      *      INPUT ARGUMENTS:
C      *      twalk - WALL TEMPERATURE, K
C      *      tsat - SATURATION TEMPERATURE, K
C      *      rhof - LIQUID DENSITY, kg/m**3
C      *
C      *****

```

```

c      *      rhog - GAS DENSITY, kg/m**3      *
c      *      condg - GAS THERMAL CONDUCTIVITY, W/m-C      *
c      *      cpg - GAS HEAT CAPACITY, J/kg-C      *
c      *      visg - GAS VISCOSITY, kg/m-s      *
c      *      dhy - CELL HYDRAULIC DIAMETER, m      *
c      *      hfg - LATENT HEAT OF VAPORIZATION, J/kg      *
c      *      sigma - SURFACE TENSION, N/m      *
c      *      dofilm - LOGICAL FLAG TO INDICATE CALCULATION OF TERMS      *
c      *      IN CORRELATION THAT ARE CONSTANT FOR FLUID CELL      *
c      *      *
c      *****
c      implicit real (a-h,o-z), integer (i-n)
c      logical dofilm
c
c      parameter (zero=0.0, half=0.5, one=1.0, two=2.0,
c      &          three=3.0, four=4.0, six=6.0)
c      parameter (boltz=5.669e-8, g=9.8066)
c
c      MINIMUM STABLE FILM BOILING TEMPERATURE PARAMETERS
c
c      parameter (cgs1=5.578e+02, cgs2=4.410e-05,
c      &          cgs3=3.720e-12, cgs4=1.000e+04,
c      &          cgs5=2.820e+00, cgs6=1.220e-06)
c
c      CORRELATION PARAMETERS
c
c      parameter (pt35=0.350, pt75=0.750,
c      &          pt67=0.6667, r2pi=0.5/3.14159)
c      parameter (cbrm=0.620, cfor=0.2552, xt1=0.172)
c
c      dimension ws(2)
c
c      save part1, part2, part3, hfgp, hfgr, dropd, tmsfb
c
c      data wa/28.97/, ws(1)/18.016/, ws(2)/20.034/
c      data dmin /1.0e-4/, dmax /3.0e-3/, epsv /0.01/
c      data aldis /0.75/, alinv /0.5/
c
c      CALCULATE CONSTANT VALUES FOR FLUID CELL
c
c      if (dofilm) then
c          gdelr = g*(rho1 - rhog)
c          hfgp = hfg + half*cpg*(twalk - tsat)
c          hfgr = hfg/((one + pt35*cpg*(twalk - tsat)/hfg)**three)
c          dfact = pt75*(one + cpg*(twalk - tsat)/(six*hfgp))
c          rlamb = r2pi*dhy*sqrt(gdelr/sigma)
c          part1 = cbrm*(rlamb**xt1)
c          part2 = (condg**3)*rhog*gdelr/visg
c          part3 = (condg**3)*rhog*g*rho1/visg
c
c      SET LIQUID DROP DIAMETER
c
c          vrel = abs(ugas - ullq) + epsv
c          dropd = four*sigma/(rhog*vrel*vrel)
c          dropd = min(dropd,dmax)
c          dropd = max(dropd,dmin)
c
c      DETERMINE MINIMUM STABLE FILM BOILING TEMPERATURE, tmsfb
c      USING GROENEVELD-STEWART CORRELATION
c
c          xstm = one - xa
c          pair = pres*xa/(xa + xstm*wa/ws(1lq))
c
c      EVALUATE AIR, STEAM, AND LIQUID ENTHALPIES (hair, hstm, hfld)

```

```

c      call air (pair,tgas,roa,dx,dx,hair,dx,dx)
c      call hsteam (tgas,tsat,dx,hgsat,dx,liq,hstm,dx,dx)
c      call hfluid (pres,tliq,hlsat,dx,hfld,dx,dx)

c
c      COMPUTE QUALITY AND tmsfb
c
c      hgas = xa*hair + xstm*hstm
c      alrg = alfa*rhog
c      alrl = beta*rhol
c      hmix = (alrg*hgas + alrl*hfld)/(alrg + alrl)
c      xe = (hmix - hlsat)/hfg
c      xe = min(xe,zero)

c
c      tmsfb = cgs1 + (cgs2 - cgs3*pres)*pres -
c      cgs4*xe/(cgs5 + cgs6*pres)

c
c      dofilm = .false.
c      end if

c
c      FOR TRANSITION BOILING REGIME, USE tmsfb IN CORRELATIONS
c
c      tfilm = max(twalk,tmsfb)
c      delt = tfilm - tsat

c
c      INTERPOLATE CORRELATIONS BASED ON VOID FRACTION
c      BETWEEN DISPERSED PHASE AND INVERTED ANNULAR REGIMES
c
c      x1 = (alfa - alinv)/(aldis - alinv)
c      x1 = min(x1,one)
c      x1 = max(x1,zero)
c      x2 = one - x1

c
c      if (x2.gt.zero) then
c
c      CALCULATE MODIFIED BROMLEY FILM HEAT TRANSFER
c      COEFFICIENT, HEAT FLUX, AND DERIVATIVE
c
c      hbrm = x2*part1*sqrt(sqrt(part2*hfqp/(dhy*delt)))
c      qbrm = hbrm*delt
c      dqbrm = dfact*hbrm
c      else
c      qbrm = zero
c      dqbrm = zero
c      end if

c
c      if (x1.gt.zero) then
c
c      CALCULATE FORSLUND-ROHSENOW DROP IMPINGEMENT HEAT
c      TRANSFER COEFFICIENT, HEAT FLUX, AND DERIVATIVE
c
c      hfor = x1*cfor*(beta**pt67)*sqrt(sqrt(part3*hfgr
c      / (dropd*delt)))
c      qfor = hfor*delt
c      dqfor = dfact*hfor
c      else
c      qfor = zero
c      dqfor = zero
c      end if

c
c      DOUGALL-ROHSENOW CORRELATION FOR GAS
c
c      gmix = rhog*(alfa*abs(ugas) + beta*abs(uliq))
c      call hconv (qgas,dqgas,hjunk,tfilm,tgas,gmix,dhy,

```

```

      visg,condg,cpg,visg,zero,1)
C
C   INCLUDE RADIATION HEAT TRANSFER TO LIQUID AND GAS
C
      tfilm3 = tfilm**3
      tsat3 = tsat**3
      tgas3 = tgas**3
C
      qradg = boltz*(tfilm*tfilm3 - tgas*tgas3)
      qradl = boltz*(tfilm*tfilm3 - tsat*tsat3)
      dgrad = four*boltz*tfilm3
C
C   CALCULATE TOTAL HEAT FLUXES AND DERIVATIVES
C   WEIGHTED BY THE RESPECTIVE VOLUME FRACTIONS
C
      qliq = beta*( qbrm + qfor + qradl)
      dqliq = beta*(dqbrm + dqfor + dgrad)
C
      qgas = alfa*( qgas + qradg)
      dqgas = alfa*(dqgas + dgrad)
C
      if (twalk.lt.tmsfb) then
C
C   TRANSITION BOILING REGIME: INTERPOLATE BETWEEN qchf AND qfilm
C
        zeta = (twalk - tchf)/(tmsfb - tchf)
        dwdt = six*zeta*(zeta - one)/(tmsfb - tchf)
        wet = one + (two*zeta - three)*zeta*zeta
        dry = one - wet
C
        qf = dry*qliq + wet*qchf
        qg = dry*qgas
        dqfdt = (qchf - qliq)*dwdt
        dqgdt = -qgas*dwdt
      else
C
C   FILM BOILING REGIME: USE FILM HEAT FLUX RESULTS
C
        wet = zero
        qf = qliq
        qg = qgas
        dqfdt = dqliq
        dqgdt = dqgas
      end if
      vapor = qf/hfgp
C
      return
      end

```

FWALLX

```

      subroutine fwallx(fwg,fwf,dfgdwg,dffdwf,
      &                  dh,theta,fmlt,kmlt,absr,fre,wg,wf,
      &                  alpgdx,alpfdx,p,tg,tf,xa,rhog,rhof,ilq)
C
C   *****
C   *
C   *   SJBROUTINE fwallx
C   *
C   *   This routine computes the azimuthal gas and liquid wall drag
C   *
C   *   ARGUMENTS (O=Output, I=Input):
C   *
C   *   O fwg   - gas azimuthal wall drag / volume, Fwg (N/m^3)
C   *   O fwf   - liquid azimuthal wall drag / volume, Fwf (N/m^3)
C   *
C   *****

```

```

c      * O dfgdwg - derivative of fwg with respect to wg      *
c      * O dffdwf - derivative of fwf with respect to wf      *
c      *
c      * I dh      - hydraulic diameter, Dh (m)                *
c      * I ttheta - fraction of liquid in contact with wall    *
c      * I fmlt    - friction multiplier                        *
c      * I kmlt    - form loss multiplier                       *
c      * I absr    - absolute roughness (m)                     *
c      * I fre     - hydraulic diameter correction factor       *
c      * I wg      - gas velocity (m/s)                         *
c      * I wf      - liquid velocity (m/s)                      *
c      * I alpgdx  - <alpg*A>/Vx (m^-1)                         *
c      * I alpfdx  - <alpf*A>/Vx (m^-1)                         *
c      * I p       - pressure, P (Pa)                           *
c      * I tg      - gas temperature, Tg (K)                    *
c      * I tf      - liquid temperature, Tf (K)                 *
c      * I xa      - air mass fraction, Xa                       *
c      * I rhog    - gas density (kg/m^3)                       *
c      * I rhof    - liquid density (kg/m^3)                    *
c      * I ilq     - liquid identifier (1=H2O, 2=D2O)           *
c      *
c      *****
c      implicit real (a-h,o-z), integer (i-n)
c      real kmlt, k
c      parameter (zero=0.0, half=0.5, one=1.0, two=2.0, fifty=50.0,
6      sixty4=64.0, rel=2000.0, ret=4000.0, fl=0.032)
c      parameter (c1=1.14, c2=21.25, c3=0.9)
c      parameter (c4=1.56522, c5=200.0)
c
c      EXPLICIT APPROXIMATION TO COLEBROOK-WHITE EQUATION
c
c      fric(relr, re) = one/(c1 - two*log10(relr + c2/re**c3))**2
c
c      EVALUATE LIQUID AND VAPOR DYNAMIC VISCOSITIES
c
c      call visgs(p,tg,xa,ilq,visg)
c      call vislq(tf,ilq,visf,dvdt)
c
c      COMPUTE THE REYNOLDS NUMBERS
c
c      de = fre*dh
c
c      reg = max(fifty, rhog*abs(wg)*de/visg)
c      ref = max(fifty, rhof*abs(wf)*de/visf)
c
c      COMPUTE THE FRICTION FACTORS
c
c      if (fmlt .ne. zero) then
c
c          relr= absr/de
c
c          if (reg .lt. rel) then
c              fricg = sixty4/reg
c          else if (reg .le. ret) then
c              fricg = (two - ret/reg)*(fric(relr,ret) - fl) + fl
c          else
c              fricg = fric(relr, reg)
c          end if
c
c          if (ref .lt. rel) then
c              fricf = sixty4/ref
c          else if (ref .le. ret) then
c              fricf = (two - ret/ref)*(fric(relr, ret) - fl) + fl
c          else

```



```

      #ricf = fric(relr, ref)
    end if

c
c  end if
c
c  COMPUTE NOMINAL FORM LOSS COEFFICIENT
c
c  k = c4 + c5/ref
c
c  COMPUTE WALL FRICTION & DERIVATIVE FOR EACH PHASE
c
c  dfgdwg = ((one-theta)*fmlt*fricg/dh + kmlt*alpgdx*k)*rhog*abs(wg)
c  dffdwf = (      theta*fmlt*fricf/dh + kmlt*alpdfx*k)*rhof*abs(wf)
c
c  fwg = dfgdwg*half*wg
c  fwf = dffdwf*half*wf
c
c  return
c  end

```

FWALLZ

```

      subroutine fwallz(fwg, fwf, dfgdug, dffduf,
&                      dh, theta, fmlt, form, absr, fre, ug, uf,
&                      alpgdz, alpdfz, p, tg, tf, xa, rhog, rhof, ilq)
c
c  *****
c  *
c  *  SUBROUTINE fwallz
c  *
c  *  This routine computes the axial gas and liquid wall drag
c  *  EXCLUDING the laminar falling film correction component of
c  *  the liquid wall frictional wall drag. Consult TF-28 for more
c  *  information.
c  *
c  *  ARGUMENTS (O=Output, I=Input):
c  *
c  *  O fwg   - gas axial wall drag per unit volume, Fwg (N/m^3)
c  *  O fwf   - liquid axial wall drag per unit vol., Fwf (N/m^3)
c  *  O dfgdug - derivative of fwg with respect to ug
c  *  O dffduf - derivative of fwf with respect to uf
c  *
c  *  I dh    - hydraulic diameter, Dh (m)
c  *  I theta - fraction of liquid in contact with wall
c  *  I fmlt  - friction multiplier
c  *  I form  - form loss coefficient
c  *  I absr  - absolute roughness (m)
c  *  I fre   - hydraulic diameter correction factor, Kh
c  *  I ug    - gas velocity (m/s)
c  *  I uf    - liquid velocity (m/s)
c  *  I alpgdz - <alpg*A>/Vz (m^-1)
c  *  I alpdfz - <alpf*A>/Vz (m^-1)
c  *  I p     - pressure, P (Pa)
c  *  I tg    - gas temperature, Tg (K)
c  *  I tf    - liquid temperature, Tf (K)
c  *  I xa    - air mass fraction, Xa
c  *  I rhog  - gas density (kg/m^3)
c  *  I rhof  - liquid density (kg/m^3)
c  *  I ilq   - liquid identifier (1=H2O, 2=D2O)
c  *
c  *  COMMON VARIABLES
c  *
c  *  I xfric - multiplier to friction factors for sensitivity
c  *           studies
c  *
c  *****

```

```

c *****
c implicit real (a-h,o-z), integer (i-n)
c parameter (zero=0.0, half=0.5, one=1.0, two=2.0, fifty=50.0,
c & sixty4=64.0, rel=2000.0, ret=4000.0, fl=0.032)
c parameter (c1=1.14, c2=21.25, c3=0.9)
c
c include 'knobs.inc'
c
c EXPLICIT APPROXIMATION TO COLEBROOK-WHITE EQUATION
c
c fric(re1r, re) = one/(c1 - two*log10(re1r + c2/re**c3))**2
c
c if (fmlt .ne. zero) then
c
c     EVALUATE LIQUID AND VAPOR DYNAMIC VISCOSITIES
c
c     call visgs(p,tg,xa,ilq,visg)
c     call vislq(tf,ilq,visf,dvdt)
c
c     O.C. JONES LAMINAR FLOW FRICTION CORRECTION
c
c     de = fre*dh
c     relr= absr/de
c
c     COMPUTE THE REYNOLDS NUMBERS
c
c     reg = max(fifty, rhog*abs(ug)*de/visg)
c     ref = max(fifty, rhof*abs(uf)*de/visf)
c
c     COMPUTE THE FRICTION FACTORS
c
c     if (reg .lt. rel) then
c         fricg = sixty4/reg
c     else if (reg .le. ret) then
c         fricg = (two - ret/reg)*(fric(re1r,ret) - fl) + fl
c     else
c         fricg = fric(re1r, reg)
c     end if
c
c     if (ref .lt. rel) then
c         fricf = sixty4/ref
c     else if (ref .le. ret) then
c         fricf = (two - ret/ref)*(fric(re1r, ret) - fl) + fl
c     else
c         fricf = fric(re1r, ref)
c     end if
c
c end if
c
c COMPUTE WALL FRICTION & DERIVATIVE FOR EACH PHASE
c (DOES NOT INCLUDE LAMINAR FALLING FILM CORRECTION)
c
c dfgdug = ((one-theta)*fmlt*fricg/dh*xfric + alpgdz*form)
c & rhog*abs(ug)
c dffduf = ( theta *fmlt*fricf/dh*xfric + alpfdz*form)
c & rhof*abs(uf)
c
c fwg = dfgdug*half*ug
c fwf = dffduf*half*uf
c
c return
c end

```

GAJOR5

```

subroutine gajor5 (ncol,ca)
c
c *****
c *
c * Performs gauss-jordan inversion of a 5x5 (cm) matrix to
c * eliminate alp, tg, tf, and xa for a pressure only problem.
c *
c * The following is a limited gauss-jordan technique for a
c * 5x5 matrix with an arbitrary number of pressure coupling
c * coefficients.
c *
c *
c *
c * | a a a a a | c | b . . . |      | 1 0 0 0 0 | e | d . . . |
c * | a a a a a | c | b . . . |      | 0 1 0 0 0 | e | d . . . |
c * | a a a a a | c | b . . . |      | 0 0 1 0 0 | e | d . . . |
c * | a a a a a | c | b . . . |      | 0 0 0 1 0 | e | d . . . |
c * | a a a a a | c | b . . . |      | 0 0 0 0 1 | e | d . . . |
c * | _ _ _ _ _ | _ _ _ _ _ |      | _ _ _ _ _ | _ _ _ _ _ |
c *
c * final result (after gauss-jordan inversion) is of the form:
c *
c * | 1 0 0 0 0 | | dp | | d . . . | | dp | | e | l=1
c * | 0 1 0 0 0 | | dalp | | d . . . | | . | | e | l=2
c * | 0 0 1 0 0 | | dtg | + | d . . . | | . | = | e | l=3
c * | 0 0 0 1 0 | | dtf | | d . . . | | . | | e | l=4
c * | 0 0 0 0 1 | | dxa | | d . . . | | dp | | e | l=5
c * | _ _ _ _ _ | | _ _ _ _ _ | | _ _ _ _ _ | | _ _ _ _ _ |
c *
c *
c * cm(5x5)      cell      cp(5xn)      neighbors      f(5x1)
c * matrix      variables  matrix              rhs vector
c *
c *          [ca] = [cm] + [f] + [cp]
c *        (5xncol) (5x5)  (5x1)  (5xncp)
c *
c * Note that: the elements contained within the upper
c * tri-angular portion of [cm] are not operated
c * upon. Only those element members employed in
c * later computations (i.e. [cp] and [f]) are
c * altered.
c *
c *****
c
cvax implicit double precision (a-h,o-z), integer (i-n)
parameter (one=1.0)
dimension ca(5,ncol)
c
c *****
c *
c *
c * | 1 0 a a a | e | d . . . |
c * | 0 1 a a a | e | d . . . |
c * | a a a a a | c | b . . . |
c *
c * step one
c *

```

```

c      *          | a a a a | c | b . . . |          *
c      *          |         |   |         |          *
c      *          | a a a a | c | b . . . |          *
c      *          | _       |   |         |          *
c      *          |         |   |         |          *
c      *****
c
c      rd = one/(ca(1,1)*ca(2,2) - ca(1,2)*ca(2,1))
c      do 10 k=3,ncol
c          temp    = ca(2,2)*ca(1,k) - ca(1,2)*ca(2,k)
c          ca(2,k) = rd*(ca(1,1)*ca(2,k) - ca(2,1)*ca(1,k))
c          ca(1,k) = rd*temp
10     continue
c
c      *****
c      *
c      *          | 1 0 a a a | e | d . . . |          *
c      *          |         |   |         |          *
c      *          | 0 1 a a a | e | d . . . |          *
c      *          |         |   |         |          *
c      *          | 0 0 a a a | e | d . . . |          *
c      * step two   |         |   |         |          *
c      *          |         |   |         |          *
c      *          | 0 0 a a a | e | d . . . |          *
c      *          |         |   |         |          *
c      *          | 0 0 a a a | e | d . . . |          *
c      *          | _       |   |         |          *
c      *          |         |   |         |          *
c      *****
c
c      do 20 k=3,ncol
c          ca(3,k) = ca(3,k) - ca(3,1)*ca(1,k) - ca(3,2)*ca(2,k)
c          ca(4,k) = ca(4,k) - ca(4,1)*ca(1,k) - ca(4,2)*ca(2,k)
c          ca(5,k) = ca(5,k) - ca(5,1)*ca(1,k) - ca(5,2)*ca(2,k)
20     continue
c
c      *****
c      *
c      *          | 1 0 a a a | e | d . . . |          *
c      *          |         |   |         |          *
c      *          | 0 1 a a a | e | d . . . |          *
c      *          |         |   |         |          *
c      *          | 0 0 1 0 a | e | d . . . |          *
c      * step three |         |   |         |          *
c      *          |         |   |         |          *
c      *          | 0 0 0 1 a | e | d . . . |          *
c      *          |         |   |         |          *
c      *          | 0 0 a a a | e | d . . . |          *
c      *          | _       |   |         |          *
c      *          |         |   |         |          *
c      *****
c
c      rd = one/(ca(3,3)*ca(4,4) - ca(4,3)*ca(3,4))
c      do 30 k=5,ncol
c          temp    = ca(4,4)*ca(3,k) - ca(3,4)*ca(4,k)
c          ca(4,k) = rd*(ca(3,3)*ca(4,k) - ca(4,3)*ca(3,k))
c          ca(3,k) = rd*temp
30     continue
c
c      *****
c      *
c      *          | 1 0 0 0 a | e | d . . . |          *
c      *          |         |   |         |          *
c      *          | 0 1 0 0 a | e | d . . . |          *
c      *          |         |   |         |          *
c      *          | 0 0 1 0 a | e | d . . . |          *
c      * step four  |         |   |         |          *

```



```

c      *   xa      = Current iterate (m level) air mass fraction      *
c      *   xa0     = Source/sink air mass fraction                    *
c      *
c      *   OUTPUT:
c      *   ga      = Source/sink rate of air mass, kg/s-m^3 fraction *
c      *   dgadxa  = Derivative of ga with respect to air mass fraction, *
c      *               kg/s-m^3-mass fraction                          *
c      *   dgada   = Derivative of ga with respect to void fraction,   *
c      *               kg/s-m^3                                         *
c      *
c      *
c      *****
c
c      implicit real (a-h,o-z), integer (i-n)
c      parameter (zero=0.0, one=1.0)
c      data epsga/1.0e+0/, epsal/0.001/
c
c      call chp(alpha,zero,epsal,chpa,dchpda)
c
c      ga      = (one - chpa)*epsga*(xa0 - xa)
c      dgada   = -dchpda*epsga*(xa0 - xa)
c      dgadxa  = -(one - chpa)*epsga
c
c      call air(p,tg,roa,droadp,droadt,ha,dhadp,dhadtg)
c      ea = ga*ha
c      deadp  = ga*dhadp
c      deada  = dgada*ha
c      deadtg = ga*dhadtg
c      deadxa = dgadxa*ha
c
c      return
c      end

```

GAMMAI

```

      subroutine gammai (gami,dgidp,dgida,dgidt,dgldtf,dgidxa,
c      *
c      *
c      *   SUBROUTINE gammai
c      *
c      *   COMPUTES INTERFACIAL MASS TRANSFER RATE gami AND INTERFACIAL
c      *   ENERGY TRANSFER RATE ei TO THE GAS PHASE (PER UNIT VOLUME)
c      *
c      *   ARGUMENTS (O=Output, I=Input):
c      *
c      *   O   gami = MASS TRANSFER RATE PER UNIT VOLUME TO GAS PHASE
c      *   O   dgidp = DERIVATIVE OF gami W.R.T. TOTAL PRESSURE, p
c      *   O   dgida = DERIVATIVE OF gami W.R.T. VOID FRACTION, alpg
c      *   O   dgldtg = DERIVATIVE OF gami W.R.T. GAS TEMPERATURE, tg
c      *   O   dgldtf = DERIVATIVE OF gami W.R.T. LIQUID TEMPERATURE, tf
c      *   O   dgldxa = DERIVATIVE OF gami W.R.T. AIR MASS FRACTION, xa
c      *
c      *   O   ei = ENERGY TRANSFER RATE PER UNIT VOLUME TO GAS PHASE
c      *   O   deidp = DERIVATIVE OF ei W.R.T. TOTAL PRESSURE, p
c      *   O   deida = DERIVATIVE OF ei W.R.T. VOID FRACTION, alpg
c      *   O   deidtg = DERIVATIVE OF ei W.R.T. GAS TEMPERATURE, tg
c      *   O   deidtf = DERIVATIVE OF ei W.R.T. LIQUID TEMPERATURE, tf
c      *   O   deidxa = DERIVATIVE OF ei W.R.T. AIR MASS FRACTION, xa
c      *
c      *   O   ysi = STEAM MOLE FRACTION AT THE GAS-LIQUID INTERFACE
c      *
c

```

```

c      * I      p = TOTAL PRESSURE                      *
c      * I      alpg = VOID FRACTION                    *
c      * I      tg = GAS TEMPERATURE                    *
c      * I      tf = LIQUID TEMPERATURE                 *
c      * I      xa = AIR MASS FRACTION                  *
c      *
c      * I      kgic = Kg /alpg(1-alpg)                  *
c      * I      hgic = Hgi/alpg(1-alpg)                  *
c      * I      hfic = Hfi/alpg(1-alpg)                  *
c      *
c      * O      it = NUMBER OF NEWTON ITERATIONS FOR ysi *
c      * O      ierr = ERROR FLAG (0=OK, 1=ERROR)        *
c      *
c      * I      igami = INTERFACIAL MODEL SELECTOR (0=SIMPLE; 1=PHYSICAL) *
c      * I      ilq = LIQUID SELECTOR (1=H2O; 2=D2O)      *
c      *
c      *****
c
c      implicit real (a-h,o-z), integer (i-n)
c      real kgic, kgi, kgis, kgi0, kgi1
c      logical redo
c      parameter (zero=0.0, pt1=0.1, half=0.5, one=1.0, two=2.0)
c      dimension watmw(2)
c
c      include 'knobs.inc'
c
c      data airmw/28.97/, watmw(1)/18.016/, watmw(2)/20.034/
c      data epsal/0.001/, epst/0.001/
c      data small/1.0e-6/, dymax/0.04/
c      data ysimin/0.0/, ysimax/1.0/
c      data hcoef/1.0e+5/, setphi/0.625/
c
c----- SIMPLE INTERFACIAL MODEL PRIMARILY FOR V&V PURPOSES -----
c      (NO MASS TRANSFER & A HIGH OVERALL HEAT TRANSFER COEFFICIENT)
c
c      if (igami .eq. 0) then
c
c          gami = zero
c          dgidp = zero
c          dgida = zero
c          dgidtg = zero
c          dgidtf = zero
c          dgidxa = zero
c
c          ei = hcoef*(tf - tg)
c          deidp = zero
c          deida = zero
c          deidtg = -hcoef
c          deidtf = hcoef
c          deidxa = zero
c
c----- PHYSICALLY BASED I.H.M.T. MODEL -----
c
c      else
c
c      SET CONSTANT VALUES IN PREPARATION FOR NEWTON ITERATION FOR
c      INTERFACIAL COMPOSITION (ysi)
c
c      phi = xphi*setphi
c      omphi = one - phi
c
c      xs = one - xa
c      ys = (xs/watmw(ilq))/(xs/watmw(ilq) + xa/airmw)
c      call cpgs(tg, zero, ilq, cps)

```

```
      call cplq(tf,      ilq,cpw)
      pcps = phi*cps
      pcpw = phi*cpw
c
      alpf = one - alpg
      call chp(alpg,zero,epsal,phiag,dpagda)
      call chp(alpf,zero,epsal,phiaf,dpafda)
      alpgf = alpg*alpf
      epsgf = epsal*(one - epsal)
c
      kgis = alpgf*kgic
      kgi0 = epsgf*kgic
      kgi1 = kgi0
      kgi = phiag*phiaf*kgis + (one - phiag)*kgi0 + (one - phiaf)*kgi1
c
      hgis = alpgf*hgic
      hgi0 = epsgf*hgic
      hgi1 = hgi0
c
      hfis = alpgf*hfic
      hfi0 = epsgf*hfic
      hfi1 = hfi0
c
c      INITIALIZE
c
      ierr = 0
      redo = .true.
      if (ys .eq. zero) then
         ysi = pt1
      else
         ysi = ys
      end if
c
c      PERFORM NEWTON ITERATION TO FIND INTERFACIAL COMPOSITION (ysi)
c      AND TEMPERATURE(ti)
c
10    continue
      do 20 it=1, nitysi
         ysim = ysi
c
         psi = ysi*p
         call tsat(psi,ilq,ti,dtidps)
c
         call tsat (p,ilq,tsp,dtspdp)
         call hssat (p,ilq,hsp,dhspdp)
         call hsteam(ti,tsp,dtspdp,hsp,dhspdp,ilq,hsi,dhsidp,dhsidt)
c
         call hfsat (ti,ilq,hwi,dhwidt)
c
         deltg = ti - tg
         deltf = ti - tf
         delys = ysi - ys
c
         dtitg = deltg
         call chp(dtitg,zero,epst,phitg,dptgdt)
         hgi = phiag*(one - phitg*(one - phiaf))*hgis
           + phitg*(one - phiaf) *hgi1
           + (one - phiag) *hgi0
         dhgdti = -dptgdt*(one - phiaf)*(phiag*hgis - hgi1)
c
         dtfti = -deltf
         call chp(dtfti,zero,epst,phitf,dptfdt)
         hfi = phiaf*(one - phitf*(one - phiag))*hfis
           + phitf*(one - phiag) *hfi0
```



```

      + (one - phiaf) * hfi1
dhfdti = +dptfdt*(one - phiag)*(phiaf*hfis - hfi0)
c
rdnom = one/(hsi - hwi + pcpw*deltf - pcps*deltg)
gami  = -rdnom*(hgi*deltg + hfi*deltf)
fg    = hgi + dhgdti*deltg - gami*pcps
ff    = hfi + dhfdti*deltf + gami*pcpw
dgidti = -rdnom*(gami*(dhsidt - dhwidt) + fg + ff)
c
fy    = one - ysi + phi*delys
fysi  = gami*fy - kgi*delys
dfdysi = fy*dgidti*dtidps*p - omphi*gami - kgi
dysi  = fysi/dfdysi
c
tol = max(epsy*ysi, small)
if (abs(dysi).lt.tol .and. abs(fysi).lt.epsf) then
c
  BAIL OUT W/O UPDATE SO THAT ABOVE QUANTITIES ARE
c
  STILL VALID (ELIMINATE NEED FOR REDUNDANT CODING BELOW)
  go to 100
else
  ysi = ysi - sign(min(abs(dysi),dymax),dysi)
end if
c
  if (ysi .lt. zero) ysi = ysimin
  if (ysi .gt. one ) ysi = ysimax
  if (ysi .eq. ysim) go to 30
20 continue
c
  ADJUST INITIAL GUESS AND TRY AGAIN IF ysi IS AT AN EXTREME
  VALUE, IF ysi IS AT AN INTERMEDIATE VALUE AND THE ITERATION
  FAILED TO CONVERGE, TRY AN AVERAGE OF THE LAST TWO VALUES AS
  AN INITIAL GUESS IN CASE A LIMIT CYCLE HAS BEEN REACHED
c
30 continue
  if (redo) then
    if (ysi .eq. ysimin) then
      ysi = ysimax
    else if (ysi .eq. ysimax) then
      ysi = ysimin
    else
      ysi = half*(ysim + ysi)
    end if
    redo = .false.
    go to 10
  end if
c
  ERROR BRANCH: NEWTON ITERATION FAILED TO CONVERGE AND LOGIC
  FOR SECOND TRY HAS FAILED TO YIELD A SOLUTION
c
  ierr = 1
  write(*,40) nitysi
40  format(/,' Newton iteration for ysi failed to converge in ',
c
  i3,' iterations',/)
  return
c
  COMPUTE REMAINING QUANTITIES
c
100 continue
c
  COMPUTE ei
c
  hspct = hsi - pcps*deltg
  ei = gami*hspct + hgi*deltg
c

```

```

c      COMPUTE kgi, hgi, hfi DERIVATIVES W.R.T. alpg, tg, tf
c
c      om2alp = one - two*alpg
c
c      dhgida = (one - phitg*(one - phiaf))
c      * (phiaf*om2alp*hgic + dpagda*hgis)
c      - phitg*dpafda*(phiaf*hgis - hgi1) - dpagda*hgi0
c      dhgdtg = -dhgdti
c
c      dhfida = (one - phitf*(one - phiaf))
c      * (phiaf*om2alp*hfic - dpafda*hfis)
c      + phitf*dpagda*(phiaf*hfis - hfi0) + dpafda*hf11
c      dhfdtf = -dhfdti
c
c      PREPARE TO COMPUTE DERIVATIVES W.R.T. BULK PARAMETERS
c
c      gdhs = fg + gami*dhsidt
c      fgkp = (kgi + omphi*gami)/p
c      rdnm = one/(fgkp/dtidps - fy*dgidti)
c
c      COMPUTE DERIVATIVES W.R.T. PRESSURE, p
c
c      fp      = -gami*dhsidp
c      dtidp = rdnm*(fgkp*ysi + fy*rdnom*fp)
c      dgidp = dgiddti*dtidp + rdnom*fp
c      deidp = hspct*dgidp + gdhs*dtidp - fp
c
c      COMPUTE DERIVATIVES W.R.T. VOID FRACTION, alpg
c
c      dgida = -rdnom*(dhfida*deltf + dhgida*deltg)
c      deida = hspct*dgida + dhgida*deltg
c
c      COMPUTE DERIVATIVES W.R.T. GAS TEMPERATURE, tg
c
c      ftg      = -pcps*gami - deltg*dhgdtg + hgi
c      dtidtg = rdnm*fy*rdnom*ftg
c      dgidtg = dgiddti*dtidtg + rdnom*ftg
c      deidtg = hspct*dgidtg + gdhs*dtidtg - ftg
c
c      COMPUTE DERIVATIVES W.R.T. LIQUID TEMPERATURE, tf
c
c      ftf      = +pcpw*gami - deltf*dhfdtf + hfi
c      dtidtf = rdnm*fy*rdnom*ftf
c      dgidtf = dgiddti*dtidtf + rdnom*ftf
c      deidtf = hspct*dgidtf + gdhs*dtidtf
c
c      COMPUTE DERIVATIVES W.R.T. AIR MASS FRACTION, xa
c
c      fxa      = -(kgi - gami*phi)
c      * (watmw(ilq)*airmw)/(airmw*xs + watmw(ilq)*xa)**2
c      dtidxa = rdnm*fxa
c      dgidxa = dgiddti*dtidxa
c      deidxa = hspct*dgidxa + gdhs*dtidxa
c
c      end if
c
c      return
c      end

```

GEOFLD

```

subroutine geofld (absrx,absrz,acx,acz,aratx,aratz,axx,azz,cosx,
c      cosz,deffz,dhx,dhz,dxm,dz,dzm,formx,formz,
c      fldmz,fldcz,c0bz,c0sz,ckbz,cksz,fmltx,fmltz,
c      frex,frez,volc,

```

```

4          absrt,act,aratt,azt, cost,defft,dht,dzt,dzmt,
4          formt, fldmt, fldct, c0bt, c0st, ckbt, ckst, fmltt,
4          fret, volt,
4          absrb,acb,aratb,azb,cosb,deffb,dhb,dzb,dzmb,
4          formb, fldmb, fldcb, c0bb, c0sb, ckbb, cksb, fmltb,
4          freb, volb,
4          acpl, volpl, actb, voltb,
4          iaz1,icc,na,nazc,nx,nchn,nxmax,nz,nzp1,nzp2,
4          nzp3,nzt,nzb,botln,subln,topln,iunits,istop)

C
C *****
C *
C * SUBROUTINE geofld
C *
C * SUBROUTINE TO READ FLUID GEOMETRY INPUT DATA
C *
C * THE FOLLOWING DATA IS READ:
C *     nx = NUMBER OF AZIMUTHAL CELLS IN EACH FLOW CHANNEL
C *
C *****
C implicit real (a-h,o-z), integer (i-n)
C parameter (zero=0.0, half=0.5, one=1.0, two=2.0,
4          grav=9.80665, d90=90.0)
C character*80 commnt

C
C GEOMETRIC PARAMETERS FOR MIDDLE SECTION
C
4 dimension absrz(nzp3,nxmax,nchn), absrx(nzp2,nxmax,nchn),
4          acz(nzp3,nxmax,nchn), acx(nzp2,nxmax,nchn),
4          aratz(nzp3,nxmax,nchn), aratx(nzp2,nxmax,nchn),
4          azz(nzp2,nxmax,nchn), axx(nzp2,nxmax,nchn),
4          cosz(nzp3,nxmax,nchn), cosx(nzp2,nxmax,nchn),
4          deffz(nzp3,nxmax,nchn), volc(nzp2,nxmax,nchn),
4          dhz(nzp3,nxmax,nchn), dhx(nzp2,nxmax,nchn),
4          formz(nzp3,nxmax,nchn), formx(nzp2,nxmax,nchn),
4          fldmz(nzp3,nxmax,nchn), fldcz(nzp3,nxmax,nchn),
4          c0bz(nzp3,nxmax,nchn), c0sz(nzp3,nxmax,nchn),
4          ckbz(nzp3,nxmax,nchn), cksz(nzp3,nxmax,nchn),
4          fmltz(nzp3,nxmax,nchn), fmltx(nzp2,nxmax,nchn),
4          frez(nzp3,nxmax,nchn), frex(nzp2,nxmax,nchn),
4          dzm(nzp3), dz(nzp2), dxm(nchn)

C
4 dimension iaz1(nxmax,nchn), icc(2,nxmax,nchn),
4          nazc(nxmax,nchn), nx(nchn)

C
C GEOMETRIC PARAMETERS FOR TOP AND BOTTOM SECTIONS
C
4 dimension absrt(nzt), absrb(nzb),
4          act(nzt), acb(nzb),
4          aratt(nzt), aratb(nzb),
4          azt(nzt), azb(nzb),
4          cost(nzt), cosb(nzb),
4          defft(nzt), deffb(nzb),
4          dht(nzt), dhb(nzb),
4          dzt(nzt), dzb(nzb),
4          dzmt(nzt), dzmb(nzb),
4          fldmt(nzt), fldmb(nzb),
4          fldct(nzt), fldcb(nzb),
4          c0bt(nzt), c0bb(nzb),
4          c0st(nzt), c0sb(nzb),
4          ckbt(nzt), ckbb(nzb),
4          ckst(nzt), cksb(nzb),
4          fmltt(nzt), fmltb(nzb),
4          fret(nzt), freb(nzb),

```

```

4          formt(nzt), formb(nzb),
4          volt(nzt), volb(nzb)
C
C      common /iounit/ ninp, nout, ndmp, ntmp, nrsti, nrsto
C
C      SET SRS TO SI CONVERSION FACTORS:
C
C          cim - CONVERSION FROM INCHES TO METERS
C          csqim - CONVERSION FROM SQUARE INCHES TO SQUARE METERS
C          ccuim - CONVERSION FROM CUBIC INCHES TO CUBIC METERS
C
C      data cim/2.540e-02/, csqim/6.45160e-04/, ccuim/1.638706e-05/
C      pi = acos(-one)
C
C      READ FLUID INPUT GEOMETRIC DATA:
C      READ PLENUM VOLUME, MID-CELL AREA, AND JUNCTION AREA
C
C      5      format (a)
C      read (ninp,5) commnt
C      read (ninp,*) volpl, acpl
C      if (iunits.eq.2) then
C          volpl = ccuim*volpl
C          acpl = csqim*acpl
C      end if
C
C      TOP SECTION MESH SPACING DATA
C
C      read (ninp,5) commnt
C      read (ninp,*) iuform
C      if (iuform.eq.1) then
C          read (ninp,*) dztot
C          dzcell = dztot/real(nzt)
C          do 10 jz=1,nzt
C              dzt(jz) = dzcell
10      continue
C      else
C          read (ninp,*) (dzt(jz), jz=1,nzt)
C      end if
C
C      READ TOP SECTION FLUID GEOMETRIC PARAMETERS
C
C      read (ninp,*) iuform
C      if (iuform.eq.1) then
C          read (ninp,*) volume, areat, areac, cosine, diamtr,
4          absr, fmlt, fre, form, deff, fldm, fldc,
4          c0b, c0s, ckb, cks
C          do 20 jz=1,nzt
C              volt(jz) = volume
C              act(jz) = areat
C              azt(jz) = areac
C              cost(jz) = cosine
C              dht(jz) = diamtr
C              absrt(jz) = absr
C              fmltt(jz) = fmlt
C              fret(jz) = fre
C              formt(jz) = form
C              defft(jz) = deff
C              fldmt(jz) = fldm
C              fldct(jz) = fldc
C              c0bt(jz) = c0b
C              c0st(jz) = c0s
C              ckbt(jz) = ckb
C              ckst(jz) = cks
20      continue
```

```

      else
        read (ninp,*) (volt(jz), act(jz), azt(jz), cost(jz),
          &          dht(jz), absrt(jz), fmltt(jz), fret(jz),
          &          formt(jz), defft(jz), fldmt(jz), fldct(jz),
          &          c0bt(jz), c0st(jz), ckbt(jz), ckst(jz),
          &          jz=1,nzt)
      end if

c
c  CONVERT TO SI UNITS
c
      if (iunits.eq.2) then
        do 30 jz=1,nzt
          dzt(jz) = cim*dzt(jz)
          volt(jz) = ccuim*volt(jz)
          act(jz) = csqim*act(jz)
          azt(jz) = csqim*azt(jz)
          dht(jz) = cim*dht(jz)
          absrt(jz) = cim*absrt(jz)
          defft(jz) = cim*defft(jz)
30      continue
        end if

c
c  READ MIDDLE SECTION FLUID GEOMETRIC PARAMETERS
c
      read (ninp,5) commnt

c
c  AXIAL MESH SPACING DATA
c
      read (ninp,*) iuform, bow, omega
      if (iuform.eq.1) then
        read (ninp,*) dztot
        dzcell = dztot/real(nz)
        do 40 jz=2,nzpl
          dz(jz) = dzcell
40      continue
      else
        read (ninp,*) (dz(jz), jz=2,nzpl)
        dztot = zero
        do 50 jz=2,nzpl
          dztot = dztot + dz(jz)
50      continue
      end if

c
c  CONVERT TO SI UNITS
c
      if (iunits.eq.2) then
        bow = cim*bow
        dztot = cim*dztot
        do 60 jz=2,nzpl
          dz(jz) = cim*dz(jz)
60      continue
      end if

c
      do 130 ic=1,nchn
        read (ninp,5) commnt

c
c  NUMBER OF AZIMUTHAL CELLS IN THE CHANNEL
c
        read (ninp,*) nsub, di, do
        dxm(ic) = half*pi*(di + do)/real(nsub)
        nx(ic) = nsub
        if (nsub.gt.nxmax .or. nsub.le.0) then
          write (*,600) ic, nx(ic), nchn, nxmax
          istop = 1

```

```

      end if
      write (nout,500) nsub, ic
c
c      AZIMUTHAL GEOMETRY DATA:
c      (TEMPORARILY HOLD RIB GAP WIDTH IN acx AREA ARRAY)
c
      read (ninp,5) commnt
      read (ninp,*) iuform
      if (iuform.eq.1) then
        read (ninp,*) gap1, gap2, cosine, diamtr,
        &      absr, fmlt, fre, form
        do 80 ix=1,nsub
          do 70 jz=2,nzp1
            acx(jz,ix,ic) = gap1
            axx(jz,ix,ic) = gap2
            cosx(jz,ix,ic) = cosine
            dhx(jz,ix,ic) = diamtr
            absrx(jz,ix,ic) = absr
            fmltx(jz,ix,ic) = fmlt
            frex(jz,ix,ic) = fre
            formx(jz,ix,ic) = form
70          continue
80          continue
        else if (iuform.eq.2) then
          read (ninp,*) (acx(2,ix,ic), axx(2,ix,ic),
        &      cosx(2,ix,ic), dhx(2,ix,ic),
        &      absrx(2,ix,ic), fmltx(2,ix,ic),
        &      frex(2,ix,ic), formx(2,ix,ic),
        &      ix=1,nsub)
          do 85 ix=1,nsub
            do 75 jz=3,nzp1
              acx(jz,ix,ic) = acx(2,ix,ic)
              axx(jz,ix,ic) = axx(2,ix,ic)
              cosx(jz,ix,ic) = cosx(2,ix,ic)
              dhx(jz,ix,ic) = dhx(2,ix,ic)
              absrx(jz,ix,ic) = absrx(2,ix,ic)
              fmltx(jz,ix,ic) = fmltx(2,ix,ic)
              frex(jz,ix,ic) = frex(2,ix,ic)
              formx(jz,ix,ic) = formx(2,ix,ic)
75              continue
85              continue
            else
              read (ninp,*) ((acx(jz,ix,ic), axx(jz,ix,ic),
        &      cosx(jz,ix,ic), dhx(jz,ix,ic),
        &      absrx(jz,ix,ic), fmltx(jz,ix,ic),
        &      frex(jz,ix,ic), formx(jz,ix,ic),
        &      ix=1,nsub), jz=2,nzp1)
            end if
c
c      AXIAL GEOMETRY DATA
c
      read (ninp,5) commnt
      read (ninp,*) iuform
      if (iuform.eq.1) then
        read (ninp,*) areaf, areac, cosine, diamtr,
        &      absr, fmlt, fre, form, deff,
        &      fldm, fldc, c0b, c0s, ckb, cks
        do 100 ix=1,nsub
          do 90 jz=2,nzp2
            acz(jz,ix,ic) = areaf
            azz(jz,ix,ic) = areac
            cosz(jz,ix,ic) = cosine
            dhz(jz,ix,ic) = diamtr
            absrz(jz,ix,ic) = absr

```



```

        dhx(jz,ix,ic) = cim*dhx(jz,ix,ic)
        dhz(jz,ix,ic) = cim*dhz(jz,ix,ic)
        absrx(jz,ix,ic) = cim*absrx(jz,ix,ic)
        absrz(jz,ix,ic) = cim*absrz(jz,ix,ic)
        deffz(jz,ix,ic) = cim*deffz(jz,ix,ic)
140      continue
        acz(nzp2,ix,ic) = csqim*acz(nzp2,ix,ic)
        dhz(nzp2,ix,ic) = cim*dhz(nzp2,ix,ic)
        absrz(nzp2,ix,ic) = cim*absrz(nzp2,ix,ic)
        deffz(nzp2,ix,ic) = cim*deffz(nzp2,ix,ic)
150      continue
160      continue
      end if
c
c      BOTTOM SECTION MESH SPACING DATA
c
      read (ninp,5) commnt
      read (ninp,*) iuform
      if (iuform.eq.1) then
        read (ninp,*) dztot
        dzcell = dztot/real(nzb)
        do 170 jz=1,nzb
          dzb(jz) = dzcell
170      continue
        else
          read (ninp,*) (dzb(jz), jz=1,nzb)
        end if
c
c      READ BOTTOM SECTION FLUID GEOMETRIC PARAMETERS
c
      read (ninp,*) iuform
      if (iuform.eq.1) then
        read (ninp,*) volume, areab, areac, cosine, diamtr,
        &      absr, fmlt, fre, form, deff, fldm, fldc,
        &      c0b, c0s, ckb, cks
        do 180 jz=1,nzb
          volb(jz) = volume
          acb(jz) = areab
          azb(jz) = areac
          cosb(jz) = cosine
          dhb(jz) = diamtr
          absrb(jz) = absr
          fmltb(jz) = fmlt
          freb(jz) = fre
          formb(jz) = form
          deffb(jz) = deff
          fldmb(jz) = fldm
          fldcb(jz) = fldc
          c0bb(jz) = c0b
          c0sb(jz) = c0s
          ckbb(jz) = ckb
          cksb(jz) = cks
180      continue
        else
          read (ninp,*) (volb(jz), acb(jz), azb(jz), cosb(jz),
        &      dhb(jz), absrb(jz), fmltb(jz), freb(jz),
        &      formb(jz), deffb(jz), fldmb(jz), fldcb(jz),
        &      c0bb(jz), c0sb(jz), ckbb(jz), cksb(jz),
        &      jz=1,nzb)
        end if
c
c      CONVERT TO SI UNITS
c
      if (iunits.eq.2) then
```



```

      do 190 jz=1,nzb
        dzb(jz) = cim*dzb(jz)
        volb(jz) = ccuim*volb(jz)
        acb(jz) = csqim*acb(jz)
        azb(jz) = csqim*azb(jz)
        dhb(jz) = cim*dhb(jz)
        absrb(jz) = cim*absrb(jz)
        deffb(jz) = cim*deffb(jz)
190      continue
    end if
C
C    READ TANK BOTTOM VOLUME AND AREA
C
    read (ninp,5) commnt
    read (ninp,*) voltb, actb
    if (iu.its.eq.2) then
      voltb = ccuim*voltb
      actb = csqim*actb
    end if
C
C    GEOMETRIC INPUT DATA HAS BEEN READ AND CONVERTED TO SI UNITS,
C    NOW COMPUTE THE REQUIRED FUNCTIONS OF THE GEOMETRIC DATA
C    -----
C
C    ADJUST DIRECTIONAL COSINES FOR BOWING
C
    if (bow.ne.zero) then
      pidz = pi/dztot
      zbow = bow*pidz
      do 220 ic=1,nchn
        tilt = omega/d90
        if (ic.eq.2*(ic/2)) tilt = tilt + half
C
        do 210 ix=1,nsub
          zface = zero
          angle = (ix - 1 - tilt)*pi*half
          do 200 jz=2,nzpl
C
C            ADJUST AXIAL DIRECTIONAL COSINES FOR BOWING
C
              theta = acos(cosz(jz,ix,ic))
              slope = zbow*cos(zface*pidz)
              phi = atan(slope)
              cosz(jz,ix,ic) = cos(theta + phi)
C
C            ADJUST AZIMUTHAL DIRECTIONAL COSINES FOR BOWING
C            ACCOUNTING FOR SUBCHANNEL ORIENTATION
C
              theta = acos(cosx(jz,ix,ic))
              zmid = zface + half*dz(jz)
              slope = zbow*cos(zmid*pidz)
              phi = atan(slope)
              cosx(jz,ix,ic) = cos(theta - phi)*sin(angle)
C
              zface = zface + dz(jz)
200          continue
C
              theta = acos(cosz(nzp2,ix,ic))
              slope = zbow*cos(zface*pidz)
              phi = atan(slope)
              cosz(nzp2,ix,ic) = cos(theta + phi)
210          continue
220        continue
      end if

```

```

c
c  CALCULATE MOMENTUM CELL AXIAL LENGTHS IN TOP SECTION
c  AND CONVERT DIRECTION COSINES TO GRAVITY VECTORS
c
  topln = zero
  do 230 jz=1,nzt
    jzm = jz - 1
    if (jz.eq.1) then
      dzmt(jz) = half*(volpl/acpl + dzt(jz))
      aratt(jz) = two*act(jz)*dzmt(jz)/(volpl + volt(jz))
    else
      dzmt(jz) = half*(dzt(jzm) + dzt(jz))
      aratt(jz) = two*act(jz)*dzmt(jz)/(volt(jz) + volt(jzm))
    end if
    cost(jz) = grav*cost(jz)
    topln = topln + dzmt(jz)
230  continue
c
c  CALCULATE MOMENTUM CELL LENGTHS AND MASS CELL VOLUMES IN
c  THE MIDDLE SECTION, CONVERT DIRECTION COSINES TO GRAVITY
c  VECTORS, AND AZIMUTHAL GAP LENGTHS TO AREAS
c
  subln = zero
  do 240 jz=2,nzpl
    jzm = jz - 1
    if (jz.eq.2) then
      dzm(jz) = half*(dzt(nzt) + dz(jz))
    else
      dzm(jz) = half*(dz(jzm) + dz(jz))
    end if
    subln = subln + dz(jz)
240  continue
c
  atop = zero
  abot = zero
  dzm(nzp2) = half*(dz(nzpl) + dzb(1))
c
  do 270 ic=1,nchn
    nsub = nx(ic)
    nset = na/nsub
    do 260 ix=1,nsub
c
c  SET UP AZIMUTHAL INTERCONNECTION ARRAYS
c
      if (ix.eq.1) then
        icc(1,ix,ic) = nsub
      else
        icc(1,ix,ic) = ix - 1
      end if
c
      if (ix.eq.nsub) then
        icc(2,ix,ic) = 1
      else
        icc(2,ix,ic) = ix + 1
      end if
c
c  FIND TOTAL FLOW AREAS AT TOP AND BOTTOM
c  FACES OF MIDDLE SECTION
c
      atop = atop + acz(2,ix,ic)
      abot = abot + acz(nzp2,ix,ic)
c
c  SET UP AZIMUTHAL CELL PARAMETERS FOR SUBCHANNEL
c

```

```

        ifaz = 1 + nset*(ix - 1)
        if (mod(ic,2).eq.0 .and. nsub.gt.1 .and. nchn.gt.1) then
            ifaz = ifaz - na/8
            if (ifaz.lt.1) ifaz = ifaz + na
        end if
        iazl(ix,ic) = ifaz
        nazc(ix,ic) = nset
        ixl = icc(1,ix,ic)
        ixr = ix
c
        do 250 jz=2,nzp1
            jzp = jz + 1
            volc(jz,ix,ic) = half*(acz(jz,ix,ic) +
&                acz(jzp,ix,ic))*dz(jz)
            cosx(jz,ix,ic) = grav*cosx(jz,ix,ic)
            cosz(jz,ix,ic) = grav*cosz(jz,ix,ic)
            acx(jz,ix,ic) = dz(jz)*acx(jz,ix,ic)
            axx(jz,ix,ic) = dz(jz)*axx(jz,ix,ic)
            aratx(jz,ix,ic) = two*acx(jz,ix,ic)*dxm(ic)/
&                (volc(jz,ixl,ic) + volc(jz,ixr,ic))
250        continue
            cosz(nzp2,ix,ic) = grav*cosz(nzp2,ix,ic)
260        continue
270        continue
c
c        CALCULATE MOMENTUM CELL AXIAL LENGTHS IN BOTTOM SECTION
c        AND CONVERT DIRECTION COSINES TO GRAVITY VECTORS
c
        botln = zero
        do 280 jz=1,nzb
            jzp = jz + 1
            if (jz.eq.nzb) then
                dzmb(jz) = half*(dzb(jz) + voltb/actb)
                aratb(jz) = two*acb(jz)*dzmb(jz)/(volb(jz) + voltb)
            else
                dzmb(jz) = half*(dzb(jz) + dzb(jzp))
                aratb(jz) = two*acb(jz)*dzmb(jz)/(volb(jz) + volb(jzp))
            end if
            cosb(jz) = grav*cosb(jz)
            botln = botln + dzmb(jz)
280        continue
c
c        SET GEOMETRIC PARAMETERS FOR FICTICIOUS CELLS
c        AT TOP AND BOTTOM OF THE MIDDLE SECTION
c
        vfract = volt(nzt)/atop
        vfracb = volb(1)/abot
        afract = act(nzt)/atop
        afracb = acb(1)/abot
c
        dz(1) = dzt(nzt)
        dzm(1) = dzmt(nzt)
        dz(nzp2) = dzb(1)
        dzm(nzp3) = dzmb(1)
        subln = subln + half*(dz(1) + dz(nzp2))
c
        do 310 ic=1,nchn
            nsub = nx(ic)
            do 300 ix=1,nsub
                volc(1,ix,ic) = vfract*acz(2,ix,ic)
                acx(1,ix,ic) = acx(2,ix,ic)
                axx(1,ix,ic) = axx(2,ix,ic)
                acz(1,ix,ic) = afract*acz(2,ix,ic)
                azz(1,ix,ic) = afract*azz(2,ix,ic)
            do 300

```

```

      cosz(1,ix,ic) = cost(nzt)
c
      volc(nzp2,ix,ic) = vfracb*acz(nzp2,ix,ic)
      acx(nzp2,ix,ic) = acx(nzp1,ix,ic)
      axx(nzp2,ix,ic) = axx(nzp1,ix,ic)
      acz(nzp3,ix,ic) = afracb*acz(nzp2,ix,ic)
      azz(nzp2,ix,ic) = afracb*azz(nzp1,ix,ic)
      cosz(nzp3,ix,ic) = cosb(1)
c
      do 290 jz=2,nzp2
        jzm = jz - 1
        aratz(jz,ix,ic) = two*acz(jz,ix,ic)*dzm(jz)/
          (volc(jzm,ix,ic) + volc(jz,ix,ic))
290      continue
300      continue
310      continue
c
c      WRITE FORMATS
c
500      format (1x,i3,' azimuthal cells are in channel ',i2,/)
c
c      ERROR MESSAGE FORMATS
c
600      format (/' << fatal error >>  nx(' ,i2,')', ' = ',i3, /
          &      ' the number of azimuthal cells in channel ',i2,
          &      ' must be 0 < nx =< ',i3)
c
      return
      end

```

GEOSLD

```

      subroutine geosld (diam,wt,mat,ribl,ribt,iorib,ioxid,nr,ichks,
          &      ncyl,nsurf,nrmax,nrmxp,nz,iunits,istop)
c
c      *****
c      *
c      *      SUBROUTINE geosld
c      *
c      *      SUBROUTINE TO READ SOLID GEOMETRY INPUT DATA
c      *
c      *      THE FOLLOWING DATA IS READ:
c      *      diam = DIAMETER OF RADIAL CELLS IN SOLID CYLINDERS (m)
c      *      wt = WEIGHT PERCENT OF LITHIUM OR URANIUM
c      *      IN METAL ALLOY
c      *      mat = RADIAL CELL MATERIAL IDENTIFICATION
c      *      ribl = RIB LENGTH (m)
c      *      ribt = RIB THICKNESS (HALF WIDTH) (m)
c      *      iorib = RIB ORIENTATION FLAG
c      *      nr = NUMBER OF RADIAL CELLS IN EACH SOLID CYLINDER
c      *      ichks = CRITERIA CHECKING FLAGS FOR SURFACES
c      *
c      *****
c      implicit real (a-h,o-z), integer (i-n)
c      parameter (zero=0.0, mats=9)
c      character*80 commnt
c
c      SOLID GEOMETRIC ARRAYS
c
c      dimension diam(nrmxp,ncyl), mat(nrmax,nz,ncyl),
          &      ribl(ncyl), ribt(ncyl), iorib(ncyl),
          &      wt(ncyl), nr(ncyl), ichks(nsurf),
          &      oxid(ncyl)
c
c      LOCAL ARRAYS

```

```
c      dimension wtmin(2), wtmax(2)
c
c      common /iounit/ ninp, nout, ndmp, ntmp, nrsti, nrsto
c
c      data wtmin /0.0, 0.0/, wtmax /10.0, 30.5/
c
c      SET SRS TO SI CONVERSION FACTOR:
c
c      cim - CONVERSION FROM INCHES TO METERS
c
c      data cim/2.540e-02/
c
c      READ IN CYLINDER RADIAL NODALIZATION:
c      nsect - NUMBER OF RADIAL SECTORS IN THE CYLINDER
c      ncell - NUMBER OF RADIAL CELLS WITHIN THE SECTOR
c
c      do 50 icyln=1,ncyln
c         read (ninp,5) commnt
c         read (ninp,*) dinner, nsect
c         nr(icyln) = 0
c
c      LOOP OVER RADIAL SECTORS AND CALCULATE CELL DIAMETERS
c
c         id = 1
c         diam(id,icyln) = dinner
c         do 20 isect=1,nsect
c            read (ninp,*) douter, ncell
c            nr(icyln) = nr(icyln) + ncell
c            dcell = (douter - dinner)/ncell
c            do 10 icell=1,ncell
c               id = id + 1
c               diam(id,icyln) = dinner + icell*dcell
10          continue
c          dinner = douter
20         continue
c
c      READ IN RIB GEOMETRY AND ALLOY WEIGHT PERCENT:
c      nsect - NUMBER OF AXIAL SECTORS IN THE CYLINDER
c
c         read (ninp,5) commnt
c         read (ninp,*) iorib(icyln), ribl(icyln), ribt(icyln)
c         read (ninp,5) commnt
c         read (ninp,*) ioxid(icyln), wt(icyln), nsect
c
c      LOOP OVER AXIAL SECTORS AND READ MATERIAL IDENTIFICATIONS
c
c         izl = 1
c         nri = nr(icyln)
c         do 40 isect=1,nsect
c            read (ninp,*) iz2, (mat(ir,izl,icyln), ir=1,nri)
c            if (iz2.gt.izl) then
c               izlp = izl + 1
c               do 30 iz=izlp,iz2
c                  do 30 ir=1,nri
c                     mat(ir,iz,icyln) = mat(ir,izl,icyln)
30          continue
c            end if
c            izl = iz2 + 1
40         continue
c
c      continue
c
c      READ IN CRITERIA CHECKING FLAG FOR EACH SOLID SURFACE
```

```
c      read (ninp,5)  commnt
      read (ninp,*)   (ichks(isurf), isurf=1,nsurf)
      write (nout,160) (isurf, ichks(isurf), isurf=1,nsurf)

c
c      CONVERT TO SI UNITS
c
c      if (iunits.eq.2) then
        do 70 icyln=1,ncyln
          nri = nr(icyln)
          do 60 ir=1,nri
            diam(ir,icyln) = cim*diam(ir,icyln)
60          continue
            nrip = nri + 1
            diam(nrip,icyln) = cim*diam(nrip,icyln)
            ribl(icyln) = cim*ribl(icyln)
            ribt(icyln) = cim*ribs(icyln)
70          continue
        end if

c
c      CHECK INPUT VALUES AND WRITE INPUT TO OUTPUT FILE
c
c      do 100 icyln=1,ncyln
        nri = nr(icyln)
        nrip = nri + 1
        write (nout,120) icyln, wt(icyln), lorib(icyln),
c          ribl(icyln),  ribt(icyln)

c
c      CHECK THAT ENTERED DIAMETERS ARE > 0 AND ARE IN ASCENDING
c      ORDER AND WRITE DIAMETERS TO OUTPUT FILE
c
c      do 80 ir=1,nrip
        write (nout,130) diam(ir,icyln)
        if (diam(ir,icyln).lt.zero) then
          write (*,230) diam(ir,icyln), icyln
          istop = 1
        end if

c      if (ir.lt.nrip) then
        deld = diam(ir+1,icyln) - diam(ir,icyln)
      else if (icyln.lt.ncyln) then
        deld = diam(1,icyln+1) - diam(ir,icyln)
      end if

c      if (deld.le.zero) then
        write (*,240) icyln
        istop = 1
      end if
80      continue

c
c      CHECK THAT WEIGHT PERCENTS FOR ALLOYS ARE WITHIN ALLOWED BOUNDS,
c      CHECK THAT MATERIAL IDENTIFICATION NUMBERS ARE ALL > 0,
c      AND WRITE MATERIAL IDENTIFICATION NUMBERS TO OUTPUT FILE
c
      write (nout,140)
      do 90 iz=1,nz
        write (nout,150) (mat(ir,iz,icyln), ir=1,nri)
        do 85 ir=1,nri
          imat = mat(ir,iz,icyln)
          if (imat.le.0 .or. imat.gt.mats) then
            write (*,220) imat, icyln
            istop = 1
          else if (imat.eq.4 .or. imat.eq.5) then
            if (wt(icyln).lt.wtmin(imat-3) .or.
```

```

        &          wt(icyln).gt.wtmax(imat-3)) then
            write (*,210) wt(icyln), icyln
            istop = 1
        end if
    end if
85      continue
90      continue
c
c      FOR REACTOR ASSEMBLIES, CHECK THAT UNIFORM MATERIAL IS INDICATED
c
        do 95 ir=1,nri
            mtest = mat(ir,1,icyln)
            do 95 iz=2,nz
                if (mat(ir,iz,icyln).ne.mtest) then
                    write (*,250) icyln, ir, iz, mtest
                    istop = 1
                end if
95      continue
100     continue
c
c      WRITE FORMATS
c
5       format (a)
110     format (5x,i2,8x,i2)
120     format (/,' cylinder # ',i2,',',
        &          3x,'alloy weight percent = ',g12.5,/,
        &          23x,'rib orientation = ',i2,/,
        &          24x,'rib length (m) = ',g12.5,/,
        &          20x,'rib half width (m) = ',g12.5,/,
        &          ' diameter (m)',/,1x,i3(' '))
130     format (1x,g12.5)
140     format (/,' material id array',/,1x,i9(' '))
150     format (1x,35(i2))
160     format (//,' surface criteria checking flags (0=off, 1=on)',/
        &          ' surface checking flag',/1x,i23(' '),/
        &          12(3x,i2,i2x,i1,/)
c
c      ERROR MESSAGE FORMATS
c
210     format (' <<< fatal error >>> weight percent = ',g12.5,/,
        &          ' weight percent is out of range for cylinder ',i2,/)
c
220     format (' <<< fatal error >>> material id = ',i3,/,
        &          ' bad material identification number in cylinder ',i2,/)
c
230     format (' <<< fatal error >>> diameter = ',g12.5,/,
        &          ' a mesh diameter is < 0 in cylinder ',i2,/)
c
240     format (' <<< fatal error >>> in cylinder ',i2,/,
        &          ' the mesh diameters are not in ascending order',/)
c
250     format (' <<< fatal error >>> material id in cylinder ',i2,/,
        &          ' at radial cell ',i2,' and axial level ',i2,/,
        &          ' does not equal ',i2,' the id at the top axial level',/
        &          ' the material id specification must be corrected'/)
c
        return
    end

```

HCONV

```

        subroutine hconv (qflux,dqdtw,hfc,twall,tfld,gfld,dhy,visf,
        &          condf,cpf,visw,dvdtw,idbst)
c
c      *****

```

```

C      *
C      * SUBROUTINE hconv
C      *
C      * SUBROUTINE TO CALCULATE FORCED CONVECTION SINGLE-PHASE HEAT
C      * FLUXES USING THE DITTUS-BOELTER OR SIEDER-TATE CORRELATIONS
C      *
C      * OUTPUT ARGUMENTS:
C      *   qflux - SURFACE HEAT FLUX (W/m**2)
C      *   dqdtw - DERIVATIVE OF HEAT FLUX WITH RESPECT TO WALL
C      *             TEMPERATURE
C      *   hfc - FORCED CONVECTION HEAT TRANSFER COEFFICIENT
C      *
C      * INPUT ARGUMENTS:
C      *   twall - WALL TEMPERATURE, K
C      *   tfld - FLUID TEMPERATURE, K
C      *   gfld - FLUID MASS FLUX, kg/m**2-s
C      *   dhy - CELL HYDRAULIC DIAMETER, m
C      *   visf - FLUID VISCOSITY, kg/m-s
C      *   condf - FLUID THERMAL CONDUCTIVITY, W/m-C
C      *   cpf - FLUID SPECIFIC HEAT, J/kg-C
C      *   visw - FLUID VISCOSITY AT WALL TEMPERATURE, kg/m-s
C      *   idbst - IDENTIFIER TO SELECT DITTUS-BOELTER (idbst=1)
C      *             OR SIEDER-TATE (idbst=2) CORRELATION
C      *   dhdtw - NORMALIZED DERIVATIVE OF HEAT TRANSFER COEFF
C      *             W.R.T. WALL TEMPERATURE (1/C)
C      *
C      *****
C      implicit real (a-h,o-z), integer (i-n)
C      parameter (zero=0.0)
C
C      SINGLE PHASE HEAT TRANSFER PARAMETERS
C
C      parameter (rnul=4.0, xre=0.80)
C
C      dimension cdbst(2), xdbst(2), xvisc(2)
C      data cdbst/0.023, 0.027/
C      data xdbst/0.400, 0.333/
C      data xvisc/0.000, 0.140/
C
C      if (gfld.eq.zero) return
C
C      (idbst=1) => DITTUS-BOELTER CORRELATION
C      (idbst=2) => SIEDER-TATE CORRELATION
C
C      cof = cdbst(idbst)
C      xpr = xdbst(idbst)
C      xvs = xvisc(idbst)
C
C      CALCULATE SINGLE PHASE HEAT TRANSFER COEFFICIENT
C
C      re = gfld*dhy/visf
C      pr = cpf*visf/condf
C      rnu = cof*(re**xre)*(pr**xpr)*(visf/visw)**xvs
C
C      if (rnu.lt.rnul) then
C
C      LAMINAR FORCED CONVECTION
C
C      hfc = condf*rnul/dhy
C      dhdtw = zero
C      else
C
C      TURBULENT FORCED CONVECTION
C
C      hfc = condf*rnu/dhy

```



```

      dhdtw = -xvs*dvdwtw
    end if
  c
  c    CALCULATE HEAT FLUX AND DERIVATIVE
  c
      delt = twall - tfld
      qflux = hfc*delt
      dqdtw = hfc + qflux*dhdtw
  c
      return
    end

```

HFTA

```

subroutine hfia (uf,rhof,thermf,viscf,cpf,delta,hf,length)
  c
  c *****
  c *
  c * THIS SUBROUTINE COMPUTES THE HEAT AND MASS TRANSFER
  c * COEFFICIENTS ON THE LIQ SIDE FOR ANNULAR OR RIB FLOW
  c *
  c *
  c * INPUT: rhof - liquid density, kg/m^3
  c *          uf - liquid velocity, m/s
  c *          thermf- liquid thermal conductivity, W/m-K
  c *          viscf - liquid viscosity, kg/m-s
  c *          cpf - liquid heat capacity, J/kg-K
  c *          delta - liquid film thickness, m
  c *          length- length of annular film, m
  c *                  (note: this parameter is used only if the
  c *                  film Reynolds number is laminar; therefore
  c *                  it is reasonable to assume it equal to the
  c *                  overall channel length)
  c *
  c * OUTPUT: hf - heat transfer coef., w/m^2-K
  c *
  c * INTERNAL:
  c *
  c *          re - film Reynolds number based on liquid properties
  c *          pr - liquid Prandtl number
  c *          pe - Peclet number for heat transfer
  c *
  c * BASIS IS:
  c *          NU = ((3/(2*PI))*(DEL/L)*PE)**.5      FOR RE < 1200
  c *          SEE TREYBAL,R.E.,MASS TRANSFER OPERATIONS,3RD.ED.,
  c *          PP.52-54, & 75.
  c *
  c *          NU = 1.76E-5*(RE**1.506)*(PR**0.5)    FOR 1300 < RE < 8300*
  c *
  c *          NU = NU(RE<1200) + 0.01*(NU(RE>1300) - NU(RE<1200))*
  c *                  (RE - 1200)
  c *          LINEAR INTERPOLATION FOR 1200 < RE < 1300*
  c *
  c *          therm= thermal conductivity, rhof= liq.density, viscf=liq.visc
  c *          cpf= liq. heat capacity, uf=liq.velocity, ug= gas velocity
  c *          difft= thermal diffusivity, pe= peclet no., anu= nusselt no.
  c *          h= heat transfer coefficient
  c *
  c *****
  c
  real length
  parameter (four=4.0, pi=3.14159)
  parameter (cnst=3.0/(2.0*pi))
  parameter (fract=0.01)
  c

```

```
data a2/1.76e-5/, a3/1.506/, relam/1200.0/, retur/1300/, eps/0.1/
```

```

subroutine hfib (uf,ug,rhof,thermf,cpf,dia,hf,visf,visg)
C
C *****
C
C *
C *
C * SUBROUTINE hfib:
C *
C * THIS SUBROUTINE COMPUTES THE HEAT TRANSFER
C * COEFFICIENT ON THE LIQUID SIDE FOR BUBBLES
C *
C * INPUT:
C *
C * OUTPUT:
C *
C * INPUT: rhof - liquid density, kg/m^3
C *          uf - liquid velocity, m/s
C *          ug - mixture gas velocity, m/s
C *          thermf- thermal conductivity, W/m-K
C *          dia - average bubble diameter, m
C *          cpf - liquid heat capacity, J/kg-K
C *          visf - dynamic viscosity of liquid, Pa-s
C *          visg - dynamic viscosity of gas, Pa-s
C *
C * NOTE: THE ABOVE ARE MIXTURE GAS PROPERTIES TO BE EVALUATED
C *        AT BULK GAS TEMPERATURE AND PRESSURE.
C *
C * OUTPUT: hf - heat transfer coef., w/m^2-K
C *
C * INTERNAL:
C *          diff- liquid thermal diffusivity, m^2/s
C *          watmw- molecular weight of light water, kg/kgmole
C *          Le - Lewis Number, Sc/Pr
C *
C *
C * HEAT TRANS. COEFF. LOGIC:
C *
C * FOR RE < 1, BASIS IS:
C *
C *          NU = 2 + 0.5*PE + 0.25*(2*VISF+3*VISG)/(3*VISF+
C *              3*VISG)*PE**2*LN(PE)

```

```

C      *
C      *      WHERE PE < 0.5
C      *      SEE BRENNER, H., CHEM. ENG. SCI., V. 18, 109-122 (1963))
C      *
C      *      AND
C      *      NU = 1 + ( 1 + .564 PE**(2/3))**(3/4)
C      *      WHERE PE > 0.5
C      *
C      *      (SEE CLIFT, ET AL. PG.50 EQN.3-50
C      *      OELLRICH, L., SCHMIDT-TRUB, H., AND BRAUER, H., CHEM. ENG.
C      *      SCI., 28, 711-721 (1973))
C      *
C      *      FOR 1 < RE < 200, BASIS IS:
C      *
C      *      NU = 2/SQRT(PI)*((1-2/3/(1+(2*RE**0.5
C      *      /8.67)**1.33)**0.75)**0.5)*PE**0.5
C      *
C      *      (SEE CLIFT ET AL, P. 136, EQN 5-39 (WITH KAPPA = 0
C      *      FOR GAS BUBBLE) AND FIGURE 5.30)
C      *
C      *      FOR 200 < RE < 1000000, BASIS IS:
C      *
C      *      NU = 2/SQRT(PI)*(1-2.89/RE**0.5)**0.5*PE**0.5
C      *
C      *      (SEE CLIFT ET AL, P. 135 EQN. 5-37, BASED ON
C      *      THIN CONCENTRATION BOUNDARY LAYER APPROXIMATION--
C      *      WORK OF LOCHIEL & CALDERBANK, CHEM. ENG. SCI,
C      *      V. 19 (471) (1964)
C      *      AND WINNIKOW, 1967, CHEM ENG SCI, V. 22.
C      *
C      *      FOR RE > 1000,000, BASIS IS:
C      *
C      *      NU = 1.13*PE**0.5
C      *
C      *      (SEE Ind. Eng. Chem., Fundamental, vol. 14, no. 4,
C      *      1975, pp. 365
C      *      THIS IS THE ASYMPTOTIC FORMULA FOR RE -> INFINITY)
C      *
C      *      AN ADDITIONAL CONSTRAINT IS THAT NU IS NEVER LESS THAN 2, THE
C      *      LIMIT FOR A SPHERE IN A STAGNANT FLUID
C      *
C      *      therm= thermal conductivity, rhof= liq.density,
C      *      cpf= liq. heat capacity, uf=liq.velocity, ug= gas velocity
C      *      diff= thermal diffusivity, pe= peclet no., anu= nusselt no.
C      *      h= heat transfer coefficient, urel= relative velocity with
C      *      low limit, visf = dynamic viscosity of liquid,
C      *      visg = dynamic viscosity of gas
C      *
C      *      *****
C
C      parameter (half=0.5, one=1.0, two=2.0, three=3.0)
C      parameter (twoth=two/three, threfr=0.75, eps=0.1)
C      parameter (pi=3.14159)
C
C      data a1/0.564/, a2/2.89/, b1/0.1415/
C      data twohun/200.0/, remax/1000000.0/
C
C      diff = thermf/(rhof*cpf)
C      urel = max(abs(uf-ug),eps)
C      re   = urel*dia*rhof/visf
C      pe   = dia*urel/diff
C
C      if (re.lt.one) then

```

```

      if (pe.lt.half) then
        anu = two + pe*half*(one + pe*half*(twoth*visf + visg)/
          (visf + visg)*alog(pe))
      else
        anu = one + (one + al*(pe**twoth))**threfr
      end if
c
      else if (re.lt.twohun) then
        anu = two*sqrt(pe*(one - twoth/(one +
          bl*(re**twoth))**threfr)/pi)
c
      else if (re.lt.remax) then
        anu = two*sqrt(pe*(one - a2/sqrt(re))/pi)
c
      else
        anu = two*sqrt(pe/pi)
      end if
c
      if (anu.lt.two) anu = two
      hf = anu*thermf/dia
c
      return
    end

```

HFIS

```

      subroutine hfis (viscf,rhof,thermf,cpf,dhydrl,hf)
c
c *****
c *
c * SUBROUTINE hfis:
c *
c * THIS SUBROUTINE COMPUTES THE HEAT TRANSFER
c * COEFFICIENT ON THE LIQUID SIDE FOR TAYLOR BUBBLES
c *
c *
c * INPUT: viscf - liquid viscosity, kg/m-s
c *          rhof - liquid density, kg/m^3
c *          thermf - thermal conductivity, W/m-K
c *          cpf - liquid heat capacity, J/kg-K
c *          dhydrl - hydraulic diameter, m
c *
c * NOTE: THE ABOVE ARE MIXTURE GAS PROPERTIES TO BE EVALUATED
c *        AT BULK GAS TEMPERATURE AND PRESSURE.
c *
c * OUTPUT: hf - heat transfer coef., w/m^2-K
c *
c * HEAT TRANS. COEFF. LOGIC
c *
c * NU = CS*DS*(G/LS)**0.25/DIFFT**0.5
c *
c * BASIS IS
c *
c * VAN HEUVEN, J. W., AND BEEK, W. J., 1963, CHEM. ENG. SCI.,
c * V. 18 (377)
c * WHERE IT IS ASSUMED THAT DS/LS > 1, SO CS = 1
c * AND LS IS SET EQUAL TO 4 CM--SEE TF DOCUMENTATION FOR
c * JUSTIFICATION OF THIS VALUE
c *
c * anu = nusselt number, hf = heat transfer coefficient
c *
c *****
c
      parameter (g=9.81)
c

```

```

      data a1/0.88/, a2/4.50/
c
      dia = a1*dhydr1
      diff = thermf/(rhof*cpf)
      slugln = a2*dhydr1
      anu = dia*sqrt(sqrt(g/slugln)/diff)
      hf = thermf*anu/dia
c
      return
      end

```

HFLUID

```

      subroutine hfluid(p,t,hfs,dhfsdt,hf,dhfdp,dhfdt)
c
c      *****
c      *
c      * INPUT:
c      *   p = TOTAL PRESSURE IN Pa
c      *   t = TEMPERATURE IN K
c      *   hfs = LIQUID SATURATION ENTHALPY AT t IN J/kg
c      *   dhfsdt = DERIVATIVE OF hfs W.R.T. t
c      *
c      * OUTPUT:
c      *   hf = ENTHALPY OF LIQUID IN J/kg
c      *   dhfdp = DERIVATIVE OF hf W.R.T. p AT CONSTANT t
c      *   dhfdt = DERIVATIVE OF hf W.R.T. t AT CONSTANT p
c      *
c      *****
c
c      parameter (zero=0.0)
c
c      hf = hfs
c      dhfdp = zero
c      dhfdt = dhfsdt
c
c      return
      end

```

HFSAT

```

      subroutine hfsat(t,l,hfs,dhfsdt)
c
c      *****
c      *
c      * INPUT:
c      *   t = TEMPERATURE IN K
c      *   l = IDENTIFIER (l=1 FOR H2O, l=2 FOR D2O)
c      *
c      * OUTPUT:
c      *   hfs = LIQUID SATURATION ENTHALPY IN J/kg
c      *   dhfsdt = DERIVATIVE OF hfs W.R.T. t
c      *
c      * RANGE:
c      *   273K < t < 453K
c      *
c      *****
c
c      parameter (two=2.0)
c      dimension c1(2), c2(2), c3(2)
c
c      H2O PROPERTIES
c
c      data c1(1)/-1.1094e+6/, c2(1)/3960.2/, c3(1)/0.36868/
c

```

```

c      D2O PROPERTIES
c
c      data c1(2)/-1.1856e+6/, c2(2)/4340.2/, c3(2)/-0.20733/
c
c      hfs = c1(1) + (c2(1) + c3(1)*t)*t
c      dhfsdt = c2(1) + two*c3(1)*t
c
c      return
c      end

```

HGIA

```

subroutine hgia (p,tg,ug,rhog,viscg,ysi,ysb,thermg,cpg,
& diffm,dhydrl,hg,akg,delta)
c
c      *****
c      *
c      * THIS SUBROUTINE COMPUTES THE HEAT AND MASS TRANSFER
c      * COEFFICIENTS ON THE GAS SIDE FOR RIB FLOW
c      *
c      *
c      * INPUT: rhog - mixture gas density, kg/m^3
c      *          p   - pressure, Pa
c      *          tg   - bulk gas temperature, K
c      *          ug   - gas velocity, m/s
c      *          viscg - mixture gas viscosity, kg/m-s
c      *          dhydrl - hydraulic diameter, m
c      *          thermg - thermal conductivity, W/m-K
c      *          diffm - mixture gas mass diffusivity, m^2/s
c      *          cpg   - mixture gas heat capacity, J/kg-K
c      *          uf    - liquid velocity, m/s
c      *
c      * NOTE: THE ABOVE ARE MIXTURE GAS PROPERTIES TO BE EVALUATED
c      *        AT BULK GAS TEMPERATURE AND PRESSURE.
c      *
c      * OUTPUT: hg   - heat transfer coef., w/m^2-K
c      *          akg  - mass transfer coef., (kgmole gas mix)-m/s
c      *
c      * therm= thermal conductivity, rhof= liq.density,
c      * cpf= liq. heat capacity, uf=liq.velocity, ug= gas velocity
c      * diff= thermal diffusivity, pe= peclet no., anu= nusselt no.
c      * h= heat transfer coefficient
c      *
c      * COEFFICIENT LOGIC:
c      *
c      *          SH = 0.023*RE**0.83*SC**0.44/ylm
c      *
c      * GILLILAND AND SHERWOOD, IND. ENG. CHEM., V. 26, 1934
c      * AS QUOTED IN SHERWOOD, PIGFORD, & WILKE, MASS TRANSFER, 1975,
c      * P. 211. NOTE RE IS BASED ON GAS VELOCITY RELATIVE TO WALL, NOT
c      * TO LIQUID VELOCITY, AND THAT THE RANGE IS DICTATED BY THE FILM
c      * REYNOLDS NUMBER, = 4*MASS FLOW/UNIT WIDTH/VISC
c      *
c      * ylm IS THE LOG MEAN MOLE FRACTION OF THE NON-DIFFUSING
c      * PHASE, BASED ON INTERFACE AND BULK PARTIAL PRESSURES
c      * THE CHILTON-COLBURN ANALOGY IS USED TO APPLY THE RELATIONS TO
c      * HEAT TRANSFER (SH*ylm IS EQUIVALENT TO NU)
c      *
c      * *****
c
c      parameter (half=0.5, one=1.0, third=1.0/3.0,
& pt8=0.8, rcon=8314.4)
c      data a1/0.023/, a2/0.83/, a3/0.44/
c      data epsya/1.0e-4/, remin/2000.0/

```

```

      re = dhydrl*rhog*abs(ug)/viscg
      re = max(re, remin)
      pr = cpg*viscg/thermg
      sc = viscg/(rhog*diffm)
      c = p/(rcon*tg)

C
      yai = max((one - ysi), epsya)
      yab = max((one - ysb), epsya)

C
C      ENSURE NUMERICAL STABILITY OF ylm
C
      if (abs(yai - yab) .lt. epsya) then
         ylm = yai
      else
         ylm = (yai - yab)/alog(yai/yab)
      end if

C
      cof = a1*(re**a2)
      sh = cof*sc**a3/ylm
      anu = cof*pr**a3

C
      hg = anu*thermg/dhydrl
      akg = sh*diffm/dhydrl
      akg = akg*c

C
      return
      end

```

HGIB

```

      subroutine hgib (dia, rhog, p, tg, thermg, diffm, cpg, hg, akg)

```

```

C
C      *****
C      *
C      *   SUBROUTINE hgib:
C      *
C      *   THIS SUBROUTINE COMPUTES THE HEAT AND MASS TRANSFER
C      *   COEFFICIENTS ON THE GAS SIDE FOR BUBBLES.
C      *
C      *   INPUT: dia   - bubble diameter, m
C      *             rhog - mixture gas density, kg/m^3
C      *             p    - fluid cell pressure, Pa
C      *             tg   - bulk mixture gas temperature, K
C      *             thermg- thermal conductivity, W/m-K
C      *             diffm - mixture gas mass diffusivity, m^2/s
C      *             cpg  - mixture gas heat capacity, J/kg-K
C      *
C      *   Note: The above are mixture gas properties to be evaluated
C      *         at bulk gas temperature and pressure.
C      *
C      *   OUTPUT: hg   - heat transfer coef., w/m^2-K
C      *             akg - mass transfer coef., (kgmole of gas phase)m/s
C      *
C      *   INTERNAL:
C      *             rcon - ideal gas constant, 8314.4 Pa-m^3/K-kgmole
C      *             diffm- mixture gas thermal diffusivity, m^2/s
C      *             watmw- molecular weight of light water, kg/kgmole
C      *             Le   - Lewis Number, Sc/Pr
C      *             c    - molar concentration of gas mixture based on
C      *                   ideal gas law, p/(rcon*tg), kgmole/m^3
C      *
C      *
C      *   HEAT TRANSFER COEFFICIENT LOGIC
C      *
C      *   BASIS: THAT BUBBLE SIDE HEAT AND MASS TRANSFER IS CONSIDERED *

```

```

C      *      TO BE MUCH MORE RAPID THAN LIQUID SIDE PHENOMENA      *
C      *      1) SEE TREYBAL, MASS TRANSFER OP, 3RD. ED. (1980), PG. 145 *
C      *      2) SHERWOOD, T.K., ET AL., MASS TRANSFER, PG. 231, SECOND *
C      *      PARA. IN SECTION 6.7 *
C      *
C      *      HEAT/MASS TRANSFER ANALOGY: CHILTON-COLBURN J-FACTORS *
C      *      1) SHERWOOD, ET AL., MASS TRANSFER (1975), CHAP. 7 *
C      *      PG. 260, EQN. 7.9 *
C      *      2) BIRD, STEWART, AND LIGHTFOOT, TRANSPORT PHENOMENA, *
C      *      CHAP. 21, PG. 647, EQN. 21.2-23 *
C      *
C      *      J-FACTOR ANALOGY IMPLIES       $Nu = Nu [Le]^{1/3}$  *
C      *      m      t *
C      *
C      *****
C
C      real lewis
C      parameter (third=1.0/3.0)
C      data rcon/8314.4/, hhigh/200.0/
C
C      lewis = thermg/(rhog*cpg*diffm)
C      c = p/(rcon*tg)
C
C      SET HEAT TRANSFER COEFFICIENT TO ARBITRARILY HIGH VALUE
C
C      anu = hhigh
C      hg = anu*thermg/dia
C
C      COMPUTE MASS TRANSFER COEFFICIENT BASED ON THE CHILTON-COLBURN
C      J-FACTOR ANALOGY
C
C      sh = anu*lewis**third
C      akq = sh*diffm/dia
C      akq = akq*c
C
C      return
C      end

```

HGIS

```

      subroutine hgis (p,tg,uf,ug,rhog,thermg,viscg,cpg,diffm,
&      dhydl,hg,akq)
C
C      *****
C      *
C      *      SUBROUTINE hgis:
C      *
C      *      THIS SUBROUTINE COMPUTES THE HEAT AND MASS TRANSFER
C      *      COEFFICIENTS ON THE GAS SIDE FOR SLUG BUBBLES
C      *
C      *
C      *      INPUT: rhog - mixture gas density, kg/m^3
C      *      p      - fluid cell pressure, Pa
C      *      tg      - bulk mixture gas temperature, K
C      *      thermg- thermal conductivity, W/m-K
C      *      diffm - mixture gas mass diffusivity, m^2/s
C      *      cpg     - mixture gas heat capacity, J/kg-K
C      *      uf      - liquid velocity, m/s
C      *      ug      - mixture gas velocity, m/s
C      *      dhydl- hydraulic diameter, m
C      *
C      *
C      *      NOTE: THE ABOVE ARE MIXTURE GAS PROPERTIES TO BE EVALUATED
C      *      AT BULK GAS TEMPERATURE AND PRESSURE.
C      *
C      *****

```



```

C      *
C      * OUTPUT: hg  - heat transfer coef., w/m^2-K
C      *              akq - mass transfer coef., kgmol of gas phase-m/s
C      *
C      * INTERNAL:
C      *      rcon - ideal gas constant, 8314.4 Pa-m^3/K-kgmole
C      *      alpha- mixture gas thermal diffusivity, m^2/s
C      *      watmw- molecular weight of light water, kg/kgmole
C      *      Le   - Lewis Number, Sc/Pr
C      *      c    - molar concentration of gas mixture based on
C      *              ideal gas law, p/(rcon*tg), kgmole/m^3
C      *      d    - slug bubble diameter, see Ishii & Mishima
C      *              NUREG/CR--1873, pg.32, between eqn 54 & eqn 55
C      *              equals .88*hydraulic diameter
C      *
C      * HEAT/MASS TRANS. COEFF. LOGIC
C      *
C      * BASIS IS
C      *      SH = 9.3              PE < 25
C      *      SH = 2.05 PE**0.5    PE > 25
C      *      (NOTE: CHANGED 9.3 TO 10.25 TO MAKE SMOOTH CHANGE)
C      *
C      * SEE
C      * FILLA ET AL., 1976,CHEM. ENG. SCI., V. 31 (359) AND
C      * DISCUSSION IN CLIFT ET AL., BUBBLES, DROPS, AND PARTICLES
C      * P. 241
C      *
C      * USE HEAT TRANSFER ANALOGY TO GET NU
C      *
C      * therm= thermal conductivity, rhof= liq.density,
C      * cpf= liq. heat capacity, uf=liq.velocity, ug= gas velocity
C      * diff= thermal diffusivity, pe= peclet no., anu= nusselt no.
C      * h= heat transfer coefficient, urel= relative velocity with low
C      * limit
C      *
C      *
C      *****
C
C      parameter (eps=0.1, rcon=8314.4)
C      data pemin/25.0/, shmin/10.25/, coef/2.05/
C
C      uslug = max(abs(ug),eps)
C      re    = dhydrl*uslug*rhog/viscg
C      pr    = cpq*viscg/thermg
C      pe    = re*pr
C      ped   = re*viscg/(rhog*diffm)
C      c     = p/(rcon*tg)
C
C      if (ped.lt.pemin) then
C          sh = shmin
C      else
C          sh = coef*sqrt(ped)
C      end if
C
C      if (pe.lt.pemin) then
C          anu = shmin
C      else
C          anu = coef*sqrt(pe)
C      end if
C
C      akq = sh*diffm/dhydrl
C      akq = akq*c
C      hg  = anu*thermg/dhydrl
C
C

```

```
return
end
```

HSSAT

```
subroutine hssat(p,l,hss,dhssdp)
c
c *****
c *
c * INPUT:
c *   p = PRESSURE IN Pa
c *   l = IDENTIFIER (l=1 FOR H2O, l=2 FOR D2O)
c *
c * OUTPUT:
c *   hss = STEAM SATURATION ENTHALPY IN J/kg
c *   dhssdp = DERIVATIVE OF hss W.R.T. p
c *
c * RANGE:
c *   611.3Pa < p < 1.0e+6Pa
c *
c *****
c
c parameter (two=2.0)
c dimension c1(2), c2(2), c3(2)
c
c H2O PROPERTIES
c
c data c1(1)/2.4057e+6/, c2(1)/3949.5/, c3(1)/1684.5/
c
c D2O PROPERTIES
c
c data c1(2)/2.2314e+6/, c2(2)/4054.7/, c3(2)/1526.0/
c
c      z = log(p)
c      hss = c1(l) + (c2(l) + c3(l)*z)*z
c      dhssdp = (c2(l) + two*c3(l)*z)/p
c
c return
c end
```

HSTEAM

```
subroutine hsteam(t,ts,dtsdp,hss,dhssdp,l,hs,dhsdp,dhsdt)
c
c *****
c *
c * INPUT:
c *   p = TOTAL PRESSURE IN Pa
c *   t = TEMPERATURE IN K
c *   ts = SATURATION TEMPERATURE AT TOTAL PRESSURE IN K
c *   dtsdp = DERIVATIVE OF ts W.R.T. TOTAL PRESSURE
c *   hss = SATURATION ENTHALPY AT TOTAL PRESSURE IN J/kg
c *   dhssdp = DERIVATIVE OF hss W.R.T. TOTAL PRESSURE
c *   l = IDENTIFIER (l=1 FOR H2O, l=2 FOR D2O)
c *
c * OUTPUT:
c *   hs = ENTHALPY OF STEAM IN J/kg
c *   dhsdp = DERIVATIVE OF hs W.R.T. TOTAL PRESSURE AT CONSTANT t
c *   dhsdt = DERIVATIVE OF hs W.R.T. t AT CONSTANT TOTAL PRESSURE
c *
c * RANGE:
c *   275K < t < 700K
c *   'low' pressure
c *
c *****
c
```

```

C
      parameter (two=2.0, three=3.0, four=4.0)
      dimension c1(2), c2(2), c3(2), c4(2)
C
C      H2O PROPERTIES
C
      data c1(1)/1901.4/,      c2(1)/-0.62129/,
&      c3(1)/1.9538e-3/, c4(1)/-1.0083e-6/
C
C      D2O PROPERTIES
C
      data c1(2)/1611.4/,      c2(2)/3.6681e-3/,
&      c3(2)/1.3023e-3/, c4(2)/-6.6266e-7/
C
      hs = hss + (c1(1) + ((c2(1)/two) + ((c3(1)/three)
&      + (c4(1)/four)*t)*t)*t
&      - (c1(1) + ((c2(1)/two) + ((c3(1)/three)
&      + (c4(1)/four)*ts)*ts)*ts
      dhssdp = dhssdp
&      - (c1(1) + (c2(1) + (c3(1) + c4(1)*ts)*ts)*ts)*dtsdp
      dhsdt = c1(1) + (c2(1) + (c3(1) + c4(1)*t)*t)*t
C
      return
      end

```

INBOND

```

      subroutine inbond (ppl0,alpp10,tgpl0,tfpl0,xapl0,
&      ptb0,alptb0,tgtb0,tftb0,xatb0,
&      qfin0,qgin0,fsplt,tnklv0,
&      ippl,ialpl,itgpl,itfpl,ixapl,
&      iptb,ialtb,itgtb,itftb,ixatb,
&      iqfin,iqgin,itnklv,tcmax,pkfac,
&      ichkc,nchn,nsubc,nspln,ncrit,ibond,
&      iunits,istop)
C
C      *****
C      *
C      * SUBROUTINE inbond
C      *
C      * SUBROUTINE TO PROCESS THERMAL-HYDRAULIC BOUNDARY CONDITIONS
C      * INPUT BOUNDARY CONDITIONS FOR FLUID-PHASE CALCULATIONS
C      *
C      *      istop = 0, OK; >0, TERMINATE PROBLEM AFTER READING INPUT
C      *
C      * SPLINE COEFFICIENT ARGUMENTS:
C      *
C      *      ppl0 - PLENUM PRESSURE
C      *      alpp10 - PLENUM VOID FRACTION
C      *      tfpl0 - PLENUM FLUID TEMPERATURE
C      *      tgpl0 - PLENUM GAS TEMPERATURE
C      *      xapl0 - PLENUM AIR MASS FRACTION
C      *      ptb0 - TANK BOTTOM PRESSURE
C      *      alptb0 - TANK BOTTOM VOID FRACTION
C      *      tftb0 - TANK BOTTOM FLUID TEMPERATURE
C      *      tgtb0 - TANK BOTTOM GAS TEMPERATURE
C      *      xatb0 - TANK BOTTOM AIR MASS FRACTION
C      *      qfin0 - INLET LIQUID FLOW RATE
C      *      qgin0 - INLET GAS FLOW RATE
C      *      tnklv0 - INITIAL TANK LEVEL
C      *
C      * POINTERS TO TRANSIENT PROFILES:
C      *
C      *      ippl - PLENUM PRESSURE
C      *      ialpl - PLENUM VOID FRACTION

```

```

c      *      itfpl - PLENUM FLUID TEMPERATURE      *
c      *      itgpl - PLENUM GAS TEMPERATURE      *
c      *      ixapl - PLENUM AIR MASS FRACTION      *
c      *      iptb - TANK BOTTOM PRESSURE          *
c      *      ialtb - TANK BOTTOM VOID FRACTION     *
c      *      itftb - TANK BOTTOM FLUID TEMPERATURE *
c      *      itgtb - TANK BOTTOM GAS TEMPERATURE  *
c      *      ixatb - TANK BOTTOM AIR MASS FRACTION *
c      *      iqfin - INLET LIQUID FLOW RATE        *
c      *      iqgin - INLET GAS FLOW RATE          *
c      *      itnklv - TANK LEVEL                  *
c      *
c      *****
c
c      implicit real (a-h,o-z), integer (i-n)
c      parameter (zero=0.0)
c      character*80 commnt
c
c      dimension fsplt(nchn), pkfac(ncrit), ichkc(ncrit)
c
c      common /iounit/ ninp, nout, ndmp, ntmp, nrsti, nrsto
c
c      CONVERSION FACTORS FOR INPUT DATA:
c      convp - CONVERSION FACTOR FROM PSI TO PASCAL
c      convf - CONVERSION FACTOR FROM GPM TO M**3/S
c      convm - CONVERSION FACTOR FROM INCHES TO METERS
c
c      data convp/6.894757e+03/, convf/6.309020e-05/,
c      6      convm/2.540000e-02/
c
c      READ SPLINE COEFFICIENTS FOR THE PLENUM BOUNDARY
c      PARAMETERS AND POINTERS TO THEIR TRANSIENT PROFILES
c
c      read (ninp,5) commnt
c      read (ninp,5) commnt
c      read (ninp,*) pp10, ippl
c      read (ninp,*) alpp10, ialpl
c      read (ninp,*) tfpl0, itfpl
c      read (ninp,*) tgpl0, itgpl
c      read (ninp,*) xapl0, ixapl
c
c      READ SPLINE COEFFICIENTS FOR THE TANK BOTTOM BOUNDARY
c      PARAMETERS AND POINTERS TO THEIR TRANSIENT PROFILES
c
c      read (ninp,5) commnt
c      read (ninp,*) ptb0, iptb
c      read (ninp,*) alptb0, ialtb
c      read (ninp,*) tftb0, itftb
c      read (ninp,*) tgtb0, itgtb
c      read (ninp,*) xatb0, ixatb
c
c      READ SPLINE COEFFICIENTS AND POINTERS FOR INLET FLOWS
c
c      read (ninp,5) commnt
c      read (ninp,*) qfin0, iqfin
c      read (ninp,*) qgin0, iqgin
c
c      INPUT INITIAL GUESS FOR FLOW SPLITS
c      TO CHANNELS IN MIDDLE SECTION
c
c      read (ninp,5) commnt
c      read (ninp,*) (fsplt(ic), ic=1,nchn)
c
c      NORMALIZE INPUT FLOW SPLITS

```

```
c      total = zero
c      do 10 ic=1,nchn
c          total = total + fsplt(ic)
10      continue
c
c      do 20 ic=1,nchn
c          fsplt(ic) = fsplt(ic)/total
20      continue
c
c      READ COEFFICIENT AND POINTER TO TANK LEVEL TRANSIENT PROFILE
c
c      read (ninp,5) commnt
c      read (ninp,*) tnklv0, itnklv
c
c      READ IN CRITERIA CHECKING FLAGS AND PEAKING FACTORS
c
c      read (ninp,5) commnt
c      read (ninp,*) (ichkc(ic), ic=1,ncrit)
c      read (ninp,*) (pkfac(ic), ic=1,ncrit)
c      write (nout,120) (ic, ichkc(ic), pkfac(ic), ic=1,ncrit)
c
c      READ IN TIME AT WHICH CRITERIA CHECKING BEGINS.
c
c      read (ninp,5) commnt
c      read (ninp,*) tcrmax
c      write (nout,130) tcrmax
c
c      CONVERT SRS UNITS TO SI FOR CALCULATIONS
c
c      if (lunits.eq.2) then
c          ppl0 = convp*ppl0
c          ptb0 = convp*ptb0
c          qfin0 = convf*qfin0
c          qgin0 = convf*qgin0
c          tnklv0 = convm*tnklv0
c      end if
c
c      CHECK THAT THE TRANSIENT POINTERS ARE CORRECT
c
c      if (ippl.le.0 .or. ippl.gt.nspln) then
c          write (nout,110) ippl, nspln
c          istop = 1
c      end if
c
c      if (ialpl.le.0 .or. ialpl.gt.nspln) then
c          write (nout,110) ialpl, nspln
c          istop = 1
c      end if
c
c      if (itfpl.le.0 .or. itfpl.gt.nspln) then
c          write (nout,110) itfpl, nspln
c          istop = 1
c      end if
c
c      if (itgpl.le.0 .or. itgpl.gt.nspln) then
c          write (nout,110) itgpl, nspln
c          istop = 1
c      end if
c
c      if (ixapl.le.0 .or. ixapl.gt.nspln) then
c          write (nout,110) ixapl, nspln
c          istop = 1
c      end if
```

```
c
  if (iptb.le.0 .or. iptb.gt.nspln) then
    write (nout,110) iptb, nspln
    istop = 1
  end if
c
  if (ialtb.le.0 .or. ialtb.gt.nspln) then
    write (nout,110) ialtb, nspln
    istop = 1
  end if
c
  if (itftb.le.0 .or. itftb.gt.nspln) then
    write (nout,110) itftb, nspln
    istop = 1
  end if
c
  if (itgtb.le.0 .or. itgtb.gt.nspln) then
    write (nout,110) itgtb, nspln
    istop = 1
  end if
c
  if (ixatb.le.0 .or. ixatb.gt.nspln) then
    write (nout,110) ixatb, nspln
    istop = 1
  end if
c
  if (itnklv.le.0 .or. itnklv.gt.nspln) then
    write (nout,110) itnklv, nspln
    istop = 1
  end if
c
  if ((ibond.eq.2 .or. ibond.eq.4) .and.
    & (iqfin.le.0 .or. iqfin.gt.nspln)) then
    write (nout,110) iqfin, nspln
    istop = 1
  else if ((ibond.eq.3 .or. ibond.eq.4) .and.
    & (iqgin.le.0 .or. iqgin.gt.nspln)) then
    write (nout,110) iqgin, nspln
    istop = 1
  end if
c
c  WARNING MESSAGE FORMAT
c
5  format (a)
110 format (' << warning >> inbond encountered a transient array',
    & ' pointer of ',i3,/, ' pointer values must be > 0 ',
    & ' and < ',i3,/)
c
120 format (/' criteria checking flags and peaking factors',/
    & ' criteria checking flag peaking factor',/
    & ' 1x,41(' _ '),/,5(4x,i2,12x,i1,10x,q12.5,/))
c
130 format (/' Time at which criteria checking begins = ',
    & f5.1, ' sec'/)
c
  return
end
```

INDPWR

```
subroutine indpwr (ninp,nout,ncynl,mnrrp,nrp,nrmax,nr,na,
    & pfrct,rphi,nrgt,nfst,nlast,nrgtm,
    & expose,iwtdry,istop)
c-----
c  PROCESS WET OR MODERATED TANK DECAY POWER RADIAL SHAPE INPUT
```

```

c          ASSUMPTIONS:
c          1. ONLY ONE AZIMUTHAL DISTRIBUTION FOR ALL SHAPES
c          2. FORM OF ALL RADIAL SHAPES IDENTICAL
c-----
c
c          ARGUMENTS:
c I  ninp  - READ FILE UNIT NUMBER
c I  ncyl  - NUMBER OF CYLINDERS
c I  mnrp  - MAX NUMBER OF POWER DATA POINTS IN ANY CYLINDER CORE,
c           OR NUMBER OF POWER POLYNOMIAL COEFFICIENTS IN CYLINDER
c I  nrp   - NUMBER OF DATA POINTS OR -1*NUMBER OF POLYNOMIAL COEFF
c           FOR RADIAL SHAPE FUNCTION IN CYLINDER CORE
c I  nrmax - MAX NUMBER OF RADIAL NODES IN ANY CYLINDER
c I  nr    - NUMBER OF RADIAL NODES IN CYLINDER
c O  istop - 0, OK; >0, TERMINATE PROBLEM AFTER PROCESSING INPUT
c O  pfrc  - ASSEMBLY REGION POWER FRACTION FOR DECAY POWER DATA
c O  rphi  - CYLINDER CORE RADIAL POWER BY POINT AND CYLINDER,
c           OR BY POLYNOMIAL COEFFICIENT AND CYLINDER, FOR DECAY
c           POWER DATA
c I  nreg  - NUMBER OF POWER FRACTION REGIONS IN ASSEMBLY
c I  nfrst - FIRST NODE IN CORE REGION OF CYLINDER
c I  nlst  - LAST NODE IN CORE REGION OF CYLINDER
c I  nrgtm - POWER FRACTION REGION NUMBER BY NODE AND CYLINDER
c I  expose - EXPOSURE DATUM FOR CORRELATION INDEPENDENT VARIABLE
c B  iwtdry - 1, AT-POWER DATA; 2, WET TANK; 3, DRY TANK -- ON INPUT
c           0, NORMAL RETURN; 100, COPY AT-POWER;
c           200, COPY WET          -- ON OUTPUT
c
c          NOTE THAT rphi AND pfrc ARE BEING USED AS DUMMY ARRAYS HERE.
c          THEIR "CORRECT" IDENTITIES ARE CONTROLLED BY THE CALL FROM INPOWR.
c
c          *****
c
c          implicit real (a-h,o-z), integer (i-n)
c          parameter (zero=0.0, one=1.0, pfbig=1.0e+10,
c                    tmin=0.9999, tmax=1.0001)
c
c          dimension pfrc(30), rphi(mnrp,ncyl), nrgtm(nrmax,ncyl)
c          dimension nr(ncyl), nfrst(ncyl),
c          &          nrp(ncyl), nlst(ncyl)
c          character*80 commnt
c
c          LOCAL ARRAYS
c
c          pfcore - COEFFICIENTS FOR POWER FRACTION POLYNOMIAL IN EXPOSURE
c                  FOR CORE REGION IN CYLINDER
c          pfinnr - COEFFICIENTS FOR POWER FRACTION POLYNOMIAL IN EXPOSURE
c                  FOR INNER CLAD REGION IN CYLINDER
c          pfoutr - COEFFICIENTS FOR POWER FRACTION POLYNOMIAL IN EXPOSURE
c                  FOR OUTER CLAD REGION IN CYLINDER
c          ncyl  - TABLE OF CYLINDER NUMBERS BY CYLINDER SET
c          coeff - COEFFICIENTS FOR RADIAL POWER POLYNOMIAL IN EXPOSURE
c                  BY POINT AND CYLINDER SET
c
c          LOCAL ARRAYS
c
c          dimension pfcore(5,20), pfinnr(5,20), pfoutr(5,20),
c          &          ncyl(5), coeff(20,20,5)
c          character*3 threex, blank, iedit1(30), iedit2(30), iedit3(30)
c          character*14 wetnes(3)
c          character*11 region(3)
c
c          data threex/'xxx'/, blank/' '/
c          data wetnes/' at-power ', 'wet tank decay', 'dry tank decay'/

```

```
data region/' core      ', ' inner clad', ' outer clad'/
c
c READ POWER FRACTION DATA, pfrcv VECTOR
c
c pfrcv - POWER FRACTION BY ASSEMBLY REGION,
c ASSEMBLY REGIONS ARE ORDERED BY CYLINDER IN THE SEQUENCE
c OF CORE, INNER CLAD, OUTER CLAD, THE ASSIGNMENT BETWEEN
c NODE AND REGION IS DONE BY THE nrgtm(ir,icyl) ARRAY
c
c read (ninp,*) commnt
c if (iwtdry.ne.1) then
c
c READ SKIP CONTROL
c iskip = 0, JUST USE AT-POWER SHAPE DATA
c       = 1, READ IN AND PROCESS WET/DRY TANK DECAY DATA
c       = 2, USE WET TANK SHAPE FOR DRY TANK
c
c read (ninp,*) iskip
c write (nout,994) wetnes(iwtdry), iskip
c if (iskip.ne.0 .and. iskip.ne.1 .and. iskip.ne.2) then
c   write (nout,87) iskip
c   istop = 1
c   goto 940
c end if
c
c ISKIP POINTS TO AT-POWER SHAPE FOR WET/DRY DECAY POWER
c
c if (iskip.eq.0) goto 940
c
c ISKIP POINTS TO WET DECAY SHAPE FOR DRY DECAY POWER
c
c if (iwtdry.eq.3 .and. iskip.eq.2) goto 950
c end if
c
c PROCESS THE DEFINED INPUT
c
c read (ninp,*) ncylnp, ncoeff
c if (ncylnp.ne.ncyln) then
c   write (nout,912) ncylnp, ncyln
c   istop = 1
c   goto 35
c end if
c
c if (ncoeff.gt.20) then
c   write (nout,921) ncoeff
c   istop = 1
c   goto 35
c end if
c
c do 1 icyln=1,ncyln
c   read (ninp,*) (pfcv(icyln,ncf), pfinnr(icyln,ncf),
c & pfoutn(icyln,ncf), ncf=1,ncoeff)
c 1 continue
c
c write (nout,998) wetnes(iwtdry), ncylnp, ncoeff
c do 996 icyln=1,ncyln
c   write (nout,997) (icyln, ncf, pfcv(icyln,ncf),
c & pfinnr(icyln,ncf),
c & pfoutn(icyln,ncf),
c & ncf=1,ncoeff)
c 996 continue
c
c MAKE REGION ASSIGNMENTS
c
```



```

nreg = 0
do 22 icyln=1,ncyln
c
c   CORE REGION IN CYLINDER
c
      nreg = nreg + 1
      iedit1(nreg) = threex
      iedit2(nreg) = blank
      iedit3(nreg) = blank
c
c   CONSTANT TERM
c
      pfrct(nreg) = pfcore(icyln,1)
      if (expose.gt.zero) then
c
c   DO REST OF EXPOSURE POLYNOMIAL
c
        do 2 ncf=2,ncoeff
          fact = expose**(ncf-1)
          pfrct(nreg) = pfrct(nreg) + pfcore(icyln,ncf)*fact
2        continue
        end if
c
c   CHECK NODAL ASSIGNMENT
c
      nf = nfirst(icyln)
      nl = nlast(icyln)
      if (nf.gt.0) then
        do 4 ir=nf,nl
          if (iwtdry.eq.1) then
            nrgtm(ir,icyln) = nreg
          else if (nrgtm(ir,icyln).ne.nreg) then
            write (nout,908) ir, icyln, region(1),
              nreg, nrgtm(ir,icyln)
4            istop = 1
          end if
        continue
4      end if
c
c   INNER CLAD REGION IN CYLINDER
c
      nreg = nreg + 1
      iedit1(nreg) = blank
      iedit2(nreg) = threex
      iedit3(nreg) = blank
c
c   CONSTANT TERM
c
      pfrct(nreg) = pfinnr(icyln,1)
      if (expose.gt.zero) then
c
c   DO REST OF EXPOSURE POLYNOMIAL
c
        do 6 ncf=2,ncoeff
          fact = expose**(ncf-1)
          pfrct(nreg) = pfrct(nreg) + pfinnr(icyln,ncf)*fact
6        continue
        end if
c
c   CHECK NODAL ASSIGNMENT
c
      nri = nr(icyln)
      if (nri.gt.0 .and. nf.gt.1) then
        nfm = nf - 1

```

```

      do 8 ir=1,nfm
        if (iwtdry.eq.1) then
          nrgtm(ir,icyln) = nreg
        else if (nrgtm(ir,icyln).ne.nreg) then
          write (nout,908) ir, icyln, region(2),
            nreg, nrgtm(ir,icyln)
        end if
        istop = 1
      end if
8      continue
    end if
c
c    OUTER CLAD REGION IN CYLINDER
c
      nreg = nreg + 1
      iedit1(nreg) = blank
      iedit2(nreg) = blank
      iedit3(nreg) = threex
c
c    CONSTANT TERM
c
      pfrct(nreg) = pfoutr(icyln,1)
      if (expose.gt.zero) then
c
c    DO REST OF EXPOSURE POLYNOMIAL
c
        do 10 ncf=2,ncoeff
          fact = expose**(ncf-1)
          pfrct(nreg) = pfrct(nreg) + pfoutr(icyln,ncf)*fact
10        continue
        end if
c
c    CHECK NODAL ASSIGNMENT
c
      if (nri.gt.0 .and. nl.lt.nri) then
        nlp = nl + 1
        do 12 ir=nlp,nri
          if (iwtdry.eq.1) then
            nrgtm(ir,icyln) = nreg
          else if (nrgtm(ir,icyln).ne.nreg) then
            write (nout,908) ir, icyln, region(3),
              nreg, nrgtm(ir,icyln)
          end if
          istop = 1
        end if
12      continue
    end if
c
22    continue
c
    if (iwtdry.eq.1) then
      nregt = nreg
    else if (nreg.ne.nregt) then
      write (nout,911) nreg, nregt
      istop = 1
    end if
c
c    CHECK IF ANY POWER FRACTIONS ARE IN 1.0-X FORM.
c    FLAG IS PFRCT>E+10.  ASSUMES ONLY ONE OTHER NONZERO
c    PFRCT WILL BE PRESENT, AND SO SETS VALUE TO 1.0 MINUS IT.
c
c    LOOP OVER ALL REGIONS LOOKING FOR VERY LARGE PFRCT
c
    do 230 nrg=1,nreg
c
c    FOUND VERY LARGE pfrct

```

```
c          if (pfrct(nrg).lt.pfbig) goto 230
c
c      LOOP OVER ALL OTHER REGIONS LOOKING FOR NONZERO PFRCT
c
c          do 225 ireg=1,nreg
c              if (ireg.eq.nrg) goto 225
c              if (pfrct(ireg).eq.zero) goto 225
c
c      FOUND NONZERO PFRCT, SET VERY LARGE PFRCT TO
c      1.0 MINUS IT, AND EXIT
c
c          pfrct(nrg) = one - pfrct(ireg)
c          goto 235
225      continue
230      continue
235      continue
c
c      EDIT OUT RESULTING POWER FRACTIONS
c
c      write (nout,23) wetnes(iwtdry), expose
c      do 25 nrg=1,nreg
c          write (nout,24) nrg, pfrct(nrg), iedit1(nrg),
c          iedit2(nrg), iedit3(nrg)
25      continue
c
c      WRITE OUT NODAL POWER FRACTION ASSIGNMENTS (NORMALLY OFF)
c
c      write (nout,26) wetnes(iwtdry)
c      do 29 icyln=1,ncyln
c          nri = nr(icyln)
c          do 28 ir=1,nri
c              write (nout,27) icyln, ir, nrgtm(ir,icyln)
c28      continue
c29      continue
c
c      CHECK THAT PFRCT SUM TO 1.0, NORMALIZE IF NOT
c
c      ptot = zero
c      do 32 i=1,nreg
c          ptot = ptot + pfrct(i)
32      continue
c      if (ptot.lt.tmin .or. ptot.gt.tmax) then
c          ptot = one/ptot
c          write (nout,33) ptot
c          do 34 i=1,18
c              pfrct(i) = ptot*pfrct(i)
34      continue
c      end if
c
c      READ RADIAL SHAPE DATA, GENERATE rphi ARRAY
c
c      read (ninp,*) commnt
c      read (ninp,*) nset, nrpa, ncoeff
c
c      if (nrpa.le.0) then
c          nrps = 1
c          nrpm = ncoeff
c          ntest = -ncoeff
c          write (nout,41) wetnes(iwtdry), nset, ncoeff
c      else
c          nrps = nrpa
c          nrpm = nrpa
c          ntest = nrpa
```

```
        write (nout,40) wetnes(iwtdry), nset, nrpa, ncoeff
    end if
c
    read (ninp,*) (ncyl(i), i=1,ncyln)
    read (ninp,*) (((coeff(nc,np,ns), nc=1,ncoeff),
        '      np=1,nrps), ns=1,nset)
c
    write (nout,42) (i, ncyl(i), i=1,ncyln)
    write (nout,44) (((ns, np, nc, coeff(nc,np,ns), nc=1,ncoeff),
        '      np=1,nrps), ns=1,nset)
c
c  ERROR CHECKING
c
    if (nset.gt.5) then
        write (nout,913) nset
        istop = 1
        goto 85
    end if
c
    if (nrps.gt.20) then
        write (nout,914) nrps
        istop = 1
        goto 85
    end if
c
    if (nrpa.gt.0 .and. nrps.gt.mnrp) then
        write (nout,712) nrps, mnrp
        istop = 1
        goto 85
    end if
c
    if (nrpa.le.0 .and. ncoeff.gt.mnrp) then
        write (nout,712) ncoeff, mnrp
        istop = 1
        goto 85
    end if
c
    if (ncoeff.gt.20) then
        write (nout,915) ncoeff
        istop = 1
        goto 85
    end if
c
c  LOOP OVER CYLINDERS AND SET UP RADIAL DATA SETS
c
    do 70 icyln=1,ncyln
c
c  ERROR CHECK
c
        if (iwtdry.eq.1) then
            nrp(icyln) = ntest
        else
            nrp2 = abs(nrp(icyln))
            if (nrpm.ne.nrp2) then
                write (nout,916) wetnes(iwtdry), nrpm, nrp2
                istop = 1
                goto 85
            end if
        end if
    end if
c
    iset = ncyl(icyln)
c
c  LOOP OVER COEFFICIENTS IN CYLINDER CORE, LOAD CONSTANTS
c
```

```
        if (nrpa.le.0) then
c
            do 45 nc=1,ncoeff
                rphi(nc,icyln) = coeff(nc,1,iset)
45          continue
c
            else
c
                do 60 np=1,nrps
                    rphi(np,icyln) = coeff(1,np,iset)
                    if (expose.eq.zero) goto 60
c
c          DO REST OF EXPOSURE POLYNOMIAL
c
                do 50 nc=2,ncoeff
                    fact = expose**(nc-1)
                    rphi(np,icyln) = rphi(np,icyln) +
                        coeff(nc,np,iset)*fact
50          continue
60          continue
            end if
c
70          continue
c
c          EDIT OUT POWER DATA
c
85          write (nout,130) wetnes(iwtdry), expose
c
            write (nout,150)
            do 170 icyln=1,ncyln
                do 160 np=1,nrpm
                    write (nout,155) icyln, np, rphi(np,icyln)
160          continue
170          continue
c
c          RETURN HAVING PROCESSED RADIAL DECAY SHAPE DATA
c
            iwtdry = 0
            return
c
c          RETURN TO LOAD AT-POWER SHAPE INTO DECAY SHAPE
c
940         continue
            iwtdry = 100
            return
c
c          RETURN TO LOAD WET SHAPE INTO DRY SHAPE
c
950         continue
            iwtdry = 200
            return
c
c          WRITE FORMATS
c
23          format ('0',a,' power fraction assignments in assembly:',
&                ' exposure = ',g12.5,/, ' -reg- -power',
&                ' fract- ---core--- --in clad- -out clad- ')
c
24          format (' ',i3,4x,g12.5,3(6x,a,3x))
c
26          format ('0',a,' power fraction region assignments by node',/,
&                ' --cyln-- --radial node-- --pf region-- ')
c
27          format (' ',2x,i3,11x,i3,15x,i3)
```

```
c
33  format ('0>>>warning--power fractions required normalization',
&        ' multiplier of ',g12.5,/)
c
40  format (///,1x,18('*'),
&        'pointwise radial ',a,' shape data',18('*'),/,
&        ' number of cylinder sets in radial shape data  = ',i3,/,
&        ' number of data points in each cylinder core   = ',i3,/,
&        ' number of coefficients in exposure polynomial = ',i3,/)
c
41  format (///,1x,18('*'),
&        'polynomial radial ',a,' shape data',18('*'),/,
&        ' number of cylinder sets in radial shape data  = ',i3,/,
&        ' number of coefficients in shape polynomial    = ',i3,/)
c
42  format (' radial shape data for cylinder ',i2,' is in set # ',i2)
c
44  format ('0  --cyl set--',3x,'--point--',3x,'--coeff no.--',3x,
&        '--coefficient--',/, (8x,i2,11x,i2,12x,i2,11x,g12.5))
c
87  format ('0>>>warning--indpwr encountered control flag for',
&        ' wet tank decay data ',i3,' .ne. 0, 1, or 2',/,
&        ' >>>need to correct iskip',/)
c
130 format ('levaluated ',a,' power shape data for ',
&        'flowtran-tf: exposure ',g11.4,/)
c
150 format ('0--cyln--',3x,'--point--',3x,'--radial power density--')
c
155 format (' ',3x,i2,9x,i2,12x,g12.5)
c
711 format ('0>>>warning--indpwr in reading radial shape data ',
&        'encountered cylinder ',i3,' >',i3,' max from geometry',
&        ' input',/, ' >>>need to correct this input or geometry',
&        ' data.',/)
c
712 format ('0>>>warning--indpwr in reading radial shape data ',
&        'encountered ',i3,' data points or polynomial coeff > ',
&        i3,/, ' >>>need to correct record or array dimension',
&        ' definition.',/)
c
908 format ('0>>>warning--indpwr finds inconsistent region',
&        ' assignment ',/, ' >>>for node ',i3,' in cylinder ',
&        i3,a,/, ' >>>decay shape region ',i3,
&        ' should be same as at-power region ',i3,/)
c
911 format ('0>>>warning--indpwr counts ',i3,' power fraction',
&        ' regions',/, ' >>>does not agree with ',i3,' for',
&        ' at-power data.',/, ' >>>change data so decay and',
&        ' at-power data are consistent.',/)
c
912 format ('0>>>warning--indpwr in reading power fraction data',
&        ' encountered ',i3,' cylinders .ne.',i3,' from',
&        ' geometry input',/, ' >>>need to correct this input',
&        ' or geometry data.',/)
c
913 format ('0>>>warning--indpwr in reading radial shape data ',
&        'encountered ',i3,' sets > 5.',/, ' >>>need to correct',
&        ' record or increase array dimension.',/)
c
914 format ('0>>>warning--indpwr in reading radial shape data ',
&        'encountered ',i3,' points > 20.',/, ' >>>need to',
&        ' correct record or increase array dimension.',/)
c
```

```

915 format ('0>>>warning--indpwr in reading radial shape data ',
& 'encountered ',i3,' coefficients > 20.',/, ' >>>need',
& ' to correct record or increase array dimension.',/)
C
916 format ('0>>>warning--indpwr in reading ',a,' decay shape data',
& ' encountered ',i3,' points .ne. ',i3,' for at-power',
& ' data.',/, ' >>>all shape data must be given for same',
& ' number of points.',/)
C
921 format ('0>>>warning--indpwr in reading power fraction data',
& ' encountered ',i3,' coefficients > 20.',/, ' >>>need',
& ' to correct record or increase array dimension.',/)
C
994 format ('0control flag for ',a,' shape data: ',i2,/,
& ' 0 = use at-power data, no decay data provided',/,
& ' 1 = read in and process decay data ',/,
& ' 2 = use wet tank data for dry tank ',/)
C
997 format (' ',5x,i3,13x,i3,9x,3g15.5)
C
998 format ('0',5x,20(' '),a,' power fraction data',
& 20(' '),/, ' number of cylinders',26x,' = ',i3,/,
& ' number of coefficients in exposure polynomial = ',i3,/,
& ' --cylinder--',3x,'--coeff no.--',3x,
& 13(' '), 'region coefficients',13(' '),/,35x,
& '----core---- -inner clad- -outer clad-')
C
end

```

INITFD

```

subroutine initfd (pt,alpt,xat,rogt,roft,hgt,hft,tgt,tft,
& p,alp,xa,rog,rof,hg,hf,tg,tf,
& pb,alpb,xab,rogb,rofb,hgb,hfb,tgb,tfb,
& ugt,uft,wgx,wfx,ugz,ufz,ugb,ufb,
& citn,cizn,cibn,hfit,hfi,hfib,hgit,hgi,hgib,
& akgit,akgi,akgib,ysit,ysi,ysib,
& act,acz,acb,dzmt,dzm,dzmb,topln,subln,botln,
& ppl,alppl,xapl,tgpl,tfpl,qfin,
& ptb,alptb,xatb,tgtb,tftb,qgin,
& fsplt,factor,xa0,nx,nzp1,nzp2,nzp3,
& nxmax,nchn,nsubc,nzt,nzb,ibond,ilq)
C
C *****
C *
C * SUBROUTINE initfd
C *
C * SUBROUTINE TO INITIALIZE FLUID VARIABLE ARRAYS
C *
C *****
C implicit real (a-h,o-z), integer (i-n)
C parameter (zero=0.0, one=1.0, hundrd=100.0)
C
C MIDDLE SECTION PHYSICAL PARAMETERS
C
dimension p(nzp2,nxmax,nchn), dzm(nzp3),
& alp(nzp2,nxmax,nchn), xa(nzp2,nxmax,nchn),
& rog(nzp2,nxmax,nchn), rof(nzp2,nxmax,nchn),
& hg(nzp2,nxmax,nchn), hf(nzp2,nxmax,nchn),
& tg(nzp2,nxmax,nchn), tf(nzp2,nxmax,nchn),
& ugz(nzp3,nxmax,nchn), ufz(nzp3,nxmax,nchn),
& wgx(nzp2,nxmax,nchn), wfx(nzp2,nxmax,nchn),
& acz(nzp3,nxmax,nchn), ysi(nzp2,nxmax,nchn),
& cizn(nzp3,nxmax,nchn), hfi(nzp2,nxmax,nchn),
& hgi(nzp2,nxmax,nchn), akgi(nzp2,nxmax,nchn)

```

```

C
C      TOP SECTION PHYSICAL PARAMETERS
C
      dimension  pt(nzt),  dzmt(nzt),
      &          alpt(nzt),  xat(nzt),
      &          rogt(nzt),  roft(nzt),
      &          hgt(nzt),  hft(nzt),
      &          tgt(nzt),  tft(nzt),
      &          ugt(nzt),  uft(nzt),
      &          act(nzt),  ysit(nzt),
      &          citn(nzt),  hfit(nzt),
      &          hgit(nzt),  akgit(nzt)
C
C      BOTTOM SECTION PHYSICAL PARAMETERS
C
      dimension  pb(nzb),  dzmb(nzb),
      &          alpb(nzb),  xab(nzb),
      &          rogb(nzb),  rofb(nzb),
      &          hgb(nzb),  hfb(nzb),
      &          tgb(nzb),  tfb(nzb),
      &          ugb(nzb),  ufb(nzb),
      &          acb(nzb),  ysib(nzb),
      &          cibn(nzb),  hfib(nzb),
      &          hgib(nzb),  akgeb(nzb)
C
      dimension  fsplt(nchn), nx(nchn)
C
      parameter (mxnz = 100)
      dimension  drogdp(mxnz), drogdt(mxnz), drgdxa(mxnz),
      &          dhgdp(mxnz), dhgdt(mxnz), dhgdxa(mxnz),
      &          drofdp(mxnz), drofdt(mxnz),
      &          dhfdp(mxnz), dhfdt(mxnz)
C
      dimension  watmw(2)
      data airmw/28.97/, watmw(1)/18.016/, watmw(2)/20.034/
      data epsal/0.001/
      rtmw = one - watmw(1q)/airmw
C
C      BEGIN FLUID INITIALIZATION:
C      CALCULATE PROPERTY DIFFERENTIALS ACROSS ASSEMBLY
C
      asmbly = topln + subln + botln
      delp = ptb - ppl
      delalp = alptb - alppl
      delxa = xatb - xapl
      deltg = tgtb - tgpl
      deltf = tftb - tfpl
C
C      INTERPOLATE BETWEEN PLENUM AND TANK BOTTOM CONDITIONS
C      TO SET LOCAL PRESSURE, GAS TEMPERATURE, FLUID TEMPERATURE,
C      VOID FRACTION, AND AIR MASS FRACTIONS
C
C      TOP SECTION
C
      fract = zero
      do 10 jz=1,nzt
        fract = fract + dzmt(jz)/asmbly
C
      pt(jz) = ppl + fract*delp
      alpt(jz) = alppl + fract*delalp
      xat(jz) = xapl + fract*delxa
      tgt(jz) = tgpl + fract*deltg
      tft(jz) = tfpl + fract*deltf
      ysit(jz) = (one - xat(jz))/(one - rtmw*xat(jz))

```



```

      alpf = one - alpt(jz)
c
      if (alpt(jz) .lt. epsal) then
        wt = alpt(jz)/epsal
        xat(jz) = (one - wt)*xa0 + wt*xat(jz)
        ysit(jz) = (one - xat(jz))/(one - rtmw*xat(jz))
        psi = ysit(jz)*pt(jz)
        call tsat(psi,ilq,ti,dtidps)
        tgt(jz) = (one - wt)*ti + wt*tgt(jz)
      end if
c
      if (alpf .lt. epsal) then
        wt = alpf/epsal
        psi = ysit(jz)*pt(jz)
        call tsat(psi,ilq,ti,dtidps)
        tft(jz) = (one - wt)*ti + wt*tft(jz)
      end if
c
      hfit(jz) = hundrd
      hgit(jz) = hundrd
      akgit(jz) = hundrd
10  continue
c
c  MIDDLE SECTION
c
      fract = topln/asmbly
      do 40 jz=2,nzpl
        fract = fract + dzm(jz)/asmbly
        do 30 ic=1,nchn
          nsub = nx(ic)
          do 20 ix=1,nsub
            p(jz,ix,ic) = ppl + fract*delp
            alp(jz,ix,ic) = alppl + fract*delalp
            xa(jz,ix,ic) = xapl + fract*delxa
            tg(jz,ix,ic) = tgpl + fract*deltg
            tf(jz,ix,ic) = tfpl + fract*deltf
            ysi(jz,ix,ic) = (one - xa(jz,ix,ic))/(one - rtmw*xa(jz,ix,ic))
            alpf = one - alp(jz,ix,ic)
c
            if (alp(jz,ix,ic) .lt. epsal) then
              wt = alp(jz,ix,ic)/epsal
              xa(jz,ix,ic) = (one - wt)*xa0 + wt*xa(jz,ix,ic)
              ysi(jz,ix,ic) = (one - xa(jz,ix,ic))/
                (one - rtmw*xa(jz,ix,ic))
              psi = ysi(jz,ix,ic)*p(jz,ix,ic)
              call tsat(psi,ilq,ti,dtidps)
              tg(jz,ix,ic) = (one - wt)*ti + wt*tg(jz,ix,ic)
            end if
c
            if (alpf .lt. epsal) then
              wt = alpf/epsal
              psi = ysi(jz,ix,ic)*p(jz,ix,ic)
              call tsat(psi,ilq,ti,dtidps)
              tf(jz,ix,ic) = (one - wt)*ti + wt*tf(jz,ix,ic)
            end if
c
            hfi(jz,ix,ic) = hundrd
            hgi(jz,ix,ic) = hundrd
            akgi(jz,ix,ic) = hundrd
20          continue
30        continue
40      continue
c
c  BOTTOM SECTION

```

```
c
fract = (topln + subln)/asmbly
do 50 jz=1,nzb
  pb (jz) = ppl + fract*delp
  alpb(jz) = alppl + fract*delalp
  tgb (jz) = tgpl + fract*deltg
  tfb (jz) = tfpl + fract*deltf
  xab (jz) = xapl + fract*delxa
  ysib(jz) = (one - xab(jz))/(one - rtmw*xab(jz))
  alpf = one - alpb(jz)

c
  if (alpb(jz) .lt. epsal) then
    wt = alpb(jz)/epsal
    xab(jz) = (one - wt)*xa0 + wt*xab(jz)
    ysib(jz) = (one - xab(jz))/(one - rtmw*xab(jz))
    psi = ysib(jz)*pb(jz)
    call tsat(psi,ilq,ti,dtidps)
    tgb(jz) = (one - wt)*ti + wt*tgb(jz)
  end if

c
  if (alf .lt. epsal) then
    wt = alpf/epsal
    psi = ysib(jz)*pb(jz)
    call tsat(psi,ilq,ti,dtidps)
    tfb(jz) = (one - wt)*ti + wt*tfb(jz)
  end if

c
  hfib (jz) = hundrd
  hgib (jz) = hundrd
  akqib(jz) = hundrd

c
  fract = fract + dzmb(jz)/asmbly
50 continue

c
c  USE EQUATION OF STATE TO SET DENSITY AND ENTHALPY
c
c  TOP SECTION:
c
  call state (pt,tgt,tft,xat,factor,ilq,
&            1,nzt,nzt,1,1,1,1,
&            rogt,drogdp,drogdt,drqdx,
&            hgt, dhgdp, dhgdt,dhgdx,
&            roft,drofdp,drofdt,
&            hft, dhfdp, dhfdt)

c
c  MIDDLE SECTION:
c
  do 90 ic=1,nchn
    nsub=nx(ic)
    do 80 ix=1,nsub
      call state (p,tg,tf,xa,factor,ilq,
&                2,nzp1,nzp2,nxmax,nchn,ix,ic,
&                rog,drogdp,drogdt,drqdx,
&                hg, dhgdp, dhgdt,dhgdx,
&                rof,drofdp,drofdt,
&                hf, dhfdp, dhfdt)
80    continue
90    continue

c
c  BOTTOM SECTION:
c
  call state (pb,tgb,tfb,xab,factor,ilq,
&            1,nzb,nzb,1,1,1,1,
&            rogb,drogdp,drogdt,drqdx,
```

```

      hgb, dhgdp, dhgdt, dhgdx,
      rofb, drofdp, drofdt,
      hfb, dhfdp, dhfdt)
c
c   SET PROPERTIES IN FICTICIOUS CELLS AT TOP
c   AND BOTTOM OF MIDDLE SECTION
c
      do 120 ic=1,nchn
        nsub = nx(ic)
        do 110 ix=1,nsub
          p(1,ix,ic) = pt(nzt)
          alp(1,ix,ic) = alpt(nzt)
          xa(1,ix,ic) = xat(nzt)
          tg(1,ix,ic) = tgt(nzt)
          tf(1,ix,ic) = tft(nzt)
          rog(1,ix,ic) = rogt(nzt)
          rof(1,ix,ic) = roft(nzt)
          hg(1,ix,ic) = hgt(nzt)
          hf(1,ix,ic) = hft(nzt)
c
          p(nzp2,ix,ic) = pb(1)
          alp(nzp2,ix,ic) = alpb(1)
          xa(nzp2,ix,ic) = xab(1)
          tg(nzp2,ix,ic) = tgb(1)
          tf(nzp2,ix,ic) = tfb(1)
          rog(nzp2,ix,ic) = rogb(1)
          rof(nzp2,ix,ic) = rofb(1)
          hg(nzp2,ix,ic) = hgb(1)
          hf(nzp2,ix,ic) = hfb(1)
110      continue
120      continue
c
c   SET AZIMUTHAL VELOCITIES TO ZERO
c
      ncell = nzp2*nxmax*nchn
      call clear (wgx,ncell)
      call clear (wfx,ncell)
c
c   ESTIMATE AXIAL VELOCITIES FROM INLET FLOW RATES
c
c   TOP SECTION:
c
      call clear (ugt,nzt)
      call clear (uft,nzt)
      do 130 jz=1,nzt
        agas = alpt(jz)*act(jz)
        afld = act(jz) - agas
c
        if (agas.gt.zero) then
          ugt(jz) = qgin/agas
        else
          ugt(jz) = qfin/afld
        end if
c
        if (afld.gt.zero) then
          uft(jz) = qfin/afld
        else
          uft(jz) = qgin/agas
        end if
c
        citn(jz) = hundrd
c
130      continue
c
```

```
c      MIDDLE SECTION:
c
c      isubl = 0
c      do 170 ic=1,nchn
c          nsub = nx(ic)
c          qg0 = fsplt(ic)*qgin
c          qf0 = fsplt(ic)*qfin
c
c      LOOP OVER AXIAL LEVELS
c
c          do 160 jz=2,nzp2
c              atot = zero
c              agas = zero
c              do 140 ix=1,nsub
c                  atot = atot + acz(jz,ix,ic)
c                  agas = agas + alp(jz,ix,ic)*acz(jz,ix,ic)
140          continue
c              aflld = atot - agas
c
c              ug0 = zero
c              uf0 = zero
c
c              if (agas.gt.zero) then
c                  ug0 = qg0/agas
c              else
c                  ug0 = qf0/aflld
c              end if
c
c              if (aflld.gt.zero) then
c                  uf0 = qf0/aflld
c              else
c                  uf0 = qg0/agas
c              end if
c
c      LOOP OVER AZIMUTHAL POSITIONS
c
c          do 150 ix=1,nsub
c              ugz(jz,ix,ic) = ug0
c              ufz(jz,ix,ic) = uf0
c              cizn(jz,ix,ic) = hundrd
c
c          continue
150      continue
160      continue
c          isubl = isubl + nsub
170  continue
c
c      BOTTOM SECTION:
c
c      call clear (ugb,nzb)
c      call clear (ufb,nzb)
c      do 180 jz=1,nzb
c          agas = alpb(jz)*acb(jz)
c          aflld = acb(jz) - agas
c
c          if (agas.gt.zero) then
c              ugb(jz) = qgin/agas
c          else
c              ugb(jz) = qfin/aflld
c          end if
c
c          if (aflld.gt.zero) then
c              ufb(jz) = qfin/aflld
c          else
c              ufb(jz) = qgin/agas
```

```

      end if
c
      cibn(jz) = hundrd
c
180  continue
c
c      SET VELOCITIES AT FICTICIOUS INTERFACES BETWEEN TOP AND
c      MIDDLE SECTIONS AND BETWEEN MIDDLE AND BOTTOM SECTIONS
c
      do 200 ic=1,nchn
        nsub = nx(ic)
        do 190 ix=1,nsub
          ugz(1,ix,ic) = ugt(nzt)
          ufz(1,ix,ic) = uft(nzt)
          ugz(nzp3,ix,ic) = ugb(1)
          ufz(nzp3,ix,ic) = ufb(1)
190      continue
200  continue
c
      return
      end

```

INITL

```

      subroutine initl
c
c      *****
c      *
c      * SUBROUTINE initl
c      *
c      * SUBROUTINE TO INITIALIZE THE CALCULATIONS TO CONDITIONS
c      * AT PROBLEM STARTING TIME
c      *
c      *****
c
      implicit real (a-h,o-z), integer (i-n)
      parameter (zero=0.0, half=0.5, fifty=50.0)
      common /iounit/ ninp, nout, ndmp, ntmp, nrsti, nrsto
c
      include 'params.inc'
      include 'points.inc'
c
      CLEAR THE DEPOSITED POWER ARRAY
c
      call clear(a(lpows),nrmax*na*nz*ncyln)
c
      INITIALIZE FLUID AND SOLID VARIABLES
c
      if (abs(istart).eq.0) then
c
c      INITIALIZE SOLID VARIABLES
c
          call initdsd (a(lts),a(ltsurf),a(lqwf),a(lqwg),
            &          a(ldqfdw),a(ldqgdw),a(lhspl),a(lqonb),
            &          tsolid,tsrfac,ia(lnr),ia(lmat),a(lwt),
            &          nsurf,nrmax,na,nz,ncyln)
c
c      OBTAIN FLUID DYNAMICS BOUNDARY CONDITIONS FOR TOP
c      AND BOTTOM OF ASSEMBLY AT TIME ZERO
c
          delt = fifty*abs(cidamp)
          tsec = zero
          tmid = zero
          call bound (a(lxtp),a(lytp),a(lztp),ia(lntp),ia(lintp),
            &          ia(litype),nspln,ntpmax,ntptot,tsec,
            &          ppl,alppl,tgpl,tfpl,xapl,rogpl,rofpl,hgpl,hfpl,

```

```

        ptb, alptb, tgtb, tftb, xatb, rogtb, roftb, hgtb, hftb,
        ppl0, alppl0, tgpl0, tfpl0, xapl0,
        ptb0, alptb0, tgtb0, tftb0, xatb0,
        qfin, qgin, qfin0, qgin0,
        ippl, ialpl, itgpl, itfpl, ixapl,
        iptb, ialtb, itgtb, itftb, ixatb,
        iqfin, iqgin, factor, ilq)

```

C
C
C

SETUP FLUID VARIABLES FROM INPUT FILE INITIAL CONDITIONS

```

        call initfd (a(lpt), a(lalpt), a(lxat), a(lrogt), a(lroft),
        a(lhgt), a(lhft), a(ltgt), a(ltft), a(lp), a(lalp),
        a(lxa), a(lrog), a(lrof), a(lhg), a(lhf), a(ltg),
        a(ltf), a(lpb), a(lalpb), a(lxab), a(lrogb), a(lrofb),
        a(lhgb), a(lhfb), a(ltgb), a(ltfb), a(lugt), a(luft),
        a(lwgx), a(lwfx), a(lugz), a(lufz), a(lugb), a(lufb),
        a(lcitn), a(lcizn), a(lcibn), a(lhfit), a(lhfi),
        a(lhfib), a(lhgit), a(lhgi), a(lhgib), a(lakgit),
        a(lakgi), a(lakgib), a(lysit), a(lysi), a(lysib),
        a(lact), a(lacz), a(lacb), a(ldzmt), a(ldzm),
        a(ldzmb), topln, subln, botln, ppl, alppl, xapl, tgpl,
        tfpl, qfin, ptb, alptb, xatb, tgtb, tftb, qgin,
        a(lfspit), factor, xa0, ia(lnx), nzpl, nzp2,
        nzp3, nxmax, nchn, nsubc, nzt, nzb, lbond, ilq)

```

C
C
C

SET OLD TIME (n) VALUES OF VARIABLES FOR FIRST TIME STEP

```

        call reset (a(lts), a(ltsurf), a(ltsn), a(ltsrfn),
        a(lp), a(lalp), a(lxa), a(lrog), a(lrof), a(lhg),
        a(lhf), a(ltg), a(ltf), a(lpn), a(lalpn), a(lxan),
        a(lrogn), a(lrofn), a(lhgn), a(lhfn), a(ltgn), a(ltfn),
        a(lpt), a(lalpt), a(lxat), a(lrogt), a(lroft), a(lhgt),
        a(lhft), a(ltgt), a(ltft), a(lptn), a(lalptn),
        a(lxatn), a(lrogt), a(lroftn), a(lhgtn), a(lhftn),
        a(ltgt), a(ltftn), a(lpb), a(lalpb), a(lxab),
        a(lrogb), a(lrofb), a(lhgb), a(lhfb), a(ltgb),
        a(ltfb), a(lpbn), a(lalpbn), a(lxabn), a(lrogbn),
        a(lrofbn), a(lhgbn), a(lhfbn), a(ltgbn), a(ltfnbn),
        ppl, xapl, rogpl, rofpl, hgpl, hfpl, tgpl, tfpl,
        ppln, xapln, rogpln, rofpln, hgpln, hfpln, tgpln, tfpln,
        ptb, xatb, rogtb, roftb, hgtb, hftb, tgtb, tftb,
        ptbn, xatbn, rogtbn, roftbn, hgtbn, hftbn, tgtbn, tftbn,
        alppl, alppln, alptb, alptbn, nzp2, nxmax, nchn, nzt,
        nzb, nrmax, na, nz, ncyl, nsurf)

```

C
C

else

C
C
C

SETUP FLUID AND SOLID VARIABLES FROM DATA IN RESTART FILE

```

        call restrt (a(lts), a(ltsurf), a(ltsn), a(ltsrfn),
        a(lqwf), a(lqwg), a(ldqfdw), a(ldqqdw), a(lpt), a(lalpt),
        a(lxat), a(lrogt), a(lroft), a(lhgt), a(lhft), a(ltgt),
        a(ltft), a(lptn), a(lalptn), a(lxatn), a(lrogt),
        a(lroftn), a(lhgtn), a(lhftn), a(ltgt), a(ltftn), a(lp),
        a(lalp), a(lxa), a(lrog), a(lrof), a(lhg), a(lhf), a(ltg),
        a(ltf), a(lpn), a(lalpn), a(lxan), a(lrogn), a(lrofn),
        a(lhgn), a(lhfn), a(ltgn), a(ltfn), a(lpb), a(lalpb),
        a(lxab), a(lrogb), a(lrofb), a(lhgb), a(lhfb), a(ltgb),
        a(ltfb), a(lpbn), a(lalpbn), a(lxabn), a(lrogbn),
        a(lrofbn), a(lhgbn), a(lhfbn), a(ltgbn), a(ltfnbn),
        a(lugt), a(luft), a(lwgx), a(lwfx), a(lugz), a(lufz),
        a(lugb), a(lufb), a(lcitn), a(lcizn), a(lcixn), a(lcibn),
        a(lhfit), a(lhfi), a(lhfib), a(lhgit), a(lhgi), a(lhgib),
        a(lakgit), a(lakgi), a(lakgib), a(lgit), a(lgi), a(lgib),

```

```

      a(leit),a(lei),a(leib),a(lysit),a(lysi),a(lysib),
      a(lhspl),a(lqonb),ia(lnx),ia(lnr),tsec0)
c
      if (abs(istart).eq.1) then
         tsec = tsec0
      else if (abs(istart).eq.2) then
         tsec = zero
      else
         tsec = tcrmax
      end if
c
      if (tsec.eq.zero) then
         tmid = zero
      else
         tmid = tsec - half*delt
      end if
      if (tmid.lt. zero) then
         tmid = zero
      end if
end if

c
c      INITIALIZE NORMALIZED POWER SHAPE FUNCTIONS
c
c      NORMALIZE AT POWER SHAPES
c
      call pnorm (a(lbigm),a(lfrdim),a(lfazmm),a(lrphi),
c
c      a(lpfrct),a(ldiam),mnrp,ia(lnrp),
c      ia(lnrgtm),na,ncyln,ia(lnr),nz,nrmax,nrmxp,nreg,
c      ia(lnfrst),ia(lnlast),nout)
c
c      NORMALIZE MODERATED TANK POWER SHAPES
c
      call pnorm (a(lbigmw),a(lfrdim),a(lfazmm),a(lrphdw),
c
c      a(lpfrdw),a(ldiam),mnrp,ia(lnrp),
c      ia(lnrgtm),na,ncyln,ia(lnr),nz,nrmax,nrmxp,nreg,
c      ia(lnfrst),ia(lnlast),nout)
c
c      NORMALIZE DRY TANK POWER SHAPES
c
      call pnorm (a(lbigmd),a(lfrdim),a(lfazmm),a(lrphdd),
c
c      a(lpfrdd),a(ldiam),mnrp,ia(lnrp),
c      ia(lnrgtm),na,ncyln,ia(lnr),nz,nrmax,nrmxp,nreg,
c      ia(lnfrst),ia(lnlast),nout)
c
c      DETERMINE TIME = ZERO NORMALIZATION PARAMETERS FOR POWER
c      DISTRIBUTION IN METAL.
c
      time = zero
      call axialp (a(laxial),a(laxal0),itimex,itime,a(ltimet),time,
c
c      a(lrdz),nz,ia(liaxlp),ia(lntp),ia(lintp),ia(litype),
c      a(lxtp),a(lytp),a(lztp),ntpmax,ntptot,nspln,nout,
c      izht,izhb)
c
      init = 1
      call pdist (a(lpows),sumdry,tnklev,a(laxial),a(laxal0),deldry,
c
c      delmod,a(ldz+1),hactiv,izht,izhb,gap,asypwr,time,
c      a(lbigm),a(lbigmw),a(lbigmd),a(lxtp),a(lytp),
c      a(lztp),ia(lntp),ia(lintp),ia(litype),ifissn,
c      itnklv,tnklv0,imodh,idryh,iconh,iexp,init,na,ncyln,
c      ia(lnr),nz,nrmax,ntpmax,ntptot,nspln,nout)
c
c      RE-INITIALIZE POWER DISTRIBUTION IN METAL IF STARTING TIME
c      GREATER THEN ZERO.
c

```

```

      if (tmid .gt. zero) then
        call axialp (a(laxial),a(laxal0),itimex,itime,a(ltimet),tmid,
          &          a(lrdz),nz,ia(liaxlp),ia(lntp),ia(lintp),
          &          ia(litype),a(lxtp),a(lytp),a(lztp),ntpmax,ntptot,
          &          nspln,nout,izht,izhb)
      c
      init = 0
      call pdist (a(lpows),sumdry,tnklew,a(laxial),a(laxal0),deldry,
        &          delmod,a(ldz+1),hactiv,izht,izhb,gap,asypwr,tmid,
        &          a(lbigm),a(lbigmw),a(lbigmd),a(lxtp),a(lytp),
        &          a(lztp),ia(lntp),ia(lintp),ia(litype),ifissn,
        &          itnklv,tnklv0,imodh,idryh,iconh,iexp,init,na,ncyln,
        &          ia(lnr),nz,nrmax,ntpmax,ntptot,nspln,nout)
      end if
      c
      PRINT THE SOLID STARTING CONDITIONS,
      NOTE THAT HEAT FLUXES ARE NOT KNOWN
      c
      call prtslid (a(lts),a(ltsurf),a(lqwf),a(lqwg),tsec,ia(lnr),
        &          nrmax,na,nz,ncyln,nsurf)
      c
      PRINT THE FLUID STARTING CONDITIONS
      c
      call prtflid (a(lpt),a(lalpt),a(lxat),a(lrogt),a(lroft),
        &          a(lhgt),a(lhft),a(ltgt),a(ltft),a(lvolt),
        &          a(lp),a(lalp),a(lxa),a(lrog),a(lrof),
        &          a(lhg),a(lhf),a(ltg),a(ltf),a(lvolc),
        &          a(lpb),a(lalpb),a(lxab),a(lrogb),a(lrofb),
        &          a(lhgb),a(lhfb),a(ltgb),a(ltfb),a(lvolb),
        &          a(lalptn),a(lrogt),a(lroftn),a(lalpn),a(lrogn),
        &          a(lrofn),a(lalpb),a(lrogb),a(lrofb),
        &          a(lugt),a(luft),a(lwgx),a(lwfx),a(lugz),a(lufz),
        &          a(lugb),a(lufb),a(lact),a(lacx),a(lacz),a(lacb),
        &          a(lysit),a(lysi),a(lysib),a(lgit),a(lgi),a(lgib),
        &          a(leit),a(lei),a(leib),a(lgw),
        &          ppl,alppl,tgpl,tfpl,xapl,rogpl,rofpl,hgpl,hfpl,
        &          ptb,alptb,tgtb,tftb,xatb,rogtb,roftb,hgtb,hftb,
        &          alppln,rogpln,rofpln,ppln,tgpln,xapl,alptbn,
        &          rogtbn,roftbn,volpl,voltb,tsec,delt,vminz,vminx,
        &          ia(licc),ia('nx'),nzpl,nzp2,nzp3,nxmax,nchn,nzt,
        &          nzb,zero,0,0,0,iunits,iprint,ilq)
      c
      PRINT THE POWER DISTRIBUTION STARTING CONDITIONS
      c
      call prtpow (a(laxial),a(laxal0),deldry,delmod,hactiv,gap,
        &          a(lpows),asypwr,tsec,a(lxtp),a(lytp),a(lztp),
        &          ia(lntp),ia(lintp),ia(litype),ifissn,itnklv,
        &          tnklv0,imodh,idryh,iconh,iexp,na,ncyln,ia(lnr),nz,
        &          nrmax,ntpma. ntptot,nspln,nout,izht,izhb)
      c
      IF A DATA DUMP FOR PLOTTING WILL BE CREATED, ALSO
      INCLUDE THE STARTING DATA IN THE PLOT DUMP FILE
      c
      if (dtpdmp.lt.runsec) then
        call dmpplt (a(lts),a(ltsurf),a(lqwf),a(lqwg),a(lpt),
          &          a(lalpt),a(lxat),a(lrogt),a(lroft),a(lhgt),
          &          a(lhft),a(ltgt),a(ltft),a(lp),a(lalp),a(lxa),
          &          a(lrog),a(lrof),a(lhg),a(lhf),a(ltg),a(ltf),
          &          a(lpb),a(lalpb),a(lxab),a(lrogb),a(lrofb),
          &          a(lhgb),a(lhfb),a(ltgb),a(ltfb),a(lugt),a(luft),
          &          a(lwgx),a(lwfx),a(lugz),a(lufz),a(lugb),a(lufb),
          &          ppl,alppl,tgpl,tfpl,xapl,rogpl,rofpl,hgpl,hfpl,
          &          ptb,alptb,tgtb,tftb,xatb,rogtb,roftb,hgtb,hftb,
          &          tsec,ia(lnx),ia(lnr),nzpl,nzp2,nzp3,nxmax,nchn,

```



```

      &          nsubc,nzt,nzb,nrmax,na,nz,ncyl,n,nsurf)
    end if
  c
    return
  end

```

INITSD

```

      subroutine initSD (ts,tsurf,qwf,qwg,dqfdw,dqgdw,hspl,qonb,
      &          tsolid,tsrfac,nr,mat,wt,nsurf,nrmax,na,
      &          nz,ncyl,n)
  c
  c *****
  c *
  c * SUBROUTINE initSD
  c *
  c * SURROUTINE TO SET INITIAL SOLID AND SURFACE TEMPERATURES
  c *
  c *****
  c
    implicit real(a-h,o-z), integer(i-n)
    common /iounit/ ninp, nout, ndmp, ntmp, nrsti, nrsto
    character*80 commnt
  c
    dimension ts(nrmax,na,nz,ncyl,n), wt(ncyl,n),
      &          mat(nrmax,nz,ncyl,n), nr(ncyl,n)
  c
    dimension tsurf(nsurf,na,nz), hspl(nsurf,na,nz),
      &          qwf(nsurf,na,nz), qwg(nsurf,na,nz),
      &          dqfdw(nsurf,na,nz), dqgdw(nsurf,na,nz),
      &          qonb(nsurf,na,nz)
  c
    INITIALIZE SURFACE HEAT FLUXES, DERIVATIVES, ONB HEAT FLUX,
    AND SINGLE-PHASE HEAT TRANSFER COEFFICIENT ARRAYS
  c
    nst = nsurf*na*nz
    call clear ( qwf,nst)
    call clear ( qwg,nst)
    call clear (dqfdw,nst)
    call clear (dqgdw,nst)
    call clear ( hspl,nst)
    call clear ( qonb,nst)
  c
    INITIALIZE SOLID NODE TEMPERATURES
  c
    do 20 icyl=n,ncyl,n
      nri = nr(icyl,n)
      do 10 ia=1,na
        do 10 ir=1,nri
          do 10 iz=1,nz
            ts(ir,ia,iz,icyl,n) = tsolid
          continue
        continue
      continue
    continue
  c
    INITIALIZE SOLID SURFACE TEMPERATURES
  c
    do 30 ia=1,na
      do 30 isurf=1,nsurf
        do 30 iz=1,nz
          tsurf(isurf,ia,iz) = tsrfac
        continue
      continue
    continue
  c
    return
  end

```

INNER

```

subroutine inner (dp,axm1,axm2,azm1,azm2,rhs,sz,sx,dpt,atml,rhst,
&               st,dpb,abm1,rhsb,sb,t,dpm,icc,cmesh,nx,nxmax,
&               nzm,nzpl,nzp2,nzt,nzb,nchn,nlarg,epsin,errin,
&               pref,initmx,initct,ischem,irebal,ncmr,ierr)

C *****
C *
C *  subroutine inner
C *
C *  ITERATIVE SCHEME TO SOLVE THE PRESSURE PROBLEM
C *
C *  ARGUMENTS:
C *      dp = NEW PRESSURE INCREMENT (FOR THIS NEWTON ITERATION)
C *      axm1 = TRIDIAGONAL PORTION OF AXIAL PRESSURE COEFFICIENT
C *             MATRIX
C *      axm2 = REMAINDER OF AXIAL PRESSURE COEFFICIENT MATRIX
C *      azm1 = TRIDIAGONAL PORTION OF AZIMUTHAL PRESSURE
C *             COEFFICIENT MATRIX
C *      azm2 = REMAINDER OF AZIMUTHAL PRESSURE COEFFICIENT MATRIX
C *      rhs = RIGHT HAND SIDE OF THE PRESSURE EQUATIONS
C *      sz = STORAGE ARRAY FOR AXIAL SOLUTION VECTORS
C *      sx = STORAGE ARRAY FOR AZIMUTHAL SOLUTION VECTORS
C *      dpt = NEW PRESSURE INCREMENT FOR TOP SECTION
C *      atml = AXIAL PRESSURE COEFFICIENT MATRIX FOR TOP
C *             SECTION OF THE ASSEMBLY
C *      rhst = RIGHT HAND SIDE OF PRESSURE EQUATIONS IN
C *             TOP SECTION
C *      st = STORAGE ARRAY FOR AXIAL SOLUTION VECTORS IN
C *            TOP SECTION
C *      dpb = NEW PRESSURE INCREMENT FOR BOTTOM SECTION
C *      abm1 = AXIAL PRESSURE COEFFICIENT MATRIX FOR BOTTOM
C *             SECTION OF THE ASSEMBLY
C *      rhsb = RIGHT HAND SIDE OF PRESSURE EQUATIONS IN
C *             BOTTOM SECTION
C *      sb = STORAGE ARRAY FOR AXIAL SOLUTION VECTORS IN
C *            BOTTOM SECTION
C *      t = TEMPORARY STORAGE ARRAY (VIRTUAL rhs)
C *      dpm = TEMPORARY STORAGE ARRAY (UPDATED PRESSURE)
C *      icc = INDICATOR FOR CHANNEL COUPLING
C *      cmesh = COARSE MESH MATRIX ELEMENTS
C *      nx = NUMBER OF AZIMUTHAL CELLS IN EACH FLOW CHANNEL
C *      nxmax = MAXIMUM NUMBER OF AZIMUTHAL CELLS IN THE GRID
C *      nzm = NUMBER OF AXIAL MESH CELLS IN MIDDLE SECTION
C *      nzpl = NUMBER OF AXIAL CELLS IN MIDDLE SECTION + 1
C *             (POINTS TO LAST AXIAL MESH CELL)
C *      nzp = NUMBER OF AXIAL LEVELS INCLUDING FICTICIOUS
C *            BOUNDARY CELLS
C *      nzt = NUMBER OF AXIAL CELLS IN TOP SECTION
C *      nzb = NUMBER OF AXIAL CELLS IN BOTTOM SECTION
C *      nchn = NUMBER OF FLOW CHANNELS
C *      nlarg = ARRAY DIMENSION, LARGER OF EITHER nxmax OR
C *             nzt + nzp2 + nzb
C *      epsin = CONVERGENCE CRITERION
C *      errin = INNER ITERATION ERROR
C *      pref = REFERENCE PRESSURE IN RELATIVE ERROR ESTIMATE
C *      initmx = MAXIMUM NUMBER OF INNER ITERATIONS ALLOWED
C *      initct = ACTUAL NUMBER OF INNER ITERATIONS (COUNT)
C *      ischem = CALCULATION SCHEME OPTION FLAG:
C *                ischem = 1 FOR AXIAL SOLUTION SCHEME
C *                ischem = 2 FOR AZIMUTHAL SOLUTION SCHEME
C *                ischem = 3 FOR ALTERNATING AXIAL AND
C *                        AZIMUTHAL SOLUTION SCHEMES
C *      irebal = COARSE MESH REBALANCE OPTION FLAG:

```

```

C      *      irebal = 0 NO COARSE MESH REBALANCE CALCULATIONS      *
C      *      irebal = 1 COARSE MESH REBALANCE INITIALIZATION      *
C      *      irebal = 2 COARSE MESH REBALANCE ON EVERY PASS      *
C      *      ncmr = NUMBER OF COARSE MESH REBALANCE SWEEPS TO MAKE      *
C      *      ierr = FLAG TO INDICATE CONVERGENCE FAILURE      *
C      *
C      *      NOTE:
C      *      THE FOLLOWING CONVENTION IS USED TO STORE AXIAL COUPLING      *
C      *      TERMS BETWEEN THE FIRST CELLS IN THE MIDDLE SECTION AND THE      *
C      *      LAST CELL IN THE TOP SECTION AND COUPLING TERMS BETWEEN THE      *
C      *      LAST CELLS IN THE MIDDLE SECTION AND THE FIRST CELL IN THE      *
C      *      BOTTOM SECTION
C      *      TOP -> MIDDLE COEFFICIENTS ARE IN      axm2(ix, 1,ic,1)
C      *      MIDDLE -> TOP COEFFICIENTS ARE IN      axm2(ix, 2,ic,1)
C      *      MIDDLE -> BOTTOM COEFFICIENTS ARE IN axm2(ix,nzp1,ic,2)
C      *      BOTTOM -> MIDDLE COEFFICIENTS ARE IN axm2(ix,nzp2,ic,2)
C      *
C      *****
C      implicit real (a-h,o-z), integer (i-n)
C      logical first, firstb, firstc
C      parameter (zero=0.0)
C      dimension axm1(nxmax,nzp2,nchn,3), azm1(nzp2,nxmax,nchn,3),
C      &          axm2(nxmax,nzp2,nchn,2), azm2(nzp2,nxmax,nchn,2),
C      &          sx(2,nxmax,nzp2,nchn), sz(2,nzp2,nxmax,nchn),
C      &          dp(nzp2,nxmax,nchn), rhs(nzp2,nxmax,nchn),
C      &          lcc(2,nxmax,nchn), nx(nchn),
C      &          dpt(nzt), st(2,nzt), atml(nzt,3), rhst(nzt),
C      &          dpb(nzb), sb(2,nzb), abml(nzb,3), rhsb(nzb),
C      &          cmesh(nlarg,nchn,3), dpm(nlarg), t(nlarg)
C      dimension iswtch(2)
C      data iswtch/+1,-1/
C
C      INITIALIZE ITERATION COUNTER AND FLAGS
C
C      first = .true.
C      firstt = .true.
C      firstb = .true.
C      firstc = .true.
C      initct = 0
C      ierr = 0
C
C      CLEAR ARRAYS
C
C      ncell = nzp2*nxmax*nchn
C      call clear (dpt(1),nzt)
C      call clear (dp(1,1,1),ncell)
C      call clear (dpb(1),nzb)
C
C      SELECT ITERATION SCHEME AND REBALANCE OPTION
C
C      if (ischem.eq.2) then
C          ipick = 2
C      else
C          ipick = 1
C      end if
C      icorsm = irebal
C
C      BEGIN ITERATIVE SOLUTION
C
C      do 800 iter=1,initmx
C          errin = zero
C          initct = initct + 1
C
C          if (icorsm.ne.0) then

```

```

c
c   PERFORM COARSE MESH CALCULATIONS TO OBTAIN AN
c   INITIAL ESTIMATE FOR THE PRESSURE SOLUTION
c
c       do 270 icmr=1,ncmr
c
c   LOOP OVER ALL FLOW CHANNELS
c
c       do 260 ic=1,nchn
c         nsub = nx(ic)
c         if (ipick.eq.1) then
c
c   SET UP AXIAL REBALANCE ARRAYS AND PERFORM
c   COARSE MESH CALCULATION
c
c         if (firstc) then
c
c   ON FIRST PASS, SET UP INVARIANT ELEMENTS OF COARSE MESH ARRAYS:
c   INSERT TOP SECTION COEFFICIENTS INTO THE COARSE MESH ARRAY
c
c           do 110 iz=1,nzt
c             cmesh(iz,ic,1) = atm1(iz,3)
c             cmesh(iz,ic,2) = atm1(iz,1)
c             cmesh(iz,ic,3) = atm1(iz,2)
110          continue
c
c   INSERT MIDDLE SECTION COEFFICIENTS INTO THE COARSE MESH ARRAY
c
c           do 120 izm=2,nzp1
c             iz = nzt + izm - 1
c             cmesh(iz,ic,1) = zero
c             cmesh(iz,ic,2) = zero
c             cmesh(iz,ic,3) = zero
c             do 120 ix=1,nsub
c               cmesh(iz,ic,1) = cmesh(iz,ic,1)
c               &             + axm2(ix,izm,ic,1)
c               cmesh(iz,ic,2) = cmesh(iz,ic,2)
c               &             + axm1(ix,izm,ic,1)
c               &             + axm1(ix,izm,ic,2)
c               &             + axm1(ix,izm,ic,3)
c               cmesh(iz,ic,3) = cmesh(iz,ic,3)
c               &             + axm2(ix,izm,ic,2)
c             &
120          continue
c
c   INSERT BOTTOM SECTION COEFFICIENTS INTO THE COARSE MESH ARRAY
c
c           nztm = nzt + nzm
c           do 130 izb=1,nzb
c             iz = nztm + izb
c             cmesh(iz,ic,1) = abm1(izb,3)
c             cmesh(iz,ic,2) = abm1(izb,1)
c             cmesh(iz,ic,3) = abm1(izb,2)
130          continue
c
c   INCLUDE TOP TO MIDDLE AND BOTTOM TO MIDDLE COUPLING TERMS
c
c           nzbl = nztm + 1
c           cmesh(nzt,ic,3) = zero
c           cmesh(nzbl,ic,1) = zero
c           do 140 ix=1,nsub
c             cmesh(nzt,ic,3) = cmesh(nzt,ic,3)
c             &             + axm2(ix,1,ic,1)
c             cmesh(nzbl,ic,1) = cmesh(nzbl,ic,1)
c             &             + axm2(ix,nzp2,ic,2)

```

```

140          continue
          end if
c
c      PLACE TOP SECTION RIGHT HAND SIDE INTO ARRAY t
c
          do 150 iz=1,nzt
              t(iz) = rhst(iz)
150          continue
c
c      PLACE MIDDLE SECTION RIGHT HAND SIDE TERMS INTO ARRAY t
c
          do 160 izm=2,nzpl
              izml = izm - 1
              izpl = izm + 1
              iz = nzt + izml
              t(iz) = zero
              do 160 ix=1,nsub
                  ixm = icc(1,ix,ic)
                  ixp = icc(2,ix,ic)
                  t(iz) = t(iz) + rhs(izm,ix,ic)
                  &      - axm1(ix,izm,ic,1)*dp(izm,ix,ic)
                  &      - axm1(ix,izm,ic,2)*dp(izm,ixm,ic)
                  &      - axm1(ix,izm,ic,3)*dp(izm,ixp,ic)
                  &      - axm2(ix,izm,ic,1)*dp(izml,ix,ic)
                  &      - axm2(ix,izm,ic,2)*dp(izpl,ix,ic)
160          continue
c
c      PLACE BOTTOM SECTION RIGHT HAND SIDE INTO ARRAY t
c
          nztm = nzt + nzm
          do 170 izb=1,nzb
              iz = nztm + izb
              t(iz) = rhsb(izb)
170          continue
c
c      ADD COUPLING TERMS LINKING THE FIRST CELLS IN MIDDLE SECTIONS
c      TO LAST CELL IN TOP SECTION AND LAST CELLS IN MIDDLE SECTIONS
c      TO FIRST CELL IN BOTTOM SECTION
c
          nzq = nztm + 1
          do 180 ik=1,nchn
              ns = nx(ik)
              do 180 ix=1,ns
                  t(nzt) = t(nzt) - axm2(ix,1,ik,1)*dp(2,ix,ik)
                  t(nzq) = t(nzq) - axm2(ix,nzp2,ik,2)*dp(nzpl,ix,ik)
180          continue
c
c      SOLVE FOR AXIAL REBALANCE CORRECTION FACTORS AND FOR THE
c      PRESSURES IN THE TOP AND BOTTOM SECTIONS IN ARRAY dpm
c
          ntot = nzt + nzm + nzb
          call tridag (firstc,1,ntot,ntot,cmesh(1,ic,1),
              &      cmesh(1,ic,2),cmesh(1,ic,3),
              &      t,dpm,sx(1,1,1,ic))
c
c      SET PRESSURES IN TOP SECTION TO NEW VALUES
c
          do 190 iz=1,nzt
              dpt(iz) = dpm(iz)
190          continue
c
c      ADJUST PRESSURE SOLUTION IN MIDDLE SECTION BY REBALANCE FACTORS
c
          do 200 izm=2,nzpl

```

```

        iz = nzt + izm - 1
        do 200 ix=1,nsub
            dp(izm,ix,ic) = dp(izm,ix,ic) + dpm(iz)
200      continue
c
c      SET PRESSURES IN BOTTOM SECTION TO NEW VALUES
c
        nztm = nzt + nzm
        do 210 izb=1,nzb
            iz = nztm + izb
            dpb(izb) = dpm(iz)
210      continue
c
        else if (ipick.eq.2) then
c
c      SET UP AZIMUTHAL REBALANCE ARRAYS AND PERFORM COARSE
c      MESH CALCULATION IN THE MIDDLE SECTION
c
        if (firstc) then
c
c      ON FIRST PASS, SET UP INVARIANT ELEMENTS OF COARSE MESH ARRAYS
c
        do 220 ix=1,nsub
            cmesh(ix,ic,1) = zero
            cmesh(ix,ic,2) = zero
            cmesh(ix,ic,3) = zero
        do 220 iz=2,nzpl
            cmesh(ix,ic,1) = cmesh(ix,ic,1)
            + azm2(iz,ix,ic,1)
            cmesh(ix,ic,2) = cmesh(ix,ic,2)
            + azm1(iz,ix,ic,1)
            + azm1(iz,ix,ic,2)
            + azm1(iz,ix,ic,3)
            cmesh(ix,ic,3) = cmesh(ix,ic,3)
            + azm2(iz,ix,ic,2)
220      continue
        end if
c
c      FORM TEMPORARY RIGHT HAND SIDE ARRAY t
c
        do 230 ix=1,nsub
            ixm = icc(1,ix,ic)
            ixp = icc(2,ix,ic)
            t(ix) = zero
        do 230 iz=2,nzpl
            izm = iz - 1
            izp = iz + 1
            t(ix) = t(ix) + rhs(iz,ix,ic)
            - azm1(iz,ix,ic,1)*dp(iz,ix,ic)
            - azm1(iz,ix,ic,2)*dp(izp,ix,ic)
            - azm1(iz,ix,ic,3)*dp(izm,ix,ic)
            - azm2(iz,ix,ic,1)*dp(iz,ixm,ic)
            - azm2(iz,ix,ic,2)*dp(iz,ixp,ic)
230      continue
c
c      ADD AXIAL COUPLING TERMS LINKING TO THE LAST CELL IN THE
c      TOP SECTION AND TO THE FIRST CELL IN THE BOTTOM SECTION
c
        do 240 ix=1,nsub
            t(ix) = t(ix) - axm2(ix,2,ic,1)*dpt(nzt)
            - axm2(ix,nzpl,ic,2)*dpb(1)
240      continue
c
c      SOLVE FOR AZIMUTHAL REBALANCE CORRECTION FACTORS dpm

```

```
c
      call tridag (firstc,1,nsup,nsup,cmesh(1,ic,1),
&                cmesh(1,ic,2),cmesh(1,ic,3),
&                t,dpm,sz(1,1,1,ic))
c
c      ADJUST PRESSURE SOLUTION BY REBALANCE FACTORS
c
      do 250 ix=1,nsup
      do 250 iz=2,nzpl
        dp(iz,ix,ic) = dp(iz,ix,ic) + dpm(ix)
250      continue
      end if
260      continue
      firstc = .false.
270      continue
    end if
c
c      SOLVE FOR PRESSURE INCREMENTS IN THE TOP SECTION:
c      PLACE RIGHT HAND SIDE OF THE EQUATION SET IN TEMPORARY ARRAY t
c
      do 310 iz=1,nzt
        t(iz) = rhst(iz)
310      continue
c
c      INCLUDE AXIAL COUPLING TERMS LINKING THE LAST TOP
c      CELL TO THE FIRST CELLS IN THE MIDDLE SECTION
c
      do 330 ic=1,nchn
        nsup = nx(ic)
        do 320 ix=1,nsup
          t(nzt) = t(nzt) - axm2(ix,1,ic,1)*dp(2,ix,ic)
320        continue
330      continue
c
c      SOLVE TRIDIAGONAL AXIAL EQUATIONS FOR NEW PRESSURE INCREMENTS
c
      call tridag (firstt,1,nzt,nzt,atml(1,3),atml(1,1),
&                atml(1,2),t,dpm,st(1,1))
c
c      UPDATE THE PRESSURE SOLUTION AND FIND MAXIMUM ERROR
c
      do 340 iz=1,nzt
        errin = max(errin,abs(dpt(iz)-dpm(iz)))
        dpt(iz) = dpm(iz)
340      continue
c
c      SOLVE FOR PRESSURE INCREMENTS IN THE MIDDLE SECTION:
c      LOOP OVER ALL FLOW CHANNELS
c
      do 600 ic=1,nchn
        nsup = nx(ic)
        if (ipick.eq.1) then
c
c      SOLVE AXIAL TRIDIAGONAL PRESSURE PROBLEMS
c      LOOP OVER AZIMUTHAL POSITIONS IN MIDDLE SECTION
c
          do 430 ix=1,nsup
            ixm = icc(1,ix,ic)
            ixp = icc(2,ix,ic)
c
c      FORM COMPLETE RIGHT HAND SIDE OF THE EQUATION SET IN
c      TEMPORARY ARRAY t BY INCLUDING AZIMUTHAL COUPLING TERMS
c
          do 410 iz=2,nzpl
```

```

        t(iz) = rhs(iz,ix,ic) - axm2(iz,ix,ic,1)*dp(iz,ixm,ic)
        - axm2(iz,ix,ic,2)*dp(iz,ixp,ic)
410      continue
C
C      INCLUDE AXIAL COUPLING TERMS LINKING THE FIRST CELL IN THE MIDDLE
C      SECTION TO THE LAST CELL IN THE TOP SECTION AND THE LAST CELL IN
C      THE MIDDLE SECTION TO THE FIRST CELL IN THE BOTTOM SECTION
C
        t(2) = t(2) - axm2(ix,2,ic,1)*dpt(nzt)
        t(nzpl) = t(nzpl) - axm2(ix,nzpl,ic,2)*dpb(1)
C
C      SOLVE TRIDAIGONAL AXIAL EQUATIONS FOR NEW PRESSURE INCREMENTS
C
        call tridag (first,2,nzpl,nzp2,azm1(1,ix,ic,3),
        4          azm1(1,ix,ic,1),azm1(1,ix,ic,2),
        4          t,dpm,sz(1,1,ix,ic))
C
C      UPDATE THE PRESSURE SOLUTION AND FIND MAXIMUM ERROR
C
        do 420 iz=2,nzpl
            errin = max(errin,abs(dp(iz,ix,ic)-dpm(iz)))
            dp(iz,ix,ic) = dpm(iz)
420      continue
430      continue
C
        else if (ipick.eq.2) then
C
C      SOLVE AZIMUTHAL TRIDIAGONAL PRESSURE PROBLEMS
C      LOOP OVER AXIAL POSITIONS IN MIDDLE SECTION
C
        do 530 iz=2,nzpl
            izm = iz - 1
            izp = iz + 1
C
C      FORM COMPLETE RIGHT HAND SIDE OF THE EQUATION SET IN
C      TEMPORARY ARRAY t BY INCLUDING AXIAL COUPLING TERMS
C
            id = 1
            dpv = zero
C
C      FOR THE FIRST CELLS IN THE MIDDLE SECTION, INCLUDE AXIAL
C      COUPLING TERMS LINKING TO THE LAST CELL IN THE TOP SECTION
C
            if (iz.eq.2) then
                id = 1
                dpv = dpt(nzt)
C
C      FOR THE LAST CELLS IN THE MIDDLE SECTION, INCLUDE AXIAL
C      COUPLING TERMS LINKING TO THE FIRST CELL IN THE BOTTOM SECTION
C
            else if (iz.eq.nzpl) then
                id = 2
                dpv = dpb(1)
            end if
C
        do 510 ix=1,nsub
            t(ix) = rhs(iz,ix,ic) - axm2(ix,iz,ic,1)*dp(izm,ix,ic)
            4          - axm2(ix,iz,ic,2)*dp(izp,ix,ic)
            4          - axm2(ix,iz,ic,id)*dpv
510      continue
C
C      SOLVE TRIDAIGONAL AZIMUTHAL EQUATIONS FOR NEW PRESSURE INCREMENTS
C
        call tridag (first,1,nsub,nsub,axm1(1,iz,ic,3),

```



```

4          axml(1,iz,ic,1),axml(1,iz,ic,2),
4          t,dpm,sx(1,1,iz,ic))
c
c      UPDATE THE PRESSURE SOLUTION AND FIND MAXIMUM ERROR
c
c          do 520 ix=1,nsub
c              errin = max(errin,abs(dp(iz,ix,ic)-dpm(ix)))
c              dp(iz,ix,ic) = dpm(ix)
520      continue
530      continue
c          end if
600      continue
c
c      SOLVE FOR PRESSURE INCREMENTS IN THE BOTTOM SECTION:
c      PLACE RIGHT HAND SIDE OF THE EQUATION SET IN TEMPORARY ARRAY t
c
c          do 710 iz=1,nzb
c              t(iz) = rhsb(iz)
710      continue
c
c      INCLUDE AXIAL COUPLING TERMS LINKING THE FIRST BOTTOM
c      CELL TO THE LAST CELLS IN THE MIDDLE SECTION
c
c          do 730 ic=1,nchn
c              nsub = nx(ic)
c              do 720 ix=1,nsub
c                  t(1) = t(1) - axm2(ix,nzp2,ic,2)*dp(nzp1,ix,ic)
720          continue
730      continue
c
c      SOLVE TRIDIAGONAL AXIAL EQUATIONS FOR NEW PRESSURE INCREMENTS
c
c          call tridag (firstb,1,nzb,nzb,abml(1,3),abml(1,1),
c          4          abml(1,2),t,dpm,sb(1,1))
c
c      UPDATE THE PRESSURE SOLUTION AND FIND MAXIMUM ERROR
c
c          do 740 iz=1,nzb
c              errin = max(errin,abs(dpb(iz)-dpm(iz)))
c              dpb(iz) = dpm(iz)
740      continue
c
c      CHECK FOR CONVERGENCE
c
c          errin = errin/pref
c          if (errin.lt.epsin) return
c
c      RESET FLAGS AND RETURN FOR ANOTHER ITERATION
c
c          first = .false.
c          firstt = .false.
c          firstb = .false.
c          icorsm = irebal/2
c          if (ischem.eq.3) then
c              icorsm = 0
c              ipick = ipick + iswtch(ipick)
c              if (initct.eq.1) first = .true.
c          end if
800      continue
c
c      FAILURE TO CONVERGE WITHIN ITERATION LIMIT
c
c          write (*,900) epsin, initmx, errin
900      format (/, ' inner pressure iteration failed to converge to',

```

```

4      /,' a tolerance of ',1pel2.4,' in ',14,' iterations',
4      /,' maximum error = ',1pel2.4)
      ierr = 1
C
      return
      end

```

INOPTS

```

      subroutine inopts (icmax,ipmax,npdat,nset)
C
C *****
C *
C *   subroutine inopts
C *
C *   SUBROUTINE TO READ INPUT OPTIONS AND PARAMETERS
C *
C *   THE FOLLOWING VARIABLES ARE READ:
C *       ibond = PLENUM BOUNDARY CONDITION FLAG
C *       nchn = NUMBER OF FLOW CHANNELS
C *       ncyl = NUMBER OF METAL CYLINDERS
C *       nrmax = MAXIMUM NUMBER OF RADIAL CELLS IN SOLID MESH
C *       nxmax = MAXIMUM NUMBER OF AZIMUTHAL CELLS IN MESH
C *       nzt = NUMBER OF AXIAL CELLS IN TOP SECTION
C *       nz = NUMBER OF AXIAL CELLS IN MIDDLE SECTION
C *       nzb = NUMBER OF AXIAL CELLS IN BOTTOM SECTION
C *
C *****
C      implicit real (a-h,o-z), integer (i-n)
C      parameter (convp=6.894757e+03, convm=0.02540, convh=5.678263,
4          ten3=1000.0, one=1.0, one80=180.0)
C      parameter (ndmax=20)
C      character*80 commnt
C
C      common /iounit/ ninp, nout, ndmp, ntmp, nrsti, nrsto
C
C      include 'params.inc'
C      include 'points.inc'
C      include 'knobs.inc'
C      dimension npdat(ndmax), nset(ndmax)
C
C      raddeg = acos(-one)/one80
C
C      READ TITLE CARD AND WRITE TO OUTPUT
C
C      read (ninp,10) commnt
C      write (nout,100) commnt
10  format (a)
C
C      INPUT TIME STEP LIMITS AND PRINT TIME INCREMENTS
C
C      read (ninp,10) commnt
C      read (ninp,*)   runsec, dtmin, dtmax, dtpfld, dtpsld,
4          dtpwpr, dtpdmp
C      write (nout,105) runsec, dtmin, dtmax, dtpfld, dtpsld,
4          dtpwpr, dtpdmp
C
C      INPUT BOUNDARY CONDITION, UNITS, RESTART, AND PRINT FLAGS
C
C      read (ninp,10) commnt
C      read (ninp,*)   ibond, iunits, istart, isave, iprint,
4          iexp, icrit, iscrn, iword, istdy,
4          ippu
C      write (nout,110) ibond, iunits, istart, isave, iprint,
4          iexp, icrit, iscrn, iword, istdy

```

```

      6          ippu
c
c      READ IN REFERENCE PRESSURE, COMPRESSIBILITY FACTOR,
c      MINIMUM VELOCITY FOR FULL DONORING, ACCURACY CHECKING
c      TOLERANCE, AND OTHER MISCELLANEOUS MODEL PARAMETERS,
c      FOR SRS INPUT UNITS, CONVERT PRESSURE TO SI UNITS
c
      read (ninp,10) commnt
      read (ninp,*) ilq, pref, factor, vminz, vminx, tol, tolss, nstdy,
      6          tsupw, htdamp, cidamp, xdelt, xturb, xa0
      if (iunits.eq.2) then
          pref = convp*pref
      end if
      write (nout,115) ilq, pref, factor, vminz, vminx, tol, tolss,
      6          nstdy, tsupw, htdamp, cidamp, xdelt, xturb, xa0
c
c      READ IN BOILING CURVE AND INTERFACIAL WALL AND BULK OPTIONS
c
      read (ninp,10) commnt
      read (ninp,*) iboil, ichf, matgas, persat, igami,
      6          igamw
      write (nout,120) iboil, ichf, matgas, persat, igami,
      6          igamw
c
c      READ IN SOLID HEAT CONDUCTION PARAMETERS
c
      read (ninp,10) commnt
      read (ninp,*) isolid, iaxial, wss, ncms, tsolid, tsrfac
      write (nout,125) isolid, iaxial, wss, ncms, tsolid, tsrfac
c
c      INPUT INNER CALCULATION OPTIONS
c
      read (ninp,10) commnt
      read (ninp,*) ischem, irebal, ncmr, epsin, initmx
      write (nout,130) ischem, irebal, ncmr, epsin, initmx
c
      read (ninp,*) epsy, epsf, nitysi
      write (nout,133) epsy, epsf, nitysi
c
      read (ninp,*) epsp, epsalp, epstg, epstf, epsxa, nitmax
      write (nout,135) epsp, epsalp, epstg, epstf, epsxa, nitmax
c
c      INPUT THE NUMBER OF TRANSIENT PROFILES USED
c      AND THE NUMBER OF POINTS IN EACH PROFILE
c
      read (ninp,10) commnt
      read (ninp,*) ndata, mnrp, itime
      ntptot = 0
      ntpmax = 0
      nspln = 0
      do 20 id=1,ndata
          read (ninp,*) npdat(id), nset(id)
          ntpmax = max(npdat(id),ntpmax)
          ntptot = ntptot + npdat(id)*nset(id)
          nspln = nspln + nset(id)
20      continue
      write (nout,140) ndata, nspln, ntptot, mnrp, itime
c
c      READ GEOMETRIC DATA AND WRITE TO OUTPUT
c
      read (ninp,10) commnt
      read (ninp,*) nchn, nxmax, ncyl, na, nrmax, nzt, nz, nzb
      write (nout,145) nchn, nxmax, ncyl, na, nrmax, nzt, nz, nzb
c
```

```

c   READ IN TANK DATA AND WRITE TO OUTPUT
c
  read (ninp,10) commnt
  read (ninp,*)   izht, izhb, gap, tmod0, itmod,
  &             hmod, iradbc, douts, emisi, emiso
  if (iunits.eq.2) then
    gap = convm*gap
    hmod = convh*hmod
    douts = convm*douts
  end if
  write (nout,150) izht, izhb, gap, tmod0, hmod,
  &             iradbc, douts, emisi, emiso
c
c   READ IN POWER ITERATION PARAMETERS AND WRITE TO OUTPUT
c
  read (ninp,10) commnt
  read (ninp,*)   asypwr, maxpi, tolpow, ncrit
  write (nout,155) asypwr, maxpi, tolpow, ncrit
  asypwr = ten3*asypwr
c
c   READ IN SENSITIVITY PARAMETERS
c
  read (ninp,10) commnt
  read (ninp,*)   xcofh, xreh, xcofl, xrel, xkmet, xcvmet,
  &             xhfi, xhgi, xkgi, xphi,
  &             cizfac, cixfac, iribv,
  &             xfric, plnht, cipln, formhs, alphs, alb2, als2,
  &             ala2, expbs, expsa,
  &             delp1, delp2, sigai, sigam, sigfi, sigfm,
  &             dalsub, theta0
  write (nout,160) xcofh, xreh, xcofl, xrel, xkmet, xcvmet,
  &             xhfi, xhgi, xkgi, xphi, cizfac
  write (nout,165) cixfac, iribv,
  &             xfric, plnht, cipln, formhs, alphs, alb2, als2,
  &             ala2, expbs, expsa
  write (nout,170) delp1, delp2, sigai, sigam, sigfi, sigfm,
  &             dalsub, theta0
  theta0 = theta0*raddeg
  if (iunits.eq.2) plnht = plnht*convm
c
c   COMPUTE CONSTANT PARAMETERS
c
  nap1 = na + 1
  nzp1 = nz + 1
  nzp2 = nz + 2
  nzp3 = nz + 3
  icent = ncyln - nchn
  nsurf = ncyln + nchn + 1
  nrmaxp = nrmax + 1
c
c   CHECK THE INPUT DATA VALUES
c
  if (ibond.lt.1 .or. ibond.gt.4) then
    write (*,200) ibond
    istop = 1
  end if
c
  if (ilq.lt.1 .or. ilq.gt.2) then
    write (*,205) ilq
    istop = 1
  end if
c
  if (nchn.lt.1) then
    write (*,210) nchn

```

```

        istop = 1
      else if (nchn.eq.1) then
        ncmr = 1
        nachk = mod(na,4)
      else
        nachk = mod(na,8)
      end if
c
      if (ncyln.lt.1) then
        write (*,220) ncyln
        istop = 1
      end if
c
      if (icent.ne.0 .and. icent.ne.1) then
        write (*,230) nchn, ncyln
        istop = 1
      end if
c
      if (na.ne.1 .and. nachk.ne.0) then
        write (*,240) na
        istop = 1
      end if
c
      if (izht.lt.1 .or. izht.gt.nz) then
        write (*,250) izht, nz
        istop = 1
      end if
c
      if (izhb.lt.izht .or. izhb.gt.nz) then
        write (*,260) izhb, izht, nz
        istop = 1
      end if
c
      if (maxpi.le.0 .or. maxpi.gt.ipmax) then
        write (*,270) maxpi, ipmax
        istop = 1
      end if
c
      if (ncrit.le.0 .or. ncrit.gt.icmax) then
        write (*,280) ncrit, icmax
        istop = 1
      end if
c
      if (dtpdmp.le.runsec .and. (iword.lt.1 .or. iword.gt.2)) then
        write (*,290) iword
        istop = 1
      end if
c
      if (ndata.le.0 .or. ndata.gt.ndmax) then
        write (*,300) ndata, ndmax
        istop = 1
      end if
c
c      WRITE FORMATS
c
100  format (//,a,/)
c
105  format ('  **      time step control parameters  **',//
&      '      total run time = ',g12.5,' seconds',/
&      '      minimum time step = ',g12.5,' seconds',/
&      '      maximum time step = ',g12.5,' seconds',/
&      '      fluid printouts every ',g12.5,' seconds',/
&      '      solid printouts every ',g12.5,' seconds',/
&      '      power printouts every ',g12.5,' seconds',/

```

```

        plotting data dumps every ',g12.5,' seconds',//)
c
110  format (' ** boundary condition, units, restart **',//
        '      boundary condition flag = ',i2,/
        '      units chosen (1=SI, 2=SRS) = ',i2,/
        '      restart option (0=new, 1,2,3=restart) = ',i2,/
        '      create restart file (0=no, 1,2,3=yes) = ',i2,/
        '      restart options: 1 - time = current tsec',/
        '      2 - time = zero ',/
        '      3 - time = tcrmax ',/
        '      Note: negative value creates ascii file',/
        '      print option (1=short, 2=long) = ',i2,/
        '      experimental rig (0=no, 1=yes) = ',i2,/
        '      criteria printing (0=no, 1=yes) = ',i2,/
        '      screen print (0=no, 1=yes, 2=short) = ',i2,/
        '      Vax or Cray (1=Vax, 2=Cray) = ',i2,/
        '      steady-state solution (0=no, 1,2,3=yes) = ',i2,/
        '      update plenum pressure (ibond=2 or 4) = ',i2,/
        '      options: 0 - no ',/
        '      1 - update based on liq mom ',/
        '      2 - update if alpl1 < abs(alphas)',//)
c
115  format (' ** constant factors for calculations **',//
        '      liquid identifier (1=H2O 2=D2O) = ',i1,/
        '      reference pressure = ',g12.5,' Pa',/
        '      liquid compressibility factor = ',g12.5,/
        '      min vel for full donoring: z-dir = ',g12.5,'m/s',/
        '      min vel for full donoring: x-dir = ',g12.5,'m/s',/
        '      accuracy check tolerance = ',g12.5,/
        '      steady-state tolerance = ',g12.5,/
        '      max iterations for steady-state = ',i4,/
        '      subcooling adjustment factor = ',g12.5,' C',/
        '      wall heat flux damping factor = ',g12.5,/
        '      interfacial drag damping factor = ',g12.5,/
        '      steady-state solid delt multiplier = ',g12.5,/
        '      turbulent exchange multiplier = ',g12.5,/
        '      Xa reference value = ',f5.3 ,//)
c
120  format (' ** additional options (boiling curve) **',//
        '      nucleate boiling (1=Mikic, 2=Chen) = ',i2,/
        '      CHF correlation (1=SRL, 2=Biasi) = ',i2,/
        '      dissolved gas (1=helium, 2=air) = ',i2,/
        '      dissolved gas percent saturation = ',g12.5,/
        '      interface bulk mass transfer (0=off, 1=on) = ',i2,/
        '      interface wall mass transfer (0=off, 1=on) = ',i2,//)
c
125  format (' ** solid heat conduction parameters **',//
        '      solid calcs performed (0=no, 1=yes) = ',i2,/
        '      axial heat conduction (0=no, 1=yes) = ',i2,/
        '      implicit conduction (0.0=no, 1.0=yes) = ',f4.1,/
        '      number of rebalance iterations = ',i3,/
        '      initial solid temperature = ',f8.3,' C',/
        '      initial surface temperature = ',f8.3,' C',//)
c
130  format (' ** inner pressure solution parameters **',//
        '      inner iteration calculation method = ',i3,/
        '      inner iteration rebalance option = ',i3,/
        '      number of rebalance iterations = ',i3,/
        '      tolerance on inner iteration = ',g12.5,/
        '      maximum number of inner iterations = ',i4,//)
c
133  format (' ** ysi iteration parameters **',//
        '      tolerance on ysi = ',g12.5,/
        '      tolerance on f(ysi) = ',g12.5,/

```

```

        ' maximum number of ysi iterations = ',i4,/)
c
135 format (' **      newton iteration tolerances      **',//
        '          tolerance on pressure = ',g12.5,/
        '          tolerance on void fraction = ',g12.5,/
        '          tolerance on gas temperature = ',g12.5,/
        '          tolerance on liquid temperature = ',g12.5,/
        '          tolerance on air mass fraction = ',g12.5,/
        '          maximum number of newton iterations = ',i4,/)
c
140 format (' **      spline profile specifications      **',//
        '          number of spline data sets specified = ',i4,/
        '          number of spline profiles used = ',i4,/
        '          total number of points in all profiles = ',i4,/
        '          number of points in radial power shapes = ',i4,/
        '          number of times for axial power shapes = ',i4,/)
c
145 format (' **      geometric input data for problem      **',//
        '          number of flow channels = ',i3,/
        '          maximum number of fluid azimuthal cells = ',i3,/
        '          number of metal cylinders = ',i3,/
        '          fixed number of solid azimuthal cells = ',i3,/
        '          maximum number of radial solid cells = ',i3,/
        '          number of axial cells in top section = ',i3,/
        '          number of axial cells in middle section = ',i3,/
        '          number of axial cells in bottom section = ',i3,/)
c
150 format (' **      active core input data for problem      **',//
        '          first heated cell in active core = ',i3,/
        '          last heated cell in active core = ',i3,/
        '          gap from active core to tank bottom = ',g12.5,' m',/
        '          initial moderator temperature = ',g12.5,' C',/
        '          moderator heat transfer coefficient = ',g12.5,
        '          W/m**2-C',/
        '          radiation b. c. flag (0=off, 1=on) = ',i1,/
        '          diameter of radiating surface = ',g12.5,' m',/
        '          emissivity of inner surface = ',g12.5,/
        '          emissivity of outer surface = ',g12.5,/)
c
155 format (' **      power iteration parameters      **',//
        '          initial assembly power = ',g12.5,' kW',/
        '          maximum number of power iterations = ',i3,/
        '          tolerance on power iteration = ',g12.5,/
        '          number of criteria to check = ',i2,/)
c
160 format (' **      sensitivity parameters      **',//
        '          multipliers for:',/
        '          turbulent heat transfer correlation = ',g12.5,/
        '          turbulent heat transfer Re exponent = ',g12.5,/
        '          annular heat transfer correlation = ',g12.5,/
        '          annular heat transfer Re exponent = ',g12.5,/
        '          metal thermal conductivity = ',g12.5,/
        '          metal heat capacity = ',g12.5,/
        '          interfacial fluid heat transfer = ',g12.5,/
        '          interfacial gas heat transfer = ',g12.5,/
        '          interfacial mass transfer = ',g12.5,/
        '          interfacial enhanced transport = ',g12.5,//
        '          **      momentum parameters      **',//
        '          axial interfacial drag factor = ',g12.5)
c
165 format ('          azimuthal interfacial drag factor = ',g12.5,/
        '          rib void model selection = ',i2 ,/
        '          global wall friction multiplier = ',g12.5,/
        '          plenum height for weir model = ',g12.5,/

```

```

&      '      interfacial drag for weir model = ',g12.5,/
&      '      form drag for weir model = ',g12.5,/
&      'min void fraction for stratification = ',g12.5,/
&      '      bubble-to-slug transition point = ',g12.5,/
&      '      pure slug point = ',g12.5,/
&      '      slug-to-annular transition point = ',g12.5,/
&      '      bubble-slug interpolation exponent = ',g12.5,/
&      '      slug-annular interpolation exponent = ',g12.5,/)
c
170  format ('      **      channel inlet void parameters      **',/)
&      '      start of chn inlet void transition = ',g12.5,/
&      '      end of chn inlet void transition = ',g12.5,/
&      '      sigma - adverse - inner channel = ',g12.5,/
&      '      sigma - adverse - middle channel = ',g12.5,/
&      '      sigma - favorable - inner channel = ',g12.5,/
&      '      sigma - favorable - middle channel = ',g12.5,/
&      '      del alpha for subchannel void tilt = ',g12.5,/
&      '      orientation of subchannel void tilt = ',g12.5,/)
c
c      ERROR MESSAGE FORMATS
c
200  format ('<< fatal error >>  ibond = ',i3,/' plenum boundary',
&      '      condition flag must be => 1 and <= 4',/)
c
205  format ('<< fatal error >>  ilq = ',i3,/' liquid must be',
&      '      specified as 1 (H2O) or 2 (D2O)',/)
c
210  format ('<< fatal error >>  nchn = ',i3,/
&      '      the number of flow channels is < 1',/)
c
220  format ('<< fatal error >>  ncyl = ',i3,/
&      '      the number of metal cylinders is < 1',/)
c
230  format ('<< fatal error >> the geometry is inconsistent',/
&      '      there can not be ',i3,' flow channels with ',i3,
&      '      metal cylinders',/)
c
240  format ('<< fatal error >>  na = ',i4,/' the number of',
&      '      azimuthal cells must be 1 or a multiple of 8',/)
c
250  format ('<< fatal error >> the heated core specification is',
&      '      inconsistent',/, ' the top cell for the heated core',
&      '      is input as ',i3,/, ' the top cell must lie between',
&      '      1 and ',i3,/)
c
260  format ('<< fatal error >> the heated core specification is',
&      '      inconsistent',/, ' the bottom cell for the heated',
&      '      core is input as ',i3,/, ' the bottom cell must lie',
&      '      between ',i3,' and ',i3,/)
c
270  format ('<< fatal error >> number of power iterations = ',i2,/
&      '      must specify 1 =< maxpi <= ',i2,' enter a',/
&      '      new value for maxpi or increase the allowed',
&      '      dimension ipmax in tfmain')
c
280  format ('<< fatal error >> number of criteria = ',i2,/
&      '      must specify 1 =< ncrit <= ',i2,' enter a',/
&      '      new value for ncrit or increase the allowed',
&      '      dimension icmax in tfmain')
c
290  format ('<< fatal error >> Vax or Cray = ',i2,/
&      '      must use 1 for Vax or 2 for Cray to generate',/
&      '      appropriate record length for graphics dump file')
c

```



```

300  format (' << fatal error >> number of spline datasets = ',i2,/
      &      ' must specify 1 =< npmax <= ',i2,' enter a',/
      &      ' new value for ndata or increase the allowed',
      &      ' dimension ndmax in inopts')
c
      return
      end

```

INPOWR

```

      subroutine inpowr (ninp,nout,na,ncyl,nmrp,nrp,nrmax,nr,
      &                  nz,itime,istop,iexp,fazmm,timet,nreg,
      &                  nfirst,nlast,nrgtm,deldry,delmod,
      &                  ifissn,laxlp,imodh,idryh,iconh,
      &                  pfrct,pfrdd,pfrdw,rphi,rphdd,rphdw)
c=====
c      PROCESS POWER INPUT REQUIRED FOR ONE FLOWTRAN CALCULATION
c=====
c
c      ARGUMENTS:
c I ninp      - READ FILE UNIT NUMBER
c I nout      - WRITE FILE UNIT NUMBER
c I na        - NUMBER OF AZIMUTHS
c I ncyl      - NUMBER OF CYLINDERS
c I nmrp      - MAX NUMBER OF POWER DATA POINTS IN ANY CYLINDER CORE,
c              OR NUMBER OF POWER POLYNOMIAL COEFFICIENTS IN CYLINDER
c O nrp       - NUMBER OF DATA POINTS OR -1*NUMBER OF POLYNOMIAL COEFF
c              FOR RADIAL SHAPE FUNCTION IN CYLINDER CORE
c I nrmax     - MAX NUMBER OF RADIAL NODES IN ANY CYLINDER
c I nr        - NUMBER OF RADIAL NODES IN CYLINDER
c I itime     - NO. OF SNAPSHOTS, AXIAL POWER SHAPE
c O istop     - 0, OK; >0, TERMINATE PROBLEM AFTER PROCESSING INPUT
c O pfrct     - ASSEMBLY REGION POWER FRACTION FOR AT-POWER DATA
c O rphi      - CYLINDER CORE RADIAL POWER BY POINT AND CYLINDER,
c              OR BY POLYNOMIAL COEFFICIENT AND CYLINDER, FOR AT-POWER
c              DATA
c O fazmm     - AZIMUTHAL METAL POWER BY AZIMUTH AND CYLINDER
c O timet     - SNAPSHOT TIMES FOR AXIAL POWER DATA
c O nreg      - NUMBER OF POWER FRACTION REGIONS IN ASSEMBLY
c I nfirst    - FIRST NODE IN CORE REGION OF CYLINDER
c I nlast     - LAST NODE IN CORE REGION OF CYLINDER
c O nrgtm     - POWER FRACTION REGION NUMBER BY NODE AND CYLINDER
c O deldry    - DRY TANK FRACTION OF POWER DUE TO DECAY HEAT
c O delmod    - MODERATED TANK FRACTION OF POWER DUE TO DECAY HEAT
c I iexp      - MODE FLAG (0=REACTOR LIMIT, 1=EXPERIMENTAL MOCKUP)
c O pfrdd     - ASSEMBLY REGION DRY DECAY POWER FRACTION
c O pfrdw     - ASSEMBLY REGION WET DECAY POWER FRACTION
c O rphdd     - CYLINDER CORE DRY DECAY RADIAL POWER SHAPE
c O rphdw     - CYLINDER CORE WET DECAY RADIAL POWER SHAPE
c
c      *****
c
c      implicit real (a-h,o-z), integer (i-n)
c      parameter (zero=0.0, one=1.0, maxset=40)
c      character*80 commnt
c
c      dimension pfrct(30), rphi(nmrp,ncyl),
c      &          pfrdd(30), rphdd(nmrp,ncyl),
c      &          pfrdw(30), rphdw(nmrp,ncyl)
c
c      dimension timet(itime), laxlp(itime),
c      &          nfirst(ncyl), nlast(ncyl),
c      &          nr(ncyl), nrp(ncyl)
c
c      dimension nrgtm(nrmax,ncyl), fazmm(na,ncyl)

```

```
C
C   LOCAL ARRAYS:
C   ncyl  - TABLE OF CYLINDER NUMBERS BY CYLINDER SET
C   azmet  - AZIMUTHAL METAL POWER BY AZIMUTH AND CYLINDER SET
C
C   dimension ncyl(5), azmet(32,maxset)
C
C   READ IN ASSEMBLY EXPOSURE FOR POLYNOMIALS
C
C   expose = zero
C   delmod = zero
C   deldry = zero
C   write (nout,999) ninp
C
C   if (iexp.eq.0) then
C       read (ninp,*)   commnt
C       read (ninp,*)   expose, delmod, deldry
C       write (nout,995) expose, delmod, deldry
C   end if
C
C   PROCESS AT-POWER DATA
C
C   iwtdry = 1
C   call indpwr (ninp,nout,ncyl,mnrrp,nrrp,nrmax,nr,na,
C   &           pfrct,rphi,nreg,nfrst,nlast,nrgtm,
C   &           expose,iwtdry,istop)
C
C   PROCESS DECAY HEAT SHAPE DATA, IF ANY
C
C   WET TANK DATA
C
C   iwtdry = 2
C   call indpwr (ninp,nout,ncyl,mnrrp,nrrp,nrmax,nr,na,
C   &           pfrdw,rphdw,nreg,nfrst,nlast,nrgtm,
C   &           expose,iwtdry,istop)
C
C   if (iwtdry.ne.0) then
C
C   SIGNALLED THAT AT-POWER DATA TO BE USED FOR DECAY SHAPE
C
C       do 10 ireg=1,nreg
C           pfrdw(ireg) = pfrct(ireg)
10      continue
C       do 30 icyl=1,ncyl
C           do 20 np=1,mnrrp
C               rphdw(np,icyl) = rphi(np,icyl)
20          continue
30      continue
C   end if
C
C   DRY TANK DATA
C
C   iwtdry = 3
C   call indpwr (ninp,nout,ncyl,mnrrp,nrrp,nrmax,nr,na,
C   &           pfrdd,rphdd,nreg,nfrst,nlast,nrgtm,
C   &           expose,iwtdry,istop)
C
C   if (iwtdry.eq.200) then
C
C   SIGNALLED THAT WET DECAY SHAPE TO BE USED FOR DRY DECAY
C
C       do 40 ireg=1,nreg
C           pfrdd(ireg) = pfrdw(ireg)
40      continue
```

```

        do 60 icyln=1,ncyln
            do 50 np=1,mnrrp
                rphdd(np,icyln) = rphdw(np,icyln)
50          continue
60        continue
c
        else if (iwtdry.ne.0) then
c
c      SIGNALLED THAT AT-POWER DATA TO BE USED FOR DECAY SHAPE
c
            do 70 ireg=1,nreg
                pfrdd(ireg) = pfrct(ireg)
70          continue
c
            do 90 icyln=1,ncyln
                do 80 np=1,mnrrp
                    rphdd(np,icyln) = rphi(np,icyln)
80          continue
90        continue
        end if
c
c      READ AZIMUTHAL SHAPE DATA, GENERATE fazmm ARRAY
c
c      SET UP DEFAULT AZIMUTHAL SHAPES
c
        do 110 icyln=1,ncyln
            do 100 ia=1,na
                fazmm(ia,icyln) = one
100          continue
110        continue
c
        read (ninp,*) commnt
        read (ninp,*) nset, naz, (ncyl(icyln), icyln=1,ncyln)
c
        write (nout,810) nset, naz
        write (nout,812) (icyln, ncyl(icyln), icyln=1,ncyln)
c
c      IF LESS THAN ONE CYLINDER SET SPECIFIED, USE DEFAULT VALUES
c      CHECK THAT LOCAL ARRAY DIMENSION IS NOT TOO SMALL
c
        if (nset.le.0) then
            write (nout,916)
            goto 140
        else if (nset.gt.maxset) then
            write (nout,918) nset
            istop = 1
            return
        end if
c
c      CHECK THAT AZIMUTHAL DIMENSIONS MATCH
c
        if (naz.ne.na) then
            write (nout,920) naz, na
            istop = 1
            return
        end if
c
c      READ AZIMUTHAL SHAPE FACTOR DATA
c
        read (ninp,*) ((azmet(ia,ns), ia=1,naz), ns=1,nset)
        write (nout,816) ((ns, ia, azmet(ia,ns), ia=1,naz), ns=1,nset)
c
c      LOOP OVER CYLINDERS AND STRIP OUT DATA
c
```

```
      do 130 icyln=1,ncyln
        iset = ncyl(icyln)
c
c      LOOP OVER AZIMUTHAL NODES IN CYLINDER CORE
c
        do 120 ia=1,na
          fazmm(ia,icyln) = azmet(ia,iset)
120      continue
130    continue
c
140    write (nout,912)
      do 160 icyln=1,ncyln
        do 150 ia=1,na
          write (nout,914) icyln, ia, fazmm(ia,icyln)
150      continue
160    continue
c
c      READ IN POWER SPLINE POINTERS
c
      read (ninp,*) commnt
      read (ninp,*) ifissn, imodh, idryh, iconh
c
c      READ IN AXIAL POWER SPLINE POINTERS AND CORRESPONDING TIMES
c
      read (ninp,*) commnt
      read (ninp,*) (iaxlp(itsec), timet(itsec), itsec=1,itime)
c
c      WRITE FORMATS
c
810    format (///,5x,20('*'),'azimuthal shape data',20('*'),/,
&          ' number of cylinder sets in azimuthal data = ',i3,/,
&          ' number of azimuths in each cylinder core = ',i3)
c
812    format (' shape data for cylinder ',i2,' is in set # ',i2)
c
816    format ('0  --cyl set--',3x,'--azimu--',3x,'--shape factr--',
&          /(8x,i2,12x,i2,10x,g12.5))
c
912    format ('0--cyln--',3x,'--ia--',3x,'--azimut power density--')
c
914    format (' ',3x,i2,8x,i2,11x,g12.5)
c
916    format ('0>>>note--inpowr azimuthal data flag set such that',
&          ' >>>azimuthal shape will default to flat 1.0',
&          ' everywhere.',/)
c
918    format ('0>>>warning--inpowr in reading azimuthal shape data ',
&          'encountered ',i3,' sets > 5.',/, ' >>>need to correct',
&          ' record or increase array dimension.',/)
c
920    format ('0>>>warning--inpowr in reading azimuthal shape data ',
&          'encountered ',i3,' azimuths .ne. ',i3,' from geometry',
&          ' input',/, ' >>>need to correct this input or geometry',
&          ' data.',/)
c
995    format (' exposure = ',g12.5,/, ' moderated tank fraction of',
&          ' power due to decay heat = ',g12.5,/,7x,'dry tank',
&          ' fraction of power due to decay heat = ',g12.5,/)
c
999    format ('1 input power data as read from unit ',i2,/)
c
      return
      end
```

INPUT

```

      subroutine input (icmax,ipmax)
      c
      c *****
      c *
      c *   subroutine input
      c *
      c *
      c *****
      implicit real (a-h,o-z), integer(i-n)
      parameter (ndmax=20)
      common /lounit/ ninp, nout, ndmp, ntmp, nrsti, nrsto
      c
      include 'params.inc'
      include 'points.inc'
      dimension npdat(ndmax),nset(ndmax)
      c
      c   OBTAIN OPTIONS AND CONTROL PARAMETERS
      c
      call inopts (icmax,ipmax,npdat,nset)
      c
      c   SET POINTERS INTO INTEGER AND REAL ARRAYS
      c
      call point
      c
      c   OBTAIN FLUID GEOMETRY INPUT PARAMETERS
      c
      call geofld (a(labsrx),a(labsrz),a(lacx),a(lacz),a(laratx),
      &             a(laratz),a(laxx),a(lazz),a(lcosx),a(lcosz),
      &             a(ldeffz),a(ldhx),a(ldhz),a(ldxm),a(ldz),
      &             a(ldzm),a(lformx),a(lformz),a(lfldmz),a(lfldcz),
      &             a(lc0bz),a(lc0sz),a(lckbz),a(lcksz),a(lfmltx),
      &             a(lfmltz),a(lfrex),a(lfrez),a(lvolc),a(labsrt),
      &             a(lact),a(larat),a(lazt),a(lcost),a(ldefft),
      &             a(ldht),a(ldzt),a(ldzmt),a(lformt),a(lfldmt),
      &             a(lfldct),a(lc0bt),a(lc0st),a(lckbt),a(lckst),
      &             a(lfmltt),a(lfret),a(lvolt),a(labsrb),a(lacb),
      &             a(laratb),a(lazb),a(lcosb),a(ldeffb),a(ldhb),
      &             a(ldzb),a(ldzmb),a(lformb),a(lfldmb),a(lfldcb),
      &             a(lc0bb),a(lc0sb),a(lckbb),a(lcksb),a(lfmltb),
      &             a(lfreb),a(lvolb),
      &             acpl,volpl,actb,voltb,ia(liaz1),ia(licc),
      &             na,ia(lnazc),ia(lnx),nchn,nxmax,nz,nzpl,nzp2,nzp3,
      &             nzt,nzb,botln,subln,topln,iunits,istop)
      c
      if (istop.ne.0) then
        write (*,*) ' error in subroutine geofld'
        stop
      end if
      c
      c   OBTAIN SOLID GEOMETRY INPUT PARAMETERS
      c
      call geosld (a(ldiam),a(lwt),ia(lmat),a(lrib1),a(lribt),
      &             ia(liorib),ia(lioxid),ia(lnr),ia(lichks),
      &             ncyln,nsurf,nrmax,nrmxp,nz,iunits,istop)
      c
      if (istop.ne.0) then
        write (*,*) ' error in subroutine geosld'
        stop
      end if
      c
      c   SETUP SOLID GEOMETRIC ARRAYS
      c
      call setsld (a(lradc),a(lar),a(ldr),a(lvols),a(lzfacm),da,

```

```

        a(ldiam),a(ldz+1),a(lrdz),hactiv,
        ia(lmat),ia(lloxid),ia(lnfrst),ia(lnlast),
        ia(lnr),nz,na,nrmax,nrmxp,ncyl,izht,izhb,
        icent,iradbc,douts,emisi,emiso,cradi)
c
        if (istop.ne.0) then
            write (*,*) ' error in subroutine setsld'
            stop
        end if
c
c      OBTAIN DATA FOR SPECIFYING THERMAL HYDRAULIC BOUNDARY CONDITIONS
c
        call inbond (pp10,alpp10,tgpl0,tfp10,xap10,
        &             ptb0,alptb0,tgtb0,tftb0,xatb0,
        &             qfin0,qgin0,a(lfsplt),tnklv0,
        &             ippl,ialpl,itgpl,itfpl,ixapl,
        &             iptb,ialtb,itgtb,itftb,ixatb,
        &             iqfin,iqgin,itnklv,tcrmax,
        &             a(lpkfac),ia(lichkc),nchn,nsubc,
        &             nspln,ncrit,ibond,iunits,istop)
c
        if (istop.ne.0) then
            write (*,*) ' error in subroutine inbond'
            stop
        end if
c
c      OBTAIN DATA FOR SPECIFYING POWER DISTRIBUTIONS
c
        call inpowr (ninp,nout,na,ncyl,mnrrp,ia(lnrp),nrmax,ia(lnr),
        &             nz,itime,istop,iexp,a(lfazmm),a(ltimet),nreg,
        &             ia(lnfrst),ia(lnlast),ia(lnrgtm),deldry,delmod,
        &             ifissn,ia(liaxlp),imodh,idryh,iconh,a(lpfrct),
        &             a(lpfrdd),a(lpfrdw),a(lrphl),a(lrphdd),a(lrphdw))
c
        if (istop.ne.0) then
            write (*,*) ' error in subroutine inpowr'
            stop
        end if
c
c      OBTAIN SPLINE PROFILE DATA
c
        call inspln (a(ltimet),a(lwb),a(lwh),a(lwu),a(lwv),a(lxtp),
        &             a(lytp),a(lztp),ia(liaxlp),ia(lintp),ia(litype),
        &             npdat,nset,ia(lntp),itime,ndata,nspln,ntpmax,
        &             ntptot)
c
c      NORMAL RETURN WHEN NO ERROR HAS OCCURRED
c
        return
        end

```

INSPLN

```

        subroutine inspln (timet,wb,wh,wu,wv,xtp,ytp,ztp,iaxlp,intp,
        &             itype,npdat,nset,ntp,itime,ndata,nspln,ntpmax,
        &             ntptot)
c-----
c      Purpose:  This routine reads the transient and spatial input data
c                for FLOWTRAN-TF and then generates the spline fitting
c                coefficients.
c-----
c      Subroutine history
c      - 11/1/92 Updated to incorporate new version of subroutine
c                SPLINE.
c-----

```

```

c
c      Arguments
c
c      NAME      I/O  TYPE      DIM      DESCRIPTION
c      -----
c      timet      I    R*4      itime      Snapshot times of axial power
c                                         shapes
c      wh,wb,wu,wv I    R*4      ntpmax     Intermediate working arrays
c      laxlp      I    I*4      itime      Pointers to axial power shapes
c      itype      I    I*4      nspln      Identifier of type of spline
c                                         = 0 (Natural cubic spline)
c                                         = 1 (First-degree spline)
c      npdat      I    I*4      ndata      Number of points per dataset
c      nset       I    I*4      ndata      Number of splines per dataset
c      itime      I    I*4              Number of snapshots for axial
c                                         power shape
c      ndata      I    I*4              Number of spline datasets
c      nspln      I    I*4              Number of splines
c      ntpmax     I    I*4              Maximum number of points per
c                                         spline
c      ntptot     I    I*4              Total number of data points
c      xtp        O    R*4      ntptot     Abscissa values or knots
c      ytp        O    R*4      (ntpmax,   Ordinate values
c                               nspln)
c      ztp        O    R*4      (ntpmax,   Slopes of first-degree splines
c                               nspln)      or second derivatives of
c                                         natural cubic splines at the
c                                         knots
c      intp       O    I*4      nspln      Pointers to start of spline
c                                         data
c      ntp        O    I*4      nspln      Number of points per spline
c=====
c
c      implicit real (a-h,o-z), integer (i-n)
c      character*80 commnt,label
c      character*8  xvalu
c
c      common /iounit/ ninp, nout, ndmp, ntmp, nrsti, nrsto
c
c      dimension xtp(ntptot), ytp(ntpmax,nspln), ztp(ntpmax,nspln),
c      &          intp(nspln),          itype(nspln),          ntp(nspln),
c      &          npdat(ndata),          nset(ndata),
c      &          laxlp(itime), timet(itime)
c
c
c      WORK ARRAYS
c
c      dimension wh(ntpmax), wb(ntpmax),
c      &          wu(ntpmax), wv(ntpmax)
c
c      LOCAL ARRAY
c
c      dimension xvalu(2)
c
c      data xvalu/'--time--', 'z (norm)'/
c
c      READ IN THERMAL-HYDRAULIC TRANSIENT DATA SETS AND
c      POWER SPATIAL AND TRANSIENT DATA SETS AND
c      GENERATE THE CORRESPONDING SPLINE COEFFICIENTS
c
c      read (ninp,10) commnt
10  format (a)
c
c      ndata - NUMBER OF DISTINCT DATA SETS ENTERED

```

```
c      npts - NUMBER OF DATA PAIRS FOR EACH CURVE
c      nset - NUMBER OF SETS OF ORDINATES FOR THESE ABSCISSA VALUES
c      itype - SPLINE REQUEST (0-CUBIC SPLINES, 1-LINEAR INTERPOLATION)
c
c      inx = 1
c      ibeg = 1
c      iend = 0
c      write (nout,120)
c
c      LOOP OVER ALL INPUT DATA SETS
c
c      do 50 id=1,ndata
c          read (ninp,10) commnt
c          read (ninp,10) label
c          iend = iend + nset(id)
c
c      READ THE DATA
c
c          read (ninp,*) (itype(ispln), ispln=ibeg, iend)
c          read (ninp,*) (xtp(inx-1+ipt), (ytp(ipt,ispln),
c              ispln=ibeg, iend), ipt=1, npdat(id))
c          do 40 ispln=ibeg,iend
c              ntp(ispln) = npdat(id)
c              intp(ispln) = inx
c              call spline (itype(ispln),ntp(ispln),xtp(inx),
c                  ytp(1,ispln),wh,wb,wu,wv,
c                  ztp(1,ispln))
c
c              write (nout,130) ispln, label, npdat(id)
c
c      CHECK FOR AXIAL POWER SHAPE PROFILE AND MAKE SPECIAL EDIT
c
c          itz = 1
c          do 20 it=1,itime
c              if (ispln.eq.iaxlp(it)) then
c                  write (nout,140) it, timet(it)
c                  itz = 2
c                  goto 25
c              end if
c          continue
20
c
c      SAVE ABSCISSA VALUES AND EDIT OUT SPLINE FIT DATA
c
c          write (nout,150) xvalu(itz)
c
c          do 30 ipt=1,npdat(id)
c              ix = inx + ipt - 1
c              write (nout,160) ipt, xtp(ix), ztp(ipt,ispln)
30          continue
c
c          continue
40      inx = inx + npdat(id)
c          ibeg = ibeg + nset(id)
c
c      continue
50
c      WRITE FORMATS
c
c      120 format ('!spline fits to input data:',//)
c
c      130 format (//' spline profile number ',i2,/,a,/,
c          ' number of axial data points in profile ',i3,/)
c
c      140 format (' snapshot ',i2,' at ',g12.5,' seconds',//)
```



```

c
150  format (' --point--  --,a,!--  ',19('-'),
      &      'coefficients' 19('-'))
c
160  format (4x,i3,6x,g12.5,2x,g13.5)
c
      return
      end

```

INTARA

```

      subroutine intara (ai,ci,akgi,hgi,hfi,
&      alp,deff,fldm,fldc,c0b,c0s,coefkb,coefks,
&      dh,vol,flowa,cosg,rof,rog,sigma,uf,ug,
&      visf,visg,p,tg,cpf,cpg,thermf,thermg,
&      diffm,ysi,xa)
c
c *****
c *
c * SUBROUTINE intara:
c *
c * COMPUTES THE INTERFACIAL AREA CONCENTRATION, INTERFACIAL
c * DRAG COEFFICIENT, AND INTERFACIAL HEAT AND MASS TRANSFER
c * COEFFICIENTS AS A FUNCTION OF FLOW REGIME.  VALID FOR
c * VERTICAL PRE-CHF DOWNWARD FLOWS.
c *
c * ARGUMENTS  (O=Output, I=Input):
c *
c * O   ai = INTERFACIAL AREA PER UNIT VOLUME, Ai/V
c * O   ci = AXIAL INTERFACIAL DRAG COEFFICIENT, Ci
c * O   akgi = Kg /alp(1 - alp)  I.H.M.T. COEFFICIENTS TIMES
c * O   hgi = Hgi/alp(1 - alp)  INTERFACIAL AREA DIVIDED BY
c * O   hfi = Hfi/alp(1 - alp)  alp(1 - alp)
c *
c * I   alp = VOID FRACTION
c * I   deff = CHARACTERISTIC DIMENSION FOR SLUG REGIME RISE VEL.
c * I   fldm = CCFL CORRELATION m
c * I   fldc = CCFL CORRELATION C
c * I   c0b = BUBBLY REGIME DISTRIBUTION COEFFICIENT, C0b
c * I   c0s = SLUG REGIME DISTRIBUTION COEFFICIENT, C0s
c * I   coefkb = BUBBLY REGIME DRIFT-VELOCITY COEFFICIENT, Kb
c * I   coefks = SLUG REGIME DRIFT-VELOCITY COEFFICIENT, Ks
c * I   dh = HYDRAULIC DIAMETER
c * I   vol = MOMENTUM CELL VOLUME
c * I   flowa = FLOW AREA
c * I   cosg = cos*g
c * I   rof = LIQUID DENSITY
c * I   rog = GAS DENSITY
c * I   sigma = SURFACE TENSION
c * I   uf = LIQUID VELOCITY
c * I   ug = GAS VELOCITY
c * I   visf = LIQUID DYNAMIC VISCOSITY
c * I   visg = GAS DYNAMIC VISCOSITY
c * I   p = PRESSURE
c * I   tg = GAS TEMPERATURE
c * I   cpf = LIQUID SPECIFIC HEAT CAPACITY
c * I   cpg = GAS SPECIFIC HEAT CAPACITY
c * I   thermf = LIQUID THERMAL CONDUCTIVITY
c * I   thermg = GAS THERMAL CONDUCTIVITY
c * I   diffm = GAS MASS DIFFUSIVITY
c * I   ysi = MOLE FRACTION OF STEAM AT GAS-LIQUID INTERFACE
c * I   xa = MASS FRACTION OF AIR IN BULK GAS
c *
c *
c * *** FLOW REGIME MAP ***
c *
c *****

```

```

c      * PURE          PURE          PURE
c      * LIQUID        SLUG          GAS
c      * -----
c      * |             |             |             |
c      * |             |             |             |
c      * |             |             |             |
c      * | BUBBLY      | BUBBLY-     | SLUG-      | ANNULAR
c      * |             | SLUG        | ANNULAR   |
c      * |             |             |             |
c      * |             |             |             |
c      * -----
c      * 0.0          **          **          **          1.0
c      *             alp          alp          alp
c      *             b            s            a
c      *
c      * TOTAL MIXTURE GAS VOID FRACTION
c      *
c      * *****
c
c      real jgstar, jfstar
c      dimension ws(2)
c
c      include 'params.inc'
c      include 'knobs.inc'
c
c      parameter (zero=0.0, half=0.5, one=1.0, four=4.0, six=6.0,
c      & eight=8.0, third=1.0/3.0)
c
c      MOLECULAR WEIGHTS
c      data wa/28.97/, ws(1)/18.016/, ws(2)/20.034/
c
c      BUBBLE REGIME PARAMETERS
c      data g/9.80665/, bfact/3.6/, dmin/0.00001/, eocrit/6.0/
c
c      SLUG REGIME PARAMETERS
c      data sfact/4.5/, rough/1.5/
c
c      ANNULAR REGIME PARAMETERS
c      data xfldc/1.05/
c
c      SINGLE-PHASE LIMIT PARAMETER
c      data epsal/0.001/
c
c----- PRELIMINARY COMPUTATIONS -----
c
c      pi = acos(-one)
c
c      call c0fcn(alp,c0b,c0s,c0, cg, ann)
c      urabs = abs(cg*ug - c0*uf)
c
c      xs = one - xa
c      ys = (xs/ws(1lq))/(xs/ws(1lq) + xa/wa)
c
c----- SINGLE PHASE LIQUID & BUBBLY REGIME -----
c
c      if (alp .le. alb2) then
c
c      deo = sqrt(eocrit*sigma/((rof - rog)*g))
c      dsb = (six*alp*vol/pi)**third
c      dmax = min(deo,dsb,dh)
c      davg = half*dmax
c      davg = max(davg,dmin)
c
c      ai = alp*bfact/davg

```

```

      frb = (bfact/davg)/(one - alp)
c
      ci = max(epsa1,alp)*(one - alp)**3*rof/coefkb**2
      &      *sqrt((rof - rog)*g/sigma)
c
      call hfib (uf,ug,rof,thermf,cpf,davg,hfb,visf,visg)
      hfi = frb*hfb
c
      call hgib (davg,rog,p,tg,thermg,diffm,cpg,hgb,akgb)
      hgi = frb*hgb
      akgi = frb*akgb
c
c----- BUBBLY & SLUG REGIME -----
c
      else if (alp .le. als2) then
c
      deo = sqrt(eocrit*sigma/((rof - rog)*g))
      dsb = (six*alp*vol/pi)**third
      dmax = min(deo,dsb,dh)
      davg = half*dmax
      davg = max(davg,dmin)
c
      albl = albl*((als2 - alp)/(als2 - albl))**expbs
      als = (alp - albl)/(one - albl)
      albl = alp - als
c
      aib = albl*bfact/davg
      als = als*sfact*rough/dh
      ai = aib + als
      frb = aib/(alp*(one - alp))
      frs = als/(alp*(one - alp))
c
      ci = albl*(one - alp)**3*rof/coefkb**2*sqrt((rof - rog)*g/sigma)
      &      + als*(one - alp)**3*rof/(coefks**2*deff)
c
      call hfib (uf,ug,rof,thermf,cpf,davg,hfb,visf,visg)
      call hfis (visf,rof,thermf,cpf,dh,hfs)
      hfi = frb*hfb + frs*hfs
c
      call hgib (davg,rog,p,tg,thermg,diffm,cpg,hgb,akgb)
      call hgis (p,tg,uf,ug,rog,thermg,visg,cpg,diffm,dh,hgs,akgs)
      hgi = frb*hgb + frs*hgs
      akgi = frb*akgb + frs*akgs
c
c----- SLUG & ANNULAR REGIME -----
c
      else if (alp .le. ala2) then
c
      alal = ala2*((alp - als2)/(ala2 - als2))**expsa
      als = (alp - alal)/(one - alal)
      alal = alp - als
c
      als = als*sfact*rough/dh
      pw = four*flowa/dh
      del = (one - ala)*flowa/pw
      pia = pw - eight*del
      aia = ala*pia/(flowa*alp)
      frs = als/(alp*(one - alp))
      fra = aia/(alp*(one - alp))
      ai = als + aia
c
      ci = als*(one - alp)**3*rof/(coefks**2*deff)
      &      + cia(aia,alp,del,flowa,pia,rog,urabs,visg)
c

```

```
      call hfis (visf,rof,thermf,cpf,dh,hfs)
      call hfia (uf,rof,thermf,visf,cpf,del,hfa,subln)
      hfi = frs*hfs + fra*hfa
c
      call hgis (p,tg,uf,ug,rog,thermg,visg,cpg,diffm,dh,hgs,akgs)
      call hgia (p,tg,ug,rog,visg,ysi,ys,thermg,cpg,diffm,dh,hga,
        &          akga,del)
      hgi = frs*hgs + fra*hga
      akgi = frs*akgs + fra*akga
c
c----- ANNULAR AND SINGLE PHASE GAS REGIME -----
c
      else
c
      beta = one - alp
      pw = four*flowa/dh
      del = beta*flowa/pw
      pia = pw - eight*del
      ai0 = pia/flowa
      phia = min(beta/epsal, one)
      phiar = one/max(epsal, beta)
      ai = phia*ai0
      fra = phiar*ai0/alp
c
      ciann = cia(ai0,alp,del,flowa,pia,rog,urabs,visg)
c
      if ((ug*cosg).lt.zero .and. (uf*cosg).gt.zero) then
        drogd = (rof - rog)*g*deff
        jgstar = alp *abs(ug)*sqrt(rog/drogd)
        jfstar = (one - alp)*abs(uf)*sqrt(rof/drogd)
        cn = sqrt(jgstar) + fldm*sqrt(jfstar)
c
        if (cn .gt. fldc) then
          wt = (cn - fldc)/((xfldc - one)*fldc)
          wt = min(one, wt)
          ciccfl = alp*(one - alp)*rof/(fldc**4*deff)
          &          *((one - alp)*fldm**2 + alp*sqrt(rog/rof))**2
          ci = (one - wt)*ciann + wt*ciccfl
c
        else
          ci = ciann
c
        end if
c
      else
        ci = ciann
c
      end if
c
      call hfia (uf,rof,thermf,visf,cpf,del,hfa,subln)
      hfi = fra*hfa
c
      call hgia (p,tg,ug,rog,visg,ysi,ys,thermg,cpg,diffm,dh,
        &          hga,akga,del)
      hgi = fra*hga
      akgi = fra*akga
c
      end if
c
c----- APPLY SENSITIVITY MULTIPLICATION FACTORS -----
c
      hfi = xhfi*hfi
      hgi = xhgi*hgi
      akgi = xkgi*akgi
```

```

c
      return
      end

```

JACOB

```

      subroutine jacobb(pbn,alpbn,tgbn,tfbn,xabn,rogbn,rofbn,hgbn,hfbn,
      & pb,alpb,tgb,tfb,xab,rogb,rofb,hgb,hfb,
      & gib,eib,hfib,hgib,akgib,ysib,
      & ptb,p,rdelt,factor,abml,rsb,azml,
      & cpab,cptgb,cptfb,cpxab,fab,ftgb,ftfb,fxab,
      & cpa,cptg,cptf,cpxa,
      & volb,advbb,advcb,advbz,advbz,
      & xa0,epsy,epsf,nitysi,
      & nzb,nzp2,nzp3,nchn,nxmax,nx,igami,ierr,ilq)

c
c      !*****!
c      !
c      !               SUBROUTINE JACOB
c      !
c      ! This routine computes the jacobian matrix at the current
c      ! iterate m for the bottom section of a three-section reactor
c      ! assembly. The mathematical and coupling considerations
c      ! are the same as for the mid-section JACOB. The
c      ! FLOWTRAN-TF manual and the FORTRAN of JACOB should be
c      ! examined for more solution detail.
c      !
c      ! This subroutine is compatible only with the FLOWTRAN-TF
c      ! program and the tank bottom section of a three-section
c      ! reactor-assembly simulation.
c      !*****!
c
c      double precision f,ca,cm,cp
c      dimension f(5),ca(5,26),cm(5,5),cp(5,20)
c
c      parameter (zero=0.0, one=1.0)
c
c      ARGUMENT ARRAYS
c
c      dimension
c      & advbz (nzp3,nxmax,nchn,5), abml (nzb,3),
c      & advz (nzp3,nxmax,nchn,5), azml (nzp2,nxmax,nchn,3),
c      & cpa (4,nzp2,nxmax,nchn), alpb (nzb),
c      & cptg (4,nzp2,nxmax,nchn), alpbn (nzb),
c      & cptf (4,nzp2,nxmax,nchn), advbb (nzb,5),
c      & cpxa (4,nzp2,nxmax,nchn), advcb (nzb,5),
c      & cpab (2,nzb), fab (nzb),
c      & cptgb (2,nzb), ftgb (nzb),
c      & cptfb (2,nzb), ftfb (nzb),
c      & cpxab (2,nzb), fxab (nzb)
c
c      dimension
c      & gib (nzb), eib (nzb),
c      & hfib (nzb), hgib (nzb),
c      & akgib (nzb), ysib (nzb),
c      & hgb (nzb), rofb (nzb),
c      & hfb (nzb), rogbn (nzb),
c      & hgbn (nzb), rofbn (nzb),
c      & hfbn (nzb), tfbn (nzb),
c      & nx (nchn), tgbn (nzb),
c      & pb (nzb), tfb (nzb),
c      & pbn (nzb), tgb (nzb),
c      & p (nzp2,nxmax,nchn), xab (nzb),
c      & rsb (nzb), xabn (nzb),

```

```
      &      rogb      (nzb),              volb      (nzb)
c
c      INTERNAL ARRAYS
c
c      dimension sma(5),smb(5)
c
c      parameter ( mxnz = 15 )
c      dimension drgdp(mxnz), drgdtg(mxnz), drgdxa(mxnz),
c      &          dhgdp(mxnz), dhgdtg(mxnz), dhgdxa(mxnz),
c      &          drfdp(mxnz), drfdtf(mxnz),
c      &          dhfdp(mxnz), dhfdtf(mxnz)
c
c      equivalence (ca(1, 1),cm(1,1)),(ca(1,6),f(1)),
c      &          (ca(1,7),cp(1,1))
c
c      Set fixed number of columns in [cm] matrix.
c
c      nzpl = nzp2 - 1
c      ncm = 5
c
c      Compute total number of pressure coupling terms for top cell
c      in contact with bottom of middle section.
c
c      ncpb = 1
c      do 10 k = 1,nchn
c          ncpb = ncpb + nx(k)
10 continue
c
c      Update densities and enthalpies as well as their derivatives.
c
c      call state (pb,tgb,tfb,xab,factor,ilq,
c      &          1,nzb,nzb,1,1,1,1,
c      &          rogb,drgdp,drgdtg,drgdxa,hgb,dhgdp,dhgdtg,dhgdxa,
c      &          rofb,drfdp,drfdtf,hfb,dhfdp,dhfdtf)
c
c      Loop over all axial mass/energy cells within bottom section.
c
c      do 80 jc = 1,nzb
c          jcm = jc - 1
c          jcp = jc + 1
c          jz = jc
c          jzm = jcm
c
c      Set the number of columns in the [ca] and [cp] matrices.
c
c      ncp = 2
c      if (jc .eq. 1) ncp = ncpb
c      if (jc .eq. nzb) ncp = 1
c      ncol = ncm + 1 + ncp
c
c      Compute reciprocal volume.
c
c      rv = one/volb(jc)
c
c      Call routines to define parameters needed in the equation set.
c
c      Set air mass source/sink terms.
c
c      call gammaa (pb(jc),alpb(jc),tgb(jc),xab(jc),xa0,
c      &          gama,          dgada,          dgadxa,
c      &          erga,deadp,deada,deadtg,deadxa)
c
c      Set interfacial heat and mass source/sink terms
c      within the bulk.
```

```

call gammai (gami,dgidp,dgida,dgidtg,dgidtf,dgidxa,
&          ergi,deidp,deida,deidtg,deidtf,deidxa,ysib(jc),
&          pb(jc),alpb(jc),tgb(jc),tfb(jc),xab(jc),
&          akgib(jc),hgib(jc),hfib(jc),
&          epsy,epsf,nitysi,
&          it,ierr,igami,ilq)
if (ierr.eq.1) return

!*****
!
!   Generate equation set for each mass/energy cell (jc):
!
!                                     Equation
!
!   | a a a a a | | dp | | b . . . | | dpl | | e | 1 Gas Mass
!   | a a a a a | | dalp | | b . . . | | . | | e | 2 Liq Mass
!   | a a a a a | | dtg | | + b . . . | | . | | e | 3 Gas Enrg
!   | a a a a a | | dtf | | b . . . | | dp | | e | 4 Liq Enrg
!   | a a a a a | | dxa | | b . . . | | ncp | | e | 5 Air Mass
!   | _ _ _ _ _ | | _ _ | | _ _ _ | | _ _ | | _ _ |
!
!   cm(5x5)      cell      cp(5xncp) neigh-  f(5x1)
!   matrix      variables  matrix  bors    rhs vector
!
!*****

Define parameters common to more than one equation

gib(jc) = gami
eib(jc) = ergi

andt      = alpbn(jc)*rdelt
amdt      = alpb (jc)*rdelt
bndt      = (one - alpbn(jc))*rdelt
bmdt      = (one - alpb (jc))*rdelt

egn       = hgbn(jc)
egm       = hg b (jc)
efn       = hfbn(jc)
efm       = hfb (jc)

prn       = pbn(jc)
prm       = pb (jc)

rgn       = rogbn(jc)
rgm       = rogb (jc)
rgmdt     = rgm*rdelt

rfn       = rofbn(jc)
rfm       = rofb (jc)
rfmdt     = rfm*rdelt

xn        = xabn(jc)
xm        = xab (jc)

dpjp = prm - ptb
if (jc .lt. nzb) dpjp = prm - pb(jcp)
if (jc .ne. 1) dpjm = pb(jcm) - prm

```

```

c      The variables used in the following do-loop are constants
c      within a given time-step. They are generated by a call in
c      the DONORB module before beginning the NEWTON iterations.
c      Compute sums sma(m) for the [cm] matrix and smb(m) for the
c      [f] vector. Also generate all rows of coefficients of
c      matrix [cp].
c
      do 40 m = 1,5
        if (jc .gt. 1) then
          sma(m) = rv*(advcb(jzm,m) + advcb(jz, m))
          smb(m) = rv*(advbb(jzm,m) + advcb(jzm,m)*dpjm
            &          -advbb(jz, m) - advcb(jz, m)*dpjp)
c
          if (jc .eq. nzb) then
            cp(m,1) = -rv*advcb(jzm,m)
          else
            cp(m,1) = -rv*advcb(jzm,m)
            cp(m,2) = -rv*advcb(jz, m)
          endif
c
        else
          suma = zero
          sumb = zero
          cp(m,ncp) = -rv*advcb(jz,m)
c
c      This double do-loop provides the interface between the top
c      single-cell rows and the mid-section multi-channel multi-cell
c      rows. The donor variables with i subscripts are evaluated in
c      the mid-section routines and account for flow direction.
c
c      Loop over all assembly channels
c
          n = 0
          do 30 k = 1,nchn
c
c      Loop over the azimuthal cells within given channel.
c
              nsub = nx(k)
              do 20 i = 1,nsub
                n = n + 1
                cp(m,n) = -rv*advbz(nzp2,i,k,m)
                suma = suma + advbz(nzp2,i,k,m)
                sumb = sumb+advbz(nzp2,i,k,m)+advbz(nzp2,i,k,m)*
                  &          (p(nzp1,i,k)-prm)
              20          continue
              30          continue
c
                sma(m) = rv*(advcb(jz,m) + suma)
                smb(m) = rv*(sumb - advbb(jz,m) - advcb(jz,m)*dpjp)
              endif
            40          continue
c
c      Generate all rows of coefficients for the [cm] matrix,
c      and vector [f].
c      MIXTURE GAS MASS
c
      cm(1,1) = amdt * drgdp(jz) - dgidp + sma(1)
      cm(1,2) = rgmdt - dgida - dgada
      cm(1,3) = amdt * drgdtg(jz) - dgidtg
      cm(1,4) = - dgidtf
      cm(1,5) = amdt * drgdx(jz) - dgidxa - dgadxa
c
c      LIQUID MASS
c

```



```

cm(2,1) = bmdt * drfdp(jz) + dgdp + sma(2)
cm(2,2) = - rfmdt + dgda
cm(2,3) = dgdtg
cm(2,4) = bmdt * drfdtf(jz) + dgdtf
cm(2,5) = dgidxa
C
C MIXTURE GAS ENERGY
C
cm(3,1) = amdt * (rgm * dhgdp(jz) + egm * drgdp(jz))
& - andt - deidp - deadp + sma(3)
cm(3,2) = rgmdt * egm - deida - deada
cm(3,3) = amdt * (rgm * dhgdtg(jz) + egm * drgdtg(jz))
& - deidt - deadtg
cm(3,4) = - deidtf
cm(3,5) = amdt * (rgm * dhgdx(jz) + egm * drgdx(jz))
& - deidx - deadxa
C
C LIQUID ENERGY
C
cm(4,1) = bmdt * (rfm * dhfdp(jz) + efm * drfdp(jz)) - bndt
& + deidp + sma(4)
cm(4,2) = - rfmdt * efm + deida
cm(4,3) = deidt
cm(4,4) = bmdt * (rfm * dhfdtf(jz) + efm * drfdtf(jz))
& + deidtf
cm(4,5) = deidxa
C
C AIR MASS
C
cm(5,1) = amdt * xm * drgdp(jz) + sma(5)
cm(5,2) = rgmdt * xm - dgada
cm(5,3) = amdt * xm * drgdtg(jz)
cm(5,4) = zero
cm(5,5) = amdt * (xm * drgdx(jz) + rgm) - dgadxa
C
C RIGHT HAND SIDES
C
f(1) = andt * rgn - amdt * rgm + smb(1) + gami + gama
f(2) = bndt * rfn - bmdt * rfm + smb(2) - gami
f(3) = andt * rgn * egn - amdt * rgm * egm
& + andt * (prm - prn) + smb(3) + ergi + erga
f(4) = bndt * rfn * efn - bmdt * rfm * efm
& + bndt * (prm - prn) + smb(4) - ergi
f(5) = andt * rgn * xn - amdt * rgm * xm + gama + smb(5)
C
C Perform gauss-jordan inversion of 5x5 [cm] matrix to eliminate
C alp, tg, tf, and xa for a pressure only problem.
C
call gajor5 (ncol,ca)
C
C Set up jacobian matrix and rhs vector for pressure only problem.
C
rhsb(jc) = f(1)
fab(jc) = f(2)
ftgb(jc) = f(3)
ftfb(jc) = f(4)
fxab(jc) = f(5)
if (jc .eq. nzb) then
C
C Store pressure coefficients for gauss-seidel iteration procedure:
C axial tri-diagonal only
C Store pressure coefficients necessary to recover alp, tg,
C tf, and xa for bottom cell of the bottom section. Compute
C diagonal dominant factor, too.

```

```
c      ddom = abs(cp(1,1))
      if (ddom .ge. one) go to 90
      abml(jc,1) = one
      abml(jc,2) = zero
      abml(jc,3) = cp(1,1)
c
      cpab(1,jc) = cp(2,1)
      cptgb(1,jc) = cp(3,1)
      cptfb(1,jc) = cp(4,1)
      cpxab(1,jc) = cp(5,1)
      endif
      if (jc .gt. 1 .and. jc .lt. nzb) then
c
c      Store pressure coefficients for gauss-seidel iteration procedure:
c      axial tri-diagonal only
c      Store pressure coefficients necessary to recover alp, tg,
c      tf, and xa for bottom cell of the bottom section. Compute
c      diagonal dominant factor, too.
c
      abml(jc,1) = one
      abml(jc,2) = cp(1,2)
      abml(jc,3) = cp(1,1)
c
      ddom = zero
      do 50 k = 1,ncp
        ddom = ddom + abs(real(cp(1,k)))
        cpab(k,jc) = cp(2,k)
        cptgb(k,jc) = cp(3,k)
        cptfb(k,jc) = cp(4,k)
        cpxab(k,jc) = cp(5,k)
50      continue
      if (ddom .ge. one) go to 90
      endif
      if (jc .eq. 1) then
c
c      Store pressure coefficients for gauss-seidel iteration procedure:
c      axial tri-diagonal only
c      Store pressure coefficients necessary to recover alp, tg,
c      tf, and xa for bottom cell of the bottom section. Compute
c      diagonal dominant factor, too.
c
      abml(jc,1) = one
      abml(jc,2) = cp(1,ncp)
      abml(jc,3) = zero
      ddom = abs(cp(1,ncp))
c
      cpab(2,jc) = cp(2,ncp)
      cptgb(2,jc) = cp(3,ncp)
      cptfb(2,jc) = cp(4,ncp)
      cpxab(2,jc) = cp(5,ncp)
c
      n = 0
      do 70 k = 1,nchn
        nsub = nx(k)
        do 60 i = 1,nsub
          n = n + 1
          azml(nzp2,i,k,2) = cp(1,n)
          ddom = ddom + abs(real(cp(1,n)))
          cpa(1,nzp2,i,k) = cp(2,n)
          cptg(1,nzp2,i,k) = cp(3,n)
          cptf(1,nzp2,i,k) = cp(4,n)
          cpxa(1,nzp2,i,k) = cp(5,n)
60      continue
70      continue
```

```

70      continue
      if (ddom .ge. one) go to 90
    endif
c
c      End axial mass/energy cell loop (index jc)
c
80 continue
  return
c
c      ERROR detected, pressure problem is not diagonally dominant.
c      Time step will be halved and newton iteration restarted.
c
90 ierr = 1
  return
end

```

JACOBN

```

subroutine jacobm(pn,alpn,tgn,tfn,xan,rogn,rofn,hgn,hfn,
&                p ,alp ,tg ,tf ,xa ,rog ,rof ,hg ,hf ,
&                gi,ei ,hfi,hgi ,akgi,ysi,gw ,hspl,
&                rdelt,factor,
&                azm1,azm2,rhs,qwg,qwf,tsurf,ar,
&                cpa,cptg,cptf,cpxa,fa,ftg,ftf,fxa,
&                volc,advbz,advbz,advdx,advex,txg,txf,
&                xa0,epsy,epsf,nitysi,
&                iaz1,nazc,na,napl,nr,nrmxp,nz,nsurf,icent,
&                nzp1,nzp2,nzp3,nchn,nxmax,nx,ncyln,icc,igami,
&                igamw,ierr,ilq)
c
c      !*****!
c      !
c      !          SUBROUTINE JACOBN
c      !
c      !      This routine computes the jacobian matrix at the current
c      !      iterate m. It is obtained by linearizing the densities
c      !      and internal energies vs temperatures, pressure, and
c      !      air mass fraction in the mixture gas, liquid, and air mass
c      !      equations, and mixture gas and liquid energy equations.
c      !      It is assumed that phase velocities are known linear func-
c      !      tions of their appropriate pressure driving forces. Upon
c      !      substitutions to eliminate phase velocities, a pressure
c      !      only poisson equation is obtained.
c      !
c      !      This subroutine is compatible only with the FLOWTRAN_TF
c      !      program and the mid_section (core) of a three-section
c      !      reactor-assembly model.
c      !
c      !*****!
c
cvax double precision f,ca,cm,cp
dimension f(5),ca(5,26),cm(5,5),cp(5,20)
c
c      parameter (zero=0.0, one=1.0)
c
c      ARGUMENT ARRAYS
c
dimension
&      azm1      (nzp2,nxmax,nchn,3),      hgn      (nzp2,nxmax,nchn),
&      azm2      (nzp2,nxmax,nchn,2),      hfn      (nzp2,nxmax,nchn),
&      alp      (nzp2,nxmax,nchn),      icc      (2,nxmax,nchn),
&      alpn      (nzp2,nxmax,nchn),      p      (nzp2,nxmax,nchn),
&      advbz      (nzp3,nxmax,nchn,5),      pn      (nzp2,nxmax,nchn),
&      advcz      (nzp3,nxmax,nchn,5),      rhs      (nzp2,nxmax,nchn),
&      advdx      (nzp2,nxmax,nchn,5),      rog      (nzp2,nxmax,nchn),

```

```

& advex (nzp2,nxmax,nchn,5), rof (nzp2,nxmax,nchn),
& cpa (4,nzp2,nxmax,nchn), rogn (nzp2,nxmax,nchn),
& cptg (4,nzp2,nxmax,nchn), rofn (nzp2,nxmax,nchn),
& cptf (4,nzp2,nxmax,nchn), tfn (nzp2,nxmax,nchn),
& cpxa (4,nzp2,nxmax,nchn), tgn (nzp2,nxmax,nchn),
& fa (nzp2,nxmax,nchn), tf (nzp2,nxmax,nchn),
& ftg (nzp2,nxmax,nchn), tg (nzp2,nxmax,nchn),
& ftf (nzp2,nxmax,nchn), volc (nzp2,nxmax,nchn),
& fxa (nzp2,nxmax,nchn), xa (nzp2,nxmax,nchn),
& hg (nzp2,nxmax,nchn), xan (nzp2,nxmax,nchn),
& hf (nzp2,nxmax,nchn), nx (nchn)

```

c

```

dimension
& gi (nzp2,nxmax,nchn), ei (nzp2,nxmax,nchn),
& hfi (nzp2,nxmax,nchn), hgi (nzp2,nxmax,nchn),
& akgi (nzp2,nxmax,nchn), ysi (nzp2,nxmax,nchn),
& gw (nzp2,nxmax,nchn), ar (nrmxp,nz,ncyl),
& hspl (nsurf,na,nz), tsurf (nsurf,na,nz),
& qwg (nsurf,na,nz), qwf (nsurf,na,nz),
& iazl (nxmax,nchn), nazc (nxmax,nchn),
& nr (ncyl)

```

c

```
dimension txg(4,nzp2,nxmax,nchn), txf(4,nzp2,nxmax,nchn)
```

c

```
INTERNAL ARRAYS
```

c

```
dimension sma(5),smb(5)
```

c

```

parameter ( mxnz = 100 )
dimension drgdp(mxnz), drgdtg(mxnz), drgdxa(mxnz),
& dhgdp(mxnz), dhgdtg(mxnz), dhgdxa(mxnz),
& drfdp(mxnz), drfdtf(mxnz),
& dhfdp(mxnz), dhfdtf(mxnz)

```

c

```

equivalence (ca(1,1),cm(1,1)),(ca(1,6),f(1)),
& (ca(1,7),cp(1,1))

```

c

```
data gamw/0.0/, ergw/0.0/
```

c

```
SET FIXED NUMBER OF COLUMNS IN [ca], [cm], AND [cp] MATRICES
```

c

```

ncm = 5
ncp = 4
ncol = ncm + 1 + ncp

```

c

```
LOOP OVER EACH FLOW ANNULUS (CHANNEL) WITHIN ASSEMBLY (CORE)
```

c

```

do 60 k = 1,nchn
  isrfi = 2*k - 1 + icent
  isrfo = isrfi + 1
  icyli = isrfi - k
  icylo = isrfo - k

```

c

```
LOOP OVER ALL AZIMUTHAL MASS/ENERGY SECTORS WITHIN 2D CHANNEL
```

c

```

nsub = nx(k)
do 50 i = 1,nsub
  im = icc(1,i,k)
  ip = icc(2,i,k)
  iazf = iazl(i,k)
  iazl = iazf + nazc(i,k) - 1

```

c

```
UPDATE DENSITIES AND ENTHALPIES AS WELL AS THEIR DERIVATIVES
```

c

```

      call state (p,tg,tf,xa,factor,ilq,
4          2,nzpl,nzp2,nxmax,nchn,i,k,
4          rog,drgdp,drgdtg,drgdxa,
4          hg,dhgdg,dhgdtg,dhgdx,rof,
4          drfdp,drfdtf,hf,dhfdp,dhfdtf)
c
c      LOOP OVER ALL AXIAL MASS/ENERGY CELLS WITHIN AZIMUTHAL SECTOR
c
      do 40 jc = 2,nzpl
          jcm = jc - 1
          jcp = jc + 1
          jz = jc
          jzp = jcp
          jx = jc
c
c      COMPUTE RECIPROCAL VOLUME
c
          rv = one/volc(jc,i,k)
c
c      COMPUTE INNER AND OUTER WALL AREAS
c
          if (icyli.eq.0) then
              aiw = zero
          else
              nrp = nr(icyli) + 1
              aiw = ar(nrp,jcm,icyli)
          end if
          aow = ar(1,jcm,icylo)
c
c      CALL ROUTINES TO DEFINE PARAMETERS NEEDED IN THE EQUATION SET
c
c      SET AIR MASS SOURCE/SINK TERMS
c
      call gammaa (p(jc,i,k),alp(jc,i,k),tg(jc,i,k),xa(jc,i,k),xa0,
4          gama, dgada, dgadxa,
4          erga,deadp,deada,deadtg,deadxa)
c
c      SET INTERFACIAL HEAT AND MASS SOURCE/SINK TERMS
c      WITHIN THE BULK
c
      call gammal (gami,dgidp,dgida,dgidtg,dgidtf,dgidxa,
4          ergl,deidp,deida,deidtg,deidtf,deidxa,ysi(jc,i,k),
4          p(jc,i,k),alp(jc,i,k),tg(jc,i,k),tf(jc,i,k),
4          xa(jc,i,k),akgi(jc,i,k),hgi(jc,i,k),hfi(jc,i,k),
4          epsy,epsf,nitysi,
4          it,ierr,igami,ilq)
      if (ierr.eq.1) return
c
c      SET INTERFACIAL MASS SOURCE/SINK TERMS AT THE WALL
c
      if (igamw .eq. 1) then
          gamw = gw(jc,i,k)*rv
          if (gamw.gt.zero) then
              call hssat (p(jc,i,k),ilq,hvap,dum)
              ergw = gamw*hvap
          else if (gamw.lt.zero) then
              call hfsat (tf(jc,i,k),ilq,hliq,dum)
              ergw = gamw*hliq
          else
              ergw = zero
          end if
      end if
c
c      COMPUTE HEAT TRANSFER FROM INNER AND OUTER WALLS TO LIQUID AND GAS

```

```

c
      qgiw = zero
      qgow = zero
      qfiw = zero
      qfow = zero
c
      do 10 iaz=iazf,iazl
        ia = iaz - na*(iaz/napl)
        qgiw = qgiw + qwg(isrfi,ia,jcm)
        qgow = qgow + qwg(isrfo,ia,jcm)
        qfiw = qfiw + qwf(isrfi,ia,jcm)
        qfow = qfow + qwf(isrfo,ia,jcm)
10    continue
c
      qwallg = (aiw*qgiw + aow*qgow)*rv
      qwallf = (aiw*qfiw + aow*qfow)*rv
c
c *****
c !
c ! Generate equation set for each mass/energy cell (jc,i,k):
c !
c !                                     Equation
c !
c ! |a a a a a| |dp| |b b b b| |dp1| |e| 1 Gas Mass
c ! |a a a a a| |dalp| |b b b b| |dp2| |e| 2 Liq Mass
c ! |a a a a a| |dtg| + |b b b b| |dp3| = |e| 3 Gas Enrg
c ! |a a a a a| |dtf| |b b b b| |dp4| |e| 4 Liq Enrg
c ! |a a a a a| |dxa| |b b b b| |_ _| |e| 5 Air Mass
c ! |_ _ _ _ _| |_ _ _ _| |_ _ _ _| |_ _|
c !
c ! cm(5x5)    cell    cp(5x4)    neigh-    f(5x1)
c ! matrix    variables matrix    bors    rhs vector
c !
c *****
c
c DEFINE PARAMETERS COMMON TO MORE THAN ONE EQUATION
c
      gi(jc,i,k) = gami
      ei(jc,i,k) = ergi
c
      andt = alpn(jc,i,k)*rdelt
      amdt = alp(jc,i,k)*rdelt
      bndt = (one - alpn(jc,i,k))*rdelt
      bmdt = (one - alp(jc,i,k))*rdelt
c
      egn = hgn(jc,i,k)
      egm = hg(jc,i,k)
      efn = hfn(jc,i,k)
      efm = hf(jc,i,k)
c
      gtxf = txf(1,jc,i,k)
      gtxg = txg(1,jc,i,k)
c
      prn = pn(jc,i,k)
      prm = p(jc,i,k)
c
      qtxf = txf(2,jc,i,k)
      qtxg = txg(2,jc,i,k)
c
      rgn = rogn(jc,i,k)

```

```

      rgm      = rog (jc,i,k)
      rgmdt    = rgm*rdelt
c
      rfn      = rofn(jc,i,k)
      rfm      = rof (jc,i,k)
      rfmdt    = rfm*rdelt
c
      xn       = xan(jc,i,k)
      xm       = xa (jc,i,k)
c
      dpjm     = p(jcm,i ,k) - prm
      dpjp     = prm          - p(jcp,i, k)
      dpim     = p(jc, im,k) - prm
      dpip     = prm          - p(jc, ip,k)
c
c   The variables used in the following do-loop are constants
c   within a given time-step. They are generated by a call to
c   the DONORM module before beginning the NEWTON iterations.
c   Compute sums sma(m) for the [cm] matrix and smb(m) for the
c   [f] vector. Also generate all rows of coefficients of
c   matrix [cp].
c
      do 20 m = 1,5
        sma(m) = rv*(advbz(jz,i,k,m) + advbz(jzp,i,k,m) +
          &          advex(jx,i,k,m) + advex(jx,ip,k,m))
        smb(m) = + advbz(jz ,i,k,m) + advbz(jz ,i,k,m)*dpjm
          &          - advbz(jzp,i,k,m) - advbz(jzp,i,k,m)*dpjp
          &          + advdx(jx, i,k,m) + advex(jx, i,k,m)*dpim
          &          - advdx(jx,ip,k,m) - advex(jx,ip,k,m)*dpij
        smb(m) = rv*smb(m)
        cp(m,1) = - rv*advbz(jz, i,k,m)
        cp(m,2) = - rv*advbz(jzp,i,k,m)
        cp(m,3) = - rv*advex(jx, i,k,m)
        cp(m,4) = - rv*advex(jx,ip,k,m)
20      continue
c
c   Generate all rows of coefficients for the [cm] matrix,
c   and vector [f].
c   mixture gas mass
      cm(1,1) = amdt * drgdp(jz) - dgidp + sma(1)
      cm(1,2) = rgmdt - dgida - dgada
      cm(1,3) = amdt * drgdtg(jz) - dgidtq
      cm(1,4) = - dgidtf
      cm(1,5) = amdt * drgdx(jz) - dgidxa - dgadxa
c   liquid mass
      cm(2,1) = bmdt * drfdp(jz) + dgidp + sma(2)
      cm(2,2) = - rfmdt + dgida
      cm(2,3) = dgidtq
      cm(2,4) = bmdt * drfdtf(jz) + dgidtf
      cm(2,5) = dgidxa
c   mixture gas energy
      cm(3,1) = amdt * (rgm * dhgdp(jz) + egm * drgdp(jz))
          &          - andt * deidp - deadp + sma(3)
      cm(3,2) = rgmdt * egm - deida - deada
      cm(3,3) = amdt * (rgm * dhgdtg(jz) + egm * drgdtg(jz))
          &          - deidtq - deadtq
      cm(3,4) = - deidtf
      cm(3,5) = amdt * (rgm * dhgdx(jz) + egm * drgdx(jz))
          &          - deidxa - deardxa
c   liquid energy
      cm(4,1) = bmdt * (rfm * dhfdp(jz) + efm * drfdp(jz)) - bndt
          &          + deidp + sma(4)
      cm(4,2) = - rfmdt * efm + deida
      cm(4,3) = deidtq

```

```

      cm(4,4) = bmdt * (rfm * dhfdtf(jz) + efm * drfdtf(jz))
      & + deidtf
      cm(4,5) = deidxa
c    air mass
      cm(5,1) = amdt * xm * drgdp(jz) + sma(5)
      cm(5,2) = rgmdt * xm - dgada
      cm(5,3) = amdt * xm * drgdtg(jz)
      cm(5,4) = zero
      cm(5,5) = amdt * (xm * drgdx(jz) + rgm) - dgadxa
c    right hand sides
      f(1) = amdt * rgn - amdt * rgm + smb(1) + gami + gama
      & + gamw + gtxg
      f(2) = bndt * rfn - bmdt * rfm + smb(2) - gami
      & - gamw + gtxf
      f(3) = amdt * rgn * egn - amdt * rgm * egm
      & + amdt * (prm - prn) + smb(3)
      & + ergi + ergw + erga + qwallg + gtxg
      f(4) = bndt * rfn * efn - bmdt * rfm * efm
      & + bndt * (prm - prn) + smb(4)
      & - ergi - ergw + qwallf + gtxf
      f(5) = amdt * rgn * xn - amdt * rgm * xm
      & + gama + smb(5) + gtxg * xn
c
c    Perform gauss-jordan inversion of 5x5 [cm] matrix to eliminate
c    alp, tg, tf, and xa for a pressure only problem.
c
      call gajor5 (ncol,ca)
c
c    Set up jacobian matrix and rhs vector for pressure only problem.
c
      rhs(jc,i,k) = f(1)
      fa (jc,i,k) = f(2)
      ftg(jc,i,k) = f(3)
      ftf(jc,i,k) = f(4)
      fxa(jc,i,k) = f(5)
c
c    Store pressure coefficients for gauss-seidel iteration procedure:
c    axial tri-diagonal
      azml(jc,i,k,1) = one
      azml(jc,i,k,2) = cp(1,2)
      azml(jc,i,k,3) = cp(1,1)
c    azimuthal tri-diagonal
      azm2(jc,i,k,1) = cp(1,3)
      azm2(jc,i,k,2) = cp(1,4)
c
c    Store pressure coefficients necessary to recover alp, tg,
c    tf, and xa. Compute diagonal dominant factor, too.
c
      ddom = zero
      do 30 m = 1,4
        ddom = ddom + abs(real(cp(1,m)))
        cpa (m,jc,i,k) = cp(2,m)
        cptg(m,jc,i,k) = cp(3,m)
        cptf(m,jc,i,k) = cp(4,m)
        cpxa(m,jc,i,k) = cp(5,m)
30      continue
      if (ddom .ge. one) go to 70
c
c    End axial mass/energy cell loop (index jc)
c
40      continue
c
c    End azimuthal mass/energy sector loop (index i)
c

```



```

50      continue
c
c      End assembly channel loop (index k)
c
60      continue
      return
c
c      ERROR detected, pressure problem is not diagonally dominant.
c      Time step will be halved and newton iteration restarted.
c
70      ierr = 1
      return
      end

```

JACOBT

```

      subroutine jacobt(ptn,alptn,tgtn,tftn,xatn,rogtn,roftn,hgtn,hftn,
&      pt ,alpt ,tgt ,tft ,xat ,rogt ,roft ,hgt ,hft ,
&      git,eit ,hfit,hgit ,akgit,ysit,
&      ppl,p,rdelt,factor,atml,rhst,azml,
&      cpat,cptgt,cptft,cpxat,fat,ftgt,ftft,fxat,
&      cpa ,cptg ,cptf ,cpxa ,
&      volt,advbt,advct,advbz,advcz,
&      xa0,epsy,epsf,nitysl,
&      nzt,nzp2,nzp3,nchn,nxmax,nx,igami,ierr,ilq)
c
c      !*****!
c      !
c      !          SUBROUTINE JACOBT
c      !
c      !      This routine computes the jacobian matrix at the current
c      !      iterate m for the top section of a three-section reactor
c      !      assembly. The mathematical and coupling considerations
c      !      are the same as for the mid-section JACOBM. The
c      !      FLOWTRAN_TF manual and the FORTRAN of JACOBM should be
c      !      examined for more solution detail.
c      !
c      !      This subroutine is compatible only with the FLOWTRAN_TF
c      !      program and the top_section (plenum) of a three-section
c      !      reactor-assembly simulation.
c      !
c      !*****!
c
cvax  double precision f,ca,cm,cp
      dimension f(5),ca(5,26),cm(5,5),cp(5,20)
c
      parameter (zero=0.0, one=1.0)
c
c      ARGUMENT ARRAYS
c
      dimension
&      advbz (nzp3,nxmax,nchn,5),      atml (nzt,3),
&      advcz (nzp3,nxmax,nchn,5),      azml (nzp2,nxmax,nchn,3),
&      cptg (4,nzp2,nxmax,nchn),      alpt (nzt),
&      cptf (4,nzp2,nxmax,nchn),      alptn (nzt),
&      cpxa (4,nzp2,nxmax,nchn),      advbt (nzt,5),
&      cpa (4,nzp2,nxmax,nchn),      advct (nzt,5),
&      cpat (2,nzt),                  fat (nzt),
&      cptgt (2,nzt),                  ftgt (nzt),
&      cptft (2,nzt),                  ftft (nzt),
&      cpxat (2,nzt),                  fxat (nzt)
c
      dimension
&      git (nzt),                      eit (nzt),
&      hfit (nzt),                      hgit (nzt),

```

```
&      akgit      (nzt),          ysit      (nzt),
&      hgt        (nzt),          tftn      (nzt),
&      hft        (nzt),          tgtn      (nzt),
&      hgtn       (nzt),          roftn     (nzt),
&      hftn       (nzt),          tft       (nzt),
&      nx         (nchn),         tgt       (nzt),
&      pt         (nzt),          rogt      (nzt),
&      ptn        (nzt),          xat       (nzt),
&      p          (nzp2,nxmax,nchn), xatn    (nzt),
&      rhst       (nzt),          roft     (nzt),
&      rogt       (nzt),          volt     (nzt)
```

```
c
c      INTERNAL ARRAYS
c
c      dimension sma(5),smb(5)
c
c      parameter ( mxnz = 15 )
c      dimension drgdp(mxnz), drgdtg(mxnz), drgdxa(mxnz),
c      &          dhgdp(mxnz), dhgdtg(mxnz), dhgdxa(mxnz),
c      &          drfdp(mxnz), drfdtf(mxnz),
c      &          dhfdp(mxnz), dhfdtf(mxnz)
c
c      equivalence (ca(1, 1),cm(1,1)),(ca(1,6),f(1)),
c      &          (ca(1,7),cp(1,1))
c
c      Set fixed number of columns in [cm] matrix.
c
c      ncm = 5
c
c      Compute total number of pressure coupling terms for bottom cell
c      in contact with top of middle section.
c
c      ncpt = 1
c      do 10 k = 1,nchn
c          ncpt = ncpt + nx(k)
c 10 continue
c
c      Update densities and enthalpies as well as their derivatives.
c
c      call state (pt,tgt,tft,xat,factor,ilq,
c      &          1,nzt,nzt,1,1,1,1,
c      &          rogt,drgdp,drgdtg,drgdxa,hgt,dhgdp,
c      &          dhgdtg,dhgdxa,roft,drfdp,drfdtf,hft,
c      &          dhfdp,dhfdtf)
c
c      Loop over all axial mass/energy cells within top section.
c
c      do 80 jc = 1,nzt
c          jcm = jc - 1
c          jcp = jc + 1
c          jz = jc
c          jzp = jcp
c
c      Set the number of columns in the [ca] and [cp] matrices.
c
c      ncp = 2
c      if (jc .eq. 1) ncp = 1
c      if (jc .eq. nzt) ncp = ncpt
c      ncol = ncm + 1 + ncp
c
c      Compute reciprocal volume.
c
c      rv = one/volt(jc)
c
```

```
C      Call routines to define parameters needed in the equation set.
C
C      Set air mass source/sink terms.
C
      call gammaa (pt(jc),alpt(jc),tgt(jc),xat(jc),xa0,
6         gama,          dgada,          dgadxa,
6         erga,deadp,deada,deadtg,deadxa)
C
C      Set interfacial heat and mass source/sink terms
C      within the bulk.
C
      call gammai (gami,dgidp,dgida,dgidtg,dgidtf,dgidxa,
6         ergi,deidp,deida,deidtg,deidtf,deidxa,ysit(jc),
6         pt(jc),alpt(jc),tgt(jc),tft(jc),xat(jc),
6         akgit(jc),hglt(jc),hfit(jc),
6         epsy,epsf,nitysi,
6         lt,ierr,igami,ilq)
      if (ierr.eq.1) return
C
C      !*****
C      !
C      !   Generate equation set for each mass/energy cell (jc):
C      !
C      !                                     Equation
C      !
C      !   | a a a a a | dp | b . . . | dpl | e | 1 Gas Mass
C      !   | a a a a a | dalp | b . . . | . | e | 2 Liq Mass
C      !   | a a a a a | dtg | + b . . . | . | = e | 3 Gas Enrg
C      !   | a a a a a | dtf | b . . . | dp | e | 4 Liq Enrg
C      !   | a a a a a | dxn | b . . . | ncp | e | 5 Air Mass
C      !   | _ _ _ _ _ | _ _ | _ _ _ _ | _ _ | _ _
C      !
C      !       cm(5x5)    cell    cp(5xncp) neigh- f(5x1)
C      !       matrix    variables matrix  bors  rhs vector
C      !
C      !*****
C
C      Define parameters common to more than one equation
C
      git(jc) = gami
      eit(jc) = ergi
C
      andt     = alptn(jc)*rdelt
      amdt     = alpt (jc)*rdelt
      bn timer  = (one - alptn(jc))*rdelt
      bmdt     = (one - alpt (jc))*rdelt
C
      egner     = hgtn(jc)
      egm       = hgt (jc)
      efn       = hftn(jc)
      efm       = hft (jc)
C
      prn       = ptn(jc)
      prm       = pt (jc)
C
      rgn       = rogt(n(jc))
      rgm       = rogt (jc)
      rgm timer  = rgm*rdelt
C
      rfn       = roft(n(jc))
```

```

      rfm      = roft (jc)
      rfmdt    = rfm*rdelt
c
      xn       = xatn(jc)
      xm       = xat (jc)
c
      dpjm = ppl - prm
      if (jc .gt. 1) dpjm = pt(jcm) - prm
      if (jc .ne. nzt) dpjp = prm - pt(jcp)
c
c   The variables used in the following do-loop are constants
c   within a given time-step. They are generated by a call in
c   the DONORT module before beginning the NEWTON iterations.
c   Compute sums sma(m) for the [cm] matrix and smb(m) for the
c   [f] vector. Also generate all rows of coefficients of
c   matrix [cp].
c
      do 40 m = 1,5
        if (jc .lt. nzt) then
          sma(m) = rv*(advct(jz,m) + advct(jzp,m))
          smb(m) = rv*(advbt(jz,m) + advct(jz ,m)*dpjm
                    - advbt(jzp,m) - advct(jzp,m)*dpjp)
c
          if (jc .eq. 1) then
            cp(m,1) = -rv*advct(jzp,m)
          else
            cp(m,1) = -rv*advct(jz, m)
            cp(m,2) = -rv*advct(jzp,m)
          endif
c
        else
          suma = zero
          sumb = zero
          cp(m,1) = -rv*advct(jz,m)
c
c   This double do-loop provides the interface between the top
c   single-cell rows and the mid-section multi-channel multi-cell
c   rows. The donor variables with i subscripts are evaluated in
c   the mid-section routines and account for flow direction.
c
c   Loop over all assembly channels
c
          n = 1
          do 30 k = 1,nchn
c
c   Loop over the azimuthal cells within given channel.
c
            nsub = nx(k)
            do 20 i = 1,nsub
              n = n + 1
              cp(m,n) = -rv*advbz(2,i,k,m)
              suma = suma + advbz(2,i,k,m)
              sumb = sumb + advbz(2,i,k,m) + advcz(2,i,k,m)*
                    (prm-p(2,i,k))
c
            20      continue
            30      continue
c
              sma(m) = rv*(advct(jz,m) + suma)
              smb(m) = rv*(advbt(jz,m) + advct(jz,m)*dpjm - sumb)
            endif
          40      continue
c
c   Generate all rows of coefficients for the [cm] matrix,
c   and vector [f].

```

c MIXTURE GAS MASS

c

```
cm(1,1) = amdt * drgdp(jz) - dgidp + sma(1)
cm(1,2) = rgmdt - dgida - dgada
cm(1,3) = amdt * drgdtg(jz) - dgidtg
cm(1,4) = - dgidtf
cm(1,5) = amdt * drgdxa(jz) - dgidxa - dgadxa
```

c

c

LIQUID MASS

c

```
cm(2,1) = bmdt * drfdp(jz) + dgidp + sma(2)
cm(2,2) = - rfmdt + dgida
cm(2,3) = dgidtg
cm(2,4) = bmdt * drfdtf(jz) + dgidtf
cm(2,5) = dgidxa
```

c

c

MIXTURE GAS ENERGY

c

```
cm(3,1) = amdt * (rgm * dhgdp(jz) + egm * drgdp(jz))
& - andt * deidp - deadp + sma(3)
cm(3,2) = rgmdt * egm - deida - deada
cm(3,3) = amdt * (rgm * dhgdtg(jz) + egm * drgdtg(jz))
& - deidtg - deadtg
cm(3,4) = - deidtf
cm(3,5) = amdt * (rgm * dhgdxa(jz) + egm * drgdxa(jz))
& - deidxa - deadxa
```

c

c

LIQUID ENERGY

c

```
cm(4,1) = bmdt * (rfm * dhfdp(jz) + efm * drfdp(jz)) - bndt
& + deidp + sma(4)
cm(4,2) = - rfmdt * efm + deida
cm(4,3) = deidtg
cm(4,4) = bmdt * (rfm * dhfdtf(jz) + efm * drfdtf(jz))
& + deidtf
cm(4,5) = deidxa
```

c

c

AIR MASS

c

```
cm(5,1) = amdt * xm * drgdp(jz) + sma(5)
cm(5,2) = rgmdt * xm - dgada
cm(5,3) = amdt * xm * drgdtg(jz)
cm(5,4) = zero
cm(5,5) = amdt * (xm * drgdxa(jz) + rgm) - dgadxa
```

c

c

RIGHT HAND SIDES

c

```
f(1) = andt * rgn - amdt * rgm + smb(1) + gami + gama
f(2) = bndt * rfn - bmdt * rfm + smb(2) - gami
f(3) = andt * rgn * egn - amdt * rgm * egm
& + andt * (prm - prn) + smb(3) + ergi + erga
f(4) = bndt * rfn * efn - bmdt * rfm * efm
& + bndt * (prm - prn) + smb(4) - ergi
f(5) = andt * rgn * xn - amdt * rgm * xm + gama + smb(5)
```

c

c

Perform gauss-jordan inversion of 5x5 [cm] matrix to eliminate
alp, tg, tf, and xa for a pressure only problem.

c

call gajor5 (ncol,ca)

c

c

Set up jacobian matrix and rhs vector for pressure only problem.

c

```
rhst(jc) = f(1)
fat(jc) = f(2)
```

```
      ftgt(jc) = f(3)
      ftft(jc) = f(4)
      fxat(jc) = f(5)
      if (jc .eq. 1) then
c
c      Store pressure coefficients for gauss-seidel iteration procedure:
c      axial tri-diagonal only
c      Store pressure coefficients necessary to recover alp, tg,
c      tf, and xa for top cell in the top section. Compute diagonal
c      dominant factor, too.
c
         ddom = abs(cp(1,1))
         if (ddom .ge. one) go to 90
         atml(jc,1) = one
         atml(jc,2) = cp(1,1)
         atml(jc,3) = zero
c
         cpat (2,jc) = cp(2,1)
         cptgt(2,jc) = cp(3,1)
         cptft(2,jc) = cp(4,1)
         cpxat(2,jc) = cp(5,1)
         endif
         if (jc .gt. 1 .and. jc .lt. nzt) then
c
c      Store pressure coefficients for gauss-seidel iteration procedure:
c      axial tri-diagonal only
c      Store pressure coefficients necessary to recover alp, tg,
c      tf, and xa for typical cell in the top section. Compute diagonal
c      dominant factor, too.
c
         atml(jc,1) = one
         atml(jc,2) = cp(1,2)
         atml(jc,3) = cp(1,1)
c
         ddom = zero
         do 50 k = 1,ncp
            ddom = ddom + abs(real(cp(1,k)))
            cpat (k,jc) = cp(2,k)
            cptgt(k,jc) = cp(3,k)
            cptft(k,jc) = cp(4,k)
            cpxat(k,jc) = cp(5,k)
50          continue
         if (ddom .ge. one) go to 90
         endif
         if (jc .eq. nzt) then
c
c      Store pressure coefficients for gauss-seidel iteration procedure:
c      axial tri-diagonal only
c      Store pressure coefficients necessary to recover alp, tg,
c      tf, and xa for the last cell in the top section. Compute diagonal
c      dominant factor, too.
c
         atml(jc,1) = one
         atml(jc,2) = zero
         atml(jc,3) = cp(1,1)
         ddom = abs(cp(1,1))
c
         cpat (1,jc) = cp(2,1)
         cptgt(1,jc) = cp(3,1)
         cptft(1,jc) = cp(4,1)
         cpxat(1,jc) = cp(5,1)
c
         n = 1
         do 70 k = 1,nchn
```

```

      nsub = nx(k)
      do 60 i = 1, nsub
        n = n + 1
        azml(1,i,k,3) = cp(1,n)
        ddom = ddom + abs(real(cp(1,n)))
        cpa(2,1,i,k) = cp(2,n)
        cptg(2,1,i,k) = cp(3,n)
        cptf(2,1,i,k) = cp(4,n)
        cpxa(2,1,i,k) = cp(5,n)
60      continue
70      continue
        if (ddom .ge. one) go to 90
      endif
c
c      End axial mass/energy cell loop (index jc)
c
80 continue
      return
c
c      ERROR detected, pressure problem is not diagonally dominant.
c      Time step will be halved and newton iteration restarted.
c
90 ierr = 1
      return
      end

```

MIKIC

```

      subroutine mikic (qflux,dqdtw,vapor,qchf,qonb,hfc,tchf,twall,
&                      tliq,tgas,tsat,pres,alfa,beta,xair,gliq,ggas,
&                      rho1,rhog,visl,visg,condl,cpl,dhy,arib,ieff,
&                      ribln,ribtk,mwall,hfg,hlsat,hgsat,sigma,
&                      matgas,persat,domiki,dochf,ichf,ilq)
c
c      *****
c      *
c      *   SUBROUTINE mikic
c      *
c      *   THIS ROUTINE COMPUTES SURFACE HEAT FLUX AND THE DERIVATIVE
c      *   WITH RESPECT TO WALL TEMPERATURE FOR LAMINAR AND TURBULENT
c      *   SINGLE-PHASE FORCED CONVECTION WITH SUBCOOLED NUCLEATE
c      *   BOILING (MIKIC AND ROHSENOW).
c      *
c      *   OUTPUT ARGUMENTS:
c      *   qflux - SURFACE HEAT FLUX, W/m**2
c      *   dqdtw - DERIVATIVE OF HEAT FLUX WITH RESPECT TO WALL
c      *           TEMPERATURE
c      *   vapor - VAPOR GENERATION AT WALL, kg/m**2-s
c      *   qchf - CRITICAL HEAT FLUX, W/m**2
c      *   qonb - HEAT FLUX AT ONSET OF NUCLEATE BOILING, W/m**2
c      *   hfc - FORCED CONVECTION OR SINGLE PHASE LIQUID
c      *           HEAT TRANSFER COEFFICIENT, W/m**2-K
c      *   tchf - TEMPERATURE WHERE qchf IS REACHED, K
c      *
c      *   INPUT ARGUMENTS:
c      *   twall - WALL TEMPERATURE, K
c      *   tliq - LIQUID TEMPERATURE, K
c      *   tgas - GAS TEMPERATURE, K
c      *   tsat - SATURATION TEMPERATURE, K
c      *   pres - CELL PRESSURE, Pa
c      *   alfa - GAS BULK VOLUME FRACTION
c      *   beta - LIQUID BULK VOLUME FRACTION
c      *   gliq - LIQUID MASS FLUX, kg/m**2-s
c      *   ggas - GAS MASS FLUX, kg/m**2-s
c      *   rho1 - LIQUID DENSITY, kg/m**3
c
c      *****

```

```

c      *      rhog - GAS DENSITY, kg/m**3      *
c      *      visl - LIQUID VISCOSITY, kg/m-s   *
c      *      visg - GAS VISCOSITY, kg/m-s      *
c      *      condl - LIQUID THERMAL CONDUCTIVITY, W/m-C *
c      *      cpl - LIQUID SPECIFIC HEAT, J/kg-C *
c      *      dhy - CELL HYDRAULIC DIAMETER, m   *
c      *      hfg - LATENT HEAT OF VAPORIZATION, J/kg *
c      *      hlsat - LIQUID SATURATION ENTHALPY, J/kg *
c      *      hgsat - GAS SATURATION ENTHALPY, J/kg *
c      *      sigma - SURFACE TENSION, N/m      *
c      *      matgas - GAS MATERIAL IDENTIFIER, 1=HELIUM, 2=AIR *
c      *      persat - PERCENT SATURATION OF GAS IN LIQUID *
c      *      dochf - FLAG TO INDICATE A CHF CALCULATION *
c      *
c      *      NOTE: tgas AND pres ARE USED TO ACCOUNT FOR LOCAL DISSOLVED *
c      *      GAS IN THE FLUID CELL; THEREFORE, SET matgas=2 IN THE *
c      *      CALL TO SELECT AIR COEFFICIENTS. *
c      *      TO ACCOUNT FOR DISSOLVED HELIUM USE: *
c      *      tgas = BLANKET GAS TEMPERATURE (K), *
c      *      pres = BLANKET GAS PRESSURE (Pa), AND *
c      *      matgas = 1 *
c      *      DISSOLVED GAS EFFECTS CAN BE ELIMINATED BY *
c      *      SETTING persat=0.0 *
c      *
c      *
c      *****
c
c      implicit real (a-h,o-z), integer (i-n)
c
c      parameter (zero=0.0, half=0.5, one=1.0, two=2.0,
c      & three=3.0, four=4.0, ten2=100.0, ten3=1000.0)
c
c      HEAT TRANSFER COEFFICIENT PARAMETERS
c
c      parameter (coefh=2.17e-2, creh=0.80, cprh=0.4,
c      & coefl=6.77e-5, crel=1.50, cprl=0.5,
c      & rnul=4.0)
c      parameter (tcmin=273.15, tcmax=647.15)
c
c      include 'knobs.inc'
c
c      logical first, dochf, domiki
c
c      dimension coefl(8), coef2(12), hn(4), a(6), tk(2)
c
c      save first, a, hn, tk, tsub, hb, pgas, hfqs,
c      & vfqs, fnfg, gamma, sigs, hfct
c
c      HENRY'S LAW COEFFICIENTS
c
c      data coefl/
c      & 0.34527291e+01, 0.87992069e+00, 0.27718148e+00, -0.84275100e-01,
c      & -0.26034660e+01, 0.83240746e+01, -0.26612343e+01, 0.28897693e+00/
c
c      MIKIC-ROHSENOW FULLY DEVELOPED BOILING CURVE COEFFICIENTS
c
c      data coef2/
c      & -0.10201219e+02, 0.90042537e+02, -0.27087881e+03, 0.44721796e+03,
c      & -0.38294426e+03, 0.13526261e+03, -0.18932962e+02, 0.15001543e+03,
c      & -0.42238743e+03, 0.62298006e+03, -0.47386928e+03, 0.15028174e+03/
c
c      data tk/647.14, 643.89/, rmax/1.0e-6/
c      data itmax/10/, toler/1.0/, delal/0.01/
c      data wa/28.97/, ws/18.016/

```



```

      data first/.true./
c
c      STATEMENT FUNCTION DECLARATIONS
c
c      HLC = HENRY'S LAW CONSTANT, PA
c
      hlc(t) = 6.89476e+03*(10.0** (hn(1)+(hn(2)+(hn(3)+hn(4)*t)*t)*t))
c
c      HFDB = MIKIC-ROHSENOW FULLY DEVELOPED BOILING CURVE COEFFICIENT
c            W/(M**2-K**3)
c
      hfdb(t) = exp(a(1)+(a(2)+(a(3)+(a(4)+(a(5)+a(6)*t)*t)*t)*t)
c
c      ON FIRST PASS INITIALIZE THE COEFFICIENT ARRAYS
c
      if (first) then
        mg = 4*(matgas-1)
        do 10 i=1,4
          mgi = mg + i
          hn(i) = coef1(mgi)
10       continue
c
        mf = 6*(ilq-1)
        do 20 i=1,6
          mfi = mf + i
          a(i) = coef2(mfi)
20       continue
        first = .false.
      end if
c
c      CHECK FOR EQUAL TEMPERATURES
c
      if (twall.eq.tliq) return
c
c      CALCULATIONS THAT DEPEND ON FLUID PROPERTIES ALONE
c      ARE PERFORMED ONLY ONE TIME FOR EACH FLUID CELL
c
      if (domiki) then
c
c        COMPUTE THE LIQUID SUBCOOLING
c
          tsub = tsat - tliq
c
c        COMPUTE THE COEFFICIENT TO THE FULLY DEVELOPED BOILING CURVE
c        USING REDUCED SATURATION TEMPERATURE
c
          tsr = tsat/tk(ilq)
          hb = hfdb(tsr)
c
c        COMPUTE THE PARTIAL PRESSURE OF THE NONCONDENSIBLE AT tsat,
c        persat = PERCENT OF SATURATION
c
          if (persat.eq.zero) then
            pgas = zero
          else
c
c        COMPUTE THE LIQUID CONCENTRATION OF THE NONCONDENSIBLE IN SOLUTION
c        tghn = INVERSE OF THE GAS TEMPERATURE X 1000
c
            call psat (tgas,ilq,pgsat,xdum)
            tghn = ten3/tgas
            xcon = (persat/ten2)*(pgsat - pres)/(pgsat - hlc(tghn))
            pgas = xcon*hlc(ten3/tsat)
          end if

```

```
c
c  EVALUATE STEAM PHYSICAL PROPERTIES AT SATURATION
c
c      call rsteam (pres,tsat,ilq,rogs,xlum,xlum)
c      call hssat (pres,ilq,hgs,xlum)
c
c  EVALUATE LIQUID PHYSICAL PROPERTIES AT SATURATION
c
c      call rofsat (tsat,ilq,rofs,xlum)
c      call hfsat (tsat,ilq,hfs,xlum)
c      call surten (tsat,sigs)
c
c  COMPUTE GAMMA TERM IN THE ONB CORRELATION
c  USING FLUID PROPERTIES AT SATURATION
c
c      hfgs = hgs - hfs
c      vfgs = one/rogs - one/rofs
c      fnfg = tsat*vfgs/hfgs
c      gamma = fnfg*pgas
c
c  COMPUTE THE LIQUID SUPERFICIAL REYNOLDS NUMBER
c  AND BULK FLUID PRANDTL NUMBER
c
c      re = glik*dhy/visl
c      pr = cpl*visl/condl
c
c  COMPUTE THE NUSSELT NUMBER FOR TURBULENT SINGLE PHASE
c  FORCED CONVECTION BASED ON SRL DERIVED CORRELATION FOR
c  TWO-PHASE FLOW IN ANNULAR GEOMETRIES
c
c  CHURN-TURBULENT CORRELATION
c
c      coef = xcofh*coefh
c      cre = xreh*creh
c      cpr = cprh
c      ret = re/beta
c      rnut = coef*(ret**cre)*(pr**cpr)
c
c  ANNULAR CORRELATION
c
c      coef = xcofl*coefl
c      cre = xrel*crel
c      cpr = cprl
c      rnua = coef*(re**cre)*(pr**cpr)
c
c  COMBINE CHURN-TURBULENT AND ANNULAR CORRELATIONS
c
c  if (delal.le.zero) then
c      rnu = min(rnua,rnut)
c  else
c      almin = max(zero,ala2-delal)
c      almax = min( one,ala2+delal)
c      wt = (alfa - almin)/(almax - almin)
c      wt = max(wt,zero)
c      wt = min(wt,one)
c      rnu = wt*rnua + (one - wt)*rnut
c  end if
c
c  CHECK IF LAMINAR OR TURBULENT FLOW AND COMPUTE LIQUID
c  FORCED CONVECTION HEAT TRANSFER COEFFICIENT, hfct
c
c      rnu = max(rnu,rnul)
c      hfct = condl*rnu/dhy
c
```

```
        domiki = .false.
    end if

c
c    CALCULATE RIB EFFECTIVENESS CORRECTION TO
c    HEAT TRANSFER COEFFICIENT
c
    if (ieff.eq.0 .or. ribln.eq.zero .or. ribtk.eq.zero) then
        psi = zero
    else
        fk = condn(mwall,twall,zero)
        xl = ribln*sqrt(hfct/(fk*ribtk))
        psi = ribln*tanh(xl)/xl
    end if
    hfc = hfct*(one + arib*(psi - ribtk))

c
    tsurf = twall
    iter = -1

c
30    iter = iter + 1
c
c    COMPUTE THE SINGLE-PHASE LIQUID FORCED CONVECTION HEAT FLUX
c
    delT = tsurf - tliq
    qfc = hfc*delT
    dqcdtw = hfc

c
    if (qfc.le.zero) then
        qflux = qfc
        dqcdtw = dqcdtw
        return
    end if

c
c    COMPUTE THE THERMAL CONDUCTIVITY AT THE WALL TEMPERATURE AND
c    DERIVATIVE OF THE THERMAL CONDUCTIVITY WITH RESPECT TO THE
c    WALL TEMPERATURE
c
    call condnq (tsurf,ilq,tcw,dkdtw)

c
c    COMPUTE SIGMA TERM IN ONB CORRELATION AND NORMALIZED
c    DERIVATIVE OF SIGMA WITH RESPECT TO WALL TEMPERATURE
c
    sig = tcw/(four*sigs*fng*hfc)
    dsqdtw = dkdtw/tcw

c
c    BEGIN ONB CALCULATIONS BASED ON BJORGE AND ROHSENOW METHODOLOGY
c
c    COMPUTE THE HEAT TRANSFER COEFFICIENT AT THE POINT OF TANGENCY
c    FOR Y=RCAV (rmax)
c
    arg = one + two*sig*(tsub - gamma)
    if (arg.gt.zero) then
        darg = sqrt(arg)
        dadtw = (tsub - gamma)/darg
    else
        darg = zero
        dadtw = zero
    end if
    htang = tcw/(rmax*(one + darg))

c
c    COMPARE THE HEAT TRANSFER COEFFICIENT TO HTANG
c
    if (hfc.lt.htang) then

c
c    COMPUTE THE NUSSELT NUMBER AT RCAV (rmax), AND
```

```

c      NORMALIZED DERIVATIVE OF rnucav
c
c      rnucav = hfc*rmax/tcw
c      oncav = one/(one - rnucav)
c      rtnsg = half/(rnucav*sig) - gamma
c      dndtw = -dsgdtw
c
c      COMPUTE - WALL SUPERHEAT AT ONB, dtonb
c      INCIPIENT HEAT FLUX FOR RTANG > RCAV (rmax), qonb
c      DERIVATIVE OF THE INCIPIENT WALL SUPERHEAT, dtdtw
c
c      dtonb = (tsub + rtnsg)*oncav - tsub
c      qonb = hfc*(dtonb + tsub)
c      dtdtw = rnucav*dndtw*(dtonb + tsub)*oncav
c
c      else
c
c      COMPUTE - WALL SUPERHEAT AT ONB, dtonb
c      INCIPIENT HEAT FLUX FOR RTANG <= RCAV (rmax), qonb
c      DERIVATIVE OF THE INCIPIENT WALL SUPERHEAT, dtdtw
c
c      dtonb = (one + darg)/sig - gamma
c      qonb = hfc*(dtonb + tsub)
c      dtdtw = dsgdtw*(dadt - dtonb - gamma)
c
c      end if
c
c      delt = max((tsurf - tsat),zero)
c      dtonb = max(dtonb,zero)
c      dtonb = min(dtonb,delt)
c
c      CALCULATE THE SUBCOOLED NUCLEATE BOILING HEAT FLUX AND ITS
c      DERIVATIVE BY THE SUPERPOSITION METHOD OF MIKIC AND ROHSENOW
c      COMPUTE - FULLY DEVELOPED BOILING HEAT FLUX, qb
c      DERIVATIVE OF qb WITH RESPECT TO WALL TEMPERATURE, dqbdw
c      FULLY DEVELOPED BOILING HEAT FLUX AT ONB, qbi
c      DERIVATIVE OF qbi WITH RESPECT TO WALL TEMPERATURE, dqidw
c      SUBCOOLED NUCLEATE BOILING HEAT FLUX, qsurf, AND ITS
c      DERIVATIVE WITH RESPECT TO THE WALL TEMPERATURE, dqsurf
c
c      qb = hb*(delt**3)
c      dqbdw = three*hb*delt*delt
c      qbi = hb*(dtonb**3)
c      dqidw = three*hb*dtonb*dtonb*dtdtw
c
c      delqb = qb - qbi
c      qsurf = sqrt(qfc*qfc + delqb*delqb)
c      dqsurf = (qfc*dqcdw + delqb*(dqbdw - dqidw))/qsurf
c
c      ON FIRST PASS, SAVE TOTAL SURFACE HEAT FLUX, DERIVATIVE WITH
c      RESPECT TO WALL TEMPERATURE, AND VAPOR GENERATION RATE
c
c      if (iter.eq.0) then
c      qflux = qsurf
c      dqdw = dqsurf
c      vapor = (qflux - qfc)/hfg
c
c      COMPUTE qchf ONCE FOR EACH FLUID CELL
c
c      if (dochf) then
c      call chf (qchf,tliq,tgas,tsat,pres,alfa,beta,ggas,
c      4      gliq,rhol,rhog,visl,visg,condl,cpl,xair,
c      6      dhy,hfg,hlsat,hgsat,sigma,ichf,ilq)
c      dochf = .false.

```

```

        end if
    end if
c
c    NEWTON ITERATION TO FIND tchf
c
    tchf = tsurf + (qchf - qsurf)/dqsurf
    tchf = min(tchf,tcmax)
    tchf = max(tchf,tcmin)
c
    dtchf = abs(tchf - tsurf)
    if (dtchf.le.toler) then
        return
    else if (iter.lt.itmax) then
        tsurf = tchf
        goto 30
    end if
c
    write (*,40) itmax, toler, dtchf
40  format (/, ' newton iteration failed to find tchf',
    &      ' within ',i3,' iterations',/,
    &      ' tolerance = ',g12.5,' error = ',g12.5)
c
    return
end

```

MOVE

```

    subroutine move (a,b,n)
c
c    *****
c    *
c    *   SUBROUTINE MOVE
c    *   THIS SUBROUTINE MOVES n WORDS FROM THE REAL ARRAY a
c    *                               INTO THE REAL ARRAY b
c    *
c    *****
c
    implicit real (a-h,o-z), integer (i-n)
    dimension a(1), b(1)
c
    do 10 i=1,n
        b(i) = a(i)
10  continue
c
    return
end

```

NEWTON

```

    subroutine newton (azm1,azm2,axm1,axm2,rhs,sx,sz,t,dpm,
    &    atml,rhst,st,abml,rhsb,sb,cmesh,
    &    ar,volc,volt,volb,
    &    cpat,cptgt,cptft,cpxat,fat,ftgt,ftft,fxat,dpt,
    &    cpa ,cptg ,cptf ,cpxa ,fa ,ftg ,ftf ,fxa ,dp ,
    &    cpab,cptgb,cptfb,cpxab,fab,ftgb,ftfb,fxab,dpb,
    &    ptn,alptn,xatn,rogt,hgt,roft,hft,tgt,tft,
    &    pt ,alpt ,xat ,rogt ,hgt ,roft ,hft ,tgt ,tft ,
    &    pn ,alpn ,xan ,rogn ,hgn ,rofn ,hfn ,tgn ,tfn ,
    &    p ,alp ,xa ,rog ,hg ,rof ,hf ,tg ,tf ,
    &    pbn,alpb,xab,rogb,hgb,rofb,hfb,tgb,tfb,
    &    git,eit,ysit,hgit,hfit,akgit,
    &    gi ,ei ,ysi ,hgi ,hfi ,akgi ,
    &    gib,eib,ysib,hgib,hfib,akgib,
    &    advbz,advbz,advdx,zdvex,advbt,advct,

```

```

&          advbb, advcb, bgt, bft, cgt, cft, bgz, bfz, cgz, cfz,
&          dgx, dfx, egx, efx, bgb, bfb, cgb, cfb,
&          gw, qwf, qwg, hspl, tsurf,
&          txg, txf, iazl, nazc, nx, nr, icc)

C
C *****
C *
C *      subroutine newton
C *
C *      SUBROUTINE TO PERFORM NEWTON ITERATIONS TO SOLVE FLUID
C *      DYNAMICS EQUATIONS
C *
C *      nitmax = FLAG INDICATING NEWTON ITERATION STRATEGY
C *      nitmax < 0 => CONVERGE TO TOLERANCE epsnt
C *      nitmax > 0 => DO FIXED NUMBER OF ITERATIONS
C *
C *****
C implicit real (a-h,o-z), integer (i-n)
C parameter (zero=0.0)
C
C include 'params.inc'
C
C INNER ARRAYS FOR ALL SECTIONS
C
C dimension azml(nzp2,nxmax,nchn,3), axml(nxmax,nzp2,nchn,3),
&          azm2(nzp2,nxmax,nchn,2), axm2(nxmax,nzp2,nchn,2),
&          sz(2,nzp2,nxmax,nchn),   sx(2,nxmax,nzp2,nchn),
&          rhs(nzp2,nxmax,nchn),
&          dp(nzp2,nxmax,nchn)
C
C dimension dpt(nzt), atml(nzt,3), rhst(nzt), st(2,nzt),
&          dpb(nzb), abml(nzb,3), rhsb(nzb), sb(2,nzb)
C
C dimension t(nlarg), dpm(nlarg), cmesh(nlarg,nchn,3)
C
C MIDDLE SECTION PHYSICAL PARAMETERS
C
C dimension p(nzp2,nxmax,nchn),   pn(nzp2,nxmax,nchn),
&          alp(nzp2,nxmax,nchn),  alpn(nzp2,nxmax,nchn),
&          xa(nzp2,nxmax,nchn),   xan(nzp2,nxmax,nchn),
&          rog(nzp2,nxmax,nchn),  rogn(nzp2,nxmax,nchn),
&          rof(nzp2,nxmax,nchn),  rofn(nzp2,nxmax,nchn),
&          hg(nzp2,nxmax,nchn),   hgn(nzp2,nxmax,nchn),
&          hf(nzp2,nxmax,nchn),   hfn(nzp2,nxmax,nchn),
&          tg(nzp2,nxmax,nchn),   tgn(nzp2,nxmax,nchn),
&          tf(nzp2,nxmax,nchn),   tfn(nzp2,nxmax,nchn)
C
C dimension gi(nzp2,nxmax,nchn),  ei(nzp2,nxmax,nchn),
&          ysi(nzp2,nxmax,nchn),  akgi(nzp2,nxmax,nchn),
&          hfi(nzp2,nxmax,nchn),  hgi(nzp2,nxmax,nchn)
C
C dimension txg(4,nzp2,nxmax,nchn), txf(4,nzp2,nxmax,nchn)
C
C dimension icc(2,nxmax,nchn), iazl(nxmax,nchn),
&          volc(nzp2,nxmax,nchn), nazc(nxmax,nchn),
&          gw(nzp2,nxmax,nchn),   nx(nchn)
C
C dimension qwf(nsurf,na,nz), ar(nrxmp,nz,ncyln),
&          qwg(nsurf,na,nz),   nr(ncyln),
&          hspl(nsurf,na,nz), tsurf(nsurf,na,nz)
C
C TOP SECTION PHYSICAL PARAMETERS
C
C dimension pt(nzt),   ptn(nzt),   git(nzt),

```

```

&      alpt(nzt), alptn(nzt),  eit(nzt),
&      xat(nzt),  xatn(nzt),  ysit(nzt),
&      rogt(nzt), rogtn(nzt),
&      roft(nzt), roftn(nzt),  volt(nzt),
&      hgt(nzt),  hgtn(nzt),  hgit(nzt),
&      hft(nzt),  hftn(nzt),  hfit(nzt),
&      tgt(nzt),  tgtn(nzt),  akgit(nzt),
&      tft(nzt),  tftn(nzt)

```

c
c
c

BOTTOM SECTION PHYSICAL PARAMETERS

```

dimension pb(nzb),  pbn(nzb),  gib(nzb),
&      alpb(nzb), alpbn(nzb),  eib(nzb),
&      xab(nzb),  xabn(nzb),  ysib(nzb),
&      rogb(nzb), rogbn(nzb),
&      rofb(nzb), rofbn(nzb),  volb(nzb),
&      hgb(nzb),  hgbn(nzb),  hgib(nzb),
&      hfb(nzb),  hfbn(nzb),  hfib(nzb),
&      tgb(nzb),  tgbn(nzb),  akgib(nzb),
&      tfb(nzb),  tfbn(nzb)

```

c
c
c

COEFFICIENT ARRAYS FOR OTHER FLUID PROPERTIES (MIDDLE SECTION)

```

dimension fa(nzp2,nxmax,nchn),  cpa(4,nzp2,nxmax,nchn),
&      ftg(nzp2,nxmax,nchn),  cptg(4,nzp2,nxmax,nchn),
&      ftf(nzp2,nxmax,nchn),  cptf(4,nzp2,nxmax,nchn),
&      fxa(nzp2,nxmax,nchn),  cpxa(4,nzp2,nxmax,nchn)

```

c
c
c

COEFFICIENT ARRAYS FOR OTHER FLUID PROPERTIES (TOP SECTION)

```

dimension fat(nzt),  cpat(2,nzt),
&      ftgt(nzt),  cptgt(2,nzt),
&      ftft(nzt),  cptft(2,nzt),
&      fxat(nzt),  cpxat(2,nzt)

```

c
c
c

COEFFICIENT ARRAYS FOR OTHER FLUID PROPERTIES (BOTTOM SECTION)

```

dimension fab(nzb),  cpab(2,nzb),
&      ftgb(nzb),  cptgb(2,nzb),
&      ftfb(nzb),  cptfb(2,nzb),
&      fxab(nzb),  cpxab(2,nzb)

```

c
c
c

DONOR COEFFICIENT ARRAYS FOR JACOB (MIDDLE SECTION)

```

dimension advbz(nzp3,nxmax,nchn,5),
&      advcz(nzp3,nxmax,nchn,5),
&      advdx(nzp2,nxmax,nchn,5),
&      advex(nzp2,nxmax,nchn,5)

```

c
c
c

VELOCITY COEFFICIENT ARRAYS (MIDDLE SECTION)

```

dimension dgx(nzp2,nxmax,nchn),  egx(nzp2,nxmax,nchn),
&      dfx(nzp2,nxmax,nchn),  efx(nzp2,nxmax,nchn),
&      bgz(nzp3,nxmax,nchn),  cgz(nzp3,nxmax,nchn),
&      bfz(nzp3,nxmax,nchn),  cfz(nzp3,nxmax,nchn)

```

c
c
c

DONOR COEFFICIENT ARRAYS FOR JACOB (TOP AND BOTTOM SECTIONS)

```

dimension advbt(nzt,5),  advbb(nzb,5),
&      advct(nzt,5),  advcb(nzb,5)

```

c
c
c

VELOCITY COEFFICIENT ARRAYS (TOP AND BOTTOM SECTIONS)

```

dimension bgt(nzt),  bgb(nzb),

```

```

      6      bft(nzt), bfb(nzb),
      6      cgt(nzt), cgb(nzb),
      6      cft(nzt), cfb(nzb)
c
c      BEGIN NEWTON ITERATION
c
      ierr = 0
      iitot = 0
      limit = abs(nitmax)
      do 100 it=1,limit
      nitno = it
c
c      SET UP JACOBIAN MATRIX FOR TOP SECTION
c
      call jacobt (ptn,alptn,tgtn,tftn,xatn,rogtn,roftn,hgtn,hftn,
      6      pt ,alpt ,tgt ,tft ,xat ,rogt ,roft ,hgt ,hft ,
      6      git,eit ,hfit,hgit ,akgit,ysit,
      6      ppl,p,rdelt,factor,
      6      atml,rhst,azml,
      6      cpat,cptgt,cptft,cpxat,fat,ftgt,ftft,fxat,
      6      cpa ,cptg ,cptf ,cpxa ,
      6      volt,advbt,advct,advbz,advcz,
      6      xa0,epsy,epsf,nitysi,
      6      nzt,nzp2,nzp3,nchn,nxmax,nx,igami,ierr,ilq)
      if (ierr.eq.1) return
c
c      SET UP JACOBIAN MATRIX FOR MIDDLE SECTION
c
      call jacobm (pn,alpn,tgn,tfn,xan,rogn,rofn,hgn,hfn,
      6      p ,alp ,tg ,tf ,xa ,rog ,rof ,hg ,hf ,
      6      gi,e1 ,hfi,hgi ,akgi,ysi,gw,hspl,
      6      rdelt,factor,
      6      azml,azm2,rhs,qwg,qwf,tsurf,ar,
      6      cpa,cptg,cptf,cpxa,fa,ftg,ftf,fxa,
      6      volc,advbz,advcb,advdx,advex,txg,txf,
      6      xa0,epsy,epsf,nitysi,
      6      iaz1,nazc,na,napl,nr,nrmxp,nz,nsurf,icent,
      6      nzpl,nzp2,nzp3,nchn,nxmax,nx,ncyl,icc,
      6      igami,igamw,ierr,ilq)
      if (ierr.eq.1) return
c
c      SET UP JACOBIAN MATRIX FOR BOTTOM SECTION
c
      call jacobbb (pbn,alpb,tgbn,tfbn,xabn,rogbn,rofbn,hgbn,hfbb,
      6      pb ,alpb ,tgb ,tfb ,xab ,rogb ,rofb ,hgb ,hfb ,
      6      gib,eib ,hfib,hgib ,akgib,ysib,
      6      ptb,p,rdelt,factor,
      6      abml,rhsb,azml,
      6      cpab,cptgb,cptfb,cpxab,fab,ftgb,ftfb,fxab,
      6      cpa ,cptg ,cptf ,cpxa ,
      6      volb,advbb,advcb,advbz,advcz,
      6      xa0,epsy,epsf,nitysi,
      6      nzb,nzp2,nzp3,nchn,nxmax,nx,igami,ierr,ilq)
      if (ierr.eq.1) return
c
c      SET UP AZIMUTHAL COUPLING ARRAYS IN MIDDLE SECTION AND
c      ELIMINATE COUPLING TERMS AT TOP AND BOTTOM OF AXIAL ARRAY
c
      do 30 ic=1,nchn
      nsub = nx(ic)
      do 20 ix=1,nsub
      do 10 jz=1,nzp2
      axml(ix,jz,ic,1) = azml(jz,ix,ic,1)
      axml(ix,jz,ic,2) = azm2(jz,ix,ic,2)

```



```

      axm1(ix,jz,ic,3) = azm2(jz,ix,ic,1)
      axm2(ix,jz,ic,1) = azm1(jz,ix,ic,3)
      axm2(ix,jz,ic,2) = azm1(jz,ix,ic,2)
10      continue
      azm1( 1,ix,ic,3) = zero
      azm1( 2,ix,ic,3) = zero
      azm1(nzp1,ix,ic,2) = zero
      azm1(nzp2,ix,ic,2) = zero
20      continue
30      continue
c
c      SOLVE FOR NEW PRESSURE INCREMENTS
c
      call inner (dp,axm1,axm2,azm1,azm2,rhs,sz,sx,
&      dpt,atml,rhst,st,dpb,abml,rhsb,sb,
&      t,dpm,icc,cmesh,nx,nxmax,nz,nzp1,nzp2,
&      nzt,nzb,nchn,nlarg,epsin,errin,pref,
&      initmx,initct,ischem,irebal,ncmr,ierr)
      if (ierr.eq.1) return
      iitot = iitot + initct
c
c      UPDATE FLUID PROPERTIES
c
      call updatp (cpat,cptgt,cptft,cpxat,fat,ftgt,ftft,fxat,dpt,
&      cpa ,cptg ,cptf ,cpxa ,fa ,ftg ,ftf ,fxa ,dp ,
&      cpab,cptgb,cptfb,cpxab,fab,ftgb,ftfb,fxab,dpb,
&      pt,alpt,tgt,tft,xat,rogt,hgt,roft,hft,
&      p ,alp ,tg ,tf ,xa ,rog ,hg ,rof ,hf ,
&      pb,alpb,tgb,tfb,xab,rogb,hgb,rofb,hfb,
&      ppl,alptn,bgt,cgt,bft,cft,advbt,advct,
&      alpn ,bgz,cgz,dgx,egx,bfz,cfz,dfx,efx,
&      advbz,advbz,advdx,advex,
&      ptb,alpb,bgb,cgb,bfb,cfb,advbb,advcb,
&      factor,nzt,nzp1,nzp2,nzp3,nxmax,nchn,nx,icc,nzb,
&      ierr,errp,erralp,errtg,errtf,errxa,ilq)
      if (ierr.eq.1) return
      if (nitmax.eq.1) return
c
c      TEST ERRORS IN p, alp, tg, tf, AND xa
c
      if (errp .le. epsp .and. erralp .le. epsalp .and.
&      errtg .le. epstg .and. errtf .le. epstf .and.
&      errxa .le. epsxa) return
100      continue
c
      if (nitmax.lt.0) then
        write (*,150) limit, errp, erralp, errtg, errtf, errxa
150        format (/, ' newton iteration failed to converge in ',
&      i3, ' iterations', /' errors = ', 1pe8.2, ' p ',
&      1pe8.2, ' alp ', 1pe8.2, ' tg ',
&      1pe8.2, ' tf ', 1pe8.2, ' xa ')
        ierr = 1
      end if
c
      return
end

```

PDIST

```

      subroutine pdist (pows,sumdry,tnklev,axial,axal0,deldry,deldmod,
&      dz,hactiv,izht,izhb,gap,asypwr,tsec,bigm,bigmw,
&      bigmd,xtp,ytp,ztp,ntp,intp,itpe,ifissn,itnklv,
&      tnklv0,imodh,idryh,iconh,iexp,init,na,ncyl,nr,
&      nz,nrmax,ntpmax,ntptot,nspln,nout)
c

```

```

C=====
C      UNFOLD DETAILED POWER DISTRIBUTION -- COMPUTE DEPOSITED POWER
C=====
C
C      ARGUMENTS:
C      O   pows - DEPOSITED POWER IN METAL NODE FOR THIS TIME STEP (W)
C      O   sumdry - SUMMATION OF Z*dz FOR EXPERIMENTAL RIGS
C      O   tnklev - TANK LEVEL FOR THIS TIME STEP (m)
C      I   axial - AXIAL POWER SHAPE AT CURRENT TIME
C      I   axal0 - AXIAL POWER SHAPE AT t=0.0
C      I   deldry - DRY TANK FRACTION OF POWER DUE TO DECAY HEAT
C      I   delmod - MODERATED TANK FRACTION OF POWER DUE TO DECAY HEAT
C      I   dz - AXIAL MESH SIZE BY LEVEL (m)
C      I   hactiv - ACTIVE HEIGHT OF CORE (m)
C      I   izht - INDEX OF TOP AXIAL CELL IN ACTIVE CORE
C      I   izhb - INDEX OF BOTTOM AXIAL CELL IN ACTIVE CORE
C      I   gap - DISTANCE FROM BOTTOM OF CORE TO TANK BOTTOM (m)
C      I   asypwr - PRE-INCIDENT ASSEMBLY POWER (W)
C      I   tsec - TIME AT MIDDLE OF TIME STEP (s)
C      I   bigm - PRECOMPUTED METAL ARRAY, radshape*azimshape*area
C               FOR FISSION POWER
C      I   bigmw - SAME AS bigm BUT FOR WET TANK DECAY POWER SHAPE
C      I   bigmd - SAME AS bigm BUT FOR DRY TANK DECAY POWER SHAPE
C      I   xtp - ABSCISSA VALUES FOR SPLINE DATA
C      I   ytp - ORDINATE VALUES FOR SPLINE DATA
C      I   ztp - SPLINE COEFFICIENTS
C      I   ntp - ARRAY CONTAINING NUMBER OF DATA POINTS IN SPLINE FITS
C      I   intp - ARRAY OF POINTERS TO START OF DATA SETS
C      I   itype - ARRAY CONTAINING TYPE OF SPLINE
C      I   ifissn - POINTER TO SPLINE COEFFICIENTS FOR FISSION RELATIVE
C               POWER SPLINE
C      I   itnklv - POINTER TO SPLINE COEFFICIENTS FOR TANK LEVEL SPLINE
C      I   tnklv0 - INITIAL TANK LEVEL (m)
C      I   imodh - POINTER TO SPLINE COEFFICIENTS FOR MODERATED DECAY
C               HEAT SPLINE
C      I   idryh - POINTER TO SPLINE COEFFICIENTS FOR DRY DECAY HEAT SPLINE
C      I   iconh - POINTER TO SPLINE COEFFICIENTS FOR CONSERVATIVE DECAY HEAT
C      I   iexp - MODE FLAG (0=REACTOR LIMIT, 1=EXPERIMENTAL MOCK-UP)
C      I   init - INITIAL PASS FLAG (0, NO; 1, YES)
C      I   na - NUMBER OF AZIMUTHAL DIRECTIONS
C      I   ncyln - NUMBER OF CYLINDRICAL TUBES
C      I   nr - NUMBER OF RADIAL DIVISIONS BY CYLINDER
C      I   nz - NUMBER OF AXIAL LEVELS
C      I   nrmax - MAX NUMBER OF RADIAL NODES IN ANY CYLINDER
C      I   ntpmax - MAXIMUM NUMBER OF POINTS IN A SPLINE
C      I   ntptot - TOTAL NUMBER OF SPLINE DATA POINTS
C      I   nspln - NUMBER OF SPLINES USED
C      I   nout - WRITE FILE UNIT NUMBER
C
C      *****
C
C      implicit real (a-h,o-z), integer (i-n)
C      parameter (zero=0.0, one=1.0, toler=1.0e-5)
C
C      dimension pows(nrmax,na,nz,ncyln), nr(ncyln),
C      &          bigm(nrmax,na,ncyln), axial(nz,3),
C      &          bigmw(nrmax,na,ncyln), axal0(nz),
C      &          bigmd(nrmax,na,ncyln), dz(nz)
C
C      dimension xtp(ntptot), ytp(ntpmax,nspln), ztp(ntpmax,nspln),
C      &          intp(nspln), itype(nspln), ntp(nspln)
C
C      IF TOTAL ASSEMBLY POWER IS ZERO, ZERO pows ARRAY AND RETURN
C

```

```

      if (asypwr.eq.zero) then
        call clear(pows,nrmax*na*nz*ncyln)
        return
      end if
c
c
c   EVALUATE TIME-DEPENDENT AMPLITUDE FACTORS:
c
c   fdkdry, DRY TANK DECAY HEAT.  NOTE--FOR THE EXPERIMENTAL
c   MOCK-UP MODE, THIS PROVIDES NORMALIZED POWER VS TIME
c   fdkmod, MODERATED TANK DECAY HEAT
c   fdkcon, CONSERVATIVE DELTA-MULTIPLIER
c   ffissn, FISSION HEAT
c   tnklelev, TANK LEVEL
c   hrat , NORMALIZED TANK LEVEL RATIO: (tnklelev - gap)/hactiv
c
      if (iexp.eq.1) then
        deldry = one
        delmod = zero
        fdkmod = zero
        fdkcon = one
        ffissn = zero
        tnklelev = zero
        hrat = zero
      else
        inx = intp(imodh)
        ityp = itype(imodh)
        ntps = ntp(imodh)
        fdkmod = yvalu(ityp,ntps,xtp(inx),ytp(1,imodh),
          & ztp(1,imodh),tsec)
c
        inx = intp(iconh)
        ityp = itype(iconh)
        ntps = ntp(iconh)
        fdkcon = yvalu(ityp,ntps,xtp(inx),ytp(1,iconh),
          & ztp(1,iconh),tsec)
c
        inx = intp(ifissn)
        ityp = itype(ifissn)
        ntps = ntp(ifissn)
        ffissn = yvalu(ityp,ntps,xtp(inx),ytp(1,ifissn),
          & ztp(1,ifissn),tsec)
c
        inx = intp(itnklelev)
        ityp = itype(itnklelev)
        ntps = ntp(itnklelev)
        tnklelev = tnklelev0*yvalu(ityp,ntps,xtp(inx),ytp(1,itnklelev),
          & ztp(1,itnklelev),tsec)
        hrat = (tnklelev - gap)/hactiv
      end if
      inx = intp(idryh)
      ityp = itype(idryh)
      ntps = ntp(idryh)
      fdkdry = yvalu(ityp,ntps,xtp(inx),ytp(1,idryh),
        & ztp(1,idryh),tsec)
c
c   COMPUTE TOTAL ASSEMBLY POWER PER EQN 1 OF TF-34
c
      if (hrat.gt.one) hrat = one
      if (hrat.lt.zero) hrat = zero
      term1 = asypwr*(one - delmod*fdkcon)*hrat*ffissn
      term2 = asypwr*delmod*fdkcon*hrat*fdkmod
      term3 = asypwr*deldry*fdkcon*(one - hrat)*fdkdry
      apowr = term1 + term2 + term3
c
      write (nout,690) init, tsec, apowr, asypwr,

```

```
c      6      term1, term2, term3
c
c      IF IN EXPERIMENTAL MOCK-UP MODE, NEED DETERMINE SUMMATION OVER
c      PRODUCT OF AXIAL POWER SHAPE AND CELL LENGTH ONLY ON INITIAL
c      ENTRY SINCE POWER SHAPE FACTORS ARE TIME INDEPENDENT
c
c      if (init.eq.0 .and. iexp.eq.1) goto 310
c
c      ZERO OUT SUMMATIONS OF Z*dz FOR EACH COMPONENT OF DEPOSITED POWER
c
c      sumfis = zero
c      summod = zero
c      sumdry = zero
c
c+++++
c      DETERMINE SUMMATIONS OVER PRODUCT OF AXIAL FLUX SHAPE AND CELL
c      LENGTH FOR THE FISSION, MODERATED DECAY, AND DRY DECAY POWER
c      COMPONENTS.  SEE EQNS 6, 8 AND 9 OF TF-34.
c+++++
c
c      LOOP OVER AXIAL LEVELS
c
c      topnod = hactiv + gap
c
c      do 300 iz=izht,izhb
c
c      EXTRACT AXIAL POWER SHAPE
c
c          faxl = axial(iz,3)
c          faxl0 = axal0(iz)
c
c      FIND AXIAL EXTENT OF NODE AND CLASSIFY IT
c      IF EXPERIMENTAL MOCK-UP MODE, GO TO DRY TANK FORM
c
c          botnod = topnod - dz(iz)
c          if (iexp.eq.1 .or. botnod.ge.tnklev) then
c
c=====
c      NODE IN DRY TANK REGION
c=====
c
c      DO SUMMATION OF Z*dz
c
c          sumdry = sumdry + faxl0*dz(iz)
c
c          else if (topnod.le.tnklev) then
c
c=====
c      NODE IN WET TANK REGION
c=====
c
c      DO SUMMATION OF Z*dz
c
c          sumfis = sumfis + faxl*dz(iz)
c          summod = summod + faxl0*dz(iz)
c
c      else
c
c=====
c      TANK LEVEL WITHIN NODE
c=====
c
c      COMPUTE WET AND DRY AXIAL LENGTHS WITHIN NODE
c
```

```

      dzwet = tnklev - botnod
      dzdry = topnod - tnklev
c
c      DO SUMMATION OF Z*dz
c
      sumfis = sumfis + faxl*dzwet
      summod = summod + faxl0*dzwet
      sumdry = sumdry + faxl0*dzdry
c
      end if
      topnod = botnod
300  continue
c
310  continue
c
c+++++
c      COMPUTE THE NORMALIZED POWER DISTRIBUTION, CONVERT TO POWER
c      DEPOSITED IN NODE (W)
c+++++
c
c      LOOP OVER AXIAL LEVELS
c
      topnod = hactiv + gap
c
      do 500 iz=izht,izhb
c
c      EXTRACT AXIAL POWER SHAPE
c
      faxl = axial(iz,3)
      faxl0 = axal0(iz)
c
c      FIND AXIAL EXTENT OF NODE AND CLASSIFY IT,
c      IF EXPERIMENTAL MOCK-UP MODE, USE DRY TANK FORM
c
      botnod = topnod - dz(iz)
      if (lexp.eq.1 .or. botnod.ge.tnklev) then
c
c=====
c      NODE IN DRY TANK REGION
c=====
c
      comb = zero
      combw = zero
      combd = term3*faxl0*dz(iz)/sumdry
c
      else if (topnod.le.tnklev) then
c
c=====
c      NODE IN WET TANK REGION
c=====
c
      comb = term1* faxl*dz(iz)/sumfis
      combw = term2*faxl0*dz(iz)/summod
      combd = zero
c
      else
c
c=====
c      TANK LEVEL LIES WITHIN NODE
c=====
c
      comb = term1* faxl*dzwet/sumfis
      combw = term2*faxl0*dzwet/summod
      combd = term3*faxl0*dzdry/sumdry

```

```
        end if
c
c      COMPUTE NODAL POWER DEPOSITION
c
c      LOOP OVER CYLINDERS
c
c        do 430 icyln=1,ncyln
c          nri = nr(icyln)
c
c      LOOP OVER AZIMUTHAL DIVISIONS
c
c        do 420 ia=1,na
c
c      LOOP OVER RADIAL DIVISIONS
c
c        do 410 ir=1,nri
c          pows(ir,ia,iz,icyln) = combw*bigmw(ir,ia,icyln)
c          & + combd*bigmd(ir,ia,icyln)
c          & + comb*bigm(ir,ia,icyln)
c
c        continue
c      continue
c    continue
c    topnod = botnod
c  500 continue
c
c  DOUBLE CHECK THAT NORMALIZATION DONE CORRECTLY
c
c  SUM OVER POWER DEPOSITED IN EACH NODE
c
c  powdep = zero
c
c  LOOP THROUGH THE METAL REGIONS
c
c  LOOP OVER CYLINDERS
c
c  do 750 icyln=1,ncyln
c    nri = nr(icyln)
c
c  LOOP OVER AXIAL LEVELS
c
c    do 745 iz=1,nz
c
c  LOOP OVER AZIMUTHAL DIVISIONS
c
c    do 740 ia=1,na
c
c  LOOP OVER RADIAL DIVISIONS
c
c    do 735 ir=1,nri
c      powdep = powdep + pows(ir,ia,iz,icyln)
c    continue
c  735 continue
c  740 continue
c  745 continue
c  750 continue
c
c  difpow = apowr - powdep
c  if (abs(difpow).gt.abs(toler*apowr)) then
c    write(6,780) tsec, apowr, powdep, difpow
c  end if
c
c  WRITE FORMAT
c
c  780 format ('0normalization test at time = ',g12.5,' sec',/,
c    & ' total power deposition in assembly in time step.... ',
```

```

6      gl2.5,' W',/,
6      ' sum of nodal power deposition in time step..... ',
6      gl2.5,' W',/,
6      ' difference, total minus sum..... ',
6      gl2.5,' W',/)

```

```

C
      return
      end

```

PNORM

```

      subroutine pnorm (bigm,frdim,fazmm,rphi,pfrct,diam,mnrrp,nrp,
6      nrgtm,na,ncyl,nr,nz,nrmax,nrmxp,nreg,nfrst,
6      nlast,nout)

```

```

C
C      *****
C      *
C      * SUBROUTINE pnorm
C      *
C      * SUBROUTINE TO NORMALIZE INITIAL POWER SHAPES, ONLY ASSEMBLY
C      * TYPE DEPENDENT. pfrct AND rphi DEFINE THE POWER SHAPES ON
C      * INPUT, FOR EITHER AT POWER, MODERATED OR DRY TANK CASES.
C      * THE bigm ARRAY CONTAINS THE NECESSARY OUTPUT LATER USED IN
C      * THE pdist ROUTINE.
C      *
C      * ARGUMENTS:
C      * O bigm - PRECOMPUTED METAL ARRAY, vol*radshape*azimshape
C      *          FOR AT-POWER SHAPE
C      * O frdim - UNNORMALIZED RADIAL POWER SHAPE BY RADIAL NODE
C      *          POINT
C      * I na - NUMBER OF AZIMUTHAL DIRECTIONS
C      * I ncyl - NUMBER OF CYLINDRICAL TUBES
C      * I nr - NUMBER OF RADIAL DIVISIONS BY CYLINDER
C      * I nz - NUMBER OF AXIAL LEVELS
C      * I nrmax - MAX. NUMBER OF RADIAL DIVISIONS IN ANY CYLINDER
C      * I nreg - NUMBER OF POWER FRACTION REGIONS IN ASSEMBLY
C      * I nfrst - FIRST NODE IN CORE REGION OF CYLINDER
C      * I nlast - LAST NODE IN CORE REGION OF CYLINDER
C      * I mnrrp - MAX NUMBER OF POINTS IN ANY CYLINDER AT WHICH
C      *          RADIAL POWER SHAPE VALUES ARE GIVEN
C      * I nrp - NUMBER OF POINTS IN CYLINDER AT WHICH RADIAL
C      *          POWER SHAPE VALUES ARE GIVEN
C      * I nrgtm - ASSEMBLY REGION NUMBER BY RADIAL NODE AND
C      *          CYLINDER
C      * I fazmm - UNNORMALIZED AZIMUTHAL POWER SHAPE BY RADIAL NODE
C      *          POINT
C      * I rphi - GIVEN RADIAL POWER SHAPE DISTRIBUTION IN CORE
C      *          CYLINDER
C      * I vols - SOLID MESH CELL VOLUMES
C      * I pfrct - POWER FRACTION BY UP TO 30 DIFFERENT ASSEMBLY
C      *          REGIONS FOR DECAY POWER SHAPE
C      *
C      *****
C
      implicit real (a-h,o-z), integer (i-n)
      parameter (zero=0.0, half=0.5, one=1.0, two=2.0, maxreg=30)
C
      dimension bigm(nrmax,na,ncyl,n)
C
      dimension fazmm(na,ncyl,n), nfrst(ncyl,n),
6      frdim(nrmax,ncyl,n), nlast(ncyl,n),
6      nrgtm(nrmax,ncyl,n), nrp(ncyl,n),
6      diam(nrmxp,ncyl,n), nr(ncyl,n),
6      rphi(mnrrp,ncyl,n)
C

```

```
c      LOCAL ARRAYS
c
      dimension preg(maxreg), pfrcf(maxreg)
      pi = acos(-one)
      da = two*pi/float(na)
c
c      CHECK FIXED ARRAY DIMENSION
c
      if (nreg.gt.maxreg) then
        write (nout,910) nreg
        stop
      end if
c
c      CREATE NON-NORMALIZED NODAL RADIAL POWER SHAPES BY
c      INTERPOLATING IN POLYNOMIAL CREATED FROM GIVEN POWER
c      SHAPE DATA
c
c      FIRST INITIALIZE RADIAL SHAPE FUNCTIONS
c
      do 20 icyln=1,ncyln
        nri = nr(icyln)
        do 10 ir=1,nri
          frdim(ir,icyln) = one
10      continue
20      continue
c
c      COMPUTE DETAILED NODAL SHAPES IN CORE REGION OF CYLINDERS
c
      call radshp (frdim,rphi,diam,ncyln,nrmax,nrmxp,
        nfrst,nlast,mnrrp,nrp,nout)
c
c      CREATE THE PRODUCT AZIMUTHAL*RADIAL SHAPE FUNCTION USED
c      IN PDIST (NEED BE DONE ONLY ONCE, TIME-INDEPENDENT)
c
c      FIRST, NORMALIZE POWER SHAPES TO PRESERVE POWER FRACTIONS
c
c      ZERO OUT REGION POWERS
c
      call clear (preg,nreg)
c
c      LOOP OVER ALL METAL NODES
c
      do 50 icyln=1,ncyln
        nri = nr(icyln)
        if (nri.eq.0) goto 50
c
        do 40 ir=1,nri
          nrg = nrgtm(ir,icyln)
          frad = frdim(ir,icyln)
          rinner = half*diam(ir,icyln)
          router = half*diam(ir+1,icyln)
          area = da*half*(router**2 - rinner**2)
          do 30 ia=1,na
            bigm(ir,ia,icyln) = frad*fazmm(ia,icyln)*area
            preg(nrg) = preg(nrg) + bigm(ir,ia,icyln)
30          continue
40        continue
50      continue
c
c      COMPUTE NORMALIZATION FACTORS BY REGION
c
      do 60 nrg=1,nreg
        if (preg(nrg).eq.zero) then
          if (pfrcf(nrg).ne.zero) write(nout,210) nrg, pfrcf(nrg)
```



```

        else
            preg(nrg) = pfrcf(nrg)/preg(nrg)
        end if
60    continue
c
c    FINALLY, NORMALIZE THE PRODUCT OF RADIAL*AZIMUTHAL SHAPES
c    AND PRECOMPUTE POWER SHAPE * AREA ARRAYS
c
    do 90 icyln=1,ncyln
        nri = nr(icyln)
        if (nri.eq.0) goto 90
c
c    LOOP OVER ALL METAL NODES IN THE CYLINDER
c
        do 80 ir=1,nri
            nrg = nrgtm(ir,icyln)
            do 70 ia=1,na
                bigm(ir,ia,icyln) = bigm(ir,ia,icyln)*preg(nrg)
70        continue
80        continue
90    continue
c
c    WRITE FORMATS
c
210  format(' <<< warning--region ',i3,' has non-zero decay',
        ' power fraction ',g12.5,/, ' >>>', ' but decay',
        ' power shape factors assign zero power here?',/)
c
910  format('0>>>warning--pnorm encountered ',i3,' assembly',
        ' power fraction regions > 30',/, ' >>>need to',
        ' recompile with increased pfrcf array dimension',/)
c
    return
end

```

POINT

```

subroutine point
c
c *****
c *
c * subroutine point
c *
c * SUBROUTINE TO SET UP PROGRAM STORAGE REQUIREMENTS
c *
c *****
c
c implicit real (a-h,o-z), integer (i-n)
c include 'params.inc'
c include 'points.inc'
c
c nsubc = nxmax*nchn
c
c SET POINTERS FOR INTEGER ARRAYS
c
c
c    lnx = 1
c    lnr = lnx + nchn
c    lnrp = lnr + ncyln
c    lnfrst = lnrp + ncyln
c    lnlast = lnfrst + ncyln
c    liorib = lnlast + ncyln
c    lioxid = liorib + ncyln
c
c    licc = lioxid + ncyln
c    liaz1 = licc + 2*nsubc
c    lnazc = liaz1 + nsubc

```

```
      lmat = lnazc + nsubc
c
      lntp = lmat + nrmax*nz*ncyln
      lintp = lntp + nspln
      litype = lintp + nspln
      liaxlp = litype + nspln
      lnrgtm = liaxlp + itime
c
      lichks = lnrgtm + nrmax*ncyln
      lichkc = lichks + nsurf
c
      lenia = lichkc + ncrit
      if (lenia.gt.maxia) then
        write (*,100) lenia, maxia
100      format(' << fatal error >> integer arrays exceed storage',
        ' allocation'/' length of ia() = ',i6,
        ' maximum ia() = ',i6/)
        istop = 1
      else
c
c      CLEAR ia ARRAY
c
        do 10 i=1,lenia
          ia(i) = 0
10      continue
      end if
c
c      SET POINTERS FOR REAL ARRAYS
c
      ncell = nzp2*nxmax*nchn
      nface = nzp3*nxmax*nchn
      nlarg = max(nxmax,nzt+nzp2+nzb)
c
      nrznc = nrmax*na*nz*ncyln
      nrac = nrmax*na*ncyln
      nrzc = nrmax*nz*ncyln
      nac = na*ncyln
      nrc = nrmax*ncyln
      nsaz = nsurf*na*nz
      nmnc = mnrp*ncyln
c
      lpkfac = 1
c
c      INNER PRESSURE SOLUTION ARRAY POINTERS (MIDDLE SECTION)
c
      laxm1 = lpkfac + ncrit
      lazml = laxm1 + 3*ncell
      laxm2 = lazml + 3*ncell
      lazml = laxm2 + 2*ncell
      lrhs = lazml + 2*ncell
      ldp = lrhs + ncell
      lsx = ldp + ncell
      lsx = lsx + 2*ncell
      lt = lsx + 2*ncell
      ldpm = lt + nlarg
      lcmesh = ldpm + nlarg
c
c      INNER PRESSURE SOLUTION ARRAY POINTERS (TOP SECTION)
c
      latml = lcmesh + 3*nlarg*nchn
      lrhst = latml + 3*nzt
      ldpt = lrhst + nzt
      lst = ldpt + nzt
c
```

c INNER PRESSURE SOLUTION ARRAY POINTERS (BOTTOM SECTION)

c

labml = 1st + 2*nzt
lrhsb = labml + 3*nzb
ldpb = lrhsb + nzb
lsb = ldpb + nzb

c

c

FLUID PROPERTY ARRAY POINTERS (MIDDLE SECTION)

c

lp = lsb + 2*nzb
lalp = lp + ncell
lxa = lalp + ncell
lrog = lxa + ncell
lrof = lrog + ncell
ltf = lrof + ncell
ltg = ltf + ncell
lhf = ltg + ncell
lhg = lhf + ncell

c

c

OLD TIME STEP VALUES

c

lpn = lhg + ncell
lalpn = lpn + ncell
lxan = lalpn + ncell
lrogn = lxan + ncell
lrofn = lrogn + ncell
ltfn = lrofn + ncell
ltgn = ltfn + ncell
lhfn = ltgn + ncell
lhgn = lhfn + ncell

c

lfsplt = lhgn + ncell

c

c

FLUID PROPERTY ARRAY POINTERS (TOP SECTION)

c

lpt = lfsplt + nchn
lalpt = lpt + nzt
lxat = lalpt + nzt
lrogt = lxat + nzt
lroft = lrogt + nzt
ltft = lroft + nzt
ltgt = ltft + nzt
lhft = ltgt + nzt
lhgt = lhft + nzt

c

c

OLD TIME STEP VALUES

c

lptn = lhgt + nzt
lalptn = lptn + nzt
lxatn = lalptn + nzt
lrogt = lxatn + nzt
lroftn = lrogt + nzt
ltftn = lroftn + nzt
ltgtn = ltftn + nzt
lhftn = ltgtn + nzt
lhgtn = lhftn + nzt

c

c

FLUID PROPERTY ARRAY POINTERS (BOTTOM SECTION)

c

lpb = lhgt + nzt
lalpb = lpb + nzb
lxab = lalpb + nzb
lrogb = lxab + nzb
lrofb = lrogb + nzb

```
        ltfb = lrofb + nzb
        ltgb = ltfb + nzb
        lhfb = ltgb + nzb
        lhgb = lhfb + nzb
c
c      OLD TIME STEP VALUES
c
        lpbn = lhgb + nzb
        lalpb = lpbn + nzb
        lxabn = lalpb + nzb
        lrogbn = lxabn + nzb
        lrofbn = lrogbn + nzb
        ltfbn = lrofbn + nzb
        ltgbn = ltfbn + nzb
        lhfbn = ltgbn + nzb
        lhgbn = lhfbn + nzb
c
c      FLUID VELOCITY ARRAY POINTERS (MIDDLE SECTION)
c
        lwgx = lhgbn + nzb
        lwfx = lwgx + ncell
        lugz = lwfx + ncell
        lufz = lugz + nface
c
c      FLUID VELOCITY ARRAY POINTERS (TOP SECTION)
c
        lugt = lufz + nface
        luft = lugt + nzt
c
c      FLUID VELOCITY ARRAY POINTERS (BOTTOM SECTION)
c
        lugb = luft + nzt
        lufb = lugb + nzb
c
c      FLUID PRESSURE COEFFICIENT ARRAY POINTERS (MIDDLE SECTION)
c
        ldgx = lufb + nzb
        ldfx = ldgx + ncell
        lbgz = ldfx + ncell
        lbfz = lbgz + nface
        legx = lbfz + nface
        lefx = legx + ncell
        lcgz = lefx + ncell
        lcfz = lcgz + nface
c
c      FLUID PRESSURE COEFFICIENT ARRAY POINTERS (TOP SECTION)
c
        lbgt = lcfz + nface
        lbft = lbgt + nzt
        lcgt = lbft + nzt
        lcft = lcgt + nzt
c
c      FLUID PRESSURE COEFFICIENT ARRAY POINTERS (BOTTOM SECTION)
c
        lbgb = lcft + nzt
        lbfb = lbgb + nzb
        lcgb = lbfb + nzb
        lcfb = lcgb + nzb
c
c      COEFFICIENT ARRAYS FOR OTHER FLUID PROPERTIES (MIDDLE SECTION)
c
        lfa = lcfb + nzb
        lftg = lfa + ncell
        lftf = lftg + ncell
```

```
lfxa = lftf + ncell
lcpa = lfxa + ncell
lcptg = lcpa + 4*ncell
lcptf = lcptg + 4*ncell
lcpa = lcptf + 4*ncell
```

```
c
c COEFFICIENT ARRAYS FOR OTHER FLUID PROPERTIES (TOP SECTION)
c
```

```
lfat = lcpa + 4*ncell
lftgt = lfat + nzt
lftft = lftgt + nzt
lfxat = lftft + nzt
lcpat = lfxat + nzt
lcptgt = lcpat + 2*nzt
lcptft = lcptgt + 2*nzt
lcpa = lcptft + 2*nzt
```

```
c
c COEFFICIENT ARRAYS FOR OTHER FLUID PROPERTIES (BOTTOM SECTION)
c
```

```
lfab = lcpa + 2*nzt
lftgb = lfab + nzb
lftfb = lftgb + nzb
lfxab = lftfb + nzb
lcpab = lfxab + nzb
lcptgb = lcpab + 2*nzb
lcptfb = lcptgb + 2*nzb
lcpab = lcptfb + 2*nzb
```

```
c
c DONOR COEFFICIENT ARRAYS FOR JACOB ROUTINES
c
```

```
ladvbz = lcpab + 2*nzb
ladvcz = ladvbz + 5*nface
ladvdx = ladvcz + 5*nface
ladvex = ladvdx + 5*ncell
```

```
c
ladvbt = ladvex + 5*ncell
ladvct = ladvbt + 5*nzt
```

```
c
ladvbb = ladvct + 5*nzt
ladvcb = ladvbb + 5*nzb
```

```
c
c FLUID GEOMETRIC ARRAY POINTERS (MIDDLE SECTION)
c
```

```
lcosx = ladvcb + 5*nzb
lcosz = lcosx + ncell
lacx = lcosz + nface
lacz = lacx + ncell
laratx = lacz + nface
laratz = laratx + ncell
laxx = laratz + nface
lazz = laxx + ncell
ldeffz = lazz + ncell
ldhx = ldeffz + nface
ldhz = ldhx + ncell
labsrx = ldhz + nface
labsrz = labsrx + ncell
lfldmz = labsrz + nface
lfldcz = lfldmz + nface
lc0bz = lfldcz + nface
lc0sz = lc0bz + nface
lckbz = lc0sz + nface
lcksz = lckbz + nface
lfmltx = lcksz + nface
lfmltz = lfmltx + ncell
```

```
lformx = lfmltz + nface
lformz = lformx + ncell
lfrex = lformz + nface
lfrez = lfrex + ncell
ldz = lfrez + nface
ldxm = ldz + nzp2
ldzm = ldxm + nchn
lvolc = ldzm + nzp3
```

c
c
c

FLUID GEOMETRIC ARRAY POINTERS (TOP SECTION)

```
lcost = lvolc + ncell
lact = lcost + nzt
laratt = lact + nzt
lazt = laratt + nzt
ldefft = lazt + nzt
ldht = ldefft + nzt
labsrt = ldht + nzt
lfldmt = labsrt + nzt
lfldct = lfldmt + nzt
lc0bt = lfldct + nzt
lc0st = lc0bt + nzt
lckbt = lc0st + nzt
lckst = lckbt + nzt
lfmltt = lckst + nzt
lformt = lfmltt + nzt
lfret = lformt + nzt
ldzt = lfret + nzt
ldzmt = ldzt + nzt
lvolt = ldzmt + nzt
```

c
c
c

FLUID GEOMETRIC ARRAY POINTERS (BOTTOM SECTION)

```
lcosb = lvolt + nzt
lacb = lcosb + nzb
laratb = lacb + nzb
lazb = laratb + nzb
ldeffb = lazb + nzb
ldhb = ldeffb + nzb
labsrb = ldhb + nzb
lflldb = labsrb + nzb
lflddb = lflldb + nzb
lc0bb = lflddb + nzb
lc0sb = lc0bb + nzb
lckbb = lc0sb + nzb
lcksb = lckbb + nzb
lfmltb = lcksb + nzb
lformb = lfmltb + nzb
lfreb = lformb + nzb
ldzb = lfreb + nzb
ldzmb = ldzb + nzb
lvolb = ldzmb + nzb
```

c
c
c

POINTERS FOR ARRAYS TO HOLD SECTION INLET VALUES

```
lacin = lvolb + nzb
lrogin = lacin + nsubc
lrofin = lrogin + nsubc
lalpin = lrofin + nsubc
lugin = lalpin + nsubc
lufin = lugin + nsubc
```

c
c
c

POINTERS FOR ARRAYS TO HOLD SECTION OUTLET VALUES

```
    lacex = lufin  + nsubc
    lrogex = lacex  + nsubc
    lrofex = lrogex + nsubc
    lalpex = lrofex + nsubc
    lugex  = lalpex + nsubc
    lufex  = lugex  + nsubc
c
c    POINTERS TO INTERFACIAL DRAG COEFFICIENT ARRAYS
c
    lcitn = lufex + nsubc
    lcixn = lcitn + nzt
    lcizn = lcixn + nface
    lcibn = lcizn + nface
c
c    POINTERS TO TURBULENT EXCHANGE ARRAYS
c
    ltxg = lcibn + nzb
    ltxf = ltxg + 4*ncell
c
c    POINTERS TO INTERFACIAL HEAT AND MASS TRANSFER ARRAYS
c    (MIDDLE SECTION)
c
    lhgi = ltxf + 4*ncell
    lhfi = lhgi + ncell
    lakgi = lhfi + ncell
    lysi = lakgi + ncell
    lei = lysi + ncell
    lgi = lei + ncell
c
c    POINTERS TO INTERFACIAL HEAT AND MASS TRANSFER ARRAYS
c    (TOP SECTION)
c
    lhgit = lgi + ncell
    lhfit = lhgit + nzt
    lakgit = lhfit + nzt
    lysit = lakgit + nzt
    leit = lysit + nzt
    lgit = leit + nzt
c
c    POINTERS TO INTERFACIAL HEAT AND MASS TRANSFER ARRAYS
c    (BOTTOM SECTION)
c
    lhgib = lgit + nzt
    lhfib = lhgib + nzb
    lakgib = lhfib + nzb
    lysib = lakgib + nzb
    leib = lysib + nzb
    lgib = leib + nzb
c
c    POINTERS TO SOLID GEOMETRY ARRAYS
c
    lwt = lgib + nzb
    lribl = lwt + ncyln
    lribt = lribl + ncyln
    ldiam = lribt + ncyln
    ldr = ldiam + nrc + ncyln
    lar = ldr + nrc
    lradc = lar + nrzc + nz*ncyln
    lvols = lradc + nrc
    lzfacm = lvols + nrzc
c
c    POINTERS TO SOLID PROPERTY ARRAYS
c
    lts = lzfacm + nrc
```

```
      ltsn = lts   + nrzsc
      lpows = ltsn  + nrzsc
c
c   POINTERS TO SURFACE PROPERTY ARRAYS
c
      ltsurf = lpows + nrzsc
      ltsrfn = ltsurf + nsaz
      ltwhld = ltsrfn + nsaz
      lqwf = ltwhld + nsaz
      lqwg = lqwf + nsaz
      ldqfdw = lqwg + nsaz
      ldqgdw = ldqfdw + nsaz
      lhspl = ldqgdw + nsaz
      lqonb = lhspl + nsaz
c
c   POINTERS TO FLUID CELL HEAT TRANSFER ARRAYS
c
      ltheta = lqonb + nsaz
      lchfq = ltheta + ncell
      lgw = lchfq + ncell
c
c   POINTERS TO POWER ARRAYS
c
      lpfrct = lgw + ncell
      lpfrdd = lpfrct + 30
      lpfrdw = lpfrdd + 30
      lrphi = lpfrdw + 30
      lrphdd = lrphi + nmnc
      lrphdw = lrphdd + nmnc
c
      lrdz = lrphdw + nmnc
      laxial = lrdz + nz
      laxal0 = laxial + 3*nz
c
      lfazmm = laxal0 + nz
      lfrdim = lfazmm + nac
c
      lbigm = lfrdim + nrc
      lbigmw = lbigm + nrac
      lbigmd = lbigmw + nrac
      ltimet = lbigmd + nrac
c
c   POINTERS FOR SPLINE COEFFICIENT ARRAYS
c
      lxtp = ltimet + itime
      lytp = lxtp + ntptot
      lztp = lytp + ntpmax*nspln
      lwh = lztp + ntpmax*nspln
      lwb = lwh + ntpmax
      lwu = lwb + ntpmax
      lwv = lwu + ntpmax
c
      lena = lwv + ntpmax
      if (lena.gt.maxa) then
        write (*,200) lena, maxima
200      format(' << fatal error >> real arrays exceed storage',
        ' allocation/' length of a() = ',i6,
        ' maximum a() = ',i6/)
        istop = 1
      else
c
c   CLEAR a ARRAY
c
        call clear (a(1),lena)
```



```

      end if
c
      return
      end

```

POWER

```

      subroutine power (asypwr,tolpow,critr,tcrit,lcrit,ichkc,iredo,
c
c          ncrit,maxpi,icmax,ipmax,ip,iquit,nout)
c
c          *****
c          *
c          *   SUBROUTINE power
c          *
c          *   SUBROUTINE TO PERFORM INTERPOLARION TO OBTAIN A NEW GUESS
c          *   FOR THE PRE-INCIDENT ASSEMBLY POWER AND TO CHECK FOR
c          *   CONVERGENCE OF THE POWER ITERATION SCHEME
c          *
c          *****
c
c          implicit real (a-h,o-z), integer (i-n)
c
c          double precision aa,bb,cc,c1,c2,c3,ckw,disc,d1,d2,f1,f2,f3,
c
c          p,p1,p2,p3,powest,root1,root2,temp,
c
c          zero,half,one,four
c
c          parameter (zero=0.0, half=0.5, one=1.0, four=4.0)
c          parameter (zeros=0.0, halves=0.5)
c          parameter (pbig=1.0e12, ipwr=20, ckw=0.001)
c          logical iquit
c
c          dimension critr(icmax,ipmax), lcrit(3,icmax,ipmax),
c
c          tcrit(icmax,ipmax), ichkc(ncrit)
c
c          LOCAL ARRAY TO HOLD POWER ITERATION VALUES
c
c          dimension p(ipwr)
c
c          DO NOT PERFORM POWER ITERATIONS FOR ZERO INITIAL POWER
c
c          if (asypwr.eq.zeros) then
c              write (nout,250)
c              iquit = .true.
c              return
c          end if
c
c          IF PREVIOUS POWER LEVEL RESULTED IN TSAT OR FLOODING
c          CRITERIA BEING EXCEEDED THEN REDO THE TRANSIENT
c
c          if (iredo.eq.1) then
c              if (ip.eq.1) then
c                  asypwr = halves*asypwr
c              else
c                  asypwr = halves*(asypwr + p(ip-1))
c              end if
c              do 5 ic=1,ncrit
c                  critr(ic,ip) = zero
c          5          continue
c              return
c          end if
c
c          BEGIN CALCULATION OF MAXIMUM PREINCIDENT POWER:
c          FIRST UPDATE SOLUTION AND PRINT LAST RESULT
c
c          p(ip) = asypwr
c          write (*,200) ip-1, p(ip)*ckw, (critr(ic,ip), ic=1,ncrit),
c
c          (tcrit(ic,ip), ic=1,ncrit)

```

```

      critm = zeros
      do 10 ic=1,ncrit
        critm = max(critm,ichkc(ic)*critr(ic,ip))
10    continue
c
c    CHECK FOR CONVERGENCE OR FAILURE OF ITERATION SEQUENCE
c
      if (maxpi.eq.1) then
        write (nout,*) ' no power search requested'
        goto 110
      else if (abs(critm-one).le.tolpow) then
        write (nout,*) ' power search converged'
        write (*,*) ' power search converged'
        goto 110
      else if (ip.gt.maxpi) then
        write (nout,*) ' power search failed'
        goto 110
      else if (iredo.eq.-1) then
        write (nout,*) ' power search ending'
        goto 110
      end if
c
      powest = pbig
      if (ip.eq.1) then
c
c    OBTAIN SECOND ESTIMATE OF POWER ASSUMING:
c    A LINEAR DEPENDENCE FOR TSAT AS RATIO=C*POWER
c    OR A QUADRATIC DEPENDENCE FOR ONB AS RATIO=C*POWER**2
c
        do 20 ic=1,ncrit
          if (ichkc(ic).eq.1) then
            temp = p(1)/critr(ic,1)
            powest = min(powest,temp)
          end if
20    continue
c
      else
c
c    BEGIN QUADRATIC ITERATIONS FOR POWER
c      ic=1 --> TSAT POWER
c      ic=2 --> ONB POWER
c
      do 30 ic=1,ncrit
        if (ichkc(ic).eq.1) then
          p1 = one
          p2 = p(ip-1)/p(ip)
c
          c1 = critr(ic,ip)
          c2 = critr(ic,ip-1)
c
          if (ip.eq.2) then
            p3 = zero
            c3 = zero
          else
            p3 = p(ip-2)/p(ip)
            c3 = critr(ic,ip-2)
          end if
c
          f1 = c1/((p1 - p2)*(p1 - p3))
          f2 = c2/((p2 - p1)*(p2 - p3))
          f3 = c3/((p3 - p1)*(p3 - p2))
c
          aa = f1 + f2 + f3
          bb = - f1*(p2 + p3) - f2*(p1 + p3) - f3*(p1 + p2)

```

```

      cc = f1*p2*p3 + f2*p1*p3 + f3*p1*p2 - one
      disc = bb*bb - four*aa*cc
C
C      IF NO REAL ROOTS DEFAULT TO LINEAR ITERATION
C
      if (disc.lt.zero) then
        temp = (p1*(one - c2) - p2*(one - c1))/(c1 - c2)
      else
        temp = half*(-bb + sqrt(disc))/aa
      endif
      temp = temp*p(ip)
      powest = min(powest,temp)
    endif
30    continue
  end if
  asypwr = powest
  return
C
C      ITERATION HAS CONVERGED OR FAILED TO CONVERGE, NO
C      POWER ITERATION WAS REQUESTED, OR INITIAL POWER WAS ZERO
C      FOR ALL CASES FLAG THE CODE TO STOP AND PRINT RESULTS
C
110  iquit = .true.
      write (nout,210)
      write (nout,220) (j-1, p(j)*ckw, (critr(ic,j),ic=1,ncrit), j=1,ip)
      write (nout,230) (j-1, (tcrit(ic,j),ic=1,ncrit), j=1,ip)
      write (nout,240) (j-1, ((lcrit(l,ic,j),l=1,3), ic=1,ncrit), j=1,ip)
C
C      WRITE FORMATS
C
200  format (' iteration #',i3,' power(kW) = ',f10.3/
      ' satr = ',f10.5,' twr = ',f10.5,' twavgr = ',f10.5,
      ' ccflr = ',f10.5/4(' time = ',f10.5,2x))
C
210  format (///23x,'*** power iteration summary ***')
C
220  format (///' iteration power(kW) tsat ratio twall ratio ',
      ' twavg ratio ccfl ratio'/1x,71('_')/
      (3x,i2,4x,f11.4,4f13.6))
C
230  format (///' iteration',13x,'tsat time twall time twavg time',
      ' ccfl time'/,1x,71('_')/(3x,i2,14x,4f13.5))
C
240  format (///' criteria locations: subchannel or surface,',
      ' azimuthal and axial positions'/
      23x,' tsat twall twavg ccfl'/
      ' iteration',12x,'ic ix iz',4x,'is ia iz',
      3x,' ic ia iz',4x,'is ia iz'/1x,68('_')/
      (3x,i2,15x,4(1x,3i3,2x)))
C
250  format (' initial power is zero - a nonzero initial power',
      ' must be used to calculate power iterations')
C
      return
    end

```

PROPCK

```

      subroutine propck (pt ,alpt ,tgt ,tft ,p ,alp ,
      ' tg ,tf ,pb ,alpb ,tgb ,tgb ,
      ' ts,nzt,nzp1,nzp2,nxmax,nchn,nx,nzb,
      ' mat,nrmax,ncyl,nr,na,nz,11q,ierr)
C-----*-----*-----*-----*-----*-----*-----*
C
C      DESCRIPTION:

```

```
c  propck checks for solid material and fluid (H2O or D2O) properties
c  out of range of the thermodynamic state and transport property
c  subroutines
c
c  GLOSSARY:  I=input, O=output
c
c  ---General---
c  O ierr  = error indicator
c           (ierr=1 denotes property values out of range)
c
c  ---Top Section---
c  I nzt    = number of cells in the top section
c  I pt (nzt) = top section pressure
c  I alpt (nzt) = top section alpha
c  I tgt (nzt) = top section gas temp.
c  I tft (nzt) = top section liquid temp.
c  I xat (nzt) = top section air mass fract.
c
c  ---Middle Section---
c  I nz      = number of axial cells in the middle section
c  I nzp1    = nz + 1
c  I nzp2    = nz + 2
c  I nxmax   = maximum number of x-direction cells in middle section
c  I nchn    = number of channels in middle section
c  I nx(nchn) = number of x-direction cells in a channel
c  I p (nzp2,nxmax,nchn) = middle section pressure
c  I alp (nzp2,nxmax,nchn) = middle section alpha
c  I tg (nzp2,nxmax,nchn) = middle section gas temp.
c  I tf (nzp2,nxmax,nchn) = middle section liquid temp.
c  I xa (nzp2,nxmax,nchn) = middle section air mass fract.
c
c  ---Bottom Section---
c  I nzb     = number of cells in the bottom section
c  I pb (nzb) = bottom section pressure
c  I alpb (nzb) = bottom section alpha
c  I tgb (nzb) = bottom section gas temp.
c  I tfb (nzb) = bottom section liquid temp.
c  I xab (nzb) = bottom section air mass fract.
c
c  -----*-----*-----*-----*-----*-----*-----*-----*-----*
c  implicit real (a-h,o-z), integer (i-n)
c  character*2 prop(3)
c  parameter (one=1.0, tconv=273.15)
c
c  TOP SECTION ARRAYS
c
c  dimension pt(nzt), alpt(nzt), tgt(nzt), tft(nzt)
c
c  MIDDLE SECTION ARRAYS
c
c  dimension p(nzp2,nxmax,nchn), alp(nzp2,nxmax,nchn),
c  &          tg(nzp2,nxmax,nchn), tf (nzp2,nxmax,nchn),
c  &          ts(nrmax,na,nz,ncyln),mat(nrmax,nz,ncyln),
c  &          nr(ncyln)
c  dimension nx(nchn)
c
c  BOTTOM SECTION ARRAYS
c
c  dimension pb(nzb), alpb(nzb), tgb(nzb), tfb(nzb)
c
c  data prop/' p', 'tf', 'tg'/
c  data epsal/0.001/
c
c  LOWER & UPPER BOUNDS ON TEMPERATURES OF SOLID MATERIALS AND ALLOY
c
```

```

      data  tslo/273.15/,  tshi/923.15/,  tssshi/773.15/,
&      tsalo/293.15/,  tslahi/533.15/,
&      tsualo/273.15/,  tsuahi/673.15/
c
c      LOWER & UPPER BOUNDS ON p, tg, tf
c      (LOWER & UPPER BOUNDS ON xa WERE CHECKED IN UPDATP)
c
      data  pllo/611.3/,  phlo/1.03e+3/,  phi/1.0e+6/,
&      tglo/275.0/,  tghi/700.0/,
&      tflo/283.0/,  tfhi/450.0/
c
c----- CHECK THE APPLICATION LIMITS OF SOLID MATERIAL AND ALLOY -----
c      PROPERTY CORRELATIONS
c
      do 20 icyln=1,ncyln
        nri = nr(icyln)
        do 10 ia=1,na
          do 10 ir=1,nri
            do 10 jz=1,nz
              nsld = mat(ir,jz,icyln)
              tsolid = ts(ir,ia,jz,icyln) + tconv
c
              if (nsld .eq. 4 .or. nsld .eq. 5) then
                if (nsld.eq.4) then
                  if (tsolid .lt. tsalo .or. tsolid .gt. tslahi) then
                    ierr = 1
                    write(*,910) nsld, ir, ia, jz, icyln
                    return
                  end if
                else
                  if (tsolid .lt. tsualo .or. tsolid .gt. tsuahi) then
                    ierr = 1
                    write(*,911) nsld, ir, ia, jz, icyln
                    return
                  end if
                end if
              end if
c
              else if (nsld .eq. 3) then
                if (tsolid .lt. tslo .or. tsolid .gt. tssshi) then
                  ierr = 1
                  write(*,912) nsld, ir, ia, jz, icyln
                  return
                end if
c
              else
                if (tsolid .lt. tslo .or. tsolid .gt. tshi) then
                  ierr = 1
                  write(*,913) nsld, ir, ia, jz, icyln
                  return
                end if
              end if
c
            10      continue
          20      continue
c
c----- CHECK FLUID PROPERTIES -----
c      (LIGHT WATER FOR ilq = 1 AND HEAVY WATER FOR ilq = 2)
c      WHEN VOID FRACTION IS NEAR ONE, CHECKS ON TEMPERATURE
c      ARE MADE ONLY FOR THE GAS PHASE
c
      if(ilq .eq. 1) then
        plo = pllo
      else
        plo = phlo

```

```
      end if
c
      alpmin = epsa1
      alpmax = one - alpmin
c
c      TOP SECTION
c
      do 100 jz=1,nzt
        if (pt(jz) .lt. plo .or. pt(jz) .gt. phi) then
          ierr = 1
          write(*,900) prop(1), jz
          return
        end if
c
        if (alpt(jz) .lt. alpmax) then
          if (tft(jz) .lt. tflo .or. tft(jz) .gt. tfhi) then
            ierr = 1
            write(*,900) prop(2), jz
            return
          end if
        end if
c
        if(alpt(jz) .gt. alpmin) then
          if (tgt(jz) .lt. tglo .or. tgt(jz) .gt. tghi) then
            ierr = 1
            write(*,900) prop(3), jz
            return
          end if
        end if
100    continue
c
c      MIDDLE SECTION
c
      do 220 ic=1,nchn
        do 210 ix=1,nx(ic)
          do 200 jz=2,nzpl
            if (p(jz,ix,ic) .lt. plo .or. p(jz,ix,ic) .gt. phi) then
              ierr = 1
              write(*,904) prop(1), jz, ix, ic
              return
            end if
c
            if (alp(jz,ix,ic) .lt. alpmax) then
              if (tf(jz,ix,ic) .lt. tflo .or. tf(jz,ix,ic) .gt. tfhi) then
                ierr = 1
                write(*,904) prop(2), jz, ix, ic
                return
              end if
            end if
c
            if (alp(jz,ix,ic) .gt. alpmin) then
              if (tg(jz,ix,ic) .lt. tglo .or. tg(jz,ix,ic) .gt. tghi) then
                ierr = 1
                write(*,904) prop(3), jz, ix, ic
                return
              end if
            end if
200    continue
210    continue
220    continue
c
c      BOTTOM SECTION
c
      do 300 jz=1,nzb
```

```

      if (pb(jz) .lt. plo .or. pb(jz) .gt. phi) then
        ierr = 1
        write(*,908) prop(1), jz
        return
      end if
c
      if (alpb(jz) .lt. alpmax) then
      if (tfb(jz) .lt. tflo .or. tfb(jz) .gt. tfhi) then
        ierr = 1
        write(*,908) prop(2), jz
        return
      end if
      end if
c
      if (alpb(jz) .gt. alpmin) then
      if (tgb(jz) .lt. tglo .or. tgb(jz) .gt. tghi) then
        ierr = 1
        write(*,908) prop(3), jz
        return
      end if
      end if
300 continue
c
c----- FORMATS -----
c
900 format (/, ' (',a,') property out of range in propck',/,
  &         ' for top section cell jz = ',i3)
c
904 format (/, ' (',a,') property out of range in propck',/,
  &         ' for middle section cell ',
  &         ' jz = ',i3, ' ix = ',i3, ' ic = ',i3)
c
908 format (/, ' (',a,') property out of range in propck',/,
  &         ' for bottom section cell jz = ',i3)
c
910 format (/, ' Li-Al alloy property out of range in propck',/,
  &         ' material index = ',i3, ' ir = ',i3, ' ia = ',i3,
  &         ' jz = ',i3, ' icyln = ',i3)
911 format (/, ' U-Al alloy property out of range in propck',/,
  &         ' material index = ',i3, ' ir = ',i3, ' ia = ',i3,
  &         ' jz = ',i3, ' icyln = ',i3)
912 format (/, ' Stainless Steel property out of range in propck',/,
  &         ' material index = ',i3, ' ir = ',i3, ' ia = ',i3,
  &         ' jz = ',i3, ' icyln = ',i3)
913 format (/, ' (mat=1;U, mat=2;Al) property out of range in propck',/,
  &         ' material index = ',i3, ' ir = ',i3, ' ia = ',i3,
  &         ' jz = ',i3, ' icyln = ',i3)
c
      return
      end

```

PRTFLD

```

      subroutine prtfld (pt,alpt,xat,rogt,roft,hgt,hft,tgt,tft,volt,
  &
  &         p ,alp ,xa ,rog ,rof ,hg ,hf ,tg ,tf ,volc,
  &         pb,alpb,xab,rogb,rofb,hgb,hfb,tgb,tfb,volb,
  &         alptn,rogt n,roft n,
  &         alpn ,rogn ,rofn ,
  &         alpbn,rogbn,rofbn,
  &         ugt,uft,wgx,wfx,ugz,ufz,ugb,ufb,
  &         act,acx,acz,acb,
  &         ysit,ysi,ysib,git,gi,gib,eit,ei,eib,gw,
  &         ppl,alppl,tgpl,tfpl,xapl,
  &         rogpl,rofpl,hgpl,hfpl,
  &         ptb,alptb,tgtb,tftb,xatb,

```

```

        rogtb,roftb,hgtb,hftb,
        alppln,rogpln,rofpln,ppln,tgpln,xapln,
        alptbn,rogtbn,roftbn,
        volpl,voltb,tsec,delt,vminz,vminx,icc,
        nx,nzp1,nzp2,nzp3,nxmax,nchn,nzt,nzb,
        cfl,lis,lic,ljz,lix,iunits,iprint,ilq)
C
C *****
C *
C * SUBROUTINE prtflld
C *
C * SUBROUTINE TO WRITE FLUID VARIABLES TO OUTPUT FILE
C *
C * iprint - PRINT CONTROL FLAG:
C *         iprint = 1, PRINT PRESSURE, VOID, QUALITY, GAS AND
C *                   FLUID TEMPERATURES, AND VELOCITIES
C *         iprint = 2, ALSO PRINT DENSITY, ENTHALPY, AND
C *                   FLOWRATES
C *
C *****
C implicit real (a-h,o-z), integer (i-n)
C real jg,jf
C logical first
C
C parameter (ckilo=0.001, thousa=1000.0, ccel=273.15)
C parameter (zero=0.0, half=0.5, one=1.0)
C parameter (cpsi=6894.757, cft=0.3048, cgpm=15850.32)
C parameter (ccfm=2.118880e+03, pstp=101325.0, tstp=298.15)
C
C character*3 top
C character*6 bottom
C character*11 plenum, tank
C character*6 upres,kpa,psia
C character*5 uvelo,mps,fps
C character*5 uflow,lps,gpm
C
C MIDDLE SECTION PHYSICAL PARAMETERS
C
C dimension          nx(nchn),      p(nzp2,nxmax,nchn),
C      alp(nzp2,nxmax,nchn),      xa(nzp2,nxmax,nchn),
C      rog(nzp2,nxmax,nchn),      rof(nzp2,nxmax,nchn),
C      hg(nzp2,nxmax,nchn),      hf(nzp2,nxmax,nchn),
C      tg(nzp2,nxmax,nchn),      tf(nzp2,nxmax,nchn),
C      ugz(nzp3,nxmax,nchn),      ufz(nzp3,nxmax,nchn),
C      wgx(nzp2,nxmax,nchn),      wfx(nzp2,nxmax,nchn),
C      ysi(nzp2,nxmax,nchn),      gi(nzp2,nxmax,nchn),
C      ei(nzp2,nxmax,nchn),      gw(nzp2,nxmax,nchn),
C      acz(nzp3,nxmax,nchn),      acx(nzp2,nxmax,nchn),
C      volc(nzp2,nxmax,nchn),      icc(2,nxmax,nchn)
C
C dimension alp(nzp2,nxmax,nchn), rogn(nzp2,nxmax,nchn),
C      rofn(nzp2,nxmax,nchn)
C
C dimension qmasfi(6)
C
C TOP SECTION PHYSICAL PARAMETERS
C
C dimension pt(nzt), alpt(nzt), xat(nzt),
C      rogt(nzt), roft(nzt), ysit(nzt),
C      hgt(nzt), hft(nzt), git(nzt),
C      tgt(nzt), tft(nzt), eit(nzt),
C      ugt(nzt), uft(nzt),
C      volt(nzt), act(nzt)
C

```



```

dimension alptn(nzt), rogtm(nzt), roftn(nzt)
c
c  BOTTOM SECTION PHYSICAL PARAMETERS
c
dimension pb(nzb), alpb(nzb), xab(nzb),
&         rogb(nzb), rofb(nzb), ysib(nzb),
&         hgb(nzb), hfb(nzb), gib(nzb),
&         tgb(nzb), tfb(nzb), eib(nzb),
&         ugb(nzb), ufb(nzb),
&         volb(nzb), acb(nzb)
c
dimension alpbm(nzb), rcgbm(nzb), rofbm(nzb)
c
common /lounit/ ninp, nout, ndmp, ntmp, nrsti, nrsto
c
dimension alpch(3)
common /civd/ alpch, delp
c
dimension ws(2)
data wa/28.97/, ws(1)/18.016/, ws(2)/20.034/
c
data first/.true./
data top/'top'/, bottom/'bottom'/
data plenum/'      plenum'/', tank/' tank bot.'/
data kpa/'(kPa) '/, psia/'(psia)'/
data mps/'(m/s) '/, fps/'(f/s)'/
data lps/'(l/s) '/, gpm/'(gpm)'/
c
c  SET UNITS AND UNIT CONVERSION FACTORS
c
c
if (first) then
  first = .false.
  rwa = ws(1q)/wa
  if (iunits .eq. 1' then
    upres = kpa
    uvelo = mps
    uflow = lps
    cpres = ckilo
    cvelo = one
    cflow = thousa
  else
    upres = psia
    uvelo = fps
    uflow = gpm
    cpres = one/cpsi
    cvelo = one/cft
    cflow = cgpm
  end if
end if
c
write (nout,110) tsec,delt,cfl,lis,lic,ljz,lix
c
if (iprint .ge. 2) then
  avgalp = zero
  totvol = zero
  do 5 ic=1,nchn
    nsub = nx(ic)
    do 5 ix=1,nsub
      do 5 jz=2,nzpl
        avgalp = avgalp + volc(jz,ix,ic)*alp(jz,ix,ic)
        totvol = totvol + volc(jz,ix,ic)
      5
    continue
    avgalp = avgalp/totvol
    stp = (ppln/pstp)*(tstp/tgpln)

```

```

        write (20,370) tsec, delt, pp1n, tgpln, xap1n, avgalp, stp
    end if
C
C    WRITE - PRESSURE, VOID FRACTION, QUALITY, GAS TEMPERATURE,
C          FLUID TEMPERATURE, AND ALL GAS AND FLUID VELOCITIES
C
C    TOP SECTION
C
    write (nout,120) top, upres, uvelo, uvelo
    write (nout,125) plenum, ppl*cpres, alpl, xapl, tgpl-ccel,
    &    tfpl-ccel
    write (nout,130) (jz, pt(jz)*cpres,
    &    alpt(jz),      xat(jz),
    &    tgt(jz)-ccel,  tft(jz)-ccel,
    &    ugt(jz)*cvelo, uft(jz)*cvelo, jz=1,nzt)
C
C    MIDDLE SECTION
C
    write (nout,140) upres, uvelo, uvelo, uvelo, uvelo
    do 20 ic=1,nchn
        nsub = nx(ic)
        do 10 ix=1,nsub
            write (nout,160) (ic,ix,jz-1 ,      p(jz,ix,ic)*cpres,
    &    alp(jz,ix,ic),      xa(jz,ix,ic),
    &    tg(jz,ix,ic)-ccel,  tf(jz,ix,ic)-ccel,
    &    ugz(jz,ix,ic)*cvelo, ufz(jz,ix,ic)*cvelo,
    &    wgx(jz,ix,ic)*cvelo, wfx(jz,ix,ic)*cvelo,
    &    jz=2,nzpl)
            jz = nzp2
            write (nout,150) ic,ix,jz-1 , ugz(jz,ix,ic)*cvelo,
    &    ufz(jz,ix,ic)*cvelo
10        continue
20    continue
C
C    BOTTOM SECTION
C
    write (nout,120) bottom, upres, uvelo, uvelo
    write (nout,130) (jz, pb(jz)*cpres,
    &    alpb(jz),      xab(jz),
    &    tgb(jz)-ccel,  tfb(jz)-ccel,
    &    ugb(jz)*cvelo, ufb(jz)*cvelo, jz=1,nzb)
    write (nout,125) tank, ptb*cpres, alptb, xatb, tgth-ccel,
    &    tftb-ccel
C
C    FOR LONG PRINTS ALSO WRITE -
C    BULK STEAM MOLE FRACTION IN GAS PHASE, INTERFACIAL STEAM MOLE
C    FRACTION, BULK INTERFACIAL GAMMA, BULK INTERFACIAL ENERGY AND
C    WALL GAMMA
C
    if (iprint.eq.2) then
        write (nout,170)
C
C    TOP SECTION
C
    write (nout,280) top
    do 25 jz=1,nzt
        xs = one - xat(jz)
        ys = xs/(xs + xat(jz)*rwa)
        gami = git(jz)*volt(jz)*thousa
        qi = eit(jz)*volt(jz)*ckilo
        call tsat (pt(jz),ilq,tfs,dtdp)
        call tsat (ysit(jz)*pt(jz),ilq,ti,dtdp)
        write (nout,290) jz, tfs-ccel, ys, ti-ccel, gami, qi
25    continue

```

```

c
c   MIDDLE SECTION
c
      write (nout,300)
      do 40 ic=1,nchn
        nsub = nx(ic)
        do 35 ix=1,nsub
          do 30 jz=2,nzpl
            xs = one - xa(jz,ix,ic)
            ys = xs/(xs + xa(jz,ix,ic)*rwa)
            gami = gi(jz,ix,ic)*volc(jz,ix,ic)*thousa
            qi = ei(jz,ix,ic)*volc(jz,ix,ic)*ckilo
            gamw = gw(jz,ix,ic)*thousa
            call tsat (p(jz,ix,ic),ilq,tfs,dtdp)
            call tsat (ysi(jz,ix,ic)*p(jz,ix,ic),ilq,ti,dtdp)
            write (nout,310) ic, ix, jz-1, tfs-ccel, ys,
              &          ti-ccel, gami, qi, gamw
30          continue
            write (nout,170)
35          continue
40          continue
c
c   BOTTOM SECTION
c
      write (nout,280) bottom
      do 45 jz=1,nzb
        xs = one - xab(jz)
        ys = xs/(xs + xab(jz)*rwa)
        gami = gib(jz)*volb(jz)*thousa
        qi = eib(jz)*volb(jz)*ckilo
        call tsat (pb(jz),ilq,tfs,dtdp)
        call tsat (ysib(jz)*pb(jz),ilq,ti,dtdp)
        write (nout,290) jz, tfs-ccel, ys, ti-ccel, gami, qi
45      continue
      end if
c
c   FOR LONG PRINTS ALSO WRITE -
c   GAS DENSITY, FLUID DENSITY, GAS ENTHALPY, AND FLUID ENTHALPY
c
      if (iprint.eq.2) then
        write (nout,170)
c
c   TOP SECTION
c
      write (nout,180) top
      write (nout,185) plenum, rogpl, rofpl, hgpl*ckilo, hfpl*ckilo
      write (nout,190) (jz, rogt(jz), roft(jz),
        &          hgt(jz)*ckilo,
        &          hft(jz)*ckilo, jz=1,nzt)
c
c   MIDDLE SECTION
c
      write (nout,200)
      do 60 ic=1,nchn
        nsub = nx(ic)
        do 50 ix=1,nsub
          write (nout,210) (ic, ix, jz-1,
            &          rog(jz,ix,ic), rof(jz,ix,ic),
            &          hg(jz,ix,ic)*ckilo,
            &          hf(jz,ix,ic)*ckilo, jz=2,nzpl)
          write (nout,170)
50          continue
60          continue
c

```

```

c      BOTTOM SECTION
c
      write (nout,180) bottom
      write (nout,190) (jz, rogb(jz), rofb(jz),
        &             hgb(jz)*ckilo,
        &             hfb(jz)*ckilo, jz=1,nzb)
      write (nout,185) tank, rogtb, roftb, hgtb*ckilo, hftb*ckilo
      end if
c
c      FOR LONG PRINTS ALSO WRITE -
c      VOLUMETRIC AND MASS FLOWRATES
c
      if (iprint.ge.2) then
c
c         if (iprint.eq.2) write (nout,170)
c
c      TOP SECTION
c
      if (iprint.eq.2) write (nout,220) top, uflow, uflow
      write (20,320) top
      do 70 jz=1,nzt
        jzm = jz - 1
        if (jz .eq. 1) then
          alpm = alppln
          rogm = rogpln
          rofm = rofpln
        else
          alpm = alptn(jzm)
          rogm = rogtn(jzm)
          rofm = roftn(jzm)
        end if
        facg = sign(half, ugt(jz))
        facf = sign(half, uft(jz))
        if (abs(ugt(jz)) .lt. vminz) facg = half*ugt(jz)/vminz
        if (abs(uft(jz)) .lt. vminz) facf = half*uft(jz)/vminz
        wtgm = half + facg
        wtfm = half + facf
        wtgp = one - wtgm
        wtfp = one - wtfm
        walpg = wtgm*alpm + wtgp*alptn(jz)
        walpf = wtfm*alpm + wtfp*alptn(jz)
        wrog = wtgm*rogm + wtgp*rogtn(jz)
        wrof = wtfm*rofm + wtfp*roftn(jz)
        qvolgz = walpg *act(jz)*ugt(jz)
        qvolfz = (one-walpf)*act(jz)*uft(jz)
        qmasgz = wrog*qvolgz
        qmasfz = wrof*qvolfz
        if (iprint.eq.2) write (nout,230) jz,
        &             qvolgz*cflow,qvolfz*cflow,qmasgz*thousa,qmasfz
        jg = qvolgz/act(jz)
        jf = qvolfz/act(jz)
        write (20,330) jz,jf,jg,jg+jf,qvolgz*ccfm,qvolgz*cgpm,
        &             qvolfz*cgpm
c
c      continue
70
c
c      MIDDLE SECTION
c
      if (iprint.eq.2) write (nout,240) uflow, uflow, uflow, uflow
      write (20,340)
      qtot = zero
      do 90 ic=1,nchn
        nsub = nx(ic)
        qmasfi(ic) = zero
      do 85 ix=1,nsub

```

```
do 80 jz=2,nzp2
```

```
c
```

```

jzm = jz - 1
facg = sign(half, ugz(jz,ix,ic))
facf = sign(half, ufz(jz,ix,ic))
if (abs(ugz(jz,ix,ic)) .lt. vminz)
  facg = half*ugz(jz,ix,ic)/vminz
if (abs(ufz(jz,ix,ic)) .lt. vminz)
  facf = half*ufz(jz,ix,ic)/vminz
wtgm = half + facg
wtfm = half + facf
wtgp = one - wtgm
wtfp = one - wtfm
walpg = wtgm*alpn(jzm,ix,ic) + wtgp*alpn(jz,ix,ic)
walpf = wtfm*alpn(jzm,ix,ic) + wtfp*alpn(jz,ix,ic)
wrog = wtgm*rogn(jzm,ix,ic) + wtgp*rogn(jz,ix,ic)
wrof = wtfm*rofn(jzm,ix,ic) + wtfp*rofn(jz,ix,ic)
qvolgz = walpg *acz(jz,ix,ic)*ugz(jz,ix,ic)
qvolfz = (one-walpf)*acz(jz,ix,ic)*ufz(jz,ix,ic)
qmasgz = wrog*qvolgz
qmasfz = wrof*qvolfz
if (jz .eq. 2) then
  qmasfi(ic) = qmasfi(ic) + qmasfz
  qtot = qtot + qmasfz
end if
```

```
c
```

```

if (jz .ne. nzp2) then
  ixm = icc(1,ix,ic)
  facg = sign(half, wgx(jz,ix,ic))
  facf = sign(half, wfx(jz,ix,ic))
  if (abs(wgx(jz,ix,ic)) .lt. vminx)
    facg = half*wgx(jz,ix,ic)/vminx
  if (abs(wfx(jz,ix,ic)) .lt. vminx)
    facf = half*wfx(jz,ix,ic)/vminx
  wtgm = half + facg
  wtfm = half + facf
  wtgp = one - wtgm
  wtfp = one - wtfm

  walpg = wtgm*alpn(jz,ixm,ic) + wtgp*alpn(jz,ix,ic)
  walpg = vrrib(walpg)
  walpf = wtfm*alpn(jz,ixm,ic) + wtfp*alpn(jz,ix,ic)
  walpf = vrrib(walpf)
  wrog = wtgm*rogn(jz,ixm,ic) + wtgp*rogn(jz,ix,ic)
  wrof = wtfm*rofn(jz,ixm,ic) + wtfp*rofn(jz,ix,ic)
  qvolgx = walpg *acx(jz,ix,ic)*wgx(jz,ix,ic)
  qvolfx = (one-walpf)*acx(jz,ix,ic)*wfx(jz,ix,ic)
  qmasgx = wrog*qvolgx
  qmasfx = wrof*qvolfx
  if (iprint.eq.2) write (nout,250) ic,ix,jzm,
    qvolgz*cflow,qvolfz*cflow,qmasgz*thousa,qmasfz,
    qvolgx*cflow,qvolfx*cflow,qmasgx*thousa,qmasfx
  jg = qvolgz/acz(jz,ix,ic)
  jf = qvolfz/acz(jz,ix,ic)
  write (20,360) ic,ix,jzm,jf,jg,jg+jf,qvolgz*ccfm,
    qvolgz*cgpm,qvolfz*cgpm
else
  if (iprint.eq.2) write (nout,260) ic,ix,jzm,
    qvolgz*cflow,qvolfz*cflow,qmasgz*thousa,qmasfz
  jg = qvolgz/acz(jz,ix,ic)
  jf = qvolfz/acz(jz,ix,ic)
  write (20,361) ic,ix,jzm,jf,jg,jg+jf,qvolgz*ccfm,
    qvolgz*cgpm,qvolfz*cgpm
end if
```

```
c
80      continue
85      continue
90      continue
c
c      BOTTOM SECTION
c
      if (iprint.eq.2) write (nout,220) bottom, uflow, uflow
      write (20,320) bottom
      do 100 jz=1,nzb
        jzp = jz + 1
        if (jz .eq. nzb) then
          alpp = alptbn
          rogp = rogtbn
          rofp = roftbn
        else
          alpp = alpbn(jzp)
          rogp = rogbn(jzp)
          rofp = rofbn(jzp)
        end if
        facg = sign(half, ugb(jz))
        facf = sign(half, ufb(jz))
        if (abs(ugb(jz)) .lt. vminz) facg = half*ugb(jz)/vminz
        if (abs(ufb(jz)) .lt. vminz) facf = half*ufb(jz)/vminz
        wtgm = half + facg
        wtfm = half + facf
        wtgp = one - wtgm
        wtfp = one - wtfm
        walpg = wtgm*alpbn(jz) + wtgp*alpp
        walpf = wtfm*alpbn(jz) + wtfp*alpp
        wrog = wtgm*rogbn(jz) + wtgp*rogp
        wrof = wtfm*rofbn(jz) + wtfp*rofp
        qvolgz = walpg*acb(jz)*ugb(jz)
        qvolfz = (one-walpf)*acb(jz)*ufb(jz)
        qmasgz = wrog*qvolgz
        qmasfz = wrof*qvolfz
        if (iprint.eq.2) write (nout,230) jz,
&          qvolgz*cflow,qvolfz*cflow,qmasgz*thousa,qmasfz
        jg = qvolgz/acb(jz)
        jf = qvolfz/acb(jz)
        write (20,330) jz,jf,jg,jg+jf,qvolgz*ccfm,qvolgz*cgpm,
&          qvolfz*cgpm
100      continue
      end if
c
c      WRITE CHANNEL FLOW SPLIT INFORMATION
c
      if (nchn .gt. 1) then
        if (qtot .ne. zero) then
          write(20,380) (ic, ic=1, nchn)
          write(20,381) (qmasfi(ic)/qtot, ic=1, nchn)
        else
          write(20,382)
        end if
      end if
c
      if (nchn .eq. 3) then
        write(20,383) delp, alpt(nzt), alpch(1), alpch(2), alpch(3)
      end if
c
c      WRITE FORMATS
c
110      format (//,'1$ fluid edit at time = ',g12.5,' seconds',/
&          '          time step size = ',g12.5,' seconds',/
```

```

        ' Courant step size = ',g12.5,' seconds',/
        ' Section (1-T,2-M,3-B) = ', i12,/
        ' Channel (0 for T/B) = ', i12,/
        ' Axial = ', i12,/
        ' Azimuthal = ', i12,/)

c
120 format (1x,a,' section fluid variables:',/
        ' 10x,'jz',2x,'pressure',2x,'void',4x,'xair',2x,'t gas',
        ' 4x,'t fld',2x,'u gas',2x,'u fld',/15x,a,
        ' 12x,2(6x,'(C) '),1x,2(2x,a),/9x,57('_'))

c
125 format (1x,a,2x,f8.4,1x,f7.4,1x,f5.3,2(1x,f7.2))

c
130 format (9x,i3,2x,f8.4,1x,f7.4,1x,f5.3,1x,f7.2,1x,f7.2,
        ' 1x,f6.2,1x,f6.2)

c
140 format (/,'@middle section fluid variables:',/
        ' 14x,'pressure',2x,'void',4x,'xair',2x,'t gas',
        ' 4x,'t fld',2x,'u gas',2x,'u fld',2x,'w gas',
        ' 2x,'w fld',/2x,'ic',2x,'ix',2x,'jz',3x,a,
        ' 12x,2(6x,'(C) '),1x,4(2x,a),/1x,79('_'))

c
150 format (3(1x,i3),40x,2(1x,f6.2),/)

c
160 format (3(1x,i3),2x,f8.4,1x,f7.4,1x,f5.3,1x,f7.2,
        ' 1x,f7.2,1x,f6.2,1x,f6.2,1x,f6.2,1x,f6.2)

c
170 format (1x)

c
180 format (/,' section densities and enthalpies:',/
        ' 16x,'rho gas',2x,'rho fld',4x,'h gas',6x,'h fld',/
        ' 10x,'jz',2x,2(1x,'(kg/m^3)'),3x,'(kJ/kg)',
        ' 4x,'(kJ/kg)'/9x,44('_'))

c
185 format (1x,a,1x,2(1x,f8.2),2(1x,f10.3))

c
190 format (9x,i3,2x,f8.2,1x,f8.2,1x,f10.3,1x,f10.3)

c
200 format (/,' middle section densities and enthalpies:',/
        ' 16x,'rho gas',2x,'rho fld',4x,'h gas',6x,'h fld',/
        ' 2x,'ic',2x,'ix',2x,'jz',2x,2(1x,'(kg/m^3)'),
        ' 3x,'(kJ/kg)',4x,'(kJ/kg)',/1x,52('_'))

c
210 format (1x,i3,1x,i3,1x,i3,2x,f8.2,1x,f8.2,1x,f10.3,1x,f10.3)

c
220 format (1x,a,' section volumetric and mass flowrates:',/
        ' 15x,'Qz gas',2x,'Qz fld',2x,'mz gas',2x,'mz fld',/
        ' 10x,'jz',1x,3x,a,3x,a,3x,'(g/s)',
        ' 2x,'(kg/s)'/9x,36('_'))

c
230 format (9x,i3,1x,4(1x,f7.3))

c
240 format (/,' middle section volumetric and mass flowrates:',/
        ' 15x,'Qz gas',2x,'Qz fld',2x,'mz gas',2x,'mz fld',
        ' 2x,'Qx gas',2x,'Qx fld',2x,'mx gas',2x,'mx fld',/
        ' 2x,'ic',2x,'ix',2x,'jz',1x,2(3x,a,3x,a,
        ' 3x,'(g/s)',2x,'(kg/s)'),/1x,76('_'))

c
250 format (3(1x,i3),1x,8(1x,f7.3))

c
260 format (3(1x,i3),1x,4(1x,f7.3),/)

c
280 format (/,' section interfacial properties:',/
        ' 16x,'tsat',6x,'bulk ys',6x,'ti',6x,'gamma(i)',

```

```

        6x,'egi',/10x,'jz',4x,'(C)',6x,'mole frc',3x,
        ' (C) ',3x,2x,'(g/s)',6x,'(kJ/s)',/9x,58(' ')
c
290  format (9x,i3,2x,f7.2,4x,f6.3,4x,f7.2,1x,2(2x,f10.4))
c
300  format (/, ' middle section interfacial properties:',/
        16x,'tsat',6x,'bulk ys',6x,'ti',6x,'gamma(i)',6x,'egi',
        7x,'gamma(w)',/2x,'ic',2x,'ix',2x,'jz',4x,'(C)',
        6x,'mole frc',3x,' (C) ',3x,2x,'(g/s)',6x,'(kJ/s)',
        7x,'(g/s)',/1x,78(' '))
c
310  format (3(1x,i3),2x,f7.2,4x,f6.3,4x,f7.2,1x,3(2x,f10.4))
c
320  format (1x,a, ' section superficial velocities:',/
        17x,'jf',6x,'jg',6x,'j',9x,'Qg',11x,'Qg',11x,'Qf'/
        10x,'jz',1x,3(3x,'(m/s)'),5x,'(cfm)',8x,'(gpm)',
        8x,'(gpm)'/9x,67(' '))
c
330  format (9x,i3,1x,3(1x,f7.3),3(1x,f12.5))
c
340  format (/, ' middle section superficial velocities:',/
        17x,'jf',6x,'jg',6x,'j',9x,'Qg',11x,'Qg',11x,'Qf'/
        2x,'ic',2x,'ix',2x,'jz',1x,3(3x,'(m/s)'),5x,'(cfm)',
        8x,'(gpm)',8x,'(gpm)'/1x,75(' '))
c
360  format (3(1x,i3),1x,3(1x,f7.3),3(1x,f12.5))
361  format (3(1x,i3),1x,3(1x,f7.3),3(1x,f12.5),/)
c
370  format (//, '1$fluid edit at time = ',g12.5,' seconds',/
        &      ' time step size = ',g12.5,' seconds',/
        &      ' ppln = ',f12.1,' Pa ',/
        &      ' tgpln = ',f12.2,' K ',/
        &      ' xapln = ',f12.6,' ',/
        &      ' avg middle sec void = ',f12.6,' ',/
        &      ' stp corr. (25C/latm) = ',f12.6,' ',/)
c
380  format(/,1x,'liquid mass flowrate fractions by channel number:',
        &      /,3x,6(12,6x))
381  format( 1x,6(f5.3,3x))
382  format(/,1x,'(middle section mass flowrate at inlet is zero)')
c
383  format(/,1x,'donored void fractions at middle section inlet:',
        &      /,1x,' dp(Pa) void: top inner middle outer',
        &      /,1x,f7.1,3x,4(3x,f6.4))
c
      return
      end

```

PRTPOW

```

      subroutine prtpow (axial,axal',deldry,delmod,hactiv,gap,pows,
        &      asypwr,tsec,ntp,ytp,ztp,ntp,intp,itype,ifissn,
        &      itnklv,tnklv0,imodh,idryh,iconh,iexp,na,ncyl,
        &      nr,nz,nrmax,ntpmax,ntptot,nspln,nout,izht,izhb)
c=====
c      PRINT OUT POWER DATA AT TIME tsec
c=====
c
c      ARGUMENTS:
c I axial - AXIAL POWER SHAPE AT CURRENT TIME
c I axal0 - AXIAL POWER SHAPE AT TIME=0.0
c I deldry - DRY TANK FRACTION OF POWER DUE TO DECAY HEAT
c I delmod - MODERATED TANK FRACTION OF POWER DUE TO DECAY HEAT
c I hactiv - ACTIVE HEIGHT OF CORE (m)
c I gap - DISTANCE FROM BOTTOM OF CORE TO TANK BOTTOM (m)

```



```

c I pows - POWER DEPOSITION IN METAL NODE FOR THIS TIME STEP (W)
c I asypwr - PRE-INCIDENT ASSEMBLY POWER (W)
c I tsec - TIME AT END OF TIME STEP (s)
c I ntp - ARRAY CONTAINING NUMBER OF DATA POINTS IN SPLINE FITS
c I intp - ARRAY OF POINTERS TO START OF DATA SETS
c I itype - ARRAY CONTAINING TYPE OF SPLINE
c I xtp - ABSCISSA VALUES FOR SPLINE DATA
c I ytp - ORDINATE VALUES FOR SPLINE DATA
c I ztp - SPLINE COEFFICIENTS
c I ifissn - POINTER TO SPLINE COEFFICIENTS FOR FISSION RELATIVE
c          POWER SPLINE
c I itnklv - POINTER TO SPLINE COEFFICIENTS FOR TANK LEVEL SPLINE
c I tnklv0 - INITIAL TANK LEVEL (m)
c I imodh - POINTER TO SPLINE COEFFICIENTS FOR MODERATED DECAY
c          HEAT SPLINE
c I idryh - POINTER TO SPLINE COEFFICIENTS FOR DRY DECAY HEAT SPLINE
c I iconh - POINTER TO SPLINE COEFFICIENTS FOR CONSERVATIVE DECAY HEAT
c I iexp - MODE FLAG (0=REACTOR LIMIT, 1=EXPERIMENTAL MOCK-UP)
c I na - NUMBER OF AZIMUTHAL DIRECTIONS
c I ncyl - NUMBER OF CYLINDRICAL TUBES
c I nr - NUMBER OF RADIAL DIVISIONS BY CYLINDER
c I nz - NUMBER OF AXIAL LEVELS
c I ntpmax - MAXIMUM NUMBER OF POINTS IN A SPLINE
c I ntptot - TOTAL NUMBER OF SPLINE DATA POINTS
c I nspln - NUMBER OF SPLINES USED
c I nout - WRITE FILE UNIT NUMBER
c I izht - FIRST HEATED AXIAL CELL IN MIDDLE SECTION
c I izhb - LAST HEATED AXIAL CELL IN MIDDLE SECTION

```

```

c *****

```

```

c implicit real (a-h,o-z), integer (i-n)
c parameter (zero=0.0, one=1.0)

```

```

c dimension nr(ncyl), axial(nz,3), axal0(nz),
c          pows(nrmax,na,nz,ncyl)

```

```

c dimension xtp(ntptot), ytp(ntpmax,nspln), ztp(ntpmax,nspln),
c          intp(nspln), itype(nspln), ntp(nspln)

```

```

c EVALUATE TIME-DEPENDENT AMPLITUDE FACTORS:

```

```

c fdkdry, DRY TANK DECAY HEAT. NOTE--FOR THE EXPERIMENTAL
c          MOCK-UP MODE, THIS PROVIDES NORMALIZED POWER VS TIME
c fdkmod, MODERATED TANK DECAY HEAT
c fdkcon, CONSERVATIVE DELTA-MULTIPLIER
c ffissn, FISSION HEAT
c hrat , NORMALIZED TANK LEVEL RATIO

```

```

c if (iexp.eq.1) then

```

```

c   deldry = one
c   delmod = zero
c   fdkmod = zero
c   fdkcon = one
c   ffissn = zero
c   hrat = zero

```

```

c else

```

```

c   inx = intp(imodh)
c   ityp = itype(imodh)
c   ntps = ntp(imodh)
c   fdkmod = yvalu(ityp,ntps,xtp(inx),ytp(1,imodh),
c                 ztp(1,imodh),tsec)

```

```

c   inx = intp(iconh)
c   ityp = itype(iconh)

```

```
      ntps = ntp(iconh)
      fdkcon = yvalu(ityp,ntps,xtp(inx),ytp(1,iconh),
        &          ztp(1,iconh),tsec)
c
      inx = intp(iffissn)
      ityp = itype(iffissn)
      ntps = ntp(iffissn)
      ffissn = yvalu(ityp,ntps,xtp(inx),ytp(1,iffissn),
        &          ztp(1,iffissn),tsec)
c
      inx = intp(itnklv)
      ityp = itype(itnklv)
      ntps = ntp(itnklv)
      tnklv = tnklv0*yvalu(ityp,ntps,xtp(inx),ytp(1,itnklv),
        &          ztp(1,itnklv),tsec)
      hrat = (tnklv - gap)/hactiv
    end if
      inx = intp(idryh)
      ityp = itype(idryh)
      ntps = ntp(idryh)
      fdkdry = yvalu(ityp,ntps,xtp(inx),ytp(1,idryh),
        &          ztp(1,idryh),tsec)
c
c    COMPUTE TOTAL ASSEMBLY POWER
c
      if (hrat.gt.one) hrat=one
      if (hrat.lt.zero) hrat=zero
      term1 = (one - delmod*fdkcon)*hrat*ffissn
      term2 = delmod*fdkcon*hrat*fdkmod
      term3 = deldry*fdkcon*(one - hrat)*fdkdry
      apowr = asypwr*(term1 + term2 + term3)
c
c    EDIT OUT ASSEMBLY POWER RELATED QUANTITIES
c
      write (nout,100) tsec, apowr, asypwr, iexp
      if (iexp.eq.0) then
        tterm = term1 + term2 + term3
        term1n = term1/tterm
        term2n = term2/tterm
        term3n = term3/tterm
        write (nout,110) ffissn, fdkmod, fdkdry, hrat,
          &          delmod, deldry, term1, term1n,
          &          term2, term2n, term3, term3n
      end if
c
c    EDIT OUT DETAILED POWER DISTRIBUTIONS
c
      write (nout,120)
      write (nout,130) (axal0(iz),iz=1,nz)
      write (nout,140) (axial(iz,3),iz=1,nz)
      write (nout,150)
c
c    LOOP THROUGH THE METAL REGIONS
c
c    LOOP OVER CYLINDERS
c
      do 750 icyln=1,ncyln
        write (nout,160) icyln
        nri = nr(icyln)
c
c    LOOP OVER HEATED AXIAL LEVELS
c
      do 745 iz=izht,izhb
        write (nout,170) iz
```

```

        write (nout,180)
c
c      LOOP OVER AZIMUTHAL DIVISIONS
c
        do 740 ia=1,na
c
c      LOOP OVER RADIAL DIVISIONS
c
        write (nout,190) ia, (pows(ir,ia,iz,icyln),ir=1,nri)
740      continue
745      continue
750      continue
c
c      WRITE FORMATS
c
100     format ('1',20x,' power edit at time ',g12.5,' sec',///,
&          ' current assembly power is ..... ',g12.5,' W',/,
&          ' pre-incident assembly power was ... ',g12.5,' W',/,
&          ' mode flag ',i2,' (0=reactor limit, 1=expt mock-up)',/)
c
110     format ('0constituents of current assembly power ',/,
&          ' relative power fractions ',/,
&          ' fission ..... ',g12.5,/,
&          ' moderated decay heat ... ',g12.5,/,
&          ' dry tank decay heat..... ',g12.5,/,
&          ' fraction of core moderated .. ',g12.5,/,
&          ' delta moderated ..... ',g12.5,/,
&          ' delta dry ..... ',g12.5,/,
&          ' final power fraction terms      --absolute--',5x,
&          '-normalized-',/,
&          ' fission ..... ',g12.5,5x,g12.5,/,
&          ' moderated decay heat ... ',g12.5,5x,g12.5,/,
&          ' dry tank decay heat..... ',g12.5,5x,g12.5,///)
c
120     format ('0',20x,'detailed power distributions ',///,
&          ' --axial shape--',4x,18(' '),
&          ' decreasing axial height',18(' '), '>')
c
130     format (' initial shape ',5x,5g12.5)
c
140     format (' current shape ',5x,5g12.5)
c
150     format ('0',///,' power (W) deposited in metal ',/)
c
160     format ('0 for cylinder number ',i2)
c
170     format (4x,'axial level number ',i2)
c
180     format (4x,'--azimuth--',5x,22(' '),
&          ' increasing radii',21(' '), '>')
c
190     format (9x,i2,9x,5g12.5,/,3(20x,5g12.5,/)
c
        return
        end

```

PRTSLD

```

        subroutine prtSLD (ts,tsurf,qwf,qwg,tsec,nr,nrmax,na,nz,
&          ncyln,nsurf)
c
c      *****
c      *
c      * SUBROUTINE prtSLD: THIS ROUTINE PRINTS THE SOLID NODAL
c      * TEMPERATURES, SURFACE TEMPERATURES,
c      *

```

```
c      *          AND SURFACE HEAT FLUXES AT EACH          *
c      *          SPECIFIED TIME STEP                      *
c      *
c      *****
      implicit real(a-h,o-z), integer(i-n)
      parameter (ckilo=0.001)
      dimension tsurf(nsurf,na,nz), ts(nrmax,na,nz,ncyl),
1      &          qwf(nsurf,na,nz), nr(ncyl),
      &          qwg(nsurf,na,nz)
      common /iounit/ ninp, nout, ndmp, ntmp, nrsti, nrsto
c
      write (nout,10) tsec
c
c      WRITE SURFACE HEAT FLUXES TO LIQUID
c
      write (nout,20) (isurf, isurf=2,nsurf)
      write (nout,80)
      do 110 iz=1,nz
        do 100 ia=1,na
          write (nout,60) iz, ia, (ckilo*qwf(isurf,ia,iz),
1      &          isurf=2,nsurf)
100      continue
110      continue
c
c      WRITE SURFACE HEAT FLUXES TO GAS
c
      write (nout,30) (isurf, isurf=2,nsurf)
      write (nout,80)
      do 130 iz=1,nz
        do 120 ia=1,na
          write (nout,60) iz, ia, (ckilo*qwg(isurf,ia,iz),
1      &          isurf=2,nsurf)
120      continue
130      continue
c
c      WRITE SOLID SURFACE TEMPERATURES
c
      write (nout,40) (isurf, isurf=2,nsurf)
      write (nout,80)
      do 210 iz=1,nz
        do 200 ia=1,na
          write (nout,70) iz, ia, (tsurf(isurf,ia,iz),
1      &          isurf=2,nsurf)
200      continue
210      continue
c
c      WRITE SOLID NODAL TEMPERATURES
c
      do 320 icyln=1,ncyl
        nri = nr(icyln)
        write (nout,50) icyln, (ir, ir=1,nri)
        write (nout,80)
        do 310 iz=1,nz
          do 300 ia=1,na
            write (nout,70) iz, ia, (ts(ir,ia,iz,icyln),
1      &          ir=1,nri)
300      continue
310      continue
320      continue
c
c      WRITE FORMATS
c
10      format ('/solid edit at time = ',g12.5,' seconds'/)
c
```

```

20  format (/ ' surface heat fluxes to liquid (kW/m**2):' /,
      &      ' surface', 6(5x,i2,5x),/, 3x, 6(10x,i2))
30  format (/ ' surface heat fluxes to gas (kW/m**2):' /,
      &      ' surface', 6(5x,i2,5x),/, 3x, 6(10x,i2))
40  format (/ ' cylinder surface temperatures (C):' /,
      &      ' surface', 6(5x,i2,5x), 10(/, 3x, 6(10x,i2)))
50  format (/ ' interior temperatures (C) in cylinder ', i2, /,
      &      ' radius', 6(5x,i2,5x), 10(/, 3x, 6(10x,i2)))
c
60  format (1x, 2(i2,1x), 1x, 6f12.3, 10(/, 8x, (6f12.3)))
70  format (1x, 2(i2,1x), 1x, 6f12.5, 10(/, 8x, (6f12.5)))
80  format (' iz ia', /1x, 6(' '))
c
      return
end

```

PRTSRN

```

      subroutine prtsrn(pt, alpt, tgt, tft, xat, rogt, roft, hgt, hft,
      &      p, alp, tg, tf, xa, rog, rof, hg, hf,
      &      pb, alpb, tgb, tfb, xab, rogb, rofb, hgb, hfb,
      &      ppl, alppl, tgpl, tfpl, xapl, rogpl, rofpl, hgpl, hfpl,
      &      ptb, alptb, tgtb, tftb, xatb, rogtb, roftb, hgtb, hftb,
      &      ugt, uft, ugz, ufz, wgx, wfx, ugb, ufb,
      &      nzt, nzpl, nzp2, nzp3, nxmax, nchn, nx, nzb,
      &      tsec, delt, dtmin, dtmax, nitno, litot,
      &      dif, difp, difalp, diftg, diftf, difxa, difts, delhm,
      &      ysit, ysi, ysib, git, gi, gib,
      &      critr, ncrit, iscrn, twinst, cfl, vminz, act1)
c
      parameter (zero=0.0, half=0.5, one=1.0)
c
      logical first
      character*1 blank
      character esc
c
      dimension critr(ncrit)
c
c      TOP SECTION ARRAYS
c
      dimension pt (nzt), rogt(nzt),
      &      alpt(nzt), hgt (nzt),
      &      tgt (nzt), roft(nzt),
      &      tft (nzt), hft (nzt),
      &      xat (nzt), ysit(nzt), git(nzt)
      dimension ugt(nzt), uft(nzt)
c
c      MIDDLE SECTION ARRAYS
c
      dimension nx(nchn)
      dimension p (nzp2, nxmax, nchn), rog(nzp2, nxmax, nchn),
      &      alp(nzp2, nxmax, nchn), hg (nzp2, nxmax, nchn),
      &      tg (nzp2, nxmax, nchn), rof(nzp2, nxmax, nchn),
      &      tf (nzp2, nxmax, nchn), hf (nzp2, nxmax, nchn),
      &      xa (nzp2, nxmax, nchn),
      &      ysi(nzp2, nxmax, nchn), gi (nzp2, nxmax, nchn)
      dimension ugz(nzp3, nxmax, nchn), ufz(nzp3, nxmax, nchn),
      &      wgx(nzp2, nxmax, nchn), wfx(nzp2, nxmax, nchn)
c
c      BOTTOM SECTION ARRAYS
c
      dimension pb (nzb), rogb(nzb),
      &      alpb(nzb), hgb (nzb),
      &      tgb (nzb), rofb(nzb),
      &      tfb (nzb), hfb (nzb),

```

```
      xab(nzb), ysib(nzb), gib(nzb)
      dimension ugb(nzb), ufb(nzb)
c
      data first/.true./
      data blank/' '/
      data hundrd/100.0/, cgpm/15850.32/, sumdt/0.0/, qgavg/0.0/
      data iclear/1/
c
c      COMPUTE FLOWRATES
c
      if (abs(uft(1)) .ge. vminz) then
         wt = sign(half, uft(1))
      else
         wt = half*uft(1)/vminz
      end if
      wtm = half + wt
      wtp = half - wt
      alpf = one - (wtm*alpp1 + wtp*alpt(1))
      qf = alpf*uft(1)*act1*cgpm
c
      if (abs(ugt(1)) .ge. vminz) then
         wt = sign(half, ugt(1))
      else
         wt = half*ugt(1)/vminz
      end if
      wtm = half + wt
      wtp = half - wt
      alpg = wtm*alpp1 + wtp*alpt(1)
      qg = alpg*ugt(1)*act1*cgpm
c
      if (first) qgprev = qg
c
c      COMPUTE AVERAGE GAS FLOWRATE
c
      qgavg = (qgavg*sumdt + half*(qgprev + qg)*delt)/(sumdt + delt)
      qgprev = qg
      sumdt = sumdt + delt
c
c      PRINT TO SCREEN IF iprint=1, OTHERWISE RETURN
c
      esc=char(27)
c
c      CLEAR SCREEN ON FIRST CALL
c
      if (first) then
         first = .false.
         write(*,10) esc
10      format(1x,a1,'[2J')
         sumdt = sumdt - delt
      end if
c
      if (iscrn.eq.2) goto 399
c
c      TOP SECTION
c
      if (iclear .eq. 1) write(*,1001) esc,(blank,k=1,80)
1001  format(1x,a1,'[1;1H',80(a1))
c
      write(*,101) esc,ppl,(pt(jz),jz=1,nzt)
101  format(1x,a1,'[1;1H','p t',5(1x,f10.2))
cc   write(*,101) esc,(ysit(jz),jz=1,nzt)
cc101 format(1x,a1,'[1;1H','y t',5(1x,f10.5))
c
      if (iclear .eq. 1) write(*,1002) esc,(blank,k=1,80)
```

```
1002 format(1x,a1,'[2;1H',80(a1))
c
      write(*,102) esc,alppl,(alpt(jz),jz=1,nzt)
102  format(1x,a1,'[2;1H','alp',5(1x,f10.6))
c
      if (iclear .eq. 1) write(*,1003) esc,(blank,k=1,80)
1003 format(1x,a1,'[3;1H',80(a1))
c
      write(*,103) esc,tgpl,(tgt(jz),jz=1,nzt)
103  format(1x,a1,'[3;1H','tgt',5(1x,f10.4))
cc   write(*,103) esc,(git(jz),jz=1,nzt)
cc103 format(1x,a1,'[3;1H','git',5(1x,e10.2))
c
      if (iclear .eq. 1) write(*,1004) esc,(blank,k=1,80)
1004 format(1x,a1,'[4;1H',80(a1))
c
      write(*,104) esc,tfpl,(tft(jz),jz=1,nzt)
104  format(1x,a1,'[4;1H','tft',5(1x,f10.4))
c
      if (iclear .eq. 1) write(*,1005) esc,(blank,k=1,80)
1005 format(1x,a1,'[5;1H',80(a1))
c
      write(*,105) esc,(ugt(jz),jz=1,nzt)
105  format(1x,a1,'[5;1H','ugt',5x,5(1x,f10.4))
c
      if (iclear .eq. 1) write(*,1006) esc,(blank,k=1,80)
1006 format(1x,a1,'[6;1H',80(a1))
c
      write(*,106) esc,(uft(jz),jz=1,nzt)
106  format(1x,a1,'[6;1H','uft',5x,5(1x,f10.4))
c
c   MIDDLE SECTION
c
      if (iclear .eq. 1) write(*,2001) esc,(blank,k=1,80)
2001 format(1x,a1,'[7;1H',80(a1))
c
      write(*,201) esc,(p (jz,1,1),jz=2,nzpl)
201  format(1x,a1,'[7;1H','p ',5x,5(1x,f10.2))
cc   write(*,201) esc,(ysl(jz,1,1),jz=2,nzpl)
cc201 format(1x,a1,'[7;1H','y ',5x,5(1x,f10.5))
c
      if (iclear .eq. 1) write(*,2002) esc,(blank,k=1,80)
2002 format(1x,a1,'[8;1H',80(a1))
c
      write(*,202) esc,(alp(jz,1,1),jz=2,nzpl)
202  format(1x,a1,'[8;1H','alp',5x,5(1x,f10.6))
c
      if (iclear .eq. 1) write(*,2003) esc,(blank,k=1,80)
2003 format(1x,a1,'[9;1H',80(a1))
c
      write(*,203) esc,(tg (jz,1,1),jz=2,nzpl)
203  format(1x,a1,'[9;1H','tg ',5x,5(1x,f10.4))
cc   write(*,203) esc,(gi (jz,1,1),jz=2,nzpl)
cc203 format(1x,a1,'[9;1H','gi ',5x,5(1x,e10.2))
c
      if (iclear .eq. 1) write(*,2004) esc,(blank,k=1,80)
2004 format(1x,a1,'[10;1H',80(a1))
c
      write(*,204) esc,(tf (jz,1,1),jz=2,nzpl)
204  format(1x,a1,'[10;1H','tf ',5x,5(1x,f10.4))
c
      if (iclear .eq. 1) write(*,2005) esc,(blank,k=1,80)
2005 format(1x,a1,'[11;1H',80(a1))
c
```

```
        write(*,205) esc, (ugz(jz,1,1), jz=2,nzp2)
205    format(1x,a1,'[11;1H','ugz',6(1x,f10.4))
c
        if (iclear .eq. 1) write(*,2006) esc, (blank,k=1,80)
2006    format(1x,a1,'[12;1H',80(a1))
c
        write(*,206) esc, (ufz(jz,1,1), jz=2,nzp2)
206    format(1x,a1,'[12;1H','ufz',6(1x,f10.4))
c
        if (iclear .eq. 1) write(*,2007) esc, (blank,k=1,80)
2007    format(1x,a1,'[13;1H',80(a1))
c
        write(*,207) esc, (wgx(jz,1,1), jz=2,nzp1)
207    format(1x,a1,'[13;1H','wgx',6(1x,f10.4))
c
        if (iclear .eq. 1) write(*,2008) esc, (blank,k=1,80)
2008    format(1x,a1,'[14;1H',80(a1))
c
        write(*,208) esc, (wfx(jz,1,1), jz=2,nzp1)
208    format(1x,a1,'[14;1H','wfx',6(1x,f10.4))
c
c        BOTTOM SECTION
c
        if (iclear .eq. 1) write(*,3001) esc, (blank,k=1,80)
3001    format(1x,a1,'[15;1H',80(a1))
c
        write(*,301) esc, (pb(jz), jz=1,nzb),ptb
301    format(1x,a1,'[15;1H','p b',5(1x,f10.2))
cc     write(*,301) esc, (ysib(jz), jz=1,nzb)
cc301  format(1x,a1,'[15;1H','y b',5(1x,f10.5))
c
        if (iclear .eq. 1) write(*,3002) esc, (blank,k=1,80)
3002    format(1x,a1,'[16;1H',80(a1))
c
        write(*,302) esc, (alpb(jz), jz=1,nzb),alptb
302    format(1x,a1,'[16;1H','alp',5(1x,f10.6))
c
        if (iclear .eq. 1) write(*,3003) esc, (blank,k=1,80)
3003    format(1x,a1,'[17;1H',80(a1))
c
        write(*,303) esc, (tgb(jz), jz=1,nzb),tgtb
303    format(1x,a1,'[17;1H','tgb',5(1x,f10.4))
cc     write(*,303) esc, (gib(jz), jz=1,nzb)
cc303  format(1x,a1,'[17;1H','gib',5(1x,e10.2))
c
        if (iclear .eq. 1) write(*,3004) esc, (blank,k=1,80)
3004    format(1x,a1,'[18;1H',80(a1))
c
        write(*,304) esc, (tfb(jz), jz=1,nzb),tftb
304    format(1x,a1,'[18;1H','tfb',5(1x,f10.4))
c
        if (iclear .eq. 1) write(*,3005) esc, (blank,k=1,80)
3005    format(1x,a1,'[19;1H',80(a1))
c
        write(*,305) esc, (ugb(jz), jz=1,nzb)
305    format(1x,a1,'[19;1H','ugb',5x,5(1x,f10.4))
c
        if (iclear .eq. 1) write(*,3006) esc, (blank,k=1,80)
3006    format(1x,a1,'[20;1H',80(a1))
c
        write(*,306) esc, (ufb(jz), jz=1,nzb)
306    format(1x,a1,'[20;1H','ufb',5x,5(1x,f10.4))
c
c        CONVERGENCE & OTHER INFO.
```



```

c
399  continue
c
      write(*,400) esc,tsec,delt,min(cfl,one),nitno,iitot
400  format(1x,a1,'[20;1H',' tsec: ',f9.3,' delt: ',f10.6,
      &      ' cfl: ',f7.4,' nitno: ',i3,' iitot: ',i4,1x,'<')
c
      write(*,401) esc,min(twinst,hundrd),qf,qg,qgavg
401  format(1x,a1,'[21;1H',' tw: ',f7.3,11x,
      &      ' qf(gpm): ',f7.2,' qg(gpm): ',f7.2,' qgavg: ',f7.2,' <')
c
      write(*,402) esc,min(critr(2),hundrd),min(critr(3),hundrd),
      &      critr(1),hundrd*dif,delh
402  format(1x,a1,'[22;1H',' twmax: ',f7.3,' twavg: ',f7.3,
      &      ' tsat: ',f7.3,' % dif ',f10.5,' h ',g12.5,1x,'<')
c
      write(*,403) esc,hundrd*difp, hundrd*difalp,hundrd*diftg,
      &      hundrd*diftf,hundrd*difxa, hundrd*difts
403  format(1x,a1,'[23;1H',' % dif: ',f6.1,' p ',f6.1,' alp ',
      &      f6.1,' tg ',f6.1,' tf ',f6.1,' xa ',f6.1,' ts',7x,'<')
c
      return
      end

```

PSAT

```

      subroutine psat(t,l,ps,dpsdt)
c
c *****
c *
c * INPUT:
c *      t = MIXTURE GAS OR LIQUID TEMPERATURE, K
c *      l = IDENTIFIER (l=1 FOR H2O, l=2 FOR D2O)
c *
c * OUTPUT:
c *      ps = SATURATION PRESSURE OF H2O OR D2O, Pa
c *      dpsdt = DERIVATIVE OF ps W.R.T. t
c *
c * RANGE:
c *      273K < t < 453K
c *
c *****
c
      parameter (two=2.0, three=3.0)
      dimension c1(2), c2(2), c3(2), c4(2)
c
c H2O PROPERTIES
c
      data c1(1)/-38.874/, c2(1)/0.29129/,
      &      c3(1)/-5.7014e-4/, c4(1)/4.0606e-7/
c
c D2O PROPERTIES
c
      data c1(2)/-39.686/, c2(2)/0.29393/,
      &      c3(2)/-5.7036e-4/, c4(2)/4.0230e-7/
c
      ps = exp(c1(1) + (c2(1) + (c3(1) + c4(1)*t)*t)*t)
      dpsdt = ps*(c2(1) + (two*c3(1) + (three*c4(1))*t)*t)
c
      return
      end

```

QWALL

```

      subroutine qwall (qw,f,qwg,dqf,dw,dqgdw,theta,gw,hspl,qonb,CHFq,

```

```

        tsurf,p,alp,xa,rog,rof,tg,tf,ugz,ufz,dhz,ar,
        tmo0,hmod,hactiv,tnklev,gap,tsec,dz,ribl,
        ribt,lorib,mat,iboil,ichf,matgas,persat,
        nsurf,na,napl,nxmax,nr,nrmax,nrmxp,nx,nz,
        nzp2,nzp3,nchn,ncyl,icent,iazl,nazc,htdamp,
        iradbc,cradi,itmod,xtp,ytp,ztp,ntp,intp,itype,
        nspln,ntpmax,ntptot,ilq)

C
C *****
C *
C * SUBROUTINE qwall
C *
C * SUBROUTINE TO CALCULATE SURFACE HEAT FLUXES THROUGHOUT THE
C * ASSEMBLY
C *
C *****
C implicit real (a-h,o-z), integer (i-n)
C
C logical dochf, dochen, docond, dofilm, domiki
C
C parameter (zero=0.0, half=0.50, one=1.0, four=4.0)
C parameter (alpmax=0.9999, ctok=273.15)
C parameter (mxnz=100)
C
C SURFACE DATA ARRAYS
C
C dimension qwf(nsurf,na,nz), dqfdw(nsurf,na,nz),
C          qwg(nsurf,na,nz), dqgdw(nsurf,na,nz),
C          tsurf(nsurf,na,nz), hspl(nsurf,na,nz),
C          qonb(nsurf,na,nz)
C
C dimension nazc(nxmax,nchn), ar(nrmxp,nz,ncyl),
C          iazl(nxmax,nchn), mat(nrmax,nz,ncyl)
C
C dimension ribl(ncyl), lorib(ncyl), nx(nchn),
C          ribt(ncyl), nr(ncyl), dz(nz)
C
C MIDDLE SECTION PHYSICAL DATA ARRAYS
C
C dimension p(nzp2,nxmax,nchn), dhz(nzp3,nxmax,nchn),
C          alp(nzp2,nxmax,nchn), xa(nzp2,nxmax,nchn),
C          rog(nzp2,nxmax,nchn), rof(nzp2,nxmax,nchn),
C          tg(nzp2,nxmax,nchn), tf(nzp2,nxmax,nchn),
C          ugz(nzp3,nxmax,nchn), ufz(nzp3,nxmax,nchn),
C          theta(nzp2,nxmax,nchn), gw(nzp2,nxmax,nchn),
C          chfq(nzp2,nxmax,nchn)
C
C LOCAL PHYSICAL PROPERTY ARRAYS
C
C dimension cond1(mxnz), cpl(mxnz), vis1(mxnz), diffm(mxnz),
C          condg(mxnz), cpg(mxnz), visg(mxnz), sigma(mxnz)
C
C dimension xtp(ntptot), ytp(ntpmax,nspln), ztp(ntpmax,nspln),
C          intp(nspln), itype(nspln), ntp(nspln)
C
C dimension ws(2)
C data wa/28.97/, ws(1)/18.016/, ws(2)/20.034/
C
C LOOP OVER ALL FLOW CHANNELS
C
C do 50 ichn=1,nchn
C   nsub = nx(ichn)
C   movz = mod(ichn-1,2)*na/8
C

```

```

c      FIND INNER AND OUTER SURFACE NUMBERS AND CORRESPONDING CYLINDERS,
c      BYPASS CALCULATIONS OVER FICTITIOUS SURFACE NUMBER 1
c
      isrfi = 2*ichn - 1 + icent
      isrfo = isrfi + 1
      if (isrfi.eq.1) isrfi=isrfo
c
      icyli = isrfi - ichn
      icylo = isrfo - ichn
      nri = nr(icyli)
      nrp = nri + 1
c
c      DETERMINE IF RIBS ARE PRESENT IN THE FLOW CHANNEL AND SET
c      THE RIB HALF THICKNESS (ribtk) AND LENGTH (ribln) AND THE
c      EFFECTIVENESS CALCULATION FLAGS FOR INNER AND OUTER SURFACES
c
      if (iorib(icylo).eq.-1) then
        ribln = ribl(icylo)
        ribtk = ribt(icylo)
        ieffi = 0
        iefft = 1
      else if (iorib(icyli).eq.+1 .and. icyli.ne.icylo) then
        ribln = ribl(icyli)
        ribtk = ribt(icyli)
        ieffi = 1
        iefft = 0
      else
        ribln = zero
        ribtk = zero
        ieffi = 0
        iefft = 0
      end if
c
c      LOOP OVER ALL AZIMUTHAL SUBCHANNEL POSITIONS
c
      do 40 ix=1,nsub
        iazf = iazl(ix,ichn)
        iazl = iazf + nazc(ix,ichn) - 1
c
c      CALCULATE PHYSICAL PROPERTIES IN AXIAL FLUID CELLS
c
      call conlaw (p(1,ix,ichn),tg(1,ix,ichn),tf(1,ix,ichn),
&                xa(1,ix,ichn),ilq,2,nzp2,visg,cpg,condg,diffm,
&                visl,cpl,condl,sigma)
c
c      LOOP OVER ALL AXIAL LEVELS
c
      do 30 iz=1,nz
        izp1 = iz + 1
        izp2 = iz + 2
        dhyc = half*(dhz(izp1,ix,ichn) + dhz(izp2,ix,ichn))
c
c      DETERMINE FLUID PROPERTIES WITHIN CELL
c
      pres = p(izp1,ix,ichn)
      alfa = alp(izp1,ix,ichn)
      xair = xa(izp1,ix,ichn)
c
      beta = one - alfa
      xstm = one - xair
      pstm = pres*xstm/(xstm + xair*ws(ilq)/wa)
      call tsat (pres,ilq,tfsat,xdum)
      call tsat (pstm,ilq,tssat,xdum)
c

```

```

c    LIQUID PROPERTIES -
c
      uliq = half*(ufz(izp1,ix,ichn) + ufz(izp2,ix,ichn))
      rhol = rof(izp1,ix,ichn)
      tliq = tf(izp1,ix,ichn)
      gliq = beta*rhol*abs(uliq)

```

```

c
c    GAS PROPERTIES -
c
      ugas = half*(ugz(izp1,ix,ichn) + ugz(izp2,ix,ichn))
      rhog = rog(izp1,ix,ichn)
      tgas = tg(izp1,ix,ichn)
      ggas = alfa*rhog*abs(ugas)

c
      call hfsat (tliq,ilq,hlsat,dhfdt)
      call hssat (pres,ilq,hgsat,dhgdp)
      hfg = hgsat - hlsat

```

```

c
c    SET AREA SUMMATION VALUES AND CALCULATION FLAGS
c
      suma = zero
      sumw = zero
      gamma = zero

```

```

c
      dochf = .true.
      dochen = .true.
      docond = .true.
      dofilm = .true.
      domiki = .true.

```

```

c
c    LOOP OVER INNER AND OUTER SURFACES
c
      do 20 isurf=isrfi,isrfo
        if (isurf.eq.isrfo) then
          awall = ar(1,iz,icylo)
          mwall = mat(1,iz,icylo)
          ieff = ieffo
        else
          awall = ar(nrp,iz,icyli)
          mwall = mat(nri,iz,icyli)
          ieff = ieffi
        end if
      end do

```

```

c
c    LOOP OVER ALL SOLID CELL AZIMUTHAL POSITIONS
c
      do 10 iaz=iazf,iazl
        ia = iaz - na*(iaz/napl)
        twall = tsurf(isurf,ia,iz)
        twalk = twall + ctok
      end do

```

```

c
c    FIND NUMBER OF RIB SURFACES WITHIN THE SOLID CELL
c    ASSUMES na = 1, 4, OR m*8 WHERE m = 1, 2, ...
c    AND nsub = 1 OR 4 (NOTE: CANNOT USE na < nsub)
c

```

```

      if (na.le.8) then
        nribs = 8/na
      else if (nsub.eq.1) then
        itest = mod(iaz+movz,na/4)
        if (itest.le.1) then
          nribs = 1
        else
          nribs = 0
        end if
      else

```

```

      nribs = iazf/iaz + iaz/iazl
      end if
      arib = nribs*dz(iz)/awall
C
C      INITIALIZE HEAT FLUXES, DERIVATIVES, AND VAPOR GENERATION
C
      qf = zero
      qg = zero
      dqf = zero
      dqg = zero
      vapor = zero
C
      hfc = zero
      wet = one
      tchf = twalk + one
C
C      DETERMINE HEAT TRANSFER REGIME
C
      if (alfa.gt.alpmax) then
C
C      SINGLE PHASE VAPOR - SIEDER-TATE CORRELATION:
C
      wet = zero
      call visgs (pres,twalk,xair,ilq,visw)
      call hconv (qg,dqg,hfc,twalk,tgas,ggas,
&                dhyc,visg(izpl),condg(izpl),
&                cpg(izpl),visw,zero,2)
C
C      CHECK FOR VAPOR CONDENSATION AT WALL
C
      if (twalk.lt.tssat) then
&        call cdens (qg,dqg,vapor,hfc,twalk,tssat,
&                  uliq,ugas,rhol,rhog,condl(izpl),
&                  cpl(izpl),visl(izpl),visg(izpl),
&                  dhyc,hfg,tgas,alfa,docond)
&
&        end if
C
      else if (iboil.eq.-1) then
C
C      USE SRL SINGLE-PHASE CORRELATION:
C
      call vislq (twalk,ilq,visw,dvdtw)
      call srlhtc (hfc,qf,dqf,twalk,tliq,gliq,ggas,
&                rhol,rhog,alfa,visl(izpl),dvdtw,
&                visg(izpl),visw,condl(izpl),
&                cpl(izpl),dhyc,arib,ieff,ribln,
&                ribtk,mwall)
C
      else if (iboil.eq.0) then
C
C      SINGLE PHASE LIQUID - SIEDER-TATE CORRELATION:
C
      call vislq (twalk,ilq,visw,dvdtw)
      call hconv (qf,dqf,hfc,twalk,tliq,gliq,
&                dhyc,visl(izpl),condl(izpl),
&                cpl(izpl),visw,dvdtw,2)
C
      else if (iboil.eq.1) then
C
C      MIKIC-ROHSENOW BOILING CURVE WITH SRL SINGLE PHASE CORRELATION:
C
      call mikic (qf,dqf,vapor,qchf,qnb,hfc,tchf,
&                twalk,tliq,tgas,tfsat,pres,alfa,
&                beta,xair,gliq,ggas,rhol,rhog,

```

```

        visl(izpl),visg(izpl),condl(izpl),
        cpl(izpl),dhyc,arib,ieff,ribln,
        ribtk,mwall,hfg,hlsat,hgsat,
        sigma(izpl),matgas,persat,domiki,
        dochf,ichf,ilq)
c
        else
c
c     NUCLEATE BOILING - CHEN CORRELATION:
c
        call chen (qf,dqf,vapor,qchf,tchf,hfc,twalk,
        tliq,tgas,tfsat,pres,alfa,beta,
        xair,gliq,ggas,rhol,rhog,visl(izpl),
        visg(izpl),condl(izpl),cpl(izpl),
        dhyc,hfg,hlsat,hgsat,sigma(izpl),
        dochen,dochf,ichf,ilq)
        end if
c
        if (twalk.gt.tchf) then
c
c     FILM OR TRANSITION BOILING -
c     BROMLEY-POMERANZ CORRELATION FOR LIQUID AND
c     DOUGALL-ROHSENOW CORRELATION FOR GAS:
c
        call filmb (qf,dqf,qg,dqg,vapor,wet,qchf,
        tchf,twalk,tliq,tgas,tfsat,pres,
        alfa,beta,xair,uliq,ugas,rhol,
        rhog,condg(izpl),cpg(izpl),
        visg(izpl),dhyc,hfg,hlsat,hgsat,
        sigma(izpl),dofilm,ilq)
        end if
c
        suma = suma + awall
        sumw = sumw + wet*awall
        gamma = gamma + vapor*awall
c
c     SET UP WEIGHTED HEAT FLUX AND DERIVATIVE ARRAYS AND STORE
c     SINGLE PHASE HEAT TRANSFER COEFFICIENTS
c
        wgtm = one - htdamp
        qwf(isurf,ia,iz) = htdamp*qf +
        wgtm*qwf(isurf,ia,iz)
        qwg(isurf,ia,iz) = htdamp*qg +
        wgtm*qwg(isurf,ia,iz)
        dqfdw(isurf,ia,iz) = htdamp*dqf +
        wgtm*dqfdw(isurf,ia,iz)
        dqgdw(isurf,ia,iz) = htdamp*dqg +
        wgtm*dqgdw(isurf,ia,iz)
        hspl(isurf,ia,iz) = htdamp*hfc +
        wgtm*hspl(isurf,ia,iz)
        qonb(isurf,ia,iz) = htdamp*qnb +
        wgtm*qonb(isurf,ia,iz)
c
        continue
10      continue
20
c
c     CALCULATE FRACTIONAL WETTED SURFACE AREA IN FLUID CELL,
c     ALSO STORE WALL VAPOR GENERATION AND CHF TEMPERATURE
c
        theta(izpl,ix,ichn) = sumw/suma
        chfq(izpl,ix,ichn) = qchf
        gw(izpl,ix,ichn) = gamma
c
30      continue

```

```

40      continue
50      continue
c
      inx = intp(itmod)
      ityp = itype(itmod)
      ntps = ntp(itmod)
      tmod = tmod0*yvalu(ityp,ntps,xtp(inx),ytp(1,itmod),
&          ztp(1,itmod),tsec)
      if (iradbc.eq.1) tmod4 = tmod**4
c
      botnod = hactiv + gap
      do 70 iz=1,nz
c
c      ASSIGN OUTER SURFACE HEAT TRANSFER COEFFICIENTS
c      BASED ON THE TANK LEVEL
c
      topnod = botnod
      botnod = topnod - dz(iz)
c
      if (botnod.ge.tnklev) then
          fract = zero
      else if (topnod.le.tnklev) then
          fract = one
      else
          fract = (tnklev - botnod)/dz(iz)
      end if
      fhmod = fract*hmod
      fradi = (one - fract)*cradi
c
      do 60 ia=1,na
c
c      SET THE CENTERLINE HEAT FLUXES AND DERIVATIVES TO ZERO
c
      qwf(1,ia,iz) = zero
      qwg(1,ia,iz) = zero
      dqfdw(1,ia,iz) = zero
      dqgdw(1,ia,iz) = zero
c
c      COMPUTE THE HEAT FLUXES AND DERIVATIVES AT THE OUTER MOST SURFACE
c      EITHER A RADIATION OR A CONVECTIVE BOUNDARY CONDITION IS IMPOSED
c
      if (iradbc.eq.1 .and. fract.eq.zero) then
          tsurf3 = tsurf(nsurf,ia,iz)**3
          qsurf = cradi*(tsurf(nsurf,ia,iz)*tsurf3 - tmod4)
          dqsrf = four*cradi*tsurf3
      else if (iradbc.eq.1 .and. fract.lt.one) then
          tsurf3 = tsurf(nsurf,ia,iz)**3
          qsurf = fradi*(tsurf(nsurf,ia,iz)*tsurf3 - tmod4) +
&          fhmod*(tsurf(nsurf,ia,iz) - tmod)
          dqsrf = four*fradi*tsurf3 + fhmod
      else
          qsurf = fhmod*(tsurf(nsurf,ia,iz) - tmod)
          dqsrf = fhmod
      end if
      qwf(nsurf,ia,iz) = qsurf
      qwg(nsurf,ia,iz) = zero
      dqfdw(nsurf,ia,iz) = dqsrf
      dqgdw(nsurf,ia,iz) = zero
c
c      60      continue
c      70      continue
c
      return
      end

```

RADSHF

```

      subroutine radshf (frdim,rphi,diam,ncyl,nrmax,nrmxp,
      & nfrst,nlast,mnrrp,nrp,nout)

```

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

c

```

      Purpose: This routine computes the unnormalized area-averaged
      radial power density for each solid radial node in the
      core (fuel) region.

```

Subroutine history

- 1983, "CREDIT Documentation and the Mark 15 Subroutine,"
McAllister, Knight and Hamm, DPST-83-402.
- 1989, "FLOWTRAN: An Algorithm for Describing the Thermal-
Hydraulic Behavior of SRP Assemblies (U) (Supplement 1),"
Aleman, et al, DPSTM-140-I.
- 1992, FLOWTRAN-TF implementation

Arguments

NAME	I/O	TYPE	DIM	DESCRIPTION
maxpt		I*4		Maximum number of points in local arrays.
maxpl		I*4		maxpt + 1
mnrrp	I	I*4		Maximum number of points in radial heat generation polynomial or maximum number of coefficients.
ncyl	I	I*4		Number of solid cylinders
nfrst	I	I*4	ncyl	Radial index of first node
nlast	I	I*4	ncyl	Radial index of last node
nout	I	I*4		Standard output
nrmax	I	I*4	ncyl	Maximum number of radial nodes per cylinder.
nrmxp	I	I*4	ncyl	nrmax + 1
nrp	I	I*4	ncyl	Number of points in radial heat generation polynomial or number of coefficients.
amat		R*4	maxpt,maxpl	Matrix used in solving for coefficients of polynomial.
bvct		R*4	maxpt	Vector of coefficients
phir		R*4	maxpt	Work array
diam	I	R*4	nrmxp,ncyl	Solid node diameter
rphi	I	R*4	mnrrp,ncyl	Radial heat generation values at solid node radial boundaries.
frdim	O	R*4	nrmax,ncyl	Radial heat generation per solid node. (unnormalized)

```

      implicit real (a-h,o-z), integer (i-n)
      parameter (zero=0.0, half=0.5, one=1.0,
      & maxpt=25, maxpl=maxpt+1)

```

```

      dimension frdim(nrmax,ncyl), nfrst(ncyl),
      & diam(nrmxp,ncyl), nlast(ncyl),
      & rphi(mnrrp,ncyl), nrp(ncyl)

```

LOCAL ARRAYS

```

      dimension amat(maxpt,maxpl), bvct(maxpt), phir(maxpt)

```

```

      if (mnrrp.gt.maxpt) then

```



```

        write (nout,200) mnrp
        stop
    end if
c
c    LOOP OVER CYLINDERS
c
    write (nout,210)
    do 150 icyln=1,ncyln
c
c    IDENTIFY ATTRIBUTES OF CYLINDER
c
c    NUMBER OF DATA POINTS AT WHICH POWER SHAPE GIVEN
c
        nr = abs(nrp(icyln))
        nr1 = nr + 1
c
c    FIRST AND LAST NODE NUMBERS IN CORE REGION OF CYLINDER
c
        nf = nfirst(icyln)
        if (nf.eq.0) goto 150
        nl = nlast(icyln)
c
c    INNER AND OUTER RADII OF CORE REGION
c
        rinner = half*diam(nf,icyln)
        router = half*diam(nl+1,icyln)
        delr = router - rinner
        rdelr = one/delr
c
c    CHECK IF SHAPE POLYNOMIAL IS TO BE CALCULATED OR HAS BEEN
c    DEFINED ON INPUT
c
        if (nrp(icyln).lt.0) then
c
c    LOAD POLYNOMIALS DIRECTLY FROM INPUT
c
            do 10 j=1,nr
                bvct(j) = rphi(j,icyln)
10          continue
            goto 90
        end if
c
c    CALCULATE POLYNOMIALS, LOAD GIVEN SHAPE DATA 'BACKWARDS'
c
        do 20 j=1,nr
            phir(nr-j+1) = rphi(j,icyln)
20          continue
c
c    COMPUTE COEFFICIENTS FOR THE RADIAL HEAT GENERATION
c    POLYNOMIAL
c
c    DEFINE THE FIRST COLUMN OF COEFFICIENTS IN amat, SPECIFY bvct
c
        do 30 j=1,nr
            amat(j,1) = one
            amat(j,nr1) = phir(j)
            bvct(j) = phir(j)
30          continue
c
c    DEFINE THE SECOND COLUMN OF COEFFICIENTS AS A FUNCTION OF
c    RADIAL DISTANCE
c
c    THE DISTANCE BETWEEN CLADDING SURFACES IS EQUI-DIVIDED GIVEN
c    N DATA POINTS FOR (N-1)'TH ORDER POLYNOMIAL, THE

```

```
c      POLYNOMIAL WILL BE IN TERMS OF THE DIMENSIONLESS RADII'S
c      (router-r)/(router-rinner), I.E., ARGUMENT SPANS 1.0-->0.0
c
c      zb = float(nr-1)
c      do 40 i=1,nr
c          amat(i,2) = float(i-1)/zb
40      continue
c
c      DEFINE (n-1) HIGHER ORDER TERMS EQUAL TO THE NUMBER OF ROWS
c      FOR n UNKNOWNNS
c
c      do 60 kk=3,nr
c          kkml = kk - 1
c          do 50 jj=1,nr
c              amat(jj,kk) = amat(jj,2)*amat(jj,kkml)
50      continue
60      continue
c
c      SUBROUTINE CHLSKI DETERMINES COEFFICIENTS FOR N'TH ORDER
c      POLYNOMIAL CURVE FIT BY SOLVING 'N' SIMULTANEOUS LINEAR
c      EQUATIONS
c
c      call chlski (amat,nr,nr1,bvct)
c
c      COMPUTE rphi VALUES USING bvct COEFFICIENTS AND COMPARE TO
c      INPUT VALUES
c
c      dr = delr/(float(nr) - one)
c      r = rinner
c      write (nout,220)
c      do 80 j=1,nr
c          rsf = zero
c          rb = (router - r)*rdelr
c          do 70 k=1,nr
c              kml = k - 1
c              if (kml .eq. 0) then
c                  rsf = rsf + bvct(1)
c              else
c                  rsf = rsf + bvct(k)*rb**kml
c              end if
70      continue
c          r = r + dr
c          write (nout,230) j,icyln,rphi(j,icyln),rsf
80      continue
c
c      COMPUTE AREA-AVERAGED RADIAL POWER DENSITY FOR EACH SOLID NODE
c      IN CORE REGION.
c
c      LOOP OVER NODES IN CYLINDER CORE
c
c
90      write (nout,240)
c      do 110 ir=nf,nl
c          etik = one
c          etok = one
c          frdim(ir,icyln) = zero
c          do 100 k=1,nr
c              rk = float(k)
c              rkpl = float(k+1)
c              ri = half*diam(ir,icyln)
c              ro = half*diam(ir+1,icyln)
c              rbi = (router - ri)*rdelr
c              rbo = (router - ro)*rdelr
c              fi = (router + rk*ri)*rbi**k
c              fo = (router + rk*ro)*rbo**k
```

```

        frdim(ir,icyln) = frdim(ir,icyln) + bvct(k)*delr
        * (fi - fo)/(rk*rkpl)
100      continue
        area = half*(ro**2 - ri**2)
        frdim(ir,icyln) = frdim(ir,icyln)/area
        write (nout,250) ir, icyln, ri, ro, frdim(ir,icyln)
110      continue
150      continue
c
c      WRITE FORMATS
c
200      format ('>>>fatal error in radshp.  number of data points in',
        &          ' core region ',i3,' exceeds 25.',/, ' recompile radshp',
        &          ' and chlski with larger dimensions.',/, ' stopping ...',/)
210      format (/,1x,'*****radshp*****')
220      format (/,1x,'Coeff      Cylinder      rphi      rphi ',/,
        &          '1x,'Index      Index      (data)      (calc) ',/,
        &          '1x,'-----')
230      format (3x,i1,11x,i1,9x,f8.6,5x,f8.6)
240      format (/,1x,'
        &          '1x,'ir      icyln      inner      outer      frdim ',/,
        &          '1x,'-----')
250      format (1x,i1,6x,i1,5x,e12.6,2x,e12.6,2x,f8.6)
c
      return
      end

```

READIN

```

      subroutine readin
c
c      *****
c      *
c      *      SUBROUTINE readin
c      *
c      *      SUBROUTINE TO STRIP USER ADDED COMMENTS OUT OF THE
c      *      INPUT FILE.  USER COMMENTS ARE RECOGNIZED AS BEING
c      *      DELIMITED BY AN !
c      *
c      *      THE USER GENERATED INPUT IS READ FROM UNIT ntmp
c      *      A MODIFIED INPUT FILE THAT IS READ BY THE
c      *      FLOWTRAN-TF CODE IS WRITTEN TO UNIT ninp
c      *
c      *****
c
      implicit real (a-h,o-z), integer (i-n)
      parameter (maxbuf=20, icmax=80)
c
      character*80 inline, outlin, buffer(maxbuf)
      character*10 digits
      character*1 letter
      logical blok, dump, look, scan, start
c
      dimension length(maxbuf)
      common /iounit/ ninp, nout, ndmp, ntmp, nrsti, nrsto
c
      data digits / '0123456789' /
c
      blok = .false.
10      read (ntmp,200,end=100) inline
      if (inline(1:1).eq.'!') goto 10
c
      LOOK FOR FIRST OCCURRENCE OF !, $, OR &
c
      dump = .false.

```

```
        look = .true.
        scan = .false.
        start = .false.
c
        lmax = icmax
        do 20 ichr=2,icmax
            letter = inline(ichr:ichr)
            if (look .and. (letter.eq.'!' .or.
6              letter.eq.'$' .or.
6              letter.eq.'&')) then
                lmax = ichr - 1
                look = .false.
                if (letter.eq.'$') then
                    if (blok) then
                        nwrite = ntime
                        ldmp = inblk
                        dump = .true.
                    end if
                    scan = .true.
                    blok = .true.
                    inblk = 1
                    ntime = 0
                else if (blok .and. letter.eq.'&') then
                    inblk = inblk + 1
                    goto 30
                else
                    goto 25
                end if
            end if
c
c        SCAN THE LINE FOR A NUMERICAL VALUE
c
        else if (scan) then
c
            do 15 id=1,10
                if (letter.eq.digits(id:id)) then
                    start = .true.
                    ntime = 10*ntime + id - 1
                    goto 20
                end if
15            continue
                if (start) goto 30
            end if
c
c        20 continue
c
c        NO BLOCK IDENTIFICATION CHARACTERS FOUND
c
25        if (blok) then
            nwrite = ntime
            ldmp = inblk
            dump = .true.
            blok = .false.
        end if
c
c        STRIP TRAILING BLANKS FROM THE LINE
c
30        len = 0
        do 40 ichr=lmax,1,-1
            if (inline(ichr:ichr).ne.' ') then
                len = ichr
                goto 50
            end if
40        continue
c
```

```

c      IGNORE BLANK LINES
c
50     if (len.gt.0) then
c
c      AT END OF BLOCK WRITE DATA BLOCKS
c
c          if (dump) then
c              do 70 it=1,nwrite
c                  do 60 iline=1,ldmp
c                      len1 = length(iline)
c                      outlin = buffer(iline)
c                      write (ninp,200) outlin(1:len1)
60                 continue
70             continue
c          end if
c
c      SAVE DATA BLOCKS OR WRITE SINGLE LINES
c
c          if (blok) then
c              buffer(inblk) = inline(1:len)
c              length(inblk) = len
c          else
c              write (ninp,200) inline(1:len)
c          end if
c      end if
c      goto 10
c
c      CHECK IF THE FILE ENDED WHILE IN A DATA BLOCK
c
c
100    if (blok) then
c          do 120 it=1,ntime
c              do 110 iline=1,inblk
c                  len = length(iline)
c                  outlin = buffer(iline)
c                  write (ninp,200) outlin(1:len)
110         continue
120     continue
c      end if
c      rewind (unit=ninp)
c
c
200    format (a)
c
c      return
c      end

```

RESET

```

subroutine reset (ts,tsurf,tsn,tsrfn,
&                p ,alp ,xa ,rog ,rof ,hg ,hf ,tg ,tf ,
&                pn ,alpn ,xan ,rogn ,rofn ,hgn ,hfn ,tgn ,tfn ,
&                pt ,alpt ,xat ,rogt ,roft ,hgt ,hft ,tgt ,tft ,
&                ptn ,alptn ,xatn ,rogtn ,roftn ,hgtn ,hftn ,tgt ,tftn ,
&                pb ,alpb ,xab ,rogb ,rofb ,hgb ,hfb ,tgb ,tfb ,
&                pbn ,alpb ,xabn ,rogbn ,rofbn ,hgbn ,hfbn ,tgbn ,tfn ,
&                ppl ,xapl ,rogpl ,rofpl ,hgpl ,hfpl ,tgpl ,tfpl ,
&                ppln ,xapln ,rogpln ,rofpln ,hgpln ,hfpln ,tgpln ,tfpln ,
&                ptb ,xatb ,rogtb ,roftb ,hgtb ,hftb ,tgtb ,tftb ,
&                ptn ,xatbn ,rogtbn ,roftbn ,hgtn ,hftbn ,tgtbn ,tftbn ,
&                alppl ,alppln ,alptb ,alptbn ,nzp2 ,nxmax ,nchn ,nzt ,
&                nzb ,nrmax ,na ,nz ,ncyl ,nsurf)
c
c      *****
c      *
c      * SUBROUTINE reset
c      *
c      *

```

```

c      * SUBROUTINE TO STORE NEW CALCULATED VALUES FOR THE      *
c      * FLUID VARIABLES IN THE OLD TIME SLOTS IN PREPARATION    *
c      * FOR THE NEXT TIME STEP. THE TRANSFER IS ACCOMPLISHED    *
c      * THROUGH MULTIPLE CALLS TO SUBROUTINE move.              *
c      *                                                           *
c      *                                                           *
c      *****
c      implicit real (a-h,o-z), integer (i-n)
c
c      SOLID VARIABLES
c
c      dimension ts(nrmax,na,nz,ncyl), tsurf(nsurf,na,nz),
c      &          tsn(nrmax,na,nz,ncyl), tsrfn(nsurf,na,nz)
c
c      MIDDLE SECTION VARIABLES
c
c      dimension p(nzp2,nxmax,nchn), pn(nzp2,nxmax,nchn),
c      &          alp(nzp2,nxmax,nchn), alpn(nzp2,nxmax,nchn),
c      &          xa(nzp2,nxmax,nchn), xan(nzp2,nxmax,nchn),
c      &          rog(nzp2,nxmax,nchn), rogn(nzp2,nxmax,nchn),
c      &          rof(nzp2,nxmax,nchn), rofn(nzp2,nxmax,nchn),
c      &          hg(nzp2,nxmax,nchn), hgn(nzp2,nxmax,nchn),
c      &          hf(nzp2,nxmax,nchn), hfn(nzp2,nxmax,nchn),
c      &          tg(nzp2,nxmax,nchn), tgn(nzp2,nxmax,nchn),
c      &          tf(nzp2,nxmax,nchn), tfn(nzp2,nxmax,nchn)
c
c      TOP SECTION VARIABLES
c
c      dimension pt(nzt), ptn(nzt),
c      &          alpt(nzt), alptn(nzt),
c      &          xat(nzt), xatn(nzt),
c      &          rogt(nzt), rogtn(nzt),
c      &          roft(nzt), roftn(nzt),
c      &          hgt(nzt), hgtn(nzt),
c      &          hft(nzt), hftn(nzt),
c      &          tgt(nzt), tgtn(nzt),
c      &          tft(nzt), tftn(nzt)
c
c      BOTTOM SECTION VARIABLES
c
c      dimension pb(nzb), pbn(nzb),
c      &          alpb(nzb), alpbn(nzb),
c      &          xab(nzb), xabn(nzb),
c      &          rogb(nzb), rogbn(nzb),
c      &          rofb(nzb), rofbn(nzb),
c      &          hgb(nzb), hgbn(nzb),
c      &          hfb(nzb), hfbn(nzb),
c      &          tgb(nzb), tgbn(nzb),
c      &          tfb(nzb), tfbn(nzb)
c
c      RESET SOLID VARIABLES
c
c      nsold = nrmax*na*nz*ncyl
c      nsrfs = nsurf*na*nz
c      call move(ts,tsn,nsold)
c      call move(tsurf,tsrfn,nsrfs)
c
c      RESET MIDDLE SECTION VARIABLES
c
c      ncell = nzp2*nxmax*nchn
c      call move(p,pn,ncell)
c      call move(alp,alpn,ncell)
c      call move(xa,xan,ncell)
c      call move(rog,rogn,ncell)

```

```

      call move (rof,rofn,ncell)
      call move (hg,hgn,ncell)
      call move (hf,hfn,ncell)
      call move (tg,tgn,ncell)
      call move (tf,tfn,ncell)
c
c   RESET TOP SECTION VARIABLES
c
      call move (pt,ptn,nzt)
      call move (alpt,alptn,nzt)
      call move (xat,xatn,nzt)
      call move (rogt,rogt,nzt)
      call move (roft,roftn,nzt)
      call move (hgt,hgt,nzt)
      call move (hft,hftn,nzt)
      call move (tgt,tgt,nzt)
      call move (tft,tftn,nzt)
c
c   RESET BOTTOM SECTION VARIABLES
c
      call move (pb,pbn,nzb)
      call move (alpb,alpb,nzb)
      call move (xab,xabn,nzb)
      call move (rogb,rogb,nzb)
      call move (rofb,rofb,nzb)
      call move (hgb,hgb,nzb)
      call move (hfb,hfb,nzb)
      call move (tgb,tgb,nzb)
      call move (tfb,tfb,nzb)
c
c   RESET PLENUM VARIABLES
c
      ppln = ppl
      alppln = alppl
      xapln = xapl
      tgpln = tgpl
      tfpln = tfpl
      rogpln = rogpl
      rofpln = rofpl
      hgpln = hgpl
      hfpln = hfpl
c
c   RESET TANK BOTTOM VARIABLES
c
      ptbn = ptb
      alptbn = alptb
      xatbn = xatb
      tgtbn = tgtb
      tftbn = tftb
      rogtbn = rogtb
      roftbn = roftb
      hgtbn = hgtb
      hftbn = hftb
c
      return
      end

```

RESTR

```

      subroutine restr (ts,tsurf,tsn,tsrfn,qwf,qwg,dqfdw,dqgdw,
&
&      pt ,alpt ,xat ,rogt ,roft ,hgt ,hft ,tgt ,tft ,
&      ptn,alptn,xatn,rogt,n,roft,n,hgt,n,hft,n,tgt,n,tft,n,
&      p ,alp ,xa ,rog ,rof ,hg ,hf ,tg ,tf ,
&      pn ,alpn ,xan ,rogn ,rofn ,hgn ,hfn ,tgn ,tfn ,
&      pb ,alpb ,xab ,rogb ,rofb ,hgb ,hfb ,tgb ,tfb ,

```

```

&          pbn,alpbn,xabn,rogbn,rofbn,hgbn,hfbn,tgbn,tfbn,
&          ugt,uft,wgx,wfx,ugz,ufz,ugb,ufb,citn,cizn,cixn,
&          cibn,hfit,hfi,hfib,hgit,hgi,hgib,akgit,akgi,
&          akgib,git,gi,gib,eit,ei,eib,ysit,ysi,ysib,
&          hspl,qonb,nx,nr,tsec0)

C
C *****
C *
C * SUBROUTINE restrt
C *
C * SUBROUTINE TO INITIALIZE FLUID VARIABLE ARRAYS BY READING
C * DATA FROM RESTART FILE AT UNIT nrsti
C *
C *****
C implicit real (a-h,o-z), integer (i-n)

C
C common /iounit/ ninp, nout, ndmp, ntmp, nrsti, nrsto
C include 'params.inc'

C
C SOLID VARIABLES
C
C dimension ts(nrmax,na,nz,ncyln),
&          tsn(nrmax,na,nz,ncyln),
&          nr(ncyln)

C
C dimension qwf(nsurf,na,nz), dqfdw(nsurf,na,nz),
&          qwg(nsurf,na,nz), dqgdw(nsurf,na,nz),
&          qonb(nsurf,na,nz), hspl(nsurf,na,nz),
&          tsurf(nsurf,na,nz), tsrfn(nsurf,na,nz)

C
C MIDDLE SECTION PHYSICAL PARAMETERS
C
C dimension p(nzp2,nxmax,nchn), pn(nzp2,nxmax,nchn),
&          alp(nzp2,nxmax,nchn), alpn(nzp2,nxmax,nchn),
&          xa(nzp2,nxmax,nchn), xan(nzp2,nxmax,nchn),
&          rog(nzp2,nxmax,nchn), rogn(nzp2,nxmax,nchn),
&          rof(nzp2,nxmax,nchn), rofn(nzp2,nxmax,nchn),
&          hg(nzp2,nxmax,nchn), hgn(nzp2,nxmax,nchn),
&          hf(nzp2,nxmax,nchn), hfn(nzp2,nxmax,nchn),
&          tg(nzp2,nxmax,nchn), tgn(nzp2,nxmax,nchn),
&          tf(nzp2,nxmax,nchn), tfn(nzp2,nxmax,nchn),
&          gi(nzp2,nxmax,nchn), ei(nzp2,nxmax,nchn),
&          ugz(nzp3,nxmax,nchn), ufz(nzp3,nxmax,nchn),
&          wxg(nzp2,nxmax,nchn), wfx(nzp2,nxmax,nchn),
&          cizn(nzp3,nxmax,nchn), cixn(nzp3,nxmax,nchn),
&          hfi(nzp2,nxmax,nchn), hgi(nzp2,nxmax,nchn),
&          akgi(nzp2,nxmax,nchn), ysi(nzp2,nxmax,nchn),
&          nx(nchn)

C
C TOP SECTION PHYSICAL PARAMETERS
C
C dimension pt(nzt), ptn(nzt),
&          alpt(nzt), alptn(nzt),
&          xat(nzt), xatn(nzt),
&          rogt(nzt), rogt n(nzt),
&          roft(nzt), roftn(nzt),
&          hgt(nzt), hgt n(nzt),
&          hft(nzt), hftn(nzt),
&          tgt(nzt), tgt n(nzt),
&          tft(nzt), tftn(nzt),
&          git(nzt), eit(nzt),
&          ugt(nzt), uft(nzt),
&          citn(nzt), hfit(nzt),
&          hgit(nzt), akgit(nzt),

```



```

      &      ysit(nzt)
C
C      BOTTOM SECTION PHYSICAL PARAMETERS
C
      dimension pb(nzb), pbn(nzb),
      &      alpb(nzb), alpbn(nzb),
      &      xab(nzb), xabn(nzb),
      &      rogb(nzb), rogbn(nzb),
      &      rofb(nzb), rofbn(nzb),
      &      hgb(nzb), hgbn(nzb),
      &      hfb(nzb), hfbn(nzb),
      &      tgb(nzb), tgbn(nzb),
      &      tfb(nzb), tfbn(nzb),
      &      gib(nzb), eib(nzb),
      &      ugb(nzb), ufb(nzb),
      &      cibn(nzb), hfib(nzb),
      &      hgib(nzb), akgeb(nzb),
      &      ysib(nzb)
C
C      READ BINARY OR ASCII RESTART FILE
C
      if (istart.gt.0) then
C
C      READ BINARY RESTART FILE
C
      read (nrsti) tsec0, delt
C
C      INITIALIZE SOLID TEMPERATURES
C
      do 10 icyln=1,ncyln
         nri = nr(icyln)
         read (nrsti) ((ts(ir,ia,iz,icyln), iz=1,nz),
      &                  ia=1,na),
      &                  ir=1,nri)
10    continue
C
C      INITIALIZE SURFACE HEAT FLUXES, HEAT FLUX DERIVATIVES,
C      SINGLE PHASE HEAT TRANSFER COEFFICIENTS, ONB HEAT FLUXES,
C      AND SURFACE TEMPERATURES
C
      read (nrsti) ((qwf(isurf,ia,iz), qwg(isurf,ia,iz),
      &      dqfdw(isurf,ia,iz), dqgdw(isurf,ia,iz),
      &      hspl(isurf,ia,iz), qonb(isurf,ia,iz),
      &      tsurf(isurf,ia,iz), iz=1,nz), ia=1,na),
      &      isurf=1,nsurf)
C
C      BEGIN FLUID INITIALIZATION:
C
C      READ LOCAL PRESSURE, VOID FRACTION, AIR MASS FRACTION,
C      GAS TEMPERATURE, FLUID TEMPERATURE, GAS DENSITY, FLUID
C      DENSITY, GAS ENTHALPY, FLUID ENTHALPY, INTERFACIAL MASS
C      AND ENERGY TRANSFER RATES, AND GAS AND FLUID VELOCITIES
C
C      PLENUM
C
      read (nrsti) ppl, alppl, xapl, tgpl, tfpl,
      &      rogpl, rofpl, hgpl, hfpl
C
C      TOP SECTION
C
      read (nrsti) ( pt(jz),
      &      alpt(jz), xat(jz),
      &      tgt(jz), tft(jz),
      &      rogt(jz), roft(jz),

```

```

&          hgt(jz),  hft(jz),
&          git(jz),  eit(jz),
&          ugt(jz),  uft(jz),
&          citn(jz), hfit(jz),
&          hgit(jz), akgit(jz),
&          ysit(jz), jz=1,nzt)
c
c  MIDDLE SECTION
c
  do 30 ic=1,nchn
    nsub = nx(ic)
    do 20 ix=1,nsub
      read (nrsti) ( p(jz,ix,ic),
&                  alp(jz,ix,ic),  xa(jz,ix,ic),
&                  tg(jz,ix,ic),  tf(jz,ix,ic),
&                  rog(jz,ix,ic),  rof(jz,ix,ic),
&                  hg(jz,ix,ic),  hf(jz,ix,ic),
&                  gi(jz,ix,ic),  ei(jz,ix,ic),
&                  wgx(jz,ix,ic),  wfx(jz,ix,ic),
&                  ugz(jz,ix,ic),  ufz(jz,ix,ic),
&                  cizn(jz,ix,ic), cixn(jz,ix,ic),
&                  hfi(jz,ix,ic),  hgi(jz,ix,ic),
&                  akgi(jz,ix,ic),  ysi(jz,ix,ic), jz=1,nzp2)
      read (nrsti) ugz(nzp3,ix,ic),  ufz(nzp3,ix,ic),
&                  cizn(nzp3,ix,ic), cixn(nzp3,ix,ic)
20    continue
30  continue
c
c  BOTTOM SECTION
c
  read (nrsti) ( pb(jz),
&              alpb(jz),  xab(jz),
&              tgb(jz),  tfb(jz),
&              rogb(jz),  rofb(jz),
&              hgb(jz),  hfb(jz),
&              gib(jz),  eib(jz),
&              ugb(jz),  ufb(jz),
&              cibn(jz),  hfib(jz),
&              hgib(jz),  akgib(jz),
&              ysib(jz), jz=1,nzb)
c
c  TANK BOTTOM
c
  read (nrsti) ptb, alptb, xatb, tgtpb, tftb,
&              rogtb, roftb, hgtb, hftb
  goto 70
c
  else
c
c  READ ASCII RESTART FILE
c
  read (nrsti,*) tsec0, delt
c
c  INITIALIZE SOLID TEMPERATURES
c
  do 40 icyln=1,ncyln
    nri = nr(icyln)
    read (nrsti,*) ((ts(ir,ia,iz,icyln), iz=1,nz),
&                  ia=1,na),
&                  ir=1,nri)
40  continue
c
c  INITIALIZE SURFACE HEAT FLUXES, HEAT FLUX DERIVATIVES,
c  SINGLE PHASE HEAT TRANSFER COEFFICIENTS, ONB HEAT FLUXES,

```

```

c      AND SURFACE TEMPERATURES
c
c      read (nrsti,*) (((qwf(isurf,ia,iz),   qwg(isurf,ia,iz),
&          dqfdw(isurf,ia,iz), dqgdw(isurf,ia,iz),
&          hspl(isurf,ia,iz),   qonb(isurf,ia,iz),
&          tsurf(isurf,ia,iz),   iz=1,nz), ia=1,na),
&          isurf=1,nsurf)
c
c      BEGIN FLUID INITIALIZATION:
c
c      READ LOCAL PRESSURE, VOID FRACTION, AIR MASS FRACTION,
c      GAS TEMPERATURE, FLUID TEMPERATURE, GAS DENSITY, FLUID
c      DENSITY, GAS ENTHALPY, FLUID ENTHALPY, INTERFACIAL MASS
c      AND ENERGY TRANSFER RATES, AND GAS AND FLUID VELOCITIES
c
c      PLENUM
c
c      read (nrsti,*) ppl, alppl, xapl, tgpl, tfpl,
&          rogpl, rofpl, hgpl, hfpl
c
c      TOP SECTION
c
c      read (nrsti,*) ( pt(jz),
&          alpt(jz),   xat(jz),
&          tgt(jz),   tft(jz),
&          rogt(jz),  roft(jz),
&          hgt(jz),   hft(jz),
&          git(jz),   eit(jz),
&          ugt(jz),   uft(jz),
&          citn(jz),  hfit(jz),
&          hgit(jz),  akgit(jz),
&          ysit(jz),  jz=1,nzt)
c
c      MIDDLE SECTION
c
c      do 60 ic=1,nchn
c          nsub = nx(ic)
c          do 50 ix=1,nsub
c              read (nrsti,*) ( p(jz,ix,ic),
&                  alp(jz,ix,ic),   xa(jz,ix,ic),
&                  tg(jz,ix,ic),   tf(jz,ix,ic),
&                  rog(jz,ix,ic),  rof(jz,ix,ic),
&                  hg(jz,ix,ic),   hf(jz,ix,ic),
&                  gi(jz,ix,ic),   ei(jz,ix,ic),
&                  wgx(jz,ix,ic),  wfx(jz,ix,ic),
&                  ugz(jz,ix,ic),  ufz(jz,ix,ic),
&                  cizn(jz,ix,ic), cixn(jz,ix,ic),
&                  hfi(jz,ix,ic),  hgi(jz,ix,ic),
&                  akgi(jz,ix,ic), ysi(jz,ix,ic),
&                  jz=1,nzp2)
c              read (nrsti,*) ugz(nzp3,ix,ic), ufz(nzp3,ix,ic),
&                  cizn(nzp3,ix,ic), cixn(nzp3,ix,ic)
50          continue
60      continue
c
c      BOTTOM SECTION
c
c      read (nrsti,*) ( pb(jz),
&          alpb(jz),   xab(jz),
&          tgb(jz),   tfb(jz),
&          rogb(jz),  rofb(jz),
&          hgb(jz),   hfb(jz),
&          gib(jz),   eib(jz),
&          ugb(jz),   ufb(jz),

```

```

      cibn(jz), hfib(jz),
      hgib(jz), akfib(jz),
      ysib(jz), jz=1,nzb)
C
C      TANK BOTTOM
C
      read (nrsti,*) ptb, alptb, xatb, tgtb, tftb,
      rogtb, roftb, hgtb, hftb
      end if
C
70      rewind nrsti
C
C      SET ALL NEW AND OLD TIME PROPERTY VALUES EQUAL
C
      call reset (ts,tsurf,tsn,tsrfn,
      p ,alp ,xa ,rog ,rof ,hg ,hf ,tg ,tf ,
      pn ,alpn ,xan ,rogn ,rofn ,hgn ,hfn ,tgn ,tfn ,
      pt ,alpt ,xat ,rogt ,roft ,hgt ,hft ,tgt ,tft ,
      ptn ,alptn ,xatn ,rogtb ,roftb ,hgtb ,hftb ,tgtb ,tftb ,
      pb ,alpb ,xab ,rogb ,rofb ,hgb ,hfb ,tgb ,tfb ,
      pbn ,alpb ,xab ,rogb ,rofb ,hgb ,hfb ,tgb ,tfb ,
      ppl ,xapl ,rogpl ,rofpl ,hgpl ,hfpl ,tgpl ,tfpl ,
      ppln ,xapln ,rogpln ,rofpln ,hgpln ,hfpln ,tgpln ,tfpln ,
      ptb ,xatb ,rogtb ,roftb ,hgtb ,hftb ,tgtb ,tftb ,
      ptn ,xatn ,rogtb ,roftb ,hgtb ,hftb ,tgtb ,tftb ,
      alpb ,alpb ,alptb ,alptb ,nzp2 ,nxmax ,nchn ,nzt ,
      nzb ,nrmax ,na ,nz ,ncyl ,nsurf)
C
      return
      end

```

RING

```

      subroutine ring (ts,tsurf,tsrfn,dr,cond,radc,ar,rhs,diag,cra,
      crc,ca,trhs,cmdag,cmrhc,cma,cmb,cmd,cri,cro,
      d,rhsi,rhso,rf,ncms,da,dz,nr,nrp,nrmax,na,nz,
      nsurf,ncyl,icyl,icent,qwf,qwg,dqfdw,dqgdw)
C
C      *****
C      *
C      * SUBROUTINE RING: THIS SUBROUTINE SOLVES THE HEAT CONDUCTION *
C      * EQUATIONS FOR A RING OF AZIMUTHAL AND RADIAL *
C      * MESH CELLS AT A PARTICULAR AXIAL LOCATION *
C      * IN A SINGLE CYLINDER *
C      *
C      *****
C
      implicit real (a-h,o-z), integer (i-n)
      parameter (zero=0.0, half=0.5, two=2.0, maxr=50, maxa=50)
      logical first, firstc
C
      dimension tsurf(nsurf,na), tsrfn(nsurf,na), ts(nrmax,na),
      qwf(nsurf,na), dqfdw(nsurf,na),
      qwg(nsurf,na), dqgdw(nsurf,na)
C
      dimension rhs(nr,na), trhs(na), d(nr),
      diag(nr,na), rhsi(na),
      ca(nr,na), rhso(na),
      cra(nr,na), cri(na),
      crc(nr,na), cro(na)
C
C      COARSE MESH ARRAYS
C
      dimension cmrhc(na), cmdag(nr,na),
      cma(na), cmb(na),

```

```

      &          cmd(na),      rf(na)
c
c      SOLID GEOMETRY AND PROPERTY ARRAYS
c
c      dimension radc(nr), dr(nr), ar(nrp), cond(nr,na)
c
c      LOCAL ARRAYS
c
c      dimension s1(2,maxr,maxa), s2(2,maxa)
c
c      THE PARAMETER wht CONTROLS THE IMPLICITNESS OF THE SURFACE HEAT
c      FLUX. THIS PARAMETER SHOULD BE SET AS FOLLOWS:
c      wht=0.5 => SURFACE HEAT FLUX IMPLICIT IN TS
c              (MUST USE wht=0.5 IN CURRENT HEAT FLUX SCHEME)
c      wht=0.0 => SURFACE HEAT FLUX EXPLICIT IN TS
c
c      wht = half
c      first = .true.
c
c      isurfi = 2*icyln - icent
c      isurfo = isurfi + 1
c
c      call clear (cra,nr*na)
c      call clear (crc,nr*na)
c
c      TEST FOR TWO-DIMENSIONAL PROBLEM
c
c      if (na.gt.1) then
c
c      THREE-DIMENSIONAL PROBLEM:
c      CALCULATE COUPLING TERMS IN AZIMUTHAL DIRECTION
c
c      fdadz = two*dz/da
c      do 20 ir=1,nr
c          c2 = cond(ir,na)/radc(ir)
c          do 10 ia=1,na
c              c1 = c2
c              c2 = cond(ir,ia)/radc(ir)
c              ca(ir,ia) = -fdadz*dr(ir)*c1*c2/(c1 + c2)
10      continue
20      continue
c
c      CALCULATE COUPLING TERMS IN RADIAL DIRECTION
c      COMPUTE ELEMENTS OF REBALANCE EQUATIONS
c
c      do 40 ia=1,na
c          c1 = wht*(dqfdw(isurfi,ia) + dqgdw(isurfi,ia))
c          c2 = cond(1,ia)/dr(1)
c          farea = ar(1)*c2/(c1 + c2)
c          cri(ia) = -two*c1*farea
c          rhsi(ia) = cri(ia)*tsurf(isurfi,ia) +
&          farea*(qwfi(isurfi,ia) + qwg(isurfi,ia))
c
c          cma(ia) = ca(1,ia)
c          cmd(ia) = diag(1,ia)
c
c      do 30 ir=2,nr
c          im = ir - 1
c
c          cma(ia) = cma(ia) + ca(ir,ia)
c          cmd(ia) = cmd(ia) + diag(ir,ia)
c
c          c1 = c2
c          c2 = cond(ir,ia)/dr(ir)

```

```

        cra(ir,ia) = -two*ar(ir)*c1*c2/(c1 + c2)
        crc(im,ia) = cra(ir,ia)
30      continue
c
        c1 = c2
        c2 = wht*(dqfdw(isurfo,ia) + dqgdw(isurfo,ia))
        farea = ar(nrp)*c1/(c1 + c2)
        cro(ia) = -two*c2*farea
        rhso(ia) = cro(ia)*tsurf(isurfo,ia) +
        &         farea*(qwf(isurfo,ia) + qwg(isurfo,ia))
c
        cmb(ia) = cma(ia)
40      continue
c
c      FORM INVARIANT ELEMENTS OF TRIDIAGONAL SYSTEM OF
c      EQUATIONS FOR RADIAL TEMPERATURES
c
        do 200 ia=1,na
            trhs(ia) = zero
            iap = ia + 1
            if (ia.eq.na) iap = 1
            cmd(ia) = cmd(ia) - cma(ia) - cma(iap)
            &         - cri(ia) - cro(ia)
c
c      ADD BOUNDARY HEAT FLUX TERMS TO RIGHT HAND SIDE
c
            rhs( 1,ia) = rhs( 1,ia) - rhsi(ia)
            rhs(nr,ia) = rhs(nr,ia) - rhso(ia)
c
c      COMPUTE DIAGONAL ELEMENTS
c
            do 100 ir=1,nr
                trhs(ia) = trhs(ia) + rhs(ir,ia)
                cmdag(ir,ia) = diag(ir,ia)
                diag(ir,ia) = diag(ir,ia) - cra(ir,ia) - crc(ir,ia)
                &         - ca(ir,ia) - ca(ir,iap)
100      continue
            diag( 1,ia) = diag( 1,ia) - cri(ia)
            diag(nr,ia) = diag(nr,ia) - cro(ia)
200      continue
c
c      BEGIN ITERATION OVER RING
c
        firstc = .true.
        do 1000 m=1,ncms
c
c      SWEEP OVER AZIMUTHAL ZONES
c
            do 500 ia=1,na
                iam = ia - 1
                if (iam.eq.0) iam = na
                iap = ia + 1
                if (ia.eq.na) iap = 1
c
c      SET UP RIGHT HAND SIDE OF TRIDIAGONAL SYSTEM
c
                do 300 ir=1,nr
                    d(ir) = rhs(ir,ia) - ca(ir,ia)*ts(ir,iam)
                    &         - ca(ir,iap)*ts(ir,iap)
300      continue
c
c      SOLVE TRIDIAGONAL SYSTEM
c
            call tridag (first,1,nr,nr,cra(1,ia),diag(1,ia),crc(1,ia),

```

```

      &          d,ts(1,ia),s1(1,1,ia))
c
500  continue
      first = .false.
c
c      PERFORM COARSE MESH REBALANCE
c
      do 700 ia=1,na
          iam = ia - 1
          if (iam.eq.0) iam = na
          iap = ia + 1
          if (iap.eq.na) iap = 1
          cmrhs(ia) = trhs(ia) + cri(ia)*ts(1,ia)
          &          + cro(ia)*ts(nr,ia)
          do 600 ir=1,nr
              cmrhs(ia) = cmrhs(ia) - ca(ir,ia)*ts(ir,iam)
              &          - ca(ir,iap)*ts(ir,iap)
              &          - (cmdag(ir,ia) - ca(ir,ia)
              &          - ca(ir,iap))*ts(ir,ia)
600  continue
700  continue
c
      call tridag (firstc,1,na,na,cma,cmd,cmb,cmrhs,rf,s2)
      firstc = .false.
c
      do 800 ia=1,na
          do 800 ir=1,nr
              ts(ir,ia) = ts(ir,ia) + rf(ia)
800  continue
c
1000 continue
c
      else
c
c      TWO-DIMENSIONAL PROBLEM (r,z):
c      CALCULATE COUPLING TERMS IN RADIAL DIRECTION
c
          c1 = wht*(dqfdw(isurfi,1) + dqgdw(isurfi,1))
          c2 = cond(1,1)/dr(1)
          farea = ar(1)*c2/(c1 + c2)
          cri(1) = -two*c1*farea
          rhsi(1) = cri(1)*tsurf(isurfi,1) +
          &          farea*(qwfi(isurfi,1) + qwg(isurfi,1))
c
          do 2100 ir=2,nr
              im = ir - 1
              c1 = c2
              c2 = cond(ir,1)/dr(ir)
              cra(ir,1) = -two*ar(ir)*c1*c2/(c1 + c2)
              crc(im,1) = cra(ir,1)
2100 continue
c
          c1 = c2
          c2 = wht*(dqfdw(isurfo,1) + dqgdw(isurfo,1))
          farea = ar(nrp)*c1/(c1 + c2)
          cro(1) = -two*c2*farea
          rhso(1) = cro(1)*tsurf(isurfo,1) +
          &          farea*(qwfi(isurfo,1) + qwg(isurfo,1))
c
c      ADD BOUNDARY HEAT FLUX TERMS TO RIGHT HAND SIDE
c
          rhs(1,1) = rhs(1,1) - rhsi(1)
          rhs(nr,1) = rhs(nr,1) - rhso(1)
c

```

```

c      COMPUTE DIAGONAL ELEMENTS
c
do 2200 ir=1,nr
    diag(ir,1) = diag(ir,1) - cra(ir,1) - crc(ir,1)
2200 continue
    diag(1,1) = diag(1,1) - cri(1)
    diag(nr,1) = diag(nr,1) - cro(1)

c
c      SOLVE TRIDIAGONAL SYSTEM FOR TEMPERATURES
c
call tridag (first,1,nr,nr,cra(1,1),diag,crc(1,1),rhs,ts,s1)

c
end if

c
c      COMPUTE SURFACE TEMPERATURES AND HEAT FLUXES AT NEW TIME
c
do 3000 ia=1,na
    c1 = cond(1,ia)/dr(1)
    c2 = half*(dqfdw(isurfi,ia) + dqgdw(isurfi,ia))
    tsurf(isurfi,ia) = (c1*ts(1,ia) + c2*tsurf(isurfi,ia) -
        half*(qwfi(isurfi,ia) + qwgi(isurfi,ia)))/
        (c1 + c2)
    delti = tsurf(isurfi,ia) - tsrfn(isurfi,ia)
    qwfi(isurfi,ia) = qwfi(isurfi,ia) + dqfdw(isurfi,ia)*delti
    qwgi(isurfi,ia) = qwgi(isurfi,ia) + dqgdw(isurfi,ia)*delti

c
    c1 = cond(nr,ia)/dr(nr)
    c2 = half*(dqfdw(isurfo,ia) + dqgdw(isurfo,ia))
    tsurf(isurfo,ia) = (c1*ts(nr,ia) + c2*tsurf(isurfo,ia) -
        half*(qwfi(isurfo,ia) + qwgi(isurfo,ia)))/
        (c1 + c2)
    delto = tsurf(isurfo,ia) - tsrfn(isurfo,ia)
    qwfi(isurfo,ia) = qwfi(isurfo,ia) + dqfdw(isurfo,ia)*delto
    qwgi(isurfo,ia) = qwgi(isurfo,ia) + dqgdw(isurfo,ia)*delto
3000 continue
c
return
end

```

ROFSAT

```

subroutine rofsat(t,l,rofs,drfsdt)

c
c      *****
c      *
c      * INPUT:
c      *      t = TEMPERATURE IN K
c      *      l = IDENTIFIER (l=1 FOR H2O, l=2 FOR D2O)
c      *
c      * OUTPUT:
c      *      rofs = LIQUID SATURATION DENSITY IN kg/m^3
c      *      drfsdt = DERIVATIVE OF rofs W.R.T. t
c      *
c      * RANGE:
c      *      275K < t < 450K
c      *
c      * NOTE: FOR PURE AND NEARLY PURE (alpha > 0.999) GAS CASES THE
c      *      LIQUID TEMPERATURE IS EQUAL TO OR APPROACHES THE GAS
c      *      TEMPERATURE, RESPECTIVELY. THE GAS TEMPERATURE MAY BE
c      *      AS LARGE AS 700K. THE LAST LINE IS ADDED TO AVOID A
c      *      NEGATIVE LIQUID DENSITY FOR HIGH TEMPERATURES
c      *
c      *****

parameter (two=2.0, hundrd=100.0)

```



```

      dimension c1(2), c2(2), c3(2)
      c
      c      H2O PROPERTIES
      c
      data c1(1),/850.87/, c2(1)/1.2788/, c3(1)/-2.6526e-3/
      c
      c      D2O PROPERTIES
      c
      data c1(2)/919.86/, c2(2)/1.5412/, c3(2)/-3.0963e-3/
      c
      rofs = c1(1) + (c2(1) + c3(1)*t)*t
      drfsdt = c2(1) + two*c3(1)*t
      c
      return
      end

```

RSTEAM

```

      subroutine rsteam(p,t,l,ros,drosdp,drosdt)
      c
      c      *****
      c      *
      c      *   INPUT:
      c      *      p = PARTIAL PRESSURE IN Pa
      c      *      t = TEMPERATURE IN K
      c      *      l = IDENTIFIER (l=1 FOR H2O, l=2 FOR D2O)
      c      *
      c      *   OUTPUT:
      c      *      ros = DENSITY OF STEAM IN kg/m^3
      c      *      drosdp = DERIVATIVE OF ros W.R.T. p AT CONSTANT t
      c      *      drosdt = DERIVATIVE OF ros W.R.T. t AT CONSTANT p
      c      *
      c      *   RANGE:
      c      *      275K < t < 700K
      c      *      'low' pressure
      c      *
      c      *****
      c
      parameter (one=1.0)
      dimension rs(2)
      c
      c      H2O PROPERTIES
      c
      data rs(1)/461.0/
      c
      c      D2O PROPERTIES
      c
      data rs(2)/415.0/
      c
      ros = p/(rs(l)*t)
      drosdp = one/(rs(l)*t)
      drosdt = -ros/t
      c
      return
      end

```

SCMSLB

```

      subroutine scmslb (in)
      c
      write(in,10)
10    format (/,
      & 9x,
      & '#####  #      #### #      ##### #####  ##  #  #',
      & /,9x,

```

[illegible]

SETS LD

```

      subroutine setsld (radc,ar,dr,vols,zfacm,da,diam,dz,rdz,
      & hactiv,mat,ioid,nfrst,nlast,nr,nz,na,nrmax,
      & nrmp,ncyln,izht,izhb,icent,iradbc,douts,
      & emisi,emiso,cradi)
C
C *****
C *
C * SUBROUTINE setsld
C *
C * SUBROUTINE TO INITIALIZE FLOWTRAN SOLID GEOMETRIC ARRAYS.
C *
C * THE FOLLOWING VARIABLES ARE COMPUTED:
C *
C *      radc(ir,icyln) CELL CENTER RADII (m)
C *      ar(ir,iz,icyln) AREAS OF CELL RADIAL FACES (m**2)
C *      dr(ir,icyln) RADIAL MESH SPACING (m)
C *      vols(ir,iz,icyln) VOLUME OF SOLID MESH CELLS (m**3)
C *      zfacm(ir,ia,icyln) AREA OF Z-FACE OF MESH CELL (m**2)
C *      nfrst(icyln) FIRST NODE IN CORE REGION BY CYLINDER
C *      nlast(icyln) LAST NODE IN CORE REGION BY CYLINDER
C *      rdz(iz) NORMALIZED AXIAL MESH SPACINGS
C *      hactiv HEIGHT OF ACTIVE CORE (m)
C *

```

```

c *****
c implicit real (a-h,o-z), integer (i-n)
c parameter (zero=0.0, quart=0.25, half=0.5, one=1.0, two=2.0)
c parameter (stfblz=5.669e-8)
c
c dimension ar(nrmxp,nz,ncyl), radc(nrmax,ncyl), dz(nz),
c mat(nrmax,nz,ncyl), dr(nrmax,ncyl), rdz(nz),
c vols(nrmax,nz,ncyl), diam(nrmxp,ncyl)
c
c dimension zfacm(nrmax,ncyl), nfrst(ncyl), ioxid(ncyl),
c nr(ncyl), nlast(ncyl)
c
c dimension node(10)
c
c COMPUTE SOLID CELL GEOMETRIC PARAMETERS
c
c pi = acos(-one)
c da = two*pi/na
c
c do 40 icyl=1,ncyl
c   nri = nr(icyl)
c   nrp = nri + 1
c
c   do 20 ir=1,nri
c     dr(ir,icyl) = half*(diam(ir+1,icyl) - diam(ir,icyl))
c     radc(ir,icyl) = quart*(diam(ir+1,icyl) + diam(ir,icyl))
c     zfacm(ir,icyl) = dr(ir,icyl)*radc(ir,icyl)*da
c     do 10 iz=1,nz
c       ar(ir,iz,icyl) = half*diam(ir,icyl)*da*dz(iz)
c       vols(ir,iz,icyl) = zfacm(ir,icyl)*dz(iz)
c     continue
c   continue
c
c COMPUTE RADIAL AREAS AT OUTER FACES
c
c   do 30 iz=1,nz
c     ar(nrp,iz,icyl) = half*diam(nrp,icyl)*da*dz(iz)
c   continue
c 30 continue
c
c CHECK ASSEMBLY MATERIAL NODALIZATION, COMPUTE
c AND STORE FIRST AND LAST NODES IN CORE REGION
c
c do 150 icyl=1,ncyl
c   nri = nr(icyl)
c
c CHECK MATERIAL ON OUTSIDE OF CYLINDER
c
c   mtest = mat(nri,1,icyl)
c   if (mtest.eq.1 .or. mtest.eq.4 .or. mtest.eq.5) then
c     write (*,200) icyl
c     stop
c   end if
c
c CHECK MATERIAL ON INSIDE OF CYLINDER
c
c   mtest = mat(1,1,icyl)
c   if ((icent*icyl).ne.1 .and.
c     (mtest.eq.1 .or. mtest.eq.4 .or. mtest.eq.5)) then
c     write (*,210) icyl
c     stop
c   end if
c
c nsect = 1

```

```
        inode = 2
c
c      FIND NUMBER OF DIFFERENT MATERIAL SECTIONS IN CYLINDER
c      AND SAVE THE FIRST AND LAST NODES OF EACH SECTION
c
        node(1) = 1
        do 110 ir=2,nri
            if (mat(ir,1,icyln).ne.mtest) then
                node(inode) = ir - 1
                node(inode+1) = ir
                nsect = nsect + 1
                inode = inode + 2
                mtest = mat(ir,1,icyln)
            end if
110      continue
        node(inode) = nri
c
c      FIND BOUNDS FOR CYLINDER CORE REGION
c
        if (nsect.eq.1 .or. nsect.eq.3 .or. nsect.eq.5) then
            nfirst(icyln) = node(nsect)
            nlast(icyln) = node(nsect+1)
c
        else if (nsect.eq.2 .or. nsect.eq.4) then
            if (ioxid(icyln).eq.1) then
                nfirst(icyln) = node(nsect-1)
                nlast(icyln) = node(nsect)
            else if (ioxid(icyln).eq.2) then
                nfirst(icyln) = node(nsect+1)
                nlast(icyln) = node(nsect+2)
            else
                write (*,220) icyln
                stop
            end if
c
        else
            write (*,230) icyln
            stop
        end if
c
150  continue
c
c      COMPUTE HEIGHT OF ACTIVE CORE AND NORMALIZED
c      AXIAL MESH SPACINGS OVER HEATED CORE
c
        hactiv = zero
        do 160 iz=izht,izhb
            hactiv = hactiv + dz(iz)
160  continue
c
        call clear (rdz,nz)
        do 170 iz=izht,izhb
            rdz(iz) = dz(iz)/hactiv
170  continue
c
c      IF A RADIATION BOUNDARY CONDITION IS SPECIFIED, CALCULATE
c      THE CONSTANT TERM IN THE RADIATION HEAT FLUX EQUATION
c
        if (iradbc.eq.1) then
            nrout = nr(ncyln) + 1
            ratio = diam(nrout,ncyln)/douts
            if (ratio.gt.one) then
                write (*,240)
                stop
            end if
        end if
```

```

        end if
        cradi = stfblz/(one/emisi + ratio*(one/emiso - one))
    end if
c
c    ERROR MESSAGES
c
200  format (' <<< fatal error >>>',/,
        &      ' outer cladding material on cylinder ',i2,/, ' is not',
        &      ' aluminum or an experimental rig surface metal')
c
210  format (' <<< fatal error >>>',/,
        &      ' inner cladding material on cylinder ',i2,/, ' is not',
        &      ' aluminum or an experimental rig surface metal')
c
220  format (' <<< fatal error >>>',/,
        &      ' oxide specification is inconsistent with the',
        &      ' number of materials for cylinder ',i2)
c
230  format (' <<< fatal error >>>',/,
        &      ' more than 5 material regions were detected for',
        &      ' cylinder ',i2)
c
240  format (' <<< fatal error >>>',/,
        &      ' the radiating surface diameter is less than that',
        &      ' of the outer cylinder')
c
    return
end

```

SOLID

```

subroutine solid (ts,tsn,tsurf,tsrfn,pows,qwf,qwg,dqfdw,dqgdw,
&               wt,radc,ar,vols,zfacm,mat,rdelt,da,dr,dz,
&               nr,na,nsurf,nz,ncyl,nrmax,nrmxp,wss,icent,
&               iaxial,ncms)
c
c *****
c *
c * SUBROUTINE SOLID: THIS SUBROUTINE IS THE MAIN DRIVER FOR THE *
c * HEAT CONDUCTION ROUTINES *
c *
c *
c *****
c
c ARGUMENTS
c
c NOTE: ALL VARIABLES LISTED BELOW ARE AT CURRENT TIME LEVEL UNLESS
c OTHERWISE INDICATED
c
c O ts(*)          SOLID TEMPERATURES FOR ALL CYLINDERS AT ALL
c                  AXIAL, AZIMUTHAL, AND RADIAL LOCATIONS
c I tsn(*)         SOLID TEMPERATURES AT OLD TIME LEVEL
c O tsurf(isurf,ia,iz) SURFACE TEMPERATURES
c I tsrfn(isurf,ia,iz) SURFACE TEMPERATURES AT PREVIOUS ITERATION
c I pows(*)        THERMAL ENERGY DEPOSITED IN THE SOLID DURING
c                  CURRENT TIME STEP
c I qwf(isurf,ia,iz) SURFACE HEAT FLUX TO LIQUID
c I qwg(isurf,ia,iz) SURFACE HEAT FLUX TO GAS
c I dqfdw(isurf,ia,iz) DERIVATIVE OF LIQUID SURFACE HEAT FLUX WITH RESPECT
c                  TO SURFACE TEMPERATURE
c I dqgdw(isurf,ia,iz) DERIVATIVE OF GAS SURFACE HEAT FLUX WITH RESPECT
c                  TO SURFACE TEMPERATURE
c I radc(**)       CELL CENTERED RADII FOR EACH CYLINDER
c I ar(**)         AREAS OF THE RADIAL FACES OF THE MESH CELLS
c I vols(**)       VOLUMES OF THE MESH CELLS

```

```

c I  zfacm(**)      AREAS OF Z FACES OF SOLID MESH CELLS
c I  mat(**)        MATERIAL DESIGNATORS FOR EACH MESH CELL
c                      (ASSUMED INDEPENDENT OF AZIMUTHAL DIMENSION)
c I  rdelt          RECIPROCAL TIME STEP SIZE IN SECONDS
c I  da            AZIMUTHAL MESH SPACING IN RADIANS
c I  dr(**)        RADIAL MESH SPACING
c I  dz(iz)        AXIAL MESH SPACINGS
c I  nr(icynl)     NUMBER OF RADIAL CELLS IN EACH CYLINDER
c I  na            TOTAL NUMBER OF AZIMUTHAL CELLS
c I  nsurf         TOTAL NUMBER OF SURFACES
c I  nz            TOTAL NUMBER OF AZIAL CELLS
c I  ncynl         TOTAL NUMBER OF CYLINDERS
c I  nrmax         MAXIMUM NUMBER OF RADIAL CELLS
c I  wss           WEIGHTING FOR STEADY STATE CALCULATION:
c                      0.0 EXPLICIT IN AXIAL AND BOUNDARY FLUXES
c                      1.0 IMPLICIT IN AXIAL AND BOUNDARY FLUXES
c I  icent         INDICATOR FOR WHAT'S AT CENTER
c                      0 COOLANT / 1 SOLID
c
c NOTE: SPECIAL INDEXING IS USED FOR SOME OF THE ABOVE ARRAYS.
c       THIS INDEXING IS DESCRIBED BELOW.
c
c *       FOR EACH CYLINDER icynl, THE ARRAY IS DIMENSIONED
c         AS (nrmax,na,nz).
c
c **      FOR EACH CYLINDER icynl, THESE ARRAYS ARE DIMENSIONED
c         AS (nrmax) OR AS (nrmax+1) FOR CELL EDGE QUANTITIES.
c
c *****
c
c LOCAL ARRAYS
c
c NOTE: THE FOLLOWING ARRAYS ARE ALL CONTAINED WITHIN THE ARRAY AS.
c
c hcap(ir,ia,iz)    HEAT CAPACITIES FOR ONE CYLINDER
c cond(ir,ia,iz)    THERMAL CONDUCTIVITIES FOR ONE CYLINDER
c rhs(ir,ia)        RIGHT HAND SIDE OF DIFFERENCE EQUATIONS (D.E.)
c                      FOR ONE RING
c diag(ir,ia)       DIAGONAL TERMS OF D.E. FOR ONE RING
c cra              RADIAL COUPLING TERMS IN D.E.
c crc              RADIAL COUPLING TERMS IN D.E.
c ca               AZIMUTHAL COUPLING TERMS IN D.E.
c cb               AXIAL (BOTTOM LAYER) COUPLING TERMS IN D.E.
c trhs(ia)         TOTAL RIGHT HAND SIDE FOR COARSE MESH REBALANCE
c                      (cmr) EQUATIONS
c cma(ia)          OFF-DIAGONAL TERMS IN CMR EQUATIONS
c cmd(ia)          DIAGONAL TERMS IN CMR EQUATIONS
c cmdag(ir,ia)     DIAGONAL CONTRIBUTION TO RIGHT HAND SIDE OF
c                      CMR EQUATIONS
c cmrhs(ia)        RIGHT HAND SIDE OF cmr EQUATIONS
c
c *****
c
c implicit real (a-h,o-z), integer (i-n)
c parameter (lntemp=100000)
c dimension as(lntemp)
c
c SOLID GEOMETRIC PARAMETERS
c
c dimension vols(nrmax,nz,ncynl),  radc(nrmax,ncynl),
c      ar(nrmxp,nz,ncynl),  zfacm(nrmax,ncynl),
c      nr(ncynl),  dr(nrmax,ncynl),
c      dz(nz)

```

```

c    SOLID PROPERTIES
c
c    dimension  ts(nrmax,na,nz,ncyl),
c    &          tsn(nrmax,na,nz,ncyl),
c    &          pows(nrmax,na,nz,ncyl),
c    &          mat(nrmax,nz,ncyl),
c    &          wt(ncyl)
c
c    SURFACE PROPERTIES
c
c    dimension  qwf(nsurf,na,nz), dqfdw(nsurf,na,nz),
c    &          qwg(nsurf,na,nz), dqgdw(nsurf,na,nz),
c    &          tsurf(nsurf,na,nz), tsrfrn(nsurf,na,nz)
c
c    logical first
c    save first,lhcap,lcond,lrhs,ldiag,lcra,lcrc,lca,lcb,ltrhs,
c    &      ld,lcrl,lcro,lrhsi,lrhs,lrfl,lcma,lcmb,lcmd,lcmdag,
c    &      lcmrhs
c    data first/.true./
c
c    SET UP POINTERS FOR TEMPORARY ARRAYS IF FIRST ENTRY
c
c    if (first) then
c      first = .false.
c      len = nrmax*na
c      lhcap = 1
c      lcond = lhcap + len*nz
c      lrhs = lcond + len*nz
c      ldiag = lrhs + len
c      lcra = ldiag + len
c      lcrc = lcra + len
c      lca = lcrc + len
c      lcb = lca + len
c      ltrhs = lcb + len
c      ld = ltrhs + na
c      lcrl = ld + nrmax
c      lcro = lcrl + na
c      lrhsi = lcro + na
c      lrhs = lrhsi + na
c      lrfl = lrhs + na
c      lcma = lrfl + na
c      lcmb = lcma + na
c      lcmd = lcmb + na
c      lcmdag = lcmd + na
c      lcmrhs = lcmdag + len
c      lend = lcmrhs + na
c
c      if (lend.gt.lntemp) then
c        write (*,10) lend, lntemp
c        format(/' <<< fatal error >>> insufficient temporary',
c        &      ' storage space in solid/' length of as() = ',
c        &      i6,' maximum as() = ',i6/)
c        stop
c      end if
c    end if
c
c    LOOP OVER ALL CYLINDERS
c
c    do 100 icyln=1,ncyl
c      nri = nr(icyln)
c      nrp = nri + 1
c
c    OBTAIN SOLID PROPERTIES
c

```

```

      call eossld (as(lhcap),as(lcond),mat(1,1,icyln),
      &            ts(1,1,1,icyln),wt(icyln),nri,na,nz,
      &            nrmax)
c
c  COMPUTE SOLID TEMPERATURES IN CYLINDER
c
      call cylndr (ts(1,1,1,icyln),tsn(1,1,1,icyln),
      &            pows(1,1,1,icyln),tsurf,tsrfrn,
      &            radc(1,icyln),ar(1,1,icyln),dr(1,icyln),
      &            zfacm(1,icyln),vols(1,1,icyln),as(lhcap),
      &            as(lcond),as(lrhs),as(ldiag),as(lcra),
      &            as(lcrc),as(lca),as(lcb),as(ltrhs),as(ld),
      &            as(lcri),as(lcro),as(lrhsi),as(lrhso),as(lrf),
      &            as(lcmdag),as(lcmrhs),as(lcma),as(lcmb),as(lcmd),
      &            rdelt,da,dz,nri,nrip,nrmax,nrmxp,na,nsurf,nz,
      &            ncyln,icyln,wss,icent,qwf,qwg,dqfdw,dqgdw,iaxial,
      &            ncms)
c
100  continue
c
      return
      end

```

SPLINE

```

      subroutine spline(itype,n,t,y,h,b,u,v,z)
c=====
c  Purpose:  This routine computes the slopes of piecewise linear
c            splines or the second derivatives of natural cubic
c            splines.
c=====
c  Subroutine history
c  - algorithm given in "Numerical Mathematics and Computing" by
c    Cheney and Kincaid, 2nd Edition, 1985.
c=====
c  Arguments
c
c      NAME      I/O  TYPE      DIM      DESCRIPTION
c      -----
c      itype      I    I*4              Identifier of type of spline
c                                     = 0 (Natural cubic spline)
c                                     = 1 (First-degree spline)
c      n          I    I*4              Number of points
c      t          I    R*4              n      Abscissa values or knots
c      y          I    R*4              n      Ordinate values
c      h,b,u,v    I    R*4              n      Intermediate working arrays
c      z          O    R*4              n      Slopes of first-degree splines
c                                     or second derivatives of
c                                     natural cubic splines at the
c                                     knots
c=====
      implicit real (a-h,o-z), integer (i-n)
      parameter (zero=0.,two=2.,six=6.)
      dimension t(n),y(n),h(n),b(n),u(n),v(n),z(n)
c
      if (itype .ne. 0) then
        do 10 i=1,n-1
          z(i)=(y(i+1)-y(i))/(t(i+1)-t(i))
10      continue
        return
      end if
c
      do 20 i=1,n-1
        h(i)=t(i+1)-t(i)
20      continue

```



```

      b(i)=(y(i+1)-y(i))/h(i)
20  continue
      u(2)=two*(h(1)+h(2))
      v(2)=six*(b(2)-b(1))
      do 30 i=3,n-1
          u(i)=two*(h(i)+h(i-1))-h(i-1)**2/u(i-1)
          v(i)=six*(b(i)-b(i-1))-h(i-1)*v(i-1)/u(i-1)
30  continue
      z(n)=zero
      do 40 i=n-1,2,-1
          z(i)=(v(i)-h(i)*z(i+1))/u(i)
40  continue
      z(1)=zero
      return
      end

```

SRLHTC

```

      subroutine srlhtc (hfc,qfc,dqdtw,twall,tliq,qliq,ggas,rhof,
&                      rhog,alpha,visf,dvisdt,visg,visw,condf,
&                      cpf,dhy,arib,ieff,ribln,ribtk,mwall)
C
C *****
C *
C * SUBROUTINE srlhtc
C *
C * SUBROUTINE TO CALCULATE FORCED CONVECTION SINGLE-PHASE HEAT
C * FLUXES USING A MODIFIED SIEDER-TATE CORRELATION BASED ON
C * CORRELATION OF DATA FROM SRL HEAT TRANSFER LABORATORY
C *
C * OUTPUT ARGUMENTS:
C *      hfc - HEAT TRANSFER COEFFICIENT, W/M**2-K
C *      qfc - SURFACE HEAT FLUX, W/M**2
C *      dqdtw - DERIVATIVE OF HEAT FLUX WITH RESPECT TO WALL
C *              TEMPERATURE
C *
C * INPUT ARGUMENTS:
C *      twall - WALL TEMPERATURE, K
C *      tliq - LIQUID TEMPERATURE, K
C *      rhof - FLUID DENSITY, kg/m**3
C *      vel - FLUID VELOCITY, m/s
C *      dhy - CELL HYDRAULIC DIAMETER, m
C *      visf - FLUID VISCOSITY, kg/m-s
C *      condf - FLUID THERMAL CONDUCTIVITY, W/m-C
C *      cpf - FLUID SPECIFIC HEAT, J/kg-C
C *      visw - FLUID VISCOSITY AT WALL TEMPERATURE, kg/m-s
C *      dhdtw - NORMALIZED DERIVATIVE OF HEAT TRANSFER COEFF.
C *              W.R.T. WALL TEMPERATURE (1/C)
C *
C *****
C      implicit real (a-h,o-z), integer (i-n)
C      parameter (zero=0.0, one=1.0, oneh=100.0)
C
C      FORCED CONVECTION PART OF CHEN CORRELATION PARAMETERS
C
C      parameter (xm1=0.900, xm2=0.100)
C      parameter (cf1=2.351, cf2=0.213, cf3=0.736)
C
C      include 'knobs.inc'
C
C      TWO-PHASE HEAT TRANSFER PARAMETERS BASED ON
C      SRL CORRELATION OF RIG-B DATA
C
C      data coefh/2.17e-2/, creh/0.80/, cprh/0.4/
C      data coefl/6.77e-5/, crel/1.50/, cprl/0.5/

```

```
      data rnul/4.0/      , delal/0.01/
c
c  CALCULATE FLUID CELL PROPERTIES
c  NOTE: PHASIC LIQUID VELOCITY CORRELATION
c
      re = gliq*dhy/visf
      pr = cpf*visf/condf
c
c  CALCULATE INVERSE MARTINELLI FACTOR AND TWO-PHASE
c  REYNOLDS NUMBER FACTOR (NORMALLY OFF)
c
      f = one
cc      xtti = zero
cc      if (gliq .gt. zero) then
cc          xtti = ((ggas/gliq)**xm1)*sqrt(rhof/rhog)*((visg/visf)**xm2)
cc      end if
cc      xtti = min(xtti,oneh)
cc      if (xtti.gt.xm2) f = cf1*((xtti + cf2)**cf3)
c
c  CALCULATE LIQUID PHASE HEAT TRANSFER COEFFICIENT FOR
c  NON-BOILING SITUATION, CHECK FOR ANNULAR FLOW REGIME
c
c  CHURN-TURBULENT CORRELATION
c
      coef = xcofh*coefh
      cre = xreh*creh
      cpr = cprh
      ret = re/(one - alpha)
      rnut = coef*f*(ret**cre)*(pr**cpr)
c
c  ANNULAR CORRELATION
c
      coef = xcofl*coefl
      cre = xrel*crel
      cpr = cprl
      rnua = coef*f*(re**cre)*(pr**cpr)
c
c  COMBINE CHURN-TURBULENT AND ANNULAR CORRELATIONS
c
      if (delal.le.zero) then
          rnu = min(rnua,rnut)
      else
          almin = max(zero,ala2-delal)
          almax = min( one,ala2+delal)
          wt = (alpha - almin)/(almax - almin)
          wt = max(wt,zero)
          wt = min(wt,one)
          rnu = wt*rnua + (one - wt)*rnut
      end if
c
c  CHECK FOR LAMINAR FLOW
c
      rnu = max(rnu,rnul)
      hfc = condh*rnu/dhy
      dhdtw = zero
c
c  CALCULATE RIB EFFECTIVENESS CORRECTION TO
c  HEAT TRANSFER COEFFICIENT
c
      if (ieff.eq.0 .or. ribln.eq.zero .or. ribtk.eq.zero) then
          psi = zero
      else
          fk = condh(mwall,twall,zero)
          xl = ribln*sqrt(hfc/(fk*ribtk))
```

```

      psi = ribln*tanh(x1)/x1
    end if
    hfc = hfc*(one + arib*(psi - ribtk))
  c
  c  CALCULATE HEAT FLUX AND DERIVATIVE
  c
    delt = twall - tliq
    qfc = hfc*delt
    dqdtw = hfc + qfc*dhdtw
  c
    return
  end

```

STATE

```

subroutine state(p,tg,tf,xa,factor,l,initz,nz,nzp2,nxmax,nchn,ix,
&               ic,rog,drogdp,drogdt,drgdxa,hg,dhgd,hgdt,
&               dhgdxa,rof,drofdp,drofdt,hf,dhfdp,dhfdt)
  c
  c  *****
  c  *
  c  * INPUT:
  c  *
  c  *   p = PRESSURE IN Pa
  c  *   tg = GAS TEMPERATURE IN K
  c  *   tf = LIQUID TEMPERATURE IN K
  c  *   xa = MASS FRACTION OF AIR
  c  *   factor = MULTIPLIER TO ARTIFICIALLY INCREASE LIQUID
  c  *             COMPRESSIBILITY
  c  *   l = IDENTIFIER (l=1 FOR H2O, l=2 FOR D2O)
  c  *
  c  * INTERMEDIATE:
  c  *
  c  *   xs = MASS FRACTION OF STEAM
  c  *   pa = PARTIAL PRESSURE OF AIR
  c  *   ps = PARTIAL PRESSURE OF STEAM
  c  *
  c  * OUTPUT:
  c  *
  c  *   rog = DENSITY OF GAS IN kg/m^3
  c  *   drogdp = DERIVATIVE OF rog W.R.T. p AT CONSTANT tg, xa
  c  *   drogdt = DERIVATIVE OF rog W.R.T. tg AT CONSTANT p, xa
  c  *   drgdxa = DERIVATIVE OF rog W.R.T. xa AT CONSTANT p, tg
  c  *   hg = ENTHALPY OF GAS IN J/kg
  c  *   dhgdp = DERIVATIVE OF hg W.R.T. p AT CONSTANT tg, xa
  c  *   dhgdt = DERIVATIVE OF hg W.R.T. tg AT CONSTANT p, xa
  c  *   dhgdxa = DERIVATIVE OF hg W.R.T. xa AT CONSTANT p, tg
  c  *
  c  *   rof = DENSITY OF LIQUID IN kg/m^3
  c  *   drofdp = DERIVATIVE OF rof W.R.T. p AT CONSTANT tf
  c  *   drofdt = DERIVATIVE OF rof W.R.T. tf AT CONSTANT p
  c  *   hf = ENTHALPY OF LIQUID IN J/kg
  c  *   dhfdp = DERIVATIVE OF hf W.R.T. p AT CONSTANT tf
  c  *   dhfdt = DERIVATIVE OF hf W.R.T. tf AT CONSTANT p
  c  *
  c  * RANGES:
  c  *
  c  *   Up to 1 MPa
  c  *   275K to 450K for liquid properties
  c  *   275K to 700K for gas properties
  c  *
  c  * *****
  c
  parameter (zero=0.0, one=1.0, two=2.0, three=3.0, four=4.0,
&           hundrd=100.0)
  c
  dimension p(nzp2,nxmax,nchn), rog(nzp2,nxmax,nchn),
&          tg(nzp2,nxmax,nchn), hg(nzp2,nxmax,nchn),
&          tf(nzp2,nxmax,nchn), rof(nzp2,nxmax,nchn),

```

```

      xa(nzp2,nxmax,nchn), hf(nzp2,nxmax,nchn)
c
      dimension drogdp(nz), drogdt(nz), drgdx(nz),
      dhgdp(nz), dhgdt(nz), dhgdx(nz),
      drofdp(nz), drofdt(nz),
      dhfdp(nz), dhfdt(nz)
c
      dimension ws(2), rs(2), drhodp(2), c01(2), c02(2), c03(2), c04(2),
      c05(2), c06(2), c07(2), c08(2), c09(2), c10(2), c14(2),
      c15(2), c16(2), c17(2), c18(2), c19(2), c20(2), c21(2),
      c22(2), c23(2), c24(2)
c
c      AIR PROPERTIES
c
      data wa/28.97/, ra/287.0/, tref/375.0/, haref/375.7e+3/
      data c11/1005.9/, c12/-8.6140e-2/, c13/2.6295e-4/
c
c      H2O PROPERTIES
c
      data ptp/611.3/
      data ws(1)/18.016/, rs(1)/461.0/, drhodp(1)/4.58e-7/
      data c01(1)/-38.874/, c02(1)/0.29129/,
      c03(1)/-5.7014e-4/, c04(1)/4.0606e-7/
      data c05(1)/850.87/, c06(1)/1.2788/, c07(1)/-2.6526e-3/
      data c08(1)/-1.1094e+6/, c09(1)/3960.2/, c10(1)/0.36868/
      data c14(1)/+146.97/, c15(1)/+30.482 /,
      c16(1)/-2.6382/, c17(1)/+0.14715/
      data c18(1)/2.4057e+6/, c19(1)/3949.5/, c20(1)/1684.5/
      data c21(1)/1901.4/, c22(1)/-0.62129/,
      c23(1)/1.9538e-3/, c24(1)/-1.0083e-6/
c
c      D2O PROPERTIES
c
      data ws(2)/20.034/, rs(2)/415.0/, drhodp(2)/5.29e-7/
      data c01(2)/-39.686/, c02(2)/0.29393/,
      c03(2)/-5.7036e-4/, c04(2)/4.0230e-7/
      data c05(2)/919.86/, c06(2)/1.5412/, c07(2)/-3.0963e-3/
      data c08(2)/-1.1856e+6/, c09(2)/4340.2/, c10(2)/-0.20733/
      data c14(2)/+137.95/, c15(2)/+33.995 /,
      c16(2)/-2.9758/, c17(2)/+0.15679/
      data c18(2)/2.2314e+6/, c19(2)/4054.7/, c20(2)/1526.0/
      data c21(2)/1611.4/, c22(2)/3.6681e-3/,
      c23(2)/1.3023e-3/, c24(2)/-6.6266e-7/
c
      do 200 jz = initz, nz
c
c      COMPUTE MASS FRACTION, PARTIAL PRESSURES
c
      xs = one - xa(jz,ix,ic)
      pa = p(jz,ix,ic)*(xa(jz,ix,ic)*ws(1))/(xa(jz,ix,ic)*ws(1) + xs*wa)
      ps = p(jz,ix,ic) - pa
c
c      COMPUTE LIQUID PROPERTIES
c
      sp = exp(c01(1) + (c02(1) + (c03(1) + c04(1)*tf(jz,ix,ic))
      *tf(jz,ix,ic))*tf(jz,ix,ic))
      dspdt = sp*(c02(1) + (two*c03(1) + (three*c04(1))
      *tf(jz,ix,ic))*tf(jz,ix,ic))
c
      rofs = c05(1) + (c06(1) + c07(1)*tf(jz,ix,ic))*tf(jz,ix,ic)
      drfsdt = c06(1) + two*c07(1)*tf(jz,ix,ic)
c
      drofdp(jz) = factor*drhodp(1)
      rof(jz,ix,ic) = rofs + drofdp(jz)*(p(jz,ix,ic) - sp)

```

```

      drofddt(jz) = drfsdt + drofdp(jz)*(-dspdt)
c
      hfs = c08(1) + (c09(1) + c10(1)*tf(jz,ix,ic))*tf(jz,ix,ic)
      dhfsdt = c09(1) + two*c10(1)*tf(jz,ix,ic)
c
      hf(jz,ix,ic) = hfs
      dhfdp(jz) = zero
      dhfddt(jz) = dhfsdt
c
c     COMPUTE AIR PROPERTIES
c
      roa = pa/(ra*tg(jz,ix,ic))
      droadp = one/(ra*tg(jz,ix,ic))
      droadt = -roa/tg(jz,ix,ic)
c
      ha = haref + (c11 + ((c12/two) + (c13/three)*tg(jz,ix,ic))*
&                tg(jz,ix,ic))*tg(jz,ix,ic)
&                - (c11 + ((c12/two) + (c13/three)*tref)*tref)*tref
      dhadp = zero
      dhadt = c11 + (c12 + c13*tg(jz,ix,ic))*tg(jz,ix,ic)
c
c     COMPUTE STEAM PROPERTIES
c
      ros = ps/(rs(1)*tg(jz,ix,ic))
      drosdp = one/(rs(1)*tg(jz,ix,ic))
      drosdt = -ros/tg(jz,ix,ic)
c
      pmin = max(p(jz,ix,ic),ptp)
      z = log(pmin)
      st = c14(1) + (c15(1) + (c16(1) + c17(1)*z)*z)*z
      dstdp = (c15(1) + (two*c16(1) + three*c17(1)*z)*z)/pmin
      if (p(jz,ix,ic) .lt. ptp) st = st - dstdp*(ptp - p(jz,ix,ic))
c
      z = log(p(jz,ix,ic))
      hss = c18(1) + (c19(1) + c20(1)*z)*z
      dhssdp = (c19(1) + two*c20(1)*z)/p(jz,ix,ic)
c
      hs = hss + (c21(1) + ((c22(1)/two) + ((c23(1)/three)
&                + (c24(1)/four)*tg(jz,ix,ic))*tg(jz,ix,ic))
&                *tg(jz,ix,ic))*tg(jz,ix,ic)
&                - (c21(1) + ((c22(1)/two) + ((c23(1)/three)
&                + (c24(1)/four)*st)*st)*st
      dhssdp = dhssdp - (c21(1) + (c22(1) + (c23(1) + c24(1)*st)
&                *st)*st)*dstdp
      dhstdt = c21(1) + (c22(1) + (c23(1) + c24(1)*tg(jz,ix,ic))
&                *tg(jz,ix,ic))*tg(jz,ix,ic)
c
c     COMPUTE GAS PROPERTIES
c
      rog(jz,ix,ic) = roa + ros
      drogdp(jz) = (pa*droadp + ps*drosdp)/p(jz,ix,ic)
      drogdt(jz) = droadt + drosdt
      drgdx(jz) = (wa*pa + ws(1)*ps)**2/(wa*ws(1)*p(jz,ix,ic))
&                *(droadp - drosdp)
c
      hg(jz,ix,ic) = xa(jz,ix,ic)*ha + xs*hs
      dhgdp(jz) = xa(jz,ix,ic)*dhadp + xs*dhssdp
      dhgdt(jz) = xa(jz,ix,ic)*dhadt + xs*dhstdt
      dhgdx(jz) = ha - hs
c
200 continue
c
      return
      end

```

STORE

```

subroutine store (tsn,tsrfn,qwf,qwg,dqfdw,dqgdw,hspl,qonb,
*
*      ptn,alptn,xatn,rogt,roftn,hgt,htn,tgt,tftn,
*      pn ,alpn ,xan ,rogn ,rofn ,hgn ,hfn ,tgn ,tfn ,
*      pbn,alpb,xbn,rogbn,rofbn,hgbn,hfbn,tgbn,tfbn,
*      ugt,uft,wgx,wfx,ugz,ufz,ugb,ufb,git,gi,gib,
*      eit,ei,eib,citn,cizn,cixn,cibn,hfit,hfi,hfib,
*      hgit,hgi,hgib,akgit,akgi,akgib,ysit,ysi,ysib,
*      ppln,alppln,xapln,rogpln,rofpln,hgpln,hfpln,
*      tgpln,tfpln,ptbn,alptbn,xatbn,rogtbn,roftbn,
*      hgtbn,htfbn,tgtbn,tftbn,tsec,delt,nx,nr,nzp2,
*      nzp3,nxmax,nchn,nzt,nzb,nrmax,na,nz,ncyl,
*      nsurf,isave)
*
*****
*
* SUBROUTINE store
*
* SUBROUTINE TO SAVE FLUID VARIABLE ARRAYS BY STORING
* DATA FOR A RESTART FILE AT UNIT nrsto. DATA FROM THE
* LAST CONVERGED ITERATION (OLD TIME VALUES) ARE STORED.
*
*****
implicit real (a-h,o-z), integer (i-n)

common /iounit/ ninp, nout, ndmp, ntmp, nrsti, nrsto

SOLID VARIABLES

dimension qwf(nsurf,na,nz), dqfdw(nsurf,na,nz),
*      qwg(nsurf,na,nz), dqgdw(nsurf,na,nz),
*      tsrfn(nsurf,na,nz), hspl(nsurf,na,nz),
*      qonb(nsurf,na,nz)

dimension tsn(nrmax,na,nz,ncyl),
*      nr(ncyl)

MIDDLE SECTION PHYSICAL PARAMETERS

dimension pn(nzp2,nxmax,nchn),
*      alpn(nzp2,nxmax,nchn), xan(nzp2,nxmax,nchn),
*      rogn(nzp2,nxmax,nchn), rofn(nzp2,nxmax,nchn),
*      hgn(nzp2,nxmax,nchn), hfn(nzp2,nxmax,nchn),
*      tgn(nzp2,nxmax,nchn), tfn(nzp2,nxmax,nchn),
*      gi(nzp2,nxmax,nchn), ei(nzp2,nxmax,nchn),
*      ugz(nzp3,nxmax,nchn), ufz(nzp3,nxmax,nchn),
*      wgx(nzp2,nxmax,nchn), wfx(nzp2,nxmax,nchn),
*      cizn(nzp3,nxmax,nchn), cixn(nzp3,nxmax,nchn),
*      hfi(nzp2,nxmax,nchn), hgi(nzp2,nxmax,nchn),
*      akgi(nzp2,nxmax,nchn), ysi(nzp2,nxmax,nchn),
*      nx(nchn)

TOP SECTION PHYSICAL PARAMETERS

dimension ptn(nzt),
*      alptn(nzt), xatn(nzt),
*      rogt(nzt), roftn(nzt),
*      hgt(nzt), hftn(nzt),
*      tgt(nzt), tftn(nzt),
*      git(nzt), eit(nzt),
*      ugt(nzt), uft(nzt),
*      citn(nzt), hfit(nzt),
*      hgit(nzt), akgit(nzt),
*      ysit(nzt)

```

```

C
C   BOTTOM SECTION PHYSICAL PARAMETERS
C
      dimension pbn(nzb),
      &         alpbn(nzb), xabn(nzb),
      &         rogbn(nzb), rofbn(nzb),
      &         hgbn(nzb), hfbn(nzb),
      &         tgbn(nzb), tfbn(nzb),
      &         gib(nzb), eib(nzb),
      &         ugb(nzb), ufb(nzb),
      &         cibn(nzb), hfib(nzb),
      &         hgib(nzb), akgib(nzb),
      &         ysib(nzb)
C
C   WRITE BINARY OR ASCII RESTART FILE
C
      if (isave.gt.0) then
C
C   WRITE BINARY RESTART FILE
C
      write (nrsto) tsec, delt
C
C   STORE SOLID TEMPERATURES
C
      do 10 icyln=1,ncyln
        nri = nr(icyln)
        write (nrsto) (((tsn(ir,ia,iz,icyln), iz=1,nz),
      &                  ia=1,na),
      &                  ir=1,nri)
10    continue
C
C   WRITE SURFACE HEAT FLUXES, HEAT FLUX DERIVATIVES, SINGLE PHASE
C   HEAT TRANSFER COEFFICIENTS, ONB HEAT FLUXES, AND TEMPERATURES
C
      write (nrsto) (((qwf(isurf,ia,iz), qwg(isurf,ia,iz),
      &                  dqfdw(isurf,ia,iz), dqgdw(isurf,ia,iz),
      &                  hspl(isurf,ia,iz), qonb(isurf,ia,iz),
      &                  tsrfn(isurf,ia,iz), iz=1,nz), ia=1,na),
      &                  isurf=1,nsurf)
C
C   STORE LOCAL PRESSURE, VOID FRACTION, AIR MASS FRACTION,
C   GAS TEMPERATURE, FLUID TEMPERATURE, GAS DENSITY, FLUID
C   DENSITY, GAS ENTHALPY, FLUID ENTHALPY, INTERFACIAL MASS
C   AND ENERGY TRANSFER RATES, AND GAS AND FLUID VELOCITIES
C
C   PLENUM
C
      write (nrsto) ppln, alppln, xapln, tgpln, tfpln,
      &               rogpln, rofpln, hqpln, hfpln
C
C   TOP SECTION
C
      write (nrsto) ( ptn(jz),
      &                  alptn(jz), xatn(jz),
      &                  tgtn(jz), tftn(jz),
      &                  rogt n(jz), roftn(jz),
      &                  hgtn(jz), hftn(jz),
      &                  git(jz), eit(jz),
      &                  ugt(jz), uft(jz),
      &                  citn(jz), hfit(jz),
      &                  hgit(jz), akgit(jz),
      &                  ysit(jz), jz=1,nzt)
C
C   MIDDLE SECTION

```

```

c
do 30 ic=1,nchn
  nsub = nx(ic)
  do 20 ix=1,nsub
    write (nrsto) ( pn(jz,ix,ic),
c      alpbn(jz,ix,ic), xabn(jz,ix,ic),
c      tgn(jz,ix,ic), tfn(jz,ix,ic),
c      rogn(jz,ix,ic), rofn(jz,ix,ic),
c      hgn(jz,ix,ic), hfn(jz,ix,ic),
c      gi(jz,ix,ic), ei(jz,ix,ic),
c      wgx(jz,ix,ic), wfx(jz,ix,ic),
c      ugz(jz,ix,ic), ufz(jz,ix,ic),
c      cizn(jz,ix,ic), cixn(jz,ix,ic),
c      hfi(jz,ix,ic), hgi(jz,ix,ic),
c      akgi(jz,ix,ic), ysi(jz,ix,ic), jz=1,nzp2)
    write (nrsto) ugz(nzp3,ix,ic), ufz(nzp3,ix,ic),
c      cizn(nzp3,ix,ic), cixn(nzp3,ix,ic)
20    continue
30    continue
c
c    BOTTOM SECTION
c
    write (nrsto) ( pbn(jz),
c      alpbn(jz), xabn(jz),
c      tgbn(jz), tfbn(jz),
c      rogbn(jz), rofbn(jz),
c      hgbn(jz), hfbn(jz),
c      gib(jz), eib(jz),
c      ugb(jz), ufb(jz),
c      cibn(jz), hfib(jz),
c      hgib(jz), akgib(jz),
c      ysib(jz), jz=1,nzb)
c
c    TANK BOTTOM
c
    write (nrsto) ptbn, alptbn, xatbn, tgtbn, tftbn,
c      rogtbn, roftbn, hgtbn, hftbn
    return
c
    else
c
c    WRITE ASCII RESTART FILE
c
    write (nrsto,*) tsec, delt
c
c    STORE SOLID TEMPERATURES
c
    do 40 icyln=1,ncyln
      nri = nr(icyln)
      write (nrsto,*) ((tsn(ir,ia,iz,icyln), iz=1,nz),
c      ia=1,na),
c      ir=1,nri)
40    continue
c
c    WRITE SURFACE HEAT FLUXES, HEAT FLUX DERIVATIVES, SINGLE PHASE
c    HEAT TRANSFER COEFFICIENTS, ONB HEAT FLUXES, AND TEMPERATURES
c
    write (nrsto,*) ((qwf(isurf,ia,iz), qwg(isurf,ia,iz),
c      dqfdw(isurf,ia,iz), dqgdw(isurf,ia,iz),
c      hspl(isurf,ia,iz), qonb(isurf,ia,iz),
c      tsrfn(isurf,ia,iz), iz=1,nz), ia=1,na),
c      isurf=1,nsurf)
c
c    STORE LOCAL PRESSURE, VOID FRACTION, AIR MASS FRACTION,

```



```

c      GAS TEMPERATURE, FLUID TEMPERATURE, GAS DENSITY, FLUID
c      DENSITY, GAS ENTHALPY, FLUID ENTHALPY, INTERFACIAL MASS
c      AND ENERGY TRANSFER RATES, AND GAS AND FLUID VELOCITIES
c
c      PLENUM
c
c      write (nrsto,*) pp1n, alpp1n, xap1n, tgpln, tfpln,
c      &      rogpln, rofpln, hgpln, hfpln
c
c      TOP SECTION
c
c      write (nrsto,*) ( ptn(jz),
c      &      alptn(jz), xatn(jz),
c      &      tgt1n(jz), tftn(jz),
c      &      rogt1n(jz), roftn(jz),
c      &      hgt1n(jz), hftn(jz),
c      &      git(jz), eit(jz),
c      &      ugt(jz), uft(jz),
c      &      citn(jz), hfit(jz),
c      &      hgit(jz), akgit(jz),
c      &      ysit(jz), jz=1,nzt)
c
c      MIDDLE SECTION
c
c      do 60 ic=1,nchn
c      nsub = nx(ic)
c      do 50 ix=1,nsub
c      write (nrsto,*) ( pn(jz,ix,ic),
c      &      alpn(jz,ix,ic), xan(jz,ix,ic),
c      &      tgn(jz,ix,ic), tfn(jz,ix,ic),
c      &      rogn(jz,ix,ic), rofn(jz,ix,ic),
c      &      hgn(jz,ix,ic), hfn(jz,ix,ic),
c      &      gi(jz,ix,ic), ei(jz,ix,ic),
c      &      wgx(jz,ix,ic), wfx(jz,ix,ic),
c      &      ugz(jz,ix,ic), ufz(jz,ix,ic),
c      &      cizn(jz,ix,ic), cixn(jz,ix,ic),
c      &      hfi(jz,ix,ic), hgi(jz,ix,ic),
c      &      akgi(jz,ix,ic), ysi(jz,ix,ic),
c      &      jz=1,nzp2)
c      write (nrsto,*) ugz(nzp3,ix,ic), ufz(nzp3,ix,ic),
c      &      cizn(nzp3,ix,ic), cixn(nzp3,ix,ic)
c      continue
c      continue
c
c      BOTTOM SECTION
c
c      write (nrsto,*) ( pbn(jz),
c      &      alpbn(jz), xabn(jz),
c      &      tqbn(jz), tfbn(jz),
c      &      rogbn(jz), rofbn(jz),
c      &      hgbn(jz), hfbn(jz),
c      &      gib(jz), eib(jz),
c      &      ugb(jz), ufb(jz),
c      &      cibn(jz), hfib(jz),
c      &      hgib(jz), akgib(jz),
c      &      ysib(jz), jz=1,nzb)
c
c      TANK BOTTOM
c
c      write (nrsto,*) ptbn, alptbn, xatbn, tgtbn, tftbn,
c      &      rogtbn, roftbn, hgtbn, hftbn
c
c      end if
c      return

```

end

SURTEN

```

subroutine surten(t,sigma)
c
c *****
c *
c * INPUT:
c *   t = TEMPERATURE IN K
c *
c * OUTPUT:
c *   sigma = SURFACE TENSION OF LIQUID H2O OR D2O IN N/m
c *
c * RANGE:
c *   10C < t < 300C
c *
c *****
c
c parameter (tconv=273.15)
c data c1/+0.75743910e-1/, c2/-0.14302481e-3/,
c & c3/-0.29108772e-6/, c4/+0.28387790e-9/
c
c   tinc = t - tconv
c   sigma = c1 + (c2 + (c3 + c4*tinc)*tinc)*tinc
c
c return
c end

```

TIMSTP

```

subroutine timstp (tsec,tmid,delt,rdelt,tprev,dtprev,dtmin,dtmax,
& ugz,ufz,wgx,wfx,ugt,uft,ugb,ufb,acz,acx,act,
& acb,volc,volt,volb,alpn,rofn,tfn,
& cfl,lis,lic,ljz,lix,na,napl,nrmxp,nz,
& nsurf,ncyln,icent,nzpl,nzp2,nzp3,nxmax,nchn,
& nx,icc,tol,dif,nzt,nzb,ierr,iptime,
& istdy,ilq)
c
c *****
c *
c * SUBROUTINE timstp
c *
c * SUBROUTINE TO DETERMINE TIME STEP SIZE.
c * IF dtmin => dtmax THEN USE A FIXED TIME STEP delt = dtmin
c * OTHERWISE, SET delt EQUAL TO MINIMUM OF dtmax, OR
c * accel*dtprev WHERE dtprev IS THE PREVIOUS TIME STEP,
c * OR THE STABILITY LIMITS IN EACH FLUID CELL
c *
c *****
c implicit real (a-h,o-z), integer (i-n)
c logical first
c
c parameter (zero=0.0, half=0.5, one=1.0)
c parameter (difmin=0.0001, big=100.0)
c common /iounit/ ninp, nout, ndmp, ntmp, nrsti, nrsto
c
c MIDDLE SECTION ARRAYS
c
c dimension wx(nzp2,nxmax,nchn), ugz(nzp3,nxmax,nchn),
& wfx(nzp2,nxmax,nchn), ufz(nzp3,nxmax,nchn),
& acx(nzp2,nxmax,nchn), acz(nzp3,nxmax,nchn),
& volc(nzp2,nxmax,nchn), icc(2,nxmax,nchn),
& alpn(nzp2,nxmax,nchn), nx(nchn),
& rofn(nzp2,nxmax,nchn),

```

```
      4      tfn(nzp2,nxmax,nchn)
c
c      TOP AND BOTTOM SECTION ARRAYS
c
      dimension ugt(nzt), uft(nzt), act(nzt), volt(nzt),
      4      ugb(nzb), ufb(nzb), acb(nzb), volb(nzb)
c
      data accel/0.9/, xcfl/0.9/
c
c      RESET CFL INDICATORS
c
      cfl = -one
      lis = 0
      lic = 0
      ljz = 0
      lix = 0
c
c      BEGIN TIME STEP CONTROL LOGIC:
c
c      ON ERROR, CUT TIME STEP AND REITERATE
c
      reduc = half
      if (ierr.eq.3) then
         reduc = accel*(tol/dif)
         ierr = 1
      end if
c
      if ((ierr.eq.1) .and. (istdy.lt.2)) then
         tsec = tsec - delt
         delt = reduc*delt
         tsec = tsec + delt
         tmid = tsec - half*delt
         goto 190
      elseif ((ierr.eq.1) .and. (istdy.ge.2)) then
         delt = reduc*delt
         goto 190
      end if
c
c      WITH NO ERROR, SAVE OLD VALUES AND
c      GO ON TO THE NEXT TIME INTERVAL
c
      tprev = tsec
      dtprev = delt
c
      if (dtmin.ge.dtmax) then
         delt = dtmin
         tsec = tsec + delt
         tmid = tsec - half*delt
         rdelt = one/delt
         return
      end if
c
c      CHECK STABILITY LIMITS IN TOP SECTION
c
      cfl = big
      tcfl = big
      do 120 jz=1,nzt
         jzp = jz + 1
c
c         (j-1/2 FACE)
c
         sumg = - act(jz)*min(zero,ugt(jz))
         sumf = - act(jz)*min(zero,uft(jz))
c
```

```
c      (j+1/2 FACE)
c
      if (jzp .le. nzt) then
        sumg = sumg + act(jzp)*max(zero,ugt(jzp))
        sumf = sumf + act(jzp)*max(zero,uft(jzp))
      else
        do 110 ic=1,nchn
          nsub = nx(ic)
          do 100 ix=1,nsub
            sumg = sumg + acz(2,ix,ic)*max(zero,ugz(2,ix,ic))
            sumf = sumf + acz(2,ix,ic)*max(zero,ufz(2,ix,ic))
100          continue
110          continue
        end if
        if (sumg .gt. zero) tcfl = xcfl*volt(jz)/sumg
        if (sumf .gt. zero) tcfl = min(tcfl, xcfl*volt(jz)/sumf)
        if (tcfl .lt. cfl) then
          cfl = tcfl
          lis = 1
          ljz = jz
        end if
120      continue
c
c      CHECK STABILITY LIMITS IN MIDDLE SECTION
c
      do 150 ic=1,nchn
        nsub = nx(ic)
c
        do 140 ix=1,nsub
          ixr = icc(2,ix,ic)
c
          do 130 jz=2,nzpl
            jzm = jz - 1
            jzp = jz + 1
c
            (j-1/2 FACE)
c
            sumg =      - acz(jz,ix,ic)*min(zero,ugz(jz,ix,ic))
            sumf =      - acz(jz,ix,ic)*min(zero,ufz(jz,ix,ic))
c
            (j+1/2 FACE)
c
            sumg = sumg + acz(jzp,ix,ic)*max(zero,ugz(jzp,ix,ic))
            sumf = sumf + acz(jzp,ix,ic)*max(zero,ufz(jzp,ix,ic))
c
            (i-1/2 FACE)
c
            sumg = sumg - acx(jz,ix,ic)*min(zero,wgx(jz,ix,ic))
            sumf = sumf - acx(jz,ix,ic)*min(zero,wfx(jz,ix,ic))
c
            (i+1/2 FACE)
c
            sumg = sumg + acx(jz,ixr,ic)*max(zero,wgx(jz,ixr,ic))
            sumf = sumf + acx(jz,ixr,ic)*max(zero,wfx(jz,ixr,ic))
c
            if (sumg .gt. zero) tcfl = xcfl*volc(jz,ix,ic)/sumg
            if (sumf .gt. zero) tcfl = min(tcfl, xcfl*volc(jz,ix,ic)/sumf)
            if (tcfl .lt. cfl) then
              cfl = tcfl
              lis = 2
              lic = ic
              ljz = jzm
              lix = ix
            end if
```

```

130     continue
140     continue
150     continue
c
c     CHECK STABILITY LIMITS IN BOTTOM SECTION
c
      do 180 jz=1,nzb
        jzm = jz - 1
c
c        (j-1/2 FACE)
c
        if (jzm .ge. 1) then
          sumg = - acb(jzm)*min(zero,ugb(jzm))
          sumf = - acb(jzm)*min(zero,ufb(jzm))
        else
          sumg = zero
          sumf = zero
          do 170 ic=1,nchn
            nsub = nx(ic)
            do 160 ix=1,nsub
              sumg = sumg - acz(nzp2,ix,ic)*min(zero,ugz(nzp2,ix,ic))
              sumf = sumf - acz(nzp2,ix,ic)*min(zero,ufz(nzp2,ix,ic))
160          continue
170          continue
            end if
c
c            (j+1/2 FACE)
c
            sumg = sumg + acb(jz)*max(zero,ugb(jz))
            sumf = sumf + acb(jz)*max(zero,ufb(jz))
            if (sumg .gt. zero) tcfl = xcfl*volb(jz)/sumg
            if (sumf .gt. zero) tcfl = min(tcfl, xcfl*volb(jz)/sumf)
            if (tcfl .lt. cfl) then
              cfl = tcfl
              lis = 3
              lic = 0
              ljz = jz
              lix = 0
            end if
180          continue
c
          dif = dif + difmin
          delt = min(cfl,dtmax,accel*tol*dtprev/dif)
c
          if (istdy.lt.2) then
            tsec = tsec + delt
            tmid = tsec - half*delt
          end if
c
190          if (delt.lt.dtmin) then
            write (*,200)
            write (nout,200)
            ierr = 2
          end if
          rdelt = one/delt
c
          if (iptime.eq.10) then
            if (lis.eq.1) then
              write (*,210) tsec, delt, cfl, ljz
            else if (lis.eq.2) then
              write (*,220) tsec, delt, cfl, ljz, lix, lic
            else if (lis.eq.3) then
              write (*,230) tsec, delt, cfl, ljz
            else

```

```

        write (*,240) tsec, delt
    end if
end if
c
c  WRITE FORMATS
c
200  format (' <<< fatal error >>> time step is less than minimum',/
        '      program execution is stopping')
c
210  format (' time (s) = ',g12.5,' delt (s) = ',g12.5,/,5x,
        ' cfl = ',g12.5,' top section jz = ',i2)
220  format (' time (s) = ',g12.5,' delt (s) = ',g12.5,/,5x,
        ' cfl = ',g12.5,' middle section jz = ',i2,
        ' ix = ',i2,' ic = ',i2)
230  format (' time (s) = ',g12.5,' delt (s) = ',g12.5,/,5x,
        ' cfl = ',g12.5,' bottom section jz = ',i2)
240  format (' time (s) = ',g12.5,' delt (s) = ',g12.5)
c
    return
end

```

TRANS

```

    subroutine trans (critr,tcrit,lcrit,iredo)
c
c  *****
c  *
c  *  SUBROUTINE trans
c  *
c  *  SUBROUTINE TO CONTROL TRANSIENT CALCULATIONS
c  *
c  *****
c
    implicit real (a-h,o-z), integer (i-n)
    parameter (zero=0.0, epsln=1.0e-03)
    logical steady
c
    dimension critr(ncrit), tcrit(ncrit), lcrit(3,ncrit)
    common /iounit/ ninp, nout, ndmp, ntmp, nrsti, nrsto
c
    include 'params.inc'
    include 'points.inc'
c
c  INITIALIZE FLAGS AND TIME COUNTERS
c
    ierr = 0
    init = 0
    tprnt = tsec + epsln
    tpfld = dtpfld*(1 + int(tprnt/dtpfld))
    tpsld = dtpsld*(1 + int(tprnt/dtpsld))
    tppwr = dtppwr*(1 + int(tprnt/dtppwr))
    tpdmp = dtpdmp*(1 + int(tprnt/dtpdmp))
    isty = istdy
    steady = .false.
c
    ntwhld = 0
    call clear (a(ltwhld), nsurf*na*nz)
c
c  IF ONLY FLUID CALCULATIONS ARE REQUESTED, THEN SET WALL
c  FLUX TERMS TO ZERO.
c
    if (isolid.eq.0) then
        call clear (a(lqwf), nsurf*na*nz)
        call clear (a(lqwg), nsurf*na*nz)
        call clear (a(lgw), nzp2*nxmax*nchn)
        call clear1 (a(ltheta),nzp2*nxmax*nchn)
    end if
end

```

```

      end if
c
c      BEGIN TIME STEPS
c
100  call timstp (tsec,tmid,delt,rdelt,tprev,dtprev,dtmin,dtmax,
      &          a(lugz),a(lufz),a(lwgx),a(lwfx),a(lugt),
      &          a(luft),a(lugb),a(lufb),a(lacz),a(lacx),
      &          a(lact),a(lacb),a(lvolc),a(lvolt),a(lvolb),
      &          a(lalpn),a(lrofn),a(ltfn),cfl,lis,lic,ljz,
      &          lix,na,napl,nrmxp,nz,nsurf,ncyln,icent,
      &          nzpl,nzp2,nzp3,nxmax,nchn,ia(lnx),ia(licc),
      &          tol,dif,nzt,nzb,ierr,iscrn,istdy,ilq)
      if (ierr.eq.2) goto 200
c
      if (isolid.eq.1) then
c
c      CALCULATE DEPOSITED POWER DISTRIBUTION IN METAL
c
      call axialp (a(laxial),a(laxal0),itimex,itime,a(ltimet),tmid,
      &          a(lrdz),nz,ia(liaxlp),ia(lntp),ia(lintp),ia(litype),
      &          a(lxtp),a(lytp),a(lztp),ntpmax,ntptot,nspln,nout,
      &          izht,izhb)
c
      call pdist (a(lpows),sumdry,tnklev,a(laxial),a(laxal0),deldry,
      &          delmod,a(ldz+1),hactiv,izht,izhb,gap,asypwr,tmid,
      &          a(lbigm),a(lbigmw),a(lbigmd),a(lxtp),a(lytp),
      &          a(lztp),ia(lntp),ia(lintp),ia(litype),iflssn,
      &          itnklv,tnklv0,imodh,idryh,iconh,iexp,init,na,ncyln,
      &          ia(lnr),nz,nrmax,ntpmax,ntptot,nspln,nout)
c
c      CALCULATE SURFACE HEAT FLUXES FOR THIS TIME STEP
c
      if (ierr.eq.0) then
        call qwall (a(lqwf),a(lqwg),a(ldqfdw),a(ldqgdw),a(ltheta),
      &          a(lgw),a(lhspl),a(lqonb),a(lchfq),
      &          a(ltsurf),a(lp),a(lalp),a(lxa),a(lrog),a(lrof),
      &          a(ltg),a(ltf),a(lugz),a(lufz),a(ldhz),a(lar),
      &          tmod0,hmod,hactiv,tnklev,gap,tsec,a(ldz+1),
      &          a(lribl),a(lribt),ia(liorib),ia(lmat),iboil,ichf,
      &          matgas,persat,nsurf,na,napl,nxmax,ia(lnr),nrmax,
      &          nrmxp,ia(lnx),nz,nzp2,nzp3,nchn,ncyln,icent,
      &          ia(liazl),ia(lnazc),htdamp,iradbc,cradi,itmod,
      &          a(lxtp),a(lytp),a(lztp),ia(lntp),ia(lintp),
      &          ia(litype),nspln,ntpmax,ntptot,ilq)
      end if
c
c      CALCULATE SOLID INTERNAL AND SURFACE TEMPERATURES
c
      if (istdy.ge.1) then
        rdelts = rdelt/xdelt
      else
        rdelts = rdelt
      end if
      call solid (a(lts),a(ltsn),a(ltsurf),a(ltsrfn),a(lpows),
      &          a(lqwf),a(lqwg),a(ldqfdw),a(ldqgdw),a(lwt),
      &          a(lradc),a(lar),a(lvols),a(lzfacc),ia(lmat),
      &          rdelts,da,a(ldr),a(ldz+1),ia(lnr),na,nsurf,
      &          nz,ncyln,nrmax,nrmxp,wss,icent,iaxial,ncms)
c
      end if
c
c      OBTAIN FLUID DYNAMICS BOUNDARY CONDITIONS AT TOP AND BOTTOM
c      OF ASSEMBLY FOR NEW TIME
c

```

```

      call bound (a(lxtp),a(lytp),a(lztp),ia(lntp),ia(lintp),
&               ia(litype),nsp1n,ntpmx,ntptot,tsec,
&               ppl,alpp1,tgpl,tfpl,xapl,rogpl,rofpl,hgpl,hfpl,
&               ptb,alptb,tgtb,tftb,xatb,rogtb,roftb,hgtb,hftb,
&               ppl0,alpp10,tgpl0,tfpl0,xapl0,
&               ptb0,alptb0,tgtb0,tftb0,xatb0,
&               qfin,qgin,qfin0,qgin0,
&               ippl,ialpl,itgpl,itfpl,ixapl,
&               iptb,ialtb,itgtb,itftb,ixatb,
&               iqfin,iqgin,factor,ilq)
c
      if (ierr.eq.0) then
c
c      COMPUTE INTERFACIAL HEAT, MASS, AND MOMENTUM TRANSFER
c      COEFFICIENTS
c
      call const (a(lptn),a(lalptn),a(ltgt),a(ltftn),a(lxatn),
&               a(lrogt),a(lroftn),a(lvolt),a(lpn),a(lalpn),a(ltgn),
&               a(ltfn),a(lxan),a(lrogn),a(lrofn),a(lvolc),a(lpbn),
&               a(lalpb),a(ltgtb),a(ltftb),a(lxabn),a(lrogb),
&               a(lrofb),a(lvolb),a(lugt),a(luft),a(lact),a(ldefft),
&               a(ldht),a(lcost),a(lfldmt),a(lfldct),a(lc0bt),
&               a(lc0st),a(lckbt),a(lckst),a(lugz),a(lufz),a(lacz),
&               a(ldeffz),a(ldhz),a(lcosz),a(lfldmz),a(lfldcz),
&               a(lc0bz),a(lc0sz),a(lckbz),a(lcksz),a(lugb),a(lufb),
&               a(lacb),a(ldeffb),a(ldhb),a(lcosb),a(lfldmb),
&               a(lfldcb),a(lc0bb),a(lc0sb),a(lckbb),a(lcksb),
&               a(lhgit),a(lhfit),a(lakgit),a(lysit),a(lcitn),a(lhgi),
&               a(lhfi),a(lakgi),a(lysi),a(lcizn),a(lcixn),a(lhgib),
&               a(lhfib),a(lakgib),a(lysi),a(lcibn),ppln,alpp1n,
&               tgpln,tfpln,xapl,rogpln,rofpln,volpl,ptbn,alptbn,
&               tgtbn,tftbn,xatbn,rogtbn,roftbn,voltb,cidamp,nzt,
&               nzp1,nzp2,nzp3,nxmax,ia(lnx),nchn,nzb,dtprev,ilq)
c
c      CALCULATE EXPLICIT TURBULENT MASS EXCHANGE RATES
c
      call turbx (a(lp),a(ltg),a(ltf),a(lxa),a(ldhz),a(lalpn),
&               a(lxan),a(lrogn),a(lrofn),a(lhgn),a(lhfn),
&               a(lugz),a(lufz),a(lacz),a(ldz),a(lvolc),
&               a(ltxg),a(ltxf),ia(lnx),ia(licc),vminz,xturb,
&               nzp1,nzp2,nzp3,nchn,nxmax,a(laxx),ilq)
c
c      CALCULATE EXPLICIT TERMS IN MOMENTUM EQUATIONS
c
      call explct (a(lbgz),a(lbfz),a(lcgz),a(lcfz),a(ldgx),a(ldfx),
&               a(legx),a(lefz),a(lacz),a(laratx),a(ldhz),a(lcosz),
&               a(lugz),a(lufz),a(labsrz),a(lfmltz),a(lformz),
&               a(lfrez),a(ldzm),a(lcizn),a(lcixn),a(lc0bz),a(lc0sz),
&               a(lacx),a(laratx),a(ldhx),a(lcosx),a(lwgx),a(lwfx),
&               a(labsrx),a(lfmltx),a(lformx),a(lfrez),a(laxx),
&               a(lazz),a(laxx),a(lvolc),a(lpn),a(lalpn),a(ltgn),
&               a(ltfn),a(lxan),a(lrogn),a(lrofn),a(ltheta),a(ltxf),
&               a(ltxg),a(lact),a(laratx),a(ldht),a(lcost),a(ldzmt),
&               a(lugt),a(luft),a(labsrt),a(lfmltt),a(lformt),
&               a(lfret),a(lcitn),a(lc0bt),a(lc0st),a(lazt),a(lvolt),
&               a(lptn),a(lalptn),a(ltgt),a(ltftn),a(lxatn),
&               a(lrogt),a(lroftn),a(lbgt),a(lbft),a(lcgt),a(lcft),
&               a(lacb),a(laratb),a(ldhb),a(lcosb),a(ldzmb),a(lugb),
&               a(lufb),a(labsrb),a(lfmltb),a(lformb),a(lfrez),
&               a(lcibn),a(lc0bb),a(lc0sb),a(lazb),a(lvolb),a(lpbn),
&               a(lalpb),a(ltgtb),a(ltftb),a(lxabn),a(lrogb),
&               a(lrofb),a(lbgb),a(lbfb),a(lcgb),a(lcfb),a(lacin),
&               a(lugin),a(lufin),a(lalpin),a(lrogin),a(lrofin),
&               a(lacex),a(lugex),a(lufex),a(lalpex),a(lrogex),

```



```

      a(lrofex),ia(lnx),ia(licc))
      if (ierr.eq.2) goto 200
C
C      SET UP DONOR ARRAYS USED BY JACOB IN TOP SECTION
C
      call donort (a(lalptn),a(lxatn),a(lrogt),a(lroftn),a(lhgt),
      a(lhftn),alppln,xapln,rogpln,rofpln,hgpln,hfpln,
      a(lugt),a(luft),a(lbgt),a(lcgt),a(lbft),a(lcft),
      a(lact),a(ladvbt),a(ladvct),vminz,nzt)
C
C      SET UP DONOR ARRAYS USED BY JACOB IN MIDDLE SECTION
C
      call donorm (a(lalpn),a(lxan),a(lrogn),a(lrofn),a(lhgn),a(lhfn),
      a(lugz),a(lufz),a(lbgz),a(lcgz),a(lbfz),a(lcfz),
      a(lwgx),a(lwfx),a(ldgx),a(legx),a(ldfx),a(lex),
      a(lacz),a(lacx),a(ladvbz),a(ladvcz),a(ladvdx),
      a(ladvex),vminz,vminx,nzp1,nzp2,nzp3,nchn,nxmax,
      ia(lnx),ia(licc))
C
C      SET UP DONOR ARRAYS USED BY JACOB IN BOTTOM SECTION
C
      call donorb (a(lalpb),a(lxab),a(lrogb),a(lrofb),a(lhgb),
      a(lhfb),alptbn,xatbn,rogtbn,roftbn,hgtbn,hftbn,
      a(lugb),a(lufb),a(lbgb),a(lcgb),a(lbfb),a(lcfb),
      a(lacb),a(ladvbb),a(ladvcb),vminz,nzb)
      end if
C
C      PERFORM NEWTON ITERATIONS TO SOLVE FLUID CONSERVATION EQUATIONS
C
      call newton (a(lazm1),a(lazm2),a(laxm1),a(laxm2),a(lrhs),a(lsx),
      a(lsz),a(lt),a(ldpm),a(latm1),a(lrhst),a(lst),a(labm1),a(lrhsb),
      a(lsb),a(lcmesh),a(lar),a(lvolc),a(lvolt),a(lvolb),a(lcpat),
      a(lcptgt),a(lcptft),a(lcpzat),a(lfat),a(lftgt),a(lftft),a(lfxat),
      a(lcpt),a(lcpa),a(lcptg),a(lcptf),a(lcpza),a(lfa),a(lftg),
      a(lftf),a(lfxa),a(ldp),a(lcpab),a(lcptgb),a(lcptfb),a(lcpxab),
      a(lrogb),a(lftgb),a(lftfb),a(lfxab),a(ldpb),a(lptn),a(lalptn),
      a(lxatn),a(lrogt),a(lhgt),a(lroft),a(lhft),a(ltgn),a(ltftn),
      a(lpt),a(lalpt),a(lxat),a(lrogt),a(lhgt),a(lroft),a(lhft),
      a(ltgn),a(ltft),a(lpn),a(lalpn),a(lxan),a(lrogn),a(lhgn),
      a(lrofn),a(lhfn),a(ltgn),a(ltfn),a(lp),a(lalp),a(lxa),a(lrog),
      a(lhg),a(lrof),a(lhf),a(ltg),a(ltf),a(lpb),a(lalpb),a(lxab),
      a(lrogb),a(lhgb),a(lrofb),a(lhfb),a(ltgb),a(ltfn),a(lpb),
      a(lalpb),a(lxab),a(lrogb),a(lhgb),a(lrofb),a(lhfb),a(ltgb),
      a(ltfn),a(lgit),a(lgit),a(lysit),a(lhgit),a(lhfit),a(lakgit),
      a(lgi),a(lei),a(lysi),a(lhgi),a(lhfi),a(lakgi),a(lgib),a(leib),
      a(lysi),a(lhgi),a(lhfi),a(lakgi),a(ladvbz),a(ladvcz),
      a(ladvdx),a(ladvex),a(ladvbt),a(ladvct),a(ladvbb),a(ladvcb),
      a(lbgt),a(lbft),a(lcgt),a(lcft),a(lbgz),a(lbfz),a(lcgz),a(lcfz),
      a(ldgx),a(ldfx),a(legx),a(lex),a(lbgb),a(lbfb),a(lcgb),a(lcfb),
      a(lgw),a(lqwf),a(lqwg),a(lhspl),a(ltsurf),a(ltxg),a(ltxf),
      ia(liaz1),ia(lnazc),ia(lnx),ia(lnr),ia(licc))
C
C      PERFORM ACCURACY CHECK ON FLUID CALCULATIONS
C
      if (ierr.eq.0) then
        call accchk (a(lpt),a(lalpt),a(ltgt),a(ltft),a(lxat),
        a(lrogt),a(lroft),a(lhgt),a(lhft),a(lp),
        a(lalp),a(ltg),a(ltf),a(lxa),a(lrog),
        a(lrof),a(lhg),a(lhf),a(lpb),a(lalpb),
        a(ltgb),a(ltfn),a(lxab),a(lrogb),a(lrofb),
        a(lhgb),a(lhfb),a(lptn),a(lalptn),a(ltgn),
        a(ltftn),a(lxatn),a(lrogt),a(lroftn),
        a(lhgt),a(lhftn),a(lpn),a(lalpn),a(ltgn),
        a(ltfn),a(lxan),a(lrogn),a(lrofn),a(lhgn),

```

```

      a(lhfn),a(lpbn),a(lalpb),a(ltgb),a(ltfb),
      a(lxabn),a(lrogb),a(lrofb),a(lhgb),a(lhfb),
      a(lvolt),a(lvolc),a(lvolb),a(ltsurf),a(ltsrfn),
      nsurf,na,nz,nzt,nzpl,nzp2,nxmax,nchn,ia(lnx),
      nzb,ierr,istdy,tol,tolss,nstdy,delt,tsec,dif,
      difp,difalp,diftg,diftf,difxa,difts,delhm,
      steady)
    end if

c
c   CHECK IF FLUID AND SOLID PROPERTIES HAVE BEEN EVALUATED AT
c   TEMPERATURES WITHIN THE RANGE OF THE DATA CORRELATIONS
c
    if (ierr.eq.0) then
      call propck (a(lpt),a(lalpt),a(ltgt),a(ltft),a(lp),a(lalp),
      a(ltg),a(ltf),a(lpb),a(lalpb),a(ltgb),a(ltfb),
      a(lts),nzt,nzpl,nzp2,nxmax,nchn,ia(lnx),nzb,
      ia(lmat),nrmax,ncyln,ia(lnr),na,nz,ilq,ierr)
    end if

c
    if (ierr.eq.0) then
c
c   UPDATE SOLUTION FOR FLUID VELOCITIES
c
      call updatv (a(lbgt),a(lbft),a(lcgt),a(lcft),a(lpt),a(lugt),
      a(luft),a(lbgz),a(lbfz),a(lcgz),a(lcfz),a(lp),
      a(lugz),a(lufz),a(ldgx),a(ldfx),a(legx),a(lefz),
      a(lwgx),a(lwfx),a(lgbg),a(lgbf),a(lcgb),a(lcfb),
      a(lpb),a(lugb),a(lufb),ppl,ptb,nzt,nzpl,
      nzp2,nzp3,nxmax,nchn,ia(lnx),ia(licc),nzb)

c
    else
c
c   RESET NEW TIME VALUES TO OLD TIME VALUES ON TIME STEP REDUCTION
c
      call reset (a(ltsn),a(ltsrfn),a(lts),a(ltsurf),
      a(lpn),a(lalpn),a(lxan),a(lrogn),a(lrofn),a(lhgn),
      a(lhfn),a(ltgn),a(ltfn),a(lp),a(lalp),a(lxa),
      a(lrog),a(lrof),a(lhg),a(lhf),a(ltg),a(ltf),
      a(lptn),a(lalptn),a(lxatn),a(lrogn),a(lroftn),
      a(lhgt),a(lhft),a(ltgt),a(ltftn),a(lpt),
      a(lalpt),a(lxat),a(lrogt),a(lroft),a(lhgt),a(lhft),
      a(ltgt),a(ltft),a(lpb),a(lalpb),a(lxab),
      a(lrogb),a(lrofb),a(lhgb),a(lhfb),a(ltgb),
      a(ltfn),a(lpb),a(lalpb),a(lxab),a(lrogb),a(lrofb),
      a(lhgb),a(lhfb),a(ltgb),a(ltfn),
      ppln,xapl,rogpl,roftpl,hgpl,hfpl,tgpl,tfpl,
      ppl,xapl,rogpl,roftpl,hgpl,hfpl,tgpl,tfpl,
      ptbn,xatbn,rogtbn,roftbn,hgtbn,hftbn,tgtbn,tftbn,
      ptb,xatb,rogtb,roftb,hgtb,hftb,tgtb,tftb,
      alppln,alppl,alptbn,alptb,nzp2,nxmax,nchn,nzt,nzb,
      nrmax,na,nz,ncyln,nsurf)

      goto 100

c
    end if

c
c   PERFORM CRITERIA CHECKING
c
    call crit (critr,tcrit,tcmax,lcrit,icrit,ncrit,a(lpkfac),tsec,
    a(ltsurf),a(lp),a(ltf),a(lugz),a(lufz),a(lpt),a(ltft),
    a(lugt),a(luft),a(lpb),a(ltfn),a(lugb),a(lufb),tfpl,
    tsupw,ia(lichks),ia(lichkc),ia(lnx),ia(liazl),
    ia(lnazc),nchn,nxmax,nz,nzpl,nzp2,nzp3,nzt,nzb,
    nsurf,na,napl,icent,iredo,nout,a(ldefft),a(ldeffz),
    a(ldeffb),a(lfldmt),a(lfldmz),a(lfldmb),a(lfldct),

```

```

6      a(lfldcz),a(lfldcb),a(ldxm),a(ldhz),vminz,alppln,
6      rogp1n,rofpln,a(lalptn),a(lrogt1n),a(lroftn),a(lalpn),
6      a(lrogn),a(lrofn),a(lalpbn),a(lrogbn),a(lrofbn),
6      alptbn,rogtbn,roftbn,twinst,a(ltwhld),ntwhld,ilq)
      if (iredo.eq.1) return
c
c      CHECK TIME AND PRINT RESULTS
c
      tprnt = tsec + epsln
c
c      SOLID EDIT
c
      if ((isolid.eq.1) .and. steady) then
          call prtsld (a(lts),a(ltsurf),a(lqwf),a(lqwg),tsec,ia(lnr),
6              nrmx,na,nz,ncyl,nsurf)
      else if ((tprnt.ge.tpsld) .and. (isolid.eq.1)) then
          tpsld = tpsld + dtpsld
          call prtsld (a(lts),a(ltsurf),a(lqwf),a(lqwg),tsec,ia(lnr),
6              nrmx,na,nz,ncyl,nsurf)
      end if
c
c      FLUID EDIT
c
      if (steady) then
          call prtflld (a(lpt),a(lalpt),a(lxat),a(lrogt),a(lroft),
6              a(lhgt),a(lhft),a(ltgt),a(ltft),a(lvolt),
6              a(lp),a(lalp),a(lxa),a(lrog),a(lrof),
6              a(lhg),a(lhf),a(ltg),a(ltf),a(lvolc),
6              a(lpb),a(lalpb),a(lxab),a(lrogb),a(lrofb),
6              a(lhgb),a(lhfb),a(ltgb),a(ltfb),a(lvolb),
6              a(lalptn),a(lrogt1n),a(lroftn),a(lalpn),a(lrogn),
6              a(lrofn),a(lalpbn),a(lrogbn),a(lrofbn),
6              a(lugt),a(luft),a(lwgx),a(lwfx),a(lugz),a(lufz),
6              a(lugb),a(lufb),a(lact),a(lacx),a(lacz),a(lacb),
6              a(lysit),a(lysi),a(lysib),a(lgit),a(lgi),a(lgib),
6              a(leit),a(lei),a(leib),a(lgw),
6              ppl,alpp1,tgpl,tfpl,xapl,rogpl,rofpl,hgpl,hfpl,
6              ptb,alptb,tgtb,tftb,xatb,rogtb,roftb,hgtb,hftb,
6              alpp1n,rogpln,rofpln,ppln,tgpln,xapl1n,alptbn,
6              rogtbn,roftbn,volpl,voltb,tsec,delt,vminz,vminx,
6              ia(licc),ia(lnx),nzp1,nzp2,nzp3,nxmax,nchn,nzt,
6              nzb,cfl,lis,lic,ljz,lix,iunits,iprint,ilq)
      else if (tprnt.ge.tpflld) then
          tpflld = tpflld + dtpflld
          call prtflld (a(lpt),a(lalpt),a(lxat),a(lrogt),a(lroft),
6              a(lhgt),a(lhft),a(ltgt),a(ltft),a(lvolt),
6              a(lp),a(lalp),a(lxa),a(lrog),a(lrof),
6              a(lhg),a(lhf),a(ltg),a(ltf),a(lvolc),
6              a(lpb),a(lalpb),a(lxab),a(lrogb),a(lrofb),
6              a(lhgb),a(lhfb),a(ltgb),a(ltfb),a(lvolb),
6              a(lalptn),a(lrogt1n),a(lroftn),a(lalpn),a(lrogn),
6              a(lrofn),a(lalpbn),a(lrogbn),a(lrofbn),
6              a(lugt),a(luft),a(lwgx),a(lwfx),a(lugz),a(lufz),
6              a(lugb),a(lufb),a(lact),a(lacx),a(lacz),a(lacb),
6              a(lysit),a(lysi),a(lysib),a(lgit),a(lgi),a(lgib),
6              a(leit),a(lei),a(leib),a(lgw),
6              ppl,alpp1,tgpl,tfpl,xapl,rogpl,rofpl,hgpl,hfpl,
6              ptb,alptb,tgtb,tftb,xatb,rogtb,roftb,hgtb,hftb,
6              alpp1n,rogpln,rofpln,ppln,tgpln,xapl1n,alptbn,
6              rogtbn,roftbn,volpl,voltb,tsec,delt,vminz,vminx,
6              ia(licc),ia(lnx),nzp1,nzp2,nzp3,nxmax,nchn,nzt,
6              nzb,cfl,lis,lic,ljz,lix,iunits,iprint,ilq)
      end if
c

```

c POWER EDIT

c

```

if ((isolid.eq.1) .and. steady) then
  call prtpow (a(laxial),a(laxal0),deldry,delmod,hactiv,gap,
&             a(lpows),asypwr,tsec,a(lxtp),a(lytp),a(lztp),
&             ia(lntp),ia(lintp),ia(litype),ifissn,itnklv,
&             tnklv0,imodh,idryh,iconh,iexp,na,ncyl,ia(lnr),
&             nz,nrmax,ntpmax,ntptot,nspln,nout,izht,izhb)
else if ((tprnt.ge.tppwr) .and. (isolid.eq.1)) then
  tppwr = tppwr + dtpwr
  call prtpow (a(laxial),a(laxal0),deldry,delmod,hactiv,gap,
&             a(lpows),asypwr,tsec,a(lxtp),a(lytp),a(lztp),
&             ia(lntp),ia(lintp),ia(litype),ifissn,itnklv,
&             tnklv0,imodh,idryh,iconh,iexp,na,ncyl,ia(lnr),
&             nz,nrmax,ntpmax,ntptot,nspln,nout,izht,izhb)
end if

```

c

c

c

PRINT RESULTS TO DATA PLOTTING FILE

```

if ((dtpdmp.le.runsec) .and. steady) then
  call dmpplt (a(lts),a(ltsurf),a(lqwf),a(lqwg),a(lpt),
&             a(lalpt),a(lxat),a(lrogt),a(lroft),a(lhgt),
&             a(lhft),a(ltgt),a(ltft),a(lp),a(lalp),a(lxa),
&             a(lrog),a(lrof),a(lhg),a(lhf),a(ltg),a(ltf),
&             a(lpb),a(lalpb),a(lxab),a(lrogb),a(lrofb),
&             a(lhgb),a(lhfb),a(ltgb),a(ltfb),a(lugt),a(luft),
&             a(lwgx),a(lwfx),a(lugz),a(lufz),a(lugb),a(lufb),
&             ppl,alppl,tgpl,tfpl,xapl,rogpl,rofpl,hgpl,hfpl,
&             ptb,alptb,tgtb,tftb,xatb,rogtb,roftb,hgtb,hftb,
&             tsec,ia(lnx),ia(lnr),nzpl,nzp2,nzp3,nxmax,nchn,
&             nsubc,nzt,nzb,nrmax,na,nz,ncyl,nsurf)
else if (tprnt.ge.tpdmp) then
  tpdmp = tpdmp + dtpdmp
  call dmpplt (a(lts),a(ltsurf),a(lqwf),a(lqwg),a(lpt),
&             a(lalpt),a(lxat),a(lrogt),a(lroft),a(lhgt),
&             a(lhft),a(ltgt),a(ltft),a(lp),a(lalp),a(lxa),
&             a(lrog),a(lrof),a(lhg),a(lhf),a(ltg),a(ltf),
&             a(lpb),a(lalpb),a(lxab),a(lrogb),a(lrofb),
&             a(lhgb),a(lhfb),a(ltgb),a(ltfb),a(lugt),a(luft),
&             a(lwgx),a(lwfx),a(lugz),a(lufz),a(lugb),a(lufb),
&             ppl,alppl,tgpl,tfpl,xapl,rogpl,rofpl,hgpl,hfpl,
&             ptb,alptb,tgtb,tftb,xatb,rogtb,roftb,hgtb,hftb,
&             tsec,ia(lnx),ia(lnr),nzpl,nzp2,nzp3,nxmax,nchn,
&             nsubc,nzt,nzb,nrmax,na,nz,ncyl,nsurf)
end if

```

c

c

c

PRINT RESULTS TO SCREEN

```

if (iscrn.gt.0 .and. iscrn.lt.3) then
  call prtscrn (a(lpt),a(lalpt),a(ltgt),a(ltft),a(lxat),
&             a(lrogt),a(lroft),a(lhgt),a(lhft),
&             a(lp),a(lalp),a(ltg),a(ltf),a(lxa),
&             a(lrog),a(lrof),a(lhg),a(lhf),
&             a(lpb),a(lalpb),a(ltgb),a(ltfb),a(lxab),
&             a(lrogb),a(lrofb),a(lhgb),a(lhfb),
&             ppl,alppl,tgpl,tfpl,xapl,rogpl,rofpl,hgpl,hfpl,
&             ptb,alptb,tgtb,tftb,xatb,rogtb,roftb,hgtb,hftb,
&             a(lugt),a(luft),a(lugz),a(lufz),a(lwgx),a(lwfx),
&             a(lugb),a(lufb),nzt,nzpl,nzp2,nzp3,nxmax,nchn,
&             ia(lnx),nzb,tsec,delt,dtmin,dtmax,nitno,iitot,
&             dif,difp,difalp,diftg,diftf,difxa,difts,delhm,
&             a(lysit),a(lysi),a(lysi),a(lgit),
&             a(lgi),a(lgib),critr,ncrit,iscrn,twinst,cfl,
&             vminz,a(lact))

```

```

      end if
C
C      RESET OLD TIME (n) VALUES OF VARIABLES FOR NEW TIME STEP
C
      call reset (a(lts),a(ltsurf),a(ltsn),a(ltsrfn),
        &      a(lp),a(lalp),a(lxa),a(lrog),a(lrof),a(lhg),a(lhf),
        &      a(ltg),a(ltf),a(lpn),a(lalpn),a(lxan),a(lrogn),
        &      a(lrofn),a(lhgn),a(lhfn),a(ltgn),a(ltfn),a(lpt),
        &      a(lalpt),a(lxat),a(lrogt),a(lroft),a(lhgt),a(lhft),
        &      a(ltgt),a(ltft),a(lptn),a(lalptn),a(lxatn),
        &      a(lrogt),a(lroft),a(lhgt),a(lhft),a(ltgt),
        &      a(ltft),a(lpb),a(lalpb),a(lxab),a(lrogb),a(lrofb),
        &      a(lhgb),a(lhfb),a(ltgb),a(ltfb),a(lpbn),a(lalpb),
        &      a(lxab),a(lrogb),a(lrofb),a(lhgb),a(lhfb),
        &      a(ltgb),a(ltfb),
        &      ppl,xapl,rogpl,rofpl,hgpl,hfpl,tgpl,tfpl,
        &      ppln,xapln,rogpln,rofpln,hgpln,hfpln,tgpln,tfpln,
        &      ptb,xatb,rogtb,roftb,hgtb,hftb,tgtb,tftb,
        &      ptbn,xatbn,rogtbn,roftbn,hgtbn,hftbn,tgtbn,tftbn,
        &      alppl,alppln,alptb,alptbn,nzp2,nxmax,nchn,nzt,nzb,
        &      nrmax,na,nz,ncyl,nsurf)
C
C      IF NOT FINISHED, RETURN FOR ANOTHER TIME STEP
C
      if ((istdy.eq.3) .and. steady) then
        istdy = 0
        steady = .false.
      end if
      if ((tsec.lt.runsec) .and. (.not. steady)) goto 100
      istdy = isty
C
C      END OF TRANSIENT CALCULATION
C
200  continue
C
C      CHECK FOR FATAL ERROR
C
      if (ierr.eq.2) then
        tsec = tprev
        delt = dtprev
        iredo = -1
        iset = 1
        call prtflld (a(lptn),a(lalptn),a(lxatn),a(lrogt),a(lroft),
          &      a(lhgt),a(lhft),a(ltgt),a(ltft),a(lvolt),
          &      a(lpn),a(lalpn),a(lxan),a(lrogn),a(lrofn),
          &      a(lhgn),a(lhfn),a(ltgn),a(ltfn),a(lvolc),
          &      a(lpbn),a(lalpb),a(lxab),a(lrogb),a(lrofb),
          &      a(lhgb),a(lhfb),a(ltgb),a(ltfb),a(lvolb),
          &      a(lalptn),a(lrogt),a(lroft),a(lalpn),a(lrogn),
          &      a(lrofn),a(lalpb),a(lrogb),a(lrofb),
          &      a(lugt),a(luft),a(lwgx),a(lwfx),a(lugz),a(lufz),
          &      a(lugb),a(lufb),a(lact),a(lacx),a(lacz),a(lacb),
          &      a(lysit),a(lysi),a(lysib),a(lgit),a(lgi),a(lgib),
          &      a(leit),a(lei),a(leib),a(lgw),ppln,alppln,tgpln,
          &      tfpln,xapln,rogpln,rofpln,hgpln,hfpln,ptbn,
          &      alptbn,tgtbn,tftbn,xatbn,rogtbn,roftbn,hgtbn,
          &      hftbn,alppln,rogpln,rofpln,ppln,tgpln,xapln,
          &      alptbn,rogtbn,roftbn,volpl,voltb,tsec,delt,
          &      vminz,vminx,ia(licc),ia(lnx),nzpl,nzp2,nzp3,
          &      nxmax,nchn,nzt,nzb,cfl,lis,lic,ljz,lix,iunits,
          &      iset,ilq)
      end if
C
C      CHECK IF A RESTART DUMP IS REQUESTED

```

TRIDAG

```

subroutine tridag (first,istart,iend,neq,a,b,c,d,x,s)

C
C *****
C
C *
C *      subroutine tridag
C *
C *      A GENERALIZED TRI-DIAGONAL MATRIX SOLVER TO HANDLE SYSTEMS
C *      OF SIMULTANEOUS LINEAR EQUATIONS WITH A TRI-DIAGONAL
C *      COEFFICIENT MATRIX AND POSSIBLY NON-ZERO ELEMENTS IN THE
C *      CORNER POSITIONS, WE SOLVE [A]x=d WHERE [A] IS AN n BY n
C *      MATRIX OF THE FORM
C *
C *
C *      | b1 c1 0      . . .      a1 |
C *      | a2 b2 c2      . . .      |
C *      | 0 a3 b3 c3    . . .      |
C *      | . . . .      . . .      |
C *      | . . . .      . . .      |
C *      | . . . .      . . .      |
C *      | cn          . . .      an bn |
C *
C *
C *      WHERE a1 AND cn MAY BE ZERO, THE POSSIBILITY OF NON-ZERO
C *      TERMS IS INCLUDED FOR AZIMUTHAL COUPLING IN CYLINDRICAL
C *      GEOMETRY
C *
C *****
implicit real (a-h,o-z), integer (i-n)
parameter (imax=100)
parameter (zero=0.0, one=1.0)
logical first

```

```

        dimension a(neq), b(neq), c(neq), d(neq), x(neq), s(2,neq),
        &          beta(imax)
c
c      istop = iend - 1
c      istrt = istart + 1
c      if (first) then
c
c      ON THE FIRST ENTRY, DECOMPOSE THE MATRIX BY COMPUTING
c      THE INTERMEDIATE ARRAYS beta AND s AND THE VALUE OF THE
c      COEFFICIENT rho
c
c      THE s VECTORS ARE INTRODUCED TO SAVE INTERMEDIATE RESULTS
c      WHICH DO NOT CHANGE FOR ITERATIVE SOLUTIONS, THESE TERMS
c      ONLY ARISE FROM THE EXTRA CORNER ELEMENTS IN THE MATRIX
c
c      NOTE THAT MATRIX VECTORS b AND c ARE MODIFIED SO THE
c      ORIGINAL [A] MATRIX IS LOST
c
c          phi = b(iend)
c          rho = d(iend)
c          s(2,istart) = c(iend)
c
c          b(istart) = one/b(istart)
c          c(istart) = c(istart)*b(istart)
c          s(1,istart) = a(istart)*b(istart)
c          beta(istart) = d(istart)*b(istart)
c
c      do 10 i=istrt,istop
c          iml = i - 1
c          b(i) = one/(b(i) - a(i)*c(iml))
c          c(i) = c(i)*b(i)
c          beta(i) = (d(i) - a(i)*beta(iml))*b(i)
c          s(1,i) = - a(i)*s(1,iml)*b(i)
c
c          rho = rho - beta(iml)*s(2,iml)
c          phi = phi - s(1,iml)*s(2,iml)
c          s(2,i) = - c(iml)*s(2,iml)
10      continue
c
c      s(1,iend) = a(iend) + s(2,istop)
c      denom = (phi - s(1,iend)*(c(istop) + s(1,istop)))
c      if (denom.eq.zero) then
c          write (*,*) ' << fatal error >>',
        &          ' singular matrix in tridag!'
c          stop
c      else
c          s(2,iend) = one/denom
c      end if
c
c      else
c
c      ON SUBSEQUENT ENTRIES, FOR AN ITERATIVE SOLUTION, ONLY RECOMPUTE
c      beta AND rho WHICH CHANGE WHEN THE RIGHT HAND SIDE IS ALTERED
c
c          rho = d(iend)
c          beta(istart) = d(istart)*b(istart)
c          do 20 i=istrt,istop
c              iml = i - 1
c              rho = rho - beta(iml)*s(2,iml)
c              beta(i) = (d(i) - a(i)*beta(iml))*b(i)
20      continue
c      end if
c
c      PERFORM BACK SUBSTITUTION TO COMPUTE SOLUTION VECTOR

```

```

c
  if (iend.eq.istart) then
    x(iend) = beta(istart)
  else
    x(iend) = (rho - s(1,iend)*beta(istop))*s(2,iend)
    do 30 i=istop,istart,-1
      x(i) = beta(i) - c(i)*x(i+1) - s(1,i)*x(iend)
30    continue
  end if
c
  return
end

```

TSAT

```

      subroutine tsat(p,l,ts,dtsdp)
c
c *****
c *
c * INPUT:
c *   p = PRESSURE IN Pa
c *   l = IDENTIFIER (1=1 FOR H2O, 1=2 FOR D2O)
c *
c * OUTPUT:
c *   ts = SATURATION TEMPERATURE IN K
c *   dtsdp = DERIVATIVE OF ts W.R.T. p
c *
c * RANGE:
c *   611.3Pa < p < 1.0e+6Pa
c *
c *****
c
c parameter (two=2.0, three=3.0)
c dimension c1(2), c2(2), c3(2), c4(2)
c
c H2O PROPERTIES
c
c data ptp/611.3/
c data c1(1)/+146.97/, c2(1)/+30.482 /,
c   c3(1)/-2.6382/, c4(1)/+0.14715/
c
c D2O PROPERTIES
c
c data c1(2)/+137.95/, c2(2)/+33.995 /,
c   c3(2)/-2.9758/, c4(2)/+0.15679/
c
c pmin = max(p,ptp)
c z = log(pmin)
c ts = c1(l) + (c2(l) + (c3(l) + c4(l)*z)*z)*z
c dtsdp = (c2(l) + (two*c3(l) + three*c4(l)*z)*z)/pmin
c
c if (p .lt. ptp) ts = ts - dtsdp*(ptp - p)
c
c return
c end

```

TURBX

```

      subroutine turbx (p,tg,tf,xa,dhz,alpn,xan,rogn,rofn,hgn,hfn,
c   ugz,ufz,acx,acz,dz,volc,txg,txf,nx,icc,
c   vminz,xturb,nzp1,nzp2,nzp3,nchn,nxmax,axx,ilq)
c
c *****
c *
c * SUBROUTINE NAME: turbx
c *

```



```

C      *
C      *  FUNCTION: turbx COMPUTES EXPLICIT TURBULENT AND VOID DRIFT
C      *  MASS, ENERGY, AND MOMENTUM EXCHANGE RATES BETWEEN FLUID
C      *  SUBCHANNELS TO BE USED IN THE JACOBM MODULE TO CONSTRUCT
C      *  THE JACOBIAN MATRIX WITHIN THE NEWTON ITERATIONS.
C      *
C      *
C      *****
C
C      parameter (zero=0.0, half=0.5, one=1.0)
C
C      parameter (xkapa=0.0025, g=9.8066, thetam=11.0, xkm=0.0)
C      parameter (alow=0.52, ahigh=0.75)
C      parameter (cre=0.52, xre=0.045, tenth=0.1, gapr=0.894,
C      &          eps=0.001)
C
C      ARGUMENT ARRAYS
C
C      dimension p(nzp2,nxmax,nchn),  tg(nzp2,nxmax,nchn),
C      &          tf(nzp2,nxmax,nchn),  xa(nzp2,nxmax,nchn),
C      &          acz(nzp3,nxmax,nchn),  acx(nzp2,nxmax,nchn),
C      &          alpn(nzp2,nxmax,nchn),  xan(nzp2,nxmax,nchn),
C      &          rofn(nzp2,nxmax,nchn),  rogn(nzp2,nxmax,nchn),
C      &          hfn(nzp2,nxmax,nchn),  hgn(nzp2,nxmax,nchn),
C      &          ufz(nzp3,nxmax,nchn),  ugz(nzp3,nxmax,nchn),
C      &          volc(nzp2,nxmax,nchn),  dhz(nzp3,nxmax,nchn),
C      &          axx(nzp2,nxmax,nchn)
C
C      dimension txf(4,nzp2,nxmax,nchn), txg(4,nzp2,nxmax,nchn)
C
C      dimension dz(nzp2), nx(nchn), icc(2,nxmax,nchn), flux(4)
C
C      CLEAR ARRAYS TO HOLD TURBULENT MIXING RATES
C
C      nt = 4*nzp2*nxmax*nchn
C      call clear (txg,nt)
C      call clear (txf,nt)
C      if (xturb.eq.zero) return
C
C      LOOP OVER EACH FLOW ANNULUS (CHANNEL) WITHIN ASSEMBLY CORE
C
C      do 70 k=1,nchn
C
C      LOOP OVER AZIMUTHAL MASS/ENERGY SECTORS WITHIN 2D CHANNEL
C
C      nsub = nx(k)
C      do 60 ix=1,nsub
C
C      LOOP OVER AXIAL MASS/ENERGY CELLS WITHIN AZIMUTHAL SECTOR
C
C      do 50 jz=2,nzpl
C          delz = dz(jz)
C          rarea = delz/volc(jz,ix,k)
C          call conlaw (p(jz,ix,k),tg(jz,ix,k),tf(jz,ix,k),
C      &          xa(jz,ix,k),ilq,1,1,visq,cpg,condg,
C      &          diffm,visl,cpf,condf,sigma)
C
C      LOOP OVER AXIAL FACES OF MASS CELL TO COMPUTE
C      CELL MASS FLUXES USING DONORED QUANTITIES
C
C      gmas = zero
C      fmas = zero
C      do 10 ncell=0,1
C
C      SET LOCAL POINTERS TO CELL FACES:

```

```

c      jcl = LOWER MASS CELL INDEX
c      jcu = UPPER MASS CELL INDEX
c      jf = INDEX FOR INTERMEDIATE CELL FACE
c
c          jcl = jz + ncell
c          jcu = jcl - 1
c          jf = jcl
c
c          ufld = ufz(jf,ix,k)
c          ugas = ugz(jf,ix,k)
c
c      CALCULATE LIQUID DONOR VOID AND DENSITY AT CELL FACE
c
c          if (abs(ufld).ge.vminz) then
c              wt = sign(half,ufld)
c          else
c              wt = half*ufld/vminz
c          end if
c          wtu = half + wt
c          wtl = half - wt
c          alpf = wtu*alpn(jcu,ix,k) + wtl*alpn(jcl,ix,k)
c          alpf = one - alpf
c          rhof = wtu*rofn(jcu,ix,k) + wtl*rofn(jcl,ix,k)
c          gmf = alpf*rhof*ufld
c          fmas = fmas + gmf*acz(jf,ix,k)
c
c      CALCULATE GAS DONOR VOID AND DENSITY AT CELL FACE
c
c          if (abs(ugas).ge.vminz) then
c              wt = sign(half,ugas)
c          else
c              wt = half*ugas/vminz
c          end if
c          wtu = half + wt
c          wtl = half - wt
c          alpg = wtu*alpn(jcu,ix,k) + wtl*alpn(jcl,ix,k)
c          rhog = wtu*rogn(jcu,ix,k) + wtl*rogn(jcl,ix,k)
c          gmg = alpg*rhog*ugas
c          gmas = gmas + gmg*acz(jf,ix,k)
c
c      10      continue
c
c      FIND REYNOLDS NUMBER BASED ON THE AIR-WATER MIXTURE
c      AND CALCULATE A MIXTURE VELOCITY
c
c          gm = abs(gmf + gmg)
c          re = gm*dhz(jz,ix,k)/(alpg*visg + alpf*visl)
c          vm = gm/(alpf*rhof + alpg*rhog)
c          fre = re**(-tenth)
c
c      FIND TWO-PHASE MULTIPLIER
c
c          if (alpg.le.alow) then
c              theta = one + (thetam - one)*alpg/alow
c          else if (alpg.ge.ahigh) then
c              xratio = cre*(re**xre)
c              theta = one + (thetam - one)*(one - xratio)/
c                  (alpg/ahigh - xratio)
c          else
c              theta = thetam
c          end if
c
c      IDENTIFY WHETHER GAS OR LIQUID DONORING OCCURS AT CELL

```

```

C      FACES AND CALCULATE TURBULENT EXCHANGE RATES
C
      do 40 nface=1,2
        ixa = icc(nface,ix,k)
        ixf = ix - (ix - ixa)*(nface - 1)
C
C      nface = 1: ixa = MASS CELL TO LEFT OF CURRENT CELL
C      nface = 2: ixa = MASS CELL TO RIGHT OF CURRENT CELL
C      ixf = CELL FACE BETWEEN ADJACENT MASS CELLS
C
C      FIND SINGLE PHASE TURBULENT VELOCITY
C
      gap = acx(jz,ixf,k)/delz
      width = axx(jz,ixf,k)/delz
      gapl = width - gap
      gapl = max(gapl, eps)
      gaprt = (gapl/gap)**gapr
      dhrt = dhz(jz,ixa,k)/dhz(jz,ix,k)
      usp = xkapa*fre*vm*(one + dhrt*sqrt(dhrt))
      *gaprt*dhz(jz,ix,k)/gapl
C
C      FIND TWO-PHASE TURBULENT VELOCITY
C
      utp = theta*usp
      suma = alpn(jz,ix,k) + alpn(jz,ixa,k)
      gmfa = alpf*rhof*ufz(jf,ixa,k)
      gmga = alpg*rhog*ugz(jf,ixa,k)
      sumg = gmf + gmga + gmfa + gmga
      delg = gmf + gmga - gmfa - gmga
      delgf = gmf - gmfa
      delgg = gmga - gmga
C
C      FIND EQUILIBRIUM VOID DIFFERENCE BETWEEN ADJACENT CHANNELS
C      ASSOCIATED WITH VOID DRIFT
C
      fact = xkm*delg/sumg
      eqla = fact*suma
      eqgg = fact*(gmga + gmga)
      eqgf = fact*(gmf + gmfa)
C
C      FIND THE VOID FRACTION DIFFERENCE BETWEEN ADJACENT CHANNELS
C
      dela = alpn(jz,ix,k) - alpn(jz,ixa,k)
      dela = dela - eqla
      if (dela.gt.zero) then
C
C      CELL IS DONORING GAS MASS TO ADJACENT CELL
C
C      CALCULATE GAS MASS, ENERGY, AND MOMENTUM TRANSFER RATES
C      INDEX: 1=MASS, 2=ENTHALPY, 3=AXIAL MOMENTUM, 4=AZIMUTHAL MOMENTUM
C
      xxtu = xturb*rarea*utp*gap*rhog
      flux(1) = xxtu*dela
      flux(2) = flux(1)*hgn(jz,ix,k)
      flux(3) = xturb*rarea*utp*gap*(delgg - eqgg)
      flux(4) = zero
C
C      ACCUMULATE GAS TURBULENT EXCHANGE TERMS
C
      do 20 im=1,4
        txg(im,jz,ix,k) = txg(im,jz,ix,k) - flux(im)
        txg(im,jz,ixa,k) = txg(im,jz,ixa,k) + flux(im)
      continue
20
C

```

```

      else
c
c      CELL IS DONORING LIQUID MASS TO ADJACENT CELL,
c      CALCULATE LIQUID MASS, ENERGY, AND MOMENTUM TRANSFER RATES
c      INDEX: 1=MASS, 2=ENTHALPY, 3=AXIAL MOMENTUM, 4=AZIMUTHAL MOMENTUM
c
c      xxtu = xturb*rarea*utp*gap*rhof
c      flux(1) = -xxtu*dela
c      flux(2) = flux(1)*hfn(jz,ix,k)
c      flux(3) = xturb*rarea*utp*gap*(delgf - eqgf)
c      flux(4) = zero
c
c      ACCUMULATE LIQUID TURBULENT EXCHANGE TERMS
c
c      do 30 im=1,4
c          txf(im,jz,ix,k) = txf(im,jz,ix,k) - flux(im)
c          txf(im,jz,ixa,k) = txf(im,jz,ixa,k) + flux(im)
30      continue
c
c      end if
c
c      continue
c
c      continue
c
c      continue
c
c      continue
c
c      return
c      end

```

UPDATP

```

      subroutine updatp(cpat,cptgt,cptft,cpxat,fat,ftgt,ftft,fxat,dpt,
c      & cpa ,cptg ,cptf ,cpxa ,fa ,ftg ,ftf ,fxa ,dp ,
c      & cpab,cptgb,cptfb,cpxab,fab,ftgb,ftfb,fxab,dpb,
c      & pt,alpt,tgt,tft,xat,rogt,hgt,roft,hft,
c      & p ,alp ,tg ,tf ,xa ,rog ,hg ,rof ,hf ,
c      & pb,alpb,tgb,tfb,xab,rogb,hgb,rofb,hfb,
c      & ppl,alptn,bgt,cgt,bft,cft,advbt,advct,
c      & alpn ,bgz,cgz,dgx,egx,bfz,cfz,dfx,efx,
c      & advbz,advbz,advdx,advex,
c      & ptb,alpb,bgb,cgb,bfb,cfb,advbb,advcb,
c      & factor,nzt,nzpl,nzp2,nzp3,nxmax,nchn,nx,icc,
c      & nzb,ierr,errp,erral,errtg,errtf,errxa,ilq)
c-----*-----*-----*-----*-----*-----*-----*-----*-----*
c
c      DESCRIPTION:
c      Subroutine updatp computes property values over the entire grid
c      for the mth newton iteration. Subroutine inner supplies the dp
c      corrections. Subroutine jacob supplies the dp coefficients needed
c      to recover gas volume fraction, gas temperature, liquid temperature,
c      and air mass fraction. Subroutine state is called to compute gas
c      density, gas enthalpy, liquid density, and liquid enthalpy.
c
c      jacob output:
c
c      |1 0 0 0 0| |dp | + |azm's| |dp1| = |rhs| <--- solve i by inner
c      |0 1 0 0 0| |dalp| + |cpa | | . | = |fa | <--- solved by updatp
c      |0 0 1 0 0| |dtg | + |cptg |*| . | = |ftg| <--- solved by updatp
c      |0 0 0 1 0| |dtf | + |cptf | | . | = |ftf| <--- solved by updatp
c      |0 0 0 0 1| |dxa | + |cpxa | |dpn| = |fxa| <--- solved by updatp
c
c      (matrix)      surrounding cell pressures

```

```

c
c   GLOSSARY:   I=input, O=output
c
c   ---General---
c   I factor = multiplier to increase liquid compressibility
c   O ierr = error indicator
c             (ierr=1 denotes an error and forces a time step reduction)
c
c   ---Top Section---
c   I nzt      = number of cells in the top section
c   I cpat (2,nzt) = coefficients to recover top section alpha
c   I          from surrounding cell pressure corrections
c   I cptgt(2,nzt) = coefficients to recover top section gas temp.
c   I          from surrounding cell pressure corrections
c   I cptft(2,nzt) = coefficients to recover top section liquid temp.
c   I          from surrounding cell pressure corrections
c   I cpzat(2,nzt) = coefficients to recover top section air mass
c   I          fract. from surrounding cell pressure corrections
c   I fat (nzt) = constants to recover top section alpha
c   I ftgt (nzt) = constants to recover top section gas temp.
c   I ftft (nzt) = constants to recover top section liquid temp.
c   I fxat (nzt) = constants to recover top section air mass fract.
c   I dpt (nzt) = top section pressure corrections
c   O pt (nzt) = top section pressure
c   O alpt (nzt) = top section alpha
c   O tgt (nzt) = top section gas temp.
c   O tft (nzt) = top section liquid temp.
c   O xat (nzt) = top section air mass fract.
c   O rogt (nzt) = top section gas density
c   O hgt (nzt) = top section gas enthalpy
c   O roft (nzt) = top section liquid density
c   O hft (nzt) = top section gas density
c
c   ---Middle Section---
c   I nz      = number of axial cells in the middle section
c   I nzp1    = nz + 1
c   I nzp2    = nz + 2
c   I nxmax   = maximum number of x-direction cells in middle section
c   I nchn    = number of channels in middle section
c   I nx(nchn) = number of x-direction cells in a channel
c   I icc(1,nxmax,nchn) = preceding x-direction cell number
c   I icc(2,nxmax,nchn) = succeeding x-direction cell number
c   I cpa (4,nzp2,nxmax,nchn) = coefficients to recover middle section
c   I          alpha from surrounding cell pressure
c   I          corrections
c   I cptg(4,nzp2,nxmax,nchn) = coefficients to recover middle section
c   I          gas temp. from surrounding cell
c   I          pressure corrections
c   I cptf(4,nzp2,nxmax,nchn) = coefficients to recover middle section
c   I          liquid temp. from surrounding cell
c   I          pressure corrections
c   I cpxa(4,nzp2,nxmax,nchn) = coefficients to recover middle section
c   I          air mass fract. from surrounding
c   I          cell pressure corrections
c   I fa (nzp2,nxmax,nchn) = constants to recover middle section
c   I          alpha
c   I ftg (nzp2,nxmax,nchn) = constants to recover middle section
c   I          gas temp.
c   I ftf (nzp2,nxmax,nchn) = constants to recover middle section
c   I          liquid temp.
c   I fxa (nzp2,nxmax,nchn) = constants to recover middle section
c   I          air mass fract.
c   I dp (nzp2,nxmax,nchn) = middle section pressure corrections
c   O p (nzp2,nxmax,nchn) = middle section pressure

```

```

c O alp (nzp2,nxmax,nchn) = middle section alpha
c O tg (nzp2,nxmax,nchn) = middle section gas temp.
c O tf (nzp2,nxmax,nchn) = middle section liquid temp.
c O xa (nzp2,nxmax,nchn) = middle section air mass fract.
c O rog (nzp2,nxmax,nchn) = middle section gas density
c O hg (nzp2,nxmax,nchn) = middle section gas enthalpy
c O rof (nzp2,nxmax,nchn) = middle section liquid density
c O hf (nzp2,nxmax,nchn) = middle section gas density
c
c ---Bottom Section---
c I nzb = number of cells in the bottom section
c I cpab (2,nzb) = coefficients to recover bottom section alpha
c I from surrounding cell pressure corrections
c I cptgb(2,nzb) = coefficients to recover bottom section gas temp.
c I from surrounding cell pressure corrections
c I cptfb(2,nzb) = coefficients to recover bottom section liquid temp.
c I from surrounding cell pressure corrections
c I cpxab(2,nzb) = coefficients to recover bottom section air mass
c I fract. from surrounding cell pressure
c I corrections
c I fab (nzb) = constants to recover bottom section alpha
c I ftgb (nzb) = constants to recover bottom section gas temp.
c I ftfb (nzb) = constants to recover bottom section liquid temp.
c I fxab (nzb) = constants to recover bottom section air mass fract.
c I dpb (nzb) = bottom section pressure corrections
c O pb (nzb) = bottom section pressure
c O alpb (nzb) = bottom section alpha
c O tgb (nzb) = bottom section gas temp.
c O tfb (nzb) = bottom section liquid temp.
c O xab (nzb) = bottom section air mass fract.
c O rogb (nzb) = bottom section gas density
c O hgb (nzb) = bottom section gas enthalpy
c O rofb (nzb) = bottom section liquid density
c O hfb (nzb) = bottom section gas density

```

STORAGE:

```

c
c Top Section - cp_t arrays Middle Section - cp_ arrays
c Bottom Section - cp_b arrays
c Numbering Scheme for Numbering Scheme for
c Top and Bottom Sections Middle Section

```

```

c
c -----
c | 1 |
c |   |
c -----
c | C |
c |   |
c -----
c | 2 |
c |   |
c -----
c
c -----
c | 1 |
c | 3 | C | 4 |
c |   |   |   |
c -----
c | 2 |
c |   |
c -----

```

```

c
c For the bottom cell of the top section and the top cell of
c the bottom section, the extra storage setup for the middle
c section fictitious cells is used to store the coupling
c quantities corresponding to the top and bottom rows of the
c middle section as follows:

```

```

c
c Bottom Cell of Top Section - cp_(2,1,...) locations
c

```

```

c      -----
c      | cp_t(1,nzt) |
c      |             |
c      |             |
c      | f_t(nzt)    |
c      |             |
c      |             |
c      | cp_(2, |   |   |   |
c      | 1,...)|   |   |   |
c      |             |
c      |             |
c      -----
c      Top Cell of Bottom Section - cp_(1,nz+2,...) locations
c      -----
c      | cp_(1, |   |   |   |
c      | nz+2, |   |   |   |
c      | ...) |   |   |   |
c      |             |
c      |             |
c      | f_b(1)      |
c      |             |
c      |             |
c      |             |
c      | cp_b(2,1)   |
c      |             |
c      |             |
c      -----
c      *-----*
c
c      parameter (zero=0.0, one=1.0, two=2.0, four=4.0, ten=10.0)
c      data dtgmax/5.0/, dtfmax/5.0/, dxamax/0.04/
c
c      include 'knobs.inc'
c
c      dimension alpch(3)
c      common /civd/ alpch, delp
c
c      dimension nx(nchn),icc(2,nxmax,nchn)
c
c      TOP SECTION ARRAYS
c
c      dimension cpat (2,nzt), fat (nzt),
c      &          cptgt(2,nzt), ftgt(nzt),
c      &          cptft(2,nzt), ftft(nzt),
c      &          cpxat(2,nzt), fxat(nzt),
c      &          dpt (nzt)
c
c      dimension pt (nzt), rogt(nzt),
c      &          alpt(nzt), hgt (nzt),
c      &          tgt (nzt), roft(nzt),
c      &          tft (nzt), hft (nzt),
c      &          xat (nzt)
c
c      dimension alpbn(nzt),
c      &          bgt(nzt),          cgt(nzt),
c      &          bft(nzt),          cft(nzt),
c      &          advbt(nzt,5), advct(nzt,5)
c
c      MIDDLE SECTION ARRAYS
c
c      dimension cpa (4,nzp2,nxmax,nchn), fa (nzp2,nxmax,nchn),

```

```

c      cptg(4,nzp2,nxmax,nchn), ftg(nzp2,nxmax,nchn),
c      cptf(4,nzp2,nxmax,nchn), ftf(nzp2,nxmax,nchn),
c      cpxa(4,nzp2,nxmax,nchn), fxa(nzp2,nxmax,nchn),
c      dp(nzp2,nxmax,nchn)

c      dimension p(nzp2,nxmax,nchn), rog(nzp2,nxmax,nchn),
c      alp(nzp2,nxmax,nchn), hg(nzp2,nxmax,nchn),
c      tg(nzp2,nxmax,nchn), rof(nzp2,nxmax,nchn),
c      tf(nzp2,nxmax,nchn), hf(nzp2,nxmax,nchn),
c      xa(nzp2,nxmax,nchn)

c      dimension alpn(nzp2,nxmax,nchn),
c      dgx(nzp2,nxmax,nchn), egx(nzp2,nxmax,nchn),
c      dfx(nzp2,nxmax,nchn), efx(nzp2,nxmax,nchn),
c      advdx(nzp2,nxmax,nchn,5), advex(nzp2,nxmax,nchn,5),
c      bgz(nzp3,nxmax,nchn), cgz(nzp3,nxmax,nchn),
c      bfz(nzp3,nxmax,nchn), cfz(nzp3,nxmax,nchn),
c      advbz(nzp3,nxmax,nchn,5), advcz(nzp3,nxmax,nchn,5)

c      BOTTOM SECTION ARRAYS
c
c      dimension cpab(2,nzb), fab(nzb),
c      cptgb(2,nzb), ftgb(nzb),
c      cptfb(2,nzb), ftfb(nzb),
c      cpxab(2,nzb), fxab(nzb),
c      dpb(nzb)

c      dimension pb(nzb), rogb(nzb),
c      alpb(nzb), hgb(nzb),
c      tgb(nzb), rofb(nzb),
c      tfb(nzb), hfb(nzb),
c      xab(nzb)

c      dimension alpbu(nzb),
c      bgb(nzb), cgb(nzb),
c      bfb(nzb), cfb(nzb),
c      advbb(nzb,5), advcb(nzb,5)

c      DERIVATIVE ARRAYS NEEDED BY SUBROUTINE STATE
c
c      parameter (mxnz = 100)
c      dimension drogdp(mxnz), drogdt(mxnz), drgdx(mxnz),
c      dhgdp(mxnz), dhgdt(mxnz), dhgdx(mxnz),
c      drofdp(mxnz), drofdt(mxnz),
c      dhfdp(mxnz), dhfdt(mxnz)

c      PARAMETER VALUES
c
c      data alpo/-0.0001/, alphi/1.0001/, xalo/-0.005/, xahi/1.001/,
c      tglo/270.0/, tghi/705.0/, tflo/270.0/, tfhi/455.0/,
c      epsag/0.0001/, epsaf/0.9999/

c      data ai/0.218/, am/0.431/, ao/0.351/

c      data cin1/+1.0/, cin2/-4.59914/, cin3/+16.47475/, cin4/-27.07490/,
c      cin5/+19.16070/, cin6/+0.0/, cin7/-3.96141/

c      data cmn1/+1.0/, cmn2/+3.01770/, cmn3/-25.83200/, cmn4/+89.93700/,
c      cmn5/-141.1920/, cmn6/+101.4110/, cmn7/-27.3417/

c      data cip1/+1.0/, cip2/-3.685884/, cip3/+8.033505/, cip4/-6.28314/,
c      cip5/+2.57241/, cip6/+0.0/, cip7/-0.636891/

c      data cmp1/+1.0/, cmp2/-5.72188/, cmp3/+29.67630/, cmp4/-53.35180/,

```



```

      4      cmp5/+46.49440/, cmp6/-22.68920/, cmp7/+5.59218/
c
c----- INITIALIZE -----
c
      pi = acos(-one)
      ierr = 0
      errp = zero
      erral = zero
      errtg = zero
      errtf = zero
      errxa = zero
c
c      STUFF FICTITIOUS CELLS ABOVE AND BELOW MIDDLE SECTION
c
      do 11 ic=1,nchn
        do 10 ix=1,nx(ic)
          dp(1,ix,ic) = dpt(nzt)
          dp(nzp2,ix,ic) = dpb(1)
10      continue
11      continue
c
c----- UPDATE P, alpha, Tg, Tf, Xa -----
c
c      TOP CELL OF TOP SECTION
c
      dalp = fat(1)
      dtg = ftgt(1)
      dtf = ftft(1)
      dxa = fxat(1)
c
      if (nzt .eq. 1) go to 109
c
      dalp = dalp - cpat(2,1)*dpt(2)
      dtg = dtg - cptgt(2,1)*dpt(2)
      dtf = dtf - cptft(2,1)*dpt(2)
      dxa = dxa - cpxat(2,1)*dpt(2)
c
      pt(1) = pt(1) + dpt(1)
      alpt(1) = alpt(1) + dalp
      tgt(1) = tgt(1) + sign(min(abs(dtg),dtgmax),dtg)
      tft(1) = tft(1) + sign(min(abs(dtf),dtfmax),dtf)
      xat(1) = xat(1) + sign(min(abs(dxa),dxamax),dxa)
c
      errp = max(errp, abs(dpt(1)))
      erral = max(erral, abs(dalp))
      errtg = max(errtg, abs(dtg))
      errtf = max(errtf, abs(dtf))
      errxa = max(errxa, abs(dxa))
c
c      MIDDLE CELLS OF TOP SECTION
c
      do 100 jz=2,nzt-1
        dalp = fat(jz) - cpat(1,jz)*dpt(jz-1) - cpat(2,jz)*dpt(jz+1)
        dtg = ftgt(jz) - cptgt(1,jz)*dpt(jz-1) - cptgt(2,jz)*dpt(jz+1)
        dtf = ftft(jz) - cptft(1,jz)*dpt(jz-1) - cptft(2,jz)*dpt(jz+1)
        dxa = fxat(jz) - cpxat(1,jz)*dpt(jz-1) - cpxat(2,jz)*dpt(jz+1)
c
        pt(jz) = pt(jz) + dpt(jz)
        alpt(jz) = alpt(jz) + dalp
        tgt(jz) = tgt(jz) + sign(min(abs(dtg),dtgmax),dtg)
        tft(jz) = tft(jz) + sign(min(abs(dtf),dtfmax),dtf)
        xat(jz) = xat(jz) + sign(min(abs(dxa),dxamax),dxa)
c
        errp = max(errp, abs(dpt(jz)))

```

```

        erral = max(erral, abs(dalp  ))
        errtg = max(errtg, abs(dtg   ))
        errtf = max(errtf, abs(dtf   ))
        errxa = max(errxa, abs(dxa   ))
100  continue
c
c  BOTTOM CELL OF TOP SECTION
c
dalp = fat (nzt) - cpat (1,nzt)*dpt(nzt-1)
dtg  = ftgt(nzt) - cptgt(1,nzt)*dpt(nzt-1)
dtf  = ftft(nzt) - cptft(1,nzt)*dpt(nzt-1)
dxa  = fxat(nzt) - cpxat(1,nzt)*dpt(nzt-1)
c
109  continue
c
do 111 ic=1,nchn
do 110 ix=1,nx(ic)
dalp = dalp - cpa (2,1,ix,ic)*dp(2,ix,ic)
dtg  = dtg  - cptg(2,1,ix,ic)*dp(2,ix,ic)
dtf  = dtf  - cptf(2,1,ix,ic)*dp(2,ix,ic)
dxa  = dxa  - cpxa(2,1,ix,ic)*dp(2,ix,ic)
110  continue
111  continue
c
pt (nzt) = pt (nzt) + dpt(nzt)
alpt(nzt) = alpt(nzt) + dalp
tgt (nzt) = tgt (nzt) + sign(min(abs(dtg),dtgmax),dtg)
tft (nzt) = tft (nzt) + sign(min(abs(dtf),dtfmax),dtf)
xat (nzt) = xat (nzt) + sign(min(abs(dxa),dxamax),dxa)
c
errp = max(errp , abs(dpt(nzt)))
erral = max(erral, abs(dalp  ))
errtg = max(errtg, abs(dtg   ))
errtf = max(errtf, abs(dtf   ))
errxa = max(errxa, abs(dxa   ))
c
c  MIDDLE SECTION
c
do 202 ic=1,nchn
do 201 ix=1,nx(ic)
do 200 jz=2,nzpl
ixl = icc(1,ix,ic)
ixr = icc(2,ix,ic)
c
dalp = fa (jz,ix,ic)
6      - cpa (1,jz,ix,ic)*dp(jz-1,ix ,ic)
6      - cpa (2,jz,ix,ic)*dp(jz+1,ix ,ic)
6      - cpa (3,jz,ix,ic)*dp(jz ,ixl,ic)
6      - cpa (4,jz,ix,ic)*dp(jz ,ixr,ic)
dtg  = ftg(jz,ix,ic)
6      - cptg(1,jz,ix,ic)*dp(jz-1,ix ,ic)
6      - cptg(2,jz,ix,ic)*dp(jz+1,ix ,ic)
6      - cptg(3,jz,ix,ic)*dp(jz ,ixl,ic)
6      - cptg(4,jz,ix,ic)*dp(jz ,ixr,ic)
dtf  = ftf(jz,ix,ic)
6      - cptf(1,jz,ix,ic)*dp(jz-1,ix ,ic)
6      - cptf(2,jz,ix,ic)*dp(jz+1,ix ,ic)
6      - cptf(3,jz,ix,ic)*dp(jz ,ixl,ic)
6      - cptf(4,jz,ix,ic)*dp(jz ,ixr,ic)
dxa  = fxa(jz,ix,ic)
6      - cpxa(1,jz,ix,ic)*dp(jz-1,ix ,ic)
6      - cpxa(2,jz,ix,ic)*dp(jz+1,ix ,ic)
6      - cpxa(3,jz,ix,ic)*dp(jz ,ixl,ic)
6      - cpxa(4,jz,ix,ic)*dp(jz ,ixr,ic)

```

```

c
      p (jz,ix,ic) = p (jz,ix,ic) + dp (jz,ix,ic)
      alp(jz,ix,ic) = alp(jz,ix,ic) + dalp
      tg (jz,ix,ic) = tg (jz,ix,ic) + sign(min(abs(dtg),dtgmax),dtg)
      tf (jz,ix,ic) = tf (jz,ix,ic) + sign(min(abs(dtf),dtfmax),dtf)
      xa (jz,ix,ic) = xa (jz,ix,ic) + sign(min(abs(dxa),dxamax),dxa)

c
      errp = max(errp , abs(dp(jz,ix,ic)))
      erral = max(erral, abs(dalp ))
      errtg = max(errtg, abs(dtg ))
      errtf = max(errtf, abs(dtf ))
      errxa = max(errxa, abs(dxa ))

c
200      continue
201      continue
202      continue
c
c      TOP CELL OF BOTTOM SECTION
c
      dalp = fab (1)
      dtg = ftgb(1)
      dtf = ftfb(1)
      dxa = fxab(1)

c
      do 301 ic=1,nchn
        do 300 ix=1,nx(ic)
          dalp = dalp - cpa (1,nzp2,ix,ic)*dp(nzp1,ix,ic)
          dtg = dtg - cptg(1,nzp2,ix,ic)*dp(nzp1,ix,ic)
          dtf = dtf - cptf(1,nzp2,ix,ic)*dp(nzp1,ix,ic)
          dxa = dxa - cpxa(1,nzp2,ix,ic)*dp(nzp1,ix,ic)
300      continue
301      continue
c
      if (nzb .eq. 1) go to 311
c
      dalp = dalp - cpab (2,1)*dpb(2)
      dtg = dtg - cptgb(2,1)*dpb(2)
      dtf = dtf - cptfb(2,1)*dpb(2)
      dxa = dxa - cpxab(2,1)*dpb(2)

c
      pb (1) = pb (1) + dpb(1)
      alpb(1) = alpb(1) + dalp
      tgb (1) = tgb (1) + sign(min(abs(dtg),dtgmax),dtg)
      tfb (1) = tfb (1) + sign(min(abs(dtf),dtfmax),dtf)
      xab (1) = xab (1) + sign(min(abs(dxa),dxamax),dxa)

c
      errp = max(errp , abs(dpb(1)))
      erral = max(erral, abs(dalp ))
      errtg = max(errtg, abs(dtg ))
      errtf = max(errtf, abs(dtf ))
      errxa = max(errxa, abs(dxa ))

c
c      MIDDLE CELLS OF BOTTOM SECTION
c
      do 310 jz=2,nzb-1
        dalp = fab (jz) - cpab (1,jz)*dpb(jz-1) - cpab (2,jz)*dpb(jz+1)
        dtg = ftgb(jz) - cptgb(1,jz)*dpb(jz-1) - cptgb(2,jz)*dpb(jz+1)
        dtf = ftfb(jz) - cptfb(1,jz)*dpb(jz-1) - cptfb(2,jz)*dpb(jz+1)
        dxa = fxab(jz) - cpxab(1,jz)*dpb(jz-1) - cpxab(2,jz)*dpb(jz+1)

c
        pb (jz) = pb (jz) + dpb(jz)
        alpb(jz) = alpb(jz) + dalp
        tgb (jz) = tgb (jz) + sign(min(abs(dtg),dtgmax),dtg)
        tfb (jz) = tfb (jz) + sign(min(abs(dtf),dtfmax),dtf)

```

```

      xab (jz) = xab (jz) + sign(min(abs(dxa),dxamax),dxa)
c
      errp = max(errp , abs(dpb(jz)))
      erral = max(erral, abs(dalp  ))
      errtg = max(errtg, abs(dtg   ))
      errtf = max(errtf, abs(dtf   ))
      errxa = max(errxa, abs(dxa   ))
310 continue
c
c      BOTTOM CELL OF BOTTOM SECTION
c
      dalp = fab (nzb) - cpab (1,nzb)*dpb(nzb-1)
      dtg  = ftgb(nzb) - cptgb(1,nzb)*dpb(nzb-1)
      dtf  = ftfb(nzb) - cptfb(1,nzb)*dpb(nzb-1)
      dxa  = fxab(nzb) - cpxab(1,nzb)*dpb(nzb-1)
c
311 continue
c
      pb (nzb) = pb (nzb) + dpb(nzb)
      alpb(nzb) = alpb(nzb) + dalp
      tgb (nzb) = tgb (nzb) + sign(min(abs(dtg),dtgmax),dtg)
      tfb (nzb) = tfb (nzb) + sign(min(abs(dtf),dtfmax),dtf)
      xab (nzb) = xab (nzb) + sign(min(abs(dxa),dxamax),dxa)
c
      errp = max(errp , abs(dpb(nzb)))
      erral = max(erral, abs(dalp  ))
      errtg = max(errtg, abs(dtg   ))
      errtf = max(errtf, abs(dtf   ))
      errxa = max(errxa, abs(dxa   ))
c
c----- CHECK FOR alp OUTSIDE [0,1]; MAKE CORRECTIONS AS NEEDED -----
c
      do 350 ic=1,nchn
      do 350 ix=1,nx(ic)
         p(1 ,ix,ic) = pt(nzt)
         p(nzp2,ix,ic) = pb(1)
350 continue
c
c      TOP SECTION
c
      do 410 jz=1,nzt
         if (alpt(jz) .ge. zero .and. alpt(jz) .le. one) then
            continue
         else if (alpt(jz) .lt. zero) then
            if (alpt(jz) .gt. alplo) then
               alpt(jz) = zero
            else
               ierr = 1
               write(*,901) jz
            end if
         end if
c
         if (alptn(jz) .lt. epsag) then
            if (jz .eq. 1) then
               ugm = bgt(jz) + cgt(jz)*(ppl - pt(jz))
            else
               ugm = bgt(jz) + cgt(jz)*(pt(jz-1) - pt(jz))
            end if
            if (ugm .lt. zero) then
               advbt(jz,1) = zero
               advct(jz,1) = zero
               advbt(jz,3) = zero
               advct(jz,3) = zero
               advbt(jz,5) = zero
               advct(jz,5) = zero

```

```

        end if
c
        if (jz .eq. nzt) then
            do 405 ic=1,nchn
            do 405 ix=1,nx(ic)
                ugp = bgz(2,ix,ic)
                    + cgz(2,ix,ic)*(pt(nzt) - p(2,ix,ic))
                if (ugp .gt. zero) then
                    advbz(2,ix,ic,1) = zero
                    advcz(2,ix,ic,1) = zero
                    advbz(2,ix,ic,3) = zero
                    advcz(2,ix,ic,3) = zero
                    advbz(2,ix,ic,5) = zero
                    advcz(2,ix,ic,5) = zero
                end if
            end if
405        continue
        else
            ugp = bgt(jz+1) + cgt(jz+1)*(pt(jz) - pt(jz+1))
            if (ugp .gt. zero) then
                advbt(jz+1,1) = zero
                advct(jz+1,1) = zero
                advbt(jz+1,3) = zero
                advct(jz+1,3) = zero
                advbt(jz+1,5) = zero
                advct(jz+1,5) = zero
            end if
        end if
    end if
else
    if (alpt(jz) .lt. alphi) then
        alpt(jz) = one
    else
        ierr = 1
        write(*,901) jz
    end if
c
    if (alptn(jz) .gt. epsaf) then
        if (jz .eq. 1) then
            ufm = bft(jz) + cft(jz)*(ppl - pt(jz))
        else
            ufm = bft(jz) + cft(jz)*(pt(jz-1) - pt(jz))
        end if
        if (ufm .lt. zero) then
            advbt(jz,2) = zero
            advct(jz,2) = zero
            advbt(jz,4) = zero
            advct(jz,4) = zero
        end if
c
        if (jz .eq. nzt) then
            do 406 ic=1,nchn
            do 406 ix=1,nx(ic)
                ufp = bfz(2,ix,ic)
                    + cfz(2,ix,ic)*(pt(nzt) - p(2,ix,ic))
                if (ufp .gt. zero) then
                    advbz(2,ix,ic,2) = zero
                    advcz(2,ix,ic,2) = zero
                    advbz(2,ix,ic,4) = zero
                    advcz(2,ix,ic,4) = zero
                end if
            end if
406        continue
        else
            ufp = bft(jz+1) + cft(jz+1)*(pt(jz) - pt(jz+1))
            if (ufp .gt. zero) then

```

```
        advbt(jz+1,2) = zero
        advct(jz+1,2) = zero
        advbt(jz+1,4) = zero
        advct(jz+1,4) = zero
      end if
    end if
  end if
end if
410 continue
c
c MIDDLE SECTION
c
do 422 ic=1,nchn
  do 421 ix=1,nx(ic)
    do 420 jz=2,nzpl
      if (alp(jz,ix,ic) .ge. zero .and.
        & alp(jz,ix,ic) .le. one ) then
        continue
      else if (alp(jz,ix,ic) .lt. zero) then
        if (alp(jz,ix,ic) .gt. alplo) then
          alp(jz,ix,ic) = zero
        else
          ierr = 1
          write(*,903) jz,ix,ic
        end if
        if (alpn(jz,ix,ic) .lt. epsag) then
          ugm = bgz(jz,ix,ic)
          & + cgz(jz,ix,ic)*(p(jz-1,ix,ic) - p(jz,ix,ic))
          if (ugm .lt. zero) then
            advbz(jz,ix,ic,1) = zero
            advcz(jz,ix,ic,1) = zero
            advbz(jz,ix,ic,3) = zero
            advcz(jz,ix,ic,3) = zero
            advbz(jz,ix,ic,5) = zero
            advcz(jz,ix,ic,5) = zero
          end if
          ugp = bgz(jz+1,ix,ic)
          & + cgz(jz+1,ix,ic)*(p(jz,ix,ic) - p(jz+1,ix,ic))
          if (ugp .gt. zero) then
            advbz(jz+1,ix,ic,1) = zero
            advcz(jz+1,ix,ic,1) = zero
            advbz(jz+1,ix,ic,3) = zero
            advcz(jz+1,ix,ic,3) = zero
            advbz(jz+1,ix,ic,5) = zero
            advcz(jz+1,ix,ic,5) = zero
          end if
          ixl = icc(1,ix,ic)
          wgm = dgx(jz,ix,ic)
          & + egx(jz,ix,ic)*(p(jz,ixl,ic) - p(jz,ix,ic))
          if (wgm .lt. zero) then
            advdx(jz,ix,ic,1) = zero
            advex(jz,ix,ic,1) = zero
            advdx(jz,ix,ic,3) = zero
            advex(jz,ix,ic,3) = zero
            advdx(jz,ix,ic,5) = zero
            advex(jz,ix,ic,5) = zero
          end if
          ixr = icc(2,ix,ic)
          wgp = dgx(jz,ixr,ic)
          & + egx(jz,ixr,ic)*(p(jz,ix,ic) - p(jz,ixr,ic))
          if (wgp .gt. zero) then
            advdx(jz,ixr,ic,1) = zero
            advex(jz,ixr,ic,1) = zero
            advdx(jz,ixr,ic,3) = zero
```

```

        advex(jz,ixr,ic,3) = zero
        advdx(jz,ixr,ic,5) = zero
        advex(jz,ixr,ic,5) = zero
    end if
end if
else
    if (alp(jz,ix,ic) .lt. alphi) then
        alp(jz,ix,ic) = one
    else
        ierr = 1
        write(*,903) jz,ix,ic
    end if
    if (alpn(jz,ix,ic) .gt. epsaf) then
        ufm = bfz(jz,ix,ic)
        + cfz(jz,ix,ic)*(p(jz-1,ix,ic) - p(jz,ix,ic))
        if (ufm .lt. zero) then
            advbz(jz,ix,ic,2) = zero
            advcz(jz,ix,ic,2) = zero
            advbz(jz,ix,ic,4) = zero
            advcz(jz,ix,ic,4) = zero
        end if
        ufp = bfz(jz+1,ix,ic)
        + cfz(jz+1,ix,ic)*(p(jz,ix,ic) - p(jz+1,ix,ic))
        if (ufp .gt. zero) then
            advbz(jz+1,ix,ic,2) = zero
            advcz(jz+1,ix,ic,2) = zero
            advbz(jz+1,ix,ic,4) = zero
            advcz(jz+1,ix,ic,4) = zero
        end if
        ixl = icc(1,ix,ic)
        wfm = dfx(jz,ix,ic)
        + efx(jz,ix,ic)*(p(jz,ixl,ic) - p(jz,ix,ic))
        if (wfm .lt. zero) then
            advdx(jz,ix,ic,2) = zero
            advex(jz,ix,ic,2) = zero
            advdx(jz,ix,ic,4) = zero
            advex(jz,ix,ic,4) = zero
        end if
        ixr = icc(2,ix,ic)
        wfp = dfx(jz,ixr,ic)
        + efx(jz,ixr,ic)*(p(jz,ix,ic) - p(jz,ixr,ic))
        if (wfp .gt. zero) then
            advdx(jz,ixr,ic,2) = zero
            advex(jz,ixr,ic,2) = zero
            advdx(jz,ixr,ic,4) = zero
            advex(jz,ixr,ic,4) = zero
        end if
    end if
end if
420 continue
421 continue
422 continue
c
c BOTTOM SECTION
c
do 430 jz=1,nzb
    if (alpb(jz) .ge. zero .and. alpb(jz) .le. one ) then
        continue
    else if (alpb(jz) .lt. zero) then
        if (alpb(jz) .gt. alplo) then
            alpb(jz) = zero
        else
            ierr = 1
            write(*,905) jz
        end if
    end if
end do

```

```
end if

c
if (alpb(jz) .lt. epsag) then
  if (jz .eq. 1) then
    do 425 ic=1,nchn
      do 425 ix=1,nx(ic)
        ugm = bgz(nzp2,ix,ic)
          + cgz(nzp2,ix,ic)*(p(nzp1,ix,ic) - pb(1))
        if (ugm .lt. zero) then
          advbz(nzp2,ix,ic,1) = zero
          advcz(nzp2,ix,ic,1) = zero
          advbz(nzp2,ix,ic,3) = zero
          advcz(nzp2,ix,ic,3) = zero
          advbz(nzp2,ix,ic,5) = zero
          advcz(nzp2,ix,ic,5) = zero
        end if
      end if
    continue
  else
    ugm = bgb(jz-1) + cgb(jz-1)*(pb(jz-1) - pb(jz))
    if (ugm .lt. zero) then
      advbb(jz-1,1) = zero
      advcb(jz-1,1) = zero
      advbb(jz-1,3) = zero
      advcb(jz-1,3) = zero
      advbb(jz-1,5) = zero
      advcb(jz-1,5) = zero
    end if
  end if

c
  if (jz .eq. nzb) then
    ugp = bgb(jz) + cgb(jz)*(pb(jz) - ptb)
  else
    ugp = bgb(jz) + cgb(jz)*(pb(jz) - pb(jz+1))
  end if
  if (ugp .gt. zero) then
    advbb(jz,1) = zero
    advcb(jz,1) = zero
    advbb(jz,3) = zero
    advcb(jz,3) = zero
    advbb(jz,5) = zero
    advcb(jz,5) = zero
  end if
end if
else
  if (alpb(jz) .lt. alphi) then
    alpb(jz) = one
  else
    ierr = 1
    write(*,905) jz
  end if

c
  if (alpb(jz) .gt. epsaf) then
    if (jz .eq. 1) then
      do 426 ic=1,nchn
        do 426 ix=1,nx(ic)
          ufm = bfz(nzp2,ix,ic)
            + cfz(nzp2,ix,ic)*(p(nzp1,ix,ic) - pb(1))
          if (ufm .lt. zero) then
            advbz(nzp2,ix,ic,2) = zero
            advcz(nzp2,ix,ic,2) = zero
            advbz(nzp2,ix,ic,4) = zero
            advcz(nzp2,ix,ic,4) = zero
          end if
        end if
      continue
    end if
  end if
end if
```

426


```

        else
            ufm = bfb(jz-1) + cfb(jz-1)*(pb(jz-1) - pb(jz))
            if (ufm .lt. zero) then
                advbb(jz-1,2) = zero
                advcb(jz-1,2) = zero
                advbb(jz-1,4) = zero
                advcb(jz-1,4) = zero
            end if
        end if
c
        if (jz .eq. nzb) then
            ufp = bfb(jz) + cfb(jz)*(pb(jz) - ptb      )
        else
            ufp = bfb(jz) + cfb(jz)*(pb(jz) - pb(jz+1))
        end if
        if (ufp .gt. zero) then
            advbb(jz,2) = zero
            advcb(jz,2) = zero
            advbb(jz,4) = zero
            advcb(jz,4) = zero
        end if
    end if
end if
430 continue
c
    if (ierr .eq. 1) return
c
c---- CHECK FOR Xa OUTSIDE [0,1]; MAKE CORRECTIONS AS NEEDED -----
c    CHECK FOR Tg and Tf OUTSIDE [270K, 705K]; CORRECT AS NEEDED
c
c
c    TOP SECTION
c
do 500 jz=1,nzt
    if      (xat(jz) .ge. zero .and. xat(jz) .le. one ) then
        continue
    else if (xat(jz) .lt. zero .and. xat(jz) .gt. xalo) then
        xat(jz) = zero
    else if (xat(jz) .gt. one .and. xat(jz) .lt. xahi) then
        xat(jz) = one
    else if (xat(jz) .le. xalo) then
        xat(jz) = zero
        errxa = one
c    write(*,900) jz
        if (alptn(jz) .lt. epsag) then
            if (jz .eq. 1) then
                ugm = bgt(jz) + cgt(jz)*(ppl      - pt(jz))
            else
                ugm = bgt(jz) + cgt(jz)*(pt(jz-1) - pt(jz))
            end if
            if (ugm .lt. zero) then
                advbt(jz,5) = zero
                advct(jz,5) = zero
            end if
c
            if (jz .eq. nzt) then
                do 495 ic=1,nchn
                do 495 ix=1,nx(ic)
                    ugp = bgz(2,ix,ic)
                    + cgz(2,ix,ic)*(pt(nzt) - p(2,ix,ic))
                    if (ugp .gt. zero) then
                        advbz(2,ix,ic,5) = zero
                        advcz(2,ix,ic,5) = zero
                    end if
                end if
            end if
        end if
    end if
end do

```

```
495         continue
           else
             ugp = bgt(jz+1) + cgt(jz+1)*(pt(jz) - pt(jz+1))
             if (ugp .gt. zero) then
               advbt(jz+1,5) = zero
               advct(jz+1,5) = zero
             end if
           end if
         end if
       else
         xat(jz) = one
         errxa = one
         write(*,900) jz
       end if
     c
     c
     if      (tgt(jz) .lt. tglo) then
       tgt(jz) = tglo
       errtg = ten
     else if (tgt(jz) .le. tghi) then
       continue
     else
       tgt(jz) = tghi
       errtg = ten
     end if
   c
   if      (tft(jz) .lt. tflo) then
     tft(jz) = tflo
     errtf = ten
   else if (tft(jz) .le. tfhi) then
     continue
   else
     tft(jz) = tfhi
     errtf = ten
   end if
500 continue
c
c MIDDLE SECTION
c
do 512 ic=1,nchn
do 511 ix=1,nx(ic)
do 510 jz=2,nzpl
  if      (xa(jz,ix,ic) .ge. zero .and.
&         xa(jz,ix,ic) .le. one ) then
    continue
  else if (xa(jz,ix,ic) .lt. zero .and.
&         xa(jz,ix,ic) .gt. xalo) then
    xa(jz,ix,ic) = zero
  else if (xa(jz,ix,ic) .gt. one .and.
&         xa(jz,ix,ic) .lt. xahi) then
    xa(jz,ix,ic) = one
  else if (xa(jz,ix,ic) .le. xalo) then
    xa(jz,ix,ic) = zero
    errxa = one
  write(*,902) jz,ix,ic
  if (alpn(jz,ix,ic) .lt. epsag) then
    ugm = bgz(jz,ix,ic)
    + cgz(jz,ix,ic)*(p(jz-1,ix,ic) - p(jz,ix,ic))
    if (ugm .lt. zero) then
      advbz(jz,ix,ic,5) = zero
      advcz(jz,ix,ic,5) = zero
    end if
    ugp = bgz(jz+1,ix,ic)
    + cgz(jz+1,ix,ic)*(p(jz,ix,ic) - p(jz+1,ix,ic))
    if (ugp .gt. zero) then
```

```

        advbz(jz+1,ix,ic,5) = zero
        advcz(jz+1,ix,ic,5) = zero
    end if
    ixl = icc(1,ix,ic)
    wgm = dgx(jz,ix,ic)
    + egx(jz,ix,ic)*(p(jz,ixl,ic) - p(jz,ix,ic))
    if (wgm .lt. zero) then
        advdx(jz,ix,ic,5) = zero
        advex(jz,ix,ic,5) = zero
    end if
    ixr = icc(2,ix,ic)
    wgp = dgx(jz,ixr,ic)
    + egx(jz,ixr,ic)*(p(jz,ix,ic) - p(jz,ixr,ic))
    if (wgp .gt. zero) then
        advdx(jz,ixr,ic,5) = zero
        advex(jz,ixr,ic,5) = zero
    end if
    end if
else
    xa(jz,ix,ic) = one
    errxa = one
    write(*,902) jz,ix,ic
end if
c
c
    if (tg(jz,ix,ic) .lt. tglo) then
        tg(jz,ix,ic) = tglo
        errtg = ten
    else if (tg(jz,ix,ic) .le. tghi) then
        continue
    else
        tg(jz,ix,ic) = tghi
        errtg = ten
    end if
c
c
    if (tf(jz,ix,ic) .lt. tflo) then
        tf(jz,ix,ic) = tflo
        errtf = ten
    else if (tf(jz,ix,ic) .le. tfhi) then
        continue
    else
        tf(jz,ix,ic) = tfhi
        errtf = ten
    end if
510    continue
511    continue
512    continue
c
c    BOTTOM SECTION
c
do 520 jz=1,nzb
    if (xab(jz) .ge. zero .and. xab(jz) .le. one ) then
        continue
    else if (xab(jz) .lt. zero .and. xab(jz) .gt. xalo) then
        xab(jz) = zero
    else if (xab(jz) .gt. one .and. xab(jz) .lt. xahi) then
        xab(jz) = one
    else if (xab(jz) .le. xalo) then
        xab(jz) = zero
        errxa = one
        write(*,904) jz
    if (alpbn(jz) .lt. epsag) then
        if (jz .eq. 1) then
            do 515 ic=1,nchn
            do 515 ix=1,nx(ic)

```

```

        ugm = bgz(nzp2,ix,ic)
        + cgz(nzp2,ix,ic)*(p(nzp1,ix,ic) - pb(1))
        if (ugm .lt. zero) then
            advbz(nzp2,ix,ic,5) = zero
            advcz(nzp2,ix,ic,5) = zero
        end if
515      continue
    else
        ugm = bgb(jz-1) + cgb(jz-1)*(pb(jz-1) - pb(jz))
        if (ugm .lt. zero) then
            advbb(jz-1,5) = zero
            advcb(jz-1,5) = zero
        end if
    end if
c
    if (jz .eq. nzb) then
        ugp = bgb(jz) + cgb(jz)*(pb(jz) - ptb )
    else
        ugp = bgb(jz) + cgb(jz)*(pb(jz) - pb(jz+1))
    end if
    if (ugp .gt. zero) then
        advbb(jz,5) = zero
        advcb(jz,5) = zero
    end if
    end if
else
    xab(jz) = one
    errxa = one
c    write(*,904) jz
end if
c
    if (tgb(jz) .lt. tglo) then
        tgb(jz) = tglo
        errtg = ten
    else if (tgb(jz) .le. tghi) then
        continue
    else
        tgb(jz) = tghi
        errtg = ten
    end if
c
    if (tfb(jz) .lt. tflo) then
        tfb(jz) = tflo
        errtf = ten
    else if (tfb(jz) .le. tfhi) then
        continue
    else
        tfb(jz) = tfhi
        errtf = ten
    end if
520  continue
c
    if (ierr .eq. 1) return
c
c---- UPDATE rhog, hg, rhof, hf BASED ON ABOVE P, Tg, Tf, Xa -----
c
c
c    TOP SECTION
c
    call state(pt,tgt,tft,xat,factor,ilq,
        1,nzt,nzt,1,1,1,1,
        rogt,drogdp,drogdt,drqdx,
        hgt ,dhgdp, dhgdt, dhqdx,
        roft,drofdp,drofdt,

```

```

      6      hft ,dhfdp, dhfdt)
c
c      MIDDLE SECTION
c
      do 602 ic=1,nchn
      do 601 ix=1,nx(ic)
      call state(p,tg,tf,xa,factor,ilq,
      6      2,nzp1,nzp2,nxmax,nchn,ix,ic,
      6      rog,drogdp,drogdt,drqdx,
      6      hg ,dhgdp, dhgdt, dhgdx,
      6      rof,drofdp,drofdt,
      6      hf ,dhfdp, dhfdt)
601      continue
602      continue
c
c      BOTTOM SECTION
c
      call state(pb,tgb,tfb,xab,factor,ilq,
      6      1,nzb,nzb,1,1,1,1,
      6      rogb,drogdp,drogdt,drqdx,
      6      hgb ,dhgdp, dhgdt, dhgdx,
      6      rofb,drofdp,drofdt,
      6      hfb ,dhfdp, dhfdt)
c
c----- COMPUTE CHANNEL INLET VOID FRACTIONS -----
c
      if (nchn .eq. 3) then
c
      pchn = zero
      do 690 ic=1,3
      do 690 ix=1,nx(ic)
      pchn = pchn + p(2,ix,ic)
690      continue
      pchn = pchn/(nx(1) + nx(2) + nx(3))
      delp = pt(nzt) - pchn
c
      avg = alpt(nzt)
c
      if (delp .le. delp1) then
c
      alpi = (cin1 + (cin2 + (cin3 + (cin4 + (cin5
      6      + (cin6 + cin7*avg)*avg)*avg)*avg)*avg)*avg
      6      + four*avg*(one - avg)*sigai
      alpm = (cmn1 + (cmn2 + (cmn3 + (cmn4 + (cmn5
      6      + (cmn6 + cmn7*avg)*avg)*avg)*avg)*avg)*avg
      6      + four*avg*(one - avg)*sigam
c
      else if (delp .le. delp2) then
c
      alpin = (cin1 + (cin2 + (cin3 + (cin4 + (cin5
      6      + (cin6 + cin7*avg)*avg)*avg)*avg)*avg)*avg
      6      + four*avg*(one - avg)*sigai
      alpmn = (cmn1 + (cmn2 + (cmn3 + (cmn4 + (cmn5
      6      + (cmn6 + cmn7*avg)*avg)*avg)*avg)*avg)*avg
      6      + four*avg*(one - avg)*sigam
c
      alpip = (cip1 + (cip2 + (cip3 + (cip4 + (cip5
      6      + (cip6 + cip7*avg)*avg)*avg)*avg)*avg)*avg
      6      + four*avg*(one - avg)*sigfi
      alpmp = (cmp1 + (cmp2 + (cmp3 + (cmp4 + (cmp5
      6      + (cmp6 + cmp7*avg)*avg)*avg)*avg)*avg)*avg
      6      + four*avg*(one - avg)*sigfm
c
      wt = one - (delp - delp1)/(delp2 - delp1)

```

```

      alpi = wt*alpin + (one - wt)*alpip
      alpm = wt*alpmn + (one - wt)*alpmp
c
      else
c
      alpi = (cip1 + (cip2 + (cip3 + (cip4 + (cip5
&      + (cip6 + cip7*avg)*avg)*avg)*avg)*avg)*avg
&      + four*avg*(one - avg)*sigfi
      alpm = (cmp1 + (cmp2 + (cmp3 + (cmp4 + (cmp5
&      + (cmp6 + cmp7*avg)*avg)*avg)*avg)*avg)*avg
&      + four*avg*(one - avg)*sigfm
c
      end if
c
      alpch(3) = (avg - ai*alpi - am*alpm)/ao
c
      alpch(1) = max(min(alpi,      one), zero)
      alpch(2) = max(min(alpm,      one), zero)
      alpch(3) = max(min(alpch(3), one), zero)
      dalmax = min(alpch(1), (one - alpch(1)),
&      alpch(2), (one - alpch(2)),
&      alpch(3), (one - alpch(3)), dalsub)
c
      else if (nchn .eq. 1) then
c
      alpch(1) = max(min(alpt(nzt), one), zero)
      dalmax = min(alpch(1), (one - alpch(1)), dalsub)
c
      end if
c
c----- STUFF FICTITIOUS CELLS ABOVE AND BELOW MIDDLE SECTION -----
c
      do 701 ic=1,nchn
      do 700 ix=1,nx(ic)
      p (1,ix,ic) = pt (nzt)
      if (nchn .eq. 3) then
      theta = (float(ix) - one)*pi/two
      if (ic .ne. 2) theta = theta + pi/four
      alp(1,ix,ic) = alpch(ic) + dalmax*cos(theta-theta0)
      else if (nchn .eq. 1) then
      theta = (float(ix) - one)*pi/two + pi/four
      alp(1,ix,ic) = alpch(1) + dalmax*cos(theta-theta0)
      else
      alp(1,ix,ic) = alpt(nzt)
      end if
      tg (1,ix,ic) = tgt (nzt)
      tf (1,ix,ic) = tft (nzt)
      xa (1,ix,ic) = xat (nzt)
      rog(1,ix,ic) = rogt(nzt)
      hg (1,ix,ic) = hgt (nzt)
      rof(1,ix,ic) = roft(nzt)
      hf (1,ix,ic) = hft (nzt)
c
      p (nzp2,ix,ic) = pb (1)
      alp(nzp2,ix,ic) = alpb(1)
      tg (nzp2,ix,ic) = tgb (1)
      tf (nzp2,ix,ic) = tfb (1)
      xa (nzp2,ix,ic) = xab (1)
      rog(nzp2,ix,ic) = rogb(1)
      hg (nzp2,ix,ic) = hgb (1)
      rof(nzp2,ix,ic) = rofb(1)
      hf (nzp2,ix,ic) = hfb (1)
700      continue
701      continue

```

```

C----- FORMATS -----
C
900  format(/, ' Time step reduction requested by updatp',/,
      &      ' for top section cell jz = ', i3,
      &      ' xa out of acceptable range')
901  format(/, ' Time step reduction requested by updatp',/,
      &      ' for top section cell jz = ', i3,
      &      ' alpha out of acceptable range')
902  format(/, ' Time step reduction requested by updatp',/,
      &      ' for middle section cell ',
      &      ' jz = ', i3, ' ix = ', i3, ' ic = ', i3,
      &      ' xa out of acceptable range')
903  format(/, ' Time step reduction requested by updatp',/,
      &      ' for middle section cell ',
      &      ' jz = ', i3, ' ix = ', i3, ' ic = ', i3,
      &      ' alpha out of acceptable range')
904  format(/, ' Time step reduction requested by updatp',/,
      &      ' for bottom section cell jz = ', i3,
      &      ' xa out of acceptable range')
905  format(/, ' Time step reduction requested by updatp',/,
      &      ' for bottom section cell jz = ', i3,
      &      ' alpha out of acceptable range')

C
      return
      end

```

UPDATV

```

      subroutine updatv(bgt,bft,cgt,cft,pt,ugt,uft,
      6          bgz,bfz,cgz,cfz,p ,ugz,ufz,
      6          dgx,dfx,egx,efx,  wgx,wfx,
      6          bgb,bfb,cgb,cfb,pb,ugb,ufb,
      6          ppl,ptb,
      6          nzt,nzpl,nzp2,nzp3,nxmax,nchn,nx,icc,nzb)
c-----*-----*-----*-----*-----*-----*-----*-----*-----*
c
c  DESCRIPTION:
c  Subroutine updatv computes velocity values over the entire grid
c  at the end of a time step. Subroutine explict supplies the
c  coefficients and subroutine updatp supplies the pressure values.
c
c
c          n          n
c  u      = B      + C      (P - P )
c    g,j+1/2    g,j+1/2    g,j+1/2    j+1
c
c          n          n
c  w      = D      + E      (P - P )
c    g,i+1/2    g,i+1/2    g,i+1/2    i+1
c
c  GLOSSARY:  I=input, O=output
c
c ---General---
c I ppl = top boundary (plenum) pressure
c I ptb = bottom boundary (tank bottom) pressure
c
c ---Top Section---
c I nzt      = number of u-velocity faces (and cells)
c I          in the top section
c I bgt(nzt) = constant in explicit u-gas velocity equation
c I          for top section
c I cgt(nzt) = pressure term coefficient in explicit u-gas
c I          velocity equation for top section
c I bft(nzt) = constant in explicit u-liquid velocity equation
c I          for top section

```

```
c I cft(nzt) = pressure term coefficient in explicit u-liquid
c I          velocity equation for top section
c I pt (nzt) = pressure in top section
c O ugt(nzt) = u-gas velocity in top section
c O uft(nzt) = u-fluid velocity in top section
c
c ---Middle Section---
c I nz      = number of axial cells in the middle section
c I nzp1    = nz + 1
c I nzp2    = nz + 2
c I nzp3    = nz + 3
c I nxmax   = maximum number of x-direction cells in middle section
c I nchn    = number of channels in middle section
c I nx(nchn) = number of x-direction cells in a channel
c I icc(1,nxmax,nchn) = preceding x-direction cell number
c I icc(2,nxmax,nchn) = succeeding x-direction cell number
c I bgz(nzp3,nxmax,nchn) = constant in explicit u-gas velocity
c I          equation for middle section
c I cgz(nzp3,nxmax,nchn) = pressure term coefficient in explicit u-gas
c I          velocity equation for middle section
c I bfz(nzp3,nxmax,nchn) = constant in explicit u-fluid velocity
c I          equation for middle section
c I cfz(nzp3,nxmax,nchn) = pressure term coefficient in explicit u-fluid
c I          velocity equation for middle section
c I p (nzp3,nxmax,nchn) = pressure in middle section
c I dgx(nzp2,nxmax,nchn) = constant in explicit w-gas velocity
c I          equation for middle section
c I egx(nzp2,nxmax,nchn) = pressure term coefficient in explicit w-gas
c I          velocity equation for middle section
c I dfx(nzp2,nxmax,nchn) = constant in explicit w-fluid velocity
c I          equation for middle section
c I efx(nzp2,nxmax,nchn) = pressure term coefficient in explicit w-fluid
c I          velocity equation for middle section
c O ugz(nzp3,nxmax,nchn) = u-gas velocity in middle section
c O ufz(nzp3,nxmax,nchn) = u-fluid velocity in middle section
c O wgx(nzp2,nxmax,nchn) = w-gas velocity in middle section
c O wfx(nzp2,nxmax,nchn) = w-fluid velocity in middle section
c
c ---Bottom Section---
c I nzb     = number of u-velocity faces (and cells)
c I          in the bottom section
c I bgb(nzb) = constant in explicit u-gas velocity equation
c I          for bottom section
c I cgb(nzb) = pressure term coefficient in explicit u-gas
c I          velocity equation for bottom section
c I bfb(nzb) = constant in explicit u-liquid velocity equation
c I          for bottom section
c I cfb(nzb) = pressure term coefficient in explicit u-liquid
c I          velocity equation for bottom section
c I pb (nzb) = pressure in bottom section
c O ugb(nzb) = u-gas velocity in bottom section
c O ufb(nzb) = u-fluid velocity in bottom section
c
c-----*-----*-----*-----*-----*-----*-----*
c
c      dimension nx(nchn),icc(2,nxmax,nchn)
c
c      TOP SECTION ARRAYS
c
c      dimension bgt(nzt), cgt(nzt),
c      6      bft(nzt), cft(nzt),
c      6      ugt(nzt), uft(nzt),
c      6      pt(nzt)
c
```



```

c      MIDDLE SECTION ARRAYS
c
c      dimension bgz(nzp3,nxmax,nchn), cgz(nzp3,nxmax,nchn),
c      &          bfg(nzp3,nxmax,nchn), cfz(nzp3,nxmax,nchn),
c      &          ugz(nzp3,nxmax,nchn), ufz(nzp3,nxmax,nchn)
c
c      dimension dgx(nzp2,nxmax,nchn), egx(nzp2,nxmax,nchn),
c      &          dfx(nzp2,nxmax,nchn), efx(nzp2,nxmax,nchn),
c      &          wgx(nzp2,nxmax,nchn), wfx(nzp2,nxmax,nchn),
c      &          p(nzp2,nxmax,nchn)
c
c      BOTTOM SECTION ARRAYS
c
c      dimension bgb(nzb), cgb(nzb),
c      &          bfb(nzb), cfb(nzb),
c      &          ugb(nzb), ufb(nzb),
c      &          pb(nzb)
c
c----- UPDATE VELOCITIES -----
c
c      TOP SECTION:
c      FACE 1
c
c      ugt(1) = bgt(1) + cgt(1)*(ppl - pt(1))
c      uft(1) = bft(1) + cft(1)*(ppl - pt(1))
c
c      FACES 2 --> nzt
c
c      do 100 jz=2,nzt
c          ugt(jz) = bgt(jz) + cgt(jz)*(pt(jz-1) - pt(jz))
c          uft(jz) = bft(jz) + cft(jz)*(pt(jz-1) - pt(jz))
100  continue
c
c      MIDDLE SECTION:
c      u VELOCITIES
c
c      do 202 jz=2,nzp2
c          do 201 ic=1,nchn
c              do 200 ix=1,nx(ic)
c                  ugz(jz,ix,ic) = bgz(jz,ix,ic)
c                  &          + cgz(jz,ix,ic)*(p(jz-1,ix,ic) - p(jz,ix,ic))
c                  ufz(jz,ix,ic) = bfg(jz,ix,ic)
c                  &          + cfz(jz,ix,ic)*(p(jz-1,ix,ic) - p(jz,ix,ic))
200  continue
201  continue
202  continue
c
c      w VELOCITIES
c
c      do 212 jz=2,nzp1
c          do 211 ic=1,nchn
c              do 210 ix=1,nx(ic)
c                  ixl = icc(1,ix,ic)
c                  ixr = ix
c                  wgx(jz,ix,ic) = dgx(jz,ix,ic)
c                  &          + egx(jz,ix,ic)*(p(jz,ixl,ic) - p(jz,ixr,ic))
c                  wfx(jz,ix,ic) = dfx(jz,ix,ic)
c                  &          + efx(jz,ix,ic)*(p(jz,ixl,ic) - p(jz,ixr,ic))
210  continue
211  continue
212  continue
c
c      BOTTOM SECTION:
c      FACES 1 --> nzb-1

```

```

c
  do 300 jz=1,nzb-1
    ugb(jz) = bgb(jz) + cgb(jz)*(pb(jz) - pb(jz+1))
    ufb(jz) = bfb(jz) + cfb(jz)*(pb(jz) - pb(jz+1))
300  continue
c
c  FACE nzb
c
  ugb(nzb) = bgb(nzb) + cgb(nzb)*(pb(nzb) - ptb)
  ufb(nzb) = bfb(nzb) + cfb(nzb)*(pb(nzb) - ptb)
c
c  STUFF FICTITIOUS CELL AXIAL VELOCITIES
c
  do 401 ic=1,nchn
    do 400 ix=1,nx(ic)
      ugz(1,ix,ic) = ugt(nzt)
      ufz(1,ix,ic) = uft(nzt)
      ugz(nzp3,ix,ic) = ugb(1)
      ufz(nzp3,ix,ic) = ufb(1)
400  continue
401  continue
c
  return
end

```

VISGS

```

      subroutine visgs(p,t,xa,l,visg)
c
c  *****
c  *
c  *  INPUT:
c  *      p = MIXTURE PRESSURE IN Pa
c  *      t = TEMPERATURE IN K
c  *      xa = MASS FRACTION OF AIR
c  *      l = IDENTIFIER (l=1 FOR H2O, l=2 FOR D2O)
c  *
c  *  OUTPUT:
c  *      visg = DYNAMIC VISCOSITY OF AIR-STEAM GAS MIXTURE IN Pa-s
c  *
c  *  RANGE:
c  *      275K < t < 700K
c  *      0 < xa < 1
c  *      p < 1MPa
c  *
c  *****
c
c  parameter (one=1.0, tconv=273.15)
c  dimension rs(2), cs1(2), cs2(2), cs3(2), cs4(2)
c
c  AIR PROPERTIES
c
c  data cal/145.8e-8/, ca2/110.4/
c
c  H2O PROPERTIES
c
c  data rs(1)/461.0/
c  data cs1(1)/8.04e-6/, cs2(1)/4.07e-8/,
c  4  cs3(1)/1.858e-7/, cs4(1)/5.9e-10/
c
c  D2O PROPERTIES
c
c  data rs(2)/415.0/
c  data cs1(2)/8.3224e-6/, cs2(2)/4.1550e-8/,
c  4  cs3(2)/0.0/, cs4(2)/0.0/

```

```

c
c   AIR VISCOSITY
c
c   visa = cal*(sqrt(t))**3/(t + ca2)
c
c   STEAM VISCOSITY
c
c   ros = p/(rs(l)*t)
c   tinc = t - tconv
c   viss = cs1(l) + cs2(l)*tinc - ros*(cs3(l) - cs4(l)*tinc)
c
c   GAS VISCOSITY
c
c   visg = xa*visa + (one - xa)*viss
c
c   return
c   end

```

VISLQ

```

subroutine vislq(t,l,visl,dvdt)
c
c   *****
c   *
c   *   INPUT:
c   *   t = TEMPERATURE IN K
c   *   l = IDENTIFIER (l=1 FOR H2O, l=2 FOR D2O)
c   *
c   *   OUTPUT:
c   *   visl = DYNAMIC VISCOSITY OF SATURATED LIQUID IN Pa-s
c   *   dvdt = NORMALIZED DERIVATIVE OF VISCOSITY WITH RESPECT TO
c   *           TEMPERATURE
c   *
c   *   RANGE:
c   *   283.15K < t < 573.15K
c   *
c   *****
c
c   dimension c1(2), c2(2), c3(2)
c
c   H2O PROPERTIES
c
c   data c1(1)/+2.41277e-5/, c2(1)/+5.74268e+2/, c3(1)/+1.3916e+2/
c
c   D2O PROPERTIES
c
c   data c1(2)/3.34625e-5/, c2(2)/490.126/, c3(2)/157.884/
c
c   visl = c1(l)*exp(c2(l)/(t - c3(l)))
c   dvdt = -c2(l)/(t - c3(l))**2
c
c   return
c   end

```

VRIB

```

function vrib (alpha)
c
c   *****
c   *
c   *   FUNCTION vrib: THIS FUNCTION RETURNS VOID FRACTION AT THE
c   *                   RIB CALCULATED FROM THE CELL CENTER VOID
c   *                   FRACTION alpha. USING THE SRL DATA GIVEN IN
c   *                   WSRC-TR-91-661 VOID FRACTION NEAR RIB GAP
c   *                   WAS CORRELATED IN TERMS OF ANNULUS AVERAGE
c   *
c   *****

```

```

c      *          VOID FRACTION.          *
c      *          *          *
c      * ARGUMENTS (O=Output, I=Input):   *
c      *          *          *
c      * O   vrib - void fraction in vicinity of rib   *
c      *          *          *
c      * I   alpha - cell center void fraction   *
c      *          *          *
c      * COMMON VARIABLES:                 *
c      *          *          *
c      * I   iribv - selects between rib void correlation (iribv.eq.1) *
c      *          and default of vrib = alpha          (iribv.ne.1) *
c      *          *          *
c      *          *****
c
c      implicit real(a-h,o-z), integer(i-n)
c
c      include 'knobs.inc'
c
c      data a1/+1.0/, a2/-5.6761/, a3/+18.7005/,
c      a4/-25.8207/, a5/+12.7963/
c
c      if (iribv .eq. 1) then
c         vrib = (a1 + (a2 + (a3 + (a4 + a5*alpha)*alpha)*alpha)*alpha)
c         *alpha
c      else
c         vrib = alpha
c      end if
c
c      return
c      end

```

YVALU

```

      real function yvalu (itype,n,t,y,z,x)
c-----
c      Purpose: This routine evaluates the first-degree spline or
c               natural cubic spline for a given value of x.
c-----
c      Subroutine history
c      - algorithm given in "Numerical Mathematics and Computing" by
c        Cheney and Kincaid, 2nd Edition, 1985.
c-----
c
c      Arguments
c
c      NAME      I/O  TYPE      DIM      DESCRIPTION
c      -----
c      itype      I    I*4              Identifier of type of spline
c                                   = 0 (Natural cubic spline)
c                                   = 1 (First-degree spline)
c      n          I    I*4              Number of points
c      t          I    R*4              Abscissa values or knots
c      y          I    R*4              Ordinate values
c      x          I    R*4              Point of interpolation
c      z          O    R*4              Slopes of first-degree splines
c                                   or second derivatives of
c                                   natural cubic splines at the
c                                   knots
c-----
c      implicit real (a-h,o-z), integer (i-n)
c      parameter (zero=0.,p5=0.5,two=2.,six=6.)
c      dimension t(n),y(n),z(n)
c
c      if (x .ge. t(n)) then

```

```

        yvalu=y(n)
        return
    end if
c
    do 10 i=n-1,2,-1
        diff=x-t(i)
        if (diff .ge. zero) go to 20
10    continue
        i=1
        diff=x-t(1)
20    if (itype .eq. 0) then
        h=t(i+1)-t(i)
        b=(y(i+1)-y(i))/h-h*(z(i+1)+two*z(i))/six
        p=p5*z(i)+diff*(z(i+1)-z(i))/(six*h)
        p=b+diff*p
        yvalu=y(i)+diff*p
        return
    else
        yvalu=y(i)+diff*z(i)
        return
    end if
end
end

```

KNOBS . INC

```

common /sense/ xcofh,xcofl,xreh,xrel,xkmet,xcvmet,
&
& xhgi,xhfi,xkqi,xphi,cizfac,cixfac,
&
& xfric,plnht,cipln,formhs,alphs,ippu,
&
& alb2,als2,ala2,expbs,expsa,
&
& delp1,delp2,sigai,sigam,sigfi,sigfm,
&
& dalsub,theta0,iribv

```

PARAMS . INC

```

common /rparam/ runsec,tsec,delt,rdelt,dtmin,dymax,dtpld,dtpld,
&
& dtppwr,dtppmp,pref,epsin,factor,vminz,vminx,da,
&
& alpp1,alppln,alptb,alptbn,acpl,actb,
&
& volpl,voltb,ppl,xapl,tgpl,tfpl,rogpl,rofpl,hgpl,
&
& hfpl,ppln,xapln,tgpln,tfpln,rogpln,rofpln,hgpln,
&
& hfpln,ptb,xatb,tgtb,tftb,rogtb,roftb,hgtb,hftb,
&
& ptbn,xatbn,tgtbn,tftbn,rogtbn,roftbn,hgtbn,hftbn,
&
& topln,subln,botln,hactiv,gap,tsolid,tsrfac,tol,
&
& asypwr,solidv,deldmod,deldry,hmod,persat,
&
& epsp,epsalp,epstg,epstf,epsxa,tolpow,termax,tmid,
&
& hpref,hexpf,tsupw,htdamp,cidamp,xdelt,tolss,wss,
&
& xturb,douts,emisi,emiso,cradi,xa0,epsy,epsf
c
common /tzeros/ ppl0,alppl0,tgpl0,tfpl0,xapl0,qfin0,qfin,
&
& ptb0,alptb0,tgtb0,tftb0,xatb0,qgin0,qgin,
&
& tnklv0,sumdry,tmod0
c
common /iparam/ maxia,maxa,nz,nzpl,nzp2,nzp3,nzt,nzb,izht,izhb,
&
& nxmax,nchn,nsubc,nlarg,nspln,ntptot,matgas,iboil,
&
& ischem,irebal,ncmr,initmx,nitmax,iitot,nitno,
&
& istop,ierr,ibond,iunits,istart,iptime,isave,
&
& ippl,ialpl,itgpl,itfpl,ixapl,iggin,iprint,
&
& iptb,ialtb,itgtb,itftb,ixatb,iqfin,itnklv,
&
& ifissn,imodh,idryh,iconh,itmod,nreg,mnrrp,itime,
&
& iexp,icent,iaxial,ncms,iscrn,ncyl,nrmx,nrmxp,
&
& napl,nsurf,igami,igamw,icrit,ncrit,maxpl,isolid,
&
& iword,istdy,nstdy,ichf,iradbc,na,ilq,nitysi,
&
& ndata,ntpmax

```

POINTS . INC

```

common /pflmid/ lnx,licc,liazl,lnazc,laxml,lazml,laxm2,lazm2,

```

```

&      lrhs,ldp,lxx,lsz,lt,ldpm,lcmesh,lwxx,lwfx,lugz,
&      lufz,lcosx,lcosz,lacx,lacz,laratx,laratz,laxx,
&      lazz,ldhx,ldhz,lvolc,ldxm,ldz,ldzm,ldeffz,
&      lp ,lalp ,lxa ,lrog ,lrof ,lhf ,lhg ,ltf ,ltg ,
&      lpn ,lalpn,lxan,lrogn,lrofn,lhfn,lhgn,ltn,ltn,
&      ldgx,ldfx,lbz,lbz,lfa ,lftg ,lftf ,lfxa ,
&      legx,lefx,lcgz,lcgz,lcpa,lcptg,lcptf,lcpxa,
&      lfspit,labsrx,labsrz,lfldmz,
&      lfldcz,lc0bz,lc0sz,lckbz,lcksz,lfmtx,lfmtz,
&      lformx,lformz,lfrx,lfrz,ltxg,ltxf
C
common /pfltop/ latml,lrht,ldpt,lst,lcost,lact,laratt,lazt,
&      ldht,lvolt,ldzt,ldzmt,ldefft,
&      lpt ,lalpt ,lxat ,lrogt ,lroft ,lhft ,lhgt ,
&      lptn,lalptn,lxatn,lrogt,lrftn,lhftn,lhgt,
&      ltft,ltftn,ltgt ,ltgt ,lugt ,luft ,
&      lbgt,lbft ,lfat ,lftgt ,lftf ,lfxat,
&      lcgt,lcft ,lcpat,lcptgt,lcptft,lcpxat,
&      labrt,lfldmt,lfldct,lc0bt,lc0st,lckbt,lckst,
&      lfmltt,lformt,lfrt
C
common /pflbot/ labml,lrhtb,ldpb,lsb,lcosb,lacb,laratb,lazb,
&      ldhb,lvolb,ldzb,ldzmb,ldeffb,
&      lpb ,lalpb ,lxab ,lrogb ,lrofb ,lhfb ,lhgb ,
&      lpb,lpbn,lxabn,lrogbn,lrofbn,lhfbn,lhgbn,
&      ltfb,ltfbn,ltgb ,ltgbn ,lugg ,lufb ,
&      lbgb,lbfb ,lfab ,lftgb ,lftfb ,lfxab,
&      lcgb,lcfb ,lcpab,lcptgb,lcptfb,lcpxab,
&      labrb,lfldmb,lfldcb,lc0bb,lc0sb,lckbb,lcksb,
&      lfmltb,lformb,lfrb
C
common /ajacob/ ladvbz,ladvbz,ladvdx,ladvex,
&      ladvbt,ladvct,ladvbb,ladvcb
C
common /inlex/ lacin,lrogin,lrofin,lalpin,lugin,lufin,
&      lacex,lrogex,lrofex,lalpex,lugex,lufex
C
common /intfac/ lcitn,lcixn,lcizn,lcibn,
&      lhgi ,lhfi ,lakgi ,lysi ,lei ,lgi ,
&      lhgit,lhfit,lakgit,lysit,leit,lgit,
&      lhgib,lhfib,lakgib,lysib,leib,lgib
C
common /psolid/ lnr,lfrst,lfnst,lloxid,llobib,lmat,lwt,
&      lrib,lribt,ldiam,ldr,lar,lradc,lvolc,lzfacm,
&      lts,ltsn,lpows,ltsurf,ltsrfn,lqwf,lqwg,ldqfdw,
&      ldqgdw,ltheta,lqw,lhsp,lchfq,lqonb,lthld
C
common /ppower/ lnrp,lrgtm,laxlp,lpfrct,lpfrdd,lpfrdw,lrphi,
&      lrphdd,lrphdw,lrdz,laxial,laxal0,ltime,
&      lfazmm,lfrdim,lbigm,lbigmw,lbigmd
C
common /splin/ lwb,lwh,lwu,lwv,lxtp,lytp,lztp,lintp,litype,
&      lntp
C
common /critrs/ lichks,lichkc,lpkfac
C
common /ic/ ia(10000)
common /rc/ a(200000)

```

END

DATE
FILMED

6 / 18 / 93