DOE/ER/40641--2

DE93 009373

PROGRESS REPORT

David Hedin, Daniel Kaplan, James Green

Studies of High Energy Phenomena Using Muons

February, 1993

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

PROGRESS REPORT

1 INTRODUCTION

This report covers the activities of the NIU high energy physics group as supported by DOE contract DE-FG02-91ER40641.A000 during the period from March of 1992 through February of 1993. Our group has three main efforts. The first is the D0 experiment at the Fermilab proton-antiproton collider, with major emphasis on its muon system. The second is the involvement of a portion of the group in Fermilab Experiment 789. Finally, we are also members of the SDC collaboration at the SSC.

2 D0-RELATED WORK

The D0 detector is a large, general-purpose detector designed to take full advantage of the 1.8 TeV energy of the Fermilab collider by a collaboration of over 375 physicists from 36 institutions. The primary physics goals of D0 include searching for new phenomena such as the top quark or compositeness and high-precision studies of the W and Z bosons. In addition, the excellent muon identification will allow the study of b -quark production and decay. The design of the experiment emphasizes accurate identification, complete angular acceptance, and precise measurement of the decay products of W and Z bosons: charged leptons (both electrons and muons), quarks and gluons, which emerge as collimated jets of particles, and noninteracting particles, such as neutrinos, which appear as an energy imbalance in the calorimeter.

The D0 detector consists of three major hardware systems, calorimetry, muon, and central tracking, which together allow fairly complete characterization of most proton-antiproton collision events. The tracking system consists of four drift-chamber systems (a microvertex, a central, and two end systems) with delay-line readout to provide measurement of space points and transition radiation detectors for electron identification. Surrounding the tracking system is a uranium/liquid-argon calorimeter. The uranium is a dense medium, allowing containment of high-energy hadron showers in a relatively short depth, as well as equal response to electrons and hadrons, while the liquid-argon

readout gives ease of calibration, stability, radiation hardness, and the ability to build in fine segmentation in all three coordinates. Finally, surrounding the calorimeter is the muon system, consisting of five magnetized iron toroids and three layers of drift chambers. The toroids are used to measure the muon momentum and to absorb all remnant portions of hadron showers. Muon trajectories in the wide angle region (greater than 9 degrees) are measured using 10 cm drift cells with 3D readout (11,000 cells in 164 chambers total) whereas the small angle region (5 to 20 degrees) is covered by 3 cm cells with 2D readout (5000 cells in 6 chambers).

D0 saw its first proton-antiproton collision in May 1992; physics running started in August and is scheduled to continue until May 1993. We anticipate an integrated luminosity of more than 20 pb^{-1} from this initial run (Ia). Starting in November of 1993, a second run (Ib) will commence and extend through much of 1994. Run II, which will feature an increase in the number of bunches from 6 to 36, is currently scheduled for the 1995-96 period.

The primary emphasis of the NIU D0 group is the muon system. Other groups involved with the muon system are Fermilab, Protvino, Arizona, Hawaii, Indiana, CBPF, Uniandes, and Riverside. NIU is involved in all aspects of the D0 muon effort, with particular responsibilities for the data readout (Fortner); calibration of the chambers (Green and Markeloff); and the muon reconstruction (Hedin and Sirotenko). Hedin also continues his role as coordinator of muon software and shares (with D. Zieminska of Indiana) the responsibility for muon identification.

In addition to our muon-system responsibilities we have a number of global responsibilities within D0. Along with G. Blazey of Rochester, Fortner is responsible for the day-to-day setting of the trigger conditions. Fortner and Green are members of a select group of data-taking experts. Finally, Hedin is co-coordinator (with D. Green of Fermilab) of the *B*-physics analysis group.

Highlights of the detector commissioning and operation during the past year and preliminary physics results will now be described. Plans for our D0-related

2.1 D0 Running

The first colliding-beam run with the D0 detector began in May 1992. As of January 20, the accelerator has provided 13 pb^{-1} integrated luminosity, and the D0 group has logged about half that much data to tape. Prior to the colliding-beam run, we had a substantial cosmic-ray run to get the detector into working order.

Members of the NIU group have been central in the daily operation of the detector. During operation of the D0 experiment, at least six physicists are on shift. These include a shift captain, one member from each detector group (Central Detector, Calorimeter, and Muon), a data-acquisition expert, and a global monitor. All of the post-doctoral and faculty members of the NIU D0 group have served as muon shift personnel. In this capacity, they are responsible for running and monitoring the muon detector. Because of the large number of people in the muon group, the muon shift burden is fairly light. Fortner and Green are data-acquisition experts. The DAQ expert is responsible for running the online computer systems and ensuring a smooth flow of data from the detector through the Level-2 farm of filter computers and onto magnetic tape. The DAQ expert also monitors the D0 alarm and control system. Since there are only about 20 DAQ experts, their shift burden represents substantial work. Fortner also serves as a shift captain. In this capacity, he coordinates efforts of the various detector groups, maintains the official log, and communicates with the Fermilab main control room. Other NIU personnel run either muon or global monitor shifts.

2.2 Trigger and Data Acquisition

There is a long menu of physics items under investigation by D0, and the trigger must be able to accomodate the full scope of this physics. The trigger for D0 is divided into two parts. There is a hardware trigger (Level 1) and a software trigger (Level 2). Both triggers, especially the muon components, have been under development during the course of our initial runs. Some of these aspects are discussed further later in this report. At each level there are limitations in the rate that can be sustained with minimal deadtime and in

the number of trigger elements that can be used.

D0 created a panel of nine members to oversee the implementation of the trigger and approve any changes. The trigger panel includes a member from each of the major physics interests in D0 (QCD, Top search, W/Z physics, B -physics, and non-standard phenomena) and meets every week to discuss changes needed due to modified hardware, software, or physics needs or changing accelerator conditions. Both Hedin and Fortner have been members of this trigger panel. The job of the trigger panel is to allocate the available trigger bandwidth among the physics topics and to approve changes to the running triggers. The panel's recommendations are implemented by the "Trigger Meister" (either Fortner or J. Blazey of Rochester), who is responsible to see that the correct triggers are available online. The Trigger Meister also measures the trigger rates and reports the results to the collaboration and defines the trigger list that the panel discusses. Examples of the trigger list and the bandwidth allocations are shown in Tables I and II. As can be seen from these tables, defining and allocating trigger resources is a complicated task but of critical importance to the experiment: it determines which events get written to tape for further analysis.

One of the limitations on the trigger rate is the readout speed of the detector. The muon system uses a number of microprocessors to control digitization and readout, executing programs implemented and tested by Fortner. Among the programs are a main data-acquisition program, used for normal data and calibration, and a local test program for debugging front-end chamber electronics. Each of these programs exists in forms for both wide-angle and small-angle operation. The small-angle regions of the muon system were found to have about double the expected number of hits. Moreover, the luminosity exceeded the D0 design specifications more than fivefold, thus digitization of hits in the small-angle muon system was causing a significant amount of deadtime. To minimize the deadtime we were forced to run at a lower Level-1 trigger rate, 40 Hz, compared to the nominal design value of 200 Hz. Studies by Markeloff were conducted to determine the relative number of hits in each crate. This information along with detailed timing

the number of trigger elements that can be used.

D0 created a panel of nine members to oversee the implementation of the trigger and approve any changes. The trigger panel includes a member from each of the major physics interests in D0 (QCD, Top search, W/Z physics, B -physics, and non-standard phenomena) and meets every week to discuss changes needed due to modified hardware, software, or physics needs or changing accelerator conditions. Both Hedin and Fortner have been members of this trigger panel. The job of the trigger panel is to allocate the available trigger bandwidth among the physics topics and to approve changes to the running triggers. The panel's recommendations are implemented by the "Trigger Meister" (either Fortner or J. Blazey of Rochester), who is responsible to see that the correct triggers are available online. The Trigger Meister also measures the trigger rates and reports the results to the collaboration and defines the trigger list that the panel discusses. Examples of the trigger list and the bandwidth allocations are shown in Tables I and II. As can be seen from these tables, defining and allocating trigger resources is a complicated task but of critical importance to the experiment: it determines which events get written to tape for further analysis.

One of the limitations on the trigger rate is the readout speed of the detector. The muon system uses a number of microprocessors to control digitization and readout, executing programs implemented and tested by Fortner. Among the programs are a main data-acquisition program, used for normal data and calibration, and a local test program for debugging front-end chamber electronics. Each of these programs exists in forms for both wide-angle and small-angle operation. The small-angle regions of the muon system were found to have about double the expected number of hits. Moreover, the luminosity exceeded the D0 design specifications more than fivefold, thus digitization of hits in the small-angle muon system was causing a significant amount of deadtime. To minimize the deadtime we were forced to run at a lower Level-1 trigger rate, 40 Hz, compared to the nominal design value of 200 Hz. Studies by Markeloff were conducted to determine the relative number of hits in each crate. This information along with detailed timing

measurements allowed Fortner to rewrite time-critical parts of the data-acquisition code and increase overall readout speed by a factor of 10. The central tracking has now replaced the muon readout as the dominant contributor to deadtime, and a Level-1 trigger rate of 100 Hz is now possible.

2.3 Muon Calibration

The muon detector electronics are calibrated in a two-step process. In the first step, pulses are sent to the front-end electronics, and the results are read out and analysed. In the second step, real data are used to refine the results of the first step. Calibrations are kept in a database so that reconstruction programs can access them. Green has overall responsibility for calibration of the muon detector by electronic pulsing. Assisted by Nellinger, he is also responsible for maintaining the calibration database. During Fall 1992, operation of the calibration program for complete "geographic sectors" (of which, for example, the wide-angle muon system has five) became possible. This allowed the routine calibration of the detector between beam stores. Direct use of the calibration constants from pulsing gives resolutions averaging about 1600 microns in the drift direction (with some modules having much worse resolution). The constants refined using data (generated using code developed in 1992 by Hedin) improve the chamber resolutions to about 900 microns and greatly reduce the resolution tails. Along the wire, positions are determined using time-difference measurements; here we get resolutions of about 20 to 40 centimeters using pulser calibrations (again with some modules having worse resolutions), and offline refinement of the calibrations gives resolutions of 15 to 20 centimeters. These are sufficient for use of the cathode-pad vernier. For the cathode pads we use pulser calibrations directly and have achieved a resolution of about 6 mm.

We also need to understand the relationship between drift time and the distance from the wire. Just prior to the start of the run, it was determined that cable delays plus the time needed to coordinate Level-1 triggers was more than 400 ns greater than expected. This forced us to change our drift gas from Ar:CO₂ (90:10) to a faster gas, Ar:CO₂:CF₄ (90:5:5), in order to maintain good chamber efficiencies. This new gas had never been

used by us (or anyone else). A preliminary measurement of its drift properties was made by Hedin. Currently, a systematic study of this gas in a D0 muon cell is being made by Markeloff, Cease and a Fermilab physicist. Proper understanding of the gas should allow us to improve our resolution from 900 microns to less than 500 microns. It is also possible for contaminants, such as water vapor, to be present in the muon gas volume. These can affect the drift velocity; for example, water vapor tends to slow down the drift. Code to correct for this was developed by Hedin, and is now being used by Markeloff to monitor the system and modify constants in the database as needed.

2.4 Muon Reconstruction

Muon identification utilizes information from the muon system itself, the central tracking, and the calorimeter. The primary backgrounds are from cosmic rays, which are out of time with the beam crossing and do not intercept the primary vertex, and hadron-induced spray (often giving uncorrelated chamber hits), which produces poorly-fit tracks which also tend to miss the vertex. The muon reconstruction is split into three stages. The first stage converts raw data to points in space, finds muon tracks, and uses only muon-chamber information to do an initial calculation of particle momentum. It uses the track's quality and its projection to the vertex for preliminary muon identification. This stage serves as the Level-2 trigger. The next stage associates information in the calorimeter and inner tracking to the tracks found in the muon system. Finally, a complete fit is performed using all information available.

The muon Level-2 trigger has been used for data taking since June 1992. Hedin wrote more than 95% of the wide-angle ($>15^\circ$) code; the small-angle code was written by physicists from IHEP, Indiana, and NIU (Sirotenko). Coordination of the muon filter with the Level-2 structure (include accessing calibration constants) is the responsibility of a Fermilab postdoc. The original version used code tested primarily on Monte-Carlo events, and in the non-bend view used incomplete information, limiting position resolution to ≈ 25 cm compared to the offline's 1 cm. The rejection rate was about 20, with backgrounds coming primarily from cosmic rays in the central region and hadronic spray in the forward.

There were also poor efficiencies ($\approx 60\%$) in the forward region, due to less than ideal chamber performance combined with a hit density somewhat larger than predicted. Finally, we did not operate with any triggers (either Level-1 or Level-2) in the small-angle region.

During the remainder of 1992, a number of improvements were made to the muon Level-2 trigger, based largely on knowledge gained by analyzing the data. Code was added to identify cosmic-ray backgrounds in the central region by searching for associated hits directly opposite the found track. This reduced the cosmic-ray rate about threefold with $<5\%$ signal loss. We also observed that hadronic-spray-induced backgrounds gave fewer hits on a track than did muon tracks, and we have reduced this background twofold using appropriate hit requirements. The trackfinding efficiency between 15° and 45° was improved by modifying the tracking selection criteria. At the same time, the code was speeded up, allowing a more complete calculation of the muon trajectory and tighter requirements on the track projection to the vertex. We have also added code to search for muons in the region below 15° . Beginning in February 1993, the complete muon Level-2 filter will be used in all D0 data collection. The Level-2 algorithm is now identical to the first stage of the offline, thereby reducing inefficiency losses and systematic errors. The Level-2 reduction factors for various muon triggers can be seen in Table I.

The Level-2 improvements just described have also been made to the offline reconstruction. In addition, a first working version of the complete muon fitting package became available in January 1993. The goal of the complete fit is to utilize all of the information in the event in order to make the best determination of the muon's momentum, including errors, and optimize the muon identification. It includes multiple scattering, handles multiple vertices, selects the best central track if there are matching ambiguities, and cycles over multiple drift solutions in the muon chambers. Currently the complete fit improves the resolution on 50 GeV/c Monte-Carlo muons by about 30% but gives smaller improvement for real data. To do such an analysis properly requires a correct understanding of the measurement errors in the central tracking and muon systems. These studies are ongoing, and we anticipate using the complete fit in muon identification and momentum

measurement by May. This will complete the muon reconstruction software development phase.

It should be noted that the primary limitation on momentum resolution is not the fit technique but the accuracy of the measured points. The Z mass resolution (and other studies as well) indicates that the muon-chamber position resolution is currently 3-5 mm; this is primarily due to our present understanding of survey values. Previous studies indicate that this can be improved to about 1 mm using the data themselves, which would give $\Delta p/p = 0.002 p$ due to this effect. The resolution would then be limited by multiple scattering to about 20% for momenta below 50 GeV/c. Three Fermilab physicists are responsible for improving the survey values.

Along with Zieminska of Indiana, Hedin has primary responsibility for providing D0 with muon identification criteria and the corresponding efficiencies and background calculations. Many other people are involved in this, with more than 15 people working on related topics. We have made preliminary estimates of these quantities and understand our muon signals to roughly 30% at the present time. For example, the background from cosmic-ray muons to our $W \rightarrow \mu\nu$ signal is about 20%, while that from hadron-induced sources is $< 5\%$. Backgrounds to muons associated with jets are $< 10\%$. With better calibrations and a complete reconstruction package, our ability to reject backgrounds while maintaining high signal efficiency will improve. During the remainder of 1993, we will use our samples of Z , J/ψ , and $B\bar{B} \rightarrow \mu\mu$ to understand our single-muon efficiencies as a function of various criteria. Combining this with background studies will then allow us to define "final" muon selection criteria.

2.5 Physics Analysis

With operation of the detector becoming routine and most of the reconstruction software developed, the primary focus of D0's effort has shifted to physics analyses. To coordinate these efforts, five groups have been formed: Top, B -physics, Electroweak, QCD, and New Phenomena. Decisions relating to trigger bandwidth, computing resources, and

presentation of results in papers or at conferences are all coordinated through these groups. There is clear overlap among the groups (for example, $B \rightarrow \mu$ events are important to the Top, B , and QCD groups), and NIU is involved in B -physics, the top search, and QCD. Hedin is co-coordinator of the B -physics group with D. Green of Fermilab. He is also on the D0 physics advisory panel, a sixteen-member group charged to advise the D0 spokesperson on physics-related issues.

The top-quark search is the highest priority for D0. Given integrated luminosity of 20 pb^{-1} , D0 (and CDF) should see evidence for top if its mass is less than about $150 \text{ GeV}/c^2$. There are two primary decay channels, dilepton and lepton+jet; these can be detected using electrons and muons. Of the two, the dilepton channel is cleaner, since very few background events have two high p_t leptons, two jets, and missing energy. The lepton+jet channel has a larger branching ratio, but increased backgrounds from QCD and W/Z production. As of this writing, D0 has a handful (fewer than 20) of interesting events in both channels, some of which are candidates for top decay. Given such a small number of events, each is investigated in detail; Hedin is a member of a group responsible for certifying those candidate events containing a muon. Some of them have multiple momentum solutions, which the current reconstruction code is unable to resolve completely. As more data are collected, and as we understand our selection criteria and our handling of large data sets, the number of top decay candidate will continue to grow. D0 is in the process of making background and efficiency estimates, aiming for limits on the top mass for presentation at conferences this coming spring. A two-day workshop on the top analysis was held at NIU on February 17 and 18, with Hedin as a co-organizer.

NIU is also involved in using $t \rightarrow b \rightarrow \mu + X$ events as an additional top-tagging method. Most top events should contain two b -quarks, and there is about a 25% probability that one of these produces a low- p_t muon associated with a jet. Beauty decay yields muons which can be distinguished from π , K , and charm decays by the topology and kinematics of the muon momentum vector with respect to the accompanying jet. These muon-jet distributions can be understood using $B\bar{B} \rightarrow \mu\mu + X$ events from data or Monte Carlo. Markeloff is studying

the separation of the various muon sources using a number of methods. A “traditional” method is to cut on parameters such as the p_t of the muon relative to the jet axis. This costs some efficiency, not a good feature for rare processes such as top decays. He is also exploring the use of neural network algorithms, which can be “trained” using our samples of known b -decays. It is hoped that these algorithms can give better b -decay identification with higher efficiencies.

The B -physics goals of D0 are quite different from its top physics goals. In many ways, D0 will be a second- (or even third-) generation experiment for certain aspects of B physics. The number of events will be large: for 20 pb^{-1} , over 400,000 $b\bar{b} \rightarrow \mu\mu$ events are reconstructible, with about 20,000 of these events having a third muon from a charm decay. Results on such topics as b -quark production cross section and mechanisms and $B^0 \bar{B}^0$ mixing will be limited by systematic errors, with the large data sets being used to better understand and thus reduce those errors. D0 will also collect large numbers of J/ψ decays, both to dimuons and to dielectrons. We have estimated 4 nb and 0.1 nb rates for $B \rightarrow \psi \rightarrow \mu\mu$ and $B\bar{B} \rightarrow \psi\mu X \rightarrow \mu\mu\mu X$ respectively. These data sets will allow studies of J/ψ production mechanisms and searches for rarer processes such as $B \rightarrow \psi K_s$.

The actual rates will depend critically on how low in p_t and angle we are able to operate the muon trigger. For much of our initial run, the various aspects of the muon trigger were still under development, with higher priority going to central, higher- p_t muon triggers. We are also limited by bandwidth: D0 is operating at a luminosity about 6-10 times design with a Level-1 bandwidth of 100 Hz, which is half the design value. Of this, only about 15 Hz is allocated to B -physics triggers. As seen in Table I, rather than prescaling triggers for rare processes (such as trimuon events), we have opted to require additional trigger elements, such as jet towers. We are still optimizing these choices, but trigger limitations will probably reduce our data sample for Run Ia threefold relative to the numbers quoted in the previous paragraph. Further improvements will wait until Run Ib.

We have performed preliminary B -physics analyses on data collected during 1992. First results, indicating the quality of our muon identification, were reported at the ICHEP

Conference in Dallas by Hedin. Subsequent papers presented at the DPF meeting at Fermilab demonstrated that the kinematic distributions for single and dimuon events in the central region ($|\eta| < 1$) were about as expected. We have also measured a preliminary value for the dimuon like-to-opposite-sign ratio, $R = 0.66 \pm 0.03$. This is in general agreement with CDF's published value of 0.556 ± 0.048 (stat), with some of the difference arising from differing kinematic cuts.

Our goal for the next few months is to obtain cross sections for both single and dimuon processes in the central region. To organize this effort, we held a four-day workshop at Indiana University in December, co-organized by Hedin. Much of the work involves understanding backgrounds and efficiencies, which overlaps with the work of the muon identification group. We will also work on converting the dimuon charge ratio R to mixing parameters which characterize the $B^0\bar{B}^0$ system. The corrections are dominated by backgrounds to direct $b\bar{b} \rightarrow \mu\mu + X$ decays. Further work on extending the kinematic acceptance to higher η and lower p_t is also proceeding with results expected during the summer.

2.6 D0 Upgrade

NIU anticipates an active role in the D0 upgrade (E823). The upgrade's goal is to maintain the performance of the D0 detector for high- p_t physics at luminosities up to $5 \times 10^{31} \text{ cm}^{-2}\text{sec}^{-1}$ and $p\bar{p}$ bunch spacing of 396 ns. In addition, we hope to improve our capabilities for some physics channels, and in particular to improve substantially D0's capabilities for reconstructing large, clean samples of exclusive B -decays. We estimate that the acceptance for $B \rightarrow \psi \rightarrow \mu\mu$ will be over 20%, as the addition of a central magnetic field both increases the geometric acceptance (by closing gaps in current coverage) and allows muons which range out in the iron toroid to be reconstructed. For a 100 pb^{-1} integrated luminosity, this translates into a $> 10^9$ -event $b\bar{b}$ sensitivity.

Some of the upgrades to the muon system have already begun. As mentioned above, we were already forced to go to a faster gas during Run Ia, and the maximum drift time

with this gas (about 700 ns) appears to be acceptable for all future running conditions. D0 will also be increasing the Level-1 rate to more than 500 Hz. Studies related to improving the current muon readout speed indicate that a few minor hardware changes (with related changes to the code) should allow the muon system to read out in less than 1 msec. This should be acceptable, and the changes will be implemented before Run Ib.

At the conclusion of the current run, D0 will begin installing the upgraded muon scintillation counters. Present plans call for enough scintillator to cover about half the central muon detector before Run Ib. Installation of the scintillator includes testing and installing new electronics, writing new data-acquisition, testing, and monitoring code, and developing a calibration procedure for the scintillator. The muon scintillator upgrade replaces the original cosmic-ray veto, using entirely new electronics as well as new scintillator. While the new scintillator can also be used for cosmic-ray rejection, the main aim of the scintillator upgrade is to tag muons to the correct beam crossing, given a Tevatron bunch spacing less than the maximum muon-chamber drift time.

The prototype and production versions of the new front-end electronics will be available in Spring 1993. Fortner has been advising the engineer on the interfacing needs of these modules. Fortner and an NIU student (Li) will work on module testing. Li will continue to provide assistance during the production and installation of the electronics this summer and will be involved with monitoring their performance during the upcoming collider run. Calibration and monitoring of the scintillator will require a program and database to track changes. Green is responsible for the calibration code for the muon system and will extend these programs to manage the scintillator as well.

Other upgrades to the muon system, such as trigger improvement, will be revisited during the Summer of 1993. We now have both the experience of our first run plus large sets of data which can give a better indication how to proceed. Any changes can then be implemented before Run II, which will not occur before 1995.

3 E789-RELATED WORK

The E789 collaboration includes physicists from eight institutions: Abilene Christian University, Berkeley, Chicago, Fermilab, Los Alamos, NIU, South Carolina, and Academia Sinica (Taiwan). A sensitive search for rare low-multiplicity decay modes of particles containing c or b quarks, E789 ran during the 1990/91 fixed-target run, recording some 1.5 billion events on ≈ 1300 8-mm magnetic tapes.

The E789 data analysis is progressing well. As of February 1993, some 50% of the (large) beauty data set and most of the (smaller) charm data sets have been reduced. We expect to complete the first analysis pass this summer. Second-pass analyses are in progress for most data sets. Preliminary results on D^0 production in 800-GeV proton collisions have been presented at a number of conferences, including the A -dependence, cross section, and $D - \bar{D}$ production asymmetry. Work using the data to refine the field map of our main analyzing magnet has reduced our rms mass resolution at the D to ≈ 5 MeV. Existing data on 800-GeV charm production come only from bubble-chamber (E743) and emulsion (E653) experiments, which have low statistical precision and represent only a single target material in each case, thus the E789 results will constitute a significant contribution.

Analysis of the "target-out" data sets (taken in a few shifts to explore large-Feynman- x J/ψ production in the beam dump) has been completed; this is also the first E789 Ph.D. thesis to be completed. Measuring the J/ψ cross section over the range $0.3 < x_F < 0.93$, we find good agreement with the semi-local duality production model. By inserting beryllium blocks into the "nose" of the beam dump, we were also able to study the A -dependence of J/ψ production over most of that x_F range; the results confirm those of E772 where there is overlap ($x_F < 0.65$) and show a substantial decrease of the A -dependence exponent α at the highest x_F . Writing up of these results for publication will commence soon.

Preliminary beauty results have been presented at the San Miniato Topical Seminar, the 1992 International Conference on High Energy Physics, and the 1992 DPF meeting. We have observed a significant $B \rightarrow J/\psi + X$ signal in the dimuon sample, consisting of J/ψ events with vertices inconsistent with origin in the target. The exact number of events depends on the vertex cuts employed; including all data analyzed to date, typical cuts give

≈ 20 events downstream of the target, while corresponding cuts selecting dimuons with apparent vertices upstream of the target show that the background due to misidentified target- J/ψ s is negligible. The rate of downstream J/ψ s indicates a $b\bar{b}$ cross section of ≈ 15 nb/nucleon (assuming linear A -dependence), consistent with expectations from QCD. Monte-Carlo studies are in progress to estimate the sensitivity of our acceptance to the assumed beauty-production model. In addition to the downstream J/ψ s, there is a dimuon continuum consistent with production and semileptonic decay of $B\bar{B}$ pairs. Work is in progress on electron identification, and we expect to demonstrate a beauty signal in dielectrons as well. Work is also in progress on the dihadron sample and the Cherenkov hadron identification.

3.2 NIU Contribution

Kaplan is co-spokesman for the E789 collaboration and is supervising and organizing the work of the "Fermilab-resident" E789 group (NIU, Fermilab, and Chicago/IIT) and the collaboration as a whole. During the past year Tanikella has worked primarily on electron identification, investigating the efficiency and hadron rejection of the various calorimetric electron-ID requirements using both data and Monte Carlo. Due to the extensive bremsstrahlung of electrons from J/ψ s produced in the (≈ 1 -radiation-length) target, this is a challenging study, but it is now close to completion. Luebke helped with off-line tape handling and worked on analysis of the optical-trigger test data. The latter analysis is now complete, with one paper accepted for publication in Nuclear Instruments and Methods and a second soon to be submitted.

4 SDC-Related Work

NIU's participation in the SDC collaboration is currently the responsibility of Willis and Sirotenko. Willis is the head of the muon simulation group, co-chair of the SDC Neutron Task Force, and a member of the Muon Technical Board and the Simulation Task Force.

The Solenoidal Detector Collaboration (SDC) has proposed a general-purpose detector aimed at pursuing a broad range of physics goals at the SSC. The detector has been designed so that all subsystems will be fully functional at the design luminosity of $10^{33} \text{ cm}^{-2} \text{ s}^{-1}$ and so that it will perform, with somewhat reduced functionality, at substantially higher luminosity. The detector has central tracking in a solenoidal magnetic field, hermetic calorimetry, identification and energy measurement of electrons and muons,

and high-resolution vertex detection.

NIU is working on the SDC muon system, including the trigger and simulations for both the forward and the barrel systems. As in D0, the muon system in SDC has been designed to perform several distinct functions: to identify muons; to trigger on high- p_t muons in Level 1; to provide information to the Level-2 and -3 triggers; and to provide an independent measurement of the momentum of muons in physics processes of interest, improving that momentum measurement by linking those muon tracks with tracks measured in the inner tracker.

The SDC barrel muon system consists of three measurement stations of wire chambers. The innermost layer is separated from the two outermost layers by a 1.5-meter iron toroid, energized to 1.8 Tesla. The magnetic field lines are in the ϕ direction, therefore most of the wires measure the θ coordinate most accurately. However, the field of the inner solenoid is in the z direction, so the inner tracker is optimized to measure ϕ ; in order to facilitate track matching, the muon system includes ϕ measuring wires as well. There are also small-angle stereo wires, which associate the two orthogonal views. BW1, the innermost station, contains 4 θ layers and 4 ϕ layers; BW2, just outside the toroid, contains 4 θ layers; and BW3, the outermost station, contains 4 θ layers, 4 ϕ layers, and two small-angle (primarily ϕ) stereo layers. Finally, there is a layer of scintillator located just outside BW2, consisting of single counters with photomultiplier tubes at each end, used to identify which beam crossing produced a particular trigger. The trigger relies on the wires having a projective geometry; that is, that a pair of wires will point back to the interaction region. The difference in drift times within a projective pair is then a measure of the momentum of the track. Coincidences between projective pairs in the chambers outside the toroid will remove left-right ambiguities and reduce low-momentum "fakes" masquerading as high-momentum tracks. The second-level trigger may include information from the inner chamber (BW1), information from the ϕ tubes within the muon system, or linking of muon tracks with tracks in the central tracker (which measures bends in ϕ).

The forward muon system consists of two identical ends, each of which has two 1.5-m-

thick toroids and four measuring stations. FW1 and FW2 are located inside the toroids; there is a gap between the toroids for an upgrade if necessary (FW3); FW4 and FW5 are outside the second toroid. There are two layers of scintillator in the forward system which will be located either just behind FW4 and behind FW5, or else together behind FW4. As in the barrel, these are placed in coincidence in order to identify the beam crossing. In addition, there is the option of using a Cherenkov counter in the trigger as well; it would identify which crossing a trigger came from and veto triggers from particles whose momentum is low or which do not come from the interaction region. The forward region presents a number of unique problems: the rates are much higher than in the central region, and the tracking and calorimetry are less well optimized. Therefore, system operation in the absence of inner-tracking information is of more concern here.

A muon is identified in two ways: by penetrating the $9\text{-}\lambda$ calorimeter and the $9\text{-}\lambda$ (at 90°) toroid, and by having its momentum measured in both the inner tracker and the muon system. The momentum measurement is limited by multiple scattering to about 20% in the barrel system and to about 10% in the forward system. At higher momenta, chamber resolution and misalignment dominate; at sufficiently high momenta, even the sign will be indeterminate.

At NIU, we are doing simulation studies of the effects of electromagnetic showers (bremsstrahlung, delta rays, and pair production) accompanying high-energy muons; experimental and simulation studies of neutron backgrounds in the forward and barrel systems; physics simulations of the effects of resolution and misalignment; and writing pattern recognition algorithms for use in track reconstruction and fitting. Sirotenko has written a first version of a track reconstruction code, and finds that the reconstructed momentum resolution is in agreement with that expected from calculations of resolution and multiple scattering. The reconstruction code also is used to study the effect of electron showers on the tracking efficiency, and whether or not the available redundancy is sufficient. A more sophisticated reconstruction possibly using a Kalman-filter-type algorithm is under development by Colorado. Besides being used for current critical studies, Sirotenko's

tracking will also serve as an aid in debugging the newer code. It is noteworthy that NIU currently has the responsibility for finding and fitting muons in the central region for both SDC and D0.

Willis is coordinating the entire SDC muon-simulation-group's efforts and is co-chair of the SDC Neutron Task Force. This task force was recently formed to coordinate studies of the effects of low-energy neutrons (from a few MeV down to thermal energies) within the collaboration, and between SDC and the rest of the Lab. Willis is responsible for coordination within SDC, and T. Pal of SSCL is responsible for external coordination. Studies of the number of such neutrons produced, and the effectiveness of shielding, are of critical importance to the design of the forward muon system, and both Willis and Sirotenko are working with the Russian physicists and engineers who are responsible for the design of that system.

Studies of the neutron flux within the SDC detector as described in the Technical Design Report (which includes minimal shielding around the collimator and none around the quadrupole magnets) show that the rates in the forward muon chambers (and in the ends of the barrel chambers as well) are too high by 2 to 3 orders of magnitude. Therefore, an intense study is taking place to determine how much shielding is required and whether other modifications to the design need to be made (moving the quadrupole magnets further away, changing the design of the forward calorimeter, and so on). Calculations are being made by several groups, including Los Alamos, Oak Ridge, and IHEP as well as NIU. It is hoped that there will be a satisfactory design by the summer. This study is being organized by Willis.

A new experimental measurement of the low-energy-neutron leakage in hadronic showers has been done (Fermilab T-821); NIU student Mierkiewicz was part of this collaboration. Preliminary results were presented at the November meeting of the DPF. The observed energy spectrum is independent of incident beam momentum and absorber thickness (in agreement with previous results), and the total neutron flux decreases about a factor of four for each additional five interaction lengths of iron. Further analysis is in

progrcss.

The muon trigger is scheduled for a review at the May SDC collaboration meeting. Understanding the trigger and its robustness is critical to understanding the acceptable level of backgrounds, from neutrons as well as from other sources. The effectiveness (efficiency and rejection) of various trigger scenarios, both at Level 1 and Level 2, needs to be evaluated through simulation. In addition, the muon trigger electronics is in the process of being designed; several designs will be tested both at a beam test at KEK in February and after the supertower prototype is constructed later this year. Again, trigger simulations are being done by a variety of groups, and their efforts are being coordinated by Willis.

END

DATE
FILMED

5/25/93