1 of 1

**Cover Sheet for a Hanford
Historical Document
Released for Public Availability**

Released 1994

**Prepared for the U.S. Department of Energy
under Contract DE-AC06-76RLO 1830**

**Pacific Northwest Laboratory
Operated for the U.S. Department of Energy
by Battelle Memorial Institute**

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This is a **historical document** that is being released for public availability. This was made from the best available copy. Neither the United States Government nor any agency thereof, nor Battelle Memorial Institute, nor any of their employees, makes **any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights.** The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

(CLASSIFICATION)

DECLASSIFIED

HW-82977 RD 3 ^{REV} ~~Rev.~~
PAGES AND COPY NO. 2

A - 7

August 3, 1964

GENERAL ELECTRIC

HANFORD ATOMIC PRODUCTS OPERATION - RICHLAND, WASHINGTON

X

THIS DOCUMENT CONTAINS RESTRICTED DATA
DEFINING THE NUCLEAR ENERGY
ITS DISSEMINATION TO THE PUBLIC
CONSENTS IN ANY MANNER. UNAUTHORIZED
PERSON IS PROHIBITED.

TITLE

IPD PRODUCTION PROJECTIONS

7

OTHER OFFICIAL CLASSIFIED INFORMATION

THIS MATERIAL CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING OF THE ESPIONAGE LAWS, TITLE 18, U.S.C., SECS. 793 AND 794, THE TRANSMISSION OR REVELATION OF WHICH IN ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW.

AUTHOR

L. W. Lang

ISSUING FILE
CIRCULATING COPY
RECEIVED 106 D AREA
AUG 5 1964
RETURN TO
TECHNICAL INFORMATION FILES

THIS DOCUMENT IS NOT TO BE LEFT UNATTENDED OR WHERE AN UNAUTHORIZED PERSON MAY HAVE ACCESS TO IT. IT IS TO BE KEPT IN A SECURE PLACE AND NOT TO BE LOANED OR REPRODUCED WITHOUT APPROVED AUTHORITY. WHILE THIS YOUR RESPONSIBILITY AND YOU HAVE OBTAINED IT RECEIVED BY YOU, IT IS YOUR RESPONSIBILITY TO PROTECT IT AND NOT TO LOAN IT OUTSIDE THE LIMITS OF THE PROJECT FROM AN UNAUTHORIZED PERSON. ITS STORAGE IN A LOCKED STORAGE YARD OF PRESIDENTIAL PROHIBITED, IT IS NOT TO BE DUPLICATED IF ADDITIONAL COPIES ARE REQUIRED. OBTAIN THE FROM THE RELATED ISSUING OFFICE. ALL PERSONS READING THIS DOCUMENT ARE REQUESTED TO SIGN IN THE SPACE PROVIDED BELOW.

SIGNATURE AND DATE

[illegible]

54-3000-340 (3-57) AEC-GE RICHLAND WASH

(CLASSIFICATION)

DECLASSIFIED

DECLASSIFIED

This document contains information of a confidential nature. It is to be controlled and its contents are to be disclosed only to an authorized person in accordance with the provisions of the Atomic Energy Act of 1954.

This document consists of
4 pages. No. 7 of
25 copies.

DISTRIBUTION

1. R. S. Bell	13. H. C. Rathvon
2. R. A. Connell	14. J. W. Riches
3. R. L. Dickeman	15. R. W. Reid
4. R. E. Dunn	16. O. C. Schroeder
5. O. H. Greager	17. H. G. Spencer
6. A. B. Greninger	18. D. R. Stenquist
7. L. W. Lang	19. J. T. Stringer
8. J. E. McDonald	20. R. E. Tomlinson
9. J. W. McCurry	21. J. H. Warren
10. R. W. McMichael	22. R. M. Watkins
11. W. N. Mobley	23. W. K. Woods
12. Roy Nilson/R. H. Meichle	24. Records Center
	25. Files

Classification Cancelled and Changed To

DECLASSIFIED

By Authority of AM Den.
PR-24, CG-PR-2

August 3, 1964

TO: DISTRIBUTION

By AM Den, D. Hanson 4-19-64
Verified By Gerri Maley, 4-19-64

IPD PRODUCTION PROJECTIONS

The attached tables are intended as an extension of the data that will be used in the forthcoming Production Studies. It considers thorium load substitution for the natural uranium cases previously reported. It is felt that the thorium cases will inevitably become part of the current production cases, and that this information should be available for record and inspection for technical details.

Should there be any disagreement in the data presented, will you kindly call the author immediately. Your thorough analysis will be appreciated.

[Signature]

Principal Engineer-Reactor Process

LWL:ewm

MASTER

DECLASSIFIED

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Table No. 1

Small Reactors

Thorium Loadings (5 ppm U-232 in U-233)

	<u>Nat U Loadings</u>		<u>Blanket Loadings</u>		<u>Full Conversion</u>	
	<u>Forecast</u>	<u>AEC Case</u>	<u>Forecast</u>	<u>AEC Case</u>	<u>Forecast</u>	<u>AEC Case</u>
<u>Power Level</u>	1 960	1 960	1 960	1 960	1 960	1 960
Percent to Nat	85	85	75	75	-	-
E	15	15	25	25	100	100
<u>Operating Efficiency</u>	76.8	73.5	75.1	71.9	68.7	65.8
<u>KMWD to Nat</u>	466.9	446.9	402.9	385.6		
E Spike	60.4	57.8	59.1	56.5	54.1	51.7
E Blanket	22.0	21.1	75.2	72.1	68.8	66.0
E Core					368.7	352.9
Total	<u>549.3</u>	<u>525.8</u>	<u>537.2</u>	<u>514.2</u>	<u>491.6</u>	<u>470.6</u>
<u>Exposure</u> - Nat (MWD/T)	600	600	600	600	-	-
E - (MWD/AT)	790	790	790	790	790	790
Thorium (MWD/AT) Fringe	-	-	1 080	1 080 (1285 g/T)	1 080	1 080
Core -	-	-	-	-	661	661 (135 g/T)
<u>Conversion Ratios - g Pu or U-233/MWD</u>						
Pu Nat	.848	.848	.848	.848	-	-
Pu E - Spike	.694	.694	.694	.694	.694	.694
Blanket	-	-	.683	.683	.683	.683
Core	-	-	-	-	.683	.683
U-233 E Blanket	-	-	.180	.180	.180	.180
Core	-	-	-	-	.189	.189
Leakage	-	-	.017	.017	.017	.017
<u>Tonnage</u> - Nat (tons/yr)	778.2	744.9	671.6	642.7	-	-
E (Spike)	104.3	99.8	74.8	71.6	68.4	65.4
(Blanket)	-	-	95.2	91.2	87.0	83.5
(Core)	-	-	-	-	466.7	446.7
Thorium (Blanket)	-	-	16.7	16.0	15.3	14.6
(Core)	-	-	-	-	51.6	49.4
<u>Production (annual kg)</u>						
Pu - Nat	395.9	378.9	341.7	327.1	-	-
Pu - E (Spike)	41.9	40.1	41.0	39.3	37.5	35.9
(Fringe)	15.6	14.9	51.4	49.2	47.0	45.0
(Core)	-	-	-	-	251.8	241.0
U-233 (Blanket)	-	-	13.5	13.0	12.4	11.9
(Core)	-	-	-	-	69.7	66.7
(Leakage)	-	-	9.1	8.7	8.4	8.0
T ₂	6.3	6.0	-	-	-	-
Total Pu	<u>459.7</u>	<u>439.9</u>	<u>434.1</u>	<u>415.6</u>	<u>336.3</u>	<u>321.9</u>
Total U-233			<u>22.6</u>	<u>21.7</u>	<u>90.5</u>	<u>86.6</u>

DECLASSIFIED

Table No. 2

C Reactor

Thorium Loading (5ppm U-232 in U-233)

	<u>Nat U</u>	<u>Blanket Thorium</u>	<u>Thorium Changeout</u>
<u>Power Level</u>	2 191	2 191	2 191
Percent to Nat	76	66	
E	24	34	100
<u>Operating Efficiency</u>	75.7	74.0	68.0
<u>KMWD to - Nat</u>	460.7	391.2	
E Spike	145.5	112.7	103.5
Blanket		89.0	81.6
Core			359.2
Total	<u>606.2</u>	<u>592.9</u>	<u>544.3</u>
<u>Exposure - Nat (MWD/T)</u>	600	600	-
E	810	810	810
Thorium (MWD/AT) Fringe -		1 080 (1 285 g/T)	1 080
Core -		-	661 (1 351 g/T)
<u>Tonnage - Nat (tons/yr)</u>	767.2	652.0	-
E (Spike)	179.4	139.1	127.8
(Blanket)	-	108.8	100.8
(Core)	-	-	443.5
Thorium (Blanket)	-	19.8	18.1
(Core)	-	-	50.3
<u>Conversion Ratios (g/MWD)</u>			
Pu - Nat	.856	.856	-
E - Spike	.701	.701	.701
Blanket	-	.688	.688
Core	-	-	.688
U-233 - Blanket	-	.180	.180
Core	-	-	.189
Leakage	-	.017	.017
<u>Production - (annual kg)</u>			
Pu - Nat	394.3	334.9	-
E - Spike	102.0	79.0	72.6
Fringe	-	61.2	56.1
Core	-	-	247.1
U-233 - Fringe	-	16.0	14.7
Core	-	-	67.9
Blanket	-	10.1	9.3
Total Pu	<u>496.3</u>	<u>475.1</u>	<u>375.8</u>
Total U-233		<u>26.1</u>	<u>91.9</u>

DECLASSIFIED

Table No. 3

K Reactors

Thorium Loadings (5 ppm U-232 in U-233)

	<u>Regular</u>	<u>Blanket Loading</u>	<u>Core and Blanket</u>
<u>Power Level</u>	4 400	4 400	4 400
Percent - Nat	88	78	-
E	12	22	100
<u>Operating Efficiency</u>	81.0	80.1	78.7
<u>KMWD</u> - Nat	1 144.7	1 003.1	-
E - Spike	156.1	154.4	151.7
Blanket	-	128.5	126.3
Core	-	-	985.5
<u>Exposure</u> - Nat	630	630	-
E	870	870	870
Thorium - Fringe(MWD/AT)	-	686 (878 g/T)	686 (878 g/T)
Core	-	-	386 (902 g/T)
<u>Tons</u> - Nat U	1 817	1 592.2	-
E	179.4	325.1	1 452.3
Thorium (Blanket)	-	41.7	41.0
(Core)	-	-	185.7
<u>Conversion Ratio (g/MWD)</u>			
Pu - Nat	.918	.918	-
Pu - E Spike	.749	.749	.749
Pu - E (Q Support)	-	.749	.749
U-233 Spike	-	.162	.162
Core	-	-	.170
Leakage	-	.009	.009
<u>Production (kg/yr)</u>			
Pu - Nat	1 050.8	920.8	-
E Spike	116.9	115.7	113.6
E Fringe	-	96.2	94.6
E Core	-	-	738.1
U-233 - Fringe	-	20.8	20.5
Core	-	-	167.5
Blanket	-	11.6	11.4
Total Pu	<u>1 167.7</u>	<u>1 132.7</u>	<u>946.3</u>
Total U-233	-	<u>32.4</u>	<u>199.4</u>

DECLASSIFIED

DATE

FILMED

5/31/94

END