DOE/ER/13256-6

CONTINUOUS CHEMICAL REACTION CHROMATOGRAPHY

DOE/ER/13256--6

DE92 015100

PROGRESS REPORT
January 1989 - January 1992
DOE/DE-FG02-84ER 13256

R. Aris and R. W. Carr
Co-Principal Investigators

Department of Chemical Engineering and Materials Science
University of Minnesota
Minneapolis, MN 55455-0132

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

pe

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United State Department of Energy, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumed any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed or represents that its use would not infringe privately owned rights.

CONTINUOUS REACTION CHROMATOGRAPHY

Research Progress (1988-1991)

Introduction

The past three years have been devoted to investigating simulated countercurrent chromatographic moving bed separators (SCMCS) and simulated countercurrent moving bed reactors (SCMCR). These are novel separators and reactors used for separation, or for carrying out a chemical reaction and separation continuously and simultaneously in fixed bed. In the SCMCR and the SCMCS the process aspects of a countercurrent moving bed, in which a stream of solids flows countercurrent to an inert fluid and past a stationary reactant inlet, is simulated by successively switching feed and product take-off streams through a series of inlets located at fixed intervals along a fixed bed or between a series of packed columns. The flow of solids past a fixed feed point, characteristic of countercurrent moving beds, is replaced by motion of the feed past a fixed packed bed. Feed enters a particular column for a fixed length of time, and then is switched to the next column. Product streams are also advanced simultaneously. When the feed point has progressed to the end it is returned to the starting position and the process repeated. The shifting of the feed and the product positions in the direction of fluid flow thus simulates the movement of solids in the opposite direction. The requisite motion between the feed and the bed, which is continuous for true countercurrency, is replaced by periodic, discrete steps in simulated countercurrency. The continuous, steady state operation characteristic of true countercurrency is replaced by periodic transients at each switch of the feed.

The reactor enhances the overall conversion of reactions which are limited either by equilibrium constraints or by the suppression of particular reactants to prevent undesirable side products. The driving force is the simultaneous separation of products from reactants as they are formed. Removing the newly formed products from the presence of the reactants will keep a local equilibrium of the two from forming and enable further conversion of the reactants.

The viability of this reactor rests with its ability to promote an efficient and continuous separation of products from reactants. The necessity of continuous operation suggests countercurrent adsorption. Earlier work evaluating a true countercurrent flow system with a moving solids stream presented doubts as to the scale-up ability of such a process; thus the simulated countercurrent flow design was envisioned. Preferential adsorption of the components of a binary mixture is capitalized upon by setting the rate of the moving-feed port between the elution rates of the two so that their relative movement is away from each other. One component can be removed ahead of the feed point and one can be withdrawn behind the feed, which allows two pure and continuous product streams to be removed from the system.

The development of these devices consisted of two phases. Initially, a simulated countercurrent chromatographic separator was developed to understand and characterize the principles that affect the operation and optimization of the separation aspect of the overall problem. A reaction was included in the second phase of the research which evaluated the

parameters which determine the overall conversion of reactants to products.

The Simulated Countercurrent Moving Bed Chromatographic Separator

The literature surrounding the SCMCS describes two different types of continuous separators. The first is the Sorbex or a Sorbex-like separator which was first developed by UOP some years ago. This mode of operation is characterized by the use of a single carrier to separate a binary liquid mixture and remove two product streams. The other type of separator utilized the same principles to simulate countercurrent flow, namely the discretized movement of the feed point past fixed chromatographic columns at a rate between the elution times of the two components, but unlike the sorbex-mode of operation it uses more than one carrier stream to remove the separate product streams.

Optimization of SCMCS-Column Configuration

Initially, a sorbex-like separator was constructed to separate a binary gas mixture. The experimental apparatus is shown in Figure 1. The design of this separator consisted of four columns where the carrier gas entered the system in the column behind the moving-feed column to sweep all material left behind from the previous switching cycle and add it to the feed gas. The effluent of the feed column is split where part is removed from the system, as the weakly adsorbed component product stream, while the other part is sent on to remove the strongly adsorbed component which trailed the feed by two columns. All inlet and outlet ports are also moved sequentially with the moving-feed port.

The cyclic switching of the feed port produces cyclic concentration profiles within the product streams, as seen in Figure 2. During any given switching cycle the steady-state concentration will rise and fall, but ideally only pure product streams should be removed. Unfortunately, for the separation of propylene from dimethyl ether on Chromosorb 101 two pure product streams were not produced. The strongly adsorbed species, dimethyl ether, was not readily desorbed and remained within the system to deteriorate the purity of the weakly adsorbed component, propylene. Improvement of the purities of the product streams was sought by column configuration modifications. An additional carrier gas stream was introduced to aid in the desorption of the strongly adsorbed component but would not remove all of the adsorbed material when set equal to the main carrier flowrate. An isolated purge gas column was then added to the system directly ahead of the feed column to eliminate residual material. This new column configuration is shown in Figure 3. A typical set of steady-state concentration profiles is presented in Figure 4. Unlike the other experimental configurations, this apparatus produced two very pure product streams.

Optimization of the SCMCS-Number of Columns

The effect of the number of columns was evaluated. The literature presents no optimal number of columns and suggests that as the number of columns is increased the simulated countercurrent separator ought to approach the performance of a true countercurrent separator. Four columns were initially evaluated in the SCMCS. Removal of the purge column produced nearly identical concentration profiles except for an increase in the product impurity levels. If, however, both components were easily desorbed then the purge column would

not be necessary and three columns would be the minimum number to operate a SCMCS.

The effect of additional columns was also evaluated. Four additional columns were added ahead of the feed column. The weakly adsorbed species was now removed four columns ahead of the feed column. The eight column configuration did not improve the separator performance as might have been expected; rather it exacerbated dispersion effects. No advantage is gained by operating the SCMCS with more than four columns for a binary separation. This is consistent with intuition because both components are only present together primarily in the feed column and for part of the switching cycle in the carrier column. Additional adsorbent columns ahead or behind of this point are not utilized to perform a separation.

Optimization of the SCMCS-Effect of Relative Adsorptivity

The separation used for all experimental trials was propylene from dimethyl ether, which had an adsorption ratio of approximately two. Although this was not a particularly difficult separation it was chosen to illustrate the capabilities of the SCMCS. The impact of the effect of adsorption ratio on the operation of the SCMCS was not addressed experimentally but still can be answered via numerical simulation with a mathematical model. Based on the insight gained from the SCMCS experimental work it can be shown that four columns, albeit three columns if no purge column is necessary, remains the optimal number of columns.

The switching time is still set between the breakthrough times of the two components. The weakly adsorbed component will breakthrough the feed column and be withdrawn from the system as a product stream before the strongly adsorbed component will break through. As successive column switchings ensue the two components will continue to move away from each other relative to the moving-feed port. As the adsorption ratios decrease the components will still be moving away from each other but at a slower rate, thus it will merely take longer to achieve steady-state.

The main criteria for obtaining a separation with the SCMCS is the requirement that the switching time is between the breakthrough time of the two components. Defining a breakthrough ratio then as the ratio of switching time to breakthrough time, the criteria then becomes that the breakthrough ratio of the weakly adsorbed component must be greater than one while the breakthrough ratio of the strongly adsorbed component must be less than one. The breakthrough ratio of the strongly adsorbed component must also be greater than one-half. As long as these criteria are met, the separator can be used. The ratio of elution times will change the range of possible switching times and thus the range of attainable breakthrough ratios, but the criteria for operation of the SCCS will still be met.

Optimization of the SCCS-Effect of Breakthrough Ratio

When the operation of the SCMCS reaches steady-state the amount of mass leaving the system during any switching cycle must equal the amount of mass entering the system during any switching cycle; ergo the breakthrough ratio can not have an effect on the amount of material removed. How the material is removed is altered by the breakthrough ratio, namely the height and duration of the concentration bands produced during each switching cycle.

The concentration will be zero for part of the cycle and thus must be greater than the feed concentration for the rest of the cycle. As the breakthrough ratio approaches unity this maximum concentration will increase while the duration of the concentration band will decrease. The opposite is true as the breakthrough ratio moves away from unity; the maximum concentration decreases but the duration increases. This point is illustrated by Figure 5 which shows the column concentration profiles for breakthrough ratios of .6 and .8.

Conclusions for the SCMCS

Use of the simulated countercurrent chromatographic separator led to efficient separations of binary gas mixtures. High purity product streams were formed. The optimal configuration consisted of four columns, where a carrier gas entered the system behind the feed column, an isolated carrier gas entered two columns behind the feed column, and a purge column enters immediately ahead of the feed column. Different binary separations will lead to varied adsorption ratios, but this has no effect on the configuration or number of columns in the SCCS, rather it affects the range of attainable breakthrough ratios. The breakthrough ratio will not affect the amount of material removed during a switching cycle, rather it will alter the concentration profiles that are produced.

The Simulated Countercurrent Moving Bed Reactor

Mathematical models have been developed for two different configurational approaches to the simulated countercurrent moving bed chromatographic reactor. In the first of these, the single column multistage configuration, a single fixed bed having a series of inlets and outlets along its length are considered. The schematic diagram is shown in Figure 6. The mass balance equations are discretized to give the equilibrium stage model. The mass balance equation for the reaction considered is as follows:

$$A(g) \xrightleftharpoons[k_{dA}]{k_{aA}} A_{ads} \xrightleftharpoons[k_b]{k_f} B_{ads} \xrightleftharpoons[k_{aB}]{k_{dB}} B(g)$$

$$\epsilon \frac{\partial C_{ij}^m}{\partial t} + \epsilon u_j \frac{\partial C_{ij}^m}{\partial X} + (1 - \epsilon) k_{ai} (N - n_{Aj}^m - n_{Bj}^m) C_{ij}^m - (1 - \epsilon) k_{di} n_{ij}^m = 0$$

$$\frac{\partial n_{ij}^m}{\partial t} - k_{ai} (N - n_{Aj}^m - n_{Bj}^m) C_{ij}^m + k_{di} n_{ij}^m + \alpha_i (k_f n_{Aj}^m - k_b n_{Bj}^m) = 0$$

where $aA = -1$, $aB = 1$.

The concentration profiles were then obtained from the numerical solution of the mass balance equations by a fourth order Runge-Kutta method. The rate constants used are that of Mesitylene hydrogenation reaction at 190°C. The model predicts 99% product purity and nearly unit conversions. The equilibrium conversion at this temperature is 0.62. Thus, performance comparable to the countercurrent moving bed reactor is predicted.

Differential models have been developed for the multicolumn configuration approaches to the SCMCR. In this approach the partial differential equations governing reactor behavior are being solved by a finite element method with uneven grid points. This method combines

the rapid convergence of the finite elements method with the convenience associated with locating grid points where the solution is important or has large gradients. Nevertheless, the use of this method becomes rather problematic and cumbersome due to the fact that the reactor consists of two sections at which the flow rates are different and to the continuous relocation (book keeping) of these sections introduced by means of the switching procedure.

Figure 7 shows the schematic diagram of a five column configuration. The reactant enters at the top of column 1, the outlet of column 1 enters at the top of column 2. 15% of the outlet flow is collected as product from the bottom of column 2, whereas the rest is being sent to column 3. The outlet of column 4 enters the top of column 1 with the 15% make up feed. Concentration profiles were obtained from the solution of the mass balance equations. Numerical simulations of reactor behavior were carried out for Mesitylene hydrogenation at 190°C, using independently obtained reaction rate constants. The model predicts 99% product purity and conversions around 98%. The results show that the concentration profiles in the individual columns are qualitatively very similar to the predictions of the equilibrium stage model.

Results obtained from the above model of simulated moving bed reactor has been compared with a single column fixed bed reactor. The exit concentration for a fixed bed reactor reaches an equilibrium value, whereas the output concentration from the simulated column results in improved conversion and product purity.

We are currently in the process of finding an analytical solution for a linear, dispersionless simulated countercurrent moving bed chromatographic reactor.

Experimental setup:

The experimental work has been done on the multicolumn configuration since it is more convenient for laboratory studies. Accordingly, such a reactor has been built. The schematic diagram of the experimental setup is shown in Figure 8 and the valving diagram has been shown in Figure 9. The simulated countercurrent moving bed reactor (SCMCR) is a bank of five 1 ft×1/2 in O. D. stainless steel columns connected by 1/8 inch tubing. The last column in the bank is connected to the first, also by 1/8 inch tubing, so that switching of feed and product streams cycles continuously. Switching of the feed injection position is done automatically with Skinner solenoid electric valves. The reactor configuration is very flexible as any number of columns can be added or subtracted without any problem and shows how all the following options are accomplished:

- (a) send the outlet stream to the next column;
- (b) collect product B;
- (c) collect reactant A;
- (d) feed and carrier gas can enter particular column.

All of these are available through the use of twenty five valves with this five column configuration. The feed is mixed constantly with hydrogen and routed to the proper column by the valving. The feed can be switched to another column by simultaneously closing one set of valves and opening another without interruption of the feed flow rate. The product

stream is automatically sampled by an analytical gas chromatograph at specified intervals. The valves are controlled by the IBM PC-XT. The digital output port of the Data Translation board are used with an OPTO solid state relay to control valves. The relays are always used in certain on-off combinations and switching decisions are made before an experiment and entered into the software menu. The relays switch on or off the valves according to they are connected. The reactant is fed to the reactor via a 391 A Sage Instruments syringe pump. The reactor is heated by heating tape wrapped around the column and insulated with glass wool cloth around the tape. The heating tapes are powered by variable resistance variacs. The switching time was set between the elution times of the two components.

Computer control

In the operation of a laboratory SCMCR decisions must be made on the time between successive switches of the feed. Decisions can be made based upon numerical simulations using models, but these are not expected to be highly accurate due to uncertainties in model parameters and any inadequacies of the model. The simultaneous switching of feed and product streams at precisely the correct time, and the rapid acquisition and analysis of data for making the next decision can be best accomplished by computer. For testing model predictions, it would be desirable to determine the time-dependent concentrations. Since switching intervals may be only a few minutes in some cases, many rapid analyses must be done in this time. Computer data acquisition and control is clearly necessary.

A laboratory microcomputer (an IBM PC-XT) is used for data acquisition and process control. Data Translation data acquisition boards (DT 2801) with DT 707 board is used as hardware interface for full data acquisition and control capabilities.

Lab Tech notebook is the software used to manage all operations. Notebook provides the interface between the experimental system and its control by computer. The combination of Notebook with data acquisition hardware board provides an instrumentation system of considerable power and flexibility and helps data acquisition and real time analysis, storage and screen display of experimental data. Notebook software performs data input from the hardware interface boards, data storage to disk files and data display on the computer monitor. With open loop control, the data output function copies data from a waveform file (on a disk) into a buffer at the beginning of the run. The contents of the data file are then transmitted to the hardware interface at a predetermined sampling rate. All these functions are controlled automatically by Notebook and have to be set up to start the run.

Experimental Results:

The catalytic hydrogenation of mesitylene to trimethyl cyclohexane is selected as a test reaction. The catalyst for the reaction is Pt containing 0.74% w/w/ Pt supported on Al_2O_3 . Chromosorb 106 porous polymer adsorbent is being used for chromatographic separations. Preliminary experiments on the hydrogenation of mesitylene have shown that mesitylene adsorbs very strongly on alumina, the adsorbent and support material for the catalyst. The adsorption characteristics were improved somewhat by treating the alumina with a solution of KOH in methanol, but retention times in individual columns were still longer than desired. After searching for several suitable adsorbents we finally decided on Chromosorb 106 for

which adsorbent characteristics were satisfactory.

Experiments performed at 200°C with 4 minutes switching time gives a product purity of 94% and conversion of 82%. A comparison study of the countercurrent moving bed chromatographic reactor (CMCR) and the SCMCR is being done. The reaction and adsorbent system are common to both, permitting similarities and differences to be discerned.

Conclusions:

The mathematical model of the two different configurational approaches to the SCMCR, and the experimental investigation reveal that improved purity can be achieved in SCMCR. Both experiment and numerical simulation show that chemical equilibrium can be shifted to favor the product, and enhance conversion.

Figure 1: multi-column Sorbex-like configuration

Figure 2: Sorbex-like configuration
 $r(A)=1.67, r(b)=.8$

Figure 3: Final column configuration

Figure 4: Concentration profiles with optimal column configuration
 $r(A)=1.5, r(B)=.7$

$r(B) = .6$

$r(B) = .8$

$t = 1t_s$

$t = 2t_s$

$t = 3t_s$

at steady-state:

- the feed concentration is removed for 1/3 of the switching cycle
- 2 times the feed concentration is removed for 1/3 of the switching cycle

Figure 5: Column concentration profiles for breakthrough ratios of .6 and .8

at steady-state: 4 times the feed conc. is removed for 1/4 of the switching cycle

FIG. 6 : Schematic Diagram of Single Column Equilibrium Stage Model

**Fig. 7 : Schematic Diagram of Five Column Configuration
of Differential Multicolumn Model**

FIG. 8 : SCHEMATIC DIAGRAM OF THE EXPERIMENTAL SETUP

Fig. 9 : Valving diagram of five column configuration

Personnel

Co-Principal Investigators

Rutherford Aris spent 100% of full time for one summer month each during 1989, 1990 and 1991. During each academic year (15 Sept. to 15 June) 1989-90, 1990-91 and 1991-92 he spent 10% of full time on the project.

Robert Carr spent 100% of full time for one summer month each during 1989, 1990 and 1991. During each academic year (15 Sept. to 15 June) 1989-90, 1990-91 and 1991-92, he spent 10% of full time on the project.

Graduate Students

Ajay Ray. Ph.D. Candidate. Degree expected in 1992. Experimental and theoretical research on simulated countercurrent moving bed reactors. Thesis currently being written.

Anna Lee Tonkovich. Ph.D. Candidate. Degree expected in 1992. Experimental and theoretical research on simulated countercurrent moving bed separators.

Khalid Alhumaizi. M.S., ChE, 1991. Mathematical modeling and control of countercurrent moving bed separators and reactors.

Publications 1989–1991

1. Published

The Continuous Countercurrent Moving Bed Separator. *AIChE Journal*, **35**, 737 (1989). (B. B. Fish, R. W. Carr and R. Aris)

An Experimental Investigation of the Countercurrent Moving Bed Chromatographic Reactor. *Chem. Eng. Sci.*, **44**, 1773 (1989). (B. B. Fish and R. W. Carr)

The Simulated Countercurrent Moving Bed Reactor. *Chem. Eng. Sci.*, **45**, 2431 (1990). (A. Ray, A. L. Tonkovich, R. Carr and R. Aris)

2. Accepted

Continuous Reaction Chromatography. To be published in the Chromatographic Science Series "Preparative and Production Scale Chromatographic Processes and Applications," by Marcel Dekker. (R. W. Carr)

3. In Preparation

Parametric Sensitivity of the Countercurrent Moving Bed Separator. (B. B. Fish and R. W. Carr)

The Simulated Countercurrent Moving Bed Separator. (B. B. Fish and R. W. Carr)

Design of Simulated Countercurrent Moving Bed Separators (A. L. Tonkovich and R. W. Carr)

4. There will be additional papers on the SCMCR, coming from Ray's thesis, in the very near future.

**DATE
FILMED**

8 / 14 / 92