RECEIVED

JUN 10 1993

OSTI

DOE/CE/23810-11A

**SOLUBILITY, VISCOSITY AND DENSITY
OF REFRIGERANT/LUBRICANT MIXTURES**

Quarterly Technical Progress Report

1 January - 31 March 1993

David R. Henderson

**Spauschus Associates, Inc.
300 Corporate Center Court
Eagle's Landing
Stockbridge, GA 30281**

April 1993

**Prepared for
The Air-Conditioning and Refrigeration Technology Institute
Under
ARTI MCLR Project Number 655-51200**

MASTER *ds*

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

This research project is supported, in whole or in part, by U.S. Department of Energy grant number DE-FG02-91CE23810: Materials Compatibility and Lubricants Research (MCLR) on CFC-Refrigerant Substitutes. Federal funding supporting this project constitutes 93.67% of allowable costs. Funding from non-government sources supporting this project consists of direct cost sharing of 6.33% of allowable costs; and in-kind contributions from the air-conditioning and refrigeration industry.

DISCLAIMER

The U. S. Department of Energy's and the air-conditioning industry's support for the Materials Compatibility and Lubricants Research (MCLR) program does not constitute an endorsement by the U. S. Department of Energy, nor by the air-conditioning and refrigeration industry, of the views expressed herein.

NOTICE

This report was prepared on account of work sponsored by the United States Government. Neither the United States Government, nor the Department of Energy, nor the Air-Conditioning and Refrigeration Technology Institute, nor any of their employees, nor of any of their contractors, subcontractors, or their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed or represents that its use would not infringe privately-owned rights.

COPYRIGHT NOTICE (for journal publication submission)

By acceptance of this article, the publisher and/or recipient acknowledges the right of the U. S. Government and the Air-Conditioning and Refrigeration Technology Institute, Inc. (ARTI) to retain a nonexclusive, royalty-free license in and to any copyrights covering this paper.

INDEX OF RESULTS

<u>Refrigerant/Lubricant Mixture</u>	<u>Page</u>
CFC-12/ISO 32 Naphthenic Mineral Oil	5
CFC-12/ISO 100 Naphthenic Mineral Oil	7
HCFC-22/ISO 32 Naphthenic Mineral Oil	9
HFC-134a/ISO 22 Pentaerythritol Ester Mixed Acid	11
HFC-134a/ISO 32 Pentaerythritol Ester Mixed Acid #1	13
HFC-134a/ISO 68 Pentaerythritol Ester Mixed Acid	15
HFC-134a/ISO 100 Pentaerythritol Ester Mixed Acid	17
HFC-134a/ISO 32 Pentaerythritol Ester Mixed Acid #2	19
HCFC-123/ISO 32 Naphthenic Mineral Oil	21
HCFC-123/ISO 100 Naphthenic Mineral Oil	23
HCFC-123/150 SUS Alkylbenzene	25
HCFC-123/300 SUS Alkylbenzene	27

SOLUBILITY, VISCOSITY AND DENSITY OF REFRIGERANT/LUBRICANT MIXTURES

ABSTRACT

This report presents results for low refrigerant concentration (70, 80, 90 and 100 weight percent lubricant) mixtures of the following fluids:

- CFC-12/ISO 32 naphthenic mineral oil
- HCFC-22/ISO 32 naphthenic mineral oil
- CFC-12/ISO 100 naphthenic mineral oil
- HFC-134a/ISO 22 pentaerythritol ester mixed acid
- HFC-134a/ISO 32 pentaerythritol ester mixed acid #1
- HFC-134a/ISO 68 pentaerythritol ester mixed acid
- HFC-134a/ISO 100 pentaerythritol ester mixed acid
- HFC-134a/ISO 32 pentaerythritol ester mixed acid #2
- HCFC-123/ISO 32 naphthenic mineral oil
- HCFC-123/ISO 100 naphthenic mineral oil
- HCFC-123/150 SUS alkylbenzene
- HCFC-123/300 SUS alkylbenzene

These data have been reduced to engineering form and are presented in the form of a Daniel Chart¹. Equations are given along with statistical measures of goodness of fit.

SCOPE

The broad scope of this research is to measure the solubility (pressure), viscosity and density of the thirty-five refrigerant/lubricant mixtures over composition and temperature ranges as given in Table 1. Low refrigerant concentrations are generally to be measured over 0 to 100°C, with the exception of HFC-32, 125 and 143a, which are to be measured over zero Celsius to slightly below the critical temperature. The experimental data are to be graphically reported in the Daniel Chart format, and mathematical relationships are to be derived.

The entire process of measurement, data reduction, mathematical modeling and plotting has been completed for the low refrigerant concentrations on fluids 1, 2, 3, 5, 6, 7, 8, 10, 13, 14, 15 and 16 (Table 1) and is reported here. Measurements have been completed on several other working fluids and data reduction is in progress.

¹G. Daniel, M. J. Anderson, W. Schmid and M. Tokumitsu, "Performance of Selected Synthetic Lubricants in Industrial Heat Pumps," Heat Recovery Systems, Vol. 2, No. 4, 1982. pp. 359-368.

Table 1: Refrigerant/Lubricant Mixtures Under Study

<u>Refrigerant/Lubricant</u>		<u>Low Refrigerant Concentrations¹ Temp. Range, C</u>	<u>High Refrigerant Concentrations² Temp. Range, C</u>
1.	12/ISO 32 MO ³	0 to 100	-40 to +40
2.	12/ISO 100 MO	0 to 100	-40 to +40
3.	22/ISO 32 MO	0 to 100	-40 to +40
4.	134a/ISO 68 PAG ⁴	0 to 100	-40 to +40
5.	134a/ISO 22 POE-MA ⁵	0 to 100	-40 to +40
6.	134a/ISO 32 POE-MA#1	0 to 100	-40 to +40
7.	134a/ISO 68 POE-MA	0 to 100	-40 to +40
8.	134a/ISO 100 POE-MA	0 to 100	-40 to +40
9.	134a/ISO 22 POE-BA ⁶	0 to 100	-40 to +40
10.	134a/ISO 32 POE-MA#2	0 to 100	-40 to +40
11.	134a/ISO 68 POE-BA	0 to 100	-40 to +40
12.	134a/ISO 100 POE-BA	0 to 100	-40 to +40
13.	123/ISO 32 MO	0 to 100	-20 to +40
14.	123/ISO 100 MO	0 to 100	-20 to +40
15.	123/ISO 32 AB ⁷	0 to 100	-20 to +40
16.	123/ISO 68 AB	0 to 100	-20 to +40
17.	32/ISO 22 POE-MA	0 to 75	-50 to +40
18.	32/ISO 68 POE-MA	0 to 75	-50 to +40
19.	32/ISO 32 POE-BA	0 to 75	-50 to +40
20.	32/ISO 100 POE-BA	0 to 75	-50 to +40
21.	125/ISO 22 POE-MA	0 to 65	-40 to +40
22.	125/ISO 68 POE-MA	0 to 65	-40 to +40
23.	125/ISO 32 POE-BA	0 to 65	-40 to +40
24.	125/ISO 100 POE-BA	0 to 65	-40 to +40
25.	152a/ISO 32 AB	0 to 100	-40 to +40
26.	152a/ISO 68 AB	0 to 100	-40 to +40
27.	152a/ISO 22 POE-MA	0 to 100	-40 to +40
28.	152a/ISO 100 POE-MA	0 to 100	-40 to +40
29.	143a/ISO 22 POE-MA	0 to 70	-45 to +40
30.	143a/ISO 68 POE-MA	0 to 70	-45 to +40
31.	143a/ISO 32 POE-BA	0 to 70	-45 to +40
32.	143a/ISO 100 POE-MA	0 to 70	-45 to +40
33.	124/ISO 32 AB	0 to 100	-40 to +40
34.	124/ISO 68 AB	0 to 100	-40 to +40
35.	142b/ISO 32 AB	0 to 100	-40 to +40

¹Low Refrigerant Concentrations are 0, 10, 20 and 30 weight percent refrigerant.

²High Refrigerant Concentrations are 80, 90 and 100 weight percent refrigerant.

³Mineral Oil

⁴Polyalkylene Glycol (butyl monoether)

⁵Pentaerythritol Ester Mixed Acid

⁶Pentaerythritol Ester Branched Acid

⁷Alkylbenzene

SIGNIFICANT RESULTS

Experimental data is presented in the form of mathematical models and two charts, the first giving the density, the second giving the viscosity and pressure as functions of temperature and composition (Daniel Chart). On the upper portion of the Daniel Chart are isobaric viscosity curves which have been numerically generated from the measured data, together with the knowledge that these fluid systems have two degrees of freedom and the assumption that linear interpolation between measured curves is valid. These charts follow the numbering system given in Table 1 and are thus not consecutively numbered in this report due to fluid availability. Accompanying each set of charts is a table of correlation coefficients and regression constants which are explained below.

The mathematical relationship chosen to represent the viscosity data is the Walther equation, which is

$$\log\{\log(\mu + 0.7)\} = A + B \cdot \log(T) \quad (1)$$

where

log = logarithm to the base 10
 μ = dynamic viscosity, centipoise
A, B = constants found by least squares regression
T = temperature, Kelvin.

Pressure data is represented by quadratic polynomials of the form

$$P = a + b \cdot T + c \cdot T^2 \quad (2)$$

where

P = pressure, kPa
a, b, c = constants found by least squares regression
T = temperature, Kelvin.

Density is given by linear equations of the form

$$\rho = \alpha + \beta \cdot T \quad (3)$$

where

ρ = density, g/cc
 α, β = constants found by least squares regression
T = temperature, Kelvin.

Using equation (3), density at each temperature for which a dynamic viscosity point has been taken (100 points per curve, or one point per degree Celsius) is calculated and divided into the dynamic viscosity to obtain a data file of kinematic viscosity versus temperature. This file is then used to find A_1 and B_1 in the following representation:

$$\log\{\log(\nu + 0.7)\} = A_1 + B_1 \cdot \log(T) \quad (4)$$

where

log = logarithm to the base 10
 ν = kinematic viscosity, centistokes
 A_1, B_1 = constants found by least squares regression
T = temperature, Kelvin.

Correlation coefficients are given as a measure of how well the regression equations fit the data represented. Following usual practice, the correlation coefficient is defined by

$$\sigma = \sqrt{\frac{\Sigma(y_{\text{cal}} - y_{\text{av}})^2}{\Sigma(y - y_{\text{av}})^2}} \quad (5)$$

where

σ = correlation coefficient
 y_{cal} = value calculated from regression equation
 y_{av} = average of measured data
 y = measured data, and
summations run over all data points.

Correlation coefficients are given for all measured data, namely dynamic viscosity, pressure and density. Since kinematic viscosity is a derived quantity, σ is not given for this property, although care has been taken to insure the most accurate representation possible, i.e. creation of kinematic viscosity data files as described above for derivation of the regression equations, as opposed to the two-point or slope-intercept methods.

These rudimentary mathematical models (equations 1 through 4) are presented in the interest of distributing this information in a timely fashion. More sophisticated models will be derived and reported as this project progresses.

Results to date begin on the next page and constitute the body of this report.

**Table 1-1: Solubility, Viscosity and Density Parameters
CFC-12/ISO 32 Naphthenic Mineral Oil**

		70% Oil	80% Oil	90% Oil	100% Oil
Dynamic Viscosity (eq. 1)	σ	0.999	0.999	0.999	0.999
	A	9.47597	10.19943	10.89065	11.38118
	B	-3.86349	-4.10609	-4.33684	-4.49652
Pressure (eq. 2)	σ	0.999	0.999	0.999	
	a	4374.051	2062.376	1305.893	
	b	-37.503	-20.012	-12.199	
	c	0.081	0.048	0.028	
Density (eq. 3)	σ	0.999	0.999	0.999	0.999
	α	1.273	1.198	1.140	1.092
	β	-0.00087	-0.00076	-0.00068	-0.00063
Kinematic Viscosity (eq. 4)	A_1	9.22713	9.83313	10.42120	10.80355
	B_1	-3.76388	-3.95592	-4.14356	-4.25893

Figure 1-1: Density of CFC-12/ISO 32 Naphthenic Mineral Oil

Figure 1-2: Viscosity and Solubility of CFC-12/ISO 32 Naphthenic Mineral Oil

**Table 2-1: Solubility, Viscosity and Density Parameters
CFC-12/ISO 100 Naphthenic Mineral Oil**

		70% Oil	80% Oil	90% Oil	100% Oil
Dynamic Viscosity (eq. 1)	σ	0.999	0.999	0.999	0.999
	A	10.19283	10.60454	10.75274	11.41539
	B	-4.10345	-4.21914	-4.23426	-4.45554
Pressure (eq. 2)	σ	0.999	0.997	0.989	
	a	7167.797	200.889	-2074.689	
	b	-56.843	-9.640	8.938	
	c	0.115	0.034	-0.004	
Density (eq. 3)	σ	0.999	0.999	0.999	0.999
	α	1.267	1.198	1.145	1.095
	β	-0.00083	-0.00073	-0.00067	-0.00062
Kinematic Viscosity (eq. 4)	A_1	9.97378	10.27182	10.33680	10.90908
	B_1	-4.01603	-4.08345	-4.06394	-4.24882

Figure 2-1: Density of CFC-12/ISO 100 Naphthenic Mineral Oil

Figure 2-2: Viscosity and Solubility of CFC-12/ISO 100 Naphthenic Mineral Oil

**Table 3-1: Solubility, Viscosity and Density Parameters
HCFC-22/ISO 32 Naphthenic Mineral Oil**

		70% Oil	80% Oil	90% Oil	100% Oil
Dynamic Viscosity (eq. 1)	σ	0.999	0.999	0.999	0.999
	A	9.25145	9.85591	10.69663	11.38118
	B	-3.79682	-3.99205	-4.27658	-4.49652
Pressure (eq. 2)	σ	0.999	0.999	0.944	
	a	5612.729	814.275	-867.667	
	b	-53.612	-17.142	-0.760	
	c	0.126	0.056	0.017	
Density (eq. 3)	σ	0.999	0.998	0.999	0.999
	α	1.253	1.204	1.144	1.092
	β	-0.00089	-0.00082	-0.00072	-0.00063
Kinematic Viscosity (eq. 4)	A_1	8.91780	9.42202	10.19665	10.80355
	B_1	-3.66083	-3.81331	-4.07022	-4.25893

Figure 3-1: Density of HCFC-22/ISO 32 Naphthenic Mineral Oil

Figure 3-2: Viscosity and Solubility of HCFC-22/ISO 32 Naphthenic Mineral Oil

**Table 5-1: Solubility, Viscosity and Density Parameters
HFC-134a/ISO 22 Pentaerythritol Ester Mixed Acid**

		70% Oil	80% Oil	90% Oil	100% Oil
Dynamic Viscosity (eq. 1)					
	σ	0.999	0.999	0.999	0.999
	A	8.66303	8.69946	9.26892	9.47542
	B	-3.53213	-3.50566	-3.69637	-3.74463
Pressure (eq. 2)					
	σ	0.999	0.999	0.999	
	a	8555.920	4036.226	1075.969	
	b	-69.408	-36.286	-12.344	
	c	0.142	0.081	0.032	
Density (eq. 3)					
	σ	0.999	0.999	0.999	0.999
	α	1.359	1.302	1.256	1.210
	β	-0.00102	-0.00091	-0.00082	-0.00074
Kinematic Viscosity (eq. 4)					
	A ₁	8.47992	8.45970	8.98226	9.17649
	B ₁	-3.46230	-3.41065	-3.58092	-3.62316

Figure 5-1: Density of HFC-134a/ISO 22 Pentaerythritol Ester Mixed Acid

Figure 5-2: Viscosity and Solubility of HFC-134a/ISO 22 Pentaerythritol Ester Mixed Acid

**Table 6-1: Solubility, Viscosity and Density Parameters
HFC-134a/ISO 32 Pentaerythritol Ester Mixed Acid #1**

		70% Oil	80% Oil	90% Oil	100% Oil
Dynamic Viscosity (eq. 1)					
	σ	0.999	0.999	0.999	0.999
	A	8.91339	9.16047	9.30513	9.73910
	B	-3.63169	-3.68527	-3.70202	-3.83538
Pressure (eq. 2)					
	σ	0.999	0.999	0.999	
	a	8501.689	5138.981	1415.953	
	b	-68.163	-43.015	-14.669	
	c	0.138	0.091	0.036	
Density (eq. 3)					
	σ	0.997	0.892	0.999	0.999
	α	1.350	1.290	1.253	1.209
	β	-0.00098	-0.00086	-0.00081	-0.00075
Kinematic Viscosity (eq. 4)					
	A ₁	8.76733	8.94779	9.02865	9.44023
	B ₁	-3.57715	-3.60129	-3.59078	-3.71402

Figure 6-1: Density of HFC-134a/ISO 32 Pentaerythritol Ester Mixed Acid #1

Figure 6-2: Viscosity and Solubility of HFC-134a/ISO 32 Pentaerythritol Ester Mixed Acid #1

**Table 7-1: Solubility, Viscosity and Density Parameters
HFC-134a/ISO 68 Pentaerythritol Ester Mixed Acid**

		70% Oil	80% Oil	90% Oil	100% Oil
Dynamic Viscosity (eq. 1)	σ	0.999	0.999	0.999	0.999
	A	8.80740	9.34660	9.77783	10.44210
	B	-3.55951	-3.73780	-3.86217	-4.07926
Pressure (eq. 2)	σ	0.999	0.999	0.997	
	a	8491.430	5967.728	643.548	
	b	-68.782	-48.594	-10.370	
	c	0.141	0.100	0.030	
Density (eq. 3)	σ	0.999	0.999	0.999	0.999
	α	1.320	1.264	1.216	1.172
	β	-0.00094	-0.00084	-0.00076	-0.00070
Kinematic Viscosity (eq. 4)	A_1	8.59080	9.06684	9.47712	10.09354
	B_1	-3.47458	-3.62526	-3.74003	-3.93750

Figure 7-1: Density of HFC-134a/ISO 68 Pentaerythritol Ester Mixed Acid

Figure 7-2: Viscosity and Solubility of HFC-134a/ISO 68 Pentaerythritol Ester Mixed Acid

**Table 8-1: Solubility, Viscosity and Density Parameters
HFC-134a/ISO 100 Pentaerythritol Ester Mixed Acid**

		70% Oil	80% Oil	90% Oil	100% Oil
Dynamic Viscosity (eq. 1)	σ	0.999	0.999	0.999	0.999
	A	9.51442	9.44837	9.28163	9.60676
	B	-3.83543	-3.76003	-3.64718	-3.72997
Pressure (eq. 2)	σ	0.999	0.999	0.998	
	a	8938.146	4492.305	1761.664	
	b	-71.830	-39.226	-16.893	
	c	0.146	0.085	0.039	
Density (eq. 3)	σ	0.998	0.999	0.999	0.999
	α	1.329	1.274	1.226	1.175
	β	-0.00096	-0.00086	-0.00078	-0.00069
Kinematic Viscosity (eq. 4)	A_1	9.30558	9.17156	9.00600	9.30143
	B_1	-3.75360	-3.64886	-3.53540	-3.60602

Figure 8-1: Density of HFC-134a/ISO 100 Pentaerythritol Ester Mixed Acid

Figure 8-2: Viscosity and Solubility of HFC-134a/ISO 100 Pentaerythritol Ester Mixed Acid

**Table 10-1: Solubility, Viscosity and Density Parameters
HFC-134a/ISO 32 Pentaerythritol Ester Mixed Acid #2**

		70% Oil	80% Oil	90% Oil	100% Oil
Dynamic Viscosity (eq. 1)	σ	0.999	0.999	0.999	0.999
	A	8.61674	9.22623	9.30455	9.46370
	B	-3.50608	-3.70102	-3.69200	-3.72377
Pressure (eq. 2)	σ	0.999	0.995	0.998	
	a	7298.391	184.671	376.180	
	b	-61.329	-10.367	-7.802	
	c	0.129	0.036	0.024	
Density (eq. 3)	σ	0.872	0.999	0.999	0.999
	α	1.358	1.313	1.266	1.218
	β	-0.00099	-0.00092	-0.00083	-0.00075
Kinematic Viscosity (eq. 4)	A ₁	8.46171	9.00929	9.03635	9.19483
	B ₁	-3.44807	-3.61558	-3.58433	-3.61474

Figure 10-1: Density of HFC-134a/ISO 32 Pentaerythritol Ester Mixed Acid #2

Figure 10-2: Viscosity and Solubility of HFC-134a/ISO 32 Pentaerythritol Ester Mixed Acid #2

**Table 13-1: Solubility, Viscosity and Density Parameters
HCFC-123/ISO 32 Naphthenic Mineral Oil**

		70% Oil	80% Oil	90% Oil	100% Oil
Dynamic Viscosity (eq. 1)	σ	0.999	0.999	0.999	0.999
	A	10.65570	10.67383	11.20571	11.38118
	B	-4.30217	-4.27624	-4.45489	-4.49652
Pressure (eq. 2)	σ	0.999	0.999	0.999	
	a	2760.394	2191.630	1165.102	
	b	-19.987	-15.561	-8.391	
	c	0.037	0.028	0.015	
Density (eq. 3)	σ	0.999	0.999	0.999	0.999
	α	1.285	1.221	1.153	1.092
	β	-0.00086	-0.00079	-0.00070	-0.00063
Kinematic Viscosity (eq. 4)	A_1	10.45903	10.33653	10.86300	10.80355
	B_1	-4.22439	-4.13881	-4.31313	-4.25893

Figure 13-1: Density of HCFC-123/ISO 32 Naphthenic Mineral Oil

Figure 13-2: Viscosity and Solubility of HCFC-123/ISO 32 Naphthenic Mineral Oil

**Table 14-1: Solubility, Viscosity and Density Parameters
HCFC-123/ISO 100 Naphthenic Mineral Oil**

		70% Oil	80% Oil	90% Oil	100% Oil
Dynamic Viscosity (eq. 1)	σ	0.999	0.999	0.999	0.998
	A	10.00582	10.61860	10.87689	11.41539
	B	-3.99599	-4.20568	-4.27593	-4.45554
Pressure (eq. 2)	σ	0.999	0.999	0.999	
	a	3202.688	2272.644	1018.503	
	b	-22.898	-16.403	-7.758	
	c	0.042	0.030	0.015	
Density (eq. 3)	σ	0.999	0.999	0.999	0.999
	α	1.283	1.216	1.151	1.095
	β	-0.00085	-0.00077	-0.00069	-0.00062
Kinematic Viscosity (eq. 4)	A_1	9.77456	10.26906	10.45355	10.90908
	B_1	-3.90392	-4.06382	-4.10295	-4.24882

Figure 14-1: Density of HCFC-123/ISO 100 Naphthenic Mineral Oil

Figure 14-2: Viscosity and Solubility of HCFC-123/ISO 100 Naphthenic Mineral Oil

**Table 15-1: Solubility, Viscosity and Density Parameters
HCFC-123/150 SUS Alkylbenzene**

		70% Oil	80% Oil	90% Oil	100% Oil
Dynamic Viscosity (eq. 1)	σ	0.999	0.997	0.999	0.999
	A	11.46558	11.37300	11.41055	11.44333
	B	-4.63799	-4.56942	-4.54302	-4.52918
Pressure (eq. 2)	σ	0.999	0.999	0.999	
	a	2364.792	1702.791	832.516	
	b	-17.311	-12.453	-6.154	
	c	0.032	0.023	0.012	
Density (eq. 3)	σ	0.999	0.999	0.999	0.999
	α	1.247	1.181	1.113	1.060
	β	-0.00087	-0.00079	-0.00071	-0.00065
Kinematic Viscosity (eq. 4)	A_1	11.12973	10.89197	10.80978	10.70913
	B_1	-4.50110	-4.37115	-4.29479	-4.22616

Figure 15-1: Density of HCFC-123/150 SUS Alkylbenzene

Figure 15-2: Viscosity and Solubility of HCFC-123/150 SUS Alkylbenzene

**Table 16-1: Solubility, Viscosity and Density Parameters
HCFC-123/300 SUS Alkylbenzene**

		70% Oil	80% Oil	90% Oil	100% Oil
Dynamic Viscosity (eq. 1)	σ	0.999	0.998	0.999	0.999
	A	11.54181	11.46732	11.66957	12.05281
	B	-4.64742	-4.57749	-4.62395	-4.74176
Pressure (eq. 2)	σ	0.999	0.999	0.999	
	a	2529.820	1640.973	928.530	
	b	-18.421	-12.130	-6.837	
	c	0.034	0.023	0.013	
Density (eq. 3)	σ	0.999	0.999	0.999	0.999
	α	1.253	1.177	1.112	1.056
	β	-0.00088	-0.00078	-0.00071	-0.00064
Kinematic Viscosity (eq. 4)	A_1	11.20939	10.97909	11.05285	11.31162
	B_1	-4.51214	-4.37677	-4.37002	-4.43757

Figure 16-1: Density of HCFC-123/300 SUS Alkylbenzene

Figure 16-2: Viscosity and Solubility of HCFC-123/300 SUS Alkylbenzene

COMPLIANCE WITH AGREEMENT

No significant modifications or deviations from the technical performance of work as described in the contract agreement have been necessary during this reporting period.

PRINCIPAL INVESTIGATOR EFFORT

During this reporting period, Mr. David R. Henderson directed and/or participated in the following activities:

- Project management and laboratory supervision
- Data reduction/mathematical modeling
- Reporting

APPENDIX A

Moisture, total acid number, iron content and copper content have been measured for the lubricants reported in this study. Table A-1 below gives these results. The intent of these measurements is to verify purity of the lubricants prior to study of the viscosity, solubility and density characteristics when mixed with various refrigerants; impurities of the order shown in Table A-1 have negligible effects on these properties. Lubricants were stored in the container as shipped by the manufacturer until used, at which time the values were measured. Storage times ranged from zero to four months.

Table A-1: Lubricant Purity

LUBRICANT	Moisture, ppm	Total Acid Number, mg KOH/g oil	Fe, ppm	Cu, ppm
ISO 32 Naphthenic Mineral Oil	31	0.02	<1	<1
ISO 100 Naphthenic Mineral Oil	42	0.03	<1	<1
ISO 22 Pentaerythritol Ester Mixed Acid	35	<0.01	<1	<1
ISO 32 Pentaerythritol Ester Mixed Acid #1	35	<0.01	<1	<1
ISO 68 Pentaerythritol Ester Mixed Acid	77	0.04	<1	<1
ISO 100 Pentaerythritol Ester Mixed Acid	80	0.06	<1	<1
ISO 32 Pentaerythritol Ester Mixed Acid #2	64	0.04	<1	<1
150 SUS Alkylbenzene	29	0.01	<1	<1
300 SUS Alkylbenzene	29	0.04	4	<1

APPENDIX B - COMMERCIAL IDENTIFICATION

Lubricants tested are commercially available and are:

ISO 32 naphthenic mineral oil: Witco Suniso 3GS
ISO 100 naphthenic mineral oil: Witco Suniso 5GS
ISO 22 pentaerythritol ester mixed acid: Mobil Arctic EAL 22
ISO 32 pentaerythritol ester mixed acid #1: Mobil Arctic EAL 32
ISO 68 pentaerythritol ester mixed acid: Castrol Icematic SW68
ISO 100 pentaerythritol ester mixed acid: Castrol Icematic SW100
ISO 32 pentaerythritol ester mixed acid #2: Castrol Icematic SW32
150 SUS alkylbenzene: Shrieve Chemical Zerol 150
300 SUS alkylbenzene: Shrieve Chemical Zerol 300

END

DATE
FILMED

6 / 30 / 93