**Idaho
National
Engineering
Laboratory**

*Managed
by the U.S.
Department
of Energy*

**EGG-WTD-10035
February 1992**

*RECEIVED
APR 27 1992*

Assessment of Incineration and Melting Treatment Technologies for RWMC Buried Waste

**R. Gelmer
T. Hertzler
R. Gillins
G. L. Anderson**

*Work performed under
DOE Contract
No. DE-AC07-76ID01570*

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

This document contains new concepts or the author(s) interpretation of new calculations and/or measurements; accordingly, EG&G Idaho, Inc. is required by the United States Government to include the following disclaimer:

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights. References herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Assessment of Incineration and Melting Treatment Technologies for RWMC Buried Waste

R. Geimer^a
T. Hertzler^a
R. Gillins^a
G. L. Anderson

Published February 1992

**Idaho National Engineering Laboratory
EG&G Idaho, Inc.
Idaho Falls, Idaho 83415**

**Prepared for the
U.S. Department of Energy
Office of Environmental Restoration and Waste Management
Under DOE Idaho Field Office
Contract DE-AC07-76ID01570**

a. Prepared for EG&G Idaho, Inc., by Science Applications International Corporation, 2300 N. Yellowstone Highway, Idaho Falls, Idaho 83401.

INDEXED

Assessment of Incineration and Melting Treatment Technologies for RWMC Buried Waste

Prepared by:

R. Geimer, SAIC

2/27/92
Date

T. Hertzler, SAIC

2/27/92
Date

R. Gillins, SAIC

2/27/92
Date

Reviewed by:

A. Donaldson

2/29/92
Date

G. Reiman

28 Feb 92
Date

Reviewed and Approved by:

G. L. Anderson

2/27/92
Date

D. E. Shropshire

2/27/92
Date

ABSTRACT

This report provides an identification, description, and ranking evaluation of the available thermal treatment technologies potentially capable of treating the Idaho National Engineering Laboratory Radioactive Waste Management Complex (RWMC) buried mixed waste. The ranking evaluation focused separately upon incinerators for treatment of combustible wastes and melters for noncombustible wastes. The highest ranked incinerators are rotary kilns and controlled air furnaces, while the highest ranked melters are the hearth configuration plasma torch, graphite electrode arc, and joule-heated melters.

EXECUTIVE SUMMARY

This study was completed as part of the Thermal Processing Technology project being conducted by the Waste Technology Development Department of EG&G Idaho, Inc. It was conducted as a follow-up to a separate study conducted by EG&G Idaho, referred to as the Preliminary Systems Design Study (SDS).¹ The SDS provided an overall evaluation of a variety of remediation systems strategies for treatment of buried waste at the Radioactive Waste Management Complex (RWMC) of the Idaho National Engineering Laboratory (INEL). Many of the SDS higher rated process systems strategies were based on retrieving the waste material and processing it into a more stable and acceptable state through some form of thermal treatment.

The SDS study identified an ex situ process strategy that would provide for separation of retrieved waste into a bulk soil waste stream, a bulk metals waste stream, a combustible waste stream, and a noncombustible waste stream. The SDS postulates that the combustible stream would be best treated in an incinerator technology and the noncombustible waste stream (and possibly the bulk soil stream) in a high temperature melter/vitrifier technology. The SDS further determined that this is one of the more desirable of the potential ex situ treatment options.

The purpose of the study reported here is to identify, describe, evaluate, and rank the potential thermal treatment technologies that could be employed in either the incineration of the RWMC combustible waste or the melt processing of noncombustible waste as separate waste streams. An earlier thermal technologies identification and screening study² was used as a starting point. This earlier study had already identified and ranked available thermal technologies against application to bulk average mixed waste and soil streams representative of the RWMC buried wastes. Technologies identified in this earlier study as "not applicable to RWMC buried waste" were not considered further.

This study provides additional consideration of the likely composition of the separated combustible and noncombustible waste streams against which to separately rank the incinerators and melters, respectively. A technology evaluation (scoring) approach was used, similar to that in the earlier study, to score each technology on a list of attributes, then rank order the technologies by total score. Although the same list of attributes was used for both incinerators and melters, each attribute was made up of criteria (sub-attributes or contributing features) which were somewhat different for incinerators and melters (see Tables 3 and 4).

The results of the evaluation and ranking of the incinerators and melters relative to the separated RWMC combustible and noncombustible waste stream applications are shown in Table 1.

It should be noted that the ranking results simply indicate which types of incinerators and melters are likely the best suited for the RWMC waste applications. It is quite possible that any of these technologies could be made to satisfactorily perform the required combustion and melting stabilization functions to some degree given sufficient engineering investment. It is also true that

Table 1. Technology rankings for incinerators and melters.

Incinerators		Melters	
Rotary Kiln	74	Plasma torch hearth	75
Controlled air	73	Graphite electrode hearth	73
Slagging kiln	66	Joule-heated	68
Fluidized bed	62	Molten metal	60
Multiple hearth	53	Fossil fueled hearth	59
Cyclone incinerator	43	Graphite electrode shaft	45
Cyclone melter	33	Slagging kiln	41
Molten salt	24	Microwave	40
		Plasma torch shaft	38
		Cyclone melter	36
		Fossil fueled shaft	24

none of the technologies have been demonstrated fully on the transuranic (TRU)-contaminated wastes and soils which make up the RWMC remediation problem.

In general, it can be stated that commercial incineration technologies for combustible wastes have been well developed over the last two decades. Incinerators are well understood for the type of combustible waste materials applications being considered at RWMC, with the recognition that incineration of TRU-contaminated wastes will require special features to ensure proper contamination and criticality control. Many incineration systems have been constructed and are now operating in hazardous and low-level radioactive waste treatment applications throughout the world.

Melting technologies can be operated such that they pyrolyze or oxidize (combust) an organic waste fraction; however, incinerators have been designed and developed specifically for this purpose, and will function much more effectively than a melter in this regard. There are also other benefits to preprocessing organics in an incineration step and processing the residual inorganics in the melter process to achieve the final waste form. Such a strategy will maintain a minimum offgas volume from the melter process, thus allowing melter afterburners and offgas trains to be small and compact systems. This creates advantages in equipment and facility design, process complexity and controllability, and perhaps even in perception. These advantages disappear rapidly with increasing organic loading in the waste, as offgas system design will then be driven by the offgas products from the processing of the organics. In addition, elimination of organics allows a greater flexibility of operation of the melter process to control chemistry (redox conditions) in the melt.

The melter technology rankings are largely driven by the operating temperature capability, robustness to feedstock variations, limitations of offgas generators, and related industrial applications experience base. The melter technologies have a considerable experience base within the pyrometallurgical industry and the glass industry, which indicate they are generally time-proven technologies for related materials applications. The specific application of the melter technologies for stabilization of radioactive wastes has, however, largely been limited to a few well defined high-level waste glass compositions (using lower temperature joule-heated melters). There are, therefore, many more open questions regarding the applications of melter technologies to the processing of RWMC TRU-contaminated wastes and soils. Other studies have been conducted by EG&G Idaho to more thoroughly evaluate the leading melter technologies (see Reference 4).

CONTENTS

ABSTRACT	iii
EXECUTIVE SUMMARY	v
ACRONYMS	xi
1. INTRODUCTION	1
1.1 Background	1
1.2 Categorization of Thermal Treatment Technologies	2
1.3 Waste Characterization	3
2. EVALUATION	5
2.1 Ranking of Incinerators	5
2.2 Ranking of Melter Technologies	10
3. CONCLUSIONS	16
4. REFERENCES	17
5. BIBLIOGRAPHY	18
Appendix A--Basis for Determination of Waste Stream Components	A-1
Appendix B--Evaluation Methodology	B-1
Appendix C--Evaluation of Technologies	C-1
Appendix D--Technology Summary Descriptions	D-1

TABLES

1. Technology rankings for incinerators and melters	vi
2. Thermal treatment technologies being evaluated in this study	4
3. Scoring explanation for incinerators (combustible wastes)	6
4. Scoring explanation for melters (noncombustible wastes)	7
5. Results from the evaluation of incineration technologies	8
6. Results from the evaluation of melter technologies	11

ACRONYMS

CERCLA	Comprehensive Environment Responses Compensation, and Liability Act
DOE	Department of Energy
EPA	Environmental Protection Agency
INEL	Idaho National Engineering Laboratory
JHM	joule-heated melter
RCRA	Resource Conservation and Recovery Act
RFP	Rocky Flats Plant
RWMC	Radioactive Waste Management Complex
SDS	Systems Design Study
TRU	transuranic
TSA	Transuranic Storage Area

Assessment of Incineration and Melting Treatment Technologies for RWMC Buried Waste

1. INTRODUCTION

1.1 Background

Beginning in 1952, low-level radioactive waste generated at the Idaho National Engineering Laboratory (INEL) was buried in the Subsurface Disposal Area (SDA) at the INEL's Radioactive Waste Management Complex (RWMC). In 1954 the INEL began receiving for burial low-level alpha emitting waste [referred to as alpha contaminated or transuranic (TRU) waste]. The low-level and transuranic wastes were disposed of in shallow pits and trenches until 1972. After this time the practice was stopped and TRU wastes were segregated and stored at the Transuranic Storage Area (TSA) of the RWMC.

Most of the transuranic-contaminated wastes were from the Rocky Flats Plant (RFP) nuclear weapons production/operation and also contained Resource Conservation and Recovery Act (RCRA) hazardous organics and toxic metals. Wastes containing both radioactive and hazardous constituents are designated as "mixed wastes."

In 1989 the INEL was placed on the National Priority List which mandates remediation of the SDA consistent with the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) decision process.

A preliminary systems design study¹ was recently completed by EG&G Idaho, Inc., which provides an overall evaluation of remediation strategies for the RWMC. A large number of strategies were defined and their overall performance was evaluated. Many of the higher-rated strategies were based upon retrieving and processing the waste material into a more stable and acceptable form using thermal treatment process technologies.

One of the specific remediation strategies evaluated in the SDS involves treatment of the waste in the "as-received" condition, i.e., without any segregation of components. An earlier thermal technologies screening study² was performed to rank the capability of various thermal treatment technologies in processing the "as-received" (bulk average) waste composition.

The purpose of the present study is to identify and evaluate potential thermal treatment technologies for the SDS strategy in which the waste materials are assumed to be separated into a bulk soil waste stream, a bulk metals waste stream, a combustibles waste stream, and a noncombustible waste stream. In particular, this study examines the available incineration

technologies for the combustible waste stream, and the available melter/vitrifier technologies for the noncombustible waste stream (which may include some portion of the TRU-contaminated soils waste stream).

This study proceeds in a manner similar to the thermal technologies screening study (see Reference 2). Thermal technologies previously identified as "not applicable to RWMC buried waste" in that study are not considered further. A technology evaluation (scoring) approach is used similar to that of the earlier study, but modified appropriately for considering incinerators and melters for separate combustible and noncombustible waste streams, respectively.

1.2 Categorization of Thermal Treatment Technologies

Thermal treatment technologies are defined as processes that utilize heat energy to physically and/or chemically transform a waste material into a less hazardous form (less toxic, less ignitable, less reactive, less mobile, etc.). Thermal processes can be categorized by process temperature, primary waste types treated, configurations, etc. Low temperature thermal process technologies are typically referred to as thermal desorbers or roasters. They are intended to volatilize (evaporate) and, thus, "desorb" or separate the hazardous organics from the waste material. The desorbed organics may then be incinerated in a separate process step. Although they may at some point be of interest in an overall thermal treatment system for RWMC wastes, the low temperature desorber will not be considered further in this study.

High temperature processes are typically aimed at pyrolyzation or combustion of hazardous organics, or melting/vitrification for stabilization of hazardous noncombustibles (toxic metals, etc.). For the purposes of this study, high temperature processes will be categorized either as incinerators or melters.

Incineration technologies will be defined as those technologies that were principally designed for the treatment of moderate to highly combustible wastes (and thus high heat release rates). Incineration provides substantial volume reduction through bulk organic material destruction, and provides for the chemical transformation of hazardous organic materials. Incinerators are devices that have been specifically designed to oxidize (combust) the organic fraction of the waste, leaving a largely inert residual (ash), generally without regard to the physical or chemical form of that residual. An incinerator can serve to prepare waste material for subsequent feed to a melter process.

Melter technologies will be defined as those high temperature furnaces that have been specifically designed to alter the chemical and/or physical form of the material by means of creating a molten intermediate product in order to change the waste form into a highly leach-resistant final waste form for permanent disposal. Such technologies, while also being capable of pyrolyzation or combustion of some amounts of organic materials, are generally intended for use in treating (stabilizing) noncombustible materials as a glass/ceramic slag product.

Table 2 displays the thermal technologies being evaluated in this study, grouped into categories based on the waste type they were primarily designed to process. The slagging kiln and cyclone melter technologies are two technologies that will be evaluated in both categories. These technologies are adaptations of an incineration process, and are thus designed primarily to accept and treat combustible waste material. They can, however, also create a molten product (slag or vitrified ash) to improve the stability of the residual solid material, and thus partially fit the melter definition as well. A description of each of the technologies considered is provided in Appendix B.

1.3 Waste Characterization

In order to evaluate a thermal process for treatment of RWMC buried waste, a description of the separate waste streams to be treated is required. Appendix A provides a description of the RWMC wastes and defines waste streams for the incinerator and melter evaluations consistent with the top-level screening nature of this study.

The waste feed stream for the evaluation of incinerator technologies is basically determined to consist of typical combustible waste materials (paper, plastic, wood, cloth, cardboard, rubber, and oil), but also possibly organically contaminated silicate and nitrate sludges, inorganic aqueous sludges for a dewatering step, any soil heavily contaminated with organic solvents, and some tramp metals. The bulk metals and soil will have been separated out for separate treatment.

The waste feed stream for evaluation of the melter technologies is determined to consist of the residual ash from the incinerator process (including soils and tramp metals), the Rocky Flats Plant sludges, a fraction of the soils not sent to the incinerator, brick, concrete, and glass wastes.

Table 2. Thermal treatment technologies being evaluated in this study.

Incinerators	Melters
Rotary kiln	Fossil fueled hearth
Controlled air	Plasma torch hearth
Fluidized bed	Graphite electrode hearth
Molten salt	Fossil fueled shaft
Cyclone	Plasma torch shaft
Multiple hearth	Graphite electrode shaft
Slagging kiln	Joule-heated melter
Cyclone melter	Molten metal bath
	Microwave
	Slagging kiln
	Cyclone melter

2. EVALUATION

In order to evaluate and rank order the different thermal technologies within each of their categories, a standard set of ranking criteria was defined. For the purpose of this study, the basic evaluation methodology advanced in Reference 2 was used and modified for the specific concerns of this study. That methodology involved the definition of a number of characteristics, or attributes, that are important when considering application of a particular thermal treatment process. The technologies were assessed on their performance with respect to these attributes, and a relative numerical score assigned. Individual attribute scores are further assigned a weighting factor based on the relative importance of that attribute. Total scores of the technologies were compared to rank order, highest being most suitable. Appendix B provides details on how this evaluation strategy was defined. A separate criteria matrix was established for each of the two technology categories to account for these differences. These matrices are displayed in Tables 3 and 4.

Appendix C provides a detailed discussion of the performance of each of the technologies as it was evaluated against the specific criteria which define each attribute. The performance rating of incinerators is presented first, followed by the rating of melter technologies. Within each treatment category, the evaluation discussion is organized by attribute. This allows a ready comparison of the performance of one technology relative to the others for a given particular attribute. The results of the ranking evaluations are presented in the remainder of this section.

2.1 Ranking of Incinerators

Table 5 is a summary of the scores assigned for each attribute for each of the incineration technologies. These results indicate a wide range of applicability of the various incineration processes that are available. Several of the technologies were rated as having a high potential for their use in treating the RWMC combustible waste. Since there appears to be a very close rating among the top four rated technologies, no one technology stands out as the obvious best choice.

The two incineration technologies that appear to have the highest potential for successful application to combustible waste streams at the RWMC are the rotary kiln and the controlled air incinerators. Each has advantages and disadvantages in differing areas.

The rotary kiln is by far the most versatile incineration technology, and will be able to accept virtually any material that can be introduced as a feed, including large fractions of noncombustibles. Whole intact drums of waste can be acceptable feed, as is routinely done in many large commercial rotary kiln applications. Rotary kilns have been used in many site restoration projects similar to the RWMC remediation, involving the incineration of organic

Table 3. Scoring explanation for incinerators (combustible wastes).

Wt.	Attribute	Category	Score	Description
15	Level of development and availability (LDA)	Development stage	1	Demonstration phase
			2	Operational phase
		Tested on waste type	0	No
			1	Yes
		Commercial availability	0	Not commercially available
			1	Commercially available
		Time proven	0	Not time proven
			1	Time proven
30	Versatility (VRSL)	Fraction applicable	1	Limited applicability
			2	Applicable to most of waste
			3	Applicable to all waste types
		Screening requirements	0	High
			1	Low
		Pretreatment requirements	0	High
			1	Low
10	Residual solid product (RSP)	Org. destr.	1	Low burnout
			2	High burnout
		Handling	0	Complex handling considerations
			1	Moderate handling considerations
			2	Minor handling considerations
		Volume reduction	0	Low volume reduction potential
			1	High volume reduction potential
15	Effluents (EFLT)	Volume	1	High volumes
			2	Low volumes
		Particulate	0	High particulate generation
			1	Low particulate generation
		Other considerations	0	Extensive offgas considerations
			1	Moderate offgas considerations
			2	Few offgas considerations
25	Operational considerations (OPS) (Divide score by 2)	Complexity	1	Highly complex process
			2	Moderately complex process
			3	Simple process
		Health and safety	1	Extensive considerations
			2	Moderate considerations
			3	Few considerations
		Maintenance	0	High maintenance reqs.
			1	Moderate maintenance reqs.
			2	Low maintenance reqs.
		Throughput	0	Low potential
			1	Moderate potential
			2	High potential
5	Cost	Capital	1	High
			3	Moderate
			5	Low

Table 4. Scoring explanation for melters (noncombustible wastes).

Wt.	Attribute	Category	Score	Description
10	Level of development and availability (LDA)	Development stage	1	Demonstration phase
			2	Operational phase
		Demonstrated on waste	0	No
			1	Yes
		Commercial availability	0	Not commercially available
			1	Commercially available
		Time proven	0	Not time proven
			1	Time proven
20	Versality (VRSL)	Waste exclusion	1	Some fraction of waste N/A
			2	All waste acceptable
		Pretreatment requirements	0	High
			1	Low
		Feed variability	0	Presents a concern
			1	No concern apparent
		Upper temperature range	0	Relatively lower temperatures
			1	Relatively higher temperatures
30	Residual solid product (RSP)	DRE potential	1	Low/unknown
			2	High/demonstrated
		Chemistry control	0	Tends to be difficult
			1	Tends to be easy
		Favorable leach data	0	Doesn't exist
			1	Exists
		Volume reduction	0	Low tendency
			1	High tendency
15	Effluents (EFLT)	Volume	1	High volumes
			2	Low volumes
		Particulate	0	High particulate generation
			1	Low particulate generation
		Other considerations	0	Extensive offgas considerations
			1	Moderate offgas considerations
			2	Few offgas considerations
20	Operational considerations (OPS) (Divide score by 2)	Complexity	1	Highly complex process
			2	Moderately complex process
			3	Simple process
		Health/safety	1	Extensive considerations
			2	Moderate considerations
			3	Few considerations
		Maintenance	0	High maintenance reqs.
			1	Moderate maintenance reqs.
			2	Low maintenance reqs.
		Throughput	0	Low potential
			1	Moderate potential
			2	High potential
5	Cost	Capital	1	High
			3	Moderate
			5	Low

Table 5. Results from the evaluation of incineration technologies.

	Wt.	Rotary Kiln	Controlled Air	Fluidized Bed	Molten Salt	Cyclone	Multiple Hearth	Slagging Kiln	Cyclone Melter
LDA	0.15	5	5	5	1	4	3	4	3
Devl.		2	2	2	1	2	2	2	2
Tested		1	1	1	0	0	0	1	0
CA		1	1	1	0	0	0	1	1
TP		1	1	1	0	1	1	0	0
VRSL	0.3	5	3	2	2	2	3	5	2
Frac		3	2	2	1	2	2	3	2
Scr		1	0	0	0	0	1	1	0
Pre-Tr		1	1	0	0	0	0	1	0
RSP	0.1	4	4	4	2	3	3	4	3
Org		2	2	2	2	1	1	2	1
Han		1	1	1	0	1	1	2	2
VR		1	1	1	0	1	1	0	0
EFFL	0.15	2	4	4	5	3	3	3	2
Vol		1	2	2	2	2	1	2	2
Part		0	1	0	1	0	1	1	0
Other		1	1	2	2	1	1	0	0
OPS (div/2)	0.25	3.5	4	3.5	2	2.5	3.5	2.5	2.5
Comp		3	3	2	1	2	2	1	1
H&S		1	2	2	2	2	2	2	3
Main		1	2	1	1	1	1	0	0
Thrpt		2	1	2	0	0	2	2	1
Cost	0.05	3	5	5	1	3	3	1	1
TOTAL	1.00	4	3.9	3.5	2	2.7	3.1	3.6	2.3
NORMALIZED		74	73	62	24	43	53	66	33

contaminated soils, sludges, and bulk combustible and inert materials. There are some drawbacks, however. Rotary kilns rate low in the area of effluent control, since they are high air-volume, high-particulate processes. Operationally, they are somewhat less desirable, mostly due to concerns with the rotating vessel and the special seals that are required. New seal designs are being developed to help minimize these concerns.

The controlled air incinerator addresses some of the concerns of the rotary kiln. Controlled air incinerators are designed specifically for the ability to use low air volumes and velocities in the primary chamber and, thus, are low-particulate generators. Controlled air incinerators rate well in the area of effluent control and are the most predominant technology in use presently for radioactive waste processing. Their primary drawback is in the area of versatility and feed preparation. For a combustible waste feed of strictly bulk organic material, the controlled air incinerator is superior. However, little is known about their ability to process soils and sludges, as other incinerators are usually chosen for those types of applications. It should be technically feasible to process soils and sludges in a controlled air incinerator, particularly because of the more versatile ash handling designs that are now available. Because of the advantages in offgas concerns, process simplicity, and overall performance of the technology, the ability to accept a more variable feed should be investigated more closely.

The slagging kiln rates somewhat lower than the rotary kiln and controlled air, but still rates relatively well. In fact, many of the advantages of the rotary kiln are obviously applicable to the slagging kiln as well, such as the versatility of feed acceptance. The one additional advantage the slagging kiln has is that the solid residual it produces is a vitrified product. It is not likely that the slagging kiln will produce the quality of product that will be required for ultimate disposal (see the melter discussion below); but, there may be an intermediate handling advantage to be gained in providing a more stable feed material for a subsequent melter process. It needs to be determined whether this factor is significant enough to outweigh the additional operational concerns that use of this technology could bring about.

The fluidized bed is down-rated primarily based on its lack of versatility for the acceptance of feed material. However, fluidized bed incinerators have some characteristics that may warrant further evaluation as a technology for this application. The high silica content of the INEL soil means that it should make an excellent fluid bed material. The thermal efficiency of the process and its turbulent mixing and abrading action will provide very high carbon burnout and promote homogeneity of the product, benefiting feed to the melter process. The residual product is a dispersible ash; however, the nature of the material, having been abraded to a fine, fluidizable state, will open the possibility of transport to the next process step via totally sealed, double walled, pneumatic transport systems, providing excellent containment. Unlike the rotary kiln and controlled air incinerators, which depend on maintaining a negative pressure inside the primary chamber to prevent out-leakage at seals, the fluidized bed process vessel is designed as a positive pressure-sealed device. The fluidized bed may then be less susceptible to leakage due to positive pressure excursions caused by nonuniform rates of combustible feedstocks. Finally, the process thermal efficiency provides for operation at lower temperatures, minimizing NO_x formation and metal volatilization. This, together with the in-bed scrubbing of HCl and the reduced air

volumes required, lead to some significant advantages in effluent control. Thus, the fluidized bed technology should be considered, focusing on methods and developments for overcoming feed versatility drawbacks.

The multiple hearth technology is not rated as a high contender for application, and appears to present no real advantages. The staged design of the multiple hearth technologies is most effective for drying large quantities of high moisture materials, such as the sewage sludges they were originally designed to treat. Its versatility is also somewhat limited by its feed requirements. The complex moving components of the rabble arm system will require frequent maintenance. The technology has never been applied for incinerating high heating value materials. Probably the most telling fact concerning the multiple hearth is that it is no longer being put into service, but is instead being replaced by other more versatile technologies. The multiple hearth should not be considered for application at the RWMC.

The cyclone melter and cyclone incinerator technologies rate moderately in most of the attributes, offering no real advantage in any category. The only real plus for the cyclone melter in this application is that it can, depending upon slagging temperature, produce a residual solid product that is partially vitrified, and thus easier to handle. However, this is not believed significant enough at this point to make up for the other disadvantages. The most restrictive problem is that the feed material pretreatment requirements will be restrictively high. In fact, it is questionable whether the bulk combustible components can be adequately prepared for feed, since the feed has to be size reduced to a material that is fluidizable by a gas stream. Certainly, tramp metals are a problem. These technologies are designed for use in treating gasses, liquids, and small particle size homogeneous solid streams, and thus are not readily applicable for the wide range of bulk heterogeneous solid materials they would have to process at the RWMC. A further more detailed evaluation of the cyclone melter is provided in Reference 3.

The molten salt furnace system is rated as the lowest overall incinerator/oxidation technology. While the molten salt process excelled in the gaseous effluent evaluation, there are a number of other concerns that cause its low rating. The molten salt technology is a relatively new technology in the waste treatment area, and little is known about its long-term effectiveness as a waste processing technology on an operational scale. The molten salt process also rated low in versatility, having significant waste pretreatment and screening requirements, and limited applicability for the waste being considered. Molten salt technology is being developed for combustible materials processing and does not handle high volumes of inerts well. Overall, the molten salt process does not appear to be an effective technology for buried waste treatment. Further more detailed evaluation of the molten salt process is provided in Reference 3.

2.2 Ranking of Melter Technologies

The results of the evaluation of melters is presented in Table 6. The electro-technologies are more desirable than the fossil-fueled technologies for radioactive waste processing for several

Table 6. Results from the evaluation of melter technologies.

	Wt.	Fossil			Plasma			Graphite			Fossil			Plasma			Graphite		
		Fueled	Hearth	Melter	Torch	Hearth	Melter	Electrode	Hearth	Melter	Fueled	Shaft	Melter	Torch	Shaft	Melter	Electrode	Shaft	Melter
LDA	0.10		3		2	4		4			3			2			3		
Devl.		2						2			2			1			1		
Demo		0			1			1			0			1			1		
CA		1			1			1			1			0			1		
TP		0			0			0			0			0			0		
Ver	0.20		5		2	5		5			2			4			4		
Waste Ex		2			2			2			2			2			2		
Pre-T		1			1			1			0			0			0		
Feed Var		1			1			1			0			1			1		
Temp Rg		1			1			1			0			1			1		
RSP	0.30		3		2	5		4			1			2			2		
Metal		2			2			2			1			1			1		
Chem		1			1			1			0			0			0		
Leach		0			1			0			0			0			0		
VR		0			1			1			0			1			1		
EFFL	0.15		2		2	3		3			2			3			3		
Vol		1			2			2			1			2			2		
Part		0			1			1			0			1			1		
Metals		1			0			0			1			0			0		
NOx		0			0			0			0			0			0		
OPS	0.20		3		2	2.5		3.5			2.5			2			3		
Comp		3			2			2			2			1			1		
H&S		1			1			2			1			1			2		
Main		1			0			1			1			0			1		
Thrpt		1			2			2			1			2			2		
Cost	0.05		5			3		3			3			1			1		
TOTAL	1.00		3.4			4		3.9			2			2.5			2.8		
NORMALIZED			59			75		73			24			38			45		

Table 6. (continued).

	Wt.	Joule- Heated Melter	Slagging Kiln	Cyclone Melter	Molten Metal	Microwave Melter
LDA	0.10	4	4	3	3	1
Devl.		2	2	1	2	1
Demo		1	1	1	0	0
CA		1	1	1	1	0
TP		0	0	0	0	0
Ver	0.20	3	4	2	5	2
Waste Ex		1	2	1	2	1
Pre-T		1	1	0	1	0
Feed Var		1	1	1	1	1
Temp Rg		0	0	0	1	0
RSP	0.30	4	2	3	3	2
Metal		2	1	1	1	1
Chem		1	0	0	1	1
Leach		1	1	1	0	0
VR		0	0	1	1	0
EFFL	0.15	5	2	2	3	5
Vol		2	1	1	2	2
Part		1	0	0	1	1
Metals		1	0	1	0	1
NOx		1	1	0	0	1
OPS	0.20	3	2.5	2.5	3	3.5
Comp		2	1	2	2	3
H&S		2	1	2	2	3
Main		1	1	1	0	1
Thrpt		1	2	0	2	0
Cost	0.05	3	1	1	3	1
TOTAL	1.00	3.7	2.7	2.5	3.4	2.6
NORMALIZED		68	41	36	60	40

reasons. The small volume of offgas expected from processing inert waste is desirable. Using a fossil-fueled technology to provide process heat to the inert waste will generate a much larger volume of offgas than would otherwise have to be handled and treated. Based on this larger offgas volume and velocity, particulate entrainment and carryover can be expected to be much higher as well. Process equipment will also have to be sized much larger for given throughput. In addition, fossil-fueled technologies rely upon combustion to create heat and, therefore, are limited to the combustion flame temperature as the upper temperature they can attain. Fluxing agents must be used to lower melting temperatures and slag viscosity characteristics. Oxygen enrichment could help obtain higher temperatures, but this creates additional operational complexity and additional cost.

Three of the technologies appear to be superior in the most important attributes, thus causing these technologies to achieve the highest overall ratings. These are the hearth configured electro-technologies, both plasma torch and graphite electrode arc melters, and the joule-heated melter technology.

There is little difference in the evaluation of the plasma/arc heated hearth technologies, which is expected based on their similarities in concept, design, and operation. The only apparent differences are in the slightly higher desirability of the graphite electrode process from an operational reliability/availability standpoint, offset by its apparent lack of leachability data from testing. The former relates to the degree of frequency of maintenance required to replace electrodes in the plasma torch (every 100 to 200 hours of operation) and the operational concerns involving the potential release of the torch coolant into the molten bath. As for the latter, there appears to be a lack of reported leaching data to confirm the potential characteristics of the slag product from the graphite system. However, it is anticipated that leachability characteristics of the product should prove to be as favorable as those of the product from the plasma torch system. When demonstrated, this will increase the rating for the graphite electrode system. For the most part, at the level of detail of this study, there is little discernable difference between the plasma torch and the graphite electrode hearth melter systems.

The third technology identified as having the highest potential for addressing the needs of a melter process for the RWMC inert waste is the joule-heated melter (JHM) process. This technology is probably the most mature melter technology with respect to radioactive waste processing, having been developed extensively as part of the high-level waste program. In addition, the effluent control inherent in the JHM process (minimal offgas, low particulate, and lower metals volatilization and NOx formation potential due to lower operating temperature) adds to the positive rating. The demonstrated ability of the system to produce a desirable end product is a plus.

On the downside, the relatively lower temperature capability of the existing JHM process detracts from its versatility. Higher melting point materials will present problems. For example, tramp metals are not readily processed in the melter, and are actually best left excluded from the feed. The lower temperature also requires the addition of a significant quantity of fluxing agents to

reduce the melt temperature when a high quantity of silica and alumina is present, as is the case for the INEL soil. This will hamper the ability to control the process chemistry, and will significantly add to the overall final disposal volume. Finally, the lower operating temperature leads to reduced throughput potential, as the rate of heat transfer to the feed material largely determines throughput potential. Currently planned developments will focus on some of these drawbacks.

The molten metal bath technology, which relies upon a molten metal pool to effect processing, represents a variation of the discussed hearth technologies, which intend to operate with slag as the molten pool rather than metal. Thus, many of the same advantages of these systems also apply to a molten metal process. The molten metal pool may have an advantage in providing a reservoir for tramp metals in the feed material and may provide a very effective system for transfer of heat to the feed materials. The potential for an accidental feed of noncombustible liquids, particularly water, below the molten surface raises the concern of a vapor explosion; the possibility for such an occurrence, although small, would have to be evaluated. There appears to be a lack of reported leaching data to confirm the potential characteristics of the slag product from the molten metal system. However, it is anticipated that leachability characteristics should prove to be similarly favorable to those of the plasma torch system. In general, little information is available to provide a sufficient evaluation of this option, and perhaps some further study may be warranted.

Of the electro-technologies, the shaft (or cupola) configuration technologies rate low, with not a great deal of variation between the plasma torch or graphite electrode heated systems. One reason for their low rating is that their stage of development in waste treatment applications is not as advanced as other technologies. In addition, shaft based configuration melter technologies have proven to have some greater operational concerns than the other processes related to the difficulties in maintaining proper waste densities in the column, the potential for the offgas to "channel" as it progresses through the waste feed, and the inherent potential for the waste material to "bridge" in the furnace. All of these create highly undesirable situations.

Most important, however, is that control of the residual solid product from the shaft melters is very difficult. The product is only controllable based on what is fed at the beginning of the travel of the waste down the shaft, which entails an approximation of the expected chemistry upon its entry into the process zone. The short residence time of the material in the process zone inhibits achieving homogeneity of the slag product. There is also little control of the fate of bulk metals in the feed material. Since the production of an optimum residual product, which is the primary function of the melter process, is the most important consideration in this evaluation, this significantly affects the shaft furnace rating.

The slagging incinerator technologies, slagging kiln and cyclone melter, are also rated low when considered as melter technologies. The fact that they are fossil-fueled technologies leads to increased offgas system concerns, as discussed previously. The slagging ability of each process is limited to lower temperature melting by maximum flame temperatures and heat transfer efficiency. This also requires significant quantities of fluxing materials to achieve a molten product, thus limiting versatility

and increasing waste volumes. In addition, slag chemistry is more difficult to control, again based on up-front estimation of the waste characteristics, prefeeding of estimated quantities of chemistry control material, and, particularly in the case of the cyclone melter, very short residence times to effect waste mixing and homogeneity. In addition, feed pretreatment sizing requirements ($<1/4$ in. dia) are further limiting in the case of the cyclone melter.

The microwave melter technology is also not rated readily applicable for the application being considered. The technology rated well in the areas of effluent control and operational considerations, based on the ability to totally enclose the process in a glovebox and control that environment. However, the technology is determined to be relatively inferior in several of the key evaluation ranking attributes. It is a relatively new process and little is yet determined about its long-term performance. It is not a versatile technology, having been designed specifically for treatment of sludges. Temperatures achievable are limited, which further limits versatility. Even more important, the residual product that results from the technology is inferior relative to the product from the other technologies. There is little driving force to promote mixing and homogeneity, leading to variability in the product. In fact, some data show that the process produces stratified layers having differing physical characteristics. Finally, there is no available data on the control of leachable metals from the residual product.

Further more detailed evaluation studies related to the plasma torch, arc melter, and joule heated melter technologies are in progress and will be reported in Reference 4. More detailed evaluations of the microwave melter, molten metal melter, and fuel fired torch melter are provided in Reference 3.

3. CONCLUSIONS

A leading strategy for the remediation of the buried TRU waste at the RWMC is to retrieve the material and effect some form of segregation of the waste components to optimize treatment. A particularly attractive treatment strategy is to use an incinerator to process the hazardous and bulk organic fraction of the waste, and to use a melter process to provide the high quality final waste form that is required for noncombustible mixed TRU residuals. Both technologies have been designed for these specific purposes and should perform effectively with a high probability of success in these applications.

Melting technologies can be operated such that they oxidize an organic waste fraction; however, incinerators have been designed and developed specifically for this purpose, and will function much more effectively than a melter in this regard. There are also other benefits to preprocessing organics in an incineration step and processing the residual inorganics in the melter process to achieve the final waste form. Such a strategy will maintain a minimum offgas volume from the melter process, thus allowing melter afterburners and offgas trains to be small and compact systems. This creates advantages in equipment and facility design, process complexity and controllability, and perhaps even in perception. These advantages disappear rapidly with increasing organic loading in the waste, as offgas system design will then be driven by the offgas products from the processing of the organics. In addition, elimination of organics allows a greater flexibility of operation of the melter process to control chemistry.

In general, incineration technologies have been well developed over the last two decades and are well understood technologies for the application being considered at the RWMC. Many incineration technologies have been constructed and are now operating in hazardous waste service throughout the U.S., and many are in use for remediating hazardous waste sites. Clearly, incineration is a remediation strategy that should be seriously considered as an alternative for the RWMC project. Several technologies, including the rotary kiln, controlled air, slagging kiln, and fluidized bed, are acceptable potential candidates for processing the materials being considered. The available data on these technologies should be evaluated in greater detail to determine which technology will provide the best alternative for application in the RWMC remediation project.

Of the melter technologies, the electrically-powered processes are the most desirable. Of these, the processes that appear to have the highest potential for successful application are the graphite electrode plasma arc technology, the plasma torch technology, and the joule-heated melter. Each of these technologies has a high potential to accept a wide range of waste materials and process them into a residual vitrified solid product that will meet or exceed the stringent requirements for product quality, integrity, and control of leachability. Near-term efforts should focus on demonstrating the capabilities to ensure they will function as intended, and developing these technologies as necessary so they can be fully adaptable for treatment of TRU containing material.

4. REFERENCES

1. J. L. Mayberry, F. Feizollahi, J. C. Del Signore, and W. J. Quapp, "Preliminary Systems Design Study Assessment Report," EGG-WTD-9594, July 1991.
2. "Thermal Processes Evaluation for RWMC Wastes," EGG-WTD-9449, January 1991.
3. J. Batdorf, R. Gillans, G. Anderson, "Selected Furnace Technology Assessments for RWMC Wastes," EGG-WTD-10036, February 1992.
4. A. Donaldson, R. Carpenedo, and G. Anderson, "Melter Development Needs Assessment for RWMC Buried Waste," EGG-WTD-9911, February 1992.

5. BIBLIOGRAPHY

"Arc Pyrolysis Technology," Electropyrolysis Inc., Wayne, PA, 1990.

Armstrong, Katherine M. et al., "Joule-Heated Glass Furnace System for the Incineration of Low-Level Radioactive Wastes," Monsanto Research Corp., Mound Laboratory, Report No. MLM-3018, 1987.

"Ausmelt Designers and Suppliers of Sinosmelt Smelters" Corporate brochure, Ausmelt Pty. Ltd., P. O. Box 1003, Dandenong, Victoria, 3175 Australia, 1990.

Babcock & Wilcox, "Cyclone Furnace for Waste and Treatment of Contaminated Soil - Phase I," Final Report, U.S. Environmental Protection Agency Risk Reduction Engineering Laboratory, March 1991.

Benedict, R. W., and F. R. Weitz, "Thermal Oxidation of Hazardous Waste in a Fluidized Bed Combustor," Waste Tech Services Inc.

Breton, Marc et al., "Technical Resource Document: Treatment Technologies for Solvent Containing Wastes," U.S. Environmental Protection Agency, EPA/600/2-86/095, October 1986.

Brunner, C. R., "Incineration Systems-Selection and Design," Incinerator Consultants Incorporated, Reston, VA, 1988.

Buelt, James L., Contact, Battelle, Pacific Northwest Laboratory, P.O. Box 999, Richland, WA 99352, (509) 375-2927.

Camacho, S. L., "The F1 Manual: Application of Plasma Technology," Plasma Energy Corp., Raleigh, N. C., 1988.

Camacho, S. L., "Industrial-Worthy Plasma Torches: State-of-the-Art," *Pure and Applied Chemistry*, Vol. 60, No. 5, 1988, pp. 619-632.

Camacho, S. L., "Plasma Heating," *Handbook of Applied Thermal Systems*, McGraw-Hill, 1988.

Cotchen, J. K. and H. F. Davis, "A Successful Slag Vitrification Arc Furnace," *Electric Furnace Proceedings*, Vol. 48, New Orleans, 1990.

Cudahy, J. and T. Eicher, "Hazardous Waste Incineration Course," IT Corp., August 1988.

- Dighe, S. V., "Westinghouse Plasma-Fired Processes for Treatment of Industrial Wastes," Westinghouse Electric Corporation, Madison, PA, published in *Iron & Steel Engineer*, January 1992.
- Draper, A. B., R. E. Keith, and J. Gerin Sylvia, "The Cupola Furnace: State-of-the-Art," Department of Industrial and Management Systems Engineering and Center for Air Environment Studies, Pennsylvania State University, 1990.
- Eschenbach, R. C., R. A. Hill, and J. W. Sears, "Process Description and Initial Test Results with the Plasma Centrifugal Reactor," *Forum on Innovative Hazardous Waste Treatment Technologies*, Atlanta, GA, June 19-22, 1989.
- Falcone, P. W. and R. J. Buchanan, "Hazardous Waste Incineration by Slagging - Mode Rotary Kiln," *20th Annual Mid-Atlantic Industrial Waste Conference*, Washington, D. C., June 1988.
- "The Feasibility of Incinerating and Vitrifying Organic Resins in a Single Step," *The Handling and Treatment of Radioactive Wastes*, edited by A. G. Blasewitz et al., James L. Buelt, Pacific Northwest Laboratory, 1984.
- Frankel, J., N. Sanders, and G. Vogel, "Profile of the Hazardous Waste Incinerator Industry," MITRE Corp., 1982.
- Freeman, H. M., "Innovative Thermal Hazardous Waste Treatment Processes," PB85-192847, April 1985.
- Freeman, Harry, *Innovative Thermal Hazardous Organic Waste Treatment*, Noyes Publications, Park Ridge, NJ, 1985.
- Freeman, H. M. et al., "Thermal Destruction of Hazardous Waste — A State-of-the-Art Review," *Journal of Hazardous Materials*, Vol. 14 (1987), pp. 103-117.
- Fruchan, R. J., "Plasma Processes for Metals Production — A Scoping Study," The Center for Metals Production, October 1985.
- Gay, R. L. et al., "Destruction of Toxic Wastes Using Molten Salts," *Technical Meeting of the American Institute of Chemical Engineers*, Anaheim, CA, April 1981.
- Goodwill, J. E., "Proceedings of the First International EPRF Plasma Symposium," CMP Report No. 90-9, May 1990, Chapters 11, 13, 14, and 16.

- Goodwill, J. E., Proceedings of the First International EPRI Plasma Symposium, The EPRI Center for Materials Production, May 1990.
- Hnat, J. G., W. F. Olix, W. F. Talley, and L. M. Bartone, "A Cyclone Melting System for Processing Hazardous Waste Dusts," Vortec Corporation, Collegeville, PA, February 1991.
- International Union for Electroheat, "Arc Plasma Processes; A Maturing Technology in Industry," *UIE Arc Plasma Review*, 1988.
- Johanson, J. G. et al., "Destruction of Hazardous Wastes by the Molten Salt Destruction Process," *Seminar of the American Society of Testing Materials Committee D-27, Nashville, TN, March 1982*.
- Klingler, Larry M. and Perry L. Abellera, "Joule-Heated Glass Furnace Processing of a Highly Aqueous Hazardous Waste Stream," EG&G Mound Applied Technologies, MLM-3577, March 1989.
- Koenig, R. A., J. McFee, and J. S. Vauruska, "Incineration Systems," *Incineration Conference 1990, San Diego, CA, May 1990*.
- Komatsu, F., et al., "Application of Microwave Treatment Technology to Radioactive Waste," *Proceedings of the 1989 Incineration Conference, Knoxville, TN*.
- Kujawa, S. T., "Plasma Arc Furnace Experiments HAZWRAP 1989 Annual Report," MSE Inc., Butte, MT, January 1990.
- Lee, C. C., G. L. Huffman, and D. A. Oberacker, "An Overview of Hazardous/Toxic Waste Incineration," *Hazardous Waste Management*, Vol. 36, No. 8, August 1986, pp. 922-931.
- Lewis, A. C., "Beyond Incineration and Landfills Photo-Electrokinetic Process for the Disposal of Solid and Semi-Solid Waste," Scorpion Mining & Manufacturing Company, Libby, MT, 1991.
- McCormick, R. J., et al., *Costs for Hazardous Waste Incineration*, Noyes Publications, Park Ridge, NJ, 1985.
- Modres, C. W., "Waste-to-Energy '87: Exploring the Total Market," Badger Engineers, Inc., 1987.
- Penberthy Electromelt International, Inc., 631 South 96th Street, Seattle, WA, 98108, "A Company Description," February 1988.

- Penberthy, Larry, "Two Pathways to Action in Dealing with Secondary Materials," *Conference on the Leading Edge of Incineration and Thermal Destruction of Hazardous Wastes, Washington, DC, September 1987.*
- Petersen, R. D. et al., "Application of Microwave Energy for Solidification of TRU Waste," *American Nuclear Society 1987 Winter Meeting, Los Angeles, CA, November 1987.*
- Petersen, R. D. "Microwave Vitrification of Rocky Flats TRU Sludge," *American Nuclear Society 1989 Winter Meeting, San Francisco, CA, November 1989.*
- Peterson, Robert D., Contact, EG&G Rocky Flats, Rocky Flats Plant, Denver, CO, (303) 966-4051.
- Rath, G., T. Vlajcic, and O. Metelmann, "Lead Smelting in a Submerged Arc Furnace," *Journal of Metals*, June 1990.
- Rich, G., and K. Cherry, *Hazardous Waste Treatment Technologies*, Pudvan Publishing Co., 1987.
- Rich, G., and K. Cherry, *Hazardous Waste Treatment Technologies*, Pudvan Publishing Co., Northbrook, IL, 1987.
- Rich, Gerald and Kenneth Cherry, *Hazardous Waste Treatment Technologies*, Pudvan Publishing Co., 1987.
- Smith, Jeffrey D., "Molten Metal Technology," *EI Digest*, July 1991, pp. 8-13.
- Sweet, W. E., R. D. Ross, and G. V. Velde, "Hazardous Waste Incineration: A Progress Report," *Journal of the Air Pollution Control Association*, Vol. 35, No. 2, February 1985.
- "Technical Resource Document: Treatment Technologies for Solvent Containing Wastes," U.S. EPA, EPA/600/2-86/095, October 1986.
- "Thermal Destruction of Hazardous Waste - A State-of-the-Art Review," *Journal of Hazardous Materials*, Vol. 14, 1987, pp. 103-117, Elsevier Science Publishers B.V., Amsterdam, Netherlands.
- Tillman, D. A. et al., "Rotary Incineration Systems for Solid Hazardous Wastes," *Chemical Engineering Progress*, July 1990.
- Van de Voarde N. et al., "High Temperature Incineration of Radioactive Waste," *Nuclear Science and Technology*, Commission of the European Communities, 1986.

Van de Voarde, N. et al., "High Temperature Slagging Incineration-Recent Operating Experience," *Spectrum '86, American Nuclear Society International Topic Meeting, Niagara Falls, NY, 1986.*

Wshima, Hirofumi et al., "Continuous Penetration Test Equipment Using Microwave Heating," RFP-TRANS-462, Translated from Toshiba Review, 39(7), 1984, pp. 611-614.

Yates, Ian C. and J. E. Johnston, "Resource Recovery with Catalytic Extraction Processing," *Environmental Waste Management*, May 1991, pp. 30-31.

Appendix A

Basis for the Determination of Waste Stream Components

Appendix A

Basis for the Determination of Waste Stream Components

The purpose of this study is to evaluate the anticipated performance of alternative thermal treatment technologies for the situation where the RWMC waste is segregated into a primarily combustible fraction and an inert fraction. It is necessary to define basic physical and chemical properties of the feed material for both categories. From the evaluation of existing data available on the RWMC waste characteristics, the following waste categories have been established.

Combustible Waste

The RWMC combustible waste is primarily composed of items that were generated in the daily operations of the RFP and the INEL. The most prevalent constituents in the buried waste are paper (e.g., blotting paper, computer paper), wood (e.g., filter frames, building debris), cardboard (e.g., boxes, containers), plastics (e.g., polyethylene bags and bottles, PVC shoe covers), and rubber (e.g., latex gloves, rubber mats). Due to the nature of operations in a radioactive environment, plastic and rubber will comprise a larger percentage of the combustible materials than would normally be expected from an industrial type of an operation. The combustible waste fraction will therefore have a higher heating value than would normally be expected.

Sludge Waste

Sludge wastes were also disposed of in the RWMC in significant quantity, and represent perhaps as much as 10% of the overall disposal volume. The vast majority of the sludge waste disposed was from the Rocky Flats Plant (RFP). RFP sludges consisted of five basic types of sludge. A general description of each sludge type along with an estimate of its quantity is presented in Table 1.

The current physical state of the disposed sludges is not known at this time. Their state will likely depend to a large extent on the condition of the disposal container that the material was disposed in, and, for breached containers, if it was chemically altered in any way by its surroundings. Originally, several of the sludges contained a large quantity of water by weight; however, since the sludges disposed were the product of a filtration dewatering process, this water is not likely to be free liquid, but rather water of hydration for the sludge.

Table A-1. Description and estimated quantity (in m³) of RFP sludges disposed of at RWMC.

Series 741 Sludge	First Stage Sludge : Obtained from treating aqueous process waste; precipitate of hydrated oxides of iron, magnesium, aluminum, silicon, plutonium, and americium is filtered to produce sludge that is 50 to 70% water by weight.	1983.87
Series 742 Sludge	Second Stage Sludge : produced from the treatment of all other plant radioactive and/or chemical contaminated wastes and further treatment of 741 Sludge; may also contain mercury and lithium batteries and small amounts of contaminated mercury in pint bottles; filtered to produce a sludge 50 to 70% water by weight.	3280.33
Series 743 Sludge	Organic Set-Ups : produced from treatment of liquid organic wastes; organic wastes were mixed with calcium silicate to form a paste-like material; consists mainly of trichloroethane, Texaco Regal Oil, and carbon tetrachloride, hydraulic oils; other organics include trichloroethylene, tetrachloroethylene, gearbox and spindle oils; also some unknown volume of oils containing PCB's.	2014.95
Series 744 Sludge	Special Set-Ups : Resulted from processing liquid waste not compatible with the 741 and 742 processes because of their plutonium complexing nature; Includes alcohols, organic acids, EDTA. Solidified with Portland cement	338.78
Series 745 Sludge	Evaporation Salts : originated from evaporation of liquid waste impounded in solar evaporation ponds; estimated to contain 60% sodium nitrate, 30% potassium nitrate, and 10% miscellaneous material.	1831.32

Brick/Concrete

Brick, concrete, and other similar construction materials represent a significant portion of the RWMC waste. These materials, obviously non-combustible in nature, will be retrieved, size reduced as needed, and are assumed to be processed in the melter system to produce their final waste form.

Glass Waste

There is a relatively small percentage of the RWMC waste that is considered to be glass. Glass waste was often managed as a separate category of waste and was packaged separately for disposal. Glass waste was generated primarily from laboratory operations, and is assumed to be processed in the melter process.

Drummed Bulk Metal Waste and Large Bulk Metal Objects

A large component of the RWMC waste is bulk metal waste. Much of this waste was sized such that it was placed into drums for shipment to the RWMC. Such bulk metal waste will consist

of primarily steels (carbon, stainless, cast); however, some aluminum, copper, and other metals will be present. Other bulk metals were disposed of in their original form, and are very large. These will be almost exclusively steels, and consist of such items as gloveboxes, vessels, lathes and other large tools. Such items will present a special problem in their retrieval and processing.

For the purpose of this study, it is assumed that, in general, these drummed bulk metals will be treated in a separate metals decontamination process, and not in the thermal processes being considered here. Therefore, large quantities of bulk metal are not addressed in this study. However, there will undoubtedly be smaller sized pieces of bulk metal objects that will be present within the waste matrix that will not be readily segregated out for separate processing. Thus, some quantity of tramp metals will be considered as a likely component in each of the two waste streams.

Soil

Retrieval of the buried waste will produce a very large quantity of peripheral soil that will potentially be contaminated with radionuclides and hazardous materials. For the segregation scenario being evaluated, it is assumed that the bulk of the soil can be separated from the waste materials for separate handling. The actual volume of soil that will need to be treated will likely be reduced through either characterization and reclassification of the soil as clean or low-level waste, or through treatment in a unit operation referred to as soil washing. (Mayberry, 1991) Soil washing a process that is postulated to concentrate radionuclides and hazardous materials into a smaller volume of soil that will then be treated thus minimizing treatment and disposal volume. The larger fraction of washed soil can be reclassified as clean or low-level, and handled without need of thermal treatment. This soil may serve as glass forming material to the melter process if desirable. The remaining smaller fraction of soil will have to be processed through either the melter or the incinerator as discussed below.

Determination of the Combustible Waste Composition for Incinerators

This combustible waste component, containing primarily paper, plastic, cloth, oil, and other highly combustible materials, is certainly applicable for treatment in an incinerator. This type of material has been and continues to be incinerated on a regular basis. For example, this type of material has been processed in the WERF incinerator to a large degree of success since 1985. (Ref WERF report).

Many commercial incinerators are operated using sludge wastes as a waste feed material. There appears to be advantages to processing each of the RFP sludges in an incineration process prior to feed to a melter. Treatment requirements for the silicate-stabilized sludge will be mostly driven by the hazardous organic solvents it contains (e.g. carbon tetrachloride) and thus the requirement for proper destruction and removal efficiency (DRE). Incinerators are often designed and operated specifically to achieve this objective. This sludge may present a potentially difficult situation in that it has been stabilized into a "paste-like" material in steel drums prior to disposal.

Retrieving this material from the drums for treatment in an incinerator may prove to be a formidable task. It is possible that the sludge drums could be fed whole to the process chamber; however, this is probably not the best solution. Feeding whole drums of volatile organic material may lead to excessive release of volatiles, causing a process upset that may lead to the release of products of incomplete combustion. It may be possible to use an organic solvent, such as diesel oil, to slurry the sludge material such that it can be removed from the containers and fed into the incinerator through a sludge lance. Another possibility is to utilize the cryofracture technique to produce a material that will be easier to shred and then treat. Since the ultimate method of handling the sludge is uncertain at this time, it should be a consideration in evaluating the versatility of incineration processes.

Treatment of the nitrate sludge in an incinerator should be useful in thermally decomposing the sludge into sodium and potassium oxides and nitrogen oxides (NO_x). The sodium and potassium oxides would remain in the incinerator as a solid ash product. The NO_x formed will be evolved as a gaseous product, and will be carried off with the offgas. Generation of NO_x in the incinerator will pose a concern from the standpoint of offgas control, and will have to be dealt with through proper offgas system design; however, this should not represent a particularly difficult situation.

The inorganic aqueous sludges would benefit from being fed to the incinerator as an initial dewatering step prior to feeding to a melter process. These sludges contain 60-70% water, principally in the hydrated form. An incinerator is probably a better process for driving off this water than a melter process. For one thing, the offgas system will be better designed for large quantities of volatile product. In addition, if the hydrated sludge is fed into a molten metal pool, a steam explosion is possible. The incineration process should also prove to homogenize the feed to the melter process for smoother feeding operation. The other slightly organic, solidified sludge should also benefit from destruction of some of the organic material contained; however, this material will likely have to be crushed prior to feeding.

The final feed component to be considered for the incineration process will be that portion of soil matrix that is heavily contaminated with organic solvents or other organic liquids. It may be much more beneficial to process soils containing high volatiles in an incinerator rather than a melter, due to the relative proportion of offgas expected from each process. One reason is that the organics contained in the soils will largely be hazardous solvents, and proper destruction efficiency will be required. Incinerators have been used many times in the past for treatment of organic contaminated soils, and have been widely accepted as a proper means of treatment. That is not to say other technologies, such as melters, cannot process this waste, rather that regulatory pressure may lead to the use of previously proven and accepted methods. Secondly, large quantities of volatiles release will be much more readily handled in the incinerator, as the secondary combustion chamber and offgas system will be better sized for this type of situation. The secondary combustion chamber (if even needed) and offgas system from the melter system will be much smaller in capacity, and may not adapt well to the sudden and extreme fluctuations that would be experienced in feeding highly volatile components for processing. It will be assumed for purposes of this study that 25% of the soil

that is destined for treatment will be highly contaminated with organics, with the rest destined for direct feed to the melter process.

The last item that will be considered as being present in combustible waste is tramp metals. As discussed previously, it is assumed that metals are to be segregated from the waste for separate handling in the metals processing system. However, some amount of tramp metal will likely pass through the screening into the combustible waste matrix. It will be noted if this presents a problem for any of the incineration processes.

Determination of Non-Combustible (Inert) Waste Matrix for Melters

For the purposes of this evaluation, the inert waste stream will be considered to consist of, the residual ash from the incinerator process, the RFP sludges, the soil fraction that was not sent to the incinerator, the brick and concrete waste, and the glass waste.

The residual from the incinerator will be fed to the melter process to produce the final disposable waste form. The inert residual from the combustible trash portion of the combustible waste will be approximately 5% of its feed mass. It can be assumed that the organic sludge will consist of approximately 50% of its original weight in ash. The soil will essentially pass through the incinerator with little or no mass reduction. The incinerator residual composition will consist of a high concentration of silica and alumina compounds, residual tramp metal, and fixed carbon not burned out by the process.

It is possible that some of the sludge waste types could be fed directly to the process rather than through the incineration process first. This evaluation will consider this as a possibility. The inorganic sludges are obvious candidates for the melter process, even though they have a high water content. Some of the sludge has been cement stabilized, and will have to be processed in some form of shredder or crusher prior to feed to the process. Those solidified drums when shredded will most likely lead to tramp metal (from the drum) that will not be able to be separated from the feed, and this will be considered in the evaluation.

The brick and concrete will be processed through the same shredder as the cemented sludges so that this waste form will be reduced in size for effective feeding to the process. This is very straight forward, and presents little apparent concern for any of the melter processes.

The glass waste will likely best be crushed to assure removal of containerized liquids prior to feed. The feeding of containerized liquid to a thermal process represents a situation where the container and its contents will heat up to the point that, when the container breeches, the liquid will be volatilized rapidly. Such a situation presents operational control difficulties, and should be avoided. Any liquid collected from the glass crushing operation will be prepared for feed to the incinerator process; however, this is assumed to represent a negligible quantity of waste.

Appendix B

Evaluation Methodology

Appendix B

Evaluation Methodology

In order to evaluate the different technologies within each of their categories, a standard set of evaluation criteria was defined. For the purpose of this study, the basic evaluation methodology advanced in EGG-WTD-9449 was used and modified for the specific concerns of this study. That methodology involved the definition of a number of characteristics, or attributes, that are important in considering a particular thermal treatment process. Technologies are assessed on their performance with respect to these attributes, and a relative numerical score is assigned. Individual attribute scores are assigned a weighing based on the relative importance of that attribute.

Specific criteria are defined within each of the individual attribute categories. These criteria are used to determine a technology's rating with respect to its performance for that attribute. The criteria are established in such a way that a technology will receive a score between 1 and 5 for each attribute. The individual attribute ratings are then adjusted by a relative weighing factor, and are summed to arrive at an overall "score" for each technology. The total scores are then normalized to a scale of 0 to 100 to provide better comparison of results. These normalized overall scores can then be compared among the similar technologies to provide a ranking of the technologies most likely to meet the requirements for processing RWMC wastes.

The general attribute categories remain the same for evaluating both the incinerators and the melters. However, some of the attributes have slightly different subcriteria for the melter and incinerator evaluation based on the specific requirements of the technology category. The relative attribute weighting factors assigned must also be slightly different between incinerators and melters, as each is intended to provide different functions and meet different requirements. Therefore, a separate criteria matrix was established for each of the two technology categories to account for these differences. These matrices are displayed in Tables 3 and 4. The following section describes the general attributes and specific criteria used in each technology evaluation.

Definition of Attributes and Evaluation Criteria

Level of Development and Availability (LDA)

This attribute was established to evaluate the maturity and availability of the various technologies. Strict timeframes are being negotiated for the remediation of the RWMC, and the period for technology development is relatively short. Therefore, technologies that are fully developed, operational, time-proven, and commercially available should be given somewhat higher consideration than emerging, unproven technologies.

The LDA attribute is composed of four criteria. The criteria are the same for both the incinerator technologies and the melter technologies. An important consideration is the stage of development of a technology. Operational technologies present more certainty in their performance over developing technologies; and are, therefore, afforded a better rating. Another consideration is whether or not the technology has been demonstrated on waste types similar to those being considered in this study, which would remove uncertainty of a particular technology's applicability to the RWMC waste. A particular technology will rate somewhat better if it is commercially available, rather than designed and built on a one-time only basis; commercially available technologies provide higher certainty of their probability of successful operation. Finally, a technology that has been time-proven in waste processing service should be afforded a higher consideration than a relatively newer technology.

Versatility (VRSL)

There are a number of factors that make up versatility with respect to the waste feed properties. Even though in the postulated scenario, where the waste to be treated will be segregated by treatment category, it is likely that the efficiency of the segregation will be limited by technology and/or safety considerations. In addition, waste within a treatment category can be expected to vary a great deal. Finally, there were some simplifying assumption made in the characterization of waste categories addressed in an earlier section of this report. It is likely that these simplifying assumptions will not prove to be completely true when more information becomes known, most likely upon the actual retrieval of the waste. Thus, for the purposes of this evaluation of technologies, it will be important to know where limitations may exist in a given technology's ability to accept a range of input materials.

The criteria defined for each technology type will be slightly different. For incinerators, there are three basic criteria. A determination is made of the fraction of materials that will be treatable for that particular category. The need to screen restricted items is judged for each technology, as the need for screening tends to increase operating costs and personnel exposure standpoint. Lastly, technologies are rated on their need to have the waste shredded or otherwise pretreated prior to feed. Such pretreatment introduces an extra operation in the overall process that should be avoided if possible. Shredders can be maintenance problems, and also tend to introduce particulate into the air.

In the case of melters, the fraction applicable and pretreatment criteria are also applied for the same reasons as discussed for incinerators. Two additional criteria are added for the melters: feed variability concerns and a measure of the upper temperature range. Since the inert waste feed will likely vary a great deal, it is important to know what effect this may have in the melter process. The upper temperature range is important in that technologies that can achieve higher temperatures will provide more versatility in handling a wide range of materials, particularly some of the higher melting temperature compounds that are anticipated in the inert waste.

Residual Solid Product (RSP)

The objective of waste treatment is to change the chemical and/or physical form of a waste to render it more safe and/or environmentally sound. In addition, because of the land disposal restrictions, treatment is necessary to meet defined standards prior to disposal. The requirements for the residual from the incinerator are different from those of the melter since each technology is intended to provide a different function. Therefore, the criteria used for the two technology categories will be different for this attribute.

The incinerator need not produce a final disposable waste form, but rather is intended to destroy the hazardous organic fraction of the waste and to process the bulk organic to prepare the material for feed to the melter. Thus the criteria are defined to judge a technology's ability to accomplish these goals. The organic destruction efficiency of the incinerators is evaluated, with those providing for high organic burnout rated as superior. Since it is a goal of the melter process to keep offgas treatment requirements to a minimum, large quantities of residual organics are not a desirable feed for the melter process. The handling complexities of the residual ash from the incinerators is also evaluated, as handling this material prior to feed to the melter process will be a concern. Finally the volume reduction potential of the technology is evaluated to account for those technologies that may require additives that will increase the final amount of material that must be treated.

For the melter, the residual solid product is the most important attribute, as producing a high quality disposable waste form is the goal of the process. There may be some amount of material that is fed to the melter that has hazardous organic contaminants. Thus, technologies that have demonstrated or are judged to be able to provide proper destruction and removal efficiency (DRE) from the feed are given higher consideration. The control of process chemistry is also an important criteria, as it is anticipated that there will be a desire to provide the capability to add glass formers or fluxes to control the melt viscosity and potentially other additives to optimize the structural and leaching properties of the final product. Technologies that allow for better chemistry control of the molten pool are more desirable. Since leachability of the residual product is an important consideration, those technologies that have been demonstrated to produce a leach-resistant final form will be judged somewhat higher than those that have not. And as in the case of the incinerators, those technologies that will tend to increase the overall disposable volume of waste will be slightly downgraded, as volume reduction of the final disposed waste is an important consideration.

Offgas Effluent (EFLT)

The EFLT attribute was used to evaluate and compare the process effluents of the technologies. A very significant aspect in the treatment of mixed TRU waste is control of the potential for release of both radioactive and hazardous constituents. The more problems created in the offgas effluents from a particular process, the more difficult offgas treatment becomes, and the greater the potential for an unplanned release. Therefore, the EFLT criterion scoring was structured

to favor technologies with inherent contamination control features that produce offgases requiring minimal treatment before release.

The criteria for both the incinerators and the melters is basically the same in this attribute. The volume of effluent generated by a particular process is important as technologies that generate relatively higher volumes of offgas will require more complicated and expensive offgas control systems. The potential for technologies to generate and carryover particulate to the offgas is evaluated since technologies that generate significant particulate create a difficult control situation in the capture and control of contaminated fly ash. Other important considerations include the potential for volatilization of heavy metals and radionuclides, control and capture of acid gasses such as HCl, and the potential generation of NO_x, a particularly difficult class of compound to scrub from the offgas.

Operational Considerations (OPS)

The OPS attribute was included to evaluate various operational aspects that should be considered in evaluating various technologies. These include process complexity, including simplicity of design and ease of operation, health and safety considerations involved in the processes, maintenance requirements, and potential level of throughput. The criteria for this attribute are the same in each of the technology categories.

Process equipment complexity is considered important because it is assumed that the simpler a technology is, the more reliable and safe it will be. Similarly, if a system is easy to operate, it is likely that operational problems that may lead to an event will be minimized.

The safety considerations evaluated in this criterion were related to the inherent safety of the technology. Technologies that operate at relatively low temperatures and pressures, produce a nondispersable waste form, and offer structural pressure excursion containment were considered most safe. Inherent design features or process features that contribute to the control of radioactive material release is also an important consideration. This is primarily evidenced in the treatment vessel seal, and thus the ability to control contamination releases during pressure excursions. Technologies designed with this inherent feature are more desirable.

Maintenance requirements were evaluated because technologies operating on TRU-contaminated waste will have to be operated remotely most likely in glovebox enclosures. This requirement makes maintenance difficult and would likely result in increased radioactivity exposure for maintenance personnel.

Finally, the throughput capability of each technology was evaluated as part of this attribute. The throughput of a given technology is very difficult to evaluate quantitatively because it is highly dependant on a number of individual variables, any of which will lead to a different consideration for separate technologies. The result is that numerical comparison of throughput will not provide a

meaningful comparison, and can thus be taken out of context. Thus, this evaluation entails a qualitative treatment of the throughput of each technology, considering with size range of equipment available, (technologies having larger available capacity will be more desirable) and potential throughput for a given process size.

Cost (COST)

In the cost attribute, the capital cost of each technology was evaluated. The capital costs were estimated and evaluated based on a 10 MBtu/hr system using a consistent set of simplifying assumptions for each technology. The cost figures were determined based primarily from contacts with vendors and developers, and from data available in published reports where applicable. While the cost data used in the evaluation is believed to indicate relative cost, they should be considered to be gross approximations at best. In the end, the cost of a particular technology is likely to be a minor consideration at best, as its cost will be insignificant in comparison to alpha facility costs and ES&H and administrative costs. Thus, cost should not be a major contributor to the overall score.

Weighting Factors

Certain of the evaluation attributes can be defensibly judged to be of greater importance than others. In order to account for this, relative weighting factors are assigned to each attribute to account for their relative importance. Each of the individual attribute raw scores is adjusted by its relative weight through a simple multiplicative operation. The resulting weighted attribute scores are then summed to provide the overall weighted score for each technology. These weighted scores are then normalized on a 0 to 100 scale to provide better comparison.

Each of the two technology categories is intended to provide a different function for the remediation scenario being evaluated in this study. Therefore, different weights were assigned to the attribute categories for the melter and the incinerator process to account for these differing process requirements. The rationale for the weights assigned is discussed below.

Weighting Factors for Incinerator Evaluation

The primary purpose of the incineration process is to destroy the hazardous organics and to reduce bulk organic material. In this regard, the incinerator could be considered to be a preprocessor of feed material to the melter. In fact, an argument could be advanced that perhaps all the waste material retrieved should be processed through the incineration system prior to introduction to the melter to assure a more homogeneous and readily processable feed to the melter. In this respect, the versatility of the incineration process becomes the most significant attribute, since the input waste could effectively encompass the range of material to be retrieved from the RWMC. In addition, because the RWMC waste is contaminated with transuranic isotopes and other hazardous materials

that present significant personnel safety and environmental problems, handling must be minimized. Versatile technologies will require minimal pretreatment and handling, reducing these risks.

The next important criteria for the incineration processes are the operational considerations involved in the technologies. The criteria display the overall operability and measure of health and safety inherent to the technologies which are significant considerations. The more complex the process in operation, maintenance, and health and safety concerns, the more difficult the process will be to permit and operate.

Level of development and effluent evaluations were considered the next important attributes. These are rated somewhat lower in importance mostly because there are only subtle differences between each of the technologies in these attributes, and therefore, only a modest weighting of importance should be afforded in this category. The residual solid product attribute follows next in importance. Since the incinerator is really only a preprocessing step for feed preparation to the melter process, the quality of the residual product is not of a major consideration. Finally, cost is the lowest consideration in this study, as technology performance is a much greater consideration than the cost, and cost should only be used as a last comparison for two identical performance technologies.

Weighting Factors for Melter Evaluation

The goal of the melter process is to produce a final waste product that has optimum qualities for control of leachability and structural integrity. Thus, the residual solid product category will obviously be the most important attribute of the technologies, and will thus be given the highest weighting.

The next most important attributes are the versatility and the operational considerations for the individual processes. Versatility is not quite as important as in the case of the incineration process, since the feed will be preprocessed into a somewhat more homogenous feed stock; however, it is still an important consideration. Operational considerations are important for the same reasons as discussed for the incinerators.

Effluent considerations, level of development, and cost follow in order of decreasing importance. Effluent considerations become important in that it will be important assure that offgas from the process will be readily controllable. Level of development will not be considered a particularly important concern in that most of the melter technologies are adaptations of well understood non-waste treatment processes, and it should be possible to fast-track their development into waste treatment technologies. Finally, as discussed above, cost should not be an overriding factor in the evaluation of the technologies.

Appendix C

Evaluation of Technologies

Appendix C

Evaluation of Technologies

EVALUATION OF INCINERATORS

Level of Development and Availability

Rotary Kiln

The rotary kiln is the basis for a perfect score in this attribute, as this technology is the most commonly built and operated incinerator for waste treatment (excluding liquid injection incinerators, which are far more used in waste treatment, but are excluded from this study). At least 75 commercial hazardous waste facilities and 2 DOE facilities are currently using rotary kilns. Thus, it is operational, commercially available, and time proven.

Controlled Air

Controlled air incineration became popular in the 1960s and clearly meets the top score in this criterion being operational, time-proven, and available commercially. At least 50 commercial hazardous waste facilities and 4 DOE facilities are currently using CAIs.

Fluidized Bed

Fluidized bed incinerator technology is operational, commercially available, and time proven. There are at least 25 FBIs in operation on hazardous waste, and at least two that have been designed and tested for radioactive waste (Rocky Flats and ICPP). FBI technology can be considered one of the more mature technologies of those evaluated.

Molten Salt

Molten salt incinerator technology is considered an emerging technology that has been demonstrated at a field scale. While the technology has been around for a while and has been demonstrated, it is not yet available in commercial models. It has not been in any waste processing service, and is thus not time proven either.

Cyclone Incinerator

Cyclonic incineration has been used for many years to process sludge wastes and clearly meets the top score in this criterion being operational, time-proven, and available commercially. However, not tested on a bulk combustible waste form.

Multiple Hearth

The multiple hearth incinerator (MHI) technology is operational having had several constructed. MHIs have been used extensively in the treatment of sludge wastes, and are therefore time proven as well. However, the use of this technology has been largely abandoned in favor of more versatile incinerators such as the rotary kiln and the technology is essentially not commercially available now. It could perhaps be brought back. Also not tested for this type of waste form.

Slagging Kiln

Generally, slagging kiln technology is operational and commercially available. At least 10 slagging kilns are in operation on hazardous waste in the United States and several more are in the planning or constructions phase. Slagging kiln technology is very similar in application and operation to a rotary kiln process, for which a great deal of operational experience exists. The technology is commercially available, but is should not be considered as time proven.

Cyclone Melter

The cyclone melter is derived from cyclone burner technology used in the coal fired electrical energy generation plants. It has been demonstrated at a field scale for waste applications, but is not an operational technology. The cyclone melter is a derivative application of the cyclone incinerator, and is, therefore, commercially available. However, it is not a time proven waste application technology, and has not been tested for this waste.

Summary of Level of Development and Availability Scoring

	Criteria Scores				Total Score (1,5)
	Dev Stg (1,2)	Tested (0,1)	Comm (0,1)	Proven (0,1)	
Rotary Kiln	2	1	1	1	5
Controlled Air	2	1	1	1	5
Fluidized Bed	2	1	1	1	5
Molten Salt	1	0	0	0	1
Cyclone	2	0	1	1	4
Multiple Hearth	2	0	0	1	3
Slagging Kiln	2	1	1	0	4
Cyclone Melter	2	0	1	0	3

Versatility

Rotary Kiln

The rotary kiln is probably the most versatile of the conventional types of incinerators. Most commercial hazardous waste applications handle liquids, solids, and sludge wastes routinely without the need for pretreatment. Whole 55-gal drums of waste are typically fed to large applications of rotary kilns (i.e. units greater in thermal rating than approximately 50 MMBtu, a very large unit). Rotary kilns are also the technology of choice for many soil remediation applications, often without pretreatment, except for grinding large pieces into smaller size to increase surface area and thus mass transfer.

Controlled Air

The CAI is not an extremely versatile technology. They are applied primarily to combustible waste with low ash contents because of drawbacks in their ability to handle large quantities of residual ash. Soils could be treated in the CAI, but likely only in small quantities. Tramp metals are best excluded. Pretreatment shredding is not extensive, only for very large objects. Feed of whole drums is not feasible.

Fluidized Bed

FBI technology is considered an omnivorous technology with the ability to handle most types of RWMC combustible waste. One exception would be high density materials such as metallic wastes, which would drop to the bottom of the bed where they may cause operational problems. This will present a problem if tramp metals are in the waste, requiring excessive screening and removal. Bulk combustible waste is readily processed in a fluidized bed; however, only with shredding prior to feeding. Contaminated soils are suitable for processing in a fluidized bed, but must be crushed to a relatively fine state.

Molten Salt

The molten salt incinerator is applicable only to low-moisture, low-ash wastes. Therefore, a molten salt incinerator would be applicable to only the bulk organic fraction of the combustible waste. Soils and high moisture sludges would not be readily processable. In addition, pretreatment would be required for the combustible wastes.

Cyclone Incinerator

The CyI is not a versatile incinerator. They are applied primarily to sludges, liquids, and gaseous wastes because of their lack of ability to handle large quantities of residual ash. The technology is not suited to processing bulk organics. Soils and sludges could be treated, but would require extensive size reduction. Therefore, only a small fraction of combustible waste could be treated with this technology.

Multiple Hearth

The MHI technology was designed primarily for use on sludge waste. While it could also be used on other types of waste, its use is limited primarily to sludge type wastes. It could probably process the soil component, and perhaps some of the bulk organics; however, pretreatment would be required. Tramp metals may pose a problem.

Slagging Kiln

The slagging kiln is considered to be an omnivorous technology. No pretreatment would be required for most types of RWMC wastes being considered in the combustible waste category. Items such as whole drums of the organic/calcium silicate sludge could feasibly be fed directly without pretreatment; however, increasing metal content in the feed has a direct impact on producing a molten product. It is better if metals are excluded from the feed. Slagging kilns are most often utilized when processing waste having a high inherent heating value, particularly organic sludge type wastes (e.g., from oil refineries). The RWMC combustible waste has only a moderate heating value, which will require much supplementary fuel and oxygen enriched operation. In general, a slagging

kiln will not be used in applications involving significant quantities of soil or other non-combustible material.

Cyclone Melter

Larger tramp metallic objects and bulk organic materials will not be effectively processed based on the difficulty of introducing the materials to the process (via pneumatically conveyed feed stream), and short retention time in the chamber. Pretreatment requirements will be very high to condition feed stream. Feed of soils and sludges should be acceptable.

Summary of Versatility Scoring

	Criteria Scores			Total Score (1, 5)
	Fraction (1-3)	Screen (0, 1)	Pretreat (0, 1)	
Rotary Kiln	3	1	1	5
Controlled Air	2	0	1	3
Fluidized Bed	2	0	0	2
Molten Salt	1	0	0	1
Cyclone	2	0	0	2
Multiple Hearth	2	1	0	3
Slagging Kiln	3	1	1	5
Cyclone Melter	2	0	0	2

Residual Product Form

Rotary Kiln

The turbulent action of the waste products moving through the kiln and the high combustion air rates in the kiln provide for excellent burnout and destruction of organics. Rotary kiln incinerators are BDAT for the organic constituents found in RWMC waste. However, they produce a dispersible ash that would present moderate considerations in handling to control migration. Volume reduction can be accomplished by destruction of the organic materials and by the production of a more homogenous stream.

Controlled Air

CAIs are BDAT for the organic constituents found in RWMC waste, and can be operated to achieve a very high degree of organic burnout and destruction. CAIs produce an ash that would tend to be dispersible, but often forms a somewhat hardened "clinker" material. Volume reduction is accomplished by destruction of the organic materials and by the production of a more homogenous stream.

Fluidized Bed

The FBI is BDAT for the organic contaminants involved in RWMC waste, and the highly turbulent nature of the bed yield very high destruction efficiency. The abrading action of the turbulent bed causes grinding of the residual ash into a fine state, creating potential handling concerns; however, the fluidizable material should be readily conveyed by pneumatic methods using sealed transport mechanisms. The FBI may not accomplish the same degree of volume reduction as other incinerator technologies because of bed material may have to be added to maintain adequate bed characteristics; however, sand is generally used as bed material, and the soil feed may adequately form sufficient bed material.

Molten Salt

The molten salt incinerator produces a spent salt final waste form, which contains the residual ash from the combustion. It is not clear whether burnout of organic material is very high, but probably is. Because the spent salt becomes part of the final waste, the final waste volume is increased. Extreme handling and treatment is required to bring the effluent into a state to prepare it for feed to the melter.

Cyclone Incinerator

CYIs are BDAT for the organic constituents found in RWMC waste, but burnout of bulk organics may not be accomplished in the short solids residence time of the primary chamber. The CYI produces a dispersible ash that would require special handling. Volume reduction can be accomplished by destruction of the organic materials and by the production of a more homogenous stream.

Multiple Hearth

The MHI is BDAT for the organic contaminants involved in RWMC waste, and should provide sufficient solids residence time to ensure burnout of organics. Again, a dispersible ash is generated, which will require handling considerations. Volume reduction will be achieved similar to other incinerators.

Slagging Kiln

The slagging kiln should provide the proper destruction of organics that will be required. A slagging kiln may result in a waste form that is likely to meet the performance standard for leachable metals, and would thus be directly disposable. The vitrification will help produce a stabilized and thus more easily handled ash product. Because of the loss of void space from vitrification, slightly higher volume reduction is also achieved, but this is offset by the addition of fluxing agents to reduce the melting point of the slag, potentially leading to greater volume than other non-vitrifying incinerators.

Cyclone Melter

The cyclone melter has a very short residence time of material in the process zone, and would not provide the time necessary to provide complete burnout of bulk organic material. Handling of the residual solidified material, however, will be optimal, with little dispersion potential. Final volume will not be minimized as additives are needed to assure product is brought to a molten state.

Summary of Residual Solid Product Scoring

	Criteria Scores			Total Score (1,5)
	Organic (1,2)	Handling (0-2)	Vol. Red. (0,1)	
Rotary Kiln	2	1	1	4
Controlled Air	2	1	1	4
Fluidized Bed	2	1	1	4
Molten Salt	2	0	0	2
Cyclone	1	1	1	3
Multiple Hearth	1	1	1	3
Slagging Kiln	2	2	0	4
Cyclone Melter	1	2	0	3

Offgas Effluents

Rotary Kiln

Rotary kilns are noted for high excess air rates in order to ensure destruction. This results in large volumes of offgas and, combined with the tumbling of waste in the chamber, high carryover of particulate from the incinerator into the offgas system. This requirement results in the need for complex offgas systems to ensure removal consistent with radioactive material. Some amount of metal volatilization and NO_x formation will occur, but not extensive. Chlorine in the waste feed will produce acid gas that will need to be scrubbed.

Controlled Air

CAIs were designed to provide very good control of particulate material generation and carryover. This is accomplished through low air rates in the primary and a relatively quiescent burning bed. H_2 will be formed and will need to be scrubbed. Lower temperatures lead to minimal formation of metals and NO_x , and thus only moderate offgas system requirements. For these reasons, CAI has often been chosen as the preferred technology for combustible radioactive waste.

Fluidized Bed

The FBI does not produce a great volume of offgas. However, the inherent design leads to relatively high gas velocities, which, combined with the abrasion of bed material, result in the high carryover of particulate contaminants into the offgas system. Because of the high particulate carryover rate associated with FBIs, a high temperature cyclone is always employed at the exit. The cyclone is necessary to return bed material to the bed and in this capacity, is considered part of the FBI. However, because cyclones are not effective on submicron particulate, the particulate removal requirements downstream are considered complex. In-bed chlorine scrubbing in FBIs is usually employed by adding a lime feed to the bed, reducing offgas scrubbing requirements. In addition, the chlorine removal in the bed reduces the available chlorine to form metal chlorides, which are more volatile than metal oxides. This may reduce the carryover of heavy metals into the offgas and therefore, the offgas treatment requirement for this contaminant. Low operating temperatures produce little NO_x .

Molten Salt

Because combustion takes place within a molten matrix, combustion efficiency is very high, and particulate control is very high. Combustion volumes are relatively low. In-bed scrubbing of chlorine is accomplished, and because the salt forms complexes with heavy metals and radionuclides, they are retained in the salt. Low temperature operation will minimize formation of NO_x and metal volatilization.

Cyclone Incinerator

CYIs are designed to operate with a very high turbulence, leading to a very high destruction efficiency and thus requiring a minimal volume of combustion air. Cyls are noted for very good control on particulate, due to the cyclonic turbulence which centrifugally de-entrains particulate. CYIs will produce a relatively high temperature combustion zone that will lead to formation of relatively higher quantities of metals and NOx. HCl scrubbing will be required. Offgas considerations are moderate.

Multiple Hearth

The MH is operated with relatively moderate excess air rates, which lead to relatively small volumes of offgas. Particulate generation is not extreme due to low air rates and design of the system where offgas from the combustion zone passes through a relatively cold feed material zone. This should also help control metal volatilization and NOx. HCl will have to be scrubbed. Offgas considerations are judged to be low.

Slagging Kiln

Offgas treatment for the slagging kiln is considered to relatively less complex than for a rotary kiln because of lower excess air rates which result smaller volumes of offgas. This and the slagging action of the waste result in less particulate generation and carryover. The offgas treatment requirement of the slagging kiln is given a moderate because of the high temperature gas handling requirement, requiring special materials, consideration for metal volatilization and Nox generation. Again, HCl will have to be scrubbed.

Cyclone Melter

Due to the efficiency of mixing and turbulence, the cyclone melter requires smaller quantities of excess air. However, the high turbulence and small feed material size required will lead to particulate formation and entrainment. The relatively higher process zone temperatures will create some concerns in the formation of NOx and the volatilization of heavy metals. Offgas concerns would be moderate.

Summary of Effluent Scoring

	Criteria Scores			Total Score (1,5)
	Volume (1,2)	Part. (0,1)	Other (0-2)	
Rotary Kiln	1	0	1	2
Controlled Air	2	1	1	4
Fluidized Bed	2	0	2	4
Molten Salt	2	1	2	5
Cyclone	2	0	1	3
Multiple Hearth	1	1	1	3
Slagging Kiln	2	1	0	3
Cyclone Melter	2	0	0	2

Operational Considerations

Rotary Kiln

- Complexity: In comparison to other technologies, the rotary kiln is a relatively complex process, particularly the moving kiln system.
- H&S: Rad control is questioned on rotary kilns, particularly for the rotating seal. Potential pressure excursions may lead to releases through the seals.
- Maintenance: Downgraded for higher than normal refractory maintenance requirements, maintenance of seals and moving parts.
- Throughput: Rotary kiln will have a relatively high throughput capacity compared to other technologies. Process unit sizes are available to very large capacities.

Controlled Air

- Complexity: The CAI is a relatively simple process. Basically simple system to operate. Air leakage into the primary chamber is a common control problem.
- H&S: Downgraded for production of a dispersible ash. Potential for release an pressure excursions i.e. not a sealed vessel.
- Maintenance: Generally a low maintenance devices, even if operated with frequent thermal cycling.

Throughput: CAIs will have a moderate throughput level. Sizes range large. Relatively long solids residence time is required for complete burnout.

Fluidized Bed

Complexity: FBIs are a very simple design, having few moving parts. Good thermal stability due to heat capacity of the bed is characteristic. Operation is somewhat difficult in transient conditions in maintaining fluidization of bed. Bed can agglomerate and cause a situation of freeze-up.

H&S: Low temperature but produces a readily dispersible ash. Units are better sealed than other processes, even designed to operate at slightly positive pressures without releases.

Maintenance: Fluidizing air inlet orifices will deteriorate with time requiring replacement. Lower temperatures should reduce refractory wear, but should be offset by abrasive nature of the bed. No moving parts to process requiring service and repair.

Throughput: Since FBIs are very efficient at transferring heat to the waste, they will provide a higher throughput capability than other technologies. Sizes range to very large units.

Molten Salt

Complexity: Handling of high temperature molten material is a consideration. Offgas unit operation will be very complex. Handling of residual solid product complicated. There is potential for bed freeze-up for some high melting compounds.

H&S: Downgraded for molten material handling. Sealed process vessel provides increased contamination control of ash

Maintenance: Will have materials compatibility problems with high temperature molten salt. Long-term maintenance requirements are unknown.

Throughput: Effective means of transferring heat to waste should provide relative economy of throughput for a given size. Unit sizes will not be very large; multiple units will be required for operations.

Cyclone Incinerator

Complexity: The process is relatively simple to operate since product is air conveyed and no moving parts are needed. Extensive feed preparation; however, adds some complexity. Basically a simple system to operate.

H&S: Process operates as a sealed vessel. Downgraded for production of a dispersible ash.

Maintenance: Low maintenance devices even with frequent thermal cycling. High temperature process zone will lead to relatively more frequent refractory wear.

Throughput: Throughput limited by ash handling capability. Unit capacities available are quite large. In general, moderate throughput potential.

Multiple Hearth

Complexity: Air cooled rotating rabble arms in the chamber are used to move waste through process. Control on a highly variable waste feed type may be difficult.

H&S: Moderate temperatures but produces a dispersible ash. Vessels will not be totally sealable.

Maintenance: Moderate maintenance requirements due to internal moving parts. Refractory wear not a large issue.

Throughput: For the waste types evaluated, throughputs should be moderate. Systems are produced in moderate capacity sizes.

Slagging Kiln

Complexity: Handling of high temperature molten material a moderate complexity. Special materials required. Maintaining molten slag chemistry a operating concern. Rotating kiln problems same as rotary kiln. Oxygen enrichment or preheated combustion air required for adequate operation.

H&S: Downgraded due to special high temperature and molten material. Slightly increased contamination control of vitrified ash. Potential for release on pressure excursion.

Maintenance: Refractory maintenance requirements will be extreme. Kiln seal maintenance requirements high.

Throughput: High throughput potential, large capacity units.

Cyclone Melter

Complexity: The process is relatively simple to operate since product is air conveyed and no moving parts are needed. Extensive feed preparation; however, adds some complexity. Preparing and feeding glass forming additives adds to complexity.

H&S: Process operates as a sealed vessel. Provides for vitrification/agglomeration of ash, thus minimizes dispersion potential.

Maintenance: Low maintenance devices even with frequent thermal cycling. High temperature process zone will lead to relatively more frequent refractory wear.

Throughput: Throughput limited by ash handling capability. Unit capacities available are quite large. In general, moderate throughput potential.

Summary of Operational Considerations Scoring

	Criteria Scores				Total Score (1, 5)
	Comp (1-3)	H&S (1-3)	Maint (0-2)	Thrpt (0-2)	
Rotary Kiln	3	1	1	2	3.5
Controlled Air	3	2	2	1	4
Fluidized Bed	2	2	1	2	3.5
Molten Salt	1	2	1	0	2
Cyclone	2	2	1	0	2.5
Multiple Hearth	2	2	1	2	3.5
Slagging Kiln	1	2	0	2	2.5
Cyclone Melter	1	3	1	0	2.5

Cost

Rotary Kiln

The rotary kiln is a moderate cost technology, experiencing some additional cost drivers based on kiln and seal difficulties. Feed handling equipment minimal.

Controlled Air

A simple design, simple constructed system, will be among the lowest of cost.

Fluidized Bed

Also a simple design, with few moving parts.

Molten Salt

Highly complex process that has not been constructed on any kind of routine basis. Will require special materials of construction due to extreme process environment. Will be one of the highest cost technologies.

Cyclone Incinerator

The special feed system configuration, and additional feed preparation equipment will add to the cost, driving the technology to a moderate cost rating.

Multiple Hearth

Will also be a moderate cost facility, as not many have been made recently, and also requires feed preparation equipment.

Slagging Kiln

Special materials of construction concerns and product handling system will drive the cost for the slagging kiln to the higher end of cost.

Cyclone Melter

Again, special materials of construction and product handling system concerns will drive the technology to the higher end of cost.

Summary of Cost Scoring

	Total Score (1,3,5)
Rotary Kiln	3
Controlled Air	5
Fluidized Bed	5
Molten Salt	1
Cyclone	3
Multiple Hearth	3
Slagging Kiln	1
Cyclone Melter	1

EVALUATION OF MELTERS

Level of Development and Availability

Fossil Fueled Hearth Melter

Also a very well developed technology for steel refining, having been used for many years. Processes are commercially available. Not demonstrated on waste processing in any great detail, and cannot be considered time proven for waste applications.

Plasma Torch Hearth Melter (PTHM)

The PTHM is a technology that has been used for many years in the metals production industry. PTHM is an emerging technology in the area of waste treatment, and has been demonstrated at what can be considered to be field scale. Equipment is commercially available from a number of vendors. The technology has been demonstrated on several close variations of the type of waste being considered. It is not a time-proven waste treatment technology.

Graphite Electrode Hearth Melter (GEHM)

The GEHM is a technology that has been used for many years in the production and recycling of steel. Some limited work in the area of waste treatment has been done for what can be considered field scale. The technology is commercially available and, based on steel operations, can be said to be time proven.

Fossil Fueled Shaft Melter

A well understood and developed process for scrap steel recycling and processing. Technology is operational; however, has not been demonstrated on waste applications. Equipment is commercially available, but is not time proven on waste applications.

Plasma Torch Shaft Melter (PTSM)

PTSM technology is gaining experience in waste treatment technology, principally in treatment of waste metal. However, the technology should still be considered demonstrated at field scale, as only one processing system has been built recently. Equipment is commercially available, but the technology cannot be said to be time proven.

Graphite Electrode Shaft Melter (GESM)

A novel adaptation of a well used shaft melter technology, having thus far only to be demonstrated at the field scale. Has been demonstrated on a basically combustible waste matrix. Equipment is not commercially available at this time, and the technology is not time proven.

Joule-Heated Melter (JHM)

The JHM is operational and commercially available as a glass production technology. As a derivative of technology utilized for glass making, there are more than 80 units throughout the world. Equipment is commercially available. Several waste treatment applications are being pursued, but the technology cannot be said to be an operational waste treatment technology. Since there is only one unit processing hazardous waste, the system is not time-proven.

Microwave Melter

The microwave melter is (on selected homogeneous waste streams) an emerging technology which has been demonstrated at pilot scale at the Rocky Flats Plant and in Japan. The technology is not available commercially or time-proven.

Molten Metal Bath

A derivative of steel making technology, this technology relies on a molten steel bath for processing of the waste. The technology itself is mature, but has not been demonstrated for waste treatment. Equipment can be said to be commercially available, but the technology is not time proven.

Cyclone Melter

The cyclone melter has been demonstrated at a field scale, but is not an operational technology. The cyclone melter is a derivative application of the cyclone incinerator, and is therefore commercially available. However, it is not a time proven technology.

Slagging Kiln

Generally, slagging kiln technology is operational and commercially available. At least 10 slagging kilns are in operation on hazardous waste in the United States and several more are in the planning or constructions phase. Slagging kiln technology is very similar in application and operation to a rotary kiln process, for which a great deal of operational experience exists. The technology is commercially available, but should not be considered as time proven.

Summary of Scoring for Level of Development

	Criteria Scores				Total Score (1,5)
	Dev Stg (1,2)	Tested (0,1)	Comm (0,1)	Proven (0,1)	
FFHM	2	0	1	0	3
PTHM	2	1	1	0	4
GEHM	2	1	1	0	4
FFSM	2	0	1	0	3
PTSM	1	1	0	0	2
GESM	1	1	1	0	3
JHM	2	1	1	0	4
Slaggin Kiln	2	1	1	0	4
Cyclone Melter	1	1	1	0	3
Molten Metal	2	0	1	0	3
Microwave	1	0	0	0	1

Versatility

Fossil Fueled Hearth Melter

None of the subject waste feed being considered should present a problem for feeding to the process. Pretreatment requirements will be minimal. Variability in feed should not pose a problem to operation of the system. Upper temperature range is high so that melt temperature is flexible.

Plasma Torch Hearth Melter

Although its versatility has not been proven completely, the PTHM is considered to be an omnivorous technology. It is claimed to be capable of handling any of the waste associated with the RWMC. Plasma systems have been demonstrated on soil matrices with minor organic and metallic contaminants, as expected in the RWMC inert waste. Bulk sludges have not been demonstrated, but should pose no special problems. Waste pretreatment should be minimal. Feed variability would appear to pose no problem in the system. Upper temperature range is very high, leading to particular flexibility in operation.

Graphite Electrode Hearth Melter

In this category, there is no apparent difference between the PTHM and the GEHM. The same description as above applies.

Fossil Fueled Shaft Melter

The FFSM should be able to adequately process any of the materials being considered. Pretreatment requirements will be relatively high, based on optimal densification of the waste material and careful control of fuel assist material. Feed variability may tend to cause operational problems due to lack of control functions. Data indicate that not significantly high temperature ranges are attainable.

Plasma Torch Shaft Melter

The PTSM should also not be limited by any of the postulated material feed. Pretreatment will also be high in this application. Feed variability will not likely be as much of a concern as controlling the torch will control the process parameters. Potentially higher temperatures may be obtained with plasma assist.

Graphite Electrode Shaft Melter

Same discussion as PTSM applies here.

Joule-Heated Melter

The glass furnace is an omnivorous technology within its temperature range and is capable of processing all of the waste types present at the RWMC. It is less well suited to high concentrations of metals and high melting temperature soils, requiring flux additives to control melt viscosity.

Microwave Melter

The microwave melter has been demonstrated only on sludges and finely divided inerts (ash). It is not capable of effectively processing tramp combustibles or nonuniform inerts. Pretreatment requirements are high for the material to be processed. Variability of feed material is not likely to be a great concern. Upper temperature range is limited.

Molten Metal Bath

The molten metal bath technology should not have a problem with any of the waste components being considered here, except possibly the hydrated sludges, due to safety concerns. Waste

pretreatment will be required for some larger bulk objects to allow their feed below the melt surface as designed. Feed variability should be no problem. Upper temperature range is high.

Cyclone Melter

Larger tramp metallic objects and bulk organic materials will not be effectively processed based on the difficulty of introducing the materials to the process (via pneumatically conveyed feed stream), and short retention time in the chamber. Pretreatment requirements will be very high to condition feed stream. Variability of feed will be a concern from a control standpoint as fuel requirements will differ. Upper temperature range is limited, limiting versatility.

Slagging Kiln

The slagging kiln is considered to be an omnivorous technology. No pretreatment would be required for most types of RWMC wastes being considered in the inert waste category. Increasing metal content in the feed has a direct impact on producing a molten product. It is better if metals are excluded from the feed. Slag forming materials have to be added to the feed. Pretreatment requirements are relatively high. Feed variability may cause problems as sufficient formers are needed to ensure proper operation. With temperatures commonly approximating 2500°F the slagging kiln is not a very high temperature process.

Summary of Versatility Scoring

	Criteria Scores				Total Score (1, 5)
	Wst Ex (1, 2)	Pre-Tr (0, 1)	Var (0, 1)	Temp (0, 1)	
FFHM	2	1	1	1	5
PTHM	2	1	1	1	5
GEHM	2	1	1	1	5
FFSM	2	0	0	0	2
PTSM	2	0	1	1	4
GESM	2	0	1	1	4
JHM	1	1	1	0	3
Slagging Kiln	2	1	1	0	4
Cyclone Melter	1	0	1	0	2
Molten Metal	2	1	1	1	5
Microwave	1	0	1	0	2

Residual Product Form

Fossil Fueled Hearth Melter

The potential to establish proper DRE has not been done for this technology. Chemistry should be readily controllable for achieving desired output. Demonstrated leaching data of residual product does not appear to exist. The potential for volume reduction should marginal based on the need for additives to lower process temperatures and addition of ash from fuel where coke is used.

Plasma Torch Hearth Melter

The PTHM should be capable of meeting DRE for organics, and, based on preliminary data, at least one current project should determine this. Chemistry of the melt should be readily controllable, particularly when considering the option of using differing plasma gasses. The PTHM produces a vitrified ash waste form which has been demonstrated to exhibit favorable leaching characteristics. Because of the loss of the loss of void space from vitrification and the lack of need for fluxes to obtain lower temperature melting, volume reduction is achieved.

Graphite Electrode Hearth Melter

Based on some PCB testing, DRE potential appears to be readily obtainable. Chemistry control of the melt should be easy to accomplish. Currency leaching data from residual slag appears to be lacking. For the same reasons as the PTHM, volume reduction is obtained.

Fossil Fueled Shaft Melter

The shaft melters will all appear to be inflexible as to the fate of metals in the residual. Chemistry control will be difficult to effect based on prefeeding materials and short column residence times. Leaching data has not been displayed. Volume reduction will not occur as additive materials will be needed to assure proper melting.

Plasma Torch Shaft Melter

The same basic discussion applies as for the fuel fired shaft melter. The exception is that higher temperatures are possible, and the overall volume should be smaller due to the lack of need for fluxes.

Graphite Electrode Shaft Melter

The same basic discussion applies as for the fuel fired shaft melter. The exception is that higher temperatures are possible, and the overall volume should be smaller due to the lack of need for fluxes.

Joule-Heated Melter

Metals could be oxidized in the JHM or allowed to collect at the bottom of the vessel for removal. Chemistry is readily controllable in this technology, and it has been demonstrated to provide a highly leach resistant product. Because of the addition of glassmaking materials, the final volume will increase.

Microwave Melter

The microwave will not be flexible in its handling of tramp metals. Chemistry control is somewhat obtainable for the molten product. Leach data doesn't appear to have been obtained. Fluxing agents will be needed to produce the molten product from the high melting point INEL constituents.

Molten Metal Bath

Control of the metal fraction of the waste is actually not applicable, but a favorable score will be granted. Chemistry control of the slag is touted as one of the prime benefits of the technology. No leaching data is available, as the technology is so new. Volume reduction of the material is obtained since temperatures should be high enough to provide melting without fluxes.

Cyclone Melter

Control of the metal fraction is not feasible for this technology. Chemistry control would be very difficult to effect based on the need to prefeed materials and the very short process zone residence time. Leaching tests have been conducted on some waste matrices. Volume reduction probably not be obtained based on the need for fluxes.

Slagging Kiln

Again, control of the metal fraction is not feasible for this technology. Chemistry control would be very difficult to effect based on the need to prefeed materials into the process, thus estimating proper chemistry with no method to make changes. Leaching tests have been conducted on some waste matrices. Volume reduction probably not be obtained based on the need for fluxes.

Summary of Residual Solid Product Scoring

	Criteria Scores				Total Score (1,5)
	Metal (1,2)	Chem (0,1)	Leach (0,1)	VR (0,1)	
FFHM	2	1	0	0	3
PTHM	2	1	1	1	5
GEHM	2	1	0	1	4
FFSM	1	0	0	0	1
PTSM	1	0	0	1	2
GESM	1	0	0	1	2
JHM	2	1	1	0	4
Slaggin Kiln	1	0	1	0	2
Cyclone Melter	1	0	1	1	3
Molten Metal	1	1	0	1	3
Microwave	1	1	0	0	2

Offgas Effluents

Fossil Fueled Hearth Melter

Being a fossil fueled process, the volume of the offgas will be high. A relatively large fraction of particulate can be expected based on the use of coke for processing. The process is not particularly high temperature, and should create little concerns in offgas handling, except for the size of the system.

Plasma Torch Hearth Melter

Being an electrical process rather than a fossil fuel fired process, the PTHM produces far less offgas volumes. Due to the low air rates in the primary, particulate entrainment and carryover should be reduced. Plasma systems operating on air have a tendency to produce high levels of NO_x, however, other torch gasses can be used. The very high temperatures of the process have a high tendency to volatilize heavy metals. Overall, offgas considerations are moderate.

Graphite Electrode Hearth Melter

Similar arguments apply for the GEHM as the PTHM above.

Fossil Fueled Shaft Melter

Being a fossil fueled process, the volume of the offgas will be high. A relatively large fraction of particulate can be expected based on the use of coke for processing. The process is not particularly high temperature, and should create little concerns in offgas handling, except for the size of the system.

Plasma Torch Shaft Melter

Being an electrical process rather than a fossil fuel fired process, the PTSM produces far less offgas volumes. Due to the low air rates, particulate entrainment and carryover should be reduced. Plasma systems operating on air have a tendency to produce high levels of NO_x, however, other torch gasses can be used. The very high temperatures of the process have a high tendency to volatilize heavy metals. Overall, offgas considerations are moderate.

Graphite Electrode Shaft Melter

The situation for the GESM is similar to that of the PTSM.

Joule-Heated Melter

Because electrical energy provides the melt heat rather than direct combustion heating, the quantity of the offgas is reduced and the quality is improved. The particulate load and the amount of gas to be treated is minimized, resulting in good contamination control and minimal offgas requirements. Lower operating temperatures lead to lower NO_x generation and lower tendency to volatilize heavy metals.

Microwave Melter

Because electromagnetic energy provides the heat for vitrification, the quantity of offgas very is low and particulate carryover is minimized. The technology operates in a glovebox, providing complete sealing. NO_x is not a concern, especially if nitrogen is excluded. Relatively lower temperatures minimize the potential volatilization of metals.

Molten Metal Bath

Volumes of offgas will be low, assuming operation with an electric heat source. Particulate control should be good based on under melt feeding of material. Metals volatilization will be a concern, as will NOx, based on the high temperature operation.

Cyclone Melter

Due to the efficiency of mixing and turbulence, the cyclone melter requires smaller quantities of excess air, but due to being a fossil fueled process, is much higher compared to other melters. The high turbulence and small feed material size required will lead to particulate formation and entrainment. The relatively higher process zone temperatures will create some concerns in the formation of NOx and the volatilization of heavy metals.

Slagging Kiln

The slagging kiln will require fuel feed to create the high temperatures, generating relatively high volumes of offgas. This results in relatively higher particulate generation and carryover than for other melters. The offgas treatment requirement of the slagging kiln is given a moderate because of the high temperature gas handling requirement, requiring special materials, consideration for metal volatilization and NOx generation.

Summary of Effluent Scoring

	Criteria Scores				Total Score (1,5)
	Vol (1,2)	Part (0,1)	Metals (0,1)	NOx (0,1)	
FFHM	1	0	1	0	2
PTHM	2	1	0	0	3
GEHM	2	1	0	0	3
FFSM	1	0	1	0	2
PTSM	2	1	0	0	3
GESM	2	1	0	0	3
JHM	2	1	1	1	5
Slaggin Kiln	1	0	0	1	2
Cyclone Melter	1	0	1	0	2
Molten Metal	2	1	0	0	3
Microwave	2	1	1	1	5

Operational Considerations

Fossil Fueled Hearth Melter

- Complexity: The FFHM will be a relative simple process to operate. Vessel configuration simple.
- H&S: Downgraded on high temperatures. Pressure sealed vessels will be hard to obtain.
- Maintenance: Increased refractory problems expected.
- Throughput: These systems are available to a very large capacity based on steel making equipment. Good efficiency in transferring energy to waste. Extreme high temperature possibility will increase throughput on a relative basis, but heating of offgas from combustible material processing will rob available heat.

Plasma Torch Hearth Melter

- Complexity: The PTHM will be a moderately complex process. Handling of high temperature molten material a concern. Vessel configuration simple.
- H&S: Downgraded on high temperatures and high voltages an industrial safety concern. Water breech from torch could lead to problems. Vacuum sealed water cooled vessels common and a big plus.
- Maintenance: Frequent torch electrode replacement required (100 to 200 hours operating time; modular replacement possible. Increased refractory problems expected.
- Throughput: Plasma systems are available to a moderate size capacity on the order of 6 MW. Good efficiency in transferring energy to waste. Extreme high temperature possibility will increase throughput on a relative basis.

Graphite Electrode Hearth Melter

- Complexity: The GEHM will be a moderately complex process. Handling of high temperature molten material a concern. Vessel configuration relatively simple. Control of are process difficult.
- H&S: Downgraded on high temperatures and high voltages an industrial safety concern. Pressure sealed vessels can be designed and used, but are usually not.
- Maintenance: Frequent torch electrode replacement required, but nowhere near as often as PTHM. Increased refractory problems expected.
- Throughput: Very large systems are available. Good efficiency in transferring energy to waste. Extreme high temperature possibility will increase throughput on a relative basis.

Fossil Fueled Shaft Melter

- Complexity: The FFSM will be a slightly more complex process to operate than a hearth process, due to waste feed process requirements, and concern for bridging. Vessel configuration simple.
- H&S: Downgraded on bridging problems. Pressure sealed vessels will be hard to design.
- Maintenance: Bridging will require extreme measures to solve. Maintenance of waste feed processing equipment will be needed. Some refractory problems expected.
- Throughput: Heating of offgas from combustible material processing will rob available heat, lowering throughput on a relative basis.

Plasma Torch Shaft Melter

- Complexity: The PTSM will be a slightly more complex process to operate than a hearth process, due to waste feed process requirements, and concern for bridging. Also torch operating function adds level of difficulty. Vessel configuration simple.
- H&S: Downgraded on bridging problems. Pressure sealed vessels will be somewhat easier to design. Electrical safety concerns.
- Maintenance: Torch electrodes require frequent replacement. Bridging will require extreme measures to solve. Maintenance of waste feed processing equipment will be needed. Some refractory problems expected.
- Throughput: Using electrical heat input, and with utilization of offgas to heat incoming feed, throughput should be among the highest.

Graphite Electrode Shaft Melter

- Complexity: The GESM will be very similar to the PTSM to operate and will score the same.
- H&S: Downgraded on bridging problems. Pressure sealed vessels will be somewhat easier to design. Electrical safety concerns are present.
- Maintenance: Torch electrodes require less frequent replacement than PTSM. Bridging problems will require extreme measures to solve. Maintenance of waste feed processing equipment will be needed. Some refractory problems expected.
- Throughput: Using electrical heat input, and with utilization of offgas to heat incoming feed, throughput should be among the highest.

Joule-Heated Melter

- Complexity: Relatively simple system; downgraded for handling of high temperature molten material. Chemistry control to keep bath molten will require attention. Presence of bulk metal could be a problem. Simple system to operate, thermally very stable.
- H&S: Credited for increased contamination control through low particulate. Possible to make a sealed process. Removing metal from process could be a problem.

Maintenance	Few moving parts; downgraded for molten material residue problems, need to remove metal from bottom of bath.
Throughput	Overall, throughput will be lower than optimum, based on the low process temperatures achieved, and thus the low heat transfer rate to the feed material.

Microwave Melter

Complexity	Relatively simple; sludge predrying is required. Simple device to operate.
H&S	Total glovebox operation is used, providing optimum contamination control. A plus is that the material is vitrified in its disposal container, enhancing contamination control. Molten materials are contained, no handling required; downgraded for uncertainty of electromagnetic energy leakage
Maintenance	Downgraded for lack of available information. Microwave generators are known to fail fairly often.
Throughput	Will be among the lowest in throughput. Very small size equipment available. Done a drum at a time.

Molten Metal Bath

Complexity	Moderately simple process to operate, scores the same as arc melters. Simple device to operate.
H&S	Same health and safety concerns as arc melters. Added concern for the introduction of water to the molten metal pool, possible steam explosion.
Maintenance	Again similar to hearth arc processes.
Throughput	Will be among the highest in throughput, having any one of many heat input devices possible.

Cyclone Melter

Complexity:	The process is relatively simple to operate since product is air conveyed and no moving parts are needed. Extensive feed preparation; however, adds some complexity. Preparing and feeding glass forming additives adds to complexity.
H&S:	Process operates as a sealed vessel. Provides for vitrification/agglomeration of ash, thus minimizes dispersion potential.
Maintenance:	Low maintenance devices even with frequent thermal cycling. High temperature process zone will lead to relatively more frequent refractory wear.
Throughput:	Throughput limited by ash handling capability. Unit capacities available are quite large. In general, low throughput potential.

Slagging Kiln

- Complexity: Handling of high temperature molten material a moderate complexity. Special materials required. Maintaining molten slag chemistry a operating concern. Rotating kiln problems same as rotary kiln. Oxygen enrichment or preheated combustion air required for adequate operation.
- H&S: Downgraded due to special high temperature and molten material. Slightly increased contamination control of vitrified ash. Potential for release on pressure excursion.
- Maintenance: Refractory maintenance requirements will be extreme. Kiln seal maintenance requirements high.
- Throughput: High throughput potential, large capacity units.

Summary of Operability Scoring

	Criteria Scores				Total Score (1,5)
	Comp (1,2)	H&S (0,1)	Main (0,1)	Thru (0,1)	
FFHM	3	1	1	1	3
PTHM	2	1	0	2	2.5
GEHM	2	2	1	2	3.5
FFSM	2	1	1	1	2.5
PTSM	1	1	0	2	2
GESM	1	2	1	2	3
JHM	2	2	1	1	3
Slaggin Kiln	1	1	1	2	2.5
Cyclone Melter	2	2	1	0	2.5
Molten Metal	2	2	0	2	3
Microwave	3	3	1	0	3.5

Relative Cost Scoring

	Total Score (1,5)
FFHM	5
PTHM	3
GEHM	3
FFSM	3
PTSM	1
GESM	1
JHM	3
Slaggin Kiln	1
Cyclone Melter	1
Molten Metal	3
Microwave	1

Appendix D

Technology Summary Descriptions

Appendix D

Technology Summary Descriptions

Rotary Kiln Incinerator

Technology Description

The rotary kiln is a cylindrical refractory-lined shell mounted on a slight incline. Rotation of the kiln provides for movement of waste through the kiln as well as for enhancement of waste mixing. Rotary kilns normally require a secondary combustion chamber to assure complete destruction of hazardous constituents. The primary chamber functions to pyrolyze or combust solid waste to gases. The gas-phase combustion reaction is completed in the secondary. Both primary and secondary chambers are generally supplied with auxiliary fuel systems. An extensive offgas system is generally required to control the high volume of emissions.

Past/Current Applications

Advantages

The most versatile type of conventional incinerator, it can handle a wide variety of solid and liquid waste types; a wider range of physical waste feed configurations is possible; ash is removed continuously and does not interfere with waste oxidation; can be operated at very high temperatures to handle difficult to destroy constituents; good turndown ratio.

Disadvantages

High capital cost for installation; high particulate loadings are often experienced; drying of some aqueous sludge waste or melting of some solid wastes can result in clinker or ring formation on refractory walls; spherical or cylindrical objects may roll through the kiln before complete combustion; not very thermally efficient, cannot be thermally cycled often (shutdown/startup cycle).

Problems

Maintaining proper seals at both ends of the kiln is a design and operational problem. Large volumes of air required for combustion give rise to large, costly, and difficult to operate offgas treatment systems. Offgas systems generate secondary by-product wastes that are often difficult to handle. Offgas systems are not capable of removing 100% of radioactive constituents, and thus some small amount of discharge is expected.

Research Needs

Better kiln seal design, advanced offgas systems, better stack monitoring and other real-time performance assurance capabilities; control of heavy metal emissions; combustion by-product formation; sub-micron particulate emissions.

Process Data

Status: Operational - Conventional

RCRA Handling Code: T07

Thermal Capacity Range: Low: MMBtu/hr
High: 150 MMBtu/hr

Rotary Kiln Incinerator

Controlled Air Incinerator

Technology Description

A controlled air incinerator is the name often used for the stationary hearth class of incinerator. This type of incinerator is usually designed as a two-stage combustion process with some systems using three chambers. Solid waste is fed into the primary chamber and burned at roughly 50 to 80% of the stoichiometric air requirement (starved air condition). This pyrolyzes the waste, thus emitting a volatile fraction with the required heat supplied by partial combustion and oxidation of the fixed carbon. The resultant smoke and pyrolytic products, consisting primarily of volatile hydrocarbons and carbon monoxide along with some combustion products, pass to the secondary chamber. Excess air is provided in the secondary chamber to assure complete combustion. Liquid waste can be incinerated in either the primary or secondary chambers. An offgas treatment system is required to provide emission control, dependent on the application and waste type.

Past/Current Applications

Advantages

The starved air condition in the primary chamber leads to a lower air velocity thus minimizing particulate entrainment and carryover; can be used to process a wide variety of wastes including solids, liquids, and sludges; can utilize a wide range of supplementary fuels; can handle wastes with high water content; low cost modular design; easy to control.

Disadvantages

Solid wastes generally have to be pre-treated or packaged in some fashion before they can be fed to the incinerator; not well suited for wastes containing fusible ash, large bulky solid wastes, or large quantities of essentially non-combustible materials (i.e. metal and glass); batch feeding of waste can lead to pressure spikes in the primary chamber.

Problems

Large volumes of air required for combustion give rise to large, costly, and difficult to operate offgas treatment systems. Offgas systems generate secondary byproduct wastes that are often difficult to handle. Offgas systems are not capable of removing 100% of radioactive constituents, and thus some small amount of discharge is expected.

Research Needs

Advanced offgas systems, better stack monitoring and other real-time performance assurance capabilities; control of heavy metal emissions; combustion by-product formation; sub-micron particulate emissions.

Process Data

Status: Operational - Conventional

RCRA Handling Code: T18

Thermal Capacity Range: Low: 0.1 MMBtu/hr
High: 50 MMBtu/hr

Controlled Air Incinerator

Fluidized Bed Incinerator

Technology Description

A vertical refractory lined vessel containing a bed of an inert granular material. The bed is "fluidized" by passing air, which serves as combustion air, through a perforated plate at the bottom of the vessel. Waste is fed to the hot bed for combustion where the high thermal mass and turbulent mixing action of the bed material rapidly transfers the heat to the waste. Auxiliary fuel is often used to maintain bed temperature. A secondary chamber may be required to ensure complete combustion for hazardous wastes. Limestone is usually added to the bed to provide capability for in-bed acid gas scrubbing capability (no scrubber required). Offgas particulate removal is required. A variation of fluidized bed technology is a circulating bed system where higher air velocities cause high carryover rates. The carryover material is recovered and returned to the system.

Past/Current Applications

Advantages

Relatively simple design (few moving parts); relatively lower capital and maintenance costs; long incinerator life; simplicity of operation; ease of process control; high thermal efficiency; lower operating temperatures leading to lower NO_x formation and metal emission rates; capability for in-bed scrubbing (eliminates the need for an offgas scrubber system); versatility (can accept solids, liquids, sludges, and gases).

Disadvantages

Relatively low throughput capacity; difficulty in removing residuals from the bed; high operating costs; solids will likely have to be pre-treated prior to introduction (shredded or sized); non-uniform residence times; high particulate entrainment rates.

Problems

Erosion of vessel and related components; offgas systems are not capable of removing 100% of radioactive constituents, thus some small amount of discharge is expected; low melting point materials in the bed may cause the bed to fuse.

Research Needs

Advanced offgas systems, better stack monitoring and other real-time performance assurance capabilities; control of heavy metal emissions; combustion by-product formation; sub-micron particulate emissions.

Process Data

Status: Operational-Conventional

RCRA Handling Code: T08

Thermal Capacity Range: Low: 0.1 MMBtu/hr
 High: 70 MMBtu/hr

Fluidized Bed Incinerator

Molten Salt Furnace^a

Technology Description

In the molten salt (MS) process, waste and air are continuously introduced beneath the surface of a sodium carbonate (Na_2CO_3) melt at a temperature of 750° to 1000°C. Supplemental fuel may be required if the waste is not sufficiently combustible. Rapid destruction of the waste results from the catalytic effect of the salt, and from the intimate contact of the waste with air and the hot molten salt, which provides rapid transfer of heat to the waste. The molten salt forms chemical complexes with toxic metals and radionuclides which reduces their thermodynamic activity and thus retains them in the salt. Sodium carbonate is used because it prevents emission of acidic gasses, such as HCl (ordinarily produced from organic chloride compounds) and SO_2 (from organic sulfur compounds). Also, it is stable, nonvolatile, inexpensive, and nontoxic. The carbon and hydrogen of the waste are converted to CO_2 and steam; halogens form their corresponding sodium halide salts; phosphorus, sulfur, arsenic, and silicon (from glass or ash in waste) form oxygenated salts; and the iron from metal containers forms iron oxide. The ash is trapped in the melt. The melt is removed periodically or batch-wise to prevent excessive build-up of halide salts or ash. If required, the melt can be immobilized prior to disposal in the appropriate burial facility. Molten salt produces clean gases which are released to the atmosphere, and spent salt. Spent salt can be disposed of without treatment, immobilized in cement or glass, or processed for metals recovery.

Past/Current Applications

Advantages

High waste destruction efficiency, high heat transfer rates; no liquid waste effluent; combustor is versatile, handling a wide variety of wastes; excellent temperature control due to thermal inertia of melt bed; no production or emission of acid gases; radioactive elements or heavy metals retained in salt.

Disadvantages

High ash waste requires greater salt make-up than liquid wastes (e.g. solvents); restricted to low-ash, low-water content wastes; feedstock must be size-reduced (will not accept large forms, e.g. 55 gal drum).

a. Gay, Richard L., Contact, Rocketdyne Division, Rockwell International Corp., 6633 Canoga Ave., Canoga Park, CA 91303, (818) 700-3505.

Problems

Special feed preparation and handling required for certain waste forms; material compatibility problems may result from some wastes; molten salt is corrosive to most metals.

Research Needs

Performance of materials of construction over range of salt chemical compositions and temperatures. Develop process for treatment of spent melt, e.g. process to separate ash from salt; develop process to recover radioactive elements or heavy metals from salt.

Process Data

Status: Emerging-Pilot/Emerging-Demonstration

RCRA Handling Code: T11

Thermal Capacity Range: Low: 0.2 MMBtu/hr
 High: 16 MMBtu/hr

Molten Salt Furnace

Cyclone Incinerator

Technology Description

The cyclone incinerator is a single hearth, vertical cylindrical vessel that by the tangential introduction of fuel and air, cyclonic flow is induced. The high-shear cyclonic flow provides intense mixing and complete combustion. Cyclonic incinerations are primarily used for sludges, but special furnaces have also been designed for gases or liquids. Typically, the hearth rotates with stationary rabble teeth for moving ash to a center discharge. Horizontal cyclone furnaces without hearths are also employed. These units carry the ash away with the offgas for downstream collection.

Past/Current Applications

Advantages

Stable and efficient combustion, small combustion volume, high energy density, centrifugal separation of offgas and particulate loading, long refractory life, low temperature requirements, fast startup and cool down, inexpensive, mechanically simple.

Disadvantages

Limited to gaseous, liquid, and sludge wastes.

Problems

None identified.

Research Needs

Destruction and removal efficiency determination.

Process Data

Status: Operational-Unique

RCRA Handling Code: T18

Thermal Capacity Range: Low: 1 MMBtu/hr
High: 150 MMBtu/hr

Research Needs

Advanced offgas systems; better stack monitoring and other real-time performance assurance capabilities; control of heavy metal emissions; combustion by-product formation; sub-micron particulate emissions.

Process Data

Status: Operational-Conventional

RCRA Handling Code: T09

Thermal Capacity Range: Low: 1 MMBtu/hr
High: 50 MMBtu/hr

Multiple-Hearth Incinerator

Cyclone Incinerator

Cyclone Incinerator Burner Cross-Section

Multiple-Hearth Incinerator

Technology Description

A multiple-hearth incinerator consists of a refractory-lined steel shell with a series of circular hearths arranged in a vertical design. A series of rotating, air-cooled rabble arms conveys the solid waste from upper to lower hearths. As the waste is conveyed down through the incinerator the successive hearths are used for drying, heating, combustion, burnout, and cooling of the waste. Fuel burners are mounted on the side of the vessel in the hearths where combustion and burnout occur. These burners can be used for high heat value hazardous liquids if desired. A secondary chamber may be required for complete destruction of hazardous wastes. Some form of air pollution control equipment will be required, and will vary with the waste being processed. This type of incinerator has been used principally for sludges, tars, or other low-heat value solids requiring long solids retention times, and has been commonly used for disposal of de-watered activated waste-water treatment sludges. Use of this type of incinerator has been largely abandoned.

Past/Current Applications

Advantages

Long solids retention times; ability to handle a wide range of wastes, including solids, sludges, liquids, and gases; ability to evaporate large amounts of water; ability to utilize a wide range of fuels.

Disadvantages

Inability to handle wastes that fuse into large chunks during incineration; high maintenance costs; not good for wastes requiring high destruction temperatures; susceptibility to thermal shock; solid wastes may have to be pre-treated (shredded) before processing.

Problems

Large volumes of air required for combustion give rise to large, costly, and difficult-to-operate offgas treatment systems. Offgas systems generate secondary byproduct wastes that are often difficult to handle. Offgas systems are not capable of removing 100% of radioactive constituents, and thus some small amount of discharge is expected.

Slagging Kiln Incinerator

Technology Description

A slagging kiln is an incinerator designed to operate at sufficiently high temperatures so that the entire charge of waste material essentially melts into a "slag". Almost all slagging kilns are based on an improved rotary kiln incinerator design (see "Rotary Kiln" entry for details), requiring more attention to the refractory lining and the slag handling equipment. Other designs are possible, however, as evidenced in one particular application of a German-designed multi-chamber slagging kiln. Slagging kilns normally require a secondary combustion chamber to assure complete destruction of hazardous constituents. The primary chamber functions to combust solid waste to gases at temperatures of 2000° to 2200° F, thus leaving a melted slag residue of the noncombustible components (i.e. alumina and silica compounds, metal, glass). The slag melt progresses through the kiln into a water quench, where it solidifies and fractures into small pieces, and is then drawn from the process. Both primary and secondary chambers are generally supplied with auxiliary fuel systems which can be used for liquid waste incineration. An extensive offgas system is generally required to control the high volume of emissions. Slagging kilns are generally used in applications involving high calorific value type wastes.

Past/Current Applications

Advantages

Can handle a wide variety of solid, liquid and sludge waste types; can accept whole metal drums of waste without breaching or shredding; slag is removed continuously and does not interfere with waste oxidation; when operated at very high temperatures leads to more complete burning and better destruction of difficult to destroy compounds; reduced offgas particulate loading due to adsorption into the slag; lower excess air requirements.

Disadvantages

High capital cost for installation; spherical or cylindrical objects may roll through the kiln before complete combustion; need to replace the refractory lining more often; higher temperatures increase probability of volatilizing heavy metals; not efficient for low calorific wastes; cannot be thermally cycled often (shutdown/startup cycle); feed composition must be tightly controlled.

Problems

Maintaining proper seals at both ends of the kiln is a design and operational problem. Large volumes of air required for combustion give rise to large, costly, and difficult to operate offgas treatment systems. Offgas systems generate secondary byproduct wastes that are often difficult to handle. Offgas systems are not capable of removing 100% of radioactive constituents, and thus some small amount of discharge is expected.

Research Needs

Better kiln seal design, slag chemistry, advanced offgas systems, stack monitoring and other real-time performance assurance capabilities; control of heavy metal emissions; combustion by-product formation; sub-micron particulate emissions.

Process Data

Status: Operational - Unique

RCRA Handling Code: T18

Thermal Capacity Range: Low: 5 MMBtu/hr
High: 150 MMBtu/hr

Slagging Kiln Incinerator

Cyclone Melter

Technology Description

A cyclone melting system utilizes cyclonic flow patterns to create high turbulence, which produces good mixing and heat transfer, enhancing combustion of organics and promoting melting, agglomeration, and separation of inorganics. Preheated combustion air (800 to 1100 °F), fuel (natural gas, fuel oil, or powdered coal) and the waste is injected tangentially into a cyclone barrel. Temperatures within the combustion chamber can reach 3000 °F. At this operating temperature the inorganic components of the feed material are melted and transported to the outer wall of the cylinder. The slag formed is tapped from the bottom of the chamber and quenched in a water bath. The resulting residue composition and quality is dependent on the waste feed composition and the addition of any glass making constituents. The organics are oxidized either within the primary chamber or in a secondary chamber with a separate burner.

Past/Current Applications

Original development centered around the combustion of crushed coal in electrical generating facilities. Past waste applications of the cyclone furnace/melting technology have been for the incineration of sewage sludge, liquid waste destruction, and the combustion of high inorganic (ash) coal. Current applications for incineration/vitrification of municipal solid waste (MSW) ash, incinerator ash, soils with particle size reduction, asbestos, and waste insulation fiberglass are being studied and are in various stages of development.

Advantages

The Cyclone melter is capable of achieving high destruction and removal efficiencies for organics mainly due to the high turbulence/mixing of the waste with the fuel/air mixture. This turbulence and mixing also promotes rapid heat transfer, allowing for the melting of inerts in a short residence time. The resulting slag residue is a glass-like material that should prove leach resistant.

Disadvantages

Chemistry of the residual solid product is difficult to control due to up-front estimation of waste feed characteristics, prefeeding estimated quantities of chemistry control additives, and short residence time effecting waste mixing and homogeneity. Other disadvantages include: restricted waste feed particle size, little control of fate of bulk metals, high temperatures and turbulence in the system generates thermal NO_x, and high temperature also volatilizes some heavy metals(e.g., Cd, Pb, Cr) which are transported into the off-gas system.

Research Needs

Research is needed to better define the slag characteristics resulting from the processing of various waste streams. Physical characteristics and chemical leaching characteristics are dependent on the types of waste processed and additives that may be added. Advanced testing needs to be performed on various anticipated waste compositions.

Process Data

Status: Emerging-pilot

RCRA Handling Code: T18

Thermal Capacity Range: Low: .70 MMBtu/hr

High: 425 MMBtu/hr

Cyclone Melter

Plasma Torch Hearth Melter^b

Technology Description

A plasma arc furnace uses the energy generated by what is known as a plasma arc "torch" to melt and vitrify inert waste components. The plasma torch is installed into a primary process chamber where the waste materials are fed. Organics present in the feed are processed through a combination of combustion and pyrolysis, depending on the atmosphere maintained in the primary. Pyrolyzed organics are further treated in a secondary combustion chamber to ensure complete destruction. The remaining inert material is brought to a molten state by the torch. The molten material is discharged from the chamber and forms a leach-resistant, vitrified (glassy) waste form when it cools. Furnace operation is similar to a dual chamber controlled air incinerator, where a plasma arc torch is used in the primary chamber rather than a fuel burner. This configuration allows operation with low primary chamber gas flows and, therefore, low particulate emissions.

One process variation of the plasma torch is called the Plasma Centrifugal Reactor (PCR). The PCR is a two-chamber incinerator that operates semi-continuously. Waste material is fed to a rotating primary chamber where rotation of the chamber at 50 rpm forces the molten slag toward the outer walls. After feeding approximately 1000 lbs. of inert material, the primary chamber rotation speed is decreased; the molten slag flows to the center of the chamber; the slag pours through a hole in the center of the primary chamber, falls through a secondary chamber, and is collected in a mold below the secondary chamber. Gaseous products are fully combusted in the secondary combustion chamber. The use of an air plasma and pure oxygen for combustion results in very low offgas volumes.

Past/Current Applications

Plasma arc torches have been used primarily in the metals production industry, particularly in the production of specialty metals, where control of the processing atmosphere is essential. The plasma arc torch has been demonstrated as a process for melting and vitrifying incinerator ash, and systems are now being constructed in Japan for this application. Two PCRs have been built, one of which has been demonstrated on a soil matrix, the other on a heterogeneous hazardous waste.

Advantages

Solid byproduct is a vitrified "glassy" slag that is excellent for stabilization of toxic metals and radionuclides; quiescent combustion in primary chamber results in reduced particulate emissions; plasma energy assists carbon burnout; reduced offgas volume decreases air pollution control equipment costs.

b. Eschenbach, R. C., private communication, June 1990, Retech Inc, Ukiah, CA.

Disadvantages

Significant electrical energy requirements; operation, start up, and control are more complex than conventional incineration. For the PCR, it is a complex system, with moving parts and rotating seals. The electrode in the plasma torch requires frequent replacement, with current life on the order of 100 - 200 hours.

Research Needs

Optimization of slag chemistry for metals stabilization; evaluation of variation in slag chemistry resulting from variations in the input stream; re-introduction of condensed volatile metals into slag phase; electrode life studies; DRE of hazardous organics.

Process Data

Status: Emerging-Bench

RCRA Handling Code: T18

Thermal Capacity Range: Low: 100 kW

High: 6 MW

Plasma Torch Hearth Melter

Graphite Electrode Hearth Melter^c

Technology Description

The graphite electrode hearth melter technology encompasses a variety of electrically powered furnaces/melters. These furnaces use electrical energy transferred through graphite electrodes to melt raw materials (ore, slag waste, scrap, etc.) charged into a molten bath. The electrodes may be submerged in the molten bath where the resistance to the electrical current passing between the electrodes creates the temperatures necessary to melt the material, or they may remain above the surface of the bath creating an arc plasma zone of high temperature. Temperatures up to 3000 °F are routinely maintained within the furnace chamber with even higher temperatures achievable. The high temperatures of the molten bath quickly destroy the organic components while melting the inert material into a glassy slag. A closed-furnace (sealed) system design would provide better offgas contamination control when dealing with radioactive and hazardous waste. Material feed for the closed furnace arrangement can be provided through feed handling chutes, hollow electrodes, or a series of air-lock doors. Material with grain sizes from 1/4" to 2" diameters can be fed through the chutes while fines (< 1/4") can be fed through the electrodes. Larger containers and objects can be fed through the air-lock door system.

Past/Current Applications

The electric-arc melting technology has been used in the steel industry for many years. Applications have focused on secondary smelting and metals recovery from steel making dusts and scrap iron. Current steel applications for sealed systems are for pig-iron smelting in a reducing atmosphere. New applications in the waste processing area are being demonstrated. An Arc Pyrolysis unit using a direct current electric arc furnace has been designed specifically for the treatment of solid hazardous waste. Limited data on this process is available at this time.

Advantages

Electric-arc furnaces can handle a wide variety of waste forms and sizes, depending on whether an open or closed system is used. The use of electrical energy rather than a fossil fuel for melting and combustion of the waste material significantly reduces the volumes of offgas and associated pollution control equipment requirements. Additionally the slag residue produced is a vitrified material that is likely to be a very stable waste form.

c. Cotchen, J. K., private communication, LECTROMELT Corporation, Pittsburgh, PA, July 1991.

Disadvantages

The high operating temperatures of the system volatilize heavy metals such as cadmium, lead, and chromium. Electrode consumption is high, particularly in an oxidizing environment. The potential for accidental feed of water below the molten surface of the melt could cause a steam explosion. Additionally high turbulence causing offgas control difficulties may result from the introduction of high combustible waste streams.

Research Needs

Optimization of slag chemistry for heavy metals stabilization; evaluation of variations in slag chemistry resulting from variations in the input waste; reintroduction of condensed volatile metals into the slag phase. Additional testing and evaluation of technology performance on anticipated waste compositions must be performed.

Process Data

Status: Emerging-pilot scale

RCRA Handling Code: T18

Thermal Capacity Range: Low Range: 0.2 MMBtu/hr

High Range: 164 MMBtu/hr

Graphite Electrode Hearth Melter

Fossil Fueled Shaft Furnace (Cupola)

Technology Description

The traditional cupola is a vertical cylindrical water-cooled shaft furnace commercially used in the foundry industry. The process feed material, typically consisting of scrap iron and steel along with coke and limestone, is fed into the furnace from the top, and the combustion (blast) air is introduced through tuyeres at the base of the vessel. The combustion of the coke and the counter current flow of the product gases through the charge material supply the heat necessary to melt the iron. The cupola furnace is operated in a reducing atmosphere to promote the reduction of metallic oxides associated with the iron scrap charge. The primary product gases are carbon monoxide (CO) and hydrogen (H₂). Limestone is the primary fluxing agent added to slag the coke ash and other non-combustibles. Metal and slag are tapped from the bottom of the furnace and the CO and H₂ are fed into an air enriched afterburner to complete combustion of the CO, H₂, and any volatiles. Conventional cupola furnaces operate with a metal to coke weight ratio of approximately 10:1 with 90% of the coke is consumed in heating and 10% added as carbon to the metal.

Variations of the basic cupola "cold-blast" (no waste heat recovery) furnace have been developed over the years. A hot-blast cupola furnace was developed to recover the sensible heat in the exhaust gases and increase the blast temperatures to 400 °C. Additional developments have centered around the use of auxiliary fuels such as natural gas, oil, anthracite coal and plasma arc (electrical) to minimize the quantity of coke needed as well as increase the productivity while decreasing the environmental impact of off gas products.

Past/Current Applications

The cupola (shaft) furnace is a very mature secondary smelting foundry technology. New areas of application are focusing on the waste treatment potential of these furnaces. With the addition of plasma torches and other auxiliary sources of heat energy, the cupola furnace may have potential waste processing applications.

Advantages

Shaft furnace smelting is a mature technology and considerable experience in adapting auxiliary heat sources (e.g., plasma arc) to enhance system flexibility have been tested and verified in the foundry industry. This experience will influence future development, however the technology is limited by the lack of development for waste treatment.

Disadvantages

Conventional fossil fuel-fired cupola furnaces have significant gas velocities which prevent the charging of fine material. Fines and small particles are easily entrained and carried into the pollution control equipment. Bridging and freezing of the charge material can occur. Non-homogeneity of feed material can cause slag chemistry control problems and temperature excursions within the furnace.

Process Data

Status: Emerging technology

RCRA Handling Code: T18

Thermal Capacity Range: Low: 4 MMBtu/hr
High: 250 MMBtu/hr

Fossil Fuel Shaft Furnace

Plasma Torch Fired Shaft Furnace^d

Technology Description

The Plasma-fired cupola operates in much the same way as the conventional fossil fuel-fired cupola except it utilizes plasma torches as an auxiliary source of thermal energy. The plasma torches are symmetrically located at the base of the vessel in the areas of the tuyeres. The plasma torches superheat the blast air up to 1000 °C. This heat source decreases the amount of coke necessary in the feed, which greatly reduces the volume of offgas generation. The decrease in offgas generation reduces the gas velocities within the furnace allowing finer material to be charged and processed. Process gases (e.g., CO, H₂) from the top of the furnace are recycled through the plasma torches additionally reducing offgas volumes. The product gases not recycled are fully oxidized in an air enriched afterburner as in the conventional cupola.

Past/Current Applications

Plasma-fired cupola furnaces have been commercially applied in the foundry industry. Plants applying this technology both in the U.S. (General Motors) and abroad (Peugeot) have verified the benefits of using plasma arc fired cupolas in foundry applications. Westinghouse Electric is presently involved in extending the application of this technology to hazardous waste treatment. Limited information is currently available on the testing of this pilot scale system.

Advantages

The Plasma-fired cupola has a number of advantages over the conventional coke fired cupola. The reduction of coke use reduces cost, decreases offgas generation and particulate emission by reducing superficial velocities within the furnace. The auxiliary heat source provided by the plasma allows flexibility in waste input characteristics and melt temperatures can be controlled rapidly reducing bridging problems.

Disadvantages

As with conventional cupola furnaces the "bridging" of the charge material can occur. Residual solid product chemical and physical characteristics is very difficult. Slag chemistry is only controllable based on initial feed characteristics, waste density and waste mixtures. Estimation of feed parameters, fluxing additives, and non-homogeneity of waste will cause final waste form

d. Dighe, S. V., private communication, Westinghouse Electric Corporation, Madison, PA, September 1991.

variations. Additionally channeling of offgas through the charge material causes variation in bed temperatures and other operational parameters.

Research Needs

Continued testing and development for waste treatment applications is necessary. Characteristics and mixes of charge material variations and resulting slag chemistry needs further study.

Process Data

Status: Emerging-bench scale

RCRA Handling Code: T18

Thermal Capacity Range: Low: 4 MMBtu/hr
High: 41 MMBtu/hr

Plasma Torch-Fired Shaft Furnace

Graphite Electrode Shaft Furnace

Technology Description

The graphite electrode shaft furnace technology focuses around the use of electrical energy rather than fossil fuels, transmitted through an electric arc to pyrolyze hydrocarbons into partially oxidized gaseous components (CO , H_2 , tars, gums, etc) which are subsequently fully oxidized in an air rich afterburner. The pyrolyzing concept of incineration utilizes a starved air environment in the primary chamber to obtain the partially oxidized effluent.

A variation to the typical pyrolysis process is known as the Skygas process. The skygas process depends on an electric arc initiating the dissociation and activation of water within the reactor and the feed to create gaseous radicals of H_2 and OH . The gaseous radicals pass up through the waste initiating a chain reaction and propagation of additional free radicals and non-radicals. The large hydrocarbon molecules are thus broken down into partially oxidized gaseous components. Predominate gas products from the skygas process are the same as the basic pyrolysis process and consist primarily of CO , and H_2 .

The gases exiting the primary chamber are again subjected to an electric arc and passed through a coke bed for additional refining and breakdown of tars and gums.

Past/Current Applications

Controlled air pyrolysis using fossil fuels as the heat source have been used as a waste treatment process for many years. The use of a controlled air electric arc process in a waste treatment application is new. Limited data is currently available on the application of this technology to waste treatment.

Advantages

The use of an electric arc rather than fossil fuels to pyrolyze and/or initiate radical chain reaction chemistry will reduce the offgas volume generation which will reduce pollution control handling requirements. Multiple sets of reactor units in the skygas process would further reduce carbon dioxide and tars/gums resulting in a higher quality of gas product for reuse.

Disadvantages

As with other shaft furnace technologies bridging of the charged material within the shaft is a problem, especially if high percentages of low melting materials (e.g. glass) exist within the feed material. The resulting residue from the primary reactor of the SkyGas process is a non-vitrified

ash. Limited feed handling capabilities were noted in testing of chopped tire feed and high moisture content sludges.

Research Needs

Limited data exists on the application of this technology on waste streams of mixed composition. Additional testing and documentation of process data, operational parameters and waste acceptability needs to be performed. Final waste form (ash) stabilization not well addressed in the Skygas process.

Process Data

Status: Emerging technology

RCRA Handling Code: T18

Thermal Capacity Range: Low: 4 MMBtu/hr
High: 41 MMBtu/hr

Graphite Electrode Shaft Furnace

Joule-Heated Melter^e

Technology Description

A refractory lined reactor in which a pool of glass is initially melted by auxiliary heating, then maintained in a molten state (2000°-2300°F) by joule heating (electric current passing through the glass between submerged electrodes). Waste is introduced into one end of the furnace above the molten glass along with combustion air. Combustion is achieved by exposure to the radiant heat above the pool or by contact with the molten pool. Exhaust gases flow out the opposite end of the furnace. Solid products of combustion and noncombustible materials are encapsulated in the glass, which can be continuously removed or batch discharged to solidify into a non-leachable matrix. A feeding variation by one developer introduces the waste and air into the body of the molten glass via a drop tube. This arrangement is intended to confine most of the combustion below the surface of the pool, enhance intermixing of the waste and combustion gases with the glass, and attain higher particulate retention.

Past/Current Applications

Advantages

Compatible with most forms of hazardous wastes; high temperatures result in high DRE's; encapsulation of hazardous materials in non-leachable glassy matrix; simple and compact design; technology proven for non-waste applications; non-flame combustion eliminates fuel-PIC contamination of offgas; offgas treatment residues (filter, ash, scrub liquors) can be disposed of by processing through the melter; high thermal stability provided by molten pool.

Disadvantages

High moisture content wastes must be pre-treated to minimize moisture; dense solids tend to settle out of the glass; significant waste metal content affects electrode operation; relatively high energy and capital costs; technology unproven for hazardous wastes.

Research Needs

Demonstrate effectiveness in treating hazardous wastes; investigate partitioning of nuclides and heavy metals in glass.

e. Penberthy, Larry, Contact, Penberthy Electromelt International, Inc., 631 S. 96th St., Seattle, WA 98108, (206) 762-4244.

Process Data

Status: Operational-Unique

RCRA Handling Code: T18

Thermal Capacity Range: Low: 1.8 MMBtu/hr

High: 78 MMBtu/hr

Joule-Heated Melter

Microwave Melter

Technology Description

This process utilizes microwave energy for in-container solidification/stabilization of radioactively contaminated non-organic wastes such as incinerator ash, sludges, or soils. Waste moisture is removed in a belt-driven microwave dryer prior to treatment. The dry waste materials are vitrified inside a metal disposal container in either a batch or continuous feed mode. Melt temperatures range from 1800°-2600°F and the resulting product is a glassy monolith that meets radioactive disposal criteria for liquid and particulate content, and RCRA LDR requirements for leaching of toxic hazardous constituents. The process results in volume reductions on the order of 80% with waste loadings on the order of 60%.

Past/Current Applications

Advantages

Direct application of energy to the wastes - surrounding equipment remains relatively cool; process occurs inside disposal container, minimizing waste handling.

Disadvantages

Applicable to dry or near-dry non-organic wastes only; waste must be relatively homogeneous fines.

Problems

Uneven melting of the wastes, especially near the bottom and sides; some oxidation of the metal waste container; melt-through of the container at hot spots.

Research Needs

Evaluation of the process for other applications, i.e. destruction of hazardous wastes; leachability of the vitrified waste.

Process Data

Status: Emerging-Pilot

RCRA Handling Code: T18

Thermal Capacity Range: Low: 0.02 MMBtu/hr

High: 0.32 MMBtu/hr

Microwave Melter

Molten Metal Bath Technology^f

Technology Description

The molten metal bath technology is a treatment process which utilizes a pool of molten metal as the medium to transfer heat to the waste material. The high temperatures associated with the molten metal destroys the organics and melts the inorganics into a glassy slag matrix. The slag is drawn off the top of the melt and the bath is maintained by tapping off or adding metal as required. As with other melting processes fluxing agents can be introduced to enhance the melting of the waste. Temperatures of the metal bath can range from 2500 °F to 3500 °F with 3000 °F being the typical average. Acceptable waste forms are gases, liquids, sludges, and solids (with size reduction). Oxygen can be injected into the bath to strip the carbon absorbed by the steel thus forming carbon monoxide. The furnace is operated in a reducing atmosphere to reduce the metal oxides.

Past/Current Applications

Metal bath processes have been used in the steel making industry for many years. Development of the technology for waste treatment applications is relatively recent. U.S. Steel developed a metal bath technology termed the catalytic extraction process (CEP). Testing has been conducted on organics with metals, municipal waste, sludges, flyash, and other chemical and industrial waste materials.

Advantages

With the high temperatures in the metal bath and the rapid heat transfer to the introduced waste a high destruction efficiency of organics can be achieved. The final waste form is a vitrified slag that is likely to be highly stable and leach resistant. Operation in a reducing mode minimizes the high thermal NO_x that is normally generated in a high temperature process.

Disadvantages

Slag chemistry is highly dependent on waste characteristics and may be difficult to control with non-homogeneous waste inputs. High temperatures result in high volatilization of heavy metals which are carried into the offgas equipment. Introduction of significant quantities of wet solids or non-combustible liquids may cause steam explosion concerns.

f. Metelmann, O., private communication, Mannesmann Demag Corporation, Coraopolis, PA, July 1991.

Research Needs

Primary research needs are in the areas of partitioning of radionuclides and heavy metals within the bath, variation of slag chemistry resulting from variations in waste composition, and continued demonstration of effective hazardous waste destruction.

Process Data

Status: Emerging pilot

RCRA Handling Code: T18

Thermal Capacity Range: Low:

High:

Fossil Fuel Hearth Melter^g

Technology Description

The fossil fuel hearth melting technology is a thermal smelting technology consisting of a molten slag bath into which metal ore, blast furnace slag, and other waste materials are introduced. The specific process variation addressed here is an adaptation of a proprietary commercial metal smelting technology, known as "Sirosmelt." The sirosmelt process utilizes a lance through which air and fuel can be injected under the surface of the slag bath. This injection of air fuel mixture creates high turbulence within the bath providing good mixing and combustion of the waste. The system is flexible in producing an oxidizing or reducing environment depending on the waste being processed. Operational temperatures of the molten bath of as much as 1600 °C destroy the organics and melts the inert fractions into a vitrified slag product. Fluxing agents can be introduced to enhance the process by lowering the melting temperatures of the inorganic mixture. Fine particulate wastes, such as flyash and dusts can be introduced into the bath through the lance while larger particle waste forms are fed through an auxiliary feed port. The resulting slag of melted inert material is removed and cast into 1 to 2 ton blocks.

Past/Current Applications

Past applications of the hearth melting technology has primarily been in the secondary steel smelting industry. The potential use of the Sirosmelt process in waste treatment applications is in very preliminary stages.

Advantages

Lance injection of air creates excellent waste/bath mixing for maximum combustion, relatively simple operating concept with few moving parts, high temperatures resulting in high waste destruction efficiencies.

Disadvantages

High temperatures within the system will volatilize metals and will generate NO_x, the high turbulence will cause high particulate carryover, and contamination control problems in a non-sealed furnace configuration.

g. Lightfoot, B., private communication, Ausmelt Pty. Ltd., Victoria, Australia, May 1991.

Research Needs

The primary research need is to develop and demonstrate the operability of the technology as a waste treatment process. The Siros melt process has had very limited testing. As with other melting technologies effects of heterogeneous waste streams on slag chemistry and process operations well as fate of heavy metals and radionuclides needs further investigation.

Process Data

Status: Emerging bench

RCRA Handling Code: T18

Thermal Capacity Range: Low: 0.9 MMBtu/hr

High: 4.5 MMBtu/hr

Fossil Fuel Hearth Melter

END

**DATE
FILMED**

6 / 16 / 92