EGG-WTD-9214
November 1991

APR 27 1992

**Idaho
National
Engineering
Laboratory**

*Managed
by the U.S.
Department
of Energy*

INFORMAL REPORT

**Summary of In Situ Vitrification
Modeling and Analysis
Accomplishments for Fiscal Year 1991**

Calvin E. Slater

*Work performed under
DOE Contract
No. DE-AC07-76ID01570*

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

This document contains new concepts or the author(s) interpretation of new calculations and/or measurements; accordingly, EG&G Idaho, Inc. is required by the United States Government to include the following disclaimer:

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights. References herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

EGG-WTD--9214

DE92 013100

SUMMARY OF IN SITU VITRIFICATION MODELING AND ANALYSIS ACCOMPLISHMENTS FOR FISCAL YEAR 1991

Calvin E. Slater

Published November 1991

Idaho National Engineering Laboratory
EG&G Idaho Inc.
Idaho Falls, Idaho 83415

Prepared for
U.S. Department of Energy
Office of Environmental Restoration and Waste Management
Under DOE Field Office, Idaho
Contract DE-AC07-76ID01570

MASTER

ds
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

**SUMMARY OF IN SITU VITRIFICATION
MODELING AND ANALYSIS
ACCOMPLISHMENTS FOR FISCAL YEAR 1991**

Reviewed by:

Ken Merrill

23 Sept 91
Date

Prepared By:

Calvin E. Slater

20 Sept 91
Date

ABSTRACT

The in situ vitrification (ISV) modeling activities encompass a variety of both modeling development efforts and analysis applications in support of the ISV project. The model development effort is directed toward modifying or developing a set of computer codes to simulate the ISV process. These codes are used to perform safety and environmental hazards analyses, assist in experimental test planning and design, assist in equipment design and development of operating procedures, and provide enhanced understanding of the ISV process.

This report presents a summary description of the accomplishments in Fiscal Year 1991 for both the model development and analysis areas. Brief descriptions of the models that were developed and the more important conclusions from the analytical studies are presented.

ACKNOWLEDGMENTS

The work reported in this document is the result of the contributions of many individuals. The major contributors are:

Michael O. Fryer
William H. Grush
Grant L. Hawkes
Paul G. Jacobs
Michael A. Langerman
Robert J. MacKinnon
Earl S. Marwil
Paul R. McHugh
Vince A. Mousseau
Paul E. Murray
Hoa D. Nguyen
Mark J. Oliver
Scungho Paik
John D. Ranshaw
Calvin E. Slater
Thomas E. Wierman.

CONTENTS

ABSTRACT.....	iii
ACKNOWLEDGMENTS.....	iv
1. INTRODUCTION.....	1
2. MODEL DEVELOPMENT ACTIVITIES.....	2
2.1 APOLLO.....	2
2.2 MAGMA.....	3
2.3 TOUGH.....	4
2.4 VESTA.....	4
2.5 VULCAN.....	5
2.6 Simplified Flow Simulation.....	5
2.7 Graphics.....	7
3. APPLICATIONS AND ANALYSIS ACTIVITIES.....	8
3.1 Simulation of PNL Test.....	8
3.2 VULCAN Parametric Studies.....	8
3.3 Pressurization beneath the Melt.....	10
3.4 Scaling.....	18
3.5 Off-Gas Estimate.....	18
4. SUMMARY.....	19
5. REFERENCES.....	20
APPENDIX A--PUBLICATIONS, REPORTS, AND PRESENTATIONS.....	A-1
APPENDIX B--ISV SUPPORT ACTIVITIES.....	B-1

FIGURES

1. Temperature profile comparison.....	6
2. Melt volume cross sections.....	9
3. Schematic of conditions in the region surrounding an ISV melt.....	11
4. One-dimensional problem domain.....	12

5.	Temperature as a function of distance.....	14
6.	Saturation as a function of distance.....	15
7.	Pressure as a function of distance.....	16
8.	Velocity as a function of distance	17

TABLES

1.	Equilibrium composition of pyrolysis problem.....	3
----	---	---

SUMMARY OF IN SITU VITRIFICATION MODELING AND ANALYSIS ACCOMPLISHMENTS FOR FISCAL YEAR 1991

1. INTRODUCTION

The in situ vitrification (ISV) modeling activities encompass a variety of both modeling development efforts and analysis applications in support of the ISV project. The model development effort is directed toward modifying or developing a set of computer codes to simulate the ISV process. These codes are used to perform safety and environmental hazards analyses, assist in experimental test planning and design, assist in equipment design and development of operating procedures, and provide enhanced understanding of the ISV process.

The ISV process is a complex process that involves the interaction of several physical and chemical phenomena. To make the modeling tractable, the important phenomena are separated into seven major categories. These categories include: electrical resistance heating, thermal energy transport with melting, process chemistry, off-gas release from the melt, gas transport in the soil, flow and combustion in the off-gas hood, and viscous flow in the melt. The approach used in developing the set of ISV codes is to develop separate models for each of the seven major categories and then integrate the models where required. Where possible, existing computer codes are modified to meet the specific requirements of the ISV process.

The development of this set of codes is now in the second full year of development. This report describes the development activities that occurred during Fiscal Year 1991 and also presents applications and analyses performed with the codes to evaluate and validate the codes, resolve technical issues, and enhance understanding of the ISV process.

The following sections of this report present a summary description of the development activities, and present a brief description and the more important conclusions from the code applications. Appendix A lists the publications, reports, and presentations that were presented during Fiscal Year 1991. These reports furnish a more detailed description of the models for the interested reader. Appendix B presents a brief description of other activities performed by modeling personnel in support of the ISV programs.

2. MODEL DEVELOPMENT ACTIVITIES

The model development activities in Fiscal Year 1991 included modifying and extending existing computer codes as well as development of new models and computer codes. The initial versions of the APOLLO, MAGMA, and VESTA computer codes were completed and the capabilities of the VULCAN and TOUGH computer codes were enhanced with the addition of new models this year. The following sections present brief descriptions of the model development accomplishments. Details of the codes and models can be found in the reports listed in the References and Appendix A.

2.1 APOLLO

The APOLLO computer code¹ was developed this year to assist in predicting the composition of the gases that are formed during the ISV process. In several proposed sites for ISV applications, there are a variety of chemical compounds that will be encountered in the waste. These compounds may react or pyrolyze and thus produce gases that will rise through or around the melt to the combustion hood. The combustible gases will burn in the combustion hood and ultimately pass to the off-gas treatment system. The APOLLO computer code calculates the composition and state of the compounds that are formed as the melt progresses through the waste. Although the code is developed primarily for ISV applications, the model should be applicable to other technologies that involve chemical reactions or pyrolysis.

The APOLLO computer code calculates both equilibrium and kinetic reactions. It is anticipated that for most compounds that enter the melt, the temperature and residence time will be sufficient for equilibrium to be reached. However, for gases that pass around the melt or through the melt very quickly, a kinetics model is required.

Although there are existing equilibrium codes that are available, none of them meet the specific requirements of quality assurance and computation time. As the number of compounds increases, the computation time for some of the available codes becomes prohibitively long. The numerical technique used in the APOLLO computer code greatly reduces the number of equations that must be solved and hence the computation time.

Code calculations show excellent agreement when compared with literature values (see Reference 1). As an example, the results of a simple pyrolysis calculation are presented and

compared with literature values in Table 1. The problem is to determine the equilibrium composition at 1000 K of a mixture initially composed of unreacted methane and water. The code converged in five iterations to four decimal places. The agreement with literature values is excellent.

Table 1. Equilibrium composition of pyrolysis problem (mole fraction)

	H ₂	CH ₄	H ₂ O	CO	CO ₂
APOLLO	0.6695	0.0199	0.0995	0.1753	0.0359
Ref. 2	0.6694	0.0199	0.0995	0.1753	0.0359

Further testing indicated that additional work does need to be done to improve the code's capability when both liquids and solids are present. However, this does not pose a significant problem for present ISV applications.

In summary, the APOLLO computer code has been developed for the analysis of complex chemical systems. The code can calculate both equilibrium and kinetic reactions. Initial validation by comparison with literature values shows excellent agreement.

2.2 MAGMA

The MAGMA computer code³ was developed this year to analyze the flows inside the ISV melt. Due to heating from the electrodes and the variation in melt density with temperature, there is the potential for developing natural convection flows in the melt interior.

MAGMA is a finite difference computer code that simulates three-dimensional incompressible viscous flow and heat transfer. The code uses a new fully implicit technique to solve the incompressible Navier-Stokes equations. The energy equation is differenced explicitly in time. One of the unique features used in the numerical solution of the momentum equation is the use of indirect addressing. This technique avoids unnecessary calculations in inactive cells.

Calculations using the MAGMA computer code have been compared with several analytical and test problems found in the literature. The results of these comparisons are presented and discussed in detail in Reference 3 and will not be repeated in this report. In general, the code calculations compare favorably both qualitatively and quantitatively with literature values and clearly demonstrate the codes capability to calculate two-dimensional conduction, two- and three-dimensional natural convection, and natural convection during melting.

2.3 TOUGH

The TOUGH computer code⁴ developed at Livermore was selected as the basis for developing a model for analyzing contaminant migration. The released version of the TOUGH computer code simulates the transport of water, vapor, air, and heat in porous and fractured media. Ultimately, the capability of simulating an organic phase would need to be added. However, for the present, the code is a valuable tool for studying the behavior of water and its vapor. Modifications were made to the code so that it could better represent the ISV process. Specifically, a moving melt front capability was added and the temperature restraints were removed so that the high temperatures experienced in the ISV process could be accommodated.

Calculations have been made with the modified code to evaluate its ability to meet the requirements of ISV applications and to study the pressure buildup under the ISV melt. These calculations are discussed in a later section.

2.4 VESTA

The VESTA computer code⁵ was developed this year to simulate flow, pressure, and combustion in the ISV combustion hood. The COYOTE computer code⁶ was originally selected as the model for simulating the flow, pressure, and combustion in the ISV hood. However, it was found that due to the explicit numerical scheme used in the code, that the computation time was excessive for long-term ISV applications. Therefore, the VESTA development was initiated. The VESTA program is based on the SIMPLE numerical method which is a velocity-pressure correction method to implicitly solve the transient compressible form of the Navier-Stokes equations. In this method, the pressure correction equation is formulated so that the discretization equations are robust to all flow velocities. Densities are calculated directly from the pressure field. Calculated results from the code have been

compared with literature values (see Reference 5) and the agreement is good. For example, VESTA calculations are compared with COYOTE calculations in Figure 1. The calculations simulate the flow and combustion in an intermediate scale off-gas confinement hood. The laminar flow case compares well. The computation time for VESTA is about one-tenth that of COYOTE.

2.5 VULCAN

The VULCAN computer code⁷ was modified this year by adding two models that allow VULCAN to simulate the subsidence and density stratification that occur during the ISV process.

During the ISV process, the volume of the pore spaces in the soil is released and, as a result, the top of the melt subsides below ground-surface level. Also, many waste forms have a significant amount of void space that is released during the ISV process which also results in considerable subsidence.

The algorithm for accounting for subsidence adjusts the height of the nodes in the finite element mesh so that the mass in each element remains constant. This enhancement to VULCAN has been implemented and successfully tested. However, due to the lack of appropriate experimental data, calculations have not been compared to data.

The second enhancement to VULCAN that was initiated this year is a stratification model that allows more dense material to remain or sink to the bottom of the melt. The initial coding has been completed and verified on a subroutine basis. However, the routines have not been integrated into the main code.

2.6 Simplified Flow Estimation

It is desirable to couple a flow field solution to the conduction and electrical field solution of the VULCAN computer code. However, calculating velocity fields is usually very computation intensive and can greatly increase the required computation time. In some cases, the computation time becomes prohibitively long for practical application. To circumvent this problem, a development effort was initiated to develop a method of estimating the effects of natural convection on temperature distributions in the melt without explicitly solving for the velocity fields. The method could then be implemented in the VULCAN computer code

Figure 1. Temperature profile comparison.

and significantly enhance its capabilities with little cost in computation time. With the addition of the simplified flow estimation model, the VULCAN computer code could then be utilized to assess scaling distortions due to velocity fields.

The approach used involves a coupled solution to Laplace's and Poisson's equation which describe the velocity and temperature fields, respectively. Simplifying assumptions include that the fluid is inviscid and incompressible, and the motion is irrotational. Constant physical properties are also assumed in the formulation of the temperature field equations. The method has been tested by comparison to literature solutions for flow along a heated vertical plate and flow in a thermally driven cavity. The agreement with literature values was reasonable.

The method is not intended to give detailed velocity information but, rather, the overall effects of velocity on temperature distribution. It is anticipated that the method could be implemented in the VULCAN computer code as a future development effort and significantly enhance the codes capabilities.

2.7 Graphics

The transient three-dimensional computer codes that comprise the set of codes for simulating the ISV processes produce large volumes of data. Analyzing and comprehending all of this data is a formidable task. To aid in this effort, graphical and visualization software was developed that make the data much easier to comprehend. The software can use data files produced by the various codes to produce three-dimensional colored images that make understanding the ISV processes much easier. The software can also use the time variable and produce movies. The visualization software has not only been valuable in understanding the ISV processes but has been very useful in debugging the codes during their development.

3. APPLICATIONS AND ANALYSIS ACTIVITIES

Several calculations and analyses were performed this year to evaluate and validate the codes, resolve technical issues, and enhance the general understanding of the ISV process. The following sections of this report will present a brief description and list the more important conclusions from these studies.

3.1 Simulation of PNL Test

As part of the validation of the VULCAN computer code, the Pilot Scale Remedial Test (PSRT) performed at Pacific Northwest Laboratory (PNL)⁸ was simulated using the VULCAN computer code. PSRT had a 1.2 meter electrode spacing with an average power of 300 kW, and a run time of 23 hours. Although, there is limited published data for comparison, the VULCAN simulation appears to give very reasonable results, for example the PSRT melt volume was 4.8 cubic meters while the VULCAN calculation indicated a melt volume of 4.6 cubic meters. When the uncertainties in the input data are taken into account, the agreement is excellent.

3.2 VULCAN Parametric Studies

A series of calculations were performed with the VULCAN computer code to examine the effects of various variables and parameters on the melting process.⁹ The primary variables that were examined were heat capacity, thermal conductivity, and electrical conductivity. Several calculations were made where the thermal properties were varied about the nominal values. The effects were evaluated at slow, nominal, and fast melt rates. These studies were done to help provide a basis for the accuracy required for experimental measurement of the physical properties and to determine the dominant parameters in the melting process.

The calculated melt boundaries were as expected. For example, a fast melting case produces a melt zone that is deeper and wider than a slow melting case (see Figure 2). Likewise, the cold cap is thicker for the faster melting cases. This is due to the higher thermal conductivity in the faster cases.

Figure 2. Melt volume cross sections.

The results of this study indicate that changes in specific heat have the most significant effects on melt volume. The melt volume is less sensitive to the effects of thermal conductivity. The electrical conductivity has even less effect on melt volume.

3.3 Pressurization beneath the Melt

An understanding of simultaneous transport of energy and moisture in the unsaturated region surrounding the ISV melt is of important practical significance because of its potential impact on process safety and performance. It is postulated that under certain conditions vaporization of water could cause a pressure buildup beneath the melt that could lead to ejection of melt material. Recent full-scale ISV tests¹⁰ in which considerable molten glass was ejected from the melt, have focused attention on the need for enhancing the understanding of these phenomena. This study was initiated in part to investigate potential causes and solutions for such events in both contaminated soil and buried waste applications.

During the ISV process, the region surrounding the melt experiences high temperatures due to conduction and convection of heat from the high temperature melt zone (see Figure 3). This heating vaporizes the liquid water causing pressurization of the gas phase and subsequent gas flow, both towards and away from the melt. The moisture that flows away from the melt condenses in the cooler soil forming a water bank which may act as a barrier and prevent the migration of contaminants away from the melt zone. The water bank may also act as a pressure barrier and if pressures in the gas phase become sufficiently high, expulsion of melt material may occur.

The relative magnitudes of the various driving forces controlling gas-phase pressure and direction of mass transfer are strongly dependent on the physical properties of the soil and process variables, such as heating rate and melt front velocity. To evaluate the potential for pressure buildup beneath the melt, simplified numerical simulations were performed using a modified version of the TOUGH computer code (see Reference 4). The simulations are designed to evaluate the importance of initial water saturation, melt permeability, and stray joule heating on gas-phase pressure and direction of gas flow.

The idealized problem domain used in each of the test cases is depicted in Figure 4. To restrict the flow of moisture and heat in one dimension, vertical boundaries are specified as impermeable and thermally insulated. Boundary pressure and temperature, at $x = 10$ m, are fixed at $P = 101330$ Pa

Figure 3. Schematic of conditions in the region surrounding an ISV melt.

Figure 4. One-dimensional problem domain.

and $T = 20^{\circ}\text{C}$. The melt boundary moves along x at a specified velocity of 5 cm/hr with $T = 1200^{\circ}\text{C}$ and $P = 101330$ Pa. Temperatures and pressures are held constant throughout the melt and are $T = 1200^{\circ}\text{C}$ and $P = 101330$ Pa.

Figures 5, 6, 7, and 8 present results from a sample calculation. This case examines the combined effects of a low soil permeability ($k = 2.5 \times 10^{-13} \text{ m}^2$) and a relatively high initial soil water saturation ($S_1 = 0.5$). Temperature, water saturation, gas-phase pressure, and velocity profiles at 20 hours are shown in Figures 5, 6, 7, and 8. As indicated in Figure 6, a water bank of increased water saturation is formed just ahead of the advancing melt front. In the region between the advancing melt front and the peak water saturation, the liquid is vaporizing causing a 20% increase in pressure up to 1.2 atmospheres as shown in Figure 7. Since pressure gradients are acting both towards and away from the melt, gas flows towards and away from the melt as shown in Figure 8. These trends in pressure, temperature, and water saturation remain similar at later times.

In summary, simplified numerical simulations were performed to evaluate the importance of initial water saturation, melt permeability, and stray joule heating on gas-phase pressure and direction of gas flow. Results from these analyses indicate that the combination of low soil permeability and high initial water saturation may lead to excessive gas pressures in the region below the melt. In fixed electrode applications, stray joule heating in the region below the melt may also lead to excessive gas pressures. It is unlikely that stray joule heating is a concern in moving electrode applications due to the electrically insulating dry region surrounding the melt.

Initial water saturations greater than 0.5 may lead to a high saturation water bank which acts as a barrier to gas migration away from the melt. Although this condition will limit the migration of contaminants away from the melt, it can also lead to excessive gas pressures if the gas cannot escape. Venting to the confinement hood may be necessary in some applications.

It is apparent from this study that site specific material properties should be determined prior to field processing. Simple analyses can then be performed to help determine operating procedures and technical specifications required to avoid off-normal events.

A second study is in progress to further define the ranges and combinations of melt rate, permeability, water saturation, etc., where pressure buildup beneath the melt may occur.

Figure 5. Temperature as a function of distance.

Figure 6. Saturation as a function of distance.

Figure 7. Pressure as a function of distance.

Figure 8. Velocity as a function of distance.

3.4 Scaling

Studies were conducted to define the scaling requirements for the upcoming intermediate scale tests to be performed at PNL.¹¹ The scaling rationale is based on similarity constraints arising from temperature and electrical field phenomena interior to the melt and off-gas generation in the porous media in front of the melt. The power scaling is assumed to be the commonly used heat flux scaling rationale which implies that the power should be proportional to the square of the scaling ratio. The scaling rationale derived in the study implies that geometric similarity of the ISV system be maintained. In the case of intermediate scale tests, the implication is that the linear dimensions of all corresponding system elements are in a constant ratio of 0.3 to the full-scale system. This also suggests that the linear dimensions of the waste containers be scaled to this same ratio.

The study indicated that there will be some distortion of the off-gas rate due to bubble rise effects. However, the magnitude of the distortion has not been quantified.

3.5 Off-Gas Estimate

The off-gas rate for application of ISV to the transuranic-contaminated pits and trenches is being estimated. A probabilistic approach is being used to quantify the pit contents. This study is currently in progress and will be published at a later date.

4. SUMMARY

The in situ vitrification (ISV) modeling activities encompass a variety of both modeling development efforts and analysis applications in support of the ISV project. The application of these ISV computer code models benefits the ISV program by providing resolution and understanding of technical and safety issues in a cost-effective and timely manner.

The model development activities in Fiscal Year 1991 included modifying and extending existing computer codes as well as development of new models and computer codes. The initial versions of the APOLLO, MAGMA, and VESTA computer codes were completed and the capabilities of the VULCAN and TOUGH computer codes were enhanced with the addition of new models this year. With the completion of these modeling efforts, there are now initial models for each of the seven major ISV phenomena.

Several calculations and analyses were performed this year with the codes to evaluate and validate the codes, resolve technical issues, and enhance the general understanding of the ISV process. These analyses included simulations of experimental data, evaluating effects of variations in physical properties, evaluating the potential of pressure buildup beneath the melt, specifying scaling criteria for experimental facilities, and estimating off-gas rate for safety studies. The results of these analyses contributed to a better understanding of safety and environmental hazards concerns, assisted in experimental test planning and design, and provided enhanced understanding of the ISV process.

5. REFERENCES

1. H. D. Nguyen, APOLLO: A Computer Program for the Calculation of Chemical Equilibrium and Reaction Kinetics of Chemical Systems, EG&G Idaho, Inc., EGG-WTD-9876, September 1991.
2. J. M. Smith and H. C. Van Ness, Introduction to Chemical Engineering Thermodynamics, New Jersey, Prentice-Hall, 1984.
3. P. R. McHugh and J. D. Ramshaw, A Computational Model for Viscous Fluid Flow, Heat Transfer, and Melting in In Situ Vitrification Melt Pools, EG&G Idaho, Inc., EGG-WTD-9845, October 1991.
4. K. Pruess, "TOUGH User's Guide," NUREG/CR-4645 SAND 86-7104, June 1987.
5. S. Paik, VESTA: A Computer Program for the Simulation of the Flow and Combustion in the In Situ Vitrification Confinement Hood, EG&G Idaho, Inc., EGG-WTD-9627, September 1991.
6. L. D. Cloutman, COYOTE: A Program for 2-D Reactive Simulations, Lawrence Livermore National Laboratory Report UCRL-ID-103611, May 1990.
7. P. E. Murray and M. O. Fryer, Simulation of Heat Conduction and Electric Fields During In Situ Vitrification of Soil: Methods Design and Verification, EG&G Idaho, Inc., EGG-WM-9045, September 1990.
8. J. L. Buelt et al., In Situ Vitrification of Transuranic Waste: An Updated Systems Evaluation and Application Assessment, PNL-4800, Supp 1, March 1987.
9. M. O. Fryer, G. L. Hawkes, and P. E. Murray, Parametric Melting Studies for In Situ Vitrification, EG&G Idaho, Inc., EGG-WTD-9872, September 1991.
10. "Report on Defense Plant Wastes," Vol 3, No 17, pp 143, August 16, 1991.

11. M. A. Langerman and R. T. MacKinnon, "Scaling Considerations for Modeling the In Situ Vitrification Process," Applied Mathematical Modeling, Vol 15, p 1652-1-1652-8, November 1991.

APPENDIX A

PUBLICATIONS, REPORTS, AND PRESENTATIONS

APPENDIX A
PUBLICATIONS, REPORTS, AND PRESENTATIONS

The following publications, reports and presentations have been done by the modeling and analysis staff during Fiscal Year 1991.

1. M. A. Langerman and R. T. MacKinnon, "Scaling Considerations for Modeling the In Situ Vittrification Process," Applied Mathematical Modeling, Vol 15, pp 1652-1-1652-8, November 1991.
2. M. A. Langerman, "Modeling the Steady-State ISV Process: A 3-D Finite Element Analysis of Coupled Thermal Electric Fields," Heat Transfer in Geophysical Media, ASME HTD-Vol 172, pp 9-16, 28th National Heat Transfer Conference, Minneapolis, Minn., July 1991.
3. M. A. Langerman and R. T. MacKinnon, "Estimating Bouyancy-Driven Convection Effects on Temperature Distributions in Ideal Fluids," Numerical Heat Transfer (submitted) 1991.
4. S. Paik and C. E. Slater, "Numerical Investigation of the Flow and Combustion in the ISV Confinement Hood," Numerical Heat Transfer: Part A. Applications (submitted).
5. P. E. Murray, and M. O. Fryer, "Simulation of Heat Conduction and Electric Fields During In Situ Vittrification of Soil," Numerical Modeling of Basic Heat Transfer Phenomena in Nuclear Systems, HTD-Vol 165, ASME, New York, 1991. (Presented at the 28th National Heat Transfer Conference, Minneapolis, Minn., July 1991.
6. G. L. Hawkes, "Influence of Natural Convection on Melt Shape During In Situ Vittrification," Heat Transfer in Geophysical Media, 28th National Heat Transfer Conference, Minneapolis, Minn., July 1991.
7. H. D. Nguyen, APOLLO: A Computer Program for the Calculation of Chemical Equilibrium and Reaction Kinetics of Chemical Systems, EG&G Idaho, Inc., EGG-WTD-9876, September 1991.

8. P. R. McHugh, and J. D. Ramshaw, A Computational Model for Viscous Fluid Flow, Heat Transfer, and Melting in In Situ Vitrification Melt Pools, EG&G Idaho, Inc., EGG-WTD-9845, September 1991.
9. S. Paik, VESTA: A Computer Program for the Simulation of the Flow and Combustion in the In Situ Vitrification Confinement Hood, EG&G Idaho, Inc., EGG-WTD-9627, September 1991.
10. M. O. Fryer, G. L. Hawkes, and P. E. Murray, Parametric Melting Studies for In Situ Vitrification, EG&G Idaho, Inc., EGG-WTD-9872, September 1991.
11. C. E. Slater, Summary of In Situ Vitrification Modeling and Analysis Accomplishments for Fiscal Year 1991, EG&G Idaho, Inc., EGG-WTD-9214, September 1991.
12. G. L. Hawkes, "Influence of Natural Convection on Melt Shape During In Situ Vitrification," Fifth Annual INEL Computing Symposium, Idaho Falls, Idaho, September 1991.

APPENDIX B

ISV SUPPORT ACTIVITIES

APPENDIX B

ISV SUPPORT ACTIVITIES

In addition to the modeling and analyses activities, the modeling and analysis staff have supported the ISV program by participating on various committees. These contributions include the following:

- Serving on the Idaho National Engineering Laboratory (INEL) ISV Steering Committee. This committee identifies and documents all of the technical issues for application of ISV at INEL and suggests roadmaps for their closure. The committee also serves as a review body for experimental designs.
- Member of investigation committee on GEOSAFE OAT2 incident. During OAT2 (full-scale ISV test) there was an incident in which large volumes of glass were ejected from the melt which resulted in the loss of the fabric confinement hood. The investigation team postulated and investigated the causes of the incident and participated in preparing two reports describing the probable causes.
- Member of national Off-Gas Technical Support Group (TSG) formed to support the national Program Planning Group (PPG). Participated in preparing a report identifying generic ISV technical issues associated with the hood and off-gas system and suggested a methodology for their closure.
- Member of technical support team for investigation of PNL buried tank test incident. PNL had an incident in which large volumes of gas were ejected from the melt during a large-scale buried tank test. A team was formed to furnish technical support for the investigation team. This investigation is still in progress.
- Review of Hazards Classification Document for Laboratory Scale Tests. Provided technical review of documents prior to submitting to the Department of Energy for approval.

END

**DATE
FILMED**

6 / 12 / 92