EGG-WTD-9432 Vol 2
November 1991

APR 27 1992

**Idaho
National
Engineering
Laboratory**

*Managed
by the U.S.
Department
of Energy*

INFORMAL REPORT

Use of Noninvasive Geophysical Techniques for the In Situ Vitrification Program

Volume 2: Demonstration at the Simulated Waste Pit

**Nicholas E. Josten
Steven T. Marts
Glen S. Carpenter**

*Work performed under
DOE Contract
No. DE-AC07-76ID01570*

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

This document contains new concepts or the author(s) interpretation of new calculations and/or measurements; accordingly, EG&G Idaho, Inc. is required by the United States Government to include the following disclaimer:

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights. References herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

EGG-WID--9432-Vol.2

DE92 012569

USE OF NONINVASIVE GEOPHYSICAL TECHNIQUES
FOR THE
IN SITU VITRIFICATION PROGRAM
VOLUME 2: DEMONSTRATION AT THE SIMULATED WASTE PIT

Steven T. Marts
Nicholas E. Josten
Glen S. Carpenter

Published November 1991

Idaho National Engineering Laboratory
EG&G Idaho, Inc.
Idaho Falls, Idaho 83415

Prepared for the
U. S. Department of Energy
Office of Environmental Restoration and Waste Management
Under DOE Field Office, Idaho
Contract DE-AC07-76ID01570

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

USE OF NONINVASIVE GEOPHYSICAL TECHNIQUES
FOR THE
IN SITU VITRIFICATION PROGRAM

VOLUME 2: DEMONSTRATION AT THE SIMULATED WASTE PIT

Approved by:

WE Harrison
W. E. Harrison, Manager
Geosciences Unit

Date:

3/1/91

Prepared by:

ST Marts
S. T. Marts

Date:

3/1/91

Reviewed by:

T. R. Wood
T. R. Wood
Technical Reviewer

Date:

3/1/91

ABSTRACT

In situ vitrification (ISV) is a waste pit remediation technology that can potentially eliminate the need for pit excavation. The ISV program at the Idaho National Engineering Laboratory (INEL) funded this study to evaluate geophysical techniques that might be useful for performing detailed screening of the materials, soil conditions, and local geology of waste pits targeted for remediation. The evaluation focusses on a specific set of characterization objectives developed by ISV engineers. The objectives are based on their assessment of safety, environmental, and cost efficiency issues associated with the ISV process. A literature review of geophysical case histories was conducted and a geophysical survey was performed at the INEL simulated waste pit so that the evaluation could be based on demonstrable results. The literature review shows that all the ISV objectives are theoretically achievable because they involve physical properties (such as electrical conductivity, density, or magnetization) that can be sensed by geophysical instruments. However, most of the ISV objectives require substantially higher resolution than is achieved in typical waste site investigations, or than has been demonstrated by researchers using state-of-the-art techniques. The survey at the INEL simulated waste pit yielded useful, qualitative information on subsurface materials and boundaries; but quantitative information, such as depth, size, or composition of buried materials, was subject to significant uncertainty. For ISV, the usefulness of geophysical characterization depends both on the capabilities of geophysical methods and on an assessment of the amount of uncertainty that is acceptable. Based on a preliminary assessment of these factors, the location of trench boundaries and detection of massive metallic objects are the important achievable objectives using current technology. Other ISV objectives are either not routinely achievable, or cannot be achieved with satisfactory confidence levels. A peer review of this report substantiated these conclusions but stressed that conventional geophysical methods are not designed for the high level of characterization sought by ISV and that continued research is needed.

Document EGG-WTD-9432 Vol 2
Revision 0
Date November 1991
Page iv

CONTENTS

VOLUME 1--LITERATURE REVIEW

ABSTRACT	iii
EXECUTIVE SUMMARY	v
INTRODUCTION	1
DESCRIPTION OF GEOPHYSICAL METHODS	3
Electromagnetic Induction	3
Magnetics	3
Ground Penetrating Radar	4
Resistivity	4
Seismic Refraction	5
Gravity	5
GEOPHYSICAL APPLICATIONS	6
Waste Material Characterization	6
Electromagnetic and Magnetic Methods	6
Radar Methods	8
Resistivity Methods	9
Seismic Methods	9
Gravity Methods	9
Waste Site Characterization	10
Electromagnetic and Magnetic Methods	10
Radar Methods	11
Resistivity Methods	12
Seismic Methods	12
Gravity Methods	13
Melt Monitoring and Postmelt Characterization	13
CONCLUSIONS	15
REFERENCES	17
APPENDIX A--ISV CHARACTERIZATION DATA NEEDS	A-1

CONTENTS

VOLUME 2--DEMONSTRATION AT THE SIMULATED WASTE PIT

ABSTRACT	iii
INTRODUCTION	1
SIMULATED WASTE PIT	3
FIELD METHODS	7
Magnetic Method	7
Electromagnetic Induction Method	8
Ground Penetrating Radar	9
RESULTS AND DISCUSSION	11
Mapping Buried Waste with the Magnetic Method	11
Mapping Buried Waste with the Electromagnetic Induction Method	12
Mapping Buried Waste Using Ground Penetrating Radar	18
Estimating Pit Boundaries, Cover Thickness, and Depth to Basalt	20
Identifying the Type of Materials Inside the Waste Pit	27
Evaluation of Electromagnetic Induction and Magnetic Methods	32
CONCLUSIONS	34
REFERENCES	36
APPENDIX A ELECTROMAGNETIC AND MAGNETIC DATA	A-1

FIGURES

1. Location of simulated waste pit	4
2. Arrangement of objects inside the simulated waste pit relative to data coordinate system	6
3. Vertical magnetic gradient map of the large object zone showing both historical and interpreted boundaries (units in gammas/meter). Shading indicates interpreted object boundaries	13
4. Vertical magnetic gradient profile along 8N showing the locations of simulated waste objects	14

5. Inphase electromagnetic data profile along 8E showing the locations of simulated waste objects	16
6. Inphase electromagnetic data map of the large object zone showing both historical and interpreted boundaries (values are unitless). Shading indicates interpreted object boundaries	17
7. Ground penetrating radar (300 Mhz) along line 13N showing reflection from pyramid stack of drums	21
8. Ground penetrating radar (300 Mhz) along line 7N showing historical and interpreted locations of steel casing	22
9. Ground penetrating radar (300 Mhz) along line 9N showing historical and interpreted locations of steel casing	23
10. Inphase electromagnetic data map of simulated waste pit showing both historical and interpreted boundaries (values are unitless). Shading indicates interpreted pit boundaries	24
11. Vertical magnetic gradient map of simulated waste pit showing both historical and interpreted boundaries (units in gammas/meter). Shading indicates interpreted pit boundaries	25
12. Quadrature phase electromagnetic data map of simulated waste pit showing historical boundaries (units in millimhos/meter)	28
13. Total magnetic field map of simulated waste pit showing historical boundaries (units in gammas).	31

TABLES

1. Description of zones in simulated waste pit	5
2. Depth estimates interpreted from total magnetic field data	27

CONTENTS

VOLUME 3--DISCUSSION AND RECOMMENDATIONS

ABSTRACT	iii
INTRODUCTION	1
BACKGROUND	2
EVOLUTION OF ISV OBJECTIVES FOR GEOPHYSICS	3
SAFETY AND EFFICIENCY ISSUES FOR ISV	4
GEOPHYSICS AND ISV	6
Uncertainty Factors for Potential Field Methods	7
Uncertainty Factors for Propagation Methods	8
CAPABILITIES AND LIMITATIONS OF GEOPHYSICS FOR ISV NEEDS	11
Trench Boundaries	11
Detection of Massive Metallic Objects	12
Void Spaces	13
Waste Type Within Containers	14
Overburden Thickness	15
Soil Density/Porosity	15
Post-Melt Evaluation	15
RECOMMENDED GEOPHYSICAL PROGRAM FOR SCREENING ISV SITES	17
RECOMMENDED RESEARCH DIRECTIONS	19
Improved Radar Antennas	19
Geophysical Modeling	19
Improved Tomographic Imaging	20
Electrode Mounted Sensors	20
Evaluation of Borehole Geophysical Methods	21
CONCLUSIONS	22
REFERENCES	23

USE OF NONINVASIVE GEOPHYSICAL TECHNIQUES FOR THE
IN SITU VITRIFICATION PROGRAM
VOLUME 2: DEMONSTRATION AT THE SIMULATED WASTE PIT

INTRODUCTION

This document is the second volume of a three volume report to evaluate geophysical methods for use in the detailed characterization of waste pits. The In Situ Vitrification (ISV) Program funded the study to support the ISV remediation technology being developed at the Idaho National Engineering Laboratory (INEL). The ISV Program is considering geophysical waste characterization as a means to enhance the efficiency of the ISV process. Volume 1 documents the results of a literature review conducted to assess the capabilities and limitations of commonly used geophysical methods and to identify promising new technologies. Volume 2 contains the results of geophysical surveys conducted at a simulated waste disposal pit. Volume 3 presents recommendations for a geophysical investigation program that effectively supports ISV operations.

Field tests were conducted to demonstrate and evaluate the application of magnetic, electromagnetic induction, and ground penetrating radar methods to waste site characterization. The primary objective was to investigate the ability of these noninvasive geophysical methods to locate and identify buried waste materials under conditions representative of the INEL Subsurface Disposal Area (SDA).

The tests were conducted at an simulated waste pit designed to represent conditions at the SDA. The test site is well suited for geophysical tests because the configuration of simulated waste materials inside the pit was mapped and documented before backfilling. Since the location and type of materials inside the pit were known, the correctness of qualitative and semiquantitative interpretation methods could be examined. The capabilities and limitations shown in the results are indicative of those achievable at an uncontrolled waste site.

This report begins with a brief description of the simulated waste pit and the geophysical methods used for this demonstration. Next, the results are discussed in terms of the ability to map simulated waste objects, determine pit boundaries, and identify the type of waste materials using the data collected by the three geophysical methods. Finally, the conclusions section summarizes the results and their implications to the ISV program.

SIMULATED WASTE PIT

The test site, known as the simulated waste pit, was constructed in 1989 and was designed to represent conditions at the SDA. The simulated waste pit is located approximately 200 m south of the SDA, which is part of the INEL Radioactive Waste Management Complex (RWMC) (Loomis, 1989).^a Figure 1 shows the simulated waste pit location relative to the SDA.

The SDA was established in 1952 as a disposal site for solid low-level radioactive waste (Vigil, 1989). Wastes were buried at the SDA primarily in trenches and pits. Trenches were approximately 3 to 4 m deep depending on basalt topography, 1.5 to 2.5 m wide, 30 to 300 m long, and spaced side-by-side on 5-m centers. Pits ranged in size to 12,000 m² and were 1.5 to 6 m deep depending on basalt topography. According to historical records, typical waste included demolition materials, laboratory equipment and materials, process equipment and materials, protective clothing, maintenance equipment, decontamination materials, and other miscellaneous items. Wastes were stacked or randomly dumped, either containerized or noncontainerized. Container types also varied, including, steel drums, wooden boxes, and tanks.

The simulated waste pit is approximately 43 m long and 12 m wide with a maximum burial depth of 4 m. The pit is divided into five zones as identified in Table 1. A 2 to 3 m wide earth berm separates Zones 3, 4, and 5. Zones 1, 2, and 3 are immediately adjacent to each other. Figure 2 shows the boundaries of Zones 2 through 5 along with most of the simulated waste in the large object zone (Zone 1).

The pit was excavated nearly to the basalt and backfilled with nearby soils. Depth to the basalt varies from 4 to 6 m. The soils are fine-grained eolian deposits with some fluvial gravelly sands. Approximately 20 to 40% of the soil grains are clay-sized with illite, montmorillonite, and kaolinite being the predominate clay minerals (Bartholomay et al., 1989).

a. Unpublished research results of R. M. Brown, EG&G Idaho, Inc., Idaho Falls, Idaho, May 1989.

Figure 1. Location of simulated waste pit.

Table 1. Description of zones in simulated waste pit

Zone	Description
1. Large objects	Contains pipes, drums, tanks, concrete vaults, and plywood boxes filled with primarily wood, paper, plastic, and metal. The location of each object is known.
2. Stacked boxes	4 x 4 x 8 ft cardboard boxes filled with metal debris, large metal objects, concrete, and asphalt. Upper boxes contain primarily metal.
3. Stacked drums	Stacked drums containing sludge, paper, wood, metal, concrete, and glass. Most drums are cardboard with the remaining being steel.
4. Random dump drums and boxes	Randomly distributed cardboard drums, steel drums, and cardboard boxes. Containers are filled with sludge, paper, wood, metal, concrete, and glass.
5. Random dump drums	Randomly distributed cardboard and steel drums containing sludge, paper, wood, metal, concrete, and glass.

Figure 2. Arrangement of objects inside the simulated waste pit relative to data coordinate system.

FIELD METHODS

Three noninvasive geophysical methods were tested at the simulated waste pit: (a) the magnetic method to measure magnetic field anomalies generated by subsurface materials, (b) the electromagnetic induction method to measure induced electromagnetic fields associated with subsurface conductive materials, and (c) the ground penetrating radar method to detect interfaces between electrically dissimilar subsurface materials. All three methods are routinely used for waste site characterization.

The three-person crew completed the field tests in approximately two days. Before beginning data collection, a 24 x 58-m coordinate system was set up with the 12 x 43-m simulated waste pit centered inside the test area (see Figure 2). The test area boundaries and several cross lines were marked every 2 m with wooden reference stakes. Fiberglass measuring tapes were stretched between reference stakes while collecting data to ensure correct locations for each station measurement.

Magnetic Method

The magnetic method measures variations in the earth's magnetic field caused by buried ferromagnetic objects. The earth's magnetic field polarizes any magnetic material creating an induced magnetic field around that material. This induced field is superimposed on the earth's magnetic field. If the induced field is strong enough, it produces a measurable anomaly. These local variations are manifested in measurements of either the total field or the vertical gradient of the total field. Vertical gradient data is usually preferred over total field data for buried waste detection because it accentuates anomalies from shallow buried objects.

The earth's magnetic field varies not only with spatial position but with time. Consequently, the diurnal variation of the magnetic field was measured by frequently returning to a fixed base station. For this survey, the diurnal

variation was negligible compared to the field variations caused by buried ferromagnetic materials.

A Scintrex Omni IV magnetometer was used that combines two proton-precession magnetometer sensors and measures both total magnetic field strength and the vertical gradient. The sensors are 1 m apart and mounted on a nonmagnetic pole. Data were collected with the lower sensor at 0, 1, and 2 m above the ground. Both total field and vertical gradient measurements were made over the presurveyed 24 x 58-m test area at 1-m spacing along survey lines oriented north-south. Survey lines were 1 m apart over the large object zone and 2 m apart elsewhere. Data were collected at a 0.5-m spacing along selected lines over the large object zone. The magnetometer stored all measurements (including those at a base station) to memory and the data logger dumped the data to a computer after each day's work. All data are presented in Appendix A.

Electromagnetic Induction Method

The electromagnetic induction method uses a transmitter coil to send a low-frequency electromagnetic field into the ground. This primary field induces eddy currents in subsurface materials creating a secondary field that is measured, together with the primary field, by a receiver coil. The depth of exploration is a function of the separation between the transmitter and receiver coils and the electrical conductivities of subsurface materials. Two components of the electromagnetic field can be useful for waste disposal site characterization: quadrature phase and inphase. The quadrature component is 90° out of phase with the primary field while the inphase component is in phase. Given a fixed distance between the coils, the subsurface electrical conductivity is directly proportional to the quadrature phase component of the secondary field when subsurface conductivities are low (i.e., metal is absent). Although measurements of the inphase components are not linearly related to conductivity, they are extremely sensitive to conductive materials such as metallic objects indicated by a measurement higher or lower than

background. McNeill (1980) provides a more detailed discussion of electromagnetic measurement theory.

Based on the depth of waste pits, the Geonics EM31 terrain conductivity meter was selected. The EM31 transmits a 17.5 Hz electromagnetic wave with a coil separation of 2.7 m. Depths of exploration using the EM31 generally range from 0 to 6 m. Quadrature and inphase measurements were made over the presurveyed 24 x 58-m test area. Inphase measurements were taken with the instrument oriented both north-south and east-west. Data were collected at 1-m spacing along survey lines oriented north-south. Lines were 1 m apart over the large object zone and 2 m apart elsewhere. Data were recorded in field notebooks and entered into a computer after each day's work. All data are presented in Appendix A.

Ground Penetrating Radar

The ground penetrating radar method uses high frequency electromagnetic wave reflections to generate a cross-sectional image of subsurface interfaces along the path of the radar antenna. An electromagnetic wave pulse travels away from a transmitter antenna into the subsurface until it encounters a boundary of significant dielectric contrast. At the boundary, the wave is reflected back to the receiver antenna. The reflected pulse is delayed a length of time that is a function of target depth and wave velocity through the materials between the target and antenna. The reflected wave pulses that arrive at the receiver antenna are recorded digitally on tape. Interpretation techniques allow conversion from time to depth below the antenna given an estimate of the dielectric properties of the materials.

A Geophysical Survey System Inc. SIR10 time-domain, pulse-reflection instrument with 100-, 120-, 300-, and 500-Mhz antennas was used. In general, a high frequency antenna has higher resolution and less depth of penetration than a lower frequency antenna. Several antenna configurations were tested in an attempt to optimize the object resolution and depth of investigation. Each antenna was tested independently, and the 100-MHz antenna (transmitter) was

coupled with the 120-MHz antenna (receiver). The antennas were pulled across several paths over the large object zone including 7E, 9E, 11E, 13E, 7N, 9N, 11N, 13N, 19N, and 0N extending southward up a nearby hill.

Data processing helped enhance the clarity of reflections from targeted waste materials. A bandpass filter applied during data acquisition reduced high and low frequency noise. Post-processing included tighter bandpass filters, background removal, and signal stacking in an attempt to increase signal-to-noise ratio and reflection clarity.

RESULTS AND DISCUSSION

Results from the data collected clearly show the resolution and accuracy possible with magnetic, electromagnetic induction, and radar technologies. These results indicate the degree of accuracy possible for a similar investigation at the SDA because conditions at the simulated waste pit are similar to those at the SDA including, soil type, depth of buried objects, disposal methods, and type of waste materials.

Interpretation of data collected by the three noninvasive geophysical techniques demonstrate a limited ability to map buried waste objects, estimate waste pit boundaries, and characterize waste materials in terms of electrical and magnetic properties. Mapping is defined as the detection and delineation of waste materials. The interpreted pit boundary was positioned to surround all mapped waste materials and often correlates with the excavation boundary. Bulk electrical and magnetic properties often allow the classification of waste into one of three categories: ferromagnetic metal, nonferromagnetic metal, and nonmetal.

In this section, the ability of each of the three methods to map buried waste and estimate pit boundaries is discussed. Next, the capability to identify waste types by electrical and magnetic properties is evaluated. Finally, a comparison of the accuracy of the electromagnetic induction and magnetic methods is provided.

Mapping Buried Waste with the Magnetic Method

Mapping objectives for the magnetic method include detection of all ferromagnetic materials and an estimation of their boundaries. The interpretation strategy involved inspection of contour maps and profile lines to recognize data anomalies that are characteristic of buried waste material. After recognizing an anomalous area of data, the position and size of a magnetic object that would cause such an anomaly was estimated by inspecting appropriate profile lines. The interpreted object boundary coincides with the

slope inflection point based on theoretical models of simple ferromagnetic bodies. Actually, the measured magnetic field arising from a magnetic body is a complex function of object shape and position, remnant magnetization, and the effects of nearby ferromagnetic objects.

As displayed in Figure 3, the interpretation of vertical magnetic gradient data in the large object zone indicates six ferromagnetic objects or groups of objects and provides an estimate of the size and position of each. Figure 4 shows the data collected along line 8N used to interpret several of the boundaries. Figure 4 also illustrates the fact that higher resolution is obtainable by positioning the sensor closer to the ground surface. Sensitivity increases because the induced magnetic field is stronger close to the magnetic object.

The magnetic data demonstrate the ability to detect the pyramid stack of drums, crushed drum pile, steel tank, reinforced concrete blocks, pair of steel casings, stack of 8 drums, and a plywood box that contains some ferromagnetic materials. The magnetic data do not show a response from the concrete-filled steel pipe. Resolution depends on object size, distance to nearby objects, and depth. In general, detection of large, shallow, isolated ferromagnetic materials is possible while detection of deeper objects situated between other magnetic materials may not be possible.

Mapping Buried Waste with the Electromagnetic Induction Method

The goal of mapping buried waste with the electromagnetic induction method is to detect all electrically conductive materials and to estimate their boundaries. The interpretation strategy involved inspection of contour maps and profile lines to recognize data anomalies that are characteristic of buried waste material. After recognizing an anomalous area of data, the position and size of a conductive object that would cause such an anomaly was estimated by inspecting appropriate profile lines. The interpreted object boundary coincides with the location having half the maximum amplitude based on theoretical models of simple conductive bodies such as spheres and

Figure 3. Vertical magnetic gradient map of the large object zone showing both historical and interpreted boundaries (units in gammas/meter). Shading indicates interpreted object boundaries.

Figure 4. Vertical magnetic gradient profile along 8N showing the locations of simulated waste objects.

cylinders. The electromagnetic response of conductive bodies is actually a complex function of object depth, size, orientation, and aspect ratio; superposition effects; and material properties as well as instrument parameters.

Electromagnetic induction theory does confirm that buried metal can cause either a positive or negative response as illustrated in Figure 5. The high values centered at 10N comes from a conductive body that is large compared to the coil spacing (pile of crushed drums). The low values centered at 13N comes from a conductive body that is small compared to the coil spacing (upper portion of the drum pyramid).

Data were collected with the long axis of the EM31 oriented both north-south and east-west. Comparison of the two resulting contour maps gives some indication of sharp lateral conductivity changes associated with object boundaries. Information on object locations could not be obtained from an integration of the two data sets beyond that obtained from data collected in a single orientation. However, the practice of collecting mutually perpendicular electromagnetic data may be potentially useful.

The interpretation of both inphase electromagnetic data sets in the large object zone show an anomalous region enclosing the entire large object zone with four individual anomalous areas inside the zone as shown in Figure 6. The data delineate an area that encloses all the metallic waste but resolution of individual metal objects is limited when the distance between the objects is small. The clearest responses are from the pyramid stack of drums because the top drums are shallow and from the combination of the crushed drum pile, the steel tank, and the reinforced concrete blocks because these conductive materials cover such a wide area. A third response is from the pair of steel casings. The casings are far enough away from nearby metal to allow a separate electromagnetic response. A fourth response comes from metal inside the wooden boxes and extends north into the stacked box zone.

Figure 5. Inphase electromagnetic data profile along 8E showing the locations of simulated waste objects.

Figure 6. Inphase electromagnetic data map of the large object zone showing both historical and interpreted boundaries (values are unitless). Shading indicates interpreted object boundaries.

Mapping Buried Waste Using Ground Penetrating Radar

Radar data were collected along several representative lines over the large object zone in order to supplement the interpretations possible with the electromagnetic and magnetic methods. The mapping objectives of the radar test were to determine the achievable resolution of individual objects and to locate nonmetallic objects. Radar data showed very little ability to map metal waste objects and was unable to detect nonmetallic objects. This section contains a brief description of the problems that were encountered.

Ground penetrating radar records are interpreted by recognizing reflections or vertical interference patterns caused by the buried waste object. Reflections from buried metal may occur for two reasons: (a) the upper surface of a buried metal object causes a reflection from its electrical impedance contrast with the surrounding soil and (b) the object behaves as a resonance target creating internal reflections and a subsequent high amplitude signal received at the antenna. The following conditions must be met in order for a buried object to be detectable by radar methods:

- The transmitted wave must be of a sufficient power to reach the buried object and return to the surface to be measured by the receiver.
- Reflections from other impedance interfaces must not interfere with the reflection emanating from the buried object.
- The object must be large enough to be detected given its depth and the antenna frequency.
- The contrast between the electrical impedance of the buried object and that of the surrounding materials must be high enough to cause a sufficient reflection.

In general, the first two conditions listed above were not met at the simulated waste pit. The data demonstrate the site specific nature of ground penetrating radar methods. The interaction of electromagnetic waves with the electrical properties of the test area soil caused two effects that complicate radar data interpretation: rapid wave attenuation and excessive ringing.

Four conditions may have contributed to the rapid attenuation of the radar signal at the simulated waste pit. Olhoeft (1986) describes the four primary attenuation mechanisms. (1) The electrical conductivity of soils causes the electromagnetic energy to be transformed into thermal energy to provide transport of charge carriers through the medium. (2) The rotation of water molecules in the presence of an applied electric field causes the radar signal to be dissipated as mechanical energy. (3) Clay minerals easily transfer ions between their high surface area and the soil water. These chemical reactions cause electromagnetic energy loss by transformation to chemical energy. Olhoeft (1987) estimates that the addition of just 5% montmorillonite clay decreases radar signal penetration by a factor of 8. (4) The last mechanism is related to scattering that occurs when the changes in electrical properties in a material are on the same geometric scale as the size of the wavelength. The conditions at the test site increased attenuation from these mechanisms because the soils have high conductivities, retain a high moisture content, and contain appreciable quantities of clay minerals and the targets are about the same dimensions as the best penetrating radar wavelengths.

Ringing is a vague term that describes unwanted multiple reflections from an impedance boundary. Antenna ringing is commonly present on radar records and was overwhelming on the records with each of the four antennas. It can be caused by an antenna mismatch with the ground surface. Antennas are designed to be operated over a ground surface with a specific set of electrical properties. When there is an impedance mismatch, the antenna does not transmit a single electromagnetic wave pulse into the ground but rather a series of pulses over time. Other sources of ringing may also occur, for example, between the antenna and a deeper clay layer or between two clay

layers. Overall, the problems associated with antenna design and soil conditions at the test site rendered very poor quality data in terms of mapping buried objects.

Only the pyramid stack of drums was clearly visible in the radar data probably because it was the shallowest target. Interferences caused by the casings, the steel drum, the concrete-filled pipe, the pile of crushed drums, and the stack of eight drums were perhaps visible but in no means clearly recognizable. When the radar method is able to image a waste object, its accuracy is high and may approach ± 0.25 m. Figure 7 displays the reflections from the top drums in the pyramid stack. Figures 8 and 9 represent the type of responses observed above the steel casing. The 300-MHz antenna provided the best results in all cases, but a conclusion that 300 MHz is the optimum frequency would be premature based on this study alone.

Estimating Pit Boundaries, Cover Thickness, and Depth to Basalt

An integrated electromagnetic and magnetic data interpretation resulted in a pit boundary that correlates with the historical boundary to ± 1 m. The interpretation assumed that the boundary coincides with the half amplitude point along the electromagnetic inphase data profile (based on consideration of simple models) and that the boundary was relatively straight (based on probable excavation and burial methods). The boundary was positioned to include electromagnetic and magnetic data anomalies. Although not evident in the simulated waste pit data, nonmetallic waste materials would also be enclosed within the boundary if detected. The radar method was not used to estimate the boundary because of the poor quality data obtained in the large object zone as described earlier.

Figure 10 shows the pit boundary interpreted from the inphase electromagnetic data. Figure 11 shows areas that contain high concentrations of ferrous metal as interpreted using magnetic vertical gradient data. These ferrous materials are enclosed by the pit boundary shown in Figure 10. The electromagnetic induction method allowed better boundary estimates than the

Figure 7. Ground penetrating radar (300 Mhz) along line 13N showing reflection from pyramid stack of drums. Interpreted location indicated by shaded box correlates well with historical location.

Figure 8. Ground penetrating radar (300 Mhz) along line 7N showing historical and interpreted locations of steel casing. Shading indicates interpreted location based on weak reflections.

Figure 9. Ground penetrating radar (300 Mhz) along line 9N showing historical and interpreted locations of steel casing. Shading indicates interpreted location based on weak reflection.

Figure 10. Inphase electromagnetic data map of simulated waste pit showing both historical and interpreted boundaries (values are unitless). Shading indicates interpreted pit boundaries.

Figure 11. Vertical magnetic gradient map of simulated waste pit showing both historical and interpreted boundaries (units in gammas/meter). Shading indicates interpreted pit boundaries.

magnetic method presumably because only low concentrations of ferrous metal were scattered throughout the pit. Furthermore, some nonferrous metal was present that the magnetic method will not detect but the electromagnetic method will detect.

The interpreted boundary encloses all detectable conductive and/or magnetic objects but does not necessarily extend to the excavation boundary. The excavation boundary was not evident in either the magnetic data or the electromagnetic induction data. The excavation boundary could be detected only if the backfill soil exhibits a significant electromagnetic or magnetic contrast from the undisturbed contrast. Such a contrast is possible if, for example, a different soil type is used as backfill or a large change in density exists. However, the response of nearby conductive or magnetic objects will likely overwhelm any measurable contrast from an excavation boundary.

In terms of vertical boundaries, the magnetic data show limited success in estimating depths to simulated waste objects. Table 2 presents both the historical and interpreted depths to several objects within the large object zone. Depth interpretations were made only for the pyramid of drums, pile of crushed drums, and steel casings. The horizontal extent of the straight slope of the magnetic response was used to estimate the depth of magnetic objects (Vacquier et al., 1951; Steenland, 1965). As a rule, shallow bodies cause short slopes while deeper bodies cause broad slopes. Electromagnetic data was not used to determine object depths. The extent of information gained from the electromagnetic method is that the anomalous low electromagnetic data above the pyramid stack of drums indicate a relatively shallow body.

The determination of object depth using ground penetrating radar was essentially impossible because an estimate of the subsurface dielectric

Table 2. Depth estimates interpreted from total magnetic field data

<u>Object</u>	<u>Historical Depth (m)</u>	<u>Interpreted Depth (m)</u>
Pyramid of Drums	1.1	0.7 - 1.4
Pile of Crushed Drums	2.3 - 2.6	1.8 - 3.0
Steel Casings	1.9 - 2.2	1.5 - 2.7

constant is required to convert radar wave travel times into depth. Independent estimates of the dielectric constant were not possible. Given the known depth to the pyramid of drums, the dielectric constant of the overlying soils was estimated at 5 to 6 at 300 MHz. Depth estimates for the objects that caused weak responses are not reliable because of the uncertainty in the dielectric constant and the unclear reflections.

Depth to the bottom of the waste pit and depth to basalt could not be determined using radar, electromagnetic induction, or magnetic methods. The radar signal will not penetrate through metal and was not shown to penetrate through the soil to the degree necessary for a reliable basalt reflection.

Identifying the Type of Materials Inside the Waste Pit

An integrated interpretation of magnetic and electromagnetic induction data is theoretically able to distinguish between (a) conductive, ferromagnetic material such as steel (b) conductive, nonmagnetic material such as aluminum, copper, lead, and some types of stainless steel, and (c) nonconductive, nonmagnetic material such as paper, clothing, and wood. In this section, the ability to make these distinctions at the simulated waste pit is discussed.

Figure 12 shows the electrical conductivity for the entire test site measured with the EM31. The measured value is a weighted average of the conductivities of all nearby materials to a depth of approximately 6 m. In a homogeneous half-space (equal conductivity of all subsurface materials nearby

Figure 12. Quadrature phase electromagnetic data map of simulated waste pit showing historical boundaries (units in millimhos/meter).

the instrument), the EM31 quadrature phase measurement is equal to the actual conductivity. Limitations in using the measured value to estimate the actual conductivity are as follows: (a) under conditions of lateral conductivity discontinuities (buried objects and horizontal boundaries), the measured value is dependent on instrument orientation, (b) for a layered earth (soil and basalt), the measured value can only be considered as a weighted average to the penetration depth of inducing field, and (c) the EM31 measurement accuracy decreases for materials having conductivities greater than about 100 mmho/m such as metal (McNeill, 1980).

The electromagnetic induction method is able to distinguish between metallic and nonmetallic materials and to estimate electrical conductivity given the limitations listed above. The following observations and conclusions were possible from the inspection of electromagnetic inphase and quadrature phase data:

- Metallic materials are distinguishable from nonmetallic materials by the electromagnetic inphase response. It follows that nonmetallic materials were present inside the pit boundaries and outside the mapped locations of conductive objects.
- The measured conductivity depends partly on the amount of metal present. In many cases it is possible to distinguish scattered metal (metal construction debris) from steel drums or large metallic waste forms based on the amplitude of the quadrature phase response signal. This is true especially when depth estimates are possible.
- Different types of waste are not distinguishable from different types of waste containers. For example, the response from cardboard drums containing metal was identical to the response from metal drums containing paper.

- The soil has a conductivity of approximately 30 mmho/m determined from the quadrature phase data.

Figure 13 shows the measured total magnetic field for the entire test site. The measured value depends on the magnetization of all nearby materials. Both the iron content of geologic materials on a large scale and the presence of a shallow steel drum will effect the measured field.

More importantly though, magnetic anomalies indicate the presence or absence of concentrated ferromagnetic elements that are common in waste materials. Buried waste materials can then be classified as ferromagnetic or nonmagnetic using magnetic measurements. The description available for the materials placed in the simulated waste pit does not allow us to clearly demonstrate this distinction since they do not specify types of metal. Most of the anomalies in the magnetic data are also present in the electromagnetic data. This implies that the metal detected by the electromagnetic induction method contains iron. The only significant discrepancy is over the stacked box zone.

The electromagnetic induction data show a conductive response over the entire stacked box zone indicating a large amount of metal. The magnetic data do not indicate the presence of a large amount of ferromagnetic materials. The most reasonable interpretation of electromagnetic and magnetic data is that conductive, nonmagnetic materials such as aluminum, stainless steel, or copper are present in this zone. However, the description and photographs of the simulated waste inside the boxes seems to contradict that interpretation. Loomis (1989) states,

For ISV users, the maximum metal content should be in the stacked box region. In addition, the metal boxes were mostly oriented on the top row. . . .Metal waste forms included discarded office furniture, pipes, I-beams, heat exchanges, cabinets, ducting wire, gears, wheels (rims), bus break drums, metal sheeting, cut up plate steel, discarded lab instruments, etc. These metal forms were used for both the drums and boxes with the larger objects put into the boxes.

Figure 13. Total magnetic field map of simulated waste pit showing historical boundaries (units in gammas).

If the zone does contain large amounts of steel, the magnetic data response cannot be explained, and the reasons for an uncharacteristic response should be investigated since the implications are important.

Evaluation of Electromagnetic Induction and Magnetic Methods

A comparison of the magnetic and electromagnetic induction methods reveals that

- In the vertical gradient mode, the magnetic method is able to resolve more individual objects than the electromagnetic method.
- The electromagnetic method is able to define the boundaries of objects more correctly than the magnetic method.
- The magnetic method is better at estimating depths than the electromagnetic method.

A comparison between the historical information and the results from the magnetic and electromagnetic induction methods yields the following conclusions:

- Most areas containing large amounts of metal can be detected.
- The size and position of conductive and/or magnetic objects or groups of objects can be estimated to ± 1 m.
- Resolution of objects in close proximity is limited. For example, the crushed drum pile, steel tank, and reinforced concrete blocks can not be identified as separate items nor can the two casings and concrete vaults be distinguished from one larger object.
- Relatively deep or relatively small objects nearby larger or shallower objects are often impossible to detect. A magnetic or

electromagnetic anomaly associated with the concrete-filled steel cylinder could not be recognized.

- Waste materials that are both nonconductive and nonmagnetic are not detectable unless their presence can be inferred by data anomalies that indicate the absence of magnetic and conductive materials (not observed at the simulated waste pit).

CONCLUSIONS

The tests demonstrate limited success in determining (a) pit boundaries, (b) location of metal inside pit, (c) type of waste materials, and (d) bulk material properties. The electromagnetic induction method provided locations for most of the large metal objects, estimated the pit boundary, and qualitatively differentiated between areas without metal, areas with scattered metal, and areas with large amounts of metal. The magnetic method detected nearly all the large metal objects, provided depth estimates for several of the objects, and distinguished between ferrous and nonferrous metal. The ground penetrating radar method is able to characterize the upper 1.1 m as shown by defining the location of the top drums in the pyramid stack.

The tests also demonstrate several important limitations especially for the ground penetrating radar method. The radar instrument had extremely limited exploration depth and thus demonstrated little use at the simulated waste pit. Rapid energy attenuation and excessive ringing associated with the SDA soils are the suspected causes of the poor quality data.

For the electromagnetic induction and magnetic methods, difficulties were experienced in using qualitative interpretation methods to provide accurate quantitative results such as depth, size, orientation, and material properties of target. The electromagnetic induction method provided only ± 1 m accuracy in object location and pit boundary estimates. The magnetic method provided only crude estimates of object locations and is limited to detecting significant amounts of ferrous metal.

The use of both electromagnetic induction and magnetic methods is useful. They provide redundant data that increases confidence in the final interpretation. They provide different levels of near-surface sensitivity and thus enhance the ability to discriminate between small shallow objects and deeper buried waste materials. They also allow an often important distinction to be made between ferrous metal and nonferrous metal.

This study at the simulated waste pit demonstrates the clear potential of each of the tested techniques for use in future investigations at the SDA. However, the study also indicates that caution is necessary in accepting the geophysical interpretation as absolute information. This acceptance or confidence in the geophysical interpretation increases by the use and integration of several methods.

REFERENCES

- Bartholomay, R. C., L. L. Knobel, and L. C. Davis, 1989, *Mineralogy and Grain Size of Surficial Sediment from the Big Lost River Drainage and Vicinity, with Chemical and Physical Characteristics of Geologic Materials from Selected Sites at the Idaho National Engineering Laboratory, Idaho, U.S.* Geological Survey Open-File Report 89-384.
- Loomis, G. G., 1989, *Design and Construction Details of the INEL Simulated TRU Test Pit*, EG&G Engineering Design File BWP-ISV-009, March.
- McNeill, J. D., 1980, *Electromagnetic Terrain Conductivity Measurement at Low Induction Numbers*, Geonics Limited Technical Note TN-6, Mississauga, Ontario.
- Olhoeft, G. R., 1986, "Direct Detection of Hydrocarbons and Organic Chemicals with Ground Penetrating Radar and Complex Resistivity," *Proceedings of the NWWA/API Conference on Petroleum Hydrocarbons and Organic Chemicals in Ground Water - Prevention, Detection, and Restoration*, November 12-14, Houston, Texas, pp. 284-305.
- Olhoeft, G. R., 1987, "Electrical Properties from 10^{-3} to 10^9 Hz - Physics and Chemistry," *Proceedings of Second International Symposium on the Physics and Chemistry of Porous Media*, October 23-27, Ridgefield, Connecticut, pp. 281-298.
- Steenland, N. C., 1965, "Oil Fields and Aeromagnetic Anomalies," *Geophysics* 30, 5, pp. 706-739.
- Vacquier, V., N. C. Steenland, R. G. Henderson, and I. Zietz, 1951, *Interpretation of Aeromagnetic Maps*, *Geologic Society of America Memoir* 47, New York, New York.
- Vigil, M. J., 1989, *Subsurface Disposal Area Waste Identification (1952-1970 Emphasis)*, EGG-WM-8727, March.

APPENDIX A
ELECTROMAGNETIC AND MAGNETIC DATA

APPENDIX NOTES

Magnetic Field Data

The following appendix includes vertical gradient (GRAD.) and total field (FIELD) magnetic measurements. The units of magnetic gradient are gammas/meter. The units of total field strength are gammas. The map locations are given in northings (N) and eastings (E) in meters from the survey origin (0,0). The two sets of magnetic data differ by the height of the transducer above the ground surface. The larger, more coarsely sampled data set was taken with a sensor height of 1 meter. That data set was followed by a smaller more finely spaced data set with the transducer at a height of 0 meters above the ground surface. All of the data have been corrected for drift based on the regular occupation of a base station.

Electromagnetic Induction

Several measurements of electrical properties were taken at each station location. Those measurements include (a) an "Inphase" measurement with the instrument transducers oriented in a north/south (N/S) alignment, (b) an "Inphase" measurement with the instrument transducers oriented orthogonally in an east/west (E/W) orientation, and (c) a conductivity measurement (COND.) made with the transducer alignment N/S. The "Inphase" measurements are a ratio of the induced-inphase field over the primary field and is unitless. The units of the conductivity measurements are millimhos/meter. As with the magnetic data, the station locations are given in northings (N) and eastings (E), in meters from the survey origin (0,0).

END

DATE
FILMED

6/09/92