201340

1 OF 1

DOE/ER/12894--3

DE92 013402

STABILITY OF A LIQUID-FILM SPACE RADIATOR
WITH INTERNAL ELECTROSTATIC FIELDS

Progress Report for Period
October 1, 1991 - September 30, 1992

S.G. Bankoff and M.J. Miksis

Northwestern University
Evanston, IL 60208

April 1992

Prepared for

THE U.S. DEPARTMENT OF ENERGY AGREEMENT NO. DE-FG02-89ER12894 ✓

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Abstract

A lightweight fully-modular radiator design is proposed, which is calculated to weight less than 1 kg/m^2 . The feature which makes this thin-membrane radiator practical is the internal electrostatic field system, which can stop radiator leaks from punctures, sudden accelerations or accidental tears.

1. Overview

A new concept in light-weight space radiators has been introduced by Kim, Miksis and Bankoff (1991a), consisting of a pumped-loop membrane radiator in which leakage of coolant from a puncture, due to micrometeorite or space debris impact, is prevented by the application of an internal electrostatic field. For nuclear space power, the coolant is generally a liquid metal, such as lithium, flowing as a thin film along the interior walls of the hollow radiator. A light radiator weight is achieved because of the very low internal pressure (0.96 Pa in the case of lithium at 800°K). The membrane wall can thus be a thin composite, and practically all micrometeorite punctures will not cause leakage, because of the restraining effect of the capillary pressure. If the exterior surface of the membrane is unwetted by the liquid metal, the capillary pressure at the mouth of a one-micron puncture is of the order of 1 MPa . Even if partial wetting at the exterior surface, due to chemical attack by the alkali liquid metal, is achieved over time, the minimum curvature of the liquid surface at the mouth of the puncture is still large enough to prevent leakage. In this respect the proposed radiator differs from space radiators which operate under

significant internal pressure. Reliance on redundancy, while clearly the simplest concept, has the strong disadvantage that a cloud of solidified coolant particles would probably be produced by the coolant jet out of the puncture. This cloud can coat sensitive optics and instrumentation for some time before finally subliming at space temperatures. It is preferable, therefore, to design for no leakage from the radiator due to micrometeorite or debris impacts.

This can be achieved by installing an internal electrode system, in order to prevent leaks from even large punctures (say, 1 cm). Such impacts, of course, would be extremely rare, and could be handled by redundancy. However, for an extra safety margin, an internal electrostatic-field system is employed. The principle is that an electrostatic field exerts a normal stress on the surface of a conductor, which tends to pull it into the non-conducting region. Thus, an electrostatic field, produced by charging a very thin electrode suspended above the liquid-metal film to a high voltage, will exert a normal tensile stress, pulling the liquid away from the puncture. Electrostatic forces are quite weak, and their use is made feasible only because of the extremely low internal pressure of this type of radiator. Even so, rather large voltages must be employed, of the order of 10-30 kv (recall that the breakdown voltage in dry air is about 30 kv). However, gas breakdown in this radiator is not possible, because of the large mean free path (of the order of 1 cm). On the other hand, small leakage currents, owing to secondary electron and field emission, can occur, and must be considered in the design of the electrodes and wires. Note that punctures of the electrodes by micrometeorites passing the radiator wall and the liquid film (about 3mm thick) are expected to be very small, and will not affect the electric field. The outside surface is provided with an

electrically-insulating coating, followed by a segmented carbon coating. Each segment is opposite an electrode of the same shape and size, in the form of a thin metallic coating on the non-conducting inner membrane. The isolated segments have individual electrical connections, which allow measurement of resistance to ground in order to detect a puncture. If the puncture is large enough to cause actual continuing leakage, this results in a decreased resistance signal, which triggers the charging of the internal electrode positioned above the puncture. The carbon segments may also be used as heaters to start up the radiator after a shutdown.

A problem which has required serious consideration is the stability of the liquid film under the combined influence of the electric field, the centrifugal body force, and the initial liquid momentum. The electrostatic tensile stress tends to destabilize the film; the normal centrifugal force component results in a hydrostatic pressure, which adds to the vapor pressure to increase the magnitude of the field necessary to stop a leak; and the centrifugal force component parallel to the inclined wall and the momentum imparted by the entrance walljet tend to drive the liquid past the puncture and out of the influence of the electric field. The design envelope of conditions to achieve the double objective of leak stoppage plus film stability has required detailed calculations (Kim, Bankoff and Miksis 1991b, 1992a).

2. Radiator Concepts

Two alternative radiator concepts have been discussed, (Kim, Miksis, and Bankoff 1992b). The first is a non-rotating radiator, in which the centrifugal force needed to stabilize the film in normal operation is achieved by the concave curvature of the membrane wall. The radius of curvature is large compared to the film thickness, so that for analysis the

wall can be considered to be locally flat, (Kim et al. 1991b). The second concept consists of an opposed pair of rotating truncated-conical radiators (Kim et al. 1992a). For small cone angles the analysis is quite similar to that for the non-rotating curved radiator, although here there is a small centrifugal force component parallel to the wall, which aids in driving the film.

If the cone angle is increased to nearly 90° , one obtains a modular hollow-disk geometry. The disk may be tapered, with straight sides, or it may be an oblate spheroid, in order to improve the view factor. In either case, over most or all of the wall area, the local slope of the wall is nearly normal to the axis of rotation, instead of being nearly parallel to it, as in the small-angle conical radiator. This minimizes the hydrostatic pressure tending to drive liquid out through the puncture, and maximizes the body force tending to drive liquid along the wall, and past the puncture. By allowing smaller Reynolds numbers, and hence thinner liquid films, this increases the range of operative conditions for the electrostatic option, and at the same time makes it less likely that it will be needed, because of the reduced hydrostatic pressure. The principal weight contributors are now the rotating pumps and piping, rather than the radiator walls and electrostatic system. The return pumps must be located on the outer periphery in order to assure positive suction. One design option employs peripheral collector pipes which feed the liquid from all the disks to the peripheral return pumps. However, armor and redundancy is then required for the exposed piping and pumps. An alternative design, which appears to be attractive, is to place the return pump and piping for each module inside the radiator. This makes use of the radiator outer membrane, the liquid film, and the internal electrostatic-system membrane for shielding against

micrometeorite impacts. Even though these impacts have large kinetic energy, breakup of the particles occurs upon passing through the membranes. Also, the collector plenum at the outer periphery is an effective energy absorber. Hence the internal pipe and pump for each disk need be only lightly armored, if at all. This requires the development of small, lightweight pumps made of corrosion-resistant materials for this application. For a good view factor, the disks must be spaced about one diameter apart. The central inlet-outlet piping is then exposed, and must be armored. As shown below, the best compromise uses an intermediate cone angle with the cone-pairs touching each other. There is then no exposed piping, and the centrifugal force component parallel to the walls is still sufficient to allow very thin liquid layers.

2. Rotating Radiators

One realization of the radiator is diagrammed (not to scale) in Fig. 1. The radiator wall is a thin membrane, which may be flexible or rigid. If rigid, it could consist of a carbon-carbon composite with an inside coating of niobium to protect the carbon from attack by the lithium. For large cone angles β , the cone becomes a tapered disk (the rotating disk radiator) (also see Fig. 6). Axial fins between adjacent disks may be used to provide increased structural rigidity and heat transfer. If flexible, this allows the radiator disks to be folded up during launch, and afterwards deployed, either by internal gas pressure, or mechanically.

The radiator disks in each module are mounted on a central single rotating inlet/outlet pipe, with insulation in between, or two separated inlet and outlet pipes. For compactness during launch, these pipes may be made of telescoping segments. These modules can be connected in series/parallel, in accordance with mission requirements.

Some typical performance, figures for a straight-sided, tapered-disk radiator without fins, operating with lithium at 800°K inlet temperature, are:

Inner and outer disk radius: 0.05, 0.5 m

Inlet and outlet Reynolds number: 400, 40

Coolant flow rate/disk: 0.05 kg/s

Exit coolant temperature: 710 K

Power/disk: 25.8 kw

The use of axial fins would further improve the performance.

3. Electrohydrodynamic Calculations

Extensive calculations, Kim, et al. (1991b, 1992a), have been performed to obtain the film thickness and bottom pressure as functions of both space and time. Three methods of calculation were employed. For a Reynolds number of $O(1)$, inertial effects can be neglected at lowest order, and a long-wave approximation is appropriate. The Reynold number Re is defined as $Re = \rho U_0 d / \mu$, where ρ is the density of the liquid, μ is the liquid viscosity, d is the inlet thickness and U_0 is the average entrance velocity. For locally flat surfaces the evolution equation is

$$\frac{\partial h}{\partial t} + 3h^2 \frac{\partial h}{\partial x} + \xi \frac{\partial}{\partial x} \left[\frac{6}{5} Re h^6 \frac{\partial h}{\partial x} - \cot(\beta) h^3 \frac{\partial h}{\partial x} + \frac{2}{3} \frac{\xi^2}{Ca} h^3 \frac{\partial^3 h}{\partial x^3} \right]$$

(1)

$$+ \frac{2}{3} \xi K \left(1 - \frac{1}{\epsilon_f} \right) \frac{\partial}{\partial x} \left[h^3 \frac{\partial}{\partial x} [E_n]^2 \right] = 0,$$

where h is the height of the film. The small parameter is ξ , equal to the ratio of the entrance film thickness to a characteristic streamwise length scale. β is the angle of inclination with respect to the horizontal, or in

this case, the axis of rotation and ϵ_f is the liquid dielectric constant.

E_n is the normal component of the electrostatic field at the surface of the film, and K , assumed to be of order one, is a dimensionless electrostatic field constant:

$$K = \frac{\epsilon_0 d F^2}{16 \pi \mu U_0} \quad (2)$$

Here ϵ_0 is the vacuum dielectric constant and F is the unit of electric field. The capillary number is given by

$$Ca = \frac{2 \mu U_0}{\sigma} \quad (3)$$

where σ is the surface tension.

For large Reynolds numbers, the inertial terms appear at lowest order, and it is necessary to use the Karman-Pohlhausen approximation to obtain an evolution equation. The local velocity is approximated by

$$u = \frac{3q}{h} \left[\frac{y}{h} - \frac{1}{2} \left(\frac{y}{h} \right)^2 \right], \quad (4)$$

where y is the distance normal to the wall, and q is the local flowrate defined by

$$q = \int_0^h u dy. \quad (5)$$

One then obtains a coupled set of nonlinear hyperbolic equations for the height h and flowrate q :

$$\frac{\partial h}{\partial t} = - \frac{\partial q}{\partial x} \quad (6)$$

$$\frac{\partial q}{\partial t} + \frac{\partial}{\partial x} \left(\frac{6}{5} \frac{q^2}{h} \right) = \frac{2 \bar{K} h}{R} \frac{\partial}{\partial x} (E_n)^2 - \frac{3}{R} \frac{q}{h^2} + \frac{\cos(\theta)}{Fr^2} \left(\frac{h}{B} - h \frac{\partial h}{\partial x} \right) \quad (7)$$

where $R = \xi Re = O(1)$, $B = \xi \cot(\beta) = O(1)$, $\bar{K} = \xi K = O(1)$ and the Froude number is given by

$$Fr = \frac{U_0}{\sqrt{gd}} \quad (8)$$

The centrifugal acceleration, g , is determined by the radius and the angular speed at the entrance. These equations are coupled to the electric field by solving the Laplace equation in the vacuum region.

The third method is a direct solution of the Navier-Stokes equations, using the finite-difference code SOLA. The code is easily modified for the presence of the electric field. Good agreement is obtained with all these methods in the regions where their applicability overlaps.

We have also performed a linear stability analysis for the long-wave approximation, obtaining an extension of the classical Yih-Benjamin result for a falling film on an inclined plane wall. Equation (1) is linearly stable if

$$Re < \frac{5}{6} \cot \beta - \frac{10}{9} K \frac{H^2(1 - 1/\epsilon_f)^2}{\left(\frac{1}{\epsilon_f} + H - 1\right)^3} + \frac{5}{9} \frac{\epsilon_f^2}{Ca} \alpha^2, \quad (9)$$

where α is the wave number of the disturbance and H is the distance from the inclined plane to the charged electrode. The second and third terms on the right represent the destabilizing effect of the electrostatic field and the stabilizing effect of surface tension.

4. Numerical Results

The coordinate system for the rotating, small-angle conical radiator is shown in Fig. 1, with the puncture being taken at $x = 0$. Solutions of the Karman-Pohlhausen approximation as applied to the rotating radiator are presented in Fig. 2 and Fig. 3 (Kim et al. 1992a). Here we plot the film

thickness h and the bottom pressure p as a function of x for $t_n = n (0.03)$ sec, $n = 0, \dots, 15$, respectively, at a film Reynolds number $Re = 662.5$, with the unit of electric field $F = 28$ kv/cm, height of the charged electrode above the radiator wall $H = 1$ cm and its length in the streamwise x -direction $l = 3$ cm, $\beta = 0.1$ rad, $d = 0.2$ cm, the angular velocity $\Omega = 4$ rad/sec and the other parameters are for lithium at 800°K . The initial film height h is given by its steady-state shape without the electric field. At $t = 0$ the electric field is turned on and a disturbance is generated. A trough appears ahead of the puncture, and a peak behind the puncture, but the peak height reaches a maximum at about 20% of the initial steady-state film thickness, and then decays, leaving a steep, propagating wave, which eventually is convected away. The bottom pressure above the puncture becomes negative, with the minimum value above the puncture reaching about -19 dynes/cm over a distance of 1 cm. This gives a safety factor of 2 for stopping a leak of lithium at 800°K (vapor pressure 9.57 dynes/cm²). The steady state film thickness in the rotating radiator is shown in Fig. 4 for three Reynolds numbers obtained by changing only the angular velocity Ω while keeping the other parameters as in Fig. 2. For the case of the rotating disk radiator, β is set to 1.5 rad and three cases of Reynolds numbers are considered, i.e., $Re = 413.7$ ($\Omega = 1$ rad/sec), $Re = 930.8$ ($\Omega = 1.5$ rad/sec) and $Re = 1654.8$ ($\Omega = 2$ rad/sec), using the same parameters as in the rotating small-angle-cone radiator to plot steady-state film profiles in Fig. 5. Comparing the results of the rotating small-angle-cone radiator, the film-thinning phenomenon is more apparent in the rotating disk radiator, owing to the increased centrifugal force in the streamwise direction. It is seen that, as the Reynolds number is increased, the wave is stabilized by convection through the field in both radiators.

5. View Factor of the Rotating Disk Radiator

One concern for the rotating disk radiator is the effective view factor. Fig. 6 shows a diagrammatic sketch of the hollow-disk radiator, with the interior cone angle being determined by the ratio $LE/\bar{R} = \cot(\beta)$. It is seen in Fig. 7 that for $LE = 0.1$ m with a disk outer radius of 0.5 m, the view factor is 0.84. The addition of two axial fins, 1 m long and 0.5 m wide, increases the view factor to above 0.9.

6. Design Calculations

Figs. 8 and 9 show two possible piping arrangements for the rotating radiator which consists of pairs of opposed cones on central rotating inlet-outlet pipes. Fig. 8 shows two cone-pairs with telescoping inlet-outlet central pipes. The peripheral pump and radial return line for each cone-pair are located within the radiator. In this design there is no exposed pump or piping, and the entire module can be collapsed. Fig. 9 shows the same pair of opposed cones with external telescoping return piping and pumps, which also can be collapsed. Figs. 10 and 11 show the folded and collapsed radiators, for the case when the radiator membrane is flexible. The central inlet and return pipes may be separate, as in Fig. 10, or concentric, with insulation between. Figs. 12 and 13 show the weight/power ratio, excluding the liquid within the radiator (which is part of secondary circulation system, present in any type of radiator) vs. the slope of the disk in degrees relative to the radial direction. The basis of the calculations plotted in Fig. 12 was that, the probability of survival of exposed piping in a ten-year period for a radiator consisting of five cone pairs to be 0.95. With interior piping, as in Fig. 8, the probability becomes very close to one because of the shielding provided by the inner and outer membranes and the liquid film. The cone-pair maximum radius and the

rotation rate in each case are determined for a chosen inlet Reynolds number and temperature drop through the radiator, as a function of the slope angle. Fig. 12 shows that the minimum weight per unit power is 0.181 kg/kw of the ceramic-piping radiator and accessories. This is obtained for zero spacing ($K=0$), and slope angle of 37.5° . For a carbon-piping radiator, the corresponding figure is 0.125 kg/kw at a slope angle of 52.5° ($K=0$). Fig. 14 shows the low figure of 0.10 kg/kw at an inlet Reynolds number of 400 for a carbon-piping radiator for an outflow temperature of 700-760K, with an inlet temperature of 800K, and a slope angle of 45° .

7. Summary

The concept of using internal electrostatic fields to stop leaks from a thin-film, pumped-loop, membrane radiator has been shown to be promising. A substantial reduction in weight appears to be possible. Other attractive features include the virtual elimination of leaks from micrometeorite or space debris impacts the rotating, hollow-disk radiator appears to be attractive because thinner liquid films, allowing closer placement of the electrodes to the film, can be attained. Modular construction allow flexibility and ruggedness. Single point failures are avoided by armoring the piping and pumps, and placing the small van de Graaf generators within the space vehicle. The electrostatic option is highly desirable, but not necessary, since only very large punctures or tears will leak. An extra advantage is that the isolated detection segments on the outside can also be used for melting the frozen liquid for startup in space.

8. Effort of Principal Investigators

SGB took one summer month in summer salary during this period while MJM took two months.

9. Papers Generated Under this Grant

1. Kim, H., Miksis, M.J. and Bankoff, S.G., 1991a, "Lightweight Space Radiator with Leakage Control by Internal Electrostatic Fields," Proc. Eighth Symp. on Space Nuclear Power Systems, Albuquerque, NM, CONF-910116, pp. 1280-1285.
2. Kim, H., Bankoff, S.G. and Miksis, M.J., 1991a, "The Effect of An Electrostatic Field on Film Flow Down an Inclined Plane," submitted to Phys. Fluids.
3. Kim, H., Bankoff, S.G. and Miksis, M.J., 1992b, "Interaction of an Electrostatic Field with a Liquid Film Flow Within a Rotating Conical Space Radiator," submitted to AIAA Journal.
4. Kim, H., Miksis, M.J. and Bankoff, S.G., 1992b, "The Electrostatic Liquid-Film Radiator for Heat Rejection in Space," Proc. of the 1992 National Heat Transfer Conference, to appear.
5. Kim, H., 1992 "The Dynamics of Selected Thin-Film Flows with an Internal Electrostatic Field", Ph.D. Thesis, Department of Chemical Engineering, Northwestern University.
6. Weidele, T., 1991, "Design of a Rotating Space Radiator," unpublished project report, Chemical Engineering Department, Northwestern University.

10. Presentations by S.G. Bankoff

1. "Lightweight Space Radiator with Leakage Control by Internal Electrostatic Fields," 1991 Eighth Symposium on Space Nuclear Power Systems, Albuquerque, NM.
2. "Advanced Radiators for Space Power," Rocketdyne Division, Rockwell International Corp., Canoga Park, CA, 1991.
3. Dynamics and Stability of a Thin Conductive Liquid Film Flowing on a Solid Surface Upon Application of an Electrostatic Field," Am. Phys. Soc., Div. of Fluid Dynamics, 44th Annual Mtg., Scottsdale, AZ, 1991.
4. "The Electrostatic Liquid Film Radiator for Heat Rejection in Space," 1992, National Heat Transfer Conference, San Diego, CA.
5. "Dynamics of the Thin Liquid Metal Film Flowing within a Rotating Corical Radiator with Internal Electrostatic Fileds," Symp. on Fundamental Research in Fluid Mechanics: Interfacial Flows, AIChE Annual Mtg, Miami, FL, 1992.
6. "Design Considerations for the Electrostatic Liquid Film Space Radiator," NTSE 92, Nuclear Technologies for Space Exploration, Jackson, WY, 1992.

Figure 1: The coordinate scheme of the rotating flow with $x = 0$ as puncture location.

Figure 2: The film thickness profile determined by equations (4) and (5) for $t = n(0.03) \text{ sec}$, $n = 0, \dots, 15$ with $F = 28 \text{ kv/cm}$, $\beta = 0.1 \text{ rad}$, $d = 0.2 \text{ cm}$, $\Omega = 4 \text{ rad/sec}$, $H = 1 \text{ cm}$, $l = 3 \text{ cm}$, $Re = 662.5$ and $\bar{K} = 0.15$.

Figure 3: The bottom pressure profile determined by equations (4) and (5) for $t = n(0.03)\text{sec}$, $n = 0, \dots, 15$ with $F = 28\text{kv/cm}$, $\beta = 0.1\text{ rad}$, $d = 0.2\text{ cm}$, $\Omega = 4\text{ rad/sec}$, $H = 1\text{ cm}$, $l = 3\text{ cm}$, $Re = 662.5$ and $\bar{K} = 0.15$.

Figure 4: The steady-state film thickness profiles determined by the Karman- Pohlhausen model with $F = 28 \text{ kv/cm}$, $\beta = 0.1 \text{ rad}$, $d = 0.2 \text{ cm}$, $H = 1 \text{ cm}$, $l = 3 \text{ cm}$ and $Re = 372.6, 507.2, 662.5$.

Figure 5: The steady-state film thickness profiles determined by the Karman- Pohlhausen model with $F = 28 \text{ kv/cm}$, $\beta = 1.5 \text{ rad}$, $d = 0.2 \text{ cm}$, $H = 1 \text{ cm}$, $l = 3 \text{ cm}$ and $Re = 413.7, 930.8, 1654.8$.

Figure 6: The diagram of the rotating disk radiator.

Figure 7: The effective view factor vs. the length LE in the rotating disk radiator.

Figure 8

Figure 9

Figure 10

Figure 11

Figure 12

Figure 13

Figure 14

END

**DATE
FILMED**

6/11/92