AIIM

Association for Information and Image Management

1100 Wayne Avenue, Suite 1100
Silver Spring, Maryland 20910
301/587-8202

Centimeter

Inches

MANUFACTURED TO AIIM STANDARDS
BY APPLIED IMAGE, INC.

1 of 1

**Cover Sheet for a Hanford
Historical Document
Released for Public Availability**

Released 1994

**Prepared for the U.S. Department of Energy
under Contract DE-AC06-76RLO 1830**

**Pacific Northwest Laboratory
Operated for the U.S. Department of Energy
by Battelle Memorial Institute**

~~RESTRICTED TO U.S. ONLY~~

DISCLAIMER

This is a **historical document** that is being released for public availability. This was made from the best available copy. Neither the United States Government nor any agency thereof, nor Battelle Memorial Institute, nor any of their employees, makes any **warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights.** The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DECLASSIFIED

DECLASSIFIED

HW-69419

This document classified by

C. B. Lewis

This document consists of
3 pages, No. 4 of 11
copies. [REDACTED]

1. AEC-HOO, Attn: RL Plum
2. AEC-HOO, Attn: JM Musser
3. JA Ayres
4. EC Bennett
5. TL Deobald
6. FC Franklin
7. CG Lewis
8. AEC-ORNL, Attn: MM Martin
9. AEC-ORNL, Attn: MM Martin
10. 300 Files
11. Record Copy

PHYSICS DATA FOR PROPOSED HAPO H-1 LOOP IRRADIATION

Classification Cancelled and Changed To

DECLASSIFIED

April 27, 1961

By Authority of RM-Hen

CG PR-2, 2-28-94

By J. E. Savelly 3-4-94

Verified By DK Hanson, 3-17-94

HANFORD ATOMIC PRODUCTS OPERATION
RICHLAND, WASHINGTON

NOTICE!

This report was prepared for use within General Electric Company in the course of work under Atomic Energy Commission Contract AT-(45-1)-1350, and any views or opinions expressed in the report are those of the authors only. This report is subject to revision upon collection of additional data.

LEGAL NOTICE

This report was prepared as an account of Government sponsored work. Neither the United States, nor the Commission, nor any person acting on behalf of the Commission:

A. Makes any warranty or representation, express or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this report, or that the use of any information, apparatus, method, or process disclosed in this report may not infringe privately owned rights; or

B. Assumes any liabilities with respect to the use of, or for damages resulting from the use of any information, apparatus, method, or process disclosed in this report.

As used in the above, "person acting on behalf of the Commission" includes any employee or contractor of the Commission to the extent that such employee or contractor prepares, handles or distributes, or provides access to, any information pursuant to his employment or contract with the Commission.

DECLASSIFIED

1954.

DECLASSIFIED

HW-69419

PHYSICS DATA FOR PROPOSED HAPO H-1 LOOP IRRADIATION

The HAPO H-1 Loop is a pressurized, water-cooled facility consisting of two horizontal concentric stainless steel flow tubes which run transverse to the normal reactor process channels. The coolant enters the loop in the annular region between the tubes and returns through the inner tube. The test fuel elements are placed in the inner tube. The loop is centered between two rows of process channels, the latter being spaced in an 8-3/8 inch square lattice arrangement. Figure I shows the materials and dimensions of the loop and process channels.

Unperturbed (in the absence of the loop), the volume average conventional thermal (2200 m/sec) neutron flux in the natural uranium in the reactor process tubes near the loop would be 3.5×10^{13} neutrons/cm² sec. The unperturbed volume average conventional thermal neutron flux in the loop location would be approximately 6.0×10^{13} neutrons/cm² sec. The actual neutron flux in this region is dependent on the material and geometry of the test elements placed in the loop. This flux can be determined by calculations and by irradiation of mock-up assemblies in the Hanford Test Reactor (HTR).

Gamma heating in aluminum components of test elements placed in the loop amounts to approximately 0.5 watt per gram.

F. C. Franklin
Irradiation Testing

F. C. Franklin/rch

DECLASSIFIED

HW-69419

4.1875" square hole
in graphite

347 S.S.
Pressure tube
O.D. = 3.75"
I.D. = 3.13"

Water entrance

water return and
test elements
inside of liner

347 S.S.
Liner
O.D. = 2.50"
I.D. = 2.402"

Helium

CROSS SECTION - H-1 LOOP

Aluminum process tube
O.D. = 1.729"
I.D. = 1.598"

Aluminum slug can
O.D. = 1.444"
I.D. = 1.356"

Water

Natural Uranium
O.D. = 1.356"
I.D. = 0.423"

Edge of graphite

Aluminum spire
O.D. = 0.423"
I.D. = 0.310"

CROSS SECTION - PROCESS CHANNEL

FIGURE I

(not to scale)

**DATE
FILMED**

6 / 28 / 94

END