AIM

Association for Information and Image Management

1100 Wayne Avenue, Suite 1100
Silver Spring, Maryland 20910
301/587-8202

Centimeter

Inches

MANUFACTURED TO AIM STANDARDS
BY APPLIED IMAGE, INC.

1 of 1

DECLASSIFIED

(CLASSIFICATION)

HANFORD TECHNICAL RECORD

GENERAL ELECTRIC

HANFORD ATOMIC PRODUCTS OPERATION - RICHLAND, WASHINGTON

DOCUMENT NO.

HW-77688

SERIES AND COPY NO.

DATE

May 21, 1963

THIS DOCUMENT CONTAINS RESEARCH DATA
DEFINING THE ATOMIC ACT OF
TRANSMITTAL OF INFORMATION
CONTENTS IN ANY MANNER TO AN UNAUTHORIZED
PERSON IS PROHIBITED.

TITLE

IRRADIATION AND PERFORMANCE OF LAMINAR

OTHER OFFICIAL CLASSIFIED INFORMATION

THIS MATERIAL CONTAINS INFORMATION AFFECTING
THE NATIONAL DEFENSE OF THE UNITED STATES
WITHIN THE MEANING OF THE ESPIONAGE LAWS,
TITLE 18, U. S. C., SECS. 793 AND 794, THE TRANS-
MISSION OR REVELATION OF WHICH IN ANY MANNER
TO AN UNAUTHORIZED PERSON IS PROHIBITED BY
LAW.

AUTHOR

C. M. Heeb
F. W. Knight
H. G. Spencer

CIRCULATING COPY

RECEIVED 100 D AREA

MAY 23 1963

RETURN TO

TECHNICAL INFORMATION FILES

THIS DOCUMENT MUST NOT BE LEFT UNATTENDED OR WHERE AN UNAUTHORIZED PERSON MAY HAVE ACCESS
TO IT. WHEN IN USE, IT MUST BE KEPT IN AN APPROVED REPOSITORY WITH AN APPROVED
GUARDIAN. WHILE IT IS IN POSSESSION AND USE, THE USER HAS OBTAINED A RECEIPT FROM
THE FILES, IT IS THE RESPONSIBILITY TO RETURN IT AND ITS CONTENTS WITHIN THE LIMITS OF
THIS PROJECT AND FOR ANY UNAUTHORIZED PERSON'S TRANSMITTAL TO STORAGE AT THEIR PLACE
OF RESIDENCE IS PROHIBITED. IT IS NOT TO BE DUPLICATED. IF ADDITIONAL COPIES ARE REQUIRED,
OBTAIN THEM FROM THE RELATED ISSUING OFFICE. ALL PERSONS RECEIVING THIS DOCUMENT ARE REQUESTED
TO SIGN IN THE SPACE PROVIDED BELOW.

ROUTE TO:

PAYROLL NO.

LOCATION

FILES ROUTE
DATE

SIGNATURE AND DATE

MAY 23 1963

DECLASSIFIED

Indefinite Retention

Disposal Date

Authority

DECLASSIFIED

EW-77688

~~This report contains restricted data as defined in Atomic Energy Commission Regulations. Its transmission or disclosure of its contents in any manner to unauthorized persons is prohibited.~~

This document consists of
5 pages, No. of
25 copies. ~~DECLASSIFIED~~

DISTRIBUTION

1-4. AEC-RLOC: Attn: AT Gifford	14-16. LW Lang
5. TW Ambrose	17. WN Mobley
6. HE Berg	18. CA Priole
7. AJ Blasewitz	19. JF Smith
8. CH Greager	20. FW Hall
9. AP Greninger	21. JF Schneider
10. RO Gumprecht	22. T. Spencer
11. CH Heath	23. JF Smith
12. FW Knight	24. RGC Files
13. LE Kusler	25. Record Center

IRRADIATION PROCESSING DEPARTMENT

Classification Cancelled and Changed To

May 22, 1963

DECLASSIFIED

By Authority of DS Lewis
CG-PR-2 (PR-24) 3-22-94
By J E Savely 3-31-94
Verified By DK Hanson, 4-4-94

HANFORD ATOMIC PRODUCTS OPERATION
RICHLAND, WASHINGTON

MASTER

NOTICE

This report was prepared for use within General Electric Company in the course of work under Atomic Energy Commission Contract AT(45-1) - 1350, and any views or opinions expressed in the report are those of the author only. This report is subject to revision upon collection of additional data.

LEGAL NOTICE

This report was prepared as an account of Government sponsored work. Neither the United States nor the Commission, nor any person acting on behalf of the Commission:

A. Makes any warranty or representation, expressed or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this report, or that the use of any information, apparatus, method, or process disclosed in this report may not infringe privately owned rights; or

B. Assumes any liabilities with respect to the use of, or for damages resulting from the use of any information, apparatus, method, or process disclosed in this report.

As used in the above, "person acting on behalf of the Commission" includes any employee or contractor of the Commission, or employee of such contractor, to the extent that such employee or contractor of the Commission, or employee of such contractor prepares, disseminates, or provides access to, any information pursuant to his employment or contract with the Commission, or his employment with such contractor.

DECLASSIFIED

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

875

DECLASSIFIED

HW-77688

IRRADIATION AND PERFORMANCE OF DEPLETED URANIUM

I. INTRODUCTION

The production of plutonium containing 17 to 18 per cent Pu-240 has been proposed for Hanford as part of the over-all process for production of transuranium isotopes.¹ The purpose of this report is to summarize the measures that would be taken to ensure good performance of the depleted uranium fuel elements and to predict the performance of the depleted fuel.

II. SUMMARY

A single reactor load to produce plutonium high in the Pu-240 isotope would consist of about 240 depleted uranium charges. These depleted fuel elements should perform satisfactorily to a minimum exposure yielding 16 to 18 per cent Pu-240. The manufacturing and quality control measures outlined in this document must be effected to assure this performance.

Three factors will have a favorable influence on the performance of these elements in comparison to the previous long-term depleted elements which were canned and irradiated in 1958. These factors are as follows:

1. Control measures are planned to ensure that the quality of the core and the over-all element is equal to or better than the best quality normal and enriched material being produced at present.
2. There has been a huge performance improvement--approximately a factor of 10--in I&E elements since their inception in 1958 when the first depleted elements were canned.
3. The depleted uranium used in the 1958 irradiation was considered to be of poor quality relative to the regular uranium at that time because of the relatively uncontrolled manner it was reduced to metal.

The prediction of satisfactory performance is also based upon the favorable experience with a limited number of fringe tubes of normal uranium which presently are near the 1200 MWD/ton exposure.

III. DISCUSSION

The scheme for producing and irradiating the long-duration, low-temperature depleted elements is outlined in some detail below. It should be emphasized that the successful execution of this program is dependent upon adherence to the specified controls.

¹ Kusler, L.E., and R.O. Gumprecht, Proposal to Produce Transuranium Isotopes in Hanford Production Reactors, HW-77202, April 12, 1963, Secret.

DECLASSIFIED

HW-77688

A. Core and Element Fabrication

We propose to improve the probability that the long-duration, low-temperature depleted uranium elements could be run to high exposure goal in the following manner:

1. Expediting the immediate processing and irradiation of a ten per cent pilot charge to verify engineering judgments and identify unidentified problems for the main irradiation.
2. Instituting special controls, in the form of process and product specifications, designed both to reduce the variability and increase the average quality of the uranium cores and the finished fuel elements.
3. Following the process schemes that are presently used for producing enriched and normal fuel where ever possible in producing this material in order to ensure that the quality of these depleted elements is equal to or better than our present fuel models.

Specifically, the processing route and major controls will be as follows:

UF₆ to UF₄ Reduction

This would be performed by Union Carbide at Paducah or Oak Ridge with rigid process and product controls designed to eliminate significant Fe, Ni, and Cu contamination of the product green salt from processing equipment. A maximum particle size of 70 to 100 mesh would also be specified on the product to ensure uniform reduction of the green salt in the subsequent bomb reduction.

UF₄ to Metal Reduction

This would be performed by MCW at Weldon Springs with rigid control of the green salt, blending, and firing operation to produce sound, uniform metal dingots free of Fe, Ni, and Cu contamination and included slag.

The addition of Fe and Si additives will be made only in the reduction rather than in the remelt operation due to the inherent control. The range of the Fe and Si additives will be reduced by 50 per cent over those permitted for enriched and normal metal.

For feed to MCO's remelt operation, MCW would either produce the metal as segmented dingots for remelt feed or would produce solid dingots and gamma extrude and cut these up as remelt feed.

DECLASSIFIED

EW-77688

Remelting, Rolling, and Heat Treating

These operations would all be campaigned at NLO with special control by their Technical and Quality Control units.

Special controls will be instituted on their melting temperatures and times, their pouring temperatures, and their furnace pressures. No vacuum outgassing would be permitted.

The rolling would all be campaigned in one period with special coverage by their Technical and Quality Control units. All materials produced outside of NLO process limits, even though not specified by HAPO, will be rejected.

Due to the superior performance of salt-oil vs. salt-water heat-treated material, all the depleted would be salt-oil treated by NLO. This will require overriding operation in the special facility used for heat treating SPP material.

Product Specification

The product specification will permit no outgassing of the metal after remelting, no hydrogen over 2.0 ppm, no "Class III" out-of-specification dimensions, and the limits on the range of the Fe and Si additives will be reduced by 50 per cent to improve uniformity.

HAPO Quality Assurance

In order to assure that the quality of this material is at least as good as the present product, the following practices will be followed during canning:

- 1) Both the uranium cores and the aluminum cans will be given an additional visual examination.
- 2) The UT-2 grain size tester will be set to reject any cores having grain size larger than A-4.
- 3) In order to assure a high-quality product, the total bond count specification will be reduced 50 per cent.
- 4) Additional controls will be placed on the bond strength testers during this program to assure a high degree of tester reliability.

6. Reactor Loading

The tentative design for an old-reactor load of depleted fuel is as follows: Depleted fuel elements would be of the same design as present natural fuel elements except they would be shortened one inch. Tube

DECLASSIFIED

HW-77688

charges would be full length--36 to 38 elements to each tube. Approximately 240 depleted charges would make an old-reactor load. The depleted charges and most supporting E columns would be loaded in a band just inside the present enrichment rings. The additional enriched uranium required initially would be placed just outside the current enrichment ring and just inside the indicated E-D band. The amounts and locations would be such as to obtain a power distribution providing reasonable tube outlet temperatures in all supporting enrichment and in adjacent natural uranium fuel. Approximately 3-4% charges of additional enrichment would be required per depleted charge, initially, but the amount required would fall rapidly and eventually reach about 2.3 to one. Power generation in the depleted fuel would start at about 40 per cent that of natural uranium fuel and would rise to about 60 per cent at 800 MWD/ton and then would rise more slowly to approximately 68 per cent at 1600 MWD/ton exposure.

The tube outlet temperatures for the depleted charges would be low in proportion to the low tube power because flow rates would be kept the same as in natural uranium. Because of the low-water temperature, there will be very little corrosion of fuel jackets. Corrosion rates would be less than one-tenth the rates currently observed in average charges.

Performance of the nondepleted portion of the load would be approximately the same as that of a conventional load and would thus not adversely affect the cost of the irradiation. The reactors would be operated with bulk outlet water temperatures near the limiting value, 93 to 95 C. Maximum specific and tube powers would be 4 to 8 per cent above those of a normal load; this is similar to the H Reactor E-N load, which has performed well.

C. M. Heeb
Reactor Engineering Unit
RESEARCH AND ENGINEERING

F. W. Knight, Supervisor
Product Engineering
PRODUCTION FUELS

H. G. Spencer, Supervisor
Process Analysis Unit
RESEARCH AND ENGINEERING

DATE

FILMED

8/8/94

END