Gammasphere Software Development

Progress Report

Department of Physics and Astronomy
Mississippi State University
Mississippi State, Mississippi 39762

Prepared for the U.S. Department of Energy
Under Contract Number DE-FG05-92ER40726

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

RECEIVED

MAY 14 1993

OSTI

Gammasphere Software Development

Progress Report

**Department of Physics and Astronomy
Mississippi State University
Mississippi State, Mississippi 39762**

**Prepared for the U.S. Department of Energy
Under Contract Number DE-FG05-92ER40726**

Gammasphere Software Development

**Rodney B. Piercey
Associate Professor of Physics
Mississippi State University**

March, 1993

Contents

Summary

I. Introduction

II. A UNIX-Based Computing Facility

III. Activities of the Software Working Group

IV. Development of a Universal Histogram Object

V. Software Development at LBL

VI. Software Development at ORNL

VII. Student Involvement

VIII. Other Work

IX. Publications, Abstracts and Presentations

X. Project Chronology

Appendix 1. UHO Header Files and Sample File Dump

Appendix 2. Preliminary UPAK Test Results

Summary

This report describes the activities of the nuclear physics group at Mississippi State University which were performed under contract DE-FG05-92ER40726 with the Department of Energy. Our nuclear physics continues to provide leadership for the Gammasphere Software Working Group (SWG). The SWG has had two full meetings and summaries of the presentations has been compiled. These summaries have been distributed to interested members of the Nuclear Physics Community. Three subcommittees have been organized to address specific issues. The subcommittee on a "standard format for histogram data" has met on several occasions and developed a draft format which was presented to the Gammasphere Users' Group and is being provided to interested parties. Other subcommittees have been organized to address issues of parallel computing and graphical user interfaces at Gammasphere. We are working closely with Robert Varner and Bill Milner at ORNL in adapting and testing the ORNL software package for use on SPARC-based workstations. Most of the display package is running at MSU, and we are investigating ways to enhance the OpenLook compatibility and user interface.

The SWG continues to interact closely with researchers at Lawrence Berkeley Laboratory (LBL). A Mississippi State University (MSU) graduate student, Mr. Pete Varmette, worked at LBL during the summer of 1992. Mr. Robert Belshe of LBL has agreed to sit on the research committee to review Mr. Varmette's masters thesis. The next full meeting of the SWG will be held at LBL in May or June, 1993.

Graduate, undergraduate and high school students have all participated in the Gammasphere Software project at MSU. Two graduate students have been partially funded by the project and an undergraduate is currently doing a special project. A very exciting element of our research effort is the involvement of high school students at the Mississippi School of Math and Science. Our research program provides challenge and a unique experience to the student who are participating.

The final two sections of this report list the abstracts, publications and presentations which resulted from our research and a short chronology of relevant events. Also included with this report please find three additional documents:

- (1) Summary and Presentations of the First Gammasphere Software Issues Workshop
- (2) Summary and Presentations of the Second Gammasphere Software Issues Workshop
- (3) Draft Specification of the Universal Histogram Object Data Format

I. Introduction

In this, the first year of our contract, we have made substantial progress in several areas by organizing the Gammasphere Software Working Group, establishing a nuclear computing facility at Mississippi State University, participating in software development at Lawrence Berkeley Laboratory, developing a common data file format and working with scientists to adapt the ORNL UPAK software to run at Gammasphere. Much of the work has been reported at various meetings and conferences.

In our role as Software Working Group (SWG) chair, we have organized two major meetings and have met with individual committee members on an as needed basis. Three subcommittee have been formed to address specific issues. Progress has been reported at the Gammasphere Users' Group Meeting where input was solicited.

We have been working with scientists at ORNL to adapt software to run at Gammasphere on a distributed system of SPARC-based, SUN workstations. We have managed to make a large portion of the UPAK software work on our SPARC-based machines and are now characterizing compatibility issues. We are also investigating methods to enhance the user interface by adding an OpenLook control window in a non intrusive way.

One of our graduate students, Mr. Pete Varmette, spent the summer of 1992 at Lawrence Berkeley Laboratory working with LBL researchers to develop the liquid nitrogen fill system for the Gammasphere. He is now writing his masters thesis on Gammasphere software development and will continue in our group as a Ph.D. student.

II. A UNIX-Based Computing Facility

With the support of the Department of Physics and Astronomy and the College of Arts and Science at Mississippi State University, the nuclear physics group has developed a UNIX-based computing facility. The facility is housed in a dedicated room in the physics building and consists of two SPARC stations, an additional external disk drive, an 8mm tape unit, a CD-ROM drive and a laser printer. The facility is connected to the campus network which provides access to the Mississippi State University NSF Engineering Research Center of Excellence (ERC) and the Nuclear Physics community.

The Mississippi State University ERC has provided resources and expertise in the areas of application development, parallel programming and data visualization. With over a 100 SUN workstations and numerous other UNIX-based computer systems from HP, IBM and SGI, the ERC represents one of the best equipped computer resources in the southeast. The ERC hosted our first Gammasphere Software Working Group meeting and provided several expert speakers.

In addition to providing general computing and project management resources, the new computing facility is being used to develop a standard format for histogram data (UHO) and as a test stand for the ORNL UPAK software. A library of routines is being developed to manipulate the UHO data format in the OpenLook windowing environment. The draft UHO format and the routine library are available to anyone who has an interest in Gammasphere software.

The new computer facility has also been the primary mechanism for the involvement of graduate, undergraduate and high school students in our research project. Access to the internet has been essential in coordinating our interaction with Software Working Group activities.

III. Activities of the Software Working Group

The Gammasphere Software Working Group (SWG) was established by the director of the Gammasphere project to "generate software that will be useful in Gammasphere operation, data acquisition, and/or data analysis and to interact with Gammasphere management to develop an effective interface for user access to and use of the Gammasphere computer facilities". The SWG currently has nine permanent members and a number of associate members. The committee has had two full meetings: one at Mississippi State University and another at the APS Nuclear Physics Division meeting in Santa Fe New Mexico. Three important subcommittees have been formed to address areas of interest. The subcommittee on Data Formats is developing a histogram file format to encourage data sharing and tool sharing. The subcommittee on Parallel Programming is tracing developments in distributed parallel systems which could impact the use of the Gammasphere computer system. The subcommittee on Graphical User Interface issues is aiding in the port of the ORNL software to a distributed SUN-based, OpenLook compatible package. The bound proceedings of both SWG meetings and the draft UHO specification is available from the SWG committee.

IV. Development of a Universal Histogram Object

One of the goals of the SWG was to encourage the nuclear physics community to contribute to the development of high quality software for the Gammasphere. The absence of a standard data format was clearly identified as one of the primary obstacles to sharing the software that already existed and the development of new software tools. To study this situation and to develop a data format that could serve the community the subcommittee for a histogram standard was formed. With the help of this committee and others in the nuclear physics community, we have developed a universal histogram object (UHO) that defines a file format and provides for an object oriented programming model. The UHO file format consists of a list of self describing records. Each record is identified by a tag and contains the record size. In addition to the data itself, these records specify such things as display characteristics, calibrations, annotations, regions, markers, sort conditions, etc. Records and record fields are provided to support graphical user interfaces and heterogeneous distributed systems. The UHO also supports event-by-event data acquisition by providing for "intelligent" histogram objects that can accept event record buffers and sort the events based on Condition and Region records.

"DATA"
"ERRS"
"DSPL"
"PARM"
"CALB"
"REGN"
"MARK"
"COND"
"ANOT"

The UHO file format provides for associated structures which support display and analysis

The UHO file is a list of self-identifying elements or records. Each record has a type and a size. This allows an application program to check for record types that it knows and skip those that it does not need. For example, an application tool to which analyzes data in "batch" mode may not need information about how to display the data. However, a plotting or drawing program would need this information. A block diagram of a UHO file are is shown in the figure above. The "DATA" record contains the actual histogram data as well as information on the byte order, word size and data lengths. The "DSPL" record contains the information required to draw the "counts" axis of the histogram. This includes the minimum and maximum values to display and symbol and color information. The "PARM" record includes similar information about the channel axes. There will usually be a "PARM" record for each of the dimensions of the histogram. "CALB" records provide calibration information for each of the channel axes. The "MARK" and "REGN" records define markers and regions in the histogram. There may be several of each of these in a UHO object. The "COND" record is a set of conditions or filters which regulate how blocks of events are sorted. A condition requires that a particular parameter set be contained in one or more histogram regions. The "ANOT" records are used to add anotations to any of the UHO records. Additional details are presented in the attached draft specification.

We are also developing a library of subroutines to aid in implementing the UHO model. The prototype library and an example application are available to interested parties. Several nuclear groups have indicated an interest in using the UHO as a data standard for their labs. Copies of the UHO draft are available from the SWG.

Abstract Submitted
for the Oak Ridge Meeting of The
American Physical Society
November 12-15, 1992
Meeting Date

Suggested title of session
in which paper should be placed
Instrumentation in Software

Physics and Astronomy
Classification Scheme
Number

A Universal Histogram Object For Nuclear Science. RODNEY B. PIERCEY, Mississippi State University; ROBERT BELSHE, Lawrence Berkeley Laboratory; RANDY MACLEOD, AECL; and ROBERT VARNER, Oak Ridge National Laboratory -- The histogram is the basic data product of most nuclear and high-energy research efforts. While data from user facilities must often be returned to member institutions for analysis and/or inclusion in reports and manuscripts, there is no single histogram file format that has been adopted for widespread use. The existence of many different histogram formats makes sharing data unnecessarily complex and time consuming. Translation of histogram data is generally the responsibility of individual researchers and often results in duplicated effort. A standard format would save many hours of research time and promote data sharing. The development of the GammaSphere facility software provides an opportunity to introduce a standard histogram architecture which could serve many users in the nuclear and high-energy community.

We are developing a universal histogram object (UHO) that defines a file format and suggests an object oriented behavior for the histogram data. While the UHO must enforce specific file formats, it is not meant to impose a specific implementation of its procedures and leaves room for an arbitrary graphical user interface (GUI) or window manager policy. The UHO file format consists of a list of self-identifying records which describe the data size, data formats plotting options, etc. A simple application to demonstrate the UHO is currently under development on a UNIX workstation.

- () Prefer Poster Session
(X) Prefer Standard Session
() No Preference

Submitted by

Signature of APS Member

Rodney B. Piercey

Same name typewritten

Mississippi State University

Address

P.O. Drawer 5167
Mississippi State Univ.
Miss. State, MS 39762

V. Software Development at LBL

Abstract Submitted
for the Oak Ridge Meeting of The
American Physical Society
November 12-15, 1992
Meeting Date

Suggested title of session
in which paper should be placed
Instrumentation in Software

Physics and Astronomy
Classification Scheme
Number

Liquid Nitrogen Control System. R.A. BELSHE, Lawrence Berkeley
Laboratory; P.G. VARMETTE, Mississippi State University -- The
GammaSphere project is well underway with early implementation set to begin
early in 1993. An automated liquid nitrogen system has been developed to
control the cooling of the 110 Germanium detectors that comprise the sphere.
The user interface to this system is a commercial XWindows display package.

The control system is a combination of hardware and software which will
provide flexibility and most important of all reliability. The control program
consists of five state machines. The state machines run independently of each
other, not being permitted to change the state of another machine. However,
the state machines are allowed to view the states of the other state machines.
This method reduces the likelihood of undetected programming errors, and
makes source code maintenance relatively easy.

- () Prefer Poster Session
(X) Prefer Standard Session
() No Preference

Submitted by

Rodney B. Piercey
Signature of APS Member

Rodney B. Piercey

Same name typewritten

Mississippi State University

Address

P.O. Drawer 5167
Mississippi State Univ.
Miss. State, MS 39762

VI. Software Development at ORNL

Oak Ridge National Laboratory has agreed to provide a histogramming software package (UPAK) to the Gammasphere facility. In addition to the job of porting the software elements to the SPARC-based machines, it has been pointed out that some effort should be expended in developing a full graphical user interface for UPAK. A subcommittee has been formed to identify the relevant issues and to suggest enhancements where they could significantly improve the usability of the software.

We have been testing the compatibility of the ported software package and are providing the test results to ORNL. The most recent test summary is included as an appendix.

VII. Student Involvement

There are currently five graduate students working in the nuclear physics group at Mississippi State University. Two of these students are working on Gammasphere software issues. Mr. Pete Varmette spent last summer working at LBL with Gammasphere researchers in developing the automated liquid nitrogen fill system for Gammasphere. He is now involved in the development of data formats and testing of the UPAK software from ORNL. Mr. Varmette will finish his masters degree in may of 1993 and will continue with our group a Ph.D. student. Ms Anita Trevida is working primarily in the area of UPAK testing. She is also part time at the Mississippi State University Engineering Research Center and acts as our liaison there. The other three graduate students, Mr. Morris Fields, Mr. Yan Yuan and Mr. Hazem Tliemat are working in nuclear spectroscopy and relativistic hydrodynamics.

Mr. Larry G. Gariepy is an undergraduate student who is doing a special project in our group. His project involves the study of message passing techniques in Solaris, the SUN operating system. Message passing techniques may be used to enhance the interoperability of the UPAK software from ORNL.

Two high school students from the Mississippi School for Math and Science, Jason Keller and Arun Sridharan are, are also working with our group. They will spend one afternoon per week working at MSU to develop UNIX techniques for process control. The work is important for understanding how software processes may be controlled in a multitasking environment and will provide the students with unique research experience.

Our graduate students also develop the nuclear experiments for the undergraduate advanced laboratory in the physics department. This year four undergraduates used nuclear instrumentation to perform a gamma-ray absorption experiment.

VIII. Other Work

Performance of a Three-Element Thin Film Detector

Z. Milosevich, M. L. Muga, R. L. Coldwell, G. J. Bamford

University of Florida

Gainesville, FL 32611

P. S. Haskins

Institute for Space Science Technology

Gainesville, FL 32601

R. B. Piercey

Mississippi State University

Starkeville, MS

Abstract

A nuclear charged particle detector has been designed and fabricated at the University of Florida for use in identifying the nuclear charge Z and mass number A of low energy (~ 1 MeV/amu) heavy mass ions. The detector consists of a stack of three sequential thin film detectors (made from NE-102A plastic scintillator) for three successive measurements of the specific luminescence $\Delta L/\Delta x$ and velocity of a transiting ion and a terminal surface barrier detector for measuring the ion residual energy. This detector assembly was tested by measuring its response to various isotopes of germanium and selenium ions which were accelerated at selected energies between 53 MeV and 169 MeV and then scattered from a thin gold target foil. The tests were performed to obtain quantitative information on the ability of the detector system to identify the nuclear Z of an impinging ion and to test the advantage of having three successive measurements of $\Delta L/\Delta x$ from three sequential and

Charge State Characteristics of Ge and Se Ions
Involved in Small Impact Parameter Collisions with a Gold Target

Z. Milosevich, M. L. Muga, R. L. Coldwell, G. J. Bamford

University of Florida

Gainesville, FL 32611

P. S. Haskins

Institute for Space Science Technology

Gainesville, FL 32601

R. B. Piercey

Mississippi State University

Starkeville, MS

Abstract

Information concerning the charge states of ions that have passed through various materials is of interest due to the application such information has to heavy ion accelerators. Data have been compiled from numerous sources that list equilibrium charge states of ions at various energies and for various targets. This information however has been limited to ions that have not been deflected from their original path after collision with target atoms. Information regarding the charge states of ions that have been involved in small impact parameter collisions with a target atom and thus scattered at large angles has been scarce. In the following experiment, a three-element thin film detector/surface barrier detector (3TFD-SBD) has been used to measure the specific luminescence of various scattered ions

Coulomb Excitation Studies to High Spin in ^{248}Cm

R. B. Piercey

Physics Department, Vanderbilt University, Nashville, Tennessee 37235
Gesellschaft für Schwerionenforschung, Darmstadt, W. Germany and
Mississippi State University, Mississippi State, MS 39762

C. Michel^a, E. Grosse, H. Emling, D. Schwalm^b, H. J. Wollersheim
Gesellschaft für Schwerionenforschung, Darmstadt, W. Germany

J. H. Hamilton, A. V. Ramayya

Physics Department, Vanderbilt University, Nashville, TN 37235 and
Institute für Theoretische Physik, Universität Frankfurt,
6000 Frankfurt/M, W. Germany

N. Trautmann

Institute für Kernchemie, Universität Mainz, 6500 Mainz, W. Germany

ABSTRACT

Coulomb excitation studies of ^{248}Cm were carried out with 5.3 MeV/u ^{208}Pb projectiles from the GSI UNILAC. A rotational band built on the ground state of ^{248}Cm has been identified to spin 28^+ and a tentative 30^+ assignment has been made. The angular dependence of the yields for transitions de-exciting levels from spin 28^+ to 6^+ have been measured and used to support the spin and parity assignments. An anomalous level spacing is observed above 22^+ and is interpreted as the crossing of a rotation-aligned band at high spin. The E2-matrix elements connecting the states of the ground-state band up to 28^+ have been determined by comparing the experimental yields to calculations based on semi-classical Coulomb excitation with subsequent gamma-ray decay. The effect of the excitation of other collective states is also considered. No strong deviation of the matrix elements from rigid-rotor behavior has been seen.

a) Present address: Universite Louvain-La-Neuve, Belgium
b) Present address: Universität Heidelberg, W. Germany

IX. Publications, Abstracts and Presentations

Publications

"Test and application of a Symmetrical Four-Detector Compton polarimeter for low temperature nuclear orientation and in-beam spectroscopy," J.K. Deng, J.H. Hamilton, A.V. Ramayya, J. Rikovska, N.J. Stone, W.L. Croft, R.B. Piercey, J.C. Morgan, P.F. Mantica, Jr., Nucl. Instr. and Meth. in Phys. Res., **A317**, pp. 242-250. (1992).

"Test of a Symmetrical Four-Detector Compton Polarimeter Using Low Temperature Nuclear Orientation," J.K. Deng, J.H. Hamilton, A.V. Ramayya, J. Rikovska, N.J. Stone, W.L. Croft, R.B. Piercey, J.C. Morgan, P.F. Mantica, Jr., Hyperfine Interactions, **75**, pp. 519-524 (1992).

"Coulomb Excitation Studies to High Spin In ^{248}Cm ," R.B. Piercey, C. Michel, H. Emling, E. Grosse, D. Schwalm, J.H. Hamilton, A.V. Ramayya and N. Trautmann, (Accepted for publication in J. Phys. G.).

"Off-Line Nuclear Orientation Studies of ^{96}Mo ," K. Butler-Moore, A.V. Ramayya, J.H. Hamilton, J.K. Deng, J. Kormicki, W. Ma, P.F. Mantica, Jr., H.K. Carter, R.B. Piercey, J.C. Morgan, W.D. Hamilton (To be published).

"Charge State Characteristics of Ge and Se Ions Involved in Small Impact Parameter Collisions with a Gold Target," Z. Milosevich, M.L. Muga, R.L. Coldwell, G.J. Bamford, P.S. Haskins and R.B. Piercey, (In preparation).

"Performance of a Three-Element Thin Film Detector," Z. Milosevich, M.L. Muga, R.L. Coldwell, G.J. Bamford, P.S. Haskins and R.B. Piercey, (In preparation).

Abstracts

"A Universal Histogram for Nuclear Science," R.B. Piercey, R.A. Belshe, R. MacLeod, and R. Varner, Bull. Am. Phys. Soc. **37**, p. 1678, (1992).

"Covariant, Grid-Based Numerical Algorithms for Nuclear Hydrodynamics," R.B. Piercey, B.K. Soni, H. Tleimat and Anita Trevedi (Submitted to the Mississippi State Annual Conference on Differential Equations & Computational Simulations, Mississippi State University, Mississippi State, MS, March 19, 1993).

Seminars

"Gammasphere Data Objects," Institute for Nuclear Physics, Kiev, Ukraine, June 30.

"Gammasphere, the National Gamma-Ray Facility," University of Alabama, Tuscaloosa, AL, February 10, 1993.

X. Project Chronology

June-July (Mississippi State University)

During the months of June and July, we received our new SUN workstations to be used in developing Gammasphere software.

June 3-5 (Mississippi State University)

In his role as chairman of the Gammasphere Software Working Group, Dr. Piercey organized a workshop on "Gammasphere Software Issues". The workshop was held at the MSU Engineering Research Center, June 3, 4 and 5. In addition to the MSU (Physics and ERC) participants, the workshop was attended by researchers from the major heavy-ion laboratories in the US and Canada. The Universal Histogram Object (UHO) was proposed for Gammasphere.

June 14 - July 2 (Kiev, Ukraine)

Dr. Piercey attended the International Symposium on Nuclear Physics sponsored by the Institute for Nuclear Research in the Ukrainian Academy of Sciences. Dr. Piercey presented a paper: "Gammasphere Data Objects".

July 28 - August 2 (San Francisco CA)

Dr. Piercey met with Bob Belshe and Pete Varmette to discuss the Gammasphere software project and Mr. Varmette's thesis. Bob Belshe agreed to be on Varmette's masters committee.

October 1-10 (Oak Ridge, TN)

Dr. Piercey held a Gammasphere Histogram File Format subcommittee meeting with Robert Varner. Dr. Piercey also attended the MSU sponsored, Radioactive Beams (ISL) Conference, the UNISOR executive council meeting and the RIB experiment apparatus meeting.

October 14-17, 1992 (Sante Fe, NM)

Dr. Piercey chaired SWG meeting and presented the UHO to the GammaSphere Users Group Meeting. He also attended the APS, Nuc. Div., & SWG workshop.

October 26-31, 1992 (Orlando, FL)

Dr. Piercey attended "Nuclear Science Symposium".

November 4-6, 1992 (Raleigh, NC)

Dr. Piercey attended SURA meeting.

November 11-14, 1992 (Oak Ridge TN)

Dr. Piercey attended Southeastern Section, American Physical Society. Two grad students (Mr. Varmette and Mr. Yan) also attended. Dr. Piercey presented a paper on the "Universal Histogram Object for Nuclear Science". Mr. Varmette presented a paper on his work at LBL on the liquid nitrogen fill system for Gammasphere. Dr. Piercey chaired one of the conference sessions.

November 16-22, 1992 (Sanibel Island, FL)

Dr. Piercey attended the "Nuclear Physics in Our Times" conference, chaired one session and spoke at the banquet as one of the invited roasters.

February 10, 1993 (Tuscaloosa, AL)

Dr. Piercey presented a seminar on Gammasphere to the physics faculty at University of Alabama.

Appendix 1. UHO Header Files and Sample File Dump

```

/*
 *      uho.h  Universal Histogram Object header file
 *
 */

#include <stdio.h>
#include <time.h>
#include <math.h>
#include <X11/Xlib.h>

/*=====
 *      uho tags for the various uho record types
 */
#define mData_tag    (long)'DATA'
#define mDSPL_tag    (long)'DSPL'
#define mPARM_tag    (long)'PARM'
#define mCALB_tag    (long)'CALB'
#define mCOND_tag    (long)'COND'
#define mMARK_tag    (long)'MARK'
#define mREGN_tag    (long)'REGN'
#define mFRAM_tag    (long)'FRAM'
#define mANOT_tag    (long)'ANOT'

#define mTEXT_tag    (long)'TEXT'

/*=====
 *      uho symbol types for plotting the data
 */
#define cHISTOGRAM    1
#define cDOT          2
#define cLINE         3
#define cSQUARE       4
#define cCIRCLE       5
#define cTRIANGLE     6

/*=====
 *      uho verticle modes for plotting 1D data
 */
#define cLINEAR       1
#define cLOG           2

/*=====
 *      uho viewing modes for plotting 2D data
 */
#define cSCATTER      1
#define cSURFACE      2
#define cCONTOUR      1

/*=====
 *      uho perspective modes for viewinf 2D data in surface mode
 */
#define cHUMAN        1
#define cTELESCOPIC   2
#define cWIDEANGLE    3

/*=====
 *      uho drawing styles
 */
#define cNORMAL        1
#define cPRINTING      2
#define cHIRESSTYLE    3
#define cCOVERPRINTSTYLE 4
#define cOVERLAYSTYLE  5
#define cTILEDSTYLE    6

/*=====
 *      uho marker styles

```

```

*/
#define CDATAANCHOR      1
#define CWINDANCHOR      2

/*=====
*      uho misc constants
*/
#define true      1
#define false     0

#define cWinMinHeight  30          /* minimum window height for drawing */
#define cWinMinwidth   70          /* minimum window width for drawing */

#define cCURS_SLOP     3           /*how close to click to drag a cursor */

#define cMAXNUMTICKS    500        /* maximum number of ticks on any axis */

#define cVMAJINTVLPIX   70         /* defalult pix width for value maj intvl */
#define cPMAJINTVLPIX   50         /* defalult pix width for value axis maj intvl */
#define cMAX_LABEL_LENGTH 64       /* maximum length of an axis label */
/*=====
*      uho types and structures
*/
typedef long uhoTag;

typedef struct rgbColor {
    short    red_index;
    short    green_index;
    short    blue_index;
} rgbColor;

typedef struct x_refs {
    void      *display;
    void      *frame;
    void      *xwindow;
    void      *canvas;
    void      *xvwindow;
    void      *the_gc;
} x_refs;
/*=====
*      uho DrawFacts holds all the information required to draw data into
*      a window.  It is calculated often so it should be as small as possible.
*/
typedef struct DrawFacts {
    short    rect_bot;
    short    rect_top;
    short    start_x_pix;
    short    start_hor_chan;
    short    start_vert_chan;
    short    vert_min_pix;          /* old VMinPix */
    short    del_hor_pixs;          /* old DelHPix */
    short    del_vert_pixs;        /* old DelVPix */
    long     val_min;              /* old DelZ */
    long     val_max;              /* old DelZ */
    long     del_vals;             /* old DelZ */
    short    del_hor_chans;        /* old DelX */
    double   hor_pix_per_chan;     /* old HperX */
    double   ver_pix_per_val;
    double   log_min_val;          /*log of the min val */
    /* for 2D plots */
    short    del_vert_chans;
    double   ver_pix_per_chan;
} DrawFacts;
/*=====

```



```

*      The uho_TEXT structure is normally not allocated in memory.  It is included here
*      in order to specify the file format.
*/
typedef struct uho_TEXT {
    uhoTag      rec_tag;          /* 'TEXT' */
    char        data[1];         /* xlength ylength, data1, data2... */
} uho_TEXT;

/*=====
*      The uho_DATA structure holds the data in memory and is copied to disk
*      when a histogram is saved as a file.  The structure is extended to hold
*      the lengtharray for each of the dimensions of the histogram and the
*      data as well.  The data[1] field contains the first length value (the
*      only one for 1D histogram).  For a 1D histogram and a word_size of 4
*      data[2] would contain the contents of channel 1.
*/
typedef struct uho_DATA {
    uhoTag      rec_tag;          /* 'DATA' */
    size_t      rec_size;        /* size in bytes of this record */
    long        rec_ver;         /* version of structure (1.0B) */
    long        rec_ID;          /* unique ID of record */
    long        dt_usr_data;      /* the user can store anything here */
    long        dt_byte_order;    /* byte order determined 0x01020304 */
    time_t      dt_creat_time;    /* the creation time and date */
    long        dt_rank;         /* identifiys the data rank: 1D, 2D,... */
    long        dt_word_size;     /* byte, word, long, etc */
    long        dt_format;        /* int, float, etc */
    long        dt_compress;      /* how data is compressed */
    long        data[1];         /* length array(longs), data follows */
} uho_DATA;

/*=====
*      The uho_DSPL record holds additional drawing control information and
*      the value axes descriptors.  There should only be one uho_DSPL record
*      even for higher dimensional data.
*/
typedef struct uho_DSPL {
    uhoTag      rec_tag;          /* 'DSPL' */
    size_t      rec_size;        /* size in bytes of this record */
    long        rec_ver;         /* version of structure (1.0B) */
    long        rec_ID;          /* unique ID of record */
    long        dp_usr_data;      /* the user can store anything here */
    long        dp_owner_ID;      /* unique ID of record */
    XRectangle   dp_window_rect;  /* how big and where to draw the window */
    XRectangle   dp_display_rect; /* where to draw the histogram */
    struct rgbColor dp_fore_color; /* The Color for the window background */
    struct rgbColor dp_back_color; /* The Color for the window background */
    long        dp_plot_symbol;   /* histogram,Dots,Squares,Lines */
    long        dp_symbol_size;   /* how big to draw symbol */
    long        dp_symbol_fill;   /* to fill the Plot */
    long        dp_remove_lines;  /* remove hidden lines */
    long        dp_val_min;       /* smallest value displayed */
    long        dp_val_max;       /* largest value displayed */
    long        dp_vert_mode;     /* cLINEAR or cLOG */
    long        dp_view_persp;    /* cHUMAN, cTELESCOPIC, ... */
    long        dp_view_type;     /* cSURFACE, cSCATTER... */
    long        dp_maj_intvl;     /* major interval for the value axis */
    long        dp_min_intvl;     /* minor interval for the value axis */
    long        dp_font_name[128]; /* specifies font for the axis */
    long        dp_show_grid;     /* says whether to draw a grid */
    long        dp_auto_axes;     /* automatically adjust axes */
    long        dp_auto_scale;    /* automatically adjust vertical scale */
    long        dp_draw_axis;     /* says whether to draw the value axis */
    char        dp_axis_label[cMAX_LABEL_LENGTH]; /* label for value axis */
} uho_DSPL;
/*=====

```

```

*
*   The uho_PARM record holds the descriptive information for each
*   dimension of the data array.  For example, if the rank is 2, there can
*   be up to 2 uho_PARM records.  The uho_PARM record provides a next_PARM
*   field to enable link-list storage in memory.
*/
typedef struct uho_PARM {
    uhoTag      rec_tag;          /* 'PARM' */
    size_t      rec_size;         /* size in bytes of this record */
    long        rec_vers;         /* version of structure (1.0B) */
    long        rec_ID;           /* unique ID of record */
    long        pm_usr_data;       /* the user can store anything here */
    long        pm_owner_ID;       /* belongs to this hist dimension */
    long        pm_parm_num;       /* belongs to this hist dimension */
    void        *next_PARM;        /* points to the next uhoPARM record */
    long        pm_sort_parm;      /* which event parm to sort */
    float       pm_sort_gain;      /* gain to apply during sorting */
    long        pm_sort_offset;    /* offset to apply during sorting */
    long        pm_next_chan;      /* place holder for sorting strip charts */
    long        pm_disp_min;       /* minimum channel currently displayed */
    long        pm_disp_max;       /* maximum channel currently displayed */
    long        pm_curs_min;       /* position of the lower cursor */
    long        pm_curs_max;       /* position of the upper cursor */
    float       pm_axis_rot;       /* amount of rotation about this axis */
    long        pm_maj_intvl;      /* major interval for drawing axis */
    long        pm_min_intvl;      /* minor interval for drawing axis */
    long        pm_draw_axis;      /* flag says whether to draw the axes */
    char        pm_axis_label[cMAX_LABEL_LENGTH]; /* axis label */
} uho_PARM;

/*=====
*
*   The uho_CALB record holds the optional calibration data for each
*   dimension.  For example, if the rank is 2, there can be up to 2
*   uho_CALB records.  The uho_CALB record provides a next_CALB
*   field to enable link-list storage in memory.
*/
typedef struct uho_CALB {
    uhoTag      rec_tag;          /* 'CALB' */
    size_t      rec_size;         /* size in bytes of this record */
    long        rec_vers;         /* version of structure (1.0B) */
    long        rec_ID;           /* unique ID of record */
    long        ca_owner_ID;       /* unique ID of record */
    long        ca_parm_num;       /* belongs to this hist dimension */
    void        *next_CALIB;       /* points to the next uhoCALB record */
    long        ca_use_calib;      /* says to use the calibration */
    float       ca_calib_coef[1]; /* calibration coefficient */
    char        ca_calib_units[cMAX_LABEL_LENGTH]; /* units for calibration */
} uho_CALB;

/*=====
*
*   The uho_REGN record holds ...
*/
typedef struct uho_REGN {
    uhoTag      rec_tag;          /* 'REGN' */
    size_t      rec_size;         /* size in bytes of this record */
    long        rec_vers;         /* version of structure (1.0B) */
    long        rec_ID;           /* unique ID of record */
    long        rg_usr_data;       /* the user can store anything here */
    long        rg_owner_ID;       /* unique ID of record */
    void        *next_REGN;        /* points to the next uhoREGN record */
    long        rg_flags;          /* visible, selected, etc */
    long        rg_rank;           /* says what kind of region */
    long        rg_color;          /* marker color */
    long        rg_font_num;       /* font for region text */
    long        rg_font_style;     /* font style for region text */
    long        rg_font_size;      /* font size for region text */
    long        rg_font_just;      /* font justification for region text */
    XRectangle  rg_rect;           /* enclosing rect for the region */
    long        rg_num_pts;        /* num of points in polygon */
}

```

```

        XPoint          rgn_point[1]; /* list of points defines a ploygon */
        char            rg_name[cMAX_LABEL_LENGTH]; /* name of region */
    } uho_REGN;
/*=====
*      The uho_COND record holds the description of the condition that is to be applied
*      to a particular ntuple. The fundamental test is whether the ntuple specified
*      by the cond_parm[i] ntuple of rank lies in the region specified by rg_name.
*/
typedef struct uho_COND {
    uhoTag          rec_tag;          /* 'COND' */
    size_t          rec_size;         /* size in bytes of this record */
    long            rec_vers;         /* version of structure (1.0B) */
    long            rec_ID;           /* unique ID of record */
    long            cd_usr_data;       /* the user can store anything here */
    long            cd_owner_ID;       /* unique ID of record */
    void            *next_COND;        /* points to the next uhoCOND record */
    long            cd_rank;           /* rank of n-tuple test */
    long            cd_mask;           /* mask for significant bits */
    long            cd_parm_1;         /* parm 1 to test */
    long            cd_parm_2;         /* parm 2 to test */
    long            cd_num_pts;        /* number of points in polygon */
    long            cd_parm[1];        /* ntuple for testing */
    char            cd_name[cMAX_LABEL_LENGTH]; /* name of region */
} uho_COND;
/*=====
*      The uho_MARK record holds .
*/
typedef struct uho_MARK {
    uhoTag          rec_tag;          /* 'MARK' */
    size_t          rec_size;         /* size in bytes of this record */
    long            rec_vers;         /* version of structure (1.0B) */
    long            rec_ID;           /* unique ID of record */
    long            mk_usr_data;       /* the user can store anything here */
    long            mk_owner_ID;       /* unique ID of record */
    void            *next_MARK;        /* points to the next uhoMARK record */
    long            mk_flags;          /* visible, selected, showmode, ... */
    long            mk_anchor;         /* says stick to data or window */
    long            mk_border;         /* specifies border style */
    long            mk_contents;       /* specifies what to show */
    long            mk_x_start;        /* chan or x pix location of label */
    long            mk_y_start;        /* val or y pix location of label */
    long            mk_x_stop;         /* chan or x pix location of line */
    long            mk_y_stop;         /* val or y pix location of line */
    long            mk_color;          /* marker color */
    long            mk_font_num;        /* font for marker text */
    long            mk_font_style;     /* font style for marker text */
    long            mk_font_size;      /* font size for marker text */
    long            mk_font_just;      /* font justification for marker text */
    char            mk_text[cMAX_LABEL_LENGTH]; /* name */
} uho_MARK;
/*=====
*      The uho_ANOT record holds notes and comments or text information of any kind .
*/
typedef struct uho_ANOT {
    uhoTag          rec_tag;          /* 'ANOT' */
    size_t          rec_size;         /* size in bytes of this record */
    long            rec_vers;         /* version of structure (1.0B) */
    long            rec_ID;           /* unique ID of record */
    long            an_usr_data;       /* the user can store anything here */
    long            an_owner_ID;       /* unique ID of record */
    void            *next_ANOT;        /* points to the next uho_ANOT record */
    char            an_font_name[128]; /* specifies font for the anotation */
    char            an_text[1];        /* anotation text starts here */
} uho_ANOT;
/*=====
*      The Hist record is used in memory. It is not part of the file structure.

```

```

*      There are pointers to each of the uho structures.  There is also a pointer
*      to the external references which the programmer may modify for a particular
*      implementation.
*/
typedef struct Hist {
    uho_DATA      *DATA_ptr;      /* points to the uho_DATA struct */
    uho_DSPL      *DSPL_ptr;      /* points to the uho_DSPL struct */
    uho_PARM      *PARM_ptr;      /* points to the first uho_PARM struct */
    uho_CALB      *CALB_ptr;      /* points to the first uho_PCALB struct */
    uho_REGN      *REGN_ptr;      /* points to the first uho_REGN struct */
    uho_COND      *COND_ptr;      /* points to the first uho_COND struct */
    uho_MARK      *MARK_ptr;      /* points to the first uho_MARK struct */
    uho_ANOT      *ANOT_ptr;      /* points to the first uho_ANOT struct */
    x_refs        *xrefs_ptr;     /* user may store axillary info here */
} Hist;

```

/*Other Optional structures might include...*/

```

/*=====
*      The uho_ANIM record holds .
*/
typedef struct uho_ANIM {
    uhoTag      rec_tag;          /* 'ANIM' */
    long        rec_size;         /* size in bytes of this record */
    long        version;          /* version of structure (1.0B) */
    void        *next_ANIM;       /* points to the next uhoANIM record */
    XRectangle   an_rect;         /* enclosing rect for animation */
    short       an_frame;         /* current frame */
    short       an_speed;         /* frame speed */
    char        an_loop;          /* says whether to loop */
    long        Reserved1;        /* reserved for future use */
    long        Reserved2;        /* reserved for future use */
    long        Reserved3;        /* reserved for future use */
    long        Reserved4;        /* reserved for future use */
} uho_ANIM;
/*=====
*      The uho_FRAM record holds ...
*/
typedef struct uho_FRAM {
    uhoTag      rec_tag;          /* 'FRAM' */
    long        rec_size;         /* size in bytes of this record */
    long        version;          /* version of structure (1.0B) */
    void        *next_FRAM;       /* points to the next uhoFRAM record */
    char        fr_parent[cMAX_LABEL_LENGTH]; /* name of source hist */
    XRectangle   fr_rect;         /* enclosing rect for frame */
    long        Reserved1;        /* reserved for future use */
    long        Reserved2;        /* reserved for future use */
    long        Reserved3;        /* reserved for future use */
    long        Reserved4;        /* reserved for future use */
    char        fr_data[1];       /* pix map starts here */
} uho_FRAM;

```

```

0000000 4441 5441 0000 802c 0000 0000 0000 0000
0000020 0000 0000 0000 0000 0000 0000 0000 0001
0000040 0000 0004 0000 0000 0000 0000 0000 1fff
0000060 0018 37b3 0000 0006 0000 0001 0000 0022
0000100 0000 0071 0000 010b 0000 048e 0000 6074
0000120 0001 663f 0001 6b19 0001 669f 0001 694e
0000140 0001 648f 0001 6645 0001 65ba 0001 6271
0000160 0001 609d 0001 5e83 0001 5f12 0001 5ce1

```

```

.
.
.

```

```

0100000 0000 0149 0000 016f 0000 0153 0000 0155
0100020 0000 0168 0000 0157 0000 0157 0000 015c
0100040 0000 0159 0000 0159 0000 0162 4453 504c
0100060 0000 02b0 0000 0000 0000 0000 0000 0000
0100100 0000 0000 0000 0000 0000 0000 0000 0000
0100120 0000 0000 0000 0000 0000 00ff 00ff 00ff
0100140 0000 0001 0000 0000 0000 0000 0000 0001
0100160 0000 0001 0018 37b3 0000 0001 0000 0001
0100200 0000 0002 0000 0064 0000 000a 0000 0000
0100220 0000 0000 0000 0000 0000 0000 0000 0000

```

```

*
```

```

0101220 0000 0000 0000 0001 0000 0000 7661 6c75
0101240 6500 0000 0000 0000 0000 0000 0000 0000
0101260 0000 0000 0000 0000 0000 0000 0000 0000

```

```

*
```

```

0101320 0000 0000 0000 0000 0000 0000 5041 524d
0101340 0000 0090 0000 0000 0000 0000 0000 0000
0101360 0000 0000 0000 0001 0000 0000 0000 0000
0101400 3f80 0000 0000 0000 0000 0000 0000 0000
0101420 0000 1ffe 0000 0096 0000 1f68 0000 0000
0101440 0000 03e8 0000 00c8 0000 0000 7061 7261
0101460 6d00 0000 0000 0000 0000 0000 0000 0000
0101500 0000 0000 0000 0000 0000 0000 0000 0000

```

```

*
```

```

0101554

```

Appendix 2. Preliminary UPAK Test Results

Damm Commands

FILE/DEVICE ASSIGNMENT SYNTAX

IN FIL.EXT	Open N-file (EXT = SPK or HIS)	y
OU FIL.EXT	Open O-file (EXT = SPK or HIS) - OUTPUT for SPK only	y
OU FIL.SPKNEW	Create and open O-file (SPK-file for output)	y
QF FIL.EXT	Open Q-file (EXT = SPK or HIS) - for display only	y
RF FIL.EXT	Open R-file (EXT = SPK or HIS) - for display only	y
SF FIL.EXT	Open S-file (EXT = SPK or HIS) - for display only	y
BAN FIL	Open FIL.BAN for store recall proj etc	y
BAN FILNEW	Create & open FIL.BAN for store recall etc	y
	(Type: HELP VFN for how to specify variable FILENAMES)	y
CLO F	Closes F-file (where F = N O P Q R S or BAN)	y
DFIL	Displays data files currently open	y
CMD CON:	Set CMD-input to be from VDT	y
CMD FIL	Set CMD-input to be from FIL.CMD & process	y
LON/LOF	Turn Log-output (to LU7) ON/OFF (default = OFF)	y

FOR SCREEN SETUP COMMANDS

FIGI	Set screen configuration library to default	y
FIGF FILNAM	Read screen configuration library from FILNAM	y
FIG N	Set current screen configuration to type-N	y
DLAF MS	Set FIG-delay to MS milliseconds (default=1000)	y
DLAD MS	Set Display-delay to MS milliseconds (default=500)	y
WIN ID	Set subsequent displays to be in window-ID (dflt=1)	y
AXON ID	Enable the drawing of axis for window-ID (dflt)	y
AXOF ID	Disable the drawing of axis for window-ID	y
CMAF	Set color map to default ("takes" after next FIG)	y
CMAF FILNAM	Set color map from FILNAM ("takes" after next FIG)	y
REVV	Reverse all color specs ("takes" after next FIG)	y
DLNS N	Set # disp-lines = N - for HELP DDIR & DSUM	y
CURT LIVE	Set full-wind cursor to track mouse LIVE (default)	y
CURT X	New full-wind cursor generated via mouse-click or key	y
	The CURT command takes effect only after next FIG	y
SSI	Set screen to initial - erase all graphic windows	y

SCREEN CONFIGURATION DIAGRAMS

EXPLANATION OF "VARIABLES IN FILE NAMES",
One symbol (integer variable) may be incorporated in a FILENAME
specification as the following examples illustrate:
.....
SYM=3
OU FIL "SYM".SPKNEW ,Creates and opens FIL3.SPK
.....
I=0
LOOP 3
I=I+1
IN FIL "I".SPK ,Opens (in succession) FIL1.SPK FIL2.SPK
FIL3.SPK
.
.
ENDLOOP
.....

LOOP EXECUTION AND SYMBOL DEFINITION

Commands related to LOOP execution and SYMBOL definition

SYM = EXPRESSION - Define symbol (SYM) up to 100 symbols supported

- symbols M N O P Q R S are reserved
- expression syntax is same as in CHIL
- no imbedded blanks are allowed in expressions
- symbols may contain up to 4 characters (5-8 ignored)

DSYM , Displays list of currently defined symbols & values,

LOOP N , Starts LOOP (executed N-times) N=SYM or CONST,

CMD , Nesting supported ,

CMD , # lines between 1st LOOP & matching ENDL = 100,

ENDL , Defines end-of-loop ,

KILL (entered before ENDL) ,kills LOOP,

Ctrl/C , aborts loop-in-progress,

, opening of CMD-file within a LOOP not allowed,

FOR DIRECTORY DISPLAY CMDS

DIR	Display Input file directory on VDT	y
DIR N	Display Input file directory on VDT	y
DIR O	Display Output file directory on VDT	y
DIR P	Display P-file directory on VDT	y
DIR Q	Display Q-file directory on VDT	y
DIR R	Display R-file directory on VDT	y
DIR S	Display S-file directory on VDT	y
DIR BAN	Display BAN-file directory on VDT	y
LDIR ...	Lists directory on Log-file/device	y
DDIR KF	Display/Log directory of KF-file in more detail	y
	Where KF = NOPQRS (default is N) and denotes:	y
	IN-FIL OU-FIL P-FIL Q-FIL R-FIL S-FIL	y

SOME GENERAL DEFINITIONS

DEFINITIONS USED IN COMMAND SYNTAX

B1 - Memory Buffer-1

B2 - Memory Buffer-2

ID - The ID-number of histogram to be read

NUID - Next ID-number to be assigned to output histogram

LO - A first-channel-number (usually of a Gate)

HI - A last- channel-number (usually of a Gate)

FAC - A multiplication factor

MEANING OF THE INDIVIDUAL COMMAND-CHARACTERS

I - Input or read

O - Output or write

A - Add or accumulate

S - Shift (gain shift)

GX - Gate on X-parameter (i.e. parameter # 1)

GY - Gate on Y-parameter (i.e. parameter # 2)

1 - Buffer-1

2 - Buffer-2

M - Multiply

C - Crunch

D - Divide

COMMANDS FOR SETTING UP NEXT ID# STD GAIN-SHIFT & CRUNCH FACTOR

NUID IV	Set next ID to be used to IV	y
IDST N	Set ID-step to be used in implied I/O loops	y
	(remains active until changed - default=1	y
CRUN IVAL	Sets standard crunch value to IVAL	y
GASP XI1 XI2 XF1 XF2 NCF	Standard gain shift specification	y
SIDA	Says treat 16-bit HIS-file data as signed	y
USDA	Says treat 16-bit HIS-file data as un-signed (default)	y

COMMANDS WHICH INPUT OR INPUT/OUTPUT 1-D HISTOGRAMS

I ID	Input to B1	y
IS ID	Input to B1 gain shift B1	y
IA IDFAC	Input to B1 $B2=B2+FAC*B1$	y
ISA IDFAC	Input to B1 shift $B1 B2=B2+FAC*B1$	y
IO ID	Input to B1 output B1	y
ISO ID	Input to B1 shift B1 output B1	y
IO IDAIDB	Input to B1 output B1 (for ID=IDAIDB)	y
ISO IDAIDB	Input to B1 shift output (for ID=IDAIDB)	y
O1	Output B1	y
O2	Output B2	y

COMMANDS WHICH PULL GATES FROM 2-D HISTOGRAMS

GY IDLOHI	Y-gate to B1	y
GYS IDLOHI	Y-gate to B1 shift B1	y
GYO IDLOHI	Y-gate to B1 output B1	y
GYO IDAIDBLOHI	Y-gate to B1 output B1 (for ID=IDAIDB)	y
GYSO IDLOHI	Y-gate to B1 shift & output B1	y
GYSO IDAIDBLOHI	Y-gate to B1 shift & output B1 (for ID=IDAIDB)	y
GYA IDLOHIFAC	Y-gate to B1 $B2=B2+FAC*B1$	y
GYSA IDLOHIFAC	Y-gate to B1 shift B1 $B2=B2+FAC*B1$	y
GX IDLOHI	X-gate to B1	y
GXS IDLOHI	X-gate to B1 shift B1	y
GXO IDLOHI	X-gate to B1 output B1	y
GXO IDAIDBLOHI	X-gate to B1 output B1 (for ID=IDAIDB)	y
GXSO IDLOHI	X-gate to B1 shift & output B1	y
GXSO IDAIDBLOHI	X-gate to B1 shift & output B1 (for ID=IDAIDB)	y
GXA IDLOHIFAC	X-gate to B1 $B2=B2+FAC*B1$	y
GXSA IDLOHIFAC	X-gate to B1 shift B1 $B2=B2+FAC*B1$	y
O1	Output B1	y
O2	Output B2	y

COMMANDS WHICH PERFORM GENERAL PROJECTIONS FROM 2-D HISTOGRAMS

PJ IDBIDDEGR	PROJ TO B1	n (3)
PJS IDBIDDEGR	Proj to B1 shift B1	n (3)
PJO IDBIDDEGR	Proj to B1 output B1	n (3)
PJO IDAIDBBIDABIDBDEGR	Proj to B1 output B1	n (3)
	(outer loop on BID inner loop on ID)	n (3)
PJSO IDBIDDEGR	Proj to B1 shift & output B1	n (3)
PJSO IDAIDBBIDABIDBDEGR -	Proj shift output	n (3)
	(outer loop on BID inner loop on ID)	n (3)
PJA IDBIDDEGRFAC	Proj to B1 $B2=B2+FAC*B1$	n (3)
PJSA IDBIDDEGRFAC	Proj to B1 shift B1 $B2=B2+FAC*B1$	n (3)
PJAL	Project all bananas in currently open	n (3)
	BAN-file for HIS-file ID's & DEGR's	n (3)
	contained therein	n (3)
O1	Output B1	n (3)
O2	Output B2	n (3)

(DEGR = Projection-axis angle in degrees)

ID denotes histogram-ID, BID denotes banana-ID

COMMANDS WHICH MANIPULATE THE INTERNAL DATA BUFFERS (B1 & B2)

M1 XM	Multiply B1 by XM	y
M2 XM	Multiply B2 by XM	y
C1 ICRUN	Crunch B1 by ICRUN (standard crunch unchanged)	y
C2 ICRUN	Crunch B2 by ICRUN (standard crunch unchanged)	y
S1	Shift B1 by standard GASP	y
S2	Shift B2 by standard GASP	y
S1 X11X12XF1XF2NCF	Shift B1 as specified (standard GASP unchanged)	y
S2 X11X12XF1XF2NCF	Shift B2 as specified (standard GASP unchanged)	y
Z1	Zero B1	y
Z2	Zero B2	y
A12 FAC	$B2=B2+FAC*B1$	y
A21 FAC	$B1=B1+FAC*B2$	y
SWAP	Swap B1 & B2	y
M2D1 FAC	$B2=(FAC*B2)/B1$	y
O1	Output B1	y
O2	Output B2	y

COMMANDS WHICH LIST DATA ON TERMINAL OR PRINTER

PR1	Print B1	y
PR2	Print B2	y
D1 LOHI	Display B1 (channels LO thru HI)	y
D2 LOHI	Display B2 (channels LO thru HI)	y

COMMANDS RELATED TO PRINTER-PLOTS

SKRZ	Set to skip repeated-zeros for printer plots	y
PLRZ	Set to plot repeated-zeros for printer plots	y
PLG IDLOHINCYC	Input to B1 & LOG plot	y
PLN IDLOHINCFS	Input to B1 & LIN plot	y
PLG IDAIDBLOHINCYC	Input to B1 & LOG plot (for ID=IDAIDB)	y
PLN IDAIDBLOHINCFS	Input to B1 & LIN plot (for ID=IDAIDB)	y
PLG1 LOHINCYC	Log Printer-plot of B1	y
PLG2 LOHINCYC	Log Printer-plot of B2	y
PLN1 LOHINCFS	Linear Printer-plot of B1	y
PLN2 LOHINCYC	Linear Printer-plot of B2	y

(NCFS = # of counts full-scale for LIN plots)

(NCYC = # of cycles for LOG plots)

COMMANDS WHICH MODIFY THE CHANNEL-CONTENTS OF INTERNAL BUFFERS

SET1 ICNYV	Set channel ICN of B1 to YV	y
SET2 ICNYV	Set channel ICN of B2 to YV	y
SET1 LOHIYV	Set channels LO-thru-HI of B1 to YV	y
SET2 LOHIYV	Set channels LO-thru-HI of B2 to YV	y
SET1 LOHIYAYB	Set channels LO-thru-HI of B1 to YA-thru-YB	y
SET2 LOHIYAYB	Set channels LO-thru-HI of B2 to YA-thru-YB	y
ADD1 ICNYV	Add YV to channel ICN of B1	y
ADD2 ICNYV	Add YV to channel ICN of B2	y
ADD1 LOHIYV	Add YV to channels LO-thru-HI of B1	y
ADD2 LOHIYV	Add YV to channels LO-thru-HI of B2	y
ADD1 LOHIYAYB	Add YA-thru-YB to channels LO-thru-HI of B1	y
ADD2 LOHIYAYB	Add YA-thru-YB to channels LO-thru-HI of B2	y

SOME CMDS RELATED TO TESTING

GEN IDKOKXNCH	Generate test spectrum in B1 (NCH channels)	y
	Channel contents = $KO + KX * (\text{channel\#} + 1)$	y
COMP NCH	Compare first NCH-channels of B1 & B2	y
	(gives # counts and # mis-matches)	y
SUM1 LOHI	Display sum of counts LO-thru-HI of B1	y
SUM2 LOHI	Display sum of counts LO-thru-HI of B2	y

1-D DISPLAY COMMANDS (NORMAL)

DLAD MS	Set Display-delay to MS milliseconds (default=500)	y
LIN/LOG	Set display to linear/log (default is linear)	y
ST /OV	Set to disp mult hist stacked/overlayed (dflt = OV)	y
CAL ABC	Define energy calibration ($E=A+B*Chan+C*Chan**2$)	y
COL UK...	Defines color sequence for display	y
	For U.. = 1 2 3 4 5 6 7	y
	COL= whiteredgreenbluecyanmagentayellow	y
RUD NC	KRUNch Display (draw 1 histogram vector per NC chans)	n (1)
GWID WID	Define cursor-mode sum-region width (channels)	y
DNOR LOHI	Normalize displayed data to count-sum of chans LOHI	y
DL LOHI	Set display limits (minmax chan#)	y
DMM LOHI	Set display limits (minmax counts)	y
D IDLST	Display histogram ID's contained in IDLST	y
DX IDLST	Display IDLST (range defined by expand-region)	y
	IDLST format is KF C ID C ID.. KF C ID C ID..	y
	C is an OPTIONAL floating-point norm-coeff (DFLT=1.0)	y
	KF = MNOPQRS (default is N) and denotes	y
	MEM-BUF IN-FIL OU-FIL PROJ-FIL Q-FIL R-FIL S-FIL	y
	If IDLST omitted uses previously defined IDLST	y
SUML LOHI	Define sum region for SUM command below	y
SUM IDLST	Sum counts (LOHI) (IDLST same as D except C illegal)	y
C	Enter cursor-mode	y
SSI	Set screen to initial - erase all graphic windows	y

1-KEY CURSOR COMMANDS FOR 1-D DISPLAY

LF-ARROW	Set expand-region lo-limit	y
RT-ARROW	Set expand-region hi-limit	y
E	Expand display	y
V	Make marker display visible/invisible (toggles)	y
DN-ARROW	Pan DOWN - move picture so cursor-chan at right-screen	y
UP-ARROW	Pan UP - move picture so cursor-chan at left-screen	y
	(you must be expanded to execute pan)	y
L	Set sum-region lo-limit	y
H	Set sum-region hi-limit	y
G	Set sum-region limits (LO=XCUR HI=XCUR+WID-1)	y
S	Display sum centroid & fwhm of sum region	y
	DATA(LO)DATA(HI) defines BGD for NETS	y
A	Display sum centroid & fwhm of sum region	y
	YCUR(LO)YCUR(HI) defines BGD for NETS	y
C	Draw peak-marker and display chan# at cursor pos	y
P	Draw peak-marker and display energy at cursor pos	y
/	Display/log XCUR YCUR channel# & energy	y
	(logs to damm.log if PLON - see note below)	y
Q	Quit cursor-mode (return to normal-mode)	y
PLON	Turns peak logging (to damm.log) ON	y
PLOF	Turns peak logging (to damm.log) OFF (default)	y

COMMANDS RELATED TO 2-D DISPLAY

CMAP	Set color map to default ("takes" after next FIG	y
CMAP FILNAM	Set color map from FILNAM ("takes" after next FIG	y
ZLEV N	Set # of color/grey-scale intensity levels to	y
ZLEV	Set # of color/grey-scale intensity levels to 10 (dflt)	y
GRAS IJK..	Set grey-scale values (range 0-100) & ZLEV (# entries)	y
	(must do after first FIG ("takes" after next FIG)	y
ZINT COLR	Set 2-D intensity mapping to Color (default)	y
ZINT GREY	Set 2-D intensity mapping to Grey-scale	y
ZINT DOTS	Set 2-D intensity mapping to Dot-matrix (3x3 or 5x5)	y
ZSON	Z-scale ON - displays counts vs colors legend (default)	y
ZSOF	Z-scale OFF	y
ZLOG	Set 2-D display to log (default)	y
ZLIN	Set 2-D display to linear	y
XC LOHI	Set min & max X-channel numbers for display	y
YC LOHI	Set min & max Y-channel numbers for display	y
ZMM LOHI	Set min & max counts/channel for display & count-sum	y
ZMM LO	Sets min & searches for max (semi-autoscale)	y
ZMM	Searches for min & max (full-autoscale)	y
DD ID	Display 2-D histogram ID from IN-file	y
DD KFID	Display 2-D histogram ID from KF-file	y
DDX ID	Display 2-D histogram ID from IN-file (expand region)	y
DDX KFID	Display 2-D histogram ID from KF-file (expand region)	y
	Where KF = NOQRS (default is N) and denotes:	y
	IN-FIL OU-FIL Q-FIL R-FIL S-FI	y
	ID (and KF) omitted says use previously defined spec	y
DDID	Shows ID-number & Filename for current 2-D display	y
ZBL	Zero in-core BAN-library	y
LBL	List in-core BAN-ID numbers	y
C	Enter cursor-mode	y
SSI	Set screen to initial - erase all graphic windows	y

1-KEY CURSOR COMMANDS FOR 2-D DISPLAY

LF-ARROW	Set expand-region lo-left- limit	y
RT-ARROW	Set expand-region hi-right-limit	y
V	Make expand markers visible/invisible (toggles)	y
1	Move display such that cursor is at lo-left	y
2	Move display such that cursor is at hi-left	y
3	Move display such that cursor is at hi-right	y
4	Move display such that cursor is at lo-right	y
Z	Zero (open) active XY-list	y
A	Add point to active XY-list	y
D	Dele nearest point in active XY-list	y
M	Move nearest point in active XY-list to cursor pos	y
I	Insert a point in active XY-list at cursor position	y
L	List active XY-list (on VDT)	y
B	Draw active BAN & BAN's in in-core library	y
G	Prompt for ID & read into in-core BAN-library	y
O	Open nearest in-core BAN for modification	y
S	Prompt for ID & store in in-core library & on disk	y
R	Store nearest BAN with original ID	y
F	Remove nearest BAN from in-core library & erase	y
K	Delete nearest BAN from in-core library and disk	y
T	Totalize counts in nearest BAN (active or not)	y
P	Totalize and & save X- & Y-projections on PLOP.SPK	y
/	Display XY-coordinates of cursor	y
E	Expand	y
Q	Quit cursor-mode (return to normal-mode)	y

COMMANDS RELATED TO PEAK-FINDING DISPLAY LOGGING

FIND	Turn peak-find & display ON (BIAS=5.0 FWHM=5)	y
FIND BIASFWHM	Turn peak-find & display ON Where	y
	BIAS = peak-detect threshold (useful values = 3-10)	y
	FWHM = approximate peak FWHM in channels (integer)	y
NOFI	Turn peak-find & display OFF (default is OFF)	y
PLON	Turns peak logging (to damm.log) ON	y
PLOF	Turns peak logging (to damm.log) OFF (default)	y

MANUAL ENTRY OF PEAK BACKGROUND & SKIP-REGIONS

PZOT	Zero the Peak Library	y
PK XWASLOASHI	List of complete peak specifications	y
BZOT	Delete Fixed Background array	y
BACK X1Y1 X2Y2 ..	XY-points for fixed background	y
SKIP	Without List turns SKIP OFF	y
SKIP I1I2 J1J2 ..	Up to 4 regions to omit from Fit	y

DEFINITION OF FWHM ASYM WLIM ALIM NBC ECAL

FW FWAFWBFWC	Coefficients for standard width function	y
ASYM ASLOASHI	Standard Lo-Side and Hi-Side asymmetries	y
WLIM FWLOFWHI	Variation limit factors for peak widths	y
ALIM FALOFAHI	Variation limit factors for peak asymmetries	y
NBC NBC	Number of power series terms in variable BGD	y
WOOD ON/OFF	Says turn Woods-Saxon background term ON/OFF	y
	ON creates an additional background component	y
	with a Woods-Saxon "jog" under each peak which	y
	is porportional to the peak intensity.	y
	(default is OFF)	y
ECAL ECOECAECB	Coefficients for standard energy calibration	y

y

RELATIVE INTENSITY FIXING COMMANDS

RELI XR	Specifies that the relative intensity of the	y
	library peak nearest to channel X is to be R.	y
	R may be in any "units" (8 character limit!)	y
	Peak-areas will be in the same ratios as the	y
	relative intensities specified ONLY if width	y
	and asymmetry parameters are the same.	y
	RELI HAS NO EFFECT UNLESS THERE ARE 2 OR	y
	MORE	
	SUCH PEAKS IN THE REGION FITTED.	y
	RELI specifications must be entered AFTER the	y
	associated peak library entries are completed	y
RELI ZOT	Says delete all relative intensity entries	y
RELI OFF	Says turn OFF (disable) relative intensity	y
	control but do not delete previously entered data	y
RELI ON	Says turn ON (enable) relative intensity control	y

VARIATION CONTROL COMMANDS

DPX XSTEPDXMAX	Initial step size and limit for peak pos	y
DEL DELDELFACTDEL	Initial step size step size multiplier and	y
	number of DEL-values to use	y
VB	Use Variable Background (the default)	y
FB	Use Fixed Background if available	y
VX KVAR	Kind of variation for peak positions	y
VW KVAR	Kind of variation for peak widths	y
VALO KVAR	Kind of variation for Lo-Side asymmetries	y
VAHI KVAR	Kind of variation for Hi-Side asymmetries	y
KVAR = UIND	says vary Unconditionally Independently	y
= CIND	says vary Conditionally Independently	y
= ULOC	says vary Unconditionally Locked	y
= CLOC	says vary Conditionally Locked	y
= FIX	says keep Fixed - this the default assignment	y

GENERAL FIT DISPLAY CONTROL COMMANDS

WIN NW	Set subsequent displays to be in window-NW	y
LIN/LOG	Set graphic display to LIN (default) or LOG	y
DMM MINMAX	Set display limits (minmax counts)	y
	MIN or MAX = X says use min or max data value	y
DL ILOIHI	Set display-range (channel# limits)	y
DS ID	Display spectrum# ID (range defined by DL)	y
DS IDILOIHI	Display spectrum# ID (DL values replaced)	y
	(MAX value of IHI-ILO = 8191)	y
DSX ID	Display Data defined by Expand Region	y
C	Enter 1-key cursor-mode	y

COMMANDS RELATED TO DISPLAY OF FITS

WIN NW	Set subsequent displays to be in window-NW	y
MON/MOF	Turn peak-markers ON/OFF for DF (dflt=ON)	y
DFI	Set to display (DF) DATAFITBGD (default)	y
DPK	Set to display (DF) DATAFITPEAKSBGD	y
DPPB	Set to display (DF) DATAFIT(PEAKS+BGD)BGD	y
DF	Display Fit (channel-limits given by Fit-range)	y
DF ILOIHI	Display Fit (channel-limits given by ILOIHI)	y
DC NPK	Display Calculated peak # NPK+ RESIDUAL	y

FIT CONTROL COMMANDS

FIT IDILOIHI	Fit Request - (non-linear gradient search)	y
GFIT IDILOIHI	Fit request - (gaussian method)	y
RFIT IDILOIHI	Resume FIT/GFIT start with Parns from last Fit	y
LFIT IDILOIHI	Linear Fit - no non-linear search	y
	(Fit-range specified by ILOIHI)	y
FIT ID X	Fit Range specified by cursors (Fit Region)	y
GFIT ID X	Fit Range specified by cursors (Fit Region)	y
RFIT ID X	Fit Range specified by cursors (Fit Region)	y
LFIT ID X	Fit Range specified by cursors (Fit Region)	y
Ctrl/C	Terminates Fit-in-progress	y

COMMANDS WHICH DISPLAY PEAKS BGD-POINTS & FIT-PARMS

PRP XLOXHI	Display peaks from Library in range XLO thru XHI	y
PRP	Display all peaks from Library	y
PRB	Display all fixed background point	y
FSTAT	Display current fit-parameters	y

COMMANDS RELATED TO LIST PRINT OR HARD-COPY

KPPL NONE	Do no printer plots (default)	y
FITS	Plot FITS only	y
ALL	Plot FITS COMPONENTS and RESIDUALS	y
PR	Print and Plot results of last Fit on printer	y
DR	List results of last Fit on VDT (terminal)	y

COMMANDS WHICH SAVE FIT PAREMETERS IN LIBRARY

SAV IJ	Save all Parns from peaks I thru J of last Fit in PK-LIB	y
SAX IJ	Save X-Parns for peaks I thru J of last Fit	y
SAW IJ	Save W-Parns for peaks I thru J of last Fit	y
SAL IJ	Save ASL-Parns for peaks I thru J of last Fit	y
SAH IJ	Save ASH-Parns for peaks I thru J of last Fit	y

(If IJ ommitted indicated Parns from ALL peaks are saved)

COMMANDS WHICH SET FIT PARAMETERS

SET- X1X2	Set STD WIDTH and ASYM for peaks in range X1-X2	y
	values (defined by FWA FWB FWC ASLO ASHI)	y
SETW X1X2	Set WIDTH for peaks in range X1-X2 to STD value	y
SETW X1X2WAWBWC	Set WIDTH for peaks in range X1-X2 to value	y
	defined by WAWBWC (FWAFWBFWC unchanged)	y
SETL X1X2	Set ASLO for peaks in range X1-X2 to STD value	y
SETL X1X2ASLOT	Set ASLO=ASLOT for peaks in range X1-X2	y
SETH X1X2	Set ASHI for peaks in range X1-X2 to STD value	y
SETH X1X2ASHIT	Set ASHI=ASHIT for peaks in range X1-X2	y

(If X1X2.. omitted indicated Parms for ALL peaks are set)

LIST OF DEFAULT PARAMETER VALUES

DEL = 0.05	FWLO = 0.5	VX = CIND
NBC = 2	DELFAC=0.25	FWHI = 2.0
VW = CLOC	WOOD = OFF	NDEL = 1
FALO = 0.5	VALO = FIX	KPPL = NONE
XSTEP = 0.5	FAHI = 2.0	VAHI = FIX
DXMAX = 5.0	ASLO = 0.0	ASHI = 0.0

1-KEY (OR 2-KEY) CURSOR RELATED COMMANDS

These commands are valid after a DS or DSX command

Type: C	to enter cursor-mode	y
P/UP	Add/Delete peak to Library (pos specified by cursor)	y
M	Move nearest displayed peak to cursor pos (FW ASYM unchanged)	y
X/UX	Fix/Free peak position (for displayed peak nearest to cursor)	y
W/UW	Fix/Free peak width (for displayed peak nearest to cursor)	y
L/UL	Fix/Free Lo-Side ASYM (for displayed peak nearest to cursor)	y
H/UH	Fix/Free Hi-Side ASYM (for displayed peak nearest to cursor)	y
O/UO	Turn peak ON/OFF (for displayed peak nearest to cursor)	y
B/UB	Add/Delete background point at cursor position	y
LF-ARO	Set Expand Region Lo-Limit	y
RT-ARO	Set Expand Region Hi-Limit	y
[	Set Fit Region Lo-Limit	y
]	Set Fit Region Hi-Limit	y
/	Display chan# cursor Y-value chan contents	y
S	Disp sum cent & fwhm of Fit-Reg - DAT(D)DAT(I) defines BGD	y
A	Disp sum cent & fwhm of Fit-Reg - CUR(D)CUR(I) defines BGD	y
Q	Return from cursor control routine	y
E	Expand display (region defined by <- ->)	y

HISTOGRAM XFER COMMANDS

HOU FILNAM	Open FILNAM for histogram Output	y
GSX XI1XI2 XF1XF2	Define X-gain-shift	y
GSY YI1YI2 YF1YF2	Define Y-gain-shift	y
GSXOF/GSYOF	Turn OFF X/Y-gain-shift	y
SNeg OFF	Turn OFF reset of neg 16bit out data (default	n (1)
SNeg IV	Says set negative 16-bit output data to IV	n (1)
	(you MUST use SIDA mode for this to work!!)	y
HSTA	Shows files open & gain-shift data	y
HCOP IDIIDO <FI>	Copy F*IDI (Input) to IDO (Output)	y
HADD IDIIDO <FI><FO>	Add FI*IDI to FO*IDO	y
HDIV IDIIDO <FI>	Div FI*IDI by IDO & save in IDO	y
SHF IDIIDO	Gain-shift IDI & store in IDO	y
SHAD IDIIDO <FI><FO>	Gain-shift IDI & add to IDO	y
HSET IDOIV	Set IDO on Output file to IV	y
HZOT IDO	Set IDO on Output file to 0	y

SPK-SUMS HIS-SUMS AND DIRECTORY COMMANDS

DDIR KF	Display directory of KF-file	y
	Where KF = NOPQRS (default is N) and denotes:	y
	IN-FIL OU-FIL P-FIL Q-FIL R-FIL S-FIL	y
DSUM KF	Displays count-sum of all histograms in KF-file	y
	Where KF has same meaning as above	y

COMMANDS DEFINING MOUSE-BUTTONS (WHEN IN 1-KEY CURSOR-MODE)

BUD LMR	Defines LeftMiddleRight buttons for cursor in D-window	y
BUDD LMR	Defines LeftMiddleRight buttons for cursor in DD-window	y
BUDS LMR	defines LeftMiddleRight buttons for cursor in DS-window	y
BUD LHS	Example (cursor in 1-D) L-butt sets sum-reg lo-limit	y
	M-butt sets sum-reg hi-limit R-butt requests S-sum	y
BUDD ATZ	Example (cursor in 2-D) L-butt adds banana points	y
	M-butt totalizes enclosed counts R-butt zots banana	y

1: COMMAND NOT RECOGNIZED.

3: READ ERROR ID NOT FOUND.

END

**DATE
FILMED**

6 / 14 / 93