WSRC-TR-92-565 (U)

Task: 92-887-H-M-1

NUCLEAR CRITICALITY SAFETY EVALUATION OF SRS 9971 SHIPPING PACKAGE (U)

WSRC-TR--92-565

DE93 012818

P. J. Vescovi

UNCLASSIFIED DOES NOT CONTAIN UNCLASSIFIED CONTROLLED NUCLEAR INFORMATION	
ADC & Reviewing Official:	<u>J. R. Chandler, Jr. Fellow Engineer</u> (Name and Title)
	Date: <u>Feb. 22, 1993</u>

Westinghouse Savannah River Company
Savannah River Site
Aiken, SC 29808

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

THIS PAGE INTENTIONALLY LEFT BLANK

CONTENTS

INTRODUCTION.....	1
SUMMARY.....	1
NOMINAL VOLUME OF SHIPPING BOTTLE.....	1
SHIPPING BOTTLE LIMITS.....	1
SHIPPING PACKAGE LIMITS.....	1
HYDROGENOUS PACKING MATERIAL LIMITS.....	2
REFERENCES.....	2
ATTACHMENT I.....	3
CRITICALITY COMPUTATION FOR THE 9971 USF PACKAGING.....	4
ATTACHMENT II.....	5
CRITICALITY EVALUATION.....	6
6.1 Discussion and Results.....	6
6.2 Package Fuel Loading.....	8
6.3 Model Specification.....	11
6.3.1 DESCRIPTION OF CALCULATION MODELS.....	11
6.3.1.1 9971 Single Package Model.....	11
6.3.1.2 9971 Undamaged and Damaged Array Model...	11
6.3.2 PACKAGE REGIONAL DENSITIES.....	17

CONTENTS *(Continued)*

ATTACHMENT II *(Continued)*

6.4	Criticality Calculation.....	23
6.4.1	CALCULATION METHOD.....	23
6.4.2	FUEL LOADING OPTIMIZATION.....	23
6.4.3	CRITICALITY RESULTS.....	24
6.4.3.1	<i>Single Package Analysis.....</i>	<i>24</i>
6.4.3.2	<i>Array Analyses.....</i>	<i>27</i>
6.4.3.2.1	<i>Mass Limit For Uniform Distribution Of UO₃ In Bottles.....</i>	<i>27</i>
6.4.3.2.2	<i>Damaged Finite Array Size Limit.....</i>	<i>27</i>
6.4.3.2.3	<i>Alternative Materials For Burned Cane Fiberboard In Damaged Infinite Array.....</i>	<i>32</i>
6.4.3.2.4	<i>O-Ring Material Effects.....</i>	<i>32</i>
6.4.4	DISPLACEMENT OF INNER CONTAINER IN DAMAGED ARRAY.....	32
6.4.5	USE OF SMALLER OR LARGER PLASTIC BOTTLES.....	33
6.5	Criticality Benchmark Experiments.....	34
6.6	References.....	36

LIST OF FIGURES

Figure 6-1	Bottle Bulk Mass Limits With Water Present.....	10
Figure 6-2	Triangular-Pitch Array To Square-Pitch Array Equivalence.....	12
Figure 6-3	Single Package Computational Model.....	14
Figure 6-4	Shipping Package Computational Model.....	15
Figure 6-5	Bottle Computational Model.....	16
Figure 6-6	Results For 9971 Single Package Analysis.....	26
Figure 6-7	Uniform Distribution Of UO_3 In Bottles.....	29
Figure 6-8	Finite Cubic Array Of Damaged Packages.....	31

LIST OF TABLES

TABLE 6-I	Summary Of Criticality Evaluation.....	6
TABLE 6-II	Density Data For Y-12 UO_3 Product.....	8
TABLE 6-III	UO_3 Moisture Content Data For Y-12 Product.....	9
TABLE 6-IV	UO_3 Loading Limits For 9971 Shipping Package.....	9
TABLE 6-V	Bottle Bulk Mass Limits With Water Present.....	10
TABLE 6-VI	Composition Of Structural Materials Used In 9971 Analysis.....	18
TABLE 6-VII	Composition Of UO_3 -Water Mixtures Used In 9971 Single Package Analysis.....	20
TABLE 6-VIII	Composition Of UO_3 -Air (Void) -Water Mixtures Used In Damaged 9971 Array Analysis.....	21
TABLE 6-IX	Results For 9971 Single Package Analysis.....	25
TABLE 6-X	Results For 9971 Package Array Analysis Mass Limit For Uniform Distribution Of UO_3 In Bottles.....	28
TABLE 6-XI	Damaged Finite Array.....	30
TABLE 6-XII	Error Range/Confidence Level.....	34

APPROVALS

PROJECT: SRS 9971 Shipping Package Certification
DOCUMENT: WSRC-TR-92-565 (U)
TITLE: Nuclear Safety Evaluation of SRS 9971 Shipping Package (U)
TASK: 92-007-H-M-1

P. J. Vescovi, AUTHOR
Applied Physics Group
SCIENTIFIC COMPUTATIONS SECTION

Date: 2-22-93

J. F. Mincey, TECHNICAL REVIEWER
Applied Physics Group
SCIENTIFIC COMPUTATIONS SECTION

Date: 2/22/93

C. E. Apperson, Jr., MANAGER
Applied Physics Group
SCIENTIFIC COMPUTATIONS SECTION

Date: 2-22-93

M. R. Buckner, MANAGER
SCIENTIFIC COMPUTATIONS SECTION

Date: 2-23-93

NUCLEAR CRITICALITY SAFETY EVALUATION OF SRS 9971 SHIPPING PACKAGE (U)

By P. J. Vescovi

**Westinghouse Savannah River Company
Savannah River Site
Aiken, SC 29808**

INTRODUCTION

This evaluation is requested to revise the criticality evaluation¹ used to generate Chapter 6 (Criticality Evaluation) of the Safety Analysis Report for Packaging (SARP) for shipment of UO_3 product from the Uranium Solidification Facility (USF) in the SRS 9971 shipping package. The pertinent document requesting this evaluation is included as Attachment I. The results of the evaluation are given in Attachment II which is written as Chapter 6 of a NRC format SARP.

SUMMARY

The criticality safety evaluation for the SRS 9971 shipping package has been revised. Recent thermal tests indicate fiberboard insulation damage exceeding pre-test predictions. An infinite array of damaged SRS 9971 shipping packages is not subcritical, but a finite array stacked together in any arrangement not to exceed two thousand (2000) packages is subcritical. Only two hundred fifty packages (250) are required to be subcritical for a Fissile Class I package. IAEA shipping requirements for a $\text{TRANSPORT INDEX} = 0^2$ are not satisfied.

The conclusion of this evaluation is that UO_3 product from the USF can be shipped in the SRS 9971 shipping package as FISSILE Class I³, provided the following limits are maintained in loading the packages:

Nominal Volume Of Shipping Bottle:

- 2.25 Liters not to exceed 2.4 Liters

Shipping Bottle Limits:

• Maximum Quantity of Dry UO_3 per Bottle	6.5 Kg
• Maximum ^{235}U Enrichment of U in UO_3	80.0 Wt%
• Maximum Added Moisture Content of Product	6.0 Wt%

Shipping Package Limits:

• Maximum Number of Filled Bottles per Package	2

Hydrogenous Packing Material Limits:

- Unlimited Quantities

REFERENCES

1. Finch, D. R., *Nuclear Criticality Safety Evaluation of SRS 8871 Shipping Package*, WSRC-TR-91-445, July 1991.
2. International Atomic Energy Agency, *Regulation for the Safe Transport of Radioactive Materials*, Safety Series No. 65, IAEA, Vienna, Austria 1985.
3. U. S. Code of Federal Regulations, *Part 71 - Packaging and Transportation of Radioactive Materials*, 10 CFR 71, November 30, 1988.

ATTACHMENT I

This attachment contains all documents requesting this evaluation and information requested or supplied pertaining to the evaluation.

OSR 3-4A-W (Rev 1-89)

WESTINGHOUSE SAVANNAH RIVER COMPANY
INTER-OFFICE MEMORANDUM

SRT-PTG-92-0099

August 4, 1992

TO: JAMES F. MINCEY, 773-22A
COURTNEY E. APPERSON, 773-42A

From: ROBERT S. MAURER, 305-2A *R.S.M.*
(5-4728)

SUBJECT: CRITICALITY COMPUTATION FOR THE 9971 USE
PACKAGING (U)

As per our conversation August 3, the Packaging and Transportation Group is requesting your support for the criticality reevaluation of the 9971 Packaging. Due to the results of the 9971 Pool Fire Test the following parameters need to be used in the computation: 1) a 3.1 inch layer of char over the entire cylindrical outer surface of the fiberboard and 2) a 2.5 inch layer of char at the top and bottom surfaces of the fiberboard. The criticality evaluation and chapter upgraded needs to be completed by November.

cc: George A. Lucky, 305-2A
Erich K. Opperman, 305-2A

ATTACHMENT II

This attachment contains the detailed results of this nuclear criticality safety evaluation in the format required by the Nuclear Regulatory Commission (NRC) to be Chapter 6 of the Safety Analysis Report for Packaging (SARP) for the 9971 shipping package for UO_3 product from the SRS Uranium Solidification Facility.

CHAPTER 6
CRITICALITY EVALUATION

6.1 DISCUSSION AND RESULTS

A nuclear criticality safety evaluation of the 9971 shipping package was performed. This evaluation was based on a computational analysis¹ of the shipping package including 1) Single Package Analysis of the water reflected inner container, 2) Array Analysis of undamaged complete packages, and 3) Array Analysis of damaged complete packages. The computational analyses¹ included determination of optimum interspersed moderation, and determination of optimum fissile material content for maximum reactivity. Results from thermal tests are used to evaluate the damaged package, and the computational analysis¹ performed prior to the thermal tests is included in this evaluation as applicable. This criticality evaluation complies with all requirements of the ANSI/ANS 8.1 standard², all requirements of DOE Order 5480.5³, and relevant requirements of 10 CFR 71⁴.

The results of the computational evaluation of the 9971 package (with fissile loading no greater than specified in Table 6-IV) show that it qualifies for shipment under DOT Fissile Class I regulations⁵. The package does **not** qualify under IAEA regulations for a transport index of 0 (zero)⁶. These results are summarized in Table 6-I.

TABLE 6-I
SUMMARY OF CRITICALITY EVALUATION
FISSILE CLASS I

NORMAL CONDITIONS	CLASS I
Number of Undamaged Packages Calculated to be subcritical	Infinite
Optimum Interspersed Hydrogenous Moderation	Dry Air or Void
Package Size , Cubic Centimeters	144,686 CM ³
Inner Container Size, Cubic Centimeters	6,850 CM ³

ACCIDENT CONDITIONS

CLASS I

Number of Damaged Packages Calculated to be subcritical	250
Optimum Interspersed Hydrogenous Moderation	Dry Air or Void
Package Size , Cubic Centimeters	144,686 CM ³
Inner Container Size, Cubic Centimeters	6,850 CM ³

The highest reactivity calculated in the single package analysis was for the single inner container containing 6.835 Kg. of UO₃ uniformly dispersed inside the water flooded and water reflected inner container. This is an optimum condition and is not a maximum allowable mass loading for UO₃. The uranium was assumed to be 100 Wt% ²³⁵U in this calculation. In this condition a safety margin of at least 0.15 in K_{eff} was calculated.

The reactivity was calculated for the undamaged infinite array for 1) a maximum loading of 13.0 Kg. of dry UO₃ at uranium enrichment up to 100 Wt% ²³⁵U, 2) dry air or void interspersed in the array, 3) dry cane fiberboard (no extra water) in the package, 4) no hydrogenous packing material inside the inner container, and 5) no more than 6 Wt% water content in the UO₃. In this condition a safety margin of 0.25 in K_{eff} was calculated.

The damaged infinite array is not subcritical for the same conditions as used to calculate K_{eff} for the undamaged infinite array. The UO₃ loading would need to be limited to approximately 20 percent of the container capacity in order to ensure subcriticality for the infinite damaged package array under accident conditions and qualify under IAEA regulations for a transport index of 0 (zero)⁵.

A finite array of at least two hundred fifty (250) damaged packages is subcritical for the same conditions used to analyze the undamaged package in an infinite array, with a maximum loading of 13.0 Kg. of dry UO₃ at uranium enrichment up to 100 Wt% ²³⁵U. Actual array size used in calculation was 256 (8 X 8 X 4). In this condition a safety margin of 0.30 in K_{eff} was calculated. The number of packages may be increased to two thousand (2000) and a safety margin of at least 0.05 was calculated. Computational analysis¹ has shown the calculated reactivity coefficient (K_{eff}) decreases for each of the following changes:

- Reducing the UO_3 content of the package.
- Reducing the water content in the UO_3 in the package.
- Introducing any hydrogenous interspersed moderation (in the space between the packages).
- Adding water content to the cane fiberboard inside the outer package container.
- Adding hydrogenous packing material in the space inside the inner container.

6.2 PACKAGE FUEL LOADING

The 9971 shipping package is specified for shipment of 13.0 Kg. of dry UO_3 in two 2.0-liter high density polyethylene or polypropylene plastic containers. This loading is maximum capacity expected for the shipment of UO_3 . UO_3 is the trioxide compound of uranium that has crystalline density of 7.29 grams/cc. The bulk density of UO_3 is dependent upon the specific chemical process used to produce the material. A fine granular UO_3 product will have a higher bulk density than a coarse granular UO_3 product because interspersed air space increases with grain size. For the purposes of this evaluation, density data for UO_3 product from the production process at the Y-12 plant in Oak Ridge, TN was used⁷. The chemical process and equipment used in the Y-12 plant are almost identical to that used in the Uranium Solidification Facility (USF) at Savannah River Site (SRS). This data is summarized in the Table 6-II.

Table 6-II
Density Data For Y-12 UO_3 Product⁷

Density of UO_3 product leaving denitrator	3.25 to 3.5 g/cc
Maximum density of UO_3 product after settling	3.75 g/cc
Maximum density for analysis purposes (Y-12)	3.90 g/cc

For purposes of this evaluation the highest credible density of UO_3 product was assumed to be 4.0 g/cc. This is a slightly more conservative assumption than indicated by the Y-12 data. To achieve this 4.0 g/cc density would require special equipment designed to pack the UO_3 product beyond what is possible by normal settling.

The second property of the UO₃ product that can affect the criticality safety of the package is the moisture content of the material. Again data from the Y-12 plant UO₃ product⁸ was used, and appears in Table 6-III.

Table 6-III
UO₃ Moisture Content Data For Y-12 Product⁸

Moisture content of nominal product material	2.3 Wt%
Maximum moisture content of product material	6.3 Wt%
Moisture content at which free pour ceases	3 to 6 Wt%

For purposes of this evaluation the requirement of criticality safety with water content up to 6 Wt% of bulk product weight was used. This limit permits visual detection of excess water content because the product ceases to pour freely before it reaches the 6 Wt% limit. For the purposes of the criticality safety evaluation the following limits were used for loading of the bottles shipped in the 9971 package.

Table 6-IV
UO₃ Loading Limits For 9971 Shipping Package

Maximum mass of dry UO ₃ product in 9971 package	13.0 Kg.
Maximum mass of dry UO ₃ product in any 2.0-liter bottle	6.5 Kg.
Maximum number of 2.0-liter bottles per 9971 package	2
Maximum added water in UO ₃ product	6 Wt%

The mass of dry UO₃ product excludes the water content. The water content is expressed as a weight percent of bulk mass in the bottle (UO₃ mass plus water mass). For reference, Table 6-V and Figure 6-1 show mass limits for bulk product material as a function of Wt% water content in the bulk product material. The limiting curve is based on a dry UO₃ content of 6.5 Kg. in each bottle.

Full brim capacity of the individual bottles is 2.3 liters. Each bottle loaded to full brim capacity with the highest credible density of UO₃, 4.0 g/cc, would contain 9.15 Kg dry UO₃. The loading limit of 6.5 Kg dry UO₃ is considered the actual maximum loading that will be encountered for the density of UO₃ product leaving the denitrator. This analysis is for the maximum loading limit of 6.5 Kg. mass of dry UO₃ product with up to 6 Wt% water in the bulk product.

Table 6-V
Bottle Bulk Mass Limits With Water Present

<u>Wt% Water In Bulk Product</u>	<u>Bulk Mass Limit For Bottle</u>
0	6.500 Kg.
1	6.566 Kg.
2	6.633 Kg.
3	6.701 Kg.
4	6.771 Kg.
5	6.842 Kg.
6	6.915 Kg.

Figure 6-1. Bottle Bulk Mass Limits With Water Present (REF: TABLE 6-V)

6.3 MODEL SPECIFICATION

This section will describe the calculation models used in the analysis of criticality safety for the 9971 shipping package.

6.3.1 Description of Calculation Models

6.3.1.1 9971 Single Package Model

The single package analysis model considered only the inner container of the 9971 package filled with a mixture of UO₃ product and water. The inner container was reflected by a minimum of 50 Cm. (19.65 inches) of water on all sides which constitutes an effectively infinite reflector. The calculation model is shown in Figure 6-3 and was derived from Engineering Drawings listed in Reference 9.

The product material-water mixture was assumed to occupy varying volumes of the inner container as shown in Figure 6-3 with all remaining volume filled with water.

The single package analysis model ignores the presence of plastic bottles, and optional packing materials within the inner container that could be admixed with the UO₃ product thus reducing the H/U atom ratios that are possible inside the container. In addition, including the bottle materials and packing could introduce mild neutron poisons (such as chlorine) into the calculation which could reduce the calculated reactivity coefficient (K_{eff}). The admixed water within the UO₃ product represents a greater quantity of hydrogen than could be provided by any credible packing material, hence represents a worse case (normally higher calculated K_{eff}) than explicitly modeling the packing materials.

6.3.1.2 9971 Undamaged and Damaged Array Model

The array analysis model considered cubic arrays of packages that extend to infinity in all directions, and finite arrays closely reflected with water on all sides. The calculation model is shown in Figure 6-4 and was derived from Engineering Drawings listed in Reference 10. The outer diameter of the 35-gallon type 17C drum was reduced by 7% to

equate a triangular-pitch array to the square-pitch array used in the calculations. The basis of this 7% reduction in diameter is to equate the area occupied by the drum in a triangular-pitch array to the area occupied by the drum in the square-pitch array, and is shown in the following diagram.

Figure 6-2. Triangular-Pitch Array To Square-Pitch Array Equivalence

The dimensions used in the calculations are shown in Figure 6-4 with dimensions for the inner container shown in Figure 6-3.

The same array model was used for undamaged and damaged arrays by replacing the material in the burned cane fiberboard region (damaged model) with normal cane fiberboard (undamaged model). As mentioned, it was not possible to show an infinite array acceptable and the damaged array calculation has finite boundaries.

The UO₃ product was confined to the two bottles shown in Figure 6-4. The calculation model for the bottles is shown in Figure 6-5 and was constructed from manufacturer's specifications and measurements of an actual bottle listed in Reference 13. Partially filled bottles were modeled by placing the UO₃ product in the region designated UO₃, and filling the rest of the bottle with dry air in the region so

designated. The region in the inner container surrounding the two bottles was filled with dry air or a variety of packing materials depending on the calculation. The bottles were sized to a volume of 2.29 liters, although the manufacturer's specification¹¹ gives a maximum brim capacity for this bottle of up to 2.2 liters.

In the damaged package model a low density carbon material (to simulate fiberboard ash) was placed in the burned cane fiberboard region shown in Figure 6-4. The low density carbon material is defined in Table 6-VI, and represents about the same carbon content as in the original fiberboard. The burned cane fiberboard region was modeled as a 3.1 inch layer over the entire cylindrical outer surface

Figure 6-3. Single Package Computational Model

Figure 6-4. Shipping Package Computational Model

Figure 6-5. Bottle Computational Model

of the fiberboard, and a 2.5 inch layer at the top and bottom surfaces of the fiberboard to reflect the results of thermal tests.¹²

The calculation model was constructed so that materials in each region in Figure 6-4 could be changed to determine the K_{eff} sensitivity to the change. The following material regions could be specified uniquely.

- UO₃ product mixture in each bottle separately.
- Atmosphere in the unfilled region of each bottle separately.
- Packing material surrounding the bottles inside the inner container.
- Material in the stainless steel inner container.
- Atmosphere in the air space inside the package outside the inner container.
- Composition of the cane fiberboard.
- Composition of the burned cane fiberboard.
- Atmosphere outside the outer drum (interspersed region).

By changing selected materials over a range of credible compositions, the criticality behavior of the 9971 package array has been determined for credible normal and abnormal conditions.¹

6.3.2 Package Regional Densities

Composition and atomic number densities for all structural materials used in calculations are shown in Table 6-VI. The composition used for dry cane fiberboard has a density of 0.2 gm/cc compared to the minimum specified density of 0.24 gm/cc on engineering drawings¹³. This 16% reduction permits miscellaneous holes to be drilled in the fiberboard with no compromise in safety. This reduction in density increased K_{eff} in calculations by a small amount.

Composition and atomic number densities for 100 Wt% ²³⁵U enrichment UO₃-water mixtures used in the single package analysis are shown in Table 6-VII.

Composition and atomic number densities for 80 Wt% and 100 Wt% ^{235}U enrichment UO_3 -air(void)-water(6 Wt%) mixtures used in the damaged and undamaged array analyses are shown in Table 6-VIII.

Table 6-VI
Composition Of Structural Materials Used In 9971
Analysis

Container Materials

MATERIAL	DENSITY (G/CM3)	ISOTOPE	WT%	ATOMS/B-CM
Stainless Steel	7.895	C	0.08	3.1691E-04
		Cr	18.01	1.6471E-02
		Mn	2.00	1.7321E-03
		Fe	70.90	6.0360E-02
		Ni	8.01	6.4834E-03
		Si	1.00	1.6940E-03
Dry Air	0.0012	N	77.791	4.013E-05
		O	22.209	1.003E-05
Neoprene Rubber	1.229	C	54.265	3.3438E-02
		Cl	40.043	8.3595E-03
		H	5.692	4.1795E-02
Buna-N Rubber	0.978	C	78.463	3.9484E-02
		N	13.072	5.4966E-03
		H	8.465	4.9462E-02

Plastic Materials

MATERIAL	DENSITY (G/CM3)	ISOTOPE	WT%	ATOMS/B-CM
Polypropylene	0.90	C	85.628	3.8848E-02
		H	14.372	7.7696E-02
Polyethylene (Medium Density)	0.925	C	85.628	3.9927E-02
		H	14.372	7.9854E-02
Polyethylene (High Density)	0.95	C	85.628	4.1010E-02
		H	14.372	8.2012E-02

Water

MATERIAL	DENSITY (G/CM3)	ISOTOPE	WT%	ATOMS/B-CM
Full Density	0.99820	O	88.1	3.3369E-02
		H	11.19	6.6738E-02
10% Density	0.09982	O	88.1	3.3369E-03
		H	11.19	6.6738E-03
1% Density	0.009982	O	88.1	3.3369E-04
		H	11.19	6.6738E-04

Normal Cane Fiberboard

MATERIAL	DENSITY (G/CM3)	ISOTOPE	WT%	ATOMS/B-CM
Dry	0.20	O	49.337	3.7141E-03
		C	44.446	4.4569E-03
		H	6.217	7.4282E-03
20 Wt% Water	0.25	O	57.234	5.3971E-03
		C	35.555	4.4569E-03
		H	7.211	1.0772E-02
40 Wt% Water	0.33	O	65.126	8.7109E-03
		C	26.668	4.4569E-03
		H	8.206	1.6342E-02
60 Wt% Water	0.50	O	73.021	1.3743E-02
		C	17.778	4.4569E-03
		H	9.201	2.7495E-02
80 Wt% Water	1.0	O	80.915	3.0457E-02
		C	8.889	4.4569E-03
		H	10.195	6.0914E-02

Burned Cane Fiberboard

MATERIAL	DENSITY (G/CM3)	ISOTOPE	WT%	ATOMS/B-CM
0.5X Normal	0.049585	C	100	2.4493E-03
Normal Density	0.0997	C	100	4.9986E-03
2X Normal	0.1994	C	100	9.9972E-03
4X Normal	0.3988	C	100	1.9994E-02

Table 6-VII
Composition Of UO₃-Water Mixtures
Used In 1991 Single Package Analysis

Uranium in UO₃ Assumed 100% Enrichment ²³⁵U

MIXTURE	DENSITY (G/CC)	WT% ²³⁵ U	WT% O	WT% H
1W	4.4445	74.732	24.148	1.120
2W	4.1442	73.163	25.506	1.331
3W	3.7983	71.049	27.335	1.616
4W	3.4968	68.865	29.225	1.910
5W	3.0658	64.997	32.571	2.432
6W	2.6370	59.894	36.987	3.119
7W	2.2906	54.378	41.760	3.862
8W	1.8598	44.649	50.178	5.173
9W	1.5170	32.959	60.292	6.749
10W	1.2576	19.879	71.610	8.511

Mixture Number Densities (Atoms/B-cm)

MIXTURE	²³⁵ U	O	H
1W	8.5102E-03	4.0398E-02	2.9735E-02
2W	7.7684E-03	3.9785E-02	3.2960E-02
3W	6.9145E-03	3.9080E-02	3.6673E-02
4W	6.1699E-03	3.8465E-02	3.9911E-02
5W	5.1056E-03	3.7586E-02	4.4539E-02
6W	4.0466E-03	3.6712E-02	4.9143E-02
7W	3.1914E-03	3.6005E-02	5.2862E-02
8W	2.1276E-03	3.5127E-02	5.7487E-02
9W	1.2811E-03	3.4427E-02	6.1168E-02
10W	6.4054E-04	3.3898E-02	6.3953E-02

MIXTURE	UO ₃ (KG.)	H/ ²³⁵ U RATIO
1W	13.0	3.494
2W	13.0	4.243
3W	13.0	5.304
4W	13.0	6.469
5W	13.0	8.724
6W	13.0	12.14
7W	10.25	16.56
8W	6.835	27.02
9W	4.116	47.75
10W	2.058	99.84

TABLE 6-VIII
Composition Of UO₃-Air(Void)-Water Mixtures
Used In Damaged 9971 Array Analysis

Uranium in UO₃ at 80 and 100 Wt% ²³⁵U Enrichments,
6 Wt% Water

Uranium in UO₃ Enriched to 80 Wt.% ²³⁵U

MIXTURE	DENSITY	WT% U	WT % O	WT% H
42EW	4.2553	78.080	21.249	0.671
43EW	3.7234	78.080	21.249	0.671
44EW	3.2586	78.080	21.249	0.671
45EW	3.0196	78.080	21.249	0.671
46EW	2.6596	78.080	21.249	0.671
47EW	2.1277	78.080	21.249	0.671

Uranium in UC₃ Enriched to 100 Wt.% ²³⁵U

48EW	4.2553	78.060	21.269	0.671
49EW	3.7234	78.060	21.269	0.671
50EW	3.2586	78.060	21.269	0.671
51EW	3.0196	78.060	21.269	0.671
52EW	2.6596	78.060	21.269	0.671
53EW	2.1277	78.060	21.269	0.671

Table 6-VIII (CONTINUED)
Composition Of UO₃-Air (Void)-Water Mixtures
Used In Damaged 9971 Array Analysis

Mixture Number Densities (Atoms/B-cm)

MIXTURE	²³⁴ U	²³⁵ U	²³⁶ U
42EW	8.9340E-05	6.8103E-03	8.3233E-04
43EW	7.8173E-05	5.9590E-03	7.2829E-04
44EW	6.8414E-05	5.2151E-03	6.3737E-04
45EW	6.3396E-05	4.8326E-03	5.9062E-04
46EW	5.5838E-05	4.2564E-03	5.2020E-04
47EW	4.4671E-05	3.4052E-03	4.1617E-04
48EW		8.5105E-03	
49EW		7.4467E-03	
50EW		6.5550E-03	
51EW		6.0392E-03	
52EW		5.3192E-03	
53EW		4.2554E-03	

MIXTURE	²³⁸ U	O	H	H/ ²³⁵ U	RATIO
42EW	7.6791E-04	3.4034E-02	1.7070E-02		2.506
43EW	6.7192E-04	2.9780E-02	1.4936E-03		2.506
44EW	5.8804E-04	2.6062E-02	1.3071E-03		2.506
45EW	5.4491E-04	2.4151E-02	1.2113E-02		2.506
46EW	4.7994E-04	2.1271E-02	1.0669E-02		2.506
47EW	3.8396E-04	1.7017E-02	8.5349E-03		2.506
48EW		3.4066E-02	1.7069E-02		2.006
49EW		2.9808E-02	1.4936E-03		2.006
50EW		2.6239E-02	1.3147E-03		2.006
51EW		2.4174E-02	1.2113E-02		2.006
52EW		2.1292E-02	1.0669E-02		2.006
53EW		1.7034E-02	8.5350E-03		2.006

6.4 CRITICALITY CALCULATION

6.4.1 Calculation Method

The single package analysis and the array analyses were based on calculated results from the multi-group Monte Carlo criticality code **KENO-IV/CG**¹⁴ using the 16 energy-group Hansen-Roach cross section library¹⁵. Mixture cross sections were prepared using the **HRXN**¹⁶ module of the **KOKO**¹⁷ system. These computer codes were chosen because of their ability to accurately model the geometry of the problem, and because they have been extensively validated against more than 500 critical experiments with a range of ²³⁵U enrichments using the Hansen-Roach cross section library. The validation will be discussed in Section 6.5.

6.4.2 Fuel Loading Optimization

The optimum loading of the 9971 package is that fuel content and configuration that corresponds to the highest value of the reactivity coefficient (K_{eff}). This information has been determined¹, and is here summarized for single package and array analyses.

In the single package analysis, the UO₃-water mixture was varied over a range corresponding to water weight fractions from 0.10 to 0.76. The H/²³⁵U atom ratios range from 3.5 to 100 for the 100 Wt% ²³⁵U enrichment in these calculations. The maximum reactivity for UO₃-water mixtures has been determined¹ which corresponded to the optimum H/²³⁵U atom ratio and the optimum UO₃ loading for the single inner package.

In the previous undamaged and damaged array analyses¹ the effects of UO₃ distribution in the bottle and material composition in regions of the package were examined. The changes included the following:

- Changing the hydrogenous packing material inside the inner container.
- Changing the hydrogen content in the normal cane fiberboard.
- Changing the hydrogen content in the interspersed atmosphere between packages.
- Changing the hydrogen content in the atmosphere internal to the package external to the inner container.
- Changing the composition of burned cane fiberboard.

The optimum condition for the highest reactivity coefficient (K_{eff}) for the damaged package is obtained with the following conditions (Assuming two bottles of UO_3 product in each package):

- Each bottle loaded with 6.5 Kg. dry UO_3 at 100 Wt.% enrichment ^{235}U and 6 Wt% water added (6.915 Kg. bulk UO_3 product mass).
- Dry air or void interspersed between packages in the array.
- Dry cane fiberboard material in the package.
- Dry air or void with no hydrogenous packing materials in the inner container.
- Low density carbon material, dry air, or void in the burned cane fiberboard region.

Under normal shipping conditions the undamaged 9971 package is subcritical with a safety margin of at least 0.14 in K_{eff} with two bottles containing 13.0 Kg. of UO_3 -water mixture with 100 Wt% ^{235}U enrichment and 6 Wt% water.

6.4.3 Criticality Results

6.4.3.1 Single Package Analysis

Calculated results for the single inner container analysis are shown in Table 6-IX, and Figure 6-6. The maximum reactivity coefficient (K_{eff}) occurs at a package loading of 6.835 Kg. of UO_3 product fully water saturated. This occurs because the optimum $H/^{235}U$ is achieved at a value that requires water to replace some of the UO_3 product. Two effects are occurring in the calculations shown in Table 6-IX and Figure 6-6:

1. The reactivity coefficient (K_{eff}) increases with increasing $H/^{235}U$ atom ratio.
2. The reactivity coefficient (K_{eff}) decreases with decreasing ^{235}U content in the package.

It is apparent from the results that the first effect is most important for this package.

The calculated results demonstrate that the single inner package loaded with optimum quantity of UO_3 and under optimum water flooding and water reflection conditions is subcritical with a minimum safety margin of 0.155 in K_{eff} .

Table 6-IX

Results For 9971 Single Package Analysis

13 Kg. Dry UO₃ Fully Water Flooded
50 Cm. Water Reflected Inner Package

MIXTURE	UO ₃ (KG/BOT.)	CALCULATED K _{eff} ¹	K _{eff} BIAS ²	MAX. K _{eff} ³
1W	6.5	0.70886±0.00417	+0.030	0.751
2W	6.5	0.71912±0.00435	+0.030	0.762
3W	6.5	0.73848±0.00487	+0.030	0.783
4W	6.5	0.76285±0.00464	+0.030	0.807
5W	6.5	0.76919±0.00540	+0.030	0.815
6W	6.5	0.79509±0.00481	+0.030	0.840
7W	5.125	0.79246±0.00533	+0.030	0.838
8W	3.4175	0.80029±0.00495	+0.030	0.845
9W	2.058	0.78956±0.00499	+0.030	0.835
10W	1.029	0.75689±0.00525	+0.030	0.803

- 1 - Uncertainties are one standard deviation (67% Confidence).
- 2 - H. K. Clark, "Subcritical Limits for ²³⁵U Systems", Nuc. Sci. & Engr. Vol 81 (1982).
- 3 - Max. K_{eff} = Calculated K_{eff} + 3 Std. Dev. + K_{eff} Bias
Max. K_{eff} cannot exceed 0.95 to assure a minimum safety margin of 0.05 in K_{eff}.

Figure 6-6. Results For 9971 Single Package Analysis (REF: TABLE 6-IX)

6.4.3.2 Array Analyses

Several sets of calculations were performed to determine the optimum reactivity configuration of the undamaged and damaged 9971 package.

6.4.3.2.1 Mass Limit For Uniform Distribution Of UO_3 In Bottles

Calculations were performed to determine the subcritical margin for a range of mass loading of UO_3 in the container. Both the infinite array of undamaged containers and a cubic array of 250 damaged containers are subcritical by a minimum safety margin of at least 0.05 for a specified loading of 13.0 Kg. UO_3 at 100 Wt% ^{235}U enrichment. For this condition with 6 Wt% water, the actual safety margin is 0.25 for the infinite undamaged array and 0.30 for the finite cubic array of 256 damaged packages. The calculations are summarized in Table 6-X and Figure 6-7.

6.4.3.2.2 Damaged Finite Array Size Limit

The damaged 9971 shipping package with a specified loading of 13.0 Kg. UO_3 at 80 Wt.% ^{235}U enrichment was used in a finite array of packages closely reflected with water, and with optimum interspersed moderation. The arrays were sized to approximate a cuboid using the dimensions of the 9971 shipping package, $2R/H=0.5$. Packages were stacked with twice the number along the x and y axes as in the z axis to approximate a cubic array which is the most reactive credible arrangement for an accident condition.

The conclusion from these calculations is that the damaged array remains subcritical up to two thousand (2000) packages in a cubic arrangement at 80 Wt% ^{235}U enrichment. These calculations are summarized in Table 6-XI and Figure 6-8.

The specific standards for a Fissile Class I package⁴ require two hundred fifty (250) damaged packages be subcritical if stacked together in any arrangement, closely reflected on all sides of the stack by water, and with optimum interspersed hydrogenous moderation. The IAEA regulations require an infinite array of damaged packages to remain subcritical. An infinite array of damaged packages will not remain subcritical unless the UO_3 loading is limited to about 20 percent of the container capacity. The 9971

shipping package does not qualify under IAEA regulations for a transportation index of zero (0) at the required loading.

Table 6-X
Results For 9971 Package Array Analysis
Mass Limit for Uniform Distribution of UO₃ in Bottles

Infinite Undamaged Array
100 Wt% ²³⁵U, 6 Wt% Water

MIXTURE	UO ₃ (KG) /BOT.	CALCULATED Keff ¹	Keff BIAS ²	MAX. Keff ³
48EW	9.15	0.82086±0.00415	+0.030	0.863
49EW	8.0	0.79168±0.00409	+0.030	0.834
50EW	7.0	0.76180±0.00406	+0.030	0.804
51EW	6.5	0.70609±0.00391	+0.030	0.748

Finite Cubic Array, 256 Damaged Packages

100 Wt% ²³⁵U, 6 Wt% Water

MIXTURE	UO ₃ (KG) /BOT.	CALCULATED Keff ¹	Keff BIAS ²	MAX. Keff ³
48EW	9.15	0.77910±0.00472	+0.030	0.823
49EW	8.0	0.72755±0.00393	+0.030	0.769
50EW	7.0	0.69299±0.00472	+0.030	0.737
51EW	6.5	0.65279±0.00442	+0.030	0.696
52EW	5.75	0.61699±0.00426	+0.030	0.660
53EW	4.6	0.56047±0.00387	+0.030	0.602

80 Wt% ²³⁵U, 6 Wt% Water

MIXTURE	UO ₃ (KG) /BOT.	CALCULATED Keff ¹	Keff BIAS ²	MAX. Keff ³
42EW	9.15	0.71444±0.00516	+0.030	0.760
43EW	8.0	0.67545±0.00415	+0.030	0.718
44EW	7.0	0.63388±0.00411	+0.030	0.676
45EW	6.5	0.60342±0.00414	+0.030	0.645
46EW	5.75	0.57094±0.00390	+0.030	0.613
47EW	4.6	0.50878±0.00398	+0.030	0.551

100 Wt% ²³⁵U, Dry

MIXTURE	UO ₃ (KG) /BOT.	CALCULATED Keff ¹	Keff BIAS ²	MAX. Keff ³
1A	9.15	0.65242±0.00465	+0.030	0.696
2A	8.0	0.61558±0.00344	+0.030	0.656
3A	7.0	0.58088±0.00392	+0.030	0.623
4A	6.5	0.53947±0.00339	+0.030	0.580
5A	5.75	0.53381±0.00371	+0.030	0.575
6A	4.6	0.48814±0.00383	+0.030	0.530

Figure 6-7. Uniform Distribution Of UO₃ In Bottles
(REF: TABLE 6-X)

Table 6-XI

Damaged Finite Array

13.0 Kg. UO_3 , 6 Wt% Water
30.5 Cm. Water Reflected on All Sides

80 Wt% ^{235}U

MIXTURE	ARRAY SIZE	CALCULATED Keff ¹	Keff BIAS ²	MAX. Keff ³
42EW	16 x 16 x 8	0.86737±0.00402	+0.030	0.909
42EW	14 x 14 x 7	0.82005±0.00420	+0.030	0.863
42EW	12 x 12 x 6	0.76214±0.00397	+0.030	0.804
42EW	10 x 10 x 5	0.68289±0.00373	+0.030	0.724
42EW	8 x 8 x 4	0.60342±0.00414	+0.030	0.646
42EW	6 x 6 x 3	0.51151±0.00382	+0.030	0.553
42EW	4 x 4 x 2	0.40890±0.00327	+0.030	0.449
42EW	2 x 2 x 1	0.29805±0.00319	+0.030	0.338
42EW	1 x 1 x 1	0.25107±0.00300	+0.030	0.290

- 1 - Uncertainties are one standard deviation (67% Confidence).
- 2 - H. K. Clark, "Subcritical Limits for ^{235}U Systems", **Nuc. Sci. & Engr. Vol 81** (1982)
- 3 - Max. Keff = Calculated Keff + 3 Std. Dev. + Keff Bias
Max. Keff cannot exceed 0.95 to assure a minimum safety margin of 0.05 in Keff.

PACKING MATERIAL INSIDE INNER CONTAINER

NORMAL CANE FIBERBOARD

INTERSPERSED MODERATION

INTERNAL TO PACKAGE EXTERNAL TO INNER CONTAINER

NO HYDROGENOUS MATERIAL

DRY

VOID

DRY AIR

Figure 6-8. Finite Cubic Array Of Damaged Packages (REF: TABLE 6-XI).

6.4.3.2.3 Alternative Materials For Burned Cane Fiberboard In Damaged Infinite Array

Calculations have been performed¹ which substituted other materials for burned cane fiberboard in the damaged infinite array. The package was assumed to be at optimum condition for all other parameters including 6 Wt% water content and 80 Wt% ²³⁵U enrichment. Results of these calculations demonstrate that a minimum safety margin of at least 0.057 in K_{eff} is retained for any of these conditions.

6.4.3.2.4 O-Ring Material Effects

Comparison was made of the different rubber compositions to dry air in the o-ring channels for two UO₃ compositions in the infinite damaged array.¹ These results indicate that changes in K_{eff} are all in the last significant digit and are of small magnitude. These results are within the scatter of the stochastic sampling performed by the **KENO-IV/CG** and represent random variations about a mean. There is no indication of any significant difference if one uses dry air, neoprene rubber, or buna-N rubber in o-ring channels in the calculations.

6.4.4 Displacement Of Inner Container In Damaged Array

All calculations of the damaged array assumed the inner package was located at or near its nominal position, and the spacing of the full package was assumed the same as for the undamaged array. The basis of these assumptions will be examined.

Assuming the spacing of packages in the damaged array is the same as for the undamaged array should produce slightly higher calculated K_{eff} values. The damaged package will have dents and bends following the drop test, and thus should not be able to be stacked as uniformly or as closely as the undamaged package array. A higher package spacing in the damaged array will produce slightly lower calculated K_{eff} values.

No calculations were performed with the inner container displaced from its normal position (axially only for the undamaged array, and in multiple directions for the damaged array) for the following reasons:

- The primary interaction between packages in the infinite array is the radial direction (more surface area than axially). Displacing the inner package axially for the undamaged array would tend to decrease the calculated reactivity by a very small amount because of reduced radial interaction with little change in the axial interaction (it might increase in the direction of displacement, but will decrease in the opposite direction).
- Displacing the entire inner contents of damaged packages will permit adjacent inner packages to be moved closer. However, this will also increase the spacing from other inner packages. This effect has been examined for a similar package¹⁸ (Type 9966) and for waste drums¹⁹ and found to decrease the calculated reactivity in all cases compared to inner package nominal position reactivities.

6.4.5 Use of Smaller or Larger Plastic Bottles

The bottles used in this evaluation were nominal 2.0-Liter plastic wide-mouth containers. Specifications for these bottles¹¹ list brim capacities of 2.14 Liters (HD Polyethylene) and 2.2 Liters (Polypropylene), although measurement of actual bottles gives higher volumes (less plastic). Use of bottles of smaller volume is unquestionably safer because product density must be higher (for a 6.5 Kg. dry loading), or mass of dry product must decrease, both producing a lower reactivity (K_{eff}) in all calculations shown previously.¹

Bottles of slightly higher volume than appear in this evaluation may be used. A bottle volume limit of 2.4 liters is justified by examination of the results that appear in the evaluation.¹ Increasing the permitted bottle volume beyond 2.4 liters does not appear possible within Fissile Class I restrictions. All bottles are assumed to have similar shape to the bottle used in this evaluation.

6.5 CRITICALITY BENCHMARK EXPERIMENTS

The **KENO-IV/CG** Monte Carlo criticality code has been extensively validated using the Hansen-Roach cross section library for a range of uranium enrichments, reflection conditions and interacting unit arrays that more than adequately describe the conditions of this evaluation. These validation studies are documented in References 20 through 27, and only a summary of the pertinent results of these studies will be presented here.

For uranium solutions or wet uranium powders the correlated bias of the **KENO-IV/CG** calculation of more than 500 experiments was shown to vary as a function of the H/²³⁵U atom ratio in the uranium-water mixture. The largest bias was found to occur for H/²³⁵U atom ratios in the range from 50 to 125; the nominal bias value being +0.030 (an experiment with $K_{eff} = 1$ is calculated to be 0.970).

The Monte Carlo criticality calculation of K_{eff} in **KENO-IV/CG** is based on a stochastic sampling technique. The errors of the calculation are based on averaging the K_{eff} values calculated in several batches of neutron histories, and expressing the error in a standard deviation assuming a gaussian error distribution function. The confidence level (percentage of total area under the error distribution function for a specified standard deviation range) for various values of standard deviation is shown in Table 6-XII.

Table 6-XII

<u>Error Range</u>	<u>Confidence Level</u>
Value $\pm$ 1 Std. Dev.	68.26%
Value $\pm$ 2 Std. Dev.	95.46%
Value $\pm$ 3 Std. Dev.	99.74%

To use the data in Table 6-XII a Maximum K_{eff} value is defined which expresses the worst possible value of K_{eff} credible from a value computed by **KENO-IV/CG**. This Max. K_{eff} is defined as:

$$\text{Max. } K_{eff} = \text{Calculated } K_{eff} + K_{eff} \text{ Bias} + 3 \text{ Std. Dev.}$$

By its definition this Max. K_{eff} places delayed criticality at a value of 1.0, and prompt criticality at about 1.01. In addition, this definition increases the confidence level to 99.87% because all errors are assumed additive only in the positive direction, thus eliminating the 0.13% area in the negative direction.

In all tables of results in Section 6.4 a Maximum K_{eff} value is assigned to each calculation. This is an estimate of the worst possible value of K_{eff} credible for each calculation. The **KENO-IV/CG** value of Standard Deviation is used to assign the error due to the stochastic sampling in the code. The K_{eff} Bias taken from validated correlations in Reference 21 is a maximum bias of 0.03. In addition, a margin of 0.05 in Max. K_{eff} is an additional required margin to assure safety from unforeseen circumstances. The highest permitted value of Max. K_{eff} is 0.95 which provides additional assurance of criticality safety for shipments in the 9971 package.

6.6 REFERENCES

1. Finch, D. R., **Nuclear Criticality Safety Evaluation of SRS 9971 Shipping Package**, WSRC-TR-91-445, July 1991.
2. American National Standards Institute, **Nuclear Criticality Safety in Operations with Fissile Materials Outside Reactors**, er 3, 1983, Reaffirmed November 30, 1988.
3. U.S. Department of Energy, **Safety of Nuclear Facilities**, USDOE Order 5480.5, September 23, 1986.
4. U.S. Code of Federal Regulations, **Part 71 - Packaging and Transportation of Radioactive Material**, 10CFR71, Paragraphs
5. U.S. Code of Federal Regulations, **Part 173 - Shippers - General Requirements for Shipments and Packagings**, 49CFR173, Paragraph 173.455, November 1, 1987.
6. **Regulations For The Safe Transport of Radioactive Materials - 1985 Edition**, Safety Series No. 5. STI/PUB/607 (Vienna: IAEA) (1985).
7. Letter D. A. Reed, Martin-Marietta Energy Systems, Inc. to D. R. Finch, Westinghouse Savannah River Company, **Typical Densities of Y-12 Enriched Uranium Trioxide**, May 31, 1991, See Appendix A.
8. Letter Patrick Adamson, Martin-Marietta Energy Systems, Inc. to James A. Purcell, Westinghouse Savannah River Company, **Summary of UO₃ Moisture Study Work**, March 28, 1991, See Appendix A.
9. U.S. Department of Energy, Savannah River Site, Separations/USF 221-H, USF-16, Engineering Drawings:

<u>Title</u>	<u>EED Drawing Number</u>
9971 Shipping Package -	
- Containment Vessel, Body, Fab.	W2012410 Rev. 0
- Containment Vessel, Lid, Fab.	W2012411 Rev. 0

10. U.S. Department of Energy, Savannah River Site,
Separations/USF 221-H, USF-16, Engineering Drawings:

<u>Title</u>	<u>EED Drawing Number</u>
9971 Shipping Package -	
- General Notes	W2012407 Rev. 0
- Final Assembly	W2012408 Rev. 0
- Fiberboard Cradle, Assembly	W2012409 Rev. 0
- Fiberboard Cover, Assembly	W2012412 Rev. 0
- Fiberboard Cradle, Support Plate	W2012413 Rev. 0
- Fiberboard Cover, Fiberboard Disks	W2012414 Rev. 0
- Fiberboard Cover, Stainless Disk	W2012415 Rev. 0
- Stainless Steel Drum, Assembly	W2012417 Rev. 0

11. Nalge Company, **Nalgene Labware 1990**, Rochester, NY,
(1990) Pgs. 12, 167, 173, 179, See Appendix A.

12. R. S. Maurer, Criticality Computation for the 9971 USF
Packinging, SRT-PTG-92-0099, Aug. 4, 1992.

13. U.S. Department of Energy, Savannah River Site,
Separations/USF, 221-H, USF-16, Engineering Drawings:

<u>Title</u>	<u>EED Drawing Number</u>
--------------	-------------------------------

9971 Shipping Package - General Notes	W2012407 Rev. 0
---------------------------------------	-----------------

14. J. T. West, III, et al., **KENO-IV/CG, The
Combinatorial Geometry Version of The KENO Monte
Carlo Criticality Safety Program**, NUREG/CR-0709, Oak
Ridge National Laboratory, Oak Ridge, TN, September
1979.

15. G. E. Hansen and W. H. Roach, **Six and Sixteen Group
Cross Sections For Fast and Intermediate Critical
Assemblies**, LAMS-2543, Los Alamos National Laboratory,
Los Alamos, NM, 1961.

16. H. K. Clark, **JOSHUA Nuclear Criticality Safety
Modules**, DPSTM-86-700-3, Section 3, Savannah River
Laboratory, Aiken, SC, 1986.

17. H. K. Clark, **JOSHUA Nuclear Criticality Safety
Modules**, DPSTM-86-700-3, Section 7, Savannah River
Laboratory, Aiken, SC, 1986.

18. **Safety Analysis Report for Packaging - SRP Type 9966 Package**, DPSPU-83-124-1, Savannah River Plant, Aiken, SC, 1984.
19. W. A. Blyckert and R. D. Carter, **Criticality Parameters of 55-Gallon Waste Drum Arrays**, RHO-SA-183, Rockwell Hanford Operations, Richland, WA, November 7, 1980.
20. H. K. Clark, **Subcritical Limits For ^{235}U Systems**, DPST-80-415, Savannah River Laboratory, Aiken, SC, 1981.
21. H. K. Clark, "Subcritical Limits for ^{235}U Systems", *Nuc. Sci. & Engr.* 81, 1982.
22. H. K. Clark, **Correlations of KENO with Critical Experiments with Interacting Units**, DPST-82-317, Savannah River February 12, 1982.
23. H. K. Clark, **Correlations with Critical Experiments with Concrete-Reflected Systems**, DPST-82-428, Savannah River Laboratory, Aiken, SC, March 25, 1982.
24. H. K. Clark, **Correlations with Critical Experiments with Cylinders Surrounded Laterally By Various Thicknesses of Water**, DPST-84-428, Savannah River Laboratory, April 6, 1984.
25. H. K. Clark, **Correlations with MARK 16 Experiments**, DPST-83-1025, Savannah River Laboratory, Aiken, SC, November 29, 1983.
26. H. K. Clark, **Correlations with Critical Experiments with Cadmium and Thick Steel Reflectors**, DPST-84-383, Savannah River Laboratory, Aiken, SC, April 11, 1984.
27. H. K. Clark, **Miscellaneous Correlations**, DPST-84-714, Savannah River Laboratory, Aiken, SC, August 22, 1984.

END

**DATE
FILMED**

6 / 21 / 93