**Idaho
National
Engineering
Laboratory**

*Managed
by the U.S.
Department
of Energy*

EGG-GEO-10158
March, 1992

RECEIVED
APR 27 1992

**GWScreen: A SEMI-ANALYTICAL MODEL
FOR ASSESSMENT OF THE GROUNDWATER
PATHWAY FROM SURFACE OR BURIED
CONTAMINATION: THEORY AND USER'S
MANUAL**

Arthur S. Rood

*Work performed under
DOE Contract
No. DE-AC07-76ID01570*

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This book was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights. References herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

EGG-GEO--10158

DE92 012532

**GWSCREEN: A SEMI-ANALYTICAL MODEL FOR ASSESSMENT OF
THE GROUNDWATER PATHWAY FROM SURFACE OR BURIED CONTAMINATION:
THEORY AND USER'S MANUAL**

Arthur S. Rood

March, 1992

Idaho National Engineering Laboratory
EG&G Idaho Inc.
PO Box 1625
Idaho Falls ID 83415

Prepared for the
U.S. Department of Energy
Office of Environmental Restoration and Waste Management
Under DOE Field Office, Idaho
Contract DE-AC07-76ID01570

MASTER

ABSTRACT

GWSCREEN was developed for assessment of the groundwater pathway from leaching of radioactive and non radioactive substances from surface or buried sources. The code was designed for implementation in the Track I and Track II assessment of Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) sites identified as low probability hazard at the Idaho National Engineering Laboratory (DOE, 1991).

The code calculates the limiting soil concentration such that regulatory contaminant levels in groundwater are not exceeded. The code uses a mass conservation approach to model three processes: Contaminant release from a source volume, contaminant transport in the unsaturated zone, and contaminant transport in the saturated zone. The source model considers the sorptive properties and solubility of the contaminant. Transport in the unsaturated zone is described by a plug flow model. Transport in the saturated zone is calculated with a semi-analytical solution to the advection dispersion equation for transient mass flux input.

One of the limitations of this code is that it does not deal with radioactive progeny. Radioactive progeny were ignored because very few of the sites identified for assessment contained radionuclides with long decay chains that would have significant ingrowth of decay progeny.

GWSCREEN has shown comparable results when compared against other codes using similar algorithms and has also been shown to provide bounding estimates of groundwater concentrations when compared to results from complex numerical codes. This code was designed for assessment and screening of the groundwater pathway when field data is limited. It was not intended to be a predictive tool.

ACKNOWLEDGMENTS

The author would like to thank Dr. James McCarthy and Ms. Christine B. Lee for their comments, suggestions and overall technical input and support during the development of this code.

TABLE OF CONTENTS

ABSTRACT	ii
1. INTRODUCTION	1
2. METHODOLOGY	2
2.1 SOURCE TERM MODELING	2
2.2 UNSATURATED ZONE MODEL	11
2.3 SATURATED ZONE MODEL	13
2.4 LIMITING SOIL CONCENTRATION	17
3. CODE IMPLEMENTATION	22
3.1 COMPUTATIONAL METHODS	23
3.2 CONTAMINANT AND SITE SPECIFIC DATA FILE	29
3.3 PROGRAM FLOW EXECUTION	34
3.4 BENCHMARKS WITH OTHER CODES	36
4. REFERENCES	46
APPENDIX A: GWSCREEN SAMPLE PROBLEMS	A-1
APPENDIX B: GWSCREEN CODE LISTING	B-1

FIGURES

1.	GWSCREEN conceptual model of the source volume, unsaturated zone and groundwater model.	4
2.	Volumetric moisture content vs hydraulic conductivity for vesicular basalt at the INEL. van Genuchten parameters, α and n were obtained from Baca (1992).	7
3.	Volumetric moisture content vs hydraulic conductivity for sediment at the INEL. van Genuchten parameters, α and n were obtained from Baca (1992).	9
4.	Solutions to Equation 24 for a steady state unit release rate using different numbers of Gaussian Quadrature zero-weighting pairs. The solution using a Simpsons rule integration routine is included for comparison.	25
5.	Solutions to Equation 24 using a 12 point Gaussian Quadrature routine for a steady state unit release rate for different Peclet numbers.	27
6.	Flow chart for the GWSCREEN code.	35
7.	GWSCREEN sample problem input file. The parameters names are listed to the right of the parameter values.	37
8.	Comparison of groundwater concentrations calculated with GWSCREEN and GRDFLX for a Pu-239 source.	38
9.	Conceptual model for benchmark problems #2 and #3.	41
10.	PORFLO-3 and GWSCREEN mass flux at the unsaturated zone-aquifer interface as a function of time for a contaminant with an infinite half-life.	43
11.	PORFLO-3 and GWSCREEN mass flux at the unsaturated zone-aquifer interface as a function of time for a contaminant with a four year half-life.	44
12.	Normalized peak concentration vs Peclet number for contaminants for contaminants with different half-life/contaminant transit time ratios.	45

TABLES

1. A brief description of the GWSCREEN subroutines. 23
2. Input file for contaminant and site specific data. NOTE: Variables given the same line number must appear in the same order on the line as presented in this table. 30
3. Definition of variables in the GWSCREEN user defined input files. . . 32
4. Parameter values for Benchmark problem #2 and #3. 40

1. INTRODUCTION

Multimedia exposure assessment of hazardous chemicals and radionuclides requires all pathways of exposure be investigated. In the assessment process, limited data is often encountered and the primary purpose for performing initial screening is to identify priority contaminants and data needs. This process is accomplished by using simplified models that make best use of the available data and conservative assumptions. The GWSCREEN code was designed for initial screening calculations of releases from surficial and buried contamination to the groundwater. The modeling approach used in GWSCREEN is a mass balance approach that has its roots in the methodology proposed by the Nuclear Regulatory Commission (NRC) (Codell, 1982 and Kozak, 1989). This methodology has also been employed in a number of other assessment codes including the Remedial Action Priority System (Whelan, 1987) and DECHEM (Killogh, 1991). The groundwater model selected for this methodology has been used at the Idaho National Engineering Laboratory (INEL) for scoping and assessment purposes (Rood, 1989), and has been shown to give reasonable results when calibrated to measured data. Leaching is modeled using the approach described by Baes and Sharp (1983) and implemented in the RESRAD (Gilbert, 1989) code. The model also considers the case where leaching of the contaminant is governed by its solubility limit.

Code output includes the limiting soil concentration that would result in the maximum groundwater concentrations that would not exceed regulatory criteria limits for groundwater. Also groundwater concentration as a function of time may be calculated. This model only considers drinking water consumption and does not include contaminant transfer to food products resulting from irrigation with contaminated water. However, these pathways may be taken into account by adjusting the water consumption rate. Both radiological and non-radiological contaminants are considered in this code. Non-radiological assessment includes both carcinogenic and non-carcinogenic criteria. Carcinogenic assessment is based on a user input risk value. Non-carcinogen criteria is based on the reference dose (RfD). Radiological assessments are based on an annual effective dose equivalent limit for

drinking water ingestion. Some radiological and non-radiological (tritium and ^{226}Ra) contaminants are regulated by maximum contaminant limits and the code has been designed to calculate limits based on user input maximum contaminant limits.

This model was not intended to be a predictive tool, rather it was intended to provide a bounding estimate of limiting soil concentrations that, after leaching, would not result in groundwater concentrations that exceed regulatory criteria limits.

2. METHODOLOGY

There are three primary models employed in GWSCREEN (Figure 1). They are the source term model, the unsaturated zone mass transport model and the saturated zone (aquifer) mass transport model. These models are linked together by the contaminant flux across model boundaries. For example, the source term model is linked to the unsaturated zone model by the contaminant flux at the source zone - unsaturated zone boundary. Depending on the options selected, groundwater concentrations are calculated for either a unit initial inventory or an initial inventory defined by the user (a value different than 1.0 units of contaminant). If the concentration as a function of time is to be calculated, then the user input inventory is used in the calculation. Otherwise, a unit inventory is assumed. The groundwater concentration from a unit inventory of contaminant in the source volume is used to calculate the limiting soil concentration based on user input groundwater concentration or contaminant intake limits.

2.1 SOURCE TERM MODELING

The source volume is defined in this model as the zone in which contaminants have been observed or are suspected to be present. This zone, in most cases, occupies the volume bounded by the soil surface to some finite depth below the soil surface, but may also include buried waste. Release from the source volume is modeled as a first order leaching process which accounts

for decay and sorption. The contaminant is assumed to be homogeneously mixed in a finite volume and a steady state infiltration rate is assumed. The leaching process is described mathematically by a first order leach rate constant. The differential equation which describes the mass balance of contaminant in the contaminated volume is given by

$$\frac{dQ}{dt} = -(\lambda_L + \lambda_d) Q \quad (1)$$

where λ_d = the decay rate constant (y^{-1})

λ_L = the leach rate constant (y^{-1})

Q = the mass (or activity) in the contaminated volume (g or Ci)

The solution to Equation 1 is

$$Q(t) = Q_0 e^{-(\lambda_L + \lambda_d) t} \quad (2)$$

where Q_0 = the initial mass or activity in the contaminated volume (Ci or g)

t = time (years).

The initial mass or activity in the contaminated volume (Q_0) is given by

$$Q_0 = C_0 \times L \times W \times T \quad (3)$$

where L, W, T = the length, width and thickness of the contaminated volume (m)

C_0 = the initial concentration (g or activity per cubic meter).

CONCEPTUAL MODEL FOR GWSCREEN

Figure 1. GWSCREEN conceptual model of the source volume, unsaturated zone and groundwater model.

The leach rate constant (λ_L) and decay rate (λ_d) constant are given by the following.

$$\lambda_L = \frac{q}{\theta_c R_{dc} T} \quad \lambda_d = \frac{\ln(2)}{T_{1/2}} \quad (4)$$

where q = the net water infiltration rate (m/y)

θ_c = the volumetric moisture content in the contaminated zone (m^3/m^3)

R_{dc} = the retardation factor in the source volume.

$T_{1/2}$ = the contaminant half life (y^{-1})

The leach rate constant was originally described by Baes and Sharp (1983) however, the formulation given in Equation 4 was taken from Gilbert (1989).

The net water infiltration rate (q) is the amount of water that enters the soil per unit time or the Darcy flux. Under steady state condition (no net storage) this can be approximated by

$$I = P - R - E \quad (5)$$

where P = precipitation (m/y)

R = runoff (m/y)

E = evapotranspiration (m/y).

The value q/θ_c represents the pore velocity in the contaminated zone and is based on the unit gradient model which assumes the hydraulic conductivity is equal to the water flux or infiltration rate. Darcy's law states

$$q = K \frac{dH}{dX} \quad (6)$$

where q = the net water flux or net infiltration rate (m/y)

dH/dX = the change in hydraulic head with respect to distance (m/m)

K = the hydraulic conductivity of the contaminated zone (m/y).

In the unit gradient model, $dH/dX = 1.0$, thus, $q = K$. Saturated hydraulic conductivity and the volumetric moisture content differ for different rock types. When a porous media is saturated (i.e. all the pore spaces are filled with water), the volumetric moisture content is equal to the effective porosity of the media. (In this model, the effective porosity is assumed equal to the total porosity.) The volumetric moisture content is related to the effective porosity by the fraction of the pore space that is saturated. The volumetric water content for a given material and a given water flux is usually determined using equations that have been fitted to field data relating suction head to volumetric moisture content and hydraulic conductivity. Curves generated using the van Genuchten (1978) fitting parameters for basalt and surface sediment at the Idaho National Engineering Laboratory (INEL), Radioactive Waste Management Complex (RWMC) are presented in Figures 2 and 3. These materials were characterized in detail by Bishop (1991) and McElroy (1990) and van Genuchten fitting parameters were given by Baca (1992).

The retardation factor in the contaminated zone (R_{dc}) is given by

$$R_{dc} = 1 + \frac{K_{dc} \rho_c}{\theta_c} \quad (7)$$

where K_{dc} = the distribution coefficient in the contaminated zone (ml/g)

ρ_c = the bulk density in the contaminated zone (g/cm³).

The contaminant flux out the bottom of the contaminated volume can now be calculated. The contaminant flux is given by

Figure 2. Volumetric moisture content vs hydraulic conductivity for vesicular basalt at the INEL. van Genchten parameters, α and n were obtained from Baca (1992).

$$q_c(t) = \lambda_L Q(t) \quad (8)$$

where $q_c(t)$ = the contaminant flux out the bottom of the contaminated volume (g or Ci per year).

The concentration of the leachate ($C_{leachate}(t)$) is given by Equation 9.

$$C_{leachate}(t) = \frac{Q(t)}{L \times W \times T \times \theta_c \times R_{dc}} \quad (9)$$

For some contaminants, the initial concentration of the leachate exceeds the solubility limit of the contaminant. In this case, the concentration of the leachate and the mass flux from the source volume will be governed by the solubility limit of the contaminant. The mass balance of the contaminant in the source volume is then given by Equation 10.

$$Q(t) = Q_o e^{-\lambda_d t} - R t \quad (10)$$

where $R = C_{sl} \times q \times L \times W$ (mg/y) (contaminant flux out bottom of source)
 C_{sl} = the solubility limit of the contaminant (mg/m³)

After a period of time, the mass in the source volume is depleted sufficiently to allow for leaching to be controlled by the contaminant sorptive properties and not the solubility limit. The amount of mass in the source volume (Q_{sl}) where leaching by sorptive properties takes over is given by Equation 11.

Figure 3. Volumetric moisture content vs hydraulic conductivity for sediment at the INEL. van Genuchten parameters, α and n were obtained from Baca (1992).

$$Q_{sl} = C_{sl} \times L \times W \times T \times \theta_c R_{ds} \quad (11)$$

For the case where decay is insignificant, the time required (t_{sl}) for the mass in the source compartment to decrease to Q_{sl} is given by Equation 12.

$$t_{sl} = \frac{Q_o - Q_{sl}}{R} \quad (12)$$

When decay is significant, the time required for the mass in the source compartment to decrease to Q_{sl} must be solved numerically.

For radionuclides, total activity in the source volume must be converted to mass so that the quantity of the radionuclide may be related to its solubility limit. The conversion from activity to mass is given by the following.

$$Q_{(mass)} = \frac{Q_{(activity)} (3.7 \times 10^{10} \text{ dps/Ci}) (3.1536 \times 10^7 \text{ s/year}) (MW)}{(\lambda_d) (6.023 \times 10^{23} \text{ atoms/mole})} \quad (13)$$

where $Q_{(mass)}$ = the mass of the radionuclide in the source volume (g)

$Q_{(activity)}$ = the total activity of the radionuclide in the source volume (Ci)

dps = number of nuclear transformations per second

MW = the molecular weight of the radionuclide (g/mole)

Solubility limited releases for radionuclides usually only affects nuclides with large half-lives since little mass is associated with nuclides with a short half-life.

Output from the source model is then given by Equation 8 for releases

not controlled by the contaminants solubility, and by the term, R , in Equation 10 for solubility limited releases. These releases provide the contaminant flux at the boundary between source zone and unsaturated zone.

2.2 UNSATURATED ZONE MODEL

The unsaturated zone is defined in this model as the zone between the base of the source volume and top of the aquifer. The unsaturated zone is assumed to be a homogeneous, isotropic, porous media with constant, unidirectional flow in the vertical (downward) direction. The model allows for differences in the transport properties between the unsaturated zone, source volume and saturated zone. Due to the complexities and inherent uncertainties in modeling unsaturated flow and transport, a simplified plug-flow model was adapted that does not account for dispersion. In the plug flow model, non-sorbing contaminants move with the vertical velocity of the water in the vadose zone. This velocity is calculated assuming the gradient condition as discussed in Section 2.1. This assumption is conservative for contaminants with long half-lives¹ because the maximum flux calculated with the plug-flow model exceeds the maximum flux of a model that includes dispersion (See Benchmarks 2 and 3 in Section 3.4) . The cumulative flux for both models is the same as time approaches infinity. For contaminants with short half-lives², under conditions where the dispersivity is large, the peak flux may actually be larger using a dispersion model as compared to a plug flow model (Seitz et al., 1991) because the contaminant arrives at the receptor sooner resulting in reduced decay time. Dispersivity in the unsaturated zone would not be readily available during the initial groundwater assessment process and since other conservative assumptions, such as increasing the percolation rate and reducing the unsaturated zone thickness, may be assumed to compensate for the effect of dispersion on short half-lived contaminants, dispersion was not considered and the simpler plug-flow model

¹The contaminant half-life is greater than 1/10 the contaminant transit time in the unsaturated zone

² Contaminant half-life is less than 1/10 the contaminant transit time in the unsaturated zone.

was used.

The amount of decay which occurs during transit is a function of the contaminant transit time in the unsaturated zone. The transit time in the unsaturated zone (T_a) is given by

$$T_a = \frac{X_u}{U_u} R_{du} \quad (14)$$

where X_u = the distance from the base of the contaminated zone to the top of the aquifer (m)

U_u = the unsaturated pore velocity (m/y)

R_{du} = the retardation factor in the unsaturated zone

The unsaturated pore velocity (U_u) is given by

$$U_u = \frac{q}{\theta_u} \quad (15)$$

where θ_u = the volumetric water content in the unsaturated zone (m^3/m^3)

The retardation factor (R_{du}) in the unsaturated zone is given by

$$R_{du} = 1 + K_{du} \frac{\rho_u}{\theta_u} \quad (16)$$

where K_{du} = the distribution coefficient in the unsaturated zone (ml/g)

ρ_u = the bulk density in the unsaturated zone (g/cm^3)

The volumetric water content in the unsaturated zone is determined exactly like the volumetric water content in the source volume (See Figures 2 and 3). The fraction of mass or activity that decays during transit from the contaminated zone to the aquifer (f) is given by Equation 17.

$$f = e^{-\lambda_d T_d} \quad (17)$$

The end result of the unsaturated zone model is the contaminant flux to the aquifer (q_a) and is given by Equation 18. It is through the flux term (q_a) that the unsaturated zone and saturated zone models are coupled.

$$q_a = f \lambda_L Q(t) \quad (18)$$

where $Q(t)$ = the mass in the source volume as a function of time (Equation 2 or 10).

2.3 SATURATED ZONE MODEL

The saturated zone model is based on an analytic solution to the advection dispersion equation for contaminants in a saturated porous media. These solutions were originally developed by Codell (1982) and have been used for assessment of radionuclide transport in groundwater. These solutions apply equally as well to non-radiological contaminants. The model contains the following assumptions and limitations:

1. The model uses a cartesian coordinate system (x,y,z) as a frame of reference. The positive x direction is in the direction of flow.
2. The flow is uniform and unidirectional. No sources or sinks are accounted for.

3. The aquifer is modeled as an isotropic, homogeneous porous media of infinite lateral extent and finite thickness.
4. Molecular diffusion is assumed to be negligible
5. The source can be represented by a rectangular area of length L and width W and centered at the origin (0,0,0).
6. The dispersion coefficients remain constant over the domain.
7. Transport is limited to a single specie which may decay or degrade as a function of time. Transport of radioactive progeny is not considered.
8. The contaminant is assumed to move as a dissolved substance. Transport in liquid organic and vapor phases are not considered.
9. Solid and liquid phases are in equilibrium and concentrations are related by the linear sorption coefficient (K_d).
10. The contaminant is assumed to be mixed vertically (z direction) in a zone defined by the length of a typical well screen for a drinking water well.

Assumption 10 states that groundwater concentrations will be averaged (mixed) over the thickness of the well screen. This assumption is reasonable for receptor wells close to the source since contaminants poorly mixed in the vertical direction will be diluted by water drawn over the *entire* well screen interval. For receptor wells located farther downgradient from the source, the estimated concentration will be conservative since the contaminant plume will likely extend to greater depths than the assumed well screen thickness.

Calibration studies at the INEL using the groundwater model described in this document have been performed by Codell (1982) and Rood (1989). Tritium plumes from the Idaho Chemical Processing Plant injection well and the Test

Reactor Area percolation ponds were modeled. The predicted concentration matched measured data reasonably well considering the simplifications and assumptions of the model; however, the results were not as accurate as those made by a finite difference model (Robertson, 1974). The differences were attributed to the ability of the finite difference model to incorporate spatial differences in the flow field. This problem is reduced in this particular application since the hypothetical well to be modeled will be relatively close (approximately 100 m) thereby reducing the effect of spatial variability in the groundwater flow.

The mass balance equation which describes contaminant transport for the stated assumptions is

$$\frac{\partial C}{\partial t} + \frac{U}{R_d} \frac{\partial C}{\partial x} = \frac{D_x}{R_d} \frac{\partial^2 C}{\partial x^2} + \frac{D_y}{R_d} \frac{\partial^2 C}{\partial y^2} - \lambda_d C \quad (19)$$

where C = the concentration (g or Ci per cubic meter)

U = the groundwater pore velocity (m/y)

$D_x D_y$ = the dispersion coefficient in the x and y direction (m^2/y)

R_d = the retardation factor in the aquifer

t = time (years)

x = the distance from the center of the area source to the receptor parallel to groundwater flow (m)

y = the distance from the center of the area source to the receptor perpendicular to groundwater flow (m).

The retardation factor in the aquifer is given by

$$R_d = 1 + K_{da} \frac{\rho_a}{\eta} \quad (20)$$

where η = the effective porosity of the aquifer

K_{da} = the distribution coefficient in the aquifer (ml/g)

ρ_a = the bulk density in the aquifer (g/cm³).

The dispersion coefficients (D_x , D_y) are given by

$$D_x = \alpha_L U \quad (21)$$

$$D_y = \alpha_T U \quad (22)$$

where α_L = the longitudinal dispersivity (m)

α_T = the transverse dispersivity (m).

The solution to Equation 19 for the initial conditions $C = C_0$ at $t = 0$ in the source area and $C = 0$ everywhere else is

$$C = \frac{Q_a}{\eta R_d b} \frac{1}{2L} \left(\operatorname{erf} \left(\frac{x + \frac{L}{2} - \frac{Ut}{R_d}}{\frac{4D_x t}{R_d}} \right) - \operatorname{erf} \left(\frac{x - \frac{L}{2} - \frac{Ut}{R_d}}{\frac{4D_x t}{R_d}} \right) \right) \times \frac{1}{2w} \left(\operatorname{erf} \left(\frac{\frac{w}{2} + y}{\frac{4D_y t}{R_d}} \right) + \operatorname{erf} \left(\frac{\frac{w}{2} - y}{\frac{4D_y t}{R_d}} \right) \right) e^{-\lambda_d t} \quad (23)$$

where b = the well screen thickness or mixing depth (m)

Q_a = the initial mass in the water volume defined by $L \times W \times b \times \eta$

erf = the error function

L = length of source parallel to groundwater flow (m)

W = width of source perpendicular to groundwater flow (m).

The terms, L and W are identical to those defined in Equation 3. For an arbitrary release, the concentration may be found by the convolution integral.

$$C(t) = \int_0^t C_i(t-\tau) f(\tau) d\tau \quad (24)$$

where τ = the time of contaminant release (y)

$t-\tau$ = the "age" of the release (y)

Equation 24 gives the instantaneous concentration at time t. For some contaminants, the average concentration over a period of exposure is desired. If the peak concentration (maximum concentration observed at the specified receptor point) is bounded by the time periods, T_a and T_b , the maximum average concentration is given by

$$C_{avg} = \frac{\int_{T_a}^{T_b} C(t) dt}{T_b - T_a} \quad (25)$$

where T_a, T_b = the averaging time period (years).

2.4 LIMITING SOIL CONCENTRATION

Regulatory limits vary depending on the contaminant considered. Some radionuclides are governed by maximum concentration levels (^{226}Ra and ^{228}Ra) in drinking water while the others are limited by the maximum permissible annual

effective dose equivalent of 4 mrem/y (40 CFR 141 and DOE Order 5400.5)³ from drinking water consumption. Regulations involving non-radiological contaminants are more complex. Some contaminants are governed by maximum contaminant levels in drinking water while others are limited by a sub-chronic or chronic ingestion dose and carcinogenic risk.

Because the concentration in groundwater is proportional to soil concentration, the limiting soil concentration may be found by a simple ratio. The limiting soil concentration is given by

$$C_s = \frac{C_L}{C_u} C_{us} \quad (26)$$

where C_s = the limiting soil concentration (Ci or g per m³)

C_L = the limiting groundwater concentration (Ci or g per m³)

C_u = The groundwater concentration from a unit concentration in the source term (Ci or g per m³)

C_{us} = the unit soil concentration (Ci or g per m³).

The groundwater concentration, C_u , may be the peak concentration or the maximum average integrated concentration for evaluation of chronic exposure scenarios. For radionuclides or contaminants regulated by maximum contaminant limits, C_u is set equal to the peak concentration. Chronic exposure criteria require the maximum average concentration integrated over the exposure period to be calculated. The maximum average concentration is given by Equation 25. If the averaging time is one year or less, then the peak concentration was conservatively assumed to represent the maximum average concentration.

The limiting groundwater concentration for a radionuclide regulated by the

³ The basis for calculating dose equivalent to determine compliance with 40 CFR 141 is based on Federal Guidance Report No. 11 (EPA-520/1-88-020) and DOE/EH-0071.

maximum dose limit is given by

$$C_L = \frac{D_L}{DCF I} \quad (27)$$

where D_L = the applicable limit, usually $4.0E-03$ rem/y

DCF = dose conversion factor (rem/Ci)

I = water intake rate, usually $0.730 \text{ m}^3/\text{y}$ (2 L/d).

If the assumption is made that radioactive progeny behave chemically similar to the parent, then progeny that are in secular equilibrium with their parent can be treated simply by summing the dose conversion factors of the parent and the progeny. If secular equilibrium cannot be assumed, then each member of the decay chain must be dealt with separately or ignored.

The limiting groundwater concentration for carcinogens is

$$C_L = \frac{1.0 \times 10^{-6} BW AT}{SF I EF ED} \quad (28)$$

where BW = body weight (70 kg)

AT = averaging time (days, 70 years $\times$ 365 days per year)

SF = slope factor $(\text{mg/kg/d})^{-1}$

I = water intake rate ($0.002 \text{ m}^3/\text{d}$)

EF = exposure frequency (days/year)

ED = exposure duration (70 years by convention).

The value 1×10^{-6} represents the probability of 1 chance in 1,000,000 of an individual developing cancer. The Environmental Protection Agency (EPA, 1989) recommends using probability values between 1×10^{-4} and 1×10^{-7} . Values for the parameters in Equation 28 should be evaluated on a site by site

basis. Consult EPA (1989) for more information. For non-carcinogens, the point departure is given by the hazard quotient (HQ).

$$HQ = \frac{E}{RfD} \quad (29)$$

where RfD = the reference dose (mg/kg/d)

E = the contaminant exposure or intake (mg/kg/d)

Contaminant intake or exposure is given by Equation 30.

$$E = \frac{BW \ AT}{I \ EF \ ED} \quad (30)$$

An HQ of unity is considered acceptable, therefore, the limiting groundwater concentration for non-carcinogens is given by the following.

$$C_L = \frac{HQ \ BW \ AT \ RfD}{I \ EF \ ED} \quad (31)$$

The methodology presented so-far is applicable for sites that contain single contaminants. Some sites may contain multiple contaminants having the same regulatory criteria endpoint (radiological dose or carcinogenic risk). In these cases, several approaches are recommended. First, the contaminant transit time of each contaminant should be considered. If the contaminant transit times are significantly different, then the contaminants can be treated separately because the peak concentrations will not overlap. For contaminants that have approximately the same transit time, then the regulatory criteria limit can be scaled for each contaminant. The general form of the scaling equation for n number of radionuclides is

$$DL_j = \frac{DCF_j}{\sum_{i=1}^n DCF_i} \times DL \quad (32)$$

Where DL = the radionuclide dose limit for drinking water (rem/y)

DL_j = the dose limit for the *j*th nuclide of *n* number of nuclides (rem/y).

DCF_j = the dose conversion factor for the *j*th nuclide of *n* number of nuclides (rem/Ci).

The general form of the scaling equation for carcinogens is

$$R_j = \frac{SL_j}{\sum_{i=1}^n SL_i} \times R \quad (33)$$

Where R = the probability risk factor (1 x 10⁻⁶)

R_j = the probability risk factor for the *j*th contaminant of *n* number of contaminants.

SL_j = the slope factor for the *j*th contaminant of *n* number of contaminants (mg/kg/day)⁻¹.

The general form of the scaling equation for non-carcinogens is

$$HQ_j = \frac{RfD_j}{\sum_{i=1}^n RfD_i} \times HQ \quad (34)$$

Where HQ = the hazard quotient (1.0)

HQ_j = the hazard quotient for the j th contaminant of n number of contaminants.

RfD_j = the reference dose for the j th contaminant of n number of contaminants (mg/kg/day).

If the limiting soil concentration exceeds the solubility limited mass (Equation 11), then a warning statement is made at the end of the output file. The warning statement indicates that the concentration of the leachate for the limiting soil mass will exceed the solubility limit of the contaminant and the limiting soil concentration may be more than what has been calculated. Under solubility limited release conditions, the maximum groundwater concentration is obtained when the source mass is greater than, or equal to, the solubility limited mass. A source mass greater than the solubility limited mass will not result in higher groundwater concentrations. If the warning statement is encountered, then the calculated limiting soil concentration is conservative and bounds the problem. See example problems 3a and 3b in Appendix A for further discussion.

3. CODE IMPLEMENTATION

GWSCREEN is written in standard FORTRAN and compiled for operation on a personnel computer with a DOS operating system. The FORTRAN source code is also compatible with most FORTRAN compilers on UNIX operating systems. Input to GWSCREEN is through one, free format ASCII file. This file contains the contaminant and site specific data such as sorption coefficients and regulatory limits and exposure scenario data such as drinking water consumption rates and standard body weight. This file is assigned a name by the user and the user is prompted for this file name during execution of the program. Line by line input for the user defined input file is found in Section 3.2, Table 2 and 3.

Equations 1 thru 36 are implemented in numerous subroutines in the code. These subroutines and the equations embedded in them are cross referenced and briefly described in Table 1. The program flow and execution are described in Section 3.3. Three benchmark problems are presented in Section 3.4 and six

sample problems that demonstrate the options in GWSCREEN are presented in Appendix A. Appendix B contains the source code listing.

Table 1. A brief description of the GWSCREEN subroutines.

SUBROUTINE	DESCRIPTION	EQUATION NUMBERS IMPLEMENTED
MAIN	Main program	13, 26
INPUT	Reads user defined input file)	
CTIME	Calls QGAUS2 to calculate GW concentration	
RAD	Calculates radiological dose impacts	27
CARCIN	Calculates carcinogen impacts	28
NCARCIN	Calculates non-carcinogen impacts	29
SOURCEX	Calculates source term parameters	4,10,11,14 15,16,17,20
ROOT	Finds the roots of Equation 10	
FUND	Calculates the derivative of Equation 10	10
PEAK	Calls GOLDEN to locate peak concentration	
GOLDEN	Finds peak groundwater concentration	
GWINT	Calls QGAUS1 to integrate GW concentrations	
QGAUS1	Integrates groundwater concentration vs time	25
QGAUS2	Solves convolution integral	24,36
SRCTERM	Calculates mass released for each call of QGAUS2	18
AREA	Calculates groundwater dispersion	23
FUNC	Calls the QGAUS2 subroutine	
SLOPE	Calculates slope of concentration vs time curve	
FLUXES	Calculates instantaneous flux and cumulative flux	8,9
ERRORD	Error function routines includes ERX, GAMMP, GAMSER, GCF, GAMMLN	

3.1 COMPUTATIONAL METHODS

The methodology presented in Section 2 requires numerical integration to calculate the instantaneous groundwater concentration (Equation 24) and the average integrated concentration (Equation 25). GWSCREEN uses a Gaussian

quadrature algorithm (Press et al. 1987) to perform all numerical integration. This routine was found to be the most computationally efficient integration algorithm for solving the convolution integral and integrating groundwater concentrations over time. However, some precautions must be taken in order to avoid numerical instability problems which can arise under some conditions. (See the discussion on Peclet numbers in this section).

Variations of this routine are found in the subroutines, QGAUS1 and QGAUS2. In QGAUS1, an 8 point (8 pairs of zeros and weights) Gaussian integration routine was used to integrate the instantaneous groundwater concentration over time. In QGAUS2, a 12 point Gaussian integration routine was used to solve the convolution integral and calculate the instantaneous groundwater concentration. The zero values and weights for these routines were obtained from Hornbeck (1975). It was necessary to increase the number of zero and weight points in the QGAUS2 routine in order to achieve numerical stability. Figure 4 shows how the number of zero and weight points in a Gaussian quadrature solution for Equation 24 affects the stability of the solution for a constant, steady state unit release (1.0 g/y). The results are compared against results obtained using a Simpsons rule integration routine also described in Press et al, 1987. The 12 point and Simpsons rule results are identical. Simpsons rule integration, with a variable number of integration points and convergence checking, was found to be the most robust solver for the convolution integral. However it is very time consuming to operate. The Gaussian routine is known to be very accurate and time efficient for smooth, well behaved functions. The Simpsons rule technique was not used because the integrand (Equation 24) is generally smooth and predictable. The 12 point Gaussian routine, using the precautions stated in the text, will yield the same results in a fraction of the time.

Numerical stability of the solution was also found to be dependent on the relative magnitudes of dispersion and advection. The ratio of advection to dispersion is given by the Peclet number.

Transport parameters: Pore velocity=570 m/y, Porosity=0.1, $\alpha_L=0.2$ m, $\alpha_T=0.02$ m, $x=200$ m, $R_d=133$, $b=1.0$ m.

Figure 4. Solutions to Equation 24 using a steady state unit release rate for different numbers of Gaussian Quadrature zero-weighting pairs and a Simpsons rule integration routine.

$$P_e = \frac{U \Delta L}{D_x} = \frac{U \Delta L}{\alpha_L U} = \frac{\Delta L}{\alpha_L} \quad (35)$$

where P_e = the Peclet number

ΔL = the characteristic length (m)

The characteristic length for this application is the "x" distance to the receptor since dispersion is neglected in the vadose zone. For example, the Peclet number for a receptor distance (x) of 100 m and a longitudinal dispersivity of 2 m is 50. Concentration vs time for a continuous, steady state unit release for different Peclet numbers are plotted in Figure 5. The solution becomes increasingly unstable for Peclet numbers greater than 5000. Therefore a Peclet number no greater than 5000 is suggested in order to assure numerical stability of the solution.

The integration limits in Equation 24 often result in values of the function $C_i(t-\tau)$ that are near zero and add little to the integrand and decrease the overall accuracy of the solution. Codell (1982) gave expressions for the integration limits, T_1 and T_2 , such that the each function call of $C_i(t-\tau)$ added significant values to the integrand. These limits were presented (in Codell) for a line source with a decay term and an area source without a decay term. The limits for an area source were modified to include a decay term in GWSCREEN. The limits, T_1 , T_2 are given by the following.

Transport Parameters: Pore Velocity=570 m/y, Porosity=0.1, $\alpha_L=0.2$ m, 0.04 m, 0.02 m, 0.01 m, $\alpha_T=0.02$ m, 0.004 m, 0.002 m, 0.001 m, $x=200$ m, $R_d=133$, $b=1.0$ m

Figure 5. Solutions to Equation 24 using a 12 point Gaussian Quadrature routine for a steady state unit release rate for different Peclet numbers.

$$T_1, T_2 = t - \frac{\frac{2U(x-L/2) + 4D_x\gamma}{R_d}}{\left(\frac{U}{R_d}\right)^2 + \frac{4D_x\gamma}{R_d}}$$

(36)

$$\pm \sqrt{\left(\frac{\frac{2U(x+L/2) + 4D_x\gamma}{R_d}}{\left(\frac{U}{R_d}\right)^2 + \frac{4D_x\gamma}{R_d}} \right)^2 - \frac{4(x-L/2)^2}{\left(\frac{U}{R_d}\right)^2 + \frac{4D_x\gamma}{R_d}}}$$

where T_1, T_2 = the upper and lower limits of integration (years)

γ = an arbitrary value such that $e^{-\gamma} \approx 0.0$

and $T_1 < (t-\tau) < T_2$

A value of 50 was found to be adequate for γ . These limits are calculated in the subroutine QGAUS2.

Equation 24 requires evaluation of error functions. The error function routine was also adapted from Numerical Recipes (Press et al., 1987) and contained in subroutines ERRORF, GAMMP, GSER, GCF and GAMLIN. Equation 24 is implemented in subroutine AREA.

Peak concentration is determined in the subroutines, PEAK, SLOPE and GOLDEN. The subroutine PEAK calculates the points which bound the peak using the subroutine, SLOPE to calculate the first derivative of the concentration vs time curve. After the peak has been bounded, the subroutine GOLDEN calculates the peak concentration using a Golden Section routine in one dimension adapted from Press et al., (1987).

Roots to Equation 10 are calculated in subroutine ROOTS which uses a one-dimensional Newton-Raphson routine adapted from Press et al., (1987).

3.2 CONTAMINANT AND SITE SPECIFIC DATA FILE

Variables and structure for the required input data files are presented in Table 2. Variable descriptions and some default values are presented in Table 3. A value for each variable must be included in the input file whether or not that value is used in the calculation. If more than one value is read on a line, then the values must be separated by spaces or commas. Comments may follow the last value on a line.

Line 13 lists 5 variables, however, only one value is read. The first value read on line 13 is assigned to one of the following variables, DCF, SFACTOR, RFD, RADMAX, or ZRADMAX depending on the value of IMODE (see Table 2 and 3). Units of the contaminant (Ci or mg) are also selected by the IMODE variable. For example, if the IMODE variable is 3, then the first value on line 13 is read as ZRADMAX, the maximum allowable contaminant concentration in groundwater, and the units of the contaminant are mg. If IMODE=1, then the first value on line 13 is read as DCF and the units of the contaminant are Ci.

Table 2. Input file for contaminant and site specific data. NOTE: Variables given the same line number must appear in the same order on the line as presented in this Table.

LINE NUMBER	VARIABLE	CODE VARIABLE	TYPE	DESCRIPTION
1	---	TITLE	CHARACTER	80 character title of project
2	---	KFLAG	INTEGER	Flag variable to select the type of calculation. If KFLAG=0, then concentration vs time is calculated. If KFLAG=1, then peak concentration and limiting soil concentration is calculated. The source is reset to 1.0 Ci or mg when KFLAG=1
3	$T_b - T_a$	INTIME	INTEGER	Integration time for determination of average concentration (years). If INTIME=0, then concentration as a function of time is output.
4	L	AL	REAL	Length of source parallel to groundwater flow (m)
4	W	WA	REAL	Width of source perpendicular to groundwater flow (m)
4	T	THICKS	REAL	Thickness of source zone (m)
5	I	PERC	REAL	The net water infiltration rate (m/y)
5	θ_s	THETAS	REAL	Volumetric moisture content in contaminated zone (m/m)
5	θ_u	THETAU	REAL	Volumetric moisture content in the unsaturated zone (m/m)
6	ρ_c	RHOS	REAL	Bulk density in the contaminated zone (g/cm^3)
6	K_{dc}	ZKDS	REAL	Sorption coefficient in contaminated zone (ml/g)
7	ρ_u	RHOU	REAL	Bulk density in unsaturated zone (g/cm^3)
7	K_{du}	ZKDU	REAL	Sorption coefficient in unsaturated zone (ml/g)
8	$T_{1/2}$	THALF	REAL	Half Life of contaminant (years)
8	Q_o	QI	REAL	Initial mass in source volume (Ci or mg)
8	MW	ZMW	REAL	Molecular weight of contaminant (g/mole)
8	C_{sl}	SL	REAL	Contaminant solubility limit (mg/L)
9	ρ_a	RHOA	REAL	Bulk density in saturated zone (g/cm^3)
9	η	PHI	REAL	Porosity of saturated zone (m/m)
9	K_{da}	ZKDA	REAL	Sorption coefficient in the saturated zone (ml/g)
10	α_L	AX	REAL	Longitudinal dispersivity (m)
10	α_T	AY	REAL	Transverse Dispersivity (m)
10	U	VX	REAL	Saturated pore velocity (m/y)
11	b	THICK	REAL	Well screen (mixing) thickness (m)
11	x_u	DEPTH	REAL	Thickness of unsaturated zone (m)

Table 2. (continued)

LINE NUMBER	VARIABLE	CODE VARIABLE	TYPE	DESCRIPTION
12	--	IMODE	INTEGER	Flag variable to select type of groundwater criteria. IMODE=1 Radiological dose limit; IMODE=2 Maximum radionuclide concentration; IMODE=3 Maximum non-radiological groundwater concentration; IMODE=4 Carcinogenic risk limit; IMODE=5 Non-radiological limit based on reference dose.
13	DCF	DCF*	REAL	Radiological dose conversion factor (rem/Ci)
13	C _L	RADMAX*	REAL	Maximum allowable radionuclide concentration in groundwater (Ci/L)
13	C _L	ZRADMAX*	REAL	Maximum allowable non-radiological groundwater contaminant concentration (mg/L)
13	SF	SFACTOR *	REAL	Carcinogenic risk slope factor (mg/kg/d) ⁻¹
13	RFD	RFD*	REAL	Reference dose for non-radiological contaminants (mg/kg/d)
14	x	XD	REAL	Receptor distance from center of source parallel to groundwater flow (m)
14	y	YD	REAL	Receptor distance from center of source perpendicular to groundwater flow (m)
15	BW	BW	REAL	Body weight of standard man (70 kg)
15	AT	AT	REAL	Averaging time (days, 365 days per year times number of 70 years = 25,550 days)
15	I	WI	REAL	Water intake rate (2.0 L/d)
15	EF	EF	REAL	Exposure frequency (350 days/year)
15	ED	ED	REAL	Exposure duration (70 years)
15	D _L	DLIM	REAL	Radiological CEDE limit (0.004 rem/y)
15	--	CRISK	REAL	Acceptable carcinogenic risk factor (1.0E-06)
15	HQ	HQ	REAL	Hazard quotient (1.0)

* Only one variable is read on line 13. The variable read depends on the value of IMODE (line 12). If IMODE=1, then line 13 variable is DCF and units are in Ci. If IMODE=2, then line 13 variable is RADMAX and units are in Ci. If IMODE=3, then line 13 variable is ZRADMAX and units are in mg. If IMODE=4, then line 13 variable is SFACTOR and units are in mg. If IMODE=5, then line 13 variable is RFD and units are in mg.

Table 3. Definition of variables in the GWSCREEN user defined input files.

Code Variable	Units	Description
AL	m	Length of source parallel to flow.
AT	days	The time that the exposure is averaged over. For carcinogenic effects, the averaging time is usually 25,550 days (70 years). See EPA/540/1-89/002 for recommended values for non carcinogens. This variable is ignored for radiological calculations.
AX	m	Longitudinal Dispersivity. Minimum value should be based on the Peclet number. (Section 2.1, Equation 21)
AY	m	Transverse Dispersivity. Minimum value should be based on the Peclet number. (Section 2.1, Equation 22)
BW	kg	Body weight of standard man (70 kg)
DCF	rem/Ci	Ingestion radiological dose conversion factor. See DOE/EH-0071 for ingestion DCF values.
DEPTH	m	Distance between base of source volume to the top of the aquifer. (the unsaturated zone)
DLIM	rem/y	Radiological Committed effective dose equivalent limit. Usually, 0.004 rem/y.
ED	years	Exposure duration. For chronic and carcinogenic calculations, this value is usually 70 years. Consult EPA/540/1-89/002 for additional guidance.
EF	days/year	Exposure frequency. For conservative estimates, assume 365 days per year. Consult EPA/540/1-89/002 for additional guidance.
CRISK	---	Acceptable carcinogenic risk factor. EPA recommends a value of $1.0E-06$.
HQ	---	Hazard Quotient. Usually, a value of 1.0 is selected.
I	L/day	Water intake rate. For conservative estimates, use 2.0 L/day, otherwise consult EPA/540/1-89/002 for guidance.
IMODE	--	Flag variable to select type of groundwater criteria. IMODE=1 Radiological dose limit; IMODE=2 Maximum radionuclide groundwater concentration; IMODE=3 Maximum non-radiological groundwater concentration; IMODE=4 Carcinogenic risk limit; IMODE=5 Non-radiological limit based on reference dose.
INTIME	years	Integration time for determination of average concentration. This variable <u>must</u> have the same value as ED for carcinogenic risk calculations (IMODE=4). If $INTIME \leq 1$, then the peak concentration is reported as the average concentration.
KFLAG	---	Flag variable to select the type of calculation. If KFLAG=0, then concentration vs time is calculated. If KFLAG=1, then peak concentration and limiting soil concentration is calculated. The source is reset to 1.0 Ci or mg when KFLAG=1
PERC	m/y	The net water infiltration rate (m/y). (See Section 2.1, Equation 5).
PHI	m/m	Effective porosity of the aquifer

Table 3. (continued).

Code Variable	Units	Description
QI	Ci or mg	Initial mass or activity in source volume. QI is reset to 1.0 units when KFLAG=1
RADMAX	Ci/L	Maximum allowable radionuclide concentration in groundwater.
RFD	mg/kg/d	Reference dose for non-radiological contaminants.
RHOA	g/cm ³	Bulk density of aquifer material
RHOS	g/cm ³	Bulk density of source volume
RHOU	g/cm ³	Bulk density of unsaturated zone
SFACTOR	(mg/kg/d) ⁻¹	Carcinogenic risk slope factor. Consult the latest Health Effects Summary Tables (published by EPA) for values.
SL	mg/L	Solubility limit. If unknown, this variable should be set to 1.0E6
THALF	years	Half life of contaminant. If no decay is to be considered, then set THALF equal to 0 years.
THETAS	m/m	Volumetric moisture content in contaminated zone. See Figure 2 and 3 for values in sediment and basalt.
THETAU	m/m	Volumetric moisture content in the unsaturated zone. See Figure 2 and 3 for values in sediment and basalt.
THICK	m	Well screen thickness. If unknown, a value of 1.0 m is suggested.
THICKS	m	Thickness of source volume.
TITLE	character	80 character title of project
WA	m	Width of source perpendicular to groundwater flow.
VX	m/y	Saturated pore velocity.
XD	m	Receptor distance parallel groundwater flow from center of source.
YD	m	Receptor distance perpendicular to groundwater flow from center of source.
ZKDA	ml/g	Sorption coefficient in the aquifer. If unknown, a value of 0.0 is suggested.
ZKDS	ml/g	Sorption coefficient in source volume. If unknown, a value of 0.0 is suggested.
ZKDU	ml/g	Sorption coefficient in the unsaturated zone. If unknown, a value of 0.0 is suggested.
ZMW	g/mole	Molecular weight of contaminant (g/mole)
ZRADMAX	mg/L	Maximum allowable non-radiological contaminant groundwater concentration

3.3 PROGRAM FLOW EXECUTION

Overall program flow (Figure 6) is controlled by the user input variables, IMODE and KFLAG. These variables determine the regulatory option to use, units of the calculation, and whether concentration vs time or limiting soil concentration is calculated. When executing GWSCREEN, the user is prompted for the name of the user defined input file (Table 1 and 3) and the name of the file output is written to. The variable, KFLAG determines whether concentration vs time or limiting soil concentration is calculated. If KFLAG equals 0, then groundwater concentration and source flux are calculated as a function of time and printed to the output file. The source mass or activity is set by the QI variable. The user is prompted for the beginning time, ending time, and print step of the groundwater concentration output. If KFLAG equals 1, then the limiting soil concentration is calculated. The source mass is reset to 1.0 Ci if $IMODE \leq 2$ or 1.0 mg if $IMODE > 2$. If the solubility limit is unknown, then the SL variable should be set to 1.0E6 mg/L or greater. This will basically eliminate a solubility limited release from being considered. For some contaminants (tritium for example) with K_d values of zero, while operating in the limiting soil concentration mode ($KFLAG=1$), the output might state that the limiting source mass exceeds the solubility limited mass. This output usually indicates that significant decay occurs during transit in the unsaturated zone and the limiting soil concentration is artificially high.

The output file prints all the input data and the date and time of the run. Space has been provided for the input data to be checked and reviewed by additional personnel. Fixed parameter values calculated in the program, such as the leach rate constant (λ_L) and the retardation factor (R_d), are printed next on the output file. Appropriate units are selected automatically with the IMODE variable. If the concentration vs time mode ($KFLAG=0$) has been selected, then the output file contains the contaminant fluxes and groundwater concentrations for the output times specified by the user. If $KFLAG=1$, then the limiting soil concentration and soil mass is calculated and printed to the output file. The code also compares the limiting soil mass with the

Figure 6. Flow chart for the GWSCREEN code. Note: Not all subroutines are shown on this figure.

solubility limited mass (Q_{sl}). If the limiting mass exceeds the solubility limited mass as given by Equation 11, then it is stated at the bottom of the output file.

3.4 BENCHMARKS WITH OTHER CODES

Three benchmark problems are presented in this section. In the first problem, the groundwater transport portion code was compared with an established code that uses a similar algorithm. The second and third benchmark cases compare the source release and unsaturated model with a more rigorous numerical model.

The problem selected for the first benchmark case involved hypothetical ^{239}Pu contamination in 50 m x 50 m x 2.5 m volume at the Idaho National Engineering Laboratory. The contaminated zone was assumed to be located primarily in surface sediment. The unsaturated zone and the aquifer were characterized as basalt. A percolation rate of 3 m/year was taken to represent the bounding rainfall (or irrigation) case (DOE/ID-10340(91)). Using the graphs illustrated in Figures 2 and 3, the volumetric moisture content was determined for the basalt and sediment. Sorption coefficients, aquifer pore velocity, and dispersivities were taken from the Radioactive Waste Management Complex Performance Assessment (Case et al., 1989). The ingestion dose conversion factor was obtained from DOE/EH-0071. The remaining parameter values were assumed.

The IMODE variable was set equal to 1 since ^{239}Pu is a radionuclide and the exposure criteria is based on the radiological dose limit of 4 mrem/year. The INTIME variable was set equal to 1 since radiological dose criteria is based on a one year exposure period. The input file used to run the problem (Figure 7) includes parameter values and comments. The code variable name is listed after the last value of each line of the input file. A general comment is placed after the last value is read. The code ignores these comments and it is not necessary to include them in the input file however, comments are useful for documentation purposes.

```

Example problem for GWSCREEN users manual; Pu-239 source  TITLE
0 KFLAG
0 INTIME
50.0 50.0 2.5 AL WA THICKS
3.0 0.44 0.096 PERC THETAS THETAU
1.8 2000. RHOS zKDS
2.0 200 RHOU zKDU
2.411E+04 1.0 239 1.0E6 THALF QI MW SL
2.0 0.228 200.0 RHOA PHI zKDA
91.0 1.0, 570 AX AY VX
1.0 100 THICK DEPTH
1 IMODE
4.3E+06 DCF-RADMAX-NRADMAX-SFACTOR-RFD
25.,0. XD YD
70. 2.555E04 2.0 350. 70. 0.004 1.0E-6 1.0 BW AT WI EF ED DLIM CRISK HQ

```

Comments:

The contaminant, Pu-239, has a 24,110 year half life. The dispersivity values (AX and AY), and sorption coefficients (zKDU, zKDA, zKDS) were taken from the Radioactive Waste Management Complex, Performance Assessment

Figure 7. GWSCREEN sample problem input file. The parameter names are listed to the right of the parameter values. After the last parameter value (HQ) is read, the input file may contain as many comments as shown.

Figure 8. Comparison of groundwater concentrations calculated with GWSCREEN and GRDFLX for a Pu-239 source.

Results (Figure 8) were compared with groundwater concentrations calculated using the GRDFLX code (Codell, 1982). The concentrations calculated with GWSCREEN match the concentrations calculated with GRDFLX very well.

The second and third benchmark tests compared the calculated mass flux at the aquifer/unsaturated zone interface using GWSCREEN and the finite difference code, PORFLO-3 (Runchal, 1989). The problem considers a source volume, 10 m long, 1 m wide and 1 m thick having an initial mass of 1 g (Figure 9). The percolation rate and volumetric water content were assumed to be the same as in the first benchmark problem. The only difference between the second and third cases was the half-life of the contaminant. The half life of the contaminant was assumed to be infinite for the second case and 4 years for the third case. Other input parameters are presented in Table 4. For the PORFLO simulation, a longitudinal and transverse dispersivity of 0.5 m was assumed. No-flux boundary conditions were given for all boundary planes except at the unsaturated-saturated boundary. A zero concentration boundary condition was applied to this plane. Nodes above the source volume were fixed at zero concentration.

Results of the simulations for case 2 (Figure 10) show the peak contaminant flux calculated with GWSCREEN exceeds the PORFLO-3 peak contaminant flux. The maximum, 70 year cumulative flux was 0.62 g using GWSCREEN and 0.44 g using PORFLO-3. The purpose of this benchmark was to demonstrate that the unsaturated model in GWSCREEN will calculate a conservative mass flux to the aquifer when compared to a simulation performed using a complex numerical code and the same data.

In the third case (Figure 11), the contaminant decays during transport in the unsaturated zone. The PORFLO peak flux exceeds the GWSCREEN peak flux. A similar observation of contaminant concentration was made by Seitz et al. (1991). It was shown that for Peclet numbers less than about 50, the peak concentration, and consequently, the peak mass flux, increased when the ratio of contaminant half-life to contaminant transit time was decreased to less than 0.1 (Figure 12). The Peclet number for this simulation was

$$P_e = 9.1 \text{ m} \div 0.5 \text{ m} = 18$$

Table 4. Parameter values for benchmark problem #2 and #3.

Parameter	Value
LENGTH OF SOURCE PARALLEL TO GW FLOW (m)	1.00E+01
WIDTH OF SOURCE PERPENDICULAR TO GW FLOW (m)	1.00E+00
THICKNESS OF SOURCE (m)	1.00E+00
PERCOLATION RATE (darcy vel m/y)	3.00E+00
VOLUMETRIC WATER CONTENT IN SOURCE	4.46E-01
VOLUMETRIC WATER CONTENT IN UNSATURATED ZONE	1.07E-01
BULK DENSITY AT SOURCE (g/cm**3)	1.80E+00
SORPTION COEFFICIENT AT SOURCE (ml/g)	1.21E+02
BULK DENSITY IN UNSAT ZONE (g/cm**3)	2.00E+00
SORPTION COEFFICIENT IN UNSAT ZONE (ml/g)	6.50E+00
HALF LIFE OF CONTAMINANT, CASE #2 (y)	infinite
HALF LIFE OF CONTAMINANT, CASE #3 (y)	4.00E+00
INITIAL MASS OR ACTIVITY (mg)	1.00E+00
BULK DENSITY OF AQUIFER (g/cm**3)	2.00E+00
POROSITY OF AQUIFER	2.28E-01
SORPTION COEFFICIENT IN AQUIFER (ml/g)	6.50E+00
X DISPERSIVITY (for PORFLO runs only) (m)	5.00E-01
Y DISPERSIVITY (for PORFLO runs only) (m)	5.00E-01
DISTANCE TO AQUIFER BELOW CONTAMINATION (m)	9.10E+00

CALCULATED VALUES

LEACH RATE CONSTANT (1/y)	1.3746E-02
UNSATURATED PORE VELOCITY (m/y)	2.8037E+01
RETARDATION FACTOR (UNSATURATED)	1.2250E+02
TRANSIT TIME IN UNSAT ZONE (years)	3.9758E+01

CONCEPTUAL MODEL FOR BENCHMARK 2 AND 3

Figure 9. Conceptual model for benchmark problem #2 and #3.

and the half-life/contaminant transit time ratio (H_r) was

$$H_r = \frac{4 \text{ years}}{(9.1 \text{ m} + \{3 \text{ m/y}/0.107\} \times (1 + [6.5 \text{ ml/g } 2.0 \text{ g/cc}]/0.107))} \approx 0.1.$$

Therefor, the results are consistent with the previously stated observations. The normalized peak concentration vs Peclet number curve for $H_r = 0.075$ (Figure 12) shows the concentration (and consequently, the mass flux) has a minimum value when the Peclet number equals 70. Increasing the Peclet number beyond 70 results in an increase in the normalized peak concentration in all cases.

One method to assure conservatism is to make sure the half-life/transit time ratio be limited to a minimum value of 0.1. This can be done by adjusting the thickness of the unsaturated zone. If the half-life/transit time ratio is around 0.05, then the fate of the contaminant will probably be completely dominated by decay and dispersion will have little effect on the conclusion reached.

If the unsaturated zone dispersivity is known, then the Peclet number can be computed. The confidence in the conservatism of the result is enhanced if the Peclet number in the unsaturated zone is greater than 70 for contaminants that have half-life/transit time ratios of 0.075 or greater.

Figure 10. PORFLO-3 and GWSCREEN mass flux at the unsaturated zone-aquifer interface as a function of time for a contaminant with an infinite half-life.

Figure 11. PORFLO-3 and GWSCREEN mass flux at the unsaturated zone aquifer interface as a function of time for a contaminant with a four year half-life,

Figure 12. Normalized peak concentration vs Peclet number for contaminants with different half-life/contaminant transit time (H_r) ratios. (Taken from Seitz et al., 1991)

4. REFERENCES

- Baca, R. G., S.O. Magnuson, H.D. Nguyen, P. Martin, A Modeling Study of Water Flow in the Vadose Zone Beneath the Radioactive Waste Management Complex. Idaho National Engineering Laboratory, EG&G Idaho Inc. EGG-GEO-10068, January, 1992.
- Baes, C. F. III, R.D. Sharp, A Proposal for Estimation of Soil Leaching and Leaching Constants for Use in Assessment Models. Journal of Environmental Quality, Vol 12, no 1, pp 17-28, 1983
- Bishop, C. W., Hydrologic Properties of Vesicular Basalt, MS Thesis, University of Arizona, Tucson AZ, 1991
- Case, M. J., S.J. Maheras, M.A. McKenzie-Carter, M.E. Sussman, P. Volilleque, Radioactive Waste Management Complex Performance Assessment. EGG-WM-8773, June, 1990.
- Code of Federal Regulations, 40 CFR 141, Title 40, Protection of the Environment, Part 141, National Primary Drinking Water Regulations, Amended by 56 FR 32113, July 15, 1991.
- Codell, R. B., A Collection of Mathematical Models for Dispersion in Surface Water and Groundwater. U.S. Nuclear Regulatory Commission, NUREG-0658, 1982.
- Hornbeck, R. W., Numerical Methods, Quantum Publishers Inc, New York, New York, 1975.
- Gilbert, T. L., C. Yo, Y.C. Yuan, A.J. Zielen, M.J. Jusko, and A. Wallo III, A Manual for Implementing Residual Radioactive Material Guidelines. Argonne National Laboratory, ANL/ES-160, 1989
- Killogh, G. G., R.E. Moore, J.E. Till, DECHEM Version 3.02: An All Pathway Assessment Procedure for Determining Acceptable Concentrations of Chemicals in Soil of Waste Sites. Radiological Assessment Corporation, Rt 2 Box 122, Neeses, SC 29107, 1991.
- Kozak, M. W. et al. Background Information for the Development of a Low Level Waste Performance Assessment Methodology; Volume 3 and 4. NUREG/CR-5453, 1989.
- McElroy, D. L., J.M. Hubbell, Hydrologic and Physical Properties of Sediments at the Radioactive Waste Management Complex, EGG-BG-9147, EG&G Idaho Inc, Idaho Falls ID, 1990.
- Robertson, J. B., Digital Modeling of Radioactive and Chemical Waste Transport in the Snake River Plain Aquifer at the National Reactor Testing

Station, Idaho, U.S. Geological Survey, Open File Report No. IDO-22054, Water Resources Division, Idaho Falls, ID, 1974.

- Rood, A. S., R.C. Arnett, J.T. Barraclough, Contaminant Transport in the Snake River Plain Aquifer: Phase I, Part 1: Simple Analytical Models of Individual Plumes. Idaho National Engineering Laboratory, EG&G Idaho Inc, EGG-ER-8623, May, 1989.
- Runchal, A. K., Sagar, B., PORFLO-3: A Mathematical Model for Fluid Flow, Heat and Mass Transport in Variability Saturated Geologic Media. Westinghouse Hanford Corporation WHC-WP-0041, July, 1989.
- Seitz, R. R., A.S. Rood, G.A. Haris, M. Kotecki, Sample Application of Sensitivity/Uncertainty Analysis Techniques to a Groundwater Transport Problem. National Low Level Waste Management Program, DOE/LLW-108, 1991.
- van Genuchten, M. Th., Calculating the Unsaturated Hydraulic Conductivity with a New Closed-Form Analytical Model, Report 78-WR-08, Water Resources Program, Department of Civil Engineering, Princeton University, Princeton, N.J., 1978.
- U.S. Environmental Protection Agency, Risk Assessment Guidance for Superfund; Volume 1; Human Health Evaluation Manual (Part A). EPA/540/1-89/002, December, 1989.
- U.S. Department of Energy, Track 1 Sites: Guidance for Assessing Low Probability Hazard Sites at INEL. DOE/ID-10340(91), October, 1991
- U. S. Department of Energy, Internal Dose Conversion Factors for Calculation of Dose to the Public. DOE/EH-0071, 1988
- Whelan, G., D.L. Streng, J.G. Droppo, B.L. Steelman, J.W. Buck, The Remedial Action Priority System (RAPS): Mathematical Formulations. Pacific Northwest Laboratories, DOE/RL/87-09, 1987.

APPENDIX A: GWSCREEN SAMPLE PROBLEMS

Six sample problems are illustrated in this Appendix. Each sample problem was intended to demonstrate a different aspect of the GWSCREEN code. A brief description of each problem follows.

1. Limiting soil concentration for Pu-239 in a 50 m x 50 m x 2.5 m source volume located in an environment similar to eastern Idaho. A bounding agriculture infiltration rate of 3 m/y was assumed. No progeny contributions were considered because the first decay product of Pu-239 (U-235) would not be in secular equilibrium at the time of peak concentration.
2. Limiting soil concentration for U-238 in a 25 m x 25 m x 1.0 m source volume located in an environment similar to eastern Idaho. A bounding agriculture infiltration rate of 3 m/y was assumed. The dose conversion factor used in the calculation included contributions from Th-234 and Pa-234. The Pa-234 DCF was multiplied by its branching ratio (1.6E-03) and added to the total.
- 3a. Limiting soil concentration for a mercury source in a 25 m x 25 m x 1.0 m source volume located in an environment similar to eastern Idaho. A bounding agriculture infiltration rate of 3 m/y was assumed. Soil concentration limit based on 1 year subchronic exposure period (RfD value of 3.0E4 mg/kg/day). Limiting soil concentration is controlled by the solubility limit of mercury.
- 3b. Concentration vs time for a 112.5 kg mercury source in a 25 m x 25 m x 1.0 m source volume at the INEL. Note that the mass used in the simulation exceeds the solubility limited mass calculated in sample problem 3a and therefore, the release is solubility limited. Contaminant flux to the unsaturated zone and aquifer, and the groundwater concentration will reach steady state since the concentration of the leachate will remain constant at the solubility limit value until the mass in the source volume drops below the

solubility limited mass of $5.07\text{E}+06$ mg. The solubility limited release time is given by Equation 12.

4. Limiting soil concentration for 2,3,7,8-tetrachlorodibenzo-p-dioxine (TCDD) for a remediated storage site in Biloxi, Mississippi. The limiting soil concentration was based on a carcinogenic slope factor of $1.5\text{E}5 \text{ (mg/kg/day)}^{-1}$.
5. Limiting Ra-226 soil concentration for a hypothetical remediated uranium mill tailings site. Limiting soil concentration is based on the maximum groundwater concentration limit of 5.0 pCi/L.
- 6a. Limiting soil concentration for a Ni-59 source at a hypothetical site. The limiting soil mass exceeds the solubility limit of Ni-59. Limiting soil concentration is based on a annual dose equivalent of 4 mrem/y.
- 6b. Concentration vs time for a 1000 Ci inventory (11 nCi/g) Ni-59 source at a hypothetical site. The release is solubility limited. Note the solubility limited release time is less than the time predicted by Equation 12 because of decay.

Sample Problem 1: Input File

```
'EXAMPLE PROBLEM #1 for users manual pu-239'  TITLE
1
1 KFLAG
1 INTIME
50.0 50.0 2.50 AL WA THICKS
3.0 0.44 0.096 PERC THETAS THETAU
1.8 2.0E+03 RHOS zKDS
2.0 2.0E+02 RHOU zKDU
2.41E+04 1.00 239.0 7.11E6 THALF QI ZMW SL
2.0 0.10 200.0 RHOA PHI zKDA
9.1 4.0 570 AX AY VX
12.0 100.0 THICK DEPTH
1 IMODE
4.30e6 DCF-RADMAX-NRADMAX-SFACTOR-RFD
25.0, 0. XD YD
70.0 2.555E+04 2.0 350. 70. 0.004 1.0E-6 1.0 BW AT WI EF ED DLIM CRISK HQ
```

Output File

```
TIME OF RUN 09:06:55.45
DATE OF RUN 03/10/92
INPUT FILE NAME: pb-1.par
OUTPUT FILE NAME: pb-1.out
```

```
*****
*
* This output was produced by the model:
*
* GWSCREEN
*
* A semi-analytical model for the assessment
* of the groundwater pathway from the leaching
* of surficial and buried contamination.
*
* Arthur S. Rood
* Idaho National Engineering Laboratory
* EG&G Idaho Inc.
* Subsurface and Environmental Modeling Unit
* PO Box 1625
* Idaho Falls, Idaho 83415
*****
```

```
>>> TITLE OF PROJECT:
'EXAMPLE PROBLEM #1 for users manual pu-239'  TITLE
```

>>> INPUT DATA

```
*****
INTEGRATION TIME (years) 1
LENGTH OF SOURCE PARALLEL TO GW FLOW (m) 5.00E+01
WIDTH OF SOURCE PERPENDICULAR TO GW FLOW (m) 5.00E+01
THICKNESS OF SOURCE (m) 2.50E+00
PERCOLATION RATE (darcy vel m/y) 3.00E+00
VOLUMETRIC WATER CONTENT IN SOURCE 4.40E-01
VOLUMETRIC WATER CONTENT IN UNSATURATED ZONE 9.60E-02
BULK DENSITY AT SOURCE (g/cm**3) 1.80E+00
SORPTION COEFFICIENT AT SOURCE (ml/g) 2.00E+03
BULK DENSITY IN UNSAT ZONE (g/cm**3) 2.00E+00
SORPTION COEFFICIENT IN UNSAT ZONE (ml/g) 2.00E+02
HALF LIFE OF CONTAMINANT (y) 2.41E+04
INITIAL MASS OR ACTIVITY (mg or Ci) 1.00E+00
MOLECULAR WEIGHT (g/mole) 2.39E+02
SOLUBILITY LIMIT (mg/L) 7.11E+06
BULK DENSITY OF AQUIFER (g/cm**3) 2.00E+00
POROSITY OF AQUIFER 1.00E-01
SORPTION COEFFICIENT IN AQUIFER (ml/g) 2.00E+02
DISPERSIVITY X DIRECTION (m) 9.10E+00
```

DISPERSIVITY Y DIRECTION (m)	4.00E+00
PORE VELOCITY (m/y)	5.70E+02
WELL SCREEN THICKNESS (m)	1.20E+01
DISTANCE TO AQUIFER BELOW CONTAMINATION (m)	1.00E+02
DISTANCE TO RECEPTOR ALONG X AXIS (m)	2.50E+01
DISTANCE TO RECEPTOR ALONG Y AXIS (m)	0.00E+00
RADIOLOGICAL DOSE CONVERSION FACTOR (rem/Ci)	4.30E+06
UNITS OF CONTAMINANT	Ci

INPUT DATA FILE CREATED BY: _____ DATE / /

INPUT DATA CHECKED BY: _____ DATE / /

~~~~~

LIMITING SOIL CONCENTRATION CALCULATION

INITIAL SOURCE RESET TO 1.0 Ci

>>> INITIAL ACTIVITY CONVERTED TO MASS (mg) 1.61E+04

>>> VALUES CALCULATED IN SOURCE SUBROUTINE

*****

LEACH RATE CONSTANT (1/y)	3.3329E-04
UNSATURATED PORE VELOCITY (m/y)	3.1250E+01
DECAY CONSTANT (1/y)	2.8761E-05
RETARDATION FACTOR (SATURATED)	4.0010E+03
RETARDATION FACTOR (UNSATURATED)	4.1677E+03
SOLUBILITY LIMITED MASS (mg)	1.5999E+17
SOLUBILITY LIMITED ACTIVITY (Ci)	9.9385E+12
TRANSIT TIME IN UNSAT ZONE (years)	1.3337E+04
FRACTION DECAYED DURING UNSAT TRANSPORT	3.1858E-01

~~~~~

>>> EXPOSURE DATA FOR LIMITING SOIL CONCENTRATION

BODY WEIGHT (kg)	7.000E+01
AVERAGING TIME (days)	2.555E+04
WATER INTAKE RATE (L/d)	2.000E+00
EXPOSURE FREQUENCY (days/year)	3.500E+02
EXPOSURE DURATION (years)	7.000E+01
RADIOLOGICAL DOSE LIMIT (rem/y)	4.000E-03
CARCINOGENIC RISK CRITERIA	1.000E-06
HAZARD QUOTIENT	1.000E+00

~~~~~

>>> RESULTS OF CALCULATIONS

*****

PEAK TIME (y) = 1.399266E+04
 PEAK CONC (Ci/m**3) = 4.5035E-09
 AVERAGE INTEGRATED CONCENTRATION (Ci/m**3) = 4.5035E-09
 LIMITING SOIL CONCENTRATION (Ci/m**3) = 4.72E-05
 LIMITING SOIL CONCENTRATION (Ci/kg) = 2.62E-08
 LIMITING SOIL AMOUNT (Ci) = 2.95E-01
 LIMITING SOIL AMOUNT (mg) = 4.75E+03

Sample Problem 2: Input File

```
EXAMPLE PROBLEM #2 for users manual U-238 DCF includes Th-234 and Pa-234  TITLE
1 KFLAG
1 INTIME
25.0 25.0 1.00 AL WA THICKS
3.0 0.44 0.096 PERC THETAS THETAU
1.8 35.0 RHOS zKDS
2.0 6.0 RHOU zKDU
4.468E+09 1.4E-2 239.0 6.0 THALF QI ZMW SL
2.0 0.10 6.0 RHOA PHI zKDA
9.1 4.0 570 AX AY VX
12.0 100.0 THICK DEPTH
1 IMODE
2.4e5 DCF-RADMAX-NRADMAX-SFACTOR-RFD
50.0, 0. XD YD
70.0 2.555E+04 2.0 350. 70. 0.004 1.0E-6 1.0 BW AT WI EF ED DLIM CRISK HQ
```

Output File

```
TIME OF RUN 09:07:12.59
DATE OF RUN 03/10/92
INPUT FILE NAME: pb-2.par
OUTPUT FILE NAME: pb-2.out
```

```
*****
*
* This output was produced by the model:
*
* GWSCREEN
*
* A semi-analytical model for the assessment
* of the groundwater pathway from the leaching
* of surficial and buried contamination.
*
* Arthur S. Rood
* Idaho National Engineering Laboratory
* EG&G Idaho Inc.
* Subsurface and Environmental Modeling Unit
* PO Box 1625
* Idaho Falls, Idaho 83415
*****
```

>>> TITLE OF PROJECT:

EXAMPLE PROBLEM #2 for users manual U-238 DCF includes Th-234 and Pa-234 TIT

>>> INPUT DATA

```
*****
INTEGRATION TIME (years) 1
LENGTH OF SOURCE PARALLEL TO GW FLOW (m) 2.50E+01
WIDTH OF SOURCE PERPENDICULAR TO GW FLOW (m) 2.50E+01
THICKNESS OF SOURCE (m) 1.00E+00
PERCOLATION RATE (darcy vel m/y) 3.00E+00
VOLUMETRIC WATER CONTENT IN SOURCE 4.40E-01
VOLUMETRIC WATER CONTENT IN UNSATURATED ZONE 9.60E-02
BULK DENSITY AT SOURCE (g/cm**3) 1.80E+00
SORPTION COEFFICIENT AT SOURCE (ml/g) 3.50E+01
BULK DENSITY IN UNSAT ZONE (g/cm**3) 2.00E+00
SORPTION COEFFICIENT IN UNSAT ZONE (ml/g) 6.00E+00
HALF LIFE OF CONTAMINANT (y) 4.47E+09
INITIAL MASS OR ACTIVITY (mg or Ci) 1.00E+00
MOLECULAR WEIGHT (g/mole) 2.39E+02
SOLUBILITY LIMIT (mg/L) 6.00E+00
BULK DENSITY OF AQUIFER (g/cm**3) 2.00E+00
POROSITY OF AQUIFER 1.00E-01
SORPTION COEFFICIENT IN AQUIFER (ml/g) 6.00E+00
DISPERSIVITY X DIRECTION (m) 9.10E+00
```

DISPERSIVITY Y DIRECTION (m)	4.00E+00
PORE VELOCITY (m/y)	5.70E+02
WELL SCREEN THICKNESS (m)	1.20E+01
DISTANCE TO AQUIFER BELOW CONTAMINATION (m)	1.00E+02
DISTANCE TO RECEPTOR ALONG X AXIS (m)	5.00E+01
DISTANCE TO RECEPTOR ALONG Y AXIS (m)	0.00E+00
RADIOLOGICAL DOSE CONVERSION FACTOR (rem/Ci)	2.40E+05
UNITS OF CONTAMINANT	Ci

INPUT DATA FILE CREATED BY: _____ DATE / /

INPUT DATA CHECKED BY: _____ DATE / /

~~~~~ LIMITING SOIL CONCENTRATION CALCULATION

INITIAL SOURCE RESET TO 1.0 Ci

>>> INITIAL ACTIVITY CONVERTED TO MASS (mg) 2.98E+09

>>> VALUES CALCULATED IN SOURCE SUBROUTINE

*****

LEACH RATE CONSTANT (1/y)	4.7289E-02
UNSATURATED PORE VELOCITY (m/y)	3.1250E+01
DECAY CONSTANT (1/y)	1.5514E-10
RETARDATION FACTOR (SATURATED)	1.2100E+02
RETARDATION FACTOR (UNSATURATED)	1.2600E+02
SOLUBILITY LIMITED MASS (mg)	2.3790E+08
SOLUBILITY LIMITED ACTIVITY (Ci)	7.9710E-02
TRANSIT TIME IN UNSAT ZONE (years)	4.0320E+02
FRACTION DECAYED DURING UNSAT TRANSPORT	6.2551E-08

>>> EXPOSURE DATA FOR LIMITING SOIL CONCENTRATION

*****

BODY WEIGHT (kg)	7.000E+01
AVERAGING TIME (days)	2.555E+04
WATER INTAKE RATE (L/d)	2.000E+00
EXPOSURE FREQUENCY (days/year)	3.500E+02
EXPOSURE DURATION (years)	7.000E+01
RADIOLOGICAL DOSE LIMIT (rem/y)	4.000E-03
CARCINOGENIC RISK CRITERIA	1.000E-06
HAZARD QUOTIENT	1.000E+00

>>> RESULTS OF CALCULATIONS

*****

PEAK TIME (y) = 4.212383E+02
 PEAK CONC (Ci/m**3) = 6.9107E-07
 AVERAGE INTEGRATED CONCENTRATION (Ci/m**3) = 6.9107E-07
 LIMITING SOIL CONCENTRATION (Ci/m**3) = 5.51E-05
 LIMITING SOIL CONCENTRATION (Ci/kg) = 3.06E-08
 LIMITING SOIL AMOUNT (Ci) = 3.45E-02
 LIMITING SOIL AMOUNT (mg) = 1.03E+08

Sample Problem 3a: Input File

```
EXAMPLE PROBLEM #3A, Mercury limit based on a 1 year exposure RfD  TITLE
1 KFLAG
1 INTIME
25.0 25.0 1.00 AL WA THICKS
3.0 0.44 0.096 PERC THETAS THETAU
1.8 100.0 RHOS zKDS
2.0 100.0 RHOU zKDU
0.0E00 1.125E+8 461.0 4.5E-02 THALF QI ZMW SL
2.0 0.10 100.0 RHOA PHI zKDA
9.1 4.0 570 AX AY VX
12.0 100.0 THICK DEPTH
5 IMODE
3.0e-04 DCF-RADMAX-NRADMAX-SFACTOR-RFD
12.5, 0. XD YD
70.0 2.555E+04 2.0 350. 1.0 0.004 1.0E-6 1.0 BW AT WI EF ED DLIM CRISK HQ
```

Output File

TIME OF RUN 09:07:23.13
DATE OF RUN 03/10/92
INPUT FILE NAME: pb-3a.par
OUTPUT FILE NAME: pb-3a.out

```
*****
*
*   This output was produced by the model:
*
*   GWSCREEN
*
*   A semi-analytical model for the assessment
*   of the groundwater pathway from the leaching
*   of surficial and buried contamination.
*
*   Arthur S. Rood
*   Idaho National Engineering Laboratory
*   EG&G Idaho Inc.
*   Subsurface and Environmental Modeling Unit
*   PO Box 1625
*   Idaho Falls, Idaho 83415
*****
```

>>> TITLE OF PROJECT:
EXAMPLE PROBLEM #3A, Mercury limit based on a 1 year exposure RfD TITLE

```
*****
>>> INPUT DATA
*****
INTEGRATION TIME (years) 1
LENGTH OF SOURCE PARALLEL TO GW FLOW (m) 2.50E+01
WIDTH OF SOURCE PERPENDICULAR TO GW FLOW (m) 2.50E+01
THICKNESS OF SOURCE (m) 1.00E+00
PERCOLATION RATE (darcy vel m/y) 3.00E+00
VOLUMETRIC WATER CONTENT IN SOURCE 4.40E-01
VOLUMETRIC WATER CONTENT IN UNSATURATED ZONE 9.60E-02
BULK DENSITY AT SOURCE (g/cm**3) 1.80E+00
SORPTION COEFFICIENT AT SOURCE (ml/g) 1.00E+02
BULK DENSITY IN UNSAT ZONE (g/cm**3) 2.00E+00
SORPTION COEFFICIENT IN UNSAT ZONE (ml/g) 1.00E+02
HALF LIFE OF CONTAMINANT (y) 1.00E+30
INITIAL MASS OR ACTIVITY (mg or Ci) 1.00E+00
MOLECULAR WEIGHT (g/mole) 4.61E+02
SOLUBILITY LIMIT (mg/L) 4.50E-02
BULK DENSITY OF AQUIFER (g/cm**3) 2.00E+00
POROSITY OF AQUIFER 1.00E-01
SORPTION COEFFICIENT IN AQUIFER (ml/g) 1.00E+02
DISPERSIVITY X DIRECTION (m) 9.10E+00
```

DISPERSIVITY Y DIRECTION (m)	4.00E+00
PORE VELOCITY (m/y)	5.70E+02
WELL SCREEN THICKNESS (m)	1.20E+01
DISTANCE TO AQUIFER BELOW CONTAMINATION (m)	1.00E+02
DISTANCE TO RECEPTOR ALONG X AXIS (m)	1.25E+01
DISTANCE TO RECEPTOR ALONG Y AXIS (m)	0.00E+00
NON-CARCINOGENIC REFERENCE DOSE RfD (mg/kg/d)	3.00E-04
UNITS OF CONTAMINANT	mg

INPUT DATA FILE CREATED BY: _____ DATE / /

INPUT DATA CHECKED BY: _____ DATE / /

LIMITING SOIL CONCENTRATION CALCULATION

INITIAL SOURCE RESET TO 1.0 mg

>>> VALUES CALCULATED IN SOURCE SUBROUTINE

*****

LEACH RATE CONSTANT (1/y)	1.6626E-02
UNSATURATED PORE VELOCITY (m/y)	3.1250E+01
DECAY CONSTANT (1/y)	0.0000E+00
RETARDATION FACTOR (SATURATED)	2.0010E+03
RETARDATION FACTOR (UNSATURATED)	2.0843E+03
SOLUBILITY LIMITED MASS (mg)	5.0749E+06
SOLUBILITY LIMITED ACTIVITY (Ci)	0.0000E+00
TRANSIT TIME IN UNSAT ZONE (years)	6.6699E+03
FRACTION DECAYED DURING UNSAT TRANSPORT	0.0000E+00

>>> EXPOSURE DATA FOR LIMITING SOIL CONCENTRATION

*****

BODY WEIGHT (kg)	7.000E+01
AVERAGING TIME (days)	2.555E+04
WATER INTAKE RATE (L/d)	2.000E+00
EXPOSURE FREQUENCY (days/year)	3.500E+02
EXPOSURE DURATION (years)	1.000E+00
RADIOLOGICAL DOSE LIMIT (rem/y)	4.000E-03
CARCINOGENIC RISK CRITERIA	1.000E-06
HAZARD QUOTIENT	1.000E+00

>>> RESULTS OF CALCULATIONS

*****

PEAK TIME (y) = 6.736256E+03
 PEAK CONC (mg/m**3) = 2.1856E-07
 AVERAGE INTEGRATED CONCENTRATION (mg/m**3) = 2.1856E-07
 LIMITING SOIL CONCENTRATION (mg/m**3) = 5.61E+06
 LIMITING SOIL CONCENTRATION (mg/kg) = 3.12E+03
 LIMITING SOIL AMOUNT (mg) = 3.51E+09
 WARNING !!! THE LIMITING SOIL MASS OF 3.51E+09 mg
 EXCEEDS THE SOLUBILITY LIMITED SOURCE MASS OF 5.07E+06

TITLE

```

EXAMPLE PROBLEM #3b, Mercury concentration vs time for 1.125e8 mg source
0                                KFLAG
1                                INTIME
25.0  25.0  1.00                AL WA THICKS
3.0   0.44  0.096                PERC THETAS THETAU
1.8   100.0                      RHOS zKDS
2.0   100.0                      RHOU zKDU
0.0E00 1.125E+8 461.0  4.5E-02  THALF QI ZMW SL
2.0   0.10  100.0                RHOA PHI zKDA
9.1   4.0   570                  AX AY VX
12.0  100.0                      THICK DEPTH
5                                IMODE
3.0e-04                          DCF-RADMAX-NRADMAX-SFACTOR-RFD
12.5, 0.                          XD YD
70.0  2.555E+04  2.0  350.  70.  0.004  1.0E-6  1.0  BW AT WI EF ED DLIM CRISK HO

```

```
TIME OF RUN 12:23:18.01
DATE OF RUN 02/24/92
INPUT FILE NAME: pb-3a.par
OUTPUT FILE NAME: pb-3b.out
```

```
*****  
*  
*  
* GWSCREEN *  
*  
* This program uses equation 4.37 in Till and Meyer (NUREG CR/3332) for advection dispersion  
* in groundwater and Equation E.3 in RESRAD (DOE/CH/8901) for leaching of contaminants from  
* the source to calculate (1) The limiting soil concentration that would result in the ground-  
* water concentration not being exceeded by appropriate regulatory standards and (2),  
* groundwater concentration and contaminant fluxes as a function of time.  
*  
*  
* Arthur S. Rood  
* Idaho National Engineering Laboratory  
* EG&G Idaho Inc.  
* Subsurface and Environmental Modeling Unit  
* PO Box 1625  
* Idaho Falls, Idaho 83415  
*****
```

>>> TITLE OF PROJECT:

EXAMPLE PROBLEM #3A, Mercury limit based on a 1 year exposure RfD	TITLE
1. The following table shows the mercury levels in fish from a lake in Ontario. The table also shows the mercury levels in fish from a lake in Ontario. The table also shows the mercury levels in fish from a lake in Ontario.	
2. The following table shows the mercury levels in fish from a lake in Ontario. The table also shows the mercury levels in fish from a lake in Ontario. The table also shows the mercury levels in fish from a lake in Ontario.	
3. The following table shows the mercury levels in fish from a lake in Ontario. The table also shows the mercury levels in fish from a lake in Ontario. The table also shows the mercury levels in fish from a lake in Ontario.	
4. The following table shows the mercury levels in fish from a lake in Ontario. The table also shows the mercury levels in fish from a lake in Ontario. The table also shows the mercury levels in fish from a lake in Ontario.	
5. The following table shows the mercury levels in fish from a lake in Ontario. The table also shows the mercury levels in fish from a lake in Ontario. The table also shows the mercury levels in fish from a lake in Ontario.	
6. The following table shows the mercury levels in fish from a lake in Ontario. The table also shows the mercury levels in fish from a lake in Ontario. The table also shows the mercury levels in fish from a lake in Ontario.	
7. The following table shows the mercury levels in fish from a lake in Ontario. The table also shows the mercury levels in fish from a lake in Ontario. The table also shows the mercury levels in fish from a lake in Ontario.	
8. The following table shows the mercury levels in fish from a lake in Ontario. The table also shows the mercury levels in fish from a lake in Ontario. The table also shows the mercury levels in fish from a lake in Ontario.	
9. The following table shows the mercury levels in fish from a lake in Ontario. The table also shows the mercury levels in fish from a lake in Ontario. The table also shows the mercury levels in fish from a lake in Ontario.	
10. The following table shows the mercury levels in fish from a lake in Ontario. The table also shows the mercury levels in fish from a lake in Ontario. The table also shows the mercury levels in fish from a lake in Ontario.	

```
>>> INPUT DATA
```

*****

INTEGRATION TIME (years)	1
LENGTH OF SOURCE PARALLEL TO GW FLOW (m)	2.50E+01
WIDTH OF SOURCE PERPENDICULAR TO GW FLOW (m)	2.50E+01
THICKNESS OF SOURCE (m)	1.00E+00
PERCOLATION RATE (darcy vel m/y)	3.00E+00
VOLUMETRIC WATER CONTENT IN SOURCE	4.40E-01
VOLUMETRIC WATER CONTENT IN UNSATURATED ZONE	9.80E-02
BULK DENSITY AT SOURCE (g/cm**3)	1.80E+00
SORPTION COEFFICIENT AT SOURCE (ml/g)	1.00E+02
BULK DENSITY IN UNSAT ZONE (g/cm**3)	2.00E+00
SORPTION COEFFICIENT IN UNSAT ZONE (ml/g)	1.00E+02
HALF LIFE OF CONTAMINANT (y)	1.00E+38
INITIAL MASS OR ACTIVITY (mg or Ci)	1.00E+00
MOLECULAR WEIGHT (g/mole)	4.61E+02

SOLUBILITY LIMIT (mg/L)	4.50E-02
BULK DENSITY OF AQUIFER (g/cm**3)	2.00E+00
POROSITY OF AQUIFER	1.00E-01
SORPTION COEFFICIENT IN AQUIFER (ml/g)	1.00E+02
DISPERSIVITY X DIRECTION (m)	9.10E+00
DISPERSIVITY Y DIRECTION (m)	4.00E+00
PORE VELOCITY (m/y)	5.70E+02
WELL SCREEN THICKNESS (m)	1.20E+01
DISTANCE TO AQUIFER BELOW CONTAMINATION (m)	1.00E+02
DISTANCE TO RECEPTOR ALONG X AXIS (m)	1.25E+01
DISTANCE TO RECEPTOR ALONG Y AXIS (m)	0.00E+00
NON-CARCINOGENIC REFERENCE DOSE RfD (mg/kg/d)	3.00E-04
UNITS OF CONTAMINANT	mg

INPUT DATA FILE CREATED BY: _____ DATE / /

INPUT DATA CHECKED BY: _____ DATE / /

~~~~~

LIMITING SOIL CONCENTRATION CALCULATION

INITIAL SOURCE RESET TO 1.0 mg

>>> VALUES CALCULATED IN SOURCE SUBROUTINE

*****	
LEACH RATE CONSTANT (1/y)	1.6626E-02
UNSATURATED PORE VELOCITY (m/y)	3.1250E+01
DECAY CONSTANT (1/y)	0.0000E+00
RETARDATION FACTOR (SATURATED)	2.0010E+03
RETARDATION FACTOR (UNSATURATED)	2.0843E+03
SOLUBILITY LIMITED MASS (mg)	5.0749E+06
SOLUBILITY LIMITED ACTIVITY (Ci)	0.0000E+00
TRANSIT TIME IN UNSAT ZONE (years)	6.6699E+03
FRACTION DECAYED DURING UNSAT TRANSPORT	0.0000E+00

~~~~~

>>> EXPOSURE DATA FOR LIMITING SOIL CONCENTRATION

BODY WEIGHT (kg)	7.000E+01
AVERAGING TIME (days)	2.555E+04
WATER INTAKE RATE (L/d)	2.000E+00
EXPOSURE FREQUENCY (days/year)	3.500E+02
EXPOSURE DURATION (years)	1.000E+00
RADIOLOGICAL DOSE LIMIT (rem/y)	4.000E-03
CARCINOGENIC RISK CRITERIA	1.000E-06
HAZARD QUOTIENT	1.000E+00

~~~~~

>>> RESULTS OF CALCULATIONS

*****	
PEAK TIME (y) =	6.736256E+03
PEAK CONC (mg/m**3) =	2.1856E-07
AVERAGE INTEGRATED CONCENTRATION (mg/m**3) =	2.1856E-07
LIMITING SOIL CONCENTRATION (mg/m**3) =	5.61E+06
LIMITING SOIL CONCENTRATION (mg/kg) =	3.12E+03
LIMITING SOIL AMOUNT (mg) =	3.51E+09
THE LIMITING SOIL MASS OF	3.51E+09 mg EXCEEDS THE
SOLUBILITY LIMITED SOURCE MASS OF	5.07E+06

Sample problem 4: Input File

```
EXAMPLE PROBLEM #4 TCDD dioxin storage at Biloxi Mississippi'  TITLE
1 KFLAG
70 INTIME
250.0 250.0 0.61 AL WA THICKS
0.58 0.125 0.125 PERC THETAS THETAU
2.0 1.65E+02 RHOS zKDS
2.0 1.65E+03 RHOU zKDU
0.0E+00 7.6E4 322.0 2.0E-04 THALF QI ZMW SL
2.0 0.25 1.65E+03 RHOA PHI zKDA
30.9 9.0 50.6 AX AY VX
5.0 1.0 THICK DEPTH
4 IMODE
1.50e5 DCF-RADMAX-NRADMAX-SFACTOR-RFD
152.0, 0. XD YD
70.0 2.555E+04 2.0 350. 70. 0.004 1.0E-6 1.0 BW AT WI EF ED DLIM CRISK HQ
```

Output File

TIME OF RUN 09:09:00.24

DATE OF RUN 03/10/92

INPUT FILE NAME: pb-4.par

OUTPUT FILE NAME: pb-4.out

```
*****
*
*   This output was produced by the model:
*
*   GWSCREEN
*
*   A semi-analytical model for the assessment
*   of the groundwater pathway from the leaching
*   of surficial and buried contamination.
*
*   Arthur S. Rood
*   Idaho National Engineering Laboratory
*   EG&G Idaho Inc.
*   Subsurface and Environmental Modeling Unit
*   PO Box 1625
*   Idaho Falls, Idaho 83415
*****
```

>>> TITLE OF PROJECT:

'EXAMPLE PROBLEM #4 TCDD dioxin storage at Biloxi Mississippi' TITLE

>>> INPUT DATA

*****

```
INTEGRATION TIME (years) 70
LENGTH OF SOURCE PARALLEL TO GW FLOW (m) 2.50E+02
WIDTH OF SOURCE PERPENDICULAR TO GW FLOW (m) 2.50E+02
THICKNESS OF SOURCE (m) 6.10E-01
PERCOLATION RATE (darcy vel m/y) 5.80E-01
VOLUMETRIC WATER CONTENT IN SOURCE 1.25E-01
VOLUMETRIC WATER CONTENT IN UNSATURATED ZONE 1.25E-01
BULK DENSITY AT SOURCE (g/cm**3) 2.00E+00
SORPTION COEFFICIENT AT SOURCE (ml/g) 1.65E+02
BULK DENSITY IN UNSAT ZONE (g/cm**3) 2.00E+00
SORPTION COEFFICIENT IN UNSAT ZONE (ml/g) 1.65E+03
HALF LIFE OF CONTAMINANT (y) 1.00E+38
INITIAL MASS OR ACTIVITY (mg or Ci) 1.00E+00
MOLECULAR WEIGHT (g/mole) 3.22E+02
SOLUBILITY LIMIT (mg/L) 2.00E-04
BULK DENSITY OF AQUIFER (g/cm**3) 2.00E+00
POROSITY OF AQUIFER 2.50E-01
SORPTION COEFFICIENT IN AQUIFER (ml/g) 1.65E+03
DISPERSIVITY X DIRECTION (m) 3.09E+01
```

DISPERSIVITY Y DIRECTION (m)	9.00E+00
PORE VELOCITY (m/y)	5.08E+01
WELL SCREEN THICKNESS (m)	5.00E+00
DISTANCE TO AQUIFER BELOW CONTAMINATION (m)	1.00E+00
DISTANCE TO RECEPTOR ALONG X AXIS (m)	1.52E+02
DISTANCE TO RECEPTOR ALONG Y AXIS (m)	0.00E+00
CARCINOGENIC SLOPE FACTOR (mg/kg/d) ⁻¹	1.50E+05
UNITS OF CONTAMINANT	mg

INPUT DATA FILE CREATED BY: _____ DATE / /

INPUT DATA CHECKED BY: _____ DATE / /

LIMITING SOIL CONCENTRATION CALCULATION

INITIAL SOURCE RESET TO 1.0 mg

>>> VALUES CALCULATED IN SOURCE SUBROUTINE

*****	
LEACH RATE CONSTANT (1/y)	2.8802E-03
UNSATURATED PORE VELOCITY (m/y)	4.6400E+00
DECAY CONSTANT (1/y)	0.0000E+00
RETARDATION FACTOR (SATURATED)	1.3201E+04
RETARDATION FACTOR (UNSATURATED)	2.6401E+04
SOLUBILITY LIMITED MASS (mg)	2.5172E+06
SOLUBILITY LIMITED ACTIVITY (Ci)	0.0000E+00
TRANSIT TIME IN UNSAT ZONE (years)	5.6899E+03
FRACTION DECAYED DURING UNSAT TRANSPORT	0.0000E+00

>>> EXPOSURE DATA FOR LIMITING SOIL CONCENTRATION

*****	
BODY WEIGHT (kg)	7.000E+01
AVERAGING TIME (days)	2.555E+04
WATER INTAKE RATE (L/d)	2.000E+00
EXPOSURE FREQUENCY (days/year)	3.500E+02
EXPOSURE DURATION (years)	7.000E+01
RADIOLOGICAL DOSE LIMIT (rem/y)	4.000E-03
CARCINOGENIC RISK CRITERIA	1.000E-06
HAZARD QUOTIENT	1.000E+00

>>> RESULTS OF CALCULATIONS

*****	
PEAK TIME (y)	= 3.703294E+04
PEAK CONC (mg/m**3)	= 7.9490E-10
AVERAGE INTEGRATED CONCENTRATION (mg/m**3)	= 7.9490E-10
LIMITING SOIL CONCENTRATION (mg/m**3)	= 8.03E-03
LIMITING SOIL CONCENTRATION (mg/kg)	= 4.01E-06
LIMITING SOIL AMOUNT (mg)	= 3.06E+02

Sample Problem 5: Input File

EXAMPLE PROBLEM #5 for users manual Ra-226 limiting soil concentration

```

1 KFLAG
1 INTIME
100.0 100.0 5.0 AL WA THICKS
0.10 0.10 0.15 PERC THETAS THETAU
1.8 1.0E+02 RHOS zKDS
2.0 1.0E+01 RHOU zKDU
1.60E+03 9.00 226. 1.0 THALF QI ZMW SL
2.0 0.30 10.0 RHOA PHI zKDA
10.0 1.0 300 AX AY VX
5.0 25.0 THICK DEPTH
2 IMODE
5.0E-12 DCF-RADMAX-NRADMAX-SFACTOR-RFD
50.0, 0. XD YD
70.0 2.555E+04 2.0 350. 70. 0.004 1.0E-6 1.0 BW AT WI EF ED DLIM CRISK HQ
  
```

TITLE

Output File

TIME OF RUN 09:09:16.61
 DATE OF RUN 03/10/92
 INPUT FILE NAME: pb-5.par
 OUTPUT FILE NAME: pb-5.out

```

*****
*
* This output was produced by the model:
*
* GWSCREEN
*
* A semi-analytical model for the assessment
* of the groundwater pathway from the leaching
* of surficial and buried contamination.
*
* Arthur S. Rood
* Idaho National Engineering Laboratory
* EG&G Idaho Inc.
* Subsurface and Environmental Modeling Unit
* PU Box 1625
* Idaho Falls, Idaho 83415
*****
  
```

>>> TITLE OF PROJECT:
 EXAMPLE PROBLEM #5 for users manual Ra-226 limiting soil concentration

>>> INPUT DATA

```

*****
INTEGRATION TIME (years) 1
LENGTH OF SOURCE PARALLEL TO GW FLOW (m) 1.00E+02
WIDTH OF SOURCE PERPENDICULAR TO GW FLOW (m) 1.00E+02
THICKNESS OF SOURCE (m) 5.00E+00
PERCOLATION RATE (darcy vel m/y) 1.00E-01
VOLUMETRIC WATER CONTENT IN SOURCE 1.00E-01
VOLUMETRIC WATER CONTENT IN UNSATURATED ZONE 1.50E-01
BULK DENSITY AT SOURCE (g/cm**3) 1.80E+00
SORPTION COEFFICIENT AT SOURCE (ml/g) 1.00E+02
BULK DENSITY IN UNSAT ZONE (g/cm**3) 2.00E+00
SORPTION COEFFICIENT IN UNSAT ZONE (ml/g) 1.00E+01
HALF LIFE OF CONTAMINANT (y) 1.60E+03
INITIAL MASS OR ACTIVITY (mg or Ci) 1.00E+00
MOLECULAR WEIGHT (g/mole) 2.26E+02
SOLUBILITY LIMIT (mg/L) 1.00E+00
BULK DENSITY OF AQUIFER (g/cm**3) 2.00E+00
POROSITY OF AQUIFER 3.00E-01
SORPTION COEFFICIENT IN AQUIFER (ml/g) 1.00E+01
DISPERSIVITY X DIRECTION (m) 1.00E+01
  
```

DISPERSIVITY Y DIRECTION (m)	1.00E+00
PORE VELOCITY (m/y)	3.00E+02
WELL SCREEN THICKNESS (m)	5.00E+00
DISTANCE TO AQUIFER BELOW CONTAMINATION (m)	2.50E+01
DISTANCE TO RECEPTOR ALONG X AXIS (m)	5.00E+01
DISTANCE TO RECEPTOR ALONG Y AXIS (m)	0.00E+00
LIMITING RADIONUCLIDE GW CONCENTRATION (Ci/L)	5.00E-12
UNITS OF CONTAMINANT	Ci

INPUT DATA FILE CREATED BY: _____ DATE / /

INPUT DATA CHECKED BY: _____ DATE / /

LIMITING SOIL CONCENTRATION CALCULATION

INITIAL SOURCE RESET TO 1.0 Ci

>>> INITIAL ACTIVITY CONVERTED TO MASS (mg) 1.01E+03

>>> VALUES CALCULATED IN SOURCE SUBROUTINE

*****

LEACH RATE CONSTANT (1/y)	1.1105E-04
UNSATURATED PORE VELOCITY (m/y)	6.6667E-01
DECAY CONSTANT (1/y)	4.3322E-04
RETARDATION FACTOR (SATURATED)	6.7667E+01
RETARDATION FACTOR (UNSATURATED)	1.3433E+02
SOLUBILITY LIMITED MASS (mg)	9.0050E+09
SOLUBILITY LIMITED ACTIVITY (Ci)	8.9102E+06
TRANSIT TIME IN UNSAT ZONE (years)	5.0375E+03
FRACTION DECAYED DURING UNSAT TRANSPORT	8.8722E-01

>>> EXPOSURE DATA FOR LIMITING SOIL CONCENTRATION

*****

BODY WEIGHT (kg)	7.000E+01
AVERAGING TIME (days)	2.555E+04
WATER INTAKE RATE (L/d)	2.000E+00
EXPOSURE FREQUENCY (days/year)	3.500E+02
EXPOSURE DURATION (years)	7.000E+01
RADIOLOGICAL DOSE LIMIT (rem/y)	4.000E-03
CARCINOGENIC RISK CRITERIA	1.000E-06
HAZARD QUOTIENT	1.000E+00

>>> RESULTS OF CALCULATIONS

*****

PEAK TIME (y) = 5.097852E+03
 PEAK CONC (Ci/m**3) = 2.7017E-10
 AVERAGE INTEGRATED CONCENTRATION (Ci/m**3) = 2.7017E-10
 LIMITING SOIL CONCENTRATION (Ci/m**3) = 3.70E-04
 LIMITING SOIL CONCENTRATION (Ci/kg) = 2.06E-07
 LIMITING SOIL AMOUNT (Ci) = 1.85E+01
 LIMITING SOIL AMOUNT (mg) = 1.87E+04

Sample Problem 6a: Input File

EXAMPLE PROBLEM #6a for users manual Ni-59 solubility limited release

TITLE

```

1          KFLAG
1          INTIME
100.0 100.0 5.0      AL WA THICKS
0.10 0.10 0.15      PERC THETAS THETAU
1.8 2.0E-1          RHOS zKDS
2.0 8.0             RHOU zKDU
7.5E+04 1000.0 59. 3.6E-3 THALF QI ZMW SL (equal to 11 nCi/g conc)
2.0 0.30 10.0       RHOA PHI zKDA
10.0 1.0 300        AX AY VX
5.0 90.0            THICK DEPTH
1          IMODE
2.0E+02          DCF-
50.0, 0.         XD YD
70.0 2.555E+04 2.0 350. 70. 0.004 1.0E-6 1.0 BW AT WI EF ED DLIM CRISK HQ
  
```

Output File

TIME OF RUN 09:09:30.72

DATE OF RUN 03/10/92

INPUT FILE NAME: pb-6a.par

OUTPUT FILE NAME: pb-6a.out

```

*****
*
*   This output was produced by the model:
*
*   GWSCREEN
*
*   A semi-analytical model for the assessment
*   of the groundwater pathway from the leaching
*   of surficial and buried contamination.
*
*   Arthur S. Rood
*   Idaho National Engineering Laboratory
*   EG&G Idaho Inc.
*   Subsurface and Environmental Modeling Unit
*   PO Box 1625
*   Idaho Falls, Idaho 83415
*****
  
```

>>> TITLE OF PROJECT:

EXAMPLE PROBLEM #6 for users manual Ni-59 solubility limited release

>>> INPUT DATA

```

*****
INTEGRATION TIME (years)          1
LENGTH OF SOURCE PARALLEL TO GW FLOW (m)  1.00E+02
WIDTH OF SOURCE PERPENDICULAR TO GW FLOW (m)  1.00E+02
THICKNESS OF SOURCE (m)          5.00E+00
PERCOLATION RATE (darcy vel m/y)  1.00E-01
VOLUMETRIC WATER CONTENT IN SOURCE  1.00E-01
VOLUMETRIC WATER CONTENT IN UNSATURATED ZONE  1.50E-01
BULK DENSITY AT SOURCE (g/cm**3)  1.80E+00
SORPTION COEFFICIENT AT SOURCE (ml/g)  2.00E-01
BULK DENSITY IN UNSAT ZONE (g/cm**3)  2.00E+00
SORPTION COEFFICIENT IN UNSAT ZONE (ml/g)  8.00E+00
HALF LIFE OF CONTAMINANT (y)      7.50E+04
INITIAL MASS OR ACTIVITY (mg or Ci)  1.00E+00
MOLECULAR WEIGHT (g/mole)        5.90E+01
SOLUBILITY LIMIT (mg/L)          3.60E-03
BULK DENSITY OF AQUIFER (g/cm**3)  2.00E+00
POROSITY OF AQUIFER              3.00E-01
SORPTION COEFFICIENT IN AQUIFER (ml/g)  1.00E+01
DISPERSIVITY X DIRECTION (m)     1.00E+01
  
```

DISPERSIVITY Y DIRECTION (m)	1.00E+00
PORE VELOCITY (m/y)	3.00E+02
WELL SCREEN THICKNESS (m)	5.00E+00
DISTANCE TO AQUIFER BELOW CONTAMINATION (m)	9.00E+01
DISTANCE TO RECEPTOR ALONG X AXIS (m)	5.00E+01
DISTANCE TO RECEPTOR ALONG Y AXIS (m)	0.00E+00
RADIOLOGICAL DOSE CONVERSION FACTOR (rem/Ci)	2.00E+02
UNITS OF CONTAMINANT	Ci

INPUT DATA FILE CREATED BY: _____ DATE / /

INPUT DATA CHECKED BY: _____ DATE / /

LIMITING SOIL CONCENTRATION CALCULATION

INITIAL SOURCE RESET TO 1.0 Ci

>>> INITIAL ACTIVITY CONVERTED TO MASS (mg) 1.24E+04

>>> VALUES CALCULATED IN SOURCE SUBROUTINE

*****

LEACH RATE CONSTANT (1/y)	4.3478E-02
UNSATURATED PORE VELOCITY (m/y)	6.6667E-01
DECAY CONSTANT (1/y)	9.2420E-06
RETARDATION FACTOR (SATURATED)	6.7667E+01
RETARDATION FACTOR (UNSATURATED)	1.0767E+02
SOLUBILITY LIMITED MASS (mg)	8.2800E+04
SOLUBILITY LIMITED ACTIVITY (Ci)	6.6949E+00
TRANSIT TIME IN UNSAT ZONE (years)	1.4535E+04
FRACTION DECAYED DURING UNSAT TRANSPORT	1.2570E-01

>>> EXPOSURE DATA FOR LIMITING SOIL CONCENTRATION

*****

BODY WEIGHT (kg)	7.000E+01
AVERAGING TIME (days)	2.555E+04
WATER INTAKE RATE (L/d)	2.000E+00
EXPOSURE FREQUENCY (days/year)	3.500E+02
EXPOSURE DURATION (years)	7.000E+01
RADIOLOGICAL DOSE LIMIT (rem/y)	4.000E-03
CARCINOGENIC RISK CRITERIA	1.000E-06
HAZARD QUOTIENT	1.000E+00

>>> RESULTS OF CALCULATIONS

*****

PEAK TIME (y) = 1.455811E+04
 PEAK CONC (Ci/m**3) = 4.0176E-07
 AVERAGE INTEGRATED CONCENTRATION (Ci/m**3) = 4.0176E-07
 LIMITING SOIL CONCENTRATION (Ci/m**3) = 1.12E-03
 LIMITING SOIL CONCENTRATION (Ci/kg) = 7.90E-07
 LIMITING SOIL AMOUNT (Ci) = 7.11E+01
 LIMITING SOIL AMOUNT (mg) = 8.80E+05
 WARNING !!! THE LIMITING SOIL MASS OF 8.80E+05 mg
 EXCEEDS THE SOLUBILITY LIMITED SOURCE MASS OF 8.28E+04

Sample Problem 6b: Input File

```

EXAMPLE PROBLEM #6b for users manual Ni-59 solubility limited release
0          KFLAG
1          INTIME
100.0 100.0 5.0      AL WA THICKS
0.10 0.10 0.15      PERC THETAS THETAU
1.8 2.0E-1          RHOS zKDS
2.0 8.0            RHOU zKDU
7.5E+04 1000.0 59. 3.6E-3  THALF QI ZMW SL (equal to 11 nCi/g conc)
2.0 0.30 10.0      RHOA PHI zKDA
10.0 1.0 300       AX AY VX
5.0 90.0           THICK DEPTH
1                IMODE
2.0E+02          DCF-
50.0, 0.         XD YD
70.0 2.555E+04 2.0 350. 70. 0.004 1.0E-6 1.0 BW AT WI EF ED DLIM CRISK HQ
  
```

TITLE

Output File

```

TIME OF RUN 09:10:35.65
DATE OF RUN 03/10/92
INPUT FILE NAME: pb-6b.par
OUTPUT FILE NAME: pb-6b.lst
  
```

```

*****
*
*   This output was produced by the model:
*
*   GWSCREEN
*
*   A semi-analytical model for the assessment
*   of the groundwater pathway from the leaching
*   of surficial and buried contamination.
*
*   Arthur S. Rood
*   Idaho National Engineering Laboratory
*   EG&G Idaho Inc.
*   Subsurface and Environmental Modeling Unit
*   PO Box 1625
*   Idaho Falls, Idaho 83415
*****
  
```

```

>>> TITLE OF PROJECT:
EXAMPLE PROBLEM #6b for users manual Ni-59 solubility limited release
  
```

>>> INPUT DATA

```

*****
INTEGRATION TIME (years)          1
LENGTH OF SOURCE PARALLEL TO GW FLOW (m)  1.00E+02
WIDTH OF SOURCE PERPENDICULAR TO GW FLOW (m)  1.00E+02
THICKNESS OF SOURCE (m)          5.00E+00
PERCOLATION RATE (darcy vel m/y)  1.00E-01
VOLUMETRIC WATER CONTENT IN SOURCE  1.00E-01
VOLUMETRIC WATER CONTENT IN UNSATURATED ZONE  1.50E-01
BULK DENSITY AT SOURCE (g/cm**3)  1.80E+00
SORPTION COEFFICIENT AT SOURCE (ml/g)  2.00E-01
BULK DENSITY IN UNSAT ZONE (g/cm**3)  2.00E+00
SORPTION COEFFICIENT IN UNSAT ZONE (ml/g)  8.00E+00
HALF LIFE OF CONTAMINANT (y)      7.50E+04
INITIAL MASS OR ACTIVITY (mg or Ci)  1.00E+03
MOLECULAR WEIGHT (g/mole)        5.90E+01
SOLUBILITY LIMIT (mg/L)          3.60E-03
BULK DENSITY OF AQUIFER (g/cm**3)  2.00E+00
POROSITY OF AQUIFER              3.00E-01
SORPTION COEFFICIENT IN AQUIFER (ml/g)  1.00E+01
DISPERSIVITY X DIRECTION (m)     1.00E+01
  
```

DISPERSIVITY Y DIRECTION (m) 1.00E+00
 PORE VELOCITY (m/y) 3.00E+02
 WELL SCREEN THICKNESS (m) 5.00E+00
 DISTANCE TO AQUIFER BELOW CONTAMINATION (m) 9.00E+01
 DISTANCE TO RECEPTOR ALONG X AXIS (m) 5.00E+01
 DISTANCE TO RECEPTOR ALONG Y AXIS (m) 0.00E+00
 RADIOLOGICAL DOSE CONVERSION FACTOR (rem/Ci) 2.00E+02
 UNITS OF CONTAMINANT Ci

INPUT DATA FILE CREATED BY: _____ DATE / /

INPUT DATA CHECKED BY: _____ DATE / /

>>> INITIAL ACTIVITY CONVERTED TO MASS (mg) 1.24E+07
 >>> VALUES CALCULATED IN SOURCE SUBROUTINE

*****
 LEACH RATE CONSTANT (1/y) 4.3478E-02
 UNSATURATED PORE VELOCITY (m/y) 6.6667E-01
 DECAY CONSTANT (1/y) 9.2420E-06
 RETARDATION FACTOR (SATURATED) 6.7667E+01
 RETARDATION FACTOR (UNSATURATED) 1.0767E+02
 SOLUBILITY LIMITED MASS (mg) 8.2800E+04
 SOLUBILITY LIMITED ACTIVITY (Ci) 6.6949E+00
 TRANSIT TIME IN UNSAT ZONE (years) 1.4535E+04
 FRACTION DECAYED DURING UNSAT TRANSPORT 1.2570E-01

>>> SOLUBILITY LIMITED RELEASE FOR 3.3090E+03 YEARS
 >>> CONCENTRATION VS TIME MODE

(simulation time) TIME (years)	CUMULATIVE SOURCE FLUX (Ci)	(simulation time+transit time) TIME (years)	CUMULATIVE AQUIFER FLUX (Ci)	GW CONC (Ci/m**3)	AQUIFER FLUX (Ci/year)
3.0000E+03	8.7325E+02	1.7535E+04	7.6349E+02	5.6513E-06	2.5450E-01
3.0200E+03	8.7908E+02	1.7555E+04	7.6858E+02	5.6513E-06	2.5450E-01
3.0400E+03	8.8490E+02	1.7575E+04	7.7367E+02	5.6513E-06	2.5450E-01
3.0600E+03	8.9072E+02	1.7595E+04	7.7876E+02	5.6513E-06	2.5450E-01
3.0800E+03	8.9654E+02	1.7615E+04	7.8385E+02	5.6513E-06	2.5450E-01
3.1000E+03	9.0236E+02	1.7635E+04	7.8894E+02	5.6513E-06	2.5450E-01
3.1200E+03	9.0818E+02	1.7655E+04	7.9403E+02	5.6513E-06	2.5450E-01
3.1400E+03	9.1401E+02	1.7675E+04	7.9911E+02	5.6513E-06	2.5450E-01
3.1600E+03	9.1983E+02	1.7695E+04	8.0420E+02	5.6513E-06	2.5450E-01
3.1800E+03	9.2565E+02	1.7715E+04	8.0929E+02	5.6513E-06	2.5450E-01
3.2000E+03	9.3147E+02	1.7735E+04	8.1438E+02	5.6513E-06	2.5450E-01
3.2200E+03	9.3729E+02	1.7755E+04	8.1947E+02	5.6513E-06	2.5450E-01
3.2400E+03	9.4311E+02	1.7775E+04	8.2456E+02	5.6513E-06	2.5450E-01
3.2600E+03	9.4894E+02	1.7795E+04	8.2965E+02	5.6513E-06	2.5450E-01
3.2800E+03	9.5476E+02	1.7815E+04	8.3474E+02	5.6513E-06	2.5450E-01
3.3000E+03	9.6058E+02	1.7835E+04	8.3983E+02	5.6513E-06	2.5450E-01
3.3200E+03	9.6574E+02	1.7855E+04	8.4435E+02	5.1725E-06	1.5746E-01
3.3400E+03	9.6815E+02	1.7875E+04	8.4645E+02	3.0445E-06	6.5998E-02
3.3600E+03	9.6915E+02	1.7895E+04	8.4733E+02	1.3884E-06	2.7662E-02
3.3800E+03	9.6958E+02	1.7915E+04	8.4770E+02	5.9558E-07	1.1594E-02
3.4000E+03	9.6975E+02	1.7935E+04	8.4786E+02	2.5102E-07	4.8595E-03
3.4200E+03	9.6983E+02	1.7955E+04	8.4792E+02	1.0530E-07	2.0368E-03
3.4400E+03	9.6986E+02	1.7975E+04	8.4795E+02	4.4140E-08	8.5368E-04
3.4600E+03	9.6987E+02	1.7995E+04	8.4796E+02	1.8499E-08	3.5781E-04
3.4800E+03	9.6988E+02	1.8015E+04	8.4796E+02	7.7523E-09	1.4997E-04
3.5000E+03	9.6988E+02	1.8035E+04	8.4797E+02	3.2487E-09	6.2857E-05

APPENDIX B: GMSCREEN CODE LISTING

APPENDIX B: GWSCREEN CODE LISTING

PROGRAM GWS6

C
C AUTHOR A.S. ROOD
C APRIL, 1991

C ***** NOTE *****
C FOR COMPILATION ON INEL CRAY, THE FUNCTION DEFINITION MUST CHANGE
C FROM REAL*8 FUNCTION(XXXX) TO FUNCTION(XXXX). REAL*8 FUNCTION(XXXX)
C IS THE LAHEY FORMAT AND FUNCTION(XXXX) IS CRAY UNIX. THE FOLLOWING
C FUNCTIONS ARE AFFECTED; AREA, FUNC, ERF, GAMMP, GAMMLN
C *****

C This program is designed to calculate the concentration of a contaminant
C in the surface soil that results in a groundwater concentration that is
C at the acceptable regulatory standard for either maximum concentration,
C radiological dose or carcinogenic risk. The program also calculates the
C groundwater concentration as a function of time for an initial inventory.

C The program uses a three stage approach:
C First, the leach rate of the contaminant from the surface is
C calculated. Next the transit time from the surface to the aquifer is
C calculated. Any decay which occurs during transit is accounted for and plug
C flow is assumed. The contaminant is then assumed to dissolve in the aquifer
C and initially mix in an volume that is equivalent to the area of the source
C on the surface times the thickness of the well screen. The peak, or an
C average integrated concentration is then calculated and compared with the
C appropriate regulatory limit.

C This program uses equation 4.37 in NUREG CR/3332 to calculate groundwater
C concentrations. The leach rate from the source is determined using
C methodology in the RESRAD code (DOE/CH/8901).
C Solution for time variant releases
C are taken from the Gaussian Quad integration. Limits of integration are
C determined by Codell's method in NUREG-0868. Gaus Quad integration
C was used in two routines in the code. The convolution integral which
C describes groundwater concentration resulting from a non-steady state
C release is solved using a modified Gaus Quad routine found in Numerical
C Recipes (Press et al) and found in the QGAUS2 subroutine.

C
C A second integration routine was taken also from Numerical Recipes (Press et al
C 1987) and is used in the subroutine QGAUS. This routine calculates the
C average integrated concentration.

IMPLICIT REAL*8 (A-H,O-Z)

C INPUT VARIABLES:

C TITLE = TITLE OF PROJECT
C KFLAG (0) = CONCENTRATION VS TIME
C (1) = LIMITING SOIL CONCENTRATION
C INTIME = INTEGRATING TIME. INTIME MUST EQUAL THE EXPOSURE DURATION
C FOR CARCINOGENIC CALCULATIONS
C AL = LENGTH OF SOURCE PARALLEL TO FLOW (m)
C WA = WIDTH OF SOURCE PERPENDICULAR TO FLOW (m)
C THICKS = THICKNESS OF CONTAMINATED ZONE (m)
C PERC = PERCOLATION RATE (m/y)
C THETAS = VOLUMETRIC MOISTURE CONTENT IN CONTAMINATED ZONE
C THETAU = VOLUMETRIC MOISTURE CONTENT IN UNSATURATED ZONE
C RHOS = DENSITY OF SURFACE SOIL (g/cm3)
C zKDS = SORPTION COEFFICIENT IN SOURCE (cm3/g)
C THALF = HALF LIFE (y)
C QI = INITIAL MASS IN SOURCE COMPARTMENT (CI OR MG)
C ZMW = MOLECULAR WEIGHT (G/MOLE)
C SL = SOLUBILITY LIMIT OF CONTAMINANT (MG/L)
C RHOA = DENSITY OF AQUIFER (G/CM3)

C PHI = POROSITY OF AQUIFER
 C ZKDA = SORPTION COEFFICIENT IN AQUIFER
 C AX = DISPERSIVITY IN THE X DIRECTION (m)
 C AY = DISPERSIVITY IN THE Y DIRECTION (m)
 C VX = PORE VELOCITY IN AQUIFER, (m/y)
 C THICK = THICKNESS OF WELL SCREEN (m)
 C DEPTH = DEPTH OF AQUIFER FROM BASE OF CONTAMINATED ZONE (m)
 C IMODE = (1) LIMIT BASED ON 4 MREM/Y
 C   (2) LIMIT BASED ON MAXIMUM CONTAMINANT LIMIT FOR RADIONUCLIDES
 C   (3) LIMIT BASED ON MAXIMUM CONTAMINANT LIMIT FOR CHEMICALS
 C   (4) LIMIT BASED ON CARCINOGENIC RISK (1.0E-6)
 C   (5) LIMIT BASED ON REFERENCE DOSE
 C DCF = DOSE CONVERSION FACTOR (rem/ci)
 C RADMAX = GROUNDWATER CRITERIA LIMIT FOR RADIONUCLIDES (ci/L)
 C ZRADMAX = GROUNDWATER CRITERIA LIMIT FOR NON-RAD (mg/L)
 C SFACTOR = SLOPE FACTOR FOR CARCINOGENIC RISK CALCULATION (MG/KG/D)**-1
 C RFD = REFERENCE DOSE FOR NON-CARCINOGENIC EFFECTS (MG/KG/D)
 C XD = RECEPTOR DISTANCE DOWNGRAIENT (m)
 C YD = RECEPTOR DISTANCE PERPENDICULAR TO GW FLOW (m)
 C TSTART = START TIME FOR CALCULATIONS (DIAGNOSTIC MODE) (y)
 C TEND = END TIME FOR CALCULATIONS (DIAGNOSTIC MODE) (y)
 C TP = PRINT TIME STEP (y)
 C EXPOSURE DATA
 C BW = BODY WEIGHT (kg)
 C AT = AVERAGING TIME (days)
 C WI = WATER INTAKE RATE (L/d)
 C EF = EXPOSURE FREQUENCY (years)
 C ED = EXPOSURE DURATION THIS VALUE SHOULD BE THE SAME AS INTIME FOR
 C   CARCINOGEN CALCULATIONS(years)
 C DLIM = RADIOLOGICAL DOSE LIMIT (rem/y)
 C CRISK = CARCINOGENIC RISK CRITERIA
 C HQ = HAZARD QUOTIENT

C FIXED VALUES

C UNITS = MG OR CI

C CALCULATED VARIABLES IN MAIN PROGRAM

C QM = INITIAL SOURCE MASS FOR RADIONUCLIDES
 C TTIME = CHARACTER VARIABLE FOR HOLDING TIME OF RUN
 C DDATE = CHARACTER VARIABLE FOR HOLDING DATA OF RUN
 C CSD = LIMITING SOIL CONCENTRATION IN CI OR mg PER KG
 C QACT = SOLUBILITY LIMITED MASS CONVERTED TO ACTIVITY
 C QCS = LIMITING CONTAMINANT AMOUNT (CI OR MG)
 C QMCS = LIMITING CONTAMINANT MASS (MG)

C CHARACTER VALUES

CHARACTER*40 FILEIN,FILEOU
 CHARACTER*78 TITLE
 CHARACTER*2 UNITS
 CHARACTER*45 MODE

C COMMON STATEMENTS

COMMON /GW/ AX, AY, VX, THICK, AL, WA, GWLIM, RD, PHI, DLR,
 ! SLEACH, FRAC, WFLUX, SL, QSL, QI, ZMW, TRANSIT, XD, YD,IMODE

COMMON /SOURCE/ THETAS, THETAU, RHOS, THICKS, zKDS,
 ! DEPTH, PERC, THALF, zKDA, RHOA, zKDU, RHOU, QM

COMMON /EXPOSURE/BW,AT,WI,EF,ED,DLIM,CRISK,HQ

COMMON /FILES/ FILEIN,FILEOU,TITLE

```

C ***** READ DATA IN SUBROUTINE INPUT *****

      CALL INPUT(KFLAG,INTIME,XDUMMY,IFLAG)
      IF(IFLAG.EQ.1)THEN
        GOTO 999
      ENDIF

C ASSIGN A VALUE TO XDUMMY BASED ON THE VALUE OF IMODE

      IF(IMODE.EQ.1)THEN
        DCF=XDUMMY
        UNITS='Ci'
        MODE='RADIOLOGICAL DOSE CONVERSION FACTOR (rem/Ci)'
C      USER IS WARNED THAT INTIME SHOULD BE SET TO 1.0 FOR RAD CALC
        IF(INTIME.GT.1)THEN
          WRITE(*,11)
          WRITE(2,11)
        ENDIF
      ENDIF

      IF(IMODE.EQ.2)THEN
        RADMAX=XDUMMY
        UNITS='Ci'
        MODE='LIMITING RADIONUCLIDE GW CONCENTRATION (Ci/L)'
      ENDIF

      IF(IMODE.EQ.3)THEN
        ZRADMAX=XDUMMY
        UNITS='mg'
        MODE='LIMITING CONTAMINANT GW CONCENTRATION (mg/L)'
      ENDIF

      IF(IMODE.EQ.4)THEN
        SFACTOR=XDUMMY
        UNITS='mg'
        MODE='CARCINOGENIC SLOPE FACTOR (mg/kg/d)-1'
      ENDIF

      IF(IMODE.EQ.5)THEN
        RFD=XDUMMY
        UNITS='mg'
        MODE='NON-CARCINOGENIC REFERENCE DOSE RFD (mg/kg/d)'
      ENDIF

      WRITE(*,*) TITLE

      WRITE(2,2000) INTIME,AL,WA,THICKS,PERC,THETAS,THETAU,RHOS,ZKDS,
        IRHOU,ZKDU,THALF,QI,ZMW,SL,RHOA,PHI,ZKDA,AX,AY,VX,THICK,DEPTH,XD,
        IYD,MODE,XDUMMY,UNITS

      IF(KFLAG.EQ.1)THEN
        WRITE(2,352) UNITS
      ENDIF

C  convert initial activity to mass if a radionuclide for solubility check
C  CONVERT CI TO MG.  USE THE CONVERSIONS 1 Ci=3.7E10 DPS, 3.1536 S/Y
C  6.023E23 ATOMS/MOLE AND 1000 MG/G

      IF(IMODE.LE.2)THEN
        QM=(((QI*3.7E10)*3.1536E7*ZMW)/(LOG(2.)/THALF))/6.023E23*1000
        WRITE(2,2001) QM
      ELSE
        QM=QI
      ENDIF

```

```

C *****
C ***** CALCULATE SOURCE *****
C ***** RELEASE AND FIXED *****
C ***** VALUES *****
C *****

```

```

CALL SOURCEX(UX,RDU,TSL,KFLAG)

```

```

C CONVERT SOLUBILITY LIMITED MASS TO ACTIVITY
  IF(IMODE.LE.2)THEN
    QACT=(QSL*DLR*(1/3.1536E+07)*6.023E23)/(3.7E10*ZMW*1000)
  ELSE
    QACT=0.0
  ENDIF

```

```

FRACD=1.00-FRAC
WRITE(2,3000) SLEACH,UX,DLR,RD,RDU,QSL,QACT,TRANSIT,FRACD
WRITE(*,3000) SLEACH,UX,DLR,RD,RDU,QSL,QACT,TRANSIT,FRACD

```

```

C IF INITIAL MASS IS GREATER THAN SOLUBILITY LIMITED MASS THEN PRINT
C SOLUBILITY LIMITED MASS FLUX IS IN CONTROL FOR THE TIME TSL

```

```

  IF(TSL.GT.0.)THEN
    WRITE(2,3001)TSL
    WRITE(*,3001)TSL
  ENDIF

```

```

C *****
C ***** CALCULATE CONCENTRATION AS A FUNCTION *****
C ***** OF TIME *****
C *****

```

```

  IF(KFLAG.EQ.0)THEN
    CALL CTIME(UNITS,TSL)
    CLOSE(2,STATUS='KEEP')
    GOTO 999
  ENDIF

```

```

C *****
C ***** CALCULATE LIMITING SOIL CONCENTRATION *****
C *****

```

```

C WRITE EXPOSURE DATA TO OUTPUT FILE
  WRITE(2,400) BW,AT,WI,EF,ED,DLIM,CRISK,HQ

```

```

C CHECK EXPOSURE DURATION TO MAKE SURE IT IS EQUAL TO INTEGRATION TIME
C FOR CARCINOGENIC CALCULATIONS

```

```

  IF(IMODE.EQ.4)THEN
    IF(ED.NE.INTIME)THEN
      WRITE(*,13)
      WRITE(2,13)
      GOTO 999
    ENDIF
  ENDIF

```

```

C CALCULATE PEAK GROUNDWATER CONCENTRATION
  CALL PEAK(GWPEAK,PKTIME,TSL)
  pktimeA=pktime+transit
  WRITE(*,4000) PKTIMEA,units,GWPEAK
  WRITE(2,4000) PKTIMEA,units,GWPEAK

```

```

C CALCULATE AVERAGE INTEGRATED CONC. (AIC) OR IF 1 YEAR INTEGRATION TIME
C IS USED THEN USE THE PEAK CONCENTRATION

```



```

      IF (INTIME.GT.1) THEN
        CALL GWINT (INTIME,PKTIME,TSL,AIC)
      ELSE
        AIC=GWPEAK
      ENDIF
      WRITE(2,200) UNITS,AIC
      WRITE(*,200) UNITS,AIC

C ***** CALCULATE SOIL CONC FOR THE GIVEN CONTAMINANT *****

      VOL=THICKS*WA*AL

C IMODE = (1) LIMIT BASED ON 4 MREM/Y
C          (2) LIMIT BASED ON MAXIMUM CONTAMINANT LIMIT FOR RADIONUCLIDES
C          (3) LIMIT BASED ON MAXIMUM CONTAMINANT LIMIT FOR CHEMICALS
C          (4) LIMIT BASED ON CARCINOGENIC RISK (1.0E-6)
C          (5) LIMIT BASED ON REFERENCE DOSE

C ***** RADIOLOGICAL DOSE
      IF (IMODE.EQ.1) THEN
        CALL RAD (CS,DCF,AIC,VOL)
      ENDIF

C ***** RADIONUCLIDE CONCENTRATION IN GROUNDWATER
      IF (IMODE.EQ.2) THEN
        CONVERT RADMAX TO CI/M3
        1/VOL=THE SOIL CONCENTRATION FOR A UNIT INVENTORY
        RADMAX=RADMAX*1000
        CS=RADMAX/AIC*(1/VOL)
      ENDIF

C ***** NON-RAD CONCENTRATION IN GROUNDWATER
      IF (IMODE.EQ.3) THEN
        CONVERT ZRADMAX TO mg/M3
        1/VOL=THE SOIL CONCENTRATION FOR A UNIT INVENTORY
        ZRADMAX=ZRADMAX*1000
        CS=ZRADMAX/AIC*(1/VOL)
      ENDIF

C ***** CARCINOGENIC RISK
      IF (IMODE.EQ.4) THEN
        CALL CARCIN (CS,SFACTOR,AIC,VOL)
      ENDIF

C ***** NON CARCINOGENIC CHRONIC EXPOSURE
      IF (IMODE.EQ.5) THEN
        CALL NCARCIN (CS,RFD,AIC,VOL)
      ENDIF

C ***** OUTPUT RESULTS AND EXIT *****
C CONVERT CONCENTRATION TO CI/KG OR mg/KG AND CALCULATE TOTAL AMOUNT IN
C SOURCE VOLUME

      CSD=CS/(RHOS*1000)
      QCS=CS*AL*WA*THICKS
C CONVERT LIMITING ACTIVITY TO AMOUNT TO MASS
      IF (IMODE.LE.2) THEN
        QMCS=(((QCS*3.7E10)*3.1536E7*ZMW)/DLR)/6.023E23)*1000
      ELSE
        QMCS=QCS
      ENDIF

      WRITE(2,300) UNITS,CS
      WRITE(2,350) UNITS,CSD
      WRITE(2,301) UNITS,QCS

```

```

WRITE(*,300) UNITS,CS
WRITE(*,350) UNITS,CSD
WRITE(*,301) UNITS,QCS

IF(IMODE.LE.2)THEN
  WRITE(2,302) QMCS
ENDIF

C COMPARE TOTAL MASS IN SOURCE VOLUME WITH THE SOLUBILITY
C LIMITED MASS

IF(QMCS.GT.QSL)THEN
  WRITE(2,351) QMCS,QSL
ENDIF
write(*,*)
WRITE(*,*) '      Normal Termination'

CLOSE(2,STATUS='KEEP')

11 FORMAT('
  1/,2X,'WARNING: VARIABLE INTIME SHOULD BE EQUAL TO 1 YEAR'
  1/,12X,'FOR RADIOLOGICAL DOSE CALCULATION'
  1/,' ')

12 FORMAT('
  1/,2X,'WARNING: VARIABLE INTIME SHOULD BE EQUAL TO 1 YEAR'
  1/,12X,'FOR MAXIMUM CONTAMINANT CONCENTRATION'
  1/,' ')

13 FORMAT('
  1/,2X,'ERROR:EXPOSURE DURATION (ED) MUST EQUAL INTEGRATION TIME (IN
  ITIME'
  1/,2X,'FOR CARCINOGENIC CALCULATION')

200 FORMAT(2X,'AVERAGE INTEGRATED CONCENTRATION (' ,a2,'/m**3) =' ,1PE11
  1.4)

300 FORMAT(2X,'LIMITING SOIL CONCENTRATION (' ,a2,'/m**3) =' ,1PE9.2)
301 FORMAT(2X,'LIMITING SOIL AMOUNT (' ,a2,') =' ,1PE9.2)
302 FORMAT(2X,'LIMITING SOIL AMOUNT (mg) =' ,1PE9.2)

350 FORMAT(2X,'LIMITING SOIL CONCENTRATION (' ,a2,'/kg) =' ,1PE9.2)
351 FORMAT(2X,'WARNING !!! THE LIMITING SOIL MASS OF ' ,1PE9.2,' mg'
  1/,2X,'EXCEEDS THE SOLUBILITY LIMITED SOURCE MASS OF ' ,1PE9.2)

352 FORMAT(2X,'
  1/,2X,'LIMITING SOIL CONCENTRATION CALCULATION'
  1/,2X,'INITIAL SOURCE RESET TO 1.0 ' ,a2)

400 FORMAT(2X,'>>> EXPOSURE DATA FOR LIMITING SOIL CONCENTRATION'
  1/,2X,'*****'
  1/,2X,'BODY WEIGHT (kg) ' ,1PE10.3
  1/,2X,'AVERAGING TIME (days) ' ,1PE10.3
  1/,2X,'WATER INTAKE RATE (L/d) ' ,1PE10.3
  1/,2X,'EXPOSURE FREQUENCY (days/year) ' ,1PE10.3
  1/,2X,'EXPOSURE DURATION (years) ' ,1PE10.3
  1/,2X,'RADIOLOGICAL DOSE LIMIT (rem/y) ' ,1PE10.3
  1/,2X,'CARCINOGENIC RISK CRITERIA ' ,1PE10.3
  1/,2X,'HAZARD QUOTIENT ' ,1PE10.3
  1/,2X,'-----'
  1/,2X,'>>> RESULTS OF CALCULATIONS '
  1/,2X,'*****')

2000 FORMAT(2X,'>>> INPUT DATA '
  1/,2X,'*****')

```

```

1/,2X,'INTEGRATION TIME (years) ',I3
1/,2X,'LENGTH OF SOURCE PARALLEL TO GW FLOW (m) ',1PE9.2
1/,2X,'WIDTH OF SOURCE PERPENDICULAR TO GW FLOW (m) ',1PE9.2
1/,2X,'THICKNESS OF SOURCE (m) ',1PE9.2
1/,2X,'PERCOLATION RATE (darcy vel m/y) ',1PE9.2
1/,2X,'VOLUMETRIC WATER CONTENT IN SOURCE ',1PE9.2
1/,2X,'VOLUMETRIC WATER CONTENT IN UNSATURATED ZONE ',1PE9.2
1/,2X,'BULK DENSITY AT SOURCE (g/cm**3) ',1PE9.2
1/,2X,'SORPTION COEFFICIENT AT SOURCE (ml/g) ',1PE9.2
1/,2X,'BULK DENSITY IN UNSAT ZONE (g/cm**3) ',1PE9.2
1/,2X,'SORPTION COEFFICIENT IN UNSAT ZONE (ml/g) ',1PE9.2
1/,2X,'HALF LIFE OF CONTAMINANT (y) ',1PE9.2
1/,2X,'INITIAL MASS OR ACTIVITY (mg or Ci) ',1PE9.2
1/,2X,'MOLECULAR WEIGHT (g/mole) ',1PE9.2
1/,2X,'SOLUBILITY LIMIT (mg/L) ',1PE9.2
1/,2X,'BULK DENSITY OF AQUIFER (g/cm**3) ',1PE9.2
1/,2X,'POROSITY OF AQUIFER ',1PE9.2
1/,2X,'SORPTION COEFFICIENT IN AQUIFER (ml/g) ',1PE9.2
1/,2X,'DISPERSIVITY X DIRECTION (m) ',1PE9.2
1/,2X,'DISPERSIVITY Y DIRECTION (m) ',1PE9.2
1/,2X,'PORE VELOCITY (m/y) ',1PE9.2
1/,2X,'WELL SCREEN THICKNESS (m) ',1PE9.2
1/,2X,'DISTANCE TO AQUIFER BELOW CONTAMINATION (m) ',1PE9.2
1/,2X,'DISTANCE TO RECEPTOR ALONG X AXIS (m) ',1PE9.2
1/,2X,'DISTANCE TO RECEPTOR ALONG Y AXIS (m) ',1PE9.2
1/,2X,A45,1X,1PE9.2
1/,2X,'UNITS OF CONTAMINANT ',a2
1/,2X,'
1/,2X,'INPUT DATA FILE CREATED BY: _____ DATE / / '
1/,2X,'
1/,2X,'INPUT DATA CHECKED BY: _____ DATE / / '
1/,2X,'
1/,2X,'-----')

```

2001 FORMAT(2X,'>>> INITIAL ACTIVITY CONVERTED TO MASS (mg) ',1PE9.2)

3000 FORMAT(2X,'>>> VALUES CALCULATED IN SOURCE SUBROUTINE '

```

1/,2X,'*****'
1/,2X,'LEACH RATE CONSTANT (1/y) ',1PE11.4
1/,2X,'UNSATURATED PORE VELOCITY (m/y) ',1PE11.4
1/,2X,'DECAY CONSTANT (1/y) ',1PE11.4
1/,2X,'RETARDATION FACTOR (SATURATED) ',1PE11.4
1/,2X,'RETARDATION FACTOR (UNSATURATED) ',1PE11.4
1/,2X,'SOLUBILITY LIMITED MASS (mg) ',1PE11.4
1/,2X,'SOLUBILITY LIMITED ACTIVITY (Ci) ',1PE11.4
1/,2X,'TRANSIT TIME IN UNSAT ZONE (years) ',1PE11.4
1/,2X,'FRACTION DECAYED DURING UNSAT TRANSPORT ',1PE11.4
1/,2X,'-----')

```

3001 FORMAT(2X,'>>> SOLUBILITY LIMITED RELEASE FOR ',1PE11.4,' YEARS')

4000 FORMAT(2X,'PEAK TIME (y) =',1PE13.6

1/,2X,'PEAK CONC (' ,a2,'/m**3) =',1PE11.4)

999 END

```

C *****
C SUBROUTINE INPUT
C *****
C SUBROUTINE INPUT(KFLAG,INTIME,XDUMMY,IFLAG)
C implicit real*8 (a-h,o-z)
C THIS SUBROUTINE READS THE INPUT FILE

COMMON /GW/ AX, AY, VX, THICK, AL, WA, GWLIM, RD, PHI, DLR,

```

```

! SLEACH, FRAC, WFLUX, SL, QSL, QI, ZMW, TRANSIT, XD, YD, IMODE
COMMON /SOURCE/ THETA, THETAU, RHOS, THICKS, ZKDS,
! DEPTH, PERC, THALF, ZKDA, RHOA, ZKDU, RHOU, QM
COMMON /EXPOSURE/BW, AT, WI, EF, ED, DLIM, CRISK, HQ
COMMON /FILES/ FILEIN, FILEOU, TITLE

```

```

CHARACTER*40 FILEIN, FILEOU
CHARACTER*78 TITLE
CHARACTER*11 TTIME
CHARACTER*8 DDATE
DIMENSION DUMMY(10)

```

```
IFLAG=0
```

```

C IFLAG CHECKS ERRORS IN INPUT DECK. IF AN ERROR IS DETECTED THEN
C IFLAG IS SET EQUAL TO 1 AND THE PROGRAM IS TERMINATED

```

```

C *****
C *****
C ***** READ IN DATA *****
C *****
C *****

```

```

CALL TIME(TTIME)
CALL DATE(DDATE)

```

```
WRITE(*,1500)
```

```
C INPUT ENVIRONMENTAL PARAMETERS
```

```

      write(*,*)
      WRITE(*,1200)
1200 format(1x,'INPUT FILE WHICH CONTAINS INPUT DATA >>> ')
      READ(*,1201) FILEIN
1201 format(a40)
      3 WRITE(*,1202)
1202 format(1x,'INPUT FILE TO WRITE OUTPUT TO >>>')
      READ(*,1201) FILEOU
      IF(FILEIN.EQ.FILEOU)THEN
        WRITE(*,*) '** OUTPUT FILE WILL OVERWRITE INPUT FILE !!!!!!!'
        GOTO 3
      ENDIF

      OPEN(unit=1,file=FILEIN, STATUS='OLD')
      OPEN(unit=2,file=FILEOU, STATUS='UNKNOWN')
      WRITE(2,*) 'TIME OF RUN ',TTIME
      WRITE(2,*) 'DATE OF RUN ',DDATE
      WRITE(2,*) 'INPUT FILE NAME: ',FILEIN
      WRITE(2,*) 'OUTPUT FILE NAME: ',FILEOU

```

```
C *****TITLE
```

```

      READ(1,1205) TITLE
1205 format(a78)

      READ(1,*) KFLAG
      IF(KFLAG.LT.0.OR.KFLAG.GT.1)THEN
        WRITE(*,*) 'ERROR:KFLAG MUST BE 0 OR 1'
        GOTO 999
      ENDIF

```

```
C ***** INTIME
```

```

      READ(1,*) INTIME
      IF(INTIME.LT.0)THEN
        WRITE(*,*) 'ERROR:INTIME CANNOT BE LESS THAN ZERO IN LINE 2'
        GOTO 999
      ENDIF

```

```

ENDIF

C ***** AL WA THICKS
  READ(1,*) DUMMY(1),DUMMY(2),DUMMY(3)
  DO 21,I=1,3
    IF(DUMMY(I).LE.0.0)THEN
      WRITE(*,*) 'ERROR:VARIABLES AL,WA OR THICKS CANNOT BE ZERO IN L
!INE 3'
      GOTO 999
    ENDIF
  21 CONTINUE
  AL=DUMMY(1)
  WA=DUMMY(2)
  THICKS=DUMMY(3)

C ***** PERC THETAS THETAU
  READ(1,*) DUMMY(1),DUMMY(2),DUMMY(3)
  DO 22,I=1,3
    IF(DUMMY(I).LE.0.0)THEN
      WRITE(*,*) 'ERROR:VARIABLES PERC,THETAS OR THETAU CANNOT BE ZE
!RO IN LINE 4'
      GOTO 999
    ENDIF
  22 CONTINUE
  PERC=DUMMY(1)
  THETAS=DUMMY(2)
  THETAU=DUMMY(3)

C ***** RHOS ZKDS
  READ(1,*) RHOS,ZKDS
  IF(RHOS.LE.0.0)THEN
    WRITE(*,*) 'ERROR:VARIABLE RHOS CANNOT BE LESS THAN OR EQUAL TO 0
!IN LINE 5'
    GOTO 999
  ENDIF

C ***** RHOU ZKDU
  READ(1,*) RHOU,ZKDU
  IF(RHOU.LE.0.0)THEN
    WRITE(*,*) 'ERROR:VARIABLE RHOU CANNOT BE LESS THAN OR EQUAL TO 0
! IN LINE 6'
    GOTO 999
  ENDIF

C ***** THALF QI ZMW AND SL
  READ(1,*) THALF,QI,ZMW,SL
  IF(THALF.EQ.0.0)THEN
    THALF=1.0E38
  ENDIF

C ***** set QI equal to 1.0 for limiting soil concentrations
  IF(KFLAG.EQ.1)THEN
    QI=1.0
  ENDIF

C ***** RHOA PHI ZKDA
  READ(1,*) DUMMY(1),DUMMY(2),DUMMY(3)
  DO 23,I=1,2
    IF(DUMMY(I).LE.0.0)THEN
      WRITE(*,*) 'ERROR:VARIABLES RHOA OR PHI CANNOT BE ZERO IN LIN
!E 8'
      GOTO 999
    ENDIF
  23 CONTINUE
  RHOA=DUMMY(1)

```

```

    PHI=DUMMY(2)
    ZKDA=DUMMY(3)
    IF(PHI.LT.0)THEN
        WRITE(*,*) 'ERROR:PHI CANNOT BE LESS THAN 0 IN LINE 8'
        GOTO 999
    ENDIF
    IF(PHI.LT.0)THEN
        WRITE(*,*) 'ERROR:PHI CANNOT BE LESS THAN 0 IN LINE 8'
        GOTO 999
    ENDIF

C ***** AX AY VX
    READ(1,*) DUMMY(1),DUMMY(2),DUMMY(3)
    DO 24,I=1,3
        IF(DUMMY(I).LE.0.0)THEN
            WRITE(*,*) 'ERROR:VARIABLES AX, AY OR VX CANNOT BE ZERO IN LI
            NE 9'
            GOTO 999
        ENDIF
    24 CONTINUE
    AX=DUMMY(1)
    AY=DUMMY(2)
    VX=DUMMY(3)

C ***** THICK DEPTH
    READ(1,*) THICK,DEPTH
    IF(THICK.LE.0)THEN
        WRITE(*,*) 'ERROR:VARIABLE THICK CANNOT BE LESS THAN 0 IN LINE 1
        10'
        GOTO 999
    ENDIF

C ***** IMODE
    READ(1,*) IMODE
    IF(IMODE.LE.0)THEN
        WRITE(*,*) 'ERROR:IMODE CANNOT BE LESS THAN 0'
        GOTO 999
    ENDIF
    IF(IMODE.GT.5)THEN
        WRITE(*,*) 'ERROR:IMODE CANNOT BE GREATER THAN 5'
        GOTO 999
    ENDIF

C ***** DCF,RADMAX,ZRADMAX,SFACTOR,RFD
    READ(1,*) XDUMMY
C XDUMMY WILL BE CONVERTED TO THE PROPER VALUE IN THE MAIN PROGRAM

C ***** XD AND YD *****
    READ(1,*) XD,YD
C ***** EXPOSURE DATA *****
    READ(1,*) BW,AT,WI,EF,ED,DLIM,CRISK,HQ
    CLOSE(1,STATUS='KEEP')

    GOTO 1000

999 IFLAG=1

1000 WRITE(2,1500)
    WRITE(2,*) ' >>> TITLE OF PROJECT:'
    WRITE(2,*) ' ',TITLE
    WRITE(2,*) ' ~~~~~~'
    !~~~~~'

    RETURN

```

```

1500 FORMAT(2X,' *****' )
      1/,2X,' *'
      1/,2X,' *   This output was produced by the model;
      1/,2X,' *
      1/,2X,' *           GWSCREEN
      1/,2X,' *
      1/,2X,' *   A semi-analytical model for the assessment
      1/,2X,' *   of the groundwater pathway from the leaching
      1/,2X,' *   of surficial and buried contamination.
      1/,2X,' *
      1/,2X,' *           Arthur S. Rood
      1/,2X,' *           Idaho National Engineering Laboratory
      1/,2X,' *           EG&G Idaho Inc.
      1/,2X,' *           Subsurface and Environmental Modeling Unit
      1/,2X,' *           PO Box 1625
      1/,2X,' *           Idaho Falls, Idaho 83415
      1/,2X,' *****' )

```

END

```

C *****
C SUBROUTINE CTIME
C *****
      SUBROUTINE CTIME(UNITS,TSL)
      IMPLICIT REAL*8(A-H,O-Z)
      CHARACTER*2 UNITS
      WRITE(*,*) ' >>> CONCENTRATION VS TIME MODE '
      WRITE(2,*) ' >>> CONCENTRATION VS TIME MODE '

      WRITE(*,8)

      WRITE(*,*) ' INPUT TIME TO BEGIN CALCULATION (y) >>> '
      READ(*,*) TSTART
      WRITE(*,*) ' INPUT END TIME OF CALCULATION (y) >>> '
      READ(*,*) TEND
      WRITE(*,*) ' INPUT PRINT TIME STEP(y) >>> '
      READ(*,*) TPRINT

      write(2,*)
      write(*,10) units,units,units,units
      write(2,9)
      write(2,10) units,units,units,units

      DO 41 T=TSTART,TEND,TPRINT

      CALL QGAUS2(T,GW,TSL)

      CALL FLUXES(RELSRC,RELAQU,FAQU,TSRC,TAQU,TSL,T)

      WRITE(*,42) TSRC,RELSRC,TAQU,RELAQU,GW,FAQU
      WRITE(2,42) TSRC,RELSRC,TAQU,RELAQU,GW,FAQU

41 CONTINUE

      8 FORMAT ('***** CONCENTRATION IS CALCULATED FOR TIME + CONTAMINANT
      IT TRANSIT TIME *****')

      9 FORMAT (3X,'(simulation time) (simulation time+transit time)'
      !)

      10 FORMAT (3X,'TIME CUMULATIVE TIME CUMULATIVE GW CO
      !NC AQUIFER'
      1/,2X,' SOURCE FLUX AQUIFER FLUX
      ! FLUX'
      1/,2X,' (years)',7X,'(',a2,')',7X,'(years)',6X,'(',a2,')',7X,'(',a2,')'

```

```

1, '/m**3) (' ,a2, '/year)'
1/,2x, '-----'
1-----')

42  FORMAT(2X,1PE11.4,1X,1PE11.4,1X,1PE11.4,1X,1PE11.4,1X,1PE11.4,1X,1
1PE11.4)
RETURN
END

C *****
C  SUBROUTINE RAD
C *****
C  SUBROUTINE RAD(CS,DCF,AIC,VOL)
C  implicit real*8 (a-h,o-z)
C  COMMON /EXPOSURE/BW,AT,WI,EF,ED,DLIM,CRISK,HQ

C  VARIABLES
C  DLIM = DOSE LIMIT (4 REM/Y)
C  CL = LIMITING GROUNDWATER CONCENTRATION CI/M**3
C  WI = WATER INTAKE RATE (L/D)
C  THE FACTOR OF 1000 IN THE BELOW EQUATION CONVERTS FROM L/D TO
C  CUBIC METERS PER DAY

      CL=DLIM/(DCF*WI*EF/1000)

C  1/VOL=THE SOIL CONCENTRATION FOR A UNIT INVENTORY

      CS=CL/AIC*(1/VOL)
RETURN
END

C *****
C  SUBROUTINE CARCIN
C *****
C  SUBROUTINE CARCIN(CS,SFACTOR,AIC,VOL)
C  implicit real*8 (a-h,o-z)
C  COMMON /EXPOSURE/BW,AT,WI,EF,ED,DLIM,CRISK,HQ

C  VARIABLES
C  BW = BODY WEIGHT (kg)
C  I = WATER INTAKE RATE (L/d)
C  ED = EXPOSURE DURATION (YEARS)
C  AT = AVERAGING TIME (days)
C  EF=EXPOSURE FREQUENCY (DAYS/YEAR)
C  DLIM = DOSE LIMIT (4 REM/Y)
C  CRISK = CARCINOGENIC RISK FACTOR (1.0E-6)
C  CL = LIMITING GROUNDWATER CONCENTRATION CI/M**3
C  WI = WATER INTAKE RATE (L/D)
C  THE FACTOR OF 1000 IN THE BELOW EQUATION CONVERTS FROM L/D TO
C  CUBIC METERS PER DAY

      CL=(CRISK*BW*AT)/(SFACTOR*WI*EF/1000*ED)

C  1/VOL=THE SOIL CONCENTRATION FOR A UNIT INVENTORY

      CS=CL/AIC*(1/VOL)
RETURN
END

C *****
C  SUBROUTINE NCARCIN
C *****
C  SUBROUTINE NCARCIN(CS,RFD,AIC,VOL)
C  implicit real*8 (a-h,o-z)

```



```

COMMON /EXPOSURE/BW,AT,WI,EF,ED,DLIM,CRISK,HQ

C VARIABLES
C BW = BODY WEIGHT (kg)
C I = WATER INTAKE RATE (L/d)
C ED = EXPOSURE DURATION (YEARS)
C AT = AVERAGING TIME (days)
C EF=EXPOSURE FREQUENCY (DAYS/YEAR)
C DLIM = DOSE LIMIT (4 REM/Y)
C CRISK = CARCINOGENIC RISK FACTOR (1.0E-6)
C CL = LIMITING GROUNDWATER CONCENTRATION CI/M**3
C WI = WATER INTAKE RATE (L/D)
C THE FACTOR OF 1000 IN THE BELOW EQUATION CONVERTS FROM L/D TO
C CUBIC METERS PER DAY

      CL=(HQ*BW*AT*RFD)/(WI*EF/1000*ED)

C 1/VOL=THE SOIL CONCENTRATION FOR A UNIT INVENTORY

      CS=CL/AIC*(1/VOL)
      RETURN
      END

C *****
C   SUBROUTINE SOURCEX
C *****
      SUBROUTINE SOURCEX(UX,RDU,TSL,KFLAG)
      implicit real*8 (a-h,o-z)

C CALCULATED VALUES IN SOURCE SUBROUTINE
C SLEACH = LEACH RATE CONSTANT (Y-1)
C UX = UNSATURATED PORE VELOCITY (M/Y)
C DLR = DECAY RATE CONSTANT (Y-1)
C RD = RETARDATION COEFFICIENT
C RDU = RETARDATION IN UNSATURATED ZONE
C TRNASIT = TRANSIT TIME IN UNSAT ZONE (Y)
C FRAC = FRACTION OF INVENTORY REMAINING AFTER UNSAT ZONE TRANSIT
C SL = SOLUBILITY LIMIT
C QSL = MASS IN SOURCE WHERE SOLUBILITY LIMIT WOULD BE EXCEEDED IN LEACHATE
C WFLUX = WATER FLUX THROUGH SOURCE COMPARTMENT (L/Y)

      COMMON /GW/ AX, AY, VX, THICK, AL, WA, GWLIM, RD, PHI, DLR,
      ! SLEACH, FRAC, WFLUX, SL, QSL, QI, ZMW, TRANSIT, XD, YD,IMODE

      COMMON /SOURCE/ THETAS, THETAU, RHOS, THICKS, zKDS,
      ! DEPTH, PERC, THALF, zKDA, RHOA, zKDU, RHOU, QM

C CALCULATE LEACH RATE CONSTANT (y-1)

      SLEACH=PERC/(THETAS*THICKS*(1+zKDS*RHOS/THETAS))

C CALCULATE PORE VELOCITY IN UNSATURATED ZONE

      UX=PERC/THETAU

C CALCULATE DECAY RATE (y-1) IF THALF = 1E38 THEN DLR=0

      IF(THALF.EQ.1.0E+38)THEN
        DLR=0.0
      ELSE
        DLR=LOG(2.)/THALF
      ENDIF

C CALCULATE RD IN AQUIFER

```

```

RD=1+zKDA*RHOA/PHI
C CALCULATE FRACTION DECAYED DURING UNSAT ZONE TRANSIT
c RDU = retardation in unsaturated zone,
C TRANSIT = UNSATURATED TRANSIT TIME

RDU=1+zKDU*RHOU/THETAU
TRANSIT=DEPTH*RDU/UX
ARG=-DLR*TRANSIT
IF (ARG.LE.-200) THEN
  ARG=-200
ENDIF
FRAC=EXP(ARG)

C CALCULATE WATER FLUX

WFLUX=AL*WA*PERC*1000

C CALCULATE QSL FROM SL CONVERT LITERS TO M3 BY FACTOR OF 1000

QSL=SL*AL*WA*THICKS*THETAS*(1+ZKDS*RHOS/THETAS)*1000

C COMPARE QM TO QSL. IF QM IS GREATER QSL THEN CALCULATE TSL, THE TIME
C SOLUBILITY LIMITED RELEASE DOMINATES ONLY IF CONC VS TIME IS DESIRED.
C LET R=CONTAMNANT FLUX VIA SOLUBILITY = SOL LIMIT X WATER FLUX

IF (QM.GT.QSL.AND.KFLAG.EQ.0) THEN
  R=WFLUX*SL
  CALL ROOT(R,DLR,QM,QSL,TSL)
ELSE
  TSL=0.0
ENDIF

RETURN
END

C *****
C SUBROUTINE ROOT
C *****
SUBROUTINE ROOT(R,DLR,Q0,QSL,RTSAFE)
C This subroutine calculates the time roots of the solubility release function
C from Numerical Recipes, Press et al.

IMPLICIT REAL*8(A-H,O-Z)
PARAMETER (MAXIT=100)
XACC=0.1
X1=0.0
X2=(Q0-QSL)/R+.1
CALL FUNCD(X1,FL,DF,R,Q0,QSL,DLR)
CALL FUNCD(X2,FH,DF,R,Q0,QSL,DLR)
IF (FL*FH.GE.0.) PAUSE 'root must be bracketed'
IF (FL.LT.0.) THEN
  XL=X1
  XH=X2
ELSE
  XH=X1
  XL=X2
  SWAP=FL
  FL=FH
  FH=SWAP
ENDIF
RTSAFE=.5*(X1+X2)
DXOLD=ABS(X2-X1)

```

```

DX=DXOLD
CALL FUNCD(RTSAFE,F,DF,R,QO,QL,DLR)
DO 11 J=1,MAXIT
  IF(((RTSAFE-XH)*DF-F)*((RTSAFE-XL)*DF-F).GE.0.
    * .OR. ABS(2.*F).GT.ABS(DXOLD*DF) ) THEN
    DXOLD=DX
    DX=0.5*(XH-XL)
    RTSAFE=XL+DX
    IF(XL.EQ.RTSAFE)RETURN
  ELSE
    DXOLD=DX
    DX=F/DF
    TEMP=RTSAFE
    RTSAFE=RTSAFE-DX
    IF(TEMP.EQ.RTSAFE)RETURN
  ENDIF
  IF(ABS(DX).LT.XACC)RETURN
  CALL FUNCD(RTSAFE,F,DF,R,QO,QL,DLR)
  IF(F.LT.0.) THEN
    XL=RTSAFE
    FL=F
  ELSE
    XH=RTSAFE
    FH=F
  ENDIF
11 CONTINUE
  PAUSE 'RTSAFE exceeding maximum iterations'
  RETURN
END

C *****
C SUBROUTINE FUNCD
C *****
SUBROUTINE FUNCD(T,F,DF,R,QO,QL,DLR)
C This subroutine calculates the value of the solubility release function
C and its first derivative
  IMPLICIT REAL*8(A-H,O-Z)
  F=QL-QO*EXP(-DLR*T)+R*T
  DF=DLR*QO*EXP(-DLR*T)+R
  RETURN
END

C *****
C SUBROUTINE PEAK
C *****
SUBROUTINE PEAK(GWPEAK,PKTIME,TSL)
  IMPLICIT REAL*8 (A-H,O-Z)

C This subroutine calculates the peak concentration

C CALCULATED VALUES IN PEAK SUBROUTINE
C DEL = TIME INCREMENT FOR PEAK BRACKET LOCATION
C TI = TIME SLOPE IS CALCULATED AT
C GWPEAK = PEAK CONCENTRATION
C PKTIME = TIME OF PEAK CONCENTRATION (Y)
C THE MINIMUM-MAXIMUM BOUNDARIES ARE THE VARIABLES ZMIN AND ZMAX
C THE MIDDLE POINT IS VARIABLE ZMID

  COMMON /GW/ AX, AY, VX, THICK, AL, WA, GWLIM, RD, PHI, DLR,
  ! SLEACH, FRAC, WFLUX, SL, QSL, QI, ZMW, TRANSIT, XD, YU,IMODE
  WRITE(*,*) ' CALCULATING PEAK CONCENTRATION'
c changes made to bracket routine 11-19-91
C BRACKET MAXIMUM VALUE TI IS FIRST GUESS OF PEAK TIME

  TI=(0.25*AL+XD)/VX*RD

```

```

      DEL=TI/2
      ZMIN=0.0
      ZMAX=0.0
      FLAG1=0.
      FLAG2=0.

C DXDT IS THE VALUE OF THE SLOPE AT T
5   CALL SLOPE(TI,DXDT,TSL)

      IF(DXDT.EQ.0.)THEN
        FLAG1=1.
        FLAG2=1.
        ZMAX=TI+DEL
        GOTO 6
      ENDIF

      IF(DXDT.LT.0.)THEN
        ZMIN=TI
        FLAG1=1.
        TI=TI-DEL
      ENDIF

      IF(DXDT.GT.0.)THEN
        ZMAX=TI
        FLAG2=1.
        TI=TI+DEL
      ENDIF

C if TI is less than zero then let zmin equal 1 second (converted to years)
C and break out of loop.
      IF(TI.LE.0.)THEN
        FLAG2=1.
        ZMIN=3.17E-8
      ENDIF

      IF((FLAG1.EQ.1.).AND.(FLAG2.EQ.1.))THEN
        GOTO 6
      ENDIF
      GOTO 5

6   ZMID=ZMIN+(ZMAX-ZMIN)/2

C CALL GOLDEN SECTION SEARCH

      CALL GOLDEN(ZMIN,ZMID,ZMAX,GWPEAK,PKTIME,TSL)

      RETURN
      END

C *****
C   SUBROUTINE GOLDEN
C *****
      SUBROUTINE GOLDEN(AX,BX,CX,GMAX,TMAX,TSL)
      IMPLICIT REAL*8 (A-H,O-Z)

C THIS SUBROUTINE IS FROM NUMERICAL RECIPES ,PRESS ET AL, 1987

      PARAMETER (R=.61803399,C=.38196602,TOL=0.001)
      X0=AX
      X3=CX
      IF(ABS(CX-BX).GT.ABS(BX-AX))THEN
        X1=BX

```

```

      X2=BX+C*(CX-BX)
    ELSE
      X2=BX
      X1=BX-C*(BX-AX)
    ENDIF
    F1=-FUNC(X1,G,TSL)
    F2=-FUNC(X2,G,TSL)
1    IF (ABS(X3-X0).GT.TOL*(ABS(X1)+ABS(X2))) THEN
      IF (F2.LT.F1) THEN
        X0=X1
        X1=X2
        X2=R*X1+C*X3
      C    F0=F1
        F1=F2
        F2=-FUNC(X2,G,TSL)
      ELSE
        X3=X2
        X2=X1
        X1=R*X2+C*X0
      C    F3=F2
        F2=F1
        F1=-FUNC(X1,G,TSL)
      ENDIF
      GOTO 1
    ENDIF
    IF (F1.LT.F2) THEN
      GMAX=-F1
      TMAX=X1
    ELSE
      GMAX=-F2
      TMAX=X2
    ENDIF
    RETURN
  END

C *****
C  SUBROUTINE GWINT
C *****
      SUBROUTINE GWINT(INTIME,PKTIME,TSL,AIC)
      IMPLICIT REAL*8 (A-H,O-Z)

C This subroutine calculates the limits of integration for
C regulatory criteria and the average integrated concentration.

C CALCULATED VALUES IN GWINT SUBROUTINE
C S = INTEGRATED CONCENTRATION
C AIC = AVERAGE INTEGRATED CONCENTRATION
C T1 = LOWER LIMIT OF INTEGRATION (Y)
C T2 = UPPER LIMIT OF INTEGRATION (Y)

C CHECK TO SEE IF INTEGRATION TIME IS BOUNDED EQUALLY ON BOTH SIDES OF THE
C OF THE PEAK  T1 AND T2 ARE THE INTEGRATION LIMITS

      IF ((PKTIME-INTIME/2).LT.0.0) THEN
        T1=0
        T2=INTIME
      ELSE
        T1=PKTIME-INTIME/2
        T2=PKTIME+INTIME/2
      ENDIF

C CALCULATE INTEGRATED CONCENTRATION USING GAUSSIAN QUAD FROM
C NUMERICAL RECIPES

```

```

CALL QGAUS1(T1,T2,S,TSL)

AIC=S/(T2-T1)

RETURN
END

C *****
C SUBROUTINE QGAUS1
C *****
SUBROUTINE QGAUS1(A,B,SS,TSL)
  IMPLICIT REAL*8 (A-H,O-Z)

  DIMENSION X(8),W(8)

C ZEROS AND WEIGHTS FOR 16 POINT GAUSSIAN QUADRATURE: FROM NUMERICAL
C METHODS, ROBERT W. HORNBECK, QUANTUM PUBLISHERS INC, NEW YORK PG 293

  DATA X/ 0.0950125098,0.281603558,0.4580167777,0.617876244
  *,0.755404484,0.8656312024,0.9445750231,0.9894009350/

  DATA W/ 0.1894506105,0.1826034150,0.1891565194,0.149595988
  *,0.1246289713,0.0951585117,0.0622535239,0.0271524594/

  WRITE(*,*) 'CALCULATING AVERAGE INTEGRATED CONCENTRATION'

  XM=0.5*(B+A)
  XR=0.5*(B-A)
  SS=0
  DO 11 J=1,8
    DX=XR*X(J)
    SS=SS+W(J)*(FUNC((XM+DX),G,TSL)+FUNC((XM-DX),G,TSL))
    WRITE(*,20) SS
11  CONTINUE
  SS=XR*SS

  20 FORMAT(2X,'SS VALUE ',1PE11.4)
  RETURN
  END

C *****
C SUBROUTINE QGAUS2
C *****
SUBROUTINE QGAUS2(T1,SS,TSL)
  IMPLICIT REAL*8 (A-H,O-Z)

  DIMENSION X(12),W(12)

C TIME UNITS ARE YEARS, CONCENTRATION UNITS ARE AMOUNT/M3
C This routine calculates the groundwater concentration at time T1. This
C routine has been adapted from Numerical Recipes, Press et al.

C COMMON STATEMENTS

  COMMON /GW/ AX, AY, VX, THICK, AL, WA, GWLIM, RD, PHI, DLR,
  I SLEACH, FRAC, WFLUX, SL, QSL, QI, ZMW, TRANSIT, XD, YD,IMODE

C ZEROS AND WEIGHTS FOR 24 POINT GAUSSIAN QUADRATURE: FROM NUMERICAL
C METHODS, ROBERT W. HORNBECK, QUANTUM PUBLISHERS INC, NEW YORK PG 293

  DATA X/ 0.0640568929,0.1911188675,0.3150426797,0.4337935076
  *,0.5454214714,0.6480936519,0.7401241916,0.8200019860
  *,0.8864155270,0.9382745520,0.9747285560,0.9951872200/

```

DATA W/ 0.1279381953,0.1258374563,0.1216704729,0.1155056681
 *,0.1074442701,0.0976186521,0.0861901615,0.0733464814
 *,0.0592985849,0.0442774388,0.0285313888,0.0123412298/

C INITIALIZE VARIABLES IF T1=0.0 RETURN TO START

```
IF(T1.EQ.0) THEN
  SS=0.0
  RETURN
ENDIF
```

C DETERMINE LIMITS FOR INTEGRATION

C T1= LOWER LIMIT T2 = UPPER LIMIT THESE VALUES ARE IN UNITS OF SECONDS
 C INTEGRATION LIMITS ARE SELECTED BY CODELL'S METHOD. THE LIMITS ARE
 C BASED ON THE VALUE OF ARB WHEN $\exp(-ARB)$ APPROACHES ZERO. DEPENDING
 C ON THE MACHINE USED, ARB MAY BE -50 TO -200
 C XC1 AND XC2 = THE X DISTANCE USED IN CALCULATION OF THE INTEGRATION LIMITS.
 C $XC1=XD+AL/2$ AND
 C $XC2=XD-AL/2$ FOR HORIZONTAL AREA SOURCES. THE TEMP VARIABLES STORE THE
 C INTERMEDIATE VALUES

```
DXX=ABS(AX*VX)
ARB=50
XC1=XD+AL/2
XC2=XD-AL/2
```

```
TEMP1=(2*VX*XC1/RD+4*DXX*ARB/RD)/((VX/RD)**2
!+4*DXX*DLR/RD)
```

```
TEMP2=TEMP1**2 - (2*XC2)**2/((VX/RD)**2
!+4*DXX*DLR/RD)
```

C IF TEMP2 IS LESS THAN ZERO THEN DO NOT PROCEED WITH INTEGRATION

```
IF(TEMP2.LE.0.0) THEN
  SS=0
  RETURN
ENDIF
```

```
TEMP3=(2*VX*XC2/RD+4
!*DXX*ARB/RD)/((VX/RD)**2
!+4*DXX*DLR/RD)
```

```
T2=T1-(TEMP3-SQRT(TEMP2))/2
```

```
T1=T1-(TEMP1+SQRT(TEMP2))/2
```

C CONDITIONAL STATEMENTS

C IF THE UPPER LIMIT IS EQ TO 0 THEN GWCON EQ 0
 IF(T2.LE.0.) THEN
 SS=0.0

```
GOTO 999
ENDIF
```

C CHECK LOWER LIMIT OF INTEGRATION TO MAKE SURE IS NOT LESS THAN 0

```
IF(T1.LE.0.) THEN
  T1=0.0
ENDIF
```

C CHECK TO SEE IF INTEGRATION LIMIT IS GREATER THAN DESIRED TIME

```
IF(T2.GE.T1) THEN
  T2=T1
ENDIF
```

C CUT OFF SOURCE TERM AFTER 100 HALF TIMES FROM SOURCE

```
IF(DLR.GT.0) THEN
  CUTOFF=100*(LOG(2.)/DLR)
```

```

        IF(T2.GT.CUTOFF)THEN
          T2=CUTOFF
        ENDIF
      ENDIF

      A=T1
      B=T2

      XM=0.5*(B+A)
      XR=0.5*(B-A)
      SS=0

      DO 11 J=1,12

C TX1 AND TX2 ARE THE TIMES TO BE USED IN THE AREA SUBROUTINE

        DX=XR*X(J)
        TX1=T1-(XM+DX)
        TX2=T1-(XM-DX)

C CALCULATE SOURCE TERM

        T=XM+DX
        CALL SRCTERM(T,TSL,Q1)

        T=XM-DX
        CALL SRCTERM(T,TSL,Q2)
        SS=SS+W(J)*(AREA(TX1,Q1)+AREA(TX2,Q2))
11      CONTINUE
        SS=XR*SS

999    RETURN
      END

C *****
C      SUBROUTINE SRCTERM
C *****
      SUBROUTINE SRCTERM(T,TSL,Q)
        IMPLICIT REAL*8 (A-H,O-Z)

C This subroutine calculates the mass or activity released

        COMMON /GW/ AX, AY, VX, THICK, AL, WA, GWLIM, RD, PHI, DLR,
         1 SLEACH, FRAC, WFLUX, SL, QSL, Q1, ZMW, TRANSIT, XD, YD,IMODE

C IF TSL=0 THEN DO LEACH EQUATION FOR EITHER ACTIVITY OR MASS

        IF(TSL.EQ.0.0)THEN
          ARG=(-(SLEACH+DLR)*(T))
          IF(ARG.LE.-300)THEN
            ARG=-300
          ENDIF
          Q=FRAC*SLEACH*Q1*EXP(ARG)
          RETURN
        ENDIF

C IF T IS LESS THAN TSL THEN A SOLUBILITY LIMITED RELEASE IS CALCULATED FOR
C THE SOURCE TERM. IF A RADIONUCLIDE, THEN MASS IS CONVERTED TO ACTIVITY

        IF(T.GE.TSL)THEN
          ARG=(-(SLEACH+DLR)*(T-TSL))
          IF(ARG.LE.-300)THEN
            ARG=-300
          ENDIF
          Q=QSL*FRAC*SLEACH*EXP(ARG)

```



```

        ELSE
          Q=FRAC*WFLUX*SL
        ENDIF
C   convert mass to activity if a radionuclide
C   CONVERT MG TO CI.  USE THE CONVERSIONS 1 CI=3.7E10 DPS, 3.1536 S/Y.
C   6.023E23 ATOMS/MOLE AND 1000 MG/G

        IF(IMODE.LE.2)THEN
          A=6.023E+23
          CI=3.7E10
          SEC=3.1536E7
          QX=(Q/(1000*ZMW)*A*(DLR/SEC))/CI
          Q=QX
        ENDIF

        RETURN
        END

        REAL*8 FUNCTION AREA(TI,Q)
        IMPLICIT REAL*8 (A-H,O-Z)
C *****
C *      FUNCTION AREA      *
C *****
C This subroutine calculates the ground water concentration for an area source
C ALL UNITS ARE IN METERS AND YEARS

C COMMON STATEMENTS

        COMMON /GW/ AX, AY, VX, THICK, AL, WA, GWLIM, RD, PHI, DLR,
        ! SLEACH, FRAC, WFLUX, SL, QSL, QI, ZMW, TRANSIT, XD, YD,IMODE

        IF(TI.LE.0.0)THEN
          AREA=0.0
          RETURN
        ENDIF

        DX=ABS(AX*VX)
        DY=ABS(AY*VX)

C   X ARGUMENTS

        ARG1=((XD+AL/2)-VX*TI/RD)/SQRT(4*DX*TI/RD)
        ARG2=((XD-AL/2)-VX*TI/RD)/SQRT(4*DX*TI/RD)

        IF(ARG1.GE.25.) THEN
          ARG1=1.0
        ELSE
          IF(ARG1.LE.-25.) THEN
            ARG1=-1.0
          ELSE
            CALL ERRORR(ARG1,ERX)
            ARG1=ERX
          ENDIF
        ENDIF

        IF(ARG2.GE.25.) THEN
          ARG2=1.0
        ELSE
          IF(ARG2.LE.-25.) THEN
            ARG2=-1.0
          ELSE
            CALL ERRORR(ARG2,ERX)
            ARG2=ERX
          ENDIF
        ENDIF

```

```

ENDIF

X2=(ARG1-ARG2)*EXP(-DLR/3.1536E+07*TI)/(2*AL)
C Y ARGUMENTS

ARG1=(WA/2+YD)/SQRT(4*DY*TI/RD)
IF (ARG1.GE.25.) THEN
ARG1=1.0
ELSE
IF (ARG1.LE.-25.) THEN
ARG1=-1.0
ELSE
CALL ERRORR(ARG1,ERX)
ARG1=ERX
ENDIF
ENDIF
ARG2=(WA/2-YD)/SQRT(4*DY*TI/RD)

IF (ARG2.GE.25.) THEN
ARG2=1.0
ELSE
IF (ARG2.LE.-25.) THEN
ARG2=-1.0
ELSE
CALL ERRORR(ARG2,ERX)
ARG2=ERX
ENDIF
ENDIF
Y2=(ARG1+ARG2)/(2*WA)

C CALCULATE Z PARAMETER FOR AVG SOLUTION

Z1=1/THICK

C CALCULATE GROUND WATER CONCENTRATION

GWCON=(Q*X2*Y2*Z1)/(PHI*RD)
AREA=GWCON
RETURN
END

C *****
C * FUNCTION FUNC(TI,G,TSL) *
C *****
C This function calls the QGAUS2 routine to calculate the groundwater
C concentration at a point in time

REAL*8 FUNCTION FUNC(TI,G,TSL)
IMPLICIT REAL*8(A-H,O-Z)

C GROUNDWATER CONCENTRATION RETURNED IN THE VARIABLE G

CALL QGAUS2(TI,G,TSL)
FUNC=G
RETURN
END

SUBROUTINE SLOPE(TI,DXDT,TSL)
IMPLICIT REAL*8 (A-H,O-Z)
C *****
C SUBROUTINE SLOPE
C *****
C UNITS IN M, Y

```

C This routine calculates the slope of the groundwater conc vs time
C curve at the point TI

```
COMMON /GW/ AX, AY, VX, THICK, AL, WA, GWLIM, RD, PHI, DLR,
! SLEACH, FRAC, WFLUX, SL, QSL, QI, ZMW, TRANSIT, XD, YD,IMODE
```

```
DEL=(0.5*AL*RD/VX)/1000
T1=TI-DEL
CALL QGAUS2(T1,GW1,TSL)
T2=TI+DEL
CALL QGAUS2(T2,GW2,TSL)
DXDT=(GW2-GW1)/(T2-T1)
RETURN
END
```

```
C *****
C SUBROUTINE FLUXES
C *****
```

```
SUBROUTINE FLUXES(RELSRC,RELAQU,FAQU,TSRC,TAQU,TSL,T)
implicit real*8 (a-h,o-z)
```

C This subroutine calculates the fluxes from the source volume
C and to the aquifer
C RELSRC = CUMULATIVE FLUX FROM SOURCE
C RELAQU = CUMULATIVE FLUX TO AQUIFER
C TSRC = THE SOURCE RELEASE TIME FRAME
C TAQU = THE AQUIFER RELEASE TIME FRAME
C FAQU = FLUX OF CONTAMINANT TO AQUIFER

```
COMMON /GW/ AX, AY, VX, THICK, AL, WA, GWLIM, RD, PHI, DLR,
! SLEACH, FRAC, WFLUX, SL, QSL, QI, ZMW, TRANSIT, XD, YD,IMODE
```

```
IF(TSL.EQ.0.0)THEN
    RELSRC=QI*(1-EXP(-SLEACH*T))
    FAQU=FRAC*SLEACH*QI*EXP(-SLEACH*T)
    RELAQU=FRAC*RELSRC
    TSRC=T
    TAQU=T+TRANSIT
    RETURN
ENDIF
```

```
IF(TSL.GE.T)THEN
    RELSRC=WFLUX*SL*T
    FAQU=FRAC*WFLUX*SL
ELSE
    RELSRC=WFLUX*SL*TSL+QSL*(1-EXP(-SLEACH*(T-TSL)))
    FAQU=FRAC*SLEACH*QSL*EXP(-SLEACH*(T-TSL))
ENDIF
```

C convert mass to activity if a radionuclide
C CONVERT MG TO CI. USE THE CONVERSIONS 1 CI=3.7E10 DPS, 3.1536 S/Y
C 6.023E23 ATOMS/MOLE AND 1000 MG/G

```
IF(IMODE.LE.2)THEN
    A=6.023E+23
    CI=3.7E10
    SEC=3.1536E7
    RELDUM=(RELSRC/(1000*ZMW)*A*(DLR/SEC))/CI
    FAQUDUM=(FAQU/(1000*ZMW)*A*(DLR/SEC))/CI
    RELSRC=RELDUM
    FAQU=FAQUDUM
ENDIF
    RELAQU=FRAC*RELSRC
    TSRC=T
```

```

      TAQU=T+TRANSIT
      RETURN
      END

```

```

      SUBROUTINE ERRORR(X,ERX)
C *****
C *      SUBROUTINE ERRORR      *
C *****
C This subroutine calculates the error function for an argument, X
C Adapted from Press et al, Numerical RECIPES: modified by A. Rood for
C use with double precision variables. This routine includes the subroutines
C GAMMLN, GSER, GAMMP AND GCF
C
      IMPLICIT REAL*8 (A-H,O-Z)
      ERX =ERF(X)
      END
C
C *****
C
      REAL*8 FUNCTION ERF(X)
      IMPLICIT REAL*8 (A-H,O-Z)
      A=0.50
      IF(X.LT.0.)THEN
         ERF=-GAMMP(A,X**2)
      ELSE
         ERF=GAMMP(A,X**2)
      ENDIF
      RETURN
      END
C
C *****
C
      REAL*8 FUNCTION GAMMP(A,X)
      IMPLICIT REAL*8 (A-H,O-Z)
      IF (X.LT.0..OR.A.LE.0.)PAUSE
      IF(X.LT.A+1.)THEN
         CALL GSER(GAMSER,A,X,GLN)
         GAMMP=GAMSER
      ELSE
C      WRITE(*,*) 'A, X, GLN ',A,X,GLN
         CALL GCF(GAMMCF,A,X,GLN)
         GAMMP=1.-GAMMCF
      ENDIF
      RETURN
      END
C
C *****
C
      SUBROUTINE GSER(GAMSER,A,X,GLN)
      IMPLICIT REAL*8 (A-H,O-Z)
      PARAMETER (ITMAX=100, EPS=3.E-3)
      GLN=GAMMLN(A)
C      WRITE(*,*) 'A=',A
      IF(X.LE.0.)THEN
         IF(X.LT.0.)PAUSE
         GAMSER=0.
         RETURN
      ENDIF
      AP=A
      SUM=1./A
      DEL=SUM
      DO 11 N=1,ITMAX
         AP=AP+1.

```

```

        DEL=DEL*X/AP
        SUM=SUM+DEL
        IF(ABS(DEL).LT.ABS(SUM)*EPS)GO TO 1
11    CONTINUE
        PAUSE 'A too large, ITMAX too small'

1    GAMSER=SUM*EXP(-X+A*LOG(X)-GLN)
    RETURN
    END

C
C *****
C
    SUBROUTINE GCF(GAMMCF,A,X,GLN)
    IMPLICIT REAL*8 (A-H,O-Z)
    PARAMETER (ITMAX=100,EPS=3.E-7)
C    WRITE(*,*) 'GAMMCF, A, X, GLN = ',GAMMCF,A,X,GLN
    GLN=GAMMLN(A)
    GOLD=0.
    AO=1.
    A1=X
    B0=0.
    B1=1.
    FAC=1.
    DO 11 N=1,ITMAX
        AN=FLOAT(N)
        ANA=AN-A
        AO=(A1+AO*ANA)*FAC
        B0=(B1+B0*ANA)*FAC
        ANF=AN*FAC
        A1=X*AO+ANF*A1
        B1=X*B0+ANF*B1
        IF(A1.NE.0.)THEN
            FAC=1./A1
            G=B1*FAC
            IF(ABS((G-GOLD)/G).LT.EPS)GO TO 1
            GOLD=G
        ENDIF
11    CONTINUE
        PAUSE 'A too large, ITMAX too small'
1    GAMMCF=EXP(-X+A*LOG(X)-GLN)*G
    RETURN
    END

C
    REAL*8 FUNCTION GAMMLN(XX)
C *****
C *      FUNCTION GAMMLN      *
C *****
    REAL*8 COF(6),STP,HALF,ONE,FPF,X,TMP,SER,XX
    DATA COF,STP/76.18009173D0,-86.50532033D0,24.01409822D0,
*    -1.231739516D0,.120858003D-2,-.536382D-5,2.50662827465D0/
    DATA HALF,ONE,FPF/0.5D0,1.0D0,5.5D0/
    X=X-ONE
    TMP=X+FPF
    TMP=(X+HALF)*LOG(TMP)-TMP
    SER=ONE
    DO 11 J=1,6
        X=X+ONE
        SER=SER+COF(J)/X
11    CONTINUE
    GAMMLN=TMP+LOG(STP*SER)
    RETURN
    END

```

END

DATE
FILMED

6 / 3 / 92