MAY 04 1992

DEVELOPMENT OF A REBURNING BOILER PROCESS MODEL

DE-FG22-91PC91159

DOE/PC/91159--T2

Second Quarterly Progress Report

DE92 016613

January 1, 1992 through March 31, 1992

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Prepared for:

AEM Milano, Italy
ENEL, Italy
and
U.S. Department of Energy

Prepared by:

K.T. Wu

RECEIVED BY OSTI
MAY 10 1992

Energy and Environmental Research Corporation
18 Mason
Irvine, California 92718

April 30, 1992

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

1.0 OBJECTIVE

The overall objective of this program is to integrate EER's expertise in boiler reburning performance evaluation into a package of analytical computer tools. Specific objectives of the program are to develop a computational capability with the following features:

- (a) can be used to predict the impact of gas reburning application on thermal conditions in the boiler radiant furnace, and on overall boiler performance
- (b) can estimate gas reburning NO_x reduction effectiveness based on specific reburning configurations and furnace/boiler configurations.
- (c) can be used as an analytical tool to evaluate the impact of boiler process parameters (e.g., fuel switching and changes in boiler operating conditions) on boiler thermal performance.
- (d) is adaptable to most boiler designs (tangential and wall fire boilers) and a variety of fuels (solid, liquid, gaseous and slurried fuels).
- (e) is sufficiently user friendly to be exercisable by engineers with a reasonable knowledge of boilers, and with reasonable computer skills. Here, "user friendly" means that the user will be guided by computer codes during the course of setting up individual input files for the boiler performance model.

2.0 APPROACH

The approach to the development of the reburning boiler process model is through the modification and integration of EER's current reburning system submodels. As with any comprehensive engineering computer models, the reburning submodels occupy a substantial amount of computer memory and usually require a list of inputs to describe the complex boiler environment. These submodels are considered to be too unwieldy to be directly incorporated into a single generalized design/evaluation procedure. As an alternative, the approach is to package these submodels into three main analytical tools, namely, a furnace heat transfer model, a boiler performance model, and a reburning NO_x model. The coupling of process design information amongst the three submodels will be established through input/output interfaces, and through the use of boiler design data and any available field measurements.

3.0 PROGRAM STRUCTURE

In order to achieve the overall objectives, the execution of the program has been broken down into five tasks. These tasks and their individual objectives are briefly discussed in the following.

Task 1. Development of a 2D Furnace Heat Transfer Model

Under this task, EER's 2D furnace heat transfer model (2DHT) will be modified for most boiler designs, firing configurations, as well as different fuels. Specifically, the 2D Model will be set up for treatment of tangential and wall fired boilers, and adapted to solid, liquid, gaseous and slurried fuels. The code will also incorporate the ability to describe gaseous reburning fuel injection, overfire air injection and flue gas recirculation.

In conjunction with the 2D Model modifications, Task 1 will also focus on modification and improvement of a guided input-code (2DINPT) so that the user will be guided stepwise through the necessary input routines, and will be provided with default values for certain key parameters. This input code will also be used by the user to update key model inputs for cases defined.

Task 2. Development of a Boiler Performance Model

The purpose of Task 2 is to develop a Boiler Performance Model which calculates steam- and gas-side heat balance for boiler sections that are not included in the domain of the 2D Model, such as the backpass convective section and air preheater. The approach taken to prepare the Boiler Performance Code will be in line with the preparation of the 2D Furnace Heat Transfer Model. EER's Boiler Performance Code will be modified and tested in responding to any changes made in the 2D Model to ensure mutual consistency. In addition, a separate input code for the operation of the Boiler Performance Model will be prepared in order to provide guidance to the user in input file preparations.

Task 3. Development of a Reburning NO_x Model

The purpose of this task is to develop a NO_x model which provides reasonable working estimates for the expected NO_x reduction potential as a function of the major boiler process controlling parameters. The boiler process parameters include furnace gas temperature profiles and residence time distributions, local stoichiometries up- and down-stream of the reburning fuel injection zone, reburn fuel and overfire air local mixing rates, and injection locations.

To develop the Reburning NO_x Model, EER's chemical kinetics codes will firstly be modified to take account of a wide range of boiler operating conditions with the consideration of reburning zone injection temperature, stoichiometry, flue gas quench rates and residence times. The model will assume that mixing of both reburning fuel and overfire air is adequate so that bulk mixing rates of the injected jets can be represented by characteristic mixing times. The model will then be coupled with the outputs of the Furnace Heat Transfer Code which in turn incorporates the input of boiler-specific information such as temperature gradients and gas residence times. This model will predict NO_x emissions for a specific set of boiler input and

reburning conditions, so that the user will be able to evaluate NO_x reduction potentials associated with the assumed operating conditions.

Task 4. System Model Integration

As discussed above, six computer codes (i.e., three input-codes, and three main-codes) will be developed upon completion of Tasks 1 to 3. Task 4 will integrate these six computer codes into a complete boiler reburning model-package through input/output file connections. The operation of the boiler modeling package will be streamlined and kept as simple as possible to the user. This task will also carry out testing and performance evaluation of the integrated computer package. Example cases will be selected to demonstrate the use of different model options and capabilities.

Task 5. Document Preparation and Model Delivery

This task consists of two major reporting items: Preparation of a User's Manual, and provision of consulting and short courses. The purpose of this task is to assist the user in applying the boiler model-package, and to provide necessary support until he become familiar with the operation of the computer codes.

The manual will be constructed to include: (a) a brief description of the physical and chemical basis of the models, (b) a complete description of the model applicability, options and input/output, (c) a description of the default inputs, (d) a detailed description of worked examples. The Reburning Boiler Performance codes will be structured in PC formats. Executable versions of the codes will be prepared in the form of floppy disk sets and delivered with the User's Manual.

This task will also provide telephone consultation service for a limited time period following delivery of the Reburning Boiler Performance Model. A three-day short course instruction will be provided on the basis of necessity.

4.0 TECHNICAL PROGRESS

During this reporting period, a request to extend the project completion-date, from March 31, 1992 to May 31, 1992, had been submitted and approved by the project funding agencies. Figure 1 shows the revised project schedule.

Major research effort had focused on the development of a Reburning NO_x model (RBNOX), and an input code, RBINPT, for the reburning model. In addition, integration of the Boiler Performance Model (BPM), and it's associated input-code, BPINPT, had been completed. Specific progress and accomplishments are summarized in the following:

(a). Completion of the Reburning-NO_x-Model Input Code (RBINPT)

This input code is designed to be used as a tool for preparation of a data-file required by the Reburning NO_x model. The code adopts similar presentation formats from the 2D heat transfer input code 2DINPT. Appendix A presents records of an interactive session when the RBINPT code was used to check the data of an existing input file.

(b). Completion of the Reburning NO_x Model (RBNOX)

In conjunction with the work accomplished in item (a), a Reburning NO_x Model had been developed. The model takes predicted furnace information from the 2D Heat Transfer Code (2DHT), and predicts reburning NO_x reductions. The RBNOX code uses detailed chemical kinetics, therefore, an elaborate thermodynamic data file is also required, and had been completed for the model applications. Appendix B shows an output example from the RBNOX code.

(c). Integration of the Boiler Performance Model (BPM)

The Boiler Performance Model must be coupled with the furnace heat transfer code (2DHT) and its input code (BPINPT) through input/output file connections. The necessary file connections had been implemented and tested.

5.0 PLANS

The next reporting period will focus on the remaining of the project tasks listed below:

- Complete the selection of the example cases for the User's Manual.
- Execute all six codes for the selected example cases.
- Refine model performance if necessary.
- Prepare the User's Manual and the computer codes for delivery.

Figure 1. Revised project schedule.

Appendix A. Interactive Outputs from RBINPT

```
-- This is an interactive program (RBINPT) for preparing
  a data file to run the EER Reburning NOx Model
-- Version 6.58, February, 1992
```

```
***** Attention *****
This interactive program accepts inputs from keyboard
in UPPER case only.
-- Please set your keyboard to the UPPER case symbols
  (i.e., Caps Lock !).
-- To continue, type C and press Return (or Enter)
*****
```

C

Chapter 1 :

PARAMETERS OF FILE SPECIFICATION

Default output-file name (from RBINPT code) : RBIN0308.100

Press: D for default values
C to change
Return to continue

File RBIN0308.100 already exists, want to over-write ?
Enter Y or N N

Press Return to continue

Default output-file name (from RBINPT code) : RBIN0308.100

Press: D for default values
C to change
Return to continue C

TEST

Default output-file name (from RBNOX code) : RBOT0308.100

Press: D for default values
C to change
Return to continue D

You can include your comments on the front page
of the printout :

-- Comment block may consist of 10 lines
-- Each line may have a max. of 78 characters
To continue, press Return

Current comments are:

```
" Line 1 is blank "
test for reburn.dat format
restart (5 iterations) from 2dht case 0306 (oil fired, gas reburning)
" Line 4 is blank "
sr1=1.1,sr2=0.9,sr3=1.2
rb fuel is ch4
0.24 mixing times for rb and ofa jets
tets rbnox formats
" Line 9 is blank "
```

" Line 10 is blank "

-- Default comments are those used in 2DHT runs

Press: D for default values
C to change
Return to continue

Please wait: reading reactor 1 data file ...

Scan reaction mechanism ?
Enter Y or N

Chapter 6 :

PROPERTIES OF FURNACE FLUE GAS

Press: P to by-pass this chapter
Return to proceed through

Oil fired furnace

Current flue gas composition, in volume fractions :

CO2	H2O	O2	N2	NO	SO2
0.085897	0.186044	0.017178	0.710880	0.000001	0.000000

Press: D for default values
C to change
Return to continue C

Type in volume fractions of the following species :

CO2	H2O	O2	N2	NO	SO2
0.085897	0.186044	0.017178	0.70788	0.005	0.0

NOTE:

SUM OF VOLUME FRACTIONS IS NOT EQUAL TO 1.0000
Press Return to re-enter

Type in volume fractions of the following species :

CO2	H2O	O2	N2	NO	SO2
0.085897	0.186044	0.017178	0.70588	0.005	0.0

Check the flue gas composition one more time ?

Press: C to check
Return to continue C

Current flue gas composition, in volume fractions :

CO2	H2O	O2	N2	NO	SO2
0.085897	0.186044	0.017178	0.705880	0.005000	0.000000

Press: D for default values
C to change
Return to continue

The following is for information only

Burner zone stoichiometric oxygen ratio : 1.1100

Mean molecular weight of the flue gas : 27.6058 kg/kg-mole

Chapter 7 :

PROPERTIES OF REBURN AND OFA JETS

Press: P to by-pass this chapter
Return to proceed through

--- Reactor No. 1: Reburn Reactor ---

Current reburn gas composition, in volume fractions :

CO2	H2O	O2	N2	CH4	C2H6
0.000000	0.000000	0.000000	0.000000	1.000000	0.000000
CO	NO	SO2			
0.000000	0.000000	0.000000			

-- Default reburn fuel is 100 % CH4

Press: D for default values
C to change
Return to continue

Enter reburn zone stoichiometric O2 ratio (SR2): 0.9

The following is for information only

(1) Reburn fuel stoichiometric O2 requirement : 3.9891 kg-O2/kg-wet-fuel
(2) Mean molecular weight of the reburn fuel : 16.0430 kg/kg-mole
(3) Reburn gas flow rate is 0.0121 kg/kg-flue

Press Return to continue

Enter reburn-jet characteristic mixing time (sec) :0.24

--- Reactor No. 2: Rich-Zone Reactor ---

This reactor does not contain external jets
Press Return to continue

--- Reactor No. 3: Over-Fired Air Reactor ---

Enter stoichiometric O2 ratio (SR3) of the OFA zone: 1.2

This is only for information :
OFA flow rate is 0.3294 kg/kg-flue
Press Return to continue

Enter OFA-jet characteristic mixing time (sec) :0.24

--- Reactor No. 4: Quench Reactor ---

This reactor does not contain external jets
Press Return to continue

Chapter 8 :

REACTOR DEFAULT OPERATING CONDITIONS

Press: P to by-pass this chapter
Return to proceed through

Zone-numbers with reburning: 11
Zone-numbers with OFA: 13

The following data have been set for reactor default values :

Reactor 1	Reactor 2	Reactor 3	Reactor 4
-----------	-----------	-----------	-----------

SR	0.9000	0.9000	1.2000	1.2000
Reac. Time	0.2400	0.1035	0.2400	1.4307
Init. Temp.	1893.8	1853.2	1847.2	1823.4
Final Temp.	1853.2	1847.2	1823.4	1192.3

Press Return to continue

Chapter 9 :

SPECIFICATION OF REACTOR RESIDENCE TIMES

Reactor No. 1: Reburn Reactor
Press Return to continue

Specification of reactor residence time (XMAX) :
Currently, XMAX = 0.2400 sec
-- Default time is 0.2400 sec

Press: D for default values
C to change
Return to continue D

Chapter 10 :

SPECIFICATION OF REACTOR TEMPERATURES

Reactor No. 1: Reburn Reactor
Press Return to continue

Specification of reactor initial (Ti) and final (Tf) temperatures :
Currently, Ti= 1893.8 K, Tf= 1853.2 K
-- Default temperatures are 1893.8 K and 1853.2 K, respectively

Press: D for default values
C to change
Return to continue

Please wait: writing reactor 1 data file ...

Please wait: reading reactor 2 data file ...

Chapter 9 :

SPECIFICATION OF REACTOR RESIDENCE TIMES

Reactor No. 2: Rich-Zone Reactor
Press Return to continue

Specification of reactor residence time (XMAX) :
Currently, XMAX = 0.1035 sec
-- Default time is 0.1035 sec

Press: D for default values
C to change
Return to continue

Chapter 10 :

SPECIFICATION OF REACTOR TEMPERATURES

Reactor No. 2: Rich-Zone Reactor

Press Return to continue

Specification of reactor initial (Ti) and final (Tf) temperatures :
Currently, Ti= 1853.2 K, Tf= 1847.2 K
-- Default temperatures are 1853.2 K and 1847.2 K, respectively

Press: D for default values
C to change
Return to continue

Please wait: writing reactor 2 data file ...

Please wait: reading reactor 3 data file ...

Chapter 9 :

SPECIFICATION OF REACTOR RESIDENCE TIMES

Reactor No. 3: Over-Fired Air Reactor
Press Return to continue

Specification of reactor residence time (XMAX) :
Currently, XMAX = 0.2400 sec
-- Default time is 0.2400 sec

Press: D for default values
C to change
Return to continue

Chapter 10 :

SPECIFICATION OF REACTOR TEMPERATURES

Reactor No. 3: Over-Fired Air Reactor
Press Return to continue

Specification of reactor initial (Ti) and final (Tf) temperatures :
Currently, Ti= 1847.2 K, Tf= 1823.4 K
-- Default temperatures are 1847.2 K and 1823.4 K, respectively

Press: D for default values
C to change
Return to continue

Please wait: writing reactor 3 data file ...

Please wait: reading reactor 4 data file ...

Chapter 9 :

SPECIFICATION OF REACTOR RESIDENCE TIMES

Reactor No. 4: Quench Reactor
Press Return to continue

Specification of reactor residence time (XMAX) :
Currently, XMAX = 1.4310 sec
-- Default time is 1.4307 sec

Press: D for default values

C to change
Return to continue D

Chapter 10 :

SPECIFICATION OF REACTOR TEMPERATURES

Reactor No. 4: Quench Reactor
Press Return to continue

Specification of reactor initial (Ti) and final (Tf) temperatures :
Currently, Ti= 1823.4 K, Tf= 1192.3 K
-- Default temperatures are 1823.4 K and 1192.3 K, respectively

Press: D for default values
C to change
Return to continue

Please wait: writing reactor 4 data file ...

NOTE:

- Output file was saved as file TEST
- To update TEST further, you have to copy file TEST to file RINPUT.DAT under DOS, then rerun RBINPT
- If you want to save the original contents of file RINPUT.DAT, make sure you save it with a different name

Appendix B. RBNOX Model Output Example

BOILER REBURNING NOX MODEL (RBNOX) OUTPUTS
 OUTPUT FILE NAME: RBO0308.100

 * USER'S COMMENTS *

C. test for reburn.dat format
 C. restart (5 iterations) from 2dht case 0306 (oil fired, gas reburning)
 C.
 C. srl=1.1, srl2=0.9, srl3=1.2
 C. rb fuel is ch4
 C. 0.24 mixing times for rb and ofa jets
 C. tets rbnox formats
 C.
 C.

ixr= 1
 iprt= 0
 x= 0.000000E+00 cm
 dx= 0.300000E-07 cm
 p= 0.100000E+01 atm
 dpdx= 0.000000E+00 atm/cm
 lausr= 0.000000E+00 sec

TEMPERATURE(K) = 1893.84 ENTHALPY(CAL/G)=-1.802E+02 VELOCITY(CM/SEC)= 1.000E+00 CP(CAL/G-K) = 3.518E-01
 DENSITY(G/CC) = 1.776E-04 MOLE/GM-TOTAL = 3.623E-02 AREA(CM2) = 1.000E+00 H.T.(CAL/CC-S) = 0.000E-01
 MASS INFLUX(XMDOTE,CM/SEC)= 1.000E-01 ENERGY INFLU X(QDOTE,CAL/SEC)= 0.000E-01 TE(K)= 3.000E+02 RHOE(G/CC)= 0.000E-01
 OFRE= 1.000E-16 FEXTNAL= 1.776E-04

I	SPECIES	MASS FRXN (OVERALL)	MASS FRXN (GAS/SOLID)	MOLE FRXN (OVERALL)	MOLE FRXN (GAS/SOLID)	NET RATE (MOLE/CC-S)	DADT(I) (FRXN/S)	ALPHA(I)	ALPHA(I)	ALPHA(I)	#N
1	H2	7.3049E-18	7.3049E-18	1.0000E-16	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	0
2	O2	1.9918E-02	1.9918E-02	1.7178E-02	1.7178E-02	0.0000E-01	0.0000E-01	0.0000E-01	7.2784E-03	5.2245E-04	0
3	H2O	6.1628E-17	6.1628E-17	1.0000E-16	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	0
4	C	5.7975E-17	5.7975E-17	1.0000E-16	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	0
5	H	3.6525E-18	3.6525E-18	1.0000E-16	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	0
6	H2O	1.2145E-01	1.2145E-01	1.8604E-01	1.8604E-01	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	6.7412E-03	0
7	CO2	1.3698E-01	1.3698E-01	8.5897E-02	8.5897E-02	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.1124E-03	0
8	HO2	1.1960E-16	1.1960E-16	1.0000E-16	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	0
9	H2O2	1.2326E-16	1.2326E-16	1.0000E-16	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	0

10	CO	1.0150E-16	1.0000E-16	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	0
11	CH4	5.8131E-17	5.8131E-17	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	0
12	CH3	5.4479E-17	5.4479E-17	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	0
13	CH2	5.0826E-17	5.0826E-17	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	0
14	CH	4.7174E-17	4.7174E-17	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	0
15	C2H4	1.0165E-16	1.0165E-16	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	0
16	C2H6	1.0896E-16	1.0896E-16	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	0
17	C2H5	1.0531E-16	1.0531E-16	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	0
18	C2H3	9.8000E-17	9.8000E-17	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	0
19	C	4.3521E-17	4.3521E-17	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	0
20	C2H2	9.4348E-17	9.4348E-17	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	0
21	C2H	9.0695E-17	9.0695E-17	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	0
22	CH2O	1.0880E-16	1.0880E-16	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	0
23	CH3O	1.1245E-16	1.1245E-16	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	0
24	CHO	1.0515E-16	1.0515E-16	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	0
25	N	5.0757E-17	5.0757E-17	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	0
26	NO	1.0873E-06	1.0873E-06	1.0000E-06	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	1
27	N2	7.2165E-01	7.2165E-01	7.1088E-01	0.0000E-01	0.0000E-01	0.0000E-01	2.7381E-02	2.5758E-02	0
28	NO2	1.6671E-16	1.6671E-16	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	1
29	N2O	1.5949E-16	1.5949E-16	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	2
30	NH3	6.1715E-17	6.1715E-17	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	1
31	NH2	5.8062E-17	5.8062E-17	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	1
32	NH	5.4410E-17	5.4410E-17	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	1
33	HN2	1.0517E-16	1.0517E-16	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	2
34	N2H2	1.0882E-16	1.0882E-16	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	2
35	HNO	1.1239E-16	1.1239E-16	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	1
36	CN	9.4279E-17	9.4279E-17	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	1
37	NCO	1.5225E-16	1.5225E-16	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	1
38	CHN	9.7931E-17	9.7931E-17	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	1
39	HNC	1.5591E-16	1.5591E-16	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	1
40	HOCN	1.5591E-16	1.5591E-16	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	1
41	SO2	2.3213E-16	2.3213E-16	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	0
42	SO3	2.9011E-16	2.9011E-16	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	0
43	HSO3	2.9375E-16	2.9375E-16	1.0000E-16	0.0000E-01	0.0000E-01	0.0000E-01	3.4659E-18	3.6235E-18	0

MOLE FRACTION OF FIXED NITROGEN IN GAS PHASE = 1.000E-06

Step size increased at: x= 0.300E-07 dx= 0.600E-07
Step size increased at: x= 0.900E-07 dx= 0.120E-06
Step size increased at: x= 0.210E-06 dx= 0.240E-06
Step size increased at: x= 0.450E-06 dx= 0.480E-06
Step size increased at: x= 0.930E-06 dx= 0.960E-06
Step size increased at: x= 0.189E-05 dx= 0.192E-05
Step size increased at: x= 0.381E-05 dx= 0.384E-05
Step size reduced at: x= 0.765E-05 dx= 0.384E-05 ideqn= 3 delmax= 0.273E+00 qm= 0.407E-07 savea= 0.172E-07
restart at: x= 3.810E-06 dx= 1.920E-06
Step size reduced at: x= 0.573E-05 dx= 0.192E-05 ideqn= 3 delmax= 0.133E+00 qm= 0.287E-07 savea= 0.172E-07
restart at: x= 3.810E-06 dx= 9.600E-07
Step size reduced at: x= 0.477E-05 dx= 0.960E-06 ideqn= 3 delmax= 0.649E-01 qm= 0.228E-07 savea= 0.172E-07
restart at: x= 3.810E-06 dx= 4.800E-07
Step size increased at: x= 0.669E-05 dx= 0.960E-06
Step size increased at: x= 0.124E-04 dx= 0.192E-05
Step size increased at: x= 0.240E-04 dx= 0.384E-05
Step size increased at: x= 0.470E-04 dx= 0.768E-05
Step size increased at: x= 0.124E-03 dx= 0.154E-04
Step size reduced at: x= 0.155E-03 dx= 0.154E-04 ideqn= 22 delmax= 0.727E-01 qm= 0.161E-07 savea= 0.118E-07
restart at: x= 1.392E-04 dx= 7.680E-06

REACH MAX. at X= 2.405E-01

page 2

```

TEMPERATURE(K) = 183.20 ENTHALPY(CAL/G)=-2.209E+02 VELOCITY(CM/SEC)= 1.000E+00 CP(CAL/G-K) = 3.602E-01
DENSITY(G/CC) = 1.763E-04 *JLE/GM-TOTAL = 3.730E-02 AREA(CM2) = 1.019E+00 H.T.(CAL/CC-S) = 0.000E-01
MASS INFLUX(XMDOTE,GM/SEC)= 0.000E-01 ENERGY INFLU X(QDOTE,CAL/SEC)= 0.000E-01 TE(K)= 5.450E+02 RHOE(G/CC)= 3.587E-04
OPRE= 1.000E-16 FEXTNAL= 1.776E-04

```

I	SPECIES	MASS FRXN (OVERALL)	MASS FRXN (GAS/SOLID)	MOLE FRXN (OVERALL)	MOLE FRXN (GAS/SOLID)	NET RATE (MOLE/CC-S)	DADT(I) (FRXN/S)	ALPHAE(I)	ALPHA(I)	ALPHA(I)	#N
1	H2	1.2469E-03	1.2469E-03	1.6580E-02	1.6580E-02	8.4705E-07	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
2	O2	1.5131E-06	1.5131E-06	1.2676E-06	1.2676E-06	-1.0913E-10	0.0000E-01	6.2332E-18	7.2784E-03	6.2245E-04	0
3	HO	4.2418E-05	4.2418E-05	6.6857E-05	6.6857E-05	-5.0956E-08	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
4	O	1.4255E-07	1.4259E-07	2.3889E-07	2.3889E-07	3.2004E-10	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
5	H	2.8864E-06	2.8864E-06	7.6762E-05	7.6762E-05	5.1211E-08	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
6	H2O	1.3393E-01	1.3393E-01	1.9928E-01	1.9928E-01	1.6296E-07	0.0000E-01	6.2332E-18	3.4659E-18	6.7412E-03	0
7	CO2	2.2511E-01	2.2511E-01	7.6206E-02	7.6206E-02	-6.1182E-07	0.0000E-01	6.2332E-18	3.4659E-18	3.1124E-03	0
8	HO2	2.0740E-10	2.0740E-10	1.6844E-10	1.6844E-10	1.7549E-13	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
9	H2O2	3.3860E-10	3.3860E-10	2.6684E-10	2.6684E-10	3.1948E-13	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
10	CO	2.5990E-02	2.5990E-02	2.4873E-02	2.4873E-02	1.1116E-06	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
11	CH4	5.0597E-05	5.0597E-05	8.4544E-05	8.4544E-05	-5.0793E-07	0.0000E-01	6.2332E-02	3.4659E-18	3.6235E-18	0
12	CH3	5.2735E-06	5.2735E-06	9.4025E-06	9.4025E-06	1.3218E-09	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
13	CH2	3.1891E-08	3.1891E-08	6.0947E-08	6.0947E-08	7.7115E-12	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
14	CH	1.5822E-10	1.5822E-10	3.2578E-10	3.2578E-10	3.5437E-13	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
15	C2H4	1.3137E-07	1.3137E-07	1.2553E-07	1.2553E-07	1.2882E-11	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
16	C2H6	3.9998E-09	3.9998E-09	3.5657E-09	3.5657E-09	1.6599E-12	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
17	C2H5	3.7973E-11	3.7973E-11	3.5026E-11	3.5026E-11	-1.9052E-13	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
18	C2H3	4.0176E-10	4.0176E-10	3.9821E-10	3.9821E-10	8.2766E-14	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
19	C	4.9185E-11	4.9185E-11	1.0977E-10	1.0977E-10	1.2649E-14	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
20	C2H2	2.5278E-05	2.5278E-05	2.6025E-05	2.6025E-05	3.2381E-09	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
21	C2H	1.2948E-09	1.2948E-09	1.3868E-09	1.3868E-09	-4.8052E-11	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
22	CH2O	3.7353E-06	3.7353E-06	3.3348E-06	3.3348E-06	9.2338E-12	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
23	CH3O	8.8236E-08	8.8236E-08	7.6215E-08	7.6215E-08	1.0256E-11	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
24	CHO	5.2636E-09	5.2636E-09	4.8624E-09	4.8624E-09	3.6601E-11	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
25	N	1.1260E-09	1.1260E-09	2.1547E-09	2.1547E-09	1.7208E-13	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	1
26	NO	4.5020E-05	4.5020E-05	4.0217E-05	4.0217E-05	-1.3892E-10	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-08	1
27	N2	7.1353E-01	7.1353E-01	6.8274E-01	6.8274E-01	-1.9551E-10	0.0000E-01	6.2332E-18	2.7381E-02	2.5758E-02	1
28	NO2	3.7016E-10	3.7016E-10	1.9237E-10	1.9237E-10	-4.4080E-14	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	1
29	N2O	1.9429E-08	1.9429E-08	1.1833E-08	1.1833E-08	3.6543E-13	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	2

30	NH3	1.7491E-06	1.7491E-06	2.7529E-06	2.7529E-06	1.8875E-10	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	1
31	NH2	2.0946E-08	2.0946E-08	3.5040E-08	3.5040E-08	-4.6320E-12	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	1
32	NH	3.9937E-09	3.9937E-09	7.1296E-09	7.1296E-09	5.8984E-13	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	1
33	HN2	1.7140E-10	1.7140E-10	1.5831E-10	1.5831E-10	-6.2266E-14	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	2
34	N2H2	2.1785E-13	2.1785E-13	1.9446E-13	1.9446E-13	1.7947E-16	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	2
35	HNO	2.6607E-09	2.6607E-09	2.2996E-09	2.2996E-09	2.9825E-12	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	1
36	CN	5.5632E-10	5.5632E-10	5.7317E-10	5.7317E-10	-1.7685E-12	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	1
37	NCN	1.7661E-10	1.7661E-10	1.1267E-10	1.1267E-10	7.9520E-15	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	1
38	CHN	5.4608E-06	5.4608E-06	5.4163E-06	5.4163E-06	3.4137E-10	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	1
39	HRCO	1.1817E-07	1.1817E-07	7.3625E-08	7.3625E-08	1.9406E-12	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	1
40	HOCN	3.1031E-08	3.1031E-08	1.9333E-08	1.9333E-08	-3.9746E-14	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	1
41	SO2	1.0480E-15	1.0480E-15	4.3852E-16	4.3852E-16	1.4717E-16	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
42	SO3	8.0064E-19	8.0064E-19	2.6807E-19	2.6807E-19	-2.4893E-20	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
43	HSO3	8.1068E-19	8.1068E-19	2.6807E-19	2.6807E-19	-1.4214E-16	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0

MOLE FRACTION OF FIXED NITROGEN IN GAS PHASE = 4.855E-05

PLUG FLOW REACTOR (CONTINUED WITH SAME CHEMISTRY)

Step size increased at: x = 0.300E-07 dx= 0.600E-07
Step size increased at: x = 0.900E-07 dx= 0.120E-06
Step size increased at: x = 0.210E-06 dx= 0.240E-06
Step size increased at: x = 0.450E-06 dx= 0.480E-06
Step size increased at: x = 0.930E-06 dx= 0.960E-06
Step size increased at: x = 0.189E-05 dx= 0.192E-05
Step size increased at: x = 0.381E-05 dx= 0.384E-05
Step size increased at: x = 0.765E-05 dx= 0.768E-05
Step size increased at: x = 0.153E-04 dx= 0.154E-04
Step size increased at: x = 0.307E-04 dx= 0.307E-04
Step size increased at: x = 0.614E-04 dx= 0.614E-04
Step size increased at: x = 0.123E-03 dx= 0.123E-03
Step size increased at: x = 0.246E-03 dx= 0.246E-03
Step size increased at: x = 0.639E-02 dx= 0.345E-03

REACH MAX. at X= 1.037E-01

page 3

----- RXR NO. 2 : RICH ZONE REACTOR -----

irxr= 2
iprt= 320
x= 0.103680E+00 cm
dx= 0.345000E-03 cm
p= 0.100000E+01 atm
dpdx= 0.000000E+00 atm/cm
tausr= 0.000000E+00 sec

TEMPERATURE(K) = 1847.22 ENTHALPY(CAL/G)=-2.227E+02 VELOCITY(CM/SEC)= 1.000E+00 CP(CAL/G-K) = 3.600E-01
DENSITY(G/CC) = 1.768E-04 MOLE/GM-TOTAL = 3.731E-02 AREA(CM2) = 1.016E+00 H.T.(CAL/CC-S) = 0.000E-01

TE(K)= 5.450E+02 RHOE(G/CC)= 3.587E-04

MASS INFLUX(XMDOTE,GM/SEC)= 0.000E-01 ENERGY INFLU X(QDOTE,CAL/SEC)= 0.000E-01
OFRE= 1.000E-16 FEXTNAL= 1.776E-04

I	SPECIES	MASS FRXN (OVERALL)	MASS FRXN (GAS/SOLID)	OVERALL (GAS/SOLID)	NET RATE (MOLE/CC-S)	DADT(I) (FRXN/S)	ALPHA(I)	ALPHA(I)	ALPHA(I) #N
1	H2	1.2554E-03	1.2554E-03	1.6690E-02	-2.9734E-09	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18

2	O2	1.1408E-06	1.1408E-06	9.5541E-07	9.5541E-07	4.8708E-12	0.0000E-01	6.2332E-18	7.2784E-03	6.2245E-04	0
3	HO	3.6560E-05	3.6560E-05	5.7610E-05	5.7610E-05	-7.7830E-09	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
4	O	1.0812E-07	1.0812E-07	1.8110E-07	1.8110E-07	3.3038E-11	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
5	H	2.5341E-06	2.5341E-06	6.7376E-05	6.7376E-05	7.4027E-09	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
6	H2O	1.3401E-01	1.3401E-01	1.9935E-01	1.9935E-01	3.6056E-09	0.0000E-01	6.2332E-18	3.4659E-18	6.7412E-03	0
7	CO2	1.2470E-01	1.2470E-01	7.5935E-02	7.5935E-02	3.4913E-09	0.0000E-01	6.2332E-18	3.4659E-18	3.1124E-03	0
8	HO2	1.4534E-10	1.4534E-10	1.1801E-10	1.1801E-10	2.8543E-14	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
9	H2O2	2.6411E-10	2.6411E-10	2.0809E-10	2.0809E-10	5.6840E-14	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
10	CO	2.6413E-02	2.6413E-02	2.5272E-02	2.5272E-02	-2.8632E-09	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
11	CH4	3.4687E-08	3.4687E-08	5.7947E-08	5.7947E-08	-9.6837E-12	0.0000E-01	6.2332E-02	3.4659E-18	3.6235E-18	0
12	CH3	3.2706E-09	3.2706E-09	5.8300E-09	5.8300E-09	9.0499E-13	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
13	CH2	7.2566E-11	7.2566E-11	1.3865E-10	1.3865E-10	-2.0805E-14	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
14	CH	3.1885E-13	3.1885E-13	6.5639E-13	6.5639E-13	3.6499E-14	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
15	C2H4	1.3489E-10	1.3489E-10	1.2887E-10	1.2887E-10	-2.1140E-14	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
16	C2H6	1.9302E-15	1.9302E-15	1.7203E-15	1.7203E-15	4.4733E-19	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
17	C2H5	3.6445E-16	3.6445E-16	3.3609E-16	3.3609E-16	2.9266E-19	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
18	C2H3	7.1327E-12	7.1327E-12	7.0680E-12	7.0680E-12	4.1485E-15	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
19	C	9.2900E-14	9.2900E-14	2.0729E-13	2.0729E-13	-3.4352E-17	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
20	C2H2	1.6283E-06	1.6283E-06	1.6760E-06	1.6760E-06	-2.7643E-10	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
21	C2H	7.1361E-11	7.1361E-11	7.6409E-11	7.6409E-11	4.4222E-13	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
22	CH2O	3.0523E-09	3.0523E-09	2.7243E-09	2.7243E-09	-4.3206E-13	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
23	CH3O	5.2223E-11	5.2223E-11	4.5098E-11	4.5098E-11	5.2042E-16	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
24	CHO	1.3587E-09	1.3587E-09	1.2548E-09	1.2548E-09	5.1065E-12	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
25	N	2.2217E-10	2.2217E-10	4.2506E-10	4.2506E-10	-2.9642E-14	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	1
26	NO	4.9046E-05	4.9046E-05	4.3804E-05	4.3804E-05	3.11179E-11	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-08	1
27	N2	7.1354E-01	7.1354E-01	6.8258E-01	6.8258E-01	5.6445E-11	0.0000E-01	6.2332E-18	2.7381E-02	2.5758E-02	0
28	NO2	3.4259E-10	3.4259E-10	1.9956E-10	1.9956E-10	-6.2021E-15	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	1
29	N2O	5.1687E-09	5.1687E-09	3.1472E-09	3.1472E-09	-2.7871E-13	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	2
30	NH3	4.2559E-07	4.2559E-07	6.6969E-07	6.6969E-07	7.4595E-11	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	1
31	NH2	4.4247E-09	4.4247E-09	7.4004E-09	7.4004E-09	-9.8770E-13	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	1
32	NH	7.9409E-10	7.9409E-10	1.4173E-09	1.4173E-09	-1.4111E-13	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	1
33	HN2	1.4559E-10	1.4559E-10	1.3444E-10	1.3444E-10	-3.2183E-15	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	2
34	N2H2	1.4460E-14	1.4460E-14	1.2904E-14	1.2904E-14	1.3265E-18	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	2
35	HNO	2.5803E-09	2.5803E-09	2.2296E-09	2.2296E-09	6.5056E-13	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	1
36	CN	3.6576E-11	3.6576E-11	3.7675E-11	3.7675E-11	-2.5202E-14	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	1
37	NCO	1.7096E-11	1.7096E-11	1.0904E-11	1.0904E-11	-1.4129E-15	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	1
38	CHN	4.1795E-07	4.1795E-07	4.1445E-07	4.1445E-07	-6.6707E-11	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	1
39	HNCO	1.8161E-08	1.8161E-08	1.1312E-08	1.1312E-08	-1.4253E-12	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	1
40	HOCN	2.3358E-09	2.3358E-09	1.4549E-09	1.4549E-09	-2.3747E-13	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	1
41	SO2	1.4122E-15	1.4122E-15	5.9078E-16	5.9078E-16	1.4062E-16	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
42	SO3	8.0064E-19	8.0064E-19	2.6801E-19	2.6801E-19	-2.2814E-20	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0
43	HSO3	8.1068E-19	8.1068E-19	2.6801E-19	2.6801E-19	-1.4059E-16	0.0000E-01	6.2332E-18	3.4659E-18	3.6235E-18	0

MOLE FRACTION OF FIXED NITROGEN IN GAS PHASE = 4.492E-05

PLUG FLOW REACTOR (CONTINUED WITH SAME CHEMISTRY)

Step size increased at: x= 0.300E-07 dx= 0.600E-07
Step size increased at: x= 0.900E-07 dx= 0.120E-06
Step size increased at: x= 0.210E-06 dx= 0.240E-06
Step size increased at: x= 0.450E-06 dx= 0.480E-06
Step size increased at: x= 0.189E-05 dx= 0.960E-06
Step size increased at: x= 0.765E-05 dx= 0.192E-05
Step size increased at: x= 0.192E-04 dx= 0.384E-05
Step size increased at: x= 0.384E-04 dx= 0.768E-05
Step size increased at: x= 0.844E-04 dx= 0.154E-04

Step size increased at: x= 0.161E-03 dx= 0.307E-04
 Step size increased at: x= 0.315E-03 dx= 0.614E-04
 Step size increased at: x= 0.179E-02 dx= 0.123E-03
 Step size increased at: x= 0.314E-02 dx= 0.246E-03
 Step size increased at: x= 0.339E-02 dx= 0.492E-03
 Step size increased at: x= 0.388E-02 dx= 0.800E-03

REACH MAX. at X= 2.407E-01

page 4

----- RXR NO. 3 : OVER-FIRED-AIR REACTOR -----

ixrf= 3
 iprt= 373
 x= 0.240678E+00 cm
 dx= 0.800000E-03 cm
 p= 0.100000E+01 atm
 dpdx= 0.000000E+00 atm/cm
 tausrf= 0.000000E+00 sec

TEMPERATURE(K) = 1823.41 ENTHALPY(CAL/G)=-1.482E+02 VELOCITY(CM/SEC)= 1.000E+00 CP(CAL/G-K) = 3.450E-01
 DENSITY(G/CC) = 1.852E-04 MOLE/GM-TOTAL = 3.608E-02 AREA(CM2) = 1.282E+00 H.T.(CAL/CC-S) = 0.000E-01
 MASS INFLUX(XMDOTE,GM/SEC)= 0.000E-01 ENERGY INFLU X(QDOTE,CAL/SEC)= 0.000E-01 TE(K)= 3.000E+02 RHOE(G/CC)= 1.172E-03
 OFRE= 1.000E-16 FEXTNAL= 1.776E-04

I	SPECIES	MASS FRXN (OVERALL)	(GAS/SOLID)	MOLE FRXN (OVERALL)	NET RATE (MOLE/CC-S)	DAT(I) (FRXN/S)	ALPHA(I)	ALPHA(I)	ALPHA(I)	#N
1	H2	4.4877E-06	4.4877E-06	6.1695E-05	-1.7809E-09	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	0
2	O2	3.7697E-02	3.7697E-02	3.2649E-02	-3.5488E-09	0.0000E-01	7.2784E-03	7.2784E-03	6.2245E-04	0
3	HO	3.8498E-04	3.8498E-04	6.2733E-04	-6.8167E-09	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	0
4	O	1.5575E-05	1.5575E-05	2.6978E-05	5.7315E-09	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	0
5	H	1.2296E-07	1.2296E-07	3.3809E-06	4.9175E-10	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	0
6	H2O	1.0963E-01	1.0963E-01	1.6865E-01	4.8805E-09	0.0000E-01	3.4659E-18	3.4659E-18	6.7142E-03	0
7	CO2	1.2553E-01	1.2553E-01	7.9049E-02	2.8371E-09	0.0000E-01	3.4659E-18	3.4659E-18	3.1124E-03	0
8	HO2	2.8814E-07	2.8814E-07	2.4193E-07	9.1989E-11	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	0
9	H2O3	3.6363E-08	3.6363E-08	2.9627E-08	1.6817E-11	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	0
10	CO	1.1368E-04	1.1368E-04	1.1248E-04	-2.8371E-09	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	0
11	CH4	1.6043E-19	1.6043E-19	2.7715E-19	5.4326E-20	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	0
12	CH3	1.5035E-19	1.5035E-19	2.7715E-19	2.3935E-19	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	0
13	CH2	1.4027E-19	1.4027E-19	2.7715E-19	-3.4317E-18	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	0
14	CH	1.3019E-19	1.3019E-19	2.7715E-19	-1.2184E-17	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	0
15	C2H4	2.8054E-19	2.8054E-19	2.7715E-19	9.1556E-18	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	0
16	C2H6	3.0070E-19	3.0070E-19	2.7715E-19	-1.8863E-19	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	0
17	C2H5	2.9062E-19	2.9062E-19	2.7715E-19	-9.0519E-18	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	0
18	C2H3	2.7046E-19	2.7046E-19	2.7715E-19	-5.4060E-18	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	0
19	C	1.2011E-19	1.2011E-19	2.7715E-19	4.2253E-19	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	0
20	C2H2	2.6038E-19	2.6038E-19	2.7715E-19	-1.7919E-17	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	0
21	C2H	2.5030E-19	2.5030E-19	2.7715E-19	-1.3519E-17	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	0
22	CH3O	3.1927E-15	3.1927E-15	2.9468E-15	1.4006E-18	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	0
23	CH2O	3.1035E-19	3.1035E-19	2.7715E-19	-1.1124E-18	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	0
24	CHO	3.1341E-13	3.1341E-13	2.9933E-13	3.4379E-15	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	0
25	N	1.3832E-11	1.3832E-11	2.7367E-11	-1.4177E-14	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	1
26	NO	4.8083E-05	4.8083E-05	4.4409E-05	2.4372E-10	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	0
27	N2	7.2658E-01	7.2658E-01	7.1878E-01	-1.2435E-10	0.0000E-01	2.7381E-02	2.7381E-02	2.5758E-02	0
28	N2O	6.5268E-08	6.5268E-08	3.9317E-08	9.3584E-13	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	1
29	N2O	1.3630E-07	1.3630E-07	8.5824E-08	2.0077E-12	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	2
30	NH3	5.9723E-12	5.9723E-12	9.7183E-12	-3.8097E-16	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	1

31	NH2	8.3443E-13	1.4432E-12	1.4432E-12	-5.8852E-17	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	1
32	NH	2.1147E-12	3.9032E-12	3.9032E-12	-3.3588E-16	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	1
33	NH2	7.2088E-12	6.8838E-12	6.8838E-12	-4.9169E-16	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	2
34	N2H2	1.4488E-17	1.3370E-17	1.3370E-17	4.1684E-21	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	2
35	HNO	1.5332E-10	1.3700E-10	1.3700E-10	5.2971E-14	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	1
36	CN	9.2408E-19	9.8432E-19	9.8432E-19	4.6762E-20	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	1
37	NCO	4.2939E-15	2.8322E-15	2.8322E-15	-1.6282E-19	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	1
38	CHN	8.1961E-16	8.4048E-16	8.4048E-16	3.4116E-19	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	1
39	HNCO	4.4683E-13	2.8782E-13	2.8782E-13	-7.3581E-18	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	1
40	HOCN	1.9598E-15	1.2624E-15	1.2624E-15	-3.5764E-20	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	1
41	SO2	1.4632E-15	6.3299E-16	6.3299E-16	1.3909E-16	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	0
42	SO3	3.2671E-18	1.1309E-18	1.1309E-18	8.3677E-20	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	0
43	HSO3	8.1068E-19	2.7715E-19	2.7715E-19	-1.3917E-16	0.0000E-01	3.4659E-18	3.4659E-18	3.6235E-18	0

MOLE FRACTION OF FIXED NITROGEN IN GAS PHASE = 4.462E-05

PLUG FLOW REACTOR (CONTINUED WITH SAME CHEMISTRY)

Step size increased at: x=	0.300E-07	dx=	0.600E-07
Step size increased at: x=	0.900E-07	dx=	0.120E-06
Step size increased at: x=	0.210E-06	dx=	0.240E-06
Step size increased at: x=	0.450E-06	dx=	0.480E-06
Step size increased at: x=	0.930E-06	dx=	0.960E-06
Step size increased at: x=	0.189E-05	dx=	0.192E-05
Step size increased at: x=	0.381E-05	dx=	0.384E-05
Step size increased at: x=	0.765E-05	dx=	0.768E-05
Step size increased at: x=	0.153E-04	dx=	0.154E-04
Step size increased at: x=	0.307E-04	dx=	0.307E-04
Step size increased at: x=	0.614E-04	dx=	0.614E-04
Step size increased at: x=	0.123E-03	dx=	0.123E-03
Step size increased at: x=	0.246E-03	dx=	0.246E-03
Step size increased at: x=	0.491E-03	dx=	0.492E-03
Step size increased at: x=	0.983E-03	dx=	0.983E-03
Step size increased at: x=	0.197E-02	dx=	0.197E-02
Step size increased at: x=	0.393E-02	dx=	0.393E-02
Step size increased at: x=	0.786E-02	dx=	0.477E-02

REACH MAX. at X= 1.434E+00

```

ixr= 4
iprt= 317
x= 0.143410E+01 cm
dx= 0.477000E-02 cm
p= 0.100000E+01 atm
dpdx= 0.000000E+00 atm/cm
tausr= 0.000000E+00 sec

```

TEMPERATURE(K)	= 1192.32	ENTHALPY(CAL/G)	= -3.602E+02	VELOCITY(CM/SEC)	= 1.000E+00	CP(CAL/G-K)	= 3.209E-01
DENSITY(G/CC)	= 2.833E-04	MOLE/GM-TOTAL	= 3.607E-02	AREA(CM2)	= 8.381E-01	H.T.(CAL/CC-S)	= 0.000E-01
MASS INFLUX(XMDOTE,GM/SEC)	= 0.000E-01	ENERGY INFLU X(QDOTE,CAL/SEC)	= 0.000E-01	TE(K)	= 3.000E+02	RHOE(G/CC)	= 1.172E-03
OFFER= 1.000E-16	FEXTNAL= 1.776E-04						

I	SPECIES	MASS FRXN (OVERALL)	MASS FRXN (GAS/SOLID)	MOLE FRXN (OVERALL)	MOLE FRXN (GAS/SOLID)	NET RATE (MOLE/CC-S)	DADT(I) (FRXN/S)	ALPHA(I)	ALPHA(I)	ALPHA(I)	ALPHA(I)	#N
1	H2	2.6845E-09	3.6915E-08	3.6915E-08	-2.2145E-12	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	0
2	O2	3.7789E-02	3.7789E-02	3.7789E-02	3.7789E-02	3.9080E-11	0.0000E-01	7.2784E-03	7.2784E-03	7.2784E-03	7.2784E-03	0
3	HO	2.8776E-06	2.8776E-06	4.6904E-06	4.6904E-06	-3.0751E-10	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	0
4	O	1.0838E-08	1.0838E-08	1.8779E-08	1.8779E-08	6.6861E-11	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	0
5	H	4.8457E-12	4.8457E-12	1.3327E-10	1.3327E-10	3.4719E-13	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	0
6	H2O	1.0987E-01	1.0987E-01	1.6907E-01	1.6907E-01	1.5463E-13	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	0
7	CO2	1.2571E-01	1.2571E-01	7.9181E-02	7.9181E-02	2.0419E-12	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	0
8	H2O2	3.7266E-09	3.7266E-09	3.1298E-09	3.1298E-09	-2.1674E-13	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	0
9	CO	3.7041E-09	3.7041E-09	3.0187E-09	3.0187E-09	1.2766E-12	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	0
10	CH4	4.2147E-08	4.2147E-08	4.1713E-08	4.1713E-08	-2.0419E-12	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	0
11	CH4	2.1101E-19	2.1101E-19	3.6463E-19	3.6463E-19	7.2922E-21	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	0
12	CH3	1.5035E-19	1.5035E-19	2.7722E-19	2.7722E-19	6.3149E-20	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	0
13	CH2	1.4027E-19	1.4027E-19	2.7722E-19	2.7722E-19	-6.9727E-18	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	0
14	CH	1.3019E-19	1.3019E-19	2.7722E-19	2.7722E-19	-2.5087E-17	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	0
15	C2H4	3.9401E-19	3.9401E-19	3.8935E-19	3.8935E-19	1.4975E-18	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	0
16	C2H6	3.0070E-19	3.0070E-19	2.7722E-19	2.7722E-19	-5.2238E-22	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	0
17	C2H5	2.9062E-19	2.9062E-19	2.7722E-19	2.7722E-19	-1.4893E-18	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	0
18	C2H3	2.7046E-19	2.7046E-19	2.7722E-19	2.7722E-19	-3.1509E-19	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	0
19	C	1.2011E-19	1.2011E-19	2.7722E-19	2.7722E-19	-9.8784E-20	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	0
20	C2H2	1.0919E-17	1.0919E-17	1.1625E-17	1.1625E-17	3.1391E-17	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	0
21	C2H	2.5030E-19	2.5030E-19	2.7722E-19	2.7722E-19	-3.3359E-17	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	0
22	CH2O	3.0027E-19	3.0027E-19	2.7722E-19	2.7722E-19	-6.431E-19	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	0
23	CH3O	3.1035E-19	3.1035E-19	2.7722E-19	2.7722E-19	-8.9887E-20	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	0
24	CHO	2.9019E-19	2.9019E-19	2.7722E-19	2.7722E-19	-2.0598E-17	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	0
25	N	4.5331E-18	4.5331E-18	8.9712E-18	8.9712E-18	-9.0079E-20	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	1
26	NO	5.2105E-05	5.2105E-05	4.8136E-05	4.8136E-05	-3.6802E-12	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	1
27	N2	7.2658E-01	7.2658E-01	7.1896E-01	7.1896E-01	-2.0010E-14	0.0000E-01	2.7381E-02	2.7381E-02	2.7381E-02	2.7381E-02	0
28	NO2	4.0289E-07	4.0289E-07	2.4276E-07	2.4276E-07	3.6802E-12	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	1
29	N2O	3.0307E-08	3.0307E-08	1.9088E-08	1.9088E-08	1.9974E-14	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	2
30	NH3	1.9940E-15	1.9940E-15	3.2456E-15	3.2456E-15	-1.8104E-19	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	1
31	NH2	1.0293E-17	1.0293E-17	1.7808E-17	1.7808E-17	5.3391E-21	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	1
32	NH	2.0201E-18	2.0201E-18	3.7295E-18	3.7295E-18	-1.0584E-20	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	1
33	HN2	1.1959E-16	1.1959E-16	1.1423E-16	1.1423E-16	-3.2787E-20	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	2
34	N2H2	3.0032E-19	3.0032E-19	2.7722E-19	2.7722E-19	-9.7713E-22	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	2
35	HNO	3.9740E-12	3.9740E-12	3.5520E-12	3.5520E-12	1.1472E-16	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	1
36	CN	2.6019E-19	2.6019E-19	2.7722E-19	2.7722E-19	-8.7419E-18	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	1
37	NO	4.2019E-19	4.2019E-19	2.7722E-19	2.7722E-19	5.1384E-18	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	1
38	CHN	7.5293E-18	7.5293E-18	7.7230E-18	7.7230E-18	3.7747E-18	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	1
39	HNCO	7.8415E-16	7.8415E-16	5.0523E-16	5.0523E-16	1.5437E-19	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	1
40	HOON	3.2988E-17	3.2988E-17	2.1254E-17	2.1254E-17	2.6880E-23	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	1
41	SO2	1.6183E-15	1.6183E-15	7.0028E-16	7.0028E-16	1.0082E-17	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	0
42	SO3	6.2970E-17	6.2970E-17	2.1803E-17	2.1803E-17	1.9897E-19	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	0
43	H2SO3	8.1068E-19	8.1068E-19	2.7722E-19	2.7722E-19	-1.0281E-17	0.0000E-01	3.4659E-18	3.4659E-18	3.4659E-18	3.4659E-18	0

MOLE FRACTION OF FIXED NITROGEN IN GAS PHASE = 4.842E-05

END

**DATE
FILMED**

8 / 19 / 92