THIRD QUARTER 1992

K-AREA ACID/CAUSTIC BASIN GROUNDWATER MONITORING REPORT (U)

KEY WORDS

hazardous waste
iron
KAC wells
specific conductance

PUBLICATION DATE: DECEMBER 1992

Authorized Derivative Classifier:

M. G. Ebra

MASTER

12/21/92

WESTINGHOUSE SAVANNAH RIVER COMPANY
SAVANNAH RIVER SITE
AIKEN, SC 29808

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Abstract

During third quarter 1992, samples from the KAC monitoring wells at the K-Area Acid/Caustic Basin were analyzed for indicator parameters, groundwater quality parameters, parameters indicating suitability as drinking water, and other constituents. New wells KAC 8 and 9 also were sampled for GC/MS VOA (gas chromatograph/ mass spectrometer volatile organic analyses). Monitoring results that exceeded the U.S. Environmental Protection Agency's Primary Drinking Water Standards (PDWS) or the Savannah River Site (SRS) flagging criteria or turbidity standards during the quarter are discussed in this report.

Iron exceeded the Flag 2 criterion in well KAC 2 during third quarter 1992, and specific conductance exceeded the Flag 2 criterion in new well KAC 9. The samples from well KAC 2 exceeded the SRS turbidity standard.

Contents

	Page
Abstract	iii
List of Figures	vii
List of Tables	vii
Executive Summary	1
Introduction	2
Discussion	3
Groundwater Monitoring Data	3
Analytical Results Exceeding Standards	4
Turbidity Results Exceeding Standards	4
Water Elevations, Flow Directions, and Flow Rates	4
Results for Upgradient vs. Downgradient Wells	5
Conclusions	6
Errata	7
References Cited	8
Appendix A – Primary Drinking Water Standards	A-1
Appendix B – Flagging Criteria	B-1
Appendix C – Figures	C-1
Appendix D – Groundwater Monitoring Results Tables	D-1
Appendix E – Data Quality/Useability Assessment	E-1

List of Figures

	Page
1. Location of the K-Area Acid/Caustic Basin at the Savannah River Site.	C-2
2. Location of Groundwater Monitoring Wells at the K-Area Acid/Caustic Basin	C-3
3. Water-Elevation Contour Map of the Water Table at the K-Area Acid/Caustic Basin	C-4

List of Tables

	Page
1. Constituents Exceeding the Primary Drinking Water Standards	D-4
2. Constituents Exceeding Half the Primary Drinking Water Standards or Other Flag 1 or Flag 2 Criteria	D-4
3. Groundwater Monitoring Results for Individual Wells	D-5

Executive Summary

The monitoring wells at the K-Area Acid/Caustic Basin are sampled quarterly as part of the Savannah River Site (SRS) Groundwater Monitoring Program and to comply with the terms of a consent decree executed May 26, 1988, by the U.S. District Court (District of South Carolina, Aiken Division). During third quarter 1992, samples from the monitoring wells were analyzed for indicator parameters, groundwater quality parameters, parameters indicating suitability as drinking water, and other constituents. Monitoring results that exceeded the U.S. Environmental Protection Agency Primary Drinking Water Standards (PDWS) or the SRS flagging criteria or turbidity standards are discussed in this report.

During third quarter 1992, wells KAC 6 and 7 at the K-Area Acid/Caustic Basin did not yield four well volumes prior to sampling; thus, the samples collected from these wells may not be representative groundwater samples. Iron exceeded the Flag 2 criterion in well KAC 2, and specific conductance exceeded the Flag 2 criterion in new well KAC 9. Well KAC 2 exceeded the SRS turbidity standard.

Water-table elevations indicate that the groundwater flow direction is southwest. All of the constituent levels exceeding standards were found in designated downgradient wells.

Introduction

The K-Area Acid/Caustic Basin is located in the eastern portion of K Area at the Savannah River Site (SRS) near a tributary of Pen Branch. The basin, constructed in the early 1950s, is an unlined earthen pit that received dilute sulfuric acid and sodium hydroxide solutions and other wastes from several areas within SRS. The basin provided an area for the mixing and neutralization of the dilute solutions before their discharge to nearby streams. The K-Area Acid/Caustic Basin remained in service until new neutralization facilities became operational in 1982 (Heffner and Exploration Resources, 1991).

Four groundwater monitoring wells were installed at the K-Area Acid/Caustic Basin between October 1983 and July 1984. Under the terms of a consent decree executed May 26, 1988, by the U.S. District Court (District of South Carolina, Aiken Division), the basin became subject to requirements of Subtitle C of the Resource Conservation and Recovery Act (RCRA), the South Carolina Hazardous Waste Management Regulations (SCHWMR), and associated regulations. The basin monitoring wells were reevaluated during the summer of 1988 to ensure compliance with SCHWMR. As part of this compliance effort, three additional wells were installed at the K-Area Acid/Caustic Basin during third quarter 1988.

The revised Groundwater Quality Assessment Plan (WSRC, 1991), submitted to the South Carolina Department of Health and Environmental Control on April 30, 1991, proposed the installation of two additional water-table wells at the K-Area Acid/Caustic Basin. These wells, KAC 8 and 9, have been installed and were first sampled during second quarter 1992.

The monitoring wells at the K-Area Acid/Caustic Basin are sampled quarterly as part of the SRS Groundwater Monitoring Program and to comply with SCHWMR.

Discussion

Groundwater Monitoring Data

During third quarter 1992, samples from the monitoring wells at the K-Area Acid/Caustic Basin were analyzed for indicator parameters, groundwater quality parameters, parameters indicating suitability as drinking water, and other constituents. New wells KAC 8 and 9 also were sampled for GC/MS VOA (gas chromatograph/mass spectrometer volatile organic analyses).

This report describes monitoring results that exceeded U.S. Environmental Protection Agency (EPA) Primary Drinking Water Standards (PDWS) (Appendix A), SRS flagging criteria (Appendix B), or SRS turbidity standards.

In general, the flagging criteria established by the Environmental Monitoring Section of the Environmental Protection Department at SRS for identifying constituents in high concentrations in groundwater are as follows:

- Flag 2 criteria are based on the PDWS; for constituents that do not have PDWS, Flag 2 criteria are based on the Secondary Drinking Water Standards (SDWS) or 10 times the method detection limits (MDL) as described in Appendix B. Constituent levels that equal or exceed Flag 2 criteria are described as *elevated*.
- Flag 1 criteria are based on half the PDWS; for constituents that do not have PDWS, Flag 1 criteria are based on half the SDWS or 5 times the MDL as described in Appendix B. A Flag 1 for a constituent may reflect analytical error or it may indicate the initial detection of a constituent. Thus, constituents exceeding Flag 1 criteria are included in this report and are described as *slightly elevated*.
- Flag 0 criteria are assigned to constituents having no flagging criteria or to constituent levels below Flag 1 criteria or below the sample detection limit.

Illustrations of the monitored unit at SRS (Figure 1), the individual monitoring wells (Figure 2), and the flow directions of the groundwater beneath the unit (Figure 3) are in Appendix C; monitoring results as well as analyses that exceeded holding times or PDWS are presented in Appendix D; and a discussion of data quality and useability is in Appendix E.

Analytical Results Exceeding Standards

Results for any analytes that exceeded the PDWS (see Appendix A) during third quarter 1992 are summarized in Table 1 (Appendix D). There were none.

Constituents that exceeded other Flag 1 or 2 criteria (see Appendix B) during third quarter 1992 are summarized in Table 2 (Appendix D). Iron exceeded the Flag 2 criterion in well KAC 2, with a concentration of 333 $\mu\text{g/L}$; and specific conductance exceeded the Flag 2 criterion in well KAC 9 at 903 $\mu\text{g/L}$. All results for individual wells are presented in Table 3 (Appendix D). Table 3 also indicates those analyses that exceeded holding times or PDWS.

The standard practice at SRS has been to purge a minimum of four well volumes from each well and ensure that the field parameters have stabilized before sample collection. If a well that goes dry during purging recovers sufficiently for sampling within 24 hours, the procedure is considered a single sampling event. Table 3 (Appendix D) lists the amount of water purged from each well during third quarter 1992 at the K-Area Acid/Caustic Basin. Wells KAC 6 and 7 each yielded less than one well volume prior to purging dry. Both were sampled the following day.

Turbidity Results Exceeding Standards

Turbidity results, in nephelometric turbidity units (NTU), are reported here for well samples exceeding 5 NTU and the SRS standard of 50 NTU. During third quarter 1992, wells KAC 1, 3, 4, 5, 8, and 9 had turbidity values of less than 5 NTU. Wells KAC 6 and 7 had values above 5 NTU but did not exceed the 50 NTU standard. Well KAC 2 exceeded the SRS turbidity standard with a value of 115 NTU.

A value of 5 NTU, established by EPA (1986) as a general standard for acceptability of groundwater samples, is considered unrealistic for monitoring wells at SRS. Gass (1989) has documented turbidity measurements ranging up to 5,000 NTU from properly designed wells screened in poorly productive formations. During the 1989 RCRA Compliance Evaluation Inspection, officials from EPA Region IV indicated that the SRS turbidity standard of 50 NTU is conservative. These officials also agreed that water-table wells in this area often correspond to nonaquifer formations, rendering development of these wells more difficult due to the low yield and high proportion of mobile fines typical of these formations (Bergren and Bennett, 1989).

Water Elevations, Flow Directions, and Flow Rates

Water-table elevations and the groundwater flow direction beneath the K-Area Acid/Caustic Basin are shown in Figure 3 (Appendix C). Historic data indicate a ponding or losing stream effect (water entering the groundwater from the K-Area outfall effluent stream) in this area, creating a mound of groundwater to the east of the basin. Water-table elevations indicate that the groundwater flow direction is southwest; this flow direction is consistent with historical flow patterns.

The top of the screen in monitoring well KAC 4 is submerged approximately 10 ft, resulting in a water-level measurement that may be artificially low and, thus, in somewhat skewed piezometric contours. The revised Groundwater Quality Assessment Plan for the basin (WSRC, 1991) proposed the installation of two additional wells at the K-Area Acid/Caustic Basin to provide more accurate water-elevation data. These wells, KAC 8 and 9, were installed during first quarter 1992. The screens in these wells, as in KAC 4, are submerged below the water level and were not used in contouring.

The groundwater flow rate in the water table beneath the K-Area Acid/Caustic Basin is estimated using the following equation:

$$\text{Flow (ft/day)} = \frac{\text{Hydraulic Conductivity (ft/day)}}{\text{Porosity (unitless)}} \times \frac{dh \text{ (ft)}}{dl \text{ (ft)}}$$

A hydraulic conductivity constant of 4 ft/day is based on recent hydrogeology studies for this location (Atlanta Testing and Engineering, 1992). The effective porosity value is estimated at 20% (Killian et al., 1987), dh is the difference in head, and dl is the length of the flow path. Flow rate estimates vary depending on the vertical gradient between wells, the size of the area under consideration, and the number of data points. For this reason, the estimation of flow rate must be considered accurate only to an order of magnitude.

Using the above equation with $dh = 2$ ft and $dl = 90$ ft (see Figure 3 in Appendix C), the flow rate estimate for groundwater in the water table beneath the K-Area Acid/Caustic Basin is as follows:

$$\frac{4}{0.20} \times \frac{2}{90} = 0.44 \text{ ft/day}$$

$$0.44 \text{ ft/day} \times 365 \text{ days} = 160 \text{ ft/yr}$$

Results for Upgradient vs. Downgradient Wells

Wells KAC 3 and 5 are the designated upgradient wells. No constituents exceeded the PDWS or other flagging criteria in these wells. Iron exceeded the Flag 2 criterion in well KAC 2, and specific conductance exceeded the Flag 2 criterion in well KAC 9.

Conclusions

Iron exceeded the Flag 2 criterion in designated downgradient well KAC 2, and specific conductance exceeded the Flag 2 criterion in new downgradient well KAC 9. Generally, constituents found in downgradient wells but not upgradient wells at a waste management unit are considered products of the waste management unit.

Wells KAC 1, 3, 4, 5, 8, and 9 had turbidity values of less than 5 NTU. Wells KAC 6 and 7, which did not yield four well volumes prior to sampling, did not exceed the 50 NTU standard. Well KAC 2 exceeded the SRS turbidity standard.

Water-table elevations at the K-Area Acid/Caustic Basin indicate that groundwater flow is toward the southwest relative to SRS grid coordinates; this flow direction is consistent with the historical flow pattern. The screen in well KAC 4 is submerged, which may affect the accuracy of the potentiometric contour map and thus the determination of the groundwater flow direction. Two additional water-table wells, KAC 8 and 9, which were first sampled during second quarter 1992 in accordance with the revised Groundwater Quality Assessment Plan (WSRC, 1991), also have submerged screens and provide anomalous water level data.

Errata

Third Quarter 1991:

- Errors in the computer program used to mark analyses that exceed holding times caused a number of analyses to be incorrectly flagged as exceeding holding time.

The only analyses performed by General Engineering Laboratories on samples from the KAC well series during third quarter 1991 that exceeded holding times were the cyanide analyses for well KAC 1 and the well KAC 3 replicates; the total organic halogen analyses for wells KAC 3 (four duplicates for one of the well KAC 3 replicates), 4, and 5 (four duplicates); and the gas chromatograph/mass spectrometer volatile organic analyses (28 constituents) for one of the well KAC 3 replicates. The latter analyses were run only one day out of holding.

Fourth Quarter 1991 and 1991 Summary:

- Page D-2, Holding Time: The statement concerning holding time for pH is incorrect. The statement should read "South Carolina Department of Health and Environmental Control allows only 15 minutes to elapse between sampling and analysis for pH. Thus, laboratory pH analyses always exceed holding time."

First Quarter 1992:

- No errata have been reported.

Second Quarter 1992:

- No errata have been reported.

References Cited

Atlanta Testing & Engineering, 1992. **Hydrogeology of the F-Area and K-Area Acid Caustic Basins, Savannah River Site**, WSRC-RP-91504. Westinghouse Savannah River Company, Aiken, SC.

Bergren, C. L., and C. B. Bennett, 1989. **Assessment of SRS Groundwater Monitoring Wells Impacted by Turbidity**, WSRC-RP-89-891. Westinghouse Savannah River Company, Aiken, SC.

EPA (U.S. Environmental Protection Agency), 1986. **RCRA Ground Water Monitoring Technical Enforcement Guidance Document**, OSWER-9950.1. Washington, DC.

Gass, T. E., 1989. *Monitoring Wells in Non-Aquifer Formations*. **Water Well Journal** 43(2):27-29.

Heffner, J. D., and Exploration Resources, Inc., 1991. **Technical Summary of Groundwater Quality Protection Program at the Savannah River Site (1952-1986), Volume I—Site Geohydrology and Waste Sites**, DPSP-88-1002. Westinghouse Savannah River Company, Aiken, SC.

Killian, T. H., N. L. Kolb, P. Corbo, and I. W. Marine, 1987. **F-Area Seepage Basins**, DPST-85-704. Savannah River Laboratory, E. I. du Pont de Nemours & Company, Aiken, SC.

WSRC (Westinghouse Savannah River Company), 1991. **F-, H-, K-, and P-Area Acid/Caustic Basins Groundwater Quality Assessment Plan**, WSRC-TR-91-178, Revision 1.0. Westinghouse Savannah River Company, Aiken, SC.

Appendix A – Primary Drinking Water Standards

Primary Drinking Water Standards

Analyte	Unit	Level	Status	Reference
Antimony	µg/L	5 ^a	Proposed	EPA, 1990
Arsenic	µg/L	50	Final	CFR, 1991
Barium	µg/L	2,000	Final	CFR, 1991
Benzene	µg/L	5	Final	CFR, 1991
Benzo[a]anthracene	µg/L	0.1	Proposed	EPA, 1990
Benzo[b]fluoranthene	µg/L	0.2	Proposed	EPA, 1990
Benzo[k]fluoranthene	µg/L	0.2	Proposed	EPA, 1990
Benzo[a]pyrene	µg/L	0.2	Proposed	EPA, 1990
Beryllium	µg/L	1	Proposed	EPA, 1990
Bromodichloromethane	µg/L	100 ^b	Final	CFR, 1991
Bromoform	µg/L	100 ^b	Final	CFR, 1991
2-sec-Butyl-4,6-dinitrophenol (Dinoseb)	µg/L	7	Proposed	EPA, 1990
Cadmium	µg/L	5	Final	CFR, 1991
Carbon tetrachloride	µg/L	5	Final	CFR, 1991
Chlordane	µg/L	2	Final	CFR, 1991
Chloroethene (Vinyl chloride)	µg/L	2	Final	CFR, 1991
Chloroform	µg/L	100 ^b	Final	CFR, 1991
Chromium	µg/L	100	Final	CFR, 1991
Chrysene	µg/L	0.2	Proposed	EPA, 1990
Copper	µg/L	1,300	Final	CFR, 1991
Cyanide	µg/L	200	Proposed	EPA, 1990
Dibenz[a,h]anthracene	µg/L	0.3	Proposed	EPA, 1990
Dibromochloromethane	µg/L	100 ^b	Final	CFR, 1991
Dibromochloropropane	µg/L	0.2	Final	CFR, 1991
1,2-Dichlorobenzene	µg/L	600	Final	CFR, 1991
1,4-Dichlorobenzene	µg/L	75	Final	CFR, 1991
1,2-Dichloroethane	µg/L	5	Final	CFR, 1991
1,1-Dichloroethylene	µg/L	7	Final	CFR, 1991
cis-1,2-Dichloroethylene	µg/L	70	Final	CFR, 1991
trans-1,2-Dichloroethylene	µg/L	100	Final	CFR, 1991
Dichloromethane (Methylene chloride)	µg/L	5	Proposed	EPA, 1990
2,4-Dichlorophenoxyacetic acid	µg/L	70	Final	CFR, 1991
1,2-Dichloropropane	µg/L	5	Final	CFR, 1991
Endrin	µg/L	0.2	Final	CFR, 1991
Ethylbenzene	µg/L	700	Final	CFR, 1991
Fluoride	µg/L	4,000	Final	CFR, 1991
Gross alpha ^c	pCi/L	1.5E + 01	Final	CFR, 1991
Heptachlor	µg/L	0.4	Final	CFR, 1991
Heptachlor epoxide	µg/L	0.2	Final	CFR, 1991
Hexachlorobenzene	µg/L	1	Proposed	EPA, 1990
Hexachlorocyclopentadiene	µg/L	50	Proposed	EPA, 1990
Lead	µg/L	15	Final	CFR, 1991
Lindane	µg/L	0.2	Final	CFR, 1991
Mercury	µg/L	2	Final	CFR, 1991
Methoxychlor	µg/L	40	Final	CFR, 1991
Nickel	µg/L	100	Proposed	EPA, 1990
Nitrate as nitrogen	µg/L	10,000	Final	CFR, 1991
Nitrate-nitrite as nitrogen	µg/L	10,000	Final	CFR, 1991
Nitrite as nitrogen	µg/L	1,000	Final	CFR, 1991
Nonvolatile beta ^d	pCi/L	5E + 01	Final	EPA, 1977
PCBs ^e	µg/L	0.5	Final	CFR, 1991
Pentachlorophenol	µg/L	1	Final	CFR, 1991
Radium-226 ^f	pCi/L	1.57E + 01	Proposed	EPA, 1991

Analyte	Unit	Level	Status	Reference
Radium-228 ^f	pCi/L	7.85E+00	Proposed	EPA, 1991
Radon-222	pCi/L	3E+02	Proposed	EPA, 1991
Selenium	µg/L	50	Final	CFR, 1991
Silver	µg/L	50	Final	CFR, 1991
Styrene	µg/L	100	Final	CFR, 1991
Sulfate	µg/L	400,000 ^a	Proposed	EPA, 1990
Tetrachloroethylene	µg/L	5	Final	CFR, 1991
Thallium	µg/L	1	Proposed	EPA, 1990
Toluene	µg/L	1,000	Final	CFR, 1991
Total radium ^f (Radium-226 and -228)	pCi/L	5E+00	Final	CFR, 1991
Total trihalomethanes	µg/L	100	Final	CFR, 1991
Toxaphene	µg/L	3	Final	CFR, 1991
2,4,5-TP (Silvex)	µg/L	50	Final	CFR, 1991
1,2,4-Trichlorobenzene	µg/L	9	Proposed	EPA, 1990
1,1,1-Trichloroethane	µg/L	200	Final	CFR, 1991
1,1,2-Trichloroethane	µg/L	5	Proposed	EPA, 1990
Trichloroethylene	µg/L	5	Final	CFR, 1991
Tritium	pCi/mL	2E+01	Final	CFR, 1991
Uranium	µg/L	20	Proposed	EPA, 1991
Uranium alpha activity	pCi/L	3E+01	Proposed	EPA, 1991
Xylenes	µg/L	10,000	Final	CFR, 1991

The following standards for beta- and photon-emitting radionuclides are not per se regulatory maximum contaminant levels. They represent the level at which consumption of 2 liters per day of water containing only one radionuclide would be expected to yield 4 mrem effective dose equivalent per year (ede/yr). See EPA (1977 and 1991) for details.

Antimony-125	pCi/L	3E+02	Final	EPA, 1977
Barium-140	pCi/L	9E+01	Final	EPA, 1977
Beryllium-7	pCi/L	6E+03	Final	EPA, 1977
Carbon-14	pCi/L	2E+03	Final	EPA, 1977
Cerium-141	pCi/L	3E+02	Final	EPA, 1977
Cerium-144	pCi/L	2.61E+02	Proposed	EPA, 1991
Cesium-134	pCi/L	8.13E+02 ^g	Proposed	EPA, 1991
Cesium-137	pCi/L	2E+02	Final	EPA, 1977
Chromium-51	pCi/L	6E+03	Final	EPA, 1977
Cobalt-57	pCi/L	1E+03	Final	EPA, 1977
Cobalt-58	pCi/L	9E+03	Final	EPA, 1977
Cobalt-60	pCi/L	1E+02	Final	EPA, 1977
Europium-154	pCi/L	2E+02	Final	EPA, 1977
Europium-155	pCi/L	6E+02	Final	EPA, 1977
Iodine-129	pCi/L	1E+00	Final	EPA, 1977
Iodine-131	pCi/L	3E+00	Final	EPA, 1977
Iron-55	pCi/L	2E+03	Final	EPA, 1977
Iron-59	pCi/L	2E+02	Final	EPA, 1977
Lanthanum-140	pCi/L	6E+01	Final	EPA, 1977
Manganese-54	pCi/L	3E+02	Final	EPA, 1977
Nickel-59	pCi/L	3E+02	Final	EPA, 1977
Nickel-63	pCi/L	5E+01	Final	EPA, 1977
Niobium-95	pCi/L	3E+02	Final	EPA, 1977
Plutonium-241	pCi/L	6.26E+01	Proposed	EPA, 1991
Potassium-40	pCi/L	3E+02	Proposed	EPA, 1986
Ruthenium-103	pCi/L	2E+02	Final	EPA, 1977
Ruthenium-106	pCi/L	3E+01	Final	EPA, 1977

Analyte	Unit	Level	Status	Reference
Sodium-22	pCi/L	4.66E+02	Proposed	EPA, 1991
Strontium-89	pCi/L	2E+01 ^h	Final	EPA, 1977
Strontium-89/90 ⁱ	pCi/L	8E+00	Final	CFR, 1991
Strontium-90	pCi/L	8E+00	Final	CFR, 1991
Technetium-99	pCi/L	9E+02	Final	EPA, 1977
Thorium-234	pCi/L	4.01E+02	Proposed	EPA, 1991
Tin-113	pCi/L	3E+02	Final	EPA, 1977
Zinc-65	pCi/L	3E+02	Final	EPA, 1977
Zirconium-95	pCi/L	2E+02	Final	EPA, 1977
Zirconium/Niobium-95 ⁱ	pCi/L	2E+02	Final	EPA, 1977

The following standards for alpha-emitting radionuclides are not per se regulatory maximum contaminant levels. They represent the level at which consumption of 2 liters per day of water containing only one radionuclide would be expected to yield a lifetime cancer incidence risk of 1×10^{-4} . See EPA (1991) for details.

Americium-241	pCi/L	6.34E+00	Proposed	EPA, 1991
Americium-243	pCi/L	6.37E+00	Proposed	EPA, 1991
Curium-242	pCi/L	1.33E+02	Proposed	EPA, 1991
Curium-243	pCi/L	8.3E+00	Proposed	EPA, 1991
Curium-244	pCi/L	9.84E+00	Proposed	EPA, 1991
Curium-246	pCi/L	6.27E+00	Proposed	EPA, 1991
Neptunium-237	pCi/L	7.06E+00	Proposed	EPA, 1991
Plutonium-238	pCi/L	7.02E+00	Proposed	EPA, 1991
Plutonium-239	pCi/L	6.21E+01	Proposed	EPA, 1991
Plutonium-239/240 ⁱ	pCi/L	6.21E+01	Proposed	EPA, 1991
Plutonium-240	pCi/L	6.22E+01	Proposed	EPA, 1991
Plutonium-242	pCi/L	6.54E+01	Proposed	EPA, 1991
Thorium-228	pCi/L	1.25E+02	Proposed	EPA, 1991
Thorium-230	pCi/L	7.92E+01	Proposed	EPA, 1991
Thorium-232	pCi/L	8.8E+01	Proposed	EPA, 1991
Uranium-233/234 ⁱ	pCi/L	1.38E+01	Proposed	EPA, 1991
Uranium-234	pCi/L	1.39E+01	Proposed	EPA, 1991
Uranium-235	pCi/L	1.45E+01	Proposed	EPA, 1991
Uranium-238	pCi/L	1.46E+01	Proposed	EPA, 1991

^a This value is the lower of two proposed levels.

^b This value is the drinking water standard for total trihalomethanes (the sum of bromoform, bromodichloromethane, chloroform, and dibromochloromethane).

^c The standard given is for gross alpha including radium-226 but excluding radon and uranium. EPA (1991) has proposed the same value as a gross alpha standard excluding radium-226 as well as uranium and radon-222.

^d This is the screening level above which providers of public drinking water should perform analyses for specific man-made radionuclides. The total dose from all such radionuclides is subject to the 4 mrem ede/yr standard.

^e Analyses were conducted in 1992 for the following: PCB 1016, PCB 1221, PCB 1232, PCB 1242, PCB 1248, PCB 1254, and PCB 1260.

^f The standard currently in effect for radium is that for total radium (as radium-226 plus radium-228). The values used in this document for the individual radionuclides, while higher, are lower than a proposed standard (EPA, 1991) of 20 pCi/L for each.

^g The Environmental Protection Department/Environmental Monitoring Section uses the proposed standard because it is a lower value; the final primary drinking water standard in 1977 may have been in error.

^h This value is the lower of two levels given for strontium-89.

ⁱ For double radionuclide analyses where each separate radionuclide has its own standard, the more stringent standard is used.

References

CFR (Code of Federal Regulations), 1991. *National Primary Drinking Water Regulations*, 40 CFR, Part 141, pp. 578-715. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1977. **National Interim Primary Drinking Water Regulations**, EPA-570/9-76-003. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1986. *Water Pollution Control; National Primary Drinking Water Regulations, Radionuclides (Proposed)*, **Federal Register**, September 30, 1986, pp. 34835-34862. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1990. *National Primary and Secondary Drinking Water Regulations; Synthetic Organic Chemicals and Inorganic Chemicals; Proposed Rule*, **Federal Register**, July 25, 1990, pp. 30369-30448. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1991. *National Primary Drinking Water Regulations; Radionuclides; Proposed Rule*, **Federal Register**, July 18, 1991, pp. 33052-33127. Washington, DC.

Appendix B – Flagging Criteria

Flagging Criteria

Beginning in 1991, the Savannah River Site Environmental Protection Department/Environmental Monitoring Section modified its guidelines for flagging constituents in the Groundwater Monitoring Program. These flagging criteria are as follows:

- Flag 2 criteria for constituents equal the U.S. Environmental Protection Agency (EPA) Primary Drinking Water Standard (PDWS), the EPA proposed PDWS, or the EPA Secondary Drinking Water Standard (SDWS). If a constituent does not have a drinking water standard, the Flag 2 criterion equals 10 times the method detection limit (MDL) calculated as the 90th percentile detection limit obtained recently by one of the primary analytical laboratories.
- Flag 1 criteria for constituents equal one-half of the EPA PDWS, one-half the EPA proposed PDWS, or one-half the EPA SDWS. If a constituent does not have an EPA drinking water standard, the Flag 1 criterion equals 5 times the MDL calculated as the 90th percentile detection limit obtained recently by one of the primary analytical laboratories.
- Flag 0 criteria are assigned to constituent levels below Flag 1 criteria, constituent levels below the sample detection limits, or constituents having no flagging criteria.

The following parameters are not assigned flagging criteria: alkalinity, calcium, carbonate, color, corrosivity, magnesium, odor, potassium, Eh, silica, sodium, total dissolved solids, total phosphorus, total phosphates (as P), and turbidity. In addition, common laboratory contaminants and cleaners including phthalates, methylene chloride, ketones, and toluene are not assigned flagging criteria.

Analyte	Unit	Flag 1	Flag 2	Source
Acenaphthene	µg/L	50	100	EPA Method 8270
Acenaphthylene	µg/L	50	100	EPA Method 8270
Acetone	µg/L	50	100	EPA Method 8240
Acetonitrile (Methyl cyanide)	µg/L	500	1,000	EPA Method 8240
Acetophenone	µg/L	50	100	EPA Method 8270
2-Acetylaminofluorene	µg/L	50	100	EPA Method 8270
Acrolein	µg/L	100	200	EPA Method 8240
Acrylonitrile	µg/L	100	200	EPA Method 8240
Aldrin	µg/L	2.5	5	EPA Method 8080
Alkalinity (as CaCO ₃)		No flag	No flag	Set by EPD/EMS
Allyl chloride	µg/L	250	500	EPA Method 8240
Aluminum	µg/L	25	50	Secondary DWS (CFR, 1991b)
Americium-241	pCi/L	3.17E+00	6.34E+00	Proposed DWS (EPA, 1991)
Americium-243	pCi/L	3.19E+00	6.37E+00	Proposed DWS (EPA, 1991)
4-Aminobiphenyl	µg/L	50	100	EPA Method 8270
Ammonia	µg/L	500	1,000	APHA Method 417B
Ammonia nitrogen	µg/L	50	100	EPA Method 350.1
Aniline	µg/L	50	100	EPA Method 8270
Anthracene	µg/L	50	100	EPA Method 8270
Antimony	µg/L	2.5	5	Proposed DWS (EPA, 1990)
Antimony-125	pCi/L	1.5E+02	3E+02	Final DWS (EPA, 1977)
Aramite	µg/L	50	100	EPA Method 8270

Analyte	Unit	Flag 1	Flag 2	Source
Arsenic	µg/L	25	50	Final DWS (CFR, 1991a)
Barium	µg/L	1,000	2,000	Final DWS (CFR, 1991a)
Barium-140	pCi/L	4.5E + 01	9E + 01	Final DWS (EPA, 1977)
Benzene	µg/L	2.5	5	Final DWS (CFR, 1991a)
alpha-Benzene hexachloride	µg/L	2.5	5	EPA Method 8080
beta-Benzene hexachloride	µg/L	2.5	5	EPA Method 8080
delta-Benzene hexachloride	µg/L	2.5	5	EPA Method 8080
Benzidine	µg/L	250	500	EPA Method 8270
Benzo[a]anthracene	µg/L	0.05	0.1	Proposed DWS (EPA, 1990)
Benzo[b]fluoranthene	µg/L	0.1	0.2	Proposed DWS (EPA, 1990)
Benzo[k]fluoranthene	µg/L	0.1	0.2	Proposed DWS (EPA, 1990)
Benzo[g,h,i]perylene	µg/L	50	100	EPA Method 8270
Benzo[a]pyrene	µg/L	0.1	0.2	Proposed DWS (EPA, 1990)
Benzoic acid	µg/L	250	500	EPA Method 8270
1,4-Benzoquinone	µg/L	50	100	EPA Method 8270
Benzyl alcohol	µg/L	100	200	EPA Method 8270
Beryllium	µg/L	0.5	1	Proposed DWS (EPA, 1990)
Beryllium-7	pCi/L	3E + 03	6E + 03	Final DWS (EPA, 1977)
Bis(2-chloroethoxy) methane	µg/L	50	100	EPA Method 8270
Bis(2-chloroethyl) ether	µg/L	50	100	EPA Method 8270
Bis(2-chloroisopropyl) ether	µg/L	50	100	EPA Method 8270
Bis(chloromethyl) ether	µg/L	50	100	EPA Method 8270
Bis(chloromethyl-ethyl) ether	µg/L	50	100	EPA Method 8270
Bis(2-ethylhexyl) phthalate		No flag	No flag	Set by EPD/EMS
Bromide	µg/L	5,000	10,000	EPA Method 300.0
Bromodichloromethane	µg/L	50	100	Final DWS (CFR, 1991a)
Bromoform	µg/L	50	100	Final DWS (CFR, 1991a)
Bromomethane (Methyl bromide)	µg/L	5	10	EPA Method 8240
4-Bromophenyl phenyl ether	µg/L	50	100	EPA Method 8270
2-sec-Butyl-4,6-dinitrophenol	µg/L	3.5	7	Proposed DWS (EPA, 1990)
Butylbenzyl phthalate		No flag	No flag	Set by EPD/EMS
Cadmium	µg/L	2.5	5	Final DWS (CFR, 1991a)
Calcium		No flag	No flag	Set by EPD/EMS
Carbon disulfide	µg/L	5	10	EPA Method 8240
Carbon tetrachloride	µg/L	2.5	5	Final DWS (CFR, 1991a)
Carbon-14	pCi/L	1E + 03	2E + 03	Final DWS (EPA, 1977)
Carbonate	µg/L	500	1,000	EPA Method 310.1
Cerium-141	pCi/L	1.5E + 02	3E + 02	Final DWS (EPA, 1977)
Cerium-144	pCi/L	1.31E + 02	2.61E + 02	Proposed DWS (EPA, 1991)
Cesium-134	pCi/L	4.07E + 01	8.13E + 01	Proposed DWS (EPA, 1991)
Cesium-137	pCi/L	1E + 02	2E + 02	Final DWS (EPA, 1977)
Chlordane	µg/L	1	2	Final DWS (CFR, 1991a)
Chloride	µg/L	125,000	250,000	Secondary DWS (CFR, 1991b)
4-Chloroaniline	µg/L	50	100	EPA Method 8270
Chlorobenzene	µg/L	5	10	EPA Method 8240
Chlorobenzilate	µg/L	50	100	EPA Method 8270
Chloroethane	µg/L	5	10	EPA Method 8240
Chloroethene (Vinyl chloride)	µg/L	1	2	Final DWS (CFR, 1991a)
Chloroethyl vinyl ether	µg/L	5	10	EPA Method 8240
2-Chloroethyl vinyl ether	µg/L	5	10	EPA Method 8240
Chloroform	µg/L	50	100	Final DWS (CFR, 1991a)
para-Chloro-meta-cresol	µg/L	50	100	EPA Method 8270
Chloromethane (Methyl chloride)	µg/L	5	10	EPA Method 8240
2-Chloronaphthalene	µg/L	50	100	EPA Method 8240
2-Chlorophenol	µg/L	50	100	EPA Method 8270

Analyte	Unit	Flag 1	Flag 2	Source
4-Chlorophenyl phenyl ether	µg/L	50	100	EPA Method 8270
Chloroprene	µg/L	1,000	2,000	EPA Method 8240
Chromium	µg/L	50	100	Final DWS (CFR, 1991a)
Chromium-51	pCi/L	3E+03	6E+03	Final DWS (EPA, 1977)
Chrysene	µg/L	0.1	0.2	Proposed DWS (EPA, 1990)
Cobalt	µg/L	20	40	EPA Method 6010
Cobalt-57	pCi/L	5E+02	1E+03	Final DWS (EPA, 1977)
Cobalt-58	pCi/L	4.5E+03	9E+03	Final DWS (EPA, 1977)
Cobalt-60	pCi/L	5E+01	1E-02	Final DWS (EPA, 1977)
Color		No flag	No flag	Set by EPD/EMS
Copper	µg/L	650	1,300	Final DWS (CFR, 1991a)
Corrosivity		No flag	No flag	Set by EPD/EMS
m-Cresol (3-Methylphenol)	µg/L	50	100	EPA Method 8270
o-Cresol (2-Methylphenol)	µg/L	50	100	EPA Method 8270
p-Cresol (4-Methylphenol)	µg/L	50	100	EPA Method 8270
Curium-242	pCi/L	6.65E+01	1.33E+02	Proposed DWS (EPA, 1991)
Curium-243	pCi/L	4.15E+00	8.3E+00	Proposed DWS (EPA, 1991)
Curium-244	pCi/L	4.92E+00	9.84E+00	Proposed DWS (EPA, 1991)
Curium-246	pCi/L	3.14E+00	6.27E+00	Proposed DWS (EPA, 1991)
Cyanide	µg/L	100	200	Proposed DWS (EPA, 1990)
p,p'-DDD	µg/L	2.5	5	EPA Method 8080
p,p'-DDE	µg/L	2.5	5	EPA Method 8080
p,p'-DDT	µg/L	2.5	5	EPA Method 8080
Di-n-butyl phthalate		No flag	No flag	Set by EPD/EMS
Di-n-octyl phthalate		No flag	No flag	Set by EPD/EMS
Diallate	µg/L	50	100	EPA Method 8270
Dibenz[a,h]anthracene	µg/L	0.15	0.3	Proposed DWS (EPA, 1990)
Dibenzofuran	µg/L	50	100	EPA Method 8270
Dibromochloromethane	µg/L	50	100	Final DWS (CFR, 1991a)
Dibromochloropropane	µg/L	0.1	0.2	Final DWS (CFR, 1991a)
1,2-Dibromo-3-chloropropane	µg/L	250	500	EPA Method 8240
1,2-Dibromoethane	µg/L	100	200	EPA Method 8240
Dibromomethane (Methylene bromide)	µg/L	5	10	EPA Method 8240
1,2-Dichlorobenzene	µg/L	300	600	Final DWS (CFR, 1991a)
1,3-Dichlorobenzene	µg/L	50	100	EPA Method 8270
1,4-Dichlorobenzene	µg/L	37.5	75	Final DWS (CFR, 1991a)
3,3'-Dichlorobenzidine	µg/L	50	100	EPA Method 8270
trans-1,4-Dichloro-2-butene	µg/L	150	300	EPA Method 8240
Dichlorodifluoromethane	µg/L	5	10	EPA Method 8240
1,1-Dichloroethane	µg/L	5	10	EPA Method 8240
1,2-Dichloroethane	µg/L	2.5	5	Final DWS (CFR, 1991a)
cis-1,2-Dichloroethene	µg/L	35	70	Final DWS (CFR, 1991a)
1,1-Dichloroethylene	µg/L	3.5	7	Final DWS (CFR, 1991a)
1,2-Dichloroethylene	µg/L	25	50	EPA Method 8240
trans-1,2-Dichloroethylene	µg/L	50	100	Final DWS (CFR, 1991a)
Dichloromethane (Methylene chloride)		No flag	No flag	Set by EPD/EMS
2,4-Dichlorophenol	µg/L	50	100	EPA Method 8270
2,6-Dichlorophenol	µg/L	50	100	EPA Method 8270
2,4-Dichlorophenoxyacetic acid	µg/L	35	70	Final DWS (CFR, 1991a)
1,2-Dichloropropane	µg/L	2.5	5	Final DWS (CFR, 1991a)
cis-1,3-Dichloropropene	µg/L	5	10	EPA Method 8240
trans-1,3-Dichloropropene	µg/L	5	10	EPA Method 8240
Dieldrin	µg/L	2.5	5	EPA Method 8080

<u>Analyte</u>	<u>Unit</u>	<u>Flag 1</u>	<u>Flag 2</u>	<u>Source</u>
Diethyl phthalate		No flag	No flag	Set by EPD/EMS
Dimethoate	µg/L	50	100	EPA Method 8270
p-Dimethylaminoazobenzene	µg/L	50	100	EPA Method 8270
p-(Dimethylamino)ethylaniline	µg/L	50	100	EPA Method 8270
7,12-Dimethylbenz[a]anthracene	µg/L	50	100	EPA Method 8270
3,3'-Dimethylbenzidine	µg/L	50	100	EPA Method 8270
a,a-Dimethylphenethylamine	µg/L	50	100	EPA Method 8270
2,4-Dimethyl phenol	µg/L	50	100	EPA Method 8270
Dimethyl phthalate		No flag	No flag	Set by EPD/EMS
1,3-Dinitrobenzene	µg/L	50	100	EPA Method 8270
4,6-Dinitro-ortho-cresol	µg/L	250	500	EPA Method 8270
2,4-Dinitrophenol	µg/L	250	500	EPA Method 8270
2,4-Dinitrotoluene	µg/L	50	100	EPA Method 8270
2,6-Dinitrotoluene	µg/L	50	100	EPA Method 8270
1,4-Dioxane	µg/L	50	100	EPA Method 8270
Diphenylamine	µg/L	50	100	EPA Method 8270
1,2-Diphenylhydrazine	µg/L	50	100	EPA Method 8270
Dissolved organic carbon	µg/L	5,000	10,000	EPA Method 9060
Disulfoton	µg/L	50	100	EPA Method 8270
Eh		No flag	No flag	Set by EPD/EMS
alpha-Endosulfan	µg/L	50	100	EPA Method 8270
beta-Endosulfan	µg/L	50	100	EPA Method 8270
Endosulfan I	µg/L	2.5	5	EPA Method 8080
Endosulfan II	µg/L	2.5	5	EPA Method 8080
Endosulfan sulfate	µg/L	2.5	5	EPA Method 8080
Endrin	µg/L	0.1	0.2	Final DWS (CFR, 1991a)
Endrin aldehyde	µg/L	2.5	5	EPA Method 8080
Endrin ketone		No flag	No flag	Set by EPD/EMS
Ethyl methacrylate	µg/L	50	100	EPA Method 8270
Ethyl methanesulfonate	µg/L	50	100	EPA Method 8270
Ethylbenzene	µg/L	350	700	Final DWS (CFR, 1991a)
Europium-154	pCi/L	1E+02	2E+02	Final DWS (EPA, 1977)
Europium-155	pCi/L	3E+02	6E+02	Final DWS (EPA, 1977)
Famphur	µg/L	50	100	EPA Method 8270
Fluoranthene	µg/L	50	100	EPA Method 8270
Fluorene	µg/L	50	100	EPA Method 8270
Fluoride	µg/L	2,000	4,000	Final DWS (CFR, 1991a)
Gross alpha	pCi/L	7.5E+00	1.5E+01	Final DWS (CFR, 1991a)
Heptachlor	µg/L	0.2	0.4	Final DWS (CFR, 1991a)
Heptachlor epoxide	µg/L	0.1	0.2	Final DWS (CFR, 1991a)
Heptachlorodibenzo-p-dioxin isomers	µg/L	0.00325	0.0065	EPA Method 8280
1,2,3,4,6,7,8-Heptachlorodibenzo-p-dioxin	µg/L	0.00325	0.0065	EPA Method 8280
Heptachlorodibenzo-p-furan isomers	µg/L	0.00225	0.0045	EPA Method 8280
1,2,3,4,6,7,8-Heptachlorodibenzo-p-furan	µg/L	0.00225	0.0045	EPA Method 8280
Hexachlorobenzene	µg/L	0.5	1	Proposed DWS (EPA, 1990)
Hexachlorobutadiene	µg/L	50	100	EPA Method 8270
Hexachlorocyclopentadiene	µg/L	25	50	Proposed DWS (EPA, 1990)
Hexachlorodibenzo-p-dioxin isomers	µg/L	0.00225	0.0045	EPA Method 8280
1,2,3,4,7,8-Hexachlorodibenzo-p-dioxin	µg/L	0.00225	0.0045	EPA Method 8280
Hexachlorodibenzo-p-furan isomers	µg/L	0.002	0.004	EPA Method 8280

Analyte	Unit	Flag 1	Flag 2	Source
1,2,3,4,7,8-Hexachlorodibenzo- p-furan	µg/L	0.002	0.004	EPA Method 8280
Hexachloroethane	µg/L	50	100	EPA Method 8270
Hexachlorophene	µg/L	250	500	EPA Method 8270
Hexachloropropene	µg/L	50	100	EPA Method 8270
2-Hexanone	µg/L	100	200	EPA Method 8240
Indeno[1,2,3-c,d]pyrene	µg/L	50	100	EPA Method 8270
Iodine	µg/L	500	1,000	EPA Method 415
Iodine-129	pCi/L	5E-01	1E+00	Final DWS (EPA, 1977)
Iodine-131	pCi/L	1.5E+00	3E+00	Final DWS (EPA, 1977)
Iodomethane (Methyl iodide)	µg/L	75	150	EPA Method 8240
Iron	µg/L	150	300	Secondary DWS (CFR, 1991b)
Iron-55	pCi/L	1E+03	2E+03	Final DWS (EPA, 1977)
Iron-59	pCi/L	1E+02	2E+02	Final DWS (EPA, 1977)
Isobutyl alcohol	µg/L	500	1,000	EPA Method 8240
Isodrin	µg/L	50	100	EPA Method 8270
Isophorone	µg/L	50	100	EPA Method 8270
Isosafrole	µg/L	50	100	EPA Method 8270
Kepone	µg/L	50	100	EPA Method 8270
Lanthanum-140	pCi/L	3E+01	6E+01	Final DWS (EPA, 1977)
Lead	µg/L	7.5	15	Final DWS (CFR, 1991a)
Lindane	µg/L	0.1	0.2	Final DWS (CFR, 1991a)
Lithium	µg/L	25	50	EPA Method 6010
Magnesium		No flag	No flag	Set by EPD/EMS
Manganese	µg/L	25	50	Secondary DWS (CFR, 1991b)
Manganese-54	pCi/L	1.5E+02	3E+02	Final DWS (EPA, 1977)
Mercury	µg/L	1	2	Final DWS (CFR, 1991a)
Methacrylonitrile	µg/L	250	500	EPA Method 8240
Methapyrilene	µg/L	50	100	EPA Method 8270
Methoxychlor	µg/L	20	40	Final DWS (CFR, 1991a)
3-Methylcholanthrene	µg/L	50	100	EPA Method 8270
2-Methyl-4,6-dinitrophenol	µg/L	250	500	EPA Method 8270
Methyl ethyl ketone		No flag	No flag	Set by EPD/EMS
Methyl isobutyl ketone		No flag	No flag	Set by EPD/EMS
Methyl methacrylate	µg/L	50	100	EPA Method 8270
Methyl methanesulfonate	µg/L	50	100	EPA Method 8270
2-Methylnaphthalene	µg/L	50	100	EPA Method 8270
Molybdenum	µg/L	250	500	EPA Method 6010
Naphthalene	µg/L	50	100	EPA Method 8270
1,4-Naphthoquinone	µg/L	50	100	EPA Method 8270
1-Naphthylamine	µg/L	50	100	EPA Method 8270
2-Naphthylamine	µg/L	50	100	EPA Method 8270
Neptunium-237	pCi/L	3.53E+00	7.06E+00	Proposed DWS (EPA, 1991)
Nickel	µg/L	50	100	Proposed DWS (EPA, 1990)
Nickel-59	pCi/L	1.5E+02	3E+02	Final DWS (EPA, 1977)
Nickel-63	pCi/L	2.5E+01	5E+01	Final DWS (EPA, 1977)
Niobium-95	pCi/L	1.5E+02	3E+02	Final DWS (EPA, 1977)
Nitrate as nitrogen	µg/L	5,000	10,000	Final DWS (CFR, 1991a)
Nitrate-nitrite as nitrogen	µg/L	5,000	10,000	Final DWS (CFR, 1991a)
Nitrite as nitrogen	µg/L	500	1,000	Final DWS (CFR, 1991a)
2-Nitroaniline	µg/L	50	100	EPA Method 8270
3-Nitroaniline	µg/L	50	100	EPA Method 8270
4-Nitroaniline	µg/L	50	100	EPA Method 8270
Nitrobenzene	µg/L	50	100	EPA Method 8270
Nitrogen by Kjeldahl method	µg/L	500	1,000	EPA Method 351.2

Analyte	Unit	Flag 1	Flag 2	Source
2-Nitrophenol	µg/L	50	100	EPA Method 8270
4-Nitrophenol	µg/L	50	100	EPA Method 8270
4-Nitroquinoline-1-oxide	µg/L	50	100	EPA Method 8270
N-Nitrosodi-n-butylamine	µg/L	50	100	EPA Method 8270
N-Nitrosodiethylamine	µg/L	50	100	EPA Method 8270
N-Nitrosodimethylamine	µg/L	50	100	EPA Method 8270
N-Nitrosodiphenylamine	µg/L	50	100	EPA Method 8270
N-Nitrosodi-propylamine	µg/L	50	100	EPA Method 8270
N-Nitrosomethylethylamine	µg/L	50	100	EPA Method 8270
N-Nitrosomorpholine	µg/L	50	100	EPA Method 8270
N-Nitrosopiperidine	µg/L	50	100	EPA Method 8270
N-Nitrosopyrrolidine	µg/L	50	100	EPA Method 8270
5-Nitro-o-toluidine	µg/L	50	100	EPA Method 8270
Nonvolatile beta	pCi/L	2.5E+01	5E+01	Proposed DWS (EPA, 1986)
Octachlorodibenzo-p-dioxin isomers	µg/L	0.005	0.01	EPA Method 8280
Octachlorodibenzo-p-furan isomers	µg/L	0.005	0.01	EPA Method 8280
Odor		No flag	No flag	Set by EPD/EMS
Oil & Grease	µg/L	5,000	10,000	EPA Method 413.1
Parathion	µg/L	2.5	5	EPA Method 8080
Parathion methyl	µg/L	2.5	5	EPA Method 8080
PCB 1016	µg/L	0.25	0.5	Final DWS (CFR, 1991a)
PCB 1221	µg/L	0.25	0.5	Final DWS (CFR, 1991a)
PCB 1232	µg/L	0.25	0.5	Final DWS (CFR, 1991a)
PCB 1242	µg/L	0.25	0.5	Final DWS (CFR, 1991a)
PCB 1248	µg/L	0.25	0.5	Final DWS (CFR, 1991a)
PCB 1254	µg/L	0.25	0.5	Final DWS (CFR, 1991a)
PCB 1260	µg/L	0.25	0.5	Final DWS (CFR, 1991a)
PCB 1262	µg/L	0.25	0.5	Final DWS (CFR, 1991a)
Pentachlorobenzene	µg/L	50	100	EPA Method 8270
Pentachlorodibenzo-p-dioxin isomers	µg/L	0.00275	0.0055	EPA Method 8280
1,2,3,7,8-Pentachlorodibenzo-p-dioxin	µg/L	0.00275	0.0055	EPA Method 8280
Pentachlorodibenzo-p-furan isomers	µg/L	0.00275	0.0055	EPA Method 8280
1,2,3,7,8-Pentachlorodibenzo-p-furan	µg/L	0.00275	0.0055	EPA Method 8280
Pentachloroethane	µg/L	50	100	EPA Method 8270
Pentachloronitrobenzene	µg/L	50	100	EPA Method 8270
Pentachlorophenol	µg/L	0.5	1	Final DWS (CFR, 1991a)
pH	pH	8	10	Set by EPD/EMS
pH	pH	4	3	Set by EPD/EMS
Phenacetin	µg/L	50	100	EPA Method 8270
Phenanthrene	µg/L	50	100	EPA Method 8270
Phenol	µg/L	50	100	EPA Method 8270
Phenols	µg/L	25	50	EPA Method 420.1
p-Phenylenediamine	µg/L	50	100	EPA Method 8270
Phorate	µg/L	2.5	5	EPA Method 8080
2-Picoline	µg/L	50	100	EPA Method 8270
Plutonium-238	pCi/L	3.51E+00	7.02E+00	Proposed DWS (EPA, 1991)
Plutonium-239	pCi/L	3.11E+01	6.21E+01	Proposed DWS (EPA, 1991)
Plutonium-239/240 ^a	pCi/L	3.11E+01	6.21E+01	Proposed DWS (EPA, 1991)
Plutonium-240	pCi/L	3.11E+01	6.22E+01	Proposed DWS (EPA, 1991)
Plutonium-241	pCi/L	3.13E+01	6.26E+01	Proposed DWS (EPA, 1991)
Plutonium-242	pCi/L	3.27E+01	6.54E+01	Proposed DWS (EPA, 1991)
Potassium		No flag	No flag	Set by EPD/EMS

Analyte	Unit	Flag 1	Flag 2	Source
Potassium-40	pCi/L	1.5E+02	3E+02	Proposed DWS (EPA, 1986)
Pronamid	µg/L	50	100	EPA Method 8270
Propionitrile	µg/L	1,000	2,000	EPA Method 8240
Pyrene	µg/L	50	100	EPA Method 8270
Pyridine	µg/L	50	100	EPA Method 8270
Radium-226	pCi/L	7.85E+00	1.57E+01	Proposed DWS (EPA, 1991)
Radium-228	pCi/L	3.93E+00	7.85E+00	Proposed DWS (EPA, 1991)
Radon-222	pCi/L	1.5E+02	3E+02	Proposed DWS (EPA, 1991)
Ruthenium-103	pCi/L	1E+02	2E+02	Final DWS (EPA, 1977)
Ruthenium-106	pCi/L	1.5E+01	3E+01	Final DWS (EPA, 1977)
Safrole	µg/L	50	100	EPA Method 8270
Selenium	µg/L	25	50	Final DWS (CFR, 1991a)
Silica		No flag	No flag	Set by EPD/EMS
Silver	µg/L	25	50	Final DWS (CFR, 1991a)
Sodium		No flag	No flag	Set by EPD/EMS
Sodium-22	pCi/L	2.33E+02	4.66E+02	Proposed DWS (EPA, 1991)
Specific conductance	µS/cm	250	500	Set by EPD/EMS
Strontium-89	pCi/L	1E+01	2E+01	Final DWS (EPA, 1977)
Strontium-89/90 ^a	pCi/L	4E+00	8E+00	Final DWS (CFR, 1991a)
Strontium-90	pCi/L	4E+00	8E+00	Final DWS (CFR, 1991a)
Styrene	µg/L	50	100	Final DWS (CFR, 1991a)
Sulfate	µg/L	200,000	400,000	Proposed DWS (EPA, 1990)
Sulfide	µg/L	5,000	10,000	EPA Method 9030
Sulfotep	µg/L	50	100	EPA Method 8270
Surfactants		No flag	No flag	Set by EPD/EMS
2,3,7,8-TCDD	µg/L	0.00225	0.0045	EPA Method 8280
2,3,7,8-TCDF	µg/L	0.002	0.004	EPA Method 8280
Technetium-99	pCi/L	4.5E+02	9E+02	Final DWS (EPA, 1977)
1,2,4,5-Tetrachlorobenzene	µg/L	50	100	EPA Method 8270
Tetrachlorodibenzo-p-dioxin isomers	µg/L	0.00225	0.0045	EPA Method 8280
Tetrachlorodibenzo-p-furan isomers	µg/L	0.002	0.004	EPA Method 8280
1,1,1,2-Tetrachloroethane	µg/L	5	10	EPA Method 8240
1,1,2,2-Tetrachloroethane	µg/L	5	10	EPA Method 8240
Tetrachloroethylene	µg/L	2.5	5	Final DWS (CFR, 1991a)
2,3,4,6-Tetrachlorophenol	µg/L	50	100	EPA Method 8270
Tetraethyl dithiopyrophosphate	µg/L	50	100	EPA Method 8270
Thallium	µg/L	0.5	1	Proposed DWS (EPA, 1990)
Thionazin	µg/L	50	100	EPA Method 8270
Thorium-228	pCi/L	6.25E+01	1.25E+02	Proposed DWS (EPA, 1991)
Thorium-230	pCi/L	3.96E+01	7.92E+01	Proposed DWS (EPA, 1991)
Thorium-232	pCi/L	4.4E+01	8.8E+01	Proposed DWS (EPA, 1991)
Thorium-234	pCi/L	2E+02	4.01E+02	Proposed DWS (EPA, 1991)
Tin	µg/L	10	20	EPA Method 282.2
Tin-113	pCi/L	1.5E+02	3E+02	Final DWS (EPA, 1977)
Toluene	µg/L	500	1,000	Final DWS (CFR, 1991a)
o-Toluidine	µg/L	50	100	EPA Method 8270
Total carbon	µg/L	5,000	10,000	EPA Method 9060
Total dissolved solids		No flag	No flag	Set by EPD/EMS
Total hydrocarbons	µg/L	5,000	10,000	EPA Method 418.1
Total inorganic carbon	µg/L	5,000	10,000	EPA Method 9060
Total organic carbon	µg/L	5,000	10,000	EPA Method 9060
Total organic halogens	µg/L	25	50	EPA Method 9020
Total organic nitrogen	µg/L	500	1,000	EPA Method 420

Analyte	Unit	Flag 1	Flag 2	Source
Total petroleum hydrocarbons	µg/L	5,000	10,000	EPA Method 418.1
Total phosphates (as P)		No flag	No flag	Set by EPD/EMS
Total phosphorus		No flag	No flag	Set by EPD/EMS
Total radium	pCi/L	2.5E+00	5E+00	Final DWS (CFR, 1991a)
Total silica	µg/L	500	1,000	EPA Method 6010
Total trihalomethanes	µg/L	50	100	Final DWS (CFR, 1991a)
Toxaphene	µg/L	1.5	3	Final DWS (CFR, 1991a)
2,4,5-TP (Silvex)	µg/L	25	50	Final DWS (CFR, 1991a)
Tributyl phosphate	µg/L	50	100	EPA Method 8270
1,2,4-Trichlorobenzene	µg/L	4.5	9	Proposed DWS (EPA, 1990)
1,1,1-Trichloroethane	µg/L	100	200	Final DWS (CFR, 1991a)
1,1,2-Trichloroethane	µg/L	2.5	5	Proposed DWS (EPA, 1990)
Trichloroethylene	µg/L	2.5	5	Final DWS (CFR, 1991a)
Trichlorofluoromethane	µg/L	5	10	EPA Method 8240
2,4,5-Trichlorophenol	µg/L	50	100	EPA Method 8270
2,4,6-Trichlorophenol	µg/L	50	100	EPA Method 8270
2,4,5-Trichlorophenoxyacetic acid	µg/L	2.5	5	EPA Method 8150
1,2,3-Trichloropropane	µg/L	5	10	EPA Method 8240
O,O,O-Triethyl phosphorothioate	µg/L	50	100	EPA Method 8270
1,3,5-Trinitrobenzene	µg/L	50	100	EPA Method 8270
Tritium	pCi/mL	1E+01	2E+01	Final DWS (CFR, 1991a)
Turbidity		No flag	No flag	Set by EPD/EMS
Uranium	µg/L	10	20	Proposed DWS (EPA, 1991)
Uranium alpha activity	pCi/L	1.5E+01	3E+01	Proposed DWS (EPA, 1991)
Uranium-233/234 ^a	pCi/L	6.9E-00	1.38E+01	Proposed DWS (EPA, 1991)
Uranium-234	pCi/L	6.95E+00	1.39E+01	Proposed DWS (EPA, 1991)
Uranium-235	pCi/L	7.25E+00	1.45E+01	Proposed DWS (EPA, 1991)
Uranium-238	pCi/L	7.3E+00	1.46E+01	Proposed DWS (EPA, 1991)
Vanadium	µg/L	50	100	EPA Method 6010
Vinyl acetate	µg/L	5	10	EPA Method 8240
Xylenes	µg/L	5,000	10,000	Final DWS (CFR, 1991a)
Zinc	µg/L	2,500	5,000	Secondary DWS (CFR, 1991b)
Zinc-65	pCi/L	1.5E+02	3E+02	Final DWS (EPA, 1977)
Zirconium-95	pCi/L	1E+02	2E+02	Final DWS (EPA, 1977)
Zirconium/Niobium-95 ^a	pCi/L	1E+02	2E+02	Final DWS (EPA, 1977)

^a For double radionuclide analyses where each separate radionuclide has its own standard, the more stringent standard is used.

References

APHA (American Public Health Association, American Water Works Association, and Water Pollution Control Federation), 1985. **Standard Methods for the Examination of Water and Wastewater**, 16th edition. Washington, DC.

CFR (Code of Federal Regulations), 1991a. *National Primary Drinking Water Regulations*, 40 CFR, Part 141, pp. 578-715. Washington, DC.

CFR (Code of Federal Regulations), 1991b. *National Secondary Drinking Water Regulations*, 40 CFR, Part 143, pp. 758-762. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1977. **National Interim Primary Drinking Water Regulations**, EPA-570/9-76-003. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1986. *Water Pollution Control; National Primary Drinking Water Regulations, Radionuclides (Proposed)*. **Federal Register**, September 30, 1986, pp. 34836-34862. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1990. *National Primary and Secondary Drinking Water Regulations; Synthetic Organic Chemicals and Inorganic Chemicals (Proposed Rule)*. **Federal Register**, July 25, 1990, pp. 30369-30448. Washington, DC.

EPA (U.S. Environmental Protection Agency), 1991. *National Primary Drinking Water Regulations; Radionuclides; Proposed Rule*. **Federal Register**, July 18, 1991, pp. 33052-33127. Washington, DC.

Appendix C – Figures

Figure 1. Location of the K-Area Acid/Caustic Basin at the Savannah River Site

Figure 2. Location of Groundwater Monitoring Wells at the K-Area Acid/Caustic Basin

Figure 3. Water-Elevation Contour Map of the Water Table at the K-Area Acid/Caustic Basin

Appendix D – Groundwater Monitoring Results Tables

Key to Reading the Tables

The following abbreviations may appear in the tabular data:

CN = Clemson Technical Center, Inc.
CS = carbon steel
D = primary drinking water standard (PDWS)
E = exponential notation (e.g., $1.1\text{E}-09 = 1.1 \times 10^{-9} = 0.0000000011$)
EM = Environmental Protection Department/Environmental Monitoring Section (EPD/EMS) Laboratory
GE = General Engineering Laboratories
GP = Environmental Physics, Inc.
H = holding time
1,2,3,4,6,7,8-HPCDD = 1,2,3,4,6,7,8-heptachlorodibenzo-p-dioxin
1,2,3,4,6,7,8-HPCDF = 1,2,3,4,6,7,8-heptachlorodibenzo-p-furan
1,2,3,4,7,8-HXCDD = 1,2,3,4,7,8-hexachlorodibenzo-p-dioxin
1,2,3,4,7,8-HXCDF = 1,2,3,4,7,8-hexachlorodibenzo-p-furan
Lindane = gamma-benzene hexachloride
mg/L = milligrams per liter
Mod = modifier
msl = mean sea level
MSL = million structures per liter
NTU = turbidity unit
PCB = polychlorinated biphenyl
1,2,3,7,8-PCDD = 1,2,3,7,8-pentachlorodibenzo-p-dioxin
1,2,3,7,8-PCDF = 1,2,3,7,8-pentachlorodibenzo-p-furan
pH = pH unit
pCi/L = picocuries per liter
pCi/mL = picocuries per milliliter
PDWS = primary drinking water standard
PVC = polyvinyl chloride
Sp. conductance = specific conductance
SP = Spencer Testing Services, Inc.
TCDD = tetrachlorodibenzo-p-dioxin
TCDF = tetrachlorodibenzo-p-furan
TM = TMA/Eberline
TOC = top of casing
WA = Roy F. Weston, Inc.
 $\mu\text{g/L}$ = micrograms per liter
 $\mu\text{S/cm}$ = microsiemens per centimeter

Holding Times

Standard analytical methods include a limit, called holding time, on the maximum elapsed time between sample collection and extraction or analysis by the laboratory. In the data tables, a large dot (●) in the H (holding time) column indicates that holding time was exceeded. Analyses performed beyond holding time may not yield valid results.

The South Carolina Department of Health and Environmental Control allows only 15 minutes to elapse between sampling and analysis for pH. Thus, only field pH measurements can meet the holding time criterion; laboratory pH analyses will always exceed it.

Laboratory-initiated procedures for reducing the number of other analyses performed out of holding time include subcontracting analyses when difficulties with equipment, personnel, or work load would prevent timely analyses. Beginning fourth quarter 1991, SRS reduced the compensation to laboratories for analyses performed out of holding time.

Data Qualification

The contract laboratories continually assess their own accuracy and precision according to U.S. Environmental Protection Agency (EPA) guidelines. They submit sample- or batch-specific quality assurance/quality control information either at the same time as analytical results or in a quarterly summary. Properly defined and used result modifiers (also referred to as qualifiers) can be a key component in assessing data useability. Result modifiers designed by EPD/EMS and provided to the primary laboratories are defined below. These modifiers appear in the data tables under the column "Mod."

<u>Result modifier</u>	<u>Definition</u>
(Blank)	Data are not qualified. Number should be interpreted exactly as reported.
A ^a	Value reported is the mean of two or more determinations.
J ^a	Value is estimated because quantitation in the sample or in associated quality control samples did not meet specifications.
L ^a	Value is off-scale high. The actual value is not known but is known to be greater than the value shown.
M ^a	Presence of the analyte is verified but not quantified.
R ^a	Result was rejected because performance requirements in the sample analysis or associated quality control analyses were not met.
T ^a	Analyte was not detected; if present, it was below the criteria for detection.
V ^a	Analyte was detected in the associated method blank.
1	Result may be an underestimation of the true value due to analytical bias.
2	Result may be an overestimation of the true value due to analytical bias.
3	The associated result may be of poor precision (high variability) due to analytical bias.
6	The associated result is from a re-analysis performed out of holding time due to problems with an earlier analysis.

^a These codes are based on the STORET codes from EPA.

Table 1. Constituents Exceeding the Primary Drinking Water Standards

<u>Well</u>	<u>Constituent</u>	<u>Unit</u>	<u>2Q92</u>	<u>3Q92</u>	<u>Mod</u>
KAC 1	Lead	µg/L	17 ^a	_ ^b	
	Lead	µg/L	17 ^a	NA ^c	

^a Duplicate/replicate samples of lead.

^b - = not above standards.

^c NA = not analyzed.

Table 2. Constituents Exceeding Half the Primary Drinking Water Standards or Other Flag 1 or Flag 2 Criteria

<u>Well</u>	<u>Constituent</u>	<u>Unit</u>	<u>3Q92</u>	<u>Mod</u>	<u>Flag</u>
KAC 1	Specific conductance ^a	µS/cm	312	J	1
	Specific conductance ^a	µS/cm	312	J	1
KAC 2	Iron	µg/L	333		2
	Specific conductance	µS/cm	348	J	1
KAC 3	Specific conductance	µS/cm	357	J	1
KAC 7	Specific conductance	µS/cm	397	J	1
KAC 8	Manganese ^b	µg/L	35		1
	Manganese ^b	µg/L	37		1
	Manganese ^b	µg/L	36		1
	Manganese ^b	µg/L	36		1
	pH	pH	8.4	J	1
	Specific conductance ^a	µS/cm	260		1
	Specific conductance ^a	µS/cm	270		1
	Specific conductance ^a	µS/cm	300		1
	Specific conductance ^a	µS/cm	290	J	1
	Specific conductance ^a	µS/cm	290	J	1
	Specific conductance ^a	µS/cm	290	J	1
KAC 9	pH	pH	9.9	J	1
	Specific conductance	µS/cm	903	J	2
	<i>Sulfate</i>	µg/L	319,000		1

Note: Constituents exceeding half the PDWS appear italicized.

^a Duplicate/replicate samples of specific conductance.

^b Duplicate/replicate samples of manganese.

Table 3. Groundwater Monitoring Results for Individual Wells

WELL KAC 1

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Formation</u>
N53167 E42614.8	33.212893 °N 81.657866 °W	229.0-199.0 ft msl	266 ft msl	4" PVC	Water table (IIB2)

FIELD MEASUREMENTS

Sample date: 08/01/92
 Depth to water: 47.41 ft (14.45 m) below TOC
 Water elevation: 218.59 ft (66.63 m) msl
 Sp. conductance: 301 μ S/cm
 Water evacuated before sampling: 51 gal

Time: 16:00
 pH: 5.7
 Alkalinity: 26 mg/L
 Water temperature: 21.8°C

LABORATORY ANALYSES

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Mod</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
•		pH	6.8	J	pH	0	WA
•		pH	6.8	J	pH	0	WA
•		Specific conductance	312	J	μ S/cm	1	WA
•		Specific conductance	312	J	μ S/cm	1	WA
•		Turbidity	3.5	J	NTU	0	WA
•		Turbidity	3.5	J	NTU	0	WA
		Arsenic	<2.0		μ g/L	0	WA
		Barium	<4.0		μ g/L	0	WA
		Cadmium	<0.35		μ g/L	0	WA
		Calcium	256		μ g/L	0	WA
		Chloride	8,110		μ g/L	0	WA
		Chloride	8,070		μ g/L	0	WA
		Chromium	<1.1		μ g/L	0	WA
		2,4-Dichlorophenoxyacetic acid	<1.1		μ g/L	0	WA
		Endrin	<0.11		μ g/L	0	WA
		Fluoride	<100		μ g/L	0	WA
		Iron	59		μ g/L	0	WA
		Lead	2.3	J3	μ g/L	0	WA
		Lindane	<0.055		μ g/L	0	WA
		Magnesium	167		μ g/L	0	WA
		Manganese	3.7		μ g/L	0	WA
		Mercury	<0.20		μ g/L	0	WA
		Mercury	<0.20		μ g/L	0	WA
		Methoxychlor	<0.55		μ g/L	0	WA
		Nitrate as nitrogen	651		μ g/L	0	WA
		Phenols	<5.0		μ g/L	0	WA
		Phenols	<5.0		μ g/L	0	WA
		Potassium	<84		μ g/L	0	WA
		Selenium	3.5	J3	μ g/L	0	WA
		Silica	4,780		μ g/L	0	WA
		Silver	<0.70		μ g/L	0	WA
		Sodium	55,200		μ g/L	0	WA
		Sulfate	94,400		μ g/L	0	WA
		Total dissolved solids	163,000		μ g/L	0	WA
		Total organic carbon	800		μ g/L	0	WA
•		Total organic halogens	20	J	μ g/L	0	WA
		Total phosphates (as P)	46		μ g/L	0	WA
		Toxaphene	<1.1		μ g/L	0	WA
		2,4,5-TP (Silvex)	<0.56		μ g/L	0	WA

• = exceeded holding time. ■ = exceeded primary drinking water standard.

WELL KAC 1 collected on 08/01/92, laboratory analyses (cont.)

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Mod</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
		Gross alpha	<2.0E+00		pCi/L	0	CN
		Nonvolatile beta	7.1E+00 ± 6.9E+00		pCi/L	0	CN
		Radium-226	1.3E+00 ± 2.6E-01		pCi/L	0	CN
		Radium-228	<1.0E+00		pCi/L	0	CN
		Tritium	9.1E-01 ± 3.2E-01		pCi/mL	0	CN

WELL KAC 2

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Formation</u>
N53255.5	33.213191 °N	225.4-195.4 ft msl	257.5 ft msl	4" PVC	Water table (IIB ₂)
E42677.2	81.657873 °W				

FIELD MEASUREMENTS

Sample date: 08/01/92
 Depth to water: 36.60 ft (11.16 m) below TOC
 Water elevation: 220.90 ft (67.33 m) msl
 Sp. conductance: 349 µS/cm
 Water evacuated before sampling: 67 gal

Time: 16:25
 pH: 6.1
 Alkalinity: 81 mg/L
 Water temperature: 22.9°C

LABORATORY ANALYSES

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Mod</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
•		pH	6.5	J	pH	0	WA
•		Specific conductance	348	J	µS/cm	1	WA
•		Turbidity	115	J	NTU	0	WA
		Arsenic	<2.0		µg/L	0	WA
		Barium	<4.0		µg/L	0	WA
		Cadmium	<0.35		µg/L	0	WA
		Calcium	600		µg/L	0	WA
		Chloride	5,290		µg/L	0	WA
		Chromium	1.6	J3	µg/L	0	WA
		2,4-Dichlorophenoxyacetic acid	<1.1		µg/L	0	WA
		Endrin	<0.11		µg/L	0	WA
		Fluoride	<100		µg/L	0	WA
		Fluoride	<100		µg/L	0	WA
		Iron	333		µg/L	2	WA
		Lead	4.1	J3	µg/L	0	WA
		Lindane	<0.056		µg/L	0	WA
		Magnesium	345		µg/L	0	WA
		Manganese	5.4		µg/L	0	WA
		Mercury	<0.20		µg/L	0	WA
		Methoxychlor	<0.56		µg/L	0	WA
		Nitrate as nitrogen	459		µg/L	0	WA
		Phenols	<5.0		µg/L	0	WA
		Potassium	<84		µg/L	0	WA
		Selenium	4.6	J3	µg/L	0	WA
		Silica	6,650		µg/L	0	WA
		Silver	<0.70		µg/L	0	WA
		Sodium	73,800		µg/L	0	WA
		Sulfate	91,400		µg/L	0	WA
		Total dissolved solids	200,000		µg/L	0	WA

• = exceeded holding time. ■ = exceeded primary drinking water standard.

WELL KAC 2 collected on 08/01/92, laboratory analyses (cont.)

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Mod</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
•		Total organic carbon	1,300		µg/L	0	WA
•		Total organic halogens	9.5	J	µg/L	0	WA
		Total phosphates (as P)	180		µg/L	0	WA
		Toxaphene	<1.1		µg/L	0	WA
		2,4,5-TP (Silvex)	<0.54		µg/L	0	WA
		Gross alpha	<2.0E+00		pCi/L	0	CN
		Nonvolatile beta	<2.0E+00		pCi/L	0	CN
		Radium-226	<1.0E+00		pCi/L	0	CN
		Radium-228	<1.0E+00		pCi/L	0	CN
		Tritium	4.4E+00 ± 4.4E-01		pCi/mL	0	CN

WELL KAC 3

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Formation</u>
N53201.8	33.213148 °N	225.8-195.8 ft msl	257.8 ft msl	4" PVC	Water table (IIB ₂)
E42723.9	81.657646 °W				

FIELD MEASUREMENTS

Sample date: 08/01/92
 Depth to water: 36.65 ft (11.17 m) below TOC
 Water elevation: 221.15 ft (67.41 m) msl
 Sp. conductance: 429 µS/cm
 Water evacuated before sampling: 67 gal

Time: 16:50
 pH: 6.3
 Alkalinity: 76 mg/L
 Water temperature: 22.7°C

LABORATORY ANALYSES

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Mod</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
•		pH	6.6	J	pH	0	WA
•		Specific conductance	357	J	µS/cm	1	WA
•		Turbidity	0.41	J	NTU	0	WA
		Arsenic	<2.0		µg/L	0	WA
		Barium	7.8	J3	µg/L	0	WA
		Cadmium	<0.35		µg/L	0	WA
		Calcium	4,270		µg/L	0	WA
		Chloride	5,980		µg/L	0	WA
		Chromium	1.3	J3	µg/L	0	WA
		2,4-Dichlorophenoxyacetic acid	<1.1		µg/L	0	WA
		Endrin	<0.11		µg/L	0	WA
		Fluoride	<100		µg/L	0	WA
		Iron	16		µg/L	0	WA
		Lead	4.0	J3	µg/L	0	WA
		Lindane	<0.055		µg/L	0	WA
		Magnesium	1,140		µg/L	0	WA
		Manganese	0.85	J3	µg/L	0	WA
		Mercury	<0.20		µg/L	0	WA
		Methoxychlor	<0.55		µg/L	0	WA
		Nitrate as nitrogen	437		µg/L	0	WA
		Phenols	<5.0		µg/L	0	WA
		Potassium	862		µg/L	0	WA
		Selenium	2.5	J3	µg/L	0	WA
		Silica	6,890		µg/L	0	WA

• = exceeded holding time. ■ = exceeded primary drinking water standard.

WELL KAC 3 collected on 08/01/92, laboratory analyses (cont.)

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Mod</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
		Silver	1.0	J3	µg/L	0	WA
		Sodium	91,400		µg/L	0	WA
		Sulfate	112,000		µg/L	0	WA
		Total dissolved solids	252,000		µg/L	0	WA
		Total organic carbon	800		µg/L	0	WA
•		Total organic halogens	16	J	µg/L	0	WA
		Total phosphates (as P)	42		µg/L	0	WA
		Toxaphene	< 1.1		µg/L	0	WA
		2,4,5-TP (Silvex)	< 0.54		µg/L	0	WA
		Gross alpha	< 2.0E+00		pCi/L	0	CN
		Nonvolatile beta	< 2.0E+00		pCi/L	0	CN
		Radium-226	< 1.0E+00		pCi/L	0	CN
		Radium-228	< 1.0E+00		pCi/L	0	CN
		Tritium	3.6E+00 ± 4.2E-01		pCi/mL	0	CN

WELL KAC 4

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Formation</u>
N53053.5	33.212743 °N	208.0-178.0 ft msl	260 ft msl	4" PVC	Water table (IIB ₂)
E42676.4	81.657484 °W				

FIELD MEASUREMENTS

Sample date: 08/01/92
 Depth to water: 42.40 ft (12.92 m) below TOC
 Water elevation: 217.60 ft (66.33 m) msl
 Sp. conductance: 71 µS/cm
 Water evacuated before sampling: 104 gal

Time: 18:00
 pH: 4.9
 Alkalinity: 1 mg/L
 Water temperature: 21.5°C

LABORATORY ANALYSES

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Mod</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
•		pH	5.9	J	pH	0	WA
•		Specific conductance	64	J	µS/cm	0	WA
•		Turbidity	2.9	J	NTU	0	WA
		Arsenic	< 2.0		µg/L	0	WA
		Barium	5.1	J3	µg/L	0	WA
		Cadmium	< 0.35		µg/L	0	WA
		Calcium	343		µg/L	0	WA
		Chloride	7,230		µg/L	0	WA
		Chromium	1.3	J3	µg/L	0	WA
		2,4-Dichlorophenoxyacetic acid	< 1.1		µg/L	0	WA
		Endrin	< 0.11		µg/L	0	WA
		Fluoride	< 100		µg/L	0	WA
		Iron	13		µg/L	0	WA
		Lead	4.3	J3	µg/L	0	WA
		Lindane	< 0.055		µg/L	0	WA
		Magnesium	418		µg/L	0	WA
		Manganese	3.2		µg/L	0	WA
		Mercury	< 0.20		µg/L	0	WA
		Methoxychlor	< 0.55		µg/L	0	WA
		Nitrate as nitrogen	205		µg/L	0	WA

• = exceeded holding time. ■ = exceeded primary drinking water standard.

WELL KAC 4 collected on 08/01/92, laboratory analyses (cont.)

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Mod</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
		Phenols	< 5.0		µg/L	0	WA
		Potassium	< 84		µg/L	0	WA
		Selenium	< 2.0		µg/L	0	WA
		Silica	6,040		µg/L	0	WA
		Silver	< 0.70		µg/L	0	WA
		Sodium	10,800		µg/L	0	WA
		Sulfate	9,690		µg/L	0	WA
		Total dissolved solids	23,000		µg/L	0	WA
		Total organic carbon	900		µg/L	0	WA
•		Total organic halogens	15	J	µg/L	0	WA
		Total phosphates (as P)	46		µg/L	0	WA
		Toxaphene	< 1.1		µg/L	0	WA
		2,4,5-TP (Silvex)	< 0.55		µg/L	0	WA
		Gross alpha	< 2.0E+00		pCi/L	0	CN
		Gross alpha	< 2.0E+00		pCi/L	0	CN
		Radium-226	< 1.0E+00		pCi/L	0	CN
		Radium-228	< 1.0E+00		pCi/L	0	CN
		Tritium	1.4E+00 ± 3.4E-01		pCi/mL	0	CN
		Nonvolatile beta	< 2.0E+00		pCi/L	0	CN
		Nonvolatile beta	< 2.0E+00		pCi/L	0	CN

• = exceeded holding time. ■ = exceeded primary drinking water standard.

WELL KAC 5

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Formation</u>
N53161.7 E42716.3	33.213047 °N 81.657589 °W	224.3-204.3 ft msl	259 ft msl	4" PVC	Water table (IIB ₂)

FIELD MEASUREMENTS

Sample date: 08/01/92	Time: 17:25
Depth to water: 38.05 ft (11.60 m) below TOC	pH: 5.1
Water elevation: 220.95 ft (67.35 m) msl	Alkalinity: 3 mg/L
Sp. conductance: 73 µS/cm	Water temperature: 21.8°C
Water evacuated before sampling: 44 gal	

LABORATORY ANALYSES

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Mod</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
•		pH	5.8	J	pH	0	WA
•		Specific conductance	61	J	µS/cm	0	WA
•		Turbidity	0.20	J	NTU	0	WA
		Arsenic	<2.0		µg/L	0	WA
		Barium	<4.0		µg/L	0	WA
		Cadmium	<0.35		µg/L	0	WA
		Calcium	398		µg/L	0	WA
		Chloride	6,430		µg/L	0	WA
		Chromium	<1.1		µg/L	0	WA
		2,4-Dichlorophenoxyacetic acid	<1.1		µg/L	0	WA
		Endrin	<0.11		µg/L	0	WA
		Fluoride	<100		µg/L	0	WA
		Iron	68		µg/L	0	WA
		Lead	3.4	J3	µg/L	0	WA
		Lindane	<0.055		µg/L	0	WA
		Magnesium	225		µg/L	0	WA
		Manganese	4.9		µg/L	0	WA
		Mercury	<0.20		µg/L	0	WA
		Methoxychlor	<0.55		µg/L	0	WA
		Nitrate as nitrogen	136		µg/L	0	WA
		Phenols	<5.0		µg/L	0	WA
		Potassium	313	J3	µg/L	0	WA
		Selenium	<2.0		µg/L	0	WA
		Silica	6,250		µg/L	0	WA
		Silver	2.1	J3	µg/L	0	WA
		Sodium	10,700		µg/L	0	WA
		Sulfate	8,880		µg/L	0	WA
		Total dissolved solids	22,000		µg/L	0	WA
		Total organic carbon	700		µg/L	0	WA
•		Total organic halogens	11	J	µg/L	0	WA
		Total phosphates (as P)	39		µg/L	0	WA
		Toxaphene	<1.1		µg/L	0	WA
		2,4,5-TP (Silvex)	<0.56		µg/L	0	WA
		Gross alpha	<2.0E+00		pCi/L	0	CN
		Nonvolatile beta	<2.0E+00		pCi/L	0	CN
		Radium-226	<1.0E+00		pCi/L	0	CN
		Radium-228	<1.0E+00		pCi/L	0	CN
		Tritium	7.5E-01 ± 3.2E-01		pCi/mL	0	CN

• = exceeded holding time. ■ = exceeded primary drinking water standard.

WELL KAC 6

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Formation</u>
N53139.9 E42693.5	33.212962 °N 81.657606 °W	224.6-204.6 ft msl	259 ft msl	4" PVC	Water table (IIB ₂)

FIELD MEASUREMENTS

Sample date: 08/02/92
 Depth to water: 38.09 ft (11.61 m) below TOC
 Water elevation: 220.91 ft (67.33 m) msl
 Sp. conductance: 87 μ S/cm
 Water evacuated before sampling: 8 gal
 The well went dry during purging.

Time: 8:30
 pH: 5.2
 Alkalinity: 2 mg/L
 Water temperature: 21.5°C

LABORATORY ANALYSES

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Mod</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
•		pH	5.6	J	pH	0	WA
•		Specific conductance	82	J	μ S/cm	0	WA
•		Turbidity	25	J	NTU	0	WA
		Arsenic	<2.0		μ g/L	0	WA
		Barium	5.3	J3	μ g/L	0	WA
		Cadmium	<0.35		μ g/L	0	WA
		Calcium	318		μ g/L	0	WA
		Chloride	6,570		μ g/L	0	WA
		Chromium	1.3	J3	μ g/L	0	WA
		2,4-Dichlorophenoxyacetic acid	<1.1		μ g/L	0	WA
		Endrin	<0.11		μ g/L	0	WA
		Fluoride	<100		μ g/L	0	WA
		Iron	103		μ g/L	0	WA
		Lead	5.3	J3	μ g/L	0	WA
		Lindane	<0.055		μ g/L	0	WA
		Magnesium	269		μ g/L	0	WA
		Manganese	6.0		μ g/L	0	WA
		Mercury	<0.20		μ g/L	0	WA
		Methoxychlor	<0.55		μ g/L	0	WA
		Nitrate as nitrogen	131		μ g/L	0	WA
		Phenols	<5.0		μ g/L	0	WA
		Potassium	336	J3	μ g/L	0	WA
		Selenium	<2.0		μ g/L	0	WA
		Silica	6,680		μ g/L	0	WA
		Silver	1.8	J3	μ g/L	0	WA
		Sodium	14,200		μ g/L	0	WA
		Sulfate	19,500		μ g/L	0	WA
		Total dissolved solids	40,000		μ g/L	0	WA
		Total dissolved solids	45,000		μ g/L	0	WA
		Total organic carbon	<500		μ g/L	0	WA
•		Total organic halogens	16	J	μ g/L	0	WA
		Total phosphates (as P)	67		μ g/L	0	WA
		Toxaphene	<1.1		μ g/L	0	WA
		2,4,5-TP (Silvex)	<0.55		μ g/L	0	WA
		Gross alpha	<2.0E+00		pCi/L	0	CN
		Nonvolatile beta	<2.0E+00		pCi/L	0	CN
		Radium-226	<1.0E+00		pCi/L	0	CN
		Radium-228	<1.0E+00		pCi/L	0	CN
		Tritium	7.2E-01 $\pm$ 3.1E-01		pCi/mL	0	CN

• = exceeded holding time. ■ = exceeded primary drinking water standard.

WELL KAC 7

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Formation</u>
N53252.9 E42574.5	33.213018 °N 81.658139 °W	223.0-203.0 ft msl	265.1 ft msl	4" PVC	Water table (IIB ₂)

FIELD MEASUREMENTS

Sample date: 08/02/92
 Depth to water: 46.26 ft (14.10 m) below TOC
 Water elevation: 218.84 ft (66.70 m) msl
 Sp. conductance: 205 μ S/cm
 Water evacuated before sampling: 6 gal
 The well went dry during purging.

Time: 8:05
 pH: 5.8
 Alkalinity: 26 mg/L
 Water temperature: 21.5°C

LABORATORY ANALYSES

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Mod</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
•		pH	5.8	J	pH	0	WA
•		Specific conductance	397	J	μ S/cm	1	WA
•		Turbidity	39	J	NTU	0	WA
		Arsenic	<2.0		μ g/L	0	WA
		Barium	4.2	J3	μ g/L	0	WA
		Cadmium	<0.35		μ g/L	0	WA
		Calcium	1,850		μ g/L	0	WA
		Chloride	8,590		μ g/L	0	WA
		Chromium	<1.1		μ g/L	0	WA
		2,4-Dichlorophenoxyacetic acid	<1.1		μ g/L	0	WA
		Endrin	<0.11		μ g/L	0	WA
		Fluoride	<100		μ g/L	0	WA
		Iron	63		μ g/L	0	WA
		Lead	3.5	J3	μ g/L	0	WA
		Lindane	<0.055		μ g/L	0	WA
		Magnesium	85		μ g/L	0	WA
		Manganese	3.7		μ g/L	0	WA
		Mercury	<0.20		μ g/L	0	WA
		Methoxychlor	<0.55		μ g/L	0	WA
		Nitrate as nitrogen	887		μ g/L	0	WA
		Phenols	<5.0		μ g/L	0	WA
		Potassium	<84		μ g/L	0	WA
		Selenium	<2.0		μ g/L	0	WA
		Silica	4,790		μ g/L	0	WA
		Silver	<0.70		μ g/L	0	WA
		Sodium	34,700		μ g/L	0	WA
		Sulfate	125,000		μ g/L	0	WA
		Total dissolved solids	214,000		μ g/L	0	WA
		Total organic carbon	700		μ g/L	0	WA
•		Total organic halogens	17	J	μ g/L	0	WA
		Total phosphates (as P)	67		μ g/L	0	WA
		Toxaphene	<1.1		μ g/L	0	WA
		2,4,5-TP (Silvex)	<0.54		μ g/L	0	WA
		Gross alpha	<2.0E+00		pCi/L	0	CN
		Nonvolatile beta	<2.0E+00		pCi/L	0	CN
		Radium-226	<1.0E+00		pCi/L	0	CN
		Radium-228	<1.0E+00		pCi/L	0	CN
		Tritium	4.6E+00 $\pm$ 4.5E-01		pCi/mL	0	CN

• = exceeded holding time. ■ = exceeded primary drinking water standard.

WELL KAC 8

SRS Coord.	Lat/Longitude	Screen Zone Elevation	Top of Casing	Casing	Formation
N53136 E42641.9	33.212869 °N 81.657734 °W	217.1-197.1 ft msl	267.1 ft msl	4" PVC	Water table (IIB ₂)

FIELD MEASUREMENTS

Sample date: 08/02/92
 Depth to water: 43.47 ft (13.25 m) below TOC
 Water elevation: 223.63 ft (68.16 m) msl
 Sp. conductance: 298 µS/cm
 Water evacuated before sampling: 71 gal

Time: 9:15
 pH: 5.5
 Alkalinity: 9 mg/L
 Water temperature: 21.9°C

LABORATORY ANALYSES

H	D	Analyte	Result	Mod	Unit	Flag	Lab
•		pH	6.0	J	pH	0	GE
•		pH	6.1	J	pH	0	GE
•		pH	6.2	J	pH	0	GE
•		pH	6.2	J	pH	0	WA
•		pH	6.2	J	pH	0	WA
•		pH	8.4	J	pH	1	WA
		Specific conductance	260		µS/cm	1	GE
		Specific conductance	270		µS/cm	1	GE
		Specific conductance	300		µS/cm	1	GE
•		Specific conductance	290	J	µS/cm	1	WA
•		Specific conductance	290	J	µS/cm	1	WA
•		Specific conductance	290	J	µS/cm	1	WA
		Turbidity	1.7		NTU	0	GE
		Turbidity	2.6		NTU	0	GE
•		Turbidity	0.76	J	NTU	0	WA
•		Turbidity	0.76	J	NTU	0	WA
•		Turbidity	1.5	J	NTU	0	WA
		Arsenic	<2.0		µg/L	0	GE
		Arsenic	<2.0		µg/L	0	GE
		Arsenic	<2.0		µg/L	0	WA
		Arsenic	<2.0		µg/L	0	WA
		Barium	16		µg/L	0	GE
		Barium	17		µg/L	0	GE
		Barium	24	J3	µg/L	0	WA
		Barium	17	J3	µg/L	0	WA
		Benzene	<1.0		µg/L	0	GE
		Benzene	<1.0		µg/L	0	GE
		Benzene	<5.0		µg/L	0	WA
		Benzene	<5.0		µg/L	0	WA
		Bromodichloromethane	<1.0		µg/L	0	GE
		Bromodichloromethane	<1.0		µg/L	0	GE
		Bromodichloromethane	<5.0		µg/L	0	WA
		Bromodichloromethane	<5.0		µg/L	0	WA
		Bromoform	<1.0		µg/L	0	GE
		Bromoform	<1.0		µg/L	0	GE
		Bromoform	<5.0		µg/L	0	WA
		Bromoform	<5.0		µg/L	0	WA
		Bromomethane (Methyl bromide)	<1.0		µg/L	0	GE
		Bromomethane (Methyl bromide)	<1.0		µg/L	0	GE

• = exceeded holding time. ■ = exceeded primary drinking water standard.

WELL KAC 8 collected on 08/02/92, laboratory analyses (cont.)

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Mod</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
		Bromomethane (Methyl bromide)	< 10		µg/L	0	WA
		Bromomethane (Methyl bromide)	< 10		µg/L	0	WA
		Cadmium	< 2.0		µg/L	0	GE
		Cadmium	< 2.0		µg/L	0	GE
		Cadmium	< 0.35		µg/L	0	WA
		Cadmium	< 0.35		µg/L	0	WA
		Calcium	1,690		µg/L	0	GE
		Calcium	1,810		µg/L	0	GE
		Calcium	1,750		µg/L	0	WA
		Calcium	2,030		µg/L	0	WA
		Carbon tetrachloride	< 1.0		µg/L	0	GE
		Carbon tetrachloride	< 1.0		µg/L	0	GE
		Carbon tetrachloride	< 5.0		µg/L	0	WA
		Carbon tetrachloride	< 5.0		µg/L	0	WA
		Chloride	8,600		µg/L	0	GE
		Chloride	8,800		µg/L	0	GE
		Chloride	8,740		µg/L	0	WA
		Chloride	8,910		µg/L	0	WA
		Chlorobenzene	< 1.0		µg/L	0	GE
		Chlorobenzene	< 1.0		µg/L	0	GE
		Chlorobenzene	< 5.0		µg/L	0	WA
		Chlorobenzene	< 5.0		µg/L	0	WA
		Chloroethane	< 1.0		µg/L	0	GE
		Chloroethane	< 1.0		µg/L	0	GE
		Chloroethane	< 10		µg/L	0	WA
		Chloroethane	< 10		µg/L	0	WA
		Chloroethene (Vinyl chloride)	< 1.0		µg/L	0	GE
		Chloroethene (Vinyl chloride)	< 1.0		µg/L	0	GE
		Chloroethene (Vinyl chloride)	< 10		µg/L	0	WA
		Chloroethene (Vinyl chloride)	< 10		µg/L	0	WA
		2-Chloroethyl vinyl ether	< 1.0		µg/L	0	GE
		2-Chloroethyl vinyl ether	< 1.0		µg/L	0	GE
		2-Chloroethyl vinyl ether	< 10		µg/L	0	WA
		2-Chloroethyl vinyl ether	< 10		µg/L	0	WA
		Chloroform	2.3		µg/L	0	GE
		Chloroform	2.3		µg/L	0	GE
		Chloroform	2.2	J	µg/L	0	WA
		Chloroform	2.2	J	µg/L	0	WA
		Chloromethane (Methyl chloride)	< 1.0		µg/L	0	GE
		Chloromethane (Methyl chloride)	< 1.0		µg/L	0	GE
		Chloromethane (Methyl chloride)	< 10		µg/L	0	WA
		Chloromethane (Methyl chloride)	< 10		µg/L	0	WA
		Chromium	< 4.0		µg/L	0	GE
		Chromium	< 4.0		µg/L	0	GE
		Chromium	1.7	J3	µg/L	0	WA
		Chromium	< 1.1		µg/L	0	WA
		Dibromochloromethane	< 1.0		µg/L	0	GE
		Dibromochloromethane	< 1.0		µg/L	0	GE
		Dibromochloromethane	< 5.0		µg/L	0	WA
		Dibromochloromethane	< 5.0		µg/L	0	WA
		1,1-Dichloroethane	< 1.0		µg/L	0	GE
		1,1-Dichloroethane	< 1.0		µg/L	0	GE
		1,1-Dichloroethane	< 5.0		µg/L	0	WA
		1,1-Dichloroethane	< 5.0		µg/L	0	WA
		1,2-Dichloroethane	< 1.0		µg/L	0	GE
		1,2-Dichloroethane	< 1.0		µg/L	0	GE
		1,2-Dichloroethane	< 5.0		µg/L	0	WA

● = exceeded holding time. ■ = exceeded primary drinking water standard.

WELL KAC 8 collected on 08/02/92, laboratory analyses (cont.)

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Mod</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
		1,2-Dichloroethane	<5.0		µg/L	0	WA
		1,1-Dichloroethylene	<1.0		µg/L	0	GE
		1,1-Dichloroethylene	<1.0		µg/L	0	GE
		1,1-Dichloroethylene	<5.0		µg/L	0	WA
		1,1-Dichloroethylene	<5.0		µg/L	0	WA
		trans-1,2-Dichloroethylene	<1.0		µg/L	0	GE
		trans-1,2-Dichloroethylene	<1.0		µg/L	0	GE
		trans-1,2-Dichloroethylene	<5.0		µg/L	0	WA
		trans-1,2-Dichloroethylene	<5.0		µg/L	0	WA
		Dichloromethane (Methylene chloride)	1.4		µg/L	0	GE
		Dichloromethane (Methylene chloride)	1.9		µg/L	0	GE
		Dichloromethane (Methylene chloride)	5.0	V	µg/L	0	WA
		Dichloromethane (Methylene chloride)	1.1	JV	µg/L	0	WA
		2,4-Dichlorophenoxyacetic acid	<0.30		µg/L	0	GE
		2,4-Dichlorophenoxyacetic acid	<0.30		µg/L	0	GE
•		2,4-Dichlorophenoxyacetic acid	<1.1	J	µg/L	0	WA
•		2,4-Dichlorophenoxyacetic acid	<1.1	J	µg/L	0	WA
		1,2-Dichloropropane	<1.0		µg/L	0	GE
		1,2-Dichloropropane	<1.0		µg/L	0	GE
		1,2-Dichloropropane	<5.0		µg/L	0	WA
		1,2-Dichloropropane	<5.0		µg/L	0	WA
		cis-1,3-Dichloropropene	<1.0		µg/L	0	GE
		cis-1,3-Dichloropropene	<1.0		µg/L	0	GE
		cis-1,3-Dichloropropene	<5.0		µg/L	0	WA
		cis-1,3-Dichloropropene	<5.0		µg/L	0	WA
		trans-1,3-Dichloropropene	<1.0		µg/L	0	GE
		trans-1,3-Dichloropropene	<1.0		µg/L	0	GE
		trans-1,3-Dichloropropene	<5.0		µg/L	0	WA
		trans-1,3-Dichloropropene	<5.0		µg/L	0	WA
		Endrin	<0.0060		µg/L	0	GE
		Endrin	<0.0060		µg/L	0	GE
		Endrin	<0.11		µg/L	0	WA
		Endrin	<0.23		µg/L	0	WA
		Endrin	<0.11		µg/L	0	WA
		Ethylbenzene	<1.0		µg/L	0	GE
		Ethylbenzene	<1.0		µg/L	0	GE
		Ethylbenzene	<5.0		µg/L	0	WA
		Ethylbenzene	<5.0		µg/L	0	WA
		Fluoride	<100		µg/L	0	GE
		Fluoride	<100		µg/L	0	GE
		Fluoride	<100		µg/L	0	WA
		Fluoride	<100		µg/L	0	WA
		Iron	117		µg/L	0	GE
		Iron	124		µg/L	0	GE
		Iron	125		µg/L	0	GE
		Iron	124		µg/L	0	GE
		Iron	132		µg/L	0	WA
		Iron	129		µg/L	0	WA
		Iron	132		µg/L	0	WA
		Iron	133		µg/L	0	WA
		Lead	<3.0		µg/L	0	GE
		Lead	<3.0		µg/L	0	GE
		Lead	5.4	J3	µg/L	0	WA
		Lead	<2.0		µg/L	0	WA
		Lindane	<0.0050		µg/L	0	GE
		Lindane	<0.0050		µg/L	0	GE
		Lindane	<0.056		µg/L	0	WA

• = exceeded holding time. ■ = exceeded primary drinking water standard.

WELL KAC 8 collected on 08/02/92, laboratory analyses (cont.)

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Mod</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
		Lindane	<0.11		µg/L	0	WA
		Lindane	<0.056		µg/L	0	WA
		Magnesium	743		µg/L	0	GE
		Magnesium	773		µg/L	0	GE
		Magnesium	783		µg/L	0	WA
		Magnesium	738		µg/L	0	WA
		Manganese	35		µg/L	1	GE
		Manganese	37		µg/L	1	GE
		Manganese	36		µg/L	1	WA
		Manganese	36		µg/L	1	WA
		Mercury	<0.20		µg/L	0	GE
		Mercury	<0.20		µg/L	0	GE
		Mercury	<0.20		µg/L	0	WA
		Mercury	<0.20		µg/L	0	WA
		Methoxychlor	<0.50		µg/L	0	GE
		Methoxychlor	<0.50		µg/L	0	GE
		Methoxychlor	<0.56		µg/L	0	WA
		Methoxychlor	<1.1		µg/L	0	WA
		Methoxychlor	<1.1		µg/L	0	WA
		Methoxychlor	<0.56		µg/L	0	WA
		Nitrate as nitrogen	525		µg/L	0	WA
		Nitrate as nitrogen	391		µg/L	0	WA
		Nitrate-nitrite as nitrogen	270		µg/L	0	GE
		Nitrate-nitrite as nitrogen	270		µg/L	0	GE
		Nitrate-nitrite as nitrogen	270		µg/L	0	GE
		Phenols	<5.0		µg/L	0	GE
		Phenols	<5.0		µg/L	0	GE
		Phenols	<5.0		µg/L	0	GE
		Phenols	<5.0		µg/L	0	WA
		Phenols	<5.0		µg/L	0	WA
		Phenols	<5.0		µg/L	0	WA
		Potassium	<500		µg/L	0	GE
		Potassium	<500		µg/L	0	GE
		Potassium	947		µg/L	0	WA
		Potassium	583	J3	µg/L	0	WA
		Selenium	<2.0	J1	µg/L	0	GE
		Selenium	<2.0	J1	µg/L	0	GE
		Selenium	<2.0		µg/L	0	WA
		Selenium	<2.0		µg/L	0	WA
		Silica	6,740		µg/L	0	GE
		Silica	7,040		µg/L	0	GE
		Silica	6,660		µg/L	0	WA
		Silica	6,500		µg/L	0	WA
		Silver	<2.0		µg/L	0	GE
		Silver	<2.0		µg/L	0	GE
		Silver	1.7	J3	µg/L	0	WA
		Silver	<0.70		µg/L	0	WA
		Sodium	52,400		µg/L	0	GE
		Sodium	54,300		µg/L	0	GE
		Sodium	49,300		µg/L	0	WA
		Sodium	53,100		µg/L	0	WA
		Sulfate	103,000		µg/L	0	GE
		Sulfate	95,500		µg/L	0	GE
		Sulfate	100,000		µg/L	0	WA
		Sulfate	109,000		µg/L	0	WA
		1,1,2,2-Tetrachloroethane	<1.0		µg/L	0	GE

● = exceeded holding time. ■ = exceeded primary drinking water standard.

WELL KAC 8 collected on 08/02/92, laboratory analyses (cont.)

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Mod</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
		1,1,2,2-Tetrachloroethane	< 1.0		µg/L	0	GE
		1,1,2,2-Tetrachloroethane	< 5.0		µg/L	0	WA
		1,1,2,2-Tetrachloroethane	< 5.0		µg/L	0	WA
		Tetrachloroethylene	< 1.0		µg/L	0	GE
		Tetrachloroethylene	< 1.0		µg/L	0	GE
		Tetrachloroethylene	< 5.0		µg/L	0	WA
		Tetrachloroethylene	< 5.0		µg/L	0	WA
		Toluene	< 1.0		µg/L	0	GE
		Toluene	< 1.0		µg/L	0	GE
		Toluene	< 5.0		µg/L	0	WA
		Toluene	< 5.0		µg/L	0	WA
		Total dissolved solids	168,000	V	µg/L	0	GE
		Total dissolved solids	176,000	V	µg/L	0	GE
		Total dissolved solids	160,000		µg/L	0	WA
		Total dissolved solids	182,000		µg/L	0	WA
		Total dissolved solids	176,000		µg/L	0	WA
		Total organic carbon	< 1,000		µg/L	0	GE
		Total organic carbon	< 1,000		µg/L	0	GE
		Total organic carbon	< 1,000		µg/L	0	GE
		Total organic carbon	696		µg/L	0	WA
		Total organic carbon	605		µg/L	0	WA
		Total organic halogens	5.2		µg/L	0	GE
		Total organic halogens	< 5.0		µg/L	0	GE
•		Total organic halogens	< 5.0	J	µg/L	0	WA
•		Total organic halogens	< 5.0	J	µg/L	0	WA
		Total phosphates (as P)	2,000		µg/L	0	GE
		Total phosphates (as P)	< 50		µg/L	0	GE
		Total phosphates (as P)	34		µg/L	0	WA
		Total phosphates (as P)	64		µg/L	0	WA
		Toxaphene	< 0.24		µg/L	0	GE
		Toxaphene	< 0.24		µg/L	0	GE
		Toxaphene	< 1.1		µg/L	0	WA
		Toxaphene	< 2.3		µg/L	0	WA
		Toxaphene	< 2.3		µg/L	0	WA
		Toxaphene	< 1.1		µg/L	0	WA
		2,4,5-TP (Silvex)	< 0.090		µg/L	0	GE
		2,4,5-TP (Silvex)	< 0.090		µg/L	0	GE
•		2,4,5-TP (Silvex)	< 0.56	J	µg/L	0	WA
•		2,4,5-TP (Silvex)	< 0.55	J	µg/L	0	WA
		1,1,1-Trichloroethane	< 1.0		µg/L	0	GE
		1,1,1-Trichloroethane	< 1.0		µg/L	0	GE
		1,1,1-Trichloroethane	< 5.0		µg/L	0	WA
		1,1,1-Trichloroethane	< 5.0		µg/L	0	WA
		1,1,2-Trichloroethane	< 1.0		µg/L	0	GE
		1,1,2-Trichloroethane	< 1.0		µg/L	0	GE
		1,1,2-Trichloroethane	< 5.0		µg/L	0	WA
		1,1,2-Trichloroethane	< 5.0		µg/L	0	WA
		Trichloroethylene	< 1.0		µg/L	0	GE
		Trichloroethylene	< 1.0		µg/L	0	GE
		Trichloroethylene	< 5.0		µg/L	0	WA
		Trichloroethylene	< 5.0		µg/L	0	WA
		Trichlorofluoromethane	< 1.0		µg/L	0	GE
		Trichlorofluoromethane	< 1.0		µg/L	0	GE
		Trichlorofluoromethane	< 5.0		µg/L	0	WA
		Trichlorofluoromethane	< 5.0		µg/L	0	WA
		Gross alpha	< 2.0E+ 00		pCi/L	0	GP

• = exceeded holding time. ■ = exceeded primary drinking water standard.

WELL KAC 8 collected on 08/02/92, laboratory analyses (cont.)

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Mod</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
		Gross alpha	3.5E+00 ± 2.1E+00		pCi/L	0	GP
		Gross alpha	<2.0E+00		pCi/L	0	CN
		Gross alpha	2.1E+00 ± 2.2E+00		pCi/L	0	CN
		Nonvolatile beta	3.2E+00 ± 1.6E+00		pCi/L	0	GP
		Nonvolatile beta	3.3E+00 ± 1.6E+00		pCi/L	0	GP
		Nonvolatile beta	<2.0E+00		pCi/L	0	CN
		Nonvolatile beta	<2.0E+00		pCi/L	0	CN
		Radium-226	<1.0E+00		pCi/L	0	GP
		Radium-226	1.7E+00 ± 2.7E-01		pCi/L	0	GP
		Radium-226	<1.0E+00		pCi/L	0	CN
		Radium-226	<1.0E+00		pCi/L	0	CN
		Radium-226	<1.0E+00		pCi/L	0	CN
		Radium-228	1.9E+00 ± 8.8E-01		pCi/L	0	CN
		Radium-228	<1.0E+00		pCi/L	0	CN
		Radium-228	<1.0E+00		pCi/L	0	TE
		Radium-228	2.1E+00 ± 1.0E+00		pCi/L	0	TE
		Total activity	2.5E+03 ± 1.2E+03		pCi/L	0	EM
		Total activity	2.4E+03 ± 1.2E+03		pCi/L	0	EM
		Tritium	1.7E+00 ± 5.0E-01		pCi/mL	0	GP
		Tritium	1.6E+00 ± 5.0E-01		pCi/mL	0	GP
		Tritium	<7.0E-01		pCi/mL	0	CN
		Tritium	<7.0E-01		pCi/mL	0	CN

WELL KAC 9

<u>SRS Coord.</u>	<u>Lat/Longitude</u>	<u>Screen Zone Elevation</u>	<u>Top of Casing</u>	<u>Casing</u>	<u>Formation</u>
N53197.8	33.212918 °N	210.9-190.9 ft msl	262.2 ft msl	4" PVC	Water table (IIB ₂)
E42588.1	81.657996 °W				

FIELD MEASUREMENTS

Sample date: 08/02/92
 Depth to water: 48.47 ft (14.77 m) below TOC
 Water elevation: 213.73 ft (65.15 m) msl
 Sp. conductance: 930 µS/cm
 Water evacuated before sampling: 61 gal

Time: 10:30
 pH: 10.4
 Alkalinity: 126 mg/L
 Water temperature: 21.7°C

LABORATORY ANALYSES

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Mod</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
•		pH	9.9	J	pH	1	WA
•		Specific conductance	903	J	µS/cm	2	WA
•		Turbidity	0.65	J	NTU	0	WA
		Arsenic	5.4	J3	µg/L	0	WA
		Barium	17	J3	µg/L	0	WA
		Benzene	<5.0		µg/L	0	WA
		Bromodichloromethane	<5.0		µg/L	0	WA
		Bromoform	<5.0		µg/L	0	WA
		Bromomethane (Methyl bromide)	<10		µg/L	0	WA
		Cadmium	<0.35		µg/L	0	WA
		Calcium	23,900		µg/L	0	WA
		Carbon tetrachloride	<5.0		µg/L	0	WA

• = exceeded holding time. ■ = exceeded primary drinking water standard.

WELL KAC 9 collected on 08/02/92, laboratory analyses (cont.)

H	D	Analyte	Result	Mod	Unit	Flag	Lab
		Chloride	22,600		µg/L	0	WA
		Chlorobenzene	< 5.0		µg/L	0	WA
		Chloroethane	< 10		µg/L	0	WA
		Chloroethene (Vinyl chloride)	< 10		µg/L	0	WA
		2-Chloroethyl vinyl ether	< 10		µg/L	0	WA
		Chloroform	2.6	J	µg/L	0	WA
		Chloromethane (Methyl chloride)	< 10		µg/L	0	WA
		Chromium	13		µg/L	0	WA
		Dibromochloromethane	< 5.0		µg/L	0	WA
		1,1-Dichloroethane	< 5.0		µg/L	0	WA
		1,2-Dichloroethane	< 5.0		µg/L	0	WA
		1,1-Dichloroethylene	< 5.0		µg/L	0	WA
		trans-1,2-Dichloroethylene	< 5.0		µg/L	0	WA
		Dichloromethane (Methylene chloride)	< 5.0		µg/L	0	WA
•		2,4-Dichlorophenoxyacetic acid	< 1.1	J	µg/L	0	WA
•		2,4-Dichlorophenoxyacetic acid	< 2.1	J	µg/L	0	WA
		1,2-Dichloropropane	< 5.0		µg/L	0	WA
		cis-1,3-Dichloropropene	< 5.0		µg/L	0	WA
		trans-1,3-Dichloropropene	< 5.0		µg/L	0	WA
		Endrin	< 0.11		µg/L	0	WA
		Ethylbenzene	< 5.0		µg/L	0	WA
		Fluoride	229		µg/L	0	WA
		Fluoride	228		µg/L	0	WA
		Iron	19		µg/L	0	WA
		Lead	< 2.0		µg/L	0	WA
		Lindane	< 0.055		µg/L	0	WA
		Magnesium	907		µg/L	0	WA
		Manganese	3.5		µg/L	0	WA
		Mercury	< 0.20		µg/L	0	WA
		Methoxychlor	< 0.55		µg/L	0	WA
		Nitrate as nitrogen	1,030		µg/L	0	WA
		Phenols	< 5.0		µg/L	0	WA
		Potassium	1,910		µg/L	0	WA
		Selenium	2.2	J3	µg/L	0	WA
		Silica	10,600		µg/L	0	WA
		Silver	< 0.70		µg/L	0	WA
		Sodium	158,000		µg/L	0	WA
		Sulfate	319,000		µg/L	1	WA
		1,1,2,2-Tetrachloroethane	< 5.0		µg/L	0	WA
		Tetrachloroethylene	< 5.0		µg/L	0	WA
		Toluene	2.6	J	µg/L	0	WA
		Total dissolved solids	610,000		µg/L	0	WA
		Total organic carbon	1,240		µg/L	0	WA
•		Total organic halogens	< 5.0	J	µg/L	0	WA
		Total phosphates (as P)	94		µg/L	0	WA
		Toxaphene	< 1.1		µg/L	0	WA
•		2,4,5-TP (Silvex)	< 0.55	J	µg/L	0	WA
•		2,4,5-TP (Silvex)	< 1.1	J	µg/L	0	WA
		1,1,1-Trichloroethane	< 5.0		µg/L	0	WA
		1,1,2-Trichloroethane	< 5.0		µg/L	0	WA
		Trichloroethylene	< 5.0		µg/L	0	WA
		Trichlorofluoromethane	< 5.0		µg/L	0	WA
		Gross alpha	< 2.0		pCi/L	0	CN
		Nonvolatile beta	< 2.0		pCi/L	0	CN
		Radium-226	< 1.0E+00		pCi/L	0	CN
		Radium-228	< 1.0E+00		pCi/L	0	CN

• = exceeded holding time. ■ = exceeded primary drinking water standard.

WELL KAC 9 collected on 08/02/92, laboratory analyses (cont.)

<u>H</u>	<u>D</u>	<u>Analyte</u>	<u>Result</u>	<u>Mod</u>	<u>Unit</u>	<u>Flag</u>	<u>Lab</u>
		Total activity	5.7E+03 ± 1.3E+03		pCi/L	0	EM
		Tritium	2.1E+00 ± 3.7E-01		pCi/mL	0	CN

● = exceeded holding time. ■ = exceeded primary drinking water standard.

Appendix E – Data Quality/Useability Assessment

Data Quality/Useability Assessment

Quality assurance/quality control (QA/QC) procedures relating to accuracy and precision of analyses performed on groundwater samples are followed in the field and laboratory and are reviewed prior to publication of results. The Environmental Protection Department/Environmental Monitoring Section's (EPD/EMS) review of the volume of analytical data acquired each quarter and presented in various reports is an ongoing process; its review of the QA/QC data cannot be completed in time to meet the deadlines for the reports required by the Resource Conservation and Recovery Act and associated regulations. Other site and regulatory personnel can obtain further information on the data quality and useability in a variety of ways.

Data Qualification

The contract laboratories continually assess their own accuracy and precision according to U.S. Environmental Protection Agency (EPA) guidelines. They submit sample- or batch-specific QA/QC information either at the same time as analytical results or in a quarterly summary. Properly defined and used result modifiers (also referred to as qualifiers) can be a key component in assessing data useability. Result modifiers designed by EPD/EMS and provided to the primary laboratories are presented in Appendix D.

Assessment of Accuracy of the Data

Accuracy, or the nearness of the reported result to the true concentration of a constituent in a sample, can be assessed in several ways.

A laboratory's general accuracy can be judged by analysis of results obtained from known samples. The non-radionuclide contract laboratories analyze commercial reference samples every quarter at EPD/EMS' request. The results of these analyses are presented in the EPD/EMS quarterly report, *The Savannah River Site's Groundwater Monitoring Program*. The primary laboratories also seek or maintain state certification by participating periodically in performance studies; reference samples and analysis of results are provided by EPA. Results of these studies also are published in the EPD/EMS quarterly reports.

Analysis of blanks provides a tool for assessing the accuracy of both sampling and laboratory analysis. Results for all field blanks for the quarter can be found in the EPD/EMS quarterly reports. Any field or laboratory blanks that exceeded established minimums are identified in the same reports, in tables associating them with groundwater samples analyzed in the same batches.

Surrogates, organic compounds similar in chemical behavior to the compounds of interest but not normally found in environmental samples, are used to monitor the effect of the matrix on the accuracy of analyses for organic parameters. For example, for analyses of volatile organics by EPA method 8240, three surrogate compounds are added to all samples and blanks in each analytical batch. In analyses of semivolatile organics, three to four acid compounds and three to four base/neutral compounds are used. Other surrogates are used

in pesticides analyses. Percent recoveries for surrogate analyses are calculated by laboratory personnel, reported to EPD/EMS, reviewed, and entered into the database, but they are not published. If recoveries are not within specified limits, the laboratory is expected to re-run the samples or attach result qualifiers to the data identifying the anomalous results.

Sample-specific accuracy for both organic and inorganic parameters can be assessed by analysis of matrix spike/matrix spike duplicate results. A sample is analyzed unspiked to determine a baseline. A second portion of sample is spiked with known concentrations of compounds appropriate to the analyses being performed, typically 5 compounds for volatile organic analyses, 11 for semivolatiles, 6 for pesticides, or all compounds for the metals and cyanide. The percentage of spike compound recovered (percent recovery) is a direct measure of analytical accuracy. EPA requires matrix spike/matrix spike duplicates to be run at least once per 20 samples of similar matrix.

Matrix spike/matrix spike duplicate results are reported to EPD/EMS but are not published. For organic compounds, according to EPA guidelines, no action is taken on the basis of matrix spike/matrix spike duplicate data alone (i.e., no result modifiers are assigned solely on the basis of matrix spike results); however, the results can indicate if a lab is having a systematic problem in the analysis of one or more analytes.

In the case of inorganic compounds, such as metals, the matrix spike sample analysis provides information about the effect of each sample matrix on the digestion and measurement methodology. Data qualifiers can be assigned on the basis of the percentage of spike recovery and are reported in the published results tables.

Assessment of Precision

Precision of the analyses, or agreement of a set of replicate results among themselves, is assessed through the use of duplicates (laboratory-initiated) and blind replicates (provided by EPD/EMS). The results of duplicate and replicate analyses are presented in the results tables in these reports as multiple entries for an analyte under a single table heading.

The laboratories assess precision by calculating the relative percent difference, or RPD, for each pair of laboratory-initiated duplicate results. During 1992, at least one of the contract laboratories used a data qualifier (J3) to modify metals analyses when the RPD for laboratory duplicates was greater than 20%.

Additional statistical comparisons of laboratory duplicate and blind replicate results, both intra- and interlaboratory, are presented in the EPD/EMS quarterly reports. The calculation used for these reports is the MRD, or mean relative difference, which is similar to EPA's RPD except that the MRD provides a single value for all of the analyses of a particular compound, either inter- or intralaboratory, during one quarter. Because detection limits may vary among samples, the MRD requires calculation of a reference detection limit, which is the detection limit at the 90th percentile of the array of limits in the population of all replicate and duplicate analyses for a given analyte during a particular quarter. The MRD is not method-specific.

Method-Specific Accuracy and Precision

The contract laboratories' EPA-approved laboratory procedures include QA/QC requirements as an integral part of the methods. Thus, knowledge of the method used in obtaining data is an important component of determining data useability. EPA has conducted extensive research and development on the methods approved for the analysis of water and waste water; information on the accuracy and precision of the method is available from EPA publications, as is full information on required QA/QC procedures. A listing of the methods used by the primary laboratories during first quarter 1992 is given below along with the source for the method description. Many, if not all, of these sources include presentations of representative accuracy and precision results.

<u>Method</u>	<u>Used to Analyze</u>	<u>Source</u>
EPA120.1	Specific conductance	EPA EMSL 1983
EPA150.1	pH	EPA EMSL 1983
EPA160.1	Filterable residue (total dissolved solids)	EPA EMSL 1983
EPA160.2	Nonfilterable residue	EPA EMSL 1983
EPA180.1	Turbidity	EPA EMSL 1983
EPA200.7	Trace elements	EPA EMSL 1983
EPA206.2	Arsenic	EPA EMSL 1983
EPA208.2	Barium	EPA EMSL 1983
EPA239.2	Lead	EPA EMSL 1983
EPA245.1	Mercury	EPA EMSL 1983
EPA270.2	Selenium	EPA EMSL 1983
EPA279.2	Thallium	EPA EMSL 1983
EPA300.0	Inorganics, non-metals	EPA EMSL 1991
EPA310.1	Alkalinity	EPA EMSL 1983
EPA325.2	Chloride	EPA EMSL 1983
EPA335.3	Cyanide	EPA EMSL 1983
EPA340.2	Fluoride	EPA EMSL 1983
EPA353.1	Nitrogen, nitrate-nitrite	EPA EMSL 1983
EPA353.2	Nitrogen, nitrate, nitrite, or combined	EPA EMSL 1983
EPA353.3	Nitrogen, nitrate-nitrite, or nitrite only	EPA EMSL 1983
EPA354.1	Nitrogen, nitrite	EPA EMSL 1983
EPA365.1	Phosphorus, all forms (reported as total phosphates)	EPA EMSL 1983
EPA365.2	Phosphorus, all forms (reported as total phosphates)	EPA EMSL 1983
EPA375.4	Sulfate, turbidimetric	EPA EMSL 1983
EPA376.2	Sulfide	EPA EMSL 1983
APHA403	Alkalinity	APHA 1985
EPA413.1	Oil & grease	EPA EMSL 1983
APHA415A	Iodine	APHA 1985
EPA415.1	A total organic carbon (TOC) method; used for dissolved organic carbon (DOC) on filtered samples	EPA EMSL 1983
EPA418.1	Petroleum hydrocarbons	EPA EMSL 1983
EPA420.1	Phenolics	EPA EMSL 1983
EPA420.2	Phenolics	EPA EMSL 1983
APHA705	Total alpha-emitting radium	APHA 1985
ASTMD3869C	Iodide	ASTM 1992
APHA5320	Dissolved organic halogen	APHA 1989
EPA6010	Metals	EPA 1986
EPA7041	Antimony	EPA 1986
EPA7060	Arsenic	EPA 1986
EPA7421	Lead	EPA 1986
EPA7470	Mercury	EPA 1986

<u>Method</u>	<u>Used to Analyze</u>	<u>Source</u>
EPA7740	Selenium	EPA 1986
EPA7841	Thallium	EPA 1986
EPA8010	Halogenated volatile organics	EPA 1986
EPA8020	Aromatic volatile organics	EPA 1986
EPA8080	Organochlorine pesticides and PCBs	EPA 1986
EPA8140	Organophosphorus pesticides	EPA 1986
EPA8150	Chlorinated herbicides	EPA 1986
EPA8240	GCMS VOA	EPA 1986
EPA8270	GCMS semivolatiles	EPA 1986
EPA8280	Dioxins and furans	EPA 1986
EPA9012	Total cyanide	EPA 1986
EPA9020	Total organic halides	EPA 1986
EPA9030	Sulfides	EPA 1986

An example of the available method-specific QA/QC information is that for the analysis of metals. Both primary laboratories, General Engineering Laboratories (GE) and Roy F. Weston, Inc. (Weston), use EPA Method 6010/200.7 (EPA 1986/EPA EMSL 1983), an inductively coupled plasma (ICP) atomic emission spectrometric method, for the analysis of trace elements, specifically metals.

The following precision and accuracy data are based on the experience of seven laboratories that applied the ICP technique to acid-distilled water matrices that had been dosed with various metal concentrates. (Note: not all seven laboratories analyzed all 14 elements.) The references give results for samples having three concentration ranges; the results here are for samples having the lowest values, similar to actual groundwater results for SRS.

ICP Precision and Accuracy Data

<u>Element</u>	<u>True value ($\mu\text{g/L}$)</u>	<u>Mean reported value ($\mu\text{g/L}$)</u>	<u>Mean percent RSD^a</u>
Beryllium	20	20	9.8
Manganese	15	15	6.7
Vanadium	70	69	2.9
Arsenic	22	19	23
Chromium	10	10	18
Copper	11	11	40
Iron	20	19	15
Aluminum	60	62	33
Cadmium	2.5	2.9	16
Cobalt	20	20	4.1
Nickel	30	28	11
Lead	24	30	32
Zinc	16	19	45
Selenium	6	8.5	42

^a Relative standard deviation. Note: When this table was printed in EPA (1986), the column heading was Mean Standard Deviation (%).

As another example, EPA Method 601/8010 (EPA 1991a/EPA 1986) is used by both GE and Weston for analyses of halogenated volatile organics. In the presentation of the method in both references, the following table gives method-specific accuracy and precision as functions of concentration. Contract laboratories are expected to achieve or at least approach these limits.

Accuracy and Precision as Functions of Concentration for EPA Method 601/8010

<u>Parameter</u>	<u>Accuracy as recovery ($\mu\text{g/L}$)</u>	<u>Single analyst precision ($\mu\text{g/L}$)^a</u>	<u>Overall precision ($\mu\text{g/L}$)^b</u>
Bromodichloromethane	$1.12C - 1.02^c$	$0.11\bar{X} + 0.04^d$	$0.20\bar{X} + 1.00$
Bromoform	$0.96C - 2.05$	$0.12\bar{X} + 0.58$	$0.21\bar{X} + 2.41$
Bromomethane	$0.76C - 1.27$	$0.28\bar{X} + 0.27$	$0.36\bar{X} + 0.94$
Carbon tetrachloride	$0.98C - 1.04$	$0.15\bar{X} + 0.38$	$0.20\bar{X} + 0.39$
Chlorobenzene	$1.00C - 1.23$	$0.15\bar{X} - 0.02$	$0.18\bar{X} + 1.21$
Chloroethane	$0.99C - 1.53$	$0.14\bar{X} - 0.13$	$0.17\bar{X} + 0.63$
2-Chloroethyl vinyl ether ^e	$1.00C$	$0.20\bar{X}$	$0.35\bar{X}$
Chloroform	$0.93C - 0.39$	$0.13\bar{X} + 0.15$	$0.19\bar{X} - 0.02$
Chloromethane	$0.77C + 0.18$	$0.28\bar{X} - 0.31$	$0.52\bar{X} + 1.31$
Dibromochloromethane	$0.94C + 2.72$	$0.11\bar{X} + 1.10$	$0.24\bar{X} + 1.68$
1,2-Dichlorobenzene	$0.93C + 1.70$	$0.20\bar{X} + 0.97$	$0.13\bar{X} + 6.13$
1,3-Dichlorobenzene	$0.95C + 0.43$	$0.14\bar{X} + 2.33$	$0.26\bar{X} + 2.34$
1,4-Dichlorobenzene	$0.93C - 0.09$	$0.15\bar{X} + 0.29$	$0.20\bar{X} + 0.41$
1,1-Dichloroethane	$0.95C - 1.08$	$0.09\bar{X} + 0.17$	$0.14\bar{X} + 0.94$
1,2-Dichloroethane	$1.04C - 1.06$	$0.11\bar{X} + 0.70$	$0.15\bar{X} + 0.94$
1,1-Dichloroethene	$0.98C - 0.87$	$0.21\bar{X} - 0.23$	$0.29\bar{X} - 0.40$
trans-1,2-Dichloroethene	$0.97C - 0.16$	$0.11\bar{X} + 1.46$	$0.17\bar{X} + 1.46$
1,2-Dichloropropane ^e	$1.00C$	$0.13\bar{X}$	$0.23\bar{X}$
cis-1,3-Dichloropropene ^e	$1.00C$	$0.18\bar{X}$	$0.32\bar{X}$
trans-1,3-Dichloropropene ^e	$1.00C$	$0.18\bar{X}$	$0.32\bar{X}$
Methylene chloride	$0.91C - 0.93$	$0.11\bar{X} + 0.33$	$0.21\bar{X} + 1.43$
1,1,2,2-Tetrachlorethane	$0.95C + 0.19$	$0.14\bar{X} + 2.41$	$0.23\bar{X} + 2.79$
Tetrachloroethylene	$0.94C + 0.06$	$0.14\bar{X} + 0.38$	$0.18\bar{X} + 2.21$
1,1,1-Trichloroethane	$0.90C - 0.16$	$0.15\bar{X} + 0.04$	$0.20\bar{X} + 0.37$
1,1,2-Trichloroethane	$0.86C + 0.30$	$0.13\bar{X} - 0.14$	$0.19\bar{X} + 0.67$
Trichloroethylene	$0.87C + 0.48$	$0.13\bar{X} - 0.03$	$0.23\bar{X} + 0.30$
Trichlorofluoromethane	$0.89C - 0.07$	$0.15\bar{X} + 0.67$	$0.26\bar{X} + 0.91$
Vinyl chloride	$0.97C - 0.36$	$0.13\bar{X} + 0.65$	$0.27\bar{X} + 0.40$

^a Expected single analyst standard deviation of measurements.

^b Expected interlaboratory standard deviation of measurements.

^c C = true value for the concentration, in $\mu\text{g/L}$.

^d $\bar{X}$ = average recovery found for measurements of samples containing a concentration of C , in $\mu\text{g/L}$.

^e Estimates based on performance in a single laboratory.

References

APHA (American Public Health Association), 1985. **Standard Methods for the Examination of Water and Wastewater**, 16th edition.

APHA (American Public Health Association), 1989. **Standard Methods for the Examination of Water and Wastewater**, 17th edition.

ASTM (American Society for Testing and Materials), 1992. **1992 Annual Book of ASTM Standards**, Volume 11.02, Water (II). Philadelphia.

EPA (U.S. Environmental Protection Agency), 1986. **Test Methods for Evaluating Solid Waste (SW-846)**, Volumes IA–IC.

EPA (U.S. Environmental Protection Agency), 1987. **Data Quality Objectives for Remedial Response Activities**. PB88-131870; EPA/540/G-87/003.

EPA (U.S. Environmental Protection Agency), 1988a. **Contract Laboratory Program Statement of Work for Inorganics Analysis, Multi-Media, Multi-Concentration**. SOW No. 788.

EPA (U.S. Environmental Protection Agency), 1988b. **Contract Laboratory Program Statement of Work for Organics Analysis Multi-Media, Multi-Concentration**. SOW No. 288.

EPA (U.S. Environmental Protection Agency), 1990. **Guidance for Data Useability in Risk Assessment**. Interim Final. EPA/540/G-90/008.

EPA (U.S. Environmental Protection Agency), 1991a. **CFR** (Code of Federal Regulations), Title 40, Part 136, Appendix A. Revised July 1, 1991.

EPA EMSL (U.S. Environmental Protection Agency, Environmental Monitoring and Systems Laboratory), 1979. **Handbook for Analytical Quality Control in Water Wastewater Laboratories**. PB-297 451; EPA-600/4-79-019. Cincinnati, OH.

EPA EMSL (U.S. Environmental Protection Agency, Environmental Monitoring and Systems Laboratory), 1983. **Methods for Chemical Analysis of Water and Wastes**. Cincinnati, OH. Revised March 1983.

EPA EMSL (U.S. Environmental Protection Agency, Environmental Monitoring and Systems Laboratory), 1991. **Test Method, The Determination of Inorganic Anions in Water by Ion Chromatography—Method 300.0**, Revised August 1991.

END

**DATE
FILMED**

5 / 12 / 93