DOE/PC/89870-T1(Suppl.)
(DE92011812)

**COMPARISON OF SLURRY VERSUS FIXED-BED REACTOR COSTS FOR
INDIRECT LIQUEFACTION APPLICATIONS**

**A Supplement to Final Report Design of Slurry Reactor for Indirect Liquefaction
Applications**

**By
Anand Prakash
Prakash G. Bendale**

December 1991

Work Performed Under Contract No. AC22-89PC89870

**Viking Systems International
Pittsburgh, Pennsylvania**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615)576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U. S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

Comparison of Slurry versus Fixed-Bed

Reactor Costs for
Indirect Liquefaction Applications

DOE/PC/89870--T1-Suppl.
DE92 011812

A Supplement to

Final Report

DESIGN OF SLURRY REACTOR FOR
INDIRECT LIQUEFACTION APPLICATIONS

DOE Contract No. DE-AC22-89PC89870

December 1991

Anand Prakash
Prakash G. Bendale

Viking Systems International
2070 William Pitt Way
Pittsburgh, PA 15238

Slurry VS Fixed-Bed Reactor

Relative differences between slurry reactor and fixed-bed reactor have been pointed out in previous reviews. Following is a summary of the differences pertinent to indirect liquefaction.

Both methanol synthesis and FT synthesis reactions are highly exothermic. Heat of reaction for FT synthesis is about 165,000 kJ/kgmol (94,000 kJ/kgmol for methanol synthesis). The high heat flux in a slurry reactor compared to a fixed-bed reactor significantly reduces the number of heat transfer tubes required for slurry reactor. Cooling surface requirement in a slurry reactor is about a quarter of that in a tubular fixed-bed reactor.

Higher conversion per pass can be achieved in a slurry reactor which lowers recycle to fresh feed ratio. The fixed-bed reactor, however, requires a high recycle ratio to limit temperature rise and improve heat transfer rate. Higher recycle rate increases the operating costs associated not only with separation and purification but also with the increased pressure drop across the bed. High heat of reaction would limit conversion per pass in a fixed bed reactor and increase recycle flow.

The volumetric loading of catalyst in a fixed-bed reactor can be significantly higher compared to slurry reactor. This advantage of fixed-bed reactor in FT synthesis can be partially offset by operating the slurry reactor at higher temperature continuously. Fixed-bed temperature is increased gradually as activity declines. This temperature difference can partially compensate for the reduced catalyst loading in a slurry reactor.

Catalyst activity in a slurry reactor can be maintained at a constant level by on-line addition and withdrawal of catalyst. A slurry reactor can operate continuously at the end of run temperature of the fixed-bed reactor thus giving higher productivity. Fixed-bed reactor temperature is increased periodically to make up for catalyst deactivation. When end-of-run temperature is reached fixed-bed reactor requires shutdown for catalyst replacement.

Slurry reactor offers the advantage of plug free operation. The fixed-bed reactor must operate with H_2/CO ratio in excess of unity due to possibility of plugging as a consequence of carbon build up. Low H_2/CO ratio can lead to carbon formation via the Boudouard reaction

A slurry reactor, however, raises the H_2/CO ratio at the catalyst surface due to higher mass transfer for hydrogen and a higher CO consumption (for iron based catalyst). Possibility of plugging is also expected to increase when a fixed-bed reactor for FT synthesis is operated for production of high molecular weight products.

Fixed-Bed Reactor Design Summary

Design information for fixed-bed reactors for methanol synthesis and Fischer-Tropsch synthesis was mainly obtained from literature although some quick checks were made using the

heterogeneous reactor model for fixed-bed reactor. The heterogeneous reactor model allows for differences in concentrations and temperature between the bulk gas stream and the catalyst pellet. The effects of internal and external resistances on the reaction rates are accounted for by using overall reaction rates rather than intrinsic rates which requires calculation of effectiveness factor for the catalyst particles.

For exothermic reactions, the design of a fixed-bed reactor is greatly governed by the control of the reactor temperature. Temperature control in turn, depends on the efficiency of the removal of heat of reaction. Overheating of the catalyst seriously affects the yield of the products and enhances the side reactions, thus affecting catalyst life.

The commonly used fixed-bed reactors for methanol synthesis are ICI quench type reactor and Lurgi shell and tube reactor. The Lurgi reactor design provides better temperature control compared to ICI design. This reactor is essentially a vertical-tube heat exchanger, the catalyst is placed inside the tubes with boiling water on the outside. The reactor temperature is controlled by controlling the pressure of the boiling water.

The design data for a Lurgi fixed-bed reactor for a production rate of 1488 MTD of methanol are reproduced in Table 1 (from Bechtel Topical Report to DOE; Fox and Degen, 1990). Figure 1 shows the overall dimensions of the reactor based on use of stoichiometric synthesis gas.

For Fischer-Tropsch synthesis tubular fixed-bed ARGE reactors (Lurgi design) have been used at Sasol, South Africa. Design data for ARGE reactors are provided in Encyclopedia of Chemical

Technology (2nd Edition, Vol. 4). The reactor ID is 116 inches and length of the catalyst bed is approximately 40 feet. Inside diameter of the tubes is 1.8 inches for a total of 2000 tubes. Production capacity of this reactor is about 60 MTD. Bechtel sized a larger tubular fixed bed reactor (ID 189 inches) for a production capacity of 290 MTD using cobalt based catalyst (Table 5). The reactor diameter of 4.8 meters is based on the current limit for commercial Lurgi methanol reactors. Design space velocity were almost the same as ARGE reactor at $1920 \text{ Nm}^3/\text{h.m}^3$. Conversion per pass was increased from 26% to 37% based on a higher pressure level and higher catalyst activity. Bechtel design was selected for cost comparison with slurry reactor. The overall dimensions of this reactor are shown in Figure 4.

Slurry Reactor Design Summary

- Slurry reactor design for the two applications is based on slurry concentration of 34 wt%. Superficial gas velocity was selected to be higher than 0.15 m/s to ensure uniform gas-liquid contact.
- Reactors were sized assuming axial mixing in both slurry and gas phases.
- Average superficial gas velocity was used to estimate hydrodynamic parameters.
- For both applications internal heat exchanger system was designed with coolant to reactor $\Delta T = 28^\circ\text{C}$.
- Calculated reactor volume was increased by about 20% to add disengaging space.
- Calculated heat transfer area was increased by 10% for added safety.

Methanol synthesis is favored by low temperature and high operating pressure. Design temperature and pressure for methanol synthesis reactor were again selected from an analysis of Laporte process development unit data. Table 2 summarizes the design data for methanol synthesis slurry reactor. In order to make a one-for-one comparison of reactor design, the slurry reactor for methanol synthesis was also sized using stoichiometric synthesis gas. The length of slurry reactor required for a production rate of 1480 MTD of methanol is about twice that of the fixed-bed reactor (Figures 1 & 2). The cost of two reactors are compared in Table 5. It can be seen that the cost of fixed-bed reactor is less than slurry reactor for methanol synthesis. The cost differential improves in favor of fixed-bed when SS 304 tubes are replaced by carbon steel tubes. SS 304 tubes and SS cladding are recommended for syngas with low H_2/CO ratio. For slurry reactor, heat exchanger tubes cost is a smaller fraction of the total reactor cost compared to fixed-bed reactor. The slurry reactor shell needs to be designed for reactor operating pressure. For the fixed-bed reactor, however, shell design pressure is the pressure of steam generated.

Since FT synthesis is not limited by equilibrium, higher reactor temperature can be used to improve productivity. FT reactor is designed for a chain growth probability factor of 0.9 to maximize high molecular weight product fraction. Table 3 summarizes design data for two FT reactors based on 70% and 81% syngas conversion. The overall dimensions of the reactor design based on 81% syngas conversion are shown in Figure 3. The costs of fixed-bed and slurry reactor systems required for a total production rate of 2300 MTD of hydrocarbons are compared in Table 6. Slurry reactor system cost also include cost of equipments for continuous catalyst addition and withdrawal. It can be seen that slurry reactors cost is about half of fixed-bed reactors cost. Table

6 also compares the cost of slurry reactor system with 70% and 81% syngas conversion. Since the cost differential is marginal, it would be advisable to design slurry reactors for higher syngas conversion to minimize operating cost due to recycling.

The estimated costs are preliminary and do not include cost of freight and installation. A procedure based on estimating charts and cost indexes was developed to obtain approximate cost estimates. For more accurate cost estimates, several equipment vendors were contacted. It was, however, difficult to find a US company with capabilities to fabricate pressure vessels of these sizes. One vendor was able to provide cost estimates for slurry reactors. For fixed-bed reactors, however, the weight and size of tube sheets required exceeded its machine shop handling capabilities. Our cost estimates for slurry reactors compared well (within 10%) with the vendor-supplied estimates. Uncertainties with fixed-bed reactors cost estimates are expected to be higher (20 to 30%) due to difficulties expressed by equipment vendors. Based on the response of equipment vendors, it may be more cost effective to consider reactor diameters in the range of 3 to 4 meters.

Table 1. Fixed-bed reactor for methanol synthesis (Lurgi design)

Diameter	4.8 m
Length	7.5 m
Temperature	255°C (outlet-at end of run)
Pressure	55.0 atm
Supf. Gas velocity	0.388 m/s
$(\text{H}_2\text{-CO}_2)/(\text{CO}+\text{CO}_2)$	2.05
Tube OD	0.038 m
Total Cooling Surface	8020 m ²
No. of Tubes	9600
CO Conversion	54.8%
STY	457.0 kg methanol/h.m ³
Space Velocity	8771.0 Nm ³ /h.m ³
Methanol Production	1488 MTD

Table 2. Slurry reactor design for methanol synthesis

Diameter	4.8 m
Length	13.5 m
Temperature	240°C
Pressure	55.0 atm
Slurry Conc.	34 wt%
Supf. Gas Velocity	0.155 m/s
$(\text{H}_2\text{-CO}_2)/(\text{CO}+\text{CO}_2)$	2.05
Catalyst Size	0.000025 m
Tube OD	0.038 m
Tube Length	13.0 m
Total Cooling Surface	2100.0 m ²
No. of Tubes	1350
CO Conversion	62%
STY	266.0 kg methanol/h.m ³
Productivity	1.0 kg methanol/h.kgcat
Space Velocity	1170.0 Nm ³ /h.m ³
Methanol Production	1480 MTD

Table 3. Slurry reactor design for Fischer-Tropsch synthesis

Diameter, m	4.8	4.8
Length, m	11.0	14.0
Temperature, °C	255.0	262.0
Pressure, atm	28.0	28.0
Slurry Conc., wt. %	34.0	34.0
Supf. Gas Velocity, m/s	0.155	0.162
H ₂ /CO	0.61	0.61
Catalyst Size, m	0.000025	0.000025
Tube OD, m	0.038	0.038
Tube Length, m	10.5	13.5
Total Cooling Surface, m ²	2600	3140
No. of Tubes	2075	1950
Syn Gas Conversion %	70	81
STY, kg HC/h.m ³	92.0	86.5
Productivity, kg HC/h.kgcat	0.35	0.33
Space Velocity, Nm ³ /h.m ³	710	584
Gas Holdup	0.275	0.275
Hydrocarbon Prod., MTD	385	463

**Table 4. Fixed-bed reactor for Fischer-Tropsch synthesis
(Bechtel design)**

Diameter	4.8 m
Length	12.65 m
Temperature	225°C (outlet-start of run)
Pressure	28.3 atm
Supf. Gas Velocity	0.53 m/s
Tube OD	0.038 m
Total Cooling Surface	13920 m ²
No. of Tubes	9602
Syn Gas Conversion	37%
STY	111 kg HC/h.m ³
Space Velocity	1917 Nm ³ /h.m ³
Hydrocarbon Production	289 MTD

Table 5. Capital cost comparison for Methanol Synthesis Reactors

Cost in \$Millions - 4th Quarter 1991

	Fixed Bed	Slurry
Methanol Production 1488 MTD		1482
SS 304 Tubes	3.2	3.85
CS Tubes	2.45	3.5

Table 6. Capital cost comparison for FT Synthesis Reactors

	Fixed Bed	Slurry	
Hydrocarbon Prod. Rate 2312 MTD	2312	2312	2310
No. of reactors	8	6	5

Cost in \$Millions - 4th Quarter 1991

Cost of each reactor system	3.65	2.65	3.2
Total cost of reactor systems	29.2	15.9	16.0

Figure 1

Fixed BED Methanol Reactor
(Lurgi Design)

Design Conditions - Tube Side 875 PSIG 550F; Shell Side 650 PSIG 550F

Metallurgy: Shell - SA516 GR70 with 1/8" C.A.; Tubes C.S. Chromized.

Figure 2

Slurry Reactor for Methanol Synthesis

Design Conditions - Tube Side 580 PSIG 550F; Shell Side 875 PSIG 550F

Metallurgy: Shell - SA516 GR70 with SS304 Cladding Tubes SS304

Slurry Reactor Fischer - Tropsch Synthesis

Design Conditions - Tube Side-580 PSIG 550F; Shell Side 460 PSIG 550F

Metallurgy: Shell - SA516 GR70 with 1/8" C.A.; Tubes C.S. Chromized

Figure 4

Fixed Bed Fischer - Tropsch Reactor
(Bechtel Design)

Design Conditions - Tube Side: 460 PSIG 550F; Shell Side: 580 PSIG 550F
Metallurgy: Shell - SA516 GR70 with 1/8" C.A.; Tubes C.S. Chromized

END

**DATE
FILMED
6 10 8 192**