**ASSESSMENT AND DEVELOPMENT OF AN
ADVANCED HEAT PUMP FOR RECOVERY
OF VOLATILE ORGANIC COMPOUNDS**

Final Report

June 1992

Work Performed Under Contract No. DE-FC07-88ID12788

Prepared for the
U.S. Department of Energy
Under DOE Idaho Field Office
Sponsored by the Office of the Assistant Secretary
for Conservation and Renewable Energy
Office of Industrial Technologies
Washington, D.C.

Prepared by
Mechanical Technology Incorporated
968 Albany-Shaker Road
Latham, New York 12110

EXECUTIVE SUMMARY

Loss of volatile organic compounds (VOCs) to the atmosphere represents a significant energy, economic, and environmental concern for government and industry. Reliable and economical ways of recovering these materials for reuse could be crucial to the economic viability and competitiveness of affected industries as environmental regulations are tightened. The U.S. Department of Energy (DOE) has sponsored several advanced heat pump development projects directed at the recovery of VOCs from solvent-laden air (SLA) streams. DOE's interest in this technology is primarily in the energy embodied in the recovered solvents, both in terms of the energy required for their manufacture and for their environmentally acceptable recovery or disposal. This report documents Phase I of a project conducted by Mechanical Technology Incorporated (MTI) for the assessment and development of an advanced heat pump for recovery of VOC solvents from process gas streams. The objective of this project is to develop a system that is economically attractive to the industrial user and will result in widespread replication. In Phase I, MTI has evaluated solvent recovery applications within New York State (NYS), identified host sites willing to implement their application, and conducted a preliminary design of the equipment required. In addition, the design and applications were evaluated for technical and economic feasibility.

The solvent recovery heat pump system concept resulting from the Phase I work is one of a mobile unit that would service multiple stationary adsorbers. The NYS study showed that a large percentage of solvent recovery applications within the state can be serviced by on-site carbon bed adsorbers that are desorbed at frequencies ranging from once per day to once per month. In this way, many users can effectively "share" the substantial capital investment associated with the system's reverse Brayton hardware, providing it can be packaged as a mobile unit (see Figure S-1).

In a typical operating scenario, a carbon adsorption module will be located permanently at the industrial site. The SLA will be ducted through the adsorber and the solvents removed, thus eliminating an air emission problem. Prior to VOC breakthrough, by schedule or by request, the mobile unit would arrive at the site to recover the concentrated solvent. An engine driven, natural gas fueled system, the mobile unit utilizes conditioned engine exhaust gases as the inert gas for desorption. Hot inert gas is directed through the carbon bed, heating it and volatilizing the adsorbed solvent. Using a reverse Brayton-cycle refrigeration system to create low temperatures, the solvent vapors are condensed and collected from the inert gas stream. The solvent can then be recycled to the production process or sold for other uses and the adsorber returned to service.

The Brayton-cycle turbomachine, a key subsystem of the mobile unit, is discussed in detail in Sections 3.0 and 4.0. The integrated machinery approach emphasizes reliability and cost reduction through reduced complexity (fewer parts), elimination of wear-prone parts (gears and seals), and the use of proven components in critical service (bearings, aerodynamic components, and motor).

MTI has conducted an extensive review of solvent recovery applications in NYS using a data base compiled for this project from a NYS Department of Environmental Conservation (DEC) data base. The DEC data base contains 65,000 emission points taken from

891866

Figure S-1. Solvent Recovery Heat Pump System: Design Concept for Mobile Unit

air quality permit applications and includes many that are not applicable to solvent recovery. By applying relevant sort criteria, a smaller, more germane data base was generated and used for the study and preliminary identification of host site candidates. Results of the study indicated an extensive need for solvent recovery and reuse as the state and nation enter an era of increasing concern for the environment. The study identified two areas that will need to be addressed in the near term: moderate-sized emission streams that cannot fully utilize a dedicated recovery system, and emission streams in the lower concentration range of less than 200 ppm. The mobile unit described above addresses both of these future needs.

The NYS applications study revealed that as regulations are made more stringent there will be an increasing need for solvent recovery technologies that are not economically feasible today. Existing solvent recovery techniques require substantial capital investment and have a poor return in terms of the value of solvent recovered. Therefore, industry and the small- to medium-sized company in particular will not adopt these measures until regulated to do so and then only at significant risk to their financial health. A second

area in need of new recovery technology is that of low concentration emissions. In the past, these have been viewed as insignificant on a local basis. Now it is recognized that the long-term cumulative effect of these sources is a global problem, and regulations are moving in this direction. The only current technology that can effectively remove solvents in concentrations below 200 ppm is adsorption. However, here again, the cost has been prohibitively high for most large streams.

The MTI mobile unit concept offers a new approach to these two problems and specifically addresses the economic feasibility issue. The mobile unit can be provided on a fee-for-service basis to the small- and medium-sized user who could not afford to purchase the complete system. The combination of dedicated and mobile plants provides the potential for wide-spread utilization to achieve a favorable energy and environmental impact for the nation.

TABLE OF CONTENTS

SECTION	PAGE
EXECUTIVE SUMMARY	iii
LIST OF FIGURES	ix
LIST OF TABLES	xi
1.0 INTRODUCTION	1-1
2.0 APPLICATIONS STUDY	2-1
2.1 NYS VOC Data Base	2-1
2.1.1 Key Process Groups	2-4
2.2 Applications Selection Criteria	2-6
2.3 Host Site Candidates	2-6
3.0 TURBOMACHINE DESIGN BASIS	3-1
4.0 PRELIMINARY TURBOMACHINE DESIGN	4-1
4.1 Mechanical Configuration	4-1
4.2 Preliminary Layout	4-2
4.3 Turbomachine Performance	4-5
4.4 Gas Bearing System	4-8
4.4.1 Gas Bearing Theory	4-8
4.4.2 Advantages of Gas Bearings	4-9
4.4.3 Design Parameters	4-11
4.4.4 Selection of Bearing Configurations and Load Analysis	4-11
4.4.5 Frictional Power Losses	4-13
4.4.6 Cooling	4-15
4.4.7 Coatings	4-16
4.4.8 Issues for Final Design	4-17
5.0 PRELIMINARY SYSTEM DESIGN	5-1
5.1 System Alternatives	5-1
5.2 Heat Pump Alternatives	5-4
5.2.1 Electric versus Thermal Engine-Driven Systems	5-5
5.2.2 Multiple-Level versus Single-Level Refrigeration Systems	5-5
5.3 Process Flow Diagram	5-9
5.4 System Simulation Model	5-10
5.4.1 Performance	5-12
5.5 Mobile Unit Design	5-16
5.5.1 Process Description	5-16
5.5.2 Mobile Unit Packaging	5-18
5.5.3 System Controls	5-19
5.6 Balance of Plant Equipment	5-19
5.6.1 Reverse Rankine Refrigeration System	5-29
5.6.2 Service Module Equipment	5-29
5.6.3 Recuperative Heat Exchanger and Solvent Condensation Module	5-31

TABLE OF CONTENTS (continued)

SECTION	PAGE
6.0 COST ANALYSIS	6-1
7.0 FEASIBILITY ASSESSMENT	7-1
7.1 Incineration	7-1
7.1.1 Thermal Incineration	7-2
7.1.2 Catalytic Incineration	7-3
7.2 Conventional Condensation Technology	7-4
7.3 Carbon Adsorption — Steam Desorption	7-5
8.0 MARKET ASSESSMENT	8-1
8.1 Multipliers	8-1
8.2 Urgency of RD&D Program.	8-3
9.0 CONCLUSIONS	9-1

LIST OF FIGURES

NUMBER		PAGE
2-1	SLA Flow Rates for NYS Emission Points	2-4
2-2	Control Technology Breakdown for NYS Emission Points	2-5
3-1	Baseline Solvent Recovery Heat Pump Schematic	3-1
3-2	Relationship Between Tasks of Phase I Design Effort	3-3
3-3	Relationship Between Turbomachine Speed and Flow for Various System Pressure Ratios	3-4
4-1	Turbomachine Critical Speed Map	4-2
4-2	Cross Section of Preliminary Layout of Brayton-Cycle Turbomachine	4-3
4-3	Turbine End Labyrinth Seal Arrangement	4-4
4-4	Turbine Efficiency versus rpm	4-6
4-5	Compressor Performance Map	4-7
4-6	Load Support for Journal and Thrust Bearings	4-9
4-7	The MTI Hydresil™ Compliant Foil-Type Air Bearing	4-10
4-8	Preliminary Concept for Foil Journal Bearing (Compressor End)	4-12
4-9	Preliminary Concept for Foil Thrust Bearings	4-14
4-10	Foil Thrust Bearing: Operating Gas Film Thickness as a Function of Load	4-14
5-1	Solvent Recovery Heat Pump System Used with Molecular Sieve VOC Solvent	5-2
5-2	Solvent Recovery Heat Pump System Used for Carbon Bed Desorption	5-3
5-3	Comparison of Electric versus Thermal Engine-Driven Systems	5-6
5-4	Brayton-Cycle Pressure Ratio versus Inlet Concentration of Methylene Chloride Solvent	5-7
5-5	Comparison of Refrigeration Cycle	5-8
5-6	Process Flow Schematic of Solvent Recovery Heat Pump System	5-9
5-7	Schematic of Combined Brayton-Rankine Process Model	5-12
5-8	System Performance for Methylene Chloride	5-13
5-9	System Performance for Toluene	5-13
5-10	System Performance for Acetone	5-14
5-11	System Performance for Tetrahydrofuran	5-14
5-12	System Performance for Trichloroethylene	5-15
5-13	System Performance for Perchloroethylene	5-15
5-14	System Performance for Methyl Ethyl Ketone	5-16
5-15	Solvent Recovery Heat Pump System	5-17
5-16	Packaging Concept for Mobile Unit	5-18
5-17	System Piping and Instrumentation Schematic	5-20
5-18	System Operating Logic Diagram	5-21
5-19	Power Supply System	5-30
6-1	Turbomachine Cost in Production Quantities	6-2
6-2	Production Unit Cost versus Capacity	6-2
7-1	Thermal Incineration with Primary Heat Recovery	7-2
7-2	Catalytic Incineration with Primary Heat Source	7-3
7-3	Direct-Cooled Condensation System	7-4
8-1	Principal Market Areas	8-2

LIST OF TABLES

NUMBER		PAGE
2-1	Solvents Used for Screening the DEC Data Base	2-2
2-2	Solvent Emissions in New York State	2-3
2-3	Summary of Companies Screened as Host Site Candidates	2-6
2-4	Host Site Candidates	2-8
3-1	Brayton-Cycle Turbomachine Operational Envelope	3-5
4-1	Performance at Nominal Design Conditions	4-8
4-2	Rotor Weight Loads on Bearings	4-15
5-1	Optimized Brayton-Cycle Heat Pump Applications	5-4
5-2	Baseline Process Conditions	5-11
5-3	Thermal Duties and Performance of Heat Exchanger and Separation Equipment	5-31
5-4	Data Sheet for Precooler Heat Exchanger (HX1)	5-32
5-5	Data Sheet for Aftercooler Heat Exchanger (HX2)	5-33
5-6	Data Sheet for Recuperative Condenser Heat Exchanger (HX3)	5-34
5-7	Data Sheet for Recuperative Condenser Heat Exchanger (HX4)	5-35
6-1	Preliminary Production System Cost Estimate	6-1
7-1	Estimated Incinerator Costs	7-3
7-2	Cost of Carbon Adsorption Systems, Not Installed	7-5
8-1	Annual Emissions in Selected States	8-3

1.0 INTRODUCTION

This report describes the results of the Phase I preliminary design and economic evaluation for an advanced heat pump for recovery of volatile organic compounds from process gas streams. The overall objective of the project is to design, build, install, and field test a system that is economically attractive to the user and will result in widespread utilization. The project consists of the following three phases:

Phase I — Preliminary Design and Economic Evaluation (This phase is reported herein)

Phase II — Final Design, Fabrication, and Performance Testing

Phase III — Industrial Installation and Operational Evaluation.

The Phase I report is structured as follows. Section 2.0 discusses the results of the New York State application study and the selection of host site candidates. Sections 3.0, 4.0, and 5.0, document the preliminary design concept and provide background analysis and trade-off studies that preceded the design conclusions. Section 6.0 presents cost information for the turbomachine and the system.

Section 7.0 describes alternative methods of emission control and solvent recovery for comparison to the Brayton cycle. Risks and benefits of the system are also discussed in this section. Section 8.0 projects the national market for the proposed solvent recovery system based on the New York State application work. Section 9.0 presents the conclusions and recommendations for Phase I.

2.0 APPLICATIONS STUDY

VOCs are used as solvents in many of the following processes and industries:

- Coating processes such as painting, tape and film manufacturing, printing, and textile manufacturing
- Cleaning processes such as manufacture of printed circuit boards, electronic parts, mechanical parts, and textiles
- Production of polymeric materials such as plastics and rubber
- Fuel production and distribution
- Foam blowing
- Production and use of refrigerants
- Manufacture of wood products such as plywood, particle board, and furniture.

In many processes, the solvent ends its cycle as a vapor component in a warm air stream. Until recently, the majority of these SLA streams were unregulated and often subject to uncontrolled release to the atmosphere. With increasing concern for the environment, associated with the greenhouse effect and the ozone layer depletion, regulations are becoming more stringent. The changing regulatory environment has left manufacturers with three choices:

- Eliminate organic and halogenated organic solvents from the process
- Incinerate solvents before release
- Recover solvents from the SLA and recycle them to the process.

Elimination of solvents is the preferred solution if it can be done without a deleterious effect on product quality. Incineration is not a long-term solution, since it simply substitutes one regulated emission for another that would soon be regulated. Due to new emission regulations anticipated for the future, the recovery and recycling of solvents is expected to play a larger role for those industries with VOC emissions. Recovery of solvents can be accomplished by direct condensation by air, water, reverse Rankine or Brayton cycle, or by carbon desorption using steam or inert gas. Each recovery process has its range of application, as well as advantages and disadvantages. The applications study summarized herein, which is based on NYS data, had two purposes: to characterize the solvent recovery needs of NYS manufacturers, and to identify field test sites for the first unit.

2.1 NYS VOC Data Base

In cooperation with DOE, the New York State Energy Research and Development Authority (NYSERDA) funded a study to characterize the solvent recovery needs of NYS. A full report on this study will be available from NYSERDA; a summary of the results is presented below.

Several sources of information were investigated to identify solvent emission sources within the state. Federal data bases, such as the U.S. Environmental Protection

Agency Background Information Documents and the Toxic Release Inventory, were found to break the solvent emissions into broad groups, states, or regions (for example, the New England region), but provided no insight into individual emission sources.

MTI then focused the search on NYS, which led to the New York State Department of Environmental Conservation and their data base of 65,000 emission points. These 65,000 emission points are based on air quality permit applications and represent all emissions into the atmosphere, whether organic solvents, hydrocarbons, or products of combustion. In order to limit the search to solvents of interest, the data base was queried for emission sources involving 26 specific solvents in large-scale use (see Table 2-1 for a listing of these solvents).

Table 2-1. Solvents Used for Screening the DEC Data Base

Ethanol	Butane Acetate
Methanol	Xylene
Isopropyl Alcohol	Naptha
Dimethyl Ketone	Butanol
1,1,2 - Trichloro - 1,2,2 - Trifluoro	Ethane
Ethane (Freon 11)	
Methyl Ethyl Ketone (MEK)	Dichloromethane
1,2 - Ethane Diol (Ethylene Glycol)	Trichloroethylene
Methyl Isobutyl Ketone (MIBK)	Cellosolve
Toluene	Ethyl Acetate
Tetrahydrofuran	Ligroine (Mineral Spirits)
	Glycol Monobutyl Ether
Cyclohexanone	
Hexane	
Acetone	
Perchloroethylene	
Heptane	

90TR7

The resulting data base contains 207 companies operating 2318 solvent streams emitted to the atmosphere through 522 emission points. Thus, the typical atmospheric emission point contains 4 or 5 different solvents. When an emission point included solvents in addition to those listed in Table 2-1, these were also included in the data base. The total emissions covered by the data base is 62×10^6 lb/yr. The U.S. Toxic Release Inventory shows about 68×10^6 lb/yr of organic and halogenated organics for NYS, indicating that the MTI VOC data base is in close agreement with the national figures. Exercising the data base provides an overview of the distribution of emission points in NYS by solvent type, SLA flow rates, and control technologies.

Table 2-2 lists the 30 solvents with the highest reported emissions in the MTI data base. It is notable that many of the top solvents, including the alcohols and ketones, have been identified as particularly suitable for recovery by the Brayton cycle. This is discussed in more detail in Section 2.2.

Figure 2-1 shows the distribution of emission points as a function of the total volume flow rate of the SLA. The emission points cover a wide range of volume flows, with nearly one-third having a volume flow of less than 2000 cfm and one-quarter having volume flows over 10,000 cfm.

Table 2-2. Solvent Emissions in New York State

Solvent	lb/yr
Methanol	7,949,569
Acetone	6,529,591
Methylene Chloride	6,415,853
Toluene	5,483,914
Ethanol	4,896,274
Xylene	3,081,882
Methyl Ethyl Ketone	2,885,952
Methyl Chloroform	2,614,476
Isopropyl Alcohol	2,283,656
Hexane	2,170,324
Ethyl Acetate	1,711,710
N-Heptane	1,707,647
Methyl Isobutyl	1,104,598
Trichloroethylene	1,087,505
Tetrachloroethylene	929,411
Propyl Acetate	700,137
Butyl Alcohol	672,088
Ligroine	635,059
Ethylene Glycol Monobutyl Ether	494,258
Propanol	450,464
Isopropyl Ether	341,248
Acetonitrile	355,462
Ethylene Glycol Monoethyl Ether	225,746
Naptha	214,742
Isoheptane	191,000
Butyl Acetate	190,436
Acetic Acid	175,505
Isopropyl Acetate	144,865
Tetrahydrofuran	127,411
Cyclohexanone	100,988
Total	55,851,771

90TR7

Figure 2-1. SLA Flow Rates for NYS Emission Points

The size of the MTI mobile unit was determined by commercially available components (see Section 3.0) and the technical market as depicted in Figure 2-1. With a carbon adsorber, a 2500-cfm turbomachine can be applied to a 10,000-cfm SLA stream. As shown in Figure 2-1, approximately 80% of the emission points are below 10,000 cfm and, thus, would be covered by this machine.

Technologies for controlling organic solvent emissions include carbon bed adsorbers, vapor condensers, thermal incinerators, and scrubbers. According to the data base, only 10% of the emission points have any form of control. As shown in Figure 2-2, the most popular control technology is vapor condensers, followed by carbon bed adsorbers and thermal incineration. Nearly half of the emission points have a fan to assist in exhausting the solvent to the atmosphere. Fans are utilized to control solvent concentrations to a safe level within a building but provide no control on global emissions. With 90% of VOCs being emitted without control, there will be a significant need for new control technologies as regulations become more stringent in the future.

2.1.1 Key Process Groups

Sorting the data base according to Standard Industrial Classification (SIC) codes allows the key user groups in NYS to be identified. The results of this analysis are presented in Table 2-2 and can be further reduced to six key groups: photographic equipment and supplies, printing, chemicals, electronics, paper and fabric coating, and metal coating and cleaning.

891863

Figure 2-2. Control Technology Breakdown for NYS Emission Points

Photographic equipment and processing suppliers in the state comprise the largest organic solvent user group. This industry, which uses a large variety of solvents, tends to operate their processes around the clock.

The printing industry (SIC codes 273, 275, 264, and 265) includes rotogravure and lithographic processes. The printing process utilizes a mixture of solvents to provide good coverage of ink on the paper or fabric in order to produce bright, bold covers. The switch to water-based inks can have a major effect on product quality and has only penetrated certain segments of the industry. A wide variety of solvents are used, with the more popular including acetone, toluene, propyl acetate, methyl isobutyl, methanol, and ethanol. Printing operations tend to operate around the clock and have a high level of fugitive emissions due to their design and operating characteristics.

The chemical manufacturers comprise another key user group in NYS. Although many operate around the clock, some companies switch between batch processes according to market demand. Thus, many solvents are utilized during the year, but the individual emissions are relatively small. Some basic processes operate continuously, and significant usage of acetone, toluene, methanol, and ethanol is observed.

Closely related to the New York chemical industry are the drug and pharmaceutical manufacturers. The general operating pattern of the drug manufacturers is a large number of small batch productions, each with its own unique solvent requirement. Because manufacturing tolerances are extremely tight in the drug business, the emission of solvents tends to be small. Therefore, while the drug manufacturers represent a significant number of emission points, they comprise a small amount of the total solvent emissions.

The final key user group are those industries that involve metal coating and cleaning. These include aerospace and automotive assembly operations, industrial equipment manufacturers, and fabricators. Popular solvents include trichloroethylene and tetrachloroethylene. Solvent usage in these industries is characterized by large dip tanks widely scattered throughout the manufacturing operation. Operating cycles are typically two shifts a day, five days a week.

2.2 Applications Selection Criteria

The NYS applications data base created under the NYSERDA study provides a source of field test site candidates for the first unit. The following selection criteria have been defined to identify those processes best suited to the operating characteristics of the solvent recovery heat pump system designed under this project.

- Air flow rates: 500- to 2500-acfm direct condensation, 1000 to 40,000 acfm with concentrator.
- Concentrations: greater than 5000 ppmv (or 40% lower explosive limit (LEL)) direct condensation possible, less than 5000 ppmv (or 40% LEL) concentrator required.
- Solvents: solvents that are difficult to recover by other methods were targeted for the Brayton cycle. The following were identified because they are miscible in water, require low condensing temperatures, or react negatively with carbon beds: ethanol, methanol, acetone, trichloroethylene, methylene chloride, methyl ethyl ketone, and naphtha.
- Operating times: greater than 6000 hr for direct condensation. This is not a limitation when a carbon concentrator is used in conjunction with a mobile desorption unit because the concentrator can be sized for the expected flow rate (pph) multiplied by operating hours and a normal period of desorption assigned. There may be a limitation on the length of time that certain solvents should sit in a carbon bed, considering the reactions that may occur.

2.3 Host Site Candidates

Forty-five companies were contacted directly as part of the search for industrial host sites. Thirty of these sites were selected by screening the applications data base for the selection criteria defined in the previous section. The balance either initiated the contact themselves or were selected based on newspaper accounts of large VOC emitters. Table 2-3 summarizes the responses received according to the representative process groups and provides some statistical information on the contacts made.

Table 2-3. Summary of Companies Screened as Host Site Candidates

	Photographic Equipment and Supplies	Printing	Paper and Fabric Coating	Chemicals	Electronics	Metal Coating and Cleaning	Others	Total
Sites Contacted	2	10	7	5	3	9	9	45
Very Interested		1	2		1	2		6
Interested	1	4	2		2	3	1	13
Not Interested	1	5	3	5		4	8	26
Using Adsorption		1	1		2	1		5
Using Condensation	1		1					2
Using Incineration		4	3					7
Eliminating Organic Solvents		1				1		2
Plant Closing			1	1				2
Has Current Need	1	3	3		4	1		12

90TR7

Following an initial phone call to obtain the name and address of the appropriate company representative, a letter describing the project and the solvent recovery heat pump system was sent to 45 sites. Follow-up phone calls were made to gauge the level of interest and obtain preliminary application information. Nineteen companies responded positively and openly discussed solvents used, emission levels, current control technologies, regulatory issues, and related topics. This high level of response to "cold phone contacts" indicates the priority that many of these companies are putting on VOC emissions. In large companies, several people will be dedicated to this area, and, even in small companies, specific individuals have been given responsibility for air quality issues.

The "not interested" category undoubtedly includes a considerable number of companies who are dealing with the same emission issues as those who were interested but want to avoid public discussion of them. The following cases are representative of the contacts made and serve to illustrate important issues highlighted by the study.

Low Concentration Emissions. A number of sites were searching for an economical control technology for VOC emissions in concentrations below 100 ppm. These include streams from parts cleaning booths and room exhaust. While low in concentration, these sources often represent significant releases in terms of pounds per year and are currently receiving close scrutiny by government regulations. While carbon adsorption can clean up these streams, the cost is currently prohibitive in most cases.

Incineration. Several companies who were currently incinerating were interested in recovery technologies. Comments from these sources indicated that they recognized that incineration was not a long-term solution to air quality. Secondly, two users of catalytic oxidation were having problems with poisoning of the catalyst.

Solvent Substitutes. Water-based inks and cleaning agents are often cited as substitutes that may eliminate organic solvents in many processes. In fact, one printing company contacted had switched to water-based inks, and, in another case, a major radiator manufacturer was phasing out all organic solvents in favor of water-based cleaning processes. However, based on comments by these and other sites, the substitutes are expensive and can affect product quality. One printer of cereal boxes stated that the duller colors associated with water-based inks were not acceptable. The investment in new equipment to deliver the water-based inks is also significant. This is even more true for the substitution of water-based cleaning agents, where, according to the radiator manufacturer, the cost in new equipment would be prohibitive for the small- or medium-size manufacturing company.

Carbon Adsorption with Steam Desorption. The concept of inert gas desorption was very appealing to a number of carbon bed users, since it would eliminate the necessity of distilling the solvent. One company who was recovering R-113 by steam desorption was also interested in eliminating the contamination of the Freon by water, which can form acids.

Regulations. While a number of sites were feeling increasing concern about future regulation, most made it clear that little money would be spent to reduce current emissions until they were regulated to do so.

Letters of intent were executed with three sites interested in the initial field tests. Most viewed this as a way to become familiar with a technology that might be needed in the future. The short list of host site candidates selected for DOE approval is presented in Table 2-4.

Table 2-4. Host Site Candidates

Business	Solvents	Emissions (lb/yr)	SLA Flow (cfm)	Approximate Concentration (ppmv)	Operating Hours Per Year
Radiator Manufacturer	VM&P Naptha TF R-113	284,000 56,000*	16,000 600	320 3000	4000 4000
Textile Coating	Mixture (55% Toluene, 15% Methyl Ethyl Ketone, 20% Isopropyl Alcohol)	1,200,000	17,000	450	6000
Aluminum Extrusion Painting	Mixture (Xylene, Naptha, Toluene, Butyl Carbitol)	20,000	18,000	Unknown	2000

*Currently being recovered by carbon bed steam desorption. Interested in inert gas desorption.

90TR7

3.0 TURBOMACHINE DESIGN BASIS

The objective of the Phase I design effort was to develop a commercially attractive, advanced heat pump for the recovery of industrial VOC solvents. To this end, MTI's technical approach was to improve upon existing Brayton-cycle solvent recovery technology via the implementation of a unique turbomachine design that offered significant advantages over previous hardware implementations of the Brayton cycle. These advantages include superior energy efficiency; installation flexibility (low weight, small size, and variable capacity); and lower installation, operating, and maintenance costs.

The unique turbomachine design developed by MTI features a high-speed electric motor, Brayton-cycle compressor and turbine on a common shaft supported by gas bearings. This single rotor machine reduces production costs by eliminating additional compressor stages, gearboxes, and oil lubrication systems. The use of gas bearings provides increased reliability with lower operating costs due to the reduced parasitic losses and maintenance requirements.

The advanced Brayton-cycle system incorporating the integrated turbocompressor is shown schematically in Figure 3-1. As shown, the SLA mixture from the process is first precooled to reduce compressor work. After exiting the compressor, the SLA mixture is sequentially cooled as it passes through a cooler, regenerator, and VOC condenser, sequentially cooled as it passes through a cooler, regenerator, and VOC condenser,

VOC = Volatile Organic Compounds

SLA = Solvent Laden Air

881283

Figure 3-1. Baseline Solvent Recovery Heat Pump Schematic

such that the temperature drops below the dew point required to condense the solvent. The gases, which are still at elevated pressure, are then expanded through the turbine. This generates power to drive the compressor impeller, which is mounted on the same shaft. The expansion process lowers the temperature further, causing further condensation of the solvents. The condensed solvents are separated from the gas stream after exiting the turbine. The solvent-lean air is returned to the process through the regenerator, where a portion of its original heat content is restored. Located between the turbine and the compressor, the motor provides the balance of the power required to drive the compressor.

Because the intent of the program was the near-term "productization" or commercialization of this equipment, the strategy was to develop the turbomachine using components of existing design and in production for other markets. This approach eliminates the significant development risk and cost that would otherwise have been spread over the relatively small number of units initially produced. Using this strategy, the turbomachine design procedure required the early establishment of the capabilities and limitations of existing key components, including compressors, turbines, and high-speed motors. It was also necessary to establish a model that could predict system performance using the performance characteristics of available component options. These tools were then used to establish an optimized turbomachine design that provided maximized performance and flexibility when combined with the balance of plant equipment for application to site-specific solvent recovery.

Figure 3-2 presents a flow chart depicting the relationships between the tasks of the Phase I design effort. As shown, the focal point was the establishment of the system model that was used initially to evaluate component requirements. As the program progressed, this model was continually upgraded to reflect the performance of the system with the selection of specific components. This, in turn, allowed further refinement of the model and evaluation of system performance on applications. The system design guide, which supplied system definition and component specifications, was heavily dependent upon the use of this model.

Developed from the model output, Figure 3-3 shows the relationship between the optimum turbomachine speed and flow for a variety of system pressure ratios (PR). Because the temperature reached at the turbine outlet is dependent upon pressure ratio, the design requirements for a specific application define both the pressure ratio as well as system flow. These two criteria then established the required motor speed and horsepower based on optimal aero performance. Within this application envelope, the design basis for the turbomachine was most heavily influenced by the available performance in commercial high-speed motors. A variety of motor types were initially considered as candidates for integration with the existing aero components. The evaluation covered the complete envelope (50 to 400 hp) shown in Figure 3-3; however, the effort was focused on motors between 75 and 150 hp. This range was chosen because it was most compatible with available aerodynamic components.

The objective of the motor performance evaluation was to establish the relationship between performance, commercial availability, and cost for use in the optimization of the turbomachine design. To assist in this evaluation, consultants were used to extend the scope of the review beyond areas where MTI had design experience and expertise. The results of the motor evaluation were reported to DOE in MTI Report 89TR11 (Task 2.1, letter report).

891749(N)

Figure 3-2. Relationship Between Tasks of Phase I Design Effort

891800

Figure 3-3. Relationship Between Turbomachine Speed and Flow for Various System Pressure Ratios

The evaluation considered permanent magnet, synchronous, homopolar inductor, round rotor synchronous, and squirrel cage induction motor types. The report concluded that the squirrel cage induction motor offered the best capability of achieving the desired performance with an existing commercial offering. Also, in the event that enhanced performance was required, this motor type could achieve higher performance levels with minimum modification. The report further concluded that although the theoretical performance of alternative motor types also met the requirements, their development cost far exceeded those of the squirrel cage induction motor.

The sizing of the Brayton-cycle turbomachine was established by overlaying the performance of existing Air Products and Chemicals Incorporated (AP) compressor and turbine designs with the performance of a commercially available squirrel cage induction motor. It was found that a good performance match existed between the motor and existing aero hardware at system flows ranging downward from 2600 cfm and compressor pressure ratios of 2.5 and below. Higher flows and pressure ratios would require scaleup of the aero hardware or implementation of a more costly, nonstandard, solid-rotor design rather than the "off-the-shelf" laminated induction rotor.

The selection of the design flow rate for the Brayton-cycle turbomachine was also influenced by the results of the NYS application survey. As described in Section 2.0, this survey showed that the predominance of the solvent recovery applications in NYS existed at low concentrations of VOC solvents and that these applications were not economically handled by Brayton-cycle technology without the use of a concentrating carbon bed adsorber. The design basis for the turbomachine developed under this

project was established based on the fact that 2500 cfm was the largest flow rate achievable with existing aero components combined with available motors. This flow rate was determined to be compatible with 80% of NYS application when combined with solvent concentrating adsorbers. The normal operational envelope of the Brayton-cycle turbomachine was then defined as shown in Table 3-1.

Table 3-1. Brayton-Cycle Turbomachine Operational Envelope

Compressor Inlet Temperature	+90 to +100°F
Turbine Inlet Temperature	+30 to -60°F
Compressor Pressure Ratio	2.1 to 2.4
Operational Speed	19,000 to 21,000 rpm
Required Motor Horsepower	100 to 140 hp
Solvent Condensation (in Turbine)	0 to 3% (by Weight)

90TR7

4.0 PRELIMINARY TURBOMACHINE DESIGN

This section describes the mechanical configuration, preliminary layout, and performance of the Brayton-cycle turbomachine. A detailed discussion of the gas bearing system design is also included.

4.1 Mechanical Configuration

Analysis showed that the use of available two-pole squirrel cage induction motor construction in the double-ended Brayton turbomachine tended to produce a flexible shaft rotor with the third critical (bending) speed near the desired operating point. The reason for this machinery rotordynamics problem was that the standard laminated rotor construction did not contribute significantly to the stiffness of the shaft.

The means available to increase the third critical speed of the operating range included:

- Reduce the weight
- Reduce the shaft length
- Increase the shaft diameter.

Corrosion resistance and material compatibility with a wide range of solvents at low cost was a design requirement. Therefore, it was determined that the machine design should include the heavier stainless steel impellers (more costly titanium and less corrosion resistant, less costly aluminum were considered as special-case alternatives). The design was therefore adjusted to achieve conservative rotordynamics using minimum shaft length and maximum shaft diameter. This resulted in the selection of a four-pole motor design. At the same speed, the four-pole design requires twice the input frequency of a two-pole motor and tends to incur high stator iron-core losses. However, because of its superior flux utilization, the four-pole motor can accommodate a larger diameter shaft at the same power and speed rating.

Figure 4-1 is a critical speed map of the final rotor configuration with stainless steel impellers. As shown, the final design obtained a conservative 30% margin between the normal operating speed (approximately 20,000 rpm) and the third critical (bending) speed of 28,000 rpm. The shaft diameter required to achieve this margin was 3 in., with minimized shaft length allowances for seals, bearings, and active motor rotor length.

Although the relationship of operational speed to the first bending critical is primarily a function of rotor stiffness and is essentially constant, the relationship of operating speed to the first and second critical speeds (rigid body criticals) is primarily a function of bearing stiffness and thus a function of bearing type. For this reason, a compliant foil gas-lubricated bearing system was selected. Ball and rolling element bearings have typical stiffnesses in the 1 to 3 million range. As shown on Figure 4-1, this would have posed potential problems with the first and second critical speeds. Also, with the 3-in. shaft diameter required to achieve the third critical speed margin at the 20,000-rpm operating speed, rolling element bearing DN values exceeded 1.7 million, indicating a poor life expectancy with this bearing type.

891823

Figure 4-1. Turbomachine Critical Speed Map

Oil-lubricated fluid-film bearings were evaluated and found to have a severe shortcoming in terms of power consumption. Because of the large shaft diameter, oil bearing losses would have added 27 kW to the motor requirement, which would otherwise require a 82-kW drive for aerodynamic power consumption and other mechanical losses. Other shortcomings include more complex seal and oil and loop configurations.

4.2 Preliminary Layout

A cross-sectional view of the turbomachine assembly developed during Phase I is presented in Figure 4-2. The machine is designed for vertical rotor operation with the turbine on the bottom. This design facilitates drainage of condensing solvent and allows the rotor weight to be offset by the upward aerodynamic forces developed by the compressor and turbine impellers.

The turbomachine design is based on an AP ETAC-9 "Compander," a single spindle, 9-in. diameter turbine impeller driving a 13-in. diameter compressor. The compressor and turbine impellers are machined from one-piece castings. The impellers are attached to the high-speed rotor by a preloaded tie bolt and located relative to the shaft by axial and radial pilot surfaces. The impellers are first balanced as components, then trim balanced upon final assembly of the high-speed rotor.

For the solvent recovery application, machining of the turbine impeller casting will be adjusted to provide an optimized flow cut for the design pressure ratio and flow. Combined with field-adjustable variable area nozzles (VANs), this flow cut achieves high turbine efficiency over the machine's anticipated operating range. With the exception of the turbine shroud and diffuser, which are modified to match the turbine impeller, the

90157

Figure 4-2. Cross Section of Preliminary Layout of Brayton-Cycle Turbomachine

balance of the aerodynamic components are anticipated to be used with little modification from the ETAC-9 design. This use of previously designed, manufactured, and performance-verified components benefited the turbomachine design effort, allowing a significant reduction in the efforts associated with stress and thermal analyses, as well as blade loading, vibration, and aerodynamic performance. Future benefits can also be expected in manufacturing due to the use of an existing design.

The compressor and turbine are separated from the bearing/motor cavity by noncontacting labyrinth seals. The motor cavity is continually purged with dry air at low pressure. The flow path for the purged air allows the air to both purge and cool the gas bearings prior to exhausting to atmosphere in the labyrinth seals. On the compressor end, the seal consists of a double labyrinth seal with common intermediate vent for both motor and compressor ends. This vent flow is returned to the compressor inlet. On the turbine end, the labyrinth sealing arrangement consists of three labyrinth sections. In the first section, a buffer gas from the turbine inlet is heated and used to prevent icing of the turbine and seal (see Figure 4-3). In the second section, the heated gas enters the manifold between the turbine and seal and prevents solvents from entering. In the third section, on the bearing side of the buffer manifold, the seal arrangement is identical to that used on the compressor end. A double labyrinth seal with intermediate vent prevents solvent-contaminated air from entering the bearing/motor cavity and also provides an exhaust point for the low-pressure bearing/motor purge flow.

Figure 4-3. Turbine End Labyrinth Seal Arrangement

The journal bearings are located directly inboard of the labyrinth seals and the double-acting thrust bearing assembly is located at the compressor end (top end) of the rotor. The thrust bearing has been designed for aerostatic thrust assist on rotor start and stop, which will eliminate wear in the absence of the aerodynamic film created during low-speed rotor rotation. The design and operation of the gas bearing system is described in detail in Section 4.4.

The high-speed, squirrel cage induction motor is straddle mounted between the journal bearings. The selected motor is a commercially available, "partial motor" set consisting of two components: an electromagnetic stator and a laminated squirrel cage rotor. Motors of this type are frequently called shell-type motors and are manufactured for OEM applications such as machine tools, spindles, boring machines, routers, grinders, pumps, and compressors. The motor consists of an 8-in. diameter stator shell with special low loss, high silicon, electrical steel laminations. These thin laminations reduce the stator iron losses, which would otherwise be high at the 700-Hz input frequency. The stator shell contains a helical passage for cooling water flow. Water cooling of the stator is necessary because of the high power density of the motor. This motor is approximately the same physical size as a 1750-rpm motor rated at 6 hp. Pertinent design parameters for the motor are:

- Motor type: Four-pole, squirrel cage induction
- Motor classification: NEMA B design
- Starting torque: 120% full load
- Cooling: 13-gpm water at 100°F inlet
- Electrical: 460 V, 3 phase, 700 Hz.

The motor rotor is a precision cast, laminated design with a 3-in. diameter bore. The rotor is attached to the shaft via an interference fit. In the current design, it is the mechanical integrity of the laminated rotor that limits turbomachine speed, pressure ratio, and flow. Although analysis indicates that the laminated rotor design will not unduly limit the turbomachine application, all aspects of the current turbomachine design (i.e., rotordynamics, bearing, motor stator, and aero components) would remain unchanged if it were desirable to increase performance. This could be achieved through the use of a more expensive solid rotor. Such designs exist in the frame size required and could provide an approximate 25% increase in speed, flow, and pressure ratio at the expense of an increase in manufacturing cost.

4.3 Turbomachine Performance

The Brayton-cycle turbomachine performance is dependent upon aerodynamic component efficiency and motor efficiency, as well as bearing, windage, and other parasitic losses. A system flow of 2200 acfm was selected as a nominal design basis. The design compressor pressure ratio of 2.25:1 and the design turbine pressure ratio of 2:1 allow for a 10% system pressure loss. Because of the wide variety of solvent recovery applications anticipated, the preliminary design phase evaluated turbomachinery operation over a wide performance range. Expansion efficiency most directly impacts Brayton-cycle refrigeration performance because higher expansion efficiency not only returns more power to the shaft but also provides lower exhaust temperatures by removing more energy from the expanding gas. The expected performance of the

turbine, expressed in terms of air equivalent parameters, is presented in Figure 4-4. Estimates show that less than a 2% variation in the design's 82% expansion efficiency over a $\pm 15\%$ range of turbine mass flow can be expected because of turbomachine's ability to control both speed and VAN area.

90158

Figure 4-4. Turbine Efficiency versus rpm

The compressor is designed for high efficiency at low specific speed and is ideally matched to the speed requirements and limitations of the turbine and motor, respectively. (The compressor is a 13-in. open centrifugal impeller with radial blading and a vaneless diffuser.) The expected performance of the compressor is shown in Figure 4-5. At the design flow of 317 lb-mol/hr and a pressure ratio of 2.3, the compressor efficiency is 82%. In normal operation, the compressor speed is controlled by motor frequency while compressor flow and head are trimmed by turbine VAN adjustment. With these adjustments, high efficiency can be maintained with conservative surge margin on the compressor.

The high-speed motor and gas bearing system are integral components of the turbomachine and contribute to its performance. The motor must be capable of delivering the differential power required to drive the compressor and overcome mechanical losses when combined with the power developed by the turbine. As discussed in Section 4.4, the use of gas bearings minimizes the parasitic bearing losses. For the purposes of developing the motor-required horsepower, gas bearing losses were taken at 1.5 hp at a design maximum speed of 21,000 rpm. Therefore, rotor windage losses became the predominant parasitic loss and were calculated to be 5.6 hp at this nominal design speed.

90161

Figure 4-5. Compressor Performance Map

The squirrel cage induction motor is essentially a constant torque machine if a constant volts-to-frequency ratio is maintained as speed is increased. At constant torque, horsepower increases in direct proportion to rotor rpm. The limits of the machine are reached when either the rotor reaches maximum allowable stress (speed) or the motor heat rejection limits are reached and maximum temperature rise occurs. For the water-cooled stator housing with Class H insulation at the laminated rotor speed of 21,000 rpm, the motor is rated at 140 hp. As discussed earlier, higher speeds and, consequently, higher power levels are achievable through the use of a solid rotor of the same physical dimensions. The solid rotor simultaneously raises the rotor critical speed, allowing higher rotational speeds and motor power levels.

Through adjustment of motor speed and turbine VAN area, the performance of the turbomachine can be matched to the solvent recovery application requirements providing the desired state points and flows. Turbomachine performance at the nominal system design basis of 317 lb-mol/hr (2200 acfm) and a compressor pressure ratio of 2.25:1 is shown in Table 4-1. Full utilization of rated motor performance could be achieved at 370 lb-mol/hr flow (2600 cfm) and a compressor pressure ratio of 2.5. At this point the motor would be providing 140 hp at 21,000 rpm.

Table 4-1. Performance at Nominal Design Conditions

Design Conditions and Aerodynamic Performance

Design Conditions	Compressor	Turbine
Pressure In (P_{in} , psia)	14.5	30.125
Temperature In (T_{in} , °F)	+100	+0
Pressure Out (P_{out} , psia)	32.6	16.4
Temperature Out (T_{out} , °F)	+277	-60.47
Flow (lb-mol/hr)	317.5	317.5
Power (hp)	154.4	52.0
η	82.0	82.0
Gas	Air	Air
Outer Diameter	13.0	7.65
rpm	19,650	—

Mechanical Performance

Bearing Losses ~ 1.5 hp
Motor Rotor Windage = 5.6 hp
Net Required Horsepower = 109.5
Available Horsepower at 19,650 rpm = 131
Motor Efficiency = 90% at Full Load

90TR7

4.4 Gas Bearing System

This subsection provides a detailed discussion of the gas bearing system design.

4.4.1 Gas Bearing Theory

A self-acting or, as commonly known, hydrodynamic type of gas bearing operates in a similar manner to a hydrodynamic oil bearing except that gas provides the fluid support film. With this bearing type, load support is generated from the relative rotation of the rotor and bearing surfaces. As shown in Figure 4-6, this produces a pressure wedge between the converging surfaces of the offset rotor in the journal bearing and from the tapered inlet or ramp region of each pad of the thrust bearing. The effectiveness of the load support is a function of many variables which include bearing size, geometry, clearance, speed, gas viscosity, and ambient pressure.

Figure 4-6. Load Support for Journal and Thrust Bearings

Being self-acting and having no residual oil film to separate the bearing/rotor surfaces, the gas bearing system starts and stops with direct surface-to-surface sliding contact. This necessitates the provision for low friction and wear-resistant surfaces.

Much of the early experience with gas bearings utilized bearings with rigid members and surfaces. These presented some problems or limitations in high performance turbomachinery and led to the development of compliant surface bearings. Compliant bearings, dating from the late 1960s, utilize thin metal foil materials in their construction and overcame many limitations. The MTI Hydresil™ designs proposed for this application are in this category.

In its simplest form, the Hydresil journal bearing consists of two foil parts mounted in a sleeve: a smooth top foil that provides the bearing surface, and a flexible "bump" or spring foil that provides controlled resilient support to this surface (see Figure 4-7a). The smooth foil operating surface is usually coated for the reasons previously discussed, and micromotions between contacting foils and the foil-to-sleeve surface when the machinery is operating generate Coulomb frictional damping forces beneficial to controlling rotor excitations. It is evident that by varying the pitch of the bumps and the foil thicknesses, the mechanical stiffnesses of the bearings can be selectively designed.

The Hydresil foil thrust bearing shown in Figure 4-7b follows the same basic design principles described above.

4.4.2 Advantages of Gas Bearings

In the solvent recovery application, there are significant advantages in the use of gas bearings as compared to oil bearings. Several unique characteristics of the compliant foil gas bearings provide additional benefits. Basic gas bearing advantages include:

- Elimination of the oil system and associated critical seals
- Lower frictional power loss at high speed
- Higher achievable operating speeds and a more compact machine
- Reduced high and low temperature sensitivity
- No long-term storage or downtime problems.

a) Typical Details of Foil Journal Bearing

b) Pad Operation of Foil Thrust Bearing

V92-127

Figure 4-7. The MTI Hydresil™ Compliant Foil-Type Air Bearing

The additional benefits of the compliant foil bearing over the rigid surface gas bearing include:

- Reduced sensitivity to dirt and thermal distortions
- Greater load capacity for a given bearing size
- Greater tolerance to shock loads and misalignment
- Increased high-speed rotor stability margin
- Lower cost in volume manufacturing.

4.4.3 Design Parameters

A matrix of interacting variables in the bearing/rotor system have to be addressed in order to reach an optimized, complete design. Several MTI-developed computer codes pertaining to bearing designs, rotordynamics, stability review, and thermal-mechanical analysis are used in this process.

The journal bearing size and characteristics are selected to match the high-speed operating loads, start-stop coating loading, a diameter that will ensure adequate rotor stiffness, and a bearing stiffness that will ensure favorable critical speeds. Journal bearing loads normally considered are a vector summation of rotor weight, electrical and aerodynamic side pull, and unbalance and shock or dynamic load (such as on a moving vehicle), as discussed in Section 4.4.4. The interplay between journal bearing characteristics, critical speeds, and rotor stability margin is discussed in Section 4.4.4.

The thrust bearing design is handled in a similar manner with a summation being made of mechanical and aerodynamic thrust loading and start-stop loadings. The bearing is sized to provide the smallest acceptable outside diameter compatible with the loads in order to minimize viscous shear frictional heat and power loss and to achieve thrust runner accuracy and minimum cost. The stiffness of the thrust bearing is engineered to control rotor float, which affects the sealing efficiency of the aerodynamic blading in the housings, and to favorably position the "bounce" frequency of the bearing/rotor system relative to the speed range. The thrust bearings consist of an opposed pair, since the loading reverses between starting and operating speed.

A thermal-mechanical stress review of the bearing/rotor system provides information on rotor, bearing, and housing dimensional changes and their effects on bearing clearances, alignment, and distortions. This permits an estimate of the quantity of cooling flow required and establishes the best cooling paths or insulation arrangements to minimize these effects.

In arriving at the selected preliminary design, several bearing/rotor configurations were considered. The selected configuration, with the rotor vertical arrangement as shown earlier in Figure 4-2, is discussed in the following subsection in terms of resultant bearing loadings.

4.4.4 Selection of Bearing Configurations and Load Analysis

As a result of an iterative review of bearing loadings, rotordynamic, and other machinery requirements, the preliminary bearing size selection was made. One important factor influencing the bearing design was the attractiveness of having a vertical rotor arrangement with the turbine at the lower end as shown earlier in Figure 4-2. This arrangement offered the following advantages:

- Prevented any solvent liquid residue in the turbine from entering the bearing section
- Provided the ability of opposing the full rotor weight against the aerodynamic thrust, thus reducing the thrust bearing loading or size
- Made it relatively easy to provide a jacking piston and pressure to relieve the rotor weight on the thrust bearing coating during starts and stops.

This vertical rotor arrangement resulted in lightly loaded journal bearings during high-speed operation. While seemingly attractive, at the same time, this also increases the rotor system's sensitivity to excitations. One method for counteracting this is to introduce a side load in the journal bearings by mounting the machine at a small tilt angle. Another machinery design feature used for stability reasons has been to ensure that the rotor center of gravity is beneath the thrust bearing plane to the greatest extent possible.

Because of the rotordynamic, rotor stiffness, weight distribution, and other fabrication and assembly considerations, the compressor end journal bearing is slightly larger than the turbine end bearing.

Figure 4-8 shows the preliminary concept arrangement for the compressor end bearing, which is typical for both journal bearings. It will be noted that this is a variation of the configuration shown in Figure 4-7a in that a three-pad design has been selected. This has been done because a multipad design has the inherent ability of minimizing cross-coupling disturbing forces in the gas film and provides a greater stability margin. The multipad bearing can also be made with greater accuracy in these larger sizes. As shown in Figure 4-8, provisions have been made for mounting the journal bearing

Figure 4-8. Preliminary Concept for Foil Journal Bearing (Compressor End)

sleeve in static, compliant elastomeric O-rings. This method of mounting can offer an additional source of damping to the bearing/rotor system, increase its ability to handle rotor misalignments, and modulate any external shock loads. The stiffness/damping characteristics of the total bearing and mounting system are also engineered to ensure control of the total rotor motions in the stationary housings.

The thrust bearing, which is the most heavily loaded bearing because of the predominant aerodynamic loading, is sized in accordance with good design practice and experience coupled with limitations on tip speed of the runner and fabrication considerations. The preliminary design shown on Figure 4-9 has 10 similar pads. Figure 4-10 shows the operating gas film thickness as a function of load at design speed and points to the importance of the compliance of the foil parts and the need for accuracy and squareness in housing and rotor parts. To this end, the thrust runner is machined as an integral part of the rotor.

In the final design, the interplay of foil and total bearing stiffness against foil stresses will be evaluated to achieve the optimum design. Because of possible load reversal, the opposed thrust bearing is made in a similar size. Selection of the optimum bearing stiffness is also important in the dynamic sense since, in association with other rotor variables, it controls the bounce frequency and amplitude of the vertical rotor between the opposed thrust bearings.

Table 4-2 summarizes the weight loadings for the journal and thrust bearings during starts and stops and at design speed conditions. Since one method for introducing journal bearing loading at high speed with a vertical rotor is to provide a small tilt angle, this has been included in the table.

The journal bearing weight loadings for the rotor design at small angles of tilting are good in terms of the proven design practice of using about 2 psi on the foil coatings to give long service life under start-stop conditions. Loads are modest at high speed even with the tilt angle and remain so even when adding representative residue rotor unbalance loads of 1 to 2 lb per bearing.

The thrust bearing weight loading values are high for long coating life under start-stop conditions, but could be accepted for occasional emergency conditions. It is, however, relatively easy to reduce the loading to 2 psi by use of the air-actuated balance piston as is planned. When the system is operating at design speed, the aerodynamic loading (not included in Table 4-2) is dominant and opposes the rotor weight loading.

For example, with the machine at 15° tilt, the resultant thrust bearing loading becomes:

$$(350 \text{ lb aero} - 112 \text{ lb rotor weight}) = 238 \text{ lb (10.3 psi)}$$

This is considered to be good design practice, and the bearing should be satisfactory if this was to increase because the balance static pressure was accidentally left on.

4.4.5 Frictional Power Losses

The frictional power loss in a fluid-film bearing results from the viscous shearing of the film between the bearing and rotor surfaces. It is a function of several variables including fluid viscosity, bearing size and configuration, clearance, and relative velocities.

90153

Figure 4-9. Preliminary Concept for Foil Thrust Bearings

90150

Figure 4-10. Foil Thrust Bearing: Operating Gas Film Thickness as a Function of Load

Table 4-2. Rotor Weight Loads on Bearings

	Turbine Journal Bearing	Compressor Journal Bearing	Thrust Bearing
Bearing Size (in.)	3 Diameter x 2 Length	3.5 Diameter x 2.25 Length	7.0 Outer Diameter x 3.5 Inner Diameter
Effective Area (in. ²)	6	7.88	23

Loadings						
Tilt Angle	Turbine Journal Bearing		Compressor Journal Bearing		Thrust Bearing	
	lb	psi	lb	psi	lb	psi
Vertical	0	0	0	0	116	5.04
10°	6.2	1.03	13.9	1.76	114	4.96
15°	9.2	1.53	20.8	2.64	112	4.87
20°	12.2	2.03	27.5	3.49	109	4.74

90TR7

While the gas bearing is larger than an equivalent oil-film bearing of the same load capacity, the significant difference in fluid viscosity results in lower power loss in most cases. The calculated frictional power losses for the two journal bearings and opposed thrust bearings at 20,000 rpm as defined in Section 4.4.4 are:

Bearing Type	Horsepower
Compressor End Journal Bearing	0.135
Turbine End Journal Bearing	0.075
Loaded Thrust Bearing	0.710
Unloaded Thrust Bearing	<u>0.230</u>
	1.150

This value is obviously small compared to the motor power. There are additional frictional losses associated with the gas pumping of other rotor components, which will be greater. Since the bearing frictional power is generated directly in the gas film, the cooling air acts to remove it for reasons discussed below.

4.4.6 Cooling

The bearing system and motor assembly between the compressor and turbine impellers are supplied with a separately controlled source of clean, dry, pressurized air flow.

Pressure is maintained at a few psi higher than the system levels adjacent to this zone. The air flow serves several purposes:

- Prevents entry of solvent liquids or gases through the shaft seals into the bearing
- Provides additional cooling to the motor components (the major cooling is from an external water jacket)
- Provides a means of reducing the rotor weight loading on the thrust bearing with a pressure balance piston during the start-stop cycle
- Provides a cooling flow through the foil bearings.

The cooling air flow through the foil bearings removes the self-generated frictional heat to ensure long coating life, balances heat flow from other sources such as the motor to minimize misalignments and distortions within the bearings, removes coating wear debris from the bearings, and prevents entry of any rotor seal debris into the bearings. Representative cooling flows for the bearings for removal of the self-generated frictional heat total 32 scfm for a 100°F temperature rise in the bearings. Any additional cooling flow needed to balance other heat sources will be determined in a thermal review during the final design work.

4.4.7 Coatings

The operating surfaces of the top foils of the bearings and the matching rotor surfaces are provided with a coating or treatment. These provide low friction and wear resistance during the start-stop sliding contacts between bearings and rotor or during any instantaneous contact occurring at operating speed during a shock-type loading.

These coatings or treatments, in the form of proven, compatible "tribological" pairs, usually consist of a very thin (0.0001 to 0.0003 in.) soft coating on the foils and a harder treatment on the rotor. The rotor treatment increases hardness and reduces the potential of surface damage to the more expensive rotor system.

The required properties of the foil coatings include:

- Low coefficient of friction in sliding
- Easy to apply
- Strong adhesion and compatible with base material
- Impervious to environment
- Minimum generation of wear debris
- Maintain good finish in service for hydrodynamic efficiency.

The required properties of the rotor journal and thrust runner surfaces include:

- Compatibility with the selected bearing surface
- Easy to process or apply
- Hardness with capability for accurate and smooth finishing
- Repairability.

The selection of the tribological pair is very dependent on the specific requirements of the application and is based on MTI baseline data from dedicated friction and wear test rigs and on prior experience. It is estimated that 15,000 to 20,000 start-stop cycles of

operation will occur before equipment replacement is performed. Based on the design loading of 2 psi defined in Section 4.4.4, the tribological pair has been selected and consists of a proprietary MTI polyamide imide-type coating.

4.4.8 Issues for Final Design

In the above discussion, some of the issues that must be addressed in the final design phase have been highlighted and the general approach to be followed for many of them defined. Some of the more straightforward issues include:

- Ensuring bearings have satisfactory load performance
- Providing adequate foil coating life
- Minimizing friction power losses
- Ensuring a rotor of required stiffness, high-speed integrity, and accuracy
- Providing optimized bearing cooling flows and paths
- Commonality of bearings for minimum costs
- Controlling bounce frequency and amplitude of rotor on thrust bearings.

Particular attention in the final design will be directed at a complete dynamic review of the journal bearing/rotor system to ensure adequate stability margin against possible excitation sources. These sources can be forces from the aerodynamic flow paths, flow through seals, and self-induced forces from within the gas film of the bearings. High-speed bearing/rotor systems operating at several multiples of the first rigid body critical speed are particularly prone to excitation of the rotor, where the first or second rigid body critical speed may appear as a subsynchronous frequency motion at operating speed.

As discussed in Section 4.4.4, particular care is required with vertical rotor machines that have lightly loaded journal bearings and, consequently, concentrically operating journals. Possible ways of providing a stabilizing side load in the bearing include:

- Bearings designed with internal preload
- Tilting the machine to provide a small radial load component
- Providing an electrically or pneumatically induced radial load.

Of these options, the first will be given priority in the design, and, as discussed, the multipad foil bearing with its inherently good stability characteristics will be used.

Damping mechanisms can come from three sources: squeeze action in the bearing gas film, enhanced Coulomb friction generated from interaction between specially treated foil members in the bearings, and from external mountings such as O-rings. All of these features will be addressed when optimizing the design.

5.0 PRELIMINARY SYSTEM DESIGN

This section provides a description of the preliminary design of the solvent recovery heat pump system, including a discussion of the system and equipment alternatives that were considered in the design process.

5.1 System Alternatives

The solvent recovery heat pump system is quite flexible and can be utilized in a variety of application configurations. Because the process recovers solvents via condensation, the dew point temperature of the vapor gas mixture strongly influences the selection of the best system configuration. The dew point temperature of a vapor/gas mixture is primarily a function of the vapor concentrations. Another consideration in establishing the system configuration is the flammability limits of the solvent, expressed as the LEL. If the concentration of the solvent exceeds 50% LEL, insurance underwriters insist that an inert carrier gas must be used to convey the mixture.

The system may be designed as an open-loop or closed-loop (recycling the gas back to the application) process. An open-loop configuration must condense at much lower temperatures to minimize the solvent concentration discharged to ambient. In general, closed-loop processes operate with higher solvent concentrations, thereby recovering more solvent for the amount of gas handled. The NYS application survey conducted by MTI showed that the majority of NYS VOC solvent emissions are found in open-loop air streams at low concentrations.

One option that extends the application range and improves the economics of the heat pump at low concentrations is to interface it to the emission source through a solvent-concentrating adsorber. Such a system can be implemented to run on a continuous basis with a molecular sieve as shown in Figure 5-1, or in a batch desorption process such as an activated carbon bed as shown in Figure 5-2. Although there are no hard and fast rules with regard to the application of the heat pump with or without a solvent concentrator of a given type, it is possible to make some fairly accurate generalizations based on the concentration levels of solvents in the exhaust process stream.

Direct application of the heat pump for solvent recovery without concentration is most competitive when combined with a continuously operating, closed-cycle solvent evaporation process where the solvent concentrations entering the system are in excess of 5000 ppm typically (40% LEL). Rotary absorbers and/or molecular sieves are best suited for concentrating solvents by a factor of 2 to 4:1. They may be used in conjunction with both open- and closed-loop application processes. Because of the difficulties of maintaining seals on a rotating continuous media, current designs are probably best suited for nonflammable solvents or for use in conjunction with flammable solvents initially in concentrations of 5% to 25% LEL and then concentrated to a maximum 50% LEL value. Fixed-bed adsorbers, typically of the activated carbon type, are best suited to solvent concentrations below 10% LEL. They are also well suited to applications with intermittent or noncontinuous solvent emissions at much higher levels.

881112

Figure 5-1. Solvent Recovery Heat Pump System Used with Molecular Sieve VOC Solvent

881113

Figure 5-2. Solvent Recovery Heat Pump System Used for Carbon Bed Desorption

By appropriate sizing of a batch-type solvent adsorber, the interval between desorption increases such that the solvent recovery system can be shared between many applications. With such a concept, the system becomes "mobile" and is periodically brought to the fixed location of the adsorber for desorption. In general, this concept is applicable for sources emitting less than 4000 lb of solvent per day, either by virtue of low concentrations and high gas volume or intermittent emissions at higher concentrations.

Table 5-1 summarizes the relationship between source emission solvent concentration and the most competitive means of interfacing the solvent recovery heat pump to the source. The solvent recovery heat pump system with its Brayton-cycle turbomachine can be common to each of the applications listed, giving this equipment wide flexibility in application. The system type found to be most compatible with NYS solvent emissions applications was a mobile system for batch desorption. The Phase I preliminary design was therefore based on this application concept.

Table 5-1. Optimized Brayton-Cycle Heat Pump Applications

	Stand-Alone Brayton-Cycle Heat Pump	Heat Pump with Continuous Concentrator	Fixed Heat Pump for Parallel Bed Desorption	Mobile Heat Pump for Infrequent Bed Desorption
Best Application Type	Closed Loop	Closed or Open Loop	Open Loop	Open Loop
VOC Emissions (lb/day)	>2000	>2000	>1000	<2000
Emission Source Operation	Continuous	Continuous	Continuous or Intermittent	Continuous or Intermittent
VOC Concentration Level (ppmV)	>5000	1000 to 5000	<1500	<1000

90TR7

5.2 Heat Pump Alternatives

Closed-loop solvent recovery, whether a direct process-connected type or the type involving a solvent concentrator, requires a supply of heat to vaporize the solvent and, simultaneously, a supply of refrigeration for solvent condensation and recovery. The extent to which the heat pump alternatives meet this requirement is discussed below. During the Phase I effort, several heat pump equipment configurations were evaluated for closed-loop operation. The final system design was the result of trade-off analysis and competitive comparison of heat pump options. Two important heat pump configuration comparisons were:

- Electric versus thermal engine-driven systems
- Brayton-cycle versus combined Brayton-Rankine cycle (multiple level) refrigeration systems.

The following subsections describe this evaluation and the resulting selection of an engine-driven/combined Brayton-Rankine cycle system as the preferred configuration for closed-loop solvent recovery.

5.2.1 Electric versus Thermal Engine-Driven Systems

Figure 5-3 shows a comparison between energy balances for Brayton-cycle solvent recovery systems powered by electric energy and thermal engine-driven systems. For both cases, it is assumed that the application requires 804,000 Btu for desorbing the concentrator (volatilization of the solvents) and a simultaneous 114,000 Btu of refrigeration for condensing the solvents. Because the thermal engine-driven system provides for cogenerated use of the rejected engine exhaust and water jacket heat, this system shows a 40% advantage in fuel consumption. In a closed-loop oven operating continuously, this advantage represents a significant operating cost differential. When applied to a closed-loop batch desorption process, the engine-driven system provides an additional advantage by eliminating the electrical demand charge associated with the intermittent use of a high horsepower electric motor. The cost of a commercially available 150-kVA electronic power converter to drive the high-speed motor is \$26,000 for small quantities.

Because most of industrial solvents are combustible, it is usually necessary to provide an inert carrier gas for their transport if the concentration is expected to reach levels of 50% LEL. In the case where an inert gas is required, the engine-driven system can provide this carrier gas from the engine exhaust. The use of the engine exhaust for system inerting eliminates the need for a separate and costly inert gas generating subsystem.

5.2.2 Multiple-Level versus Single-Level Refrigeration Systems

In a typical solvent recovery application, the desired turbine exhaust temperature might be -100°F. The cooling of the solvent-laden gas to this temperature is achieved with a combination of refrigeration (gas expansion) and recuperative heat transfer. Only the sensible portion of the thermal duty can be handled by the recuperation of heat with the returning, cold carrier gas. The additional heat load associated with the condensing vapors must be handled by active refrigeration because the returning dry carrier gas has inadequate heat capacity.

In the Brayton refrigeration cycle, the amount of temperature drop across the turbine is dependent upon the pressure ratio developed by the compressor. As the solvent or water vapor latent heat load increases, there is a proportional increase in the Brayton-cycle work required to handle this refrigeration load and maintain the same exhaust dew point temperature. Figure 5-4 shows the relationship between increasing inlet concentration of methylene chloride solvent and the pressure ratio (compressor power) required to achieve outlet solvent concentrations of 700 ppm and 3000 ppmv. Also shown in Figure 5-4 is the impact of water vapor on required pressure ratio and resulting motor horsepower.

Refrigeration-cycle thermodynamic analysis shows that the power required to produce a unit of refrigeration (capacity) is proportional to the temperature difference between the available heat sink and the source to be cooled. That is, the lower the minimum cycle

Thermal Engine-Driven System

Electric System

891748(N)

Figure 5-3. Comparison of Electric versus Thermal Engine-Driven Systems

90160

Figure 5-4. Brayton-Cycle Pressure Ratio versus Inlet Concentration of Methylene Chloride Solvent

temperature, the higher the power requirements per unit of refrigeration capacity. There are differences between the power requirements of the Brayton cycle and conventional reverse Rankine refrigeration both in terms of sensitivity to cycle temperature difference and actual power requirements. Figure 5-5 shows the relative power requirements per unit of refrigeration capacity for both reverse Brayton (air cycle) and reverse Rankine refrigeration as a function of minimum temperature achieved. From Figure 5-5, it can be seen that although reverse Rankine refrigeration has only a 30% advantage over Brayton refrigeration in power consumption at a temperature of -100°F, the advantage in reverse Rankine refrigeration at a temperature of 20°F is nearly 400%.

This significant efficiency advantage with reverse Rankine refrigeration can have a major favorable impact on the performance of a solvent recovery heat pump system when that system is applied to exhaust streams having high concentrations of VOC solvents or water vapor. The reason is because the refrigeration load associated with high concentrations of solvents occurs at high dew point temperatures. Of course, the refrigeration load associated with condensing water vapor occurs almost completely at dew points above 32°F. By taking advantage of the fact that this refrigeration load exists at higher

Energy Requirements (Rejection to Heat Sink at 95°F)

All Heat Exchangers = 80%

Rankine Compressor = 80%

Air Cycle $\eta_c = 82\%$ - $\eta_t = 83\%$

90166

Figure 5-5. Comparison of Refrigeration Cycle

temperatures and using reverse Rankine refrigeration to handle this refrigeration load at the elevated temperature, a significant system energy advantage can be achieved. For example, in an exhaust stream, with a 40% LEL solvent concentration and a 70% relative humidity (70°F dry bulb), roughly 50% of the refrigeration load occurs at temperatures above -20°F. In this case, the use of an intermediate temperature reverse Rankine refrigeration system to handle this load with a -30°F evaporator temperature provides nearly a 40% reduction in required system energy usage over the alternative of handling all of the refrigeration load at -100°F with Brayton refrigeration.

5.3 Process Flow Diagram

A process flow schematic of the solvent recovery heat pump system is shown in Figure 5-6. Solvent-laden air is cooled to 100°F in a heat exchanger (HX1) prior to entering the Brayton compressor. Typically, a mixture of solvent vapors and water is present. The baseline process inlet conditions are taken as 2200-cfm flow, which consists of 9372 lb/hr air, 138 lb/hr methylene chloride, and 100 lb/hr water vapor. Operating at 19,600 rpm, the turbomachine compresses the mixture to 33.4 psia and a temperature of 275°F. A high-temperature recuperative heat exchanger (HX2) cools the compressed gas to 100°F, using the solvent lean gas returning from the cold solvent condensation process. The lean gas is heated to 220°F in heat exchanger HX2 prior to returning to the process for additional solvent vaporization.

90164

Figure 5-6. Process Flow Schematic of Solvent Recovery Heat Pump System

In the intermediate temperature heat exchanger (HX3), the solvent-laden compressed gas is cooled to 15°F, removing via condensation and frosting the majority of the water vapor present (see section 5.6.3 for a discussion of water vapor and frost). To handle the large latent loads associated with water vapor in normal ambient relative humidities, both reverse Rankine refrigeration combined with cold (-20°F) solvent lean gas returning from a low-temperature heat exchanger (HX4) are employed. As shown, the reverse Rankine system is incorporated in a recirculation side stream of the returning solvent lean gas, typically cooling the dry gas from 40°F to -15°F. Although the fixed surface evaporative coil operates at -20°F, no frosting occurs because the gas has a dew point of -110°F, having previously completed the expansion process.

The low-temperature heat exchanger (HX4) cools the compressed solvent-laden gas from -15 to -60°F, utilizing the -110°F gas exiting the Brayton-cycle turbine. Solvent is condensed on the compressed gas side of heat exchanger HX4 as well as in the expansion process. Solvent separator S1 is designed to prevent expander erosion by eliminating droplets larger than 5 micron from entering the turbine. Solvent separator S2, a cyclone separator and coalescing filter, collects the condensed solvent vapor from the turbine exhaust.

Table 5-2 shows the baseline process conditions of pressure, temperature, and vapor concentration at the 19 process points shown in the process flow schematic of Figure 5-6. In this baseline case, the 2200-cfm system recovers methylene chloride at 95% efficiency and simultaneously separates water vapor. For this case, water vapor was assumed to enter the system at the rate of 100 lb/hr. (This is the equivalent of 90% relative humidity at a room temperature of 70°F.) At these solvent and water vapor loading conditions and a system pressure ratio of 2.3, a turbine outlet temperature of -108°F is achieved.

5.4 System Simulation Model

A computer model simulating system performance was instrumental in establishing the Phase I system design. The model was continuously updated to reflect refinements in process and equipment. The end result was a model that could be used to predict baseline system performance on seven common industrial solvents: toluene, acetone, methanol, methyl ethyl ketone, methylene chloride, perchloroethylene, and trichloroethylene. Characteristics of these seven solvents were included in the program data base. The model was also capable of assessing the sensitivity of system performance to various options in component selection and specification.

Figure 5-7 shows a simple schematic of the combined Brayton-Rankine solvent recovery heat pump process model. A mathematical model included the algorithms for calculation of compressor, turbine, and motor performance based on shaft speed and process conditions. In addition to the turbomachine speed, the other model input variables included:

- PR_C = compressor pressure ratio
- T_A = ambient temperature for heat rejection
- T_5 = temperature of reverse Rankine evaporator
- T_2 = compressor inlet temperature

Table 5-2. Baseline Process Conditions

Process Point	Fluid Allocation			Pressure (psia)	Temperature (°F)
	Air (lb/hr)	Solvent (lb/hr)	Water (lb/hr)		
1	9,372	138.0	100	14.7	+150
2	9,372	138.0	100	14.5	+95
3	9,372	138.0	100	33.35	+275
4	9,372	138.0	100	33.15	+100
5	9,372	138.0	5.5	32.65	+15
6	9,372	--	0.08	31.65	-60
7	9,372	--	0	16.4	-107
8	9,372	4.9	0	15.4	-107
9	9,372	4.9	0	15.1	-20
10	13,021	6.8	0	15.1	-10
11	22,393	11.7	0	15.1	-14
12	22,393	11.7	0	14.8	+40
13	9,372	4.9	0	15.0	+40
14	9,372	4.9	0	14.7	+222
15	--	--	94.5	32	~75
16	--	42.4	5.4	32	-60
17	--	90.7	--	16.4	-107
Process Point	R-22 Fluid			Pressure (psi)	Temperature (°F)
	Flow (lb/hr)				
18	2650			270.2	+115
19	2650			19.7	-30

90TR7

- SLA stream characteristics:
 - Flow rate, lb/hr
 - Temperature, °F
 - Inlet water vapor, grains/lb dry air
 - Inlet solvent composition and concentration ppmv.

The computer model calculated the turbomachine performance parameters of motor horsepower and component efficiencies as well as system temperatures, pressures, and vapor concentrations at the nine process points indicated in the Figure 5-7. At the completion of the Phase I effort, the capability of the model was limited to single component solvent streams with and without water vapor under steady-state conditions. The data presented in Table 5-2 are representative of the output available from the model.

Figure 5-7. Schematic of Combined Brayton-Rankine Process Model

5.4.1 Performance

Using the system model, the heat pump performance in the direct process-connected arrangement was estimated for seven common industrial solvents. It was found that both application-specific factors and equipment operational parameters influence system recovery efficiency, i.e., percent of inlet solvent recovered. The primary application factors involved are solvent vapor pressure, solvent concentration, and amount of water vapor present. Equipment-specific factors include turbomachine speed (pressure ratio) and reverse Rankine refrigeration system loading.

Figures 5-8 through 5-14 present the calculated system performance for the seven industrial solvents used in the system model. These performance curves show the percent of solvent recovered as a function of the concentration of solvent entering the system. The impact of water vapor on system performance is also indicated. A turbo-machine operational speed of 19,600 rpm and a reverse Rankine refrigeration load of 7 tons were used in the calculation of performance shown in these figures. Variations in these operational set points would, of course, produce different system performance.

90141

Figure 5-8. System Performance for Methylene Chloride (2200-cfm System)

90140

Figure 5-9. System Performance for Toluene (2200-cfm System)

90159

Figure 5-10. System Performance for Acetone (2200-cfm System)

90139

Figure 5-11. System Performance for Tetrahydrofuran (2200-cfm System)

90138

Figure 5-12. System Performance for Trichloroethylene (2200-cfm System)

90134

Figure 5-13. System Performance for Perchloroethylene (2200-cfm System)

90135

Figure 5-14. System Performance for Methyl Ethyl Ketone

5.5 Mobile Unit Design

5.5.1 Process Description

To meet the solvent recovery needs of applications typical to NYS, a mobile heat pump unit for the desorption of fixed base, solvent concentrating (carbon bed) adsorbers was established. As previously discussed, a key feature of this approach is that it spreads the high cost of the solvent recovery system over a large number of users. These users may also lease the site-based adsorbers, thereby eliminating all capital costs.

Figure 5-15 shows a schematic of the mobile unit for inert desorption. As shown, three system connections to the host site via a flexible hose are required: natural gas supply, inert gas supply, and inert gas return. A truck-mounted service module interfaces the solvent-concentrating adsorber with the heat pump system and provides all of the services required to operate the system.

A natural gas fueled, internal combustion engine drives a 40-pole, synchronous generator, providing the variable, high-frequency power required by the Brayton-cycle turbo-machine. An electric drive control system controls reverse Rankine refrigeration system speed and provides 60-cycle power to the balance of plant equipment.

Engine jacket cooling water is used in conjunction with a blower (B1) and a heat exchanger (HX6) to provide process heat at high volumetric flow to the fixed-bed adsorber for rapid heat-up. Engine exhaust heat is used in conjunction with another heat exchanger (HX7) to vaporize the solvent from the bed. The exhaust is also used to supply oxygen-deficient, noncombustible inert gas to the system.

90165

Figure 5-15. Solvent Recovery Heat Pump System (Mobile Brayton System)

Key subsystems of the service module include the following:

- A natural-gas-fueled engine-generator supplying 170-kW, 700-Hz, 3-phase electrical power.
- An electric drive and control subsystem that distributes high-frequency power and converts high-frequency power to 60 Hz for small motors. Also used for control and data acquisition purposes.
- An inert gas subsystem used to purge oxygen from the system prior to desorption.
- Process interface subsystem used to increase rate of heat input for desorption. The equipment consists of two heat exchangers (HX6 and HX7) and one blower (B1) along with appropriate ducting and diverter valves.

5.5.2 Mobile Unit Packaging

The packaging concept for the mobile unit is shown roughly to scale in Figure 5-16. The complete system is housed in a standard 28-ft box van, allowing 5 ft of space near the rear of the van for storage of the flexible duct work.

891866

Figure 5-16. Packaging Concept for Mobile Unit

5.5.3 System Controls

The operational procedure for fixed-bed desorption using the mobile unit consists of five phases:

- Phase 1 - Site Connection. The adsorber is isolated from the emission source and connected to the mobile unit with flexible duct work. The internal combustion engine is also connected to the natural gas stub up.
- Phase 2 - System Inerting. An inert gas blanket is generated through the operation of the internal combustion engine. The refrigeration equipment is put on line to provide a load for the engine and to remove the water vapor produced in the combustion process via condensation. Oxygen concentration is monitored, and the purge is complete when oxygen content is below 4% by volume.
- Phase 3- Bed Heat-up and Water Removal. The Brayton-cycle turbomachine compressor heat plus heat rejected from the engine exhaust and water jacket are diverted to the bed. The bed temperature slowly rises. With concurrent desorption, water is desorbed first from the bed and is removed from the system via condensation in a recuperative heat exchanger module.
- Phase 4 - Solvent Recovery. High-temperature engine exhaust heat is diverted to the bed. As the bed temperature rises, the mass transfer zone moves and solvent is released from the bed in high concentration. Brayton pressure ratio and reverse Rankine capacity are modulated for maximized solvent recovery.
- Phase 5 - Cool Down and Water Replacement. Heat input to the bed is stopped, cool dry inert gas is returned for cooling the bed. Water previously removed from the bed in Phase 3 is vaporized and returned to the bed.

An elementary piping and instrumentation drawing showing all of the active components in the mobile unit is presented in Figure 5-17. Figure 5-18 presents the operating logic diagram defining the sequential operations of the system during start-up and shutdown, identifying operator actions and automated functions, and indicating safety shutdown and warning sequences, as well as displays and operator indications.

5.6 Balance of Plant Equipment

The Phase I preliminary design effort included performance definition of the balance of plant equipment and the establishment of commercial availability for this equipment. The major system modules include the refrigeration module, which combines a reverse Rankine refrigeration system with the Brayton-cycle turbomachine, the recuperative heat exchanger and solvent condensation module, and the service module, which includes the engine/generator, electrical power distribution, and inert gas cleanup equipment. The performance requirements of each of these modules, with the exception of the Brayton-cycle turbomachine and the system controls described earlier, is presented in the following subsections.

90163

Figure 5-17. System Piping and Instrumentation Schematic

11 ENGINE GENERATOR START

90143

Figure 5-18. Continued

Figure 5-18. Continued

IV. REVERSE BRAYTON CYCLE STARTUP

Figure 5-18. Continued

90145

Figure 5-18. Continued

VI SOLVENT RECOVERY CYCLE

OPERATOR ACTION

DISPLAYS & INDICATIONS

ACTION

OPERATING CONDITIONS

90147

Figure 5-18. Continued

90148

Figure 5-18. Continued

90149

Figure 5-18. Continued

5.6.1 Reverse Rankine Refrigeration System

The reverse Rankine refrigeration system is a standard, skid-mounted refrigeration unit consisting of a two-stage positive-displacement compressor and an air-cooled condenser capable of providing 10 tons of refrigeration at an evaporator temperature of -30°F and of rejecting heat at 115°F . Refrigerant R-22 was selected as the process fluid because it has been determined to be one of the most environmentally safe chlorinated fluorocarbons (CFC) and is not scheduled to be removed from production in accordance with the Montreal protocol that limits global CFC manufacture. The prepackaged unit is to be supplied with unloaded start capability, oil separator, suction/liquid heat exchanger, air-cooled condenser with fan and head pressure control, high-pressure receiver system, pressure and temperature limit safeties, and electric motor drive.

This system is capable of capacity modulation via both hot gas bypass and variable speed operation resulting from variable frequency input to the compressor drive motor. The system is to be capable of operation at temperatures as low as -50°F evaporator temperature. The nominal design point is to be 9.8 tons of refrigeration at -30° evaporator temperature/ 115°F condenser temperature. Proposals for equipment meeting these requirements showed that the required motor horsepower at this design point is 31.1 bhp.

5.6.2 Service Module Equipment

Shown schematically in Figure 5-19, the power supply system is the heart of the service module and includes the following equipment:

- A 175-kW, 460-V ac, 700-Hz, synchronous generator equipped with brushless exciter
- A 250-hp, natural gas fueled, internal combustion engine with all necessary engine accessories and controls for service
- A generator circuit breaker together with overcurrent protective relays necessary to safeguard the equipment and personnel from electrical fault malfunctions
- A suitable rigid frame skid on which the engine/generator is mounted together with all the auxiliary equipment needed for proper operation
- A size 5 motor starter suitable for connecting 140-hp, 460-V, 3-phase Brayton turbomachine to the electrical bus
- A 460-V, 3-phase, 25-kW inverter capable of outputting 0- to 60-Hz power for variable speed drive of the reverse Rankine refrigeration system. The input power is to be 700 Hz, 460 V, 3 phase
- A 460-V, 3-phase, 10-kW power supply capable of converting 700-Hz, 3-phase power to 60-Hz power.

The natural gas fueled, internal combustion engine will be capable of alternative propane operation. During the initial start sequence, the electrical load will be disconnected from the generator by means of the generator circuit breaker. After the engine has reached its idle speed rating, the generator breaker will be closed and the high-speed motor drive will be energized. The engine-generator set will then be accelerated to rated speed. The electrical load on the generator during the acceleration cycle to

90167

Figure 5-19. Power Supply System

rated speed will vary as the cube of the speed from approximately 20 kW at idle to 100 kW at full rated speed. The generator will be equipped with a voltage regulator capable of maintaining a constant ratio of voltage output to frequency (volts divided by Hertz) during the start-up cycle.

The following performance is typical of several commercial offerings that meet the system requirements.

- Maximum Input: 2380 scfm of low pressure (8- through 12-in. WC) natural gas or propane
- Maximum Output: electrical: 200 kW, 480 V, 3 phase, 700 Hz at 2000 rpm with 40-pole synchronous generator
- Maximum Thermal: 774,000 Btu/hr hot water at 200°F and 408,000 Btu/hr steam at 350°F
- Efficiency: electrical 31.7% (lower heating value, LHV) combined electrical and thermal 86.6% (LHV).

5.6.3 Recuperative Heat Exchanger and Solvent Condensation Module

The solvent recovery heat pump system incorporates four primary process heat exchangers. HX1 is a nonpressure vessel heat exchanger that provides precooling to the solvent-laden inert gas entering the Brayton-cycle compressor at atmospheric pressure. Recuperative heat exchangers HX2, HX3, and HX4 handle the solvent-laden gas at compressor discharge pressure. This requires that these heat exchangers be designed and built in compliance with Section VIII of the ASME Boiler and Pressure Vessel Code.

Two solvent liquid separators (S1 and S2) are also included in the recuperative heat exchanger module. The purpose of separator S1 is to prevent liquid droplets larger than 5 micron from entering the turbine. Droplets or particles smaller than 5 micron have been shown not to contribute to turbine erosion. The purpose of separator S2 is to collect and recover condensed solvent vapor from the turbine exhaust. Separator S1 is a pressure vessel operating at compressor discharge pressure, while separator S2 is an atmospheric vessel. Both separators operate on a combined centrifugal and coalescing principal. The second-stage coalescer provides high removal efficiency, while the upstream centrifugal portion removes ice particles that would otherwise plug the second stage.

Table 5-3 provides the design thermal duties and performance of the heat exchangers and separation equipment. In summary, roughly 45% of the recuperative thermal duty is handled (at temperatures above 40°F) in the high-temperature heat exchanger HX2. In this heat exchanger, there is generally no condensation and no concern for frosting. Heat exchangers HX3 and HX4 are designed for both condensing and frosting service. All of the process heat exchangers in the solvent recovery heat pump system have been designed with a temperature effectiveness in the 75% range.

Table 5-3. Thermal Duties and Performance of Heat Exchanger and Separation Equipment

Heat Exchangers	Duty (Btu/hr)	Temperature Effectiveness (Duty)
HX1	127,598	0.75 (Precooler)
HX2	411,080	0.77 (Sensible Heat Recuperation)
HX3	297,568	0.74 (Condensing and Frosting)
HX4	177,561	0.72 (Condensing and Frosting)

Solvent Liquid Separators	Desired Filtration Level	Pressure Drop (psi)
S1	99% >5 micron	<0.7
S2	99% >5 micron	<1.0

90TR7

Frost formation in heat exchangers HX3 and HX4 may be handled by parallel redundant heat exchangers or by special continuous defrosting heat exchanger designs.* Parallel redundant heat exchangers represent the baseline case for commercial performance verification. These heat exchangers may be of the shell-and-tube or plate type. In general, fin pitch and thickness are greater than normal for air-to-air heat exchangers of this type to minimize mechanical problems with ice formation. Heat exchangers of the type required are available from a large number of commercial sources. Tables 5-4 through 5-7 present the specified performance for the four process heat exchangers described above.

Table 5-4. Data Sheet for Precooler Heat Exchanger (HX1)

Designation: HX1 Precooler; Duty: 127,598 Btu/hr; Type: Air to Air

	Hot Side	Cold Side
Pressure In (psia)	14.7	15.11
Temperature In (°F)	150	70
Temperature Out (°F)	90	118
Fluid		
• Air (lb/hr)	9372	12,560
• Water (lb/hr)	100	—
• Solvent (lb/hr) ¹	138	—
Sensible Heat Duty (Btu/lb)	145,000	145,500
Condensing Heat Duty (Btu/lb)	—	—
Allowable Pressure Drop (psia)	0.25	0.1
Design <ul style="list-style-type: none"> • Materials - corrosion resistant 316 stainless steel • Provision for condensation collection and drainage (hot side) • Provision for temperature and pressure monitoring for inlet and outlet on hot and cold sides 		

¹ Baseline solvent is methylene chloride; latent heat ~ 160 Btu/lb;
Cp ~ 0.3 Btu/lb°F

90TR7

*Not described herein due to patent restrictions.

Table 5-5. Data Sheet for Aftercooler Heat Exchanger (HX2)

Designation: HX2 Aftercooler; Duty: 411,080 Btu/hr; Type: Air to Air

	Hot Side	Cold Side
Pressure In (psia)	33.2	15.0
Temperature In (°F)	275	40
Temperature Out (°F)	100	222
Fluid		
• Air (lb/hr)	9372	9372
• Water (lb/hr)	99	—
• Solvent (lb/hr) ¹	138	—
Sensible Heat Duty (Btu/lb)	411,080	411,080
Condensing Heat Duty (Btu/lb)	—	—
Allowable Pressure Drop (psia)	0.25	0.3
Design <ul style="list-style-type: none"> • Materials - corrosion resistant 316 stainless steel • Provision for condensation collection and drainage (hot side) • Provision for temperature and pressure monitoring for inlet and outlet on hot and cold sides 		

¹Baseline solvent is methylene chloride; latent heat ~ 160 Btu/lb;
Cp ~ 0.3 Btu/lb°F

90TR7

Table 5-6. Data Sheet for Recuperative Condenser Heat Exchanger (HX3)

Designation: HX3 Recuperative Condenser; Duty: 297,568 Btu/hr

	Hot Side	Cold Side
Pressure In (psia)	33.2	-14.0
Temperature In (°F)	100	40
Temperature Out (°F)	15	40
Fluid		
• Air (lb/hr)	9372	22,960
• Water (lb/hr)	99	—
• Solvent (lb/hr) ¹	138	—
Sensible Heat Duty (Btu/lb)	198,493	—
Condensing Heat Duty (Btu/lb)	99,075 ²	—
Allowable Pressure Drop (psia)	0.5	0.35
Design <ul style="list-style-type: none"> • Materials - corrosion resistant 316 stainless steel • Design for cyclic defrost duty • Provision for condensation collection and drainage (hot side) • Design for ease of cleaning • Provision for temperature and pressure monitoring for inlet and outlet on hot and cold sides 		

¹ Baseline solvent is methylene chloride; latent heat ~ 160 Btu/lb;
Cp ~ 0.3 Btu/lb°F

² Water

90TR7

Table 5-7. Data Sheet for Recuperative Condenser Heat Exchanger (HX4)

Designation: HX4 Recuperative Condenser; Duty: 177,561 Btu/hr

	Hot Side	Cold Side
Pressure In (psia)	32.5	15.3
Temperature In (°F)	15	-104
Temperature Out (°F)	-60	-20
Fluid		
• Air (lb/hr)	9372	9372
• Water (lb/hr)	5.5	—
• Solvent (lb/hr) ¹	138	—
Sensible Heat Duty (Btu/lb)	120,000	—
Condensing Heat Duty (Btu/lb)	5760 ²	—
Allowable Pressure Drop (psia)	0.1	0.3
Design <ul style="list-style-type: none"> • Materials - corrosion resistant 316 stainless steel • Design for cyclic defrost duty • Provision for condensation collection and drainage (hot side) • Provision for temperature and pressure monitoring for inlet and outlet on hot and cold sides 		

¹Baseline solvent is methylene chloride; latent heat ~ 160 Btu/lb;
Cp ~ 0.3 Btu/lb°F

²36-lb solvent

90TR7

6.0 COST ANALYSIS

The direct material cost breakdown for the 2500-cfm mobile unit is presented in Table 6-1. This estimate was made for a production unit in quantities of 100 units per year. No profit margin is included. Until manufacturing drawings are made, the system costs in Table 6-1 should be considered a study estimate with a probable error of $\pm 30\%$. The turbomachine, which makes up 7% of the system cost, is composed of many parts that are in commercial production for which the costs are well defined. Therefore, the turbomachine estimate is within the narrower range of $\pm 20\%$. The effect of production quantities is shown in Figure 6-1, with the first unit (configured as shown in Figure 4-2) estimated at \$83,000. This cost includes inspection, pressure testing, balancing, cleaning, painting, and assembly. Figure 6-2 estimates the cost of the turbomachine as a function of flow capacity (quantities of 100 units per year). A 5000-cfm unit would cost approximately \$100,000 or about 7% less per unit of capacity than the \$54,000 production unit. A greater economy of scale is evidenced between the half-size unit and the production unit (2500 cfm). The half-size unit is estimated at \$34,000 or 26% more per unit of capacity than the production unit.

Table 6-1. Preliminary Production System Cost Estimate

Turbomachine	\$ 54,000
Heat Exchangers (See Figure 5-6)	
Heat Exchanger (Hx) 1	\$ 18,000
Heat Exchanger (Hx) 2	28,000
Heat Exchanger (Hx) 3 (Quantity: 2)	102,000
Heat Exchanger (Hx) 4 (Quantity: 2)	79,000
Heat Exchanger (Hx) 5	12,000
Heat Exchanger (Hx) 6 (see Figure 5-17)	19,000
Heat Exchanger (Hx) 7 (See Figure 5-17)	19,000
Subtotal	\$277,000
Service Module	
Engine	\$ 12,000
Generator	8,000
Controls	20,000
Power Distribution	12,000
Gas Subsystem	35,000
Air Skid and Accessories	15,000
Piping, Wiring, and Assembly	138,000
Subtotal	\$240,000
Truck Package	\$100,000
Balance of Plant	\$107,000
Total	\$778,000

90TR7

90136

Figure 6-1. Turbomachine Cost in Production Quantities

90137

Figure 6-2. Production Unit Cost versus Capacity

The heat exchanger costs are based on vendor quotations and are also in the $\pm 20\%$ range. With 35% of the system cost being devoted to heat exchangers, this is an important area for future cost reduction. The cost estimate in Table 6-1 includes redundant heat exchangers to accommodate a defrost cycle. Elimination of these duplicate heat exchangers could save approximately \$120,000.

The balance of the estimate for the system is based on a combination of engineering estimates and historical cost figures for comparable hardware.

7.0 FEASIBILITY ASSESSMENT

Since the solvent recovery heat pump mobile unit must be applicable to a wide variety of VOC emissions, this section presents a general feasibility assessment. For an analysis of the heat pump and its compatibility with processes see Section 5.0.

Regarding risk, the systems and components of the preliminary design are made up of commercially available components and existing designs and therefore do not represent high development risks. The major risk identifiable at this time lies in operating the system over a broad spectrum of solvents and processes. This operating profile raises two important issues: material compatibility and flow path fouling. Materials selection will be a critical step in the detailed design process, since system cost is extremely sensitive to the materials used in the heat exchangers, duct work, valves, and rotating machinery. The selection of titanium throughout can result in a fourfold cost increase over conventional materials. Therefore, the corrosion risks must be carefully weighed against cost benefits. A second operating risk is flow path fouling from particulates, plasticizers, resins, or other compounds that exhibit buildup in duct work, heat exchangers, or turbocompressor components. The full impact of this phenomenon will only be known with operating experience on various processes. However, provision can be made in the design phase to moderate the effect on system operation and maintenance. These features will include prefilters, separators, and cleanable components, particularly heat exchangers, where many of the high boilers will tend to condense out.

The amount of VOC solvent recovered and left unrecovered is dependent on the application. Solvent recovery efficiency and heat recovery are discussed in Section 5.0. Waste heat is recovered from both the engine-generator and the electric motor.

Alternative technologies for VOC control include carbon adsorption, condensing systems, and incineration. The following are important factors influencing the selection of a particular control technology:

- Process exhaust volume flow
- Process exhaust temperature
- Solvent concentrations
- Solvent composition
- Hours of operation per year
- Energy costs.

7.1 Incineration

Incineration is a technique that relies on oxidation (burning) of the solvent to carbon dioxide and water, which can be released safely to the atmosphere. This technique has proven effective for many hydrocarbons, but compounds that contain halides (such as chlorine or bromine), sulfur compounds, silicon, or heavy metals may require additional treatment to produce satisfactory emission streams. Incineration systems may be designed to handle a few hundred scfm, or may be designed to handle as much as 15,000 scfm. Larger systems have been designed with two incineration units in parallel.

Incinerators are used on a wide range of industrial products such as printing, drying, metal coating, and systems where odor is a problem. If simple, easily purifiable compounds are in the gas stream, other techniques such as carbon adsorption may be preferred. However, for low VOC-concentration systems, or for chemicals that are difficult to purify to a level suitable for reuse, incineration may be the process of choice. Incineration falls into two broad categories: thermal and catalytic.

7.1.1 Thermal Incineration

Thermal incineration is one of the simplest air pollution control techniques. The waste gas stream (with sufficient oxygen) is raised to a temperature of 1250 to 1500°F and held for a period of about 0.3 to 0.5 sec. Reduction of solvents may be expected to be in the range of 90 to 95%, and the technique may be used in a wide range of applications. For low VOC concentrations, a natural gas or fuel oil flame is the usual source of heat. Solvent concentration of typical sources is limited by safety considerations. Fire underwriters usually limit solvent concentration in ovens and dryers to 25% of the lower flammability limit (LFL) if there are no controls, and to 50% of the LFL if there are adequate controls, alarms, and shutdowns installed. As a rule, the temperature rise from combustion of solvent in a gas stream is 25°F for each percent LFL.

Thermal oxidation usually incorporates recuperative or regenerative heat recovery to reduce the purchased fuel required to maintain the required oxidation temperature. A recuperative system is shown in Figure 7-1. These systems utilize surface-type heat exchangers to preheat the SLA.

Regenerative systems use high density media or packed beds to preheat the inlet stream to the incinerator. These systems have the ability to achieve 95% heat recovery and are often recommended for flows over 10,000 scfm and solvent concentrations below 10% LEL.

Figure 7-1. Thermal Incineration with Primary Heat Recovery

7.1.2 Catalytic Incineration

The primary difference between thermal and catalytic incineration systems is that the reaction chamber of a thermal system is replaced by a catalyst bed for the catalytic system. The catalyst bed permits satisfactory oxidation of the solvents at input temperature as low as 500°F. Less fuel is required to heat the gas to the incinerator or lower percent LFL feed can be accepted with minimum fuel use. There are, however, some negatives to catalytic incinerators compared to thermal incinerators — first cost of catalytic incinerators is higher, overheating may reduce the catalyst activity, and certain elements such as chlorine, silicon, zinc, and tar may cause rapid degradation of the catalyst. In addition, Figure 7-2 shows a catalytic incineration system with a primary heat exchanger and a heat exchanger bypass. As in the case for thermal incineration, additional fuel savings can be achieved by installation of a primary heat exchanger for preheating the SLA mixture.

Figure 7-2. Catalytic Incineration with Primary Heat Source

The low first cost of thermal incineration makes it an attractive alternative. However, the potential user must consider a life-cycle cost with energy and maintenance costs included. Some representative first costs are given in Table 7-1.

Table 7-1. Estimated Incinerator Costs^{1,2,3}

Size (cfm)	Thermal without Heat Exchanger	Thermal with 70% Heat Exchanger	Catalytic without Exchanger	Catalytic with 74% Exchanger
4000	64	178	80	143
8000	90	260	100	233

¹All costs in thousands of dollars.

²1989 dollars.

³Installation costs not included.

90TR7

7.2 Conventional Condensation Technology

Conventional condensation technology is based on the fact that air can hold a limited amount of a given solvent in the vapor state at a given temperature. Less vapor is held at lower temperatures, and the excess will condense out as mist or rain.

A commonly used, direct-cooled condensation system is shown in Figure 7-3. Such a direct-cooled system consists of a blower, a cooler, and a device such as a demister to collect the condensed material. The blower is usually a conventional centrifugal unit operating at a few inches of water discharge pressure. The cooler may be a water- or air-cooled heat exchanger, but Freon-cooled refrigeration systems are more common. The final section to collect the condensed material may be an electrostatic precipitator, a demister packed with metal or plastic mesh, a cyclone, or another similar device.

90130

Figure 7-3. Direct-Cooled Condensation System

Operation of direct-cooled systems is usually limited by the degree to which the gas stream can be cooled. Most gas streams contain water vapor. Experience demonstrates that the water will freeze on the cooling surface of a standard heat exchanger and build up to the point that, if the gas temperature is below about 40°F, gas flow is impeded or stopped. Simple systems have found their broadest application in lower vapor pressure solvents (higher condensing temperatures), i.e., solvents in the offset web printing process.

Reverse Rankine refrigeration systems are currently used in solvent recovery applications at temperatures as low as -90°F. These systems have a distinct energy advantage over Brayton refrigeration systems. However, they tend to be more complex and require sophisticated means of handling frost.

In general, the technology is best suited to closed-loop, direct-process connection in applications where the VOC concentration level is above 5000 ppm. The technology may also be well suited to solvent recovery when combined with inert gas desorption of solvent concentrators.

7.3 Carbon Adsorption — Steam Desorption

Carbon adsorption systems depend on the fact that carbon granules can be treated so that vapors and gases will be held at the carbon surface. By proper treatment, the surface may be increased so that a pound of activated carbon contains many thousand square feet of surface. Because the activity (ability to adsorb) varies with temperature, a mass of carbon may be made to alternately hold and release the adsorbed material.

A typical adsorbing system consists of two or more carbon beds: one is in the adsorbing cycle, and the other is in the regeneration (release) cycle. The inlet gas stream flows through the blower and through the bed where the solvents are captured. Capture efficiencies in excess of 99% have been achieved, but capture levels of 90 to 95% are more common. The discharge from the bed is exhausted to atmosphere.

To release the solvent, steam is made to flow through the bed, raising the bed temperature and carrying off the desorbed solvent. Steam and desorbed solvent flow to a condenser, and the condensed steam and solvent flow to a separation system. The separation system may be a simple decanter if the solvents are not soluble in water, otherwise a complex distillation system may be required. In some cases, a combination of distillation and decantation may prove to be the optimum system. The desorption cycle is usually time controlled, and, when desorption is complete, the bed is placed in a standby mode.

The cycle of the active bed may be controlled by a timer, but it is more usually controlled by a sensor in the exhaust duct that reacts to an increase in solvent concentration. At the appropriate time or signal, the beds are switched from adsorbing to regeneration.

Carbon bed systems have been designed over wide flow ranges. Systems as small as a few hundred scfm have been designed for small dry cleaning stores, while larger systems have been designed to handle 20,000 scfm. Multiple bed systems may economically handle 100,000 scfm.

Capital cost of carbon adsorption systems varies widely. Table 7-2 lists cost estimates of basic systems for varying flow rates.

*Table 7-2. Cost of Carbon Adsorption Systems,
Not Installed (September 1989)*

Size (scfm)	Cost (dollars)
2000	\$100,000
4000	\$150,000
8000	\$205,000

90TR7

The system selected for this cost comparison is suitable for capturing toluene from gravure printing presses. Other systems may cost two to three times as much. For example, a system to adsorb the solvents from a magnetic tape drying system might require stainless steel beds, special carbon, and a complex distillation system to provide reusable solvents. Systems to handle chlorinated solvents may require titanium vessels.

Chlorinated solvents tend to break down to form hydrochloric acid in small quantities. Partially oxidized compounds such as methyl ethyl ketone oxidize readily and may cause bed fires or may produce strong smelling aldehydes in the discharge. Materials such as epoxy monomers, which can polymerize, may blind the carbon, requiring early replacement of the carbon bed. Similarly, silicones in small quantities may blind the carbon bed.

The primary operating cost of a simple carbon adsorption system is steam for regeneration. This cost is not related to the gas flow rate, but is a function of the captured solvent. Three to five pounds of steam are typically required for each pound of recovered solvent. If the solvent must be distilled, the steam rate may double or triple.

The activity of a carbon bed decreases with time because the carbon adsorbs heavy molecules, present in small amounts in the atmosphere, and does not release them during regeneration. Thus, the carbon bed must be replaced periodically depending on the service.

The inert gas desorption system will have certain advantages over the steam desorption system primarily related to the separation of water from the solvent. This is an energy advantage that can double the energy input, since the distillation step is eliminated with inert gas desorption. Secondly, the solvent quality is improved by eliminating water contamination, which can have a deleterious effect on many solvents.

Another major advantage to the user of inert gas desorption is the elimination of waste water disposal downstream of the distillation plant. This potential disposal problem is a concern for sites considering solvent recovery that do not want to trade one environmental release for another.

The description of emission control technologies provides a basis for comparison, but each application must be evaluated with regard to the many variables that can influence the final selection. Key advantages of the advanced heat pump system as either Brayton, Rankine, or a combination of the two, will be its ability to recover solvent at low condensing temperatures and to maintain solvent quality by minimizing contamination of the recovered solvent.

8.0 MARKET ASSESSMENT

The market assessment utilized the EPA Toxic Release Inventory (TRI) in conjunction with factors derived from the detailed NYS study described earlier and other judgments. The EPA TRI reports that about 2.7 billion lb of pollutants were released in 1987. Of this total, point source and fugitive emissions comprised 68% and 32%, respectively.

In preparing the market assessment, detailed information was available only for NYS. It was therefore necessary to make the assumption that NYS is typical of the U.S. average, even though other states' industrial mix may differ. Ideally, the "macroscopic" NYS study should be replicated in at least six additional states (Texas, Ohio, Louisiana, Tennessee, Virginia, and Michigan) to increase the confidence level of the assessment.

8.1 Multipliers

Six multipliers were generated for application to the EPA TRI data. The product of these multipliers and the basic EPA data then provide a state-by-state estimate of VOC releases addressed by the proposed technology.

M1: Elimination of VOCs. Some manufacturers have the option of modifying their processes to eliminate the need for solvents and other VOCs. For example, within the printing industry, the potential exists for switching from solvent to water-based inks. Based on a limited number of interviews, our judgment is that very few manufacturers will elect to institute process changes if low-cost VOC recovery methods are available. Both the cost of process modifications and compromises in product quality are the important considerations. This multiplier is estimated at 0.90 (i.e., only 10% of existing manufacturers would elect to change their basic processes).

M2: Competing Technology. Incineration, other condensing systems, and new recover approaches are assumed to capture 50% of the market. This multiplier is estimated at 0.50.

M3: Emission Levels within Regulation. Based on recent proposals for Clean Air Legislation, industry will be required to reduce their present emissions by 90%. Therefore, this multiplier is estimated at 0.90.

M4: VOCs as Fraction of Total Emissions. The EPA TRI lists 89 million lb/yr total NYS toxic releases. The VOC data base generated from air quality permit data showed that 66% of that total comprised VOCs suitable for recovery by the proposed technology (i.e., about 59 million lb/yr). This multiplier is estimated at 0.66.

M5: Size of Source. With the mobile concept, no source is too small. Small sources will simply need desorption at a low frequency. Desorption rates as low as a few times per year can be handled adequately by appropriate scheduling of the mobile desorption unit. The upper limit frequency for mobile desorption was set at once per day. Statistical analysis of the NYS data shows that systems above 40000-cfm inlet flow, at average concentration levels, will require desorption at rates greater than once per day. This limit eliminates about 26% of the NYS applications. This multiplier is estimated at 0.74.

M6: Retrofit Market. The EPA TRI data does not cover VOCs that are now being captured by existing pollution control systems. Penetration of this market, because of improved technology, therefore generates a multiplier greater than 1.0.

The NYS data base provides information on pollutant quantities from incineration processes, as well as quantities emitted from other nonincineration control means (namely, condensing systems and others). Assuming an average 95% capture efficiency for the latter systems, the input quantity of VOCs would be estimated at 19 times the quantity emitted. It was assumed that 50% of the incinerator applications and 10% of the nonincinerator applications would be penetrated by the technology proposed herein. This calculation procedure results in a favorable multiplier of 1.30. The retrofit market is, therefore, estimated at an additional 30% over the new installation market.

The above six factors produce a combined multiplier of:

$$(0.90) (0.50) (0.90) (0.66) (0.74) (1.30) = 0.26$$

This is the multiplier applied on a state-by-state basis to the EPA TRI. As stated earlier, the assumption inherent in this analysis approach is that all states are similar to New York. Additional detailed information, particularly for the six states mentioned, will greatly improve the quality of the market assessment.

A second phase of the analysis examined the geographic distribution of the market. This is an important consideration when a mobile concept is to be implemented. Three significant territories emerged: North, South, and California. Figure 8-1 shows the geographic grouping, which covers 17 of the top 18 states and about 70% of the total U.S. VOC releases.

Table 8-1 shows the estimated breakdown by state based on the EPA TRI and the derived multiplier.

90133

Figure 8-1. Principal Market Areas

8.2 Urgency of RD&D Program

The market buildup rate will be extremely rapid. This results from the near-term compliance dates associated with impending clean-air legislation. If the June 1989 White House press release outlining the Administration's clean-air plan is used as an estimate, 75-90% of the VOC potential market listed in Table 8-1 should be acquired by the end of 1995. This means that systems capable of recovering approximately 400 million lb/yr need to be in place by that date.

Table 8-1. Annual Emissions in Selected States

U.S. Rank	Total Toxic Releases, million lb	VOC Potential Market, million lb	Cumulative Market, %
1. Texas	239	62	9.0
2. Ohio	173	45	15.5
3. Louisiana	138	36	20.7
4. Tennessee	135	35	26.0
5. Virginia	132	34	30.7
6. Michigan	116	30	35.1
7. Indiana	113	29	39.3
8. Illinois	99	26	43.0
9. Alabama	98	25	46.7
10. North Carolina	95	25	50.3
11. Georgia	94	24	53.8
12. New York	89	23	57.1
13. Pennsylvania	88	23	60.4
14. California	83	21	63.5
16. South Carolina	64	17	65.9
17. Mississippi	57	15	68.1
18. Arkansas	56	14	70.1
Subtotal	1869	484	70.1
U.S. Balance	797	206	100.0
U.S. Total	2666	690	100.0

90TR7

Legislative slippage in the proposed compliance dates and a softening of the 75-90% emission abatement requirements will probably occur. Notwithstanding, the task of building market presence (a sales network), production capacity, and service facilities is enormous. If the efficient recovery technologies now being pursued by MTI and others are to have an impact on this market, the applied level of resources must be significantly increased and, most importantly, the time frame for development must be shortened. If this is not done, private enterprise will not have the technical data available at the time investment decisions regarding the necessary marketing, manufacturing, and service facilities are to be made.

The need for early technology demonstration relates to business risk. The manufacturing business requires a large initial investment to capture nearly a step increase in sales (driven by legal compliance dates). This large initial investment results from both inventory buildup and tooling requirements. Depending on the exact structure of the business, an investment range of \$20-40 million can be anticipated in order to serve the national market at a rate consistent with the time frame certain to be imposed by clean-air legislation. This investment gamble becomes too risky if an adequate technology demonstration program has not occurred. This is especially true given the sophistication of the recovery technologies being pursued and the impending 1995 compliance dates.

9.0 CONCLUSIONS

Based on the NYS applications study and contacts with host site candidates, MTI concluded that VOC solvent recovery technology will be driven by environmental regulations. Currently, the economics of solvent recovery alone are not sufficient inducement to control emissions. Therefore, VOC emitters are inclined to maintain the status quo. As regulations become more stringent, as it appears they will, emitters will eliminate the use of organic solvents, recover and reuse the solvents, or go out of business. Incineration and other disposal techniques that create their own environmental problems will probably not be an option. For those processes that continue to use organic solvents, a decision will be made between alternative methods of recovery based on cost to maintain product quality. A near-term need for new solvent recovery equipment was identified in two broad areas: small users and low concentration emissions. The small user (under 20,000 lb/yr) will not be able to afford the high first cost of the solvent recovery heat pump system, nor will they be comfortable with the operation and maintenance of this relatively sophisticated equipment.

The second area of interest is that of low concentration emissions (air streams with less than 200-ppm solvent). These streams are not practical for direct-coupled condensing systems because the energy requirement per pound of solvent recovered is very high. In addition, based on conversations with these sites, solvent recovery by steam desorption is prohibitively expensive for these applications.

The mobile system for inert gas desorption of carbon adsorption modules proposed herein offers a practical solution to both the small user and the low concentration dilemmas. The concept is to share the expensive equipment among a number of users by a fee-for-service plan. The relatively low-cost carbon adsorption module would be purchased and optimized for the specific site. Because the module will be desorbed by inert gas at low pressure, its cost is much less than that required for steam desorption, thus moderating one of the principal barriers to recovery from low concentration SLA. In addition, when a company has a small low concentration source, the desorption and distillation equipment is not required on site. Instead, the mobile unit visits as required, once a day or once a month.

Large permanent installations are viable for systems directly coupled to the process (no concentrator) when SLA concentrations are high enough (generally less than 40% LEL).

END

**DATE
FILMED**

9 / 1 / 92