EFFECT OF FRACTURE SURFACE ROUGHNESS ON SHEAR CRACK GROWTH

Progress Report
for Period August 1, 1991 to May 31, 1992

Todd S. Gross and David W. Watt
Department of Mechanical Engineering
University of New Hampshire
Durham, NH 03824-3591

and

Daniel A. Mendelsohn
Department of Engineering Mechanics
Ohio State University
Columbus, OH 43210

December 1992

Prepared for

THE U.S. DEPARTMENT OF ENERGY
AGREEMENT NO. DE-FG02-90ER45433

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Table of Contents

1. Project Summary	1
2. Joint Accomplishments	2
3. Accomplishments at UNH	10
4. Accomplishments at OSU	19
5. Proposed work for remainder of funding period	29
6. Proposed work for the next funding period	29
7. Students funded by this project	30
8. Publications	30
9. Presentations	31
10. Other federal funding	31

1. PROJECT SUMMARY

The joint analytical-experimental program to investigate the effect of fracture surface roughness has achieved several milestones during the last, short project period.

A model of fracture surface interference for actual Mode I fatigue crack profiles was developed and evaluated. It is proposed that, for a given effective Mode II stress intensity factor, the crack faces are displaced in shear according to a $r^{1/2}$ displacement law and the crack tip shear displacements can be estimated using an Irwin plasticity correction factor. The opening required to prevent the shifted crack profiles from occupying the same volume is then numerically evaluated and the induced Mode I stress intensity factor is estimated assuming the relevant $r^{1/2}$ displacement dependence and an Irwin plasticity correction factor for crack tip displacements. The force required to open the crack faces the required amount is estimated from point contact expressions for the Mode I stress intensity factor. Force transfer across the contacting asperities is estimated assuming Coulomb friction using the average of the local asperity slopes and is used to calculate the Mode II "resistance" stress intensity factor. The applied Mode II stress intensity factor is simply the sum of the effective and resistance stress intensity factors.

The electro-optic holographic interferometry system has been used to measure the three dimensional displacement field around a (Mode I) fatigue pre-crack in 7075-T6 aluminum subsequently loaded in Mode II shear. The induced Mode I crack face displacements were observed to be greater than the Mode II crack face displacements which is consistent with the predictions of the previously described model. Also, the plane stress shear lip was observed to cause displacement normal to the surface as the crack faces are displaced. Several improvements in the data acquisition and analysis have been described in a Letter to the Editor of Applied Optics. Since the magnitude of the accumulated displacements was observed to be greater than the camera pixel spacing, algorithms are being developed to track the displacements associated with the original coordinate system. This is expected to lead to an improvement in spatial and displacement resolution.

A 2D boundary element method (BEM) code for mixed mode I and II loading of a rough crack, with surfaces modeled by an array of sawtooth asperities, has been completed. The code is for general external boundary and crack geometry, and includes the case of a bi-material interface crack. The elastic BEM code has been used to study the effects of mode mixity and the fracture surface parameters on the shielding in mode and the anti-shielding in mode I for cracks in an infinite and finite geometries. The parameter study has extended significantly our understanding of the behavior and limitations of the sawtooth asperity model at an elastic crack tip. The addition of small-scale crack tip yielding to the numerical code using a mixed mode Dugdale approach has been completed, but no parameter studies performed. The addition of a wear model using contact induced plasticity is underway, as is mesh generation and convergence studies for the compact tension specimen used in the experiments at UNH. Some related work on stochastic representations of rough surfaces has also been completed with another graduate student.

2. Joint Accomplishments

As part of the ongoing effort to create a more synergistic relationship between experiments and analytical results, the PIs at UNH and OSU meet regularly to discuss the course of the research and chart new directions. The following model was the result of two meetings during this project period. A paper describing the model is being prepared for submission to *Acta Metallurgica* and *Materialia*.

The first task is to characterize an actual fracture surface. Compact tension specimens of 7075 T6511 aluminum and 4140 quenched and tempered steel were fatigue cracked in tension at $\Delta K = 8\text{-}10 \text{ MPa m}$ with $R=1$. Crack lengths of about 4-5 mm were obtained before taking the samples to complete failure and sectioning them. The digitized crack profiles obtained from micrographs of the sections using a sampling interval of $0.41 \text{ }\mu\text{m}$ were then used in a mathematical simulation of relative crack face sliding and opening due to pure shear loading. Although results are completed for both, only the aluminum is discussed below.

Assuming that the crack faces are perfectly meshed at zero applied shear, a single surface description is used for both the top and bottom crack surfaces. Since each point on the rough fatigue crack was, at some time during crack growth, the location of the crack tip one may choose any point along the surface as a crack tip for the present purpose. The bottom surface is shifted relative to the top surface according to the classical near tip square root crack sliding displacement (CSD) distribution with small scale plastic yielding accounted for at the crack tip. The CSD distribution is proportional to the assumed given value of the effective mode II stress intensity factor (SIF), $K_{II\text{eff}}$. The surfaces are then opened until crack face interpenetration is eliminated everywhere, which was found to leave contact at one point only. The contact point x_c and the crack opening displacement at that point, COD_{max} are thus found for a given set of material properties and are shown in Figures 1 and 2, respectively, for the aluminum as functions of $K_{II\text{eff}}$. Plots of the displaced and deformed fracture surface are shown in Figures 3a-3e, for various loading states. Note that in this section x is taken along the crack length and y is normal to the crack plane.

These mathematical simulations of sliding, which ignore asperity flexibility, show that prior to any asperity wear the tendency is for the crack faces to "hang up" at a single dominant asperity interaction leaving the crack open over most of its length. The contact is

maintained before and after the first dominant asperity peak is traversed and then contact is shifted to the next dominant asperity. This forms the basis for the point contact loading assumption used in the rest of the model.

Next we obtain the normal contact force applied at a distance from the tip, $x = x_c$, necessary to create the COD_{max} at that point. This is done using the well known plane strain solution for the opening of a line loaded (N/t) semi-infinite crack. Once N is known the induced mode I SIF, K_{Iind} is also given by this well known solution:

$$K_{Iind} = \frac{N}{t} \sqrt{\frac{2}{\pi x_c}} \quad (1)$$

$$N = \sqrt{\frac{-1 + \sqrt{1 + 4\beta\gamma^2}}{2\beta}} \quad (2)$$

$$\beta = \frac{2}{(\pi x_c t \sigma_y)^2}, \quad \gamma = \frac{\pi E t COD_{max}}{4(1 - \nu^2)} \quad (3)$$

In these expressions E and ν are Young's modulus and Poisson's ratio, respectively, σ_y is the uniaxial yield stress, and t is the thickness of the specimen.

The associated frictional force F on the asperity at $x = x_c$ is found by applying Coulomb sliding friction on the inclined asperity, whose slope $\tan(\alpha)$ is found from the digitized surface profile. Figure 4 shows the contacting asperities and two normal and tangential forces systems, one on the actual plane of contact (N_a and F_a), Figure 4b, and one on the macroscopic crack plane (N and F), Figure 4c. Setting $F_a = \mu N_a$ where μ is the coefficient of sliding friction, and equating the forces in the two systems gives a modified Coulomb sliding law on the macroscopic crack plane, $F = \Gamma N$. Since the only resistance to relative crack face shear displacements is due to F , the mode II rough surface resistance SIF, K_{IIr} , is simply the mode II SIF for a crack with a concentrated shear line load of strength (F/t)

acting at the point x_c on the crack face. This SIF is well known also, and we obtain the formulas:

$$K_{IIr} = \frac{F}{t} \sqrt{\frac{2}{\pi x_c}} \quad (4)$$

$$F = \Gamma N \quad (5)$$

$$\Gamma = \frac{\mu + \tan(\alpha)}{1 - \mu \tan(\alpha)} \quad (6)$$

The necessary K_{IIapp} to give the above solutions is, by superposition, simply $K_{IIapp} = K_{IIeff} + K_{IIr}$.

To obtain more realistic behavior for 2D crack resistance, the variation along the crack front through the thickness is accounted for by using the model on a series of cracks obtained from the same fracture surface, but with varying crack tip position. If the randomness of the surface is similar in both directions (crack front and crack length) then this should give the same results as using a series of profiles through the thickness and keeping the crack front position fixed. Results for both a fixed tip and the averaged tip results are given in Figures 5-7, again for the aluminum only. The material and geometric constants used in the calculations are: $E = 70.3$ GPa, $\nu = 0.35$, $\sigma_y = 505$ MPa, $\mu = 0.1$, $t = 12.7$ mm. The smaller dashed lines in Figs. 6 and 7 denote the line of no shielding. In both cases points above the line represent crack tip shielding in shear and those below represent crack tip anti-shielding.

Comparison of Fig. 5 to Fig. 6 shows that the dilatant opening effect of surface roughness, which must occur to accommodate sliding displacements, induces a mode I SIF which is of the same order of magnitude as the applied mode II SIF. The dependence of K_{Iind} on K_{IIeff} basically follows that of COD_{max} shown in Fig. 2, but there is a marked and highly erratic dependence of the calculated mode II quantities. This is due to the random variation

in asperity slope as a function of contact position. While the peaks are smoothed somewhat by the averaging process, there is still an irregular dependence. We believe this is a real physical effect which we expect to see reflected in the experiments. Focusing on Fig. 7 (Fig. 6 is similar) we can associate the three major features with three contact states. The first peak at $K_{\text{Ieff}} \approx 2 \text{ MPa}\sqrt{\text{m}}$ represents the extremely strong resistance to initial sliding motion. The next peak at $K_{\text{Ieff}} \approx 14 \text{ MPa}\sqrt{\text{m}}$ shows the resistance to climbing over the asperity at $x \approx 400 \text{ }\mu\text{m}$. This event occurs between the states shown in Figs. 3a and 3b. And finally the smaller feature in Fig. 7 at $K_{\text{Ieff}} \approx 37\text{-}40 \text{ MPa}\sqrt{\text{m}}$ corresponds to the decreased resistance as the top surface easily slides down the asperity at $x \approx 400 \text{ }\mu\text{m}$, and then the sudden rise occurs as contact is transferred to the asperity at $x \approx 600 \text{ }\mu\text{m}$. The model is simple, makes physical sense, and is in a closed form. Yet, we feel that the basic kinematics of the sliding and opening have been captured and the effects of interest are clearly exhibited. However, the model is quite "stiff", and all SIF results are overestimated because of the rigid asperity assumption and the neglect of wear once the climb up the first asperity occurs. Both of these and other modeling improvements are addressed below. However, comparison to the upcoming experimental results is the best way to judge and improve the model further.

Figure 1. x_c vs. K_{IIeff} for the aluminum.

Figure 2. COD_{max} vs. K_{IIeff} for the aluminum.

Figure 3a. $K_{IIeff}=5 \text{ Mpa}\cdot\text{m}^{1/2}$

Figure 3b. $K_{IIeff}=35 \text{ Mpa}\cdot\text{m}^{1/2}$

Figure 3c. $K_{IIeff}=38 \text{ Mpa}\cdot\text{m}^{1/2}$

Figure 3d. $K_{IIeff}=40 \text{ Mpa}\cdot\text{m}^{1/2}$

Figure 3e. $K_{IIeff}=45 \text{ Mpa}\cdot\text{m}^{1/2}$

Figure 4. Asperity contact model: (a) point contact of two opposing asperities, tangent to the contact makes an angle α with the macroscopic crack plane; (b) resolution of contact forces into normal and tangent to the actual contact plane; (c) resolution of contact forces into normal and tangent to the macroscopic crack plane.

Figure 5. K_{IInd} vs. K_{Ileff} for the aluminum.

Figure 6. K_{IIr} vs. K_{Ileff} for the aluminum.

Figure 7. K_{Iapp} vs. K_{Ileff} for the aluminum.

3. Accomplishments at UNH

The primary experimental accomplishment was the demonstration that the three dimensional displacement field could be obtained for specimens under load. This entailed several unplanned improvements in the hydraulic loading system, finishing of the manufacture of the Mode II loading grips, and completion of the manufacture of the three illumination beam system. A *supposedly* high speed array processor was purchased to facilitate and speed up data acquisition and analysis. The software took at least five months to develop. After completion of the software development, it was determined that most of the routines in the programs ran slower on the array processor than on the host - some could not be made to work at all. The board was returned in exchange for two standard frame grabber boards. The failure of this system to perform as expected was a major drain on our financial and more importantly, our intellectual resources. In spite of this problem, we were able to obtain a number of interesting experimental results.

A modified compact tension specimen of 7075-T6 aluminum was fatigue pre-cracked in Mode I and the fracture surface profile was obtained by methods described in the progress report for the first project period. The specimen was then loaded in Mode II. Interferograms from three different illumination beams were recorded in $K_{II} = 0.25 \text{ MPa}\sqrt{\text{m}}$ increments. The individual interferograms were analyzed to determine the opening (x), sliding (y), and out-of-plane (z) displacements on a point-by-point basis. The crack lies in the y-z plane. (Note that the analytical model uses a rotated coordinate system.) The maps were numerically accumulated and stored at $K_{II} = 1.5, 3.0, 4.5, \text{ and } 5.5 \text{ MPa}\sqrt{\text{m}}$. The x, y, and z displacement fields for $K_{II} = 5.5 \text{ MPa}\sqrt{\text{m}}$ were displayed in gray scale format (Figure 8a, b, and c) and in mesh-type surface plots (Figure 9 a, b, and c). Displacement vs position slices through various portions of the map were also plotted (Figure 10).

The gray scale maps encode the displacements in terms of shades of gray where black corresponds to the least displacement and white corresponds to the most displacement. The conversion factor is selected to use the full gray scale range. We are currently modifying our display software to include the display of iso-displacement contour lines so the actual magnitude is included on the gray scale map.

The gray scale maps for $K_{II} = 5.5 \text{ MPa}\sqrt{\text{m}}$, in Figure 8 a, b, and c, show a distinct discontinuity across the crack faces in all three maps. The range of displacement is indicated next to each of the maps. The x map clearly shows that the crack faces are wedged open. This can be seen more clearly in the x, y, and z displacement slice plot shown in Figure 10. This horizontal slice was made near the notch which can be seen in the top of the gray scale maps. The z map and the slice plot show some displacement around the crack. We believe that this is due to the wedging out of the plane stress shear lip as the crack faces are displaced in shear. It is interesting to note that the crack opening displacement is greater than the crack face shear displacements.

Upon study of the maps and displacement slices, we realized that another level of processing is required to obtain spatial resolution on the order of the pixel spacing ($\approx 10 \text{ }\mu\text{m}$). The interferograms are recorded at intervals such that the total lateral motion is roughly less than one fifth of pixel. This ensures that the phase fields are well correlated and that the displacement information corresponds to a given location. As a number of phase fields are summed, the original point has laterally moved a distance corresponding to several pixels away. When the information is simply summed on a pixel by pixel basis, the displacements at a given location actually correspond to an average of several of the original points that have passed through that pixel location. The displacements of the points under the original pixels must be tracked similar to the way the particles are tracked in a moving fluid.

There are two steps that will be taken to ensure that the displacements of the original will be properly tracked. First, in future experiments, a high contrast marker will be placed in some non-critical location in the field of view. Its position and its lateral displacement can be tracked by standard image correlation algorithms to approximately half a pixel ($5 \text{ }\mu\text{m}$) accuracy. This information will be used as a reference point to track the displacement of the original pixel locations i.e. the relevant coordinate system. Second, as the original pixel location displaces across a group of four pixels between any two interferograms, the information stored in the array location will correspond to an average of the four pixels weighted by the area overlap with the original pixel. It is expected that these steps will decrease the amplitude of the noise evident in the slice plots (Fig 10). The noise in the x displacement is greatest, which is the displacement with the most misregistry with respect to

the original pixel location.

One final accomplishment of this period was the refining of the phase unwrapping methods. A method proposed by Bone was implemented with minor corrections in his algorithm. Briefly, the method searches the locally unwrapped phase maps for areas of high curvature using a second difference equation. These points are excluded from the first unwrapping of the map by masking. Once the unmasked areas are unwrapped, the fringe order for the masked areas are determined from the unwrapped neighbors until all the pixels have a fringe order assigned. Occasionally, a single bad point causes an area on the map to be off by one fringe order. The floodfill method proposed by Bone lead to irregularly shaped areas which made manual correction quite difficult. A modified horizontal fringe order assignment method generated square incorrect areas when it failed which were easily corrected. This procedure is described in a Letter to the Editor submitted to the Journal of Applied Optics.

Figure 8a
13

Figure 8b
14

Figure 8c

$K=4.5 \text{ MPa}/\sqrt{\text{m}}$

$K=5.5 \text{ MPa}/\sqrt{\text{m}}$

Displacement
in x-axis

Displacement
in y-axis

Displacement
in z-axis

$K=1.5 \text{ MPa}/\sqrt{\text{m}}$

$K=3.0 \text{ MPa}/\sqrt{\text{m}}$

Displacement
in x-axis

Displacement
in y-axis

Displacement
in z-axis

Figure 10

4. Accomplishments at OSU

The BEM formulation and code for mixed mode I and II loading of a rough crack, whose surfaces are modeled by an array of sawtooth asperities, has been completed, and an extensive parameter study performed, concluding the study of the unworn uniform sawtooth model for the elastic crack tip. The formulation and some selected results are presented below. The formulation and coding for plasticity at the crack tip has also been completed, and a few numerical examples have been successfully obtained. The formulation is discussed but no results presented, awaiting the inclusion of the Dugdale type crack tip in future parameter studies. The coding for the actual compact tension specimen geometry used in the experiments is almost complete and the wear formulation is also underway. Both are discussed briefly. Finally some related stochastic modelling of randomly rough surfaces done with a graduate student from another project will be discussed.

4.a. BEM Sawtooth Model - Elastic Crack Tip

The physical asperity interaction model is described schematically in Fig. 11, which illustrates a representative segment of displaced crack surfaces. The first relation shown in Fig. 11 states that asperity sliding is governed by Coulomb's law of friction, with coefficient of friction μ . In order to implement this in the BEM formulation without modeling the actual sawtooth surface a macroscopic crack plane is taken parallel to the midplane of the perfectly meshed sawtooth surfaces and standard stress transformation performed to obtain an effective Coulomb sliding law on that plane. This yields the second relations in Fig. 11, where Γ , the effective coefficient of friction, is also defined in the figure, and α is the asperity angle. The assumption of rigid body asperity sliding yields an induced opening proportional to the sliding as expressed by the last relation in Fig. 11, where g is the crack opening displacement, COD, and h is the crack sliding displacement, CSD, both referring to the macroscopic crack plane. Since g and h will vary along the length of the crack, the asperities may only be considered to be locally rigid in so far as they maintain planar surfaces, however they must be considered deformable in bulk so that they may accomodate the varying g and h .

The first step in the BEM solution is to divide the cracked body into two bodies along the plane of the crack, referred to below as the interface. The interaction between the two bodies is included through boundary conditions relating the displacements and stress on either side of

the interface. At points on the uncracked portion of the interface the 2 displacement components and the 2 stress components must be continuous. At points on the cracked portion of the interface the stresses are continuous (2 conditions) and are related by the second relation in Fig. 11 (1 condition), and the final condition comes from the last relation in Fig. 11 after expressing g and h in terms of the displacements on opposite crack faces. Thus at each pair of points on the interface we have four conditions involving eight quantities. Four of these are eliminated algebraically using the boundary conditions, thus leaving four unknowns at each point. Two coupled boundary integral equations, written as a function of position on the boundary of a body, enforce all of the field equations of elasticity for that body. The two equations for each of the two artificially divided bodies are applied to each discretized point on the interface, thus giving four equations and four unknowns at each pair of interface points. If the boundary of either of the artificially divided bodies consists of other than the common interface then at each such boundary point there are four boundary quantities to be accounted for. The only conditions we have used on these external boundaries has been prescribed stress, thus leaving the two displacements as unknowns, with two equations provided by that body's two boundary integral equations. The case of a crack lying on the interface between dissimilar materials is obtained from the above formulation simply by making the elastic constants in the two bodies different.

The BEM consists of the discretization of the boundary surfaces and the numerical approximation of the boundary quantities in the set of equations obtained from the boundary integrals as described above. In our code we model the boundary using straight-line elements, centered about nodes at which the integral equations are applied. For a straight boundary this introduces no approximations. We assume, though, that the stress and displacement are constant throughout each straight-line element. This approximation allows their removal from inside the integral, resulting in integrals of the known 2D Green's functions which have been evaluated in closed form. The final result is a system of simultaneous linear algebraic equations for the unknown nodal displacements and stresses. After the system is solved the crack tip SIF's are calculated by fitting the calculated COD or CSD to the standard square root form at an elastic crack tip.

The results shown here are for a finite length crack (10 mm) either in an infinite homogeneous body with shear modulus G and Poisson's ratio ν , or for a crack of the same

length at the interface of two semi-infinite dissimilar bodies, identified by subscripts 1 and 2. The applied loading is uniform remote tensile stress N and shear stress S . The effective (applied minus resistance) mode II shear SIF and the total (induced plus applied) mode I SIF for a homogeneous aluminum medium are denoted by K_{II} and K_I in Figs. 12 and 13. They are plotted versus the applied shear SIF K_{IIapp} , which is calculated using S in the open crack SIF solution. K_{Iapp} is found in the same way using N . Each curve in Figs. 12 and 13 is for one value of N and the asperities are characterized by $\alpha = 40^\circ$ and $\mu = 0.2$ which gives $\Gamma = 1.250$. Here K_{II} and K_I refer to the actual or effective mode II and I SIF, respectively. Thinking of N as being applied first and then S being increased from zero there is a range of applied shear for which the crack surfaces are not in contact and the applied and actual K_{II} are equal. This range is denoted by "OPEN" on the $N = 150$ Mpa curves. But, when S is large enough to make $K_{IIapp} = K_{IIclosure} = K_{Iapp} \cot(\alpha)$ the asperities come into contact, and as S increases further the model goes into effect and shielding occurs. This portion is denoted by "CLOSED" on the $N = 150$ Mpa curves. The results are linear and when closed the ratio of the mode II effective SIF to the mode I induced SIF is constant and equal to $\cot(\alpha)$.

Figure 14 is an example of a parameter study with respect to the micro-mechanical variables. K_{II} and K_I are plotted versus asperity angle α for three different values of coefficient of friction μ , keeping N and S fixed. The plots cover the entire physical range of α and, since μ represents the coefficient of friction for a smooth faceted asperity surface, zero to one is a fairly wide range for μ as well. Focusing on the $\mu = 1.0$ curves, the crack is open if $\alpha < 14^\circ$, closed if $\alpha > 14^\circ$. The open/closed transition depends on N and S only. If $\alpha > 45^\circ$ the effective coefficient of friction Γ is infinite and the crack is locked. The value of the locked K_I is K_{Iapp} and the value of the locked K_{II} depends on the amount sliding which occurs before contact occurs, and happens to be equal to K_{Iapp} in this case because the locking angle for $\mu = 1.0$ is 45° . The $\mu = 0.0$ and 0.2 curves may be interpreted similarly. The results show that as α increases K_I increases for a while, as expected from the imposed COD/CSD relationship, but at some critical α the counteracting effect of greater normal contact stress σ_c and greater Γ , and hence greater frictional stress τ_c , takes over and K_I begins to decrease with increasing α . Several other parameter studies have been performed and will be included in the paper in preparation.

We note that the results validate the a-priori assumption of classical open crack CSD and

COD distributions made in our earlier models. Here they are solved for, but in every case, because the crack is closed and subjected to sufficiently large shear, the same slip boundary conditions apply everywhere and we found that the CSD and COD are proportional to the classical open crack solutions. This would not be the case for loading in which the contact or slip status changes along the length of the crack, as for example when partial wear is considered.

Figure 15 is an example of some interface crack results. It has been shown that the behavior of a closed or partially closed interface crack depends on the material constants primarily through the parameter β which is defined in the caption to Fig. 15, and is known as one of Dundur's bi-material constants. The plots are of K_{II} versus β , solid curves being for one asperity characterization ($\alpha = 27^\circ$, $\mu = 0.0$, $\Gamma = 0.505$) and the dashed curves for another ($\alpha = 40^\circ$, $\mu = 0.2$, $\Gamma = 1.250$). The top curve in each case is for the right crack tip and the bottom for the left tip. If the direction of S is reversed or the constituents reversed, the left and right tip results are interchanged. The material mismatch effect of increased or decreased SIF's is seen to be enhanced by a rougher more resistant fracture surface. Since the crack is all closed for these examples the additional mismatch induced closure effect is not seen here and the effect of roughness on it is not evaluated.

4.b. Plastic Crack Tip

The formulation for small-scale plasticity at the crack tip has been completed and implemented in the code described above in Section 4.b. It is based on a re-formulation of the Dugdale strip yielding model to the mixed mode open crack case, in which the normal and shear stresses in the plastic zone have the same ratio as the applied normal and shear stress, but are both functions of the uni-axial tensile yield stress and the applied stresses [W.Becker and D. Gross, Int. J. Fracture, 37, 163-170, 1988]. In the single mode case the stress is either the tensile yield stress or the shear yield stress. The length of the mixed-mode plastic zone is also given in terms of the same quantities, just as in the single mode open crack Dugdale cases. Our contribution is to adapt these ideas to our numerical formulation by replacing the applied loading with effective SIF's and writing the, now unknown plastic zone stresses and unknown plastic zone length in terms of the unknown effective mode I and II SIF's. We solve the non-linear problem directly for the two effective SIF's using Newton's method subject to the conditions of zero slope in the COD and CSD at the end of the plastic zone. For a given iteration on the effective K_I and

K_{II} , the associated plastic zone stresses and plastic zone length are calculated from Becker and Gross's modified results in terms of K_I and K_{II} . These plastic zone stresses are used in prescribed stress boundary conditions for the newly formulated plastic zone interface region in a revised BEM code and the COD, CSD and their slopes at the end of the plastic zone are calculated. These are then put into the 2D Newton's method formulas for the next iterated values of K_I and K_{II} . The iteration is stopped when the difference between two subsequent guesses reaches some prescribed small number. The code is complete and has been checked against the known single and mixed mode open crack results and has been implemented in the rough crack mixed-mode code, but no parameter studies have been performed.

4.c. Specimen Analysis and Wear Analysis

A BEM mesh for the uncracked compact tension specimen specimens used in the experiments at UNH has been completed. It is being subjected to shear loading at the pin holes and the notch displacements and crack plane stresses are being evaluated. Convergence of the results with respect to the mesh is being studied now.

Further work on the wear formulation for the sawtooth asperity model has been done. The calculation of the mean shear stress in the asperities along potential wear planes has been added along with a critical flow stress criterion. This is similar to what is proposed for the single contact model in Section 3.

4.d. Stochastic Modeling of Randomly Rough Surfaces

One of the PI's (D.A.M.) has served as co-adviser for the Ph.D. dissertation research of C. Pecorari (dissertation completed August 1992), who was supported on a grant to the other co-adviser, L. Adler (Dept. of Welding Engineering, OSU). The work involved the stochastic and micro-mechanical modeling of rough solid-solid interfaces for use in numerical computations of the scattering of elastic waves by the interface. The application is ultrasonic inspection of imperfect, cracked interfaces. This work is directly applicable to the present effort and has resulted in two publications and one presentation to date. Applying these ideas to our crack models is one of the future goals.

Figure 11

K_{II} vs. K_{IIapp} for various values of applied tension N .
 $[G_1 = G_2 = 80 \text{ GPa}, \nu_1 = \nu_2 = 0.3, \alpha = 40^\circ, \mu = 0.2, a = 5 \text{ mm}]$

Figure 12

Mode I Enhancement

K_I vs. K_{IIapp} for various values of applied tension N .
 $[G_1=G_2=30 \text{ GPa}, \nu_1=\nu_2=0.3, \alpha=40^\circ, \mu=0.2, a=5 \text{ mm}]$

Figure 13

Dependence on Surface Asperity Properties

Stress Intensity Factors vs. asperity slope for various
coefficients of friction μ . The state of contact
is shown for the case of $\mu = 1.0$

[$G_1=G_2=80$ GPa, $\gamma_1=\gamma_2=0.3$, $N=30$ MPa, $S=130$ MPa, $a=5$ mm]

Figure 14

Bi-Material Mismatch Effect

K_{II} vs. β for two asperity configurations. [$N = 0$, $S = 400 \text{ MPa}$]

$$\beta = \frac{1}{2} \frac{G_2(1 - 2\nu_1) - G_1(1 - 2\nu_2)}{G_2(1 - \nu_1) + G_1(1 - \nu_2)}$$

Figure 15

END

DATE
FILMED

5 / 4 / 93