**Coal Liquefaction Process
Streams Characterization
and Evaluation**

**Quarterly Technical Progress
Report, October 1 through
December 31, 1991**

G. A. Robbins, S. D. Brandes
R. A. Winschel, F. P. Burke

March 1992

CONSOL INC.
Research & Development
4000 Brownsville Road
Library, PA 15129

Prepared for the:

United States Department of Energy
Under Contract No. DE-AC22-89PC89883

U.S. DOE Patent Clearance was provided by
Chicago Operations Office on March 3, 1992.

MASTER

APR 13 1992

NOTICE

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States nor any agency thereof, nor any of their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for any third party's use or the results of such use of any information, apparatus, product or process disclosed in this report, or represents that its use by such third party would not infringe privately owned rights.

**Coal Liquefaction Process
Streams Characterization
and Evaluation**

**Quarterly Technical Progress
Report, October 1 through
December 31, 1991**

G. A. Robbins, S. D. Brandes
R. A. Winschel, F. P. Burke

March 1992

CONSOL INC.
Research & Development
4000 Brownsville Road
Library, PA 15129

Prepared for the:

United States Department of Energy
Under Contract No. DE-AC22-89PC89883

U.S. DOE Patent Clearance was provided by
Chicago Operations Office on March 3, 1992

TABLE OF CONTENTS

	<u>Page</u>
INTRODUCTION	1
Overview	1
Contract Objectives	2
Contract Activities - This Period	3
RESULTS AND DISCUSSION	6
Wilsonville Run 261	6
Summary	6
Wilsonville Run 261 Overview	10
Plant Description	14
Abbreviated History of Wilsonville Run 261	16
Sample Descriptions	24
Analyses	24
Process Oil Properties	25
850°F ⁺ Resid Conversion and Kinetics	29
Comparison of Oils From Run 261 With Oils From Run 257	35
Analyses of Wilsonville Runs 260D and 259G Net Products and Fractions	38
Procedure	38
¹ H-NMR Results	38
GC/MS Results	39
Phenolic -OH Concentrations	40
Caustic Washing of Wilsonville Run 260D Net Product Fractions	41
Summary	41
Introduction	41
Procedures	42
Results	43
Reactivity Comparison of Wilsonville Black Thunder Coals	45
Background	45
Results and Discussion	45
Participants Program Status	47
Summary	47
Discussion	48
Consol Evaluation and Executive Summaries of Final Reports from Western Research, The Pennsylvania State University, SRI International, and Virginia Polytechnic Institute and State University	51
General Description	51
Western Research Institute	51
Summary	51
Program Description	52
Methodology	52
Major Findings	53
CONSOL Evaluation	54
Further Development	55
Statement of Work	55
WRI Executive Summary	57
The Pennsylvania State University	59
Summary	59
Program Description	60
Methodology	61

TABLE OF CONTENTS (Continued)

	<u>Page</u>
The Pennsylvania State University	
Major Findings	62
CONSOL Evaluation	63
Further Development	64
Statement of Work	65
PSU Executive Summary	67
SRI International	71
Summary	71
Program Description	72
Methodology	73
Major Findings	74
CONSOL Evaluation	75
Further Development	77
Statement of Work	77
SRI Executive Summary	79
Virginia Polytechnic Institute and State University	81
Summary	81
Program Description	82
Methodology	82
Major Findings	83
CONSOL Evaluation	85
Further Development	86
Statement of Work	87
VPI Executive Summary	88
Participants Program - Interim Assessment	92
Summary	92
Introduction	92
Program Organization	93
Phase I	93
Technical Evaluation	94
Program Direction - Recommendations	96
EXPERIMENTAL	98
REFERENCES	99

LIST OF TABLES

<u>Table</u>	<u>Page</u>
1 Operating Conditions and Yields for Material Balance Periods - Wilsonville Run 261	102
2 Component Distribution of V-131B Samples - Wilsonville Run 261	104
3 Component Distribution of V-1067 Samples - Wilsonville Run 261	104
4 Component Distribution of R-1235 Samples - Wilsonville Run 261	105
5 Solubility Fractionation of V-131B Samples - Wilsonville Run 261	105
6 Solubility Fractionation of V-1067 Samples - Wilsonville Run 261	106

LIST OF TABLES (Continued)

<u>Table</u>	<u>Page</u>
7 Solubility Fractionation of R-1235 Samples - Wilsonville Run 261	106
8 Proton Distribution of V-131B Whole Samples - Wilsonville Run 261	107
9 Proton Distribution of V-1067 Whole Samples - Wilsonville Run 261	107
10 Proton Distribution of R-1235 Whole Samples - Wilsonville Run 261	108
11 Proton Distribution of V-131B Distillate Samples - Wilsonville Run 261	108
12 Proton Distribution of V-1067 Distillate Samples - Wilsonville Run 261	109
13 Proton Distribution of R-1235 Distillate Samples - Wilsonville Run 261	109
14 Proton Distribution of V-131B Resid Samples - Wilsonville Run 261	110
15 Proton Distribution of V-1067 Resid Samples - Wilsonville Run 261	110
16 Proton Distribution of R-1235 Resid Samples - Wilsonville Run 261	111
17 Phenolic -OH Concentration by FTIR - Wilsonville Run 261	111
18 Microautoclave Test Results - Wilsonville Run 261	112
19 Conversion of Resid Components - Wilsonville Run 261	113
20 850°F ⁺ Conversion and Kinetics - Wilsonville Run 261	114
21 Comparison of Wilsonville Runs 257 and 261 - Operating Conditions	115
22 Comparison of Wilsonville Runs 257 and 261 - Process Performance and Yields	115
23 Comparison of Wilsonville Runs 257 and 261 - Process Oil Characteristics, Conversions and Kinetic Constants	116
24 Proton Distributions of Crude Oil Fractions - Wilsonville Runs 260D and 259G	117
25 Phenolic -OH and Total Oxygen Contents of Crude Oil Fractions - Wilsonville Runs 260D and 259G	117
26 Results of Caustic Washing of Wilsonville Run 260D Crude Oil Fractions	118
27 ¹ H-NMR Analyses of Caustic Washing Raffinates - Wilsonville Run 260D Crude Oil Fractions	118
28 Compositions of Phenolic Extracts by GC/MS - Wilsonville Run 260D Crude oil Fractions	119
29 Subcontractors - Phase I	120

LIST OF FIGURES

<u>Figure</u>	<u>Page</u>
1 Simplified CC-ITSL Process Diagram for Wilsonville Run 261	121
2 Partial CC-ITSL Process Diagram for Wilsonville Run 261 Showing Major Distillate Streams	122
3 Component Distribution of Whole Feed (V-131B) Oils From Wilsonville Run 261	123

LIST OF FIGURES (Continued)

<u>Figure</u>		<u>Page</u>
4	Component Distribution of Whole Product (V-1067) Oils From Wilsonville Run 261	124
5	Component Distribution of Whole Interstage (R-1235) Oils From Wilsonville Run 261	125
6	Solubility Fractionation of V-131B THF-Soluble 850°F ⁺ Resid Samples From Wilsonville Run 261	126
7	Solubility Fractionation of V-1067 THF-Soluble 850°F ⁺ Resid Samples From Wilsonville Run 261	127
8	Solubility Fractionation of Interstage THF-Soluble 850°F ⁺ Resid Samples From Wilsonville Run 261	128
9	Proton Distribution of V-131B Distillate and THF-Soluble Resid Samples (850°F ⁺ Cutpoint) From Wilsonville Run 261	129
10	Proton Distribution of V-1067 Distillate and THF-Soluble Resid Samples (850°F ⁺ Cutpoint) From Wilsonville Run 261	130
11	Proton Distribution of Interstage Distillate and THF-Soluble Resid Samples (850°F ⁺ Cutpoint) From Wilsonville Run 261	131
12	Phenolic -OH Concentrations of Distillate and THF-Soluble Resid Samples (850°F ⁺ Cutpoint) from Wilsonville Run 261	132
13	Microautoclave Solvent Quality Assays of Samples From Wilsonville Run 261	133
14	First-Stage and Total Conversions of THF-Soluble 850°F ⁺ Resid and coal + IOM for Wilsonville Run 261	134
15	THF-Soluble 850°F ⁺ Conversions for Wilsonville Run 261	135
16	Conversion of Oils (Hexane Solubles) in Wilsonville Run 261	136
17	Conversion of Asphaltenes in Wilsonville Run 261	137
18	Conversion of Preasphaltenes in Wilsonville Run 261	138
19	Resid + UC Conversion Activity in Wilsonville Run 261	139
20	Catalyst Activity for Resid + UC Conversion in Wilsonville Run 261	140
21	Total Ion Chromatogram, Naphtha Fraction, Wilsonville Run 260D Product	141
22	Total Ion Chromatogram, Jet Fuel Fraction, Wilsonville Run 260D Product	142
23	Total Ion Chromatogram, Diesel Fuel Fraction, Wilsonville Run 260D Product	143
24	Total Ion Chromatogram, Residuum Fraction, Wilsonville Run 260D Product	144
	Key to Peak Identifications	145

APPENDIX

<u>Appendix</u>	<u>Page</u>
1 Trip Reports - Teaming Arrangements	146

ABSTRACT

COAL LIQUEFACTION PROCESS STREAMS CHARACTERIZATION AND EVALUATION, QUARTERLY TECHNICAL PROGRESS REPORT, OCTOBER 1 THROUGH DECEMBER 31, 1991

This is the ninth Quarterly Technical Progress Report under DOE Contract DE-AC22-89PC89883. Major topics reported are:

- Process oils from Wilsonville Run 261 were analyzed to provide information on process performance. Run 261 was operated with Illinois 6 bituminous coal from the Burning Star No. 2 mine and EXP-AO-60 and Criterion 324 catalysts. Run 261 was operated in the catalytic/catalytic Close-Coupled Integrated Two-Stage Liquefaction (CC-ITS²) configuration with ash recycle. Reactor volumes in use were 100% and the interstage separator was in use throughout the run. Low/high and high/low temperature configurations were used. In the last run period, a new resid injection system was tested.
- The four fractions of the crude oil from Wilsonville Run 260D and the three fractions and the crude oil from Wilsonville Run 259G were further characterized by several analytical techniques.
- The four fractions of the crude oil from Wilsonville Run 260D were washed with caustic to extract the phenolic components. The extracts from these caustic washes were characterized.
- The reactivities of two samples of Black Thunder coal from Wilsonville were compared using laboratory tests and analytical techniques.
- The status of the Participants Program is described.
- Summaries of the final reports from Western Research Institute, SRI International, Virginia Polytechnic Institute and State University, and The Pennsylvania State University are presented.
- An Interim Assessment of the Participants Program is reported.
- Three site visits were made to potential Phase II subcontractors. This completes all planned site visits. Trip summaries are appended to this report.

Section 1

INTRODUCTION

This is the Technical Progress Report for the ninth quarter of activities under DOE Contract No. DE-AC22-89PC89883. It covers the period October 1, 1991, through December 31, 1991.

OVERVIEW

Direct coal liquefaction is a complicated chemical process. Recent advances in the technology, which significantly reduced the product costs, have come about through an improved fundamental understanding of liquefaction chemistry. Further improvements are possible, and will depend on continued advances in our knowledge of process chemistry. Supplying this knowledge requires the use of a variety of the tools of analytical chemistry applied to the appropriate samples, and interpretation of the analytical data in context to process development.

The R&D Department of CONSOL INC. (CONSOL R&D) is conducting a three-year project to characterize process and product streams from direct coal liquefaction process development programs sponsored by the Department of Energy. In this project, CONSOL R&D obtains samples from current process development activities in coal liquefaction and coal-oil coprocessing, and characterizes them using established analytical techniques. In addition, selected samples are characterized by other analytical techniques to evaluate their potential for aiding process development. These analyses and interpretation of the results in relation to process operations are provided by a subcontracted project team.

In addition to samples from current process development programs, CONSOL R&D maintains a bank of coal liquids samples from the SRC-I, H-Coal, ITSL (Lummus and Wilsonville) and HRI-CTSL coal liquefaction programs, and the Lummus, HRI and UOP coprocessing development programs. These samples, which represent important stages in the recent development of coal liquefaction technology, are also used in the analytical program.

CONTRACT OBJECTIVES

CONSOL R&D is conducting a three-year program to characterize process and product streams from direct coal liquefaction process development projects. The program objectives are two-fold: 1) to obtain and provide appropriate samples of coal liquids for the evaluation of analytical methodology, and 2) to support ongoing DOE-sponsored coal liquefaction process development efforts. The two broad objectives have considerable overlap and together serve to provide a bridge between process development and analytical chemistry.

More specifically, the first objective is to identify, collect and disburse appropriate samples of coal liquids for analysis by techniques that hold promise, but are not fully demonstrated, for use in liquefaction process development efforts. Samples are chosen from ongoing DOE-funded liquefaction and coprocessing projects and from CONSOL's collection of coal liquids produced during the past ten years. Samples are chosen based on their relevance to process development programs, and are well-documented in terms of feedstocks, sampling location, time and operating conditions. The samples chosen are sufficient to judge the applicability of the analytical methods being evaluated. These process oils are analyzed by CONSOL R&D in a base characterization program using techniques established in previous CONSOL research. Selected samples also are provided to project team participants (as subcontractors), other researchers active in the analysis of coal liquids, who characterize them using a range of methods beyond those used in the base program. Subcontracts to approximately 16 organizations that have specialized analytical capabilities are a major aspect of this work. Individual analytical specialists from the subcontractors take a major role in interpreting their own results in context to the liquefaction process, and not merely provide data. This portion of the program includes an evaluation of the utility of promising analytical techniques for providing useful information for coal liquefaction process development; those results will be applied to ongoing development efforts. This evaluation will be based on the usefulness of an analytical method in

process monitoring, to obtain specific chemical information, and as judged by precision and accuracy.

The second objective is to support the process developers. This includes support in the form of providing results and interpretation of data obtained with the analytical techniques being assessed. However, more directly, appropriate process oils are being characterized in the base program by a variety of standard techniques that have proven relevance to development efforts. The results from these more routine analyses aid plant operations and planning. Also, these results provide the data needed to select appropriate samples for the non-routine techniques and provide a set of data for correlations with the results of the more exploratory techniques.

CONTRACT ACTIVITIES - THIS PERIOD

Contract activities for this quarter are listed below. Each topic is summarized and discussed in detail under a separate heading in Section 2, Discussion. Because each topic is summarized, where appropriate, in the corresponding section of the Discussion, no overall Summary section is provided in this report.

- A set of twenty-one process oils from Wilsonville Run 261 were analyzed to provide information on process performance. Run 261 was operated with Illinois 6 bituminous coal from the Burning Star No. 2 mine and with two different catalysts. Run 261 was operated in the catalytic/catalytic Close-Coupled Integrated Two-Stage Liquefaction (CC-ITSL) configuration with ash recycle. Reactor volumes in use were 100% and the interstage separator was in use throughout the run. Low/high and high/low temperature configurations were used. The catalysts used were EXP-AO-60 and Criterion 324, both Ni/Mo on alumina support, and equivalent to Amocat 1C and Shell 324, respectively. In the last run period, a new resid injection system was tested. The objectives for Run 261 were to obtain high performance in the catalytic/catalytic low/high mode of operation, to evaluate the performance of both catalysts, and to obtain a better-

defined boiling end-point of the distillate product. Run 261 was the first Wilsonville run which began with low/high temperature operation, and in which fresh catalyst was aged to equilibrium in this mode. It was the first run with Illinois 6 coal which was made with the changes in the product distillation system. It was also the first run made with the EXP-AO-60 catalyst.

- The four fractions of the net product crude oil from Wilsonville Run 260D and the three fractions and the net product crude oil from Wilsonville Run 259G were further characterized by several analytical techniques.
- The four fractions of the crude oil from Wilsonville Run 260D were washed with caustic to extract the phenolic components. The extracts from these caustic washes were characterized.
- The reactivities of two samples of Black Thunder coal from Wilsonville were compared using laboratory tests and analytical techniques.
- A status report of progress made in the Participants Program during the ninth quarter is given here. Four final reports and one draft final report were received from Phase I subcontractors. Phase I now is nearly complete.
- The final reports were received from Western Research Institute, SRI International, Virginia Polytechnic Institute and State University, and The Pennsylvania State University, completing their subcontracts under Phase I of the Participants Program. Those reports are summarized here, and will be issued later as topical reports.
- An Interim Assessment of the Participants Program was made and is reported here.

- Three site visits were made to potential Phase II subcontractors. This completes all planned site visits. Trip summaries are appended to this report.
- Phase II progress includes the issuance of eight statements of work and four purchase order subcontracts; three subcontracts were initiated. Nine proposals were rejected for various reasons.
- Ongoing work, in addition to the Participants Program, includes the analysis of samples from Wilsonville Run 262, and evaluation of the alkylation work in which the role of phenolic groups in donor solvent properties is being examined.
- R. A. Winschel co-chaired a session on "Applied Liquefaction" at the Eighth Annual International Pittsburgh Coal Conference.
- F. P. Burke participated in the DOE-PETC/AIST-NEDO joint technical exchange meeting in Fukuoka, Japan. F. P. Burke and R. A. Winschel participated in the DOE/PETC Low-Rank Coal Liquefaction Workshop, September 6, 1991.

Section 2

RESULTS AND DISCUSSION

WILSONVILLE RUN 261

SUMMARY

CONSOL analyzed twenty-one process oils from Wilsonville Run 261, which was operated in the catalytic/catalytic Close-Coupled Integrated Two-Stage Liquefaction (CC-ITSL) configuration with ash recycle. Run 261 was operated with Illinois 6 bituminous coal from the Burning Star No. 2 mine and EXP-AO-60 and Criterion 324 catalysts. Other conditions included 100% reactor volumes in use, interstage separator in use, low/high and high/low temperature configurations. In the last run period, a new resid injection system was tested. The major results from CONSOL's analyses are summarized below.

- Consistent with Wilsonville observations, CONSOL analytical results show that many properties of oils from periods A through D differed significantly from those from periods E through G. The change in properties resulted from changes in many process conditions after period D, which are described in the main body of the report. The greatest change evident in oil properties occurred from period D to period E. The process oils increased significantly in resid and distillate aromaticity, decreased in paraffinicity, and decreased in hydroaromaticity from D to E. Significant increases in the phenolic -OH concentrations of all distillates and the V-131B resid also took place. Whole-oil donor solvent quality was similar to that of the distillates in periods A through D. During periods E-G, the donor quality of the distillates increased by several wt% MAF, whereas the whole-oil donor quality fell by about 15 wt% MAF. In spite of the decreased resid quality in periods E-G, concentrations of oils, asphaltenes, preasphaltenes in the resids did not change. Furthermore, there was relatively little change in phenolic -OH concentration in the resids, but substantial changes in the distillates. The solvent quality and aromaticity changes correspond

closely to observations at Wilsonville of lower pasting solvent quality and lower hydrogen in the pasting and interstage solvent during operation with Criterion catalyst. In some respects, periods E-G were similar to Run 259 with Ireland coal, in that high aromaticities were observed with moderately low space velocities.

- Many oil properties did not change substantially from periods A through D, and from periods E through F. However, from period B to C there was a noticeable increase in resid preasphaltene concentration, an increase in resid aromaticity, and an increase in resid phenolic -OH concentration. The condition changes from B to C were a decreased coal feed rate and an increased catalyst age through batch aging. These conditions are expected to have opposing effects on most oil properties. Since the resid properties became worse, it appears that the higher catalyst age dominated the changes in resid properties, with no substantial change in distillate properties.
- Resid injection had a minor impact on some oil properties, although distillate and resid yields differed from period F (no resid injection) to period G (resid injection). Resid concentration, resid preasphaltene concentration, resid and distillate aromaticity, and resid and distillate phenolic -OH concentration decreased by small amounts in period G in many of the process oils. Since period F was unstable and period G was transitional, and they were otherwise nominally equivalent conditions, no attempt was made to attribute the observed property differences to variation in any particular operating condition.
- In general, the first-stage 850°F⁺ conversion activities for periods B-D of Run 261 were relatively high, and the second-stage conversion activities were relatively low. First-stage and second-stage conversion activities were both low during periods E-G. Observations made from a plot of conversion activity vs catalyst age were: 1) the 850°F⁺ resid + UC conversion activity of each catalyst type was higher when it was used in the first stage; 2) the conversion

activity during operation with Criterion 324 catalyst was consistently lower than during operation with EXP-AO-60 catalyst; and 3) there was little or no detectible loss in conversion activity with increasing catalyst age. Deactivation rate constants obtained by catalyst type and reactor stage were not significantly different from zero. The initial conversion activity of the Criterion 324 catalyst was calculated to be higher for the second stage than for the first stage (borderline statistical significance). The first-stage 850°F⁺ conversion activity was highest in period B and consistently decreased from then on. Period B has the highest activity CONSOL has calculated for a run period since we began calculating them with Run 250. If the high first-stage activity is not an artifact of the high space velocity used in period B, perhaps it is related to the onset of catalyst replacement late in period A. Period A was unusual in that the second-stage conversion was slightly higher than that of the first stage. The first-stage activity was low, and the second-stage activity was high for period A.

- Process oil properties, 850°F⁺ resid + IOM conversions, and kinetic constants for selected periods of Runs 261 and 257 were compared because both runs were made with Illinois 6 feed coal. Periods 257E, 257J, 261B, 261D, and 261E were chosen for comparison. Note that the Run 257 periods differed from the Run 261 periods in many process conditions. Distillate and resid aromaticities were higher in the Run 261 oils. Many 261B oil properties were equivalent to those from 257E and J. The properties of oils from periods 261D and E were generally worse than those from the other periods. Conversions of 850°F⁺ resid (including coal and IOM), and the corresponding rate constants and activities for periods 261B and D were generally equivalent to or greater than those in the Run 257 periods, whereas, the values for period 261E generally were smaller than those in the Run 257 periods.
- In general, the soluble resid and its asphaltene and preasphaltene components showed net yields (negative conversions) in the first-

stage reactor and the overall system, but positive conversions in the second stage. In contrast, the first-stage, second-stage, and total conversions of the oil component of the resid generally were near zero. Large yields (negative conversions) of preasphaltenes in the first stage suggest that preasphaltenes are the primary coal solubilization product. However, consistently high conversion of preasphaltenes took place in the second stage. The total system conversions (negative, and thus, net yields) of preasphaltenes were greater than those of the asphaltenes. The soluble resid and most of its components showed a net yield (negative conversion) on average and in most balance periods. This is consistent with Wilsonville having net resid yields in all the balance periods.

- The total system conversion of soluble resid and most of its components reached a maximum or relative maximum with period D. This seems to be consistent with Wilsonville's results, which gave the lowest resid yield in period D.
- The average ratios of CONSOL conversions to Wilsonville conversions in Run 261 were compared with those from previous runs. The average ratios for Run 261 periods B-D were high for the first-stage and total, and moderate for the second stage. The average ratios for Run 261 periods E-G were typical of the Run 250-259 average (but high for the 257 average) in the first stage, and low in the second stage and total system. A ratio higher than one indicates that the percentage conversion of 850 x 1050°F material is relatively greater than the percentage conversion of 1050°F+ material. The ratio for the first stage in 261B-D is quite high and is greater than unity, suggesting high 850 x 1050°F conversion. A number of possible reasons for this are discussed in the report text. Wilsonville reported negative yields of 850°F-endpoint distillate for periods A through D of Run 261. The average conversion ratio for the first stage in 261E-G was near unity, indicating the same conversion of 850 x 1050°F as of 1050°F+. The average second-stage Run 261 ratios show lower ratios than unity, as is typically observed.

- As is typically observed, the second stage provided very little additional conversion of coal + IOM, but provided a substantial part of the THF-soluble 850°F⁺ conversion. The soluble resid conversion was negative for the first stage (there was a net yield), but was higher (and positive) for the total system. The conversion of soluble resid was relatively low in periods A, E, and G for the first stage and total system. The first-stage and total system conversion of 850°F⁺ (including coal and IOM) as calculated by CONSOL was lower in periods E-G relative to periods A-D, in agreement with Wilsonville observations. To some degree, the first-stage and total THF-soluble resid conversions also show this.
- The V-131B samples show a jump in 850°F⁺ resid concentration from period C to D, as a result of the increase in target resid concentration in the pasting solvent. Resid concentration in the R-1235 and V-1067 samples appears to increase from C to D to E, as a result of an increase in the target recycle resid concentration and the operation at higher temperature, different catalyst, etc.
- There was a decrease in the preasphaltenes concentration and in the phenolic -OH concentration of the THF-soluble V-131B and V-1067 resids from period A to B. This may have resulted from the transitional nature of period A, the increase in recycle resid from period A to period B, or the change from batch aging to catalyst replacement, which began in the latter part of period A. The addition of fresh catalyst might increase the defunctionalization activity, even though catalyst ages were nominally equivalent in A and B.

WILSONVILLE RUN 261 OVERVIEW

CONSOL analyzed 21 process oils from Wilsonville Run 261 which was operated with Illinois 6 bituminous coal from the Burning Star No. 2 mine and with two catalysts (one bimodal, one unimodal) in different run segments.¹ Run 261 was operated from January 12 through May 31, 1991 in the catalytic/catalytic mode of operation with ash recycle. Although the entire run was planned to use the low/high temperature sequence, because

of certain operating constraints, the second-stage temperature was slightly lower than the first-stage temperature in the last two of seven periods of operation. The catalysts used were EXP-AO-60 (bimodal) and Criterion 324 (unimodal), both Ni/Mo on 1/16" extrudate alumina support. These catalysts are equivalent in all respects to Amocat 1C and Shell 324, respectively. In practical terms, they may be considered as name changes only. The catalysts used in Run 261 represent different sources and production runs from those previously designated Amocat 1C and Shell. Criterion 324 is a version of Shell 324 produced in Europe. EXP-AO-60 is an experimental catalyst which is equivalent to Amocat 1C (i.e., nominally made to the same specifications).² However, the catalysts differ in some physical properties. For example, the EXP-AO-60 catalyst had a lower bulk density and a higher surface area than the Amocat 1C. The EXP-AO-60 was produced for Amoco by Akzo in the 1/16" pellet size for good ebullation performance. The 1/12" Amocat 1C previously tested showed some breakage in Run 257³ and also in period A of Run 259.^{4,5} Prior to that, 1/16" Amocat 1C was used in Runs 251, 251-II⁶, and 252⁷.

Run 261 was made using 100% of the available volume of both reactors and the interstage separator was in use throughout the run. The major operating variables were catalyst variables (type, age, and replacement rate), reactor temperatures, coal feed rate (and consequently, space velocity), and resid concentration. Because of operating difficulties, the ashy recycle stream was changed from V-1082 bottoms to V-1067 (see Figure 1) during the period from January 22 through March 2 (periods A and B).

In the last run period (period G), a new resid injection system was tested. This system provides a way to inject most of the resid directly, without mixing it as a pasting solvent component. It was designed to lower the recycle resid inventory requirements for the plant, and thereby to decrease the plant's equilibration time.

The objectives for Run 261 were: 1) to obtain high performance in the catalytic/catalytic low/high mode of operation with Illinois 6 coal and the new bimodal catalyst EXP-AO-60, 2) to evaluate performance of the new

catalyst, 3) to obtain a better-defined boiling end-point of the Illinois 6 distillate product, and 4) to obtain steady-state data operating with Criterion 324 catalyst and Illinois 6 coal.

Run 261 was the first Wilsonville run which began with low/high temperature operation, and in which fresh catalyst was aged to equilibrium in this mode. It was the first run with Illinois 6 coal which was made with the changes in the product distillation system (in use beginning with Run 259). It was also the first run made with the EXP-AO-60 catalyst.

Operating period A was transitional, but period B was stable. Periods A and B had most conditions in common. Although the target resid concentration in the recycle solvent was 40 wt %, resid conversion was higher than anticipated and resid concentrations of only 32.7 wt % and 38.3 wt %, respectively, could be achieved in periods A and B. Coal conversion was 91-92 wt % MAF, typical for the Burning Star 2 Mine coal. However, in period C, the coal conversion increased to nearly 94 wt % MAF. The first-stage coal conversion became as high as 90 wt % MAF in periods C and D when operating at 790°F in the first stage, and higher yet to 92 wt% MAF in periods E through G, when the first stage was operated at 809°F. Distillate yields were 59 and 64 wt % in periods A and B, respectively, with corresponding resid yields of 7 and 5 wt %. Period B was considered to be "all-distillate" operation. Period D was also "all-distillate" with a distillate yield of about 66 wt% MAF and a resid yield of 3.7 wt%. This was similar to the 261B results obtained with a higher coal feed rate and catalyst replacement rate. Thus, the higher catalyst replacement rate in period B allowed a higher coal throughput, even with a lower resid recycle. Prior to period E, the bimodal EXP-AO-60 catalyst used in periods A through D was removed from both reactors and replaced by aged unimodal Criterion (Shell) 324 catalyst from Run 259. Period E was run with 810/825°F target reactor temperatures. Distillate and resid yields were 61 and 5 wt %, respectively. For periods F (unstable) and G (transitional), the catalyst replacement rate was lowered from 3.0 to 2.25 lb/T MF coal (each reactor). This required a lower coal feed rate; however, at the lower feed rate the reaction heat was inadequate to maintain the second-stage

target temperature of 825°F. Second-stage temperature was 800°F for those periods. Period F gave distillate and resid yields of 58 and 10 wt %, respectively. During period G, the resid injection system was tested. Distillate yield was 64 wt%, and resid yield was 5 wt% during period G.

In the resid circulation test, a 50 wt % coal slurry was prepared with V-1074 distillate solvent. Two separate storage and feed systems handle deashed and ashy resid, respectively. The resid streams are injected at the proper feed rates into the slurry feed line just after the slurry feed pump, which pumps the feed through the preheater and into the reactor. The goal of the test was to test operability with 50 wt % resid and 12 wt % CI in the recycle solvent, at a 33 wt % coal concentration. At these conditions, the 50 wt % coal-distillate slurry constituted about two-thirds of the feed to the reactor, the remainder being the two resid streams in the proper proportions. When operation became difficult, coal and/or resid concentration was reduced and the coal-distillate slurry was diluted further with resid. This caused the required resid inventory to be greater than the minimum possible (ideal case), but it was still substantially reduced from the previous requirements (about 10,000 lb). In the ideal case, it is projected that the resid inventory requirements could be reduced to approximately 3,000 lb. The test was largely successful, although the coal concentration in the slurry could not be made as high as desired. The target was 57 wt % coal in the slurry, which corresponds to a total feed composition of 33 wt % coal, 50 wt % resid and 12 wt % cresol insolubles. The highest concentration practical was 50 wt % coal in the slurry. Period G was considered transitional due to fluctuations in feed composition, inventories, etc., but the yields during the test indicated good overall performance. Distillate and resid yields were 64 and 5 wt %, respectively.

Wilsonville's results from Run 261 generally showed poorer performance with Criterion 324 catalyst than with the experimental Amoco catalyst EXP-AO-60. When the plant began using the Criterion catalyst, several changes occurred: recycle solvent quality decreased, hydrogen content of the process solvent and interstage streams decreased, resid + UC conversion decreased, and nitrogen content of the catalyst increased.

No "all-distillate" product slate was obtained during periods E-G. It was also concluded that operation above 825°F in a catalytic reactor was detrimental, because of high gas yields. An unusually low proportion of the Criterion catalyst was recovered from the second stage at the end of the run. Catalyst breakage or accumulated error in addition and withdrawal have been offered as explanations for the low recovery. Wilsonville observed high catalyst activity with the new bimodal catalyst. Carbon deposition was higher on EXP-A0-60 from Run 261 than on Amocat 1C from Run 257. At a given carbon content, however, the new catalyst was found to be more active than the Amocat. Reportedly, there has been no evidence for break-up of the 1/16" EXP-A0-60 catalyst as was observed when the 1/12" Amocat 1C was used. Product distillates from periods A through E had boiling end-points of about 752-786°F.

Operating conditions and yields¹ for material balance periods appear in Table 1. A simplified flow scheme⁸ of the Wilsonville plant, as configured for Run 261, appears in Figure 1. More detail on the part of the plant involving the major distillate streams is shown in Figure 2.

PLANT DESCRIPTION

During Run 261, the Wilsonville plant was operated in the catalytic/catalytic CC-ITSL mode with ash recycle. The plant configuration during standard operation (most of the run) is described below. Exceptions to the standard configuration are described after that, for operation with ashy recycle from V-1067 (instead of ashy recycle from V-1082 bottoms), and for operation with the resid injection system. For standard operation, coal was slurried with a mixture of second-stage vacuum-flashed bottoms (ashy resid, V-1082 bottoms), second-stage heavy distillate (V-1074), and deashed second-stage product resid (V-130). The pasting solvent stream is called V-131B. CONSOL received a sample of this stream as the first-stage feed. The slurry was mixed with hydrogen and passed through the preheater and first-stage ebullated-bed reactor (R-1235). Run 261 was made with the interstage separator (V-1258) in place. The interstage separator removed the gas and light products from the first-stage products prior to processing in the second stage. The

liquid portion of the separator overheads was sent to the product distillation system. The separator bottoms were sent to the second stage, along with make-up hydrogen. Each interstage sample received by CONSOL consisted of the feed to the second stage. The second-stage ebullated-bed reactor was R-1236. Gases and light oils were separated from the second-stage product in an atmospheric flash (V-1250). The atmospheric flash bottoms (V-1067) were separated in a vacuum flash into distillate (V-1082 overheads) and resid (V-1082 bottoms). Samples of the V-1067 material were received by CONSOL as second-stage product samples. It contains ash, IOM, resid and distillate-range material, and represents the recycled material prior to fractionation into distillate, ashy resid, and deashed resid components. A portion of the V-1082 bottoms stream was recycled to the first stage as a component of the pasting solvent. The remainder of the V-1082 bottoms stream was deashed in the Kerr-McGee ROSE-SR (formerly called Critical Solvent Deashing) unit, which rejected an ash concentrate and produced a deashed resid product (V-130). The deashed resid was recycled back to V-131B as the second component of the pasting solvent. The atmospheric flash overhead liquids and the V-1082 overheads were sent to the distillation system (consisting of the T-105 atmospheric tower, followed by the T-102 vacuum tower), which produced naphtha (V-161, the T-105 overheads), middle-distillate (V-182, the T-102 overheads), and heavy distillate (V-1074, the T-102 bottoms). The heavy distillate was recycled as the third component of the pasting solvent. The withdrawal tube flush during Run 261 consisted of T-102 vacuum column overheads (V-182), the middle distillate product.

The exception to the standard plant operation is described here for V-1067 recycle. For most of Run 261 (from January 12 through January 22 and from March 2 through May 31, as described above), the V-1074 stream was the only source of distillate solvent for recycle. During these periods, all of the V-1067 material was sent to the vacuum flash unit, V-1082. The other two components of the recycle solvent were the V-1082 bottoms stream (i.e., the ROSE-SR unit feed stream, which contains the resid, IOM and ash portion of V-1067) and the deashed resid (V-130). During V-1067 recycle (January 22 through March 2), a portion of the V-1067 was recycled directly in place of the V-1082 bottoms. This

provided the recycle of ashy resid and some distillate. V-1074 (at a relatively reduced rate) supplied the remainder of the distillate, and the deashed resid (V-130) was recycled as in the rest of the run. Recycle of V-1067 reduced the flow through V-1082 and through T-102, relative to operation with recycle of V-1082 bottoms. During V-1082 bottoms recycle on March 2 through the end of the run, all the distillate went through the T-105/T-102 distillation system. All the 850°F⁺ distillate was recycled, since the T-102 bottoms made up the distillate portion of the recycle oil. V-1082 bottoms recycle also resulted in slightly less recycle of 650-850°F material after periods A and B (when V-1067 recycle was in effect).

In operation without resid injection (January 12 through May 23), all the components of the recycle oil (process or pasting solvent) were combined in V-131B to make the slurry oil. The slurry was prepared batchwise in V-101A by adding the coal. During resid injection (May 23 through May 31), the oil used for slurry preparation consisted of distillate only, or distillate plus some deashed resid. The remaining deashed and ashy resid required to achieve the target composition for the recycle material was injected separately through pump P-1090 (for deashed resid) and through pump P-1091 (for V-1082 bottoms). Slurry was still prepared batchwise in V-101A, but the oil used to prepare coal slurry contained no ashy resid (some batches contained no resid at all).

ABBREVIATED HISTORY OF RUN 261

This section is paraphrased from Wilsonville technical review meeting handouts.¹ Run 261 began on January 12, 1991, in the catalytic/catalytic CC-ITSL mode feeding Illinois 6 bituminous coal. The first-stage reactor was R-1235 and the second-stage reactor was R-1236. Both reactors were configured to use 100% of the available reactor volume. The interstage separator (V-1258) was in use throughout the run, but did not remove all the gas during operation at the highest coal feed rate (January 28-February 25).

The first- and second-stage reactors were charged with 242 and 241 lbs (dry), respectively, of EXP-A0-60 1/16-inch (Ni/Mo) catalyst. Subsequent additions of catalyst on January 14 (first stage) and January 23 (second stage) brought the charge up to 270 lb (dry) in each reactor. The start-up solvent was made from distillate from Run 257 (Burning Star 2 coal) and solids and resid from Run 260 (Black Thunder coal). Start-up conditions were: 450 MF lb/hr coal feed rate, 33 wt % coal in the slurry (2.0 solvent/coal ratio), 40 wt % resid (target) and 12 wt % cresol insolubles (CI) in the recycle solvent, and 760/810°F reactor temperatures.

On April 12, the run restarted with 1/16" Criterion 324 catalyst. In order to shorten the time required to get to the desired equilibrium age for the run, a mixed catalyst consisting of aged catalyst from Run 259 (Ireland coal) and fresh presulfided catalyst was loaded into the reactors. The first-stage catalyst consisted of 286.3 lb Shell 324 1/16" from Run 259 (catalyst age 810 lb MF coal/lb cat, or 1573 lb resid+CI/lb cat) and fresh presulfided Criterion 324 catalyst to bring the charge to 440 lb catalyst. The starting age for the mixed first-stage catalyst was 527 lb MF coal/lb cat, or 1024 lb resid + CI/lb cat. The second-stage catalyst consisted of 302.6 lb Shell 324 1/16" from Run 259 (catalyst age 821 lb MF coal/lb cat, or 1971 lb resid + CI/lb cat) and fresh presulfided Criterion 324 catalyst to bring the charge to 440 lb catalyst. The starting age for the mixed second-stage catalyst was 565 lb MF coal/lb cat, or 1356 lb resid+CI/lb cat. Re-start-up conditions were: 425 MF lb/hr coal feed rate, 33 wt % coal in the slurry (2.0 solvent/coal ratio), 50 wt% resid (target) and 12 wt % cresol insolubles (CI) in the recycle solvent, and 810/825°F reactor temperatures.

A chronological account of the run follows:

Jan 12, 1991: Run 261 started.

Jan 13: An outage lasting several hours was caused by a steam line leak.

Jan 14: 50.5 lb of catalyst was added to the second stage (R-1236) according to the run plan.

Jan 15: The ROSE-SR unit was not deashing. The high solvent content in the ROSE-SR feed (V-1082 bottoms) was attributed to the high coal feed rate. The coal feed rate was lowered from 450 to 400 lb/hr to reduce the feed rate to the vacuum flash unit (V-1082).

The withdrawal tube flush rate in the second stage was erratic, affecting the reactor temperature profile.

Jan 17: The hydrogen flow to the second stage was low due to a compressor problem.

Jan 18: Because the resid inventory was low, the coal feed rate was increased from 400 to 425 MF lb/hr.

Jan 21: Because the resid inventory was low, the coal feed rate was increased from 425 to 450 MF lb/hr.

5 lb of catalyst was added to the second stage (R-1236) according to the run plan.

Jan 21-22: An outage resulted from slurry recirculation problems.

Jan 22: The solvent content in the ROSE-SR feed was still high, so ashy recycle was taken from V-1067, instead of V-1082 bottoms.

Jan 23: The first-stage temperature was increased from 760 to 790°F and the catalyst charge was increased from 242 to 270 lb, in order to increase distillate yield.

Jan 24: An interstage separator valve leak caused gas to blow into the second stage, brief loss of ebullation, and brief lowering of the coal feed rate.

The coal feed rate was increased from 450 to 500 lb/hr, in order to build up the low resid solvent inventory.

Jan 26: A system upset resulted from a power outage and an interstage separator valve leak.

Jan 27: Resid content of the recycle solvent was low, because of low resid inventory.

An interstage separator valve problem occurred.

Jan 28: Because of a low resid solvent inventory, the coal feed rate was increased from 500 to 550 lb/hr and the resid content in the recycle solvent was adjusted to 30 wt%.

Jan 29: The resid content of the recycle solvent was increased from 30 to 35 wt%.

A high water injection rate to the second stage caused water to be present in the distillate.

- Jan 29-Feb 2: Balance period A was transitional because resid inventories were low, causing variation in the concentration of resid in the recycle solvent and deviation from target concentrations. In addition, catalyst replacement began during period A.
- Jan 30: The coal feed rate was temporarily lowered because of a high-pressure letdown valve problem.
- Jan 30-Feb 1: The reported interstage separator overheads flow rates were low because the condensate was routed to the wrong tank.
- Feb 1: A valve problem forced a temporary maintenance shutdown. Catalyst addition to the first stage (R-1235) began at 3 MF lb/T MF coal.
- Feb 2: Catalyst addition to the second stage (R-1236) at 3 MF lb/T MF coal was attempted, but failed because of problems with the valves.
- Feb 3-7: Extended outage for repairs of high pressure letdown valves and catalyst addition valves.
- Feb 4-6: During the outage, the temperature of the slurry preparation tank (V-101A) rose to 440°F and the viscosity of material in the slurry feed tank (V-101B) was high. This may have resulted from improper operation of the new vent system (causing oxidation of solvent).
- Feb 7: Run 261 was restarted after the outage.
- Feb 7-8: An outage lasting several hours resulted from problems in preparing coal slurry.
- Feb 8: The target resid content of the recycle solvent was increased from 35 to 40 wt%.
- Feb 11-15: Balance period B
- Feb 12: There were catalyst addition problems due to failure of the valves in the first-stage addition system to open completely.
- Feb 14: Cooler weather lowered the temperature of the Dowtherm heater, lowering the temperature of the second stage.
- Feb 15: Failure of a pump in the T-102 vacuum distillation column caused a temporary shutdown.

Feb 16: There was an outage lasting several hours to repair a vacuum leak in the vacuum flash vessel (V-1082).

Feb 17-20: Leaks in the line from V-1079 to V-1067 caused an outage. The first-stage ebullation pump (P-1222) failed.

Feb 20: Run 261 restarted. Batch deactivation of catalyst in both reactor stages began, so that a higher equilibrium catalyst age could be obtained.

Feb 20-22: As a result of a malfunction, the second-stage flashed overheads feeding to the distillation columns contained a lot of water.

Feb 22-24: The first-stage (R-1235) preheater B-1200 shut down several times for unknown reasons, causing small temperature decreases.

Feb 25: There was a brief loss of the fresh hydrogen compressor (C-1205).

Feb 26: The ebullating pump P-1236 failed, causing the second-stage (R-1236) catalyst bed to reach 828°F, and the plant to be shut down.

Feb 27: There was poor circulation in B-102 (the reboiler for the vacuum distillation column T-102) since Feb 15, due to coke formation. The coke was removed.

Mar 2: The run was restarted with a coal feed rate of 425 MF lb/hr (550 lb/hr at shutdown on Feb 26) and ash recycle taken from V-1082 bottoms. (The run started this way, but was operated from January 21 or 22 to February 26 with ash recycle from V-1067).

Mar 4: The T-105 atmospheric column was down to bypass a leaking condenser.

Mar 5: The water pump to the vent separator line was down for repair.

Mar 7-11: Balance period C

Dates unspecified: Frequent pressure drops developed across seal in ebullating pumps. Problem was alleviated by increasing the flow rate of seal oil for a short period of time each day.

Mar 11: A plug in the impulse line on R-1235 invalidated the R-1235 delta P readings.

The recycle solvent composition was changed from 40 to 50 wt% resid.

Mar 13: Catalyst replacement started in R-1236 at 1.5 lb/T MF coal.

Mar 14: Catalyst replacement started in R-1235 at 1.5 lb/T MF coal.

Mar 14-18: Balance period D

Mar 16: Catalyst was withdrawn from reactor R-1235; problems prevented addition.

Mar 17: Catalyst was successfully added to R-1235 (see Mar 16).

Mar 19-Apr 12: A scheduled shutdown took place to prepare for the second run segment.

Apr 12: The run restarted with Criterion 324 catalyst.

Apr 13-15: Water was present in the ROSE-SR deashing solvent, causing the recycle solvent composition to deviate from target conditions.

Apr 16: Valves in the ROSE-SR feed measurement system were not operating and were repaired. This caused recycle solvent composition to deviate from target conditions.

Apr 16-17: Overconversion of resid was noted.

Apr 17: Several brief power outages occurred.

Apr 18: The coal feed rate was increased from 425 to 500 MF lb/hr because of decreasing solvent inventories. Catalyst replacement at 3.0 lb/T MF coal started in the second stage (R-1236).

Apr 19: Catalyst replacement at 3.0 lb/T MF coal started in the first stage (R-1235).

Apr 18: Pressure drops developed across seal in ebullating pumps daily. Problem was alleviated by increasing the flow rate of seal oil for a short period of time each day.

Apr 19-25: High slurry viscosity noted.

Apr 19-30: Pressures in the reactors were lowered due to high pressure drops in the feed line and first-stage preheater (B-1200). As a result, hydrogen partial pressure was about 100 psi lower in 261E compared to 261A-D in each stage.

Apr 20, 23-26: Balance period E

- After Apr 21: To prevent plugging, the line from V-1082 vacuum flash vessel to V-131B was flushed with heavy gas oil (V-1074) after every transfer of ashy resid through the line.
- Apr 27: The coal feed rate was decreased from 500 to 425 MF lb/hr and batch deactivation of the catalyst was begun.
- Apr 29: The coal feed rate was decreased from 425 to 360 MF lb/hr to lower the slurry viscosity.
- Apr 30: The coal concentration was decreased from 33% to 30% to lower the slurry viscosity.
- The lower coal feed rate and consequently reduced exotherm caused the temperature at the second-stage preheater outlet to be excessive. The second-stage temperature was reduced to 800°F from the original target of 825°F.
- At the lower feed rates and coal concentration, the pressure drop in the lines were lower, allowing reactor pressures to be increased back to normal levels (see Apr 19-30).
- May 1: While the second-stage hydrogen compressor was down (one hour), low purity gas from the first stage was used.
- A leak around the second-stage recycle gas compressor caused an upset.
- May 2: The computer was off line, causing a loss of data for 1.2 hours.
- May 5: During a heavy rain, failure of an electronic controller on the interstage separator caused a pressure upset.
- May 7-10: The first-stage (R-1235) catalyst tube plugged, preventing withdrawal of the catalyst.
- May 7-9: The line from the deashed resid tank to V-131B plugged, because of inadequate heating. It caused problems with preparation of the recycle solvent.
- May 8: Catalyst replacement at 2.25 lb/T MF coal began in the second stage (R-1236). Operating constraints made batch aging to 1.5 lb/T equivalent age (as planned) difficult. The plan was revised to batch age and test at 2.25 lb/T equilibrium age.
- May 10: Catalyst replacement at 2.25 lb/T MF coal began in the first stage (R-1235). Double the normal quantity was used, to make up for the failed replacement on May 7-10.

May 11: Catalyst replacement in the second stage (R-1236) was double the normal quantity, to adjust for the disrupted replacement schedule.

May 12-14: An extended outage was needed to repair a leak in an outlet line from the atmospheric flash vessel V-1250.

May 14: Restart of the run was delayed, but succeeded after a plug was cleared from the R-1235 feed line.

May 15: A brief power outage occurred.

May 16: The second-stage hydrogen compressor was down, upsetting process conditions. Low purity gas from the first stage was used during the compressor outage.

May 17-21: Balance period F was unstable because material balance closure errors were quite high.

May 21: The interstage overhead water separator plugged, causing uncertainty in the V-1258 overhead flow rates.

May 22: Failure of the second-stage (R-1236) withdrawal tube flush pump caused a change in the overall reactor temperature profile.

May 22 or 23: Material balances were found to be off by about 3 wt% overall (see note for May 21). Suspect V-107z and V-1258 overheads flow meters were tested and found to be accurate.

May 23: The resid injection system test was begun.

Difficulty was encountered in pumping the slurry consisting of 53 wt% coal and 47% heavy gas oil (V-1074). In order to get the centrifugal pumps to pump the slurry, backflushing from V-101B to V-101A was performed. The coal concentration in the slurry was decreased.

May 24: A batch of slurry made up as 57 wt% coal and 43 wt% V-1074 recycle distillate (to bring the net feed slurry composition to 53 wt% coal) could not be pumped. Dilution of the batch of slurry to 50 wt% coal was required.

May 24-27: Balance period G was transitional because the distillate content of slurry had to be increased to facilitate smooth operation and because the eventual recycle solvent composition deviated from target.

May 28: Addition of deashed resid to the recycle solvent began (addition through the resid injection system was discontinued). The recycle solvent used for slurry preparation consisted of 29 wt% deashed resid and 71 wt%

V-1074 distillate. The coal concentration in the slurry was 47 wt%.

May 29: Coal concentration in the slurry was set to 45 wt%. Operation was good at these conditions.

May 31: End of run.

SAMPLE DESCRIPTIONS

CONSOL received 21 process oil samples from Run 261. The process oils consisted of a recycle oil (V-131B) sample, an interstage oil (R-1235) sample, and a product oil (V-1067) sample from each of the seven material balance periods A through G. V-1067 is the second-stage flashed bottoms product. Although the interstage samples were labelled R-1235, R-1235 HP or R-1235 OTL, they will be referred to as R-1235 samples throughout this report. The HP (high pressure) or OTL (outlet) suffix designates that these samples were taken after the high-pressure flash (interstage separator in operation). The sample from period G (resid injection) designated V-131B actually was composited to represent the entire recycle feed (including injected resid, but without the fresh coal), and not just the slurry oil.

In previous runs, CONSOL received daily composite or individual daily samples from Wilsonville runs. At CONSOL's request, Wilsonville personnel composited samples over the complete material balance period for each of the Run 261 samples. This was done to reduce uncertainty in interpretation of analytical results from one period to another.

ANALYSES

Proton distributions were obtained by ^1H -NMR for each of the V-131B, interstage and V-1067 whole samples (Tables 8-10). All the whole samples were tested in the microautoclave at the modified equilibrium conditions (Table 18). Prior experience has shown that the microautoclave results may show high variability when the samples have high solids concentrations, as was the case in Run 261. The whole samples were distilled (Tables 2-4) to 320°C pot/270°C column/5 torr (850°F/atm). Each 850°F+

resid was analyzed by solubility fractionation (Tables 5-7), $^1\text{H-NMR}$ (Tables 14-16) and FTIR for phenolic -OH content (Table 17). Each 850°F distillate was analyzed by $^1\text{H-NMR}$ (Tables 11-13) and FTIR (Table 17). Microautoclave tests were made at the modified equilibrium conditions with each 850°F distillate (Table 18).

Details of the sample work-up and analytical procedures have been presented elsewhere.^{9,10} All samples for proton distribution by NMR were dissolved in 99.96% deuterated pyridine (whole or resid samples) or in CDCl_3 (distillate samples) and integrated electronically. Response factors used for flame ionization detection of solubility fractions were those previously used for Run 257 samples produced from Burning Star 2 coal. A different set of response factors is used for each feed coal used to produce an oil sample.

PROCESS OIL PROPERTIES

Process oil properties are presented in Tables 2 through 18 and in Figures 3 through 14. The discussion is most easily followed by referring to the figures. Some general observations will be made here about process oil properties during Run 261. Referring to the run conditions presented in Table 1, differences in conditions from one material balance period to another will be described as a reference point for comparison of oil properties. From period A (transitional) to period B, there was an increase in the resid concentration in the process solvent from 32.7 to 38.3 wt%. During period A, catalyst replacement was begun in both stages, whereas catalyst replacement was used throughout period B. Periods A and B were obtained with a very high coal feed rate of about 550 MF lb/hr. From period B to period C, the coal feed rate was decreased from about 550 to 420 MF lb/hr, and batch catalyst aging was used (no replacement). From period C to period D, there was an increase in the resid concentration in the process solvent from 38.3 to 48.4 wt%, and catalyst replacement was used at a lower rate than before. From period D to E, many conditions changed. The EXP-AO-60 catalyst was removed and replaced by Criterion 324 catalyst. The catalyst replacement rate was increased from 1.5 to 3.0 lb/T MF coal, and was accompanied by

a decrease in catalyst age. The coal feed rate was increased from 423 to 494 MF lb/hr. The reactor temperatures were increased from 791/809 to 809/824°F. From period E to period F (unstable), there were decreases in coal feed rate (from 494 to 359 MF lb/hr), coal concentration in the slurry (from 33 to 30 wt%), catalyst replacement rate (from 3.0 to 2.25 lb/T MF coal), and second-stage reactor temperature (from 824 to 800°F). An increase in catalyst age accompanied the lower catalyst replacement rate. The lower second-stage reactor temperature is a consequence of lowering the coal feed rate, which lowered the heat input of the reactor and the generation of heat from the exothermic reaction. For this reason, period F and period G were not at low/high temperature conditions as planned. Period G (transitional) was made at nominally the same conditions as period F, except that resid injection was used during period G. There was a slightly lower coal concentration in the slurry, and a slightly lower resid concentration in the recycle in period G relative to period F.

The major change in operating conditions occurred from period D to E, when catalyst type, replacement rate, catalyst age, coal feed rate, and reactor temperatures changed. Results of operation before and after this change will be described in more detail later.

Component distributions of the whole process oils are shown in Figures 2-4. The V-131B samples show a jump in 850°F⁺ resid concentration from period C to D, as a result of the increase in target resid concentration in the pasting solvent. The 850°F⁺ resid concentrations determined by CONSOL for the V-131B samples were 13-23 wt% higher than Wilsonville's reported resid concentrations. Wilsonville uses a distillation endpoint of about 1050°F, whereas CONSOL uses an endpoint of 850°F. Thus, CONSOL reports 850x1050°F material as resid, and Wilsonville reports it as distillate.¹¹ Resid concentration in the R-1235 and V-1067 samples appears to increase from C to D to E, as a result of the recycle resid concentration increase and the operation at higher temperature, different catalyst, etc.

The sum of IOM and ash values obtained by CONSOL for the V-131B samples from periods A, B, C, and E (Table 2, Figure 3) were slightly low (by 1-1.5 wt%) relative to Wilsonville's measured CI concentrations. Our analyses were obtained as THF insolubles from a true composite over each material balance period, whereas Wilsonville's values were combined from daily operation analyses or flow rates and were based on cresol insolubles.

Many oil properties did not change substantially from periods A through D, and from periods E through F. However, from period B to C there was a noticeable increase in resid preasphaltene concentration (Figures 6-8), an increase in resid aromaticity (Figures 9-11), and an increase in resid phenolic -OH concentration (Figure 12). The condition changes from B to C were a decreased coal feed rate and an increased catalyst age through batch aging. These conditions are expected to have opposing effects on most oil properties. Since the resid properties became worse, it appears that the higher catalyst age dominated the changes in resid properties, with no substantial change in distillate properties. There was a decrease in the preasphaltene concentration (Figures 6 and 7) and in the phenolic -OH concentration (Figure 12) of the THF-soluble V-131B and V-1067 resids from period A to B. This may have resulted from the transitional nature of period A, the increase in recycle resid from period A to period B, or the change from batch aging to catalyst replacement, which began in the latter part of period A. The addition of fresh catalyst might increase the defunctionalization activity, even though catalyst ages were nominally equivalent in A and B.

Resid injection had a minor impact on some oil properties, although distillate yield was much higher in period G (resid injection used) than in period F (resid injection not used). Resid concentration, resid preasphaltene concentration, resid and distillate aromaticity, and resid and distillate phenolic -OH concentration decreased by small amounts in period G in many of the process oils (Figures 3-5, 8-12). Since period F was unstable and period G was transitional, and they were nominally at equivalent operating conditions, no attempt will be made to attribute the observed property differences to variation in any particular conditions.

As previously mentioned, the greatest change in run conditions occurred at the time the run was restarted after loading the reactors with Criterion 324 catalyst. Several detrimental effects noted by Wilsonville during the period of operation with Criterion catalyst were mentioned in the run overview section of this report. Because the condition changes were numerous, changes in oil properties can not be attributed solely to the use of Criterion 324 catalyst. Higher temperatures (both stages in period E, first-stage in periods F and G), a higher coal feed rate (period E), and a lower hydrogen partial pressure (period E) are expected to be detrimental to oil properties. The aged catalyst which constituted most of the reactor charge used came from Run 259, and may have been excessively deactivated before it was used in Run 261. On the positive side, the average catalyst age was lower in periods E through G than in periods C and D, the coal feed rate was lowest in periods F and G, the second-stage temperature was lower in periods F and G than in A through D, and the coal concentration was lower in periods F and G than in the rest of the run. With generally higher reactor temperatures and lower coal feed rates, it may be useful to consider periods E-G as operation at higher thermal severity than operation during periods A-D. Consistent with Wilsonville observations, CONSOL's analytical results show that many properties of oils from periods A through D differed significantly from those from periods E through G. The greatest change evident in oil properties occurred from period D to period E. The process oils increased significantly in resid and distillate aromaticity, decreased in paraffinicity, and decreased in hydroaromaticity from D to E (Figures 9-11). Significant increases in the phenolic -OH concentrations of all distillates and the V-131B resid also took place (Figure 12). Although the whole-oil donor solvent quality was roughly equivalent to that of the distillate in periods A through D, in periods E through G the whole oils had much poorer solvent quality than their respective distillates (Figure 13). The donor quality of the distillates actually increased by several wt% MAF during periods E-G, whereas the whole-oil donor quality fell by about 15 wt% MAF. Since the resid quality showed such a significant decrease, as indicated by the changes in donor solvent quality and aromaticity, it is surprising that the resid solubility fractions (oils, asphaltenes, preasphaltenes) showed no change whatsoever

(Figures 6-8). Furthermore, there was relatively little change in phenolic -OH concentration in the resids, but substantial changes in the distillates (Figure 12). The solvent quality and aromaticity changes correspond closely to observations at Wilsonville of lower pasting solvent quality and lower hydrogen content in the pasting and interstage solvents during operation with Criterion catalyst. They also noted higher N on the catalyst, lower resid+UC conversion, and no "all-distillate" yields during this segment of the run. In some respects, periods E-G were similar to Run 259 with Ireland coal, in that high aromaticities were observed with moderately low space velocities.⁴

During one period of Run 259, some evidence suggested that hydrogenation may have been equilibrium controlled. Such a situation also may apply in period E of Run 261, where high temperature and low space velocity was used. The confounding effects of other variables prevent a straightforward interpretation of the results in this manner. Wilsonville reported an unusually low activation energy for resid + UC conversion in the second stage for periods E through G of Run 261, which supports the notion that operation may have been in the equilibrium (vs kinetic) regime. Calculated rate constants would have less meaning at these conditions, since composition is not kinetically controlled.

850°F⁺ RESID CONVERSION AND KINETICS

CONSOL analyses of the process oils were used to calculate conversions (forced ash balance method) of the 850°F⁺ material and its various components in each reactor stage (Table 19, Figures 14-18). The 850°F⁺ conversions then were used to calculate conversion rate constants and conversion activities (Table 20, Figure 19). A deactivation rate constant was obtained from these data by a method described later. The conversion and kinetic calculations were made as described elsewhere.⁷ Briefly, the following equations are used in the calculations:

$$C = \text{Conversion} = \left(\frac{850^{\circ}\text{F}^{+} \text{ In/Ash In} - 850^{\circ}\text{F}^{+} \text{ Out/Ash Out}}{850^{\circ}\text{F}^{+} \text{ In/Ash In}} \right) \times 100\%$$

$$K = \text{Rate Constant} = \text{WHSV} \left(\frac{C}{100 - C} \right)$$

$$A = \text{Conversion Activity} = K e^{E_{\text{act}}/RT},$$

where E_{act} is assumed to be 23,500 cal/mol, as has been used in the past at CONSOL.

Conversions of 850°F⁺ resid and its components calculated for each reactor stage and the total system are given in Table 19. Figure 14 shows the first-stage and total THF-soluble 850°F⁺ and coal + IOM conversions for Run 261. As is typically observed, the second stage provided very little additional conversion of coal + IOM, but provided a substantial part of the THF-soluble 850°F⁺ conversion. The soluble resid conversion in the first stage was negative (there was a net yield), but was higher for the total system. The conversion of soluble resid was relatively low in periods A, E, and G for the first stage and total system. The total system conversion of 850°F⁺ (including coal and IOM) was lower in periods E-G relative to periods A-D (Table 19). Lower conversion in periods E-G (total system) is also manifested in the THF-soluble resid results (Figure 14). The conversion of 850°F⁺ (including coal and IOM) (Table 19) and the soluble portion (Figure 14), both in the first stage, show the same result, except that period A is much lower. Wilsonville reported lower resid + UC conversions during operation with Criterion 324 catalyst. Explanations for such differences were discussed in the previous section on oil properties.

More detail is given in Figures 15-18 in the conversions of the 850°F⁺ resid components and their averages and standard deviations. The reader should be aware that the conversions calculated for the resid solubility components (Table 19, Figures 16-18) are subject to error accumulated from determination of total THF-solubles, IOM, ash, and the solubility fractions. Thus the results for the balance periods may show high variability. The average and standard deviation may provide a more reliable indication of the results. In general, the soluble resid and its asphaltene and preasphaltene components (Figures 15, 17, 18) showed

first-stage and total net yields (negative conversions), but positive second-stage conversions. In contrast, the first-stage, second-stage, and total conversions of the oil component of the resid (Figure 16) generally were near zero. Net yields in the first stage appear to result from the solubilization of coal to resid, but insufficient conversion of resid to other products (in the first stage).

Excluding results from period A, the conversions of soluble resid (Figure 15), and the oil and asphaltene components (Figures 16 and 17) show similar trends from period to period over the course of the run: period G was relatively low in first-stage, second-stage, and total system conversions; period E was relatively low in first-stage and total system conversions; period E was relatively high in second-stage conversions; period D was relatively high in first-stage, second-stage, and total system conversions; and period A was relatively low in first-stage and total system conversions. The first-stage preasphaltene conversion was an exception in that period A was relatively high and period B was relatively low, for reasons not clear. Since the conversion of the oil component was generally about zero, we will ignore it and explore further the role of the asphaltene and preasphaltene components. As a rough approximation, we can consider the concentration of the asphaltene and preasphaltene fractions of these resids to be equal (Tables 5-7). Figures 17 and 18 show that the preasphaltene conversions (each stage and total) are greater in magnitude than the asphaltene conversions. The large yields (negative conversions) of preasphaltenes in the first stage suggest that preasphaltenes are the primary coal solubilization product. It is also evident that consistently high conversion of preasphaltenes took place in the second stage (Figure 18). The total system conversions (net yields) of preasphaltenes were greater in magnitude than those of the asphaltenes. The soluble resid and most of its components (Figures 15-18) showed a net yield (negative conversion) on average and in most balance periods. This is consistent with Wilsonville having net resid yields in all the balance periods (Table 1). The total system conversion of soluble resid and most of its components (Figures 15-18) reached a maximum or relative maximum with period D. This seems to be consistent

with Wilsonville's results, which gave the lowest resid yield in period D (Table 1).

In Table 20, the 850°F⁺ resid + UC conversions obtained by CONSOL are compared with those obtained by Wilsonville. The associated kinetic rate constants and conversion activities obtained by CONSOL also are given. The conversions obtained by CONSOL are different from those obtained by Wilsonville because of a difference in laboratory distillation conditions. CONSOL uses an 850°F atmospheric equivalent distillation endpoint, whereas Wilsonville uses a 1050°F atmospheric equivalent endpoint. Therefore, CONSOL calculates conversion of 850°F⁺ material, but Wilsonville calculates conversion of 1050°F⁺ material. The effect of this difference on measured conversions has been discussed elsewhere.⁷

The average ratios of CONSOL conversions to Wilsonville conversions are compared below.

RATIO CONSOL/WILSONVILLE CONVERSIONS OF RESID + UC

Period	First Stage	Second Stage	Total
261B-D	1.17 $\pm$ 0.10	0.79 $\pm$ 0.20	1.00 $\pm$ 0.04
261E-G	0.98 $\pm$ 0.14	0.70 $\pm$ 0.19	0.86 $\pm$ 0.14
261 (all)	1.01 $\pm$ 0.22	0.82 $\pm$ 0.27	0.93 $\pm$ 0.11
257 (all) ⁷	0.91 $\pm$ 0.14	0.82 $\pm$ 0.22	0.90 $\pm$ 0.07
257E ⁷	0.89	0.74	0.86
257J ⁷	0.99	0.79	0.94
Average Runs 250-259 ^{4,7}	0.98 $\pm$ 0.10	0.85 $\pm$ 0.16	0.94 $\pm$ 0.06

The ratios for all of Run 261 for the first and second stage and total system were equivalent to the global averages (Runs 250-259) and the ratios for period 257J. However, the averages for all of Run 261 were higher than the 257E ratio and Run 257 (all) average for the first stage, similar to the Run 257 (all) ratio (second-stage and total) and higher than the 257E averages (second-stage and total). By run segment (catalyst type and other variables), the average ratios for Run 261 periods B-D (A was omitted) were high for the first stage and total, and moderate for the second stage. The average ratios for Run 261 periods

E-G were typical of the Run 250-259 average (high for the 257 average) in the first stage, and low in the second stage and total system.

A ratio higher than one indicates that the percentage conversion of 850 x 1050°F material is relatively greater than the percentage conversion of 1050°F⁺ material. The ratio for the first stage in 261B-D is quite high, indicating high 850 x 1050°F conversion or, alternatively, low conversion of 1050°F⁺ (including unconverted coal). The first explanation seems most likely, in light of the high coal conversion and use of fresh catalyst aged (for the first time) in low/high operation. It is possible that changes in the distillation system and the use of a different ashy recycle streams (Run 261 periods C-G), relative to Run 257 has some effect on the 850 x 1050°F conversion. It is interesting that Wilsonville reported negative yields of 850°F-endpoint distillate for periods A through D of Run 261 (Table 1, no yields were reported for that fraction for later periods). The average for the first stage in 261E-G was near unity, indicating the same conversion of 850 x 1050°F as of 1050°F⁺. The second stage typically has a lower ratio than unity, as the average Run 261 ratios also show. Perhaps this is because most of the conversion of soluble resid takes place here and there is more 1050°F⁺ material to convert.

The kinetic rate constants and conversion activities for each reactor stage are given in Table 20 and the activities are plotted in Figure 19. The first-stage conversion activity was highest in period B and consistently decreased from then on. Period B has the highest activity CONSOL has calculated for a run period since we began calculating them with Run 250.⁷ If the high first-stage activity is not an artifact of the high space velocity used in period B, perhaps it is related to the onset of catalyst replacement late in period A. Period A was unusual in that the second-stage conversion was slightly higher than that of the first stage. The first-stage activity was low, and the second-stage activity was high for period A. In general, the first-stage conversion activities for periods B-D of Run 261 were relatively high, whereas the second-stage conversion activities were relatively low. First-stage and

second-stage conversion activities were low during operation in periods E-G.

A catalyst activity plot is shown in Figure 20. Periods of operation with the same catalyst and reactor stage are plotted with the same symbol. For clarity, they are grouped together into four groups (two catalysts, two reactor stages). Several observations can be made from this plot: 1) the 850°F⁺ resid + UC activity of each catalyst type was higher when it was used in the first stage; 2) the conversion activity during operation with Criterion 324 catalyst was consistently lower than during operation with EXP-AO-60 catalyst; and 3) there was little or no detectible loss in conversion activity with increasing catalyst age. The first point undoubtedly results from the primary role the first stage plays in converting coal to solubles. The conversion of coal + IOM dominates the conversion of resid. As was noted earlier, the first-stage conversion of THF-soluble resid was actually negative. The second point made above could result from any number of factors which have already been discussed: catalyst type, catalyst history, reactor temperatures, etc. The third point made above may result from a number of factors: insufficient data, high variability especially with use of transitional or unstable balance periods, use of equilibrium vs batch deactivated catalyst data, catalyst age too low, inappropriate assumed activation energy or kinetic model. For the sake of completeness, deactivation rate constants were calculated for each of the groups of points shown in Figure 20. Transitional and unstable periods were included, so that sufficient data were available to perform the calculations for each set. The deactivation rate constant was evaluated by considering the conversion activity, A, to have an exponential dependence on catalyst age, t, as $A = A'e^{\alpha t}$, where A' is the initial conversion activity. As written, catalyst deactivation will result in negative values of α , the deactivation rate constant. The value of α was determined by regression of $\ln A$ on t. Wilsonville uses a different method, in which E_{act} is variable. Results are given below for each combination of catalyst type and reactor stage.

First Stage, EXP-A0-60 Catalyst (Periods A-D):

$$\begin{aligned}\alpha &= 0.2 \times 10^{-4}, \sigma(\alpha) = 3.0 \times 10^{-4}, \\ A' &= 4.1 \times 10^7, \sigma(A') = 1.5 \times 10^7, \\ R^2 &= 0.00\end{aligned}$$

Second Stage, EXP-A0-60 Catalyst (Periods A-D):

$$\begin{aligned}\alpha &= -2.6 \times 10^{-4}, \sigma(\alpha) = 3.4 \times 10^{-4}, \\ A' &= 3.1 \times 10^7, \sigma(A') = 1.4 \times 10^7, \\ R^2 &= 0.24\end{aligned}$$

First Stage, Criterion 324 (Periods E-G):

$$\begin{aligned}\alpha &= -3.5 \times 10^{-4}, \sigma(\alpha) = 2.6 \times 10^{-4}, \\ A' &= 2.5 \times 10^7, \sigma(A') = 1.1 \times 10^7, \\ R^2 &= 0.65\end{aligned}$$

Second Stage, Criterion 324 (Periods E-G):

$$\begin{aligned}\alpha &= -13.3 \times 10^{-4}, \sigma(\alpha) = 14.4 \times 10^{-4}, \\ A' &= 7.1 \times 10^7, \sigma(A') = 1.5 \times 10^7, \\ R^2 &= 0.46\end{aligned}$$

In each case, the deactivation rate constant is not significantly different from zero, since the standard deviation is about equal to each rate constant. Differences in calculated initial activity, A' are not statistically significant, except that the initial activities of Criterion 324 catalyst in the two reactor stages appear to be different (borderline statistical significance). This may result, in part, from differences in space velocities, etc. not properly corrected for by the kinetic models involved.

COMPARISON OF OILS FROM RUN 261 WITH OILS FROM RUN 257

Since Run 261 was intended, in part, to go beyond results achieved in Run 257, it is useful to compare results from these two runs. Three periods from Run 261 (periods B, D, and E) will be compared with two periods from Run 257 (periods E and J) in process oil properties, 850°F+ resid+IOM conversions, and kinetic constants. Given in Table 21 are the major operating conditions for these five periods. The two runs used the same feed coal. The coal fed in Run 257 contained slightly less ash than the coal fed in Run 261, though the ash content varied only from 11.2 to 12.1 MF wt%. Period 257J is the only one listed in which 50% reactor volumes were used; all the other periods used 100%. The interstage separator was not used in Run 257, but it was in Run 261. All the periods were

equivalent in coal concentration in the slurry and in CI concentration in the recycle. Period 261B used a low resid concentration in the recycle. Period 261E was the only one made using the unimodal catalyst. In space velocity (WHSV), 261B was similar to but lower than 257J, 261D was similar to but higher than 257E, and period 261E was the lowest. In catalyst age, 257E and J were similar in both reactors, 257E and J were similar to all in the first stage except 261D (which was higher), 257E and J were higher in the second stage than all the others except 261D (which was about the same), 261B and E were the lowest in the second stage.

Periods 257J and 261B were similar in WHSV, but differed in reactor volume, interstage separator use, temperatures and temperature configuration, resid concentration in the recycle, and second-stage catalyst age. Periods 257E and 261D were similar in WHSV, but differed in interstage separator use, second-stage temperature and temperature configuration, and first-stage catalyst age. Period 261E was made at a slightly lower space velocity than period 257E, but there were differences in catalyst type, reactor temperatures and temperature configuration, and second-stage catalyst age.

Some relevant process performance data are given in Table 22 for these five periods. The five periods had similar distillate yields (261 was lower), coal conversions, and total resid + UC conversions. Resid yields were slightly higher and ash concentrate yields were slightly lower in Run 261. The distribution of resid + UC conversion between reactor stages in the Run 261 periods differed from each other and from the Run 257 periods.

Process oil properties, 850°F⁺ resid + IOM conversions, and kinetic constants for these five periods are given in Table 23. The solvent quality indices for all the periods are similar (but slightly low for 261D). Distillate and resid aromaticity was higher in the Run 261 oils. The 261E distillates were lower in paraffinic hydrogen, relative to the Run 257 and 261B and D distillates. The phenolic -OH concentration of distillates ranged from low (261B) to high (261E), relative to the 257E

and J distillates. The phenolic -OH concentration of resids from 261D and E were slightly high, relative to the 257E and J resids. The concentration of the hexane-soluble (oil) component of the resids from Run 261 were lower than in the Run 257 resids, except that the 261B recycle resids were intermediate between the Run 257 values. The resids from Run 261 were higher in asphaltene concentration than the Run 257 resids, except that the 261B interstage resid intermediate between the Run 257 values. Relative to the Run 257 resids, the recycle resids from 261 were similar, but the interstage resids were higher in preasphaltene concentration.

Conversions of 850°F⁺ resid (including coal and IOM), and the corresponding rate constants and activities for periods 261B and D were generally equivalent to or greater than those in period 257E, and most of those in period 257J. However, some values for period 257J were greater than those from periods 261B and D.

Generally, the values obtained for the conversions, rate constants, and activities for period 261E were smaller than those obtained for periods 257E and J, although some values for period 261E were equivalent to or greater than the period 257E and J values.

In summary, many 261B oil properties were similar to those from 257E and J. Overall, the 261B oil properties are intermediate between those of the two Run 257 periods. The concentration of phenolic -OH in 261B distillates was lower than in the corresponding 257E and J distillates, however. The properties of oils from periods 261D and E were generally worse than the others, though some 261D oil properties were similar to those from 257J. The phenolic -OH concentration of 261D distillates were in the range of those from the Run 257 periods.

ANALYSES OF WILSONVILLE RUNS 260D AND 259G NET PRODUCTS AND FRACTIONS

The four distillation fractions of the net product oil (crude oil) of Wilsonville Run 260D were returned to CONSOL by Conoco Petroleum Products Research Division in September, 1991 after Conoco completed the petroleum inspection tests on them.¹² CONSOL determined the phenolic -OH concentrations of the fractions by FTIR spectroscopy and analyzed them by gas chromatography/mass spectrometry (GC/MS) and ¹H-NMR for further characterization. The entire sample of the whole crude oil was consumed by Conoco and so it was unavailable for further analysis by CONSOL. The Wilsonville Run 259G crude net product oil and its three distillations were also analyzed by ¹H-NMR. The results of these analyses are reported here and, in some cases, compared to additional results obtained earlier^{13,14} with the Run 259G crude oil.

PROCEDURE

Our customary procedures were used for the determination of phenolic -OH concentrations⁹ and ¹H-NMR proton distributions.¹⁰ GC/MS analyses were performed with an HP 5970 system equipped with a 30 m x 0.25 mm DB-5 column (0.25 μ m film thickness). For the crude, jet fuel and diesel fuel fractions, the GC conditions were: injection port at 300°C; column 5 min @ 35°C then to 100°C at 35°C/min, then to 320°C @ 4°C/min; 20 psig of He carrier gas; scan from 45 to 300 amu. For the naphtha fraction, the GC conditions were 5 min @ 10°C then to 100°C @ 2°C/min, then to 320°C @ 4°C/min. Splitless injection was used. The naphtha was injected neat, the other fractions were injected as 1% solutions in tetrahydrofuran. The mass spectra were searched against the Wiley/NBS mass spectral library. Identifications are based on the search results supplemented in some cases by retention times.

¹H-NMR RESULTS

Proton distributions were obtained by ¹H-NMR for the four fractions of the crude oil from Wilsonville Run 260D and for the three fractions and the crude oil from Wilsonville Run 259G. These data are shown in

Table 24. Also shown in Table 24 are the yield of each fraction and its hydrogen content, as determined by Conoco.¹² The 260D crude oil was not available for analysis; its proton distribution was calculated from the data of its fractions. The Run 260D sample has a higher boiling-point distribution (yield of 510°F+ is 57.4 vs 41.9% for Run 259G) and slightly lower hydrogen content (11.2 vs 11.6% for Run 259G); it yielded less jet fuel fraction and more diesel fuel plus residuum. As might be expected from this, the Run 260D crude oil is more aromatic. The proton distributions and hydrogen contents of the two naphtha fractions are fairly similar to each other. The sum of alkyl β plus cyclic β concentrations are almost identical in these two fractions even though there are differences in the individual values. Apparently, the difference arises because the signal for cyclohexane, a major component of both fractions, appears on the border of these two classes in the spectra. The proton distributions and hydrogen contents of the two diesel fuel fractions are also similar to each other, despite the fact that the Run 260D fraction was cut at 650°F and the Run 259G fraction was not. In general, the fractions contain less hydrogen and become more aromatic with increasing boiling point. However, the Run 260D jet fuel fraction is a notable exception to this trend; apparently, its high concentration of Dowtherm A components give it a lower than expected hydrogen content (10.6 vs 11.5% for Run 259G) and a higher than expected aromaticity (17.0 vs 8.8% for Run 259G).

GC/MS RESULTS

The total ion chromatograms are shown in Figures 21 through 24. Identifications of prominent peaks are provided in a key that immediately follows Figure 24. The predominantly cyclic nature of these materials is apparent from the chromatograms. A comparison of the chromatograms of the Wilsonville Run 260D products (Figures 21 through 24) with those of the Wilsonville Run 259G products¹⁴ shows that the subbituminous coal crude (Run 260D) has a greater concentration of normal paraffins, olefins and phenols and is contaminated with the Dowtherm A components (biphenyl and diphenyl ether).

PHENOLIC -OH CONCENTRATIONS

The phenolic -OH concentrations and the phenolic and total oxygen contents of the crudes and their fractions are shown in Table 25. The phenolic -OH concentration of the Run 260D crude oil was calculated from the data of its fractions because the crude was unavailable for analysis. The phenolic oxygen content is calculated from the determined phenolic -OH concentration. The Run 260D crude oil has a phenolic oxygen concentration almost three times greater than the Run 259G crude. The Run 260D naphtha and jet fuel fractions have phenolic oxygen contents that are 2.2 and 3.7 times greater than that of the respective Run 259G samples. The Run 260D diesel fuel fraction has a phenolic oxygen content that is four times greater than the Run 259G fraction even though it was cut at 650°F and the Run 259G diesel fuel fraction was not. The phenolic oxygen is concentrated in the jet fuel fraction in both cases, as has been observed by other workers¹⁵ with different coal-derived syncrudes. The total oxygen contents shown in Table 25 are by-difference numbers from the Conoco reports.^{12,13} The total oxygen (by difference) value reported for the Run 260D crude oil appears to be spuriously low; we suspect that Conoco's determined carbon content for this crude is about 0.5% too high on the basis of comparison with the Run 259G crude. With only that exception, the Run 260D samples show total oxygen contents that are 1.5 to 2.4 times higher than the respective Run 259G fractions. The very high total oxygen content of the Run 260D jet fuel fraction appears to result from the presence of diphenyl ether (from the Dowtherm A contamination), in addition to its high phenolic oxygen content.

CAUSTIC WASHING OF WILSONVILLE RUN 260D NET PRODUCT FRACTIONS

SUMMARY

Caustic washing was used to extract the phenolic compounds from the distillation fractions of the net product of Wilsonville Run 260D. The method employed was highly efficient and highly selective for the naphtha and jet fuel fractions. In those cases, the extracts were composed almost entirely of phenols and the raffinates were almost devoid of phenols. The specific phenolic compound types present in the extracts were identified. Caustic washing was much less efficient and less selective for removal of phenols from the higher-boiling fractions. There was little or no noticeable change in the color or appearance of the oils after caustic washing.

INTRODUCTION

Coal-derived synthetic crude oils frequently contain high concentrations of oxygen-containing compounds, particularly phenols, relative to conventional petroleum crude oils. Though these oxygenated species are found at elevated concentrations in all of the distillation fractions (e.g., naphtha, kerosene, etc.), they are most frequently concentrated in the kerosene or jet fuel fraction (b.pt. approx. 380 X 510°F). This is particularly true of the phenolic compounds.¹⁵ Phenolic compounds must be reduced to low concentrations to produce finished transportation fuels. In a typical modern petroleum refining scheme, this would be accomplished by hydrotreating. However, because coal liquids have high concentrations of phenols, it may be advantageous to reduce their concentration by some route other than hydrotreating, for example, by caustic extraction. This route for removal of phenols could have several advantages over the hydrotreating route: it would reduce overall hydrogen consumption, it could produce a valuable by-product (cresylic acid) and it would simultaneously strip from the oil mercaptans and hydrogen sulfide in addition to phenols. Indeed, caustic washing was once a popular unit operation in petroleum refineries because of its ability to sweeten light distillates.¹⁶

As a follow-up to the petroleum inspection tests performed under the Participants Program portion of this contract, Burns & Roe Services Corp. personnel asked CONSOL to examine the effectiveness of caustic washing for removal of phenols from Wilsonville Run 260D net product fractions. Depending on the results of these tests, the caustic-washed fractions were to be submitted for additional petroleum inspection tests. (This later was decided against, because of the contamination of the Run 260D product with Dowtherm A).¹⁷

CONSOL's work was conducted on the Wilsonville Run 260D net product fractions that were returned after completion of the petroleum inspection tests.¹² These fractions were the naphtha (IBP X 380°F), the jet fuel or kerosene (380 X 510°F), the diesel fuel or gas oil (510 X 650°F) and the residue (650°F+). The whole crude oil was consumed in the inspection tests and was unavailable for further testing here.

PROCEDURES

All four fractions were caustic washed to create a raffinate and a phenolic extract. The raffinates were analyzed by ¹H-NMR for proton distributions and by FTIR to determine phenolic -OH concentrations. The phenolic extracts were analyzed by GC/MS to determine their molecular compositions.

For the naphtha and jet fuel crude fractions, a straightforward extraction scheme was devised, based on work reported in the literature.¹⁸ For the caustic wash step, a 20-gram aliquot of each crude fraction was extracted in a separatory funnel with two washings with 20 g each of 20 wt% NaOH, followed by three washings with 20 g each of distilled water. For recovery of the phenolic extract, the collected aqueous phases were combined and acidified to a pH of 5-5.5 with concentrated HCl. The acidified aqueous phase was then extracted several times with 20 g each of methylene chloride. The combined methylene chloride phases were rotary evaporated to obtain the phenolic extract. Five 20-gram methylene chloride extractions were used to obtain the naphtha phenolic extract,

and six 20-gram methylene chloride extractions were used to obtain the jet fuel phenolic extract.

For the gas oil and residuum fractions, the straightforward extraction scheme would not work without modification. Many problems were encountered in caustic washing these heavier fractions. These included droplets of viscous crude fractions clinging to the funnel wall, poor separation of layers, material which was insoluble or immiscible in either phase, and white crystals of solid NaOH in recovered phenolic extracts. Two different trials were made with the residuum fraction and one with the gas oil fraction. Several ad hoc modifications were tried to improve the separation and recovery when problems were encountered. These included such things as: heating the caustic/organic mixed phases for 20-60 minutes at 40°C to facilitate layer separation; diluting the crude fraction with methylene chloride to reduce viscosity and facilitate layer separation; addition of ethyl acetate to dissolve insolubles formed; and use of ethyl acetate to recover the phenolic extract. A long list of the modifications tried would be required to describe them in detail. Such detail is not reported here, for the sake of brevity and because the purpose of this study does not require it. To varying degrees, these modifications ameliorated problems, but did not provide satisfactory and efficient extraction and recovery, as the results show.

RESULTS

The results of the caustic washing tests are shown in Table 26. Caustic washing quite effectively removed the phenolic species from the two lowest boiling fractions (naphtha and jet fuel). In both cases, the yield of phenolic extract was about 3.5% of the feed oil and the phenolic extract contained virtually all of the phenolic functionality of the respective feed. Extraction was less complete with the two higher boiling fractions (diesel fuel and residuum); only about half of the phenolic functionality was removed in the extract.

¹H-NMR analysis of the raffinates (Table 27), when compared with similar analyses of the feed fractions (Table 24), show that the relative concen-

trations of uncondensed aromatic and alpha protons are reduced in the raffinates of the naphtha and jet fuel fractions. This is consistent with the selective removal of alkyl phenols from those fractions.

The phenolic extracts from all four fractions were analyzed by GC/MS. The results of the analyses on the naphtha and jet fuel extracts are summarized in Table 28. The naphtha phenolic extract is composed of C₀- to C₃-phenols and it is nearly pure; i.e., there are no major non-phenolic components. The jet fuel phenolic extract is composed of C₀- to C₄-phenols and indanol; it too is fairly pure, though there are some non-phenolic minor components present (mainly alkyl benzenes and Dowtherm A components). The extracts from the diesel fuel and residuum fractions were heavily contaminated with hydrocarbons. Specific phenols identified in the diesel fuel extract include indanol and cyclohexyl phenol, as well as others.

REACTIVITY COMPARISON OF WILSONVILLE BLACK THUNDER COALS

BACKGROUND

Wilsonville has found, on occasion, that the liquefaction reactivity (as measured by microautoclave tests) of low-rank coal samples from the coal stockpile differed from that of the samples of pulverized coal being fed to the plant. In microautoclave tests of Black Thunder coal fed during Run 262, Wilsonville obtained coal conversions of 75-80% with pile samples and 60-65% with tote-bin (pulverized feed coal) samples. Test conditions were: (10 g of solvent of 25% tetralin/75% 1-methylnaphthalene, 5 g of coal, 30 min at 750°F).¹⁹ Dr. Charles Cantrell sent one Black Thunder pile sample and one Black Thunder tote-bin sample to CONSOL and requested that we check their relative liquefaction reactivities.

RESULTS AND DISCUSSION

CONSOL tested the reactivity of the two Black Thunder coal samples from Wilsonville. One sample was lump coal taken from the stockpile prior to the start of Run 262 (Wilsonville sample no. 21959, dated 6/25/91), the other was composited from tote-bins (TB) of ground coal used during the run (Wilsonville sample No. 22461, dated 7/3/91, composited from TB sample 11076 (Wilsonville No. 21964) and TB sample 11088 (Wilsonville No. 21976)). After the samples were received (8/13/91), the pile sample was air-dried for a few hours and one-half of it was ground to approximately the same particle size (95% -200 mesh) as the tote-bin sample. Lab analyses gave 22.38 wt % as-determined moisture and 6.11 wt % MF ash for the pile sample and 22.48 wt % as-determined moisture and 6.45 wt % MF ash for the tote-bin sample. Microautoclave tests were performed in duplicate with both coals at modified-equilibrium conditions (9 g solvent, 6 g coal, 30 min at 750°F) using Wilsonville Run 260 V-131B distillate composite as the solvent. The pile sample gave coal conversions of 71.6 and 70.7% MAF, and the tote-bin sample gave conversions of 67.2 and 70.7% MAF. Thus, the coals do not appear to differ in reactivity, when tested with the process solvent. Since the Wilsonville tests were made with a model solvent, a set of tests was performed with

the same composition of model solvent as was used at Wilsonville. However, the CONSOL microautoclave tests used a 1.5 solvent/coal ratio, whereas the Wilsonville microautoclave tests were made with a 2.0 solvent/coal ratio. The CONSOL tests using the model solvent gave 58.5% conversion with the pile sample, and 60.8% conversion with the tote-bin sample. These results combined with those obtained with the process solvent lead to the conclusion that there is no significant reactivity difference between the two coals.

We determined FTIR oxidation indices of the two samples using a diffuse reflectance sampling technique.^{20,21} The pile sample had an index of 4.48 ± 0.02 and the tote-bin sample had an index of 3.90 ± 0.51 .

Alkali extraction tests also were performed in duplicate on the two Black Thunder coal samples. The alkali extraction test developed by Lowenhaupt and Gray²² for bituminous coals was modified to accommodate low-rank coals. The only modification made was to dilute the extract solution by 50:1 prior to spectroscopic analysis. Results were 91.7 and 94.4% transmittance (T) for the pile sample tests and 89.7 and 92.5% T for the tote-bin sample tests. The results indicate no significant difference between the coals. We note, however, that the applicability of this test to detection of low-rank coal oxidation has not been fully demonstrated.

The conclusion drawn from the analysis of the Black Thunder samples sent to CONSOL is that the pile and tote-bin samples do not significantly differ in liquefaction reactivity in microautoclave tests, nor do they appear to differ significantly by two techniques used to detect coal oxidation. Either these samples were not typical of those Wilsonville had previously observed reactivity differences in, or other differences exist in CONSOL and Wilsonville test conditions which affected the test results. No further work is planned with these samples.

PARTICIPANTS PROGRAM STATUS

SUMMARY

The following items were accomplished in the ninth quarter of this contract.

Phase I

- Final reports were received from Western Research Institute, SRI International, Virginia Polytechnic Institute and State University, and The Pennsylvania State University. CONSOL evaluations were written for each report.
- The Western Research Institute and The Pennsylvania State University final reports were given patent and technical approval and were sent for printing.
- Draft final reports were received from Advanced Fuel Research, and National Institute for Petroleum and Energy Research (NIPER).
- An interim assessment was written. It is included elsewhere in this report.
- With this progress, Phase I now is nearly complete.

Phase II

- Site visits were made to three potential participants. This completes all planned site visits. Trip reports were issued.
- Statements of Work were issued to eight potential participants.
- Purchase order contracts were issued to four potential participants.
- Nine proposals were declined due to technical merit, time, or budgetary constraints.

- Contracts were signed and initiated with Lehigh University, West Virginia University, and University of Kentucky/IMMR. Samples were shipped.

DISCUSSION

Phase I

The final version of the WRI and SRI final reports were received and the CONSOL evaluations were written. A draft final report was received from Virginia Polytechnic Institute. A discussion was held with the researchers at Virginia Polytechnic Institute concerning the draft report; some revisions were agreed to. The revised final report was subsequently received and the CONSOL evaluation was written. A final report was received from The Pennsylvania State University; a CONSOL evaluation was written. The CONSOL evaluation and Executive summaries of the WRI, Pennsylvania State University, SRI International, and Virginia Polytechnic Institute and State University final reports are found elsewhere in this report.

The WRI and Penn State final reports with CONSOL evaluations received DOE technical and patent approvals. The SRI final report with CONSOL evaluation received DOE technical approval.

A draft final report was received from Advanced Fuel Research (AFR). It was reviewed; AFR has agreed to make some changes. A draft final report was received from NIPER. It is being reviewed.

An interim assessment for the program was drafted. It is included elsewhere in this report.

Phase II

Site visits were made to West Virginia University, Iowa State University, and the University of Utah to discuss possible collaborative efforts with Drs. Mohindar Seehra, John Verkade and Ron Pugmire, respectively. This

completes all planned site visits. Trip reports were issued for each site visit. Trip reports issued to all planned Phase II participants are appended to this report (Appendix 1).

Statements of Work based on proposals and trip reports were written and issued to Lehigh University, the University of Kentucky, the Massachusetts Institute of Technology, West Virginia University, The University of Pittsburgh, the University of Chicago, and Iowa State University. A sample of THF-soluble distillation resid was sent to Dr. Ron Pugmire (University of Utah) for evaluation by different NMR techniques. Based on his findings with this sample a statement of work was issued.

Cost proposals and Representations and Certification packages were received from Lehigh University, the University of Kentucky, West Virginia University (WVU), the University of Pittsburgh, the University of Chicago, and Iowa State University. The statements of work and ancillary documentation were sent to DOE for technical review and approval. Technical approval was received for subcontracts with the Lehigh, Kentucky, University of Pittsburgh, West Virginia University, and Iowa State University. Purchase order contracts were issued to each organization except Iowa State.

Signed contracts were received from Lehigh University, University of Kentucky, and West Virginia University. Samples were shipped. Analytical and Processing information pertinent to the samples was sent to each of these participants. Sample sets for other Phase II participants are being prepared.

A number of submitted projects for Phase II were declined. They include those submitted by Frank Lee, Research and Development Department, Amoco Oil Co., David Wertz, University of Southern Mississippi, Kent Voorhees, Colorado School of Mines, John McClelland, Robert Jacobsen, and Robert Cozemius of Iowa State University. Irving Wender (University of Pittsburgh) contacted us and offered to submit a research proposal for Phase II. We declined his offer due to time and budgetary constraints.

David Wertz (University of Southern Mississippi) responded by offering to analyze samples on a no-cost basis. A letter was sent to Dr. Wertz offering to send samples.

CONSOL EVALUATION AND EXECUTIVE SUMMARIES OF FINAL REPORTS FROM WESTERN RESEARCH, THE PENNSYLVANIA STATE UNIVERSITY, SRI INTERNATIONAL, AND VIRGINIA POLYTECHNIC INSTITUTE AND STATE UNIVERSITY

GENERAL DESCRIPTION

This section consists of four parts. Each part is comprised of the CONSOL summary of the program and results of one of the Phase I subcontracts and the Executive Summary supplied by that contractor. The four subcontracts described were completed by Western Research Institute (WRI), The Pennsylvania State University (PSU), SRI International, Inc. (SRI), and Virginia Polytechnic Institute and State University (VPI).

WESTERN RESEARCH INSTITUTE

Summary

This study clearly demonstrated the usefulness of liquid- and solid-state ^{13}C - and ^1H -NMR for the examination of process-derived materials from direct coal liquefaction. The techniques can provide data not directly obtainable by other methods to examine the saturation of aromatic rings and to determine the modes of hydrogen utilization during coal liquefaction. In addition, these methods can be used to infer the extent of condensation and retrograde reactions occurring in the direct coal liquefaction process. Five NMR techniques were employed. Solid-state ^{13}C -NMR measurements were made using the Cross Polarization Magic Angle Spinning (CP/MAS) and Single Pulse (SP) techniques. Solid-state ^1H -NMR measurements were made using the technique of Combined Rotation and Multiple-Pulse Spectroscopy (CRAMPS). Conventional liquid-state ^{12}C - and ^1H -NMR techniques were employed as appropriate. Interpretation of the NMR data, once obtained, is relatively straightforward. Combined with other information, such as elemental analyses and process conversion data, the NMR data prove to be a powerful tool for the examination of direct coal liquefaction process-derived material. Further development and more wide-spread application of this analytical method as a process development tool is justified on the basis of these results.

Program Description

This report describes the work performed at Western Research Institute under a subcontract to CONSOL INC., Research and Development. CONSOL's prime contract to the U.S. Department of Energy (Contract No. DE-AC22-89PC89883, "Coal Liquefaction Process Streams Characterization and Evaluation") established a program for the analysis of direct coal liquefaction materials. The program involves a number of participating organizations whose analytical expertise is being applied to these materials. This Participants Program has two main objectives. The broad objective is to improve our understanding of fundamental coal liquefaction chemistry to facilitate process improvement and new process development. The specific approach to achieving this objective is to provide a bridge between direct coal liquefaction process development and analytical chemistry by demonstrating the application of various advanced analytical methods to coal liquefaction materials. The methodologies (or techniques) of interest are those which are novel in their application for the support of coal liquefaction process development and those which have not been fully demonstrated in this application. CONSOL is providing well-documented samples from different continuous direct coal liquefaction facilities to the program participants. The participants are required to interpret their analytical data in context to the processing conditions under which the samples were generated. The methodology employed is then evaluated for its usefulness in analyzing direct coal liquefaction-derived materials.

Methodology

WRI used solid- and liquid-state ^{13}C - and ^1H -NMR to analyze nineteen samples. The sample set consisted of four coals, six coal liquefaction distillation resids (850°F⁺), two coal liquefaction process distillates, and one coal liquefaction ash concentrate. The resids are solid at room temperature and contain THF-soluble and insoluble organics and mineral matter. The samples were produced at two different continuous liquefaction facilities: the Wilsonville pilot plant and the Hydrocarbon Research Inc. (HRI) bench unit. The major processing parameter varied among the

Wilsonville runs was feed coal. Samples from Wilsonville were taken from five locations around the plant. These samples are expected to represent different extents of coal liquefaction. Some of the Wilsonville samples were composites of samples taken over long periods of single runs; others were samples obtained from a single run day. The samples from HRI also were chosen to represent material which had undergone different degrees of processing and were obtained from different plant locations.

Major Findings

The following principal observations for the application of solid- and liquid-state ^{13}C - and ^1H -NMR to coal liquefaction materials were reported by WRI.

^{13}C - and ^1H -NMR measurements were used to obtain the aromatic H/C ratio of the feed coals and liquefaction products of Wilsonville Runs 251-II, 257 and 259. This information was used to assess the relative degree of condensation of samples at different stages in the liquefaction process. Little difference in the aromatic H/C ratio was observed in interstage and second stage product samples obtained from the same Wilsonville run. Though the interpretation of this observation is not conclusive, it can be inferred that neither condensation reactions nor the reduction of aromatic-ring cluster size are extensive in the second stage.

^{13}C -NMR data were collected on a set of samples obtained from different sampling points during a single run period at the Wilsonville facility (Run 259G). The NMR data were used along with elemental analyses and mass balance data to examine the progress of aromatic carbon saturation at various stages of liquefaction. About 58% of the aromatic carbon in Pittsburgh coal was saturated through the process, most of it in the second stage. The modes of hydrogen utilization during the same Wilsonville run were determined using the same set of NMR, analytical and mass balance data according to a slightly modified version of the method of Finseth et al.²³ It was shown that aromatic ring saturation consumes most of the hydrogen in the two-stage liquefaction process. This is

followed by hydrogen consumed by coal matrix cleavage, by the production of heterogases, by the production of hydrocarbon gases ($C_1 \times C_6$) through hydrogenolysis, and by that consumed to replace carbon-heteroatom bonds with carbon-hydrogen bonds through hydrogenolysis. Almost all of the hydrogen consumed by matrix cleavage is consumed in the first stage. Additionally, the first stage accounts for about 70% of the hydrogen consumption for total gas production, i.e., for hydrogenolysis to produce hydrocarbon gases and heterogases and for the hydrogen contained in heterogases. Two-thirds of the hydrogen consumed in the second stage is consumed by saturation of aromatic rings.

The NMR measurements provided quantitation of numerous carbon and hydrogen types that could, in theory, be used as pseudo-components for lumped kinetic modeling in a manner similar to that of Chen and Schindler.²⁴

Repeat measurements showed that reproducible aromaticity measurements could be made on a routine basis. SP and CP/MAS measurements agreed well for coal but not as well for the coal liquids.

CONSOL Evaluation

Solid-state NMR appears to be the most direct means to obtain the aromaticity value of solids-containing process streams. This useful piece of information, when combined with the mass balances and the elemental analyses of the materials analyzed, provides information on the degree of hydrogenation and modes of hydrogen utilization during coal liquefaction. Additionally, the extent of condensation or retrograde reactions that occur in the various product streams can be inferred from this measurement.

The precision of the techniques examined is high. The aromaticity measurements of the same samples are highly reproducible. The SP and CP/MAS techniques give good agreement for the aromaticity of coals; there is also good agreement with findings of other laboratories for different samples of coal from the same seam. The solid-state ^{13}C -NMR techniques

can be fairly rapid, requiring about one-half hour per sample for data acquisition to obtain adequate signal-to-noise ratios. The initial capital investment for a 100 Mhz instrument with the appropriate equipment for CRAMPS measurements is approximately \$175,000. The labor costs are relatively low. Sample preparation is minimal, requiring only that the sample be uniformly ground and uniformly packed into the NMR tube. Samples need not be ground smaller than 100 mesh (150 μ m). Solid-state ^1H -NMR and liquid NMR require only 1-2 minutes data acquisition time. There is, however, some time required to do the set-up for the CRAMPS procedure. Once the initial set-up is done, the sample preparation and examination can be done by a laboratory technician. Computer integration of sample signal provides quantitative information. Visual inspection of CRAMPS spectra can provide qualitative information.

Further Development

The information obtainable with the solid-state NMR techniques could be used to develop a lumped kinetic model for coal liquefaction. Because of the lower resolution of the solid-state measurements, spectral curve-fitting techniques may need to be employed to obtain the necessary structural parameters for input to the kinetic model.

Statement of Work

Solid-state nuclear magnetic resonance (NMR) techniques have been applied to various fuel materials such as coals and shales; however, little work has been done to utilize solid-state NMR for analysis of coal liquefaction process streams. As such, this technique is novel and fits within the scope of the participants program.

Four applications of this technique will be explored in this work.

1. Aromatic hydrogen to aromatic carbon ratios will be determined for a suite of coals and coal liquefaction sample distillation residues via solid state ^{13}C and ^1H -NMR.

2. A carbon aromaticity balance will be determined to gain a more fundamental understanding of the chemistry associated with each stage of the liquefaction process starting with the feed coal for two different processes (Wilsonville and HRI).
3. Each spectrum generated will be deconvoluted to measure pseudo-component contents of coals and resids to partially evaluate the use of the technique to generate data for an extended lumped kinetic model.
4. A hydrogen balance will be made over the Wilsonville plant based NMR data, and information provided to WRI by CONSOL, using the method of Finseth et al.²³

CONSOL will supply to WRI seventeen well documented samples (four coals, six non-distillable resids, two process distillates, and five process oils), for solid-state and liquid NMR analyses. Each process oil and resid sample will be supplied to WRI with the following information as appropriate and as available: elemental analysis, ash content, ash elemental analysis, phenolic -OH concentration, calorific value, hydrogen classes by ¹H-NMR, and the full history of the resid samples (plant, process conditions, age, storage conditions, total hydrogen consumption, and heteroatom and hydrocarbon gas yield data for the associated run). The coal samples will be supplied with a proximate and ultimate analysis and will be supplied ground to pass 100 mesh (0.15 mm). The resids are brittle pitch-like materials, and will be supplied as particles which pass approximately 8 mesh (2.4 mm). All resid and process oil samples may contain ash. Sample size will be at least 5 g. These seventeen samples will form a basis for an evaluation of the method.

The two process distillates will be analyzed by WRI using conventional liquid NMR techniques. The remaining samples will be analyzed by WRI utilizing the following methodology. Carbon aromaticity measurements will be made at a ¹³C frequency of 25 MHz on a Chemagnetics CMX-100/200 solids NMR spectrometer. Cross-Polarization Magic-Angle Spinning (CP/MAS) experiments will be employed using a 9.5 mm zirconia spinner.

Carbon aromaticity measurements will be made using currently accepted NMR parameters. Hydrogen aromaticity measurements will be made at a ^1H frequency of 200 MHz on a Chemagnetics CMX-100/200 solids NMR spectrometer using the technique of combined rotation and multiple pulse spectroscopy (CRAMPS). Replicate analyses will be performed as necessary to assess reproducibility. At least one of the coals, one of the resids and one of the whole process oils will be analyzed by the single-pulse magic angle spinning (SP/MAS) method to provide data for comparison with those generated by the CP/MAS method.

The deconvolution of the spectra to component classes (or psuedocomponents) will be done for each sample. Component classes will include, as a minimum, H_{ar} , C_{ar} , $\text{H}_{\text{ar}}/\text{C}_{\text{ar}}$, $\text{C}_{\text{carbonyl}}$, $\text{H}_{\text{aliph.}}$, $\text{C}_{\text{aliph.}}$, and $\text{H}_{\text{aliph.}}/\text{C}_{\text{aliph.}}$. Additional component classes will be provided as available. Hydrogen accounting techniques will be applied to four of the samples.

WRI Executive Summary

Solid-State ^{13}C and ^1H -NMR measurements were made on whole coals, product oil resids, and whole product oils obtained from different stages of coal liquefaction and from different liquefaction processes. Cross polarization (CP) and magic-angle spinning (MAS), and single pulse measurements were made to determine carbon aromaticities; combined rotation and multiple-pulse spectroscopy (CRAMPS) techniques were employed to determine the hydrogen aromaticities in these materials. The objectives of this study were to provide data that are important for closing aromaticity balances, for determining the extent of condensation and retrograde reactions, and for determining the modes of hydrogen utilization during coal liquefaction. Such data are difficult, if not impossible, to acquire by any other means.

The NMR measurements were made on nineteen samples comprising coals and liquefaction products obtained from Wilsonville and Hydrocarbon Research Incorporated (HRI) coal liquefaction experiments on subbituminous and bituminous coals. The coal samples were divided into three sets. One set was used for measuring aromatic hydrogen-to-carbon ratios in raw

coals and process oil resids from Wilsonville liquefaction runs on Illinois No. 6, Pittsburgh, and Wyodak coals. A second set of samples was obtained from HRI liquefaction runs on Black Thunder mine subbituminous coal and Wilsonville runs on Ireland Mine Pittsburgh seam coal. A third set of samples from Pittsburgh seam coal was used for hydrogen utilization measurements.

^{13}C -NMR aromaticity measurements were made in duplicate on several samples to assess the reproducibility of the aromaticity measurements. The results showed that reproducible aromaticity measurements could be obtained on a routine basis. Comparisons between single pulse and cross polarization aromaticity measurements were good for coal, but only fair for coal products.

Aromatic hydrogen-to-carbon (H/C) ratios were calculated from elemental analyses and ^{13}C and ^1H -NMR aromaticity measurements. The aromatic H/C ratio of the resids remained fairly constant between the first-stage and the second-stage reactors from Wilsonville runs, suggesting that most of the condensation/retrograde reactions take place in the first-stage reactor. The aromatic H/C ratios of some of the raw coals had values similar to the resids. However, by comparing their CP/MAS ^{13}C -NMR spectra, it was inferred that the raw coal aromatic H/C values were influenced mainly by small, highly substituted aromatic rings rather than by large, condensed aromatic ring systems. Some resids had lower carbon aromaticities and higher aliphatic carbon intensities than the starting coal. These observations are consistent with some hydrogenation of aromatic rings taking place during liquefaction.

NMR measurements were combined with elemental analysis and mass balance data to obtain aromatic carbon balances for Wilsonville coal liquefaction run 259G. By measuring the increase or decrease of aromatic carbon in the various liquefaction products, the degree of hydrogenation at various stages of liquefaction and under various conditions can be ascertained. On the basis of the feed coal, about 58% of the aromatic carbon in Pittsburgh coal was hydrogenated during two-stage liquefaction, and 57% of the hydrogenation occurred during the second stage.

Liquid- and solid-state NMR measurements, in conjunction with other analytical and conversion data, were employed to determine the modes of hydrogen utilization during liquefaction. In principle, the amount of hydrogen consumed for producing coal liquids, producing hydrocarbon gases, and removing heteroatoms can be obtained from these combined measurements. A net of 54.8 mol of hydrogen per 100 mol of coal carbon were consumed during the first stage of Wilsonville Run 259G. This amounted to 66.5% of the total overall two-stage hydrogen consumption. Matrix cleavage and hydrogenation reactions accounted for 40% and 33%, respectively, of the total first-stage hydrogen consumption. Most (77%) of the hydrogen consumed during the second stage was used for hydrogenation. Overall, hydrogenation reactions accounted for 48% of the overall two-stage total hydrogen consumption. These observations are consistent with the notion that the first stage involves a dissolution stage, whereas the second stage is primarily an upgrading stage.

THE PENNSYLVANIA STATE UNIVERSITY

Summary

This study demonstrated the use of the gold tube carbonization technique and reflectance microscopy analysis for the examination of process-derived materials from direct coal liquefaction. The carbonization technique, which was applied to coal liquefaction distillation resid, yields information on the amounts of gas plus distillate, pyridine-soluble resid, and pyridine-insoluble material formed when a coal liquid sample is heated to 450°C for one hour at 5000 psi in an inert atmosphere. The pyridine-insolubles then are examined by reflectance microscopy to determine the type, amount, and optical texture of isotropic and anisotropic carbon formed upon carbonization. The gold tube carbonization technique is a potentially useful method to measure the propensity of coal liquids to undergo retrograde (coking) reactions. The amount of pyridine-insoluble material formed upon carbonization of different resids was found to correspond with process conditions and feed coal characteristics. Experimental difficulties were experienced in the application of the carbonization technique to these samples; some were

apparently related to problems in obtaining representative small aliquots of the heterogeneous, solids-containing samples. Other problems were attributable to the equipment used and the experimental procedures employed.

The reflectance microscopy technique, which was applied to insoluble residues from coal liquefaction process samples, also has the potential to provide insight into the progress of conversion and retrograde reactions in the liquefaction system. It was possible to evaluate the reflectance variations of vitrinite- and process-derived residue components and determine their relationship with the rank of the feed coal, reaction temperature, and the impact of catalysts. Further development of these analytical methods as process development tools may be justified on the basis of these results.

Program Description

This report describes the work performed at the Energy and Fuels Research Center of The Pennsylvania State University under a subcontract to CONSOL INC., Research and Development. CONSOL's prime contract to the U.S. Department of Energy (Contract No. DE-AC22-89PC89883, "Coal Liquefaction Process Streams Characterization and Evaluation") established a program for the analysis of direct coal liquefaction materials. The program involves a number of participating organizations whose analytical expertise is being applied to these materials. This Participants Program has two main objectives. The broad objective is to improve our understanding of fundamental coal liquefaction chemistry to facilitate process improvement and new process development. The specific approach to achieving this objective is to provide a bridge between direct coal liquefaction process development and analytical chemistry by demonstrating the application of various advanced analytical methods to coal liquefaction materials. The methodologies (or techniques) of interest are those which are novel in their application for the support of coal liquefaction process development and those which have not been fully demonstrated in this application. CONSOL is providing well-documented samples from different continuous direct coal liquefaction

facilities to the program participants. The participants are required to interpret their analytical data in context of the processing conditions under which the samples were generated. The analytical methodology employed then is evaluated for its usefulness in analyzing direct coal liquefaction-derived materials.

Methodology

Penn State applied the gold tube carbonization technique and reflectance microscopy analysis to a total of twenty-eight samples. The sample set for application of the gold tube carbonization tests consisted of eighteen coal liquefaction distillation resids (850°F⁺) and two blind samples. The resids are solid at room temperature and contain THF-soluble and insoluble organics and mineral matter. THF-insoluble portions of eight distillation resids were supplied for petrographic analysis by reflectance microscopy. The 28 samples were produced at three different continuous liquefaction facilities: the Wilsonville pilot plant, the Hydrocarbon Research Inc. (HRI) bench unit, and the Lummus process development unit. The major processing parameters which varied among the Wilsonville runs were feed coal, catalyst, ash recycle, and sampling location in the plant. Samples from Wilsonville were taken from two different locations in the plant. These samples are expected to represent different extents of coal liquefaction. Some of the Wilsonville samples were composites of samples taken over long periods of single runs; others were samples obtained from a single run day. The samples from HRI also were chosen to represent material which had undergone different degrees of processing and were obtained from different plant locations. HRI samples also were chosen for a comparison of materials produced with and without the use of a thermal pretreatment of the feed coal. The Lummus samples represented ash-containing and deashed recycle streams.

The gold tube carbonization technique is a three-step procedure: the sample is carbonized, the product is extracted, and the insoluble material is evaluated petrographically by reflectance microscopy.

The reflectance microscopy (petrography) technique allows for an evaluation of the degree of condensation or hydrogenation of the resid. An increase in reflectance, upon processing, of the vitroplast contained in the sample indicates that the material has undergone condensation. Alternatively, a decrease in reflectance indicates that the material has undergone hydrogenation.

Major Findings

The following principal observations were reported by Penn State for the application of the gold tube carbonization technique and reflectance microscopy to coal liquefaction materials. The gas plus condensate values obtained in the gold tube test correlate with the total paraffinic proton content of the resids. The quality and quantity of pyridine-insoluble material produced in the carbonization test was dependent on several factors including feed coal rank, oxygen content of the resids and of the native feed coal, and sampling location in the production facility. The production of pyridine-insolubles was greater with resids produced from low-rank and weathered coals and resids taken from the first-stage reactor, especially when that reactor was operated thermally. The pyridine-insoluble carbonization residues were comprised of substantial amounts of anisotropic carbon formed through the development of mesophase. Interstage samples generated higher concentrations of mesophase spheres and mosaics than recycle samples; thus, the interstage samples appear to have a greater propensity for coking. However, high concentrations of ash and insoluble organic material in some samples interfered with the development, growth, and coalescence of mesophase.

Petrographic analyses were performed on a set of tetrahydrofuran-insoluble process samples. Various components were quantified by point counting, and reflectance values were determined for partially reacted vitrinite and high- and low-reflecting vitroplast. The processing variable which had the strongest influence on the vitroplast reflectance was reactor temperature. Higher temperatures produced higher reflectances. The comparison of interstage samples taken during operations with a low-temperature catalytic first stage with those taken during

operations with a high-temperature thermal first stage showed that temperature, not degree of conversion, had the principal influence on vitroplast reflectance. The inference from this is that higher temperature promoted condensation reactions. The reflectance of partially reacted vitrinite increased in the order: feed coal < interstage sample < recycle sample; thus, its reflectance increased with residence time in the system.

CONSOL Evaluation

The gold tube carbonization test has potential for application to process-derived samples. For the samples analyzed here, the reproducibility of the method was not high. However, trends clearly can be detected. This indicates that the technique has the potential for analysis of these materials and is useful for process development. This utility could be increased by improving reproducibility. The presence of IOM and ash in the samples studied was partially responsible for the poor observed reproducibility. In general, analyzing inhomogeneous materials may be problematic. It appears that reproducibility problems could be minimized by application of the technique to solids-free samples. However, dedication of this technique to solids-free samples will reduce its usefulness as a process development tool. The gold tube carbonization test is labor intensive. Sample preparation is time consuming and requires considerable skill. The carbonization experiment requires roughly three hours, including pressurization, heat up, soak time, cool down, and depressurization. Sample work-up requires approximately 48 hours for pyridine extraction of the samples plus the time necessary to examine the samples by optical microscopy. The carbonization equipment is costly (approximately \$100,000), because high pressures and temperatures are required for the reaction. The gold tubing, which is preferred for use as the mini-reactor, also is costly.

Two blind samples were provided for testing in the gold tube experiment. One sample was correctly identified as an interstage resid produced at the Wilsonville facility. It was, in fact, the same material that was issued as sample Reference No. 8, the whole interstage resid from

Wilsonville Run 257. The second blind sample was a duplicate of the sample issued to Penn State as sample Reference No. 9, a whole recycle resid from Wilsonville Run 259. The Penn State researchers correctly identified it as a Wilsonville recycle resid. However, they found no mineral matter in either sample and believed them to be deashed samples. This illustrates the sampling difficulties discussed earlier. In both cases, they incorrectly identified the blind samples as the products of a low rank feed coal. Run 257 used Illinois No.6 coal as feed, and Run 259 used Pittsburgh seam coal as feed; both are of high-volatile bituminous rank. The incorrect identifications resulted, in part, from sampling difficulties.

The reflectance microscopy technique was shown to be potentially useful for the analysis of solid heterogeneous, process-derived samples. The method demonstrated a high degree of reproducibility in examination of the vitroplast reflectance (0.008% mean deviation in reflectance) and somewhat poorer precision for partially reacted vitrinite (0.032%). Some relationships can be observed between reflectance measurements and processing parameters such as reactor temperatures, the presence or absence of catalyst, and feed coal rank. In some cases, certain expected trends due to major process variable changes such as reactor temperature or the presence or absence of catalyst were obscured by other process variables such as residence time. A clear explanation for differences in the reflectance measurements of samples produced under diverse conditions may not be possible. The reflectance method is relatively rapid, requiring only a few minutes for examination of the sample. The equipment cost is on the order of \$85,000.

Further Development

There are a number of avenues for further development of the techniques described here. The gold tube carbonization method needs to be further refined. Experimental parameters were originally established to accommodate solvent refined coal (SRC) samples, and may not be appropriate for samples from current liquefaction processes. Problems associated with sampling heterogeneous samples need to be resolved before the method can

be considered a tool for process development. This may entail better homogenizing the samples mechanically or using only the soluble portion of the resids. The latter choice may cause problems in interpretation of the results.

A relationship was observed between the amount of pyridine-insoluble material produced in the gold tube experiment and the oxygen content (rank) and weathered status of the feed coal. Additionally, the phenolic -OH content of the resid was correlated with the amount of pyridine-insolubles formed in the gold tube experiment. These relationships are of considerable interest. Relationships with these and other resid properties should be further explored after the precision of the method is improved.

Reflectance microscopy is well developed for inspection of coal macerals, but not for solid direct coal liquefaction process-derived materials. In the work done here, the method showed considerable potential for analysis of the THF-insoluble portion of direct coal liquefaction resids. Prior to full utilization of the method for process development, however, an expanded sample set of well-documented materials will need to be examined and evaluated so that a better understanding of the influence of process variables on the reflectance measurements can be obtained.

Statement of Work

Within the liquefaction process, coal-derived liquids may participate in condensation reactions and the formation of semi-coke through a mesophase mechanism. These reactions are inimical to the process and may be responsible for some operational problems, reduced reactivities toward conversion, and reduced yields of desirable products. Controlled carbonization experiments, followed by optical microscopy (for examination of the pyridine insoluble portion of the carbonization product), may be a useful empirical test for an improved understanding of these mechanisms. The gold tube carbonization test devised at Penn State is such a method. In this technique the propensity of different coal liquids to become involved in retrograde (coking) reactions can be determined. This

technique has been applied to SRC-II materials and liquid chromatographic fractions of coal liquids, but not coal liquefaction process streams produced by current technology. As such, this technique fits within the scope of the participants program. This test yields information on the total amount of isotropic and anisotropic carbon formed, and its mosaic texture, when a coal liquid sample is heated in an inert atmosphere to 450°C for one hour at 5000 psi. The technique requires approximately 250 mg of sample.

Examination of the solid organic materials resident in coal liquefaction process streams by reflectance microscopy may also provide some insight into the progress of conversion and retrograde reactions in the liquefaction system. A shift to higher reflectance of the vitroplast contained in the sample, relative to the feed coal vitrinite, will indicate that the material has undergone retrogressive reactions to more condensed structures, and a lower reflectance can be interpreted as evidence of hydrogenation.

CONSOL will supply to Penn State twenty-eight (28) samples; twenty for gold tube carbonization tests and optical microscopy, and eight for reflectance microscopy.

Eighteen of the twenty samples designated for gold tube carbonization experiments will be supplied to Penn State with the following information, as available: elemental analyses, ash content, ash elemental analysis, phenolic -OH concentration, calorific value, hydrogen classes by 1H-NMR, and the full history of the sample (plant, process conditions, age, and storage conditions). Two of the twenty samples for gold tube tests will be supplied to Penn State with no documentation to serve as blind controls. The twenty samples designated for gold tube carbonization tests are non-distillable residual materials which may contain insoluble organic matter (IOM) and ash. Sample size will be at least 1 g. Most samples will be brittle pitch-like materials that will be supplied as approximately minus 8 mesh (2.4 mm) pieces. These twenty samples will form the basis for an evaluation of the gold tube carbonization method.

Eight samples designated for reflectance microscopy are the THF-insoluble portion of process stream samples. These samples contain IOM and also may contain ash. Identification of the source stream and other pertinent information will be supplied with these samples. Sample size will be at least 0.5 g.

Penn State will perform the above noted tests and analyses. Replicate reflectance microscopy analyses will be performed as necessary to assess data quality.

PSU Executive Summary

Twenty-eight samples were received from CONSOL in December 1990. Eighteen well-characterized non-distilled resid samples were provided for the evaluation by the gold-tube carbonization technique (Nos. 1-18) and two additional resid samples (Nos. 19 and 20) were provided for blind analysis. The remaining eight samples were provided as THF-insoluble fractions for reflectance photometric measurements on the coal- and process-derived residue materials. These samples (Nos. 21-28) corresponded respectively to eight of the whole product resids (Nos. 7-14) designated for gold-tube carbonization.

The gold-tube carbonization technique employed in this study utilized a 250 mg sample of resid which was welded into gold tubing under a nitrogen atmosphere and at liquid nitrogen temperatures. The tubes were then heated to 450°C for 1 h at a pressure of 5000 psi. Following the reaction, the tubes were vented and the contents Soxhlet extracted in pyridine for 48 h. The percentages of gas + condensate, pyridine-insoluble and -soluble products were obtained. The pyridine-insoluble fraction was prepared for optical microscopy where a point-count analysis was used to determine the amount of anisotropic and isotropic carbon produced from the carbonization.

Complications associated with the gold-tube carbonization tests related to the difficulty in obtaining a representative sample, some furnace control problems, and difficulty with pyridine extraction. Most of these

problems resulted from the use of extremely small samples with variable and unevenly distributed ash and insoluble organic matter (IOM). These problems in combination resulted in poor repeatability with regard to the correlation between pyridine-insoluble material reported following carbonization and the ash + IOM contained in the original sample. Nevertheless, although random variability exists in these data, it was not expected to interfere with the interpretation of major trends.

The percentage of gas + condensate was twice as high for the HRI Black Thunder resids compared to Lummus and Wilsonville resids. A correlation matrix of the data provided at least a partial explanation for this difference. It seems that as the total content of paraffinic protons (^1H -NMR alkyl beta + gamma fractions) increased, the percentage make of gas + condensate during carbonization increased. The Black Thunder resids have the largest amount of paraffinic protons. However, it was not possible to determine with certainty whether the higher paraffinic nature of these resids results from the particular coal being used or from HRI process conditions.

Production of pyridine insolubles appear to be greatly influenced by coal rank and process conditions. Regardless of the liquefaction process, resids from the Wyodak subbituminous coal, those of the Ohio 6 runs using weathered coal, and the thermal/catalytic interstage Illinois 6 samples produced the most pyridine insolubles. Each of these coals have more associated oxygen functionality, some of which has been passed to the resid. A relationship was identified which showed that as the concentration of phenolic hydroxyl increased, so did the amount of pyridine insolubles produced during the gold-tube carbonization.

Comparison of phenolic -OH concentrations with percentage conversion of soluble resid to pyridine insolubles (pyridine-insoluble values corrected for ash + IOM) showed two distinct relationships; generally one for the Wilsonville samples and the other for HRI samples (Lummus is divided among the two relationships). Both relationships show that as phenolic -OH increases, so does conversion of pyridine solubles to insolubles. Thus, for a given level of phenolic -OH, the Black Thunder HRI samples

appear to produce relatively more pyridine insolubles. The Wilsonville samples form a fairly tight relationship, which suggests that when phenolic -OH content of the resids falls below 0.76 meq/g, there may be a net production of pyridine solubles during carbonization.

A rank suite of coals was provided from two-stage catalytic processing at the Wilsonville pilot plant. Samples included resids from the first-stage reactor (interstage) and recycle material that had passed through both stages. More pyridine insolubles were produced from coals of lower (subbituminous) and higher (hvAb) rank compared with two other bituminous coals of intermediate rank. Also, more pyridine insolubles were produced from the interstage resids compared to the recycle material. Thus, the additional catalytic processing provided by the two-stage liquefaction serves to reduce the potential of forming pyridine insolubles. This conclusion was supported by a comparison of the Illinois 6 catalytic/catalytic and thermal/catalytic Wilsonville runs in which more pyridine-insoluble material was formed from the interstage thermal run and the least was produced from the recycle catalytic/catalytic run.

Petrographic analyses performed on all gold-tube carbonization residues (pyridine insoluble) enabled comparisons to be made of the amounts of mesophase carbon produced, and the relative size of the constituent spheres and mosaics to be contrasted. Unfortunately, interpretation of these data was severely hampered by our inability to account for ash and IOM concentrations in the resids. It also may explain why no correlations were found between our petrographic and the chemical data provided by CONSOL. As the concentration of the ash and IOM increased, the size and coalescence of the mesophase decreased.

Generally, a greater total volume percentage of mesophase (spheres and mosaics) was produced from the Wilsonville interstage samples compared to the recycle samples, suggesting that first-stage catalytic reaction generates products having a greater propensity to lead to coking problems. The Illinois 6 thermal/catalytic runs showed higher mesophase production as well. Both the Illinois 6 and Wyodak coals have generated mesophase at the Wilsonville plant over the years. However, analysis of

the gold-tube residues from the Wyodak runs (Lummus and Wilsonville) showed that low-reflecting vitroplast was formed in greater concentration from runs with this coal. This may explain our further observations of a significant amount of secondary vitroplast in the THF-insoluble residues from Wilsonville (Wyodak runs).

Mean random reflectance was performed on process- and vitrinite-derived components (high-reflecting vitroplast, partially reacted vitrinite and low-reflecting vitroplast) of the THF-insoluble residues and their corresponding whole product resids. Evaluation of precision using duplicate analyses showed that vitroplast reflectance could be repeated within an average of 0.008%, whereas that of partially reacted vitrinite had a repeatability of 0.032%. Results of the analyses show that high-reflecting vitroplast reflectance values for the interstage catalytic/catalytic samples are lower or equal to those of the recycle. this trend was reversed for the thermal/catalytic (Illinois 6) runs. Comparing high-reflecting vitroplast reflectance values with the first-stage reaction temperature revealed that initial stage reaction temperature could be maintained at lower levels in the presence of catalyst to achieve the same level of conversion without introducing significant molecular condensation.

Reflectance values for partially reacted vitrinite are higher than those of the feed coals and are higher for the recycle compared with the interstage samples. This may be directly related to the increased residence time in the system for the recycle samples. The Wyodak runs produced a considerable amount of partially reacted vitrinite (huminite), a result which was not unexpected. However, the presence of high-reflecting vitroplast in relatively high concentration was surprising and suggests that the material may be derived from the product fraction.

Partially reacted vitrinite and low-reflecting vitroplast also were observed in fairly large amounts (13-20 and 16-18 volume percent, respectively) in the thermal/catalytic Illinois 6 recycle sample. Point count analyses of the residues revealed that on a whole-residue basis, the two components were found in about 1.0% concentration by volume.

This concentration, although relatively low, may suggest that space rate was perhaps too high during the thermal/catalytic recycle run. This could cause incomplete thermal rupture of coal particles and incomplete hydrogenation of preasphaltenes (low-reflecting vitroplast).

Our general assessment of the application of the two analytical procedures presented in this report to liquefaction process control can be summarized as follows. The gold-tube carbonization technique, although difficult to perform, has some potential for correlating process and coal parameters with resid chemistry(quality). Also, the test can provide a means of evaluating the potential of coals and/or process conditions to produce pyridine insolubles and provide information on whether mesophase-derived carbon may be a problem during processing. Reflectance variations of vitrinite- and process-derived residue components shows some relationship with the rank of the original feed coal, with reaction temperature and the presence or absence of catalysts.

Further, some specific recommendations have been offered to improve the precision of the gold-tube carbonization test. These include performing the test on samples which are free of ash and IOM, samples should be properly homogenized before analysis to eliminate subsampling problems, a greater sample weight should be employed, and alundum thimbles should be used during Soxhlet extraction.

SRI INTERNATIONAL

Summary

This study provided a clear demonstration of the potential utility of field ionization mass spectrometry (FIMS) for the examination of distillation resid materials (b.pt. >850°F) derived from direct coal liquefaction. The technique can be used to determine the molecular weight profile of a resid sample and provide speciation of some components of the resid. A simple data analysis method which deconvolutes the mass profile into two groups was applied to the FIMS profiles generated in this study. Using this approach, quantified differences among the

samples could be related to the various process conditions under which the samples were produced. It was also possible to make inferences from the FIMS data regarding resid reactivity. The FIMS technique, coupled with this or similar data analysis methods, therefore, can be considered a potentially useful technique for the process developer. Homologous series of various tetra- to hexacondensed aromatics (and naphthenoaromatics for which no corresponding fully aromatic structures exist) were identified in the samples. These compounds have been shown by others to be related to the reactivity of petroleum vacuum gas oil toward hydroprocessing. It appears that this is also true concerning the reactivity of coal-derived resids toward hydrocracking and that the presence of these compounds is related to the processing conditions that produced the samples. Further development of this analytical method as a process development tool is justified based on these results.

The use of iodotrimethylsilane to derivatize and subsequently quantitate the oxygen bound to alkyl carbon in coal liquefaction resids also was investigated in this study. The total amount of derivatizable oxygen was found to be less than 20% of the total oxygen for all samples. Experimental problems were encountered in the application of this method that prevented a more precise determination of the concentrations of alkyl carbon/oxygen bonds. Further development of this analytical method as a process development tool does not seem to be justified on the basis of these results.

Program Description

This report describes the work performed at SRI International under a subcontract to CONSOL INC., Research and Development. CONSOL's prime contract to the U.S. Department of Energy (Contract No. DE-AC22-89PC89883, "Coal Liquefaction Process Streams Characterization and Evaluation") established a program for the analysis of direct coal liquefaction derived materials. The program involves a number of participating organizations whose analytical expertise is being applied to these materials. This Participants Program has two main objectives. The broad objective is to improve our understanding of fundamental coal

liquefaction chemistry to facilitate process improvement and new process development. The specific approach to achieving this objective is to provide a bridge between direct coal liquefaction process development and analytical chemistry by demonstrating the application of various advanced analytical methods to coal liquefaction materials. The methodologies (or techniques) of interest are those which are novel in their application for the support of coal liquefaction process development, and those which have not been fully demonstrated in this application. CONSOL is providing well-documented samples from different direct coal liquefaction process development facilities to the program participants. The participants are required to interpret their analytical data in context to the processing conditions under which the samples were generated. The methodology employed then is evaluated for its usefulness in analyzing direct coal liquefaction derived materials.

Methodology

SRI used field ionization mass spectrometry (FIMS) to analyze distillation resids (850°F⁺). These are solids at room temperature, and contain THF-soluble and insoluble organic material and mineral matter. The samples were produced at the Wilsonville pilot plant. Two major processing parameters were varied among the Wilsonville runs: feed coal and reactor configuration (thermal/catalytic or catalytic/catalytic). Samples from Wilsonville were taken from three locations: between the reactors, after the second-stage reactor, and at the recycle oil tank. These samples are expected to represent different extents of coal liquefaction. The majority of the Wilsonville samples were composites of samples taken over long periods of single runs. Two interstage samples were obtained from single run periods and were chosen to represent thermal vs. catalytic first-stage processing.

The oxygen derivatization (iodotrimethylsilane analysis) technique was applied to whole process oils obtained from two facilities: the Wilsonville pilot plant and Hydrocarbon Research Inc. (HRI) bench unit. Feed coal rank was the major processing parameter which varied among the Wilsonville runs. Samples from HRI were chosen to represent production

of material from runs utilizing a raw feed coal and a feed coal that had been pretreated to reduce its oxygen content.

Major Findings

FIMS

SRI reported the following principal observations for the application of FIMS to coal liquefaction materials. Many of the FIMS spectra showed distinct bimodal distributions. Because of this, a simplified data analysis scheme was applied in which the mass profiles were mathematically deconvoluted into two curves with maxima at about 350 and 600 Da. The areas under these curves were assigned the names "Component A" and "Component B", respectively. Components A and B were quantified and used in a simple conversion model for the assumed production and consumption routes of the components. Relative changes in Components A and B could be observed in relation to process parameters such as feed coal, sampling point, reaction conditions, and yield structure. The SRI researchers noted that changes in Components A and B were consistent with changes in resid conversion and retrogression, as observed in the process yields.

Specific chemical structures could be assigned to prominent peaks in the 240 to 320 Da range of the FIMS spectrum. The compounds identified are either tetra- to hexacondensed aromatic hydrocarbons, or naphthenoaromatic compounds that have no fully aromatic analog. Homologues of these compounds with molecular weights of up to 350 Da were observed. These structural assignments correspond closely to the compounds observed by Sullivan et al.²⁵ in hydroprocessed petroleum vacuum gas oils. Sullivan et al. implicated these compounds in decreased reactivity toward conversion, and increased coking and catalyst deactivation. SRI found the highest average concentration of these compounds in the resids from Wilsonville Run 259 (Pittsburgh seam coal), intermediate concentrations in the resids from Wilsonville Runs 257 (Ill. 6 coal) and 255 (Texas lignite), and the lowest concentrations in the resids from Wilsonville Runs 251-II (Wyodak coal) and 250 (Ill. 6 coal). In light of the work of Sullivan et al., the fact that the resids with the lowest apparent

reactivity toward conversion (Run 259) contained the highest concentration of these compounds appears to be a significant finding regarding resid reactivity. SRI speculates that it is probably condensed aromatic structures such as these, not oxygenated structures, which are responsible for retrogressive reactions in highly processed coal liquefaction resids.

Derivatization

In an effort to quantify the oxygen bound to alkyl carbon in coal liquefaction resids, researchers at SRI used a derivatization technique which employs iodotrimethylsilane in an organic solvent. The extent of reaction of the iodosilane reagent with the resid is determined by measuring the amount of unreacted iodide in solution. Although the solvent of choice (acetonitrile) is a poor solvent for the resid, good solvents (e.g., pyridine, tetrahydrofuran) interfere with the iodotrimethylsilane reagent; therefore, chloroform, which is a moderately good solvent, was used. An attempt to use an ion-selective electrode to quantify the amount of iodide ion produced from unconverted iodotrimethylsilane was unsuccessful; ion-exchange chromatography was used instead. Unexpected background reactions with the chloroform were responsible for about a 10% loss of iodide ion in the analysis. Analysis of the data corrected for the 10% loss shows that less than approximately 20% of the total oxygen in the resids is bound to aliphatic carbon. Though this is not a precisely determined result, it is consistent with the known phenolic oxygen contents of these materials, which are about 50 to 75% of the total oxygen. Accuracy and precision of the method employed would need to be improved to improve the utility of the method. SRI notes that further development of this method should not be a high priority.

CONSOL Evaluation

The FIMS technique was shown to be potentially useful for the analysis of direct coal liquefaction resid samples in support of process development. The FIMS profile consists of a broad distribution of molecular weights ranging from 200 to 1000 Da. In many cases, the spectra had a

distinctly bimodal distribution. The novel use of a simplifying two-component model to handle the complex FIMS profiles proved to be highly effective. The two pseudocomponents, centered at about 350 and 600 Da, were quantified by use of a non-linear regression routine that fitted an expression to the general forms of the peaks. Fitting parameters were derived from a few sample spectra. Although the function chosen may not provide the best fit for these data, it was sufficiently good for interpretive purposes. Differences in the relative weight percent of these components for different samples could be attributed to changes in process parameters. This simple scheme holds great potential for process development application. Another possible application of these easily derived values is their use in sophisticated numerical models of coal liquefaction processes.

The structural identification of some molecular components in the 240 to 320 Da range may provide important information regarding the fundamental chemistry involved in resid reactivity and coal processing. It is considered highly likely that the concentration of these compounds is related to the degree of difficulty in hydrocracking/hydrotreating the resids examined.

The FIMS method relies on volatilizing the sample under high vacuum. Although the percent of volatiles closely matched the tetrahydrofuran (THF) solubility of the sample, it did not correspond to the total organic content of the sample. It is likely that the FIMS analyses performed here did not include the highest molecular weight, least soluble portion of the distillation resid. This will have to be considered in the application of the method. The capital investment for FIMS equipment is approximately \$250,000; cost for expendables is on the order of \$40 per sample. It requires one-half hour for sample preparation and approximately one to two hours of instrument time to analyze one sample. The computer time and cost for the mathematical deconvolution and curve fitting technique are trivial.

Quantitation of the aliphatic oxygen in resids by derivatization with an iodosilane reagent showed that typically less than 20% of the total

oxygen contained in these materials is bound to alkyl carbon atoms. Although the results obtained by this method are consistent with other available information, the accuracy and precision of the method are considered poor. The technique can not be considered rapid as applied here; i.e., with ion chromatographic, rather than ion-selective electrode, detection. The chromatographic method must be conducted by a skilled technician and it requires more manpower than the electrochemical technique originally attempted.

Further Development

There are a number of avenues for further development of the FIMS technique for analyzing coal liquefaction derived resids in support of process development. A better curve-fitting routine could be developed using a more sophisticated mathematical function. This may provide some further insight into the nuances of shifts in the molecular weight distributions attributable to processing conditions. Analyses of whole process stream samples, rather than of only resids, and evaluation of data on a mass-flow basis would aid in understanding the pseudocomponent reactions. Additional speciation of the compounds in the FIMS profile will provide a better picture of the fundamental chemistry of the coal-derived resids. Some attention should be given to better quantifying the completeness of volatilization of the samples.

Statement of Work

Field Ionization Mass Spectrometry (FIMS) is a technique which has been used for a variety of applications relevant to coal liquefaction. It has not, however, been demonstrated widely for its ability to answer questions pertaining to the chemistry of coal conversion. As such, it fits well within the scope of the participants program.

The application of FIMS to a reasonably large sample set (17 samples) will allow a demonstration of the value of this technique. These samples have been selected so that the utility of FIMS for addressing the issue

supplied to SRI with the following information, as available: elemental analyses, ash content, ash elemental analysis, phenolic -OH concentration, calorific value, hydrogen classes by $^1\text{H-NMR}$, resid reactivity data (calculated), and the full history of the sample (plant, process conditions, age, and storage conditions). All samples are non-distillable residual materials which may contain insoluble organic matter (IOM) and ash. Sample size will be at least 0.5 g. Most samples will be brittle pitch-like materials that will be supplied as approximately -8 mesh (2.4 mm) pieces.

The evolution of various compound types (for example, alkanes, phenols, dihydroxybenzenes, etc.) will be followed through the thermal program of the FIMS experiment. This FIMS profiling will be done for each sample. These data then will be used in a factor analysis for correlation of the FIMS data with other sample properties or attributes such as feed coal, operating conditions, chemical analyses, and resid reactivity.

The analysis of oxygen functional groups in coal-derived resids is of particular interest. A wet chemical technique in which trimethyl-iodosilane is used to derivatize the alkyl carbon-oxygen bond will be applied to resid-containing coal liquefaction oils. Alkyl carbon-oxygen bonds are quantified by measuring the reacted iodine. The reaction and analysis will be performed in pyridine solution. Six samples will be provided to SRI for derivatization. Four of these samples (those from Wilsonville) are whole oil composites comprised of samples taken over a large portion of a specific run. These materials may contain ash and THF insoluble organic material. The two samples from HRI are pressure filter liquids and as such contain only traces of insolubles. Each of these samples will be supplied with the following information: elemental analyses, ash content and ash elemental analysis (where appropriate), phenolic -OH concentration, calorific value, hydrogen classes by $^1\text{H-NMR}$, and the full history of the sample (plant, process conditions, age, and storage conditions). Sample size will be at least 5 g.

SRI Executive Summary

SRI International has analyzed a series of coal-derived residual oils by field ionization mass spectrometry (FIMS) and explored the feasibility of using iodotrimethylsilane as an ether-cleavage reagent for determining the amounts of aliphatic carbons bearing oxygen in these resids. The general objective of this work is to understand how coal characteristics and/or variations in process configuration impact resid reactivity and ultimately to determine the chemical and physical differences in these resids responsible for the reactivity differences.

The FIMS analysis of 15 resid samples, taken from three sampling points in five close-coupled two-stage liquefaction runs at the Wilsonville facility, shows the samples to be very similar in some respects. This similarity was expected since these resids are constrained to appear similar by their complexity (which usually gives similar intensities for nearby nominal masses), by identical distillation processes, and by changes in process parameters that are typically made to keep product quality and operability within acceptable limits. Nevertheless, FIMS analysis of the whole resids provided spectra showing significant differences, easily apparent to the eye, in the overall spectral profiles.

Because the spectral profiles appeared as if they resulted from the superposition of two curves, with intensities peaking at about 350 and 600 Da, we mathematically deconvoluted the profiles into lumped Components A and B, respectively, and assigned these components places in a simple lumped conversion model. We then proceeded to test whether the changes in the two components with sampling point, coal type, and process conditions made a picture that was self-consistent and bore any relationship to the changes in yield structure with changes in these same variables. This test showed that the correspondence was surprisingly good, given the complexities and the simplifying assumptions. That is, the changes in the percent of low-mass and high-mass components were consistent with the ease or difficulty of resid conversion and retrogression, as observed in the yield structures.

In addition to differences in the overall profiles, FIMS analysis of resids also showed substantial level of "structure" in the 240 to 350 Da range. This structure, seen as large ratios (5/1 or more) in the intensity of adjacent even masses, most certainly carries additional chemical information, but it requires great hubris to speculatively assign, without benefit of additional information, chemical structures to nominal masses in this range where the starting material was itself an unknown and exceedingly complex material. In view of this complexity, we were gratified to note that all of the prominent peaks in this range corresponded to PCAH species that have previously been identified by Sullivan and Boduszynski and co-workers in petroleum vacuum gas oils (VGO), and implicated in increased coking catalyst deactivation, and decreased process performance in VGO hydrotreatment. Thus, while phenolics and other oxygenated structures have been implicated as a primary candidates for the retrogressive reactions limiting the initial conversion of coals during liquefaction or pyrolysis, it is probably PDAH structures such as these that are responsible for coking in these heavily processed resids.

The use of iodotrimethylsilane to quantitate the oxygen bound to alkyl carbon in the resids yielded the finding that the levels of such oxygen are quite low, typically less than 20% of the total oxygen. A background reaction of the iodotrimethylsilane with the solvent chloroform limited the accuracy of the determinations for these low levels of alkyl-O structures, and would need to be suppressed if accuracy and precision are to be improved. The finding of low levels of cleavable oxygen compounds may also carry information about the abundance of another class of oxygen structures, benzylic phenols. Such structures are potentially important as retrograde intermediates in the thermal conversion of virtually any phenolic feedstock, but specific information on their presence would require additional pure compound studies. On balance, we judge, from the low levels of total oxygen in these resids, from the small percentage in alkyl ether (i.e., thermally labile) structures, and from the recognition of prominent PCAH components in the resids that are likely coke precursors, that future efforts in oxygen speciation via iodotrimethylsilation do not warrant first priority.

VIRGINIA POLYTECHNIC INSTITUTE AND STATE UNIVERSITY

Summary

This study was designed to demonstrate the use of two different methods for the separation of direct coal liquefaction process-derived materials into defined fractions. The two methods, liquid chromatography (LC) and supercritical fluid extraction (SFE), were employed to determine if the same or complementary information could be obtained by the two methods. The primary objective was to evaluate the potential of supplementing or replacing the conventional LC method with SFE and in so doing to exploit the advantages of SFE. A solvent density gradient can be employed in SFE in much the same way that a gradient of solvent strength or polarity is employed in LC. Alternatively, modifiers or co-solvents can be used in SFE to change the extraction properties of the primary solvent. Potential advantages of SFE over LC include: a relatively low amount of solvent is necessary to effect separation, SFE solvents are usually non-flammable and non-toxic, solvent disposal problems are minimized, separation is frequently faster.

Preparative-scale liquid chromatography was successful in separating the tetrahydrofuran (THF)-soluble resids into four fractions of differing polarity. Two of the fractions, originally believed to be the oxygen- and nitrogen-rich, were subsequently characterized by LC-FTIR. The LC method shows some potential usefulness for process development support. However, the time requirement for this method should be improved and the chemical fractionation should be better understood to improve the utility of the method.

Seven different extraction conditions were employed in the SFE fractionation of eighteen samples. The samples could only be minimally extracted (<16 wt %) at the conditions chosen. The low extract yields prevented the completion of planned LC-FTIR characterization of the extracts. The SFE method, as employed in this work, was not successful in effecting a selective separation of liquefaction resids into multiple fractions.

Still, SFE methods appear to hold potential for use as selective separation techniques. Further methods development work appears warranted.

Further development of these analytical methods will be required before their use as process development tools can be recommended.

Program Description

This report describes the work performed at Virginia Polytechnic Institute and State University (VPI) under a subcontract to CONSOL INC., Research and Development. CONSOL's prime contract to the U.S. Department of Energy (Contract No. DE-AC22-89PC89883, "Coal Liquefaction Process Streams Characterization and Evaluation") established a program for the analysis of direct coal liquefaction derived materials. The program involves a number of participating organizations whose analytical expertise is being applied to these materials. This Participants Program has two main objectives. The broad objective is to improve our understanding of fundamental coal liquefaction chemistry to facilitate process improvement and new process development. The specific approach to achieving this objective is to provide a bridge between direct coal liquefaction process development and analytical chemistry by demonstrating the application of various advanced analytical methods to coal liquefaction materials. The methodologies (or techniques) of interest are those which are novel in their application for the support of coal liquefaction and those which have not been fully demonstrated in this application. CONSOL is providing well-documented samples from different direct coal liquefaction development facilities to the program participants. The participants are required to interpret their analytical data in context to the processing conditions under which the samples were generated. The methodology employed is then evaluated for its usefulness in analyzing direct coal liquefaction derived materials.

Methodology

VPI applied preparative-scale liquid column chromatographic (LC) fractionation followed by normal-phase liquid chromatography-Fourier

transform infrared spectroscopy (LC-FTIR) analyses of the resulting fractions, and supercritical fluid extraction (SFE) to eighteen tetrahydrofuran (THF)-soluble portions of direct coal liquefaction distillation resid (850°F⁺). VPI also inspected the samples by infrared spectroscopy prior to conducting the separations.

The samples were produced at three different continuous coal liquefaction facilities: the Wilsonville pilot plant, the Hydrocarbon Research Inc. (HRI) bench unit, and the Lummus process development unit. The major processing parameters which were varied among the Wilsonville runs were feed coal, catalyst, ash recycle, and sampling location in the plant. Samples from Wilsonville were taken from two different locations in the plant. These samples are expected to represent different extents of coal liquefaction. Some of the Wilsonville samples were composites of samples taken over long periods of single runs; others were samples obtained from a single run day. The HRI samples were also obtained from different plant locations and thus represent material which has undergone different degrees of processing. HRI samples were chosen to compare materials produced with a raw feed coal and with a feed coal that had been thermally pretreated to reduce its oxygen content. The Lummus samples were representative of ashy and deashed recycle streams.

Major Findings

The following principal observations for the application of preparative-scale liquid column chromatography and LC-FTIR to coal liquefaction materials were reported by VPI.

Prior to separation, each sample was examined by diffuse reflectance infrared spectroscopy (DRIFT). Though the spectra showed the same basic features, significant differences were apparent in the O-H, N-H and C=O regions of the spectra. The presence of the carbonyl band in some of the samples may indicate that those samples (or their precursors) had become oxidized during storage or handling.

The samples were separated by preparative-scale liquid column chromatography on a silica gel column with four solvents (hexane, hexane/hl, m, acetonitrile, THF) into four fractions of increasing polarity. The relative quantities of the four fractions (F1, non-polars; F2, intermediate polars; F3, polars; F4, very polars) show some correspondence with feed coal, processing plant, and thermal treatment. In addition, a correlation can be observed between the phenolic -OH content of the samples (as measured by CONSOL) and the yield of fraction F4 (very polars), as shown in the following figure.

Phenolic -OH Concentration vs wt % Very Polar Fraction (F4), Corrected

NOTE: Numbers in Parentheses are sample numbers

Each of the four separated fractions from several samples was examined by DRIFT analysis. Increasing functionality was observed for progressive fractions. Analytical-scale LC-FTIR analyses were performed on Fractions 2 and 3 from each sample. Prior to this work, Fractions 2 and 3 were expected to be oxygen- and nitrogen-rich, respectively. The Fractions 2 prepared from all samples showed a near absence of O-H, C=O and ether bands; however, in some cases minor carbonyl bands were observed and some evidence for the presence of phenols was observed in the Wilsonville

samples. VPI concluded that, in retrospect, Fraction 2 apparently contained very low concentrations of oxygen-containing species. The Fractions 3 prepared from all samples showed no evidence of nitrogen-containing species; however, many of the spectra showed strong carbonyl bands and in some cases, phenolic or etheric bands.

Seven different experimental conditions were employed in the supercritical CO₂ extraction of eighteen THF-soluble distillation resids to examine the impact of those conditions on the yield of extractables. As expected, increasing the supercritical CO₂ density from 0.3 to 0.9 g/mL increased the yield of material extracted. However, the yield of extracted material was less than 10 wt% for all samples when pure CO₂ was the solvent. Methanol, toluene, and acetonitrile (1 to 4 wt %) were added to the supercritical CO₂ to modify the solvating power of the extracting fluid; surprisingly, extract yields were lower than with pure CO₂ in all but one case. VPI identified several limitations in the SFE experiments: the method for determining extract yield may have been biased low, extraction time was probably insufficient for the sample size used, some samples fused in the extraction vessel and probably had poor contact with the extracting fluid. The VPI team believe that these problems could be overcome with additional work. The low extract yields (<16 wt % in all cases) precluded the planned characterization of the extracts by LC-FTIR.

CONSOL Evaluation

The preparative-scale liquid chromatographic technique used in this study provides a separation of complex resids into four chemically distinct fractions. The fraction yields are correlatable to gross processing changes; thus, this method has some potential for use in process monitoring and development. This conclusion must be tempered because the chemical nature of the fractions is apparently strongly affected by the sample being analyzed. For example, Fractions 2 and 3 from these samples were chemically quite different from the respective fractions from samples analyzed earlier by VPI. The method is relatively inexpensive in terms of consumables (on the order of \$300/sample for supplies) and

can be executed by trained laboratory technicians; however, sample turn-around time is several days.

The LC-FTIR method can provide detailed chemical class information on complex mixtures. Unlike gas chromatography and mass spectrometry, it is applicable to non-volatile species. The cost of the LC equipment used in this study is about \$20,000. The FTIR detection can be done with any of a number of commercially available instruments which range in cost from \$50,000 to \$150,000.

The value of the SFE method for analysis of direct coal liquefaction materials cannot be evaluated from this study. The conditions tested were chosen on the basis of VPI's experience with other samples. In light of the uniformly low extraction yields obtained, it appears that the chosen conditions were far from optimum. This study was aimed at application of established techniques; it was not designed to accommodate development of methodology. Optimization of extraction conditions and further testing of SFE is recommended to discover if the method has a potential use for the support of direct coal liquefaction process development. The equipment cost for SFE is approximately \$50,000.

Further Development

There are a number of avenues for further development of the techniques described here. LC techniques have frequently been used to reduce complex mixtures, including coal liquids, into chemically analyzable fractions (for example the SESC²⁶ and the SARA²⁷ procedures). The simple four-fraction separation used in this study may be sufficient to observe changes in processing conditions or to provide fractions for further analysis that are chemically less complex than the original sample. A better understanding of the chemical nature of the fractions would improve the usefulness of the method. A reduction in analysis time would also make the preparatory-scale LC procedure used here more useful. It may be possible to perform the same preparative separation under pressure in a high performance liquid chromatography (HPLC) system, with a subsequent reduction in analysis time.

The LC-FTIR method, because of its ability to deal with non-volatile samples and its speed, shows potential usefulness as a characterization tool for process development. The 2-D LC/FTIR contour plots may contain more information relating to processing conditions than was detailed in this scoping study. Possible on-line application of this method is indicated in this study; this aspect requires further study.

Supercritical fluid extraction of coal liquefaction process materials will require additional development before the technique has practical application. A multi-dimensional study of solvent/modifier/pressure/temperature/time would be required to establish appropriate analytical conditions.

Statement of Work

The analysis of coal liquefaction process streams for heteroatomic species, particularly oxygen- and nitrogen-containing compounds, is of particular importance. The nitrogen-containing compounds are poisons for downstream refining catalysts. The oxygen compounds appear to be important in retrogressive reactions in the conversion process. In order to obtain a better understanding of the species present in relation to process performance, VPI will use liquid chromatography (LC) and supercritical fluid extraction (SFE) to separate a number of coal liquefaction-derived resids into fractions. These fractions then will be analyzed to determine oxygen- and nitrogen-containing species. The fractions generated by LC will be analyzed by Fourier transform infrared (FTIR) spectroscopy. The fractions generated by SFE will be further fractionated using supercritical fluid chromatography (SFC) coupled to appropriate detectors inclusive of FTIR, nitrogen chemiluminescence, or nitrogen-phosphorous (NPD) for analysis.

Liquid chromatography will be performed on eight samples. This method will yield well-defined classes of compounds. However, the tetrahydrofuran (THF) soluble resids will first be separated on a preparatory-scale into fractions of varying polarity (as described in Ametis, P. G. and L. T. Taylor, *Chromatographia* 1984, 18(4), pp. 175-

182). Supercritical fluid extraction (SFE) will be employed on the unfractionated sample as a comparative method for the separation and characterization of the THF soluble resids. The technique of supercritical fluid extraction (SFE) will be used to separate the materials into multiple fractions so as to be comparable to the LC fractions. Multiple fractions will be generated in three ways. The first method will be by using a density gradient of the extracting fluid; twelve samples will be separated. The second and third methods involve the use of modifiers which are added to the bulk solvent to vary its selectivity. In the second method, modifiers will be used to generate multiple fractions by varying the concentration of a single modifier in the bulk solvent as the experiment proceeds. The third method will be to change the modifier and, therefore, the extraction power of the supercritical fluid at designated points in the extraction.

The LC-FTIR method and the SFE-SFC method are not applicable to solids-containing samples and, therefore, a sample set has been selected which contains only the tetrahydrofuran (THF) soluble portion of distillation resids from different process streams. CONSOL will supply to VPI eighteen THF-soluble resid samples. These samples will be supplied with the following information (as available): elemental analyses, phenolic - OH concentration, calorific value, hydrogen classes by $^1\text{H-NMR}$, and the full history of the sample (plant, process conditions, age, and storage conditions). At least 20 g of each sample will be supplied. Replicate analyses will be performed as appropriate to define precision.

VPI Executive Summary

In January 1991, Virginia Polytechnic Institute and State University began the analysis of coal liquefaction process products under a subcontract from CONSOL INC. The prime contractor for this effort has been the U.S. Department of Energy (Contract No. DE-AC22-89PC89883). The goals of the overall project were to identify promising analytical methodologies for supporting direct coal liquefaction process development and to demonstrate their application to well-documented samples obtained from process development units. This report provides a description of

the analytical techniques employed at Virginia Polytechnic Institute and State University, their application to a discrete set of eighteen tetrahydrofuran (THF) soluble resid products, an interpretation of the results in the context of the liquefaction process and an evaluation of the chosen methodologies with regard to liquefaction process understanding and development.

To attain the goals previously mentioned, a set of six specific task objectives (5 experimental, 1 report) was proposed. Briefly, the five experimental objectives involved the application of preparative scale column fractionation, normal phase LC/FT-IR and quantitative supercritical fluid extraction for the characterization of the THF-soluble process stream resids. As these methods currently are underutilized, the intent of these objectives was to fully exploit their application concerning liquefaction products and to evaluate their usefulness for further process development.

Preparative scale column fractionation was applied to eight resid specimens. Elution of approximately 5 grams of each resid with hexane/chloroform (80/20) and chloroform/acetonitrile (90/10) gave rise to what we believed to be an oxygen enriched (~20%) and a nitrogen enriched (~40%) fraction. These two fractions then were characterized via LC/FT-IR as developed by Amateis et al. The study revealed predominantly hydrocarbon content for both fractions, although phenolics, carbonyls and, in several cases, ethers were observed. More specifically, the suspected oxygen-enriched fraction (No. 2) proved to be mostly hydrocarbon and to a lesser degree phenolic in character. The suspected nitrogen-enriched fraction (No. 3) turned out to contain an abundance of carbonyl and ether components as no infrared absorbances due to nitrogen were observed. Our inability to preliminarily "fine-tune" both the preparative step and the spectrometric parameters employed in order to compensate for the unknown samples agreed to for investigation was a serious impediment to the overall quality of the data obtained. For example dissimilarities in chromatographic column packing, column dimensions and infrared flow cell geometry had a considerable impact upon the quality of the information yielded here. In spite of these

difficulties, infrared appears to have excellent potential for readily assessing carbonyl and ether heteroatoms in coal-derived products. Phenolics were not as quickly detected due to either their lower abundance and/or their lower infrared absorbing capacity.

Rather than chromatographically separate resids by perceived differences in polarity, four resids in another study were evaluated for extractability with supercritical fluids under eight different conditions. The SFE conditions differed in terms of CO₂ fluid density, modifier type (methanol, toluene, etc.), and percent modifier content 1-4% in the supercritical fluid. The arbitrarily chosen extraction parameters (i.e., not optimized) yielded small amounts of extractables in each resid. The amounts were relatively low, probably because of limited mass transfer and non-exhaustive extraction procedures. Since the LC/FT-IR protocol chosen for this work was analytical scale, the small quantity of extractables (which differ in solubility) precluded our applying the LC/FT-IR methodology to these solubility fractions. Employing what at the time were our "best" perceived extraction conditions, seven THF-soluble resids yielded again only a small amount of extractable material. Sufficient data were obtained, however, to indicate the future success of this approach. Again, LC/FT-IR of these fractions employing an analytical-scale column was precluded. In spite of our inability to perform LC/FT-IR on supercritical fluid extracted fractions, this six-month project yielded a staggering amount of data and little extra time to reflect upon the data's significance and impact.

A number of observations and recommendations can be made from this six-month project.

1. The budget did not allow us to utilize an optimized analytical-scale LC/FT-IR system since our work with coal-derived products ceased in 1987 due to the lack of DOE funding.
2. Miniaturization of LC/FT-IR would enable smaller size samples to be studied and would consume much less organic solvents.
3. The number of tasks and samples were too large and gave rise to insufficient time for data interpretation.

4. Both LC/FT-IR and SFE of unknown samples require a certain amount of optimization time. The amount of work to perform an analysis on one sample is not too different from the amount of work necessary for ten samples. The ten-fold increase in data, however, requires considerably more time for interpretation.
5. The issue of repeatability could not be addressed because of the large sample load. For example, Task I generated 32 fractions and Task II gave rise to 16 LC/FT-IR runs, each of which generated at least 100 spectra for interpretation.
6. Supercritical fluid extraction should be seriously examined in this type of study because of the tremendous volume of organic solvent used, especially in the preparative separation task (i.e., 3 liters per fraction generated). Solvent disposal costs and environmental concerns are major disadvantages to traditional coal fractionation procedures.
7. Closer inspection of each LC/FT-IR fraction in terms of computer spectral (solution phase) library searching and compound modeling would have yielded more specific information.
8. Infrared analysis of coal resid fractions on-line with chromatography affords unique chemical class information that is readily interpretable with minimal training. For example, the presence of carbonylic material is immediately obvious without extensive data manipulation and no chemical derivatization.
9. Both SFE and FT-IR are readily quantifiable and are most amenable to non-volatile species, in contrast to gas chromatography and mass spectrometry.
10. A study should be commissioned to determine if LC/FT-IR can ascertain differences in processing with the same raw coal. The samples agreed to for study compared mostly differences in coal origin.

PARTICIPANTS PROGRAM - INTERIM ASSESSMENT

SUMMARY

An assessment is given here of the first phase (Phase I) of the Participants Program. Major findings of the research groups in Phase I of the program are detailed. Recommendations are made for the future direction of the program in Phase II. This interim assessment concludes that the program, to date, has been successful in achieving program goals.

INTRODUCTION

The Participants Program is broadly based on achieving two main objectives. They are 1) the advancement of a basic understanding of the chemistry inherent in direct coal liquefaction, and 2) an attempt to bring about a concerted effort between process developers and analytical chemists for the advancement of direct coal liquefaction process development. These objectives are being met by supplying a number of analytical research groups with well documented process-derived samples from several direct coal liquefaction facilities. The choice of methodology employed and the choice of samples for analysis was made in collaboration with each research group. The results obtained by each group were interpreted by the respective research group, with CONSOL's help, in the context of the liquefaction process from which the samples were derived.

The following assessment is made at an interim point in the Participants Program when all Phase I contracts have been completed and Phase II is beginning. Inclusive in this assessment is a summary of the program structure and status of the program. Eight participating research groups (comprising Phase I of the program) have completed their efforts and have submitted final reports to CONSOL for evaluation. A description of the major findings of the participating groups is given here. The future direction of the program is also described.

PROGRAM ORGANIZATION

The Participants Program was divided into four sequential parts. In the first part, an assessment was made of analytical needs for process development and available, although not necessarily developed, analytical technology to address those needs. This assessment took the form of a document which issued as a Topical Report under this contract.²⁸ In the second part of the Participants Program (Phase I), eight organizations were placed under subcontract to analyze well documented direct coal liquefaction samples utilizing analytical techniques which are novel in their application to these materials. The third part of the program, which occurs at the conclusion of Phase I, is the drafting of an interim evaluation (or assessment) of the program. This assessment will be based on the performance of the Participants Program at that point, and may result in the redirection of effort of certain team members from Phase I, or the addition of new team members. Thus, the fourth part of the program (Phase II) will be directed by the results by this assessment.

PHASE I

Chronology

This contract was initiated in September 1989. In January of 1990, requests for research proposals were sent to a number of potential teaming members. Replies were received by March 1990. Site visits were then made to the proposers' facilities to make arrangements for cooperative work and to receive input for the Analytical Needs Assessment.²⁸ In a number of cases, discussions held with the proposer at his site produced an expanded or completely different direction for research than that which had been originally proposed. All site visits were completed by July 1990. Trip reports were written for each site visit and reviewed by the proposers for accuracy. Based on the proposal, the trip report, and the Analytical Needs Assessment, statements of work were written for each potential participant. All subcontracts with participants were in place by March 1991.

At the conclusion of each subcontract a draft final report was received from the participant. The drafts were revised by the participants, in consultation with CONSOL. An evaluation of the technical merit of each analytical method employed was made in each case by CONSOL. The CONSOL evaluation and the respective final report were combined and issued as a Topical Report under this contract.²⁹⁻³⁵ The participating research groups, the principal investigator, the duration of the contract, and the methods employed by each research group in Phase I of the program are given in Table 29.

One of the eight groups listed in Table 29 is Conoco Petroleum Products Research Division. Conoco's activity in the Participants Program was to evaluate crude oils produced at the Wilsonville Advanced Two-Stage Coal Liquefaction Facility. Reporting of the Conoco work was handled differently than the other seven participants. A topical report was not issued; rather, the final reports from Conoco and CONSOL evaluations of the work were included in Quarterly Technical Progress Reports of the Prime contract.^{12,13}

Status

Eight research projects under Phase I of the Participants Program are complete. Each participant's final report was submitted. The CONSOL evaluation of the technical merit of each research tool employed, for use as an aid for process development, was written, included with the participants final report, and issued as a topical report.

TECHNICAL EVALUATION

In Phase I of the Participants Program, analytical techniques were chosen that, although not necessarily new, were novel in that their use for the analysis of well-documented coal liquefaction process derived materials had not been fully demonstrated. A total of fifteen analytical techniques, exclusive of the petroleum inspection tests performed by Conoco, were employed (see Table 29). In most cases, the application of these techniques proved to be useful in that, not only were data collectable

for these materials, but the collected data could be related to the process conditions under which the samples had been generated.

Technical evaluations of each project were made and included as part of the each subcontractor's final report. These final reports were issued as individual technical reports (except for the Conoco report, see above).²⁹⁻³⁵ A brief synopsis of the major technical findings derived from each subcontract follows:

SUBCONTRACTOR'S MAJOR FINDINGS	
Phase I	
ORGANIZATION/METHOD	MAJOR FINDINGS
University of Kentucky/CAER Fluorescence Microscopy	<ol style="list-style-type: none"> 1. Distinct variations in samples can be discerned 2. Solid, heterogeneous samples can be examined 3. Can infer the degree of upgrading and relative resid reactivity from analytical data
Conoco Crude Oil Assay	<ol style="list-style-type: none"> 1. Crudes are aromatic, low sulfur, free of metals 2. Naphthas are good refining feedstocks 3. Oxygen is the principal heteroatom in all fractions 4. A few problems were encountered in applying petroleum tests to coal liquids
Western Research Institute ¹ H- and ¹³ C-NMR	<ol style="list-style-type: none"> 1. Aromatic H/C ratios can be determined 2. Can determine the degree of saturation of aromatic rings 3. Can determine the modes of hydrogen utilization in the liquefaction process 4. Provides data useful for a pseudo-component lumped kinetic model
The Pennsylvania State University Carbonization and Reflectance Microscopy	<ol style="list-style-type: none"> 1. Pyridine insolubles produced in carbonization could be correlated with processing variables 2. Sampling inhomogeneous samples was difficult - poor reproducibility could, in part, be attributed to ash and IOM in samples 3. Petrographic analyses can be related to processing conditions
SRI International FIMS and Iodosilane Oxygen Derivatization	<ol style="list-style-type: none"> 1. Molecular weight profiles of distillation resids can be determined; Mathematical deconvolution of FIMS profiles proved to be an effective means to assess process variables 2. High molecular weight components of resids can be speciated; Fundamental chemistry can be determined 3. Total volatility of samples should be considered in future use of method 4. The oxygen derivatization technique was not recommended as a useful method for process development
Virginia Polytechnic Institute Liquid Chromatography, LC-FTIR, Supercritical Fluid Extraction	<ol style="list-style-type: none"> 1. Liquid chromatography can separate process materials into defined classes whose relative concentrations can be related to process conditions 2. LC-FTIR can be used to characterize different compound classes in the chemically complex mixtures 3. Supercritical fluid extraction, as an analytical technique for process derived materials, requires considerable developmental work before it can be considered useful

SUBCONTRACTOR'S MAJOR FINDINGS	
Phase I	
ORGANIZATION/METHOD	MAJOR FINDINGS
Advanced Fuel Research Quantitative FTIR and TG-FTIR	<ol style="list-style-type: none"> 1. A single FTIR analysis, used in place of multiple conventional analytical techniques provides numerous sample properties, but with reduced accuracy. 2. TG-FTIR can monitor changes in chemical structure, by analysis of pyrolytically-produced volatiles from each sample. 3. The utility of FTIR as an on-line analytical technique requires demonstration before it can be recommended for process application.
National Institute for Petroleum and Energy Research Separation Methods	<ol style="list-style-type: none"> 1. Non-aqueous ion exchange chromatography can separate process materials into well-defined acid, base, and neutral fractions with quantitative recovery. 2. The fractions are amenable to further characterization 3. Coal-derived resids contain much stronger acidic components than petroleum resids.

PROGRAM DIRECTION - RECOMMENDATIONS

The overall system established to make teaming arrangements in Phase I proved to be efficient and effective. It is recommended that this system be continued in putting together a team of researchers for Phase II.

Techniques used in Phase I of the Participants Program were novel, in that their application to well documented coal liquefaction process derived materials had not been fully explored. In setting up Phase II of the program, it is recommended that additional analytical techniques should be used which are more on the "cutting edge" of technology. In a continuing effort to address the needs of process development as detailed in the Analytical Needs Assessment, Phase II of the program will emphasize research on the high-boiling resid materials derived from process streams, the heteroatomic species present in the process streams, and process catalysts.

Due to time and budgetary constraints, Phase II projects will be more limited in duration and costs than Phase I projects. One consequence of this may be to limit the number of samples for examination by any one research group. It is likely that the number of subcontracts in Phase II will be similar to Phase I; however, because of the expected small

value of each contract, interest in participation in the program is anticipated to be highest among academic research groups.

Section 3

EXPERIMENTAL

Experimental details are described, where appropriate, in the Discussion section of this report. Details of the other analytical techniques used in this work were reported previously.^{9,10}

Section 4

REFERENCES

1. Southern Clean Fuels, Wilsonville Advanced Coal Liquefaction R&D Facility, Handouts from Technical Meeting No. 109 (March 20-21, 1991), No. 110 (May 8-9, 1991), and No. 111 (July 17-18, 1991).
2. D. C. Cronauer (Amoco), phone conversation with G. A. Robbins (CONSOL), December 19, 1991.
3. Winschel, R. A.; Robbins, G. A.; Burke, F. P. "Coal Liquefaction Process Solvent Characterization and Evaluation, Technical Progress Report, July 1 through September 30, 1988", DOE/PC 70018-68, July 1989.
4. Robbins, G. A.; Brandes, S. D.; Winschel, R. A.; Burke, F. P. "Coal Liquefaction Process Streams Characterization and Evaluation, Quarterly Technical Progress Report, April 1 through June 30, 1990", DOE/PC 89883-22, July 1991.
5. Southern Clean Fuels, Wilsonville Advanced Coal Liquefaction R&D Facility, Handouts from Technical Meeting No. 103 (March 14, 1990).
6. Robbins, G. A.; Winschel, R. A.; Burke, F. P. "Coal Liquefaction Process Solvent Characterization and Evaluation, Technical Progress Report, July 1 through September 30, 1987", DOE/PC 70018-59, March 1989.
7. Burke, F. P.; Winschel, R. A.; Robbins, G. A. "Coal Liquefaction Process Solvent Characterization and Evaluation - Final Report", DOE/PC 70018-70, September 1989.
8. Adapted from various handouts from Wilsonville Technical Review Meetings.
9. Burke, F. P.; Winschel, R. A.; Robbins, G. A. "Recycle Slurry Oil Characterization Final Report - October 1980 through March 1985", DOE/PC 30027-61, March 1985.
10. Winschel, R. A.; Robbins, G. A.; Burke, F. P. "Coal Liquefaction Process Solvent Characterization and Evaluation, Technical Progress Report, July 1 through September 30, 1985", DOE/PC 70018-13, December 1985.
11. Winschel, R. A.; Robbins, G. A.; Burke, F. P. "Coal Liquefaction Process Solvent Characterization and Evaluation, Technical Progress Report, January 1 through March 31, 1988", DOE/PC 70018-62, March 1989.
12. R. A. Winschel; Brandes, S. D.; Robbins, G. A.; Burke, F. P. "Coal Liquefaction Process Streams Characterization and Evaluation,

Quarterly Technical Progress Report, July 1 through September 30, 1991", DOE/PC 89883-34, November 1991.

13. Brandes, S. D.; Winschel, R. A.; Robbins, G. A.; Burke, F. P. "Coal Liquefaction Process Streams Characterization and Evaluation, Quarterly Technical Progress Report, October 1 through December 31, 1990", DOE/PC 89883-24, June 1991.
14. Brandes, S. D.; Winschel, R. A.; Burke, F. P.; Robbins, G. A. "Coal Liquefaction Process Streams Characterization and Evaluation, Quarterly Technical Progress Report, January 1 through March 31, 1991", DOE/PC 89883-27, September 1991.
15. Zhou, P; Rao, S. N. "Assessment of Coal Liquids as Refinery Feedstocks (Interim Report)", November 1990, DOE Contract DE-AC22-89PC88400, in preparation.
16. Nelson, W. L. *Petroleum Refinery Engineering*, Fourth Ed.; McGraw-Hill: New York, 1958; Chapter 10.
17. Robbins, G. A.; Brandes, S. D.; Winschel, R. A.; Burke, F. P. "Coal Liquefaction Process Streams Characterization and Evaluation, Quarterly Technical Progress Report, April 1 through June 30, 1991", DOE/PC 89883-29, November 1991.
18. Erwin, J.; Sefer, N. R.; Glavincevski, B. "Production and Analysis of EDS Coal-Derived Middle Distillate Test Fuels from Hydrogenation at Three Levels of Severity", SAE Int. Fuels and Lubricants Meeting, Paper 872038, November 1987.
19. C. Cantrell (SEI) phone conversation with G. Robbins (CONSOL), October 21, 1991.
20. Wu, M. M.; Robbins, G. A.; Winschel, R. A.; Burke, F. P. *Energy & Fuels* 1988, 2, 150-157.
21. Huffman, G. P.; Huggins, F. E.; Dunmyre, G. P.; Pignoco, A. J.; Lin, M.-C. *Fuel* 1985, 64, 847-856.
22. Lowenhaupt, D. E.; Gray, R. J. *Int. J. Coal Geol.* 1983, 1, 63-73.
23. Finseth, D. H.; Cillo, D. L.; Sprecher, R. F.; Retcofsky, H. L.; Lett, R. G. *Fuel* 1985, 64, 1718.
24. Chen, J. M.; Schindler, H. D.; *Ind. Eng. Chem. Res.* 1987, 26, 921.
25. Sullivan, R. F.; Boduszynski, M. M.; Fetzer, J. C. *Energy & Fuels* 1989, 3, 603.
26. Farcasiu, M. "Fractionation and Structural Characterization of Coal Liquids", *Fuel* 1977, 57, 47.
27. Given, P. H.; Cronauer, D. C.; Spakman, W.; Lovell, H. L.; Davis, A.; Biswas, B. *Fuel* 1975, 54, 34.

28. Brandes, S. D.; Robbins, G. A.; Winschel, R. A.; Burke, F. P. "Coal Liquefaction Process Streams Characterization and Evaluation, Analytical Needs Assessment Topical Report", DOE/PC 898883-18, March 1991.
29. Rathbone, R. F.; Hower, J. C.; Derbyshire, F. J. "Coal Liquefaction Process Streams Characterization and Evaluation, Novel Analytical Techniques for Coal Liquefaction: Fluorescence Microscopy, Topical Report", DOE/PC 89883-30, October 1991.
30. Miknis, F. P. "Coal Liquefaction Process Streams Characterization and Evaluation, Solid-State NMR Characterization of Coal Liquefaction Products, Topical Report", DOE/PC 89883-36, November 1991.
31. Mitchell, G.; Davis, A. "Coal Liquefaction Process Streams Characterization and Evaluation, Gold Tube Carbonization and Reflectance Microscopy, Topical Report, DOE/PC 89883-37, December 1991.
32. Malhotra, R.; McMillen, D.F. "Coal Liquefaction Process Streams Characterization and Evaluation, Characterization of Coal Liquids by Field Ionization Mass Spectrometry and Iodotrimethylsilane Derivatization, Topical Report", DOE/PC 89883-39, January 1992.
33. Taylor, L.T.; Hellgeth, J.W.; Sequeira, A. "Coal Liquefaction Process Streams Characterization and Evaluation, Analysis of Coal Liquefaction Process Streams by Chromatographic and Spectroscopic Techniques, Topical Report", DOE/PC 89883-41, January 1992.
34. M. A. Serio, M. A.; Teng, H.; Bassilakis, R.; Solomon, P. R. "Coal Liquefaction Process Streams Characterization and Evaluation, FT-IR Methods for Characterization of Coal Liquefaction Products, Topical Report", in preparation.
35. Green, J. B.; Pearson, C. D.; Young, L. L.; Green, J. A. "Coal Liquefaction Process Streams Characterization and Evaluation, Analysis of Coal Liquefaction Process Oils by Nonaqueous Ion Exchange Liquid Chromatography, Topical Report", in preparation.

TABLE 1
OPERATING CONDITIONS AND YIELDS FOR MATERIAL BALANCE PERIODS
Wilsonville Run 261

Operating Period Date, 1991 Operational Days	261A, Transitional 1/29-2/2 16-20	261B 2/11-15 24-28	261C 3/7-11 40-44	261D 3/14-18 47-51
<u>Coal</u>				
Feed rate, MF lb/hr	543.0	547.9	420.0	423.0
Ash, wt % MF	12.2	12.1	11.2	11.8
Conc. in slurry, wt % MF	33.0	32.9	32.8	31.9
<u>Process Solvent, wt %</u>				
Resid	32.7	38.3	38.3	48.4
Cl	12.0	12.1	11.8	11.9
<u>First Stage</u>				
Reaction temp., °F (avg)	790	789	790	791
Inlet H ₂ partial pressure, psia	2611 ±20	2610 ±23	2643 ±14	2656 ±22
Total gas flow, scfh	5390	5760	5080	5285
Recycle gas, scfh	800	1040	710	880
Space vel., lb feed/hr/lb cat	6.3	8.4	5.0	5.0
Space vel., lb MF coal/hr/ft ³ cat	66.4	66.9	51.3	51.7
Catalyst type	EXP-AO-60	EXP-AO-60	EXP-AO-60	EXP-AO-60
Catalyst age, lb (res+Cl)/lb cat	1328 ±74	1324 ±55	2537 ±120	2812 ±45
lb MF coal/lb cat	680 ±35	671 ±28	1256 ±53	1375 ±20
Cat replacement rate, lb/ton MF coal	3.0 (a)	3.0	0	1.5
<u>Second Stage</u>				
Reaction temp., °F (avg)	810	808	809	809
Inlet H ₂ partial pressure, psia	2479 ±13	2515 ±27	2478 ±16	2472 ±7
Total gas flow, scfh	4860	4650	4400	4140
Recycle gas, scfh	1610	1640	2210	1930
Space vel., lb feed/hr/lb cat	5.9	6.0	4.6	4.6
Space vel., lb MF coal/hr/ft ³ cat	66.4	66.9	51.3	51.7
Catalyst type	EXP-AO-60	EXP-AO-60	EXP-AO-60	EXP-AO-60
Catalyst age, lb (res+Cl)/lb cat	1128 ±117	1090 ±46	2067 ±97	2238 ±35
lb MF coal/lb cat	723 ±78	689 ±30	1269 ±53	1360 ±20
Cat replacement rate, lb/ton MF coal	3.0 (a)	3.0	0	1.5
ROSE-SR SM DAS type	2414	2394	2514	2544
<u>Yield, wt % MAF coal</u>				
H ₂	-5.4 ±0.4	-5.7 ±0.2	-6.1 ±0.3	-6.0 ±0.2
Water	7.7 ±0.7	8.3 ±1.5	9.1 ±0.5	9.7 ±0.5
H ₂ S	3.5 ±0.5	3.6 ±0.5	3.4 ±0.1	3.3 ±0.1
CO, CO ₂	0.4 ±0.1	0.3 ±0.1	0.6 ±0.4	0.4 ±0.1
NH ₃	1.3 ±0.1	1.4 ±0.1	1.3 ±0.1	1.5 ±0.4
C ₁ -C ₃ gas	5.4 ±0.5	5.1 ±0.6	6.0 ±0.4	6.5 ±0.7
C ₄ + distillate	59.0 ±0.5	64.4 ±2.6	64.8 ±3.8	65.6 ±1.6
C ₄ -C ₆	2.7 ±0.2	2.4 ±0.5	2.6 ±0.3	2.4 ±0.2
IBP-350°F	13.4 ±0.2	13.2 ±0.5	14.9 ±0.6	18.9 ±5.5
350-450°F	7.4 ±0.4	7.4 ±0.5	8.2 ±0.1	9.2 ±1.2
450-650°F	32.9 ±3.8	37.0 ±2.2	36.8 ±2.0	33.6 ±7.3
650-850°F	9.7 ±2.2	11.6 ±2.0	11.7 ±6.2	9.5 ±5.0
850-EP	-7.2 ±3.8 (c)	-7.2 ±3.0 (c)	-9.3 ±8.9 (c)	-8.0 ±4.2
Resid (b)	7.4 ±2.8	4.7 ±3.3	5.1 ±1.6	3.7 ±2.6
Solid Product (ash-free)	20.9 ±1.0	17.9 ±1.4	15.8 ±1.6	15.3 ±0.7
<u>H₂ efficiency</u>				
lb C ₄ + dist/lb H ₂ consumed	10.9 ±0.7	11.3 ±0.4	10.6 ±0.3	10.9 ±0.3
<u>C₁-C₃ selectivity</u>				
to C ₄ + distillate	9.2 ±0.8	7.9 ±0.7	9.2 ±0.9	9.8 ±0.9
<u>Coal conversion, wt % MAF</u>				
1st stage	84.5 ±1.7	87.0 ±1.0	89.7 ±0.5	90.5 ±0.8
1st and 2nd stages	91.1 ±0.9	92.4 ±0.2	93.8 ±0.2	93.9 ±0.3
Overall TSL	91.1 ±0.5	91.7 ±0.7	93.6 ±0.4	93.0 ±0.2
<u>Resid + UC conversion, wt % feed</u>				
1st stage	24.3 ±1.0	21.9 ±1.0	23.7 ±1.3	22.9 ±0.8
2nd stage	17.2 ±2.6	20.7 ±1.3	20.0 ±0.9	17.3 ±1.2
<u>Resid + UC conversion, wt % feed</u>				
1st stage	45.8 ±2.8	43.8 ±2.1	46.8 ±3.2	50.4 ±1.7
2nd stage	25.8 ±2.1	33.7 ±2.0	32.3 ±1.5	30.8 ±2.4
Overall	71.7 ±2.3	77.5 ±2.2	79.1 ±3.2	81.2 ±2.6

(a) Started 2/1/91 in first stage, 2/2/91 in second stage; (b) includes UC accumulation; (c) negative 850-EP may be due to seal oil conversion, solvent generation in ROSE unit, etc.; * not adjusted for H from separator; **estimated

TABLE 1 (Continued)

OPERATING CONDITIONS AND YIELDS FOR MATERIAL BALANCE PERIODS
Wilsonville Run 261

Operating Period Date, 1991 Operational Days	261E 4/20, 23-26 59, 62-65	261F, Unstable 5/17-21 84-88	261G, Transitional 5/24-27 91-94 (Resid Injection)
<u>Coal</u>			
Feed rate, MF lb/hr	494.3	359.1	357.0
Ash, wt % MF	11.6	11.8	11.5
Conc. in slurry, wt % MF	33.0	29.7	28.8
<u>Process Solvent, wt %</u>			
Resid	48.9	48.9	47.4
Cl	12.0	11.8	11.4
<u>First Stage</u>			
Reaction temp., °F (avg)	809	809	809
Inlet H ₂ partial pressure, psia	2538 ±64	2624 ±8	2636 ±10
Total gas flow, scfh	5370	5518	5688
Recycle gas, scfh	830	1400	1353
Space vel., lb feed/hr/lb cat	3.5	2.9	3.0
Space vel., lb MF coal/hr/ft ³ cat	60.7	44.1	43.8
Catalyst type	Criterion 324	Criterion 324	Criterion 324
Catalyst age, lb (res+Cl)/lb cat	1345 ±31	1936 ±25	1966 ±24
lb MF coal/lb cat	660 ±14	885 ±10	884 ±10
Cat replacement rate, lb/ton MF coal	3.0	2.25	2.25
<u>Second Stage</u>			
Reaction temp., °F (avg)	824	800	800
Inlet H ₂ partial pressure, psia	2354 ±58	2444 ±15	2308 ±14
Total gas flow, scfh	5020	4455	4759
Recycle gas, scfh	1975	2476	2775
Space vel., lb feed/hr/lb cat	3.3	2.6	2.7
Space vel., lb MF coal/hr/ft ³ cat	60.7	44.1	43.8
Catalyst type	Criterion 324	Criterion 324	Criterion 324
Catalyst age, lb (res+Cl)/lb cat	1450 ±38	1800 ±22	1790 ±23
lb MF coal/lb cat	669 ±13	861 ±9	860 ±10
Cat replacement rate, lb/ton MF coal	3.0	2.25	2.25
<u>ROSE-SPSM DAS type</u>	2654	2684	2654
<u>Yield, wt % MAF coal</u>			
H ₂	-5.4 ±0.2	-6.0 ±0.2	-6.2 ±0.1
Water	9.7 ±0.5	9.8 ±1.1	9.0 ±1.1
H ₂ S	3.4 ±0.0	2.7 ±0.0	2.8 ±0.1
CO, CO ₂	0.6 ±0.1	0.5 ±0.1	0.5 ±0.0
NH ₃	1.3 ±0.2	1.0 ±0.1	1.3 ±0.2
C ₁ -C ₃ gas	7.7 ±0.5	7.7 ±0.2	7.6 ±0.3
C ₄ + distillate	60.6 ±2.8	58.4 ±2.0	64.3 ±2.6
C ₄ -C ₆	2.9 ±0.3	3.3 ±0.1	3.2 ±0.1
IBP-350°F	14.0 ±1.8	13.1 ±0.7	14.3 ±0.3
350-450°F	8.9 ±1.2	8.1 ±0.3	8.2 ±0.2
450-EP	34.8 ±3.0	33.8 ±2.0	38.5 ±2.0
Resid (a)	5.4 ±3.6	10.3 ±2.9	5.1 ±2.2
Solid Product (ash-free)	16.7 ±1.5	15.6 ±0.8	15.6 ±0.7
<u>H₂ efficiency</u>			
lb C ₄ + dist/lb H ₂ consumed	11.2 ±0.4	9.7 ±0.4	10.3 ±0.2
<u>C₁-C₃ selectivity</u>			
to C ₄ + distillate	12.7 ±0.6	13.2 ±0.5	11.8 ±0.4
<u>Coal conversion, wt % MAF</u>			
1st stage	92.4 ±0.6	92.2 ±0.7	92.0 ±0.7
1st and 2nd stages	93.9 ±0.3	93.7 ±0.1	93.7 ±0.5
Overall TSL	92.7 ±0.6	92.5 ±0.4	92.2 ±0.2
<u>Resid + UC conversion, wt % feed</u>			
1st stage	19.4 ±1.6	17.6 ±2.7	19.4 ±1.1
2nd stage	20.0 ±1.8	16.4 ±1.8	15.8 ±0.9
<u>Resid + UC conversion, wt % feed</u>			
1st stage	42.5 ±3.9	41.2 ±6.8	47.2 ±2.2
2nd stage	35.4 ±3.2	32.9 ±4.5	32.1 ±1.7
Overall	77.9 ±3.4	74.1 ±2.6	79.2 ±2.9

(a) includes UC accumulation

/ls

TABLE 2
COMPONENT DISTRIBUTION OF V-131B SAMPLES
Wilsonville Run 261

Sample Number	Period	wt % of Sample			
		850°F Distillate	THF-Soluble Resid	IOM	Ash
18384	A*	34.8	54.0	3.7	6.8
18676	B	28.7	60.9	3.1	6.3
19413	C	34.1	55.1	3.5	6.5
19478	D	16.9	70.2	3.8	8.0
21347	E	24.5	64.3	3.5	7.2
21899	F*	20.8	67.1	3.9	7.7
21957	G*	26.1	60.7	3.9	7.4

*Transitional or unstable period.

TABLE 3
COMPONENT DISTRIBUTION OF V-1067 SAMPLES
Wilsonville Run 261

Sample Number	Period	wt % of Sample			
		850°F Distillate	THF-Soluble Resid	IOM	Ash
18121	A*	31.8	50.4	6.1	10.9
18569	B	26.1	56.1	5.9	11.2
19414	C	29.6	52.1	6.2	11.2
19488	D	26.7	55.8	5.3	11.5
21390	E	22.6	60.2	5.4	11.2
21902	F*	25.2	58.4	5.2	10.7
21932	G*	26.6	58.1	4.9	9.8

*Transitional or unstable period.

/1s

TABLE 4
COMPONENT DISTRIBUTION OF R-1235 SAMPLES
Wilsonville Run 261

Sample Number	Period	wt % of Sample			
		850°F Distillate	THF-Soluble Resid	IOM	Ash
18148	A*	28.3	55.0	6.5	9.2
18572	B	30.1	52.8	6.7	9.4
19489	C	31.7	51.3	6.4	9.4
18572	D	26.0	57.7	5.9	9.9
21391	E	20.6	63.2	5.5	9.8
21900	F*	23.5	61.4	4.9	9.7
21933	G*	25.8	59.4	5.3	9.3

*Transitional or unstable period.

TABLE 5
SOLUBILITY FRACTIONATION OF V-131B SAMPLES
Wilsonville Run 261

Period	wt % of THF-Soluble Resid		
	Oils	Asphaltenes	Preasphaltenes
A*	69.7	15.8	14.4
B	75.9	16.3	7.8
C	68.5	19.1	12.3
D	67.7	20.5	11.8
E	67.2	21.4	11.4
F*	67.4	21.3	11.3
G*	68.1	21.0	10.9

*Transitional or unstable period.

/ls

TABLE 6

SOLUBILITY FRACTIONATION OF V-1067 SAMPLES
Wilsonville Run 261

Period	wt % of THF-Soluble Resid		
	Oils	Asphaltenes	Preasphaltenes
A*	63.0	19.1	17.8
B	73.1	15.7	11.1
C	64.4	19.8	15.8
D	65.4	21.3	13.3
E	65.7	20.5	13.7
F*	63.4	22.0	14.6
G*	68.2	20.7	11.2

*Transitional or unstable period.

TABLE 7

SOLUBILITY FRACTIONATION OF R-1235 SAMPLES
Wilsonville Run 261

Period	wt % of THF-Soluble Resid		
	Oils	Asphaltenes	Preasphaltenes
A*	60.6	15.4	24.0
B	62.8	15.2	22.0
C	54.4	19.3	26.3
D	57.7	21.1	21.2
E	57.9	21.2	20.8
F*	58.0	23.0	19.0
G*	60.7	21.1	18.2

*Transitional or unstable period

/ls

TABLE 8
PROTON DISTRIBUTION OF V-131B WHOLE SAMPLES
Wilsonville Run 261

Period	Proton Distribution, %						
	Cond Arom	Uncond Arom	Cyclic Alpha	Alkyl Alpha	Cyclic Beta	Alkyl Beta	Gamma
A*	16.0	4.4	15.6	8.5	16.8	24.4	14.3
B	17.0	3.9	16.2	8.4	17.8	23.1	13.6
C	18.8	3.5	17.3	8.4	17.2	22.3	12.4
D	21.2	4.0	17.7	8.4	16.2	20.9	11.5
E	29.1	4.2	16.7	9.2	14.3	17.3	9.2
F*	25.7	4.9	18.4	9.1	13.9	17.6	10.3
G*	24.6	4.2	18.7	9.2	14.9	18.3	10.1

*Transitional or unstable period.

TABLE 9
PROTON DISTRIBUTION OF V-1067 WHOLE SAMPLES
Wilsonville Run 261

Period	Proton Distribution, %						
	Cond Arom	Uncond Arom	Cyclic Alpha	Alkyl Alpha	Cyclic Beta	Alkyl Beta	Gamma
A*	17.1	4.1	16.1	8.6	17.0	23.3	13.8
B	17.4	3.1	17.8	8.8	18.3	22.3	12.2
C	18.0	4.0	17.5	8.6	17.6	22.0	12.3
D	20.4	4.3	17.9	9.0	16.5	20.3	11.5
E	22.7	4.9	19.0	9.4	13.8	16.3	8.9
F*	24.3	5.5	17.9	9.2	14.6	17.6	11.0
G*	22.1	6.6	16.6	9.4	14.7	18.4	12.3

*Transitional or unstable period.

/ls

TABLE 10
PROTON DISTRIBUTION OF R-1235 WHOLE SAMPLES
Wilsonville Run 261

Period	Proton Distribution, %						
	Cond Arom	Uncond Arom	Cyclic Alpha	Alkyl Alpha	Cyclic Beta	Alkyl Beta	Gamma
A*	15.6	4.7	15.9	8.6	17.4	23.3	14.6
B	16.0	4.6	16.3	8.6	17.9	23.1	13.5
C	15.3	5.4	16.7	9.2	16.9	22.5	14.1
D	18.4	4.6	18.4	9.6	16.9	20.4	11.6
E	26.4	4.0	19.9	9.5	14.3	16.8	9.2
F*	24.5	4.8	19.0	9.4	14.1	18.1	10.0
G*	23.1	5.0	19.0	9.7	15.0	17.9	10.2

*Transitional or unstable period.

TABLE 11
PROTON DISTRIBUTION OF V-131B DISTILLATE SAMPLES
Wilsonville Run 261

Period	Proton Distribution, %						
	Cond Arom	Uncond Arom	Cyclic Alpha	Alkyl Alpha	Cyclic Beta	Alkyl Beta	Gamma
A*	11.7	4.1	15.1	8.1	19.1	27.6	14.4
B	10.9	4.7	15.2	8.1	19.2	27.5	14.3
C	11.9	4.4	14.5	8.0	17.9	28.5	14.8
D	12.7	3.9	12.0	8.1	18.7	30.1	14.6
E	17.9	5.3	15.9	8.4	15.0	25.0	12.5
F*	15.7	5.0	16.0	8.0	15.2	26.9	13.2
G*	16.5	3.7	17.4	8.1	17.2	25.4	11.6

*Transitional or unstable period.

/ls

TABLE 12
PROTON DISTRIBUTION OF V-1067 DISTILLATE SAMPLES
Wilsonville Run 261

Period	Proton Distribution, %						
	Cond Arom	Uncond Arom	Cyclic Alpha	Alkyl Alpha	Cyclic Beta	Alkyl Beta	Gamma
A*	11.0	4.9	14.6	8.2	18.7	27.2	15.4
B	10.7	5.0	15.3	8.8	20.2	25.7	14.4
C	11.1	4.9	15.0	8.6	19.2	26.4	14.7
D	10.8	6.0	13.4	8.5	18.2	26.6	16.4
E	17.5	5.5	16.6	9.2	15.8	23.4	11.9
F*	14.4	6.0	16.0	8.8	16.9	24.7	13.3
G*	14.6	5.1	16.9	9.2	17.8	23.4	13.0

*Transitional or unstable period.

TABLE 13
PROTON DISTRIBUTION OF R-1235 DISTILLATE SAMPLES
Wilsonville Run 261

Period	Proton Distribution, %						
	Cond Arom	Uncond Arom	Cyclic Alpha	Alkyl Alpha	Cyclic Beta	Alkyl Beta	Gamma
A*	9.4	5.3	13.9	8.5	19.7	27.5	15.7
B	9.0	5.9	13.4	8.4	19.4	28.0	15.9
C	9.4	5.5	14.1	8.5	19.0	27.4	16.0
D	9.0	6.7	12.3	8.6	18.3	27.5	17.5
E	15.1	6.5	15.5	9.7	16.2	24.0	13.0
F*	14.0	6.1	15.1	9.4	16.7	24.9	13.8
G*	13.4	5.8	15.5	9.4	17.5	24.6	13.7

*Transitional or unstable period.

/ls

TABLE 14
PROTON DISTRIBUTION OF V-131B RESID SAMPLES
Wilsonville Run 261

Period	Proton Distribution, %						
	Cond Arom	Uncond Arom	Cyclic Alpha	Alkyl Alpha	Cyclic Beta	Alkyl Beta	Gamma
A*	22.2	2.6	19.6	8.9	17.3	19.8	9.5
B	21.6	2.8	19.6	8.7	17.4	20.3	9.5
C	24.1	3.4	20.2	8.8	16.2	17.8	9.5
D	26.0	2.6	21.0	9.0	16.2	16.8	8.4
E	35.0	4.4	19.9	9.1	12.8	11.9	6.9
F*	30.8	4.8	20.8	9.5	13.4	13.0	7.6
G*	30.6	4.4	21.0	9.4	14.1	13.2	7.2

*Transitional or unstable period.

TABLE 15
PROTON DISTRIBUTION OF V-1067 RESID SAMPLES
Wilsonville Run 261

Period	Proton Distribution, %						
	Cond Arom	Uncond Arom	Cyclic Alpha	Alkyl Alpha	Cyclic Beta	Alkyl Beta	Gamma
A*	22.4	3.1	20.0	8.8	17.0	19.0	9.7
B	20.8	3.6	18.2	8.1	18.9	19.5	10.8
C	24.1	2.9	20.8	9.1	15.8	17.8	9.5
D	25.0	4.0	20.1	9.5	15.7	15.6	10.0
E	34.7	3.8	21.7	9.1	12.9	11.5	6.3
F*	30.5	4.9	21.3	9.4	13.4	12.9	7.6
G*	31.5	3.2	22.7	9.2	14.2	12.5	6.7

*Transitional or unstable period.

/ls

TABLE 16
PROTON DISTRIBUTION OF R-1235 RESID SAMPLES
Wilsonville Run 261

Period	Proton Distribution, %						
	Cond Arom	Uncond Arom	Cyclic Alpha	Alkyl Alpha	Cyclic Beta	Alkyl Beta	Gemma
A*	21.1	2.7	21.1	8.8	17.3	19.6	9.4
B	21.7	2.9	21.9	9.2	17.1	17.6	9.6
C	21.7	4.8	19.7	9.0	16.2	16.6	11.9
D	23.3	5.8	19.8	9.4	15.5	16.2	9.9
E	29.1	7.6	20.1	9.5	13.1	12.4	8.2
F*	30.2	5.1	21.2	9.4	13.2	13.2	7.6
G*	29.5	4.8	22.1	9.7	13.8	12.9	7.3

*Transitional or unstable period.

TABLE 17
PHENOLIC -OH CONCENTRATION BY FTIR
Wilsonville Run 261

Period	Phenolic -OH Concentrations, meq/g											
	V-131B				V-1067				R-1235			
	Dist.	ν cm ⁻¹	Resid	ν cm ⁻¹	Dist.	ν cm ⁻¹	Resid	ν cm ⁻¹	Dist.	ν cm ⁻¹	Resid	ν cm ⁻¹
A*	0.19	3308	0.69	3297	0.19	3310	0.90	3298	0.28	3312	0.80	3297
B	0.17	3311	0.56	3299	0.18	3310	0.60	3298	0.29	3313	0.86	3298
C	0.19	3307	0.80	3298	0.20	3310	0.79	3297	0.28	3311	0.99	3297
D	0.23	3308	0.73	3298	0.28	3309	0.83	3298	0.36	3311	0.98	3296
E	0.36	3304	0.83	3297	0.41	3306	0.84	3295	0.56	3308	1.01	3295
F*	0.33	3305	0.87	3297	0.40	3307	0.88	3296	0.57	3308	1.03	3295
G*	0.29	3306	0.82	3297	0.33	3310	0.87	3296	0.44	3309	1.00	3296

*Transitional or unstable period.

/ls

TABLE 18
MICROAUTOCLAVE TEST RESULTS
Wilsonville Run 261

Period						
	V-131B		V-1067		V-1235	
	Dist.	Whole	Dist.	Whole	Dist	Whole
A*	72.4	78.8	73.5	74.7	71.8	67.7
B	74.8	80.8	76.1	78.7	75.4	80.3
C	74.8	93.0	76.7	79.0	74.1	73.3
D	73.4	73.9	77.1	73.9	76.5	72.9
E	83.8	65.6	83.9	49.4	79.0	61.4
F*	80.8	50.4	85.2	69.0	80.0	61.6
G*	83.2	73.4	83.7	43.8	81.6	54.1

*Transitional or unstable period.

Conditions: 750°F, 30 min, 9 g solvent, 6 g Old Ben Mine No. 1 coal

/ls

TABLE 19
CONVERSION OF RESID COMPONENTS
Wilsonville Run 261

Period	Conversion, %					
	850°F ⁺ (a)	Oils	Asphal- tenes	Preasphal- tenes	Coal + IOM	THF-Soluble Resid
First Stage						
A*	15.2	-23.3	-38.2	-136.3	80.7	-41.8
B	27.7	6.6	-5.2	-218.2	81.1	-12.8
C	27.9	5.9	-19.8	-153.4	82.6	-18.5
D	24.6	4.3	-15.6	-101.8	82.1	-12.3
E	18.7	-11.6	-28.3	-136.3	84.6	-29.5
F*	19.9	-3.0	-29.2	-101.2	84.4	-19.7
G*	16.5	-13.0	-27.4	-111.7	82.7	-26.8
All Periods: Avg ±S.D.	21.5 ±5.2	-4.9 ±11.4	-23.4 ±10.8	-137.0 ±40.9	82.6 ±1.5	-23.1 ±10.5
Periods B-D: Avg ±S.D.	26.8 ±1.8	5.6 ±1.2	-13.5 ±7.5	-157.8 ±58.3	82.0 ±0.8	-14.6 ±3.4
Periods E-G: Avg ±S.D.	18.4 ±1.7	-9.2 ±5.4	-28.3 ±0.9	-116.4 ±18.0	83.9 ±1.1	-25.3 ±5.1
Second Stage						
A*	22.5	19.6	4.1	42.6	20.8	22.7
B	12.5	-3.8	7.9	55.0	26.1	10.8
C	15.2	-0.9	12.6	48.8	18.7	14.8
D	17.3	5.6	16.0	47.8	22.7	16.7
E	16.4	5.4	19.4	45.1	14.1	16.7
F*	13.0	5.7	17.5	33.7	3.8	13.8
G*	7.6	-4.3	8.9	42.9	12.3	7.2
All Periods: Avg ±S.D.	14.9 ±4.6	3.9 ±8.2	12.3 ±5.6	45.1 ±6.6	16.9 ±7.5	14.7 ±4.9
Periods B-D: Avg ±S.D.	15.0 ±2.4	0.3 ±4.8	12.1 ±4.0	50.5 ±3.9	22.5 ±3.7	14.1 ±3.0
Periods E-G: Avg ±S.D.	12.4 ±4.5	2.3 ±5.7	15.3 ±5.6	40.6 ±6.0	10.1 ±5.5	12.5 ±4.9
Total						
A*	34.2	0.9	-32.6	-35.6	84.7	-9.7
B	36.8	3.1	3.1	-43.2	86.1	-0.6
C	38.9	5.0	-4.7	-29.8	85.9	-1.0
D	37.7	9.7	2.9	-5.4	86.2	6.5
E	32.1	-5.5	-3.4	-29.7	86.8	-7.9
F*	30.4	2.9	-6.6	-33.3	85.0	-3.2
G*	22.8	-17.9	-16.0	-20.9	84.8	-17.7
All Periods: Avg ±S.D.	33.3 ±5.5	-0.3 ±9.0	-8.2 ±12.5	-28.3 ±12.1	85.6 ±0.8	-4.8 ±7.8
Periods B-D: Avg ±S.D.	37.8 ±1.1	5.9 ±3.4	0.4 ±4.4	-26.1 ±19.2	86.0 ±0.2	1.6 ±4.2
Periods E-G: Avg ±S.D.	28.4 ±4.9	-6.8 ±10.5	-8.7 ±6.6	-28.0 ±6.4	85.5 ±1.1	-9.6 ±7.4

*Transitional or unstable period.

(a) Includes THF-soluble resid and IOM.

/18

TABLE 20

850°F⁺ CONVERSION AND KINETICS
Wilsonville Run 261

Period	First Stage							
	Temp., °F	WHSV (a)	Cat. Age (b)	Conversion (c)			K (a)	A, 10 ⁷ (a)
				CONSOL (d)	W'ville (e)	Ratio C/W (f)		
A*	790	6.3	1328	15.2	24.30	0.626	1.13	2.83
B	789	6.4	1324	27.7	21.90	1.265	2.45	6.22
C	790	5.0	2537	27.9	23.70	1.177	1.93	4.84
D	791	5.0	2812	24.6	22.90	1.074	1.63	4.03
E	809	3.5	1345	18.7	19.40	0.964	0.81	1.56
F*	809	2.9	1936	19.9	17.60	1.131	0.72	1.40
G*	809	3.0	1966	16.5	19.40	0.851	0.59	1.15
Averages for Stage 1:								
Average All Periods				21.5	21.3	1.01	1.32	3.15
± Std. Dev.				5.2	2.5	0.22	0.70	1.95
Average Periods B-D				26.7	22.8	1.17	2.01	5.03
± Std. Dev.				1.9	0.9	0.10	0.41	1.11
Average Periods E-G				18.4	18.8	0.98	0.71	1.37
± Std. Dev.				1.7	1.0	0.14	0.11	0.21

Period	Second Stage								Total Conversion		
	Temp., °F	WHSV (a)	Cat. Age (b)	Conversion (c)			K (a)	A, 10 ⁷ (a)	CONSOL (d)	W'ville (e)	Ratio C/W (f)
				CONSOL (d)	W'ville (e)	Ratio C/W (f)					
A*	810	5.9	1128	22.5	17.2	1.308	1.71	3.28	34.3	37.3	0.919
B	808	6.0	1090	12.5	20.7	0.604	0.86	1.68	36.7	38.1	0.965
C	809	4.6	2067	15.2	20.0	0.760	0.82	1.60	38.9	39.0	0.997
D	809	4.6	2238	17.3	17.3	1.000	0.96	1.87	37.6	36.2	1.039
E	824	3.3	1450	16.4	20.0	0.820	0.65	1.03	32.0	35.5	0.902
F*	800	2.6	1800	13.0	16.4	0.793	0.39	0.85	30.3	31.1	0.974
G*	800	2.7	1790	7.6	15.8	0.481	0.22	0.49	22.8	32.1	0.711
Averages for Stage 2 and Total:											
Average All Periods				14.9	18.2	0.82	0.80	1.54	33.2	35.6	0.93
± Std. Dev.				4.6	2.0	0.27	0.48	0.91	5.5	3.0	0.11
Average Periods B-D				15.0	19.3	0.79	0.88	1.72	37.7	37.8	1.00
± Std. Dev.				2.4	1.8	0.20	0.07	0.14	1.1	1.4	0.04
Average Periods E-G				12.3	17.4	0.70	0.42	0.79	28.4	32.9	0.86
± Std. Dev.				4.4	2.3	0.19	0.21	0.28	4.9	2.3	0.14

*Transitional or unstable period.

- (a) Basis was lb total feed/hr/lb catalyst. K and A were calculated from CONSOL conversion data.
 (b) lb coal + resid + UC/lb catalyst
 (c) First stage and total conversion: wt % resid + MAF coal + UC fed to first stage
 Second stage conversion: wt % resid + UC fed to second stage
 (d) 850°F distillation end point, atm equivalent
 (e) 1050°F distillation end point, atm equivalent
 (f) Ratio of CONSOL conversion to Wilsonville conversion

/ls

TABLE 21
COMPARISON OF WILSONVILLE RUNS 257 AND 261
Operating Conditions

	257E	257J	261B	261D	261E
Reference	3, 7	3, 7	This Report	This Report	This Report
Coal	(a)	(a)	(a)	(a)	(a)
Coal Ash Content, wt % MF	11.4	11.2	12.1	11.8	11.6
% of Avail Volume in Both Reactors	100	50	100	100	100
Coal Feed Rate, MF lb/hr	402.3	234.8	547.9	423.0	494.3
Coal Conc. in Slurry, wt % MF	33.2	33.3	32.9	31.9	33.0
Resid in Recycle Solvent, wt %	49.9	50	38.3	48.4	48.9
Cl in Recycle Solvent, wt %	12.1	12	12.1	11.9	12.0
Interstage Separator	No	No	Yes	Yes	Yes
T ₁ , °F	791	809	789	791	809
T ₂ , °F	760	760	808	809	824
Catalyst	Am 1C	Am 1C	EXP-AO-60	EXP-AO-60	Crit. 324
Cat. Age, lb (Resid + Cl)/lb Cat.	1434/2313	1367/2248	1324/1090	2812/2238	1345/1450
WHSV, lb Feed/lb Cat. hr	4.3/4.3	6.7/7.0	6.4/6.0	5.0/4.6	3.5/3.3

(a) Burning Star 2

NOTE: All runs catalytic/catalytic. Distillation and recycle changes were in effect in Run 261.

TABLE 22
COMPARISON OF WILSONVILLE RUNS 257 AND 261
Process Performance and Yields

Period	257E*	257J*	261B	261D	261E
Distillate Yield, wt % MAF Coal	66.5	65.8	64.4	65.6	60.6
Resid Yield, wt % MAF Coal	2.1	1.2	4.7	3.7	5.4
Ash Conc., wt % MAF Coal	18.8	18.5	17.9	15.3	16.7
TSL Coal Conversion, wt % MAF	92.6	91.7	91.7	93.0	92.7
Resid + UC Conversion, wt % Feed					
1st Stage	26.4	26.5	21.9	22.9	19.4
2nd Stage	12.1	12.2	20.7	17.3	20.0
Total	35.3	35.5	38.1	36.2	35.5

*Reference 3

/is

TABLE 23

COMPARISON OF WILSONVILLE RUNS 257 AND 261
Process Oil Characteristics, Conversions and Kinetic Constants

	257E	257J	261B	261D	261E
<u>SQI (a)</u>					
Recycle Distillate	81.8-83.0	78.4-80.6	81.3-82.6	76.5-77.9	78.2-80.4
Interstage	83.7	78.3	79.0	76.3	79.0
<u>Hydrogen Aromaticity, % of Protons (b)</u>					
Recycle Distillate	11.7-12.2	12.2-12.3	15.6-15.7	16.6-16.8	23.0-23.2
Interstage Distillate	12.5	14.0	14.9	15.7	21.6
Recycle Resid	18.9-19.8	22.1-23.3	24.4	28.6-29.0	38.5-39.4
Interstage Resid	20.5	25.4	24.6	29.1	36.7
<u>Paraffinic Hydrogen, % of Protons (c)</u>					
Recycle Distillate	42.2-43.4	44.1-46.4	40.1-41.8	43.0-44.7	35.3-37.5
Interstage Distillate	41.0	44.3	43.9	45.0	37.0
<u>Phenolic -OH Concentration, meq/g Sample</u>					
Recycle Distillate	0.20	0.24-0.28	0.17-0.18	0.23-0.28	0.36-0.41
Interstage Distillate	0.32	0.45	0.29	0.36	0.56
Recycle Resid	0.49-0.52	0.66-0.74	0.56-0.60	0.73-0.83	0.83-0.84
Interstage Resid	0.67	0.95	0.86	0.98	1.01
<u>Recycle Resid Components, wt %</u>					
Oils	75.6-78.6	71.5-75.2	73.1-75.9	65.4-67.7	65.7-67.2
Asphaltenes	13.2-13.3	15.3-15.4	15.7-16.3	20.5-21.3	20.5-21.4
Preasphaltenes	8.2-11.0	9.5-13.1	7.8-11.1	11.8-13.3	11.4-13.7
<u>Interstage Resid Components, wt %</u>					
Oils	71.7	68.6	62.8	57.7	57.9
Asphaltenes	14.3	16.6	15.2	21.1	21.2
Preasphaltenes	14.0	14.8	22.0	21.2	20.8
<u>850°F⁺ Conversion, %</u>					
First Stage	23.6	26.2	27.7	24.6	18.7
Second Stage	8.9	9.6	12.5	17.3	16.4
Total	30.5	33.3	36.7	37.6	32.0
<u>Kinetic Rate Constants for 850°F⁺ Conv. (d)</u>					
First Stage	1.33	2.38	2.45	1.63	0.81
Second Stage	0.42	0.74	0.86	0.96	0.65
<u>Activities for 850°F⁺ Conversion, 10⁷ (d)</u>					
First Stage	3.29	4.63	6.22	4.03	1.56
Second Stage	1.60	2.84	1.68	1.87	1.03

(a) SQI - Solvent Quality Index, predicted microautoclave donor solvent quality based on proton distribution of each distillate sample.

(b) Sum of condensed and uncondensed aromatic protons.

(c) Sum of alkyl beta and gamma (paraffinic) protons.

(d) lb total feed/hr/lb catalyst.

/ls

TABLE 24

PROTON DISTRIBUTIONS OF CRUDE OIL FRACTIONS
Wilsonville Runs 260D and 259G

Fraction	Yield, wt % of Crude (a)	H Content, wt % (a)	Proton Distribution, wt %						
			Cond Arom	Uncond Arom	Cyclic Alpha	Alkyl Alpha	Cyclic Beta	Alkyl Beta	Gamma
Run 260D Fractions									
Naphtha, IBP x 380°F	23.65	13.6	2.1	2.1	2.1	4.3	34.6	25.8	29.1
Jet Fuel, 380 x 510°F	18.95	10.6	6.6	10.4	8.3	10.1	18.4	27.4	18.9
Diesel Fuel, 510 x 650°F	22.89	10.7	4.9	6.9	12.6	9.7	20.9	28.3	16.7
Residuum, 650°F ⁺	34.51	10.13	8.7	5.4	14.5	8.7	18.6	29.6	14.5
Whole Crude Oil (b)	100.00	11.2	5.3	5.9	8.8	7.9	23.9	27.6	20.5
Run 259G Fractions									
Naphtha, IBP x 380°F	26.72	13.3	2.1	3.0	2.8	5.2	30.2	29.4	27.4
Jet Fuel, 380 x 510°F	31.39	11.5	2.0	6.8	8.0	8.6	22.8	29.7	22.0
Diesel Fuel, 510°F ⁺	41.89	10.5	5.7	6.3	12.2	8.5	22.0	27.5	17.7
Whole Crude Oil	100.00	11.55	3.1	5.4	7.6	7.3	23.9	30.3	22.4

(a) Yield and hydrogen content data from References 12 and 13.

(b) Sample unavailable for analysis. Proton distribution of Run 260D crude oil calculated from the H-contents and yields and ¹H-NMR data of its fractions.

TABLE 25

PHENOLIC -OH AND TOTAL OXYGEN CONTENTS OF CRUDE OIL FRACTIONS
Wilsonville Runs 260D and 259G

Fraction	Yield, wt % of Crude (a)	Phenolic -OH Concentration, meq/g	Oxygen Content, wt %	
			Phenolic	Total (diff.) (a)
Run 260D Fractions				
Naphtha, IBP x 380°F	23.65	0.40	0.64	1.9
Jet Fuel, 380 x 510°F	18.95	0.92	1.47	3.3
Diesel Fuel, 510 x 650°F	22.89	0.52	0.83	2.0
Residuum, 650°F ⁺	34.51	0.41	0.66	1.0
Whole Crude Oil	100.00	0.53 (b)	0.85 (b)	1.0 (c)
Run 259G Fractions				
Naphtha, IBP x 380°F	26.72	0.18	0.29	1.3
Jet Fuel, 380 x 510°F	31.39	0.25	0.40	1.4
Diesel Fuel, 510°F ⁺	41.87	0.13	0.21	0.9
Whole Crude Oil	100.00	0.18	0.29	1.4

(a) Yield and total oxygen data from References 1 and 2.

(b) Sample unavailable for analysis, calculated from the properties of the fractions.

(c) Suspect low.

/ls

TABLE 26

RESULTS OF CAUSTIC WASHING OF WILSONVILLE RUN 260D CRUDE OIL FRACTIONS

Run 260D Syncrude Fraction	Phenolic -OH Concentration, meq/g Sample		Yields, wt % of Feed	
	Feed Oil	Raffinate	Acidic Fraction	Raffinate
Naphtha	0.40	0.02*	3.7	92.7
Jet Fuel	0.92	0.07*	3.6	94.7
Diesel Fuel	0.52	0.27	4.6	94.4
Residuum - Trial 1	0.41	0.28	1.9	95.4
Residuum - Trial 2	0.41	0.31	2.0	97.9

*Quantitation is uncertain at extremely low concentrations.

TABLE 27

¹H-NMR ANALYSES OF CAUSTIC WASHING RAFFINATES
 Wilsonville Run 260D Crude Oil Fractions

Raffinate Fraction	Proton Distribution, %						
	Cond Arom	Uncond Arom	Cyclic Alpha	Alkyl Alpha	Cyclic Beta	Alkyl Beta	Gamma
Naphtha	1.9	0.6	1.8	3.7	32.5	28.8	30.7
Jet Fuel	6.5	8.3	6.0	7.7	21.4	28.8	21.2
Diesel Oil	5.7	6.2	13.4	9.5	21.2	27.6	16.5
Residuum - Trial 1	8.2	5.2	13.6	8.9	18.4	30.5	15.3
Residuum - Trial 2	8.1	5.6	13.1	8.8	17.9	30.1	16.3

/ls

TABLE 28

**COMPOSITIONS OF PHENOLIC EXTRACTS BY GC/MS
Wilsonville Run 260D Crude Oil Fractions**

Compound	Naphtha Phenolic Extract		Jet Fuel Phenolic Extract	
	No. of Resolved Peaks	Relative Peak Area, (Largest Peak = 100)	No. of Resolved Peaks	Relative Peak Area, (Largest Peak = 100)
Phenol	1	96	1	2
o-cresol	1	60	1	6
m/p-cresol	2	127	1	24
Dimethyl phenol	6	51	6	77
Ethyl phenol	2	66	3	72
Ethyl methylphenol	4	4	5	60
Propyl phenol	1	1	2	83
Trimethyl phenol	-	-	5	35
C ₄ -phenols	-	-	10	92
Indanol	-	-	1	100
Dihydroxy toluene (a)	-	-	1	5
Tetralinol (a)	-	-	1	10

(a) Tentative identification

NOTE: No hydrocarbon contaminants found in the naphtha extract. The jet fuel extract contained minor quantities of biphenyl, diphenyl ether and alkyl benzenes.

/ls

TABLE 29
SUBCONTRACTORS - PHASE I

ORGANIZATION	PRINCIPAL INVESTIGATOR	CONTRACT DURATION	METHODS
University of Kentucky/CAER	F. Derbyshire	6 months	Fluorescence Microscopy
Conoco Petroleum Products Research Division	R. Kramer	12 months	Petroleum Inspection Tests
Western Research Institute	F. Miknis	10 months	¹³ C and ¹ H NMR
The Pennsylvania State University	A. Davis	11 months	Carbonization, Microscopy
SRI International	R. Malhotra	8 months	FIMS, O-Derivatization
Virginia Polytechnic Institute	L. Taylor	10 months	SFE, SFC, LC-FTIR
Advanced Fuel Research	M. Serio	10 months	FTIR, TG-FTIR, On-line FTIR
National Institute for Petroleum and Energy Research	R. Anderson	9 months	Separations, Structural Analysis

/ls

Figure 1. Simplified CC-ITSL Process Diagram for Wilsonville Run 261.

Dotted lines represent operation with ash recycle from V-1067 in Periods A and B. Bold lines represent operation with ash recycle from V-1082 bottoms in Periods C, D, E, F, and G. Resid injection system used in Period G is not shown.

Figure 2. Partial CC-ITSL Process Diagram for Wilsonville Run 261 Showing Major Distillate Streams.

Dotted lines represent operation with ashy recycle from V-1067 in Periods A and B. Bold lines represents operation with ashy recycle from V-1082 bottoms in Periods C, D, E, F, and G. Resid injection system used in Period G is not shown.

Figure 3. Component Distribution of Whole Feed (V-131B) Oils From Wilsonville Run 261.

Figure 4. Component Distribution of Whole Product (V-1067) Oils From Wilsonville Run 261.

Figure 5. Component Distribution of Whole Interstage (R-1235)
Oils From Wilsonville Run 261.

Figure 6. Solubility Fractionation of V-131B THF-Soluble 850°F⁺ Resid Samples From Wilsonville Run 261.

Figure 7. Solubility Fractionation of V-1067 THF-Soluble 850°F⁺ Resid Samples From Wilsonville Run 261.

Figure 8. Solubility Fractionation of Interstage THF-Soluble 850°F⁺ Resid Samples From Wilsonville Run 261.

Figure 9. Proton Distribution of V-131B Distillate and THF-Soluble Resid Samples (850°F⁺ Cutpoint) From Wilsonville Run 261.

Figure 10. Proton Distribution of V-1067 Distillate and THF-Soluble Resid Samples (850°F⁺ Cutpoint) From Wilsonville Run 261.

Figure 11. Proton Distribution of Interstage Distillate and THF-Soluble Resid Samples (850°F* Cutpoint) From Wilsonville Run 261.

Figure 12. Phenolic -OH Concentrations of Distillate and THF-Soluble Resid Samples (850°F* Cutpoint) From Wilsonville Run 261.

Figure 13. Microautoclave Solvent Quality Assays of Samples From Wilsonville Run 261.

Figure 14. First-Stage and Total Conversions of THF-Soluble 850°F+ Resid and Coal + IOM for Wilsonville Run 261.

Figure 15. THF-Soluble 850°F⁺ Conversions for Wilsonville Run 261.

Figure 16. Conversion of Oils (Hexane Solubles) in Wilsonville Run 261.

Figure 17. Conversion of Asphaltenes in Wilsonville Run 261.

Figure 18. Conversion of Preasphaltenes in Wilsonville Run 261.

Figure 19. Resid + UC Conversion Activity in Wilsonville Run 261.

Figure 20. Catalyst Activity for Resid + UC conversion in Wilsonville Run 261.

Figure 21. Total Ion Chromatogram, Naphtha Fraction,
Wilsonville Run 260D Product.
(See key following Figure 4)

Figure 22. Total Ion Chromatogram, Jet Fuel Fraction,
Wilsonville Run 260D Product.
(See key following Figure 4)

Figure 23. Total Ion Chromatogram, Diesel Fuel Fraction,
Wilsonville Run 260D Product.
(See key following Figure 4)

Figure 24. Total Ion Chromatogram, Residuum Fraction,
Wilsonville Run 260D Product.
(See key following Figure 4)

KEY TO PEAK IDENTIFICATIONS **Figures 21 through 24**

Peak No.	Identification	Peak No.	Identification	Peak No.	Identification
1	Butane	45	Decalin	86A	n-Tetradecane
2	C ₆ H ₁₂	46	n-Decane	86	Diphenyl ether
3	C ₆ H ₁₂	47	C ₃ -benzene	87	C ₂ -naphthalene
4	C ₆ H ₁₄	48	Indan	88	C ₂ -naphthalene
5	C ₆ H ₁₂	49	C ₄ -cyclohexane	89	n-Pentadecane
6	Methylcyclopentene	50	Methylhexahydroindan	90	Octahydroanthracene
7	Cyclohexane	51	C ₁₀ H ₁₈	91	C ₄ -tetralin
8	C ₇ H ₁₆	52	C ₄ -benzene	92	Methylbiphenyl
9	C ₈ H ₁₀	53	Decalin	93	n-Hexadecane
10	Dimethylcyclopentane	54	O-cresol	94	C ₂ -biphenyl
11	Methylcyclohexane	55	Methylindan	95	Octahydrophenanthrene
12	Ethylcyclopentane	56	C ₄ -Benzene	96	Methylfluorene
13	Methylcyclohexene	57	Cresol	97	n-Heptadecane
14	Methylcyclohexene	58	Cresol	98	Pristane
15	C ₃ -cyclopentane	59A	n-Undecane	99A	C ₂ -biphenyl
16	C ₃ -cyclopentane	59	Methyldecalin	99	Octahydrophenanthrene
17	C ₇ H ₁₂	60A	Methylindan	100A	C ₂ -biphenyl
18	C ₇ H ₁₂	60	Methylindan	100B	C ₂ -biphenyl
19	Toluene	61	C ₅ -cyclohexane	100	Tetrahydrophenanthrene
20	Methylcyclohexene	62	Ethylphenol	101	Tetrahydrophenanthrene
21	C ₂ -cyclohexane	63	Methyldecalin	102	Phenanthrene
22	C ₂ -cyclohexane	64	Tetralin	103	n-Octadecane
23	C ₃ -cyclopentane	65	Xylenol	104	Phytane
24	C ₃ -cyclopentane	66	Ethylphenol	105A	Methylphenanthrene
25	C ₂ -cyclohexane	67	Ethylphenol	105	n-Nonadecane
26	C ₆ H ₁₆	68	Methyldecalin	106A	Hexahydropyrene
27	C ₃ -cyclopentane	69	Naphthalene?	106	n-Eicosane
28	C ₂ -cyclohexane	70A	n-Dodecane	107	Hexahydropyrene
29	C ₃ -cyclohexane	70	Methyltetralin	108	Dihydropyrene
30	C ₉ H ₂₀	71	C ₃ -phenol	109	n-Heneicosane
31	C ₃ -cyclohexane	72	Methyltetralin	110	Pyrene
32	C ₃ -cyclohexane	73	C ₆ -cyclohexane	111	n-Docosane
33	C ₃ -cyclohexane	74	C ₂ -indan	112	Methylpyrene or Benzofluorene
34	C ₃ -cyclohexane	75	C ₃ -phenol	113	Methylphenylnaphthalene
35	C ₃ -cyclohexane	76	Methyltetralin	114	n-Tricosane
36	C ₃ -cyclohexane	77	C ₂ -indan	115	Terphenyl
37	C ₄ -cyclopentane	78	Methyltetralin	116	n-Tetracosane
38	Hexahydroindan	79	n-Tridecane	117	n-Pentacosane
39	C ₄ -cyclohexane	80	Bicyclohexyl	118	n-Hexacosane
40	C ₃ -benzene	81	Methylnaphthalene	119	n-Heptacosane
41	C ₃ -benzene	82	Methylnaphthalene	120	n-Octacosane
42	C ₁₀ H ₂₂	83	C ₃ -indan		
43	Phenol	84	Biphenyl		
44	C ₄ -cyclohexane	85	C ₂ -tetralin		

NOTES: Identifications based on search of Wiley/NBS Library of mass spectra, C_x refers to alkyl substituents of x carbon atoms. Search results may misidentify isomers, e.g., "hexahydropyrene" may refer to hexahydrofluoranthene and "C₂-biphenyl" may refer to C₂-acenaphthene.

/ls

APPENDIX 1

Site visits were made to seven research groups for the purpose of discussing possible teaming arrangements under Phase II of the Participants Program. Recommendations for analytical work were drafted from each visit.

Visits were made to the following organizations:

Date of Visit	Organization	Host
8/15/91	University of Pittsburgh	S. Asher
8/30/91	Lehigh University	J. Larsen
9/26/91	Massachusetts Institute of Technology	S. Vander Sande
9/27/91	University of Chicago	L. Stock
10/2/91	West Virginia University	M. Seehra
10/21/91	Iowa State University	J. Verkade
10/23/91	University of Utah	R. Pugmire

Trip Report: University of Pittsburgh

Date of Visit: August 16, 1991

Address: University of Pittsburgh
Department of Chemistry
Chevron Science Center
Pittsburgh, PA 15260

Principal Contact: Dr. Sanford A. Asher
Professor of Chemistry
Phone: (412) 624-8200
Fax: (412) 624-8552

Attendees:

University of Pittsburgh
Sanford Asher

CONSOL
R.A. Winschel
S.D. Brandes

DISCUSSION

CONSOL Introduction

The project objectives and approaches were briefly discussed. The proposal made to CONSOL by Dr. Sanford (Sandy) Asher of the University of Pittsburgh (June 10, 1991) deals with the use of UV Resonance Raman (UVR) Spectroscopy for the analysis of coal and coal derived resins, extracts, and asphaltenes. Dr. Asher is the inventor of the UVR technique.

University of Pittsburgh Interest

Dr. Pat Keeloh, a chemist for Shell Oil, joined the initial discussions. Pat currently is working with the tunable UV Resonance Raman equipment at the University of Pittsburgh. He is examining HPLC fractions of crude petroleum and catalytic cracker products. His short term goals are to establish a UVR library of typical polycyclic aromatic hydrocarbon (PAH) structural components in the crude oil fractions. This library of information will be used in the future for the characterization of other petroleum samples. That characterization will primarily entail determination of the aromatic ring number distribution. He believes that a major advantage of the method is the short time required to analyze a sample of complex structural components (once the library of reference structures has been established). He pointed out that extended wet chemical and chromatographic techniques normally required to determine

the distribution and character of conjugated ring structures could be eliminated all-together with the use of this technique.

The limits on the technique were discussed. Individual classes of species (e.g., phenanthrenes) can be selectively excited; each has a distinct excitation profile. We were told that there was little matrix effect on identification of any one species (i.e., no solvent effects) and that only direct substitution on a conjugated ring would cause a shift in the absorption spectra (although slight) and a larger change in the UVRR spectra. Fluorescence does not interfere, because all the fluorescence occurs at lower energies than where the Raman UV measurements are made. Part of the ongoing work at Pitt is to refine the method for the determination of the substitution patterns of aromatics. PAHs can be determined in parts-per-trillion concentrations.

We were shown the UVRR equipment. At the time, it was being run with samples of pure compounds in solution. Samples are pumped past the laser focal point. The flow system is used to prevent the samples from becoming heated by the laser. Dr. Asher's instrument is home-made; there are none manufactured commercially. He believes his is the best in the world. A UVRR analysis takes about 5 min.

The library that is being built with the petroleum materials, and the small amount of work previously done at Pitt with coal liquids, would have to be supplemented with additional model compounds before an extensive and quantitative application of the UVRR to coal liquids could be made. However, specific PAH backbone structures in coal liquids can now be singled out and monitored; specifically pyrene, anthracene, phenanthrene, and naphthalene. Substitutions on these conjugated backbone structures also can be determined with the technique.

Dr. Asher's group has applied the UVRR technique on various types of materials: interactions of hemoglobin, proteins and other bio-medical materials, olefins in polypropylene and several coal liquids, the latter work was done in conjunction with PETC. The technique can be applied to analyzing flowing streams "on the fly", even streams containing some particulates. Thus, it could be applied as a chromatographic detector (LC or SFC) or perhaps on-line to a process stream. Dr. Asher thinks it should be possible down the road to quantify 100 compounds in a one-hour data collection/calculation process. The method is most useful for strongly fluorescing materials, such as condensed aromatics. For multi-component determinations in complex samples, the data are processed by factor analysis. Dr. Asher supplied us with numerous relevant publications.

General Analytical Needs and Suggestions

Dr. Asher suggested the following program which could be integrated into the thesis work of a graduate student.

1. Do some fundamental studies on characteristic compound types expected to be encountered in the coal liquids; i.e., expand the UVRR library.

2. Determine the optimum methodology for doing the spectroscopy, including sample preparation. Because the samples must be moved past the focal point of the laser to prevent localized heating, and because sample solubility in UV transparent solvents (H₂O, EtOH, MeOH, AcCN, iPA, cyclohexane and fluoroform) will not be good for coal liquid resid samples, the methodology for casting a film of the material, which then will be agitated in the focal plane (e.g., a spinning disk), will have to be worked out. Good coal solvents (THF, pyridine, dmf) are strong interferents, but could be used to cast a film.
3. Apply the method to direct coal liquefaction process derived samples. Aromatic ring systems would be quantified by number of condensed rings on four soluble resids. Two whole oils would be analyzed similarly, but in a flowing system.

If available, CONSOL will supply small quantities (0.25-0.50g) of coal liquid model compounds to Pitt for addition to the UVRR library.

Recommendations

Based on previous communications and this meeting, we recommend that the UV Resonance Raman technique be applied to four very different direct coal liquefaction-derived tetrahydrofuran-soluble resid samples. Ten to twenty grams of material would be sufficient for optimization and analysis. These four samples would be characterized by groups of different ring conjugation (mainly 2, 3, and 4 ring groups, and possibly 5 and 6 rings). Speciation of compounds within these groups also would be attempted. The resids would be analyzed as cast film. Two samples of whole process oil would then be characterized by the technique using the information obtained from the resid samples. The whole process oils would be pumped past the laser focal point as a simulation of on-line measurements.

Follow-up

CONSOL will prepare a more detailed program for use of the UVRR technique for review and comment by Dr. Asher. A detailed cost proposal then will be requested of Dr. Asher. The proposed work was projected to take roughly six months. Costs were projected to be less than \$25,000. There were no objections to a purchase order contract, as long as contractual terms and agreements were within the scope of the University of Pittsburgh policy. If contractual arrangements were complete, work could start in October, 1991. Dr. Asher suggested that a publication could serve as the final report. We noted that this would be acceptable only if all details, including the fundamental and optimization work, were included.

Trip Report: Lehigh University
Date of Visit: August 30, 1991
Address: Lehigh University
Department of Chemistry
Seely G. Mudd Building 6
Bethlehem, PA 18015-3172
Principal Contact: Dr. John W. Larsen
Chairman, Department of Chemistry
Phone: (215) 758-3470
Fax: (215) 758-3461

Attendees:

Lehigh University
J. W. Larsen

CONSOL
R.A. Winschel
S.D. Brandes

DISCUSSION

CONSOL Introduction

The project objectives and approaches were briefly discussed. The proposal made to CONSOL by Dr. John Larsen of Lehigh University (June 10, 1991) deals with the use of ^{252}Cf -Plasma Desorption Mass Spectrometry (^{252}Cf -PDMS) for the analysis of coal and coal-derived resids.

Lehigh University Interest

Dr. Larsen gave us a description of the workings of the ^{252}Cf -plasma desorption mass spectrometer. The machine is a commercial instrument (Bio-ion, Model 20, cost: \$220,000) purchased one year ago under a DOE instrument grant. It was modified to reach accelerating voltages of just under 20,000 volts. The Californium source decays and simultaneously emits daughter nuclei (principally ^{106}Tc and ^{142}Ba) in opposite directions. Approximately 3,000,000 fission events occur hourly. The Californium source is situated between the detector of a timer and the sample. Some of the decay events occur along this axis. In those cases, one emitted ion strikes the detector which starts the timer; the other ion strikes the back of the sample support, which can be a thin film of Mylar, aluminum foil or other material. The ion transfers most of its energy to the sample in the form of translational energy. There is little vibrational energy and, thus, little fragmentation. The sample desorbs multiple secondary ions which are accelerated by a voltage down the drift tube of a time-of-flight mass spectrometer. The sample ion is detected and the mass calculated by its time of flight. The data resulting from two nearly simultaneous fission events (based on the arrival at the

detector which activates the timer) are discarded by the computer. There is almost no fragmentation of the sample ions. Primarily M^+ and $M+1$ ions are detected; however, occasionally doubly ionized ions also are detected. In order to analyze data from non-polar materials, special software was written at Lehigh.

The Lehigh system has been demonstrated with a polypeptide of 24,700 daltons. The best results with mixtures was obtained at Lehigh with materials with a distribution around 1000 daltons. The researchers at Lehigh already have examined pyridine extracts of coal and have obtained very broad molecular weight distributions (a few hundred to 10,000 daltons). They encountered a sensitivity problem because the distribution was so broad. This is overcome by extending the data accumulation time. For coals, data are accumulated for several hours (6 million counts). Twenty minutes (2 million counts) is sufficient for low molecular weight samples.

One question which has not been answered, and which Dr. Larsen would like to address in the work under the Participants Program, is whether or not there is discrimination inherent in the ionization process. Specifically, do the aromatic and aliphatic species have different ionization cross sections? One approach to answering this question was outlined by Dr. Larsen. Analysis would be made of an aromatic rich sample and an aliphatic rich sample. The samples then would be mixed and analyzed to determine if the spectra are additive. If not, there is discrimination in the ionization process. Separation by silica gel chromatography of mixtures to concentrate aromatic-rich and aliphatic-rich fractions would be one way to approach this work. It is anticipated that the high energy ionization process (100 MeV) reduces any selectivity.

Dr. Larsen pointed out the advantage of the ^{252}Cf -PDMS technique over Field Ionization Mass Spectrometry (FIMS) or Field Desorption Mass Spectrometry (FDMS) is that there is no need for the sample to be at all volatile. In addition, the mass range is much greater. There may be less selectivity with the ^{252}Cf -PDMS technique because of its high energy ionization process, but that has not yet been determined.

We met Mr. Bill Anderson who has primary responsibility for the care and operation of the equipment. He gave us a detailed run-down on the operation of the machine, described the sample preparation techniques, and showed us how the data are handled on a PC-driven system. Eight individual samples can be loaded on a sample carousel simultaneously. This reduces the number of times the vacuum in the sample chamber has to be broken in examining a number of samples. The acceleration tube is quite short (about 6 inches). Reestablishment of operating vacuum (10^{-5} torr) takes only five to ten minutes. Samples are currently being prepared by an electro-spray technique which deposits a monomolecular layer on a support. The support can be aluminum foil, gold foil, or mylar film. Additional sample preparation techniques which have been tried include evaporative deposition, and simply dusting a fine powder on the surface. Other techniques such as lifting an interfacial layer of material from a solution are routinely used in the biochemical applications of the instrument. In general, samples that are soluble in some solvent are best. He told us that the longest accumulation time

that had been used to date by the Lehigh researchers was overnight (18 hours). The Californium source does produce low-level radiation and prolonged exposure was not recommended; however, it is well below levels of concern for the brief exposure encountered in using the machine. Replacement cost of the source was estimated as approximately \$5000. Its lifetime is about five years.

General Analytical Needs and Suggestions

Comparison of the ^{252}Cf -PDMS results to those obtained from other molecular weight determining methods such as Field Ionization Mass Spectrometry (FIMS) and Field Desorption Mass Spectrometry (FDMS) would be made by the researchers at Lehigh. The data would be supplied by CONSOL from work done under Phase I of the Participants Program. This will necessitate the issuance of at least some of the same samples that were examined in Phase I by these other methods. Lehigh also would compare PDMS data with results of gel permeation chromatography, vapor phase osmometry and ebulliometry, obtained at Lehigh. Another need is to obtain the ionization cross-section information, as discussed above.

Recommendations

Based on previous communications and this meeting, we recommend that the ^{252}Cf -PDMS technique be used for analysis of approximately thirty THF-soluble samples to be chosen by CONSOL. Less than one gram of each sample will be required. For selected samples, a preliminary liquid chromatographic separation will be made of the sample to separate it into chemical classes using something like a PONA separation. Material retained on the column will be recovered by dissolution of the silica gel by NaOH solution. Each fraction then will be examined by the ^{252}Cf -PDMS technique and certain other molecular weight determining methods.

Lehigh has several important qualifications for this work: 1) they were the first to use the method on coals and petroleums (it is primarily used by biochemists), 2) they have the know-how to analyze non-polar materials (the use of Mylar instead of the commonly used cellulose supports appears to be crucial), 3) they have developed the software needed to collect and manipulate the data generated from complex mixtures, and 4) Larsen's group is well experienced with coal-derived materials.

Follow-up

CONSOL will prepare a more detailed program for use of the ^{252}Cf -PDMS method for review and comment by Dr. Larsen. A detailed cost proposal will then be requested of Dr. Larsen. The proposed work was projected to take roughly five months. Costs were projected to be less than \$25,000, including instrument time and supplies. There were no objections to a purchase order contract, as long as contractual terms and agreements were within the scope of the Lehigh University policy. If contractual arrangements were complete, work could start in November 1991. Dr. Larsen would prefer to submit monthly reports. He believes, at this time, that some initial start-up monies for supplies may be required and a single final payment upon CONSOL's receipt of a final report would be acceptable.

Trip Report: Massachusetts Institute of Technology
Date of Visit: September 26, 1991
Address: Dept. of Materials Science and Engineering
Massachusetts Institute of Technology
Cambridge, MA 02139
Principal Contact: Dr. John B. Vander Sande
Phone: (617) 253-6933

Attendees:

MIT

J. B. Vander Sande

CONSOL

R. A. Winschel

S. D. Brandes

DISCUSSION

CONSOL Introduction

The project objectives and approaches were discussed. The proposal made to CONSOL by Dr. John Vander Sande of MIT (June 10, 1991) deals with the use of Transmission Electron Microscopy (TEM) and Scanning Transmission Electron Microscopy (STEM) for the analysis of coal and coal derived resids.

MIT Interest

Dr. Vander Sande described his past work in microscopy. The main thrust of his work has been in structural analysis, on a near-atomic scale, of metals, earth minerals, ceramics, superconducting oxides, and in general, fine particle (10nm to 2 μ m). He is particularly interested in the influence of structural properties on mechanical and electrical properties. He has some experience examining the mineral matter in coal. This work was done a number of years ago while working at Sandia National Laboratory. Dr. Vander Sande's group consists of two research associates, two post-docs, and six graduate students.

Two methods of microscopic analysis were discussed, Transmission Electron Microscopy (TEM) and Scanning Transmission Electron Microscopy (STEM). TEM is a technique that can be used, at high resolution, to discern structural details at less than 2 Å point-to-point resolution; this can provide atomic-size imaging. STEM yields slightly poorer image resolution than TEM, but allows for the analysis of composition with a spatial resolution of about 20 Å. Dr. Vander Sande stressed that the analyses could only be made on solid materials. There is only limited localized

heating of samples because the technique deposits very little incident energy in the sample. Additionally, the samples are very thin and there is, therefore, very little mass for heat adsorption. To minimize any localized sample heating, low dosage techniques that are routinely used for biological samples can be applied. Work at MIT also can be done on samples that are maintained at liquid nitrogen temperatures. However, this increases the time per analysis. Dr. Vander Sande's experience with coal was that no cooling is necessary.

Dr. Vander Sande explained that TEM and STEM have certain advantages over scanning electron microscopy (SEM). Though SEM gives optical resolution to 10nm, the associated EDX analysis is of $1 \mu\text{m}^3$ of volume.

An overview of a two-stage direct liquefaction process was discussed with Dr. Vander Sande. The idea of examining samples from the Wilsonville Direct Coal Liquefaction R&D facility, Run 262, in which a dispersed molybdenum catalyst (Molyvan L) was used, was discussed. An examination (size, morphology, occurrence and chemical nature) of the molybdenum in samples taken at different points in the process may give clues to the reactivity of the catalyst as the material is cycled through the plant. THF-insoluble samples containing mineral matter and insoluble organics could be examined by the TEM and STEM techniques. These samples are dry powders with particle sizes (unagglomerated) of ca. <100 mesh, and therefore require minimal sample preparation. The powder would be distributed on a carbon-coated copper grid by dipping the grid in the sample and shaking off the excess. Samples with larger sizes can be imbedded in a polymer and microtomed. Examination of these samples would be done in two steps. First, the samples would be globally scanned to map the molybdenum concentration. This would require about one hour per sample. Then, the Mo-rich areas of the sample would be examined in a point-by-point analysis at high magnification. The point-by-point examination would include X-ray diffraction (XRD) or microdiffraction analysis, and energy dispersive X-ray spectroscopy (EDX) or electron energy loss spectrometry (EELS). It requires several hours of instrument time to examine a micron element and many micron elements would be examined for each sample until the sample is "fully" analyzed. It was estimated that the full analysis for a single sample would be approximately one man-week.

The supporting analytical experiments also were discussed. EDX looks at the X-ray emitted in the STEM experiment from the outer electronic shells of the species being examined. The elements with atomic number ≤ 9 are not detectable via the EDX experiment. Those elements are examined by the primary energy loss event that occurs on impingement of the electron on the outer shell (EELS). Microdiffraction analysis distinguishes the structure of crystalline material by rocking the electron beam through a few degree precession about the point of incidence.

Dr. Vander Sande cautioned that although there is a considerably large information content from TEM and STEM experiments, it must be realized that these are not bulk techniques and only localized portions of the sample are examined. It, therefore, requires many measurements to get statistically significant data.

Available instrumentation includes: a 300kV VG STEM (the only one in the world, beam size of 1nm, will be used for this work), a 100kV VG STEM with a field emission gun source, a 200kV JEOL 200C mid-resolution TEM, a JEOL 200CX low-resolution TEM, a 200kV HSI high-resolution TEM, and a Phillips EM300 controlled-atmosphere (to 0.2atm) SEM.

General Analytical Needs and Suggestions

In order to get a full picture of the samples it may be necessary to supplement the TEM and STEM data with Auger electron spectroscopy and secondary ion mass spectroscopy (SIMS) experiments.

Recommendations

Based on previous communications and this meeting, we recommend that the TEM and STEM techniques be used for analysis of six THF-insoluble samples to be chosen by CONSOL. These samples would be selected from Wilsonville Run 252. The program would be structured to provide information on the physical and chemical nature of the dispersed molybdenum and iron catalysts as they exist in the process oils. Examination by other techniques such as Auger electron spectroscopy and SIMS will be employed to provide additional information for each sample. Less than one gram of each sample will be required.

Follow-up

CONSOL will prepare a more detailed program for use of the TEM and STEM methods for review and comment by Dr. Vander Sande. A detailed cost proposal will then be requested of Dr. Vander Sande. The proposed work was projected to take six months at a half time level of effort of a post-doctoral researcher. Costs were projected to be approximately \$17,000 (\$15k manpower, \$2k instrument time and supplies). Manpower could be reduced to 2.5 man months by reducing the sample set to four, if needed. There appears to be no objection to a purchase order contract, as long as contractual terms and agreements were within the scope of MIT policy. If contractual arrangements were complete, work could start in November 1991.

Trip Report: University of Chicago
Meeting Site: Argonne National Laboratory
Date of Visit: September 27, 1991
Address: University of Chicago
Department of Chemistry
5735 South Ellis Avenue
Chicago, IL 60637
Principal Contact: Dr. Leon M. Stock
Department of Chemistry
Phone: (312) 702-7058

Attendees:

University of Chicago
L. M. Stock

CONSOL
R. A. Winschel
S. D. Brandes

DISCUSSION

The meeting was held at the Argonne National Laboratory site at the request of Dr. Stock. All work discussed at this meeting will be performed at the University of Chicago, utilizing the University's staff and facilities.

CONSOL Introduction

The project objectives and approach were briefly discussed. The proposal made to CONSOL by Dr. Leon Stock of the University of Chicago (June 26, 1991) deals with the use of chemical methods to speciate the oxygen functional groups in coal-derived resids.

University of Chicago Interest

Two research avenues were discussed. The first dealt with the derivatization of hydroxyl oxygen (phenolic, alcoholic, carboxylic) in coal liquefaction derived resids. Dr. Stock described some previous work with a Lloydminster petroleum resid (1% oxygen), in which the alkylation procedure (with D or ^{13}C labeled methyl iodide) followed by D- or ^{13}C -NMR resulted in clearly distinguishable signals in the NMR attributable to different -OH species. Hydroxyl groups are quantitatively converted. He felt that this same experiment with the coal-derived materials would yield correspondingly good results. Phenolic oxygen contents of the coal

resids (ca. 0.8 to 1.6 wt %) are well within the limits of detection for this technique. This procedure will also provide some information on thiols and amines, though this will not be the principal focus. Dr. Stock's prior work has been with solubles and he thinks that they should be the focus of this work. However, it would be possible with this technique to derivatize solids-containing resids and use solid state ^{13}C -NMR to examine the products. The drawback is that NMR resolution is poor for solids and thus speciation is hindered. Perhaps one such sample should be included.

The second avenue of research entailed selective cleavage of the etheric bonds in the coal-derived resids followed by derivatization and identification of the derivatized species by NMR. This work would involve some developmental effort. Two techniques to determine the nature of the cleaved ether bond could be used. In the first, the native hydroxyls would be alkylated, a baseline NMR spectrum obtained, then the ethers cleaved and the material again alkylated. An increase in the various frequencies in the NMR spectrum assigned to the different hydroxyl groups then would be attributed to the cleaved ethers. The second technique entails blocking the native hydroxyls in the starting material, then selectively cleaving the ethers in such a way that the protected groups are left untouched. The material then would be alkylated with a labeled reagent and the new peaks in the NMR spectrum could be directly attributed to the cleaved ethers. Dr. Stock would anticipate using the second method. Unfortunately, dibenzofurans do not react in either scheme.

Dr. Stock expressed an interest in looking at Illinois No. 6 coal-derived materials, because most of his experience is with this coal. The samples should be free of mineral matter and insoluble organic material. Dr. Stock would prefer that the samples not be prepared with THF, an oxygen-containing compound that would react and interfere in the frequency range of interest in the NMR (40-65 ppm). Pyridine, which has no interfering bands in this region, should be a suitable extraction solvent for sample preparation.

General Analytical Needs and Suggestions

It will require approximately five man-days per sample to speciate the hydroxyls and an additional man-week to complete the ether speciation work. It was recommended that the project extend over a four-month period and examine in total five or six pyridine-soluble samples.

Recommendations

Based on previous communications and this meeting, we recommend that the technique be used for analysis of five or six pyridine-soluble resid samples to be chosen by CONSOL. Approximately 10 grams of each sample will be required.

Follow-up

CONSOL will prepare a more detailed program for alkylation and follow-up analysis by NMR for review and comment by Dr. Stock. A detailed cost proposal will then be requested of Dr. Stock. The proposed work was

projected to take four months. Costs were projected to be less than \$25,000. There were no objections to a purchase order contract, as long as contractual terms and agreements were within the scope of the University of Chicago policy. If contractual arrangements were complete work could start in November 1991.

Trip Report: West Virginia University
Date of Visit: October 2, 1991
Address: West Virginia University
Department of Physics
Hodges Hall
Morgantown, WV 26506
Principal Contact: Dr. Mohindar S. Seehra
Department of Physics
Phone: (304) 293-3422
Fax: (304) 293-5732

Attendees:

West Virginia University
M. S. Seehra
Arthur S. Pavlovic
Saresh Babu
Eric Hopkins

CONSOL
R. A. Winschel
S. D. Brandes

DISCUSSION

CONSOL Introduction

The project objectives and approaches were discussed. The proposal made to CONSOL by Dr. Mohindar Seehra of West Virginia University (June 11, 1991) deals with the use of in situ electron spin resonance (esr) spectroscopy, thermogravimetric/differential thermogravimetric (TGA/DTG) analysis and X-ray diffraction analysis of coal derived resids.

West Virginia University Interest

Dr. Seehra described the in situ esr experiment. The "in situ" esr technique is basically a means of obtaining an esr spectrum of a sample as it is ramped through a temperature program. The equipment employed includes a variable-temperature probe that can be operated at temperatures up to 500°C. Sample size is usually about 100mg. The temperature of the sample is ramped from ambient to 500°C in (typically) 20°C steps. At each step, the free radical concentration is stabilized, the spectrum is measured and the temperature then is taken to the next plateau. Temperature is controlled by a stream of preheated N₂ gas that flows around the sample tube. Temperatures are measured by a thermocouple suspended above the sample in the flow chamber. The sample can be

examined in a sealed tube, an open tube (to release volatiles), or in a tube that is located in a specially designed flow chamber that is flushed with flowing N_2 or H_2 at pressures up to 750 psi (50atm). Volatiles either are allowed to condense on the upper, cool portion of the tube (sealed tube), or are vented to the outside when an open tube or the specially designed flow chamber is used. Samples containing ferric iron prove troublesome for esr analysis; however, there is no problem looking at organic solids or solids that contain no ferric iron. Dr. Seehra and his group have a great deal of experience with solid coal samples.

Samples which are completely or partially volatile can pose a certain interpretational problem in that, after a portion of the material volatilizes away from the area of detection, its free radical content can no longer be accounted for. A separate thermogravimetric analysis (TGA) at the same conditions (i.e., temperature program, pressure, atmosphere, etc.) to track the volatiles losses is run in tandem with the esr experiments to help overcome this problem. Even though the experiment can be run in a controlled atmosphere, differences in mass transfer and diffusion would probably make it impossible to closely mimic the liquefaction reactor environment. Dr. Seehra noted that esr can detect only stable free radicals, i.e., those with life-times of nanoseconds or longer.

A discussion was held on the determination of a term that the WVU group calls "hydrogen donor ability" (HDA) by in situ esr. Dr. Seehra described his work with different coal samples. The free radical density (N_s) as a function of temperature goes through two maxima, one at approximately 200°C and the other at about 600°C. Differences in N_s at the maximum near 600°C are correlated with HDA. Coals with lower N_s values are considered to have higher HDAs because there is more internal hydrogen to cap the free radicals that formed. An alternative explanation for the lower N_s value is that fewer free radicals formed in the first place. It is not possible to distinguish between these two interpretations from the esr data alone. Dr. Seehra stressed that the hydrogen content and NMR data (e.g., aromaticity) for each sample must be supplied to aid in the interpretation. Dr. Seehra was interested in seeing if the interpretations made for coal could be extended to coal-derived resids.

Dr. Seehra conducted a tour through his laboratories. The esr is a 9.4 GHz Varian model with a 12" magnet that can operate at fields up to 11000 G but is usually operated at 3000 G. It is sensitive to 10^{15} spins/g (coals usually produce about 10^{18} spins/g). Its magnet is mounted on a track so that it can be moved between the hot-probe area and a cold-probe area. The hot probe is equipped with a flow system which vents to the outside. The TGA is a Mettler TG50 system which can be operated up to 1000°C, but which cannot be pressurized. The X-ray diffractometer is two years old. It is manufactured by Rigaku/DMax. It is completely computerized and is tied into a library file system for mineral identification. A Mattson Cygnus 100 FTIR with a SpectaTech microscope also is available.

General Analytical Needs and Suggestions

A single man-day is required to analyze one sample in a temperature-programmed esr experiment. It was proposed that each sample would be analyzed in both flowing nitrogen and hydrogen atmospheres, and that each esr experiment should be accompanied by a corresponding TGA experiment so that mass losses can be correlated to the esr data. Since the TGA cannot be pressurized, the TGA and esr analyses would both be run at ambient pressure. Because the process temperature to which samples of interest are exposed typically does not exceed 850°F (454°C), it may not be necessary to do the esr experiments up to 500°C; however, this would be specified.

Samples will be supplied to WVU as THF-solubles. Therefore, potential mineral-matter interference in the esr spectra will be eliminated. Perhaps one solids-containing sample would be provided for comparison. The data collected by the esr would include intensity, g-value and line shape. No X-ray work will be requested.

Recommendations

Based on previous communications and this meeting, we recommend that the temperature-programmed esr technique and the corresponding TGA experiments be used for analysis of eight to fifteen THF-soluble samples to be chosen by CONSOL. Approximately 1 g of each sample will be required.

Follow-up

CONSOL will prepare a more detailed program for esr and TGA for review and comment by Dr. Seehra. A detailed cost proposal then will be requested of Dr. Seehra. The proposed work was projected to take approximately eight months; a fully reviewed, revised final report would be provided no later than June 30, 1992. Costs were projected to be approximately \$20,000. There were no objections to a purchase order contract, as long as contractual terms and agreements were within the scope of West Virginia University policy. If contractual arrangements were complete, work could start in November 1991.

Trip Report: Iowa State University
Date of Visit: October 21, 1991
Address: Iowa State Mining and Minerals
Resource Research Institute
111 Metals Development
Iowa State University
Ames, IA 50011
Principal Contact: Dr. John G. Verkade
Department of Chemistry
Phone: (515) 294-5023

Attendees:

Iowa State University
John G. Verkade
Richard Markuszewski
William Buttermore
Richard F. Gaertner - ISU Center for Advanced Technology Development
Robert S. Harris - ISU Center for Advanced Technology Development

CONSOL
R. A. Winschel
S. D. Brandes

DISCUSSION

CONSOL Introduction

We initially met with just Dr. John Verkade of Iowa State University. The project objectives and approaches were briefly discussed. The proposal made to CONSOL by Dr. Verkade (July 31, 1991) deals with the derivatization of functional groups with phosphorous tagging reagents, followed by phosphorous nuclear magnetic resonance (^{31}P -NMR) spectroscopy for the speciation and quantitation of labile hydrogen functional groups in coal-derived resids.

Iowa State University Interest

Dr. Verkade informed us that he is no longer funded by any agency (including the University) to continue his work on the phosphorous labeling reagents; therefore, his work in this area was suspended, at least temporarily, in August. Dr. Verkade made it clear that unless he can acquire enough funding, including whatever we may provide, to support both a graduate student and a post-doctoral researcher for a full year, he would be unable to enter into a contractual agreement with us. This

would require about \$24,000/yr for the post-doc, \$14,000/yr for the graduate student and \$1,500/mo for supplies and instrument time. Both time and funding constraints prevent the Participants Program from supporting a full year of effort. Dr. Verkade indicated that Amoco has expressed an interest in funding a small project in the same line of research; however, there is no firm commitment at this time. If work were to proceed, Dr. Verkade would have to bring in two new researchers (a post-doc and a graduate student). There could be a learning curve for these two individuals to overcome before reliable data would be produced.

The method described allows for speciation of the labile hydrogen functional groups present in the sample. Individual species or classes of labile hydrogen functional groups can be quantitated by integration of the NMR signals. Assignments are all made by comparison to model compounds. Samples must be a liquid or soluble in a solvent such as pyridine.

Different phospholane reagents can be used depending on the information required. If speciation is desired, then one or more phospholane reagent can be employed which spreads the resulting NMR peaks out over a large delta value and allows for separate integration. Identification of the individual resonances is done by comparison to model compounds derivatized with the corresponding reagent. Since complete speciation requires comparisons with model compounds, it is only practical for distillable oils. This is because no model compounds are available for resid components. Iowa State already has run numerous model compounds related to distillates, though it may be desirable to expand that list. The lower limit of detectability is about 0.5% of the derivatizable compound in the sample.

If complete speciation of the components is not of interest, a reagent can be employed which derivatizes all the labile hydrogen but does not provide high resolution of the resulting NMR peaks. In that case, only compound classes are quantified. This procedure may be the best one to apply to resids because relevant model compounds are not available for complete speciation anyway. Dr. Verkade does not know the lower limit of quantitation for this variation of the method. Of course, compound class quantitation is also provided by the method that gives full speciation.

In both methods, the amount of water in the samples also is quantified. Iowa State has examined moisture in solid coal this way. Two different rates of reaction were measured as the phospholane reacted with a solid coal. Thus, two different kinds of water (roughly divided into strongly and weakly adsorbed) were measured.

It requires approximately two weeks to prepare a ten-gram batch of the phospholane tagging reagent. It requires 200 mg of sample per reaction. It was indicated that over the course of a five-month project, a total of twenty-five samples could be derivatized and examined (including full speciation), once the researchers were familiar with the methods. If full speciation is not required, more samples could be analyzed in the same amount of time.

The advantages of using the phospholane reagents and ^{31}P -NMR over other tagging/NMR methods based on nuclei such as ^{19}F and ^{29}Si were discussed. Both the ^{31}P and ^{19}F isotopes have 100% abundance, whereas ^{29}Si is only 4.7% abundant. The phospholane reagents will react at room temperature, reducing the possibility for alteration of the species being derivatized, this is not true with some other tagging reagents. After reaction with phospholanes, the ^{31}P nucleus is only one atom removed from the target heteroatom and thus provides excellent NMR resolution. With most other tagging reagents, the NMR nucleus is three atoms removed from the target heteroatom and NMR resolution is much poorer. This resolution advantage holds true even when the method is applied to quantitation of compound classes (as opposed to full speciation). Dr. Verkade notes that the resolution of the method may be compared with that of gas chromatography/mass spectrometry.

Available instruments include 200, 300 and 500 MHz Bruker NMRs that are communal property of the Chemistry Department. Dr. Verkade anticipates using the 200 and 500 MHz instruments in this program.

General Analytical Needs and Suggestions

The choice of ^{31}P reagent would have to be determined based on whether or not complete speciation or only compound class quantitation was required. To do speciation, model compound work would likely have to be done to add to the library already accumulated at Iowa State. It may be of some interest to examine a sample with and without mineral matter to determine if, and to what extent, the minerals cause signal broadening in the ^{31}P -NMR spectrum.

The meeting was continued as a further discussion of funding. We met with R. Markuszewski and W. Buttermore (Director and Associate Director, respectively) of Iowa State Mining and Mineral Resources Research Institute and R. Gaertner and R. Harris (Director and Associate Director, respectively) of the Iowa State Center for Advanced Technology Development and Dr. Verkade. We told Mr. Gaertner that we were interested in funding Dr. Verkade for this project and also that we could not possibly fund a one-year program. ISU-CATD will consider alternate sources for additional funding.

Follow-up

Iowa State will determine if enough additional funding can be found to allow this program to proceed and so notify CONSOL. We request such notification by November 21, 1991. Upon notification, we would expect to draft a Statement of Work for review by Dr. Verkade. A detailed cost proposal would then be requested of Dr. Verkade. The proposed work was projected to take approximately five months and to extend no later than July 31, 1992. Iowa State has no objection to a purchase order contract, as long as contractual terms and agreements are within the scope of Iowa State University policy. If contractual arrangements were complete, work could start in January, 1992.

Trip Report: University of Utah
Date of Visit: October 23, 1991
Address: University of Utah
210 Park Building
Salt Lake City, UT 84112
Principal Contact: Dr. Ronald J. Pugmire
Acting Vice President for Research
Phone: (801) 581-7236

Attendees:

University of Utah
R. J. Pugmire

CONSOL
R. A. Winschel
S. D. Brandes

DISCUSSION

CONSOL Introduction

The project objectives and approaches were briefly discussed. The proposal made to CONSOL by Dr. Pugmire of the University of Utah (July 29, 1991) deals with the use of solid-state and high-resolution ^{13}C nuclear magnetic resonance (NMR) spectroscopy for the analysis of coal-derived resids. We told Dr. Pugmire that what originally interested us in working with him was the possibility of obtaining a set of molecular structure descriptors on liquefaction resids in a manner similar to those obtained and reported by him for coals.¹ With such data, one might be able to begin understanding the molecular properties that determine resid reactivity and process operating conditions which affect resid reactivity.

University of Utah Interest

Dr. Pugmire described some work done by him with tar/char pairs obtained from the Sandia National Laboratory pyrolysis reactor. In that work, various Argonne premium coals were pyrolyzed using a very rapid temperature/time program. The chars produced at different temperatures were examined by solid-state ^{13}C -NMR and the various molecular structure descriptors¹ were obtained. The aromatic-ring cluster sizes of all the char samples examined, regardless of feed coal, converged at high pyrolysis temperatures. Dr. Pugmire expressed concern that liquefaction

materials might exhibit the same convergence of properties and therefore show no differences. We speculated that such behavior would not occur in liquefaction because of the much milder and varying operating conditions. Also, we already know that the materials in our sample bank have a great variation in numerous properties.

By use of various chemical descriptors obtained from solid-state ^{13}C -NMR (bridge-head carbons, pendant groups, etc.) and a chemical percolation devolatilization model, the researchers at Utah have been able to predict how the molecular structure of the coal will break apart in pyrolysis. In this manner, they can predict pyrolysis yields. They are currently working to extend their model to coal liquefaction.

We toured Dr. Pugmire's laboratory and we were introduced to Anita Orendt and Mark Solum (both post doctoral fellows at the University) and Prof. David Grant. Dr. Pugmire's group has numerous NMRs at their disposal including a Bruker 100 MHz (usually used for coals), a Varian VXR-200, and a Varian VXR-500 high-resolution instrument. A new ChemSystems instrument will be delivered soon. A Varian VXR-500 would probably be used for any high-resolution work for this project. We also saw various NMR accessory equipment such as a special zirconia spinner that can contain 1.4g samples for single-pulse work. This spinner was claimed to be superior to Maciel's Delrin spinner because it generates no background interference signal. With this spinner, an excellent SP spectrum can be generated in 12 to 24 hr. The discussion continued concerning the best way to handle the coal liquefaction process-derived resids.

The methods for obtaining ^{13}C -NMR chemical descriptors from coals, chars and other solids are well developed. However, the methods for obtaining this information on tars, pitches and liquefaction resids and oils are not fully developed. Those materials are not true solids; they have enough molecular mobility that it may be difficult to obtain accurate structural parameters (e.g., aromatic-ring cluster size) when using the methods used with coals. Three approaches for overcoming this potential problem were outlined by Dr. Pugmire. The first is to use the solid-state cross polarization/magic angle spinning (CP/MAS) technique, as used with coals, but to include different relaxation responses for each different carbon type to sort out protonated, non-protonated, bridgehead, etc. carbons. The second approach is to use the solid-state single-pulse (SP) Bloch-decay method. In both solid-state cases, the sample could be run at reduced temperature (perhaps -50°C). At low temperatures, the NMR peaks broaden and the sample behaves more solid-like. The third approach is to abandon solid-state NMR altogether and use high-resolution solution techniques. A potential fourth approach was discussed, in which the spectrum is obtained while the sample is contacted with a supercritical solvent to significantly narrow the NMR line width; however, this approach is in its infancy.

Dr. Pugmire noted that he also holds a professorial position at Brigham Young University. He also has a Varian VXR-500 instrument there. One of his BYU students currently is using that instrument for coal-related high-resolution ^{13}C -NMR work. He indicated that, if we decide to use the high-resolution method for this work, he may prefer to perform it at BYU.

General Analytical Needs and Suggestions

The single best method (CP/MAS, SP or high-resolution) to examine the coal-derived resids still needs to be determined. We must still determine if the two solid-state methods can be used with samples containing mineral matter and insoluble organic matter. The high-resolution method is only applicable to soluble samples. Chloroform or methylene chloride are Utah's preferred solvents, although THF could be used. Pyridine is not a desirable solvent. The Utah researchers are quite confident that at least one of these methods would be able to provide the molecular structure descriptors we desire. We recommend that this concept be pursued through a teaming arrangement with the University of Utah.

Recommendations

It generally was agreed that the CP/MAS and SP solid-state and high resolution-liquid ^{13}C -NMR techniques would be used for the analysis of a single THF-soluble 850°F+ distillation resid sample to be chosen by CONSOL before we enter into an agreement. This would allow the Utah researchers to select the best method for analysis of this type of sample and to better anticipate their costs for any teaming arrangement with CONSOL. This one experiment will help determine the approach, complexity, and number of samples for a possible subcontract.

Follow-up

CONSOL will ship approximately 3g of the sample discussed above as soon as possible. Upon Utah's examination of this sample by solid-state and high resolution liquid ^{13}C -NMR techniques, a further discussion will be held by phone to decide the appropriate course of action to take with coal liquefaction process-derived samples. If the high-resolution method is chosen as the best, arrangements may be made with BYU rather the University of Utah. CONSOL will then prepare a more detailed program (a draft statement of work) for the examination by ^{13}C -NMR of coal liquefaction process-derived samples for review and comment by Dr. Pugmire and his associates based on the findings of their investigation of the one sample as described above, the University of Utah proposal, and this meeting. A detailed cost proposal then will be requested of Dr. Pugmire. The proposed work will extend no later than July 30, 1992. Costs were projected to be less than \$25,000. Approximately ten samples will be examined in the program, although the exact number will depend on the findings of the work with the one sample described above. There were no objections to a purchase order contract, as long as contractual terms and agreements were within the scope of University of Utah policy. If contractual arrangements were complete, work could start in December 1991.

1. Solum, M. S.; Pugmire, R. J.; Grant, D. M. *Energy & Fuels* 1989, 3, 187.

END

**DATE
FILMED**

6 / 24 / 92