PARTIAL CONTROL OF COMPLEX PROCESSING SYSTEMS

PROGRESS REPORT

For the Period May 15, 1992 to September 14, 1993

Prepared for

**THE U. S. DEPARTMENT OF ENERGY
DE-FG02-91ER14221**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

**Prepared by:
Professor Reuel Shinnar
Principal Investigator
Department of Chemical Engineering
The City College of CUNY
Convent Avenue @ 138th Street
New York, NY 10031**

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

ja

Partial Control of Complex Chemical Plants
Summary of Work for the Period 9/15/92 to 9/14/93

Reuel Shinnar and Irven Rinard
Dept. of Chemical Engineering, The City College of New-York.
DOE Contract #: DE-FG02-91-ER14221

This last year saw substantial advances in the development of our model of Fluidized Catalytic Crackers (FCC's). It now allows us to calculate both the steady state and dynamic behavior of the system with sufficient detail and reliability to provide a proper basis for our control studies. The model has been compared to actual results.

While there are suitable models in existence, these are proprietary. No model of sufficient detail for both the reactor and the regenerator has been published in the open literature. Regrettably, substantial detail is necessary. The simplifying assumptions generally used in the published models obscure important control features of the system. This in turn makes it difficult to understand why people operate present FCC's the way they do.

Our goal here is twofold. One is to understand FCC control, an important goal in itself as the FCC is the kingpin of the modern refinery. The new specifications for environmentally acceptable fuels increase the need to control the product composition of the FCC.

Our second goal is to use the FCC example to teach and learn about the control problems of complex chemical plants. The FCC control problem is rich enough to contain many of the nonlinear features found in such plants. It also is a good example of partial control as the number of product specifications and process constraints is far larger than the number of manipulated variables available [1].

Nonlinear features are very important in such plants. They may exhibit multiple steady states, instabilities, limit cycles and other typical nonlinear behavior. While linearized transfer functions are often sufficient to describe the dynamic behavior, these linearized transfer functions can change dramatically from one operating region to the next. Such systems can also have input multiplicities.

Our first goal was to elucidate these nonlinear features using our model. It is well known that FCC's have multiple steady states [2] but there has been no work to describe their topology or the impact of design, operating conditions, catalysts, promoters, and feed properties on the existence of such states.

This work is being finished. A paper describing it is going to be given at the AIChE meeting in St. Louis this November and will also be submitted for publication. The basic results are summarized in the paper given at Argonne.

Every FCC, being an adiabatic reactor, has three steady states when it operates at a useful operating point. However, due to the nature of the CO to CO₂ reaction in the regenerator, there is a potential for five steady states. Experience and our model show that this can occur within the range of practical operating conditions. Some of these multiple steady states are very close together which would give difficulties in control. Modern active catalysts and the desire for higher octane have made this more likely.

Our model shows that adding a combustion promoter that catalyzes the CO - CO₂ reaction reduces the chances for multiple steady states within the range of desirable operating conditions. By adding enough promoter, one can also eliminate them. This is illustrated in Figure 1 and 2 for a typical case. Figure 1 shows the different stability regions for a specific example without a promoter. Figure 2 shows the impact of the promoter, which reduces

the chance for 5 steady states to occur. Our results show that present operating trends with modern catalysts increase the likelihood to operate in the region where five steady states could occur. This has been observed and our results suggest ways to solve these problems, that sometimes arise.

Figure 1: Multiple Steady States in FCC.

Figure 2: Effect of Promoter on Multiple Steady States.
(18.5 x unpromoted combustion rate).

We have also shown that the conventional control structure can lead to input multiplicities as shown in Figure 3. In FCC control the number of manipulated variables available depends on the design. However several combinations of measured variables are available. Several recent papers [3,4] have discussed the impact of the control matrix chosen with the speed of the response. This approach totally neglects input multiplicities and the fact that a control scheme preferable at one operating condition may be useless in a different operating range. A paper being presently worked on will discuss these results in detail.

Figure 3: Input Multiplicities in Riser Temperature and Air/Oil. Triser=980 F, ----- stable, - - - - unstable

This prepares the stage for the next phase of our work, namely, how to deal simultaneously with all the specifications and constraints with a limited number of available inputs.

References

- 1) Shinnar, R., "Chemical Reactor modelling For Purposes of Controller Design," **Chem. Eng. Commun.**, Vol 9, pp. 73-99, (1981).
- 2) Edwards, W.M., and Kim, H.N., "Multiple Steady States in FCC Unit Operations," **Chem. Eng. Sci.**, Vol 43, No. 8, pp. 1825-1830, (1988).
- 3) Balchen, J.G., Ljungquist, D. and Strand, S., " State-Space Predictive Control," **Chem. Eng. Sci.**, Vol 47, No 4, pp. 787-807, (1992).
- 4) Hovd, M. and Skogstad, S., "Controllability Analysis for the Fluid Catalytic Cracking process," Presented at the AIChE Meeting, Los-Angeles, paper 145g (1991).

Publications

- 1) Shinnar, R., Morari, M., Doyle, F., "Design Considerations for Tubular Reactors with Highly exothermic Reactions," **AIChE Journal**, Vol. 38, No. 11 (1992).
- 2) Farrell, R.J., and Rinard, I.H., "A Comparison of Sequential and Simultaneous Modular Convergence of Complex, Tightly - Recycled Flowsheets," **Chemical Engineering Communications** (accepted for publication).
- 3) Arbel, A., Huang, Z., Rinard, I. and Shinnar, R., "Multiple Steady States in Fluidized Catalytic Cracker". Paper accepted for presentation at the AIChE meeting in St. Louis, November 1993.

END

DATE
FILMED

6 / 8 / 93