WSRC-TR---90-336

DE92 013360

TECHNICAL STUDIES ON A COMPOSITE GROUNDWATER SAMPLE FROM F- AND H-AREA (U)

WSRC Contact:

G. F. Stejskal

Westinghouse Savannah River Company
Savannah River Laboratory
Aiken, South Carolina 29808

This is a technical report

This report was prepared in connection with work done under Contract No. DE-AC09-89SR18035 with the U.S. Department of Energy. By acceptance of this paper, the publisher and/or recipient acknowledges the U.S. Government's right to retain a nonexclusive, royalty-free license in and to any copyright covering this paper, along with the right to reproduce and to authorize others to reproduce all or part of the copyrighted paper.

MASTER

ck
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by the trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

WESTINGHOUSE SAVANNAH RIVER COMPANY
SAVANNAH RIVER LABORATORY

WSRC-TR-90-336

Keywords: F/H
Seepage Basins,
Groundwater Remediation,
Surface Treatment,
Precipitation, Ion Exchange

Retention time: Permanent

August 15, 1990

TO: D. L. FISH, 773-A

FROM: J. P. BIBLER, 773-A *JPB*

**TECHNICAL STUDIES ON A COMPOSITE GROUNDWATER
SAMPLE FROM F- AND H-AREA (U)**

INTRODUCTION

A composite sample of groundwater from F- and H-Areas was collected by Waste Management Tech and delivered to the Savannah River Laboratory to use in preliminary experiments that would test three remediation technologies under consideration. The three technologies are pH adjustment and filtration, decontamination with a strong acid ion exchange resin, and decontamination with a chelating ion exchange resin.

SUMMARY

The composite was pH adjusted to 6, 7, 7.5, and 8 from 3.3. A small amount of precipitate formed at each pH, the greatest amount of material coming out of solution at pH 8. Calculations based on the mass of precipitate formed per liter at pH 8 show that only 4 grams of solids would be recovered per gallon of composite treated. Of that amount, however, approximately 3.6 g would be due to incorporated water and only 0.4 grams would be due to inorganic solids. RCRA metals were precipitated by increasing the pH of the solution.

Treating the composite with a strong acid ion exchanger removes cations in solution and replaces them with, in this study, sodium ion. Similarly, treating the composite with a chelating ion exchange resin exchanges polyvalent cations for sodium. A small column of a strong acid resin and another containing a chelating resin were used to process samples of the composite. The strong acid resin was not exhausted until approximately 300 column volumes of composite had been processed. The chelating resin did not behave satisfactorily with this feed; ionic components were concentrated chromatographically on the column, giving concentration surges, greater than influent concentrations, in the effluent when breakthrough occurred. Both resins were eluted with 0.1 M nitric acid. Elutions curves showed that 30 column volumes of the acid were insufficient for the complete regeneration of both resins. Either more concentrated acid or larger elution volumes would be necessary to elute the resins.

pH ADJUSTMENT STUDIES

One liter samples of the F/H composite solution were pH adjusted to 6, 7, 7.5, and 8, respectively, using 0.1 M NaOH. The original pH of the composite was 3.3. A glass electrode was standardized using a pH 7 buffer. Table 1 lists the concentration of ionic species in the composite before and after pH adjustment and filtration through a 0.45 μ m filter. Solids were allowed to air dry over night (approximately 12 hours) before weighing.

The amount of precipitate formed per liter is given in Table 2. When computed on a per gallon basis, the expected mass of precipitate from each of the pH values would be 0.37 g at pH 6, 0.081 g at pH 7, 1.2 g at pH 7.5, and 4.2 g at pH 8.

The precipitation at pH 8 was repeated because of the anomalously high precipitate mass for that sample relative to the others. Also, filtrate analyses could not account for the mass of the precipitate. One liter of composite was pH adjusted to 8.1 with 0.1 M NaOH. The mixture was filtered using a weighed 0.45 μ m filter. After drying overnight, the precipitate and filter were weighed. Analyses of the feed composite and filtrate for this sample were essentially identical to those for the earlier pH 8 adjustment study. The precipitate, which was still noticeably damp, weighed 1.2130 g. After drying in an oven at 100°C for two hours the weight of this solid had reached a constant weight of 0.1100 g. Thus, about 91% of the weight of the precipitate was due to water. Filtration of one liter of pH adjusted composite using a 0.45 μ m filter required about 30 minutes.

Table 1. Precipitation Studies - DF's and Filtrate Analyses

SPECIES	Average Initial conc	pH 6 Filtrate conc	pH 6 DF Filtrate conc	pH 7 Filtrate conc	pH 7 DF Filtrate conc	pH 7.5 Filtrate conc	pH 7.5 DF Filtrate conc	pH 8 Filtrate conc	pH 8 DF Filtrate conc	Sulfide Filtrate conc	IN
Ca	14.576	14.049	1.0	13.703	1.1	13.961	1.0	12.599	1.2	10.249	1.4
Cd	0.607	0.005	1.4	0.004	1.8	0.004	1.8	<0.001	≥7	0.003	4.0
Co	0.071	0.059	1.2	0.042	1.7	0.049	1.4	0.009	7.9	0.012	6.4
Cu	0.034	0.004	8.5	0.008	4.3	0.013	2.6	0.002	17.0	0.014	3.4
Mg	4.405	4.252	1.0	4.205	1.0	4.110	1.1	3.86	1.1	3.056	1.5
Mn	1.161	1.033	1.1	0.887	1.3	0.901	1.3	0.428	2.7	0.115	10.2
Na	0.068	<0.020	234	0.040	1.7	0.036	1.9	0.04	1.7	0.077	1.2
Zn	0.234	0.123	1.9	0.075	3.1	0.057	4.1	0.029	8.1	0.005	43.6
Zr	0.052	0.006	8.7	0.010	5.2	0.016	3.3	<0.002	226	0.020	3.6
Al	29.12	0.05	582.4	3.911	7.4	0.200	145.6	0.717	40.6	4.281	6.8
Ba	0.21	0.203	1.0	0.018	11.7	0.201	1.0	0.111	1.9	0.069	3.2
Fe	0.067	0.005	13.4	0.032	2.1	0.007	9.6	0.004	16.8	0.010	6.2
La	0.076	0.03	2.5	0.021	3.6	0.031	2.5	0.009	8.4	0.037	2.7
Li	0.011	0.011	1.0	0.011	1.0	0.021	0.5	0.01	1.1	0.022	1.0
Mo	0.01	<0.004	22.5	0.006	1.7	<0.004	22.5	0.006	1.7	0.004	2.5
Na	57.305	131.53	0.4	136.110	0.4	135.590	0.4	140.28	-	229.790	-
N1	0.034	0.031	1.1	0.028	1.2	0.032	1.1	<0.005	26.8	0.021	2.0
Sn	0.025	0.01	2.5	0.014	1.8	0.009	2.8	<0.007	23.6	0.051	-
Sr	0.078	0.077	1.0	0.074	1.1	0.078	1.0	0.067	1.2	0.058	1.4
Ti	0.028	0.004	7.0	0.007	4.0	0.010	2.8	0.002	14.0	0.013	2.8
V	0.002	0.002	1.0	0.005	0.4	0.011	0.2	0.001	2.0	0.015	1.0
B	0.017	0.014	1.2	0.008	2.1	0.041	0.4	0.005	3.4	0.041	1.0
Cr	0.01	0.607	1.4	0.010	1.0	0.010	1.0	0.009	1.1	0.016	1.0
P	0.078	0.067	1.2	0.059	1.3	0.070	1.1	0.065	1.2	0.123	1.0
Si	13.355	4.851	2.8	4.832	2.8	4.475	3.0	2.326	5.7	2.384	5.8
U	0.7	0.000	2700	<0.003	2233	NA	-	0.003	233	NA	-
NO3	440	443	-	443	-	NA	-	445	-	NA	-

NA-not analyzed

Table 2. Mass of Precipitate Formed (Per Liter) on pH Adjustment of F/H Composite Groundwater

	<u>pH 6, g</u>	<u>pH 7, g</u>	<u>pH 7.5, g</u>	<u>pH 8, g</u>
Clean filter	69.1659	57.8681	36.1573	68.7072
Filter + precipitate	69.2638	57.8895	36.4711	69.8085
precipitate	0.0979	0.0214	0.3138	1.1013

A titration curve was determined using 20 mL of the composite groundwater and 0.1069 M NaOH. This is shown in Figure 1. To neutralize this groundwater, it will require $1.3 \text{ E-}2$ moles of NaOH per gallon of groundwater. Since most of the neutralization is done on site using 50% caustic (19 M) solutions, it is of interest to note that one gallon of 50% caustic could neutralize $5.5 \text{ E}+3$ gallons of groundwater.

Figure 1. F/H Composite Water Titration

PARTICLE SIZE ANALYSIS OF pH ADJUSTED COMPOSITE PRECIPITATES

Particle size distributions were studied using the Brinkman Model 2010 laser-based optical particle size analyzer. Table 3 lists the per cent of the total number of particles analyzed by the instrument in several particle diameter ranges. These data are all for scans made

in the 0.5-150 μm region. Particles have been suspended by stirring with a magnetic stirrer inside the analytical cuvette. The size of particles did not appear to change significantly with pH. Previous studies on hydroxide precipitates have shown, however, that flocculated precipitates can be broken up by the stirring motion of the stirring bar and the similarities may simply be a result of formation of a stable particle size within the cuvette.

Table 3. Number Distribution - Local Percentages of Total Recorded Particles

Range, μm	Local %				
	Composite Feed	pH 6	pH 7	pH 7.5	pH 8
0.0 - 1.0	27.68	42.57	21.82	25.26	30.34
1.0 - 2.0	36.02	32.57	29.29	29.41	27.42
2.0 - 3.0	14.60	11.62	19.21	17.98	16.25
3.0 - 4.0	9.09	6.31	13.79	12.11	12.39
4.0 - 5.0	5.78	3.69	7.99	7.05	7.30
5.0 - 6.0	3.47	1.72	4.33	3.95	3.44
6.0 - 7.0	1.32	0.75	1.66	1.87	1.72
7.0 - 8.0	0.77	0.35	0.85	0.80	0.40
8.0 - 9.0	0.38	0.19	0.33	0.46	0.26
9.0 - 10.0	0.20	0.13	0.26	1.24	0.15
10.0 - 20.0	0.62	0.09	0.44	0.75	0.26
20.0 - 30.0	0.04	0.00	0.02	0.07	0.06
30.0 - 40.0	0.01	0.01	0.00	0.04	0.02
40.0 - 50.0	0.00	0.00	0.01	0.00	0.00

PRECIPITATION USING SULFIDE

It was of interest to determine whether precipitation with sulfide would give better decontamination of heavy metals than precipitation with hydroxide. Therefore, a 1.0 M Na_2S solution was added to one liter of the composite groundwater sample until precipitation occurred. This required 40 mL of solution. The precipitate was collected on a weighed 0.45 μm filter, air dried for 12 hours, and weighed. Solids collected on the filter weighed 0.015 g. ICP analysis of the filtrate is given in Table 1. Sulfide precipitation was slightly more efficient than hydroxide precipitation for Ca^{2+} and Ba^{2+} but not as efficient for other ions, particularly Al^{3+} . The pH of the filtrate was 8.6 and this was higher than any of the hydroxide adjustment studies. The hydroxide concentration in the sulfide filtrate may have caused some of the metal hydroxides to begin to

redissolve. Precipitation using Na_2S added more than 1.5 times the amount of sodium ion to the system than that added by precipitation at pH 8 using NaOH .

RESIN SCREENING TESTS - Kd DETERMINATIONS

Seven commercially available resins were tested with F/H composite groundwater in batch experiments to determine distribution coefficients (K_d) for various ions in the composite. This screening test enabled the selection of one strong acid resin and one chelating resin for column experiments.

In the batch experiments, approximately 0.1 g of resin was shaken overnight with 15 mL of the composite. The system was presumed to be at equilibrium at that time. The equilibrium solution was then analyzed by ICPEES and K_d 's were calculated for each ion and each resin using the formula:

$$K_d = [(C_0/C-1) (v/g)]$$

where C_0 is the initial concentration of the ion in the groundwater, C is the equilibrium concentration of the ion, v is the volume of solution (15 mL), and g is the dry weight of resin used. In general, the larger the K_d , the better the resin will remove the ion. Thus, resins with the highest K_d 's overall for divalent cations were selected for column tests. Those resins were Dowex 50x8 and Chelex 100. The results from the K_d experiments are given in Table 4. The chelating resins tested were Chelex 100, TP-207, CR-10, and CR-20. The strong acid resins tested were Dowex 50x8, PK-228, and PK-216.

RESIN COLUMN TESTS

Dowex 50x8 Strong Acid Resin

A two-milliliter column of Dowex 50x8 resin in the sodium form was prepared in deionized water. The mass of the resin column was 1.543 grams. The diameter of the column was 0.354 inches. A total of 800 mL (400 column volumes) of F/H composite groundwater was processed downflow through the resin at a flow rate of 30 mL/hr. This represents 15 column volumes per hour and a linear flow rate of 2.9 gpm/ft². A more rapid flow rate was not possible because it would have required volumes of feed that the hood could not have accommodated. Effluent from the column was collected in 200-mL fractions and analyzed for total uranium by U-Chemcheck and other

Table 4. Average Kd Values for Eight Resins

Species	Average Kd, mL/g						
	Dowex 50X8	CR-20	CR-10	PK-216	TP-207	Chalex 100	PK-228
Ca	7.0E+4	1.2E+0	1.2E+4	3.1E+4	1.6E+4	6.3E+4	2.8E+4
Cd	≥9.0E+2	3.7E+2	≥3.8E+2	≥9.0E+2	5.9E+1	≥3.8E+2	≥3.8E+2
Co	≥2.5E+3	9.7E+1	2.5E+3	≥2.5E+3	1.6E+2	2.0E+3	≥2.5E+3
Cu	≥1.6E+3	≥2.4E+3	2.4E+3	≥5.0E+3	6.2E+1	2.0E+3	≥2.4E+3
Mg	1.4E+4	---	6.5E+3	2.6E+3	9.9E+3	9.3E+4	2.2E+4
Mn	2.5E+4	---	4.1E+4	4.3E+4	5.7E+2	1.7E+5	5.6E+2
Pb	≥3.0E+2	1.7E+2	≥3.6E+2	2.0E+2	1.8E+1	1.7E+2	≥3.6E+2
Zn	1.1E+2	8.3E+1	4.2E+2	1.0E+2	1.3E+2	2.9E+2	1.3E+2
Zr	≥3.8E+3	4.0E+2	≥3.8E+3	≥3.8E+3	3.3E+2	2.1E+3	≥3.8E+3
Al	7.8E+4	2.7E+2	5.4E+2	2.9E+4	1.8E+2	8.8E+2	3.0E+4
Ba	2.1E+2	4.6E+2	1.6E+4	---	4.1E+3	3.1E+4	3.1E+4
Fe	1.1E+3	1.3E+2	2.1E+2	5.4E+2	9.7E+2	4.7E+2	4.3E+2
La	1.9E+3	1.4E+2	2.1E+3	3.6E+3	2.6E+2	9.3E+2	1.2E+2
Li	1.8E+2	2.4E+1	1.8E+2	1.8E+2	1.5E+2	2.2E+2	1.3E+2
Mo	≥2.3E+2	1.2E+2	≥1.8E+2	≥2.3E+2	4.9E+1	≥6.4E+1	1.5E+2
Ni	≥8.7E+2	1.1E+2	≥8.7E+2	≥8.7E+2	1.3E+2	≥4.9E+2	≥4.9E+2
Sn	≥3.9E+2	1.6E+2	≥3.7E+2	≥3.9E+2	7.7E+1	≥1.2E+2	≥1.0E+2
Sr	≥1.2E+4	---	1.2E+4	≥3.0E+3	5.6E+3	1.2E+4	1.2E+4
Ti	1.2E+3	4.1E+2	8.9E+2	1.9E+3	2.3E+2	7.8E+2	1.4E+3
B	2.0E+2	4.6E+1	1.6E+2	1.2E+4	≥4.9E+2	≥4.9E+2	≥4.9E+2
Cr	≥2.3E+2	≥6.4E+1	≥2.3E+2	≥1.5E+2	≥2.3E+2	1.5E+2	1.5E+2
P	8.1E+1	2.1E+2	3.9E+1	6.6E+1	4.3E+1	1.1E+2	9.1E+1
Si	2.6E-1	1.1E+2	1.0E+2	8.2E-1	7.9E+1	4.7E+1	7.6E-1

cations by ICPEs methods. The column appears to begin to experience breakthrough for most ions at about 300 column volumes throughput. The results from the column run are given in Table 5 and are shown graphically for a representative ion, Ca^{2+} , in Figure 2. It is evident from Table 5 that the other ions begin to break through at about the same throughput.

Figure 2. Calcium Ion Breakthrough on Dowex 50x8

The column was then eluted downflow at 30 mL/hr flow rate using 60 mL of 0.1 M HNO_3 . Six 10-mL elution fractions were collected and analyzed for Hg by atomic absorption, total U by Chemcheck, and cations by ICPEs. The results of these analyses are found in Table 6 and are shown graphically in Figure 3 for the sodium ion.

Figure 3. Elution of Na^+ from Dowex 50x8

Table 5. Dowex 50x8 Column Run Effluent Concentrations

SPECIES	Average Feed. ppm	Treated Effluent			
		First 100 CV. ppm	Second 100 CV. ppm	Third 100 CV. ppm	Fourth 100 CV. ppm
Ca	14.58	0.101	0.19	0.43	1.80
Cd	0.01	<0.001	<0.001	<0.001	0.00
Co	0.07	<0.004	<0.004	<0.004	0.01
Cu	0.03	<.003	0.00	0.00	0.01
Mg	4.41	0.015	0.05	0.20	0.97
Mn	1.16	0.004	0.01	0.05	0.22
Pb	0.07	0.057	0.02	0.04	0.02
Zn	0.23	0.015	0.01	0.04	0.17
Zr	0.05	0.002	<0.002	0.00	0.00
Al	29.12	0.153	0.20	0.49	1.05
Ba	0.21	0.003	0.00	0.01	0.01
Fe	0.07	0.009	0.01	0.01	0.01
La	0.08	0.003	0.00	0.01	<0.003
Li	0.01	0.003	0.01	0.01	0.02
Mo	0.01	<0.004	0.01	<0.004	<0.004
Ni	0.03	0.005	0.01	0.01	0.01
Sn	0.03	0.007	0.01	<0.007	0.02
Sr	0.08	0.001	0.00	0.00	0.01
Ti	0.03	0.002	0.00	0.00	0.00
V	0.00	0.001	0.00	0.00	0.00
B	0.02	0.153	0.18	0.20	0.23
Cr	0.01	0.004	0.01	<0.004	<0.004
P	0.08	0.033	0.04	0.03	0.03
Si	13.36	14.397	14.245	13.96	14.72
U	0.7	<0.01	<0.01	0.020	0.090
Hg	<0.01	<0.01	<0.01	<0.01	<0.01

Table 6. Dowex 50x8 Elution With 0.1 M HNO₃

SPECIES	Average Feed PPM	Elution Fraction					10 mL Samples, 5 CV				
		#1. PPM	#2. PPM	#3. PPM	#4. PPM	#5. PPM	#1. PPM	#2. PPM	#3. PPM	#4. PPM	#5. PPM
Ca	14.58	19.779	49.58	31.65	27.91	25.71	23.27				
Cd	0.01	<0.010	0.02	<0.010	0.02	<0.010	<0.010				
Co	0.07	0.116	0.326	0.22	0.18	0.02	0.16				
Cu	0.03	0.075	0.16	0.13	0.1	0.09	0.08				
Mg	4.41	10.664	25.21	19.2	16.88	15.39	13.99				
Mn	1.16	2.228	5.58	4.1	3.64	3.33	3.03				
Pb	0.07	<0.020	0.26	<0.020	<0.020	<0.020	<0.020				
Zn	0.23	1.131	1.51	1.44	1.39	1.31	1.26				
Zr	0.05	<0.020	<0.020	<0.020	<0.020	<0.020	<0.020				
Al	29.12	18.042	36.64	10.77	7.26	5.19	4.33				
Ba	0.21	0.067	0.19	0.08	0.06	0.05	0.04				
Fe	0.07	0.054	0.16	0.08	0.1	0.32	0.11				
La	0.08	<0.030	<0.030	0.1	<0.030	<0.030	<0.030				
Li	0.01	0.046	0.02	<0.030	<0.008	<0.008	<0.008				
Mo	0.01	<0.040	<0.040	<0.008	<0.040	<0.040	<0.040				
Na	57.31	712.18	878.7	309	108.53	32.49	9.04				
Ni	0.03	0.066	0.13	0.11	0.06	0.08	<0.050				
Sn	0.05	<0.070	<0.070	<0.070	<0.070	<0.070	<0.070				
Sr	0.08	0.075	0.2	0.11	0.09	0.09	0				
Ti	0.03	<0.010	0.02	<0.010	<0.010	<0.010	<0.010				
V	0.00	<0.010	<0.010	<0.010	<0.010	<0.010	<0.010				
B	0.02	<0.040	<0.040	<0.040	<0.040	<0.040	<0.040				
Cr	0.01	<0.040	0.06	<0.040	<0.040	<0.040	<0.040				
P	0.08	0.174	0.5	0.45	0.35	0.16	0.16				
Si	13.36	9.964	0.35	0.3	<0.060	<0.050	<0.060				
U	0.7	2.3	8.4	6.3	5.9	5.3	5.2				
Hg	<0.01	<0.010	<0.010	<0.010	<0.010	<0.010	<0.010				

It is apparent from Table 6 that, although the monovalent ions, such as Na^+ , elute well in 0.1 M HNO_3 , the polyvalent ions, for example Al^{3+} , UO_2^{2+} , and Mn^{2+} , do not.

Chelex 100 Chelating Resin

A two-milliliter column of Chelex 100 resin in the sodium form was prepared in deionized water. The mass of the resin column was 0.978 grams. The diameter of the column was 0.354 inches. A total of 1600 mL (800 column volumes) of F/H composite groundwater was processed downflow through the resin at a flow rate of 30 mL/hr. This represents 15 column volumes per hour and a linear flow rate of 2.9 gpm/ft². Once again, a more rapid flow rate was not possible because it would have required volumes of feed that the hood could not have accommodated. Effluent from the column was collected in 200-mL fractions and analyzed for total uranium and cations by ICPEs and U-Chemcheck methods. The results from the column run are given in Table 7 and are shown graphically in Figure 4 for Ca^{2+} , a representative ion.

Figure 4. Calcium Ion Breakthrough on Chelex 100

In addition to early breakthrough, the polyvalent ions appear to be concentrating in chromatographic bands before breaking through since they emerge from the column in much higher concentrations than in the feed. A chelating resin does not give good decontamination with this groundwater.

The column was then eluted downflow at 30 mL/hr flow rate using 60 mL of 0.1 M HNO_3 . Six 10-mL elution fractions were collected and analyzed

Table 7. Chelex 100 Column Run Effluent Concentrations

SPECIES	Average Feed. ppm	Treated Effluent							
		First 100 CV. ppm	Second 100 CV. ppm	Third 100 CV. ppm	Fourth 100 CV. ppm	Fifth 100 CV. ppm	Sixth 100 CV. ppm	Seventh 100 CV. ppm	Eighth 100 CV. ppm
Ca	14.58	0.014	0.01	39.00	20.72	17.68	16.33	16.946	17.58
Cd	0.01	<0.001	<0.001	0.01	0.02	0.01	0.01	0.009	0.011
Co	0.07	<0.004	<0.004	0.05	0.11	0.06	0.05	0.055	0.075
Cu	0.03	<0.001	<0.001	0.00	0.00	0.00	<0.001	0.003	0.012
Mg	4.41	0.001	0.00	13.23	4.92	5.42	5.00	5.231	5.312
Mn	1.16	<0.000	<0.000	1.86	2.79	1.42	1.30	1.329	1.405
Pb	0.07	0.034	<0.020	0.03	0.02	0.05	0.06	0.088	0.123
Zn	0.23	0.026	0.01	0.21	0.34	0.23	0.24	0.234	0.259
Zr	0.05	<0.002	<0.002	<0.002	0.01	0.03	0.05	0.067	0.079
Al	29.12	2.588	0.01	0.90	10.28	22.11	26.06	28.102	30.539
Ba	0.21	<0.000	<0.004	0.54	0.32	0.26	0.24	0.249	0.255
Fe	0.07	0.005	<0.002	0.01	0.01	0.01	0.01	0.014	0.019
La	0.08	<0.003	<0.003	0.01	0.01	0.03	0.06	0.091	0.12
Li	0.01	<0.001	0.01	0.02	0.61	0.01	0.01	0.011	0.017
Mo	0.01	<0.004	<0.004	0.00	0.01	0.03	0.01	0.009	0.014
Ni	0.03	<0.005	0.01	0.03	0.02	0.01	69.01	0.017	0.026
Sn	0.03	0.008	0.01	0.01	0.01	0.03	0.01	0.027	0.027
Sr	0.08	<0.000	<0.000	<0.001	0.10	0.10	0.02	0.094	0.095
Ti	0.03	<0.001	<0.001	0.00	0.00	0.01	0.09	0.025	0.035
V	0.00	<0.001	<0.001	0.09	0.003	0.00	0.02	0.003	0.008
B	0.02	0.036	0.04	0.02	0.138	0.25	<0.001	0.167	0.121
Cr	0.01	<0.004	<0.004	0.04	0.01	0.01	0.23	0.011	0.016
P	0.08	0.019	0.03	13.95	0.04	0.04	0.04	0.42	0.224
Si	13.36	13.425	14.047	13.96	13.93	16.75	15.50	15.306	16.097
U	0.7	NA	NA	NA	NA	<0.01	<0.01	<0.01	<0.01

NA=not analyzed

for Hg by atomic absorption, total U by Chemcheck, and cations by ICPEs. The results of these analyses are found in Table 8 and are shown graphically in Figure 5 for the sodium ion. The resin does not elute efficiently with acid of this concentration.

Figure 5. Elution of Na⁺ from Chelex 100

DISCUSSION

Precipitation by pH adjustment to values from 6-8 effect formation of few solids. Approximately 3.4×10^{-3} moles of NaOH per liter of groundwater (1.3×10^{-2} moles/gallon) were required to raise the pH to 8. The hydroxide precipitates are gelatinous in nature and are not easily filtered through a $0.45 \mu\text{m}$ filter. Although the mass of precipitate produced increased on going from pH 6 to 8, it was demonstrated, by heating to dryness in an oven, that the increase was due to the mass of water that had been incorporated in the gel and not the mass of salts precipitated. Since filtration was very slow, alternative separation methods, such as centrifugation or decantation, should be studied. The properties of the precipitate would indicate that it will require dewatering after separation.

Treatment of the groundwater using sodium sulfide does effect precipitation as well as pH elevation of the solution. There are several arguments against the use of sulfide as a precipitating agent for this groundwater which must be considered. The final pH, at which precipitation took place, was 8.55, slightly above the drinking water maximum of 8.5. The concentrations of Cd^{2+} , Pb^{2+} , and total chromium in solution after sulfide precipitation are essentially the same or greater as those when NaOH was used as a precipitating agent,

Table 8. Chelex 100 Elution With 0.1 M HNO₃

SPECIES	Average Feed ppm	Elution Fraction			10 mL Samples, 5 CV		
		#1. ppm	#2. ppm	#3. ppm	#4. ppm	#5. ppm	#6. ppm
Ca	14.58	3.62	2.06	0.72	0.93	0.86	0.74
Cd	0.01	0.066	0.06	0.07	0.03	0.02	<0.010
Co	0.07	0.955	1.26	1.24	0.59	<0.040	<0.040
Cu	0.03	0.066	0.05	0.56	1.34	0.88	0.50
Mg	4.41	0.066	0.51	0.14	193.00	0.18	0.15
Mn	1.16	0.522	0.19	0.06	0.57	0.07	0.04
Pb	0.07	1.45	1.15	2.27	1.61	0.55	<0.200
Zn	0.23	2.4	3.76	3.90	3.98	2.02	1.93
Zr	0.05	0.86	0.80	1.09	0.78	0.13	<0.020
Al	29.12	667.4	686.60	709.80	462.65	78.94	18.27
Ba	0.21	0.098	0.04	0.04	0.01	0.01	<0.004
Fe	0.07	0.08	0.06	0.22	0.41	0.21	0.25
La	0.08	1.26	1.26	1.96	1.70	0.36	0.06
Li	0.01	0.028	0.01	0.03	<0.008	<0.008	<0.008
Mo	0.01	0.21	0.28	0.26	0.15	0.07	<0.040
Na	57.31	4.58	6.86	2.83	3.74	3.29	2.60
Ni	0.03	0.39	0.94	1.90	1.17	0.07	<0.050
Sn	0.03	0.42	0.45	0.59	2.25	0.09	<0.070
Sr	0.08	0.055	0.02	0.02	0.01	0.01	0.00
Ti	0.03	0.55	0.62	0.87	0.63	0.10	<0.010
V	0.00	0.022	0.02	0.06	0.01	<0.010	<0.010
B	0.02	<0.040	<0.040	<0.040	<0.040	<0.040	<0.040
Cr	0.01	0.64	<0.040	0.08	0.07	<0.040	<0.040
P	0.08	0.47	0.62	1.68	1.68	0.39	0.17
Si	13.36	2.46	1.80	1.68	0.63	0.51	0.31
U	0.7	<0.01	0.49	6.9	14.9	13.4	10.2
Hg	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01

indicating no significant benefit in heavy metal decontamination when using sulfide. Addition of Na₂S increased the sodium ion concentration in treated effluent much more (>1.5 times) than treatment with NaOH. The ultimate total sodium ion concentration in treated liquid may be a consideration. Finally, although the equilibrium concentration of H₂S in treated groundwater will be below the allowable drinking water concentration of 2 ppb¹, reinjection to a system that is at pH 3-4 will temporarily convert all available sulfide in the treated solutions to H₂S in concentrations in excess of that 2 ppb limit.

Processing composite groundwater through a strong acid resin such as Dowex 50x8 will remove all cationic species except hydrogen ion. Approximately 300 column volumes of feed were processed before breakthrough was apparent. Elution of the column with 30 column

volumes of 0.1 M HNO_3 was not efficient. Further elution studies should be made using more concentrated acid in order to optimize the complete regeneration of the column.

Chelex 100, a complexing ion exchange resin, did not perform well with the composite groundwater feed. The presence of many cation species resulted in a pronounced multicomponent effect^{2,3} wherein ions, once sorbed, concentrated in chromatographic bands before breaking through. Initial breakthrough concentrations of each ion were greater than feed concentrations. Elution of the saturated column with 30 column volumes of 0.1 M HNO_3 was not sufficient to completely regenerate the resin. If a chelating resin is to be considered for decontamination of this groundwater, more studies, including pH adjustment of the feed before ion exchange and different acid concentrations for elution, will have to be done.

QUALITY ASSURANCE

Data pertaining to this report can be found in WSRC-NB-89-106 on pages 92-110. The notebook is maintained in room B-132 of 773-A.

Chemical and radiochemical analyses were performed by Analytical Development Section (ADS) according to the ADS QA standards for "Routine Customer Assisted" analyses. The various techniques and methods are listed below:

<u>Method Number</u>	<u>Procedure Title</u>
ADS-2420	Gamma Sample Preparation and Analysis
ADS-2306	Analysis of solutions by Ion Chromatograph
ADS-2408	Tritium Extraction for Liquid Scintillation Analysis
ADS-2503	Cold Vapor Atomic Absorption for Hg
ADS-2506	Direct Elemental analysis by ICP-AES
ADS-2201	OIC-700 Total Carbon Analyzer
ADS-2405	Alpha and Beta Plate Making Direct Mount and Count
DPSOP 82-11	IP#89331 Rev 0 11/89 U-Chemcheck, Analytical Laboratories Separations Control Procedures

Particle size analyses were performed on a Brinkman Model 2010 laser-based computerized system for measuring particle size distributions. The system is self-calibrating but is also checked against a standard sample of 10 μm polyethylene spheres purchased from NASA (National Aeronautics and Space Administration) by ADS. The standard is maintained by A. Jurgensen of ADS.

An Orion Model 701A digital ionanalyzer equipped with a glass electrode was standardized using pH 4, 7, and 10 buffer solutions purchased from stores. Temperature corrections were made based on a calibrated thermometer⁴, BB-1, maintained in B-127 of 773-A.

REFERENCES

1. "Quality Criteria for Water", U.S. Environmental Protection Agency, Washington, D.C., pp. 213-215.
2. HELEFFERICH, F., and KLEIN, G., *Multicomponent Chromatography, Theory of Interference*, Marcel Dekker, Inc., New York, New York, 1970.
3. BIBLER, J.P., "Effects of Heavy Metals on Cation Exchange Proposed for the F/H Effluent Treatment Facility", DPST-86-521, June 20, 1986.
4. BIBLER, J.P., "Technical Studies on Cs Decon of the Organic Product Stream from the DWPF", WSRC-TR-90-295.

CC: W.L. Tamosaitis, 773-A

M.A. Ebra, 703-H

G.W. Becker, 703-H

K. Wierzbicki, 703-H

O.B. Wheat, 703-H

C.M. Lewis, 703-H

J.C. Guynn, 703-H

B.B. Looney, 773-42A

J.B. Gladden, 773-42A

R.H. Sentelle, CDC-North Augusta

D. Nix, CDC-North Augusta

~~P.N. Brandt, 703-A~~

~~M. McDerment, 703-A~~

G. Turner

S. R. Suroucha K, 703-A

ACTION ITEM

Action Initiator:

Meeting _____

Inspection _____

Telephone
Conversation _____

Other
(Explain) X _____

MAIL From IMD

Date: 2/20/92

Participants:

<u>Steve Horton</u>	_____	_____
<u>Ken Franken</u>	_____	_____
<u>Steve Wright</u>	_____	_____

ACTION DESCRIPTOR

Action From: ERD Action To: DEA Due Date: 2/4/92

Person Responsible: Steve Horton

Subject: WSRC - TR - 90 - 336

Action: Review + have Steve W. sign

END

DATE
FILMED

6/12/92