RECEIVED
DOE/PC/ETC

DEC 13 1992

DOE/PC/92147--1

DE93 013063

CATALYTIC MULTI-STAGE LIQUEFACTION OF COAL

FIRST QUARTERLY REPORT FOR THE PERIOD

8 DECEMBER 1992 - 31 DECEMBER 1992

A.G. Comolli
E.S. Johanson
L.K. Lee
R.H. Stalzer

**WORK PERFORMED UNDER CONTRACT
DE-AC22-93PC92147**

**HYDROCARBON RESEARCH, INC.
100 OVERLOOK CENTER, SUITE 400
PRINCETON, NEW JERSEY 08540**

JANUARY 1993

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

CATALYTIC MULTI-STAGE LIQUEFACTION OF COAL

FIRST QUARTERLY REPORT FOR THE PERIOD

8 DECEMBER 1992 - 31 DECEMBER 1992

A.G. Comolli
E.S. Johanson
L.K. Lee
R.H. Stalzer

**WORK PERFORMED UNDER CONTRACT
DE-AC22-93PC92147**

**HYDROCARBON RESEARCH, INC.
100 OVERLOOK CENTER, SUITE 400
PRINCETON, NEW JERSEY 08540**

JANUARY 1993

PRINTED IN THE UNITED STATES OF AMERICA

AVAILABLE FROM:

**National Technical Information Center
U.S. Department of Energy
5285 Port Royal Road
Springfield, Virginia 22161**

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Department of Energy, nor any of their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, mark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendations, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

TABLE OF CONTENTS	<u>PAGE</u>
ABSTRACT	1
SUMMARY	2
INTRODUCTION	3
Task 2 - Laboratory Scale Studies	4
Task 3 - Continuous Bench-scale Operations	4
Subtask 3.1	4
Subtask 3.2	4
Subtask 3.3	5
Subtask 3.4	5
Subtask 3.5	6
Subtask 3.6	6
Task 4 - Technical Assessment	7
Subtask 4.1 Process Modelling	7
Subtask 4.2 Economic Studies	7
TASK 1 - PROJECT MANAGEMENT PLAN	9

ABSTRACT

This quarterly report covers activities of Catalytic Multi-Stage Liquefaction of Coal during the period December 8 - December 31, 1992, at Hydrocarbon Research, Inc. in Lawrenceville and Princeton, New Jersey. This DOE contract period is from December 8, 1992 to December 7, 1994.

The overall objective of the program is to produce liquid fuels from direct coal liquefaction at a cost that is competitive with conventional fuels. Specifically, this continuous bench-scale program are provisions to examine new ideas in areas such as: low temperature pretreatments, more effective catalysts, on-line hydrotreating, new coal feedstocks, other hydrogen sources, more concentrated coal feeds and other highly responsive process improvements while assessing the design and economics of bench-scale results.

The quarterly report covers work on Project Management Plan, Laboratory Scale Studies, Continuous Bench-Scale Operations, Technical Assessment and Project Management/Administration.

SUMMARY

A new two-year contract to study novel concepts using Catalytic Multi-Stage Liquefaction in a Continuous Bench-Scale Operation commenced on December 8, 1992. A Project Management Plan was prepared and submitted for review in late December.

Planning of the first continuous bench run of the program is in progress.

INTRODUCTION

This is the first progress report of a two-year contract to evaluate novel process concepts for Direct Coal Liquefaction using the Catalytic Two-Stage process. The primary objective is:

- To produce liquid fuels from direct coal liquefaction at a cost that is competitive with conventional fuels.

The specific objectives of the program in Catalytic Multi-Stage Liquefaction of coal are to:

- Improve the effectiveness, use and to lower the costs of catalysts.
- Investigate coal pretreatment and low temperature hydrogenation.
- Test hydrogen sources and improve hydrogen management to reduce the cost of liquid fuels to less than \$30.00/bbl.
- Improve the quality and acceptability of fuels from direct liquefaction, addressing concerns of 1990 Clean Air Amendment.
- Evaluate coals of national interest and identify coals that have a good potential for easy liquefaction at mild conditions.
- Improve process energy efficiency and reduce carbon oxide emissions during processing.
- Provide data for base line design i.e. on-line hydrotreating and more concentrated feeds.
- Screen new concepts using continuous bench-scale units prior to the higher cost Proof of Concept demonstration.
- Provide input for the "Proof of Concept" Program

Following the preparation of a Project Management Plan in Task 1, the major effect of the contract falls into the following categories:

Task 2 - Laboratory Support

Microautoclave, microreactor and autoclave tests shall be carried out to support the operation of the continuous bench unit for the following applications:

- a. Pretreatments & low temperature activation.
- b. Coal feedstock evaluation.
- c. Catalyst qualification.
- d. Catalyst deactivation studies.
- e. Solvent quality testing.
- f. Product preliminary and reactivity testing.
- g. Process modelling combined with Bench-Scale results.
- h. Product hydrotreating and refining.

Task 3 - Continuous Bench-Scale Operations

About eight Bench-Scale Studies of about 14 days duration shall be conducted to define conditions of operations, and new process concepts. These runs will scout different catalysts, alternate feedstocks, on-line hydrotreating, various promoters, hydrogen sources and pretreatments, coal slurry feed compositions and other new concepts.

This task can be divided into the following sub-tasks:

Sub-Task 3.1 - Catalysis

Dispersed, soluble and supported catalysts have been used in coal liquefaction since the discovery of the technology. Research and Development activities are continuing in this area and new promising catalysts are becoming available. Present work with sub-bituminous coals and soluble molybdenum catalysts has shown promise and further testing is warranted. A Bench-Scale database on the comparison of various catalysts from more than 10 studies has been compiled.

Sub-Task 3.2 - Alternate Feed Stock Testing

Under DOE's Two-Stage Coal Liquefaction Programs, many coals have been evaluated; however, the majority of testing has been on Illinois #6 Burning Star and Pittsburgh #8 bituminous coal and Wyoming Clovis Pt. and Black Thunder sub-bituminous coals. Other coals briefly tested were Ohio 5/6 and New Mexico, McKinley Mine.

Coals of national interest that need to be evaluated utilizing the CTSL Technology are large reserves of high sulfur, high H/C ratio bituminous coals such as from Kentucky and West Virginia which will have low value under the new Clean Air Act of 1990. Also, the lignites and sub-bituminous western coals which have high reserves at low cost. Assessment of these alternate coals will also lead to improved understanding of the important feedstock properties on process performance.

Sub-Task 3.3 - On-Line Hydrotreating

On-Line hydrotreating has been shown to be an economic method of upgrading coal derived naphtha through the utilization of available hydrogen pressures. In previous experiments on low rank coals, nitrogen levels were reduced from 1300 ppm to less than 10 ppm, and sulfur from 230 to less than 15 ppm.

This work needs to be continued on both a laboratory and bench-scale and with high sulfur bituminous coals. A study is recommended, particularly, with a high sulfur Illinois or similar coal.

Data from this run could be utilized for the DOE Baseline Design and for scale-up to the Proof of Concept.

Sub-Task 3.4 - Promoters Hydrogen Sources and Pretreatments

The effects of various concentrations of light and heavy distillates, off gases (CO , CH_4 , CO_2 , H_2S & NH_3), additives (SO_2) and pretreatments (thermal or CO_2 , SO_2) have been studied to a very limited extent in continuous back-mixed systems. Knowledge of these effects with different coals and catalysts would be invaluable in direct liquefaction. H_2S addition has been found to improve conversion by as much as 50%, CO_2 improves coal conversion but also shifts to more gas and water production. Pretreatment with dispersed FeOOH and molybdenum salts also appears to enhance operability and yields.

A bench run using CO-H_2 Syngas as a lower cost feedstock is recommended since it has a 5 to 15% impact on capital costs.

Sub-Task 3.5 - Coal Slurry Feeds

The maximum allowable concentrations of coal in carrier solvent shall be determined through the optimization of the following parameters.

Coal particle size
Recycle solvent viscosity
Recycle solvent composition
Coal particle size distributions
Additives to reduce viscosity

Coal-Water slurries at concentrations of 70% are commercially pumpable through pipelines. Approaching this level of coal in oil as feed to direct liquefaction is a goal of this Task.

Sub-Task 3.6 - Process Improvements

This sub-task is directed to the evaluation of new concepts developed under DOE auspices or from other sources. Included may be ideas in the following areas:

- Introduction of soluble homogeneous catalysts in combination with dispersed and/or supported catalysts.
- The use of surfactants to increase diffusion and reaction rates for higher conversions at lower severity.
- A two-stage experiment with in-line hydrotreating and bottoms coking with recycle of coker liquids; incorporating some of process concepts tested at the Bortrap Pilot Plant in Germany.
- Tailored recycle streams - 1) Remove phenols and oxygenates from recycle oils, 2) extract nitrogen compounds, 3) introduce a light distillate that flashes at reactor conditions thus improving kinetics of coal and heavy oils.

Task 4 - Technical Assessment

Sub-Task 4.1 - Process Modelling

The test results of the program shall be evaluated in light of and in conjunction with previously published studies. Kinetic models developed in the current program will be extended to define the interrelationships among the product species and the operating parameters of the reaction stages. This effort shall be concurrent with the experimental work so that maximum guidance can be given to selection of specific test conditions through process simulation and kinetic modelling.

Sub-Task 4.2 - Economic Studies

The impact of process improvements as well as alternate coals tested for this program shall be quantified using HRI's base line economics models and current cost data. Sensitivity studies to include process modifications and improvements and different cost basis shall be included.

Current efforts to design and scale direct coal liquefaction processes have highlighted the need to determine the maximum feasible reactor size using currently available and new techniques. HRI's considerable experience in reactor design, new findings from the program and other current ASME standards shall guide the course of this study. These efforts will be coordinated with an update of the Direct Coal Conversion Base Line Design.

A schedule of these events over the next 24 months is shown in *Figure 1*.

FIGURE 1

TASK 1 - PROJECT MANAGEMENT PLAN

A Project Management Plan was prepared during December, 1992 and submitted for DOE review in January, 1993.

TASK 2 - LABORATORY SCALE STUDIES

TASK 3 - CONTINUOUS BENCH-SCALE OPERATIONS

TASK 4 - TECHNICAL ASSESSMENT

TASK 5 - PROJECT MANAGEMENT AND ADMINISTRATION

There was no activity on these four tasks during this reporting period.

END

**DATE
FILMED**

6 / 3 / 93