TRISOL

**DOE/PC/88874-T16(Vol.1)
(DE92013480)**

**THEORETICAL APPROACH FOR ENHANCED MASS TRANSFER EFFECTS
IN-DUCT FLUE GAS DESULFURIZATION PROCESSES**

Volume 1: Dry Sorbent Injection

Final Report

**By
Wojciech Jozewicz
Gary T. Rochelle**

January 29, 1992

Work Performed Under Contract No. AC22-88PC88874

**For
U.S. Department of Energy
Pittsburgh Energy Technology Center
Pittsburgh, Pennsylvania**

**By
Acurex Corporation
Research Triangle Park, North Carolina**

and

**University of Texas at Austin
Austin, Texas**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615)576-8401, **DTIC-OR-000000**.

Available to the public from the National Technical Information Service, U. S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

Theoretical Approach for Enhanced Mass Transfer Effects In-Duct Flue Gas Desulfurization Processes

Volume I: Dry Sorbent Injection

Final Report

Prepared for:

**DOE Project Manager
Richard E. Tischer
Environmental Control Division
Pittsburgh Energy Technology Center
U.S. Department of Energy
Pittsburgh, PA 15236**

**Under Contract No. DE-AC22-88PC88874
Date Prepared: January 29, 1992**

Prepared by:

**Wojciech Jozewicz
Acurex Corporation
Environmental Systems Division
4915 Prospectus Drive
P.O. Box 13109
Research Triangle Park, NC 27709**

and

**Gary T. Rochelle
University of Texas at Austin
Department of Chemical Engineering
Austin, TX 78712**

ABSTRACT

Based on fundamental mass transfer investigation in the short time differential reactor (STDR), gas phase mass transfer and chemical reaction steps could be excluded as rate limiting. This leaves solid phase diffusion as a rate limiting step in the reaction of Ca(OH)_2 with SO_2 under conditions of dry sorbent injection (DSI) into the duct. Global reactivity testing in the long time differential reactor (LTDR) revealed that the conversion of a given calcium sorbent was most strongly affected by the flue gas relative humidity. Given identical reaction conditions, conversion of the fly ash/ Ca(OH)_2 sorbent attained higher value than did the Mississippi Ca(OH)_2 . Recarbonation of Mississippi Ca(OH)_2 took place as a result of CO_2 presence in the flue gas and was enhanced by gas relative humidity and sorbent surface area. For practical range of CO_2 concentration (0-10 vol percent), the effect of CO_2 on reactivity of Ca(OH)_2 with SO_2 was insignificant. Novel techniques designed to enhance sorbent utilization that were investigated included sorbents with initial free moisture and grinding of DSI recycle material. Presence of initial free moisture significantly increased sorbent reactivity with SO_2 , compared with reactivity of sorbent with equilibrium amount of moisture. The initial free moisture content and corresponding level of maximum sorbent conversion with SO_2 varied with the surface area of the sorbent. A procedure was developed to measure the agglomeration of damp fly ash/ Ca(OH)_2 sorbents. Exceeding the critical moisture caused sorbent agglomeration. Critical moisture increased with sorbent specific surface area independently of fly ash type, grinding, and recycle materials. Under conditions of the STDR, dry ground recycle solids were significantly more reactive with SO_2 than unground solids. Pilot plant data indicated that the DSI recycle material lost its reactivity toward SO_2 after the first pass. Very little improvement in SO_2 removal was accomplished by DSI recycle downstream of the humidifier. Significant SO_2 removal enhancement was achieved for DSI recycle upstream of the humidifier.

TABLE OF CONTENTS

<u>Section</u>	<u>Page</u>
VOLUME I	
ABSTRACT	i
EXECUTIVE SUMMARY	1
E.1 Duct Injection Program Overview	1
E.2 Introduction	2
E.3 Experimental	3
E.4 Mass Transfer Testing	6
E.5 Novel Techniques	15
E.6 Conclusions	35
1. DUCT INJECTION PROGRAM OVERVIEW	38
2. INTRODUCTION	40
3. EXPERIMENTAL	44
3.1 Short Time Differential Reactor	44
3.2 Long Time Differential Reactor	47
3.3 Pilot Plant Facility	49
3.4 Baseline Sorbent Selection/Characterization	52
4. MASS TRANSFER TESTING	62
4.1 Verification of Rate Limiting Step	62
4.2 Investigation of Solid Phase Diffusion	75
4.3 Effect of Moisture on Reactivity	90
4.4 Effect of CO ₂ on Reactivity	91
4.5 Global SO ₂ Kinetics Testing	100
4.5.1 General Findings	100
4.5.2 Effect of Residence Time	103
4.5.3 Effect of Relative Humidity	104
4.5.4 Effect of Initial Sorbent Moisture	104
4.5.5 Effect of Sorbent Type	108
4.5.6 Effect of SO ₂ Concentration	111
4.5.7 Effect of Sorbent Accumulation over Time	111

TABLE OF CONTENTS (continued)

<u>Section</u>	<u>Page</u>
5. NOVEL TECHNIQUES	116
5.1 Moist Solids	116
5.1.1 Theory	116
5.1.1.1 Assumptions for Theoretical Development	116
5.1.1.2 Derivation	117
5.1.1.3 Effects of Equilibrium Reaction	119
5.1.1.4 Derivation of Modified Equilibrium Conversion Estimate	121
5.1.2 Long Time Differential Reactor Results and Discussion	122
5.1.2.1 Sorbents with Ambient Moisture	123
5.1.2.2 Sorbents with Initial Free Moisture	128
5.1.2.3 Comparison: Additive Model vs. Experiment	141
5.1.2.4 Comparison: Interactive Model vs. Experiment	148
5.1.2.5 Conversion of Fly Ash/ $\text{Ca}(\text{OH})_2$ Sorbent by Reaction with CO_2	159
5.1.3 Short Time Differential Reactor Results and Discussion	159
5.1.3.1 Effect of Sorbent Type	162
5.1.3.2 Combined Effect of the Amount of Initial Free Moisture and Sorbent Surface Area	169
5.1.3.3 Effect of the Approach to Saturation	178
5.1.3.4 Effect of Fly Ash Source	182
5.2 Solids Moisture Capacity	185
5.2.1 Introduction	185
5.2.2 Theory of Agglomeration	185
5.2.3 Approach	186
5.2.4 Results for Individual Reactants and Dry Mixtures	189
5.2.5 Results for Sorbents Prepared From Slurry	197
5.3 Recycle Operation	212
5.3.1 Dry-Sorbent Injection Downstream of Humidification	212
5.3.2 Dry-Sorbent Injection Upstream of Humidification	218
5.4 Grinding of Dry-sorbent Injection Material	221
5.4.1 Grinding of Spent $\text{Ca}(\text{OH})_2$	221
5.4.2 Grinding of Spent $\text{Ca}(\text{OH})_2$ /Fly Ash	222
6. DISCUSSION	225
7. CONCLUSIONS	228
8. REFERENCES	231

TABLE OF CONTENTS (continued)

<u>Section</u>	<u>Page</u>
VOLUME II	
ABSTRACT	i
EXECUTIVE SUMMARY	1
E.1 Introduction	1
E.2 Theory of SO ₂ Absorption in Ca(OH) ₂ Slurries	4
E.2.1 Basic Mass Transfer Principles	5
E.2.2 Enhancement Predicted by Surface Renewal Theory	6
E.2.3 Slurry Absorption Model	7
E.3 Experimental	9
E.3.1 Design of Reactor and Supporting Equipment	9
E.3.2 Mass Transfer Properties of the Stirred Tank Reactor	11
E.3.3 Comparison of Mass Transfer Properties of the Stirred Tank to that in a Slurry Droplet	18
E.4 Results of Experiments in Clear Solutions	18
E.4.1 Experimental Conditions	18
E.4.2 Enhancement in Water	19
E.4.3 Enhancement in 0.1 M CaCl ₂ Solution	19
E.4.4 Enhancement in 2.5 mM Ca(OH) ₂ Solution Containing 0.1 M CaCl ₂	20
E.4.5 Enhancement in 17 mM Ca(OH) ₂ Solution Containing 0.1 M CaCl ₂	20
E.4.6 Enhancement in Solutions of Varying Ionic Strength	21
E.5 Results of Experiments in Ca(OH) ₂ Slurries	24
E.5.1 Results of Slurry Experiments	24
E.5.2 Validation of Slurry Absorption Model For Ca(OH) ₂ Slurries	28
E.5.3 Discussion of Slurry Absorption Experiments	30
E.6 Computer Modeling	32
E.6.1 Model	32
E.6.2 Modeling Results	40
E.7 Conclusions and Recommendations	47
E.7.1 Mass Transfer Theory	53
E.7.2 Stirred Tank Reactor Experiments	53
E.7.3 Model Validation	54
E.7.4 Computer Modeling	54
1. INTRODUCTION	55
2. THEORY OF SO ₂ ABSORPTION IN Ca(OH) ₂ SLURRIES	63
2.1 Basic Mass Transfer Principles	64
2.1.1 Mass Transfer Coefficients	64
2.1.2 Enhancement of Absorption With Reaction	65

TABLE OF CONTENTS (continued)

<u>Section</u>	<u>Page</u>
2.1.3 Gas Film Resistance	66
2.2 Enhancement Predicted by Surface Renewal Theory	67
2.2.1 Enhancement in Water	68
2.2.2 Enhancement in CaCl_2 Solution	69
2.2.3 Enhancement in Dilute $\text{Ca}(\text{OH})_2$ Solutions	70
2.3 Slurry Absorption Model	72
2.3.1 Absorption With Reaction	73
2.3.2 $\text{Ca}(\text{OH})_2$ Solids Dissolution	73
2.3.3 CaSO_3 Crystallization	74
2.3.4 Inputs to the Model	74
2.3.5 Model Output	76
3. EXPERIMENTAL	78
3.1 Design of Reactor and Supporting Equipment	78
3.1.1 Agitation	81
3.1.2 System Improvements	82
3.1.3 Gas Phase Analysis and Material Balance	84
3.1.4 Liquid Phase Analysis	86
3.2 Mass Transfer Properties of the Stirred Tank Reactor	87
3.2.1 Gas Film Mass Transfer Properties	87
3.2.1.1 Experimental Results	88
3.2.1.2 Discussion	93
3.2.2 Liquid Film Mass Transfer Properties	96
3.2.2.1 Experimental Results	97
3.2.2.2 Discussion	103
4. RESULTS OF EXPERIMENTS IN CLEAR SOLUTIONS	107
4.1 Experimental Conditions	108
4.2 Enhancement in Water	110
4.3 Enhancement in 0.1 M CaCl_2 Solution	114
4.4 Enhancement in 2.5 mM $\text{Ca}(\text{OH})_2$ Solution Containing 0.1 M CaCl_2	119
4.5 Enhancement in 17 mM $\text{Ca}(\text{OH})_2$ Solution Containing 0.1 M CaCl_2	124
4.6 Enhancement in Solutions of Varying Ionic Strength	129
4.7 Summary of Experiments in Clear Solutions	131
4.7.1 Enhancement and Gas Film Resistance	134
4.7.2 Slurry Absorption Model and Theory	137
5. RESULTS OF EXPERIMENTS IN $\text{Ca}(\text{OH})_2$ SLURRIES	140
5.1 Experimental Conditions	140
5.2 Results of Slurry Experiments	142
5.2.1 Enhancement in Increasing Concentrations of Reagent Grade $\text{Ca}(\text{OH})_2$	143
5.2.2 Enhancement in Slurries Made From Mississippi $\text{Ca}(\text{OH})_2$	147

TABLE OF CONTENTS (concluded)

<u>Section</u>	<u>Page</u>
5.2.3 Enhancement in Three Different Lime Types	152
5.3 Validation of Slurry Absorption Model for $\text{Ca}(\text{OH})_2$ Slurries	156
5.3.1 Inputs that Establish Slurry Properties	156
5.3.2 Enhancement Predicted by Slurry Absorption Model	157
5.3.3 Solids Settling in the Boundary Layer	162
5.4 Summary of Slurry Absorption Experiments	165
5.4.1 Effect of Solids Concentration on Enhancement and Gas Film Resistance in the Stirred Tank	166
5.4.2 Effect of Solids Concentration on Enhancement and Gas Film Resistance in a Slurry Droplet	167
5.4.3 Alternate Interpretation of Slurry Absorption Model Data	175
5.4.4 Effect of Varied $\text{Ca}(\text{OH})_2$ Reactivity	180
5.4.5 Slurry Absorption Model Validation	182
6. COMPUTER MODELING	184
6.1 Model	184
6.1.1 Equilibria	184
6.1.2 $\text{Ca}(\text{OH})_2$ Dissolution	185
6.1.3 CaSO_3 Crystallization	189
6.1.4 SO_2 Absorption	189
6.1.5 Numerical Solution	192
6.1.6 Modeling Conditions	198
6.2 Modeling Results	200
6.2.1 $\text{Ca}(\text{OH})_2$ Reactivity	200
6.2.2 Concentration Profiles Without $\text{Ca}(\text{OH})_2(\text{s})$ in the Liquid Bulk	203
6.2.3 Concentration Profiles With $\text{Ca}(\text{OH})_2(\text{s})$ in the Bulk Liquid	206
6.2.4 Partial Pressure of SO_2 at the Gas Liquid Interface	209
6.2.5 Effects of $\text{Ca}(\text{OH})_2(\text{s})$ Concentration	209
6.2.6 Effects of Different Partial Pressures of SO_2	213
6.2.7 Effects of $\text{Ca}(\text{OH})_2(\text{s})$ Reactivity	213
6.2.8 Penetration Distance	218
7. CONCLUSIONS AND RECOMMENDATIONS	223
7.1 Mass Transfer Theory	223
7.2 Stirred Tank Reactor Experiments	223
7.3 Model Validation	225
7.4 Implications for a Slurry Droplet	225
7.5 Computer Modeling	226
7.6 Recommendations for Additional Study	226
8. REFERENCES	228

LIST OF FIGURES

<u>Figure</u>	<u>Page</u>
E-1. Schematic of duct injection pilot plant facility.	5
E-2. Evaluation of gas phase mass transfer by changing gas flow rate. Commercial Mississippi $\text{Ca}(\text{OH})_2$, 2,000 ppm SO_2 , 11 °C approach to saturation.	7
E-3. Comparison of conversion for the case of gas phase resistance controlling with actually measured conversion in the STDR.	8
E-4. The effect of surface moisture on reactivity of sorbents with SO_2	11
E-5. Recarbonation of Mississippi $\text{Ca}(\text{OH})_2$ upon contact with CO_2	12
E-6. The effect of CO_2 on reactivity of Mississippi $\text{Ca}(\text{OH})_2$ with SO_2 (dry, warm N_2 conditioning, 2,000 ppm SO_2 , 11 °C approach to saturation).	14
E-7. Predicted conversion in the presence of liquid H_2O : ($\text{Ca}(\text{OH})_2$ /fly ash sorbent containing 3.65×10^{-3} moles Ca/g sorbent).	17
E-8. Effect of Ca dispersion on sorbent conversion (5,000 ppm SO_2 in flue gas, 70 °C, 1.0 percent initial moisture on Mississippi $\text{Ca}(\text{OH})_2$, 3.5 percent on $\text{Ca}(\text{OH})_2$ /fly ash, 60 to 67 percent RH in flue gas).	19
E-9. Comparison of theoretical and observed conversions of $\text{Ca}(\text{OH})_2$ /fly ash sorbent with initial free moisture (Additive Model, 1,000 ppm SO_2 in flue gas, 70 °C, 60 s reaction, 0 percent RH).	21
E-10. Baseline tests with dry Meredosia fly ash added to dry Mississippi $\text{Ca}(\text{OH})_2$ (STDR, 2,000 ppm SO_2 , 60 percent RH).	23
E-11. The effect of initial free moisture on the reactivity of chemically reacted fly ash/ $\text{Ca}(\text{OH})_2$ (STDR, 2,000 ppm SO_2 , 60 percent RH).	25
E-12. Effect of initial free moisture on the reactivity with SO_2 of 27.4 m^2/g sorbent (ground Meredosia fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio of 3:1; reactor: 60 percent RH, 2,000 ppm SO_2).	26
E-13. Effect of sorbent specific surface area on the reactivity of moist sorbent (Meredosia fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio of 3:1; reactor: 60 percent RH, 2,000 ppm SO_2).	27
E-14. Correlation of the moisture data (points represent all fly ash/ $\text{Ca}(\text{OH})_2$ sorbents, including duplicates, tested during this study; silica sources were Clinch River fly ash, ground Clinch River fly ash, Harrington fly ash, and silica fume).	29
E-15. Correlation of critical moisture ratio at the critical moisture content.	30
E-16. Effect of fly ash grinding and the presence of $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ on critical moisture content (all samples slurried for 8 h, slurry composition represented as g Clinch River fly ash/g $\text{Ca}(\text{OH})_2$ /g $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ /g $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$).	32
2-1. Schematic of duct injection with damp solids.	42
3-1. Short time differential reactor (STDR) system.	45
3-2. Slider assembly.	46
3-4. Schematic of duct injection pilot plant facility.	50
3-5. Particle size distribution for Mississippi $\text{Ca}(\text{OH})_2$ as measured by cascade impactor.	54
3-6. TGA analysis of Mississippi $\text{Ca}(\text{OH})_2$	55
3-7. Chemical analysis of Mississippi $\text{Ca}(\text{OH})_2$ (by Mississippi Lime Company).	56
3-8. Particle size distribution for Mississippi CaO as measured by cascade impactor.	57
3-9. SEM photograph of Mississippi CaO , x 5,000.	58

LIST OF FIGURES (continued)

Figure	Page
3-10. SEM photograph of Mississippi Ca(OH)_2 , x 5,000.	59
3-11. TGA analysis of Mississippi CaO	60
3-12. Chemical analysis of Mississippi CaO (Mississippi Lime Company).	61
4-1. Evaluation of gas phase mass transfer by changing gas flow rate. Commercial Mississippi Ca(OH)_2 , 2,000 ppm SO_2 , 11 °C approach to saturation.	63
4-2. Evaluation of gas phase mass transfer by changing the nature of carrier gas. Commercial Mississippi Ca(OH)_2 , 2,000 ppm SO_2 , 60 percent RH, dry/warm nitrogen conditioning.	64
4-3. SEM photograph of commercial Mississippi Ca(OH)_2 , x 200.	68
4-4. SEM photograph of an agglomerate of commercial Mississippi Ca(OH)_2 , x 5,000.	69
4-5. SEM photograph of a unit particle of commercial Mississippi Ca(OH)_2 , x 20,000.	70
4-6. Time needed for complete conversion of Ca(OH)_2 particle with SO_2 for gas phase mass transfer controlling; 72 °C, 15 SLPM N_2 , 2,000 ppm SO_2	71
4-7. Comparison of conversion for the case of gas phase resistance controlling with actually measured conversion in the STDR.	72
4-8. Evaluation of the effect of chemical reaction; commercial Mississippi Ca(OH)_2 , 2,000 ppm SO_2 , 30 percent RH, dry/warm nitrogen conditioning.	73
4-9. Evaluation of the effect of chemical reaction; commercial Mississippi Ca(OH)_2 , 2,000 ppm SO_2 , 60 percent RH, dry/warm nitrogen conditioning.	74
4-10. The effect of the approach to saturation on the reactivity of Mississippi Ca(OH)_2 with SO_2 (2,000 ppm SO_2 , dry/warm N_2 conditioning).	76
4-11. Temperature conditioning (dry N_2 , 2,000 ppm SO_2 , $\Delta t_s = 22$ °C).	77
4-12. Moisture conditioning (moist N_2 , 2,000 ppm SO_2 , $\Delta t_s = 11$ °C).	79
4-13. Moist conditioning (moist N_2 , 2,000 ppm SO_2 , $\Delta t_s = 16$ °C).	80
4-14. SEM photograph of laboratory Ca(OH)_2 Miss 4 (32 m^2/g , 30 percent porosity), x 200.	82
4-15. SEM photograph of laboratory Ca(OH)_2 Miss 4 (32 m^2/g , 30 percent porosity), x 20,000.	83
4-16. Effect of the specific surface area of the sorbent on the conversion with SO_2 (2,000 ppm SO_2 , 11 °C approach to saturation, 61 °C/dry nitrogen conditioning).	85
4-17. Effect of the specific surface area of the sorbent on the conversion with SO_2 (2,000 ppm SO_2 , 11 °C approach to saturation, sorbent conditioning with room air).	86
4-18. The effect of sorbent conditioning on the reactivity with SO_2 (Miss Ca(OH)_2 , 2,000 SO_2 , 11 °C approach to saturation).	87
4-19. The effect of evaporation of moisture from the sorbent (commercial Mississippi Ca(OH)_2 , 2,000 ppm SO_2 , no moisture in the process gas, conditioning with 21 °C, water saturated nitrogen).	88
4-20. The effect of the approach to saturation on the reactivity with SO_2 (Miss 4 Ca(OH)_2 , 2,000 ppm SO_2 , dry/warm nitrogen conditioning).	89
4-21. Combined effect of sorbent surface area and conditioning techniques on sorbent's reactivity with SO_2	92
4-22. Reactivity of Ca(OH)_2 as a function of initial moisture content as measured by TGA.	93
4-23. The effect of surface moisture on reactivity of sorbents with SO_2	94
4-24. Recarbonation of Mississippi Ca(OH)_2 upon contact with CO_2	96

LIST OF FIGURES (continued)

<u>Figure</u>	<u>Page</u>
4-25. Carbonation of Mississippi $\text{Ca}(\text{OH})_2$ as a function of initial surface area (10 vol percent of CO_2).	97
4-26. The effect of CO_2 on reactivity of Mississippi $\text{Ca}(\text{OH})_2$ with SO_2 (2,000 ppm SO_2 , 11 °C to saturation).	99
4-27. Effect of RH on conversion of Clinch River fly ash/ $\text{Ca}(\text{OH})_2$ sorbent.	101
4-28. Effect of RH on conversion of Mississippi $\text{Ca}(\text{OH})_2$	102
4-29. Effect of pretreating time on conversion of fly ash/ $\text{Ca}(\text{OH})_2$ sorbent.	106
4-30. Effect of pretreating RH on conversion of fly ash/ $\text{Ca}(\text{OH})_2$ sorbent.	107
4-31. Effect of reagent type on conversion (CR, MH denote Clinch River fly ash/ $\text{Ca}(\text{OH})_2$ sorbent and Mississippi $\text{Ca}(\text{OH})_2$, respectively).	109
4-32. Effect of reagent surface area on conversion (CR, MH denote Clinch River fly ash/ $\text{Ca}(\text{OH})_2$ sorbent and Mississippi $\text{Ca}(\text{OH})_2$, respectively).	110
4-33. Effect of SO_2 concentration on conversion of Mississippi $\text{Ca}(\text{OH})_2$ and fly ash/ $\text{Ca}(\text{OH})_2$ sorbent (CR, MH denote Clinch River fly ash/ $\text{Ca}(\text{OH})_2$ sorbent and Mississippi $\text{Ca}(\text{OH})_2$, respectively).	112
4-34. Effect of bag filter cycle time on conversion of accumulating filter cake (CR, MH denote Clinch River fly ash/ $\text{Ca}(\text{OH})_2$ sorbent and Mississippi $\text{Ca}(\text{OH})_2$, respectively).	114
5-1. Predicted conversion in the presence of liquid H_2O : ($\text{Ca}(\text{OH})_2$ fly ash sorbent containing 3.65×10^{-3} moles Ca/g sorbent).	120
5-2. Conversion of fly ash/ $\text{Ca}(\text{OH})_2$ sorbent containing ambient moisture (1,000 ppm SO_2 in flue gas, 70 °C, 3.5 percent initial moisture on sorbent).	124
5-3. Conversion of $\text{Ca}(\text{OH})_2$ sorbents containing ambient moisture (5,000 ppm SO_2 in flue gas, 70 °C, 1.0 percent initial moisture on sorbents, 58 to 67 percent RH in flue gas).	125
5-4. Comparison of fly ash/ $\text{Ca}(\text{OH})_2$ and Mississippi $\text{Ca}(\text{OH})_2$ sorbent (5,000 ppm SO_2 in flue gas, 70 °C, 1.0 percent initial moisture on Mississippi $\text{Ca}(\text{OH})_2$, 3.5 percent on fly ash/ $\text{Ca}(\text{OH})_2$, 60 to 67 percent RH in flue gas).	126
5-5. Effect of Ca dispersion on sorbent conversion (5,000 ppm SO_2 in flue gas, 70 °C, 1.0 percent initial moisture on Mississippi $\text{Ca}(\text{OH})_2$, 3.5 percent on $\text{Ca}(\text{OH})_2$ /fly ash, 60 to 67 percent RH in flue gas).	129
5-6. Conversion of fly ash/ $\text{Ca}(\text{OH})_2$ sorbent with initial free moisture (1,000 ppm SO_2 in flue gas, 70 °C, 10 s reaction).	130
5-7. Conversion of fly ash/ $\text{Ca}(\text{OH})_2$ sorbent with initial free moisture (1,000 ppm SO_2 in flue gas, 70 °C, 60 s reaction).	131
5-8. Conversion of fly ash/ $\text{Ca}(\text{OH})_2$ sorbent with initial free moisture (1,000 ppm SO_2 in flue gas, 70 °C, 120 s reaction).	132
5-9. Conversion of fly ash/ $\text{Ca}(\text{OH})_2$ sorbent with initial free moisture (5,000 ppm SO_2 in flue gas, 70 °C, 10 s reaction, 58 to 63 percent RH).	135
5-10. Conversion of fly ash/ $\text{Ca}(\text{OH})_2$ sorbent with initial free moisture (5,000 ppm SO_2 in flue gas, 70 °C, 60 s reaction, 58 to 68 percent RH).	136

LIST OF FIGURES (continued)

<u>Figure</u>	<u>Page</u>
5-11. Conversion of fly ash/Ca(OH) ₂ sorbent with initial free moisture (5,000 ppm SO ₂ in flue gas, 70 °C, 120 s reaction, 58 to 62 percent RH).	137
5-12. Conversion of Ca(OH) ₂ sorbents with initial free moisture (5,000 ppm SO ₂ in flue gas, 70 °C, 10 s reaction, 56 to 66 percent RH).	138
5-13. Conversion of Ca(OH) ₂ sorbents with initial free moisture (5,000 ppm SO ₂ in flue gas, 70 °C, 60 s reaction, 58 to 69 percent RH).	139
5-14. Conversion of Ca(OH) ₂ sorbents with initial free moisture (5,000 ppm SO ₂ in flue gas, 70 °C, 120 s reaction, 58 to 64 percent RH).	140
5-15. Comparison of theoretical and observed conversions of fly ash/Ca(OH) ₂ sorbent with initial free moisture (Additive Model, 1,000 ppm SO ₂ in flue gas, 70 °C, 120 s reaction, 55 to 65 percent RH).	142
5-16. Comparison of theoretical and observed conversions of fly ash/Ca(OH) ₂ sorbent with initial free moisture (Additive Model, 1,000 ppm SO ₂ in flue gas, 70 °C, 60 s reaction, 0 percent RH).	143
5-17. Comparison of theoretical and observed conversions of fly ash/Ca(OH) ₂ sorbent with initial free moisture (Additive Model, 1,000 ppm SO ₂ in flue gas, 70 °C, 10 s reaction, 80 to 90 percent RH).	144
5-18. Comparison of theoretical and observed conversions of Ca(OH) ₂ sorbents with initial free moisture (Additive Model, 5,000 ppm SO ₂ in flue gas, 70 °C, 10 s reaction, 80 to 90 percent RH).	145
5-19. Comparison of theoretical and observed conversions of Ca(OH) ₂ sorbents with initial free moisture (Additive Model, 5,000 ppm SO ₂ in flue gas, 70 °C, 60 s reaction, 80 to 90 percent RH).	146
5-20. Comparison of theoretical and observed conversions of fly ash/Ca(OH) ₂ sorbent with initial free moisture (Additive Model, 5,000 ppm SO ₂ in flue gas, 70 °C, 120 s reaction, 55 to 60 percent RH).	147
5-21. Determination of instantaneous sorbent conversion rate for Ca(OH) ₂ sorbents (5,000 ppm SO ₂ in flue gas, 70 °C, 55 to 65 percent RH).	150
5-22. Determination of instantaneous sorbent conversion rate for fly ash/Ca(OH) ₂ sorbent (1,000, 5,000 ppm SO ₂ in flue gas, 70 °C, 55 to 65 percent RH).	151
5-23. Interactive Model of fly ash/Ca(OH) ₂ conversion (1,000 ppm SO ₂ in flue gas, 70 °C, 55 to 65 percent RH, 10 s reaction).	153
5-24. Interactive Model of fly ash/Ca(OH) ₂ conversion (1,000 ppm SO ₂ in flue gas, 70 °C, 55 to 65 percent RH, 120 s reaction).	154
5-25. Interactive Model of fly ash/Ca(OH) ₂ conversion (5,000 ppm SO ₂ in flue gas, 70 °C, 55 to 65 percent RH, 10 s reaction).	155
5-26. Interactive Model of fly ash/Ca(OH) ₂ conversion (5,000 ppm SO ₂ in flue gas, 70 °C, 55 to 65 percent RH, 120 s reaction).	156
5-27. Interactive Model of Ca(OH) ₂ conversion (5,000 ppm SO ₂ in flue gas, 70 °C, 55 to 65 percent RH, 10 s reaction).	157

LIST OF FIGURES (continued)

<u>Figure</u>	<u>Page</u>
5-28. Interactive Model of $\text{Ca}(\text{OH})_2$ conversion (5,000 ppm SO_2 in flue gas, 70 °C, 55 to 65 percent RH, 120 s reaction).	158
5-29. Reaction of fly ash/ $\text{Ca}(\text{OH})_2$ sorbent with CO_2 (1,000 ppm SO_2 in flue gas, 70 °C, 55 to 65 percent RH).	160
5-30. SEM photomicrograph of "as-received" Clinch River fly ash sample, x 2,000.	163
5-31. SEM photomicrograph of ground Clinch River fly ash sample, x 5,000.	164
5-32. Baseline tests with dry Meredosia fly ash added to dry Mississippi $\text{Ca}(\text{OH})_2$ (STDR, 2,000 ppm SO_2 , 60 percent RH).	165
5-33. $\text{Ca}(\text{OH})_2$ physically mixed with Meredosia fly ash (STDR, 2,000 ppm SO_2 , 60 percent RH).	167
5-34. The effect of initial free moisture on the reactivity of chemically reacted fly ash/ $\text{Ca}(\text{OH})_2$ (STDR, 2,000 ppm SO_2 , 60 percent RH).	168
5-35. Reactivity comparison for physically mixed and chemically reacted fly ash/ $\text{Ca}(\text{OH})_2$ (STDR, 2,000 ppm SO_2 , 60 percent RH, 12-14.7 percent at limited moisture contents).	170
5-36. The effect of an initial moisture on the reactivity of physically mixed and reacted fly ash/ $\text{Ca}(\text{OH})_2$ (STDR, 2,000 ppm SO_2 , 60 percent RH, 5 s contact time).	171
5-37. Effect of initial free moisture on the reactivity with SO_2 of 27.4 m^2/g sorbent (ground Meredosia fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio of 3:1; reactor: 60 percent RH, 2,000 ppm SO_2).	173
5-38. Effect of initial free moisture on the reactivity with SO_2 of 33.2 m^2/g sorbent (ground Meredosia fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio of 3:1; reactor: 60 percent RH, 2,000 ppm SO_2).	174
5-39. Effect of initial free moisture on the reactivity with SO_2 of 47.0 m^2/g sorbent (ground Meredosia fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio of 3:1; reactor: 60 percent RH, 2,000 ppm SO_2).	175
5-40. Effect of sorbent-specific surface area on the reactivity of moist sorbent (Meredosia fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio of 3:1; reactor: 60 percent RH, 2,000 ppm SO_2).	177
5-41. Effect of the approach to saturation on the reactivity of 30.2 m^2/g sorbent with 30 weight percent initial free moisture (ground Clinch River fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio of 3:1, 2,000 ppm SO_2).	179
5-42. Effect of the approach to saturation on the reactivity of 27.4 m^2/g sorbent with 60 weight percent initial free moisture (ground Meredosia fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio of 3:1; reactor: 2,000 ppm SO_2).	180
5-43. Effect of the approach to saturation on the reactivity of 27.4 m^2/g sorbent with equilibrium moisture (ground Meredosia fly ash, $\text{Ca}(\text{OH})_2$ weight ratio of 3:1; reactor: 2,000 ppm SO_2).	181
5-44. Effect of fly ash source on reactivity of sorbent with SO_2 (ground fly ash-to- $\text{Ca}(\text{OH})_2$ weight ratio of 3:1, 30 weight percent initial free moisture, 2,000 ppm SO_2 , 60 percent RH).	183
5-45. Combined effect of fly ash source and initial free moisture content on sorbent's reactivity with SO_2 (ground fly ash-to- $\text{Ca}(\text{OH})_2$ weight ratio of 3:1, 2,000 ppm SO_2 , 60 percent RH, 5 s residence time).	184
5-46. Typical results for sieve tests of fly ash/ $\text{Ca}(\text{OH})_2$ sorbent (critical moisture content 17 percent, Clinch River fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio slurried for 8 h at 92 °C).	190

LIST OF FIGURES (continued)

<u>Figure</u>	<u>Page</u>
5-47. Correlation of the moisture data (points represent all fly ash/Ca(OH) ₂ sorbents, including duplicates, tested during this study; silica sources were Clinch River fly ash, ground Clinch River fly ash, Harrington fly ash, and silica fume).	192
5-48. Correlation of critical moisture ratio at the critical moisture content.	193
5-49. Correlation of particle pore volume with specific surface area (the dotted line and equation are a least-squares fit of the data).	194
5-50. Critical moisture content of reactant and dry mixtures (CaSO ₄ •2H ₂ O, Harrington fly ash, Clinch River fly ash, CaSO ₃ •0.5H ₂ O, ground Clinch River fly ash, and 20-m ² /g Ca(OH) ₂).	196
5-51. Effect of slurry time and fly ash/Ca(OH) ₂ ratio on critical moisture content of sorbent from low-calcium fly ash (open symbols are the 3:1 Clinch River fly ash/Ca(OH) ₂ weight ratio; solid symbols are 4:1 ratio).	198
5-52. Effect of CaSO ₃ and CaSO ₄ •2H ₂ O with CaSO ₃ on sorbents from low-calcium fly ash (solid symbols are 4:1 Clinch River fly ash/Ca(OH) ₂ weight ratio; open squares 4:1:4 fly ash/Ca(OH) ₂ /CaSO ₃ •0.5H ₂ O; triangles 4:1:3:1 fly ash/Ca(OH) ₂ /CaSO ₃ /CaSO ₄ •2H ₂ O).	200
5-53. Effect of CaSO ₃ and CaSO ₄ •2H ₂ O with CaSO ₃ on solution composition of low-calcium fly ash slurry (solid symbols 4:1 Clinch River fly ash/Ca(OH) ₂ weight ratio; open squares 4:1:4 fly ash/Ca(OH) ₂ /CaSO ₃ •0.5H ₂ O; triangles 4:1:3:1 fly ash/Ca(OH) ₂ /CaSO ₃ /CaSO ₄ •2H ₂ O).	201
5-54. Effect of fly ash grinding and the presence of CaSO ₄ •2H ₂ O on critical moisture content (all samples slurried for 8 h, slurry composition represented as g Clinch River fly ash/g Ca(OH) ₂ /g CaSO ₃ •0.5H ₂ O/g CaSO ₄ •2H ₂ O).	202
5-55. Effect of CaSO ₄ •2H ₂ O and CaSO ₃ on sorbent from ground low-calcium fly ash (solid symbols 1:1 ground Clinch River fly ash/Ca(OH) ₂ weight ratio; open symbols 4:4:3:1 fly ash/Ca(OH) ₂ /CaSO ₃ •0.5H ₂ O/CaSO ₄ •2H ₂ O).	203
5-56. Effect of fly ash fraction on sorbent from ground low-calcium fly ash (all samples slurried for 8 h, ground Clinch River fly ash/CaSO ₃ •0.5H ₂ O/CaSO ₄ •2H ₂ O weight ratio constant at 4:3:1; zero fly ash fraction represents unreacted Ca(OH) ₂).	205
5-57. Effect of fly ash fraction and slurry time on surface area of sorbent from ground low-calcium fly ash (slurry times of 2, 4, and 8 h, ground Clinch River fly ash/CaSO ₃ •0.5H ₂ O/CaSO ₄ •2H ₂ O weight ratio constant at 4:3:1; zero fly ash fraction represents unreacted Ca(OH) ₂).	206
5-58. Effect of fly ash fraction on solution composition of ground low-calcium fly ash slurry (slurry times of 2, 4, and 8 h, ground Clinch River fly ash/CaSO ₃ •0.5H ₂ O/CaSO ₄ •2H ₂ O weight ratio constant at 4:3:1).	207
5-59. Critical moisture content of sorbent prepared from high-calcium fly ash alone, and fly ash with Ca(OH) ₂ ("Ash Alone": Harrington fly ash slurried without Ca(OH) ₂ at 26 percent solids, "With Ca(OH) ₂ ": weight ratio of Harrington fly ash/Ca(OH) ₂ slurried at 92 °C at 26 percent solids).	209
5-60. Effect of CaSO ₄ •2H ₂ O on critical moisture content of sorbent prepared from high-calcium fly ash ("Ash Alone": average values of data shown in Figure 5-14 for sorbent prepared from Harrington fly ash, "With Gypsum": 3:0:6 Harrington fly ash/CaSO ₄ •2H ₂ O, "Ca(OH) ₂ & Gypsum": 3:1:0.67 Harrington ash/Ca(OH) ₂ /CaSO ₄ •2H ₂ O).	210

LIST OF FIGURES (concluded)

<u>Figure</u>	<u>Page</u>
5-61. Solution composition of slurries with high-calcium fly ash ("Ash Alone": Harrington fly ash slurried without $\text{Ca}(\text{OH})_2$ at 23 percent solids, "With Gypsum": 3:0:6 Harrington fly ash/ $\text{CaSO}_4 \cdot \text{H}_2\text{O}$ weight ratio).	211
5-62. Effect of $\text{Ca}(\text{OH})_2$ loading on sorbent prepared from high-calcium fly ash with $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ (constant Harrington fly ash/ $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ weight ratio of 3:0:6 and slurry time of 8 h except points at 0.33 loading, which are 9 h samples).	213
5-63. Effect of $\text{Ca}(\text{OH})_2$ loading on solution composition for slurry of high-calcium fly ash with $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ present.	214
5-64. Dry-sorbent injection upstream of the humidifier (Meredosia fly ash/ $\text{Ca}(\text{OH})_2$ mixture).	215
5-65. SO_2 removal for recycle operation during the DSI downstream of the humidification zone.	217
5-66. Comparison of DSI upstream and downstream of humidifier.	219
5-67. Results for DSI recycle tests upstream of humidifier.	220
5-68. Reactivation of spent Mississippi $\text{Ca}(\text{OH})_2$ baghouse catch by dry grinding baghouse catch/Beverly fly ash (mixed at the weight ratio of 3:5:1).	223
5-69. Reactivation of spent $\text{Ca}(\text{OH})_2$ /Beverly fly ash solid by dry-grinding in a bench-scale attritor (reactor: 60 percent RH, 2,000 ppm SO_2).	224

LIST OF TABLES

<u>Table</u>	<u>Page</u>
E-1. Structural Properties of Fly Ash/Ca(OH) ₂ Sorbents	22
E-2. Pilot Plant Operating Conditions	34
3-1. Sorbent Selection and Characterization	52
4-1. Mississippi Ca(OH) ₂ s	81
4-2. The Effect of Sorbent Type and Conditioning Scheme on the Amount of Moisture	90
5-1. Properties of Sorbents used in the Course of LTDR Work	123
5-2. Rate of Sorbent Conversions for Interactive Mode	149
5-3. Structural Properties of Fly Ashes used to Produce Fly Ash/Ca(OH) ₂ Sorbents	161
5-4. Structural Properties of Fly Ash/Ca(OH) ₂ Sorbents	162
5-5. Effect of Specific Surface Area on Reactivity of Moist Sorbent with SO ₂ (Meredosia Fly Ash/Ca(OH) ₂ Weight Ratio of 3:1, 90 °C Slurrying)	176
5-6. Chemical Composition of Silica Sources (From Energy-Dispersive Spectroscopy)	187
5-7. Pilot Plant Operating Conditions	216
5-8. Structural Properties of Pilot Plant Solids	221
5-9. Structural Properties of Dry Ground Baghouse Catch/Beverly Fly Ash Solids	222

EXECUTIVE SUMMARY

E.1 DUCT INJECTION PROGRAM OVERVIEW

In 1988, the Department of Energy Pittsburgh Energy Technology Center (DOE-PETC) initiated a broad program to develop duct injection technology for the reduction of sulfur dioxide (SO₂) emissions from existing coal-fired plants. Duct injection program follows three proof-of-concept tests programs sponsored by DOE that indicated duct injection was successful at achieving 50 percent SO₂ removal. Current program consists of five major components: Duct Configuration Survey (Burns and Roe Services), Enhanced Sorbent Utilization (Acurex Corporation and Energy and Environmental Research Corporation), Fundamental Investigation of Duct and ESP Phenomena (Radian Corporation), Scale-up Tests and Supporting Research (Gilbert/Commonwealth), and Duct Injection Technology Prototype Development (United Engineers and Constructors).

As of this report date (January 1992), the Duct Configuration Survey was completed and assembled into a database. Energy and Environmental Research Corporation completed their Enhanced Sorbent Utilization study. Fundamental Investigation of Duct and ESP Phenomena was completed by Radian. The ongoing efforts under the duct injection program include testing at the 12 MW Duct Injection Test Facility located at the Ohio Power Company's Muskingum River Station in Beverly, Ohio. Another ongoing effort is the Duct Injection Technology Prototype Development by United Engineers and Constructors.

This Final Report describes results from the Enhanced Sorbent Utilization Study conducted by Acurex Corporation and the Department of Chemical Engineering at the University of Texas since late 1988. The work was performed under Contract No. DE-AC22-88PC898874 "Theoretical Approach for

Enhanced Mass Transfer Effects In Duct Flue Gas Desulfurization Processes". This report is arranged into two volumes: Volume I - Dry Sorbent Injection, and Volume II - Duct Spray Drying. The objectives of Acurex/University of Texas work were threefold: determine the controlling physical and chemical processes which limit sorbent utilization, examine various techniques which are capable of sorbent utilization improvement, and evaluate various sorbents, operating conditions and process schemes to support pilot-scale field testing and demonstration. Acurex key personnel included: Dr. Wojciech Jozewicz, Dr. John C. S. Chang, Brent Hall, and Carl Singer. University of Texas key personnel included: Dr. Gary T. Rochelle with Stephen P. Beaudoin, Lynn M. McGuire, Charlotte Stromblad, David E. Stroud, and William G. White.

E.2 INTRODUCTION

Reductions in SO₂ emissions from coal fired electric utilities are mandated by the 1990 amendments to the Clean Air Act. Coal combustion is used to supply more than one-half of the electrical power demand in the United States. Utilities can reduce emissions from existing boilers by: (1) retiring boilers that do not have SO₂ controls, (2) repowering for other fuels or with new combustion technology, (3) removing sulfur from coal before combustion (coal cleaning), (4) switching to low sulfur coal, or (5) retrofitting with flue gas desulfurization.

A variety of processes are available for flue gas desulfurization (FGD) and they are not limited to retrofit applications; in fact, nearly 25 percent of the current coal fired utility generating capacity already has FGD; but, there is an opportunity for retrofit applications to achieve additional emissions reductions.

Duct injection of sorbents is an emerging technology attractive for retrofit applications. Development of the technology has focused on increased sorbent reactivity. In this process, sorbent is injected into the existing ductwork as a slurry [duct spray drying (DSD)], a dry solid with gas humidification [dry sorbent injection (DSI)], or a damp solid. Damp solids injection seeks to obtain the benefits of sorbent free moisture.

This report presents the results of fundamental mass transfer testing for in-duct removal of SO_2 . Following this initial part of an experimental program, it became clear that the amount of initial moisture on the sorbent strongly affected the extent of $\text{Ca}(\text{OH})_2$ conversion (Section 4). Novel techniques aimed at increasing sorbent utilization were investigated and are described in Section 5. Major novel technique investigated and reported on here was the reaction with SO_2 of sorbents with an initial free moisture (damp sorbents). The mechanisms of agglomeration due to moisture and solids moisture capacity were also investigated. Another novel technique described in Section 5 is grinding of recycle DSI solids in order to increase the availability and subsequent utilization of $\text{Ca}(\text{OH})_2$. Section 6 presents conclusions and Section 7 lists references used throughout this study.

E.3 EXPERIMENTAL

A short time differential reactor (STDR) was used to investigate short-time reactivity of sorbents with SO_2 . It is a fixed bed reactor in which sorbent dispersed on a quartz wool is rapidly moved into the process gas stream and then extracted after a preset exposure time. The process gas was conditioned to a desired temperature and RH. The RH was attained by the injection of water into the evaporation chamber heated between 130 and 180 °C. The reaction system was designed for reaction times ranging from 0.3 s to 5 s or more. To prevent the condensation of the process gas moisture, the whole slider assembly was heat traced and insulated. Temperature of the process gas was measured at the exit from the slider assembly. Reactivity of sorbent is expressed as $\text{Ca}(\text{OH})_2$ conversion. $\text{Ca}(\text{OH})_2$ conversion is defined as a ratio of numbers of moles of SO_2 captured to numbers of moles of $\text{Ca}(\text{OH})_2$ multiplied by 100.

The fixed bed long time differential reactor (LTDR) was used to investigate reactivity of sorbents with SO_2 . In order to minimize SO_2 removal from the bulk gas, reagent loading was drastically reduced in the LTDR relative to the reactors used to simulate bag filter conditions. The experiments were conducted using a packed bed reactor in which the solid reagent (approximately 15 mg) was suspended in quartz wool and supported on a fritted glass disk. The solids were preconditioned by first exposing them to humid nitrogen for 2 min and then nitrogen at the desired

relative humidity for 2 min. The reaction system was designed for reaction times ranging from 10 s to 1 h or more.

The pilot plant facility incorporated a Niro Atomizer Mobile Minor spray dryer facility. The spray dryer has been retrofitted with additional ductwork downstream of the spray dryer vessel, plus a dry sorbent injection system, and a pulse-jet baghouse. The pilot plant arrangement is depicted in Figure E-1. The spray dryer total volume is 0.42 m^3 , providing for a gas retention time of approximately 15-20 s based on the outlet gas conditions. For dry injection tests, the spray dryer served as a humidifier to condition the flue gas humidity and temperature to desired level. Different lengths of duct section, 9.8 m or, alternatively, 24.4 m, provided gas retention times of 0.8 s or 2 s. A dry sorbent injection system was installed at the vertical duct section just downstream of the spray dryer vessel (upstream of the main duct section). The SO_2 concentrations throughout the system were determined by extractive sampling from the spray dryer inlet duct, the spray dryer outlet duct, and cyclone outlet duct/baghouse inlet duct.

Mississippi $\text{Ca}(\text{OH})_2$ from Mississippi Lime Company has been selected as the baseline sorbent for experiments with dry hydrated lime. The specific surface area was measured to be $17 \text{ m}^2/\text{g}$ and porosity 19 percent. Mass median particle size was measured to be $2.86 \text{ }\mu\text{m}$ by the Sedigraph method. The sample of the parent quicklime (Mississippi CaO) intended for use in the slaking tests was also characterized. The measured specific surface area and porosity were $1.2 \text{ m}^2/\text{g}$ and 3 percent, respectively.

Figure E-1. Schematic of duct injection pilot plant facility.

E.4 MASS TRANSFER TESTING

The effect of gas phase mass transfer was evaluated by two independent series of experiments. In the first experiment, the regular process gas flow rate (15 SLPM) was decreased to 7.5 SLPM, and conversion was measured for 11 °C approach to saturation (approximately 60 percent RH) and 2,000 ppm SO₂. The sorbent was conditioned with dry/warm nitrogen prior to injection into the humidified process gas. The results are presented in Figure E-2. The data show that Ca(OH)₂ conversion was not affected by changing the gas flow rate. If the gas phase resistance were controlling, the conversion would decrease with decreasing gas flow rate. In another set of experiments, the composition of the carrier gas was changed to the mixture of helium/nitrogen. Ca(OH)₂ conversion was not affected by changing the composition of the carrier gas. If the gas phase resistance were controlling, the conversion would increase for experiments using the mixture of helium/nitrogen as a carrier gas in place of nitrogen only. Levenspiel's formula was used to calculate the time, τ , needed for 100 percent conversion when the gas phase resistance is controlling:

$$\tau = \frac{\rho_s \cdot r}{3b \cdot k_g \cdot C_{SO_2}} \quad (E-1)$$

Where: ρ_s = sorbent particle molar density, g mol/cm³; r = sorbent particle radius; b = reaction stoichiometry; k_g = gas phase mass transfer coefficient, g mol/s·cm²; C_{SO_2} = bulk concentration of SO₂ in gas phase, mol/mol.

The time needed for the complete reaction of a 2.86 μ m Ca(OH)₂ particle was calculated to be 0.004 s. The time needed to reach 100 percent conversion was also calculated for particle sizes ranging from 2.86-200 μ m. For the conditions used in the calculations, 0.004 and 7.8 s would be needed for complete conversion of 2.86 and 200 μ m agglomerates, respectively. Should gas phase resistance be controlling, 20 μ m agglomerate would need 0.16 s for the complete conversion. Measured conversion after 5 s in the STDR was below 2 percent. The comparison is shown in Figure E-3.

Figure E-2. Evaluation of gas phase mass transfer by changing gas flow rate. Commercial Mississippi Ca(OH)₂, 2,000 ppm SO₂, 11 °C approach to saturation.

Figure E-3. Comparison of conversion for the case of gas phase resistance controlling with actually measured conversion in the STDR.

The effect of the chemical reaction was evaluated at two RH levels. Different levels of conversions should be measured for varying temperature in the reactor, should the chemical reaction step be controlling. The same level of conversion was measured for three different temperatures investigated. In this case, the Ca(OH)_2 conversion was not significantly affected by temperature changes. In other words, the activation energy was low, and the SO_2 absorption was probably not controlled by chemical reaction. Following the exclusion of gas phase mass transfer and chemical reaction as possible controlling mechanisms for SO_2 absorption, solid phase diffusion control is the most likely candidate.

The approach to adiabatic saturation temperature (or RH of a process gas) has been recognized as a very important parameter governing the reactivity of sorbent with SO_2 under conditions of DSI for SO_2 removal. Two different scenarios of dry nitrogen conditioning were used: dry room temperature (20-21 °C) N_2 and dry bulb temperature (72 °C) N_2 . For both conditioning scenarios conversion was gradually increasing with increasing residence time in the STDR. Little difference was observed between conversion of sorbents conditioned with dry nitrogen at room temperature or at 72 °C. This would imply that the temperature of dry sorbent does not have significant effect on the extent of its subsequent conversion with SO_2 in the humidified gas. Higher reaction rates were observed when sorbent dispersed on the quartz wool was conditioned with water saturated nitrogen at room temperature. Sorbent subjected to conditioning with water saturated nitrogen would be expected to have an increased amount of moisture on its surface. This moisture would, in turn, enhance the reactivity of the sorbent with SO_2 . Based on results presented above it seems that the sorbent initial moisture content is important in determining its reactivity with SO_2 . Initial sorbent temperature appears to be of less importance. STDR data showed that the Ca(OH)_2 conversion was affected by the approach to saturation temperature (RH of the gas) and initial moisture content. However, Ca(OH)_2 conversion was not significantly affected by the flue gas SO_2 concentration.

The amount of moisture on the sorbent was measured by the TGA for different conditioning schemes and for sorbents with varying surface area. Except for the commercial Mississippi Ca(OH)_2 ,

the amount of moisture was increasing with increasing specific surface area of Ca(OH)_2 for conditioning with 61 °C, dry nitrogen. For all sorbents tested, the amount of moisture detected by the TGA following the room air conditioning was approximately the same. It appears that there is a combined effect of surface area and initial moisture content of the sorbent on its reactivity with SO_2 . The reactivity was increasing with both increasing surface area and initial moisture content.

Sorbent with lower surface area could become more reactive by increasing its initial moisture content. However, for samples tested the amount of initial moisture content of Ca(OH)_2 resulting from conditioning techniques applied was always below 1 wt percent, regardless of the sorbent's surface area. One other sorbent was tested and it was produced by slurring fly ash from coal-fired power plant with Ca(OH)_2 at the weight ratio of 3:1 at 90 °C for 16 h. Following 2 min conditioning with room air, the conversion of Ca(OH)_2 measured after 5 s in the STDR operated under conditions previously described was 7.6 percent. The comparison of fly ash/ Ca(OH)_2 and Ca(OH)_2 sorbent is shown in Figure E-4.

Typical flue gas contains CO_2 , which can potentially react with Ca(OH)_2 under DSI conditions. By reacting with CO_2 , the sorbent can be partially converted to CaCO_3 . Since it is known that CaCO_3 is not reactive with SO_2 under duct conditions, the presence of CO_2 could potentially decrease the reactivity of sorbent with SO_2 . Figure E-5 presents the percent carbonation as the function of the exposure time to CO_2 -containing gas. Two levels of CO_2 concentration were tested: 10 and 20 vol percent. The CO_2 -containing gas was dry or humidified (11 °C approach to saturation) and it did not contain SO_2 . For humidified gas, the percent of carbonation increased with increasing contact time. For dry gas, the percent carbonation increased with residence time up to 5 s and later levelled off. Several sorbents were produced in the laboratory to investigate the effect of specific surface area (17-78 m^2/g) on the extent of carbonation. Carbonation conditions were constant at 5 s residence time and 10 vol percent CO_2 concentration. Measured percent carbonation was increasing with the increasing initial surface area of Ca(OH)_2 .

Figure E-4. The effect of surface moisture on reactivity of sorbents with SO₂.

Figure E-5. Recarbonation of Mississippi Ca(OH)₂ upon contact with CO₂.

To investigate the possible effect of SO_2 on the extent of carbonation, the sample of Mississippi $\text{Ca}(\text{OH})_2$ was exposed to the humid $\text{N}_2/\text{CO}_2/\text{SO}_2$ gas. No significant effect of SO_2 presence on the extent of carbonation of $\text{Ca}(\text{OH})_2$ was measured. In the next step, the reactivity of Mississippi $\text{Ca}(\text{OH})_2$ with SO_2 in the presence of CO_2 was investigated in the STDR. The results are presented in Figure E-6. The effect of CO_2 presence on $\text{Ca}(\text{OH})_2$ reactivity with SO_2 varied with the concentration of CO_2 . However, for the practical range of CO_2 concentration (0-10 vol percent) its effect on reactivity of $\text{Ca}(\text{OH})_2$ was insignificant.

Residence time strongly influenced reagent conversion in the LTDR. However, with 10 s for sulfation, the maximum conversion (achieved at 85 percent RH) was only 11 percent with fly ash/ $\text{Ca}(\text{OH})_2$ sorbent and 4 percent with Mississippi $\text{Ca}(\text{OH})_2$. Conversion generally increased with system RH. However, the effect of RH was diminished as reagent conversion approached unity at long residence times. The maximum effect of RH occurred at a residence time of approximately 600 s. With the fly ash/ $\text{Ca}(\text{OH})_2$ sorbent, conversions above 88 percent were achieved at 85 percent RH for residence times above 1 h. Sulfation at 85 percent RH enabled conversion to reach 30 percent approximately 5 times faster than did sulfation at 51 percent RH. Conversion of the $\text{Ca}(\text{OH})_2$ was also strongly influenced by the system RH. At 85 percent RH after 3,600 s of sulfation time, 71 percent conversion was attained, and after 200 s 28 percent conversion was reached. In contrast, at 51 percent RH a second sulfation time was required to attain 28 percent conversion. In addition, conversion at 24 percent was poor, reaching only 5 percent.

Two separate methods to vary the initial moisture content of fly ash/ $\text{Ca}(\text{OH})_2$ reagent were employed during the pretreating step in the LTDR. In the pretreating step, the sorbent was contacted with humid, SO_2 -free nitrogen stream prior to sulfation. In the first group of these experiments, initial moisture content was controlled by changing the pretreating time. Over the range of pretreating times, conversion increased from 11 to 17 percent. Conversion rose rapidly as pretreating time increased from 10 to 60 s reaching 16 percent conversion with a pretreating time of approximately 120 s. The

Figure E-6. The effect of CO₂ on reactivity of Mississippi Ca(OH)₂ with SO₂ (dry, warm N₂ conditioning, 2,000 ppm SO₂, 11 °C approach to saturation).

above procedure called for contacting the sorbent with nitrogen at 90 percent RH, then 58 percent RH nitrogen, and finally the sulfation reaction was carried out for 30 s with 450 ppm SO_2 . Additional tests were performed in which the initial moisture content of the sorbent was varied by adjusting the pretreating RH. During this group of experiments fly ash/ $\text{Ca}(\text{OH})_2$ sorbent was first pretreated with 90 percent RH nitrogen for 2 min followed by nitrogen pretreating for an additional 2 min at the desired RH. Reagent conversion generally increased with the pretreating RH for a given sulfation time.

Results for both fly ash/ $\text{Ca}(\text{OH})_2$ and $\text{Ca}(\text{OH})_2$ were combined. For the same RH and residence time, fly ash/ $\text{Ca}(\text{OH})_2$ sorbent provided a higher conversion than did $\text{Ca}(\text{OH})_2$. With higher relative humidities (above 24 percent) and residence times from 60 to 1,000 s, the superior performance of the fly ash/ $\text{Ca}(\text{OH})_2$ sorbent was evident. The difference in performance of the two reagents was least apparent at low residence times and low RH (because conversion was tending toward 0) and at 85 percent RH and residence times greater than 1 h as reagent conversion asymptotically approached unity. The conversions of sorbents with varying specific surface area (m^2/g of $\text{Ca}(\text{OH})_2$ in the reagent) were compared. The higher surface area material provided for a greater conversion for a given residence time. The relative increase in conversion brought about by using a preferable sorbent appeared to be dependent on the sorbent surface area rather than the chemistry of the reagent.

The conversion of $\text{Ca}(\text{OH})_2$ in the LTDR showed no response toward increased SO_2 concentration, and the fly ash/ $\text{Ca}(\text{OH})_2$ sorbent appeared to show only a slight sensitivity toward SO_2 concentration. Several of the above discussed parameters, specifically RH, residence time, and sorbent surface area, were shown to strongly influence reagent conversion. Conversely, SO_2 concentration had virtually no effect. These general experimental results are consistent with solid phase mass transfer as the rate-limiting step.

E.5 NOVEL TECHNIQUES

A major novel technique investigated was the reaction with SO_2 of $\text{Ca}(\text{OH})_2$ and fly ash/ $\text{Ca}(\text{OH})_2$ sorbents with an initial free moisture (damp sorbents). The reaction between sorbent with an initial free moisture and SO_2 is assumed to be fast compared to gas-phase mass transfer of SO_2 to the particle surface. The transfer is assumed to occur by Knudsen diffusion within the pores of the reactive sorbent. The evaporation of water from the pores of the solid and the transport of SO_2 through the pores to the gas-liquid interface can be represented by:

$$\frac{d(\text{SO}_2/\text{area})}{dt} = N_{\text{SO}_2} = -(D_{\text{SO}_2}) \frac{dC_{\text{SO}_2}}{dx} \quad (\text{E-2})$$

$$\frac{d(\text{H}_2\text{O}/\text{area})}{dt} = N_{\text{H}_2\text{O}} = -(D_{\text{H}_2\text{O}}) \frac{dC_{\text{H}_2\text{O}}}{dx} \quad (\text{E-3})$$

Where: N_i = molar flux ; [mole l/(area-time)], x = diffusion distance ; [length], D = mass diffusion coefficient; [length²/time], and C_i = concentration i ; [mole l/volume].

The relationship between the water evaporated from the solid surface and the SO_2 captured is determined by integrating this expression, as follows:

$$\frac{\Delta \text{SO}_2}{\Delta \text{H}_2\text{O}} = \frac{D_{\text{SO}_2} K (P_{\text{SO}_2})}{D_{\text{H}_2\text{O}} K (P_{\text{H}_2\text{O}}^* - P_{\text{H}_2\text{O}})} \quad (\text{E-4})$$

Where: ΔSO_2 = SO_2 captured; [moles], $\Delta \text{H}_2\text{O}$ = H_2O evaporated; [moles], P_{SO_2} = partial pressure SO_2 in bulk gas; [atm], $P_{\text{H}_2\text{O}}$ = partial pressure H_2O in bulk gas; [atm], and $P_{\text{H}_2\text{O}}^*$ = partial pressure H_2O at gas-liquid interface; [atm].

Figure E-7 shows the conversions predicted by the model under typical experimental conditions.

Figure E-7. Predicted conversion in the presence of liquid H₂O: (Ca(OH)₂/fly ash sorbent containing 3.65×10^{-3} moles Ca/g sorbent).

The effects of the wet reaction and the reaction occurring in the presence of equilibrium moisture may not be additive, but rather the presence of liquid moisture on the sorbent surface may affect the reaction with equilibrium moisture. The initial free moisture on the sorbent surface is assumed to evaporate instantly during reaction, the differential expression for conversion attributable to reaction in the presence of equilibrium moisture must be integrated over the entire reaction time. The resulting conversion predicted attributable to reaction in the presence of equilibrium moisture will be added to the conversion expected attributable to wet reaction in order to determine the total conversion of the sorbent. This model will be referred to as the Additive Model. When the ambient-moisture portion of the total conversion is predicted accounting for the effect of free moisture, the model will be referred to as the Interactive Model.

The LTDR experimental work addressing the SO_2 -removal performance of $\text{Ca}(\text{OH})_2$ -based sorbents with initial free moisture under DSI conditions was performed in 2 stages. In the first stage, sorbents containing moisture in equilibrium with laboratory RH (~ 50 percent) were exposed to flue gas of varying RH and SO_2 content. In the second stage, water was added to the sorbent so that its water content was above that attained through equilibrium with the room RH. The increase in sorbent conversion with increasing residence time was not as significant for the lower RHs as for the higher RHs, implying that for a given reaction time, greater surface moisture content of the sorbent results in greater conversion. The conversions of the high-surface-area $\text{Ca}(\text{OH})_2$ and the $\text{Ca}(\text{OH})_2$ /fly ash sorbent were approximately the same at all conditions, implying that the sorbent conversion was controlled by the dispersion of Ca throughout this surface area. Figure E-8 presents a comparison between the m^2 sorbent/mole $\text{Ca}(\text{OH})_2$ and sorbent conversion in 5,000-ppm SO_2 flue gas when the sorbent contained moisture in equilibrium with flue gas RH. The $\text{Ca}(\text{OH})_2$ /fly ash and $\text{Ca}(\text{OH})_2$ sorbents fall approximately on the same curves, implying that the dispersion of the $\text{Ca}(\text{OH})_2$ over the sorbent surface area is more important than the quantity of $\text{Ca}(\text{OH})_2$ applied.

Figure E-8. Effect of Ca dispersion on sorbent conversion (5,000 ppm SO₂ in flue gas, 70 °C, 1.0 percent initial moisture on Mississippi Ca(OH)₂, 3.5 percent on Ca(OH)₂/fly ash, 60 to 67 percent RH in flue gas).

The results obtained using Ca(OH)_2 /fly ash sorbent with an initial free moisture in 1,000 ppm SO_2 for 10, 60, and 120 s show the sorbent conversion increases with increasing moisture content and increasing flue gas RH. At high RH, the sorbent conversion increased greatly with increasing initial free moisture content for all reaction times.

Comparisons of theoretical and observed conversions of solids with initial free moisture for various conditions of SO_2 concentration, RH, and contact time were made. The Additive Model correctly predicted the conversion of the Ca(OH)_2 /fly ash sorbent at 0 percent RH in 1,000 ppm SO_2 flue gas for 60 s reaction as shown in Figure E-9. At these conditions, the effect of the equilibrium-moisture reaction was nearly negligible, and the sorbent conversion increased linearly with increasing moisture content. For the other conditions presented, the Additive Model consistently overpredicted the sorbent conversion at high sorbent moisture contents.

The Interactive Model used the same expression as the Additive Model to account for sorbent conversion with free moisture on the sorbent surface. In both models, the predictions accounting for the wet and equilibrium-moisture effects are additive. The Interactive Model assumes that the equilibrium-moisture reaction does not occur with free moisture on the sorbent surface. The Interactive Model also assumes that the rate of sorbent conversion by the equilibrium-moisture mechanism is a function of the amount of product present on the sorbent surface. The Interactive Model underpredicts Ca(OH)_2 /fly ash conversion with 1,000 ppm SO_2 in the flue gas at long times at 55 to 65 percent RH. At these conditions, the equilibrium-moisture conversions are significant. The Additive Model overpredicted the system performance at these conditions. The wet reaction apparently influenced the equilibrium-moisture reaction and the model has overcompensated for this effect.

Figure E-9. Comparison of theoretical and observed conversions of Ca(OH)_2 /fly ash sorbent with initial free moisture (Additive Model, 1,000 ppm SO_2 in flue gas, 70 °C, 60 s reaction, 0 percent RH).

The STDR previously used to identify a rate-limiting step for the reaction of dry Ca(OH)_2 with SO_2 was used for testing solids with free moisture. Two types of sorbents were used to study the effect of initial free moisture on the conversion with SO_2 : Ca(OH)_2 physically mixed with fly ash and Ca(OH)_2 reacted with fly ash. Work on fundamental mass transfer mechanisms discussed earlier indicated that the conversion of Ca(OH)_2 increased with increases in initial moisture on the solids. In each experiment, 6 mg of dry Mississippi Ca(OH)_2 was physically mixed with 20 or 30 mg of Meredosla moist fly ash. Another type of sorbent tested was chemically reacted fly ash with Ca(OH)_2 . These sorbents were produced by slurrying fly ash with reagent grade Ca(OH)_2 at varying weight ratios, elevated temperature, and prolonged slurrying time. Their slurrying conditions and structural properties are presented in Table E-1.

TABLE E-1. STRUCTURAL PROPERTIES OF FLY ASH/ Ca(OH)_2 SORBENTS

Fly Ash Source	Fly Ash Type	Slurrying		Fly Ash/ Ca(OH)_2 Weight Ratio [g/g]	Sorbent		
		Time [h]	Temperature [°C]		Surface Area [m^2/g]	Pore Vol. [cm^3/g]	Median Pore Size [Å]
Meredosla	U ^a	8	90	3:1	6.9	0.039	225
Meredosla	G ^b	3	90	3:1	27.4	0.122	178
Meredosla	G	3	90	2:1	17.5	0.100	229
Meredosla	G	3	90	1:1	16.6	0.132	239
Meredosla	G	8	90	3:1	33.2	0.167	201
Meredosla	G	24	90	3:1	47.0	0.213	180
Clinch River	G	3	90	3:1	30.2	0.132	174
Beverly	G	3	90	3:1	18.6	0.082	-

U = Unground fly ash

G = Ground fly ash

Moist sorbents were exposed to 2,000 ppm SO_2 in the STDR operated at 11 °C approach to saturation, which corresponded to approximately 60 percent RH. The results for moist Ca(OH)_2 /fly ash mixtures are presented in Figure E-10. Higher conversions were measured for sorbents with increased levels of initial free moisture than for dry Ca(OH)_2 . For a given residence time, the conversion

Figure E-10. Baseline tests with dry Meredosia fly ash added to dry Mississippi Ca(OH)₂ (STDR, 2,000 ppm SO₂, 60 percent RH).

generally increased with increased initial free moisture contents of solids. The effect of initial free moisture was more pronounced at longer residence times.

Chemically reacted fly ash/ $\text{Ca}(\text{OH})_2$ sorbent was rewetted to yield 3 levels of initial free moisture: 8.5, 12, and 40 percent. The results are shown in Figure E-11. For each initial moisture content tested, the conversion increased with increased residence time. The conversion after any residence time increased with increased initial free moisture contents (except 0.3 s). For the residence time range tested, chemically reacted fly ash/ $\text{Ca}(\text{OH})_2$ sorbent consistently had higher conversions than physically mixed fly ash/ $\text{Ca}(\text{OH})_2$ sorbent. The difference between the 2 sorbents was more pronounced for longer residence times.

Figure E-12 presents results for the fly ash/ $\text{Ca}(\text{OH})_2$ sorbent for which the initial free moisture was varied from equilibrium (no moisture added) up to 60 weight percent. Maximum conversion, measured for longer residence times (3 and 5 s) of fly ash/ $\text{Ca}(\text{OH})_2$ sorbent ($27.4 \text{ m}^2/\text{g}$) in the STDR, occurred for solids with 30-40 weight percent initial moisture.

Figure E-13 shows conversions measured after 5 s residence time in the STDR, operated at 60 percent RH and with 2,000 ppm SO_2 . Initial free moisture content tested ranged from equilibrium to 60 percent. Maximum conversion with SO_2 measured for each sorbent with varying surface area increased as sorbent-specific surface area increased. For 6.9, 27.4, 33.2, and $47.0 \text{ m}^2/\text{g}$ sorbents tested, the corresponding maxima were 12.3, 15.2, 17.5, and 25.1 percent respectively. The initial free moisture content, for which the maximum conversion for a given sorbent was measured, varied with the sorbent's specific surface area. The initial free moisture contents of the 4 aforementioned sorbents, for which the maximum conversion with SO_2 was measured, were 30, 30, 40, and 50 percent, respectively.

A sorbent with $27 \text{ m}^2/\text{g}$ specific surface area was used to investigate the effect of the approach to saturation on the conversion of sorbents with 60 weight percent initial free moisture and with only equilibrium moisture content. Only a very weak effect was detected of an approach to saturation (2.8 to

Figure E-11. The effect of initial free moisture on the reactivity of chemically reacted fly ash/ Ca(OH)_2 (STDR, 2,000 ppm SO_2 , 60 percent RH).

Figure E-12. Effect of initial free moisture on the reactivity with SO₂ of 27.4 m²/g sorbent (ground Meredosia fly ash/Ca(OH)₂ weight ratio of 3:1; reactor: 60 percent RH, 2,000 ppm SO₂).

Figure E-13. Effect of sorbent specific surface area on the reactivity of moist sorbent (Meredosia fly ash/ Ca(OH)_2 weight ratio of 3:1; reactor: 60 percent RH, 2,000 ppm SO_2).

22 °C range) on the conversion of 60 percent initial free moisture sorbent with 2,000 ppm SO₂ gas. No significant effect was detected of an approach to saturation on conversion with SO₂ for long (5 s) residence time in the STDR. At short (0.5 and 1 s) residence times, higher conversions were measured for sorbent exposed to dry gas than for sorbent exposed to humid gas.

In order to evaluate solids moisture capacity, a sample was placed on an 80-mesh sieve (177 µm between wires) and shaken for 10 min. Tests were run on samples with varying amounts of moisture to determine the amount of moisture that caused half the sample to be retained by the 80-mesh sieve. This amount was called the critical moisture (grams of water/g of wet solids expressed as a percentage). The moist sample was spread uniformly over the sieve, the lid placed on, and the assembly placed in a mechanical sieve shaker (without a tapping device) and shaken for 10 min.

To relate critical moisture content to a more commonly measured sorbent property, values were plotted against specific surface area. Figure E-14 shows that critical moisture content increases with surface area. The data are from all fly ash/Ca(OH)₂ sorbents tested in this study, and, therefore, reflect a broad range of preparation conditions. Most of the surface area of these sorbents occurs in the particle pore space, which is filled, to some degree, by water when it is added to the dry sorbent. When moist sorbent agglomerates, much of the moisture may be hidden in the particle pore space. Therefore, critical moisture content may correspond more directly to pore volume than to surface area. Figure E-15 shows the results of critical moisture tests, expressed as a ratio of water-to-dry solid, plotted versus particle-specific pore volume. The relationship is nearly 1:1; that is, each mL of pore space corresponds roughly to 1 mL of absorbed water at the critical moisture content. If the pore space was completely filled with water, the moisture ratio at the critical moisture content would be greater than the pore volume because water is needed outside the pore space to cause agglomeration. However, water added to a dry solid does not necessarily fill all the pore space, so the critical volume of water need not equal the pore volume.

Figure E-14. Correlation of the moisture data (points represent all fly ash/Ca(OH)₂ sorbents, including duplicates, tested during this study; silica sources were Clinch River fly ash, ground Clinch River fly ash, Harrington fly ash, and silica fume).

Figure E-15. Correlation of critical moisture ratio at the critical moisture content.

Most of the reactants tested were relatively low surface area materials with correspondingly low critical moisture. The exception was Ca(OH)_2 which had an area of $20 \text{ m}^2/\text{g}$, yet had a critical moisture content of zero. The zero-value critical moisture content for the small particles may occur because these Ca(OH)_2 particles can pack closer, allowing attractive forces to exert a greater influence. The poor critical moisture content of Ca(OH)_2 can be diluted by mixing it with other materials. Therefore, whereas Ca(OH)_2 has a poor critical moisture content (it falls below the correlation with surface area), its effect on mixtures can be diluted. The behavior of dry mixtures is not accurately predicted by simply averaging on a mass basis the values of the pure reagents.

Sorbent preparation from Clinch River fly ash and the reactivity of those sorbents toward SO_2 has been studied extensively at Acurex Corporation and the University of Texas. Therefore, Clinch River fly ash was used as a baseline material in this study. The critical moisture content of fly ash/ Ca(OH)_2 sorbents increased with slurry time up to 8 h. A significant difference in values was not detected between sorbents prepared from 3:1 and 4:1 ratios, and values were comparable for the same composition prepared on different occasions. $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ did not have an effect on either critical-moisture content or surface area. $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ mixed with $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ did not have an appreciable effect on critical moisture. The effect of $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ was not pronounced at short slurry times but may be more pronounced at longer slurry times. Results from ground Clinch River ash, which reacts faster than unground ash, show that $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ enhanced critical moisture after 8 h.

Ground Clinch River fly ash produced sorbents with a greater critical-moisture content than those from unground ash. The increase in critical moisture over that of sorbents from unground fly ash is shown in Figure E-16 for several slurry compositions. Also shown is the enhancement of critical moisture after 8 h of reaction with $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ and $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ in the slurry. Recycle materials enhanced surface area after only 6 h of slurry reaction with ground ash, whereas unground ash required 12 h.

Figure E-16. Effect of fly ash grinding and the presence of $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ on critical moisture content (all samples slurried for 8 h, slurry composition represented as g Clinch River fly ash/g $\text{Ca}(\text{OH})_2$ /g $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ /g $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$).

The fly ash/ $\text{Ca}(\text{OH})_2$ ratio in the slurry is an important process variable. Fly ash/ $\text{Ca}(\text{OH})_2$ ratio was varied over the range from 1:4 to 4:1 in slurries of ground fly ash with $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ and $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$. A maximum in both critical moisture and surface area occurred at a 1:1 fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio when the slurry time was 8 h. The high availability of silica and large calcium content in high-calcium fly ash suggest that it would make an attractive reagent for sorbent production. $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ enhanced critical moisture, as it did surface area, in slurries of high-calcium fly ash with $\text{Ca}(\text{OH})_2$. The data indicate that $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ was not beneficial unless $\text{Ca}(\text{OH})_2$ was present. A minimum amount of $\text{Ca}(\text{OH})_2$ appears to be required to achieve fly ash activation, but greater amounts were of no additional benefit.

Pilot plant (50 cfm) was used for evaluation of DSI mass transfer enhancement by the recycle operation. The first test series was to evaluate the baseline performance to establish the $\text{Ca}(\text{OH})_2$ utilization and data reproducibility of once-through operations for DSI downstream of the humidifier. The major operating parameters are listed in Table E-2. Fly ash from the Meredosia Power Plant was injected into the flue gas at a rate equivalent to 1.1 gr/acf dust loading. Mississippi $\text{Ca}(\text{OH})_2$ was used as the sorbent and was injected into the duct after the humidifier. Therefore, no sorbent wetting was expected by water droplet/sorbent particulate collision. The average SO_2 removal observed after 6 runs on the pilot plant was about 27 percent at a calcium-to-sulfur ratio of 2.0. Therefore, the $\text{Ca}(\text{OH})_2$ utilization was about 13.5 percent. Following establishment of the baseline once-through operation, the effect was evaluated of recycle on DSI downstream of the humidification zone. Very little improvement in SO_2 removal was accomplished by recycle operation during the third recycle test, which should provide a fairly close simulation of the long-term, steady-state recycle operation. The pilot plant data indicate that the recycle material rapidly lost its reactivity toward SO_2 after the first pass. The absorbed SO_2 is suspected to form CaSO_3 crystals on the surface of $\text{Ca}(\text{OH})_2$, which tends to block the active surface and plug the pores. As a result, the recycled $\text{Ca}(\text{OH})_2$, although less than 30 percent utilized, became almost nonreactive toward SO_2 after the second pass.

TABLE E-2. PILOT PLANT OPERATING CONDITIONS

Operation	Conditions
Flue gas temperature	149 °C
Flue gas SO ₂ concentration	2,000 ppm
Simulated fly ash loading	1.1 gr/acf at 149 °C
Duct residence time	~ 2 s
Calcium-to-sulfur ratio	2.0
Approach to saturation	11 °C
Recycle ratio	2.0

In the next series of pilot plant runs, the effect was evaluated of the recycle operation on DSI upstream of the humidifier. Significant wetting was expected by water droplet/sorbent particulate collision. The major operating parameters were the same as for DSI downstream of the humidifier (Table E-2). After significant hardware modifications and several trial-and-error tests, stable operation of pilot testing was sustainable for up to 4 h at an approach to saturation temperature of 14 to 17 °C. Higher SO₂ removal was accomplished when the sorbent was injected upstream rather than downstream. Following the once-through DSI tests upstream of the humidifier, the effectiveness of recycle was evaluated with sorbent and recycle material injected upstream of the humidifier. Again, considerable operating problems included wet deposits on the walls, pluggage of sorbent dispersion section, and sorbent build-up around the spraying section. After several trial-and-error tests and some modifications of operating procedures, stable operation was sustainable for up to 3 h at an approach to saturation of 14 to 17 °C. Significant SO₂ removal enhancement was achieved by DSI recycle upstream of the humidifier.

As discussed above, DSI recycle downstream of the humidifier was not significantly beneficial. The majority of the Ca(OH)₂ recycled remained unused after the particulate collector. By grinding partially reacted Ca(OH)₂, the active surface area may possibly be restored, resulting in additional SO₂ removal. Solids intended for dry grinding were taken from the pilot plant baghouse catch and dry ground in a bench-scale attrition grinder for 15 min. Following grinding, the increase in specific surface area and porosity was measured. Reactivity of ground solids with SO₂ was tested in the STDR operated at 60 percent RH (11 °C approach to saturation) and with 2,000 ppm SO₂. The reactivity of

"as-received" baghouse catch was measured first, followed by solids ground for 15 min. Reactivity with SO_2 was significantly enhanced by dry grinding baghouse catch.

Following DSI, solids from the baghouse catch would contain inherent fly ash and spent $\text{Ca}(\text{OH})_2$. To simulate the effect of fly ash on reactivity of ground spent $\text{Ca}(\text{OH})_2$, baghouse catch solids were dry mixed with fly ash prior to grinding.

Reactivity of ground, spent $\text{Ca}(\text{OH})_2$ /fly ash solids with SO_2 was tested in the STDR operated at 60 percent RH (11 °C approach to saturation) and with 2,000 ppm SO_2 . Under conditions of the STDR, 15-min dry ground solids were significantly more reactive with SO_2 than unground solids. Reactivity difference was more pronounced at longer residence times in the STDR (3 and 5 s).

E.6 CONCLUSIONS

Based on fundamental mass transfer investigations in the STDR, gas phase mass transfer and chemical reaction steps could be excluded as rate limiting. This leaves solid phase diffusion as a rate limiting step in the reaction of $\text{Ca}(\text{OH})_2$ with SO_2 under conditions of DSI.

Based on global reactivity testing in the LTDR, the conversion of a given calcium-based reagent was most strongly affected by the flue gas RH. At moderate to high relative humidities, conversion was a strongly increasing function of residence time. The effect of higher flue gas SO_2 concentration was limited.

Given identical reaction conditions, conversion of the Clinch River fly ash/ $\text{Ca}(\text{OH})_2$ sorbent attained a higher value than did the Mississippi $\text{Ca}(\text{OH})_2$. Differentiation between the sorbents was probably due largely to their BET surface areas (measured in m^2/gram of $\text{Ca}(\text{OH})_2$ in the reagent). Conversion of the fly ash/ $\text{Ca}(\text{OH})_2$ sorbent could approach 100 percent given sufficient RH and residence time.

The carbonation of commercial Mississippi $\text{Ca}(\text{OH})_2$ was enhanced by the presence of moisture in the flue gas. Increased initial surface area of $\text{Ca}(\text{OH})_2$ could increase the amount of CO_2 combined with the sorbent. For any surface area sorbent tested, the percent carbonation was higher for humid than dry N_2/CO_2 gas. No significant effect of SO_2 presence on the extent of carbonation of $\text{Ca}(\text{OH})_2$

was found. For practical range to concentration (0-10 vol percent) the effect of CO_2 on reactivity of $\text{Ca}(\text{OH})_2$ with SO_2 was insignificant.

Initial equilibrium moisture content of sorbent (measured by TGA) was a function of conditioning scheme. For dry, warm nitrogen conditioning, the moisture content was increasing with increasing surface area of sorbent. There was more initial moisture on the fly ash/ $\text{Ca}(\text{OH})_2$ sorbent than on any Mississippi $\text{Ca}(\text{OH})_2$ sorbent. Reactivity of fly ash/ $\text{Ca}(\text{OH})_2$ was approximately twice that of $\text{Ca}(\text{OH})_2$. Conversion in the STDR was increasing with the initial amount of moisture on the sorbent (as detected by TGA) conditioned with dry, warm nitrogen.

At 2,000 ppm SO_2 and 60 percent RH, the presence of up to 30 percent initial free moisture significantly increased sorbent reactivity with SO_2 , compared with sorbent reactivity with equilibrium amount of moisture. For any initial free moisture content tested, fly ash/ $\text{Ca}(\text{OH})_2$ sorbent was more reactive than a physical mixture of fly ash and $\text{Ca}(\text{OH})_2$. Maximum conversion for 5 s residence time in the STDR and 60 percent RH (11 °C approach to saturation) was measured for sorbents with 30 to 50 weight percent initial free moisture. The conversion decreased when the initial free moisture increased beyond 30 to 50 weight percent. The initial free moisture content and corresponding level of maximum sorbent conversion with SO_2 varied with the surface area of the sorbent. Conversion of solids with initial free moisture was not affected by the approach to saturation in the STDR for short residence times of 0.5 and 1 s. With longer residence time of 5 s, conversion in the STDR increased with decreasing approach to saturation. For sorbents with comparable surface areas, fly ash source (2 fly ashes tested) did not have a significant effect on reactivity of solids with initial free moisture.

Reaction could be adequately modeled between fly ash/ $\text{Ca}(\text{OH})_2$ sorbent with initial free moisture and low concentration SO_2 and $\text{Ca}(\text{OH})_2$ sorbents with initial free moisture and high concentration SO_2 , assuming that the wet reaction is gas phase, mass transfer controlled and that the products of the wet reaction affect the progress of the equilibrium-moisture reaction. The conversion of the $\text{Ca}(\text{OH})_2$ and fly ash/ $\text{Ca}(\text{OH})_2$ sorbents as a result of wet reactions affected the surface properties

of the sorbents and the extent of equilibrium moisture conversion that occurred upon evaporation of the free moisture.

A procedure was developed to measure the agglomeration of damp fly ash/ $\text{Ca}(\text{OH})_2$ sorbents. Agglomeration of damp fly ash/ $\text{Ca}(\text{OH})_2$ sorbents was a function of sorbent pore volume. Critical moisture also increased with specific surface area. The correlation between critical moisture and surface area was independent of fly ash type (low- and high-calcium ash), fly ash grinding, and recycle materials.

Pilot plant data indicated that the recycle material lost its reactivity toward SO_2 after the first pass. Very little improvement in SO_2 removal was accomplished by DSI recycle downstream of the humidifier. Significant SO_2 removal enhancement was achieved for DSI recycle upstream of the humidifier.

Reactivation of spent DSI solids by dry grinding was possible. Dry ground spent DSI solids were significantly more reactive than unground one.

SECTION 1

DUCT INJECTION PROGRAM OVERVIEW

In 1988, the Department of Energy Pittsburgh Energy Technology Center (DOE-PETC) initiated a broad program to develop duct injection technology for the reduction of sulfur dioxide (SO₂) emissions from existing coal-fired plants. Duct injection program follows three proof-of-concept tests programs sponsored by DOE that indicated duct injection was successful at achieving 50 percent SO₂ removal: Bechtel National's Confined Zone Dispersion Process, General Electric Environmental Services' In-Duct Scrubbing Process, and Dravo Lime Company's Hydrate Addition at Low Temperature Process. Current program consists of five major components: Duct Configuration Survey (Burns and Roe Services), Enhanced Sorbent Utilization (Acurex Corporation and Energy and Environmental Research Corporation), Fundamental Investigation of Duct and ESP Phenomena (Radian Corporation), Scale-up Tests and Supporting Research (Gilbert/Commonwealth), and Duct Injection Technology Prototype Development (United Engineers and Constructors).

As of this report date (January 1992), the Duct Configuration Survey was completed and assembled into a database. The survey indicated the number of facilities with ducts suitable for possible installation of duct sorbent injection. Energy and Environmental Research Corporation completed their Enhanced Sorbent Utilization study, which investigated mass transfer on a global basis by combining fundamental droplet experiments with development of a predictive model. Fundamental Investigation of Duct and ESP Phenomena was conducted by Radian in a 1.7 MW pilot plant in Central Illinois Public Service Company's Meredosia Power Plant. The study has been completed, and among other findings, indicated the advantage of conducting the dry sorbent injection in a scavenging mode

(sorbent injection upstream of humidification). The ongoing efforts under the duct injection program include testing at the 12 MW Duct Injection Test Facility (DITF) located at the Ohio Power Company's Muskingum River Station in Beverly, Ohio, and operated by Gilbert/Commonwealth and Southern Research Institute. Another ongoing effort is the Duct Injection Technology Prototype Development by United Engineers and Constructors. Prototype Development project uses results from all laboratory and pilot plant tests combined with supporting test work of subcontractors. The end result will be the publication of the Design Handbook (of which the preliminary version has been completed) and of the Predictive Mathematical Model.

This Final Report describes results from the Enhanced Sorbent Utilization Study conducted by Acurex Corporation and the Department of Chemical Engineering at the University of Texas since late 1988. The work was performed under Contract No. DE-AC22-88PC898874 "Theoretical Approach for Enhanced Mass Transfer Effects In Duct Flue Gas Desulfurization Processes". This report is arranged into two volumes: Volume I - Dry Sorbent Injection, and Volume II - Duct Spray Drying. The objectives of Acurex/University of Texas work were threefold: determine the controlling physical and chemical processes which limit sorbent utilization, examine various techniques which are capable of sorbent utilization improvement, and evaluate various sorbents, operating conditions and process schemes to support pilot-scale field testing and demonstration. Acurex key personnel included: Dr. Wojciech Jozewicz, Dr. John C. S. Chang, Brent Hall, and Carl Singer. University of Texas key personnel included: Dr. Gary T. Rochelle with Stephen P. Beaudoin, Lynn M. McGuire, Charlotte Stromblad, David E. Stroud, and William G. White.

SECTION 2

INTRODUCTION

Reductions in SO₂ emissions from coal fired electric utilities are mandated by the 1990 amendments to the Clean Air Act. Coal combustion is used to supply more than one-half of the electrical power demand in the United States. In the process, it accounts for more than 65 percent of U.S. manmade SO₂ emissions (NAPAP, 1990). Utilities can reduce emissions from existing boilers by: (1) retiring boilers that do not have SO₂ controls, (2) repowering for other fuels or with new combustion technology, (3) removing sulfur from coal before combustion (coal cleaning), (4) switching to low sulfur coal, or (5) retrofitting with flue gas desulfurization.

A variety of processes are available for flue gas desulfurization (FGD) and they are not limited to retrofit applications; in fact, nearly 25 percent of the current coal fired utility generating capacity already has FGD; but, there is an opportunity for retrofit applications to achieve additional emissions reductions. A retrofit application generally should have low capital cost and minimal space requirements. SO₂ removal somewhat less than that achievable by state-of-the-art technology which would be applied to new boilers is acceptable in many cases. Limestone slurry scrubbing is the state-of-the-art for FGD. It is used at 99 of the 135 utility boilers with FGD (Peterson, 1990). Slurry scrubbing can achieve greater than 90 percent SO₂ removal. It is a mature technology and is generally the control technology chosen for a new boiler. It is not well suited for retrofit applications because of its high capital cost and space requirements.

Duct injection of sorbents is an emerging technology for emissions reduction that is attractive for retrofit applications. Development of the technology has focused on increased sorbent reactivity.

Reactivity is enhanced by free moisture on the sorbent, but large amounts of moisture may adversely affect sorbent handling and utilization, as well as system reliability. As duct injection technology begins large pilot scale and demonstration scale development, these effects become of greater interest. In this process, sorbent is injected into the existing ductwork as a slurry [duct spray drying (DSD)], a dry solid with gas humidification [dry sorbent injection (DSI)], or a damp solid. The sorbent reacts with the SO_2 in the flue gas to form calcium sulfite and is removed from the system as a dry solid by existing particulate control equipment. Duct injection is attractive for retrofit applications because minimal new equipment is required, resulting in lower capital costs and space requirements than slurry scrubbing. Development of DSD and DSI has been hampered by the occurrence of wall deposits which reduce system performance and reliability. Damp solids injection seeks to obtain the benefits of sorbent free moisture while avoiding wall deposits.

This report presents the results of fundamental mass transfer testing for in-duct removal of SO_2 . Following this initial part of an experimental program, it became clear that the amount of initial moisture on the sorbent strongly affected the extent of $\text{Ca}(\text{OH})_2$ conversion (Section 4). Novel techniques aimed at increasing sorbent utilization were investigated and are described in Section 5. Major novel technique investigated and reported on here was the reaction with SO_2 of sorbents with an initial free moisture (damp sorbents). The duct injection process using damp solids (shown in Figure 2-1) has the following steps: preparation of sorbent as a slurry, blending of the slurry with dry recycle materials to create damp solids, injection of the solids into the duct, reaction and drying of the solids with flue gas in the duct, collection in particulate control equipment, and finally recycle of dry solids with some bleed to disposal. The moisture content of the solids at each step affects system performance. Various factors favor high moisture whereas others favor low moisture.

Reaction with SO_2 occurs as the sorbent is transported by flue gas through the duct and also during the time that it is retained by particulate control equipment. Sorbent agglomerates less than $100\ \mu\text{m}$ containing free moisture can be expected to dry an equilibrium moisture content within the 1 to 2 s residence time in the duct. Pilot studies have shown five to seven percent equilibrium

Figure 2-1. Schematic of duct injection with damp solids.

moisture on fly ash/ $\text{Ca}(\text{OH})_2$ sorbents collected in a baghouse with an 11 °C approach to saturation (Chang and Sedman, 1989). The moisture content was the same whether the sorbents were injected dry or with greater than 7 percent moisture. Therefore, damp solids can be used to humidify the flue gas, thus reducing or replacing the water injection necessary with dry solids injection.

The reaction of sorbent containing equilibrium moisture is affected by relative humidity (RH) and sorbent surface area. Reactivity [$\text{Ca}(\text{OH})_2$ conversion] increases with RH (Jozewicz and Rochelle, 1986; Rochelle et al., 1990). The humidification limit is generally a 10 to 20 °C approach to saturation to avoid condensation. Reactivity also increases with specific surface area because there is greater area for the gas/liquid reaction to occur (Jozewicz et al., 1988a; Peterson and Rochelle, 1988). When moisture in excess of equilibrium amounts is present, damp sorbent reactivity [$\text{Ca}(\text{OH})_2$ conversion] is even greater (Chang and Sedman, 1989).

Damp solids are beneficial for dust collection because they humidify the gas, resulting in a greater equilibrium moisture content on the dust. The moisture lowers the particle resistivity which can aid dust collection by ESPs. Increases in sorbent moisture introduce the problem of sticky solids, which are difficult to handle and inject, may form wall deposits, and which agglomerate, resulting in lower utilization. The mechanisms of agglomeration due to moisture and solids moisture capacity were also investigated.

Another novel technique described in Section 5 is grinding of recycle DSI solids in order to increase the availability and subsequent utilization of $\text{Ca}(\text{OH})_2$. Section 6 presents conclusions and Section 7 lists references used throughout this study.

SECTION 3

EXPERIMENTAL

3.1 SHORT TIME DIFFERENTIAL REACTOR

A short time differential reactor (STDR) is a fixed bed reactor in which sorbent dispersed on a quartz wool is rapidly moved into the process gas stream and then extracted after a preset exposure time. The STDR apparatus shown in Figure 3-1, is centered around a pneumatically actuated sample slider assembly. The slider assembly is made of polytetrafluoroethylene (PTFE) as shown in detail in Figure 3-2. This construction allows an inert carrier for the sample. To activate the slider assembly the start button is pushed, which simultaneously activates the 4-way valve and starts the timer. The valve then allows the compressed gas (90 psi) to move the sample slider assembly. This results in positioning the sample bed holder under the reactive process gas. The valve reverses the flow of gas and drives the piston and connected sample slider assembly after the preset time expires.

The sorbent sample is supported by a wire mesh, which holds a thin bed of quartz wool containing the dispersed sorbent. Another thin layer of quartz wool is placed on top of a thin bed containing the dispersed sorbent. This additional layer prevents sorbent carryover as a result of rapid actuation of the slider assembly by the 4-way valve. To investigate the effect of sorbent conditioning, the sample may reside under a stream of nitrogen with controlled temperature and humidity. The sample slider is constructed in such a way as to allow for an uninterrupted gas flow. This prevents a sudden pressure buildup while sliding the sample bed from the nitrogen flow to the reactive gas flow.

The process gas is conditioned to a desired temperature and RH. The RH is attained by the injection of water into the evaporation chamber heated between 130 and 180 °C. Syringe pump from

Figure 3-1. Short time differential reactor (STDR) system.

Figure 3-2. Slider assembly.

Figure 3-3. Long time differential reactor (LTDR) system.

The experiments were conducted using a packed bed reactor (5 cm diameter x 7.5 cm height) in which the solid reagent (approximately 15 mg) was suspended in quartz wool and supported on a fritted glass disk. The reactor and associated preheat tubing were immersed in a water bath controlled at 66 °C. After the reactor had warmed up (for a minimum of 10 min), the solids were exposed to flue gas. The dry synthetic flue gas was 10 percent CO₂, 7 percent O₂, and 83 percent N₂. The SO₂ flow was manually controlled with a needle valve, and the concentration in the flue gas was confirmed by SO₂ analyzer. RH was maintained by sparging the nitrogen and air into two 5,000 mL water-filled flasks contained in a separate water tank from the reactor. The solids were preconditioned by first exposing them to humid nitrogen for 2 min and then nitrogen at the desired RH for 2 min. The reaction system was designed for reaction times ranging from 10 s to 1 h or more.

Conversion of the reacted solids was determined by first dissolving them in approximately 10 mL of 0.1 N HCl solution and adding 10 drops of 30 percent hydrogen peroxide to oxidize any sulfite to sulfate. The reaction productions were then allowed to dissolve for about 20 to 30 min. The solution was filtered, diluted, and tested for presence of sulfate with an ion chromatograph (IC). A given solution was tested in the ion chromatograph two or three times and the results averaged.

3.3 PILOT PLANT FACILITY

The pilot plant facility used in the present work incorporates a Niro Atomizer Mobile Minor spray dryer facility. The spray dryer has been retrofitted with additional ductwork downstream of the spray dryer vessel, plus a dry sorbent injection system, a Dustex pulse-jet baghouse for particulate collection, and a stainless steel fan (Cincinnati Fan & Ventilator Co.) for exhausting the cleaned gas into the atmosphere. The pilot plant arrangement is depicted in Figure 3-4.

Air flow is drawn from ambient through an air filter and an electrical heater. The heated air enters the spray dryer chamber through an air disperser located in the center of the chamber roof. The air disperser is designed to swirl the air flow around the rotary atomizer wheel from which water, or slurry, is atomized. The rotary atomizer is equipped with an abrasion resistant stainless steel wheel with 4 silicon carbide inserts, with an inside diameter of 2 mm. The wheel is mounted on a high speed

Figure 3-4. Schematic of duct injection pilot plant facility.

spindle which is driven by a compressed air turbine. The compressed air is supplied at a pressure of around 5 bar (75 psig), which normally provides an atomizer speed around 40,000 rpm. Feed liquid (slurry or water) is pumped to the atomizer wheel and atomized into a fine spray of droplets. The droplet spray into the hot air causes very rapid evaporation of the water and simultaneously cools the air stream inside the insulated chamber. The spray dryer diameter is 800 mm and its total volume is 0.42 m^3 , providing for a gas retention time of approximately 15-20 s based on the outlet gas conditions. For dry injection tests, the spray dryer served as a humidifier to condition the flue gas humidity and temperature to desired level.

The gas (and any dried sorbent) is drawn off at the base of the chamber through a 50 mm diameter heat traced and isolated duct section. Different lengths of duct section, 9.8 m in length or, alternatively, 24.4 m, provide gas retention times of 0.8 s or 2 s. A dry sorbent injection system is installed at the vertical duct section just downstream of the spray dryer vessel upstream of the main duct section). The injection system consists of a Vibra Screw or AccuRate Model 604 volumetric feeder, equipped with a helix (19-44 mm diameter) for feeding the dry or semidry sorbent directly into the duct. Another dry sorbent injection point is located on the top of the spray dryer vessel (upstream of the spray dryer).

The dry particulates are collected by the pulse-jet baghouse equipped with 4 polyester bags, providing a total solids collection area of 2.3 m^2 . A rotary air lock discharges, batchwise, the collected solids from the baghouse hopper. Alternatively, a cyclone separator (from Niro Atomizer's Mobile Minor unit) with a cut size of about $3 \mu\text{m}$ can be inserted just upstream of the baghouse to collect a large fraction (normally 80-95 percent) of the particulates. This cyclone has been equipped with a vortex breaker and a bucket for continuously discharging the particulates from the flue gas system. Both the baghouse and the cyclone are insulated, and the baghouse hopper is also equipped with electrical heaters to minimize heat loss. An induced draft fan located downstream of the baghouse provides negative pressure in the entire simulated flue gas system. It also exhausts the cleaned gas into the atmosphere through the roof of the building via a PVC pipe stack (inside diameter 78 mm).

The SO₂ concentrations throughout the system were determined by extractive sampling from the spray dryer inlet duct, the spray dryer outlet duct, and cyclone outlet duct/baghouse inlet duct. The extractive sampling system was made of a filter which separates the solid and gas in the gas samples. The filter was heat traced and the temperature was maintained above 100 °C. The gas samples were constantly pumped through heated sample lines at 150 °C to continuous SO₂ monitors. A DuPont 411 ultraviolet spectrophotometer and a Thermo Electron Model 40 pulsed fluorescent analyzer were used. Calibrations were conducted on a daily basis using commercially available span gases of SO₂ in nitrogen or air for the DuPont analyzer, and SO₂ in air for the Thermo Electron analyzer.

Temperatures, pressures, flow rates, SO₂ concentrations, etc. were recorded every 1/2 h during a 4-8 h test run at fairly stable conditions. An average value was calculated for each test parameter at the end of the test run and reported for that particular test.

3.4 BASELINE SORBENT SELECTION/CHARACTERIZATION

Mississippi Ca(OH)₂ from Mississippi Lime Company has been selected as the baseline sorbent for experiments with dry hydrated lime. Following the selection, the sorbent structural properties were characterized and are shown in Table 3-1. The specific surface area was measured to be 17 m²/g and porosity 19 percent (the instrument used was a multipoint surface area analyzer ASAP 2400 from Micrometrics). Two other commercially available sorbents, as well as the reagent grade Ca(OH)₂ from Fisher, are also shown in Table 3-1 for comparison of structural properties.

TABLE 3-1. SORBENT SELECTION AND CHARACTERIZATION

Ca(OH) ₂	S _A [m ² /g]	E [percent]	P ₅₀ [Å]	D ₅₀ ^a [μm]
Mississippi	17	19	213	18.5
Longview	16	14	250	--
Linwood	18	15	220	18.0
Reagent Grade Fisher C-97	12	--	--	--

^aMeasured by cascade impactor.

The last column in Table 3-1, D_{50} , is a median particle size of the sorbent measured by the inertial cascade impactor technique. The measured value of D_{50} for Mississippi $\text{Ca}(\text{OH})_2$ was 18.5 μm . While this value is somewhat higher than usually reported for $\text{Ca}(\text{OH})_2$, it may reflect the propensity of the sorbent for agglomeration. D_{50} measured previously by the Sedigraph method was 2.86 μm . The inertial cascade impactor used consists of a preimpactor and 6 trays measuring particles in the 0.52-33.5 μm size range. The sorbent is fed directly from the feeder tube into the impactor through syringe tubing. The particle size distribution measured by the inertial cascade impactor is shown in Figure 3-5. The sample of sorbent was analyzed for the degree of hydration by thermogravimetry (TGA System 7 from Perkin Elmer) and the results are shown in Figure 3-6. Measured weight loss from the starting temperature to 535 $^{\circ}\text{C}$ corresponds to 94 percent $\text{Ca}(\text{OH})_2$ in the sample. The manufacturer's data is shown in Figure 3-7.

The sample of the parent CaO (Mississippi CaO) intended for use in the future slaking tests was also characterized. The measured specific surface area and porosity were 1.2 m^2/g and 3 percent, respectively. Median particle size, D_{50} , was measured to be 20 μm (inertial cascade impactor) and the particle size distribution for Mississippi CaO is shown in Figure 3-8. The relatively small difference between D_{50} of Mississippi $\text{Ca}(\text{OH})_2$ and CaO may result from the fact that the number for CaO represents "true" particle size for CaO , since a significantly smaller extent of agglomeration is known to take place for this material than for $\text{Ca}(\text{OH})_2$. This is evident from the SEM photographs of CaO and $\text{Ca}(\text{OH})_2$ presented in Figures 3-9 and 3-10, respectively. Large agglomerates of micron/submicron unit particles can be seen in Figure 3-10. The TGA analysis presented in Figure 3-11 reveals that CaO has rehydrated about 11 percent. Manufacturer supplied chemical analysis of CaO is shown in Figure 3-12.

Figure 3-5. Particle size distribution for Mississippi $\text{Ca}(\text{OH})_2$ as measured by cascade impactor.

Figure 3-6. TGA analysis of Mississippi $\text{Ca}(\text{OH})_2$.

Mississippi Lime Company

General Offices

Alton, Illinois 62002-2247

7 Alby Street

Phone: 618-465-7741

MISSISSIPPI ROTARY PLANT

Hydrated Lime

Code MR200

Meets AWWA and Water Chemicals Codex Specifications

Chemical Analysis

Ca (OH) ₂	96.0%	to	97.2%
CaO Equivalent	72.6	to	73.6
CaO Total	73.6	to	74.3
CaCO ₃	0.65	to	1.75
CaSO ₄	0.05	to	0.10
S Equivalent	0.012	to	0.024
SiO ₂	0.38	to	0.65
Al ₂ O ₃	0.20	to	0.30
Fe ₂ O ₃	0.07	to	0.10
MgO	0.04	to	0.55
Free H ₂ O	0.30	to	0.95
P ₂ O ₅	0.008	to	0.012
MnO	0.0015	to	0.0025

Typical Physical Analysis

Minus 100 mesh	100.0%
Minus 200 mesh	98.5
Minus 325 mesh	92.0
Density - pounds per ft ³ - 20 to 32 (Depending upon degree of compaction)	

Figure 3-7. Chemical analysis of Mississippi Ca(OH)₂ (by Mississippi Lime Company).

Figure 3-8. Particle size distribution for Mississippi CaO as measured by cascade impactor.

Figure 3-9. SEM photograph of Mississippi CaO, x 5,000.

Figure 3-10. SEM photograph of Mississippi $\text{Ca}(\text{OH})_2$, x 5,000.

Figure 3-11. TGA analysis of Mississippi CaO.

Mississippi Lime Company

General Offices

Alton, Illinois 62002-2247

7 Alby Street
Phone: 618-435-7741

MISSISSIPPI VERTICAL PLANT

Pulverized Quicklime

Meets AWWA and Water Chemicals Codex Specifications.

Chemical Analysis

CaO - Available	93.0%	to	96.5%
CaO - Total	96.0	to	97.8
CaCO ₃	0.50	to	4.00
CaSO ₄ (Gas Fuel)	0.05	to	0.09
S - Equivalent	0.012	to	0.021
CaSO ₄ (Oil Fuel)	0.22	to	0.46
S - Equivalent	0.053	to	0.108
SiO ₂	0.70	to	1.00
Al ₂ O ₃	0.13	to	0.45
Fe ₂ O ₃	0.07	to	0.10
MgO	0.53	to	0.75
LOI	0.30	to	2.00
P ₂ O ₅	0.010	to	0.016
MnO	0.0019	to	0.0033

Physical Analysis

Minus 100 mesh	99.8%	to	100.0%
Minus 200 mesh	99.0	to	100.0
Minus 325 mesh	97.5	to	99.5
Density - Pounds per ft ³ .. 58		to	78
(Depending upon degree fo compaction)			

Figure 3-12. Chemical analysis of Mississippi CaO (Mississippi Lime Company).

SECTION 4

MASS TRANSFER TESTING

4.1 VERIFICATION OF RATE LIMITING STEP

The conceivable process steps related to the reaction of SO_2 with $\text{Ca}(\text{OH})_2$ in the dry duct injection process are:

- Gas phase mass transfer
- Chemical reaction of SO_2 with $\text{Ca}(\text{OH})_2$
- Solid phase diffusion

The effect of gas phase mass transfer was evaluated by two independent series of experiments. In the first experiment, the regular process gas flow rate (15 SLPM) was decreased to 7.5 SLPM, and conversion was measured for 11 °C approach to saturation (approximately 60 percent RH) and 2,000 ppm SO_2 . The sorbent was conditioned with dry/warm nitrogen prior to injection into the humidified process gas. The results are presented in Figure 4-1. The data show that lime conversion was not affected by changing the gas flow rate. Decreasing the gas flow rate would decrease the gas phase mass transfer coefficient. If the gas phase resistance were controlling, the conversion would decrease with decreasing gas flow rate.

In another set of experiments, the nature of the carrier gas was changed. The carrier gas was 80 vol percent helium and 20 vol percent nitrogen, and the total gas flow rate was 15 SLPM. Conversion of $\text{Ca}(\text{OH})_2$ was measured at 60 percent RH, 2,000 ppm SO_2 , with dry/warm nitrogen conditioning of sorbent prior to injection. The results are presented in Figure 4-2. The data show that $\text{Ca}(\text{OH})_2$ conversion was not affected by changing the nature of the carrier gas. If the gas phase

Figure 4-1. Evaluation of gas phase mass transfer by changing gas flow rate. Commercial Mississippi Ca(OH)₂, 2,000 ppm SO₂, 11 °C approach to saturation.

Figure 4-2. Evaluation of gas phase mass transfer by changing the nature of carrier gas. Commercial Mississippi Ca(OH)_2 , 2,000 ppm SO_2 , 60 percent RH, dry/warm nitrogen conditioning.

resistance were controlling, the conversion would increase for experiments using the mixture of helium/nitrogen as a carrier gas in place of nitrogen only. The diffusion coefficient for a binary mixture of sulfur dioxide/nitrogen at 72 °C, calculated with the Chapman-Enskog formula, is 0.685 cm²/s. The same coefficient for a binary mixture of sulfur dioxide/helium is 2.005 cm²/s. Levenspiel's formula was used to calculate the time, τ , needed for 100 percent conversion when the gas phase resistance is controlling:

$$\tau = \frac{\rho_s \cdot r}{3b \cdot k_g \cdot C_{SO_2}} \quad (4-1)$$

Where: ρ_s = sorbent particle molar density, g mol/cm³; r = sorbent particle radius, cm; b = reaction stoichiometry; k_g = gas phase mass transfer coefficient, g mol/s·cm²; C_{SO_2} = bulk concentration of SO₂ in gas phase, mol/mol.

For this case, $\rho_s = 0.03$ g mol/cm³, $b = 1$, $C_{SO_2} = 2 \cdot 10^{-3}$ mol/mol. It was assumed that the sorbent particle radius was $1.43 \cdot 10^{-4}$ cm. This number is based on a Sedigraph measurement (X-ray sedimentation) that gave median diameter, D_{50} , of commercial Mississippi Ca(OH)₂ equal to 2.86 μ m.

The gas phase mass transfer coefficient was calculated from the Sherwood analogy:

$$Sh = 2 + 0.6 \cdot (Re)^{1/2} \cdot (Sc)^{1/3} \quad (4-2)$$

where:

$$\text{Sherwood Number} = Sh = \frac{k_m \cdot d_p}{c_f \cdot D} \quad (4-3)$$

$$\text{Reynolds Number} = Re = \frac{d_p \cdot u \cdot \rho_g}{\mu} \quad (4-4)$$

$$\text{Schmidt Number} = Sc = \frac{\mu}{\rho_g \cdot D} \quad (4-5)$$

And: d_p = sorbent particle diameter, cm; u = relative velocity, cm/s; ρ_g = gas density, g/cm³; μ = gas viscosity, g/cm · s. For this case, $d_p = 2.86 \cdot 10^{-4}$ cm, $u = 249$ cm/s, $\rho_g = 0.95 \cdot 10^{-3}$ g/cm³, $\mu = 195 \cdot 10^{-6}$ g/cm s, $D = 0.685$ cm²/s.

Inserting the above data in (4-4) and (4-5) yields:

$$Re = \frac{2.8 \cdot 10^{-4} \text{ cm} \cdot 249 (\text{cm/s}) \cdot 0.95 \cdot 10^{-3} (\text{g/cm}^3)}{195 \cdot 10^{-6} (\text{g/cm} \cdot \text{s})} = 0.347 \quad (4-6)$$

and:

$$Sc = \frac{195 \cdot 10^{-6} (\text{g/cm} \cdot \text{s})}{0.95 \cdot 10^{-3} (\text{g/cm}^3) \cdot 0.685 (\text{cm}^2/\text{s})} = 0.3 \quad (4-7)$$

and calculating (4-2) gives:

$$Sh = 2 + 0.6 (0.347)^{1/2} \cdot (0.3)^{1/3} = 2.237 \quad (4-8)$$

Finally, the gas phase mass transfer coefficient is:

$$K_m = \frac{Sh \cdot c_f \cdot D}{d_p} = \frac{2.237 \cdot 3.53 \cdot 10^{-5} (\text{g mol/cm}^3) \cdot 0.685 (\text{cm}^2/\text{s})}{2.86 \cdot 10^{-4} (\text{cm})} = 0.189 \frac{(\text{g mol})}{(\text{s} \cdot \text{cm}^2)} \quad (4-9)$$

where gas molar density, c_f , at 72 °C (345 K) is:

$$c_f = \frac{1}{82.05 (\text{cm}^3/\text{g mol} \cdot \text{K}) \cdot 345 (\text{K})} = 3.53 \cdot 10^{-5} (\text{g mol/cm}^3) \quad (4-10)$$

According to (4-1), the time needed for the complete reaction of a 2.86 μm Ca(OH)₂ particle is:

$$\tau = \frac{0.03 (\text{g mol/cm}^3) \cdot 1.43 \cdot 10^{-4} (\text{cm})}{3 \cdot 1 \cdot 0.189 (\text{g mol/s} \cdot \text{cm}^2) \cdot 2 \cdot 10^{-3} (\text{mol/mol})} = 0.004 (\text{s}) \quad (4-11)$$

It has been assumed that the representative sorbent particle diameter is 2.86 mm. However, this number was obtained from the Sedigraph measurement. This instrument uses dispersant and effectively measures unit particle size by breaking the majority of agglomerates. Considerable agglomeration is known to take place in Ca(OH)_2 sorbent; this finding was documented by the *in situ* measurement of particle size with the inertial cascade impactor, which yielded median particle diameter, D_{50} , of 18.5 μm . The feeder used to deliver particulate matter for the measurement in the impactor is biased toward fine particulate (fluidized bed, secondary agglomeration as a result of vibration). When sorbent was sized with an electron scanning microscope (SEM) agglomerates/particles as large as 50 μm could be seen, as illustrated in Figure 4-3, which shows the general microscope field for Mississippi Ca(OH)_2 . Typical agglomerate size under SEM was between 10-20 μm , as shown in Figure 4-4. Even smaller particles (several μm), such as the one shown in Figure 4-5, appeared to be agglomerates of submicron grains. Considerable caution should therefore be exercised when selecting a representative number for particle size for the calculations of the sorbent injected into the duct.

The time needed to reach 100 percent conversion was also calculated for particle sizes ranging from 2.86-200 μm . The results are shown in Figure 4-6. For the conditions used in the calculations, 0.004 and 7.8 s would be needed for complete conversion of 2.86 and 200 μm agglomerates, respectively. Should gas phase resistance be controlling, 20 μm agglomerate would need 0.16 s for the complete conversion. Measured conversion after 5 s in the STDR was below 2 percent. The comparison is shown in Figure 4-7.

The effect of the chemical reaction was evaluated at two RH levels (30 and 60 percent). Different levels of conversions should be measured for varying temperature in the reactor, should the chemical reaction step be controlling. The results for 30 percent RH are presented in Figure 4-8 for 2,000 ppm SO_2 , with temperature ranging from 50-72 $^{\circ}\text{C}$. The same level of conversion was measured for three different temperatures investigated. The results for 60 percent RH are presented in Figure 4-9. In this case, the Ca(OH)_2 conversion was not significantly affected by temperature

Figure 4-3. SEM photograph of commercial Mississippi Ca(OH)_2 , x 200.

Figure 4-4. SEM photograph of an agglomerate of commercial Mississippi $\text{Ca}(\text{OH})_2$, x 5,000.

Figure 4-5. SEM photograph of a unit particle of commercial Mississippi $\text{Ca}(\text{OH})_2$, x 20,000.

Figure 4-6. Time needed for complete conversion of $\text{Ca}(\text{OH})_2$ particle with SO_2 for gas phase mass transfer controlling; 72 °C, 15 SLPM N_2 , 2,000 ppm SO_2 .

Figure 4-7. Comparison of conversion for the case of gas phase resistance controlling with actually measured conversion in the STDR.

Figure 4-8. Evaluation of the effect of chemical reaction; commercial Mississippi Ca(OH)_2 , 2,000 ppm SO_2 , 30 percent RH, dry/warm nitrogen conditioning.

Figure 4-9. Evaluation of the effect of chemical reaction; commercial Mississippi Ca(OH)_2 , 2,000 ppm SO_2 , 60 percent RH, dry/warm nitrogen conditioning.

changes. In other words, the activation energy was low, and the SO_2 absorption was probably not controlled by chemical reaction.

Following the exclusion of gas phase mass transfer and chemical reaction as possible controlling mechanisms for SO_2 absorption, solid phase diffusion control is the most likely candidate.

4.2 INVESTIGATION OF SOLID PHASE DIFFUSION

The approach to adiabatic saturation temperature (or RH of a process gas) has been recognized as a very important parameter governing the reactivity of sorbent with SO_2 under conditions of duct injection of dry sorbent for SO_2 removal. Baseline sorbent, Mississippi $\text{Ca}(\text{OH})_2$, was used and the sample size was 12 mg. The concentration of SO_2 was 2,000 ppm. The wet bulb temperature was set at 50 °C and the approach to saturation was varied from 11-22 °C which would correspond to approximately 60-30 percent RH of the gas. The results are shown in Figure 4-10, giving the conversion as a function of residence time in the STDR for three approaches to saturation. The conversion of $\text{Ca}(\text{OH})_2$ was increasing with the decreasing approach to saturation (increasing RH).

To eliminate the possibility of sorbent coming in contact with SO_2 prior to its actual injection into the reactor chamber, a special procedure was developed. This procedure included by-passing the reactor by the process gas during the loading of reactor with the sorbent and placing the sample under dry nitrogen stream. The dry nitrogen stream could be heated to the desired temperature. The effect of temperature conditioning with dry nitrogen on the reactivity of Mississippi hydrated lime at 22 °C approach to saturation is shown in Figure 4-11. Two different scenarios of dry nitrogen conditioning are used:

- Room temperature (20-21 °C) N_2
- Dry bulb temperature (72 °C) N_2

For both conditioning scenarios conversion was gradually increasing with increasing residence time in the STDR. Little difference was observed between conversion of sorbents conditioned with dry nitrogen at room temperature and dry bulb temperature. This would imply that the temperature of dry sorbent

Figure 4-10. The effect of the approach to saturation on the reactivity of Mississippi Ca(OH)₂ with SO₂ (2,000 ppm SO₂, dry/warm N₂ conditioning).

Figure 4-11. Temperature conditioning (dry N_2 2,000 ppm SO_2 , $\Delta t_s = 22^\circ\text{C}$).

does not have significant effect on the extent of its subsequent conversion with SO_2 in the humidified gas.

In the next step the effect of the sorbent moisture content on its reactivity was investigated. Sorbent dispersed on the quartz wool was conditioned with water saturated nitrogen at room temperature. This was achieved by bubbling nitrogen through two impingers connected in series. The results are presented in Figures 4-12 and 4-13 for 11 °C and 17 °C approach to saturation, respectively. Higher reaction rates were observed in this case, compared to conditioning with the dry nitrogen. Sorbent subjected to conditioning with water saturated nitrogen would be expected to have an increased amount of moisture on its surface. This moisture would, in turn, enhance the reactivity of the sorbent with SO_2 .

Based on results presented above it seems that the sorbent initial moisture content is important in determining its reactivity with SO_2 . Initial sorbent temperature appears to be of less importance. STDR data showed that the Ca(OH)_2 conversion was affected by the approach to saturation temperature and initial mixture content. However, Ca(OH)_2 conversion was not significantly affected by the flue gas SO_2 concentration. The above data could be explained on the assumption that the SO_2 absorption was solid phase diffusion controlled. The diffusing species was a compound composed of SO_2 and H_2O , and its concentration on the sorbent surface was controlled by the available moisture but not by the available SO_2 .

Several sorbents were produced in order to investigate solid phase diffusion. Varying specific surface area would affect diffusion through the product layer. Ca(OH)_2 samples were produced in a laboratory-scale hydrator consisting of a 0.41 Pyrex beaker suspended in a constant temperature oil bath. A mechanical stirrer was used to mix the water and CaO . Each hydration was conducted by loading 10 g of Mississippi CaO into the hydrator and allowing CaO to achieve thermal equilibrium in the bath. The stirrer was started, and a single, rapid addition of water was syringed into the hydrator at the desired molar ratio of $\text{H}_2\text{O}/\text{CaO}$. After 15 min, the hydration vessel was purged of remaining

Figure 4-12. Moisture conditioning (moist N_2 , 2,000 ppm SO_2 , $\Delta t_g = 11^\circ\text{C}$).

Figure 4-13. Moist conditioning (moist N_2 , 2,000 ppm SO_2 , $\Delta t_g = 1.6^\circ\text{C}$).

water vapor with nitrogen, leaving a thoroughly dry product. The amount of water used was between 2.6 and 10 times the amount stoichiometrically required, and the temperature of solids/liquid was 100 °C/100 °C or 20 °C/20 °C. The properties of produced Ca(OH)_2 are shown in Table 4-1. For 100 °C/100 °C hydration temperature, the amount of water used for hydration (within the range investigated) had only a moderate effect on the specific surface area of the hydrate. There was significant effect of hydration temperature at the constant amount of hydration water. Lowering the temperature of hydration lowered the specific surface area and porosity of Ca(OH)_2 . Hydration of Mississippi CaO was only used here as a means of producing Ca(OH)_2 with a surface area greater than the 17 m²/g measured for commercial Mississippi Ca(OH)_2 . Sorbent number 4 (Miss 4), as shown in Table 4-1 (32 m²/g surface area and 30 percent porosity) was selected for further study of specific surface area effects. The general microscope field representing this sorbent is shown in Figure 4-14. The absence of large particles like those in Figure 4-3 (showing the sample of a commercial Mississippi Ca(OH)_2) is evident. The largest particle in Figure 4-14 for laboratory-produced sorbent is smaller than 25 µm. Figure 4-15 shows fine particles of Miss 4 Ca(OH)_2 . The morphology of these particles is dramatically different from that of particle of commercial Mississippi Ca(OH)_2 , shown in Figure 4-5. Particle in Figure 4-5 seems to be composed of relatively smooth grains of submicron size. The morphology of Miss 4 reveals a well-developed, irregular surface.

TABLE 4-1. MISSISSIPPI Ca(OH)_2

No.	Hydrate Type	Amount of Water [x SR] ^a	Temperature T_S/T_L^b [°C/°C]	Specific Surface Area [m ² /g]	Porosity [percent]	Median Pore Size [Å]
1	Commercial	NA	NA	17	19	225
2	Laboratory	2.6	100/100	28	24	207
3	Laboratory	5	100/100	31	30	240
4	Laboratory	10	100/100	32	30	232
5	Laboratory	5	20/20	20	21	238

^ax SR = times stoichiometric amount

^b T_S = initial temperature of solids; T_L = initial temperature of liquid

Figure 4-14. SEM photograph of laboratory Ca(OH)_2 Miss 4 ($32 \text{ m}^2/\text{g}$, 30 percent porosity), x 200.

Figure 4-15. SEM photograph of laboratory Ca(OH)_2 Miss 4 ($32 \text{ m}^2/\text{g}$, 30 percent porosity), x 20,000.

The reactivity of Miss 4 was measured following different sorbent conditioning scenarios. Sulfation conditions were 2,000 ppm SO₂ and 11 °C approach to saturation. Figures 4-16 and 4-17 present the effect of surface area on reactivity measured after dry/warm nitrogen conditioning and after room air conditioning, respectively. Room air used for conditioning was typically about 22 °C and 60 percent RH. Significant differences between the reactivity of the two sorbents investigated were measured following the dry/warm nitrogen conditioning. The difference between reactivities following room air conditioning was insignificant.

The importance of the initial moisture content is also evident from Figure 4-18. It shows the effect of sorbent conditioning on its reactivity for Miss 4. For longer residence times (3 s and longer), there is a significant difference between the reactivity of sorbent conditioned with water saturated 21 °C nitrogen and sorbent conditioned with dry/warm nitrogen. No significant difference in reactivity was observed at contact times below 1 s.

The effect of evaporation is presented in Figure 4-19. These data were measured by injecting moisture-conditioned sorbent into dry process gas. Commercial Mississippi Ca(OH)₂ was used for these experiments. The sorbent was conditioned with 21 °C water-saturated nitrogen prior to injection into 61 or 72 °C process gas containing 2,000 ppm SO₂ and no moisture. As can be seen in Figure 4-19, the reactivity was increasing up to 1 s contact time but leveled off thereafter, probably indicating a completely dry sorbent surface.

The effect of the approach to saturation on the reactivity of Miss 4 sorbent is shown in Figure 4-20 for 2,000 ppm SO₂ and dry/warm nitrogen conditioning. The reactivities measured for 11 °C approach to saturation are significantly higher than those measured for other approaches. There is no significant difference between reactivities measured at 17 °C and 22 °C approach to saturation. After exposure to SO₂ for 5 s, about 1.5 percent conversion was measured with Miss 4 sorbent for both 17 and 22 °C approach to saturation. Conversion below 1 percent was observed for commercial Mississippi Ca(OH)₂ exposure to 2,000 ppm SO₂ at 22 °C approach to saturation.

Figure 4-16. Effect of the specific surface area of the sorbent on the conversion with SO₂ (2,000 ppm SO₂, 11 °C approach to saturation, 61 °C/dry nitrogen conditioning).

Figure 4-17. Effect of the specific surface area of the sorbent on the conversion with SO_2 (2,000 ppm SO_2 , 11 °C approach to saturation, sorbent conditioning with room air).

Figure 4-18. The effect of sorbent conditioning on the reactivity with SO_2 (Miss Ca(OH)_2 , 2,000 SO_2 , 11 °C approach to saturation).

Figure 4-19. The effect of evaporation of moisture from the sorbent (commercial Mississippi Ca(OH)_2 , 2,000 ppm SO_2 , no moisture in the process gas, conditioning with 21 °C, water saturated nitrogen).

Figure 4-20. The effect of the approach to saturation on the reactivity with SO_2 (Miss 4 Ca(OH)_2 , 2,000 ppm SO_2 , dry/warm nitrogen conditioning).

4.3 EFFECT OF MOISTURE ON REACTIVITY

In previous chapters, the data was presented indicating relatively significant effect of sorbent conditioning on the reactivity with SO_2 . The amount of moisture was measured by the TGA for different conditioning schemes and for sorbents with varying surface area. The results are presented in Table 4-2, giving the amount of weight loss over 20-100 °C temperature range, as measured by TGA.

This weight loss may be related to the so-called free moisture (or surface moisture) that can potentially be evaporated upon the contact of sorbent with dry gas. The conditioning time was fixed at 2 min and 2 conditioning schemes were investigated:

- Dry nitrogen, 61 °C
- Room air

TABLE 4-2. THE EFFECT OF SORBENT TYPE AND CONDITIONING SCHEME ON THE AMOUNT OF MOISTURE

Ca(OH)_2	Surface Area [m ² /g]	Porosity [percent]	Conditioning	TGA wt Loss ^a [percent]
Commercial Mississippi	17	19	room air	0.73
			warm, dry N_2	0.73
Mississippi 2	32	30	room air	N/A
			warm, dry N_2	0.47
Mississippi 7	48	31	room air	0.70
			warm, dry N_2	0.54
Mississippi 6	75	49	room air	0.70
			warm, dry N_2	0.66

^aUpon heating from 20-100 °C

For both conditioning schemes and for all Ca(OH)_2 the amount of surface moisture after 2 min conditioning was below 1 wt percent. Except for the commercial Mississippi Ca(OH)_2 , the amount of moisture was increasing with increasing specific surface area of Ca(OH)_2 for conditioning with 61 °C, dry nitrogen. For all sorbents tested, the amount of moisture detected by the TGA following the room air conditioning was approximately the same.

Conditioned sorbents were exposed to SO_2 in the STDR operated at 11 °C approach to saturation and with 2,000 ppm SO_2 . Figure 4-21 presents Ca(OH)_2 conversion after 5 s in the STDR as a function of sorbent surface area for both conditioning schemes. There appears to be little sensitivity of Ca(OH)_2 conversion with SO_2 to the surface area of the sorbent following the conditioning with room air. The sensitivity of Ca(OH)_2 conversion to the original surface area of sorbent was higher when sorbents were conditioned with dry, 61 °C nitrogen. Figure 4-22 was constructed to explain the effect of conditioning on reactivity in more detail. It presents the Ca(OH)_2 conversion as a function of a measured TGA weight loss. The amount of TGA weight loss following the dry, 61 °C conditioning varied from 0.47 to 0.66 wt percent. The amount of loss following room air conditioning was approximately 0.7 wt percent for 3 sorbents tested. The conversion ranged from 2.1-3.5 percent following dry, 61 °C conditioning and from 2.7-3.5 percent following room air conditioning.

Based on data presented in Figures 4-21 and 4-22, it appears that there is a combined effect of surface area and initial moisture content of the sorbent on its reactivity with SO_2 . Conversion was increasing with both increasing surface area and initial moisture content.

Sorbent with lower surface area could be made more reactive by increasing its initial moisture content. However, for samples tested the amount of initial moisture content of Ca(OH)_2 resulting from conditioning techniques applied was always below 1 wt percent, regardless of the sorbent's surface area.

One other sorbent was tested and it was produced by slurring fly ash from coal-fired power plant with Ca(OH)_2 at the weight ratio of 3:1 at 90 °C for 16 h. Following 2 min conditioning with room air, 1.25 wt percent loss was measured for this sorbent by TGA. The conversion of Ca(OH)_2 measured after 5 s in the STDR operated under conditions previously described was 7.6 percent. This comparison of fly ash/ Ca(OH)_2 and Ca(OH)_2 sorbent is shown in Figure 4-23.

4.4 EFFECT OF CO_2 ON REACTIVITY

Typical flue gas contains CO_2 , which can potentially react with Ca(OH)_2 under conditions of duct injection for the removal of SO_2 . By reacting with CO_2 , the sorbent can be partially converted to

Figure 4-21. Combined effect of sorbent surface area and conditioning techniques on sorbent's reactivity with SO₂.

Figure 4-22. Reactivity of Ca(OH)_2 as a function of initial moisture content as measured by TGA.

Figure 4-23. The effect of surface moisture on reactivity of sorbents with SO_2 .

CaCO_3 (recarbonated). Since it is known that CaCO_3 is not reactive with SO_2 under duct conditions, the presence of CO_2 could potentially decrease the reactivity of sorbent with SO_2 .

In order to investigate the extent of recarbonation, the sorbent was placed in STDR under N_2/CO_2 flow for a desired contact time and later analyzed by TGA for the amount of CaCO_3 . The weight loss by the sample between 550-700 °C was assumed to be indicative of the amount of CaCO_3 in the sample. The baseline content of CaCO_3 in the untreated commercial Mississippi $\text{Ca}(\text{OH})_2$ (6.0 or 6.4 wt percent, depending upon the batch used) was then subtracted. The resulting number is reported as the percent carbonation in Figure 4-24. Figure 4-24 presents the percent carbonation as the function of the exposure time to CO_2 -containing gas. Two levels of CO_2 concentration were tested: 10 and 20 vol percent. The CO_2 -containing gas was dry or humidified (11 °C approach to saturation) and it did not contain SO_2 . Mississippi $\text{Ca}(\text{OH})_2$ was used for experiments. The contact time range tested was 0.5-300 s. For humidified gas, the percent of carbonation increased with increasing contact time. For dry gas, the percent carbonation increased with contact time up to 5 s and later levelled off. For any contact time with either dry or humidified gas, there was no significant difference in the extent of carbonation for gas containing 10 or 20 vol percent CO_2 . Significantly less recarbonation occurred in the dry gas than in the humidified gas, especially for contact times longer than 50 s. Data presented in Figure 4-24 indicates that the presence of moisture in the flue gas can increase the amount of CO_2 combined with $\text{Ca}(\text{OH})_2$.

Several sorbents were produced in the laboratory to investigate the effect of specific surface area on the extent of carbonation. The specific surface range investigated was from 17-78 m^2/g . Carbonation conditions were constant at 5 s contact time and 10 vol percent CO_2 concentration. Both dry and humid (60 percent RH) carbonation was tested. The results are presented in Figure 4-25 giving the percent carbon after 5 s as a function of initial $\text{Ca}(\text{OH})_2$ surface area. Measured percent carbonation was increasing with the increasing initial surface area of $\text{Ca}(\text{OH})_2$. For any sorbent tested, the percent of carbonation was higher for humid than for dry N_2/CO_2 gas. Data presented in Figure

Figure 4-24. Recarbonation of Mississippi Ca(OH)₂ upon contact with CO₂.

Figure 4-25. Carbonation of Mississippi Ca(OH)₂ as a function of initial surface area (10 vol percent of CO₂).

4-25 indicates that increased initial surface area of Ca(OH)_2 can increase the amount CO_2 combined with the sorbent.

In the actual environment of duct, the carbonation of dry injected Ca(OH)_2 due to the presence of CO_2 would take place in the presence of SO_2 . To investigate the possible effect of SO_2 on the extent of carbonation, the sample of Mississippi Ca(OH)_2 was exposed to the humid $\text{N}_2/\text{CO}_2/\text{SO}_2$ gas. The concentration of CO_2 was 10 vol percent and the concentration of SO_2 was 2,000 ppm. After 5 s exposure the sample was analyzed for the amount of CaCO_3 by TGA. Additionally, the sample was analyzed with C, H, N elemental analyzer to avoid the interference of CaSO_3 with CaCO_3 analysis. The extent of carbonation in the presence of SO_2 and at the conditions described above was measured to be 8.08 and 8.31 wt percent by the TGA and C,H,N, elemental analysis methods, respectively. Previously measured extent of carbonation in humid N_2/CO_2 gas and after 5 s contact time in the STDR was 8.72 wt percent of CaCO_3 . Based on the above set of data, there was no significant effect of SO_2 presence on the extent of carbonation of Ca(OH)_2 .

In the next step, the reactivity of Mississippi Ca(OH)_2 with SO_2 in the presence of CO_2 was investigated in the STDR. The sorbent was conditioned for 2 min with dry 61 °C nitrogen and later injected into gas stream with 2,000 ppm SO_2 at 11 °C approach to saturation and with between 10 and 40 vol percent of CO_2 . The results are presented in Figure 4-26, giving 5 s conversion in STDR as a function of residence time for 4 different concentrations of CO_2 . The effect of CO_2 presence on Ca(OH)_2 reactivity varied with the concentration of CO_2 . There was moderate decrease of Ca(OH)_2 reactivity in the presence of CO_2 for high concentration of CO_2 . For example, after 5 s exposure to 2,000 ppm SO_2 at 11 °C approach to saturation the conversion was 2.1 and 1.6 percent for nitrogen/ SO_2 and nitrogen/ SO_2 /40 vol percent CO_2 gas, respectively. However, for the practical range of CO_2 concentration (0-10 vol percent) its effect on reactivity of Ca(OH)_2 was insignificant.

Figure 4-26. The effect of CO₂ on reactivity of Mississippi Ca(OH)₂ with SO₂ (2,000 ppm SO₂, 11 °C to saturation).

4.5 GLOBAL SO₂ KINETICS TESTING

4.5.1 General Findings

This section chiefly addresses the effects of sorbent moisture content and time on conversion. Additional results compare the performance of Ca(OH)₂ to fly ash/Ca(OH)₂ sorbent. Finally, the effect of flue gas SO₂ concentration on reagent conversion is described.

Conversion of both calcium-based reagents increased with both residence time and RH. For a 60-min reaction, approximately one half of the final reagent conversion (value attained in 1-2 h) occurred in the first 5-10 min. However, even at the highest RH (85 percent), sorbent conversion did not reach 20 percent with sulfation times at or below 30 s. Variation in the reagent pretreating technique (pretreating time or RH) altered the reagent conversion by up to 10 percent. Use of fly ash/Ca(OH)₂ sorbent achieved a higher conversion relative to use of Ca(OH)₂ under the same reaction conditions. The different behavior of the two reagents appeared to be linked to the sorbent surface area. Flue gas SO₂ concentration had no noticeable effect on Ca(OH)₂ conversion, and fly ash/Ca(OH)₂ sorbent conversion was affected only slightly during the first 2 min of reaction. Data which describe the effects of RH and residence time are shown in Figures 4-27 and 4-28.

The majority of the experiments, which are discussed in the next two subsections, were performed under equilibrium moisture conditions with 450 ppm SO₂ using both Ca(OH)₂ and fly ash/Ca(OH)₂ sorbent. The fly ash/Ca(OH)₂ sorbent data include RH of 85, 51-58, 24, and 0 percent and residence times from 10-7,200 s. The sorbent was first pretreated for 2 min with nitrogen at 90 percent RH then with nitrogen at the experimental RH for an additional 2 min. With 85 percent RH, conversion increased from 11-93 percent for the range of residence times. With 51-58 percent RH, conversion rose from 7-62 percent for the range of residence times. With 24 percent RH, conversion increased from 3-15 percent and at 0 percent RH, conversion remained at about 4 percent.

Figure 4-27. Effect of RH on conversion of Clinch River fly ash/ Ca(OH)_2 sorbent.

Figure 4-28. Effect of RH on conversion of Mississippi Ca(OH)_2 .

The data with Mississippi $\text{Ca}(\text{OH})_2$ include RH of 85, 58, 51, and 24 percent and residence times from 10-3600 s (one additional experiment was run for 7,200 s at 24 percent RH). The sorbent was first pretreated for 2 min with nitrogen at 90 percent RH then with nitrogen at the experimental RH for an additional 2 min. With 85 percent RH, conversion increased from 4-71 percent for the range of residence times. For the experiments conducted at 51 and 58 percent RH, conversion from 3-28 percent was attained over the range of residence times. While at 24 percent RH, conversion increased from 1 to only 5 percent.

4.5.2 Effect of Residence Time

Residence time strongly influenced reagent conversion. Previous workers performed experiments to simulate the reaction of a $\text{Ca}(\text{OH})_2$ -based sorbent in the bag filter environment, for which a 60-min reaction time is characteristic. Using sorbents enhanced with fly ash, conversion of 50-70 percent were commonly achieved. A goal of the present study was to perform similar experiments but at sulfation times more representative of the duct injection environment (on the order of 10 s). It was hoped that the relatively high conversions experienced at the bag filter conditions would not be too greatly diminished due to operation at duct injection residence times. However, this was not the case. With 10 s for sulfation, the maximum conversion (achieved at 85 percent RH) was only 11 percent with fly ash/ $\text{Ca}(\text{OH})_2$ sorbent and 4 percent with Mississippi $\text{Ca}(\text{OH})_2$.

The effects of sulfation time were shown in Figures 4-27 and 4-28. As was discussed above, conversion generally increased with system RH. However, the effect of RH was diminished as reagent conversion approached unity at long residence times. For a 10 s sulfation time, fly ash/ $\text{Ca}(\text{OH})_2$ sorbent conversion ranged from 3-11 percent as RH increased from 0-85 percent. The maximum effect of RH occurs at a residence time of approximately 600 s. At this residence time conversion with 85 percent RH was 75 percent, and conversion at 51 percent RH was 33 percent. However, with a 7,200 s sulfation time, values of conversion (95 and 62 percent) at the two RHs became less differentiated. Similar trends exist in the $\text{Ca}(\text{OH})_2$ data. Additional details of the data are given in the following section.

4.5.3 Effect of Relative Humidity

RH also demonstrated a strong effect on system performance. With the fly ash/ $\text{Ca}(\text{OH})_2$ sorbent, conversions above 88 percent were achieved at 85 percent RH for residence times above 1 h. With both reagents, sulfation at 85 percent RH enabled conversion to reach 30 percent approximately 5 times faster than did sulfation at 51 percent RH (Figures 4-27 and 4-28). At 85 percent RH a conversion of 30 percent was reached in approximately 60 s; while, with 51 to 58 percent RH, 30 percent conversion was achieved in approximately 300 s. For both reagents, very little conversion (no more than 15 percent) occurred for RH at or below 24 percent.

Conversion of the $\text{Ca}(\text{OH})_2$ was also strongly influenced by the system RH. At 85 percent RH after 3,600 s of sulfation time, 71 percent conversion was attained, and after 200 s 28 percent conversion was reached. In contrast, at 51 percent RH a second sulfation time was required to attain 28 percent conversion. In addition, conversion at 24 percent RH was poor, reaching only 5 percent. In previous work with reagent grade $\text{Ca}(\text{OH})_2$, conversion of the $\text{Ca}(\text{OH})_2$ approximately doubled (from 15 to 30) when RH increased from 55 to 85 percent, indicating that $\text{Ca}(\text{OH})_2$ conversion was not as strong a function RH as demonstrated by the present work. However, in a separate study (Klingspor, et al. 1984), a stronger dependence of conversion on RH was found. Initial reaction rates of several $\text{Ca}(\text{OH})_2$ reagents were found to increase by a factor of 5 as the RH increased from 55 to 85 percent. In addition, the relatively high conversion of the Mississippi $\text{Ca}(\text{OH})_2$ present work may be due to the higher surface area of the sorbent.

4.5.4 Effect of Initial Sorbent Moisture

The initial moisture content of the solid also had an effect on the reagent conversion although, with the techniques employed, this effect was comparatively minor relative to the sulfation time and RH. Two separate methods to vary the initial moisture content of fly ash/ $\text{Ca}(\text{OH})_2$ reagent were employed during the pretreating step. In the pretreating step, the sorbent was contacted with humid, SO_2 -free nitrogen stream prior to sulfation.

In the first group of these experiments, initial moisture content was controlled by changing the pretreating time. Over the range of pretreating times, conversion increased from 11 to 17 percent (Figure 4-29). Conversion rose rapidly as pretreating time increased from 10 to 60 s reaching 16 percent conversion with a pretreating time of approximately 120 s. Rate of conversion was not significantly affected as pretreating time increased from 2 to 9 min suggesting attainment of an equilibrium moisture condition on the sorbent surface. The above procedure called for contacting the sorbent with nitrogen at 90 percent RH, then 58 percent RH nitrogen, and finally the sulfation reaction was carried out for 30 s with 450 ppm SO_2 . Moisture content was controlled by varying the time of pretreating with 90 percent RH nitrogen from 10 to 540 s. For example, a 60 s pretreating time indicates the sorbent was exposed to nitrogen at 90 percent RH for 60 s and then to nitrogen at 58 percent RH (the reaction condition) for an additional 60 s.

Additional tests were performed in which the initial moisture content of the sorbent was varied by adjusting the pretreating RH. During this group of experiments fly ash/ $\text{Ca}(\text{OH})_2$ sorbent was first pretreated with 90 percent RH nitrogen for 2 min followed by nitrogen pretreating for an additional 2 min at the desired RH. After pretreating, the reagent was sulfated with flue gas containing 500 ppm SO_2 with a RH from 51 to 58 percent. The pretreating RHs included 0, 53, 60, 86, and 94 percent. Reagent exposure times ranged from 10 to 120 s (Figure 4-30).

With solids pretreated with nitrogen at 53 to 60 percent RH, the moisture initially present of reagent was very nearly at equilibrium with the flue gas and provided a baseline against which subsequent experiments were compared. With pretreating at 53 to 60 percent RH, conversion increased from 7 to 27 percent over the range of sulfation times. The extremes of the pretreating relative humidities, 94 and 0 percent, resulted in a 5 to 10 percent (percent of total conversion) deviation from the baseline results. Reagent conversion generally increased with the pretreating RH for a given sulfation time. However, results for 86 percent RH pretreating seem low compared to results obtained under the other conditions.

Figure 4-29. Effect of pretreating time on conversion of fly ash/ Ca(OH)_2 sorbent.

Figure 4-30. Effect of pretreating RH on conversion of fly ash/ Ca(OH)_2 sorbent.

In the previous subchapter, it was demonstrated that the sorbent reached equilibrium with moisture in the flue gas after pretreating for approximately 2 min. Since the moisture history of the sorbents becomes less unique with increasing reaction time, it is surprising that the data do not converge toward a specific conversion for the 120 s (longest residence time) reaction. Data discussed previously in this chapter show the effect of varying pretreating RH for sulfation times less than 10 s. The effect of varied pretreating RH is most evident at the longest residence time (5 s). In addition, with a 5 s residence time, conversion only increased from 0.8 percent to 2.8 percent when pretreating RH increased from 0 to 100 percent. Both results were reasonably consistent with data shown in Figure 4-30.

4.5.5 Effect of Sorbent Type

Results from Figures 4-27 and 4-28 describing the effect of RH residence time on conversion of both fly ash/ $\text{Ca}(\text{OH})_2$ and $\text{Ca}(\text{OH})_2$ are combined in Figure 4-31. For the same RH and residence time, fly ash/ $\text{Ca}(\text{OH})_2$ sorbent provided a higher conversion than did $\text{Ca}(\text{OH})_2$. With higher relative humidities (above 24 percent) and residence times from 60 to 1,000 s, the superior performance of the fly ash/ $\text{Ca}(\text{OH})_2$ sorbent was evident. For a 600 s sulfation time at 85 and 51 percent RH, use of fly ash/ $\text{Ca}(\text{OH})_2$ sorbent enabled conversion to reach 78 and 33 percent, respectively. Conversion of $\text{Ca}(\text{OH})_2$ reached 52 and 14 percent under similar conditions. The difference in performance of the two reagents was least apparent at low residence times and low RH (because conversion was tending toward 0) and at 85 percent RH and residence times greater than 1 h as reagent conversion asymptotically approached unity. In previous work comparing fly ash/ $\text{Ca}(\text{OH})_2$ sorbent to $\text{Ca}(\text{OH})_2$, the maximum benefit of the fly ash/ $\text{Ca}(\text{OH})_2$ sorbent occurred at 80 percent RH with a 3,600 s residence time. Under these conditions, conversion values of the fly ash/ $\text{Ca}(\text{OH})_2$ sorbent and $\text{Ca}(\text{OH})_2$ were 70 and 20 percent, respectively.

In Figure 4-32, conversion of several calcium-based sorbents is plotted as a function of residence time. The sorbents listed in order of decreasing specific surface (m^2/g of $\text{Ca}(\text{OH})_2$ in the reagent) are the following: Clinch River fly ash/ $\text{Ca}(\text{OH})_2$ sorbent ($64 \text{ m}^2/\text{g}$), laboratory-hydrated

Figure 4-31. Effect of reagent type on conversion (CR, MH denote Clinch River fly ash/ Ca(OH)_2 sorbent and Mississippi Ca(OH)_2 , respectively).

Figure 4-32. Effect of reagent surface area on conversion (CR, MH denote Clinch River fly ash/Ca(OH)₂ sorbent and Mississippi Ca(OH)₂, respectively.)

Mississippi $\text{Ca}(\text{OH})_2$ ($32 \text{ m}^2/\text{g}$), and commercially-available Mississippi $\text{Ca}(\text{OH})_2$ ($17 \text{ m}^2/\text{g}$). Although the data do not overlap over the complete range of residence times, qualitative comparisons can be made. Consistently, the higher surface area material provided for a greater conversion for a given residence time. The relative increase in conversion brought about by using a preferable sorbent appeared to be dependent on the sorbent surface area rather than the chemistry of the reagent. Also, conversion of the $17 \text{ m}^2/\text{g}$ material increased from 0.3 to 30 percent over the range of residence times, and the data from separate sources fell on the same curve. The experiments were performed in the flue gas containing 500 to 3,000 ppm SO_2 with 51 to 58 percent RH over residence times ranging from 0.5 to 3,600 s.

4.5.6 Effect of SO_2 Concentration

Figure 4-33 compares the result of experiment run with 450 and 2,000 ppm SO_2 . The conversion of $\text{Ca}(\text{OH})_2$ showed no response toward increased SO_2 concentration, and the fly ash/ $\text{Ca}(\text{OH})_2$ sorbent appeared to show only a slight sensitivity toward SO_2 concentration.

Scatter exists in the data, but for residence times under 5 min, reagent conversion was approximately 5 percent (percent of total conversion) higher when SO_2 concentration was increased from 450 to 2,000 ppm. However, for residence times greater than 5 min fly ash/ $\text{Ca}(\text{OH})_2$ sorbent conversion was not affected by flue gas SO_2 concentration. Various earlier workers (Jozewicz, 1989; Ruiz-Alsop, 1986; Klingspor, et al., 1984) concluded that SO_2 concentration has a negligible effect upon reagent conversion. The experiments in the present work were performed at 51 to 58 percent RH over residence times ranging from 10 to 3,600 s.

4.5.7 Effect of Sorbent Accumulation over Time

In the DSI process, sorbent would be continuously fed into the untreated flue gas stream, and the reacted sorbent would be collected with a bag filter. Bag filters are periodically cleaned with the effect of creating distribution of solid/gas contact times. It is desirable to predict SO_2 removal under these cyclic conditions using the data gathered in this work. Since fractional SO_2 removal and reagent

Figure 4-33. Effect of SO_2 concentration on conversion of Mississippi $\text{Ca}(\text{OH})_2$ and fly ash/ $\text{Ca}(\text{OH})_2$ sorbent (CR, MH denote Clinch River fly ash/ $\text{Ca}(\text{OH})_2$ sorbent and Mississippi $\text{Ca}(\text{OH})_2$, respectively).

conversion are related through the stoichiometric ratio (moles of SO_2 in the untreated flue gas per mole of $\text{Ca}(\text{OH})_2$ sorbent), it is necessary to calculate only the reagent conversion for a given cycle time. Conversion of the accumulating solids is calculated by integrating the experimental relationship between conversion and residence time (for a batch reaction). Conversion for batch system was represented by the empirical fit of data in Figures 4-31 and 4-34. There is a unique expression for each reagent and RH. The reaction is treated as zero order in SO_2 . Accumulated solids conversion, C_τ , as a function of cycle time, τ , is calculated as follows:

$$C_\tau = \frac{\int_0^\tau C(t) \dot{m} dt}{\int_0^\tau \dot{m} dt} = \frac{\int_0^\tau C(t) dt}{\tau} \quad (4-1)$$

Where: τ = bag filter cycle time; C_τ = total reagent conversion over time τ ; $C(t)$ = experimental relationship between conversion and residence time for a given RH and a given reagent type and; $\dot{m}$ = molar flow rate [as $\text{Ca}(\text{OH})_2$] of reagent, assumed constant with time.

The expressions were numerically integrated using the trapezoid rule with a time step of 10 s. Figure 4-34 shows accumulated sorbent conversion as a function of bag filter cycle time of fly ash/ $\text{Ca}(\text{OH})_2$ sorbent and $\text{Ca}(\text{OH})_2$ for several RH's. As was found with the fixed-bed experiments, reagent conversion increased with time and RH. For the same conditions, conversion of the fly ash/ $\text{Ca}(\text{OH})_2$ sorbent was higher than that of $\text{Ca}(\text{OH})_2$. 51 to 58 percent RH is a practical upper limit for operations of a large scale DSI. With fly ash/ $\text{Ca}(\text{OH})_2$ sorbent under these conditions, conversion increased from 10 to 45 percent as cycle time increased from 30 to 3,600 s. Conversion was 23 percent at a cycle time of 300 s. Under the same conditions, $\text{Ca}(\text{OH})_2$ conversion ranged from 5 to 20 percent and reached 10 percent conversion at a cycle time of 300 s.

Figure 4-34. Effect of bag filter cycle time on conversion of accumulating filter cake (CR, MH denote Clinch River fly ash/ $\text{Ca}(\text{OH})_2$ sorbent and Mississippi $\text{Ca}(\text{OH})_2$, respectively).

Several of the above discussed parameters, specifically RH, residence time, and sorbent surface area, were shown to strongly influence reagent conversion. Conversely, SO_2 concentration had virtually no effect. These general experimental results are consistent with solid phase mass transfer as the rate-limiting step.

SECTION 5

NOVEL TECHNIQUES

5.1 MOIST SOLIDS

5.1.1 Theory

The key variables that affect the gas-solid reaction between SO_2 and $\text{Ca}(\text{OH})_2$ -based sorbents during dry-sorbent injection (DSI) are flue gas RH, sorbent water content, flue gas SO_2 concentration, and sorbent surface structure. Previous spray dryer studies involved the reactivity of sorbent particles suspended in liquid droplets, which, as they dried, passed through the liquid, free moisture, and equilibrium stages of reactivity. In the equilibrium stage, the particle is assumed to contain surface water in equilibrium with the RH of the flue gas. While the total reactivity of such a solid has been studied, there have been no efforts to decouple these effects. Mass transfer theory may be applied to the gas-solid reaction system in the presence of moisture in excess of equilibrium on the surface of a reactive sorbent. The theoretical model below (Beaudoin, 1990) describes the reaction occurring when a wet solid is drying and relates the evaporative drying and the SO_2 capture mechanisms.

5.1.1.1 Assumptions for Theoretical Development

The reaction between sorbent with an initial free moisture and SO_2 is assumed to be fast compared to gas-phase mass transfer of SO_2 to the particle surface. The transfer is assumed to occur by Knudsen diffusion within the pores of the reactive sorbent. The following assumptions also are necessary for the development of the model:

- Liquid water present on the solid with initial free moisture is present predominantly in the pores of the solid.

- The resistance to mass transfer for both the evaporation process and the SO₂ capture process is controlled by diffusion in the gas phase.
- Reaction between SO₂ and a sorbent with initial free moisture which dries during the course of reaction occurs in 2 separate stages: reaction in the presence of excess surface moisture (sorbent with initial free moisture), and reaction in the presence of equilibrium moisture (sorbent in equilibrium with flue gas RH). The effects of 2 stages are additive.
- The bulk flow contribution to the overall mass flux of the exchanged species is negligible during pore diffusion.

5.1.1.2 Derivation

The evaporation of water from the pores of the solid and the transport of SO₂ through the pores to the gas-liquid interface can be represented by:

$$\frac{d(\text{SO}_2/\text{area})}{dt} = N_{\text{SO}_2} = -(D_{\text{SO}_2}) \frac{dC_{\text{SO}_2}}{dx} \quad (5-1)$$

$$\frac{d(\text{H}_2\text{O}/\text{area})}{dt} = N_{\text{H}_2\text{O}} = -(D_{\text{H}_2\text{O}}) \frac{dC_{\text{H}_2\text{O}}}{dx} \quad (5-2)$$

Where: N_i = molar flux, [mole l/(area-time)]; x = diffusion distance, [length]; D = mass diffusion coefficient, [length²/time]; and C_i = concentration i , [mole l/volume].

These expressions are based on a rectangular coordinate system and a 1-dimensional concentration gradient. The mechanism assumes that the reaction occurs in a liquid droplet at the bottom of a pore. Because no reaction will occur at the walls of the pore, it is not necessary to model diffusion in the radial direction.

Transport of H₂O and SO₂ is assumed to occur by Knudsen diffusion, which is a valid assumption if the gas/liquid interface is located within small pores in the sorbent. Knudsen diffusion is

applicable when the mean free path over which a molecule can travel is greater than the pore diameter through which it is diffusing. The mean free path of a molecule is defined as follows:

$$l = \frac{1}{\sqrt{2} \pi d^2 n} \quad (5-3)$$

Where: l = mean free path, [length]; d = particle diameter, [length] and; n = concentration of molecules, [number molecules/volume].

The Knudsen diffusion coefficient is defined by:

$$D_{AK} = 97 r \sqrt{\frac{T}{M_k}} \quad (5-4)$$

Where: D_{AK} = Knudsen diffusion coefficient, [length²/time]; r = radius of diffusing particle, [length]; T = system temperature; and M_k = diffusing particle molecular weight, [mass].

The pore irregularities traditionally are handled using an empirical factor, the tortuosity of a pore, along with the particle porosity. These factors are ignored here as the ratio of the 2 flux expressions will be taken, and the tortuosities and porosities will cancel from the final expression. It is now possible to insert the Knudsen diffusion coefficient into the flux expressions and, taking the ratio of the 2, the following relationship holds:

$$\frac{N_{SO_2}}{N_{H_2O}} = \frac{D_{SO_2K}(dSO_2/dx)}{D_{H_2OK}(dH_2O/dx)} \quad (5-5)$$

The relationship between the water evaporated from the solid surface and the SO_2 captured is determined by integrating this expression, as follows:

$$\frac{\Delta SO_2}{\Delta H_2O} = \frac{D_{SO_2K}(P_{SO_2})}{D_{H_2OK}(P_{H_2O}^* - P_{H_2O})} \quad (5-6)$$

Where: ΔSO_2 = SO_2 captured, [moles]; ΔH_2O = H_2O evaporated, [moles]; P_{SO_2} = partial pressure SO_2 in bulk gas, [atm]; P_{H_2O} = partial pressure H_2O in bulk gas, [atm]; and $P_{H_2O}^*$ = partial pressure H_2O at gas-liquid interface, [atm].

The model allows one to predict the conversion of the porous sorbent as a function of the quantity of water evaporated from the sorbent while in contact with SO_2 . This representation does not account for reaction that occurs when the sorbent contains water in equilibrium with the flue-gas RH.

In each experiment, the initial weight percent water on the reactive sorbent, the RH of the flue gas, and the SO_2 content of the flue gas are noted. The aforementioned expression is modified to predict the Ca utilization of the sorbent based on these parameters. The modified predictive expression is:

$$\frac{\Delta SO_2}{Ca} = \frac{0.53 (P_{SO_2})}{(P_{H_2O}^* - P_{H_2O})} \left(\frac{\Delta H_2O}{Ca} \right) \quad (5-7)$$

Where: Ca = Ca content of the sorbent, [moles/g sorbent].

Figure 5-1 shows the conversions predicted by the model under typical experimental conditions. These results assume that all H_2O initially present on the surface of the solid evaporates from the solid. The results do not include reaction between the sorbent and SO_2 in the absence of excess moisture on the surface of the sorbent.

5.1.1.3 Effects of Equilibrium Reaction

The effects of the wet reaction and the reaction occurring in the presence of equilibrium moisture may not be additive, but rather the presence of liquid moisture on the sorbent surface may affect the reaction with equilibrium moisture. Initial free moisture on the surface of the sorbent occupies free surface area otherwise available for reaction attributable to equilibrium moisture. If the conversion observed during the equilibrium-moisture reaction is significant, the conversion attained in the combined

Figure 5-1. Predicted conversion in the presence of liquid H₂O: (Ca(OH)₂ fly ash sorbent containing 3.65×10^{-3} moles Ca/g sorbent).

wet/equilibrium moisture system will be lower than a linear combination of the expected results for the independent wet and equilibrium moisture systems.

The conversion predicted as a function of initial free moisture on the surface of the sorbent is considered correct, but the magnitude of the equilibrium-moisture reaction's contribution must be adjusted to reach a correct total conversion. To calculate the conversion that will occur by the equilibrium-moisture reaction, the results of equilibrium-moisture reaction studies will be analyzed to determine the instantaneous rate of sorbent conversion as a function of sorbent conversion. For each experiment to be modeled, the conversion expected attributable to liquid water will be noted, and the instantaneous conversion rate corresponding to this conversion level will be used to calculate the conversion attributable to equilibrium-moisture reaction. The initial free moisture on the sorbent surface is assumed to evaporate instantly during reaction, the differential expression for conversion attributable to reaction in the presence of equilibrium moisture must be integrated over the entire reaction time. The resulting conversion predicted attributable to reaction in the presence of equilibrium moisture will be added to the conversion expected attributable to wet reaction in order to determine the total conversion of the sorbent. This model will be referred to as the Additive Model.

5.1.1.4 Derivation of Modified Equilibrium Conversion Estimate

The expression that predicts sorbent conversion attributable to excess moisture is shown in Equation 5-7. The expression for total sorbent conversion is:

$$\text{Pred. conversion} = a_{H_2O} + g_{EQ} \quad (5-8)$$

Where: a_{H_2O} = conversion due to excess H_2O , [mole SO_2 /mole Ca]; and g_{EQ} = equilibrium moisture conversion, [moles SO_2 /mole Ca].

It is possible to evaluate g_{EQ} as follows:

$$g_{EQ} = h_{EQ}(t + t_0) - a_{H_2O} \quad (5-9)$$

Where: t_0 = time required to achieve f_{H_2O} conversion by the equilibrium moisture mechanism, [s]; t = time available for equilibrium-moisture reaction, [s]; and $h_{eq}(t + t_0)$ = instantaneous rate of conversion by equilibrium moisture mechanism evaluated at $(t + t_0)$, [(moles S/mole Ca)/(s)].

When the ambient-moisture portion of the total conversion is predicted using this method, the model will be referred to as the Interactive Model.

5.1.2 Long Time Differential Reactor Results and Discussion

The Long Time Differential Reactor (LTDR) experimental work addressing the SO_2 removal performance of $Ca(OH)_2$ -based sorbents with initial free moisture under DSI conditions was performed in 2 stages. In the first stage, sorbents containing moisture in equilibrium with laboratory RH (~ 50 percent) were exposed to flue gas of varying RH and SO_2 content. In the second stage, water was added to the sorbent so that its water content was above that attained through equilibrium with the room humidity. Four sorbents, of varying surface properties and chemical composition, were used, and the flue gas SO_2 content and RH were varied during both stages of testing.

In the course of LTDR work, 2 different gas-phase SO_2 concentrations were used: 1,000 and 5,000 ppm. At 1,000 ppm, significant Ca utilizations were expected in the $Ca(OH)_2$ /fly ash sorbent when both equilibrium moisture and moisture in excess of the equilibrium condition were applied to the reaction system. The sorbent was not expected to approach 100 percent Ca utilization under these conditions. When 5,000 ppm SO_2 was present in the flue gas, significant Ca utilizations were expected in all of the sorbents for reactions utilizing sorbent containing both equilibrium moisture and moisture in excess of the equilibrium quantity. Because of the possibility that the fly ash/ $Ca(OH)_2$ sorbent would approach 100 percent Ca utilization if significant quantities of moisture were present on the sorbent during reaction with 5,000 ppm flue gas, a limited amount of water was added to this sorbent during the 5,000 ppm testing.

Several different sorbents were used in this study. Their properties are presented in Table 5-1. The reactivities of Mississippi $Ca(OH)_2$ and the $Ca(OH)_2$ /fly ash sorbent have been studied by researchers at The University of Texas at Austin (Peterson and Rochelle, 1988). The other 2 sorbents

were selected to determine the effects of surface area and porosity on the reaction with SO_2 . The sorbents are made from Ca(OH)_2 that has been calcinated and subsequently hydrated in the presence of alcohol (double hydration) to promote the formation of high surface area, high porosity Ca(OH)_2 .

5.1.2.1 Sorbents with Ambient Moisture

Presented below is experimental work performed with sorbents containing moisture in equilibrium with laboratory temperature and RH. The results presented in Figures 5-2, 5-3, and 5-4 are the culmination of the work done to investigate sorbent reactivity when the sorbent contains moisture in equilibrium with laboratory RH. Initially, the sorbents contained moisture in equilibrium with the laboratory RH. When the flue gas was introduced into the

TABLE 5-1. PROPERTIES OF SORBENTS USED IN THE COURSE OF LTDR WORK

Sorbent Name	Surface Area [m ² /g]	Porosity [cm ³ /g]	Formation Conditions
Fly ash/ Ca(OH)_2	16	0.21	3:1 ratio Clinch River fly ash Mississippi Ca(OH)_2 slurried at 90 °C for 12 h
Mississippi Ca(OH)_2	17	0.19	
Ca(OH)_2 "A"	74	0.47	hydrated (alcohol present) at 74 °C for 50 min, N ₂ blanket for 41 min
Ca(OH)_2 "B"	51	0.25	hydrated (alcohol present) at 74 °C for 35 min, N ₂ blanket for 26 min

reactors, the sorbents' moisture content shifted to attain equilibrium with the flue gas RH. The magnitude of the change in the sorbent's surface moisture content was presumed negligible during this process.

Figure 5-2 indicates that increasing the RH of the flue gas and increasing the gas-sorbent contact time enhances the conversion (moles SO_2 captured/mol Ca(OH)_2) of the fly ash/ Ca(OH)_2

Figure 5-2. Conversion of fly ash/ Ca(OH)_2 sorbent containing ambient moisture (1,000 ppm SO_2 in flue gas, 70 °C, 3.5 percent initial moisture on sorbent).

Figure 5-3. Conversion of Ca(OH)_2 sorbents containing ambient moisture (5,000 ppm SO_2 in flue gas, 70 °C, 1.0 percent initial moisture on sorbents, 58 to 67 percent RH in flue gas).

Figure 5-4. Comparison of fly ash/ Ca(OH)_2 and Mississippi Ca(OH)_2 sorbent (5,000 ppm SO_2 in flue gas, 70 °C, 1.0 percent initial moisture on Mississippi Ca(OH)_2 , 3.5 percent on fly ash/ Ca(OH)_2 , 60 to 67 percent RH in flue gas).

sorbent. At the higher relative humidities, conversions reach 50 and 20 percent for 120 and 10 s reactions, whereas the average sorbent conversion for 120 s gas/solid contact time is 30 percent at approximately 60 percent RH. The increase in sorbent conversion with increasing reaction time is not as significant for the lower RHs as for the higher RHs, implying that for a given reaction time, greater surface moisture content of the sorbent results in greater conversion.

Figure 5-3 shows that the equilibrium conversion of the $\text{Ca}(\text{OH})_2$ sorbents increases with increasing sorbent surface area, and the conversion of lower-surface-area sorbents does not approach that of the high-surface-area sorbents at short or long times. The conversion of $\text{Ca}(\text{OH})_2$ sorbents increases slightly with increasing reaction time, although the effect is not as significant as for the $\text{Ca}(\text{OH})_2$ /fly ash sorbent in the 1,000 ppm flue gas (Figure 5-2).

Significant conversion of the $\text{Ca}(\text{OH})_2$ sorbents occurs, ranging to approximately 22 and 33 percent, for 10 and 120 s reactions at approximately 61 percent RH with the high surface area $\text{Ca}(\text{OH})_2$. The high surface area provides adequate space for instantaneous reaction, but the formation and precipitation of product on the particle surface limits additional conversion. In Figure 5-4, a comparison is presented of fly ash/ $\text{Ca}(\text{OH})_2$ sorbent's reactivity with that of Mississippi $\text{Ca}(\text{OH})_2$. 5,000-ppm SO_2 was in the flue gas during these tests, which were conducted at approximately 60-percent RH. The conversion of the fly ash/ $\text{Ca}(\text{OH})_2$ sorbent was superior to that of the Mississippi $\text{Ca}(\text{OH})_2$ at all reaction times, although the surface areas of the 2 sorbents are similar. In contrast to its performance in the presence of low concentrations of SO_2 , the conversion of the $\text{Ca}(\text{OH})_2$ /fly ash sorbent did not increase drastically with increasing reaction time in the presence of 5,000 ppm SO_2 . The conversion of the fly ash/ $\text{Ca}(\text{OH})_2$ sorbent is approximately the same for the 120 s reaction, although the 10 and 60 s reactions provide significantly higher conversions in the presence of the 5,000 ppm SO_2 than the 1,000 ppm SO_2 , which was not expected. With 5,000 ppm SO_2 in the flue gas, the conversion occurring during the short time reactions of all the sorbents studied appears to be the dominant conversion, with incremental reactions occurring at long times.

The gas-solid reaction in the presence of equilibrium moisture on the sorbent surface is possibly controlled by the effective surface area of the sorbent. Increasing sorbent conversion reduces the rate of additional conversion, probably because of product precipitation on the reactive surface. The instantaneous conversion of a high surface area sorbent is high, but additional conversion is incremental by comparison when 5,000 ppm SO_2 is in the flue gas. With lower SO_2 contents in the flue gas, the instantaneous reaction is less significant than in the high SO_2 cases, but the additional conversion is more significant at the low SO_2 levels than at the high levels. The conversions of the high surface area $\text{Ca}(\text{OH})_2$ and the fly ash/ $\text{Ca}(\text{OH})_2$ sorbent are approximately the same at all conditions, implying that the sorbent conversion is controlled by the dispersion of Ca throughout this surface area. Such a mechanism would result in:

- Higher SO_2 capture on high surface area sorbents compared to low-surface-area sorbents.
- An inverse relationship, for a given surface area, between the Ca content of sorbents and their conversions.
- High sorbent conversions for short time reactions, which occur when the sorbent surface area is not blocked by the formation of a product layer, followed by incremental increases in conversion for longer time reactions, when the sorbent surface area has been reduced by product layer formation.

Figure 5-5 presents a comparison between the m^2 sorbent/mole $\text{Ca}(\text{OH})_2$ and sorbent conversion in 5,000 ppm SO_2 flue gas when the sorbent contains moisture in equilibrium with flue gas RH. The fly ash/ $\text{Ca}(\text{OH})_2$ and $\text{Ca}(\text{OH})_2$ sorbents fall approximately on the same curves, implying that the dispersion of the $\text{Ca}(\text{OH})_2$ over the sorbent surface area is more important than the quantity of $\text{Ca}(\text{OH})_2$ applied.

5.1.2.2 Sorbents with Initial Free Moisture

Figures 5-6, 5-7, and 5-8 present the results obtained using fly ash/ $\text{Ca}(\text{OH})_2$ sorbent with an initial free moisture in 1,000 ppm SO_2 for 10, 60, and 120 s. The results shown are for work performed

Figure 5-5. Effect of Ca dispersion on sorbent conversion (5,000 ppm SO₂ in flue gas, 70 °C, 1.0 percent initial moisture on Mississippi Ca(OH)₂, 3.5 percent on Ca(OH)₂/fly ash, 60 to 67 percent RH in flue gas).

Figure 5-6. Conversion of fly ash/Ca(OH)₂ sorbent with initial free moisture (1,000 ppm SO₂ in flue gas, 70 °C, 10 s reaction).

Figure 5-7. Conversion of fly ash/Ca(OH)₂ sorbent with initial free moisture (1,000 ppm SO₂ in flue gas, 70 °C, 60 s reaction).

Figure 5-8. Conversion of fly ash/ Ca(OH)_2 sorbent with initial free moisture (1,000 ppm SO_2 in flue gas, 70 °C, 120 s reaction).

at 0, 54-64, and 80-91 percent RH. For all cases shown, the sorbent conversion increases with increasing moisture content and increasing flue gas RH.

At 0 percent RH, the magnitude of the sorbent conversions attained is not high, so that while the beneficial effect of initial free moisture is clearly visible, the slope of the increase is less certain than it appears on the plots. At the intermediate RH, the effect of initial free moisture levels off above ~25 percent initial free moisture in the 60 s plot, and, anomalous data not withstanding, in the 10 s plot as well. In the 120 s plot, the conversion of sorbent containing 3.5 percent moisture is not likely as great as the data present, and the conversions attained at the higher moisture contents are essentially independent of the moisture content. At high RH, the sorbent conversion increases greatly with increasing initial free moisture content for all reaction times.

Sorbents with high initial free moisture contents were not expected to dry completely in the short (10 s) reaction time, negating the beneficial effect of the initial free moisture. The increase in sorbent conversion with increasing initial free moisture at the 10 s reaction time was still significant for all RHs, indicating that the initial free moisture promoted sorbent reactivity. At high initial free moisture contents, moisture was expected to be lost from the sorbent surface and to absorb onto the sand during the sorbent preparation process. The data taken at 55 to 65 percent RH contain points at which this water loss may have occurred (~50 percent initial free moisture). Loss of moisture prior to the reaction could explain why the increase in sorbent conversion is not as significant at the high moisture content than at the lower levels, although the intermediate moisture results support the trend that conversion levels off with increasing moisture.

The initial free moisture may possibly evaporate very rapidly at the lower RHs, resulting in high instantaneous conversion of the sorbent, but blockage of the surface area by product and limited reaction because of equilibrium moisture after the sorbent has dried. Also, the evaporation rate at the low RHs possibly is competitive with the rate of dissolved SO_2 migration within the initial free moisture, resulting in a saturated liquid phase and limited SO_2 absorption into the free moisture. At the higher

RH, the free moisture remains on the particle for longer time periods, resulting in increased H_2O available for SO_2 absorption.

Figures 5-9 through 5-14 present the results using sorbents with initial free moisture in 5,000-ppm SO_2 . Neither the fly ash/ $\text{Ca}(\text{OH})_2$ sorbent nor the $\text{Ca}(\text{OH})_2$ sorbents reacting in 5,000 ppm flue gas showed the expected significant increase in conversion with increasing initial free moisture content. The conversion increase of the $\text{Ca}(\text{OH})_2$ sorbents with increasing initial free moisture content is not significant, and within the data spread the conversion can be considered essentially constant with increasing initial free moisture content of the moderate surface area $\text{Ca}(\text{OH})_2$. Conversion of the highest surface area $\text{Ca}(\text{OH})_2$ decreases with increasing initial free moisture content of the sorbent, whereas the conversion of the low surface area $\text{Ca}(\text{OH})_2$ increases with increasing initial free moisture content.

These results indicate that, for $\text{Ca}(\text{OH})_2$, the presence of initial free moisture on the sorbent surface interferes with the reaction occurring by the equilibrium-moisture mechanism on the sorbent surface. For the high surface area materials, the surface reaction occurring with the equilibrium moisture is significant and results in high sorbent conversions. The addition of free moisture reduces the sorbent surface area available for equilibrium-type reaction, and after the free moisture has evaporated, the product formed blocks the sorbent surface area and continues to inhibit the equilibrium-moisture reaction. Whereas the reaction is very fast in the presence of free moisture, the reaction occurring after free moisture evaporation is greatly reduced by the surface products, consequently reducing the net benefit of adding free moisture to the high surface area $\text{Ca}(\text{OH})_2$. The addition of free moisture increases the sorbent conversion of the low surface area $\text{Ca}(\text{OH})_2$, in which the equilibrium moisture conversion is not significant, the conversion of all $\text{Ca}(\text{OH})_2$ sorbents clearly is approximately the same when large quantities of initial free moisture are added. This result implies that the reaction due to free moisture is independent of sorbent surface area and that overall conversion in the presence of significant quantities of free moisture is dominated by the wet-reaction mechanism.

Figure 5-9. Conversion of fly ash/ Ca(OH)_2 sorbent with initial free moisture (5,000 ppm SO_2 in flue gas, 70 °C, 10 s reaction, 58 to 63 percent RH).

Figure 5-10. Conversion of fly ash/ Ca(OH)_2 sorbent with initial free moisture (5,000 ppm SO_2 in flue gas, 70 °C, 60 s reaction, 58 to 68 percent RH).

Figure 5-11. Conversion of fly ash/ $\text{Ca}(\text{OH})_2$ sorbent with initial free moisture (5,000 ppm SO_2 in flue gas, 70 °C, 120 s reaction, 58 to 62 percent RH).

Figure 5-12. Conversion of Ca(OH)_2 sorbents with initial free moisture (5,000 ppm SO_2 in flue gas, 70 °C, 10 s reaction, 56 to 66 percent RH).

Figure 5-13. Conversion of Ca(OH)_2 sorbents with initial free moisture (5,000 ppm SO_2 in flue gas, 70 °C, 60 s reaction, 58 to 69 percent RH).

Figure 5-14. Conversion of Ca(OH)₂ sorbents with initial free moisture (5,000 ppm SO₂ in flue gas, 70 °C, 120 s reaction, 58 to 64 percent RH).

For the fly ash/Ca(OH)₂ sorbent, the conversions at low moisture contents are significantly greater in the 5,000 ppm flue gas than for the 1,000 ppm flue gas for both the 10 and 60 s reactions at 56 to 68 percent RH. The conversions at higher sorbent moisture contents are approximately equal between the 5,000 and 1,000 ppm SO₂ flue gas. An instantaneous reaction appears to occur when 5,000 ppm SO₂ is in the flue gas. Upon completion of this reaction, additional sorbent conversion, with increasing reaction time or increasing moisture content, provides incremental additional conversion. The instantaneous reaction with 1,000 ppm SO₂, is not significant, so significant additional conversion can be accomplished by increasing the reaction time or moisture content of the sorbent.

5.1.2.3 Comparison: Additive Model vs. Experiment

An expression describing the effect of excess moisture on the conversion of damp sorbent is presented below:

$$\frac{\Delta SO_2}{Ca} = \frac{D_{SO_2} K(P_{SO_2})}{D_{H_2O} K(P_{H_2O}^* - P_{H_2O})} \left(\frac{\Delta H_2O}{Ca} \right) \quad (5-10)$$

The total conversion of the sorbent is the combination of the reactions occurring because of the moisture in excess of the equilibrium (with the flue gas RH) quantity and the reaction occurring due to moisture in equilibrium with the flue gas RH. The Additive Model assumes that excess moisture on the sorbent does not interfere with the equilibrium-moisture reaction. To predict the sorbent's total conversion with the Additive Model, conversion values from equilibrium moisture studies must be added to the conversion predicted because of the excess moisture on the sorbent.

Comparisons of theoretical and observed conversions of solids with initial free moisture for various conditions of SO₂ concentration, RH, and contact time are presented in Figures 5-15 through 5-20. The Additive Model correctly predicts the conversion of the fly ash/Ca(OH)₂ sorbent at 0 percent RH in 1,000 ppm SO₂ flue gas for 60 s reaction. At these conditions, the effect of the equilibrium-moisture reaction is nearly negligible, and the sorbent conversion increases linearly with increasing moisture content. For the other conditions presented, the Additive Model consistently overpredicts the

Figure 5-15. Comparison of theoretical and observed conversions of fly ash/ Ca(OH)_2 sorbent with initial free moisture (Additive Model, 1,000 ppm SO_2 in flue gas, 70 °C, 120 s reaction, 55 to 65 percent RH).

Figure 5-16. Comparison of theoretical and observed conversions of fly ash/ Ca(OH)_2 sorbent with initial free moisture (Additive Model, 1,000 ppm SO_2 in flue gas, 70 °C, 60 s reaction, 0 percent RH).

Figure 5-17. Comparison of theoretical and observed conversions of fly ash/ Ca(OH)_2 sorbent with initial free moisture (Additive Model, 1,000 ppm SO_2 in flue gas, 70 °C, 10 s reaction, 80 to 90 percent RH).

Figure 5-18. Comparison of theoretical and observed conversions of $\text{Ca}(\text{OH})_2$ sorbents with initial free moisture (Additive Model, 5,000 ppm SO_2 in flue gas, 70 °C, 10 s reaction, 80 to 90 percent RH).

Figure 5-19. Comparison of theoretical and observed conversions of Ca(OH)_2 sorbents with initial free moisture (Additive Model, 5,000 ppm SO_2 in flue gas, 70 °C, 60 s reaction, 80 to 90 percent RH).

Figure 5-20. Comparison of theoretical and observed conversions of fly ash/ Ca(OH)_2 sorbent with initial free moisture (Additive Model, 5,000 ppm SO_2 in flue gas, 70 °C, 120 s reaction, 55 to 60 percent RH).

sorbent conversion at high sorbent moisture contents. At low initial moisture contents, the observed effect of free moisture is small compared with the equilibrium-moisture reaction. At these low moisture contents, the Additive Model is essentially the equilibrium-moisture conversion. For high free moisture contents, the overpredictions are usually less than the equilibrium-moisture contribution to the overall predicted conversion, implying that the effect of free moisture is correctly approximated, but not the effect of the wet reaction on the equilibrium-moisture reaction. The results of the 5,000 ppm study with fly ash/ $\text{Ca}(\text{OH})_2$ sorbent with initial free moisture do not fall into this category. The Additive Model grossly overpredicts the sorbent utilization, implying that the effect of initial free moisture is not as significant as expected with the fly ash/ $\text{Ca}(\text{OH})_2$ sorbent at these conditions.

The assumption appears to be erroneous that the initial free moisture on the surface of the sorbents does not interfere with the equilibrium-moisture reaction mechanism, which is the basis for the Additive Model. Significant quantities of moisture on the sorbent surface significantly reduce the surface area available for equilibrium-moisture reaction, and the equilibrium-moisture reaction likely does not begin until significant amounts of the free moisture have evaporated and the product has blocked the sorbent surface.

In the Additive Model, the sorbent conversion expected for a sorbent reacting in equilibrium moisture is added to the conversion predicted because of the initial free moisture. However, the model probably could be made more accurate by adjusting the equilibrium-moisture component to account for the reduced surface area and reduced reaction time available. Because the model correctly predicts sorbent conversions when either the free-moisture or equilibrium-moisture reactions are dominant, properly adjusting the 2 additive portions probably will provide accurate predictions.

5.1.2.4 Comparison: Interactive Model vs. Experiment

The Interactive Model uses the same expression as the Additive Model to account for sorbent conversion with free moisture on the sorbent surface. The difference between the 2 lies in the relationship between the equilibrium-moisture mechanism and the wet-sorbent mechanism. In both models, the predictions accounting for the wet and equilibrium-moisture effects are additive, although

the Additive Model assumes that excess moisture does not alter the extent of reaction occurring by the equilibrium-moisture pathway, whereas the Interactive Model assumes that the equilibrium-moisture reaction does not occur with free moisture on the sorbent surface.

The Interactive Model also assumes that the rate of sorbent conversion by the equilibrium-moisture mechanism is a function of the amount of product present on the sorbent surface. The Interactive Model requires expressions for the rate of conversion by the equilibrium-moisture mechanism as a function of sorbent conversion. The plots used to generate these expressions are presented in Figures 5-21 and 5-22. The expressions are presented in Table 5-2. To use the Interactive Model, the conversion attained by the wet-reaction mechanism is noted and the expressions presented in Table 5-2 are manipulated to determine the time required to attain this conversion by the equilibrium-moisture mechanism (t_0). The free moisture is then assumed to evaporate instantly from the sorbent surface upon introduction of the flue gas, so that the time available for reaction by the equilibrium-moisture mechanism is approximately the original reaction time (t). The rate expressions presented in Table 5-2 are evaluated twice, at time = ($t_0 + t$) and time = (t_0). The conversion expected

TABLE 5-2. RATE OF SORBENT CONVERSIONS FOR INTERACTIVE MODE

Sorbent Type	ppm SO ₂ in Flue Gas	RH [percent]	Value of Slope	Value of Intercept
Fly ash/Ca(OH) ₂	1,000	0	3.62×10^{-2}	-2.36×10^{-2}
Fly ash/Ca(OH) ₂	1,000	51-64	0.19	-0.14
Fly ash/Ca(OH) ₂	1,000	80-90	0.26	-0.11
Fly ash/Ca(OH) ₂	5,000	51-64	3.64×10^{-2}	0.18
Ca(OH) ₂ "A"	5,000	58-67	7.32×10^{-2}	0.15
Ca(OH) ₂ "B"	5,000	58-67	0.12	1.61×10^{-2}
Miss. Ca(OH) ₂	5,000	58-67	4.61×10^{-2}	5.38×10^{-2}

at t_0 is then subtracted from that expected at $t_0 + t$ to determine the conversion occurring by the equilibrium-moisture mechanism after the wet reaction is complete.

Figure 5-21. Determination of instantaneous sorbent conversion rate for Ca(OH)₂ sorbents (5,000 ppm SO₂ in flue gas, 70 °C, 55 to 65 percent RH).

Figure 5-22. Determination of instantaneous sorbent conversion rate for fly ash/Ca(OH)₂ sorbent (1,000, 5,000 ppm SO₂ in flue gas, 70 °C, 55 to 65 percent RH).

Figures 5-23 through 5-28 present comparisons between the conversions predicted by the Interactive Model and the experimentally observed conversions with 1,000 and 5,000 ppm SO_2 at 55 to 65 percent RH and 10 s and 120 s contact times. The model underpredicts fly ash/ $\text{Ca}(\text{OH})_2$ conversion with 1,000 ppm SO_2 in the flue gas at long times at 55 to 65 percent RH. At these conditions, the equilibrium-moisture conversions are significant. The Additive Model overpredicted the system performance at these conditions, whereas the Interactive Model, which incorporates into the final result a significantly lower contribution due to the equilibrium-moisture reaction, underpredicted system performance. The wet reaction apparently influences the equilibrium-moisture reaction and the model has overcompensated for this effect.

The model flaw may be attributed to inaccuracy in determining the instantaneous rate of sorbent conversion. In Figures 5-21 and 5-22, the best-fit lines do not always accurately represent the data. Errors in the projected slopes of these lines will influence the expected equilibrium-moisture conversion used in the Interactive Model.

The Interactive Model overpredicts, as does the Additive Model, the attained conversions using fly ash/ $\text{Ca}(\text{OH})_2$ sorbent in 5,000 ppm SO_2 flue gas. The overprediction apparently is generated within the expression for conversion as a function of initial moisture content, which has proven reliable with the other sorbents and with the fly ash/ $\text{Ca}(\text{OH})_2$ sorbent at low- SO_2 content. The wet reaction occurring on fly ash/ $\text{Ca}(\text{OH})_2$ with high- SO_2 contents is inhibited, falling outside the gas-phase controlled pattern.

Considering the $\text{Ca}(\text{OH})_2$ sorbents, the Additive Model slightly overpredicts the conversion of the high surface area sorbent and underpredicts the conversion of the low surface area sorbent at high moisture contents, independent of reaction time. The high surface area sorbent achieved high conversion because of the equilibrium-moisture reaction, which was inhibited by the wet reaction to a greater degree than the Interactive Model allowed. The low surface area $\text{Ca}(\text{OH})_2$ achieved minimal conversion due to the equilibrium-moisture reaction, but the Interactive Model overcompensated for the reduction in this reaction.

Figure 5-23. Interactive Model of fly ash/ Ca(OH)_2 conversion (1,000 ppm SO_2 in flue gas, 70 °C, 55 to 65 percent RH, 10 s reaction).

Figure 5-24. Interactive Model of fly ash/ Ca(OH)_2 conversion (1,000 ppm SO_2 in flue gas, 70 °C, 55 to 65 percent RH, 120 s reaction).

Figure 5-25. Interactive Model of fly ash/Ca(OH)₂ conversion (5,000 ppm SO₂ in flue gas, 70 °C, 55 to 65 percent RH, 10 s reaction).

Figure 5-26. Interactive Model of fly ash/Ca(OH)₂ conversion (5,000 ppm SO₂ in flue gas, 70 °C, 55 to 65 percent RH, 120 s reaction).

Figure 5-27. Interactive Model of Ca(OH)_2 conversion (5,000 ppm SO_2 in flue gas, 70 °C, 55 to 65 percent RH, 10 s reaction).

Figure 5-28. Interactive Model of Ca(OH)_2 conversion (5,000 ppm SO_2 in flue gas, 70 °C, 55 to 65 percent RH, 120 s reaction).

5.1.2.5 Conversion of Fly Ash/ $\text{Ca}(\text{OH})_2$ Sorbent by Reaction with CO_2

The fly ash/ $\text{Ca}(\text{OH})_2$ sorbent contained CO_2 in the form of carbonate prior to reaction with the 1,000 ppm SO_2 , 10 percent CO_2 flue gas. The initial carbonate content of the sorbent was 2×10^{-4} moles $\text{CO}_2/\text{mol Ca}$. Significant additional CO_2 capture was not discovered for short- or long-time reactions in the presence of initial free moisture on the sorbent surface (Figure 5-29). Within the ability to experimentally determine CO_2 capture on the sorbent, no CO_2 capture occurred, and more importantly, the Ca-conversion by CO_2 was much lower than conversion by SO_2 with 10 percent CO_2 and 1,000 ppm SO_2 in the flue gas.

5.1.3 Short Time Differential Reactor Results and Discussion

The Short Time Differential Reactor (STDR) previously used to identify a rate-limiting step for the reaction of dry $\text{Ca}(\text{OH})_2$ with SO_2 was used for testing solids with free moisture. Two types of sorbents were used to study the effect of initial free moisture on the conversion with SO_2 : $\text{Ca}(\text{OH})_2$ physically mixed with fly ash and $\text{Ca}(\text{OH})_2$ reacted with fly ash. Even small amounts of free moisture are known to deteriorate the handling properties of $\text{Ca}(\text{OH})_2$, which tends to agglomerate and become a paste unsuitable for DSI. Because previous work on fundamental mass-transfer mechanisms indicated that the conversion of $\text{Ca}(\text{OH})_2$ increased with increases in initial moisture on the solids, an alternative means of moisture delivery was used. The modified STDR was used to simulate the moist-duct injection (MDI) moisture delivery system. To simulate the MDI, 6 mg of dry Mississippi $\text{Ca}(\text{OH})_2$ was physically mixed with 20 or 30 mg of moist fly ash prepared in the manner described in the previous section. (Actual TGA-Detected moisture contents of a commercial Mississippi $\text{Ca}(\text{OH})_2$ was 0.55 wt percent.) Meredosia fly ash was used for MDI experiments.

Another type of sorbent tested was chemically reacted fly ash with $\text{Ca}(\text{OH})_2$. These sorbents were produced by slurring fly ash with reagent grade $\text{Ca}(\text{OH})_2$ at varying weight ratios, elevated temperature, and prolonged slurring time. Previous work indicated that using ground rather than unground fly ash can increase significantly the reactivity of sorbent for any given slurring conditions. Therefore, ground fly ash was used to produce some $\text{Ca}(\text{OH})_2$ /fly ash sorbents. Sorbents produced by

Figure 5-29. Reaction of fly ash/ Ca(OH)_2 sorbent with CO_2 (1,000 ppm SO_2 in flue gas, 70 °C, 55 to 65 percent RH).

slurrying fly ash with Ca(OH)_2 were capable of holding 20-30 wt percent moisture without significant deterioration of handling properties.

Several sorbents produced by reacting fly ash with Ca(OH)_2 were used. The two fly ashes used throughout this study, Clinch River and Meredosia result from combustion of eastern bituminous coal. For some sorbents, the fly ash was ground prior to reaction with Ca(OH)_2 . The weight ratio of fly ash to Ca(OH)_2 was varied to produce sorbents with varying surface areas. Table 5-3 shows the structural properties of fly ashes used to produce sorbents.

TABLE 5-3. STRUCTURAL PROPERTIES OF FLY ASHES USED TO PRODUCE FLY ASH/ Ca(OH)_2 SORBENTS

Fly Ash Source	Fly Ash Type	Surface Area [m^2/g]	Pore Volume [cm^3/g]	Median Pore Size [$\text{\AA}$]	Median Particle Size [μm]
Meredosia	U ^a	1.2	0.003	91	11.10
Meredosia	G ^b	6.8	0.027	159	2.00
Clinch River	U	2.2	0.005	92	12.05
Clinch River	G	5.6	0.020	145	4.96

^aU = Unground fly ash

^bG = Ground fly ash

As indicated in Table 5-3, the structural properties of Meredosia, Clinch River, and Beverly fly ashes were similar before grinding. Grinding significantly increased surface area and porosity for 3 of them.

Both ground and unground fly ashes were used to produce sorbents. These sorbents' slurrying conditions and structural properties are presented in Table 5-4. Sorbents with similar structural properties were produced by slurrying ground Meredosia or ground Clinch River fly ash for 3 h at 90 °C, using a 3:1 weight ratio of fly ash to Ca(OH)_2 . The surface area and pore volume for Meredosia- and Clinch River-based sorbents produced at the aforementioned conditions were 27 m^2/g and 0.122 cm^3/g , and 30 m^2/g and 0.132 cm^3/g , respectively. Sorbents produced by slurrying ground fly ash and Ca(OH)_2 had higher surface area and pore volume than the sorbent produced with unground fly ash. For a given source and type of fly ash, increasing the weight ratio of fly ash to Ca(OH)_2 resulted in a sorbent with greater surface area and pore volume.

TABLE 5-4. STRUCTURAL PROPERTIES OF FLY ASH/Ca(OH)₂ SORBENTS

Fly Ash Source	Fly Ash Type	Slurrying		Fly Ash/Ca(OH) ₂ Weight Ratio [g/g]	Sorbent		
		Time [h]	Temperature [°C]		Surface Area [m ² /g]	Pore Vol. [cm ³ /g]	Median Pore Size [Å]
Meredosia	U ^a	8	90	3:1	6.9	0.039	225
Meredosia	G ^b	3	90	3:1	27.4	0.122	178
Meredosia	G	3	90	2:1	17.5	0.100	229
Meredosia	G	3	90	1:1	16.6	0.132	239
Meredosia	G	8	90	3:1	33.2	0.167	201
Meredosia	G	24	90	3:1	47.0	0.213	180
Clinch River	G	3	90	3:1	30.2	0.132	174

U = Unground fly ash

G = Ground fly ash

Scanning Electron Microscope (SEM) photomicrographs of "as-received" and ground Clinch River fly ash are shown in Figures 5-30 and 5-31, respectively. The typical microscope field of "as-received" Clinch River fly ash in Figure 5-30 shows spherical particles with smooth surfaces. The median particle size of this sample measured by X-ray sedimentation (Sedigraph) was 12.05 µm.

As Figure 5-31 shows, grinding changed significantly the morphology of Clinch River fly ash. All particles visible in the SEM field are smaller than 10 µm, and most have an irregular shape. The Sedigraph method yielded a median particle size of 4.96 µm.

5.1.3.1 Effect of Sorbent Type

Moist sorbents were exposed to 2,000 ppm SO₂ in the STDR operated at 11 °C approach to saturation, which corresponded to approximately 60 percent RH. The residence time in the STDR varied from 0.5-5 s with occasional experiments performed at 60 and 400 s. Baseline experiments were done first with 6 mg of dry Mississippi Ca(OH)₂ only, and then with 6 mg of dry Mississippi Ca(OH)₂ physically mixed with 20 mg of dry Meredosia fly ash. The results are shown in Figure 5-32. No significant difference was detected (except for an outlying data point for 3-s contact time) in conversion of dry Ca(OH)₂ and dry Ca(OH)₂ physically mixed with dry fly ash.

Figure 5-30. SEM photomicrograph of "as-received" Clinch River fly ash sample, x 2,000.

Figure 5-31. SEM photomicrograph of ground Clinch River fly ash sample, x 5,000.

Figure 5-32. Baseline tests with dry Meredosia fly ash added to dry Mississippi Ca(OH)₂ (STDR, 2,000 ppm SO₂, 60 percent RH).

Following baseline tests, solids were prepared by physically mixing Ca(OH)_2 and moist Meredosia fly ash to yield 3 levels of initial free moisture: 3.9, 12.4, and 18.3 percent. The results are presented in Figure 5-33, which presents the conversion of calcium as a function of contact time. Baseline results for dry Ca(OH)_2 also are shown in Figure 5-33 for comparison. Higher conversions were measured for sorbents with increased levels of initial free moisture than for dry Ca(OH)_2 . For a given residence time, the conversion generally increased with increased initial free moisture contents of solids. The results of additional experiments performed at 60 and 400 s residence times also are shown in Figure 5-33. The effect of initial free moisture was more pronounced at longer residence times (60 and 400 s). For example, the conversion was 2.18 and 4.72 percent at 5 s residence time for dry Mississippi Ca(OH)_2 and the conversion was 7.27 and 36.3 percent at 400 s residence time for a physical mixture of dry Mississippi Ca(OH)_2 and moist Meredosia fly ash with 18.3 percent initial free moisture.

In the next series of experiments, chemically reacted fly ash with Ca(OH)_2 was used. The sorbent was microwaved after slurring to ensure dryness. Baseline experiments were done first with dry solids produced by slurring ground Clinch River fly ash and Ca(OH)_2 (3:1 weight ratio, 90 °C, 3 h, 30.2 m²/g overall dry sorbent surface area). Considerably higher conversions were measured for dry sorbent produced by slurring Ca(OH)_2 and ground fly ash than for dry Ca(OH)_2 alone. For example, following the 5 s residence time the conversion of dry fly ash/ Ca(OH)_2 sorbent was 7.35 percent, compared with 2.18 percent for dry Mississippi Ca(OH)_2 .

Following baseline tests, solids were prepared by re-wetting chemically reacted fly ash/ Ca(OH)_2 sorbent to yield 3 levels of initial free moisture: 8.5, 12, and 40 percent. The results are shown in Figure 5-34, which presents the conversion of calcium as a function of contact time with 2,000 ppm SO_2 at approximately 60 percent RH (11 °C approach to saturation). For each initial moisture content tested, the conversion increased with increased residence time. Except for 0.3 s residence time, the conversion after any residence time increased with increased initial free moisture contents.

Figure 5-33. Ca(OH)_2 physically mixed with Meredosia fly ash (STDR, 2,000 ppm SO_2 , 60 percent RH).

Figure 5-34. The effect of initial free moisture on the reactivity of chemically reacted fly ash/Ca(OH)₂ (STDR, 2,000 ppm SO₂, 60 percent RH).

The comparison of conversions measured for 2 types of sorbent is shown in Figure 5-35. Both sorbents had a comparable amount of initial free moisture: 12 percent in the chemically reacted sorbent and 12.4 percent in the physically mixed fly ash and Ca(OH)_2 . For the residence time range tested, chemically reacted fly ash/ Ca(OH)_2 sorbent consistently had higher conversions than physically mixed fly ash/ Ca(OH)_2 sorbent. The difference between the 2 sorbents was more pronounced for longer residence times (60 and 400 s). Notably, the 2 sorbents tested had different surface areas (32 m^2/g overall for chemically reacted fly ash/ Ca(OH)_2 sorbent and 17 m^2/g for Mississippi Ca(OH)_2 used for physical mixture). However, results with a physical mixture of fly ash and Ca(OH)_2 , using in-house-produced 70 m^2/g surface area Ca(OH)_2 , indicate only marginally increased conversion because of the increased specific surface area of Ca(OH)_2 (5.2 and 4.7 percent conversion after 5 s contact time when 70 and 17 m^2/g Ca(OH)_2 was used for physical mixture, respectively).

In Figure 5-36, more data are presented comparing the effect of the initial free moisture on the conversion of 2 sorbents under consideration. The physical mixture of fly ash/ Ca(OH)_2 was tested with up to approximately 20 percent initial free moisture. Chemically reacted fly ash/ Ca(OH)_2 was tested with up to approximately 40 percent initial free moisture. Attempts were unsuccessful to produce a physical mixture of Ca(OH)_2 and fly ash with initial free moisture contents above 20 percent. Figure 5-36 presents calcium conversion after 5 s residence time in the STDR with 2,000 ppm SO_2 and approximately 60 percent RH (11 °C approach to saturation). For any initial free moisture tested, reacted Ca(OH)_2 /fly ash sorbent revealed higher conversion than physically mixed Ca(OH)_2 and fly ash. The 5 s conversion of reacted Ca(OH)_2 /fly ash appears to level off at 30 percent initial free moisture contents.

5.1.3.2 Combined Effect of the Amount of Initial Free Moisture and Sorbent Surface Area

Results for Clinch River fly ash/ Ca(OH)_2 sorbent indicate that increasing the amount of initial free moisture up to 30-40 weight percent results in increased calcium conversion with SO_2 . This range of the initial free moisture content has been expanded up to 60 weight percent.

Figure 5-35. Reactivity comparison for physically mixed and chemically reacted fly ash/ $\text{Ca}(\text{OH})_2$ (STDR, 2,000 ppm SO_2 , 60 percent RH, 12-14.7 percent at limited moisture contents).

Figure 5-36. The effect of an initial moisture on the reactivity of physically mixed and reacted fly ash/ Ca(OH)_2 (STDR, 2,000 ppm SO_2 , 60 percent RH, 5 s contact time).

Figure 5-37 presents results for the sorbent produced by slurring ground Meredosia fly ash and Ca(OH)_2 for 3 h (sorbent's surface area of $27.4 \text{ m}^2/\text{g}$). Conditions in the reactor were 60 percent RH (11°C approach to saturation) and 2,000 ppm SO_2 . The initial free moisture of the sorbent was varied from equilibrium (no moisture added) up to 60 weight percent. Maximum conversion, measured for longer residence times (3 and 5 s) of $27.4 \text{ m}^2/\text{g}$ fly ash/ Ca(OH)_2 sorbent in the STDR, occurred for solids with 30 weight percent initial moisture. The effect was rather weak of initial free moisture at short (0.5 and 1 s) residence times in the STDR. The solid line in Figure 5-37 represents the conversion of equilibrium and moist solids increased as residence times in the STDR increased.

The same conditions in the STDR were used to test the effect of initial free moisture on reactivity of ground Meredosia fly ash/ Ca(OH)_2 sorbent with $33.2 \text{ m}^2/\text{g}$ surface area (sorbent preparation conditions: weight ratio = 3:1, 90°C , 8 h). Figure 5-38 presents the results for equilibrium to 60 weight percent initial free moisture range. For this sorbent, the maximum conversion was measured at 40 weight percent initial free moisture. The results for $33.2 \text{ m}^2/\text{g}$ sorbent, with equilibrium amount of initial free moisture only, are represented by the solid line in Figure 5-38. For all residence time/initial free moisture conditions tested, the addition of moisture resulted in increased conversion with SO_2 compared with levels measured for the sorbent with equilibrium moisture. Similar to $27.4 \text{ m}^2/\text{g}$ sorbent (Figure 5-37), the difference between conversions measured for equilibrium and moist solids increased as residence time in the STDR increased. However, a stronger effect occurred for initial free moisture at short residence time than for $27.4 \text{ m}^2/\text{g}$ sorbent. Maximum conversions measured for 5 s residence time in the STDR were 15.2 and 17.5 percent, for 27.4 and $33.2 \text{ m}^2/\text{g}$, respectively.

Another fly ash/ Ca(OH)_2 sorbent, which was tested in the STDR operated at 60 percent RH with 2,000 ppm SO_2 , was prepared by slurring ground Meredosia fly ash with Ca(OH)_2 at a weight ratio of 3:1, at 90°C for 24 h, and sorbent surface area of $47 \text{ m}^2/\text{g}$. Figure 5-39 shows reactivity results for this sorbent with an initial free moisture content ranging from equilibrium to 60 weight percent. For all residence time/initial free moisture conditions tested, the addition of moisture

Figure 5-37. Effect of initial free moisture on the reactivity with SO₂ of 27.4 m²/g sorbent (ground Meredosia fly ash/Ca(OH)₂ weight ratio of 3:1; reactor: 60 percent RH, 2,000 ppm SO₂).

Figure 5-38. Effect of initial free moisture on the reactivity with SO₂ of 33.2 m²/g sorbent (ground Meredosia fly ash/Ca(OH)₂ weight ratio of 3:1; reactor: 60 percent RH, 2,000 ppm SO₂).

Figure 5-39. Effect of initial free moisture on the reactivity with SO_2 of $47.0 \text{ m}^2/\text{g}$ sorbent (ground Meredosia fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio of 3:1; reactor: 60 percent RH, 2,000 ppm SO_2).

resulted in increased conversion with SO₂ compared with levels measured for the equilibrium-moisture sorbent. Maximum conversion of 25.1 percent following 5 s residence time with SO₂ was measured for a sorbent with an initial free moisture of 50 weight percent.

Data presented in Figures 5-37 to 5-39 were combined with those for sorbent produced by slurring unground Meredosia fly ash with Ca(OH)₂ at the same weight ratio of 3:1 (slurring conditions: 90 °C, 8 h) and having a surface area of only 6.9 m²/g. Figure 5-40 shows conversions measured after 5 s residence time in the STDR, operated at 60 percent RH and with 2,000 ppm SO₂. Initial free moisture content tested ranged from equilibrium to 60 percent. Maximum conversion with SO₂ measured for each sorbent increased as sorbent-specific surface area increased. For 6.9, 27.4, 33.2, and 47.0 m²/g sorbents tested, the corresponding maxima were 12.3, 15.2, 17.5, and 25.1 percent, respectively. The initial free moisture content, for which the maximum conversion for a given sorbent was measured, varied with the sorbent's specific surface area. The initial free moisture contents of the 4 aforementioned sorbents, for which the maximum conversion with SO₂ was measured, were 30, 30, 40, and 50 percent, respectively. The reactivity differential between 40 and 60 percent initial free moisture increased, resulting in a steeper slope between 40 and 60 percent initial free moisture, as the sorbent's surface area increased. For example, for 6.9 and 47.0 m²/g sorbents, the reactivity differentials between 40 and 60 weight percent were 1.7 and 12.9 percent, respectively. Table 5-5 compares the aforementioned data.

TABLE 5-5. EFFECT OF SPECIFIC SURFACE AREA ON REACTIVITY OF MOIST SORBENT WITH SO₂ (MEREDOSIA FLY ASH/Ca(OH)₂ WEIGHT RATIO OF 3:1, 90 °C SLURRYING)

Sorbent Surface Area [m ² /g]	Pore Volume [cm ³ /g]	Maximum Measured Conversion with SO ₂ [percent] ^a	Corresponding Initial Free Moisture [weight percent]	Reactivity Differential [percent] ^b
6.9	0.039	12.3	30	1.7
27.4	0.122	15.2	30	-0.8
33.2	0.167	17.5	40	7.0
47.0	0.213	25.1	50	12.9

^aConversion after 5 s in the STDR, 60 percent RH, 2,000 ppm SO₂

^bMeasured reactivity differential for sorbent with 40 and 60 percent initial free moisture

Figure 5-40. Effect of sorbent-specific surface area on the reactivity of moist sorbent (Meredosia fly ash/ Ca(OH)_2 weight ratio of 3:1; reactor: 60 percent RH, 2,000 ppm SO_2).

5.1.3.3 Effect of the Approach to Saturation

Experiments with equilibrium-moisture Ca(OH)_2 indicated that conversion of Ca(OH)_2 with an equilibrium amount of moisture increased as the approach to saturation decreased. Sorbents were produced by slurring ground Clinch River fly ash and Ca(OH)_2 at the weight ratio of 3:1 at 90 °C for 3 h with sorbent-specific surface area of 30.2 m²/g and with 30 weight percent initial free moisture. Test results of these sorbents revealed weak effect of approach to saturation (2.8 °C to 22 °C approach) on conversion of the sorbent with SO_2 . When the sorbent with 30 weight percent initial free moisture was exposed to dry gas with 2,000 ppm SO_2 , conversion decreased for longer (3 and 5 s) residence times in the STDR, compared with conversion measured for moist gas. No decrease was measured for short (0.5 and 1 s) residence times in the STDR. These results are shown in Figure 5-41.

A sorbent produced with ground Meredosia fly ash was used to investigate the effect of the approach to saturation on the conversion of sorbents with 60 weight percent initial free moisture and with only equilibrium-moisture content. Ground Meredosia fly ash was slurried with Ca(OH)_2 at a weight ratio of 3:1 at 90 °C for 3 h and sorbent-specific surface area of 27.4 m²/g. Figure 5-42 shows the results of experiments with the sorbent containing 60 weight percent initial free moisture. Similar to the results presented in Figure 5-41, only a very weak effect was detected of an approach to saturation (2.8 to 22 °C range) on the conversion with 2,000 ppm SO_2 gas. No significant effect was detected of an approach to saturation on conversion with SO_2 for long (5 s) contact time in the STDR. At short (0.5 and 1 s) residence times, higher conversions were measured for sorbent exposed to dry gas than for sorbent exposed to humid gas.

Finally, conversion of the 27.4 m²/g sorbent with equilibrium moisture only was measured in the STDR with 2,000 ppm SO_2 . Figure 5-43 presents the results of the approach to saturation, which varied from 2.8 to 22 °C, and for the dry gas. Conversion with SO_2 increased as approach to saturation decreased. Conversion measured after the contact with dry gas was less than 1 percent.

Figure 5-41. Effect of the approach to saturation on the reactivity of 30.2 m²/g sorbent with 30 weight percent initial free moisture (ground Clinch River fly ash/Ca(OH)₂ weight ratio of 3:1, 2,000 ppm SO₂).

Figure 5-42. Effect of the approach to saturation on the reactivity of 27.4 m²/g sorbent with 60 weight percent initial free moisture (ground Meredosia fly ash/Ca(OH)₂ weight ratio of 3:1; reactor: 2,000 ppm SO₂).

Figure 5-43. Effect of the approach to saturation on the reactivity of 27.4 m²/g sorbent with equilibrium moisture (ground Meredosia fly ash, Ca(OH)₂ weight ratio of 3:1; reactor: 2,000 ppm SO₂).

5.1.3.4 Effect of Fly Ash Source

Sorbents were produced using 2 different fly ashes to compare the effect of fly ash source on their reactivity. Both fly ashes (Clinch River and Meredosia) were ground to approximately the same extent prior to reacting them with $\text{Ca}(\text{OH})_2$ at the same time/temperature conditions (3 h at 90 °C), and at the same fly ash-to- $\text{Ca}(\text{OH})_2$ weight ratio of 3:1. The resulting sorbents developed similar specific surface areas of 30.2 and 27.4 m^2/g using Clinch River and Meredosia fly ash, respectively. Both sorbents were loaded with moisture to yield 30 weight percent of initial free moisture content. The sorbents were then exposed to SO_2 in the STDR operated at 60 percent RH (11 °C approach to saturation) and with 2,000 ppm SO_2 . Figure 5-44 presents results for STDR residence times from 0.5 to 5 s. For a given contact time, no significant difference was detected in reactivity with SO_2 for the sorbents produced with the 2 fly ashes.

In the next step, both sorbents, with initial free moisture content varying from 10 to 60 weight percent, were reacted with SO_2 . STDR results for 5 s residence time, shown in Figure 5-45, are similar to the results presented in Figure 5-44. For the aforementioned 2 fly ashes tested, fly ash source had no significant effect on sorbent reactivity with SO_2 . The data points at approximately 5 weight percent initial free moisture represent conditions for "dry" sorbents at equilibrium with the gas. The slightly higher reactivity of sorbent produced with ground Clinch River fly ash in comparison with ground Meredosia fly ash may be a consequence of the former sorbent's somewhat higher specific surface area. (For sorbents with equilibrium moisture, conversion increases with increasing surface area.)

For both sorbents, an optimum initial free moisture content was detected for maximum conversion with SO_2 at conditions tested in the STDR. For solids produced with ground Clinch River fly ash, the maximum conversion occurred with initial free moisture contents of 30 and 40 weight percent. For solids produced with Meredosia fly ash, the maximum conversion occurred at 30 weight percent initial free moisture content. This maximum conversion was approximately 15 percent for both sorbents after 5 s residence time in the STDR operated at 11 °C approach to saturation and with 2,000 ppm SO_2 .

Figure 5-44. Effect of fly ash source on reactivity of sorbent with SO_2 (ground fly ash-to- Ca(OH)_2 weight ratio of 3:1, 30 weight percent initial free moisture, 2,000 ppm SO_2 , 60 percent RH).

Figure 5-45. Combined effect of fly ash source and initial free moisture content on sorbent's reactivity with SO_2 (ground fly ash-to- Ca(OH)_2 weight ratio of 3:1, 2,000 ppm SO_2 , 60 percent RH, 5 s residence time).

5.2 SOLIDS MOISTURE CAPACITY

5.2.1 Introduction

As shown in previous sections, $\text{Ca}(\text{OH})_2$ sorbent reactivity is enhanced by free moisture on the sorbent. However, large amounts of moisture may adversely affect sorbent handling and utilization, and system reliability. As duct injection technology begins large pilot-scale and demonstration-scale development, these effects assume greater significance.

The duct-injection process using solids with initial free moisture consists of the following steps: preparation of sorbent as a slurry; blending of the slurry with dry recycle materials to create solids with initial free moisture; injection of the solids into the duct; reaction and drying of the solids with flue gas in the duct; collection in particulate control equipment; and, finally, recycle of dry solids with some bleed to disposal. The moisture content of the solids at each step affects system performance.

The hydrothermal reaction of fly ash with $\text{Ca}(\text{OH})_2$ produces calcium silicates that are more reactive than $\text{Ca}(\text{OH})_2$ toward SO_2 (Jozewicz and Rochelle, 1986) because of the greater surface area, amorphous surface structure, and molecular moisture of the calcium silicates (Jozewicz et al., 1988a). The moisture content of the slurry leaving the reaction tank must be reduced. The proposed method is to mix dry recycle material with the slurry. Recycle of unreacted sorbent would increase its utilization. However, as the moisture content of the mixture is reduced by addition of more recycle material, the load on the particulate control device increases, which may affect its performance. Furthermore, reactivity of the sorbent is generally reduced by decreasing its moisture content. As the moisture content of the slurry is decreased, it becomes a paste, making handling and injection difficult. Further drying eventually would produce a dry powder. Exploration of the gap between a poorly manageable paste and a dry powder is the focus of this section (Stroud, 1991).

5.2.2 Theory of Agglomeration

Several forces may contribute to particle agglomeration. A particle in a dry atmosphere will experience the following forces: (1) Van der Waals forces caused by fluctuating dipoles, (2) electrostatic attractions caused by excess charge on nonconducting materials, (3) mechanical interactions caused by particle interlocking and solid bridges formed from crystallizing salt, sintering, or chemical reactions, and (4) magnetic forces between particles of certain materials. For particles with

radii less than 100 μm , the van der Waals force is much greater than the electrostatic attraction (Rumpf, 1977). Magnetic attractions can cause very significant interactions between certain particles, but are not evident with calcium-based sorbents.

These forces can be reduced significantly by materials acting as spacers between the particles (Dutta and Dullea, 1989). Spacers could include fine particles or adsorbed gas molecules. A particle in equilibrium with RH but with no free moisture would experience an increase in the van der Waals force because the adsorbed vapor acts as part of the particle and thus reduces the interparticle distance. However, electrostatic forces would decrease because of the conductivity of the humid air, and frictional resistance to particle movement might decrease by action of the adsorbed layer as a lubricant.

When liquid is present on the surface of particles, the reduction in surface energy from merging liquid films results in particle agglomeration. The cohesive strength of such agglomerates has been found to be directly proportional to the surface tension of the binding liquid (Newitt and Conway-Jones, 1958). Agglomerates are strengthened further by capillary pressure from liquid in the void volume of the agglomerate. The opportunity for agglomeration depends on the amount of contact between particles. The size of agglomerates formed from damp particles was shown to increase with time in a tumbling contactor (Newitt and Conway-Jones, 1958).

The cohesive strength of an agglomerate increases with moisture content, reaching a maximum when the void volume of the agglomerate is almost completely filled with liquid (Newitt and Conway-Jones, 1958). The strength also is dependent on whether the moisture content in the void volume is reached by absorption or drainage (Rumpf, 1977).

5.2.3 Approach

Fly ash/ $\text{Ca}(\text{OH})_2$ sorbents were prepared by slurring fly ash with $\text{Ca}(\text{OH})_2$ and analyzed for critical moisture, surface area, and pore volume. Critical moisture quantifies a powder's capacity for moisture and is defined by the test procedure described below. Slurry liquids were analyzed for pH and various ions to monitor the fly ash/ $\text{Ca}(\text{OH})_2$ reaction.

The slurries generally contained a silica source—fly ash or silica fume—and $\text{Ca}(\text{OH})_2$. Calcium sulfite hemihydrate ($\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$) and gypsum ($\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$) sometimes were added; they represented species present in recycle material. Two types of fly ash were used: a low-calcium ash

from eastern bituminous coal and a high-calcium ash from western subbituminous coal. The former was a sample of Clinch River fly ash taken in October 1986 from the Appalachian Power Company's Clinch River plant (Peterson, 1987). Because the composition of the ash may vary slightly depending on sample date, the composition of the ash used in this study is listed in Table 5-6. The second type of fly ash was high-calcium Harrington fly ash taken in July 1987 from the Southwestern Electric Power Company's Harrington Station where subbituminous coal from the Powder River basin of Wyoming was burned. The ash also was used by Peterson (1990). The ash had a surface area of 2 m²/g; its composition is listed in Table 5-6.

Silica fume, a by-product from the manufacture of silicon metal, was used in place of fly ash in some experiments, and material also was used by Peterson (1990). The silica fume was obtained from the University of Texas' Ferguson Structural Engineering Laboratory. The material was 92-percent SiO₂ and non-crystalline, with a 20-m²/g surface area (Peterson, 1990).

The Ca(OH)₂ used in nearly all experiments was commercial Mississippi Rotary Ca(OH)₂ (Code MR200) from the Mississippi Lime Company. CaSO₄•2H₂O used in experiments was reagent-grade material from the Aldrich Chemical Company. CaSO₃•0.5H₂O used in experiments was prepared in the laboratory by adding 1 M CaCl₂ to 1 M Na₂SO₃. CaSO₄•2H₂O and CaSO₃•0.5H₂O had surface areas of 2 and 6 m²/g, respectively. Fly ash/Ca(OH)₂ sorbents were prepared by slurring solid reactants in a 500-mL stainless steel vessel. Slurry samples were drawn (usually about 50 mL) at times ranging from 15 min to 24 h.

TABLE 5-6. CHEMICAL COMPOSITION OF SILICA SOURCES
(FROM ENERGY-DISPERSIVE SPECTROSCOPY)

Silica Source	CaO	SiO ₂	Al ₂ O ₃	Fe ₂ O ₃	(Na & K) Na ₂ O
Clinch River Fly Ash	4	57	27	8	
Harrington Fly Ash	30	32	22	5	1.7*
Silica Fume	0.1	92	3	2	0.3

Critical moisture, as defined here, quantifies a powder's capacity for moisture before exceeding a specified degree of agglomeration. Most powder tests measure the cohesiveness of a powder and alternatively, the ability of a powder to flow. A more cohesive powder is less freely flowing and,

therefore, the 2 measures are related (Carr, 1970). Flow characteristics are commonly evaluated by simple tests to determine the angle of repose, angle of fall and, to evaluate adhesiveness to a dissimilar surface, the angle of slide.

Powder cohesiveness can be evaluated by measuring shear yield strength, compressibility, or retention by sieves. Shear strength is measured in a split-cell shear cell with a vertical compressive force (Jenike et al., 1960). The procedure is derived from soils testing and is not practical for samples with very low cohesiveness. The yield strength is affected by the water content and particle size distribution of the material. A second measure, compressibility, is determined by comparing the loosely packed bulk density of a material with its packed density. Cohesive powders are more compressible (Carr, 1970). A third method for evaluating the cohesiveness of a powder measures retention on a nest of 60-, 100-, and 200-mesh sieves (Carr, 1965). The procedure involves placing 2 g of material on the nest and vibrating for 20 to 120 s according to the density of the material. The sieve sizes also can be altered for varying density materials. If the entire 2 g of sample remains on the 60-mesh sieve, cohesion is 100 percent. Cohesion is zero if all the material passes through the 200-mesh sieve.

In this study, a 5-g sample was placed on an 80-mesh sieve (177 μm between wires) and shaken for 10 min. Tests were run on samples with varying amounts of moisture to determine the amount of moisture that caused half the sample to be retained by the 80-mesh sieve. This amount was called the critical moisture (grams of water/g of wet solids expressed as a percentage).

A standard, full-height, 80-mesh sieve with pan and cover from Brainard-Kilman was used. Water was added dropwise to 5 g of a dry powdered sample in a glass beaker. The water was mixed in manually with a metal chemical spatula. The mixture was spread against the beaker wall and repeatedly chopped in an attempt to distribute the water uniformly and break any clumps. The sample was weighed before water was added and after it was mixed in to determine the initial moisture content. After the moist sample was weighed, subsequent steps were performed without delay to minimize evaporation. Each complete test took about 15 min.

The moist sample was spread uniformly over the sieve, the lid placed on, and the assembly placed in a mechanical sieve shaker (without a tapping device) and shaken for 10 min. After 10 min the material retained by the sieve and the material collected in the pan was weighed. This procedure usually was repeated on 3 or more samples at different moisture contents until the critical moisture was bracketed and could be determined by linear interpolation. A fresh sample was used for each test, but all samples came from the same experiment.

5.2.4 Results for Individual Reactants and Dry Mixtures

This section addresses results of experiments with low-calcium fly ash, ground low-calcium fly ash, and high-calcium fly ash. Presented in Figure 5-46 are data for a standard sorbent (3 g of Clinch River fly ash/g $\text{Ca}(\text{OH})_2$ slurried for 8 h at 92 °C) tested over a wide range of moisture content. The critical moisture content is determined by linear interpolation between the 2 points closest to the horizontal line indicating 50-percent passing. The value determined from Figure 5-46 is 17 percent. Values are rounded to a whole number because of uncertainty in the number.

A sorbent was subjected, on average, to 3 sieve tests at different moisture contents. When critical moisture content was determined more than once for a particular sorbent, the values were reproducible within a range of 3 percentage points. The critical moisture content was measured more than once for 13 sorbents and reactant mixtures. The values differed by 2 or less in all but 1 case. Multiple values of critical moisture were determined on separate occasions.

The average sample recovery after sieve tests was 94.4 percent of the initial wet weight. Losses were due to evaporation, dispersion of fines, and retention by the sieve. Evaporative losses were measured in 14 tests in which the sample was subjected to 15 min of sieving. The samples initially contained from 7.3 to 29.7 percent moisture. The average evaporative loss was 3.9 percent of the initial wet weight. Although critical moisture content was based on the initial moisture content, the amount passing through a sieve was affected by the final moisture content. Therefore, a faster drying material would be expected to have increased critical moisture content. The change is insignificant

Figure 5-46. Typical results for sieve tests of fly ash/ $\text{Ca}(\text{OH})_2$ sorbent (critical moisture content 17 percent, Clinch River fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio slurried for 8 h at 92 °C).

except in samples with a low critical moisture, although those samples would be expected to lose moisture at the slowest rate because of the small driving force.

To relate critical moisture content to a more commonly measured sorbent property, values were plotted against specific surface area. Figure 5-47 shows that critical moisture content increases with surface area. The data are from all fly ash/ $\text{Ca}(\text{OH})_2$ sorbents tested in this study, and, therefore, reflect a broad range of preparation conditions. Deviations from the general cluster are random and are discussed in the sections following for each silica source.

Most of the surface area of these sorbents occurs in the particle pore space, which is filled, to some degree, by water when it is added to the dry sorbent. When moist sorbent agglomerates, much of the moisture may be hidden in the particle pore space. Therefore, critical moisture content may correspond more directly to pore volume than to surface area. Figure 5-48 shows the results of critical moisture tests, expressed as a ratio of water-to-dry solid, plotted versus particle-specific pore volume. The relationship is nearly 1:1; that is, each mL of pore space corresponds roughly to 1 mL of absorbed water at the critical moisture content. If the pore space was completely filled with water, the moisture ratio at the critical moisture content would be greater than the pore volume because water is needed outside the pore space to cause agglomeration. However, water added to a dry solid does not necessarily fill all the pore space, so the critical volume of water need not equal the pore volume.

Pore volume and surface area are related by the cylindrical pore model. Figure 5-49 shows the relation between the values for fly ash/ $\text{Ca}(\text{OH})_2$ sorbents. The data in Figure 5-49 indicate an effective pore radius of 110 Å. Surface area measurements require much less time than pore volume measurements and are routinely measured. Therefore, all further critical moisture results are correlated with surface area.

Figure 5-47. Correlation of the moisture data (points represent all fly ash/Ca(OH)₂ sorbents, including duplicates, tested during this study; silica sources were Clinch River fly ash, ground Clinch River fly ash, Harrington fly ash, and silica fume).

Figure 5-48. Correlation of critical moisture ratio at the critical moisture content.

Figure 5-49. Correlation of particle pore volume with specific surface area (the dotted line and equation are a least-squares fit of the data).

The critical moisture content of unreacted reagents and their mixtures has been compared to surface area, as shown in Figure 5-50. Most of the reactants are relatively low-surface-area materials with correspondingly low critical moisture. The exception is Ca(OH)_2 which has an area of $20 \text{ m}^2/\text{g}$, yet has a critical moisture content of zero; that is, only half of an oven-dried sample with no water added will pass through an 80-mesh sieve during 10 min of sieving. The anomaly cannot be attributed to large particles. The median particle size of Mississippi Ca(OH)_2 has been reported as $2.86 \mu\text{m}$ (Rochelle et al., 1990), whereas unground Clinch River fly ash has a $12 \mu\text{m}$ median diameter and a 2 percent critical moisture. Another example is that of ground Clinch River fly ash, which has a median diameter smaller than that of unground fly ash yet also has a lower critical moisture content of zero percent. Conversely, $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$, which has a large diameter of $25 \mu\text{m}$ (Tseng and Rochelle, 1986), has a critical moisture of 5 percent. The zero-value critical-moisture content for the small particles may occur because these particles can pack closer, allowing attractive forces to exert a greater influence.

The poor critical moisture content of Ca(OH)_2 can be diluted by mixing it with other materials. A dry mixture of ground Clinch River fly ash and Ca(OH)_2 (4:1 weight ratio) had, not surprisingly, a critical moisture of zero. The same mixture with $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ and $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ added (44 percent) had a critical moisture of 2 percent. Without Ca(OH)_2 , the critical moisture of the mixture (now 50-percent calcium sulfite and gypsum) increased to 5 percent. Although the critical moisture of each subsequent mixture increased, the surface area of each mixture decreased, probably because of dilution of the large area of Ca(OH)_2 . The same increase in critical moisture with Ca(OH)_2 dilution was seen with unground fly ash. Therefore, whereas Ca(OH)_2 has a poor critical moisture content (it falls below the correlation with surface area), its effect on mixtures can be diluted. The behavior of dry mixtures is not accurately predicted by simply averaging on a mass basis the values of the pure reagents. However, the uncertainty of critical moisture and surface area measurements at low values may be at fault.

Figure 5-50. Critical moisture content of reactant and dry mixtures ($\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$, Harrington fly ash, Clinch River fly ash, $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$, ground Clinch River fly ash, and 20-m²/g $\text{Ca}(\text{OH})_2$).

The correlation presented in Figure 5-47 shows that a discussion of surface-area development also can be considered a discussion of critical moisture development. Therefore, previous research on fly ash/ $\text{Ca}(\text{OH})_2$ sorbent preparation, which reported surface area data, now can be used to indicate moist-sorbent behavior. The remainder of this section focuses on the critical moisture content of sorbents prepared from a variety of slurry compositions.

5.2.5 Results for Sorbents Prepared From Slurry

Sorbent preparation from Clinch River fly ash and the reactivity of those sorbents toward SO_2 has been studied extensively at Acurex Corporation and the University of Texas. Therefore, Clinch River fly ash was used as a baseline material in this study. Previous work has shown that sorbent reactivity increases with slurry time and temperature (Jozewicz and Rochelle, 1986). However, a limit is achieved with pressure hydration and dependent on the fly ash/ $\text{Ca}(\text{OH})_2$ ratio, beyond which reactivity decreases (Jozewicz et al., 1988b). This limit is believed to be due to the formation of another phase with less molecular water and a more crystalline structure. A slurry temperature of 92 °C was chosen for this study to maximize the reaction rate at atmospheric pressure and to allow direct comparison with the results of Peterson (1990). Sorbents were prepared with 3 g and 4 g of fly ash/g $\text{Ca}(\text{OH})_2$. These compositions commonly are used by others in bench- and pilot-scale work. Figure 5-51 shows that the critical moisture content of the sorbents increased with slurry time up to 8 h. A significant difference in values was not detected between sorbents prepared from 3:1 and 4:1 ratios, and values were comparable for the same composition prepared on different occasions.

The presence of $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ in slurries of high-calcium fly ash with $\text{Ca}(\text{OH})_2$ has been shown to enhance the surface area and reactivity of the product solids (Peterson, 1990). $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ appears to interact selectively with the aluminum of the fly ash to reduce its reaction with $\text{Ca}(\text{OH})_2$ and to reduce the formation of low-surface-area calcium-aluminate materials. The effect of $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ is not expected to be as great with low-calcium fly ash because aluminum dissolution occurs to a lesser extent (Peterson, 1990). $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ also has been shown to have a beneficial effect, although the effect is believed due to $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$, which is present in small amounts in laboratory-prepared

Figure 5-51. Effect of slurry time and fly ash/ $\text{Ca}(\text{OH})_2$ ratio on critical moisture content of sorbent from low-calcium fly ash (open symbols are the 3:1 Clinch River fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio; solid symbols are 4:1 ratio).

calcium sulfite. Figure 5-52 shows that $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ did not have an effect on either critical-moisture content or surface area. $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ mixed with $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ did not have an appreciable effect on critical moisture, although surface area was greater at 12 h. The effect of $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ may be more pronounced at longer slurry times. Figure 5-53 shows that dissolved calcium essentially was spent after 12 h in slurries without $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$, but was still available for calcium silicate production in the slurry containing $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$. Results from ground Clinch River ash (discussed below), which reacts faster than unground ash, show that $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ enhanced critical moisture after 8 h. The presence of $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ and $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ in slurries did not alter the relationship between critical moisture and surface area. All samples prepared with unground Clinch River fly ash generally correlate (Figure 5-47).

Ground fly ash has a greater silica dissolution rate than unground fly ash, which results in greater production of calcium silicates (Peterson, 1990). Sorbents prepared from ground fly ash have greater surface area and are more reactive with SO_2 than sorbents prepared from unground ash (Petersen et al., 1989; Hall et al., 1991). In this study, ground Clinch River fly ash produced sorbents with a greater critical moisture content than those from unground ash. The increase in critical moisture over that of sorbents from unground fly ash is shown in Figure 5-54 for several slurry compositions. Also shown is the enhancement of critical moisture after 8 h of reaction with $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ and calcium sulfite in the slurry. Figure 5-55 shows that recycle materials enhanced surface area after only 6 h of slurry reaction with ground ash, whereas unground ash (Figure 5-47) required 12 h.

The fly ash/ $\text{Ca}(\text{OH})_2$ ratio in the slurry is an important process variable. Previous work with unground Clinch River fly ash showed that $\text{Ca}(\text{OH})_2$ conversion (moles SO_2 /mole $\text{Ca}(\text{OH})_2$) increases as the fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio increases over a range from 0.8:1 to 15.9:1 (Jozewicz et al., 1988b). In addition to an increase in conversion, surface area is reported to increase from 9.9 m^2/g to 19.2 m^2/g when the ratio is increased from 2:1 to 10:1 (slurrying 8 h at 90 °C) and from about 12 m^2/g

Figure 5-52.

Effect of CaSO_3 and $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ with CaSO_3 on sorbents from low-calcium fly ash (solid symbols are 4:1 Clinch River fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio; open squares 4:1:4 fly ash/ $\text{Ca}(\text{OH})_2/\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$; triangles 4:1:3:1 fly ash/ $\text{Ca}(\text{OH})_2/\text{CaSO}_3/\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$).

Figure 5-53. Effect of CaSO₃ and CaSO₄·2H₂O with CaSO₃ on solution composition of low-calcium fly ash slurry (solid symbols 4:1 Clinch River fly ash/Ca(OH)₂ weight ratio; open squares 4:1:4 fly ash/Ca(OH)₂/CaSO₃·0.5H₂O; triangles 4:1:3:1 fly ash/Ca(OH)₂/CaSO₃/CaSO₄·2H₂O).

Figure 5-54. Effect of fly ash grinding and the presence of $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ on critical moisture content (all samples slurried for 8 h, slurry composition represented as g Clinch River fly ash/g $\text{Ca}(\text{OH})_2$ /g $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ /g $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$).

Figure 5-55. Effect of $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ and CaSO_3 on sorbent from ground low-calcium fly ash (solid symbols 1:1 ground Clinch River fly ash/ $\text{Ca}(\text{OH})_2$ weight ratio; open symbols 4:4:3:1 fly ash/ $\text{Ca}(\text{OH})_2$ / $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ / $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$).

to 20 m²/g when the ratio is increased from 1:2 to 5:1 (slurrying 2 h at 150 °C) (Jozewicz et al., 1988a). With Clinch River fly ash ground to 5.0 m²/g, increasing the ratio from 2:1 to 3:1 results in increased surface area; for unground ash the change in ratio does not cause a significant change in surface area (Peterson, 1990).

Figure 5-56 shows the effect on both critical moisture and surface area of varying the fly ash/Ca(OH)₂ ratio over the range from 1:4 to 4:1 in slurries of ground fly ash with CaSO₄•2H₂O and CaSO₃•0.5H₂O. Solids from a slurry with no Ca(OH)₂ also were tested. A maximum in both critical moisture and surface area occurred at a 1:1 fly ash/Ca(OH)₂ weight ratio (0.50 fly ash fraction) when the slurry time was 8 h. Critical moisture data at shorter times are insufficient, but surface area data at 2, 4 and 8 h are shown in Figure 5-57. The surface area of 4 and 2 h samples remained constant or decreased slightly as the fly ash/Ca(OH)₂ ratio was increased. The 2 h data follow a line between the endpoints that dry mixtures would be expected to follow, which suggests minimal reaction at 2 h. The decreasing values of surface area are contradictory to the results of other values discussed above. However, these values differ because the slurries in this study contained CaSO₄•2H₂O and CaSO₃•0.5H₂O. The 8 h data show increasing area as the fly ash/Ca(OH)₂ ratio was increased except at a 0.80 fly ash fraction. The lower surface area may be attributed to a low pH value. Figure 5-58 shows solution data for the slurries. Calcium concentrations always were adequate for calcium silicate formation and pH values were consistently high except at 8 h in the slurry with a 0.80 fraction. The pH dropped below levels of Ca(OH)₂ saturation between 2 and 8 h. Solution equilibria was then controlled probably by calcium aluminate silicate solids. The rate of ash dissolution and surface area development would decrease.

The high Ca(OH)₂ fraction in some slurries did not necessarily produce sorbents with poor critical moisture relative to their surface area. One exception is the sorbent produced after 8 h of slurrying with 80 percent Ca(OH)₂ and no CaSO₄•2H₂O or CaSO₃•0.5H₂O (sample with: 38 m²/g and

Figure 5-56. Effect of fly ash fraction on sorbent from ground low-calcium fly ash (all samples slurried for 8 h, ground Clinch River fly ash/ $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ / $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ weight ratio constant at 4:3:1; zero fly ash fraction represents unreacted Ca(OH)_2).

Figure 5-57.

Effect of fly ash fraction and slurry time on surface area of sorbent from ground low-calcium fly ash (slurry times of 2, 4, and 8 h, ground Clinch River fly ash/ $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ / $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ weight ratio constant at 4:3:1; zero fly ash fraction represents unreacted Ca(OH)_2).

Figure 5-58. Effect of fly ash fraction on solution composition of ground low-calcium fly ash slurry (slurry times of 2, 4, and 8 h, ground Clinch River fly ash/ $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ / $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ weight ratio constant at 4:3:1).

8 percent critical moisture). Unreacted Ca(OH)_2 was probably present even at 8 h, which could have a deleterious effect on the critical moisture. Data points for other sorbents also lie off the correlation, but the deviations appear to be independent of slurry composition because similar sorbents at different slurry times lie on the correlation.

The high availability of silica and large calcium content in high-calcium fly ash suggest that it would make an attractive reagent for sorbent production (Peterson and Rochelle, 1988). When high-calcium fly ash is slurried alone (e., without Ca(OH)_2) the product solids are more reactive (SO_2 capture) with SO_2 than solids prepared similarly from low-calcium fly ash, and also have greater surface area. However, with both types of fly ash, the addition of Ca(OH)_2 to the slurry enhances surface area (Peterson, 1987). The development of critical moisture with slurry time for a slurry of Harrington fly ash (high-calcium fly ash) with no Ca(OH)_2 present is shown in Figure 5-59. The critical moisture increased with slurry time, although only slightly, after 4 h. Results for a sorbent prepared with Ca(OH)_2 in a 3:1 fly ash/ Ca(OH)_2 ratio also are shown. Both sorbents developed the same critical moisture at 8 h, and surface area development was similar.

The effect of $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ in the slurry on critical moisture is shown in Figure 5-60. Critical moisture was about the same at long times (12 and 24 h) for sorbents produced from slurries of fly ash alone and from slurries of fly ash with $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$. The result was similar when $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ was used instead of $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$. Surface area was lower when $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ or $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ was present ($14 \text{ m}^2/\text{g}$ at 8 h versus $19 \text{ m}^2/\text{g}$ for fly ash slurried alone). Dissolved sodium concentrations reflect the values of surface area. Figure 5-61 shows that sodium increased with slurry time, which reflects its release from reacting fly ash during calcium silicate formation (surface area development). The concentration at 8 and 12 h was greater in the slurry without $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$, as was the surface area of the sorbents. A relationship between surface area and sodium concentration was displayed by all the data from experiments with Harrington fly ash. The pH values in Figure 5-61 are dependent on $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ concentrations as well as sodium (as NaOH) concentrations, and, therefore, do not

Figure 5-59.

Critical moisture content of sorbent prepared from high-calcium fly ash alone, and fly ash with $\text{Ca}(\text{OH})_2$ ("Ash Alone": Harrington fly ash slurried without $\text{Ca}(\text{OH})_2$ at 26 percent solids, "With $\text{Ca}(\text{OH})_2$ ": weight ratio of Harrington fly ash/ $\text{Ca}(\text{OH})_2$ slurried at 92 °C at 26 percent solids).

Figure 5-60. Effect of $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ on critical moisture content of sorbent prepared from high-calcium fly ash ("Ash Alone": average values of data shown in Figure 5-14 for sorbent prepared from Harrington fly ash, "With Gypsum": 3:0:6 Harrington fly ash/ $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$, " $\text{Ca}(\text{OH})_2$ & Gypsum": 3:1:0.67 Harrington ash/ $\text{Ca}(\text{OH})_2/\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$).

Figure 5-61. Solution composition of slurries with high-calcium fly ash ("Ash Alone": Harrington fly ash slurried without $\text{Ca}(\text{OH})_2$ at 23 percent solids, "With Gypsum": 3:0:6 Harrington fly ash/ $\text{CaSO}_4 \cdot \text{H}_2\text{O}$ weight ratio).

correlate with surface area. All of the solution data indicate Ca(OH)_2 saturation, even when ash was slurried alone.

Another result shown in Figure 5-60 is that $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ enhanced critical moisture, as it did surface area, in slurries of ash with Ca(OH)_2 . The data in Figure 5-60 indicate that $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ was not beneficial unless Ca(OH)_2 was present. To investigate that behavior the Ca(OH)_2 loading (g Ca(OH)_2 /g fly ash) was varied in slurries with constant amounts of fly ash and $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$.

Figure 5-62 shows that both critical moisture and surface area remained about the same for loadings from 0.07 to 0.33 (fly ash/ Ca(OH)_2 ratios from 15:1 to 3:1). As the loading was decreased further both properties decreased. A minimum amount of Ca(OH)_2 appears to be required to achieve fly ash activation, but greater amounts were of no additional benefit, a conclusion supported by pH values in Figure 5-63. These values were relatively low and constant until the loading reached 0.07, which also was the point at which surface area reached its ultimate value. The sodium concentrations simply reflect increased ash activation as pH increased.

5.3 RECYCLE OPERATION

5.3.1 Dry-Sorbent Injection Downstream of Humidification

Pilot plant (50 cfm) was used for evaluation of dry-sorbent injection (DSI) mass transfer enhancement by the recycle operation. The first test series was to evaluate the baseline performance to establish the Ca(OH)_2 utilization and data reproducibility of once-through operations for DSI downstream of the humidifier. The major operating parameters are listed in Table 5-7. Fly ash from the Meredosia Power Plant was injected into the flue gas at a rate equivalent to 1.1 gr/acf dust loading. Mississippi Ca(OH)_2 was used as the sorbent and was injected into the duct after the humidifier. Therefore, no sorbent wetting was expected by water droplet/sorbent particulate collision. The average SO_2 removal observed after 6 runs on the pilot plant was about 27 percent at a calcium-to-sulfur ratio of 2.0. Therefore, the lime utilization was about 13.5 percent. The results are presented in Figure 5-64. In addition, 2 runs were conducted to evaluate the reactivity of Meredosia fly ash toward SO_2 .

Figure 5-62.

Effect of Ca(OH)_2 loading on sorbent prepared from high-calcium fly ash with $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ (constant Harrington fly ash/ $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ weight ratio of 3:0:6 and slurry time of 8 h except points at 0.33 loading, which are 9 h samples).

Figure 5-63. Effect of Ca(OH)_2 loading on solution composition for slurry of high-calcium fly ash with $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ present.

Figure 5-64. Dry-sorbent injection upstream of the humidifier (Meredosia fly ash/ Ca(OH)_2 mixture).

TABLE 5-7. PILOT PLANT OPERATING CONDITIONS

Operation	Conditions
Flue gas temperature	149 °C
Flue gas SO ₂ concentration	2,000 ppm
Simulated fly ash loading	1.1 gr/acf at 149 °C
Duct residence time	~ 2 s
Calcium-to-sulfur ratio	2.0
Approach to saturation	11 °C
Recycle ratio	2.0

As shown in Figure 5-64 by the data point represented by the triangle, almost no SO₂ removal resulted from injecting only Meredosia fly ash as the sorbent. Meredosia fly ash apparently is quite inert toward SO₂. This conclusion is further supported by the lack of difference in SO₂ removal between runs with and without fly ash.

Following establishment of the baseline once-through operation, the effect was evaluated of recycle on DSI downstream of the humidification zone. The product collected from the previous baseline (once-through) tests was used as the recycle material. The recycle material was mixed with fresh Ca(OH)₂ and fly ash before duct injection. The mixing ratio was controlled so that the fresh calcium-to-sulfur ratio would be 2.0 at a recycle ratio of 2.0. As shown in Figure 5-65, approximately 42 percent SO₂ removal efficiency was accomplished during the first recycle test. However, the SO₂ removal declined to 28 percent during the second and third recycle tests, which used as recycle material the product from the first and second recycle tests. Compared with the baseline SO₂ removal (27 percent), the pilot-plant data show that very little improvement in SO₂ removal was accomplished by recycle operation during the third recycle test, which should provide a fairly close simulation of the long-term, steady-state recycle operation.

To further investigate the effect of recycle operation, pilot-plant tests were conducted with recycle material only (i.e., no fresh Ca(OH)₂). As shown in Figure 5-65 by crosses, the recycle material used by the first recycle test yielded approximately 15-percent SO₂ removal. However, the recycle

Figure 5-65. SO₂ removal for recycle operation during the DSI downstream of the humidification zone.

materials used by the second and third recycle tests yielded only 2-percent SO_2 removal. The pilot-plant data indicate that the recycle material rapidly lost its reactivity toward SO_2 after the first pass. The absorbed SO_2 is suspected to form $\text{CaSO}_3 \cdot 0.5\text{H}_2\text{O}$ crystals on the surface of $\text{Ca}(\text{OH})_2$, which tends to block the active surface and plug the pores. As a result, the recycled $\text{Ca}(\text{OH})_2$, although less than 30 percent utilized, became almost nonreactive toward SO_2 after the second pass.

5.3.2 Dry-Sorbent Injection Upstream of Humidification

In the next series of pilot plant runs, the effect was evaluated of the recycle operation on DSI upstream of the humidifier. The major operating parameters were the same as for DSI downstream of the humidifier (Table 5-7). Fly ash from the Meredosia Power Plant was injected into the flue gas at a rate equivalent to 1.1 gr/acf dust loading. The sorbent, Mississippi $\text{Ca}(\text{OH})_2$, was injected into the duct upstream of (before) the humidifier. Therefore, significant wetting was expected by water droplet/sorbent particulate collision. Initially, considerable difficulties were encountered for once-through DSI upstream of humidification, including wet deposits on the walls, pluggage of sorbent dispersion section, and sorbent build-up around the spraying section. After significant hardware modifications and several trial-and-error tests, stable operation of pilot testing was sustainable for up to 4 h at an approach to saturation temperature of 14 to 17 °C. Figure 5-66 presents the baseline performance of DSI upstream of the humidifier at a 2.0 calcium-to-sulfur ratio. As indicated, higher SO_2 removal was accomplished when the sorbent was injected upstream rather than downstream.

Following the once-through DSI tests upstream of the humidifier, the effectiveness of recycle was evaluated with sorbent and recycle material injected upstream of the humidifier. The recycle material was generated from the baseline (once-through) test conducted previously. Again, considerable operating problems included wet deposits on the walls, pluggage of sorbent dispersion section, and sorbent build-up around the spraying section. The high dust loading because of the recycle operation seemed to aggravate the problems when compared with baseline tests. After several trial-and-error tests and some modifications of operating procedures, stable operation was sustainable for up to 33 h at an approach to saturation of 14 to 17 °C. Figure 5-67 compares the SO_2 removal

Figure 5-66. Comparison of DSI upstream and downstream of humidifier.

Figure 5-67. Results for DSI recycle tests upstream of humidifier.

from recycle tests with that from baseline tests, indicating that significant SO₂ removal enhancement was achieved by DSI recycle upstream of the humidifier.

5.4 GRINDING OF DRY-SORBENT INJECTION MATERIAL

5.4.1 Grinding of Spent Ca(OH)₂

As discussed, DSI recycle downstream of the humidifier was not significantly beneficial. The majority of the Ca(OH)₂ recycled remains unused after the particulate collector. The absorbed SO₂ likely forms CaSO₃·0.5H₂O crystals on the surface of Ca(OH)₂, reducing the active surface area and average pore size of the sorbent. Therefore, even though Ca(OH)₂ is only partially used, it may have lost its reactivity. As a result, the reinjection of the partially used Ca(OH)₂ does not result in significant additional SO₂ removal. By grinding partially reacted Ca(OH)₂, the active surface area may possibly be restored, resulting in additional SO₂ removal.

Sample of spent Ca(OH)₂ was generated by injecting Mississippi Ca(OH)₂ downstream of the humidification zone in the 50-cfm pilot plant. Once-through injection resulted in 26 percent SO₂ removal in the duct (2 s residence time) at Ca/S = 2, 11 °C approach to saturation, and 2,000 ppm SO₂ concentration. The pilot-plant run was made with the cyclone in line between the duct and the fabric filter. Solids intended for dry grinding were taken from the baghouse catch and dry ground in a bench-scale attrition grinder for 15 min. Following grinding, the increase in specific surface area and porosity was measured. Table 5-8 presents structural properties of "as-received" and dry-ground, pilot-plant solids.

TABLE 5-8. STRUCTURAL PROPERTIES OF PILOT-PLANT SOLIDS

Solids	Specific Surface Area [m ² /g]	Pore Volume [cm ³ /g]
"As-received" ^a	9.1	0.051
Ground for 15 min ^b	13.9	0.065

^afrom the pilot plant

^bin the bench-scale attrition grinder

Reactivity of ground solids with SO₂ was tested in the STDR operated at 60 percent RH (11 °C approach to saturation) and with 2,000 ppm SO₂. The reactivity of "as-received" baghouse catch was

measured first, followed by solids ground for 15 min. Results are presented in Figure 5-68. Reactivity with SO_2 was significantly enhanced by dry grinding baghouse catch.

5.4.2 Grinding of Spent $\text{Ca}(\text{OH})_2$ /Fly Ash

Following DSI, solids from the baghouse catch would contain inherent fly ash and spent $\text{Ca}(\text{OH})_2$. To simulate the effect of fly ash on reactivity of ground spent $\text{Ca}(\text{OH})_2$, baghouse catch solids were dry mixed with Beverly fly ash prior to grinding. (Fly ash was from Beverly DITF, $0.7\text{m}^2/\text{g}$, $0.001\text{ cm}^3/\text{g}$.)

Reactivity of ground, spent $\text{Ca}(\text{OH})_2$ /fly ash solids (structural properties in Table 5-9) with SO_2 was tested in the STDR operated at 60 percent RH (11 °C approach to saturation) and with 2,000 ppm SO_2 . "As-received" baghouse catch reactivity was measured first, followed by reactivity of dry mixture of baghouse catch/Beverly fly ash at the weight ratio of 3.5:1, which was intended to simulate the recycle material from the DSI process. No significant reactivity difference was detected between baghouse catch alone and dry mixture of baghouse catch/Beverly fly ash, as evident in Figure 5-69. Finally, the reactivity of baghouse catch/Beverly fly ash solids dry-ground in the bench-scale attritor was measured for 15 min. Under conditions of the STDR, 15-min dry ground solids were significantly more reactive with SO_2 than unground solids. Reactivity difference was more pronounced at larger residence times in the STDR (3 and 5 s), as evident in Figure 5-69.

TABLE 5-9. STRUCTURAL PROPERTIES OF DRY GROUND BAGHOUSE CATCH/BEVERLY FLY ASH SOLIDS

Solids Type	Surface Area [m^2/g]	Pore Volume [cm^3/g]
Baghouse Catch	9.1	0.051
Baghouse Catch/Beverly fly ash dry-mixed	7.1	0.037
Baghouse Catch/Beverly fly ash dry-mixed and dry-ground for 15 min	14.8	0.064

Figure 5-68. Reactivation of spent Mississippi Ca(OH)_2 baghouse catch by dry grinding baghouse catch/Beverly fly ash (mixed at the weight ratio of 3:5:1).

Figure 5-69. Reactivation of spent Ca(OH)_2 /Beverly fly ash solids by dry-grinding in a bench-scale attritor (reactor: 60 percent RH, 2,000 ppm SO_2).

SECTION 6

DISCUSSION

The results of mass transfer testing and of novel techniques investigation were presented in Sections 4 and 5, respectively. In presentation of these results, values of $\text{Ca}(\text{OH})_2$ conversion with SO_2 were used for bench-scale data, and values of SO_2 removal were used for small pilot-scale data. Conversions measured for $\text{Ca}(\text{OH})_2$ in the bench-scale reactors under conditions typical of dry sorbent injection (DSI) (2,000 ppm SO_2 , 11 °C approach to saturation, and below 5 s residence time) were typically below 2 percent. Twenty-seven percent SO_2 removal was measured in the small pilot-plant (50 cfm) duct at a Ca/S stoichiometry of 2, and at 2,000 ppm SO_2 , 11°C approach to saturation, 2 s duct residence time, and DSI downstream of the humidification point. Forty-two percent SO_2 removal was measured for DSI upstream of the humidification point under the same conditions.

Recently presented results from the "Fundamental Investigation of Duct and ESP Phenomena" on a 1.7 MW_g pilot installation revealed 32 percent SO_2 removal at Ca/S stoichiometry of 2, 17 °C approach to saturation, and DSI downstream of humidification point (Brown et al., 1991). Forty percent SO_2 removal was measured in the same plant for DSI upstream of humidification under the same conditions. Scale up tests in 12 MW_g installation (Felix et al., 1991) demonstrated 27 percent removal for DSI downstream of humidification at Ca/S stoichiometry of 3.15 and 14 °C approach to saturation. DSI upstream of humidification (coplanar injection) resulted in 41 percent SO_2 removal at Ca/S stoichiometry of 1.97 and 14 °C approach to saturation.

Evaluation of the three sources of pilot-plant data (small pilot-scale, 1.7, and 12 MW_g) indicates great sensitivity of $\text{Ca}(\text{OH})_2$ conversion to the humidification mode. DSI upstream of the humidification

point creates an opportunity for $\text{Ca}(\text{OH})_2$ particles to collide with water droplets. These collisions would result with the coverage of $\text{Ca}(\text{OH})_2$ particles with moisture. The results from the aforementioned 3 pilot facilities revealed the same trend of higher $\text{Ca}(\text{OH})_2$ conversion for DSI upstream than DSI downstream of the humidification. The measured conversions were 13.5 (at $\Delta t_g = 11^\circ\text{C}$), 16 (at $\Delta t_g = 17^\circ\text{C}$), and 8.5 percent (at 14°C) in small pilot scale, 1.7, and 12 MW_g installations, respectively, and each operated in DSI downstream mode. For these 3 installations operating in DSI upstream mode, $\text{Ca}(\text{OH})_2$ conversion was 21 (at $\Delta t_g = 11^\circ\text{C}$), 20 (at $\Delta t_g = 17^\circ\text{C}$), and 21 percent (at $\Delta t_g = 14^\circ\text{C}$), respectively. The correlating DSI data from the 3 installations for DSI upstream mode confirms the critical role of incorporating water droplet collision scavenging by $\text{Ca}(\text{OH})_2$ particles into the experimental regime. Discrepancies observed for the results from the same 3 plants operating in downstream mode of DSI may reflect varying intensity of residual droplet scavenging at the point of dry $\text{Ca}(\text{OH})_2$ injection. Droplet scavenging is a function of droplet evaporation rate, which, in turn, can depend on the atomization quality (inherent to the type of nozzles used) and turbulence in the duct (plant specific).

Bench-scale experiments contacting $\text{Ca}(\text{OH})_2$ with humidified gas were performed in the reactors in which gas was humidified by steam injection. Literature review, performed as a part of DOE Duct Injection Program (Gooch et al., 1989), reveals that under similar operating conditions, SO_2 removal was approximately 3 times greater when humidification was performed via spray injection rather than steam injection. Therefore, it is reasonable to assume that the apparent discrepancy between bench-scale data and proof-of-concept data results from using steam humidification on the bench scale (no droplet scavenging), which would tend to lower the SO_2 removal. Additionally, any incomplete evaporation of droplets during pilot-plant tests and resulting scavenging during DSI downstream mode would tend to increase the SO_2 removal, and thus widening the apparent discrepancy between bench-scale and proof-of-concept data. Bench-scale results indicated the trend of increasing $\text{Ca}(\text{OH})_2$ conversion with an increasing amount of moisture on the particle surface and predicted the effects of RH and SO_2 concentration in agreement with trends observed during pilot-scale

testing. Bench-scale results demonstrated that humid N₂ conditioning of the sample before contact with SO₂ resulted in a higher conversion than that following dry N₂ conditioning (Figures 4-12 and 4-13). Additionally, conversion was increasing with increasing RH of pretreatment N₂ (Figure 4-30) and increasing pretreatment time for given RH of pretreatment gas (Figure 4-29). Therefore, it is reasonable to assume that bench-scale data are representative of trends, such as determination of a relative reactivity of sorbents and effects such as relative humidity, or SO₂ concentration. However, the agreement between absolute reactivity data from bench- and pilot-scale tests may be biased by the pilot-plant process variables (atomization, evaporation, etc.) and bench-scale experimental limitations (no droplet scavenging, quality of sorbent dispersion).

SECTION 7

CONCLUSIONS

Based on fundamental mass transfer investigations in the STDR, gas phase mass transfer and chemical reaction steps could be excluded as rate limiting. This leaves solid phase diffusion as a rate limiting step in the reaction of $\text{Ca}(\text{OH})_2$ with SO_2 under conditions of DSI. Based on lack of sensitivity of $\text{Ca}(\text{OH})_2$ conversion to SO_2 concentration in the gas phase, on significant effect of the approach to saturation, and on initial moisture content, the diffusing species could be a compound composed of SO_2 and H_2O . The concentration of the compound was controlled by the available moisture content on the surface of the sorbent.

Based on global reactivity testing in the LTDR, the conversion of a given calcium-based sorbent was most strongly affected by the flue gas RH. At moderate to high RHs, conversion was a strongly increasing function of sulfation time. The effect of higher flue gas SO_2 concentration was limited. Increased SO_2 concentration only slightly affected conversion of fly ash/ $\text{Ca}(\text{OH})_2$ sorbents at relatively short residence times and with moderate to high RH. Given identical reaction conditions, conversion of the Clinch River fly ash/ $\text{Ca}(\text{OH})_2$ sorbent attained a higher value than did the Mississippi $\text{Ca}(\text{OH})_2$. Differentiation between the sorbents was probably due largely to their BET surface areas. Conversion of the fly ash/ $\text{Ca}(\text{OH})_2$ sorbent could approach 100 percent given sufficient RH and residence time.

The carbonation of commercial Mississippi $\text{Ca}(\text{OH})_2$ was enhanced by the presence of moisture in the flue gas (60 percent RH). The percent carbonation of commercial Mississippi $\text{Ca}(\text{OH})_2$ was increasing with increasing CO_2 concentration in 0-10 vol percent range. Increasing the CO_2 concentration above 10 vol percent did not affect the measured percent carbonation. Increased initial

surface area of $\text{Ca}(\text{OH})_2$ could increase the amount of CO_2 combined with the sorbent. For any surface area sorbent tested, the percent carbonation was higher for humid than dry N_2/CO_2 gas. No significant effect of SO_2 presence on the extent of carbonation of $\text{Ca}(\text{OH})_2$ was found. Moderate decrease of reactivity of $\text{Ca}(\text{OH})_2$ with SO_2 took place as a result of high CO_2 concentration (40 vol percent). For practical range to concentration (0-10 vol percent) the effect of CO_2 on reactivity of $\text{Ca}(\text{OH})_2$ with SO_2 was insignificant.

Initial equilibrium moisture content of sorbent (as measured by TGA) was a function of conditioning scheme. For dry, warm nitrogen conditioning, the moisture content was increasing with increasing surface area of sorbent. Following the conditioning methods used, the initial moisture content for $\text{Ca}(\text{OH})_2$ sorbents was below 1 percent. There was more initial moisture on the fly ash/ $\text{Ca}(\text{OH})_2$ sorbent than on any Mississippi $\text{Ca}(\text{OH})_2$ sorbent. Reactivity of fly ash/ $\text{Ca}(\text{OH})_2$ was approximately twice that of $\text{Ca}(\text{OH})_2$. Conversion in the STDR was increasing with the initial amount of moisture on the sorbent (as detected by TGA) conditioned with dry, warm nitrogen.

At 2,000 ppm SO_2 and 60 percent RH (11 °C approach to saturation), the presence of up to 30 percent initial free moisture significantly increased sorbent reactivity with SO_2 , compared with sorbent reactivity with equilibrium amount of moisture. For any initial free moisture content tested, fly ash/ $\text{Ca}(\text{OH})_2$ sorbent was more reactive than a physical mixture of fly ash and $\text{Ca}(\text{OH})_2$. Maximum conversion for 5 s residence time in the STDR and 60 percent RH (11 °C approach to saturation) was measured for sorbents with 30 to 50 weight percent initial free moisture. The conversion decreased when the initial free moisture increased beyond 30 to 50 weight percent. The initial free moisture content and corresponding level of maximum sorbent conversion with SO_2 varied with the surface area of the sorbent. Conversion of solids with initial free moisture was not affected by the approach to saturation in the STDR for short residence times of 0.5 and 1 s. With a longer residence time of 5 s, conversion in the STDR increased with decreasing approach to saturation. For sorbents with comparable surface areas, fly ash source (2 fly ashes tested) did not have a significant effect on reactivity of solids with initial free moisture.

Reaction could be adequately modeled between fly ash/ $\text{Ca}(\text{OH})_2$ sorbent with initial free moisture and low-concentration SO_2 and $\text{Ca}(\text{OH})_2$ sorbents with initial free moisture and high-concentration SO_2 , assuming that the wet reaction was gas-phase-controlled and that the products of the wet reaction affect the progress of the equilibrium-moisture reaction. The conversion of the $\text{Ca}(\text{OH})_2$ and fly ash/ $\text{Ca}(\text{OH})_2$ sorbents as a result of wet reactions affected the surface properties of the sorbents and the extent of equilibrium-moisture conversion that occurred upon evaporation of the free moisture.

A procedure was developed to measure the agglomeration of damp fly ash/ $\text{Ca}(\text{OH})_2$ sorbents. Agglomeration of damp fly ash/ $\text{Ca}(\text{OH})_2$ sorbents was a function of sorbent pore volume. Greater specific pore volume allows a sorbent to carry more water before forming the same size agglomerates as a sorbent with less pore volume (critical moisture, which increases with pore volume). The correlation of critical moisture with pore volume suggests that majority of the water added to a sorbent exists in the pore space, with only a minor fraction existing outside and causing agglomeration. Critical moisture also increases with specific surface area. The correlation between critical moisture and surface area is independent of fly ash type (low- and high-calcium ash), fly ash grinding, and recycle materials. The slurry time required for $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ to enhance critical moisture and surface area dependent on fly ash properties, which is probably related to the rate of aluminum dissolution from the ash. The effect of $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ was evident after 8 h when ground Clinch River fly ash was slurried. Sorbent prepared from high-calcium fly ash benefitted from $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ after 3 h.

Pilot plant data indicate that the recycle material lost its reactivity toward SO_2 after the first pass. Very little improvement in SO_2 removal was accomplished by DSI recycle downstream of the humidifier. Significant SO_2 removal enhancement was achieved for DSI recycle upstream of the humidifier.

Dry grinding of DSI recycle solids could be used as a means of reactivating spent DSI solids. Under conditions of the STDR, dry ground recycle DSI solids were significantly more reactive with SO_2 than unground solids.

SECTION 8

REFERENCES

Beaudoin, S.P., "The Effect of Moisture on the Reactivity of $\text{Ca}(\text{OH})_2$ -Based Sorbents for Flue Gas Desulfurization," M.S. Thesis, The University of Texas at Austin, August, 1990.

Brown, C.A., M. Maibodi, and L.M. McGuire, "1.7 MW Pilot Results for the Duct Injection FGD Process Using Hydrated Lime Upstream of an ESP", presented at the 1991 SO_2 Symposium, Washington, D.C., December 1991.

Carr, R.L., "Evaluating Flow Properties of Solids," Chemical Engineering, 72, 163-168, January 18, 1965.

Carr, R.L., "Particle Behaviour Storage and Flow," British Chemical Engineering, 15, 1541-1549, December 1970.

Chang, J.C.S. and C.B. Sedman, "Scale-Up Testing of the ADVACATE Damp Solids Injection Process," Proceedings: First Combined Flue Gas Desulfurization and Dry SO_2 Control Symposium, EPRI GS-6307, 2, 8-123 April 1989.

Dutta, A. and L.V. Dullea, "A Comparative Evaluation of Negatively and Positively Charged Submicron Particles as Flow Conditioners for a Cohesive Powder," presented at the AIChE 1989 Annual Meeting, San Francisco, CA, November 1989.

Felix, L.G., J.P. Gooch, R.L. Merritt, M.G. Klett, J.E. Hunt, and A.G. Demian, "Scaleup Tests and Supporting Research for the Development of Duct Injection Technology", presented at the 1991 SO_2 Symposium, Washington, D.C., December 1991.

Gooch, J.P., E.B. Dismukes, R.S. Dahlin, M.G. Faulkner, M.G. Klett, T.L. Buchanan, and J.E. Hunt, "Scaleup Tests and Supporting Research for the Development of Duct Injection Technology", Topical Report No.1 Literature Review, May 1989.

Hall, B.W., C. Singer, W. Jozewicz, C.B. Sedman, and M.A. Maxwell, "Current Status of ADVACATE Process for Flue Gas Desulfurization," presented at the 1991 Annual Meeting of the Air and Waste Management Association, Vancouver, B.C., June 1991.

Jenike, A.W., P.J. Elsey, and R.H. Woolley, "Flow Properties of Bulk Solids," A.S.T.M. Proceedings, 60, 1168-1181, 1960.

Jozewicz, W. and G.T. Rochelle, "Fly Ash Recycle in Dry Scrubbing," Environmental Progress, 5, 218-223, November 1986.

Jozewicz, W., J.C.S. Chang, C.B. Sedman, and T.G. Brna, "Silica-Enhanced Sorbents for Dry Injection Removal of SO_2 from Flue Gas," JAPCA, 38, 1027-1034, August 1988a.

Jozewicz, W., J.C.S. Chang, C.B. Sedman, and T.G. Brna, "Characterization of Advanced Sorbents for Dry SO₂ Control," *Reactivity of Solids*, 6, 243-262, December 1988b.

Jozewicz, W., C. Jorgensen, J.C.S. Chang, C.B. Sedman, and T.G. Brna, "Development and Pilot Plant Evaluation of Silica-Enhanced Lime Sorbents for Dry Flue Gas Desulfurization," *JAPCA*, 38, 796-805, June 1988b.

Jozewicz, W., and J.C.S. Chang, "Evaluation of FGD Dry Injection Sorbents and Additives, Volume 1: Development of High Reactivity Sorbents," EPA-600/7-89-006b, Research Triangle Park, NC, May 1989.

Klingspor, J., A. Stromberg, H.T. Karlsson, and I. Bjerle, "Similarities Between Lime and Limestone in Wet-Dry Scrubbing," *Chem. Eng. Prog.*, 18, 239-247, 1984.

NAPAP, "Annual Report, 1989 and Findings Update," The National Acid Precipitation Assessment Program, Washington, DC June 1990.

Newitt, D.M. and J.M. Conway-Jones, "A Contribution to the Theory and Practice of Granulation," *Trans. Instn. Chem. Engrs.*, 36, 422-440, December 1958.

Petersen, T., J. Peterson, H.T. Karlsson, and I. Bjerle, "Physical and Chemical Activation of Fly Ash to Produce Reagent for Dry FGD Processes," *Proceedings: First Combined Flue Gas Desulfurization and Dry SO₂ Control Symposium*, EPRI GS-6307, 2, 7-165, April 1989.

Peterson, J.R., "Aqueous Reaction of Fly Ash and Ca(OH)₂ to Produce Calcium Silicate Absorbent for Flue Gas Desulfurization," M.S. Thesis, The University of Texas at Austin, August, 1987.

Peterson, J.R. and G.T. Rochelle, "Aqueous Reaction of Fly Ash and Ca(OH)₂ to Produce Calcium Silicate Absorbent for Flue Gas Desulfurization," *Environ. Sci. Technol.*, 22, 1299-1304, November 1988.

Peterson, J.R., "Hydrothermal Reaction of Lime with Fly Ash to Produce Calcium Silicates for Dry Flue Gas Desulfurization," Ph.D. Dissertation, The University of Texas at Austin, December, 1990.

Rochelle, G.T., W.G. White, W. Jozewicz, and J.C.S. Chang, "Reaction of Hydrated Lime with SO₂ in Humidified Flue Gas," *Proceedings: 1990 SO₂ Control Symposium*, EPRI GS-6963, 2, 7A-119, September 1990.

Ruiz-Alsop, R.N., and G.T. Rochelle, "Effect of Deliquescent Salt Additives on the Reaction of Sulfur Dioxide with Dry Ca(OH)₂," *ACS Symposium Series*, 319, 202-222, 1986.

Rumpf, H., "Particle Adhesion," *Agglomeration 77*; *Proceedings of the 2nd International Symposium on Agglomeration*, K.V.S. Sastry, ed., American Institute of Mining, Metallurgical, and Petroleum Engineers, Inc., New York, NY, 1977.

Stroud, D. E., "Agglomeration of Damp Calcium Silicate Sorbents for Flue Gas Desulfurization," M.S. Thesis, The University of Texas at Austin, August 1991.

Tseng, P.C. and G.T. Rochelle, "Calcium Sulfite Hemihydrate: Crystal Growth Rate and Crystal Habit," *Environmental Progress*, 5, 5-11, February 1986.

END

**DATE
FILMED**

6 / 29 / 92