NOTICE

**CERTAIN DATA
CONTAINED IN THIS
DOCUMENT MAY BE
DIFFICULT TO READ
IN MICROFICHE
PRODUCTS.**

Babcock & Wilcox

Research & Development Division

Received by
MAR 19 1992

Flow Excursion Experiments With a Savannah River Mark 22 Fuel Assembly Mockup

VOLUME 2:
TEST PROGRAM AND RESULTS

(Appendix B — Part 2)

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DOES NOT CONTAIN
UNCLASSIFIED CONTROLLED
NUCLEAR INFORMATION

Reviewing
Official: *C. J. Banick*
C. J. Banick, Area Chief Officer
Date: *1/23/91*

MASTER

RDD:90:4427-13-01-01:01

FEBRUARY 1990

Babcock & Wilcox

Research and Development Division

a McDermott company

1562 Beeson Street
Alliance, OH 44601
(216) 821-9110

August 9, 1989

WSRC-OS--90-66-Vol.2-App.B-Pt.2

Charles A. Nash
Westinghouse Savannah River Company
Savannah River Site
Building 786-5A
Aiken, SC 29808-0001

DE92 009868

Subject: Transmittal of the Complete Quick Plot Set for Test 867_13,
90% OSV Power Best Estimate LOCA at 80 F, SRP-1,038

Dear Charles:

Attached for your information is the subject plot set containing data plots for the complete test spanning from about -330 to 70 seconds, time scale enhancements at -1 to 5 seconds, and a few custom plots. Unlike the previous tests, the power supply safety trips were returned to their "non-recovery" values with a 30% post-LOCA nominal flow reduction trip and 400 F metal temperature trips on the HP oscillograph and METRAScope. A couple of observations are noted comparing this test to its predecessor, Test 867_08.

I have reviewed the data and have the following test anomalies and data observations to document.

Instrument or Control Anomalies

There are no control anomalies to report. The power was tripped as required on low total flow to the assembly at about 0.9 seconds, slightly earlier than the 1 second trip in Test 867_08.

The safety trip metal temperature, OFMT12, was moved from the HP oscillograph to the METRAScope due to unacceptable amplifier noise prior to test performance. As the test was performed late at night and Charles Nash was attending a technical conference, no WSRC contact and approval was received prior to the switch and test performance.

There is one instrument anomaly to report, consistent with prior tests. Thermocouple IFMT07 was once again erratic during the test and will be set to NOREAD before final data conversion. WSRC was previously alerted that this thermocouple is beyond repair and could be removed completely from the data acquisition system.

cc: (w/o attachment)

D. P. Birmingham, B&W
J. E. Blake, B&W
J. A. Curtis, B&W
R. B. Pagett, WSRC
R. M. Privette, B&W

0846

Test Response/Performance

The test setup to initial pre-LOCA steady-state as well as the LOCA transient proceeded without any significant events that might otherwise have jeopardized fuel assembly integrity during the test. Channel 3 pressure oscillations were monitored with C3DP01 on the HP oscillograph, consistent with the previous test. Significant oscillations were observed in the measured channel pressure drop between about 4.5 MW and the starting power but dissipated during the 2 minute power hold period prior to LOCA initiation.

As in Test 867 08, the power tripped to zero early in the controlled power decay transient (0.9 and 1.0 seconds, respectively, for Tests 867 13 and 867 08). Void generated in channel 3 (maximum of about 70%) was followed by lesser void production in channel 4 (maximum of about 5%) as measured by the optical void fraction sensors. Channel 4 voiding in Test 867 08 was greater (maximum of about 60% void), reflecting some subtle differences between the two tests even though power was nominally the same and inlet flow temperatures matched within 0.1 F. Both inner and outer heater tube metal temperatures remained below the 400 F high metal trip value. Test termination activities progressed without incident.

The peak-to-peak fluctuation of 80 kW during steady-state power at about 5.34 MW was unlike that of Test 867 08 and was more consistent with prior tests. The approximate 300 kW peak-to-peak power oscillation in Test 867 08 was not repeated in the subject test, thereby, indicating an anomaly in Test 867 08.

The attached plot of heater tube resistance as a function of current matches early characterization test data and confirms the absence of heater tube electrical damage following Test 867 12 in which the inner heater tube metal temperatures exceeded 700 F. The steady-state pressure drop data acquired prior to performing this test also supports the absence of any measurable internal damage to the fuel assembly.

Sincerely,

BABCOCK & WILCOX
Research and Development Division

Greg / L

Greg C. Rush
Group Supervisor
Nuclear Steam Systems & Components

L
Attachment

0847

LOSS OF COOLANT FROM 90% OSV (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A
 ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (e 80 F) - BEST ESTIMATE SCRAM
TEST: 867_13.E3A ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A
 ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A ZERO-TIME: 07-AUG-1989 22:56:06.83

E N E R G Y B A L A N C E x

THOUSANDS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a
 ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a
 ZERO-TIME: 07-AUG-1989 22:56:06.83

THOUSANDS OF COOLANT FROM 90% OSV (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a
 ZERO-TIME: 07-AUG-1989 22:56:06.83

Scram Interval seconds

LOSS OF COOLANT FROM 90% OSV (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (e 80 F) - BEST ESTIMATE SCRAM
TEST: 867_13.E3A
ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (0 80 F) - BEST ESTIMATE SCRAM
TEST: 867_13.E3A
ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A ZERO-TIME: 07-AUG-1989 22:56:06.83

0802

LOSS OF COOLANT FROM 90% OSV (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A
 ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (e 80 F) - BEST ESTIMATE SCRAM
TEST: 867_13.E3A ZERO-TIME: 07-AUG-1989 22:56:06.83

0808

LOSS OF COOLANT FROM 90x OSV (0 80 F) - BEST ESTIMATE SCRAM
TEST: 867_13.E3A ZERO-TIME: 07-AUG-1989 22:56:06.83

0802

LOSS OF COOLANT FROM 90% OSV (e 80 F) - BEST ESTIMATE SCRAM
TEST: 867_13.E3A
ZERO-TIME: 07-AUG-1989 22:56:06.83

0808

LOSS OF COOLANT FROM 90% OSV (0 80 F) - BEST ESTIMATE SCRAM
TEST: 867_13.E3A
ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a
 ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A
 ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 00X OSV (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a
 ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A
 ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a
 ZERO-TIME: 07-AUG-1989 22:56:06.83

T E M P E R A T U R E F

LOSS OF COOLANT FROM 90% OSV (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A
 ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90x OSV (e 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a
 ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a
 ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A
 ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a
 ZERO-TIME: 07-AUG-1989 22:56:06.83

THOUSANDS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a
 ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a
 ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A
 ZERO-TIME: 07-AUG-1989 22:56:06.83

THOUSANDS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
TEST: 867_13.E3A ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90x OSV (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a
 ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A ZERO-TIME: 07-AUG-1989 22:56:06.83

P R E S S U R E P S I A

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (e 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A ZERO-TIME: 07-AUG-1989 22:56:06.83

D I F F P R E S S U R E P S I D

LOSS OF COOLANT FROM 90% OSV (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a
 ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (e 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90x OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a ZERO-TIME: 07-AUG-1989 22:56:06.83

867_13.E3A
AUGUST 7, 1989

867_13.E3A
AUGUST 7, 1989

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.E3A
 ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a
 ZERO-TIME: 07-AUG-1989 22:56:06.83

LOSS OF COOLANT FROM 90% OSV (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_13.e3a
 ZERO-TIME: 07-AUG-1989 22:56:06.83

Babcock & Wilcox

a McDermott company

Research and Development Division

1562 Beeson Street
Alliance, OH 44601
(216) 821-9110

September 15, 1989

Charles A. Nash
Westinghouse Savannah River Company
Savannah River Site
Building 786-5A
Aiken, SC 29808-0001

Subject: Transmittal of the Complete Quick Plot Set for Test 867_19,
5.13 MW Best Estimate LOCA at 80 F, SRP-1,099

Dear Charles:

Attached for your information is the subject plot set containing data plots for the complete test spanning from about -360 to 80 seconds, time scale enhancements at -1 to 5 seconds and a few custom plots. The time scale is set up so that 0 seconds corresponds to the start of the LOCA transient.

The power supply safety temperature trips for the METRAScope and HP oscillograph were set at 400 F, consistent with previous tests. Flow trip setpoints (total flow from the venturi (IPDP04) and channel pitot measurements) were configured for a power trip at an 80% reduction in flow from the post-LOCA expected flow value.

I have reviewed the data and have the following test anomalies and data observations to document.

Instrument or Control Anomalies

There are no instrument anomalies to report.

There are no control anomalies to report.

Inlet temperature, measured by IPRT01, at the start of the LOCA was 81.3 F. The fuel assembly backpressure, measured by RTAP01, was within the 28.5 ± 1 psia control band prior to the LOCA and was centered about 21 psia during the LOCA transient. Inlet plenum pressure control was centered about 37 psia during the LOCA. The pre-LOCA flow rate was within the 345 +17/-0 gpm range.

ct: (w/o attachment)

D. P. Birmingham, B&W
J. E. Blake, B&W
J. A. Curtis, B&W
R. B. Pagett, WSRC
G. C. Rush, B&W/GC^R

0533

Test Response/Performance

The LOCA transient in Test 867_19 proceeded through the entire 60 second Best Estimate scram without tripping the power supply. The overall flow rate measured by the venturis (IPVN20) dropped to about 37,000 lbm/hr (74 gpm) during the first second of the LOCA. This represented a 70% reduction in the flow rate from the post-LOCA flow value and was approaching the low-flow power trip point of 80% flow reduction from Post-LOCA flow rate. The pitot tube measured dynamic pressures showed small excursions in all but channel 3 where the differential pressure climbed to 6 psi before falling to the post-LOCA value of 1.8 psi.

The test setup to initial pre-LOCA steady-state, as well as the LOCA transient, went smoothly without any events which would have jeopardized the integrity of the fuel assembly. The LOCA transient proceeded from 5.13 MW by the Best Estimate Scram power decay until the end of the 60 second event. At the end of 60 seconds, the test was terminated and the power was reduced to zero. Fluid and heater tube metal temperatures increased to as high as 265 F and 330 F, respectively (C3TC03 and IFMT14) during the transient.

The test was successfully terminated and the fuel assembly secured with no detectable damage.

Sincerely,

BABCOCK & WILCOX
Research and Development Division

Ref

Rob M. Privette
Nuclear Steam Systems & Components

L
Attachment

0004

LOSS OF COOLANT FROM 5.13 MW (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 15:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

THOUSANDS OF COOLANT FROM 5.13 MW (± 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19_E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (280 F) - BEST ESTIMATE SCRAM
TEST: 867_19.E3A
ZERO-TIME: 13-SEP-1989 16:53:40.14

THOUSANDS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A
 ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (Q 80 F) - BEST ESTIMATE SCRAM
TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (Q 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (2080 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

0047

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A
 ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

0040

LOSS OF COOLANT FROM 5.13 MW (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A
 ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
TEST: 867_19.E3A
ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.e3a ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.e3a ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (280 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.e3a ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.e3a ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.e3a ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.e3a ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (e 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.e3a ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.e3a ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (Q 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (280 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (Q 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.e3a ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (e 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.e3a ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (e 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.e3a ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (± 80 F) - BEST ESTIMATE SCRAM
TEST: 867_19.e3a ZERO-TIME: 13-SEP-1989 16:53:48.14

LOSS OF COOLANT FROM 5.13 MW (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A
 ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.e3a ZERO-TIME: 13-SEP-1989 16:53:40.14

Time (seconds)

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.e3a
 ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (e 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (± 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A
 ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

THOUSANDS OF COOLANT FROM 5.13 MW (0.80 f) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (280 F) - BEST ESTIMATE SCRAM
TEST: 867_19.E3A
ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

THOUSANDS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A
 ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (280 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (Q 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.e3a ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.e3a ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.e3a ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.e3a ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (Q 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.e3a ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.e3a ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.e3a ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.e3a
 ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (e 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A
 ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (2 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.e3a ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.e3a ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.e3a ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0 80 F) - BEST ESTIMATE SCRAM
TEST: 867_19.e3a
ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.e3a ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.e3a ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (± 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.E3A ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (± 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.e3a ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0 80 F) - BEST ESTIMATE SCRAM
TEST: 867_19.E3A
ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.e3a ZERO-TIME: 13-SEP-1989 16:53:40.14

LOSS OF COOLANT FROM 5.13 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_19.e3a ZERO-TIME: 13-SEP-1989 16:53:40.14

Babcock & Wilcox

a McDermott company

Research and Development Division

1562 Beeson Street
Alliance, OH 44601
(216) 821-9110

September 18, 1989

Charles A. Nash
Westinghouse Savannah River Company
Savannah River Site
Building 786-5A
Aiken, SC 29808-0001

Subject: Transmittal of the Complete Quick Plot Set for Test 867_20,
5.13 MW Best Estimate LOCA at 80 F, SRP-1,100

Dear Charles:

Attached for your information is the subject plot set containing data plots for the complete test spanning from about -360 to 80 seconds, time scale enhancements at -1 to 5 seconds and a few custom plots. The time scale is set up so that 0 seconds corresponds to the start of the LOCA transient.

The power supply safety temperature trips for the METRAScope and HP oscillograph were set at 400 F, consistent with previous tests. Flow trip setpoints (total flow from the venturi (IPDP04) and channel pitot measurements) were configured for a power trip at an 80% reduction in flow from the post-LOCA expected flow value.

I have reviewed the data and have the following test anomalies and data observations to document.

Instrument or Control Anomalies

There are no instrument anomalies to report.

There are no control anomalies to report.

Inlet temperature, measured by IPRT01, at the start of the LOCA was 81.6 F. The fuel assembly backpressure, measured by RTAP01, was within the 28.5 ± 1 psia control band prior to the LOCA and was centered about 21 psia during the LOCA transient. Inlet plenum pressure control was centered about 37 psia during the LOCA. The pre-LOCA flow rate was within the $345 \pm 17/-0$ gpm range.

ct: (w/o attachment)

D. P. Birmingham, B&W
J. E. Blake, B&W
J. A. Curtis, B&W
R. B. Pagett, WSRC
G. C. Rush, B&W /GC

1624

Test Response/Performance

The LOCA transient in Test 867 20 proceeded through the entire 60 second Best Estimate scram without tripping the power supply. The overall flow rate measured by the venturis (IPVN20) remained above 220 gpm during the entire LOCA transient. This value represented a reduction in flow of just 12% from the Post-LOCA flow rate. The pitot tube measured dynamic pressures also experienced only minor fluctuations during the transient event.

The test setup to initial pre-LOCA steady-state, as well as the LOCA transient, went smoothly without any events which would have jeopardized the integrity of the fuel assembly. The LOCA transient proceeded from 5.13 MW by the Best Estimate Scram power decay until the end of the 60 second event. At the end of 60 seconds, the test was terminated and the power was reduced to zero. Metal temperatures remained generally below 300 F with the exception of a short duration 340 F measurement by IFMT14 approximately 1.2 seconds after the start of the LOCA. Fluid temperatures remained below 240 F during the entire LOCA transient. Void generation during the transient was measured only in channel 3 by the outlet plane fiber optic void sensor.

The test was successfully terminated and the fuel assembly secured with no detectable damage.

Sincerely,

BABCOCK & WILCOX
Research and Development Division

Rob M. Privette
Nuclear Steam Systems & Components

L
Attachment

LOSS OF COOLANT FROM 5.1 MW (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (280 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

THOUSANDS OF COOLANT FROM 5.1 MW (0.80 F) -- BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0 80 F) - BEST ESTIMATE SCRAM
TEST: 967_20_e3a
ZERO-TIME: 14-SEP-1989 15:02:50.15

THOUSANDS OF COOLANT FROM 5.1 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

FLOW DIFFERENCE

LOSS OF COOLANT FROM 5.1 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (280 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0 80 F) - BEST ESTIMATE SCRAM
TEST: 867_20.e3a
ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0.80 F) - BEST ESTIMATE SCRAM
TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0 80 F) - BEST ESTIMATE SCRAM
TEST: 867_20.e3a
ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0 80 F) - BEST ESTIMATE SCRAM
TEST: 867_20.e3a
ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0.80 F) - BEST ESTIMATE SCRAM
TEST: 867_20.e3a
ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (± 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (± 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (280 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (280 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (2 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (± 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

THOUSANDS OF COOLANT FROM 5.1 MW (± 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (e 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

THOUSANDS OF COOLANT FROM 5.1 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (± 80 F) - BEST ESTIMATE SCRAM
TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.030 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0 80 F) - BEST ESTIMATE SCRAM
TEST: 867_20.e3a
ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (± 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (280 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (280 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (280 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (Q 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (e 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (e 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (Q 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0.88 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (2 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (280 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (@ 80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0 80 F) - BEST ESTIMATE SCRAM
TEST: 867_20.e3a ZERO-TIME: 14-SEP-1989 15:02:50.15

LOSS OF COOLANT FROM 5.1 MW (0.80 F) - BEST ESTIMATE SCRAM
 TEST: 867_20.e3a
 ZERO-TIME: 14-SEP-1989 15:02:50.15

Babcock & Wilcox

a McDermott company

Research and Development Division

1562 Beeson Street
Alliance, OH 44601
(216) 821-9110

September 21, 1989

Charles A. Nash
Westinghouse Savannah River Company
Savannah River Site
Building 786-5A
Aiken, SC 29808-0001

Subject: Transmittal of the Complete Quick Plot Set for Test 867_22,
4.0 MW Best Estimate Scram LOCA at 125 F, SRP-1,106

Dear Charles:

Attached for your information is the subject plot set containing data plots for the complete test spanning from about -360 to 80 seconds, time scale enhancements at -1 to 5 seconds, and a few custom plots. The time scale is set up so that 0 seconds corresponds to the start of the LOCA transient.

The power supply safety temperature trips for the METRAScope and HP oscillograph were set at 400 F, consistent with previous tests. Flow trip setpoints (total flow from the venturi (IPDP04) and channel pitot measurements) were configured for a power trip at an 80% reduction in flow from the post-LOCA expected flow value.

I have reviewed the data and have the following test anomalies and data observations to document.

Instrument or Control Anomalies

There are no instrument anomalies to report.

There is one control anomaly to report. The inlet plenum temperature was 85.3 F at the start of the test, 0.3 F above the maximum control limit. Per your instruction, B&W will repeat this test as 867_23 at a reduced starting temperature to eliminate the flow instability observed in this test.

The fuel assembly backpressure, measured by RTAP01, was within the 28.5 ± 1 psia control band prior to the LOCA and was centered about 21 psia during the LOCA transient. Inlet plenum pressure control was centered about 37 psia during the LOCA. The pre-LOCA flow rate was within the $345 \pm 17/-0$ gpm range. The power curve matched the target decay curve very closely between the start of the LOCA and the time that power tripped off.

ct: (w/o attachment)

D. P. Birmingham, B&W
J. E. Blake, B&W
J. A. Curtis, B&W
R. B. Pagett, WSRC
G. C. Rush, B&W/GCR

1112

Test Response/Performance

The LOCA transient in Test 867 22 was halted following a flow instability at about 1.1 seconds due to a high Inner fuel metal temperature, IFMT10, above 400 F. In subchannel 3C, the metal temperatures were above saturation temperature for the entire steady-state hold period prior to the LOCA event. Metal temperatures in subchannels A, B, and D were lower, however, than those measured in C and remained below saturation prior to the transient. The overall flow rate measured by the venturis (IPVN20) dropped to approximately 81 gpm during the LOCA transient. This represented a 68% reduction from the post-LOCA flow rate. During the LOCA the pitot tube measured dynamic pressures experienced large fluctuations, especially in channels 3 and 4.

The test setup to initial pre-LOCA steady-state conditions was without any events which would have jeopardized the integrity of the fuel assembly. During the transient metal temperature excursions were large with IFMT10 peaking at 445 F. Fluid temperatures reached 275 F during the LOCA transient. Void generation was measured in both channels 3 and 4 during the transient by the outlet plane fiber optic void sensors.

The test was successfully terminated and the fuel assembly secured with no detectable damage.

Sincerely,

BABCOCK & WILCOX
Research and Development Division

Rob M. Privette
Nuclear Steam Systems & Components

L
Attachment

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a
 ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a
 ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

THOUSANDS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a
 ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22_e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

THOUSANDS OF COOLANT FLOW 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a
 ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a
 ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
TEST: 867_22.e3a
ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a
 ZERO-TIME: 19-SEP-1989 16:21:43.78

P R E S S U R E P S I A

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a
 ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a
 ZERO-TIME: 19-SEP-1989 16:21:43.78

1102

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a
 ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
TEST: 867_22.e3a
ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a
 ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a
 ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a
 ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

T E M P E R A T U R E F

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a
 ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

THOUSANDS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a
 ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

(PSRF03-2.93E-4)DI=IPVN200/PSRF03
 (PSRF03-2.93E-4)DI=WSIM200/PSRF03

Time (seconds)

1162

THOUSANDS OF COOLANT FLOW 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

P R E S S U R E P S I A

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (C125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (e125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_22.e3a ZERO-TIME: 19-SEP-1989 16:21:43.78

Babcock & Wilcox

Research and Development Division

a McDermott company

1562 Beeson Street
Alliance, OH 44601
(216) 821-9110

September 22, 1989

Charles A. Nash
Westinghouse Savannah River Company
Savannah River Site
Building 786-5A
Aiken, SC 29808-0001

Subject: Transmittal of the Complete Quick Plot Set for Test 867_23,
4.0 MW Best Estimate Scram LOCA at 125 F, SRP-1,109

Dear Charles:

Attached for your information is the subject plot set containing data plots for the complete test spanning from about -300 to 90 seconds, time scale enhancements at -1 to 5 seconds, and a few custom plots. The time scale is set up so that 0 seconds corresponds to the start of the LOCA transient.

The power supply safety temperature trips for the METRAScope and HP oscillograph were set at 400 F, consistent with previous tests. Flow trip setpoints (total flow from the venturi (IPDP04) and channel pitot measurements) were configured for a power trip at an 80% reduction in flow from the post-LOCA expected flow value.

I have reviewed the data and have the following test anomalies and data observations to document.

Instrument or Control Anomalies

There are no instrument anomalies to report.

There are no control anomalies to report. Note, however, the controlled decay power ramp lagged the target by about 0.06 seconds as shown in the attached plot.

Inlet plenum temperature at the start of the LOCA was 122.7 F. The fuel assembly backpressure, measured by RTAP01, was within the 28.5 ± 1 psia control band prior to the LOCA and was centered about 21 psia during the LOCA transient. Inlet plenum pressure control was centered about 37 psia during the LOCA. The pre-LOCA flow rate was within the 345 +17/-0 gpm range.

ct: (w/o attachment)

D. P. Birmingham, B&W
J. E. Blake, B&W
J. A. Curtis, B&W
R. B. Pagett, WSRC
G. C. Rush, B&W/GC2

1200

Test Response/Performance

The LOCA transient in Test 867_23 proceeded through the entire 60 second event. Initial power was approximately 4.025 MW and was ramped to zero following the Best Estimate decay curve. The overall flow rate measured by the venturis (IPVN20) dropped to approximately 115 gpm during the LOCA transient. This represented a 54% reduction from the post-LOCA flow rate. During the LOCA the dynamic pressure in channel 3, indicated by pitot tube C3DP02, experienced moderate fluctuations.

The test setup to initial pre-LOCA steady-state conditions was without any events which would have jeopardized the integrity of the fuel assembly. During the transient the maximum metal temperature IFMT10, peaked at 330 F. Fluid temperatures reached 270 F during the LOCA transient. Void generation was measured in both channels 3 and 4 during the transient by the outlet plane fiber optic void sensors.

The test was successfully terminated and the fuel assembly secured with no detectable damage.

Sincerely,

BABCOCK & WILCOX
Research and Development Division

Rob M. Privette
Nuclear Steam Systems & Components

L
Attachment

LOSS OF COOLANT FROM 4.0 MW (E125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a
 ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a
 ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a
 ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

THOUSANDS LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a
 ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
TEST: 867_23.e3a
ZERO-TIME: 20-SEP-1989 15:11:45.57

THOUSANDS LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a
 ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
TEST: 867_23.e3a
ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MM (Ø125F) - BEST ESTIMATE SCRAM
TEST: 867_23.e3a
ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
TEST: 867_23.e3a
ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
TEST: 867_23.e3a
ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
TEST: 867_23.e3a
ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a
 ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a
 ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a
 ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (e125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

THOUSANDS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a
 ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a
 ZERO-TIME: 20-SEP-1989 15:11:45.57

V O I T S

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

THOUSANDS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a
 ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a
 ZERO-TIME: 20-SEP-1989 15:11:45.57

F L O W R A T E G P M

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

F L O W D I F F E R E N C E Z

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (E125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a
 ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (C125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (E125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a
 ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a
 ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (C125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a
 ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
TEST: 867_23.e3a
ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
TEST: 867_23.e3a
ZERO-TIME: 20-SEP-1989 15:11:45.57

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_23.e3a ZERO-TIME: 20-SEP-1989 15:11:45.57

Babcock & Wilcox

a McDermott company

Research and Development Division

1562 Beeson Street
Alliance, Ohio 44601
(216) 821-9110

October 17, 1989

Charles A. Nash
Westinghouse Savannah River Company
Savannah River Site
Building 786-5A
Aiken, SC 29808-0001

Subject: Transmittal of the Complete Quick Plot Set for Test 867_26,
4.0 MW Best Estimate Scram LOCA at 125 F, SRP-1,133

Dear Charles:

Attached for your information is the subject plot set containing data plots for the complete test spanning from about -300 to 90 seconds, time scale enhancements at -1 to 5 seconds and a few custom plots. The time scale is set up so that 0 seconds corresponds to the start of the LOCA transient.

The power supply safety temperature trips for the METRAScope and HP oscillograph were set at 400 F, consistent with previous tests. Flow trip setpoints (total flow from the venturi (IPDP04) and channel pitot measurements) were configured for a power trip at an 80% reduction in flow from the post-LOCA expected flow value.

I have reviewed the data and have the following test anomalies and data observations to document.

Instrument or Control Anomalies

There are no instrument anomalies to report.

There are no control anomalies to report.

Inlet plenum temperature at the start of the LOCA was 124.5 F. The fuel assembly backpressure, measured by RTAP01, was within the 28.5 ± 1 psia control band prior to the LOCA and was centered about 21 psia during the LOCA transient. Inlet plenum pressure control was centered about 37 psia during the LOCA. The pre-LOCA flow rate was within the 345 +17/-0 gpm range.

ct: (w/o attachment)

D. P. Birmingham, B&W
J. E. Blake, B&W
J. A. Curtis, B&W
R. B. Pagett, WSRC
G. C. Rush, B&W/GCR

3

Test Response/Performance

The test setup to initial pre-LOCA steady-state conditions was without any events which would have jeopardized the integrity of the fuel assembly. Initial power was approximately 4.00 MW. The transient proceeded through the entire 60 second event, power decay followed the Best Estimate decay curve. The overall flow rate measured by the venturis (IPVN20) dropped to approximately 96 gpm during the transient. This represented a 61% reduction from the post-LOCA flow rate. During the LOCA the dynamic pressure in channel 3, indicated by pitot tube C3DP02, experienced moderate fluctuations. The maximum metal temperature, IFMT14, peaked at about 320 F. Fluid temperatures in channel 3 reached about 265 F during the transient. Void generation was measured in channel 3 and to a much lesser extent in channel 4 by the outlet plane fiber optic void sensors.

The test was successfully terminated and the fuel assembly secured with no detectable damage.

Sincerely,

BABCOCK & WILCOX
Research and Development Division

Rob M. Privette
Nuclear Steam Systems & Components

L
Attachment

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
TEST: 867_26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
TEST: 867_26.e3a
ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCI-1989 15:54:28.69

THOUSANDS LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a
 ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
TEST: 867_26.e3a
ZERO-TIME: 10-OCT-1989 15:54:28.69

THOUSANDS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-0CI-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-01-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a
 ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-0CI-1989 15:54:28.69

Seconds

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-0CI-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
TEST: 867_26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
TEST: 867_26.e3a
ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a
 ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a
 ZERO-TIME: 10-OCT-1989 15:54:28.69

P R E S S U R E P S I A

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCI-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (e125F) - BEST ESTIMATE SCRAM
TEST: 867_26.e3a
ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (C125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a
 ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (C125F) - BEST ESTIMATE SCRAM
TEST: 867_26.e3a ZERO-TIME: 10-0CI-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
TEST: 867_26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
TEST: 867_26.e3a ZERO-TIME: 10-0CI-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-0CI-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCI-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (2125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCI-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-0CI-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a
 ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a
 ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCI-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-0CI-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-0CI-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-0CI-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-0CI-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-0CI-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a
 ZERO-TIME: 10-OCT-1989 15:54:28.69

THOUSANDS LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-0CI-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a
 ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

THOUSANDS LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-0CT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (E125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-0C1-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-0CI-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCI-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-0CI-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a
 ZERO-TIME: 10-0CI-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

P R E S S U R E P S I A

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-0C1-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (C125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (E125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-0CI-1989 15:54:28.69

Time (seconds)

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-0CI-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (E125F) - BEST ESTIMATE SCRAM
 TEST: 867 26.e3a ZERO-TIME: 10-OCI-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-0C1-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867 26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (E125F) - BEST ESTIMATE SCRAM
 TEST: 867 26.e3a ZERO-TIME: 10-OCI-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (e125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCI-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (2125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (C125F) - BEST ESTIMATE SCRAM
 TEST: 867 26.e3a ZERO-TIME: 10-0CI-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867 26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (C125F) - BEST ESTIMATE SCRAM
 TEST: 867 26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a
 ZERO-TIME: 10-01-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-0CI-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a
 ZERO-TIME: 10-0CI-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
TEST: 867_26.e3a ZERO-TIME: 10-OCI-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a
 ZERO-TIME: 10-OCI-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867 26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a ZERO-TIME: 10-0CI-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (Q125F) - BEST ESTIMATE SCRAM
TEST: 867_26.e3a
ZERO-TIME: 10-OCT-1989 15:54:28.69

LOSS OF COOLANT FROM 4.0 MW (0125F) - BEST ESTIMATE SCRAM
 TEST: 867_26.e3a
 ZERO-TIME: 10-OCT-1989 15:54:28.69

Babcock & Wilcox

a McDermott company

Research and Development Division

1562 Beeson Street
Alliance Ohio 44601
(216) 821-9110

December 14, 1989

Charles A. Nash
Westinghouse Savannah River Company
Savannah River Site
Building 786-5A
Aiken, SC 29808-0001

Subject: Transmittal of the Complete Quick Plot Set for Test 867_38,
4.04 MW Best Estimate LOCA at 125 F, SRP-1,226

Dear Charles:

Attached for your information is the subject plot set containing data plots for the complete test spanning from about -300 to 90 seconds, time scale enhancements at -1 to 5 seconds and a few custom plots. The time scale is set up so that 0 seconds corresponds to the start of the LOCA transient.

The power supply safety temperature trips for the METRAScope and HP oscillograph were set at 400 F, consistent with previous tests. Flow trip setpoints (total flow from the venturi (IPDP04) and channel pitot measurements) were configured for a power trip at an 80% reduction in flow from the post-LOCA expected flow value.

I have reviewed the data and have the following test anomalies and data observations to document.

Instrument or Control Anomalies

There are no instrument anomalies to report.

There are no control anomalies to report.

The test was set up to repeat 867_05. Target values of initial temperature, flow rate, and power corresponded to those in 867_05. Inlet plenum temperature (IPRT01) at the start of the LOCA was approximately 124.4 F, slightly higher than the 123.6 F target value. The pre-LOCA flow rate, approximately 353 gpm, agreed well with the 356 gpm target value. The fuel assembly backpressure, measured by RTAP01, was within the 28.5 ± 1 psia control band prior to the LOCA. Post-LOCA pressures at the inlet plenum and reactor tank were centered on 36.1 psia and 20.7 psia, respectively.

ct: (w/o attachment)

D. P. Birmingham, B&W
J. E. Blake, B&W
J. A. Curtis, B&W
T. R. Ohrn, B&W
R. B. Pagett, WSRC
G. C. Rush, B&W/GR

1577

Test Response/Performance

The test setup to initial pre-LOCA steady-state conditions was without any events which would have jeopardized the integrity of the fuel assembly. Initial power was approximately 4.04 MW, closely matching the target value. The test proceeded through the entire 60 second LOCA event with the power scram following the best estimate target decay curve.

Temperatures remained relatively low during the transient with the maximum metal temperature reaching approximately 303 F (IFMT14) and the maximum fluid temperature climbing to 253 F (BFTC02). These values compare well with the corresponding VTAB values of 298 F and 253 F recorded during 867_05.

The channel pitot tubes indicated moderate fluctuations in dynamic pressure during both transients. Void generation was detected in channels 3 and 4 as was the case during 867_05. The duration of void generation in channel 4 was somewhat greater than that in the earlier test.

Oscillations in bundle differential pressure (TFDP01), a probable result of nucleate boiling, developed during both tests as the inner fuel metal temperature rose above saturation temperature. During the current test, the oscillations continued until the start of the LOCA. During 867_05, the oscillations damped out prior to LOCA initiation.

The test was successfully terminated and the fuel assembly secured with no detectable damage.

Sincerely,

BABCOCK & WILCOX
Research and Development Division

Rob M. Privette
Nuclear Steam Systems & Components

L
Attachment

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.F3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.F3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

THOUSANDS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a ZERO-TIME: 11-DEC-1989 23:54:27.92

THOUSANDS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
TEST: 867_38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a
 ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
TEST: 867_38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (Q125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.F3A ZERO-TIME: 11-DEC-1989 23:54:27.92

100x

LOSS OF COOLANT FROM 4.04 MW (2125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
TEST: 867_38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
TEST: 867_38.E3A
ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.84 MW (2125 F) - BEST ESTIMATE SCRAM
TEST: 867_38.F3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (e125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (Q125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (Q125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a
 ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867 38.e3a ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 86738.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.F3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a ZFRO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a
 ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (2125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.E3A
 ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a
 ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a
 ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a ZERO-TIME: 11-DEC-1989 23:54:27.92

THOUSANDS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a
 ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867 38.e3a 2100-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867 38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (Q125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

THOUSANDS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867 38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.F3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.L3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.F3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (e125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (Q125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a
 ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a
 ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (2125 F) - BEST ESTIMATE SCRAM
 TEST: 867 38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a
 ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a
 ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
TEST: 867_38.e3a
ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (2125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a
 ZERO-TIME: 11-DEC-1989 23:54:27.92

TEMPERATURE F

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.E3A ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
TEST: 867_38.e3a
ZERO-TIME: 11-DEC-1989 23:54:27.92

LOSS OF COOLANT FROM 4.04 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_38.e3a
 ZERO-TIME: 11-DEC-1989 23:54:27.92

Babcock & Wilcox

a McDermott company

Research and Development Division

1562 Beeson Street
Alliance, Ohio 44601
(216) 821-9110

December 15, 1989

Charles A. Nash
Westinghouse Savannah River Company
Savannah River Site
Building 786-5A
Aiken, SC 29808-0001

Subject: Transmittal of the Complete Quick Plot Set for Test 867_39,
4.10 MW Best Estimate LOCA at 125 F, SRP-1,230

Dear Charles:

Attached for your information is the subject plot set containing data plots for the complete test spanning from about -300 to 90 seconds, time scale enhancements at -1 to 5 seconds and a few custom plots. The time scale is set up so that 0 seconds corresponds to the start of the LOCA transient.

The power supply safety temperature trips for the METRAScope and HP oscillograph were set at 400 F, consistent with previous tests. Flow trip setpoints (total flow from the venturi (IPDP04) and channel pitot measurements) were configured for a power trip at a 90% reduction in flow from the post-LOCA expected flow value.

I have reviewed the data and have the following test anomalies and data observations to document.

Instrument or Control Anomalies

There are no instrument anomalies to report.

There are no control anomalies to report.

The test was setup to repeat 867_15. Target values of initial temperature, and flow rate corresponded to those in 867_15. Inlet plenum temperature (IPRT01) at the start of the LOCA was approximately 123.9 F, slightly lower than the 124.1 F target value. The pre-LOCA flow rate, approximately 350 gpm, agreed well with the 351 gpm target value. The fuel assembly backpressure, measured by RTAP01, was within the 28.5 ± 1 psia control band prior to the LOCA. Post-LOCA pressures at the inlet plenum and reactor tank were centered on 36.5 psia and 21.0 psia, respectively.

ct: (w/o attachment)

D. P. Birmingham, B&W
J. E. Blake, B&W
J. A. Curtis, B&W
T. R. Ohrn, B&W
R. B. Pagett, WSRC
G. C. Rush, B&W/GC²

1104

Test Response/Performance

The test setup to initial pre-LOCA steady-state conditions was without any events which would have jeopardized the integrity of the fuel assembly. Initial power was approximately 4.125 MW. This satisfied the target power of slightly above 4.1 MW. During 867_15 power tripped off due to low flow rate. For the current test, flow trips were reduced from 20% of post-LOCA flow rate used during 867_15 to 10% of post-LOCA flow rate. The test proceeded without a power trip through the entire 60 second LOCA event. The power scram followed the best estimate target decay curve.

Temperatures remained relatively low during the transient with the maximum metal temperature reaching approximately 315 F (IFMT08) and the maximum fluid temperature climbing to 280 F (C3TC03). These values compare well with the corresponding VTAB values of 317 F and 265 F recorded during 867_15. The maximum metal temperature during 867_15, 358 F, was recorded on IFMT10 rather than IFMT08 as in the current test.

Channel 3 differential pressure (C3DP07) fluctuations were several times larger than those during 867_15 in the 2 minute hold period prior to the LOCA. Peak amplitudes were about 8 psid compared to approximately 1.9 psid during 867_15. This characteristic was observed in the prior test (867_38) and appears to be related to the new rib configuration in channel 3.

Dynamic pressure changes sensed by the pitot tubes during the LOCA transient showed good repeatability with 867_15 prior to the power trip in Test 867_15. Channel 3 flow excursion was large. Void generation was detected in channels 3 and 4 during both tests. The onset of void generation in channel 3 occurred somewhat later in the current test than in 867_15.

The test was successfully terminated and the fuel assembly secured with no detectable damage.

Sincerely,

BABCOCK & WILCOX
Research and Development Division

Rob

Rob Privette
Nuclear Steam Systems & Components

L
Attachment

LOSS OF COOLANT FROM 4.1 MW (Q125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a
 ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3e
 ZERO-TIME: 13-DEC-1989 22:35:57.48

THOUSANDBOSS OF COOLANT FROM 4.1 MW (Q125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a
 ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

THOUSANDBOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a
 ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (Q125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3e ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (Q125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a
 ZERO-TIME: 13-DEC-1989 22:35:57.48

Seconds

LOSS OF COOLANT FROM 4.1 MW (2125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a
 ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (Q125 F) - BEST ESTIMATE SCRAM
TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e30 ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a
 ZERO-TIME: 13-DEC-1989 22:35:57.48

P R E S S U R E P S I A

LOSS OF COOLANT FROM 4.1 MW (Q125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a
 ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e30
 ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
TEST: 867_39.e3a
ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
TEST: 867_39.e3a
ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a
 ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (Q125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a
 ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a
 ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (2125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a
 ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (Q125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a
 ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (2125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (Q125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (2125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a
 ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (Q125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a
 ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3e
 ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (Q125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a
 ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a
 ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e2a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (2125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

THOUSANDS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a
 ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39_e3a
 ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e30 ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e30 ZERO-TIME: 13-DEC-1989 22:35:57.48

THOUSANDS OF COOLANT FROM 4.1 MW (Q125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
TEST: 867_39.E3A ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e30 ZERO-TIME: 13-DEC-1989 22:35:57.49

LOSS OF COOLANT FROM 4.1 MW (e125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a
 ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125.F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (Q125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3e ZERO-TIME: 13-DEC-1989 22:35:57.48

P R E S S U R E P S I A

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (Q125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a
 ZERO-TIME: 13-DEC-1989 22-35-57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a
 ZERO-TIME: 13-DEC-1989 22:35:57.48

D I F F P R E S S U R E P S I D

Time (seconds)

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a
 ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a
 ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (Q125 F) - BEST ESTIMATE SCRAM
 TEST: 867 39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3e
 ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3e ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (Q125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (Q125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (Q125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a
 ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (2125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a
 ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (Q125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a
 ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
TEST: 867_39.e3e ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (2125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 12-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a
 ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e30
 ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a
 ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e30
 ZERO-TIME: 13-DEC-1989 22:35:57.48

LOSS OF COOLANT FROM 4.1 MW (0125 F) - BEST ESTIMATE SCRAM
 TEST: 867_39.e3a
 ZERO-TIME: 13-DEC-1989 22:35:57.48

Babcock & Wilcox

Research and Development Division

a McDermott company

July 21, 1989

1562 Beeson Street
Alliance, OH 44601
(216) 821-9110

Charles A. Nash
Westinghouse Savannah River Company
Savannah River Site
Building 786-5A
Aiken, SC 29808-0001

Subject: Transmittal of the Complete Quick Plot Set for Test 867_06,
90% OFI Power Fast Scram LOCA at 125 F, SRP-1,002

Dear Charles:

Attached for your information is the subject plot set containing data plots for the complete test spanning from about -300 to 70 seconds, time scale enhancements at -1 to 5 seconds, and a few custom plots.

I have reviewed the data and have the following test anomalies and data observations to document:

Instrument or Control Anomalies

- 1) The fast scram power control did not achieve a sharp break at 0.10 seconds as intended. Rather, the DATAtak control resolution "rounded" the break beginning at about 0.0 seconds. As a result, the power transient was simultaneously initiated along with the hydraulic transient instead of the intended 0.10 second delay in power decay.

The sharp break and steep descent of the initial fast scram power decay to the first plateau exceeds the control response of the DATAtak with its fastest gearset installed (20 second full scale drum rotation). As such, future fast scram tests should use these test results to factor this control limitation into the start of the power scram, appropriately delaying its start time relative to that of the hydraulic transient.

- 2) Thermocouple IFMT07 was erratic during the test, consistent with prior test observations, and will be set to NOREAD before final data conversion. B&W has verified this thermocouple reads well without power applied and experiences the noisy reading only after power is applied. The thermocouple will be switched to a new reference oven channel prior to performing the next test to determine if the reference oven channel is the noise source.

cc: (w/o attachment)

D. P. Birmingham, B&W
J. E. Blake, B&W
R. B. Pagett, WSRC

1551

Test Response/Performance

The test setup to initial pre-LOCA steady state as well as the LOCA transient proceeded without any significant events that might otherwise have jeopardized fuel assembly integrity during the test. The overshoot in power to about 4.7 MW during the power ramp to the pre-LOCA initial conditions was manually adjusted downward to the 4.5 MW starting value via the DATAtrak trim pot. One anomaly was observed between about -175 and -125 seconds during the power ramp (power about 4 MW) to pre-LOCA steady state conditions. As observed on the overall subchannel differential pressure plot (C2DP01, C2DP03, etc.), pressure oscillations probably originating from both inner and outer heater tube wall subcooled nucleate boiling were present during this time period. The oscillations damped, however, as steady state power conditions were achieved. Oscillations of a similar characteristic were observed during the previous tests, 867_04 and 867_05, at about the same power.

This transient proceeded with minimal hydraulic disturbance. The channel differential pressure measurements oscillated following LOCA initiation as in previous LOCA power tests. Void generation in channel 3 was minimal and not detected at the outlet plane until after the first power plateau was achieved. Flow remained strong the entire transient with no indication of a flow instability. This was in agreement with WSRC predictions. As a result, the power decay persisted for the complete 60 second time interval before test termination activities ramped the power to zero and safely secured the fuel assembly.

Sincerely,

BABCOCK & WILCOX
Research and Development Division

Greg C. Rush
Group Supervisor
Nuclear Steam Systems & Components

L
Attachment

LOSS OF COOLANT FROM 90 x OSV (0125F) - IP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - TP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - TP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - 1P-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - 1P-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

THOUSANDS LOSS OF COOLANT FROM 90 x OSV (0125F) - 1P-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - 1P-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

THOUSANDS LOSS OF COOLANT FROM 90 x OSV (0125F) - IP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - TP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

F L O W R A T E G P M

LOSS OF COOLANT FROM 90 x OSV (0125F) - 1P-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - TP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - TP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

Seconds

LOSS OF COOLANT FROM 90 x OSV (0125F) - IP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - IP-867
TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - IP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 % OSV (0125F) - TP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 ± OSV (0125F) - TP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 X OSV (0125F) - IP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - IP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - TP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - 1P-867
TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - 1P-867
TEST: 867_06.e30 ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - 1P-867
TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - IP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 & OSV (@125F) - TP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - IP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - TP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - TP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - 1P-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - 1P-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - IP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - TP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - IP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - IP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (E125F) - TP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 % OSV (0125F) - TP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - IP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - TP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 & OSV (0125F) - IP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - IP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - 1P-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 & OSV (0125F) - IP-867
 TEST: 867_06.e3a
 ZERO-TIME: 19-JUL-1989 15:27:25.37

TEST: 867_06.e3a
 LOSS OF COOLANT FROM 90 x OSV (0125F) - TP-867
 ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - 1P-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - IP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

TEST: 867_06.e3a

LOSS OF COOLANT FROM 90 x OSV (0125F) - IP-867

ZERO-TIME: 19-JUL-1989 15:27:25.37

THOUSANDS LOSS OF COOLANT FROM 90 & OSV (0125F) - IP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 & OSV (0125F) - TP-867
TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 & OSV (01251) - 1P-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

THOUSANDS LOSS OF COOLANT FROM 90 x OSV (0125F) - TP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - 1P-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

FLOW RATE GPM

LOSS OF COOLANT FROM 90 & OSV (0125F) - IP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - IP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - 1P-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - 1P-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - 1P-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - IP-867
TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - TP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

P R E S S U R E P S I A

LOSS OF COOLANT FROM 90 X OSV (0125F) - TP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 & OSV (0125F) - IP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - IP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - TP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (e125F) - IP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - IP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - IP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - TP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 & OSV (0125F) - IP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - 1P-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (@125F) - 1P-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (@125F) - IP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - 1P-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - 1P-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 & OSV (0125F) - IP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - 1P-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 & OSV (0125F) - 1P-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - 1P-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (#125F) - TP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - 1P-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - TP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - IP-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 % OSV (@125F) - 1P-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (E125F) - 1P-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

LOSS OF COOLANT FROM 90 x OSV (0125F) - 1P-867
 TEST: 867_06.e3a ZERO-TIME: 19-JUL-1989 15:27:25.37

Babcock & Wilcox

a McDermott company

Research and Development Division

1562 Beeson Street
Alliance, OH 44601
(216) 821-9110

August 11, 1989

Charles A. Nash
Westinghouse Savannah River Company
Savannah River Site
Building 786-5A
Aiken, SC 29808-0001

Subject: Transmittal of the Complete Quick Plot Set for Test 867_14,
90% OSV Power Fast Scram LOCA at 125 F, SRP-1,043

Dear Charles:

Attached for your information is the subject plot set containing data plots for the complete test spanning from about -310 to 70 seconds, time scale enhancements at -1 to 5 seconds, and a few custom plots. Included for the first time in the custom plots are the bottom fitting and channel exit temperature measurements relative to the monitor pin RTD, BFRT01. The power supply safety trips were set to their "non-recovery" values with a 30% post-LOCA nominal flow reduction trip and 400 F metal temperature trips on the HP oscillograph and METRAScope.

I have reviewed the data and have the following test anomalies and data observations to document.

Instrument or Control Anomalies

There are no control anomalies to report. The transient progressed for the complete 60 second power decay without power trip.

There is one instrument anomaly to report, consistent with prior tests. Thermocouple IFMT07 was once again erratic during the test and will be set to NOREAD before final data conversion. WSRC is formally requested to approve the disconnect of this instrument from the data acquisition system to eliminate the need to mess with this instrument (set it to NOREAD) during final data conversions and data base quality assurance.

cc: (w/o enclosure)

D. P. Birmingham, B&W
J. E. Blake, B&W
J. A. Curtis, B&W
R. B. Pagett, WSRC
R. M. Privette, B&W

1636

Test Response/Performance

The test setup to initial pre-LOCA steady-state as well as the LOCA transient proceeded without any significant events that might otherwise have jeopardized fuel assembly integrity during the test. Channel 3 pressure oscillations were monitored with C3DP01 on the HP oscillograph, consistent with the previous test. As expected, significant oscillations were observed in the measured channel pressure drop between about 3 MW and the starting power but dissipated during the 2 minute power hold period prior to LOCA initiation.

As shown in the attached power decay plot, the power remained constant at the onset of the LOCA before the rapid descent at about 0.1 seconds. Consistent with the previous fast scram test, 867_06, the initial power descent is too steep for the DATAttrak to simulate. The test power is observed to lag the fast scram descent until the intermediate power plateau was reached at which time the DATAttrak power control matched the target fast scram power descent. During the initial power descent void developed in channel 3, achieving a value of about 25% for a 1 second period. Channel 4 voiding followed, lasting about 0.3 seconds at an equal magnitude. The void production reduced the total fuel assembly flow rate and nearly yielded a low flow trip set at 70% of the post-LOCA nominal flow rate. Void generation was not sustainable as the fast scram power decay progressed and flow recovered to effectively cool the heater tubes. The test was successfully terminated at the end of the 60 second power decay and the fuel assembly secured with no detectable damage.

Sincerely,

BABCOCK & WILCOX
Research and Development Division

Greg C. Rush
Group Supervisor
Nuclear Steam Systems & Components

L
Enclosure

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - 1P-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A
 ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (@125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

THOUSANDS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - 1P-86
TEST: 867_14.E3A
ZERO-TIME: 09-AUG-1989 12:30:59.66

THOUSANDS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A
 ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - 1P-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90x OSV (0125F) - FAST SCRAM - 1P-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (#125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A
 ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - IP-86
TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A
 ZERO-TIME: 09-AUG-1989 12:30:59.66

P R E S S U R E P S I A

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - 1P-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - 1P-86
 TEST: 867_14.E3A
 ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90x OSV (0125F) - FAST SCRAM - IP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - IP-86
TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - 1P-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - 1P-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 98% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - IP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (#125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - 1P-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - 1P-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - IP-86
 TEST: 867_14_E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - IP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A
 ZERO-TIME: 09-AUG-1989 12:30:59.66

1074

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - IP-86
 TEST: 867_14.E3A
 ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - IP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

TEMPERATURE F

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - 1P-86
 TEST: 867_14.E3A
 ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - 1P-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90x OSV (0125F) - FAST SCRAM - 1P-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

THOUSANDS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - IP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - 1P-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90x OSV (0125F) - FAST SCRAM - 1P-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

THOUSANDS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - IP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (Q125F) - FAST SCRAM - IP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - 1P-86
 TEST: 867_14.E3A
 ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - 1P-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - 1P-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - IP-86
 TEST: 867_14.E3A
 ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - 1P-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - 1P-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 9A% OSV (0125F) - FAST SCRAM - 1P-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

P R E S S U R E P S I A

LOSS OF COOLANT FROM 90% OSV (Q125F) - FAST SCRAM - 1P-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

P R E S S U R E P S I A

LOSS OF COOLANT FROM 90% OSV (2125F) - FAST SCRAM - TP-86
 TEST: 867_14.53A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - IP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - IP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - IP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A
 ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - 1P-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - IP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - IP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (Q125F) - FAST SCRAM - 1P-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (@125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - 1P-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - 1P-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - 1P-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - 1P-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

LOSS OF COOLANT FROM 90% OSV (0125F) - FAST SCRAM - TP-86
 TEST: 867_14.E3A ZERO-TIME: 09-AUG-1989 12:30:59.66

END

**DATE
FILMED**

4 / 17 / 92