AIM

Association for Information and Image Management

1100 Wayne Avenue, Suite 1100
Silver Spring, Maryland 20910
301/587-8202

Centimeter

Inches

MANUFACTURED TO AIM STANDARDS
BY APPLIED IMAGE, INC.

1 of 1

Coal Log Pipeline Research at the University of Missouri

3rd Quarterly Report for 1993

7/1/93 - 9/30/93

Henry Liu
Professor and Director
Capsule Pipeline Research Center

DE-FC22-93PC 92578

Project Sponsors:

National Science Foundation (IUCRC Program)

State of Missouri (Department of Economic Development)

U.S. Department of Energy (Pittsburgh Energy Technology Center)

Coal Log Pipeline Consortium:

Arch Mineral Corporation
Associated Electric Coop.
MAPCO Transportation, Inc.
Union Electric Company
Williams Pipe Line Company
Williams Technologies, Inc.

Small Business Participants:

Bonnot Company
Gundlach Machine Company
Erie Press Systems
Nova Tech, Inc.
Pro-Mark Process Systems
Ramer & Associates

MASTER

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

92578

do

CONTENT

	<u>Page</u>
Executive Summary	2
Coal Log Fabrication using Hydrophobic Binders	5
Compaction of Binderless Coal Logs.	9
Coating of Coal Logs.	12
Machine Design for Coal Log Fabrication and Extrusion Research . . .	16
Slurry Effects on Hydrodynamics of CLP.	20
Hydrodynamics of CLP	24
Unsteady Flow in Capsule Pipeline.	27
Automatic Control of Coal Log Pipeline System	30
Legal Aspect of CLP.	33
Slurry Impregnation of Dry Coal Logs.	36
Economics of Coal Log Pipelines.	39

Executive Summary

During this quarter, major progress has been made in the following areas of coal log pipeline (CLP) research:

1. With as little as 2% of emulsified asphalt, with compression pressure of 5,000 psi, and temperature of 70°C, good coal logs were made that passed the durability test in pipeline. The low pressure and low temperature required greatly facilitate coal log compaction because they reduce energy consumed, simplifies machine design, and reduces operational difficulties. (Based on Dr. Wilson and Dr. Ding's work).
2. Earlier study of the hot-water-dried (HWD) process of making binderless coal logs required 20,000 psi pressure and 180°C temperature. During this period, it was shown that durable binderless logs can be produced by the HWD process with pressure as low as 10,000 psi, and temperature 150°C. This is a step forward. It was also demonstrated that this process was applicable to different types of coal including a Powder River Basin sub-bituminous coal, an Illinois bituminous coal, a MAPCO bituminous coal, and an Arch Mineral sub-bituminous coal. They all made good durable coal logs. (Based on Dr. Gunnink's work).
3. A split mold was designed, built and tested in the laboratory. It produced coal logs that don't have circumferential cracks and hence are stronger than those produced before in single-piece molds. As a result of this finding, future molds for commercial manufacture of coal logs will use the split-mold concept. (Based on Dr. Lin's design. Used by Drs. Gunnink, Luecke and research associate Burkett).
4. An effective coal-log impregnation method was developed. The method required placing dry coal logs in a chamber with partial vacuum and then immersing the logs in molten asphalt while the vacuum is maintained. Then, air pressure is applied to force the asphalt to enter the logs. The resultant logs contain 3 to 6% asphalt by weight. They became impermeable to water infiltration at 500 psi for several hours. When the same process is used for large coal logs in commercial operations, it will be even more effective and will require much less asphalt (of the order of 1% which is affordable). (Based on Dr. Luecke's work).
5. Completed the design of a commercial coal log fabrication machine and submitted the machine to the judge (Erie Press) for evaluation. (Based on Dr. Lin's work).
6. Completed a study on using coal slurry to suspend coal logs. The study verified the prediction that heavy coal logs can be lifted off (suspended) in slurry at a velocity much lower than that in water. A significant finding was that the pressure drop in a coal-log/slurry flow is identical to that in a slurry-only flow at the same velocity. This means a coal-logs/slurry system transports more coal and uses less water and energy than a coal slurry system. The system is especially useful for transporting heavy logs in a large pipe. (Based on Dr. Seaba's work).

7. Started testing coal log wear in pipe, drag reduction using polymer, and zeta potential effect on coal log fabrication. It was found that erosion of coal logs by water velocity and damage of coal logs by water hammer are both negligible. Wear by rough joints was identified to be the most serious problem. Completed preparation for drag reduction study; results will be reported in the next quarterly report. The zeta potential of coal in contact with tap water, distilled water and deionized water was measured. The effect of some electrolytes (such as aluminum chloride) on neutralizing zeta potential was tested and confirmed. Effects on coal log compaction will be determined during next quarter. (Based on Dr. Liu and three students' work).
8. Experimental data on unsteady capsule flow have been collected. Comparison with theory showed good agreement. Considerable progress has been made in analyzing the operation of the coal log injection system. Initial difficulties encountered were solved by using individual low-head pumps at CLP intake, and using a 3-step valve stroking strategy. (Based on Dr. Lenau and two students' work).
9. In the study of automatic control of CLP systems, two important reports have been produced during this quarter. One is on computer control of the small-scale CLP system, and the other is on design of mechanical subsystems for an automated capsule pipeline. These reports mark a milestone in research on automatic control of CLP. (Based on Dr. Nair and two students' work).
10. In the legal area, research on state "taking" definitions statutes and its effect on coal pipelines has been completed. Research has also begun on authority of railroads under Interstate Commerce Act and state railroad and pipeline statutes to construct and/or operate pipelines, and on transfer of Indian water right for coal pipelines. (Based on Dr. Davis and two students' work).
11. Collected data on coal log water absorption, permeability, binder effects, etc. Completed a M.S. thesis in this area. (Based on Dr. Marrero and Susan Chen's work). Tried different ways to impregnate dry coal logs with a slurry. (Marrero with Becky Smith). Started work on coal log heating, cooling and drying study. (Marrero and Ssu-Hsueh Sun's work).
12. Completed a report which presents a preliminary theoretical model to predict water absorption by coal logs. (Based on Dr. Liu's work).

Major activities planned for the next quarter include the following:

1. Complete design of coal log manufacturing machine for commercial operations (Lin and Ramer).

2. Improve Binderless extrusion of coal logs (Lin).
3. Make large coal logs with the large (100-ton) ram extruder (Burkett).
4. Make large coal logs by compaction (Gunnink, Ding/Wilson, and Luecke).
5. Further reduction of temperature and pressure and make other simplifications in coal log compaction—both in the binderless process (Gunnink) and in the process that uses emulsified asphalt (Ding/Wilson).
6. Complete a preliminary study to determine effectiveness of controlling zeta potential to improve coal log fabrication (Liu).
7. Evaluate the effectiveness of using polymer for drag reduction in CLP (Liu).
8. Testing coal log wear by rough joints in pipe (Liu).
9. Prepare for field test in a 6-inch pipe in Conway, Kansas (Liu).
10. Complete dynamic modeling of CLP system (Lenau).
11. Conduct research on coal log heating, cooling and drying rates (Marrero).
12. Perform sensitivity analysis on economic model (Liu).
13. Test capsule train spacing adjuster in laboratory (Nair).

3rd Quarterly Report Coal Log Pipeline Project

Project Title: Coal Log Fabrication Using Hydrophobic Binders

PI: Dr. John W. Wilson

Post-Doctoral Fellow: Dr. Yungchin Ding

Graduate Research Assistant: Bing Zhao

OVERVIEW:

In recent tests, emulsified asphalts and the Macrotech binder have proved to be beneficial to coal log fabrication and coal log performance. Several 2% asphalt coal logs were made at a temperature of 70°C with the aid of a vacuum. All these coal logs showed promising performance in the pipeline degradation tests. The water absorption tests performed on coal logs made from various types of asphalt emulsions and under varying operating conditions, have been completed.

PROGRESS TO DATE:

A. Water Absorption Tests:

Coal log water absorption tests were carried out using a pressurized water absorption chamber at pressures of 500, 750, 1000, and 1250 psi. All coal logs tested showed no sign of disintegration, however they exhibited different degrees of water absorption.

1. Time effect:

In order to determine the influence of absorption time on the asphalt coal logs, the coal logs were tested at a pressure of 500 psi over various periods of time ranging from one hour to 24 hours. Test results show that the amount of water absorbed by the coal logs tested during one hour tests was 1% less than the 24 hours water absorption tests. This suggests that the amount of water absorbed becomes constant (the coal log is saturated) after approximately one hour testing time.

For coal logs made without heating and vacuum processes, the amount of water absorbed was approximately 22% of the original weight of the tested coal logs. For coal logs made with the aid of heating and vacuum, the amount of water absorbed was approx. 9-12%. These tests showed that the coal logs made with the aid of heating and vacuum had higher water absorption resistance.

2. Influence of pressure:

Water pressures of 500, 750, 1,000, and 1,250 psi were applied to the absorption chamber for determining the influence of water pressure on coal log water resistance. It was found that the amount of water absorbed by the coal logs under test (no heating and vacuum) showed no significant change as the applied pressure increased from 500 psi (19.84%) to 1,250 psi (22.44%). For coal logs made with the aid of heating and vacuum, the amount of water absorbed increased from 8.6% to 10.8% as the pressures increased from 500 to 1,250 psi.

B. Effect of Vacuum, Heating and Compaction Pressure on the Performance of Coal Logs:

The heating and vacuum processes used during coal log compaction demonstrated a positive effect on the performance of coal logs exposed to the 2" pipeline degradation tests. Improved log performance has been accomplished by changing the operating parameters, i.e., lower heating temperature, lower asphalt percentage, and lower compaction pressure.

1. Lower compaction pressure:

In the most recent tests, the compaction pressure applied for coal log fabrication has been reduced to 5,000 psi. The coal logs so produced performed almost the same in the pipeline degradation tests as the coal logs made at a higher pressure (10,000 psi).

2. Lower percentage of asphalt used:

Two percent asphalt (3% asphalt was used in previous tests) coal logs have been successfully made using the compaction method with the aid of heating and vacuum. A 1-2% loss of

weight occurred after 2 hours in the degradation test (2" pipeline test loop).

3. Lower temperature:

Heating coal logs to a temperature of 70°C was used during coal log compaction (90°C to 100°C temperatures were used in previous tests). The coal logs made at this temperature and using this process were found to maintain their strength and survive the 2" pipeline degradation test.

4. Moisture content of coal logs

The coal logs made using the operating parameters mentioned above (5,000 psi, 2% asphalt, heating, and vacuum) have moisture contents of 11-13%, which are only 4 -5% higher than the moisture content of the original coal (7.9%) used for coal log fabrication. These low moisture contents of coal logs indicate that the asphalt emulsions have good hydrophobic characteristics and can expel water during the coal log compaction process.

C. Performance of MacroTech Coal Logs

As noted previously, the Macrotech 8" coal logs did not perform well in the field pipeline degradation tests. This poor test result can be attributed to the combined effects of the low strength of the coal logs due to long term storage in the open air, and the rough inner surfaces of the test pipeline. Degradation tests were also carried out on 2" Macrotech coal logs made by core drilling un-used 8" Macrotech coal logs. The core drilled 2" coal logs were stored in water to prevent surface cracking, before conducting degradation tests. The results of these tests showed that the coal logs satisfied the 2" pipeline degradation tests, by traveling more than one hour in the pipe.

The moisture content of Macrotech coal logs was measured and found to be in the range 12 to 13% (sampled from the center of the tested coal logs), whereas the original coal used to make these logs had a moisture content of more than 25%. This low moisture content confirms visual observations that the Macrotech binder expels water during the coal log extrusion process.

These are encouraging results, and it is proposed that the Macrotech binder should be investigated further for use in benefiting the coal log fabrication process.

Currently, the Macrotech binder is planned to be used for further coal log fabrication tests in Rolla using the compaction method. The test results will be reported as the work progresses. In addition, it is proposed to use and study the extrusion method for coal log fabrication using the Macrotech binder.

Capsule Pipeline Research Center

Quarterly Report

for

Individual Projects

(Period Covered: 6/1/93-8/31/93)

Project Title: Compaction of Binderless Coal Logs

P.I.: Dr. Brett Gunnink, Assistant Professor of Civil Engineering

Research Assistants: Zhuoxiong Liang, Jayanth Kanunur, and Feng Chen

Purpose of Study: To explore and optimize a compaction technique for making binderless coal logs.

Work Accomplished During the Period:

Work accomplished during the past quarter continued the development of Hot Water Dried (HWD) coal logs. HWD logs are high strength water resistant logs. The HWD logs have performed very well and we believe that their development constitutes a major breakthrough in coal log fabrication. The HWD logs meet the durable coal log test performance criteria adopted by the CPRC in May of 1992.

Work during this quarter included parametric studies of the effect of compaction temperature and pressure on the strength of HWD logs. Our results indicate that durable HWD logs can be made at temperatures as low as 150 °C and pressures as low as 10,000 psi. Further details of these parametric studies are included in the key results section of this report.

We have also begun making HWD logs from other coals. For our initial work, only Powder River Basin coal was used. This quarter, we have successfully made HWD logs using an Illinois bituminous coal, a Mapco bituminous coal and an Arch Mineral sub-bituminous coal. We conclude that the HWD process can be used to make high strength water resistant logs from many types of coal. A comparison of the characteristics of Powder River Basin coal logs with Illinois coal logs is included in the key results section of this report.

Finally, we have completed the fabrication of a multi-part mold and have begun making HWD logs with this mold. Preliminary results indicate that detrimental circumferential cracking of coal logs can be eliminated by making logs in this multi-part mold. This will significantly increase the strength and durability of coal logs. The mold will also be used to more closely simulate the fabrication process that would be used in a coal log manufacturing machine.

Work Proposed for Next Quarter:

Work for next quarter will include:

1. making coal logs in the multi-part mold and eliminating circumferential cracking,
2. evaluating the durability and strength of logs made in the multi-part mold without circumferential cracks,
3. continuing to make HWD coal logs made from different coals, and evaluating their strength and durability,
4. planning for the fabrication of large diameter logs and designing a large diameter compaction mold.

Publications Resulting from Work on this Project:

Gunnink, B.W., Kanunar, J., and Liang, Z. "Compaction of Hot Water Dried Coal Agglomerates", Preliminary Invention Disclosure, April 15, 1993.

Gunnink, B.W. and Liang, Z., "Compaction of Binderless Coal for Coal Log Pipelines", accepted for publication in *Fuel Processing Technology*, Elsevier, Amsterdam.

Liang, Z., (1993) "Compaction of Binderless Coal for Coal Log Pipelines", thesis presented to the University of Missouri-Columbia, at Columbia, Missouri, in partial fulfillment of the requirements for the degree of Master of Science.

Gunnink, B.W. and Liang, Z., (1992) "Compaction of Binderless Coal Logs for Coal Pipelines", *Proceedings 17th International Conference on Coal Utilization and Slurry Technologies*, Coal and Slurry Technology Association, 677-686.

Key Results of Recent Work:

We have investigated the effects of compaction temperature and pressure on the post adsorption tensile strength of HWD coal logs made from Powder River Basin coal.

Figure 1 shows the observed relationship between strength and temperature. All the data in this figure are for logs compacted at a pressure of 20,000 psi. Five logs were

made at each compaction temperature. The logs were placed in 500 psi water for 24 hour prior to the measurement of their splitting tensile strength. The average strength increases with an increase in compaction temperature. However, log strength is more variable at higher temperatures.

Figure 1 inserted here

Pressure Study data and text inserted here

The results of these parametric studies lead us to believe that satisfactory coal logs can be made at 150 oC with a compaction pressure of 10,000 psi. We did not conduct durability test as part of this study. Log durability is adversely affected by circumferential cracking. Our preliminary test results indicate that circumferential cracking is eliminated by using a multi-part mold. We will evaluate the strength and durability of logs made using the multi-part mold during the next quarter.

Table 1 contrasts characteristics of Powder River Basin HWD logs with Illinois HWD logs. The HWD log fabrication process lowers the equilibrium moisture content of the Illinois coal from 17% to 10%. In contrast, the Powder River Basin coal's equilibrium moisture content is lowered from 30% to 21%. The initial density of Illinois logs is somewhat higher than Powder River Basin logs, 1.286g/cm³ versus 1.260. However, Illinois logs adsorb less water and thus post adsorption densities are nearly equal for logs made from both coals. Powder River Basin logs are significantly stronger than Illinois logs. The strength difference is largest for pre-adsorption compressive strength. However, for post-adsorption tensile strength, which is the most critical strength parameter, the strength difference is much less. These results indicate that durable coal logs can be made from Illinois coal, and presumably other coals, as well as Powder River Basin coal.

Quarterly Report

Period Covered: 7/1/93 - 9/30/93

Project Title: Coating of Coal Logs

P.I.: Dr. Richard H. Luecke, Professor of Chemical Engineering

Graduate Student Assistant: Daniel Carney

Undergraduate Assistant: Andrew Rockabrand

Purpose: To impregnate coal logs with asphalt to prevent water infiltration.

Work Accomplished During the Period:

An asphalt impregnation procedure has been demonstrated for coal logs made from dried coal which resists water infiltration. A negligible amount of water is absorbed during the high pressure (500 psi) water absorption test and the log subsequently endures the capsule pipeline circulation test.

Work Proposed for the Next Quarter:

- Task 1. Test 1-3/4" diam logs using the new split mold configuration. Specific gravities for the previous logs have ranged from 1.20 to 1.28. Lower specific gravities are desirable and were attained in earlier phases of the log manufacture program. Lower pressures and temperatures during the log formation process will be investigated. These coal logs will be completely characterized including not only the high pressure water absorption and pipeline endurance tests described above but also for other important factors such as tensile strength and grindability tests (Rolla).
- Task 2. Begin the extension of coal log fabrication to larger scale. This will require design, construction and installation of 5+" molds for the large press. Also required will be design and construction of impregnation equipment suitable for larger logs. Our group will focus on design and operation of impregnation procedures.

Key Results of Recent Work:

Various methods of producing water impervious casings for coal logs have been tried ranging from dipping the logs in molten waxes or asphalts to spraying them with polymers. While some of the other methods showed some promise, only a vacuum impregnation technique with asphalt has been demonstrated to give consistent protection against water infiltration.

All of the results discussed here used western coal (Powder River Basin) that had been air-dried to 2-3% moisture and ground to a particle size distribution previous found approximately optimal for the formation of strong logs (largest particle size through 20 mesh).

The log is placed in a closed vessel and the interior air pressure is reduced to about 1/10 atmosphere to remove air from the log. Maintaining the vacuum, the log is then submerged in molten asphalt after which air is readmitted to the vessel to force molten asphalt into the evacuated log. Air pressures up to about 50 psig may also be used in the vessel to accelerate the asphalt in-flow.

So far 32 dried coal logs have been impregnated using variations of the procedure described above. A set of conditions was defined that gave consistent satisfactory performance both at high water pressures and in the circulating pipeline. The principal objective of this work so far has been to demonstrate a feasible log made from dried coal that has the needed properties of durability and density. Only a few experiments have been conducted to optimize the impregnation procedure with respect to the processing variables of time, temperature, pressure, etc.

Typically asphalt impregnation levels of 3% to 6% have been obtained in the 1-3/4" diam x 3" long test logs from this procedure. Since only the outer layers of the log may need to be impregnated, it is anticipated that far lower levels of asphalt will be required in commercial (20" diam) logs.

Of the 32 dried coal logs that have been impregnated using these procedures, five failed after 1 to 5 hrs in the 500 psi water immersion test. However all these five had been impregnated with a higher pressure during the evacuation phase (0.5 atm) and lower pressure (1 atm) during the asphalt immersion and impregnation phase. Both of these factors work to reduce the amount of asphalt absorption and although these logs gained 3% to 5% asphalt, apparently the asphalt distribution was not sufficient to resist water infiltration.

Nine of the logs (treated with full vacuum and both with and without air pressure during the asphalt inflow) were subjected to the high pressure water test until failure occurred. The shortest observed failure time was 5.4 hours. Some logs persisted unchanged for well over 48 hrs. After these experiments, a standard procedure was developed as follows:

1. A 1-3/4" diam x 3" long coal log is impregnated with asphalt after heating for 30 minutes in the vapor space.
2. The air is then evacuated to the maximal attainable vacuum (about 0.1 psia) for one hour.
3. The log is immersed in molten asphalt while the vacuum is maintained for 1 additional hour (to permit heating of the log interior).

4. The vacuum is discontinued and air at 50 psig is maintained over the molten liquid for 2-4 hr to force asphalt into the pore structure of the log.
5. Pressure is reduced to atmospheric and the log is removed from the molten asphalt and is allowed to drain and cool.
6. The log is then immersed in water at 500 psi for 5-6 hr.
7. After removal from the high pressure test system, the log is tested by circulation for 1 hour in the test pipeline (300-400 revolutions).
8. After the circulation test, the log is again immersed into the 500 psi water system for additional test of its resistance to high pressure water.

A total of six logs were put through this entire cycle with the following results:

1. The amount of asphalt absorbed during the impregnation step varied from 2% to 7% with no apparent correlation with any of the measured variables.
2. Despite the variation, none of the logs failed in the 5+ hr high pressure water immersion test.
3. None of the logs failed in the 1+ hr pipeline circulation test. None broke or lost large chips.
4. Abrasion (wear) losses in the pipeline were 1% to 1.5%.
5. In the post-circulation high pressure water immersion test, several failed in about 1 hr (additional).

Discussion of Results:

Despite what seems relatively short exposure times, these results indicate that coal logs produced by some variation of the above procedure are promising candidates for transporting Powder River Basin coal in a commercial coal capsule pipeline. There are three principal reasons for this statement:

1. Scale-up from 1-3/4" diam tests logs to 20" diam commercial pipeline is beneficial in a key way. The rate of water flow into the log is proportional to the square of the diameter (and length). Thus if a similar log to the above is prepared at the larger diameter, the 5 hour endurance time scales to over 650 hours. This is far greater than the 150 to 175 hours transport time from Wyoming to Missouri. Alternatively the amount of asphalt required for the casing could be a smaller fraction of the total mass of the large log than of the smaller.
2. The 2" diam capsule test pipeline is much more abrasive than large commercial

pipelines. Based on experience with logs in the 2" and 8" pipelines, we believe (but can not prove at this time) that logs that endure for over one hour in the test line will last many hours in the larger pipelines. Actually, none of the test logs failed and probably would endure much longer time in the test line.

3. We have made what appears to be a major improvement in the manufacture of coal logs. Previous logs have all had circumferential cracks throughout the interior of the logs. In failure of any kind (from moisture, tensile tests, etc.) the breakage usually was observed to occur across these cleavage planes. During the impregnation process, it was observed that elimination of air from the interior occurs from these cracks even though they may not be visible on the surface. Furthermore, inspection of fractured logs has shown that a large fraction of the impregnated asphalt is stored in these interior flaws. A new procedure has been developed using molds that split apart to release the log rather than forcing it out with the axial ram. The new logs do not show the circumferential cracks. These logs should require less asphalt sealant and should be inherently stronger than our previous logs.

Project Title: Machine Design for Coal Log Fabrication and Extrusion Research

Principal Investigator: Yuyi Lin, Assistant Professor of Mech. & Aero. Engineering

Duration: May 18-October 5, 1993

Graduate Research Assistant: Guoping Ji (50% of GRA support)

Other students who worked on project: Brent Leonard, Dwayne Bargfrede (undergraduate, approximate 20% of support each)

Purpose of Research:

The main objective of machine design project is to conceptually design a machine for coal log fabrication at commercial mass production rate. Coal log surface treatment equipment and other accessories are also included in the design.

The purpose of coal log extrusion research is to explore the feasibility of extrusion of coal logs with minimum amount of binder or without binder.

Need for Research:

The machine design can suggest desirable improvements for laboratory coal log fabrication process, provide a basis for better estimation of the fabrication rate, and the cost of coal log fabrication in commercial operation.

The fabrication of strong coal logs, so that they can withstand up to 2000 psi water pressure and long distance transportation in pipeline without breakage, with minimum energy and cost, is of vital importance to future commercial success of the coal log pipeline technology. Also, it may be advantageous if coal logs from a fabrication machine can be injected directly into a pressurized, water-filled pipeline, so that the coal logs are not exposed to atmospheric air after fabrication. The underwater extrusion process could reduce adverse effect on extrusion due to gravity, increase the strength of the coal logs, reduce the manufacturing time, and simplify the process of coal log injection.

Work Done Since Last Board Meeting (May 18-Oct. 5, 1993):

(1). New conceptual design of coal log compaction machine. Two design teams, one led by this PI and another one led by Mr. James Remer, were having a design contest from early July to end of August. Each of the team has based the design on a different concept. We completed the conceptual design of a compaction machine based on the capped-mold. For detail, please refer to the design report (23 pages, 5 large drawings).

(2). Manufactured a split mold, tested the concept for future design. From the research results, it seems clear that the compaction mold for commercial coal log fabrication machine should be splittable. We want to verify the idea, and manufactured a two-section split mold (2 inch

diameter). The mold improved the surface damage caused by pushing logs out of the one-piece mold. There are some new problems which need to be corrected in the future design. One of the problem is that the threaded end caps on the mold are difficult to remove.

(3). Extruded binderless coal log at lower moisture content (about 24%). We were able to extrude binderless log at lower moisture content, from 27% to 24%, on our small extruder.

(4). Increased set time improved extruded log quality. From experiments, we found out that the coal log quality can be significantly improved, if extruded logs left in the extrusion die for extended time. This is an expensive way to improve the log quality in commercial operation.

(5). Continued on 5.3" split mold design. The design was started recently. We want to incorporate the lessons learned from the 2 inch split mold design. The design will be finished by the end of the month (October).

(6). Statistical method based experiment sequence designed for identifying best combination of extrusion parameters. See report drafted by Mr. Leonard and Mr. Bargfrede for details.

(7). Measured extrusion temperature and pressure as a time function. Mr. Bargfrede and Mr. Leonard have finished instrumenting and taking temperature and exit pressure data from our small extruder. The temperature profile showed that there is a stable temperature for each extrusion die and coal properties (particle size, brand name of coal). If this temperature is high enough for quality log extrusion, then artificial heating is not necessary. This temperature for North Antelope (Powder River Basin) coal for a specific die is about 120°F.

Plan for Next Two Year (10/1/93-9/31/95):

Machine Design Area:

Although we may never have sufficient research funds to build a complete machine unit, as designed in the recent compaction machine contest, it is highly desirable to complete to some extent the production design of a single unit of the capped-mold compaction machine. It is also highly desirable to build and test some key parts of the design for the following reasons:

(1). The capped-mold design is suitable for testing and experimenting compaction machine design ideas and concepts, in conjunction with the improvement of the hot-water-drying compaction process.

(2). We need to produce some 5 inch logs for the 6 inch pipeline field test within a year. The mold for producing such logs can be incorporated into part of a capped-mold compaction machine design. Experience gained from making 5 inch logs in a designed mold will help to improve the capped-mold design concept.

Based on the above reasoning, I suggest that we carry out the following tasks on machine design in the next two years:

Task 1: Design and manufacture a 5-inch split mold, which should be usable by the end of 1993. This mold is designed for use with the 100-ton ram-type extruder, so that a fixture must be designed for attachment to the extruder. In this mold design, considerations for ease of use, economy and future commercial application are very important. Some lessons learned from the 2-inch split mold should be incorporated into this design.

Task 2: Design a single compaction station, similar to but more powerful than Station G in the capped-mold design report, using hydraulic power to reach a maximum of 250 ton of net compaction force. If we can find a used ram-type extruder available to provide the net force, it probably would cost less to modify this extruder. It is desirable to have this machine ready for use by the end of 1994, or at the latest the end of first quarter of 1995. An 8-inch mold is desirable but not necessary, since scale-up experience from 2-inch to 5-inch logs should be convincing enough for the commercial implementation of an 8-inch coal log machine and process. Some other fixtures, such as clamping device, moving mechanism (for one single station as described in the design report) can be build and tested with some additional manufacturing cost.

Task 3: In the last 3 to 6 months of the two-year period, a detailed, almost production level machine design should be available for future use in commercial projects. I will need more helpers to prepare a detailed, production quality design at this stage.

Table 1. Schedule for Coal Log Fabrication Machine Design

	1993	1994				1995		
	10-12	1-3	4-6	7-9	10-12	1-3	4-6	7-9
Task 1	*****							
Task 2		*****						
Task 3							*****	

Extrusion Area:

Because of the limited power available from the small extruder, any significant back pressure (such as that from a pressure water chamber) will cause the machine to clog. Although the shear effect from an auger-type extruder is helpful in making logs, we may not have enough resources to conduct auger and ram extrusion research simultaneously. Therefore, I suggest that we switch our emphasis to ram-type extrusion process using the 100-ton extruder as quickly as we can. There are many potentially useful and viable ideas that can be tested on this large extruder, including under-water extrusion, modeling of the coal log extrusion process, optimal shape design for extrusion dies, etc. Based on these considerations, I suggest that we carry out the following research work:

Task 1: In the next 3 months, start instrumenting the 100-ton machine with the smallest existing die available. We do not want to build a die since it is too time-consuming. We need to do the instrumentation since the analytical model relies on many experimental data, such as pressure, temperature distribution and history. Mr. Brent Leonard can do the instrumentation, but it would be desirable if he could work with Mr. Deng.

Task 2: Start the literature search for building the analytical model for ram extrusion. There are many publications, for materials other than coal, that can be useful to our work in coal. We need to build our model based on the current knowledge reflected in the literature. This work could be assigned to Mr. Qingwen Deng.

Task 3: The under-water chamber that we built can be modified by adding an adaptor, so that this fixture can be used with this 100-ton extruder. Mr. Brent Leonard can do the adaptor design. It is desirable to have the design and manufacture of this adaptor finished by the end of the year. So far, the water chamber is the only way we can apply variable back pressure to the extrusion process. There are other potential advantages to warrant the continuation of the under-water extrusion experiment.

Task 4: When the instrumentation and under-water fixture are completed, a statistical based experiment (Taguchi method) can be designed for parameter investigation. This work can complement the analytical work. It is desirable to have the optimal set of parameters identified, and the analytical model verified by the end of 1994, or early 1995.

Task 5: Have a conceptual design for an optimum extrusion machine. Thus we may be able to report to our sponsors by the end of the two year period, we have an alternative process available for commercial production of coal logs, the piston extrusion process.

Table 2. Schedule for Studying Ram Extrusion

	1993	1994				1995		
	10-12	1-3	4-6	7-9	10-12	1-3	4-6	7-9
Task 1	*****							
Task 2	*****							
Task 3		*****						
Task 4				*****				
Task 5							*****	

Project Title: Slurry Effects on Hydrodynamics of CLP
Principal Investigator: James Seaba, Assistant Professor of Mech. & Aero. Engineering
Duration: 7/1/93 - 9/30/93
Graduate Research Assistant: Gang Xu (0.5 person/yr)
Visiting Scholar: Mr. Yu Lin (0.5 person/yr)

Purpose of Proposed Research:

To study the feasibility of using coal slurry in place of water as the transporting medium in the CLP.

Need for Research:

The replacement of water with coal-water slurry increases the density of the carrier fluid and decreases the velocity required to transport the coal log. The lift-off velocity of the coal log during transport can be reduced by up to 62% using coal slurry, assuming the lift-off equation derived using water is also valid using coal slurry. Benefits of using coal slurry as the transporting medium for coal log transport are: water consumption is reduced 50% by weight, mass flow of coal per unit volume pipe is increased, and possible reduction of wear of the coal log due to lower transportation velocities. Current research in the manufacturing of coal logs indicates a trend toward high density, high compressive strength logs, for resistance against abrasion. Transporting high density logs (specific gravity = 1.3) makes the coal slurry investigation an important aspect of capsule pipeline transport.

Slurry effects on coal log transport is an exploratory investigation to access the effects of density and rheology on capsule pipeline transportation. These aspects of capsule transportation have not been explored previously, and may expand the capsule pipeline technology to other areas of solid bulk transportation.

Research Progress:

The experimental approach to investigate the feasibility of using coal slurry in place of water can be divided into three parts; first, the transport of capsules in water to compare with previous work. This step will also provide confidence in our new experimental facilities. Secondly, study the transport of coal slurry only and compare with current slurry models. The slurry used in this project was donated by Williams Technologies from the Black Mesa Pipeline. The final phase of this experiment was to assess the transport of capsules (specific gravity, $S = 1.3$) in the commercial coal slurry. All three parts of this experiment were completed this quarter for aluminum capsules with aspect ratios (a) of 2 and 4 in a 2-inch pipe. Details of the results are presented in Gang Xu's Thesis.

Capsule flows in pure water

In this study, the capsule pressure gradient is directly measured for the first time. The experimental results of the capsule pressure gradient for both aspect ratios show a peak at a velocity between 5 and 6 ft/sec, which corresponds to the macro lift condition of the capsule. The maximum capsule pressure gradient for the long capsule ($a=4$) occurs at a higher velocity than the short capsule. This trend agrees with the theoretical prediction relative to the microlift regime.

The total pressure gradient shows an increase in pressure gradient with a decrease in capsule aspect ratio. This agrees with the results of Richards (1992). The velocity relationship between capsule velocity and bulk fluid velocity is shown to be independent of the aspect ratio, which is again matched with that of Richards (1992).

The experimental system can not provide enough bulk fluid flow rate for the longer capsules ($a=4$) to reach the calculated lift-off velocity. However, for the small capsules, the experimental data agrees with the lift off formula.

The theoretical model matched the capsule velocity versus bulk fluid velocity results extremely well. However, the model has difficulties predicting the total pressure gradient, particularly at the point where capsule velocity begins to exceed bulk fluid velocity. Overall, the new test facility did an outstanding job measuring pressures, capsule velocities and clearance, and fluid velocity and presenting the data graphically in the new data acquisition system.

Slurry flow only

The coal water slurry pressure versus flowrate was compared to pure water, the moody diagram, and three slurry models as shown in Figure 1. The slurry has a greater pressure loss compared to water.

Figure 1. Pressure drop of water and slurry in a 2-inch pipeline

Capsule flows in coal-water slurry

The additional gradient due to the capsule in coal-water slurry was less than 1% and constant over a large bulk velocity. Comparing capsule transport in water and slurry, it was observed that at most bulk flowrates the water had slightly less pressure drop than slurry. However, at some flow rates (approximately 6 ft/sec) the pressure drop was nearly the same as shown in Figure 2. The calculated lift-off velocities for capsules with $a=4$ and $S = 1.3$ are 10.5 ft/sec and 7.3 ft/sec for water and slurry, respectively. Figure 2 represents a 2-inch pipe with $a=4$, the $a=2$ case showed the same trends.

Figure 2. Pressure drop for aluminum capsules ($S=1.3$) in water and slurry in a 2-inch pipe

The angle of attack was greater at all flow rates using coal slurry as the transporting medium compared to water. The short capsules ($a=2$) showed a significant increase in the angle of attack at the calculated lift off velocity. However, the long capsules ($a=4$) did not reveal a well defined increase relative to the angle of attack. The coal-log-in-water case revealed no well defined increase for both length capsules, unlike Richards (1992) where a dramatic increase was observed. Further work needs to be done, both in slurry and water to determine if a sharp increase in the angle of attack exists at the lift off condition. An increase in the angle of attack is observed for all cases at the calculated lift off condition.

The rheology of the coal slurry fits the Bingham plastic model. The yield stress τ_y and Bingham plastic viscosity η were 0.145 dynes/sq. cm and 2.9 cps, respectively. Degradation of the slurry occurred after 12 hours of continuous run time, after this time the slurry was replaced.

In summary, to transport coal logs in slurry has its potential advantages compared to water. The optimum operating range of a slurry is broad since little additional pressure loss is associated with the capsule. Further testing of real coal logs relative to their deterioration may affect the operating range. Transporting capsules in slurry can be at lower velocities compared to water. The scale up from the 2-inch pipeline is not clear. Further work is required to determine particle-coal log interaction effects, bed flow effects and how these relate to the scale up version of CLP. But other problems, such as dewatering of slurry, coal log clogging by slurry, restart, contamination of slurry to pipeline facilities, etc. needs to be assessed.

Recommendations for future work using slurry

In order to fully explore the benefit and the possibility of using slurry to transport coal log, more work needs to be done. Based on present knowledge of this study, several recommendation on future work is given as follows:

1. Extensive data of capsule flow in slurry, with different aspect ratio, diameter ratio, specific density, slurry concentration, PSD, etc. should be collected.
2. Capsule-particle interaction effects needs to be assessed.
3. A scale-up method needs to be determined to extend the experimental results for commercial use.
4. Modify the existing experimental setup to minimize valve lockup, leaks, etc.

CAPSULE PIPELINE RESEARCH CENTER

Quarterly Report for Period 7/1/93-9/30/93

Project Title: Hydrodynamics of CLP

P.I.: Dr. Henry Liu, Professor of Civil Engineering

Research Assistants: C.C. Cheng, and X. Huang

Purpose of Study:

Explore remaining hydrodynamic problems important to the application of CLP. The two main areas studied during this period include coal log wear in pipe and use of polymer to reduce drag.

Work Accomplished During the Period:

(A) Coal Log Wear in Pipe:

The various causes of coal log wear in pipe have been established. They include (1) erosion of coal log by water, (2) abrasion by coal particles in water, (3) abrasion by rough joints, (4) abrasion by jet pumps (only in laboratory systems), (5) abrasion by pipe bends, (6) impact of coal logs on partially closed valve, (7) impact (collision) between coal logs, (8) impact due to water hammer.

Exploratory experiments on erosion by water have been conducted in a 2-inch-diameter transparent (Plexiglas) pipe with coal logs held stationary in the pipe (by a stopper), and with water passing around the logs. The tests were carried out at various water velocities, and no coal log weight loss was measurable even at the maximum bulk velocity of 7 ft/sec (annular velocity of 35 ft/sec) over a period of 3 days. Based on this study, it is tentatively concluded that erosion of coal logs can be safely neglected in most if not all cases.

A new phenomenon was discovered during the erosion tests. The logs stopped by the stopper, which is a small rod protruding into the pipe through the bottom of the pipe,

tilt up in a nose-down position due to the drag and lift moments generated by the flow. This has implications on capsule jam and must be considered carefully. A set of experiments were conducted to determine the tilt velocity and to compare it with that predicted from theory. The comparison was reasonably good.

It was noted that the wear of coal logs moving through a pipe increases with increased coal particles in the pipe, especially large particles. This is caused by the lodging of such particles between coal logs and the pipe wall, which generates abrasion. This kind of wear (abrasion) will be studied in more detail later.

It was found that a single bad joint (discontinuity) caused by misalignment of pipe or mismatch of pipe cross-sectional geometry causes serious abrasion to coal logs. In contrast, wear of coal logs is minor when all joints are smooth. Based on this finding in the laboratory test, it is expected that rough joints will be the greatest source of coal log wear in commercial pipelines. How to make smooth joints in commercial coal log pipelines is vital to the success of the CLP technology. More studies on the effect of rough joints are currently underway; the results will be reported in the next quarterly report.

Another type of coal log wear studied briefly is that due to water hammer. A coal log was suspended by the flow in the pipe at the lift-off velocity of 7.5 fps. A valve was suddenly closed, and a water hammer pressure rise of the order of 120 psi was generated. The log was subjected to the water hammer twice and no damage to the log was observed. Although this result is encouraging, it must be realized that stronger water hammer exists in commercial pipe than in the short water pipeline in the laboratory. Moreover, in a commercial long CLP, the logs must be subjected to many cycles of pressure fluctuations rather than only a few. Therefore further study in a pipe with stronger water hammer for many cycles is required to better simulate the field condition.

(B) Drag Reduction by Using Polymer

A 2-inch test loop made of Plexiglas pipe has been constructed for the test. Most of the time spent during this period was to get the loop ready, calibrate the flow meters, pressure transducers and electromikes, fabricate the plastic logs to be used in the tests, and run preliminary tests with water only and with water and polymer (Polyox Water-Soluble Resins, Union Carbide Company) but without capsules.

The data for water only compared well with the Moody diagram for smooth pipe. The data for water with polymer (but without capsules) showed sudden decrease in drag and increase in flow rate through the test loop.

Work Proposed for Next Quarter:

(A) Coal Log Wear in Pipe:

Focus on abrasion due to rough joints. Use the 2-inch Plexiglas pipe loop and install artificial rough joints of two different roughness heights (1 mm and 2 mm). Compare the results with those based on smooth joints, and with those tested in a similar loop made of steel pipe. Work on a theory to predict coal log wear due to rough joints. With such a theory, abrasion results can be scaled up for predicting coal log wear in large-diameter commercial pipeline.

(B) Drag Reduction by Polymer:

During the next quarter, tests with polymer and capsules will be conducted over the concentration range of 1 to 50 ppm. The effect of polymer on drag reduction and on the behavior of capsules will be determined as a function of concentration. Degradation of polymer with time will also be determined.

Capsule Pipeline Research Center

Quarterly Report

(Period Covered: 7/1/93-8/30/93)

Project Title: Unsteady Flow in Capsule Pipeline

P.I.: Dr. Charles Lenau, Professor of Civil Engineering

Research Assistants: (1) Majed El-Bayya and (2) Jianping Wu

Purpose of Studies: (1) To develop a methodology for analyzing unsteady flow and hydraulic transients generated by the operation of coal log pipelines. (2) To study the hydraulic transients associated with the operation of a pump bypass system and an injector system.

Work Accomplished During the Period:

(1) Unsteady Flow of Coal Logs

El-Bayya continues to work with his experimental apparatus for studying hydraulic transients in a coal log pipeline. The purpose of these experiments is to allow us to check the validity of the theoretical model developed to study unsteady capsule flow (El-Bayya 91, Lenau and El-Bayya 92). As reported in the past El-Bayya has had number of experimental problems.

To get around these problems a slightly different experimental procedure is being followed. The original plan was to release a capsule/s at the upstream end of the system, to accelerate it/them until it /they reached steady state velocity and to quickly close the downstream valve. The pressure was to be measured with a pressure transducer near the valve. The new procedure is to release the capsule/s near the upstream end of the system and to track the displacement of the capsule/s with six photo cells as it/they accelerates to steady state velocity. At the same time the pressure is measured near the downstream end and near the midpoint of the system with pressure transducers. There is no valve closure at all (no valve at all).

The new experimental procedure has a number of advantages. The data recorded permits the tracking of capsule displacement and capsule velocity as it accelerates through the system. At the same time the downstream and midpoint pressures are measured. This give three different quantities to compare with the theoretical model. Because there is no valve closure, the pressure transients are smaller the upstream head on the system. Thus there is no column separation and the pressure transducers can have a much smaller maximum allowable pressure. Using a pressure transducer with a lower maximum allowable pressure permits the accurate measurement of smaller pressure transients. The theoretical model predicts a very distinctive pressure signature during a brief time period after the capsule release. The more sensitive pressure

transducers permitted by the new experimental procedure allows this pressure signature to be measured.

At the present time El-Bayya has enjoyed some success verifying the theoretical model. Many more experimental runs are needed. Currently, the most difficult problem is achieving a smooth capsule release.

(2) Pump Bypass and Injector Systems

Since last reported Jianping Wu has made considerable progress in analyzing the transients associated with the operation of the injector and pump bypass systems. Both the pump bypass and injector systems are associated with a very high head increase (4,615') which permits approximately 40 miles between bypass systems or between the injection system and the first bypass system.

The injector system consisted of a high head driver pump and four low head centrifuge pumps which serve to draw the coal logs into four locks at a speed of approximately 2.67 fps. Each lock contains 1000' of loading pipe capable of holding several hundred coal logs. Normal operation of the injector call for pumping the coal logs from one lock into the main pipe at the same time the other three locks are being filled with coal logs. After a lock is emptied of coal logs valves are switched so that coal logs are pumped from a second lock and at the same time the lock just emptied begins to fill with coal logs. The injector system operates in a cyclic manor so that one lock is always being emptied of coals logs while the other three are being filled with coals logs.

Difficulties with the proposed operation of the injector system were soon discovered. The main problem was that during valve switch-over the high pressure portion of the injector system was connected to the low pressure portion. This cross connection caused severe discharge transients in the four locks. The original injector configuration investigated called for a single low head pump to operate the four locks. By placing a pump in each lock only one of the four locks would be cross connected during valve switch-over. The discharge transients in the remaining lock was controlled by completing one set of valve adjustments before starting other valve adjustments so that the high and low pressure portions of the injection system were never cross connected. However, to do this required bringing the flow in the lock (next to be emptied) almost to rest and then acceleration the flow after valve switch-over.

Although much less severe than the original problem described in the previous paragraph bringing the flow in the lock to near zero before valve switch-over created other problems. First, bringing the flow to rest caused discharge transients that were not particularly large but didn't dampen out quickly enough. This problem was solved by three-step valve stroking strategy that maximized transient energy dissipation just before complete valve closure. Second, after a lock had been emptied of coal logs and valve switch-over was complete the flow was almost at rest. The low head pump used to draw the coal logs into the lock required too much time to accelerate the flow. This last problem was solved by increasing the shaft speed of this pump until the proper discharge was reestablished.

Work To Be Accomplished Next Period:

1) Unsteady Flow of Coal Logs

During the next quarter El-Elbayya should continue to data and analyse data. This project will probably continue into the second quarter of next year.

(2) Pump Bypass and Injector Systems

During the next quarter Wu will continue his analysis of injector and pump bypass systems with capsules. He hopes to complete the project and graduate in December 1993.

References:

El-Bayya, M., 1991, "Transient Flow in Hydraulic Capsule Pipeline," M. S. Thesis, Department of Civil Engineering, University of Missouri-Columbia.

Lenau, C. W. and El-Bayya M. M., 1992, "Treatment of Unsteady Flow through Capsule Pipelines: Capsule-Water Interaction," International Conference on Bulk Materials Handling and Transportation: Symposium on Freight Pipelines (Wollongong, Australia), Vol. 1, preprints of papers, The Institution of Engineers, Australia.

Capsule Pipeline Research Center Quarterly Report

(Period Covered : 5/1/93 - 8/31/93)

Project Title : Automatic Control of Coal Log Pipeline System

Principal Investigator : Satish S. Nair, Asst. Professor of Mechanical and Aerospace Engrg

Graduate Research Assistants : C. Y. Shieh, D. Sun, and J. Wu

Purpose of the Research :

To study, design, test, and improve an automatic control system needed for reliable operation of coal log pipeline systems. To model the system dynamics as well as the interactions between the pumps, valves and the capsules for effective control design and system sizing.

Work Accomplished During the Period :

Two students, C-Y Shieh and D. X Sun completed their MS Reports the details of which are as given below :

Shieh, Choung-Yaw, "Computer Control of a Small Scale Pipeline System," August 1993.

Sun, De-Xiang, "Design of Certain Mechanical Subsystems for an Automated Capsule Pipeline," August 1993.

These reports dealt with two separate issues concerning the computer controlled testbed pipeline system. One dealt with the computer system, interfacing, control algorithm and program development aspects while the other pertained to the mechanical design aspects for several subsystems. Both the studies provided considerable experience with several issues regarding the design of such systems at a large scale level, which was the main objective in each case.

Shieh's report dealt with computer hardware configuration and software design issues, including relevant literature review ; a comparison of distributed control architectures using PLCs, RTUs and microcontrollers ; a comparison of SCADA options ; software design for real-time control and monitoring ; implementation of multi-tasking control for simulating actual injection system functioning; incorporation of safety features such as controlled startup and emergency shutdown ; development of diagnostic routines; and finally, extensions to commercial pipeline systems and future research.

Sun's report included mechanical design issues such as design, implementation and testing of Y-joints (4) ; design, implementation and testing of a high performance diverter ; design, implementation and testing of prebent pipe sections ; two proposed designs for train separator - electromagnetic brake and flow by-pass types ; a proposed design for automatic injection subsystem ; observational studies using the computer controlled testbed system based on upwards of 50 runs ; extensions to large scale systems and future research.

Both studies, in addition to reporting the improved designs and projected use in commercial pipelines, also documented carefully all details regarding the test bed system which included mechanical drawings, control program documentation, specification sheets for all sensors and proposed computer configuration, etc. This provides an excellent source for developing operational manuals, both hardware and software, at a later stage of the project where the test bed system is envisaged to be used for training purposes.

J. Wu continues to work on the dynamic simulation study as detailed in the previous report and is making satisfactory progress on the computer modeling studies currently under the supervision of Dr. Lenau.

Work Proposed for the Next Quarter :

1. Small-Scale Pipeline System (1-inch test loop)

Hardware

- Fabricate and test a train separator using a stopper with by-pass bleed type design.
- Study the effect of capsules of varying densities and speeds on the following : separation effect within trains and between trains, etc.
- Investigate whether instrumenting the pipeline with velocity and pressure sensors is necessary (low priority).
- Investigate other test requirements for the pipeline, e.g. erosion testing etc. (low priority)
- Automate the injection system to simulate at-least 3-4 injection cycles, and if continuous runs are required in a closed loop, redesign the injection system.(low priority)

Software

- Select the appropriate unit for local monitoring and control. Under consideration are RTUs, PLCs and regular PCs. Acquire the unit and interface it with the 486 PC.
- Select the communication protocols to be used for the system.
- Select the SCADA software to be used for display and other functions, install and test it.

2. Large-Scale Commercial Prototype Pipeline System

- initiate component sizing studies for a commercial prototype pipeline system based on a typical scenario.
- develop, test, and implement control hardware and software for the pipeline.
- investigate the appropriate sensors needed for the coal log case, by first testing in the small-scale pipeline in the hydraulics lab.
- investigate how commercial oil/gas pipelines operate currently from the system design and control viewpoint. The issues include :
 - component selection (e.g. pump) and sizing
 - control hardware, strategy and monitoring
 - sensing
 - pipeline integrity monitoring and inspection
 - documentation and training issues - i.e. training manuals etc.
- study the possibility of developing an intelligent pig for coal log pipeline systems.
- investigate whether any issues could be studied by automating the existing 8-inch pipeline, and, if needed, automate the 8-inch pipeline.
- study reliability issues and safety features in detail for the pipeline.
- develop design and training manuals for the large-scale pipeline.

The objectives in both items 1 and 2 will be pursued concurrently, with 2 graduate students. Item 1 objectives are expected to take 1 year to complete while those in item 2 should take 2 years. Developmental work of this kind requires qualified graduate students with solid background rather than beginners, for efficient and timely completion. The students should also have working knowledge of computer interfacing and control hardware and software.

Capsule Pipeline Research Center

Preliminary Quarterly Report

(Period Covered: 7/1/93 to 9/31/93)

Project Title: **Legal Aspects of CLP**

P.I.: Dr. Peter N. Davis, Isidor Loeb Professor of Law

Research Ass'ts: Pat Sullivan (until 8/23/93), James Kelly, Eileen Petito (after 8/27/93)

Purpose of Study: To explore legal issues involved in commercialization of CLP, including eminent domain powers for right-of-way and water rights acquisition, nature of water rights acquired by voluntary transfer, right to cross railroads, conversion of existing pipelines, pipeline waste disposal, environmental assessment, etc.

Work Accomplished During the Period:

Research conducted during the period:

- (1) *State "taking" definition statutes.* Conducted nationwide research on texts of proposed state "property rights" statutes which attempt to define when a compensable taking occurs. These statutes could have a significant impact on land use control ordinances generally (such as, flood plain & wetlands zoning and historic preservation ordinances) and specifically on state water transfer and export permit statutes. Research was completed, but analysis was not; the incomplete manuscript was submitted by the author to the MISSOURI ENVIRONMENTAL LAW & POLICY REVIEW in August. In September, the *Review* accepted the article and the author will complete the article during Fall 1993. The article contains general analysis of the impact of "property rights" statutes on regulation. Particular analysis determining the impact of those statutes on regulations affecting coal pipelines (such as, water anti-export and transfer regulations) will be done by Peter Davis thereafter. [Pat Sullivan]

- (2) *Operation of pipelines by railroads.* Began research on authority of railroads under Interstate Commerce Act and state railroad and pipeline statutes to construct and/or operate pipelines. [Jim Kelly]
- (3) *ETSI Pipe Line v. Railroads litigation.* Continued seeking additional information on the consent decrees agreed to by the defendant railroads; in particular, we are seeking to determine if the railroads agreed to allow coal pipelines to cross their rights-of-way. [Jim Kelly]
- (4) *Authority of Indian Tribes to convey their water rights to non-Indians.* Began research on this topic, since several tribes in recent years have considered such sales. Indian water may be a significant source for pipeline water. [Jim Kelly]

Work Proposed for Next Quarter:

Research work:

- (1) Continue legal research on topics 2-4, above.
- (2) Complete the analysis of proposed state "property rights" statutes and their application to coal pipeline legal issues. [See topic 1, above.]
- (3) Begin work on research into general authority of federal agencies to authorize diversions from federal reservoirs. Although this topic is inspired by *ETSI Pipeline Project v. Missouri*, 108 S.Ct. 805 (1988), this research will not address site-specific issues, such as Missouri River diversions.
- (4) Begin work on typical environment issues discussed in Environmental Impact Statements prepared under the National Environmental Policy Act for pipeline construction projects in the midwest.

Publication work:

- (1) Coordinate manuscript editing of Pat Sullivan's article on state "property rights" statutes, which has been accepted for publication by the MISSOURI ENVIRONMENTAL LAW & POLICY REVIEW.
- (2) Continue preparation of law review article based on Florida conference paper Davis, Cress & Sullivan, *Legal Aspect of Coal Pipelines in the United States - Preliminary Findings* (Apr. 1993).

Key Results of Recent Work:

- (1) Two types of state "property rights" statutes have been proposed to define when a compensable "taking" occurs. The "weaker" statutes require a taking analysis to be conducted before enactment to enable legislators to assess the possible costs of compensation the state and municipalities might have to pay. These statutes do not attempt to define when a compensable taking occurs. The "stronger" statutes provide that a compensable taking occurs whenever a 50% reduction in property values results from the regulation.

At this intermediate stage of the research, no attempt was made to determine the constitutional validity of either type of "property rights" statute or to assess their application to coal pipeline legal issues. The application of these statutes to regulations affecting coal pipelines will be done in the next quarter. [See "work accomplished", topic 1, above.]

Publications:

None.

Unpublished Research Reports:

- (1) Sullivan, Pat, untitled paper on state "property rights" statutes (Aug. 1993). 31 pp.

file: rpt993

CAPSULE PIPELINE RESEARCH CENTER
QUARTERLY REPORT

(Period Covered: 7/1/93 to 9/30/93)

Project Title Slurry Impregnation of Dry Coal Logs

Principal Investigators Thomas R. Marrero
Associate Professor of Chemical
Engineering

Graduate Research Assistant Rebecca J. Smith

Purpose of the Research

To develop a method to include coal fines in a coating around dry coal logs in order to reduce the amount of more costly coating material and to reduce the permeability of a coal log coating.

Work Accomplished

Research continued to focus on a coal/water slurry; however, results indicate that the absorption of slurry water by the dry log during impregnation was damaging the log structure. Attempts to lower impregnation pressure, alter the weight percent solid in the slurry, decrease particle size in the slurry, and lower the impregnation time still resulted in damaged logs. After deciding that the water was the major cause of the damage, efforts were made to find a new slurry carrier fluid. The fluids were judged by several criteria:

1. Possible reaction with coal
2. Hydrophobic characteristics
3. Suitable viscosity
4. Cost
5. Safety Hazards
6. Suitability as a fuel component

Two fluids were selected: stearic acid and cut back asphalt.

At room temperature, stearic acid is a white, waxy solid. Stearic acid is an 18 carbon acid with a carboxyl group and is essentially insoluble in water. Cut-back asphalt is a liquid at room temperature and contains about 20 percent of a fuel oil.¹

¹ The term cut-back asphalt refers to a liquid petroleum product produced by fluxing an asphaltic base with suitable distillates.

A new impregnation process has been developed that allows for heating the slurry. A heating mantle is placed below a glass reactor, and the reactor is connected to a vacuum pump. A vacuum of up to 26 in. Hg can be obtained. The impregnation process involves pulling a vacuum for a specified amount of time and then allowing the log to soak in the slurry.

A series of experiments was started to examine the following factors of impregnation.

1. Compaction temperature of the coal log
2. Weight percent solid in the slurry
3. Impregnation pressure
4. Impregnation time

Both Powder River Basin and Illinois coal are being used. Possibly due to its lower inherent moisture, the Illinois coal logs are performing better in the water absorption tests. One Illinois log has been in the 500 psi water absorption test for several days with weight gain less than one percent.

The coal is dried at 105 °C until the moisture content is below three percent.

Two compaction temperatures are being examined, 150 °C and 200 °C. Compaction at 200 °C frequently produces logs that have broken ends. The 150 °C logs exhibit more circumferential cracks. The 150 °C logs absorb more slurry possibly due to the presence of these cracks. These logs generally fail within a couple of hours in the 500 psi water absorption test.

The stearic acid aids the adhesion of fine coal particle to the surface of the logs to further reduce water absorption.

Presently, the main factor that reduces log quality is the circumferential cracking resulting from the compaction process.

The trials with cut back asphalt indicate that the carrier fluid must be solid at room temperature, otherwise water will penetrate the log during the water absorption tests.

Tests with both stearic acid and cut back asphalt have been completed.

Additional tests are being made to determine the feasibility of making coal logs from samples of coal fines and raw coal provided by Souther Company Services. These feasibility tests should be completed by the end of this reporting period.

Work Proposed for the Next Quarter

During the next quarter, tests will be initiated using coal fines from the Syncoal Process (a process under DOE development to upgrade sub-bituminous coal mined in Montana)

to impregnate coal logs made from the upgraded coal. The Syncoal product is relatively dry with less than five percent moisture. During the Syncoal process approximately 10 percent of the feed coal is lost to provide an economic offset to the processing costs. The proposed tests will include the measurements of the effects of particle size, impregnation pressure, and the use of a locally available asphalt as a binder.

Capsule Pipeline Research Center
Quarterly Report

(Period Covered: 6/1/93 - 8/30/93)

Project Title:	Economics of Coal Pipelines
Principal Investigator:	Henry Liu
Co-Investigator:	James S. Noble
Research Assistant:	Robert Zuniga
Purpose of Studies:	(1) Update and improve the CLP economic report for use in the 1995 version. (2) Investigate railroad costs models and structures for comparison with pipeline economics.

Work Accomplished During the Period:

1. Update and improve the CLP economic report for use in the 1995 version.

The economic report completed and published by the Center in January 1993 is the most current attempt to provide Coal Log Pipeline (CLP) cost estimates. Some of the cost assumptions used in the report will be updated in the future 1995 version to reflect the new cost of improved CLP technology. The report included a computer program with over 1000 lines of code that generated cost estimates based upon 32 user defined CLP operating scenarios. Robert has been refining the program to incorporate a more user friendly interface so that a sensitivity analysis and update of the CLP cost model can be performed with relatively little effort.

2. Investigate railroad costs models and structures for comparison with pipeline economics.

The CLP will compete directly with railroads in the transport of coal. To analyze the comparative merits of the CLP as an alternative coal transport mode, an understanding of the cost and price structure of railroads is

required. The analysis will provide anticipated short-term and long-term rail rates that will be incorporated into the 1995 version of the economic report. Robert has been studying railroad cost methods from sources including the Office of Technical Assessment (OTA), and the Interstate Commerce Commission (ICC).

The 1993 CLP economic report was modeled similarly to the OTA's approach to coal slurry pipelines. The OTA also analyzed railroads within their report for a comparison evaluation of coal transport. Robert has outlined their model which will be used as an estimate of short-term and long-term rail rates. The ICC currently provides two computer versions (personal computer and mainframe) of their uniform cost model approach for determining rail rates. Both version are based upon a historical cost approach. Included with the mainframe version is the source code used to determine railroad cost and rate estimates along with five years of cost data for Class I Railroads in the United States. We have just received the programs and are in the process of installing the files on the mainframe.

Robert attended a seminar entitled "Controlling the Cost of Railroad Contracts." The seminar offered an opportunity to learn about current methods used within the transportation industry on determining railroad costs. Issues covered in the seminar included: contract structuring, defining the shipper's and railroad's long term price objectives, increasing competition in commodity transport, contract index issues, railroad cost analysis including how costs are calculated (with historical and future trends), railroad productivity, and other relevant investment decisions.

Exposure to railroad and shipper concerns will aid in railroad future cost and price estimates.

Work To Be Accomplished Next Period:

1. Update and improve the CLP economic report for use in the 1995 version.

Robert will assist in a sensitivity analysis of the existing 1993 cost model with respect to the discount rate, inflation rate and energy cost. Separately, the UMC/OTA model will be compared with the pipeline industry model (Williams Technology, Inc.) and the Electric Power Research Institute (EPRI) cost model. The similarities and differences between models will be pointed out.

2. Investigate railroad costs models and structures for comparison with pipeline economics.

The computer programs received by the ICC will be initiated on the mainframe computer. Future work will include using this model as another estimate of rail rates.

References:

1. A Technical Assessment of Coal Slurry Pipeline, Office of Technical Assessment (OTA), U.S. Congress, Washington, D.C., March 1978.
2. Liu, Henry, Zuniga, Robert and Richards, James L. Economic Analysis of Coal Log Pipeline Transportation of Coal, Capsule Pipeline Research Center Report No. 93-1, University of Missouri, January 1993.
3. Uniform Railroad Costing System Phase II Computer Program, Bureau of Accounts, Interstate Commerce Commission, Washington D.C., October 1989.

DATE

FILMED

9 / 15 / 94

END