**FUSION
RESEARCH
AT
GENERAL
ATOMICS**

ANNUAL REPORT

**OCTOBER 1, 1991
THROUGH
SEPTEMBER 30, 1992**

FUSION TECHNOLOGY DEVELOPMENT

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced
directly from the best available copy

Available to DOE and DOE contractors from the
Office of Scientific and Technical Information
P.O. Box 62
Oak Ridge, TN 37831
Prices available from (615) 576-8401,
FTS 626-8401

Available to the public from the
National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Road
Springfield, VA 22161

FUSION TECHNOLOGY DEVELOPMENT

ANNUAL REPORT TO THE U.S. DEPARTMENT OF ENERGY

OCTOBER 1, 1991 THROUGH SEPTEMBER 30, 1992

by
PROJECT STAFF

Work prepared under
U.S. Department of Energy
Contract DE-AC03-89ER52153

GENERAL ATOMICS PROJECT 3469
DATE PUBLISHED: FEBRUARY 1993

GENERAL ATOMICS

MASTER

CONTENTS

1. DEVELOPMENT AND TECHNOLOGY OVERVIEW	1
2. REACTOR DESIGN STUDIES	3
2.1. Overview and R&D Needs	3
2.2. Project Directions	3
2.3. Engineering Innovation/Fusion Power Core Design	4
3. RF TECHNOLOGY	11
4. PLASMA FACING COMPONENTS	15
4.1. Overview	15
4.2. Integral Exposure Experiment	16
4.3. DIMES Sample Changer System	16
5. FY92 PUBLICATIONS	19

FIGURES

1. The nested-shell blanket concept for ARIES-IV	6
2. Fabrication concept for the nested-shell blanket structure	7
3. Schematic of the test setup for a low power fast ferrite hybrid tuner on DIII-D	12
4. Response time in reduction of the magnitude of the reflection coefficient at the output generator during a DIII-D discharge	13
5. DIMES mechanical system	17

1. DEVELOPMENT AND TECHNOLOGY OVERVIEW

In FY92, the General Atomics (GA) Fusion Group made significant contributions to the technology needs of the controlled fusion power program. The work was supported by the Office of Fusion Energy, Development and Technology Division, of the U.S. Department of Energy. These studies included work on Reactor Studies, RF Technology, and Plasma Facing Components.

The efforts by GA are based on the recognition that the implementation of controlled fusion as a major energy source requires significant technology development. This is needed to support both near-term experimental efforts and the eventual construction of fusion reactors. We continue to be committed to the development of fusion power and its commercialization by U.S. industry.

2. REACTOR DESIGN STUDIES

2.1. OVERVIEW AND R&D NEEDS

The goal of reactor design studies is to provide critical assessment of the projected performance of fusion experiments, reactors, systems and components; to develop potential solutions to the key technical problems uncovered in these assessments; and to offer recommendations for fusion research and development that could help resolve these problems and lead to improved fusion system performance. This activity helps to define the goals and R&D needs of the fusion program, and thus adds focus to near-term activities.

During FY92, GA continued to play a lead role in the Advanced Reactor Innovations Evaluation Study (ARIES) directed by Prof. Robert Conn of UCLA. This was the last year of a five-year study focused on different advanced embodiments of tokamak reactor design, with emphasis on innovation, attractiveness, safety, and economics. Within the ARIES project, GA was responsible for the project operation, with Dr. Kenneth Schultz acting as the Deputy Project Director for Operation. We are supporting the design, analysis, and evaluation of high performance fusion power core components such as divertors, first walls, blankets and shields, including detailed neutronics evaluations and safety designs. We also are continuing to provide senior plasma physics personnel to integrate the latest tokamak experimental results into the ARIES study.

2.2. PROJECT DIRECTIONS

The ARIES study has developed four different "visions" of a fusion power reactor based on the tokamak concept. During the first-year scoping phase of ARIES through February 1989, we identified the major characteristics of the visions. In the second year, a more detailed conceptual design of the first vision was developed. The third year was used to complete the first ARIES design and initiate the second and third ARIES designs. The ARIES-III design was completed in the fourth year and the ARIES-II and IV designs were continued. The fifth year has been used to complete the ARIES-II and IV designs.

During FY92, we supported the ARIES-II lithium breeder self-cooled Vanadium alloy structure design; and completed the ARIES-IV toroidal flow, helium-cooled, Li_2O) solid breeder and SiC-composite structure design.

2.3. ENGINEERING INNOVATION/FUSION POWER CORE DESIGN

2.3.1. ARIES-II DESIGN

Over the past year, GA has supported the ARIES-II lithium breeding, self-cooled, vanadium-structure reactor design. Our major responsibilities were to study the recycling of the vanadium alloys, safety design issues, and concepts for the balance-of-plant.

It was determined that vanadium alloys appear to be strong candidates for recycling; the material can probably be re-processed and used several times before the build-up of high activation isotopes mandates deep geologic burial.

We also applied the techniques of the safety design approach that GA had devised in the Reversed Field Pinch TITAN reactor study (a lithium self-cooled design) to this ARIES-II design. The safety features of the confinement building, the inert gas cover, and the lithium drain tank are directly transferable features. By adopting this approach, both with respect to the reactor and to the balance-of-plant, the ARIES-II design was rated as a Level of Safety Assurance 2 (LSA-2) passive safety design.

2.3.2. ARIES-IV DESIGN

During FY92, we completed the ARIES-IV reactor design by working in the areas of materials selection, thermal hydraulics and configuration design of the blanket and divertor, safety, and balance-of-plant design. Our design improvements were based upon the reference design selected for ARIES-I and our goal was to improve upon the Level of Safety Assurance 2 (LSA-2) rating achieved in that study.

For the blanket design, the key change was the use of Li_2O to replace the highly activated Li_2ZrO_3 as the breeding material. In the divertor design, we adopted the gaseous divertor concept which led to lower surface heat flux (around 5 MW/m^2) and reduced electron temperature at the divertor surface. This permits the highly activated tungsten coating originally proposed for the divertor surface to be eliminated.

These material changes were then used as inputs for the safety design evaluation performed by our collaborators at EG&G. Based upon this new materials selection, we achieved the goal of obtaining a rating of LSA-1; i.e., an inherently safe reactor design.

In the following writeup, more details of the configuration design for the ARIES-IV toroidal-flow blanket and an engineering analysis on this proposed module are provided. These results are crucial to establish credibility for building a fusion reactor blanket employing ceramic-composite materials.

Ceramic Blanket Configuration

We continued to develop the ARIES-IV toroidal-flow blanket design during the year based upon the reference design selected for ARIES-I. This blanket utilizes a series of nested shells for the toroidal flow of the helium coolant as illustrated in Fig. 1. The structural material is silicon carbide composite (SiC-C) and the helium coolant circulates at a pressure of 10 MPa through 0.5 to 0.9 cm diameter channels in the U-shaped shells. The spaces between the nested shells are filled with pellets of beryllium and lithium oxide for neutron multiplication and tritium breeding, a sintered beryllium pellet shell for neutron multiplication and kink stabilization (necessary for a plasma operating in the second stability regime) is used as the outermost layer.

The design is relatively straightforward and each module would be fabricated from smaller assemblies in layers as shown in Fig. 2. Each of the shells is pre-formed from panels of tubes; this helps to improve the predicted reliability by minimizing the number of joints. The shells are attached to poloidal plena in the surface farthest away from the plasma. Pipes for the helium inlet and exhaust are then brazed to the plena. This blanket configuration appears to be quite acceptable from the point-of-view of ceramic materials construction techniques.

This nested shell configuration can also be used for various combinations of metallic and ceramic-composite structural materials and for different solid and liquid metal breeder materials. This concept also has the advantage that a smooth first wall surface facing the plasma can be incorporated. No unresolved critical issues have yet been identified. Indeed, for a metallic structure design, this configuration offers much promise as a driver and test module blanket for machines such as ITER.

FIG. 1. The nested-shell blanket concept for ARIES-IV.

FIG. 2. Fabrication concept for the nested-shell blanket structure.

Structural Design

The ARIES-IV blanket design is composed of nested shells made of silicon carbide composite. In the inboard blanket there are 15 shells plus the first wall, which faces the plasma. The outboard blanket has 22 shells plus the first wall. Each shell is composed of toroidal cooling tubes carrying helium at 10 MPa with an inlet temperature of 350°C and an outlet temperature of 650°C. The diameter of these tubes is 9 mm for the outboard first wall, 8 mm for the in-board first wall, 5 mm for the first shell of both designs, and 4 mm for the rest of the shells. Between the first wall and the first shell is a sintered beryllium multiplier sphere-pac, 22 mm thick for the inboard blanket and 20 mm for the outboard. The spaces between the remaining shells are filled with a lithium oxide breeder sphere-pac 8 mm thick.

A first order estimate of the thermal and structural behavior of this blanket/shield design was made using the two dimensional thermal code TOPAZ-2D and the thermal/structural code COSMOS/M. These codes model the first wall and first shell of the outer and inner blankets. Results from the analysis revealed that a spacing of around 1 cm is required between the blankets in order to leave room for thermal expansion in the toroidal direction. Also, the first walls of both blankets expand radially at a different magnitude than the first shells. Therefore, the beryllium sphere-pac of the outer blanket should have a gap of 0.15 cm before thermal expansion, and the inner blanket a gap of 0.06 cm. In the present design concept, the inner blanket has almost horizontal top and bottom sections; therefore compression of the beryllium sphere-pac will occur there if a space of 0.75 cm is not left for vertical expansion. In all cases, the analysis showed that the maximum primary and secondary stresses were well within the allowable for the combination of these stresses, 190 MPa.

Materials Studies

The swelling of Be at high temperature and high neutron fluence is an unresolved critical problem. The use of hollow Be spheres may accommodate the possible 30% volumetric change. A costing estimate for the fabrication of Li₂O micro-spheres was made and it is believed that these microspheres can be fabricated and sintered/pressed from lithium hydroxide at a reasonable cost of \$50 to 80/Kg.

2.3.3. PHYSICS

Studies were initiated on ways to reduce the toroidal field ripple by including iron in the casing structure of the toroidal field coils. This provides a simple way to obtain a peak-to-average field ripple of well below the required 0.5% at the plasma edge and would allow the ARIES design to use as few as 12 TF coils. Modifications were made to the 3-D ripple code to simulate the ARIES-IV design. A limit on ripple of 0.3% (peak-to-average) was shown to be adequate to meet the alpha particle loss criterion. This can be achieved with a 16 coil design TF system (the reference design) without the additional complication of needing an iron insert.

Work also continued on developing a simple electromagnetic model of the disruption phenomena. An analysis was performed comparing the disruptive forces predicted for the second stability, ARIES plasma with those for the first stability, ITER-HARD design. The results indicate the ARIES disruptive forces will be much less severe than those experienced in HARD; they will be comparable in magnitude to those experienced in JET and JT60U. This is mainly due to the relatively low plasma current of 5 to 6 MA for the ARIES design. The analysis method used in this study is unique in the fusion community and allows an estimation of the disruption pressures and forces to be made without regard to the details of the structure. The same disruption characterization performed on the double null plasma is being extended to the single null plasma. We also made good progress on developing an engineering model for the disruption process.

A study of the vertical stability properties of the ARIES-II and IV single null equilibria incorporating the cuts, kink-stability shells and the vacuum vessel has also been made. MHD calculations have shown that the conducting shell must be located less than 30 cm from the plasma edge; much closer to the plasma than originally anticipated if a kink-stable plasma is to be maintained. This has a major impact on the ARIES-II reduced activation and ARIES-IV low activation designs.

The Be-shell used for neutron multiplication has also been proposed to serve as the kink-stabilization shell but the cuts and high resistance of the Be material greatly reduce the overall vertical stability time constant. This makes the control using external PF coils virtually impossible because the field is unable to penetrate the vacuum vessel fast enough. In addition, the response time constants are prohibitively fast for a superconducting PF system. It does, however, appear that an internal,

active, coil located behind the shield will be capable of controlling the plasma at reasonable power requirements.

3. RF TECHNOLOGY

FY92 has been a very productive year in the development and demonstration of rf technology at GA.

Fast Ferrite Tuner

One of the major activities of the year has been to test a prototype fast ferrite tuner (FFT) system developed by ANT-Bosch Telecom on DIII-D. The objective was to attempt to optimize the coupling of the plasma to the transmission line and the FW transmitter by better matching the respective impedances. This enables maximum generated power to flow to the plasma. An experimental campaign during the final DIII-D run weeks of FY92 used an FFT hybrid system provided by ANT-Bosch Telecom inserted in the line to one strap of the FW antenna. The goal of the test was to find the rate at which this circuit element could respond to dynamic loading conditions. A schematic of the circuit used is shown in Fig. 3. A feedback loop monitored the complex reflection coefficient at the output of the fast ferrite hybrid (FFH) system and controlled the magnet power supplies on the FFT1 and FFT2 units to cancel out the reflections.

Tests were conducted on DIII-D in a background mode. No FW heating was actually applied. Low power antenna strap-plasma matching was studied using this fast ferrite hybrid tuning system. The tests demonstrated conclusively the ability of the tuner to respond to loading changes with less than a 20 msec response time. This is shown in Fig. 4 where the reduction in the magnitude of the reflection coefficient, ρ , is seen to drop dramatically in response to a command from the control system. The simple command circuitry used in these tests was too slow to be used in an actual plasma heating experiment because of the limited data transmission rate from the network analyzer to the microcomputer controlling the power supplies. However, new customized digital hardware can eliminate this long delay and bring it down to the millisecond timescale.

FIG. 3. Schematic of the test setup for a low power fast ferrite hybrid tuner on DIII-D.

The next step would be to build a full power tuner and incorporate it into the experimental setup for the FWCD antenna. This is probably the most effective and economical approach to pursue in order to maximize the power coupled to the plasma in terms of \$/watt delivered. It also has the advantage of protecting the transmitter from the adverse effects of a high voltage standing-wave ratio.

Gyrotron AC Sweeping Coil

In the gyrotron development program, an ac sweeping coil system was developed and tested at Varian on a dummy gyrotron collector assembly. The function of this system is to spread the beam energy out uniformly over the collector surface to eliminate the hot spots and thereby allow long pulse operation of the gyrotron. The sweeping coil built was shown to develop a uniform magnetic field that was within 5% of the predicted value. The system was subsequently installed on an actual gyrotron undergoing tests at Varian and has recently been shown to meet expectations in lowering the peak power densities at the collector by factors of around 2.5. This brings the power on the collector down to the safe operating level.

FIG. 4. Response time in reduction of the magnitude of the reflection coefficient at the output generator during a DIII-D discharge.

Coordination of International Activities

The U.S./Japan RF Technology Exchange Meeting was held during the period October 4-7, 1991 in San Diego in conjunction with the IEEE Conference on Fusion Engineering. Japanese representatives from both the Ministry of Education and the Science and Technology Administration attended along with observers from other U.S. labs and the European community. There was general agreement that the exchange benefited all participants. A proposal was initiated, and approved, to hold another such meeting in October 1992.

Planning and execution of a Workshop on Dynamic Tuning Networks, held in Rome in conjunction with the SOFT Conference in September 1992 was completed. There were 19 participants in the meeting, 7 from the US, 10 from Europe and 2 from Japan.

Planning and coordination for the Second International ECH Transmission Line Workshop, scheduled for December 1992, was also completed.

U.S./Japan Collaboration on ICH Feed-Through Testing

A series of rf vacuum feed-throughs are being produced by the Massachusetts Institute of Technology (MIT), Oak Ridge National Laboratory (ORNL), and Princeton Plasma Physics Laboratory (PPPL) groups and it was proposed that the various designs should be tested under uniform conditions at the Japan Atomic Energy Research Institute (JAERI) test facility at Naka. Each feed-through is inserted into a transmission line between a transmitter module and a dummy load and run up in voltage until it breaks down. Previous tests in FY91 indicated that all the tested feed-throughs at that time were able to handle voltages of 50 to 55 kV. Modifications to the designs should now permit them to survive higher voltage operation. However, delays in obtaining new units from MIT and PPPL have caused the tests to be delayed until FY93.

4. PLASMA FACING COMPONENTS

4.1. OVERVIEW

The most challenging conditions to be dealt with by fusion technology occur at the interface between the fusion plasma and the fusion machine. Material erosion of the divertor target materials by physical and chemical sputtering processes and from disruption events are critical issues for high-power, long-pulse divertor tokamaks such as ITER. In the ITER-CDA design study, the ability to develop divertor plates that survive over extended periods of plasma operation stands out as the most critical technology issue.

An ITER R&D program has been initiated in response to the need to understand the interaction between the plasma and different divertor surface materials. Material erosion, tritium retention, disruption effects and material transport are very important topics for the design of this machine. We are using DIII-D as a test bed to directly measure and model the erosion/redeposition characteristics of the graphite divertor plates and other phenomena of plasma and material interaction.

This project is being carried out as a cooperative effort by a team from Sandia National Laboratory-Livermore (SNL-L) (material characterization), Lawrence Livermore National Laboratory (LLNL) (edge plasma measurements and analysis), and GA (project coordination, experimental operations, experiment hardware, and analysis). Erosion/redeposition analysis is being done in conjunction with SNL-Albuquerque and Argonne National Laboratory (ANL). Disruption analysis is being done in conjunction with the University of New Mexico, North Carolina State University, and ANL. GA will perform experiments in DIII-D to measure erosion/redeposition and impact from disruption on divertor target materials and other phenomena of plasma and material interaction, and compare experimental results to analytic model predictions.

The project is divided into two phases. In the first phase, 12 divertor tiles were exposed to the divertor plasma from March to December of 1989. The integrated net erosion/redeposition was determined by accurate profiling of the tile surface and compared to predicted behavior. A Divertor Materials Evaluation System (DIMES)

sample was also exposed in DIII-D for a period of five months in FY90. The second phase, which was initiated in FY 90, involves the design, fabrication, and installation of the DIMES and the real-time measurements of the erosion during a plasma discharge. The motorized sample changer mechanism was installed in FY92 and the erosion/redeposition and disruption experiments will begin in FY93. The ellipsometry *in situ* measurement system will be installed in FY94.

4.2. INTEGRAL EXPOSURE EXPERIMENT

From March 29 to December 15, 1989, we exposed 12 well-characterized bottom divertor tiles in DIII-D. The DIII-D Confinement, Stability and Transition (CS&T) data base was reviewed. Out of a total of 4682 records, approximately 1400 were high power H-mode diverted plasma shots that can have significant impact on the bottom divertor tile erosion. These shots were studied and a strike point distribution was put together and provided as input for the REDEP modeling calculation at ANL. Net erosion of the tiles was measured at SNL-L. It was found that the magnitude of net erosion was comparable between measured and modeled results, yet the distribution of erosion was not well matched. This possibly was due to the plasma events that had happened during the exposed period which were more complicated than the relatively simple plasma model used in the code calculation.

For the second integral experiment, a DIMES graphite sample that had a ^{13}C coating applied to a spot 0.8 cm in diameter was exposed to the DIII-D experiments for five months. The distribution of the ^{13}C isotope was measured and correlated with the plasma conditions at the bottom divertor. Details of the ^{13}C distribution on the DIMES sample were studied at SNL.

4.3. DIMES SAMPLE CHANGER SYSTEM

Great progress has been made with the DIMES material exposure system in the past year. The entire mechanical system, illustrated in Fig. 5, is now complete and has been installed on a lower vertical port of the DIII-D vacuum vessel.

The heart of the system, the two stage telescoping hydraulic cylinder and its fluid control system, was manufactured to our design by the Anker-Holth Corp. of Toronto. The entire system was subsequently assembled and tested here at GA and operation under a vacuum, simulating the DIII-D vessel conditions, was performed. The system functioned extremely well and can be controlled from the DIII-D control

FIG. 5. DIMES mechanical system.

room. Our hydraulic system uses an extremely low vapor pressure vacuum pump oil (Santovac 5) for its working fluid rather than standard hydraulic oil. This is to achieve full vacuum compatibility and minimize contamination of the torus in the extremely unlikely event of fluid leakage into the primary vacuum chamber.

Instrumentation leads have been installed within the hydraulic cylinders and these will allow connection of sensors on the DIMES material samples to external data collection devices. Ellipsometry and thin-foil measurement techniques for *in situ* measurement of material erosion and re-deposition are being developed by our SNL-L collaborators.

An initial portfolio of DIMES experiments has been developed following a meeting of the community of fusion materials experimentalists. These proposals are now being integrated into the experimental plan for the DIII-D machine when it resumes operation in the Spring of 1993.

5. FY92 PUBLICATIONS

C.P.C. Wong *et al.*, *The Evolution of U.S. Helium Cooled Blankets*, *Fus. Eng. Design* **17** (1991) 123.

C.P.C. Wong *et al.*, *Divertor Materials Evaluation system at DIII-D*, *J. Nucl. Mater.* **196-198** (1992) 871.

END

DATE
FILMED

4 103 / 93