10
6/16/92 Jm ①

ORNL-6711

**OAK RIDGE
NATIONAL
LABORATORY**

**Energy Division Annual Progress
Report for Period Ending
September 30, 1991**

MARTIN MARIETTA

**MANAGED BY
MARTIN MARIETTA ENERGY SYSTEMS, INC.
FOR THE UNITED STATES
DEPARTMENT OF ENERGY**

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615) 576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

ORNL--6711

DE92 014934

**ENERGY DIVISION
ANNUAL PROGRESS REPORT
for Period Ending September 30, 1991**

R. B. Shelton, Director
J. B. Cannon, Associate Director
M. A. Kuliasha, Associate Director
K. H. Zimmerman, Technical Assistant

M. S. Bronzini, Director, Center for Transportation Analysis
R. M. Reed, Section Head, Integrated Analysis and Assessment Section
G. E. Courville, Section Head, Efficiency and Renewables Research Section
C. R. Kerley, Section Head, Energy and Economic Analysis Section
T. J. Wilbanks, Senior Planner, Planning and Coordination

Date Published—April 1992

J. N. Stone, Editor
L. A. Daniel, Electronic Publisher

Prepared by the
OAK RIDGE NATIONAL LABORATORY
Oak Ridge, Tennessee 37831
managed by
MARTIN MARIETTA ENERGY SYSTEMS, INC.
for the
U. S. DEPARTMENT OF ENERGY
under Contract No. DE-AC05-84OR21400

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DEDICATION DORIS J. SLAUGHTER

December 1927–July 1991

Doris attended Kate Duncan Smith High School in Grant, Alabama. She received a B.S. in Business Administration from Lincoln Memorial University in Harrogate, Tennessee, in 1949. After graduation, she worked for 7 years as a secretary for ORNL's Director's divisions and for the Metals and Ceramics (M&C) Division. While in M&C, Doris met and married Gerry Slaughter, who still works in that division. In 1956, she left ORNL to start her family. She became actively involved in volunteer work with the Girl Scouts, the school system, YWCA, Red Cross, and the church while raising two children, Richard and Donna. In 1977, Doris came back to ORNL on a part-time basis as a secretary assigned to the Energy and Environmental Sciences divisions. A year later she accepted a full-time position as secretary for what is now known as the Power Systems Technology Program of the Efficiency

and Renewables Research Section in the Energy Division.

In 1985, Doris received the Energy Division award for sustained contribution of excellence for administrative support. She received this award for being the "glue" for the Power Systems Technology Program, for which there were three new program managers during the last 7 years. Doris educated five new program managers and trained numerous new secretaries in the group. More recently, Doris assisted in the administration of a 700-page *Superconductivity Assessment Report* and in organizing and coordinating a book on the Athens Automation and Control System.

Doris possessed perseverance, competence, and enthusiasm, providing an example to all of those with whom she worked. She will be greatly missed.

TABLE OF CONTENTS

ACKNOWLEDGMENTS	xvii
1. INTRODUCTION AND EXECUTIVE SUMMARY	1-1
1.1 ANALYSIS AND ASSESSMENT	1-3
1.1.1 Energy and Resource Analysis	1-4
1.1.2 Environmental Assessments	1-5
1.1.3 Emergency Preparedness	1-5
1.1.4 Developing Country Analysis	1-5
1.1.5 Transportation Analysis	1-6
1.2 ENERGY CONSERVATION TECHNOLOGIES	1-6
1.2.1 Building Equipment	1-6
1.2.2 Building Envelopes	1-7
1.2.3 Existing Buildings	1-7
1.2.4 Electric Power Systems Technology	1-7
1.2.5 Other Activities in Energy Conservation Technologies	1-7
1.3 MILITARY TRANSPORTATION	1-7
1.3.1 Military Transportation	1-7
2. INTEGRATED ANALYSIS AND ASSESSMENT SECTION OVERVIEW	2-1
2.1 INTRODUCTION	2-1
2.2 NEPA PROJECTS	2-1
2.2.1 Site-Specific EIS for the Destruction of Chemical Weapons at ANAD	2-4
2.3 EMERGENCY PREPAREDNESS	2-7
2.3.1 Chemical Stockpile Emergency Preparedness Program	2-7
2.3.2 Dose Estimate Model	2-7
2.4 APPLIED PHYSICAL SCIENCES	2-10
2.4.1 Gaseous Diffusion Plant Safety Analysis Upgrade Program	2-10
2.4.2 Hydrogeologic Support for ER Program	2-11
2.5 TECHNOLOGY AND SOCIAL SYSTEMS	2-13
2.6 ENERGY AND ENVIRONMENTAL ANALYSES	2-14
2.6.1 The External Costs of Fuel Cycles Project	2-14
3. ENERGY AND ECONOMIC ANALYSIS SECTION OVERVIEW	3-1
3.1 INTRODUCTION	3-1
3.2 INFORMATION TRANSFER	3-2
3.3 RESEARCH PROGRAM	3-2
3.3.1 Productivity and Energy Supply	3-2
3.3.2 Energy and Environment	3-3
3.3.3 Modeling and Technology	3-10
3.3.4 Emergency Management and Risk Assessment	3-12
3.4 RESEARCH UTILIZATION	3-13
3.5 REFERENCES	3-14
4. CENTER FOR TRANSPORTATION ANALYSIS OVERVIEW	4-1
4.1 INTRODUCTION	4-1

4.2	POLICY ANALYSIS AND CONSERVATION	4-1
4.2.1	Impacts on the Environment	4-1
4.2.2	Transportation Planning and Policy	4-2
4.2.3	Motor Vehicle Fuel Economy	4-5
4.2.4	Alternatives for the Panama Canal	4-5
4.3	METHODS AND DATA	4-8
4.3.1	Highway Safety and Geometric Design	4-8
4.3.2	National Transportation Surveys	4-8
4.3.3	Highway Vehicle MPG and Market Shares Report: Model Year 1990	4-10
4.4	MILITARY PLANNING AND SCHEDULING SYSTEMS	4-10
4.4.1	FAST Planning for USTRANSCOM	4-10
4.4.2	Tracking Household Goods and Other Shipments	4-14
4.5	SHARING CTA EXPERTISE	4-15
4.5.1	Reliability-Centered Maintenance	4-15
4.5.2	Workstations and Secure Networking	4-15
5.	EFFICIENCY AND RENEWABLES RESEARCH SECTION OVERVIEW	5-1
5.1	INTRODUCTION	5-1
5.2	BUILDING EQUIPMENT RESEARCH PROGRAM	5-1
5.2.1	Thermally Activated Heat Pumps	5-1
5.2.2	Novel Cycles	5-4
5.2.3	Refrigeration Systems	5-4
5.2.4	Work for Others for the BER Program	5-5
5.2.4.1	Advanced Surfaces for Vertical-Tube Absorbers	5-5
5.2.4.2	EPRI CFC Alternatives for Centrifugal Chillers	5-6
5.3	THERMAL AND ENVIRONMENT CONTROL SYSTEMS	5-6
5.4	BUILDING THERMAL ENVELOPE SYSTEMS AND MATERIALS	5-11
5.4.1	Non-CFC Polyisocyanurate Insulation Testing	5-12
5.4.2	Builders' Handbooks	5-13
5.4.3	Heat and Mass Transfer Modeling in Foundations	5-13
5.4.4	Cooperative Research and Development Agreements	5-13
5.5	EXISTING BUILDINGS RESEARCH	5-14
5.6	ENERGY PROGRAM PLANNING AND EVALUATION	5-16
5.7	INTEGRATED RESOURCE PLANNING FOR ELECTRIC UTILITIES	5-17
5.8	TECHNOLOGY TRANSFER	5-19
5.9	COMMUNITY ENERGY SYSTEMS	5-20
5.10	POWER SYSTEMS TECHNOLOGY	5-20
5.10.1	Higher Capacity Transmission	5-20
5.10.1.1	Real-time Control and Operation of Electric Power Systems	5-20
5.10.1.2	Higher Capacity Transmission Using HVDC	5-21
5.10.1.3	High Phase-Order Transmission	5-21
5.10.2	Power Transients	5-22
5.10.3	Materials	5-23
5.10.4	Biological Effects from Electric and Magnetic Fields	5-23
5.10.5	PST Work for Others	5-24
5.10.6	Energy for Developing Countries	5-24
5.11	REFERENCES	5-24

6. PLANNING AND COORDINATION OVERVIEW	6-1
6.1 INTRODUCTION	6-1
6.2 DEVELOPING COUNTRY PROGRAMS	6-1
6.2.1 Energy Strategy Development	6-1
6.2.2 Energy Efficiency Improvement	6-1
6.2.3 Environmental Management	6-2
6.2.4 Renewable and Rural Energy Systems	6-4
6.2.5 Energy R&D Applications	6-4
6.2.6 Institution-Building and Technology Transfer	6-6
6.3 OTHER ACTIVITIES	6-6
6.3.1 SUMMARY OF ISSUES REGARDING GLOBAL ELECTRICITY SUPPLY AND DEMAND	6-7
6.3.1.1 Reconciling Development Needs with Environmental Impacts	6-7
6.3.1.2 Potentials and Limits of Alternative Paths	6-7
6.3.1.3 Different Regional Roles and Realities	6-9
6.4 REFERENCES	6-9
7. ABSTRACTS OF PUBLICATIONS	7-1
7.1 ABSTRACTS OF INTEGRATED ANALYSIS AND ASSESSMENT SECTION	7-1
7.2 ABSTRACTS OF ENERGY AND ECONOMIC ANALYSIS SECTION	7-25
7.3 ABSTRACTS OF CENTER FOR TRANSPORTATION ANALYSIS	7-38
7.4 ABSTRACTS OF EFFICIENCY AND RENEWABLES RESEARCH SECTION	7-60
8. PUBLICATIONS AND PROFESSIONAL ACTIVITIES	8-1
8.1 ENERGY DIVISION ADVISORY COMMITTEE 1991	8-1
8.2 ENERGY DIVISION PERSONNEL BY DISCIPLINE	8-2
8.3 ENERGY DIVISION PROFESSIONAL HONORS AND AWARDS FY 1991	8-3
8.4 ENERGY DIVISION PROFESSIONAL ACTIVITIES FY 1991	8-4
8.5 ENERGY DIVISION PUBLICATIONS FY 1991	8-9
8.6 ENVIRONMENTAL ASSESSMENTS AND ENVIRONMENTAL IMPACT STATEMENTS	8-25
8.7 PUBLICATIONS BY SUBCONTRACTORS	8-26
8.8 PRESENTATIONS BY ENERGY DIVISION STAFF FY 1991	8-27
8.9 ENERGY DIVISION CONSULTANTS AND SUBCONTRACTORS	8-36
8.9.1 Consultants	8-36
8.9.2 Subcontractors by Company	8-36
8.10 INVITED SPEAKERS	8-38
8.11 WORKSHOPS AND SYMPOSIA ORGANIZED BY ENERGY DIVISION STAFF	8-39
8.12 ENERGY DIVISION PATENT INFORMATION	8-40
8.13 ENERGY DIVISION SPONSORS, EXPENDITURES, AND COMMITMENTS OF SCIENTIFIC STAFF FOR FY 1991	8-41

ORGANIZATIONAL CHART

PROJECT HIGHLIGHTS

Draft Environmental Impact Statement (EIS) on the Healy Clean Coal Project	2-3
Impacts of Hydropower in the Nooksack and Skagit River Basins	2-6
Automation Prototype for Emergency Management Information System	2-8
Quantitative Assessment for Completing the Hazardous Waste Remediation Task	3-7
China's Evolving Energy and Environmental Policy	3-8
Regional Recruiting Potential Model	3-11
Intelligent Vehicle Highway Systems	4-3
Navy Mobility Fuels Forecasting System	4-6
Transportation Energy Data Book	4-9
Airlift Deployment Analysis System Supports the Operation Desert Storm Airlift	4-11
Ternary Solutions for GAX Absorption Heat Pumps and Air Conditioners	5-2
Alternative Fluorocarbons Environmental Acceptability Study Cooperative Research and Development Agreement	5-8
Attic Testing	5-10
Low-Income Weatherization Assistance Program	5-16
The Mayarema Biosphere Preserve Project	6-3
Innovative Uses of Biomass Energy in China	6-4

ACRONYMS

AC	Area Command
ADANS	Airlift Deployment Analysis System
ADSS	automated decision-support system
AEO	Annual Energy Outlook
AFB	air force base
AFEAS	Alternative Fluorocarbons Environmental Acceptability Study
AFGD	advanced flue gas desulfurization
AHAM	Association of Home Appliance Manufacturers
AID	Agency for International Development
AIDEA	Alaska Industrial Development and Export Authority
AIM	Acquisition Information Management
AMPMOD	Army Materiel Plan Modernization
ANAD	Anniston Army Depot
APDC	Asian and Pacific Development Centre
APG	Aberdeen Proving Ground
AREFG	air refueling group
ARI	Air-Conditioning and Refrigeration Institute
ARNG	Army National Guard
ASHRAE	American Society of Heating, Refrigerating, and Air Conditioning Engineers
ASTM	American Society for Testing and Materials
ATC	Air Training Command
ATIS	Advanced Traveler Information System
ATMS	Advanced Traffic Management System
BER	Building Equipment Research
BCR	benefit-to-cost ratio
BMW	bombardment wing
BOM	U.S. Bureau of Mines
BPA	Bonneville Power Administration
BTESM	Building Thermal Envelope Systems and Materials
Btu	British thermal unit
CAA	Clean Air Act
CADDET	Center for the Analysis and Dissemination of Demonstrated Technologies
CAFE	Corporate Average Fuel Economy
CAP	Communications Alarm Processor
CARES	Central American Rural Electrification Support
CCT	Clean Coal Technology
CCTDP	Clean Coal Technology Demonstration Program
CCTP	Clean Coal Technology Program
CEC	Commission of the European Communities
CF	Citizens' Forum
CFBC	Circulating Fluidized Bed Combustion
CFC	chlorofluorocarbon
CFR	Code of Federal Regulations
CHP	chemical heat pump
CMAFB	Cheyenne Mountain Air Force Base
CNG	Canadian Natural Gas
CO ₂	carbon dioxide
CONUS	continental United States
COP	coefficient of performance

CORA	Cost of Remedial Action
CORECT	Committee on Renewable Energy Commerce and Trade
CRADA	Cooperative Research and Development Agreement
CSDP	Chemical Stockpile Disposal Program
CSEPP	Chemical Stockpile Emergency Preparedness Program
CTA	Center for Transportation Analysis
dBA	decibels on an A-weighted scale
DCD	desiccant cooling and dehumidification
DELTA	Dynamic Ecological Land Tenure Analysis
DFA	damage-function approach
DGP	Data Gathering Project (Bonneville's)
DHC/C	District Heating, Cooling, and Cogeneration
DIAMOND	Decision Impact Assessment Model
DNPP	Denali National Park and Preserve
DOD	U.S. Department of Defense
DOE	U.S. Department of Energy
DOT	U.S. Department of Transportation
DSM	demand-side management
DSNET 1	Defense Secure Network Level 1
DSS	Decision Support System
DST	Dempster-Shafer Theory
DW	defense waste
EA	1. environmental assessment 2. economic analysis
ECM	energy conservation measure
EEAS	Energy and Economic Analysis Section
EIA	Energy Information Administration
EIS	environmental impact statement
EMIS	Emergency Management Information System
EMP	electromagnetic pulse
EMT	emergency medical technician
EOC	Emergency Operations Center
EPA	U.S. Environmental Protection Agency
EPPE	Energy Program Planning and Evaluation
EPRI	Electric Power Research Institute
ER	Environmental Restoration
ERIP	Energy-Related Inventions Program
ERRS	Efficiency and Renewables Research Section
ESEERCO	Empire State Electric Energy Research Corporation
ES&H	environmental, safety, and health
ESP	earth-surface potentials
FAST	Flow and Analysis System for USTRANSCOM
FEMA	Federal Emergency Management Agency
FERC	Federal Energy Regulatory Commission
FHWA	Federal Highway Administration
FPEIS	final programmatic environmental impact statement
FPSEHP	free-piston Stirling-engine-driven heat pump
FRERP	Federal Radiological Emergency Response Plan
FTE	full-time-equivalent
FTW	flying training wing
FY	fiscal year
GAX	generator-absorber heat exchange

GDP	gaseous diffusion plant
GDT	geophysical diffraction tomography
GEEI	Global Energy Efficiency Initiative
GEIS	Generic Environmental Impact Statement
GIS	Geographic Information System
GMD	geomagnetic disturbance
GPS	Global Positioning System
GRI	Gas Research Institute
GVEA	Golden Valley Electric Association, Inc.
HAZMAT	hazardous material
HCCP	Healy Clean Coal Project
HCFC	hydrochlorofluorocarbon
HEMP	high-altitude EMP
HMIMS	Hazardous Materials Incident Management System
HPMS	Highway Performance Monitoring System
HTFS	Highway Traffic Forecasting System
HVAC	heating, ventilating, and air-conditioning
HX	heat exchanger
IAAS	Integrated Analysis and Assessment Section
IBS	Integrated Booking System
IC	internal combustion
IRM	information resource management
IRP	integrated resource planning
ITDS	Integrated Traffic System
IVHS	intelligent vehicle highway system
JACADS	Johnston Atoll Chemical Agent Disposal System
JCS	Joint Chiefs of Staff
LBL	Lawrence Berkeley Laboratory
LEPC	local emergency planning committee
LiBr	lithium bromide
LKP	Lee-Kesler-Plöcker
LM	Lorenz-Muetzner (refrigeration cycle)
LSCS	Large Scale Climate Simulator
M&C	Metals & Ceramics Division
MAC	1. Military Airlift Command 2. mobile air-conditioning
MAILS	Multiple-Aircraft Instantaneous Line Source
MAJCOMS	Major Commands
MBD	million barrels per day
MCS	Model Conservation Standards
MHD	magnetohydrodynamic
MLE	maximum likelihood estimator
MOA	military operations areas
MOS	military occupational speciality
MOV	metal-oxide varistor
mpg	miles per gallon
MSW	municipal solid waste
MTI	Mechanical Technology, Inc. (subcontractor)
MTIT	Military Traffic Management Command Directorate of International Traffic
MTMC	Military Traffic Management Command
MTPP	Military Traffic Management Command Personal Property Program
MTR	military training routes
NAAQS	National Ambient Air Quality Standards

NAEP	National Assessment of Educational Progress
NARM	nonazeotropic refrigerant mixture
NCEST	National Council on Education Standards and Testing
NEPA	National Environmental Policy Act of 1969
NES	National Energy Strategy
NETSIM	Network Simulation
NIIS/FDAM	National Infrastructure Information System Facility Damage Assessment Module
NIST	National Institute of Standards and Technology
NO _x	nitrogen oxides
NRC	Nuclear Regulatory Commission
NRECA	National Rural Electric Cooperative Association
NSF	National Science Foundation
NTACS	Nationwide Truck Activities and Commodity Survey
NTP	National Transportation Policy
NTU	number of transfer units
OBT	Office of Building Technologies
OH	Ontario Hydro
OPEC	Organization of Petroleum Exporting Countries
ORNL	Oak Ridge National Laboratory
ORR	Oak Ridge Reservation
OTM	Oil Trade Model
PACER	Program for the Acceleration of Commercial Energy Research
PAECE	Protective Action Evaluator for Chemical Emergencies
PBA	Pine Bluff Arsenal
PCB	polychlorinated biphenyl
PEIS	programmatic environmental impact statement
PGM	Precision Guided Munition
PM	particulate matter
PMF	probable maximum flood
PSD	Prevention of Significant Deterioration Areas
PUC	public utility commission
R&D	research and development
RA	restricted areas
RCCPDS	Reserve Components Common Personnel Data System
RCM	reliability-centered maintenance
RCRA	Resource Conservation and Recovery Act
RD ₁ D ₂ &I	research, development, demonstration, and implementation
REAT	Renewable Energy Applications and Training
RF	refrigerator/freezer
RFF	Resources for the Future
RFP	request for proposal
RIM	rate impact measure
ROD	record of decision (U.S. Army)
RPPR	Refined Petroleum Product Reserve
RRPM	Regional Recruiting Potential Model
RTI	Research Triangle Institute
RTMAS	Real-Time Traffic Monitoring and Analysis System
RTP	real-time pricing
RTRA	Roof Thermal Research Apparatus
RWP	Residential Weatherization Program
RYM	Refinery Yield Model

ABSTRACT

The Energy Division is one of 17 research divisions at Oak Ridge National Laboratory. Its goals and accomplishments are described in this annual progress report for FY 1991. The Energy Division is a multidisciplinary research organization committed to (1) increasing the knowledge and understanding of how societies make choices in energy use; (2) improving society's understanding of the environmental, social, and economic implications of technological change; (3) developing and transferring energy-efficient technologies; (4) developing improved transportation policy and planning; (5) providing a unique environment in which engineers and physical, environmental, and social scientists address major societal problems; (6) enhancing basic knowledge in the social sciences as related to energy and associated issues; and (7) creating an atmosphere that will encourage all staff members to develop professionally in their respective disciplines.

The division's total expenditures in FY 1991 were \$39.1 million. The work is supported by the U.S. Department of Energy, U.S. Department of Defense, many other federal agencies, and some private organizations. Disciplines of the 124 technical staff members include engineering, social sciences, physical and life sciences, and mathematics and statistics.

The Energy Division's programmatic activities focus on three major areas: (1) analysis and assessment, (2) energy conservation

technologies, and (3) military transportation systems. Analysis and assessment activities cover energy and resource analysis, the preparation of environmental assessments and impact statements, research on waste management, analysis of emergency preparedness for natural and technological disasters, analysis of the energy and environmental needs of developing countries, technology transfer, and analysis of civilian transportation. Energy conservation technologies include electric power systems, building equipment (thermally activated heat pumps, advanced refrigeration systems, novel cycles), building envelopes (walls, foundations, roofs, attics, and materials), and technical issues for improving energy efficiency in existing buildings. Military transportation systems concentrate on research for sponsors within the U.S. military on improving the efficiency of military deployment, scheduling, and transportation coordination.

Much of the information produced from the division's research is valuable to other organizations as well as to sponsors. Dissemination of this information was accomplished by the staff's being involved in professional and trade organizations; holding workshops; engaging private sector firms and universities in research; interfacing with state and local governments; presenting work at conferences; and publishing the results of research in journals, reports, and conference proceedings.

ACKNOWLEDGMENTS

The authors wish to express their gratitude to the many individuals who assisted in preparation of this document. Brenda Bush, Sue Damewood, Lois Gosslee, Terri Simmons, Mary Ann Hensley, and Stephanie Floyd managed to collect and compile the information for their sections while continuing to fulfill a multitude of day-to-day responsibilities. Nancy Pope, Donna Leggett, and Jan Draine also provided information essential to the report, while Scott Stevens compiled and prepared Section 4. Sonya Plemmons prepared the distribution list, Curtis Boles provided quality

photography services, and Bob Eldridge helped prepare the manuscript for printing. Artistic contributions to the report were made by Leon Smith, Sonia Burger, Renee Manning, Dottie Patton, Allison Baldwin, and Leroy Gilliam. Publications staff members Joe Stone, Leigh Ann Daniel, Karen Vogel, Philip Wolff, and Christopher Coulter devoted long hours to the production of this report, demonstrating the effectiveness of harmonious interaction without regard for strictly defined roles. To all of these individuals we say, "Thank you," and for their quality work we are grateful.

Introduction

and Executive Summary

ORNL-Photo 1753-92

Bob Shelton, Division Director

1. INTRODUCTION AND EXECUTIVE SUMMARY

One of 17 research divisions at Oak Ridge National Laboratory (ORNL), Energy Division was formed in 1974 to unite work on environmental, technological, and regional assessments related to energy development and to perform research on improving the efficiency of

energy use and conversion. Energy Division is a multidisciplinary research organization serving many federal and nonfederal sponsors. The division's research programs for fiscal year (FY) 1991 are summarized in the following pages.

MISSION

The mission of the Energy Division is to provide innovative solutions to energy and related issues of national and global importance through interdisciplinary research and development (R&D).

- The division focuses on technology and human systems. While much of its work emphasizes energy and environmental issues, the division also addresses other pressing concerns on the national agenda.
- The division's issue-oriented disciplinary diversity is its greatest strength—the ability to combine perspectives from natural, social, and engineering sciences.

VALUES

Energy Division staff members fully embrace Martin Marietta Energy Systems' values of concern for people, working together, and challenging goals. The division's mission and uniqueness also compels it to explicitly observe the following principles:

- **Quality:** the division is committed to providing the best practical knowledge for sponsors and the American people to pursue national goals.
- **Creativity:** the innovative talent of its staff is the division's most precious resource.
- **Intellectual risk taking:** the division encourages and rewards novel approaches to problem solving.
- **Integrity:** the division conducts and communicates its work honestly and objectively.
- **Entrepreneurship:** the division encourages and rewards staff leadership in developing new initiatives.

VISION

The Energy Division at ORNL strives to realize the following vision:

- to be one of the world's foremost centers of excellence in conducting research related to energy, environment, and the economy;
- to become the preeminent U.S. institution in mobilizing teams that combine perspectives from natural, social, and engineering sciences to solve energy and related problems of national and global importance; and
- to provide a working environment that promotes creativity, encourages staff interaction, fosters institutional collaboration, and develops an internationally recognized research staff.

ORNL-Photo 1505-92

Michael Kuliasha, Associate Division Director.

Energy Division's expenditures in FY 1991 totaled \$39.1 million, as indicated in Fig 1.1. One-half of the budget was provided by the U.S. Department of Energy (DOE), one-third by the U.S. Department of Defense (DOD), and the remainder by private industries and other federal agencies. In terms of expenditures by research area (Fig. 1.2), analysis and assessment activities accounted for one-half of the budget, energy

ORNL-Photo 1506-92

Johnnie Cannon, Associate Division Director.

conservation technologies for almost one-third, and military transportation for about one-sixth.

In terms of personnel, 174.5 full-time-equivalent staff and 150 on-site guests contributed their talents to the division during FY 1991. Staff members include 124 technical personnel (Fig. 1.3), 34.5 administrative support personnel, and 16 technical support personnel. Slightly more than one-third of the technical staff are engineers, another one-third are social scientists, one-sixth are physical and life scientists, and the remaining portion are data systems personnel. Over 90% of the technical staff hold advanced degrees (Fig. 1.4). Over half of the staff hold doctoral degrees, over one-third hold master's degrees, and the rest hold bachelor's degrees.

In addition to staff members, consultants and subcontractors perform work for the division (Sect. 8.9), as do staff members in other ORNL divisions, including Analytical Chemistry, Applied Technology, Chemical Technology, Engineering Physics and Mathematics, Engineering Technology, Environmental Sciences, Health and Safety Research, Metals and Ceramics, and Research Reactors divisions. The list of subcontractors in Sect. 8.9 indicates the wide range of institutions that contribute to Energy Division research activities.

Contained in this report are overviews of the division's achievements for FY 1991 (October 1, 1990–September 30, 1991). Chapters 2–6 summarize the work of the different sections within the division. Chapter 2 provides a survey of work done in the Integrated Analysis and Assessment Section, which experienced a change of leadership last year. Effective August 1991, Bob Reed assumed the position of Section Head, replacing Johnnie Cannon, who was promoted to Associate Division Director. Chapter 3 describes the work of the Energy and Economic Analysis Section, headed by Charles Kerley. Chapter 4 covers the work of the Center for Transportation Analysis (CTA). The CTA directorship was filled when Michael Bronzini arrived in January 1991 from Penn State University. Frank Southworth and Michael Kuliasha served as acting directors at different times during the year. Chapter 5 covers the work of the Efficiency and Renewables Research Section, headed by George Courville, and Chapter 6 describes the activities of Planning and Coordination, headed by Tom Wilbanks.

To more effectively develop interdisciplinary research potential and to enhance new R&D initiatives, Energy Division's upper management structure was reorganized in June 1991 to include two associate directors. This restructuring allowed the division to maintain its leadership in Environmental Safety and Health, while continuing aggressive R&D marketing and beginning new efforts in human resource development. Johnnie Cannon was appointed Associate Energy Division Director to work parallel with Michael Kuliasha, who held the position during the previous fiscal year. Cannon has technical oversight responsibilities for the Integrated Analysis and Assessment and Energy and Economic Analysis sections and heads human resource development. Kuliasha holds technical oversight responsibilities for the Efficiency and Renewables Research section and the Center for Transportation Analysis and maintains responsibility for quality assurance and environmental, safety, and health issues within the division.

To strategically shape and direct Energy Division research activities, the division categorizes its work by three major themes. The first theme, analysis and assessment, incorporates energy and resource analysis, environmental assessments, emergency preparedness, analysis of developing countries, and analysis of civilian transportation. The second theme, energy conservation technologies, embraces issues involving building equipment, building envelopes, electric power systems, and existing buildings. Finally, the third theme includes extensive R&D of planning models and decision support tools for military transportation systems.

1.1 ANALYSIS AND ASSESSMENT

Analysis and assessment activities include five major areas: (1) energy and resource analysis, (2) environmental assessments (EAs), (3) emergency preparedness, (4) developing country analysis, and (5) transportation analysis. Energy and resource analysis, common to every section of the division, covers a wide range of topics from energy security to utility resource planning. Assessment work includes waste management research and preparation of EAs and environmental impact statements (EISs) for various sponsors, to comply with the National Environmental Policy Act of 1969. Emergency preparedness research is concerned with

Fig. 1.1. Fiscal year 1991 Energy Division expenditures by sponsor.

improving society's ability to cope with natural and technological disasters. Developing country analysis assesses the energy and environmental needs of such countries as China and Guatemala. Lastly, transportation analysis covers civilian sector research on the development of data and analytical methods for conducting policy studies for DOE and other agencies concerned with transportation. Highlights of some of the year's most promising work are presented in the following sections.

Fig. 1.2. Fiscal year 1991 Energy Division expenditures by research area.

Fig. 1.3. Energy Division technical staff for fiscal year 1991.

1.1.1 Energy and Resource Analysis

A project initiated in FY 1991 continues to provide best-practice information on the external costs of fuel cycles. ORNL and Resources for the Future are the principal U.S. research institutions. The European Communities will conduct similar studies (see Sect. 2.6.1).

Staff members studied whether part of the U.S. petroleum stockpile should be stored regionally, as petroleum products, rather than stored centrally, as crude. An investigation of the

feasibility of a regional gasoline reserve found it to be cost-effective only if the reserve were completed and filled within four years and used within a year or two after being filled (see Sect. 3.3.1).

Research staff members prepared a quantitative assessment of prospective resource requirements for completing the nation's Hazardous Waste Remediation Task. The best-guess total cost of hazardous waste remediation under current policy is approximately \$750 billion (see Sect. 3 highlight, "Quantitative Assessment for Completing the Hazardous Waste Remediation Task").

Work continued on the development and analysis of the Army National Guard Regional Recruiting Potential Model. Analysis showed potential growth rates of U.S. guard members in the year 2000 (see Sect. 3 highlight, "Regional Recruiting Potential Model").

Researchers continued work on the Navy Mobility Fuels Forecasting System, which can predict the availability, cost, and quality of military and civilian fuels for various peacetime and wartime scenarios. Based on analyses of year 2000 scenarios (assuming free market economies for Eastern Europe, the former U.S.S.R., and the People's Republic of China), researchers recommend that the Navy continue to monitor projected trends in specific properties of Navy fuels, which should aid in the R&D of future Navy engines (see Sect. 4 highlight, "Navy Mobility Fuels Forecasting System").

Researchers finished planning and initiated the five studies comprising the national evaluation of DOE's low-income Weatherization Assistance Program (WAP). These studies are (1) characterization of the WAP Network, (2) scope of the WAP, (3) estimating impacts of the WAP in single-family and small multifamily dwellings, (4) estimating impacts of the WAP in high-density multifamily dwellings, and (5) estimating impacts of the WAP in fuel-oil heated homes (see Sect. 5 highlight, "Low-Income Weatherization Assistance Program").

A new planning model for electric utilities was completed to analyze the effects of utility demand-side management (DSM) programs on electricity costs and prices (see Sect. 5.7).

Fig. 1.4. Energy Division technical staff by level of education for fiscal year 1991.

1.1.2 Environmental Assessments

A draft EIS was prepared to assess environmental issues associated with the Healy Clean Coal Project (HCCP). HCCP proposes a new 50-MW coal-fired power plant built adjacent to an existing plant in Healy, Alaska, near the Denali National Park and Preserve (see Sect. 2 highlight, "Draft EIS on the Healy Clean Coal Project").

A site-specific EIS was prepared that examines potential environmental impacts of constructing and operating a facility for destroying chemical weapons at the Anniston Army Depot (ANAD) in Alabama. ANAD is one of eight depots where the U.S. stockpile of lethal chemical munitions is stored (see Sect. 2.2.1).

ORNL researchers have prepared two EAs on potential cumulative environmental impacts from the development of 19 hydroelectric projects proposed in the Skagit and Nooksack river basins. These studies explore the possibility of harmful effects to anadromous fish, terrestrial ecological resources, recreation, and cultural resources (see Sect. 2 highlight, "Impacts of Hydropower in the Nooksack and Skagit River Basins").

Analyses that contribute to the Safety Analysis Reports are being upgraded to meet the more stringent requirements of DOE Order 5480.1B. This evaluation includes the flooding potential of major rivers near the Paducah and Portsmouth gaseous diffusion plants and the development of groundwater models for evaluating effects from normal and accidental releases of hazardous materials (see Sect. 2.4.1).

1.1.3 Emergency Preparedness

A prototype of an Emergency Management Information System was developed, based on the philosophy that the functions of an automated emergency management system are parallel—but not identical—to emergency management functions as traditionally conceived by emergency managers (see Sect. 2 highlight, "Automation Prototype for Emergency Management Information System").

ORNL researchers revised a simulation model to evaluate various protective action strategies for chemical weapons accidents. The new version is capable of comparing two protective action scenarios, changing single

parameters, and providing pop-up screens for data input (see Sect. 2.3.2).

Researchers applied the National Infrastructure Information System model developed by ORNL to an emergency assessment exercise that hypothesized an externally produced nuclear power plant disaster. The model generated potential fallout zones, economic production capacity lost, and the resulting distribution of county industrial capacity loss rates (see Sect. 3.3.4).

Researchers completed six of eight initial evacuation time estimate studies under the Chemical Stockpile Emergency Preparedness Program. Improved methods for collecting daytime population estimates and associated vehicle use rates are currently being incorporated into traffic simulation models (see Sect. 4.2.2).

1.1.4 Developing Country Analysis

The Symposium on Electricity and the Environment, organized by 11 international agencies as an important preliminary to the 1992 United Nations Conference on the Environment and Development, was held in May 1991. Conclusions of the symposium are presented in this report (see Sect. 6.4).

ORNL researcher Keith Kline continues to oversee the establishment of the Maya Biosphere Preserve in Guatemala. This project seeks to improve the long-term economic outlook of Guatemala's population through the rational management of their renewable natural resources (see Sect. 6 highlight, "The Mayarema Biosphere Preserve Project").

Korea was studied as an example of how a country short on resources was able to finance its utility development through private power-plant construction, pricing, and operational efficiency improvements (see Sect. 3.3.2).

ORNL researchers continued studies of energy and environmental policy in China. China's energy-supply alternative to coal, biomass production and conversion, has received the least systematic attention until now (see Sect. 3 highlight, "China's Evolving Energy and Environmental Policy" and Sect. 6 highlight, "Innovative Uses of Biomass Energy in China").

1.1.5 Transportation Analysis

Research staff members conducted a study on the cost-effectiveness of increased automotive fuel economy as a means to reduce atmospheric hydrocarbon emissions. The study indicates that total benefits of increasing new car fuel economy from 28 to 40 mpg are roughly the same as for revising on-board refueling controls or reducing tailpipe emissions to new Clean Air Act levels (see Sect. 4.2.1).

ORNL is currently assisting the Federal Highway Administration in generating alternative candidate national highway networks for the year 2020. Goals such as traveler mobility, equity, intercity trade, and connectivity involving national security are being translated into network highway design and selection criteria. Candidate highway networks are being evaluated and mapped (see Sect. 4.2.2).

Researchers continued a cost and benefit analysis of increasing automotive fuel economy. The detailed analysis includes quantitative consideration of such diverse aspects as the effects of conservation technologies on safety and the transfer of wealth from U.S. consumers to oil producers (see Sect. 4.2.3).

An analysis of vehicle fuel economies, sales, and market shares shows that the new 1990 automobile fleet experienced a fuel economy loss of 0.4 mpg from the previous model year, dropping to 27.6 mpg. The new 1990 light truck fleet increased 0.3 mpg from the previous year to a current 20.5 mpg (see Sect. 4.3.3).

ORNL staff members provided insight into a strategic plan for Intelligent Vehicle Highway Systems (IVHSs), for submission to Congress by the Department of Transportation. IVHS applies advanced technologies to improve the operational performance of the U.S. highway system (see Sect. 4 highlight, "Intelligent Vehicle Highway Systems").

1.2 ENERGY CONSERVATION TECHNOLOGIES

Energy conservation technologies cover (1) building equipment, (2) building envelopes, (3) existing buildings, and (4) electric power systems. Work in the building equipment area includes developing thermally activated heat pumps for residential and commercial applications, novel cycles, and refrigeration

systems. Building envelopes research focuses on energy efficiency in walls, foundations, roofs, attics, and building materials, while research on existing buildings examines technical and implementation issues for improving energy efficiency in existing buildings. Electric power systems research concentrates on developing technology options for increased transmission and distribution capacity, integrating new technologies, and developing enhanced control and operation strategies for future electric power systems. The following sections present a summary of major research activities.

1.2.1 Building Equipment

Thermal efficiency goals were achieved for the residential generator-absorber heat exchange absorption heat pump. The compact laboratory package unit, developed by a subcontractor, demonstrated coefficients of performance of 1.6 in heating and 0.7 in cooling (see Sect. 5.2.1).

A subcontractor completed a dynamic analysis of starting and stability of the conceptual free-piston Stirling-engine-driven heat pump design. Design work and component testing in connection with the development of a low-cost Stirling-engine combustor using low-pressure natural gas were also completed (see Sect. 5.2.1).

A collaborative R&D agreement (CRADA) was established with a consortium of chemical manufacturers to assess the total global warming impact of chlorofluorocarbon (CFC) alternatives. The study indicates that CFC-user industries have substantially approached near-equal energy efficiency with many of the CFC alternatives (see Sect. 5 highlight, "Alternative Fluorocarbons Environmental Acceptability Study Collaborative Research and Development Agreement").

To develop efficient alternatives to CFC-12, researchers conducted experimental and analytical studies of advanced two-evaporator refrigeration cycles for refrigerator/freezers. An advanced cycle that uses nonazeotropic refrigerants proved to be 10–15% more efficient in steady-state operation than the original refrigerator/freezer using CFC-12 (see Sect. 5.2.3).

Also, construction of an experimental apparatus with a vertical-tube lithium bromide-water falling-film type absorber was completed. Preliminary tests were conducted to

characterize smooth-tube performance (see Sect. 5.2.4.1).

1.2.2 Building Envelopes

Measurements on various loose-fill fiberglass attic insulation confirmed that significant natural convection heat loss can occur under cold winter conditions and, in some loose-fill fiberglass insulation, can be responsible for up to half of the heat lost at very low attic temperatures (see Sect. 5 highlight, "Attic Testing").

ORNL has conducted field testing of boardstock foam insulations blown with halogenated CFC (HCFC) for over 2 years. Conclusions from thermal performance and mechanical property measurements show that all of the HCFC alternatives have acceptable behavior and could be considered as replacements for the CFC-11 blown polyisocyanurate board currently used in over half of the low-sloped roofs in the United States (see Sect. 5.4.1).

Two handbooks targeted at residential builders and contractors were completed and distributed: the *Builder's Foundation Handbook* and the *Moisture Control Handbook* (see Sect. 5.4.2).

1.2.3 Existing Buildings

A field test was initiated to measure the actual cooling energy savings and change in electric demand profiles due to exterior insulation retrofit on walls of concrete block houses (see Sect. 5.5).

A consumer-oriented fact sheet on the use of radiant barriers in residential attics was completed and published (see Sect. 5.5).

Also, a pre-prototype system was developed for high-speed collection of electrical power data in buildings (see Sect. 5.5).

1.2.4 Electric Power Systems Technology

Construction began on a high phase-order transmission line demonstration project to convert an existing 1.5 mile double-circuit three-phase line operating at 115 kV line-to-line to six-phase operating at 161 kV line-to-line. The line's performance will be analyzed following completion of construction (see Sect. 5.10.1.3).

A summary of the electromagnetic pulse (EMP) research program was completed and published. The summary concludes that a nominal high-altitude EMP environment with a peak electric field of tens of kV/m, followed by a magnetohydrodynamic EMP of less than 20 V/km, would disturb electric power systems. However, major power failures are not expected (see Sect. 5.10.2).

This year, ORNL was given management and coordination responsibilities for a significant part of the DOE research on biological effects associated with electric and magnetic fields (see Sect. 5.10.4).

1.2.5 Other Activities in Energy Conservation Technologies

ORNL continues to track the progress of inventors whose technologies are supported by the DOE Energy-Related Inventions Program. Through FY 1990, 23 spin-off applications have generated \$32 million in sales, representing 6% of total sales attributable to the program (see Sect. 5.6).

A District Heating, Cooling, and Cogeneration (DHC/C) Workshop was held to formulate an action plan that will promote the application and growth of DHC/C in the United States for the 1990s (see Sect. 5.9).

A prototype of an electron attachment leak detector for discovering R-134a leakage has been built and successfully tested (see Sect. 5.3).

1.3 MILITARY TRANSPORTATION

Research and development on military transportation deals with conceptualizing new approaches to planning and executing strategic deployment of personnel and materiel. Some highlights from this year's work are summarized in the following section.

1.3.1 Military Transportation

New analytical tools have been designed and incorporated into the Flow and Analysis System (FAST) for the U.S. Transportation Command. FAST is a prototype set of analysis tools to meet DOD's needs for analysis of deployments during deliberate planning, exercises, and real-world contingencies (see Sect. 4.4.1).

In October 1990, the Airlift Deployment Analysis System (ADANS) was selected as the Military Airlift Command's exclusive Operation Desert Shield and Storm airlift scheduling system (see Sect. 4 highlight, "Airlift Deployment Analysis System Supports the Operation Desert Storm Airlift").

Staff members have designed and prototyped the Worldwide Household Goods Information System for Transportation Modernization to fully automate the Military Traffic Management Command's tracking of household goods (see Sect. 4.4.2).

Integrated

Analysis and Assessment

ORNL-Photo 1513-92

Bob Reed, Section Head

2. INTEGRATED ANALYSIS AND ASSESSMENT SECTION OVERVIEW

2.1 INTRODUCTION

The Integrated Analysis and Assessment Section (IAAS) conducts research in the physical and social sciences and prepares environmental assessments (EAs) and environmental impact statements (EISs) for various federal agencies to comply with the National Environmental Policy Act (NEPA). As a result of past NEPA activities, the section has developed expertise in such areas as emergency preparedness, radioactive-waste management, siting and characterizing geohydrologic systems for waste-disposal facilities, contaminant-transport modeling in atmospheric and aqueous systems, public acceptance of hazardous technologies, institutional mechanisms for managing complex technologies, socioeconomic impacts of technological change on communities, and global environmental decision making. IAAS specializes in research and applied work in these and related areas, both independently and in collaboration with other divisions at Oak Ridge National Laboratory (ORNL).

2.2 NEPA PROJECTS

In the NEPA area, IAAS oversees all EAs and EISs prepared by ORNL for the U.S. Department of Energy (DOE) and other federal agencies. This work is performed as needed by multidisciplinary teams from IAAS, Energy Division, other ORNL divisions (particularly Environmental Sciences, Health and Safety Research, Chemical Technology, Engineering Technology, and Research Reactors), and subcontractors.

The section provides NEPA support to a diversity of federal agencies, including DOE, the Nuclear Regulatory Commission (NRC), the Army and Air Force, the Federal Energy Regulatory Commission (FERC), the National Science Foundation (NSF), and the National Park Service. Table 2.1 provides a partial listing of NEPA projects under preparation in fiscal year

(FY) 1991. The scope of these projects varies from consideration of broad programmatic issues to evaluation of impacts of specific actions at a given site.

During FY 1991, the section continued to support the NRC in developing a generic EIS (GEIS) associated with renewal of licenses for commercial nuclear power plants. The draft GEIS was published by NRC for public review in August 1991 and will be revised in response to submitted comments. The GEIS will be used to support NRC rule making and will help limit the issues addressed in NEPA documents prepared for specific license-renewal applications. This year, IAAS also completed work for the NSF on a Supplemental EIS (SEIS) on the U.S. Antarctic Program. The draft SEIS was published for public comment in December 1990, and the final SEIS was completed by the end of the fiscal year. The SEIS evaluates current programs for improving safety, environment, and health protection. It will be used by NSF's Division of Polar Programs in assessing future research activities and facilities that could affect the pristine antarctic environment.

IAAS continued to support the Army's Chemical Stockpile Disposal Program (CSDP), which is responsible for destruction of the nation's lethal unitary chemical agents and munitions stored in the continental United States. During FY 1991, the final EIS on the stockpile at Anniston Army Depot (ANAD) in Alabama and the draft EIS on the Umatilla, Oregon, stockpile were published; and work continued on various phases of three other EISs. The section also continued support for DOE's Clean Coal Program, preparing a draft EIS on the Healy Clean Coal Power Plant in Alaska and an EA on an integrated gasification combined-cycle facility in Springfield, Illinois.

During the latter part of 1991, IAAS initiated two new EAs for FERC to evaluate potential, cumulative environmental impacts from hydroelectric development in the Skagit and Nooksack river basins in Washington state. The

(text continues on page 2-4)

Table 2.1. Partial listing of fiscal year 1991 National Environmental Policy Act projects

Project	Sponsor ^a
Environmental Assessments	
Sale of Parcel A to the city of Oak Ridge	DOE
Reduction of polychlorinated biphenyl contamination in ventilation ducts at the Portsmouth and Paducah gaseous diffusion plants	DOE
Installation of waste water treatment facilities at the Kansas City Plant	DOE
Demonstration of uranium-atomic vapor laser isotope separation at Oak Ridge, Tennessee	DOE
Retrievable solid transuranic (TRU) waste operations at Oak Ridge National Laboratory (ORNL)	DOE
Contact-handled and remote-handled TRU waste facilities at ORNL	DOE
Melton Valley Low-Level Waste Collection and Treatment System Upgrade, Oak Ridge, Tennessee	DOE
Receipt and storage at ORNL of TRU waste from Nuclear Fuel Services, Inc.	DOE
Coal Gasification Project, Ft. Martin, West Virginia	DOE
Integrated Gasification Combined Cycle and Clean Coal Demonstration Project in Springfield, Illinois	DOE
Demonstration of coal reburning for cyclone boiler nitrogen oxides control at the Nelson Dewey Generating Station, Wisconsin	DOE
Cumulative impacts of hydropower development in the Skagit River Basin, Washington	FERC
Cumulative impacts of hydropower development in the Nooksack River Basin, Washington	FERC
Development of the Rocky Point Pumped Storage Hydroelectric Project, Colorado	FERC
Development of C-17 facilities at Kelly Air Force Base	USAF
Defense Meteorological Satellite Program Facility Modification at Vandenberg Air Force Base	USAF
F-16 sorties with live munitions, Kelly Air Force Base, Texas	USAF
Construction of a boundary fence at Cheyenne Mountain Air Force Base	USAF
Environmental Impact Statements	
Healy Clean Coal Demonstration Project in Alaska	DOE
Hawaii Geothermal Project	DOE
Environment, safety, and health improvements for the U.S. Antarctic Program	NSF
Relicensing of nuclear power plants in the United States	NRC
Disposal of chemical munitions and agents stored at Anniston Army Depot	Army
Disposal of chemical munitions and agents stored at Umatilla Depot Activity	Army
Disposal of chemical munitions and agents stored at Pine Bluff Arsenal	Army
Disposal of chemical munitions and agents stored at Aberdeen Proving Ground	Army
Disposal of chemical munitions and agents stored at Pueblo Depot Activity	Army
Disposal of chemical munitions and agents using cryofracture or incineration demonstration plant	Army
Environmental Reports	
Advanced Neutron Source Facility	DOE
Construction of Section 8D of the Foothills Parkway near Gatlinburg, Tennessee	NPS

^aSponsors are abbreviated as follows: DOE indicates U.S. Department of Energy; FERC, Federal Energy Regulatory Commission; USAF, U.S. Air Force; NSF, National Science Foundation; NRC, Nuclear Regulatory Commission; NPS, National Park Service.

DRAFT ENVIRONMENTAL IMPACT STATEMENT (EIS) ON THE HEALY CLEAN COAL PROJECT

As part of the environmental support for the U.S. Department of Energy (DOE) Clean Coal Technology (CCT) Program, a draft EIS was prepared to assess environmental issues associated with the Healy Clean Coal Project (HCCP), a demonstration project cost-shared by DOE and the project participant, the Alaska Industrial Development and Export Authority. The goal of the CCT Program, a planned \$5 billion national commitment, is to provide the U.S. energy marketplace with several more efficient, reliable, and environmentally sound coal-utilization and pollution-control technologies.

The HCCP would be a new 50-MW coal-fired power-generating facility built adjacent to the existing 25-MW Healy Unit 1 conventional pulverized-coal unit owned and operated by Golden Valley Electric Association, Inc. (GVEA) in rural Healy, Alaska, located approximately 100 miles southwest of Fairbanks and 250 miles north of Anchorage (Fig. 2.1). The site is approximately 4 miles from the nearest border of Denali National Park and Preserve (DNPP) and 8 miles north of the park entrance. The HCCP would use low-sulfur coal from the nearby Usibelli Coal Mine (UCM). After a 1-year testing period, commercial operation of the HCCP would begin. Intended to demonstrate the combined removal of sulfur dioxide (SO_2), nitrogen oxides (NO_x), and particulate matter (PM), the HCCP would use innovative combustion and flue gas cleanup technologies. The

draft EIS considers the proposed action, a no-action alternative, and an alternative site.

Impacts to air quality, surface water, groundwater, ecological, and socioeconomic resources from use of the HCCP at the proposed site were evaluated and, for most resource areas,

ORNL-DWG 91M-13334

Fig. 2.1. Location of Healy Clean Coal Project.

found to be insignificant. Impacts to air quality and visibility expected from HCCP operation are of primary concern, as predicted by computer models. Analyses of visibility impacts indicated that a yellowish-brown plume from HCCP emissions might occasionally be perceptible along the Nenana River Valley at the eastern edge of DNPP, about 2% of the time during fall and 5% during winter. For cumulative impacts from the HCCP and Healy Unit 1, a visible plume was predicted about 3% of the time during fall and about 10% during winter. Plume perceptibility during summer, the peak season for DNPP, is expected to be no greater than predicted for fall. Views from the DNPP interior are not expected to suffer adverse effects.

During winter, the length of ice-free water downstream of the proposed site should increase from the current 4 miles to about 9 miles during combined operations of the HCCP and Healy Unit 1. Therefore, the thermal discharges of cooling water might affect ice-bridge formation (used by residents to transport supplies) on the Nenana River at the village of Ferry, located about 13 miles downstream. Even if the river were to freeze during combined operation, remnants of the thermal plume reaching Ferry would probably cause a delay in freezing at the beginning of winter and an earlier breakup of the ice sheet in spring.

The no-action alternative would result if DOE does not provide cost-shared funding support for the HCCP. In addition to not demonstrating these advanced technologies, two reasonably foreseeable scenarios could result. First, GVEA could continue to operate Healy Unit 1 and buy natural-gas-generated power from Anchorage utilities without building new generating facilities, with no changes in operations. Coal requirements and electricity generated for the existing plant would remain constant. Consequently, impacts would remain unchanged from the baseline conditions.

Second, a conventional coal-fired power plant, equivalent in capacity to the proposed project with conventional flue-gas desulfurization, could be built at Healy without DOE's financial assistance. Best-available control technology would be used, including dry scrubbers using lime to remove SO₂ from the flue gas, low-NO_x burners, and a baghouse to remove PM. The dry scrubbers would generate a solid waste that, along with PM from the baghouse, would be returned to the UCM for disposal. Impacts for this scenario would closely match HCCP impacts for most areas because projected resource requirements and discharges are nearly identical.

The EIS also considers an alternative site located about 4 miles from the proposed site. Environmental effects generally would be greater at the alternative site because the proposed site has already been disturbed by Healy Unit 1. The final EIS will be used by DOE in determining funds for the project. ♦

section also participated in the FERC scoping process for the proposed Rocky Point pump storage facility near Gunnison, Colorado.

2.2.1 Site-Specific EIS for the Destruction of Chemical Weapons at ANAD

Under a mandate from Congress and in agreement with international disarmament treaties, the U.S. Army has been directed to destroy the entire U.S. stockpile of lethal unitary chemical munitions (i.e., those filled with nerve gas or blister agents). ANAD, at Anniston, Alabama, is one of eight depots where such munitions are stored (7% of the U.S. total, by weight) and where the Army proposes to conduct disposal activities (Fig. 2.2). ORNL assisted the Army in preparing a site-specific EIS that examines potential environmental impacts of constructing a facility for destroying the ANAD chemical-weapon inventory.

Analyses in the EIS focus on potential environmental impacts and socioeconomic effects associated with construction and disposal activities.

The disposal technology to be used at ANAD is a munition-disassembly process followed by incineration of the chemical agents and all associated munition parts—including explosive components. Using a variety of analytical and computer techniques (Fig. 2.3), analyses in the EIS focus on potential environmental impacts and socioeconomic effects associated with construction and disposal activities. For comparison, the assessment also

ORNL-DWG 89-10459

Fig. 2.2. Site of proposed disposal facility at Anniston Army Depot in 20-km, 50-km, and 100-km zones.

includes continued storage of the ANAD inventory.

Routine disposal operations and hypothetical accidents were both included in the analyses. Key concerns included possible impacts on air and water quality and on local endangered species. A probabilistic risk assessment addressed potential human health impacts from accidental releases of chemical agents. Atmospheric dispersion of accidentally released chemical agents was modeled to determine the downwind hazard and provide a basis for impact assessment.

The draft EIS was issued in November 1990; the final EIS, in June 1991. The Army issued a Record of Decision (ROD) in July 1991 specifying that the proposed disposal activities would indeed be conducted at ANAD and selected a location for the facility in the north-central portion of the depot, which the EIS identifies as environmentally preferable. To decrease the possibility and consequence of severe accidents, the ROD also specified enhancements to facility design and operation, as well as an emergency preparedness program for ANAD and surrounding areas.

(text continues on page 2-7)

ORNL-DWG 89-7343R

Fig. 2.3. Computer-generated, three-dimensional representation of the topography at Anniston Army Depot, for use in assessing potential local environmental impacts.

IMPACTS OF HYDROPOWER IN THE NOOKSACK AND SKAGIT RIVER BASINS

Development activities sometimes have impacts far beyond their immediate areas. Hydroelectric development and logging in the Pacific Northwest, for example, have eliminated numerous salmon subspecies and put many others at the brink of extinction. Extensive logging has nearly eliminated the region's ancient forests and the species that depend on them (e.g., the controversial northern spotted owl). The Federal Energy Regulatory Commission (FERC) asked Oak Ridge National Laboratory (ORNL) researchers to evaluate the potential cumulative environmental impacts from 19 hydroelectric projects proposed in the Skagit and Nooksack river basins (Fig. 2.4). Researchers taking part in this study examined potential impacts to river-spawning fish (primarily salmon), terrestrial ecology (e.g., spotted owl and ancient forests), recreation, and cultural resources.

The principal concern for salmon was the possibility of increased sedimentation from the proposed development adversely affecting spawning and rearing habitats. In most parts of the basins, the mountains are composed of surficial materials that are stabilized by the overlying forest. Removal of these forests by clearcut logging significantly increases erosion and frequency of landslides, which can result in damage to salmon

habitat and disruption of terrestrial habitats. Most of the proposed hydroelectric projects include long penstocks, containing millions of gallons of pressurized water, that could be ruptured by landslides, causing more erosion than the original landslide and resulting in significant harm to salmon habitat.

In unlogged areas, pipeline rupture from landslides is less likely, but other resources could be at risk. The few remaining unlogged areas in the basins support most of the important terrestrial ecology and recreation—as well as many of the remaining areas for Native American cultural use. These resources are all sensitive to the disturbance that would result from proposed hydropower projects. The ORNL study found that most of the proposed projects, except those targeted for previously disturbed but relatively stable areas, could contribute to cumulative adverse impacts. ORNL's study was used by FERC decision makers in determining the level of National Environmental Policy Act review needed for each project. Further, ORNL will continue to assist FERC in preparing site-specific environmental assessments and impact statements on each of the hydropower projects proposed in the basins. ♦

ORNL-DWG 91-16517

Fig. 2.4. Skagit and Nooksack river basins are the location for 19 proposed hydroelectric projects.

Researchers from Oak Ridge National Laboratory and the Federal Energy Regulatory Commission visit forested areas that could be affected by proposed hydroelectric developments.

Construction of the facility should begin in early 1993; disposal of the ANAD inventory is expected to take 38 months, after which the facility would be dismantled.

2.3 EMERGENCY PREPAREDNESS

2.3.1 Chemical Stockpile Emergency Preparedness Program

The Hazard Management Group continues to support the Chemical Stockpile Emergency Preparedness Program (CSEPP), which is jointly operated by the Army and the U.S. Federal Emergency Management Agency. The group performed the following tasks in FY 1991:

- development of the Program Guidance Document and Planning Standards,
- development of a Prototype Automated Decision Support System,
- refinement of a model to estimate dose reduction from protective actions,

- development of training materials for emergency medical technicians,
- assessments of the acoustical coverage of outdoor siren system designs at the eight sites,
- development of Emergency Broadcast System Message Protocols,
- preparation of a handbook on conducting focus group discussions with the public, and
- development of an exercise handbook and evaluation methodology.

The Hazard Management Group also took the lead in managing and coordinating work on CSEPPs conducted outside IAAS, including preparation of quantitative evacuation time estimates, development of re-entry guidelines, and testing of protective clothing for permeation by simulated agents.

2.3.2 Dose Estimate Model

ORNL has developed a simulation model to evaluate various protective-action strategies for

(text continues on page 2-10)

AUTOMATION PROTOTYPE FOR EMERGENCY MANAGEMENT INFORMATION SYSTEM

In fiscal year (FY) 1991, IAAS developed a prototype of an Emergency Management Information System (EMIS), based on the philosophy that the functions of an automated emergency management system are parallel but not identical to emergency management functions as traditionally conceived by emergency managers. This is because some automated functions may support many traditional functions. For example, traffic management is a matter of formulating procedures (the where and how) and of managing resources associated with facilitating traffic flow (policemen or volunteers). From the perspective of automation, traffic management can be handled through generic procedures and resource management functions, if those are flexibly designed. The same procedures and resource management modules can be used to manage many other traditional functions. In fact, procedures and resource management are essential for nearly every emergency management function.

The prototype in question was based on the generic requirements of an EMIS. Table 2.2 summarizes the generic functional requirements associated with an EMIS and the potential applications of each. These requirements

represent the critical areas in which an EMIS provides assistance to emergency managers.

Near real-time capabilities are required to handle data collection from agent monitors, meteorological stations, critical facility operations, and other automated indicators of potential problems. Manual data input is required for the detection of hazards from human observation in connection with the stockpile, emergency operations and response, and as backup to real-time monitors (should they fail).

The ability to locate key inventory, resources, and personnel—and to graphically display those locations—is needed. Mapping capability also allows emergency officials to locate populations at risk, potential exposures, and sample coverage.

The EMIS should not only activate alarms when critical tasks are required, but also keep an ongoing record of information flow and decision making. This record should be permanent, unalterable, and show the progression of events throughout any emergency.

A relational data base is at the heart of the system, distributing and updating information among the various parties. It is useful for

ORNL-Photo 1508-92

A relational data base is at the heart of the Emergency Management Information System.

tracking resources, personnel, and equipment, as well as for monitoring exposure, population response, and command structure.

Analytic and modeling capabilities are required to calculate exposures, source terms, and effectiveness of various critical functions, such as protective actions. These models and analyses are critical in monitoring an accident and its emergency response.

Procedures will essentially guide emergency operations and re-entry phases and are likely to result from a task analysis that will help emergency managers avoid failures to perform critical functions during specific operations. The associated checklists also provide a record of performance and help assure compliance with guidelines.

Communication and ring-down provide specific mechanisms for establishing and maintaining effective communication among people involved in emergency response and offer timely implementation of communication channels. Like communication and ring-down, warning-device activation considers the timely activation of a communication channel, with the major difference being the receiver. Controlling the activation of public warning devices and channels from the EMIS is a critical system function.

The ongoing monitoring of time, elapsed time, and criticality is essential for an effective EMIS. In addition, the system must provide easy linkage to more routine operations (such as word processing and graphics functions) for effective communication to all concerned. ♦

Table 2.2. Generic system requirements and potential applications

Generic requirement	Potential applications
Near-real-time data	Facility parameters; agent monitors; meteorology monitors; seismology; transponder movement during transport; traffic-flow monitors
Manual data inputs	Event detection; resource tracking; backup real-time data; traffic reports
Mapping	Site; site area; installation; community
Reporting	Chain of command; event logging; alarms
Relational data base	Locational Geographical Information System; inventory; resources; personnel; protocols; population exposure; institutions; command authority; warning devices; protective-action effectiveness (public and institutions)
Analysis	Accident classification; monitor protective action capacity
Modeling	Meteorology; dispersion; protective action; traffic flow
Procedures	Traffic access and control; notification; protective-action selection; monitoring; shelter registration; sampling; decontamination; reentry teams; public affairs
Communications	Facility with Emergency Operations Center (EOC); field with EOC; FAX or other equivalent written message
Ring-down	Chain of command; emergency personnel; institutions; plant operator
Warning-device activation	Siren controller; tone or alert radio controller; telephone ring-down; pagers
Time monitoring	Alarm critical events and activities; record times in event log; track critical events
Support	Word processing; drawing; charts

chemical weapons accidents. Given an accident scenario and its response, the Protective Action Evaluator for Chemical Emergencies (PAECE) model generates estimates of downwind dosage and exposure reduction. Imbedded in the system is the Army's Gaussian plume atmospheric dispersion code for chemical agents. To analyze a scenario with the initial model, a single-run version operating under DOS required that the user input the entire data set for each model run. The user interface for this version was cumbersome and did not allow for near real-time application in an emergency. In September 1991, a version was released capable of comparing two protective actions at five different downwind distances. Additionally, the user can load a predefined scenario or change a single parameter and rerun the model. Finally, the interface was changed to include pop-up screens that allow users to input values or use a point-and-click technique to set parameters of the scenario. This version, programmed in THINK C, runs under the Macintosh operating system. Figure 2.5 shows an example of a PAECE data-input screen.

Fig. 2.5. Example of a PAECE data-input screen.

2.4 APPLIED PHYSICAL SCIENCES

IAAS continued to support safety analysis, radioactive-waste management, and environmental restoration activities. Involvement in the safety analysis programs was expanded this fiscal year to include site analysis and characterization

of the geology and hydrogeology of the Y-12 Plant. Environmental Restoration (ER) Program activities also increased to include geology and hydrogeology of the K-25 Site, as well as ORNL.

2.4.1 Gaseous Diffusion Plant Safety Analysis Upgrade Program

The primary emphasis of IAAS activities in the safety analysis area was (1) the evaluation of the potential flooding of major rivers near the Paducah and Portsmouth gaseous diffusion plants (GDPs) and (2) the development of groundwater models for evaluating the effects of normal and accidental releases of hazardous materials. This work contributes to the Safety Analysis Reports (SARs) that are being upgraded to meet the more stringent requirements of DOE Order 5480.1B. As part of the SAR, these new requirements mandate consideration of natural phenomena hazards that include extreme floods as well as groundwater contamination from normal and accidental operations.

The extreme flooding event for each GDP is prescribed with an annual exceedance probability of occurring once in 10,000 years. The GDPs are required to have adequate capabilities to secure the facility during the flood and continue operations following the event. Evaluations of such extremely unlikely events at the Paducah GDP are complicated by its proximity to the Ohio River. Extreme flood forecasts beyond a frequency of 500 years are not supported by the U.S. Army Corps of Engineers (who have the regulatory responsibility for the Ohio River), because of the watershed size (203,000 square miles) and the observation that floods result from storm sequences rather than from a single storm.

Analysis for the Paducah GDP was performed using deterministic methodology associated with the Probable Maximum Flood (PMF). This approach was chosen because it has a record of being defensible and could be applied to the Ohio River system. The flood discharge was specified using NRC Regulatory Guide 1.59, and the flood stage was determined with the HEC-2 flood stage predictive model developed by the U.S. Army Corps of Engineers and extended to consider events at the Paducah GDP. Results indicate that the Paducah GDP grade was above the PMF and appears to have a frequency substantially larger than the 10,000 year

exceedance criteria. However, some below-grade structures could be affected by such an extreme flood. The importance of these structures to facility safety is still under consideration. A similar analysis was performed for the Portsmouth GDP using probabilistic flood forecasting techniques. Results indicate that the Portsmouth facility is well above the flood stage associated with the nearby Scioto River.

Groundwater transport models were developed for both the Paducah and Portsmouth GDPs. Conceptualization of groundwater flow systems and numerical model input parameters was based on available data, much of which resulted from the ER Program. The models, which used the FTWORK Code developed by GeoTrans, were developed to resolve contaminant releases from individual facilities within the plant site and were made site-specific to represent both geology and hydrology. The complex hydrogeology at Paducah—which includes several interconnected aquifers that are highly dependent on localized leakage between aquifers and the effects of the Ohio River on groundwater regime—proved to be especially challenging. The results of this code development (Fig. 2.6) will be used to evaluate the consequences of plant operations. Further, the models are being considered for use by the ER and waste management programs at each plant for evaluating historical as well as future events.

2.4.2 Hydrogeologic Support for ER Program

IAAS geoscientists participate in a broad range of ER programs. Involvement includes participation in the ER Program Technical Oversight Committee, which acts as a steering committee for site investigations at all DOE–Oak Ridge facilities. Experience gained by IAAS geoscientists through a variety of project activities at all five DOE facilities managed by Martin Marietta Energy Systems, Inc., provides numerous vital insights. Participation in the Technical Integration Committee for the ER Program is a local activity that directs the site-specific investigation and assessment planning for all waste area groupings at ORNL. Additionally, the IAAS geoscientists prepare and interpret geologic and hydrologic data, which leads to additional field investigations to characterize sites for baseline risk assessments

and to support feasibility studies for remedial technology selection and design. The group has developed key resources in data handling and interpretation, coupled with the use of groundwater models to verify site interpretations. During FY 1991, ER Program activities at K-25 focused on interpreting groundwater data and drafting a plan for additional site investigations for three solid-waste management units and a surface-water holding pond. ER Program activities at ORNL involved extensive interface, including interactions in the field, with subcontractor staff performing the Phase I Site Investigation of the main plant area at ORNL. Continuing studies include research in groundwater-model development for solute behavior and remedial design assessment.

ORNL-Photo 1507-92

Groundwater models are used to aid in the characterization of the underground migration of hazardous wastes. [Left to right: Harriet Hardee (University of Tennessee), Dick Ketelle, Don Lee, John Bownds, Mark Yambert (Computing and Telecommunications Division).]

Fig. 2.6. Groundwater transport models for Paducah Gaseous Diffusion Plant using FTWORK Code developed by GeoTrans.

2.5 TECHNOLOGY AND SOCIAL SYSTEMS

Research in the area of technology and social systems is directed at understanding the institutional mechanisms by which society manages technologies. It is critical to understand the full potential impacts of technology on society so that appropriate institutional responses can be implemented to guide technological development. For society, it is vital that those institutions reflect a high level of public trust, operate according to procedures to which society has given its consent, and provide for an equitable distribution of cost and risk liabilities in implementing the technology.

To further these objectives, IAAS staff maintained a variety of projects during the year. NEPA projects again played a central role. Projects in the Army's CSDP (Sect. 2.2) provided an opportunity to examine how host communities respond to technological changes generated by an outside institution. Community concerns have focused not on traditional impacts to local public and private infrastructures from commuting workers, but instead have centered on perceived risks of on-site disposal.

Another project studied the socioeconomic aspects of an environmental report for the National Park Service on proposed construction and operation of Segment 8D of the Foothills Parkway near the Great Smoky Mountains National Park. Predictions of impacts occurring from Parkway operations required projection of likely land-use changes prior to completion of construction by the year 2005. Baseline projections were made with the help of local realtors, based on two different pre-Parkway scenarios of study-area growth. Eventually, these baseline land-use conditions will be used to predict postconstruction land-use impacts, as well as impacts in such areas as housing and public services.

Socioeconomic impacts to public and private infrastructures around seven operating nuclear power plants were assessed as part of NRC's GEIS on license renewal for nuclear plants (Sect. 2.2). Most plant areas experienced few adverse impacts during construction or operation. Road congestion did occur at several sites because of the local road network. In very rural areas and communities with strict development codes, housing availability was a problem for workers.

Growth-induced socioeconomic impacts were identified in the proposed construction of a demonstration clean-coal power plant at Healy, Alaska (see Sect. 2 highlight, "Draft Environmental Impact Statement on the Healy Clean Coal Project"). The area, just north of Denali National Park, is rather remote. The town has only about 600 residents and would likely experience difficulty in providing housing and services to the estimated 285 workers required to build the plant. As a result, the proponent is examining the possibility of building a construction camp for most of the workers.

IAAS staff were involved in analyzing ongoing Integrated Resource Planning work in FY 1991. This required studying demand-side management (DSM) collaboratives. Outside of the traditional regulatory process, collaboration among utilities and nonutility parties is a new approach to problem solving that attempts to reach consensus among often-times adversarial parties. IAAS staff examined nine cases, involving 24 utilities and approximately 50 nonutility parties in 10 states, in which participants representing various interests worked together to design mutually acceptable DSM programs and policies. The study will be completed early in FY 1992, at which time a report will be published

It is critical to understand the full potential impacts of technology on society so that appropriate institutional responses can be implemented to guide technological development.

containing descriptive material, advantages and disadvantages of the collaborative process, and recommendations for improving new and ongoing collaboratives.

Decision making was also the focus of a project associated with ORNL's Global Climate Change Program. This effort, presently in progress, is examining the institutional and economic capabilities, opportunities, and constraints of major international contributors to greenhouse gas emissions. These contributors include the United States, China, the European Community, India, Indonesia, and the former

Soviet Union. This project will help DOE understand what kinds of international policies would be reasonable in addressing global-warming issues.

IAAS staff concluded a project for the Army National Guard that focused on factors contributing to unit effectiveness. IAAS conducted two sets of interviews with battalion-level Guard personnel. Information from the first interview, which consisted of open-ended questions about factors contributing to unit success, was categorized into ten criteria defining unit success. In the second interview, respondents were asked to rank the criteria in order of importance. Leadership was consistently identified as the most important criterion. Availability of funding and equipment, as well as quality of recruiters and the recruiting process, were identified as the least important.

Several projects relating to impacts on cultural resources were conducted for the U.S. Air Force. A cultural resources management plan was developed for Cheyenne Mountain Air Force Base, Colorado. Further, cultural resource surveys were conducted for Clear Air Force Station, Alaska, and Cavalier Air Force Station, North Dakota. No resources were identified at any of the facilities in the areas surveyed.

Cultural resources, along with recreational resources, were assessed for potential adverse impacts from the licensing of small hydroelectric dams on the Skagit and Nooksack rivers in

areas. Using a methodology developed for the region by the National Park Service, potential archaeological sites on stream terraces were identified in areas that would be affected by several proposed dam projects. In respect to recreation, the major concern was impact to protected areas, such as wilderness areas and wild and scenic river segments in the Mt. Baker-Snoqualmie National Forest. Several proposed dam projects could allow too much unintended access to pedestrians and recreational vehicles.

2.6 ENERGY AND ENVIRONMENTAL ANALYSES

2.6.1 The External Costs of Fuel Cycles Project

In today's energy market, the prices of using energy do not include all the costs and benefits of producing and delivering energy. Airborne emissions from coal-fired power plants, for example, can not only cause human illness but can also add nutrients for plant growth. However, neither of these effects is reflected in electricity prices. Where these external effects are large, producers and consumers may be responding to the "wrong" price signals for their energy choices. Unfortunately, estimates for external costs and benefits, and the extent to which they are reflected in market prices, have only recently become serious research topics.

Preparers of the 1990 *National Energy Strategy* recognized that the lack of high-quality information on external costs and benefits was distorting federal and state decision making. Consequently, DOE launched a major initiative to provide best-practice information about the external physical impacts of energy use and how these impacts should affect planning and investment. The European Communities began similar efforts to address external costs in the context of Western European energy planning.

In February 1991, W. Henson Moore, Deputy Secretary of the DOE, and Filippo Maria Pandolfi, Vice President of the Commission of the European Communities (CEC), signed a joint statement regarding the external costs of fuel cycles. This 18-month agreement commits the respective organizations to "develop a comparative analytical methodology and to

DOE launched a major initiative to provide best-practice information about the external physical impacts of energy use and how these impacts should affect planning and investment.

northwest Washington (see Sect. 2 highlight, "Impacts of Hydropower in the Nooksack and Skagit River Basins"). No impacts to historic resources could be identified. Based on discussions with Native American tribes in the area, a determination was made that several dam projects could possibly affect important tribal cultural sites because of intrusion into remote

develop the best range of estimates of costs from secondary sources" for eight fuel cycles and four conservation options. Responsibilities for the fuel cycles were distributed as follows: both research teams were to undertake the coal-fuel cycle and conservation options; the United States was to take the lead on the biomass, oil, natural gas, and small hydroelectric fuel cycles; and the CEC was to take the lead on the uranium, photovoltaic, and wind fuel cycles.

ORNL and Resources for the Future are the principal research institutions for the United States, while the CEC team draws on expertise from the United Kingdom, France, the Netherlands, and Germany. However, interest in the project extends well beyond the members of the research teams and their immediate sponsors. Because many state and local regulatory bodies are struggling with their own positions on external-costs issues, tremendous emphasis has been placed on sharing information as the project proceeds. The U.S. and CEC teams have produced a series of widely distributed position papers that discuss important definitions, methodological choices, and bounding assumptions for the analyses. In addition, three series of technical meetings have been conducted to enhance information flow within and between participating countries.

The principal organizational tool for the project is the damage-function approach (DFA).

Application of the DFA begins with a conceptual understanding of the impact pathways by which fuel cycle emissions "cause" physical consequences. Impact pathways identify residual emissions from fuel cycle activities; they address (1) the transport, deposition, or chemical transformations of these emissions, and (2) the physical response of ecological, human, and social resources (which are spatially and temporally distributed) to changed concentrations of pollutants. The final step of the DFA is to consider how these physical responses are valued by the affected individuals to produce damage and benefit estimates.

The DFA highlights how technological and descriptive factors (such as environmental baseline and resource locations) influence the damage calculations, and forces its users to reveal what is known about physical and behavioral processes. Thus, the resulting "knowledge base" of the project also identifies fundamental gaps in our understanding of technologies, physical processes, and economic behavior, to prevent quantifying damages.

To date, the project teams have applied the DFA to aspects of the coal, oil, biomass, and uranium fuel cycles. A guidance document published this year details how to apply the approach, with special emphasis on the coal fuel cycle. All fuel cycles and conservation options should be completed by August 1992.

Energy

and Economic Analysis

ORNL-Photo 1498-92

Charles Kerley, Section Head

3. ENERGY AND ECONOMIC ANALYSIS SECTION OVERVIEW

3.1 INTRODUCTION

The Energy and Economic Analysis Section (EEAS) specializes in economics research. The section is staffed with economists trained in such areas as energy economics, natural resource and environmental economics, public policy studies, applied microeconomic theory, econometrics and mathematical modeling, and economic geography and regional science. Most of the professional staff members hold doctoral degrees. EEAS maintains an independent research agenda for the U.S. Department of Energy (DOE) and other sponsoring agencies and supports research projects in other Energy Division sections and other Oak Ridge National Laboratory (ORNL) divisions. Collaborative research with university programs (Fig. 3.1) is accomplished through joint research staff appointments to EEAS and a university.

During fiscal year (FY) 1991, two collaborating scientists—Milton Russell, former Assistant Administrator for Policy and Planning

at the U.S. Environmental Protection Agency (EPA) and University of Tennessee- (UT-) ORNL appointee, and James Kahn, UT-ORNL Associate Professor and research staff member—have collaborated with EEAS staff on various research initiatives. In FY 1991, Russell completed two important research projects—a study of energy and environmental policy in China and another on hazardous waste remediation in the United States. The findings of these studies are detailed in Sect. 3.3.2. In addition to his research agenda, Russell serves as Chairman of the National Acid Precipitation Assessment Program Oversight Committee. Kahn has begun a research program related to cost-benefit assessment in environmental management and regulatory policy. These collaborative efforts are influencing directions of U.S. environmental legislation and are expected to contribute unique insights into the best strategies for assisting with energy planning and technology policy in developing countries.

ORNL-Photo 1435-92

Fig. 3.1. Footbridge on the campus of the University of Tennessee, Knoxville, one of many universities with which the Energy and Economic Analysis Section conducts collaborative research.

3.2 INFORMATION TRANSFER

An important objective of the EEAS research program is the dissemination of research information to DOE, the scientific community, other government agencies, and the public. Staff members publish the results of EEAS research in refereed journals and ORNL reports and make frequent presentations to scientific conferences and workshops, national advisory boards, and Congress. In the past, EEAS has been asked to provide white paper summaries for newly appointed agency administrators to aid in formulating mission plans and programs.

This year David Bjornstad was chosen by DOE to undertake a special assignment in Washington, D.C., for the Secretary of Energy Advisory Board. He is leading a task force to study and report to Admiral Watkins on three broad areas related to energy and economic modeling: defining and setting priorities for DOE's near-term modeling needs and problems; providing a vision for DOE's participation in future economic modeling in the federal government; and guiding the National Research Council's value-enhancement review of the National Energy Modeling System.

3.3 RESEARCH PROGRAM

The EEAS research program consists of projects in four broad categories: productivity and energy supply, energy and environment, modeling and technology, and emergency management and risk assessment. The research activities are conducted by two groups in the

An important objective with the EEAS research program is the dissemination of research information to DOE, the scientific community, and the public.

section—the Energy and Environmental Economics Group, which is being led by Randall Curlee during David Bjornstad's special assignment, and the Resource Modeling and Tech-

nology Economics Group led by Russell Lee. The ensuing sample of these two groups' research efforts demonstrates how other government agencies benefit from DOE research and how

interdisciplinary teams from ORNL divisions, universities, and private research organizations are advancing scientific understanding of world energy and environmental issues.

3.3.1 Productivity and Energy Supply

The projects concerning productivity and energy supply assist DOE in addressing policy issues related to strategic fuel reserves, reserve drawdown, energy efficiency, fossil energy technology, and energy security.

The Strategic Petroleum Reserve (SPR) research project initially investigated the costs and benefits of expanding the U.S. strategic stockpile of crude oil from 700 million to 1 billion barrels and the timing of drawdowns during a supply disruption. In more recent work, the staff began analysis of a separate planning question: whether part of the U.S. petroleum stockpile should be stored regionally, as petroleum products, rather than centrally stored as crude oil. Such a Refined Petroleum Product Reserve would be a part of the SPR system but might be, for example, distillate heating oil stored in New England or gasoline stored in California. Previous DOE studies have established that life-cycle costs for refined product storage are significantly higher than those for centralized crude storage. Specifically, product storage facilities (possibly steel tanks rather than abandoned salt mines) would have a higher capital cost, and operating costs might be higher because of the shorter shelf life of refined products.

In investigating the feasibility of a regional gasoline reserve, staff members found that it would be cost-effective only if it could be completed and filled within about 4 years and the payoff (i.e., actual use of the reserve to offset a disruption) occurred within 1–2 years of being filled. This finding is illustrated in Fig. 3.2.¹ The upward-sloping curves indicate the cumulative costs of having a 10 million barrel reserve of gasoline under different options: expanding the underground facilities at the existing Big Hill site, purchasing above-ground storage tanks, and renting tanks. The cumulative costs increase over the period of constructing and filling (or renting) the reserve. The benefits are somewhat greater for larger disruptions. The benefits of using the reserve decline over time since they are more discounted the further in the future the reserve is used.

With the recent war in Kuwait and Iraq, considerable attention was given to the politically sensitive issue of when the SPR would actually be used during a disruption in the oil market. An unpublished white paper prepared by staff members Paul Leiby and Russell Lee discusses different strategies and criteria that could be used for deciding the use of the SPR. In the paper, the authors discuss each of the following:²

- optimizing the economic benefits of using the SPR, making explicit trade-offs between using the SPR immediately or later, and comparing its current value to its hedging value;
- offsetting price increases so that rapid increases would trigger use of the SPR;
- offsetting physical shortages, compared to production prior to the disruption;
- using contracts or other financial instruments (such as call options) that enable the market to participate in the decision on when the SPR is to be used;
- using rules of thumb, such as a pre-commitment to certain policies or rules;
- working with the International Energy Agency to negotiate a coordinated drawdown of the SPR; and
- negotiating with foreign suppliers to obtain increased production from those suppliers in combination with use of the SPR.

As plans are being made to expand the size of the SPR to 1 billion barrels, the appropriate rate at which oil should be withdrawn and distributed is a continuing issue of debate. Increasing the capability has the benefit of increasing the options available for the SPR to address severe disruptions. This increased capability comes at a cost, however: the cost of installing more pumps, building more pipelines, and enlarging terminal facilities. Study results indicate that expansion of

Fig. 3.2. Cumulative cost versus benefit of a 10 million barrel reserve of gasoline.

the drawdown and distribution capability to 7 million barrels per day (the current plan is for expansion from 4.5 to 6 million barrels per day) is justified in most of the analyses, if the SPR is to be used to its full potential to offset disruptions in supply. This policy of using the SPR means that a disruption with a net shortage in supply—compared to production before the disruption—would be offset completely, to the extent possible, by the SPR. However, this use of the SPR is not optimal for maximizing the expected economic benefits of using the reserve. An optimal strategy would hedge the use of the reserve, meaning that a much smaller drawdown and distribution capability would be needed—perhaps as little as 4.5 million barrels per day.³

3.3.2 Energy and Environment

Energy and environment projects include economic analysis of the following: conventional energy use, the substitution of biomass fuels in developing countries, the protection and reestablishment of natural environmental systems, the interaction between agriculture and the environment, and air quality.

EEAS staff, including Robert Perlack, Larry Hill, Milton Russell, and Zhongmin Shen (a UT student working with ORNL staff), played important roles on the international stage by

ORNL-Photo 5436-90

Researchers are studying energy and environmental policy in China.

publishing journal articles on energy planning and environmental policy in developing countries. Much of the international research effort focuses on achieving energy efficiency, protecting the environment, and transferring new concepts such as demand-side management (DSM) to developing countries.

A DSM process requires that electric utilities promote measures on the customer's side of the meter to directly or indirectly influence electricity consumption to meet desired load objectives instead of constructing new power plants. In developed countries, innovative electricity pricing—such as time-of-use (TOU) hour by hour, day by day, or season by season—has been found effective in smoothing out irregularities and slowing the rate of increase in absolute level of electricity demand. Subsequently, new generating capacities require less capital investment to maintain system reliability.

The question arising from the DSM studies in western economies is whether a rapid transfer of that experience to developing countries is practical and appropriate for achieving more

efficient energy use, less environmental degradation, and better use of scarce capital. In many developing countries, a fundamental structural flaw underpinning the economy is the failure to price energy at its true cost of production and to effectively apply capital resources to promote economic development. In a series of papers published this year in *Natural Resources Forum*, *International Journal of Global Energy Issues*, *Energy Policy*, *Utilities Policy*, and the *Electricity Journal*, Larry Hill examines the role of innovative pricing and energy-efficiency improvements (two closely related concepts) in meeting growth objectives of developing countries.⁴⁻⁸ In these papers, he discusses the limitations of the western DSM experience for energy management in developing countries and analyzes in detail the

exceptional case of Korea, a country whose management of its fledgling energy sector overcame the inherent difficulties of energy-pricing reform and capital formation to propel the country into rapid industrial development.

The key lesson from experiments in TOU pricing is that energy-consuming behavior can be influenced by tariffs. Hill maintains, however, that for many developing countries, adopting the real-time pricing (RTP) technology of DSM would be an expensive and long-term undertaking, not a first-, second-, or even third-order priority. The embryonic stage of many developing countries' residential loads, relying on relatively unsophisticated electrical appliances with low levels of per-capita electricity consumption, is a major limiting factor. Metering problems and costs associated with TOU policy would worsen development problems for all but middle-income developing countries in which rapid load growth is following the penetration of residential air conditioners and other appliances. Only in these higher-income developing countries would TOU pricing appear to be an economically

attractive option for moving away from government-subsidized energy toward a market in which the full cost of energy supply is captured. The most urgent priority for many countries is not adopting new technology, but developing the political will and social mechanism for rationalizing electricity tariffs—raising them to cost-based levels.

Hill is more optimistic about the industrial sectors of developing countries. Industry offers the best opportunity for TOU rates, even though available evidence supports meager load shifting from peak to off-peak periods for U.S. industrial customers. The difference in potential is that in many developing economies, the industries in which discrete loads were found to be amenable to TOU-pricing response—cement and wood products industries, for example—are large electricity users and important for economic development. Studies in France and Britain for these industries indicate that cement producers reduce their electrical load by 50% during weekday peak periods and shift to weekends when off-peak tariffs apply (Fig. 3.3), retaining an

almost constant weekend load at the level of highest off-peak, weekday consumption. Therefore, certain key industries important in early stages of development should show large short- and long-term response potential to TOU rates, based on experiments in Western economies.

Given some industrial potential for TOU application, how could tariffs on energy use through DSM promote economic development? The model of development most familiar to such countries might be characterized as unconstrained resource exploitation and technology application without regard for environment or efficiency. To answer the question, Korea provides one success story of a country short on resources that was able to finance the development of its utility sector through a combination of pricing, private power plant construction, and improvement in operational efficiency.

Korea's development during the 1960s and 1970s closely approximates the condition of many developing countries today. The opportunity cost of investing in a capital-intensive energy sector

ORNL-DWG 92-6212

Source: ORNL graph adapted from Mitchell, Manning and Acton, 1978, Fig. 17, p. 92.

Fig. 3.3. Load curves for a French cement plant.

was high, with scarce funds competing for alternative uses in social and industrial sectors to improve prospects for economic growth. Yet the opportunity cost of *not* investing was also high because investment in energy is required for growth to proceed.

Korea directed public policy on power development toward obtaining as many resources for new electric-generating capacity as possible through pricing and complementary initiatives

Given some industrial potential for TOU application, how could tariffs on energy use through DSM promote economic development?

during its formative stages of development in the 1960s. For pricing alone, the percentage of capital expenditures financed from within the state power monopoly averaged close to 50% from 1967 to 1973. During this period, two companion initiatives were also implemented to complement the pricing strategy. In July 1961, the three existing electric utilities were merged into one, resulting in significant economic benefits. In addition, a number of technical efficiency improvements were introduced, including a power-loss prevention program that reduced transmission-line loss from nearly 30% in 1961 to 18% in 1966. Partially because of these two initiatives, real (in 1988 *won*) average (per kilowatt-hour sales) operating expenses declined from 127.2 *won* in 1961 to 37.9 *won* in 1973. Finally, the government allowed private companies to construct generating capacity in the mid-1960s, when rising standards of living and rapid industrialization

strained existing capacity on the central grid.

The estimated amount of electric-generating capacity saved by these initiatives during the 1960s and early 1970s is summarized in Table 3.1, assuming a capacity cost of \$760/kW (1988 dollars). About 27% of capacity-equivalent gains were due to pricing, 26% to operational efficiency, and 40% to construction of private power plants. The estimated equivalent amount of capacity and the corresponding percentage of net capacity additions are presented for magnitude and scale only and do not necessarily represent the actual sources of resources for the Korean power sector in either a financial or economic sense.

In addition to utility-capacity initiatives, a time-of-day tariff was introduced for large voltage, industrial electricity users in December 1977. Over the decade subsequent to its introduction, capacity savings reached an estimated 800 MW. More recently, the Government-Invested Enterprise Management Act was enacted to provide incentives for managers to improve the performance of their firms, with rewards accruing directly to the managers rather than the firms. This legislation reduced operating costs of the power monopoly an estimated 33% four years after its enactment.

(text continues on page 3-10)

**Table 3.1. Korea Electric Power Corporation
estimated capacity equivalents from pricing
and related initiatives implemented
from 1961 to 1973**

Initiative	Capacity equivalents ^a (MW)	Net capacity additions ^b (%)
Pricing	1055	27.0
Improvements in operational efficiency	1004	25.7
Construction of private power plants	1565	40.1

Source: Hill, L. J., "Pricing Initiatives and Development of the Korean Power Sector: Policy Lessons for Developing Countries," accepted for publication in *Energy Policy*.

^aBased on \$760/kW (1988 dollars), the cost of constructing a 500-MW coal-fired generating plant in Korea in 1988.

^bThe ratio of the capacity savings of the three initiatives to 3095 MW (the net capacity additions in Korea from 1962 through 1973) excluding capacity constructed for private use.

QUANTITATIVE ASSESSMENT FOR COMPLETING THE HAZARDOUS WASTE REMEDIATION TASK

This year, a consortium of organizations—including AT&T, E.I. DuPont de Nemours, General Electric Capital Corporation, General Electric Corporation, Charles Stewart Mott Foundation, the University of Tennessee Waste Management Research and Education Institute, Oak Ridge National Laboratory (ORNL) Energy Division, ORNL Environmental Sciences Division, and the U.S. Department of Energy—supported a major collaborative investigation. That research, directed by Milton Russell, undertook a quantitative assessment of requirements for completing the nation's Hazardous Waste Remediation Task.⁹

Table 3.2 presents "best guess" estimates for accomplishing hazardous waste cleanup in the United States. The current policy case is modeled on observed behavior in each remediation program. The less stringent case envisions greater use of containment technologies; the more stringent case, greater use of destruction technologies. All three cases would provide roughly equal protection to human health and the environment.

The total cost under current policy (on an "as built" basis using no discounting) is approximately \$750 billion. Plausible bounds on this estimate range from \$500 billion to \$1 trillion. The less stringent case reduces the best guess to about \$500 billion and moves the lower and upper bounds to \$400 billion and \$700 billion, respectively. Alternately, the more stringent case raises the best guess to about \$1.2 trillion, with the plausible lower bound under \$1 trillion and the plausible upper bound about \$1.7 trillion. These totals come from cost estimates of the six programs presented in Table 3.2.

By comparison, the current policy estimate would absorb as much of the country's productive potential as approximately 1 year of nondefense federal expenditures or a decade of total public and private expenditures on *all other* environmental objectives at FY 1990 levels. Significantly, the

difference in expenditures between a less and a more stringent policy roughly equals the amount that the nation will soon spend on cleanup. Programs requiring such significant choices deserve the closest scrutiny of operations, goals, and benefits.

These estimates involve three major uncertainties. For example, technological improvement could come faster (or slower) than inflation, thereby changing the totals in Table 3.2. The second uncertainty involves the number of Resource Conservation and Recovery Act (RCRA) corrective action sites which could be underestimated because the point estimate used from the 1986 survey data bases was systematically inaccurate due to under-reporting. Further, remediation cost per unit of contamination under RCRA may not compare with Superfund sites because firms can exercise tight management supervision of activities. Finally, the current policy used for these estimates does *not* consider other policy changes. For example, implications of the 1990 Clean Air Act (CAA) Amendments, which may augment cleanup costs, are not incorporated in these estimates. Restriction of waste movement across state boundaries might increase other disposal costs, as would changes defining waste disposal in landfills. ♦

Table 3.2. Best guess resource requirements under current, less stringent, and more stringent cleanup policy^a

Remediation authority	Current	Less stringent	More stringent
National priority list (Superfund)	151	90	352
Resource Conservation and Recovery Act corrective action	234	199	258
Underground storage tanks	67	67	67
U.S. Department of Defense	30	18	70
U.S. Department of Energy	240	92	360
State and private programs	30	18	70
Total	752	484	1177

^aValues represent billions of 1990 dollars.

CHINA'S EVOLVING ENERGY AND ENVIRONMENTAL POLICY

EEAS international efforts included work by Robert Perlack, Milton Russell, and Zhongmin Shen. Their paper in the *Annual Review of Energy and Environment* discusses evolving energy and environmental policy in China.¹⁰ The largest developing country in the world, China has an economic goal of doubling its present gross national product by the year 2000. But as the world's third-largest source of greenhouse-gas emissions, China must address future environmental degradation caused by energy production.

China presents a development planning problem because of the magnitude of energy requirements and the implied global environmental consequences of their most commonly used energy forms. Energy consumption of China's modern sector has grown rapidly since 1949, averaging nearly 10% annually. As shown in Fig. 3.4, this growth has been driven largely by coal, which frees their oil for export. Consequently, coal provides

about 72% of the energy in the industrial sector (including power), 61% in agriculture, 94% in the residential sector (including cooking and space heating), 45% in the combined commerce and public service sector, and about 49% in the mostly rail transport sector. Unfortunately, most coal is used in inefficient, small- and medium-scale industrial boilers, building boilers, and coal stoves. Beijing alone uses more than 6000 heating boilers and a million household coal-burning stoves.

Because of inefficient burning, China's total annual emissions of sulfur dioxide (SO₂) and suspended particulates are approximately 15.6 million tons and 14 million tons, respectively. The World Health Organization has established guidelines of 100–150 µg/m³ for SO₂ and 150–230 µg/m³ for total suspended particulates (TSP). For comparison, recent estimates of average daily SO₂ concentrations over all cities in China come to 105 µg/m³ (119 µg/m³ in southern

Fig. 3.4. Primary energy output and carbon emissions.

cities). Average daily concentrations of TSP come to $526 \mu\text{g}/\text{m}^3$ in northern cities, about $318 \mu\text{g}/\text{m}^3$ in southern cities, and about $432 \mu\text{g}/\text{m}^3$ over all of China. Huge amounts of carbon dioxide (CO_2) are released as well. In 1986, China accounted for about 10% of global carbon emissions from all fossil fuels and 20% from coal, five to six times as much fossil carbon per unit of economic activity as industrialized countries.

Energy-use efficiency was ignored in China until growing industrialization and rising incomes in the 1980s placed greater demands on energy supply than could be met. This supply problem was worsened because energy prices did not guide production and use. In 1985, a two-tier price system for energy resources went into effect. Based on state-controlled prices and negotiated market prices, the policy allowed distribution of coal at the previous low price as an allocation, but firms and individuals could purchase more on the free market. This two-tier system creates market distortions: better-quality coal (higher heating value, lower sulfur) is sometimes sold in the allocated market at a lower price than poorer-quality coal in the free market.

Insufficient coal supplies continue to compound problems in the power sector, which has inadequate capacity to meet full demand in most locations, and one-third of the industry is unable to operate at full capacity. China has announced plans to add 70 GW of new coal-fired capacity during the 1990s. These additions will increase installed thermal capacity to 160 GW, with annual generation of 900 TWh. Use of hydropower will be expanded from 32 GW to 72 GW (30% of total national capacity). China envisions 6–7 GW of installed nuclear power capacity by the year 2000, though thermal power would still account for at least 70% of total electricity generated. Investments are planned for high-voltage transmission lines to move electricity from the west to the east and for rail networks to help move coal from the north to the south.

The Chinese economy also suffers from a shortage of petroleum products. The growth of automobile transport and farm mechanization over the

past decade has increased the demand for already scarce gasoline. Refineries have resorted to heavy use of tetraethyl lead as an additive—which, as demonstrated by research on the effects of lead on children, has serious implications for public health.

China's stated energy policy for the next decade places equal emphasis on the development and conservation of energy, supported by environmental protection measures. How can China protect the environment while continuing to increase its coal consumption to meet economic goals? EEAS research findings suggest a combination of strategies: enacting energy price reform; coordinating investment strategies for implementing environmental policies; increasing financial and human resources for environmental control; strengthening

environmental standards and enforcement; and investing in technical improvement of conversion technologies, end-use equipment, and alternative fuels. Much of China's expected demand for

***How can China protect the
environment while continuing to
increase its coal consumption to meet
economic goals?***

energy—1400–1700 million tce by the turn of the century—can come from efficiency improvements and price reform in the energy sector. Environmental protection in China will be determined by the implementation and effectiveness of three instruments: (1) emission standards mandating the installation of certain equipment, (2) economic incentives such as tort liabilities and effluent and emission fees, and (3) changes in public opinion and private behavior through persuasion.

Whether China can increase the efficiency of industrial coal use while encouraging energy substitution in the residential sector remains to be seen. So far, improvements have been largely administrative and easy to implement. But China has little of the capital that technical improvements require. What effects price reform will have in motivating efficiency improvements and generating funds for investment in energy and environmental control is uncertain. The Korean experience suggests that these actions can be successful. However, increased efficiency of energy use in China (or any other country) must result from examination of the conditions in *that* country, not from predetermined measures imported directly from abroad. ♦

These initiatives were significant resources for the Korean power sector, allowing for expansion to match the country's industrialization program, and they were implemented without serious political or economic instability. Even though its political system and workforce differ from many developing countries, Korea provides useful lessons about possibilities for—and payoffs from—resource mobilization in the power sector through pricing and related initiatives.

3.3.3 Modeling and Technology

Projects and activities in economic modeling and technology research include model development and expert review, manpower studies, new technology, and materials development and transfer. Two important activities this year have been the development of an integrated-model prototype for projecting biofuels consumption and continuation of development and analytical support of the Regional Recruiting Potential model developed by ORNL for the National Guard Bureau.

Our dependence on fossil fuels has created significant interest in renewable sources of energy from both environmental and energy security concerns. Use of renewable energy not only reduces the net emission of carbon dioxide (CO₂), which causes global climate changes, but diversifies our energy sources and reduces dependence on foreign oil as well.

This year, Russell Lee, Steve Cohn, and Robert Perlack completed initial development of an integrated modeling framework that projects consumption of liquid biomass fuels.¹¹ The researchers drew on work within a number of ongoing or recently completed research programs, including programs by DOE's Conservation and Renewable Energy Office, DOE's Policy Office, the Department of Transportation's Federal Highway Administration, and the

Interagency Commission on Alternate Motor Fuels.

Figure 3.5 illustrates the basic supply and demand components of this prototype model. Supply combines assumptions about related economics and perceived risks (crop yields, soil and water effects, agriculture programs, and macroeconomic conditions) with output from farmers' decisions to grow energy crops. In the model, conversion technology delivers the potential of biofuels' supply and attributes, while supply (quantity, price, and attributes of other fuels) ultimately affects consumer buying of vehicles and fuel. Forecasting the demand of liquid biofuels includes consideration of vehicle stock, scrappage rates, gross national product (GNP), and population demographics to arrive at updated vehicle stock and travel demands. These, in turn, affect consumer purchases of vehicles and fuel. Combined demand and supply determine fuel consumption and quads of biomass energy.

Initial tests of this prototype were based on the best available information to compile supply curves for the production of ethanol from both corn and energy crops. A model algorithm was used to compute a market-clearing condition in which the supply of ethanol equals demand. Model projections were similar to the projections made in other major studies. Projections of

(text continues on page 3-12)

ORNL-DWG 92-6214

Fig. 3.5. Overview of integrated supply and demand framework for forecasting liquid biomass fuels.

REGIONAL RECRUITING POTENTIAL MODEL

In manpower modeling, work has continued on development and analysis of the Regional Recruiting Potential Model (RRPM) by EEAS's David Vogt, Sharon Bell (of Science Applications International Corporation), and Arlene Katzman (of PAI Corporation).¹² The model incorporates regional economic analysis techniques in a sophisticated software package that enables users with scant computer and economics backgrounds to generate regional analysis reports. The model also allows advanced users to conduct more complex analyses, such as force-structure planning or facility-location planning. For example, Fig. 3.6

displays the potential growth states for the Army National Guard in the year 2000. (The model also has the capability to rank counties for potential draw rates.) The figure legend distinguishes between the numbers of potential guard members above current authorizations. Where authorizations are smaller than potential, the number can be negative. The RRPM analysis helps the National Guard identify locations where units would not be supportable and prevents erroneously identifying good locations as poor. Therefore, the model prevents wasted resources as well as lost opportunities. ♦

ORNL-DWG 92-2210

Fig. 3.6. Army National Guard potential growth areas, 2000.

biofuel usage for the year 2000 have ranged from 0.20 to 0.30 quads for corn-produced ethanol and from 0.01 to 0.04 quads for ethanol produced from energy crops. Projections for the year 2010 ranged from 0.30 to 0.40 quads for corn-produced ethanol and from 0.05 to 2.0 quads for energy-crop ethanol. These initial findings indicate that the prototype is reasonable, but further enhancements are needed. These refinements include incorporating more consumer-behavior information regarding fuel choice with dual-fuel vehicles. Also, a number of demand- and supply-side issues still need to be modeled, including penetration of alternative-fueled vehicles, use of biomass for other purposes, and policy concerning the Clean Air Act (CAA) and CO₂ emissions. Supply-side issues relate to the production of energy crops in the overall context of agricultural costs, as well as the use of forest residues. Key elements that need to be developed for the modeling framework over several years include:

- supply curves for various biomass categories,
- market penetration rates of biomass conversion technologies,
- biomass partitions between various alternative end uses,
- penetration rates of alternative-fueled vehicles and fueling infrastructure,
- policy effects on biomass production (such as Federal Farm Commodity

programs) and on usage of biomass fuels (such as the CAA), and

- estimates of fuels from other sources (such as methanol).

Finally, the model must fit explicitly into the integrated framework of the National Energy Modeling System, which is currently under development at the Energy Information Administration (EIA).

3.3.4 Emergency Management and Risk Assessment

Projects in the emergency management and risk assessment category evaluated questions associated with safety and risk, mobilization capabilities, national disasters, and emergencies. This year, the National Infrastructure Information System model developed by ORNL for the U.S. Federal Emergency Management Agency (FEMA) was applied in an emergency-assessment exercise that proposed a hypothetical, externally produced (e.g., meteorite impact) nuclear power plant disaster. This three-step assessment included (1) prediction of industrial-facility damage within the plumes; (2) assessment of regional economic impacts; and (3) focus on potentially unsatisfied military support procurements—size, location, and industry contacts.

The nuclear plant chosen for this exercise was Enrico Fermi 2, located in Cook County,

Fig. 3.7. Economic capacity loss profile from the hypothetical disaster incident at Fermi 2.

Illinois. Potential fallout zones and economic production capacity that would be lost due to such a disaster are illustrated in Fig. 3.7. As shown in Table 3.3, a large number of counties would receive over \$1 billion in losses. At least five counties include large manufacturing facilities that are important military support industries. Analysis suggests that a Fermi 2 accident would produce damage to ball and roller bearings production, with serious impacts on military support industries. About 20% of U.S. bearing production would be at risk, with 12% loss predicted from the plume assumption illustrated in Fig. 3.7. Bearings are a key input item in 21 of 33 military support industries; the largest orders come from companies in Illinois, Texas, California, Wisconsin, Michigan, Ohio, and Kentucky—including McDonnell Douglas, Rockwell, Lockheed, and Northrop, from Los Angeles County alone. The disaster would also put at risk 27% of U.S. tire and inner tube production and 9% of coal mining. Total estimated production lost comes to \$512 billion (1982 rates).

In addition to financial impacts under current assumptions, the assessment points out other critical aspects of real accidents, including:

- industry damage due to wind direction;
- radiation-assessment revisions to damage estimates;
- alternative sources for military support goods; and
- infrastructure damage to utilities, railways, highways, rivers, lakes, and reservoirs.

3.4 RESEARCH UTILIZATION

Like the projects described here, most EEAS research contributes directly to the planning, policy, and analysis activities of public agencies. The research focuses predominantly on sponsors' needs and normal avenues of use. For example, the petroleum-modeling studies are used by DOE to assist in SPR planning activities. Information and analysis developed for EIA support its data and information activities, including the Secretary of Energy's report to Congress on the uranium industry, the National

Table 3.3. FERMI 2 plume analysis counties with losses of at least \$1 billion (1982)

County	Dollar loss ^a	Military support facilities
Summit, Ohio	7.8	X
Henrico, Virginia	7.0	X
Stark, Ohio	6.1	X
Lorain, Ohio	3.7	
Washington, Pennsylvania	1.9	
Erie, Ohio	1.7	
Wayne, Ohio	1.6	
Medina, Ohio	1.3	
Ohio, West Virginia	1.2	
Prince George, Virginia	1.1	X
Tuscarawas, Ohio	1.1	
Jefferson, Ohio	1.1	X
Belmont, Ohio	1.1	
Chesterfield, Virginia	1.0	

^aIn billions.

Energy Strategy, and the Annual Energy Outlook. Studies on energy conservation and impacts are used by DOE, the U.S. Department of the Interior, and other agencies to understand energy retrofit decisions. Other agencies that use EEAS research results in program planning and analysis include FEMA, the Bonneville Power Administration, EPA, the U.S. Department of the Air Force, the U.S. Department of the Navy, and the U.S. Agency for International Development.

Though the primary objective of EEAS research is to solve individual sponsors' problems, it is by no means limited to those purposes. The section's mix of economics research projects for DOE and work-for-others sponsors, conducted in a laboratory environment, provides a multidisciplinary forum in which many technical and social aspects of individual problems emerge. These findings ultimately contribute to a better understanding of complicated social and economic systems and become incorporated into solutions for general energy-related issues of national importance. These include energy, environmental, and emergency problems such as atmospheric increases of CO₂ and depletion of stratospheric

Another strength of the Energy Division is the administrative support provided to the technical staff. (Left to right: Russ Lee, Pam Witcher, Paul Leiby.)

ozone, infrastructure modernization, energy efficiency, hazardous waste management, energy for development of Third World nations, and public and private resources for emergency response.

3.5 REFERENCES

1. Curlee, T. R., S. Das, R. Lee, and P. N. Leiby, "Refined Petroleum Product Reserve (RPPR) Deterministic Cost Benefit Analysis, Briefing before the Office of Planning and Financial Management, Office of Petroleum Reserves, U.S. Department of Energy, Washington, D.C., February 15, 1991.
2. Leiby, P. N., and R. Lee, "A Discussion of Strategies and Approaches for Planning the Drawdown of the SPR," note prepared for the Office of Planning and Financial Management, Office of Petroleum Reserves, U.S. Department of Energy, Oak Ridge National Laboratory, Oak Ridge, Tennessee, March 21, 1991.
3. Trumble, D. A., and R. Lee, "Benefits of Alternative Drawdown and Distribution Capabilities for the Strategic Petroleum Reserve: Results Under Revised Base Case Scenarios," draft report prepared for the Office of Planning and Financial Management, Office of Petroleum Reserves, U.S. Department of Energy, Oak Ridge National Laboratory, Oak Ridge, Tennessee, October 31, 1991.
4. Hill, L. J., "Can Developing Countries Benefit from Innovative Pricing in the Power Sector," *Natural Resources Forum* 15(1), February 1991.
5. Hill, L. J., "Large Power Users and Capacity Shortages in Developing Countries: The Role of Innovative Pricing," *International Journal of Global Energy Issues* 3(2), 1991.
6. Hill, L. J., with E. Hirst, and M. Schweitzer, "A Look at the Resource Portfolio of 24 Electric Utilities," *Electricity Journal* 4(7), 1991.
7. Hill, L. J., "Residential Time-of-Use Pricing as a Load Management Strategy," accepted for publication in *Utilities Policy*.

8. Hill, L. J., "Pricing Initiatives and Development of the Korean Power Sector: Policy Lessons for Developing Countries," accepted for publication in *Energy Policy*.
9. Russell, M., E. W. Colglazier, and M. R. English, *Hazard Waste Remediation: The Task Ahead*, Waste Management Research and Education Institute, The University of Tennessee, December 1991.
10. Perlack, R. D., M. Russell, and Z. Shen, "Energy and Environmental Policy in China," *Annual Review of Energy and Environment*, 1991, 16:205-33.
11. Lee, R., S. M. Cohn, and R. D. Perlack, *Prototypes of an Integrated Model for Projecting Biofuels Consumption*, draft report prepared for the Nuclear and Alternate Fuels Division, Energy Information Administration Oak Ridge National Laboratory, November 1991.
12. Vogt, D. P., S. Bell, and A. Katzman, unpublished briefing presented to U.S. National Guard Bureau, July 17, 1991.

Center

for Transportation Analysis

ORNL-Photo 1509-92

Mike Bronzini, Director

4. CENTER FOR TRANSPORTATION ANALYSIS OVERVIEW

4.1 INTRODUCTION

The Center for Transportation Analysis (CTA), now in its second year, exemplifies the strengths of a national laboratory with a strong combination of diverse talents and expertise. The center was established to support both civilian and military transportation research needs and has received much recognition in 1991 for its successful programs in transportation analysis and planning. From its critical efforts for the Military Airlift Command during Operation Desert Storm to its thorough analysis of options for automotive fuel economy, the center continues to meet the needs of its sponsors.

In addition to their primary transportation research mission, the center's staff also carry out research devoted to understanding human impacts on the environment and research into theories and techniques of artificial intelligence. Much of the research crosses disciplinary boundaries and is carried out in collaboration with others at Oak Ridge National Laboratory (ORNL) and outside the laboratory as well.

Research in support of the civilian transportation community ranges from collection and analysis of current data about the motor vehicle fleet and its impact on the economy and the environment to long-term studies of effective national transportation networks. The research is an essential resource for policy makers at local, state, and national levels. Staff experts also serve the nation as members of important commissions and committees working for the U.S. Departments of Energy and Transportation (DOE and DOT).

Military transportation research and development within the center originates new techniques for planning and executing strategic deployment of personnel and materiel. Tools developed by the center's staff have played a

major role in recent accomplishments by military agencies responsible for deployment of U.S. forces. Based on a solid foundation of operations research theory, the new tools incorporate the practical knowledge of the center's staff, who have developed a base of expertise that spans several branches of the armed forces and various transportation media.

The scope and integrity of research carried out within the center—as well as the successes enjoyed by its developed products—demonstrate the validity of the center-of-excellence concept and indicate that the center has proven reliable for effective transportation research.

4.2 POLICY ANALYSIS AND CONSERVATION

Center staff members have traditionally provided insight into the implications of national and international energy policies, including consumption patterns, and center activities in 1991 continued that significant tradition. The hazards of dependence on imported fuels were vividly demonstrated this year by events in southwest Asia, lending importance and a sense of urgency to studies of transportation energy use, transportation system planning, and alternative energy sources for transportation. Our understanding of the effects of human activities on

the global environment is also benefiting from research carried out by staff scientists.

4.2.1 Impacts on the Environment

In a joint effort between ORNL's Energy and Environmental Sciences divisions, the Dynamic Ecological-Land Tenure Analysis (DELTA) gaming tool is being developed to

In addition to their primary transportation research mission, the center's staff also carry out research devoted to understanding human impacts on the environment and research into theories and techniques of artificial intelligence.

quantify the ecological consequences of particular land colonization and land tenure practices over time. The project is supported by a grant from the Laboratory Director's Research and Development Fund.

In 1991, the center prepared a study that demonstrates the cost-effectiveness of increased automotive fuel economy as a means of reducing hydrocarbons emissions into the atmosphere.

The process consists of three interlinked submodels that simulate settlement diffusion, land-use change, and the ecological impacts of the resulting land-clearing process. A Geographic Information System (GIS), using Arc/Info software, is used both to create the necessary data base for simulation runs and to compare the model results with satellite images and other sources of information on past land-clearing patterns. DELTA uses stochastic microsimulation as a process for replicating land-use transportation system dynamics. Pattern formation and change are simulated at the microspatial, land lot, and tenant-specific level. For example, DELTA's first application is an analysis of the effects of spatial patterning within the rapid deforestation of the Brazilian Amazon.

Since motor vehicles are a major source of air pollution, strategies to reduce vehicle emissions can have significant effects on the environment. The center prepared a study in 1991 that demonstrates the cost-effectiveness of increased automotive fuel economy as a means to reduce emissions of hydrocarbons into the atmosphere. The study indicates that total long-run benefits of increasing new car fuel economy from 28 to 40 mpg are of roughly the same magnitude as instituting Stage II or "on-board" refueling controls, or reducing tailpipe emissions to levels called for in the new Clean Air Act (CAA). Hydrocarbon reductions cannot justify major increases in costs to improve motor vehicle fuel economy; however, indications that the hydrocarbon emission reductions possible with higher fuel economy constitute a major incentive to ensure that attainable, cost-effective levels of motor vehicle fuel economy are realized.

The use of alternative fuels for motor vehicles could also have major impacts on the environment and infrastructure. In 1991, CTA staff members coordinated the production of the *Second Interim Report of the Interagency Commission on Alternative Motor Fuels*, which describes progress made by the commission and government agencies in implementing provisions of the Alternative Motor Fuels Act of 1988. Significant portions of the work described in the report were also carried out by center staff members.

The center is also participating in a large-scale project with the University of Tennessee to estimate the costs of cleaning up hazardous waste sites under the provisions of the Resource Conservation and Recovery Act (RCRA) (see Sect. 3 highlight, "Quantitative Assessment for Completing the Hazardous Waste Remediation Task"). Data from two data bases developed by Research Triangle Institute and a remedial-action, cost-estimation model developed by CH2M Hill for the U.S. Environmental Protection Agency provide the foundation for this work. Eight kinds of solid waste management units are included in the analysis, and cost estimates are developed under several scenarios. The base case assumes a best-as-practical cleanup to safe standards. Other scenarios would either tighten or weaken the level of cleanup. Analysis will continue, providing results that may be applicable to two potential changes to the RCRA remediation policy.

4.2.2 Transportation Planning and Policy

ORNL is assisting the Federal Highway Administration (FHWA) in the generation of alternative, candidate 2020 national highway networks, as part of DOT's effort to define the role for federal highway funding in the continued maintenance and improvement of our nation's highway system. Goals such as traveler mobility, equity, intercity trade, and connectivity for national security reasons are being translated into network highway design and selection criteria. Candidate highway networks are being evaluated and mapped using Arc/Info software. This GIS-based system, which continues to grow, contains numerous national transportation data bases operating on ORNL's National Highway

(text continues on page 4-4)

INTELLIGENT VEHICLE HIGHWAY SYSTEMS

The nation's highways, streets, and transit systems provide an essential source of mobility for U.S. citizens. While our system is still the best in the world, congestion problems from the growth of vehicle travel now threaten this mobility. The Federal Highway Administration (FHWA) estimates that delays from congestion alone result in productivity losses of up to \$100 billion annually. In addition, tens of thousands of injuries and fatalities occur annually due to traffic accidents. Other negative effects of ever-growing vehicle travel include increased pollution and energy-related concerns.

Advances in telecommunications, computers, and related technologies are now unfolding new possibilities for improving the quality and nature of travel. Intelligent Vehicle Highway Systems (IVHSs) are defined as the application of advanced technologies to improve the operational performance of the highway system. These technologies, as indicated in Fig. 4.1, involve a spectrum of devices and capabilities ranging from collision avoidance systems in vehicles to advanced traffic management centers and automated highways. IVHSs have been designated as a national priority in the recently passed Surface Transportation Assistance Act of 1992.

A strategic plan for IVHS is currently under development for submission to Congress by the U.S. Department of Transportation (DOT). Oak Ridge National Laboratory (ORNL) staff members have provided input to this plan through their affiliation with IVHS America, a federal advisory organization. This strategic plan outlines the role of national laboratories in the IVHS research, development, and deployment agenda. The national laboratories are identified as having a significant technical asset that can be utilized effectively in a national IVHS program.

The Center for Transportation Analysis (CTA) research staff have been

quite active in many areas of IVHS research and development. Since the early 1980s, staff members have assisted the FHWA with development of integrated simulation models. Support from the ORNL Director's Research and Development Fund has been used to develop dynamic traffic assignment models essential for realization of real-time, traffic-adaptive control envisioned in IVHS. Funding from the U.S. Army and U.S. Federal Emergency Management Agency is being used to develop decision-support systems with user-friendly graphical interfaces.

The significance and importance of ORNL's contribution to this effort is evident from a Senate report on IVHS that states, "The Department of Energy national laboratories have substantial

ORNL-DWG-92-6665

Fig. 4.1. Diagram of the various components of an Intelligent Vehicle Highway System.

scientific manpower and facilities that should be used in our national IVHS program. For example, the committee strongly supports FHWA's ongoing use of the Oak Ridge National Laboratory in its IVHS traffic systems modeling work."

CTA's Planning and Policy Group was recently tasked to provide IVHS research and analysis support to DOT. The CTA IVHS team will provide research and analysis support to the FHWA in two primary IVHS technology clusters dealing with commuter mobility: Advanced Traffic Management Systems (ATMSs) and Advanced Traveler Information Systems (ATISs). ATMS involves the management of traffic on highway networks composed of freeways and surface streets in real-time and full-adaptive fashion. ATIS provides in-vehicle information through a combination of sensors, on-board computers, and communications links with centralized traffic operations centers.

The CTA staff will assist FHWA with the development of state-of-the-art traffic modeling and analysis systems, decision-support systems, human-factors studies for IVHS, field testing, and evaluation of IVHS demonstration projects. As required by the FHWA, the CTA staff will conduct basic research in the area of traffic flow theory and operations.

Since the receipt of initial funding for IVHS activities, CTA staff have been assisting FHWA with plans for IVHS research, development, and deployment in the near term as well as long term. CTA's role in FHWA's IVHS program is expected to grow in coming years. ♦

Planning Network, which is a 49,000-link "multiattribute" highway network data base. Research is in progress to use these data in computationally efficient algorithms for network design and evaluation. A key use for the data base anticipates the sheer size of the multiyear network design problem being posed, requiring innovative operations research methods that ultimately serve policy analysis. An early success of the project has been the discovery of one of the largest optimal network design problems to be reported in the open literature.

An innovative effort was undertaken in 1991 to model highway use, including the limiting case in which highway supply is insufficient. The object of this project was to develop a reproducible procedure for forecasting the distribution of functional system mileage, particularly in

newly urbanized and suburbanized areas. An innovative time-series and cross-sectional travel-demand modeling system was developed to project future vehicle miles traveled (VMT) and highway lane-mileage needs by region, highway type, intra-urban location and city size. A statistical relationship was generated that, for the first time, measures the effects of restricted highway supply (in the nation's largest, most congested cities) on the demand for travel. The results of the analysis were used by the FHWA to predict a more realistic estimate of future highway needs for the Secretary of Transportation's biennial highway needs report to Congress.

In cooperation with the University of Tennessee's Transportation Center, ORNL is revising a number of the national freight forecasting and analysis tools used by the FHWA and placing them within a GIS- (TransCAD-) based freight policy analysis tool known as the revised Highway Traffic Forecasting System (HTFS). HTFS contains numerous linked algorithms for assessing the effects of national, state-specific, or highway-specific controls on truck size and gross operating weight and for analyzing, at the fully national scale, the effects on large truck and truck-rail competition of projected changes in fixed and variable operating costs. Outputs include revised VMT forecasts and payload ton-miles of travel forecasts by truck type, highway type, and state.

This year CTA staff have been steadily involved in the Federal Waste Management System Institutional Program, which is planning for the transportation of spent nuclear fuel from generating sites, such as reactors, to a storage facility. The ongoing program of the Office of Civilian Radioactive Waste Management facilitates involvement of the public in the policy-making process.

Over the past year and a half, the center's Transportation Planning and Policy Group has completed six of eight initial evacuation time estimate studies under the Chemical Stockpile Emergency Preparedness Program. Improved methods for collecting daytime population estimates and associated vehicle-utilization rates are being incorporated within network-based traffic assignment and simulation models. Theoretical and practical advances in the state of the art in dynamic traffic assignment are under development, and a number of publications on this topic are to appear in the open literature. Strongly

related to the group's research into real-time applications of Intelligent Vehicle Highway Systems (IVHSs) is the goal for development of planning methods and supporting algorithms for real-time evacuation planning.

Towards the end of the fiscal year, ORNL began research for FHWA's IVHS program (see Sect. 4 highlight, "Intelligent Vehicle Highway Systems"). Initial efforts have included technical inputs into the development of national research plans for IVHS research, design, and testing. The center expects to play a significant role in the definition and structuring of this new research initiative, including the development and testing of system prototypes; the organization of conferences and professional forums; and the promotion of partnerships among academia, industry, and government.

4.2.3 Motor Vehicle Fuel Economy

The center continued its leadership in the analysis of the costs and benefits of increasing automotive fuel economy. A detailed analysis completed in 1991 included quantitative consideration of such diverse aspects as the effects of conservation technologies on safety and the transfer of wealth from U.S. consumers to oil producers. The study indicated that generally positive net social benefits could be gained by increasing fuel economy levels up to 36 mpg for new cars and up to 27.5 mpg for new light trucks. Assumptions about oil discount rates and values of environmental and energy security effects strongly influenced the finding of net social benefits.

4.2.4 Alternatives for the Panama Canal

One of the major advances in ocean-going transportation in this century, the Panama Canal, often operates at or near full capacity, and a commission has been established to study possible plans for improvements or alternatives to the 77-year-old canal. A private organization, TAMS Consultants, Inc., has been awarded a contract to study oper-

ating characteristics and their relation to the capacity of the canal. TAMS will consider 19 alternative configurations, one of which would leave the canal in its current condition. Other configurations under consideration include one with proposed improvements to the canal and another for a proposed sea-level canal. Widening of the 8-mile-long Gaillard Cut, which is too narrow to allow two-way large ship traffic, is one example of future improvements that have already been approved by the Panama Canal Commission.

TAMS has asked CTA for assistance in developing computer models to simulate operation of the proposed alternative versions of the canal. Center staff members have begun their task with on-site collection of data about the daily operation of the canal. Figure 4.2 shows the Gatun Locks, where Pacific-bound vessels are raised to the level of Gatun Lake—a height of 85 ft—while

(text continues on page 4-8)

ORNL-Photo 1437-92

Fig. 4.2. The Panama Canal's Gatun Locks, where Pacific-bound vessels are raised to the level of Gatun Lake, 85 ft above sea level.

NAVY MOBILITY FUELS FORECASTING SYSTEM

For the Navy Energy and Natural Resources Office, researchers at the Center for Transportation Analysis (CTA) continued work with the Navy Mobility Fuels Forecasting System, which forecasts the availability, cost, and quality of military and civilian fuels for different peacetime and wartime scenarios (see Figs. 4.3 and 4.4). This year's work for the Navy included analyses of year 2000 scenarios, with free market economies assumed for Eastern Europe, the former U.S.S.R. and the People's Republic of China, and with greatly reduced crude oil production in the former Soviet Union. Based on forecasting system results and on-site reviews with refiners, CTA researchers recommended that the Navy continue to monitor projected trends in specific properties of Navy fuels that should be important in research and development of future Navy engines (Fig. 4.5).

The forecasting system was also used in Clean Air Act (CAA) assessments for the U.S. Department of Energy (DOE) Office of Energy Demand Policy. The CAA Amendments of 1990 will affect petroleum refining more than any other industry because, in addition to complying with all other provisions of the amendments, refiners will have to modify, design, permit, and construct new process units to produce mandated clean fuels such as reformulated gasolines. The forecasting system has provided estimates of the costs of gasoline reformulation, changes in gasoline composition, and requirements for additional refinery capacity. ♦

ORNL-Photo 1438-92

Fig. 4.3. Unrest in the Persian Gulf prompted the U.S. Navy to escort reflagged tankers—one example of the types of scenarios that affect fuel cost, availability, and quality.

Fig. 4.4. Potential problem areas for Navy fuels in year 2000 scenarios.

Fig. 4.5. Aboard the destroyer *USS Peterson* in the Atlantic Ocean, a crew member inspects fuel received from the fleet oiler *USNS Neosho*.

Atlantic-bound vessels are lowered to sea level. Data will include enough information to allow accurate modeling of end-to-end transit of the canal, including locking operations and intermediate transit. ORNL's models will be run to forecast the behavior of canal traffic in the years 2020 and 2060, or until the models indicate that capacity is reached. The results will facilitate the plotting of a delay curve for each alternative. Models will be validated using historical data about the existing canal.

The center has attained a position of national leadership in the compilation, maintenance, and analysis of transportation data.

4.3 METHODS AND DATA

The center has attained a position of national leadership in the compilation, maintenance, and analysis of transportation data. Examples that illustrate that leadership in 1991 include initiation of a study to determine relationships between highway geometry and truck accidents, and publication of two major collections of vehicle data, the *Transportation Energy Data Book* and *Highway Vehicle MPG and Market Shares Report*.

4.3.1 Highway Safety and Geometric Design

The Surface Transportation Assistance Act of 1982 (STAA) preempted more restrictive state vehicle size and weight limits. STAA has allowed longer and wider trucks to travel on designated national highways. Safety questions, such as whether the current highway design is adequate to serve these larger trucks and what highway geometric design variables pose the most serious safety problems for large trucks, are important public and government concerns. However, vehicle accidents have long been recognized as

complex events involving the interactions of many factors: road, vehicles, drivers (human factors), traffic, and environment (e.g., weather and lighting conditions). Previous attempts to establish relationships between truck accidents and highway geometric design variables have had mixed results, and no specific relationships are widely accepted.

During 1991, the FHWA initiated a two-phase process to study this relationship between highway geometric design and truck accidents. The Phase I objectives were (1) to identify a statistical framework with desirable properties to establish relationships between truck accidents and highway geometric design; (2) based on the identified statistical framework, to develop preliminary models using recent and more detailed data from the existing data sources; and (3) to suggest areas in which the quality and quantity of existing data can be enhanced to improve the developed models. CTA's Statistics and Data Analysis Group made significant contributions to the Phase I work, which was completed at the end of November 1991. Phase II will focus on collecting additional data and improving data quality to enhance the projection capability of the models developed in Phase I.

4.3.2 National Transportation Surveys

Several projects are under way for the FHWA, as a result of DOT's Statement of National Transportation Policy (NTP). The NTP identifies a wide range of issues and policies related to the collection, processing, and distribution of transportation data, and it states clearly that it is the federal government's specific policy to identify national needs for information on transportation. This year, the center played a significant role in three major national transportation data collection and distribution efforts.

- 1987 Truck Inventory and Use Survey (TIUS) provides data on the physical and operational characteristics of the nation's truck population. ORNL's involvement focused on developing methods to improve data quality and on analyzing the data.
- 1989 Nationwide Truck Activities and Commodity Survey (NTACS) provides

This year the center played a significant role in three major national transportation data collection and distribution efforts.

(text continues on page 4-10)

TRANSPORTATION ENERGY DATA BOOK

The *Transportation Energy Data Book* is a statistical compendium prepared and published for the U.S. Department of Energy's (DOE's) Office of Transportation Technologies. Designed for use as a desk-top reference, the data book presents statistics and information that characterize transportation activity, as well as data on factors relevant to transportation energy use. The purpose of the document is to present relevant statistical data in the form of tables and graphs. Each of the major transportation modes—highway, air, water, rail, pipeline—is treated in separate chapters or sections.

Recognized internationally as a primary source for transportation data, the *Transportation Energy Data Book* reached an external distribution of almost 1000 copies this year. This publication's users include Congress, the automobile industry (viz., General Motors Company), numerous federal and state government agencies, regulatory boards, and foreign government and research institutes. For example, data contained in this publication were used in the development of the National Energy Strategy by DOE. ♦

ORNL-Photo 1510-92

ORNL's Pat Hu (left) and Stacy Davis (University of Tennessee) coordinate the production of the *Transportation Energy Data Book*, which has an external distribution approaching 1000.

additional information to TIUS on commodities carried, basic commodity flow information, and safety features. The center's involvement included an evaluation of the survey design, a determination of priorities to most efficiently allocate the available resources, and development of statistical methods to establish the link between TIUS and NTACS.

- 1990 National Personal Transportation Study collects information on the travel behavior of the nation's population. Survey data will be analyzed and published in a four-volume report series.

The center is also undertaking a project to estimate the extent of local governments' involvement in constructing and maintaining the nation's highway infrastructure. In addition, the center is participating in the planning of several national surveys—1992 TIUS and NTACS, 1993 Commodity Flow Survey, and the Intercity Passenger Travel Survey.

4.3.3 Highway Vehicle MPG and Market Shares Report: Model Year 1990

The report series *Highway Vehicle MPG and Market Shares Report* analyzes the estimated sales-weighted fuel economies, sales, market shares, and other production costs of new automobiles and light trucks. The estimates are made on a make and model basis (e.g., Chevrolet is a make and Corsica is a model) from model year 1976 to the most current year. Vehicle sales data are used as weighting factors in estimating production and consumption costs. Thus, the estimates represent averages of the overall new vehicle fleet, reflecting the composition of the fleet. Highlights are provided on trends in vehicle costs and sales characteristics from one model year to the next. Analyses are also made on fuel economy changes to determine what has caused the changes.

The new 1990 automobile fleet experienced a fuel economy loss of 0.4 mpg from the previous model year, dropping to 27.6 mpg. This is the second consecutive decline in the fuel economy of new automobiles since model year 1983. The

main reason for this decline is that the compact, midsize, and large size classes—which together claimed more than 75% of the new automobile market—each experienced fuel economy declines of 0.4 mpg or more. In contrast, the new 1990 light truck fleet showed an increase of 0.3 mpg from the previous year to a current rating of 20.5 mpg. The fuel economy increase in new 1990 light trucks was primarily because the large pickup class, which represents 35.0% of the new 1990 light truck market, experienced a gain of 0.7 mpg in its fuel economy. In a combined fleet total, the sales-weighted fuel economy of the new light-duty vehicle fleet (automobiles and light trucks) dropped to 24.8 mpg in model year 1990, a reduction of 0.2 mpg from model year 1989.

4.4 MILITARY PLANNING AND SCHEDULING SYSTEMS

Researchers in the center and its predecessor organizations have worked closely with military traffic planners for several years and have developed extensive and unique expertise in a broad spectrum of military transportation problems. Working from solid foundations in operations research and computer technology, CTA staff members have helped the military transportation agencies solve problems that dwarf most civilian movement efforts.

4.4.1 FAST Planning for USTRANSCOM

During crisis action planning, the Office of the Joint Chiefs of Staff (JCS) is responsible for quickly providing the Secretary of Defense with estimates of the transportation assets and time required to move components of the armed forces from one location to another. For large deployments, the JCS delegates this responsibility to the U.S. Transportation Command (USTRANSCOM) at Scott Air Force Base. However, recent experience in operations Desert Shield and Desert Storm has demonstrated a significant shortfall in the required capability to analyze large deployments. Prior to Operation Desert Shield, available transportation analysis systems were designed for peacetime and out-year planning. The systems needed a large data base of movement requirements, which would have taken days or months to build, and which would

(text continues on page 4-14)

AIRLIFT DEPLOYMENT ANALYSIS SYSTEM SUPPORTS THE OPERATION DESERT STORM AIRLIFT

When Iraq invaded Kuwait on August 2, 1990, and President Bush ordered the deployment of armed forces to the Persian Gulf region, the Military Airlift Command (MAC) began the largest airlift in history. A typical airlift mission carrying troops and cargo to the Persian Gulf required a 3-day round trip, visited seven or more different airfields, burned almost a million pounds of fuel, and cost \$280,000. During Operation Desert Storm, MAC originated more than 100 such missions daily. As of August 7, 1991, 25,000 missions had delivered more than 966,000 passengers and 774,000 tons of cargo to and from the Persian Gulf region. Each mission required scheduling aircraft, crew, and mission support resources to maximize the on-time delivery of cargo and passengers. To meet this challenge, MAC worked with the Oak Ridge National Laboratory (ORNL) through the Center for Transportation Analysis to develop and deploy the Airlift Flow Planning component of the Airlift Deployment

Analysis System (ADANS). Within 3 months of the onset of Operation Desert Shield, ORNL delivered a working software module to provide a set of decision support tools for the management of information on cargo and passengers to be moved and the available airlift resources. ORNL also provided tools to schedule missions, analyze the schedule, and distribute the schedule to MAC's worldwide command and control system. Using this decision support system, airlift planners can now react more efficiently to crises anywhere in the world (Fig. 4.6).

For each airlift mission, MAC needed to create a detailed itinerary, including the type of aircraft to be used, the operator assigned to fly the mission, the arrival and departure times at each station, the activities at each station (onloading cargo, offloading cargo, changing crews, refueling), the military units that would be transported, and any special instructions necessary for completing the mission. As the first missions departed for the

ORNL-DWG 92-6666

Fig. 4.6. The Airlift Deployment Analysis System's (ADANS's) accelerated development schedule, precipitated by operations Desert Shield and Desert Storm.

Persian Gulf, flow planners began to use the planning systems in place at MAC Headquarters. The existing automated systems were soon found to be inadequate to support an enormous airlift operation. Due to slow speed and lack of flexibility for incorporating real-world scheduling constraints, the existing systems did not provide sufficient automated support to effectively meet the airlift scheduling challenge. The flow planners had little help from any automated system; they were limited to planning missions on paper and typing them directly into the MAC command and control system. The planners had no automated decision support or analysis tools that allowed them to view the overall schedule and address "what if" questions.

On August 20, 1990, MAC's crisis action team director requested that the development of ADANS be accelerated to provide an automated airlift scheduling capability as quickly as possible. Knowing that MAC's system would be tested to the maximum, he believed that an improved scheduling capability would help ensure the nation's success. Several center staff went to Illinois to work with MAC's crisis action team at Scott Air Force Base so that they could better understand the concept of operations for the deployment. The ADANS development effort was reorganized into several "tiger teams" that could confront specific critical issues. These teams addressed airlift network and resource management, communications, reports, data management, schedule analysis, and end-user support. The center's operations group accelerated the development of a dynamic programming-based automated airlift scheduling algorithm that would become the centerpiece of ADANS's automated scheduling tools. The ADANS development staff worked 7 days a week with flow planners at MAC, providing continuous participation by ORNL from early August 1990 until mid-January 1991. By working directly with the flow planners, ORNL developers were able to see problems first-hand, to design

solutions quickly, and to communicate needs to the software development staff. The program staff met the challenge; on October 23, 1990, ADANS became MAC's exclusive Operation Desert Shield airlift scheduling system. The result of the partnership between developers and flow planners was an integrated system that MAC's flow planners could use to enter and evaluate cargo and passenger movement requests; to allocate airlift resources, including aircraft availability, aircraft characteristics, crews, airfield resources, and airlift network configurations; to schedule missions; to update mission schedules; to analyze schedules; and to distribute schedules through MAC's command and control system (Fig. 4.7).

ADANS coordinated a deployment that moved the equivalent of the combined population of Oklahoma City and Arlington, Virginia, with all of their household goods . . . from the United States to the Persian Gulf and returned them home.

It is difficult to quantify the benefits of ADANS for MAC. MAC had never responded to an airlift challenge of this magnitude before. As MAC commanders have pointed out, ADANS coordinated a deployment that moved the equivalent

of the combined population of Oklahoma City and Arlington, Virginia, with all of their household goods, vehicles, food, and supplies, from the United States to the Persian Gulf and returned them home. During the first months of the Persian Gulf airlift, flow planners spent much of their time reacting to events that complicated the scheduling process. The more efficient ADANS scheduling tools enabled the flow planners to make a transition from their reactive posture to a proactive stance by providing them with more time to evaluate the quality of their airlift schedules. The result was more efficient airlift operations due to better coordination between the military units being moved and the MAC staff scheduling the missions.

ADANS has made scheduling missions more effective at MAC by replacing manual scheduling methods and providing planners with better information so that they can do their job more efficiently. Flow planners can now react more efficiently to quick response missions, create channel missions in minutes instead of hours.

The ADANS Processing Environment

Fig. 4.7. The Airlift Deployment Analysis System (ADANS) provides tools for matching movement requirements with airlift resources to create a schedule for an airlift operation.

evaluate multiple courses of action, and develop time-phased airlift flows. Schedule analysis tools and graphical displays highlight conflicts and excess commitments of resources, allowing planners to assess multiple concepts of operation more rapidly. Major General Vernon J. Kondra, MAC's Deputy Chief of Staff for Operations and Transportation, visited ORNL on April 3, 1991, to thank the staff members for their work. He spoke of the transition from the early days of the operation when there were no scheduling tools to the advent of ADANS and the beginning of a controlled and managed flow of aircraft and materiel. He thanked the development staff and said, "I guarantee you that we could not have done that [the deployment to the Persian Gulf] without your help and the contributions you made to ADANS—we absolutely could not have done that."

MAC continues to use the system daily to respond to crises, to provide disaster and humanitarian relief, and to plan military exercises, but the completion of the capabilities used in Operation Desert Storm was not the end of the ADANS effort. During the latter months of fiscal year 1991, the ADANS staff concentrated on developing increased capabilities for peacetime planning and coordination of all airlift operations through the development of the Special Assignment Airlift Missions and Airlift Allocation (Barrelmaster) components. Current research is focusing on specialized tools to assess courses of action and provide quick estimates of resource requirements and capabilities based on the limited information available in the early phases of an operation. As MAC and ORNL develop these capabilities, the goal is always to improve MAC's ability to respond to crises quickly and effectively anywhere in the world. ♦

have made it extremely difficult to respond quickly.

To meet military needs for transportation analysis during deployment and "no-plan situations" (when no requirements data base is available) CTA staff have designed and implemented new analytical tools for incorporation into an existing model, the USTRANSCOM Flow and Analysis System (FAST). Revisions and extensions include changes to the sealift scheduler and airflow estimator to mirror the constraints experienced during the execution of Desert Shield, an ability to track (in near-real time) the position and activity of all ships as reported by USTRANSCOM's Component Commands, and an ability to forecast changes in delivery profiles based on possible changes in the transportation infrastructure (such as closing the Suez Canal). The changes have been implemented and integrated into the FAST prototype that has been distributed to seven test sites.

4.4.2 Tracking Household Goods and Other Shipments

An expensive and important adjunct to the dramatic movement of soldiers and weapons is the more mundane movement of the soldiers' baggage and household goods. Staff members at the center have designed and prototyped the Worldwide Household Goods Information System for Transportation Modernization (WHIST-MOD) to fully automate the Military Traffic Management Command's (MTMC's) tracking of household goods and household goods carriers. WHIST-MOD is based on an MTMC household goods shipment data base that the system keeps current by automatically acquiring data from shipping offices worldwide. The system provides MTMC's analysts easy data retrieval, analysis, and graphical displays that allow them to spot and analyze problems in the household goods shipment system in a timely manner. Recognizing that the shipment of personal property is in a constant state of

ORNL-Photo 1551-92

Staff members have designed and prototyped the Worldwide Household Goods Information System for Transportation Modernization to fully automate the tracking of household goods carriers.

regulatory and administrative flux, CTA members have included design features that enhance software maintainability and extensibility.

For another division of MTMC [the Directorate of International Traffic (MTIT)], the center is analyzing requirements for the Integrated Booking System, an international cargo booking system for unit and nonunit movements in both peacetime and wartime. In addition, ORNL will provide assistance in describing a shared-data environment for MTIT. The proposed system will provide global visibility for international cargo traffic, support data exchange, maintain historical data for analysis, and automate the processing of shared data.

4.5 SHARING CTA EXPERTISE

4.5.1 Reliability-Centered Maintenance

Center staff who have significant recent experience with the Bonneville Power Administration (BPA) grid have been asked to undertake a multiyear project to provide assistance to BPA in the implementation of a reli-

ability-centered maintenance (RCM) program. RCM techniques have the potential to improve the quality of maintenance of electrical and mechanical equipment and simultaneously reduce the maintenance costs.

4.5.2 Workstations and Secure Networking

One of the center's computer experts is advising the Assistant Secretary of the U.S. Army for Research and Development, Acquisitions—Product Manager of Acquisition Information Management (AIM) at Fort Belvoir, Virginia. Consultation includes assessing workstation and secure telecommunications technologies and planning the transition from dedicated secure telephone lines to connection to the Defense Secure Network (DSNET). The center will develop a prototype for linking classified and unclassified electronic mail (when approved means become available), and benchmark AIM connectivity on DSNET as on-line sites become available.

Efficiency

and Renewables Research

ORNL-Photo 1511-92

George Courville, Section Head

5. EFFICIENCY AND RENEWABLES RESEARCH SECTION OVERVIEW

5.1 INTRODUCTION

The Efficiency and Renewables Research Section (ERRS) conducts research to improve the efficiency of energy end-use and delivery technologies, participating in industry interactions and joint projects such as Cooperative Research and Development Agreements (CRADAs). The major research areas within the section are related to energy use in buildings, transmission and distribution of electricity, and development and assessment of strategies for implementing energy-efficiency measures. Buildings research includes studies of equipment such as heating, ventilation, and air-conditioning (HVAC) systems; refrigeration; district heating, cooling, and cogeneration; building envelopes and materials; and monitoring and retrofitting of existing buildings. Electricity delivery systems research analyzes real-time power control, high voltage dc transmission, interfacing renewables with the utility grid, biological effects of 60-Hz radiation, power systems transients due to disturbances such as high electromagnetic pulses (EMPs) or geomagnetic storms, and assessment of novel transmission and distribution materials and components. Implementation strategies include integrated resource planning/demand side management (IRP/DSM) systems and weatherization assistance programs. Additional research areas include thermal environment control systems, automobile air-conditioning, performance audits for existing buildings, energy systems in developing countries, and research on technology transfer processes. The section continues to focus on assessment of the characteristics of replacement materials for foam insulations and refrigerant fluids that use chlorofluorocarbon (CFC) compounds.

5.2 BUILDING EQUIPMENT RESEARCH PROGRAM

The Building Equipment Research (BER) Program at Oak Ridge National Laboratory (ORNL), sponsored principally by the U.S. Department of Energy (DOE) Office of Building

Technologies, has as its primary focus the development of technology for more efficient space heating and cooling, refrigeration, and water-heating equipment used in residential and commercial buildings. Because environmental issues such as ozone depletion and global warming are increasingly important, the program is contributing to the U.S. industry's transition from CFC refrigerants to acceptable, atmospherically safe alternatives that provide equal or better energy efficiency. The BER program has strengthened its ties with industry and is actively working with individual companies and through industry consortia and major trade associations to plan and conduct government and industry cooperative research and development programs. Research sponsorship has also been broadened to include other federal agencies, technical societies, and national utility research institutes. The research pursued in the BER program continues to fall under three areas of activity: thermally activated heat pumps, novel cycles, and advanced refrigeration systems.

5.2.1 Thermally Activated Heat Pumps

System development, component development, and supporting research activities were continued on a residential generator-absorber heat exchange (GAX) absorption heat pump, on an advanced commercial absorption chiller, and on Stirling-engine-driven and internal combustion (IC) engine-driven vapor compression heat pumps. A new project was initiated to formulate and evaluate improved fluid mixtures for absorption heat pumps.

Thermal efficiency goals for the GAX heat pump were achieved with a compact, laboratory package unit at Phillips Engineering Company. The unit demonstrated coefficients of performance (COPs) of 1.6 in heating and 0.7 in cooling, but thermal capacity remained below the design objective.¹ Development efforts on the system's thermal design are continuing, and the technology

(text continues on page 5-3)

TERNARY SOLUTIONS FOR GAX ABSORPTION HEAT PUMPS AND AIR CONDITIONERS

An in-house project was initiated to formulate ternary ammonia/water/salt solutions for generator-absorber heat exchange (GAX) absorption heat pumps and air conditioners. Adding a salt to the ammonia/water solution reduces the water content of the vapor phase, thus reducing the need for rectification at the generator exit and allowing greater generator-absorber temperature overlap for improved efficiency (as illustrated in Fig. 5.1). The objective here is to identify mixtures that improve system performance without unacceptably increasing corrosion. Several promising quaternary mixtures were formulated in preliminary screening corrosion tests (see Fig. 5.2). ♦

ORNL-Photo 1222-91

Fig. 5.2. Preliminary screening corrosion tests are being conducted for several promising quaternary mixtures.

ORNL-DWG 91-5400

Fig. 5.1. Cooling-performance improvement as a function of generator temperature for various generator-absorber heat exchange (GAX) fluids. All results relative to ammonia/water fluid performance.

remains highly promising. Also, component development for an engineering field test unit neared completion. An independent manufacturing cost estimate confirmed the potential for low first cost (potentially the same cost as existing midline products). ORNL program staff members initiated facilitation of private-sector adoption and commercialization of this technology through collaboration with the American Gas Cooling Center, which is supported by the gas utility industry.

A new subcontract was awarded to Battelle Memorial Institute's Columbus Division and York International for the development of an advanced high-efficiency absorption chiller for commercial building applications, with a predicted cooling COP of up to 1.6. Battelle will use a modified commercially available York chiller to evaluate alternative absorber performance additives and corrosion inhibitors for a lithium bromide/water solution and will evaluate engineering materials for the high-temperature generator section. Technical work was just getting underway at year's end.

RA Technology conducted an analytical study of a high-efficiency ammonia/water absorption chiller cycle with funding from ORNL/DOE, California Energy Commission, and Pacific Gas and Electric Company. A cooling COP of up to 1.4 appears possible with this cycle.

Subcontractors Sunpower, Inc., and Mechanical Technology, Inc. (MTI) continued work on magnetically coupled free-piston Stirling-engine-driven heat pumps (FPSEHPs). The Stirling engine is most promising for implementing an engine-driven thermally activated heat pump. Compared to conventional prime movers, an engine based on the Stirling cycle has the potential for higher efficiency, longer life, and lower manufacturing cost. Sunpower's dynamic analysis of their existing engine-compressor hardware led to a compressor-end redesign to reduce friction and resolve starting problems.² The modified unit should be tested in early fiscal year (FY) 1992. MTI completed a dynamic analysis of their conceptual FPSEHP design's starting and stability. They also completed design work and component tests for the development of a low-cost Stirling-engine combustor using low-pressure natural gas.

With cofunding from the National Aeronautics and Space Administration (NASA)-Lewis Research Center, basic research continued at Massachusetts Institute of Technology on the heat transfer processes which take place in Stirling engines.

Subcontractor Tectonics Companies, Inc., (TCI) worked with ORNL on an improved dynamic simulation of the TCI segmented, articulated bellows-type refrigerant seal for TCI's free-piston linear engine-compressor.³ The

ORNL-Photo 1502-92

Laboratory technicians Randy Linkous and Phil Childs provide valuable support to the technical staff.

simulation showed that the seal performance is sensitive to harmonics from the piston motion, providing a design tool for avoiding resonances. TCI began evaluations on sliding contact refrigerant seals as a backup to the bellows seal. TCI also began fabrication of a demonstration unit of their linear free-piston IC engine-compressor for light commercial applications and started construction of test-bed engines for fuel-system and starting-and-control system development.

Adiabatics, Inc., and Southwest Research Institute completed scoping studies of novel, high-durability, low-maintenance internal combustion engine designs for heat pump drive.

Both engine concepts were based on single-cylinder, fuel-injected, two-stroke-cycle configurations with advanced combustion systems for low emissions, possibly operating several years without maintenance. Limited funding prevented further experimentation on these designs.

5.2.2 Novel Cycles

As part of a continuing effort to evaluate potential refrigeration cycle alternatives, Sunpower, Inc., and MTI performed studies to determine Stirling cycle performance in the cooling mode. Results of prototype machine tests compared with computer simulations. Analytical studies were also performed to determine efficiency limits. Conclusions indicate that the Stirling cycle might serve well in domestic refrigeration applications. A project examining electric motor-driven gas-cycle refrigerator options (including Stirling, Brayton, Ericsson, etc.) has begun; the study includes design, fabrication, and testing activities intended to demonstrate the commercial feasibility of the gas-cycle refrigerator.

A project assessing the feasibility of desiccant cooling and dehumidification (DCD)

Research on CFC alternatives continued to grow in scope, including development of utilization technology for ozone-safe refrigerant mixtures.

technology indicates that such technologies can be economically integrated into commercial HVAC systems. A completed draft report anticipates reduced summer electric utility peak loads among the desirable impacts of DCD technology implementation.

Subcontractor Quantum Group, Inc., completed an assessment of thermophotovoltaic (TPV) concepts, which would provide power for controls and other auxiliaries in a thermally activated heat pump. The draft final report concludes that if future costs can be reduced significantly, TPV subsystems may be attractive candidates with absorption and Stirling-engine-driven heat pumps.

5.2.3 Refrigeration Systems

Research on CFC alternatives continued to grow in scope, including development of utilization technology for ozone-safe refrigerant mixtures. CRADAs were signed and approved with chemical and appliance industry consortia. In collaboration with the HVAC industry, new programs currently are developing tools to expedite heat exchanger design with alternative refrigerants and are screening potential alternatives to hydrochlorofluorocarbons (HCFCs)—particularly R-22—for heating and air-conditioning applications.

A second CRADA was signed late in the year with the Appliance Research Consortium, a subsidiary of the Association of Home Appliance Manufacturers. The goal here is to develop advanced technology that will reduce energy consumption of post-1998 domestic refrigerator-freezers (RFs) by 40–50%. This will involve analytical screening of various advanced cycle design options, along with experimental verification using two breadboard RF test stands. Participating appliance manufacturers have agreed to provide almost all of the components for the test stands, as well as baseline data for the analyses.

Efforts to develop efficient alternatives to R-12 (CFC-12) in domestic RFs are continuing. A project cosponsored by DOE and the Environmental Protection Agency completed evaluation of advanced, two-evaporator refrigeration cycles. One such cycle, the Lorenz-Muetzner (LM), uses nonazeotropic refrigerant mixtures (NARMs). Testing of this cycle in a modified RF with a R-32/R-124 NARM yielded daily energy consumption about 3% lower than the original RF with R-12 (2.9 kWh/day versus 3.0 kWh/day). This result includes the effects of cycling and defrost energy consumption. Comparison of steady-state operation showed that the LM unit is 10–15% more efficient, paralleling analytical estimates of steady-state performance with this NARM.⁴ Cosponsored by the American Society of Heating, Refrigerating, and Air-Conditioning Engineers, another project completed this year determined the energy efficiency potential of R-12 alternatives in standard single-evaporator RF designs. Americold Compressor Co. provided compressors tailored for each alternative refrigerant. R-152a was found to be the best

performing alternative, with daily energy consumption about 3% higher than with R-12.⁵

Research continued on improving heat exchanger (HX) effectiveness (ϵ) with NARMs. A novel, segmented evaporator was installed on a laboratory test rig. The first section of the designed evaporator improves nucleate boiling of the low-quality (high liquid fraction) entering refrigerant; the second section augments flow evaporation in the high-quality region. Tests with R-22 and an R-143a/R-124 NARM show that the NARM takes much better advantage of this evaporator's heat transfer augmentation potential (Fig. 5.3). A theory for HX performance with NARMs—incorporating variable specific heat into the classical ϵ -NTU (number of transfer units) analysis—was verified with laboratory test data.⁶

ORNL-DWG. 91-5379

Fig. 5.3. Nonazeotropic refrigerant mixture (NARM) test rig cycle coefficient of performance (COP) versus capacity: comparison of R-143a/R-124 and R-22 COPs with segmented evaporator and smooth-surface evaporator.

New program areas are being initiated in collaboration with the HVAC industry through the Air-Conditioning and Refrigeration Institute (ARI). The first involves development of tools for designing heat-transfer surfaces to yield optimum HX thermal performance with alternative refrigerants. The industry is providing baseline data for an initial sensitivity analysis of the impact of HX augmentation levels on system performance for a number of applications. Analytical and experimental investigations to develop generalized design correlations will be

conducted at government (ORNL, National Institute of Standards and Technology), industry, and academic labs. ARI will form an industry advisory board to review and guide the program.

5.2.4 Work for Others for the BER Program

5.2.4.1 Advanced Surfaces for Vertical-Tube Absorbers

A project initiated last year at ORNL involving absorber design is being supported by the Gas Research Institute. This project uses a combined experimental and analytical approach for the development and codification of an absorber design methodology. The objective is to develop a practical, simple, yet broadly applicable technique to design vertical-tube LiBr (lithium bromide)/water falling-film type absorbers with enhanced tube-surface geometries. This year, the experimental apparatus (see Fig. 5.4) was completed and tests were conducted to

ORNL-Photo 3788-91

Fig. 5.4. An experimental absorber design developed by Oak Ridge National Laboratory and the Gas Research Institute.

characterize smooth-tube performance. An analytical model has been formulated to predict absorber performance, and heat- and mass-transfer correlations were extracted from the literature. Testing of correlations for enhanced tube geometries are currently in progress. This year, a proposed extension will provide experiments with a nonintrusive, laser-induced phosphorescence method of determining solution film temperature profiles along the tube's length. The temperature-profile information will help determine local heat- and mass-transfer coefficients.

candidates. The major results are given in Table 5.1. A number of the alternatives gave modeled performances comparable to R-11, though they all appear to be flammable.⁷ The method used to determine flammability, however, was developed for fluoroalkane compounds and might not be valid for ethers like E-143.

5.3 THERMAL AND ENVIRONMENT CONTROL SYSTEMS

The main research objective of this group is to develop innovative thermal and environmental control technologies for cost-effective and efficient energy use. Research activities include thermal sciences for industrial and utility technologies, and environmental control applications for transportation and the military.

During the year, a thermomagnetic refrigeration cycle loss analysis was completed, which finds the regenerative cycle to be most efficient. For gadolinium operating between 0 and 7 T in a heat pump cycle with a heat-rejection temperature of 320 K, analysis predicted a 42% loss in COP at 260 K cooling temperature for the constant-field cycle, as compared with the ideal regenerative cycle. Such substantial losses indicate that potential irreversibilities from the additional heat transfer needed for the constant-field cycle may

adversely affect the viability of certain proposed magnetic heat pumping (MHP) concepts—if these performance flaws are not adequately addressed.

Critical magnetocaloric material data and thermal physical property model review were used to establish a reliable data base. A subcontract was awarded for the design and fabrication of a pulsed dc superconducting magnet

(text continues on page 5-9)

ORNL-Photo 1512-91

Data from laboratory experiments are used to verify computer modeling. (Left to right: Bill Miller, Gene Holt.)

5.2.4.2 EPRI CFC Alternatives for Centrifugal Chillers

An Electric Power Research Institute (EPRI)-sponsored project within the BER Program investigated zero-ozone-depletion alternatives to R-11 and R-123 for centrifugal chiller applications. This work focused on long-term alternatives beyond the initial CFC phaseout, including several partially fluorinated alkanes and ethers proposed as potential

Table 5.1. Modeled performance results of zero-ozone-depletion alternative refrigerants for centrifugal chiller application

Refrigerant	Formula	Normal boiling point (°F)	Modeled COP	Kilowatt per ton	Superheat added (°F)	Flammability indexing
E-254cb	CHF ₂ -O-CF ₂ CH ₃	97.6	7.38	0.641	7.8	Flammable ^a
E-245cb	CF ₃ -O-CF ₂ CH ₃	93.3	7.33	0.643	11.7	Uncertain-to-flammable ^a
R-152	CH ₂ FCH ₂ F	87.2	7.60	0.615	0.0	Flammable
E-143	CHF ₂ -O-CH ₂ F	86.1	7.50	0.628	0.0	Flammable ^a
R-123	CHCl ₂ CF ₃	81.7	7.42	0.629	2.0	Nonflammable
R-245ca	CHF ₂ CF ₂ CH ₂ F	78.1	7.33	0.639	7.0	Uncertain
R-11	CCl ₃ F	74.9	7.54	0.614	0.0	Nonflammable
R-245fa	CF ₃ CH ₂ CHF ₂	59.5	7.26	0.642	7.6	Uncertain
R-236ea	CF ₃ CHFCHF ₂	43.7	7.14	0.650	11.7	Nonflammable
R-236ca	CHF ₂ CF ₂ CHF ₂	41.0	7.11	0.651	12.1	Nonflammable
R-143	CHF ₂ CH ₂ F	41.0	7.49	0.611	0.0	Flammable
E-134	CHF ₂ -O-CHF ₂	40.4	7.32	0.633	0.0	Uncertain ^a
R-114	CClF ₂ CClF ₂	38.5	7.12	0.645	14.2	Nonflammable
R-236cb	CF ₃ CF ₂ CH ₂ F	34.2	7.08	0.651	12.9	Nonflammable
R-236fa	CF ₃ CH ₂ CF ₃	30.0	7.04	0.654	12.9	Nonflammable
R-134	CHF ₂ CHF ₂	-3.5	7.17	0.635	2.6	Nonflammable
R-152a	CHF ₂ CH ₃	-13.0	7.17	0.633	0.0	Flammable
R-134a	CF ₃ CH ₂ F	-15.7	6.97	0.653	0.0	Nonflammable

^aValidity of index for ethers uncertain.

ALTERNATIVE FLUOROCARBONS ENVIRONMENTAL ACCEPTABILITY STUDY COOPERATIVE RESEARCH AND DEVELOPMENT AGREEMENT

A cooperative research and development agreement (CRADA) was established with the Alternative Fluorocarbons Environmental Acceptability Study (AFEAS), a consortium of chemical manufacturers, to assess the total global warming impact of CFC alternatives. A concept of Total Equivalent Warming Impact (TEWI) was developed for combining the *direct* global warming effects from fluorocarbon emissions (greenhouse gases) and *indirect* effects of CO₂ emissions from energy use. The concept, used for evaluating CFC-replacement options, is illustrated in Fig. 5.5 for replacement of CFCs with HCFCs or HFCs in a household refrigerator. The study involved extensive interaction with both CFC-user industries and the chemical producers throughout North America, Europe, and Japan. Analyses of industry technology surveys indicate that CFC-user industries have made substantial progress toward

near-equal energy efficiency with many HCFC/HFC alternatives. The findings also question the relative importance of the *direct* effect in many applications and stress energy efficiency when searching for suitable CFC alternatives. For chillers, household refrigerators, unitary air-conditioning or heat pump equipment, and foam wall insulation, changes in efficiency of only 2-5% would have a greater effect on future TEWI than completely eliminating the *direct* effect. The report for this project⁸ will be used next year by the United Nations Environment Programme (UNEP) during its revision of the 1987 Montreal Protocol. BER staff member E. A. Vineyard also participates in the Protocol revision process as principal author of the household-refrigeration chapter of the *UNEP Refrigeration, AC and Heat Pump Technical Option Report*.⁹ ♦

ORNL-DWG 91Z-15747

The following two examples are based upon an identical energy efficiency of systems compared.

Conceptual Basis For The Study

Fig. 5.5. Refrigerator-freezer shows impact of CFC alternatives.

for MHP cycle heat-transfer experiments, which is underway jointly with the Fusion Energy Division.

A condensing/absorbing heat-transfer test has been initiated to directly support development of an advanced binary working fluid Kalina power cycle system under construction by Energy, Inc., in Canoga Park, California (Fig. 5.6). Because 80% of heat exchanger surface-area costs result from the condenser design's uncertainty, a successful effort—cofunded through a CRADA between DOE-OIT and Exergy—will make Kalina cycle power systems more cost-competitive.

A performance model for small gas turbines and a design model for safety-critical, compact heat pipe heat exchangers have been developed in support of the U.S. Army program on auxiliary-

powered environmental control systems. In addition, a portable self-powered space heater was developed for military use this year.

Developing non-CFC mobile air-conditioning (MAC) technology is another major program area. A draft report was completed, and promising non-CFC alternatives were identified in a technology assessment of broad-range MAC concepts. Based on the assessment, work has been initiated to develop a computer code for MAC applications. Intended to improve the energy efficiency of near-term non-CFC vapor compression MAC technology, design of a laboratory experiment is underway to test a MAC unit using refrigerant R-134a.

Transportation CFC emission reduction is an important issue in MAC technology

(text continues on page 5-11)

ORNL-Photo 980-92

Fig. 5.6. 3-MW(e) kalina cycle power plant under construction in Canoga Park, California.

ATTIC TESTING

This last year, a major research project conducted with the Large Scale Climate Simulator involved measuring how effectively attic insulation keeps heat in during winter. The results directly challenge some long-established assumptions. Measurements on some types of loose-fill fiberglass insulation confirmed that significant natural convection heat loss can occur under sufficiently cold winter conditions (Fig. 5.7). This work verifies that natural convective heat loss in some loose-fill fiberglass insulations can be responsible for as much as half of the heat lost when the attic is 0°F or colder (Fig. 5.8).^{10,11} Similar tests on high-density cellulose insulation showed no significant natural convection at low temperatures.

Fig. 5.7. Benard-cell pattern for enclosed fluid heated from below.

Testing and modeling are continuing for innovative ways to retard natural convection in attics and to find optimum methods of keeping heat from escaping when it is most needed—on that cold winter morning (Fig. 5.9). This research will likely lead to several major changes in test procedures and the physical characteristics of some commercially available loose-fill fiberglass insulations. ♦

Fig. 5.8. Attic temperature versus R-value of loose-fill fiberglass insulation (note: curves show only an approximate fit to data points from test).

Fig. 5.9. Ken Wilkes inspects the attic testing facility.

development. Two patents have been filed this year for several new non-CFC leak detecting and identification technologies developed jointly with the Health and Safety Research Division. A prototype of an electron attachment leak detector (Fig. 5.10) has been built and successfully tested for R-134a leakage, and three technology transfer workshops were co-sponsored by the Office of Technology Applications of Martin Marietta Energy Systems, Inc.

5.4 BUILDING THERMAL ENVELOPE SYSTEMS AND MATERIALS

The Building Thermal Envelope Systems and Materials (BTESM) Program receives most of its funding from the Building Systems and Materials Division of the Office of Building Energy Research of DOE. The research covers walls, foundations, roofs, attics, and building materials.

The overall mission of this program is to lead private industry to substantially improve the energy efficiency and environmental acceptability of new and existing building envelope components. To accelerate the development and

acceptance of advanced envelope systems, this program manages six separate experimental test facilities:

- The Large Scale Climate Simulator is a 20- by 20-ft horizontal indoor and outdoor environmental box for testing flat roofs and attics. The outdoor box (climate chamber) can simulate any climate in the United States; air temperatures in the climate chamber can be controlled from 66 to -25°C (150 to -40°F). Roof surface temperatures can be controlled with infrared heating up to 93°C (200°F).
- The Roof Thermal Research Apparatus (RTRA) is composed of four 4- by 8-ft panels on an outdoor facility for testing flat roof sections, four insulated

The overall mission of this program is to lead private industry to substantially improve the energy efficiency and environmental acceptability of new and existing building envelope components.

Fig. 5.10. Prototype of electron attachment refrigerant leak detector.

masonry walls, and two slab-on-grade test sections exposed to the East Tennessee climate.

- The Envelope Systems Research Apparatus (Fig. 5.11) is a new 32- by 72-ft facility, built last year for field testing large, flat roof areas (currently testing 40 different roof systems and eight different basement wall insulation systems). Also, this facility could be easily modified to test residential frame walls.
- The Rotatable Calibrated Hot Box can test thermal performance of 10- by 13-ft sections of wall, floor, and roof and can simulate outdoor temperatures from -40°F to 140°F . This standard American Society for Testing and Materials (ASTM) C-97G device is expected to be operational by 1993.
- The ORNL Heat Flow Meter Apparatus is a 2- by 2-ft comparative heat flow meter designed to meet ASTM standard C-518. Equipped with a dedicated computer for unmanned test control, data acquisition, and data analysis, this apparatus calibrates heat flux

transducers used in the field exposure tests of roof, wall, and foundation systems.

- The ORNL Unguarded Thin-Heater Apparatus is a 3- by 5-ft absolute heat flow meter with less than 2% uncertainty for steady-state thermal resistance measurements. This device can also make transient measurements to determine specific heat and thermal diffusivity of building materials at different mean specimen temperatures.

5.4.1 Non-CFC Polyisocyanurate Insulation Testing

Field testing of non-CFC polyisocyanurate roof insulation systems has been conducted for 867 days on the RTRA. Data indicate that the experimental HCFC alternatives have k-factors 3–9% higher than the CFC-11 produced insulation boards currently used.^{12–16}

Thermal performance of HCFC boards has actually remained more stable over the last year than that of CFC-11 boards. After the first year of testing, the measured thermal penalty of the HCFC alternatives was 7–12%. The thermal drift of both CFC and HCFC boards, after 2.5 years, has slowed considerably.

Data from the thermal performance and mechanical property measurements conducted on the Envelope Systems Research Apparatus—largely by Roof Research Center Users from the National Roofing Contractors Association—conclude that all HCFC alternatives have acceptable behavior and could be considered as replacements for the CFC-11 blown polyisocyanurate board currently used in more than 50% of the low-sloped roofs in the United States.¹⁷

ORNL-Photo 9114-91

Fig. 5.11. Envelope Systems Research Apparatus, built last year for field testing large, flat roof areas.

5.4.2 Builders' Handbooks

The BTESM Program also distributed several useful handbooks to residential builders and contractors. One, the *Builder's Foundation Handbook*, is a tool for making foundation design decisions, complete with a worksheet for determining optimum insulation levels based on site-specific economic conditions (Figs. 5.12 and 5.13).^{18,19} A second handbook, prepared under subcontract, is the *Moisture Control Handbook—New, Low-rise Residential Construction* by Joseph Lstiburek and John Carmody. This handbook provides the building designer and contractor with information for analyzing moisture-transport mechanisms and for integrating moisture-control strategies to minimize the risk of such problems in energy-efficient buildings.²⁰

ORNL-DWG 92-6196

Fig. 5.12. The *Builder's Foundation Handbook* has an easy to use worksheet for determining how much insulation to install in your house.

5.4.3 Heat and Mass Transfer Modeling in Foundations

A heat and mass transfer model is being developed to account for the effect of moisture movement in soil adjacent to building foundations. This model is being validated with data collected around the RTRA, which has two

ORNL-DWG 92M-6236

A. CONCRETE OR MASONRY FOUNDATION WALLS WITH EXTERIOR INSULATION

CONFIGURATION	DESCRIPTION	RECOMMENDED CONFIGURATIONS AT THREE FUEL PRICE LEVELS														
		0-2000 HDD (LOS ANG)			2-4000 HDD (FT WORTH)			4-6000 HDD (KAN CITY)			6-8000 HDD (CHICAGO)			8-10000 HDD (MPLS)		
		L	M	H	L	M	H	L	M	H	L	M	H	L	M	H
EXTERIOR HALF WALL	NO INSULATION	●	●	●	○	○	○	○	○	○	○	○	○	○	○	○
	4 FT. R-5 RIGID	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
	4 FT. R-10 RIGID	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
EXTERIOR FULL WALL	8 FT. R-5 RIGID	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
	8 FT. R-10 RIGID	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
	8 FT. R-15 RIGID	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
	8 FT. R-20 RIGID	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

B. CONCRETE OR MASONRY FOUNDATION WALLS WITH INTERIOR INSULATION (COSTS DO NOT INCLUDE INTERIOR FINISH MATERIALS)

CONFIGURATION	DESCRIPTION	RECOMMENDED CONFIGURATIONS AT THREE FUEL PRICE LEVELS														
		0-2000 HDD (LOS ANG)			2-4000 HDD (FT WORTH)			4-6000 HDD (KAN CITY)			6-8000 HDD (CHICAGO)			8-10000 HDD (MPLS)		
		L	M	H	L	M	H	L	M	H	L	M	H	L	M	H
INTERIOR FULL WALL	NO INSULATION	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
	8 FT. R-4 RIGID	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
	8 FT. R-8 RIGID	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
	8 FT. R-11 BATT	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
	8 FT. R-19 BATT	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

C. CONCRETE OR MASONRY FOUNDATION WALLS WITH INTERIOR INSULATION (COSTS INCLUDE SHEETROCK ON INTERIOR WALL)

CONFIGURATION	DESCRIPTION	RECOMMENDED CONFIGURATIONS AT THREE FUEL PRICE LEVELS														
		0-2000 HDD (LOS ANG)			2-4000 HDD (FT WORTH)			4-6000 HDD (KAN CITY)			6-8000 HDD (CHICAGO)			8-10000 HDD (MPLS)		
		L	M	H	L	M	H	L	M	H	L	M	H	L	M	H
INTERIOR FULL WALL	NO INSULATION	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
	8 FT. R-4 RIGID	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
	8 FT. R-8 RIGID	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
	8 FT. R-11 BATT	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
	8 FT. R-19 BATT	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

D. PRESSURE-TREATED WOOD FOUNDATION WALLS

CONFIGURATION	DESCRIPTION	RECOMMENDED CONFIGURATIONS AT THREE FUEL PRICE LEVELS														
		0-2000 HDD (LOS ANG)			2-4000 HDD (FT WORTH)			4-6000 HDD (KAN CITY)			6-8000 HDD (CHICAGO)			8-10000 HDD (MPLS)		
		L	M	H	L	M	H	L	M	H	L	M	H	L	M	H
WOOD FULL WALL	NO INSULATION	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
	8 FT. R-11 BATT	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
	8 FT. R-19 BATT	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
	8 FT. R-30 BATT	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

1. L, R, AND M REFER TO THE LOW, MEDIUM AND HIGH FUEL COST LEVELS.
 2. THE DARKENED CIRCLE REPRESENTS THE RECOMMENDED LEVEL OF INSULATION IN EACH COLUMN FOR EACH OF THE FOUR BASIC INSULATION CONFIGURATIONS.
 3. THESE RECOMMENDATIONS ARE BASED ON ASSUMPTIONS THAT ARE SUMMARIZED IN THE BUILDER'S FOUNDATION HANDBOOK.
 4. LOS ANG = LOS ANGELES, FT. WORTH = FORT WORTH, KAN CITY = KANSAS CITY, MPLS = MINNEAPOLIS

Fig. 5.13. Easy look-up tables can be generated from the *Builder's Foundation Handbook* worksheet for different economic assumptions. The recommendations shown in this table are based on national average economic assumptions in 1988.

well-controlled soil volumes adjacent to uninsulated and insulated portions of monolithic slab-on-grade foundation.

5.4.4 Cooperative Research and Development Agreements

At this time, the BTESM Program has signed four CRADAs:

- the Polyisocyanurate Insulation Manufacturers Association/Society for Plastic Industries will be developing non-CFC foam insulation;
- the Cellulose Industry Standards Enforcement Program will measure cellulose loose-fill insulation in an attic;
- Foamseal, Inc., will be exploring thermal benefits of polyurethane

- adhesive in factory-manufactured ceiling panels; and
- the Appliance Research Consortium will be developing a k-factor test procedure for vacuum insulation panels.

Use of the Roof Research Center has increased substantially, with about 30% of activities sponsored or conducted by users in FY 1991.

5.5 EXISTING BUILDINGS RESEARCH

Research focusing on technical and implementation issues for improving the energy efficiency of existing buildings is included in two programs for DOE: the Existing Buildings Efficiency Research Program for the Office of Building Energy Research, and the Weatherization Assistance Program (WAP) for the Office of Grants Management. The U.S. Army Engineering and Housing Support Center sponsored related research on energy efficiency during family-housing revitalization, and an evaluation of an efficient lighting installation program in small commercial buildings was initiated for Commonwealth Electric Company.

A key objective of the program is to provide reliable data on the energy and cost savings of

individual and combined retrofit measures. As shown in Fig. 5.14, field tests in North Carolina and Arizona during this period and weatherization impact measurements for oil-heated homes in the Northeast have significantly increased coverage of different climatic regions.

The field test initiated with the state of Arizona measures the actual cooling energy savings and change in electric demand profiles due to exterior insulation retrofit on walls of eight concrete block houses. (Figure 5.15 shows partially completed installation of the lath strips and foam board insulation.) Insulated walls were finished with stucco. Costs were shared by DOE, the Arizona Energy Office, the City of Scottsdale, Dow Chemical Co., Salt River Project (the local electric utility), and Western Stucco Products. During the summer of 1991, 30-minute average electricity use for air conditioning was collected before and after the wall insulation retrofit, in order to evaluate cooling energy use impacts. The cost and details of installation were also collected for cost-effectiveness assessments from private and utility perspectives. Data analysis and reporting will be completed next year.

Modification of the advanced, interactive energy audit for use in hot and humid climates was completed, and the field test in the North Carolina WAP continued. The test includes monitoring indoor temperature and heating and cooling energy use for a full year before and after weatherization in three groups of 40 houses: (1) a group weatherized by the current North Carolina program, (2) a group weatherized as recommended by the audit, and (3) a control group that received no weatherization. At the end of this period, all field data were collected and entered into data bases for analysis.

Work was initiated to improve the single-family energy audit format and to add weatherization measures applicable to all other regions. When completed next year, the audit will be distributed to all states as an approved national energy audit for the DOE WAP.

DOE completed and published a consumer-oriented fact sheet on the use of radiant barriers in residential attics. This fact sheet, which explains what radiant barriers are and how they

Fig. 5.14. Existing buildings research program field-monitoring projects are providing building retrofit performance results from across the country.

work, provides information on the range of installed costs and estimates of dollar savings for heating and cooling for a wide variety of climates. Energy savings estimates rely heavily upon the modeling work. The fact sheet also provides sources for further information on installation procedures and a work sheet to account for conditions of a specific house.*

A draft planning guide for whole-neighborhood revitalization of Army family housing was completed for the U.S. Army Engineering and Housing Support Center and was distributed to all Army commands for review. On many Army installations, existing family quarters are no longer comparable with new or older, remodeled private-sector housing. The Whole-Neighborhood Revitalization Program was established to provide a systematic approach for determining the extent of repair and modernization needed to appropriately upgrade Army housing units and surrounding neighborhoods. The Planning Guide was developed to simplify identification of a revitalization project's scope and cost estimate, as well as preparation of forms required for project approval. ORNL provided guidance to ensure the maximum cost-effective level of energy efficiency during rehabilitation, while the National Association of Home Builders National Research Center contributed insight on structural and functional considerations, architectural improvements, and health and safety issues.

The ASTM standard guide on energy-monitoring "protocols" for commercial and institutional facilities, developed under ASTM Committee E06 on Performance of Buildings, was revised and approved this year by the full committee. Next year, the standard guide will proceed to ASTM society-level ballot, which means it may be available in 1992.

A project was started to evaluate the energy savings and cost effectiveness of a DSM program (initially focused on lighting retrofits) for small commercial buildings at Commonwealth Electric

Fig. 5.15. Existing buildings research program, Arizona field test—partially completed installation.

in Massachusetts. An initial evaluation was completed, which helped identify erroneous cost data. Although actual energy savings appear to be in line with engineering estimates, installed costs are higher than expected, and energy savings are less than energy-audit projections. Corrections are being made for further evaluation.

High-speed collection of electrical-power data (up to 1 kHz sampling) may be an important method for improving collection of detailed data to identify both energy-using equipment and energy-saving opportunities in commercial buildings. A pre-prototype system developed this year to collect such data will be installed next year at ORNL to begin initial testing to determine needs for pattern-recognition software that would allow on-line analysis of key events contained in the electric-power data.

Demonstration of a cooperative retrofit installation program involving a DOE regional support office (Atlanta) and ORNL has been proposed and funding for implementation requested. The program would cover lighting retrofits in small- to medium-sized commercial buildings. Details of the cooperative arrangement

* The "Attic Radiant Barrier Fact Sheet" (DOE/CE-0335P) dated June 1991 is available from the U.S. Department of Energy Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37830.

LOW-INCOME WEATHERIZATION ASSISTANCE PROGRAM

During FY 1991, the Energy Program Planning and Evaluation (EPPE) group finished planning and initiated five studies comprising the national evaluation of the U.S. Department of Energy's (DOE's) low-income Weatherization Assistance Program (WAP).^{21,22} Preliminary reports have been prepared for two of the studies. One, the "Characterization of the WAP Network," describes weatherization practices of state and local WAP agencies, the nature of agency staff and resources, public and private partnerships, obstacles to progress, and opportunities for the future. Another, the "Scope of the WAP," describes the types of low-income dwellings weatherized with DOE, utility, and other funds. The study indicates that from 1978 to 1989, \$4.4 billion was spent on full-scale weatherization activities, resulting in partial or complete weatherization of 3.9 million units. The next phase of this study (targeted for 1992-93) will characterize the eligible population that remains to be served.

The other three studies will estimate impacts of the WAP in key submarkets, including (1) single-family and small multifamily dwellings, (2) high-density multifamily dwellings, and (3) homes heated with fuel oil. Altogether, information is being collected from 48 states, 400 local WAP agencies, 800 utilities, and 15,000 homes. Some of the many innovations incorporated into these studies include the following:

- close involvement of stakeholder representatives in the evaluation;
- retention of homes where occupants have changed, in the savings analysis;
- split-winter design with metering to quantify energy savings in fuel-oil homes;
- application of a heating and cooling model for weather normalization;
- assessment of weatherization impacts on the health and safety of occupants; and
- estimation of indirect economic and environmental externality impacts. ♦

will be developed next year as the support office receives funding.

Field demonstration of the energy-saving benefits of energy controls retrofits in large commercial buildings is under development for a case-study building in Washington, D.C. The demonstration, expected to begin next year, will measure energy savings for different control functions and will indicate areas where possible DOE involvement in energy controls would be useful.

5.6 ENERGY PROGRAM PLANNING AND EVALUATION

The major research focus of the Energy Program Planning and Evaluation (EPPE) group continues to be quantitative assessments of energy-efficiency programs operated by utilities and government agencies. During FY 1991, the group continued assessment of the commercial impacts of DOE's Energy-Related Inventions Program (ERIP), evaluated two residential conservation programs operated by the Bonneville Power Administration, completed planning for a comprehensive evaluation of DOE's low-income WAP, and initiated each of the five studies that comprise the WAP evaluation.

Since 1984, ORNL has tracked the progress of inventors whose technologies have been ERIP-supported. The goal has been to assess program impacts on the commercialization of new energy technologies. During FY 1991, the EPPE group continued to compile information on the progress of ERIP inventions.^{23,24} Multiple progress indicators included (1) the commercialization rate of ERIP-supported technologies, (2) the time required to move a technology from the laboratory to the marketplace, (3) the number of years ERIP technologies experienced sales, (4) the number of jobs generated, and (5) the amount of funding raised. Comparing these indicators to private-sector, new product development statistics suggests that ERIP has been effective. ERIP-supported technologies have generated more than a half-billion dollars of sales; through 1990, 23 spin-off applications generated sales of \$32 million, representing only 6% of total program sales.

Over the past decade, the group has completed a series of evaluations of Bonneville Power Administration's residential weatheri-

zation programs, which examined the energy saved by participants and assessed the durability of savings up to 3 years after weatherization. During FY 1991, preliminary evaluations of the 1988 and 1989 programs were completed.²⁵ Altogether, these studies constitute an unprecedented analysis of the persistence and durability of energy savings, which decreased by only 8–10% each of the first 3 years after weatherization. For both the 1988 and 1989 programs, actual savings during the first post-weatherization year fell far short of the audit-estimated savings—55% and 36%, respectively. This is consistent with prior evaluations conducted for Bonneville and others.

Another major project completed during FY 1991 evaluated Bonneville's efforts to promote energy-efficient Model Conservation Standards (MCSs) for single-family home construction in the Pacific Northwest. Since 1988, the EPPE group has been collecting and evaluating information on two MCS programs: a marketing program administered by utilities (the Super Good Cents Program) and a code program administered by local governments (the Early Adopter Program). An analysis of electricity billing data indicates that homes participating in both programs saved 0.9 kWh/ft². On-site audit data show that construction characteristics have been significantly improved by both programs. Despite comparable rates of market penetration, the two programs have served markedly different market niches.²⁶

5.7 INTEGRATED RESOURCE PLANNING FOR ELECTRIC UTILITIES

Integrated Resource Planning (IRP) continues to be an important topic for utilities, state regulatory commissions, and the federal government. DOE's National Energy Strategy emphasized IRP and DOE's role in encouraging widespread use of this new and evolving planning approach.

ORNL's work in this area during FY 1991 continued to build on past projects and successes. For example, in FY 1990, the group assessed the methods that utilities use to integrate DSM options into overall resource planning. The basis for the project was a survey of 24 electric utilities, including site visits with five utilities. In early

FY 1991, the group published two reports on this project and immediately began new projects, building on the information learned from the site visits and surveys. The new projects (1) quantitatively examine the effects of different ways to analytically integrate DSM into an IRP on the amounts of DSM resources chosen, and (2) examine the methods utilities use to combine DSM technologies into programs. Key accomplishments during FY 1991 include the following projects:

- completion of a new planning model for electric utilities, Decision Impact Assessment Model (DIAMOND),²⁷ and application of the model to analyze the effects of utility DSM programs on electricity costs and prices;²⁸
- completion of two reports that examine the processes electric utilities use to integrate DSM programs into overall resource plans^{29,30} and initiation (and completion in early FY 1992) of an analysis of the effects of integrating method on the amount of DSM resources selected;³¹

Should DSM programs aim to minimize the total cost of providing electric-energy services, or should they minimize only the price of electricity?

- completion of an analysis and report that examines the potential benefits of ambitious electric-utility DSM programs during the next two decades;³²
- initiation (and completion in early FY 1992) of two handbooks, one on DSM-program terminology³³ and the other on evaluation of DSM programs;³⁴ and
- initiation (and completion in early FY 1992) of a project that reviews the activities and outcomes of nine DSM sites throughout the United States.³⁵

Use of the new DIAMOND model is a good example of the group's FY 1991 accomplish-

ments. More and more U.S. utilities are running larger DSM programs. Assessing the cost-effectiveness of these programs raises difficult questions for utilities and their regulators. Should these programs aim to minimize the total cost of providing electric-energy services, or should they minimize only the price of electricity?

Most of the debates about the appropriate economic tests for assessing utility programs are philosophical and do not address the real magnitude of the impacts. As a result, questions remain about the relationships among utility DSM programs and acquisition of supply resources and the effects of these choices on electricity prices and costs. This study³⁶ does not resolve these philosophical debates. Instead, it offers quantitative estimates on the tradeoffs between total costs and electricity prices. This study uses DIAMOND to assess the effects of energy-efficiency programs on utility revenues, total resource costs, electricity prices, and electricity consumption for the period 1990 to 2010. These DSM programs are then assessed under

alternative scenarios for three utilities: (1) a "base" that is typical of U.S. utilities; (2) a "surplus" utility that has excess capacity, few planned retirements, and slow growth in fossil-fuel prices and incomes; and (3) a "deficit" utility that has little excess capacity, many planned retirements, and rapid growth in fossil-fuel prices and incomes.

Figure 5.16 illustrates the key findings from these simulations:

- In general, DSM programs reduce electricity costs and raise electricity prices. Utilities and public utility commissions (PUCs) must make tradeoffs between the total resource cost (TRC) and the rate impact measure (RIM) tests.
- Typically, the percentage reduction in electricity cost far exceeds the percentage increase in electricity price caused by DSM programs. Roughly speaking, the ratio of percentage

ORNL-DWG 92-6199

Fig. 5.16. The effects of utility demand-side management (DSM) programs on the net present value of utility revenues and average electricity price (1990–2010) for the base, surplus, and deficit utilities. The utility pays 100% of costs of the DSM measures. The prices shown refer to the maximum cost of conserved electricity (in cent/kWh) paid by the utility in its programs.

changes is 2:1 for the surplus utility, 5:1 for the base utility, and 8:1 for the deficit utility.

- The financial outlay of DSM programs is important. Utilities absorbing costs of DSM programs raise electricity prices in the short term, whereas capitalizing these costs defers the price increase for several years.
- Even if DSM is very inexpensive or the utility avoids high costs, the problem of tradeoff between costs and prices remains. However, under either circumstance, the percentage reduction in costs will be far greater than the percentage increase in prices. In special cases where the cost per kWh of DSM programs is very low, both prices and costs can be reduced.
- After assessing costs from the TRC test, DSM programs are cost-effective even if the utility has excess capacity and slow load growth. This occurs because DSM programs not only offset the operating costs of existing power plants, but also reduce the other costs of operating the utility system, defer construction of new transmission and distribution facilities, and in the long term defer the construction and operation of new power plants.
- The cost tradeoff between the TRC and RIM tests can be addressed by having customers share in the costs of the DSM measures, by reducing the maximum cost of conserved energy paid by the utility, or by delaying program implementation. However, each of these approaches also reduces the amount of electricity savings achieved by the programs, increasing the need for additional power supplies.

In addition to in-house research, the section manages projects for the DOE Integrated Resource Planning Program. Currently, ERRS oversees projects conducted by the National Association of State Utility Consumer Advocates and the Energy Conservation Committee of the National Association of Regulatory Utility Commissioners. In August 1991, the section issued a request for proposals (RFP) on IRP; almost 300 people and organizations requested

the RFP package in October. Proposals were received in December and are now being reviewed to select the 6-10 that will be funded.

This work is funded primarily by DOE's IRP Program. Additional support comes from the Electric Power Research Institute and the New York State Energy Research and Development Authority. Much of the work is conducted in close cooperation with individual utilities and PUCs, and with the Energy Conservation Committee of the National Association of Regulatory Utility Commissioners. Finally, the section makes numerous presentations at

Most of the debates about the appropriate economic tests for assessing utility programs are philosophical and do not address the real magnitude of the impacts.

conferences, seminars, and workshops. As examples, staff members belong to a new committee of the Southern States Energy Board, gave talks at two workshops for utilities that are customers of the Western Area Power Administration, and testified before several state regulatory commissions and committees of the U.S. Congress.

5.8 TECHNOLOGY TRANSFER

The mission of the Technology Transfer Program is to implement a system for efficient and effective transfer of research and development results to private and public sector users. The program supports activities that will have a long-term positive impact on the design, construction, and maintenance of energy-efficient buildings.

A Summer Institute Workshop on Energy and Environmental Systems, conducted by the American Collegiate School of Architecture, was held at the University of Washington in July 1991. The workshop focused on topics related to the teaching of engineering subjects and promoted the integration of energy-efficient options into academic design courses. Forty participants representing 33 universities attended. Topics included passive solar design for residences; heating, cooling, and lighting design; factory-

built homes; high density housing; and daylighting.

Applied Management Sciences has prepared and disseminated four "technical briefs" (short, general interest data sheets prepared for media takeoff) on Low-E and Superwindows, Life Cycle Costing, Passive Solar Design Strategies, and Radiant Barriers in Attics.

The Technology Transfer Program is providing technical and logistical support to the DOE Southeast Regional Support Office for a regional workshop on delivery of energy-efficiency services. The workshop is scheduled for Spring 1992.

5.9 COMMUNITY ENERGY SYSTEMS

After almost 10 years, ORNL was given lead-laboratory responsibility by the DOE Office of Utility Technologies, Utility Systems Division, for the District Heating, Cooling, and Cogeneration (DHC/C) Program. The mission of this program is to develop and promote the adoption of cost-effective DHC/C technologies in conjunction with other DHC/C industry partners for the benefit of national energy and economic efficiency, energy security, and environmental quality.

The highlight of last year's program was the planning and execution of a DHC/C Workshop designed to formulate an action plan for the 1990s that will promote the application and growth of DHC/C in the United States. This workshop, attended by over 50 DHC/C industry leaders, addressed the following major issues:

- building a supportive policy and regulatory climate;
- using DHC/C's unique value to strengthen its competitive advantage;
- modernizing, expanding, and linking systems, users, and sources; and
- developing a strategic marketing plan.

Other program highlights include experimental research to investigate the effects of thermal cycling on the thermal-hydraulic performance of low-temperature phase-change material/water slurries being done in conjunction with Drexel University, and preparation and execution of an RFP (entitled *Cogeneration Designs for District Heating and Cooling Systems*) that will result in several grants being

issued to apply innovative cogeneration applications to existing DHC systems.

5.10 POWER SYSTEMS TECHNOLOGY

The objectives of the Power Systems Technology Program are to improve the reliability, efficiency, and security of the nation's electric power delivery system. Program activities are directed towards developing technology options for increased transmission and distribution capacity; integration of new technologies, including distributed energy resources; and development of enhanced control and operation strategies for future electric power systems. Management responsibilities include Electric and Magnetic Field Effects and Transmission and Distribution programs funded by the DOE-Office of Energy Management. Program staff members participate in the ORNL Superconductivity Program and also manage research projects for the Defense Nuclear Agency on EMP vulnerability and mitigation and for the Bonneville Power Administration on maintenance procedures.

5.10.1 Higher Capacity Transmission

The National Energy Strategy projects that electricity demand will nearly double by the year 2030, necessitating a concurrent growth in transmission capacity. The electricity delivery system is becoming increasingly more complex at the same time, because of growing interconnections, reduced reserve margins, and emerging competition from opening access of the transmission system to independent power producers. The need to provide access to renewable generating sources and the distributed nature of these types of generators will require capacity as well as sophisticated control and protection schemes.³⁷ Components of this research include real-time control technology, high-voltage dc transmission, and high phase-order transmission.

5.10.1.1 Real-time Control and Operation of Electric Power Systems

Real-time control and operation of the nation's electricity delivery system is of major

importance in order to use the full capacity of the delivery system and at the same time successfully maintain the performance of the electric power system.

The object of this initiative is to identify the technologies and procedures needed to achieve real-time control and operation, and to develop and test these in cooperation with industry and the utilities. Faster, more precise power system controls and capabilities to analyze data and state estimations will be needed to maintain system stability and security and to continue the accepted high reliability of the electricity supply. A workshop was held in Denver, Colorado, in November 1991, to identify the issues, research needs, and priorities of the research and time schedules. The DOE Power Marketing Administrations, Bonneville Power Administration (BPA), and Western Area Power Administration (WAPA) are key partners in this initiative.

An important ongoing component of real-time control is phasor measurements. A reduced-order load flow for power systems, termed the "generator axis load flow," has been formulated for use with synchronized phasor measurements.³⁸

Real-time phasors (a complex number of both magnitude and angle that represents the voltage or current sinusoidal wave form at a single frequency) can be accurately measured and synchronized at different substations of a power system by using satellite time transmissions [i.e., the 1 pulse per second output from the Global Positioning System (GPS) satellite]. A phase angle accuracy of 0.02 degrees can be achieved on a 60 Hz power system with GPS signals and phase-locked oscillators. The positive sequence voltages and currents in a power network are the key parameters for most monitoring and control. The generator axis load flow, essential for most dynamic studies of the power system, offers an efficient method for computing power flows, particularly where high speed simulations are needed for predicting system instability. The generator axis load flow is an equivalent of the system loads that have been analytically transferred to the generator terminals where phasor measurements are taken. Phasor measurement has advanced to the stage where several field installations are already in place at a number of electric utilities.

5.10.1.2 Higher Capacity Transmission Using HVDC

ORNL, in cooperation with BPA and WAPA, has determined that high-voltage direct current (HVDC) has a large potential to help meet projected transmission capacity increases for 2020. The object of the HVDC initiative is to reduce the cost of converting ac to HVDC by 40–50% so that HVDC can be economically applied to upgrade ac high-voltage transmission lines of 150 miles or longer. Today, HVDC can be the economical choice for lines longer than 300–600 miles because of high terminal costs.

An assessment of market potential is underway for upgrading transmission capacity using HVDC, and a workshop is being planned for Portland, Oregon in May 1992.

5.10.1.3 High Phase-Order Transmission

ORNL is the technical monitor for a demonstration project cofunded by DOE of high phase-order transmission. High phase-order transmission refers to the use of more than three phases to increase the power density (kW/ft²) of a transmission corridor. The electric and magnetic fields of a high phase-order transmission line are lower at the edge of the right-of-way than those of a comparable three-phase line.

Construction began in April 1991 on the high phase-order transmission line demonstration project at New York State Electric and Gas Company in Binghamton, New York. The project will convert an existing 1.5-mile double-circuit three-phase line operating at 115 kV line-to-line to a six-phase operating at 161 kV line-to-line and will analyze the performance. The \$11.6 million dollar project is being jointly funded by several organizations with the Empire State Electric Energy Research Corporation (ESEERCO), a New York State utility research and development organization, taking the lead as the funding coordinator. Other funding organizations are New York State Electric & Gas Corporation, New York Energy Research and Development Administration, the State of New York, Electric Power Research Institute, and DOE. A DOE grant to ESEERCO was completed in September 1991. The line is scheduled to be energized in March 1992 for two years of operation and testing.

5.10.2 Power Transients

The primary objective of this major research area is to assess the effects of power transients on the nation's electric power systems and to develop recommendations for increasing their reliability when subjected to transients. A major past effort has been the assessment of nuclear EMPs. Emphasis is currently placed on geomagnetic disturbance impacts on electric power systems, which includes monitoring the extent of disturbances and the correlation with magnetic field changes over large regions of the United States. Other transients that can impact electric power systems, such as lightning EMPs and steep-front surges from power system generated transients, are also investigated.

A major review of geomagnetic disturbance impacts on electric power systems was performed to determine the history and extent of this phenomenon.^{39,40} Geomagnetic storms can cause severe problems for electric power systems, especially those power systems in coastal regions and in northern areas with igneous rock geology. An example of a severe geomagnetic storm is shown in Fig. 5.17, which is a histogram of the events recorded in North America on March 13, 1989. This storm caused the entire electrical system in the Province of Quebec to shut down for almost 9 hours. Note that all events occurred with K greater than or equal to 6, which generally corresponds to fields of a few volts per kilometer. K is a rating factor ranging from 1 (lowest) to 10 (highest) to designate the severity of a geomagnetic storm. The largest number of events occur during changes from one K classification to another. The fast change in a geomagnetic field

results in larger electric fields and the associated geomagnetically induced currents in power transmission lines. An effort to install many magnetometers for recording magnetic field variation and its correlation with current flow in the neutral of power transformers is now being planned for DOE. Implementation of this project will start in 1992.

This research is important because of the increasing vulnerability of electric power systems to geomagnetic disturbances during the 1990s, due to the combination of equipment, design, and operating circumstances of modern-day power systems that employ long transmission lines operated near capacity limits.

A summary of the EMP research program was completed and published,⁴¹ which concludes that a nominal high-altitude EMP environment with a peak electric field of tens of kV/m followed by a magnetohydrodynamic EMP (MHD-EMP) of less than 20 V/km will likely disturb electric power systems by causing some isolated load and generation loss and limited equipment damage. Major power failures are not expected. Electric power system components have been found, in general, to be quite robust and resistant to high-altitude EMP (HEMP) induced stresses. In distribution systems, grounded or previously damaged insulators could flash over or puncture when subjected to HEMP surges. Protective relays could be rendered inoperative by blown fuses in the dc control circuits.

In addition, major power failures cannot be ruled out for one or more HEMP events that result in very strong MHD-EMPs, which could impact transmission systems by geomagnetically inducing quasi-dc currents in a manner similar to that of geomagnetic storms.^{42,43} A very strong MHD-EMP could also possibly affect distribution systems. An extended blackout is not anticipated from high-altitude nuclear bursts, since major components such as power transformers are not likely to be damaged by HEMP-induced surges. Nevertheless, chaotic conditions associated with HEMP events may result in restoration delays.

As part of the EMP program, analysis of data was completed from simultaneous measurements of electric fields and induced voltages on a 448-m overhead power line obtained during summer 1986 at NASA's Kennedy Space Center. The lightning strikes

Fig. 5.17. Events and K Intensity recorded in North America during the March 13, 1989, geomagnetic storm. Source: North American Electric Reliability Council.

were artificially initiated by firing rockets into cloud formations, causing lightning to strike the ground about 20 m from one end of the power line. Observed voltage amplitudes ranged from tens of kilovolts for oscillatory voltages to hundreds of kilovolts for impulsive voltages.⁴⁴ The voltages induced on an unenergized overhead power line by electric fields from close artificially initiated lightning can be characterized into two categories: (1) "oscillatory" waveforms—those in which multiple, similarly shaped, evenly spaced pulses with decaying amplitudes are observed (Fig. 5.18); and (2) "impulsive" waveforms—those dominated by a principal pulse with subsidiary oscillations of much smaller amplitude (Fig. 5.19).

5.10.3 Materials

A CRADA has been established to study the production and mitigation of disulphur decafluoride (S_2F_{10}), one of several toxic by-products formed by electrical discharges in the insulating gas sulphur hexafluoride (SF_6). The CRADA members are Martin Marietta Energy Systems, Inc., Ontario Hydro (OH), Canadian Electrical Association, EPRI, and NIST. Funding will be provided by DOE, EPRI, OH, Empire State Electric Energy Research Corporation, Canadian Electrical Association, Bonneville Power Administration, and Tennessee Valley Authority. The total funding level over 3 years will be \$1.8 million. The three laboratories performing the research as part of the CRADA are the ORNL-Health and Safety Research Division, NIST, and OH. The CRADA objectives are to develop detection techniques for S_2F_{10} down to 10 ppb; to review gas handling procedures, perform field sampling, and study mitigation techniques, if necessary; and to disseminate information and transfer relevant technology.

Fig. 5.18. Vertical electric field measured 500 m from artificially initiated lightning return stroke and oscillatory voltages at both ends of the test line.

The particular concerns for S_2F_{10} are its highly toxic nature, the Ceiling Limit Value being 10 ppb, and the fact that no established and accepted detection techniques are sensitive enough to reach this level. Because much SF_6 gas-insulated electric power equipment is already in service in North America, particularly circuit breakers, ensuring safe operation and maintenance of this equipment is an important issue for the utility industry.

5.10.4 Biological Effects from Electric and Magnetic Fields

In FY 1991, ORNL was given management and coordination responsibilities for a significant part of the DOE research on biological effects associated with electric and magnetic fields. This has included the placing and monitoring of several

Fig. 5.19. Vertical electric field measured 500 m from artificially initiated lightning return stroke and impulsive voltages at both ends of the test line.

subcontracts, site visits, coordination with EPRI, and participation in a DOE task force on establishing goals, objectives, and road maps for the DOE research, engineering, and outreach effort on electromagnetic fields. ORNL is working with DOE to define the appropriate role.

5.10.5 PST Work for Others

The Defense Nuclear Agency is sponsoring work on mitigation of MHD-EMP effects for commercial electric power. The purpose of this project is to investigate methods of mitigating effects from MHD-EMP-caused, geomagnetically induced currents in power lines on critical facilities. Solar geomagnetic storm effects have been used to gain insight and to validate models. The experiences of electric utilities with geomagnetic disturbances have been documented

and analyzed. It was determined that electric power systems can be affected by geomagnetic disturbances with fields as low as a few volts per kilometer. A special experiment on distribution transformers and a parametric study of the MHD-EMP currents on power lines have been performed.

5.10.6 Energy for Developing Countries

An integrated power sector efficiency analysis in Costa Rica has been completed for the U.S. Agency for International Development (AID). The overall objective of the work will be to produce an investment plan and research recommendations. ORNL conducted an assessment of power plant transmission and distribution losses, end-use energy efficiency, and opportunities for increased energy savings.

ORNL continues to provide program review and occasional technical assistance to U.S. AID on a National Rural Electric Cooperative Association (NRECA) study of rural electrification in Central America. Since June 1991, D. B. Waddle has been on a leave of absence to NRECA to help establish a field office and NRECA program in La Paz, Bolivia.

5.11 REFERENCES

1. Phillips, B. A., and R. C. DeVault, "Residential Absorption Heat Pump Using a Generator-Absorber Heat Exchange Cycle," *Proceedings of the 26th IECEC*, Boston, August 1991.
2. Berchowitz, D. M., and J. A. Shonder, "Estimated Size and Performance of a Natural Gas Fired Duplex Stirling for Domestic Refrigeration Applications," *Proceedings of the XVIIIth International*

- Congress of Refrigeration*, Montreal, August 10-17, 1991.
3. Braun, A. T., R. J. Fiskum, and M. S. Alam, "Braun Heat Pump Engine/Compressor and its Hermetic Rod Seal," *Proceedings of the 26th IECEC*, Vol. 2, Boston, August 1991.
4. Sand, J. R., C. K. Rice, and E. A. Vineyard, *Alternative Refrigerants and Refrigeration Cycles for Domestic Refrigeration Project* (to be published).
5. Vineyard, E. A., "The Alternative Refrigerant Dilemma for Refrigerator-Freezers: Truth or Consequences," *ASHRAE Transactions* 1991 97, Pt 2.
6. Conklin, J. C., and E. A. Vineyard, "Heat Exchanger Thermal Performance for Two Nonazeotropic Refrigerant Mixtures," *Proceedings of XVIIIth International Congress of Refrigeration*, August 1991.
7. Sand, J. R., S. K. Fischer, and P. A. Joyner, "Modeled Performance of Non-Chlorinated Substitutes for CFC-11 and CFC-12 in Centrifugal Chillers," *Proceedings of International CFC and Halon Alternatives Conference*, December 1991.
8. Fischer, S. K., P. J. Hughes, P. D. Fairchild, et al., "Energy and Global Warming Impacts of CFC Alternative Technologies," (to be published).
9. Vineyard, E. A., et al., "Domestic Refrigeration," *UNEP Refrigeration, AC, Heat Pump Technical Options Report*, Chapter 3, L. Kuijpers, ed. (to be published in 1992).
10. Wilkes, K. E., R. L. Wendt, A. Delmas, and P. W. Childs, "Thermal Performance of One Loose-Fill Fiberglass Attic Insulation," *Insulation Materials: Testing and Applications*, 2nd Volume, ASTM STP 1116, Philadelphia, 1991.
11. Christian, J. E., "Technics: Under Steep Roofing," *Progressive Architecture*, May 1991.
12. Christian, J. E., G. E. Courville, et al., "The Technical Viability of Alternative Blowing Agents in Polyisocyanurate Roof Insulation: Part 4 In-Situ Thermal Aging and Performance in Different Roof Systems," *Proceedings, 33rd Annual Polyurethane Conference*, Orlando, Fla., September 30-October 3, 1990.
13. Christian, J. E., "Roof Insulation and CFCs: The Search for Alternative Blowing Agents," *The Construction Specifier* 43(11), November 1990.
14. Christian, J. E., G. E. Courville, R. S. Graves, et al., "Thermal Measurement of In-Situ and Thin-Specimen Aging of Experimental Polyisocyanurate Roof Insulation Foamed with Alternative Blowing Agents," *Insulation Materials: Testing and Applications*, Vol. 1, ASTM STP 1116, American Society for Testing and Materials, Philadelphia, October 10-11.
15. Graves, R. S., J. E. Christian, and D. L. McElroy, "Joint Industry/Government Research Project—Comparison of Thermal Aging for Roof Exposures and Thin-Specimens of Experimental Polyisocyanurate Insulation Foamed with Alternative Blowing Agents," *Proceedings, Polyurethanes World Congress 1991*, Nice, France, September 24-26, 1991.
16. Courville, G. E., J. E. Christian, et al., "Thermal Properties of Polyisocyanurate Foam Board Insulation Blown with CFC-11 Substitutes," *Third International Symposium on Roofing Technology*, Montreal, April 17-19, 1991.
17. Smith, T. L., J. E. Christian, et al., "Mechanical Properties Evaluation of Polyisocyanurate Roof Insulation Blown with CFC-11 Substitutes," *Third International Symposium on Roofing Technology*, Montreal, April 17-19.
18. Carmody, J., J. Christian, and K. Labs, *Builder's Foundation Handbook*, ORNL/CON-295, Oak Ridge National Laboratory, May 1991.
19. Christian, J. E., "Energy Efficient Residential Building Foundations Enhance Indoor Air Quality," *ASHRAE Journal* 33(11), November 1991.
20. Lstiburek, J., and J. Carmody, *Moisture Control Handbook—New, Low-Rise Residential Construction*, ORNL/Sub/89-SD350/1, Oak Ridge National Laboratory, October 1991.
21. Beschen, D. A., and M. A. Brown, *Evaluation Plan for the Weatherization Assistance Program*, ORNL/TM-11668/V1, Oak Ridge National Laboratory, August 1991.

22. Berry, L. G., M. A. Brown, T. Wright, and D. L. White, *Experimental Plan for the Single-Family Study*, ORNL/TM-11668/V3, Oak Ridge National Laboratory, August 1991.
23. Brown, M. A., C. R. Wilson, and C. A. Franchuk, *The Energy-Related Inventions Program: Decade of Commercial Progress*, ORNL/CON-339, Oak Ridge National Laboratory, December 1991.
24. Brown, M. A., and C. R. Wilson (1991), "Government Promotion of Energy Innovations: An Evaluation of the Energy-Related Inventions Program" (forthcoming in *Policy Studies Journal*).
25. Brown, M. A., and D. L. White (1992), *Electricity Savings in Bonneville's 1988 and 1989 Residential Weatherization Program*, ORNL/CON-323, Oak Ridge National Laboratory (forthcoming).
26. Brown, M. A., J. O. Kolb, D. Baylon, M. H. Haeri, and D. L. White, *The Impact of Bonneville's Model Conservation Standards on the Energy Efficiency of New Home Construction*, ORNL/CON-310, Oak Ridge National Laboratory, August 1991.
27. Gettings, M., E. Hirst, and E. Yourstone, *DIAMOND: A Model of Incremental Decision Making for Resource Acquisition by Electric Utilities*, ORNL/CON-315, Oak Ridge National Laboratory, February 1991.
28. Hirst, E., *The Effects of Utility DSM Programs on Electricity Costs and Prices*, ORNL/CON-340, Oak Ridge National Laboratory, November 1991.
29. Hill, L. J., E. Hirst, and M. Schweitzer, *Integrating Demand-Side Management Programs into the Resource Plans of U.S. Electric Utilities*, ORNL/CON-311, Oak Ridge National Laboratory, January 1991.
30. Schweitzer, M., E. Hirst, and L. J. Hill, *Demand-Side Management and Integrated Resource Planning: Findings from a Survey of 24 Electric Utilities*, ORNL/CON-314, Oak Ridge National Laboratory, February 1991.
31. Hill, L. J., *Comparison of Methods to Integrate DSM and Supply Resources in Electric Utility Planning*, ORNL/CON-341, Oak Ridge National Laboratory, December 1991.
32. Hirst, E., *Possible Effects of Electric-Utility DSM Programs, 1990 to 2010*, ORNL/CON-312, Oak Ridge National Laboratory, January 1991.
33. Hirst, E., and C. Sabo, *Electric-Utility DSM-Programs: Terminology and Reporting Formats*, ORNL/CON-337, Oak Ridge National Laboratory, October 1991.
34. Hirst, E., and J. Reed (eds.), *Handbook on Evaluation of Utility DSM Programs*, ORNL/CON-336, Oak Ridge National Laboratory, December 1991.
35. Raab, J. D., and M. Schweitzer, *Public Involvement in Integrated Resource Planning: A Study of Demand-Side Management Collaborative*, ORNL/CON-344, draft, Oak Ridge National Laboratory, November 1991.
36. Hirst, E., ref. 27.
37. Dale, S. J., J. P. Stovall, and K. W. Klein, *Maintaining Electric Power System Performance: Preparing for the Year 2000, Research Needs*, ORNL-6678, Oak Ridge National Laboratory, 24 pages (in publication).
38. Phadke, A. G., J. S. Thorp, and L. Mili, *Adaptive Dynamic Control with Phasor Measurements*, ORNL/Sub/SC203C/1, Oak Ridge National Laboratory (to be published).
39. Barnes, P. R., et al., *Electric Utility Industry Experience with Geomagnetic Disturbances*, ORNL-6665, Oak Ridge National Laboratory, September 1991.
40. Barnes, P. R., and J. W. Van Dyke, "Potential Economic Costs from Geomagnetic Storms," IEEE Special Panel Session Report 90TH0357-4-PWR, *Geomagnetic Storm Cycle 22: Power System Problems on the Horizon*, pp. 80-83, July 17, 1990.
41. Barnes, P. R., *EMP Research on Electric Power Systems—Program Update*, ORNL/M-1392, Oak Ridge National Laboratory, May 1991.
42. McConnell, B. W., et al., *An Experiment to Determine the Impact of Quasi-DC*

Currents on Three-Phase Distribution Transformer Installations—Results and Observations, ORNL/Sub/89-SE912/1, Oak Ridge National Laboratory (to be published).

43. Barnes, P. R., F. M. Tesche, and A. P. Meliopoulos, *MHD-EMP Interaction with Power Transmission and Distribution Systems*, ORNL/Sub/90-SG828/1, Oak Ridge National Laboratory (to be published).

44. Rubenstein, M., M. A. Uman, E. M. Thomson, and P. U. Medelius, "Characterization of Vertical Electric Fields and Associated Voltages Induced on an Overhead Power Line from Close Artificially Initiated Lightning," *Proceedings of the 1991 International Conference on Lightning and Static Electricity*, Cocoa Beach, Fla., April 16-19, 1991.

Planning

and Coordination

ORNL-Photo 1501-92

Tom Wilbanks, Senior Planner

6. PLANNING AND COORDINATION OVERVIEW

6.1 INTRODUCTION

In fiscal year (FY) 1991, Planning and Coordination activities continued to focus on Oak Ridge National Laboratory's (ORNL's) developing country programs. In addition, Planning and Coordination provided its customary support for the Energy Division's planning and program development functions and took a role in the science-related educational reform process in the United States, as part of ORNL's growing commitment to science education.

6.2 DEVELOPING COUNTRY PROGRAMS

During FY 1991, the developing country programs of the Energy Division became the heart of a larger laboratory-wide effort to actively participate in energy and environmental research and development (R&D) for developing countries (including Eastern and Central Europe). An ad hoc Committee on ORNL Programs Related to Developing Countries and Eastern Europe was formed in May 1991 by Associate Directors Bill Fulkerson and Dave Reichle to promote the broader involvement of ORNL staff in project development and execution, with the Energy Division providing the committee's secretariat. In June 1991, Tom Wilbanks made an invited presentation in ORNL's Showcase Series on "ORNL's Role in Meeting the Energy and Environmental Needs of Developing Countries."

Meanwhile, the division's major activities were in energy strategy development, energy efficiency improvement, environmental management, renewable and rural energy systems, energy R&D applications, and institution-building and technology transfer.

6.2.1 Energy Strategy Development

As indicated in last year's *Annual Progress Report*, T. J. Wilbanks represented the United States in the Advisory Group on Energy and Electricity Supply and Demand for the Senior Expert Symposium on Electricity and the

Environment (held May 13-17, 1991), organized by 11 international agencies as the principal energy-focused preliminary to the 1992 United Nations Conference on the Environment and Development. The conclusions of this group, composed of representatives from eight countries and three multinational organizations, are summarized in Sect. 6.3.1.¹ ORNL also prepared background papers for the symposium on the outlook for electricity efficiency improvements in the United States and developing countries.^{2,3}

The program also produced an invited paper on energy policy responses to global climate-change concerns emphasizing potentials for improving energy efficiency, uses of natural gas and renewable energy sources, and the importance of environmental institution-building.⁴ In addition, continuing an ORNL role initiated by Bill Fulkerson, the program participated in United States-Japan discussions of "Cooperative Leadership for Environmental Protection and Economic Development," which resulted in a policy paper by the Atlantic Council.

6.2.2 Energy Efficiency Improvement

Throughout FY 1991, the program maintained its emphasis on energy efficiency improvement. As a part of ORNL's support for the Global Energy Efficiency Initiative (GEEI),⁵ the Energy Division developed and coordinated a number of proposals to be included in the GEEI project portfolio, took the lead in preparing a GEEI training strategy for developing countries and Eastern Europe, and designed a technical report and brochure for the U.S. Working Group for Global Energy Efficiency. The program also prepared two reports on potential energy efficiency improvements in the developing world,^{2,6} participated in the preparation of an issue paper by the Energy Efficiency Committee of the U.S. Energy Association (a member of the World Energy Council), and was actively involved in discussions with the U.S. Department of Energy's (DOE's) Office of Conservation about program directions for developing countries.

6.2.3 Environmental Management

The main emphasis during FY 1991 involved upgrading linkages with technical strengths across ORNL, especially in the Environmental Sciences and Health and Safety Research divisions. Three major projects were underway during FY 1991:

(1) Biosphere preservation in Guatemala. Energy Division staff member Keith Kline, on long-term assignment as environmental advisor to the U.S. Agency for International Development's (AID's) mission in Guatemala, was leading a multiyear effort to establish a biosphere preserve in the Petén region that will be the first such preserve in Central America (see highlight, "The Mayarema Biosphere Preserve Project").

(2) Health impacts of coal briquette use in Pakistan. As part of half a decade of work by the Energy Division on developing coal briquettes as an energy option for wood-scarce developing countries with domestic coal resources, ORNL compared emissions from Pakistani coal briquettes with emissions from other local household fuels and assisted the Fuel Research Center at Pakistan's Center for Scientific and

Industrial Research in conducting similar tests. This mentoring activity, led by Richard Gammage of the Health and Safety Research Division, is an example of promoting sister-laboratory institution-building in areas of ORNL technical strength.

(3) Environmental management in the electric power sector in Indonesia. On leave of absence from ORNL, Energy Division staff member Carl Petrich leads a large project sponsored by World Bank for improving environmental management capabilities and practices supporting electric power production in Indonesia. With DOE approval, other ORNL staff members are providing additional support as well, also taking vacation time or leave of absence. While not an ORNL project as such, this individual support builds the Laboratory's base of field experience and adds knowledge of energy and environmental problems and prospects in a key developing country.

(text continues on page 6-4)

Planning and Coordination continues to focus on developing country programs. (Left to right: Eddie Vineyard, Stephanie Floyd, Tom Wilbanks, John Shonder, Sherry Wright, and Bob Conrad.)

THE MAYAREMA BIOSPHERE PRESERVE PROJECT

Under a project jointly funded by the U.S. Agency for International Development (AID), the Government of Guatemala, and several international nongovernment organizations, Energy Division's Keith Kline continues to provide leadership in the establishment of the Maya Biosphere Preserve in the Petén region of northern Guatemala (see Fig. 6.1). This project seeks to improve the long-term economic outlook of Guatemala's population through the rational management of their renewable natural resources. It also attempts to curb current destructive agricultural practices in the Preserve area and protect against degradation of the area's resource base by promoting more sustainable opportunities for economic development.

Comprising nearly one-third of the country—and the largest area of rain forest in Central America—the Petén region has seen a tenfold increase in its population in the last 30 years. Over the same interval, land area cleared for agricultural production has increased fiftyfold. Current slash-and-burn agricultural practice places the rate of deforestation at approximately 40,000 hectares per year. In addition, rapid depletion of nutrient soil reserves is forcing additional clearing in order to sustain agricultural production. Observers predict that if action is not taken

immediately to promote rational management, degradation of the region's rich natural resources will continue to accelerate, and primary forests will disappear within thirty years.

Working closely with the local U.S. AID mission and the Guatemalan environmental protection agency, Kline focuses primarily on strengthening public and private institutions in Guatemala to enable them to enforce the legal protection of the Biosphere resource before these widespread destructive practices cause further damage. ♦

ORNL-DWG 92M-6561R

Fig. 6.1. Location of the Maya Biosphere Preserve in the Petén region of northern Guatemala.

INNOVATIVE USES OF BIOMASS ENERGY IN CHINA

Meeting the growing needs for energy services among China's 1.1 billion population without dramatically increasing coal use is one of the highest priorities for balancing international development and environmental management concerns. China's energy-supply alternative to coal that has received the least systematic attention is biomass production and conversion. Two very recent developments indicate the potential for this option in China. First, at the suggestion of Milton Russell of the Oak Ridge National Laboratory, a team conducted a 1990 feasibility study of the utilization of short-rotation, plantation-grown trees for electricity production in Yunnan Province, supported by the U.S. Department of Energy's CORECT program. Based on that study, the Chinese have decided to pursue a major biomass electricity program in this region. Within the past year, two sites have been identified for biomass plantations, and Chinese investment funds have been allocated. The only long-term need for foreign involvement is relatively low-level technical assistance—a sizeable payoff indeed from a small feasibility study. Second, a high official of the Chinese government has approached Russell about technical cooperation related to energy technologies for farmers and rural villages. For example, the Shandong Provincial Energy Research Institute has developed a biomass gasifier for use in rural villages, to be fueled by farm residuals. The Shandong design appears promising, both for Chinese development and for reducing the growing use of fossil fuels in rural areas for heating and cooking. Its success, however, is likely to depend on problem solving in such areas as reducing a high carbon monoxide content in the product gas and improving gas cleanup. Again, relatively inexpensive technical cooperation is likely to pay off handsomely. ♦

6.2.4 Renewable and Rural Energy Systems

Major accomplishments in this subject area during the year included the following projects:

- Biomass energy development in China. An initiative for biomass electricity production, begun in 1990 at the suggestion of Milton Russell, bore fruit more rapidly than expected, and a second opportunity for technical cooperation in rural technologies was identified as well (see highlight, "Innovative Uses of Biomass Energy in China").
- Rural electrification in Central America. ORNL continued its role as technical monitor and evaluator of a \$12 million rural electrification project in Central America being conducted by the U.S. National Rural Electric Cooperative Association (NRECA) for the Regional Office for Central American Programs. The Energy Division was active during the year in shaping the project's directions for FY 1992 and beyond, and it began preparations for the 1994 end-of-project evaluation.
- Renewable energy applications in rural Mexico. Supported by AID, ORNL collaborated with Oak Ridge Associated Universities and Sandia National Laboratory in developing a major new DOE-AID project to explore potentials for photovoltaic energy, windpower, and other renewable technologies to meet energy needs in Mexico's rural villages.

In addition, the Energy Division's Dan Waddle took a two-year leave of absence to lead a major rural electrification project in Bolivia, conducted by NRECA under the auspices of AID.

6.2.5 Energy R&D Applications

Continuing its leadership in exploring potentials for energy R&D and its contribution to the needs of developing countries, ORNL organized a major workshop in November 1990 on energy R&D for developing countries,

cosponsored by the University of Tennessee. Involving about 30 experts from the U.S. government, national laboratories, universities, other R&D centers, and developing countries, the workshop came to a consensus on a number of key issues.

As with any issue related to economic and social progress in developing countries, a consideration of energy R&D for low- and middle-income countries must start from an understanding of local development needs. After all, the fundamental objective of energy R&D is to promote improvements in economic productivity and quality of life by making better energy options available for specific local conditions—"better" meaning better able to deliver such improvements.

Turning this aim into a global energy R&D strategy, however, is complicated by the great diversity of development situations from region to region and country to country, leading in turn to inevitable uncertainties about energy markets, technology performance, institutional roles, and political will. Clearly, not everything that would be good for local development can be done. Energy R&D is only one of many development tools, and it is not always the easiest to implement.

Workshop participants identified several important priorities for energy technology improvement. Energy efficiency improvement is especially salient, because it directly addresses critical development problems such as capital shortages and environmental impacts. Other environmentally sound energy technology options are needed as well. The transportation sector deserves more attention than it has received, and other pressing development issues (e.g., urban poverty) would also benefit from innovative energy R&D. The most widespread need is simply to reduce the social cost of energy services to consumers in developing countries, keeping economic costs low without sacrificing environment, health, or safety.

These priorities grow out of a consensus that energy R&D for developing countries should be viewed very broadly. The R&D challenge can be viewed as (1) increasing the rate of change at the technology frontier and (2) reducing the gap between technology use in most developing countries and that frontier. If R&D is expanded to RD₁D₂&I (research, development, demonstration, and implementation), the former focuses on RD₁, while the latter focuses on D₂I.

The consensus of the workshop participants was that the current emphasis should be placed on D₂I, reflecting a feeling that, in general, developing countries' needs cannot wait for long-term solutions. Most developing countries are operating well within the technology frontier; combined with the urgency of their needs, this calls for a strong international effort to get promising technologies demonstrated, adapted where appropriate, and moved into use.

This does not mean, however, that no RD₁ is called for. Improvements in energy technologies that respond to growing concerns about global environmental change and regional environmental degradation are still needed, as are cost-reducing innovations for developing country conditions. These requirements include fossil energy supply sources as well as efficiency improvements and renewables. In addition, R&D addressing the process of implementing innovations (e.g., price reform) is a critical need throughout many parts of the developing world.

To be effectively targeted and implemented, development requires direct participation by professionals from the developing countries themselves.

The frequent need for price and energy policy reform is, in fact, part of a broader set of issues affecting energy R&D strategies for developing countries. In many cases, institutional issues lie at the heart of relating energy R&D to development needs. Institutional performance, institutional roles, and linkages are frequently where attention is most needed. For example, financing is a prerequisite for energy sector innovation; endogenous capacities in developing countries to participate actively in the RD₁D₂&I process are essential for both effectiveness and equity; and the integration of nongovernmental institutions into the process—especially local market forces—is a key to sustaining progress.

In any event, RD₁D₂&I for developing countries should be conducted *with* developing countries. To be effectively targeted and implemented, development requires direct participation by professionals from the developing countries themselves.

Besides the November workshop, the division also participated in a June 1991 conference on Technologies for a Greenhouse Constrained Society, organized by ORNL with DOE support. Mike Kuliasha assisted Laboratory Assistant Director Alex Zucker in conference coordination, and Tom Wilbanks presented an invited paper.⁶

One of the program's strongest interests is establishing long-term relationships with counterpart institutions in key developing countries and regions.

6.2.6 Institution-Building and Technology Transfer

During FY 1991, the Energy Division expanded its commitment to institution-building in developing countries, with particular reference to technology transfer. For example, activities included the following:

- As one contribution to the workshop, a paper was prepared on "Institutional Issues in Energy R&D Strategies for Developing Countries."⁷ At the invitation of one of the participants, a related paper was prepared on institutional issues in improving capabilities in developing countries for technology assessment,⁸ as part of a book by the U.N. Centre for Science and Technology for Development.
- One of the program's strongest interests is in establishing long-term relationships with counterpart institutions in key developing countries and regions. Besides the interactions with China already mentioned, the workshop strengthened ORNL's relationships with the Latin American Organization for Energy and Development and the Asian and Pacific Development Centre (APDC); in addition, ORNL contributed a chapter

on "Energy Technology Systems and Their Impacts" to an APDC handbook on "Rapid Environmental Assessment." The program also began working with the Tata Energy Research Institute, in New Delhi, India, on possible R&D collaborations in such areas as chlorfluorocarbon (CFC) emission-reducing refrigeration technologies.

Further, the program played an active role in the initiation of a new Atlantic Council Working Group on Energy Technology Transfer for Sustainable Economic Development. Anticipating that the 1992 U.N. Conference on Environment and Development will lead to international agreements to accelerate North to South technology transfer, this group is endeavoring to identify the major constraints on such transfers in both industrial and developing countries. The Energy Division also began an effort to develop an inventory of U.S. technology cooperation related to global change, led by Ed Hillsman, supported by DOE's Office of Policy Analysis, and coordinated with activities of the U.S. State Department.

6.3 OTHER ACTIVITIES

During FY 1991, President Bush's new education strategy for the United States, *America 2000*, was implemented. Among other things, this strategy calls for establishing world-class standards in five core subjects—English, mathematics, science, history, and geography—and developing a system of voluntary national examinations for fourth, eighth, and twelfth grade students in these five subjects. Toward these ends, the National Assessment of Educational Progress (NAEP) began preparing for an assessment of knowledge and skills in geography in 1994, and the National Council on Education Standards and Testing (NCEST) prepared to report to the U.S. Congress on the issue of national standard-setting for the five subjects.

Besides its roles in the areas of science and mathematics, ORNL was centrally involved in these foundation activities for geography as a core subject as well, as a nationally recognized center

for geographic research. T. J. Wilbanks served on the 19-member Geography Consensus Planning Committee for the NAEP assessment and also served on the Geography Task Force for the NCEST report.

6.3.1 SUMMARY OF ISSUES REGARDING GLOBAL ELECTRICITY SUPPLY AND DEMAND

The following is a summary of conclusions resulting from the May 1991 Advisory Group on Energy and Electricity Supply and Demand for the Senior Expert Symposium on Electricity and the Environment.

6.3.1.1 Reconciling Development Needs with Environmental Impacts

The global demand for electricity services will continue to increase, subject only to constraints on economic growth. Electricity services are essential to the quality of life to which most of the world's people aspire. As incomes rise, especially in developing countries where electricity is only beginning to penetrate potential markets, substantially more services will be demanded than are currently provided.

The electricity sector can make significant contributions towards a reduction in future environmental impacts. Efficiency improvements, demand-side management, and the use of non-fossil fuel supply-side alternatives are available options towards a substantial reduction in emissions. Moreover, increased electricity use may lead to a reduction in emissions from the energy system by permitting substitution of cleaner generation sources for directly burnt fossil fuels.

The most stringent global impact reduction targets cannot be met by the electric power sector without curtailing electricity services significantly. Total CO₂ emissions within the electric power sector worldwide cannot be reduced dramatically without socially and economically unacceptable curtailments in electricity services in many countries. The most ambitious feasible global target for carbon emissions from total energy sources in the year 2010 would involve emissions above those

released in 1990. Such a target would still require vigorous intervention and carry substantial political and economic costs, including commitments by higher income countries to much greater reductions in emissions than in lower income countries.

Less stringent global impact reduction targets can be met by the electric power sector without curtailing electricity services significantly, but only with forceful policy intervention. Such targets can be met through a combination of widespread efficiency improvement, institutional and policy changes, and increased use of non-fossil and lower impact fossil electricity supply options, including nuclear energy, to displace large-scale coal use.

Substantial progress in impact reduction will require sustained attention to capital investment and institutional development needs in the electric power sector. To realize the potentials for health and environmental impact reduction, new capital investment will be required, as will effective implementation by institutions operating within their own national policy. Capital investment will be especially critical for progress in the former Soviet Union, Eastern Europe, and developing countries. Institutional steps—including price reform and regulatory changes to treat demand-side options equitably—will be important throughout the world.

Capital investment will be especially critical for progress in the former Soviet Union, Eastern Europe, and developing countries.

6.3.1.2 Potentials and Limits of Alternative Paths

Any evaluation of alternative paths for electricity system development is pervaded by uncertainty and diversity. When long-term economic, political, and energy conditions cannot be forecast with confidence, when countries and regions differ from each other dramatically in resources and needs, and when the range of electricity system options is apparently so extensive, it is difficult to get decision makers to take firm actions. The challenge is to incorporate these complexities into strategy development

without resulting in inaction. In the meantime, institutional inertia, uncertainty, and diversity complicate any global effort to reduce environmental impacts associated with the provision of electricity services.

Efficiency improvement throughout electric power systems, from generation to end use, has a substantial potential to reduce impacts and should be pursued vigorously. Throughout the world, there is a greater realistic potential to reduce emissions and other impacts through efficiency improvement rather than through supply side fuel substitution, at least over the next several decades. In most countries, a great deal can be accomplished relatively quickly on the supply side at relatively low costs, even without significant policy interventions. Improvements in end-use efficiencies would be possible only with significant policy interventions and would materialize only in the medium and long term. Within an impressive domain of specific alternatives, efficiency improvements can be considered a virtual "no regrets" option.

Efficiency improvement alone, however, will not realize the full potential for impact reduction; supply-side alternatives to fossil fuels should also be emphasized wherever they can contribute towards economic growth and environmental management. It is illusory to think that efficiency improvements will prevent the need for investments in electricity supply facilities. To realize the entire potential for impact reduction, every part of the electricity system must play a part. Besides efficiency improvements, other alternatives include supply options that emit little or no greenhouse gases.

Coal will represent powerful competition with alternative energy sources in many countries. Coal is an abundant, relatively inexpensive and familiar option for electricity generation. Many of its environmental impacts can be limited by increased use of the coal conversion and environmental control technologies already available. However, *carbon* emissions from coal conversion cannot be limited, other than by efficiency improvements that enable more services to be delivered per unit of coal consumed. Coal will not easily be displaced, and in developing countries such as China and India, its use will grow substantially in the coming decades. This reality puts additional pressure on other emission reduction potentials in other regions.

Oil will continue to be used for electricity generation where it is competitive and where other energy sources are not readily available. However, the priority use of oil products for transportation fuels and petrochemicals will provide further stresses on resources, hence the total contribution of oil to global electricity generation will decrease.

Natural gas will play an important role in impact reduction, especially in Europe and North America, but the magnitude of its availability is uncertain. Natural gas is a relatively inexpensive and clean option for those countries that have access to it, and it will receive particular attention as an alternative to coal for electricity generation. The critical constraint to a greater use of gas will be the limits in its resource availability.

Nuclear energy has the potential to make a significant contribution towards a reduction in carbon emissions, but its social acceptability remains in question. Technologies and resources are available to support greatly expanded use of nuclear energy in higher and middle income countries. However, public concerns about health, safety risks, and waste disposal have currently blocked nuclear energy as an option for new power generation in many countries. Its outlook depends mainly on social attitudes, which may be influenced by technological and policy responses to social and climatic concerns.

Hydroelectric energy could play an important role globally because of its large resource potential in developing countries and its freedom from carbon emissions. Hydro energy is a clean and familiar power option that continues to be attractive in many countries, both developing and industrialized, particularly because of the large economic resource base still unharnessed. However, the financial constraints faced by many countries, and also environmental impacts (such as land-use requirements, risk of accidents, and possible local climate changes), may limit its development.

Other renewable energy sources are increasingly contributing towards electricity generation but are unlikely to meet a large share of the global electricity demand. Options such as solar, wind, geothermal, and biomass energy are showing some success worldwide, and their prospects will improve over the next few decades. While these renewable sources are an

essential part of any impact reduction strategy, their contribution will only grow as their economics improve. Therefore, their overall contribution towards global electricity generation is likely to remain small.

6.3.1.3 Different Regional Roles and Realities

Appropriate and effective strategies for impact reduction will be region-, country-, and location-specific. Because countries and regions differ so markedly in energy and economic conditions, institutional settings, priorities, and preferences, detailed strategies for impact reduction cannot be introduced usefully at a global level. They will emerge from local decision-making processes that respond in part to global concerns and resource allocations.

OECD countries have a special responsibility for pioneering alternative strategies. Their expertise, experience, and financial resources place OECD countries in a particularly favorable position to pursue impact-reducing alternatives, thereby minimizing uncertainties in their costs and benefits.

The former Soviet Union and Eastern Europe face major uncertainties about paths for economic growth and institutional change, but they have a substantial potential to contribute towards impact reduction through energy-efficiency improvement if financial and other resources are available. This region is unique in the near-term uncertainties it faces. Its potential for energy-efficiency improvement, however, represents one of the most significant opportunities for impact reduction worldwide, provided capital investment and other resources can be invested to realize this potential.

Developing countries, particularly those in the lower income group, are fundamentally different from higher income countries in their needs and options. Although they can indeed contribute to global impact reduction, their first priority will be economic and social development. If the gap between higher and lower income countries is to be reduced, developing countries will need not only substantially more electricity services in the years to come, but also more efficient electricity supply facilities. Meanwhile, they face severe constraints on capital supply and institutional capabilities, which affect both electric power sector strategies and the more

general development process. Strategies related to electricity supply and demand will have to be developed and pursued as an integral part of this process.

Most developing countries will have to increase carbon emissions and other environmental impacts in order to power their economic and social development. This means that other regions will have to adopt more stringent targets to approach global impact reduction goals.

Effective international cooperation will be needed to realize the potentials for impact reduction. Just as environmental concerns have become globalized over the past several decades, so have many elements of the impact reduction strategies. The pace and ultimate magnitude of impact reduction will depend heavily on the effectiveness of international partnerships—treated not as North to South "assistance" but as true international collaboration—to facilitate adaptation and transfer of technologies, access to financial resources, and cooperation in institutional development.

6.4 REFERENCES

1. "Energy and Electricity Supply and Demand: Implications for the Global Environment," in *Electricity and the Environment*, Senior Expert Symposium, Helsinki (IAEA-STI/PUB/877) Vienna: International Atomic Energy Agency, 1991.
2. T. J. Wilbanks, "The Outlook for Electricity Efficiency Improvements in Developing Countries," in *Electricity and the Environment*, Senior Expert Symposium, Helsinki (IAEA-TECDOC-624) Vienna: International Atomic Energy Agency, 1991: 121-145.
3. T. J. Wilbanks, "The Outlook for Electricity Efficiency Improvements in the United States," in *Electricity and the Environment*, Senior Expert Symposium, Helsinki (IAEA-TECDOC-624) Vienna: International Atomic Energy Agency, 1991: 147-160.
4. T. J. Wilbanks, "Energy Policy Responses to Concerns about Global Climate Change," in S. Majumdar and others, eds., *Global Climate Change: Implications, Challenges and Mitigation Measures*, Easton, Pa:

- Pennsylvania Academy of Sciences, forthcoming.
5. T. J. Wilbanks, "Planning and Coordination," in *Energy Division Annual Progress Report: 1990*, Oak Ridge National Laboratory, 1991, pp. 6-1- 6-6.
 6. T. J. Wilbanks, "The Case for Energy Efficiency Improvement as a Global Strategy," in A. Zucker and M. Kuliasha, eds., *Technologies for a Greenhouse-Constrained Society*, forthcoming.
 7. T. J. Wilbanks, "Institutional Issues in Energy R&D Strategies for Developing Countries," *Forum for Applied Research and Public Policy*, forthcoming.
 8. T. J. Wilbanks, "Institutional Issues in Capacity-Building for Energy Technology Assessment," in *Energy Systems, Environment and Development*, United Nations Centre for Science and Technology for Development, forthcoming.

Abstracts

of Publications

7. ABSTRACTS OF PUBLICATIONS

7.1 ABSTRACTS OF INTEGRATED ANALYSIS AND ASSESSMENT SECTION

[7.1.1] Implementation Plan for Air Force Environmental Noise Assessment Center

R. B. Braid
J. H. Reed

(Abstract of ORNL/TM-11479, Oak Ridge National Laboratory, February 1991)

This report details a plan for establishing the Air Force Environmental Noise Assessment Center (AFENAC). However, recent changes in the Air Force since this effort began have provided other alternatives that were not considered in this report. Thus, the report's findings are tentative, and a follow-on study may be warranted when Air Force organizational changes are completed. AFENAC would serve as the Air Force's single center for environmental noise assessment and would manage the use of noise assessment technologies that the Air Force has developed or will develop. Public concern over aircraft noise around air bases and below low altitude and supersonic airspaces continues to grow, and these assessment technologies are intended to help the Air Force develop better environmental and community planning documents that address these public concerns. For AFENAC to fulfill its mission as a premier environmental noise center,

it should be able to serve as the Air Force's single office of environmental noise assessment [including supporting the Office of Assistant Secretary of the Air Force for Safety and Environment (SAF/MIQ) and U.S. Air Force (USAF/LEEV) by providing draft responses to public and Congressional inquiries]; maintain and upgrade computer software developed for assessment technologies; assist major commands (MAJCOMs) and bases in using technologies; suggest appropriate mitigative actions; train environmental and operations personnel in using technologies; maintain a field assistance team; maintain a strong quality assurance function; update literature and other databases; recommend research and policy initiatives; and serve as a strong advocate for noise analysis.

Research sponsored by the U.S. Department of the Air Force.

[7.1.2] Thinking the Unthinkable: Preparing for Global Disaster

R. A. Cantor
S. Rayner

[Abstract of *New Risk: Issues in Management* P. Ricci (ed.), Plenum Press, New York, 1990]

The Federal Emergency Management Agency is responsible for national planning and management functions regulating emergency preparedness, natural disasters, civil defense, and major industrial accidents. These activities place

the agency in the role of a risk manager and, in some cases, make it responsible for planning where little is known about the likelihood or consequences of the risk. One area where risk analysis and management is particularly difficult

is preparing for global disasters such as nuclear war. Among the research areas related to this risk are issues pertaining to the restoration of mechanisms for exchange of goods and services in the wake of a global disaster. Such investigations present two major challenges. First, the range of uncertainties involved implies that the possible scenarios examined must be capable of providing sufficient insight for planning purposes but reasonably limited in number to be feasibly researched. Second, the unique nature of this problem implies that theoretical and empirical evidence must be

extracted from a variety of disciplines, including anthropology, economics, and sociology. Thus, the investigation requires a novel approach, merging very diverse bodies of existing research. This paper discusses the design of an analytical framework for examining the exchange and distribution problem, focusing on these challenges and the implications for similar risk-management problems.

Research sponsored by the Federal Emergency Management Agency.

[7.1.3] Chemical Stockpile Emergency Preparedness Program Focus Groups: A Manual

S. A. Carnes
C. A. Garkovich^a
T. E. Shriver^a

(Abstract of ORNL/TM-11769, Oak Ridge National Laboratory, April 1991)

While implementing the congressionally mandated destruction of the U.S. stockpile of unitary chemical weapons, the U.S. Army decided that enhanced emergency planning was needed to reduce the potential consequences of an accidental release of agent. This decision is being implemented cooperatively by the U.S. Department of the Army and the U.S. Federal Emergency Management Agency in the form of the Chemical Stockpile Emergency Preparedness Program (CSEPP), with additional cooperation from other federal agencies and affected state and local governments. This manual supports the CSEPP effort by providing information about a commonly used qualitative data and information gathering technique, "focus group interviewing," that may be used to design public education materials and otherwise enhance communication among CSEPP providers and users. The focus group technique is characterized by structured discussions on a specific topic among a carefully

selected group of participants. This manual provides background information on the CSEPP and the program's current management plan. The manual describes the focus group technique and how it may be applied—either by itself or in conjunction with other appropriate research techniques—by state and local government officials to investigate many of the behavioral and organizational impacts of CSEPP. Sample questions and probes that may be useful in designing and conducting specific CSEPP focus groups are also provided. The manual also includes a list of suggested readings and other reference material that may be useful in designing focus groups.

Research sponsored by the U.S. Department of the Army, Office of Assistant Secretary, Installation Logistics, and Environment, and the Federal Emergency Management Agency, Office of Natural and Technological Hazards.

^aUniversity of Tennessee.

[7.1.4] Management Plan for Chemical Stockpile Emergency Preparedness Program Medical Course (Re)Design

E. D. Copenhaver

(Abstract of ORNL/TM-11842, Oak Ridge National Laboratory, May 1991)

Oak Ridge National Laboratory was asked to prepare a chemical-agent-specific course (and complementary "train-the-trainer" program) for civilian emergency medical technicians (EMTs) and paramedics in the 10 states involved in the Chemical Stockpile Emergency Preparedness Program. This will be based on the Centers for Disease Control course "Medical Management of Chemical Exposures" and the U.S. Army Medical Research Institute of Chemical Defense course entitled "Medical Management of Chemical Casualties." Though the material will be based mainly on those courses already reviewed and approved by the U.S. Department of Health and Human Services and the Army, it will have to be significantly redeveloped. Orientation will change from on-site to potential off-site conditions and will allow the courses or course

modules to be used in the conditions outlined—the most difficult being use by an individual without an instructor present. This necessitates development of self-study guides for each module, instructional materials geared to group interaction, and instructor-controlled presentation. Completion of this task will result in a suite of medical training materials directed toward EMTs and other emergency medical personnel. The diversity in these materials will enable them to be adapted to the multiple training environments expected. Some modules would also be useful as general awareness training for emergency managers and other response personnel.

Research sponsored by the Federal Emergency Management Agency.

[7.1.5] Implications of SARA Title III for Community Based Emergency Planning in the U.S. Army Chemical Stockpile Disposal Program: The Acquisition of Emergency Equipment

D. L. Feldman

(Abstract of ORNL/TM-11388, Oak Ridge National Laboratory, October 1990)

This report examines the implications of Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III for the acquisition of warning, notification, communications, and other equipment designed to provide effective emergency response for the U.S. Army's Chemical Stockpile Disposal Program (CSDP). Decisions on procurement of emergency equipment in the CSDP are made by local communities adjacent to chemical disposal facilities. Various federal agencies have a direct influence on this process, including the U.S. Department of the Army, the U.S. Federal Emergency Management Agency (FEMA), and the U.S. Environmental Protection Agency

(EPA). Two models of equipment acquisition and procurement in the CSDP have emerged. The first, put forth by FEMA and the Department of the Army, views the appropriate role of federal agencies as providing guidance to local emergency managers in the acquisition of warning, notification, and communications equipment. A second view, put forth by EPA, contends that Local Emergency Planning Committees (LEPCs)—established under SARA Title III for the purposes of overseeing development of chemical emergency planning, collecting information on chemical hazards, and evaluating available resources for emergency response—should become the focal point of

community-based efforts to acquire warning systems and other emergency equipment. The examination of these contending views focuses on four aspects: (1) the capabilities and limitations of LEPCs in relation to emergency equipment procurement, (2) the impact of tort liability on procurement decision making by LEPC members and state and local emergency managers, (3) the cohesiveness of established procurement and planning networks within states and communities affected by the CSDP, and (4) the differing programmatic goals of EPA and CSDP (FEMA, Department of the Army) relative to community-based emergency planning. Methods of reconciling these contending approaches are suggested.

The report concludes that, although all levels of government are involved in emergency preparedness decisions for the CSDP, the most effective decisions are community-based and responsive to local needs, characteristics, infrastructure, and resources. Thus, EPA and FEMA should make every effort to rely on established procurement systems for the acquisition of emergency equipment while involving LEPCs in areas of consultation and advice appropriate to their capabilities.

Research sponsored by the U.S. Department of the Army.

[7.1.6] SARA Title III and Community Hazards Planning for Chemical Emergencies: Lessons From the U.S. Army's Chemical Stockpile Emergency Preparedness Program

D. L. Feldman

(Abstract of pp. 131-44 in *Proceedings of the Fourth Annual Hazardous Materials Management Conference/Central, 1991*, Tower Conference Management Company, Glen Ellyn, Illinois, 1991)

This paper provides an overview and analysis of the impact of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA Title III) on improving community participation and risk communication for facilitating decisions leading to enhanced emergency preparedness for timely response to accidental hazardous chemical releases. It employs the U.S. Army's Chemical Stockpile Disposal Program (CSDP) and attendant Chemical Stockpile Emergency Preparedness Program (CSEPP) as case studies. In addition to reviewing the progress of SARA Title III implementation in the 10 states directly affected by these programs, staff members interviewed the regional U.S. Environmental Protection Agency (EPA) and U.S. Federal Emergency Management Agency (FEMA) representatives responsible for administering the decisions that enable this law to take effect. These interviews also provide a broad federal perspective on SARA Title III's success (or lack thereof) in heightening public awareness

of chemical hazards and improving local political competence in addressing issues associated with chemical hazards (i.e., warning, notification, communications, procurement, and equipment acquisition issues). The findings indicate that SARA Title III has significantly transformed the process of chemical and other technological hazards management by forcing greater cooperation between federal agencies (particularly EPA, FEMA, and, in some instances, the Occupational Safety and Health Administration) and states in planning and conducting emergency exercises. In so doing, SARA Title III is producing an increasingly decentralized emergency planning process. At the same time, however, Local Emergency Planning Committees and State Emergency Response Commissions—institutions established under SARA Title III—are faced with several challenges that must be addressed to ensure viable risk communications and achievement of

enhanced preparedness in local communities nationwide.

Research Sponsored by the U.S. Department of the Army.

**[7.1.7] The Chemical Stockpile Intergovernmental Consultation Program:
Lesson for High Level Waste Public Involvement**

D. L. Feldman

[Abstract of pp. 1015-21 in *High Level Radioactive Waste Management: Proceedings of the Second International Conference, Volume 2*, American Society of Civil Engineers and American Nuclear Society (1991)]

This paper assess the appropriateness of the U.S. Army's Chemical Stockpile Disposal Program's Intergovernmental Consultation and Coordination Boards (ICCBs) as models for incorporating public concerns in the future siting of high-level radioactive waste (HLW) reposi-

tories by the U.S. Department of Energy. ICCB structure, function, and implementation are examined, along with other issues relevant to HLW.

Research sponsored by the U.S. Department of the Army.

**[7.1.8] Transferring Superconductivity Technology at a National
Laboratory User Center**

D. L. Feldman

[Abstract of *Journal of Technology Transfer* 15(1), pp. 15-24 (1990)]

U.S. Department of Energy national laboratories have long sought to expedite the transfer of commercially viable technologies to the private sector through publications and reports; workshops; the licensing of inventions; personnel exchanges; and other cooperative agreements between laboratories, industry, and universities. This article focuses on the transfer of patentable technologies through a case study of the Oak Ridge National Laboratory High Temperature Superconductivity (HTSC) Pilot Center. The Pilot Center was established in 1988 to encourage rapid development and commercialization of HTSC technologies. The success of this venture will depend upon (1) assuring the compatibility of objectives of the

center and likely industrial participants and (2) directing center efforts toward the aspirations of potential collaborators and the ultimate consumers of HTSC technologies. Lessons for general multiprogram laboratory technology transfer indicate the need for (1) a model of collaboration that emphasizes openness and nonrigidity and facilitates the streamlining of information vital to the cross-fertilization of ideas, (2) continued reform of the licensing and royalty-sharing process, and (3) a simplified process of scientific exchange with private companies.

Research sponsored by the U.S. Department of Energy
Office of Energy Management.

[7.1.9] The Great Plains Garrison Diversion Unit and the Search for an Environmental Ethic

D. L. Feldman

[Abstract of *Policy Sciences* 24(1), pp. 41-64 (1991)]

The Garrison Diversion Unit (GDU), authorized by Congress in 1965, is one of the largest and most expensive public works projects ever undertaken in the United States. When completed, it may very well become the last major federal irrigation project constructed in the West. Concerted litigation, Canadian opposition, and federal budget cuts have sharply reduced the size and scope of GDU since 1984. The GDU controversy illustrates the consequences of the lack of a coherent environmental ethic guiding American natural resources policy. These consequences are two-fold. First, although GDU's impacts extend to Canada, there is little agreement between the United States and Canada over what values

should guide transboundary water resources development. Second, American beneficiaries of the project define its need in "preemptory" terms (i.e., as compensation to an entire region for losses of land associated with the original construction of Garrison Dam). Opponents, meanwhile, argue their case in "meliorative" terms (i.e., that the costs to society of building additional water projects are ameliorated by their benefits). While both views have some merit, neither view alone can encompass the range of social, economic, and environmental consequences of complex river basin development.

Research sponsored by the U.S. Department of Energy.

[7.1.10] Policy Analysis and the Management of Climate Change: Institutional Adaptability in the Face of Scientific Uncertainty

D. L. Feldman
D. Mann

[Abstract of pp. 43-49 in *Policy Studies Journal* 19(2) (1991)]

This article introduces ten papers on the policy implications of climate change. Climate change issues have faced resistance in the past. Climate change is a paramount political concern for three reasons: (1) the existence of protocols for the management of transboundary resources provide precedents that can be adapted to climate change issues; (2) the inability of such frameworks to reconcile the various demands of stakeholders without engendering resistance, and (3) other, more immediately pressing environmental, economic, and security priorities that demand the attention of decision-makers. Three conclusions warranting further study emerge from the papers comprising this symposium. First, participants in the negotiation of global agreements are unlikely

to accept conditions that they believe could have adverse economic impacts to their constituents; therefore, the standards articulated in such agreements generally will reflect a "lowest common denominator" that imposes only minor restraint. Second, despite this fact, proponents of such agreements may be willing to accept limited restraints in hopes that a wide consensus will lead to united action, and the issue of global climate change will gain a toehold on national political agendas. By getting nations to agree on basic reduction targets, signatories can arrive at their own means to enforce preventive or adaptive measures. Third, while the litany of challenges posed by economic and environmental tradeoffs in international environmental agreements are

considerable, constructive opportunities to balance tradeoffs exist, including regional targeting of advantageous economic measures for both sides.

Research sponsored by the U.S. Department of Energy Office of Policy, Planning and Analysis, and the University of Illinois, Policy Studies Organization.

[7.1.11] Estimating Costs of Electric Utility Compliance with Proposed Revisions to the Clean Air Act

E. L. Hillsman
D. R. Alvic^a

(Abstract of ORNL/TM-11712, Oak Ridge National Laboratory, April 1991)

Several bills have been introduced in Congress to reduce emissions of sulfur dioxide and nitrogen oxides from electric power plants. The effects that these bills have on electricity costs depend on the features of the bills, on the mix of generating capacity owned by the different electric utilities, on the technologies available for complying with the legislation, and on the time over which the costs are calculated. A system of computer software has been developed to make utility-specific estimates of the effects of different legislation on electricity costs. A sampling of results obtained from the model suggest that the emissions trading systems proposed in some legislation may have less effect than expected on compliance costs.

Initial emission rates and estimated range of cost increases for 11 utilities under 6 acid rain control bills.

Research sponsored by the U.S. Bureau of Mines.

^aThe University of Tennessee.

[7.1.12] Reducing Global, Regional, and Cumulative Impacts with the National Environmental Policy Act

L. N. McCold

(Abstract of The Environmental Professional, 1991)

The National Environmental Policy Act of 1969 (NEPA) is a product of national environmental concerns that developed in the late 1960s. The Council on Environmental Quality's regulations for implementation grew out of early experience with applying NEPA. The environmental impact statement (EIS) has been the principal vehicle for agencies' consideration of the effects of their proposed actions that might "significantly" affect the quality of the human environment. The number of EISs prepared by federal agencies has declined each year from 1981 to 1989, which suggests that agencies are implementing the intent of NEPA by proposing and designing actions that have less severe adverse impacts on the environment. However, the fact that some of the most worrisome environmental problems (e.g., global climate change or loss of biological diversity) are caused by the cumulative effects of many minor actions suggests that agencies may be paying too little attention to actions that they do not consider "significant." Current regulations governing NEPA implementation (40 CFR 1500-1508) give agencies little direction for

responding to environmental problems of global or regional concern such as anthropogenic climate change, stratospheric ozone depletion, and loss of biological diversity. This paper reviews NEPA regulations relevant to such concerns as anthropogenic climate change, stratospheric ozone depletion, and loss of biological diversity. It examines the treatment of global climate change and biological diversity issues in three recent NEPA documents, examines obstacles to effective consideration of the cumulative impacts of their actions, and identifies options for increasing NEPA-process responsiveness to such issues. Options for improving NEPA responsiveness include considering these issues early in the decision process, developing alternatives directed toward minimizing adverse impacts to global and regional resources, adding further significance criteria to existing NEPA regulations, and enacting legislation to limit damage to these resources.

Research sponsored by the U.S. Department of Energy
Office of Fossil Energy.

[7.1.13] Cultural Theory and Risk Analysis

S. Rayner

(Abstract in Theories of Risk, eds. D. Golding and S. Krimsky, Praeger, New York, 1991)

Cultural theory argues that risk is defined, perceived, and managed according to principles that inhere in particular forms of social organization. The cultural theory of risk entered public policy debates a decade ago. This paper presents the author's personal perspective on the origins of cultural theory in anthropology and its introduction in the field of risk analysis. The implications of a specific focus on cultural

interpretations for developing trust, distributing liability, and expressing consent are reviewed along with the implications of regime theory. The paper replies to six specific objections that are encountered frequently by cultural analysis. The paper also identifies future directions for cultural analysis, the first of which is the development of a systematic theory of regimes. The second is the

development of authentic interdisciplinary research approaches.

Research sponsored by the U.S. Department of Energy Office of Policy, Planning, and Analysis.

[7.1.14] A Cultural Perspective on the Structure and Implementation of Global Environmental Agreements

S. Rayner

[Abstract of *Evaluation Review* 15(1), February 1991]

This paper introduces the concept of management frameworks as institutional cultures. Nations and organizations tend to favor one or another of a variety of decision-making styles composed of unique combinations of three basic types known as hierarchies, markets, and collectives. The decision styles systematically constrain discourse and lead decision makers to frame problems in specific, sometimes incompatible manners. Such constraints affect the selection of issues for attention, the perceptions of urgency, the recognition of other stakeholders as legitimate participants in decisions, and the preferences for

different instruments of policy implementation. The paper explores the implications of these decision styles for climate decision making, especially in the context of polycentric management regimes. The paper concludes that greater attention to nongovernmental institutional contacts across national boundaries could possibly provide opportunities to conclude and implement global agreements for environmental management.

Research sponsored by the U.S. Department of Energy Office of Policy, Planning, and Analysis.

[7.1.15] Prospects for Greenhouse Gas Policy in the U.S. Energy Sector

S. Rayner

[Abstract of *Energy Policies and the Greenhouse Effect*, M. Grubb (ed.), Vol. 2, Gower Press for the Royal Institute of International Affairs, Brookfield, Vt. (1991)]

This study consists of three parts, the first of which considers the present state of the U.S. energy system and presents illustrative scenarios that encompass a wide range of technical possibilities for the U.S. energy sector. It is concluded that, although the prospects for reducing CO₂ emissions through energy efficiency are promising, socially acceptable alternatives to fossil energy are not sufficiently mature to provide U.S. primary energy needs. The second section considers the technical, institutional, and economic constraints for efficiency and fuel switching in the four major energy conversion sectors of the United States: electric utilities, transportation, manufacturing, and residential and commercial uses. Various opportunities exist for

institutional and regulatory changes that could enhance the prospects for greenhouse gas reductions. However, major obstacles are raised by the complexity of decision-making procedures (especially in transport) and institutional inertia (especially in manufacturing and construction). The final section examines the U.S. political context and the prospects for greenhouse gas reduction policies throughout the energy system. The obstacles noted above are exacerbated by the confrontational nature of the global environmental debate in the United States, which occurs in an open political system that empowers dissenters to impede policy developments that may be to their disadvantage. In light of this, it is concluded that a realistic U.S. contribution to

global greenhouse gas reduction would consist of four elements: (1) aggressive pursuit of energy efficiency throughout all sectors; (2) pursuit of an ambitious program of energy research and development to provide practical alternatives to fossil fuels; (3) development of an extensive technology transfer program (perhaps linked to emissions trading) to save developing countries from reliance on fossil fuels in their economic

development; and (4) use of new technologies that have become economically more attractive in the United States (because of implementation in developing countries), replacing the existing U.S. fossil fuel infrastructure over the long term.

Research sponsored by the U.S. Department of Energy
Office of Policy, Planning, and Analysis.

[7.1.16]

Risk Management for Global Environmental Change

S. Rayner
T. O'Riordan^a

[Abstract of Global Environmental Change 1(2), 1991]

Global environmental change is both a concept and a process that changes in meaning with scientific discovery, public concern, and political responsiveness. The relationship between the problems, as perceived, and the various institutions that help shape such problems defines global environmental change. Holistic risk analysis, because of its capacity to recognize this relationship in many spheres of problem identification, can contribute to the political debate. Such analysis will suggest an institutional reorganization of the relationship between scientific research, public entry, and experimental

readjustments to consensus formation and international action. This paper examines the changing nature of the global change issue, considers how the disciplines of risk analysis and risk management are trying to respond to the new challenges offered by global environmental change, suggests ways in which global risks can be classified, and recommends different approaches to science and policy evaluation.

Research sponsored by the U.S. Department of Energy
Office of Policy, Planning, and Analysis.

^aUniversity of East Anglia, Norwich, England.

[7.1.17] Establishing Functional Requirements for Emergency Management Information Systems

J. H. Reed
G. Rogers
J. H. Sorensen

(Abstract of Simulation in Emergency Management and Engineering, J. Sullivan and A. Clymer, eds., Society for Computer Simulation, San Diego, 1991)

The advancement of computer technologies has led to the development of a number of emergency management information systems. The design of these systems has tended to be technologically driven rather than oriented to meeting information management needs during an emergency. Of course, emergency management needs vary,

depending on the characteristics of the emergency. For example, in hurricanes, onset is typically slow enough to allow emergency managers to dynamically simulate evacuations; in chemical disasters, onset may be sufficiently rapid to preclude such simulation(s). This paper describes a system design process in which the

analysis of widely recognized emergency management functions was used to identify information requirements and the requisite software and hardware capabilities to deal with rapid onset, low probability, and high consequence events. These requirements were then implemented as a prototype emergency management system using existing hardware and software to assure feasibility. Data, hardware,

and software requirements were further developed, refined, and made more concrete through a repetitious prototyping effort. This approach directly focuses attention on meeting emergency management information needs, while avoiding unneeded technological innovations.

Research sponsored by the U.S. Department of the Army, Chemical Stockpile Emergency Preparedness Program.

[7.1.18] Description of Interview Data Regarding Pittsburgh and Confluence Toxic Chemical Accidents

G. Rogers
B. Shumpert^a
J. H. Sorensen

(Abstract of ORNL/TM-11599, Oak Ridge National Laboratory, November 1990)

Evacuation is the protective action most often recommended in response to accidental chemical releases in the United States. The appropriateness of a decision to evacuate depends on whether the affected area can be cleared of residents before it is contaminated by the chemical release. In determining whether an evacuation can be completed in time, emergency officials must consider both technical and behavioral aspects. The technical components (e.g., size of area to be evacuated and length and capacity of evacuation routes) can be readily conceived and quantified. In contrast, the behavioral components (i.e., how and when the public will react to the evacuation warning) are much more abstract and difficult to estimate. This report summarizes the univariate analysis of behavioral responses to surveys conducted in two communities where evacuation was recommended following train derailments involving hazardous chemicals. The surveys were designed to identify the actions taken by residents upon receiving the emergency warning; determine when people received the warning, decided to take action, and implemented the action; and ascertain factors that might explain the nature and timing of their actions. The surveys were conducted in the Bloomfield section of Pittsburgh, Pennsylvania, and in the town of Confluence, Pennsylvania. Interesting

similarities and differences were found in the responses from residents of the two communities. Confluence residents were found to have been more likely to have complied with the evacuation recommendation than their counterparts in Pittsburgh. They also received and responded to the warning more quickly and were less likely to report the need for additional information

Distribution of mobilization times in two chemical accidents.

regarding the hazard. In both communities, most respondents first received the warning to evacuate from official sources but reported that informal "contagion" was important in spreading the warning and in helping them decide how to respond. The surveys also provide information on the specific actions the respondents took when they received warning, their evacuation logistics and concerns, and their evaluation of the performance of public officials and the media in handling the emergency. The study confirms that compliance with an emergency warning to evacuate varies, and that potentially dangerous delays can be expected. Significant differences were noted, however, in the rate and speed of compliance in the two communities. The surveys

provide information on several factors that may be useful in determining the reasons for differences in the responses as well as differences among individual respondents. Such factors include the time of day at which the accident occurred, the location of the respondent at that time, whether the family was together, previous disaster experience, pet ownership, the content of the warning message, and demographic characteristics.

Research sponsored by the U.S. Department of Army, Chemical Stockpile Disposal Program.

*The University of Tennessee, Energy, Environment, and Resource Center

[7.1.19] Demand-Side Management and Integrated Resource Planning: Findings from a Survey of 24 Electric Utilities

M. Schweitzer
E. Hirst
L. J. Hill

(Abstract of ORNL/CON-314, Oak Ridge National Laboratory, February 1991)

Recently, Oak Ridge National Laboratory surveyed 24 United States electric utilities concerning their operating environments, organizational characteristics, and the mix of resources selected for their integrated resource plans. This synopsis briefly describes key

findings from that study. Currently, utility demand-side management (DSM) programs are responsible for an average reduction of 1.7% in capacity requirements and 0.8% in electricity generation. By the year 2000, DSM's share of the resource mix is expected to jump to 7.1% of capacity and 4.1% of generation. While the importance of DSM is clearly increasing, it continues to be favored more for limiting peak load rather than for limiting overall electricity sales. In 5 years or less, two-thirds of the responding utilities will need additional capacity. Over the next 10 years, the mean rate of growth among these utilities is projected to be nearly 30% in terms of required capacity and electricity generation. This study identifies a number of relationships between utility characteristics and the resources selected for the integrated plan: (1) utilities that include more DSM in their plans will not need new capacity as soon as other utilities; (2) utilities required to prepare integrated resource plans select more DSM than other

Location of utilities responding to Oak Ridge National Laboratory survey.

utilities; (3) utilities that depend heavily on oil and gas for generating electricity favor purchased power and DSM more and put less emphasis on new utility-owned generation than other utilities; (4) utilities that greatly value input from technical advisory groups or consumer panels when identifying potential DSM options during the screening process select more DSM than other utilities; (5) utilities that place substantial importance on collaborative planning with nonutility interests emphasize DSM more than other utilities; (6) utilities that give simultaneous and equal treatment to both supply- and demand-side resources when developing an

integrated plan select more DSM than other utilities; (7) utilities that subtract projected DSM savings from the load forecast and meet remaining needs only with supply options rely more on utility-owned generation than other utilities do; and (8) utilities that place greater importance on cost when choosing options for the integrated plan select less DSM than other utilities do, while those that favor environmental concerns select more DSM.

Research sponsored by the U.S. Department of Energy
Office of Conservation and Renewable Energy.

[7.1.20] A Look at the Resource Portfolios of 24 Electric Utilities

M. Schweitzer
E. Hirst
L. J. Hill

[Abstract of pp. 38-45 in *The Electricity Journal* 4(7), August/September 1991]

In recent years, the resources electric utilities use to meet customer needs has changed considerably, most notably with an increased emphasis on demand-side management (DSM). This paper examines current utility reliance on DSM and looks ahead to the mix of resources that utilities plan to use by the year 2000. The data here come from a recent Oak Ridge National Laboratory survey of 24 utilities nationwide, which account for approximately one-third of U.S. electricity generation. Two-thirds of the responding utilities will need additional capacity within 5 years. Over the next 10 years, the mean rate of growth among these utilities is projected to be nearly 30% in terms of required capacity and electricity generation. Utility DSM programs are currently responsible for an average reduction of 1.7% in

capacity requirements and 0.8% in electricity generation. In the next 8 years, DSM's share of the resource mix should swell to 7.1% of capacity and 4.1% of generation. However, DSM continues to be favored more for limiting peak load than for limiting overall electricity sales. State public utility commissions can promote increased use of DSM measures through economic incentives, education, and mandates. Further, utilities themselves can take additional steps to identify new DSM options and to enhance their desirability by explicitly considering environmental issues when assessing cost effectiveness.

Research sponsored by the U.S. Department of Energy
Office of Conservation and Renewable Energy.

[7.1.21] Nuclear Power Station Seismic Hazard Curves in the Eastern United States and the Uniform Building Code

W. P. Staub

[Abstract of Bulletin of the Association of Engineering Geologists 28(3), 227-34 (1991)]

Bernreuter and others published 50th, 85th, and 15th percentile seismic hazard curves for 69 nuclear plants sited on rock and soil in the eastern United States (the percentiles represent median and one standard deviation above and below the mean, respectively). This paper compares Bernreuter's curves for a subset of 38 nuclear plants sited on rock with seismic hazard curves derived from data provided by the International Conference of Building Officials (ICBO), the U.S. Federal Emergency Management Agency (FEMA), and the Applied Technology Council (ATC) to assess the degree of conservatism represented by ICBO, FEMA, and ATC data. Without exception, seismic hazard curves based on data provided by ICBO's 1988

Uniform Building Code (UBC) and FEMA are more conservative than the 50th percentile seismic hazard curves of Bernreuter and others. The seismic hazard curves derived from the 1988 UBC are, on average, approximately midway between Bernreuter's 50th percentile and 85th percentile seismic hazard curves, and they are somewhat more conservative than those based on ATC guidelines. The 1988 UBC guidelines (with respect to seismic design) appear to be sufficiently—but not overly—conservative when compared with Bernreuter's seismic hazard curves.

Research sponsored by the U.S. Department of the Army.

ENVIRONMENTAL ASSESSMENTS AND IMPACT STATEMENTS**[7.1.22] ENVIRONMENTAL ASSESSMENT, ADVANCED COAL CONVERSION PROCESS DEMONSTRATION PROJECT CLEAN COAL TECHNOLOGY PROGRAM, WESTERN ENERGY COMPANY, ROSEBUD MINE, ROSEBUD COUNTY, MONTANA**

A. W. Campbell

(Summary of DOE/EA-0469, March 1991)

This environmental assessment was prepared for the U.S. Department of Energy to evaluate the effects of a Clean Coal Technology demonstration project that is being partially funded by the federal government. The Advanced Coal Conversion Process (ACCP) demonstration project, proposed by the Western Energy Company, would be located at the Rosebud Mine near Colstrip, Montana. The objective of the proposed ACCP project is to demonstrate the technical and economic feasibility of an advanced process that can enhance the thermal value and environmental acceptability of subbituminous coal and lignite.

Basically, the process dries coal, liberates ash particles, and converts organic molecules to a denser structure. The product is a stable, solid fuel that is high in volatile material content and will not reabsorb moisture. The proposed ACCP facility would require about 445,000 tons of raw coal feed annually, or about 4% of the annual coal production of the Rosebud Mine. About 5 million tons of propane would be burned annually in the ACCP furnace. The flue gas desulfurization system would require about 230 tons per year of the sorbent nahcolite (NaHCO_3). Electrical requirements for the proposed demonstration

plant would be about 27,000 megawatt-hours per year obtained from the grid by a connection with existing lines. Atmospheric emissions from the proposed project would represent an extremely small potential increase in the levels of all air emissions currently being released from the existing mining and power-generating facilities at Colstrip. Emissions of criteria pollutants would increase, by substantially less than the 100 tons per year, the regulatory threshold established for a major new source and for prevention of significant deterioration review under existing state and federal standards. The proposed project would not adversely affect surface water or groundwater resources in Rosebud County. Nonpotable water requirements for the proposed project would be provided from ample supplies at an existing mine dewatering pit. Use of water from this source is consistent with the existing state permit in place for the facility; a state permit to appropriate additional water for the project would not be needed. No effluent would be discharged as a result of the proposed action.

Wastes and by-products from the process would consist of slack material separated from the product fuel and spent sorbent from the flue gas desulfurization system. The process slack would be transported to an off-site user as a refuse fuel blended with pit slack currently generated at the mine or, as an alternative, disposed of in the mine pit with the pit slack. The spent nahcolite sorbent is collected by a baghouse system, bruquetted together with other coal fines, and combined with the final product for storage pending shipment of off-site users. No hazardous wastes would be generated by process operations. An increase in noise would not be noticeable at the residential areas in Colstrip, 3 miles away. A small increase in local traffic, primarily associated with truck transport of materials, is expected. Endangered species; historic, cultural, and archaeological resources; wetlands; floodplains; and other sensitive environmental resources would not be affected.

Research sponsored by the U.S. Department of Energy.

[7.1.23]

ENVIRONMENTAL ASSESSMENT, PROPOSED SALE OF PARCEL A2 OF THE OAK RIDGE RESERVATION TO THE CITY OF OAK RIDGE

R. E. Saylor
R. H. Ketelle
F. O'Donnell^b

D. B. Hunsaker, Jr.
R. L. Kroodsma^a
J. W. Van Dyke

The U.S. Department of Energy proposed to sell 295.8 hectares (ha) (681.5 acres) of Oak Ridge Reservation to the City of Oak Ridge. This tract of land (Parcel A2) is bound on the south by Edgemoor Road and on the east by Melton Lake Drive. The city anticipates development of 400 to 500 single family dwellings on about 220 ha (550 acres) of the parcel within 8 years. It also anticipates industrial development on about 55 ha (140 acres) within 2 years. The proposed sale of Parcel A2 would have no immediate environmental impacts; however, subsequent development by the City would affect the existing environment as follows: (1) Three plant species listed by the Tennessee Department of Conservation occur on Parcel A2. Restricted use

areas would be needed to protect the plants. (2) An accidental release of two tons of chlorine from the nearby Y-12 facility would impose a health hazard for residents in this land tract. However, this is highly unlikely. (3) Four sites are recommended for study of their archaeological significance before they are disturbed. Deed restrictions will require these studies. (4) In general, the opportunity to acquire land suitable for residential purposes could provide major benefits to the City of Oak Ridge.

Research sponsored by the U.S. Department of Energy.

^aEnvironmental Sciences Division.

^bEnvironmental and Health Protection Division

**[7.1.24] ENVIRONMENTAL ASSESSMENT, DEMONSTRATION OF COAL
REBURNING FOR CYCLONE BOILER NITROGEN OXIDE (NO_x)
CONTROL NELSON DEWEY GENERATING STATION
WISCONSIN POWER & LIGHT COMPANY
CASSVILLE, WISCONSIN**

R. L. Kroodsmas^a
A. W. Campbell
R. O. Johnson
V. R. Tolbert^a

T. J. Blasing
G. K. Eddlemon^a
R. L. Miller
J. W. Van Dyke

(Summary of DOE/EA-0440, February 1991)

Prepared for the U.S. Department of Energy (DOE), this environmental assessment evaluates environmental issues associated with a proposed demonstration project that would be cost-shared by DOE and private industry under DOE's Clean Coal Technology Program. The proposed action is to share the cost of installing and operating coal-reburning equipment on the existing Unit No. 2 boiler at the Nelson Dewey Generating Station, located on the Mississippi River at Cassville, Wisconsin. A portion of the crushed coal currently burned at the plant would be pulverized and then coal-reburned above the boiler's main combustion zone. The purpose of the project is to demonstrate the commercial feasibility of a technology for reducing the amount of nitrogen oxides (NO_x) emitted from the stacks of coal-fired power plants having cyclone boilers. Alternatives discussed include no action, delayed action, using alternative sites, and employing alternative technologies. No significant environmental impacts are expected from the proposed action for the following reasons: (1) Reburning equipment would be installed and operated in an existing industrial facility in a previously disturbed location. (2) The amount and type of coal stored and burned at the power plant would not change. (3) The only changes in atmospheric emissions would be a decrease of 25% or more in NO_x emissions for the two-unit power plant and an increase of 42% or

less in fly ash emissions (which contribute to particulate concentrations). Predicted maximum ambient ground-level concentrations of particulate matter would be lower than applicable National Ambient Air Quality Standards and Prevention of Significant Deterioration increments. Opacity of stack emissions would increase by 1% and would remain below Wisconsin's limit of 20% for new or modified facilities. (4) The amount of effluent released to the Mississippi River or to the groundwater would remain the same as for current operations, and water quality and aquatic biota in the river would not be adversely affected. (5) The project would not require any land acquisition, change in land use, or loss of wildlife habitat, on or off the site. (6) No floodplains or wetlands would be affected. (7) No threatened or endangered species would be affected. (8) Only a small construction-work force would be required, and no increase in the operational work force would be needed. The local economy would not be affected. (9) No sites on or eligible for the *National Register of Historic Places* would be affected. (10) Noise levels from construction and operation of the project would have no significant impact on off-site areas.

Research sponsored by the U.S. Department of Energy.

^aEnvironmental Sciences Division.

**[7.1.25] DRAFT ENVIRONMENTAL IMPACT STATEMENT, PROPOSED
HEALY CLEAN COAL PROJECT**

R. L. Miller
R. O. Johnson
W. P. Straub

A. W. Campbell
J. W. Saulsbury
G. W. Suter II^d

(Summary of report, October 1991)

This environmental impact statement (EIS) was prepared for the U.S. Department of Energy (DOE) to assess environmental issues associated with the Healy Clean Coal Project (HCCP), a proposed demonstration project whose cost would be shared by DOE and the Alaska Industrial Development and Export Authority under the Clean Coal Technology Program. HCCP would be a 50-MW coal-fired power generating facility built adjacent to the existing 25-MW Healy Unit No. 1 conventional pulverized coal unit on a site about 4 miles north of the Denali National Park and Preserve (DNPP). HCCP would use low-sulfur coal from Usibelli Coal Mine, located about 4 miles north of the site. After a 1-year demonstration and testing period, commercial operation of HCCP is anticipated in 1997. HCCP is intended to demonstrate the combined removal of sulfur dioxide (SO₂), nitrogen oxides (NO_x), and particulate matter using innovative combustion and flue gas cleanup technologies. The project is expected to generate sufficient data to allow private industry to assess its potential for commercial application. Environmental impacts from construction and operation of HCCP at the proposed site were evaluated and found not to be significant for most resource areas. However, one concern is the impact to air quality and visibility expected from HCCP operation, as predicted by computer-based models. (Because of conservative assumptions in the model, actual impacts are expected to be somewhat less.) HCCP NO_x emissions for the expected case were predicted to use up to 33% of the degradation

allowed for annual concentrations within DNPP (for the conservative case, the prediction increases to 95%); similar high percentages were predicted for SO₂. Analyses of cumulative air quality impacts during simultaneous operation of HCCP and Healy Unit No. 1 also revealed high percentages. Other concerns are that ice bridge formation over the Nenana River near Ferris, Alaska, may be affected by the thermal discharge from HCCP and Healy Unit No. 1, and that construction rubble may exacerbate existing landfill concerns in Healy. Moderate to major socioeconomic impacts are expected during HCCP construction and operation, particularly in the area of housing, education, police and fire protection, and medical services. In addition to the proposed action, the EIS considers the no-action alternative and an alternative site located about 4 miles from the proposed site. For the no-action alternative, if no new electrical generating facilities were built, impacts would remain unchanged from baseline conditions. If a conventional plant were built at Healy, the level of impacts would be almost identical to that of HCCP for most areas. At the alternative site, environmental impacts are generally expected to be greater because the proposed site has already been disturbed by the construction and operation of Healy Unit No. 1.

Research sponsored by the U.S. Department of Energy.

^dEnvironmental Sciences Division.

**[7.1.26] DRAFT ENVIRONMENTAL ASSESSMENT, RETRIEVABLE SOLID
TRANSURANIC WASTE OPERATIONS AT THE
OAK RIDGE NATIONAL LABORATORY**

R. E. Saylor
C. E. Easterly^b
R. H. Ketelle
R. B. McLean

F. O'Donnell^a
C. W. Hagan
R. L. Kroodsmas^c
R. L. Miller

The purpose of the proposed action is to continue the management of retrievably stored transuranic (TRU) waste at Oak Ridge National Laboratory (ORNL) in compliance with applicable federal, state, and local laws and regulations, as well as U.S. Department of Energy Orders and policies. Existing ORNL contact-handled (CH) TRU mixed waste storage facilities do not currently meet the requirements for a Resource Conservation and Recovery Act (RCRA) waste storage facility and are scheduled for closure beginning in November 1992, in accordance with the 1984 amendments to RCRA. Therefore, new waste storage facilities with RCRA permits will be needed for CH TRU mixed waste; the mixed waste subsequently would be transferred to the new RCRA-permitted storage facilities. The existing RCRA-permitted remote-handled (RH) TRU mixed waste storage facility also has limited storage capacity. Remaining space can provide about 2 years of continued RH TRU storage, after which additional storage facilities would be needed. Plans call for all ORNL TRU wastes to be shipped to, and permanently disposed of at, the Waste Isolation Pilot Plant located in New Mexico. The proposed action will have no

significant environmental impacts or limit the choices of reasonable alternatives of the Programmatic Environment Impact Statement for Environment Restoration and Waste Management being prepared for the Oak Ridge Reservation. A proposed Nuclear Fuel Services, Inc. (NFS) waste storage Facilities, Buildings 7572 and 7577. Environmental impacts of construction and operation socioeconomics. A low marshy area where a state-listed lily grows is located 30 ft west of the site. This site must be protected from physical disturbance, run-off, and siltation. The Waste Handling and Packaging Plant (WHPP), which is proposed to be constructed near the future RH TRU waste storage facility, would be designed as a "zero-discharge" (i.e., zero discharge of effluents) facility. Therefore, routine operations at WHPP would not be expected to contribute to cumulative impacts at this site.

Research sponsored by the U.S. Department of Energy.

^aEnvironmental and Health Protection Division.

^bHealth and Safety Research Division.

^cEnvironmental Sciences Division.

[7.1.27] DRAFT ENVIRONMENTAL ASSESSMENT, ALTERATIONS AND ADDITIONS TO THE DEFENSE METEOROLOGICAL SATELLITE SYSTEM SATELLITE PROCESSING FACILITY (BUILDING 1559) VANDENBERG AIR FORCE BASE, CALIFORNIA

A. W. Campbell R. L. Graham^a
E. J. Liebsch S. F. Railsback^a
B. L. Shumpert^b M. A. Mitckes^c
W. P. Straub

(Summary of report, November 1990)

In this environmental assessment (EA) prepared for the U.S. Air Force, the proposed action (which consists entirely of construction activities) is to modify and add to Building 1559 at Vandenberg Air Force Base, California; these modifications will allow prelaunch satellite processing and postlaunch satellite checkout to be fully accomplished in one facility. After completion of the new wing, the electronic satellite testing and communications hardware located in another building would be transferred by military vehicles to Building 1559. Atmospheric emissions of fugitive dust from earthwork, vehicle and equipment exhaust, and volatile organic compounds from asphalt paving. The only effluent discharge from construction and operation would be sanitary sewage; and construction would generate conventional nonhazardous wastes such as excavated soil, concrete rubble, wood, and building material debris. The nature or quantity of hazardous and

nonhazardous solid or liquid wastes generated by operation would not change as a result of the proposed action. Resource areas evaluated in the EA are the man-made environment (e.g., land use, population and housing, community facilities) and the natural environment (i.e., climate and air quality, surface water resources, groundwater resources, terrestrial ecology, aquatic and marine ecology, threatened and endangered species, and floodplains and wetlands). The analyses in the EA indicate that no significant impacts are expected in the man-made environment as a result of the proposed action. Also, no significant impacts are expected to the natural environment.

Research sponsored by the U.S. Air Force, Space Systems Division.

^aEnvironmental Sciences Division.

^bThe University of Tennessee.

^cEbasco Service, Inc.

[7.1.28] DISPOSAL OF CHEMICAL AGENTS AND MUNITIONS STORED AT ANNISTON ARMY DEPOT, ANNISTON, ALABAMA FINAL PHASE I ENVIRONMENTAL REPORT

D. B. Hunsaker, Jr. G. P. Zimmerman
E. L. Hillsman R. L. Miller
G. M. Schoepfle V. R. Tolbert^a
R. L. Kroodsma^a L. W. Rickert
G. O. Rogers W. P. Staub

(Summary of ORNL/TM-11206/V1&2, September 1990)

The Anniston Army Depot (ANAD) is one of eight continental U.S. Army installations where lethal unitary chemical agents and munitions are stored and where destruction of agents and

munitions is proposed under the Chemical Stockpile Disposal Program (CSDP). In 1988 the U.S. Army issued a Final Programmatic Environmental Impact Statement (FPEIS) for the

CSDPO that identified on-site disposal of agents and munitions as the environmentally preferred alternative (i.e., the alternative with the least potential to cause significant adverse impacts). In some instances, the FPEIS included generic data and assumptions that were developed to allow a consistent comparison of potential impacts among programmatic alternatives and did not include detailed conditions at each of the eight installations. The environmentally preferred alternative was identified using a method based on five measures of risk directed at potential human health and ecosystem/environmental effects; the adequacy of emergency response also played a key role in the method. In the Record of Decision following the FPEIS, on-site disposal at each of the eight sites was selected for implementation of the program. Volume 1 of the Phase I report examines the proposed implementation of on-site disposal at ANAD in light of more detailed and more recent data than those included in the FPEIS. Two principal issues are addressed: (1) whether or not the new data would result in identification of on-site disposal at ANAD as the environmentally preferred alternative (using the same selection method and data analysis tools as in the FPEIS), and (2) whether or not the new data indicate the presence of significant environmental resources that could be affected by on-site disposal at ANAD. In addition, a status report is

presented on the maturity of the disposal technology (and how it could affect on-site disposal at ANAD). Inclusion of these more recent data into the FPEIS decision method resulted in confirmation of on-site disposal for ANAD. No unique resources with the potential to prevent or delay implementation of on-site disposal at ANAD have been identified. A review of the technology status identified four principal technology developments that have occurred since publication of the FPEIS and should be of value in the implementation of on-site disposal at ANAD: the disposal of nonlethal agent at Pine Bluff Arsenal located near Pine Bluff, Arkansas; construction and testing of facilities for disposal of stored lethal agent disposal tests at the chemical agent pilot plant operations at Tooele Army Depot located near Salt Lake City, Utah; and equipment advances. Volume 2 represents an addendum to the final Phase I report to summarize the external review of the Phase I report by cooperating agencies and Argonne National Laboratory and to include additional information in the Phase I process, as recommended by an independent review. Principal new information added deals with seismicity.

Research sponsored by the U.S. Army.

^aEnvironmental Sciences Division.

[7.1.29] CHEMICAL STOCKPILE DISPOSAL PROGRAM FINAL PHASE I ENVIRONMENTAL REPORT FOR TOOELE ARMY DEPOT, TOOELE, UTAH

G. P. Zimmerman	R. L. Miller
C. R. Boston	L. W. Rickert
E. L. Hillsman	G. O. Rogers
R. O. Johnson	W. P. Staub
R. L. Kroodsma ^a	V. R. Tolbert ^a

(Summary of ORNL/TM-11211, April 1991)

The Tooele Army Depot (TEAD) in Utah is one of eight continental U.S. Army installations where lethal unitary chemical agents and munitions are stored and where destruction of agents and munitions is proposed under the Chemical Stockpile Disposal Program (CSDP).

In 1988 the U.S. Army issued a Final Programmatic Environmental Impact Statement (FPEIS) for the CSDP that identified on-site disposal of agents and munitions as the environmentally preferred alternative. In some instances, the FPEIS included generic data and

assumptions that were developed to allow a consistent comparison of potential impacts among programmatic alternatives and did not include detailed conditions at each of the eight installations. The FPEIS identified the environmentally preferred alternative using a method based on five measures of risk directed at potential human health and ecosystem or environmental effects; the adequacy of emergency response also played a key role in the method. In the Army's Record of Decision following the FPEIS, on-site disposal was selected for implementation of on-site disposal at TEAD in light of more detailed and more recent data than those included in the FPEIS. The objectives of this Phase I report are to (1) reexamine those site-specific data that were important in selecting the environmentally preferred alternative in the FPEIS (i.e., on-site disposal); (2) make recommendations for the scope and content of the subsequent

environmental impact statement to be prepared for TEAD under Phase II; and (3) address the concern that the FPEIS was too generic to adequately determine a programmatic environmentally preferred alternative. It was found that none of the newly collected data added any information that would have changed the FPEIS conclusion for TEAD. In addition, none of these data lends credibility to the argument that something of significance was overlooked in the FPEIS. The recommendation of this Phase I report is to proceed with the preparation of a site-specific environmental impact statement for TEAD. The site-specific document should focus on the implementation of on-site disposal and should not consider other alternatives for disposing of the TEAD stockpile.

Research sponsored by the U.S. Army.

^aEnvironmental Sciences Division.

[7.1.30]

FINAL ENVIRONMENTAL IMPACT STATEMENT, DISPOSAL OF CHEMICAL AGENTS AND MUNITIONS STORED AT ANNISTON ARMY DEPOT, ANNISTON, ALABAMA

D. B. Hunsaker, Jr.	T. J. Blasing
G. P. Zimmerman	C. W. Hagan, Jr.
E. L. Hillsman	C. R. Boston
R. L. Miller	S. A. Carnes
G. M. Schoepfle	J. B. Cannon
R. O. Johnson	J. D. Harris ^c
V. R. Tolbert ^a	J. W. Saulsbury
R. L. Kroodsmas ^a	J. H. Sorensen
L. W. Rickert	R. J. Andermann ^d
F. E. Latham ^b	D. C. West ^a

W. P. Staub

(Summary of report, May 1991)

This Final Environmental Impact Statement assesses the potential environmental impacts of on-site destruction of the lethal unitary chemical agents and munitions stockpiled at Anniston Army Depot (ANAD), Alabama. The demilitarization process involves three major steps: handling and transport of munitions from the existing chemical storage area to the munitions demilitarization building, reverse assembly and

incineration of munitions and agents, and management of the waste materials that remain after incineration. Four incinerators would be used. The facility, including the incinerators, would meet stringent Resource Conservation and Recovery Act, Toxic Substances Control Act, and Clean Air Act permitting requirements. The disposal facility would not discharge liquid waste except for sanitary sewage. The current schedule

calls for construction of the facility to begin in August 1992, and disposal operations to begin in May 1996. Disposal operations are expected to take about 3 years. The construction work force is estimated to peak at about 335 individuals; the estimated operating work force is about 370 individuals, with about 285 depot support staff members. Total cost is estimated at \$692 million. The potential environmental impacts associated with construction are judged to be minimal, and socioeconomic impacts of construction activities would be beneficial. Operations under incident-free conditions would result in minimal impacts to the environment. Potential impacts could be produced by disposal plant emissions, transport of chemical agents and munitions from the storage site to the disposal plant, solid waste generated from incineration, and possible exposure to low, but permissible, levels of chemical agent. No significant impacts would be expected from these activities.

Accidents involving explosions, fires, or spills could have environmental consequences of major proportions, including human fatalities, destruction of wildlife and wildlife habitat, destruction of economic resources, and contamination of water resources and water supplies. Such high-consequence accidents have extremely low probabilities of occurring. Risk analyses in this report indicate that continued storage would result in greater risk to the public than the proposed on-site disposal. Mitigation measures considered fall into three categories: safety enhancements; emergency planning; and operation limitations (i.e., limiting the daily operational period of demilitarization).

Research sponsored by the U.S. Army.

^aEnvironmental Sciences Division.

^bComputing and Telecommunications Division.

^cEngineering Technology Division.

^dChemical Technology Division.

[7.1.31] DRAFT GENERIC ENVIRONMENTAL IMPACT STATEMENT FOR LICENSE RENEWAL OF NUCLEAR POWER PLANTS

R. B. McLean

D. C. Agouridi^a

C. R. Boston

R. B. Braid

G. F. Cada^b

A. W. Campbell

S. W. Christensen^b

J. B. Cannon

S. M. Cohn

C. E. Easterly^c

D. L. Feldman

C. W. Hagan

R. L. Kroodsmas^b

D. B. Lasley

R. R. Lee

L. K. Mann^b

M. A. Linn^d

L. N. McCold

R. L. Miller

G. A. Murphy^c

C. H. Petrich

L. W. Rickert

R. M. Rush

J. W. Saulsbury

R. E. Saylor

S. M. Schexnayder^f

M. Schweitzer

W. P. Staub

V. R. Tolbert^b

J. W. Van Dyke

J. S. Watson^g

E. Z. Seighami^c

This Generic Environmental Impact Statement (GEIS) was prepared to support a rulemaking to change Nuclear Regulatory Commission (NRC) environmental protection rules in 10 CFR Part 51, regarding requirements for the renewal of nuclear power plant operating licenses. The rulemaking was undertaken to address the environmental impacts that may result from activities associated with the renewal of an operating license and to codify the findings concerning these impacts so that they may be applied with limited further

analysis in future environmental reviews for license renewals at individual plants. The objectives of this GEIS are to (1) provide an understanding of the types and severity of environmental impacts that may occur as a result of renewing operating licenses for nuclear power plants, (2) identify and assess those impacts expected to be generic to license renewal, and (3) support the proposed 10 CFR Part 51 rule by defining the issues that need to be addressed by the NRC and the applicants in plant-specific

license renewal proceedings. The GEIS identified 104 environmental issues associated with the renewal of individual plant licenses and evaluated the significance of the environmental impact of each. For a large number of issues, a generic conclusion was made on the potential environmental impacts. For other issues, this conclusion could be reached for some subset of all nuclear power plants which were within defined bounds specified in the GEIS. For two issues, it was concluded that no generic conclusion on impacts could be reached. The Commission is proposing to limit the scope of environmental review in individual plant license renewal cases to

only those impacts for which no generic conclusion could be reached (i.e., Categories 2 and 3). All applicants will be required to provide appropriate information and analysis in their license renewal applications for all Category 2 and 3 issues identified in the GEIS.

Research sponsored by the Nuclear Regulatory Commission.

^aInstrumentation and Controls Division.

^bEnvironmental Sciences Division.

^cHealth and Safety Research Division.

^dResearch Reactors Division.

^eEngineering Technology Division.

^fUniversity of Tennessee.

^gChemical Technology Division.

[7.1.32] DRAFT SUPPLEMENTAL ENVIRONMENTAL IMPACT STATEMENT FOR THE UNITED STATES ANTARCTIC PROGRAM

R. M. Reed
S. F. Railsback^a
J. W. Saulsbury
C. L. Hardy
J. M. MacDonald

R. B. McLean
J. B. Cannon
D. B. Hunsaker, Jr.
E. J. Liebsch
L. W. Rickert

Four alternatives are evaluated for continued operation of the United States Antarctic Program (USAP). Each alternative involves actions to improve USAP activities and facilities with respect to safety, and environmental and human health protection. The National Science Foundation proposes to implement the third alternative that involves completing an ongoing, 5-year Safety, Environment, and Health Initiative. In addition, that alternative involves streamlining USAP operations by reducing the number of support personnel and by consolidating facilities and activities, in particular at McMurdo Station. Implementation of this alternative includes completing an ongoing materials and waste (solid and hazardous) management study and implementing the study's recommendations where appropriate and feasible. The alternative's source reduction program coupled with a decrease in support personnel would reduce and limit the amounts of material taken to Antarctica in support of scientific research. Also, increased emphasis would be placed on retrograding (removing) wastes from all coastal stations and inland stations

and sites, including Amundsen-Scott South Pole Station. Impacts to air and water quality associated with current operations would be reduced under the proposed alternative. Modifications to wastewater discharges would be completed, and wastewater discharges (and surface water runoff, if any) and their effects would be measured and studied. Land-use plans for USAP facilities would be evaluated and updated on a regular basis, following formalized guidelines. USAP would continue to review its policies and procedures related to antarctic tourism and update them as the need arises. Systematic investigation of deactivated stations and other former sites of United States antarctic activity would be undertaken. The results of these investigations would be used to prioritize remedial actions and to implement cleanups at those sites where the costs and the risks are fully justified.

Research sponsored by the National Science Foundation.

^aEnvironmental Sciences Division.

[7.1.33]**FINAL ENVIRONMENTAL ASSESSMENT,
THE CONSTRUCTION OF A BOUNDARY FENCE AROUND
CHEYENNE MOUNTAIN AIR FORCE BASE, COLORADO**A. K. Wolfe
R. M. ReedR. L. Miller
D. B. Hunsaker, Jr.

(Summary of report, July 1991)

The proposed action in this environmental assessment (EA) is to construct a fence around the entire perimeter of Cheyenne Mountain Air Force Base (CMAFB) property, except where barbed-wire fencing already exists along easement property. The purpose of the fence is to provide a physical demarcation of the CMAFB installation boundary and to enhance security. The EA examines potential impacts of building the boundary fence as well as potential impacts once the fence is in place. The primary construction impacts are related to noise levels, air quality, and effects on wildlife. The major issues associated with the fence once it is in place are impacts on wildlife movement and aesthetics. No significant impacts are likely to occur as a result

of fence construction activities. Also, several mitigative measures (e.g., the use of sprinkler trucks for dust suppression) would be taken to ensure that no significant impacts would occur during construction. Once in place, the fence is unlikely to produce significant impacts. The proposed action includes two mitigative measures as assurance that no significant impacts would occur. First, a vegetative cover would be planted and maintained on patrol paths for erosion control. Second, the Air Force would consider modifications to the fence if evidence of significantly increased road kills of mule deer or disruption of wildlife movement became apparent.

Research sponsored by the U.S. Air Force.

**[7.1.34] CULTURAL RESOURCES OVERVIEW AND MANAGEMENT PLAN
FOR CHEYENNE MOUNTAIN AIR FORCE BASE, COLORADO**A. K. Wolfe
W. R. Arbogast^a

(Summary of report, July 1991)

This cultural resource management plan was prepared to fulfill the Air Force Regulation 126-7 requirement that each U.S. Air Force installation maintain "a current and approved historic preservation plan of appropriate scope." According to the regulation, a plan should (1) assign historic resource recognition and maintenance responsibilities; (2) include inventories and evaluations of known historic resources; (3) scientifically identify the likelihood of the existence of other significant historic resources; (4) describe strategies to maintain historic resources and to comply with Air Force Regulations; (5) coordinate with the installation's mission and identify how continuing mission

functions affect historic resources as well as how such impacts may be resolved; and (6) conform to all relevant local, state, and federal programs. This document is the first cultural resource management plan for Cheyenne Mountain Air Force Base. There were no cultural resource surveys of the installation until this plan was being prepared. At that time, a reconnaissance survey covering the entire installation was conducted (and is reproduced as part of this report), and the results of the survey form the basis for this plan. The survey found virtually no evidence of cultural resource remains on base property. Therefore, the specific objectives of this plan are to (1) document the apparent lack of resources, (2) provide

guidance for additional work that might supply more information about potential cultural and historical resources on the site, and (3) recommend steps to determine if the underground Cheyenne Mountain Complex is

eligible for listing on the *National Register of Historic Places*.

Research sponsored by the U.S. Air Force.

^aSubcontractor.

[7.1.35]

NATURAL RESOURCES MANAGEMENT PLAN CHEYENNE MOUNTAIN AIR FORCE BASE, COLORADO

R. M. Reed
A. K. Wolfe
R. L. Miller

Under Air Force Regulation 126-1, each U.S. Air Force installation is required to develop a continuing management program for restoring, improving, developing, and conserving natural resources. The overall objective of a management program is to protect and enhance environmental quality. Specific objectives are to (1) protect and enhance habitat used by federal- and state-listed, and proposed, endangered and threatened species; (2) manage, conserve, develop, and maintain all natural resources in the best national interest, compatible with military operations and in accordance with multiple use and sustained yield; (3) design management activities to benefit the total environment; (4) provide the greatest net public benefit for the greatest period of time, based upon analysis of prevailing ecological

factors, the supply and demand of the various resources, and their public uses; and (5) conduct all management activities to minimize the Bird Aircraft Hazard potential. This Natural Resources Management Plan has been prepared for Cheyenne Mountain Air Force Base to meet the applicable requirements of Air Force Regulation 126-1 and to update the existing Natural Resources Plan. This plan contains a description of the base's location, mission, and facilities; a description of natural resources on the installation; a land management plan; a forest management plan; a wildlife management plan; and an outdoor recreation plan.

Research sponsored by the U.S. Air Force.

7.2 ABSTRACTS OF ENERGY AND ECONOMIC ANALYSIS SECTION

[7.2.1]

Plastics Recycling: Quantity Projections and Cost Estimates

T. R. Curlee
S. Das

[Abstract of pp. 41-73 in *Materials and Society* 15(1), 1991]

The production and use of plastics are expected to increase at a rapid rate during the coming decade, increasing from an estimated 55 billion pounds in 1987 to almost 72 billion pounds in 2000. Post-consumer wastes are projected to increase from 35.8 billion pounds in 1990 to 48.7 billion pounds in 2000. Plastic packaging is expected to

account for about 46% of all post-consumer plastics during the coming decade and remain by far the largest single contributor to the waste stream. The consumer category with the largest projected percentage increase of packaging consumption is the building and construction sector, which is projected to increase its use from

2.0% of the total in 1990 to 8.0% in 2000. Information on the percentage of manufacturing throughput that becomes a manufacturing "nuisance plastic" was obtained from several industry experts. While there is significant variance between the high and low estimates provided by the experts, estimates of the throughput that becomes a nuisance plastic are generally lower than those used in the most recent published assessments. Recent assessments of the costs and revenues of recycling plastic wastes

suggest that the data are not sufficiently detailed or validated to draw definitive conclusions. Given the caveats, secondary recycling appears to be economically viable only if the appropriate materials are available. In only the most pessimistic cases do the expected costs of recycling exceed the average costs of landfilling.

Research sponsored by the U.S. Department of Energy
Office of Technical and Financial Assistance.

[7.2.2] Identifying and Assessing Targets of Opportunity for Plastics Recycling

T. R. Curlee
S. Das

[Abstract of pp. 343-63 in *Resource Conservation and Recycling* 5 (1991)]

This paper identifies and assesses "targets of opportunity" for additional recycling of plastic wastes. The targets of opportunity are discussed in terms of quantities of plastics wastes that might be affected, the relevant supply-side and demand-side constraints that must be overcome before these targets can be met, and the degree to which meeting these targets might be facilitated by government-sponsored incentive programs or other regulatory measures. For the purposes of

this paper, targets of opportunity are defined as the segments of the plastic waste stream that are most amenable to additional recycling. Several hypothetical scenarios are developed that depict various supply-side and demand-side conditions. In some cases, the supply-side and demand-side assumptions are consistent with current technical, economic, institutional, and regulatory conditions. In other cases, particularly with respect to supply-side constraints, the assumptions represent significant shifts in the ways plastics are collected and processed in the United States. The quantities and types of plastics that could be recycled, given the hypothetical conditions, are estimated. Three broad options exist—each with certain pros and cons. First, would be to promote the collection and recycling of relatively clean plastic waste. Technical constraints and the relative sizes of markets for different resins suggest that a focus on polyethylene terephthalate, and high-density polyethylene packaging is most appropriate. Second, actions can be taken to promote the collection and recycling of commingled plastics. Third, plastics can be collected with other

Plastic waste segmented for recycling value.

combustible wastes and incinerated to recover the heat value of the plastics.

Research sponsored by the U.S. Department of Energy
Office of Industrial Programs.

[7.2.3] World Petroleum Trade Forecasts for the Year 2000

S. Das

[Abstract of p. 10 in *Petroleum Intelligence Weekly* 30(28), July 15, 1991]

This paper provides forecasts of worldwide business-as-usual petroleum trade in the year 2000, taking into account the supply and demand of the Centrally Planned Economies. The forecasts are from a PC-based nonlinear programming mode [Oil Trade Model (OTM)]. For this study, the U.S. Department of Energy's (DOE's) version of OTM was enhanced to include the former Soviet Union, Eastern Europe, and the People's Republic of China as participants in free-market trade. Regional characterizations are limited to a total of 12 regions, with Japan and the Far East representing the Pacific Rim. Based on DOE's forecasts of crude oil supply and product

demand, the forecasts indicate that in most cases current petroleum trade patterns would be maintained in the year 2000. The Middle East would continue to play the major role in crude oil exports, an increase of 7 million barrels per day from its current level. The United States and Canada would be importing crude oil and petroleum products from the U.S.S.R. Eastern Europe would be importing most of its crude oil from the Middle East instead of U.S.S.R.

Research sponsored by the Navy Energy & Natural
Resources Office, Office of Naval Research of the U.S.
Department of Navy.

[7.2.4] Advanced Materials Information Needs: A Survey Report

S. Das
T. R. Curlee

[Abstract of pp. 234-39 in *Ceramic Bulletin* 70(3), 1991]

The Energy Division of Oak Ridge National Laboratory (ORNL) recently completed a study for the U.S. Bureau of Mines (BOM) to assess advanced materials information and analysis needs. As a part of that study, a questionnaire was designed and implemented to assess the opinions of potential users of information on advanced materials. The questionnaire elicited opinions about (1) how advanced materials should be defined, (2) which advanced materials are of greatest interest, (3) how advanced materials differ from traditional materials, and (4) which advanced materials problems and issues are of greatest concern. This paper presents the findings of that questionnaire. From seven suggested components of a definition of advanced materials,

higher strength per density ratios were considered most important. Greater hardness and superior optical properties were considered least important. From 11 categories of advanced materials, composite engineering polymers and structural metals were identified as most important to the sample population. Significantly less importance was given to electronic and optical functional devices, monolithic and composite structural ceramics, and structural engineering polymers. Respondents were asked to comment on numerous potential differences between advanced and traditional materials. There was general agreement that advanced materials are less dependent on supplies of strategic minerals and that because of import

vulnerability we should be focused on processing technology and intermediate products, rather than raw material imports. Respondents agreed that advanced materials require a broader range of expertise and scientific knowledge than do traditional materials. In addition, advanced materials require more emphasis on technology transfer, especially from the public sector to the private sector. The lack of standards for advanced materials, uncertain performance reliability of advanced materials, problems in advanced material fabrication techniques, higher cost of

advanced materials, and the necessity of the U.S. advanced materials industry to compete with foreign competitors were considered to be the major problems facing the advanced materials industry. Limited availability of raw materials used in the manufacture of advanced materials, their ease in recycling, and potential environmental concerns were identified as issues of lesser concern.

Research sponsored by the U.S. Bureau of Mines.

[7.2.5] A Computerized System to Estimate Potential Uranium Resources

S. Das
R. Lee

[Abstract of pp. 201-15 in *Resources and Energy* 13(2), June 1991]

The URAD system is the only comprehensive computerized database for information and estimates of the quantity of undiscovered uranium resources in the United States. The data base includes subjective uranium endowment estimates and geographic and geologic

descriptions for approximately 700 area-specific assessments. The estimated quantity of undiscovered resources are represented in the form of probability distributions. This probabilistic approach makes the uncertainty about these resources explicit. It also relieves

ORNL-DWG 91M-6455

Energy Information Administration uranium (U), assessment data: \$30/lb uranium resources.

users and decisionmakers from the burden of assigning a measure of uncertainty to the assessments.

Research sponsored by Energy Information Administration.

[7.2.6] Residential Time-of-Use Pricing as a Load Management Strategy: Effectiveness and Applicability

L. J. Hill

[Abstract of pp. 308-18 in *Utilities Policy* 1(4), July 1991]

Innovative electricity pricing is increasingly used as a load management strategy by Western utilities. The most common types fall into the general class called time-of-use (TOU) tariffs, which are used alone or in conjunction with other demand-side programs for load management (i.e., to shave peak load or to shift load from peak to off-peak periods). Although they are more widely applied to higher-voltage users, TOU tariffs have proven to be cost-effective for certain types of

residential loads. This paper addresses TOU pricing in the residential sector, discussing customer response to the tariffs, cost-effectiveness, and applicability for implementation by utilities outside of the industrialized world.

Research sponsored by the U.S. Agency for International Development, Office of Energy.

[7.2.7] Large Power Users and Capacity Shortages in Developing Countries: The Role of Innovative Pricing

L. J. Hill

[Abstract of pp. 86-96 in *International Journal of Global Energy Issues* 3(2) (1991)]

This paper addresses innovative electricity tariff pricing as a strategy for managing electric load, offering pricing as an alternative to building generating capacity to meet electric load commitments in the developing world. Drawing upon the Western experience with pricing as a "demand-side" management strategy, three questions are addressed: (1) Do innovative pricing strategies alter the amount and pattern of electricity consumption for high-voltage users?, (2) What are future directions in electricity pricing for industrial users? and (3) Are these strategies relevant for power systems in the developing world? The most widely adopted innovative pricing strategies by Western utilities are variants of time-of-use pricing, which have generally been

effective in reducing load during peak periods. More recently, technological advances have been effective in reducing load during peak periods. More recently, technological advances have allowed utilities to experiment with aligning electricity prices more closely with actual power delivery costs. While short range applicability of these innovative pricing strategies are usually effective as a load management strategy, the power systems in many developing countries have more urgent pricing priorities than can be addressed by adopting the most recent strategies of Western utilities.

Research sponsored by the U.S. Agency for International Development, Office of Energy.

**[7.2.8] Can Developing Countries Benefit from Innovative Pricing
in the Power Sector**

L. J. Hill

[Abstract of pp. 15-25 in *Natural Resources Forum* 15(1) (February 1991)]

This study explores electricity pricing as a demand-side management (DSM) strategy, looking to the Western experience for insights into the types of approaches currently used, their effects, and the direction in which electricity pricing is headed. The discussion should be especially useful for electric utilities in developing countries that are exploring alternatives to capacity expansion for meeting current and future electric power demand. For these electric utilities, demand-side options are

especially important under today's conditions: capital cost of new generating capacity is increasing rapidly, international funds for expanding power sectors are not expected to be sufficient for meeting projected capacity needs, and environmental concerns over fossil fuel emissions have raised new questions about constructing thermal power plants.

Research sponsored by the U.S. Agency for International Development, Office of Energy.

**[7.2.9] Electricity Pricing in Korea: A Case Study of Pricing Initiatives as
Positive Contributors to the Development Process**

L. J. Hill

(Abstract of ORNL-6633, Oak Ridge National Laboratory, October 1990)

The South Korean "economic miracle" of the past three decades has been supported by a corresponding increase in electric generating capacity in a relatively short period of time, accomplished in a country with limited domestic energy resources and large commitments of capital to export-oriented industries. Generating capacity increased nearly 12-fold in a 12-year period during the formative stages of Korea's development from 1962 to 1973, and more than 50-fold from 1962 to the present. For capital- and energy-short developing countries, the Korean experience is a good example of the contribution of pricing-related initiatives to development of the

power sector. Besides setting prices at a level sufficient to provide resources for the power sector, a number of initiatives designed to reduce the cost of electricity supply were implemented. These pricing-related initiatives were a significant source of resources for the power sector during the 1962-73 period. More recently, implementation of time-of-day pricing and enactment of legislation aimed at improving the performance of public enterprises significantly contributed to the efficiency of the power system.

Research sponsored by the U.S. Agency for International Development, Office of Energy.

**[7.2.10] Electricity Pricing as a Demand-Side Management Strategy:
Western Lessons for Developing Countries**

L. J. Hill

(Abstract of ORNL-6620, Oak Ridge National Laboratory, December 1990)

Electric utilities in the Western world have increasingly realized that load commitments can be met, not only by constructing new generating plants, but also by influencing electricity demand. This demand-side management (DSM) process requires that electric utilities promote measures on the customer's side of the meter to directly or indirectly influence electricity consumption thereby meeting desired load objectives. An important demand-side option in achieving these load objectives is innovative electricity pricing, both by itself and as a financial incentive for other demand-side measures. This study explores electricity pricing as a DSM strategy, addressing four questions in the process:

- What is the Western experience with DSM in general and electricity pricing in particular?
- Do other innovative pricing strategies alter the amount and pattern of electricity consumption?
- Do the benefits of these pricing strategies outweigh the costs of implementation?

- What are future directions in electricity pricing?

Although DSM can be used to promote increases in electricity consumption for electric utilities with excess capacity, as well as to slow demand growth for capacity-short utilities, emphasis here is placed on the latter. The discussion should be especially useful for electric utilities in developing countries that are exploring alternatives to capacity expansion to meet current and future electric power demand. For these electric utilities, demand-side options are especially important under today's conditions, in which the capital cost of new generating capacity is increasing, international funds for expanding power sectors are not expected to be sufficient to meet projected capacity needs, and environmental concerns over fossil fuel emissions have raised new questions about constructing thermal power plants.

Research sponsored by the U.S. Agency for International Development, Office of Energy.

[7.2.11] Assessment of Using Oil Shale for Power Production in the Hashemite Kingdom of Jordan

L. J. Hill
R. S. Holcomb^a

C. H. Petrich
R. D. Roop

(Abstract of ORNL-6643, Oak Ridge National Laboratory, November 1990)

Until the present, Jordan has relied almost exclusively on imported petroleum for its primary energy requirements. Encouraged by emerging technologies and recent fossil fuel discoveries, Jordanians are seriously examining exploitation of their own indigenous energy resources to meet projected mid- and long-term power requirements. These resources include (1) potentially significant amounts of natural gas

and some crude oil (both only recently discovered and not yet adequately quantified); (2) large oil shale deposits in at least four sites; and, to a lesser extent, (3) renewable energy forms, including wind, sun, and biomass. Planning for future capacity expansion in the power sector is particularly difficult in Jordan because of uncertainties about the extent of its oil and gas reserves, the costs of exploiting its large oil shale

reserves, and the future price of petroleum. This report addresses the option of using oil shale for power production in Jordan. Under consideration are 20- and 50-MW demonstration units and a 400-MW, commercial-scale plant with a mining operation capable of supplying 7.8 million *tonnes* per year of shale fuel and of disposing of up to 6.1 million *tonnes* per year of wetted ash. The plant would be a direct combustion facility, burning crushed oil shale through use of circulating fluidized bed combustion (CFBC)

technology. The report emphasizes four areas: (1) the need for power in Jordan, (2) environmental aspects of the proposed use of oil shale for power production, (3) the engineering feasibility of using Jordan's oil shale in a CFBC boiler, and (4) the economic feasibility of the proposed plant(s).

Research sponsored by the U.S. Agency for International Development, Office of Energy.

"Engineering Technology Division.

[7.2.12]

A Primer on World and U.S. Foreign Trade

D. W. Jones

(Abstract of ORNL/PPA-90/2, Oak Ridge National Laboratory, June 1991)

In the last 20 years, the prominence of foreign trade has increased, and the United States' large trade deficits of the 1980s have emphasized international competition in both domestic and foreign markets. International competition in high-technology markets has highlighted research and development as a possible element in a national effort to bolster industrial productivity and international competitiveness. This study provides an empirical background on trends in the volume and composition of world and U.S. trade from the late 1970s through the late 1980s, and it reviews the economic and technological bases of foreign trade, with particular emphasis on the role of research and development in promoting foreign trade. The study uses United Nations annual trade data for 1976 through 1987 broken down by

trading partners for all reporting countries with products reported at the 2-digit product code level. For each year, the percentage of world trade accounted for by each product group is calculated. For the United States, more detail is reported. Exports and imports as percents of gross national product are reported, as are trends in composition of imports and exports and patterns of import and export partners. Explanations of the trade deficit of the 1890s are reviewed. Against the empirical background, a number of theories of foreign trade are reviewed, with particular emphasis on the consequences of technical progress for a country's trade balance.

Research sponsored by the U.S. Department of Energy.

[7.2.13] Navy Mobility Fuels Forecasting System Phase VI Report: The Potential Impacts of a Worst-Case Military Conflict on World Petroleum Availability

R. Lee
S. Das
P. N. Leiby

(Abstract of ORNL-6636, Oak Ridge National Laboratory, January 1991)

A major Middle East and European military confrontation would cause an extremely large disruption in the supply of oil worldwide. Supply and demand imbalances could only be solved by

rationing and military actions to ensure an adequate flow of crude oil and products.

Research sponsored by Department of the Navy, Office of Naval Research.

ORNL-Photo 1436-92

Oil wells ablaze during Desert Storm.

[7.2.14]**Greenhouse Gas Emissions in SubSaharan Africa**R. L. Graham^a

R. D. Perlack

A. M. Prasad^aJ. W. Ranney^a

D. B. Waddle

(Abstract of ORNL-6640, Oak Ridge National Laboratory, November 1990)

Current and future carbon emissions from land-use change and energy consumption were analyzed for subSaharan Africa. The energy sector analysis was based on United Nation energy data tapes, while the land-use analysis was based on a spatially explicit land-use model developed specifically for this project. The impacts of different energy and land-use strategies on future carbon emissions were considered. The land-use model predicts carbon emissions from land-use change and the amount of carbon stored in vegetation (carbon inventory) on a year basis between 1985 and 2001. Using current land-use trends, the land-use model results show that three countries (Ivory Coast, Zaire, and Nigeria) contributed over 50% of 1985 carbon emissions from land-use change in subSaharan Africa. If deforestation were to accelerate in Zaire and the other countries of the Congo Basin, land-based emissions from subSaharan Africa could become much more significant in a global context. Of the three land-use options for reducing carbon emissions, aggressive forest protection (total halt of deforestation in conjunction with recovery of degraded forest) would yield the greatest carbon benefit. Widespread adoption of agroforestry would also yield significant reductions in carbon emissions. Establishment of industrial plantation forests, assuming implementation rates comparable to those recommended by the Tropical Forestry Action Plan, are predicted to reduce regional carbon emissions by 5 million tonnes per year. The minimum costs for implementing these options are estimated to range

between \$25 and \$115/ha for preservation, \$50 and \$150/ha for agroforestry, and \$560 and \$1060/ha for industrial plantations. Several general land-use policy recommendations can be made on the basis of these findings, although specific policy recommendations are not appropriate, given the very broad and general scope of this study. First, the Congo Basin of Central Africa shelters an enormous pool of carbon in vegetation. Due to inaccessibility and fairly low population pressures, this pool is still largely intact. However, it could suffer the fate of the Amazon basin with similar carbon emissions if transportation access improves and governments do not reevaluate their overly lenient timber concession policies. Policies that promote the maintenance of this carbon pool such as controlled logging, reforestation, and reduction of agricultural and fuelwood pressures should be pursued. Second, the information base upon which to develop sound specific policies is extremely limited for Central Africa. Development of that information base should take high priority. Finally, as elsewhere in the tropics, deforestation in subSaharan Africa is driven by agriculture, fuelwood needs, and international wood markets. These issues must be addressed if deforestation is to be successfully controlled and reforestation or afforestation implemented.

Research sponsored by the U.S. Agency for International Development, Office of Technical Resources.

^aEnvironmental Sciences Division.

[7.2.15] Energy and Environmental Policy in China

R. D. Perlack
M. Russell

(Abstract of *Annual Review of Energy*, ed. J. M. Hollander et al., Annual Review, Inc., Palo Alto, Calif., May 1991)

China is the third largest energy-consuming country in the world and the largest producer of coal. About three-fourths of its primary energy production is based on coal. Not surprisingly, the use of coal in China pollutes the land, air, and water; it also threatens public health, causes acid rain, and contributes to global warming. The expectation is that coal use will continue to dominate China's energy consumption well into the next century. Publicly, the Chinese have dedicated themselves to improving environmental

quality, and they have made major strides to implement proenvironment policies. The Chinese are emphasizing pollution prevention, as well as technological and managerial interventions (e.g., price reform), that would limit environmental degradation from energy use and cause minimal reduction in economic growth.

Research sponsored by the U.S. Department of Energy
Office of Solar Energy.

[7.2.16] Biomass Energy Development in Yunnan Province, China: Preliminary Evaluation

R. D. Perlack
J. Ranney^a
M. Russell

(Abstract of ORNL/TM-11791, Oak Ridge National Laboratory, June 1991)

A preliminary feasibility study of generating electricity from energy plantations in Central Yunnan Province identified sites with a biomass resource potential of 24,000–45,000 Mg/year (dry) within an effective transportation range. Average annual productivity rates of about 8 Mg/ha (dry) are feasible. This level of feedstock production would be sufficient to fuel a 20-MW conversion plant operating with a margin of safety sufficient to cover all but catastrophic failures. Cost of electricity generation was estimated to be about 0.24 yuan/kWh (\$0.05/kWh), which may be competitive with alternative generation sources. The ancillary economic development benefits are substantial because of the shortages of electricity, so the value of electricity exceeds its cost of production. Environmental effects are also positive, but neither of these benefits are included in this preliminary analysis. In assessing the biomass resource potential, it was concluded that further research (tree crop improvement,

site-species trials, and soil stabilization methods) would be necessary before large-scale deployment to avoid major cost and supply risks and to improve long-run results. This research will require another 5–7 years of effort. Nonetheless, a demonstration project to prove the concept and to gain information required for scale-up appears sufficiently promising to warrant immediate follow-up and a detailed second stage investigation. Seven years would be a reasonable target for the development of an operating facility. The Chinese commitment of support (labor and land) and leadership at all levels is overwhelming, exceeding all pre-site-visit expectations. A limited amount of technical assistance would be helpful in augmenting an already sophisticated and dedicated forestry technical base. External expertise appears to be needed in biomass electricity conversion processes, and much of the most appropriate conversion technology seems to be available only from the United States. A

relatively minor investment in further investigation at this time could open a potentially large market for U.S. technology, the deployment of which would have substantial local and global environmental benefits as well as economic benefits.

Research sponsored by the U.S. Department of Energy, Biofuels Systems Division.

*Environmental Sciences Division.

[7.2.17] A Survey of Energy Technologies for Rural Applications

R. D. Perlack
H. M. Jones^a
D. B. Waddle

[Abstract of *The International Journal* 15(12), 1990]

The availability of modern energy has long been recognized as one of the requirements for rural economic development. Recent advances in renewable energy technologies have broadened their applicability despite the recent decline in world oil prices. This paper summarizes the technology status of renewable energy technologies—photovoltaics, wind energy, hydro, and biomass technologies—that are considered

appropriate for rural areas. In addition, the paper discusses the economic and institutional constraints that inhibit their widespread dissemination in rural areas.

Research sponsored by the U.S. Agency for International Development, Office of Energy.

^aOak Ridge Associated Universities.

[7.2.18] Analysis of Military Occupational Specialty in Army National Guard Units

C. G. Rizy
D. J. Bjornstad
D. P. Vogt

(Abstract of ORNL/TM-11680, Oak Ridge National Laboratory, August 1991)

In its initial phase of development, the Oak Ridge National Laboratory Army National Guard Regional Recruiting Potential Model addressed the supportability of a "generic unit." But it did not address the supportability of a specific type of unit (e.g., engineers, medical corps, infantry), as would be reflected in different mixtures of military occupational specialties (MOSs), and potentially limited by the availability of persons within the market area with the skills necessary to fill these positions. The Reserve Components Common Personnel Data System was used to conduct a five-step analysis: (1) Guard units were

classified by type and class (combat, support, or service); (2) the MOS profile of Guard membership was discerned; (3) skill level, special qualification identifiers, and additional skill identifiers were determined; (4) unit type versus MOS mix was investigated; and (5) Guard members were classified by their civilian occupation classification [as defined in the *Dictionary of Occupational Titles* (DOT)]. The analysis revealed, that almost 50% of National Guard units are in the combat class; 94% of Guard members are men; and the majority of Guard members have no special qualifications beyond

those required for award of their primary MOS. Additionally, in the analysis of unit type versus MOS mix, five unit types were found to have "special" MOS mixes in the sense that within each of these five unit types, there is one MOS or a small number of MOSs that comprises a large proportion of membership within that unit type; however, these MOSs are not generally among the top MOSs in other unit types. Furthermore, the *Military Occupational Classification and Structure* suggests related civilian occupations, as

defined in the DOT, for each MOS. When the civilian jobs of Guard members in the "special" MOSs are classified in detailed, disaggregated categories, the relationship between actual civilian jobs and suggested civilian jobs is not a strong one. However, the relationship looks stronger when civilian jobs are classified in broad occupational categories.

Research sponsored by the Army National Guard Bureau.

[7.2.19] Feasibility Study to Update Annualized Cost of Leaving (ACOL) Procedures at the Navy Personnel Research and Development Center (NPRDC)

D. A. Trumble
D. M. Flanagan^a

(Abstract of ORNL/TM-10613, Oak Ridge National Laboratory, December 1990)

Accurate forecasts of officer retention rates are required in order to shape correctly the size and internal structure of the Navy manpower force through accession, promotion, and related policies. This study, conducted in 1987 for NPRDC, reviews existing forecasting and simulation methodologies and suggests methods for future implementation to improve forecasts of naval officer retention rates. The study also considers alternative sources of data to capture civilian earnings opportunities in the models.

Two major types of models—ACOL and Dynamic Retention—are discussed in detail with respect to the ability to emulate and evaluate manpower policies to NPRDC staff. A variety of other techniques that should be considered during the estimation of salaries stage are also discussed.

Research sponsored by the Navy Personnel Research and Development Center.

^aEngineering Physics and Mathematics Division.

[7.2.20]**Emissions of CO₂ from Energy Crop Production**

A. F. Turhollow

R. D. Perlack

(Abstract of *Biomass and Bioenergy*, May 1991)

Estimates of CO₂ emissions in kg C dry Mg⁻¹ of biomass under present and likely future production technology (with biomass yields in dry Mg ha⁻¹ in parenthesis) are hybrid poplar, 26.5

(11.3) and 21.9 (18.5); sorghum, 31.1 (13.3) and 21.8 (30.2); and switchgrass 32.3 (9.0) and 29.2 (14.4). The lower yield for each energy crop can be achieved today, while the potential exists to reach the higher yield; and under some circumstances the higher yield can be reached today. On a kg C GJ⁻¹ basis, CO₂ emissions from energy crops range from a high of 1.85 for switchgrass to a low of 1.11 at the higher yield for hybrid poplar. These carbon releases are considerably lower than emissions from fossil fuels, which on a kg C GJ⁻¹ basis are 13.78, 22.29, and 24.65 for natural gas, petroleum, and coal, respectively.

Carbon dioxide (CO₂) emissions from the production, transport, and combustion of energy crops are much lower than CO₂ emissions from fossil fuels.

Research sponsored by the U.S. Department of Energy Office of Conservation and Renewable Energy.

7.3 ABSTRACTS OF CENTER FOR TRANSPORTATION ANALYSIS**[7.3.1]****Information Technology and Global Change Science**

F. P. Baxter

(Abstract of *Proceedings of the Conference on Global Change: Economic Issues in Agriculture, Forestry, and Natural Resources*, U.S. Department of Agriculture, Washington, D.C., November 21, 1990)

Desktop computer systems have changed dramatically during the past 7 years. Data processing will become even faster in the future, through full development of traditional serial computer architectures. Some other proven

information technologies may be currently unfamiliar to global-change scientists. This paper identifies and briefly describes major existing and near-term information technologies that could have a positive impact on the topics discussed at

this conference, by helping to manage the data and research of global-change scientists. Relational data base management systems and good organization through thoughtful design would enable the scientific community to better share and maintain quality research data. Custodians of the data should use rigorous administration to ensure integrity and long-term value of the data resource. Still other emerging information technologies that involve artificial intelligence, parallel computer architectures, and new sensors for data collection will soon be in relatively

common use and should become part of the global-science community's technical tool kit. Consideration should also be given to the establishment of Information Analysis Centers to facilitate effective management of interdisciplinary data and prototype testing of advanced information technology to encourage rapid, cost-effective integration of these tools into global-change science.

Research sponsored by the Department of Energy Office of Policy, Planning, and Analysis.

[7.3.2] **Increasing the Pool of Transportation Engineers**

M. S. Bronzini
J. P. Tarris^a

J. M. Mason^a
E. Zaki^a

(Abstract of *Proceedings of the 61st Annual Meeting of the Institute of Transportation Engineers*, Milwaukee, September 22-25, 1991)

This paper reports on the project entitled "Expanding the Civil Engineering Pool." The research has documented practices and attitudes in the career-choice decision-making process among students in U.S. schools. Information was collected from state transportation agencies and approximately 200 college and university civil engineering technology departments in the United States. A variety of identified programs provide career-choice information to students from kindergarten through grade 12, although they predominantly focus on junior and senior high-school age groups. Many of the programs target currently under-represented groups; however, in comparison to the numerous "general" programs, few specific civil engineering orientation programs exist at any precollege level.

A series of focus group interviews identified attitudes and expectations about engineering as a career alternative. A marketing research team conducted the sessions with junior and senior high school students, college students, parents, teachers, guidance counselors, college faculty, and practicing civil engineers. This technique yielded insights necessary for initiating a successful marketing program. The recommended strategies address public awareness, student retention, and curriculum modifications for grades kindergarten through 12, precollege, and college students.

Research sponsored by the U.S. Department of Energy.

^aThe Pennsylvania Transportation Institute, Pennsylvania State University.

[7.3.3] **Transportation Energy Data Book: Edition 11**

S. C. Davis
P. S. Hu

(Abstract of ORNL-6649, Oak Ridge National Laboratory, January 1991)

The *Transportation Energy Data Book: Edition 11* is a statistical compendium prepared and

published by Oak Ridge National Laboratory (ORNL) under contract with the Office of

United States petroleum production and consumption, 1970-89.

Transportation Technologies in the Department of Energy. Designed for use as a desk-top reference, the data book gathers statistics and related information that characterize transportation activity, and presents data on other factors that

influence transportation energy use. The purpose of this document is to present relevant statistical data in tables and graphs. Each of the major transportation modes—highway, air, water, rail, pipeline—is treated in separate chapters or sections. Chapter 1 compares U.S. transportation data with seven other countries. Aggregate energy use and energy supply data for all modes are presented in Chap. 2. Chapter 3 treats separately the highway mode, which accounts for over three-fourths of total transportation energy consumption. Topics in this chapter include data regarding automobiles, trucks, buses, fleet automobiles, federal standards, fuel economies and households. Chapter 4 is a new addition to the data book series, containing information on alternative fuels and alternatively fueled vehicles. Finally, Chap. 5 covers energy consumption in each of the nonhighway modes: air, water, pipeline, and rail, respectively.

Research sponsored by the U.S. Department of Energy, Office of Transportation Technologies.

[7.3.4]

Short-Run Pricing Strategies to Increase Corporate Average Fuel Economy

D. L. Greene

(Abstract from article in *Economic Inquiry*, Vol. 29, pp. 101-114, January 1991)

In 1974, the fuel efficiency of new automobiles sold in the United States reached a low of 14.2 mpg. Close on the heels of the Arab-Organization of Petroleum Exporting Countries oil embargo of 1973-74 and the ensuing high petroleum price increases, Congress passed the 1975 Energy Policy and Conservation Act. The new law required manufacturers to individually meet Corporate Average Fuel Economy (CAFE) standards of 18 mpg in 1978, increasing each year to 27.5 mpg in 1985. The expressed purpose of the CAFE standards was to stimulate efficiency improvements by means of improved technology. The option of raising prices of the least energy efficient models was considered as a strategy to meet the standards, but

only as a last resort. This paper explores a method of estimating the costs of achieving fuel economy goals by increasing consumer prices on some car models. The method employs the "closed form equation for consumers' surplus" derived from the multinomial logit model of discrete automobile choice (McFadden 1973), and assumes that manufacturers must bear the full cost of meeting the miles per gallon (mpg) target. The estimated cost represents a ceiling on the losses firms would incur by setting prices to minimize loss of profit. Using estimates from the economic literature on the relationship of vehicle choice to vehicle price, together with market shares and efficiencies for 1986, the method produces costs of short-term mpg improvements in pricing strategies for

General Motors, Ford, and Chrysler. Minor adjustments of up to 1 mpg cost 1-2% of the price of a \$10,000 car. For improvements of 2 mpg or more, however, increasing prices is apparently a costly way for the manufacturer to improve fuel economy. The analysis also estimates the market

shares for each car line corresponding to their particular pricing strategy. The study thereby identifies the car lines that would be most affected.

Research sponsored by the U.S. Department of Energy, Office of Policy, Planning and Analysis.

ORNL-DWG 92M-6358

Pricing strategies in dollars to cover manufacturer's cost of meeting 1985 corporate average fuel economy (CAFE) standard of 27.5 miles per gallon (mpg).

[7.3.5]**Survey of Data Compression Techniques**

R. K. Gryder
K. A. Hake

(Abstract of ORNL/TM-11797, Oak Ridge National Laboratory, November 1990)

This report examines the current status of data compression technology and assesses its applicability to the Defense Secure Network Level 1 (DSNET1). Optimizing a packet-switched network (X.25) may involve the use of data compression techniques. However, data encryption devices complicate the use of this tool. The rapidly changing field of data compression must be periodically assessed to determine if it is viable for networks, especially those undergoing technology refreshment. Computerized on-line data base searches, CD-ROM-based literature searches, and follow-up telephone interviews were used to rapidly acquire information on data compression. This information was compared with the accelerator improvement and modification DSNET1 integration plans to determine potential data compression solutions. The

address information is part of each packet header prepared by the networking software running in the host computer. For the addresses to be preserved, the compression must either take place before execution of the software that prepares the packets for the network, or it must be done so that the address and control information is preserved, and only the data are encoded. Neither of these options is possible with existing hardware data-compression devices. Data compression must be accomplished through data base design, reduction in the frequency of data base updates, or through distribution of partial updates.

Research sponsored by the U.S. Department of the Army, Acquisition Office of the Product Manager, Acquisition Information Management.

[7.3.6] Ultra Low Sulphur Diesel Fuel Impacts on Availability of Other Fuels

G. R. Hadder S. Das
R. Lee N. Domingo^a
R. M. Davis^b

[Abstract of pp. 488-93 in *Energy Policy* 19(5), June 1991]

Legislation for ultra low sulfur (ULS) diesel fuel, with a greatly reduced allowable sulfur content and a new limit on aromatics content, is expected in the United States by 1995. The ULS diesel fuel has been specified to satisfy U.S. standards for particulate emissions from heavy-duty diesel engines. The Navy Mobility Fuels Forecasting System was used to study the impacts of ULS diesel fuel production on other refined petroleum products. The study predicts that to produce ULS

diesel fuel, U.S. Gulf and West Coast refiners will have to invest about \$4.4 billion in new processing capacity. Refiners will shift aromatics from No. 2 diesel fuel to jet fuel and No. 2 fuel oil. Therefore, particulate emissions could be transferred from the highways to the airways, as well as to communities using No. 2 fuel oil for residential and commercial heating. The study also predicts an increase in the aromatics content of Navy JP-5 jet fuel and F-76 marine diesel fuel

produced in the United States. The gum-forming tendencies of F-76 and F-77 burner fuel oil will increase in most cases, but the freezing point of JP-5 will improve. There will be minor changes in the cost of JP-5 but sizable reductions in the cost of F-76 and F-77.

Research sponsored by the U.S. Navy Energy and Natural Resources R&D Division, Office of Naval Research.

^aEngineering Technology Division.

^bCentral Management Offices.

Transportation center researchers developed the Navy Mobility Fuels Forecasting System to examine the regulations on the availability and quality of Navy fuels.

[7.3.7] Navy Mobility Fuels Forecasting System Report: Navy Fuel Production in the Year 2000.

G. R. Hadder
R. M. Davis^a

(Abstract of ORNL-6684, Oak Ridge National Laboratory, September 1991)

The Navy Mobility Fuels Forecasting System was implemented to study fuel production scenarios in the year 2000 and in the reference year 1990. The forecasting system consists of the Oil Trade Model (OTM) and the Refinery Yield Model (RYM). OTM is a personal computer-based, static, nonlinear programming model that balances petroleum supply and demand by maximizing consumer and producer surpluses, as constrained by world petroleum refining and distribution capabilities. Crude oil supplies and the production of refined products are forecast by OTM for input to the RYM. RYM is a personal computer-based linear program that represents regional refining operations. RYM includes 37 refinery processes, which can be used to produce

over 30 products from at least 100 crude oils. Most of the RYM petroleum products are described by detailed quality specifications. Study results suggest the following for both year-2000 scenarios: (1) JP-5 availability will be adequate to meet peacetime requirements; (2) the aromatics content of JP-5 produced in the United States will increase, but with no serious quality degradations compared to 1990; (3) based on increased production costs, F-76 availability could be relatively tight compared to 1990; (4) the aromatics content of F-76 produced in the United States and in the Middle East will increase and there will be a large increase in light cycle oils blended with F-76 in the Middle East. Light cycle oils can cause plugging of diesel engine filters and

fouling of fuel injectors; and (5) as a result of Clean Air Act restrictions, aromatics will be shifted from domestic motor gasolines and highway diesel fuel to Navy fuels and home heating oil. Pollutant emissions of home-heating oils could increase because of higher percentages of aromatics. In the year-2000 scenario postulating low oil production in the former U.S.S.R., coupled with otherwise business-as-usual conditions, results suggest that there will

be: (1) no adverse effects on the availability of Navy fuels, (2) degradations of JP-5 smoke and freezing points in several domestic regions, and (3) no adverse effects on the quality of F-76.

Research sponsored by the U.S. Department of the Navy, Office of Naval Research, Navy Energy and Natural Resources Office.

*Central Management Offices.

[7.3.8] An Examination of Electronic File Transfer Between Host and Microcomputers for the AMPMODNET/AIMNET Classified Network Environment

K. A. Hake

(Abstract of ORNL/TM-10874, Oak Ridge National Laboratory, November 1990)

This report presents the results of investigation and testing conducted by Oak Ridge National Laboratory for the Project Manager-Acquisition Information Management and the U.S. Army Materiel Command Headquarters. It concerns the establishment of file transfer capabilities on the Army Materiel Plan Modernization (AMPMOD) classified computer system. A new, secure hardware and telecommunications environment was installed to run two initial applications as well as expected enhancements. In addition, Tempest microcomputers (TPC3s) were included in the AMPMOD system in 1986, establishing a requirement for full microcomputer to mainframe computer interaction. This meant going beyond terminal interaction with a host to allow information stored on floppy disks or removable data cartridges of the TPC3 to be transferred to AMPMOD host computers (IBM 4381s) Direct Access Storage Device. The study demonstrated the feasibility of file transfer between an AMPMOD host and its attached TPC3

microcomputers and among AIMNET-attached TPC3 or DOS-based microcomputers using the Distributed Office Support System e-mail. The most effective throughput was seen in the time-share option (TSO) environment. A file the size of a double-sided, double-density 1/4-in. floppy was transferred in 20-25 min over a 4800 baud line. This system, however, is geared for a more sophisticated computer user and requires host security access to TSO not normally afforded an AMPMOD user. This includes specification of TSO-capable terminals on a remote cluster controller defined in the operating system "gen." It also requires direct user privilege for host dataset creation and deletion. The command-line interface is meant for a user who understands concepts of computer file structure and storage.

Research sponsored by the U.S. Army Materiel Command, Acquisition Information Management.

[7.3.9] Light-Duty Vehicle Summary: First Six Months of Model Year 1991

P. S. Hu

(Abstract of ORNL-6672/S1, Oak Ridge National Laboratory, August 1991)

As part of the U.S. Department of Energy, Oak Ridge National Laboratory Conservation and Renewable Energy Program, this supplement reports sales-weighted fuel economies, market shares, and vehicle characteristics of the new light-duty vehicle fleet for each model year. The reporting period for this issue is from model year 1976 to the first 6 months of model year 1991. Detailed information on individual new vehicles is kept on computer files, which is updated with quarterly sales data on a regular basis for use as factors in a sales-weighted estimation procedure. Model year 1991 fuel economies are weighted averages based on the sales in the first 6 months

of the period (October 1990–March 1991). Two of the most popular sizes (compact and midsize) showed fuel economy declines from model year 1990. A 0.4 mpg gain in the increasingly popular subcompact class compensated for the losses experienced by the compact and midsize classes. Consequently, the overall 1991 fuel economy of all new automobiles remained relatively stable compared to the 1990 figures: 27.6 mpg in model year 1990 and 27.5 mpg for the first half of model year 1991. Unlike automobiles, new light trucks showed an overall 0.2 mpg gain from model year 1990, primarily due to the increased fuel economy of the small light truck size class. In the first half

ORNL-DWG 91-14582

^a Represents sales of the 1st six months of 1991

Market shares of domestic and import automobiles of selected manufacturers for selected model years.

of model year 1991, small light trucks gained an additional 0.4% of their class market. The overall 1991 fuel economy for the entire light-duty vehicle fleet remained approximately the same as for model years 1989 and 1990.

Research sponsored by the U.S. Department of Energy
Office of Transportation Technologies.

[7.3.10] A Study of Interstate Motor Carrier Vehicle Miles of Travel

P. S. Hu
S. P. Miaou
T. Wright^a
R. Gorman^b
S. C. Davis

(Abstract of article in *Transportation Research A*, Vol. 25A, No. 6, 1991)

This paper summarizes the evaluation results of six data sources in terms of their viability for quantifying the number of commercial trucks operating in interstate commerce and their vehicle miles of travel by carrier type and by state. This study also presents two cost-effective methodologies for estimating these parameters based on the evaluations. The six data sources are:

- Truck Inventory and Use Survey from the Bureau of the Census;
- Nationwide Truck Activity and Commodity Survey from the Bureau of the Census;
- National Truck Trip Information Survey from the University of Michigan Transportation Research Institute;
- Highway Performance Monitoring System from the Federal Highway Administration, Department of Transportation;

- International Registration Plan of the American Association of Motor Vehicle Administrators, and;
- State fuel tax reports from each individual state and the International Fuel Tax Agreement.

Evaluation results concluded that none of the data sources *by themselves* were capable of providing reliable estimates of operating vehicles at the *state* level. Although several attempts were made to combine the strengths of different data sources so that reliable estimates could be generated, none of them were successful. Data inconsistency and incompatibility contributed to the failures.

Research sponsored by the U.S. Department of
Transportation, Federal Highway Administration.

^aEngineering Physics and Mathematics Division.

^bDepartment of Transportation, Federal Highway
Administration.

[7.3.11] Highway Vehicle MPG and Market Shares Report: Model Year 1990

L. S. Williams^a
P. S. Hu

(Abstract of ORNL-6672, Oak Ridge National Laboratory, May 1991)

This issue of *Highway Vehicle MPG and Market Shares Report: Model Year 1990* reports the estimated sales-weighted fuel economies, sales, market shares, and other vehicle characteristics of

new automobiles and light trucks. The estimates are made for each make and model (e.g., Chevrolet is a make and Corsica is a model), from model year 1976 to model year 1990. Vehicle

sales data are used as weighting factors in the sales-weighted estimation procedure. Thus, the estimates represent averages of the overall new vehicle fleet, reflecting the diverse composition of the fleet. Highlights are provided on the trends in the vehicle characteristics from one model year to the next. Analyses are also made on fuel economy changes to determine what caused the changes. The new automobile fleet of 1990 experienced a fuel economy loss of 0.4 mpg from the previous model year, dropping to 27.6 mpg. This is the second consecutive decline in the fuel economy of new automobiles since model year 1983. The main reason for the fuel economy decline in automobiles was that the compact, midsize, and large-size classes, which together claimed more than 75% of the new automobile market, each experienced fuel economy declines of 0.4 mpg or more. In contrast, the new light truck fleet showed an increase of 0.3 mpg from the previous year (1989) to a current mpg of 20.5. The fuel economy increase in light trucks was due primarily to the fact that the large pickup class, which represents 35.0% of the new 1990 light truck market, experienced a gain of 0.7 mpg in its fuel economy. Overall, the cost effective fuel economy of the new light-duty vehicle fleet (automobiles and light trucks) dropped to 24.8

Note: Motorcycles (50.0 mpg) are excluded from chart.

Average MPG of vehicle stock by vehicle type, 1987.

mpg in model year 1990, a reduction of 0.2 mpg from model year 1989. Total sales of light-duty vehicles in 1990 fell 8% from the previous year, reaching a record low of 13.7 million units (based on data since 1983). Automobile sales dropped for the fourth consecutive year. The trend of light trucks gaining a larger portion of the entire new light-duty vehicle market continued, reaching a record high of 33.0% in model year 1990. Increased fuel economy performance influenced sales of the light-duty fleet, especially light trucks.

Research sponsored by the U.S. Department of Energy, Office of Transportation Technologies.

^aThe University of Tennessee, Knoxville.

[7.3.12] Modified Seasonal Factors in Exponential Smoothing

J. S. Armstrong^a
H. L. Hwang
J. Bandy^b

(Abstract of ORNL/TM-1262, Oak Ridge National Laboratory, October 1991)

Current practice uses statistical tests to determine whether seasonal factors should be applied in a given forecasting situation. Research suggests that an optimal policy might lie somewhere

between using full seasonal factors and using no seasonal factors on series. This research proposes and tests use of a modified seasonality factor. Modified seasonal factors reduce the emphasis on

the seasonal adjustments when forecasts are made. The adjustments account for errors in the estimation of the seasonal factors and for possible changes in the factors over the forecast horizon. An analysis of data from U.S. Navy personnel inventories was conducted to test the use of a modified seasonality factor.

For predictions of inventories by pay grade, using quarterly data from the Navy Personnel Research and Development Center, modified seasonal factors led to improved accuracy. Under certain selections of factors, the mean absolute percent

error was reduced by 4.4%. No gain was obtained, however, for the inventories by length of service. It is expected, but not shown here, that the modified seasonal factors will only be of value for series where the estimated seasonal factors show a substantial variation across the year.

Research sponsored by Navy Personnel Research and Development Center.

^aUniversity of Pennsylvania.

^bUniversity of Tennessee.

[7.3.13] Meeting the Military Airlift Command's Airlift Scheduling Challenge

R. D. Kraemer
M. R. Hilliard
Lt. Col. C. Davis^a

[Abstract of article from *Airlift* (The Journal of the Airlift Operations School), 8(2), pp. 2-4, Summer 1991]

To meet its scheduling challenge, the Military Airlift Command (MAC) combined in-house operations research and systems management staff with a new airlift scheduling tool: the Airlift Deployment Analysis System (ADANS). ADANS provides a set of tools to manage the requirements and the resources (aircraft, airfields, crews) needed to move the cargo, as well as tools to generate missions, analyze the schedule, and distribute the schedule to MAC's command and control system. Although some of the peacetime

scheduling tools were in place when Iraq invaded Kuwait on August 2, 1990, ADANS wartime execution tools were still on the drawing board or in the early stages of development. Application of the software to a real-world deployment in a time-critical environment was a massive endeavor.

Research sponsored by Military Airlift Command.

^aMilitary Airlift Command.

[7.3.14] Providing Dynamic Sorting and Searching Capabilities Using SQL*FORMS

J. P. Loftis

(Abstract of partial *Proceedings of the International ORACLE Users Group*, pp. 303-310, Anaheim, Calif., September 23-28, 1990)

This paper describes two techniques being used for a prototype software system—ORACLE's SQL*Forms—under development at Oak Ridge National Laboratory (ORNL) that provide easy interactive capability between the user and the data base. The first technique demonstrates how to build an ORACLE application that allows users

to decide whether they would like a subset of data retrieved to a multirecord display form and, if so, to define the boundaries for the subset. The second technique allows users to choose how these displayed data will be sorted. Neither of these techniques requires the user to understand SQL or

the underlying data base structure of table and column names.

Research sponsored by the U.S. Department of Defense,
Military Traffic Management Command.

[7.3.15] A Flexible User Interface Developed Using SAS/AF and SAS/Graph

J. P. Loftis
T. L. James^a

(Abstract of partial *Proceedings of the SAS Users Group International 16th Annual Conference*,
pp. 1000-1005, New Orleans, February 18, 1991)

Oak Ridge National Laboratory was asked by the Military Traffic Management Command's Personal Property Directorate (MTPP) to design and prototype a decision support system to quickly and easily locate and display data for assistance in evaluating and monitoring the Personal Property Program. This paper describes the user interface developed in SAS/AF and SAS/GRAPH that comprises this system and explains how the SAS user interface works with an ORACLE interface. The primary goal in the design of this interface was to develop a set of screens and windows that could be used by MTPP

staff to produce an almost infinite variety of reports. This single feature allows even inexperienced users to quickly and easily produce the charts and tabular output the users need to perform their jobs. It also discusses the goals of the SAS user interface and describes the screens and pop-up windows developed for the interface and explains how these screens achieve the system goals.

Research sponsored by the U.S. Department of Defense,
Military Traffic Management Command.

^aThe University of Tennessee.

[7.3.16] Computing κ -Shortest Path for Nuclear Spent Fuel Highway Transportation

S. P. Miaou
S. M. Chin

(Abstract of article from *European Journal of Operational Research*, Vol. 53, No.1, pp. 64-80, July 1991)

Four κ -shortest path algorithms were used to select a set of optimal routes for transporting nuclear spent fuel on the U.S. Interstate Highway system. Six nuclear reactors and two potential repository sites distributed over the United States were selected to evaluate the computational performance of each algorithm under different origin and destination pairs in the highway network. The first two algorithms compared the relative efficiency of maintaining a "priority

queue" under two management systems, namely a linear search and a binary heap. The third was an adaptive algorithm that exploited the knowledge of the Euclidean distances between nodes to reduce search effort. Its effectiveness in determining the κ -shortest path was examined in terms of both computation time and its capability to identify the correct paths. Finally, a simple (or loopless) path algorithm was introduced for situations when a large set of simple paths is

needed. This simple path algorithm required only a minor modification of the κ -shortest path algorithm.

Research sponsored by the U.S. Department of Energy.

ORNL-DWG 92-6202

Turkey Point Nuclear Power Plant, FL
to
Hanford Repository Site, WA

The relationship between computation time and the number of paths (κ) for three algorithms examined.

[7.3.17]

An Error Detection and Correction Strategy for a Decision Support System

V. Ng

(Abstract of ORNL/TM-11749, Oak Ridge National Laboratory, June 1991)

Decision support systems (DSSs) require data generated from external sources. To be effective, a DSS needs a good data quality management program to ensure that every user has quality data on which to base his or her decisions. Hence, complete data integration is very important in such a system. A major issue for data integration is that given one or more objects that contain members with distinct keys one must be able to determine with some fair degree of certainty:

- whether two members from different objects having distinct keys (due to errors) are indeed functional duplicates, and

- whether two members from different objects having the same keys (due to errors) are actually functionally discrete.

In this paper, an error detection and correction strategy based on distance measures with weights is proposed for data integration. A real application example developed for the Worldwide Household Goods Information System for Transportation Modernization project for the Personal Property Directorate of the Military Traffic Management Command is also presented.

Research sponsored by the U.S. Department of Defense, Military Traffic Management Command.

[7.3.18] Description of the National Highway Planning Network

B. E. Peterson

(Abstract of ORNL/TM-11553, Oak Ridge National Laboratory, September 1991)

The National Highway Planning Network is a data base of major highways in the continental United States. Its network data are for analytic studies of highway performance, for vehicle routing and scheduling problems, and for mapping purposes. The network data consist of a set of roadways digitized from the National Atlas by the U.S. Geological Survey. It has been enhanced at Oak Ridge National Laboratory with additional roads

and attribute detail. Topological errors are then corrected to produce a true analytic network. This documentation is intended primarily to assist users of this data base by describing its structure and implementation.

Research sponsored by the U.S. Army Forces Command and the Department of Transportation, Federal Highway Administration.

[7.3.19] Traffic Metering: An Effectiveness Study

A. K. Rathi

(Abstract of article from *Transportation Quarterly Journal*, Vol. 45, No. 3, pp. 421-440, July 1991)

This paper describes the results of a study used to evaluate metering traffic at the periphery of a congested urban grid. Traffic operations before and after the implementation of metering control at the periphery of a high-density sector in mid-Manhattan are simulated using the TRAF-NETSIM model. Several metering control policies with varying metering rates and locations are analyzed. The results of this simulation study suggest that peripheral metering has the potential to improve the overall performance of traffic in a

highly congested urban area. Metering control proves to be essential along the periphery of an urban area that is so congested that the ensuing traffic demand causes overflow lines that back up the streets. The study also shows that the optimal metering control policy choice will vary, depending upon the traffic condition.

Research sponsored by the U.S. Department of Transportation, Federal Highway Administration.

[7.3.20] ITDS: Past, Present, and Future

A. K. Rathi
A. J. Santiago^a
D. E. Valentine^b

(Abstract of article from *ASCE Journal of Transportation Engineering*, TE6-13, pp. 799-808, November-December 1990)

Integrated Traffic System (ITDS) is a PC-based system that is designed to allow traffic engineers to store, maintain, and update traffic network information in a centralized data base. This information can then be used to create input data files for some of the widely used traffic simulation and network signal-timing optimization models.

ITDS uses the data base management concept to provide a friendly front-end (or preprocessor) to models such as TRAF-NETSIM and TRANSYT-7F. Interactive and static graphics displays have been added to further simplify the task of the users. The interactive graphics displays allow the user to enhance or modify the network

Concept of the Integrated traffic data system (ITDS).

geometry, including a detailed depiction of all the traffic data. This paper describes the evolution and current status of ITDS, while anticipating completion.

Research sponsored by the U.S. Department of Transportation; Federal Highway Administration.

^aOffice of Traffic Safety and Operations Research and Development, Federal Highway Administration.

^bTransportation Center, The University of Tennessee.

[7.3.21] Urban Network Simulation Model: TRAF-NETSIM Program

A. K. Rathi
A. J. Santiago^a

(Abstract of article from *ASCE Journal of Transportation Engineering*, TE6-13, pp. 734-803, November-December 1990)

NETSIM (for NETWORK SIMulation program) is now a component model of the TRAF simulation system. The current version of the model is therefore referred to as the TRAF-NETSIM program. As part of an effort aimed at developing, maintaining, and supporting the TRAF simulation system, TRAF-NETSIM has been extensively modified over the past 5 years. Four new features have been added to the TRAF-NETSIM program: actuated controller logic, identical traffic streams, conditional turning movements, and signal transition. Several major modifications have also been made to the simulation logic to resolve the problems encountered during the testing of the

simulation program; to enhance the logic to represent more complex decision processes; and to enhance and extend the input-output capabilities, user interaction, and computational efficiency of the program. These new features in the TRAF-NETSIM simulation model receive closest attention.

Research sponsored by the U.S. Department of Transportation, Federal Highway Administration.

^aOffice of Traffic Safety and Operations Research and Development, Federal Highway Administration.

[7.3.22] An Execution Planning Algorithm for Military Airlift

R. S. Solynki
F. Southworth

(Abstract of article in *Interfaces*, July-August 1991)

Execution planning at the Military Airlift Command (MAC) of the U.S. Air Force involves updating the routes and schedules of aircraft to reflect the changing status of the movement requirements and the airlift resources. The scheduling issues are primarily those of pickup and delivery, with time windows and node capacities. The constraints on planning depend on the capacities of the airlift nodes (airfields limit the rate at which the aircraft can be serviced) and the amount of requirements (tonnage of cargo, number of passengers) loaded or unloaded at an

airfield per day. The execution planning algorithm described can be used each day to modify the existing airlift operations plan. An algorithm based on the insertion heuristic was selected for implementation due to its computational feasibility and its capability to absorb complex constraints arising in the execution planning problem. The insertion heuristic has the additional desirable feature of keeping intact as much of the existing schedule as possible.

Research sponsored by Military Airlift Command.

[7.3.23] Regional Evacuation Modeling: A State of the Art Review

F. Southworth

(Abstract of ORNL/TM-11740, Oak Ridge National Laboratory, March 1991)

Regional evacuation modeling is treated as a five-step process involving vehicle trip generation, trip departure time, trip destination, and trip route selection modeling, supplemented by separate plan start-up and analysis procedures. Progress under each of these headings is reviewed and gaps in the process identified. The potential for emergency planners to make use of real-time traffic data, resulting from the recent technical and economic revolutions in telecommunications and infrared traffic sensing, is identified as the single greatest opportunity for the near future; and some developments in real-time dynamic traffic modeling that advance evacuation planning are also highlighted. A second area requiring extensive research covers significant data

problems associated with the time-of-day location of large urban populations. A third area requiring much additional effort is the translation of the considerable knowledge we have on evacuee behavior in times of crisis into reliable quantitative measures of the timing of evacuee mobilization, notably by distance from the source of the hazard. Specific evacuation models are referenced and categorized by method. Incorporation of evacuation model findings into the definition of emergency planning zone boundaries is also discussed.

Research sponsored by the U.S. Army, the Federal Emergency Management Agency, and ORNL Director's Research and Development Fund.

[7.3.24] A Dynamic Settlement Diffusion—Land Tenure Model Emphasizing the Ecological Impacts of Deforestation

F. Southworth
R. O'Neill^a

V. Dale^a
R. Frohn^b

(Abstract from article in *Proceedings of University of Tennessee, Geography Department Seminar Series*, Association of American Geographers, Knoxville, Tenn., October 18, 1990)

The DIFFU model is being used to examine the impact of rapid immigration and settlement on deforestation and related ecological effects in the state of Rondonia, Brazil. While these results, such as the dynamics of land-use pattern formation and change are simulated within DIFFU at the micro-spatial-, land lot-, and tenant-specific levels. Extensive use is being made of GIS applications, satellite imagery, vegetation and soil maps, and local contacts to develop the necessary data base. The project

culminates with a significant effort to mathematically integrate the human and physical representations of a region's geography for the purposes of policy analysis.

Research sponsored by ORNL Director's Research and Development Fund.

^aEnvironmental Sciences Division.

^bUniversity of California, Santa Barbara, Calif.

[7.3.25] Recommendations for Decentralized Information Technology Innovation and Management

B. E. Tonn

(Abstract from article in *The Information Society*, Vol. 7, No. 2, pp. 139-154, 1991)

Numerous factors, such as the emergence of microcomputers and changing attitudes towards job design and responsibility, are leading to the increased decentralization of information technology and management in large organizations. This paper presents five recommendations that could foster technology

innovation within a decentralization context. The recommendations have potential value for any large organization, public or private, that has "cross-cutting" information technology needs.

Research sponsored by U.S. Census Bureau.

[7.3.26] The Development of Ideas of Uncertainty Representation

B. E. Tonn

(Abstract from article in *Environment and Planning A*, Vol. 23, No. 6, pp. 783-812, 1990)

This article reviews the historical range and current applications of important ideas about uncertainty. It is undertaken for the benefit of decision makers and policy analysts who need more rigorous definitions of complex problems that entail large uncertainties. Addressed here are numerous ideas gleaned from many disciplines

including philosophy, mathematics, and artificial intelligence, which can supplement the basic approaches to uncertainty associated with objective and subjective probability. This review of the literature underscores the need for additional research on a number of topics, including uncertainty kinematics, uncertainty

estimate probabilities, subjective uncertainty elicitation, and the synthesis of new approaches to uncertainty with more traditional decision analysis techniques.

Research sponsored by Naval Sea Systems Command.

[7.3.27] The Case for Lower Probabilities as Measures of Uncertainty

B. E. Tonn
C. Wagner^a

(Abstract from article in *Proceedings of the EPRI Expert Systems Conference*, Boston, September 9-11, 1991)

Traditional expert systems approaches to the representation of uncertainty employ a wide range of methods, including probabilities, although evidence to support the principled assessment of such additive measures is often lacking. To the extent that AI researchers have realized this limitation, they have gravitated to Dempster-Shafer Theory (DST). We argue that DST is a generalization of probability theory insufficient to accommodate the full range of uncertainty encountered in applications. We show how a

substantial generalization of DST, the Theory of Lower Probabilities, provides for a more realistic representation of uncertainty, while at the same time admitting methods of combination, consensus, and conditionalization as rigorously based as others in probability theory and DST.

Research sponsored by Electric Power Research Institute.

^aUniversity of Tennessee.

[7.3.28] An Example of Systems Integration for RCRA Policy Analysis

B. E. Tonn
R. T. Goeltz
K. Schmidt^a

(Abstract from article in *Proceedings of the Advanced Computing for the Social Sciences Conference*, University of Georgia, Athens, Ga., April 8-10, 1991)

This paper describes the synthesis of various computer technologies and software systems used on a project to estimate the costs of remediating Solid Waste Management Units (SMMUs) that fall under the corrective action provisions of the Resource Conservation and Recovery Act (RCRA). The project used two data bases collected by Research Triangle Institute (RTI) that contain information on SWMUs and a PC-based software system called CORA (Cost of Remedial Action) that develops cost estimates for remediating SWMUs. The project team developed rules to categorize every SWMU in the data bases by the kinds of technologies required

to clean them up. These results were input into CORA, which estimated costs associated with the technologies. Early on, several computing challenges presented themselves. First, the data bases have several hundred thousand records each. Second, the categorization rules could not be written to cover every combination of variables. Third, CORA is run interactively, and the analysis plan called for running CORA tens of thousands of times. Fourth, large data transfers needed to take place between RTI and Oak Ridge National Laboratory. Solutions to these problems required systems integration. SMMU categorization was streamlined by using INTERNET as

was the data transfer. SAS was used to create files in a program called SuperKey that was used to run CORA. Because the analysis plan required the generation of hundreds of thousands of cost estimates, memory management software was needed to allow the portable IBM P70 to do the job. During the course of the project, several other software packages were used, including SAS System for Personal Computers, DBase III,

LOTUS 1-2-3, PIZAZZ PLUS, LOTUS Freelance Plus, and Word Perfect. Only the comprehensive use of all available hardware and software resources allowed this project to be completed within the time and budget constraints.

Research sponsored by the U.S. Department of Energy.

^aResearch Triangle Institute.

[7.3.29] Practical Implications of Theories of Uncertainty for Uncertainty Elicitation

B. Tonn
D. G. MacGregor^a

(Abstract from article in *Proceedings of the EPRI Expert Systems Conference*, Boston, September 9-11, 1991)

A major challenge for developers of expert systems is the elicitation of the uncertainties associated with experts' reasoning processes. Classical theories of probability are clear in prescribing how uncertainties should be represented, but offer no guidelines for how they should be elicited. Modern theories of uncertainty, such as Dempster-Shafer Theory (DST), provide a compelling representational framework for uncertainties, but also are moot on how elicitation from experts should be done. This paper presents an overview of the psychology of uncertainty, and summarizes the findings of research in the

cognitive sciences that relates to uncertainty elicitation. Techniques for eliciting classical, bayesian probabilities are reviewed and evaluated in light of research that has examined sources of bias in probability assessments, as well as the efficacy of corrective procedures. The practical implications of eliciting the components of DST are explored.

Research sponsored by the Electric Power Research Institute.

^aBates, Inc., Eugene, Oregon.

[7.3.30] Decision Support System Development Using A Migration Approach

D. G. MacGregor^a
B. E. Tonn
R. T. Goeltz

(Abstract from article in *Proceedings of the EPRI Expert Systems Conference*, Boston, September 9-11, 1991)

Virtually all organizations in the utility industry rely on some form of computerized decision support in the management of operations and maintenance. As decision-support needs evolve, new technologies are introduced and old technologies are updated, when possible and cost effective. Inevitably, new designs are superior to

old ones, and retrofitting does not prove feasible, resulting in many pieces of "stand alone" equipment that are not integrated into a common decision support framework. This paper develops a model for integrating decision-support systems of diverse vintage into a common workstation, using a migration approach. The model is applied

in the design and development of an integrated workstation to support operations and maintenance of a microwave communication system for power system monitoring and control. The system, called CAP (Computerized Alarm Processing), provides an integration of decision-support functions previously performed manually, integrates dispersed data bases, and provides both expert system and statistical analysis capabilities. The fielded system is

currently in operation at the Bonneville Power Authority's Dittmer Control Center. The implications of the migration approach for upgrading power system decision support are discussed.

Research sponsored by the Electric Power Research Institute.

^aBates, Inc., Eugene, Oregon.

[7.3.31] Test Plan and Implementation Procedures for the Integrated Booking System Prototype (IBS-P)

L. F. Truett T. G. Yow
V. V. Wheeler^a D. E. Valentine^a
S. E. Stamm^a

(Abstract from ORNL/TM-11832, Oak Ridge National Laboratory, June 1991)

The Test Plan for the Integrated Booking System-Prototype (IBS-P) describes system testing procedures and schedules. It also provides a specific list of requirements specifications. The testing of the IBS-P was conducted by Headquarters, Military Traffic Management Command (HQ-MTMC), and by each of the MTMC Area Commands (ACs). As a result of testing, modifications to the software were made, as appropriate, and text was added to the Functional Description of the target system. The

prototype system was accepted by MTMC. The Implementation Procedures outlined the process for installing the IBS-P at three sites: HQ-MTMC, MTMC Eastern AC, and MTMC Western AC. This report is a guidebook for this procedure. Implementation was successful at each of the three sites.

Research sponsored by the U.S. Department of Defense, Military Traffic Management Command.

^aThe University of Tennessee, Knoxville.

[7.3.32] User Interface Guidelines for the Integrated Booking System Prototype (IBS-P)

L. F. Truett T. G. Yow
V. V. Wheeler^a D. E. Valentine^a
S. E. Stamm^a

(Abstract from ORNL/TM-11833, Oak Ridge National Laboratory, June 1991)

The *User Interface Guidelines for the Integrated Booking System-Prototype (IBS-P)* describes the design requirements for the human-computer interface. The user interface design conforms to standards reported in the open literature, as well

as to standards provided through Department of Defense guidelines. The IBS-P interface was evaluated by personnel at Headquarters, Military Traffic Management Command (HQ-MTMC) and at each of the MTMC Area Commands. As a

result of comments received during demonstrations of the prototype at these sites, modifications to the design were made, as appropriate. The user interface was well accepted by the end users.

Research sponsored by the U.S. Department of Defense,
Military Traffic Management Command.

^aThe University of Tennessee, Knoxville.

[7.3.33] Functional Description for the Integrated Booking System (IBS)

L. F. Truett V. V. Wheeler^a
S. E. Stamm^a T. G. Yow
D. E. Valentine^a

(Abstract of ORNL/TM-11884, Oak Ridge National Laboratory, July 1991)

The Military Traffic Management Command, Directorate of International Traffic (MTIT) asked the Oak Ridge National Laboratory to analyze the requirements for an Integrated Booking System (IBS), to design and build a prototype, and to provide documentation for use in building the target system. This document describes current methodologies for accomplishing the booking mission and defines the functional requirements for IBS. It also discusses general architectural requirements and issues such as security, data exchanges, and system impacts. The ultimate goal of IBS is to provide international cargo booking for both unit and nonunit movements during peacetime and wartime. However, this functional description provides booking

requirements for the continental United States only. The results of the analysis show that IBS is a feasible system for accomplishing MTIT's cargo-management goals. IBS will replace aging systems, integrate automated and manual procedures, and will provide a single automated system during wartime for viewing both unit and nonunit international cargo requests. Good human-computer interface design will be incorporated into the system during development. Because of IBS querying capabilities, visibility of the booking process by MTIT will be enhanced.

Research sponsored by the U.S. Department of Defense
Military Traffic Management Command.

^aUniversity of Tennessee, Knoxville.

[7.3.34] Economic Analysis for the Integrated Booking System (IBS)

L. F. Truett
V. V. Wheeler^a

(Abstract from ORNL/TM-11910, Oak Ridge National Laboratory, August 1991)

The Military Traffic Management Command's proposed Integrated Booking System (IBS) will provide automation support for movement of international surface cargo. IBS will operate during peacetime and wartime to book unit and nonunit cargo. This Economic Analysis (EA) provides draft cost estimates over a 10-year life cycle for four IBS-generated alternative

strategies. The EA considered costs only for implementation and operation in the continental United States although IBS will be implemented worldwide. Through the year 2004, costs for Alternative 1 (maintaining the status quo) are estimated at a total of \$11,461,000. Costs for Alternative 2 (modification of current systems) are estimated at \$11,821,000. Costs for

Alternative 3 (development of IBS with a client and server architecture) are estimated at \$10,690,500. Costs for Alternative 4 (development of IBS on a midrange mainframe computer with terminal access) are estimated at \$10,622,900. Alternatives 3 and 4 are preferred from a technological and operational viewpoint as well as from a cost perspective. Alternative 3

provides additional benefits over Alternative 4 because of its cost-saving potential. Thus, Alternative 3 is the recommended course of action.

Research sponsored by the U.S. Department of Defense, Military Traffic Management Command.

^aThe University of Tennessee, Knoxville.

[7.3.35] Database Specifications for the Integrated Booking System Prototype (IBS-P)

T. G. Yow L. F. Truett
V. V. Wheeler^a D. E. Valentine^a
S. E. Stamm^a

(Abstract from ORNL/TM-11831, June 1991)

The Integrated Booking System (IBS) is an automated cargo booking system that has been developed for the Military Traffic Management Command to provide traffic management for international surface cargo movements during war and peace. The IBS prototype system (IBS-P), developed by Oak Ridge National Laboratory, conceptually defines an approach for the fully developed IBS. The purpose of this data base specification for the IBS-P is to provide the following:

- data base administration information, including data base management system configuration, hardware configuration, data base software utilities, data base physical structure and sizing, security; and
- a description of applications software requirements, including information needed in the development, maintenance, and enhancement of the software.

Research sponsored by the U.S. Department of Defense, Military Traffic Management Command.

^aThe University of Tennessee, Knoxville.

- a description of the IBS-P data base, including data base identification, interfaces, organization, mapping of data base files, storage allocation, and physical allocation;

[7.3.36] End-User's Handbook for the Integrated Booking System Prototype (IBS-P)

T. G. Yow L. F. Truett
V. V. Wheeler^a D. E. Valentine^a
S. E. Stamm^a

(Abstract from ORNL/TM-11834, June 1991)

The Integrated Booking System (IBS) is an automated cargo booking system that has been developed for the Military Traffic Management Command to provide traffic management for

international surface cargo movements during war and peace. The IBS prototype system (IBS-P), developed by Oak Ridge National Laboratory, conceptually defines an approach for the target

IBS. The purpose of this end-user's handbook is to provide the IBS-P end user with the information necessary to run the prototype. This information includes a discussion of IBS-P menu and screen options; information on option selection, user input, and system output and displays; instructions for navigating through the system; and guidelines for correcting data entry errors. This handbook does not contain detailed technical information on computer or system operation, nor

does it contain detailed information on transportation functionality. It is assumed that the personnel using the IBS-P know the transportation functionality required.

Research sponsored by the U.S. Department of Defense, Military Traffic Management Command.

^aThe University of Tennessee, Knoxville.

7.4 ABSTRACTS OF EFFICIENCY AND RENEWABLES RESEARCH SECTION

[7.4.1] Densities and Refractive Indexes of Aqueous (Li,K,Na)NO₃ and LiBr Solutions

M. R. Ally
A. Zaltash

L. N. Klatt^a
R. L. Linkous

(Abstract of pp. 209-13 in *Journal of Chemical Engineering Data*, 1991)

This paper describes experimental procedures for measuring densities and refractive indexes of aqueous salt solutions at 25-200°C and 18.90-90.50 wt % salt. An electrolyte solution of (Li,K,Na) NO₃ salts in water was chosen because of its recent development as a potential high-temperature heat pump fluid, but any appropriate fluid may be used. The densities and refractive indexes are a convenient way of measuring the concentration of salt (or water), and

accuracies of ±0.8 and ±0.3 wt % salt were achieved. For highly concentrated salt solutions, with their attendant handling problems, this measurement technique is convincingly more convenient than traditional methods of titration or gravimetric analysis.

Research sponsored by the U.S. Department of Energy Office of Industrial Programs.

^aAnalytical Chemistry Division.

[7.4.2] Geomagnetic Storms: Potential Economic Impacts on Electric Utilities

P. R. Barnes
J. W. Van Dyke

(Abstract of *Geomagnetic Storms: Potential Economic Impacts on Electric Utilities*, proceedings from the 4th Electric Utility Business Environment Conference, Denver, March 20, 1991)

Geomagnetic storms associated with sunspot and solar flare activity can disturb communications and disrupt electric power. A severe geomagnetic storm could cause a major blackout with an economic impact of several billion dollars. The vulnerability of electric power systems in the northeast United States will likely increase during

the 1990s because of the trend of transmitting large amounts of power over long distances to meet the electricity demands of this region. A comprehensive research program and a warning satellite to monitor solar wind are needed to enhance the reliability of electric power systems under the influence of geomagnetic storms.

ORNL-DWG 92-4511

Effects of the March 1989 solar system on electric power systems.

Research sponsored by the U.S. Department of Energy
Office of Energy Management.

[7.4.3] Electric Utility Industry Experience with Geomagnetic Disturbances

P. R. Barnes D. T. Rizy
B. W. McConnell F. M. Tesche^a
E. R. Taylor, Jr.^b

(Abstract of ORNL/6665, Oak Ridge National Laboratory, March 1991)

This study reviews and documents the impacts of geomagnetic disturbances (GMDs) on electric utilities. Also, the limited data measured by utilities during solar-induced GMDs and from experiments on power-system components are analyzed and discussed. Geomagnetic field disturbances due to solar-induced GMDs are compared with field disturbances caused by a high-altitude nuclear detonation, to provide insight into the consequences of such a nuclear event on power systems. Perturbations in the earth's magnetic field during GMDs induce voltage gradients along the earth's surface. These gradients result in earth-surface potentials (ESPs) between any two grounded, neutral points of

ORNL-DWG 90-14264

Global magnetohydrodynamic electromagnetic pulse electric field pattern at 3.0 seconds.

power-transmission lines with wye-connected transformers or autotransformers. The quasi-dc geomagnetically induced currents produced by ESPs cause transformers to magnetically saturate on alternate half-cycles. The saturated transformers generate harmonic currents and consume reactive power, causing electric utilities to experience system voltage-depression, real and reactive power flow variations in transmission lines, transformer and capacitor failures, and protection misoperations resulting in transmission

line, shunt capacitor, and static VAR compensator trips. These effects have caused local power disruptions and, in one case in March 1989, a major widespread blackout of the Hydro-Québec power system.

Research sponsored by the U.S. Department of Energy
Office of Energy Management and Defense Nuclear Agency.

^aConsultant.

^bABB Power Systems, Inc.

[7.4.4] The Response of MOV and SiC Arresters to Steep-Front Longer Duration Current Pulses

D. B. Miller^a

H. B. Fan^b

P. R. Barnes

[Abstract of *IEEE Transactions on Power Delivery*, 6(2), 666-671 (April 1991)]

An 80 m section of 138 kV transmission cable is used to produce pulses with voltages of several hundred kilovolts, currents greater than 20,000 A, and rise times equal to approximately 50 ns. This line pulser is used to test the response of metal oxide varistor (MOV) and gapped silicon carbide (SiC) surge arresters to steep-front, high current, 1.4 s duration pulses. The typical arrester voltage during a pulse consists of a strong initial "overshoot" voltage spike, followed by a nearly constant "residual" voltage that lasts to the end of the pulse. The overshoot voltage is believed to be related to the inductance of the arrester/divider circuit; this voltage increases linearly with peak

current and is similar for the MOV and SiC arresters. The residual voltage indicates the protection offered by the arrester due to its voltage-clamping action and is larger for the SiC arrester. Replacing the arrester with a similarly sized aluminum tube removes the inductive portion of the response, and the true arrester response then becomes quite fast.

Research sponsored by the U.S. Department of Energy
Office of Energy Management.

^aMississippi State University.

^bNorth China Institute of Electric Power.

[7.4.5] EMP Research on Electric Power Systems—Program Update

P. R. Barnes

(Abstract of ORNL/M-1382, Oak Ridge National Laboratory, May 1991)

This report describes the electromagnetic pulse (EMP) research program formulated by the U.S. Department of Energy in 1983. It covers major accomplishments, assessment results, and present research activities. Emphasis of this EMP

research has recently shifted from assessments to cost-effective reliability enhancement.

Research sponsored by the U.S. Department of Energy
Office of Energy Management.

[7.4.6] On the Direct Calculation of a Transient Plane Wave Reflected from a Finitely Conducting Half-Space

P. R. Barnes
F. M. Tesche^a

[Abstract of *IEEE Transactions on Electromagnetic Compatibility*, 33(2), 90-96 (May 1991)]

This paper discusses an approach for computing the electromagnetic field reflected from a lossy half-space directly in the time domain. This approach requires first evaluating the impulse response of the half-space and then convolving it with the specified incident field waveform. To obtain the impulsive reflected field, either for vertical or horizontal polarization, approximations to the Fresnel reflection coefficients are

made, thereby permitting an analytical expression in the time domain. Several different numerical examples using this technique are presented to illustrate the use of the method and the error contained in the solution.

Research sponsored by the U.S. Department of Energy
Office of Energy Management.

^aConsultant, Dallas.

[7.4.7] Impacts of a Nominal Nuclear Electromagnetic Pulse on Electric Power Systems: A Probabilistic Approach

V. J. Kruse^a D. L. Nickel^a
J. J. Bonk^b P. R. Barnes
E. R. Taylor, Jr.^b

[Abstract of *IEEE Transactions on Power Delivery* 6(3), 1251-63 (July 1991)]

A high-altitude nuclear detonation several hundred kilometers above the central United States would create an electromagnetic pulse (EMP) consisting of intense steep-front, short-duration, transient electromagnetic fields followed by a geomagnetic disturbance lasting tens of seconds. Since 1983, the Department of Energy has been actively researching the potential impacts of EMP events on the nation's electric energy supply. Using a nominal EMP environment, research has provided an indication of EMP impacts on geographically large electric power systems. A single high-altitude burst, which significantly disturbs the geomagnetic

field, would likely cause major load and generation loss, but permanent damage would be isolated. Multiple bursts would increase blackout areas, component failures, and restoration time. A long-term blackout is not expected, however, since major components such as power transformers would probably not be damaged.

Research sponsored by the U.S. Department of Energy
Office of Energy Management.

^aABB Power Systems, Inc.

^bConsultants.

[7.4.8]

The U.S. DOE Least-Cost Utility Planning Program

L. G. Berry
E. Hirst

[Abstract of *Energy*, 15(12), 1107-1117 (December 1990)]

This document reviews the most significant accomplishments of recent projects sponsored by the Least-Cost Utility Planning Program of the U.S. Department of Energy. This overview, with its accompanying bibliography, makes the resources of these projects (completed in 1989) more accessible to the program's utility planners and regulators. The most significant contributions of the projects relate to three areas: (1)

Demand-Side Management technology assessments and data base development, (2) assessments of current planning methods and future policy directions, and (3) consensus building and the development of organizational structures to support least-cost planning.

Research sponsored by the U.S. Department of Energy
Office of Conservation and Renewable Energy.

[7.4.9]

Evaluation of the Computerized Utilities Energy Monitoring and Control System Installed at the U.S. Army, Europe, 26th Support Group, Heidelberg, Germany

M. A. Broders
B. W. McConnell

(Abstract of ORNL/CON-320, Oak Ridge National Laboratory, May 1991)

The Oak Ridge National Laboratory is evaluating the Computerized Utilities Monitor and Control System (CUMACS) installed at Headquarters, USAREUR, 26th Support Group in Heidelberg, Germany. Using existing data, this evaluation takes an in-depth look at the overall performance of CUMACS to determine if it is achieving operational objectives and meeting projected energy and cost savings. This report indicates that CUMACS is well-maintained and managed by a dedicated, well-trained staff. Between fiscal year (FY) 1984 and FY 1990, CUMACS operations have contributed significantly to the overall reduction in energy consumption achieved by the USAREUR 26th Support Group. Simultaneously implemented energy-conservation programs incrementally reduce the aggregate installation energy consumption. The energy and cost savings attributed to CUMACS operations are significant, and Energy Conservation Investment Program military-construction project requirements (savings-to-investment ratio, simple payback

period, and energy-to-cost ratio) have been exceeded by a large margin. A very important consideration in evaluating an energy monitoring and control system (EMCS) is to determine which conservation measures yield the greatest energy and cost savings. Over 50% of reported cost savings are attributable to more energy-efficient operation of space- and water-heating systems in CUMACS/EMCS-controlled facilities. Further, over 95% of reported energy savings can be attributed to CUMACS/EMCS use of thermal-energy systems. This report graphically details the evaluation and determines that the benefits of CUMACS go beyond energy and cost savings. In addition, CUMACS personnel have demonstrated an ability for accessing these benefits, which could then be constructively shared with other installations.

Research sponsored by the U.S. Department of Defense and
the U.S. Army, Europe.

[7.4.10]

Guidelines for Successfully Transferring Government-Sponsored Innovations

M. A. Brown
L. G. Berry
R. K. Goel^a

[Abstract of *Research Policy* 20(2), 121-143 (April 1991)]

This paper develops guidelines that managers of government-sponsored research and development (R&D) could use in identifying appropriate technology-transfer strategies for specific innovations. It begins with a description of six types of commercialization strategies that have been successfully used by federal agencies: contracting R&D to industrial partners, working with industrial consortia, licensing to industry, influencing key decision makers, working with broker organizations, and generating end-user demand. Next, five case studies of government-supported research results that have been successfully transferred to users are summarized. These case studies illustrate the need to tailor commercialization strategies to specific innovations. Three ways of classifying innovations (based on technological, market, and policy criteria) are proposed. Technological

criteria evaluate inventions on scientific and technical grounds, while market criteria evaluate inventions with respect to characteristics of the marketplace. Policy criteria refer to a government agency's resources and goals. Once these evaluations are completed, the choice of a commercialization mode is facilitated. Finally, guidelines for selecting a technology-transfer strategy are discussed. Examples from the case studies are used to illustrate the general principles contained in the guidelines. These guidelines are summarized in a matrix that presents the relationships between the evaluation criteria and appropriate technology-transfer strategies.

Research sponsored by the U.S. Department of Energy
Office of Conservation and Renewable Energy.

^aIllinois State University.

[7.4.11] The Impact of Bonneville's Model Conservation Standards on the Energy Efficiency of New Home Construction

M. A. Brown J. O. Kolb
D. Baylon M. Haeri^a
D. L. White

(Abstract of ORNL/CON-310, Oak Ridge National Laboratory, July 1991)

An evaluation was undertaken to assess the impacts resulting from the establishment of Model Conservation Standards (MCSs) for single-family home construction in the Pacific Northwest. The analysis compared the energy efficiency of four categories of homes: Super Good Cents, Early Adopter, non-MCS homes built in 1987, and homes built in the pre-MCS period (1976-84). The three interrelated approaches used were analysis of billing data, construction-characteristics analysis, and energy-use simulations.

Results indicate that the energy efficiency of residential construction practices in the Pacific Northwest improved significantly between 1984 and 1987. Evidence suggest that the progress made over this period has been positively influenced by Bonneville's MCS programs, for while the difference in energy efficiency between 1976-1984 construction and 1987 homes constructed outside of MCS programs is significant, the difference between 1976-84

construction and 1987 MCS homes is even more substantial.

Research sponsored by the Bonneville Power Administration, Office of Energy Resources.

^aCentral Main Power Company.

[7.4.12]

**Promoting Energy-Efficient Home Construction:
Alternative Policy Instruments**

M. A. Brown
B. Cody^a

P. Brandis^a
P. Degens^b

(Abstract of Proceedings of the Energy Program Evaluation Conference, August 1991)

This study assesses the relative effectiveness of codes and marketing as alternative approaches to promoting energy-efficient new homes. Insights are drawn primarily from comparing the experiences of a code program [the Early Adopter (EA) Program] and a marketing program [Super Good Cents (SGC)] operated by Bonneville Power Administration in the Pacific Northwest. The results indicate that the energy efficiency of residential construction practices in Bonneville's region has been significantly improved by the two programs. The penetration rate of each program was 4-5% of new electrically heated single-family homes constructed in 1987. However, the SGC program has a bias towards more "up-scale"

households, while EA homes include a more representative cross section of the region's new-home construction. This difference occurs partly because only 16% of the eligible homes built in 1987 in EA jurisdictions were EA homes. After accounting for differences in the occupant and general housing characteristics of participants in the two programs, the annual savings of both programs is 1,900 kWh per home.

Research sponsored by the Bonneville Power Administration, Office of Energy Resources.

^aBonneville Power Administration.

^bERC Environmental and Energy Services Co.

[7.4.13]

**Codes Vs. Marketing: How Far Have They Advanced Home
Construction Practices in the Pacific Northwest**

M. A. Brown
J. O. Kolb
P. Brandis^a

(Abstract of the Fifth National Demand-Side Management Conference, July 1991)

Improving the efficiency of new-home construction offers many advantages to utilities. It decreases the energy load that new construction places on the power system, reduces the need to weatherize buildings at a later date, and avoids "lost opportunities" that occur because efficiency measures that may be economical during construction can become too expensive or structurally impossible to add later. This paper assesses the relative effectiveness of codes versus marketing approaches to promote energy-efficient

new homes. Insights are drawn primarily from comparing the experiences of a code program, the Early Adopter Program (EA), and a marketing program, Super Good Cents (SGC), operated by Bonneville Power Administration in the Pacific Northwest to nonprogram houses. Both programs promote the adoption of Model Conservation Standards (MCSs) for new-home construction. Results indicate that the energy efficiency of residential construction practices in the Pacific Northwest improved significantly as a result of

Bonneville's two MCS programs. By 1988, both programs had attracted approximately the same level of participation in terms of numbers of homes being built to MCSs, and the energy efficiency of the home construction under the two programs was comparable. The building thermal envelopes of both SGC and EA homes built in 1987 are more energy efficient than those of other homes built during the same year. In addition, all three types of 1987 homes (SGC, EA, and

non-MCS) are more energy efficient than homes built over the previous decade. SGC homes, however, tend to be "up-scale," while EA homes include a more representative cross section of the region's new-home construction.

Research sponsored by the Bonneville Power Administration, Office of Energy Resources.

^aBonneville Power Administration.

[7.4.14] Commercializing Government-Sponsored Computer Software

R. K. Goel^a
M. A. Brown

[Abstract of pp. 263-275 in *Advances in the Implementation and Impacts of Computer Systems*, M. Fleisher and J. A. Morell (eds.), JAI Press, Greenwich, Conn., 1991]

This report describes some of the problems government agencies encountered in promoting government-sponsored computer software. The extent of market penetration and use of government-supported software is highly dependent on decisions concerning the transfer process, and software-technology transfer is plagued by several problems that do not, in general, hinder the transfer of more conventional technologies. The report begins with the federal government's current policies regarding development, promotion, and distribution of government-supported software. Emphasis is placed on the policies of the U.S. Department of Energy (DOE), which provide the empirical basis for the rest of the paper. Three case studies, drawn from the experiences of DOE's Conservation Program, are examined. Each deals with a software package developed with DOE funding for use by practitioners and researchers in the buildings industry. To maintain consistency and facilitate comparison across case studies, the following five software management decisions are evaluated in each case:

- the extent of public funding,
- the extent of private-sector involvement,
- the reliance on public- versus private-sector distribution systems,
- methods used to generate public awareness, and
- copyrighting and licensing approaches.

Results indicate varying degrees of success in the commercialization of government-sponsored software. DOE-2 was by far the most successful of the three software programs studied here, with an extensive distribution network, considerable market penetration, and much more documentation of its progress compared to the other two case studies. Reasons and recommendations are offered for the varying levels of success for improving software-technology transfer.

Research sponsored by the U.S. Department of Energy Office of Building Technologies.

^aIllinois State University.

[7.4.15] Evaluation Plan for the Weatherization Assistance Program

D. A. Beschen^a
M. A. Brown

(Abstract of ORNL/TM-11668/V1, Oak Ridge National Laboratory, August 1991)

The most recent national evaluation of the Weatherization Assistance Program (WAP) of the U.S. Department of Energy was completed in 1984 based on consumption data for households weatherized in 1981. WAP regulations and operations have changed substantially over the last decade, and new opportunities are on the horizon. DOE recognizes the need for a more current national evaluation of the program and has developed a plan for conducting the evaluation with the support of the Oak Ridge National Laboratory. The national WAP evaluation as currently proposed has seven major goals:

- to estimate the energy saved by the program one, two, and three years after participation;
- to assess nonenergy impacts such as comfort, safety, and affordability;
- to assess program cost effectiveness;
- to analyze factors that influence energy savings, nonenergy impacts, and cost effectiveness;
- to describe the WAP network's capabilities and the innovative weatherization technologies and procedures it has employed;
- to characterize the WAP-eligible population and the federal and nonfederal funds that have been used to meet its weatherization needs; and

- to identify promising WAP opportunities for the future.

The data collection, analyses, and reports are to be completed in phases between 1991 and 1993. The evaluation methodologies vary by fuel type, housing type, and climate zone. For gas and electrically heated or cooled housing units (both single-family and multifamily), the evaluation will focus on weatherization jobs completed in 1989. The analysis of energy savings and cost effectiveness will be based primarily on weather-normalized, retrospective utility billing records (collected for pre- and postretrofit years). For fuel-oil heated homes, analysis will be based upon pre- and postretrofit metered consumption and temperature data collected from homes scheduled for weatherization in 1991 and 1992. The fuel-oil study will cover the nine states where fuel-oil use is most prevalent (New England and New York, New Jersey, and Pennsylvania).

Research sponsored by the U.S. Department of Energy, Office of State and Local Programs.

^aU.S. Department of Energy.

[7.4.16] Technology-Transfer Strategies of DOE's Conservation Programs

M. A. Brown
C. H. Major^a

[Abstract of pp. 33-40 in *Journal of Technology Transfer*, 15(1) (1990)]

This paper examines the processes by which research and development (R&D) results funded by the U.S. Department of Energy conservation program have generated commercial applications. It looks at examples of successful technology-transfer activities across three different offices

corresponding to the major energy end-use sectors: transportation, buildings, and industry. Close industry cooperation characterizes the conservation program's technology-transfer approach, but the unique context of each office (e.g., concentrated versus fragmented audiences

and basic versus applied research) has necessitated individually tailored approaches. The transportation program, with a highly concentrated primary audience, is largely exploratory. The result is a reliance on contracting basic R&D to major automotive manufacturers having the ability to produce derivative commercial products, and licensing to capitalize on non-automotive spin-off applications. The buildings program, serving a highly fragmented audience, conducts a wide array of basic and applied research. Contracting with small businesses has been a successful technology-transfer strategy, and trade and

professional organizations are often employed as technology and information brokers. Faced with easily targeted audiences and an R&D focus on mature technologies, the industrial program relies on cost-shared performance testing by industrial end-users to generate demand. Thus, what might appear at first glance to be a confusing array of strategies actually represents a logical and effective solution to the technology-transfer problems faced by each conservation office.

Research sponsored by the U.S. Department of Energy Office of Conservation.

^aU.S. Department of Energy.

[7.4.17] Performances of Four Magnetic Heat-Pump Cycles

F. C. Chen
V. C. Mei

R. W. Murphy
G. L. Chen^a

(Abstract of pp. 103–115 in *Thermo-Physical Aspects of Energy Conversion*, AES-Vol. 16 of the 1990 ASME Winter Annual Meeting, Dallas, American Society of Mechanical Engineers, 1990)

Magnetic heat pumps (MHPs) have been successfully used for refrigeration applications at temperatures near absolute zero. In these applications, a temperature lift of a few degrees in a cryogenic environment is sufficient and can be easily achieved by a simple MHP cycle. To extend magnetic heat pumping to other temperature ranges—and other types of applications in which the temperature lift is more than just a few degrees—requires more involved cycle processes. This paper investigates the characteristics of a few better-known thermomagnetic heat-pump cycles (Carnot, Ericsson, Stirling, and regenerative) in extended ranges of temperature lift. The regenerative cycle is the most efficient. For gadolinium operating between 0 and 7 T (Tesla) in a heat-pump cycle with a

heat-rejection temperature of 320 K, analysis predicted a 42% loss in coefficient of performance at 260 K cooling temperature and a 15% loss in capacity at 232 K cooling temperature for the constant-field cycle as compared with the ideal regenerative cycle. Such substantial penalties indicate that the potential irreversibilities from this one source (the additional heat transfer that would be needed for the constant-field versus the ideal regenerative cycle) may adversely affect the viability of certain proposed MHP concepts if the relevant loss mechanisms are not adequately addressed.

Research sponsored by the U.S. Department of Energy Office of Industrial Technologies.

^aComputing and Telecommunications Division.

**[7.4.18] Loss Analysis of the Thermodynamic Cycle of Magnetic Heat Pumps,
Phase I Final Report**

F. C. Chen
V. C. Mei
J. W. Lue^b

R. W. Murphy
G. L. Glen^a
M. S. Lubell^b

(Abstract of ORNL/TM-11608, Oak Ridge National Laboratory, February 1991)

Recently, the need for developing non-ozone-depleting, no-greenhouse-effect heat-pump systems and for exploring new high-temperature superconducting materials has prompted a

renewed interest in the study of magnetic heat pumps (MHPs). The new materials can provide the high magnetic field that an effective superconducting MHP requires; MHPs do not use

ORNL-DWG 90-11718R

T-S with constant magnetization, ideal regenerative and constant field cycles.

freon for a working fluid. Traditionally, MHP concepts have been successfully developed and used for refrigeration applications at temperatures near absolute zero. In these cases, a temperature lift of a few degrees in a cryogenic environment is sufficient and can be easily achieved by a simple MHP cycle. The working media are usually the chemical compounds of gadolinium. Extending magnetic heat pumping to other temperature ranges—and other types of applications in which the temperature lift is more than just a few degrees—requires more involved cycle processes dependent upon the thermomagnetic properties of the working media and the availability of a high magnetic field. This report documents efforts to study the thermophysics of MHPs, including a survey of literature, a study of thermodynamic

cycles and cycle thermal losses, and an analysis of pulse magnets. The regenerative cycle has been identified as the most efficient, with a maximum of 42% loss in coefficient of performance at 260 K cooling temperature and a maximum of 15% loss in capacity at 232 K cooling temperature for the constant field (magnetic Ericsson) cycle, between 200 K and 320 K, as compared with the ideal regenerative cycle with gadolinium as the core material.

Research sponsored by the U.S. Department of Energy
Office of Industrial Technologies.

^aComputing and Telecommunications Division.

^bFusion Energy Division.

**[7.4.19] The Technical Viability of Alternative Blowing Agents in
Polyisocyanurate Roof Insulation; Part 4 In-situ
Thermal Aging and Performance in
Different Roof Systems**

J. E. Christian
R. L. Linkous
R. S. Graves^a

G. E. Courville
R. L. Wendt
T. L. Smith^b

(Abstract of *Proceedings 33rd Annual Polyurethane Conference*, September 30-October 3, 1990, Orlando, Florida)

This paper presents a progress report on field thermal performance measurements on a set of private-industry-produced, experimental polyisocyanurate laminate board stock foams blown with CFC-11, HCFC-123, HCFC-141b, 50/50, and 65/35 blends of HCFC-123/HCFC-141b. These boards have been observed for almost 300 days of roof field exposure in East Tennessee. The field data are used to derive an empirical model that can be used to predict effective diffusion coefficients for the air components into the foam cells. These coefficients are compared with those developed from steady-state laboratory measurements of thin-sliced samples from the same batch of experimental boards. The relative performance of test specimens of HCFC-141b under a black and a white membrane are reported. Aging of the HCFC-141b blown foam under the white

membrane occurred more slowly during cold weather but accelerated after winter, resulting in no significant resistivity difference after 280 days of exposure from September 1989–May 1990. Analysis suggests that the percent increase in k over that of the foam blown with CFC-11 is, after one year of aging, 5.5% for HCFC-123 and 11.7% for HCFC-141b—the same order as derived from the laboratory thin-slicing analysis report in Part 3 of this session. Additional plans are described for further thermal- and mechanical-property measurements to be conducted on two Oak Ridge National Laboratory roof field testers. After the first year of this three-year study, there has been no indication that thermal-performance differences are serious enough to suggest that any of the alternate blowing agents would not be technically viable in polyisocyanurate roof insulations.

Measured resistivity at weekly mean insulation temperatures for CFC-11, HCFC-123, and HCFC-141b.

Research sponsored by the U.S. Department of Energy
Office of Building Technologies and the National Roofing
Contractors Association.

^aMetals and Ceramics Division.

^bNational Roofing Contractors Association.

[7.4.20]

Thermal Mass Credits Relating to Building Envelope Energy Standards

J. E. Christian

[Abstract of ASHRAE Transactions 97(2), 1991]

The U.S. Department of Energy (DOE) supported this research directed at a systematic study of the effects of exterior-envelope thermal mass beginning in 1979 when there was considerable

debate in the private sector over the magnitude of the effect of building envelope mass on annual heating and cooling loads. The result was an experimental data base consisting of thermal-

performance measurements on 14 test houses in two locations with various amounts of external wall mass, detailed measurements on a massive 4000 ft² office and dormitory building, independent consistency checks on the measurements, validation of a variety of building simulation models, several extended simulated data bases of full-size, single-family residences, and several simplified techniques to predict the effect of exterior thermal mass on annual heating and cooling loads. The simplified technique used to develop the Thermal Mass Credit Tables in the Council of American Building Officials' *Model Energy Code* (1989 Edition) is the simplified technique most consistent with the DOE-2.1C simulated data base used to develop the envelope component recommendations in ASHRAE Standard 90.2P, "Energy Efficient Design of New Low-Rise Residential Buildings." This paper also briefly discusses the history of DOE Thermal Mass Research, which has lead in part to the inclusion of Thermal Mass Credits in the *Model Energy Code* (1989 Edition) and ASHRAE 90.2P.

ORNL-DWG 92M-6357

Seasonal heating and cooling load savings for thermal mass envelope components.

Research sponsored by the U.S. Department of Energy Office of Building Energy Research and Development, Building Systems Division.

[7.4.21] ASHRAE Standard 90.2 Envelope Load Factors and Trade Off Procedures

M. McBride^a
B. Wilcox^b
J. E. Christian

[Abstract of ASHRAE Transactions 97(2), 1991]

The Standards Project Committee for Standard 90.2, "Energy Efficient Design of New Low-Rise Residential Buildings," has developed simplified procedures to estimate seasonal heating and cooling load savings for all envelope components, above- and below-grade, of single-family and multifamily housing. The general form of the simplified load savings equations is to predict a load savings as a function of a change in U-factors and a single weather variable (HDD65 for heating and CDH74 for cooling). All of the equations are linear; their slopes are called load factors. Another application of the load-saving equations has been the development of a simplified trade-off

procedure for all of the envelope components. One advantage of these equations is the ability to trade off opaque components with glazing shading coefficients and orientations as well as the traditional glazing U-factor. This simplified capability did not exist in previous versions of the standard.

Research sponsored by the U.S. Department of Energy Office of Building Technologies.

^aOwens Corning Fiberglass, Granville, Ohio.

^bBerkeley Solar Group, Oakland, California.

[7.4.22]**Builder's Foundation Handbook**

J. Carmody^a
J. E. Christian
K. Labs^b

(Abstract of ORNL/CON-295, Oak Ridge National Laboratory, May 1991)

This handbook contains a worksheet to select insulation levels based on specific building construction, climate, heating, ventilating, and air conditioning equipment, insulation cost, and other economic considerations. The worksheet permits optimization of foundation insulation levels for new or retrofit applications. Construction details representing good practices for the design and installation of energy-efficient basement, crawl-space, and slab-on-grade foundations are the focal point. These construction details are keyed to a list of critical design information useful for specifying structural integrity; thermal and vapor controls; subsurface drainage; water-proofing; and mold, mildew, odor, decay, termite, and radon control strategies. Another feature, useful during design and inspection, is checklist chapter summaries covering major design considerations for each foundation type. The

information here draws heavily from the first foundation handbook from the 1988 Department of Energy/Oak Ridge National Laboratory Building Envelope Systems and Materials Program, *Building Foundation Design Handbook*, an extensive technical reference manual. This book presents "what to do in foundation design" in an inviting, concise format. Although intended for active home builders, the information is pertinent to anyone involved in foundation design and construction decisions, including homeowners, architects, and engineers.

Research sponsored by the U.S. Department of Energy
Office of Building Technologies.

^aUniversity of Minnesota.

^bUndercurrent Design Research.

**[7.4.23] Thermal Properties of Polyisocyanurate Foam Board Insulation
Blown With CFC-11 Substitutes**

G. E. Courville J. E. Christian
R. S. Graves^a R. L. Linkous
D. L. McElroy^a

(Abstract of *Third International Symposium on Roofing Technology*, Montreal, April 17-19, 1991)

Participants at government- and industry-sponsored workshops evaluated several hydrochlorofluorocarbons (HCFCs) for their suitability as blowing agents in polyisocyanurate laminate boardstock. Laminated boardstock was chosen because of its superior insulating qualities, commercial significance, high technical dependence on alternate blowing agents, and diverse requirements. The project is guided by a cooperative industry and government steering committee, with representation by the Society of the Plastics Industry, the Polyisocyanurate

Insulation Manufacturers Association, the National Roofing Contractors Association, the U.S. Environmental Protection Agency, and the U.S. Department of Energy. A specific polyisocyanurate formulation with an organic and inorganic facer was selected as generally representing current roof insulation technology. With this as a base, foams with HCFC-123, HCFC-141b, and two blends of HCFC-123 and HCFC-141b were compared to foam with CFC-11, the current industry standard. This study examines whether foams with alternate blowing

agents yield the same thermal properties as foam with CFC-11. Results reported will compare foam thermal performance under laboratory and accelerated conditions, as well as the thermal performance in long-term in situ testing of roof sections. The former involves both full-thickness and thin-slicing techniques and utilizes an advanced R-Matic apparatus with expanded temperature range capabilities (ASTM C-518) and an Unguarded Thin Heater Apparatus (ASTM C-111-4). The long-term testing will be carried out on small-scale, conventionally installed roof systems on the Roof Thermal Research Apparatus. All tests are being conducted at the Oak Ridge National Laboratory.

Measured k conductivity at weekly mean insulation temperatures for CFC-11, HCFC-123, and HCFC-141b boards.

Research sponsored by the U.S. Department of Energy
Office of Building Technologies.

^aMetals and Ceramics Division.

[7.4.24] Residential Absorption Heat Pump Using a Generator-Absorber Heat Exchange Cycle

B. A. Phillips^a
R. C. DeVault

(Abstract of IECEC Conference Proceedings, Boston, August 8, 1991)

A natural-gas fired, air-to-air, absorption heat pump using the generator-absorber heat exchange (GAX) cycle is being developed for residential and small commercial applications. This paper discusses the energy-saving potentials of thermally actuated heat pumps using basic thermodynamic principles and gives a progress report on the development of the GAX absorption heat

pump and its components for residential applications.

Research sponsored by the U.S. Department of Energy
Office of Building Technologies.

^aPhillips Engineering Company, St. Joseph, Michigan.

[7.4.25] National Energy Impacts of CFC Alternatives in Heating, Air-Conditioning, and Refrigerating Equipment and Foam Insulation

S. K. Fischer

[Abstract of pp. 49-56 in *ASHRAE Technical Data Bulletin* 6(1), 1990]

Chlorofluorocarbons (CFCs) are used extensively as the working fluids in high-efficiency refrigeration equipment and as blowing agents in manufacturing high R-value foam insulations. However, because CFCs contribute to the destruction of stratospheric ozone, they significantly threaten the global environment. Future production and emissions of CFCs will be controlled under the provisions of the Montreal Protocol, and the use of these compounds will be phased out. The U.S. Department of Energy is concerned about the energy-efficiency of

alternative chemical compounds and technologies that may be used as substitutes for CFC-11 and CFC-12 as refrigerants and blowing agents. This paper discusses the possible increase in national energy use resulting from the replacement of CFCs with alternative compounds. Significant increases in energy use could occur, particularly in refrigerators, freezers, water heaters, and commercial buildings.

Research sponsored by the U.S. Department of Energy Office of Building Technologies.

[7.4.26] Assessment of Weatherization Assistance Program Needs for Improved Residential Measure Selection Techniques

M. B. Gettings
J. O. Kolb

(Abstract of ORNL/CON-316, Oak Ridge National Laboratory, February 1991)

This report examines a study conducted by the Oak Ridge National Laboratory to evaluate the current measure selection techniques of agencies within the Weatherization Assistance Program (WAP). The study precedes a project to revise and upgrade current means of selecting energy-conservation measures for low-income, single-family and multifamily housing and includes recommendations for the revision. Issues relevant to revised audit procedures are discussed, and currently available audits are reviewed. No audit program currently in use was found capable of fulfilling the needs of the WAP. Recommendations include the development of separate single-family and multifamily audits. Specific features recommended for addition to the single-family audit include (1) measure-ranking unique to each eligible house, (2) heating and cooling equipment measures, (3) cooling envelope measures, (4) means for determining the

amount of infiltration work to be performed, (5) potential for customizing and simplifying to meet local needs, and (6) implementation on a personal computer or as an alternate manual technique. A single-family audit development plan proposes examination of several existing programs as potential starting points. Recommendations related to the development of a WAP multifamily audit include examination of several existing private programs for use by WAP agencies with the greatest need and further study of DOE-supported programs ASEAM and CIRA as possible starting points. Early identification of approved multifamily measures and their applicability to various building stock, equipment types, and fuels is also recommended.

Research sponsored by the U.S. Department of Energy Office of State and Local Assistance Programs, Weatherization Assistance Program.

[7.4.27] A Bright Future for Electric-Utility DSM Programs

E. Hirst

(Abstract of pp. 899-906 in *Proceedings of the Canadian Electrical Association Conference, Enhancing Electricity's Value to Society*, Toronto, October 22-24, 1990)

Between now and the year 2010, utilities are likely to face major changes that will affect the mix of resources used to meet energy demands. Utilities' organizational structures, management activities, and means of providing services will also be affected by these changes, a key element of which will be the increasing importance of utility demand-side management (DSM) programs. New utility DSM programs could cut electricity use in the year 2010 by more than one-fifth. Assuming that, between 1990 and 2010, the proportion of utilities offering DSM programs were to increase to 50%; the proportion of customers participating, to 15%; and the savings

per customer, to 25%. These assumptions imply ambitious programs far beyond current utility practices. However, a few utilities are planning such innovative programs. According to the U.S. Department of Energy projection, these programs would cut electric bills by \$60 billion a year and eliminate the need for about 400 medium and large power plants by the year 2010. In addition, total U.S. emissions of carbon dioxide would be cut by 10%, easing the threat of global warming.

Research sponsored by the U.S. Department of Energy Office of Conservation and Renewable Energy.

[7.4.28] Encouraging Electric-Utility Energy-Efficiency and Load-Management Programs

E. Hirst

(Abstract of pp. 813-21 in *Proceedings of MIT Conference on Energy and the Environment in the 21st Century*, March 26-28, 1991)

Through the cooperation of the federal government with electric utilities, energy-efficiency and load-management programs can save money for customers, provide more services, reduce financial risks to the utilities, and improve the environment. Utilities have recognized the benefits of efficiency-improving programs that reduce environmental pollutants, increase customer savings, and reduce peak demand by the use of load-control, high-efficiency systems, adoption of newer technologies, and construction of energy-efficient buildings. Utilities need to conduct more technology assessments, concentrate on understanding their markets better (to assess electricity-use patterns), and evaluate

savings and costs of demand-side management programs. Utilities should encourage the implementation of more federal and state efficiency standards, public utility commissions should encourage utilities to experiment with demand-side programs, and the U.S. Department of Energy should assist with technology transfer and funding. This paper shows how some programs have produced large savings, and it provides information on ways agencies can continue to promote and support energy efficiency.

Research sponsored by the U.S. Department of Energy Office of Conservation and Renewable Energy.

[7.4.29] Possible Effects of Electric-Utility DSM Programs, 1990 to 2010

E. Hirst

(Abstract of ORNL/CON-312, Oak Ridge National Laboratory, January 1991)

This report examines the trends that will likely affect utility demand-side management (DSM) programs and develops a scenario of future electricity use. The reference projection developed by the Energy Information Admin-

istration (EIA) for the National Energy Strategy was used only as the starting point for this scenario. In contrast to the National Energy Strategy, the scenario here assumes that utilities will conduct more aggressive and effective DSM programs. Specifically, this scenario assumes that between 1990 and 2010 the proportion of utilities offering DSM programs will increase from 20% to 75%, the proportion of customers participating each year will increase from 7% to 12%, and the electricity savings per customer (produced by the installation of more efficient equipment and systems) will increase from 15% to 22%. However, these assumptions go far beyond what most utilities are now doing. Relative to the EIA projection, these utility DSM programs would cut electricity use in the year 2010 by one-fifth. Moreover, these new programs would cut electric bills by \$61 billion a year and, by cutting electricity growth nearly in half, would eliminate the need for 430 power plants. In addition, total U.S. emissions of carbon dioxide would be cut by 9%, thereby easing the threat of global warming.

ORNL-DWG 92M-8359

Electricity savings with demand-side management programs, projected 1990–2010.

Research sponsored by the U.S. Department of Energy
Office of Conservation and Renewable Energy.

[7.4.30] Utility DSM Programs Could Cut Electricity Use 20% During the Next Two Decades

E. Hirst

(Abstract of *DSM and the Global Environment Conference*, pp. 27–35, Synergic Resources Corporation, Bala Cynwyd, Penn., April 1991)

Between now and the year 2010, electric utilities will face major changes. These changes will affect the mix of resources that utilities use to produce energy services as well as the ways that utilities deliver services to their customers. A key element of these changes will be the growing importance of utility demand-side management

(DSM) programs. This paper examines the trends that will likely affect DSM programs and develops a scenario of future electricity use. A projection developed by the Energy Information Administration (EIA) was used as the starting point. In contrast to this projection, the scenario developed here assumes that increasing numbers

of utilities will conduct more aggressive and effective DSM programs. Compared to the EIA projection, these utility programs would reduce electricity use in the year 2010 by one-fifth. Moreover, these new programs would cut electric

bills by \$61 billion a year and eliminate the need for 430 new power plants.

Research sponsored by the U.S. Department of Energy, Office of Conservation and Renewable Energy.

[7.4.31] Benefits and Costs of Flexibility: Small, Short-Lead-Time Power Plants and Demand-Side Programs

E. Hirst

[Abstract of pp. 106-15 in *Long Range Planning* 23(5), October 1990]

Electric utilities face unprecedented variables that complicate long-term resource planning. As a consequence, many utilities emphasize small resources that can be constructed quickly. However, insufficient data exist to adequately assess this risk-reduction strategy. This report compares the benefits of such flexible resources (including conservation and load-management programs) with their costs relative to large, long-lead-time power plants. The flexibility benefits computed for various examples amount to 2-20% (0.1-1 cent/kWh). Cost estimates from the Northwest Power Planning Council suggest that these benefits generally do not justify the higher costs of small power plants. However, the benefits more than justify the incremental costs associated with expansion of simple-cycle combustion turbines to combined-cycle operation. Also, the benefits amply justify

application of the Council's option-and-build strategy. The first stage of their strategy involves the time-consuming but inexpensive activities of siting, designing, and licensing the plant. Then, the plant can be constructed, the site can be held as an option for several years, or the plans can be terminated. This strategy permits timely construction that matches changes in load growth at very little cost. Further, utility conservation and load-management programs can provide substantial flexibility benefits. With construction of a single 600-MW power plant, implementing the demand-side program described here cuts the price of electricity by 10% (0.7 cent/kWh), 50-100% more than do small, short-lead-time power plants.

Research sponsored by the U.S. Department of Energy Office of Building Technologies.

[7.4.32] A Rose by Any Other Name: Defining Key Terms on Utility DSM Programs

E. Hirst

[Abstract of pp. 305-18 in *Energy Systems and Policy* 14(4), 1991]

As the number, scope, and cost of utility demand-side management (DSM) programs increase, the need for accurate data grows. Such data are required to document the performance of these programs to be sure that they deliver the cost-effective energy and capacity resources

expected of them. Unfortunately, the amount and quality of data available on DSM programs fall far short of what is needed. Lack of explicit, widely used definitions of DSM terms is a key deficiency. Variables that describe program participation, electricity savings, and costs must be carefully

defined, and these definitions should then be used throughout the electric-utility industry.

Research sponsored by the U.S. Department of Energy Office of Conservation and Renewable Energy and the Electric Power Research Institute.

[7.4.33] Creating the Future: Integrated Resource Planning for Electric Utilities

E. Hirst
C. Goldman^a

(Abstract of pp. 91-121 in *Annual Review of Energy and the Environment* 16, 1991)

During the past few years, the scope and nature of resource planning at electric utilities have changed dramatically. The scope has expanded to consider energy-efficiency and load-management programs, the environmental costs of electricity production, and various resource-selection criteria beyond electricity price. The nature of planning has expanded to include regulatory commissions, nonutility energy experts, customers, and utilities themselves. This paper discusses a few of the key issues related to resource planning: provision of financial incentives to utilities for successful implemen-

tation of integrated resource plans; incorporation of environmental factors; bidding for demand and supply resources; treatment of utility demand-side management programs as resources; development of guidelines for preparation and review of utility integrated resource plans; and greater efforts by the U.S. Department of Energy to encourage integrated resource planning.

Research sponsored by the U.S. Department of Energy Office of Conservation and Renewable Energy.

^aLawrence Berkeley Laboratory, Berkeley, California.

[7.4.34] Technical Competence of Integrated Resource Plans Prepared by Electric Utilities

E. Hirst
E. Yourstone^a

M. Schweitzer
J. Eto^b

(Abstract of pp. 39-55 in *Resources and Energy* 13, May 1991)

Integrated resource planning is a new way for electric utilities and state regulatory commissions to cost-effectively meet future energy needs. As part of this process, many utilities prepare long-term plans that integrate demand-side programs into their mix of resources. This paper discusses guidelines for the preparation and review of utility reports on their resource plans, focusing on the technical competence of the underlying analysis. Load forecasts, demand-side

resources, supply resources, integration of resources, and treatment of uncertainty are discussed.

Research sponsored by the U.S. Department of Energy Office of Conservation and Renewable Energy.

^aConsultant, Albuquerque, New Mexico.

^bLawrence Berkeley Laboratory, Berkeley, California.

[7.4.35] Commercial Sector Gas Cooling Technology Frontier and Market Share Analysis

D. M. Hamblin^a
R. J. Maddigan^c
H. A. McLain

G. D. Pine^b
J. M. MacDonald
J. Y. Rimpo^d

(Abstract of pp. 239-50 in *International Association for Energy Economics Twelfth Annual North American Conference Proceedings*, October 1990)

This paper describes a method that can assist planning for commercial sector, natural-gas cooling systems research and development. The initial cost of these systems, developed for the Gas Research Institute of the United States, is higher than conventional electric chiller costs. Yet, engine-driven chiller designs exist that are currently competitive in U.S. markets typified by high electricity or demand charges. Section II describes a scenario-analysis approach used to develop and test the method. Section III defines the technology "frontier," a conceptual tool for identifying new designs with sales potential. Section IV describes a discrete choice method for predicting market shares of technologies with sales potential. Section V shows how the method predicts operating parameter, cost, and performance goals for technologies without current sales potential (or for enhancing a frontier technology's sales potential). Finally, section VI concludes with an illustrative example for the Chicago office building retrofit market.

Research sponsored by the U.S. Department of Energy Office of Building Technologies and the Gas Research Institute.

^aDan Hamblin & Associates, Inc.

^bGas Research Institute.

^cScience Applications International Corporation.

^dRimpo & Associates.

Illustration of the analysis framework for examining commercial cooling markets and R&D goals.

Illustration of the analysis framework for examining commercial cooling markets and research and development goals.

**[7.4.36] Exploratory Investigation of Energy Use Metering and Data Analysis
Methods for Multifamily Buildings in the Pacific Northwest**

J. M. MacDonald
D. L. White

(Abstract of ORNL/CON-304, Oak Ridge National Laboratory, May 1991)

This investigation focuses on analyzing energy data for all-electric (single-fuel) multifamily (MF) buildings in the Pacific Northwest. Its purpose is to search for insights that could lead future field-energy measurement studies and analyses of conservation potential to better evaluations of energy standards for MF buildings. A two-dimensional index is proposed here to compare energy use between MF buildings: heating-energy use per square foot of floor area by nonheating-energy use per residence. A similar index should be considered for all future representations of MF energy use. This study proposes a new empirical modeling tool for

evaluating heating-energy use. The model represents the fraction of total energy used by the heating system as a translated, truncated, simple sine function, which appears capable of estimating annual space-heating energy consumption in all-electric MF buildings. Results from this study conclude that for MF buildings both weather and occupancy normalizations are important. However, the available end-use energy consumption data are limited.

Research sponsored by the Bonneville Power Administration.

**[7.4.37] Energy and Economic Benefits of Gas Cooling Options
in Large Office Buildings**

H. A. McLain
D. M. Hamblin^a

J. M. MacDonald
R. J. Maddigan^b

[Abstract of pp. 345-52 in *ASHRAE Transactions* 97(1), 1991]

A flexible, public-domain methodology was developed for estimating financial indicators for alternative heating, ventilating, and air-conditioning equipment in commercial buildings. Based on a simulation of the building's hourly energy use, it allows for many economic parameters, including detailed utility rate structures, fuel-price escalation rates, inflation rates, and loan expenses. The methodology was applied to the evaluation of natural-gas-fired engine-driven chillers in large commercial office

buildings, which prove promising for buildings located in Chicago, Boston, and San Diego (cities that have high demand and time-of-day charges). The study emphasizes the initial cost premium for the engine-driven chiller.

Research sponsored by the U.S. Department of Energy Office of Building Technologies and the Gas Research Institute.

^aDan Hamblin & Associates, Inc.

^bEconomic System Analysis, Inc.

ORNL-DWG 92-6205

Internal Rate of Return (IRR) values for engine-driven chiller options in building with Variable Air Volume (VAV) air-handling systems—Chicago.

[7.4.38] Heat Transfer of Buried Pipe for Heat Pump Application

V. C. Mei

(Abstract of pp. 51–55 in *ASME Journal of Solar Energy Engineering* 113, February 1991)

The application of line-source theory for ground-coil design usually results in excessive oversize; therefore, for ground coil heat pump systems to be economically competitive with other residential heating and cooling systems, oversize must be avoided. Consequently, a new ground coil model was derived that uses energy balance rather than the traditional line-source theory to predict more accurately ground-coil operation. This study compares this ground-coil model with models based on line-source theory (a simple line-source model

and a modified line-source model) by using them to simulate the same field test data for both summer and winter operations. For winter operation, the new model predicts a coil-liquid exit temperature with a maximum deviation from the measured values of less than 2°C and an average deviation of less than 1°C. The modified line-source model predictions have an average deviation of more than 1.5°C. For summer operation, all models underpredict the measured soil temperatures because the effect of thermal backfill material has not been included. The new

model still predicts the test results better than the other two models. Furthermore, when the effect of sand thermal backfill (which is not easy for the two line-source models to accommodate) is

included in the new model, the calculated soil temperatures are almost identical to test results.

Research sponsored by the U.S. Department of Energy Office of Building Technologies.

[7.4.39] Test of Condensate Subcooling Coils for Air Conditioners

V. C. Mei
F. C. Chen

N. Gulati^a
W. A. Miller

[Abstract of pp. 256-62 in *ASHRAE Transactions* 97(1), February 1991]

A 2-ton, compact air conditioner was developed for shelter environmental control application. Design requirements included a cooling capacity of 2 tons at an outdoor ambient temperature of 110°F (43°C) and an indoor dry-bulb temperature of 80°F (27°C) (wet-bulb temperature of 67°F [19°C]), with a sensible heat ratio of 0.8. A

serpentine coil was installed at the bottom of the drain pan to take advantage of condensate for improved cooling capacity. The coil was arranged in the prototype unit so that three different condensate reuse options could be tested by connecting the coil to the condenser exit, connecting it to the compressor inlet (desuper-

ORNL-DWG 92-6208

Schematic of prototype unit and refrigerant-side test setup.

heating) or completely disconnecting it from the system. The added coil did increase cooling capacity by 5.5–8.8% and lower the discharge pressure by 5–10 psi (35–70 KPa) at 95°F (35°C) outdoor temperature, compared with the test data when the coil was not used. The coil worked best when used as subcooling for refrigerant liquid. This study presents some quantitative results for

the performance of the unit when the additional coil was used as a subcooling coil, a desuperheating coil, or not used at all.

Research sponsored by the U.S. Army, Environmental Control Division.

^aU.S. Army.

[7.4.40] Study of Asymmetric Supersonic Jet Flow for Ejectors

C. M. Ho^a G. S. Knoke^b
E. W. Geller^b H. T. Liu^b
W. H. Jou^b R. W. Murphy
F. C. Chen

[Abstract of pp. 55–66 in *Thermo-Physical Aspects of Energy Conversion*, AES-Vol. 16, 1990 ASME Winter Annual Meeting, Dallas (November 25–30, 1990)]

An asymmetric subsonic jet nozzle with a small aspect ratio can entrain a mass several times higher than can a circular jet in a low subsonic flow. In this study, the Mach of the jet is extended to 2.5. The advantage of an asymmetric jet over a circular jet in enhancing mass transfer still exists in the supersonic range. The main objective here is to explore the possibility of applying the asymmetric jet to a supersonic ejector with

pressure buildup. The wall confinement was found to have a strong effect on entrainment, also.

Research sponsored by the U.S. Department of Energy Office of Building Technologies.

^aAerospace Engineering Department, University of Southern California, Los Angeles.

^bFlow Research, Inc.

[7.4.41] Evaluation of Potential Performance Additives for the Advanced LiBr Chiller

R. H. Reiner W. Del Cul^a
M. R. Ally A. Zaltash
H. Perez-Blanco^b

(Abstract of ORNL/CON-318, Oak Ridge National Laboratory, April 1991)

The effectiveness and stability of potential heat-and-mass transfer (performance) additives for an advanced lithium bromide (LiBr) chiller were evaluated in a series of experimental studies. These studies were necessary because many currently used performance additives decompose at the high generator temperatures (220°C–260°C) desired for this advanced LiBr chiller. For example, one common performance additive, 2-ethyl-1-hexanol (2EH), reacts with the

corrosion inhibitor, lithium chromate (Li₂CrO₄), even at moderate generator temperatures (180°C). These stability problems can be decreased by using less-reactive corrosion inhibitors such as lithium molybdate (Li₂MoO₄) and by using more stable performance additives such as 1-heptanol (HEP) or 1H,1H,7H-dodecafluoro-1-heptanol (DFH). There seems to be a trade-off between additive stability and effectiveness; in other words, the most effective performance additives

are not the most stable ones. These studies indicate that HEP or DFH may be effective in the advanced LiBr chiller if Li_2MoO_4 is used as a corrosion inhibitor.

Research sponsored by the U.S. Department of Energy
Office of Building Technologies.

^aChemistry Division.

^bPennsylvania State University.

ORNL-DWG 90-15946

Schematic of minilabsorber apparatus used to evaluate performance additive effectiveness.

[7.4.42]

System Reconfiguration Analysis Program (SYSRAP) User's Manual

J. B. Patton^a

D. T. Rzy

J. S. Lawler^b

(Abstract of ORNL-6575, Oak Ridge National Laboratory, April 1991)

This report describes the installation, use, functional capabilities, algorithms, and data-handling techniques of a distribution-automation-applications software package. SYSRAP was developed as part of the Athens Automation and Control Experiment (AACE) to assess system reconfiguration opportunities and volt/var control on the radial distribution feeders

of the Athens Utilities Board (AUB). The AACE was a large-scale distribution automation research project conducted on the AUB system in Athens, Tennessee. The SYSRAP software was developed on a personal computer to facilitate the incorporation of new hardware and software tools at low cost and because the mainframe computer used for the distribution automation system at

AUB was fully occupied by the real-time Supervisory Control and Data Acquisition software. SYSRAP uses a highly detailed distribution feeder model including voltage-sensitive loads. Comparison of experimental observations and SYSRAP results have proven the adequacy of the computer program for simulating system response to

reconfiguration and volt/var control that affect the feeder voltage profile.

Research sponsored by the U.S. Department of Energy
Office of Energy Management.

^aConsultant.

^bUniversity of Tennessee.

[7.4.43] Advantages of Enthalpy-Temperature Diagrams for Nonazeotropic Mixtures

J. R. Sand
E. Granryd^a
J. Conklin^b

(Abstract of Proceedings of the XVIIIth Congress of Refrigeration, Montreal, Quebec, August 10-17, 1991)

The enthalpy-temperature diagram for nonazeotropic refrigerant mixtures (NARMs) has illustrative and useful features, combining the advantages of the entropy-temperature diagram and the enthalpy-pressure diagram commonly used in the refrigeration and heat-pump industry. Plotting temperature versus enthalpy has similar advantages to plotting pressure versus enthalpy, with the additional advantage of depicting the temperature profiles for both sides of the heat-exchange equipment during the cycle. This is particularly useful for analyzing the vapor-compression refrigeration cycle using NARMs, where nonisothermal phase-change processes occur. Problems such as heat exchanger pinch-points and wet compression are easily detected. The possible cycle enhancement due to a liquid-to-suction heat exchanger is readily apparent. This paper presents and discusses examples of enthalpy-temperature diagrams.

Research sponsored by the U.S. Department of Energy
Office of Building Technologies.

^aThe Royal Institute of Technology, Stockholm, Sweden.

^bEngineering Technology Division.

[7.4.44] Leaders in the Electric Utility Industry Do Least-Cost Planning

E. Yourstone^a
M. Schweitzer
E. Hirst

(Abstract of pp. 24-31 in *Planning Review*, January/February 1991)

This paper presents key findings from a recent study performed by Oak Ridge National Laboratory on the least-cost planning processes of 29 utilities. Following a brief description of the research methods used, the plans are discussed in detail. Both long-term plans and their associated short-term action plans are treated, with substantial attention to the specific supply- and demand-side resources selected to meet future

electricity requirements. The paper concludes with a discussion of the changing resource mix used by electric utilities and the importance of action plans in implementing long-term plans.

Research sponsored by the U.S. Department of Energy
Office of Conservation and Renewable Energy.

^aConsultant, Albuquerque, New Mexico.

[7.4.45] Estimated Size and Performance of a Natural Gas Fired Stirling for Domestic Refrigeration Applications

D. M. Berchowitz^a
J. A. Shonder

(Abstract of *XVIIIth International Congress of Refrigeration*, Montreal, August 10-17, 1991)

Calibrated calculations are used to optimize and size an integrated Stirling cooler and engine (referred to as the Duplex configuration) for application in domestic food preservation. The fuel source for this engine is natural gas. Questions concerning life, noise, and performance are addressed with reference to existing hardware. For example, noise levels are extremely low because the fuel is combusted externally in a shrouded combustor; in addition, vibration levels are lower than conventional refrigerator compressors. Recuperation of the exhaust gas heat allows the unit to discharge exhaust at a low

temperature. Operating costs of conventional electrically powered refrigerators and the natural-gas-fired Duplex Stirling are compared. By including a small linear alternator, some electrical power generation is also possible, which could power the internal light and other accessories. Concept-demonstration models have been built and tested.

Research sponsored by the U.S. Department of Energy
Office of Building Technologies.

^aSunpower, Inc., Athens, Ohio.

[7.4.46] The National Fuel End-Use Efficiency Field Test: Energy Savings and Performance of an Improved Energy Conservation Measure Selection Technique

M. P. Ternes
L. S. Williams

P. S. Hu
P. Goewey^a

(Abstract of ORNL/CON-303, Oak Ridge National Laboratory, March 1991)

The Oak Ridge National Laboratory developed and field tested a selection technique in Wisconsin for residential energy conservation measures (ECMs). Results show that the technique more than doubles the annual energy savings per dollar expenditure of a weatherization program compared with a priority system. Improved by the Wisconsin Energy Conservation Corporation, the technique currently analyzes a house to identify all ECMs that are cost effective in the building envelope, space-heating system, and water-heating system. The benefit-to-cost ratio (BCR) for each ECM is determined, and cost-effective ECMs (BCR 1) are selected, taking interactions between ECMs into account. The objectives of this project were to verify the energy savings and program improvements achieved from using an advanced measure-selection technique in conservation programs and determine whether utility investments in residential gas end-use conservation are cost effective. For the duration of the field test, eighty-nine houses with the following characteristics were monitored: occupants were low-income, houses were single-family and detached (but not mobile homes), and primary space- and water-heating systems were gas fired. Forty-five audit houses received a mix of ECMs as selected by the measure-selection technique, and 44 served as a control group. Preweatherization data were collected from January–April 1988, and post-weatherization data were collected from December 1988–April 1989. Gas

consumption and indoor temperature were monitored weekly during the two winters. A house energy consumption model and regression analysis were employed to normalize the space-heating energy savings to average outdoor temperatures and a 68°F indoor temperature. Space- and water-heating energy savings for the audit houses were adjusted by the savings for the control houses. The average savings of 257 therms per year for the audit houses were 17% of the average preweatherization house gas consumption and 78% of that predicted. Average space-heating energy savings were 252 therms per year (25% of preweatherization space-heating energy consumption and 85% of the predicted value), and average water-heating energy savings were five therms per year (2% of preweatherization water-heating energy consumption and 17% of predicted). The overall BCR for the installation of the ECMs was 1.24 using the same assumptions followed in the selection technique (no administration cost, residential fuel costs, real discount rate of 0.05, and no fuel escalation). A weatherization program would be cost effective at an administration cost of less than \$335 per house. On average, the indoor temperature increased in the audit houses by 0.5°F following weatherization, and decreased in the control houses by 0.1°F.

Research sponsored by the U.S. Department of Energy
Office of Buildings Research.

^aNational Fuel Gas Distribution Corporation.

[7.4.47] Tubeside Evaporation of Nonazeotropic Refrigerant Mixtures from Two Enhanced Surfaces

J. C. Conklin^a
E. A. Vineyard

(Abstract of the 1990 ASME Winter Annual Meeting, Dallas, ASME Pamphlet 90-WA/HT-8, The American Society of Mechanical Engineers, New York, November 1990)

As part of the Building Equipment Research Program at Oak Ridge National Laboratory, nonazeotropic refrigerant mixtures (NARMs) are being investigated to replace chlorofluorocarbon compounds. The evaporation of NARMs is not isothermal, which can improve the heat-exchanger effectiveness of an evaporator as well as thermodynamic cycle efficiencies. The evaporating heat transfer coefficient for four nonazeotropic mixtures of refrigerants R143a and R124 was investigated for two inside tube surfaces, one having spiral ridged fins and the other, a corrugated or fluted surface. Refrigerant R22 was also evaporated for a performance comparison of the finned and fluted surfaces. The measured pressure drop and the heat-transfer coefficient for the complete evaporation from 25% quality to a slight amount of superheat of the NARMs and R22 are presented as a function of

mass flux for both enhanced surfaces. Both the heat transfer coefficient and the pressure drop of the fluted tube are higher than those of the finned tube at a given refrigerant mass flux and at a given heat exchanger load for all the refrigerant mixtures. When plotted as a function of the mass fraction of R143a, the heat transfer coefficient for the fluted tube is minimal, at approximately 40% by mass (51% by mole) of R143a. However, the heat transfer coefficient for the finned tube does not show a degradation as a function of R143a mass fraction, and it appears to be a linear function of the mass fraction of R143a for a given mass flux.

Research sponsored by the U.S. Department of Energy Office of Building Technologies.

^aEngineering Technology Division.

[7.4.48] The Alternative Refrigerant Dilemma for Refrigerator-Freezers: Truth or Consequences

E. A. Vineyard

[Abstract of ASHRAE Transactions 97(2)]

In response to regulatory actions arising from the Montreal Protocol and the National Appliance Energy Conservation Act, refrigerator-freezer manufacturers and government researchers are investigating energy-efficient replacement refrigerants for R12. The Montreal Protocol, enacted in 1987, requires that by mid-1998 the production of R12 be reduced to 50% of 1986 levels. As a result, a replacement refrigerant must be chosen as soon as possible to allow time for design changes, product-life tests, and retooling. In an effort to select a refrigerant that has minimal impact on energy consumption and the

environment, a screening analysis of potential refrigerants was performed that resulted in the selection of six candidates. The screening results show that R134a, R134, R152a, R134a/R152a, R22/R152a/R124, and R134a/R152a/R124 are the most promising refrigerants based on the following criteria: ozone-depletion potential, greenhouse-warming potential, coefficient of performance, and safety. Following the screening study, energy consumption tests were performed for the three pure refrigerants in an 18-ft³ (0.51-m³) automatic-defrost top-mount refrigerator-freezer in accordance with the

Association of Home Appliance Manufacturers standard. The results indicate an increased energy consumption of 6.8%, 7.3%, and 7.3% for R134, R152a, and R134a, respectively. However, when the effects of compressor efficiency are taken into account, the normalized energy consumption

results in an increase of only 2.7% for R152a and 5.5% for both R134a and R134.

Research sponsored by the U.S. Department of Energy
Office of Building Technologies.

[7.4.49] Tubeside Condensation of Nonazeotropic Refrigerant Mixtures for Two Enhanced Surfaces

J. C. Conklin^a
E. A. Vineyard

(Abstract of *Proceedings of the ASME/JSME Thermal Engineering Joint Conference*, Third ASME-JSME Thermal Engineering Joint Conference, Reno, Nevada, March 17-22, 1991)

As part of the Building Equipment Research Program at Oak Ridge National Laboratory, nonazeotropic refrigerant mixtures (NARMs) are being investigated to replace chlorofluorocarbon compounds. The condensation of NARMs is not isothermal, thereby improving the heat-exchanger effectiveness of a condenser as well as thermodynamic cycle efficiencies. The total condensing heat-transfer coefficients for refrigerant R22 and for four nonazeotropic mixtures of refrigerants R143a and R124 were measured and are presented as a function of mass flux for two inside tube surfaces, with either spiral ridged fins or a spirally corrugated surface. The total condensing coefficient for the finned tube is higher than for the fluted tube, at any given refrigerant mass flux for all the refrigerant mixtures. The measured irrecoverable pressure

drop for the finned tube is approximately half that for the fluted tube; thus, the finned tube has the better thermal performance. The condensing heat-transfer coefficient is also presented as a function of the mass fraction of R143a for three values of mass flux. Degradation of the condensing coefficient is apparent for intermediate values of R143a mass fraction but has different trends with respect to mass flux for the two enhanced surfaces. Therefore, the geometry of the enhanced surface appears to affect the physical mechanism for condensation of NARMs.

Research Sponsored by the U.S. Department of Energy
Office of Building Technologies.

^aEngineering Technology Division.

[7.4.50] Heat Exchanger Thermal Performance for Two Nonazeotropic Refrigerant Mixtures

J. C. Conklin^a
E. A. Vineyard

(Abstract of *Proceedings of the XVIIIth International Congress of Refrigeration*, August 1991)

Two nonazeotropic refrigerant mixtures (NARMs), the first consisting of 71% R22 and 29% R114 and the second consisting of 75% R143a and 25% R124, were studied at various mass flow rates and heat loads in an experimental

apparatus at Oak Ridge National Laboratory. The measured thermal performance of the evaporator and condenser are presented in the number of transfer units (NTUs) and effectiveness (ϵ). Because the phase-change process of the NARMs

is nonisothermal, a specific heat for the two-phase region can be defined. This two-phase specific heat for the NARMs varies with respect to enthalpy. Because the standard NTU-e analysis is valid only for constant specific heat fluids, an analysis that considers variable-specific heat fluids is used to compare analytical predictions

with observed thermal performance. The predicted and measured results agree closely when the pressure drop is low.

Research sponsored by the U.S. Department of Energy
Office of Building Technologies.

*Engineering Technology Division.

[7.4.51] A Summary of the Status of Biomass Conversion Technologies and Opportunities for Their Use in Latin America

D. B. Waddle
R. D. Perlack

[Abstract of *Proceedings of the Union Pan Americana de Asociaciones de Ingenieros (UPADI)*, Washington, D.C., August 19–24, 1990, and *Proceedings of the 6th International Symposium on Agricultural Food Processing Wastes*, Chicago, December 17–18, 1990]

Biomass plays a significant role in energy use in developing countries; however, these resources are often used very inefficiently. Recent technology developments have improved conversion efficiencies for utility-scale technologies. These developments may be of interest in the wake of several countries' recent policy changes with respect to independent power production. Efforts are also being directed at developing biomass conversion technologies that can interface or compete with internal combustion

engines for small, isolated loads. This paper reviews the technological status of biomass conversion technologies appropriate for commercial, industrial, and small utility applications in developing countries. Market opportunities, constraints, and new technologies are also discussed.

Research sponsored by the U.S. Agency for International
Development Office of Energy.

[7.4.52] Electricity Savings Among Participants Three Years After Weatherization in Bonneville's 1986 Residential Weatherization Program

D. L. White
M. A. Brown

(Abstract of ORNL/CON-305, Oak Ridge National Laboratory, September 1990)

This study continues evaluations of the Bonneville Power Administration's Long-Term Residential Weatherization Program (RWP). Data were collected from households weatherized in 1986 under Bonneville's Data Gathering Project (DGP) and from a control group of nonparticipants. An update of the original analysis, this study examines retrofit activities, costs, and electricity savings one and two years

after participation in the 1986 Long-Term RWP. Specifically, this update examines electricity savings three years after weatherization. The households selected come from seven of the eight utilities examined in the original analysis. The original analysis showed that in the 1986 Long-Term RWP, 83% of audit-recommended measures were installed, approximately the same rate participants attained in the Residential

Weatherization Pilot Program (1980-82), the Interim RWP (1982-83), and the 1985 Long-Term RWP. Also, as in previous program years, the installation rate was higher for recommended measures with greater estimated energy savings. Although Bonneville's retrofit costs have remained fairly constant over time, total retrofit costs have increased from \$1700 per house in 1982 to \$2400 in 1986 (in 1986 dollars); additional costs have been absorbed by participating households and utilities. Similarly, *Bonneville's cost* per estimated kWh of first-year electricity savings has stayed at about 27 cents/kWh while the average *total cost* has risen from 28 cents/kWh in 1982 to 44 cents/kWh in 1986 (in 1986 dollars). The characteristic difference in preprogram electricity consumption between participant and control group is becoming less distinct. In the Bonneville Residential Weatherization Pilot Program conducted 1980-1982, participating households used 30,280 kWh/year in the preweatherization year, while nonparticipants used 25,780 kWh/year. Thus, participants used nearly 18%

more electricity than nonparticipants. In the 1986 Long-Term RWP, participants used 24,310 kWh (weighted) in the preretrofit year, while control-group households used an average 22,270 kWh (weighted). Participants used only 9% more electricity than nonparticipants. From the pilot program to the 1986 Long-Term DGP, the difference in preprogram electricity consumption between participants and control groups declined by almost 50%. For the 1986 Long-Term RWP overall, the savings participants experienced were substantial. During the first year after weatherization, weighted net savings averaged 3060 kWh, or almost 13% of the previous year's energy consumption for the updated sample. In the second postweatherization year, a weighted average of 2112 kWh was saved, amounting to 9% of preweatherization energy use. In the third postweatherization year, a net weighted average of 2140 kWh was saved, also 9% of preweatherization electricity use.

Research sponsored by Bonneville Power Administration Office of Energy Resources.

[7.4.53] Analysis of Annual Thermal and Moisture Performance of Radiant Barrier Systems

K. E. Wilkes

(Abstract of ORNL/CON-319, Oak Ridge National Laboratory, April 1991)

This report summarizes a project to model the annual thermal and moisture performance of radiant barrier systems installed in residential attics. A previously developed model for the thermal performance of such attics was modified to allow for estimates of moisture condensation on the underside of radiant barriers laid directly on top of existing attic insulation. The model was partially validated by comparing its predictions of ceiling heat flows and moisture condensation with data and visual observations made during a field experiment with full-size houses near Knoxville, Tennessee. Since the model predictions were found to be in reasonable agreement with experimental data, the models were used to estimate annual energy savings and moisture-

Calculated annual cooling load reductions due to the addition of a clean horizontal radiant barrier on top of R-11 ceiling insulation.

accumulation rates for a wide variety of climatic conditions. Also, the results have been used to identify locations where radiant barriers are cost effective as well as where they have potential for causing moisture problems.

Research sponsored by the U.S. Department of Energy Office of Buildings Energy Research and the Electric Power Research Institute.

[7.4.54] Thermal Model of Attic Systems with Radiant Barriers

K. E. Wilkes

(Abstract of ORNL/CON-262, Oak Ridge National Laboratory, August 1991)

This report summarizes the first phase of a project to model the thermal performance of radiant barriers. The objective here has been to develop a refined model for the thermal performance of attics—with and without radiant barriers—in residential houses and to verify the model by comparing its predictions against selected experimental thermal-performance data. Models have been developed and implemented on an IBM PC/AT computer. The validity of the models has been tested by comparing their predictions with ceiling heat fluxes measured in a number of laboratory and field experiments. Cumulative heat flows predicted by the models were usually within about 5–10% of measured values. In future phases of the project, the models for attic and radiant barrier performance will be coupled with a whole-house model, and further comparisons with experimental data will be made. Following this, the models will be used to provide an initial assessment of the energy-savings potential of radiant barriers in various configurations and under various climatic conditions.

Attic heat transfer mechanisms.

Research sponsored by the U.S. Department of Energy Office of Buildings Energy Research and the Tennessee Valley Authority.

[7.4.55] Effect of Additives on the Film Heat Transfer Coefficients of (Li,K,Na)NO₃ and LiBr Aqueous Mixtures

A. Zaltash
R. L. Linkous

M. R. Ally
R. H. Reiner

(Abstract of Proceedings of the XVIIIth International Congress of Refrigeration, Montreal, August 10-17, 1991)

Heat and mass transfer rates are important factors controlling the cycle performance of an absorption heat pump. This study examines the use of additives for improving the film heat transfer coefficients of (Li,K,Na)NO₃ and LiBr aqueous mixtures. Two additives (Galden Perfluorinated Fluid and 3M FC-5312 Fluorinert) were tested with 77 wt% (Li, K, Na) NO₃ aqueous mixture. Both additives have high thermal stability. Five additives were tested with 61 wt% LiBr aqueous solution. These additives are 2-ethyl-1-hexanol, 1H,1H,7H-dodecafluoro-1-heptanol, 1-heptanol, 1,1,1-trifluoro-2-octanol and a mixture of 400 wppm 2-ethyl-1-hexanol/weight of LiBr solution with varying amounts of 2-methyl-2-propanol. The results are based on the ratio of the film heat transfer coefficient of the working fluid at a given additive concentration (w) to its value without any additive (w = 0), $h_{o \text{ exp. } w} / h_{o \text{ exp. } w=0}$. This ratio represents the effect of additives on the film heat transfer coefficient.

The two additive used for (Li, K, Na)NO₃ did not improve the film heat transfer coefficient ($h_{o \text{ exp. } w} / h_{o \text{ exp. } w=0}$ ranging from 0.86 to 1.0). However, significant improvements were achieved when 2-ethyl-1-hexanol and 1-heptanol were added to aqueous LiBr solution. In these two cases, the ratios of $h_{o \text{ exp. } w}$ to $h_{o \text{ exp. } w=0}$ were as high as 1.22 and 1.48 for 2-ethyl-1-hexanol and 1-heptanol, respectively. Results show that the heat transfer enhancement depends on the additive concentration and the film mass flow rate. The ratio $h_{o \text{ exp. } w} / h_{o \text{ exp. } w=0}$ in LiBr with approximately 200 wppm of 2-ethyl-1-hexanol is shown to vary between 1.35 and 1.20, and the mass flow rate of fluid entering the absorber, between 399.6 and 603.1 g/min, respectively.

Research sponsored by the U.S. Department of Energy Office of Industrial Programs and the Office of Building Technologies.

ORNL-DWG 90-15946R

Schematic of the apparatus used to evaluate the effectiveness of additives on aqueous LiBr solution.

Publications

and Professional Activities

8. PUBLICATIONS AND PROFESSIONAL ACTIVITIES

8.1 ENERGY DIVISION ADVISORY COMMITTEE 1991

Dr. Bruce G. Buchanan

Computer Science Department
University of Pittsburgh
206 Mineral Industries Building
Pittsburgh, Pennsylvania 15260
Phone: (412) 624-9183

Dr. Allan Hirsch
(Chairman)

Vice President, Environmental Sciences
Director Washington Operations
Midwest Research Institute
5109 Leesburg Pike
Suite 414
Falls Church, Virginia 22041
Phone: (703) 671-0400

Dr. Helen M. Ingram

Director, Udall Center for Studies in Public Policy
The University of Arizona
803/811 East First Street
Tucson, Arizona 85719
Phone: (602) 621-7189

Mr. Calvin D. MacCracken

President, Calmac Manufacturing Corporation
101 West Sheffield Avenue
P. O. Box 710
Englewood, New Jersey 07631
Phone: (201) 569-0420

Ms. Jacqueline B. Shrago

Director, Office of Technology Transfer
405 Kirkland Hall
Vanderbilt University
Nashville, Tennessee 37240
Phone: (615) 322-7056

Dr. Martin Williams

Professor, Department of Economics
Northern Illinois University
DeKalb, Illinois 60115
Phone: (815) 753-6960

8.2 ENERGY DIVISION PERSONNEL BY DISCIPLINE
[Full-time equivalents (FTEs)]
September 1991

Discipline	IAAS ^a	EEAS	CTA	ERRS	P&C	Division Administration	Total (FTEs)
Technical Professional							
Social sciences							
Anthropologists	2.0						2.0
Economists	2.0	11.5		1.0		1.0	14.5
Geographers	2.0	2.0	6.0	1.0	1.0		12.0
Planners	2.0				1.0		4.0
Political scientists	3.0			.5			3.0
Sociologists	1.5						2.0
Other	3.0			2.5			3.0
<i>Total social sciences</i>	<i>15.5</i>	<i>13.5</i>	<i>6.0</i>		<i>2.0</i>	<i>1.0</i>	<i>40.5</i>
Physical and life sciences							
Biologists	4.5		1.0				5.5
Chemists	1.0			2.0			3.0
Ecologists	1.0						1.0
Geologists	3.0		1.0				4.0
Meteorologists	2.0			4.0			2.0
Physicists	2.0			6.0			6.0
<i>Total physical and life sciences</i>	<i>13.5</i>		<i>2.0</i>				<i>21.5</i>
Engineering Sciences							
Chemical engineers	1.0		1.0	5.0			7.0
Civil engineers			4.0				4.0
Electrical engineers	1.0		1.0	4.0			6.0
Engineering physicists				1.0			1.0
Engineering scientists	1.0			2.0			3.0
Environmental engineers	1.0			15.0			1.0
Mechanical engineers	4.0			1.0		1.5	20.5
Nuclear engineers				2.0		1.0	2.0
Other				30.0			2.0
<i>Total engineering sciences</i>	<i>8.0</i>		<i>6.0</i>			<i>2.5</i>	<i>46.5</i>
Data Systems							
Computer sciences		1.0	2.5				3.5
Mathematicians/statisticians	1.0		6.0	1.0			8.0
Operations research			2.0				2.0
Other	1.0		1.0	1.0			2.0
<i>Total data systems</i>	<i>2.0</i>	<i>1.0</i>	<i>11.5</i>	<i>39.5</i>			<i>15.5</i>
<i>Total technical professionals</i>	<i>39.0</i>	<i>14.5</i>	<i>25.5</i>		<i>2.0</i>	<i>3.5</i>	<i>124.0</i>
Administrative and Technical Support							
Accountants						2.0	2.0
Administrative assistants						1.0	1.0
Administrative support	6.5	4.0	7.0	9.0	1.0	4.0	31.5
Technical support	4.0	1.0	3.0	7.0	1.0		16.0
<i>Total administrative and technical support</i>	<i>10.5</i>	<i>5.0</i>	<i>10.0</i>	<i>16.0</i>	<i>2.0</i>	<i>7.0</i>	<i>50.5</i>
<i>Total</i>	<i>49.5</i>	<i>19.5</i>	<i>35.5</i>	<i>55.5</i>	<i>4.0</i>	<i>10.5</i>	<i>174.5</i>

^aIAAS = Integrated Analysis and Assessment Section; EEAS = Energy and Economic Analysis Section; CTA = Center for Transportation Analysis; ERRS = Efficiency and Renewables Research Section; and P&C = Planning and Coordination.

8.3 ENERGY DIVISION PROFESSIONAL HONORS AND AWARDS FY 1991

The Airlift Deployment Analysis System (ADANS) Team received a Martin Marietta Energy Systems, Inc., *Significant Event Award* for their role in the development of ADANS for the Military Airlift Command. Energy Division staff members who contributed to the project were I. K. Busch, S. W. Diegel, K. G. Gilley, I. G. Harrison, M. R. Hilliard, R. D. Kraemer, C. Liu, A. K. Sexton, and R. S. Solanki. The ADANS team was also nominated for the Franz Edelman Award for Management Science Achievement.

Bownds, J. M., received the National Association for Search and Rescue Hal Foss Award for developing a mathematical algorithm used in search management.

Brown, M. A., received the Gold Medal Award, along with H. Major of the U.S. Department of Energy, for the best paper published in the *Journal of Technology Transfer* in 1989/1990. The paper is entitled "Technology-Transfer Strategies for DOE's Conservation Programs."

Cannon, J. B., received a Martin Marietta Energy Systems, Inc., *Significant Event Award* for overseeing the preparation of the Nuclear Regulatory Commission's (NRC's) *Generic Environmental Impact Statement for License Renewal of Nuclear Plants*.

Carnes, S. A., guest editor, along with R. L. Miller, E. L. Hillsman, J. H. Sorensen, and D. L. Feldman, were awarded a 1991 Technical Communication Award for the publication "Integrated Environmental Assessment for a Major Project"

recognized as "Distinguished in Technical Reports" by the East Tennessee Chapter of the Society for Technical Communication.

Chen, F. C., was selected as an Accreditation Visitor for Mechanical Engineering by the Accreditation Board for Engineering and Technology.

Courville, G. E., received a Federal Laboratory Consortium Award for Excellence in Technology Transfer for 1991.

Kuliasha, M. A., received a Martin Marietta Energy Systems, Inc., *Significant Event Award* for leading the preparation of the ORNL Tiger Team Action Plan in response to the Tiger Team Report.

Liu, C., received the Association of American Geographer's 1991 Applied Geography Project Citation Award, along with B. Ralston of UT, for work on the Bangladesh Transportation Modeling System.

McConnell, B. W., received a Technical Achievement Award at the Martin Marietta Energy Systems Awards Night, along with a team of seven other staff members from other divisions, for leadership and technical contributions to the design, construction, and testing of a novel axial gap, variable speed ac, low temperature superconducting motor.

McLean, R. B., received a Martin Marietta Energy Systems, Inc., *Significant Event Award* for managing the preparation of the NRC's *Generic Environmental Impact Statement for License Renewal of Nuclear Power Plants*.

Peelle, E. B., was awarded an Honorary Doctor of Laws Degree from Miami University of Ohio for her outstanding

contribution to the nation's environmental consciousness.

Sand, J. R., and E. A. Vineyard were awarded a 1990 Best Paper Award by the American Society of Heating, Refrigerating and Air Conditioning Engineers, Inc., for their paper, "Experimental Performance of Ozone-Safe Alternative Refrigerants."

Shelton, R. B., K. H. Zimmerman, R. H. Selden, L. A. Daniel, and others were awarded a 1991 Technical Communication Award recognizing "Merit in Periodic Activity Reports" by the East Tennessee Chapter of the Society for Technical Communication, for the report *The Energy Division*

Annual Progress Report for Period Ending September 30, 1989.

Southworth, F., was elected to Director of the Energy Specialty Group of the Association of American Geographers for a three-year term.

Wendt, R. L., P. M. Love, and G. L. Anderson were awarded a 1991 Technical Communication Award recognizing "Merit in House Organs" by the East Tennessee Chapter of the Society for Technical Communication, for the brochure *Roof Research Center UPDATE*.

Wilbanks, T. J., was elected Vice-President of The Association of American Geographers for the term July 1991 to June 1992.

8.4 ENERGY DIVISION PROFESSIONAL ACTIVITIES FY 1991

Bjornstad, D. J., Director, Secretary of Energy Advisory Board Task Force on Economic Analysis and Modeling Related to Energy, 1991.

Blasing, T. J., Adjunct Associate Professor of Geography, University of Tennessee, Knoxville, 1981 to present.

Blasing, T. J., Referee, Proposals to the National Science Foundation, 1991.

Bownds, J. M., Referee, *Advances in Water Resources*, 1991.

Bownds, J. M., Referee, *Mathematical Reviews*, 1968 to present.

Bownds, J. M., Instructor, ORNL Saturday Academy of Computing and Mathematics, 1989 to present.

Bownds, J. M., Adjunct Professor of Mechanical and Aerospace Engineering, North Carolina State University, 1990 to present.

Bronzini, M. S., Committee 2-39, Transportation Engineering Textbook

Needs, Institute of Transportation Engineers, 1989-1992.

Bronzini, M. S., Planning Group on Strategic Issues in Domestic Freight Transportation, Transportation Research Board, National Research Council, 1990-1991.

Bronzini, M. S., Steering Committee, Marine Transportation Strategic Planning Workshop, Transportation Research Board, National Research Council, 1991.

Bronzini, M. S., Chairman, Study Committee on Landside Access to U.S. General Cargo Ports, Transportation Research Board, National Research Council, 1990 to present.

Bronzini, M. S., Referee, *Transportation Research Board*, 1981 to present.

Bronzini, M. S., Referee, *Logistics and Transportation Review*, 1976 to present.

Bronzini, M. S., Referee, *Transportation Research*, 1977 to present.

- Bronzini, M. S., Civil Engineering Program Evaluator, Accreditation Board for Engineering and Technology, 1989 to present.
- Bronzini, M. S., Group 1 Council, Transportation Research Board, National Research Council, 1991 to present.
- Bronzini, M. S., Referee, *Journal of Transportation Engineering*, 1930 to present.
- Bronzini, M. S., Committee A3C10, Transportation of Hazardous Materials, Transportation Research Board, National Research Council, 1990 to present.
- Bronzini, M. S., Referee, *Journal of the Transportation Research Forum*, 1979 to present.
- Bronzini, M. S., Referee, *Interfaces*, 1986 to present.
- Bronzini, M. S., A1B51, Task Force on Freight Transportation Data, Transportation Research Board, National Research Council, 1989 to present.
- Bronzini, M. S., Committee A5004, Transportation Education and Training, Transportation Research Board, National Research Council, 1989 to present.
- Bronzini, M. S., Committee A1B01, Inland Water Transportation, Transportation Research Board, National Research Council, 1981 to present.
- Brown, M. A., Editorial Board of *Economic Geography*, 1991-1994.
- Brown, M. A., Editorial Board of *Home Energy*, 1990-1993.
- Brown, M. A., National Councillor, Association of American Geographers, 1988-1991.
- Brown, M. A., Co-Editor of the 1991-92 AAG's Energy and Environmental Specialty Group Newsletter.
- Brown, M. A., Editorial Board of *The Professional Geographer*, 1987-1990.
- Brown, M. A., Adjunct Associate Professor, Department of Geography, University of Tennessee, 1989 to present.
- Busch, I., The Washington Operations Research/Management Science Council.
- Campbell, A. W., Committee Member, Ecology Committee, Air and Waste Management Association, 1991.
- Carnes, S. A., Referee, *The Environmental Professional*, 1987 to present.
- Carnes, S. A., Editorial Board, *Verification Technologies*, 1990 to present.
- Christian, J. E., ASHRAE 90.2P, Energy Standard for Residential Buildings, 1985-1992.
- Christian, J. E., ASHRAE TC 4.4 Technical Committee on Insulation and Vapor Retarder Performance, 1992-1993.
- Christian J. E., ASHRAE TC 4.7, Technical Committee on Energy Calculations, 1991-1993.
- Christian, J. E., Board of Directors, Building Thermal Envelope Coordinating Council, 1990-1992.
- Curlee, T. R., Member, Municipal Solid Waste Peer Review Panel, U.S. Department of Energy, Office of Waste Reduction, 1990 to present.
- Curlee, T. R., Formal Contributor, The National Advisory Council for Environmental Policy and Technology (NACEPT), U.S. Environmental Protection Agency, Office of the Administrator, 1990 to present.
- Curlee, T. R., Member, Knoxville Solid Waste Task Force, Office of the Mayor, City of Knoxville, 1990 to present.
- Curlee, T. R., Member, RecyclingPlas Advisory Committee, Plastics Institute of America, 1988 to present.
- Dale, S. J., Chairman, IEEE Dielectrics and Electrical Insulation Society, Meetings Committee, 1988 to present.
- Dale, S. J., Expert Advisor, U.S. National Committee of CIGRE, Study Committee 15, Insulation.
- Dale, S. J., Division II Representative, IEEE Technical Meetings Council, 1989-1990.

- Dale, S. J., U.S. Representative CIGRE Study Committee 15, Working Group 15.03 Gas Insulation and 15.06-01 Cryogenic Insulation.
- Dale, S. J., Reviewer, IEEE Transaction on Power Delivery.
- Dale, S. J., Chairman, IEEE Insulated Conductors Committee Task Force 5.12 Insulation. Systems for Gas Cables, 1982 to present.
- Dale, S. J., Member IEEE, USA Congressional Fellows Committee, 1991 to present.
- Dale, S. J., Member IEEE, USA Engineering R&D Policy Committee, 1987 to present.
- Dale, S. J., Reviewer, IEEE Transaction on Electrical Insulation.
- Ensminger, J. T., NEPA Working Group, National Association of Environmental Professionals, 1990-1992.
- Feldman, D. L., Referee, *Western Political Quarterly*, 1990 to present.
- Feldman, D. L., Senior Editor, *Forum for Applied Research and Public Policy*; Energy, Environment, and Resources Center, University of Tennessee-Knoxville, 1990 to present.
- Feldman, D. L., Referee, *Policy Sciences*, 1988 to present.
- Feldman, D. L., Referee, *The Environmental Professional*, 1988 to present.
- Feldman, D. L., Referee, *Choice*; *The Association of College and Research Libraries*, 1983 to present.
- Gant, K. S., Federal Monitoring and Assessment Center Work Group on Training and Education, 1991 to present.
- Hillsman, E. L., Member, Board of Directors, Association of American Geographers Energy and Environment Specialty Group, 1988-1991.
- Hillsman, E. L., Manuscript Reviewer, *Papers in Regional Science*.
- Hillsman, E. L., Member, Board of Directors, Association of American Geographers Applied Geography Specialty Group, 1991-1992.
- Hirst, E., Advisory Committee, Energy Conservation Coalition, 1987 to present.
- Hirst, E., Associate Editor, *Energy*, 1976 to present.
- Hirst, E., Editorial Board, *Energy Journal*, 1984 to present.
- Hirst, E., Editorial Board, *Forum for Applied Research and Public Policy*, 1991 to present.
- Hirst, E., Editorial Board, *Energy Systems and Policy*, 1984 to present.
- Hirst, E., Editorial Board, *Energy Policy*, 1984 to present.
- Hirst, E., Editorial Board, *Evaluation Exchange*, 1991 to present.
- Kerley, C. R., Member, Infrastructure Modernization Implementation Committee (IMIC), Federal Energy Management Program, 1990 to present.
- Lee, R., Editorial Board, *Energy Studies Review*, 1990 to present.
- Lee, R., Referee, *National Science Foundation*, 1978 to present.
- Lee, D. W., Reviewer, *Waste Management Journal*, 1988 to present.
- Lee, D. W., Chairman, Air and Radiation Management Committee, Environmental Engineering Division, American Society of Civil Engineers, 1990-1991.
- Lee, D. W., Member, Mixed Waste Task Committee, Air and Radiation Management Committee, Environmental Engineering Division, American Society of Civil Engineers, 1988 to present.
- Lee, D. W., Reviewer, *ASCE Journal of Hydraulics*, 1982 to present.
- Lee, D. W., Adjunct Associate Professor, North Carolina State University, Department of Mechanical and Aerospace Engineering, 1987 to present.
- Lee, R. R., Member, Executive Steering Committee, Mayor's Solid Waste Task Force, City of Knoxville, Tennessee, 1990-1991.

- MacDonald, J. M., Association of Demand-Side Management Professionals (ADSMP) Policy Subcommittee on Utility and Commercial/Industrial Interaction for Demand-Side Management, 1991 to present.
- MacDonald, J. M., ASHRAE TC 9.6 on Systems Energy Utilization, 1987 to present.
- MacDonald, J. M., Chairperson, ASTM E06.25.21, Task Group on Energy Monitoring Protocols, 1989 to present.
- MacDonald, J. M., ASHRAE TC 9.6 Subcommittee on Building Energy Monitoring, 1987 to present.
- MacDonald, J. M., ASHRAE SPC 100P on Energy Conservation in Existing Buildings, 1990 to present.
- McCold, L. N., NEPA Working Group, National Association of Environmental Professionals, 1991 to present.
- McLean, R. B., Chairman, NEPA Working Group, National Association of Environmental Professionals, 1991 to present.
- Miaou, S. P., Reviewer, *Water Resources Research*, 1991.
- Mixon, W. R., Member, Monitoring Advisory and Review Committee for the Texas LoanSTAR Program, 1990 to present.
- Mixon, W. R., Chairman, ASHRAE TC 9.6, Subcommittee on Building Energy Monitoring, 1991 to present.
- Mixon, W. R., Member, Radiant Barrier System Technical Panel, 1987 to present.
- Mixon, W. R., Member, ASHRAE TC 9.6 on Systems Energy Utilization, 1985 to present.
- Russell, M., Chairman, Oversight Review Board, National Acid Precipitation Assessment Program, 1989 to present.
- Russell, M., Member, Environmental Advisory Committee, Westinghouse Savannah River Corporation, 1990.
- Russell, M., Member, Advisory Panel on Environmental Risk Communication, Center for Environmental Information, Inc., 1989 to present.
- Russell, M., Member, International Advisory Council on the Economic Development of Hainan in Harmony with the Natural Environment, Haikou, People's Republic of China, 1990 to present.
- Russell, M., Member, Mitigation Panel, Global Climate Change Committee, National Academy of Science/National Academy of Engineering, 1989 to present.
- Russell, M., Member, National Research Council, Board on Environmental Studies and Toxicology, 1988–1991.
- Russell, M., President, Southern Appalachian Man and the Biosphere Foundation, 1990 to present.
- Russell, M., Member, Editorial Board, *The Annals of Regional Science*, 1988 to present.
- Russell, M., Member, Board of Editors, *Journal of Cultural Economics*, 1978 to present.
- Russell, M., Member, Advisory Committee, Wharton Risk and Decision Processes Center, 1986 to present.
- Sorensen, J., Member, National Research Council, Commission on Physical Sciences, Mathematics, and Resources, Earth Sciences Board, Subcommittee on Earthquake Research, 1988–1991.
- Sorensen, J., Proposal Reviews for Critical Engineering Systems, Earthquake Hazards Mitigation Program, National Science Foundation, 1990 to present.
- Southworth, F., Director, Energy Specialty Group, Association of American Geographers, 1991–1994.
- Tonn, B. E., Reviewer, National Science Foundation, 1990–1991.
- Wilbanks, T. J., Treasurer and Member of the Board of Directors, 27th International

- Geographical Congress (1992), 1986 to present.
- Wilbanks, T. J., Vice Chairman, U.S. National Committee for the International Geographical Union, National Academy of Sciences/National Research Council, 1989 to present.
- Wilbanks, T. J., Editorial Board, *Annals of the Association of American Geographers*, 1987 to present.
- Wilbanks, T. J., Vice-President, Association of American Geographers, 1991–1992.
- Wilbanks, T. J., Expert Group on Energy and Electricity Supply and Demand for the 1991 Senior Expert Symposium on Electricity and the Environment (Helsinki), 1990–1991.
- Wilbanks, T. J., Editorial Board, *Forum for Applied Research and Public Policy*, 1990 to present.
- Wilbanks, T. J., Member, Advisory Committee, Energy Conservation Services Program, Office of Energy and Infrastructure, U.S. Agency for International Development, 1989 to present.
- Wilbanks, T. J., Councillor, American Geographical Society, 1985 to present.
- Wilbanks, T. J., Joint Steering Committee for Association between the Oak Ridge National Laboratory and the Universidad Nacional Autonoma de Mexico, 1990 to present.
- Wilbanks, T. J., Atlantic Council Working Group on Technology Transfer and the Agenda for the Environment and Development, 1991–1992.
- Wilbanks, T. J., Member, Geography Consensus Planning Committee, National Assessment of Educational Progress, 1991 to present.
- Wilbanks, T. J., Member, Geography Task Force, National Council on Education Standards and Testing, 1991 to present.
- Wilbanks, T. J., Committee on Energy Efficiency, United States Energy Association, 1990 to present.
- Wilbanks, T. J., Executive Committee, U.S. Working Group for the Global Energy Efficiency Initiative, 1990 to present.
- Wilkes, K. E., Chairman, ASTM C16.21:104 Task Group on Thermal Performance of Radiant Barriers, 1991 to present.
- Wilkes, K. E., ASHRAE TC4.9, Technical Committee on Building Envelope Systems, Research Project Monitoring Subcommittee Chairman, 1989 to present.
- Wilkes, K. E., ASTM C16 Task Group on C687 Method for R-Value of Loose-Fill Insulation, 1991 to present.
- Wilkes, K. E., ASHRAE TC4.4, Technical Committee on Thermal Insulation and Moisture Retarders, Research Subcommittee Chairman, 1990 to present.
- Wolfe, A. K., Proposal reviewer, National Science Foundation, 1990.
- Wolfe, A. K., Chairperson, Committee of Anthropologists in Environmental Planning, 1988 to present.
- Wolfe, A. K., Reviewer, *Human Organization*, *Forum*; and *The Environmental Professional*, 1990 to present.
- Wolfe, A. K., Corresponding Editor, *Practicing Anthropology*, 1990–1993.
- Wolfe, A. K., Membership Committee, Society for Applied Anthropology, 1987–1993.
- Wolfe, A. K., Secretary, East Tennessee Chapter, Society for Risk Analysis, 1991.

8.5 ENERGY DIVISION PUBLICATIONS FY 1991

- Ally, M. R., L. N. Klatt, A. Zaltash, and R. L. Linkous, "Densities and Refractive Indexes of Aqueous (Li,K,Na)NO₃ and LiBr Solutions," *Journal of Chemical Engineering Data* **36**, 209–13 (1991). [See Abstract 7.4.1.]
- Armstrong, J. S., H. L. Hwang, and J. Bandy, *Modified Seasonal Factors in Exponential Smoothing*, ORNL/M-1262, Oak Ridge National Laboratory, October 1991. [See Abstract 7.3.12.]
- Barnes, P. R., *EMP Research on Electric Power Systems—Program Update*, ORNL/M-1392, Oak Ridge National Laboratory, May 1991. [See Abstract 7.4.5.]
- Barnes, P. R., and F. M. Tesche, "On the Direct Calculation of a Transient Plane Wave Reflected from a Finitely Conducting Half Space," *IEEE Transactions on Electromagnetic Compatibility* **33**(2), 90–96 (May 1991). [See Abstract 7.4.6.]
- Barnes, P. R., and J. W. Van Dyke, "Economic Consequences of Geomagnetic Storms," *IEEE Power Engineering Review* **10**(11), 3 (November 1990).
- Barnes, P. R., et. al., *Compilation and Preliminary Analysis of HEMP System Effects Test Data—Vol. 1 Executive Summary*, CD90-0180—Vol. 1, Lawrence Livermore National Laboratory, Livermore, Calif., July 1991.
- Barnes, P. R., and J. W. Van Dyke, "Potential Economic Costs From Geomagnetic Storms," *IEEE Special Panel Session Report 90TH0357-4-PWR Geomagnetic Storm Cycle 22: Power System Problems on the Horizon*, 80–83, December 1990.
- Barnes, P. R., and J. W. Van Dyke, "Geomagnetic Storms: Potential Economic Impacts on Electric Utilities," *Proceedings of the 4th Electric Utility Business Environment Conference*, Denver, March 20, 1991. [See Abstract 7.4.2.]
- Barnes, P. R., D. T. Rizey, B. W. McConnell, F. M. Tesche, and E. R. Taylor, Jr., *Electric Utility Industry Experience with Geomagnetic Disturbances*, ORNL/6665, Oak Ridge National Laboratory, March 1991. [See Abstract 7.4.3.]
- Bates, J. B., J. C. Wang, Y. T. Chu, "Interface and Bulk Relaxation in Solid Ionic Conductors," *Journal of Non-Crystalline Solids* **1046**, 131–33 (1991).
- Baxter, F. P., "Information Technology and Global Change Science," *Proceedings of the Conference on Global Change: Economic Issues in Agriculture, Forestry, and Natural Resources*, U.S. Department of Agriculture, November 21, 1990. [See Abstract 7.3.1.]
- Baxter, V. D., and P. D. Fairchild, *Examining Substitutes for Ozone Depleting Chemicals*, Oak Ridge National Laboratory Review, Oak Ridge National Laboratory, **23**(3), 18–27, 1990.
- Berchowitz, D. M., and J. A. Shonder, "Estimated Size and Performance of a Natural Gas Fired Stirling for Domestic Refrigeration Applications," *XVIIIth International Congress of Refrigeration*, Montreal, August 10–17, 1991. [See Abstract 7.4.45.]
- Berry, L., and E. Hirst, "The U.S. Department of Energy Least-Cost Utility Planning Program," *Energy* **15**(12), 1107–17 (December 1990). [See Abstract 7.4.8.]
- Beschen, D. A., and M. A. Brown, *Evaluation Plan for the Weatherization Assistance Program*, ORNL/TM-11668/V1, Oak Ridge

- National Laboratory, August 1991. [See Abstract 7.4.15.]
- Bjornstad, D. J., and G. Horwich, "Spending and Manpower in Four U.S. Mobilizations: A Macro/Policy Perspective," *Journal of Policy History* 3(2) (1991).
- Braid, R. B., and J. H. Reed, *Implementation Plan for Air Force Environmental Noise Assessment Center*, ORNL/TM-11479, Oak Ridge National Laboratory, February 1991. [See Abstract 7.1.1.]
- Braid, R. B., Review of "A Commitment to Campaign: A Sociological Study of CND," *The Sociological Review* 38(4), 800-803 (1990).
- Broders, M. A., and B. W. McConnell, *Evaluation of the Computerized Utilities Energy Monitoring and Control System Installed at the U.S. Army, Europe, 26th Support Group, Heidelberg, Germany*, ORNL/CON-320, Oak Ridge National Laboratory, May 1991. [See Abstract 7.4.9.]
- Bronzini, M. S., J. M. Mason, J. P. Tarris, and E. Zaki, "Increasing the Pool of Transportation Engineers," in *Proceedings of the 61st Annual Meeting of the Institute of Transportation Engineers*, Institute of Transportation Engineers, Milwaukee, September 22-25, 1991. [See Abstract 7.3.2.]
- Brown, M. A., L. G. Berry, and R. K. Goel, "Guidelines for Successfully Transferring Government-Sponsored Innovations," *Research Policy* 20(2), 121-43 (April 1991). [See Abstract 7.4.10.]
- Brown, M. A., P. Brandis, B. Cody, and P. Degens, "Promoting Energy-Efficient Home Construction: Alternative Policy Instruments," *Proceedings of the Energy Program Evaluation Conference*, August 1991. [See Abstract 7.4.12.]
- Brown, M. A., B. Prindle, M. I. Scherr, and D. L. White, *Energy Efficiency in Non-Profit Agencies: Creating Effective Program Models*, ORNL/TM-11602, Oak Ridge National Laboratory, September 1990.
- Brown, M. A., and C. H. Major, "Technology-Transfer Strategies of DOE's Conservation Programs," *Journal of Technology Transfer* 15(1), 33-40 (1990). [See Abstract 7.4.16.]
- Brown, M. A., J. O. Kolb, D. Baylon, M. Haeri, and D. L. White, *The Impact of Bonneville's Model Conservation Standards on the Energy Efficiency of New Home Construction*, ORNL/CON-310, Oak Ridge National Laboratory, July 1991. [See Abstract 7.4.11.]
- Brown, M. A., J. O. Kolb, and P. Brandis, "Codes Vs. Marketing: How Far Have They Advanced Home Construction Practices in the Pacific Northwest," *Proceedings of the Fifth National Demand-Side Management Conference*, July 1991. [See Abstract 7.4.13.]
- Cannon, J. B., C. R. Boston, R. B. Braid, C. E. Easterly, R. H. Ketelle, R. L. Kroodsmas, M. W. Knazovich, D. W. Lee, R. L. Miller, and W. P. Staub, *Complex 21—A Proposal for the Nuclear Weapons Complex Reconfiguration Site*, Vol. 4, Environment, Safety and Health, Oak Ridge Operations Office, U.S. Department of Energy, 1991.
- Cantor, R. A., M. Schoepfle, and E. Szarleta, "Sources and Consequences of Hypothetical Bias in Economic Analysis of Risk Behavior," in *The Analysis, Communication, and Perception of Risk*, eds. B. J. Garrick and W. C. Gekler, Plenum Press, New York, 1991.
- Cantor, R. A., and S. Rayner, "Thinking the Unthinkable: Preparing for Global Disaster," in *New Risk: Issues in*

- Management*, ed. P. Ricci, Plenum Press, New York, 1990. [See Abstract 7.1.2.]
- Cantor, R. A., and C. G. Rizy, "Biomass Energy: Exploring the Risks of Commercialization," *Bioresource Technology* **35**(1), 1-13 (1991).
- Cantor, R. A., "Applying Construction Lessons in Decommissioning Estimates," special issue edited by M. J. Pasqualetti, *The Energy Journal* **12**, 105-117 (1991).
- Carmody, J., J. E. Christian, and K. Labs, *Builder's Foundation Handbook*, ORNL/CON-295, Oak Ridge National Laboratory, May 1991. [See Abstract 7.4.22.]
- Carnes, S. A., "CWC Policy Issues" in *CWC Verification System Concept Development for the Chemical Weapons Convention*, RS9241/90/00122 (S), ed. by R. G. Gough, Sandia National Laboratories, January 1991.
- Carnes, S. A., C. A. Garkovich, and T. E. Shriver, *Chemical Stockpile Emergency Preparedness Program Focus Groups: A Manual*, ORNL/TM-11769, Oak Ridge National Laboratory, April 1991. [See Abstract 7.1.3.]
- Chen, F. C., and S. I. Freedman, "Heat Pumps for the 1990s," *Mechanical Engineering*, 65-7, September 1990.
- Chen, F. C., R. W. Murphy, V. C. Mei, G. L. Glen, J. W. Lue, and M. S. Lubell, *Technology Analysis of Auxiliary Powered Environmental Control Systems*, Interagency Agreement Army No. A12GV, DOE No. 1481-1380-A1, July 1991.
- Chen, F. C., R. W. Murphy, V. C. Mei, G. L. Glen, J. W. Lue, and M. S. Lubell, *Loss Analysis of the Thermodynamic Cycle of Magnetic Heat Pumps, Phase I Final Report*, ORNL/TM-11608, Oak Ridge National Laboratory, February 1991. [See Abstract 7.4.18.]
- Chen, F. C., R. W. Murphy, V. C. Mei, and G. L. Chen, "Performances of Four Magnetic Heat-Pump Cycles," 1990 ASME Winter Annual Meeting, Dallas, November 25-30, 1990, *Thermo-Physical Aspects of Energy Conversion*, AES **16**, 103-115 (1990). [See Abstract 7.4.17.]
- Christian, J. E., "Technics: Under Steep Roofing," *Progressive Architecture*, May 1991.
- Christian, J. E., G. E. Courville, R. L. Linkous, R. L. Wendt, R. S. Graves, and T. L. Smith, "The Technical Viability of Alternative Blowing Agents in Polyisocyanurate Roof Insulation; Part 4, In-situ Thermal Aging and Performance in Different Roof Systems," *Proceedings of 33rd Annual Polyurethane Conference*, Orlando, Fla., September 30-October 3, 1990. [See Abstract 7.4.19.]
- Christian, J. E., "Energy Efficient Residential Building Foundations Enhance Indoor Air Quality," *ASHRAE Journal* **33**(11) (November 1991).
- Christian, J. E., "Thermal Mass Credits Relating to Building Envelope Energy Standards," *ASHRAE Transactions* **97** (Pt. 2) (1991). [See Abstract 7.4.20.]
- Christian, J. E., "Southern Exposure," *Practical Homeowner* **VI**(3) (March 1991).
- Christian, J. E., "Viability of Alternative Insulation Blowing Agents," *ORNL Review* **23**(3) (1990).
- Christian, J. E., "Oak Ridge National Laboratory Envelope Systems Research Apparatus (ESRA)," *Journal of Thermal Insulation*, Technomic Publishing Co., Inc., Vol. 15, July 1991.
- Christian, J. E., "Roof Insulation and CFCs; The Search for Alternative Blowing Agents," *The Construction Specifier* **43**(11) (November 1990).
- Christian, J. E., "Materials and Structures Program," in *Proceedings Buildings*

- Sector Field Program Planning Workshop*, January 19–30, March 1991.
- Christian, J. E., "A Heat Flux Transducer Guard Plate for Exterior Envelope Surface Measurements," in *Proceedings of the In-Situ Heat Flux Measurements in Buildings Applications and Interpretations of Results*, Hanover, N.H., February 1991.
- Conklin, J. C., and E. A. Vineyard, "Tubeside Condensation of Nonazeotropic Refrigerant Mixtures for Two Enhanced Surfaces," in *Proceedings of the ASME/JSME Thermal Engineering Joint Conference*, Reno, Nev., Vol. 3, 251–56, March 17–22, 1991. [See Abstract 7.4.49.]
- Conklin, J. C., and E. A. Vineyard, "Tubeside Evaporation of Nonazeotropic Refrigerant Mixtures from Two Enhanced Surfaces," 1990 ASME Winter Annual Meeting, Dallas, ASME Pamphlet 90-WA/HT-8, New York, November 1990. [See Abstract 7.4.47.]
- Conklin, J. C., and E. A. Vineyard, "Heat Exchanger Thermal Performance for Two Nonazeotropic Refrigerant Mixtures," in *Proceedings of the XVIIIth International Congress of Refrigeration*, August 1991. [See Abstract 7.4.50.]
- Copenhaver, E. D., *Management Plan for Chemical Stockpile Emergency Preparedness Program Medical Course (Re)Design*, ORNL/TM-11842, Oak Ridge National Laboratory, May 1991. [See Abstract 7.1.4.]
- Courville, G. E., J. E. Christian, R. S. Graves, R. L. Linkous, and D. L. McElroy, "Thermal Properties of Polyisocyanurate Foam Board Insulation Blown With CFC-11 Substitutes," *Third International Symposium on Roofing Technology*, Montreal, April 17–19, 1991. [See Abstract 7.4.23.]
- Curlee, T. R., "Statement before the Subcommittee on Energy Regulation and Conservation," *Hearing on the Energy Production and Conservation Act of 1990*, Committee on Energy and Natural Resources, United States Senate, S. HRG., 101–928, Washington, U.S. Government Printing Office, 1990.
- Curlee, T. R., and S. Das, "Plastics Recycling: Quantity Projections and Cost Estimates," *Materials and Society* 15(1), 41–73 (1991). [See Abstract 7.2.1.]
- Curlee, T. R., and S. Das, "Identifying and Assessing Targets of Opportunity for Plastics Recycling," *Resource Conservation and Recycling* (5), 343–63 (1991). [See Abstract 7.2.2.]
- Cushman, J. H., and A. F. Turhollow, "Selecting Herbaceous Energy Crops for the Southeast and Midwest/Lake States," pp. 465–80, *Energy from Biomass and Wastes XIV*, ed. by D. L. Klass, Institute of Gas Technology, Chicago, 1991.
- Dale, S. J., S. M. Wolf, and T. R. Schneider, eds., *Energy Applications of High-Temperature Superconductivity*, ER-6682, Vol. 2, Electric Power Research Institute, Palo Alto, Calif., November 1990.
- Das, S., and T. R. Curlee, "Advanced Materials Information Needs: A Survey Report," *Ceramic Bulletin* 70(3), 234–39 (1991). [See Abstract 7.2.4.]
- Das, S., "World Petroleum Trade Forecasts for the Year 2000," *Petroleum Intelligence Weekly* XXX(28)10 (July 15, 1991). [See Abstract 7.2.3.]
- Das, S., and R. Lee, "A Computerized System to Estimate Potential Uranium Resources," *Resources and Energy* 13(2), 201–15 (June 1991). [See Abstract 7.2.5.]
- Daugherty, P. F., *Final—System Dictionary Application for the Worldwide Household Goods Information System for Transportation Modernization (WHIST-MOD)*, ORNL/M-1708,

- Oak Ridge National Laboratory, September 1991.
- Davis, S. C., and P. S. Hu, *Transportation Energy Data Book: Edition 11*, ORNL-6649, Oak Ridge National Laboratory, January 1991. [See Abstract 7.3.3.]
- Ensminger, J. T., and D. W. Swindle, eds., *Environmental Restoration Program National Environmental Policy Act Workshop Handbook*, ES/ER/INT-24, Oak Ridge Environmental Restoration Program, March 1991.
- Feldman, D. L., and D. Mann, "Policy Analysis and the Management of Climate Change: Institutional Adaptability in the Face of Scientific Uncertainty," *Policy Studies Journal* 19(2), 43-49 (Spring 1991). [See Abstract 7.1.10.]
- Feldman, D. L., and D. Mann, eds., "Global Climate Change and Public Policy," *Policy Studies Journal* 19(2), 43-194 (Spring 1991).
- Feldman, D. L., and S. A. Carnes, "Policy and Institutional Issues" in *Verification of a Chemical Weapons Convention: Lessons Learned from the Verification Experience of the International Atomic Energy Agency*, N-DO/SG:90-135 (C), ed. by M. F. Mullen, Los Alamos National Laboratory, December 1990.
- Feldman, D. L., *Water Resources Management: In Search of an Environmental Ethic*, Johns Hopkins University Press, Baltimore, 1991.
- Feldman, D. L., "The Great Plains Garrison Diversion Unit and the Search for an Environmental Ethic," *Policy Sciences* 24(1), 41-64 (1991). [See Abstract 7.1.9.]
- Feldman, D. L., M. F. Mullen, W. D. Stanbro, K. E. Apt, J. Sanborn, M. S. Lu, A. Reisman, D. Dougherty, S. Carnes, and L. Scheinman, *Verification of a Chemical Weapons Convention: Lessons Learned from the Verification Experience of the International Atomic Energy Agency*, Los Alamos National Laboratory, Los Alamos, N.M., and U.S. Department of Energy, Washington, D.C., March 1991.
- Feldman, D. L., "The Chemical Stockpile Intergovernmental Consultation Program: Lesson for High Level Waste Public Involvement," *High Level Radioactive Waste Management: Proceedings of the Second International Conference, Volume 2*. New York, American Society of Civil Engineers and American Nuclear Society: 1015-21 (1991). [See Abstract 7.1.7.]
- Feldman, D. L., *Implications of SARA Title III for Community Based Emergency Planning in the U.S. Army Chemical Stockpile Disposal Program: The Acquisition of Emergency Equipment*, ORNL/TM-11388, Oak Ridge National Laboratory, October 1990. [See Abstract 7.1.5.]
- Feldman, D. L., "Transferring Superconductivity Technology at a National Laboratory User Center," *Journal of Technology Transfer* 15(1), 15-24 (Fall 1990). [See Abstract 7.1.8.]
- Feldman, D. L., "SARA Title III and Community Hazards Planning for Chemical Emergencies: Lessons From the U. S. Army's Chemical Stockpile Emergency Preparedness Program," *Proceedings of the Fourth Annual Hazardous Materials Management Conference/Central, 1991*, Glen Ellyn, Ill., Tower Conference Management Company: 131-44 (1991). [See Abstract 7.1.6.]
- Fischer, S. K., "Energy Use Impacts of CFC Alternatives," *Energy Engineering* 88(3), 6-21 (1991).
- Fischer, S. K., "National Energy Impacts of CFC Alternatives in Heating, Air-Conditioning, and Refrigerating Equipment and Foam Insulation,"

- ASHRAE Technical Data Bulletin 6(1), 49-56 (1990). [See Abstract 7.4.25.]
- Gettings, M. B., E. Hirst, and E. Yourstone, *DIAMOND: A Model of Incremental Decision Making for Resource Acquisition by Electric Utilities*, ORNL/CON-315, Oak Ridge National Laboratory, February 1991.
- Gettings, M. B., and J. O. Kolb, *Assessment of Weatherization Assistance Program Needs for Improved Residential Measure Selection Techniques*, ORNL/CON-316, Oak Ridge National Laboratory, February 1991. [See Abstract 7.4.26.]
- Goel, R. K., and M. A. Brown, "Commercializing Government-Sponsored Computer Software" in *Advances in the Implementation and Impacts of Computer Systems*, eds. M. Fleisher and J. A. Morell, JAI Press, Greenwich, Conn., 263-75, 1991. [See Abstract 7.4.14.]
- Graham, R. L., R. D. Perlack, A. M. Prasad, J. W. Ranney, and D. B. Waddle, *Greenhouse Gas Emissions in SubSaharan Africa*, ORNL-6640, Oak Ridge National Laboratory, November 1990. [See Abstract 7.2.14.]
- Graves, R. S., J. E. Christian, and D. L. McElroy, *Joint Industry/Government Research Project- Comparison of Thermal Aging for Roof Exposures and Thin-Specimens of Experimental Polyisocyanurate Insulation Foamed with Alternative Blowing Agents* *Proceedings, Polyurethanes World Congress*, Nice, France, September 24-26, 1991.
- Greene, D. L., and P. N. Leiby, "Understanding the Potential Impact of Alternative Fuel Use," Chapter IV of the *Second Interim Report to Congress*, U.S. Interagency Commission on Alternative Fuels, August 15, 1991.
- Greene, D. L., "Short-Run Pricing Strategies to Increase Corporate Average Fuel Economy," *Economic Inquiry* 29(1), 101-14 (January 1991). [See Abstract 7.3.4.]
- Gryder, R. K., and K. A. Hake, *Survey of Data Compression Techniques*, ORNL/TM-11797, Oak Ridge National Laboratory, November 1990. [See Abstract 7.3.5.]
- Gunn, M. E., D. Knoebel, J. I. Mills, and F. C. Chen, eds., "Thermo-Physical Aspects of Energy Conversion—1990," *ASME Symposium Volume, AES-Vol. 16*, December 1990.
- Hadder, G. R., and R. M. Davis, *Navy Mobility Fuels Forecasting System Report: Navy Fuel Production in the Year 2000*, ORNL-6684, Oak Ridge National Laboratory, September 1991. [See Abstract 7.3.7.]
- Hadder, G. R., S. Das, R. Lee, N. Domingo, and R. M. Davis, "Ultra Low Sulphur Diesel Fuel Impacts on Availability of Other Fuels," *Energy Policy* 19(5), 488-93 (June 1991). [See Abstract 7.3.6.]
- Hake, K. A., "Understanding the Computing System Domain of Advanced Computing with Microcomputers," *Social Science Computer Review* 9(1) (Spring 1991).
- Hake, K. A., *An Examination of Electronic File Transfer Between Host and Microcomputers for the AMPMODNET/AIMNET Classified Network Environment*, ORNL/TM-10874, Oak Ridge National Laboratory, November 1990. [See Abstract 7.3.8.]
- Hamblin, D. M., G. D. Pine, R. J. Maddigan, J. M. MacDonald, H. A. McLain, and J. Y. Rimpo, "Commercial Sector Gas Cooling Technology Frontier and Market Share Analysis," *International Association for Energy Economics Twelfth Annual North American*

- Conference Proceedings*, 239–50, October 1990. [See Abstract 7.4.35.]
- Hardy, B., and D. J. Bjornstad, *Handbook for State Energy Emergency Planning*, ORNL-6681, Oak Ridge National Laboratory, September 1991.
- Harrison, I. G., F. Southworth, D. Russell, A. K. Sexton, M. R. Hilliard, M. Holcomb, T. Wood, H. Brenner, J. Jacobi, and R. D. Kraemer, *Functional Description of the Airlift Deployment Analysis System (ADANS)*, ORNL-6560, Oak Ridge National Laboratory, May 1991.
- Hawsey, R. A., W. K. Kahl, S. W. Schwenler, J. M. Bailey, C. W. Sohns, J. N. Luton, B. W. McConnell, and V. W. Campbell, "Analysis and Performance of an Axial-Gap Superconducting Motor," *IEEE Transactions on Magnetics*, MAG-27, No. 2, March 1991.
- Hill, L. J., "Large Power Users and Capacity Shortages in Developing Countries: The Role of Innovative Pricing," *International Journal of Global Energy Issues* 3(2), 86–96 (1991). [See Abstract 7.2.7.]
- Hill, L. J., E. Hirst, and M. Schweitzer, *Integrating Demand-Side Management Programs into the Resource Plans of U.S. Electric Utilities*, ORNL/CON-311, Oak Ridge National Laboratory, January 1991.
- Hill, L. J., *Electricity Pricing as a Demand-Side Management Strategy: Western Lessons for Developing Countries*, ORNL-6620, Oak Ridge National Laboratory, December 1990. [See Abstract 7.2.10.]
- Hill, L. J., "Can Developing Countries Benefit from Innovative Pricing in the Power Sector?," *Natural Resources Forum* 15(1), 15–25 (February 1991). [See Abstract 7.2.8.]
- Hill, L. J., "Residential Time-of-Use Pricing as a Load Management Strategy: Effectiveness and Applicability," *Utilities Policy* 1(4), 308–18 (July 1991). [See Abstract 7.2.6.]
- Hill, L. J., C. H. Petrich, R. S. Holcomb, and R. D. Roop, *An Assessment of Using Oil Shale for Power Production in the Hashemite Kingdom of Jordan*, ORNL-6643, Oak Ridge National Laboratory, November 1990. [See Abstract 7.2.11.]
- Hill, L. J., *Electricity Pricing in Korea: A Case Study of Pricing Initiatives as Positive Contributors to the Development Process*, ORNL-6633, Oak Ridge National Laboratory, October 1990. [See Abstract 7.2.9.]
- Hillsman, E. L., and D. R. Alvic, *Estimating Costs of Electric Utility Compliance with Proposed Revisions to the Clean Air Act*, ORNL/TM-11712, Oak Ridge National Laboratory, April 1991. [See Abstract 7.1.11.]
- Hillsman, E. L., and F. Southworth, "Factors That May Influence Responses of the U.S. Transportation Sector to Policies for Reducing Greenhouse Gas Emissions," *Transportation Research Record*, No. 1267, 1–11, 1990.
- Hillsman, E. L., "Spatial Energy Analysis," book review in *Journal of Regional Science* 31(2), 233–35 (May 1991).
- Hirst, E., *Possible Effects of Electric-Utility DSM Programs, 1990 to 2010*, ORNL/CON-312, Oak Ridge National Laboratory, January 1991. [See Abstract 7.4.29.]
- Hirst, E., "Possible Effects of Electric-Utility DSM Programs by the Year 2010," *DSM and the Global Environment*, 27–35, Synergic Resources Corp., Philadelphia, April 1991.
- Hirst, E., "Boosting U.S. Energy Efficiency Through Federal Action," *Environment* 33(2), 6–11 and 32–36 (March 1991).
- Hirst, E., and R. Lee, "Independent Expert Review of the EIA Residential Energy

- End-Use Model (REEM) and the EIA Building Energy End-Use Model (BEEM)," prepared for Office of Statistical Standards, Energy Information Administration, June 1991.
- Hirst, E., "What Happens When Utility Financial Incentives Depend on Evaluation Results?," *Proceedings of the 1991 International Energy Program Evaluation Conference, Energy Program Evaluation: Uses, Methods, and Results*, CONF-910807, 621-25, August 1991.
- Hirst, E., and C. Goldman, "Creating the Future: Integrated Resource Planning for Electric Utilities," *Annual Review of Energy and the Environment* 16, 91-121 (1991). [See Abstract 7.4.33.]
- Hirst, E., "A Rose By Any Other Name: Defining Key Terms on Utility DSM Programs," *Energy Systems and Policy* 14(4), 305-18 (1991). [See Abstract 7.4.32.]
- Hirst, E., "Improving Energy Efficiency in the United States: The Federal Role," *Energy Policy* 19(6), 567-77 (July-August 1991).
- Hirst, E., "Utility DSM Programs Could Cut Electricity Use 20% During the Next Two Decades," DSM and the Global Environment Conference, 27-35, Synergic Resources Corp., Bala Cynwyd, Pa., April 1991. [See Abstract 7.4.30.]
- Hirst, E., "Fulfilling the Demand-Side Promise," *Public Utilities Fortnightly* 128(1), 31-32 (July 1, 1991).
- Hirst, E., C. Goldman, and M. E. Hopkins, "Integrated Resource Planning: Electric and Gas Utilities in the USA," *Utilities Policy* 1(2), 172-86 (January 1991).
- Hirst, E., M. Schweitzer, E. Yourstone, and J. Eto, "Technical Competence of Integrated Resource Plans Prepared by Electric Utilities," *Resources and Energy* 13, 39-55 (May 1991). [See Abstract 7.4.34.]
- Hirst, E., "Benefits and Costs of Flexibility: Small, Short-Lead-Time Power Plants and Demand-Side Programs," *Long Range Planning* 23(5), 106-15 (October 1990). [See Abstract 7.4.31.]
- Hirst, E., "A Bright Future for Electric-Utility DSM Programs," *Proceedings of the Canadian Electrical Association Conference, Enhancing Electricity's Value to Society*, Toronto, 899-906, October 22-24, 1990. [See Abstract 7.4.27.]
- Hirst, E., C. Goldman, and M. E. Hopkins, "Integrated Resource Planning for Electric and Gas Utilities," *State of the Art of Energy Efficiency: Future Directions*, 7-35, E. Vine and D. Crawley, eds., American Council for an Energy-Efficient Economy, Washington, D.C., 1991.
- Hirst, E., "Encouraging Electric-Utility Energy-Efficiency and Load-Management Programs," in *Proceedings of MIT Conference on Energy and the Environment in the 21st Century*, 813-21, March 26-28, 1991. [See Abstract 7.4.28.]
- Hirst, E., "Evaluating Demand-Side Management Programs," *Electric Perspectives* 14(6), 24-30 (November-December 1990).
- Hirst, E., "Analytical Foundations of Successful DSM Programs," in *Proceedings of National Conference on Integrated Resource Planning at Santa Fe, New Mexico*, National Association of Regulatory Utility Commissioners, Washington, D.C., 96-107, April 1991.
- Ho, C. M., G. S. Knoke, E. W. Geller, H. T. Liu, W. H. Jou, R. W. Murphy, and F. C. Chen, "Study of Asymmetric Supersonic Jet Flow for Ejectors," 1990 ASME Winter Annual Meeting, Dallas, *Thermo-Physical Aspects of Energy Conversion*, AES-Vol. 16, 55-66

- (November 25–30, 1990). [See Abstract 7.4.40.]
- Hu, P. S., *Light-Duty Vehicle Summary: First Six Months of Model Year 1991*, ORNL-6672/S1, Oak Ridge National Laboratory, August 1991. [See Abstract 7.3.9.]
- Hu, P. S., T. Wright, S. P. Miaou, R. Gorman, and S. C. Davis, "A Study of Interstate Motor Carrier Vehicle Miles of Travel," *Transportation Research A* 25A(6) (1991). [See Abstract 7.3.10.]
- Hwang, H. L., and J. Bandy, "Using a Rule-Based Approach in the Development of a Conventional Information Management System," Abstract in *Proceedings of the TIMS/ORSA Meeting*, Nashville, Tenn., May 12–15, 1991.
- James, T. L., and J. P. Loftis, "Dynamic Column Ordering in ORACLE SQL*FORMS," *DBMS* 4(5), 88 (May 1991).
- James, T. L., J. P. Loftis, and T.-L. Chiang, *The Program Specifications for the User Interface Using SAS Software for the Worldwide Household Goods Information System for Transportation Modernization*, ORNL/TM-11847, Oak Ridge National Laboratory, July 1991.
- Jones, D. W., *A Primer on World and U.S. Foreign Trade*, ORNL/PPA-90/2, Oak Ridge National Laboratory, June 1991. [See Abstract 7.2.12.]
- Kolb, J. O., *Guidebook on Performance Contracting for Public Housing Agencies*, (undocumented report to DOE), July 1991.
- Kraemer, R. D., M. R. Hilliard, and Lt. Col. C. Davis, "Meeting the Military Airlift Command's Airlift Scheduling Challenge," *Airlift* (The Journal of the Airlift Operations School) 8(2), 2–4 (Summer 1991). [See Abstract 7.3.13.]
- Kraemer, R. D., and M. R. Hilliard, "Scheduling the Operation Desert Shield Airlift: An Advanced Automated Scheduling Support System," *OR/MS Today Magazine* 18(2), 44–45 (April 1991).
- Kruse, V. J., D. L. Nickel, J. J. Bonk, E. R. Taylor, Jr., and P. R. Barnes, "Impacts of a Nominal Nuclear Electromagnetic Pulse on Electric Power Systems: A Probabilistic Approach," 90SM 347-5-PWRD, *IEEE Transactions on Power Delivery* 6(3), 1251–63 (July 1991). [See Abstract 7.4.7.]
- Kweller, E., V. E. Mei, and F. C. Chen, "Options of Desiccant Cooling and Dehumidification Technology," *Proceedings of the 26th IECEC*, Boston, Vol. 2, 566–70, August 1991.
- Lee, R., S. Das, and P. N. Leiby, *Navy Mobility Fuels Forecasting System Phase VI Report: The Potential Impacts of a Worst-Case Military Conflict on World Petroleum Availability*, ORNL-6636, Oak Ridge National Laboratory, January 1991. [See Abstract 7.2.13.]
- Lee, R., "Projections of Biomass Energy in the United States," p. 112, Abstract in *Proceedings of the Association of the American Geographers Annual Meeting*, April 13–17, 1991.
- Lee, R. R., *Portsmouth Gaseous Diffusion Plant Safety Analysis Report, Section 3.5.1, Regional Subsurface Hydrology*, K/GDP/SAR-4 (1991).
- Lee, R. R., *Paducah Gaseous Diffusion Plant, Safety Analysis Report, Section 3.5.1, Regional Subsurface Hydrology*, K/GDP/SAR-5 (1991).
- Lee, D. W., et al., *Gaseous Diffusion Plant Safety Analysis Report Upgrade Program Plan*, K/GDP/SAR-102 (1991).
- Lee, D. W., and A. S. Wineman, "Groundwater Phenomena and the Theory of Mixtures," in *Recent Advances in Mechanics of Structured Continua*, eds. M. Masoudi and K. R.

- Rajagopal, AMD-Vol. 117, American Society of Mechanical Engineers.
- Leiby, P. N., and T. Teisberg, *Economic Benefits of Methanol Fuel Use: A Report of Market Analysis Using the Alternative Fuels Trade Model*, ORNL-6676, Oak Ridge National Laboratory, April 4, 1991.
- Liu, C., B. Guinn, and I. G. Harrison, "An Allocation Model for Channels Scheduling," Abstract in *Proceedings of the TIMS/ORSA Joint National Meeting*, Nashville, Tenn., May 12-15, 1991.
- Loftis, J. P., and T. L. James, "A Flexible User Interface Developed Using SAS/AF and SAS/Graph," pp. 1000-1005 in *Proceedings of the SAS Users Group International 16th Annual Conference*, New Orleans, February 18, 1991. [See Abstract 7.3.15.]
- Loftis, J. P., and T. L. James, *Final—User-Back-End Application Design for the Worldwide Household Goods Information System for Transportation Modernization (WHIST-MOD)*, ORNL/M-1711, Oak Ridge National Laboratory, September 1991.
- Loftis, J. P., "Providing Dynamic Sorting and Searching Capabilities Using SQL*FORMS," pp. 303-10 in *Proceedings of the International ORACLE Users Group*, Anaheim, Calif., September 23-28, 1990. [See Abstract 7.3.14.]
- MacDonald, J. M., "Building Energy Monitoring," *1991 ASHRAE Handbook*, Chapter 37.
- MacDonald, J. M., and D. L. White, *Exploratory Investigation of Energy Use Metering and Data Analysis Methods for Multifamily Buildings in the Pacific Northwest*, ORNL/CON-304, Oak Ridge National Laboratory, May 1991. [See Abstract 7.4.36.]
- MacDonald, J. M., and D. L. White, "Exploratory Investigation of a New Modeling Approach and an Energy Index for Multifamily Buildings in the Pacific Northwest," *Proceedings of the ACEEE 1990 Summer Study on Energy Efficiency in Buildings*, pp. 10.145-10.152, Pacific Grove, Calif., August 26-September 1, 1990.
- MacGregor, D., B. E. Tonn, and R. T. Goeltz, "Decision Support System Development Using A Migration Approach," in *Proceedings of the EPRI Expert Systems Conference*, Boston, September 9-11, 1991. [See Abstract 7.3.30.]
- Marland, G., and A. F. Turhollow, "Coin Power," *Science* **253**, 1194 (September 1991).
- McBride, M., B. Wilcox, and J. E. Christian, "ASHRAE Standard 90.2 Envelope Load Factors and Trade off Procedures," *ASHRAE Transactions* **97**(Pt. 2) (1991). [See Abstract 7.4.21.]
- McCold, L. N., "Reducing Global, Regional, and Cumulative Impacts with the National Environmental Policy Act," *The Environmental Professional* **13**(2), 107-13 (1991). [See Abstract 7.1.12.]
- McConnell, B. W., "Motors," Chapter 3 in *Energy Applications of High-Temperature Superconductivity*, eds. S. J. Dale, S. M. Wolf, T. R. Schneider, EPRI, ER-6682, Vol. 2, October 1990.
- McKenna, T., K. Jackson, G. Brown, W. Reckley, R. Hogan, J. Jolicoeur, K. Gant, and B. Burnett, *The Response Technical Manual*, Vol. 1 and 2, NUREG/BR-0150, Rev. 1, U.S. Nuclear Regulatory Commission, Washington, D.C., April 1991.
- McLain, H. A., J. M. MacDonald, D. M. Hamblin, and R. J. Maddigan, "Energy and Economic Benefits of Gas Cooling Options in Large Office Buildings,"

- ASHRAE Transactions 97(1), 345-52 (1991). [See Abstract 7.4.37.]
- Mei, V. C., F. C. Chen, and R. A. Miller, *Development of Army 2-Ton Subcompact Air Conditioners—Final Report*, Interagency Agreement No. A92RB, DOE No. 1481-1380-A1, November 1990.
- Mei, V. C., "Heat Transfer of Buried Pipe for Heat Pump Application," *ASME Journal of Solar Energy Engineering* 113, 51-55 (February 1991). [See Abstract 7.4.38.]
- Mei, V. C., N. Gulati, F. C. Chen, and W. A. Miller, "Test of Condensate Subcooling Coils for Air Conditioners," *ASHRAE Transactions* 97(1), 256-62 (February 1991). [See Abstract 7.4.39.]
- Miaou, S. P., and S. M. Chin, "Computing K-Shortest Path for Nuclear Spent Fuel Highway Transportation," *European Journal of Operational Research* 53(1), 64-80 (July 1991). [See Abstract 7.3.16.]
- Miller, D. B., H. B. Fan, and P. R. Barnes, "The Response of MOV and SiC Arresters to Steep-Front Longer Duration Current Pulses," *IEEE Transactions on Power Delivery* 6(2), 666-71 (April 1991). [See Abstract 7.4.4.]
- Mixon, W. R., "Building Energy Monitoring," *1991 ASHRAE Handbook*, Chapter 37.
- Mixon, W. R., and A. Meier, "Monitoring Made Easier," *Home Energy* 7(5), 36-37 (September-October 1990).
- Murphy, R. W., F. C. Chen, et al., "Analysis of Magnetic Refrigeration Cycles," *Proceedings of the 26th IECEC* 2, 482-86, Boston, August 1991.
- Ng, V., *An Error Detection and Correction Strategy for a Decision Support System*, ORNL/TM-11749, Oak Ridge National Laboratory, June 1991. [See Abstract 7.3.17.]
- Peterson, B. E., *Description of the National Highway Planning Network*, ORNL/TM-11553, Oak Ridge National Laboratory, September 1991. [See Abstract 7.3.18.]
- Patton, J. B., D. T. Rizy, and J. S. Lawler, *System Reconfiguration Analysis Program (SYSRAP) User's Manual*, ORNL-6575, Oak Ridge National Laboratory, April 1991. [See Abstract 7.4.42.]
- Perlack, R. D., J. Ranney, and M. Russell, *Biomass Energy Development in Yunnan Province, China: Preliminary Evaluation*, ORNL/TM-11791, Oak Ridge National Laboratory, June 1991. [See Abstract 7.2.16.]
- Perlack, R. D., and M. Russell, "Energy and Environmental Policy in China," *Annual Review of Energy*, ed. by J. M. Hollander et al., Annual Review Inc., Palo Alto, Calif., Vol. 16, 205-33, May 1991. [See Abstract 7.2.15.]
- Perlack, R. D., H. M. Jones, and D. B. Waddle, "A Survey of Energy Technologies for Rural Applications," *Energy: The International Journal* 15(12) (1990). [See Abstract 7.2.17.]
- Phillips, B. A., and R. C. DeVault, "Residential Absorption Heat Pump Using a Generator-Absorber Heat Exchange Cycle," *IECEC Conference Proceedings*, Boston, August 8, 1991. [See Abstract 7.4.24.]
- Rathi, A. K., A. J. Santiago, and D. E. Valentine, "ITDS: Past, Present, and Future," *ASCE Journal of Transportation Engineering*, TE6-13, 799-808 (November-December 1990). [See Abstract 7.3.20.]
- Rathi, A. K., "Traffic Metering: An Effectiveness Study," *Transportation Quarterly Journal* 45(3), 421-40 (July 1991). [See Abstract 7.3.19.]
- Rathi, A. K., and A. J. Santiago, "Urban Network Simulation Model:

- TRAF-NETSIM Program," *ASCE Journal of Transportation Engineering*, TE6-13, 734-803, November-December 1990. [See Abstract 7.3.21.]
- Rathi, A. K., "Variance Reduction in TRAF-NETSIM Simulation Model," Abstract in *Proceedings of the TMS/ORSA Joint National Meeting*, Nashville, Tenn., May 12-15, 1991.
- Rayner, S., and T. O'Riordan, "Risk Management for Global Environmental Change," *Global Environmental Change* 1(2) (1991). [See Abstract 7.1.16.]
- Rayner, S., "Oran R. Young: International Cooperation: Building Regimes for Natural Resources and the Environment," *International Affairs* 67(2) (April 1991).
- Rayner, S., "A Cultural Perspective on the Structure and Implementation of Global Environmental Agreements," *Evaluation Review* 15(1) (February 1991). [See Abstract 7.1.14.]
- Rayner, S., "Prospects for Greenhouse Gas Policy in the U.S. Energy Sector," ed. M. Grubb, *Energy Policies and the Greenhouse Effect Vol. 2*, Gower Press for the Royal Institute of International Affairs, Brookfield, Vt., 1991. [See Abstract 7.1.15.]
- Rayner, S., "Cultural Theory and Risk Analysis," eds. D. Golding and S. Krinsky, *Theories of Risk*, Praeger, New York, 1991. [See Abstract 7.1.13.]
- Rayner, S., "Risk Subcultures and the Definition of Technology," eds. F. Holzhen and P. Wiedemann, *Society and Uncertainty II: Risk Perception*, Verlag Versicherungs-Wirtschaft, Karlsruhe, 1991.
- Reed, J. H., G. Rogers, and J. H. Sorensen, "Establishing Functional Requirements For Emergency Management Information Systems," eds. J. Sullivan and A. Clymer, *Simulation in Emergency Management and Engineering*, San Diego: Society for Computer Simulation, 1991. [See Abstract 7.1.17.]
- Reiner, R. H., W. Del Cul, M. R. Ally, A. Zaltash, and H. Perez-Blanco, *Evaluation of Potential Performance Additives for the Advanced LiBr Chiller*, ORNL/CON-318, Oak Ridge National Laboratory, April 1991. [See Abstract 7.4.41.]
- Rizy, C. G., D. J. Bjornstad, and D. P. Vogt, *Analysis of Military Occupational Specialty in Army National Guard Units*, ORNL/TM-11680, Oak Ridge National Laboratory, August 1991. [See Abstract 7.2.18.]
- Rogers, G., and J. H. Sorensen, "Adoption of Emergency Planning Practices for Chemical Hazards in the United States," *Journal of Hazardous Materials* 27(1), 3-26 (1991).
- Rogers, G., J. H. Sorensen, and J. Morell, "Using Information Systems in Emergency Management," eds. J. Morell and M. Flesher, *Advances in the Implementation and Impact of Computer Systems*, JAI Press, 161-81, 1991.
- Rogers, G., B. Shumpert, and J. H. Sorensen, *Description of Interview Data Regarding Pittsburgh and Confluence Toxic Chemical Accidents*, ORNL/TM-11599, Oak Ridge National Laboratory, November 1990. [See Abstract 7.1.18.]
- Russell, M., "Ozone Puzzle Offers Few Easy Choices," *Forum for Applied Research and Public Policy* 5(3), 31-37 (Fall 1990).
- Russell, M., "The Verdict on Acid Rain," *Oak Ridge National Laboratory Review* 23(4), 30-39 (1990).
- Russell, M., *The Experience and Legacy of NAPAP*, Report of The Oversight Review Board of the National Acid Precipitation Assessment Program (NAPAP), April 1991.

- Russell, M., "Cleanup of Old Waste: Is Superfund Broke?," *Risk Analysis* 11(1), 71-74 (1991).
- Sand, J. R., E. A. Vineyard, and R. Nowak, "Experimental Performance of Ozone-Safe Alternative Refrigerants," CFC Alternatives, *ASHRAE Technical Data Bulletin* 6(1) (1990).
- Sand, J. R., E. Granryd, and J. Conklin, "Advantages of Enthalpy-Temperature Diagrams for Nonazeotropic Mixtures," *Proceedings of the XVIIIth Congress of Refrigeration*, Montreal, Quebec, August 10-17, 1991. [See Abstract 7.4.43.]
- Schweitzer, M., E. Hirst, and L. J. Hill, *Demand-Side Management and Integrated Resource Planning: Findings from a Survey of 24 Electric Utilities*, ORNL/CON-314, Oak Ridge National Laboratory, February 1991. [See Abstract 7.1.19.]
- Schweitzer, M., E. Hirst, L. J. Hill, "A Look at the Resource Portfolios of 24 Electric Utilities," *The Electricity Journal* 4(7), 38-45 (August-September 1991). [See Abstract 7.1.20.]
- Sheiton, R. B., M. A. Kuliasha, K. H. Zimmerman, M. S. Bronzini, J. B. Cannon, G. E. Courville, C. R. Kerley, T. J. Wilbanks, *Energy Division Annual Progress Report for Period Ending September 30, 1990*, ORNL-6661, Oak Ridge National Laboratory, June 1991.
- Singley, P. T., P.F. Daugherty, J. P. Loftis, and T. L. James, *Final-Bridge Documentation for the Worldwide Household Goods Information System Modernization (WHIST-MOD)*, ORNL/M-1709, Oak Ridge National Laboratory, September 1991.
- Smith, T. L., J. E. Christian, et al., *Mechanical Properties Evaluation of Polyisocyanurate Roof Insulation Blown with CFC-11 Substitutes*, Third International Symposium on Roofing Technology, Montreal, April 17-19, 1991.
- Solanki, R. S., C. Liu, and I. K. Busch, "A Dynamic Programming Algorithm for the Military Airlift Problem," Abstract in *Proceedings of the TIMS/ORSA Joint National Meeting*, Nashville, Tenn., May 12-15, 1991.
- Solanki, R. S., and F. Southworth, "An Execution Planning Algorithm for Military Airlift," *Interfaces*, July-August 1991. [See Abstract 7.3.22.]
- Sorensen, J. H., "Society and Emergency Preparedness: Looking From the Past Into the Future," ed. A. Kirby, *Hazard and Society*, University of Arizona Press, Tucson, Ariz., 1991.
- Sorensen, J. H., and D. Mileti, "Risk Communication for Emergencies," eds. R. Kasperson and P. Stallen, *Communicating Risks to the Public: International Perspectives*, 369-94 Kluwer Academic Publishers, 1990.
- Southworth, F., V. Dale, R. Frohn, and R. O'Neill, "A Dynamic Settlement Diffusion-Land Tenure Model Emphasizing the Ecological Impacts of Deforestation," Abstract in *Proceedings of the Association of American Geographers Annual Meeting*, Miami, April 21, 1991.
- Southworth, F., V. Dale, R. Frohn, and R. O'Neill, "A Dynamic Settlement Diffusion-Land Tenure Model Emphasizing the Ecological Impacts of Deforestation," Abstract in *Proceedings of University of Tennessee, Geography Department Seminar Series*, Association of American Geographers, Knoxville, Tenn., October 18, 1990. [See Abstract 7.3.24.]
- Southworth, F., and J. H. Sorensen, "Modeling in Emergency Response Planning: Some Developments and Opportunities," *Keynote Address in Proceedings of the Emergency Planning*

- '91 International Conference,
University of Lancaster, England,
September 8–11, 1991.
- Southworth, F., *Regional Evacuation Modeling: A State of the Art Review*, ORNL/TM-11740, Oak Ridge National Laboratory, March 1991. [See Abstract 7.3.23.]
- Spears, P. M., *Final—Data Acquisition Documentation for the Worldwide Household Goods Information System for Transportation Modernization (WHIST-MOD)*, ORNL/M-1707, Oak Ridge National Laboratory, September 1991.
- Staub, W. P., "Nuclear Power Station Seismic Hazard Curves in the Eastern United States and the Uniform Building Code," *Bulletin of the Association of Engineering Geologists* XXVIII(3), 227–34 (1991). [See Abstract 7.1.21.]
- Staub, W. P., J. C. Wang, and R. J. Selfridge, *Assessment and Interpretation of Cross- and Down-Hole Seismograms at the Paducah Gaseous Diffusion Plant*, K/GDP/SAR-9, September 1991.
- Stevenson, G. G., *Common Property Economics: A General Theory and Land Use Applications*, Cambridge University Press, Cambridge, Mass., 1991.
- Ternes, M. P., P. S. Hu, L. S. Williams, and P. Goewey, *The National Fuel End-Use Efficiency Field Test: Energy Savings and Performance of an Improved Energy Conservation Measure Selection Technique*, ORNL/CON-303, Oak Ridge National Laboratory, March 1991. [See Abstract 7.4.46.]
- Tonn, B. E., "The Court of Generations: A Proposed Amendment to the U.S. Constitution," *Futures* 23(5), 482–98 (1991).
- Tonn, B. E., and C. Wagner, "Risk Assessment with Lower Probabilities," *Journal of Environmental Sciences* 20(2), 169–78 (1991).
- Tonn, B. E., guest editor, "Symposium on Advanced Social Science Computing," *Social Science Computer Review* 9(1) (Spring 1991).
- Tonn, B. E., "The Development of Ideas of Uncertainty Representation," *Environment and Planning A* 23(6), 783–812 (1990). [See Abstract 7.3.26.]
- Tonn, B. E., "Recommendations for Decentralized Information Technology Innovation and Management," *The Information Society* 7(2), 139–54 (1991). [See Abstract 7.3.25.]
- Tonn, B. E., M. Russell, H. L. Hwang, R. T. Goeltz, and J. Warren, *Costs of RCRA Corrective Action: Interim Report*, ORNL/TM-11864, Oak Ridge National Laboratory, August 1991.
- Tonn, B. E., and C. Wagner, "The Case for Lower Probabilities as Measures of Uncertainty," in *Proceedings of the EPRI Expert Systems Conference*, Boston, September 9–11, 1991. [See Abstract 7.3.27.]
- Tonn, B. E., and D. G. MacGregor, "Practical Implications of Theories of Uncertainty for Uncertainty Elicitation," in *Proceedings of the EPRI Expert Systems Conference*, Boston, September 9–11, 1991. [See Abstract 7.3.29.]
- Tonn, B. E., and L. J. Valverde A., "The Changing Face of Probability," in *Proceedings of the EPRI Expert Systems Conference*, Boston, September 9–11, 1991.
- Tonn, B. E., R. T. Goeltz, and K. Schmidt, "An Example of Systems Integration for RCRA Policy Analysis," in *Proceedings of the Advanced Computing for the Social Sciences Conference*, University of Georgia, Athens, April 8–10, 1991. [See Abstract 7.3.28.]
- Truett, L. F., T. G. Yow, V. V. Wheeler, D. E. Valentine, and S. E. Stamm, *Test*

- Plan and Implementation Procedures for the Integrated Booking System Prototype (IBS-P)*, ORNL/TM-11832, Oak Ridge National Laboratory, June 1991. [See Abstract 7.3.31.]
- Truett, L. F., and V. V. Wheeler, *Economic Analysis for the Integrated Booking System (IBS)*, ORNL/TM-11910, Oak Ridge National Laboratory, August 1991. [See Abstract 7.3.34.]
- Truett, L. F., T. G. Yow, V. V. Wheeler, D. E. Valentine, and S. E. Stamm, *User Interface Guidelines for the Integrated Booking System Prototype (IBS-P)*, ORNL/TM-11833, Oak Ridge National Laboratory, June 1991. [See Abstract 7.3.32.]
- Truett, L. F., V. V. Wheeler, S. E. Stamm, T. G. Yow, and D. E. Valentine, *Functional Description for the Integrated Booking System (IBS)*, ORNL/TM-11884, Oak Ridge National Laboratory, July 1991. [See Abstract 7.3.33.]
- Truett, L. F., V. V. Wheeler, D. E. Valentine, and S. E. Stamm, "Prototyping—Bane or Boon?," Abstract in *Proceedings of the TIMS/ORSA Joint National Meeting*, The Operations Research Society of America and The Institute of Management Science, Nashville, Tenn., May 12–15, 1991.
- Truett, L. F., V. V. Wheeler, and T. G. Yow, "Designing a Booking System That Integrates It All," Abstract in *Proceedings of the TIMS/ORSA Joint National Meeting*, The Operations Research Society of America and the Institute of Management Science, Nashville, Tenn., May 12–15, 1991.
- Trumble, D. A., and D. M. Flanagan, *Feasibility Study to Update Annualized Cost of Leaving (ACOL) Procedures at the Navy Personnel Research and Development Center (NPRDC)*, ORNL/TM-10613, Oak Ridge National Laboratory, December, 1990. [See Abstract 7.2.19.]
- Turhollow, A. F., J. H. Cushman, and J. W. Johnston, *Herbaceous Energy Crops Program Annual Report*, ORNL-6639, Oak Ridge National Laboratory, November 1990.
- Turhollow, A. F., "Emissions of CO₂ from Energy Crop Production," pp. IV.B.1., Abstract, *Southern Biomass Conference*, Baton Rouge, La., January 1991.
- Turhollow, A. F., and R. D. Perlack, "Emissions of CO₂ from Energy Crop Production," *Biomass and Bioenergy*, May 1991. [See Abstract 7.2.20.]
- Turhollow, A. F., "Screening Herbaceous Lignocellulosic Energy Crops in Temperate Regions of the United States," *Bioresource Technology* 36, 247–52 (1991).
- Vineyard, E. A., "The Alternative Refrigerant Dilemma for Refrigerator-Freezers: Truth or Consequences," *ASHRAE Transactions* 97(Pt. 2) (1991). [See Abstract 7.4.48.]
- Waddle, D. B., and R. D. Perlack, A *Summary of the Status of Biomass Conversion Technologies and Opportunities for Their Use in Latin America*, Proceedings of the Union Pan Americana de Asociaciones de Ingenieros (UPADI), Washington, D.C., August 19–24, 1990, and Proceedings of the 6th International Symposium on Agricultural Food Processing Wastes, Chicago, December 17–18, 1990. [See Abstract 7.4.51.]
- Wang, J. C., "Model for Lithium Intercalation into TiS₂," *Solid State Ionics* 40/41, 548 (1990).
- White, D. L., and M. A. Brown, *Electricity Savings Among Participants Three Years After Weatherization in Bonneville's 1986 Residential Weatherization Program*, ORNL/CON-305, Oak Ridge National

- Laboratory, September 1990. [See Abstract 7.4.52.]
- Wilbanks, T. J., "Energy Policy Responses to Concerns About Global Climate Change," eds. S. Majumder, et al., *Global Climate Change: Implications, Challenges, and Mitigation Measures*, Pennsylvania Academy of Sciences, Easton, Pa., 1991.
- Wilbanks, T. J., "The Outlook for Electricity Efficiency Improvements in Developing Countries," in *Electricity and the Environment*, Senior Expert Symposium, Helsinki (IEA-TEDOC-624) Vienna, International Atomic Energy Agency, 147-60, 1991.
- Wilbanks, T. J., "The Outlook for Electricity Efficiency Improvements in the United States," *Electricity and the Environment*, Senior Expert Symposium, Helsinki (IEA-TEDOC-624) Vienna, International Atomic Energy Agency, 121-45, 1991.
- Wilbanks, T. J., "Energy Efficiency and Developing Countries," with M. Levine and S. Meyers, *Environmental Science and Technology* **25**, 584-89 (1991).
- Wilbanks, T. J., "Energy Efficiency, Developing Nations, and Eastern Europe," with M. Levine, et al., Report to the U.S. Working Group on Global Energy Efficiency, Washington, D.C., June 1991.
- Wilkes, K. E., and P. W. Childs, *Evaluation of Attic Seal Products Applied to Loose-Fill Fiberglass Insulation in a Simulated Residential Attic: Phase II and III*, Letter Report, ORNL/M-1644, Oak Ridge National Laboratory, August 1991.
- Wilkes, K. E., *Analysis of Annual Thermal and Moisture Performance of Radiant Barrier Systems*, ORNL/CON-319, Oak Ridge National Laboratory, April 1991. [See Abstract 7.4.53.]
- Wilkes, K. E., *Thermal Model of Attic Systems with Radiant Barriers*, ORNL/CON-262, Oak Ridge National Laboratory, August 1991. [See Abstract 7.4.54.]
- Wilkes, K. E., *Radiant Barrier Attic Fact Sheet*, DOE/CE-0335P, June 1991.
- Williams, L. S., and P. S. Hu, *Highway Vehicle MPG and Market Shares Report: Model Year 1990*, ORNL-6672, Oak Ridge National Laboratory, May 1991. [See Abstract 7.3.11.]
- Yourstone, E., M. Schweitzer, and E. Hirst, "Leaders in the Electric Utility Industry Do Least-Cost Planning," *Planning Review*, 24-31 (January-February 1991). [See Abstract 7.4.44.]
- Yow, T. G., L. F. Truett, V. V. Wheeler, D. E. Valentine, and S. E. Stamm, *Data Base Specifications for the Integrated Booking System Prototype (IBS-P)*, ORNL/TM-11831, Oak Ridge National Laboratory, June 1991. [See Abstract 7.3.35.]
- Yow, T. G., L. F. Truett, V. V. Wheeler, D. E. Valentine, and S. E. Stamm, *End-User's Handbook for the Integrated Booking System Prototype (IBS-P)*, ORNL/TM-11834, Oak Ridge National Laboratory, June 1991. [See Abstract 7.3.36.]
- Zaltash, A., M. R. Ally, R. L. Linkous, and R. H. Reiner, *Effect of Additives on the Film Heat Transfer Coefficients of (Li,K,Na)NO₃ and LiBr Aqueous Mixtures*, Proceedings of the XVIIIth International Congress of Refrigeration, Montreal, Paper No. 52, August 10-17, 1991. [See Abstract 7.4.55.]

8.6 ENVIRONMENTAL ASSESSMENTS AND ENVIRONMENTAL IMPACT STATEMENTS

- Department of the Air Force, Space Systems Division, *Draft Environmental Assessment, Alterations and Additions to the Defense Meteorological Satellite System Satellite Process Facility (Building 1559) Vandenberg Air Force Base, California*, Nov. 1990. [A. W. Campbell, E. J. Liebsch, B. L. Shumpert, R. L. Graham, S. F. Railsback, M. A. Mitckes, W. P. Straub] [See Abstract 7.1.27.]
- Department of the Air Force, *Final Environmental Assessment, The Construction of a Boundary Fence Around Cheyenne Mountain Air Force Base, Colorado*, July 1990. [A. K. Wolfe, R. M. Reed, R. L. Miller, D. B. Hunsaker, Jr.] [See Abstract 7.1.33.]
- Department of the Air Force, *Cultural Resources Overview and Management Plan for Cheyenne Mountain Air Force Base, Colorado*, July 1991. [A. K. Wolfe, W. R. Arbogast] [See Abstract 7.1.34.]
- Department of the Air Force, *Natural Resources Management Plan for Cheyenne Mountain Air Force Base, Colorado*. [R. M. Reed, A. K. Wolfe, R. L. Miller] [See Abstract 7.1.35.]
- Department of the Army, *Disposal of Chemical Agents and Munitions Stored at Anniston Army Depot, Anniston, Alabama, Final Phase I Environmental Report*, ORNL/TM-11206/V1&2, September 1990. [D. B. Hunsaker, Jr., E. L. Hillsman, G. M. Schoepfle, R. L. Kroodsmas, G. O. Rogers, G. P. Zimmerman, R. L. Miller, V. R. Tolbert, L. W. Rickert, W. P. Staub] [See Abstract 7.1.28.]
- Department of the Army, *Chemical Stockpile Disposal Program, Final Phase I Environmental Report for Tooele Army Depot, Tooele, Utah*, ORNL/TM-11211, April 1991. [G. P. Zimmerman, C. R. Boston, E. L. Hillsman, R. O. Johnson, R. L. Kroodsmas, R. L. Miller, L. W. Rickert, G. O. Rogers, W. P. Staub, V. R. Tolbert] [See Abstract 7.1.29.]
- Department of the Army, *Final Environmental Impact Statement, Disposal of Chemical Agents and Munitions Stored at Anniston Army Depot, Anniston, Alabama*, May 1991. [D. B. Hunsaker, Jr., G. P. Zimmerman, E. L. Hillsman, R. L. Miller, G. M. Schoepfle, R. O. Johnson, V. R. Tolbert, R. L. Kroodsmas, L. W. Rickert, F. E. Latham, T. J. Blasing, C. W. Hagan, Jr., C. R. Boston, S. A. Carnes, J. B. Cannon, J. D. Harris, J. W. Saulsbury, J. H. Sorensen, R. J. Anderman, D. C. West. [See Abstract 7.1.30.]
- U.S. Department of Energy, *Environmental Assessment, Advanced Coal Conversion Process Demonstration Project Clean Coal Technology Program Western Energy Company, Rosebud Mine, Rosebud County, Montana*, DOE/EA-0469, March 1991. [A. W. Campbell] [See Abstract 7.1.22.]
- U.S. Department of Energy, *Environmental Assessment, Proposed Sale of Parcel A2 of the Oak Ridge Reservation to the City of Oak Ridge*, 1991. [R. E. Saylor, R. H. Ketelle, F. O'Donnell, D. B. Hunsaker, Jr., R. L. Kroodsmas, J. W. Van Dyke] [See Abstract 7.1.23.]
- U.S. Department of Energy, *Environmental Assessment, Demonstration of Coal Burning for Cyclone Boiler Nitrogen Oxide (NO_x) Control Nelson Dewey Generating Station, Wisconsin Power & Light Company, Cassville,*

- Wisconsin, DOE/EA-0440, February 1991. [R. L. Kroodsmas, A. W. Campbell, R. O. Johnson, V. R. Tolbert, T. J. Blasing, G. K. Eddlemon, R. L. Miller, J. W. Van Dyke] [See Abstract 7.1.24.]
- U.S. Department of Energy, *Draft Environmental Impact Statement, Proposed Healy Clean Coal Project*, October 1991. [R. L. Miller, R. O. Johnson, W. P. Staub, A. W. Campbell, J. W. Saulsbury, G. W. Sutter II] [See Abstract 7.1.25.]
- U.S. Department of Energy, *Draft Environmental Assessment, Retrievable Solid Transuranic Waste Operations at the Oak Ridge National Laboratory*, 1991. [R. E. Saylor, C. E. Easterly, R. H. Ketelle, R. B. McLean, F. O'Donnell, C. W. Hagan, Jr., R. L. Kroodsmas, R. L. Miller] [See Abstract 7.1.26.]
- National Science Foundation, *Draft Supplemental Environmental Impact Statement for the United States Antarctic Program*. [R. M. Reed, S. F. Railsback, J. W. Saulsbury, C. L. Hardy, J. M. MacDonald, R. B. McLean, J. B. Cannon, D. B. Hunsaker, Jr., E. J. Liebsch, L. W. Rickert] [See Abstract 7.1.32.]
- Nuclear Regulatory Commission, *Draft Generic Environmental Impact Statement for License Renewal of Nuclear Power Plants*. [R. B. McLean, D. C. Agouridi, C. R. Boston, R. B. Braid, G. F. Cada, A. W. Campbell, S. W. Christensen, J. B. Cannon, S. M. Cohn, C. E. Easterly, D. L. Feldman, C. W. Hagan, R. L. Kroodsmas, D. B. Lasley, R. R. Lee, L. K. Mann, M. A. Linn, L. N. McCold, R. L. Miller, G. A. Murphy, C. H. Petrich, L. W. Rickert, R. M. Rush, J. W. Saulsbury, R. E. Saylor, S. M. Schexnayder, M. Schweitzer, W. P. Staub, V. R. Tolbert, J. W. Van Dyke, J. S. Watson, E. Z. Seighami] [See Abstract 7.1.31.]

8.7 PUBLICATIONS BY SUBCONTRACTORS

- Burrage, L. M., E. F. Veverka, J. H. Shaw, and B. W. McConnell, *Impact of Steep-Front Short-Duration Impulse on Electric Power System Insulation, Phase II: Laboratory Evaluation of Selected Power System Components*, ORNL/Sub/85-28611/2, Oak Ridge National Laboratory, April 1991.
- Grossman, G., K. Gommed, and D. Gadoth, *Computer Model for Simulation of Absorption Systems in Flexible and Modular Form*, ORNL/Sub/90-89673, Oak Ridge National Laboratory, May 1991.
- Kruse, V. J., D. L. Nickel, J. J. Bonk, and E. R. Taylor, Jr., *Impacts of a Nominal Nuclear Electromagnetic Pulse on Electric Power Systems, Phase III Final Report*, ORNL/Sub/83-43374/2, Oak Ridge National Laboratory, April 1991.
- Lstiburek, J., and J. Carmody, *Moisture Control Handbook—New, Low-Rise Residential Construction*, ORNL/Sub/89-SD350/1, Oak Ridge National Laboratory, October 1991.
- Phillips, B. A., *Development of a High-Efficiency, Gas-Fired, Absorption Heat Pump for Residential and*

- Small-Commercial Applications - Phase I Final Report: Analysis of Advanced Cycles and Selection of the Preferred Cycle*, ORNL/Sub/86-24610/1, Oak Ridge National Laboratory, January 1991.
- Schoch, K. R., Jr., A. I. Bennett, R. R. Burghardt, et al., *Assessment of Conducting Polymer Applications in Power Equipment Technology*, ORNL/Sub/87-SA681/1, Oak Ridge National Laboratory, May 1991.
- Waldron, W. D., and G. T. Riecke, "Natural Gas Fueled Combustor for a 3 kW Output Stirling Engine," *Proceedings of the 26th IECEC Conference* 92(1), 566, Boston, August 1991.

8.8 PRESENTATIONS BY ENERGY DIVISION STAFF FY 1991

- Barnes, P. R., and J. M. Van Dyke, "Potential Economic Impacts of Geomagnetic Storms on Electric Utilities," presented at Fourth Electric Utility Business Environment Conference, Denver, March 20-22, 1991.
- Baxter, F. P., "Information Technology and Global Change Science," presented at Global Change: Economic Issues in Agriculture, Forestry, and Natural Resources, Washington, D.C., November 21, 1990.
- Baxter, F. P., and J. S. Olson, "Global Carbon Dioxide Control Strategy: A Role for Land," presented at 1990 Annual Meeting, American Society of Agronomy, San Antonio, Texas, October 21-24, 1990.
- Baxter, F. P., and S. S. Stevens, "Integrating Available Technology to Control the Application Rate and Spatial Distribution of Agrichemicals Applied to Land," presented at Conference on Environmental Sound Agriculture, Orlando, Florida, April 17-18, 1991.
- Berchowitz, D.M., and J.A. Shonder, "Estimated Size and Performance of a Natural Gas Fired Duplex Stirling for Domestic Refrigeration Applications," presented at XVIIIth International Congress of Refrigeration, Montreal, August 10-17, 1991.
- Bhat, M., A.F. Turhollow, B. English, "Biofuels From Energy Crops: Economics and Environmental Impact," presented at American Agricultural Economics Association Annual Meeting, Manhattan, Kansas, August 4-7, 1991.
- Bohi, D., D. Burtraw, R. Cantor, A. Krupnick, and R. Shelton, "Beyond the Market: Recent Regulatory Responses to the Externalities of Energy Production," presented at National Association of Environmental Professionals, Baltimore, April 30, 1991.
- Braid, R. B., "The Struggle for Science: Representing the Public While Conducting Objective Social Impact Assessment," presented at Annual Meeting of the International Association for Impact Assessment, Champaign-Urbana, Illinois, June 8-11, 1991.
- Braid, R. B., "Applied Social Science in Environmental Analyses: Is it Science?" presented at 50th Annual Meeting, Society for Applied Anthropology, Charleston, South Carolina, March 13-17, 1991.
- Bronzini, M. S., P. Elliot, and R. Bird, "Simulation Study of Measures to

- Expedite Barge Traffic at Winfield Locks," presented at the 70th Annual Meeting, Transportation Research Board, Washington, D.C., January 14, 1991.
- Bronzini, M. S., J. M. Mason, Jr., and J. P. Tarris, "Expanding the Civil Engineering Pool," presented at the 70th Annual Meeting, Transportation Research Board, Washington, D.C., January 14, 1991.
- Brown, M. A., "Measuring the Nonenergy Impacts of Conservation Programs," presented at the Socioeconomic Energy Research and Analysis Conference, Baltimore, June 28, 1991.
- Brown, M. A., "Regulatory vs. Marketing Approaches to Energy Efficient Home Construction," presented at the AAG Annual Meeting, Miami, April 16, 1991.
- Brown, M. A., P. Brandis, and B. Cody, "Promoting Energy-Efficient Home Construction: The Impacts of Alternative Policy Instruments," presented at National Energy Program Evaluation Conference, Chicago, August 23, 1991.
- Brown, M. A., J. O. Kolb, and P. Brandis, "Codes Vs. Marketing: How Far Have They Advanced Home Construction Practices in the Pacific Northwest" presented at 5th National DSM Conference, Boston, July 30, 1991.
- Burridge, L. M., and B. W. McConnell, "The Measured Response of a Selected Group of Lightning Arresters to Very Steep Front, Short Duration Impulses," presented at IEEE/PES T&D Exposition, Dallas, September 22-27, 1991.
- Cantor, R., A. Krupnick, and C. Rizy, "Beyond the Market: Recent Regulatory Responses to the Externalities of Energy Production," presented at National Association of Environmental Professionals, Baltimore, April 30, 1991.
- Cantor, R. A., T. R. Curlee, and E. L. Hillsman, "Selecting the Incremental Use of the Fuel Cycle and Regional Reference Environments," presented at Energy Conservation Consumption and Utilization, Brussels, October 22-26, 1990.
- Chen, F. C., R. W. Murphy, V. C. Mei, and G. L. Chen, "Performances of Four Magnetic Heat-Pump Cycles," presented at ASME Winter Annual Meeting, Dallas, November 26-30, 1990.
- Chen, F. C., R. W. Murphy, G. L. Chen, and V. C. Mei, "Thermodynamic Performance of Magnetic Refrigeration Cycles Using Gadolinium Gallium Garnet," presented at Cryogenic Engineering Conference, Huntsville, Alabama, June 11-14, 1991.
- Chen, F. C., G. L. Chen, V. C. Mei, and R. W. Murphy, "Performance Comparison of Magnetic Refrigeration Cycles," presented at International Cryocooler Conference, Plymouth, Maine, October 25-26, 1990.
- Chester, C. V., "Strategic Potential of Biological Weapons," presented at The American Civil Defense Association Annual Meeting, Las Vegas, September 25, 1991.
- Chester, C. V., "Obstacles to Large-Scale Biological Terrorism," presented at Annual Meeting of Doctors for Defense Preparedness, Las Vegas, September 22, 1991.
- Christian, J. E., "Roof, Wall and Foundation Futures," presented at Managers Conference, Big Sky, Montana, September 9-12, 1991.
- Christian, J. E., "Thermal Mass Credits Relating to Building Envelope Standards," presented at the ASHRAE Meeting, Indianapolis, June 22-24, 1991.
- Christian, J. E., "Moisture Control Strategies for Envelope Design in Hot and Humid Climates," presented at the American

- Hotel and Motel Executive Engineers Meeting, West Palm Beach, Florida, March 13, 1991.
- Christian, J. E., "Thermal Properties of Polyisocyanurate Foam Board Insulation Blown with CFC-11 Substitutes," presented at Third International Symposium on Roofing Technology, Montreal, April 17-19, 1991.
- Christian, J. E., "Status of ASHRAE 90.2," presented at BTECC, Washington, D.C., June 3-4, 1991.
- Christian, J. E., G. E. Courville, R. L. Linkous, and R. S. Graves, "The Technical Viability of Alternative Blowing Agents in Polyisocyanurate Roof Insulation," presented at Polyurethane '90 Conference, Orlando, Florida, October 1-4, 1990.
- Christian, J. E., "Alternative Materials for CFC-Based Polyisocyanurate Insulation," presented at the NAHB Technology Reports Forum in Atlanta, January 17, 1991.
- Conklin, J. C., and E. Granryd, "Thermal Performance Analysis for Heat Exchangers Using Nonazeotropic Refrigerant Mixtures," presented at Heat Transfer Division Technical Program, ASME Winter Annual Meeting, Dallas, November 25-30, 1990.
- Conklin, J. C., and E. A. Vineyard, "Tubeside Condensation of Nonazeotropic Refrigerant Mixtures for Two Enhanced Surfaces," presented at 3rd ASME-JSME Thermal Engineering Joint Conference, Reno, Nevada, March 17-22, 1991.
- Conklin, J.C., and E.A. Vineyard, "Heat Exchanger Thermal Performance for Two Nonazeotropic Refrigerant Mixtures," presented at XVIIIth International Congress of Refrigeration, Montreal, Quebec, August 15, 1991.
- Courville, G. E., P. W. Childs, R. L. Linkous, and K. L. Daniels, "Analysis of Roof Systems Thermal Performance From Field Data," presented at Third International Symposium on Roofing Technology Montreal, Quebec, April 17-19, 1991.
- Courville, G. E., R. S. Graves, R. L. Linkous, and D. L. McElroy, "Thermal Properties of Polyisocyanurate Foam Board Insulation Blown With CFC-11 Substitutes," presented at Third International Symposium on Roofing Technology, Montreal, Quebec, April 17-19, 1991.
- Feldman, D. L., "Some Lessons of the IAEA's Nuclear Non-Proliferation Regime for Confidence-Building Under a Greenhouse Gas Convention," presented at A Regime to Control Greenhouse Gases: Issues of Verification, Monitoring, Institutions, Sponsored by KFA Research Center, Julich, Germany, June 12, 1991.
- Feldman, D. L., "The Chemical Stockpile Intergovernmental Consultation Program: Lessons for HLW Public Involvement," presented at International High-Level Radioactive Waste Management Conference, Caesars Palace, Las Vegas, April 28-May 2, 1991.
- Feldman, D. L., "SARA Title III and Community Hazards Planning: Lessons from the U.S. Army's Chemical Stockpile Emergency Preparedness Program," presented at Hazardous Materials Management Conference and Exhibition, Rosemont, Illinois, April 3, 1991.
- Gant, K. S., "Multi-Purpose Exercises: Making Industry Exercises Meet State and Local Requirements," presented at Third Topical Meeting on Emergency Preparedness and Response, Chicago, April 16-19, 1991.
- Granryd, E., J.C. Conklin, and J.R. Sand, "Advantages of Enthalpy-Temperature

- Diagrams for Nonazeotropic Refrigerant Mixtures," presented at XVIIIth International Congress of Refrigeration, Montreal, Quebec, August 15, 1991.
- Greene, D. L., "The Implications for Fuel Consumption: Alternative Fuels and Fuel Economy," presented at the 70th Annual Meeting of the Transportation Research Board, Washington, D.C., January 15, 1991.
- Greene, D. L., "The Future of Automobile Efficiency (CAFE) Standards," presented at the International Energy Seminar—The John Hopkins Foreign Policy Institute, Washington, D.C., March 13, 1991.
- Greene, D. L., "Energy and Transportation—Is There a Policy Formula for E^3 ?", presented at the Institute of Transportation Engineers 1991 International Conference, New Orleans, March 6, 1991.
- Greene, D. L., "VMT Rebound Effect," presented at the Washington Statistical Society Meeting, September 18, 1991.
- Hake, K. A., "Computing Security for Advanced Computing Surveying Technologies and its Impact on Human Subject Reviews," presented at Conference on Advanced Computing and Information Technologies for the Social Sciences, 2nd Annual Meeting, Athens, Georgia, April 9, 1991.
- Hill, L. J., "Aspects of Integrated Resource Planning," presented at the National Energy Program Managers Conference, Big Sky, Montana, September 9-12, 1991.
- Hilliard, M. R., R. D. Kraemer, and I. G. Harrison, "Operations Research Lessons Learned from MAC's Airlift Operation in Support of Desert Shield," 31st Joint National Meeting, The Institute of Management Sciences and The Operations Research Society of America, Nashville, Tennessee, May 12-15, 1991.
- Hilliard, M. R., R. S. Solanki, I. K. Busch, C. Liu, R. D. Kraemer, and I. G. Harrison, "Scheduling the Operation Desert Shield Airlift: An Advanced Automated Scheduling Support System," presented at the TIMS/ORSA Edelman Competition, Nashville, Tennessee, May 12, 1991.
- Hillsman, E. L., "Think Locally, Act Globally: Local Problem-Solving that Reduces Greenhouse Gas Emissions," presented at 87th Annual Meeting of the AAG, Miami, April 13-17, 1991.
- Hillsman, E. L., "The Bureau of Mines Electric Utility Model II," presented at TIMS/ORSA Joint National Meeting, Nashville, Tennessee, May 14, 1991.
- Hillsman, E. L., "Transportation and Greenhouse Gas Reduction Policy," presented at 2nd Interdisciplinary Conference on Urban Air Quality, Boulder, Colorado, October 29-31, 1990.
- Hirst, E., "Utility DSM Programs Could Cut Electricity Use 20% During the Next Two Decades," presented at Demand-Side Management and the Global Environment, Arlington, Virginia, April 22-23, 1991.
- Hirst, E. A., "A Bright Future for Electric-Utility DSM Programs," presented at Enhancing Electricity's Value to Society, Harbour Castle Westin, Toronto, October 22-24, 1990.
- Hirst, E., "Federal Actions to Improve Efficiency of Electric Use," Testimony before the Subcommittee on Environment, Committee on Science, Space and Technology; U.S. House of Representatives, April 17, 1991.
- Hirst, E., "Making Energy Efficiency Happen," presented at Technologies for a Greenhouse Constrained Society Conference, Oak Ridge, Tennessee, June 11-13, 1991.

- Hirst, E., "Analytical Foundations of Successful Utility DSM Programs," presented at NARUC Third National Conference on Integrated Resource Planning, Santa Fe, New Mexico, April 8-10, 1991.
- Hu, P. S., T. Wright, and S. Miaou, "A Study of Interstate Motor Carrier Vehicle Miles of Travel," presented at Annual Transportation Research Board Meeting, Washington, DC, January 13-17, 1991.
- Hwang, H. L., "Using a Rule-Based Approach in the Development of a Conventional Information Management System," presented at TIMS/ORSA Nashville Meeting, Nashville, Tennessee, May 12-15, 1991.
- Janson, B. N., "A Convergent Algorithm for Dynamic Traffic Assignment," presented at ORSA/TIMS Annual Meeting, Philadelphia, October 29-31, 1990.
- Jones, D. W., R. V. O'Neill, "Modeling Land Use-Environmental Problems and Interactions," presented at the Seminar on Natural Resource Economics, Partners in America Program, U. S. Agency for International Development, September 13, 1991.
- Jones, D. W., and R. V. O'Neill, "Human-Environmental Influences and Interactions in Shifting Agriculture," presented at Western Regional Science Meeting, Monterrey, California, February 27, 1991.
- Kweller, E., V.C. Mei, and F.C. Chen, "Options of Desiccant Cooling and Dehumidification Technology," presented at 26th IECEC Conference, Boston, August 4-9, 1991.
- Lec, R. M., and P. N. Leiby, "Optimal Capacity of the U.S. Strategic Petroleum Reserve with Coordinated Use of OECD Stockpiles," presented at 12th Annual Meeting North American Conference for International Association for Energy Economics in Ottawa, Canada, October 1-3, 1990.
- Lee, D. W., and A. S. Wineman, "Groundwater Phenomena and the Theory of Mixtures," presented at Recent Advances on Mechanics of Structure Continua ASME Applied Mechanics Conference, Columbus, Ohio, June 16-19, 1991.
- Lee, R. M., "Projections of Biomass Energy in the United States," presented at the 1991 Annual Meeting Association of the American Geographers, Miami, April 13-17, 1991.
- Leiby, P. N., and R. M. Lee, "Approximating the Full Costs of Oil Market Disruptions," presented at 12th Annual North American Conference for International Association for Energy Economics in Ottawa, Canada, October 1-3, 1990.
- Leiby, P. N., W. W. Hogan, "An Adjacent Condensation Procedure to Aggregate Discrete Probability Distributions," presented at Operations Research Society of America, Philadelphia, October 20-31, 1990.
- Liu, C., B. Guinn, and I. G. Harrison, "An Allocation Model for Channels Scheduling," presented at 31st Joint National Meeting, The Institute of Management Sciences and The Operations Research Society of America, Nashville, Tennessee, May 12-15, 1991.
- Loftis, J. P., "The WHIST-MOD User Interface," presented at Tennessee ORACLE Users Groups, Oak Ridge, Tennessee, November 8, 1990.
- Loftis, J. P., and T. L. James, "A Flexible User Interface Developed Using SAS/AF and SAS/GRAPH," presented at SAS Users Group International 16th Annual Conference, New Orleans, February 18, 1991.

- MacGregor, D. G., and B. E. Tonn, "Practical Implications of Theories of Uncertainty for Uncertainty Elicitation," presented at EPRI Conference, Boston, September 9-11, 1991.
- MacGregor, D., B. E. Tonn, and R. T. Goeltz, "Decision Support System Development Using Migration Approach," presented at EPRI Conference, Boston, September 9-11, 1991.
- Mason, J. M., J. P. Tarris, E. Zaki, and M. S. Bronzini, "Increasing the Pool of Transportation Engineers," presented at 61st Annual Meeting of the Institute of Transportation Engineers, Milwaukee, September 22-25, 1991.
- McCold, L. N., and M. Salk, "NEPA and the Endangered Species Act: Complementary Approaches of Regulatory Excess," presented at 16th Annual Conference of the National Association of Environmental Professionals and NEPA Symposium, Baltimore, April 28-May 1, 1991.
- McLain, H. A., D. M. Hamblin, G. P. Pine, R. Maddigan, J. M. MacDonald, and J. Y. Rimpo, "Commercial Sector Gas Cooling Technology Frontier and Market Share Analysis," presented at International Association for Energy Economics Twelfth Annual North American Conference, Ottawa, October 1-3, 1990.
- McLain, H. A., J. M. MacDonald, D. M. Hamblin, and R. J. Maddigan, "Energy and Economic Benefits of Gas Cooling Options in Large Office Buildings," presented at ASHRAE Meeting, New York, January 19-23, 1991.
- Mei, V. C., and V. D. Baxter, "Experimental Analysis of Direct-Expansion Ground-Coupled Heat Pump Systems," presented at IEA Workshop on Ground-Source Heat Pumps, Montreal, August 12-13, 1991.
- Mei, V. C., N. Gulati, F. C. Chen, and W. A. Miller, "Test of Condensate Subcooling Coils for Air Conditioners," presented at ASHRAE 1990 Winter Annual Meeting, New York, January 20-23, 1991.
- Miaou, S. P., A. K. Rathi, F. Southworth, and D. L. Greene, "Forecasting Urban Highway Travel for Year 2005," presented at Transportation Research Board 70th Annual Meeting, Washington, D.C., January 13-17, 1991.
- Miller, R. L., and L. N. McCold, "NEPA and the Clean Air Act: Complementary Approaches to Maintaining Air Quality," presented at 16th Annual Conference of the National Association of Environmental Professional and NEPA Symposium, Baltimore, April 28-May 1, 1991.
- Pedersen, C. R., T. W. Petric, G. E. Courville, and P. W. Childs, "Moisture Migration and Drying Rates for Low Slope Roofs—Preliminary Results," presented at Third International Symposium on Roofing Technology, Montreal, Quebec, April 17-19, 1991.
- Pecelle, E. B., "Helping with the Cleanup: A Two-State Citizen Task Force Responds to the Department of Energy on Defense Waste," presented at SPECTRUM 90 International Topical Meeting on Radioactive Waste Technologies Decontamination and Decommissioning and Hazardous Waste, Knoxville, Tennessee, September 30-October 4, 1990.
- Pecelle, E., "The Widening Gap Between Citizens and Experts: Can it be Bridged?" presented at Social Science Plenary Presentation at Second International High Level Radioactive Waste Management Conference, Las Vegas, May 1, 1991.
- Pecelle, E., "Citizen Advisory Groups: A Mechanism for Two-Way Communication with Stakeholders,"

- presented at Wattec '91 Technical Session panel on "Communicating Scientific & Technical Information to the Public," Knoxville, Tennessee, February 19, 1991.
- Phillips, B. A., R. C. DeVault, "Residential Absorption Heat Pump Using a Generator-Absorber Heat Exchange Cycle," presented at IECEC Conference, Boston, August 8, 1991.
- Purucker, S. L., and M. B. Gettings, "Evaluation of the Utilities and Energy Management and Control System (UEMCS)," presented at Report of UEMCS Evaluation, Geopingen, Germany, USAREUR Community, August 23, 1991.
- Rathi, A. K., F. Southworth, and S. Miaou, "Travel Demand Management: Impacts on Future Urban Highway Needs," presented at Asilomar Conference, Pacific Grove, California, August 25-28, 1991.
- Rathi, A. K., "Variance Reduction in the TRAF-NETSIM Simulation Program," presented at ORSA Bulletin, Maryland, May 1991.
- Rathi, A. K., and R. S. Solanki, "Allocating Resources to Support a Multicommodity Flow with Time Windows," presented at the 70th Annual Meeting of the Transportation Research Board, Washington, D.C., January 13-17, 1991.
- Rayner, S., "National and Institutional Culture in the Transfer of Environmental Expertise," presented at Environmental Risk Management: The European Case, Kiev, Ukraine, November 22-23, 1990.
- Shonder, J. A., P. Badgley, D. McNulty, and M. Woods, "Uncooled Two-Stroke Gas Engine for Heat Pump Drive," presented at SAE Annual Meeting, Detroit, December 15, 1990.
- Solanki, R. S., C. Liu, and I. Busch, "A Dynamic Programming Algorithm for the Military Airlift Problem," presented at 31st Joint National Meeting, The Institute of Management Sciences and The Operations Research Society of America, Nashville, Tennessee, May 12-15, 1991.
- Sorensen, J. H., "Planning for Emergency Evacuation," presented at The Emergency Management Exposition and Conference (EMEX), Las Vegas, January 17, 1991.
- Sorensen, J. H., "A Preliminary Analysis of Protective Action Effectiveness in the IRZ," presented at CSEPP National Conference, Little Rock, Arkansas, May 8, 1991.
- Southworth, F., S. Chin, and M. Meador, "Telemetric Monitoring and Analysis of Traffic During Urban Evacuations," presented at Applied Geography Conference, Charlotte, North Carolina, October 24-27, 1990.
- Southworth, F., "Modeling Departure Time, Route and Destination Choice During Regional Evacuations," presented at Emergency Planning '91 International Conference, United Kingdom, September 3-11, 1991.
- Southworth, F., V. Dale, B. Frohn, and B. O'Neill, "A Dynamic Settlement Diffusion-Land Tenure Model Emphasizing the Ecological Impacts of Deforestation," presented at University of Tennessee, Geography Department Seminar Series, Knoxville, Tennessee, October 18, 1990.
- Southworth, F., and J.H. Sorensen, "Modelling in Emergency Response Planning: Some Developments and Opportunities," presented at Emergency Planning '91 International Conference, University of Lancaster, England, September 8-11, 1991.
- Southworth, F., V. Dale, B. Frohn, and B. O'Neill, "A Dynamic Settlement Diffusion-Land Tenure Model Emphasizing the Ecological Impacts of

- Deforestation," presented at Association of American Geographers Annual Meeting, Miami, April 21, 1991.
- Southworth, F., V. Dale, and R. V. O'Neill, "Dynamic Microsimulation of Deforestation and Tenant Mobility," presented at 6th International Conference on Travel Behavior, Quebec City, Quebec, May 22-24, 1991.
- Thomas, D. E., C. M. Wiggins, T. M. Salas, and P. R. Barnes, "On the HEMP Environment for Protective Relays," presented at IEEE/PES Winter Meeting, New York, February 3-7, 1991.
- Tonn, B., R. Goeltz, and K. Schmidt, "An Example of Systems Integration for RCRA Policy Analysis," presented at Advanced Computing for the Social Sciences, Athens, Georgia, April 9, 1991.
- Tonn, B. E., and C. Wagner, "The Case for Lower Probabilities as Measures of Uncertainty," presented at EPRI Conference, Boston, September 9-11, 1991.
- Tonn, B. E., and L. J. Valverde, "The Changing Face of Probability," presented at EPRI Conference, Boston, September 9-11, 1991.
- Truett, L. F., V. V. Wheeler, D. Valentine, and S. Stamm, "Prototyping—Bane or Boon?" presented at TIMS/ORSA Joint National Meeting, Nashville, Tennessee, May 12-15, 1991.
- Truett, L. F., T. G. Yow, and V. V. Wheeler, "Designing a Booking System that Integrates It All," presented at TIMS/ORSA Joint National Meeting, Nashville, Tennessee, May 12-15, 1991.
- Turhollow, A. F., "Emissions of CO₂ From Energy Crop Production," presented at the 1991 Southern Biomass Conference, Baton Rouge, Louisiana, January 8-10, 1991.
- Turhollow, A. F., and L. L. Wright, "New Energy Crops," presented at 1990 Conference on Biomass for Utility Applications, Tampa, Florida, October 23-25, 1990.
- Turhollow, A. F., "Economics and Pollution Aspects of Biomass-Derived Fuels Conversion and End-Use," presented at American Agricultural Economics Association Annual Meeting, Manhattan, Kansas, August 4-7, 1991.
- Vineyard, E. A., and J. C. Conklin, "Cycle Performance Comparison Between Nonazeotropic Refrigerant Mixture and R-22," presented at XVIIIth International Congress of Refrigeration Montreal, Quebec, August 13, 1991.
- Vineyard, E. A., "The Alternative Refrigerant Dilemma for Refrigerator-Freezers: Truth or Consequences," presented at the ASHRAE Meeting, Indianapolis, June 25, 1991.
- Vineyard, E. A., and J. C. Conklin, "Tubeside Evaporation of Nonazeotropic Refrigerant Mixtures from Two Enhanced Surfaces," presented at Heat Transfer Division, ASME Winter Annual Meeting, Dallas, November 25-30, 1990.
- Vogt, D. P., and S. Bell, "Frontier Equation Estimation of Regional Participation Rates in the Army National Guard," presented at Mid-Continent Regional Science Association, Chicago, May 30-June 1, 1991.
- Waddle, D. B., and R. D. Perlack, "A Summary of the Status of Biomass Conversion Technologies and Opportunities for Their Use in Developing Countries," presented at ISAFPW '90, 6th International Symposium on Agriculture and Food Processing Wastes, Chicago, December 17-18, 1990.
- Waldron, W. D., and G. T. Riecke, "Natural Gas Fueled Combustor for a 3-kW Output Stirling Engine," presented at 26th IECEC, Boston, August 5, 1991.

- Wang, J. C., and J. B. Bates, "Non-Debye Dielectric Response, Distribution of Activation Energies, and Equivalent Circuit for Data Analysis," presented at Materials Research Society Symposium Proceedings, Boston, November 26–December 1, 1990.
- White, D. L., "Measuring the Effects of Conservation Program Special Services: Client Education, Fuel Assistance, and Other Indirect Outcomes," presented at Affordable Comfort V Conference, Philadelphia, March 12, 1991.
- Wilbanks, T. J., "Institutional Issues in Energy R&D Strategies for Developing Countries," presented at Workshop on Energy Research and Development for Developing Countries, Oak Ridge, Tennessee, November 29–30, 1990.
- Wilbanks, T. J., "Affecting National Policy Through Geographic Research," presented at 41st Annual Meeting, West Lakes Division, Association of American Geographers, DeKalb, Illinois, October 25–27, 1990.
- Wilbanks, T. J., "Geographic Perspectives for the United Nations Conference on Environment and Development: The 'Earth Summit,'" presented at the Association of American Geographers, Miami, April 14, 1991.
- Wilbanks, T. J., "The Case for Energy Efficiency Improvement as a Global Strategy," presented at the Conference on Technologies for a Greenhouse-Constrained Society, Oak Ridge, Tennessee, June 12, 1991.
- Wilbanks, T. J., "Energy Strategies in an Era of Concern About Global Environmental Change," presented at Central Michigan University, Mt. Pleasant, Michigan, March 19, 1991.
- Wilbanks, T. J., "Energy Policymaking in the United States: Roles of the D.O.E. National Laboratories," presented at the U.S. Department of Energy, Washington, D.C., January 28, 1991.
- Wilbanks, T. J., "GIS Applications in Global Environmental Monitoring: A User's Perspective," presented at the 1991 Winter Seminar Series, Center for Mapping, Ohio State University, Columbus, Ohio, February 25, 1991.
- Wilbanks, T. J., "ORNL's Role in Meeting the Energy and Environmental Needs of Developing Countries," presented at the ORNL Showcase Series, Oak Ridge National Laboratory, Oak Ridge, Tennessee, June 19, 1991.
- Wilkes, K. E., "Heat Transfer in Porous Insulation Materials," presented at Mechanical Engineering Graduate Seminar at Old Dominion University, Norfolk, Virginia, March 29, 1991.
- Wilkes, K. E., R. L. Wendt, and A. Delmas, "Attic Testing at the Roof Research Center—Initial Results," presented at Third International Symposium on Roofing Technology, Montreal, April 17–19, 1991.
- Witten, A. J., and J. E. Molyneux, "Enhanced Signal Processing for Shallow Subsurface Geophysics," presented at Society of Engineering and Mineral Exploration Geophysicists, Knoxville, Tennessee, March 19, 1991.
- Witten, A. J., J. E. Molyneux, W. C. King, J. Sypmewski, A. J. Deveney, and G. A. Tsihrinteis, "Detection and Imaging of Subsurface Features Using Scaler Wave Backpropagation," presented at 8th Thematic Conference on Geologic Remote Sensing, Denver, April 29–May 2, 1991.
- Wolfe, A. K., and D. L. Feldman, "Public Participation and Societal Acceptance of Controversial Facilities," presented at Society for Applied Anthropology, Charleston, South Carolina, March 13–17, 1991.

8.9 ENERGY DIVISION CONSULTANTS AND SUBCONTRACTORS

8.9.1 Consultants

Adibi, M. M.	Kolstad, C. D.
Arbogast, W. R.	Kuff, H.
Armstrong, J. S.	Lavan, Z.
Balzer, R. A.	Lubin, N.
Biermann, W. J.	Maddala, G. S.
Bohman, R.	Manne, A. S.
Bronfman, B. H.	McAdams, H. T.
Carmody, J.	McCorkle, J.
Chapman, D.	McIlvanine, C. M.
Christianson, L. L.	Mellin, R. C.
Chronowski, R. A.	Mount, T. D.
Clements, K.	Nadel, S. M.
Considine, T. J.	O'Hara, F.
Deluchi, M. A.	Raab, J. D.
Fitzpatrick, G. L.	Radasky, W. A.
Franchuk, C. A.	Rothwell, G.
Franks, A. A.	Shafer, C. S.
Galley, P. C.	Sherrod, E. E.
Gnadt, P. A.	Spurrier, S. W.
Groff, G. C.	Tesche, F. M.
Grossman, G.	Tschirhart, J. T.
Hammitt, W. E.	Vance, E. F.
Hardy, B.	Vandergrift, L.
Harrje, D. T.	Wagner, C.
Hecht, S. B.	Wang, Q.
Hicks, E.	Wilson, C. R.
Jones, H. G.	Yourstone, N. E.
Kitamura, R.	

8.9.2 Subcontractors by Company

ABB Power Systems, Inc.	Berks Community Action Program
Advanced Mechanical Technology, Inc.	Bethel Valley Resources, Inc.
Allied Technology Group	BMS Management Services
American Consulting Engineers Council	Bonneville Power Administration
Analysas Corporation	Camden Corporation
Anstech, Inc.	Camden County Council of Economic Opportunity
Applied Management Sciences, Inc.	Carlton Enterprises
Arthur D. Little, Inc.	Cayuga County Program
Association of Collegiate Schools	CERF
Authorization Systems, Inc.	Champlain Valley Office of Equal Opportunity
Automated Sciences Group	Charles River Associates
B D M Corporation	City of Richland
Barakat & Chamberlin, Inc.	Clemson University
Battelle, Columbus Laboratories	Collier Engineering Services
Bedford County Weatherization	

Commission on Economic Opportunity
 Community Action for Greater Middletown
 Community Renewal Team of Greater Hartford, Inc.
 Dames & Moore
 Dan Hamblin & Associates, Inc.
 Distinct Management Consultants, Inc.
 Drexel University
 Electric Research & Management, Inc.
 Electrotek Concepts, Inc.
 Energetics, Inc.
 Energy & Environmental Analysis, Inc.
 Energy Concepts Company
 Energy Exchange
 Enersol Associates, Inc.
 Engineering Science, Inc.
 Ensys Energy & Systems, Inc.
 ERCE, Environmental and Energy Services
 Franklin Community Action Corporation
 Green County Community Action Agency
 Home Energy Magazine
 IBIF
 IEA Annex 5
 IEA Annex III
 International Institute for Energy Conservation
 Jaycor
 Kennebeck Valley Community
 Knoxville College
 Logicon, Inc.
 Los Alamos Technical Associates, Inc.
 MacGregor-Bates, Inc.
 Market Tracks Ltd.
 Marquette University
 Mason-Grant Company
 Massachusetts Institute of Technology
 Mechanical Technology, Inc.
 Midwest Research Institute
 Mississippi State University
 Mitre Corporation
 Mohawk Research Corporation
 Monitck, Inc.
 NAHB National Research Center
 National Association of State Consultant
 Advocate
 National Association for State Community
 Service Programs
 National Association of Home Builders
 National Bureau of Standards
 NIST
 North Carolina State University
 Northeast Employment & Training Organization
 Nuclear Assurance Corporation

Oak Ridge Associated Universities
 PAI Corporation
 PEACE
 PEI Associates, Inc.
 Pennsylvania State University
 Phillips Engineering Company
 Policy Planning Associates
 Polyisocyanurate Insulation
 Princeton Synergetics, Inc.
 Princeton University
 Puerto Rican Action Board
 Quantum Group, Inc.
 R A Technology
 R C G/Hagler Bailly, Inc.
 R O H, Inc.
 Resources For The Future
 Rocky Research Corporation
 S. Shore Community Action Council, Inc.
 Schneider Engineers
 Science Applications International Corporation
 Simpac Associates
 Southern N H Services
 Southwest Foundation for Biomedical
 Southwest Research Institute
 Springfield Action Commission
 Sterling Hobe Corporation
 Stonleigh Housing, Inc.
 Sunpower, Inc.
 Synertech Systems Corporation
 T. J. Murphy & Associates P A
 Tacoma City Light
 Technion Research & Development
 Tectonics Research, Inc.
 Telesoft, Inc.
 Tennessee State University
 Tennessee Technological University
 Texas A & M University
 The CEIP Fund, Inc.
 Thomason & Associates
 Tompkins County Equal Opportunity
 Commission
 Tri Town E O C, Inc.
 Tri-County Community Action
 University of Arizona
 University of Colorado at Boulder
 University of Florida
 University of North Carolina
 University of Pennsylvania
 University of Rochester
 University of Tennessee
 Virginia Polytechnic Institute

W/L Associates
 Warwick Community Action
 Washington Consulting Group
 Wayne State University

Weatherization, Inc.
 Widener University
 Xenergy, Inc.

8.10 INVITED SPEAKERS

Date	Subject	Speaker
1990		
October 29	Is the Oil Price Run-Up Deja Vu All Over Again?	<i>Dan Santini</i> Argonne National Laboratory Argonne, Illinois
October 30	Greenhouse Gas Emissions from Alternative Transportation Fuels	<i>Mark Deluchi</i> University of California, Davis
December 7	The Role of the Private Sector in Disaster Mitigation and Response: A Research Agenda	<i>George Horwich</i> Purdue University West Lafayette, Indiana
1991		
February 8	Major Impacts of the Free Export Zone in Korea	<i>Manik Hwang</i> Visiting Fulbright Scholar University of Tennessee Knoxville, Tennessee and Department of Geography Education Seoul National University Seoul, South Korea
February 14	Environmental Knowledge, Risk, and Social Learning: A Local Case Study with Global Implications	<i>Brian Wynne</i> Lancaster University United Kingdom
March 7	A Fuzzy Intelligent Information System with Learning Capabilities	<i>Maria Zemankova</i> National Science Foundation
March 13	Farm Energy Programs in California	<i>Charles Brush</i> California Energy Commission
March 22	Marketable Permits for Controlling Sulphur Dioxide Emissions	<i>Douglas Hale</i> Energy Information Administration Washington, D.C.
April 1	Getting the Science Right in Environmental Decisions: Science Policy at the EPA	<i>Sheila Jasanoff</i> Cornell University Ithaca, New York
April 5	Iterative Networking: A Tool for Addressing Global Climate Change	<i>William A. Nitze</i> President, Alliance to Save Energy Washington, D.C.

Invited Speakers (Continued)

Date	Subject	Speaker
May 6	An Approach to Policy Design	<i>Helen Ingram</i> Director, Udall Center for Studies in Public Policy University of Arizona Tucson, Arizona
May 10	Myths, Models, and the Fate of the Forest	<i>Susanna Hecht</i> University of California Los Angeles, California
June 7	Interfacing with Government and Business from the Universities' Perspective: Why, What, How, Who, Where	<i>Jacqueline B. Shrager</i> Director, Office of Technology Transfer Vanderbilt University Nashville, Tennessee
June 26	Development of Small Twin-Valveless Pulse Combustors for Space Heating	<i>Ichiro Hongo</i> Consumer Products Engineering Laboratory Toshiba Corporation Yokohama, Japan
August 7	Fan Efficiency Fundamentals	<i>Robert C. Mellin</i> Consultant
August 15	Improved Ocean Current Routing by Satellite Altimetry	<i>Hong Lo</i> The Ohio State University
August 27	Magnetocaloric Nanocomposites for Magnetic Refrigeration	<i>Robert D. Shull</i> Materials Science and Engineering Laboratory National Institute of Standards and Technology Gaithersburg, Maryland
September 27	Application of Benefit-Cost Analysis to Global Climate Policy: The Need to Consider Real Options	<i>Robert C. Lind</i> Johnson Graduate School of Public Policy

**8.11 WORKSHOPS AND SYMPOSIA ORGANIZED BY ENERGY
DIVISION STAFF**

Anniston Army Depot Green Cover Review
Meeting, Atlanta, March 26-27, 1991,
organized by D. B. Hunsaker.

Buildings Sector Field Program Planning
Workshop, Oak Ridge, Tennessee,
January 29-30, 1991, organized by G. E.
Courville.

Chemical Stockpile Demilitarization
Program Governors' Tour of Johnston
Island, Honolulu, July 24, 1991,
organized by T. G. Patton.

Chemical Stockpile Emergency Preparedness
Program Technical Workshop,
Emittsburg, Pennsylvania, September
9-13, 1991, organized by John Sorensen.

Conference on Transportation and Global Climate Change: Long Run Options, Pacific Grove, California, August 25-28, 1991, organized by D. L. Greene.

Electron Attachment Refrigerant Leak Detector, Oak Ridge, Tennessee, August 29, 1991, organized by Fang Chen.

Energy Research and Development for Developing Countries Workshop, Oak Ridge, Tennessee, November 29-30, 1990, organized by R. B. Shelton.

Healy Clean Coal Project Public Scoping Meetings, October 22, 1990, Fairbanks, Alaska; October 23-24, 1990, Anchorage, Alaska, organized by R. L. Miller.

Lexington Blue-Grass Army Depot Public Scoping Meeting, Richmond, Kentucky, April 24-25, 1991, organized by G. P. Zimmerman.

National Intergovernmental Consultation and Coordination Board (ICCB) Meeting, Denver, April 10, 1991, organized by G. P. Zimmerman.

National Labs Global Energy Efficiency Initiative Meeting, Denver, December 5, 1990, organized by T. J. Wilbanks.

Public Meeting for the Site Specific EIS for the Chemical Stockpile Disposal Program (CSDP), Aberdeen Proving Ground, Maryland, February 12, 1991, organized by T. G. Patton.

Symposium on the National Environmental Policy Act, in conjunction with the 16th Annual Conference of the National Association of Environmental Professionals, April 28-May 1, 1991, Baltimore, organized by L. N. McCold.

Technologies for a Greenhouse-Constrained Society, Oak Ridge, Tennessee, June 11-13, 1991, organized by M. A. Kuliasha.

Transportation Coordination Group Meeting, Albuquerque, New Mexico, December 4-5, 1990, organized by I. G. Harrison.

8.12 ENERGY DIVISION PATENT INFORMATION

Applications Filed

Title	Inventor(s)
Photoelectron Ion Mobility Refrigerant Leak Detector	F. C. Chen C. H. Chen ^a
Process for Preparing Salt Mixtures with Predicted Crystalline Phases	M. R. Ally J. Braunstein ^b
Triple-Effect Absorption Refrigeration System with Double-Condenser Coupling	R. C. DeVault W. J. Biermann ^c

^aHealth and Safety Research Division.

^bChemistry Division.

^cConsultant.

8.13 ENERGY DIVISION SPONSORS, EXPENDITURES, AND COMMITMENTS OF SCIENTIFIC STAFF FOR FY 1991

Sponsor	Expenditures ^a (\$10 ³)	Scientific staff (person-years)		Direct person- year costs ^c (\$10 ³)	Subcontract costs with overhead ^d (\$10 ³)
		Energy Division	Other Divisions ^b		
Department of Energy work					
Assistant Secretary for Conservation and Renewable Energy					
AK-Electric Energy Systems	1,783	3.8	0.0	602	1,047
AL-Energy Storage Systems	187	0.3	0.0	53	0
AM-Geothermal	34	0.2	0.0	28	0
EB-Solar Energy	367	2.0	0.0	289	32
EC-Buildings and Community Systems	9,084	24.0	0.8	3,617	4,132
ED-Industrial Energy Conservation	456	1.3	0.0	202	242
EE-Transportation	469	1.4	0.0	206	188
EF-State/local programs	1,822	4.5	0.0	692	906
EG-Multisector	473	1.0	0.2	227	195
Subtotal	14,675	38.5	1.0	5,916	6,742
Office of Civilian Radioactive Waste Management					
DB-Nuclear Waste Fund	5	0.0	0.0	0	4
Subtotal	5	0.0	0.0	0	4
Assistant Secretary for Defense Programs					
GE-Materials Production	40	0.1	0.0	29	0
Subtotal	40	0.1	0.0	29	0
Office of Environmental Restoration and Waste Management					
EW-Environmental Restoration and Waste Management—Defense	39	0.0	0.0	12	0
Subtotal	39	0.0	0.0	12	0
Energy Information Administration					
TA-National Energy Information System	849	2.3	0.0	343	414
Subtotal	849	2.3	0.0	343	414
Office of Energy Research					
KC-Basic Energy Sciences	240	1.2	0.2	217	0
KD-Energy Research Analysis	67	0.3	0.0	60	0
Subtotal	307	1.5	0.2	277	0
Assistant Secretary for Environment, Safety and Health					
HA-Environmental R&D-ES&H	150	0.0	0.0	0	0
Subtotal	150	0.0	0.0	0	0

ANNUAL PROGRESS REPORT

Sponsor	Expenditures ^a (\$10 ³)	Scientific staff (person-years)		Direct person- year costs ^c (\$10 ³)	Subcontract costs with overhead ^d (\$10 ³)
		Energy Division	Other Divisions ^b		
Federal Energy Regulatory Commission					
VR-Federal Energy Regulatory Commission	348	1.7	0.0	252	53
<i>Subtotal</i>	<i>348</i>	<i>1.7</i>	<i>0.0</i>	<i>252</i>	<i>53</i>
Assistant Secretary for Fossil Energy					
AA-Coal	153	0.0	0.0	6	0
AC-Petroleum	20	0.0	0.0	16	0
AZ-Innovative Clean Coal Technology	429	1.9	0.2	326	14
SA-Strategic Petroleum Reserve	208	1.2	0.0	186	0
<i>Subtotal</i>	<i>810</i>	<i>3.1</i>	<i>0.2</i>	<i>534</i>	<i>14</i>
Assistant Secretary for International Affairs and Energy Emergencies					
NB-Emergency Preparedness	71	0.2	0.0	36	26
<i>Subtotal</i>	<i>71</i>	<i>0.2</i>	<i>0.0</i>	<i>36</i>	<i>26</i>
Assistant Secretary for Nuclear Energy					
AF-Nuclear Energy R&D	50	0.0	0.0	0	0
CD-Uranium Enrichment	124	0.0	0.0	0	0
<i>Subtotal</i>	<i>174</i>	<i>0.0</i>	<i>0.0</i>	<i>0</i>	<i>0</i>
Office of Policy, Planning and Analysis					
PE-Policy, Planning and Analysis	1,314	5.6	0.9	981	657
<i>Subtotal</i>	<i>1,314</i>	<i>5.6</i>	<i>0.9</i>	<i>981</i>	<i>657</i>
DOE Related Projects					
Bonneville Power Administration	402	1.5	0.0	269	33
K-25 Miscellaneous	73	0.5	0.0	51	4
K-25 RWMD	269	0.7	0.7	176	26
K-25 SAR	263	2.3	0.0	217	20
K-25 Superfund	49	0.3	0.0	32	10
Portsmouth	7	0.0	0.0	7	0
Rocky Flats	10	0.0	0.0	9	0
Sandia National Laboratory	7	0.0	0.0	0	0
Silas Mason Company, Inc.	8	0.0	0.0	7	0
University of Tennessee	15	0.2	0.0	13	0
<i>Subtotal</i>	<i>1,103</i>	<i>5.5</i>	<i>0.7</i>	<i>781</i>	<i>93</i>
Total DOE Work	19,885	58.5	3.0	9,161	8,003

Publications and Professional Activities

Sponsor	Expenditures ^a (\$10 ³)	Scientific staff (person-years)		Direct person- year costs ^c (\$10 ³)	Subcontract costs with overhead ^d (\$10 ³)
		Energy Division	Other Divisions ^b		
Other federal agencies work					
Department of Defense					
Department of the Air Force					
Engineering & Services Command	696	1.8	0.5	367	229
Logistics Command	200	0.8	0.1	162	0
Military Airlift Command	3,870	4.5	0.0	598	2,732
Shaw Air Force Base	3	0.0	0.0	3	0
Space Division	101	0.3	0.0	62	20
Strategic Air Command	1	0.0	0.0	1	0
Tyndall Air Force Base	2	0.0	0.0	1	0
U.S. Transcom	669	1.7	0.0	246	298
Subtotal	5,542	9.1	0.6	1,440	3,279
Department of the Army					
Army-Europe	160	0.8	0.0	116	0
Belvoir	197	1.3	0.0	185	0
Construction Engineering Research Laboratory	20	0.0	0.0	8	0
Facilities Engineering Support Agency	249	0.8	0.0	110	113
Natick R&D & Engineering Center	2	0.0	0.0	1	0
Toxic & Hazardous Materials Agency	4,088	9.1	0.2	1,405	2,057
Subtotal	4,716	12.0	0.2	1,825	2,170
Department of the Navy					
Marine Corps	11	0.0	0.0	0	11
Military Sealift Command	271	0.0	0.0	0	0
Naval Research	329	1.3	0.0	224	46
Naval Sea System Command	159	0.0	0.0	10	145
Navy Personnel R&D Center	5	0.0	0.0	0	4
Subtotal	775	1.3	0.0	234	206
Joint Agencies					
DARPA	15	0.1	0.0	12	0
Defense Communications Agency	117	0.0	0.0	50	0
Defense Nuclear Agency	149	0.6	0.0	85	53
Military Traffic Management Command	1,103	4.9	0.0	684	237
National Guard Bureau	560	0.7	0.0	112	210
Office of Joint Chiefs of Staff	1	0.0	0.0	0	0
Subtotal	1,945	6.3	0.0	943	500
Subtotal DOD Work	12,978	28.7	0.8	4,442	6,155

ANNUAL PROGRESS REPORT

Sponsor	Expenditures ^a (\$10 ³)	Scientific staff (person-years)		Direct person- year costs ^c (\$10 ³)	Subcontract costs with overhead ^d (\$10 ³)
		Energy Division	Other Divisions ^b		
Bureau of the Census	2	0.0	0.0	0	0
Bureau of Labor Statistics	157	0.4	0.0	74	48
Bureau of Mines	161	0.6	0.0	88	57
Department of State-AID	870	2.7	0.0	416	274
Department of Transportation-FHWA	787	2.4	0.3	394	228
Environmental Protection Agency	197	0.3	0.1	81	41
Federal Emergency Management Agency	1,880	4.4	0.5	754	757
National Park Service	194	0.7	0.0	105	77
National Science Foundation	119	0.4	0.2	91	0
Nuclear Regulatory Commission	1,054	3.2	1.7	743	9
Total Other Federal Agencies Work	18,399	43.8	3.6	7,188	7,646
Private organizations work					
AFEAS	50	0.0	0.0	0	0
ASHRAE	46	0.3	0.0	45	0
Attic Seal, Inc.	15	0.1	0.0	15	0
CISEP	24	0.0	0.0	0	0
Commonwealth Electric	68	0.4	0.0	59	0
Electric Power Research Institute	163	0.7	0.0	119	34
Gas Research Institute	350	1.6	0.0	226	43
New York State Energy R&D Authority	88	0.3	0.0	45	38
Pacific Power & Light Company	50	0.2	0.0	40	0
TAMS Consultants, Inc.	9	0.1	0.0	8	0
Total private organizations work	863	3.7	0.0	557	115
Total non-DOE work	19,262	47.5	3.6	7,745	7,761
Total DOE work	19,885	58.5	3.0	9,161	8,003
Total Energy Division work	39,147	106.0	6.6	16,906	15,764

^aThe difference between total expenditures (column 2) and the sum of columns 5 and 6 is money spent on computer, programmer, and analyst support from Computer Services; travel; material purchases; technical information services; P&E, I&C; etc.

^bIncludes the following research divisions: Analytical Chemistry, Applied Technology, Chemical Technology, Engineering Physics and Mathematics, Engineering Technology, Environmental Sciences, Health and Safety Research, Metals and Ceramics, and Research Reactors.

^cIncludes technical staff labor costs for Energy Division and other research divisions and Laboratory overhead.

^dIncludes Laboratory overhead for onsite services and the subcontract surcharge for off-site services. The subcontract surcharge is to pay for the costs of accounts payable, auditing, and accounting.

R. B. Shelton, Director
N. L. Pope
S. M. Plemmons
J. B. Cannon, Associate
Secretary
M. A. Kullasha, Assoc
J. S. Sexton
T. D. Ferguson, Adml
C. L. Rose
K. H. Zimmerman, ² T

**EMERGENCY PREPAREDNESS RESEARCH
COORDINATION**
C. V. Chester ¹
GLOBAL CLIMATE CENTER
S. F. Rayner, ¹ Deputy Center Director
ENERGY INFORMATION ADMINISTRATION
PROGRAM
D. J. Bjornstad ^{1,6}

FINANCIAL SERVICES GROUP
D. S. Leggett ³
J. M. Draine
B. T. Edwards
C. B. Foust
TECHNICAL PUBLICATIONS GROUP
E. W. Whitfield ⁴
K. J. Ballew ⁴
D. C. Brown ⁴
L. A. Daniel ⁴
L. D. Gilliam ⁴
P. S. Gillis ⁴
M. Ortigara ⁴
R. H. Selden ⁴
C. M. Shupe ⁴
J. N. Stone ⁴
SAFETY PROGRAM
S. M. Cohn ¹
P. W. Childs ¹
J. T. Ensminger ¹
T. D. Ferguson ¹
J. O. Kolb ¹
P. M. Spears ¹
**ENVIRONMENTAL SAFETY AND
HEALTH UPGRADE REPRESENTATIVE**
S. M. Cohn ¹
SPECIAL STAFF ASSIGNMENTS
L. F. Truett ² Affirmative Action
Representative
P. S. Hu, ¹ Alternate Affirmative
Action Representative
S. Das, ¹ Quality Assurance
Coordinator
T. D. Ferguson, ¹ Computer Security
Officer, Property Coordinator, &
Training Coordinator
L. N. McCold, ¹ Environmental
Protection Officer
V. D. Baxter ¹ University
Relations Coordinator
S. M. Cohn, ¹ Hazard
Communication Coordinator &
Radiation Control Officer

**INTEGRATED ANALYSIS AND
ASSESSMENT SECTION**
R. M. Reed
Secretary
T. F. Ault ²
F. M. Glenn

**ENERGY AND ECONOMIC
ANALYSIS SECTION**
C. R. Kerley, Head
B. L. Bush
T. E. Rhea ¹

DOE NEPA PROJECTS
R. B. McLean
C. J. Penland
A. W. Campbell
L. N. McCold ¹
R. E. Saylor
B. A. Walker
DOD NEPA PROJECTS
C. R. Boston
Secretary
B. D. Barkenbus
J. T. Ensminger
C. W. Hagan, Jr.
T. G. Patton
G. P. Zimmerman
ATMOSPHERIC SCIENCES GROUP
R. L. Miller, Acting
B. J. Snow
T. J. Blasing
**TECHNOLOGY AND SOCIAL
SYSTEMS GROUP**
R. B. Braid
M. G. Huskey
E. B. Peelle ²
S. F. Rayner
J. W. Saulsbury
M. Schweitzer ¹
J. W. Van Dyke
A. K. Wolfe ¹
POLICY AND ANALYSIS
R. A. Cantor

**APPLIED PHYSICAL
SCIENCES GROUP**
D. W. Lee
L. S. Edwards
J. M. Bownds
R. O. Johnson
R. H. Kettle
R. R. Lee
W. P. Staub
J. C. Wang
EMERGENCY PLANNING GROUP
C. V. Chester ¹
K. E. Bowman
M. V. Adler ²
K. S. Gant
HAZARD MANAGEMENT GROUP
J. H. Sorensen
C. J. Coomer
S. A. Carnes
E. D. Copenhaver
D. L. Feldman
**ENERGY AND ENVIRONMENTAL
APPLICATIONS GROUP**
J. H. Reed
P. J. Daley
E. L. Hillsman
E. G. Llewellyn
C. H. Petrich ¹²
S. L. Purucker
T. G. Yow
TECHNOLOGY APPLICATIONS
A. J. Witten

**ENERGY AND ENVIRONMENTAL
ECONOMICS GROUP**
D. J. Bjornstad, ^{1,6}
M. Russell, ¹
K. R. Ballew
Secretary
T. R. Curlee ¹
S. R. Elliott
L. J. Hill ¹
D. W. Jones ¹
R. D. Perlack
S. F. Rayner ¹
C. G. Rizy ²
B. E. Tonn ¹
D. P. Vogt
PROGRAM PLANNING
M. Russell, UT/ORNL
Collaborating Scientist
T. R. Curlee ¹
**RESOURCE MODELING AND
TECHNOLOGY ECONOMICS GROUP**
R. Lee
V. M. Bollinger
P. D. Witcher
S. M. Cohn ¹
S. Das ¹
G. R. Hadder ¹
P. N. Leiby
D. A. Trumble
A. F. Turhollow, Jr.

DEFENSE
R. G. Edw.
D. T.
TRAN
F. Southw
C. D.
B. E. Pe
A. K. Ra
OP
I. G. Harris
J. E.
I. K. Bus
M. R. Hill
C. Liu ¹
R. S. Sc
S
P. S. Hu ¹
J. E.
S. C. D.
G. R. I.
T. G. V.
ENE
D. L. Gree
J. L.
S. M. C.
DE
B. K. Jone
D. T.
R. G. E.
J. E. H.
R. A. M.

LEGEND: 1 DUAL CAPACITY, 2 PART-TIME, 3 FINANCE AND MATERIALS DIVISION, 4 PUBLICATIONS DIVISION, 5 COMPUTING AND TELECOMMUNICATIONS DIVISION, 6 OFF-SITE.

11 HEALTH AND SAFETY RESEARCH DIVISION, 12 LEAVE OF ABSENCE

DIVISION

1991

te Director

ate Director

istrative Assistant

chnical Assistant

PLANNING AND COORDINATION

T. J. Wilbanks, ¹ Corporate Fellow
and Senior Planner
S. B. Floyd

DEVELOPING COUNTRY PROJECTS

T. J. Wilbanks ¹
S. B. Wright
K. L. Kline ⁸

CENTER FOR TRANSPORTATION ANALYSIS

M. S. Bronzini, Director
L. D. Gosslee
R. K. Gryder
S. S. Stevens

EFFICIENCY AND RENEWABLES RESEARCH SECTION

G. E. Courville, Head
T. J. Simmons
E. A. Hirst, Corporate Fellow
E. M. Schorn

TRANSPORTATION SYSTEMS

ds, ¹ Program Manager
Bain ¹

PORTATION PLANNING AND POLICY

ih
teelman
erson
il

RATIONS RESEARCH

en ¹
orenson ¹
h ¹
ard ¹
nikl ¹²

ATISTICS AND DATA ANALYSIS

Sorensen ¹
vis
dder ¹
ight ⁸

QV POLICY RESEARCH

o
vans
iin

LOYMENT ANALYSIS

Bain ¹
wards ¹
wthorne ⁵
Laren ⁵

AIR TRANSPORTATION

R. D. Kraemer
K. G. Gilley
I. K. Busch ¹
I. G. Harrison ¹
M. R. Hilliard ¹
C. Liu ¹
S. M. Margle ⁵
I. R. Moisson ⁵
A. K. Sexton ²

SURFACE TRANSPORTATION

P. T. Singley, Acting
R. L. Noe
P. F. Daugherty
S. W. Diegel
J. P. Loftis ¹
P. M. Spears
L. F. Truett ¹

INTELLIGENT COGNITIVE SYSTEMS

B. E. Tonn, ¹
Secretary
R. T. Goeltz
K. A. Hake
M. S. Hubbard
H. L. Hwang
L. F. Truett ¹

BUILDING EQUIPMENT RESEARCH

P. D. Fairchild
M. A. Hensley
Secretary
P. J. Hughes ¹
P. J. Lewis

REFRIGERATION SYSTEMS

V. D. Baxter
S. K. Fischer
C. V. Hardin
W. A. Miller
C. K. Rice
J. R. Sand
E. A. Vineyard

NOVEL CYCLES

F. C. Chen, ¹
V. C. Mel ¹
R. W. Murphy ¹

THERMALLY ACTIVATED HEAT PUMPS (TAHP)

F. A. Creswick, ¹ Coordinator

STIRLING-ENGINE TAHP

F. C. Chen, ¹
R. W. Murphy ¹
J. A. Shonder ¹

ABSORPTION AND IC ENGINE TAHP

F. A. Creswick, ¹
R. C. DeVault
D. E. Holt
P. J. Hughes ¹
R. H. Reiner
J. A. Shonder ¹

CHEMICAL HEAT PUMPS

M. R. Ally
R. R. Parks ¹
A. Zaltash

ENVIRONMENTAL CONTROL TECHNOLOGY

F. C. Chen ¹
D. E. Penland ¹
V. C. Mel ¹
R. W. Murphy ¹

ENERGY PROGRAM PLANNING AND EVALUATION

M. A. Brown
D. P. Bivens
L. G. Berry ²
J. O. Kolb ¹
D. L. White ⁸

BUILDING THERMAL ENVELOPE SYSTEMS AND MATERIALS

J. E. Christlan
C. L. Brown
P. W. Childs
P. M. Love ¹
K. E. Wilkes ¹

EXISTING BUILDINGS RESEARCH

W. R. Mixon, ¹
R. N. Scogin
R. R. Parks
R. L. Linkous

FIELD PERFORMANCE

M. P. Ternes
T. R. Sharp
K. E. Wilkes ¹
W. P. Levins
H. A. McLain

MODELING AND ANALYSIS

W. R. Mixon ¹
M. B. Gettlings ¹
J. O. Kolb ¹
J. M. MacDonald

PROGRAM PERFORMANCE

W. R. Mixon ¹
M. B. Gettlings ¹
J. O. Kolb ¹
J. M. MacDonald

INTEGRATED RESOURCE PLANNING

E. A. Hirst, ¹
E. M. Schorn
M. B. Gettlings ¹
L. J. Hill ¹
M. Schweitzer ¹
A. K. Wolfe ¹

POWER SYSTEMS TECHNOLOGY

S. J. Dale
N. J. Jett
J. E. Johnson

POWER SYSTEM TRANSIENTS

P. R. Barnes
B. W. McConnell ¹

SYSTEMS RESEARCH

J. P. Stovall
D. T. Rizy

MATERIALS AND COMPONENTS R&D

D. R. James ¹¹
G. D. Oriffin ¹¹
I. Sauers ¹¹

ELECTRIC AND MAGNETIC FIELDS

B. W. McConnell ¹

ENERGY FOR DEVELOPING COUNTRIES

D. B. Waddle ¹²

COMMUNITY ENERGY SYSTEMS

M. A. Broders
D. E. Penland ¹

TECHNOLOGY TRANSFER

G. E. Courville, Acting
P. M. Love ¹

INTERNAL DISTRIBUTION

1.	T. D. Anderson	92.	W. Fulkerson
2.	B. R. Appleton	93.	K. S. Gant
3.	D. Armstrong	94.	R. K. Genung
4.	D. T. Bain	95.	M. B. Gettings
5.	B. D. Barkenbus	96.	L. Gilliam
6.	P. R. Barnes	97.	P. S. Gillis
7.	V. D. Baxter	98.	H. A. Glover
8.	L. G. Berry	100.	L. D. Gosslee
9.	D. P. Bivens	101.	D. L. Greene
10.	D. J. Bjornstad	102.	R. K. Gryder
11.	T. J. Blasing	103.	G. R. Hadder
12.	V. M. Bolinger	104.	C. W. Hagan
13.	C. R. Boston	105.	K. A. Hake
14.	J. M. Bownds	106.	C. V. Hardin
15-17.	M. A. Broders	107.	I. G. Harrison
18-38.	M. S. Bronzini	108.	M. A. Hensley
39.	C. L. Brown	109.	S. G. Hildebrand
40.	M. A. Brown	110.	L. J. Hill
41.	J. B. Cannon	111.	E. L. Hillsman
42.	R. S. Carlsmith	112.	E. A. Hirst
43.	S. A. Carnes	113.	D. E. Holt
44.	F. C. Chen	114.	R. B. Honca
45.	P. W. Childs	115.	P. S. Hu
46.	J. E. Christian	116.	P. J. Hughes
47.	R. E. Conrad	117.	D. B. Hunsaker, Jr.
48-68.	G. E. Courville	118.	M. G. Huskey
69.	F. A. Creswick	119.	R. O. Johnson
70.	T. R. Curlee	120.	B. K. Jones
71.	S. J. Dale	121.	J. E. Jones, Jr.
72.	P. J. Daley	122.	L. Jung
73.	L. A. Daniel	123.	S. V. Kaye
74.	S. J. Das	124-149.	C. R. Kerley
75.	P. F. Daughtery	150.	R. H. Kettle
76-78.	R. M. Davis	151.	P. W. King
79.	J. M. Draine	152.	A. J. Klein
80.	B. T. Edwards	153.	E. H. Krieg, Jr.
81.	L. S. Edwards	154.	C. H. Krause
82.	R. G. Edwards	155.	A. J. Kuhaida, Jr.
83.	A. E. Ekkebus	156.	M. A. Kuliasha
84.	J. T. Ensminger	157.	D. W. Lee
85.	P. D. Fairchild	158.	R. M. Lee
86.	D. L. Feldman	159.	D. S. Leggett
87.	R. E. Fenstermaker	160.	P. N. Leiby
88.	T. D. Ferguson	161.	W. P. Levins
89.	S. B. Floyd	162.	C. Lewis
90.	C. Forsberg	163-173.	P. J. Lewis
91.	C. B. Foust	174.	R. L. Linkous

175-185.	P. M. Love	237.	M. Schweitzer
186.	P. Y. Lu	238.	R. N. Scogin
187.	J. M. MacDonald	239.	T. R. Sharp
188.	G. Marland	240.	J. Sheffield
189.	L. N. McCold	241.	R. B. Shelton
190.	B. W. McConnell	242.	J. A. Shonder
191.	R. N. McGill	243.	L. L. Sigal
192.	H. A. McLain	244.	T. J. Simmons
193.	S. A. Meachum	245.	J. E. Sorensen
194.	V. C. Mei	246.	J. H. Sorensen
195.	R. L. Miller	247.	F. Southworth
196.	W. A. Miller	248.	J. N. Stone
197.	W. R. Mixon	249.	J. P. Stovall
198.	O. B. Morgan	250.	S. H. Stow
199.	R. W. Murphy	251.	M. P. Temes
200.	N. C. Myers	252.	B. E. Tonn
201.	R. L. Noe	253.	D. B. Trauger
202.	J. L. Parham	254.	L. F. Truett
203.	R. R. Parks	255.	D. A. Trumble
204.	E. B. Peelle	256.	A. F. Turhollow
205.	R. D. Perlack	257.	J. W. Van Dyke
206.	B. E. Peterson	258.	E. A. Vineyard
207.	J. L. Petty	259.	D. P. Vogt
208.	S. M. Plemmons	260.	D. B. Waddle
209.	N. L. Pope	261.	R. C. Ward
210.	M. L. Poutsma	262.	D. A. Waters
211.	S. L. Purucker	263.	D. L. White
212.	J. W. Ranney	264.	T. J. Wilbanks
213.	A. K. Rathi	265.	S. B. Wright
214-224.	R. M. Reed	266.	T. G. Yow
225.	D. E. Reichle	267.	G. P. Zimmerman
226.	T. E. Rhea	268.	K. H. Zimmerman
227.	C. K. Rice	269.	A. Zucker
228.	C. R. Richmond	270.	ORNL Patent Office
229.	C. G. Rizy	271.	Central Research Library
230.	D. T. Rizy	272.	Document Reference Section
231.	J. B. Roberts	273-275.	Laboratory Records
232.	W. L. Roberts	276.	Laboratory Records (Record Copy)
233.	M. W. Rosenthal		
234.	R. M. Rush		
235.	A. C. Schaffhauser		
236.	E. M. Schorn		

EXTERNAL DISTRIBUTION

- 277. B. G. Buchanan, Computer Science Department, University of Pittsburgh,
206 Mineral Building, Pittsburgh, Pennsylvania 15260
- 278. A. Hirsch, Vice President of Environmental Sciences and Director of
Washington Operations, Midwest Research Institute, 5109 Leesburg
Pike, Suite 414, Falls Church, Virginia 22041
- 279. H. M. Ingram, Director of Udall Center for Studies in Public Policy,
University of Arizona, 803/811 East First Street, Tucson, Arizona 85719
- 280. C. D. MacCracken, President of Calmac Manufacturing Corporation,
101 West Sheffield Avenue, P. O. Box 710, Englewood, New Jersey 07631
- 281. J. B. Shrager, Director of Office of Technology Transfer, 405 Kirkland Hall,
Vanderbilt University, Nashville, Tennessee 37240
- 282. M. Williams, Professor, Department of Economics, Northern Illinois
University, DeKalb, Illinois 60115
- 283. MERT Division Library, ORAU
- 284. Office of Assistant Manager for Energy Research and Development,
DOE-ORO, P. O. Box 2001, Oak Ridge, Tennessee 37831-8600
- 285. Office of Information Services, ORAU
- 286-295. OSTI, U.S. Department of Energy, P.O. Box 62, Oak Ridge, Tennessee 37831
- 296-900. Energy Division External Distribution

END

**DATE
FILMED**

7 / 20 / 92