DOE/PC/88874-T16(Vol.2)
(DE92013481)

**THEORETICAL APPROACH FOR ENHANCED MASS TRANSFER EFFECTS
IN-DUCT FLUE GAS DESULFURIZATION PROCESSES**

Volume 2: Duct Spray Drying

Final Report

By
Wojciech Jozewicz
Gary T. Rochelle

January 29, 1992

Work Performed Under Contract No. AC22-88PC88874

For
U.S. Department of Energy
Pittsburgh Energy Technology Center
Pittsburgh, Pennsylvania

By
Acurex Corporation
Research Triangle Park, North Carolina

and

University of Texas at Austin
Austin, Texas

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615)576-8401, ~~NTIS-62-2-101~~.

Available to the public from the National Technical Information Service, U. S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

Theoretical Approach for Enhanced Mass Transfer Effects In-Duct Flue Gas Desulfurization Processes

Volume II: Duct Spray Drying

Final Report

Prepared for:

**DOE Project Manager
Richard E. Tischer
Environmental Control Division
Pittsburgh Energy Technology Center
U.S. Department of Energy
Pittsburgh, PA 15236**

**Under Contract No. DE-AC22-88PC88874
Date Prepared: January 29, 1992**

Prepared by:

**Wojciech Jozewicz
Acurex Corporation
Environmental Systems Division
4915 Prospectus Drive
P.O. Box 13109
Research Triangle Park, NC 27709**

and

**Gary T. Rochelle
University of Texas at Austin
Department of Chemical Engineering
Austin, TX 78712**

ABSTRACT

Removal of sulfur dioxide (SO_2) from the flue gas of coal-burning power plants can be achieved by duct spray drying (DSD) using calcium hydroxide [$\text{Ca}(\text{OH})_2$] slurries. A primary objective of this research was to discover the aspects of mass transfer into $\text{Ca}(\text{OH})_2$ slurries which limit SO_2 absorption. A bench-scale stirred tank reactor with a flat gas/liquid interface was used to simulate SO_2 absorption in a slurry droplet. The absorption rate of SO_2 from gas concentrations of 500 to 5,000 ppm was measured at 55 °C in clear solutions and slurries of $\text{Ca}(\text{OH})_2$ up to 1.0 M (7 wt percent). Results are reported in terms of the enhancement factor, Φ . This research will allow prediction of conditions where the absorption of SO_2 in $\text{Ca}(\text{OH})_2$ slurries can be enhanced by changes to liquid phase constituents (under which SO_2 absorption is controlled by liquid film mass transfer). Experiments in the stirred tank have shown that SO_2 absorption in a 1.0 M $\text{Ca}(\text{OH})_2$ slurry was completely dominated by gas film mass transfer. For conditions of a slurry droplet, the model predicts that absorption of SO_2 is controlled by gas film mass transfer with a large excess of $\text{Ca}(\text{OH})_2$ but becomes controlled by liquid film resistance at greater than 50 percent $\text{Ca}(\text{OH})_2$ utilization.

An algorithm using penetration theory for the SO_2 absorption and film theory for the $\text{Ca}(\text{OH})_2$ dissolution has been developed to model the SO_2 absorption rate in a stirred tank reactor. This algorithm has been coded in FORTRAN and executed on a CRAY computer. Results have been calculated for conditions representative of DSD. The results are expressed as the average fraction gas film resistance. With short contact times (0.1 s), high slurry concentration [1,000 mole $\text{Ca}(\text{OH})_2/\text{m}^3$], or low SO_2 concentration (500 ppm), gas film resistance approaches 100 percent. With a typical gas film transfer coefficient at 2,000 ppm SO_2 , gas film resistance decreases to less than 100 percent when the penetration distance of the absorption wave exceeds 10 to 20 μm .

TABLE OF CONTENTS

<u>Section</u>	<u>Page</u>
VOLUME I	
ABSTRACT	i
EXECUTIVE SUMMARY	1
E.1 Duct Injection Program Overview	1
E.2 Introduction	2
E.3 Experimental	3
E.4 Mass Transfer Testing	6
E.5 Novel Techniques	15
E.6 Conclusions	35
1. DUCT INJECTION PROGRAM OVERVIEW	38
2. INTRODUCTION	40
3. EXPERIMENTAL	44
3.1 Short Time Differential Reactor	44
3.2 Long Time Differential Reactor	47
3.3 Pilot Plant Facility	49
3.4 Baseline Sorbent Selection/Characterization	52
4. MASS TRANSFER TESTING	62
4.1 Verification of Rate Limiting Step	62
4.2 Investigation of Solid Phase Diffusion	75
4.3 Effect of Moisture on Reactivity	90
4.4 Effect of CO ₂ on Reactivity	91
4.5 Global SO ₂ Kinetics Testing	100
4.5.1 General Findings	100
4.5.2 Effect of Residence Time	103
4.5.3 Effect of Relative Humidity	104
4.5.4 Effect of Initial Sorbent Moisture	104
4.5.5 Effect of Sorbent Type	108
4.5.6 Effect of SO ₂ Concentration	111
4.5.7 Effect of Sorbent Accumulation over Time	111

TABLE OF CONTENTS (continued)

<u>Section</u>	<u>Page</u>
5. NOVEL TECHNIQUES	116
5.1 Moist Solids	116
5.1.1 Theory	116
5.1.1.1 Assumptions for Theoretical Development	116
5.1.1.2 Derivation	117
5.1.1.3 Effects of Equilibrium Reaction	119
5.1.1.4 Derivation of Modified Equilibrium Conversion Estimate	121
5.1.2 Long Time Differential Reactor Results and Discussion	122
5.1.2.1 Sorbents with Ambient Moisture	123
5.1.2.2 Sorbents with Initial Free Moisture	128
5.1.2.3 Comparison: Additive Model vs. Experiment	141
5.1.2.4 Comparison: Interactive Model vs. Experiment	148
5.1.2.5 Conversion of Fly Ash/ $\text{Ca}(\text{OH})_2$ Sorbent by Reaction with CO_2	159
5.1.3 Short Time Differential Reactor Results and Discussion	159
5.1.3.1 Effect of Sorbent Type	162
5.1.3.2 Combined Effect of the Amount of Initial Free Moisture and Sorbent Surface Area	169
5.1.3.3 Effect of the Approach to Saturation	178
5.1.3.4 Effect of Fly Ash Source	182
5.2 Solids Moisture Capacity	185
5.2.1 Introduction	185
5.2.2 Theory of Agglomeration	185
5.2.3 Approach	186
5.2.4 Results for Individual Reactants and Dry Mixtures	189
5.2.5 Results for Sorbents Prepared From Slurry	197
5.3 Recycle Operation	212
5.3.1 Dry-Sorbent Injection Downstream of Humidification	212
5.3.2 Dry-Sorbent Injection Upstream of Humidification	218
5.4 Grinding of Dry-sorbent Injection Material	221
5.4.1 Grinding of Spent $\text{Ca}(\text{OH})_2$	221
5.4.2 Grinding of Spent $\text{Ca}(\text{OH})_2$ /Fly Ash	222
6. DISCUSSION	225
7. CONCLUSIONS	228
8. REFERENCES	231

TABLE OF CONTENTS (continued)

<u>Section</u>	<u>Page</u>
VOLUME II	
ABSTRACT	i
EXECUTIVE SUMMARY	1
E.1 Introduction	1
E.2 Theory of SO ₂ Absorption in Ca(OH) ₂ Slurries	4
E.2.1 Basic Mass Transfer Principles	5
E.2.2 Enhancement Predicted by Surface Renewal Theory	6
E.2.3 Slurry Absorption Model	7
E.3 Experimental	9
E.3.1 Design of Reactor and Supporting Equipment	9
E.3.2 Mass Transfer Properties of the Stirred Tank Reactor	11
E.3.3 Comparison of Mass Transfer Properties of the Stirred Tank to that in a Slurry Droplet	18
E.4 Results of Experiments in Clear Solutions	18
E.4.1 Experimental Conditions	18
E.4.2 Enhancement in Water	19
E.4.3 Enhancement in 0.1 M CaCl ₂ Solution	19
E.4.4 Enhancement in 2.5 mM Ca(OH) ₂ Solution Containing 0.1 M CaCl ₂	20
E.4.5 Enhancement in 17 mM Ca(OH) ₂ Solution Containing 0.1 M CaCl ₂	20
E.4.6 Enhancement in Solutions of Varying Ionic Strength	21
E.5 Results of Experiments in Ca(OH) ₂ Slurries	24
E.5.1 Results of Slurry Experiments	24
E.5.2 Validation of Slurry Absorption Model For Ca(OH) ₂ Slurries	28
E.5.3 Discussion of Slurry Absorption Experiments	30
E.6 Computer Modeling	32
E.6.1 Model	32
E.6.2 Modeling Results	40
E.7 Conclusions and Recommendations	47
E.7.1 Mass Transfer Theory	53
E.7.2 Stirred Tank Reactor Experiments	53
E.7.3 Model Validation	54
E.7.4 Computer Modeling	54
1. INTRODUCTION	55
2. THEORY OF SO ₂ ABSORPTION IN Ca(OH) ₂ SLURRIES	63
2.1 Basic Mass Transfer Principles	64
2.1.1 Mass Transfer Coefficients	64
2.1.2 Enhancement of Absorption With Reaction	65

TABLE OF CONTENTS (continued)

<u>Section</u>	<u>Page</u>
2.1.3 Gas Film Resistance	66
2.2 Enhancement Predicted by Surface Renewal Theory	67
2.2.1 Enhancement in Water	68
2.2.2 Enhancement in CaCl_2 Solution	69
2.2.3 Enhancement in Dilute $\text{Ca}(\text{OH})_2$ Solutions	70
2.3 Slurry Absorption Model	72
2.3.1 Absorption With Reaction	73
2.3.2 $\text{Ca}(\text{OH})_2$ Solids Dissolution	73
2.3.3 CaSO_3 Crystallization	74
2.3.4 Inputs to the Model	74
2.3.5 Model Output	76
3. EXPERIMENTAL	78
3.1 Design of Reactor and Supporting Equipment	78
3.1.1 Agitation	81
3.1.2 System Improvements	82
3.1.3 Gas Phase Analysis and Material Balance	84
3.1.4 Liquid Phase Analysis	86
3.2 Mass Transfer Properties of the Stirred Tank Reactor	87
3.2.1 Gas Film Mass Transfer Properties	87
3.2.1.1 Experimental Results	88
3.2.1.2 Discussion	93
3.2.2 Liquid Film Mass Transfer Properties	96
3.2.2.1 Experimental Results	97
3.2.2.2 Discussion	103
4. RESULTS OF EXPERIMENTS IN CLEAR SOLUTIONS	107
4.1 Experimental Conditions	108
4.2 Enhancement in Water	110
4.3 Enhancement in 0.1 M CaCl_2 Solution	114
4.4 Enhancement in 2.5 mM $\text{Ca}(\text{OH})_2$ Solution Containing 0.1 M CaCl_2	119
4.5 Enhancement in 17 mM $\text{Ca}(\text{OH})_2$ Solution Containing 0.1 M CaCl_2	124
4.6 Enhancement in Solutions of Varying Ionic Strength	129
4.7 Summary of Experiments in Clear Solutions	131
4.7.1 Enhancement and Gas Film Resistance	134
4.7.2 Slurry Absorption Model and Theory	137
5. RESULTS OF EXPERIMENTS IN $\text{Ca}(\text{OH})_2$ SLURRIES	140
5.1 Experimental Conditions	140
5.2 Results of Slurry Experiments	142
5.2.1 Enhancement in Increasing Concentrations of Reagent Grade $\text{Ca}(\text{OH})_2$	143
5.2.2 Enhancement in Slurries Made From Mississippi $\text{Ca}(\text{OH})_2$	147

TABLE OF CONTENTS (concluded)

<u>Section</u>	<u>Page</u>
5.2.3 Enhancement in Three Different Lime Types	152
5.3 Validation of Slurry Absorption Model for $\text{Ca}(\text{OH})_2$ Slurries	156
5.3.1 Inputs that Establish Slurry Properties	156
5.3.2 Enhancement Predicted by Slurry Absorption Model	157
5.3.3 Solids Settling in the Boundary Layer	162
5.4 Summary of Slurry Absorption Experiments	165
5.4.1 Effect of Solids Concentration on Enhancement and Gas Film Resistance in the Stirred Tank	166
5.4.2 Effect of Solids Concentration on Enhancement and Gas Film Resistance in a Slurry Droplet	167
5.4.3 Alternate Interpretation of Slurry Absorption Model Data	175
5.4.4 Effect of Varied $\text{Ca}(\text{OH})_2$ Reactivity	180
5.4.5 Slurry Absorption Model Validation	182
6. COMPUTER MODELING	184
6.1 Model	184
6.1.1 Equilibria	184
6.1.2 $\text{Ca}(\text{OH})_2$ Dissolution	185
6.1.3 CaSO_3 Crystallization	189
6.1.4 SO_2 Absorption	189
6.1.5 Numerical Solution	192
6.1.6 Modeling Conditions	198
6.2 Modeling Results	200
6.2.1 $\text{Ca}(\text{OH})_2$ Reactivity	200
6.2.2 Concentration Profiles Without $\text{Ca}(\text{OH})_2(\text{s})$ in the Liquid Bulk	203
6.2.3 Concentration Profiles With $\text{Ca}(\text{OH})_2(\text{s})$ in the Bulk Liquid	206
6.2.4 Partial Pressure of SO_2 at the Gas Liquid Interface	209
6.2.5 Effects of $\text{Ca}(\text{OH})_2(\text{s})$ Concentration	209
6.2.6 Effects of Different Partial Pressures of SO_2	213
6.2.7 Effects of $\text{Ca}(\text{OH})_2(\text{s})$ Reactivity	213
6.2.8 Penetration Distance	218
7. CONCLUSIONS AND RECOMMENDATIONS	223
7.1 Mass Transfer Theory	223
7.2 Stirred Tank Reactor Experiments	223
7.3 Model Validation	225
7.4 Implications for a Slurry Droplet	225
7.5 Computer Modeling	226
7.6 Recommendations for Additional Study	226
8. REFERENCES	228

LIST OF FIGURES

<u>Figure</u>	<u>Page</u>
E-1. Schematic of the in-duct injection process.	2
E-2. Stirred tank reactor and supporting equipment.	10
E-3. Dependence of k_g on SO_2 concentration.	12
E-4. Dependence of k_g on gas agitation speed at 25 °C and 55 °C (2.0-in diameter propeller). ...	13
E-5. Dependence of k_g on gas agitation speed at 25 °C and 55 °C (2.5-in diameter propeller). ...	14
E-6. Dependence of k_l on SO_2 concentration at 25 °C.	16
E-7. Dependence of k_l on agitation speed.	17
E-8. Enhancement of SO_2 absorption in 17 mM $\text{Ca}(\text{OH})_2$ /0.1 M CaCl_2 solution.	22
E-9. Comparison of enhancement of SO_2 absorption in 17 mM $\text{Ca}(\text{OH})_2$ solutions at various ionic strengths.	23
E-10. Comparison of enhancement in Mississippi $\text{Ca}(\text{OH})_2$ slurry at higher $\text{Ca}(\text{OH})_2$ concentrations.	26
E-11. Comparison of enhancement in slurry from three different sources of $\text{Ca}(\text{OH})_2$ at 0.1 M $\text{Ca}(\text{OH})_2$	27
E-12. Effect of particle size on enhancement predicted by slurry absorption model for 0.1 M $\text{Ca}(\text{OH})_2$ slurry.	29
E-13. Effect of slurry $\text{Ca}(\text{OH})_2$ concentration on enhancement predicted by slurry absorption model for tests performed in the stirred tank (corresponding $d_{\text{droplet}} = 800 \mu\text{m}$, $d_p = 5\text{-}10 \mu\text{m}$, $\theta = 0.9$ s).	31
E-14. Effect of slurry $\text{Ca}(\text{OH})_2$ concentration on gas film resistance predicted by slurry absorption model for tests performed in the stirred tank (corresponding $d_{\text{droplet}} = 800 \mu\text{m}$, $d_p = 5\text{-}10 \mu\text{m}$, $\theta = 0.9$ s).	33
E-15. Enhancement in a slurry droplet predicted by slurry absorption model ($d_{\text{droplet}} = 75 \mu\text{m}$, $d_p = 5 \mu\text{m}$, $\theta = 0.9$ s).	34
E-16. Effect of $\text{Ca}(\text{OH})_2$ concentration in a slurry droplet on enhancement predicted by slurry absorption model ($d_{\text{droplet}} = 75 \mu\text{m}$, $d_p = 5 \mu\text{m}$, $\theta = 0.9$ s).	35
E-17. Gas film resistance as a function of $\text{Ca}(\text{OH})_2$ utilization: using DI $\Delta[\text{S(IV)}] = 7.0 \times 10^{-8}$ mole/m s (equation 5-14).	36
E-18. The gas film resistance versus the contact time. The different curves correspond to different particle sizes of $\text{Ca}(\text{OH})_2$. 200 Pa SO_2 , 0 and 200 mol/m ³ $\text{Ca}(\text{OH})_2$, 100 μm droplet, 0.5-5.0 μm $\text{Ca}(\text{OH})_2$, 0.1-10 s contact time.	41
E-19. The gas film resistance versus the contact time. The different curves correspond to different particle sizes of $\text{Ca}(\text{OH})_2$. 200 Pa SO_2 , 0 and 200 mol/m ³ $\text{Ca}(\text{OH})_2$, 10 μm droplet, 0.5-5.0 μm $\text{Ca}(\text{OH})_2$, 0.1-10 s contact time.	42
E-20. Concentration profiles corresponding to 45 percent gas film resistance. No $\text{Ca}(\text{OH})_2$ (s) in the liquid bulk. 200 Pa SO_2 , 100 μm droplet, 1.6 s contact time.	43
E-21. Concentration profiles corresponding to a gas film resistance of 45 percent. No $\text{Ca}(\text{OH})_2$ (s) in the liquid bulk. 200 Pa SO_2 , 100 μm droplet, 1.6 s contact time.	44
E-22. Concentration profiles corresponding to 45 percent gas film resistance with $\text{Ca}(\text{OH})_2$ (s) in the liquid bulk. 200 Pa SO_2 , 500 mol/m ³ $\text{Ca}(\text{OH})_2$, 100 μm droplet, 2.0 μm $\text{Ca}(\text{OH})_2$, 8.1 s contact time.	45

LIST OF FIGURES (continued)

Figure	Page
E-23. Concentration profiles corresponding to 45 percent gas film resistance with $\text{Ca}(\text{OH})_2$ (s) in the liquid bulk. 200 Pa SO_2 , 500 mol/m ³ $\text{Ca}(\text{OH})_2$, 100 μm droplet, 2.0 μm $\text{Ca}(\text{OH})_2$, 8.1 s contact time.	46
E-24. Gas film resistance versus contact time for different concentrations of $\text{Ca}(\text{OH})_2$ (s). 200 Pa SO_2 , 100 μm droplet, 5 μm $\text{Ca}(\text{OH})_2$	48
E-25. Gas film resistance versus the ratio between k_g and k_l for different reactivities of $\text{Ca}(\text{OH})_2$ (s). k_g corresponds to a 100 μm droplet. 200 Pa SO_2 , 200 mol/m ³ $\text{Ca}(\text{OH})_2$, 100 μm droplet, 0.5-5 μm $\text{Ca}(\text{OH})_2$	49
E-26. Gas film resistance versus the ratio between k_g and k_l for different reactivities of $\text{Ca}(\text{OH})_2$. k_g corresponds to a 10 μm droplet. 200 Pa SO_2 , 200 mol/m ³ $\text{Ca}(\text{OH})_2$, 10 μm droplet, 0.5-5 μm $\text{Ca}(\text{OH})_2$	50
E-27. Gas film resistance versus penetration distance. 200 Pa SO_2 , 200-1,000 mol/m ³ $\text{Ca}(\text{OH})_2$, 100 μm droplet.	51
E-28. Gas film resistance versus penetration distance. 200 Pa SO_2 , 200-1,000 mol/m ³ $\text{Ca}(\text{OH})_2$, 10 μm droplet.	52
1-1A. Schematic of the dry sorbent injection (DSI) process.	56
1-1B. Schematic of the duct spray drying (DSD) process.	57
3-1. Stirred tank reactor and supporting equipment.	79
3-2. Propeller designs used in stirred tank reactor.	83
3-3. Dependence of k_g on SO_2 concentration.	90
3-4. Dependence of k_g on gas agitation speed at 25 °C and 55 °C (2.0-in diameter propeller). ..	91
3-5. Dependence of k_g on gas agitation speed at 25 °C and 55 °C (2.5-in diameter propeller). ..	94
3-6. Comparison of k_g at 55 °C with two propeller sizes.	95
3-7. Dependence of k_l^o on SO_2 concentration at 25 °C.	98
3-8. Dependence of k_l^o on liquid agitation speed at 25 °C and 55 °C.	100
3-9. Contact time as a function of liquid agitation speed.	101
3-10. Comparison of k_l^o measured in several studies as a function of liquid agitation speed.	104
4-1. Enhancement of SO_2 absorption in water.	113
4-2. Enhancement of SO_2 absorption in 0.1 M CaCl_2 solution.	118
4-3. Enhancement of SO_2 absorption in 2.5 mM $\text{Ca}(\text{OH})_2$ /0.1 M CaCl_2 solution.	123
4-4. Enhancement of SO_2 absorption in 17 mM $\text{Ca}(\text{OH})_2$ /0.1 M CaCl_2 solution.	128
4-5. Effect of low D_{OH^-} on enhancement of SO_2 absorption in 2.5 mM $\text{Ca}(\text{OH})_2$ /0.1 M CaCl_2 solution.	130
4-6. Comparison of enhancement of SO_2 absorption in 17 mM $\text{Ca}(\text{OH})_2$ solutions at various ionic strengths.	133
4-7. Enhancement of SO_2 absorption in clear solutions as a function of bulk SO_2 concentration (model: $\theta = 0.9$ s, data: $\theta = 0.9 - 2.5$ s).	135
4-8. Gas film resistance in clear solutions of $\text{Ca}(\text{OH})_2$ as a function of bulk SO_2 concentration (model: $\theta = 0.9$ s, data: $\theta = 0.9 - 2.5$ s).	136
4-9. Gas film resistance in 17 mM $\text{Ca}(\text{OH})_2$ as a function contact time.	138
5-1. Comparison of tests performed in reagent grade slurry.	146
5-2. Estimated error associated with tests performed in 0.1 M $\text{Ca}(\text{OH})_2$ MCB reagent grade slurry.	148

LIST OF FIGURES (continued)

Figure	Page
5-3. Comparison of enhancement in Mississippi hydrate and reagent grade slurry at 0.1 M Ca(OH)_2	150
5-4. Comparison of enhancement in Mississippi Ca(OH)_2 slurry at higher Ca(OH)_2 concentrations.	153
5-5. Comparison of enhancement in slurry from three different sources of Ca(OH)_2 at 0.1 M Ca(OH)_2	155
5-6. Enhancement predicted by slurry absorption model for 35 mM Ca(OH)_2 slurry.	158
5-7. Effect of particle size on enhancement predicted by slurry absorption model for 0.1 M Ca(OH)_2 slurry.	160
5-8. Enhancement predicted by slurry absorption model for 0.4 M Ca(OH)_2 slurry.	161
5-9. Effect of slurry Ca(OH)_2 concentration on enhancement predicted by slurry absorption model for tests performed in the stirred tank (corresponding $d_{\text{droplet}} = 800 \mu\text{m}$, $d_p = 5\text{-}10 \mu\text{m}$, $\theta = 0.9 \text{ s}$).	167
5-10. Effect of slurry Ca(OH)_2 concentration on gas film resistance predicted by slurry absorption model for tests performed in the stirred tank (corresponding $d_{\text{droplet}} = 800 \mu\text{m}$, $d_p = 5\text{-}10 \mu\text{m}$, $\theta = 0.9 \text{ s}$).	168
5-11. Enhancement in a slurry droplet predicted by slurry absorption model ($d_{\text{droplet}} = 75 \mu\text{m}$, $d_p = 5 \mu\text{m}$, $\theta = 0.9 \text{ s}$).	172
5-12. Effect of Ca(OH)_2 concentration in a slurry droplet on enhancement predicted by slurry absorption model ($d_{\text{droplet}} = 75 \mu\text{m}$, $d_p = 5 \mu\text{m}$, $\theta = 0.9 \text{ s}$).	173
5-13. Effect of Ca(OH)_2 concentration in a slurry droplet on gas film resistance predicted by slurry absorption model ($d_{\text{droplet}} = 75 \mu\text{m}$, $d_p = 5 \mu\text{m}$, $\theta = 0.9 \text{ s}$).	174
5-14. Spherical droplet with shrinking core of Ca(OH)_2	176
5-15. Values of $\text{DI } \Delta[\text{S(IV)}]$ derived from the slurry absorption model.	179
5-16. Gas film resistance as a function of Ca(OH)_2 utilization: using $\text{DI } \Delta[\text{S(IV)}] = 7.0 \times 10^{-8} \text{ mole/m s}$ (equation 5-14).	181
6-1. The gas film resistance versus the contact time. The different curves correspond to different particle sizes of Ca(OH)_2 . 200 Pa SO_2 , 0 and 200 mol/m^3 Ca(OH)_2 , 100 μm droplet, 0.5-5.0 μm Ca(OH)_2 , 0.1-10 s contact time.	201
6-2. The gas film resistance versus the contact time. The different curves correspond to different particle sizes of Ca(OH)_2 . 200 Pa SO_2 , 0 and 200 mol/m^3 Ca(OH)_2 , 10 μm droplet, 0.5-5.0 μm Ca(OH)_2 , 0.1-10 s contact time.	202
6-3. Concentrations profiles corresponding to 45 percent gas film resistance. No Ca(OH)_2 (s) in the liquid bulk. 200 Pa SO_2 , 100 μm droplet, 1.6 sec contact time.	204
6-4. Concentration profiles corresponding to a gas film resistance of 45 percent. No Ca(OH)_2 (s) in the liquid bulk. 200 Pa SO_2 , 100 μm droplet, 1.6 sec contact time.	205
6-5. Concentration profiles corresponding to 45 percent gas film resistance with Ca(OH)_2 (s) in the liquid bulk. 200 Pa SO_2 , 500 mol/m^3 Ca(OH)_2 , 100 μm droplet, 2.0 μm Ca(OH)_2 , 8.1 sec contact time.	207
6-6. Concentration profiles corresponding to 45 percent gas film resistance with Ca(OH)_2 (s) in the liquid bulk. 200 Pa SO_2 , 500 mol/m^3 Ca(OH)_2 , 100 μm droplet, 2.0 μm Ca(OH)_2 , 8.1 sec contact time.	208

LIST OF FIGURES (concluded)

<u>Figure</u>		<u>Page</u>
6-7.	Concentration profiles of Ca(OH)_2 (s). 200 Pa SO_2 , 500 mol/m ³ Ca(OH)_2 , 100 μm droplet, 2 μm Ca(OH)_2 .	210
6-8.	The partial pressure of SO_2 at the gas-liquid interface as a function of contact time. The numbers are corresponding penetration depths. 200 Pa SO_2 , 500 mol/m ³ Ca(OH)_2 , 100 μm droplet, 2 μm Ca(OH)_2 .	211
6-9.	Gas film resistance versus contact time for different concentrations of Ca(OH)_2 (s). 200 Pa SO_2 , 100 μm droplet, 5 μm Ca(OH)_2 .	212
6-10.	The gas film resistance versus contact time for different Ca(OH)_2 (s) concentrations. 200 Pa SO_2 , 0-1,000 mol/m ³ Ca(OH)_2 , 100 μm droplet, 2 μm Ca(OH)_2 , 0.1-10 sec contact time.	214
6-11.	The gas film resistance versus contact time for different partial pressures of SO_2 . 50-500 Pa SO_2 , 500 mol/m ³ Ca(OH)_2 , 100 μm droplet, 2 μm Ca(OH)_2 .	215
6-12.	Gas film resistance versus the ratio between k_g and k_l for different reactivities of Ca(OH)_2 (s). k_g corresponds to a 100 μm droplet. 200 Pa SO_2 , 200 mol/m ³ Ca(OH)_2 , 100 μm droplet, 0.5-5 μm Ca(OH)_2 .	216
6-13.	Gas film resistance versus the ratio between k_g and k_l for different reactivities of Ca(OH)_2 . k_g corresponds to a 10 μm droplet. 200 Pa SO_2 , 200 mol/m ³ Ca(OH)_2 , 10 μm droplet, 0.5-5 μm Ca(OH)_2 .	217
6-14.	Gas film resistance versus penetration distance. 200 Pa SO_2 , 200-1,000 mol/m ³ Ca(OH)_2 , 100 μm droplet.	220
6-15.	Gas film resistance versus penetration distance. 200 Pa SO_2 , 200-1,000 mol/m ³ Ca(OH)_2 , 10 μm droplet.	221
6-16.	Gas film resistance versus penetration distance for different partial pressures of SO_2 . 50-500 Pa SO_2 , 200-1,000 mol/m ³ Ca(OH)_2 , 10 μm droplet, 0.5-5 μm Ca(OH)_2 .	222

LIST OF TABLES

<u>Table</u>	<u>Page</u>
E-1. Input Variables for the Slurry Absorption Model Used in Clear Solution Tests	8
E-2. Clear Solution Test Conditions	19
2-1. Input Variables for the Slurry Absorption Model Used in Clear Solution Tests	74
2-2. Estimate Diffusivities of Important Species Used by the Slurry Absorption Model ($\text{cm}^2/\text{s} \times 10^5$)	75
3-1. Comparison of Experimentally Determined Gas Film Mass Transfer Coefficients	96
3-2. Comparison of Experimentally Determined Liquid Film Mass Transfer Coefficients	103
4-1. Clear Solution Test Conditions	108
4-2. Enhancement of SO_2 Absorption in Water at Various Liquid Agitation Speeds ($K_g = 1.51 \times 10^{-5}$ Mole/ m^2 Pa s)	111
4-3. Conditions for Slurry Absorption Model for Absorption of SO_2 in Water	112
4-4. Enhancement of SO_2 Absorption in 0.1 M CaCl_2 at Various Liquid Agitation Speeds	115
4-5. Enhancement of SO_2 Absorption in 0.1 M CaCl_2 at Various SO_2 Concentrations	115
4-6. Conditions for Slurry Absorption Model for Absorption of SO_2 in 0.1 M CaCl_2	117
4-7. Presence of Absorbed Sulfur Species in 0.1 M CaCl_2 Solutions at Various SO_2 Concentrations	119
4-8. Enhancement of SO_2 Absorption in 2.5 mM $\text{Ca}(\text{OH})_2$ with 0.1 M CaCl_2	120
4-9. Conditions for Slurry Absorption Model for Absorption of SO_2 in 2.5 mM $\text{Ca}(\text{OH})_2$ with 0.1 M CaCl_2	122
4-10. Enhancement of SO_2 Absorption in 17 mM $\text{Ca}(\text{OH})_2$ with 0.1 M CaCl_2	125
4-11. Conditions for Slurry Absorption Model for Absorption of SO_2 in 17 mM $\text{Ca}(\text{OH})_2$ with 0.1 M CaCl_2	126
4-12. Enhancement of SO_2 Absorption in 17 mM $\text{Ca}(\text{OH})_2$ Containing No CaCl_2	132
4-13. Enhancement of SO_2 Absorption in 17 mM $\text{Ca}(\text{OH})_2$ Containing 0.1 M NaCl	132
5-1. Test Conditions for $\text{Ca}(\text{OH})_2$ Experiments	141
5-2. Results of Tests Performed in 35 mM $\text{Ca}(\text{OH})_2$ MCB Reagent Grade Slurry	144
5-3. Results of Tests Performed in 0.1 M $\text{Ca}(\text{OH})_2$ MCB Reagent Grade Slurry	145
5-4. Results of Tests Performed in 0.1 M $\text{Ca}(\text{OH})_2$ Mississippi $\text{Ca}(\text{OH})_2$ Slurry	149
5-5. Results of Tests Performed in 0.4 M $\text{Ca}(\text{OH})_2$ Mississippi $\text{Ca}(\text{OH})_2$ Slurry	151
5-6. Results of Tests Performed in 0.1 M $\text{Ca}(\text{OH})_2$ Mississippi Slaked Lime Slurry	154
5-7. Predicted Gas Film Resistance in 1.0 M $\text{Ca}(\text{OH})_2$ Slurry at Various SO_2 Concentrations ...	162
5-8. Penetration Distances and Maximum Settling Velocities Predicted by the Slurry Absorption Model - 4,000 ppm SO_2	164
5-9. Measured Settling Velocities of Three Slurry Types	165
6-1. Typical Bulk Solution Composition and Activity Coefficients	199
6-2. Range of Slurry Conditions	199
6-3. Equilibrium Constants at 55 °C	200

EXECUTIVE SUMMARY

E.1 INTRODUCTION

Emission control technologies for power plants fall into three categories, depending on where they are applied: before, during or after combustion. Post-combustion, flue gas desulfurization (FGD) processes using calcium-based sorbents have gained interest as promising techniques. Such processes applied to older power plants must be inexpensive and must be able to retrofit the existing power plant equipment. The DOE-PETC has initiated a comprehensive effort aimed at developing in-duct injection technology to a point of commercial readiness for use by power plants requiring SO_2 control in the near future.

A schematic of a typical in-duct injection process is shown in Figure E-1. Sorbent, typically calcium hydroxide [$\text{Ca}(\text{OH})_2$], is injected into flue gas which is typically at 130-180 °C downstream of the air preheater and upstream of the particulate collection device. The dry, reacted sorbent is collected in the existing particulate collector, commonly an electrostatic precipitator, and forms a non-hazardous, dry solid waste product. Since water is required for the reaction of SO_2 and sorbent, the flue gas must either be humidified [dry sorbent injection (DSI)], or the sorbent must be mixed with water and injected as a slurry [duct spray drying (DSD)]. In either case, the water that is injected reduces the temperature to about 50-70 °C.

While this in-duct injection technology may be simple to apply and has low capital costs compared to commercially-available wet scrubbing processes, the economics of this process can be improved substantially by enhancing sorbent utilization. The in-duct injection process, although simple

Figure E-1. Schematic of the in-duct injection process.

in concept, is a very complicated process to describe fully in a theoretical sense, and additional study will be necessary to produce a comprehensive model of this process.

The general physical or "global" mechanisms are important for predicting the SO_2 removal potential of DSD. However, these mechanisms are not the focus of this research. Equally important for prediction of SO_2 absorption in these processes is understanding and modeling the absorption of SO_2 into a single droplet in the absence of the more complicated global effects. Once the basic mass transfer principles which control SO_2 absorption and reaction are understood and described, these principles can serve as a basis upon which to couple the theory describing the global mechanisms. This study focuses on describing SO_2 absorption into a single droplet in order to learn more about how the absorption might be enhanced. The experimental work performed in the stirred tank reactor was intended to simulate absorption of SO_2 into a slurry droplet.

Also, a computer model of SO_2 absorption into $\text{Ca}(\text{OH})_2$ slurries based on mass transfer theories and engineering principles was developed as part of this project. This computer program will be used to predict the relative contribution of gas and liquid mass transfer, solid dissolution, and other chemical processes which control SO_2 absorption into a slurry droplet under a variety of conditions. The experimental work supports this effort by providing measurements of the absorption of SO_2 which are used to validate the model.

Three theories have prevailed which describe the type of mass transfer associated with SO_2 absorption into liquid solutions. The oldest and simplest, which serves as a basis for most mass-transfer theories, is the film theory. In this theory, a concentration gradient is assumed from the interface to the bulk solution over a thin film. In the penetration theory, mass transfer is determined by how much contact time a fluid element spends at the gas/liquid interface. Another theory for description of gas absorption is the surface-renewal theory, which is a generalized version of the penetration theory. This theory is used to predict the mass transfer that governs SO_2 absorption in the stirred tank. Results of some studies which described and measured gas absorption in slurries and alkaline solutions are presented in this report and compared to the measured absorption in the stirred

tank. Most of the current models of SO_2 absorption in slurry droplets have not treated the absorption and reaction of SO_2 in a rigorous fashion. Some begin with the assumption that the absorption is controlled by gas film resistance and do not fully address the liquid film resistances based on the complex chemical reactions, or on the dissolution of $\text{Ca}(\text{OH})_2$. Some allow only a monosized droplet distribution, although other models have shown the importance of accounting for the size distribution of droplets in a typical spray. There are considerable differences in the conclusions reached as a result of these modeling efforts. Those that attempt to describe the complex global mechanisms of the absorption in detail typically simplify the calculation of absorption and reaction of SO_2 by making assumptions that may not be sufficient. The objective of this program was to conduct measurements intended to discover mass transfer processes that limit the absorption and investigate other chemical and physical processes that might affect absorption of SO_2 as well as the role of sorbent reactivity. The experimental data was used to validate the slurry absorption model that was developed in parallel to the experimental work.

E.2 THEORY OF SO_2 ABSORPTION IN $\text{Ca}(\text{OH})_2$ SLURRIES

The reaction of SO_2 with alkaline species occurs in the dissolved or aqueous state. Therefore a number of experiments were designed to measure and describe absorption into the aqueous clear solution.

The absorption and reaction of SO_2 becomes more complicated in the presence of an excess of solids. In a $\text{Ca}(\text{OH})_2$ slurry, there is an aqueous solution saturated with $\text{Ca}(\text{OH})_2$ and containing the remaining excess solids. Reaction with SO_2 consumes dissolved $\text{Ca}(\text{OH})_2$, which must be replenished. The dissolution rate of $\text{Ca}(\text{OH})_2$ is fast but may not be fast enough to maintain a completely saturated bulk solution. Another factor that may be important in influencing the absorption rate of SO_2 into slurries is the rate at which CaSO_3 crystallizes. As the slurry absorbs and reacts with SO_2 , the amount of CaSO_3 increases in solution and eventually precipitates when the point of saturation is achieved. Enhancement from crystallized CaSO_3 is much less than the enhancement from CaSO_3 in solution.

The crystallization of CaSO_3 and how it affects SO_2 absorption must therefore also be considered in absorption modeling.

A model was developed to predict the absorption of SO_2 into $\text{Ca}(\text{OH})_2$ slurries with all of these factors considered. The model combines equations to describe the absorption and reaction of SO_2 , the dissolution rate of $\text{Ca}(\text{OH})_2$ solids, and the crystallization rate of CaSO_3 . Experimental results were used to validate the model.

E.2.1 Basic Mass Transfer Principles

The absorption of SO_2 proceeds in two steps. First, SO_2 in the gas phase must diffuse from the bulk gas mixture to the interface. Next, it must diffuse from the interface into the liquid. At the interface, the flux of SO_2 from the gas must equal the flux of SO_2 into the liquid. A key objective of this research is to determine the degree to which the gas phase and liquid phase driving forces are limiting or controlling the absorption. The absorption is frequently referred to as "gas film controlled" or "liquid film controlled" for this reason. As aqueous SO_2 is reacted, the absorption of SO_2 is enhanced by reducing the mass transfer resistance and increasing the driving force for absorption. The degree to which liquid phase mass transfer is enhanced is quantified in terms of the enhancement factor. The enhancement factor is the ratio of the measured absorption rate with reaction to the expected absorption rate without reaction.

The percent of gas film resistance reflects the degree to which gas film mass transfer dominates the absorption of SO_2 . When gas film mass transfer dominates the absorption, changes to the liquid phase composition cannot enhance mass transfer further. The transfer of SO_2 from the bulk gas phase to the surface of the liquid is the limiting or controlling mechanism. As gas film resistance approaches 100 percent, the interface concentration of SO_2 is insignificant. In other words, the liquid phase is so reactive toward SO_2 that as soon as the SO_2 is absorbed, it reacts immediately.

Ultimately, this would be the most desirable condition because the absorption rate is maximized. The research focuses on determining conditions where the mass transfer is not gas film controlled so that

enhancement of absorption under these conditions might be improved by altering liquid phase characteristics.

E.2.2 Enhancement Predicted by Surface Renewal Theory

Predicting the absorption rate of SO_2 is complicated by the fact that the absorption is an unsteady state process. Therefore a series of unsteady state material and charge balances must be solved to determine the concentration of constituents that influence absorption. Solutions are calculated based on assumed boundary conditions. Boundary conditions are developed from one of a number of theories which have been proposed to describe mass transfer across a fluid surface.

A review of proposed mass transfer models for absorption in stirred tanks found that the surface renewal theories could be approximated closely by solving the simpler film theory and replacing the species diffusivities by their square roots. The surface renewal theory solution for SO_2 absorption in water assumes, first, that H_2O is not included in the species balance, and, second, that the bisulfite and hydrogen ions diffuse at the same rate. Thus, the approximate solution takes the form:

$$\phi = 1 + \frac{\sqrt{D_{\text{HSO}_3^-}}}{\sqrt{D_{\text{SO}_2}}} \frac{\sqrt{K_a/4}}{\sqrt{[\text{SO}_2]_i} - \sqrt{[\text{SO}_2]_o}} \quad (\text{E-1})$$

This relationship shows a linear dependence of ϕ on $1/\sqrt{[\text{SO}_2]_i}$ when $[\text{SO}_2]_o$ can be neglected. In a solution of pure water, HSO_3^- formed by absorption and reaction of SO_2 must diffuse at the same rate as the H^+ ions that are formed by the reaction. This effect is referred to as ion-pairing.

For SO_2 absorption into a solution containing CaCl_2 , the bisulfite and hydrogen ions diffuse independently. Thus, the approximate solution gives this relationship:

$$\phi = 1 + \frac{\sqrt{D_{\text{HSO}_3^-}}}{\sqrt{D_{\text{SO}_2}}} \frac{[\text{HSO}_3^-]_i - [\text{HSO}_3^-]_o}{[\text{SO}_2]_i - [\text{SO}_2]_o} \quad (\text{E-2})$$

The bulk concentrations of aqueous SO_2 and bisulfite can be neglected in most cases. The interfacial bisulfite concentration is determined from the equilibrium relationship. The hydrogen ion concentration is determined by material and charge balances at the interface. Because $[\text{HSO}_3^-]_i$ depends on the square root of $[\text{SO}_2]_i$, this theory again shows a dependence of ϕ on $1/\sqrt{[\text{SO}_2]_i}$.

The surface renewal theory was also applied to absorption in solutions containing dissolved $\text{Ca}(\text{OH})_2$. Formation of sulfite is significant in $\text{Ca}(\text{OH})_2$ solutions. Therefore, the enhancement in $\text{Ca}(\text{OH})_2$ solutions can be expressed by the following relationship:

$$\phi = 1 + \frac{\sqrt{D_{\text{HSO}_3^-}}}{\sqrt{D_{\text{SO}_2}}} \left(\frac{[\text{HSO}_3^-]_i - [\text{HSO}_3^-]_o}{[\text{SO}_2]_i - [\text{SO}_2]_o} \right) + \frac{\sqrt{D_{\text{SO}_3^{2-}}}}{\sqrt{D_{\text{SO}_2}}} \left(\frac{[\text{SO}_3^{2-}]_i - [\text{SO}_3^{2-}]_o}{[\text{SO}_2]_i - [\text{SO}_2]_o} \right) \quad (\text{E-3})$$

The alkaline solution reacts with aqueous SO_2 very quickly. In all solutions containing $\text{Ca}(\text{OH})_2$ that were tested, $[\text{SO}_2]_o$ and $[\text{HSO}_3^-]_o$ were found to be insignificant. The interfacial concentrations of sulfite and bisulfite are not known but are related to $[\text{H}^+]_i$ and $[\text{SO}_2]_i$ by the equilibrium relations. When the appropriate bulk concentrations are neglected and the two equilibrium expressions are applied to equation (E-3), the equation for the enhancement factor becomes:

$$\phi = \frac{\sqrt{D_{\text{HSO}_3^-}}}{\sqrt{D_{\text{SO}_2}}} \frac{K_{c1}}{[\text{H}^+]_i} + \frac{\sqrt{D_{\text{SO}_3^{2-}}}}{\sqrt{D_{\text{SO}_2}}} \left(\frac{K_{c1} K_{c2}}{[\text{H}^+]_i^2} + [\text{SO}_3^{2-}]_o \right) \quad (\text{E-4})$$

E.2.3 Slurry Absorption Model

The slurry absorption model was developed as part of this research. Experiments performed for this research are intended to verify the model and draw attention to factors which affect SO_2 absorption in $\text{Ca}(\text{OH})_2$ solutions and slurries. The slurry absorption model consists of three parts. The

first part simulates absorption of SO_2 into the solution, which is enhanced by chemical reaction. The second part includes dissolution of Ca(OH)_2 solids in the solution. The third part consists of CaSO_3 crystallization calculated from a rate expression developed experimentally. The model has been run successfully to simulate the clear solution experiments performed in the stirred tank reactor to verify the first part of the model. The model was also run for conditions which simulate the experiments performed in slurry solutions to verify the second part of the model. No experiments were run specifically to verify the third part of the model.

The model uses the penetration theory to develop the boundary conditions necessary to solve the unsteady state differential mass balance equations for the absorption of SO_2 . The unsteady state material balances are included for total S(IV) species, calcium species, and chloride. A charge balance at the interface is made by adjusting the level of chloride in the solution. Also, the fluxes of calcium and chloride are set equal to zero at the interface. The unsteady state material balance for calcium requires that the rate of dissolution of Ca(OH)_2 be known. The dissolution rate of Ca(OH)_2 varies with time and distance from the interface. The operating conditions and solution compositions used in the stirred tank experiments had to be specified as inputs to the model. Table E-1 lists the input variables for the clear solution experiments.

Model runs for various solution composition were performed with the bulk gas phase SO_2 concentration, p_{SO_2} , set at 500, 1,000, 2,000, 3,000, 4,000, and 5,000 ppm. The pH and ion concentrations were set to values which represented the liquid phase at steady state in the stirred tank reactor. The model provides several forms of output. Since the absorption rate is generally a function of the contact time, the model lists the output for ten periods of time over a specified range of time. The model calculates an average absorption rate.

TABLE E-1. INPUT VARIABLES FOR THE SLURRY ABSORPTION MODEL
USED IN CLEAR SOLUTION TESTS

Operating Conditions	p_{SO_2} , K_g , contact time, temperature, pH
Solution Composition	Ca^{2+} , Mg^{2+} , Na^+ , K^+ , SO_3^{2-} , SO_4^{2-} , CO_3^{2-} , Cl^- , H_2O

E.3 EXPERIMENTAL

The reactor system is designed to provide a bulk gas phase with a known SO_2 concentration in contact with liquid solutions. The area of gas/liquid contact at the interface is known by maintaining a flat, undisturbed surface. The reactor was designed to approximate the mass transfer properties that are common to slurry droplets. Measurements of the range of gas and liquid film mass transfer coefficients available in the reactor were made. Mass transfer coefficients can be varied in the reactor by changing gas and liquid agitator speeds. The reactor is capable of providing a range of liquid film mass transfer coefficients corresponding to contact times from 0.7 to 6.6 s at 55 °C. The maximum gas film mass transfer coefficient available in the reactor is about one order-of-magnitude smaller than would be for a typical slurry droplet.

E.3.1 Design of Reactor and Supporting Equipment

The stirred tank reactor and supporting equipment used to measure the absorption rate of SO_2 are pictured in Figure E-2. The gas/liquid contact area was 81 cm². The base plate also contains ports for liquid inlet and outlet. The top plate contains fitted ports for the gas inlet and outlet and the thermocouple.

Gas was continuously removed from the reactor for SO_2 analysis. Liquid was typically fed continuously to the reactor, although some experiments were performed with liquid introduced in batch mode. An important feature of the reactor design is that the gas and liquid phases are stirred independently. Experiments required that gas agitation be maximized to maintain a high gas film mass transfer coefficient.

The SO_2 absorption rate was determined primarily by gas phase material balance. The material balance was based on supplying a known concentration of SO_2 to the reactor and measuring the reactor outlet (bulk) gas concentration. Also, a cross-check of the accuracy of the gas phase material balance was made by directly analyzing the absorbed total S(IV)_0 in the liquid. Two types of liquid phase analyses were performed. Direct titration with iodine and ion chromatography were used to determine total sulfur of liquid samples.

Figure E-2. Stirred tank reactor and supporting equipment.

E.3.2 Mass Transfer Properties of the Stirred Tank Reactor

The reactor has a characteristic gas film mass transfer coefficient, k_g , and a liquid film mass transfer coefficient, k_l , which depend on specific operating conditions. A series of initial experiments were performed to determine these mass transfer properties of the reactor and relate them to variable operating conditions such as agitation speeds. In tests run to determine the gas film coefficient, the reactor was filled with 1.1 L of 1.0 M NaOH for reaction in batch mode. The gas phase was stirred with the 2-in diameter propeller blade. Results showed that k_g was not a function of SO_2 concentration. The k_g also did not vary measurably because of changing temperature from 25 °C to 55 °C. The k_g was, however, strongly dependent on gas agitation speed. The k_g could also be affected by changes in the liquid level in the reactor (i.e., changes in gas volume), however this was maintained constant throughout all experiments. The results at various SO_2 concentrations are shown in Figure E-3 and show that k_g can be repeatedly measured to within ± 2.5 percent.

Next, the liquid agitator was held constant at approximately 500 rpm and the gas agitation speed was varied between 150 and 1400 rpm. Inlet gas flow rate was varied such that the outlet SO_2 concentration remained near 1500 ppm. As expected, higher gas agitation speeds result in much higher gas film mass transfer coefficients (Figure E-4). A correlation for k_g and gas agitation speed was developed from these measurements for use in calculating k_g in later experiments:

$$k_g A = 1.86 \times 10^{-4} (\text{rpm})^{0.50} \quad (\text{E-5})$$

The $k_g A$ does not appear to have a strong temperature dependence, especially at the higher agitation speeds.

Since disturbance of the gas/liquid surface was not approached with the 2.0-in diameter propeller at maximum gas agitation speed, the reactor could benefit from greater agitation. Tests were run with a 2.5-in propeller under the same conditions as the 2.0-in diameter propeller. Results for tests run with this larger propeller at both 25 °C and 55 °C are shown in Figure E-5. Compared with data in

Figure E-3. Dependence of k_g on SO_2 concentration.

Figure E-4. Dependence of k_g on gas agitation speed at 25 °C and 55 °C (2.0-in diameter propeller).

Figure E-5. Dependence of k_g on gas agitation speed at 25 °C and 55 °C (2.5-in diameter propeller).

Figure E-4 for a 2-in diameter propeller, the 2.5-in diameter propeller resulted in about a 50 percent increase in k_g at a corresponding rpm. Because of the increased gas film mass transfer, the 2.5-in diameter propeller was used for remaining experiments.

When studying gas film mass transfer, it is preferred that the reactor have a k_g which approaches the range of values expected for slurry droplets. Values of k_g for slurry droplets are estimated to be in the range of 10^{-2} to 10^{-3} mole/cm² s bar. The maximum k_g measured for this study was on the order of 10^{-4} mole/cm² s bar. The results obtained in these experiments are comparable to gas film coefficients derived by other authors. The gas film mass transfer coefficients measured in this study are slightly greater than the values measured in other studies.

The values of k_l° were measured as a function of temperature, agitation and SO₂ concentration. The k_l° should only be a function of the properties of the liquid phase. The results shown in Figure E-6 confirm that k_l° is not a function of SO₂ concentration. These results also indicate that k_l° can be measured repeatedly within about ± 5 percent. The relationship between k_l° and liquid agitation speed was determined at 25 °C. During this set of tests, the SO₂ concentration was allowed to vary between 1690 and 3070 ppm, and the liquid agitation speed was varied from 160 to 1350 rpm. Figure E-7 shows the strong dependence of k_l° on liquid agitation speed. A correlation for k_l° as a function of liquid agitation speed was developed from this data for use in future experiments performed at 25 °C. Figure E-7 also presents the values of k_l° measured at 55 °C as a function of liquid agitation speed. The increase in temperature from 25 °C to 55 °C results in a factor-of-2 increase in k_l° .

Values of k_l° measured by other researchers are of the same order-of-magnitude. k_l° values vary from one study to the next, probably due to the different geometry of the reactors and diffusivities of the gases. Most of the previous experiments were run at lower liquid agitation speeds and, therefore, did not produce very high values for k_l° . Since contact times on the order of 1 s were preferred in this research, higher values for k_l° were required, and liquid agitation speeds were greater.

Figure E-6. Dependence of k°_1 on SO_2 concentration at 25 °C.

Figure E-7. Dependence of k_l on agitation speed.

E.3.3 Comparison of Mass Transfer Properties of The Stirred Tank to that in a Slurry Droplet

The mass transfer properties of the reactor determined in the tests discussed above can be compared to the properties of a slurry droplet to determine how closely the reactor simulates the mass transfer properties of a droplet. Assuming the Sherwood number equals 2, a slurry drop of 10 μm would have a corresponding k_g of 1.1×10^{-2} moles/cm² s bar. A 100- μm droplet would have a k_g of 1.1×10^{-3} moles/cm² s bar. The highest value of k_g measured in the stirred tank was 1.5×10^{-4} moles/cm² s bar. This corresponds to a slurry droplet diameter of approximately 800 μm , which is much larger than would be considered typical of droplets in commercial use. It is easy to understand from this relationship why the design of the reactor included steps to minimize gas film resistance (i.e., increase k_g). Unfortunately, the attempts made to minimize gas film resistance did not produce the order-of-magnitude increase in k_g necessary to simulate a more reasonable droplet size (<100 μm).

The liquid film mass transfer coefficient, k_l , is a function of the surface renewal time in the liquid. The amount of contact time in commercial slurry injection applications is determined by the slurry droplet drying time (usually on the order of 1 s). A contact time of 1 s is equivalent to a k_l of 7.0×10^{-5} m/s. For comparison, the range of k_l values measured in the stirred tank at 55 °C was between 2.7×10^{-5} and 8.6×10^{-5} m/s. This is equivalent to a range of contact times of 0.65 to 6.6 s.

These comparisons show that the stirred tank is capable of representing the mass transfer properties associated with a very large droplet with a drying time typical of a smaller droplet. The ratio of the degree of gas film mass transfer to the liquid film mass transfer in the stirred tank is a useful quantity, which can also be used for comparison. Because of the low values of k_g available in the reactor, the ratio of mass transfer coefficients will be about an order-of-magnitude lower than that expected for a slurry droplet.

E.4 RESULTS OF EXPERIMENTS IN CLEAR SOLUTIONS

E.4.1 Experimental Conditions

During these tests, SO₂ was absorbed into several different solutions at 55 °C. The gas phase was mixed at the maximum agitation speed of approximately 1400 rpm, resulting in a gas phase mass

transfer coefficient of 1.5×10^{-4} mole/s cm² bar. Solution compositions and other variables are listed in Table E-2.

E.4.2 Enhancement in Water

Enhancement of SO₂ absorption in water was measured over a narrow range of SO₂ concentrations at varied liquid agitation speeds. The initial pH of the water was adjusted to 5.0 with a small amount of HCl so that absorption would not be biased by the presence of alkaline species in the water. The results show that for SO₂ concentrations between 2,200 and 2,450 ppm, the reaction of SO₂ with pure water enhanced SO₂ absorption by a factor of 3 over absorption of SO₂ into a non-reactive solution. The absorption of SO₂ was primarily limited or controlled by the reaction occurring in the liquid phase (2-7 percent of gas film resistance).

The slurry absorption model was run with bulk solution concentrations and other conditions that simulated the absorption experiments in water. The enhancement measured in the stirred tank reactor experiments compared favorably with both the surface renewal prediction and the slurry absorption model.

E.4.3 Enhancement in 0.1 M CaCl₂ Solution

The effect that calcium chloride has on SO₂ absorption was studied first by absorbing SO₂ into a solution containing 0.1 M CaCl₂. The enhancement factor ranged between about 4 at the high SO₂

TABLE E-2. CLEAR SOLUTION TEST CONDITIONS

Liquid Makeup	SO ₂ Concentration (ppm)	Liquid Agitation (rpm)	k ₁ × 10 ⁵ (m/s)
Water	2,200 - 2,600	110 - 1,360	2.4 - 8.6
0.1 M CaCl ₂	1,000 - 4,970	76 - 1,330	2.2 - 8.4
2.5 mM Ca(OH) ₂ 0.1 M CaCl ₂	1,070 - 5,450	200 - 1,330	2.7 - 8.4
17 mM Ca(OH) ₂ 0.1 M CaCl ₂	580 - 3,790	230 - 1,360	2.9 - 8.6
17 mM Ca(OH) ₂	710 - 2,600	706 - 1,190	5.0 - 7.6
17 mM Ca(OH) ₂ 0.1 M NaCl	710 - 2,690	706 - 1,210	5.0 - 7.7

concentrations near 4,400 ppm and 6 at the low SO_2 concentration of 1,000 ppm. At an SO_2 concentration of 2,500 ppm, enhancement was improved about 30 percent over enhancement measured in water. Gas film resistance for the tests in 0.1 M CaCl_2 solutions is slightly higher than for the tests in water. Absorption of SO_2 in CaCl_2 solutions differs from that in water only because Cl^- is present, allowing HSO_3^- and H^+ to diffuse independently. In other words, the reaction of SO_2 in the CaCl_2 solution is not inhibited by the ion-pairing effect.

Both the slurry absorption model and the surface renewal theory predict that enhancement is reduced when larger amounts of sulfur species, mostly SO_2 and HSO_3^- , are present in the liquid phase. The results measured in the stirred tank correlate best with the lower enhancement predicted by the slurry absorption model.

E.4.4 Enhancement in 2.5 mM $\text{Ca}(\text{OH})_2$ Solution Containing 0.1 M CaCl_2

The clear $\text{Ca}(\text{OH})_2$ solutions containing 0.1 M CaCl_2 were intended to simulate the liquid composition and the chemical properties of slurry solutions. The first set of tests was run at a $\text{Ca}(\text{OH})_2$ level of 2.5 mM. These experiments were aimed at measuring the enhancement factor over a range of SO_2 concentrations (1,070-5,450 ppm). Enhancement factors measured during these tests ranged from just above 5, at high SO_2 concentrations, up to 19 at the lowest concentrations. Gas film resistance increased considerably over levels measured with water and with CaCl_2 solutions, ranging from about 10 percent at the highest SO_2 concentrations to 30 percent at the lowest SO_2 concentration.

The experimental data appear to be described relatively well by both the surface renewal theory and the slurry absorption model over the range of SO_2 concentrations studied. Again, the two models differ slightly. The slurry absorption model predicts the experimentally measured enhancement more accurately at the lower SO_2 concentrations.

E.4.5 Enhancement in 17 mM $\text{Ca}(\text{OH})_2$ Solution Containing 0.1 M CaCl_2

Another set of tests was run with $\text{Ca}(\text{OH})_2$ at 17 mM, the level of saturation in 0.1 M CaCl_2 . This set of conditions is particularly interesting because it represents the same liquid conditions in the dissolved portion of a $\text{Ca}(\text{OH})_2$ slurry. The only difference between it and a slurry is the ability of the

slurry to replenish the reacted $\text{Ca}(\text{OH})_2$ with the dissolution of solids lime. The SO_2 concentrations studied during experiments with 17 mM $\text{Ca}(\text{OH})_2$ ranged from 580 to 3,790 ppm. The test conducted at the lowest SO_2 concentration resulted in absorption that was too gas film controlled to accurately determine the enhancement. Gas film resistance for the test runs varied from 12 percent to 83 percent. The enhancement factor measured during these tests ranged from about 13, at the highest SO_2 concentrations to 133 at the lowest SO_2 concentration that could be evaluated.

The slurry absorption model was run with bulk solution concentrations and other conditions that simulated a 17 mM $\text{Ca}(\text{OH})_2$ in 0.1 M CaCl_2 solution. The results of the slurry absorption model are plotted with enhancement estimated by the surface renewal theory, and enhancement measured in the stirred tank reactor in Figure E-8. The slurry absorption model predicted over twice the enhancement measured in the stirred tank. The surface renewal theory also predicted much greater enhancement than that measured in the stirred tank, and slightly greater enhancement than that predicted by the slurry absorption model. The rate of crystallization of CaSO_3 had little effect on the SO_2 absorption predicted by the model. Of all the properties considered, only the changes made to the diffusivity of OH^- had a significant effect on the prediction of the SO_2 absorption.

E.4.6 Enhancement in Solutions of Varying Ionic Strength

To investigate the effect of the ionic strength in the bulk solution, 17 mM $\text{Ca}(\text{OH})_2$ solutions of varying ionic strength were tested. One test was run using 17 mM $\text{Ca}(\text{OH})_2$ solution containing no CaCl_2 . Another test was run with 0.1 M NaCl added, which is 1/3 the ionic strength of 0.1 M CaCl_2 .

By changing the ionic strength of the bulk solution, activities of constituents can change, which directly affects solution equilibria. Equilibrium constants and solubility constants as well as diffusivities of ionic species can be affected.

The results of tests performed in 17 mM $\text{Ca}(\text{OH})_2$ solutions with varied ionic strength are compared in Figure E-9. Varying the ionic strength of the bulk solution had no significant effect on the enhancement of SO_2 absorption.

Figure E-8. Enhancement of SO_2 absorption in 17 mM $\text{Ca}(\text{OH})_2/0.1$ M CaCl_2 solution.

The clear solution experiments revealed a few important details about the absorption of SO_2 in solutions containing Ca(OH)_2 . The relative SO_2 absorption rate was measured in terms of the enhancement factor and in terms of the extent that gas film resistance controls the absorption. Also, the enhancement of SO_2 absorption measured in these solutions was used to validate the enhancement predicted by the slurry absorption model.

E.5 RESULTS OF EXPERIMENTS IN Ca(OH)_2 SLURRIES

The experiments performed in Ca(OH)_2 slurries were designed to study two factors affecting absorption. The most important factor was the amount of solids present in the slurry. SO_2 absorption was measured in slurries with total Ca(OH)_2 concentration ranging from 35 mM to 1.0 M. Absorption of SO_2 at concentrations of 500 to 5,000 ppm into slurries containing 1.0 M (7 wt percent) Ca(OH)_2 or more solids was found to be controlled primarily by gas film resistance.

A second factor that was studied involved measuring SO_2 absorption into slurries with varied Ca(OH)_2 reactivity. Thus, slurries were prepared with Ca(OH)_2 from different sources, and SO_2 absorption rate was measured. Properties of the solid Ca(OH)_2 particles, such as surface area and particle size, are known to affect reactivity toward SO_2 . These measurements were made to determine how much of an effect such properties could have on the enhancement factor and, hence, on their ability to control or limit the absorption of SO_2 .

The slurry experiments allowed for further verification of the slurry absorption model. Several important factors affecting the absorption of SO_2 into a clear solutions of Ca(OH)_2 were investigated. The slurry experiments also provide data to evaluate the effect of various properties of the Ca(OH)_2 solids. This allows for validation of the Ca(OH)_2 dissolution portion of the slurry absorption model.

E.5.1 Results of Slurry Experiments

The first set of slurry experiments used reagent grade Ca(OH)_2 . Slurries containing three levels of total Ca(OH)_2 concentration (35 mM, 0.1 M, and 1.0 M) were tested with these reagents. Initial experiments at these concentrations showed that absorption was greatly improved with solids present. The second set of test runs with 35 mM Ca(OH)_2 slurry, prepared with MCB Reagent

Ca(OH)_2 , produced measurable values of $\emptyset$. Gas film resistance was moderately high. Contact times for these experiments were varied from about 1 to 2 s. Enhancement factors measured in the 35 mM Ca(OH)_2 slurry ranged from about 20 to 80, while gas film resistance ranged from 23 to 65 percent.

Another set of tests were performed at the higher solids concentration of 0.1 M Ca(OH)_2 . The higher solids level in the 0.1 M Ca(OH)_2 slurry resulted in enhancement factors ranging from 35 to 185 and gas film resistance increased to the range of 34 to 81 percent. The highest enhancement factor and gas film resistance is always achieved at lowest SO_2 concentrations and short contact times.

Tests in slurries prepared with Mississippi Ca(OH)_2 at three Ca(OH)_2 concentrations were performed. The first had a Ca(OH)_2 concentration of 0.1 M so that results could be compared to the test using 0.1 M reagent grade Ca(OH)_2 . The other two tests used slurries prepared at higher Ca(OH)_2 concentrations of 0.4 M and 1.0 M. For the range of contact times of 1-2 s, enhancement factors ranged from about 50 to 250. Gas film resistance varied from 42 to 85 percent.

The results of the test with Mississippi Ca(OH)_2 slurry containing 0.4 M Ca(OH)_2 are compared to the test results with Mississippi Ca(OH)_2 slurry containing 0.1 M Ca(OH)_2 and those from tests with 35 mM Reagent grade Ca(OH)_2 in Figure E-10. An increase in enhancement was measured, but this increase was only 20 to 25 percent for a 4-fold increase in solids concentration. Gas film resistance during these experiments was above 50 percent. Experiments were run with different types of Ca(OH)_2 to determine if measurement of the enhancement in the stirred tank is sensitive enough to show significant differences from one type to another. One batch of Mississippi CaO was slaked at a concentration of 0.1 M Ca(OH)_2 over a period of approximately 1 h. Figure E-11 compares the test results of the three types of Ca(OH)_2 . No Significant differences in enhancement were measured among these three types of Ca(OH)_2 . An analysis of the surface area of the Ca(OH)_2 particles in each slurry was not performed. These results indicate that either the three Ca(OH)_2 s tested had similar reactivities toward SO_2 or the stirred tank reactor is capable of measuring only large differences in absorption seen with changes in solids concentration.

Figure E-10. Comparison of enhancement in Mississippi $\text{Ca}(\text{OH})_2$ slurry at higher $\text{Ca}(\text{OH})_2$ concentrations.

Figure E-11. Comparison of enhancement in slurry from three different sources of Ca(OH)_2 at 0.1 M Ca(OH)_2 .

E.5.2 Validation of Slurry Absorption Model For $\text{Ca}(\text{OH})_2$ Slurries

The model was validated for the solution containing 17 mM $\text{Ca}(\text{OH})_2$ and 0.1 M CaCl_2 by adjusting the diffusivity of hydroxide to 40 percent of the referenced value. The composition of the slurry was assumed to be the same as the 17 mM (saturated) $\text{Ca}(\text{OH})_2$ solution with additional solid $\text{Ca}(\text{OH})_2$.

Solids concentration was specified as the same concentrations used in the stirred tank absorption experiments. The model was run for slurries containing total $\text{Ca}(\text{OH})_2$ at levels of 35mM, 0.1 M, 0.4 M and 1.0 M in 0.1 M CaCl_2 . The model was run at several particle sizes to determine which sizes represent the conditions of the slurry used in the stirred tank experiments. Particle sizes of 0.5, 1, 5 and 10 μm were used as input to the model.

A first step in predicting enhancement in slurries with the slurry absorption model was to validate that reducing the D_{OH^-} to 40 percent improved the ability of the model to predict the experimental results obtained in the stirred tank. In the case of the 17 mM $\text{Ca}(\text{OH})_2$ solution, the model overpredicted enhancement by a factor of 2 without adjusting the D_{OH^-} to 40 percent of the referenced value. The model was then run with reduced D_{OH^-} at two different particle sizes. By reducing D_{OH^-} , the slurry absorption model was able to predict the enhancement measured in the stirred tank experiments for the 35 mM slurry. Increasing the particle size of the $\text{Ca}(\text{OH})_2$ solids from 1 to 5 μm did not have a significant effect on the predicted enhancement.

A comparison was made between enhancement predicted at different contact times. Figure E-12 shows model results generated at a particle size of 1.0 μm at a 2.5 s contact time. The model verified that the enhancement factor in slurries is not a function of contact time over the range investigated by the experiments. The model predicts that no significant change in enhancement should result from reducing the particle size from 1.0 μm to 0.5 μm . However, increasing the particle size to 5 μm and further to 10 μm results in measurably lower enhancement. The experimental results appear to be best described by a slurry with a particle size between 5 and 10 μm .

Figure E-12. Effect of particle size on enhancement predicted by slurry absorption model for 0.1 M $\text{Ca}(\text{OH})_2$ slurry.

There is a possible explanation for the difference in enhancement predicted by the model and measured in the stirred tank when solids content is increased. As is the case for all slurries, $\text{Ca}(\text{OH})_2$ particles will settle due to gravity if not well mixed. Although the bulk solution was well mixed in slurry experiments in the stirred tank, the boundary layer is inherently stagnant. Dissolved species remain present in the boundary layer for the defined contact time, but the solid particles may have settled out of the boundary layer sooner. Thus, the solid particles may not have enhanced the absorption of SO_2 as much as the model would predict. The experiments showed that this effect was more pronounced at higher solids concentrations. Model results show that the penetration distance becomes much smaller as the slurry solids content is increased. Also, the penetration distance is smaller for larger slurry particles. Solids are more likely to settle out of the boundary layer if the penetration distance is smaller.

E.5.3 Discussion of Slurry Absorption Experiments

The slurry absorption experiments documented the effects that increased solids content and changes to reactivity of the slurry have on SO_2 absorption. The effects were reported in terms of the enhancement factor and the extent that gas film resistance controlled the absorption. In some of these experiments, a completely gas film controlled absorption was achieved, thus enhancing the absorption to the highest degree. The results of the slurry absorption experiments were used to validate enhancement and degree of gas film resistance predicted by the slurry absorption model. Because solid $\text{Ca}(\text{OH})_2$ is present in the slurries, these experiments were used to validate the part of the model that governs solid $\text{Ca}(\text{OH})_2$ dissolution and reaction. Conclusions that were reached regarding the model's ability to predict the experimentally measured absorption of SO_2 are also summarized below.

Enhancement factors predicted by the slurry absorption model for absorption in the 35 mM, 0.1 M, 0.4 M, and 1.0 M $\text{Ca}(\text{OH})_2$ slurries studied are summarized in Figure E-13. Enhancement factors are presented as a function of SO_2 concentration. The clear solution experiments pointed out that measurements of enhancement in slurries would not be possible with bulk gas SO_2 concentrations less than 2,000 ppm because these conditions would yield a gas film controlled absorption. Initial slurry tests were limited to the range of 2,000 to 5,000 ppm SO_2 , and tests with higher slurry solids content

Figure E-13. Effect of slurry Ca(OH)_2 concentration on enhancement predicted by slurry absorption model for tests performed in the stirred tank (corresponding $d_{\text{droplet}} = 800 \mu\text{m}$, $d_p = 5\text{-}10 \mu\text{m}$, $\theta = 0.9 \text{ s}$).

required over 3,000 ppm SO_2 to avoid an 80 percent or more gas film controlled condition. Finally, the tests with 1.0 M $\text{Ca}(\text{OH})_2$ required over 4,000 ppm SO_2 to make accurate measurements of enhancement. The stirred tank and the model were not able to produce meaningful enhancement factors under these conditions because the absorption was too gas film controlled. These limitations due to gas film resistance are easily seen in Figure E-14. In order to predict the enhancement and gas film resistance in a slurry droplet for SO_2 absorption of the in-duct injection process, the global mass transfer effects cannot be ignored. Thus, this analysis falls short of predicting the mass transfer that would be expected in a slurry droplet.

Figures E-15 and E-16 present the enhancement factors predicted by these slurry droplet model runs. Figure E-15 shows the predicted enhancement as a function of SO_2 concentration. Figure E-16 shows the relationship of enhancement in a slurry droplet with increasing solids concentration. For a given SO_2 concentration and total $\text{Ca}(\text{OH})_2$ concentration, the enhancement predicted for a slurry droplet in Figures E-15 and E-16 is less than the enhancement shown in Figure E-13 for the stirred tank.

Figure E-17 shows the relationship between gas film resistance and $\text{Ca}(\text{OH})_2$ utilization for several SO_2 concentrations. The results show that the absorption of SO_2 is primarily liquid film controlled at low to moderate levels of $\text{Ca}(\text{OH})_2$ utilization. This confirms the results determined by the slurry absorption model that were previously shown.

E.6 COMPUTER MODELING

E.6.1 Model

The model includes three kinetic phenomena which all depend on the solution composition:

- Dissolution of $\text{Ca}(\text{OH})_2$
- Crystallization of CaSO_3
- Absorption of SO_2

These kinetic rates are not independent from each other. To calculate the dissolution rate and the crystallization rate, the bulk solution composition is needed which depends on the amount of

Figure E-14. Effect of slurry Ca(OH)_2 concentration on gas film resistance predicted by slurry absorption model for tests performed in the stirred tank (corresponding $d_{\text{droplet}} = 800 \mu\text{m}$, $d_p = 5\text{-}10 \mu\text{m}$, $\theta = 0.9 \text{ s}$).

Figure E-15. Enhancement in a slurry droplet predicted by slurry absorption model ($d_{\text{droplet}} = 75 \mu\text{m}$, $d_p = 5 \mu\text{m}$, $\theta = 0.9 \text{ s}$).

Figure E-16. Effect of Ca(OH)₂ concentration in a slurry droplet on enhancement predicted by slurry absorption model ($d_{\text{droplet}} = 75 \mu\text{m}$, $d_p = 5 \mu\text{m}$, $\theta = 0.9 \text{ s}$).

Figure E-17. Gas film resistance as a function of Ca(OH)_2 utilization: using DI $\Delta[\text{S(IV)}] = 7.0 \times 10^{-8}$ mole/m s.

absorbed SO_2 and vice versa. The model assumes instantaneous equilibrium of the species H^+ , H_2O , OH^- , SO_2 , HSO_3^- and SO_3^{2-} . The liquid is saturated with SO_2 at the gas liquid interface. The solid $\text{Ca}(\text{OH})_2$ dissolution rate is calculated by steady state mass transfer theory. The solid $\text{Ca}(\text{OH})_2$ is assumed to be spherical particles in an infinite stagnant solution. Electrical potential gradient is assumed to be very small so the diffusivities are constant throughout the liquid phase.

The differential material balances for total calcium, S(IV) species and the charge can easily be integrated to the following expressions.

$$D_{\text{Ca}^{2+}} C_{\text{Ca}^{2+}} + D_{\text{CaOH}^+} C_{\text{CaOH}^+} + D_{\text{CaSO}_3^0} C_{\text{CaSO}_3^0} = \alpha_1 + \beta_1 y \quad (\text{E-6})$$

$$D_{\text{SO}_2} C_{\text{SO}_2} + D_{\text{HSO}_3^-} C_{\text{HSO}_3^-} + D_{\text{SO}_3^{2-}} C_{\text{SO}_3^{2-}} + D_{\text{CaSO}_3} C_{\text{CaSO}_3} = \alpha_2 + \beta_2 y \quad (\text{E-7})$$

$$2 D_{\text{Ca}^{2+}} C_{\text{Ca}^{2+}} + D_{\text{CaOH}^+} C_{\text{CaOH}^+} + D_{\text{H}^+} C_{\text{H}^+} - D_{\text{OH}^-} C_{\text{OH}^-} - D_{\text{HSO}_3^-} C_{\text{HSO}_3^-} - 2 D_{\text{SO}_3^{2-}} C_{\text{SO}_3^{2-}} - D_{\text{O}^{1-}} C_{\text{O}^{1-}} = \alpha_3 + \beta_3 y \quad (\text{E-8})$$

where α_i and β_i are integration constants.

Calcium sulfite will precipitate in the liquid film during the absorption. The supersaturation of CaSO_3 , RS_{CaSO_3} , is defined as:

$$RS_{\text{CaSO}_3} = \frac{a_{\text{Ca}^{2+}} a_{\text{SO}_3^{2-}}}{K_{sp} C_{\text{CaSO}_3}} \quad (\text{E-9})$$

The crystallization/dissolution rate, R_c , can be written as a function of the supersaturation of CaSO_3 :

$$R_c = 1.62 \cdot 10^{-1} \exp(-5153/T) (RS_{\text{CaSO}_3} - 1)^n A / RS_{\text{CaSO}_3}^{1/4} \quad (\text{mol} / \text{m}^3 \text{ s}) \quad (\text{E-10})$$

where A is the BET surface area of calcium sulfite per volume of slurry.

The crystallization rate, R_c , is in the same way as the dissolution rate of $\text{Ca}(\text{OH})_2$ a function of both time, t , and the distance, x , from the gas-liquid interface.

The absorption of SO_2 is modeled with the penetration model. The unsteady state material balance for each species is:

$$\frac{\partial C_i}{\partial t} = -\nabla J_i + r_i \quad (\text{E-11})$$

$$J_i = z_i D_i \frac{F}{RT} C_i \nabla \phi - D_i \nabla C_i \quad (\text{E-12})$$

All the material balances with S(IV) species are combined to one differential equation and all the material balances involving calcium species are combined. This allows not having to use rate constants fixed at arbitrarily high values for the equilibrium reactions.

$$\frac{\partial C_{S(IV)}}{\partial t} = \sum_{i=1}^4 \left(D_i \nabla^2 C_i - z_i D_i \frac{F}{RT} \nabla (C_i \nabla \phi) \right) - R_d(x,t) \quad (\text{E-13})$$

$i = \text{SO}_2, \text{HSO}_3^-, \text{SO}_3^{2-}, \text{CaSO}_3^0$

$$\frac{\partial C_{Ca \text{ tot}}}{\partial t} = \sum_{i=1}^3 \left(D_i \nabla^2 C_i - z_i D_i \frac{F}{RT} \nabla (C_i \nabla \phi) \right) - R_d(x,t) + R_d(x,t) \quad (\text{E-14})$$

$i = \text{Ca}^{2+}, \text{CaOH}^+, \text{CaSO}_3^0$

$$\frac{\partial C_{OI}}{\partial t} = D_{OI} \nabla^2 C_{OI} + D_{OI} \frac{F}{RT} \nabla (C_{OI} \nabla \phi) \quad (\text{E-15})$$

The absorption rate will vary with time. At the start when the liquid element is brought up to the surface, the absorption rate is large since the interfacial concentration of SO_2 is small. As the absorption proceeds, the concentration of SO_2 at the gas-liquid interface increases, and the absorption rate decreases. The average absorption rate, measured from the stirred tank reactor experiments, is calculated from:

$$\overline{N_{\text{SO}_2}} = \frac{1}{\theta} \int_0^\theta N_{\text{SO}_2} dt \quad (\text{E-16})$$

where θ is the total contact time.

The computer code is written in FORTRAN 77 and is available both on a VAX computer and on a Cray computer. In order to solve the differential equations that describe the absorption process, the dissolution rate of Ca(OH)_2 , R_d , and the crystallization rate of CaSO_3 , R_c , need to be calculated.

To solve the equations for the concentrations at the Ca(OH)_2 surface, all the concentrations are expressed in the concentrations of hydrogen and sulfite by using the equilibria equations. That reduces the number of equations to two nonlinear equations, $f_1=0$ and $f_2=0$.

$$\begin{aligned} C_{H^+N+1} \left(\frac{\partial f_1}{\partial C_{H^+}} \right)_N + C_{SO_3^{2-}N+1} \left(\frac{\partial f_1}{\partial C_{SO_3^{2-}}} \right)_N &= -f_1 (C_{H^+N}, C_{SO_3^{2-}N}) \\ &+ C_{H^+N} \left(\frac{\partial f_1}{\partial C_{H^+}} \right)_N + C_{SO_3^{2-}N} \left(\frac{\partial f_1}{\partial C_{SO_3^{2-}}} \right)_N \end{aligned} \quad (E-17)$$

$$\begin{aligned} C_{H^+N+1} \left(\frac{\partial f_2}{\partial C_{H^+}} \right)_N + C_{SO_3^{2-}N+1} \left(\frac{\partial f_2}{\partial C_{SO_3^{2-}}} \right)_N &= -f_2 (C_{H^+N}, C_{SO_3^{2-}N}) \\ &+ C_{H^+N} \left(\frac{\partial f_2}{\partial C_{H^+}} \right)_N + C_{SO_3^{2-}N} \left(\frac{\partial f_2}{\partial C_{SO_3^{2-}}} \right)_N \end{aligned} \quad (E-18)$$

Orthogonal collocation transforms the partial differential equations in t and x into ordinary differential equations in t . The first and the second spatial derivative at any collocation points can be expressed in terms of the value of the function at the collocation points in that specific element. The gas film resistance is calculated as the average absorption rate divided by k_g and P_{SO_2} . The gas film resistance is thus a normalized flux which makes it possible to compare results for cases with different P_{SO_2} and different mass transfer coefficients. The gas film resistance is also a ratio between the average flux and the maximum flux for that specific case. If the absorption is totally gas film controlled,

the gas film resistance is equal to one, and the absorption rate can not further be increased by any chemical reaction in the absorbing liquid. If the gas film resistance is equal to 50 percent, this condition implies that up to this point the slurry has absorbed 50 percent of the amount that could have been absorbed if the process was totally gas film controlled. The modeling results are often presented as a function of contact time. The contact time is the time the liquid element stays at the gas-liquid interface before it is transported back to the liquid bulk.

E.6.2 Modeling Results

The reactivity of Ca(OH)_2 has been altered by changing the size of the Ca(OH)_2 particles in the slurry. The particle size ranged from 0.2 μm to 5 μm . Figures E-18 and E-19 show how the gas film resistance varies with contact time for different Ca(OH)_2 reactivities. In the modeling results shown in Figure E-18, k_g was set at a value corresponding to a 100- μm slurry droplet. The corresponding droplet size for the results in Figure E-19 is 10 μm .

Initially, all the resistance to mass transfer is concentrated in the gas film, since the concentration of SO_2 in the liquid is approximately zero. During the absorption, hydrogen ions are produced and Ca(OH)_2 dissolves to neutralize the formed hydrogen ions. If the dissolution of Ca(OH)_2 is not fast enough or if the concentration of Ca(OH)_2 approaches zero, the pH at the gas-liquid interface decreases and the gas film resistance decreases.

Figures E-20 and E-21 show the concentration profiles for an absorption case without any $\text{Ca(OH)}_2(\text{s})$ in the liquid bulk. These profiles take 1.6 s to be formed, and they correspond to an instantaneous gas film resistance of 45 percent. The partial pressure of SO_2 is 2,000 ppm, and k_g is $1.1 \times 10^{-4} \text{ mol/m}^2 \text{ s Pa}$.

Figures E-22 and E-23 show the profiles for the same absorption case as above when the bulk concentration of $\text{Ca(OH)}_2(\text{s})$ is 500 mol/m^3 . These profiles also correspond to a gas film resistance of 45 percent, but since the presence of $\text{Ca(OH)}_2(\text{s})$ maintains a high gas film resistance a longer time, it takes 8.1 s until these profiles are formed. Figure E-22 with the profiles of H^+/OH^- and $\text{SO}_2/\text{HSO}_3^-/\text{SO}_3^{2-}$ looks approximately the same as Figure E-20.

Figure E-18. The gas film resistance versus the contact time. The different curves correspond to different particle sizes of Ca(OH)_2 . 200 Pa SO_2 , 0 and 200 mol/m³ Ca(OH)_2 , 100 μm droplet, 0.5-5.0 μm Ca(OH)_2 , 0.1-10 s contact time.

Figure E-19. The gas film resistance versus the contact time. The different curves correspond to different particle sizes of Ca(OH)_2 . 200 Pa SO_2 , 0 and 200 mol/m³ Ca(OH)_2 , 10 μm droplet, 0.5-5.0 μm Ca(OH)_2 , 0.1-10 s contact time.

Figure E-20. Concentrations profiles corresponding to 45 percent gas film resistance. No $Ca(OH)_2$ (s) in the liquid bulk. 200 Pa SO_2 , 100 μm droplet, 1.6 s contact time.

Figure E-21. Concentration profiles corresponding to a gas film resistance of 45 percent. No $\text{Ca}(\text{OH})_2$ (s) in the liquid bulk. 200 Pa SO_2 , 100 μm droplet, 1.6 s contact time.

Figure E-22. Concentration profiles corresponding to 45 percent gas film resistance with $Ca(OH)_2$ (s) in the liquid bulk. 200 Pa SO_2 , 500 mol/m³ $Ca(OH)_2$, 100 μ m droplet, 2.0 μ m $Ca(OH)_2$, 8.1 s contact time.

Figure E-23. Concentration profiles corresponding to 45 percent gas film resistance with Ca(OH)_2 (s) in the liquid bulk. 200 Pa SO_2 , 500 mol/m³ Ca(OH)_2 , 100 μm droplet, 2.0 μm Ca(OH)_2 , 8.1 s contact time.

During the absorption of SO_2 into a slurry of calcium hydroxide the partial pressure of SO_2 at the gas-liquid interface increases, causing the absorption rate to decrease. Figure E-23 shows how the P_{SO_2} varies with contact time for the same conditions as in Figure E-21 and E-22. Figure E-24 shows how the gas film resistance varies with different concentrations of $\text{Ca}(\text{OH})_2(\text{s})$. At higher concentrations of $\text{Ca}(\text{OH})_2(\text{s})$ it takes a longer time for the $\text{Ca}(\text{OH})_2(\text{s})$ front to move away from the gas-liquid interface. When there is no $\text{Ca}(\text{OH})_2(\text{s})$ present in the liquid bulk the gas film resistance is only 60 percent after 0.1 s, while for a $\text{Ca}(\text{OH})_2(\text{s})$ concentration of $1,000 \text{ mol/m}^3$, the gas film resistance is larger than 60 percent up to a contact time of 6 s.

Figures E-25 and E-26 show how the $\text{Ca}(\text{OH})_2(\text{s})$ reactivity affects the absorption rate of SO_2 . The gas film resistance is plotted versus the ratio between k_g and k_l for a k_g corresponding to a $100 \text{ }\mu\text{m}$ slurry droplet in Figure E-25, and for a k_g corresponding to a $10 \text{ }\mu\text{m}$ slurry droplet in Figure E-26. Figures E-27 and E-28 shows how the gas film resistance varies with the penetration distance for different reactivities of $\text{Ca}(\text{OH})_2(\text{s})$. The results in Figure E-27 are modeled with a k_g corresponding to a $100 \text{ }\mu\text{m}$ slurry droplet and the results in Figure E-28 correspond to a $10 \text{ }\mu\text{m}$ slurry droplet. The partial pressure of SO_2 is 2,000 ppm and the concentration of $\text{Ca}(\text{OH})_2(\text{s})$ is varied from 200 up to $1,000 \text{ mol/m}^3$.

E.7 CONCLUSIONS AND RECOMMENDATIONS

The theory, experiments and modeling activities of this research allowed for many conclusions to be made about absorption of SO_2 into $\text{Ca}(\text{OH})_2$ slurries, and validation of the slurry absorption model. Below is a summary of the conclusions that are discussed throughout the preceding sections of this report.

Also during the course of this research, a number of areas which require additional study were identified. Some additional experiments are recommended to address assumptions made in this research. Recommendations are also made for modifying the slurry absorption model.

Figure E-24. Gas film resistance versus contact time for different concentrations of Ca(OH)_2 (s).
200 Pa SO_2 , 100 μm drop, 5 μm Ca(OH)_2 .

Figure E-25. Gas film resistance versus the ratio between k_g and k_l for different reactivities of Ca(OH)_2 (s). k_g corresponds to a $100 \mu\text{m}$ droplet. 200 Pa SO_2 , $200 \text{ mol/m}^3 \text{ Ca(OH)}_2$, $100 \mu\text{m}$ drop, $0.5\text{-}5 \mu\text{m Ca(OH)}_2$.

Figure E-26. Gas film resistance versus the ratio between k_g and k_l for different reactivities of Ca(OH)_2 . k_g corresponds to a $10 \mu\text{m}$ droplet. 200 Pa SO_2 , $200 \text{ mol/m}^3 \text{ Ca(OH)}_2$, $10 \mu\text{m}$ droplet, $0.5\text{-}5 \mu\text{m Ca(OH)}_2$.

Figure E-27. Gas film resistance versus penetration distance. 200 Pa SO_2 , 200-1,000 mol/m³ Ca(OH)_2 , 100 μm droplet.

Figure E-28. Gas film resistance versus penetration distance. 200 Pa SO_2 , 200-1,000 mol/m³ Ca(OH)_2 , 10 μm droplet.

E.7.1 Mass Transfer Theory

1. The surface renewal theory is the best available mass transfer model to use for describing the absorption of SO_2 into $\text{Ca}(\text{OH})_2$ slurries. Applied as the penetration theory (assuming constant contact times for slurry elements) absorption of SO_2 into slurries can be accurately predicted.
2. The enhancement factor (normalized flux) is a valuable basis for comparison of absorption. It was proved to be independent of contact time (or k^o_l), but strongly dependent on SO_2 concentration.

E.7.2 Stirred Tank Reactor Experiments

1. The stirred tank was designed to maximize the gas film mass transfer coefficient, k_g , so that mass transfer would be similar to that of a slurry droplet and experiments would not be gas film controlled. However, k_g was an order of magnitude less than expected for a typical droplet and some experiments were gas film controlled.
2. The liquid film coefficient, k^o_l , measured in the stirred tank represented reasonable contact times between 0.7 and 6.6 s. For the range of slurry concentrations studied, k^o_l did not vary due to increased solids content (i.e., greater viscosity). Corrections to k^o_l may need to be made to slurries with greater than 1.0 M $\text{Ca}(\text{OH})_2$ solids.
3. Gas film resistance began to control absorption of SO_2 in the reactor when enough solids were added to the $\text{Ca}(\text{OH})_2/\text{CaCl}_2$ solution to form a slurry. Measurement of enhancement factors for SO_2 absorption in slurries could not be made at low SO_2 concentrations because gas film resistance was too high.
4. Addition of $\text{Ca}(\text{OH})_2$ solids greatly enhanced SO_2 absorption, although the increment of enhancement measured in the stirred tank diminished as the slurry solids concentration was increased.
5. Enhancement measured in slurries prepared with $\text{Ca}(\text{OH})_2$ from three different sources was virtually the same.

E.7.3 Model Validation

1. The slurry absorption model predicted enhancement factors that compared well with both the surface renewal theory solutions and with the measured enhancement from clear solution experiments in the stirred tank. However, both the model and the surface renewal theory solutions overpredicted enhancement that was measured in the stirred tank for the case of a 17 mM Ca(OH)_2 solution.
2. Adjusting the diffusivity of hydroxide, D_{OH^-} , to 40 percent of the referenced value allowed the model to more accurately predict enhancement in the 17 mM Ca(OH)_2 solution and in slurries. Adjusting D_{OH^-} did not significantly change the enhancement predicted by the model for dilute Ca(OH)_2 solutions.
3. The model predicted the enhancement of SO_2 absorption measured in the stirred tank for slurries of low solids content, but predicted higher enhancement than measured in the stirred tank for slurries of high solids content. Experimental data might be influenced by solids settling in the boundary layer, but it is unclear whether this occurs in droplets.
4. The model predicted little difference in enhancement for changes in particle size (reactivity) of Ca(OH)_2 unless the particle size is changed by an order of magnitude. This supports that enhancement is not sensitive to changes in the reactivity of the solids unless the reactivity is grossly different, as found also in stirred tank experiments.

E.7.4 Computer Modeling

Although this is not a model of a slurry droplet it seems probable that the absorption of SO_2 into a slurry of Ca(OH)_2 is in most cases gas film controlled. The contact time when the liquid film resistance becomes important is often too long to be practical. For example, in a spray dryer, the drying of the droplet is so fast that the absorption process, as long as the droplet is wet, will be gas film controlled. When the water has evaporated, other processes determine the absorption rate. The only time the liquid film resistance can be of importance is when very unreactive lime is used in small droplets.

SECTION 1

INTRODUCTION

Emission control technologies for power plants fall into three categories, depending on where they are applied: before, during or after combustion. Post-combustion, flue gas desulfurization (FGD) processes using calcium-based sorbents have gained interest as promising techniques. Such processes applied to older power plants must be inexpensive and must be able to retrofit the existing power plant equipment. Several initial studies (Babu, 1988; Bechtel Inc., 1988; Samuel, 1989; Giovanni, 1988; Yoon, 1985) showed that injection of calcium-based sorbents into the existing ductwork of a power plant might be a low cost option worthy of further research. Thus, the DOE-PETC has initiated a comprehensive effort aimed at developing in-duct injection technology to a point of commercial readiness for use by power plants requiring SO_2 control in the near future.

A schematic of a typical in-duct injection process is shown in Figure 1-1. Sorbent, typically calcium hydroxide [$\text{Ca}(\text{OH})_2$], is injected into flue gas which is typically at 130-180 °C downstream of the air preheater and upstream of the particulate collection device. The dry, reacted sorbent is collected in the existing particulate collector, commonly an electrostatic precipitator, and forms a non-hazardous, dry solid product. Since water is required for the reaction of SO_2 and sorbent, the flue gas must either be humidified or the sorbent must be mixed with water and injected as a slurry. In either case, the water that is injected reduces the temperature to about 50-70 °C. Figure 1-1A presents the schematic of dry sorbent injection (DSI). In this process, $\text{Ca}(\text{OH})_2$ is typically injected into a duct upstream of the water humidification point, but may alternatively be injected downstream of water

Figure 1-1A. Schematic of the dry sorbent injection (DSI) process.

Figure 1-1B. Schematic of the duct spray drying (DSD) process.

humidification. Figure 1-1B presents the schematic of duct spray drying (DSD) in which Ca(OH)_2 slurry is injected into a duct upstream of the existing particulate control device.

Although this in-duct injection technology may be simple to apply and has low capital costs compared to commercially available wet scrubbing processes, the economics of this process can be improved substantially by enhancing sorbent utilization. The studies noted above found that the in-duct injection process is capable of removing about 40 to 60 percent of the SO_2 present in the flue gas at a Ca to S ratio of 1.5 to 2.0. Therefore, only 20 to 40 percent of the sorbent is typically utilized, depending upon how much sorbent is injected. Techniques which enhance the absorption of SO_2 and promote utilization of the sorbent could make the in-duct injection process much more commercially attractive.

In order to improve absorption of SO_2 in the in-duct injection process, the overall mechanisms which govern the absorption must be understood. Some basic understanding of these mechanisms has been gained by Energy and Environmental Research (1989), under the same DOE Duct Injection Program. More has been gained through previous studies such as those conducted by Lee (1988), and Harriot (1988). However, the in-duct injection process, although simple in concept, is a very complicated process to describe fully in a theoretical sense, and additional study will be necessary to produce a comprehensive model.

For instance, different mechanisms occur when Ca(OH)_2 is injected as a dry powder and mixed with water inside the duct, as opposed to being injected as a slurry. In the first case, the sorbent must impact or "scavenge" the water droplets to form a reactive slurry. Some of the sorbent particles may only become partially wet and never reach a full slurry state. When sorbent is injected as a slurry, mechanisms which become important are the atomization of the droplet (which determines its size) and the droplet drying time. To describe or model these processes involves coupling fluid dynamics and simultaneous heat transfer and mass transfer.

Although the general physical or "global" mechanisms are important for predicting the SO_2 removal potential of the two types of in-duct injection processes, these mechanisms are not the focus of

this research. Equally important for prediction of SO_2 absorption in these processes is understanding and modeling the absorption of SO_2 into a single droplet in the absence of the more complicated global effects. Once the basic mass transfer principles which control SO_2 absorption and reaction are understood and described, these principles can serve as a basis upon which to couple the theory describing the global mechanisms. This study focuses on describing SO_2 absorption into a single droplet in order to learn more about how the absorption might be enhanced. The experimental work performed in the stirred tank and the other analyses that comprise this section were intended to simulate absorption of SO_2 into a slurry droplet.

In addition, the DOE program called for a computer model of SO_2 absorption into $\text{Ca}(\text{OH})_2$ slurries based on mass transfer theories and engineering principles. This computer model was developed and will be used to predict the relative contribution of gas and liquid mass transfer, solid dissolution, and other chemical processes which control SO_2 absorption into a slurry droplet under a variety of conditions. The experimental work described in this section supports this effort by providing measurements of the SO_2 absorption rate which are used to validate the model.

It should be noted that this research, although funded in support of in-duct injection technology, may be equally as useful in understanding and describing SO_2 absorption in $\text{Ca}(\text{OH})_2$ slurries used in spray drying applications. Since the results of experiments and the model describe absorption into slurry droplets, the in-duct injection and spray drying processes are essentially the same at this fundamental level. For application of these results to spray dryers, however, slightly longer contact times of 2 to 10 s would be of more interest.

Three theories have prevailed to describe the type of mass transfer associated with SO_2 absorption into liquid solutions. The oldest and simplest, which serves as a basis for most mass transfer theories, is the film theory proposed by Whitman (1923). In this theory, a concentration gradient from the interface to the bulk solution over a thin film thickness is assumed. In the penetration theory developed by Higbie (1935), mass transfer is determined by how much contact time a fluid element spends at the gas/liquid interface. The third theory for description of gas absorption is the

surface renewal theory proposed by Danckwerts (1955), which is a generalized version of the penetration theory. This theory, as applied by Chang and Rochelle (1980), is used to predict the mass transfer that governs SO_2 absorption in the stirred tank. Chang and Rochelle added the important chemical reactions of SO_2 in several solutions and produced equations that were relied on to predict SO_2 absorption for this study.

Results of some studies which described and measured gas absorption in slurries and alkaline solutions are discussed in this report and compared to the measured absorption in the stirred tank. Of these studies, only those by Uchida (1977,1978), Sada (1977,1979), and Vivian (1973) specifically reported measurements of absorption of SO_2 into $\text{Ca}(\text{OH})_2$ slurries. More extensive and valuable information is available regarding absorption of SO_2 into alkaline solutions and water. This program also relied heavily on the experimental work of Chang and Rochelle (1979, 1980, 1981, 1982) and Weems and Rochelle (1981) who studied SO_2 absorption in several alkaline solutions with emphasis on enhancing the absorption with buffer additives. Others who have reported useful measurements of SO_2 absorption in alkaline solutions and water include Sada, et al., (1978) and Hikita et al., (1977,1978). Several researchers reported useful results of gas absorption into slurries other than $\text{Ca}(\text{OH})_2$ slurries. Many of the slurries studied were alkaline and involved instantaneous reaction such as that of SO_2 in $\text{Ca}(\text{OH})_2$ slurries [Uchida (1975,1977), Sada (1981) and Ramachandran (1969)]. Other studies, such as those by Quicker, Alper and Deckwer (1989), Sada and Kumazawa (1982), Holstvoogd, et al. (1986) and Miyachi, et al. (1981), were useful in determining the effect of increased slurry solids content on mass transfer properties.

Most of the current models of SO_2 absorption in slurry droplets have not treated the absorption and reaction of SO_2 in a rigorous fashion. Some, such as the model of Jozewicz and Rochelle (1984) began with the assumption that the absorption is controlled by gas film resistance and therefore, do not fully address liquid film resistances based on the complex chemical reactions, or dissolution of $\text{Ca}(\text{OH})_2$. Damle (1985) and Karlsson and Klingspor (1987) determined that liquid phase resistances would be minor and constructed models of SO_2 absorption controlled by gas film resistances and the

dissolution of $\text{Ca}(\text{OH})_2$. Another model by Malbodi (1986) considered both the gas and liquid film resistances and $\text{Ca}(\text{OH})_2$ dissolution and concluded that the absorption of SO_2 is controlled primarily by $\text{Ca}(\text{OH})_2$ dissolution.

Some of the models allow only a monosized droplet distribution, whereas other more developed models, such as those by Jozewicz and Rochelle and by Kinsey and Harriot (1986,1988), have shown the importance of accounting for the size distribution of droplets in a typical spray. The model of Kinsey and Harriot includes both gas and liquid phase resistances but does not consider $\text{Ca}(\text{OH})_2$ dissolution as a controlling process. There are some considerable differences in the conclusions reached as a result of these modeling efforts. Those that attempt to describe the complex global mechanisms of the absorption in detail typically simplify the calculation of absorption and reaction of SO_2 by making assumptions that may not be sufficient. Thus, under this DOE sponsored program, Energy and Environmental Research (1989) has developed a model that focuses on the global mechanisms that affect mass transfer and used a rigorous treatment of the absorption and reaction of SO_2 in a slurry droplet.

The objective of this program was to conduct measurements designed to discover the mass transfer processes that limit absorption of SO_2 , the chemical and physical processes that might affect SO_2 absorption and the role of sorbent reactivity. As discussed in Section 1, the experimental data was used to validate the concurrently developed slurry absorption model. Section 2 introduces the mass transfer theory which governs the SO_2 absorption process. The stirred tank reactor that was used to perform the absorption experiments is described in Section 3 along with a discussion of the methods used to measure absorption of SO_2 into the solutions and slurries. Results of SO_2 absorption experiments are presented in Sections 4 and 5. The clear solution experiments of Section 4 allow for validation of the model with experimental measurements and theory. The results of slurry experiments described in Section 5 further validate the model. Also, the slurry absorption model was extrapolated to predict SO_2 absorption into slurry droplets, and the results are summarized in Section 5. Conclusions reached during the course of this research are discussed throughout the report. Section 6 gives

detailed discussions of the computer model developed. Section 7 provides a summary of conclusions and recommendations that address the specific objectives outlined above.

SECTION 2

THEORY OF SO_2 ABSORPTION IN $\text{Ca}(\text{OH})_2$ SLURRIES

This research is focused on describing and measuring the absorption of SO_2 from a dilute gas into several solutions and, ultimately, into $\text{Ca}(\text{OH})_2$ slurries. Since SO_2 reacts instantaneously in the solutions studied, the absorption and reaction of SO_2 is controlled, or limited, by mass transfer principles.

The reaction of SO_2 with alkaline species occurs in the dissolved or aqueous state. Therefore a number of experiments were designed to measure and describe absorption into the aqueous clear solution. Chang and Rochelle (1979, 1981) investigated the absorption of SO_2 into aqueous clear solutions and developed equations to predict the absorption rate into solutions undergoing instantaneous reversible reaction.

The absorption and reaction of SO_2 becomes more complicated in the presence of an excess of solids. In a $\text{Ca}(\text{OH})_2$ slurry, there is an aqueous solution saturated with $\text{Ca}(\text{OH})_2$ and containing the remaining excess solids. Reaction with SO_2 consumes dissolved $\text{Ca}(\text{OH})_2$, which must be replenished. The dissolution rate of $\text{Ca}(\text{OH})_2$ is fast but may not be fast enough to maintain a completely saturated bulk solution. Another factor that may be important in influencing the absorption rate of SO_2 into slurries is the rate at which CaSO_3 crystallizes. As the slurry absorbs and reacts with SO_2 , the amount of CaSO_3 increases in solution and eventually precipitates when the point of CaSO_3 saturation is achieved. The crystallization of CaSO_3 and its effects on SO_2 absorption must also be considered.

A model was developed to predict the absorption of SO_2 into $\text{Ca}(\text{OH})_2$ slurries with all of these factors considered. The model combines equations describing the absorption and reaction of SO_2 , the

dissolution rate of solid $\text{Ca}(\text{OH})_2$, and the crystallization of CaSO_3 . Experimental results were used to validate the model.

2.1 BASIC MASS TRANSFER PRINCIPLES

For the experiments performed for this research, we are interested in describing the absorption of SO_2 across a gas/liquid interface into a liquid phase where it is available for reaction. Because the reaction of SO_2 with the slurry influences the absorption rate, the liquid phase reactions must be considered when describing the mass transfer of SO_2 .

2.1.1 Mass Transfer Coefficients

Absorption proceeds in two steps. First, SO_2 in the gas phase must diffuse from the bulk gas mixture to the interface. The absorption rate of SO_2 to the interface is described frequently, as in Treybal (1980), in terms of a gas film mass transfer coefficient, k_g , and the concentration driving force:

$$N_{\text{SO}_2} = k_g A (p_{\text{SO}_2, o} - p_{\text{SO}_2, i}) \quad (2-1)$$

Next the SO_2 must diffuse from the interface into the bulk liquid. At the interface, the flux of SO_2 from the gas must equal the flux of SO_2 in the liquid. The absorption rate of SO_2 from the interface into the bulk liquid is described in terms of a liquid film mass transfer coefficient, k_l , and the concentration driving force (in mole/m³):

$$N_{\text{SO}_2} = k_l A ([\text{SO}_2]_i - [\text{SO}_2]_o) \quad (2-2)$$

Reaction of SO_2 in the liquid phase can therefore enhance absorption by reducing $[\text{SO}_2]_o$ and increasing the liquid film mass transfer coefficient, k_l . A key objective of this research is to determine the degree to which the gas phase and liquid phase driving forces are limiting or controlling the absorption. The absorption is frequently referred to as "gas film controlled" or "liquid film controlled" for this reason.

2.1.2 Enhancement of Absorption With Reaction

The following reactions occur when SO_2 is absorbed into the solutions and slurries studied in this research:

As previously mentioned, the $\text{Ca}(\text{OH})_2$ dissolution and CaSO_3 crystallization reactions which follow are also important for absorption of SO_2 into slurries:

As aqueous SO_2 is consumed by this series of reactions, the absorption of SO_2 is enhanced by increasing the driving force for absorption defined in equation (2-2). The degree to which liquid phase mass transfer is enhanced is quantified by Sherwood, et al. (1975) in terms of the enhancement factor, $\emptyset$. The enhancement factor is the ratio of the measured liquid phase mass transfer coefficient, k_l , and k_l° , the characteristic liquid phase mass transfer coefficient for the conditions that no chemical reactions occur. The k_l° for different experimental conditions is known based on the correlations developed later in Section 3. The value of $\emptyset$ can be determined experimentally from the following relationship:

$$N_{\text{SO}_2} = \emptyset k_l^\circ A ([\text{SO}_2]_i - [\text{SO}_2]_o) \quad (2-8)$$

where concentration of SO_2 in the bulk liquid phase, $[\text{SO}_2]_b$, is usually negligible. The absorption rate is known directly from gas phase material balance measurements, and $[\text{SO}_2]_i$ is known by applying the following expression of Henry's law to the known gas concentrations:

$$[\text{SO}_2]_i = H \times p_{\text{SO}_2,i} \quad (2-9)$$

2.1.3 Gas Film Resistance

The percent of gas film resistance reflects the degree to which gas film mass transfer dominates the absorption of SO_2 . When gas film mass transfer dominates the absorption, changes to the liquid phase composition resulting from the previously listed reactions cannot enhance mass transfer further. The transfer of SO_2 from the bulk gas phase to the surface of the liquid is the limiting or controlling mechanism. Experiments in very alkaline solutions, such as the experiments in 1.0 M NaOH described in Section 3, are 100 percent gas film controlled. Experiments in $\text{Ca}(\text{OH})_2$ slurries approach 100 percent gas film controlled absorption as the solids content of the slurry is increased. Gas film resistance is defined as:

$$\text{Gas Film Resistance (\%)} = \frac{p_{\text{SO}_2,o} - p_{\text{SO}_2,i}}{p_{\text{SO}_2,o}} \times 100 \quad (2-10)$$

As gas film resistance approaches 100 percent, the interface concentration of SO_2 becomes insignificant. In other words, the liquid phase is so reactive towards SO_2 that as soon as it is absorbed, it reacts immediately. Enhancement of the liquid phase absorption is thus infinite, and a liquid phase enhancement factor cannot be defined for a gas film controlled absorption. A totally gas film controlled absorption in $\text{Ca}(\text{OH})_2$ slurries represents a condition where no properties of the liquid, such as liquid phase mass transfer reactions, $\text{Ca}(\text{OH})_2$ dissolution, or CaSO_3 crystallization are affecting absorption. Ultimately, this would be the most desirable condition because the absorption rate is maximized.

Below is another way to define gas film resistance that shows its relationship to other important mass transfer properties:

$$\text{Gas Film Resistance (\%)} = \frac{1}{\left(\frac{k_g}{H k^o_l \phi} \right) + 1} \times 100 \quad (2-11)$$

In many cases, absorption of SO₂ into slurries can become gas film controlled. In these instances, no additives or improvements to the properties of the Ca(OH)₂ can improve absorption. The research focuses on determining conditions where the mass transfer is not gas film controlled, so that enhancement of absorption under these conditions might be improved by altering liquid phase characteristics. It was important, therefore, to monitor the degree of gas film resistance encountered during the slurry experiments.

2.2 ENHANCEMENT PREDICTED BY SURFACE RENEWAL THEORY

As found by Chang (1979), predicting the absorption rate of SO₂ is complicated by the fact that the absorption is an unsteady state process. Therefore a series of unsteady state material and charge balances must be solved to determine the concentration of constituents that influence absorption. Solutions to the unsteady state equations are made based on assumed boundary conditions. Boundary conditions for the equations are developed from one of a number of theories, as discussed in Section 1, which have been proposed to describe mass transfer across a fluid surface.

Chang (1979) applied the surface renewal theory to SO₂ absorption into different solutions which represented four different types of equilibrium reactions. Solutions of the unsteady state equations were made for these 4 cases and compared to film theory solutions for the same cases given by Olander (1960). By this comparison, Chang and Rochelle found that the surface renewal theories could be closely approximated by solving the simpler film theory and replacing the species diffusivities by their square roots.

A review of proposed mass transfer models for absorption in stirred tanks by Versteeg, et al. (1987) arrived at a similar conclusion. This study points out that most mass transfer models for gas/liquid absorption, such as those described above, are the same except for the dependence of the mass transfer coefficient on the diffusivity of the absorbed species. Additional review of liquid film mass

transfer coefficients by Bin (1984) supports this conclusion and goes further to study differences in the geometry of the stirred tank reactor designs and how these differences influence the liquid film mass transfer coefficient. Since the design of the stirred tank reactor used for this research is similar to that used by Chang, the mass transfer coefficient should be represented well by assuming a dependence on the square-root of the diffusivity of SO₂.

Solutions to the unsteady state surface renewal theory equations were developed by Chang and Rochelle and reported in terms of the enhancement factor for the absorption. The solutions were verified by several experiments (1980, 1981, 1982). However, the solutions were not used to predict absorption in Ca(OH)₂ slurries. Clear solution experiments were performed for this research to support experiments performed in slurries. The results of the clear solution experiments are compared in Section 4 to the enhancement factors which result from applying the equations developed by Chang and Rochelle that follow. The enhancement factors are then compared to enhancement predicted by the slurry absorption model, which is described further below, for model validation.

2.2.1 Enhancement in Water

The surface renewal theory solution for SO₂ absorption in water is based on the reaction represented by equation (2-3). The solution assumes that in an excess of water, H₂O is not included in the species balance and the bisulfite and hydrogen ions diffuse at the same rate. Thus, the reaction takes the form of A ⇌ 2 B and the approximate solution to the unsteady state equations takes the form:

$$\phi = 1 + \frac{\sqrt{D_{\text{HSO}_3^-}}}{\sqrt{D_{\text{SO}_2}}} \frac{\sqrt{K_o/4}}{\sqrt{[\text{SO}_2]_i} - \sqrt{[\text{SO}_2]_o}} \quad (2-12)$$

This relationship shows a linear dependence of ϕ on $1/\sqrt{[\text{SO}_2]_i}$ when $[\text{SO}_2]_o$ can be neglected. The proportionality constant is a function of the diffusivities of SO₂ and bisulfite, and the K_o is the concentration-based equilibrium constant of the reaction represented by equation (2-3).

In a solution of pure water, HSO_3^- formed by absorption and reaction of SO_2 must diffuse at the same rate as the H^+ ions that are formed by the reaction. This effect is referred to as ion-pairing and is a result of the condition of electrical neutrality that must exist within the solution. The diffusivities of HSO_3^- and H^+ must therefore be equal to an effective diffusivity as follows:

$$\frac{2}{D_{\text{eff}}} = \frac{1}{D_{\text{HSO}_3^-}} + \frac{1}{D_{\text{H}^+}} \quad (2-13)$$

Diffusivities of HSO_3^- and H^+ at 55 °C are calculated to be 2.54×10^{-5} and $1.78 \times 10^{-4} \text{ cm}^2/\text{s}$, respectively, from values reported at 25 °C by Chan and Rochelle (1981). The diffusivities were corrected for viscosity and temperature differences at 55 °C using the Stokes-Einstein Equation. The resulting effective diffusivity, D_{eff} , for both species is $4.45 \times 10^{-5} \text{ cm}^2/\text{s}$ based on equation (2-13). This effective diffusivity was used instead of $D_{\text{HSO}_3^-}$ in equation (2-12).

2.2.2 Enhancement in CaCl_2 Solution

For SO_2 absorption into a solution containing CaCl_2 , the bisulfite and hydrogen ions diffuse independently. Thus, the reaction takes the form of $\text{A} \rightleftharpoons \text{B} + \text{C}$ and the approximate solution to the unsteady state equations gives this relationship:

$$\phi = 1 + \frac{\sqrt{D_{\text{HSO}_3^-}}}{\sqrt{D_{\text{SO}_2}}} \frac{[\text{HSO}_3^-]_i - [\text{HSO}_3^-]_o}{[\text{SO}_2]_i - [\text{SO}_2]_o} \quad (2-14)$$

The bulk concentrations of aqueous SO_2 and bisulfite can be neglected in most cases. The interfacial bisulfite concentration, $[\text{HSO}_3^-]_i$, is determined from the equilibrium relationship of equation (2-3) as follows:

$$[\text{HSO}_3^-]_i = \frac{K_{c1} [\text{SO}_2]_i}{[\text{H}^+]_i} \quad (2-15)$$

The hydrogen ion concentration is determined by material and charge balances at the interface. Chang (1979) solved these expressions to arrive at:

$$[\text{HSO}_3^-]_i = \frac{[\text{HSO}_3^-]_o - R [\text{H}^+]_o + \sqrt{([\text{HSO}_3^-]_o - R [\text{H}^+]_o)^2 + 4RK_{a1}[\text{SO}_2]_i}}{2} \quad (2-16)$$

$$\text{where } R = \frac{\sqrt{D_{\text{H}^+}}}{\sqrt{D_{\text{HSO}_3^-}}}$$

Because $[\text{HSO}_3^-]_i$ depends on the square root of $[\text{SO}_2]_i$, this theory again shows a dependence of ϕ on $1/\sqrt{[\text{SO}_2]_i}$.

This differs from the expression for enhancement in water, equation (2-12), only because diffusion of HSO_3^- and H^+ are considered independently. Therefore, the additional enhancement observed in the experiments in CaCl_2 solutions is a result of Cl^- being present, allowing HSO_3^- and H^+ to diffuse independently. In other words, the reaction of SO_2 in the CaCl_2 solution is not inhibited by the ion-pairing effect.

2.2.3 Enhancement in Dilute $\text{Ca}(\text{OH})_2$ Solutions

Chang (1979) were also able to apply the surface renewal theory to absorption in solutions containing dissolved $\text{Ca}(\text{OH})_2$. Formation of sulfite is significant in $\text{Ca}(\text{OH})_2$ solutions. Therefore, the solution of the unsteady state equations has to be stated in its most general form for the reaction of $\text{A} + \text{B} \rightleftharpoons \text{C} + \text{D}$. This analysis showed that enhancement in $\text{Ca}(\text{OH})_2$ solutions can be expressed by the following relationship:

$$\phi = 1 + \frac{\sqrt{D_{\text{HSO}_3^-}}}{\sqrt{D_{\text{SO}_2}}} \left(\frac{[\text{HSO}_3^-]_i - [\text{HSO}_3^-]_o}{[\text{SO}_2]_i - [\text{SO}_2]_o} \right) + \frac{\sqrt{D_{\text{SO}_3^{2-}}}}{\sqrt{D_{\text{SO}_2}}} \left(\frac{[\text{SO}_3^{2-}]_i - [\text{SO}_3^{2-}]_o}{[\text{SO}_2]_i - [\text{SO}_2]_o} \right) \quad (2-17)$$

The alkaline solution reacts with aqueous SO_2 very quickly. Thus, reactions represented by equations (2-3) and (2-4) dominate the liquid phase. In all solutions containing $\text{Ca}(\text{OH})_2$ that were tested, $[\text{SO}_2]_o$ and $[\text{HSO}_3^-]_o$ were found to be insignificant. Virtually all of the sulfur species present in the bulk liquid phase were completely converted to sulfite.

The interfacial concentrations of sulfite and bisulfite are not known but are related to $[\text{H}^+]_i$ and $[\text{SO}_2]_i$ by the equilibrium relations for the reactions of equations (2-4) and (2-5). The expression for $[\text{HSO}_3^-]_i$ was shown in equation (2-15). The equilibrium expressions for $[\text{SO}_3^{2-}]_i$ and $[\text{OH}^-]_i$ are defined as follows:

$$[\text{SO}_3^{2-}]_i = \frac{K_{c1} K_{c2} [\text{SO}_2]_i}{[\text{H}^+]_i^2} \quad (2-18)$$

$$[\text{OH}^-]_i = \frac{K_w}{[\text{H}^+]_i} \quad (2-19)$$

When the appropriate bulk concentrations are neglected and the two equilibrium expressions are applied to equation (2-17), the equation for the enhancement factor becomes:

$$\phi = \frac{\sqrt{D_{\text{HSO}_3^-}}}{\sqrt{D_{\text{SO}_2}}} \frac{K_{c1}}{[\text{H}^+]_i} + \frac{\sqrt{D_{\text{SO}_3^{2-}}}}{\sqrt{D_{\text{SO}_2}}} \left(\frac{K_{c1} K_{c2}}{[\text{H}^+]_i^2} + [\text{SO}_3^{2-}]_o \right) \quad (2-20)$$

$[\text{H}^+]_i$ can be found by solving the following equation, which was derived by Chang and Rochelle from solution of surface renewal theory material balances for SO_2 and acidity:

$$\begin{aligned} \sqrt{D_{\text{H}^+}} [\text{H}^+]_i^3 + \left(\sqrt{D_{\text{HSO}_3^-}} [\text{HSO}_3^-]_o - \sqrt{D_{\text{H}^+}} [\text{H}^+]_o + 2\sqrt{D_{\text{SO}_3^{2-}}} [\text{SO}_3^{2-}]_o + \sqrt{D_{\text{OH}^-}} [\text{OH}^-]_o \right) \\ [\text{H}^+]_i^2 - \left(\sqrt{D_{\text{HSO}_3^-}} [\text{SO}_2]_i K_{c1} + \sqrt{D_{\text{OH}^-}} K_w \right) [\text{H}^+]_i - 2\sqrt{D_{\text{SO}_3^{2-}}} [\text{SO}_2]_i K_{c1} K_{c2} = 0 \end{aligned} \quad (2-21)$$

It was found that the last term in this expression was small relative to the other terms, so that $[\text{H}^+]_i$ could be solved directly by reducing the expression to quadratic form.

2.3 SLURRY ABSORPTION MODEL

The slurry absorption model was developed by Stromblad and Rochelle (1989) as part of this program. Experiments performed for this research are intended to verify the model and draw conclusions about factors which affect SO_2 absorption in $\text{Ca}(\text{OH})_2$ solutions and slurries. The results of experiments and the model are compared to predictions from the approximate solution of the surface renewal theory equations that were outlined above.

The slurry absorption model consists of 3 parts. The first part simulates absorption of SO_2 into the solution, which is enhanced by chemical reaction. The SO_2 absorption calculation is based on the penetration theory. The second part of the model includes dissolution of $\text{Ca}(\text{OH})_2$ solids in the solution based on the film theory. The third part consists of CaSO_3 crystallization calculated from a rate expression developed experimentally by Gleason and Rochelle (1987). The expressions developed in each of these 3 parts are coupled nonlinear differential equations which are solved numerically on the Cray X-MP at the University of Texas Center for High Performance Computing.

The approximate solutions to the surface renewal theory developed by Chang and Rochelle differ from the slurry absorption model in a few ways. First, the approximate solutions to the surface renewal theory calculate a time-averaged flux of SO_2 and do not solve the unsteady-state equations directly. The slurry absorption model provides a rigorous solution to the unsteady-state equations. Thus, in the approximate solutions developed by Chang and Rochelle, $p_{\text{SO}_2\text{i}}$ is assumed to be constant. The slurry absorption model allows for $p_{\text{SO}_2\text{i}}$ to vary with time.

Secondly, the approach used by Chang and Rochelle does not allow for the presence of a potential gradient to exist in the boundary layer of the solution. Although such a gradient might be small if it exists, the slurry absorption model allows for the presence of a small potential gradient due to the relative diffusion of charged species.

Lastly, there is a fundamental difference in the theories supporting the model and those in the approximate solutions of Chang and Rochelle. The slurry absorption model is based on the penetration theory, whereas the solutions of Chang and Rochelle are actually film theory solutions that approximate

the surface renewal theory. Chang and Rochelle documented that their modified film theory solutions approximated the surface renewal theory well in most cases. However, some conditions might exist in which differences in the theories might cause disparity in predicted SO_2 absorption.

The slurry absorption model has been run successfully to simulate the clear solution experiments performed in the reactor to verify the first part of the model. The model was also run for conditions which simulate the experiments performed in slurry solutions to verify the second part of the model. No experiments were run specifically to verify the third part of the model. Although the effects of CaSO_3 crystallization may be relatively less significant than the first two parts of the model, some experimental work should be done in the future to fine tune the model with respect to CaSO_3 crystallization.

2.3.1 Absorption With Reaction

The model uses the penetration theory to develop the boundary conditions necessary to solve the unsteady state differential mass balance equations for the absorption of SO_2 . Each element of liquid at the surface is exposed to the gas for the same length of time, which is defined as θ , the contact time. During its time at the surface, the liquid element is assumed to be stagnant.

The unsteady state material balances are included for total S(IV) species, calcium species, and chloride. A charge balance at the interface is made equal to zero by adjusting the level of chloride in the solution. Also, the fluxes of calcium and chloride are set equal to zero at the interface. Solution of the equations proceeds by recognizing that the absorption rate of SO_2 is equal to the sum of the S(IV) fluxes at the interface. This treatment of the unsteady-state equations allows for a small potential gradient to exist in the solution due to the relative differences in diffusion of charged species.

2.3.2 $\text{Ca}(\text{OH})_2$ Solids Dissolution

The unsteady state material balance for calcium requires that the rate of dissolution of $\text{Ca}(\text{OH})_2$ be known. To calculate the dissolution rate, the $\text{Ca}(\text{OH})_2$ particles are assumed to be spherical particles in an infinite stagnant solution. Also, the solution is assumed to be saturated with $\text{Ca}(\text{OH})_2$ at the surface of the particle. Simple differential mass balances are made for calcium, S(IV) species, and

for the charge balance. Although solution of these equations is straightforward, the rate of dissolution is complicated by the fact that the size of the particle decreases with time as it dissolves. Also, the dissolution rate depends upon the concentration of hydroxide ions in the solution, which is not uniform. Therefore, the dissolution rate of $\text{Ca}(\text{OH})_2$ varies with time and distance from the gas/liquid interface.

2.3.3 CaSO_3 Crystallization

At some point during the absorption, the concentration of CaSO_3 reaches a point of supersaturation where solid CaSO_3 begins to precipitate. Based on the work done by Gleason and Rochelle (1987), the rate of crystallization, R_c , was found to be represented by the following third order expression:

$$R_c = -k_c (RS_{\text{CaSO}_3} - 1)^3 \quad (2-22)$$

The constant, k_c , includes both a rate constant and the BET surface area per volume of the CaSO_3 crystals. This expression is also a function of both time and distance from the gas/liquid interface because RS_{CaSO_3} , the relative saturation, depends upon the concentration of CaSO_3 in solution which is nonuniform and time dependent.

2.3.4 Inputs to the Model

The operating conditions and solution compositions used in the stirred tank experiments had to be specified as inputs to the model. Table 2-1 lists the input variables for the clear solution experiments.

The temperature, contact time, and gas film coefficient, k_g , remained the same throughout most of the clear solution and slurry model runs. Contact time was varied on a few occasions to verify that it

TABLE 2-1. INPUT VARIABLES FOR THE SLURRY ABSORPTION MODEL
USED IN CLEAR SOLUTION TESTS

Operating Conditions	P_{SO_2} , K_g , contact time, temperature, pH
Solution Composition	Ca^{2+} , Mg^{2+} , Na^+ , K^+ , SO_3^{2-} , SO_4^{2-} , CO_3^{2-} , Cl^- , H_2O

does not have an appreciable effect on the absorption rate. Model runs for each solution composition were performed with the bulk gas phase SO_2 concentration, p_{SO_2} , set at 500, 1,000, 2,000, 3,000, 4,000 and 5,000 ppm. The pH and ion concentrations were set to values which represented the liquid phase at steady state in the stirred tank reactor.

The first step of the model calculation is to determine the concentrations and activity coefficients of important species, concentration based equilibrium constants, and the Henry's law constant. This is done by using the Bechtel Modified Radian Equilibrium Program, BMREQ (Epstein, 1975), with the specified solution composition, pH and temperature. Estimated diffusivities of important species used by the model are listed in Table 2-2. In general, values were obtained at 25 °C from Chan and Rochelle (1981) and corrected for the change in viscosity and temperature at 55 °C using the Stokes-Einstein relationship. Together, this information provides all the necessary input for the main program to perform the absorption calculations.

TABLE 2-2. ESTIMATED DIFFUSIVITIES OF IMPORTANT SPECIES USED BY THE SLURRY ABSORPTION MODEL ($\text{cm}^2/\text{s} \times 10^5$)

Species	25 °C	55 °C
H^+	9.31	17.8
OH^-	5.24	10.0
SO_2	2.00	3.83
HSO_3^-	1.33	2.54
SO_3^{-2}	0.96	1.84
Ca^{+2}	0.79	1.51
CaSO_3^0	0.53	1.01
CaOH^+	0.79	1.51
Cl^-	2.03	3.88

2.3.5 Model Output

The model provides several forms of output. Since the absorption rate is generally a function of the contact time, θ , the model lists the output for 10 periods of time over a specified range of θ . Therefore, each time the model is run, information is available for 10 incremental contact times. The most useful model output for the purposes of this study was the average absorption rate of SO_2 , N_{SO_2} . The model calculates an average absorption rate (as opposed to an instantaneous absorption rate) from the following equation, and reports the average N_{SO_2} at 10 contact times:

$$\overline{N_{\text{SO}_2}} = \frac{1}{\theta} \int_0^{\theta} N_{\text{SO}_2} dt \quad (2-23)$$

The average absorption rate at a specified contact time was measured in the stirred tank and reported in terms of the enhancement factor, ϕ . To compare the results from the stirred tank experiments to the absorption rate predicted by the model, the average N_{SO_2} computed as above by the model is also expressed in terms of the enhancement factor. To arrive at the value of the enhancement factor, the expression for liquid phase absorption, equation (2-8) is solved for ϕ using the average SO_2 absorption rate given by the model at the contact time of interest.

Also available are concentration profiles of the species listed in Table 2-2 as a function of distance from the interface as well as a function of the 10 incremental fractions of contact time. Because concentration profiles in the boundary layer could not be measured in the stirred tank, this information was not used directly for comparison to experimental data. Concentration profiles for several cases were generated by Stromblad and Rochelle (1989). The profiles were screened for their ability to represent expected behavior of chemical species concentrations in the boundary layer. The model also lists the gas phase concentration of SO_2 at the interface, Y_{SO_2i} , at a series of contact times.

Other useful output of the model is the penetration distance, which defines the liquid film thickness. The model specifies this as the distance from the gas/liquid interface to the point where the concentration of solid $\text{Ca}(\text{OH})_2$ particles is half of the concentration in the bulk liquid. The penetration

distance is also a measure of the amount of solid Ca(OH)_2 that has been consumed. Therefore, this definition only applies to slurries. The penetration distance is reported by the model for slurries at each of the 10 incremental contact times.

SECTION 3

EXPERIMENTAL

The purpose of the stirred tank reactor experiments is to simulate absorption of SO_2 across the gas/liquid interface of a droplet, into slurries of $\text{Ca}(\text{OH})_2$ with varied solution compositions. The reactor system is designed to provide a bulk gas phase with a known SO_2 concentration in contact with liquid solutions. The area of gas/liquid contact at the interface is known by maintaining a flat, undisturbed surface.

The reactor was designed to approximate the mass transfer properties that are common to slurry droplets. Measurements of the range of gas and liquid film mass transfer coefficients in the reactor were made. Mass transfer coefficients can be varied in the reactor by changing gas and liquid agitator speeds. The reactor is capable of providing a range of liquid film mass transfer coefficients corresponding to contact times from 0.7 to 6.6 s at 55 °C. The maximum gas film mass transfer coefficient available in the reactor was estimated to be one order of magnitude smaller than would be typical for a slurry droplet in the duct.

3.1 DESIGN OF REACTOR AND SUPPORTING EQUIPMENT

The stirred tank reactor and supporting equipment used to measure the absorption rate of SO_2 are pictured in Figure 3-1. This design was based on similar gas/liquid contact devices for which mass transfer properties have been determined by several previous investigators, including Chang and Rochelle (1979), Versteeg (1987), Sada (1981), Huasheng (1988) and Uchida (1978).

Figure 3-1. Stirred tank reactor and supporting equipment.

The reactor has a 4-in diameter and 6 1/2-in height. The total volume of the reactor is 1.275 L, of which 1.10 L is the maximum liquid volume. The gas/liquid contact area is 81 cm². The reactor vessel is a thick glass cylinder with 316 stainless steel metal plates sealed to the top and bottom by thick gasket clamps. Four 3/8-in wide, equally-spaced baffles of 316 stainless steel are welded to the base plate. The base plate also contains swagelok-fitted ports for liquid inlet and outlet. The top plate contains swagelok-fitted ports for the gas inlet and outlet and the thermocouple.

Heating tape was wrapped around the reactor and used with a temperature controller to maintain a constant temperature. Experiments were run at both 25 °C and 55 °C.

Gas was supplied to the reactor from a standard cylinder containing 1 percent SO₂ with a balance of helium. The flow rate of gas was measured using mass flow meters manufactured by Brooks Instrument Division of Emerson Electric Company. The models used were series 5850 E and C. Three sizes of mass flow meters were used, depending upon the range of flow rate of gas that was required for the experiment. These included flow meters with capacities of 1 L/min, 5 L/min, and 100 mL/min. The output of the mass flow meters was displayed in percent of full capacity on a Brooks model 5878 digital readout device. This device had multiple channels, allowing selection of the readout for up to 4 mass flow meters.

Gas was continuously removed from the reactor for SO₂ analysis using a Thermo Electron Model 40 source-level pulsed-fluorescent SO₂ analyzer. The range of the analyzer was typically set at the 0 to 1,000 ppm, or 0 to 5,000 ppm scale. The SO₂ concentration was read from a digital readout device on the PID controller, which accepted the analyzer signal as an input. Prior to entering the analyzer, water vapor was condensed in a chilled flask.

It was determined that dilution of the sample stream with air was necessary for 2 reasons. First, because the sample stream contained mostly helium, the analyzer pump had difficulty providing adequate sample flow because of the difference in density of the gas. Secondly, the amount of sample drawn from the reactor was less than the 2 L/min required by the analyzer. Although the analyzer was plumbed with a recirculation loop, the analyzer required a larger amount of sample than the reactor

provided. Dilution air was added at a 10:1 ratio to sample and was measured with mass flow meters of 20 L/min or 5 L/min capacity.

Liquid was generally fed continuously to the reactor, although some experiments were performed with liquid introduced in batch mode. The continuous flow system required a feed tank, a peristaltic pump and a waste collection bucket. A 10 gal mix tank with mounted agitator was added to the system for testing with slurries.

The pump had a capacity to deliver 205 mL/min. Two heads were installed on the pump to deliver and withdraw liquid at the same rate. This provided a relatively stable liquid level in the tank, although the level tended to drop a few millimeters over the course of a minute. A mark was made on the wall of the reactor 3/4 in below the top of the glass reactor vessel to indicate the level where experiments would be performed. The liquid level was monitored constantly and adjusted manually by pinching the liquid exit stream tubing. This maintained the level to within 1/8 in of the mark throughout the tests.

3.1.1 Agitation

An important feature of the reactor design is that the gas and liquid phases are stirred independently. Both liquid and gas phases had dedicated agitators with separate speed control mechanisms. Agitators were each set at the desired speed setting, and the speed was measured using a hand-held tachometer. This allowed for higher speed agitation of the gas phase relative to the liquid phase. The liquid phase agitation was strong enough, at speeds of approximately 1,100 rpm, to disturb the interface. Thus, experimental conditions were limited to liquid agitation speeds of less than 1,100 rpm.

Experiments required that gas agitation be maximized to maintain a high gas film mass transfer coefficient. Most experiments were performed at the maximum gas agitation speed of approximately 1,400 rpm. Another advantage of independent agitation was that the amount of agitation in the liquid could be changed while maintaining a constant gas agitation speed. Therefore, the liquid and gas film mass transfer coefficients could be varied independently in the reactor.

At the maximum agitation speed of 1450 rpm, the gas phase agitation was not strong enough to disturb the interface. Additional propeller designs were tested to discover if turbulence could be increased at the maximum speed. A 2.0-in diameter turbine-type propeller was chosen to improve turbulence. This propeller was designed to produce high shear and moderate pumping action. To improve gas film mass transfer further, the propeller was modified, increasing the blade lengths to 2.5-in diameter. A comparison of gas film mass transfer coefficients measured with each propeller is made later in this section. The various propellers used are shown in Figure 3-2.

Both the top and bottom plates of the reactor were originally fitted with Teflon O-ring seals for the agitator shafts. The liquid phase agitator was typically operated between 200 and 1100 rpm without disturbing the liquid surface. At these lower speeds, the O-ring seal was sufficient. O-rings required replacement after approximately 50 to 100 h of operation, depending upon agitation speeds of the tests performed. However, these seals were found to be inadequate for constant operation at higher speeds of 1,300 to 1,450 rpm required by the gas phase agitator. The upper plate of the reactor was redesigned with a mechanical (vacuum pump) shaft seal. Although more difficult to align, this shaft seal performed well throughout testing.

3.1.2 System Improvements

As experiments were performed, some changes to the original design were made to improve accuracy and functionality. Original design allowed only for manual control of the gas flow rate. One of the first improvements was the addition of a PID controller to monitor the analyzer SO_2 concentration output and automatically adjust the rate of gas flow to the reactor, a very useful adaption for the sets of experiments performed at a constant SO_2 level.

In initial measurements of the gas film mass transfer coefficient, there was suspicion that incomplete gas mixing was occurring as the gas entered the reactor, especially at high flow rates. Gas entered the reactor vertically, from the top plate and may have been impinging directly on the surface of the liquid without mixing with the bulk gas. This area of impingement would experience a higher gas

Original Gas
Phase Propeller

New Gas Phase
Propeller

Liquid Phase
Propeller

Figure 3-2. Propeller designs used in stirred tank reactor.

concentration and, therefore, enhanced mass transfer. In order to avoid such localized enhancement, a steel elbow was fit into the gas inlet to direct the incoming gas horizontally into the reactor.

The initial gas film coefficient tests were performed with continuous gas flow and liquid phase in batch mode. Changing from a batch system to a continuous flow system for the remainder of the experiments required a few more improvements. When running liquid through the system at the maximum flow rate of 205 mL/min, the heating tape alone could not maintain the 55 °C specified for most of the experiments. Therefore, a pre-heated water bath was also added to the liquid inlet line and provided adequate heating to the continuous liquid stream. The heating tape was then used only to fine tune the temperature and help insulate the glass walls.

3.1.3 Gas Phase Analysis and Material Balance

The SO₂ absorption rate was determined primarily by gas phase material balance. The material balance was based on supplying a known concentration of SO₂ to the reactor and measuring the reactor outlet (bulk) gas concentration. The bulk gas concentration was varied from 500 to 5,000 ppm SO₂ for experiments by varying the inlet gas flow rate. The inlet gas flow rate was measured and adjusted using a mass flow meter. Since inlet and outlet flow rates were approximately equivalent, the absorption rate was determined by the following relationship:

$$N_{SO_2} = (C_{SO_2in} - C_{SO_2out}) q_{out} \quad (3-1)$$

Several steps were taken to ensure that the gas phase material balance provided accurate measurement of N_{SO₂}. First, the system was checked frequently for leaks. This could be done easily at the beginning of tests because the reactor and tubing were always under a slight positive pressure during experiments and responded to testing with a soap solution. Also, the analyzer was calibrated each day before testing using the same flow meters, tubing, dilution system and ice bath set up but with just the reactor bypassed. Any leaks or contamination of the system were usually identified at this stage of the test.

Also, a cross-check of the accuracy of the gas phase material balance was made by directly analyzing the absorbed total $S(IV)_o$ in the liquid. Thus, the amount of absorbed $S(IV)_o$ could be calculated from the gas phase material balance and compared to the liquid phase sample analysis. Methods of liquid phase analysis are discussed further, later in this section.

The gas supply used in most experiments was a purchased, certified mixture of 1 mole percent SO_2 in helium. Helium was chosen as the balance of the gas mixture as a means of minimizing the gas film resistance because of its higher diffusivity. Using a theoretical equation to predict diffusivities in a binary gas mixture reported by Hirschfelder, Curtiss and Bird (1964), and the method prescribed by Sherwood (1975), the diffusivities of SO_2 in N_2 , and SO_2 in He were predicted. The value of D_{SO_2-He} is $2.07 \text{ cm}^2/\text{s}$ and of $D_{SO_2-N_2}$ is $0.60 \text{ cm}^2/\text{s}$.

Experiments performed by Versteeg (1987) verified that the dependence of the gas film coefficient, k_g , on the diffusivity of the absorbed species is proportional to $\sqrt{D}$ for a similar stirred vessel. This relationship shows that using helium should increase the mass transfer coefficient for SO_2 by a factor of 2 over using nitrogen. The experiments performed by Versteeg also indicate that the use of helium may allow operation at higher agitation speeds. In experiments where NH_3 in a balance of N_2 was used, rippling of the surface was noted at 600 rpm. With NH_3 in a balance of He, no surface disturbance was noticed at stirrer speeds of over 1,200 rpm. Operation at the higher agitation speeds could also increase k_g .

Use of helium caused some initial problems with gas analysis, however. Because the analyzer could read from 0 to 5,000 ppm SO_2 , a dilution system did not appear necessary. Initial measurements of the He/ SO_2 reactor outlet mixture were analyzed directly, without a dilution system.

Helium had 2 observable effects on the analyzer. First, since it has a lower density than air, the pumping capacity was much less. In order to operate the analyzer at the recommended pressure, the sample flow rate was greatly reduced. This increased the amount of time required for the analyzer to make a steady state measurement. Secondly, helium caused the analyzer to be much less sensitive to SO_2 . Span and zero adjustments were far from settings for air. Readings were being made in a

non-linear range, which made interpretation of the results more complicated. In addition, sensitivity toward SO_2 appeared to deteriorate over time. After several weeks of operation, problems with this system indicated that dilution system was necessary.

A dilution system was installed so that the analyzed sample would be mainly SO_2 in air. In experiments following this modification, the reactor outlet gas was diluted 10:1 to eliminate the effects of helium. Calibration was then made with mixtures of SO_2 in nitrogen. Calibration of the analyzer was performed before each test run. Generally, at least a 3-point check was made to ensure that the analyzer was linear and was not drifting, as had been noted in the earlier experiments using the undiluted helium/ SO_2 mixture. These changes resolved the analyzer drift problem and produced reliable SO_2 concentration data. Typically, SO_2 concentration could be read to ± 5 ppm.

Later, experiments were performed to verify that use of helium instead of nitrogen was actually increasing gas film mass transfer. The results of these experiments showed that no significant improvement in gas film mass transfer resulted from using helium. Although the diffusivity of SO_2 was increased due the lower molecular weight of helium, the lower density also caused less mixing action for a given agitation speed. This apparently had an equally important effect on the mass transfer coefficient.

3.1.4 Liquid Phase Analysis

During some of the tests, it was important to know the concentration of sulfur species in the liquid phase. Knowing these concentrations also provided a means of checking the accuracy of the gas phase material balance. Two types of liquid phase analyses were performed and direct titration with iodine and ion chromatography were used to determine total sulfur of liquid samples.

Samples of liquid taken from tests which measured liquid film coefficients contained SO_2 absorbed in HCl . These samples had to be analyzed immediately by direct iodine titration because of the tendency for SO_2 to be desorbed from the collected sample. A known concentration of iodine was placed in a beaker with starch solution and weighed. When the experiment reached a steady state, a

sample of the reactor effluent was pumped into the beaker until the clear endpoint was reached, and the net weight of reactor solution was recorded.

Samples collected during slurry tests were analyzed for total sulfur, mainly in the form of the bisulfite ion, HSO_3^- . These samples were oxidized using a 30 percent hydrogen peroxide solution to form sulfate, SO_4^{2-} . A 1-mL portion of each sample was withdrawn and diluted 100:1 for analysis by ion chromatography. The ion chromatograph used was a Dionex Corporation model 2000/SP. A Hewlett-Packard 3390A integrator was used to report the output peak heights and areas. The peak heights reported for samples were compared to peak heights of standards of known concentration to determine the sample concentration. The relationship of peak height to concentration was linear for the range used. Standards were made from NaSO_4 to provide SO_4^{2-} concentrations of 0.01 mM, 0.005 mM, and 0.001 mM. The standards and diluted samples were analyzed in random order to account for potential drift of the chromatograph.

3.2 MASS TRANSFER PROPERTIES OF THE STIRRED TANK REACTOR

The reactor has a characteristic gas film mass transfer coefficient, k_g , and liquid film mass transfer coefficient, k_l , which depend upon specific operating conditions. A series of initial experiments were performed to determine these mass transfer properties of the reactor, and relate them to variable operating conditions such as agitation speeds. The gas film mass transfer coefficient was determined by SO_2 absorption in 1 M NaOH. The liquid film mass transfer coefficient was determined by SO_2 absorption in 0.3 M HCl.

3.2.1 Gas Film Mass Transfer Properties

The amount of SO_2 absorbed by the liquid, N_{SO_2} , depends on a driving force for mass transfer between the bulk gas and liquid interface as described in equation (2-1). The k_g can be easily determined by measuring the absorption rate of SO_2 into a strong alkali solution that causes immediate removal of SO_2 at the interface. In strong alkaline solutions, SO_2 reacts instantaneously, causing p_{SO_2} to be insignificant.

In tests run to determine the gas film coefficient, the reactor was filled with 1.1 L of 1.0 M NaOH for reaction in batch mode. Batch mode was chosen simply for ease of operation. At this concentration, there was sufficient OH^- available to maintain a high enough pH to support the reactions listed as equations (2-3) through (2-5) to allow for several hours of operation. The key assumption in these experiments is that SO_2 reacts immediately with NaOH, resulting in a negligible SO_2 concentration at the interface.

Initial experiments used a continuous flow of helium containing 1 mole percent SO_2 . The gas phase was stirred first with the 2.0-in diameter propeller blade. Experiments were performed at room temperature, varying first the gas and liquid agitation speeds and then the SO_2 concentration. The k_g was then measured at the elevated temperature of 55 °C and also with a larger diameter propeller blade. Final measurements of k_g were made using nitrogen containing 1 percent SO_2 as a gas source but were not significantly different from initial measurements made with 1 percent SO_2 in helium.

3.2.1.1 Experimental Results

The following presents the values of k_g measured as a function of temperature, agitation and SO_2 concentration. Results showed that k_g was not a function of SO_2 concentration. It also did not vary measurably when changing the temperature from 25 °C to 55 °C. It was, however, strongly dependent on gas agitation speed. Although the k_g could also be affected by changes in the liquid level in the reactor (i.e., changes in gas volume), the liquid level/gas volume was maintained constant throughout all experiments.

Holding the inlet gas flow rate constant at approximately 1500 mL/min and the upper agitator speed at the maximum, the liquid phase agitation speed was varied between 200 and 1100 rpm. No change to the outlet SO_2 concentration resulted. As expected, varying the liquid agitation speed had no effect on the gas phase mass transfer coefficient.

Holding the liquid agitation speed constant at approximately 500 rpm and gas agitation at maximum, the k_g was measured at various outlet SO_2 concentrations. Under these conditions, theoretically, the gas phase mass transfer coefficient should not vary. However, the first 8

measurements taken indicated that k_g increased with each reading. This was caused by the analyzer drift problems previously discussed. Once this problem was solved and the air dilution system was adopted, new measurements of k_g were made. The results of these tests are shown in Figure 3-3. In these tests, the value of $k_g A$ was not dependent on SO_2 concentration, as also witnessed by Chang and Rochelle (1979, 1981) and Versteeg (1987). These results also show that k_g can be repeatedly measured to within ± 2.5 percent.

Next, the liquid agitator was held constant at approximately 500 rpm and the gas agitation speed was varied between 150 and 1400 rpm. Inlet gas flow rate was varied such that the outlet SO_2 concentration remained near 1,500 ppm.

Values of $k_g A$ calculated from these tests are plotted in Figure 3-4. As expected, higher agitation speeds result in much higher gas film mass transfer coefficients. A correlation for k_g and gas agitation speed was developed from these measurements for use in calculating k_g in later experiments. The correlation for the $k_g A$ using the 2.0-in diameter propeller was:

$$k_g A = 1.86 \times 10^{-4} (rpm)^{0.50} \quad (3-2)$$

The dependence of k_g on gas agitation speed is similar to that found by Versteeg (1987), who determined that k_g is proportional to $(rpm)^{0.63}$.

Also plotted in Figure 3-4 are values of $k_g A$ determined under the same conditions described above, except that the reactor was heated to 55 °C. The $k_g A$ does not appear to have a strong temperature dependence, especially at the higher agitation speeds. Chang and Rochelle (1979, 1981) also found this to be the case in experiments performed between 15 and 30 °C.

The fact that k_g exhibits little dependence on temperature can be explained by examining the properties it depends on. As determined by Versteeg (1987), k_g can be expressed empirically in dimensionless form in terms of the Reynolds number as:

$$Sh = \frac{k_g d_{st}}{D} = c_1 Re^{c_2} \quad (3-3)$$

Figure 3-3. Dependence of k_g on SO_2 concentration.

Figure 3-4. Dependence of k_g on gas agitation speed at 25 °C and 55 °C (2.0-in diameter propeller).

where c_1 and c_2 are constants. In Versteeg's work, c_2 generally ranged from 0.61 to 0.74 for systems of different gases using different stirrers. Using this correlation (assuming a constant stirrer diameter), k_g can be approximated by:

$$k_g = c_3 D Re^{2/3} \quad (3-4)$$

where:

$$Re = \frac{d_{st}^2 N \rho}{\mu} \quad (3-5)$$

The parameters that depend on temperature are D , ρ , and μ . Empirical equations that predict the temperature dependence of these parameters have been developed by several researchers and are compiled in the Chemical Engineer's Handbook (Perry and Chilton, 1973). For the diffusivity of gases, $D \propto T^{2/3}$. For ideal gases, $\rho \propto 1/T$. The viscosity of gases has a more complicated temperature dependence. This is given in Perry and Chilton (1973) as:

$$\mu = \frac{T^{2/3}}{T + 1.47 T_b} \quad (3-6)$$

Thus, the temperature dependence of the gas film coefficient becomes:

$$k_g \propto t^{2/3} \left(\frac{1}{T}\right)^{2/3} \left(\frac{T^{2/3}}{T + 1.47 T_b}\right)^{2/3} \quad (3-7)$$

The temperature dependence due to diffusivity and viscosity cancel each other, and the temperature dependence due to viscosity is weak. Thus, experiments showed no influence of temperature on k_g for a difference of 30 °C.

Since disturbance of the gas/liquid surface was not observed with the 2.0-in diameter propeller at maximum gas agitation speed, the reactor could benefit from greater agitation. This suggested the

attempt to increase agitation by increasing the diameter of the propeller to 2.5 in, the maximum which would fit in the reactor. Although the 2.5-in diameter impeller increased agitation and increased k_g , the point of surface disturbance was still not attained. Tests were run with this propeller under the same conditions as the 2.0-in diameter propeller. Results for tests run with this propeller at both 25 °C and 55 °C are shown in Figure 3-5. The correlation for $k_g A$ for the 2.5-in diameter propeller was:

$$k_g A = 4.95 \times 10^{-4} (\text{rpm})^{0.76} \quad (3-5)$$

Comparison of $k_g A$ measured with each propeller at 55 °C is shown in Figure 3-6. Because of the increased gas film mass transfer, the 2.5-in diameter propeller was used for the remaining experiments.

3.2.1.2 Discussion

A goal of this research was to design the reactor such that k_g is maximized, an important factor for several reasons. Most importantly, a low value of k_g results in absorption which becomes limited by gas film mass transfer. When gas film mass transfer is the limiting mechanism of absorption, changes to the liquid phase do not have an effect on absorption. This limiting condition represents 100 percent gas film resistance. The objective of these experiments was to study the behavior of SO_2 absorption due to changes to clear solution and slurry solution compositions. When the absorption is gas film controlled, study of these effects is not possible.

Also, it is preferred that the reactor have a k_g which approaches the range of values expected for slurry droplets. Values of k_g for slurry droplets are estimated to be in the range of 10^{-2} to 10^{-3} mole/cm² s bar. The maximum k_g measured for this study was on the order of 10^{-4} mole/cm² s bar.

The results obtained in these experiments are comparable to gas film coefficients derived by other authors, as shown in Table 3-1. The gas film mass transfer coefficients measured in this study are slightly greater than the values measured in other studies.

Figure 3-5. Dependence of k_g on gas agitation speed at 25 °C and 55 °C (2.5-in diameter propeller).

Figure 3-6. Comparison of k_g at 55 °C with two propeller sizes.

**TABLE 3-1. COMPARISON OF EXPERIMENTALLY DETERMINED
GAS FILM MASS TRANSFER COEFFICIENTS**

Previous Study	Temp (°C)	Gas Composition	Max rpm	$k_g \times 10^4$ (mole/cm ² s bar)
Sada (1978)	25	4 percent SO ₂ in N ₂	600	0.76
Chang & Rochelle (1979)	15 - 30	pure SO ₂ in N ₂	350	0.99
Weems & Rochelle (1981)	55	pure SO ₂ in N ₂	540	0.32
This study	25	1 percent SO ₂ in He	1365	1.55
This study	55	1 percent SO ₂ in He	1440	1.66

The higher k_g measured in this study was due primarily to the ability to stir the liquid and gas phases separately. Some improvement in k_g was also due to optimizing propeller design. Also, helium was used as the balance of the SO₂ gas mixture because of its lower density. This was originally expected to improve k_g as well, however measurement of k_g in a gas containing SO₂ in nitrogen showed no benefit of using helium instead of nitrogen. Overall, the design improvements resulted in an increase of about a factor of 2 in k_g . An order-of-magnitude increase in k_g was not feasible with this apparatus.

3.2.2 Liquid Film Mass Transfer Properties

A characteristic value of the liquid film mass transfer coefficient, k_l° , was determined at specific operating conditions in the reactor. Reactions, such as those listed as equations (2-3) through (2-5), greatly enhance liquid film mass transfer. To study the degree of enhancement due to reaction, the reactor's characteristic k_l° , measured in the absence of chemical reaction, must be known for the range of conditions studied. This k_l° can then be compared to k_l measured in solutions where reaction of SO₂ occurs to compute the enhancement factor. The value of k_l° is determined from equation (2-2).

Experimental conditions necessary for determining k°_l require that SO_2 be absorbed in a solution where negligible reaction in the liquid occurs. According to equations (2-3) through (2-5), a strongly acidic solution inhibits reaction. Weems and Rochelle (1981) found that a concentration of 0.3 M HCl or greater was sufficient to inhibit reaction. Therefore, experiments were performed in a solution of 0.3 M HCl to determine k°_l .

To calculate k°_l from equation (2-2), the concentrations of SO_2 at the interface, $[\text{SO}_2]_i$, and in the bulk phase, $[\text{SO}_2]_o$, must be known. The interface concentration was calculated using equation (2-1), Henry's law and the measured value of k_g . The bulk phase SO_2 concentration was maintained at a level low enough to be insignificant when compared to the interface concentration. Thus, a continuous flow of HCl solution through the reactor was necessary to prevent accumulation of SO_2 in the liquid phase.

This also helped to provide a large driving force for absorption. A liquid flow rate of 205 mL/min was found to be sufficient. Typically, the absorbed SO_2 concentration was 0.2 mM or less. The absorbed SO_2 concentration in the liquid was estimated using the gas phase material balance and liquid flow rate and then confirmed by the direct iodine titration method previously described.

3.2.2.1 Experimental Results

The following presents the values of k°_l measured as a function of temperature, agitation and SO_2 concentration. The k°_l should only be a function of the properties of the liquid phase. It should be completely independent of the properties of the gas phase, such as k_g and the SO_2 concentration. As a quality control check on the measurement of k°_l , a set of experiments were performed holding the liquid agitation speed constant at about 670 to 690 rpm and varying the SO_2 concentration between 1150 and 3070 ppm. The results shown in Figure 3-7 confirm that k°_l is not a function of SO_2 concentration. These results also indicate that k°_l can be measured repeatedly to within about ± 5 percent.

Figure 3-7. Dependence of k'_1 on SO_2 concentration at 25 °C.

Next, the relationship between k_i° and liquid agitation speed was determined at 25 °C. During this set of tests, the SO_2 concentration was allowed to vary between 1690 and 3070 ppm, and the liquid agitation speed was varied from 160 to 1350 rpm. Figure 3-8 shows the strong dependence of k_i° on liquid agitation speed. A correlation for k_i° as a function of liquid agitation speed was developed from this data for use in future experiments performed at 25 °C.

As found in the study by Chang (1979), the liquid film coefficient depends on temperature so it was measured at both 25 °C and 55 °C. Figure 3-8 also presents the values of k_i° measured at 55 °C as a function of liquid agitation speed. The increase in temperature from 25 °C to 55 °C results in a factor of 2 increase in k_i° . Another correlation for k_i° as a function of liquid agitation speed was developed from this data for use in future experiments performed at 55 °C. Results obtained by Versteeg (1987) showed roughly the same dependence of k_i° on agitation speed. In experiments performed at 20 °C and 30 °C, he reports that k_i° is proportional to $(\text{rpm})^{0.72}$.

According to the penetration theory, the value of k_i° determines the contact time, θ , (or surface renewal time) achieved in the vessel by the relationship (Treybal, 1980):

$$\theta = \frac{4 D_{\text{SO}_2}}{\pi k_i^{\circ 2}} \quad (3-9)$$

Contact times determined from k_i° data are plotted in Figure 3-9. The value of D_{SO_2} at 30 °C was taken from Peaceman (1951). To arrive at a value of D_{SO_2} at 55 °C, corrections for temperature and change in viscosity were made using the Stokes-Einstein relationship shown below (Bird, Stewart and Lightfoot, 1960):

$$D = \frac{k_B T}{6 \pi r_o \mu} \quad (3-10)$$

Figure 3-8. Dependence of k_l on liquid agitation speed at 25 °C and 55 °C.

Figure 3-9. Contact time as a function of liquid agitation speed.

When used to correct for temperature and viscosity, the relationship becomes:

$$\frac{D}{D_{25^{\circ}\text{C}}} = \frac{T \mu_{298}}{298 \mu} \quad (3-11)$$

Although lower mass transfer coefficients were found at 55 °C, contact time is not affected by a change in temperature. Since time and temperature are not intensive properties of the fluid, they are unrelated. Temperature dependence in k_l is mainly a function of the dependency of D_{SO_2} on temperature. As can be seen by the values reported above, D_{SO_2} is strongly dependent on temperature.

Preliminary tests were run with chemically inert solids present in the 0.3 M HCl solution to determine if there would be any significant physical effect on the liquid film mass transfer coefficient (i.e., changing fluid viscosity, surface renewal ability). The original test plan called for use of CaSO_4 solids, but a purified mixture of kaolinite and bentonite clay powder was used instead. These chemically inert solids were felt to be closer to the particle size and shape of $\text{Ca}(\text{OH})_2$ than CaSO_4 solids, which are large, round particles.

The tests with inert solids were performed at 55 °C, approximately 700 rpm liquid agitator speed and maximum gas agitation. Under these conditions, the correlation given in Figure 3-8 shows that k_l was 4.7×10^{-5} m/s with no solids in the solution. The test run under the same conditions with 3.0 wt percent solids in the solution measured a value of k_l that was not significantly different. For this test, k_l was 4.5×10^{-5} m/s. However, another test run under the same conditions with 8.0 wt percent solids in the solution measured a significantly lower value of k_l . In this case, k_l was 1.1×10^{-5} m/s.

Similar experiments were performed by Sada et al. (1977), where NO_2 was absorbed into $\text{Ca}(\text{OH})_2$ slurries at 25 °C. Concentrations of 0, 3, 5, 10 and 20 weight percent solids were prepared. The k_l was measured with liquid agitation speeds from 60 to 220 rpm and found to be unaffected by solids concentration at all levels. These results are also verified by the work performed by Quicker, et al., (1989). Their experiments involved absorption of CO_2 into slurries of inert particles. The absorption

rate was found to drop dramatically at concentrations of solids greater than 10 weight percent due to increase in viscosity and blockage of the interface.

The Ca(OH)_2 concentrations studied in this work ranged up to only 3 weight percent. One test was attempted at 7.3 weight percent, but enhancement could not be measured due to high gas film resistance. Based on the measurements made with the inert solids and Sada's previous findings, the correlations developed for k°_l are considered valid for use with the slurry solutions studied.

3.2.2.2 Discussion

Values of k°_l measured by other researchers with the conditions of their experiments and are listed in Table 3-2. In order to compare these values on an equivalent basis, the dimensionless quantities of the Sherwood number, Sh , and the Reynolds number, Re , are compared in Figure 3-10. The Reynolds number for the reactor was defined in equation (3-5). The Sherwood number is defined in terms of the liquid film properties of the reactor as follows:

$$Sh = \frac{k^\circ_l d_{st}}{D} \quad (3-12)$$

TABLE 3-2. COMPARISON OF EXPERIMENTALLY DETERMINED LIQUID FILM MASS TRANSFER COEFFICIENTS

Previous Study	Temp (°C)	Gas & Liquid Phases	Max rpm	$k^\circ_l \times 10^5$ (m/s)
Chang & Rochelle (1979)	25	pure SO_2 - HCl	300	1.62
Quicker, et al. (1989)	25	CO_2 - H_2O	120	0.47
Versteeg, et al. (1987)	20	CO_2 - H_2O	68	2.5
Versteeg, et al. (1987)	30	CO_2 - H_2	72	3.2
This study	25	1 percent SO_2 - HCl	1350	6.0
This study	55	1 percent SO_2 - HCl	1350	9.9

Figure 3-10. Comparison of k'_l measured in several studies as a function of liquid agitation speed.

Although the measured k_g values are of the same order-of-magnitude, they vary from one study to the next, probably due to the different geometry of the reactors and diffusivities of the gases. Most of the previous experiments were run at lower liquid agitation speeds and therefore did not produce very high values for k_g . Since contact times on the order of 1 s were preferred in this research, higher values for k_g were required, and liquid agitation speeds were greater.

3.3 COMPARISON OF MASS TRANSFER PROPERTIES OF THE STIRRED TANK TO THAT IN A SLURRY DROPLET

The mass transfer properties of the reactor determined in the tests discussed above can be compared to the properties of a slurry droplet to determine how closely the reactor simulates the mass transfer properties of a droplet.

The gas film mass transfer coefficient, k_g , can be defined in units of m/s as a function of the diameter of the droplet and the diffusivity of the species which is diffusing from the surrounding gas. The relationship was developed first by Harriot (1962) who applied the Ranz and Marshall Equation, below, to describe mass transfer into a droplet travelling at its terminal velocity, assuming this is equivalent to its slip velocity:

$$Sh = \frac{k_g d_{droplet}}{D} = 2 + 0.6 Re^{0.5} Sc^{0.33} \quad (3-13)$$

Based on studies by Jozewicz and Rochelle (1984) even very large droplets over 100 μm decelerate quickly to the gas velocity. Thus, according to the analysis made by Chan and Rochelle (1981), the droplet is assumed to be stagnant relative to the gas and $Sh = 2$ is a valid approximation.

Using this relationship, a slurry droplet of 10 μm would have a corresponding k_g of 1.1×10^{-2} moles/cm² s bar. A 100 μm droplet would have a k_g of 1.1×10^{-3} moles/cm² s bar. This covers the range of droplet sizes that would be found in common commercial sprays in dry scrubbing applications, based on the measurements made by Kinsey and Harriot (1988). The highest value of k_g measured in the stirred tank was 1.5×10^{-4} moles/cm² s bar. This corresponds to a slurry droplet diameter of

approximately 800 μm , which is much larger than would be considered typical of droplets in commercial use.

It is easy to understand from this relationship why the design of the reactor included steps to minimize gas film resistance (i.e., maximize k_g). Unfortunately, the attempts made to minimize gas film resistance did not produce the order-of-magnitude increase in k_g necessary to simulate a more reasonable droplet size ($<100 \mu\text{m}$).

The liquid film mass transfer coefficient, k_l° , is a function of the surface renewal time in the liquid. The penetration theory gives a relationship for the dependence of k_l° on the surface renewal or contact time as defined in equation (3-9). The amount of contact time in commercial slurry scrubbing applications is determined by the slurry droplet drying time. This is usually on the order of 1 s and depends on the operating temperature and humidity, droplet size, gas flow characteristics and size distribution of other droplets in the spray (Kinsey and Harriot, 1988). A contact time of 1 s is equivalent to a k_l° of $7.0 \times 10^{-5} \text{ m/s}$. For comparison, the range of k_l° values measured in the stirred tank at 55 °C was between 2.7×10^{-5} and $8.6 \times 10^{-5} \text{ m/s}$. This is equivalent to a range of contact times of 6.6 to 0.65 s.

These comparisons show that the stirred tank is capable of representing the gas film mass transfer properties associated with a very large droplet with a drying time typical of a smaller droplet. The ratio of the gas film mass transfer to the liquid film mass transfer in the stirred tank is a useful quantity and can also be used for comparison. A k_g/k_l° of up to 0.17 to 0.50 $\text{mole/m}^3 \text{ Pa}$ can be obtained in the stirred tank. Slurry droplets within the range of 10 to 100 μm with a 1 to 2 s drying time would give a range of k_g/k_l° from 1.6 to 22.3 $\text{mole/m}^3 \text{ Pa}$, based on the preceding analysis. Because of the low values of k_g available in the reactor, the ratio of mass transfer coefficients will be about an order-of-magnitude lower than expected for a slurry droplet.

SECTION 4

RESULTS OF EXPERIMENTS IN CLEAR SOLUTIONS

The slurry can be considered to be comprised of two parts: an aqueous, clear solution of Ca(OH)_2 including any added dissolved species and a uniformly dispersed phase of suspended solid Ca(OH)_2 particles. Reaction with absorbed SO_2 occurs entirely in the clear solution phase. It follows, then, that the conditions that will enhance SO_2 absorption in slurries can be determined, in part, by studying the effects they will have on the absorption of SO_2 into clear solutions.

Studying the clear solutions is also beneficial because mass transfer effects can be studied without some of the complications introduced by the addition of solids, such as Ca(OH)_2 . In addition, physical effects, such as increased viscosity, need not be considered. Eliminating effects of solid particles also allowed a clearer look at those effects occurring entirely as a result of changes to solution composition, such as the effect of ionic strength.

Experiments were designed to validate the first part of the slurry absorption model. For comparison, the slurry absorption model was run under conditions similar to those run in the stirred tank experiments. The surface renewal theory equations developed by Chang & Rochelle (1979) were solved for the same conditions as an additional basis of comparison. It was assumed that if the slurry absorption model adequately predicts measured absorption rate under the conditions in the stirred tank, that it is capable of predicting absorption under the conditions expected in a slurry droplet.

Initial clear solution tests establish a baseline for absorption of SO_2 into solutions containing no Ca(OH)_2 at all. Additional clear solution tests then measure the increase in SO_2 absorption due to increasing the amount of dissolved Ca(OH)_2 . Results of these tests are later compared to the

increased SO₂ absorption measured in the slurry tests of Section 5, where Ca(OH)₂ solids are added.

The slurry absorption model was run for each of these conditions.

4.1 EXPERIMENTAL CONDITIONS

During these tests SO₂ was absorbed into several different solutions at 55 °C. The gas phase was mixed at the maximum agitation speed of approximately 1,400 rpm, resulting in a gas phase mass transfer coefficient of 1.5×10^{-4} mole/s cm² bar. Solution compositions and other variables are listed in Table 4-1.

TABLE 4-1. CLEAR SOLUTION TEST CONDITIONS

Liquid Makeup	SO ₂ Concentration (ppm)	Liquid Agitation (rpm)	$k'_l \times 10^5$ (m/s)
Water	2,200 - 2,600	110 - 1,360	2.4 - 8.6
0.1 M CaCl ₂	1,000 - 4,970	76 - 1,330	2.2 - 8.4
2.5 mM Ca(OH) ₂ 0.1 M CaCl ₂	1,070 - 5,450	200 - 1,330	2.7 - 8.4
17 mM Ca(OH) ₂ 0.1 M CaCl ₂	580 - 3,790	230 - 1,360	2.9 - 8.6
17 mM Ca(OH) ₂	710 - 2,600	706 - 1,190	5.0 - 7.6
17 mM Ca(OH) ₂ 0.1 M NaCl	710 - 2,690	706 - 1,210	5.0 - 7.7

Reagents were prepared in a large 20 L plastic carboy which was stirred from the top manually until the reagents dissolved. An anhydrous laboratory grade 4-20 mesh CaCl₂ produced by Fisher Reagents was used. The Ca(OH)₂ was a fresh supply of MCB Reagents stock, opened on 7/11/89 for testing. The NaCl was a laboratory grade salt made by Fisher Reagents. Solutions were prepared by first dissolving the CaCl₂ or NaCl salt and then adding the specified amount of Ca(OH)₂.

Solutions containing 17 mM Ca(OH)₂ are assumed to be saturated with respect to Ca(OH)₂. The concentration of Ca(OH)₂ required to produce a saturated solution in 0.1 M CaCl₂ was measured by making a solution containing 0.1 M CaCl₂ in a 500 mL beaker, stirred, and heated to 55 °C. Excess Ca(OH)₂, corresponding to at least 30 mM, was added to the solution. The solution was then filtered,

and three 50 mL samples were titrated with 0.1 N standard HCl. The resulting concentrations of the saturated solutions were 16.9, 17.0 and 17.2 mM Ca(OH)_2 .

Measurements of Ca(OH)_2 solubility in water and salt solutions including CaCl_2 by Larsson (1931), Blix (1928) and Markarov (1954) show that addition of chloride salts increases the solubility of Ca(OH)_2 in water. However, adding a 0.1 M of these salts only results in approximately 1 percent increase in Ca(OH)_2 solubility. Therefore, the solutions containing 17 mM Ca(OH)_2 with no CaCl_2 and 0.1 M NaCl are essentially saturated to Ca(OH)_2 as well.

In the clear solution experiments, absorption of SO_2 is affected by the properties of the liquid phase constituents. Liquid phase mass transfer is enhanced by choosing constituents that favor the reaction of SO_2 as outlined in equations (2-3) through (2-5). The amount that liquid phase mass transfer is enhanced is quantified in terms of the enhancement factor, $\emptyset$, which is the ratio of the measured liquid phase mass transfer coefficient, k_l , and k_l° , the characteristic liquid phase mass transfer coefficient in the absence of chemical reactions for the conditions of the experiment. The k_l° for different conditions is known based on the correlations developed in Section 3.

The value of $\emptyset$ can be determined from the following relationship:

$$\emptyset = \frac{N_{\text{SO}_2}}{k_l^\circ A ([\text{SO}_2]_i - [\text{SO}_2]_o)} \quad (4-1)$$

This equation shows that $\emptyset$ is a normalized absorption rate or flux is equivalent to the absorption rate divided by the liquid film mass transfer coefficient and the driving force. The enhancement factor is important because it allows comparison of data obtained in the stirred tank reactor independent of the value of k_l° (or contact time) and the level of SO_2 maintained in the liquid phase reactor. Because the driving force and the contact time are constantly changed within the reactor, the absorption rate, N_{SO_2} , cannot usually be compared directly from one test run to another.

Calculating $\emptyset$ from equation (4-1) is simplified by knowing that in solutions containing Ca(OH)_2 , the concentration of SO_2 in the bulk phase, $[\text{SO}_2]_o$, is negligible due to the instantaneous reaction of

SO₂ forming sulfite and bisulfite. In clear solutions such as water and CaCl₂, the bulk concentration of SO₂ is significant. It is estimated by material balance and backed by direct measurement of total absorbed sulfur by ion chromatography, as described in Section 3.

The absorption rate, N_{SO_2} , was measured directly by gas phase material balance. The interface concentration, $[\text{SO}_2]_i$, was calculated using the Henry's law relationship given in equation (2-10). The gas phase concentration of SO₂ at the interface, $p_{\text{SO}_2,i}$, was determined by equation (2-1) and the relationship for k_g given in equation (3-8).

Buildup of sulfur species, especially the bisulfite ion, can affect the equilibrium of the reaction of SO₂ and water, equation (2-3). It was important to maintain a low concentration of sulfur species in the bulk liquid phase. A continuous flow of 205 mL/min solution through the reactor was maintained to prevent accumulation of bisulfite and other reacted sulfur species. This helped provide a large driving force for absorption. Results of the gas phase material balance and ion chromatography verified that the total sulfur concentration was typically 2 mM or less. This was adequate to allow the reaction of SO₂ to proceed without being inhibited greatly by buildup of sulfur species.

4.2 ENHANCEMENT IN WATER

Enhancement of SO₂ absorption in water was measured over a narrow range of SO₂ concentrations at varied liquid agitation speeds. The initial pH of the water was adjusted to 5.0 with a small amount of HCl so that absorption would not be biased by the presence of alkaline species in the water. These tests were designed to confirm that varying the liquid agitation, (i.e., k_l or contact time) does not have a significant effect on enhancement. The results are summarized in Table 4-2. The results confirmed that ϕ is independent of liquid agitation speed and, therefore, k_l , and contact time. ϕ can be measured in these solutions to approximately ± 5 percent.

The results show that for SO₂ concentrations between 2,200 and 2,450 ppm, the reaction of SO₂ with pure water enhanced SO₂ absorption by a factor of 3 over absorption of SO₂ into a non-reactive solution, such as the HCl solution used in experiments described in Section 3. Although the SO₂ absorption was enhanced, the gas film resistance associated with these experiments ranged

from only 2 to 7 percent. Referring to equation (2-10), this means that the interfacial concentration of SO_2 was quite high during these experiments. In other words, the absorption of SO_2 was primarily limited or controlled by the reaction occurring in the liquid phase.

TABLE 4-2. ENHANCEMENT OF SO_2 ABSORPTION IN WATER AT VARIOUS LIQUID AGITATION SPEEDS ($K_g = 1.51 \times 10^{-5}$ Mole/m² Pa s)

Test #	SO_2 Conc. (ppm)	Liq. Agitator Speed (rpm)	$k'_l \times 10^5$ (m/s)	Contact Time (s)	ϕ	Gas Film Res. (%)
CW1	2429	1363	8.5	0.66	3.2	7
CW2	2264	1042	6.8	1.1	3.2	6
CW3	2223	715	5.1	1.9	3.5	5
CW4	2431	332	3.3	4.5	3.4	3
CW5	2640	113	2.4	8.6	2.9	2

Enhancement of SO_2 absorption in water can be estimated by the surface renewal theory as proposed by Chang and Rochelle (1979). As found in Section 2, equation (2-12), the theory predicts a linear dependence of ϕ on $1/\sqrt{[\text{SO}_2]_i}$. The proportionality constant is a function of the diffusivities of SO_2 and HSO_3^- and the concentration-based equilibrium constant, K_c , of the reaction shown in equation (2-3).

In a solution of pure water, the diffusivity of HSO_3^- is altered by the ion-pairing effect described in Section 2. The HSO_3^- and H^+ ions formed by the reaction in equation (2-3) must diffuse within the boundary layer at the same rate to maintain electrical neutrality of the solution. Diffusivities of HSO_3^- and H^+ at 55 °C are 2.54×10^{-5} and 1.78×10^{-4} cm²/s, respectively. These diffusivities are based on values reported at 25 °C by Chan and Rochelle (1981) and corrected for viscosity and temperature changes at 55 °C using the Stokes-Einstein relationship in equation (3-11). The effective diffusivity for both species calculated using equation (2-13) is 4.45×10^{-5} cm²/s.

The slurry absorption model was run with bulk solution concentrations and other conditions that simulated the absorption experiments in water. The amount of total sulfur in the reactor liquid was

calculated to average about 0.5 mM by material balance. The bulk solution pH was determined initially by knowing that the H^+ concentration must be approximately equal to the HSO_3^- concentration as per equation (2-3). A charge balance performed by the slurry absorption model was checked to assure the correct solution composition.

The remainder of the component concentrations were determined by the Bechtel Modified Radian Equilibrium Program, BMREQ, Epstein (1975), which is used by the slurry absorption model. Table 4-3 summarizes the conditions and compositions used to simulate the solution in the stirred tank. Of the concentrations that are listed, only H^+ , HSO_3^- and SO_2 are appreciable. These are the same species which are included in the surface renewal theory solution in equation (2-12) (noting that the concentrations and diffusivities of H^+ and HSO_3^- are equivalent based on the ion-pairing assumption). The results from this model, the surface renewal theory prediction, and the measured results in the stirred tank reactor are shown together in Figure 4-1.

TABLE 4-3. CONDITIONS FOR SLURRY ABSORPTION MODEL
FOR ABSORPTION OF SO_2 IN WATER

Concentrations of Important Species (mM)	
H^+	0.515
OH^-	1.4×10^{-7}
SO_2	3.13×10^{-2}
HSO_3^-	0.469
SO_3^{-2}	4.1×10^{-5}
Cl^-	0.046
Other Conditions	
Temperature	55 °C
pH	3.3
k_g	1.44×10^{-5} mole/Pa m ² sec
Contact Time	0.0075 to 7.53 s
P_{SO_2}	500 to 4,000 ppm

Figure 4-1. Enhancement of SO₂ absorption in water.

The slurry absorption model predicts enhancement that is greater than the enhancement predicted by the surface renewal theory by about 0.5 for the range of SO_2 concentrations studied. The enhancement measured in the stirred tank reactor experiments falls in between the predictions of the surface renewal and the slurry absorption models. The measured values do not distinguish which of the two models best predicts the observed absorption because of the degree of inaccuracy associated with the measurements.

4.3 ENHANCEMENT IN 0.1 M CaCl_2 SOLUTION

Chloride is a common constituent found in slurry solutions used in commercial scrubbing. Calcium chloride was added to some of the clear solutions described later in this chapter, and to all slurries studied in experiments described in Section 5. CaCl_2 does not have an active role in the SO_2 absorption reactions shown in equations (2-3) through (2-5). However, adding an excess amount of this electrolyte causes the solution to maintain a constant ionic strength that might otherwise be changing as reaction of Ca(OH)_2 with SO_2 takes place.

The effect that calcium chloride has on SO_2 absorption was studied first by absorbing SO_2 into a solution containing 0.1 M CaCl_2 . Absorption in this solution differs from absorption in water because the ionic strength is altered. By adding CaCl_2 , the ion-pairing effect is no longer a requirement for electrical neutrality, so H^+ and HSO_3^- species can diffuse independently.

Experiments in 0.1 M CaCl_2 solutions were designed to measure enhancement at several SO_2 concentrations. Also, experiments were run at similar SO_2 concentrations with varied liquid agitation speeds to confirm that changing speeds has a negligible effect on absorption of SO_2 . Again, the initial pH was adjusted to 5.0 with a small amount of HCl.

Table 4-4 shows the results of tests run at similar SO_2 concentrations of around 4400 ppm. The results of the first 4 tests show that enhancement can be measured repeatedly to within ± 5 percent. The SO_2 concentration was a bit higher during the following 2 tests, which was significant enough to cause a drop in enhancement.

TABLE 4-4. ENHANCEMENT OF SO₂ ABSORPTION IN 0.1 M CaCl₂ AT VARIOUS LIQUID AGITATION SPEEDS
($k_g = 1.45 \times 10^{-5}$ mole/m² Pa s)

Test #	SO ₂ Conc. (ppm)	Liq. Agitator Speed (rpm)	$k_l \times 10^5$ (m/s)	Contact Time (s)	ϕ	Gas Film Res. (%)
CC1	4460	1330	8.4	4.5	3.7	9
CC2	4300	1019	6.7	7.2	3.9	7
CC3	4440	679	4.9	13.2	3.9	6
CC4	4620	412	3.7	23.8	3.6	4
CC5	4880	236	2.9	38.1	3.2	3
CC6	4970	76	2.2	64.0	2.9	2

TABLE 4-5. ENHANCEMENT OF SO₂ ABSORPTION IN 0.1 M CaCl₂ AT VARIOUS SO₂ CONCENTRATIONS
($k_g = 1.45 \times 10^{-5}$ mole/m² Pa s, $k_l = 4.9 \times 10^{-5}$ m/s)

Test #	SO ₂ Conc. (ppm)	Liq. Agitator Speed (rpm)	ϕ	Gas Film Resistance (%)
CC3	4,440	679	3.9	6
CC7	2,490	674	4.2	6
CC8	1,000	674	6.0	8
CC9	1,990	674	4.8	7

Table 4-5 reports the effect of SO₂ concentration on enhancement. The enhancement factor ranged between about 4 at the high SO₂ concentrations near 4,400 ppm, to 6 at the low SO₂ concentration of 1,000 ppm. At an SO₂ concentration of 2,500 ppm, enhancement was improved about 30 percent over enhancement measured in water.

The gas film resistance is reported in both Tables 4-4 and 4-5. Gas film resistance for the tests in 0.1 M CaCl₂ solutions is slightly higher than for the tests in water. As indicated by equation (2-11) gas film resistance increases as either k_l and/or ϕ increases.

The enhancement factor in CaCl₂ solutions can be estimated by the surface renewal theory developed by Chang and Rochelle (1979). The solution for the enhancement factor shown in equations

absorption in water, absorption depends on the concentrations and diffusivities of SO_2 , HSO_3^- , H^+ and the equilibrium constant, K_a , of the reaction shown in equation (2-3).

Absorption of SO_2 in CaCl_2 solutions differs from that in water only because Cl^- is present, allowing HSO_3^- and H^+ to diffuse independently. In other words, the reaction of SO_2 in the CaCl_2 solution is not inhibited by the ion-pairing effect.

The slurry absorption model was run with bulk solution concentrations and other conditions that simulated the absorption experiments in 0.1 M CaCl_2 under steady state conditions. Again, the bulk solution pH was estimated by knowing that the H^+ concentration must be approximately equal to the HSO_3^- concentration as per equation (2-3). The pH was then adjusted until the charge balance of ionic species was satisfied. The remaining component concentrations were determined by BMREQ.

The amount of total sulfur in the bulk liquid during experiments was calculated to range between 0.4 and 2.0 mM by material balance. Two solution compositions were determined for running the slurry absorption model. The first has a low value of 0.5 mM S(IV)_0 . The second has a value of 0.8 mM S(IV)_0 , which was the average for the conditions in the stirred tank. Table 4-6 summarizes the conditions and compositions that were used in the slurry absorption model to simulate the solution in the stirred tank.

Two solutions for the surface renewal theory were calculated as well, based on the equilibrium concentrations calculated by BMREQ for these 2 cases. Enhancement predicted by the slurry absorption model, the surface renewal theory, and the measured results in the stirred tank reactor are shown together in Figure 4-2.

TABLE 4-6. CONDITIONS FOR SLURRY ABSORPTION MODEL FOR ABSORPTION OF SO₂
IN 0.1 M CaCl₂

Concentrations of Important Species (mM)		
	Case 1	Case 2
H ⁺	0.843	0.497
OH ⁻	1.35 x 10 ⁻⁷	2.28 x 10 ⁻⁷
SO ₂	4.75 x 10 ⁻²	1.79 x 10 ⁻²
HSO ₃ ⁻	0.750	0.479
SO ₃ ⁻²	1.32 x 10 ⁻⁴	1.43 x 10 ⁻⁴
Ca ⁺²	100	100
CaSO ₃ ⁰	2.56 x 10 ⁻³	2.78 x 10 ⁻³
CaOH ⁺	9.97 x 10 ⁻⁸	1.69 x 10 ⁻⁷
Cl ⁻	200	200
Other Conditions		
	Case 1	Case 2
Temperature (°C)	55	55
pH	3.15	3.38
k _g (mole/Pa m ² s)	1.44 x 10 ⁻⁵	1.44 x 10 ⁻⁵
Contact Time (s)	.0075 to 7.53	.0075 to 7.53
pSO ₂ (ppm)	500 to 5,000	500 to 2,000

Both the slurry absorption model and the surface renewal theory using the BMREQ concentrations and diffusivities predict that enhancement is reduced when larger amounts of sulfur species, mostly SO₂ and HSO₃⁻, are present in the liquid phase. The reduction in enhancement is more pronounced at the lower SO₂ concentrations (i.e., higher values of 1/√[SO₂]). The slurry absorption model predicts a greater reduction in enhancement due to the increase in absorbed sulfur species than does the surface renewal theory. At high SO₂ concentrations, the models compare relatively well to one another, and the amount of absorbed sulfur species has little effect on enhancement.

Figure 4-2. Enhancement of SO₂ absorption in 0.1 M CaCl₂ solution.

The results measured in the stirred tank correlate best with the lower enhancement predicted by the slurry absorption model. During the stirred tank experiments, the $S(IV)_o$ concentrations varied depending upon the degree of absorption occurring. Table 4-7 lists results of experiments at various SO_2 concentrations including the estimated amount of absorbed sulfur species in the liquid. Generally, within the stirred tank, as SO_2 concentration increases the amount of sulfur species in the bulk liquid increases as well.

4.4 ENHANCEMENT IN 2.5 mM $Ca(OH)_2$ SOLUTION CONTAINING 0.1 M $CaCl_2$

The clear $Ca(OH)_2$ solutions containing 0.1 M $CaCl_2$ is more representative of the liquid composition and the chemical properties of slurry solutions than water. The first set of tests was run at a $Ca(OH)_2$ level of 2.5 mM. These experiments were aimed at measuring the enhancement factor over a range of SO_2 concentrations.

Two sets of experiments were performed with 2.5 mM $Ca(OH)_2$ /0.1 M $CaCl_2$ solutions. The first set of experiments was performed on 7/11/89. Another set of experiments was performed several months later, 9/12/89, after some minor replumbing and recalibration of flow meters during slurry testing. The objective of the second set of tests was to check the reproducibility of the results and obtain measurements over a wider range of $[SO_2]_i$ levels. The results of these 2 sets of experiments are summarized in Table 4-8. The reported total sulfur content of the liquid, $[S(IV)]_o$, was calculated by material balance.

TABLE 4-7. PRESENCE OF ABSORBED SULFUR SPECIES IN 0.1 M $CaCl_2$ SOLUTIONS AT VARIOUS SO_2 CONCENTRATIONS

Test #	Bulk Gas SO_2 Conc. (ppm)	$[SO_2]_i$ (mM)	$S(IV)_o$ Conc. (mM)
CC3	4,440	2.06	1.23
CC7	2,490	1.15	0.72
CC8	1,000	0.45	0.41
CC9	1,990	0.92	0.66

TABLE 4-8. ENHANCEMENT OF SO₂ ABSORPTION IN 2.5 mM Ca(OH)₂
WITH 0.1 M CaCl₂
($k_g = 1.44 \times 10^{-5}$ mole/m² Pa s)

Test #	SO ₂ Conc. (ppm)	$k_l \times 10^5$ (m/s)	Contact Time (s)	ϕ	[S(IV)] _o (mM)	Gas Film Res. (%)
7/11/89 ($k_g = 1.44 \times 10^{-5}$ mole/m ² Pa s)						
CD1	4,000	8.4	0.70	5.9	1.8	13
CD2	3,850	6.5	1.1	8.6	2.0	15
CD3	4,270	4.9	2.0	8.5	1.7	11
CD4	4,680	3.6	3.7	5.4	0.9	6
CD5	2,760	3.6	3.7	7.1	0.7	7
CD6	1,490	3.6	3.7	10.0	0.5	10
CD7	2,260	2.7	6.6	11.6	0.7	9
9/12/89 ($k_g = 1.42 \times 10^{-5}$ mole/m ² Pa s)						
CD8	3,600	7.4	0.90	9.7	2.2	19
CD9	2,890	7.4	0.90	10.2	1.9	19
CD10	2,111	7.4	0.90	10.4	1.4	19
CD11	1,070	7.4	0.90	18.9	1.1	30
CD12	1,210	6.5	1.2	17.7	1.1	26
CD13	2,170	6.5	1.2	11.3	1.4	19
CD14	3,110	6.5	1.2	10.2	1.8	17
CD15	5,450	6.5	1.2	5.9	2.0	11
CD16	3,730	4.9	2.0	9.7	1.7	13
CD17	3,140	4.9	2.0	8.3	1.2	11

Overall, the SO₂ concentrations studied ranged from 1,070 to 5,450 ppm. Enhancement factors measured during these tests ranged from about 5, at high SO₂ concentrations, to 19 at the lowest SO₂ concentrations. Gas film resistance increased considerably over levels measured in water and CaCl₂ solutions, ranging from about 10 percent at the high SO₂ concentrations to 30 percent at the lowest SO₂ concentration.

Chang and Rochelle (1979) were also able to apply the surface renewal theory to absorption in solutions containing dissolved Ca(OH)₂. Enhancement, as given by equations (2-20) and (2-21), is a

function of additional species. Of course, the absorption depends heavily on the bulk concentration of OH^- . Also, at the higher pH, HSO_3^- reacts to form SO_3^{2-} , which reaches significant levels.

The slurry absorption model was run with bulk solution concentrations and other conditions that simulated the absorption experiments with the 2.5 mM $\text{Ca}(\text{OH})_2$ /0.1 M CaCl_2 solution. Since the addition of $\text{Ca}(\text{OH})_2$ made the solution very alkaline, the bulk solution pH was determined by estimating the OH^- concentration. The initial amount of OH^- added to the feed was 5.0 mM. However, the net result of equations (2-3) through (2-5) requires that for every mole of SO_3^{2-} formed, two moles of OH^- are consumed.

The amount of total sulfur in the reactor liquid was calculated to range between 0.5 and 2.2 mM by material balance. A typical value of 0.85 mM was chosen as the total S(IV) concentration for modeling purposes. Under these alkaline conditions, almost all of the absorbed S(IV) is reacted to SO_3^{2-} . Therefore under steady state conditions, the OH^- concentration is 3.3 mM. As a first approximation, the pH was chosen such that the OH^- and CaOH^+ concentrations summed close to 3.3 mM. The pH was then fine-tuned to ensure a proper charge balance.

The remainder of the component concentrations were determined by BMREQ, which is called by the slurry absorption model. Table 4-9 summarizes the conditions and compositions used to simulate the solution in the stirred tank. As shown in the table, bulk concentrations of H^+ , HSO_3^- and SO_2 are no longer important species as they were in the solutions with lower pH previously studied. Instead, important bulk species are OH^- , SO_3^{2-} , CaSO_3^0 and CaOH^+ . Note that the surface renewal theory solution does not consider the presence of the CaOH^+ and CaSO_3^0 ion pairs.

The results of the slurry absorption model are plotted along with enhancement estimated by the surface renewal theory, and enhancement measured in the stirred tank reactor in Figure 4-3. The experimental data appear to be described relatively well by both the surface renewal theory and the slurry absorption model over the range of SO_2 concentrations studied. Again, the two models differ slightly. The slurry absorption model predicts the experimentally measured enhancement more accurately at the lower SO_2 concentrations (i.e., the higher values of $1/[\text{SO}_2]_i$).

TABLE 4-9. CONDITIONS FOR SLURRY ABSORPTION MODEL FOR ABSORPTION OF SO₂ IN 2.5 mM Ca(OH)₂ WITH 0.1 M CaCl₂

Concentrations of Important Species (mM)	
H ⁺	5.97 x 10 ⁻⁸
OH ⁻	1.90
SO ₂	negligible
HSO ₃ ⁻	1.72 x 10 ⁻⁵
SO ₃ ⁻²	4.3 x 10 ⁻²
Ca ⁺²	100.3
CaSO ₃ ⁰	0.83
CaOH ⁺	1.41
Cl ⁻	199.9
Other Conditions	
Temperature	55 °C
pH	10.30
k _g	1.44 x 10 ⁻⁵ mole/Pa m ² s
Contact Time	0.01 to 10 s
P _{SO2}	500 to 5,000 ppm

One unknown factor which could have influenced absorption measured in the stirred tank was how much of the CaSO₃⁰ precipitated during the individual runs. The slurry absorption model was run under the assumption that the solution was saturated to CaSO₃. According to the BMREQ data from the slurry absorption model conditions, of the 1.0 mM S(IV)₀ assumed to be present, 0.95 mM was present as CaSO₃⁰ under saturated conditions. This means that the model assumed that a small amount of CaSO₃ had precipitated.

Of the solutions studied, most had S(IV)₀ concentrations estimated to be above 1.0 mM. The few measurements taken during the first set of tests which measured low absorption also had low absorbed S(IV)₀ concentrations. These solutions were probably not saturated with CaSO₃, which may account for the poor agreement with the absorption predicted by the model. The amount of total absorbed sulfur determined by material balance, S(IV)₀, was given in Table 4-8.

Figure 4-3. Enhancement of SO_2 absorption in 2.5 mM $Ca(OH)_2$ /0.1 M $CaCl_2$ solution.

Solutions with greater than 1.0 mM $S(IV)_o$ either reached a supersaturated concentration of $CaSO_3^o$ at steady state or had precipitated $CaSO_3$ solids during the experiment. During some of the experiments, it was noted that the bulk solution became cloudy, and during experiments where the absorption rate was greatest (i.e., high bulk gas SO_2 concentrations) some small, round platelets were found in the bulk solution. The bulk solutions of most of the experiments run were therefore known to be merely saturated with $CaSO_3$ and not supersaturated.

It was expected that conditions of saturation versus supersaturation of $CaSO_3$ in the boundary layer of the solution could have influenced absorption of SO_2 . Since it was not possible to monitor such conditions, the actual condition of $CaSO_3$ in the boundary layer is not known. Because the absorption of SO_2 measured in the stirred tank agreed well with the model and theory, whatever influence these conditions may have had was not significant enough to affect the measured absorption. Such behavior should only be of concern in describing the absorption of SO_2 in dilute solutions of $Ca(OH)_2$. In slurries and solutions saturated with $Ca(OH)_2$, precipitation of $CaSO_3$ will surely occur. The bulk liquid (and probably the boundary layer as well) will always be saturated with $CaSO_3$ in $Ca(OH)_2$ slurries studied.

4.5 ENHANCEMENT IN 17 mM $Ca(OH)_2$ SOLUTION CONTAINING 0.1 M $CaCl_2$

Another set of tests was run with $Ca(OH)_2$ at 17 mM, the saturation level in 0.1 M $CaCl_2$. This set of conditions is particularly interesting because it represents the same conditions as those in the dissolved portion of a $Ca(OH)_2$ slurry. The only difference between it and a $Ca(OH)_2$ slurry is the ability of the slurry to regenerate the reacted $Ca(OH)_2$ with dissolution of solid lime. Again, experiments were run on two occasions. A summary of results are presented in Table 4-10.

The SO_2 concentrations studied during experiments with the 17 mM $Ca(OH)_2$ solution ranged from 580 to 3,790 ppm. The test conducted at the lowest SO_2 concentration resulted in absorption that was too gas film controlled to accurately determine the enhancement. Gas film resistance for the test runs varied from 12 percent to 83 percent. The enhancement factor measured during these tests

TABLE 4-10. ENHANCEMENT OF SO₂ ABSORPTION IN 17 mM Ca(OH)₂ WITH 0.1 M CaCl₂

Test #	SO ₂ Conc. (ppm)	k ₁ × 10 ⁵ (m/s) Contact Time (s)	[S(IV)] ₀ (mM)	Ø	Gas Film Res. (%)	
7/11/89 (k _g = 1.44 × 10 ⁻⁵ mole/m ² Pa s)						
CS1	2895	8.6	0.66	15	2.8	28
CS2	3181	7.0	1.00	15	2.7	24
CS3	2359	5.0	1.92	32	2.7	33
CS4	2287	3.6	3.77	25	1.7	22
CS5	1179	3.6	3.77	40	1.3	31
CS6	3570	3.6	3.77	19	2.1	17
CS7	2172	2.9	5.88	15	0.9	12
9/19/89 (k _g = 1.42 × 10 ⁻⁵ mole/m ² Pa s)						
CS8	2496	7.3	0.92	35	3.8	44
CS9	1271	7.3	0.92	99	3.0	69
CS10	582	7.3	0.92	--	1.6	83
CS11	952	6.4	1.19	133	2.4	72
CS12	2301	6.4	1.19	36	3.3	42
CS13	2841	6.0	1.35	25	3.1	31
CS14	3521	6.0	1.35	24	3.8	31
CS15	3044	6.0	1.35	21	3.0	29
CS16	3793	6.0	1.35	21	3.6	28
CS17	1051	6.0	1.35	42	1.6	44
CS18	1274	5.1	1.88	69	2.3	52
CS19	3342	5.1	1.88	21	2.8	25

ranged from about 13 at the high SO₂ concentrations to 133 at the lowest SO₂ concentration that could be evaluated.

The slurry absorption model was run with bulk solution concentrations and other conditions that simulated a solution containing 17 mM Ca(OH)₂ in 0.1 M CaCl₂. The bulk solution pH was determined by estimating the OH⁻ concentration as described previously for the dilute Ca(OH)₂ solution. An initial

pH of 11.3 was chosen such that the OH^- and CaOH^+ concentrations summed close to 34 mM. The pH was then fine tuned to achieve the proper charge balance. The amount of total sulfur in the reactor liquid was calculated to range between 0.9 and 3.8 mM by material balance. A typical value of 2.0 mM was chosen as the total S(IV) concentration for modeling purposes.

The remainder of the component concentrations were determined by BMREQ. The solution was assumed to be saturated with CaSO_3 since the calcium sulfite precipitated during all of the experiments. Again, important bulk species are OH^- , SO_3^{2-} , CaSO_3^0 and CaOH^+ . Table 4-11 summarizes the conditions and compositions used to simulate the 17 mM Ca(OH)_2 solution in the stirred tank. Because of our error in computer input, the calculations were done for 18 mM Ca(OH)_2 .

TABLE 4-11. CONDITIONS FOR SLURRY ABSORPTION MODEL FOR ABSORPTION OF SO_2 IN 18 mM Ca(OH)_2 WITH 0.1 M CaCl_2

Concentrations of Important Species (mM)	
H^+	5.76×10^{-8}
OH^-	19.6
SO_2	negligible
HSO_3^-	1.67×10^{-5}
SO_3^{2-}	4.34×10^{-2}
Ca^{+2}	102.5
CaSO_3^0	0.82
CaOH^+	14.7
Cl^-	200.0
Other Conditions	
Temperature	55 °C
pH	11.313
k_g	1.44×10^{-5} mole/Pa m^2 s
Contact Time	0.01 to 10.0 s
P_{SO_2}	1,000 to 4,000 ppm

As previously mentioned, Chang and Rochelle (1979) used the surface renewal theory to predict the enhancement factor in $\text{Ca}(\text{OH})_2$ solutions. Using equations (2-20) and (2-21) with bulk species concentrations given by BMREQ, enhancement for SO_2 absorption in 17 mM $\text{Ca}(\text{OH})_2$ solution was estimated. The results of the slurry absorption model are plotted with enhancement estimated by the surface renewal theory, and enhancement measured in the stirred tank reactor shown in Figure 4-4.

The predicted enhancement at contact times of 0.9 and 2.5 s is shown in Figure 4-4. Notice that enhancement does not appear to be a function of contact time for the conditions studied. However, the slurry absorption model predicted over twice the enhancement measured in the stirred tank. The surface renewal theory also predicted much greater enhancement than that measured in the stirred tank, and slightly greater those predicted by the slurry absorption model.

The species which influence absorption most are OH^- and SO_3^{-2} . Properties of these species were changed, and the model was run to test whether the absorption rate of SO_2 predicted by the model would be affected. Initially, equilibrium conditions for formation of the CaOH^+ and CaSO_3^0 ion pairs were changed but did not result in a significant effect on the predicted SO_2 absorption.

The rate of crystallization of CaSO_3 was also changed but had little effect on the resulting SO_2 absorption predicted by the model. Of all the properties, only the changes made to the diffusivity of OH^- had a significant effect on predicted absorption of SO_2 .

In fact, there may be some physical explanation for why the diffusivity of OH^- in the 17 mM $\text{Ca}(\text{OH})_2$ solution may be altered. For example, the diffusivities of Ca^{2+} and OH^- used by the model assume diffusion occurs in an infinitely dilute solution. Perhaps as the concentration of $\text{Ca}(\text{OH})_2$ is increased, the assumption of an infinitely dilute solution no longer holds, and the diffusivities of one or both of these species are affected. This was not documented by any experiments performed for this type of research.

The slurry absorption model was run initially using a value of $1.00 \times 10^{-4} \text{ cm}^2/\text{s}$ for the diffusivity of the hydroxide ion. This value was taken from D_{OH^-} reported at 25 °C by Chan and Rochelle (1981)

Figure 4-4. Enhancement of SO_2 absorption in 17 mM $\text{Ca}(\text{OH})_2$ /0.1 M CaCl_2 solution (calculations done at 18 mM $\text{Ca}(\text{OH})_2$).

and corrected for the change in viscosity and temperature at 55 °C using equation (3-11), based on the Stokes-Einstein relationship.

An adjusted diffusivity of OH^- was chosen such that the model predictions would match the absorption of SO_2 measured in the stirred tank. The resulting diffusivity was $3.83 \times 10^{-5} \text{ cm}^2/\text{s}$. The results of the slurry absorption model and the surface renewal theory based on this lower D_{OH^-} are shown in Figure 4-4 for comparison. Under these conditions the surface renewal theory no longer predicts to the same degree of enhancement as does the slurry absorption model.

Since the lower value for D_{OH^-} will be used to model absorption in solutions and slurries containing $\text{Ca}(\text{OH})_2$, it is important to model the absorption in the 2.5 mM $\text{Ca}(\text{OH})_2$ solution with the low D_{OH^-} as well. Figure 4-5 contains the same results plotted in Figure 4-3 with the addition of the enhancement predicted by the slurry absorption model for this solution assuming the low D_{OH^-} of $3.83 \times 10^{-5} \text{ cm}^2/\text{s}$. Under these conditions, enhancement is nearly the same as that predicted using the higher D_{OH^-} at values of $1/[\text{SO}_2]_i$ near 1400 L/mole. However, the model predicted unexplainably lower enhancement at both higher and lower values of $1/[\text{SO}_2]_i$. The enhancement measured in the stirred tank could be described by using either value of D_{OH^-} with about the same degree of accuracy, however.

4.6 ENHANCEMENT IN SOLUTIONS OF VARYING IONIC STRENGTH

All tests previously run in $\text{Ca}(\text{OH})_2$ solutions and slurries have contained 0.1 M CaCl_2 . To investigate the effect of the ionic strength in the bulk solution, 17 mM $\text{Ca}(\text{OH})_2$ solutions of varying ionic strength were tested. One test was run using 17 mM $\text{Ca}(\text{OH})_2$ solution containing no CaCl_2 . Another test was run with 0.1 M NaCl added, which is 1/3 the ionic strength of 0.1 M CaCl_2 .

By changing the ionic strength of the bulk solution, a number of properties can be affected. Without CaCl_2 or some other electrolyte present, a constant ionic strength would not be ensured throughout the solution. Activities of constituents can change, which directly affects solution equilibria.

Figure 4-5. Effect of low D_{OH} on enhancement of SO_2 absorption in 2.5 mM $Ca(OH)_2$ /0.1 M $CaCl_2$ solution.

Equilibrium constants and solubility constants can be affected. Also, diffusivities of ionic species can be affected. Of course, absorption and reaction of SO_2 occurs within the boundary layer at the surface of the gas/liquid interface, and absorption and reaction depend upon the ionic strength of the boundary layer solution. These experiments will show whether there is significant change to the conditions within the boundary layer when ionic strength in the bulk solution is altered.

Shown in Tables 4-12 and 4-13 are summaries of results for tests performed in solutions of 17 mM $\text{Ca}(\text{OH})_2$ containing no CaCl_2 and containing 0.1 M NaCl , respectively. The range of SO_2 concentrations tested was 600 to 2,700 ppm. Under these conditions, enhancement and gas film resistance were high. In fact, two tests at low SO_2 concentrations resulted in absorption that was too gas film controlled to yield a measurable enhancement factor.

The results of tests performed in 17 mM $\text{Ca}(\text{OH})_2$ solutions with varied ionic strength are compared in Figure 4-6. Varying the ionic strength of the bulk solution had no significant effect on enhancement of SO_2 absorption.

Inputs which simulate the composition of the solutions used in these tests were developed for running the slurry absorption model. However, the model had trouble converging and would not run at all for solutions containing NaCl . It would be interesting to note whether the model predicts any significant effect of changes in ionic strength in the bulk solution. The model should be modified in the future to allow for such a comparison.

4.7 SUMMARY OF EXPERIMENTS IN CLEAR SOLUTIONS

The clear solution experiments revealed a few important details about the absorption of SO_2 in solutions containing $\text{Ca}(\text{OH})_2$. The degree of absorption of SO_2 was measured in terms of the enhancement factor and in terms of the degree that gas film resistance controls the absorption. The results are compared and summarized below. Also, the enhancement of SO_2 absorption measured in these solutions was used to validate enhancement predicted by the slurry absorption model. Conclusions reached from comparing the experimentally measured absorption of SO_2 to the absorption predicted by this model are also summarized below.

TABLE 4-12. ENHANCEMENT OF SO₂ ABSORPTION IN 17 mM Ca(OH)₂ CONTAINING NO CaCl₂
($k_g = 1.49 \times 10^{-5}$ mole/m² Pa s)

Test #	SO ₂ Conc. (ppm)	Liq. Agitator Speed (rpm)	$k_l \times 10^5$ (m/s)	Contact Time (s)	Ø	Gas Film Res. (%)
CNo1	1942	1193	7.6	0.8	61	58
CNo2	1145	1193	7.6	0.8	124	74
CNo3	710	1193	7.6	0.8	78	64
CNo4	817	1028	6.7	1.1	219	81
CNo5	1836	1028	6.7	1.1	55	52
CNo6	2074	891	6.0	1.4	46	45
CNo7	2601	891	6.0	1.4	47	46
CNo8	921	891	6.0	1.4	52	48
CNo9	1232	706	5.0	1.9	71	52
CNo10	2358	706	5.0	1.9	41	38

TABLE 4-13. ENHANCEMENT OF SO₂ ABSORPTION IN 17 mM Ca(OH)₂ CONTAINING 0.1 M NaCl
($k_g = 1.49 \times 10^{-5}$ mole/m² Pa s)

Test #	SO ₂ Conc. (ppm)	Liq. Agitator Speed (rpm)	$k_l \times 10^5$ (m/s)	Contact Time (s)	Ø	Gas Film Res. (%)
CNa1	1745	1212	7.7	0.8	74	66
CNa2	899	1212	7.7	0.8	--	97
CNa3	643	1212	7.7	0.8	97	72
CNa4	734	1035	6.7	1.1	--	91
CNa5	2023	1035	6.7	1.1	38	47
CNa6	1903	863	5.8	1.4	51	50
CNa7	2692	863	5.8	1.4	40	44
CNa8	711	863	5.8	1.4	90	64
CNa9	968	706	5.0	1.9	125	68
CNa10	2421	706	5.0	1.9	34	37

Figure 4-6. Comparison of enhancement of SO₂ absorption in 17 mM Ca(OH)₂ solutions at various ionic strengths.

4.7.1 Enhancement and Gas Film Resistance

The enhancement factor has proven to be a valuable parameter for comparing the degree of SO_2 absorption measured in the stirred tank reactor. Because it represents a normalized flux of SO_2 , it was possible to vary the bulk gas SO_2 concentration and the contact time in the reactor and still have a constant basis for comparison of absorption. The enhancement factor was shown to be independent of contact time, or k'_l , determined by the liquid agitation rate in the reactor. Measurement of enhancement in water and CaCl_2 solutions was found to be repeatable to within about 5 percent.

The enhancement factor was found to be a strong function of the SO_2 concentration of the bulk gas. The enhancement factor increased about 30 percent when CaCl_2 was added to water. Even more dramatic increases in enhancement were measured when increasing amounts of dissolved $\text{Ca}(\text{OH})_2$ were tested. Changes to the bulk ionic strength did not influence the enhancement measured in 17 mM $\text{Ca}(\text{OH})_2$ solutions, however. Figure 4-7 summarizes the enhancement factors presented in this section, with the enhancement predicted by the slurry absorption model to illustrate the influence of the bulk gas SO_2 concentration. The model for the 17 mM $\text{Ca}(\text{OH})_2$ solution was run assuming the low value of D_{OH^-} .

Generally, as the enhancement factor increased, the degree of gas film resistance for the absorption of SO_2 also increased in the stirred tank experiments. The percentage of gas film resistance was an important parameter to monitor because it defined the operating limits for the stirred tank reactor. The degree of gas film resistance increased for conditions of low bulk SO_2 concentration and short contact times. As a solution nears 100 percent gas film resistance, enhancement can no longer be measured. The absorption is dominated by the gas film properties. Some clear solution tests resulted in absorption that was over 90 percent gas film controlled, and enhancement could not be measured accurately.

Gas film resistance increased as the solutions in the stirred tank were made more reactive towards SO_2 . The highest degree of gas film resistance was measured in 17 mM $\text{Ca}(\text{OH})_2$ at low bulk SO_2 concentrations. Figure 4-8 shows the degree of gas film resistance measured in the stirred tank

Figure 4-7. Enhancement of SO₂ absorption in clear solutions as a function of bulk SO₂ concentration (model: $\theta = 0.9$ s, data: $\theta = 0.9 - 2.5$ s).

Figure 4-8. Gas film resistance in clear solutions of Ca(OH)₂ as a function of bulk SO₂ concentration (model: $\theta = 0.9$ s, data: $\theta = 0.9 - 2.5$ s).

and predicted by the slurry absorption model for the 2.5 mM and 17 mM Ca(OH)_2 solutions. The model was run for a contact time of 0.9 s. Note that the experimental data spans contact times of 0.9 to 2.5 s, which is why most of the data is below the model curves. Again, the model for the 17 mM Ca(OH)_2 solution was run assuming the low value of D_{OH} .

This figure shows that when the clear solution containing 17 mM Ca(OH)_2 was exposed to SO_2 concentrations of less than 2,000 ppm, the absorption was over 50 percent gas film controlled. As determined in the slurry experiments discussed in Section 5, it was difficult to measure enhancement in Ca(OH)_2 slurries subjected to SO_2 concentrations of less than 2,000 ppm because gas film resistance increased to over 90 percent.

As previously mentioned, the absorption tended to be more gas film controlled at the shorter contact times. The range of contact times available in the stirred tank was about 0.9 to 2.5 s. In Figure 4-8, the model was run at a contact time of 0.9 s, thus some of the data obtained in the stirred tank at higher contact times lies below the curve predicted by the model. The slurry absorption model clearly illustrates the dependence of gas film resistance on contact time. Figure 4-9 shows gas film resistance predicted in 17 mM Ca(OH)_2 over a range of contact times from 0.1 to 10 s for three SO_2 concentrations.

4.7.2 Slurry Absorption Model and Theory

The measurements of the absorption of SO_2 in clear solutions were useful in validating the slurry absorption model. The surface renewal theory solutions for the enhancement of SO_2 absorption developed by Chang and Rochelle (1979) were used as a reference for comparison. The predictions made by Chang and Rochelle, based on the surface renewal theory, had been experimentally proven in their work (1980, 1981, 1982) and in experiments performed by Weems (1981). The clear solution experiments in water, 0.1 M CaCl_2 and 2.5 mM Ca(OH)_2 performed for this research produced enhancement factors which compared well with those predicted by the surface renewal theory solutions. Also, the slurry absorption model predicted enhancement factors for SO_2 absorption in these solutions

Figure 4-9. Gas film resistance in 17 mM $\text{Ca}(\text{OH})_2$ as a function contact time.

that compared well with the measured enhancement factors and generally followed the surface renewal theory solutions.

However, both the surface renewal theory solutions and the slurry absorption model were not initially capable of predicting measured enhancement of SO_2 absorption in the 17 mM $\text{Ca}(\text{OH})_2$ solution. Both overpredicted the absorption by more than 2 times that measured in the stirred tank. Apparently, as the solution reaches saturation, some changes to the properties of some individual species have occurred.

For example, the diffusivities of Ca^{2+} and OH^- used by the model are those for diffusion in an infinitely dilute solution. Perhaps as the concentration of $\text{Ca}(\text{OH})_2$ is increased, the assumption of an infinitely dilute solution no longer holds, and the diffusivities of one or both of these species are affected. Although these changes have not been fully investigated and are not understood, the slurry absorption model was adjusted to yield an accurate prediction of enhancement of SO_2 absorption. The adjustment, which involves reducing the diffusivity of OH^- to approximately 40 percent of its referenced value, will be used further in Section 5 for validation of absorption in slurry solutions.

SECTION 5

RESULTS OF EXPERIMENTS IN $\text{Ca}(\text{OH})_2$ SLURRIES

The experiments performed in $\text{Ca}(\text{OH})_2$ slurries were designed to study two factors affecting absorption, the most important of which was the amount of solids present in the slurry. SO_2 absorption was measured in slurries with total $\text{Ca}(\text{OH})_2$ concentration ranging from 35 mM to 1.0 M. Absorption of SO_2 at concentrations of 500 to 5,000 ppm into slurries containing 1.0 M (7 wt percent) $\text{Ca}(\text{OH})_2$ or more solids was found to be controlled primarily by gas film resistance.

A second factor studied involved measuring SO_2 absorption into slurries with varied reactivity. Properties of the solid $\text{Ca}(\text{OH})_2$ particles, such as surface area and particle size, are known to affect reactivity toward SO_2 . Thus, slurries were prepared from different sources of $\text{Ca}(\text{OH})_2$ and SO_2 absorption was measured. The measurements were intended to determine how much of an effect such properties could have on the enhancement factor, and hence, their ability to control or limit absorption of SO_2 .

The absorption experiments in slurries also allowed for further verification of the slurry absorption model. Several conditions studied in the last chapter were determined to be important factors affecting absorption into a clear solutions of $\text{Ca}(\text{OH})_2$. The slurry experiments go further to provide data to evaluate the effect of various properties of the solids. This allows for validation of the $\text{Ca}(\text{OH})_2$ dissolution portion of the slurry absorption model.

5.1 EXPERIMENTAL CONDITIONS

Slurry was fed to the reactor at a rate of 205 mL/min from an agitated mix tank. Continuous feed helped provide a steady-state condition for reaction of $\text{Ca}(\text{OH})_2$ solids and prevented buildup of

calcium sulfite solids. All slurry tests were run at 55 °C with 0.1 M CaCl₂ added to the slurries. A variety of Ca(OH)₂ concentrations and Ca(OH)₂ sources were used.

As in the clear solution experiments, the gas phase was mixed at the maximum agitation speed of approximately 1,400 rpm. This resulted in a gas phase mass transfer coefficient of 1.5×10^{-4} mole/s cm² bar. The liquid phase mass transfer coefficient was varied by changing the liquid agitation speed. Slurry compositions and other variables are listed in Table 5-1. All concentrations of Ca(OH)₂ indicated in this report represent the total amount of Ca(OH)₂ in the slurry, as opposed to the amount of Ca(OH)₂ solids.

The total absorbed sulfur concentration in the liquid was estimated using a gas phase material balance and a liquid phase material balance, which accounted for the continuous flow of slurry through the reactor. The concentration of total sulfur was then confirmed by analyzing samples of reactor effluent by ion chromatography, as previously described.

Again, increase in liquid phase mass transfer due to solids addition is reported in terms of the enhancement factor, Φ . The enhancement factor is the ratio of the measured liquid phase mass transfer coefficient, k_l , and k_l° , the characteristic liquid phase mass transfer coefficient in the absence of chemical reactions for the conditions of the experiment. The k_l° for different conditions is known based on the correlations developed in Section 3.

TABLE 5-1. TEST CONDITIONS FOR Ca(OH)₂ SLURRY EXPERIMENTS

Total Ca(OH) ₂ Conc. (M)	Ca(OH) ₂ Type	SO ₂ Conc. (ppm)	Liq. Agitator (rpm)	$k_l^\circ \times 10^5$ (m/s)
0.035	MCB Reagent	2,450 - 4,560	340 - 1,180	3.3 - 7.5
0.1	MCB Reagent	1,660 - 4,360	650 - 1,280	4.8 - 8.1
1.0	MCB Reagent	1,440 - 5,000	440 - 1,380	3.8 - 8.7
0.1	Mississippi	2,120 - 4,560	680 - 1,150	4.9 - 7.4
0.4	Mississippi	2,140 - 4,480	690 - 1,150	5.0 - 7.3
0.1	Mississippi Slaked	2,130 - 4,460	670 - 1,170	4.9 - 7.5

The value of $\emptyset$ was determined from equation (4-1). It is important to remember that $\emptyset$ is a normalized absorption rate or flux. It allows comparison of data obtained in the stirred tank reactor independent of the value of k_l (or contact time) and the level of SO_2 maintained in the liquid phase reactor. Because the driving force and the contact time were constantly changed within the reactor during slurry experiments, the absorption rate, N_{SO_2} , could not be compared from one test to another on a consistent basis.

The absorption rate, N_{SO_2} , was measured directly by gas phase material balance. The interface concentration, $[\text{SO}_2]_i$, was calculated using the Henry's law relationship given in equation (2-10). The gas phase concentration of SO_2 at the interface, p_{SO_2} , was determined by equation (2-1) and the relationship for k_g given in equation (3-8). In $\text{Ca}(\text{OH})_2$ slurries, the concentration of SO_2 in the bulk phase, $[\text{SO}_2]_o$, is negligible due to the instantaneous reaction of SO_2 .

Calculation of the enhancement factor required a combination of several measured values, each of which has a degree of error associated. Such values include mass flow meter measurements, SO_2 concentrations, and measurement of k_g and k_l . To obtain an idea of the accuracy of $\emptyset$, the estimated errors were carried through the calculations for $\emptyset$. The error associated with $\emptyset$ is presented with the test data later in this section.

In general, measurements became less precise as gas film resistance increased. This occurred typically at low SO_2 concentrations and higher solids concentrations. In fact, for most experiments performed in slurries, the absorption was over 90 percent gas film controlled at SO_2 concentrations less than 2,000 ppm. Accurate determination of the enhancement factor could only be made when gas film resistance was 80 percent or less. Some enhancement factors reported from tests with higher degrees of gas film resistance may be questionable.

5.2 RESULTS OF SLURRY EXPERIMENTS

The following presents the results of experiments in $\text{Ca}(\text{OH})_2$ slurries. Enhancement of SO_2 absorption was measured in slurries of increasing solids concentration and in slurries made from different sources of $\text{Ca}(\text{OH})_2$.

5.2.1 Enhancement in Increasing Concentrations of Reagent Grade Ca(OH)_2

The first slurry experiments used reagent grade Ca(OH)_2 purchased from chemical suppliers. A stock of MCB Reagent (lot 3031) Ca(OH)_2 and Fisher Reagent (lot 883017) were available. The Fisher Reagent Ca(OH)_2 had been received on 7/5/88 but was unopened. The MCB Reagent was received just prior to testing clear solutions containing Ca(OH)_2 which began 7/11/89. The difference in the age of the reagents may have had an effect on their reactivity.

Slurry containing three levels of total Ca(OH)_2 concentration (35 mM, 0.1 M, and 1.0 M) were tested with these reagents. Initial experiments at these concentrations showed that absorption was greatly improved with solids present. In fact, since so much SO_2 was being absorbed, the concentration level of SO_2 in the reactor was very low. At the low concentrations, the absorption was gas film controlled, so determination of an enhancement factor was not possible. A mass flow meter with a higher flow capacity (5 L/min) was installed so that higher SO_2 concentrations in the reactor could be achieved.

After the new mass flow meter was installed, a second set of experiments at the same Ca(OH)_2 slurry concentrations was performed. The conditions were changed such that SO_2 concentrations above 2,000 ppm could be produced.

The second set of test runs in 35 mM Ca(OH)_2 slurry, prepared with MCB Reagent Ca(OH)_2 , produced measurable values of $\emptyset$. Gas film resistance was moderately high. Contact times for these experiments were varied from about 1 to 2 s. Enhancement factors measured in the 35 mM Ca(OH)_2 slurry ranged from about 20 to 80, whereas gas film resistance ranged from 23 to 65 percent.

Table 5-2 summarizes the results of this set of test runs.

Another set of tests were performed at the higher solids concentration of 0.1 M Ca(OH)_2 using the MCB Reagent stock. Again, SO_2 concentration in the reactor was maintained at much higher levels to produce measurable enhancement factors. As before, contact times were varied from about 1 to 2 s. The higher solids level in the 0.1 M Ca(OH)_2 slurry resulted in enhancement factors ranging from 35 to 185 and gas film resistance which increased to the range of 34-81 percent. The largest enhancement

TABLE 5-2. RESULTS OF TESTS PERFORMED IN 35 mM Ca(OH)₂ MCB
REAGENT GRADE SLURRY
($k_g = 1.44 \times 10^{-5}$ mole/m² Pa s).

Test #	SO ₂ Conc. (ppm)	$k_g \times 10^5$ (m/s)	Contact Time (s)	Ø	Gas Film Res. (percent)
S35R1	3945	7.5	0.9	40	48
S35R2	3323	7.5	0.9	49	53
S35R3	2429	7.5	0.9	79	65
S35R4	3157	6.7	1.1	40	45
S35R5	3846	6.7	1.1	36	42
S35R6	4152	6.7	1.1	35	42
S35R7	4555	5.6	1.5	32	36
S35R8	4338	5.6	1.5	31	35
S35R9	3635	5.6	1.5	28	33
S35R10	4066	4.9	2.0	25	28
S35R11	3869	4.9	2.0	20	23
S35R12	4471	4.9	2.0	26	28

and largest degree of gas film resistance is always achieved at lower SO₂ concentrations and short contact times. The results of these experiments are summarized in Table 5-3.

A final set of tests were run using the old, unopened Fisher Reagent at 1.0 M Ca(OH)₂, 7 weight percent. Unfortunately, the results of these tests were questionable and are not reported. Initially, the 1 L/min flow meter was used and at least 4 of 7 tests were too gas film controlled to measure the enhancement factor. The flow meter was changed and plumbing modified. The reagent was kept covered and constantly stirred but over a full day passed before testing was resumed. The remaining 5 test runs resulted in suspiciously low enhancement factors. This was probably caused by two factors. First, the reagent was old and its reactivity may have been affected. A greater factor was that it was prepared a day and a half before it was used. This allowed for the slurry to react with CO₂ in the air to form carbonate, which is less reactive toward SO₂ under these experimental conditions.

TABLE 5-3. RESULTS OF TESTS PERFORMED IN 0.1 M Ca(OH)_2 MCB REAGENT GRADE SLURRY
 $(k_g = 1.44 \times 10^{-5} \text{ mole/m}^2 \text{ Pa s})$

Test #	SO_2 Conc. (ppm)	$k_g \times 10^5$ (m/s)	Contact Time (s)	ϕ	Gas Film Res. (percent)
SO.1R1	3374	7.4	0.9	70	62
SO.1R2	3730	7.4	0.9	65	60
SO.1R3	2756	7.4	0.9	99	69
SO.1R4	2044	7.4	0.9	185	81
SO.1R5	2390	6.6	1.1	96	66
SO.1R6	3038	6.6	1.1	75	61
SO.1R7	3609	6.6	1.1	61	56
SO.1R8	3962	6.6	1.1	58	54
SO.1R9	3972	5.7	1.5	52	48
SO.1R10	3807	5.7	1.5	43	43
SO.1R11	3056	5.7	1.5	51	47
SO.1R12	3574	4.8	2.1	35	34
SO.1R13	2862	4.8	2.1	39	36
SO.1R14	4364	4.8	2.1	36	34

The enhancement factors calculated from the two valid tests are shown in Figure 5-1. Also shown are the test results for the clear solution case of 17 mM Ca(OH)_2 (no solids) presented earlier in Section 4. An increase in enhancement has resulted by increasing the solids content of the slurry.

Although the Ca(OH)_2 content was doubled from 17 mM to 35 mM and then nearly tripled to 0.1 M, the increase in enhancement was not nearly as great. Enhancement increased by about 50 percent from increasing Ca(OH)_2 concentration from 17 mM to 35 mM, and only increased by about 25-30 percent from increasing Ca(OH)_2 concentration from 35 mM to 0.1 M. Apparently, adding solids at higher initial slurry concentrations has less of an affect on enhancement than adding solids at lower initial slurry concentrations.

Figure 5-1. Comparison of tests performed in reagent grade slurry.

As previously mentioned, the degree of accuracy of the enhancement factor is less as the absorption becomes more gas film controlled. An analysis of the expected amount of error for the enhancement factor was made for the measurements taken during slurry tests. Figure 5-2 shows the results of the analysis for 0.1 M Ca(OH)_2 reagent grade slurry plotted in Figure 5-1 with high and low error limits designating the range of accuracy of the enhancement factors.

Error is dramatically increased at higher enhancement factors. This is because the greater degree of enhancement causes the absorption to become more gas film controlled. The largest enhancement factor measured during this set of experiments in 0.1 M Reagent grade Ca(OH)_2 was 185, and the gas film resistance of the absorption was 81 percent. The error analysis shows that the enhancement factor is only known to within ± 40 percent accuracy. Unfortunately, this cannot be improved much by improving the accuracy of the measurements taken. The high degree of uncertainty results because $p\text{SO}_2$ becomes very small as the absorption approaches gas film controlled conditions, yet it must be obtained from subtracting two large concentrations (i.e., the bulk SO_2 concentration and the amount of SO_2 which is transferred to the liquid phase). Therefore, although enhancement factors are reported for tests in which absorption was over 80 percent gas film controlled, it should be remembered that these measurements have an inherently high error.

5.2.2 Enhancement in Slurries Made From Mississippi Ca(OH)_2

A supply of Mississippi Ca(OH)_2 was purchased so that further tests could be performed in slurries of higher solids concentrations. Tests in slurries prepared with Mississippi Ca(OH)_2 at three Ca(OH)_2 concentrations were performed. The first had a Ca(OH)_2 concentration of 0.1 M, so that results could be compared to the test results previously presented using 0.1 M Ca(OH)_2 made with reagent grade material. The other two tests used slurry prepared at the higher Ca(OH)_2 concentration levels of 0.4M and 1.0 M. Unfortunately, it was difficult to obtain reasonable measurements of absorption with the slurry containing 1.0 M Ca(OH)_2 since gas film resistance was very high, even at high SO_2 concentrations. As in the case of the reagent grade material, no enhancement factors from the attempted test in slurry containing 1.0 M Ca(OH)_2 were considered reportable. Table 5-4 presents

Figure 5-2. Estimated error associated with tests performed in 0.1 M $Ca(OH)_2$ MCB reagent grade slurry.

TABLE 5-4. RESULTS OF TESTS PERFORMED IN 0.1 M Ca(OH)_2 MISSISSIPPI Ca(OH)_2 SLURRY
($k_g = 1.42 \times 10^{-5}$ mole/m² Pa s)

Test #	SO ₂ Cono. (ppm)	$k^o \times 10^5$ (m/s)	Contact Time (s)	$\emptyset$	Gas Film Res. (percent)
S.1M1	3006	7.4	0.9	120	74
S.1M2	3548	7.4	0.9	82	65
S.1M3	2380	7.4	0.9	249	85
SO.1M4	2866	6.5	1.2	97	68
SO.1M5	2115	6.5	1.2	175	78
SO.1M6	3872	6.5	1.2	65	57
SO.1M7	3359	6.5	1.2	82	63
SO.1M8	3706	5.7	1.5	66	54
SO.1M9	4190	5.7	1.5	56	50
SO.1M10	2574	5.7	1.5	86	61
SO.1M11	2566	4.9	2.0	62	49
SO.1M12	3488	4.9	2.0	49	43
SO.1M13	4293	4.9	2.0	48	42
SO.1M14	4562	4.9	2.0	49	43

a summary of the results for a set of test runs with Mississippi Ca(OH)_2 slurry containing 0.1 M Ca(OH)_2 . Again, SO₂ concentrations were maintained above 2,000 ppm to avoid gas film controlled absorption.

For the same range of contact times of 1 to 2 s studied during reagent grade Ca(OH)_2 experiments, enhancement factors ranged from about 50 to 250. Gas film resistance varied from 42 to 85 percent. As can be seen in Figure 5-3, the enhancement measured with Mississippi Ca(OH)_2 slurry is nearly the same as that measured in the reagent slurry. Although the Mississippi Ca(OH)_2 appears to yield slightly greater enhancement, the difference is well within experimental error.

A summary of the results of tests performed in Mississippi Ca(OH)_2 slurry containing 0.4 M Ca(OH)_2 are shown in Table 5-5. The test conducted at the lowest SO₂ concentration of 2135 ppm resulted in a gas film controlled absorption of about 98 percent. This made enhancement an

Figure 5-3. Comparison of enhancement in Mississippi hydrate and reagent grade slurry at 0.1 M $Ca(OH)_2$.

unmeasurable parameter within reasonable experimental error. Enhancement factors that were measurable ranged from 60 to 360. Tests run at low contact times ranged between 70 and 98 percent gas film controlled. Those at the longer contact times and higher SO₂ concentrations ranged from about 50 to 70 percent gas film controlled.

These results show that measurement of the enhancement factor in slurries of higher solids content would only be possible under conditions of SO₂ concentrations greater than 3,000 ppm and contact times greater than 1.5 s. Conditions of lower SO₂ concentration or shorter contact times would result in an absorption that was completely gas film controlled.

TABLE 5-5. RESULTS OF TESTS PERFORMED IN 0.4 M Ca(OH)₂ MISSISSIPPI Ca(OH)₂ SLURRY
($k_g = 1.42 \times 10^{-5}$ mole/m² Pa s)

Test #	SO ₂ Conc. (ppm)	$k_l \times 10^5$ (m/s)	Contact Time (s)	Ø	Gas Film Res (percent)
SO.4M1	2677	7.3	0.9	277	86
SO.4M2	2861	7.3	0.9	367	89
SO.4M3	3126	7.3	0.9	232	84
SO.4M4	3503	6.6	1.1	120	71
SO.4M5	3112	6.6	1.1	188	79
SO.4M6	2651	6.6	1.1	342	88
SO.4M7	2135	6.6	1.1	--	98
SO.4M8	2688	5.8	1.5	146	73
SO.4M9	3392	5.8	1.5	89	62
SO.4M10	3806	5.8	1.5	78	59
SO.4M11	4092	5.0	1.5	69	56
SO.4M12	4484	5.0	2.0	58	48
SO.4M13	4267	5.0	2.0	61	49
SO.4M14	4008	5.0	2.0	58	48

The results of the test with Mississippi Ca(OH)₂ slurry containing 0.4 M Ca(OH)₂ are compared to the test results from Mississippi Ca(OH)₂ slurry containing 0.1 M Ca(OH)₂ and those from tests in 35 mM reagent grade Ca(OH)₂ in Figure 5-4. Again, an increase in enhancement was measured, but

this increase was only 20 to 25 percent for a 4-fold increase in solids concentration. Gas film resistance during these experiments was about 50 percent and above. It is unlikely that the stirred tank reactor can measure enhancement accurately in slurries with solids concentrations much greater than about 0.5 M.

Another attempt at measuring SO_2 absorption in 1.0 M Ca(OH)_2 slurry was made using the Mississippi Ca(OH)_2 slurry. Again, the absorption was determined to be too gas film controlled to obtain measurement of the enhancement factor.

5.2.3 Enhancement in Three Different Lime Types

Results from two experiments performed in 0.1 M Ca(OH)_2 have already been presented previously. One was made from MCB Reagent stock Ca(OH)_2 . The other was prepared using Mississippi Ca(OH)_2 . A third set of experiments was performed in 0.1 M Ca(OH)_2 from another source. A supply of Mississippi pebble quicklime was obtained and slaked in the lab to make Ca(OH)_2 . Experiments were run with the different lime types to determine if measurement of the enhancement in the stirred tank is sensitive enough to show significant differences from one type to another.

Slaking is the process whereby quicklime, CaO , is reacted with water to form Ca(OH)_2 . The reaction is quick and highly exothermic. By providing conditions such as adequate mixing and a constant high temperature of over 190 °C, the surface area, and hence, the reactivity of the product solids can be maximized. Freshly slaked lime is generally more reactive than powdered Ca(OH)_2 because the material has not had time to agglomerate or degrade (e.g., from CO_2 contamination). Therefore, the Ca(OH)_2 particles produced by slaking are typically smaller, fresher and more reactive to SO_2 .

The slaked Mississippi Ca(OH)_2 slurry was prepared in the agitated mix tank generally used as the slurry feed tank. One batch of Mississippi CaO was slaked at a concentration of 0.1 M Ca(OH)_2 over a period of approximately 1 h. During the slaking, the temperature in the mix tank was monitored and found to achieve only 140-150 °C. Since this is not an optimum slaking temperature, it may have produced fewer reactive particles. In fact, lime slaked at this lower temperature typically results in a

Figure 5-4. Comparison of enhancement in Mississippi $Ca(OH)_2$ slurry at higher $Ca(OH)_2$ concentrations.

Ca(OH)_2 product which has a 5-10 percent lower surface area (Boynton, 1980). The results of the test runs in slaked Mississippi Ca(OH)_2 slurry are shown in Table 5-6.

TABLE 5-6. RESULTS OF TESTS PERFORMED IN 0.1 M Ca(OH)_2 MISSISSIPPI
SLAKED LIME SLURRY
($k_g = 1.42 \times 10^{-5}$ mole/m² Pa s)

Test #	SO ₂ Conc. (ppm)	$k' \times 10^5$ (m/s)	Contact Time (s)	Ø	Gas Film Res. (percent)
SO.1MS1	3653	7.5	0.9	71	62
SO.1MS2	3871	7.5	0.9	67	61
SO.1MS3	3012	7.5	0.9	118	73
SO.1MS4	2359	7.5	0.9	266	86
SO.1MS5	2724	6.7	1.1	118	71
SO.1MS6	2126	6.7	1.1	166	60
SO.1MS7	3461	6.7	1.1	71	60
SO.1MS8	3950	6.7	1.1	59	55
SO.1MS9	4182	6.7	1.1	55	54
SO.1MS10	4522	5.7	1.5	49	47
SO.1MS11	4403	5.7	1.5	47	46
SO.1MS12	3970	5.7	1.5	52	48
SO.1MS13	3436	5.7	1.5	58	51
SO.1MS14	2624	5.7	1.5	80	59
SO.1MS15	3373	4.9	2.1	47	41
SO.1MS16	4011	4.9	2.1	44	40
SO.1MS17	4462	4.9	2.1	43	40

Figure 5-5 compares the test results of the three lime types. Significant differences in enhancement were not measured between them. An analysis of the surface area of the Ca(OH)_2 particles in each slurry was not performed. These results indicate that either the three limes tested had similar reactivities toward SO₂ or the stirred tank reactor is capable of measuring only large differences in absorption such as those seen with changes in solids concentration.

Figure 5-5. Comparison of enhancement in slurry from three different sources of $Ca(OH)_2$ at 0.1 M $Ca(OH)_2$.

5.3 VALIDATION OF SLURRY ABSORPTION MODEL FOR Ca(OH)_2 SLURRIES

In Section 4, the degree of SO_2 absorption enhancement predicted by the slurry absorption model was validated for several clear solution compositions. The model was validated for the solution containing 17 mM Ca(OH)_2 and 0.1 M CaCl_2 by adjusting the diffusivity of hydroxide to 40 percent of the referenced value. This adjusted D_{OH^-} was used for prediction of the enhancement in slurries reported in this section as well.

5.3.1 Inputs that Establish Slurry Properties

The composition of the slurry was assumed to be the same as the 17 mM (saturated) Ca(OH)_2 solution with additional solid Ca(OH)_2 . Therefore the input for the model resulted in the same conditions listed in Table 4-10 for the 17 mM Ca(OH)_2 clear solution. Only two additional inputs were required for the slurries: solids concentration and particle size.

Solids concentration was specified as the same concentrations used in the stirred tank absorption experiments. The model was run for slurries containing total Ca(OH)_2 at levels of 35 mM, 0.1 M, 0.4 M and 1.0 M in 0.1 M CaCl_2 .

The particle size of Ca(OH)_2 while in the slurry is a difficult quantity to measure. Measurement of the particle size after drying the slurry is misleading due to particle agglomeration. Particle size of dry Ca(OH)_2 has been measured often and mean particle sizes are typically on the order of 1-5 μm (Boynton, 1980). Therefore, the slurry absorption model was run at several particle sizes to determine which represent the conditions of the slurry used in the stirred tank experiments. Particle sizes of 0.5, 1, 5 and 10 μm were used as input to the model.

The slurry absorption model is currently set up for no other inputs to establish the level of reactivity of the solids. Large particles are typically less reactive because the amount of exposed surface area per volume is small. When more exposed surface area is present, reaction of Ca(OH)_2 and SO_2 is increased. Therefore, by changing the particle size of the solid, the reactivity of the slurry is directly affected.

In practice, particle size alone is not the only factor which influences the reactivity of the Ca(OH)_2 solids in the slurry. Porosity of the particles can also increase the amount of exposed surface area, and hence, the reactivity of the solids. This is why surface area per volume of dry Ca(OH)_2 is typically measured and reported as an indicator of reactivity. Also, contamination of the solids (typically by exposure to CO_2 over long periods of time) can influence reactivity. Reagent purity and the source of the Ca(OH)_2 may also have some effect on reactivity.

The particle sizes used in the model may not actually represent the true particle size of the solids in the slurry. Instead, the particle size input is used to establish the relative reactivity of the Ca(OH)_2 solids in the slurry.

5.3.2 Enhancement Predicted by Slurry Absorption Model

A first step in predicting enhancement in slurries with the slurry absorption model was to validate that reducing the D_{OH^-} by 40 percent improved the ability of the model to predict the experimental results obtained in the stirred tank. Figure 5-6 shows enhancement measured in the stirred tank for a 35 mM Ca(OH)_2 slurry compared to enhancement predicted by the slurry absorption model under three conditions. First, the model was run without adjusting the D_{OH^-} to 40 percent of the referenced value. As found in the case of the 17 mM Ca(OH)_2 solution, the model overpredicted enhancement by a factor of 2. The model was then run with D_{OH^-} reduced by 40 percent at two different particle sizes.

By reducing D_{OH^-} by 40 percent, the slurry absorption model was able to predict the enhancement measured in the stirred tank experiments for the 35 mM slurry. This was in fact found to improve agreement of the model with all the slurries studied. All remaining model results for slurries presented in this section were generated using the reduced D_{OH^-} .

Increasing the particle size of the solids from 1 to 5 μm did not have a significant effect on the predicted enhancement in this slurry. The larger particle size did result in a slightly lower enhancement factor, which was expected.

Figure 5-6. Enhancement predicted by slurry absorption model for 35 mM Ca(OH)₂ slurry.

The effect of particle size was studied in more detail for a 0.1 M Ca(OH)_2 slurry since experiments with different sources of Ca(OH)_2 were performed at this slurry concentration. Figure 5-7 shows the results of enhancement predicted by the model at four different particle sizes compared to experimental results from tests in reagent grade 0.1 M Ca(OH)_2 slurry.

In addition, a comparison was made between enhancement predicted at different contact times. All model results presented in this section are evaluated at a contact time of 0.9 s. Figure 5-7 shows model results generated at a particle size of 1.0 μm at a 2.5 s contact time. The range of contact times simulated in the stirred tank was 0.9 to 2.5 s. It has been assumed that the enhancement factor in slurries is not a function of contact time over the range studied in the experiments. The model verifies that this is a good assumption.

The model predicts that relatively no change in enhancement results from reducing the particle size from 1.0 μm to 0.5 μm . However, increasing the particle size to 5 μm and further to 10 μm results in measurably lower enhancement. The experimental results appear to be best described by a slurry with a particle size between 5 and 10 μm .

The model was run at 3 different particle sizes at a slurry concentration of 0.4M Ca(OH)_2 for comparison of enhancement with that measured in the stirred tank. Figure 5-8 shows that little difference in enhancement was predicted upon increasing the particle size from 1 to 5 μm . A larger difference in enhancement was predicted when increasing the particle size to 10 μm . The few model runs at a particle size of 10 μm indicate that the experimental measurements of enhancement are best predicted by a particle size of at least 10 μm .

The particle sizes required by the slurry absorption model for predictions that agree with the enhancement measured in the stirred tank experiments increased as solids concentration increased. In other words, when the particle size used by the model is fixed, the model predicts a greater increase in enhancement due to the addition of solids to the slurry than the stirred tank experimental results indicate.

Figure 5-7. Effect of particle size on enhancement predicted by slurry absorption model for 0.1 M $Ca(OH)_2$ slurry.

Figure 5-8. Enhancement predicted by slurry absorption model for 0.4M Ca(OH)₂ slurry.

This conclusion is further supported by the few measurable results obtained from the stirred tank using 1.0 M $\text{Ca}(\text{OH})_2$ slurry. Most of the measurements were too gas film controlled to accurately estimate the enhancement factors. However, three test runs indicated less than 100 percent gas film controlled absorption. The slurry absorption model was run with 1.0 M $\text{Ca}(\text{OH})_2$ slurry concentration specified at two particle sizes to predict the degree of gas film control expected in this slurry. A comparison of gas film resistance predicted by the model with that measured in the stirred tank is made in Table 5-7.

The slurry absorption model predicts that this 1.0 M $\text{Ca}(\text{OH})_2$ slurry should be more reactive than the results of the stirred tank experiments indicate. The model predicted that the absorption should have been completely gas film controlled for all SO_2 concentrations less than 4,000 ppm.

5.3.3 Solids Settling in the Boundary Layer

There is a possible explanation for the difference in enhancement predicted by the model and measured in the stirred tank when solids content is increased. As is the case for all slurries, $\text{Ca}(\text{OH})_2$ particles will settle due to gravity if not well mixed. Although the bulk solution was well mixed in slurry experiments in the stirred tank, the boundary layer is inherently stagnant. Dissolved species remain present in the boundary layer for the defined contact time, but the solid particles may have settled out of the boundary layer sooner. Thus, the solid particles may not have enhanced the absorption of SO_2 as much as the model would predict. The experiments showed that this effect was more pronounced at higher solids concentrations.

TABLE 5-7. PREDICTED GAS FILM RESISTANCE IN 1.0 M $\text{Ca}(\text{OH})_2$ SLURRY AT VARIOUS SO_2 CONCENTRATIONS

	SO_2 Concentration				
	1,000 ppm	2,000 ppm	3,000 ppm	4,000 ppm	5,000 ppm
Model 1.0 μm	100 %	100 %	100 %	100 %	100 %
Model 10 μm	100 %	100 %	100 %	90 %	75 %
Stirred Tank	100 %	85 %	80 %	--	--

In order to judge whether this explanation is reasonable, some comparisons of settling velocities and boundary layer thickness were made. The boundary layer thickness can be roughly estimated by calculating the penetration distance, δ_D , as follows (Bird, Stewart and Lightfoot, 1960):

$$\delta_D = 4 \sqrt{D t} \quad (5-1)$$

A characteristic settling velocity related to this penetration distance would be:

$$V_D = \frac{\delta_D}{t} \quad (5-2)$$

$$\text{or} \quad V_D = 4 \frac{\sqrt{D}}{\sqrt{t}} \quad (5-3)$$

Using the range of contact times available in the stirred tank, and a characteristic diffusivity, $D_{Ca^{++}}$, for the calcium ion, a range of settling velocities and penetration distances can be estimated for the conditions in the stirred tank.

The slurry absorption model calculates a more precise penetration distance as a function of contact time, solids concentration and particle size. Penetration distances predicted by the model are shown in Table 5-8 for slurries exposed to 4,000 ppm SO_2 . Also shown are the maximum settling velocities calculated from the penetration distances and contact times. Any particles with settling velocities greater than the maximum settling velocities would settle out of the boundary layer sooner than the specified contact time.

These model results show that the penetration distance becomes much smaller as the slurry solids content is increased. Also, the penetration distance is smaller for larger slurry particles. Solids are more likely to settle out of the boundary layer if the penetration distance is smaller.

TABLE 5-8. PENETRATION DISTANCES AND MAXIMUM SETTLING VELOCITIES PREDICTED BY THE SLURRY ABSORPTION MODEL - 4,000 ppm SO₂

Contact Times	δ_D (μm)		Maximum V_D (m/s $\times 10^6$)	
	0.90 s	2.50 s	0.90 s	2.50 s
10 μm Particle Size				
35 mM Ca(OH) ₂	85.1	157.6	94.5	63
0.1 M Ca(OH) ₂	40.9	77.7	45.4	31.1
0.4 M Ca(OH) ₂	13.5	32.0	15.0	12.8
1.0 M Ca(OH) ₂	5.6	15.5	6.2	6.2
5.0 μm Particle Size				
35 mM Ca(OH) ₂	38.5	104.8	42.7	41.9
0.1 M Ca(OH) ₂	28.2	61.3	31.3	24.5
0.4 M Ca(OH) ₂	10.3	26.4	11.4	10.6
1.0 M Ca(OH) ₂	4.0	13.0	4.4	5.2

Some simple measurements of particle settling velocities were made in the laboratory. A slurry of each of the three Ca(OH)₂ types used in experiments was prepared at a Ca(OH)₂ concentration level of 0.4 M. A small amount was poured into a 1 L graduated cylinder. Generally, as the particles settled, a clear liquid front was observed. As the front dropped in the cylinder, the time and distance was recorded. The rate of settling was constant over most of the experiment, but reached a point where it slowed considerably. At this point, the particles were heavily concentrated at the bottom of the cylinder. Since the slurry became more concentrated as it dropped within the cylinder, estimates of the changing concentration were made as well. Table 5-9 summarizes the results of these simple experiments.

The measurements show that the reagent grade Ca(OH)₂ and the slaked Mississippi lime Ca(OH)₂ settled faster than the Mississippi hydrate Ca(OH)₂. However, even the Mississippi hydrate Ca(OH)₂ slurry settled faster than the maximum settling velocities in Table 5-8 prescribe. These

TABLE 5-9. MEASURED SETTLING VELOCITIES OF THREE SLURRY TYPES

	Measured Settling Velocity, V_D (m/s $\times 10^6$)		
	Reagent Grade	Miss. Hydrate	Miss. Slaked
< 0.4 M Ca(OH)_2	670	110	480
1.0 M Ca(OH)_2	510	80	350
2.0 M Ca(OH)_2	210	56	130

measurements appear to support the assumption that solids may have been settling out of the boundary layer during the concentrated slurry experiments.

It is not clear whether such behavior would be expected in an actual slurry droplet. Therefore, the model may be producing an accurate estimate of the enhancement of SO_2 absorption in a slurry droplet, although it tends to overpredict the measurements taken in the stirred tank. Additional study of the behavior of solids suspended in droplets may be needed to address this issue.

5.4 SUMMARY OF SLURRY ABSORPTION EXPERIMENTS

The slurry absorption experiments documented the effects that increased solids content and changes to reactivity of the slurry have on SO_2 absorption. The effects were reported in terms of the enhancement factor and the degree that gas film resistance controlled the absorption. In some of these experiments a completely gas film controlled absorption was achieved, thus the absorption was enhanced to the highest degree achievable in the stirred tank reactor. The results are compared and summarized below.

The results of the slurry absorption experiments were used to validate enhancement and degree of gas film resistance predicted by the slurry absorption model. Because solid Ca(OH)_2 is present in the slurries, these experiments were used to validate the part of the model that governs solid Ca(OH)_2 dissolution and reaction. Conclusions that were reached regarding the model's ability to predict the experimentally measured absorption of SO_2 are also summarized below.

5.4.1 Effect of Solids Concentration on Enhancement and Gas Film Resistance in the Stirred Tank

Slurries containing four levels of total Ca(OH)_2 concentration were studied: 35 mM, 0.1 M, 0.4 M, and 1.0 M. Addition of solids significantly enhanced the absorption of SO_2 in all cases. However, the increment of enhancement appeared to diminish as the slurry solids concentration was increased. A 50 percent increase in enhancement was observed when Ca(OH)_2 concentration was doubled from 17 mM to 35 mM. Only 25-30 percent increase in enhancement was measured when Ca(OH)_2 concentration was nearly tripled from 35 mM to 0.1 M. When Ca(OH)_2 concentration was quadrupled from 0.1 M to 0.4M, only 20-25 percent increase in enhancement resulted.

Enhancement factors predicted by the slurry absorption model for absorption in each of the slurries studied are summarized in Figure 5-9. The data was taken from the model runs which best represented the stirred tank results. Enhancement factors are presented as a function of SO_2 concentration. In absorption that was gas film controlled, the enhancement in the liquid phase becomes infinite and could not be measured in the stirred tank.

Few enhancement factors over 200 could be measured in the stirred tank because the absorption was too gas film controlled at that point. The model also showed gas film controlled absorption at that point, thus few enhancement factors over 200 are plotted.

The clear solution experiments in Section 4 pointed out that measurements of enhancement in slurries would not be possible with bulk gas SO_2 concentrations less than 2,000 ppm because these conditions would yield a gas film controlled absorption. Initial slurry tests were limited to the range of 2,000 to 5,000 ppm SO_2 , and tests with higher slurry solids content required over 3,000 ppm SO_2 to remain under 80 percent gas film controlled. Finally, the tests at 1.0 M Ca(OH)_2 required over 4,000 ppm SO_2 to make accurate measurements of enhancement. The stirred tank experiments were not able to produce meaningful enhancement factors at SO_2 concentrations lower than those mentioned because the absorption was too gas film controlled.

These limitations due to gas film resistance are easily seen in Figure 5-10. The gas film resistance was determined from the same data generated by the slurry absorption model that was

Figure 5-9. Effect of slurry Ca(OH)₂ concentration on enhancement predicted by slurry absorption model for tests performed in the stirred tank (corresponding $d_{\text{droplet}} = 800 \mu\text{m}$, $d_p = 5\text{-}10 \mu\text{m}$, $\theta = 0.9 \text{ s}$).

Figure 5-10. Effect of slurry Ca(OH)_2 concentration on gas film resistance predicted by slurry absorption model for tests performed in the stirred tank (corresponding $d_{\text{droplet}} = 800 \mu\text{m}$, $d_p = 5\text{-}10 \mu\text{m}$, $\theta = 0.9 \text{ s}$).

plotted in Figure 5-9. The model accurately predicted where the gas film resistance became great enough to make measurement difficult in the stirred tank.

The degree of error associated with determination of the enhancement factor increased dramatically as gas film resistance became dominant. In tests where the conditions resulted in gas film resistances of greater than 80 percent, the enhancement factor could not be determined with accuracy. As Figure 5-10 indicates, this began to limit the range of measurements that could be taken in the stirred tank, especially when solids concentration was increased to 0.4 and 1.0 M $\text{Ca}(\text{OH})_2$. Inaccuracy was found to be inherent in the calculation of ϕ and could not be improved much by improving the accuracy of individual measurements.

Discussion in Section 3 pointed out that the stirred tank reactor operates at a gas film mass transfer coefficient that is an order-of-magnitude smaller than might be expected for a slurry droplet. Therefore, it should be remembered that the enhancement factors and gas film resistances measured in the slurry absorption experiments may not be of the same magnitude as found in a slurry droplet. However, the trends identified in the stirred tank reactor should be similar to the behavior within a slurry droplet.

5.4.2 Effect of Solids Concentration on Enhancement and Gas Film Resistance in a Slurry Droplet

In order to predict the actual degree of enhancement and gas film resistance in a slurry droplet present during SO_2 absorption in the in-duct injection process, the global mass transfer effects described briefly in Section 1 need to be considered. So far, only the rigorous treatment of SO_2 absorption, $\text{Ca}(\text{OH})_2$ dissolution, and CaSO_3 crystallization has been developed. Some of the key elements to be considered in this analysis are:

- 1) The effects of evaporation of water are not yet considered. Therefore, the droplet is considered to have a constant size, and the solids concentration does not increase as water from the slurry evaporates. Some kind of shrinking core model must be added.
- 2) The version of the model that was used to predict absorption in the stirred tank was written in Cartesian coordinates. A version of the model exists in spherical coordinates but was

not run in this validation effort. The results presented in this section were run with the stirred tank version of the model.

- 3) Solids distribution in the bulk liquid and in the boundary layer are not adjusted for the effects of droplet shrinking or the potential for solids settling. Recirculation patterns in the droplet were not addressed.
- 4) The droplet size and drying time only represent an example of what might be typical. A full analysis of droplet size distributions and drying times such as proposed by Kinsey and Harriot (1988) would require modeling droplets of different sizes and determining drying times based on a polydisperse spray.

Although the model has not yet been coupled with theories that address these important issues, it has addressed the basic absorption and reaction of SO_2 in $\text{Ca}(\text{OH})_2$ slurries in a rigorous fashion. To illustrate how absorption in a slurry droplet will differ from the absorption in the stirred tank, the model was run with inputs that would simulate absorption in a droplet rather than absorption in the stirred tank. The only input that required changing was the value of k_g , the gas film coefficient. The k_g was increased an order of magnitude from 1.44×10^{-5} to 1.44×10^{-4} mole/m² Pa s, representing a slurry droplet of 75 μm .

A single droplet of 75 μm would dry after about 0.5 to 0.7 s, depending on the duct temperature, whereas this same droplet in a monodisperse spray would take as much as 1.7 s to dry (Kinsey and Harriot, 1988). An exact drying time cannot be estimated because it depends upon the gas flow characteristics, size distribution of other droplets in the spray, and temperature. This analysis assumes that the droplet is in slurry form (i.e., not totally dry) for at least 0.9 s, which was the contact time chosen for the model runs.

The slurry composition was assumed to be the same as in the slurry model runs presented already in this chapter. Therefore, the input of species concentrations for the model was the same as listed in Table 4-10 for the 17 mM (saturated) $\text{Ca}(\text{OH})_2$ clear solution, and solids concentrations were 35 mM, 0.1 M, 0.4M and 1.0 M (7 wt percent) $\text{Ca}(\text{OH})_2$. Two higher $\text{Ca}(\text{OH})_2$ concentrations were

modeled as well. Model runs were made at 2.0 M (13 wt percent) and 4.0 M (23 wt percent) Ca(OH)_2 . A Ca(OH)_2 particle size of 5 μm was assumed.

Figures 5-11 and 5-12 present the enhancement factors predicted by these slurry droplet model runs. Figure 5-11 shows the enhancement results as a function of SO_2 concentration, as most of the results have been presented in this chapter. Figure 5-12 shows the relationship of enhancement in a slurry droplet with increasing solids concentration.

For a given SO_2 concentration and total Ca(OH)_2 concentration, the enhancement predicted for a slurry droplet in Figures 5-11 and 5-12 is less than the enhancement shown in Figure 5-9 for the stirred tank. For instance, an enhancement factor of about 100 was measured in the stirred tank for a 0.1 M Ca(OH)_2 slurry at 3,000 ppm. The model predicted that a slurry droplet with the same solids content at 3,000 ppm would produce an enhancement factor of about 25. The main reason for the lower enhancement is that absorption in the slurry droplet is not nearly as gas film controlled as in the stirred tank. Figure 5-13 shows the amount of gas film resistance predicted for SO_2 absorption in the slurry droplet at a 0.9 s contact time.

By increasing the gas film coefficient by an order of magnitude, the model predicts that absorption into most of the slurry compositions studied is still controlled by liquid film resistances to a great degree. In fact, most of the resulting gas film resistances were less than 20 percent.

Note that the model was run for the 2.0 M (13 wt percent) and 4.0 M (23 wt percent) Ca(OH)_2 slurries as well. For gas concentrations of over 1,000 ppm SO_2 , absorption in all slurry concentrations studied, including these high solids slurries, resulted in gas film resistance less than 100 percent. Therefore, it appears that liquid film resistance is an important controlling factor in SO_2 absorption in slurry droplets. This conclusion is important, since it indicates that changes to the slurry could be made to further enhance the absorption of SO_2 in Ca(OH)_2 slurries.

Figure 5-11. Enhancement in a slurry droplet predicted by slurry absorption model ($d_{\text{droplet}} = 75 \mu\text{m}$, $d_p = 5 \mu\text{m}$, $\theta = 0.9 \text{ s}$).

Figure 5-12. Effect of Ca(OH)_2 concentration in a slurry droplet on enhancement predicted by slurry absorption model ($d_{\text{droplet}} = 75 \mu\text{m}$, $d_p = 5 \mu\text{m}$, $\theta = 0.9 \text{ s}$).

Figure 5-13. Effect of Ca(OH)_2 concentration in a slurry droplet on gas film resistance predicted by slurry absorption model ($d_{\text{droplet}} = 75 \mu\text{m}$, $d_p = 5 \mu\text{m}$, $\theta = 0.9 \text{ s}$).

5.4.3 Alternate Interpretation of Slurry Absorption Model Data

As previously discussed, the predictions made by the slurry absorption model for the case of a droplet undergoing SO_2 absorption must be considered carefully. Some key elements have not yet been considered in the model to allow direct use of the results. These key elements include such phenomenon as droplet drying and shrinking, and expression of the model in Cartesian coordinates.

However, the model results currently provide enough information to develop a less rigorous expression of SO_2 absorption in a slurry droplet, that is not a function of the droplet geometry. In this way, the effects of droplet drying and shrinking, and coordinate system used do not compromise the results. One key assumption made to simplify the expression which is developed here, however, is that the solids in the slurry droplet are uniformly dispersed throughout the droplet. As in the rigorous slurry absorption model, this simplified expression assumes that the slurry droplet is stagnant and does not circulate.

To begin this analysis, consider the spherical droplet in Figure 5-14. As the Ca(OH)_2 is depleted by reaction, the reaction front of the droplet changes from r_1 to r_2 . As absorption progresses, there will be a change in the total dissolved sulfur, denoted $\Delta[\text{S(IV)}]$. Ca(OH)_2 remains dispersed in the shrinking core of the droplet.

Gas and liquid film absorption rate expressions were given as equations (2-1) and (2-2). These rate expressions are listed below in a slightly different form, expressing the gas and liquid film coefficients in terms of gas and liquid diffusivities of SO_2 and of penetration distance. Equation (5-5) assumes a pseudo-steady-state distribution of solution species giving an effective driving force of $\Delta[\text{S(IV)}]$.

$$N_{\text{SO}_2} = \frac{D_g \Delta Y_{\text{SO}_2} A}{\delta_D} \quad (5-4)$$

Figure 5-14. Spherical drop with shrinking core of Ca(OH)_2 .

$$N_{SO_2} = \frac{D_l \Delta[S(IV)] A}{\delta_D} \quad (5-5)$$

Gas phase mass transfer occurs at the droplet surface denoted by r_1 . The liquid phase mass transfer occurs at the changing reaction front between r_1 and r_2 . Thus, the area and penetration distance can be defined in terms of r_1 and r_2 , and the resulting expressions for absorption of SO_2 would be:

$$N_{SO_2} = \frac{D_g \Delta Y_{SO_2} 4 \pi r_1^2}{r_1} \quad (5-6)$$

$$N_{SO_2} = \frac{D_l \Delta[S(IV)] 4 \pi r_1 r_2}{r_1 - r_2} \quad (5-7)$$

During the absorption, these rates must be equal at all times. By setting them equal, the following expression results:

$$\Delta Y = \frac{D_l}{D_g} \Delta[S(IV)] \frac{r_1}{r_1 - r_2} \quad (5-8)$$

A new term, F , is defined to be the volume fraction of $Ca(OH)_2$ remaining. It is equivalent to $1 - (\text{utilization of } Ca(OH)_2)$. As applied to the spherical droplet, F is expressed as:

$$F = \frac{4/3 \pi r_2^3}{4/3 \pi r_1^3} \quad (5-9)$$

Therefore,

$$(5-10)$$

$$F^{1/3} = \frac{r_2}{r_1}$$

Substituting this expression into equation (5-8), a new expression for the amount of gas film resistance is derived.

$$\text{Gas film resistance} = \frac{\Delta Y_{SO_2}}{Y_g} = \frac{D_l \Delta[S(IV)]}{D_g Y_g} \frac{F^{1/3}}{1 - F^{1/3}} \quad (5-11)$$

This expression can be used to estimate the gas film resistance in a slurry droplet for any given degree of utilization of Ca(OH)_2 . The only information which must be provided is the value of D_l , $\Delta[S(IV)]$, gas diffusivity, and bulk gas concentration. Notice that the geometry of the droplet is accounted for by the substitution of the term, F , the fraction of Ca(OH)_2 remaining.

The diffusivity of SO_2 in N_2 was given in Section 3 as $0.6 \text{ cm}^2/\text{s}$. Expressed in the units required for this equation, $D_g = 2.2 \times 10^{-8} \text{ mole/m s Pa}$. Values of $D_l \Delta[S(IV)]$ have been taken from model runs at several slurry Ca(OH)_2 concentrations and gas SO_2 concentrations. The values of $D_l \Delta[S(IV)]$ were easily calculated by noting that:

$$\frac{D_l \Delta[S(IV)] A}{\delta_D} = k_g \Delta Y_{SO_2} A \quad (5-12)$$

And this defines $D_l \Delta[S(IV)]$ in terms of gas phase properties and the penetration distance as follows:

$$D_l \Delta[S(IV)] = k_g \Delta Y_{SO_2} \delta_D \quad (5-13)$$

The model provided the necessary gas phase concentrations and penetration distances to calculate the values of $D_l \Delta[S(IV)]$ shown in Figure 5-15. These are shown as a function of PSO_2 I, as

Figure 5-15. Values of $D \Delta[S(IV)]$ derived from the slurry absorption model.

well as concentration of Ca(OH)_2 in the slurry. It does not appear that $D_1 \Delta[S(\text{IV})]$ depends on the bulk gas SO_2 concentration or on the slurry solids concentration.

An average value of $D_1 \Delta[S(\text{IV})]$ for this series of model runs is 7.0×10^{-8} mole/m sec. Using this value, a general relationship for the average gas film resistance can be made in terms of utilization of Ca(OH)_2 and bulk SO_2 concentration.

$$\text{Gas film resistance (\%)} = \frac{12.8 \text{ Pa}}{P_{\text{SO}_2}} \frac{F^{1/3}}{1 - F^{1/3}} \times 100 \quad (5-14)$$

Figure 5-16 shows the relationship between gas film resistance and Ca(OH)_2 utilization for several SO_2 concentrations. The results show that the absorption of SO_2 is primarily liquid film controlled at moderate to high levels of Ca(OH)_2 utilization. This confirms the results determined by the slurry absorption model that were previously shown in Figure 5-13. It should be remembered, however, that the model and the expression in equation (5-14) do not account for the change in Ca(OH)_2 concentration in the slurry droplet that occurs when evaporation is considered. Higher degrees of gas film resistance would be expected when this phenomenon is included in the analysis.

5.4.4 Effect of Varied Ca(OH)_2 Reactivity

Three slurries of 0.1 M Ca(OH)_2 were prepared, each using a different source of Ca(OH)_2 , and absorption of SO_2 was measured in each slurry. Enhancement factors from the first two experiments were compared but showed that little difference in enhancement was measured. This enabled comparison of further tests performed with Mississippi Ca(OH)_2 to those performed with reagent grade Ca(OH)_2 since the two sources of Ca(OH)_2 showed the same reactivity toward SO_2 . Another test using freshly slaked Mississippi lime slurry at a concentration of 0.1 M Ca(OH)_2 was run, but also showed little difference in measured enhancement.

Reactivity of the three Ca(OH)_2 slurries was not quantified by any other measurements. Measurements of particle size and surface area are difficult to make on solids which are suspended in the slurry. Drying the slurry would yield agglomerated particles, which would not be representative of

Figure 5-16. Gas film resistance as a function of Ca(OH)_2 utilization: using $\text{DI } \Delta[\text{S(IV)}] = 7.0 \times 10^{-8} \text{ mole/m s}$ (equation 5-14).

the particles as they exist in the slurry. Although properties of the particles in the three types of slurry were not measured, it is unlikely that all three types had very similar particle sizes, surface areas, and other properties which influence reactivity toward SO_2 . It is more likely that enhancement, as measured in the stirred tank, is not very sensitive to changes in properties of $\text{Ca}(\text{OH})_2$ particles.

5.4.5 Slurry Absorption Model Validation

Only two inputs to the slurry absorption model determine the nature of the slurry: solids concentration and particle size. The remaining inputs to the model were assumed to be the same as for the 17 mM $\text{Ca}(\text{OH})_2$ solution. The stirred tank experimental results in 35 mM $\text{Ca}(\text{OH})_2$ slurry supported the use of a diffusivity of the hydroxide ion reduced to 40 percent, as suggested by clear solution experiments in 17 mM $\text{Ca}(\text{OH})_2$.

The model was run at conditions representing the stirred tank for the slurry concentrations of 35 mM, 0.1 M, 0.4M, and 1.0 M $\text{Ca}(\text{OH})_2$ using several particle sizes. Experimentally determined enhancement factors and those predicted by the model agreed well for the slurries of less than 0.1 M $\text{Ca}(\text{OH})_2$. Assuming that a particle size on the order of 1 to 5 μm is reasonable for $\text{Ca}(\text{OH})_2$ slurry, the model overpredicted the enhancement measured in the stirred tank with slurries containing over 0.1 M $\text{Ca}(\text{OH})_2$.

Experimental results showed that the amount of enhancement attributed to adding more solids appeared to diminish as the slurry solids concentration was increased. In other words, the increases in enhancement were not proportional to the additional amount of solids added. The slurry absorption model predicted this behavior also, but it predicted that the slurries should have been more reactive than the results of the stirred tank experiments indicated. One explanation for this discrepancy is that solids may have been settling out of the boundary layer during experiments. Enhancement measured in the stirred tank would then be low as solids content was increased, since the model does not account for this behavior. It is currently not known whether solids settling influences absorption in slurry droplets.

In many cases, the model predicted that changes in particle size produced only minor differences in the enhancement factor. Changing the particle size from 1 to 5 μm showed little effect on enhancement for slurries of 35 mM, 0.1 M and 0.4 M Ca(OH)_2 . This appears to confirm that such changes in particle size or surface area may have little effect on the enhancement factor. This supports the conclusions drawn earlier from the comparison of the three types of Ca(OH)_2 studied.

SECTION 6

COMPUTER MODELING

6.1 MODEL

The model includes three rate phenomena which all depend on the solution composition:

- Dissolution of $\text{Ca}(\text{OH})_2$
- Crystallization of CaSO_3
- Absorption of SO_2

These rates cannot be separated from each other. To calculate the dissolution rate and the crystallization rate, we need the bulk solution composition which depends on the amount of absorbed SO_2 and vice versa.

6.1.1 Equilibria

The model assumes instantaneous equilibrium of the species H^+ , H_2O , OH^- , SO_2 , HSO_3^- and SO_3^{2-} . This assumption gives the following equilibria which apply throughout the liquid.

$$K_1 = \frac{a_{\text{H}^+} a_{\text{HSO}_3^-}}{a_{\text{SO}_2}} \quad (6-1)$$

$$K_2 = \frac{a_{\text{H}^+} a_{\text{SO}_3^{2-}}}{a_{\text{HSO}_3^-}} \quad (6-2)$$

$$K_W = a_{\text{H}^+} a_{\text{OH}^-} \quad (6-3)$$

The liquid is saturated with SO_2 at the gas liquid interface.

$$H = \frac{P_{\text{SO}_2}}{a_{\text{SO}_2}} \quad (6-4)$$

The model takes into account two ion pairs CaOH^+ and CaSO_3° .

$$K_{\text{CaOH}^+} = \frac{a_{\text{Ca}^{2+}} a_{\text{OH}^-}}{a_{\text{CaOH}^+}} \quad (6-5)$$

$$K_{\text{CaSO}_3^\circ} = \frac{a_{\text{Ca}^{2+}} a_{\text{SO}_3^{2-}}}{a_{\text{CaSO}_3^\circ}} \quad (6-6)$$

At the Ca(OH)_2 surface the following equilibria is assumed to be valid:

$$K_{sp\text{Ca(OH)}_2} = a_{\text{Ca}^{2+}} a_{\text{OH}^-}^2 \quad (6-7)$$

The solubility product of calcium sulfite is equal to:

$$K_{sp\text{CaSO}_3} = a_{\text{Ca}^{2+}} a_{\text{SO}_3^{2-}} \quad (6-8)$$

Equilibrium constants, activity coefficients and the initial bulk concentrations of the slurry are calculated by the Bechtel Modified Radian Equilibrium Program, BMREQ (Epstein, 1975; Lowell et al., 1970). The BMREQ program is only called once as the equilibrium constants and activity coefficients are assumed to be approximately constant throughout the absorption process.

6.1.2 Ca(OH)_2 Dissolution

The Ca(OH)_2 dissolution rate is calculated by steady state mass transfer theory. The Ca(OH)_2 particles are assumed as spherical particles in an infinite stagnant solution. We also assume the electrical potential gradient to be very small so the diffusion constants are constant. The differential

material balance for total calcium at steady state in spherical coordinates gives, if it is assumed that there is no precipitation of calcium sulfite in the liquid film:

$$\sum_{i=1}^3 -D_i \frac{\partial}{\partial r} \left[r^2 \frac{\partial C_i}{\partial r} \right] = 0 \quad i = Ca^{2+}, CaOH^+, CaSO_3^0 \quad (6-9)$$

Similar material balances can be set up for the sum of S(IV) species and for the charge. The net production of S(IV) is zero if there is no precipitation of $CaSO_3$, and it is also assumed that the net production of charge is equal to zero. Substituting $y=d/2r$, where d is the particle diameter and r is the distance from the center of the sphere, transforms the material balances into very simple differential equations. The differential material balances for total calcium, S(IV) species and for the charge can easily be integrated to the following expressions:

$$D_{Ca^{2+}} C_{Ca^{2+}} + D_{CaOH^+} C_{CaOH^+} + D_{CaSO_3^0} C_{CaSO_3^0} = \alpha_1 + \beta_1 y \quad (6-10)$$

$$D_{SO_2} C_{SO_2} + D_{HSO_3^-} C_{HSO_3^-} + D_{SO_3^{2-}} C_{SO_3^{2-}} + D_{CaSO_3} C_{CaSO_3} = \alpha_2 + \beta_2 y \quad (6-11)$$

$$2 D_{Ca^{2+}} C_{Ca^{2+}} + D_{CaOH^+} C_{CaOH^+} + D_{H^+} C_{H^+} - D_{OH^-} C_{OH^-} - D_{HSO_3^-} C_{HSO_3^-} - 2 D_{SO_3^{2-}} C_{SO_3^{2-}} - D_{Cl^-} C_{Cl^-} = \alpha_3 + \beta_3 y \quad (6-12)$$

where α_i and β_i are integration constants

There is no flux of S(IV) species and the flux of charge is equal to zero since the electrical gradient is assumed to be negligible. Constants β_2 and β_3 are therefore also equal to zero. Constants α_1 , α_2 and α_3 are calculated from the boundary conditions in the liquid bulk. When α_1 , α_2 and α_3 are determined, the constant β_1 can be calculated from the boundary condition at the $Ca(OH)_2$ surface by assuming equation (6-7) to be valid, giving the following equations:

$$\beta_1 = \sum_{i=1}^3 D_i (C_{is} - C_{ib}) = D\Delta C \quad i = \text{Ca}^{2+}, \text{CaOH}^+, \text{CaSO}_3^0 \quad (6-13)$$

$$\sum_{i=1}^4 D_i C_i = \sum_{i=1}^4 D_i C_{ib} \quad i = \text{SO}_2, \text{HSO}_3^-, \text{SO}_3^{2-}, \text{CaSO}_3^0 \quad (6-14)$$

$$\sum_{i=1}^n z_i D_i C_i = \sum_{i=1}^n z_i D_i C_{ib} \quad n = \text{all species present} \quad (6-15)$$

where index s refers to the $\text{Ca}(\text{OH})_2$ surface and index b refers to the liquid bulk.

These equations make it possible to calculate the flux of total calcium, $2D\Delta C/d$ ($\text{mol/m}^2\text{s}$), from given bulk concentrations and equation (6-7). The dissolution rate from one sphere can be written as $2\pi dD\Delta C$ (mol/s). Due to the dissolution of $\text{Ca}(\text{OH})_2$, the volume of the $\text{Ca}(\text{OH})_2$ particles will decrease. The dissolution rate is thus time dependent since the mass transfer area of $\text{Ca}(\text{OH})_2$ decreases with time.

$$-\frac{dV}{dt} = \frac{2\pi d}{\rho_m} D\Delta C \quad (6-16)$$

$$V(t) = V_0 \left(1 - \frac{8}{d_0^2 \rho_m} \int_0^t D\Delta C(t) dt \right)^{1.5} \quad (6-17)$$

where V_0 is the initial volume of the spheres with diameter d_0 (m^3) and ρ_m is the molar density of $\text{Ca}(\text{OH})_2$ (mol/m^3)

For a polydisperse size distribution, where ϕ_j is the fraction of total initial particle volume with initial diameters from d_j to d_{j+1} , the change in total volume is:

$$(6-18)$$

$$V_{tot}(t) = V_{tot0} \sum_{j=1}^N \left[\phi_j \left(1 - \frac{8}{\rho_m} \frac{1}{d_j d_{j+1}} \int_0^t D \Delta C(x,t) dt \right)^{1.5} \right]$$

The consumption of hydroxide ions is not uniform through the slurry during the SO₂ absorption. Near the gas-liquid interface, the concentration of Ca(OH)₂ decreases quickly, whereas closer to the liquid bulk where the pH still is high the concentration of Ca(OH)₂ decreases slowly. The dissolution rate is thus dependent on both time, t, and the distance, x, from the gas liquid interface.

$$R_d(x,t) = \frac{\rho_m}{V_{slurry}} \frac{dV_{tot}}{dt} \quad (6-19)$$

$$R_d(x,t) = \frac{12 C_0}{\rho_m} D \Delta C(x,t) \sum_{j=1}^N \left[\phi_j \frac{1}{d_j d_{j+1}} \left(1 - \frac{8}{\rho_m} \frac{1}{d_j d_{j+1}} \int_0^t D \Delta C(x,t) dt \right)^{0.5} \right] \quad (6-20)$$

$$C_0 = \rho_m \frac{V_{tot0}}{V_{slurry}} \quad (6-21)$$

where $R_d(x,t)$ is the dissolution rate and (mol/m³s) and C_0 is the initial molar concentration of Ca(OH)₂ (mol/m³).

6.1.3 CaSO₃ Crystallization

Calcium sulfite will precipitate in the liquid film during the absorption. The supersaturation of CaSO₃, RS_{CaSO_3} , is defined as:

$$RS_{CaSO_3} = \frac{a_{Ca^{2+}} a_{SO_3^{2-}}}{K_{sp} CaSO_3} \quad (6-22)$$

If the magnitude of the supersaturation is below unity, calcium sulfite will dissolve instead of precipitate. The crystallization/dissolution rate, R_c , can be written as a function of the supersaturation of CaSO_3 , (Tseng and Rochelle, 1986; Gleason and Rochelle, 1987):

$$R_c = 1.62 \cdot 10^{-1} \exp(-5153/T) (RS_{\text{CaSO}_3} - 1)^n A / RS_{\text{CaSO}_4} \quad (\text{mol} / \text{m}^3 \text{ s}) \quad (6-23)$$

where A is the BET surface area of calcium sulfite per volume slurry.

Tseng and Rochelle found the crystallization rate to be second order relative to the supersaturation of CaSO_3 , $n=2$. Gleason and Rochelle (1987) found the reaction order to be 3 instead of 2. The cubic dependence was especially significant for high supersaturations. In this modeling work the exponent 3 was chosen because of high supersaturations of calcium sulfite near the gas-liquid interface during the absorption process. From Gleason's data, the rate constant should be approximately the same even though the reaction order in Tseng's equation is changed from 2 to 3. The value of the supersaturation of calcium sulfate is set at 0.025. The BET surface area of calcium sulfite is assumed to be $10 \text{ m}^2/\text{g}$. The total area of calcium sulfite per volume of slurry is calculated from the following equation:

$$A = 10 \bar{M}_{\text{CaSO}_3} C_{\text{CaSO}_3} \quad (\text{m}^2 / \text{m}^3) \quad (6-24)$$

where $\bar{M}_{\text{CaSO}_3}$ is the molar weight for CaSO_3 , 120 g/mol.

The crystallization rate, R_c , is in the same way as the dissolution rate of $\text{Ca}(\text{OH})_2$ a function of both time, t , and the distance, x , from the gas liquid interface.

6.1.4 SO_2 Absorption

The absorption of SO_2 is modeled with the penetration model, which assumes that liquid elements rise from the turbulent bulk liquid up to the gas liquid interface, where the elements are exposed for the same length of time, θ , before being replaced by liquid of the bulk composition. Initially, the concentration of dissolved gas in the liquid element is uniform, C_0 , and, internally, the element is considered to be stagnant. When the element is exposed to the gas at the surface, the

concentration in the liquid at the gas-liquid interface is C_i , which is the equilibrium solubility of the gas in the liquid. During the time θ , the liquid element is subject to unsteady-state diffusion of solute in the x direction (Danckwerts, 1970, Treybal, 1980).

The unsteady state material balance for each species is:

$$\frac{\partial C_i}{\partial t} = - \nabla J_i + r_i \quad (6-25)$$

$$J_i = z_i D_i \frac{F}{RT} C_i \nabla \phi - D_i \nabla C_i \quad (6-26)$$

where ∇ is the first spatial derivative and J_i is the flux. The flux consists of two terms, one due to an electrical potential gradient, $\nabla \phi$, and the other due to a concentration gradient, ∇C_i . The electrical potential gradient can be calculated by assuming the total flux of charge being equal to zero (Glasscock, 1988).

$$\nabla \phi = \frac{RT}{F} \frac{\sum_{i=1}^n z_i D_i \nabla C_i}{\sum_{i=1}^n z_i^2 D_i C_i} \quad n = \text{all species present} \quad (6-27)$$

All the material balances with S(IV) species are combined to one differential equation, and all the material balances involving calcium species are combined. By doing this, we do not have to use rate constants fixed at arbitrarily high values for the equilibrium reactions.

$$\frac{\partial C_{S(IV)}}{\partial t} = \sum_{i=1}^4 \left(D_i \nabla^2 C_i - z_i D_i \frac{F}{RT} \nabla (C_i \nabla \phi) \right) - R_d(x,t) \quad (6-28)$$

$i = \text{SO}_2, \text{HSO}_3^-, \text{SO}_3^{2-}, \text{CaSO}_3^0$

$$\frac{\partial C_{Ca \text{ tot}}}{\partial t} = \sum_{i=1}^3 \left(D_i \nabla^2 C_i - z_i D_i \frac{F}{RT} \nabla (C_i \nabla \phi) \right) - R_d(x,t) + R_d(x,t) \quad (6-29)$$

$i = \text{Ca}^{2+}, \text{CaOH}^+, \text{CaSO}_3^0$

(6-30)

$$\frac{\partial C_{Cl}}{\partial t} = D_{Cl} \nabla^2 C_{Cl} + D_{Cl} \frac{F}{RT} \nabla (C_{Cl} \nabla \phi)$$

This way of treating the problem is more advantageous because it reduces the number of differential equations to be solved. The concentration profiles of S(IV) and total calcium can be treated more effectively than, for example, the concentration profile of hydrogen ion. The hydrogen ion concentration profile is very steep at some points in the liquid film and flat at other regions, depending on the buffering species present, whereas the S(IV) and total calcium profiles should have a constant gradient. Individual concentrations can be calculated from the S(IV), total calcium, chloride concentrations and by assuming the sum of charge to be equal to zero. Due to the unsteady-state absorption, the interfacial concentration of SO₂ will not be constant even though the partial pressure of SO₂ in the gas bulk is constant. The absorption rate of SO₂ is equal to the sum of S(IV) fluxes at the gas liquid interface. This must also be equal to the flux of SO₂ in the gas film.

(6-31)

$$N_{SO_2} = J_{S(IV)}$$

(6-32)

$$k_g (P_{SO_2} - P_{SO_2,i}) = \sum_{i=1}^4 \left(z_i D_i \frac{F}{RT} C_i \nabla \phi - D_i \nabla C_i \right)$$

$i = SO_2, HSO_3^-, SO_3^{2-}, CaSO_3^0$

The flux of calcium and chloride must be equal to zero at the gas liquid interface.

(6-33)

$$0 = \sum_{i=1}^3 \left(z_i D_i \frac{F}{RT} C_i \nabla \phi - D_i \nabla C_i \right) \quad i = Ca^{2+}, CaOH^+, CaSO_3^0$$

(6-34)

$$0 = -D_{Cl} \frac{F}{RT} C_{Cl} \nabla \phi - D_{Cl} \nabla C_{Cl}$$

At $t=0$, when the liquid element is brought up to the interface the whole liquid element is assumed to be in equilibrium with a given SO₂ loading. The initial conditions and the boundary conditions are accordingly:

$$t \leq 0 \quad x \geq 0$$

$$C_{S(IV)} = C_{S(IV)0}$$

$$C_{Ca \text{ tot}} = C_{Ca \text{ tot } 0}$$

$$C_{Cl} = C_{Cl 0}$$

$$t \geq 0 \quad x = 0$$

flux of S(IV) - equation (37)

flux of Ca tot - equation (38)

flux of chloride - equation (39)

$$t \geq 0 \quad x = \infty$$

$$C_{S(IV)} = C_{S(IV) 0}$$

$$C_{Ca \text{ tot}} = C_{Ca \text{ tot } 0}$$

$$C_{Cl} = C_{Cl 0}$$

Index 0 refers to the initial slurry bulk conditions.

The absorption rate will vary with time. At the start when the liquid element is brought up to the surface, the absorption rate is large since the interfacial concentration of SO_2 is small. As the absorption proceeds, the concentration of SO_2 at the gas-liquid interface increases and the absorption rate decreases. The average absorption rate, which is what we measure from the stirred tank reactor experiments, is calculated from:

$$\overline{N_{SO_2}} = \frac{1}{\theta} \int_0^{\theta} N_{SO_2} dt \quad (6-35)$$

where θ is the total contact time

6.1.5 Numerical Solution

The computer code is written in FORTRAN 77 and is available both on a VAX computer and on a Cray computer. In order to solve the differential equations that describe the absorption process, the dissolution rate of Ca(OH)_2 , R_d , and the crystallization rate of CaSO_3 , R_c , need to be calculated.

The dissolution rate is a function of the flux of total calcium from the Ca(OH)_2 surface. The flux of total calcium is equal to the sum of concentration differences of the calcium species between the Ca(OH)_2 surface and the bulk, multiplied with the diffusion constants, $D\Delta C$. $D\Delta C$ is calculated from equations (6-13) to (6-14) by using the equilibria equations (6-1) to (6-3) and assuming the liquid to be saturated with Ca(OH)_2 at the Ca(OH)_2 surface.

To solve the equation system for the concentrations at the Ca(OH)_2 surface, all the concentrations are expressed in the concentrations of hydrogen and sulfite, by using the equilibria equations. That reduces the equation system down to two nonlinear equations, $f_1=0$ and $f_2=0$. These equations are solved iteratively according to the method of Gauss-Newton:

$$\begin{aligned} f_1(C_{H^+N+1}, C_{\text{SO}_3^{2-}N+1}) &= f_1(C_{H^+N}, C_{\text{SO}_3^{2-}N}) + (C_{H^+N+1} - C_{H^+N}) \left(\frac{\partial f_1}{\partial C_{H^+}} \right)_N \\ &\quad + (C_{\text{SO}_3^{2-}N+1} - C_{\text{SO}_3^{2-}N}) \left(\frac{\partial f_1}{\partial C_{\text{SO}_3^{2-}}} \right)_N \end{aligned} \quad (6-36)$$

$$\begin{aligned} f_2(C_{H^+N+1}, C_{\text{SO}_3^{2-}N+1}) &= f_2(C_{H^+N}, C_{\text{SO}_3^{2-}N}) + (C_{H^+N+1} - C_{H^+N}) \left(\frac{\partial f_2}{\partial C_{H^+}} \right)_N \\ &\quad + (C_{\text{SO}_3^{2-}N+1} - C_{\text{SO}_3^{2-}N}) \left(\frac{\partial f_2}{\partial C_{\text{SO}_3^{2-}}} \right)_N \end{aligned} \quad (6-37)$$

The above equations can be rewritten accordingly:

$$\begin{aligned}
C_{H^+N+1} \left(\frac{\partial f_1}{\partial C_{H^+}} \right)_N + C_{SO_3^{2-N+1}} \left(\frac{\partial f_1}{\partial C_{SO_3^{2-}}} \right)_N &= -f_1 (C_{H^+N}, C_{SO_3^{2-N}}) \\
+ C_{H^+N} \left(\frac{\partial f_1}{\partial C_{H^+}} \right)_N + C_{SO_3^{2-N}} \left(\frac{\partial f_1}{\partial C_{SO_3^{2-}}} \right)_N &
\end{aligned}
\tag{6-38}$$

$$\begin{aligned}
C_{H^+N+1} \left(\frac{\partial f_2}{\partial C_{H^+}} \right)_N + C_{SO_3^{2-N+1}} \left(\frac{\partial f_2}{\partial C_{SO_3^{2-}}} \right)_N &= -f_2 (C_{H^+N}, C_{SO_3^{2-N}}) \\
+ C_{H^+N} \left(\frac{\partial f_2}{\partial C_{H^+}} \right)_N + C_{SO_3^{2-N}} \left(\frac{\partial f_2}{\partial C_{SO_3^{2-}}} \right)_N &
\end{aligned}
\tag{6-39}$$

This is a linear equation system which is easily solved by Gauss-elimination. The difficult step is to choose suitable starting values of C_{H^+} and $C_{SO_3^{2-}}$ for the iteration.

When DAC is determined, the dissolution rate is calculated from equation (6-20). Notice that DAC has to be calculated for every (x,t) . The dissolution rate is a function of both the actual DAC and DAC integrated from 0 to t . The crystallization/dissolution rate of $CaSO_3$ rate is calculated from equation (6-23). Equations (6-20), (6-23), the equilibrium equations, and the given initial and boundary conditions are needed to solve the differential equations (6-28) to (6-30). The coupled nonlinear differential equations are solved by using orthogonal collocation on finite elements in the spatial dimension (Finlayson, 1980).

Orthogonal collocation transforms the partial differential equations in t and x into ordinary differential equations in t . Orthogonal collocation on finite elements involves division of the spatial region into suitable elements, smaller near the gas-liquid interface and larger near the liquid bulk. Each element is then divided into a number of collocation points.

The first and the second spatial derivative at any of these collocation points can be expressed in terms of the value of the function at the collocation points in that specific element. For example, the derivative of hydrogen ion is calculated as a polynomial of the hydrogen ion concentrations at the collocation points in that element.

$$Y' = A Y \quad (6-40)$$

$$Y'' = B Y \quad (6-41)$$

where A and B are $n \times n$ matrices with the coefficients in the collocation polynomials; Y is a vector with the function values at the collocation points $(y_1, y_2, \dots, y_n)$; Y' and Y'' are vectors with the first and second derivatives at the collocation points $(y_1', y_2', \dots, y_n')$ and $(y_1'', y_2'', \dots, y_n'')$

The coefficients in matrices A and B are calculated by a FORTRAN package DJACOBI. By introducing orthogonal collocation on finite elements the number of equations to be solved is increased, but PDE are transformed to ODE which makes the equations much easier to solve. At the collocation points representing the gas-liquid interface and the liquid bulk, there are three equations respectively for the boundary conditions, and there are three ODE at the other collocation points that are not shared between two elements. At the collocation points that are in common for two elements, $C_{S(IV)}$, $C_{Ca^{2+}}$ and C_{Cl} must have continuous derivatives.

$$\left(\frac{\partial C_i}{\partial x} \right)_{x_k^-} = \left(\frac{\partial C_i}{\partial x} \right)_{x_k^+} \quad (6-42)$$

This set of coupled ordinary differential algebraic equations is integrated through time by the FORTRAN package DDASSL.

Because the spatial region goes from zero to infinity, spatial transformation needs to be done. With the transformation suggested by Versteeg (1987), the calculation domain is restricted to the interval given by the penetration depth.

$$r = \operatorname{erf} \left(\frac{x}{\sqrt{4 D_{H^+} t}} \right) \quad (6-43)$$

$$x = 0 \rightarrow r = 0$$

$$x = \infty \rightarrow r = 1$$

This transformation has its origin in the analytical solution of the one-dimensional diffusion problem.

The maximum diffusion coefficient (hydrogen) is chosen in the transformation. The time is transformed according to the following equation:

$$\tau = \left(\frac{t}{\theta} \right)^{0.5} \quad (6-44)$$

This transformation is especially helpful in the beginning of the integration when t is very small. The concentration of all the individual species H^+ , SO_2 , Ca^{2+} , etc. are calculated from the concentrations of $S(IV)$, total calcium, and chloride and by assuming the sum of charge to be equal to zero. The equation system is reduced to two equations by expressing the concentrations in terms of hydrogen and sulfite. The nonlinear equation system is then solved iteratively according to the method of Gauss-Newton, described above.

Because of the spatial transformation, the collocation points are moving in space (x) when t is changing.

To calculate the dissolution rate of Ca(OH)_2 at the collocation points for a different t the value of the integral, $\Delta C \, dt$, must be estimated at the new x points. This can be done with a spline interpolation or with a linear approximation from the values corresponding to the earlier t . Both methods have been tested and gave approximately the same result. The linear approximation was chosen to reduce the computer time. The integral, $\Delta C \, dt$, is updated for each new time by the method of Euler. Euler is not the most accurate integration model, but since this integration is done at the same time as DDASSL is solving the differential equations, it is difficult to introduce a more sophisticated model. Updating of the concentration of $\text{CaSO}_3(\text{s})$ is done in a similar way. The gas film resistance is calculated as the average absorption rate divided by k_g and P_{SO_2} .

$$\frac{\overline{N_{\text{SO}_2}}}{k_g P_{\text{SO}_2}} = 1 - \frac{P_{\text{SO}_2 \text{I}}}{P_{\text{SO}_2}} \quad (6-45)$$

The gas film resistance is thus a normalized flux which makes it possible for us to compare results for cases with different P_{SO_2} and different mass transfer coefficients. The gas film resistance is also a ratio between the average flux and the maximum flux for that specific case. If the absorption is totally gas film controlled, the gas film resistance is equal to one, and the absorption rate can not further be increased by any chemical reaction in the absorbing liquid. A gas film resistance of 50 percent implies that, up to this point, the slurry has absorbed 50 percent of the amount that could have been absorbed if the process was totally gas film controlled.

The modeling results are often presented as a function of contact time. The contact time is the time the liquid element stays at the gas liquid interface before it is transported back to the liquid bulk and is related to the liquid mass transfer coefficient by the following equation based on the penetration theory.

$$k_l = 2 \sqrt{\frac{D_l}{\pi t}} \quad (6-46)$$

The contact time can also be thought of as the contact time for a slurry droplet in a spray dryer if the droplet is considered to be stagnant.

Another variable, called the penetration distance, is used. This is the distance from the gas liquid interface to the point where the concentration of $\text{Ca(OH)}_2(\text{s})$ is half of the concentration of $\text{Ca(OH)}_2(\text{s})$ in the liquid bulk. This distance also defines the size of the liquid film since almost all the concentrations are maintained at the bulk conditions as long as $\text{Ca(OH)}_2(\text{s})$ is present. The penetration distance is also a measure of the amount of consumed lime.

6.1.6 Modeling Conditions

Equilibrium constants, activity coefficients and the initial bulk concentrations of the slurry are calculated by the Bechtel Modified Radian Equilibrium Program, BMREQ (Epstein, 1975). The BMREQ program is only called once as the equilibrium constants and activity coefficients are assumed to be approximately constant throughout the absorption process.

For a given pH value, the program calculates the other concentrations assuming that the solution is in equilibrium with $\text{Ca(OH)}_2(\text{s})$ and $\text{CaSO}_3(\text{s})$. The chloride concentration is iterated until the charge balance is valid.

The slurry conditions for the modeling results are given in Tables 6-1 and 6-2. The bulk concentrations of the ions have been the same for all the modeling results presented in this report. The initial concentration of $\text{CaSO}_3(\text{s})$ was also kept constant at 10 mol/m^3 . The concentration of $\text{Ca(OH)}_2(\text{s})$ was varied from 0 to $1,000 \text{ mol/m}^3$. The partial pressure of SO_2 ranged from 500 to 5,000 ppm. The reactivity of $\text{Ca(OH)}_2(\text{s})$ was varied by changing the particle size of $\text{Ca(OH)}_2(\text{s})$ from 0.5 to $5 \mu\text{m}$. Values of the equilibrium constants are listed in Table 6-3. The K_{SP} of CaSO_3 was set at 55 percent of the BMREQ value.

During these calculations, two values of k_g , 1.1×10^{-3} and $1.1 \times 10^{-4} \text{ mol/m}^2 \text{ s Pa}$ have been used. These correspond to a slurry droplet size of 10 and $100 \mu\text{m}$, respectively. The corresponding droplet size is calculated from a Sherwood number equal to two.

(6-47)

$$\frac{k_c d_p}{D} = 2$$

The above equation is valid for a slurry droplet when the droplet reaches the same velocity as the surrounding gas. In a spray dryer, the droplets reach the terminal velocity almost immediately. When the fluid around the droplet is stagnant, mass transfer occurs only by molecular diffusion, (Sherwood et al., 1975). The diffusivity of SO_2 in a flue gas is $1.5 \times 10^{-5} \text{ m}^2/\text{s}$ (Jozewicz and Rochelle, 1984). The gas film coefficients (k_g) corresponding to slurry droplets of $10 \mu\text{m}$ and $100 \mu\text{m}$ are $1.067\text{E-}3$ and $1.067\text{E-}4 \text{ mol/m}^2 \text{ Pa s}$, respectively.

TABLE 6-1. TYPICAL BULK SOLUTION COMPOSITION AND ACTIVITY COEFFICIENTS

Species	Concentration (mol/m ³)	Activity Coefficient
H ⁺	0.3060E-8	0.8457
OH ⁻	0.3456E-2	0.8113
SO ₂	0.9219E-15	1.0088
HSO ₃ ⁻	0.3171E-5	0.8116
SO ₃ ⁼	0.9131E-1	0.4340
Ca ²⁺	0.1454E-2	0.4449
CaSO ₃ ^o	0.9058	1.0088
CaOH ⁺	0.6414E-1	0.8113
Cl ⁻	0.7509	0.8068
RS _{Ca(OH)2}		1.0
RS _{CaSO3}		1.0

TABLE 6-2. RANGE OF SLURRY CONDITIONS

Ca(OH) ₂ (s)	0 - 1,000 mol/m ³
CaSO ₃ (s)	10 mol/m ³ (always)
pm Ca(OH) ₂	0.135E-5 ml/m ³
d _p	0.5 - 5 μm

TABLE 6-3. EQUILIBRIUM CONSTANTS AT 55 °C

	Activity Based	Concentration Based	Units
Henry	218	220.1	Pa m ³ /mol
KSO ₂	7.17	1.053E-2	mol/m ³
KHSO ₃	3.99E-5	0.8813E-4	mol/m ³
KW	7.3E-8	0.1058E-6	(mol/m ³) ²
KCaOH	34.86	0.7835E-2	mol/m ³
KCaSO ₃	0.28	0.1466E-1	mol/m ³
KSPCaSO ₃	5.1E-3	0.1328E-1	(mol/m ³) ² ~55% of BMREQ value
KSPCa(OH) ₂	0.256	0.1735E-5	(mol/m ³) ³

6.2 MODELING RESULTS

6.2.1 Ca(OH)₂ Reactivity

The reactivity of Ca(OH)₂ has been altered by changing the particle size of the Ca(OH)₂ particles in the slurry. The particle size ranged from 0.2 µm to 5 µm. Figures 6-1 and 6-2 show how the gas film resistance varies with contact time for different Ca(OH)₂ reactivities. In the modeling of the results in Figure 6-1, k_g was set at a value corresponding to a 100 µm slurry droplet. The corresponding droplet size for the results in Figure 6-2 is 10 µm.

Initially all the resistance to mass transfer is concentrated in the gas film since the concentration of SO₂ in the liquid is approximately zero. During the absorption, hydrogen ions are produced and Ca(OH)₂ dissolves to neutralize the formed hydrogen ions. If the dissolution of Ca(OH)₂ is not fast enough or if the concentration of Ca(OH)₂ approaches zero, the pH at the gas liquid interface decreases, and the gas film resistance decreases.

The dissolution rate of Ca(OH)₂ increases with decreasing pH so the consumption of Ca(OH)₂ will be largest close to the gas-liquid interface. Because of the nonuniform consumption of Ca(OH)₂, a concentration profile of Ca(OH)₂ is formed. When the concentration of Ca(OH)₂ close to the gas liquid interface eventually becomes zero, calcium ions have to be transported from the region where Ca(OH)₂

Figure 6-1. The gas film resistance versus the contact time. The different curves correspond to different particle sizes of Ca(OH)_2 . 200 Pa SO_2 , 0 and 200 mol/m³ Ca(OH)_2 , 100 μm droplet, 0.5-5.0 μm Ca(OH)_2 , 0.1-10 s contact time.

Figure 6-2. The gas film resistance versus the contact time. The different curves correspond to different particle sizes of Ca(OH)_2 . 200 Pa SO_2 , 0 and 200 mol/m³ Ca(OH)_2 , 10 μm droplet, 0.5-5.0 μm Ca(OH)_2 , 0.1-10 s contact time.

still remains toward the gas liquid interface to react with SO_2 . The gas film resistance is then less dependent on the reactivity of Ca(OH)_2 since there also must be a transportation of calcium. The concentration profile of Ca(OH)_2 becomes steeper with time since the dissolution rate is larger where there is a low Ca(OH)_2 concentration. The steeper the Ca(OH)_2 profile is, the less dependent is the actual absorption rate on the reactivity of Ca(OH)_2 . When a step-concentration profile of Ca(OH)_2 is developed, the gas-liquid concentration of SO_2 is almost constant, which implies that the absorption rate of SO_2 is approximately stable. The absorption process has reached a form of steady-state. The reactivity of Ca(OH)_2 thus has less significance for a large contact time in a spray scrubber or for a small k_l in the stirred tank. This can be seen in Figures 6-1 and 6-2.

The absorption rate can be increased up to a certain point by decreasing the particle size of Ca(OH)_2 . In Figure 6-1, the absorption rate is increased when the particle size is decreased from 5 μm to 2 μm , but the absorption rate is not increased when the particle size goes from 2 μm to 0.5 μm . The reason for this is that 2 μm Ca(OH)_2 is reactive enough to neutralize all the formed hydrogen ions, in other words to react with all absorbed SO_2 to calcium sulfite. After 0.4 s, a sharp concentration profile of Ca(OH)_2 is formed and the absorption is less dependent on the reactivity. The same sharp concentration profile is formed for 0.5 μm as for 2 μm .

For a smaller slurry droplet size, corresponding to a smaller value of k_g , the Ca(OH)_2 has to be more reactive to increase the absorption rate, Figure 6-2. The relation between Ca(OH)_2 reactivity and k_g is thus an important parameter. This relation can be expressed as a quotient between the particle size of Ca(OH)_2 and the slurry droplet size.

6.2.2 Concentration Profiles Without $\text{Ca(OH)}_2(\text{s})$ in the Liquid Bulk

Figures 6-3 and 6-4 show the concentration profiles for an absorption case without any $\text{Ca(OH)}_2(\text{s})$ in the liquid bulk. These profiles take 1.6 s to be formed, and they correspond to an instantaneous gas film resistance of 45 percent. The partial pressure of SO_2 is 2,000 ppm and k_g is $1.1 \times 10^{-4} \text{ mol/m}^2 \text{ s Pa}$.

Figure 6-3. Concentrations profiles corresponding to 45 percent gas film resistance. No $Ca(OH)_2$ (s) in the liquid bulk. 200 Pa SO_2 , 100 μm droplet, 1.6 sec contact time.

Figure 6-4. Concentration profiles corresponding to a gas film resistance of 45 percent. No $\text{Ca}(\text{OH})_2$ (s) in the liquid bulk. 200 Pa SO_2 , 100 μm droplet, 1.6 sec contact time.

From Figure 6-3, we can see that SO_2 reacts instantaneously with water at the gas-liquid interface to form hydrogen ions and bisulfite ions. The absorbed SO_2 also reacts with some sulfite forming bisulfite. These two reactions enhance the absorption rate of SO_2 since they decrease the concentration of SO_2 in the liquid. The SO_2 and H^+ concentration decreases rapidly with the distance from the gas-liquid interface. At a distance approximately $10\ \mu\text{m}$ from the gas-liquid interface, there is a drastic change in pH. The concentration of hydroxide increases, and the hydroxide ions react with bisulfite ions to form sulfite. Therefore the sulfite concentration increases and the bisulfite concentration decreases.

Figure 6-4 shows the profiles for the ions involving calcium and the two ion pairs. The Ca^{2+} is approximately constant throughout the liquid film, the ion pairs CaOH^+ and CaSO_3^0 follow the profiles of OH^- and SO_3^{2-} , respectively. Approximately 50 percent of the sulfite ions are present as the ion pair CaSO_3^{2-} . There is also some precipitation of $\text{CaSO}_3(\text{s})$ since sulfite is produced during the absorption.

6.2.3 Concentration Profiles With $\text{Ca}(\text{OH})_2(\text{s})$ in the Bulk Liquid

Figures 6-5 and 6-6 show the profiles for the same absorption case as above when the bulk concentration of $\text{Ca}(\text{OH})_2(\text{s})$ is $500\ \text{mol/m}^3$. These profiles also correspond to a gas film resistance of 45 percent, but, since the presence of $\text{Ca}(\text{OH})_2(\text{s})$ maintains a high gas film resistance a longer time, it takes 8.1 s until these profiles are formed. Figure 6-5 with the profiles of H^+/OH^- and $\text{SO}_2/\text{HSO}_3^-/\text{SO}_3^{2-}$ looks approximately the same as Figure 6-3. The increase in pH is occurring closer to the gas-liquid interface in Figure 6-5, $5\ \mu\text{m}$ instead of $10\ \mu\text{m}$, but otherwise there is no significant difference between Figure 6-5 and Figure 6-3.

It can be seen from Figure 6-6 that $\text{Ca}(\text{OH})_2(\text{s})$ is totally consumed at the gas liquid interface. There is no $\text{Ca}(\text{OH})_2(\text{s})$ until the distance from the gas-liquid interface exceeds $50\ \mu\text{m}$. The concentration of Ca^{2+} is approximately constant throughout the film. The CaSO_3 ion pair has a significant concentration due to a very large supersaturation of calcium sulfite. A significant amount of $\text{CaSO}_3(\text{s})$ precipitates during the absorption, since Ca^{2+} ions are formed from the dissolution of

Figure 6-5. Concentration profiles corresponding to 45 percent gas film resistance with $Ca(OH)_2$ (s) in the liquid bulk. 200 Pa SO_2 , 500 mol/m³ $Ca(OH)_2$, 100 μ m droplet, 2.0 μ m $Ca(OH)_2$, 8.1 sec contact time.

Figure 6-6. Concentration profiles corresponding to 45 percent gas film resistance with $\text{Ca(OH)}_2 \text{ (s)}$ in the liquid bulk. 200 Pa SO_2 , 500 mol/m³ Ca(OH)_2 , 100 μm droplet, 2.0 μm Ca(OH)_2 , 8.1 sec contact time.

$\text{Ca(OH)}_2(\text{s})$ and SO_3^{2-} ions are formed from the reaction between SO_2 and OH^- ions. It is significant that CaSO_3 crystallizes close to the gas-liquid interface where no $\text{Ca(OH)}_2(\text{s})$ is present.

Figure 6-7 shows how the concentration profile of $\text{Ca(OH)}_2(\text{s})$ varies with contact time. The $\text{Ca(OH)}_2(\text{s})$ is consumed during the absorption, making the $\text{Ca(OH)}_2(\text{s})$ front move away from the gas liquid interface. Figure 6-7 can also exemplify the penetration distance. For a contact time of 0.4 s, the penetration distance is equal to 10 μm .

6.2.4 Partial Pressure of SO_2 at the Gas-Liquid Interface

During the absorption of SO_2 into a slurry of calcium hydroxide, the partial pressure of SO_2 at the gas-liquid interface increases, causing the absorption rate to decrease. At the start of the absorption, $P_{\text{SO}_{2\text{i}}}$ is equal to zero when the absorption process is gas film controlled. When $P_{\text{SO}_{2\text{i}}}$ increases, the absorption rate decreases, and the absorption becomes more liquid film controlled. The partial pressure of SO_2 at the interface starts to increase when all the hydroxide ions are consumed close to the interface.

Figure 6-8 shows how the $P_{\text{SO}_{2\text{i}}}$ varies with contact time for the same conditions as in Figure 6-5 and 6-6. The different numbers in Figure 6-8 correspond to the penetration distance for that contact time. The driving force for mass transfer, which is the difference between the two curves of P_{SO_2} and $P_{\text{SO}_{2\text{i}}}$, is large for small contact times but decreases with increasing time. The absorption is totally gas film controlled up to 1 s, or to a penetration distance of 20 μm . After 1 s, $P_{\text{SO}_{2\text{i}}}$ starts to increase, and the gas film resistance decreases. The $P_{\text{SO}_{2\text{i}}}$ increases quickly up to 1500 ppm. Thereafter, a kind of steady state is developed where the $P_{\text{SO}_{2\text{i}}}$ is approximately constant even though the penetration distance increases from 45 to 70 μm . After about 6 s, the average gas film resistance is 50 percent, while the instantaneous gas film resistance is only 25 percent.

6.2.5 Effects of $\text{Ca(OH)}_2(\text{s})$ Concentration

Figure 6-9 shows how the gas film resistance varies with different concentrations of $\text{Ca(OH)}_2(\text{s})$. The partial pressure of SO_2 is 2,000 ppm, and k_g is $1.1 \times 10^{-4} \text{ mol/m}^2 \text{ s Pa}$. The reactivity of $\text{Ca(OH)}_2(\text{s})$ is 5 μm . At higher concentrations of $\text{Ca(OH)}_2(\text{s})$, it takes a longer time for the $\text{Ca(OH)}_2(\text{s})$

Figure 6-7. Concentration profiles of Ca(OH)_2 (s). 200 Pa SO_2 , 500 mol/m³ Ca(OH)_2 , 100 μm droplet, 2 μm Ca(OH)_2 .

Figure 6-8. The partial pressure of SO_2 at the gas-liquid interface as a function of contact time. The numbers are corresponding penetration depths. 200 Pa SO_2 , 500 mol/m³ $Ca(OH)_2$, 100 μm droplet, 2 μm $Ca(OH)_2$.

Figure 6-9. Gas film resistance versus contact time for different concentrations of Ca(OH)_2 (s). 200 Pa SO_2 , 100 μm droplet, 5 μm Ca(OH)_2 .

front to move away from the gas-liquid interface, which means that the absorption can be maintained at a high rate for a longer time. When there is no $\text{Ca(OH)}_2(\text{s})$ present in the liquid bulk, the gas film resistance is only 60 percent after 0.1 s, whereas for a $\text{Ca(OH)}_2(\text{s})$ concentration of $1,000 \text{ mol/m}^3$, the gas film resistance is larger than 60 percent up to a contact time of 6 s. Similar results are given in Figure 6-10 for a particle of $2 \text{ }\mu\text{m}$.

6.2.6 Effects of Different Partial Pressures of SO_2

Figure 6-11 shows how the gas film resistance varies with different partial pressures of SO_2 in the bulk gas. The concentration of $\text{Ca(OH)}_2(\text{s})$ is 500 mol/m^3 and k_g is $1.1 \times 10^{-4} \text{ mol/m}^2 \text{ s Pa}$. The reactivity of $\text{Ca(OH)}_2(\text{s})$ corresponds to a particle size of $2 \text{ }\mu\text{m}$. At higher partial pressures of SO_2 , more SO_2 is absorbed and the $\text{Ca(OH)}_2(\text{s})$ is consumed faster.

6.2.7 Effects of $\text{Ca(OH)}_2(\text{s})$ Reactivity

Figures 6-12 and 6-13 show how the $\text{Ca(OH)}_2(\text{s})$ reactivity affects the absorption rate of SO_2 . The gas film resistance is plotted versus the ratio between k_g and k_l for a k_g corresponding to a $100 \text{ }\mu\text{m}$ slurry droplet in Figure 6-12, and for a k_g corresponding to a $10 \text{ }\mu\text{m}$ slurry droplet in Figure 6-13. The partial pressure of SO_2 is 2,000 ppm, and the concentration of $\text{Ca(OH)}_2(\text{s})$ is 200 mol/m^3 . By plotting the gas film resistance versus k_g/k_l , the results would have been the same for different values of k_g , if all the reactions were instantaneous. Since the crystallization of $\text{CaSO}_3(\text{s})$ and the dissolution of $\text{Ca(OH)}_2(\text{s})$ have finite rates, the results shown in the two graphs are somewhat different. A contact time of 1 s for a $100 \text{ }\mu\text{m}$ slurry droplet corresponds to a contact time of 0.01 s for a $10 \text{ }\mu\text{m}$ slurry droplet. It follows that if the droplet size is decreased one order-of-magnitude, the contact time is decreased with two orders-of-magnitude needed to get the same ratio between k_g and k_l .

A higher reactivity increases the absorption rate. A higher reactivity also gives a faster dissolution rate, which can keep the pH at the gas liquid interface at a higher value as long as there is $\text{Ca(OH)}_2(\text{s})$ present.

Figure 6-10. The gas film resistance versus contact time for different Ca(OH)_2 (s) concentrations. 200 Pa SO_2 , 0-1,000 mol/m³ Ca(OH)_2 , 100 μm droplet, 2 μm Ca(OH)_2 , 0.1-10 sec contact time.

Figure 6-11. The gas film resistance versus contact time for different partial pressures of SO_2 . 50-500 Pa SO_2 , 500 mol/m^3 Ca(OH)_2 , $100 \mu\text{m}$ droplet, $2 \mu\text{m}$ Ca(OH)_2 .

Figure 6-12. Gas film resistance versus the ratio between k_g and k_l for different reactivities of Ca(OH)_2 (s). k_g corresponds to a 100 μm droplet. 200 Pa SO_2 , 200 mol/m³ Ca(OH)_2 , 100 μm droplet, 0.5-5 μm Ca(OH)_2 .

Figure 6-13. Gas film resistance versus the ratio between k_g and k_l for different reactivities of Ca(OH)_2 . k_g corresponds to a 10 μm droplet. 200 Pa SO_2 , 200 mol/m^3 Ca(OH)_2 , 10 μm droplet, 0.5-5 μm Ca(OH)_2 .

6.2.8 Penetration Distance

Figures 6-14 and 6-15 show how the gas film resistance varies with the penetration distance for different reactivities of $\text{Ca(OH)}_2(\text{s})$. The results in Figure 6-14 are modeled with a k_g corresponding to a 100 μm slurry droplet, and the results in Figure 6-15 correspond to a 10 μm slurry droplet. The partial pressure of SO_2 is 2,000 ppm, and the concentration of $\text{Ca(OH)}_2(\text{s})$ is varied from 200 up to 1,000 mol/m^3 .

For a given penetration distance, only the reactivity of $\text{Ca(OH)}_2(\text{s})$ is of importance for the gas film resistance. The concentration of $\text{Ca(OH)}_2(\text{s})$ affects how fast the penetration distance increases with time, but for 100 percent utilization of the lime, the average absorption rate is only dependent on the reactivity and not dependent on the concentration of $\text{Ca(OH)}_2(\text{s})$.

For the lower k_g , the absorption is totally gas film controlled as long as the penetration distance is smaller than 10 μm . For the larger k_g , the absorption rate is more dependent on the reactivity of $\text{Ca(OH)}_2(\text{s})$. For the low reactivity, 5 μm , the absorption is liquid film controlled even though the penetration distance is zero.

For a 100 μm slurry droplet, the maximum penetration distance would be 50 μm corresponding to a 100 percent utilization of the lime, meaning a gas film resistance of about 60, 50 and 30 percent for the three different reactivities. The maximum penetration distance in a 10 μm slurry droplet is 5 μm , which gives a gas film resistance of 40, 20 and 10 percent for the three reactivities in Figure 6-15. It is not reasonable to assume a Ca(OH)_2 particle size of 5 μm in a slurry droplet of 10 μm . Figures 6-14 and 6-15 only demonstrate how different reactivities affect the absorption rate for different values of k_g . For a smaller slurry droplet corresponding to a higher k_g , it is more important that Ca(OH)_2 is more reactive, or the dissolution rate will not "keep up with" the rate that hydrogen ions are produced during the absorption, and the gas film resistance will accordingly decrease.

Figure 6-16 shows that the partial pressure of SO_2 also has an effect on the gas film resistance for a given penetration depth. For a larger P_{SO_2} , the absorption rate is faster since the driving force is larger. For this reason, the lime has to be more reactive to give a high gas film resistance. For a P_{SO_2}

equal to 500 ppm, the absorption is gas film controlled when the penetration distance is smaller than 5 μm , whereas for a P_{SO_2} of 5,000 ppm the absorption is liquid film controlled even for very small penetration distances.

Figure 6-14. Gas film resistance versus penetration distance. 200 Pa SO_2 , 200-1,000 mol/m^3 Ca(OH)_2 , 100 μm droplet.

Figure 6-15. Gas film resistance versus penetration distance. 200 Pa SO_2 , 200-1,000 mol/m^3 Ca(OH)_2 , 10 μm droplet.

Figure 6-16. Gas film resistance versus penetration distance for different partial pressures of SO₂. 50-500 Pa SO₂, 200-1,000 mol/m³ Ca(OH)₂, 10 μm droplet, 0.5-5 μm Ca(OH)₂.

SECTION 7

CONCLUSIONS AND RECOMMENDATIONS

The theory, experiments and modeling activities of this research allowed for many conclusions to be made about absorption of SO_2 into $\text{Ca}(\text{OH})_2$ slurries, and validation of the slurry absorption model. Below is a summary of the conclusions that have been discussed throughout the preceding sections of this report.

During the course of this research, a number of areas which require additional study were identified. Several additional experiments are recommended to address assumptions made here. Recommendations are also made for modifying the slurry absorption model.

7.1 MASS TRANSFER THEORY

1. The surface renewal theory is the best available mass transfer model to use for describing the absorption of SO_2 into $\text{Ca}(\text{OH})_2$ slurries. Applied as the penetration theory (assuming constant contact times for slurry elements), absorption of SO_2 into slurries can be accurately predicted.
2. The enhancement factor (normalized flux) is a valuable basis for comparison of absorption. It was proven to be independent of contact time (or k_g) but strongly dependent on SO_2 concentration.

7.2 STIRRED TANK REACTOR EXPERIMENTS

1. The stirred tank was designed to maximize the gas film mass transfer coefficient, k_g , so that mass transfer would be similar to that of a slurry droplet, and experiments would not

be gas film controlled. However, k_g was an order-of-magnitude less than expected for a droplet, and some experiments were gas film controlled.

2. The liquid film coefficient, k_l , measured in the stirred tank, represented reasonable contact times between 0.7 and 6.6 s. For the range of slurry concentrations studied, k_l did not vary due to increased solids content (i.e., greater viscosity). Corrections to k_l may need to be made to slurries with greater than 1.0 M Ca(OH)_2 solids.
3. Changes to the bulk solution ionic strength of a 17 mM (saturated) Ca(OH)_2 solution did not show measurable changes to the enhancement factor for SO_2 absorption.
4. Gas film resistance began to control absorption of SO_2 in the reactor when enough solid Ca(OH)_2 were added to the $\text{Ca(OH)}_2/\text{CaCl}_2$ solution to form a slurry. Measurement of enhancement factors for SO_2 absorption in slurries could not be made at low SO_2 concentrations because gas film resistance was too high.
5. If experiments resulted in greater than 80 percent gas film controlled absorption, enhancement factors could not be calculated accurately. Thus, enhancement factors greater than about 200 could not be measured accurately in the stirred tank.
6. Enhancement measured from stirred tank experiments in clear solutions compared well with the surface renewal theory solutions proposed by Chang and Rochelle (1979) except for the case of a 17 mM Ca(OH)_2 solution.
7. Addition of Ca(OH)_2 solids greatly enhanced SO_2 absorption, although the increment of enhancement measured in the stirred tank diminished as the slurry solids concentration was increased.
8. Enhancement measured in slurry prepared from three different sources of Ca(OH)_2 was virtually the same. Pilot of full-scale test data are needed to confirm that there is no significant difference in reactivities among the three Ca(OH)_2 s.

7.3 MODEL VALIDATION

1. The slurry absorption model predicted enhancement factors that compared well with both the surface renewal theory solutions proposed by Chang and Rochelle (1979) and with the measured enhancement from clear solution experiments in the stirred tank. However, both the model and the surface renewal theory solutions overpredicted enhancement that was measured in the stirred tank for the case of a 17 mM Ca(OH)_2 solution.
2. Adjusting the diffusivity of hydroxide, D_{OH^-} , to 40 percent of the referenced value allowed the model to more accurately predict enhancement in the 17 mM Ca(OH)_2 solution and in slurries. Adjusting D_{OH^-} did not significantly change the enhancement predicted by the model for dilute Ca(OH)_2 solutions.
3. The model predicted the enhancement of SO_2 absorption measured in the stirred tank for slurries of low solids content, but predicted higher enhancement than measured in the stirred tank for slurries of high solids content. Experimental data might be influenced by solids settling in the boundary layer, but it is unclear whether this occurs in droplets.
4. The model predicted little difference in enhancement for changes in particle size (reactivity) of Ca(OH)_2 unless the particle size is changed by an order-of-magnitude. This supports that enhancement is not sensitive to changes in the reactivity of the solids unless the reactivity is grossly different, as found also in stirred tank experiments.

7.4 IMPLICATIONS FOR A SLURRY DROPLET

1. Enhancement factors for SO_2 absorption in a slurry droplet would be lower than those measured in the stirred tank under similar conditions because of the difference in k_g . Depending on the size of the droplet, enhancement factors for a slurry droplet may be only about 25 percent of the values reported for the stirred tank.
2. Under the experimental conditions studied in this research, absorption of SO_2 in a slurry droplet is controlled primarily by liquid film resistances. However, under commercial conditions, gas film resistance is expected to dominate.

3. The slurry absorption model predicted that, for slurries of up to 23 weight percent Ca(OH)_2 , absorption in a slurry droplet could be less than 100 percent gas film controlled in gases containing over 1,000 ppm SO_2 .

7.5 COMPUTER MODELING

Although this is not a model of a slurry droplet, it seems probable that the absorption of SO_2 into a slurry of Ca(OH)_2 is, in most cases, gas film controlled. The contact time when the liquid film resistance becomes important is often too long to be practical. For example, in a spray dryer drying of the droplet is so fast that the absorption process, as long as the droplet is wet, will be gas film controlled. When the water has evaporated, other processes determine the absorption rate. The only time the liquid film resistance can be of importance is when we have very unreactive lime in small droplets.

7.6 RECOMMENDATIONS FOR ADDITIONAL STUDY

1. Experiments should be performed to verify the CaSO_3 crystallization part of the slurry absorption model.
2. A physical reason for the low measured enhancement in the 17 mM Ca(OH)_2 solution should be determined. This should explain why the adjustment of D_{OH^-} must be made for the model to accurately predict the measured enhancement. Additional experiments may be needed.
3. Experiments should be run in the stirred tank using solutions which might eliminate the effects of solids settling in the boundary layer. Solutions of higher viscosity might be considered. Such experiments would help validate the slurry absorption model better for slurries of high solids content.
4. It should be determined, through experimentation whether solids settling influences absorption in slurry droplets.

5. Code in the slurry absorption model could be modified so that it converges on solution of the absorption rate more reliably. Also, calculations for the enhancement factor could be added directly to the model.
6. The slurry absorption model is presently configured so that solutions containing cations other than Ca^{2+} (i.e., Na^+) can be considered. However, the model has difficulty running for such solution compositions and needs to be modified.
7. The slurry absorption model should be coupled with the necessary theories which account for evaporation of water, solids distribution in the bulk liquid and in the boundary layer, and representative droplet sizes and drying times.
8. Experiments using buffer additives, such as those studied by Chang and Rochelle (1979, 1982) and Weems and Rochelle (1981) could be performed in slurries to measure improvements in enhancement and validate the slurry absorption model for the effects of buffers.

SECTION 8

REFERENCES

Alper, E., W.D. Deckwer, and Danckwerts, P.V., "Comparison of Effective Interfacial Areas With the Actual Contact Area for Gas Absorption in a Stirred Cell," *Chemical Engineering Science*, 35, 1263 (1980).

Babu, M., J. College, R. Forsythe, R. Herbert, D. Kanary, D. Kervan, and K. Lee, "5-MW Toronto HALT Pilot Plant Testing - Final Test Results," DOE Contract DE-AC22-85PC81012 (1988).

Bechtel Inc., "Desulfurization of Flue Gas by the Confined Zone Dispersion Process," Draft Final Report, DOE Contract DE-AC22-85PC81009 (1988).

Bin, A.K., "Mass Transfer to the Free Interface in Stirred Vessels," *Chemical Engineering Communication*, 31, 155-183 (1984).

Bird, R.B., W.E. Stewart and E.N. Lightfoot, *Transport Phenomena*, John Wiley & Sons, New York, N.Y. (1960).

Blix, G., *Z. Physiol. Chem.*, 178, 109 (1928).

Boynton, R.S., *Chemistry and Technology of Lime and Limestone*, 2nd edition, John Wiley and Sons, New York, NY (1980).

Chan, P.K.R., and G.T. Rochelle, "CaCO₃ Dissolution in SO₂ Scrubbing Solution Mass Transfer Enhanced by Chemical Reactions," masters thesis, the University of Texas at Austin (1981).

Chang, C.S. and G.T. Rochelle, "Effect of Organic Acid Additives on SO₂ Absorption Into CaO/CaCO₃ Slurries," *AIChE Journal*, 28, 2 (1982).

Chang, C.S. and G.T. Rochelle, "SO₂ Absorption Into NaOH and Na₂SO₃ Aqueous Solutions," presented at the AIChE National Meeting, Philadelphia (1980).

Chang, C.S., and G.T. Rochelle, "SO₂ Absorption Into Aqueous Solutions", *AIChE Journal*, 27, 2, (1981).

Chang, C.S., "Mass Transfer With Equilibrium Chemical Reaction, Sulfur Dioxide Absorption in Aqueous Solutions," Ph.D. dissertation, The University of Texas at Austin (1979).

Damle, A.S., "Modeling of SO₂ Removal in Spray-Dryer Flue-Gas Desulfurization System," prepared for the U.S. EPA, contract no. EPA-600/7-85-038 (1985).

Danckwerts, P.V., "Gas Absorption Accompanied by Chemical Reaction," AIChE Journal, 1, 456 (1955).

Danckwerts, P.V., "Gas Absorption with Instantaneous Reaction," Chemical Engineering Science, 23, 1045 (1968).

Danckwerts, P.V., Gas-Liquid Reactions, McGraw-Hill, New York (1970).

Danckwerts, P.V., "Significance of Liquid-Film Coefficients in Gas Absorption," Industrial and Engineering Chemistry, 43, 1460 (1951).

Energy and Environmental Research Corp., "Global Approach for Enhanced Mass Transfer Effects In-Duct Flue Gas Desulfurization Processes, In-Duct Slurry Droplet Model," Topical Report No. 2 prepared for US. Department of Energy, Pittsburgh, contract no. DE-AC22-88PC88873 (1989).

Epstein, M., "EPA Alkaline Scrubbing Test Facility: Summary of Testing Through October 1974", prepared for the U.S. EPA, contract no. EPA 650-2-75-047 (1975).

Giovanni, D.V., R.G. Rhudy, J. McCarthy, and R. Giles, "Technical and Economic Evaluation of HYPAS," presented at the 1st Combined FGD and Dry SO₂ Control Symposium, St. Louis, M(1988)

Gleason, C.L. and Rochelle, G.T., "Dissolution and Crystallization of Calcium Sulfite Platelets", presented at the AIChE National Meeting, Houston, Texas (1987).

Harriot, P., "Mass Transfer to Particles: Part I. Suspended in Agitated Tanks", AIChE Journal, 8, 93-102 (1962).

Higbie, R., "The Rate of Absorption of a Pure Gas Into a Still Liquid During Short Periods of Exposure," Transactions of AIChE Journal, 31, 365 (1935).

Hikita, H., S. Asai and H. Nose, "Absorption of Sulfur Dioxide Into Water", AIChE Journal, 24, 1, 147 (1978).

Hikita, H., S. Asai and T. Tadashi, "Absorption of Sulfur Dioxide into Aqueous Sodium Hydroxide and Sodium Sulfite Solutions," AIChE Journal, 23, 4, 538 (1977).

Hirschfelder, J.O., C.F. Curtiss and R.B. Bird, Molecular Theory of Gases and Liquids, John Wiley and Sons, New York, NY (1964).

Holstvoogd, R.D., K.J. Ptasinsky and W.P.M. van Swaaij, "Penetration Model for Gas Absorption With Reaction in a Slurry Containing Fine Insoluble Particles," Chemical Engineering Science, 41, 867-873 (1986).

Huasheng, L., and F. Wenchi, "Kinetics of Absorption of Nitric Oxide in Aqueous Fe(II)-EDTA Solution", Ind. Eng. Chem. Res., 27, 5 (1988).

Jozewicz, W. and G.T. Rochelle, "Modeling of SO₂ Removal by Spray Dryers," presented at the Pittsburgh Coal Conference (1984).

Karlsson, H.T., and J. Kilngspor, "Tentative Modeling of Spray-Drying Scrubbing of SO₂," Chemical Engineering Technology, 10, 2, 104 (1987).

Kinsey, M. and P. Harriott, "Modeling the Gas and Liquid Resistances in the Dry Scrubbing Process for SO_2 Removal," presented at the Third Annual Pittsburgh Coal Conference (1986).

Kinsey, M.K., and P. Harriott, "Effects of Droplet-Size Distribution on the Dry Scrubbing Process for Flue Gas Desulfurization," presented at the AIChE National Meeting, Washington D.C. (1988).

Kosinski, A.A. and C.J. King, "The Influence of Diffusivity on Liquid Phase Mass Transfer to the Free Interface in a Stirred Vessel," AIChE Journal, 12, 109 (1966).

Larsson, E., B. Adell, Z. Anorg. Chem., 196, 354 (1931).

Lee, J.J., "Numerical Modeling of Direct Sorbent Injection for SO_2 Removal," prepared for the University of Tennessee Space Institute, American Chemical Society - Division of Gas and Fuel Chemistry (preprints), 33, 2, 120-125 (1988).

Malibodi, M., T.L. Pearson, R.M. Counce, and W.T. Davis, "Simulation of Spray Dryer Absorber for Removal of SO_2 from Flue Gases," presented at the Tenth Symposium on Flue Gas Desulfurization, 1, EPRI CS-5167 (1987).

Markarov, S.Z., and I.I. Vol'nov, Izv. Sektora Fiz-Khim. Anal., Inst. Obshch. Neorgan. Khim., Akad Nauk, SSSR, 25, 320 (1954).

McGuire, L.M., "Sulfur Dioxide Absorption Experiments in Calcium Hydroxide Slurries," M.S. Thesis, The University of Texas at Austin, Austin, Texas, December 1990.

Miyachi, M., A. Iguchi, S. Uchida, K. Koide, "Effect of Solid Particles in Liquid Phase on Liquid-side Mass Transfer Coefficient," Canadian Journal of Chemical Engineering, 59, 690-691 (1981).

Olander, D.R., "Simultaneous Mass Transfer and Equilibrium Chemical Reaction," AIChE Journal, 6, 2, 233 (1960).

Peaceman, D.W., "Liquid-Side Resistance in Gas Absorption With and Without Chemical Reaction," Sc.D. Thesis, Massachusetts Institute of Technology, Cambridge, MA (1951).

Perry, R.H., and C.H. Chilton, "Prediction and Correlation of Physical Properties," Chemical Engineer's Handbook, 5th edition, McGraw-Hill Book Company, New York, NY (1973).

Quicker, G., E. Alper, and W.D. Deckwer, "Gas Absorption Rates in a Stirred Cell With Plane Interface in the Presence of Fine Particles," The Canadian Journal of Chemical Engineering, 67, 32-38 (1989).

Ramachandran, P.A., and M.M. Sharma, "Absorption With Fast Chemical Reaction in a Slurry Containing Sparingly Soluble Fine Particles," Chemical Engineering Science, 24, 1681 (1969).

Sada, E. et al., "Kinetics of Absorptions of Lean Sulfur Dioxide into Aqueous Slurries of Calcium Carbonate and Magnesium Hydroxide," Chemical Engineering Science, 36, 149-155 (1981).

Sada, E., H. Kumazawa and M.A. Butt, "Single and Simultaneous Absorptions of Lean SO_2 and NO_2 into Aqueous Slurries of $\text{Ca}(\text{OH})_2$ or $\text{Mg}(\text{OH})_2$ Particles," Journal of Chemical Engineering of Japan, 12, 111-117 (1979).

Sada, E., H. Kumazawa and M.A. Butt, "Single Gas Absorption With Reaction in a Slurry Containing Fine Particles", Chemical Engineering Science, 32, 1165-1170 (1977).

Sada, E., H. Kumazawa, N. Hayakawa, I. Kudo and T. Kondo, "Absorption of Ni in Aqueous Solutions of KMnO_4 ", Chemical Engineering Science, 32, 1171-1175 (1987).

Sada, E., H. Kumazawa, "Some Consideration on Chemical Absorption into a Slurry Containing Fine Catalyst Particles," Chemical Engineering Science, 37, 945-948 (1982).

Sada, E., H. Kumazawa, Y. Yamanaka, I. Kudo and T. Kondo, "Kinetics of Absorption of Sulfur Dioxide and Nitric Oxide in Aqueous Mixed Solutions of Sodium Chlorite and Sodium Hydroxide," Journal of Chemical Engineering of Japan, 11, 4, 276-282 (1978).

Samuel, E.A., K.R. Murphy, and A. Demian, "A 12-MW Pilot Study of In-Duct Scrubbing (IDS) Using a Rotary Atomizer," Final Report, DOE Contract DE-AC22-85PC81010 (1989).

Sherwood, T.K., R.L. Pigford and C.R. Wilke, Mass-Transfer, McGraw-Hill Inc., New York, N.Y., (1975).

Stromblad, C. and G.T. Rochelle with Acurex Corporation, "Theoretical Approach for Enhanced Mass Transfer Effects - In-Duct Flue Gas Desulfurization Processes - Quarterly Report No. 4," prepared for the U.S. Department of Energy, Pittsburgh, under Contract No. DE-AC22-88PC88874 (1989).

Treybal, R.E., Mass-Transfer Operations, 3rd Edition, McGraw-Hill Inc., New York, N.Y., (1980).

Uchida, S., and C.Y. Wen, "Rate of Gas Absorption into a Slurry Accompanied by Instantaneous Reaction", Chemical Engineering Science, 32, 1277-1281 (1977).

Uchida, S., H. Moriguchi, H. Maejima, K. Koide and S. Kageyama, "Absorption of Sulfur Dioxide into Limestone Slurry in a Stirred Tank Reactor", Canadian Journal of Chemical Engineering, 56, 696-697 (1978).

Uchida, S., K. Koide, and M. Shindo, "Gas Absorption With Fast Reaction into a Slurry Containing Fine Particles", Chemical Engineering Science, 30, 644 (1975).

Versteeg, G.F., P.M.M. Blauwhoff and W.P.M. Van Swaaij, "The Effect of Diffusivity on Gas-Liquid Mass Transfer in Stirred Vessels. Experiments at Atmospheric and Elevated Pressures," Chemical Engineering Science, 42, 5, 1103-1119 (1987).

Vivian, J.W., "Absorption of SO_2 into Lime Slurries: Absorption Rates and Kinetics," prepared for the U.S. EPA, contract no. EPA-650/2-73-047 (1973).

Weems, W.T., "Enhanced Absorption of Sulfur Dioxide by Sulfite and Other Buffers," masters thesis, The University of Texas at Austin (1981).

Whitman, W.G., "Preliminary Experimental Confirmation of the Two-Film Theory of Gas Absorption," Chem. Met. Engineering, 29, 146-148 (1923).

Yoon, H., P.A. Ring, and F.P. Burke, "Coolside Abatement Technology: 1-MW Field Tests", presented at Coal Technology '85, Pittsburgh, PA (1985).

END

**DATE
FILMED**

6 / 29 / 92