DOE/PC/88935--T10

88PC-88935-QTR-13

**INHIBITION OF RETROGRESSIVE REACTIONS
IN COAL/PETROLEUM CO-PROCESSING**

QUARTERLY TECHNICAL PROGRESS REPORT

Reporting Period: October 1, 1991 - December 30, 1991

Harold H. Schobert
Jasna Tomic

January 1992
Contract No. DE-FG22-88PC88935

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DE92 011934

INHIBITION OF RETROGRESSIVE REACTIONS IN COAL/PETROLEUM CO-PROCESSING

QUARTERLY TECHNICAL PROGRESS REPORT

Reporting Period: October 1, 1991 - December 30, 1991

Harold H. Schobert
Jasna Tomic

January 1992
Contract No. DE-FG22-88PC88935

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

TABLE OF CONTENTS

OBJECTIVE.....	1
SUMMARY.....	1
CHARACTERIZATION OF PETROLEUM RESIDS.....	2
SOLVENT FRACTIONATION AND LIQUID CHROMATOGRAPHY OF PETROLEUM RESIDS	2
NUCLEAR MAGNETIC RESONANCE SPECTROSCOPY OF PETROLEUM RESIDS FRACTIONS.....	4
PYROLYSIS-GAS CHROMATOGRAPHY-MASS SPECTROMETRY OF RESID ASPHALTENES.....	15
COAL/RESID REACTION	18
LITERATURE CITED.....	20
APPENDIX.....	21

OBJECTIVE

The overall objective of this project is to develop a fundamental understanding of the reactions occurring at the onset of coke formation during the co-processing of coals with petroleum residua. The specific objectives include examination of chemical components, or groups of components, in coals and petroleum feedstocks to quantify and rank the effects of these components in retarding or enhancement of coke formation. The work involves bench scale reactions in microautoclaves, supplemented by studies of the carbonaceous residues by such techniques as diffuse reflectance Fourier transform infrared spectroscopy and ^{13}C nuclear magnetic resonance spectrometry.

During this reporting period work focused on Task 4, identification of mechanisms of coke formation. The objective of this task is to identify those compounds or components which are specifically responsible for initiating coke formation. Major components of the petroleum resids were analyzed using solvent separation techniques and instrumental methods such as nuclear magnetic resonance spectrometry and pyrolysis/gas chromatography-mass spectrometry. The analytical data obtained in this task will allow for identification of coke precursors and establish a ranking system for predicting compatibility of particular coals and petroleum resids as feedstocks for coprocessing with minimal coke formation.

SUMMARY

Solvent fractionation of the petroleum resids to pentane-solubles and pentane insolubles was continued using a somewhat modified method than the previous. The results agreed well with the previously obtained. West Texas vacuum resid contains the highest amount of asphaltenes followed by Blend and Hondo resid. The maltene fractions were subsequently analyzed by liquid chromatography and separated into saturate, aromatic and polar fractions. The weight percent aromatics in the two maltenes were similar while the distribution of the saturate and polar fractions were different.

More structural information on the maltenes and asphaltenes was obtained by ^1H and ^{13}C NMR spectroscopy. Structural parameters such as hydrogen aromaticity and carbon aromaticity indicated the differences in the chemical components of the project resids. The asphaltenes were in addition analyzed by flash pyrolysis/GC/MS. The chromatograms exhibited differences especially in the number of compound containing S and N. Heterocompounds present in the petroleum resids may play an important role in the retrogressive reactions.

CHARACTERIZATION OF PETROLEUM RESIDS

Several techniques were used for further characterization of the project petroleum resids. In the previous period we employed nuclear magnetic spectroscopy on the whole resid samples. We also separated the whole resid samples into solvent fractions, that is the pentane-soluble (maltenes) and pentane-insoluble (asphaltenes). During this quarterly report period nuclear magnetic resonance spectra were obtained for the solvent fractions; maltenes and asphaltenes.

The pentane-solubles were earlier analyzed by gas chromatography (GC) and gas chromatography-mass spectrometry (GC/MS) when possible. Some preliminary GC results on the Hondo maltenes (pentane-solubles) were obtained, but the GC analyses of the West Texas and Blend vacuum resid maltenes were not successful. The reason is probably the higher molecular weight compounds present in these vacuum resid samples have a boiling point which is beyond the range of temperatures used in the GC program (40° - 280°C). Therefore, characterization of the West Texas and Blend vacuum resid maltenes required further separation into saturate, aromatic and polar compound classes.

Since the asphaltene fractions seem to have a significant influence on the overall coprocessing reactions, an attempt was made to apply additional analytical methods for structural characterization of the asphaltene fractions. Flash pyrolysis-gas chromatography-mass spectrometry (Py-GC-MS) was used for structural study of the asphaltenes.

SOLVENT FRACTIONATION AND LIQUID CHROMATOGRAPHY OF PETROLEUM RESIDS

Fractionation of the whole resids into asphaltenes (toluene-soluble/pentane-insoluble) and maltenes (pentane-soluble) was continued. In the previous quarterly report [1] we noted a considerable difference in the asphaltene values reported by the suppliers and those that were obtained in this laboratory. Due to this disagreement and some problems encountered in mixing of the Blend and West Texas vacuum resids with pentane, we repeated the solvent fractionation of the resid samples. The procedure was similar to the previously reported except that we now replaced the cellulose thimble with a Millipore vacuum filtration using filter of 0.45µm pore size for filtration of the asphaltenes. The amount of asphaltenes was determined after evaporation of pentane from the separated solids and drying of the asphaltene solids in vacuum at 60°C.

Table 1. Asphaltene content of petroleum resids

Asphaltene wt%		
Hondo	Blend	W. Texas
17.97 a	21.44 a	28.18 a
19.31 b	22.07 a	26.16 b
/	23.38 b	25.72 b

a filtered through a thimble

b filtered through a Millipore vacuum filtration

Table 1 shows the weight percent of asphaltenes obtained by solvent fractionation. The repeated separations are in agreement with the trend in asphaltene yields acquired in the first separation. The differences between each separation conducted are within 2% but the relative values are in agreement. The weight percent asphaltenes is the lowest for Hondo resid followed by Blend vacuum resid and West Texas vacuum resid. These values disagree with those provided by the suppliers, which are 15.9 wt%, 14.8 wt% and 0.5 wt% for Hondo, Blend and West Texas, respectively. The differences possibly arise due to the different methods of separation employed or due to the aging of the samples over time. The information about the specific separation method used by the suppliers of the resids unfortunately is not available.

The pentane-soluble fractions (maltenes) were further fractionated into saturates, aromatic and polar compound classes following a procedure similar to Wallace et al.[2]. A 35 cm x 2 cm o.d.column was packed with silica gel (60 mesh). Approximately 300 mg of sample was diluted with dichloromethane (DCM) and mixed with a small amount of silica gel and the sample was then dried under nitrogen till the maltenes were fully absorbed on the silica gel. This sample was then loaded as a powder onto the top of the column which was filled with pentane. The column was eluted successively with 100 ml of pentane, benzene and tetrahydrofuran (THF) to obtain the saturate, aromatic and polar fractions.

Figure 1. Separation scheme of the maltene fraction.

The solvents were removed in a rotavap and the samples were dried under nitrogen to a constant mass in order to determine the weight percent of each compound class. The results of a liquid chromatography separation of West Texas maltenes and Blend resid maltenes are shown in Table 2.

Table 2. Fractionation data of petroleum resid maltenes.

Maltene sample	Saturates, wt%	Aromatics, wt%	Polars, wt%
West Texas	25.58	49.15	25.26
Blend	16.47	46.99	36.54

The results of the liquid chromatography separation indicate a different proportion of compound classes in the two petroleum resids, Blend and W. Texas. Both resid maltenes have close to 50% aromatic compounds, as indicated by the weight percent of the benzene fractions, but a greater difference is observed in the distribution of the saturate and polar fractions. While West Texas resid maltenes yielded about equal amounts of saturate and polar fractions, the yield of the polar fraction from Blend resid maltenes was much greater.

NUCLEAR MAGNETIC RESONANCE SPECTROSCOPY OF PETROLEUM RESID FRACTIONS

Nuclear magnetic resonance analysis was performed on the maltene and asphaltene fractions. ^1H spectra were recorded on a Bruker WM-360 pulse FT NMR spectrometer operating at a frequency of 360 MHz. Approximately 50 mg of sample was dissolved in chloroform- d (the peak at chemical shift of 7.3 ppm is due to the chloroform). The distribution of aromatic and aliphatic hydrogens was determined by digital integration of the aromatic region (9 - 6 ppm) and aliphatic region (6 - 0.50 ppm) and normalized over the complete spectrum.

Table 3. Chemical shift assignments of hydrogen types from ^1H NMR spectra.[3].

9.00 - 6.00	Ar-H	Aromatics
6.00 - 4.50	R-CH*=CH ₂	Olefins
4.50 - 3.40	Ar-CH ₂ *-Ar	Alpha Methylene
3.40 - 2.60	Ar-CH ₂ *-R	Alpha Methylene
2.60 - 2.00	Ar-CH ₃	Alpha Methyl
2.00 - 1.05	R-CH ₂ *-R	Paraffinic Methylene
	Ar-CH ₂ -CH ₃ *	Beta Methyl
	Ar-(CH ₂) ₂ -(CH ₂) _n *-CH ₃	Gamma Methylene
	Ar-CH ₂ -CH ₂ *-R	Beta Methylene
1.05 - 0.50	R-(CH ₂) _n -CH ₃ *	Paraffinic Methyl
	Ar-(CH ₂) _n -CH ₃ *	Gamma or Terminal Methyl

The ^{13}C NMR spectra were recorded on the same instrument at an operating frequency of 90.5 MHz with inverse gate proton decoupling on during acquisition. Chloroform-d was used as a solvent in which 100 mg of sample was dissolved to obtain good quality spectra in a reasonable time. The distribution of aromatic and aliphatic carbons was determined by digital integration of the aromatic (148 - 118 ppm) and aliphatic region (53 - 13 ppm).

Table 4. Hydrogen and carbon aromaticities of petroleum resid fractions.

Sample	H _{ar} , % ^a	C _{ar} , % ^b
Hondo-maltenes	5.33	
Blend-maltenes	6.62	
W. Texas-maltenes	8.51	
Hondo-asphaltenes	7.44	37.33
Blend-asphaltenes	12.80	
W. Texas-asphaltenes	10.48	51.47

a from proton NMR data.

b from ^{13}C NMR data.

The hydrogen aromaticity is lowest for Hondo resid maltenes and highest for W. Texas vacuum resid maltenes. In the case of the asphaltenes the hydrogen aromaticities do not follow the same trend as for the maltenes. As expected, the aromaticities are higher for the asphaltene fractions than for the respective maltene fractions. Among the asphaltene fractions, Blend resid asphaltenes have the highest amount of aromatic hydrogens.

Previously collected NMR data [4] showed that the Blend vacuum resid was the most aromatic in terms of the aromatic hydrogen and aromatic carbon.

Some structural information can be deduced from the NMR spectra of the maltenes and asphaltenes. Comparing the ^1H NMR spectra of the maltenes shown on Figures 2 - 4, it is obvious that while the W. Texas and Blend resid maltenes seem quite similar, Hondo maltenes have some more distinctive features. The aromatic region for Hondo maltenes is less complex but the aliphatic region shows greater number of peaks than the other two maltenes spectra such as the peaks in the region from 0.5-1.05 ppm assigned to paraffinic methyl groups or γ -methyl groups. The strongest peak in all three maltenes spectra is that of β -methyl or γ -methylene at 1.27 ppm. The peak at 2.27 ppm which appears in all the spectra is assigned to α -methyl groups and is due to residual toluene which was used for solvent fractionation of the resids.

The proton NMR spectra of the asphaltenes are shown on Figures 5-7. These spectra do not provide much structural information, which is probably due to the high conjugation in the asphaltenes. The main observation is the absence of peak at 1.45 ppm in the spectrum of Blend asphaltenes which is present in the other two asphaltene ^1H NMR spectra. This peak is attributed to β -methyl or γ -methylene groups. The ^{13}C NMR spectra of the asphaltenes (Figures 8 and 9) provide some more information on the structural components. Of the two spectra presently at hand the West Texas asphaltenes are considerably more aromatic while the Hondo asphaltenes are richer in aliphatics. The major difference between these two spectra is the presence of peaks in the Hondo spectra assigned to bridgehead carbons of naphthenes and methylene bridge carbons.

Figure 9. ^{13}C NMR spectrum of West Texas vacuum resid asphaltene.

Figure 7. ^1H NMR spectrum of Blend vacuum resid asphaltene.

Figure 6. ^1H NMR spectrum of West Texas vacuum resid asphaltene.

ASPHALT.H01

7.26828

~~BRUKER~~
PPM

ASPHALTS.H01
DATE 24-1-92

SF 360.196
SY 83.0
O1 5800.000
SI 32768
TD 32768
SW 5000.000
HZ/PT .305

PW 18.7
RD 5.000
AQ 3.277
RG 400
NS 48
TE 297

FW 6300
O2 12100.000
DP 10L P0

LB 0.0
GB 0.0
CX 25.00
CY 23.00
F1 9.999P
F2 -.999P
HZ/CM 158.459
PPM/CM .440
SR 3981.00

1.44799
1.26849
1.08738
.89175

9.0 8.0 7.0 6.0 5.0 4.0 3.0 2.0 1.0 0.0
PPM

Figure 5. ¹H NMR spectrum of Hondo resid asphaltene.

Figure 4. ¹H NMR spectrum of Blend vacuum resid maltenes.

1.31607
1.27847
90528
08197
07839
86129

2,3773

7,20735

Wdd

MALTS.B01
DATE 24-1-92

SF	360.134
SY	60.0
01	5800.000
SI	32768
TD	32768
SW	5000.000
HZ/PT	.305

PW	18.7
PD	5.000
AG	3.277
RG	200
NS	48
TE	297

FW 6300
02 12100.000
DP 10L PO

LB	0.0
GB	0.0
CX	25.00
CY	23.00
F1	10.001P
F2	-1.000P
HZ/CM	158.459
PPM/CM	.440
SR	3984.00

Figure 3. ^1H NMR spectrum of West Texas vacuum resid maltenes.

Figure 2. ¹H NMR spectrum of Hondo resid maltenes.

PYROLYSIS-GAS CHROMATOGRAPHY-MASS SPECTROMETRY (Py/GC/MS) OF RESID ASPHALTENES

The asphaltenes were in addition analyzed by Pyrolysis/GC/MS. The analysis was performed on a Du Pont 490B GC-MS system using a 30 x 0.25 mm i.d. capillary column DB-17 coated with phenylmethylsilicone stationary phase and film thickness of 0.25 μm . The system was interfaced to a Chemical Data System Pyroprobe-1000 pyrolyzer. The sample was flash-pyrolyzed at 610° C (or 710° C) for 10 seconds and the GC-MS was conducted at a temperature program from 40° C to 280° C at a rate of 4° C/min. The mass spectrometer was conducted in the electron impact ionization mode at an ionizing frequency of 70 eV.

Two asphaltene samples were flash pyrolyzed; Blend asphaltenes (ASPH-B) and Hondo asphaltenes (ASPH-H). Hondo asphaltenes were pyrolyzed at 610° C. The total ion chromatogram for pyrolysis-GC-MS of Hondo asphaltenes is shown on Figure 10. Most noticeable is the peak at retention time 29.7 minutes which was identified as 3-ethyl-2-phenyl-indole ($\text{C}_{16}\text{H}_{15}\text{N}$). A series of alkanes and alkenes peaks is present in the TIC of the Hondo asphaltenes, but an especially interesting observation is the presence of a number of thiophenes. Thiophenes from C_1 to C_6 were identified amongst the compounds in the region of retention time 5-20 minutes. The presence of a significant number of compounds containing sulfur is in agreement with the elemental analysis of the parent resid. The Hondo resid sample contains 5.10% sulfur and according to the information provided by the supplier, the asphaltene fraction should contain approximately 7.73% sulfur and 1.93% nitrogen. We are presently obtaining elemental and sulfur analysis of the asphaltene separated fractions.

In an attempt to achieve better resolution and separation of the peaks throughout the spectra, the next flash-pyrolysis was conducted at 710° C. The total ion chromatogram of the Blend resid asphaltenes is shown in Figure 11. The pyrolysis temperature of 710° C resulted in a greater concentration of the eluted material at smaller retention time values. This higher pyrolysis temperature resulted in a much simpler ion chromatogram than the previous lower temperature. Most of the peaks identified in Figure 11 are those of the alkane and alkene series (to C_{31}) with some of the minor peaks assigned to C_1 through C_3 -benzene. The main difference from the chromatogram of the Hondo asphaltenes and Blend asphaltenes is the absence of the thiophenes in the Blend asphaltenes. A better comparison should be achieved in the future work when both samples are pyrolyzed at the same temperature.

TIC * 139.733: Min = 0. Max = 469. Delta = 469

D: \DATAAQ\JASNA\C\ASPH-B

1633 scans acquired on 24 Jan. 1992 at 09:15:21. Rate = 2.70185 seconds/scan

BLEND ASPHALTENE

PYROLYSIS 710/10C/MS 10SEC

GC: ramp=4C/min from ambient to 280C

Figure 11. Total ion chromatogram for pyrolysis-GC-MS of Blend vacuum resid asphaltene.

TIC * 182.549: Min = 0. Max = 359. Delta = 359

D: \DATAAG\JASNA\C\ASPH-H

1888 scans acquired on 23 Jan, 1992 at 09:05:48. Rate = 2.70185 seconds/scan

Hondo asphaltene 2 0.821mg

Pyrolysis 10C/ms\610C\10s

GC: ramp=4C/min from ambient to 280C

Figure 10. Total ion chromatogram for pyrolysis-GC-MS of Hondo resid asphaltene.

The information obtained by the several analytical methods used provide a better understanding of the structural composition of the resids and their fractions. The solvent separation of the resids indicate that of the three project resids the West Texas is highest in asphaltenes followed by Blend and Hondo resids. Liquid chromatography of the maltene fractions showed that of the two vacuum resids (West Texas and Blend) West Texas was slightly more aromatic but Blend resid contains more polar compounds. The proton NMR data agrees with this finding. Namely, the hydrogen aromaticity of the West Texas maltenes is higher than that of Blend resid. The NMR spectra of the West Texas and Blend fractions showed great similarities while the spectrum of Hondo fractions was different. In terms of hydrogen aromaticity, the Blend asphaltenes have the highest aromaticity. The ^{13}C NMR results presently on hand on the Hondo and West Texas asphaltenes again confirmed the greater aromaticity of West Texas over Hondo asphaltenes and probably a greater degree of conjugated aromatic ring structures. This is concluded on the basis of the peaks representative of bridgehead carbons (naphthene and methylene type) identified in the spectra of Hondo asphaltenes but absent in that of West Texas asphaltenes. The flash pyrolysis results on the asphaltenes confirm the greater variety of chemical components present in the Hondo fractions versus those in the Blend fraction. Hondo asphaltenes are particularly rich in heteroatoms (S and N compounds).

COAL/RESID REACTIONS

From the coprocessing experiments between the five coals and the three resids samples influences of both coals and resids were noted. The nature of the coal and in particular dissolution of the coal particles in the solvent (resid) is dominant at temperatures up to 400°C (see Appendix). On the other hand, the chemical composition of the resids seems to have a major influence at reaction temperature of 450°C . West Texas vacuum resid was found to be a more compatible solvent for coprocessing reactions than Blend vacuum resid and much more compatible than Hondo resid. In preliminary analysis there were implications for correlation of the coal conversion results with the asphaltenes fractions and in particular, the chemical composition of the asphaltenes. Some of the analysis conducted on the resid fractions gave further insight on the types of structures in petroleum resids which influence the retrogressive reactions and hence the formation of insoluble material during coprocessing.

The petroleum resids which are more aromatic produce much less THF-insoluble matter in reactions with coal and lead to higher coal conversion yields. This is in our case the Blend and West Texas resid versus Hondo resid. At higher reaction temperatures the

chemical nature of the resid has a determining influence. For the three project resids for which coprocessing experiments were conducted it was shown that West Texas vacuum resid achieves better coal conversion results than the other two resid samples. The reason for poor performance of Hondo and Blend resids as coal coprocessing solvents is possibly the presence of heteroatom compounds. The Blend maltenes contain a higher proportion of polar compounds as detected by liquid chromatography separation and Hondo asphaltenes when subject to flash pyrolysis yielded in a considerable amount of heteroatom type of compounds. Heteroatoms are generally very reactive compounds and could under coprocessing conditions at higher temperatures (450°C) lead to insoluble matter.

The assorted analytical data on the whole resids and their solvent fractions will provide more insight into the types of structures involved in retrogressive reactions. Correlations of THF-insolubles yield with composition parameters of the resids can be investigated by statistical analysis tests of the resid composition and results obtained from the reaction of the three resids with five coals. The correlations will be investigated using the compositional data of the whole resids and their solvent fractions such as the hydrogen aromaticity (H_{ar}) and carbon aromaticity (C_{ar}). In this fashion we will examine the influence of the compositional data rather than the gross properties of the resids taken from the suppliers as significant parameters which contribute to formation of semi-coke in coprocessing systems.

LITERATURE CITED

- [1]. Schobert, H. H., J Tomic, "Inhibition of Retrogressive Reactions in Coal/Petroleum Co-processing", U.S.D.O.E. Report, No.88PC-88935-QTR-12, **1991**.
- [2]. Wallace, S., K. D. Bartle, B. Egia, S. Lu, N. Taylor, T. Flynn, W. Kemp, and W. Steedman, *Fuel*, **1989**, 68, 961.
- [3]. Song, C., S. Eser, H. H. Schobert, P. G. Hatcher, M. M. Coleman, Y. Peng, L. Selveraj, M. Parzynski, J. Bortiatynski, Y. Liu, R. M. Copenhaver, R. Arumugam, "Compositional Factors Affecting Thermal Degradation of Jet Fuels", Annual Progress Report for Period July 1990 - July 1991, DOE/Sandia National Laboratory, No.78-0899-TPR-4 August **1991**.
- [4]. Schobert, H. H., J Tomic, and J. Green, "Inhibition of Retrogressive Reactions in Coal/Petroleum Co-processing", U.S.D.O.E. Report, No.88PC-88935-QTR-11, **1991**.

conf paper cycled
separately
etc

END

**DATE
FILMED**

6 / 11 / 92