MAY 22 1992

DOE/ER/54092--1

DE92 014427

Annual Progress Report
Helium Transport and Ash Control Studies*
for
1 June 1991 - 31 March 1992

Prepared by
George H. Miley
Principal Investigator

Fusion Studies Laboratory
Department of Nuclear Engineering
University of Illinois
Urbana-Champaign Campus
103 South Goodwin Avenue
Urbana, Illinois 61801
Telephone Number: (217) 333-3772

*Work Supported by the U. S. DOE under contract
DEFG02-90ER54092

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Abstract

The Primary goal of this research is to develop a helium (ash) transport scaling law based on experimental data from devices such as TFTR and JET. To illustrate the importance of this, we have studied ash accumulation effects on ignition requirements using a 0-D transport model. Ash accumulation is characterized in the model by the ratio of the helium particle confinement time to the energy confinement time τ_{α} / τ_E . Results show that the ignition "window" shrinks rapidly as τ_{α} / τ_E increases, closing for high τ_{α} / τ_E . A "best" value for τ_{α} / τ_E will ultimately be determined from our scaling law studies.

A helium transport scaling law is being sought that expresses the transport coefficients (D_{α} , V_{α}) as a function of the local plasma parameters. This is necessary for use in transport code calculation, e.g. for BALDUR. Based on experimental data from L-mode plasma operation on TFTR, a scaling law to a power law expression has been obtained using a least-square fit method. It is found that the transport coefficients are strongly affected by the local magnetic field and safety factor q .

A preliminary conclusion from this work is that active control of ash buildup must be developed. To study control, we have developed a 0-D plasma model which employs a simple pole-placement control model. Some preliminary calculations with this model are presented.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Table of Contents

1	Introduction.....	1
2	Helium Ash Accumulation Effects on Fusion Ignition	1
3	Puffed Impurity Transport Modelling With Simplified Point Source Model.....	2
4	Helium Transport Scaling Law Studies	7
4.1	Introduction.....	7
4.2	Analysis Technique	7
4.3	The best-fit helium transport scaling law for L-mode plasma on TFTR	8
4.4	The application of helium transport scaling to the future tokamak design.....	12
4.5	The invariance analysis of the helium transport scaling law for high- β plasma by using the collisionlessness and quasineutrality mode	14
5	Conclusions.....	16
6	Study of Helium Ash Control	17
6.1	Introduction.....	17
6.2	Dynamic model.....	18
6.3	Equilibrium	20
6.4	Operating Window.....	21
6.5	Non-linear Control Model	24
6.6	Linearization	25
6.7	Computer Program.....	27

6.8 Results.....	27
References.....	30

Table of Figures

Fig. 1 The ignition curve in the $n_e \tau_E \sim T_e$ space for ARIES--3 design where $\frac{\tau_\alpha}{\tau_E} = 1.0$ and radiation reflectivity is 0.975	3
Fig. 2 The ignition curve in the $n_e \tau_E \sim T_e$ space for ARIES--3 design where $\frac{\tau_\alpha}{\tau_E} = 2.0$ and radiation reflectivity is 0.975	4
Fig. 3 The ignition curve in the $n_e \tau_E \sim T_e$ space for ARIES--3 design where $\frac{\tau_\alpha}{\tau_E} = 1.0$ and radiation reflectivity is 0.965	5
Fig. 4 The background plasma parameter profiles for the L-mode plasma on TFTR	9
Fig. 5 The helium diffusion coefficient $D_\alpha(r)$ from experiment and our scaling law results.....	11
Fig. 6 The profiles of helium pinch velocity $V_a(r)$ from the experiment result and our scaling law results.....	13
Fig. 7 Contours of γ in f - T plane. No possible equilibrium exists if $\gamma = \frac{\tau_\alpha^*}{\tau_E} > 15.3$	22
Fig. 8 Contours of γ in $n\tau_E$ - T plane.....	23

1 Introduction

Impurity behavior within the tokamak fusion plasma is a main concern for the future tokamak operation. Thermalized α -particles, i.e., helium ash constitute a key impurity within the plasma core. In the period 8/90--5/91, we have concentrated our research on helium ash accumulation effects using the 0-D code developed by S. Hu, et al.⁽¹⁾. Also, we studied the helium transport behavior by modelling the puffed impurities with simplified point source and fully recycling boundary condition. In the period 5/91--5/92, we explored the scaling laws of helium transport diffusion coefficient and pinch velocity as the function of local plasma parameters by using the transport flux model: $\Gamma_{\alpha} = -D \frac{\partial n_{\alpha}}{\partial r} - n_{\alpha} V$ and the experimental data of L-mode plasma on TFTR. Several significant innovations have been achieved through these studies. The application and significance of helium transport scaling law to the future tokamak design, such as ITER, is also presented in this report.

2 Helium Ash Accumulation Effects on Fusion Ignition

Helium ash accumulation within the tokamak plasma core not only dilutes the fusion fuel, but it also enhances the radiation energy loss. These effects eventually can prevent the fusion ignition, and degrade the fusion output power even after ignition. How great the effects of helium ash accumulation on the ignition are is the key problem we have explored. In this 0-D study, the helium ash accumulation is characterized by the ratio of effective α -particle confinement time to energy confinement time $\rho = \tau_{\alpha} / \tau_E$. This ratio is assumed to be constant in this model. Based on this assumption, the helium ash concentration n_{α} / n_e within the plasma core can be calculated. For steady-state operation, the energy balance equation is set up, and then the ignition curves are plotted in the $n_e \tau_E \sim T$ space (assuming $T = T_e = T_i = T_{\alpha}$). The recycling of helium in the edge region is considered, and all the fusion reaction products are assumed to thermalize before participating transport losses. The studies we completed during this period include:

2.1) We first plot the ignition curves with the same input parameters as that used by D. Reiter, et al.⁽²⁾ for the purpose of benchmarking the 0-D code. The result shows excellent agreement.

2.2) Using the design parameters of ARIES-3, we vary the ratio of α -particle confinement time to energy confinement time and the radiation reflectivity to see how the ignition curve changes in $n_e \tau_E \sim T$ space. We find that the ignition contour curve shrinks as τ_α/τ_E increases (compare Fig. 1 and Fig. 2). Additionally, we find that the ignition contour curves are very sensitive to the radiation reflectivity (compare Fig. 1 and Fig. 3). The ignition is very demanding, making a high radiation reflectivity and low τ_α/τ_E essential for the ARIES-3 design.

3 Puffed Impurity Transport Modelling With Simplified Point Source Model

We assume that the impurities are injected into the plasma confinement region, and the impurity profile just after injection is a δ -function which can be considered as the initial condition ($t=0$) of the impurity transport process. The impurity flux is simplified to have a diffusion term and a pinch term. In the first calculation, we just consider the diffusion term and assume that the diffusion coefficient D_{im} is independent of time and position. The transport could be thought of as corresponding to a tokamak with a large aspect ratio. With fully recycling boundary conditions, we obtain the impurity profile: $n_{im}(r,t) \sim n_0 + n_1(r) \exp[-D_{im}(a/\pi)^2 t]$ after a period of impurity puffing, where n_0 is a certain constant density, $n_1(r)$ is the r -dependence of impurity density profile and a is the tokamak limiter radius. We see that the larger the impurity diffusion coefficient D_{im} , the faster the impurity profile spreads out from the source. In this generalized model, the impurities could be helium ash, lithium or carbon ions.

In a tokamak plasma, impurity transport is strongly affected by the plasma turbulence. We assume that the plasma generates fluctuating electric fields of amplitude $\sim E'$. These fields cause impurity drifts with characteristic velocity $V_c \sim E'/B$ which changes direction randomly after a particle drifts a distance l' . (l' is similar to the mean free path). Therefore, the effective impurity diffusion coefficient can be estimated (in MKS unit system) as⁽³⁾

$$D_{im} \sim D_{turb} \sim l' V_c = \frac{E' l'}{B} \quad (3.1)$$

Assuming $qE'l' \sim kT$ (thermal energy of particles), then we obtain:

Fig. 1 The ignition curve in the $n_e \tau_E \sim T_e$ space for ARIES--3 design where $\frac{\tau_{\alpha}}{\tau_E} = 1.0$ and radiation reflectivity is 0.975

Fig. 2 The ignition curve in the $n_e \tau_E \sim T_e$ space for ARIES--3 design where $\frac{\tau_{\alpha}}{\tau_E} = 2.0$ and radiation reflectivity is 0.975

Fig. 3 The ignition curve in the $n_e \tau_E \sim T_e$ space for ARIES--3 design where $\frac{\tau_{\alpha}}{\tau_E} = 1.0$ and radiation reflectivity is 0.965

$$D_{im} \sim \frac{kT}{qB} \quad (3.2)$$

where q is the charge of impurity particle, T is impurity thermal temperature. Therefore, in this turbulent plasma, the diffusion coefficient for helium ash (D_α) and for another ion species (D_i) have relation:

$$\frac{D_\alpha}{D_i} \sim \frac{q_i}{q_\alpha} = \frac{Z_i}{Z_\alpha} \quad (3.3)$$

where Z_i and Z_α are the charge numbers for i and α respectively. For example, let us compare the diffusion coefficients of helium ash and the fuel ions (D-T):

$$\frac{D_\alpha}{D_i} \sim \frac{1}{2} \quad (3.4)$$

Thus, in this case, the α -particles diffuse somewhat slower than fuel ions, but the difference is not large.

According to the neoclassical theory, if only one species of impurity, such as helium ash, is considered, the equilibrium density profiles of impurity and the fuel ions have relation⁽⁴⁾:

$$\frac{n_\alpha(\psi_0)}{n_\alpha(\psi)} = \left[\frac{n_i(\psi_0)}{n_i(\psi)} \right]^2 \left[\frac{T_i(\psi)}{T_i(\psi_0)} \right]^2 \quad (3.5)$$

where ψ_0 , ψ are numbers which label the magnetic flux surfaces. For a simplified circular magnetic flux surface, ψ_0 and ψ can be replaced by r_0 and r respectively. We see that if temperature gradient is neglected, the helium ashes preferentially concentrate in the central region of the plasma core than fuel ions. This effect is similar to what we find from the above turbulent analysis. Clearly, highly-charged impurity particles are more accumulative within the inner confinement region of plasma core in either turbulent analysis or neoclassical theory.

4 Helium Transport Scaling Law Studies

4.1 Introduction

The transport problem, if turbulence is involved, has been recognized as a most difficult problem for centuries. In a tokamak fusion plasma, the transport of impurities is even more difficult to deal with because of the unique geometrical property and electromagnetic turbulences involved. This research is based on the experimental data and simulation results. The objective of this research is to explore the thermal helium particle transport scaling law in the tokamak fusion plasma core.

Based upon the transport model, we can write the helium flux as:

$$\Gamma_{\alpha} = -D(r) \frac{dn_{\alpha}}{dr} - n_{\alpha} V(r) \quad (4.1)$$

Considerable simulation work has been done to study the helium particle density profile evolution in the experiments by using various $D(r)$ and $V(r)$ profiles(5,6,7,8). Obviously, those results are only valid for a specific machine under certain conditions. Essentially, the helium transport behavior is determined by the local plasma characteristics. The $D(r)$ and $V(r)$, if model (4.1) is valid, should be some functions of the plasma parameters. In our research, we have studied the helium transport scaling law in the form of power law. We have also explored some constraints of the power law form scaling by applying the invariance principle.

4.2 Analysis Technique

From the helium transport experiment, the background plasma parameters can be obtained directly or indirectly as the functions of minor radius, i.e. $X(r)$, $Y(r)$, $Z(r)$,..... . The helium transport diffusion coefficient $D(r)$ and pinch velocity $V(r)$ can also be obtained by simulating the helium density profile evolution following helium puffing. We assume that the helium transport is determined by the local plasma conditions. Therefore, the diffusivity $D(r)$ and pinch velocity $V(r)$ should be functions of local plasma characteristic parameters, i.e.,

7

$$\begin{aligned} & (8Q_{\alpha} \langle \sigma v \rangle + 12T\gamma \langle \sigma v \rangle) f^3 - (8Q_{\alpha} \langle \sigma v \rangle + 16A_b \sqrt{T} + 36T\gamma \langle \sigma v \rangle) f^2 + \\ & + (2Q_{\alpha} \langle \sigma v \rangle - 8A_b \sqrt{T} + 27T\gamma \langle \sigma v \rangle) f - 6T\gamma \langle \sigma v \rangle = 0 \end{aligned} \quad (6.14)$$

Once f is solved from eq.(14), n is given by

$$n\tau_{\alpha} = \frac{4f}{\dots} \quad (6.15)$$

$$D(r) = D(X(r), Y(r), Z(r), \dots) \quad (4.2)$$

$$V(r) = V(X(r), Y(r), Z(r), \dots) \quad (4.3)$$

We assume the scaling law in the form of scaling law, i.e.,

$$D = D_0 X^\alpha Y^\beta Z^\gamma \dots \quad (4.4)$$

$$V = V_0 X^\theta Y^\delta Z^\lambda \dots \quad (4.5)$$

and seek the best fit fluid-scaling factors $\alpha, \beta, \gamma, \theta, \delta, \lambda, \dots$ by using the least-square method.

4.3 The best-fit helium transport scaling law for L-mode plasma on TFTR

By using Charge-Exchange Recombination Spectroscopy (CHERS) measurement, Synakowski et al.⁽⁸⁾ measured He^{+2} profiles at different times after a helium puffing into the L-mode plasma on TFTR. By simulating He^{+2} profile evolution, Synakowski et al.⁽⁸⁾ obtained the best-fitted spatial profiles of $D(r)$ and $V(r)$ based on the model (4.1). With the plasma data from this experiment, we explored the scaling law of D and V in the form of (4.4) and (4.5). Fig. 4 is the background plasma parameter profiles at a specific time after the helium puffing. The toroidal magnetic field B_t is assumed as : $B_t(r) = B_0 / (r+R)$, where B_0 is magnetic field in the axis and R is the tokamak major radius. Safety factor $q(r)$ profile comes from the toroidal current density $J(r)$ and $B_t(r)$. The experimental simulation result of $D(r)$ is also on Fig. 4. We assume that the local helium transport is determined by the local plasma parameters $[n_e, T_i, \frac{dn_e}{dr}, q, B_t]$. We use an least-square fit method to seek power-law-form scaling laws for both D and V , namely:

$$D \sim n_e^{s1} T_i^{s2} \left| \frac{dn_e}{dr} \right|^{s3} q^{s4} B_t^{s5}$$

$$V \sim n_e^{c1} T_i^{c2} \left| \frac{dn_e}{dr} \right|^{c3} q^{c4} B_t^{c5}$$

Fig. 4 The background plasma parameter profiles for the L-mode plasma on TFTR

where $s1, s2, s3, s4, s5$, and $c1, c2, c3, c4, c5$ are the scaling factors. The best-fit scaling expression for the diffusion coefficient obtained is:

$$D_{\alpha} \sim n_e^{-0.13} T_i^{-0.04} \left| \frac{dn_e}{dr} \right|^{0.00} q^{0.43} B_t^{-6.22} \quad (4.6)$$

where the units used correspond to n_e in $[10^{13} \text{cm}^{-3}]$, T_i in $[\text{KeV}]$, $\frac{dn_e}{dr}$ in $[10^{13} \text{cm}^{-4}]$ and B_t in $[\text{T}]$. Because of the large uncertainty in the diffusion coefficient measured in the experiment, and the large uncertainties in the measured plasma parameter profiles [at least 25% for helium density, and 10%~15% for the temperature and the electron density], the scaling law we obtained also has a large uncertainty. To illustrate this, we explored the two limits of D_{α} scaling based on the uncertainty range of the experimental results. In Fig.5, curve (d) is the diffusion coefficient profile from the experimental simulation result, curve (b) is the result of our best fit scaling given by Equation (4.6). The curve (a) and (b) are the two limiting cases. The corresponding scaling laws for the two limiting cases are :

$$D_{\alpha} \sim n_e^{-0.18} T_i^{-0.05} \left| \frac{dn_e}{dr} \right|^{0.00} q^{0.59} B_t^{-8.36} \quad \text{for curve (a) (4.6.1)}$$

$$D_{\alpha} \sim n_e^{-0.06} T_i^{-0.02} \left| \frac{dn_e}{dr} \right|^{0.00} q^{0.20} B_t^{-2.82} \quad \text{for curve (c) (4.6.2)}$$

We see that the diffusion coefficient is mainly affected by the magnetic field. The safety factor is also significant in the helium transport. According to this result, the electron density gradient does not contribute significantly to the helium transport.

In the same way, we get the best-fit scaling law for the pinch velocity as;

$$V_{\alpha} \sim n_e^{-0.06} T_i^{0.01} \left| \frac{dn_e}{dr} \right|^{0.00} q^{0.15} B_t^{-2.00} \quad (4.7)$$

where n_e is in $[10^{13} \text{cm}^{-3}]$; T_i is in $[\text{KeV}]$; $\frac{dn_e}{dr}$ is in $[10^{13} \text{cm}^{-4}]$; B_t is in $[\text{T}]$.

Fig. 5 The profiles of helium diffusion coefficient $D_\alpha(r)$ from the experiment result and our scaling law results.

In Fig. 6, the curve (A) is the pinch velocity profile from the experimental simulation ; the curve (C) is from our best fit scaling law for pinch velocity (4.7). We see that fit in the range from $r=18$ cm to 46 cm is very good. The experimental simulation profile of pinch velocity increases rapidly as spatial position approaches the wall. This is most probably due to the effect of helium recycling on the wall. The scaling law we find here, which is assumed to reflect the local helium transport behavior, should not be responsible for the effect of wall-recycling noted above. Curves (B) and (D) in Fig.6 are two cases of the scaling law for pinch velocity. Both are within the uncertainty range of experimental simulation result for pinch velocity. The purpose of showing both curves here is to test the sensitivity of the scaling factors on the actual $V_{\alpha}(r)$ profile. The corresponding scaling laws are given as;

$$V_{\alpha} \sim n_e^{-0.11} T_i^{0.01} \left| \frac{dn_e}{dr} \right|^{0.00} q^{0.30} B_t^{-3.89} \quad \text{for curve (B) (4.7.1)}$$

$$V_{\alpha} \sim n_e^{-0.01} T_i^{0.00} \left| \frac{dn_e}{dr} \right|^{0.00} q^{0.03} B_t^{-0.34} \quad \text{for curve (D) (4.7.2)}$$

From the above result, we see that the pinch velocity is mainly affected by the magnetic field; the electron density gradient and ion temperature are not important in the pinch velocity term of the transport flux formula. The scaling factors of magnetic field and safety factor are very sensitive to the experimental pinch velocity profile.

4.4 The application of helium transport scaling to the future tokamak design

Once we have the helium transport scaling law, we can calculate the helium confinement time by using the designed plasma profiles. Combining the energy confinement scaling law, the fusion ignition can be judged with the 0-D transport code.

Assuming one-dimensional geometry of the plasma core, the helium continuity equation is given as;

$$\frac{\partial n_{\alpha}}{\partial t} + \frac{1}{V} \frac{\partial [V \Gamma_{\alpha}]}{\partial r} = S_{\alpha}(r) \quad (4.8)$$

Fig. 6 The profiles of helium pinch velocity $V_\alpha(r)$ from the experiment result and our scaling law results.

where $n_\alpha = n_\alpha(r, t)$ is the helium density ; Γ_α is the helium flux which could be given by scaling law; $S_\alpha(r)$ is the thermal helium source in the plasma core; and $V' = \frac{dV(r)}{dr}$.

Averaging over the volume V , we obtain:

$$\left\langle \frac{\partial n_\alpha}{\partial t} \right\rangle = \frac{1}{V} \int \frac{\partial n_\alpha}{\partial t} dv$$

$$\langle S_\alpha(r) \rangle = \frac{1}{V} \int S_\alpha(r) dv$$

$$\left\langle \frac{1}{V'} \frac{\partial [V' \Gamma_\alpha]}{\partial r} \right\rangle = \frac{\langle n_\alpha \rangle}{\tau_\alpha}$$

$$\langle n_\alpha \rangle = \frac{1}{V} \int n_\alpha(r, t) dv$$

Therefore, eq.(4.8) becomes

$$\frac{\partial \langle n_\alpha \rangle}{\partial t} = \langle S_\alpha(r) \rangle - \frac{\langle n_\alpha \rangle}{\tau_\alpha} \quad (4.9)$$

In this case, the helium particle confinement time τ_α is defined as:

$$\tau_\alpha = \langle n_\alpha \rangle \frac{1}{\left\langle \frac{1}{V'} \frac{\partial [V' \Gamma_\alpha]}{\partial r} \right\rangle} \quad (4.10)$$

Γ_α could be obtained from the scaling law if the designed plasma profiles are given.

4.5 The invariance analysis of the helium transport scaling law for high- β plasma by using the collisionlessness and quasineutrality mode

The invariance principle states that: if the basic equations of the plasma are invariant under a group of transformations, the scaling law (empirical or semi-empirical) describing the plasma behavior must also be invariant under the same group of transformations⁽⁹⁾. For the typical tokamak fusion plasma, $T \sim 20\text{keV}$, $n_e \sim$

10^{14} cm^{-3} , Debye length $\sim 10^{-2} \text{ cm}$, and the ratio of particle collision frequency to plasma frequency is about 10^{-7} . Therefore, the collisionlessness-quasineutrality model is a reasonable approximation. The basic equations for this plasma are Vlasov and Maxwell equations.

$$\frac{\partial f_{\alpha}(\mathbf{x}, \mathbf{v}, t)}{\partial t} + (\mathbf{v} \cdot \nabla) f_{\alpha}(\mathbf{x}, \mathbf{v}, t) + \frac{q_{\alpha}}{m_{\alpha}} \left(\mathbf{E} + \frac{\mathbf{v} \times \mathbf{B}}{c} \right) \cdot \frac{\partial f_{\alpha}(\mathbf{x}, \mathbf{v}, t)}{\partial \mathbf{v}} = 0 \quad (4.11)$$

$$\nabla \times \mathbf{E} = -\frac{1}{c} \frac{\partial \mathbf{B}}{\partial t} \quad (4.12)$$

$$\nabla \times \mathbf{B} = \frac{4\pi}{c} \mathbf{J} \quad (4.13)$$

Equations (4.11)-(4.13) remain invariant under linear transformations;

$$\text{Tr.1: } f_{\alpha} = \beta^{-3} f_{\alpha}, \mathbf{v} = \beta \mathbf{v}, \mathbf{B} = \beta \mathbf{B}, \mathbf{E} = \beta^2 \mathbf{E}, \mathbf{J} = \beta \mathbf{J}, t = \beta^{-1} t \quad (4.14)$$

$$\text{Tr.2: } f_{\alpha} = d^{-2} f_{\alpha}, \mathbf{x} = d \mathbf{x}, \mathbf{B} = d^{-1} \mathbf{B}, \mathbf{E} = d^{-1} \mathbf{E}, \mathbf{J} = d^{-2} \mathbf{J}, t = dt \quad (4.15)$$

where β and d are any transformation constants. Next we assume that the helium transport scaling law is in the form of:

$$\Gamma_{\alpha} = -n_e^{x_1} n_{\alpha}^{x_2} T^{x_3} q^{x_4} \frac{dn_{\alpha}}{dr} - V n_{\alpha} \quad (4.16)$$

where $x_1, \dots, x_4$ are exponents to be determined by fitting to experimental data.

Under transformations Tr.1 and Tr.2, we obtain:

$$\Gamma_{\alpha} = \frac{\beta}{d^2} \Gamma_{\alpha}$$

$$n_{\alpha} = \frac{1}{d^2} n_{\alpha}, n_e = \frac{1}{d^2} n_e \text{ (assumed)}$$

$$T = \frac{\beta^2}{d^2} T, q = q$$

$$\frac{dn_{\alpha}}{dr} = \frac{1}{d^3} \frac{dn_{\alpha}}{dr}$$

Then by applying the invariance principle, we have

$$x_1 + x_2 = -1, \quad x_3 = \frac{1}{2} \quad (4.17)$$

Therefore, the constraints for the diffusion coefficient scaling are given as:

$$D \sim \left[\frac{n_{\alpha}}{n_e}\right]^{x_2} q^{x_4} \frac{T^{0.5}}{n_e} \quad (4.18)$$

where the scaling factors have been reduced from four to two. Thus, we see that the scaling law for D can be written as:

$$D \sim \frac{T^{0.5}}{n_e} F\left[\frac{n_{\alpha}}{n_e}, q\right] \quad (4.19)$$

where $F\left[\frac{n_{\alpha}}{n_e}, q\right]$ is a function of $\frac{n_{\alpha}}{n_e}$ and q . With this result, the next step is to find the scaling factors using a fit to experiment data. This illustrates the basic power that can be applied using the invariant principle. In future work, we may use this technique with other plasma model and form for the scaling law.

5 Conclusions

5.1 As the ratio of helium particle confinement to energy confinement (τ_{α}/τ_E) increases, (i.e., the helium ash accumulation is enhanced), the fusion ignition curve shrinks. This is crucial in D-T devices and, as shown here, is even more important for D- ^3He designs such as ARIES-3.

5.2 The fusion ignition curve for D- ^3He is also very sensitive to the radiation reflectivity at the first wall. For the ARIES-3 design parameters, the radiation reflectivity must exceed 95% to achieve ignition according to our 0-D calculation.

5.3 Ash accumulation is particularly serious because, unlike other high-Z impurities, alphas are born and thermalized in the volume of the plasma.

Consequently, divertor action does not prevent the entry of helium ash into the plasma as it does for wall impurities. Therefore, to achieve ignition or sustain steady-state operation, effective techniques for enhancing the ash transport outward must be explored for future tokamak designs.

5.4 The best fit scaling law of D_α and V_α in the plasma parametric space $(n_e, T_i, \frac{dn_e}{dr}, q, B_t)$ for L-mode operation on TFTR is found to be:

$$D_\alpha \sim n_e^{-0.13} T_i^{-0.04} \left| \frac{dn_e}{dr} \right|^{0.00} q^{0.43} B_t^{-6.22}$$

$$V_\alpha \sim n_e^{-0.06} T_i^{-0.01} \left| \frac{dn_e}{dr} \right|^{0.00} q^{0.15} B_t^{-2.00}$$

This result suggests that under these conditions in TFTR, helium transport is mainly affected by the toroidal magnetic field B_t and the safety factor q . Surprisingly, the gradient of the electron density does not appear to be important.

5.5 An invariance analysis for the collisionless quasineutrality plasma has shown that the number of scaling factors can be reduced for the assumed form scaling law. This will be studied further later.

6 Study of Helium Ash Control

6.1 Introduction

Due to poor confinement of the L-mode plasma, ignition of the fusion reaction is not likely achievable in this mode. The confinement time was almost doubled when the H-mode was found, giving a hope that ignition might be achieved in the H-mode. However, the helium ash is better confined than the background hydrogen ions in the H-mode. Thus, helium ash tends to accumulate within the plasma, enhancing Bremsstrahlung losses, making ignition difficult, if not impossible. Unless problem of helium ash exhaustion is solved, it is not possible to take full advantage of H-mode operation.

6.2 Dynamic model

A rigorous description of plasma dynamics is exceedingly complex and well beyond the needs of a study such as this. Thus, we seek to construct the simplest model which retains the essential physics of the phenomena which we wish to investigate. We choose to construct our model from physical arguments and to resort to previous work for approximate mathematical representations of the various phenomena. We start with the assumption that the time scale of interest for the variation of the average particle and energy densities in the plasma is long with respect both to the self-equilibration times for ions and electrons and to the alpha slowing-down times. Thus, we envision ions or electrons which are injected into the plasma as instantaneously equilibrating in energy with particles in the plasma, through collisions. Similarly, the alpha particles produced in the D-T fusion reaction are assumed to instantaneously distribute their energy among the ions and electrons. Thus, we are able to characterize the average energy of particle by a single parameter which we denote as a temperature, T , which is related to the energy by $E = \frac{3}{2}kT$, where k is the Boltzmann constant.

The fundamental equations governing the evolution of the plasma are taken to be eq.(1)-(3) as follow. The helium ion density, n_α , evolves as

$$\frac{dn_\alpha}{dt} = \left(\frac{n_h}{2}\right)^2 \langle \sigma v \rangle - \frac{n_\alpha}{\tau_\alpha^*} \quad (6.1)$$

where $n_h \equiv$ hydrogen ion density, and $\tau_\alpha^* \equiv$ effective helium confinement time. This equation implies that supra-thermal α particles slow instantaneously and completely within the plasma. n_h evolves as

$$\frac{dn_h}{dt} = S - 2\left(\frac{n_h}{2}\right)^2 \langle \sigma v \rangle - \frac{n_h}{\tau_p} \quad (6.2)$$

where $S \equiv$ refueling rate and $\tau_p \equiv$ hydrogen confinement time. This equation implies that a 50%-50% mixture of D-T fuel is maintained during the plasma burn. The thermal energy evolves as:

$$\begin{aligned} & \frac{d}{dt} \left[\frac{3}{2} (n + n_h + n_\alpha) T \right] \\ &= P_{aux} + \left(\frac{n_h}{2} \right)^2 \langle \sigma v \rangle Q_\alpha - A_b Z_{eff} n^2 \sqrt{T} - \frac{\frac{3}{2} (n_e + n_i + n_\alpha) T}{\tau_E} \end{aligned} \quad (6.3)$$

where n = electron density, τ_E = energy confinement time, $A_b = 3.33 \times 10^{-15} \frac{\text{cm}^3 \sqrt{\text{KeV}}}{\text{sec}}$ and $Q_\alpha = 3.5 \text{ MeV}$. This equation assumes that electrons and ions have the same temperature. The neutrality condition relates n , n_α and n_h as

$$n = n_h + 2n_\alpha \quad (6.4)$$

Choosing the electron density, n , the ratio of densities of helium and electron, $f \equiv \frac{n_\alpha}{n}$, and the temperature, T , as the dependent variables, the state equations will read as

$$\dot{n} = S - \left(\frac{1-2f}{\tau_p} + \frac{2f}{\tau_\alpha^*} \right) n \equiv g_1 \quad (6.5)$$

$$\dot{f} = \frac{n(1-2f)^2 \langle \sigma v \rangle}{4} - \frac{fS}{n} + \left(\frac{1}{\tau_p} - \frac{1}{\tau_\alpha^*} \right) (1-2f) f \equiv g_2 \quad (6.6)$$

$$\begin{aligned} \dot{T} = & \left(T + \frac{2}{3} Q_\alpha \right) \frac{1}{2-f} \frac{n(1-2f)^2 \langle \sigma v \rangle}{4} + \frac{2P_{aux}}{3(2-f)n} - \frac{2TS}{(2-f)n} - \frac{2A_b n(1+2f)\sqrt{T}}{3(2-f)} \\ & - \frac{T}{\tau_E} + \frac{T}{\tau_p} \frac{2(1-2f)}{2-f} + \frac{T}{\tau_\alpha^*} \frac{3f}{2-f} \equiv g_3 \end{aligned} \quad (6.7)$$

In vector notation, eq.(5)-(7) can be written as

$$\dot{\mathbf{x}} = \mathbf{g}(\mathbf{x}, \mathbf{u}) \quad (6.8)$$

where $\mathbf{x} = \begin{pmatrix} n \\ f \\ T \end{pmatrix}$, $\mathbf{u} = \begin{pmatrix} S \\ P_{aux} \end{pmatrix}$ and $\mathbf{g} = \begin{pmatrix} g_1 \\ g_2 \\ g_3 \end{pmatrix}$. The reaction parameter $\langle \sigma v \rangle$ is a function of the temperature; the empirical formula of Hively⁽¹⁰⁾ are used in this work:

$$\begin{aligned} \langle \sigma v \rangle = \exp \left[-\frac{21.377592}{T^{0.2915}} - 25.204054 - 7.1013427 \times 10^{-2} T + \right. \\ \left. + 1.9375451 \times 10^{-4} T^2 + 4.9246592 \times 10^{-6} T^3 - 3.9836572 \times 10^{-8} T^4 \right] \end{aligned} \quad (6.9)$$

where: T is in KeV, and is in the range $1 \leq T \leq 80 \text{ KeV}$; $\langle \sigma v \rangle$ is in cm^3/s .

6.3 Equilibrium

We denote the equilibrium solution as $\mathbf{x}_0, \mathbf{u}_0$. Then from eqs. (5)-(7) we obtain

$$S_0 - \left(\frac{1-2f_0}{\tau_p} + \frac{2f_0}{\tau_\alpha^*} \right) n_0 = 0 \quad (6.10)$$

$$\frac{n_0(1-2f_0)^2 \langle \sigma v(T_0) \rangle}{4} - \frac{f_0 S_0}{n_0} + \left(\frac{1}{\tau_p} - \frac{1}{\tau_\alpha^*} \right) (1-2f_0) f_0 = 0 \quad (6.11)$$

$$\begin{aligned} \left(T_0 + \frac{2Q_\alpha}{3} \right) \frac{1}{2-f_0} \frac{n_0(1-2f_0)^2 \langle \sigma v(T_0) \rangle}{4} + \frac{2P_{aux0}}{3(2-f_0)n_0} - \frac{2T_0 S_0}{(2-f_0)n_0} \\ - \frac{2A_b n_0 (1+2f_0) \sqrt{T_0}}{3(2-f_0)} - \frac{T_0}{\tau_E} + \left(\frac{2(1-2f_0)}{\tau_p} + \frac{3f_0}{\tau_\alpha^*} \right) \frac{T_0}{2-f_0} = 0 \end{aligned} \quad (6.12)$$

In vector notation this result can be written as:

$$\mathbf{g}(\mathbf{x}_0, \mathbf{u}_0) = \mathbf{0} \quad (6.13)$$

Eq. (10)-(12) are a set of algebraic equations with five unknowns, i.e. n_0, f_0, T_0, S_0 and P_{aux0} . Given any two of n_0, f_0, T_0, S_0 and P_{aux0} , we can solve for the equilibrium. In this report, we assume constant ratios of $\eta = \frac{\tau_p}{\tau_E}$ and $\gamma = \frac{\tau_\alpha^*}{\tau_E}$. For the study of ignition, let $P_{aux0} = 0$. We will drop the subscript in the following discussion.

For any given T, f are the roots of the following polynomial, in the range $[0, \frac{1}{2}]$,

$$\begin{aligned}
& (8Q_\alpha \langle \sigma v \rangle + 12T\gamma \langle \sigma v \rangle) f^3 - (8Q_\alpha \langle \sigma v \rangle + 16A_b \sqrt{T} + 36T\gamma \langle \sigma v \rangle) f^2 + \\
& + (2Q_\alpha \langle \sigma v \rangle - 8A_b \sqrt{T} + 27T\gamma \langle \sigma v \rangle) f - 6T\gamma \langle \sigma v \rangle = 0
\end{aligned} \tag{6.14}$$

Once f is solved from eq.(14), n is given by

$$n\tau_E = \frac{4f}{\gamma(1-2f)^2 \langle \sigma v \rangle} \tag{6.15}$$

Having T , f and $n\tau_E$, we can find S from:

$$S\tau_E^2 = \left(\frac{1-2f}{\eta} + \frac{2f}{\gamma} \right) n\tau_E \tag{6.16}$$

6.4 Operating Window

In this section, we will investigate how the equilibrium changes with the constants η and γ . As in the previous section, here we are dealing with quantities at equilibrium. We will also drop the subscript in the following discussion. From eqs.(10)-(12), we obtain:

$$\gamma = \frac{[8f^3 - 8f^2 + 2f] \langle \sigma v \rangle Q_\alpha - [16f^2 + 8f] A_b \sqrt{T}}{[-12f^3 + 36f^2 - 27f + 6] \langle \sigma v \rangle T} \tag{6.17}$$

$$\begin{aligned}
\gamma = & \frac{1}{n\tau_E \langle \sigma v \rangle (8A_b n\tau_E \sqrt{T} + 9T)^2} \left\{ 2n\tau_E \langle \sigma v \rangle Q_\alpha (8A_b n\tau_E \sqrt{T} + 9T) \right. \\
& - 4(A_b n\tau_E \sqrt{T} + 3T) [(4A_b n\tau_E \sqrt{T} - 3T) + \\
& \left. + \sqrt{(4A_b n\tau_E \sqrt{T} - 3T)^2 + 4n\tau_E \langle \sigma v \rangle Q_\alpha (8A_b n\tau_E \sqrt{T} + 9T)} \right\}
\end{aligned} \tag{6.18}$$

Eq.(17) gives contours of γ in the f - T plane, as shown in fig.7. equilibrium is not possible if $\gamma = \frac{\tau_\alpha^*}{\tau_E} > 15.3$. Equation (18) gives contours of γ in $\tau_E n$ - T plane, as shown in fig.8.

Fig. 7 Contours of γ in f - T plane. We can see that there is no possible equilibriums if

$$\gamma = \frac{\tau_a^2}{\tau_e} > 15.3.$$

Fig. 8 Contours of γ in τ_c - τ plane.

6.5 Non-linear Control Model

We define a Cost Function V as:

$$V(\mathbf{x}(t_0), \mathbf{u}(\cdot), t_0) = \int_{t_0}^{\infty} l(\mathbf{x}(\tau), \mathbf{u}(\tau), \tau) d\tau \text{ with } (l(\dots) \geq 0) \quad (6.19)$$

The Hamilton-Jacobi equation is:

$$-\frac{\partial V}{\partial t} = \min_{\mathbf{u}} \left[l(\mathbf{x}, \mathbf{u}, t) + \frac{\partial V}{\partial \mathbf{x}} \mathbf{f}(\mathbf{x}, \mathbf{u}) \right] \quad (6.20)$$

The minimization of the RHS occurs when:

$$\frac{\partial}{\partial \mathbf{u}} \left[l(\mathbf{x}, \mathbf{u}, t) + \frac{\partial V}{\partial \mathbf{x}} \mathbf{f}(\mathbf{x}, \mathbf{u}) \right] = 0 \quad (6.21)$$

The solution of the above equation is denoted as $\mathbf{u}^* = \mathbf{u}^*(\mathbf{x}, t, \frac{\partial V}{\partial \mathbf{x}})$. Substituting this result back into the Hamilton-Jacobi equation, we obtain:

$$-\frac{\partial V}{\partial t} = l(\mathbf{x}, \mathbf{u}^*(\mathbf{x}, t, \frac{\partial V}{\partial \mathbf{x}})) + \frac{\partial V}{\partial \mathbf{x}} \mathbf{f}(\mathbf{x}, \mathbf{u}^*(\mathbf{x}, t, \frac{\partial V}{\partial \mathbf{x}})) \quad (6.22)$$

This is a partial differential equation with a boundary condition $V(\mathbf{x}(\infty), \infty) = 0$.

Eq. (22) is a non-linear problem, which is very difficult, if not impossible, to deal with. Thus, we will not discuss this topic further here. Instead, we will assume small deviation from the equilibrium and linearize the problem as described below.

6.6 Linearization

We define matrix **A** as the matrix with element in row *i* and column *j* as $\left(\frac{dg_i}{dx_j}\right)_{\mathbf{x}_0, \mathbf{u}_0}$. The **B** matrix has elements $\left(\frac{dg_i}{du_j}\right)_{\mathbf{x}_0, \mathbf{u}_0}$. With these partial derivatives,

Taylor's expansion of our state equations near $\mathbf{x}_0, \mathbf{u}_0$ can be written as:

$$\dot{\mathbf{x}}_0 + d\dot{\mathbf{x}} = \mathbf{g}(\mathbf{x}_0, \mathbf{u}_0) + \mathbf{A}d\mathbf{x} + \mathbf{B}d\mathbf{u} + \text{higher order terms.} \quad (6.23)$$

The equilibrium solution, $\mathbf{x}_0$, is a constant, so that $\dot{\mathbf{x}}_0 = 0$. We also have $\mathbf{g}(\mathbf{x}_0, \mathbf{u}_0) = 0$.

Thus, the linearized equations are:

$$d\dot{\mathbf{x}} = \mathbf{A}d\mathbf{x} + \mathbf{B}d\mathbf{u} \quad (6.24)$$

Stability of the equilibrium points are determined by the real part of the eigenvalues of matrix **A**. If the real part of any of the eigenvalues is positive, then the equilibrium is unstable. Next, we will check the controllability of our linearized system model by transforming it into diagonalized form. One should keep in mind that our original system is not linear, so if our linearized system is controllable, our original system will be controllable only at the vicinity of the selected equilibrium point. This property will be checked by numerical simulation.

Once the confinement mode, L or H, is selected, and an equilibrium is chosen as the operating point, the controllers at our disposal are the auxiliary heating P_{aux} and the refueling rate *S*. Ashby & Hughes⁽¹¹⁾ has demonstrated that the plasma is controllable with the refueling alone if the density excursion do not exceed about $\frac{dn}{n} \sim \frac{\tau_E}{2\tau_p}$. Since in their model, helium ash buildup was not considered. Here in our model, we will demonstrate the controllability of plasma with refueling alone with the ash buildup being considered.

Mathematically, for our special case of single input system (refueling alone), if the determinant of matrix

$$C=[b_1, Ab_1, (A)^2b_1] \quad (6.25)$$

is not zero, the system is controllable. In eq.(25), b_1 is the first column of matrix B . Numerically, one may always get non-zero $\det(C)$, thus we will not use the method of checking whether $\det(C)=0$. We use instead the method of diagonalization.

Suppose the columns of matrix T is the eigenvectors of matrix A , then we can select a new set of state variables dx' which relates to dx as

$$dx = Tdx' \quad (6.26)$$

Our linearized model will become

$$Tdx' = ATdx' + b_1 dS \quad (6.27)$$

Multiply by T^{-1} , the inverse of T , gives

$$dx' = T^{-1}ATdx' + T^{-1}b_1 dS = A'dx' + b'dS \quad (6.28)$$

Since T is composed of eigenvectors of A ,

$$A' = T^{-1}AT = \text{diagonalized form} = \begin{pmatrix} \lambda_1 & 0 & 0 \\ 0 & \lambda_2 & 0 \\ 0 & 0 & \lambda_3 \end{pmatrix} \quad (6.29)$$

where $\lambda_1, \lambda_2, \lambda_3$ are eigenvalues of A . The system is controllable with refueling alone if and only if

- i) eigenvalues $\lambda_1, \lambda_2, \lambda_3$ are distinct,
- ii) no element of b' is zero.

Because of the rounding errors on a computer, one will have difficulty to determine the distinctness of λ 's or the zero-ness of elements of b' . We use the criteria of distinctness as

$$\frac{|\lambda_i - \lambda_j|}{\max(|\lambda_1|, |\lambda_2|, |\lambda_3|)} > 10^{-3} \quad (i, j = 1, 2, 3) \quad (6.30)$$

If we adopt a simple proportional state feedback control

$$dS = -KdX = -(K_1, K_2, K_3) \begin{pmatrix} dn \\ df \\ dT \end{pmatrix} \quad (6.31)$$

we have a handy formula, Ackermann's formula, to determine the appropriate feedback gains $K=(K_1, K_2, K_3)$ after we specify the desired closed-loop pole loci

$$K = e^T C^{-1} \alpha(A) \quad (6.32)$$

where $e^T = (0, 0, 1)$, C^{-1} is the inverse of C as defined by eq(25). $\alpha(A)$ is a polynomial of matrix A

$$\alpha(A) = (A - p_1 I)(A - p_2 I)(A - p_3 I) \quad (6.33)$$

where p_1, p_2, p_3 are closed-loop poles, and I =unit matrix(12).

6.7 Computer Program

A corresponding FORTRAN program, named ASH, has been written on MFE Cray computer. This code will search for the equilibrium point of state equations (5)-(7) as described in section 1.3. It will linearize the state equations and calculate the feedback gains as described in section 1.6. It then simulates the evolution of the plasma from an initial condition.

6.8 Results

Table I lists possible equilibriums of the plasma, without auxiliary heating. The last row in the table is the positive eigenvalues of our 3-D model. The values $\frac{1}{\lambda}$ indicates a time scale for the rate of change of the plasma. The results listed in table I indicate two things:

(1) In section 1.2 when we made up our dynamic model, we assumed that any change in the plasma is slow compared with the alpha slowing down time. In retrospect, we assured that our previous assumption is valid.

(2) Any excursion of the plasma is slow enough for the controller to react and compensate the change, enabling us to maintain a steady state.

Table I
Characteristics of equilibrium

	case I	case II	case III
τ_E (s)	10	7	10
η	3	3	3
γ	9	3	9
T (KeV)	13.3	10.7	8.31
n_h (cm ⁻³)	3.0×10^{13}	4.93×10^{13}	7.0×10^{13}
S (1/s.cm ³)	1.1×10^{12}	2.5×10^{12}	2.5×10^{12}
λ (1/s)	0.109	0.236	0.269
$1/\lambda$ (sec)	9.17	4.24	3.72

Designed ITER operating points⁽¹³⁾ are indicated in fig.8 as point A for L-mode and point B for H-mode. It is clear that under L-mode, ITER will not be ignited. The H-mode is ignited only if the ratio $\frac{\tau_{\alpha}^*}{\tau_E}$ is less than about 7. From fig.8, we can conclude two things:

(1) Since the γ -contours are crowded around point B in fig.8, the ignition of ITER H-mode design will be very sensitive to the value of $\frac{\tau_{\alpha}^*}{\tau_E}$. This high sensitivity is undesirable.

(2) The H-mode design point is deep in the unstable region. This design is similar to the case II shown in table I. Thus, the time scale associated with any thermal excursion of the plasma is about half of the confinement time. For the ITER design, the controller must be able to react within about 2 seconds.

References

- 1 Hu, S., et al., Fusion Studies Lab., University of Illinois.
- 2 Reiter, D., et al., Burn Condition for Fusion Plasmas, Helium Particle Confinement and Exhaust Efficiency. January, 1990. ISSN 0366-0885
- 3 Braginskii, S.I. Transport Processes In a Plasma. Reviews of Plasma Physics, Vol. 1, by M.A. Leontovich, (1965), 205.
- 4 Hirshman, S.P., D.J. Sigmar, Neoclassical Transport of Impurities In Tokamak Plasmas, Vol. 21, No. 9 (1981), 1121.
- 5 Fonck, R.J. and Hulse, R.A., " He^{++} Transport in the PDX Tokamak ", Physics Review Letters, Vol.52, 1984, pp.530-533.
- 6 Jones, T.T., et al., " Simulated Ash Transport Experiments in JET using Helium Neutral Beam and Charge Exchange Spectroscopy", Proceedings of 18th EPS conference on Controlled Fusion and Plasma Physics, FRG, June, 1991, pp121 - 124.
- 7 Redi, M. H., et al., "Transport Simulations of ITER Helium Exhaust Using the Recent Data from TFTR, TEXTOR and JET-60", PPPL-2765, Princeton University, Princeton, New Jersey, July, 1991.
- 8 Synakowski, E.J., et al., " Measurements of Radial Profiles of He^{+2} Transport Coefficients on TFTR Tokamak", Physics Review Letters, Vol. 65, 1990, pp.2255-2258.
- 9 Connor, J.W. and Taylor, J.B., "Scaling laws For Plasma Confinement", Nuclear Fusion 17, May, 1977, pp. 1047- 1055. 10. Connor, J.W. "Invariance Principle and Plasma Confinement", Plasma Physics and Controlled Fusion, Vol. 30, No.6, pp.619-650, 1988.
- 10 Hively, L. M. *Nucl. Fusion*, **17:4** (1977) 873.
- 11 Ashby & Hughes. *Nucl. Fusion*. **20:4** (1980) 451.

- 12 Franklin, Powell & Emami-Naeini. *Feedback Control of Dynamic Systems*. Addison-Wesley Pub. Co. (1988), chap. 6.
- 13 Post, D. E. *et al.*, "ITER Operating Scenarios." ITER/US/91/PC-06-2.

**DATE
FILMED**
7 / 9 / 92