AIM

Association for Information and Image Management

1100 Wayne Avenue, Suite 1100
Silver Spring, Maryland 20910
301/587-8202

Centimeter

Inches

MANUFACTURED TO AIM STANDARDS
BY APPLIED IMAGE, INC.

1 of 1

BIOTECHNOLOGY OF INDIRECT LIQUEFACTION

CONTRACT NO. DE-AC22-88 PC79815

FINAL REPORT

May 7, 1990

Co-Principal Investigators:

**Rathin Datta
Mahendra K. Jain
R. Mark Worden**

Research Personnel:

**Andrew J. Grethlein
Bhupendra Soni**

Advisors:

**J. Gregory Zeikus
Hans Grethlein**

**Michigan Biotechnology Institute
P. O. Box 27609
3900 Collins Road
Lansing, MI 48909**

Telephone (517) 337-3181

TABLE OF CONTENTS

1.	Executive Summary	1
2.	Background	4
3.	Goals and Objectives	5
4.	Technical Approach	7
5.	Significant Accomplishments	9
6.	Results	10
	Acidogenic Phase	10
	Batch Culture Studies	11
	Continuous Culture Studies	18
	Continuous Cell-Recycle Studies	24
	Solventogenic Phase	26
7.	Conclusions and Recommendations	39
8.	Presentations, Publications and Patents	40
9.	References	43

LIST OF TABLES

1.	Percent of Available Electrons Contained in Products	16
2.	Fermentation Stoichiometry of CO in <i>Butyribacterium methylotrophicum</i> in relation to pH	22
3.	Electron Partitioning During pH-Dependent CO Fermentation by <i>Butyribacterium methylotrophicum</i>	22
4.	Carbon Partitioning During pH-Dependent CO Fermentation by <i>Butyribacterium methylotrophicum</i>	23
5.	Molar Yield Coefficients During pH-Dependent CO Fermentation by <i>Butyribacterium methylotrophicum</i>	23
6.	Product Ratios During pH-Dependent CO Fermentation by <i>Butyribacterium methylotrophicum</i>	24
7.	Specific Product Weight Ratios During pH-Dependent CO Fermentation by <i>Butyribacterium methylotrophicum</i>	24
8.	Product Concentrations in Fermentation Broth During pH Dependent CO Fermentations by <i>Butyribacterium methylotrophicum</i> (g/L)	25
9.	Continuous Cell Recycle Fermentations of Carbon Monoxide by <i>Butyribacterium methylotrophicum</i> Steady State Operation	26
10.	Continuous Cell Recycle Fermentation of Carbon Monoxide by <i>Butyribacterium methylotrophicum</i> Steady State Operation	27
11.	Analysis of Mutants of <i>Clostridium acetobutylicum</i> Obtained after NTG Mutagenesis	28
12.	Analysis of Mutants of <i>Clostridium acetobutylicum</i> Obtained After EMS Mutagenesis	29
13.	Comparison of Wild Type and Mutant Strain of <i>Clostridium acetobutylicum</i> (Batch Fermentation)	30
14.	Continuous Multistage Fermentation of <i>Clostridium acetobutylicum</i> Mutant E-604	31
15.	Comparison of E-604 and Wild Type for Butyrate Uptake of Stage 2 Effluent for 24 Hours	32

16.	Influence of Different Levels of Butyrate Supplementation on Global Performance of Stage 2 Effluents Incubated at 30°C (E-604 Mutant)	33
17.	Batch completion of Stage 3 Effluent at High Concentration of Carbohydrate at Different Temperatures (E-604 Mutant)	35

LIST OF FIGURES

1.	Constant pH Fermentation with Continuous CO Gas Feed	12
2.	pH-Shift Batch Fermentation with Continuous CO Gas Feed	13
3.	Batch Fermentation of MeOH/CO/CO ₂ at a pH of 6.8	16
4.	Batch Fermentation of MeOH/CO/CO ₂ at a pH of 6.8	17
5.	Product Formation and Substrate Utilization Pattern in Two-Stage Cell recycle System.	35
6.	Product Formation and Substrate Utilization Pattern in Two-Stage Cell Recycle System. Feed Carbohydrate conc. was 95.6 g/l.	36
7.	Product Formation and Substrate Utilization Pattern in Two-Stage Cell Recycle System. Feed Carbohydrate Conc. was 87.0 g/l.	38

Executive Summary

The project on biotechnology of indirect liquefaction was focused on conversion of coal derived synthesis gas to liquid fuels using a two-stage, acidogenic and solventogenic, anaerobic bioconversion process. The acidogenic fermentation used a novel and versatile organism, *Butyribacterium methylotrophicum*, which was fully capable of using CO as the sole carbon and energy source for organic acid production. This organism initially produced acetate as the sole product from CO, and sometimes very minor amounts of butyrate. In extended batch CO fermentations the organism was induced to produce butyrate at the expense of acetate at low pH values. An equimolar acetate/butyrate product ratio was achieved in these conditions. Long-term, steady-state operation was achieved during continuous CO fermentations with this organism, and at low pH values (a pH of 6.0 or less) minor amounts of butanol and ethanol were produced. During continuous, steady-state fermentations of CO with cell recycle, concentrations of mixed acids and alcohols were achieved (approximately 12 g/l and 2 g/l, respectively) which are high enough for efficient conversion in stage two of the indirect liquefaction process. The metabolic pathway to produce 4-carbon alcohols from CO was a novel discovery and is believed to be unique to our CO strain of *B. methylotrophicum*.

In the solventogenic phase, the parent strain ATCC 4259 of *Clostridium acetobutylicum* was mutagenized using nitrosoguanidine and ethyl methane sulfonate. The E-604 mutant strain of *Clostridium acetobutylicum* showed improved characteristics as compared to parent strain ATCC 4259 in batch fermentation of carbohydrates. The mutant strain (E-604) was, therefore, evaluated in continuous multistage fermentation process for carbohydrate conversion rates, butanol yield and butyrate uptake. The exceptionally high

concentration of solvent (30-31 g/l) was achieved by the mutant strain with about 90 g/l of substrate consumption. The mutant strain (E-604) was evaluated for butyrate uptake and very high levels of butyrate (8-10 g/l) were utilized for butanol production compared to wild strain (ATCC 4259) under controlled conditions. In the continuous cell recycling, using carbon composite membrane, solvent production rate of 2.0 g/l/h was achieved and significant improvements in the butyrate uptake rates were noted under controlled conditions.

Some significant accomplishments achieved in both acidogenic and solventogenic fermentation are:

- Production of butyrate (C₄ acid) directly from CO by shifting fermentation pH and changing metabolic regulation.
- Novel discovery of butanol production (C₄ alcohol) from direct fermentation of CO by *B. methylophilum* as the sole carbon and energy source.
- Demonstration of significant level of butanol (1 g/l) from direct fermentation of CO in continuous, steady state fermentation by *B. methylophilum*.
- Demonstration of more than 5 weeks of operation of cell-recycle without membrane fouling.
- Production of an improved asporogenic mutant strain of *Clostridium acetobutylicum* with increased stability, productivity, and product tolerance.
- Demonstration of high levels of butyrate (10 g/l) uptake by the mutant strain of *C. acetobutylicum*.
- Demonstration of high levels of carbohydrate tolerance, and exceptionally high concentration of butanol (>20 g/l) and solvent (~30 g/l) production by the mutant strain of solventogenic bacteria.

- Achievement of 3-fold increase in the rate of solvent production by the mutant strain of *C. acetobutylicum* using cell recycle.
- Demonstration of continuous, multistage fermentation for solvent production by the stable asporogenic mutant strain of *C. acetobutylicum*.

These results have already been communicated through 7 presentations and 3 manuscripts. About 6 additional manuscripts are being submitted for publication. In addition, one patent application has also been submitted.

In light of these significant achievements the following recommendations are made for further development work:

1. The unique discovery of direct conversion of CO to butanol should be further investigated by physiological studies.
2. The fermentation process for this unique bioconversion should be further developed and process parameters such as productivity, concentration and mass transfer needs should be determined.
3. Strain improvement of *B. methylotrophicum* and isolation of new strains with high product tolerance and conversion of CO to butanol should be conducted.
4. Process scale-up parameters and preliminary design and economics should be determined for both the acidogenic and solventogenic processes.

Background

The use of coal-derived synthesis gas as an industrial feedstock for chemical processing has provided an increasingly attractive alternative to the present petroleum-based chemicals production stemming from recent developments in C_1 chemistry and gasification technology. One of the major drawbacks in utilizing coal-derived gases for chemical and fuel production is the required removal of catalyst poisons such as hydrogen sulfide (H_2S), carbonyl sulfide (COS), and other trace contaminants from the synthesis gas. The levels of sulfur gases are relatively high, and these gases must be removed prior to catalytic conversion. These purification steps are energy-intensive and add significantly to the product costs, particularly for coals having a high sulfur content (1). Biological conversion of synthesis gas offers some key advantages over more conventional chemical processing routes. These include elimination of sulfur gas removal from the synthesis gas, elimination of requirement of gas-shift operations, operation of fermentation process at low temperatures and pressure, and a high degree of selectivity and efficiency for CO conversion; thus, reducing both operating and capital costs. The proposal of Michigan Biotechnology Institute on biological conversion of synthesis gas to liquid fuels using a two-stage process was accepted by PETC-DOE which resulted into this contract for a two-year period.

At the inception of this contract, the CO strain of *Butyribacterium methylotrophicum* was strictly an acetate producing organism when grown on CO. The selection of this strain for use in the first stage of the indirect liquefaction process was governed by its ability to utilize CO as well as methanol/ CO_2 in order to produce acetate or butyrate, respectively. It required few growth factors, did not produce slime, and had simple medium requirements.

These factors made it ideally suited for study as a potential biocatalyst for conversion of synthesis gas to mixed acids.

In the acidogenic stage of bioconversion of coal derived gases, acetic acid and butyric acid are the major end-products of *B. methylotrophicum*. These acids can be biologically reduced to solvents by *Clostridium acetobutylicum*. The classic fermentation of glucose to acetone, butanol and ethanol (ABE) with the known strains can produce about 10-12 g/l of butanol. In the previous studies on biological reduction of organic acids, about 2-3 g/l of butyric acid was utilized for the solvent production (2,3). Thus, *C. acetobutylicum* was selected for conversion of organic acids to solvents in a second stage.

It is known that distillation cost could be reduced to half if butanol concentrations of 20 g/l could be achieved (4). The desired high concentration of butanol had not been achieved by existing strains developed for solvent production. Moreover, the stable operation of chemostat culture could only be achieved under phosphate limitation at the reduced solvent productivity (5).

Goals and Objectives

The first stage of this bioconversion process was an acidogenic bioconversion of CO and/or methanol/CO₂ by the *B. methylotrophicum* to acetate and butyrate, while the second stage was solventogenic where the end products of first stage were converted to acetone and butanol by *C. acetobutylicum*. Several tasks and objectives for acidogenic stage were defined, achieved, and exceeded during the time of the contract. Specifically, the objectives for the acidogenic stage were to: 1) develop and operate a chemostat fermentation for synthesis gas (CO) conversion; 2) study the effect of electron donors such as methanol on product

formation during growth of *B. methylotrophicum* on CO; 3) develop and operate a biocatalyst recycle system for biotransformation of synthesis gas to fatty acids; and 4) select an adapted or mutant strain of *B. methylotrophicum* for high fatty acid tolerance. Experiments and fermentations to investigate all of these objectives were performed and completed. Objective 2 was achieved first by using batch CO fermentations. Objectives 1 and 3 were then achieved applying the knowledge gained from the results from objective 1. Objective 4 was an ongoing effort achieved primarily through fermentor operation conducted throughout the period of this contract.

The major objectives in solventogenic phase were to isolate a high butanol producing mutant and to evaluate the efficiency of the new mutant strain of *Clostridium acetobutylicum* for solventogenic fermentation. In the initial phase the primary goal was to compare the performance for solvent yields and productivity of several mutants with wild strain (ATCC 4259) and select a mutant producing more solvent compared to wild strain in batch fermentation. In the later phase the major objectives were to develop a multistage continuous fermentation system and establish the conditions for operation of this system. The major goal was to evaluate the efficiency of the mutant strain of *Clostridium acetobutylicum* for organic acids uptake and solventogenic fermentation. The primary objectives in the last phase of work were to design, construct and test a prototype for a laboratory scale cell recycle system using carbon composite membranes and to complete the evaluation of efficiency of the new mutant strain of *Clostridium acetobutylicum* for organic acids uptake, high solvent production, yield and solvent productivity.

Technical Approach

The experimental approach used to achieve the research objectives for the acidogenic stage of this process were based primarily on operation of extended CO fermentations. Due to the toxicity and explosion potential of CO, these fermentations were all performed in an explosion proof, well-vented laboratory with fermentors located in chemical safety hoods. Extended batch fermentations of CO were conducted in 0.5 L or 1.0 L Multigen fermentors (New Brunswick Scientific Co., Edison, NJ) with continuous gas sparging of CO into a phosphate buffered basal media. Agitation rates were set just high enough for complete mixing (approximately 50 rpm). Conditions were calculated to be severely mass-transfer limited in these systems. The effect of fermentation pH was investigated during this mode of operation. The effect of fermentation pH during methanol/CO/CO₂ metabolism was also investigated during extended batch culture. Extended batch fermentations of CO were also conducted in 12 L microform fermentors (New Brunswick Scientific Co., Edison, NJ) to grow cells for biochemical analysis.

Continuous CO fermentations were then designed and conducted at steady-state using 1.5 L Bioflo fermentors (New Brunswick Scientific Co., Edison, NJ). The effect of fermentation pH during continuous culture was investigated. Conditions during these fermentations were also severely mass-transfer limited. Continuous CO fermentations with a cell recycle membrane were then designed. A new, enriched media was formulated, tested and subsequently applied during these fermentations, in order to support the high cell densities obtainable with such systems. Steady-state operation was achieved and the effect of fermentation pH investigated. These systems also incorporated gas recycle equipment to maintain high gas/liquid mass transfer rates without excessive loss of feed gas. High

agitation rates, as high as 450 rpm, were also employed to increase rates of CO transfer.

Steady-state results were achieved during long term operation of these systems.

The CO strain of *B. methylotrophicum* was continuously transferred during the course of these investigations such that the organism at the end of one fermentation was used to inoculate the next. In this way, any gains or increases in product tolerance, growth rates, and general metabolic efficiency were conserved from generation to generation. As a result of this approach, the final form of the CO strain obtained during the investigations outlined in this contract was in several ways quite different from the initial CO strain.

Mutagenesis of *Clostridium acetobutylicum* with chemical mutagens, nitrosoguanidine (NTG) and ethyl methane sulfonate (EMS) was initiated and several possible mutants were picked up from plates. These mutants were evaluated for substrate consumption, solvent concentration and yield. One of the mutants isolated, E-604 was much better in butanol concentration and butanol yield and was, therefore, further evaluated for stability, solvent tolerance and carbohydrate conversion rate in continuous multistage fermentation and compared with the wild type culture ATCC 4259 under identical process set-up. Comparative evaluation of fermentation parameters such as productivity, yield, organic acid uptake and solvent production were conducted for the two cultures. It was indicated that volumetric reactor productivities were limited by low cell concentration. Hence recycle of the cells to the fermentor was done using different membranes. Recently developed carbon-composite membranes were chosen for prototype design and construction of the cell recycle system. These membranes were steam sterilizable and had low fouling problems. Continuous multistage cell recycle was conducted over week-long periods and the uptake of added butyrate in these fermentations was studied under different process conditions to maximize the uptake rates. Finally, the performance of purged stream cell recycle system was compared to

cell recycle without any purge stream, for rates of solvent production, carbohydrate consumption and organic acid uptake.

Significant Accomplishments

There have been several new discoveries and significant accomplishments for the acidogenic as well as solventogenic stage of the indirect liquefaction process since its inception. These include:

Acidogenic stage:

1. Production of butyrate (C₄ acid) directly from CO by shifting fermentation pH and changing metabolic regulation.
2. Novel discovery of production of butanol (C₄ alcohol) directly from CO as the sole carbon and energy source.
3. Proposition of a novel metabolic pathway for production of butanol directly from CO fermentation.
4. Demonstration of significant levels of butanol (1 g/l) from direct fermentation of CO in the first stage alone.
5. Continuous, steady-state fermentation of CO under various controlled conditions.
6. Demonstration of butanol production from CO in continuous, steady-state fermentation systems.
7. Achievement of 5-10 fold increases in cell and product concentrations by use of cell-recycle in continuous, steady-state CO fermentations.
8. Demonstration of more than 6 weeks of operation of continuous cell recycle CO fermentation without significant membrane fouling.

9. Production of organic acids from CO in concentrations (5-10 g/l) appropriate to sustain the second stage solventogenic fermentation.

Solventogenic Stage:

1. Development of an improved asporogenic mutant strain of *C. acetobutylicum* that exhibited higher productivity, increased solvent tolerance and higher butanol yield compared to the parent strain in batch fermentation of carbohydrates
2. Demonstration of improved performance of mutant strain in a continuous, multistage fermentation
3. Demonstration of high level of carbohydrate tolerance and exceptionally high concentration of butanol (>20 g/l) and total solvent production (30-31 g/l) by mutant strain
4. Demonstration of very high levels of butyrate uptake (8-10 g/l) by the mutant strain (E-604) of *C. acetobutylicum* under controlled conditions
5. Demonstration of long-term (1-2 weeks) operation of cell-recycle solventogenic fermentation without significant membrane fouling
6. Demonstration of significant levels of butyrate uptake and conversion to solvents in the continuous cell recycle, solventogenic fermentation.

Results

Acidogenic Phase

Acidogenic conversion of CO by *B. methylotrophicum* was investigated first in batch and then in continuous culture fermentations, with emphasis on manipulation of carbon flow to maximize butyric acid production. Previous studies without pH control had shown low levels of butyric acid production and culture pH drop to be linked during stationary phase

growth. Thus, our primary approach was to analyze the effect of lower broth pH on the carbon monoxide fermentation.

1. Batch Culture Studies.

An extended batch fermentation with continuous CO sparging was first conducted at a pH of 6.8. The results are shown in Figure 1. Trends in the growth and product formation curves are consistent with those observed previously in both batch and in fed-batch culture with intermittent CO addition. CO assimilation led to cell growth, and acetate was the primary reduced end product. Only small amount of butyrate was detected in this study. The initial specific growth rate was 0.05 hr^{-1} .

Carbon and electron balances were used to calculate the amount of CO consumed from the product formation data. These balances were found by Lynd, et al. (6) to be accurate to within 3-5% for batch CO fermentations using *B. methylotrophicum*. The overall carbon balance determined for the data in Figure 1 is

where the cell mass term represents the number of carbon-moles of cells (for *B. methylotrophicum*, 1 carbon-mole of cells equals 26 g dry weight). Acetate production occurs during both the growth and the stationary phase. Butyrate, on the other hand, appears to be a secondary metabolite. Its production begins as the growth rate declines, and is most rapid during the stationary phase.

Figure 2 shows the results of a second extended-batch fermentation designed to investigate the effect of pH on stationary phase butyrate production. *B. methylotrophicum* cells were grown as in the first experiment until the cell concentration reached a value of 0.31 g/l, i.e., towards the end of the growth phase. At this time the setpoint of the pH controller was changed from 6.8 to 6.0. The resulting pH shift led to a dramatic increase in butyrate

Figure 1. Constant pH Batch Fermentation with Continuous CO Gas Feed

Figure 2. pH-Shift Batch Fermentation with Continuous CO Gas Feed

production relative to the constant-pH experiment. A final butyrate concentration of 6 g/l was obtained. The overall carbon balance for the pH-shift fermentation represented in Figure 2 is:

The effect of the pH shift on product formation is even more pronounced when the growth and stationary phases are analyzed separately. The growth phase was taken to be the time between the onset of growth and up until a major decrease in the growth rate, approximately 72 hr. The carbon balance during the growth phase is

and the carbon balance for the stationary phase is

For comparison, the constant-pH experiment fermentation can also be divided into growth and stationary phases. The carbon balances are

for the growth phase and

for the stationary phase.

Thus, by decreasing the pH from 6.8 to 6.0 at the onset of the stationary phase, the metabolism of *B. methylotrophicum* can be shifted from acetate to butyrate production. The flow of available electrons is shown in Table 1. Since heats of combustion are proportional to the available electron content, Table 1 can also be interpreted as the relative chemical energy content of the products.

Table 1. Percent of Available Electrons Contained in Products

Fermentation Conditions	Acetate	Butyrate	Cell Mass
Constant pH, Growth Phase	80	0	20
Constant pH, Stationary Phase	88	8	4
Constant pH, Overall	86	6	8
pH Shift, Growth Phase	71	5	24
pH Shift, Stationary Phase	21	78	1
Ph Shift, Overall	27	70	3

These batch fermentation results are very important and unique because they show that the metabolic regulation of the organism can be altered dramatically by manipulation of the fermentation pH, with lower pH environments inducing the production of a 4-carbon organic acid (butyrate) directly from gaseous CO.

Batch fermentations of this organism using methanol, CO₂, and CO were also conducted at both pH values of 6.8 and 6.0. These fermentation results indicate that acetate is a major product at both pHs when methanol is used as a co-substrate with CO in the presence of CO₂. Figure 3 shows the fermentation profile at a pH of 6.8 and Figure 4 shows the profile at pH 6.0. The carbon and electron balances are

at a pH of 6.8 and

Figure 3. Batch Fermentation of MeOH/CO/CO₂ at a pH of 6.8

Figure 4. Batch Fermentation of MeOH/CO/CO₂ at a pH of 6.0

at a pH of 6.0. Earlier results have shown that simultaneous methanol/CO₂ fermentation leads to primarily butyrate production. It is apparent from these data that the introduction of CO in a methanol/CO/CO₂ fermentation yields acetate as the primary product, regardless of fermentation pH. However, the pH effect was present during this study, since the relative proportion of butyrate was increased at a pH of 6.0.

2. Continuous Culture Studies

With the important and unique results obtained from the batch culture studies indicating fermentation pH as a direct metabolic regulator of the C₁ to C₄ metabolic pathway, the next task of the project was to determine the extent of this regulation under similar conditions in continuous culture. This involved first establishing conditions for steady-state operation of a chemostat and then conducting steady-state operation over a range of broth pH values. Steady-state operation was defined as deviations of the cell density of not more than 10% of the mean cell density value over a period of three residence times, or approximately 9 days. Although rigorous, this stricture provided increased confidence in the accuracy of data obtained. All data presented in this section are steady-state values defined by this criteria.

All the continuous culture studies were performed strictly under the same conditions with fermentation pH as the variable parameter. Thus direct correlations can be drawn between all experiments relating pH to product mix and concentrations.

An initial continuous fermentation of CO using *B. methylotrophicum* was conducted for three weeks with approximately 10 days of steady-state operation at a pH of 6.8. Similar conditions in batch culture described previously favor acetate production with a corresponding acetate/butyrate ratio (molar) of 30:1. In continuous culture, these conditions resulted in production of acetate and butyrate at 0.88 and 0.11 g/l, respectively, yielding a molar product

ratio of approximately 8.3:1. Ethanol production was also observed in quantities less than 0.05 g/l. Carbon and electron balance calculations give an overall stoichiometry of

These values allow calculation of some key fermentation parameters--mainly electron and carbon partitioning and molar yield coefficients. Molar yield coefficients, defined as moles product produced divided by the moles of substrate consumed, are helpful in analyzing the overall conversion of substrate to multiple products. For the above products from CO, the molar yield coefficient values are

$$Y_{\text{CO}_2/\text{CO}} = .522 \quad Y_{\text{Ac}/\text{CO}} = .158 \quad Y_{\text{Bu}/\text{CO}} = .011$$

$$Y_{\text{EtOH}/\text{CO}} = .007 \quad Y_{\text{Cells}/\text{CO}} = .108$$

which shows acetate as the primary reduced product. Electron partitioning, which corresponds to the distribution of the total chemical energy content of the substrate CO, is

Carbon partitioning, or the total carbon distribution from CO to products, can be calculated

When analyzed together, these values present some interesting and valuable information for subsequent comparison at lower fermentation pH:

1. As determined previously in batch culture, CO_2 generation results in a loss of approximately half of the consumed carbon in CO.
2. Acetate is the major reduced product at a pH of 6.8 as observed before, accounting for 67% of the reduced product carbon.

3. Compared to batch fermentation results at the same pH, the continuous culture data indicates a metabolic shift towards more reduced product formation, based solely on the continuous nature of the system.

Therefore, as the fermentation pH of this system was lowered, the induced metabolic shift was expected to become more pronounced, until cell washout began to influence the detectable product mix.

Once the conditions for continuous culture of CO were established, experiments based on fermentation pH were conducted and compared to the above fermentation at pH 6.8. Steady-state data was collected at fermentation pH values of 6.5, 6.0, and 5.5. Operation was then attempted at pH 5.0 but was discontinued due to cell washout. The results for these fermentations have been combined with the pH 6.8 results and are presented as overall stoichiometries, electron partitioning, carbon partitioning, and molar yield coefficients in Tables 2, 3, 4, and 5, respectively. Table 6 provides molar (weight) product ratios while specific product weight ratios based on grams product per gram cell are given in Table 7. The product concentrations (g/l) observed in fermentation broth are presented in Table 8.

Once again, as was observed in batch culture, there was a significant relationship between the fermentation pH and the product selectivity during continuous culture of CO. Several important conclusions can be drawn from the data presented in Tables 2-8. First, and of prime importance, is the trend towards more reduced product formation, mainly butyrate and alcohols, as the pH of the fermentation is reduced. This trend parallels what has been observed during batch fermentation, and is clearly shown in all the tables. The data at a pH of 5.5 is not consistent with this trend, and could indicate that there is a different metabolism below pHs of 6.0. Another highly significant discovery shown by these data is the production of alcohols, specifically the 4-carbon butanol, solely from the 1-carbon substrate CO. Data

Table 2. Fermentation Stoichiometry of CO in *Butyribacterium methylotrophicum* in relation to pH

pH	Fermentation Stoichiometry
6.8	$4\text{CO} \rightarrow 2.09\text{CO}_2 + .63\text{Ac} + .043\text{Bu} + .027\text{EtOH} + .43\text{Cells}$
6.5	$4\text{CO} \rightarrow 2.13\text{CO}_2 + .56\text{Ac} + .082\text{Bu} + .026\text{EtOH} + .37\text{Cells}$
6.0	$4\text{CO} \rightarrow 2.27\text{CO}_2 + .303\text{Ac} + .161\text{Bu} + .032\text{EtOH} + .029\text{BuOH} + .31\text{Cell}$
5.5	$4\text{CO} \rightarrow 2.18\text{CO}_2 + .402\text{Ac} + .154\text{Bu} + .40\text{Cells}$

Table 3. Electron Partitioning During pH-Dependent CO Fermentation by *Butyribacterium methylotrophicum*

<u>pH</u>	<u>% Electrons</u>				
	<u>Acetate</u>	<u>Butyrate</u>	<u>EtOH</u>	<u>BuOH</u>	<u>Cells</u>
6.8	63.0	11.0	4.0	--	22.0
6.5	56.0	20.5	4.0	Trace	19.5
6.0	30.3	40.2	4.8	8.7	16.0
5.5	40.2	38.5	Trace	Trace	21.3

Table 4. Carbon Partitioning During pH-Dependent CO Fermentation by *Butyribacterium methylotrophicum*

<u>pH</u>	% Carbon					
	<u>CO₂</u>	<u>Acetate</u>	<u>Butyrate</u>	<u>EtOH</u>	<u>BuOH</u>	<u>Cells</u>
6.8	52.0	32.0	4.0	1.5	--	10.5
6.5	53.0	28.0	8.2	1.3	Trace	9.5
6.0	56.8	15.2	16.1	1.6	2.9	7.4
5.5	54.5	20.1	15.4	Trace	Trace	10.0

Table 5. Molar Yield Coefficients During pH-Dependent CO Fermentation by *Butyribacterium methylotrophicum*

<u>pH</u>	<u>CO₂</u>	<u>Acetate</u>	<u>Butyrate</u>	<u>EtOH</u>	<u>BuOH</u>	<u>Cells</u>
6.8	.522	.158	.011	.007	--	.108
6.5	.532	.140	.020	.007	Trace	.092
6.0	.568	.076	.040	.008	.007	.078
5.5	.545	.100	.038	Trace	Trace	.100

Table 6. Product Ratios During pH-Dependent CO Fermentation by *Butyribacterium methylotrophicum*

<u>pH</u>	<u>Ac/Bu</u>	<u>Ac/EtOH</u>	<u>Ac/BuOH</u>
6.8	14.7(10)*	23.4(30.7)	--
6.5	6.83(4.65)	22.0(28.5)	Trace
6.0	1.88(1.28)	9.5(12.3)	10.5(8.51)
5.5	2.61(1.79)	Trace	Trace

* Product ratios on molar (weight basis)

Table 7. Specific Product Weight Ratios During pH-Dependent CO Fermentation by *Butyribacterium methylotrophicum*

<u>pH</u>	<u>Acetate</u>	<u>Butyrate</u>	<u>EtoH</u>	<u>BuOH</u>
6.8	3.47	0.35	0.11	--
6.5	3.72	0.80	0.13	Trace
6.0	2.41	1.87	0.20	0.28
5.5	2.42	1.36	Trace	Trace

Table 8. Product Concentrations in Fermentation Broth During pH Dependent CO Fermentations by *Butyribacterium methylotrophicum* (g/L)

<u>pH</u>	<u>Acetate</u>	<u>Butyrate</u>	<u>EtOH</u>	<u>BuOH</u>	<u>Cells</u>
6.8	.860	.086	.028	--	.248
6.5	1.055	.227	.037	Trace	.284
6.0	.689	.536	.056	.081	.286
5.5	.475	.266	Trace	Trace	.196

presented in Table 7 indicate that butanol, when normalized to the cell density, is produced by weight in greater amounts than the 2-carbon ethanol. Butanol also contains a significant portion of the available energy content from CO (Table 3). This novel finding indicates a direct metabolic pathway in *B. methylotrophicum* for bioconversion of gaseous CO directly to butanol. As expected, cell production dropped as the pH decreased below 6.0 (Table 8). Cell washout was observed at a pH of 5.0. Fermentation pH did not significantly alter the carbon loss as CO₂ (Tables 2, 4 and 5).

3. Continuous Cell-Recycle Studies

Continuous fermentations using a cell-recycle membrane in order to retain biomass in the fermentor were conducted at low and high pH values. Results for steady-state fermentation stoichiometry and carbon and electron balances are shown in Tables 9 and 10 for fermentations operated at pH values of 6.8 and 6.0. Concentrations of butyrate and acetate indicated a 5-fold increase over conventional chemostat operation. Alcohol

Table 9. Continuous Cell Recycle Fermentations of Carbon Monoxide by *Butyribacterium methyilotrophicum* Steady State Operation

Stoichiometries

$$\text{pH} = 6.8$$

$$\text{pH} = 6.0$$

Carbon Partitioning (% Total Carbon):

$$\text{pH} = 6.8$$

$$\text{pH} = 6.0$$

Electron Partitioning (% Total Electrons):

$$\text{pH} = 6.8$$

$$\text{pH} = 6.0$$

Table 10. Continuous Cell Recycle Fermentation of Carbon Monoxide by *Butyribacterium methylotrophicum* Steady State Operation

Products	Product Concentrations (g/l)	
	pH 6.8	pH 6.0
Acetate	8.06	2.71
Butyrate	4.40	2.15
Ethanol	0.459	0.397
Butanol	1.20	0.698
Cell Mass	7.09	2.41

concentrations were approximately 10 times more than was observed in the normal chemostat fermentations. These results show that a significant fraction of the electrons (free energy) from CO are converted to butanol (16.5% at pH 6.0) and that the electron partitioning to butanol increases as the pH is lowered. The concentrations of butyrate and acetate produced (4.4 g/l and 8.0 g/l, respectively) are also well within the concentration range for uptake in the second solventogenic fermentation.

Solventogenic phase

The wild type strain ATCC 4259 of *Clostridium acetobutylicum* was mutagenized using NTG and EMS. Mutants obtained with either NTG (Table 11) or EMS (Table 12) varied greatly in terms of substrate consumption, solvent concentration and yield. They also

Table 11. Analysis of Mutants of *Clostridium acetobutylicum* Obtained After NTG Mutagenesis

Strain	Sporulation	Starch Utilization (g/l)	Acids (g/l)		Solvents (g/l)			Butanol Yield (%)
			Acetic	Butyric	Acetone	Ethanol	Butanol	
WT	S	33.0	1.7	0.0	2.4	t	7.3	22.1
N303	S	38.6	1.4	0.0	2.1	t	7.5	19.4
N306	WS	42.2	1.0	0.0	2.4	0.9	9.1	21.6
N308	WS	26.3	2.0	0.7	2.5	t	7.5	20.7
N310	S	32.9	2.1	0.8	2.3	t	6.9	21.0
N604	WS	40.5	1.1	0.0	2.6	0.8	8.8	21.7
N607	S	32.3	2.0	1.2	2.1	t	6.3	19.5

Table 12. Analysis of Mutants of *Clostridium acetobutylicum* Obtained After EMS Mutagenesis

Strain	Sporulation	Starch Utilization (g/l)	Acids (g/l)		Solvent (g/l)			Butanol Yield (5)
			Acetic	Butyric	Acetone	Ethanol	Butanol	
WT	S	33.0	1.7	0.0	2.4	t	7.3	22.1
E301	S	2.3	0.4	0.7	0.0	0.0	0.0	--
E303	S	3.9	0.4	0.8	0.0	0.0	0.0	--
E305	S		0.4	0.7	0.0	0.0	0.0	--
E306	S		0.4	0.7	0.0	0.0	0.0	--
E308	S	2.4	0.3	0.7	0.0	0.0	0.0	--
E309	S	39.9	1.4	0.0	2.1	0.7	7.0	17.5
E601	S	34.3	1.5	0.4	2.0	t	6.4	18.7
E602	WS	38.0	1.1	0.0	2.3	t	7.8	20.5
E604	WS	34.2	1.9	0.4	2.6	t	8.1	23.7
E606	S	43.3	0.8	0.0	2.4	1.0	7.9	18.2
E610	NS	46.2	1.2	0.0	2.6	0.8	9.2	19.9

varied in sporulation ability. Of the mutants isolated mutant N306, N604, E-604 and E-610 were much better either in butanol concentration, butanol yield or both (Tables 11 and 12). Interestingly, sporulation ability in these mutants was affected. While only <10% cells were observed sporulating (weak sporulation) in mutants N306, N604 and E-604 in comparison to wild type, no spores were detected in mutant E-610.

Since mutant E-604 had better yield of butanol concentration, it was further evaluated in 2-liter batch fermentation. The comparison data presented in Table 13 indicate that mutant E-604 had substrate consumption (1.45 vs. 0.79 g/l-hr) and productivity rates (0.33 vs. 0.17 g/l hr) much higher than the sporeforming wild type strain. Mutant strain also produced a higher butanol concentration (13.0 vs. 10.6 g/l) in fermentation broth and resulted in higher butanol yield (22.7 vs. 21.3 wt %) when compared with the wild type. The mutant strain was, therefore, further evaluated in multistage chemostat system.

Table 13. Comparison of Wild Type and Mutant Strain of *Clostridium acetobutylicum* (Batch Fermentation)

Strain	Substrate Consumption Rate (g/l hr)	Actual Final Butanol g/l	Butanol Productivity (g/l-hr)	Butanol Yield (wt %)
Wildtype	0.75	10.6	0.17	21.30
E604	1.45	13.0	0.33	22.70

The respective dilution rates of stage 1, 2 and 3 were 0.25, 0.135 and 0.135 h⁻¹ respectively. All the three stages were operated at 36°C. The pH in stage 1 was regulated at

5.1. The results presented in Table 14 indicate that about 18.6 g/l of total solvent could be produced in stage 3 of chemostat culture system. Lowering the temperature of stage 3 to 30°C did not alter the solvent production significantly when the

Table 14. Continuous Multistage Fermentation of *Clostridium acetobutylicum* Mutant E-604

Fermentation Stage	Solvents (g/l)		Solvent Production Rate (g/l/h)	% Carbohydrate Consumed
	Butanol	Total		
Stage 1	---	---	---	19.3
Stage 2	7.1	11.1	0.97	56.4
Stage 3	11.8	18.6	0.99	66.2

CONDITIONS:	Stage	Dilution Rates,	H ⁺ Temperature	pH
	1	0.25	36°C	5.1
	2	0.135	36°C	uncontrolled
	3	0.135	36°C	uncontrolled

effluents from both the system were batch incubated, fermentation was over within 48h. Total solvent and butanol concentrations of 27 g/l and 18.5 g/l were obtained under these conditions.

Multistage chemostat culture studies were continued for butyrate uptake by both mutant and wild type (ATCC 4259) strain. The effluent of stage 2 was incubated with added Butyrate (4.7 ± 0.6 g/l) at different temperatures. The results presented in Table 15 indicate

Table 15. Comparison of E-604 and Wild Type for Butyrate Uptake of Stage 2 Effluent for 24 Hours

Parameter	INCUBATION TEMPERATURE			
	36° C		30° C	
	Wild Type ATCC 4259	Mutant E-604	Wild Type ATCC 4259	Mutant E-604
Butanol (G/L)	8.3	10.3	13.9	17.6
Toal Solvents (G/L)	12.3	16.2	18.8	25.3
Solvent Production Rate (G/L/H)	0.35	0.45	0.53	0.71
Butyrate Uptake Rate (G/L/H)	0.02	0.05	0.26	0.33
Butyrate Conversion Efficiency (%)	8.2	13.0	86.6	97.5

Butyrate was added at the concentration of 4.7 ± 0.6 G/L

that the mutant E-604 has higher butyrate uptake rate and butyrate conversion efficiency than the wild type. The rates of butyrate uptake were higher at low temperature (30°C) in wild as well as mutant strain indicating a novel discovery that butyrate uptake can be significantly improved under the appropriate temperature modulated conditions. A detailed investigation was, therefore, undertaken for different levels of butyrate supplementations at this temperature (30°C). The results summarized (Table 16) indicate that butyrate up to 14 g/l did not inhibit the butyrate uptake rate. Butyrate and solvent production was affected only minimally. However, butyrate concentration higher than 16 g/l totally inhibited the solvent production.

Table 16. Influence of Different Levels of Butyrate Supplementation on Global Performance of Stage 2 Effluents Incubated at 30°C (E-604 Mutant)

Parameter	Control Time (Hrs)			Control + Butyrate 1 Time (Hrs)			Control = Butyrate 2 Time (Hrs)			Control + Butyrate 3 Time (Hrs)			Control + Butyrate 4 Time (Hrs)		
	0	18	48	0	18	48	0	18	48	0	18	48	0	18	48
Butyrate (G/L)	2.8	0.2	0.2	2.8 + 4.0*	1.4	0.2	2.8 + 6.5*	3.1	1.1	2.8 + 9.2*	6.7	4.5	2.8 + 11.4*	9.0	6.5
Butanol (G/L)	6.3	13.9	18.7	6.3	15.9	19.7	6.3	16.3	19.5	6.3	15.3	19.0	6.3	14.6	18.2
Total Solvent (G/L)	9.1	20.4	26.6	9.1	21.9	26.4	9.1	22.2	26.0	9.1	20.8	25.3	9.1	19.8	24.0
Butyrate Uptake Rate (G/L/H)	--	0.14	--	--	0.30	--	--	0.34	--	--	0.29	--	--	0.29	--
Butyrate Conversion Efficiency (%)	--	100	--	--	79.4	97.0	--	66.7	88.2	--	44.2	62.5	--	37.1	54.2
Carbohydrate Consumed (%)	50.0	79.0	98.6	50.0	78.7	90.4	50.0	76.7	84.0	50.0	72.8	80.6	50.0	69.7	77.9

* Externally added butyrate

The results indicate 6-12 g/l butyrate as an optimum for uptake of butyrate and production of butanol which is nearly the concentration of acids produced in acidogenic stage.

Multistage, continuous culture studies were completed for evaluating the fermentation of high carbohydrate substrate concentrations (approx. 100 g/l). The mutant strain initiated growth and fermentation at 97 g/l carbohydrates, and produced over 21 g/l butanol and 31 g/l total solvents (Table 17). This proves the robustness of the mutant strain (E-604) for fermentability of high concentration of carbohydrate substrates and tolerance of exceptionally high concentration of end product solvents.

Since chemostat cultures were limited by biomass, a cell recycle system was developed by using carbon composite membrane under appropriate operating conditions. Initial work at the increased transmembrane pressure (5-10 psi) showed a decrease in the permeate flux after operation of the system for some time. Therefore, the transmembrane pressure was reduced to about 1.5 - 2.0 psi and backflushing was done at interval of 10 min. for 4 sec. The results (Figure 5) indicate that at the reduced transmembrane pressure there was no reduction in permeate flux even after continuous operation of cell recycling for nearly 150 hrs. The solvent and butanol concentrations reached to the maximum of 24.5 g/l and 16.5 g/l, respectively after about 30 hrs. of cell recycling. However, oscillation in solvent and acid concentration was observed during the entire period of cell recycling. The solvent concentration achieved under these conditions is higher than any reported literature value.

Butyrate uptake studies were started by feeding butyrate at an initial lower concentration of 1-5. Since all the fed butyrate was consumed, the butyrate feed concentration was increased to 10 g/l. The results (Figure 6) demonstrated that maximum butanol concentration of 16.2 g/l could be achieved in less than 30 hrs. of cell recycling. The global carbohydrate consumption for butanol production was significantly reduced. The

Table 17. Batch Completion of Stage 3 Effluent at High Concentration of Carbohydrate at Different Temperatures (E-604 Mutant)

	Incubation Temperature									
	30° C					27° C				
	Batch Fermentation Time (Hrs)					Batch Fermentation Time (Hrs)				
	0	24	48	72		0	24	48	72	
Butanol (G/L)	10.8	18.4	20.2	20.6		10.8	18.2	20.6	21.2	
Total Solvents (G/L)	16.2	27.6	30.1	30.7		16.2	26.7	29.9	31.0	
Solvent Production (G/L/H)	0.86	0.64	0.45	0.34		0.86	0.62	0.45	0.34	
% Carbohydrate Consumed	59.8	81.4	89.7	91.2		59.8	80.9	90.6	92.7	

Stage Dilution (H⁻¹)

1 0.25
2 0.135
3 0.135

Initial Carbohydrate Concentration 97.0 G/L

FIGURE 5

Product formation and substrate utilization pattern in two-stage cell recycle system. Feed carbohydrate conc. was 87.0 g/l.

Fig.6. product utilization and substrate utilization pattern in two-stage cell recycle system. Feed carbohydrate conc. was 95.6 g/l

Substrate consumed	butyric acid	butanol	solvent
—○—	—□—	—△—	—×—
Stage	dilution rate (h^{-1})	temperature	
1	0.25	36 C	
2	0.132	30 C	

residual butyrate was increased slightly (4.6 vs. 2.4 g/l) compared to controlled experiments. The fermentation was never limited due to butyrate inhibition, but due to accumulation of solvents. In the last phase of work on solventogenic fermentation, the cell recycle experiments were modulated for purge stream after about 42 hrs of continuous operation. The results indicate (Figure 7) that global solvent production pattern did not alter, as a butanol concentration of 17.0 g/l was achieved at 83 hrs. The residual butyrate concentration was low at the maximal condition of solvent production. The solvent production rate of 1.85 g/l/h was achieved under these conditions.

Fig.7.product formation and substrate utilization pattern in two-stage cell recycle system. Feed carbohydrate conc. was 87.0 g/l

Substrate consumed	butyric acid	butanol	solvent
—○—	—□—	—△—	—*—
Stage	dilution rate (h^{-1})	temperature	
1	0.25	36 C	
2	0.108	30 C	

Conclusions and Recommendations

Some significant accomplishments achieved in both acidogenic and solventogenic fermentation are:

- Production of butyrate (C₄ acid) directly from CO by shifting fermentation pH and changing metabolic regulation.
- Novel discovery of butanol production (C₄ alcohol) from direct fermentation of CO by *B. methylotrophicum* as the sole carbon and energy source.
- Demonstration of significant level of butanol (1 g/l) from direct fermentation of CO in continuous, steady state fermentation by *B. methylotrophicum*.
- Demonstration of more than 5 weeks of operation of cell-recycle without membrane fouling.
- Production of an improved asporogenic mutant strain of *Clostridium acetobutylicum* with increased stability, productivity, and product tolerance.
- Demonstration of high levels of butyrate (10 g/l) uptake by the mutant strain of *C. acetobutylicum*.
- Demonstration of high levels of carbohydrate tolerance, and exceptionally high concentration of butanol (>20 g/l) and solvent (<30 g/l) production by the mutant strain of solventogenic bacteria.
- Achievement of 3-fold increase in the rate of solvent production by the mutant strain of *C. acetobutylicum* using cell recycle.
- Demonstration of continuous, multistage fermentation for solvent production by the stable asporogenic mutant strain of *C. acetobutylicum*.

The results obtained for the acidogenic stage of the CO-fermentation point to several key areas requiring further investigation. The enzymatic mechanism for production of butanol and ethanol must be further studied in order to more accurately and efficiently manipulate the expression of those products. The finding of direct biological routes for production of butyrate and butanol from CO has strengthened the biological synthesis gas conversion concept. These findings have also indicated a strong potential for further improvements of the butyrate and butanol yield. With enough biochemical information concerning the major factors influencing the production of butyrate and butanol from CO, there is the possibility of further reducing the acetate production. The ultimate goal is to regulate the carbon and electron flow in *B. methylotrophicum* to achieve a strictly 4-carbon product from CO fermentation. The butyrate uptake (8-10 g/l) by this mutant of *C. acetobutylicum* is higher than the expected levels of butyrate production by *B. methylotrophicum* from CO conversion. Thus, this mutant can be efficiently utilized in the second stage of syngas bioconversion process to liquid fuels. Low levels of carbohydrate substrate would be required for cofermentation of butyrate to butanol. Future studies may include batch fermentation after continuous fermentation or cell recycle system for completion of fermentation. Oscillation of solvent production needs to be minimized by development of suitable solvent separation processes. Different membranes may be examined to minimize the membrane fouling. In general, the following recommendations are made for future research and development work.

1. The unique discovery of direct conversion of CO to butanol should be further investigated by physiological studies.
2. The fermentation process for this unique bioconversion should be further developed and process parameters such as productivity, concentration and mass transfer needs should be determined.

3. Strain improvement of *B. methylotrophicum* and isolation of new strains with high product tolerance and conversion of CO to butanol should be conducted.
4. Process scale-up parameters and preliminary design and economics should be determined for both the acidogenic and solventogenic processes.

Presentations, Publications, and Patents

Presentations

1. Datta, R. 1988. Biotechnology of indirect liquefaction. DOE Indirect Liquefaction Contractors' Review Meeting, Nov. 15-17, 1988, Washington, D.C.
2. Worden, R. M., A. J. Grethlein, J. G. Zeikus and R. Datta. 1988. Butyrate production from carbon monoxide by *Butyribacterium methylotrophicum*. Tenth Symposium on Biotechnology for Fuels and Chemicals, Gatlinburg, Tennessee.
3. Grethlein, A. J., R. M. Worden, M. K. Jain and R. Datta. 1989. Continuous production of mixed alcohols and acids from carbon monoxide. Eleventh symposium on biotechnology for Fuels and Chemicals, May 8-12, 1989, Colorado Springs, Colorado.
4. Grethlein, A. J., R. M. Worden, M. K. Jain, B. K. Soni and R. Datta. 1989. Two stage production of mixed solvents and organic acids by fermentation. Eleventh symposium on biotechnology for fuels and chemicals, May 8-12, 1989, Colorado Springs, Colorado.
5. Grethlein, A. J., R. M. Worden, M. K. Jain and R. Datta. 1990. Butanol production from carbon monoxide by *Butyribacterium methylotrophicum*. MBI Symposium on "Bridging the Gap: Case Studies of University Technology Transfer to Industry", April 30 - May 1, 1990, East Lansing, MI.
6. Grethlein, A. J., R. M. Worden, M. K. Jain and R. Datta. 1990. Butanol production from carbon monoxide by *Butyribacterium methylotrophicum*. Twelfth Symposium on Biotechnology for Fuels and Chemicals, May 7-11, 1990, Gatlinburg, Tennessee.
7. Worden, R. M., A. J. Grethlein, M. K. Jain and R. Datta. 1990. Production of butanol and ethanol from synthesis gas via fermentation. Symposium on "Biotechnology for the Production of Clean Fuels", Fuel Chemistry Division, American Chemical Society Meeting, August 26-31, 1990, Washington, D.C.

Publications

1. Worden, R. M., A. J. Grethlein, J. G. Zeikus, R. Datta. 1989. Butyrate production from carbon monoxide by *Butyribacterium methylotrophicum*. Appl. Biochem. Biotechnol. 20/21:687-698.
2. Grethlein, A. J., R. M. Worden, M. K. Jain and R. Datta. 1990. Continuous production of mixed alcohols and acids from carbon monoxide. Appl. Biochem. Biotechnol. (in press).

3. Worden, R. M., A. J. Grethlein, M. K. Jain and R. Datta. 1990. Production of butanol and ethanol from synthesis gas via fermentation. Preprints, Fuel Chemistry Division, ACS (in press).

Patent

1. Jain, M. K., D. Beacom and R. Datta. An improved mutant strain of *Clostridium acetobutylicum* for production of high levels of butanol and solvents (submitted).

References

1. Wilson, J. S., J. Halow and M. R. Ghate. *Chemtech.*, February, 123-128 (1988).
2. Martin, J. R., H. Petidemange, J. Ballongue and R. Gray. *Biotechnol. Lett.* 5:89 (1983).
3. Soni, B. K., K. Day and T. K. Ghose. *Biotechnol. Lett.* 4:19 (1982).
4. Linden, J. C., A. R. Moreira and T. G. Lenz. In C. L. Cooney and a. E. Humphrey (ed.), *Compressive Biotechnology*. Pergamon Press, Oxford, pp. 915 91986).
5. Andersch, W., H. Bahl and G. Gottschalk. *Biotechnol. Lett.* 4:29 (1982).
6. Lynd, L. H., R. Kerby and J. G. Zeikus. *J. Bacteriol.* 149:255 (1982).

**DATE
FILMED**

7/30/93

END