ANL-HEP-TR--92-24

DE92 014624

Argonne National Laboratory
9700 South Cass Avenue
Argonne, IL 60439

***HIGH ENERGY PHYSICS DIVISION
SEMIANNUAL REPORT OF RESEARCH ACTIVITIES***

July 1, 1991 - December 31, 1991

Prepared from information gathered and edited by
the Committee for Publications and Information:

Members: P. Schoessow
P. Moonier
R. Talaga
R. Wagner

April 1992

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Table of Contents

	Page
Abstract	1
I. Experimental Program	2
A. Physics Results	2
B. Experiments Taking Data	14
C. Experiments in Preparation Phase	17
II. Theoretical Program	30
III. Experimental Facilities Research	41
A. Mechanical Support	41
B. Electronic Support	42
IV. Accelerator Research and Development	46
A. Advanced Accelerator Test Facility (AATF) Program	46
B. Progress on the Argonne Wakefield Accelerator (AWA)	48
C. Accelerator Physics	49
V. SSC Detector Research and Development	50
A. Overview of ANL SSC Related R&D Programs	50
B. Compensating Scintillator Plate Calorimeter R&D	51
C. SDC Data Systems R&D	79
VI. Publications	80
VII. Colloquia and Conference Talks	90
VIII. High Energy Physics Community Activities	93
IX. High Energy Physics Research Personnel	95

Abstract

This report describes the research conducted in the High Energy Physics Division of Argonne National Laboratory during the period of July 1, 1991 - December 31, 1991. Topics covered here include experimental and theoretical particle physics, advanced accelerator physics, detector development, and experimental facilities research. Lists of division publications and colloquia are included.

I. EXPERIMENTAL PROGRAM

A. Physics Results

1. Collider Detector at Fermilab

Data analysis has continued on CDF direct photon studies and b quark cross section measurements using the 1988-1989 data. Papers on both topics are under review by the collaboration.

CDF direct photon studies have expanded beyond the basic inclusive photon cross section to include the single photon angular distribution and diphoton production. The inclusive cross section is shown in Fig. 1. Also shown is the data from the CERN Collider UA2 experiment. Both data sets give a qualitative agreement with NLO QCD predictions, but both sets show a slightly steeper slope at low p_T . A good test of QCD is the photon angular distribution in the c.m. frame, shown in Fig. 2. This differs significantly from the dijet angular distribution, due to the spin 1/2 nature of the propagator in the photon case (and spin 1 for the dijets). The measured dijet angular distribution is also shown, along with the QCD predictions. Good agreement is found between theory and data. Figure 3 shows the diphoton production cross section from CDF, compared to QCD predictions. It is displayed in two ways, with and without the effects of k_T smearing removed from the data, and with the appropriate change in QCD prediction. With limited statistics, it also shows agreement with the QCD prediction.

CDF has measured the b quark production cross section, using the central detector electron sample. This is shown in Fig. 4, along with the data from the CERN Collider UA1 experiment and the NLO QCD predictions of Berger and Weng. The UA1 data agrees well with QCD, while the CDF measurement is systematically somewhat higher.

(S. Kuhlmann)

2. Soudan Data Analysis

An important milestone was passed in October with the publication of the first physics result from Soudan 2 in Physics Letters B. The paper describes the observation of an excess flux of underground muons from the direction of the X-ray binary Cygnus X-3 during its January 1991 radio flare. These results were described in the previous HEP Division semiannual report. The observations were also presented at the International Cosmic Ray Conference in Dublin in August, where three other experiments, one underground detector and two cosmic-ray air shower arrays, reported somewhat weaker evidence for excess flux from the direction of Cygnus X-3 during the radio flare. Two

Fig. 2. CDF center-of-mass scattering angle distributions for direct photons and jets, compared to QCD predictions.

Fig. 1. Inclusive direct photon cross section from CDF and UA2, compared to NLO QCD calculations.

Fig. 4. Inclusive b quark cross section from CDF and UA1. The QCD calculations are from Berger and Weng.

Fig. 3. CDF diphoton production compared to a QCD prediction.

other large underground experiments and several large air shower arrays reported no excess flux during the radio flare period, so the question of whether particles from Cygnus X-3 are responsible for anomalous fluxes of underground muons remains unresolved. Since the Soudan 2 detector is in nearly continuous operation (75% duty cycle), signals from Cygnus X-3 radio bursts will continue to be observed (if the effect is real), with eventual confirmation by other experiments.

Initial results from the search for magnetic monopole tracks in Soudan 2 were prepared for publication during the Fall of 1991. Super heavy GUT monopoles with velocities greater than $10^{-3} c$ would leave heavily ionized tracks in Soudan 2. The detector's dE/dx resolution allows it to distinguish easily between ordinary cosmic-ray muon tracks and the continuous heavy ionization of a monopole track. A software filter identified several thousand tracks with high ionization in the data recorded during 1989, 1990, and 1991. Examination of computer reconstructions of these tracks showed that none had the continuous heavy ionization expected of magnetic monopole tracks. The excellent spatial resolution of Soudan 2 showed that nearly all candidate tracks had associated electromagnetic showers, inelastic interactions, or delta rays, which could not have been produced by magnetic monopoles. Figure 5 shows a typical showering track, and Fig. 6 is an example of a muon track which would have been rejected due to the presence of a low energy delta ray. The remaining candidates were found to have passed through regions of the detector which were known to produce larger than average pulses.

Monte Carlo simulations of magnetic monopole tracks were passed through the entire analysis chain to obtain the efficiency and acceptance. With no monopole tracks identified in the three-year exposure, the 90% confidence level upper limit on the flux of monopoles with velocities greater than $10^{-3} c$ was calculated to be $8.7 \times 10^{-15} \text{ cm}^{-2} \text{ s}^{-1} \text{ sr}^{-1}$. Figure 7 compares this result with other published monopole flux limits obtained by various techniques. Also shown in the figure is the Parker Bound, which is the upper limit on the average magnetic monopole flux imposed by the value and rate of regeneration of the galactic magnetic field, and the rate at which monopoles would remove energy from this field. The Soudan 2 limit is more restrictive than any result published to date using the gas ionization technique.

A major accomplishment during this period was the completion of the reprocessing of all Soudan 2 data taken over the past two years with the current offline software. The main goal of this work was to improve the selection efficiencies for nucleon decay and neutrino interaction events. In addition to assembling files of these fully contained event candidates, files of partially contained events (including stopping muons, up going muons, and high energy neutrino interactions), multiple muon events, and single muon tracks were

Fig. 5. Computer reconstruction of one view of a heavily ionizing track selected during the Soudan 2 magnetic monopole search. The high ionization results from the clearly visible electromagnetic showers. Such interactions are not expected to occur along a monopole track, which would exhibit uniform heavy ionization, so this event was easily rejected as a monopole candidate.

Fig. 6. Computer reconstruction of a cosmic ray muon track in Soudan 2, showing an easily recognizable low energy delta ray. The presence of such delta rays along magnetic monopole candidate tracks was used to identify them as cosmic ray muons. A monopole with high enough velocity to produce a delta ray (velocity greater than $0.95 c$) would be very heavily ionizing (about 1000 times minimum ionization) and easily recognizable.

Monopole Flux Limits

Fig 7. Recent published monopole flux limits, including the current Soudan 2 result. Several techniques are shown: magnetic induction (dashed line), track etch (dotted lines), and gas ionization (solid lines). The Parker Bound upper limit, from galactic magnetic field considerations, is also shown.

also collected. Data currently recorded by the detector are being processed by the same software, and interesting events in various categories are being selected by the same criteria used during the reprocessing. These event summary files are the input for all the ongoing physics analyses of Soudan 2 data.

A total of 0.50 fiducial kiloton years of contained event exposure was reprocessed, yielding a file of 550,000 events passed by the contained event filter. A second software filter selected 27,000 of these events for scanning by physicists. An initial examination of these events has led to the identification of about 70 neutrino interaction candidates plus a number of possible neutron interaction events (which are associated with hits in the active shield). The number of neutrino events found agrees well with the expected rate of atmospheric neutrino interactions. A second scan of the 27,000 event sample is now being performed, and detailed analysis of the neutrino event candidates is being carried out by University of Minnesota students Don Roback (an Argonne Lab Grad student) and Dave Schmid for their Ph.D. theses. The subjects of these theses are the search for neutrino oscillations using the ν_μ/ν_e ratio, and the search for nucleon decay, respectively.

In addition to the paper published in Physics Letters B described above, Argonne physicists coauthored several external documents submitted by the Soudan 2 collaboration. Most notable among these were nine papers presented at the 22nd International Cosmic Ray Conference in Dublin in August, which are now available in the published proceedings. Argonne physicists also wrote a number of internal PDK notes during the last half of 1991. In conjunction with work on the design of the proposed Fermilab-Soudan long baseline neutrino oscillation experiment, P-822, Argonne physicist Maury Goodman chaired the organizing committee of the Workshop on Long Baseline Neutrino Oscillations which was held at Fermilab in November.

(D. Ayres)

3. Polarized Proton Physics

During this period, activities associated with the future program of polarized proton-proton collisions at RHIC (the Relativistic Heavy Ion Collider at Brookhaven National Laboratory) increased significantly, while at the same time the analysis of Fermilab E-704 data was proceeding.

a) E-880 Approval

In August 1991, AGS Proposal # 880 was presented to the HENP Program Advisory Committee. The proposal was to test the effects of a partial Siberian snake on polarization at the AGS. The collaboration consists of Indiana University, Argonne National Laboratory, Brookhaven National Laboratory, KEK (Japan), and TRIUMF

(Canada). We were informed by Mel Schwartz, ALD for high energy and nucleon physics, that the proposal had been approved. According to his letter dated September 3, 1991, we learned that the PAC was enthusiastic about the elegant solution which the partial snake provides for obtaining polarization in the AGS. The letter also states that this enthusiasm is primarily a reflection of the Committee's belief that spin physics at RHIC is both feasible and potentially exciting.

b) Workshop on E-880 Collaboration

In October 1991, the first workshop on the E-880 experiment was held at Argonne, organized by members of the polarization physics group. The workshop included reviews of partial snake experiments and beam polarimeters, discussions of various problems associated with a new AGS internal polarimeter, accelerator physics of polarized proton acceleration, and discussions of the AGS program, priorities for our future work, and project scheduling.

c) RHIC Spin Collaboration (RSC)

RHIC offers an exciting opportunity to study collisions of polarized protons at high energy with high luminosity. RSC presented a letter of intent to the PAC in August 1991, and was encouraged to submit a proposal.

The physics issues for the polarized collider include a study of the spin content of the proton (particularly the helicity distribution of gluon and antiquark polarization), quark transversity distribution in polarized protons, study of asymmetries predicted by PQCD for parton-parton subprocesses, W and Z physics, and parity-violation studies and searches. To accomplish these physics goals, measurements of high p_T jets, direct photons, Drell-Yan process, $W^\pm$, and heavy quarks are needed.

The institutions presently participating in RSC are ANL, BNL, Dubna (Russia), Indiana, Helsinki (Finland), ITEP (Serpukhov), KEK (Japan), Kyoto (Japan), Marseille (France), MIT, Padova (Italy), Penn State, Trieste (Italy), Genova (Italy), and UCLA.

In RHIC, spin depolarizing resonances can be overcome with two Siberian snakes located in straight sections 180° opposite to each other. Using the split snake configuration, proton collisions with longitudinal or transverse polarization can be achieved. Top energy for proton on proton will be at $250 \text{ GeV} \times 250 \text{ GeV}$ with luminosity of $L = 2 \cdot 10^{32} \text{ (cm}^{-2} \text{ sec}^{-1})$, the same luminosity as unpolarized beams. The beam polarization $P_B = 0.70$ will be reversed in each bunch.

For measurements of beam polarization, we may utilize the kinds of polarimeters and monitors developed for the Fermilab polarized-beam facility at 200 GeV/c. Currently we are devising concrete plans on how to use these in the collider mode.

There are two major detectors planned for RHIC. A considerable number of studies were made to determine how well the spin programs of RSC could be carried out by each detector.

d) E-704 Data Analyses

Our new experimental results which show the spectacular mirror symmetry effect observed in π^+ and π^- inclusive production with 200 GeV/c polarized proton beam were published (Phys. Lett. B264, 462 (1991)). These data (Fig. 8) show that the π^- data are consistent with zero up to $x_F = 0.4$ whereas the π^+ data show a sizeable asymmetry.

We observe two kinds of physical phenomena:

Large x_F regime -

This mirror symmetry effect was explained by Soffer and Törnquist (to appear in Phys. Rev. Lett.) who relate this to the mirror symmetry of the polarizations for $\pi^\pm p \rightarrow p\pi^\pm$ in the backward direction at low energies via a dynamical mechanism in the fragmentation region.

Small x_F regime -

π^- data at 18.5 GeV/c in the interval of $x_T = 0.2$ to 0.8 show $A_N \approx 0$ up to $x_F = 0.4$ where π^+ data show sizeable asymmetry for $x_T > 0.4$. Our Fermilab π^0 data at 200 GeV/c also show sizeable asymmetry in the region $x_T > 0.4$. We note the quark contents of pions: $\pi^+ = u\bar{d}$, $\pi^0 = (u\bar{u} - d\bar{d})/\sqrt{2}$, and $\pi^- = \bar{u}d$. A polarized proton can be viewed as a scalar (ud) diquark and an unpaired u quark which is the carrier of the spin information. (A. Yokosawa)

4. Computational Physics

The main interests of the Computational Physics effort are focused on two areas: one is the continuation of the investigation on the properties of the strong interaction (QCD) using numerical methods. The other is a study of the continuum limits of various lattice models related to quantum field theories such as QED and Abelian Higgs theory. The choices of numerical simulation methods depend on the nature of problems. For lattice QCD and QED with dynamical staggered fermions, the Hybrid Molecular Dynamics algorithm is used. For lattice QCD with Wilson fermions, the Hybrid Monte Carlo method is used. The Metropolis Monte Carlo method with the Over-relaxation methods is used for the quenched QCD hadron spectrum calculation and for the Abelian Higgs theory.

The study of lattice QCD with two light staggered quark flavors of which mass is 0.0125 in lattice units on a $16^3 \times 8$ lattice is almost completed. It is part of efforts in collaboration with members of the HEMCGC (High Energy Monte Carlo Grand Challenge) on the CM-2 at PSC (Pittsburgh). D.K.Sinclair presented the results of simulation at Lattice'91 conference in Japan last November. In that talk (ANL-HEP-CP-92-4), it is concluded that there is no evidence for a first order phase transition in this system, and the transition temperature is estimated to be $T_c = 143 \pm 7$ MeV. All the measured observables, the Wilson/Polyakov line, $\langle \bar{\psi}\psi \rangle$ and entropy densities support these conclusions. Additionally, the hadronic screening mass was measured (Fig 9). Currently, we are simulating at $6/g^2 = 5.55$ with a different starting condition and at $6/g^2 = 5.575$ to clarify further the characteristics of the transition. Also the simulation of the same system with smaller mass, 0.00625 in lattice unit is under way. Smaller mass simulation is necessary because we are interested in the chiral limit $m_q a \rightarrow 0$. So far, we have run for 1000 time units at $6/g^2 = 5.55$ and the run at $6/g^2 = 5.525$ reached 800 time units.

The preparation for quenched QCD hadron spectrum on a $32^3 \times 64$ lattice at $6/g^2 = 6.5$ using the Concurrent Supercomputing Consortium's Intel Touchstone Delta computer at Caltech is finished. The VAX Fortran program is fully converted into i860 assembly language program to speed up the performance. The code is using Metropolis Monte Carlo algorithm with over-relaxation steps. At present, we have produced two field configurations which are 1000 sweeps apart. We plan to collect 100 configurations to calculate hadron spectrum. S.Kim gave a talk summarizing the current status of our project at the first Concurrent Supercomputing Consortium application workshop. Due to ardent programming efforts by S.Kim and D.K.Sinclair, the QCD code sustains 9.45 Gflops (10^9 floating point operation per second) on a 16×32 node configuration of Delta computer, which is the highest speed achieved among all the applications on this machine.

In collaboration with J.B. Kogut of the University of Illinois, we are investigating non-perturbative fixed points of various lattice models. The question addresses fundamental and interesting problems involved in lattice formulation of quantum field theories: the existence of interacting theory in continuum limits of a lattice model. In the work with J.B.Kogut and R.L.Renken of the University of Illinois, S.Hands of the University of Glasgow and A.Kocic of the University of Arizona (ILL-TH-91-04), we have studied the strong coupling phase transition of QED (quantum electrodynamics) using non-compact lattice model of the theory and found that the transitions observed in this system appear to be driven by lattice artifacts. Further study on the system is under way. Also, we have initiated studies on the Abelian Higgs theory. Our main interests lie in the continuum limit of non-compact lattice models of this theory, which is the same as our

Fig 8. $p^+ p^- \rightarrow \pi^\pm X$ at 200 GeV/c.

Fig. 9. Hadronic screening masses. The dashed lines are at $\text{mass} = 2\pi/N_t$ and $\text{mass} = \sqrt{8\pi}/N_t$.

study on strong coupling QED. However, since the Abelian Higgs theory has more complicated and richer classical structure, fixed points of this theory may be more interesting. We will employ the Metropolis Monte Carlo method and use a Connection Machine.

(D. Sinclair)

B. Experiments Taking Data

1. Soudan 2

The Soudan 2 experiment operated smoothly during the second half of 1991, and recorded data for 139 days of live time, with a duty cycle of 75%. This brought the total Soudan 2 exposure to 833 days, or 83% of a fiducial kiloton year for contained events. The detector is operated for physics data primarily during night and weekend periods when installation work is not in progress and the underground laboratory is unoccupied.

The quality of the data recorded by Soudan 2 continued to improve during the second half of 1991. Although no additional detector mass was installed during this period, several older modules with nonuniform wireplane response were replaced. These modules were overhauled and reinstalled in the detector, as described below. A number of anode high voltage splitters, which allow top and bottom modules to operate at different, optimum wireplane voltages, were installed while the detector was open for module replacement. The filling of cracks between active shield floor panels also continued, and 65 new shield tubes were brought into operation.

(D. Ayres)

2. Medium Energy Spin Physics (LAMPF/SATURNE)

The goal of the ANL-HEP medium energy physics program in the past few years has been to measure sufficient np elastic scattering spin observables to determine the isospin-0 ($I = 0$) amplitudes and phase shifts between kinetic energies of 500-800 MeV. These measurements included LAMPF experiment E-665/770, E876, E-960, E-1234, and others. Recently, a new nucleon-nucleon scattering program has begun at Saclay, France with a goal to extend the $I = 0$ measurements to higher energies and to investigate the origin of energy-dependent structure in various spin observables near 2100 MeV.

The final paper on E-665, documenting much of the hardware and data analysis for E-665/770, is essentially complete, and will be submitted in the next few months. Pure spin observables C_{LL} and C_{SL} , with a polarized neutron beam scattering from a polarized proton target, were extracted from the data and are shown in Fig. 10. In addition, a number of phase shift predictions, some including preliminary data from this experiment, are shown for comparison. These phase shift predictions have typical deviations of $\chi^2/d.f.$

~ 2.6 from the data. The final data will contribute significantly to the knowledge of the $I = 0$ amplitudes between 484 and 788 MeV.

A full draft of a major paper of E-770 has been written, and final results were obtained during the past half year. Pure spin observables (C_{SS} , C_{LS}) were extracted from the mixed spin parameters actually measured. Also, the quantities $C_{SS} d\sigma/d\Omega$ and $C_{LS} d\sigma/d\Omega$ for pure $I = 0$ amplitudes, and for the interference between $I = 0$ and $I = 1$ amplitudes, were extracted. Work is in progress to relate these quantities to phase shifts and to understand the observed energy dependence in the data. This paper on E-770 may be submitted for publication during the next six month period.

Work has begun on a re-analysis of the remaining E-770 data from existing data summary tapes. Some of these data have been published in a short paper, but improvements in data analysis and revised spin direction information make the re-analysis necessary. Essentially all the remaining data are mixtures of the spin parameters C_{LL} , C_{SS} , C_{LS} , and C_{NN} .

Experiments E-876 and E-1234 collected data during this period. The first is a measurement of np elastic scattering with a polarized neutron beam scattering from a liquid hydrogen target and the outgoing proton spin determined with a carbon polarimeter. The spin parameters K_{LL} , K_{LS} , K_{SL} , and K_{SS} were measured last year at 788 MeV and were recently published. The same parameters were measured at 634 MeV this year, and the data are being analyzed and a paper written. The second experiment, E-1234, used a similar setup but had the neutron beam scatter from a liquid deuterium target with the outgoing proton spin measured. The goal of E-1234 is to obtain independent information on the neutron beam polarization. Preliminary results, shown in Fig. 11, suggest that the polarization parameter P for np elastic scattering measured by other groups at LAMPF may be systematically too large in magnitude. A paper on E-1234 and an instrumentation article on the relative neutron polarimeter used in E-876 and E-1234 are being written. An instrumentation paper describing the ANL neutron counters used in E-876 and E-960 was recently published.

The experimental program at Saclay was begun in November. A multiwire proportional chamber (MWPC) with four planes of wires was constructed, as well as the associated cables. The chamber, cables, MWPC electronics, supports and tools were shipped to Saclay before the run, but were delayed by over two weeks in French customs. As a result, there was not time to install the chamber before the experimental runs. However, cables were strung and the electronics mounted before the end of the run. It is hoped to complete this work before the next run.

Fig. 10. Final results on the np elastic scattering spin observables C_{LL} and C_{SL} at 484, 634, and 788 MeV as a function of c.m. angle. The curves are phase shift predictions of Arndt et al. (solid line), Bugg (dot-dash), Saclay-Geneva (dashed), and Hoshizaki et al. (dot-dot).

Fig. 11. Preliminary results for the spin transfer parameter K_{LL} for the reaction $\bar{p} + d \rightarrow \bar{n} + X$ and $\bar{n} + d \rightarrow \bar{p} + X$ from experiments E-1234 as a function of beam kinetic energy. The data are compared to a prediction by Bugg and Wilkin (solid line) and to the free np results (dashed line).

During the run, the pp polarization parameter P and C_{NN} were measured at a few energies near reported energy dependent structure. However, problems with an aging data acquisition computer and with the electronics did not allow sufficient data to be collected. These measurements will continue in the Spring of 1992.

(H. Spinka)

C. Experiments in Preparation Phase

1. Collider Detector at Fermilab

Installation of preradiator chambers has been completed. Checkout in situ of preradiator, crack, and strip chambers was delayed by the unavailability of the data acquisition system, which also delayed the PMT checkout and calibration. Test beam data on preradiators and such cosmic ray testing as could be acquired bodes well for the performance of the preradiator system as shown in Fig. 12. The high voltage and gas systems for all chambers have been brought up.

Design work on the Level 2 FASTBUS trigger electronics for the strip and preradiator chamber electron trigger is nearing completion. Our colleagues are preparing a sample of modified wire readout front end cards and a sample of trigger cables from the detector to the counting house has been installed. This should allow some checkout in the upcoming run with an eye toward complete installation during the next shutdown.

The Fermilab fixed target run and brief machine studies extended throughout the period. As much of the CDF detector as was available (i.e. not locked in the hall or with uncompleted upgrades), was made ready for global cosmic ray testing. This served its purpose for early diagnosis of various DAQ, gas, high voltage and noise problems.

The length of the shutdown after the run which should eventually begin some time this spring has become a topic of much speculation. Also, the bunch spacing for 1995+ running is still not settled. Funding for the DAQ/front end, plug calorimeter, and silicon vertex detector upgrades for 1995 is likely to be too slow to maintain that year as a target. The Argonne group has a slight association with the plug upgrade effort, particularly as correlated with SDC activity, and we hope to get involved in the front end upgrade. Attention is now focussed on getting the hardware and software ready for the coming collider cycle. Vertex drift chambers, muon extension, muon hardener, and silicon vertex detectors join the preradiator in being added to CDF for the coming run. Data taking should resume this spring after a hiatus of three years.

(L. Nodulman)

1991 Test Beam

Fig. 12. Tests of electromagnetic shower development with the CDF Central Strip Chambers (CES). We vary the amount of material in front of the CES for 10 GeV electrons, and compare the relative energy response to a shower theory parameterization. The agreement is poor, perhaps indicative of the problems inherent in using a thin gas detector. The response of the Central Preradiator Chambers (CPR) to minimum ionizing particles is also shown, demonstrating that the response in the CES is not due to gas gain changes (the two chambers shared the same gas supply).

2. Soudan Detector Installation

Only nine 5-ton modules were constructed at the Argonne module factory during the last six months of 1991 because of problems with the supplies of corrugated steel sheets and bandolier. During the two month period when steel supplies prevented the construction of new modules, the Argonne collaborators developed techniques to remove an electronegative contaminant which had suddenly appeared in recently constructed bandolier. The contaminant was identified as excess methylene chloride solvent in the bandolier adhesive, which should have been removed at an early stage of the manufacturing process. By the time the contamination was recognized, many of the 20 U.S. and U.K. modules which had been constructed with the faulty material had been shipped to the Soudan mine. During the summer, the Argonne mechanical support group developed a procedure for bandolier decontamination, using a 3-day oven heat treatment prior to module assembly. A second technique was developed for decontaminating modules which had already been assembled. This involved special fixtures for heating modules to 50° C with a hot air purge for a three week period. By the end of the 1991 shipping season, all modules at Argonne had been decontaminated, routine module construction had resumed, and 12 modules had been shipped to the Soudan mine.

Because of the shortage of modules without electronegative contamination, no new halfwalls were added to the Soudan 2 detector during the last six months of 1991. The operating mass remained at 688 tons during this period. The 12 modules which arrived at the mine site from the Argonne module factory brought the total number of modules underground to 192 (825 tons). The uncontaminated modules which were available were used to rebuild the two detector halfwalls which contained the worst performing modules in the detector. The modules from the first of these halfwalls were overhauled and used to rebuild the second halfwall. (A halfwall is a subassembly of eight 5-ton modules, stacked four across and two high.) Several individual modules were also replaced during this period. In December, the module heating fixtures used to decontaminate modules at Argonne were shipped to Soudan, where heat treatment of contaminated modules will begin in early 1992.

Argonne physicists continued to play major roles in the installation, turnon, and data acquisition activities at the Soudan mine site. Important activities during the second half of 1991 included diagnosis of the source of module contamination which caused recent modules to drift very poorly, electronics maintenance and troubleshooting, and coordination of the module replacement and repair activities described above.

A team of DOE program officers met with Soudan 2 collaborators at Argonne in July to consider the request for additional funds to build the last 100 tons of the detector.

Although this proposal was turned down, the previous commitment of funds, which is sufficient for a 930 ton detector, was reaffirmed. It was agreed that the detector construction would be completed in 1992, and that the full detector would be operated for six years. This includes an additional year of operation to compensate for the mass reduction from the originally planned 1100 tons. (D. Ayres)

3. ZEUS Detector at HERA

a) HERA Status

By the end of 1991, all of the major problems confronting HERA appeared to be solved. The proton linac III was reliably delivering 8-10 mA of H^+ (multiturn injection into DESY III). DESY III, the most difficult component, was routinely accelerating 70 mA to 7.5 GeV. The maximum current obtained so far is 90 mA (the design value is 150 mA). PETRA III has accelerated up to 3.5×10^{11} protons in a single bunch up to 40 GeV although there is need to upgrade the vacuum. Transfer efficiency of 100% from PETRA III to HERA is obtained. In the electron ring, the required single bunch intensity of $3.7 \times 10^{10} e^-$ has been transferred into HERA. The maximum intensity is limited by multibunch instabilities. The design current of 58 mA from 210 bunches has been achieved at the level of 6 mA for 20 bunches without the multibunch feedback system which has now been successfully tested in PETRA. The last machine test in November achieved collisions with 10×10 bunches at 96 nsec spacing. A simple scaling from this in terms of bunch current and number extrapolates to a luminosity close to design. Machine operation is expected to resume in April 1992 with physics data taking starting in June. An example of the luminosity monitor data from the November run is shown in Fig. 13.

b) Test Beam Operations

The ZEUS test beam in Lab E at Fermilab was operated from June to August. Although a small amount of data was taken during commissioning of the beam in 1990, this recent run provided most of the module calibration data. In all, seven modules, including the prototype, were calibrated. Analysis of these data continued at DESY after the beam operation was concluded. First results presented at the ZEUS collaboration meeting at DESY in December demonstrated that the design requirements for the hadron energy resolution and linearity had been met. The measured electron energy resolution was somewhat worse than expected.

The energy resolution for fully contained 50 GeV pions is shown in Fig. 14a. The measured hadron energy resolution as a function of energy is compared to the design value $\sigma/E = 35\%/\sqrt{E}$ in Fig. 14b. As expected for a compensating calorimeter, the response to

ZEUS: Fermilab Test Beam Data

Fig. 14. Energy resolution of the ZEUS barrel calorimeter for (a) 50 GeV pions; (b) as a function of pion energy. The backing calorimeter was used to veto events with energy leakage from the rear of the module.

Fig. 13. Electron-proton collisions in HERA as seen by the ZEUS luminosity monitor.

hadrons demonstrates very good linearity, as shown in Fig. 15. In Fig. 16 one sees that the tower-to-tower response is uniform at the level of about 1%.

c) ZEUS BCAL Installation and Commissioning

Commissioning of the ZEUS detector began in August-September, although at that time only 29 of the 32 BCAL modules were installed. The detector was closed in August and the magnet was energized so that the magnetic forces on the coil could be measured for the first time with the real distribution of iron in the detector. It was only possible to reach a solenoidal field of 1.33 T before the maximum force of 5 tons allowed by ANSALDO (the manufacturer) for the coil was reached. It was found that the cell geometry used in TOSCA in modelling the iron distribution in the BCAL was inadequate and thus TOSCA incorrectly predicted there would be no problem in attaining full field. This was aggravated by the problems encountered in loading the 29 BCAL modules into the spokesplates in May, when the spokesplates moved on the system of Hillman rollers on which they rest, so that their position was incorrect by 8 mm in the z (beam) direction as well as being rotated by about 1 milliradian.

A cosmic ray run of the detector in September was partially successful in integrating all detector components into the trigger. Most of the detector components had useful stand alone runs, but because of problems in obtaining the Wiener power supplies on schedule, only four BCAL modules were included in the run. A Lego plot showing cosmic ray muons in the BCAL for the up-down trigger is found in Fig. 17.

The last 3 BCAL modules from the FNAL test beam were installed in ZEUS in October. On November 23, the BCAL was translated to within 0.5 mm of its nominal z position although it was only possible to reduce the rotational misalignment to 0.7 mrad. Moving the approximately 350 ton system with respect to the four Hillman roller systems on which the spokesplates rested was accomplished by pushing/pulling with a system of hydraulic rams.

A second cosmic ray/magnet test run was carried out in December. It was possible to achieve a field of 1.43 T, in good agreement with the TOSCA prediction (with improved modeling of the iron distribution in the detector). A further prediction of TOSCA is that if the rear calorimeter (RCAL) is moved 1 cm away from BCAL the attainable field will be very close to the design of 1.8 T, provided that ANSALDO agrees, as expected, to allow a maximum force of 6 tons on the coil.

ZEUS: Fermilab Test Beam Data

Module #26

Leakage from back vetoed

Hadron Linearity (BCAL)

Hadron Linearity

Fig. 15. Linearity of the ZEUS barrel calorimeter response as a function of hadron energy.

ZEUS: Fermilab Test Beam Data
Module #26

RMS
Error bar shown is RMS not $\sqrt{N}$

Fig. 16. The tower-to-tower response of a ZEUS barrel calorimeter module to (a) muons; (b) electrons.

"Left" side PMT's

"Right" side PMT's

Fig.17. A cosmic ray muon seen in the ZEUS barrel calorimeter.

d) Photomultiplier Base Problem

In the process of testing modules on the cosmic ray stand, photomultiplier (PMT) bases were observed to fail at the level of several percent per module. The base failure rate was established during extended periods of Fermilab module testing and BCAL commissioning at DESY as one base/module/week. Studies by the VPI group suggest the failure is due to capacitors in the dynode chain becoming resistive. Leakage of charge to the outside of the PMT results in sparking to ground and capacitive coupling to the dynodes exposes the capacitors to high frequency voltage transients causing their failure. The suggested remedy is to wrap the PMT in aluminum foil which is then grounded. Observation of a somewhat statistically limited sample of PMT's treated in this way suggests this may reduce the failure rate to manageable proportions. This modification is being implemented on more modules.

e) Changes in PMT Gain Due to the Detector Magnet Field

It is now well known that the light output of plastic scintillator varies with the magnitude of magnetic field to which it is exposed. The expectation was that the response of the ZEUS BCAL PMT's to the uranium activity (DU noise current) would be essentially a uniform shift in value within each section, EMC, HAC1 and HAC2 of a module at the level of a few percent. During the first cosmic ray run in September it was found that the DU current apparently varied randomly within a module, with variations of up to 4% observed. The magnetic shielding provided for the BCAL PMT's was expected to reduce the field in the region of the photocathode below 100 mG, generally considered to be sufficient.

Measurements were made on a BCAL PMT-magnetic shield unit in the field of a bending magnet at ANL in October. These measurements showed that the field in the region of the photocathode was about 50 mG but the gain of the PMT could still vary by as much as $\pm 5\%$ depending on the direction of the field with respect to the plane of the PMT dynode structure. Since the PMT's were not installed in the BCAL modules so that their dynode structures all had the same orientation with respect to the essentially solenoidal field in the module backbeam region, this accounted for the apparently random observed variation of the DU current when the detector solenoid is energized. Techniques to standardize the PMT orientation with respect to the field direction are being explored. The sensitivity of the PMT orientation with respect to the field direction for that orientation which would give minimum gain change is shown in Fig. 18. This illustrates that a precise location of the PMT is required to avoid gain changes of 1-2% with the present shielding.

(B.Musgrave)

Fig. 18. The variation of photomultiplier gain as a function of the angle between the B-field direction and the plane of the photomultiplier dynode.

4. SDC Calorimeter Engineering Design

Advances in the design of the SDC detector for use at SSC continued in the second half of 1991. Argonne is a leading member of the Central Calorimeter group and has also contributed strongly to the computing and physics application groups. The SDC as a whole grew to a total of 102 institutions with over 700 physicists during this period. As such, it is undoubtedly the largest scientific collaboration ever dedicated to a single project. It will remain a challenge to demonstrate that an assemblage of people this large can maintain its focus and deliver a successful detector and its scientific program on the desired schedule. In this context, it is useful to note the valuable participation of the Bicron Corporation and the Westinghouse Science and Technology Center as industrial partners of Argonne (and SDC) in the work reported below. In the sections below, the Argonne contributions to this goal are discussed by topic.

a) Calorimeter Mechanical Design

The mechanical design of the barrel section of the Central Calorimeter (CC) evolved steadily to a buildable, cost-effective structure that was able to meet or exceed all the SDC design requirements. The final decisions were made on the passive absorbers for the electromagnetic (EM) and first hadronic (HAD1) calorimeter sections. 4 mm cast Pb plates will be used for the EM section as proposed by Argonne and 24 mm steel plate will be adopted for the HAD1 section as proposed by Fermilab. This also sets the thickness of the catcher calorimeter plates (HAD2) as 54 mm, also of steel. Having set these parameters, those of the endcap calorimeter were also determined by the specification that the resolution in p_T was to be maintained constant over the eta range of 0-3. The total thickness of the CC was set at 10λ at $\eta = 0$ (and increased logarithmically to 12λ at $\eta = 3$). Thus, the main CC physics parameters were set and confirmed by the whole SDC during the period of this report. The status of the CC design at the end of 1991 is shown in Fig. 19.

Important as the physics-related decisions noted above were, the detailed engineering of the wedge modules for both barrel and endcap calorimeters, including their detailed mechanical configurations, stress analyses, connection and assembly methods, fiber routing, fabrication techniques, etc. were the result of the technical efforts of ANL engineers and physicists. These design elements were gradually brought into an elegant and complete mechanical design for the barrel and to a workable basic concept for the endcaps. The leadership of Argonne in these detailed aspects of the CC design is reflected in the drawings of the calorimeter supplied in the SDC Design Report (issued in April 1992) which reflect the detailed design concepts developed and produced here.

Tile/Fiber Central Calorimeter (Quadrant Cross Section)

Fig. 19. Status of the CC design at the end of 1991.

Of particular note is the achievement of a final mechanical design for the transition of the barrel and endcap sections of the calorimeter, a difficult geometrical region where preservation of the energy resolution across the interface crate had to be achieved while maintaining all the essential mechanical support functions for the superconducting solenoid and the central tracking apparatus. After study of several geometrical alternatives, a final design was chosen. This design is reflected in the SDC Design Report.

Also, it is worth noting that the barrel and endcap designs chosen for the calorimeter (wedges in ϕ) have been the subject of extensive finite element stress analysis (FEA) carried out by both ANL and Westinghouse engineers with the result that the final configurations chosen can be fabricated, erected and operated without exceeding allowed stresses or deflections in the materials of the component parts. Adoption of a steel passive absorber in the HAD sections facilitated this latter goal tremendously. Elaboration of this FEA is included in section V.B.4 of this report.

b) Calorimeter Optical Design

Optical design of the calorimeter (scintillator tile and optical fiber elements) evolved in parallel with the mechanical design during this period. Again, Argonne physicists played a key role in the evolution of a successful design. This design evolved and detailed a tile/fiber configuration that maximized uniformity of response to ionizing radiation across the entire surface of the tile (while preserving maximum total light yield). The elegant result achieved was simple; it required no tile edge polishing or painting (beyond the basic tile machining to size needed in any design) or tile optical masking, generic or custom. The simplicity and success of this design will save time and money when the production phase is reached. Since over 300 thousand tiles are needed for the full CC, the savings will be measured in millions of dollars. Details of the R&D work leading to the present design are given in section V.B.2 of this report.

Much of the success in this effort is attributable to the development (and subsequent patenting) of a scanning beta-ray spectrometer by an Argonne physicist (reported in an earlier edition of this report). This instrument was heavily used in the evolution of the optical design finally chosen for a test calorimeter built and tested by the ANL/WSTC team (and described in sections V.B.5-6 of this report).

(T. Kirk)

II. THEORETICAL PROGRAM

Quantum Algebras

A spate of activity, exploration, and publication on quantum algebras and their physics applications has attracted renewed interest in the mathematics community, which is increasingly appreciative of "sloppy" physics results that, nevertheless, work. In order to address the demand for an overview and bibliographical orientation in the area, C. Zachos has reworked and expanded his 1990 survey of Quantum Algebras and adapted it for mathematicians. The number of references categorized and discussed has been more than doubled. The end result, "Elementary Paradigms of Quantum Algebras", appears in *Deformation Theory of Algebras and Quantization with Applications to Physics*, Contemporary Mathematics, edited by J. Stasheff and M. Gerstenhaber, AMS (1992).

A new set of questions on multiplet permutations has grown out of the work of C. Zachos and D. Fairlie (Durham) on quantum-algebra-based alternate statistics. Those questions have now moved to the forefront and are currently being analyzed by C. Zachos. In particular, for special values of the quantum parameter, in, for example, the q -deformation of $SU(2)$, the symmetry of the states may, in fact, alternate *within* a given multiplet. An example of this phenomenon appears in the composition of two doublets. For $q = 1$, the singlet is symmetric:

$$\alpha = |i \uparrow \downarrow + i \downarrow \uparrow \rangle ;$$

whereas the symmetry of the triplet alternates:

$$\beta = |\uparrow \uparrow \rangle$$

$$\Delta(J_-)\beta = \frac{1}{\sqrt{2}}|i \uparrow \downarrow - i \downarrow \uparrow \rangle$$

$$\Delta(J_-)^2 \beta = |\downarrow \downarrow \rangle.$$

This turns out to be a feature encountered so far only in supersymmetric theories. Quantum algebras are thus observed to simulate supersymmetric effects, which may, in time, reveal hidden supersymmetries in bosonic systems. New invariant Hamiltonians based on this principle have not yet been found, but this question is left for the future. [ANL-HEP-PR-92-12].

Rigorous QCD Predictions for Decays of P-Wave Quarkonia

A straightforward perturbative calculation in QCD of the decays of p-wave heavy quarkonia leads to the appearance of logarithms of the quark binding energy. The presence of such logarithms is a signal that processes involving soft gluons make important contributions to the decay rates, thereby invalidating the purely perturbative calculation. G. Bodwin, E. Braaten (Northwestern), and G.P. Lepage (Cornell) have shown that, to leading order in v/c , the soft-gluon effects can be factored from the decay rate and take the form of a single nonperturbative quantity: the probability to find the quark-antiquark pair at zero separation, with their original spin orientation, and in a color-octet s-wave state. The remaining factor in the decay rate, the annihilation of the color-octet s-wave state, involves only short-distance interactions and, hence, can be calculated reliably in perturbation theory. The nonlogarithmic contributions to the decays of the p-states can be expressed in terms of the derivative of the quark-antiquark wave function at the origin. Thus, rigorous predictions for the decays of the four p-wave states into light hadrons or into two photons can be made in terms of α_s , α , and just two additional phenomenological parameters.

The Current Status of High-Energy Elastic Scattering

Motivated by recent results from the Fermilab Tevatron Collider and in anticipation of the UA4/2 experiment at the CERN Collider, M. Block (Northwestern), K. Kang (Brown) and A. White have published a review (ANL-HEP-PR-91-61) of the current experimental and phenomenological status of high-energy elastic scattering. While emphasizing that the new results conform to an overall simplicity and consistency with lower-energy data, the authors discussed a variety of interpretations of experimental forward-scattering parameters. A simple Regge-pole Pomeron looks very appealing given the latest data. There are, nevertheless, small but clear deviations from the predictions of this model that are not easily explained. An asymptotic amplitude analysis, although unjustified as a matter of principle, shows that the total cross section rises essentially linearly with $\ln s$. Within this formalism the UA4 result for the real part of the amplitude cannot be fit, with or without an Odderon. Indeed the UA4 result can only be fit with a very special form of new threshold close to the energy range of the CERN collider. Such a threshold would have to be associated with (dramatic) new physics. If the UA4 result is discounted, a wide class of eikonal models provides a generally satisfactory description of almost all the features of the data. However, the complexity of the relationship between input assumptions on the nature of the eikonal and output amplitudes tends to obscure the physical significance of this success.

A similar review, but with a different emphasis, is contained in a paper by Block and White (ANL-HEP-CP-91-95), which was presented at the XXI International Symposium on Multiparticle Dynamics.

Chiral-Symmetry Breaking In Gauge Theories From Reggeon-Diagram Analysis

In a paper prepared for the Hiroshima International Workshop on Electroweak Symmetry Breaking, A. White described the use of Reggeon diagrams to study dynamical properties of gauge theories containing a large number of massless fermions. Reggeon-diagram infrared analysis is directly valid when enough massless fermions are present to produce an infrared fixed point for the gauge coupling. This analysis also requires the gauge symmetry to be built up step-by-step via a series of infrared limits. Consequently, information is obtained about gauge theories in a very different dynamical situation compared to most other starting points. White has studied SU(2) gauge theory in detail and has argued that there is a high-energy solution that is analogous to the solution of the massless Schwinger model. "Anomalous interactions" due to the triangle singularity in massless-quark Reggeon diagrams play a vital role in the emergence of a Reggeon condensate. The condensate, which can be interpreted as a generalized winding-number condensate, produces the massless pseudoscalar spectrum associated with confinement and chiral symmetry breaking and also leads to a high-energy S-Matrix that is "trivial" in the extreme sense that there is no Pomeron. The no-Pomeron solution of SU(2) gauge theory plays a vital role in the emergence of a physically sensible Pomeron in QCD and SU(N) gauge theories.

Transverse-Momentum Distribution of Z-Boson Pairs at Hadron Supercolliders

R. Meng, T. Han (Fermilab), and J. Ohnemus (Durham) have studied the transverse-momentum distribution of the Z-pairs in the process $pp \rightarrow ZZ$ at supercollider energies. In this work they obtained the whole $p_T(ZZ)$ spectrum by matching the low- p_T result (from resummation of soft gluons to all orders in α_s) to the high- p_T result (from the $O(\alpha_s)$ perturbative calculation). They found that the perturbative $O(\alpha_s)$ calculation is invalid for $p_T(ZZ) < 25$ (35) GeV at the LHC (SSC) energy.

In heavy-Higgs-boson searches, a minimum cutoff on M_{ZZ} may be needed in order to suppress the $ZZ + \text{jet}$ backgrounds. However, in order to make the $O(\alpha_s)$ background calculation reliable, it is also necessary to place a cutoff on p_T that increases with increasing M_{ZZ} . Meng and collaborators have shown that, in order to avoid large logarithms of the form $\ln(p_T^2 / M_{ZZ}^2)$, which spoil the $O(\alpha_s)$ perturbative calculation, one

needs to impose, for example, $p_T(ZZ) > 45$ GeV for $M_{ZZ} > 500$ GeV, and $p_T(ZZ) > 60$ GeV for $M_{ZZ} > 800$ GeV at the SSC energy.

Since the $p_T(ZZ)$ spectrum is governed entirely by QCD radiation, and since the ZZ production rate at supercollider energies is sizable, the results of Meng and collaborators could also provide a good test of perturbative QCD at a scale of order 200 GeV.

Meng and collaborators have also compared their results for the $p_T(ZZ)$ distribution with shower Monte Carlo results from PYTHIA. They have found good agreement in shape for $p_T(ZZ) < 100$ GeV. However, PYTHIA significantly underestimates the rate for large $p_T(ZZ)$.

Heavy-Quark Cross Sections at Hadron-Collider Energies

Calculations of heavy-flavor cross sections at current hadron-collider energies are of interest for tests of perturbative quantum chromodynamics (QCD) and for the exploration of the sensitivity of results to the gluon density. At energies relevant for future colliders, the predictions assist in the design of experiments and in the evaluation of the merits of various options, such as the possibility of using the Superconducting Super Collider (SSC) in a fixed-target mode. In Argonne report ANL-HEP-PR-92-11, E. Berger and R. Meng present calculations of inclusive cross sections for bottom-quark production in proton-proton and proton-antiproton collisions at energies ranging from $\sqrt{s} = 100$ GeV to $\sqrt{s} = 40$ TeV. For several energies, cross sections are shown as functions of transverse momentum, rapidity, and pseudo-rapidity (see Fig. 20). The computations are based on next-to-leading order QCD hard-scattering cross sections and on the latest published sets of two-loop evolved parton densities obtained from global fits of data from deep-inelastic lepton scattering and other reactions. Variations of the behavior of the gluon density in the region of very small x provide an estimate of the range of theoretical uncertainty. At SSC energies, results are presented for both the collider configuration $\sqrt{s} = 40$ TeV and the fixed-target option $\sqrt{s} = 200$ GeV. Included in the paper are calculations of charm-quark inclusive cross sections at $\sqrt{s} = 200$ GeV and 1.8 TeV.

Isolated Prompt-Photon Production at Collider Energies

The goals of the study of prompt-photon production at large transverse momentum at collider energies include tests of perturbative quantum chromodynamics and the determination of the gluon density in nucleons at small values of Bjorken's $x \approx x_T 2p_T / \sqrt{s}$. In addition, isolated photons at large p_T may be signals for new physics processes. During the latter half of 1991, E. Berger and J. Qiu (Iowa State University)

continued their investigations of the theory and phenomenology of isolated prompt-photon production. In Argonne report ANL-HEP-CP-91-72, published in the proceedings of *Particles and Fields '91*, Vancouver, Canada, Berger and Qiu summarized the progress they have made toward a consistent treatment of the isolated prompt-photon cross section in QCD perturbation theory. They showed that well-behaved predictions can be derived for a wide range of isolation parameters.

Restoration of Spontaneously Broken Symmetry at High Temperature: Resolving the Unitary Gauge Puzzle

Broken gauge symmetries are typically restored at high temperature, and the critical temperature T_c can be found to leading order through a simple, one-loop calculation in a renormalizable gauge. However, when one investigates the restoration of broken gauge symmetries at finite temperature, calculations in unitary gauge appear to give different results than calculations in other gauges. Gauge invariance requires that physical quantities, such as effective particle masses or the critical temperature, be independent of gauge choice. It has long been a puzzle as to how to bring unitary gauge calculations into agreement with those in renormalizable gauges. In a paper submitted to the Physical Review, S. Vokos, in collaboration with P. Arnold (Northwestern) and E. Braaten (Northwestern), showed that, in the Abelian Higgs model, for temperature T small compared to T_c , the loop expansion in unitary gauge is an expansion in T^2 / T_c^2 . Thus, all orders in the loop expansion are relevant to the leading-order determination of the critical temperature. In this work (ANL-HEP-PR-91-108), Vokos and collaborators verified by explicit two-loop calculation that gauge-invariant quantities, such as the effective scalar mass and the free energy of the vacuum, agree with renormalizable gauge results to order T^4 / T_c^4 . To this order, the equivalence of unitary and renormalizable gauges may be succinctly summarized by the corresponding high-temperature effective Lagrangians, which differ only by a non-linear field redefinition. In addition, Vokos, Arnold, and Braaten have derived the effective mass of the vector boson and found that there are two contributions to it. One is proportional to the scalar mass, as expected for a spontaneously broken theory, while the second contribution is the result that one obtains in the unbroken theory. Above the critical temperature, the first term is absent. In Fig.21, the scalar (solid) and vector plasmon (dashed) masses are plotted vs. T^2 . It is interesting to note that at the critical temperature, the vector mass does not go to zero.

Fig. 21. Qualitative behavior of the scalar (solid) and propagating-vector (dashed) masses plotted as $m^2(T)/m_0^2$ and $M^2(T)/M_0^2$ vs. T^2 . The vector electric-screening mass behaves similarly to the dashed line, although the question of whether it crosses the solid line at $T > T_c$ then depends on the value of λ/e^2 .

Fig. 20. The integral p_T distribution $\sigma(p_T > p_T^{\min})$ is plotted as a function of $p_T^{\min}$ for $p\bar{p} \rightarrow b\bar{b}$ at $\sqrt{s} = 630$ GeV and $\sqrt{s} = 1.8$ TeV. The data are from the UA1 collaboration and from the CDF collaboration. The solid curves calculated by E. Berger and R. Meng show the predictions obtained by convoluting the $O(\alpha_s^3)$ QCD hard-scattering cross sections with parton densities from the Morfin-Tung set B1, taking the b quark mass $M_b = 4.75$ GeV, and choosing the scale μ according to $\mu^2 = M_b^2 + (p_T^{\min})^2$. The dotted curves are an estimate of the theoretical systematic uncertainty obtained by varying the gluon density, μ , and M_b .

Radiative Corrections in Two-Scalar Doublet Models

I.G. Knowles, C.D. Froggatt (Glasgow), and R.G. Moorhouse (Glasgow) have continued their studies of extensions to the standard model, with particular emphasis on determining the way in which particles acquire their masses. A general model that incorporates all viable two-scalar doublet realizations of the Higgs mechanism for generating particle masses, including supersymmetry, has been developed. These general models involve a rich phenomenology, which includes a new source of CP violation of present interest in early universe scenarios for baryogenesis. In a paper to appear in *Physical Review D* (1 April 1992), the generic structure of these models is discussed, and all leading radiative corrections are calculated and summarized in compact expressions. In particular, the results confirm that predictions for the top-quark mass using precision measurements from the LEP experiments, CDF, etc. are no longer valid in certain of the models. Further investigation is in progress.

Identification of New Gauge Bosons at High-Energy Supercolliders

In a paper published in *Phys. Rev. D* **45**, 161 (1992), J. Hewett and T. Rizzo examine the ability of the SDC detector to identify the origin of a new neutral gauge boson, Z_2 , in the TeV mass range at the SSC. Specifically, given the measurements of the Z_2 production cross section (σ), width (Γ_2), and leptonic forward-backward asymmetry (A_{FB}), together with their associated statistical and systematic errors, Hewett and Rizzo address two related questions: (i) for two different extended electroweak models, up to what mass can their corresponding Z_2 bosons be distinguished, and (ii) how well can the Z_2 couplings be determined? The calculations include $O(\alpha_s^2)$ QCD, as well as oblique electroweak radiative corrections to the above quantities, and allow for uncertainties due to structure functions, detector efficiencies, lepton identification, luminosity measurement errors, and finite lepton-pair mass resolution, using the specifications of the SDC detector. Nine distinct classes of extended electroweak models are investigated, and results are obtained for integrated luminosities of 10^4 and 10^5 pb $^{-1}$. Results for a particular E_6 model are given in Fig. 22.

In a contribution (ANL-HEP-CP-91-90) to the *Physics and Experiments with Linear Colliders Workshop*, Hewett and Rizzo extend their studies on the discovery and identification of new gauge bosons to the NLC e^+e^- linear collider with $\sqrt{s} = 500$ GeV. The effects of new gauge bosons with masses in excess of the machine's center of mass energy can be probed via deviations from the predictions of the Standard Model for the total cross section, forward-backward asymmetry, and left-right polarization asymmetry in the

Fig. 22. $\Delta\chi^2$ as a function of the parameter θ , which is present in rank-5 E_6 models and governs the fe couplings of the new Z boson, Z_2 . Here it is assumed that the produced Z_2 is from the E_6 model $\psi(\theta)$ with a mass of 2 TeV (4 TeV), corresponding to the inner (outer) set of curves. The horizontal solid line represents the 95% CL at the SDC in determining the value of θ , the dotted (dashed, dashed-dot, and so curves depict the results from measurements of σ alone (σ and Γ_2 , σ and A_{FB} , and all data combined).

process $e^+e^- \rightarrow f\bar{f}$. It is found that new gauge bosons with masses in the few TeV regime can be probed at such a collider.

CP Violation in Top Quark Decays

A new mechanism for CP violation is applied to top quark decays by G. Eilam (Technion, Israel Institute of Technology), J. Hewett, and A. Soni (BNL) in a paper published in Phys. Rev. Lett. **67**, 1979 1991. It is found that an on-shell unstable particle produced in a tree-level process, such as the W -boson in $t \rightarrow qW$, induces a CP-violating signal through its width. This effect arises from the interference between the imaginary part of the amplitude for $t \rightarrow qW \rightarrow qq'\bar{q}$ and the real part of the amplitude for the one-loop flavor-changing process $t \rightarrow q'g \rightarrow q'q\bar{q}$. The resulting CP asymmetry (denoted by a) is directly proportional to the total width of the W -boson, and the largest asymmetry is obtained for the process $t \rightarrow dc\bar{d}$ with $a \simeq 10^{-4}$ for $m_t = 120$ GeV. The rescattering effects of the final-state particles is also examined and is found to lead to CP violation in semi-leptonic decays of the top quark. Although the semi-leptonic CP asymmetry is numerically smaller, ($a \simeq 10^{-6}$ with $m_t = 120$ GeV for $t \rightarrow de^+\nu$), these final states have cleaner experimental signatures. This paper was presented, along with earlier results on rare decays of the top quark (published in Phys. Rev. **D44**, 1473 1991), at the conference *Particles and Fields '91* (ANL-HEP-CP-91-77).

Phenomenology of Supersymmetric Models with R-Parity Violation

J. Hewett has examined rare decays of the Z -boson in supersymmetric models with R-Parity Violation. R-parity is a multiplicative quantum number (the standard fields possess $R = +1$, while their super-partners have $R = -1$) that is conserved in the minimal supersymmetric standard model. Conservation of R-parity implies that (i) sparticles can only be produced in pairs and (ii) that the lightest supersymmetric particle is stable. However, the most general superpotential contains R-parity-violating interactions that violate lepton and baryon number (separately, so as to suppress rapid proton decay). These models result in a very different super-partner phenomenology, and the two conditions mentioned above no longer hold. In a recent paper (ANL-HEP-PR-91-110), Hewett discussed signatures of these models in Z -boson decays. The decay $Z \rightarrow \tilde{\nu}\gamma$ proceeds through a one-loop diagram with internal b-quarks via a $\tilde{\nu}b\bar{b}$ coupling. The branching fraction for this process was found to be similar to that for $Z \rightarrow H\gamma$ for the largest values of the R-violating couplings that are consistent with low-energy data. The sneutrino can then decay subsequently into b-quark pairs, yielding a $b\bar{b}\gamma$ final state, and

this process can mimic Higgs production for $M_{Higgs} \geq 60$ GeV. The three-body decays $Z \rightarrow \tilde{f}\tilde{f}'$ were also studied, and the rates were found to be small.

Desert GUTS and New Light Degrees of Freedom

Recently Amaldi, deBoer, and Fürstenau have shown that the predictions of Supersymmetric SU(5) are in agreement with current high-precision data from LEP and the lower bounds on the proton lifetime, provided that the mass scale for SUSY particles is not far above the usual electroweak scale. The predictions of ordinary SU(5) were, however, found to lie many standard deviations away from present data.

In a recent paper (ANL-HEP-PR-91-92) submitted for publication in Physical Review D, T. Rizzo addressed the question of the uniqueness of this SUSY solution, by investigating whether other additional light degrees of freedom could be introduced at the electroweak scale in such a way that one maintains (i) correct predictions for $\sin^2 \theta_w$ and $\alpha_s(M_z)$ and (ii) agreement under renormalization group analysis with present bounds on the proton lifetime. The problem here is to know what kinds of additional particles to add to the conventional standard-model spectrum so that the theory is anomaly free, in agreement with (i) and (ii), and consistent with restrictions from all other data.

In order to give as complete an analysis as possible, Rizzo allowed the new particles to transform under $SU(3)_C$ as either 1, 3, 6, or 8 and under $SU(2)_L$ as 1, 2, or 3 and gave them electric charges of 0, ± 1 , $2/3$, $-1/3$, $5/3$, $-4/3$, or 2. These new particles were considered to be either bosons or fermions that could exist singly or together with other representations. In all, over 43000 combinations of particles were considered in an extensive numerical search, and, of these, only 12 were found to satisfy all of the existing constraints. Thus, while SUSY does not provide a unique solution, it was found to be quite difficult to construct other viable solutions satisfying all of the present constraints. In all the scenarios that did pass the constraints, a rich spectrum of new, exotic particles appeared and was found to be accessible to existing and future collider experiments.

The Physics of New Gauge Bosons at Colliders

In workshop contributions (ANL-HEP-CP-92-85 and -91-96) to the *Physics and Experiments with Linear Collider Workshop* and the *15th Johns Hopkins Workshop on Current Problems in Particle Theory*, T. Rizzo discussed the physics issues associated with extensions of the standard model (SM) gauge group, i.e., the existence of new gauge bosons. Existing limits on such particles arise from two sources (i) direct searches by the CDF Collaboration at the Tevatron and (ii) indirect searches, which are strongly model dependent. Current indirect bounds include those obtained via radiative correction (RC)

analyses using high-precision data to look for small deviations from the predictions of the SM, and astrophysical/cosmological limits obtained by using data from SN1987A and the He^4 abundance. The bounds from RC analyses are presently somewhat better than those obtained from the direct-search results and are expected to improve substantially during the next few years as more high-precision LEP and Tevatron data is accumulated and existing atomic parity violation experiments are improved. During the same period, improvements in the Main Injector will result in increased luminosity at the Tevatron and will allow an increase by more than a factor of two in the mass reach of the direct searches for new gauge bosons. Unfortunately, even if such new particles are discovered in the Tevatron mass range, the relatively low statistics available will not allow us to learn much about their properties from the Tevatron data alone.

The advent of the SSC and LHC will open up a new era in the search for new gauge bosons, since, for most extended electroweak models, all of the mass range below ≈ 10 TeV will eventually be accessible. While the capabilities of hadron supercolliders to find such particles has been discussed for many years, only recently has serious work begun to evaluate the capability of detectors at such machines to identify new gauge bosons, i.e., to specify their models of origin. This is a particularly difficult problem at a hadron collider, as precious few of the properties of new gauge bosons are easily measurable in such an environment. The ongoing work of Hewett and Rizzo has shown, however, that planned detectors for the SSC (both SDC and GEM) can do a reasonable job of identifying new neutral gauge bosons, if they are indeed produced.

III. EXPERIMENTAL FACILITIES RESEARCH

A. Mechanical Support

1. SDC Design

During this reporting period, the major portion ($\approx 80\%$) of the mechanical support group's activities was concentrated on the design and finite element analysis of the SDC barrel and endcap calorimeters. This effort is described in detail in section V.B.4 of this report.

2. SDC Test Beam Prototypes

The two beam prototypes of the barrel electromagnetic calorimeter were cast, instrumented, and installed in the Fermilab MP Hall. The moving and positioning fixture for transporting the test modules in the horizontal and vertical directions were also designed, fabricated, and installed during this period.

The data accumulated during the test beam runs will be used for further refinement of the calorimeter mechanical design.

3. ZEUS

There was little activity pertaining to the ZEUS detector during this reporting period. The last three ZEUS modules were removed from the test beam at Fermilab Lab E and shipped to DESY, Hamburg. The installation of these last modules completed the barrel calorimeter mechanical installation. The actual roll-in and data run will commence early in calendar year 1992.

4. Soudan 2

During this period, a problem was discovered relating to the adhesive used to bond the bandolier mylar. Large amounts of methylene chloride were being released into the gas essentially killing the electron drift in the drift tubes. The reasons for this phenomenon are not understood since the adhesive system is the same as that used in previous module construction. To remedy this, it was necessary to design and build a forced-air heating system to accelerate the outgassing of the contaminant. New bandolier is also being baked prior to installation in the modules. Other problems associated with moisture content in the drift tubes had to be dealt with as a result of baking.

5. Argonne Wakefield Accelerator

During this period work continued on design of components and supports for the linac (gun and preaccelerator). Installation will commence in early 1992. The enclosures for the control room and laser room were designed and constructed, and work has begun on the installation of utilities for these enclosures.

(N. Hill)

B. Electronic Support

1. ZEUS Calorimeter Electronics

Our major effort during this period was the development of the first level calorimeter trigger processor (CFLTP). The ZEUS calorimeter first-level trigger processor presents summary data on energy deposition in the uranium/scintillator sampling calorimeter to the global first-level trigger (GFLT). The summary data includes global and regional sums of electromagnetic and hadronic energy deposition, the number of isolated muons and isolated electrons, missing transverse energy, jet cluster information, and the likelihood of beam-ga background. The CFLTP receives data from 16 regional trigger preprocessors which digitize the calorimeter signals and perform regional energy sums and logical operations. Design and construction of these regional preprocessors is the responsibility of our collaborators from the University of Wisconsin.

The CFLTP is a pipelined processor that contains data from eight crossing periods at any instant. It can capture input and output data from a sequence of up to 4096 consecutive beam crossings or first-level trigger events for detailed examination. All data variables are accessible for histogramming. The histograms can be computed and evaluated by a 68030 processor that resides in the VME bus, embedded within the CFLTP. Input or output data emulation capability is provided to operate the CFLTP at full speed in a stand-alone mode. In addition, the design includes a number of utility functions to inspect the data flow and to assist in troubleshooting.

During the period, seven input cards were manufactured as 12U 400 mm VME cards. This is a twelve-layer card designed entirely in surface mount technology. Production was completed on seven of the algorithm cards. These are extremely dense cards produced in a multiwire/surface mount technology. To implement all the algorithms set forth in the specifications requires 16 different algorithm cards. For the initial period, however, there will be only ten. The algorithms omitted relate to clustering, and will be implemented later. Perhaps the most challenging aspect of this work has been to produce these very dense cards, but to make only two of each.

Extensive effort has gone into designing and producing the diagnostic software which is essential to provide assurance that the trigger processor is functioning correctly. Overall, there are some 300 look-up tables implemented in the pipelined architecture of the trigger processor. Clearly the ability to diagnose problems in a system this vast is absolutely essential.

2. CDF Trigger Upgrade

During the period we have been working very hard on electronics for the CDF trigger upgrade. This is an effort to bring the preshower radiator (CPR) and shower max detector wires (CES) into the trigger at second level to improve the efficiency for B physics. We are responsible for the digital aspects of the work and our collaborators from The University of Chicago are responsible for the analog electronics.

The digital electronics to incorporate CES and CPR data in the CDF second level trigger is in Fastbus on two cards which are identical to avoid doubling the CAD expenses. Data and strobes from the CFT which come to the CTCX card are bussed to this module to provide the wire address, momentum, and strobes. This electronics is built on two cards, because it is extremely difficult to provide space for chips and connectors required for the 384 CES and 192 CPR bits with only one card. Our plan had been to build the cards using multi-wire technique with all devices implemented in surface mount. Since there is such a nice flow to the logic, we are trying currently to route the card and produce it in multilayer. It appears this will be successful, although the card with over 600 chips is quite dense.

In order to deal with the connector problem the CES and CPR bits are brought to an active patch panel near the digital electronics. The bits are carried as differential TTL and translated to single-ended TTL on this patch panel. They go from there on some short lengths of ribbon cable to the digital electronics. High density connectors are used to bring the single-ended bits from the active patch panel to the digital module. The CES electronics is built on one card and the CPR electronics on the other. All memories and registers can be written/read from Fastbus, and for diagnostic purposes it is possible to set bit patterns of the CES and CPR hits. This is accomplished by permitting all the input latches to be set, and then the mask words are used to create the bit patterns which can be run through memory, and the output data tested.

3. MHD Test Program Support

This is an ongoing program to investigate MHD propulsion of vessels in ocean water. The program utilizes the large 6T superconduction magnet which was built originally for the University of Tennessee MHD energy conversion program. We have designed and built all the data acquisition hardware and have written the on-line software for data acquisition.

4. Soudan 2 Electronics

Work continued to support the Soudan 2 nucleon decay experiment. Our involvement has become primarily one of construction and maintenance.

5. Construction, Maintenance, and Procurement Summary

SOUDAN

Veto Shield Shutoff Cards - Produced 8
 Front/Back Splitters - Produced 120
 High Voltage Feeders - Produced 30
 Anode High Voltage Distribution - Produced 4 - Upgraded 3
 Preamps - On order 134
 Calibration Modules - On order 30
 Existing Electronics - Maintained as necessary

ZEUS

Backplane - Produced 2
 Communication Card - On order 2
 Simple Comm Card - Produced 2
 Input Card - On order 7
 Algorithm Card 1A - Produced 2
 Algorithm Card 1B - Produced 2
 Algorithm Card 2 - Produced 2
 Algorithm Card 3A - Produced 2
 Algorithm Card 3B - Produced 2
 Algorithm Card 4 - Produced 2
 Algorithm Card 5A - In design
 Algorithm Card 5B - In design
 Algorithm Card 7 - In design
 48/96 VME Multiplexer - In Production 18

CDF

CES/CPR Trigger - In design
 Active Patch Panel - In design

MHD TEST FACILITY

Shunt Rack - Produced 1
 Electrode Tap Interface Box - Produced 1

Physics Division

Built Prototype APEX Trigger Module

(J.Dawson)

C. Computer Support

During the past year a significant upgrade to the the HEP computing resources has been implemented by the design, acquisition and installation of a Unix-based workstation network. This is a centrally managed group of Silicon Graphics based servers and workstations. The two server systems are based on SGI 4D/35S and include 2 8mm tape drives and 5 Gbytes of disk available as a shared resource to the other workstation via NFS and RPC on a tcp/ip ethernet. Four workstations (three 4D/25 and one 4D/35) were acquired for HEP personnel working on SDC and CDF. This Unix cluster provides an aggregate increase of 5 times the computing available in the HEP VAX/VMS cluster. The planning and acquisition of two new low cost 4D/rpc workstation is in progress. The computing group has also taken on the management of the two electronics group workstations, and has provided advice and help on the integration of individual workstations for the ZEUS, PPT and Accelerator groups. The number of 30x86 based PC using Pathworks networks in the Accelerator and Engineering groups has grown, and the computer group provides continuing help, maintenance and network integration. An AppleTalk network of Apple Macintosh workstations and laser printer for the division management was installed during the past year. In addition to the continuing general maintenance of the HEP VAX/VMS cluster, the following software systems were added to the cluster:

- Mathematica
- C compiler
- TeX
- Upgrades to the CERN Library

Support for design and implementation of software for the ZEUS data acquisition system was provided. A VAXstation 3100 from the HEP cluster was loaned to Fermilab for one year to support the SDC detector test beam work.

(E. May)

IV. ACCELERATOR RESEARCH AND DEVELOPMENT

A. Advanced Accelerator Test Facility (AATF) Program

1. SLAC NLC Cavity Measurements

The focus of the AATF effort in this period involved engineering tests related to the upcoming measurements of full-sized prototype NLC structures. In order to perform these experiments, it will be necessary to measure wakes out to delays of 3 ns (near the maximum extension of the trombone) through a 1 m long structure, whereas typical measurements to date have been performed out to delays of 1 ns in 50 cm test devices.

The low energy line was manually retuned at approximately 500 ps delay intervals, and the tune parameters stored on disk. The online control program was modified to read in these tune parameters and interpolate between them in the course of data taking. Tuning through the longer test section posed no serious difficulties. Figure 23 shows the results of a full 3 ns scan, using the damped structure described in the next section as a test device.

We expect to perform the next round of NLC structure measurements in the spring of 1992, pending completion of the prototype device construction at SLAC.

2. Damped Structures

Experiments are continuing on damped accelerator structures. Damped structures propagate unaltered the desirable azimuthally symmetric accelerating waveguide modes while damping the harmfully deflecting non-axisymmetric modes spawned as wakes of misaligned beams. The latest tests are being performed on conventional iris-loaded accelerator structures for application not only in future high-gradient linear colliders, but also for circular machines such as the SSC or B-factories.

Deflection-mode damping is achieved by slotting the irises radially and inserting disks of a ferrite loaded absorbing material. The degree of deflection-mode damping resulting from this technique has been found to be sensitive to the waveguide mode group velocity. Thus tests are being performed on low group velocity structures with damping times on the order of several nanoseconds as opposed to the much faster (~ 100 ps) damping times achieved in the past with high group velocity dielectric-lined waveguide.

Some preliminary measurements were made at the AATF during the course of the long-delay engineering runs. The data appear to show some damping of the transverse wakes but are not conclusive due in part to beam stability problems. Further experiments are planned.

Fig.23. AATF long-delay measurement of the longitudinal wake in a test structure. No baseline subtraction or other corrections have been applied to the data.

3. Conductive Dielectric Structures

Practical dielectric wakefield structures will require some mechanism for ameliorating charging effects caused by beam halo. Use of a dielectric with a very small ohmic conductivity is one possible solution. A dielectric structure was fabricated from borosilicate glass which exhibits a slight conductivity when heated. Initial results were very promising. No charging effects were observed, even with cold glass. The expected wakes were present, however.

B. Progress on the Argonne Wakefield Accelerator (AWA)

1. Conventional Facilities

The installation of basic services at the AWA was completed. Electric power and lighting were installed in the accelerator vault, laser room, and control room. Air conditioning was provided in the laser and control rooms and cooling water supplied for the laser system. The control console was moved into place, and a support table for laser electronics was constructed.

The laser safety interlock system and associated warning displays were installed. Smoke detectors were placed in the control and laser rooms. The laser room and gas cabinet ventilation systems were made operational.

The upstream labyrinth on the accelerator vault was reconfigured to provide better accessibility and to further reduce potential radiation leakage. The hole through the shield wall for laser beam transport to the gun was bored.

2. Laser System

The laser table was designed and installed upon the completion of the laser room. The laser system will ultimately be capable of producing 2 ps 5 mJ pulses at 248 nm. The installation of the laser system began in November.

The laser consists two major sub-systems, a Coherent ultra-short pulse generator and a Lambda Physik amplifier. The commissioning of the first part of the system is complete. Mode locked pulses at the design specifications (80 Mhz rep rate, 150 mW, 1.7 ps at 496 nm) were produced. All individual parts of the amplification system have been tested and the integration of the whole system will be completed in the first half of 1992.

3. Gun Cavity High Power Test

The AWA photocathode gun cavity was tested under high power using 1.3 GHz rf available at the building 211 Chemistry linac. The cavity conditioning process to achieve high electric fields for electron acceleration was initiated by applying increasingly higher

levels of rf power to the cavity while monitoring dark current and input waveguide forward and reflected rf signals.

This time consuming process was carried out to the rf input power level of 1.1 MW, which corresponds to an accelerating electric field on the photocathode electron emitter surface of 80 MV/m. At this point, high dark current out of the cavity and intermittent rf breakdown required long periods of steady operation to allow these effects to dwindle.

Although the field strength attained on the photocathode is sufficient for initial beam studies, further long-term conditioning will be required to achieve the design accelerating electric field of 92 MV/m (corresponding to an input power of 1.8 MW). This may be postponed until the AWA dedicated high-power rf source is delivered in June 1992. In the interim, the photocathode cavity will be removed from the building 211 rf circuit, inspected, cleaned, and reassembled in the building 366 AWA vault.

4. Data Acquisition

The benchmarking of workstations for use as the initial control and data acquisition machine at the AWA was completed, with the HP/Apollo 750 emerging as the computer of choice. An acquisition plan was prepared and the order for the machine submitted.

C. Accelerator Physics

Measurement of very small (few nm), high power beams, of the sort that might be produced by the next generation of linear colliders, is difficult. A system using bremsstrahlung radiation nonimaging optics has been developed and proposed to DOE for use on the SLAC Final Focus Test Beam. The particular system being considered is expected to have a resolution on the order of 20-30 nm. This is not close to the ultimate limits of the method, which might be in the range 1.5 - 4 nm, because of compatibility problems with beam line elements downstream of the final spot. Nevertheless, the method should be adequate for the 60 nm spot size proposed for this line, and useful for measurements of the phase space density, beam focusing in foils and plasmas, and beam line performance and stability.

(J.Simpson/P.Schoessow)

V. SSC DETECTOR RESEARCH AND DEVELOPMENT

A. Overview of ANL SSC Related R&D Programs

Argonne's work on the SSC physics program is strongly concentrated on R&D and on design work for the Solenoidal Detector Collaboration (SDC), one of the two major detectors expected to be built for the initial physics program at the Supercollider. About 20 physicists and engineers from ANL are members of the SDC, taking several leadership roles in both management and technical aspects of the collaboration. Management work includes membership by Argonne staff on all major governing boards of the collaboration and on several ad hoc technical review committees charged with recommending technology choices to the Technical Manager and Executive Board.

Technical work has been focused on R&D and design of central calorimetry and of offline computing for SDC. The focus of the collaboration and of Argonne's work during the second half of 1991 has been on the preparation of the Technical Design Report, due to SSC Laboratory on April 1, 1992. In addition to preparing clear descriptions of our plans and designs, preparation of the report has involved finalizing requirements and developing conceptual designs as far as practical by the due date. The extensive work done on calorimetry, both in design and in beam testing, is described below.

Argonne physicists and engineers have participated centrally in many aspects of defining the detector and preparing the Technical Proposal/Design Report (TDR), due at the Laboratory on April 1, 1992. In particular, we note the major contributions:

- Calorimeter Working Group co-chair from Argonne. The working group identified requirements and specifications for SDC calorimetry and organized reviews of calorimetry culminating in the selection of Calorimeter technology in September, 1991. The working group has prepared the calorimeter section of the TDR.
- Calorimeter review committee. Two Argonne physicists sat on this committee which reviewed calorimeter technology choices from the standpoints of physics requirements, performance, and cost, and presented evaluations to the Technical Board.
- Computing Working Group co-chair from Argonne. The working group has prepared requirements and specifications for SDC computing and written the Computing chapters of the TDR.
- Calorimeter cost studies, working with industrial partners.

In the computing area, Argonne has provided leadership of the SDC Computing Working group as it has prepared requirements and a conceptual design of the SDC offline computing system. Argonne physicists also forged a collaboration of physicists and

computer scientists to carry out R&D on the single toughest computing problem facing experiments at the SSC: efficient means of storing and accessing data estimated at 2×10^{15} bytes (2 Petabytes) per year of both raw and reconstructed data. Funding for the computer science portion of this collaboration were provided in FY 1991 and early FY 1992 as an early start High Performance Computing and Communication Initiative project through the DOE/Energy Research office of the Scientific Computing Staff.

Meeting at SDC collaboration meetings and in several special workshops, the SDC computing group has defined requirements and provided a conceptual design for a computing system that will meet the requirements. In particular, Argonne physicists have taken responsibility for sections of the TDR on hardware design, networking, and cost and schedule projections. (L. Price)

B. Compensating Scintillator Plate Calorimeter R&D

1. Program Overview

The compensating scintillator plate calorimeter R&D program successfully accomplished many objectives during this period. Both test calorimeter modules were cast, instrumented with tile-fiber assemblies, and tested in a high energy beam at Fermilab. The complexity of the fiber installation and routing involved in this assembly can be seen in Fig. 24, which shows Module 1 prior to installation of the cover plates and mounting of the phototubes. Due to tile production difficulties, only a partial complement of towers were instrumented in the first module. However, all ten towers of the second module were instrumented. Beam data, showing that the calorimeter performance met the SDC specification, were successfully obtained in time for the SDC technology decision in September of 1991. Following installation of the combined pair of modules in the MP testbeam in November, our full testbeam program was accomplished prior to the termination of the Fermilab fixed target program. This included data on hermeticity in the region of the stainless steel bulkheads within the module and in the gap between modules. Preliminary data were presented to the SDC in early December, and the collaboration has decided to adopt this design of electromagnetic calorimeter as its baseline design for the technical proposal to be submitted to the SSC Laboratory in April 1992. However, our simulation program has demonstrated that with the reduced scope of the hadron calorimeter, compelled by cost, the use of iron absorber would be wholly adequate and therefore the development of a hadron calorimeter based on cast lead absorber plates was dropped in the latter part of the year.

The basic R&D elements of this program are now complete. The engineering and additional development associated with the design and construction of the EM calorimeter

modules are now being carried out under the oversight of the SDC management. Further details are given below on the technical program completed in this reporting period (optical system fabrication, simulation, engineering design and finite element analysis and testbeam evaluation of the test calorimeters). (J. Proudfoot)

2. Optics for the SDC Scintillator Plate Calorimeter

During this time our main activity was the assembly and testing of about 450 tile-fiber units for the two cast lead calorimeters used in the test beam. Much experience was gained in dealing with different materials and performing quality control.

Tiles for the first three towers were completed and the calorimeter was put into the beam in August. Construction, testing, and installation went relatively smoothly. The tiles were fabricated from a co-polymer material from Bicon. Each of the 87 tiles was a different size. BCF-91 wavelength shifter (WLS) fiber, 1 mm in diameter, was used. Each WLS fiber was a different length to match the tile size, typically 55 cm. The clear fiber was obtained from Kuraray, with a diameter of 1 mm and an attenuation length of about 6 meters. As described in the previous report, the tiles in the first calorimeter were laser cut and then annealed to prevent crazing. Some difficulty was experienced in laser cutting so that the tiles were produced with a slightly rounded edge and a slight ridge on top. The tile-fiber assemblies were wrapped tightly in thin aluminized mylar and the fibers routed on top of each tile within the slot in the cast lead. It was found that by a simple masking of the WLS fiber to prevent double counting near where both ends exited the tile, a uniform response (better than 3% over most of the tile) could be obtained with no masking of the tile. No glue was used to hold the fibers in the grooves in the tile, only two very small pieces of tape and the aluminized mylar wrapping. The 2.4 meter clear fibers were welded to the WLS fibers before assembly into the tiles. Thin steel tubing ferrules were glued onto the splices to relieve mechanical stress. An example of a tile fiber assembly prior to wrapping is shown in Fig. 25. These tiles performed well, with an average light output of about 3.6 photoelectrons at the R580 tube with an rms spread of about 7%. This is shown in the first three points in Fig. 26. We recall that a test with a Philips 2081 green extended tube gave no improvement in performance even though it was in principle better matched to the green from the K27 shifter. Perhaps bad photocathode efficiency cancelled what should have been a factor of two better matching.

Considerable production difficulties were experienced with the remaining two towers of tiles installed in the first calorimeter. A typical spread in the response before some problems were corrected was 2.6 to 4.4 photo-electrons, i.e. $\pm 26\%$. Three major

factors were found to contribute. First, we had received a new spool of wave shifter fiber during the production and it was not known that it was BCF-91A instead of BCF-91. The new fiber gave ~ 20% less light output. There was no labeling of each of our fiber assemblies to indicate the fiber batch from the factory. (Other differences between the two kinds of fiber are described later). Second, the procedure for gluing the steel ferrules over the fiber splice developed for construction of the previous three towers was not transmitted to the summer students available to do the gluing on the later assemblies. It is necessary to glue the ferrule well to both the shifter and clear fibers. (The ten-day half life of optical transmission in stressed joints was described in our previous report.) Thirdly, some of the tiles had 28% less intrinsic light output than the average. On close inspection, these had a wavy internal appearance. They were sliced and polished and the wavy appearance persisted in the bulk material. It is not known whether this is due to inadequate mixing of the co-polymer or damage from the annealing by the laser cutter. We eventually replaced the BCF-91A fibers in the two utilized towers with the remaining BCF-91 fibers from what was to have been a third tower. The rms spread for these three towers was about 13% to 14%, as shown in the second three points in Fig. 26.

For the second cast lead module, 290 tiles plus spares and test pieces were made for 10 towers. The materials used were different from the first calorimeter. The scintillator was polystyrene instead of co-polymer and gave less light output. The tiles were machined at Florida State, and no polishing was done. BCF-91A waveshifter was used. Also, an improved version of Bicon clear fiber was used which had an attenuation length about the same as the Kuraray fiber. The net light output was about 1.8 photoelectrons instead of 3.6, but the tradeoff was in improved tile-to-tile uniformity and ease of construction. Most of the towers had rms spreads of 5% to 6.5% over the 29 tiles per tower. Larger spreads resulted in cases where a few tile assemblies appeared to have bad fibers which were discovered too late for replacement. In general, an effort was made to insure that tiles near shower maximum got good fibers while the poor fibers were juggled to the backs of the towers. Again, each tower had 29 different sizes of tile, and each of the five η positions was different, so there were 145 different tile sizes. The response data for the second module are summarized in the right half of Fig. 26.

Some tests of fiber properties were made which suggest that more investigation is needed. One spool of BCF-91A was made up of three lots. The response of the individual lots to scintillator light was the same within about 2% (on the order of the measurement error), but other tests were less encouraging. In one test, the center of 1 meter of BCF-91A was wound about 3 turns in circle of 5 cm diameter. Transmission tests in both red and green light showed only half the light transmission while part of the fiber was coiled in

a 5 cm circle compared to the transmission with the fiber in a 30 cm circle. After the fiber had been coiled in a 5 cm circle and straightened, the transmission largely recovered within 1/2 hour. Similar tests on BCF-91 before design of the calorimeter had shown such effects only at much smaller radii, even after irradiation by Co^{60} . Thus, we believe that most of the loss is related to fiber properties and not just due to loss of cladding carried light. In another test, a piece of BCF-91A was wound around a 5 cm paper cup and exposed to room lights from July 9 to October 9. The output, when tested with a scintillator, had fallen to 0–1 adc count from the 165 adc counts measured in July. We have other cases of fiber becoming less effective after being exposed to room light for a month, but these are less well documented. Another problem, reported by the person at Fermilab who did most of the fiber splicing, was that the 91A was very different from the 91 in that more applied pressure was required to obtain a proper splice.

In the course of preparing tiles for a beam dump irradiation test, we discovered that the scintillator light is coupled to the shifter fiber much more effectively if the fiber is on the edge of the 2.5 mm thick tile rather than in a groove in the surface. The aluminized mylar wrapping may function as an almost parabolic focuser onto the fiber. This geometry had been tried previously but with glue providing inferior light transmission on both the fiber-tile interface and on the aluminized surface. No glue is used in this more effective coupling scheme. The increase was from about 100 adc counts to about 188 counts in this new geometry.

A simple test was made which might be useful for calibration. A blue (silicon carbide) light emitting diode was embedded in a tile. The excitation of the waveshifter fiber is similar to that from scintillator light and may have a similar dependence on the transmission of blue light in a radiation damaged tile. The chips for such LED's could possibly be cast into the tiles during manufacture. We hope to do an irradiation test to determine the utility of this calibration scheme in the future.

(D. Underwood)

3. Simulation Studies for Calorimeter Design

Development of the simulation tools for calorimeter design and the optimization studies for a scintillating plate calorimeter for SDC were the major activities of this reporting period. CALOR89 simulation results were earlier compared with four experimental test beam configurations (NIM A309, 60 (1991) and the input parameters were optimized. We then used these optimized parameters to estimate the performance of the suggested configurations for SDC.

Six configurations, with one electromagnetic and two hadronic sections, were simulated to explore the feasibility of a lead-iron based three segment calorimeter (ANL-HEP-PR-91-83). Table 1 summarizes the six configurations that have been examined with CALOR. The first section is a fine sampling electromagnetic calorimeter consisting of lead scintillator cells. The composition and thickness of the passive material for the second segment are varied. Iron and lead with different sampling thicknesses are used in this section. The third segment is iron in all the configurations, with the sampling thickness being varied. In all the configurations the thickness of the scintillator is 0.25 cm. The total longitudinal dimension of the three segments together is approximately 10λ of the absorber material. The signal from each segment is weighted appropriately using the (dE/dX) weighting scheme and summed up for each event. The e/π ratio, electromagnetic and hadronic resolutions are estimated as a function of energy. The range of incident energy scanned in this study was 10 to 250 GeV.

The results are given in Figs. 27 and 28. These results show that the e/π ratio and the hadronic resolution depend upon both composition and thickness of the passive material of the second segment. When either the thickness of the lead is increased in the second segment (configuration 2), or the lead is replaced with iron (configuration 3, 4 and 6), the resolution worsens, both in terms of the coefficient of the energy dependent term and the constant term. Doubling the iron thickness in the third segment (configuration 1 and 5) did not significantly worsen the resolution or the constant term. Configurations 1 and 5 are nearly as good from the point of view of the SDC design specification of $50\% \sqrt{E}$ resolution with the constant term $\leq 2\%$.

In order to decide the question of Pb/Fe absorber for the hadron calorimeter of SDC last November, two hanging file configurations were simulated using CALOR89 along with several variations of these configurations. These consisted of an electromagnetic section of Pb/scintillator of 0.32/0.30 cm, and a hadronic section of 2.54 cm of Pb or Fe with 0.30 cm of scintillator. One of the important issues in these multiabsorber-multisegment calorimeters is the matching of signals from electromagnetic and hadronic sections such that the hadronic resolution will be a minimum. Weight factors other than dE/dX are used in the simulation so that the hadron resolution can be minimised. It has been observed that while the dE/dX weight factor is a good choice for lead absorber, the weight factor differs considerably from dE/dX for iron to have the minimum hadronic resolution. For easy comparison with the experiment, the weight factors optimized by the hanging file measurements at FNAL have been used to calculate the hadronic resolution (Fig. 29). A preliminary comparison with hanging file measurements show that while simulation agreed well with the Pb configuration in the hadronic section, there is

Fig. 27. Hadronic resolution as a function of inverse square root of energy (GeV) for the three segment lead-iron configurations. The curves are chi-square fits to the data points.

Fig. 26. Average response over all tiles in a tower from Ruthenium source measurements. The error bar represents the rms spread in the measurements.

Fig. 29. Hadronic resolution as a function of inverse square root of energy (GeV) for the two hanging file experimental configurations.

Fig. 28. e/π ratios as a function of energy for the three segment lead-iron configurations.

considerable disagreement ($\sim 20\%$) with the measurement with Fe in the hadronic section. The measurements show slightly better resolution for Fe than Pb hadronic calorimeters while simulation shows the converse. Several other hanging file configurations are being analyzed to resolve this discrepancy.

Table 1
Three-Segment Calorimeter Configurations Simulated by CALOR

	<i>EMC</i>	<i>HAD I</i>	<i>HAD II</i>
Conf. 1	Pb/SCIN	Pb/SCIN	Fe/SCIN
Thickness (cm)	0.55/0.25	1.55/0.25	3.55/0.25
Unit Cells	20	34	27
Conf. 2	Pb/SCIN	Pb/SCIN	Fe/SCIN
Thickness (cm)	0.55/0.25	3.55/0.25	7.55/0.25
Unit Cells	20	15	13
Conf. 3	Pb/SCIN	Fe/SCIN	Fe/SCIN
Thickness (cm)	0.55/0.25	3.55/0.25	3.55/0.25
Unit Cells	20	15	27
Conf. 4	Pb/SCIN	Pb/SCIN	Fe/SCIN
Thickness (cm)	0.55/0.25	3.55/0.25	7.55/0.25
Unit Cells	20	15	13
Conf. 5	Pb/SCIN	Fe/SCIN	Fe/SCIN
Thickness (cm)	0.55/0.25	1.55/0.25	7.55/0.25
Unit Cells	20	34	13
Conf. 6 ^(a)	Pb/SCIN	Fe/SCIN	Fe/SCIN
Thickness (cm)	0.32/0.25	2.54/0.25	5.08/0.25
Unit Cells	35	31	12

(a) 10 cm Al plate in front of EMC and 2.5 cm Al plate between EMC and HAD I.

(P. K. Job and L. Price)

4. Mechanical Design and Testing for the SDC Central Calorimeter

a) Barrel Calorimeter Design

Within the SDC collaboration a serious effort was made to achieve a consensus, which resulted in convergence in many areas of the design. A decision was made, based on simulation results, to construct the HAD1 section of the barrel and end cap from steel plate instead of lead. This required a restructuring of the mechanical layouts to accommodate this change. There was also agreement, late in the actual reporting period, to use an axisymmetric design for the 64ϕ wedges that will yield 32 actual ϕ wedges. This design will be incorporated into the cast lead barrel EM segments.

A first try at routing optical fibers and placement of photomultiplier tubes was also incorporated into the barrel design. Figure 30 illustrates a worst case mapping of the

Tile/Fiber Model-B Calorimeter

Fig. 30. Phototube layout at outer radius of the barrel calorimeter.

phototube layout at the outer radius of the barrel calorimeter. The routing of fibers to terminate at these locations is illustrated in Fig. 31. Changes in absorber plate thicknesses resulted in many iterated mechanical layouts to achieve a coherent design. The details of the current layouts incorporating these changes are illustrated in Figs. 32 and 33.

b) Barrel Calorimeter Finite Element Analysis

The finite element analysis was done using the design shown in Fig. 32. The recent design change, from lead to steel absorber in the HAD1 sections, is not reflected in the analysis presented here. The primary changes from a mechanical standpoint are a reduction in overall weight and an increase in the stiffness of the system. The reanalysis of the barrel calorimeter configuration with the steel absorber is in progress.

A simplified numerical model was used for module simulation. The structural frame, consisting of the inner and outer plates, the end plates, and the connecting bulkhead membranes was modeled in detail. The lead absorber plates, due to the complexity of modeling laminate structures, were represented as solids with the stiffness and density adjusted to reproduce the properties of the lead plate construction. The composite stiffness used to model the lead structure was determined by using the ratio of load carrying area to the total area and using this ratio to modify the stiffness of solid lead. The densities are modeled by using the ratio of total volume to occupied volume.

To connect the wedge model into the assembly, the interface boundaries between modules were separated by .030" and attached at discreet points along those boundaries, located as shown in Fig. 34. These points were deliberately chosen to represent actual boundary load transfer points. The difference between modeled and actual nodes was in total number. The design will increase the number of load transfer points in most cases by a factor of five. The finite element model of the final assembled quarter barrel is depicted in Fig. 35.

The EM, HAD1 and HAD2 sections are layered structures that have been approximated by solid elements. Since the stiffness of these sections is unknown, certain assumptions were made. The HAD2 section is a welded structure with alternating cells, so it was assumed that the modulus of steel, 60×10^6 psi, would be a good approximation to the HAD2 stiffness. The HAD1 and EM sections, however, are composed of layers of lead connected together with thin (.020 in.) bulkheads. The stiffness of these structures is unknown, so upper and lower limiting cases were established. The upper limit of the stiffness of these sections is the modulus of solid lead. The lower limit was found by taking the ratio of the load carrying area to the area of a cell (the bulkhead area) and multiplying it by the modulus of lead. Separate cases of the analysis were run using these

Fig. 31. Fiber routing scheme for the barrel calorimeter.

Barrel Calorimeter

Fig. 32. Cross section of half the barrel calorimeter.

Endcap Calorimeter

Fig. 33. Cross section of the end cap calorimeter.

Fig. 34. Wedge module connecting points.

Fig. 35. Finite element model of the quarter barrel calorimeter assembly.

upper and lower limits of the EM and HAD1 stiffness. This method does not allow exact values of the connecting forces to be calculated, but rather an upper bound on the forces. The final design will reflect the case in which the forces are largest.

Four different cases were run using a combination of the limiting case stiffnesses for the EM and HAD1 sections and different size connecting rods between the modules as summarized in Table 2. The use of different size rods permitted the study of the effect of size on the connections.

Table 2. Case Numbers for Connection and Stiffness Variations.

Case #	EM Stiffness σ/ϵ (psi)	HAD1 Stiffness σ/ϵ (psi)	Rod Diameter (inch)
1 (Lead Modulus)	2×10^6	2×10^6	1/4
2 (Modified Modulus)	24×10^3	35×10^3	1/4
3 (Lead Modulus)	2×10^6	2×10^6	1
4 (Modified Modulus)	24×10^3	35×10^3	1

The connecting forces calculated for the barrel are distributed along the length of the boundary plates. For example, if a maximum normal connecting force of 400,000 lb is found along the EM-HAD1 boundary, and this boundary has 29 bearing points at which the modules are connected, each point with a cross sectional area of 1 in², then each point carries a load of ~ 14,000 lb and has a stress of 14,000 psi. The forces, normal to the interface surfaces and the radial and axial shear loads are shown in Figs. 36 through 38.

When the lead in the HAD1 section is replaced with steel the forces will be reduced by the decrease in weight, and the individual connecting forces will change due to the increased stiffness.

c) Endcap Calorimeter Design

The baseline parameters were set for the end cap calorimeter during this reporting period. The end caps will be constructed of independent wedges, each a 1/32 section of the 360° end cap. The electromagnetic portion also consists of 32 sections but will be independently removable from the front end. The high radiation area of the hadronic section, in the η range of 2.0 - 3.0, will be a monolithic removable plug. An isometric projection of an end cap wedge is shown in Fig. 39.

INTER-MODULE NORMAL FORCE

Fig. 36. Barrel calorimeter forces normal to the surface as a function of module position.

RADIAL SHEAR FORCE

Fig. 37. Barrel calorimeter radial shear force as a function of module position.

Fig. 39. Isometric projection of a single endcap wedge.

Fig. 38. Barrel calorimeter beam direction (longitudinal) shear forces as a function of module position.

d) Endcap Calorimeter Finite Element Analysis

The endcap was modeled in a manner similar to the barrel. The EM front plate, the EM-HAD1 boundary plate, HAD1-HAD2 boundary plate and the back iron structure were modeled first using plate elements with the appropriate thicknesses to form the basic frame shown in Fig. 40. The individual modules were connected to each other at 22 points, 8 along the EM-HAD1 boundary, 6 along the HAD1-HAD2 boundary and 8 along the back iron. The EM section once again is composed of layers of lead plates separated by thin bulkheads. This presents the same problem of modeling as it did in the barrel, namely how to model the stiffness of these structures appropriately. Instead of modeling the EM and HAD1 structures using solid elements and then varying the stiffnesses of this solid to approximate the stiffness of the structures, individual plates of lead were used. The EM section has 12 lead plates, each 10.5 mm thick, separated by bulkheads. These were approximated by 4 plates which were 1.24" thick and separated by 7 bulkheads. This method approximates the stiffness of the EM structure but is not so detailed that the problem becomes too large to run. Similarly the HAD1 section has 28 steel plates, each 20.5 mm thick which were approximated by 5 plates, each 4.5" thick and separated by 9 bulkheads. The stiffness of lead, 2×10^6 psi, was used for all of these plates. The HAD2 section was approximated by solid elements and the stiffness of steel, 30×10^6 psi, was used. HAD2 is a welded structure with very few cells and therefore it is expected to behave as if it were a solid structure. Figure 41 shows the module wedge and the position of the connecting points. This module was then copied and rotated to form a half endcap as shown in Fig. 42. Advantage was taken of symmetry so that only half of the endcap was modeled. This reduced the size of the problem and the required computation time considerably. The bottom 4 modules were fully supported along the entire length of the outside diameter of the structural iron.

The results of this analysis produced similar results to those obtained for the barrel. A summary of the maximum forces expected at any interface boundary are represented in Table 3.

Fig. 40. Endcap wedge module rough frame model.

Fig. 41. Endcap wedge connecting points.

Table 3. Interface boundary maximum forces.

Boundary	Max. Normal Force	Max. Radial Shear	Max. Long. Shear
EM/HAD 1	+0 (tension) -17,000 lbs. (compr)	-3,000 (inward) +7,000 (outward)	-2000 +2000
HAD1/HAD2	+0 -30,000	-10,000 +12,000	+2,000 +2,000
Outer Row	+2,000 -35,000	-15,000 +15,000	+12,000 +2,000

e) Lead Creep Tests

To help supplement the sketchy knowledge available on the creep characteristics of lead, a series of mechanical creep tests have been conducted at Argonne on a number of lead samples. These measurements will provide information on the behavior of lead under loading in the SDC detector.

The first series of tests were performed with 1/8" lead sheets cut to 1" wide by 6" long. Weights were hung off the bottom of these strips to create a constant stress loadings of 40, 50, 60, and 80 psi. The weighted strips were hung in an oven at 327°K (129°F) for 1961 hours. This effectively simulated the creep that would occur in 211,000 hours (approximately 24 years) at 80°F (the assumed mean operating temperature of the calorimeter).

The results show that under a maximum load of 80 psi, a lead sheet would creep at about the rate of 1.18×10^{-8} in/in/hour (.0001 in/in/year) (Fig. 43). Another battery of creep tests are currently being conducted on samples of a calcium-lead alloy, which is much stronger than regular lead. (N. Hill)

4. Test Beam Program

a) Overview of Test Beam Installation

The performance of two EM test calorimeters was measured using high energy electron and pion beams in the MP9 area at Fermilab. This area was also the location used by the polarized beam group at Argonne, during earlier running periods, and much of the beamline instrumentation and expertise was provided by this group. In particular this included the beam tagging and triggering system, the operation of which was essential to the success of this test effort. We acknowledge here the great efforts of this group in supporting our own endeavor.

A schematic of the MP9 beam transport is shown in Fig 44. The beam momentum tagging is obtained from the hodoscopes. The two threshold Cherenkov counters provide

Fig. 42. Finite element model of one half endcap assembly.

Fig. 43. Lead creep results after 1961 hours (equivalent to 24 years at the detector's operating temperature).

electron-pion tagging for momenta less than about 200 GeV. A key issue is the resolution and spread of the tagged beam as one of our goals is to determine the constant term in the resolution of the calorimeter and how this constant term is related to the rms spread in the response in a tower and the distribution of this variation. A study was done several years ago which indicated that the initial momentum selection in the parasitic mode of beam running which we used was about 0.4%. Unfortunately, the beam traverses material which can broaden this by bremsstrahlung. We have a momentum measurement system after some of this material. A Monte-Carlo study was done to determine the effects of multiple scattering in the measurement system on the quality of the measurement. The results are shown in Fig. 45. Unfortunately, it appears that the momentum spread in the beam is dominated at high energy (100 GeV) by bremsstrahlung from materials in the Cherenkov counter, gas and mirrors, and the 20 meters of air and plastic hodoscopes in front of the calorimeter. This additional spread has not yet been calculated.

In early November, the Fermilab operation group informed us that it would be possible for us to operate the beam line up to 200 GeV. As a result we implemented a plan to improve the beam tagging by addition of wire chambers. These chambers were installed and read out successfully only in the last days of the run and as yet we do not know if we were successful in improving the beam momentum measurement.

b) Test Program

Module 1 was installed and first read out in the MP9 area in July 1991. From then until the completion of the Fermilab fixed target program, beam time was shared both with other groups within the T841P collaboration (studying pre-shower and shower maximum detectors, and hadron calorimetry) and with other testbeam efforts in the experimental area. In total, T841P accumulated approximately 1000 hours of scheduled beamtime. Although primarily concerned with testing the calorimeters, the Argonne group contributed to all of the above elements of the program and provided much of the technical leadership of the enterprise. The objective of the Argonne group was to demonstrate the uniformity, hermiticity and linearity of our test electromagnetic calorimeter. Data were taken on the following aspects of this design (for reference a layout of the front face of the calorimeter is shown in Fig. 46):

- Tower center response to 35 GeV electrons, for all instrumented towers in the calorimeter.
- Response and energy resolution for electron energies between 10 and 150 GeV, in several towers.

Fig. 44. Fermilab MP line beam transport.

Fig. 45. Monte Carlo calculation of multiple scattering limit on the momentum determination from material in the beam tagging system.

- A horizontal scan across the center of all towers, with emphasis on evaluating uniformity of response and resolution across bulkheads between towers (Scan A).
- A vertical scan across the center of towers 1, 2 and 3 to study both tile uniformity and the azimuthal gap between modules, through which the readout fibers run (Scan B1, 2, 3).
- A horizontal scan along the azimuthal gap between module at angles of inclination -3,-2, 0, 2, 3, 4 degrees with respect to the incident beam. This included one tower whose calorimeter readout was segmented into depths, which therefore provides additional information on the location of the particle shower. The scans at 0 and 3 degrees were repeated with 1 mm of lead sheet placed between the two modules.
- A full face scan of one tower to determine overall uniformity and to search for "hotspots" associated with the readout fibers.
- A measurement of the energy resolution in one tower in which a 2.6 attenuating neutral density filter had been placed between the readout fibers and the phototube. This allows an estimation of the light output of the tower.
- A measurement, in one tower, of the response to 35 GeV electrons as a function of integration gate.
- Various measurements taken in conjunction with other detector tests also provide data for calorimetry. Tests with the preshower detector and coil simulator provide data on the effect on the calorimeter response from material in front of it as well as information on electron identification. In addition, data were taken with a lead glass calorimeter to measure the beam profile and particle identification criteria.
- The response of the calorimeter was measured using a calibration system with Cs¹³⁷ line sources at several points in the run for comparison with the beam response.
- Part of the running included use of an unseparated beam, so data on the response to high energy muons was also obtained.

Some of the above data have already been analysed. Preliminary results are presented in Section V.B.6.

(J. Proudfoot)

6. Compensating Scintillator Plate Calorimeter Test Beam Results and Implications for the Module Design

As noted in Section V.B.5 the first of the two E-M calorimeter tile/fiber modules was installed for study in the Fermilab MP9 test beam area in July. This module initially had three towers instrumented. Scintillator tile/fiber assemblies were added to two more towers of the module in October. The second of the test modules was installed into the test beam area in November. This module was fully instrumented in all ten towers. A series of studies was made in the period from September through December to determine the viability of the basic design of the calorimeter and to answer a number of questions concerning potential problems such a calorimeter might have in the SSC experimental environment. Most of the analysis to date was done online as the data were taken. The results described in the following discussion are taken mainly from this online analysis. Upon the completion of the Fermilab fixed target run in January 1992, a comprehensive analysis of the data will be performed.

The studies made using the two test calorimeters included the following:

- "Calibration" of each of the 15 instrumented towers via a long data run with the beam centered on each tower. In preparation for these runs the phototube voltages were adjusted to obtain nearly equal response from all of the towers.
- Resolution of the calorimeter as a function of electron energy in the range 15-35 GeV.
- Study of the linearity of the response for incident electrons from 15-150 GeV.
- Study of the variation of the response of the calorimeter when the showering particle enters near or on the azimuthal crack between two modules. Data were recorded when the electron had a trajectory parallel to the crack and at angles of 2, 3, and 4 degrees with respect to the crack. Data were also recorded for cases in which the crack between the modules was "filled in" with a 1 mm lead sheet.
- Study of the variation of response of the calorimeter over the area of a single tower. The tower was mapped in a grid of cell size approximately 0.5×0.5 cm².

- Measurement of the response of the calorimeter at the tower center for angles of incidence of the showering particle of 0 and 3 degrees.
- Mapping of the calorimeter response in the vicinity of the stainless steel support bulkheads.

The resolution of the calorimeter as a function of energy was measured shortly after the first module was installed in the beam. Figure 47 shows σ/mean response to be consistent with the expected resolution of $18\% / \sqrt{(E)}$. The mean response and its variance were determined from a sample of electrons selected by demanding that the electron had traversed a $3 \times 3 \text{ cm}^2$ scintillation counter immediately upstream of the calorimeter. A small fraction of the incident electrons lose significant energy in the material upstream of the calorimeter and produce a low energy tail in the measured response. This low energy tail has been excluded from the fit region in the data shown in the figure.

A measurement of the linearity of the calorimeter for electrons of energies 15-150 GeV was made and the detector was found to give a linear response to within approximately 1% over this energy range. The data are displayed in Fig. 48. The hodoscope used to measure beam momentum limited the precision to which linearity could be determined. Data were taken near the end of December in which two planes of wire chambers were used along with one of the hodoscope planes to give a more accurate beam momentum determination. We therefore expect an improved determination of the response and resolution of the calorimeter at 100 and 150 GeV.

One of the problems faced by all calorimeters is that of hermiticity. The tile/fiber calorimeter will have uninstrumented gaps of a few millimeters width at the boundary between modules (azimuthal cracks). If the cracks point to the interaction region, high energy photons are able to "escape" the detector through the cracks giving rise to spurious missing energy signals in the event data. Using the electron beam at 35 GeV a study was performed to determine the observed effect of a projective crack and the extent to which the effect can be ameliorated by orienting the crack at a slight angle with respect to the interaction region. Data were taken with the electron beam incident parallel to the azimuthal crack between the two test modules and with the beam at angles of 2, 3, and 4 degrees with respect to the crack. An indication of the effect of the crack can be made by studying the pattern of energy deposited in the calorimeter towers on either side of the crack. Figure 49 shows the pulse height recorded in the lower of the two towers versus the response in the upper of the two towers. Plots for incident angles of 0 and 3 degrees are shown. One can

Fig. 46. EM test calorimeter test layout (not to scale).

Fig. 47. Resolution of the calorimeter versus energy. Vertical axis is the standard deviation of the energy distribution divided by the mean response. Both quantities were determined by a fit to the data excluding the low energy tail produced by energy loss of electrons in material upstream of the calorimeter.

EM Test Module Energy Scan (preliminary)

Fig. 48. Mean calorimeter response in ADC counts versus electron beam energy. The straight line is a fit to the data. The measurement at 150 GeV is within 0.5% of the fit value.

Fig. 49. Electron shower response in the tower below the azimuthal crack between modules versus response in the tower above the crack. Pulse heights have been normalized to give equal response for each tower for showers in the center of a tower. The beam momentum was 35 GeV and the data have been corrected for the spread in beam momentum.

see the prominent region in the 0 degree data in which the electron deposits essentially no energy in the calorimeter. By contrast, a rotation of the calorimeter by 3 degrees with respect to the beam restores the response in this region to a great extent. A simple correction can be made to the response in this region to provide a nearly flat response as a function of position of the shower within the calorimeter. Data taken with a 1mm lead sheet inserted between the modules to fill in the crack indicate that this scheme does little to enhance the response in the region between the modules. As a result of this study, we have adopted a rotation of the modules of 3.5 degrees as our baseline design for the SDC EM barrel calorimeter.

Final results on all the studies listed above will be forthcoming from the offline analysis to be performed after the end of the fixed target run.

C. SDC Data Systems R&D

During the second half of 1991 (with a slight overlap from the first half), work started on a project to develop a data access and storage system that will be appropriate to SDC at the end of the decade. During the first half of CY 1991, partial support had been requested from the DOE Scientific Computing Staff, who were planning an early start on a few projects that could lead into the President's High Performance Computing and Communication Initiative, planned to start in FY 1992. Initial funds were received for this project in June 1991.

An Argonne physicist is spokesman for this project which is aimed at solving one of the hardest new computing problems raised by SSC data: how to store it and provide access to it in a way that lets the physicists think primarily about physics and not about how the data is stored on tape or other media. Funds have been provided by the Scientific Computing Staff of DOE/ER to allow computer scientists to work with physicists on this problem. The collaboration includes the University of Maryland, University of Illinois at Chicago, Lawrence Berkeley Laboratory, and SSC Laboratory, in addition to Argonne. In the past year, this project has applied a computer-science approach to HEP data, with entity-relationship and object-oriented analysis of HEP data structures. A sample of almost 1 gigabyte of CDF data has been loaded into commercial relational and object-oriented databases to provide initial experience with database approaches to HEP data. Argonne did the major work on Sybase, the relational demonstration platform. Initial performance measurements indicate that the database approaches are at least competitive with the now-aging YBOS data management system used by CDF.

(L. Price)

VI. PUBLICATIONS

A. Journal Publications, Conference Proceedings, Books

Measurement of $\sigma_B(W \rightarrow e\nu)$ and $\sigma_B(Z^0 \rightarrow e^+e^-)$ in $\bar{p}p$ Collisions at $\sqrt{s} = 1800$ GeV

L. Nodulman and CDF Collaboration
Physical Review D44, 29 (1991)

Improved beta detection efficiency with granular aluminum superconducting strips

A. Gabutti (ANL/HEP), K. Gray (ANL/MSD), G. Pugh and R. Tiberio
(National Nanofabrication Facility)
Nuclear Instruments and Methods A306, 220 (1991)

Status of NP Spin-Dependent Total Cross Sections and Spin-Spin Correlation Parameters

M. Beddo (ANL/HEP)
4th Conference on the Intersections between Particle and Nuclear Physics,
AIP Conference Proceedings No. 243, Tucson, Arizona (August 1992).

Analyzing Power in Inclusive p^+ and p^- Production at High x_F with a 200 GeV Polarized Proton Beam

A. Yokosawa (ANL/HEP) and E-704 Collaboration
Physics Lett. B264, 462 (1991)

Fermilab Polarized Beam Experiments - π^0 and η Production Results

A. Yokosawa
4th Conference on the Intersections Between Particle and Nuclear Physics
AIP Conference Proceedings No. 243, (August 1992)

Summary of Spin Session Talks

H. Spinka
4th Conference on the Intersections Between Particle and Nuclear Physics,
AIP Conference Proceedings No. 243, 921 Tucson, Arizona (August 1992)

Prospects for Electroweak Parameter Measurements at CDF

L. Nodulman
Proceedings of Particles and Fields '91 Conference, TRIUMF, Vancouver, Canada
(August 1991)

Measurement of QCD Jet Broadening in $p\bar{p}$ Collisions at $\sqrt{s} = 1.8$ TeV

L. Nodulman
Physical Review D44, 601 (August 1991)

Gauge Propagator Contribution to High-Energy Baryon Number Violation

P. Arnold and M. Mattis
Mod. Phys. Lett. A6, 2059 (1991)

The Odderon Versus a New Threshold

K. Kang (Brown Univ.) and A. White (ANL)
Phys. Lett. B266, 147 (1991)

Isolated Prompt Photon Production at Collider Energies

E. Berger (ANL) and J. Qui (State Univ. of NY, Stony Brook)
 Proceedings of Particles and Fields '91 Conference, TRIUMF, Vancouver,
 Canada (August 1991)

A New Lattice Method for Chiral Fermions

G. Bodwin and E. Kovacs (Fermilab)
 Proceedings of Particles and Fields '91 Conference, TRIUMF, Vancouver,
 Canada (August 1991)

Identifying the Origin of New Gauge Bosons at the SSC and LHC

J.. Hewett and T. Rizzo(ANL/HEP)
 ANL-HEP-CP-91-76
 Proceedings of Particles and Fields '91 Conference, TRIUMF, Vancouver,
 Canada (August 1991)

Probing the Flavor Changing Vertex of the Top-Quark

G. Eilam (Technion, Israel Institute of Tech), J. Hewett (ANL/HEP), and A. Soni
 (Brookhaven Nat. Lab)
 ANL-HEP-CP-91-77
 Proceedings of Particles and Fields '91 Conference, TRIUMF, Vancouver,
 Canada (August 1991)

η_6 Production

K. Kang (Brown Univ.) and A. White (ANL/HEP)
 ANL-HEP-CP-91-88
 Proceedings of the Joint International Lepton-Photon Symposium and
 Europhysics Conference on High Energy Physics (August 1991)

The Hunt for New Gauge Bosons: Present Status and Future Prospects

T. Rizzo
 Conference Proceedings of the 15th Johns Hopkins Workshop on Current
 Problems in Particle Theory, (August 1991)

Identifying New Gauge Bosons at the SSC and LHC

T. Rizzo
 Proceedings of Particles and Fields '91 Conference, TRIUMF, Vancouver,
 Canada (August 1991)

Experimental Results for High -Energy Polarization Asymmetry

A. Yokosawa
 Proceedings of XXI International Symposium on Multiparticle Dynamics,
 Wuhan, China (September 1991)

Higgs-Boson p_T in Gluon Fusion

R. Kauffman (ANL/HEP)
 Phys. Rev. D44, 1415 (1991)

Dilepton Production by Protons on Nuclei and the Partonic Origin of Depletion at Small Momentum Fraction

K. Lassila (Argonne and Iowa State), U. Sukhatme (U. of I.),
 A. Harindranath (Ohio State), and J. Vary (Iowa State)
 Phys. Rev. C44(3), 1188 (1991)

- Hunting and Identifying New Gauge Bosons at the NLC
J. Hewett and T. Rizzo (ANL/HEP & Iowa State)
Proceedings of the Workshop on Physics and Experiments with Linear Colliders, Saariselka, Finland (September 1991)
- Review of Total Cross Sections and Forward Scattering Parameters at Ultra-High Energies
M. Block (Northwestern Univ.) and A. White (ANL/HEP)
Proceedings of the XXI International Symposium on Multiparticle Dynamics, (September 1991)
- Believability of Signals From Cosmic Ray Sources
M. Goodman
AIP Conference Proceedings 200, High Energy Gamma-Ray Astronomy 210 (October 1991)
- On Glueballs & Topology in Lattice QCD with Two Light Flavors
K. Bitar, R. Edwards, U. Heller, A. Kennedy (SCRI), T. DeGrand (Univ. of Colorado); S. Gottlieb, A. Krasnitz (IN Univ.); J. Kogut, R. Renken (Univ. of IL); W. Liu, P. Rossi (Thing Mach. Corp.); M. Ogilvie (WA Univ.); D. Sinclair, K. Wang (ANL/HEP); R. Sugar (Univ. of CA); M. Teper (Univ. of Oxford); D. Tousaint (Univ. of AZ)
Phys. Rev. D44, 2090 (1991)
- Modeling of the Transverse Mode Suppressor for Dielectric Wake-Field Accelerator
W. Gai and C-H Ho
Journal of Applied Physics 70(7) (1991)
- Compositeness and New Physics Signatures via g Final States at LEP
T. Rizzo
Workshop on Photon Radiation from Quarks, Annecy, France (December 1991)
- Peace in the Valley: Concordant Approaches to Distorted Instantons
Peter B. Arnold and Michael P. Mattis (Los Alamos Nat. Lab.)
Phys. Rev. D44, 3650 (1991)
- NP Elastic Spin Transfer Measurements at 788 MeV
M.W. McNaughton, K. Koch, I. Supek, N. Tanaka, LANL; K.H. McNaughton, P.J. Riley, D.A. Ambrose, J.D. Johnson, A. Smith, Univ. Texas, Austin; G. Glass, J.C. Hievert, L.C. Northcliffe, A.J. Simon; Texas A&M; D.L. Adams, Rice Univ.; R.D. Ransome, D.B. Clayton, Rutgers Univ.; H.M. Spinka, ANL/HEP; R.H. Jeppesen, Univ. Montana; C.E. Tripard, Washington State Univ.
Phys. Rev. C44, 2267 (1991)
- Measurement of the W-Boson Distribution in $\bar{p}p$ Collisions at $\sqrt{s} = 1.8$ TeV
L.J. Nodulman (ANL/HEP) and CDF Collaboration
Phys. Rev. Lett. 66, 2951 (1991)

B. Papers Submitted for Publication and ANL Reports

The Current Status of High Energy Elastic Scattering

M.M. Block (Northwestern Univ.), Kyungsik Kang (Brown Univ.), and
A.R. White (ANL/HEP)

ANL-HEP-PR-91-61

Submitted to International Journal of Modern Physics

S-Matrix Bootstrap of a Scalar Higgs

D. Sivers and J. L. Uretsky (also at College of DuPage)

ANL-HEP-PR-91-79

Submitted to Phys. Rev. Letters

Design Considerations for a Scintillating Plate Calorimeter

P.K. Job, L.E. Price, J. Proudfoot, (ANL/HEP); T. Handler, (Univ. Tennessee);
T.A. Gabriel, (Oak Ridge National Lab.)

ANL-HEP-PR-91-83

Submitted to Nuclear Instruments and Methods

Leading Radiative Corrections in Two Scalar Doublet Models

C.D. Froggatt, R.G. Moorhouse (Univ. of Glasgow), and I.G. Knowles (ANL)

ANL-HEP-PR-91-87

Submitted to Phys. Rev. D.

Desert GUTS and New Light Degrees of Freedom

T.G. Rizzo (ANL/HEP)

ANL-HEP-PR-91-92

Submitted to Phys. Rev. D

Transverse Momentum Distribution of Z-Boson Pairs at Hadron Supercolliders

T. Han (Fermilab), R. Meng (ANL), and J. Ohnemus (Fermilab, ANL, Univ. of
Durham, Eng.)

ANL-HEP-PR-91-94

Submitted to Nucl. Phys.

Experimental Study of Neutrino Absorption on Carbon

D.A. Krakauer, R.L. Talaga, (ANL/HEP); R. Allen, H. Chen, R. Hausammann,
W. Lee, H. Mahler, X. Lu, K. Wang, Univ. of California; T. Bowles, R. Burman,
R. Carlini, D. Cochran, P. Doe, J. Frank, E. Piasetzky, M. Potter, V. Sandberg, LANL

ANL-HEP-PR-91-97

Submitted to Phys. Rev. C

Global Nontopological Vortices

C. Kim (Seoul Nat. Univ.), S. Kim (ANL), and Y. Kim (Columbia U.)

ANL-HEP-PR-91-99

Submitted to Physics Review D.

Quick Polarization Analyzer (QPAN)

I. Supek, M.W. McNaughton, K. Koch, N. Tanaka, LANL; R.D. Ransome,
Rutgers; D.A. Ambrose, K.H. McNaughton, P.J. Riley, Univ. Texas; G. Glass;
J. Hiebert, L. Northcliffe, A.J. Simon, Texas A&M; R. Jeppesen, Univ. Montana;
H. Spinka (HEP/ANL); G. Tripart, Washington State Univ.

ANL-HEP-PR-91-102

Submitted to Nuclear Instruments and Methods

Resolving the Unitary Gauge Puzzle of Thermal Phase Transitions

S. Vokos (ANL), Peter Arnold, Eric Braaten (Northwestern U.)

ANL-HEP-PR-91-108

Submitted to Phys. Rev. D

C. Papers or Abstracts Contributed to Conferences

Testing Proton Spin Models with Polarized Beams

G. Ramsey (ANL/HEP)

ANL-HEP-CP-91-93

IV Workshop on High Energy Spin Physics, Protvino, Moscow Region
(September 1991)

New Gauge Boson Physics and the NLC

T. Rizzo (ANL/HEP and Iowa State Univ.)

Workshop on Physics and Experiments with Linear Colliders

ANL-HEP-CP-91-96

(September 1991)

Realization of Large Systems - A Summary Talk

M. Derrick (ANL/HEP)

ANL-HEP-CP-91-107

II International Conference on High Energy Physics, Capri, Italy
(October 1991)

Chiral Symmetry Breaking in Gauge Theories from Reggeon Diagram Analysis

A. White (ANL/HEP)

ANL-HEP-CP-91-109

Presented at the International Workshop on Electroweak Symmetry
Breaking, Hiroshima, Japan, (November 1991)

Combination of Probabilities in Looking for Cosmic Ray Sources

M. Goodman (ANL/HEP)

ANL-HEP-CP-91-113

22nd International Cosmic Ray Conference Vol. 4, (August 1991)

Composition Studies Based on Coincident Air Shower Array and Underground Muon Data

U. DasGupta (University of Minnesota), T.H. Fields and K. Ruddick (ANL/HEP)

ANL/HEP/CP-91-119

22nd International Cosmic Ray Conference Vol. 2, (August 1991)

The Extended Gauge Sector at the NLC

T. Rizzo

Workshop on Physics and Linear Colliders, Saariselka, Finland (September
1991)

Muon/Electron Separation for Atmospheric Neutrino Interactions

Soudan 2 Collaboration*

ANL-HEP-CP-91-112

22nd International Cosmic Ray Conference V2, (August 1991)

Multiple Muon Events in Soudan 2

Soudan 2 Collaboration*

ANL-HEP-CP-91-114

22nd International Cosmic Ray Conference V4, (August 1991)

A Search for Magnetic Monopoles with the Soudan 2 Detector

Soudan 2 Collaboration*

ANL-HEP-CP-91-115

22nd International Cosmic Ray Conference V4, (August 1991)

Underground Muons From the Direction of Cygnus X-3 during the January 1991 Radio Flare

Soudan 2 Collaboration*

ANL-HEP-CP-91-116

22nd International Cosmic Ray Conference V4, (August 1991)

Simultaneous Observations of Extensive Air Showers and Underground Muons at Soudan 2

Soudan 2 Collaboration*

ANL-HEP-CP-91-117

22nd International Cosmic Ray Conference V4, (August 1991)

Underground Muons Observed in the Soudan 2 Detector From the Directions of X-Ray Sources

Soudan 2 Collaboration*

ANL-HEP-CP-91-118

22nd International Cosmic Ray Conference V4, (August 1991)

*W. Allison, G. Barr, C. Brooks, J. Cobb, L. Kirby-Gallagher, R. Giles, G. Giller, D. Perkins, P. Shield, M. Thomson, N. West (U. of Oxford), G. Alner, D. Cockerill, V. Edwards, C. Garcia-Garcia, P. Litchfield, G. Pearce, C. Woods (Rutherford Appleton Lab), I. Ambats, D. Ayres, L. Balka, W. Barrett, J. Dawson, T. Fields, M. Goodman, N. Hill, D. Jankowski, F. Lopez, E. May, L. Price, J. Schlereth, J. Thron, J. Uretsky (ANL/HEP), D. Benjamin, B. Ewen, T. Kafka, J. Kochocki, W. Mann, L. McMaster, R. Milburn, A. Napier, W. Oliver, B. Saitta, J. Schneps, N. Sundaralingam (Tufts U), P. Border, H. Courant, B. Dahlin, D. Demuth, R. Gray, S. Heppelmann, K. Johns, T. Joyce, S. Kasahara, N. Longley, M. Lowe, M. Marshak, W. Miller, C. Minor, E. Peterson, D. Roback, D. Rosen, K. Ruddick, D. Schmid, M. Shupe, G. Villaume, S. Werkema (U. of Minnesota)

D. Technical Notes

On Implications of $e/h = 1$

L. Nodulman

ANL-HEP-TR-91-20

Central Calorimeter Configuration - A Study Report to the SDC Technical Board

T. Kirk, A. Wicklund

ANL-HEP-TR-91-26

Light Yield from a Scintillator Tile with Embedded Readout Fibers

H. Trost, J. Tonnison, V. Barnes

ANL-HEP-TR-91-49

Simulation of the Passage of Muons Through the Rock Overburden into the Soudan 2 Cavern

H. Trost

ANL-HEP-TR-91-56

HEP Semi-Annual Report (January - June, 1991)

P. Schoessow, P. Moonier, R. Talaga, R. Wagner

ANL-HEP-TR-91-60

The Effects of Passive Material on the Detection of Hadrons in Configurations for the SDC Detector

T. Kirk, H. Trost

ANL-HEP-TR-91-62

Design Considerations for a Scintillating Plate Calorimeter for SDC

T. Handler, P. Job, T. Gabriel

ANL-HEP-TR-91-68

Fiber-Tile Optical Studies at Argonne

D. Underwood, D. Morgan, J. Proudfoott

ANL-HEP-TR-91-69

b-Jet Tagging Using Electrons at SDC

A.B. Wicklund

ANL-HEP-TR-91-70

Conversion Electrons in the SDC

A.B. Wicklund

ANL-HEP-TR-91-71

$Z^0 \rightarrow$ Hadrons in SDC

A.B. Wicklund

ANL-HEP-TR-91-74

Effects of Shower Spreading on $Z^0 \rightarrow JJ$ Mass Resolution

A.B. Wicklund

ANL-HEP-TR-91-78

Luminosity Evolution at the SSC

T. Kirk

ANL-HEP-TR-91-84

Shower Counter Resolution Scaling

T. Kirk

ANL-HEP-TR-91-91

Some Physics Requirements for Triggering in the Intermediate Tracking System of SDC

H. Trost

ANL-HEP-TR-91-100

Calculations of Bottom Quark Production at Hadron Colliders

D. Kuebel

ANL-HEP-TR-91-111

AGN-11 Supports for Vacuum Waveguide

M. Rosing

AGN-12 Achromatic Beam Optics for the Photocavity

J. Norem

AGN-13 Shielding Calculations

J. Norem

AGN-14 Measurement of Frequency Response to Temperature Change of the RF Gun Cavity

C.H. Ho, R. Konecny

AGN-15 Things Your Mother Never Told You About Solenoid Lenses

J. Simpson

AGN-16 A Helical Quad Alternative for WF Tube FODO Focussing

J. Simpson

AGN-17 AWA Solenoid Design Revisited

M. Rosing

AMZEUS- Feasibility Tests for a Scintillator Pad Shower Maximum Detector

107

D. Rainwater, D. Morgan, J. Repond, D. Underwood

CDF-1505 Report of the "Neural Net Godfathers"

H. Jensen, M. Miller, A. B. Wicklund

CDF-1509 Systematic Uncertainties in the Measurement of Isolated Direct Photons

R. Harris, R. Blair, S. Kuhlmann

CDF-1516 Electron Finding Efficiency for B Electrons

F. Ukegawa, A. B. Wicklund

- CDF-1524 Combined CES and CDT Measurement of Isolated Prompt Photon Production
R. Harris, J. C. Yung, R. Blair, S. Kuhlmann
- CDF-1528 New Particle Searches at CDF
S. Kuhlmann, The CDF Collaboration
- CDF-1530 Prospects for Electroweak Parameter Measurements at CDF
L. Nodulman
- CDF-1556 A Measurement of the Bottom Quark Production Cross Section Using the E
F. Ukegawa, A. B. Wicklund
- CDF-1559 Underlying Event ET In Cones
S. Kuhlmann
- CDF-1598 Comments on Strip Chamber Alignment
A.B. Wicklund
- CDF-1623 A Prompt Photon Cross Section Measurement (PRL Support + PRD Draft)
R. Blair, S. Kuhlmann, R. Harris
- CDF-1635 YMON Detector Lists (Updated)
L. Nodulman
- CDF-1639 EGS4 Study of CDF Preshower Response
A. B. Wicklund
- CDF-1640 Hadron Backgrounds in the Inclusive Electron Sample
A. B. Wicklund, F. Ukegawa
- CDF 1641 Central Strip/Wire Maps
A. B. Wicklund, F. Ukegawa
- CDF 1652 K_o^* (892) Production and Charm Electrons
F. Ukegawa, A. B. Wicklund
- CDF 1653 A Measurement of the Bottom Quark Production in 1.8-TeV Proton-Antiproton
F. Ukegawa, A. B. Wicklund
- CDF 1655 Study of Electron Momentum with Respect to Jet Axis
F. Ukegawa, A. B. Wicklund
- PDK-475 Quarterly Activity Report (April - June 1991)
D. Ayres
- PDK-476 The Observation of Underground Muons From the Direction of Cygnus X-3
During the January 1991 Radio Flare
D. Ayres

PDK-477	Decisions of the Argonne Collaboration Meeting June 23-26, 1991 D. Ayres
PDK-491	Comments about a Soudan 2 External Muon Identifier T. Fields
PDK-492	Drift Velocity J. Cobb, E. Peterson, N. West
PDK-493	Quarterly Activity Report (July - September, 1991) D. Ayres
PDK-496	Decisions of the Tufts Collaboration Meeting D. Ayres
PDK-497	Quarterly Activity Report (Oct.-Dec, 1991) D. Ayres
PDK-498	Search for Atmospheric Neutrino Oscillations with the Soudan2 Detector D. Roback
PDK-500	On the scattering of atmospheric muons in the rock above Soudan 2 H. Trost
PDK-504	Construction of $\Delta m^2 - \sin^2 2\theta$ Plots R. Snyder, M. Goodman
PDK-506	Update of P822 The Soudan 2 Proposal for a Long Baseline Neutrino Oscillation Experiment E. Peterson
PDK-507	Prospects for Long Baseline Neutrino Oscillation Experiments M. Goodman
WF-162	Photo-Cathode Cavity Fabrication M. Rosing
WF-163	Radiation Field of Photocathode Electron M. Rosing

VII. COLLOQUIA AND CONFERENCE TALKS

E. Berger

"Calculation of Isolated Prompt Photon Production at Collider Energies"
 "Particles and Fields '91, Vancouver, Canada (August 1991)

"Recent HEPAP Meeting and Subsequent Developments"
 Argonne National Laboratory (November 1991)

G. Bodwin

"A New Lattice Method for Chiral Fermions"
 Particles and Fields '91, Vancouver, Canada (August 1991)

T. Fields

"Anomalous Nuclear Enhancements in Hard Collisions at Fermilab Energies"
 Quark Matter 1991 International Conference (November 1991)

M. Goodman

"Prospects for Long Baseline Neutrino Oscillation Experiments"
 Rutherford Laboratory, UK (August 1991)

"Long Baseline Workshop"
 Fermilab (November 1991)

"Long Baseline Neutrino Oscillation Experiments"
 U. of Chicago (August 1991)

"Combination of Probabilities in Looking for Cosmic Ray Sources"
 Cosmic Ray Conference (August 1991)

J. Hewett

"Probing the Flavor Changing Vertex of the Top-Quark"
 Particles and Fields '91 Conference, Vancouver, BC (August 1991)

"Identifying the Origin of the New Gauge Bosons at the SSC"
 SSC Laboratory, Dallas, TX (November 1991)

"The Search for Top: A Status Report"
 Iowa State University (December 1991)

" $Z \rightarrow q\bar{q}\gamma$ as a Signal for R-Parity Violation"
 Workshop on Photon Radiation from Quarks, Annecy, France (December 1991)

T. Kirk

"The Supercollider in Texas"
Argonne Sigma Xi Society (December 1991)

L. Knowles

"Thoughts on Models with Two Scalar Doublets"
Argonne National Laboratory (October 1991)

"Making Sense of Electroweak Radiative Corrections"
Argonne National Laboratory (December 1991)

R. Meng

"Sea Quark Distributions in QCD"
Southern Methodist University, Dallas, TX (November 1991)

L. Nodulman

"Prospects for Electroweak Measurements at CDF"
DPF Meeting, Vancouver (August 1991)

"Electroweak Measurements at CDF"
Univ. of Maryland (October 1991)

"Electroweak Physics at CDF"
Univ. of New Mexico (November 1991)

T. Rizzo

"Compositeness and New Physics Signatures via $q\bar{q}\gamma$ Final States at LEP"
Workshop on Photon Radiation from Quarks, Annecy, France (December 1991)

"The Extended Gauge Sector and the NLC - Summary Talk"

"Hunting and Identifying New Gauge Bosons at the NLC"
Workshop on Physics with Linear Colliders, Saariselka, Finland (September 1991)

"Identifying the Origin of New Neutral Gauge Bosons at the SSC and LHC"
Rutherford Laboratory, Oxford, England (September 1991)

"The Hunt for New Gauge Bosons: Present Status and Future Prospects"
15th Johns Hopkins Workshop on Current Problems in High Energy Physics,
Baltimore, MD (August 1991)

P. Schoessow

"Wakefield Measurements - Applications to SLAC NLC Structures"
Coupling Impedance Measurement Techniques Workshop, Argonne National
Laboratory (August 1991)

S. Vokos

"Instability of Hot Electroweak Theory: Bounds on M_{top} and M_{Higgs} "
Fermilab (September 1991)

A. White

"Chiral Symmetry Breaking in Gauge Theories from Reggeon Diagram Analysis"
International Workshop on Electroweak Symmetry Breaking, Hiroshima,
Japan (November 1991)

VIII. HIGH ENERGY PHYSICS COMMUNITY ACTIVITIES

E. Berger

Member, High Energy Physics Advisory Panel, 1991-

Member (Past-chairman), Executive Committee, Division of Particles and Fields, American Physical Society, 1991

Member, Committee on Meetings, American Physical Society 1991-

Fellowship Committee Chairman, Division of Particles and Fields, American Physical Society, 1991

International Advisory Committee, 1991 General Meeting of the Division of Particles and Fields, University of British Columbia, Vancouver, Canada, August 1991

Scientific Advisory Board, Hadron '91, University of Maryland, August (1991)

International Advisory Committee, DPF Meeting, Fermilab, November 1991

Local Organizing Committee, DPF Meeting, Fermilab, November 1991

Scientific Program Committee XXVII Rencontre de Moriond, "QCD and High Energy Hadronic Interactions", Les Arcs, France, March 1992

M. Derrick

Organizer, "Realization of Large Systems" session at the International Conference on Calorimetry for HEP held in Italy, October 1991

M. Goodman

Chair of the Organizing Committee, "Workshop on Long Baseline Neutrino Oscillations", Fermilab, November 17-20, 1991

J. Hewett

Parallel Session Coordinator, Workshop on Physics and Experiments with Linear Colliders, Saariselka, Finland, September 1991

T. Kirk

Elected to Executive Committee of APS Division of Particles & Fields
DOE Consultant for RHIC Construction Project

L. Price

Executive Committee of Users Organization of SSC (Secretary)
SSC Detector R&D Committee
ESNET Steering Committee
SDC Executive Board (Vice Chair)
SDC Computing Working Group (Chair)
SDC Physics Working Group (Chair)
ANL Computer Policy Committee

H. Spinka

LAMPF Board of Directors

T. Kirk **P. Moonier**

W. Gai	M. Rosing
S. Mtingwa	P. Schoessow
J. Norem	J. Simpson

D. Ayres	Y. Ohashi
R. Blair	L. Price
M. Derrick	J. Proudfoot
T. Fields	J. Repond
M. Goodman	H. Spinka
D. Grosnick	R. Stanek
R. Hagstrom	K. Sugano
P. Job	R. Talaga
S. Kuhlmann	J. Thron
D. Lopiano	H.-J. Trost
S. Magill	D. Underwood
E. May	R. Wagner
B. Musgrave	A. B. Wicklund
L. Nodulman	A. Yokosawa

E. Berger	T. Rizzo
G. Bodwin	D. Sinclair
J. Hewett	S. Vokos
S. Y. Kim	A. White
I. Knowles	C. Zachos
R. Meng	

E. Chojnacki	N. Hill
J. Dawson	J. Nasiatka
T. Ekenberg	R. Noland
V. Guarino	H. Rhude
D. Hill	J. Schlereth

I. Ambats	T. Kasprzyk
L. Balka	R. Konecny
H. Blair	R. Laird
W. Haberichter	R. Rezmer
D. Jankowski	J Sheppard

C. Ho J. Power

END

**DATE
FILMED**

7 / 8 / 92