**DOE/PC/88814-T7
(DE92009473)**

**FUNDAMENTAL STUDIES OF RETROGRADE REACTIONS IN DIRECT
LIQUEFACTION**

Final Report for the Period September 20, 1988–November 20, 1990

**By
Michael A. Serio
Peter R. Solomon
Erik Kroo
Sylvie Charpenay
Rosemary Bassilakis**

December 17, 1991

Work Performed Under Contract No. AC22-88PC88814

**For
U.S. Department of Energy
Pittsburgh Energy Technology Center
Pittsburgh, Pennsylvania**

**By
Advanced Fuel Research, Inc.
East Hartford, Connecticut**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615)576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U. S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

DOE/PC/88814--T7

DE92 009473

**FUNDAMENTAL STUDIES OF RETROGRADE REACTIONS IN DIRECT
LIQUEFACTION**

Final Report for the Period September 20, 1988—November 20, 1990

**By
Michael A. Serio
Peter R. Solomon
Erik Kroo
Sylvie Charpenay
Rosemary Bassilakis**

December 17, 1991

Work Performed Under Contract No. DE-AC22-88PC88814

**For
U.S. Department of Energy
Pittsburgh Energy Technology Center
Pittsburgh, Pennsylvania**

**By
Advanced Fuel Research, Inc.
East Hartford, Connecticut**

ACKNOWLEDGEMENT

The authors gratefully acknowledge the support for the work provided by the Pittsburgh Energy Technology Center of the Department of Energy under Contract No. DE-AC22-88PC88814. The contract monitors were Malvina Farcasiu and William McKinstry and their assistance is gratefully acknowledged. The preparation of the manuscript and illustrations was ably performed by Susan Bradway, Laura Jamieson and Lori Bellone.

"FUNDAMENTAL STUDIES OF RETROGRADE REACTIONS IN DIRECT LIQUEFACTION"

Final Report
DOE Contract No. DE-AC22-88PC88814

Table of Contents

DISCLAIMER	i
ACKNOWLEDGEMENTS	ii
1. EXECUTIVE SUMMARY	1
2. INTRODUCTION AND BACKGROUND	5
2.1 Introduction	5
2.2 Background	5
3. OBJECTIVES	12
4. EXPERIMENTAL METHODS	14
4.1 Coal Modifications	14
4.1.1 Dried Coals	14
4.1.2 Ion-Exchange	14
4.1.3 Demineralization	14
4.1.4 Methylation	15
4.2 Polymer Synthesis	16
4.3 Analytical Techniques	16
4.3.1 SEM/x-ray	16
4.3.2 FT-IR	16
4.3.3 TG-FTIR	17
4.3.4 Solvent Swelling	17
4.3.5 FIMS	17
4.4 Coal Liquefaction Experiments	18
4.5 Polymer Liquefaction Experiments	21
5. RESULTS AND DISCUSSION	22
5.1 Task 2 - Studies with Polymeric Model Compounds	22
5.1.1 Introduction	22
5.1.2 Polymer Synthesis	24

5.1.3	Polymer Characterization by Pyrolysis-FIMS and by TG-FTIR	29
5.1.4	Liquefaction of C-C-O Polymers	34
5.1.5	Discussion	36
5.2	Task 3 - Experiments with Coals and Modified Coals	38
5.2.1	Coal Characterizations	38
5.2.2	Liquefaction Experiments	51
5.3	Task 4 - Data Evaluation	78
5.3.1	Quantitative Modeling	78
5.3.2	Mechanistic Modeling	88
6.	CONCLUSIONS AND RECOMMENDATIONS	91
6.1	Conclusions	91
6.2	Recommendations	92
7.	REFERENCES	93
APPENDIX A - Quantitative FT-IR Data for Raw and Modified Coals		
APPENDIX B - Publications Resulting from this Contract		

1. EXECUTIVE SUMMARY

Most of the proposed processing schemes for improving liquefaction yields involve favoring bond-breaking and radical stabilization reactions over the retrograde reactions. The retrograde reactions are often encountered before liquefaction temperatures are reached. The goal of this program was to elucidate and model the retrograde reaction chemistry in direct coal liquefaction through the application of experimental techniques and theoretical models which have been successfully employed at Advanced Fuel Research (AFR) and SRI International (a subcontractor) to understand and predict coal reaction behavior. The program necessarily included studies of bond-breaking reactions, since these are intimately related to the retrograde reaction chemistry. The results of the work in this program led to an improved mechanistic understanding of retrograde reaction mechanisms in liquefaction that can be used to explore improved process concepts designed to minimize retrograde reactions and, thus, to improve liquefaction yields. The program had two major elements, as described below.

1. Chemical Probes - Fourier Transform Infrared Spectroscopy (FT-IR) was used to analyze coals, modified coals and coal conversion products in order to monitor the functional group changes. Field Ionization Mass Spectrometry (FIMS) was used for direct measurement of the molecular weight and chemical class distributions of coal liquids. Both FT-IR and FIMS were valuable tools for following the progress of the thermal reactions in coal conversion systems.

2. Multi-System Approach - The study of retrograde reactions was done by an integrated approach using extensive characterization of the liquefaction chemistry of three kinds of systems: 1) model polymers; 2) coal; and 3) modified coals. Each system has advantages as well as drawbacks. The experience of AFR has primarily been in studying the reaction behavior of coal and model polymers, mainly under pyrolysis conditions, to identify global reactions and transport effects. The experience of SRI has primarily been in studying thermal reactions of model compounds from a chemical mechanism perspective, mainly under liquefaction conditions. Each organization has developed specialized experiments, techniques, and models required to examine, elucidate and describe these systems. The combination of these resources was used in this program to try to reconcile the often conflicting observations which have been reported from experiments with model compounds and coal.

Three coals from the Argonne sample bank were used for these studies: Illinois No. 6 bituminous, Wyodak subbituminous, and Beulah Zap lignite. For each coal, samples of raw coal,

dried coal, ion-exchanged (for removal of alkali metals), methylated (for removal of hydroxyl and carboxyl groups), and demineralized coal were prepared. The coals and modified coals were characterized by a variety of techniques (TG-FTIR, elemental analysis, SEM/x-ray microanalysis, FIMS, FT-IR, solvent swelling). The coals and modified coals were subjected to liquefaction conditions in a microautoclave reactor system and the products characterized by their solubility fractions. The microautoclave reactor system that was developed allows liquefaction experiments on one gram quantities of coal and enables an analysis of the gas phase to be done. This capability is important since the evolution of certain gases has been associated with retrograde reactions. Experiments with one solvent system (phenanthrene) were done at two different degrees of hydrogenation.

The purpose of the liquefaction experiments was to see how these pretreatments affect the liquefaction yields and gain an understanding of the mechanisms of the retrograde reactions. The primary conclusions from this study are as follows:

- The extent of retrograde reactions for low rank coals (lignite, subbituminous) is significantly reduced by methylation and demineralization. However, these treatments do not have much impact on bituminous coal.
- Ion-exchange and drying have modest negative or positive impacts on liquefaction yields for all coal ranks.
- In nearly all cases, the changes in the amounts of pyridine solubles by these pretreatments parallel the changes in the amounts of toluene solubles, and hexane solubles and are inversely related to the CO₂ yields from liquefaction.
- The occurrence of retrogressive reactions under pyrolysis conditions for coals and modified coals is related to the occurrence of retrogressive reactions under liquefaction conditions.
- The FG-DVC liquefaction model provides good quantitative predictions of liquefaction yields for raw coals for experiments where significant mass transfer effects are not present.

- Under the same constraints, it can make good predictions of the yields for modified coals by adjustment of the initial extractables yield and ultimate CO₂ yield to agree with results for the starting coal and liquefaction experiments, respectively.
- Both the experimental and modeling results support the role of crosslinking associated with CO₂ evolution as a key factor in retrogressive reactions during liquefaction of low rank coals.
- The role of ion-exchanged calcium in promoting CO₂ formation accompanied by crosslinking is strongly supported by the experimental results.

A second component of the work was the preparation and characterization of model polymers in order to study retrograde reactions which are simpler to interpret. The objective of this work was to determine the competing kinetics of bond cleavage and retrogressive reactions for polymers containing chemical bonds relevant to the elements of chemical structure of coals. Under the present contract, three-atom-bridged polymers of the C-C-C and C-C-O types were prepared in order to mimic the linkages most commonly invoked in lignin and low-rank coal structures. These polymer models were subjected to various liquefaction conditions and an assessment of the bond cleavage and bond forming reactions was made by analyzing the resulting products with a variety of analytical methods such as FIMS, NMR, FT-IR and GC-MS.

In brief, the preparation of two C-C-O polymers (I and II; R = H and OCH₃) and one C-C-C polymer (III, R = H) was accomplished. In the case of the C-C-O polymers, literature procedures were adapted to achieve the previously unreported Hg(CF₃CO₂)₂-catalyzed polymerization. High molecular weights were achieved in both cases, but subsequent characterization of the polymers indicated that the polymerization was accompanied by varying degrees of side reactions, so the polymers do not consist entirely of the desired linkages. Because of these difficulties, only limited conversion studies were performed on the polymers.

Notwithstanding the fact that the polymers prepared in this program do not consist 100% of the intended linkages, the desired linkages are prominent enough that behavior of the C-C-C and C-C-O polymers offers interesting insights into the behavior of coals, and further indicates the importance and nature of retrograde reactions. Thus, the C-C-O polymers, on which most of the work was done, have shown a very high tendency for formation of refractory crosslinks, even though the individual C-C-O linkages themselves, when in low molecular weight analogs, are

known to be very labile. Furthermore, it is believed these results underscore the importance of understanding the retrograde processes that occur during reaction of polymeric structures which contain the linkages expected to be dominant in real coals, rather than the ethylene-bridged structures that dominate the model compound studies reported in the literature.

2. INTRODUCTION AND BACKGROUND

2.1 Introduction

Most of the proposed processing schemes for improving liquefaction yields involve favoring bond-breaking and radical stabilization reactions over the retrograde reactions. The retrograde reactions are often encountered before liquefaction temperatures are reached. The goal of this program was to elucidate and model the retrograde reaction chemistry in direct coal liquefaction through the application of experimental techniques and theoretical models which have been successfully employed at Advanced Fuel Research (AFR) and SRI International (a subcontractor) to understand and predict coal reaction behavior. The program necessarily included studies of bond-breaking reactions, since these are intimately related to the retrograde reaction chemistry. The results of the work in this program led to an improved mechanistic understanding of retrograde reaction mechanisms in liquefaction, that can be used to explore improved process concepts designed to minimize retrograde reactions and, thus, to improve liquefaction yields. The program had two major elements, as described below.

2.1 Background

The motivation of the present study comes from work that has been done on the pyrolysis of coals, modified coals, and model compounds. This work has identified several key factors which are important in retrograde reactions which occur under pyrolysis conditions. Solvent swelling (Green et al., 1982, 1984) has been used as a method for measuring the crosslink density of pyrolysis chars. The amount of tar formation in pyrolysis is another indication of the amount of crosslinking which has occurred (Suuberg et al., 1985, 1987, 1988; Deshpande et al., 1988; Solomon et al., 1988).

Measurements of the solvent swelling ratio for a number of coals pyrolyzed under the same conditions show that the early crosslinking which reduces liquid yields, occurs in low rank coals, as shown in Figure 2.2-1. This result is consistent with the observation that the short time liquefaction yields are lowest for these coals (Whitehurst et al., 1980). Suuberg et al. (1985, 1987) observed that the low temperature crosslinking associated with low rank coals appeared to correlate with the evolution of CO_2 . This correlation was confirmed in recent work done by Solomon and coworkers, as shown in Figure 2.2-2. A similar correlation was found with the loss of H_2O . Based on the assumption that low temperature crosslinking was related to decomposition

Figure 2.2-1. Comparison of Solvent Swelling Ratios for Coals of Various Ranks at a Series of Pyrolysis Temperatures.

Figure 2.2-2. Correlation Between Loss of Swelling and Gas Evolution.

of carboxyl and/or hydroxyl groups, FT-IR functional group analysis was done on the pyrolysis chars. The results, which are shown in Figure 2.2-3, support the role of both functional groups in crosslinking.

The water content of the coal also appears to play a role in retrograde reaction chemistry. Studies have shown that drying the coal can increase the amount of crosslinking which occurs in pyrolysis (Suuberg et al., 1988) and liquefaction (Frazee and Silver, 1985). Steam pretreatment has been found to have a beneficial effect on pyrolysis (Graff and Brandes, 1987) and liquefaction yields (Bienkowski et al., 1987 a,b).

In addition to solvent swelling, an examination of the tar yield and tar molecular weight distribution has been valuable in assessing the degree of crosslinking (Solomon, et al., 1988; Solomon and Squire, 1985). Results for Field Ionization Mass Spectrometry (FIMS) analysis (done at SRI International) of the eight Argonne coals are shown in Figure 2.2-4. It can be seen that the tar molecular weight distribution (MWD) for low rank coals drops off fairly dramatically above 200 AMU. The dramatic cut off is consistent with the occurrence of crosslinking in these coals and the lower tar yields that have been measured. When a low rank coal is methylated, it has been found that the tar yield and the tar MWD begin to resemble a bituminous coal, as shown in Figure 2.2-5 for a Texas lignite (Solomon and Squire, 1985).

The removal of cations from a low rank coal by ion-exchange or demineralization also has a beneficial effect on the tar yield and the extent of crosslinking in pyrolysis studies (Tyler and Schaefer, 1983). The role of cations in direct liquefaction has not been extensively studied, although calcium has been implicated in reducing yields (Mochida, et al., 1983; Whitehurst, et al., 1980).

The results from these pyrolysis studies, which have shown the importance of oxygen functional groups, water content, and cations on crosslinking, provided much of the motivation for the present study of retrograde reactions in liquefaction using similar analytical techniques.

Figure 2.2-3. Correlation Between Loss of Swelling and Loss of Functional Groups.

Figure 2.2-4. Tar Molecular Weight Distributions from Pyrolysis-FIMS of the Argonne Premium Coals.

Figure 2.2-5. Comparison of Spectra for Raw and Perdeutero-Methylated Texas Lignite.

3. OBJECTIVES

The overall objective of the program was to improve the understanding of retrograde reactions and their dependencies on coal rank and structure, and/or coal modifications and reaction conditions. Because retrograde reactions are competitive with bond breaking reactions, an understanding of both is required to shift the competition in favor of the latter. Related objectives were to clarify the conflicting observations reported in literature on such major topics as the role of oxygen groups in retrograde reactions and to provide a bridge from very fundamental studies on pure compounds to phenomenological studies on actual coal. This information was integrated into the FG-DVC model, which was improved and extended to the liquefaction context. In order to accomplish this, the program had the following specific objectives.

- Experiments with model polymer systems representative of coal. The polymers were synthesized at SRI, studied in microautoclave reactors and also using temperature-programmed Field Ionization Mass Spectrometry (FIMS). The same polymers were studied at AFR in a TG-FTIR apparatus which includes on-line analysis of product gases.
- Experiments with coals and modified coals of a range of rank were done in the above-mentioned TG-FTIR and in a micro-autoclave liquefaction reactor constructed at AFR.
- Modeling of all of the above experiments was done. This modeling ranged from fully-mechanistic in the model compounds, when feasible, to mechanistically-based, parametric modeling for coals. The mechanisms were streamlined for input into the AFR FG-DVC model which was refined and modified to describe liquefaction systems.

This program was a collaborative effort between AFR and SRI International. A schematic of the work breakdown structure of the project is given in Figure 3-1.

Level 1

IMPROVED UNDERSTANDING OF RETROGRADE REACTIONS DURING COAL LIQUEFACTION

Level 2

Task 1
Work Plan
AFR/SRI

Task 2
Studies with
Polymeric Models

Task 3
Studies with Coals
and Modified Coals

Task 4
Integration and
Reporting
(AFR/SRI)

Level 3

Polymer
Synthesis

Liquefaction
Studies

Modification
of Coals

Liquefaction
Studies

Level 4

C-C-C Polymers

C-C-O Polymers

C-C-C Polymers
SRI

C-C-O Polymers
AFR

Methylation
SRI

Ion-Exchanged
Demineralization
AFR

Methylated
SRI

Ion-Exchanged
Demineralized
Coal AFR

Raw/Dried
Coals
AFR/SRI

Figure 3-1. Work Breakdown Structure of the Project.

4. EXPERIMENTAL METHODS

4.1 Coal Modifications

Three coals from the Argonne sample bank were used for these studies: Illinois No. 6 bituminous, Wyodak subbituminous and Beulah Zap lignite. The chemical and physical properties of these coals have been summarized by Vorres (1990). Coal samples were prepared so that for each coal there was a supply of raw coal, dried coal, acid-demineralized coal, ammonium ion-exchanged coal, and methylated coal. In the case of the Illinois coal, the starting material for the methylation work was a PSOC 1098. All of the coal modifications were done at AFR, except for the methylation work, which was done at SRI. These procedures are described below.

4.1.1 Dried Coals

Samples of dried coals were prepared by heating at 105°C under vacuum for a minimum period of two hours.

4.1.2 Ion-Exchange

This modification was a variation of procedure of Hengel and Walker (1984). A beaker charged with 30 g of coal and 375 ml of 1.5M ammonium acetate was stirred at room temperature for 1 hour, 20 minutes. The coal was then filtered and washed with 200 ml of fresh 1.5 ml ammonium acetate. The coal sample was mixed with fresh ammonium acetate and stirred for periods of 5, 18, 6, 6, and 21 hours. The final rinse was with 200 ml fresh ammonium acetate followed by 350 ml de-ionized H₂O. The coal was then dried under vacuum at 105°C for a minimum of two hours.

4.1.3 Demineralization

This modification was a variation of the procedure of Bishop and Ward (1958). A teflon wash bottle (adapted for the demineralization procedure) was charged with 55 grams of raw coal, 525 ml de-ionized water, and 150 ml 6M HCl and heated under nitrogen in a boiling water bath for 15 minutes. The slurry was allowed to cool and was filtered and washed with de-ionized water. The washed and filtered coal was placed back into the teflon wash bottle. A mixture of 150 ml

50% HF and 150 ml 6M HCl was added to the coal. The heating, filtering, and washing procedures were repeated. The coal was dried under vacuum at 105°C for a minimum of two hours.

4.1.4 Methylation

This modification was based on the procedure of Liotta (1979). The vial of coal was opened in a nitrogen glove box and its contents (~5 g) poured into a Schlenk reaction vessel. The coal was vacuum dried (≥ 0.05 Torr) at 60°C to constant weight for 16 hours. In the nitrogen glove box, an analytical sample of the dried coal was prepared in a glass ampoule. The sample was evacuated (0.05 Torr) at ambient temperature for 1 h and then sealed under static vacuum with a flame.

The remaining coal was treated with THF (freshly distilled from Na/benzophenone, 15mL) followed by a solution of [(n-Bu)₄N][OH] in methanol (23.0 mL of 1.0 M, 23.0 mmol). The resulting dark brown slurry was subjected to three pump/Ar purge cycles to remove any trace oxygen and was then stirred at ambient temperature. After a reaction time of 30 h, additional [(n-Bu)₄N][OH] in methanol (10.0 mL of 1.0 M, 10.0 mmol) was added. The reaction mixture was then stirred for 25 h at ambient temperature, and then CH₃I (4.1 mL, 66 mmol) was added. This slurry was stirred at ambient temperature for 86 h.

Solvents were removed under reduced pressure (≥ 0.05 Torr) without applied heat to give a black mud, which was diluted with distilled water that had been deoxygenated by bubbling Ar through it for 1.5 h. A few mL of this water were stirred with the mud, and the solution phase showed a pH of 7-8 by Hydrion paper. Aqueous hydrochloric acid was added (2.0 mL of a 1.0 M solution), and the pH of the solution phase was measured as ca. 3. Additional water (400 mL) was added and the suspension filtered under Ar through a medium sintered glass frit. The coal was washed with water (2 x 50 mL) and then taken to near dryness at ambient temperature under reduced pressure (≥ 0.05 Torr). The slightly damp coal was transferred to a Soxhlet thimble under a stream of Ar and extracted with refluxing water for 24 h. The water in contact with the bottom of the Soxhlet thimble then gave no precipitate with aqueous AgNO₃; whereas the water in the extraction pot gave a heavy yellow precipitate with aqueous AgNO₃.

The coal was dried in the thimble under reduced pressure (0.05 Torr) at ambient temperature for 5 h, and then transferred from the thimble to a round-bottom flask under an Ar

stream. The coal was dried under reduced pressure (0.05 Torr) at 60°C for 16 h. An analytical sample was prepared as for the unmethylated sample. The dried coal was stored in the nitrogen glove box.

The progress of methylation was monitored using IR spectrometry. All the active hydrogens could not be methylated in one step and experiments were conducted with multiple stages of methylation and longer reaction times.

4.2 Polymer Synthesis

The polymer synthesis work is described in Section 5.1.

4.3 Analytical Techniques

The starting coal samples have been characterized by the following procedures: TG-FTIR to determine proximate analysis, condensable product yield, gas yields, etc.; elemental analysis to determine C,H,N,O, and S; mineral analysis and spatial distribution by a SEM/x-ray microanalyzer; quantitative FT-IR analysis of minerals and functional groups; FIMS analysis of molecular weight distributions of condensable products; and solvent swelling to determine the crosslink density. The analytical methods are described below.

4.3.1 SEM/x-ray

AFR has a SEM/x-ray analysis system which was used to measure the total ash and cation contents of each sample. This was especially useful for verifying the degree of cation exchange. The SEM/x-ray system is based on a method originally described by Solomon and Manzione (1977) and is further described elsewhere (Hamblen, et al., 1980; Hamblen, 1981; Hamblen and Best, 1982). It consists of an ISI model SX-30 scanning electron microscope with a Princeton Gamma Tech System 4 x-ray analyzer. The analyzer has the capability of measuring elements heavier than sodium.

4.3.2 FT-IR

Quantitative FT-IR analysis was used to monitor the changes in the coal structure due to the modifications described above. AFR has considerable experience using this technique to

make functional group analysis of coals and residues from liquefaction and pyrolysis experiments. The techniques for quantitative analysis have been described previously (Solomon, 1981; Solomon and Carangelo, 1982, 1988; Solomon, et al., 1982, 1985).

4.3.3 TG-FTIR

The use of thermogravimetric (TG) analysis combined with FT-IR analysis of evolved products is called TG-FTIR. The instrument used was the TG/plus from Bomem, Inc. Its components are as follows: DuPont™ 951 TGA; a hardware interface (including a furnace power supply); an Infrared Analysis 16 pass gas cell with transfer optics; a MICHELSON 100 FT-IR; (Resolution: 4 cm^{-1} , Detector: MCT). This apparatus was developed at AFR and is described in Carangelo et al. (1987) and Whelan et al. (1988). Since analysis of the volatile products in pyrolysis is related to the functional group composition of the sample, routine TG-FTIR analysis provides a valuable complement to the FT-IR functional group analysis.

4.3.4 Solvent Swelling

Solvent swelling measurements were done using a modification of the procedure of Green et al., (1982, 1984). A weighed amount (~ 100 mg) of sample is put into a centrifugation vial. The sample is then centrifuged for 10 minutes and the volume of the sample is recorded. Next, the vial is filled with the solvent (pyridine), intensively mixed using a piece of metal wire or by vibration and then plugged to avoid solvent evaporation. After several hours (usually a day), the system is mixed again, centrifuged for 10 minutes and the liquid phase is separated carefully with the help of a syringe. Fresh solvent is then added, the sample mixed again, centrifuged for 10 minutes and the sample volume recorded. To enhance the visibility of the boundary between the liquid and solid phase, a UV light source is used. This last step is repeated until no change is observed in the sample volume. This can take several days. To measure the pyridine-soluble fraction, the solvent phase from the above procedure is collected into an aluminum foil dish to evaporate the solvent and measure the residue by weight. In this case, the procedure is repeated until no change is observed in the residue weight.

4.3.5 FIMS

The use of Field Ionization Mass Spectrometry (FIMS) (St. John et al., 1978) has also been very useful as a method of characterizing modified coals as illustrated in Section 2.2 (Figs. 2.2-4

and 2.2-5). The Py-FIMS spectrum is markedly different for coals which undergo crosslinking compared to those which do not. This technique was used for characterizing the modified coals in this program.

4.4 Coal Liquefaction Experiments

After the coal samples were characterized, experiments were done under donor solvent liquefaction conditions in a microautoclave reactor which allows for gas analysis. The microautoclave reactor used was model MS-16 supplied by the High Pressure Equipment Co. (Erie, PA) with an internal volume of 19 ml. A schematic of the reactor system is shown in Figure 4.4-1. One liquefaction solvent was used (dihydrophenanthrene) with two degrees of hydrogenation (pure and in a 50/50 mixture with phenanthrene). The experimental procedure is given below.

After leak testing of the reactor containing the coal and solvent, it was purged (pressurized - depressurized) with N_2 , and the valve on the reactor was closed. The reactor was then immersed into a 400°C fluidized sandbath for the required time, lifted out and quenched with water. The reactor was subsequently pressurized to 1000 psig and was equilibrated into a 870 cc evacuated gas sample tank. The entire volume was taken to be 900 cc. The gases were measured chromatographically from the sample tank.

Products were dissolved and washed out of the reactor with toluene. The insoluble products were filtered into a paper thimble and put into a Soxhlet extractor for 24 hour extraction with toluene, and into the vacuum oven for drying. In work done early in the program, the drying process was monitored for toluene removal by putting the partially dried samples into a high pressure, high temperature continuous extractor/FT-IR monitor system (see Fig. 4.4-2). In this system, hexane was pumped through the coal sample using an HPLC pump. The eluent was monitored for traces of toluene using an FT-IR spectrometer coupled to a flow through cell (circle-cell). Hexane was used for the extraction of toluene out of the coal because hexane can easily be dried out afterwards. It was found that an eight hour drying at 100°C in the vacuum oven was enough to get rid of the toluene from the coal residue.

The toluene solubles (solvents + oils + asphaltenes) were concentrated in a rotary vacuum evaporator and measured by weight in aluminum foil dishes. A stable weight was usually reached after drying them at room temperature for 24 hours and at 80°C for 2 hours.

1. Bomb Reactor
2. High Temperature Valve
3. High Temperature Adapter (High Pressure Equipment Corp. #20-12LF4-HT) with Teflon Packing
4. Short (1") Connection Between Reactor and Valve (1/4" O.D. x 1/16 I.D.)
5. Base Plate to Hold Reactor
6. Thermal Insulation
7. Electrically Heated Fluidized Sand Bath

Figure 4.4-1. Schematic of AFR Microautoclave Reactor System.

1. Eluent Reservoir (under He atmosphere)

2. HPLC Pump

3. Inline Filter (a: 10μ , b: 2μ)

4. Pulse Damper

5. Pressure Gauge

6. Inline Filter (2μ metal frit thimble holding the coal)

7. Furnace

8. Temperature Regulator

9. Circle-cell for FT-IR Monitoring

10. Bomem 110 FT-IR Spectrometer

11. PC

12. Back Pressure Regulator

13. Relief Valve

Figure 4.4-2. Schematic of the Continuous Extraction Unit.

The asphaltenes were determined from the toluene solubles by extracting the solvent and oil fraction with hexane and measuring the remaining fraction the same way the toluene solubles were measured. The residue from the toluene extraction was subsequently extracted with pyridine to allow determination of the pyridine solubles and insolubles.

4.5 Polymer Liquefaction Experiments

These experiments are described in Section 5.1.

5. RESULTS AND DISCUSSION

5.1 Task 2 - Studies with Polymeric Model Compounds

5.1.1 Introduction

The objective of this task was to determine the competing kinetics of bond cleavage and retrogressive reactions for polymers containing chemical bonds relevant to the structure of coals. The rationale and approach are discussed below. The synthesis, characterization, and liquefaction of these polymeric coal surrogates is described in the following subsections.

Efforts to understand the key chemical reactions responsible for coal conversion have been severely hindered over the years by the necessity of having to infer a complex sequence of chemical reactions for a substrate coal, whose critical linkages are basically unknown. To aid in this effort, many workers have studied the reactions of coal "models" under various conversion conditions. However, this already imperfect solution has itself been limited by the inappropriateness of many of the models, and by the widespread misconception that the spontaneous thermal scission of inherently weak linkages in the coal structures is solely responsible for the fragmentation of the coal matrix. In fact, the combination of these two factors has compounded the situation; the perception of control by homolysis of weak linkages has led to a disproportionate focus on weakly bonded models such as bibenzyl, benzylphenyl ether, and related structures. In this project, model structures were chosen that (1) have inter-cluster linkages that are considered more representative of those in coals, and (2) are incorporated into polymeric networks in order that mass transport and other effects that can be important in heterogeneous systems might be more appropriately mimicked.

The basic linkage chosen for the present study is the oxy-ethylene linkage of phenyl phenethyl ether. Although phenyl phenethyl ether and related structures have been previously studied as coal models (Poutsma and Dyer, 1982; Gilbert and Gajewski, 1982; Gilbert, 1984, Klein and Virk, 1983), they have not received the attention commensurate with their recognized abundance in lignins and their presumed importance in low-rank coals. No studies, to our knowledge, have been reported for specially synthesized and characterized polymers containing this linkage. As it happens, the weakest bond in phenyl phenethyl ether, the phenoxy-carbon bond, is about equal in strength to the central bond in bibenzyl (McMillen and Golden, 1982; Pedley et al, 1986). At -61 kcal/mol, the bibenzyl bond undergoes homolysis at 400°C with a

half life of ~25 hours, but as has been demonstrated in studies of several three-atom-linked di-aryls (Poutsma and Dyer, 1982; Gilbert and Gajewski, 1982; Gilbert, 1984; Klein and Vrik, 1983), homolysis typically serves only as the initiation process for their decomposition. In the case of phenyl phenethyl ether itself, the very facile β -scission of the benzylic radical formed by H-abstraction results in an observed half-life (at 400°C) that is at least 10 times shorter than that for the homolysis of either its weakest bond or that of bibenzyl (Gilbert and Gajewski, 1982). Clearly, either coals do not have very many such linkages, or some other factor (viz., retrograde reaction) counteracts the demonstrated reactivity of the O-C-C linkage. Interestingly, low-rank coals have for a long time been known to be more reactive than bituminous coals, but they give lower liquefaction conversions (Given, et al., 1980; Whitehurst, 1980; Song et al., 1989). Therefore, it seems likely that a crosslinked or intertwined polymeric network, or the presence of additional functional groups (i.e., -OH, -OMe, or -COOH), result in a proclivity for retrograde reactions that make coals with very labile linkages unusually hard to convert. To better understand those retrograde processes and the approaches that might be used to limit them, it was proposed to prepare and study the following three-atom-bridged polymers. Polymers I and II have C-C-O bridges between phenylene residues while Polymers III and IV have C-C-C bridges.

These polymer models were then to be subjected to various liquefaction conditions and an assessment of the bond cleavage and bond forming reactions made by analyzing the resulting products with a variety of analytical methods such as FIMS, NMR, FT-IR, and GC-MS.

The results are described in the following sections. In brief, the preparation of two C-C-O polymers (I and II; R = H and OCH₃) and one C-C-C polymer (III, R = H) was accomplished. In the case of the C-C-O polymers, literature procedures were adapted to achieve the previously unreported Hg(CF₃CO₂)₂-catalyzed polymerization. High molecular weights were achieved in both cases, but subsequent characterization of the polymers indicated that the polymerization was accompanied by varying degrees of side reactions, so the polymers do not consist entirely of the

desired linkages. Because of these difficulties, only limited conversion studies on the polymers were performed.

Notwithstanding the fact that the polymers prepared in this program do not consist 100% of the intended linkages, the desired linkages are prominent enough that behavior of the C-C-C and C-C-O polymers offers interesting insights into the behavior of coals, and further indicates the importance and nature of retrograde reactions. Thus, the C-C-O polymers, on which most of the work was done, have shown a very high tendency for formation of refractory crosslinks, even though the individual C-C-O linkages themselves, when in low molecular weight analogs, are known to be very labile. Furthermore, it is believed that these results underscore the importance of understanding the retrograde processes that occur during reaction of polymeric structures which contain the linkages expected to be dominant in real coals, rather than the ethylene-bridged structures that dominate the model compound studies reported in the literature. For instance, it was noted that pyrolysis of polymers consisting of naphthalene units connected by ethylene bridges show substantial volatiles evolution in the same temperature region as do coals (Squire et al., 1986). However, under liquefaction conditions these polymers are converted 100% to toluene-soluble materials in 1 h at 400°C (Malhotra et al., 1989). The presence of a donor solvent makes liquefaction of a polymeric model linked entirely by weak bridges (and containing no oxygen) far more facile than the liquefaction of coals is observed to be. In other words, the ratio of cleavage and retrograde reactions is readily manipulated by a solvent for these polymers in a way that is not possible with real coals.

5.1.2 Polymer Synthesis

C-C-O Polymers - Polymers containing the C-C-O linkage between single phenyl rings have been prepared by the oxymercuration of eugenol ($R = \text{OCH}_3$) and 4-allylphenol ($R = \text{H}$). Eugenol was obtained from Aldrich Chemical, Inc. 4-Allylphenol was obtained by custom synthesis from Saber Laboratories (Morton Grove, Illinois).

The original plan called for either direct or indirect polymerizations of eugenol (or 4-allylphenol) via oxymercuration. As expected, oxymercuration of eugenol, a readily available starting material, with $\text{Hg}(\text{OAc})_2$ afforded the diol in a reasonable yield.

As shown, the reaction sequence would have involved the conversion of the olefin function into an alcohol (after reductive cleavage of the C-Hg linkage with NaBH₄ in alkali). The alcohol would have then been converted into a bromide and the product bromophenol subjected to polymerization. Before proceeding any further with the indirect polymerization, direct polymerization of eugenol with Hg(NO₃)₂ as a catalyst was attempted. The yield was very low, probably because the Hg(NO₃)₂ catalyst was too moist. However, polymerization with dry Hg(CF₃CO₂)₂ in nitromethane at 80°C proceeded smoothly. Thus, the low nucleophilicity of the trifluoroacetate (TFA) complex of eugenol apparently allows for attack on the mercurated complex by the phenolic oxygen on the complexed end of the eugenol molecule, resulting in direct polymerization of the substrate that involves two fewer steps than the indirect route shown above. Mercury was removed from the initial polymerization product using sodium borohydride.

The polymers were characterized using elemental analysis, GPC, NMR, and field ionization mass spectrometry (FIMS). GPC shows that the poly(eugenol) sample discussed here has a broad distribution of molecular weights (1×10^4 to 2×10^6 ; $M_n \sim 2 \times 10^5$). The poly(4-allylphenol) sample, on the other hand, has a narrow MW range with a $M_n \sim 5 \times 10^6$. Light scattering experiments confirmed the very high molecular weights of these polymers. The initially prepared polymers are insoluble in most common solvents and only sparingly soluble in cold DMF. However, they have high solubility in hot DMF. ^1H NMR peak area ratios were generally consistent with the expected ratios, but were not highly precise, owing to limited solubility in the cold DMF as well as interference from water and traces of protonated solvent in the deuterated DMF. ^{13}C CPMAS NMR of the solid samples is also consistent with the expected structure, however, reliable quantitative information on the relative amounts of alkyl and aryl protons could not be obtained on these high molecular weight samples. Elemental analysis (Galbraith Laboratories) in both cases indicates H/C ratios somewhat lower than expected (0.99 and 0.97 vs calculated values of 1.20 and 1.11 for the poly(eugenol) and poly(4-allylphenol), respectively).

Characterizations by pyrolysis-FIMS (Py-FIMS) and by Thermogravimetric FT-IR analysis (TG-FTIR), as well as some preliminary liquefaction studies, were performed on the poly(eugenol) and the poly (4-allylphenol). Some of these experiments constitute both characterization and conversion experiments, and will be discussed under Conversion Studies. In the remainder of this section, the focus is on the non-thermal characterizations (but including elemental analysis) and on the attempts to improve the synthesis of C-C-O polymers.

It was first suspected that the lack of better elemental analysis data was due to the inability to purify the polymer products. For both of the C-C-O bridged polymers, a substantially greater oxygen content than expected from the respective formulas was obtained, as well as some nitrogen. Polymers that are prepared in solvents often give erroneous elemental analyses because of the difficulty of removing all the solvent. In our case, the polymers were soluble only in DMF, which is particularly hard to remove. FT-IR of the poly(4-allylphenol) showed the presence of DMF, along with some nitromethane. If most of the nitrogen was ascribed to nitromethane, the solvent in which the polymerization was conducted, and then the analysis was corrected for the accompanying carbon, hydrogen, and oxygen, the C, H, and O content of the polymer worked out in good agreement with the calculated value for the case of poly(4-allylphenol). However, a similar analysis for the poly(eugenol) sample resulted in only a marginal improvement, which basically means that there must be other contaminants besides occluded solvent.

In order to obtain improved solution phase NMR, as well as to facilitate purification before elemental analysis, the preparation of lower molecular weight polymers was done by carrying out the polymerization at lower temperatures and by including phenol in the reaction mixtures to terminate the growing polymer chains. When poly(4-allylphenol) was prepared by conducting the polymerization at room temperature for three days with a reaction mixture containing five mol% phenol, most of the reduced product (>90%) was soluble in THF. NMR of the soluble portion showed, in addition to the characteristic peaks due to 4-allylphenol, peaks that are consistent with a C-C-C-O linked polymer. The peak due the methyl group of the expected C-C-O coupling product was absent. These results point to anti-Markownikov addition during initial mercuration, which is surprising.

One sample of the phenol-terminated poly(4-allylphenol), designated 8874-25, was examined by elemental analysis and by TG-FTIR. The elemental analysis (oxygen by direct determination) of as prepared 8874-25 and after dissolution in methanol followed by precipitation with ether and rigorous drying provided the following C, H, O, and N content:

	C	H	O	N
8874-25	71.80	6.07	13.79	0.75
8874-25-washed	71.19	6.01	14.48	0.65
Calculated (allylphenol)	80.59	7.46	11.94	

There was considerably less nitrogen in these samples compared to that found in the other samples of poly(4-allylphenol). However, there was some excess of oxygen and the observed CHNO values add up to only about 92%. There was no residue, thus the missing 8% is not due to a metal; it could be halogen, possibly fluorine from incorporation of trifluoroacetic acid.

Analysis by TG-FTIR yields trifluoromethane, in support of the trifluoroacetate hypothesis. If all of the missing 8% is attributed to fluorine in the sample, the frequency of incorporation of trifluoromethyl residues would appear to be approximately once every five monomers. If it is further assumed that fluorine was incorporated as trifluoroacetate groups (and evolved as CF₃H under elemental analysis), the fractional weight of carboxyl functions (CO₂) in the polymer calculates out to 5.0%, a number slightly larger than the weight of CO₂ (3.5 wt%) observed in TG-FTIR, suggesting that either not quite all of the 8%-discrepancy is due to fluorine or that fluorine may also be incorporated by means other than trifluoroacetate residues.

Incorporation of trifluoroacetate groups would normally lead to termination of the polymer chain. However, high molecular weights for the C-C-O polymers were consistently observed. The very high molecular weights of the polymers together with substantial levels of CF₃ groups points to the occurrence of other coupling mechanisms; for example, mercury catalyzed electrophilic substitution, which might be made even more facile by the presence of the phenolic function. In summary, it appears that the direct polymerization route is plagued under some conditions by side reactions.

Monomer Studies - The side reactions that became evident through analysis of the phenol-terminated, lower molecular weight poly(4-allylphenol) samples indicated it was necessary to examine in more detail the dependence on various reaction conditions. Accordingly, experiments were conducted on oxymercuration of allylbenzene with phenol. When the reaction was conducted at 90°C, the temperature at which the polymerization was originally done, many products were formed and the product mixture was dark brown. Also, precipitation of mercury was observed. When the reaction was carried out at room temperature, the reaction was slow, and the precipitation of mercury was not observed. NMR of this product mixture (which included substantial quantities of unconverted starting materials) suggests isomerization of allylbenzene to β -methylstyrene is another side reaction of 4-allylphenol.

The residue obtained from oxymercuration was reduced using borohydride. The oily product obtained after reduction was distilled under reduced pressure to remove most of the phenol and allylbenzene (confirmed by IR, NMR, and TLC). Separation of the residue on a chromatotron showed four bands. Extraction of the bands followed by TLC, NMR, and IR examination showed the presence of the expected C-C-O coupling product, and another coupling product with the C-C-C-O linkage. The last product results from the anti-Markownikov attack of phenol on the Hg(II)-activated double bond. The consequences of producing a polymer having a small fraction of its linkages of the C-C-C-O type are discussed under Polymer Characterization.

C-C-C Polymers - Initial efforts to produce well-characterized C-C-C polymers have used the following reaction sequence:

The α,α' -dibromo-p-xylene (V) was treated with the monoanion of dithiane (VI) in THF at -50° to -30°C . The product was characterized by TLC and NMR and found to be consistent with the anticipated structure. The dianion from VII was treated with the dibromide (V) at low temperatures for 3 h and thereafter at room temperature for 15 h. The THF-soluble fraction showed a polymer of MW ~ 2500. Desulfurization of the THF-soluble portion was effected using Raney Ni and the product was exhaustively extracted to yield a polymer of MW ~ 1500. Elemental analysis gave C = 83.86% and H = 8.7%, indicating an H/C ratio of 1.24 (as compared with an expected ratio of 1.11). The 8%-unaccounted material could be due to oxygen in occluded solvent, or due to sulfur retained from the dithiane rings. The discrepancy was not resolved as more effort was devoted to eliminating the side reactions in the preparation of the C-C-O polymers.

5.1.3 Polymer Characterization by Pyrolysis-FIMS and by TG-FTIR

C-C-O Polymers - Since the Py-FIMS and TG-FTIR analyses both involve programmed-temperature heating to pyrolytically generate volatiles which are then analyzed, both of these techniques constitute conversion as well as characterization. They thus form a bridge between the synthesis efforts described above, and the liquefaction studies reported below. As with the elemental and NMR analyses, the Py-FIMS characterization of the poly(eugenol) and the poly(4-allylphenol) is appropriately described as roughly consistent with, but certainly not conclusive evidence of, polymers containing the desired structures.

The Py-FIMS spectra of the poly(eugenol) and the poly(4-allylphenol) are shown in Figures 5.1-1 and 5.1-2. The spectra are relatively simple and are dominated by C_1 - to C_3 - phenols or dihydroxybenzenes (catechols), and, in the case of the poly(eugenol), by an ion corresponding

Figure 5.1-1. Pyrolysis-FI Mass Spectrum of Poly(eugenol).

Figure 5.1-2. Pyrolysis-FI Mass Spectrum of Poly(4-allylphenol).

to the monomer (m/z 164). These products are all to be expected from the desired polymer structure. However, the relative amounts of the various fragments are quite unexpected, indicating either the decomposition sequence is not as anticipated or the polymer structure is not exactly as desired, or both.

In both cases, the sequence of oligomeric groupings commonly seen in Py-FIMS of linear polymers (10) is essentially absent. The spectrum from the poly(eugenol) sample (Figure 5.1-1) shows a large peak at m/z 164, representing the monomer, but has very little intensity in the vicinity of the dimer (m/z 328) and none in the vicinity of the trimer (m/z 492). The spectrum of the poly(4-allylphenol) is even more pronounced in this regard; there is only moderate intensity at the monomer (m/z 134) and essentially none at the dimer and trimer masses (m/z 268, 402). The ten-fold decline in intensity of the dimer relative to the monomer and the total absence of any ion intensity corresponding to the trimer is highly unexpected for a linear polymer that cannot unzip and is thus limited to scission by random attack on its linkages. The principal expected bond scission pathways shown below for the case of the eugenol polymer should occur randomly along the polymer chain and would result in a whole sequence of oligomers, as has been reported in the pyrolysis of other linear polymers (Squire et al., 1980).

Scheme 1. Anticipated pathway for decomposition of poly(eugenol).

Along with the absence of higher oligomers, Figures 5.1-1 and 5.1-2 also show that each polymer yields substantial amounts of several alkylated dihydroxybenzenes and phenols, respectively. In the case of poly(eugenol), the C_1 - and C_2 - dihydroxybenzenes are of comparable abundance to the monomer itself. In the case of the poly(4-allylphenol), C_1 - and C_2 - phenols are about ten times as abundant as the monomer. In both cases, the sum of C_1 -, C_2 - and C_3 -phenols is substantially greater than the intensities of the monomers themselves.

Examination of the temperature dependence for evolution of the major peaks in Figures 5.1-1 and 5.1-2 suggests there are separate production routes for the monomers and the more highly fragmented phenolics, at least in the case of the poly(eugenol). Figures 5.1-3 and 5.1-4 show the abundance of the individual peaks as a function of temperature for the two polymers. In the case of poly(4-allylphenol) (Figure 5.1-3), the monomer and the C₁-phenol evolve at similar temperatures. On the other hand, in the case of poly(eugenol) (Figure 5.1-4), there are two peaks for the monomer (or its isomer, at m/z 164), both occurring well before methyl catechol (m/z 124), which peaks at about 400°C. The first of these peaks may be due primarily to traces of monomer in the polymer, but the second peak represents the evolution of a low molecular weight material at ca. 300°C, and is clearly the result of thermal degradation.

Preferred evolution of the monomers at lower temperatures than phenol and catechol is consistent with the expectation (Poutsma and Dyer, 1982; Gilbert and Gajewski, 1982; Gilbert, 1984; Squire et al., 1986) that depolymerization results from H-abstraction--β-scission chain processes, as depicted above in Scheme 1. The C₁- to C₃-phenols and catechols, on the other hand, do not have easily identifiable radical chain routes and would be expected to be rapidly evolved only at higher temperatures. Monomer evolution is expected to be more facile for poly(eugenol) because the methoxy group decreases the strength of the phenoxy-carbon bond in the C-C-O linkage by about 4 kcal/mol (Poutsma, 1987; Suryan, et al., 1989). All other things being equal (i.e., kinetic chain lengths and propagation rates), this decrease in bond strength would be expected to lower by about 150°C the temperature at which an equivalent decomposition rate is observed. As Figures 5.1-3 and 5.1-4 show, the second peak of monomer evolution in poly(eugenol) is about 100°C lower than for poly(4-allylphenol).

The mode of formation of the C₁- to C₃-catechols and phenols is even more puzzling than the distribution of eugenol and its oligomers. Possible routes to the C₁- to C₃-catechols could involve initial methyl-phenoxy cleavage, as the homolysis of the ca. 61 kcal/mol methyl-O bonds becomes rapid in the vicinity of 400°C. However, this suggestion is not consistent with the fact that the relative yield of C₁- and C₂-phenolics is actually greater for the poly(4-allylphenol), which has no methoxy group, nor with the fact that the evolution of methylphenols reaches its maximum at about the same temperature for both the poly(eugenol) and the poly(4-allylphenol). It should be noted that, while only purely radical routes to the pyrolysis products in Scheme 1 were considered, this does not rule out the potential role of reductive electron transfer followed by radical anion cleavage of the ether linkage. In fact, the difficulty in accounting for the relative abundance of the various peaks in terms of purely radical reactions may be indicating significant

Figure 5.1-3. Thermal Evolution of Cresol and Monomer from Poly(4-allylphenol).

Figure 5.1-4. Thermal Evolution of Methyl Dihydroxybenzene and Monomer from Poly(eugenol).

intervention by electron-transfer processes. A concerted reaction (a retro-ene elimination) is also possible, but the preponderance of evidence in the literature at this time suggests that even for favored structures, like phenyl phenethyl ether, concerted reactions are less important than radical chain processes, particularly under condensed phase conditions which tend to favor radical chain over molecular elimination reactions. In any event, to move beyond the stage of speculation about alternatives to simple radical reaction pathways on the basis of the Py-FIMS data, it is necessary to eliminate the structural ambiguities for the poly(eugenol) and poly(4-allylphenol) that were discussed above.

C-C-C- Polymers - The Py-FIMS spectrum of the C-C-C polymer (Polymer III, R = H) is shown in Figure 5.1-5. This spectrum contrasts in several ways with those obtained for the C-C-O polymers. There is a roughly Gaussian distribution of molecular weights in the evolved volatiles, peaking about m/z 800. Thus there is less evidence of rapid crosslinking, which would have limited the molecular weight of the tars to monomers and dimers, as in the the poly(eugenol) and poly(4-allylphenol). In the mass range of 800, extensive dealkylation has produced a wide range of peaks differing by multiples of 14 mass units largely obscuring any sequence of oligomeric groups that may exist.

The temperature at which most these peaks evolved centers around 250°C, which is very low even for a radical chain thermolysis process. Thermolysis of 1,3-diphenylpropane at 250°C does not lead to any detectable quantities of products. Thus, one has to consider the possibility that what is observed is merely the evaporation of the starting polymer. Measurements with GPC indicated a No. Av. MW of about 1500, which is twice that observed by FIMS. A factor of two in MW discrepancy, particularly in the range of 1000 daltons is not large enough to warrant a categorical statement that some degree of depolymerization is taking place during FIMS analysis.

5.1.4 Liquefaction of C-C-O Polymers

The batch microautoclave liquefaction results for poly(eugenol) and poly(4-allylphenol), and for comparison, the results for a weakly linked (-O-C-) polymer and a sample of the Argonne Zap Lignite are shown below.

T = 32 T0 500 DEG C N AV MW=764 WT AV MW=855

Figure 5.1-5. FIMS Spectrum of the C-C-C Polymer, Poly(4-phenylene propylene).

PRODUCT YIELDS^a IN THE LIQUEFACTION OF MODEL POLYMERS

<u>Sample</u>	<u>Hexane-Solubles</u>	<u>Toluene-Solubles</u>	<u>Pyridine-Solubles</u>	<u>Toluene-Insolubles</u>	<u>Pyridine-Insolubles</u>	<u>Gas</u>
Poly(eugenol)	27	66	93	27	0	8
Poly(4-allylphenol)	1	52	96	44	0	5
Polymer VIII	85	96	100	4	0	3
Zap Lignite	14	28	46	62	50	5

^a The liquefaction tests were performed in a microautoclave reactor, using 9,10-dihydrophenanthrene as the solvent. The reactor was purged and sealed under N₂, and then immersed in a sand bath at 400°C for 30 minutes.

^b Polymer VIII is a linear polymer having the structure:

The hexane- and toluene-soluble conversions of the two C-C-O linked polymers are in the same order as the Py-FIMS volatilities (53 and 28%, respectively for the poly(eugenol) and the poly(4-allylphenol)). They are substantially harder to convert than the weakly bonded Polymer VIII, but in the case of the poly(eugenol), easier to convert than low-rank coal. The similarities and differences will be further considered in the Discussion Section.

5.1.5 Discussion

The fact that the pyrolysis products are dominated by lower oligomers and smaller fragments does not, by itself, indicate whether the crosslinks were pre-existing or were generated in the course of the thermal treatment. This question is, of course, central to both the characterization of the original polymers, and also to an understanding of their behavior under liquefaction and other conversion conditions. Comparison of the conversion of the two C-C-O linked polymers with the "conversion" of other three-atom-linked models, including phenyl phenethyl ether itself, shows the apparent rate of polymer conversion to be somewhat slower than expected. Gilbert and Gajewski report (1982) apparent rate parameters for phenyl phenethyl ether decomposition that correspond to a half-life at 400°C of about 2 h. In view of the fact that the linkages are somewhat weaker in both poly(4-allylphenol) and poly(eugenol) (McMillen and Golden, 1982; Suryan, et al., 1989), and that many fewer than half the linkages need to be broken to make either of these polymers, if linear, fully soluble in toluene, the observed lack of

complete conversion to toluene-solubles certainly supports the other indications of significant crosslinking at some stage. Additional batches of the poly(4-allylphenol) with phenol added during the synthesis to purposely terminate the growing polymer chains have shown evidence of double bond isomerization, termination of trifluoroacetate, and Hg-catalyzed crosslinking. NMR analysis does indicate that most of the linkages are the desired C-C-O bridges. Nevertheless a detailed understanding of liquefaction behavior awaits synthesis of polymers having the side reactions suppressed.

In general, the behavior of these two polymers is similar to the behavior of other polymeric models that are either crosslinked to begin with or are easily crosslinked during conversion and to the behavior of low-rank coals themselves, as previously discussed by Solomon and coworkers (Squire et al., 1986; Serio et al., 1988; Deshpande et al., 1988; Solomon, et al., 1990). Facile crosslinking limits the fragments that are released to mainly small units, rather than large segments of a linear polymer chain. In addition, the high yields of the dihydroxybenzenes and the cresols are quite similar to products generated during the pyrolysis (or liquefaction) of lignites and subbituminous coals (Serio et al., 1988; Deshpande et al., 1988; Solomon et al., 1990).

The behavior of the C-C-O polymers can be summarized by noting that they (1) have a linkage known to be highly reactive; (2) produce substantial monomer at temperatures lower than 350°C; (3) are nevertheless rather hard to fully convert to soluble or volatile products; and (4) have as their most abundant pyrolysis products those same alkylated phenols and catechols which tend to dominate the pyrolysis products of lignites and subbituminous coals. In other words, these polymers bear a rather curious similarity to low-rank coals given the limited range of structures in the original polymer. Thus it appears that these polymers containing C-C-O linkages may represent appropriate structures for further use in determining the chemical details (and therefore what controls) the facile retrograde reactions of low-rank coals.

It is important to remember that these studies are an attempt to make a bridge between monomeric model compound studies, where establishing with certainty the structure of the starting material is often trivial, and the studies of real coals, where it is impossible. If one wishes to move from bibenzyl or diphenylmethane, which is understood rather well, but which basically do not behave much like real coals, then some pillars have to be put down in currently unknown waters. This study is the first attempt to determine the behavior of structurally defined polymeric models containing lignin-like linkages, but not containing the lignin functional groups known not

to persist into coals. Although many difficulties in synthesis and analysis have limited the amount of information that could be derived from the present study, the approach that was taken is believed to be appropriate to learning more about the structure of coal-like materials.

5.2 - Task 3 - Studies with Coals and Modified Coals

5.2.1 Coal Characterizations

The starting samples were characterized by the following procedures: TG-FTIR to determine proximate analysis, condensable product yield, gas yields, etc.; mineral analysis and spatial distribution by the SEM/ x-ray microanalysis; quantitative FT-IR analysis of minerals and functional groups; pyrolysis - FIMS analysis of molecular weight distributions of condensable products; and solvent swelling to determine the extractables content and the crosslink density.

Characterization of Methylated Coals - Initial experiments on the methylation of coals using Liotta's (1979) procedure were conducted with PSOC 1098, an Illinois No. 6 coal. Subsequent experiments were conducted with the Argonne Wyodak coal and the Argonne Beulah Zap Lignite. Several techniques were used to assess the degree of alkylation. In contrast to literature reports, it was found that the titrimetric estimation of active hydrogens was very difficult because of the absence of clear end points. Infrared analysis (KBr Pellet, transmission mode) showed a distinct decrease in the % transmission in the OH region. However, the OH band was not eliminated. Elemental analysis of the methylated Illinois No. 6 coal showed that about 5 additional carbons were added for every 100 carbons. This result suggests that nearly all the hydroxyls were methylated.

Methylated Wyodak coal showed a very substantial decrease in the OH intensity, although the peak was not completely eliminated. The elemental analysis of the starting coal (dried) and the once methylated derivative gave the following compositions, assuming constant oxygen:

Starting Coal:	$C_{100}H_{72}O_{25}N_{1.4}$
Once Methylated:	$C_{116}H_{102}O_{25}N_{1.6}$

Every OH group that is methylated should result in an increase of one carbon and two hydrogen atoms. The observed increase in hydrogen (30) matches closely with that in carbon (16). If the slight increase in nitrogen is to be ascribed to remaining tetrabutylammonium ions, the number of O-methyls introduced reduces from 16 to 12.

Methylation of the Argonne Zap lignite was also attempted. The IR spectrum of the product showed a much larger amount of residual OH intensity as compared with the Wyodak. Elemental analysis also showed a disproportionately large increase in carbon and nitrogen. It was suspected that not all of the tetrabutylammonium ion was removed during the aqueous wash and perhaps more than one methylation step may be necessary for lignites. The product was subjected to a second methylation and a second batch of Zap lignite was methylated using a longer alkylation period and a more extensive wash to remove excess alkylammonium salt.

The elemental analysis data for the methylation of the three coals were re-examined in order to assess the degree of uncertainty in calculating the number methyl groups introduced. The calculation is based on the reasonable assumption that the number of oxygen atoms has not changed during methylation and so one calculates the atomic composition from the elemental analysis data keeping the number of oxygen atoms in the methylated coal the same as that calculated for the raw coal on 100-carbon basis. **However, there are factors such as incorporation of tetrabutylammonium ion, C-methylation, loss of water, and loss of CO₂, which complicate the derivation. There are also uncertainties in the elemental analysis data.** Because each N is associated with 16 C in the tetrabutylammonium ion, even variations in the N value that are within the range of instrumental uncertainty can translate into several methyls. Thus, the overall precision of calculating methyls from elemental analysis has these inherent limitations. In view of these limitations, all three (dried) coals and their respective methylated products (the final large-scale preparations), were reanalyzed at Huffman Laboratories; oxygen content was determined by direct analysis. The results are shown in Table 5.2-1. In the following paragraphs, the possible impact of each of the complicating factors is discussed.

Incorporation of Tetrabutylammonium ion - Adduction of tetrabutylammonium ion could be due to excess free hydroxide, but this scenario is not likely given the extensive water wash following the methylation. Use of methanol has been suggested, but any remaining methanol would also affect the analysis. The formation of tetrabutylammonium salts of the phenolic and/or carboxylic functions in the coal that did not get methylated provide an

TABLE 5.2-1 - ELEMENTAL ANALYSIS OF RAW AND METHYLATED COALS

	Wyodak		Lignite		Illinois No. 6	
	<u>Raw^{1,2}</u>	<u>Methylated</u>	<u>Raw^{1,2}</u>	<u>Methylated</u>	<u>Raw^{1,2}</u>	<u>Methylated</u>
C	67.71	70.99	64.69	68.86	65.25	65.77
H	5.10	5.89	4.68	5.44	4.63	5.29
O	19.33	17.67	23.29	20.04	9.97	8.82
N	1.00	1.12	0.97	1.13	1.22	1.36
S	0.51	0.34	0.54	0.58	4.20	4.49
Ash	8.42	4.29	8.99	4.42	14.63	13.09

1 Dried to constant weight under high vacuum at 60°C.

2 Average of duplicate runs. Typical variance for C, H, and O was about 2%, variance was less 1% for N.

opportunity for N-adduction that would be more resistant to removal by aqueous washing. Table 5.2-2 gives the changes in the elemental composition resulting from methylation when calculated keeping the number of oxygen atoms in the derivatized coal the same as those for 100 C in the starting coal.

**TABLE 5.2-2 - CALCULATED CHANGES IN THE ATOMIC COMPOSITION
DUE TO METHYLATION**

<u>Coal</u>	Keeping O Constant			Then Correct for ΔN	
	<u>ΔC</u>	<u>ΔH</u>	<u>ΔN</u>	<u>ΔC</u>	<u>ΔH</u>
Wyodak	15	24	0.28	10	13.0
Ill. No. 6	14	24	0.42	7	9.4
Zap Lignite	24	30	0.45	16	14.0

As can be seen, the ΔN values are positive in all cases ranging between 0.28 and 0.45. If it is assumed that the excess nitrogen is strictly due to the tetrabutylammonium ions, then a ΔN value of 0.2 implies an overestimate of the ΔC by 3.2. Table 5.2-2 also gives the ΔC and ΔH values when correction is made for N-incorporation. As can be seen, this correction can be severe and skew the $\Delta H/\Delta C$ ratio.

Variations in Moisture Content - To the extent that moisture content affects the direct oxygen determination, differing extents of moisture in the raw and derivatized coal could give misleading results. To minimize errors from moisture variations, all coals should be thoroughly dried before submitting them for elemental analysis. The raw and methylated samples were generally dried in vacuum (< 0.05 torr) at 60°C to constant weight, which typically required several days. Weight loss was followed for several coals and, although the different coals displayed varying kinetics of drying, they all showed minimal change after drying for 16 h at 60°C under vacuum. The variations in moisture content are expected to have the largest impact on low rank coals which have high initial moisture contents. During alkylation and subsequent work up, the coal experiences significantly harsher conditions such that the alkylated coal could have less moisture than dried raw coal even though they were both dried under nominally the same conditions. Another factor that could contribute to the difference is that the methylated coal will be less hydrophilic than the raw coal and hence more easily dried. One can correct for

the moisture content, if it is assumed that there is no change in either nitrogen or sulfur content. However this calculation is not very accurate because, as mentioned above, the N content could increase due to adduction of tetrabutylammonium ion, and because the S content is so low that errors in its analysis have an unduly large leverage. If the calculation is based on the N-value, then one must decide whether to first correct for moisture variations or for N-adduction. The final results are different and therefore some judgement has to be exercised in deciding which factor is the more important one.

C-Alkylation - Stock and coworkers have shown that some C-alkylation also occurs during methylation under basic conditions. This complication will result in erroneous estimation of the methyls introduced. However, C-alkylation is generally more pronounced in high rank coals. In the present study with Zap lignite, Wyodak, and Illinois No. 6 coals, it is believed that C-alkylation would be minimal and not warrant any corrections.

CO₂ Loss - As with water loss, correction for any CO₂ loss during alkylation can be calculated only if one assumes fixed N or fixed S content. As discussed above, the impact of these corrections can be very large because of the large leverage exerted by S or N.

Summary - After examining all data, the conclusion is that calculating the number of methyls introduced is not straightforward. In Table 5.2-3 the ΔC and ΔH results are given after first correcting for variations in moisture content and then correcting for N-adduction.

TABLE 5.2-3 - CALCULATED CHANGES IN THE ATOMIC COMPOSITION DUE TO METHYLATION

<u>Coal</u>	<u>Keeping O Constant</u>			<u>Directly Correct for Variations in Moisture</u>			<u>Then Correct for N-Adduction</u>	
	<u>ΔC</u>	<u>ΔH</u>	<u>ΔN</u>	<u>ΔC</u>	<u>ΔH</u>	<u>ΔN</u>	<u>ΔC</u>	<u>ΔH</u>
Wyodak	15	24	0.28	11	20	0.23	6.9	11.4
Ill. No. 6	14	24	0.42	10	21	0.35	4.4	8.1
Zap Lignite	24	30	0.45	12	20	0.29	7.6	9.0

Note that the $\Delta H/\Delta C$ ratio after the correction is close to 2.0 only in the case of the Illinois No. 6 coal.

SEM/X-Ray Analysis - The results of the x-ray analysis of the ion-exchanged, demineralized and methylated samples confirmed that the concentrations of ion-exchangeable metal cations (Ca, Mg, Na, K) were significantly reduced as shown in Table 5.2-4. It is evident that the Zap and the Wyodak coals have higher concentrations of Ca and Mg which are often ion-exchanged on carboxyl groups in high oxygen coals. It is not clear why the Ca content of the demineralized Zap lignite was higher than for the ion-exchanged Zap lignite. Neither the ion-exchange procedure or the methylation procedure had as much effect on the clay material (Al, Si) as the demineralization procedure.

TG-FTIR Analysis - The results of TG-FTIR analysis of the raw, ion-exchanged, demineralized and methylated Zap lignite are shown in Figures 5.2-1 and 5.2-2. Each figure shows differential and integral plots for the major volatile species. An integral plot for the overall weight loss (labeled "Balance") is included as the first plot in each figure, along with the time-temperature profile and the sum of the gases measured by FT-IR (labeled "Sum"). The standard analysis includes a short (~ 5 min) drying period at 150°C. The main differences are seen in the yields of tar and CO₂, which have been identified previously (see Section 2.2) as key indicators of the extent of crosslinking. The CO₂ yields were lower for the ion-exchanged, demineralized, and methylated Zap lignite when compared to the raw coal. The corresponding tar yields are higher.

The results of TG-FTIR analysis of the raw, ion-exchanged, demineralized and methylated Wyodak subbituminous coal are shown in Figs. 5.2-3 and 5.2-4. The corresponding plots for the Illinois No. 6 bituminous coal are shown in Figs. 5.2-5 and 5.2-6. The trends for the Wyodak subbituminous coal are very similar to the Zap lignite. The main differences are seen in the yield of tar, which has been identified previously (Solomon, et al., 1988; Serio, et al., 1990) as a key indicator of the extent of crosslinking. The differences in the CO₂ (and CO and H₂O) yields are primarily in the shape of the evolution profile rather than the overall yield. An early CO₂ feature that was present for the raw and ion-exchanged Wyodak and Zap was absent in the demineralized and methylated samples. The corresponding tar yields are higher for the latter coals. From these results, one can infer that the amount of crosslinking decreases in the order methylated < demineralized < ion-exchanged < raw for the two low rank coals. However, the

TABLE 5.2-4 - MINERAL COMPONENTS OBTAINED FROM SEM X-RAY MICROANALYSIS OF
RAW, ION-EXCHANGED, DEMINERALIZED, AND METHYLATED COALS

	Illinois #6				Beulah Zap				Wyodak			
	<u>Raw</u>	<u>Ion- Exchanged</u>	<u>Demin.</u>	<u>Methyl</u>	<u>Raw</u>	<u>Ion- Exchanged</u>	<u>Demin.</u>	<u>Methyl</u>	<u>Raw</u>	<u>Ion- Exchanged</u>	<u>Demin.</u>	<u>Methyl</u>
Na	0.04	0.00	0.00	0.12	0.32	0.00	0.00	0.00	0.00	0.00	0.00	0.01
Mg	0.07	0.00	0.02	0.02	0.35	0.05	0.11	0.03	0.23	0.01	0.03	0.10
Al	1.23	0.71	0.34	0.45	0.33	0.39	0.19	0.22	0.55	0.50	0.05	0.35
Si	2.60	1.83	0.00	1.00	0.38	0.40	0.02	0.45	0.66	0.63	0.05	0.59
K	0.18	0.11	0.03	0.02	0.02	0.01	0.00	0.00	0.01	0.01	0.00	0.00
Ca	0.63	0.05	0.04	0.02	1.09	0.06	0.37	0.02	1.09	0.11	0.04	0.01
Ti	0.08	0.04	0.03	0.01	0.03	0.02	0.00	0.02	0.07	0.07	0.00	0.01
S(o)	1.48	1.36	1.57	0.42	0.30	0.28	0.33	0.21	0.36	0.38	0.35	0.14
S(m)	1.54	1.65	0.86	0.22	0.39	0.37	0.12	0.19	0.19	0.08	0.13	0.10
Fe*	0.47	0.30	0.22	0.03	0.17	0.14	0.07	0.01	0.20	0.20	0.01	0.00
Ash	13.17	8.06	1.12	3.66	6.86	2.50	1.80	1.72	6.44	3.11	0.30	2.27

*Non-Pyritic Iron

Figure 5.2-1. TG-FTIR Analysis of Zap Lignite.

Figure 5.2-2. TG-FTIR Analysis of Zap Lignite.

Figure 5.2-3. TG-FTIR Analysis of Wyodak Subbituminous Coal.

Figure 5.2-4. TG-FTIR Analysis of Wyodak Subbituminous Coal.

Figure 5.2-5. TG-FTIR Analysis of Illinois No. 6 Bituminous Coal.

Figure 5.2-6. TG-FTIR Analysis of Illinois No. 6 Bituminous Coal.

results for the Illinois coal are not significantly different for the various pretreatments when compared to the raw coal, as shown in Figs. 5.2-5 and 5.2-6.

FIMS Analysis - Pyrolysis - FIMS analyses were done at SRI of the raw coals and modified coals. The results for the three coals are shown in Figs. 5.2-7 to 5.2-9. These can be compared to FIMS analyses of the raw coals done previously at SRI for AFR under a different contract. The latter two treatments modify the FIMS spectra of the two lowest rank coals to make them appear more like bituminous coals (higher average molecular weight). These trends are consistent with the increased tar yields in pyrolysis and the increased liquids yields in the liquefaction experiments. All of these trends indicate a reduced extent of crosslinking (retrograde) reactions.

FT-IR Analysis - Quantitative analysis of the raw coals and modified coals was done using a KBr Pellet method described in Section 4.3.2. The results are given in Appendix A. The results show the expected changes in the hydroxyl content and mineral content with the various modifications.

5.2.2 Liquefaction Experiments

After the samples were characterized, experiments were done under coal liquefaction conditions in microautoclave reactors. A schematic of the experimental system is shown in Figure 4.4-1. One liquefaction solvent was used (dihydrophenanthrene) with two degrees of hydrogenation (pure in a 50/50 mixture with phenanthrene). The yields of toluene solubles, pyridine solubles, residue, and gas were routinely determined. For selected experiments, the gas, liquids, and the solid products were subjected to more detailed characterization by the same techniques used for the starting materials.

Experiments in Pure Solvent (DHP) - The results of liquefaction experiments with the coals and modified coals in pure DHP at 400°C, 30 min. are given in Tables 5.2-5 and 5.2-6 for the liquid and gas products, respectively. The results show that the decrease in crosslinking, as implied by the reduction in CO₂ yield, roughly correlates with the increased liquefaction yields based on the toluene solubles. **The trends in CO₂ yield and toluene solubles from liquefaction parallel the results for CO₂ yield and tar yield, respectively, determined from pyrolysis in the TG-FTIR analysis.**

**TABLE 5.2-5 - SOLUBLE AND INSOLUBLE PRODUCT YIELDS FROM LIQUEFACTION EXPERIMENTS
WITH COALS AND MODIFIED COALS IN PURE DHP**

(All Yields in DAF Weight Percent)

Exp. #	Coal (Type/Preparation)	Toluene Solubles		Toluene Insolubles	Pyridine		Gas	V.S.R. of Coal	DAF% Pyridine Extract of Coal
		Total	Oils		Solubles	Insolubles			
North Dakota Lignite									
24	fresh	26	12	69	38	57	5.0	2.0	15
26	vacuum dry	15	4	78	29	64	7.2	2.7	5
15	ion-exchanged (old)	46	26	48	80	14	6.0	2.3	7
	ion-exchanged (new)	42	20	51	65	30	4.5	ND	ND
18	demineralized	52	23	46	88	9	2.1	3.0	10
21	methylated	54	30	42	76	21	3.5	2.4	40
Wyodak									
25	fresh	39	13	56	48	46	5.2	—	7
28	vacuum dry	56	11	62	45	50	4.7	2.7	11
17	ion-exchanged (old)	25	8	75	47	53	0.4	2.5	9
	ion-exchanged (new)	29	7	69	38	60	2.0	ND	ND
20	demineralized	56	23	43	97	2	1.5	3.1	18
23	methylated	62	27	32	89	4	6.5	1.6	53
Illinois No. 6									
6,8,13	fresh	47	17	52	98	1	0.9	—	27
27	vacuum dry	56	5	41	96	1	2.1	2.5	36
16	ion-exchanged (old)	22	5	77	82	17	1.0	2.5	19
	ion-exchanged (new)	53	22	46	99	0	1.3	ND	ND
19	demineralized	53	12	46	91	8	0.9	3.0	22
22	methylated*	67	33	30	100	0	3.0	1.7	48

Notes: Experimental conditions: 400°C, 30 min., 100% dihydrophenanthrene (DHP); 1 g coal, 4 g solvent

* PSQC 1098

ND = Not Determined

TABLE 5.2-6 - GAS PRODUCT YIELDS FROM LIQUEFACTION EXPERIMENTS
WITH COALS AND MODIFIED COALS IN PURE DHP

(All Yields in DAF Weight Percent)

Exp. #	Coal (Type/Preparation)	H ₂	CO ₂	CO	CH ₄	C ₂ H ₆	C ₂ H ₄	C ₂ H ₂	H ₂ S	CS ₂	E Yield %
North Dakota Lignite											
24	fresh	—	430	24	25	21	2.5	—	—	—	5.0
26	vacuum dry	—	641	31	30	20	6.2	—	—	—	7.3
15	ion-exchanged (old)	7.4	491	43	28	52	2.8	—	—	—	6.2
	ion-exchanged (new)	10.0	343	36	29	32	5.0	—	—	—	4.5
18	demineralized	3.6	120	24	24	34	7.9	—	—	—	2.1
21	methylated	2.2	185	31	115	17	3.1	—	—	—	3.5
Wyodak											
25	fresh	2.1	409	34	31	36	8.4	—	—	—	5.2
28	vacuum dry	8.7	332	31	20	27	6.2	—	3.7	40	4.7
17	ion-exchanged (old)	7.4	—	24	7	4	1.8	—	—	—	0.4
	ion-exchanged (new)	20	164	17	2	8	2.0	—	—	—	2.0
20	demineralized	5.6	97	19	6	20	5.4	—	—	—	1.5
23	methylated	112.6	219	39	247	29	6.0	—	—	—	6.5
Illinois No. 6											
6,8,13	fresh	3.9	35	2	16	31	4.6	—	—	—	0.9
27	vacuum dry	19.6	44	11	22	30	3.5	—	—	76	2.1
16	ion-exchanged (old)	4.6	73	6	5	13	2.1	—	—	—	1.0
	ion-exchanged (new)	19.0	25	7	8	21	5.0	—	—	—	1.3
19	demineralized	9.9	28	8	9	33	5.1	—	—	—	0.9
22	methylated	36.5	47	13	153	32	3.3	3.1	4.0	7	3.0

Notes: Experimental conditions: 400°C, 30 min., 100% dihydrophenanthrene (DHP); 1 g coal, 4 g solvent.

* PSOC 1098

Figure 5.2-7. Py-FIMS Analysis of Zap Lignite.

Figure 5.2-8. Py-FIMS Analysis of Wyodak.

Figure 5.2-9. Py-FIMS Analysis of Illinois No. 6.

The extent of retrograde reactions for low rank coals (lignite, subbituminous) is significantly reduced by methylation and demineralization. However, these treatments do not have much impact on bituminous coal. In general, ion-exchange has a modest positive impact for low rank coals while drying has a modest negative impact. Drying had little impact on the liquefaction yields from the bituminous coal, while the ion-exchange procedure had a modest negative impact, although this may have been from oxidation, as discussed below. In nearly all cases, the changes in the amounts of pyridine solubles by these pretreatments parallel the changes in the amounts of toluene solubles.

Experiments in Mixed Solvent - Liquefaction experiments were also done on samples of dried, methylated, demineralized, and ion-exchanged coals in 50/50 dihydrophenanthrene/phenanthrene (DPH/PH). A summary of the results is given in Table 5.2-7. In general, the results were similar to those observed in pure DPH, which were presented in Tables 5.2-5 - 5.2-6. The yields of toluene solubles and oils were generally lower with the lower amount of hydrogen donor (DHP). The yields of pyridine solubles were also generally lower, except for the Illinois No. 6 coal, where the yields were about the same. This makes sense since the Illinois coal has less oxygen, therefore less external hydrogen is required to make up for the amount of coal hydrogen that is "wasted" in forming H_2O or in disrupting oxygen crosslinks.

One surprise was the fact that the toluene and hexane solubles yields for the dried Wyodak coal in mixed solvent were significantly higher than for the raw coal. Similarly, the hexane solubles yield for the Zap lignite was essentially zero for the mixed solvent experiments. The hexane solubles yields are determined by difference and are subject to some variation.

Experiments with Ion-Exchanged Samples - A second group of ion-exchanged samples were prepared for each of the three coals under anaerobic conditions. This work was done under our other contract (Fundamental Studies of Water Pretreatment of Coal, Contract No. DE-AC22-89PC89878), while the liquefaction experiments with these samples were done under the current contract. The results are included in Tables 5.2-5 to 5.2-8. The reason for preparing a second group of samples was the idea that the coals may have been partially oxidized during the first procedure. The yields for the toluene solubles and pyridine solubles from the liquefaction experiments for the Zap and Wyodak coals are similar, indicating that whatever oxidation may have occurred was mild or that low rank coals are not as sensitive. However, in the case of the Illinois No. 6 coal, which would be most sensitive to oxidation, the yields of toluene solubles and pyridine solubles were significantly higher, suggesting that oxidation had

TABLE 5.2-7 - LIQUID AND GASEOUS PRODUCT YIELDS FROM LIQUEFACTION EXPERIMENTS
WITH COALS AND MODIFIED COALS IN MIXED SOLVENT

(All Yields in DAF Weight Percent)

Coal Preparation	T _s Total	T _s Oils	T _i	P _s	P _i	Gas	D _H	H ₂	CO ₂	CO	CH ₄	C ₂ H ₆	C ₂ H ₄	C ₂ H ₂	H ₂ S
Zap															
fresh	28	12	68	46	50	4.6	ND	0.00	4.07	0.23	0.18	0.02	0.13	0	0
vacuum dry	33	14	62	47	47	5.5	ND	0.00	5.02	0.25	0.11	0.02	0.11	0	0
ion-exchanged (old)	30	15	65	51	44	4.8	ND	0.00	4.28	0.31	0.09	0.02	0.09	0	0
ion-exchanged (new)	29	14	65	62	34	4.2	0.040	0.11	3.54	0.25	0.09	0.15	0.03	0	0
demineralized	39	27	57	85	11	4.0	ND	0.00	3.01	0.41	0.27	0.03	0.29	0	0
methylated	49	0	46	84	12	4.5	ND	0.00	2.95	0.33	1.04	0.03	0.19	0	0
Wyodak															
fresh	4	0	95	20	78	1.6	0.072	0.00	1.47	0.08	0.00	0.00	0.00	0	0
vacuum dry	39	15	57	54	42	3.9	0.030	0.01	3.32	0.28	0.07	0.18	0.03	0	0
ion-exchanged (new)	17	2	81	44	54	2.0	0.037	0.01	1.83	0.09	0.01	0.06	0.02	0	0
demineralized	13	2	85	49	49	2.1	0.042	0.00	1.96	0.11	0.03	0.01	0.00	0	0
methylated	56	23	39	89	6	5.1	0.033	0.01	2.44	0.57	1.60	0.41	0.07	0	0
Illinois No. 6															
fresh	19	0	76	94	0	5.7	0.051	0.02	0.34	0.03	0.02	0.11	0.00	0	0.05
vacuum dry	35	6	63	83	15	2.0	0.028	0.02	0.36	0.06	0.03	0.16	0.03	0	0.35
ion-exchanged (new)	37	23	62	99	0	0.8	0.035	0.06	0.22	0.05	0.02	0.12	0.02	0	0.31
demineralized	32	13	66	97	1	1.8	0.046	0.02	0.51	0.13	0.05	0.30	0.02	0	0.75
methylated*	38	0	40	98	0	1.9	0.047	0.01	0.22	0.09	1.10	0.13	0.02	0	0.38

Notes:

Experimental conditions: 400°C, 30 min, 1g coal, 2g DHP, 2g P

* PSOC 1098

T_s = Toluene Solubles

T_i = Toluene Insolubles

P_s = Pyridine Solubles

P_i = Pyridine Insolubles

D_H = Hydrogen Transfer Index = 2ΔDHP/180/T_s

ND = Not Determined

occurred. Based on this result, it can be concluded that the ion-exchange procedure (using ammonium acetate) does not have a negative impact on the yields from liquefaction of Illinois No. 6 coal. The conclusion that the yields from the low rank coals (Zap, Wyodak) are moderately improved, still stands.

Experiments at Short Times - Liquefaction experiments at short times (10 minutes) were also completed for all the coals and coal modifications. These were done in pure DHP. The detailed results are given in Table 5.2-8. The results at 10 minutes indicated very different behavior when compared to the results at 30 minutes, depending on the coal type and the modification. Some of the experiments with the raw coals had to be repeated and as a result of problems with the temperature control system. The results of the repeats of the 10 minute experiments with the three raw coals have been included in Table 5.2-8 (replacing the original set of 10 minute data). The results from the first set of experiments were affected by the deterioration of the heating elements in the fluidized sand bath (which was rebuilt) and were not used.

There is still more variation with the 10 minute experiments than with the 30 minute experiments (± 3 wt.%). This is likely due to the fact that the former experiments are more sensitive to temperature fluctuations. The short time experiments would also be more sensitive to mass transfer effects. For this reason, the liquefaction system was subsequently modified to allow the reactor to be shaken during the experiment (see below). This allowed the assessment of the presence of heat and/or mass transport effects which may be important, particularly in the short contact time experiments.

In general, for all three coals the yields of soluble products for the raw and dried coals at 10 minutes were much less than 50% of the values at 30 minutes. This indicates that the liquefaction process in our system increases slowly to the final product yields rather than immediately. In the case of the chemically modified coals (ion-exchanged, demineralized, methylated), the soluble product yields at 10 minutes were generally much closer to 50% of the 30 minute values. This result suggests that these modifications "loosen" the coal structure. In the case of the gas yields, the relative trends were much different and highly coal dependent. In general, the CO_2 yields appear to approach their 30 minute values much more rapidly than the CH_4 or CO yields. Surprisingly, for the experiments with demineralized Zap and demineralized Wyodak, the CO_2 yields at 10 minutes were higher than at 30 minutes, suggesting that CO_2 is consumed by a reaction, perhaps the water-gas shift.

TABLE 5.2-8 - LIQUID AND GASEOUS PRODUCT YIELDS FROM LIQUEFACTION EXPERIMENTS
IN PURE DHP DONE AT SHORT TIMES (10 MIN.)

(All Product Yields are DAF wt.%)

Coal Preparation	T _s Total	Oils	T _i	P _s	P _i	Gas	D _H	H ₂	CO ₂	CO	CH ₄	C ₂ H ₆	C ₂ H ₄	C ₂ H ₂	H ₂ S
Zap															
fresh	11	9	87	19	79	2.1	0.055	0.00	1.99	0.08	0.00	0.00	0.00	0.00	0.00
a)															
b)	7	4	90	21	77	2.5	—	0.03	2.29	0.15	0.00	0.01	0.00	0.00	0.00
vacuum dry	9	7	89	16	82	2.4	0.041	0.02	2.24	0.13	0.01	0.01	0.00	0.00	0.00
ion-exchanged (new)	22	1	76	53	45	2.5	0.038	0.01	2.24	0.14	0.03	0.06	0.01	0.00	0.00
demineralized	14	1	84	43	56	2.6	0.061	0.03	2.31	0.19	0.01	0.04	0.00	0.00	0.00
methylated	23	9	76	59	40	1.1	0.015	0.00	0.99	0.07	0.05	0.00	0.00	0.00	0.00
Wyodak															
fresh	11	7	89	24	76	0.7	0.034	0.00	0.65	0.03	0.00	0.00	0.00	0.00	0.00
a)															
b)	17	10	81	43	54	2.5	0.058	0.03	2.26	0.12	0.00	0.06	0.00	0.00	0.00
vacuum dry	2	0	97	15	85	0.8	0.087	0.00	0.76	0.03	0.00	0.00	0.00	0.00	0.00
ion-exchanged (new)	2	0	97	10	89	0.6	0.067	0.00	0.61	0.03	0.00	0.00	0.00	0.00	0.00
demineralized	24	16	74	58	40	2.5	0.030	0.03	2.20	0.21	0.03	0.07	0.00	0.00	0.00
methylated	31	11	68	88	11	1.2	0.014	0.03	0.88	0.09	0.16	0.05	0.00	0.00	0.00
Illinois No. 6															
fresh	12	5	88	62	38	0.1	0.033	0.00	0.08	0.00	0.00	0.00	0.00	0.00	0.06
a)															
b)	12	3	88	80	19	0.4	0.066	0.02	0.27	0.02	0.06	0.00	0.07	0.01	0.00
vacuum dry	10	3	89	46	54	0.4	0.022	0.00	0.05	0.00	0.00	0.06	0.00	0.32	0.00
ion-exchanged (new)	27	15	72	95	4	0.7	0.023	0.03	0.13	0.02	0.00	0.06	0.01	0.00	0.47
demineralized	10	1	89	11	89	0.2	0.029	0.00	0.16	0.01	0.00	0.00	0.00	0.00	0.06
methylated	34	14	65	95	4	1.3	0.025	0.09	0.15	0.03	0.61	0.11	0.01	0.00	0.34

Notes: Experimental conditions: 400°C, 10 min.,
100% DHP, 1 g coal, 4 g solvent

T_s = Toluene Solubles
T_i = Toluene Insolubles
P_s = Pyridine Solubles
P_i = Pyridine Insolubles
D_H = Hydrogen Transfer Index = 2ΔDHP/180/T_s

Experiments with Reactor Shaking - Experiments were done at 10 minutes with raw Zap lignite coal at 400°C in pure dihydrophenanthrene with the added feature of shaking the reactor during the experiment. The results are summarized in Table 5.2-9. The toluene solubles yields were significantly higher than without shaking, which suggests the yields from the 10 minute experiments (without shaking) are limited by mass transport. This is consistent with the fact that the FG-DVC liquefaction model overpredicts the yields at 10 minutes for the latter experiments (see Section 5.3). There was a relatively larger increase in the toluene soluble fraction than in the oil fraction.

Experiments were also done at 30 minutes with raw Zap lignite coal at 400°C in pure dihydrophenanthrene with the added feature of shaking the reactor during the experiment. As in the case of the 10 minute experiments, the solubles yields were higher with shaking. However, the differences were not as great, which confirms our hypothesis that the results for the longer reaction times are not as sensitive to mass transfer effects. At both long and short times, the yields of toluene solubles and pyridine solubles were more sensitive to the presence or absence of shaking than the yields of oils.

Experiments at Higher Temperatures - Some liquefaction experiments were done at a higher temperature (425 vs 400°C) and a shorter time (10 min. vs 30 min.) on both raw and demineralized Zap and Wyodak coals. This was done to see if the improvements in liquefaction yields by demineralization were comparable to those obtained by catalytic pretreatment using the technique of Derbyshire and coworkers (1986). A summary of the results is given in Table 5.2-10. **Under these conditions, the improvement in the yield of chloroform solubles for the Wyodak coal by demineralization was about 14%, which is comparable to the approximately 17 wt.% improvement obtained by catalytic pretreatment.** On an absolute basis the improvement was smaller in the case of demineralized Zap (11 wt.%). However, on a percentage basis, this represented about a factor of 2 increase in the yield of chloroform solubles, which was greater than for the case of the Wyodak coal.

The column labeled D_H in Table 5.2-10 is an index of the amount of hydrogen transferred from the DPH normalized by the amount of toluene solubles formed. This index does not appear to be very sensitive for the coal type or coal modification.

Experiments with Calcium Exchanged Coals - It was believed that the improved liquefaction yields from demineralized low rank coals were primarily the result of removal of

**TABLE 5.2-9 - COMPARISON OF PRODUCT YIELDS WITH AND WITHOUT SHAKING OF THE REACTOR
FROM LIQUEFACTION OF ZAP LIGNITE IN PURE DHP**

(All Yields in DAF Weight Percent)

Zap	<u>T_s</u>			P _s	P _i	Gas	D _H ^{Ts}	H ₂	CO ₂	CO	CH ₄	C ₂ H ₆	C ₂ H ₄	C ₂ H ₂	H ₂ S
	Total	Oils	T _i												
10 minutes without shake	11.2	7.8	86.4	18.6	79.3	2.1	0.055	0.00	2.00	0.08	0.00	0.00	0.00	0.0	0.0
10 minutes with shake	24.2	9.5	72.0	35.6	60.6	3.9	0.049	0.02	2.10	0.13	0.17	0.01	0.07	0.0	0.0
30 minutes without shake	25.9	11.8	69.1	38.3	56.7	5.0	0.051	0.00	4.30	0.24	0.35	0.21	0.03	0.0	0.0
30 minutes with shake	35.8	13.6	56.7	43.9	48.6	7.5	0.056	0.97	5.59	0.28	0.24	0.33	0.10	0.0	0.0

Notes: Experimental Conditions = 400°C, 100% DHP, 1 g coal, 4 g solvent

T_s = Toluene Solubles

T_i = Toluene Insolubles

P_s = Pyridine Solubles

P_i = Pyridine Insolubles

D_H = Hydrogen Transfer Index = 2 Δ DHP/180/T_s

**TABLE 5.2-10 - LIQUEFACTION RESULTS IN DIHYDROPHENHTHRENE
FOR RAW AND DEMINERALIZED ZAP AND WYODAK COALS AT HIGH TEMPERATURES
(425°C) AND SHORT TIMES (10 MIN.)**

<u>Coal Type</u>	DAF wt. %					10 ⁻² DAF wt. %							
	<u>T_s</u>	<u>T_{is}</u>	<u>Chl_s</u>	<u>Chl_{is}</u>	<u>Gas</u>	<u>D_H^{Ts}</u>	<u>H₂</u>	<u>C₂H₆</u>	<u>C₂H₄</u>	<u>CH₄</u>	<u>H₂S</u>	<u>CO₂</u>	<u>CO</u>
Zap	6	93	7	92	1.4	.04	0	0	0	0	0	138	0
Zap Demin.	15	82	18	79	2.7	.04	0	2	1	4	0	228	13
Wyodak	37	61	43	54	2.4	.03	1	8	0	6	0	221	9
Wyodak Demin.	54	40	57	37	5.8	.04	99	77	8	48	2	381	68

Notes: Experimental Conditions: 425°C, 10 min., 100% DHP, 1 g coal, 4 g solvent.

T_s = Toluene Solubles
T_{is} = Toluene Insolubles
Chl_s = Chloroform Solubles
Chl_{is} = Chloroform Insolubles
D_H = 2 Δ DHP/MW/T_s
 MW = 180

exchanged metal cations (principally calcium, which is the most abundant). This conclusion is based on the evidence that calcium addition depresses the tar yields from pyrolysis experiments (see Section 2.2) and the close correlation of pyrolysis tar and solubles yields that have been observed in this study. In order to test this hypothesis, samples of Argonne Zap lignite were loaded with calcium following either a mild (HCl) acid wash or a standard HCl/HF demineralization. The results from TG-FTIR analysis of the samples are given in Table 5.2-11. As expected, the addition of calcium reduces the tar yield and increases the CO₂ evolution. The same samples were subjected to liquefaction experiments at 30 minutes, 400°C, 100% DPH, with shaking.

The results from the liquefaction experiments calcium loaded coals are summarized in Table 5.2-12. It was found that calcium loading of a HCl/HF demineralized coal did not have a negative effect on liquefaction yields but that calcium loading of a mild acid-washed coal did have a negative impact. This is not entirely consistent with the corresponding effects on the pyrolysis tar yields. Apparently, the severe (HCl/HF) demineralization process changes the coal to the extent that the calcium cannot be put back on in the same manner.

Summary of Liquefaction Results - The liquefaction results for the baseline experiments at 30 minutes, 400°C, pure DHP and for additional experiments in mixed solvent (50/50 DHP/P) and at shorter times (10 minutes) are summarized in Figures 5.2-10 to 5.2-18 for the three coals. The most general conclusion that can be made is that for the two low rank coals (Zap, Wyodak), the solubles yields are enhanced for the demineralized and methylated coals under all three conditions. There is a corresponding decrease in the CO₂ yield from liquefaction.

A comparison which shows the effects of the various coal modifications on the toluene solubles yields (from 30 min. liquefaction in pure DHP) for the three coals is given in Fig. 5.2-19. This indicates the dramatic effects of demineralization and methylation on the two low rank coals. In Fig. 5.2-20, a comparison is made between the tar yields and the toluene solubles yields for the three coals. This indicates the strong correlation between liquid (tar) yields in pyrolysis and soluble product yields from liquefaction.

**TABLE 5.2-11 - RESULTS FROM TG-FTIR ANALYSIS OF DEMINERALIZED,
ACID-WASHED, AND/OR CALCIUM LOADED ZAP LIGNITE**

(All Yields In DAF Wt.% Unless Otherwise Indicated)

Zap	Tar	CH ₄	CO ₂	CO	H ₂ O	Ash (AF basis)
Demineralized	19	2.4	5.8	9.8	10.2	0.9
Demineralized C _a ²⁺ Loaded	10	2.4	9.0	12.1	17.0	2.7
Demineralized C _a ²⁺ Loaded Mild Acid Wash	15	2.3	6.3	10.1	14.8	1.1
Fresh	8	1.7	7.3	12.8	11.6	14.3
Mild Acid Wash	19	2.1	5.8	9.0	14.3	2.7
Mild Acid Wash C _a ²⁺ Loaded	12	2.2	7.4	12.3	14.7	8.9

TABLE 5.2-12 - LIQUID AND GAS PRODUCT YIELDS FROM LIQUEFACTION EXPERIMENTS WITH
DEMINERALIZED, ACID-WASHED, AND/OR CALCIUM LOADED ZAP LIGNITE

(All Product Yields are DAF wt.%)

Zap	Ts		T _i	P _s	P _i	Gas	D _H ^{Ts}	H ₂	CO ₂	CO	CH ₄	C ₂ H ₆	C ₂ H ₄	C ₂ H ₂	H ₂ S
	Total	Oils													
Demineralized	47	17	51	88	9	2.6	0.049	0.00	1.60	0.44	0.23	0.04	0.32	0.0	0.0
Demineralized Ca ²⁺ Loaded	56	24	38	81	14	6.0	0.036	9.12	4.72	0.41	0.33	0.06	0.37	0.0	0.0
Demineralized Ca ²⁺ Loaded Mild Acid Wash	56	31	39	87	8	5.1	0.030	0.13	4.26	0.30	0.19	0.02	0.24	0.0	0.0
Fresh	36	14	57	44	48	4.6	0.056	0.97	5.59	0.27	0.24	0.10	0.33	0.0	0.0
Mild Acid Wash	54	22	41	82	14	4.5	0.033	0.12	3.43	0.42	0.23	0.02	0.28	0.0	0.0
Mild Acid Wash Ca ²⁺ Loaded	41	19	54	62	32	5.4	0.043	0.00	4.48	0.38	0.25	0.00	0.34	0.0	0.0

Notes:

Experimental Conditions: 400°C, 30 min., 100% DHP, 1 g coal, 4 g solvent, with shaking

T_s = Toluene Solubles

T_i = Toluene Insolubles

P_s = Pyridine Solubles

P_i = Pyridine Insolubles

O_H = Hydrogen Transfer Index = 2 Δ DHP/180/T_s

Figure 5.2-10. Liquefaction Results for North Dakota Lignite at 400°C, 30 minutes, in DHP.

Figure 5.2-11. Liquefaction Results for Zap Lignite at 400°C, 30 minutes, P/DHP.

Figure 5.2-12. Liquefaction Results for Zap Lignite at 400C, 10 Minutes, Pure DHP.

Figure 5.2-13. Liquefaction Results for Wyodak Subbituminous Coal at 400°C, 30 Minutes, Pure DHP.

Figure 5.2-14. Liquefaction Results for Wyodak Subbituminous Coal at 400C, 30 Minutes, 50/50 P/DHP.

Figure 5.2-15. Liquefaction Results for Wyodak Subbituminous Coal at 400°C, 10 Minutes, Pure DHP.

Figure 5.2-16. Liquefaction Results for Illinois No. 6 Coal at 400°C, 30 minutes, Pure DHP.

Figure 5.2-17. Liquefaction Results for Illinois No. 6 Coal at 400°C, 30 minutes, 50/50 P/DHP.

Figure 5.2-18. Liquefaction Results for Illinois No. 6 Coal at 400C, 10 Minutes, Pure DHP.

Figure 5.2-19. Toluene Solubles Yields from Raw and Modified Coals.

Figure 5.2-20. Comparison of Toluene Solubles and Pyrolysis Tar Yields.

5.3 - Task 4 - Data Evaluation

5.3.1 Quantitative Modeling

Work was done using the AFR FG-DVC liquefaction model (Solomon, et al., 1989) to simulate the results of the experiments on coals and modified coals from this program. Some refinements were made of the liquefaction model concerning the mode of calculation of the soluble and insoluble products, which are now directly taken from the DVC model. The weight percent calculation of the "char" bin was improved by eliminating an approximation.

Model Assumptions - One of the first steps was to methodically examine the effects of the various model assumptions on the product distributions. Three sets of assumptions were examined: 1) similar to pyrolysis model with no external hydrogen provided; 2) allow for hydrogen donation from solvent; 3) same as 2) except all of the bonds are assumed to be breakable (no hard bonds). The last set of assumptions appears to give the best fit to our liquefaction results, as shown in Figure 5.3-1. The rationale for including no unbreakable bonds is based on work done at SRI International which demonstrates that donor solvents can cause strong bonds to break (Malhotra, et al., 1989).

Model Predictions - It was possible to estimate from pyrolysis measurements the kinetic rate of bond breaking for Illinois No. 6 coal with a high degree of accuracy. The rates of Zap and Wyodak were more difficult to obtain because the tar peak for the raw coals is dominated by olefins, paraffins, and polymethylenes. As a first approximation, it was decided to simulate the liquefaction behavior of all three coals using the exact coal composition and network configuration files derived from pyrolysis experiments and using a single kinetic rate for the breaking of weak bridges, i.e., the one derived for Illinois No. 6. The results showed an underprediction of the pyridine, toluene, and hexane solubles yields for all three coals, as shown in Figure 5.3-1 (case 2). To improve the predictions, it was decided to allow all the bridging bonds of the network to be broken, which is equivalent to saying that bonds that cannot be broken during pyrolysis can be broken during liquefaction. The 30 minute solubles predictions obtained with this assumption were good for Illinois No. 6, but still underpredicted for Zap and Wyodak. It was then decided to increase the bridge breaking rate of those two coals by a factor of two based on pyrolysis experiments performed on demineralized Zap which showed a higher rate. The tar peak from the demineralized coal is less influenced by the polymethylene species.

Figure 5.3-1. Effect of Liquefaction Model Assumptions on Toluene Solubles Predictions.

COMPARISON OF LIQUEFACTION MODEL PREDICTIONS WITH DATA FOR RAW COALS

Figure 5.3-2. Comparison of Liquefaction Model Predictions with Data for Raw Coals.

This last modification led to a good fit for the 30 minute solubles values for Zap and Wyodak. The results for all three coals are shown in Fig. 5.3-2. The 10 minute data seemed, however, to be overpredicted.

Simulations of modified (methylated, demineralized) coals, keeping the same composition and kinetic parameter files as for the fresh coals, except for adjusting the CO_2 , CH_4 and (initial) extractables amounts, predicted very well the 30 minute solubles values. The results for the demineralized and methylated coals are shown in Figs. 5.3-3 and 5.3-4, respectively. These simulations, however, also tended to overpredict the 10 minute data, except for the methylated coals where both 10 and 30 minute data are fairly well fitted.

A comparison of the model predictions to the liquefaction yields at 30 minutes is shown in Figure 5.3-5 for the toluene solubles. The agreement for both the raw and modified coals is quite good. The problem remained that the FG-DVC liquefaction model generally overpredicted the yields at short times, but was in good agreement with the 30 minute data. It was decided to simulate some literature data which included both time resolution and mixing. Good agreement was obtained with the data of Prasad et al. (1986) for two Australian coals which are similar to Illinois No. 6. These comparisons are shown in Fig. 5.3-6. The data were taken over a range of residence times from 100 to 3600 s and over a range of temperatures from 380 to 420°C. Equally good agreement was obtained with the data of Foster et al. (1985) on Liddell coal (similar to Pittsburgh No. 8) over a range of residence times from 100 to 1200 seconds and temperatures from 380 to 420°C. These comparisons are shown in Fig. 5.3-7. Consequently, the conclusion is that the yields from our 10 minute experiments are probably mass transfer limited. Some additional experiments were done with Zap lignite coal at 10 minutes and 30 minutes, with and without shaking. These data (discussed in Section 5.2, see Table 5.2-9) also support this conclusion.

A simulation was also made of the data of Derbyshire and Whitehurst (1981) on the conversion of coals of a wide range of ranks to pyridine solubles in a non-donor solvent system. The predictions followed the correct trend with rank but were somewhat lower, as shown in Fig. 5.3-8 (solid triangles). This would suggest that the model is not as good in non-donor solvent systems and/or there were some other conditions present in these experiments that the model does not account for.

Figure 5.3-3. Comparison of Liquefaction Model Predictions with Data for Demineralized Coals.

Figure 5.3-4. Comparison of Liquefaction Model Predictions with Data for Methylated Coals.

Figure 5.3-5. Predicted vs. Measured Toluene Solubles Yields for Raw and Modified Coals (30 minute, 400°C liquefaction in DHP).

Figure 5.3-6. Comparison of FG-DVC Liquefaction Model Predictions with Literature Data for Two Australian Coals. Data from Prasad et al. (1986).

Figure 5.3-7. Comparison of DFG-DVC Liquefaction Model Predictions with Literature Data for Liddell Coal. Data from Foster et al. (1985).

Figure 5.3-8. Coal Conversion to Pyridine Solubles in a Non-Hydrogen Donor Solvent. Figure Adapted from Derbyshire and Whitehurst (1981).

5.3.2 Mechanistic Modeling

Some possible chemical mechanisms for crosslinking are shown in Fig. 5.3-9. The first is the crosslinking which accompanies methane formation by ipso substitution reactions, shown in Figure 5.3-9a. This mechanism is believed to be responsible for the reduction in fluidity for softening coals (Solomon, et al., 1990). However, it is unlikely that this is an important retrogressive reaction for low rank coals in liquefaction systems. Two possible reactions in this category are: 1) crosslinking as a result of CO₂ formation (shown in Fig. 5.3-9b) and 2) crosslinking accompanying water formation (shown in Figure 5.3-9c). The experimental results presented in the previous section (5.2) and the modeling results in the current section strongly support the first mechanism as being important in liquefaction systems. Support for the second mechanism is derived mainly from previous work in model compound systems at SRI (McMillen, et al., 1985).

The role of calcium in reducing liquefaction yields from low rank coals has been suggested in previous work by Whitehurst et al. (1980) and Mochida et al. (1983). It is also consistent with work which shows an effect of calcium on reducing pyrolysis tar yields (Tyler and Schafer, 1980). The role of calcium may be to provide a nascent crosslink site in the coal by allowing coordination of groups like carboxyl and hydroxyl which are prone to such reactions. Otherwise, these sites would be more likely to coordinate with water (through hydrogen bonding) than with each other. Some proposed mechanisms for low temperature crosslinking reactions involving carboxyl and hydroxyl groups in the presence and absence of cations are shown in Fig. 5.3-10.

Additional work is required on the mechanisms of crosslinking reactions involving oxygen groups and the role of associated moisture and cations on these reactions. However, it is clear that the removal of these cations by demineralization is beneficial to liquefaction yields. The possible role of clays in retrogressive reactions also requires further study.

a. Crosslinking Accompanying Methane Formation.

b. Crosslinking Accompanying CO₂ Formation.

c. Crosslinking Accompanying Water Formation.

Figure 5.3-9. Possible Mechanisms for Crosslinking.

a. Acid-Form Coals

b) Cation-Exchanged Coals

Figure 5.3-10. Possible Mechanisms of Low Temperature Crosslinking Reactions Involving Carboxyl and Hydroxyl Group.

6. CONCLUSIONS AND RECOMMENDATIONS

6.1 Conclusions

The conclusions from this study are as follows:

- The extent of retrograde reactions for low rank coals (lignite, subbituminous) is significantly reduced by methylation and demineralization. However, these treatments do not have much impact on bituminous coal.
- Ion-exchange and drying have modest negative or positive impacts on liquefaction yields for all coal ranks.
- In nearly all cases, the changes in the amounts of pyridine solubles by these pretreatments parallel the changes in the amounts of toluene solubles and hexane solubles, and are inversely related to the CO₂ yields from liquefaction.
- The occurrence of retrogressive reactions under pyrolysis conditions for coals and modified coals is related to the occurrence of retrogressive reactions under liquefaction conditions.
- The results from the model polymer experiments were partly obscured by side reactions during the synthesis, so the polymers do not consist entirely of the desired linkages. However, the results do underscore the differences in behavior between polymers and low molecular weight analogs with the same bridging bonds, with regard to retrogressive reaction behavior.
- The FG-DVC liquefaction model provides good quantitative predictions of liquefaction yields for raw coals for experiments where significant mass transfer effects are not present.
- Under the same constraints, it can make good predictions of the yields for modified coals by adjustment of the initial extractables, yield and ultimate CO₂ yield to agree with results for the starting coal and liquefaction experiments, respectively.

- Both the experimental and modeling results support the role of crosslinking associated with CO₂ evolution as a key factor in retrogressive reactions during liquefaction of low rank coals.
- The role of ion-exchanged calcium in promoting CO₂ formation accompanied by crosslinking is strongly supported by the experimental results.

6.2 Recommendations

The recommendations which result from this study are as follows:

- Additional work is required on the mechanisms of crosslinking reactions involving oxygen groups and the role of associated moisture and cations on these reactions.
- The role of clays in causing or promoting retrogressive reactions has yet to be elucidated.
- The quantitative modeling of liquefaction yields will require additional study of the role of mass transfer, particularly in the early stages of liquefaction.

REFERENCES

- Benson, S.W., Thermochemical Kinetics, John Wiley and Sons, Inc., New York, 1976, 2nd Edition.
- Bienkowski, P.R., Narayan, R., Greenkorn, R.A., Choa, K.W., IEC Res., **26**, 202, (1987a).
- Bienkowski, P.R., Narayan, R., Greenkorn, R.A., and Choa, K.C., IEC Res. **26**, 206, (1987b).
- Bishop, M. and Ward, D.L., Fuel, **37**, 191, (1958).
- Botto, R.E., Choi, C-Y., Muntean, J.V., and Stock, L.M., Energy & Fuels, **1**, 270, (1987).
- Carangelo, R.M., Solomon, P.R., and Gerson, D.J., Fuel, **66**, 690, (1987).
- Derbyshire, F., Davis, A., Epstein, M., and Stansberry, P., Fuel, **56**, 1233, (1986).
- Derbyshire, F.J. and Whitehurst, D.D., Fuel, **60**, 655, (1981).
- Deshpande, G.V., Serio, M.A., and Solomon, P.R., ACS Div. of Fuel Chem. Prepr., **33**(2), 310, (1988).
- Deshpande, G.V., Solomon, P.R., and Serio, M.A., ACS Div. of Fuel Chem. Preprints, (1988), **33**, (2), 310.
- Foster, N.R., Shah, Y.T., and Clark, K.N., Fuel, **64**, 1116, (1985).
- Frazee, W.S. and Silver, H.E., "Effects of Drying on the Liquefaction of Subbituminous Coal", presented at the Tenth Annual EPRI Contractor's Conference on Clean Liquid and Solid Fuels, Palo Alto, CA, (April 23-25, 1985).
- Gilbert, K.E., J. Org. Chem., **49**, 6, (1984).
- Gilbert, K.E. and Gajewski, J.J., J. Org. Chem., **47**, 4899, (1982).
- Given P.H., Spackman, W., Davis, A., and Jenkins, R.G., "Some Proved and Unproved Effects of Coal Geochemistry on Liquefaction Behavior with Emphasis on U.S. Coals", Coal Fundamentals, (D.D. Whitehurst, Ed.), ACS Symposium Series 139, Washington, DC, 1980, pg. 3.
- Graff, R.A. and Brandes, S.D., Energy and Fuels, **1**, 84, (1987).
- Green, T.K., Kovac, J., and Larsen, J.W., in Coal Structure, (R.A. Meyers, Ed.), Academic Press, NY, (1982), p. 199.
- Green, T.K., Kovac, J., and Larsen, J.W., Fuel, (1984), **63**, 935.
- Hamblen, D.G., "A Study of Coal Characterization Using a Scanning Electron Microprobe", Final Report to EPA under Subcontract No. 68-02-3129, Technical Directive No. 110 (1981).
- Hamblen, D.G. and Best, P.E., "Microanalysis Methods for Inhomogeneous Materials" Phase I and II - NSF Grant Numbers, PHY9113867 and PHY8212895, (1982).

- Hamblen, D.G., Solomon, P.R., and Hobbs, R.H., "Physical and Chemical Characterization of Coal", EPA Report 600/7-80-106, (1980).
- Hengel, T.D. and Walker, P.L., Fuel, **63**, 1214, (1984).
- Klein, M.T. and Virk, P.S., Ind. Eng. Chem. Fundam., **22**, 35, (1983).
- Liotta, R., Fuel, **58**, 724, (1979).
- Malhotra, R., McMillen, D.F., Tse, D.S., and St.John, G.A., Energy & Fuels, **3**, 465, (1989).
- McMillen, D.F. and Golden, D.M., "Hydrocarbon Bond Dissociation Energies", Annu. Rev. Phys. Chem., **33**, 497, (1982).
- McMillen, D.F., Chang, S.J., Nigenda, S.E., and Malhotra, R., ACS Div. of Fuel Chem. Prepr., **30**, (4), 414, (1985).
- McMillen, D.F., Malhotra, R., Tse, D.S., Nigenda, S.E., "Factors Controlling Hydrogenolysis in Coal Liquefaction", DOE Quarterly Report No. 6, Contract No. DE-FG22-86PC90908, (February 1988).
- Mochida, I., Shimohara, T., Korai, Y., Fujitsu, H., and Takeshita, K., Fuel **62**, 659, (1983).
- Morgan, M.E. and Jenkins, Fuel, **65**, 757, (1986).
- Morgan, M.E. and Jenkins, Fuel, **65**, 764, (1986).
- Morgan, M.E. and Jenkins, Fuel, **65**, 769, (1986).
- Pedley, J.B., Naylor, R.D., and Kirby, S.P., Thermochemical Data of Organic Compounds, Chapman and Hall, New York, 1986, 2nd Edition.
- Poutsma, M.L., "A Review of Thermolysis Studies of Model Compounds Relevant to Processing of Coal", Report ORNL.TM-10637, Oak Ridge National Laboratory, (1987).
- Poutsma, M.L. and Dyer, C.W., J. Org. Chem., **47**, 4903, (1982).
- Prasad, G.N., Agrew, J.B., Sridhar, T., AIChE J., **32**, 1288, (1986).
- Serio, M.A., Solomon, P.R., and Carangelo, R.M., ACS Div. of Fuel Chem. Prepr., **33**(2), 295, (1988).
- Serio, M.A., Solomon, P.R., Kroo, E., Bassilakis, R., Malhotra, R., and McMillen, D., "Studies of Coal Pretreatment in Direct Liquefaction", ACS Div. of Fuel Chemistry, Spring Meeting, Boston, MA, (1990).
- Squire, K.C., Solomon, P.R., Carangelo, R.M., and DiTaranto, M.B., Fuel, **65**, 833, (1986).
- Solomon, P.R., in Coal Structure, Advances in Chemistry Series, **192**, 95, (1981).
- Solomon, P.R., Best, P.E., Yu, Z.Z. and Deshpande, G.V., "A Macromolecular Network Model for Coal Fluidity", ACS Div. of Fuel Chem. Prepr., **34** (3), 895, (1989).
- Solomon, P.R. and Carangelo, R.M., Fuel, **61**, 663, (1982).

- Solomon, P.R. and Carangelo, R.M., *Fuel*, **67**, 949, (1988).
- Solomon, P.R., Hamblen, D.G. and Carangelo, R.M., *ACS Symposium Series*, **205**, 4, 77 (1982).
- Solomon, P.R., Hamblen, D.G., Carangelo, R.M., Markham, J.R. and Chaffee, M.R., *ACS Division of Fuel Chemistry Preprints*, **30**, #1 1 (1985).
- Solomon, P.R., Hamblen, D.G., Carangelo, R.M., Serio, M.A. and Deshpande, G.V., *Energy and Fuels*, (1988), **2**, 405.
- Solomon, P.R. and Manzione, A.V., *Fuel*, **56**, 393, (1977).
- Solomon, P.R., Serio, M.A., Deshpande, G.V. and Kroo, E., "An Investigation of the Chemistry of Catalytic Preliquefaction", *ACS Div. of Fuel Chem. Prepr.*, **34**, (3), 803, (1989).
- Solomon, P.R., Serio, M.A., Deshpande, G.V. and Kroo, E., "Crosslinking Reactions During Coal Conversion", *Energy & Fuels*, **4**(1), 42, (1990).
- Solomon, P.R. and Squire, K.R., *ACS Div. of Fuel Chem. Preprints*, (1985), **30**, (4), 346.
- Song, C., Hanaoka, K., and Nomura, M., *Fuel*, **68**, 287, (1989).
- StJohn, G.A. Buttrill, S.E., Jr., and Anbar, M., in "Organic Chemistry of Coal," Ed., J. Larsen, *ACS Symposium Series* **71**, 223 (1978).
- Suryan, M.M., Kafafi, S.A., and Stein, S.E., *J. Am. Chem. Soc.*, **111**, 1423, (1989).
- Suuberg, E.M., Lee, D., and Larsen, J.W., *Fuel*, (1985), **64**, 1668..
- Suuberg, E.M., Otake, Y., and Deevi, S., *ACS Div. of Fuel Chem. Preprints*, (1988), **33**, (1), 387.
- Suuberg, E.M., Unger, P.E., and Larsen, J.W., *Energy & Fuels*, (1987), **1**, 305.
- Tyler, R.J. and Schafer, H.N.S., *Fuel*, **59**, 487, (1980).
- Vorres, K.S., *Argonne Premium Coal Users Handbook* (1990).
- Whelan, J.K., Solomon, P.R., Deshpande, G.V., and Carangelo, R.M., *Energy and Fuel*, **2**, 65, (1988).
- Whitehurst, D.D., "A New Outlook on Coal Liquefaction Through Short-Contact-Time Thermal Reactions: Factors Leading to High Reactivity", Coal Fundamentals, (D.D. Whitehurst, Ed.), *ACS Symposium Series* 139, Washington, DC, 1980, pg. 3.
- Whitehurst, D.D., Mitchell, T.O., and Farcasiu, M. Coal Liquefaction. The Chemistry and Technology of Thermal Processes, Academic Press, NY (1980).

APPENDIX A
QUANTITATIVE FT-IR RESULTS

TABLE A-1 - SUMMARY OF FT-IR DATA ON RAW AND MODIFIED ZAP LIGNITE (ORGANIC)

Sample	Hydrogen					Aromatic Hydrogen			Carbonyl		Units (Abs. x cm ⁻¹)	
	H _{al}	H _{oh}	H _{ar}	H _{total}	H _{ar} / H _{total}	1 Adj	2 Adj	3 or More	C _{al}	O _{oh}		
												Carbon
Raw	2.02	0.34	1.58	3.94	0.40	0.46	0.74	0.37	13.47	24.67	5.50	5.00
Demin.	2.20	0.45	1.23	3.88	0.32	0.41	0.53	0.29	14.67	31.43	7.25	6.40
Demin.	2.12	0.45	1.16	3.73	0.31	0.33	0.60	0.23	14.13	29.81	7.25	6.20
Ion-Ex.	2.35	0.48	1.34	4.17	0.32	0.36	0.62	0.36	15.67	35.82	7.75	6.10
Ion-Ex.	2.48	0.48	1.36	4.32	0.31	0.34	0.68	0.34	16.53	36.62	7.75	7.10
Methyl	3.63	0.19	1.81	5.63	0.32	0.50	0.80	0.51	24.20	31.87	3.10	5.25
Methyl	3.70	0.19	1.71	5.60	0.33	0.45	0.82	0.44	24.67	32.39	3.10	6.00

TABLE A-2 - SUMMARY OF FT-IR DATA ON RAW AND MODIFIED ZAP LIGNITE (MINERAL)

Sample	Mixed Clay	Quartz	Calcite	Kaolin	Total
Raw	2.36	0.73	1.38	0.71	5.18
Demin.	1.74	0.56	0.00	0.00	2.30
Demin.	1.50	0.31	0.01	0.09	1.91
Ion-Ex	1.99	0.73	0.46	1.08	4.26
Ion-Ex	2.44	0.00	0.14	0.91	3.49
Methyl	4.96	1.21	0.24	0.99	7.40
Methyl	5.66	0.87	0.39	0.82	7.74

TABLE A-3 - SUMMARY OF FT-IR DATA ON RAW AND MODIFIED WYODAK COALS (ORGANIC)

Sample	Hydrogen				Aromatic Hydrogen			Carbonyl				
	H _{al}	H _{oh}	H _{ar}	H _{total}	H _{ar} / H _{total}	1 Adj	2 Adj	3 or More	C _{al}	Units (Abs. x cm ⁻¹)	Oxygen	
											O _{oh}	O _{ether}
Raw	3.03	0.33	1.73	5.09	0.34	0.52	0.78	0.43	20.20	23.86	5.25	5.00
Demin. Demin.	2.86 3.03	0.47 0.47	1.59 1.22	4.92 4.72	0.32 0.26	0.59 0.39	0.64 0.55	0.36 0.28	19.07 20.20	27.42 29.32	7.50 7.50	4.80 5.90
Ion-Ex. Ion-Ex.	3.07 3.11	0.48 0.57	1.60 1.43	5.15 5.11	0.31 0.28	0.51 0.46	0.67 0.58	0.42 0.39	20.47 20.73	33.66 32.66	7.60 9.10	5.90 5.50
Methyl Methyl	3.84 4.19	0.16 0.16	1.77 1.62	5.77 5.97	0.31 0.27	0.56 0.51	0.73 0.68	0.48 0.43	25.60 27.93	27.02 27.59	2.50 2.50	4.50 4.60

**TABLE A-4 - SUMMARY OF FT-IR DATA ON RAW AND MODIFIED
WYODAK COAL (MINERAL)**

Sample	Mixed Clay	Quartz	Calcite	Kaolin	Total
Raw	2.57	0.76	1.04	2.11	6.48
Demin.	1.23	0.05	0.00	0.00	1.28
Demin.	1.14	0.00	0.79	0.00	1.93
Ion-Ex	2.43	1.55	0.99	1.84	6.81
Ion-Ex	1.61	0.78	0.00	2.04	4.43
Methyl	3.88	0.22	0.37	2.31	6.78
Methyl	3.51	0.86	0.39	2.33	7.09

TABLE A-5 - SUMMARY OF FT-IR DATA ON RAW AND MODIFIED ILLINOIS NO. 6 COAL (ORGANIC)

Sample	Hydrogen					Aromatic Hydrogen			Carbonyl			
	H _{al}	H _{oh}	H _{ar}	H _{total}	H _{ar} / H _{total}	1 Adj	2 Adj	3 or More	C _{al}	Carbon	Oxygen	
										Units (Abs. x cm ⁻¹)	O _{oh}	O _{ether}
Raw	3.41	0.23	2.07	5.71	0.36	0.69	0.78	0.60	22.73	4.48	3.75	2.25
Demin.	3.38	0.25	1.48	5.11	0.29	0.53	0.62	0.33	22.53	4.52	2.75	4.80
Demin.	3.42	0.26	1.48	5.16	0.29	0.58	0.58	0.32	22.80	5.48	4.25	2.80
Ion-Ex.	3.26	0.22	2.09	5.57	0.38	0.70	0.85	0.54	21.73	8.51	3.60	3.20
Ion-Ex.	3.38	0.30	1.95	5.63	0.35	0.73	0.81	0.41	22.53	6.89	4.75	2.50
Methyl*	4.35	0.06	1.79	6.20	0.29	0.57	0.73	0.49	29.00	7.47	1.00	1.90
Methyl*	4.71	0.06	1.88	6.65	0.28	0.61	0.74	0.53	31.40	7.72	1.00	1.90

*PSOC 1098

**TABLE A-6 - SUMMARY OF FT-IR DATA ON RAW AND MODIFIED
ILLINOIS COAL (MINERAL)**

Sample	Mixed Clay	Quartz	Calcite	Kaolin	Total
Raw	2.57	0.76	1.04	2.11	17.02
Demin.	1.28	0.50	0.22	0.00	2.00
Demin.	0.88	0.09	0.90	0.28	2.15
Ion-Ex	9.23	2.92	1.46	2.84	16.45
Ion-Ex	8.22	2.38	0.14	3.15	13.89
Methyl*	6.56	0.93	1.02	2.28	10.79
Methyl*	7.21	1.50	0.79	2.18	11.68

APPENDIX B

PUBLICATIONS RESULTING FROM THIS CONTRACT

McMillen, D.F., Malhotra, R., and Serio, M.A., "Synthesis and Conversion Studies of Polymeric Models for Low Rank Coals", ACS Div. of Fuel Chem. Prepr., **35** (2), 430, (1990).

Serio, M.A., Solomon, P.R., Kroo, E., Bassilakis, R., Malhotra, R., and McMillen, D., "Studies of Coal Pretreatment in Direct Liquefaction", ACS Div. of Fuel Chem. Prepr., **35** (1), 61, (1990).

Serio, M.A., Solomon, P.R., Kroo, E., Bassilakis, R., Malhotra, R. and McMillen, D. "Studies of Retrogressive Reactions in Direct Liquefaction", proceeding of the 1991 Int. Conf. on Coal Science, Newcastle, England, pp. 656-659 (Sept. 1991).

END

**DATE
FILMED**

5 / 20 / 92