DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DOE/ER/40677--1-Pt. 2

DE92 014622

RESEARCH ON ELEMENTARY PARTICLE PHYSICS

Annual Progress Report

for Period January 1, 1992–October 31, 1992

Co-Principal Investigators: L. E. Holloway, T. A. O'Halloran

University of Illinois at Urbana-Champaign
Department of Physics
Loomis Laboratory of Physics
1110 West Green Street
Urbana, Illinois

May 1992

Prepared for

THE U.S. DEPARTMENT OF ENERGY
AGREEMENT NO. DE-FG02-91ER40677

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED *db*

ABSTRACT

This report describes the activities of the University of Illinois Experimental High Energy Physics Group. The physicists in the University of Illinois High Energy Physics Group are engaged in a wide variety of experiments at current and future accelerator laboratories. These include:

- 1) The CDF experiment at the Fermilab Tevetron $p\bar{p}$ collider.
- 2) Design and developmental work for the SDC group at SSCL.
- 3) Experiments at the wide band photon beam at Fermilab.
- 4) The SLD experiment at SLAC and design studies for a tau-charm factory.
- 5) CP violation experiments at Fermilab.
- 6) The HiRes cosmic ray experiment at Dugway Proving Grounds, Utah
- 7) Computational facilities.
- 8) Electronics systems development.

Many of the University of Illinois physicists collaborate on several experiments with different colleagues and outside groups in order to make up teams that will allow them to study the physics in which they are interested. In this sense, and in the sharing of common equipment and facilities, the University of Illinois physicists constitute one large group.

Colliding Beam Studies at Fermilab

Leland E. Holloway

Scientific and Professional Staff:

D. Errede, S. Errede, L. Holloway, D. Kardelis, R. Keup,
T. LeCompte, T. Liss, C. Luchini, A. Martin,
V. Simaitis, R. Swartz, M. Vondracek, in collaboration
with physicists of the Collider Detector Group

OVERVIEW

The Collider Detector at Fermilab (CDF) is a multipurpose detector used in studying proton anti-proton collisions at the Fermilab Tevatron Collider. The center of mass energy of the $p\bar{p}$ system is 1.8 TeV.

The Illinois group has primary responsibility for the central muon, the central drift tubes, and the central muon upgrade systems, their associated readout and trigger electronics, offline calibration and analysis software. The Illinois group is currently installing the CDF muon upgrade drift chambers to be used in the next CDF run IA. We are finishing several analyses using the data acquired in the 1988-1989 collider.

THE CENTRAL MUON SYSTEM

The purpose of this system is to provide precise position measurements of muons which penetrate the central electromagnetic and hadron calorimeters and to provide a signal suitable for triggering on potentially interesting events containing muons. One hundred forty four modules containing a total of 2304 drift channels were fabricated, tested, and installed into the CDF. The performance of the central muon chambers during the 1989 CDF run was excellent.

The level one and level two single and dimuon trigger electronics for the central muon system were successfully operated during the 88-89 collider run, providing trigger signals for readout of the whole CDF detector. The level two trigger matches, at the hardware level, muon "stubs" with stiff tracks found in the central tracking chamber. By making a cut on the stiffness of these tracks, we can suppress the number of low-PT background muons that have managed to pass the level one trigger due to multiple scattering.

A significant amount of work has been done on offline calibration, track reconstruction, track matching and trigger simulation programs. Identification of muons is made by matching tracks in the central tracking chamber and

looking for signals in the central electromagnetic and hadronic calorimeters which are consistent with minimum-ionizing particles. Analysis of the data from the 1989 CDF run show that the central muon system is operating according to design.

THE CENTRAL DRIFT TUBE ARRAY

An array of 2016 drift tubes organized in three close-packed layers surrounding the central tracking chamber has been designed, fabricated and installed in CDF. The purposes of this detector component are to aid in offline track reconstruction, by providing 3D information at a radius of 1.4m, and to augment the ultimate offline momentum resolution by 10% (important for high-PT tracks).

Each element of the CDT array consists of a thin-walled cold-drawn stainless steel tube 12.7 mm in diameter x 3.0 long, operated in the limited streamer mode. The electronics readout is identical to that of the central muon chambers. Both drift timing and charge division are measured. Calibration of the array is achieved via Fe55 sources embedded at the ends of each tube and with collision data. The Z-resolution from charge division is measured to be 0.1% L.

A Level-1 trigger system for the CDT array has been designed and installed. This programmable electronics system enables versatile triggering on individual tubes for Fe-55 source calibration, or multiple tubes for single and multiple cosmic ray events and collisions. With the CDT Level-1 trigger used as a Level-0 pre-trigger for CDF, low charged multiplicity events from rare processes occurring in 1.8 TeV collisions can be retained in the data stream. In addition, by scaling the counting rates from individual sub-sections and the global counting rate of the CDT array from outputs from the Level-1 trigger cards, the CDT array is able to be used as a 90 degree luminosity monitor.

Photon conversions in the outer skin of the Central Tracking Chamber and in the CDT tubes can be observed. A measurement of direct photon production via QCD processes has been measured using this procedure.

THE CDF MUON UPGRADE

In collaboration with Harvard University and The University of Tsukuba we are building an upgrade to the CDF muon detection system. The project was approved by the Fermilab PAC in 1989.

The upgrade consists of two parts, the Central Upgrade and the Central Extension. The Central Extension will extend the muon coverage out to zenith angles of 45 degrees with respect to both the proton and anti-proton directions (the

present Central Muon system covers out to 56 degrees) giving us an approximately 40% increase in acceptance for $W \rightarrow \mu\nu$ events and approximately a factor of two increase in acceptance for high mass dimuons from all sources, including top production. The Central Upgrade, which is being built at the University of Illinois, consists of adding an additional 60cm of steel behind the current Central Muon system followed by a second set of muon chambers. This additional absorber and second set of muon chambers will reduce the hadronic contamination of the muon signal by a factor of 20. This will allow us to keep trigger thresholds constant as the luminosity of the Tevatron increases over the next several runs. In addition, there is a significant impact on the offline analysis of muons where the background from non-interacting hadrons is virtually indistinguishable from a true muon signal. The level of this background is directly related to the sensitivity to rare physics processes involving muons.

The Central Upgrade consists of 858 21 foot long drift chambers each 1 inch by 6 inches in cross section. The chambers will be arrayed in 4 half-cell staggered layers outside the additional steel and will provide a track segment to be matched to the track segment in the inner muon chambers. The total area covered by the Central Upgrade is over 2000 square feet.

Because of the 6 to 1 aspect ratio of the chambers, it is necessary to shape the electric field by using graded potential strips. This is done by inserting, into the chambers, a 21 foot long "circuit board" into which the potential strip pattern has been cut. The circuit board potential strip pattern is made entirely here at Illinois, starting with 50 foot rolls of a 20mil thick copper clad fiberglass (similar to G-10) material called Glasteel. The Glasteel is first cut to the appropriate width (to ± 0.002 inches !) using a diamond wheel cutter made by our machinist, then cleaned, deburred, cut to chamber lengths and high voltage tested (it will have to hold a maximum of 3kV). Finally, a 1 inch strip at one end is first nickel, then gold plated (for good electrical contact with the chamber endplate which provides the 8 different voltages) and the material is run through a scoring machine (also made by our machinist) which uses precisely held exacto blades to score lines along the length of the copper surface. Once the lines have been scored, the unwanted copper material can be simply peeled away by hand, leaving the desired potential strip pattern. Over 14 miles of Glasteel, including material for both the Central Upgrade and Central Extension has now been processed and tested here at Illinois.

After a full year of prototype testing, we began processing the Glasteel material in January of 1990. Chamber production began in earnest in the early summer of 1990, shortly after our extrusions arrived, and our last chamber to be installed for the coming run was passed through the test stand in April of 1991. The Central Upgrade which was originally approved, and which we have just finished building, leaves some holes in the phi coverage, primarily between the magnet return yoke pieces on the top and bottom of the detector. When we first proposed the upgrade those areas were "off limits" because of cabling to the

central calorimeter and cooling air for the calorimeter electronics. The muon upgrade has now taken on an increased importance within the collaboration because people have begun to realize the impressive physics potential of a fully upgraded muon system, and because of the ever increasing luminosity goals of the Tevatron which necessitates further reductions in the trigger cross section. We are now working on a design for filling these previously "off limits" gaps and have just begun construction of additional chambers to complete the coverage for the scheduled 1993 run.

The implementation of the muon upgrade for the CDF detector will have a profound impact on both the quality and the type of physics done at CDF. In conjunction with the silicon vertex detector, which will also be in place for the next run, CDF will have a powerful detector with which to do heavy flavor physics. The upgraded muon system will be able to trigger on dimuons with transverse momenta as low as 1.8 GeV/c and on inclusive single muons with transverse momentum above 6 GeV/c. Together with an offline displaced vertex cut, we expect to be able to extract a rather clean b sample from both the single and dimuon triggers. Physics goals for the next run include measurement of the B_s mass through the decay $B_s \rightarrow \psi\phi$, $\phi \rightarrow K^+K^-$. Ratio of the production cross sections B_s/B_d which, together with a measurement of the combined mixing of B_d and B_s will allow an extraction of the mixing rate for B_s alone (note that e^+e^- mixing results at the upsilon(4s) measure B_d mixing alone), rare decay modes of B_s , lifetime measurements of B_s etc. Certainly one must not forget that the enhanced muon system together with the silicon vertex detector will also give us an excellent handle for finding the top quark should its mass be accessible at the Tevatron. Since the standard model top quark (which we now know to be heavier than 90 GeV) decays to a W and a b quark, we can tag these decays by looking for a high transverse momentum muon and a displaced vertex from the b decay. For all of these topics and more, we are increasing our acceptance with the upgraded muon system and at the same time improving our efficiency for identifying the events with the vertex detector.

The construction of the CDF muon upgrade chambers which began in late 1989 was completed in mid-1991. In early 1991, while we were still building chambers at the University of Illinois, we began installation of the chambers at CDF. The installation of the chambers occurred in stages and was completed in March of 1992. In addition to this, a large portion of the muon trigger electronics was built here at Illinois and this was installed and tested in November and December of 1991.

At the present time we are extremely busy commissioning the new chambers. This activity includes debugging the electronics, integrating the readout into the CDF data acquisition system and taking cosmic ray data with the entire detector. In the cosmic ray data taken so far, the performance of our new chambers has been excellent. We are anticipating an exciting run at the Tevatron Collider.

PHYSICS RESULTS

The physics results from the 1989 data arising from central muon triggers are significant. Thus far, we have a data sample of six hundred $W \rightarrow \mu \nu$ candidates, 150 $Z \rightarrow \mu^+ \mu^-$ candidates, several thousand low-mass dimuons, a strong signal for $J/\psi \rightarrow \mu^+ \mu^-$ is observed as well as up-silon production in 1.8 TeV collisions. The low-mass Drell-Yan muon pairs are of interest for small- x physics; like-sign and opposite-sign di-leptons contain information relevant to $\bar{B}B$ mixing. In addition, we are also searching for evidence of the top quark, via their semi-leptonic decays. The CDF lower bound on the mass of the top quark at the present stage of the analysis is 91 GeV/c².

The analysis of the data is proceeding well. Attention is focused on the physics signals associated with muons and electrons in the central region. Among the current topics being studied by Illinois PhD students are:

- 1) Measurement of Drell-Yan production of di-muon pairs.
(Victor Scarpine. Publication in progress.)
- 2) A study of photons associated with di-muon events.
(Chris Luchini. Work in progress.)
- 3) The ratio of W to Z production cross sections.
(Ray Schwartz. Work in progress.)
- 4) Z production at $\sqrt{s} = 1.8$ TeV
(David Kardelis. Work in progress)

PUBLICATIONS

"The Dijet Angular Distribution at $\sqrt{s} = 1.8$ TeV," F. Abe et al., The CDF Collaboration, submitted to Phys. Rev. Lett.

"Limits on the Production of Massive Stable Charged Particles," F. Abe et al., The CDF Collaboration, submitted to Phys. Rev. D, Rapid Communications.

"A Measurement of Jet Shapes in $\bar{p}p$ Collisions at $\sqrt{s} = 1.8$ TeV," F. Abe et al., The CDF Collaboration, to be submitted to Phys. Rev. Lett.

"Limit on the Rare Decay $W^\pm \rightarrow \gamma + \pi^\pm$ in $\bar{p}p$ Collisions at $\sqrt{s} = 1.8$ TeV," F. Abe et al., The CDF Collaboration, submitted to Phys. Rev. Lett.

"A Measurement of the Bottom Quark Production in 1.8-TeV Proton-Antiproton Collisions using Semileptonic Decay Electrons," F. Abe et al., The CDF Collaboration, submitted to Phys. Rev. Lett.

"A Measurement of the Production and Muonic Decay Rate of W and Z Bosons in $p\bar{p}$ Collisions at $\sqrt{s} = 1.8$ TeV," F. Abe et al., The CDF Collaboration, submitted to Phys. Rev. Lett., February 25, 1992. FERMILAB-PUB-92/69-E.

"Measurement of the Isolated Prompt Photon Cross Section Measurement in $p\bar{p}$ Collisions at $\sqrt{s} = 1.8$ TeV," F. Abe et al., The CDF Collaboration, submitted to Phys. Rev. Lett., February 3, 1992. FERMILAB-PUB-92/31-E.

"A Measurement of the B Meson and b Quark Cross Section at $\sqrt{s} = 1.8$ TeV Using the Exclusive Decay $B^{+-} \rightarrow J/\psi K^{+-}$," F. Abe et al., The CDF Collaboration, submitted to Phys. Rev. Lett., January 24, 1992. FERMILAB-PUB-92/21-E.

"A Limit on the Top Quark Mass from Proton-Antiproton Collisions at $\sqrt{s} = 1800$ GeV," F. Abe et al., the CDF Collaboration, submitted to Phys. Rev. D., December 19, 1991. FERMILAB-PUB-91/352-E.

"A Search for New Gauge Bosons in $p\bar{p}$ Collisions at $\sqrt{s} = 1.8$ TeV," F. Abe et al., the CDF Collaboration, Phys. Rev. Lett. 68, 1463 (1992). FERMILAB-PUB-91/327-E.

"Properties of Events with Large Total Transverse Energy Produced in Proton-Antiproton Collisions at $\sqrt{s} = 1.8$ TeV," F. Abe et al., The CDF Collaboration, Phys. Rev. D. 45, 2249 (1992). FERMILAB-PUB-91/283-E.

"Search for Squarks and Gluinos from $p\bar{p}$ Collisions at $\sqrt{s} = 1.8$ TeV," F. Abe et al., The CDF Collaboration, submitted to Phys. Rev. Lett.

"A Lower Limit on the Top Quark Mass from Events with Two Leptons in $p\bar{p}$ Collisions at $\sqrt{s} = 1.8$ TeV," F. Abe et al., The CDF Collaboration, Phys. Rev. Lett. 68, 447 (1992).

"Measurement of the Ratio $\sigma(B(W \rightarrow \tau\nu))/\sigma(B(W \rightarrow e\nu))$ in $p\bar{p}$ Collisions at $\sqrt{s} = 1.8$ TeV, as a Test of Lepton Universality," F. Abe et al., The CDF Collaboration, submitted to Phys. Rev. Lett., December 23, 1991. FERMILAB-PUB-91/356-E.

"Measurement of $B^0 \bar{B}^0$ Mixing at the Fermilab Tevatron Collider," F. Abe et al., The CDF Collaboration, Phys. Rev. Lett. 67, 3351 (1991). Fermilab PUB-91/201-E.

"Search for $W' \rightarrow e\nu$ and $W' \rightarrow \mu\nu$ in $p\bar{p}$ Collisions at $\sqrt{s} = 1.8$ TeV," F. Abe et al., The CDF Collaboration, Phys. Rev. Lett. 67, 2609 (1991). Fermilab PUB-91/208-E.

"Inclusive Jet Cross Section in $p\bar{p}$ Collisions at $\sqrt{s} = 1.8$ TeV," F. Abe et al., The CDF Collaboration, to be submitted to Phys. Rev. D.

"Inclusive Jet Cross Section in $p\bar{p}$ Collisions at $\sqrt{s} = 1.8$ TeV," F. Abe et al., The CDF Collaboration, Phys. Rev. Lett. 68, 1104 (1992). Fermilab-PUB-91/231-E.

"Topology of Three Jet Events in $p\bar{p}$ Collisions at $\sqrt{s} = 1.8$ TeV," F. Abe et al., The CDF Collaboration, Phys. Rev. D 45, 1448 (1992). Fermilab-PUB-91/181-E.

"Lepton Asymmetry in W Decays from $p\bar{p}$ Collisions at $\sqrt{s} = 1.8$ TeV," F. Abe et al., the CDF Collaboration, Phys. Rev. Lett. 68, 1458 (1992). FERMILAB-PUB-91/263-E.

"Measurement of the e^+e^- Invariant Mass Distribution in $p\bar{p}$ Collisions at $\sqrt{s} = 1.8$ TeV," F. Abe et al., the CDF Collaboration, Phys. Rev. Lett. 67, 2418 (1991). Fermilab PUB-91/169-E.

"Measurement of the Z p_T Distribution in $p\bar{p}$ Collisions at $\sqrt{s} = 1.8$ TeV," F. Abe et al., The CDF Collaboration, Phys. Rev. Lett. 67, 2937 (1991). Fermilab PUB-91/199-E.

"Measurement of the W Boson P_T Distribution in $p\bar{p}$ Collisions at $\sqrt{s} = 1.8$ TeV," F. Abe et al., Phys. Rev. Lett. 66, 2951 (1991). Fermilab-PUB-91/33-E

"A Measurement of $\sigma(W \rightarrow e\nu)$ and $\sigma(Z^0 \rightarrow e^+e^-)$ in $p\bar{p}$ Collisions at $\sqrt{s} = 1800$ GeV," F. Abe et al., Phys. Rev. D 44, 29 (1991). Fermilab-PUB-90/229-E.

"A Determination of $\sin^2 \theta_W$ from the Forward-Backward Asymmetry in $p\bar{p} \rightarrow Z^0 X \rightarrow e^+e^- X$ Interactions at $\sqrt{s} = 1.8$ TeV," F. Abe et al., Phys. Rev. Lett. 67, 1502 (1991). Fermilab-PUB-91/135-E.

"Measurement of QCD Jet Broadening in $p\bar{p}$ Collisions at $\sqrt{s} = 1.8$ TeV," F. Abe et al., Phys. Rev. D 44, 601 (1991). Fermilab PUB-91/23-E.

"Top Quark Search in the Electron + Jets Channel in Proton-Antiproton Collisions at $\sqrt{s} = 1.8$ TeV," F. Abe et al., Phys. Rev. D. 43, 664 (1991).

"A Measurement of the W Boson Mass in 1.8 TeV $p\bar{p}$ Collisions," F. Abe et al., Phys. Rev. D. 43, 2070 (1991).

CONFERENCE PROCEEDINGS AND TALKS

"Search for the Λ_b Baryon at CDF," The CDF Collaboration, A. Gauthier, published Proceedings XXVIIth Rencontres de Moriond, QCD and High Energy Hadronic Interactions, Les Arcs, Savoie, France, March 22-28, 1992.

"The Search for Top at CDF," The CDF Collaboration, T. Liss, published Proceedings Particles and Fields '91, University of Vancouver, Vancouver, British Columbia, Canada, August 18-22, 1991. FERMILAB-CONF-91/253-E.

Superconducting Supercollider Detector R & D

S. Errede, J. Thaler, and J. Wiss

Scientific and Professional Staff:

S. Errede, R. Gardner, E. Golin, M. Haney
E. Hughes, D. Knapp, J. Thaler, G. Tharakan

TASK SUMMARY

Our SSC work has been supported by the SSC R&D budget, first for generic, then subsystem, and now SDC detector R&D. Our group is a member of the SDC collaboration, working on two parts of the detector: the data acquisition and muon subsystems. We plan to begin to allocate some of our HEP grant money to this work in 1993. We receive support for some related work from the TNRLC.

PROJECT DESCRIPTIONS

A: DAQ subsystem studies:

We have been working on the design of the SDC data acquisition (DAQ) system. While our effort has been focussed on the interface (the "data collection chip", or DCC) between the DAQ and the subsystem specific front end electronics, we have also kept our eye on the larger issues of system integration and the design environment. One goal is to determine the extent to which it is possible to use a single design for as many of the different SDC front ends as possible. Another goal is to demonstrate that it is possible to start with an abstract model of a system and carry it all the way to hardware fabrication. This approach has not yet been taken in high energy physics. Many of our ideas have been incorporated into the DAQ portion of the SDC's EoI, LoI and TDR documents.

We feel that the time scale for SSC detector construction allows us to incorporate ideas from outside the HEP community. To this end, we have formed a collaboration with computer scientists (also from Illinois) who have expertise in computer aided engineering (CAE) and visual programming. The collaborative part of our work is supported by the TNRLC, but it is closely enough related to the DOE work that we will describe it briefly here.

The TNRLC supported project is directed at creating a visual VHDL (vVHDL) programming environment. Such an environment will allow designers to draw a picture of the system in much the same way that a PCB designer draws a schematic diagram of the electronic circuit. Computer software turns this

schematic into a PCB layout suitable for construction. Our vVHDL environment will do the same for the larger scale DAQ designs that the SDC will produce. The vVHDL environment is desirable, because VHDL is a difficult language, although a powerful one (the only one suitable for SDC DAQ design). By giving the engineers a visual environment similar to the one they already use, the speed and accuracy of design will be increased. Also, by encouraging the use of VHDL, which is the language used for the behavioral modeling, we will increase our confidence that the DAQ that is eventually built will behave as expected.

B: SDC Muon Subsystem Studies:

We have been actively involved in the design of the barrel, intermediate and forward muon subsystems for the SDC detector. Our efforts have focussed primarily on design issues and detailed studies associated with the online and offline physics performance of the SDC muon subsystems, such as requirements for the number and deployment of drift chamber layers, in order to obtain/maintain reasonable momentum resolution for muons while simultaneously attempting to minimize overall cost and complexity. Our work has been documented in a series of SDC notes, totalling approximately 25 such notes to date, and has been used in the muon portion(s) of the SDC's EoI, LoI and TDR documents.

GOALS AND MAJOR RESULTS TO DATE

A: DAQ subsystem studies:

Two graduate students are supported by SDC R&D to work on the DCC. One has been working on behavioral (ie. functional) models which are needed in order to study the response of the DCC to varying data loads. We have obtained preliminary results, but a better understanding is needed before we build physical prototypes. Our studies have shown that data correlations have a significant effect on performance. Thus reliable DAQ design needs to take this effect into account.

The other graduate student has extended the behavioral DCC model to create the beginning of a real structural (ie, physical) design. We have completed the first pass through a novel design which uses adaptive queues to solve many of the problems that the DCC must face.

We recently demonstrated our first working version of the vVHDL environment to a group of physicists at the SSCL. The response was positive and encouraging. We plan to use this environment to simplify the SDC R&D work described above.

B: SDC Muon Subsystem Studies:

We have carried out detailed Monte Carlo simulation studies of acceptance, momentum and mass resolution, and charge sign measurement capabilities for various benchmark muon physics processes anticipated at the SSC, such as the production and decay of $W \rightarrow \mu\nu$, $Z \rightarrow \mu^+\mu^-$, the production and decay of heavy gauge bosons $W' \rightarrow \mu\nu$ and $Z' \rightarrow \mu^+\mu^-$, ZZ pairs $\rightarrow 4\mu$, $\text{Higgs} \rightarrow ZZ \rightarrow 4\mu$, $T\bar{T} \rightarrow W^+b$, $W^-b\bar{b}$, and $B\bar{B} \rightarrow 1\mu + X$ production and decay.

We have also made detailed studies of muon chamber alignment requirements, the physics impact of various types of misalignments. We have carried out detailed studies of matching muon track segments with e.g. tracks from the inner tracking system for the barrel and forward muon subsystems, in order to maximize the robustness of the design of the muon subsystems for each of these regions, in terms of pattern recognition capabilities, both at the trigger and offline data analysis level.

We have carried out detailed Monte Carlo simulation studies of the performance of various candidate Level-1 muon trigger schemes, for inclusive single muons and also for muons from benchmark physics processes as mentioned above. The Monte Carlo simulations consist of the event generation, detailed transport of muons through various magnetic field regions (solenoid, return flux and toroid(s)), muon interactions (MCS, delta-rays & bremsstrahlung) in traversing the various materials of the SDC detector, and detailed transport through the barrel, intermediate and/or forward muon subsystems, generating simulated raw data. The raw muon data is then passed through Verilog and more recently, VHDL simulation(s) of candidate Level-1 muon trigger schemes, to obtain e.g. trigger efficiencies vs. muon Pt and overall Level-1 trigger rates. This effort is in the process of continuous evolution as the design of the SDC muon subsystem(s) evolve with time. In the near future we hope to begin work on detailed simulations of candidate Level-2 muon trigger schemes, such as combining refined muon stub information from the Level-1 muon trigger with that from prompt track trigger information from the inner tracking system(s). Ultimately we intend to carry out studies involving the detailed simulation of the entire pipeline and DAQ system for the SDC muon subsystem(s), including Level-3.

SDC MUON TEST BEAM STUDIES

We have also been heavily involved in Fermilab experiment T-816, the study of high energy muons (50-750 GeV) traversing matter. The purpose of this experiment was to determine the fraction of "clean" muons exiting a 1-m length of magnetizable steel, and to measure the various properties of secondary particles (mostly delta-rays, bremsstrahlung and e^+e^- pairs) produced by muon interactions in traversing this amount of material. In this way, explicit measurements of these

processes could be compared with detailed simulations of the same, with the hope of optimizing the overall performance and robustness of the design of the SDC muon subsystem(s). Illinois was responsible for setting up, making operational the Fastbus-based VAX-3500 online data acquisition system and the trigger electronics. We had an extremely successful data-taking run during the last fixed target running period at Fermilab, and are currently in the process of analyzing the data taken with this apparatus. We hope to publish several papers from this experiment, and will be presenting results from this experiment at various conferences in the near future. Preliminary results have already been presented internally at various SDC collaboration meetings.

PUBLICATIONS

The following papers were written by our SSC DAQ design group. This work, is supported partially by our DOE grant and partly by the TNRLC.

We issued Eric Hoffmann's thesis as a Department of Computer Science technical report:

E. B. Hoffmann, *Implementation of an Incremental CAD Environment*, Report #UIUCDCS-R-92-1718, Department of Computer Science, University of Illinois at Urbana-Champaign, January 1992.

In addition, five papers describing aspects of our work were accepted for publication or presentation during 1991:

L. G. Jones, "An Incremental Zero/Integer-Delay Switch-Level Simulation Environment," *IEEE Transactions on Computer-Aided Design of Integrated Circuits and Systems*, accepted for publication.

K. P. Smith, and L. G. Jones, "Efficient Maintenance of Consistency in Derived Data Using Join Numbers," *Journal of Computer and Software Engineering*, accepted for publication.

E. Hughes, G. Tharakan, R. Downing, M. Haney, E. Golin, L. Jones, D. Knapp, J. Thaler, "Modeling and Simulation of the SDC Data Collection Chip," *IEEE Transactions on Nuclear Science*, **39**, 139(1992).

L. G. Jones, "Exploiting Hierarchy in a Cache-Based Switch-Level Simulator", to be presented at the 1992 European Design Automation Conference, Brussels, Belgium, March 1992.

E. J. Golin, S. Danz, S. Larison and D. Miller-Karlow, "Palette: an Extensible Visual Editor," *Proceedings of the 1992 ACM/SIGAPP Symposium on Applied Computing*, (March 1992), pp. 1208-1216.

One invited talk was written up as a technical report:

Robert Downing, "Electrical Engineering Standards for the NExt Generation of High Energy Physics Experiments," UIUC-HEPG-91-82, presented at the *Conference on Electronics for Future Colliders*, May, 1991.

Neutral Beams at Fermilab

James E. Wiss

Scientific and Professional Staff:

J. Wiss, R. W. Gardner, R. Culbertson, R. Greene

OVERVIEW

E687 represents a collaboration between the University of Illinois, and other groups from the United States and Italy. This experiment, a continuation of our neutral beam efforts at Fermilab dating from 1972, studies high energy photoproduction at ≈ 200 GeV with an emphasis on the photoproduction of charmed particles.

E687 is a multiparticle magnetic spectrometer with excellent particle identification, calorimetric, and lifetime tagging capabilities. Lifetime tagging is provided by a fine pitch silicon microstrip detector which offers a proper time resolution of about 0.045 picoseconds for charm particles -- roughly 1/10 the D^0 lifetime. Charged particle identification is provided by a Cerenkov system which consists of three ≈ 100 cell Cerenkov counters. The spectrometer features fine grain electromagnetic shower calorimetry and an extensive array of muon counters shielded against hadron punch through by steel walls. A complete description of the E687 detector can be found in Reference (5).

The University of Illinois group has played a significant role in all aspects of E687 including the construction of one of our three Cerenkov counters, the construction of several components of the data acquisition system, and contributions to the E687 trigger hardware. Our major contribution to the experiment has been in the area of software development and data analysis. Contributions to the experimental data reduction software including the algorithms for Cerenkov identification of charged particles, the programs for the identification and measurement of neutral Vees, magnetic field tracing and chamber alignment, the vertex finder used to tag charm particles, and many of the routines to reduce our huge data samples down to a manageable size by skimming off events containing charm. The University of Illinois contributions to the (published) E687 data analysis effort include, studies of the performance of the E687 spectrometer⁽⁵⁾, measurements of the D^0 & D^+ lifetimes⁽²⁾, new measurements of Cabibbo suppressed branching ratios⁽³⁾, and amplitude analyses⁽⁴⁾ of the decay mode $D_0 \rightarrow \bar{K}^0 \pi^+ \pi^-$ and $D_0 \rightarrow \bar{K}^0 K^+ K^-$. We also wrote and maintain the experiment's Monte Carlo program.

In 1988 we concluded our first major data run of the experiment in which 80 million photo-hadronic triggers were recorded. The analysis of this data is essentially complete and we have published results on a sample of about 10,000

fully reconstructed charm particle decays. Our second data run of the experiment was completed in early 1991 in which 525 million triggers recorded resulting in an anticipated fully reconstructed charm sample of about 100,000-150,000 fully reconstructed charm particles. Approximately 1/2 of this new data has been processed to date, and approximately 20% of the new data has been disseminated to collaborating institutions and is actively being analyzed at the University of Illinois and the other E687 collaborating institutions.

1991 ACCOMPLISHMENTS

After completing the 1991 run, our efforts within the last year have been divided between helping with the processing and certification of the new data, and data analysis efforts on both the old data and incoming data. The processing and certification activities include help with managing data reduction production on the FNAL Unix farm, and performing many studies on the integrity of the new data using a data monitoring package written here, which checks geometry, detector performance, and charm signals for each data tape. We have used these studies of detector performance to upgrade the E687 Monte Carlo to accurately simulate 1990/91 data as well as 1987/88 data.

We recently initiated an effort to skim much of the newly processed E687 data on the University of Illinois Vax cluster in order to provide an influx of new data which was discussed at the recent APS meeting⁽⁸⁾. About 1.5 times our previous charm sample was skimmed from the new data on to summary tapes at the University of Illinois and distributed to the other twelve E687 collaborating institutions. This new data has dramatically increased our charm yield, our sensitivity to $D^0 - \bar{D}^0$ mixing, our ability to observe new charmed baryon states, and significantly extended our studies of charm semileptonic decays.

E687 has made substantial progress in data analysis since 1991. Our analysis of charm lifetime evolution has resulted in new published measurements of the charm particle lifetimes⁽²⁾ which complements our previous measurements⁽¹⁾. These measurements are summarized below:

E687 Charm Particle Lifetimes

	E687 τ (ps)	1990 PDG
D^0	$.42 \pm .011 \pm .007$	$.42 \pm .01$
D^+	$1.075 \pm .040 \pm .018$	$1.062 \pm .028$
D_s^+	$.50 \pm .06 \pm .03$	$.445 (+ .035 - .029)$
Λ_c^+	$.20 \pm .03 \pm .03$	$.19 (+ .017 - .013)$

We have also obtained new limits on $D^0 - \bar{D}^0$ mixing⁽⁶⁾. With the inclusion of $\approx 13\%$ of the new data we announced⁽⁸⁾ a new world mixing limit of:

$$r = \frac{D^{*+} \rightarrow D^0 \pi^+ \rightarrow \bar{D}^0 \pi^+}{D^{*+} \rightarrow D^0 \pi^+} < 0.0034 \text{ (90\% CL)}$$

At present our mixing limit is falling inversely proportional to the size of our charm sample and we may be able to reach $r = 5 \times 10^{-4}$ on the basis of our complete data set. This value lies in the range expected by Colangelo, Nardulli, and Paver (Phys Lett. B242 (1990) 691) who include dispersive, long distance contributions to real part of ΔM .

We have begun an investigation of fully hadronic and semileptonic charm decays. Branching ratio's have been presented^(3,4,7) on the following Cabibbo suppressed hadronic decays:

Branching Ratios

		E687		
D^0	$\pi^+\pi^-\pi^+\pi^-/K^-\pi^+\pi^-\pi^+$	$.11 \pm .024 \pm .008$	$.096 \pm .018 \pm .007\gamma$	$.102 \pm .013^c$
D^0	$K^+K^-/K^-\pi^+$	$.14 \pm .03 \pm .01$	$.119 \pm .018^p$	$.122 \pm .018 \pm .012^m$
D^0	$\bar{K}^0 K^+K^-/\bar{K}^0\pi^+\pi^-$	$.20 \pm .05 \pm .04$	$.20 \pm .05^p$	$.170 \pm .022^a$
D^0	$\bar{K}^0 \phi/\bar{K}^0 \pi^+\pi^-$	$.13 \pm .06 \pm .02$	$.155 \pm .033^a$	$.163 \pm .023^c$
D^0	$\bar{K}^0(K^+K^-)_{\text{non-}\phi}/\bar{K}^0 \pi^+\pi^-$	$.11 \pm .04 \pm .03$	$.084 \pm .02^a$	$.12 \pm .032^p$
D_s^+	$\phi\pi^+\pi^-\pi^+/\phi\pi^+$	$.58 \pm .20 \pm .10$	$.42 \pm .13\gamma$	$1.11 \pm .37 \pm .28^a$

a ARGUS c CLEO m MARK3 γ E691 p Particle Data Group

Complete amplitude analyses have been presented for the decay⁽⁴⁾ $D^0 \rightarrow K_s^0 \pi^+\pi^-$ and $D_s^+ \rightarrow K^+K^-\pi^+$ and $D^+ \rightarrow K^-\pi^+\pi^+$. Preliminary work is underway for the $D^0 \rightarrow K^-\pi^0\pi^+$ Dalitz analysis which represents the first physics we've performed with the rebuilt E687 electromagnetic calorimeter. Our collaborators have performed analyses of the $D_s^+ \rightarrow K^+K^-\pi^+$ Dalitz plot. In all cases investigated so far, we find significant structure in the Dalitz plot indicating considerable resonance production. We hope to extend this work to other accessible charm meson final states and ultimately hope that such information can be use to test models for hadronic charm decays such as the Bauer, Stech, and Wirbel model (Z. Phys. C34 (1987) 103).

We recently presented new preliminary results⁽⁸⁾ charm meson semileptonic decays. At Illinois, our emphasis has been on the decay $D^+ \rightarrow (K^-\pi^+)\mu^+\nu$ and the determination of the branching ratio, and axial-vector form factor ratios. A great deal of experimental and theoretical interest centers around the determination of the $K^*\ell^+\nu$ form factors. Our E687 collaborators have made new measurements of the $D^0 \rightarrow K^-\mu^+\nu$ branching ratio.

E687 has made considerable progress in the study of charmed baryons. We recently presented preliminary results⁽⁸⁾ on the observation of $\Lambda_c^+ \rightarrow PK^-\pi^+$ & $\Xi^-K^+\pi^+$ and $\Xi_c^+(2465) \rightarrow \Xi^-\pi^+\pi^+$ & $\Omega^-K^+\pi^+$.

E687 REFERENCES

- (1) P.L. Frabetti, *et al.*, Measurement of the Λ_c^+ and D_s^+ Lifetimes. Phys. Lett. **B251**, 639-644 (1990)
- (2) P.L. Frabetti, *et al.*, A Measurement of the D^0 and D^+ Lifetimes. Phys. Lett. **B263**, 584-590 (1991)
- (3) P.L. Frabetti, *et al.*, Measurements of the decays $D^0 \rightarrow \pi^+\pi^+\pi^-\pi^-$, $D^0 \rightarrow K^+K^-$ and $D_s^+ \rightarrow \phi\pi^+\pi^+$. (Accepted for publication in Physics Letters)
- (4) P.L. Frabetti, *et al.*, Study of $D^0 \rightarrow K_s^0\pi^+\pi^-$ and $D^0 \rightarrow K_s^0K^+K^-$ in High Energy Photoproduction. (Submitted to Physics Letters)
- (5) P.L. Frabetti, *et al.*, Description and Performance of the Fermilab E687 Spectrometer. (Accepted for publication in Nuclear Instruments and Methods) Fermilab-Pub-90/258-E.
- (6) R. Culbertson, E687 Preliminary Mixing Results and Lifetime Review. The Vancouver Meeting, Particle & Fields '91, Edited by David Axen and Douglas Bryman, & Martin Comyn, World Scientific, p. 423 - 424 (1991)
- (7) J. Wiss for the E687 Collaboration, Heavy Flavor Photoproduction Results from E687. Proceedings of the 3rd Topical Seminar on Heavy Flavors, San Miniato, Tuscany (Italy) 17-21 June 1991: Edited by P.G. Pelfer, F. Grancagnolo and F. Navarra (To be published in Nuclear Physics B, Proceedings Supplements Section)
- (8) J. Wiss for the E687 Collaboration, Recent Charm Photoproduction Results from E687. Invited talk at the 1992 Joint April Meeting of the American Physical Society and the American Association of Physics Teachers, April 1992, Washington, D.C.

Experiments at e^+e^- Colliders

B. Eisenstein, G. Gladding, J. Thaler

Scientific and Professional Staff:

I. Abt, B. Downing, B. Eisenstein,
G. Gladding, M. Haney, I. Karliner, D. Lesny, W. Majid,
J. McGowan, V. Simaitis, G. Stewart, J. Thaler

TASK SUMMARY

This section describes our participation in three e^+e^- experiments, the Mark III and SLD at SLAC and the proposed Tau-Charm factory in Seville. The Mark III is nearly done; the last students will finish their Ph.D. theses in the next year. The SLD is currently taking data to study the Z^0 boson. The polarized electron source has been installed. With it and the CCD vertex detector, we should be able to make some asymmetry and B-meson measurements which are inaccessible to LEP. The Tau-Charm factory is in the initial design phase. A beam test of the Cesium Iodide calorimeter is planned for the summer of 1992.

PROJECT DESCRIPTIONS

A. Mark III:

The Mark III experiment took data at 4 center of mass energies: 3.1 GeV (J/Ψ), 3.7 GeV (Ψ'), 3.77 GeV (Ψ''), and 4.03 GeV. The last data run was completed in 1989. We have three graduate students, Majid, McGowan, and Stewart, who are currently writing theses using this data.

B. SLD:

The SLD experiment is designed to obtain data on Z^0 production and decay at the SLAC Linear Collider (SLC). The SLC will provide polarized electrons to the SLD, making the sensitivity to some weak interaction effects greater than at LEP even with a smaller data sample. Our superior vertex detector and smaller beam pipe will also allow cleaner identification of B-mesons. Specific Illinois contributions to the SLD have been the event trigger, the Fastbus plant and monitor software, and the vertex detection software. An engineering run was made in the summer of 1991; the first data run is currently in progress (April 1992).

C. Tau-Charm Factory

The Tau-Charm Factory is a proposed e^+e^- storage ring, operating in the 3 - 4.5 GeV region with a design luminosity of $10^{33} \text{ cm}^{-2}\text{sec}^{-1}$. The physics which can be done with such a machine promises to be quite rich and was initially documented in the Proceedings of the Tau-Charm Factory Workshop (SLAC-Report-343) held at SLAC in May, 1989. The ability to run near the threshold for $\tau^+\tau^-$ production and at charm resonances (J/Ψ , Ψ'') with 1000 times the luminosity of SPEAR are the crucial features which will produce unique physics possibilities at the Tau-Charm Factory.

Goals and Major Results to Date

A. Mark III:

The Mark III experiment has been quite successful. The current publication count stands at 24 Phys. Rev. Letters, 11 Phys. Rev. D articles, and 5 Phys. Letters. Seven University of Illinois graduate students have received their Ph.D.'s for work on this experiment. Our final three students on this experiment should be finishing their theses during 1993.

McGowan's thesis topic is the electromagnetic form factor of the $\rho^\pm$ meson. Meson form factors are a central topic in QCD, and a measurement at M_Ψ will test the calculations. This result will appear in mid-1992.

Majid's thesis topic is a search for non-charm decays of the Ψ'' . The existence of such decay modes has been suggested to explain some discrepancies between the Ψ'' production cross-section and the measured D decay branching ratios. This work will be finished in 1993.

Stewart has begun a study of our sensitivity to CP violation in the Ψ'' data. Differences between partial decay rates for particle and antiparticle states represent a model-independent test of CP violation. The asymmetry in rates between D and $\bar{D}$ decays to the CP=+1 state K^+K^- has been measured to be 0.20 ± 0.15 by E691 at FNAL. We hope to make a more sensitive measurement using this and other final states.

B. SLD:

We are currently taking data in a run which is scheduled to last until August, 1992. At the present time (April 1992), we have accumulated approximately 1000 hadronic Z^0 decays. The polarized electron source has been recently installed. Polarized beams have been transported to the intersection point, but no data with collisions have been taken as of yet. If all continues well,

we should accumulate several thousand events with polarized beams which should result in an interesting first measurement of A_{LR} .

All of the Illinois hardware contributions to the SLD are complete. These include the trigger, LAC online software, data acquisition software, online controls and monitors, and Fastbus system. Details of this work were given in last year's proposal.

The secondary vertex reconstruction software is complete. Details of this work were given in last year's proposal. Current analysis work is focussed on improving the linking of vertex detector measurements with found drift chamber tracks and the development of the final track fitting procedure. This work should be completed within the next month at which time our efforts will be directed toward understanding the new data. The analysis focus of the Illinois group will be B meson production and decay. In particular, we will concentrate initially on those topics which can be addressed with a few thousand hadronic Z events, *e.g.* lifetime measurements, the $b\bar{b}$ and $c\bar{c}$ partial widths of the Z, and the asymmetries (A_{FB} , A_{LR}) for the b and c quarks.

C. Tau-Charm Factory:

The physics expectations for the proposed Tau-Charm Factory were detailed in last year's proposal. This past year, discussions between CERN and Spain have intensified. The project was discussed and endorsed at the March 1992 meeting of the Scientific Policy Committee of CERN. We understand that only questions of organization remain. A further discussion is scheduled for the June 26, 1992 CERN Council meeting. The Spanish government has asked for a formal decision in June, 1992.

The work in the United States this past year has been directed to two main efforts: (1) research and development relating to the proposed CsI calorimeter, and (2) development of Monte Carlo tools needed for detector design decisions. Studies are continuing on all aspects of the calorimeter, *e.g.* the mechanical supports, the wave-shifters, the photo-diodes, and the front-end electronics. These preliminary studies will culminate in a beam test using 48 CsI crystals presently scheduled for a run in August 1992 at TRIUMF. The Monte Carlo has been developed so that a variety of physics generators (both τ and charm production and decay) have been implemented in a GEANT environment with an interface which allows detector modifications to be made easily. Issues which are currently being studied include (1) the effects of different proposed structures for the central drift chamber on the track resolution and (2) the effect of a smaller drift chamber (to reduce the cost of the CsI) on the physics capabilities of the detector.

PUBLICATIONS

D. Coffman, J. S. Brown, B. I. Eisenstein, T. Freese, G. E. Gladding, J. M. Izen, C. Simopoulos, I. E. Stockdale, B. Tripsas et al. Measurement of the inclusive decay properties of charmed mesons. Phys. Lett. B 263, 135-140 (1991).

Z. Bai, J. J. Becker, G. T. Blaylock, R. E. Cassell, B. I. Eisenstein, T. Freese, G. E. Gladding, J. M. Izen, S. A. Plaetzer, C. Simopoulos, A. I. Spadafora, I. E. Stockdale, J. J. Thaler, B. Tripsas, A. Wattenberg et al. Measurement of the hadronic structure of semileptonic D^0 and D^+ decays. Phys. Rev. Lett. 66, 1011-1014 (1991).

Studies of CP and CPT in the Neutral K System

George Gollin

Scientific and Professional Staff:

E. M. Collins, G. D. Gollin, M. Sendelbach, M. Palmer

OVERVIEW

This group performs CP and CPT studies in the K meson system at Fermilab using a twin beam spectrometer with active regenerators. Novel features of the detector include excellent veto coverage to reduce backgrounds from $K_L \rightarrow 3\pi^0$ decays, an 804-block lead glass array, and a high-rate, high-precision tracking chamber system. We have been searching for signs of a direct CP-violating amplitude in $K \rightarrow \pi\pi$ decays in Experiment 731's data. We are performing a CPT test through a measurement of $\text{Arg}(\eta_{00}) - \text{Arg}(\eta_{+-})$ using Experiment 773's data, and are searching for the decays $K_L \rightarrow \pi^0 e^+e^-$ and $K_L \rightarrow \pi^0 \mu^+\mu^-$ in Experiment 799's data. We are involved in design studies for a new direct CP experiment at the Fermilab Tevatron (E832) which will evolve into a high rate CP and rare decay search at the proposed Fermilab Main Injector.

SEARCH FOR DIRECT CP VIOLATION BY EXPERIMENT 731

(G. Blair, G. Gollin, G. Grazer, M. Karlsson, and J. Okamitsu, and in collaboration with physicists from the University of Chicago, Elmhurst College, Fermilab, and CEN Saclay)

Analysis of Fermilab E731's 1987-1988 data sample is nearing completion. We have published a number of results based on the full data set. The physics issues addressed to date by E731 publications include the following:

a) Determination of $\text{Re}(\epsilon'/\epsilon)$ in $K \rightarrow \pi\pi$ decays. If the Standard Model's description of the electroweak interaction is correct, there should be a small amplitude for CP violation which makes possible the decay $K_2 \rightarrow \pi\pi$. $\text{Re}(\epsilon'/\epsilon)$ depends on the top quark mass but is expected to be less than .001. NA31 at CERN has reported that $\text{Re}(\epsilon'/\epsilon) = .0022 \pm .0007$; a value this large is difficult to reconcile with Standard Model calculations. We do not confirm the NA31 result. Based on our full data set, we conclude that $\text{Re}(\epsilon'/\epsilon) = .00060 \pm .00058 \pm .00018$. We will submit this result for publication in late 1992.

b) Measurement of $\text{Arg}(\eta_{00}) - \text{Arg}(\eta_{+-})$ with E731's data. The phase difference between η_{00} and η_{+-} should be smaller than one degree if CPT is conserved in the K meson system. The earlier value for $\text{Arg}(\eta_{00}) - \text{Arg}(\eta_{+-})$,

$(12 \pm 6)^\circ$, came from an experiment performed more than 14 years ago. We have obtained a new measurement of the phase difference from the E731 data; our result is $(-0.6 \pm 1.4 \pm 0.8)^\circ$ from our full data set. The new result is consistent with CPT invariance and formed the basis of M. Karlsson's PhD thesis. The measurement is analysis-intensive and will probably be systematics limited once the full data sample has been processed. We will measure the phase difference with a new method in E773 (described below); the new technique minimizes sensitivity to such systematic perils as acceptance corrections and ignorance of the value of $\text{Re}(\epsilon'/\epsilon)$.

c) New limit on the branching ratio for $K_L \rightarrow \pi^0 e^+ e^-$. The decay process $K_L \rightarrow \pi^0 e^+ e^-$ is expected to contain a sizeable CP violating amplitude. As a byproduct of our ϵ' data, we have been able to obtain the limit $\text{BR}(K_L \rightarrow \pi^0 e^+ e^-) < 7.5 \times 10^{-9}$ (90% confidence level) based on 100% of the E731 data set. The Standard Model expectation is that the branching ratio should be roughly 5×10^{-12} .

d) A measurement of the branching ratio for $K_L \rightarrow \pi^0 \gamma \gamma$. To determine the CP-conserving contribution to the process $K_L \rightarrow \pi^0 e^+ e^-$, it is necessary to measure the rate for the decay $K_L \rightarrow \pi^0 \gamma \gamma$. The theory expectation is that the $\pi^0 \gamma \gamma$ branching ratio should be about 7×10^{-7} ; measurement from the full E731 data set is $(1.86 \pm 0.60 \pm 0.65) \times 10^{-6}$.

e) Simultaneous measurement of K_S and K_L decays into $\pi \pi \gamma$. We have measured the relative rates and form factors for the decays $K_S \rightarrow \pi \pi \gamma$ and $K_L \rightarrow \pi \pi \gamma$.

f) A measurement of the quadratic slope parameter in the $K_L \rightarrow 3\pi^0$ decay Dalitz plot. We have measured the quadratic slope parameter in the $K_L \rightarrow 3\pi^0$ decay Dalitz plot to be $-(3.3 \pm 1.1 \pm 0.7) \times 10^{-3}$. This is the first measurement of this parameter; its value can be used to constrain chiral perturbation theory calculations.

g) A limit on the decay $K_L \rightarrow \pi^0 \nu \bar{\nu}$. The decay $K_L \rightarrow \pi^0 \nu \bar{\nu}$ is almost entirely due to a decay amplitude which directly violates CP conservation. No previous limits on the decay rate have been reported. Our limit is $\text{B}(K_L \rightarrow \pi^0 \nu \bar{\nu}) < 2.2 \times 10^{-4}$ (90% CL). The expected Standard model rate is quite small, below 10^{-11} .

We will set limits on (or observe) a number of other rare K decay modes. This group's responsibilities in E731 have included the photon veto system and most of the scintillator banks, in addition to analysis work. The E731 data have been very rich in physics.

AN IMPROVED MEASUREMENT OF $\text{ARG}(H_{00}) - \text{ARG}(H_{+-})$
BY EXPERIMENT 773

(E. Collins, G. Gollin, W. Hogan in collaboration with physicists from the University of Chicago, Elmhurst College, Fermilab, and Rutgers University)

Systematic and statistical uncertainties limit the precision of an E731-style experiment which measures the η_{00}, η_{+-} phase difference to be about 1.5 degrees at best. The chief sources of systematic error involve the necessity of understanding the differences in detector response for K_L and K_S decays, which exhibit different decay z distributions. Resolution effects, coupled with the steeply falling z spectra, make it difficult to extract sufficient information from the experimental distributions to determine the phases accurately. In addition, ignorance of the value of ϵ' couples directly into the extracted value of the phase difference. Most of these problems are avoided by E773. The E773 detector used a pair of K_S beams created by regenerators spaced along the beam direction by 12 meters. By tuning the relative thicknesses and separations of the regenerators, it was possible to produce decay spectra which were nearly identical inside the fiducial decay volume for both beams. The E773 spectrometer was based on the E731 detector with modifications and new hardware as appropriate. To reduce possible backgrounds from inelastic and diffractive K_S production, we replaced the boron carbide E731 regenerator with finely segmented, solid scintillator regenerators. The regenerators switched beams after every machine spill.

University of Illinois contributions to E773 included phototubes, bases, and moving machines for the regenerators, controlling electronics for the movers, and additional lead/lucite photon antis. The new photon antis were built at Illinois and installed in the vacuum region between the two regenerators to veto possible background events from $K_L \rightarrow 3\pi^0$ decays. George Gollin is the spokesman for the experiment. A diagram of E773 appears in the following figure:

Figure 1. E773: $\phi_{+-} - \phi_{00}$ (elevation view)

E773 wrote 450 million triggers to tape during the first half of Fermilab's 1991 fixed target run. We are presently analyzing the run's data; we estimate E773's ultimate statistical error to be about 0.4° ; the systematic uncertainty should be less than 0.2° . All of the data have been run through the first pass analysis. Monte Carlo development and the generation of accurate calibration constants for the lead glass and drift chambers is in progress. The following figure shows mass plots for candidate $\pi^+\pi^-$ and $\pi^0\pi^0$ events from both beams. The figure represents a small fraction of the run's data.

PRELIMINARY $\pi\pi$ mass plots from some E773 data

UR beam, $\pi^+\pi^-$ decays

DR beam, $\pi^+\pi^-$ decays

UR beam, $\pi^0\pi^0$ decays

DR beam, $\pi^0\pi^0$ decays

A SEARCH FOR THE DECAYS $K_L \rightarrow \pi^0 e^+ e^-$ AND $K_L \rightarrow \pi^0 \mu^+ \mu^-$ BY EXPERIMENT 799

(E. Collins, G. Gollin, W. Hogan in collaboration with physicists from the University of Chicago, Elmhurst College, Fermilab, Rutgers University, and U.C.L.A.)

There have been a number of interesting developments in high energy physics in the last two years. CDF sees no evidence for a top quark with mass below 90 GeV. The nonzero value of ϵ'/ϵ reported by CERN has not been confirmed by our data from E731. SLAC and LEP experiments report that there are only three generations. These new results place tight constraints on the Standard Model and cast some doubt on its ability to describe completely the electro-weak interaction. Consequently, it is important to study other rare processes to check the level of agreement between experiment and theory. In particular, a search for the (unobserved) decays $K_L \rightarrow \pi^0 e^+ e^-$ and $K_L \rightarrow \pi^0 \mu^+ \mu^-$ is appropriate at this time. The decays are expected to occur with branching ratios of $\sim 5 \times 10^{-12}$ and $\sim 1.3 \times 10^{-12}$ respectively. It is expected that the dominant amplitude contributing to both decay modes is CP violating. A determination of the decay rates serves as a test of the Standard Model. Some extensions to the Model (such as the existence of a non-standard Higgs sector) could produce an unusual ratio between the muonic and electronic branching ratios.

E799 has been approved to search for the decays $K_L \rightarrow \pi^0 e^+ e^-$ and $K_L \rightarrow \pi^0 \mu^+ \mu^-$ in two runs, the first was completed in 1992. The systematic uncertainties associated with a $\pi^0 \mu^+ \mu^-$ search are very different from those of a $\pi^0 e^+ e^-$ search: backgrounds from the copious decay $K_L \rightarrow \pi^0 \pi^+ \pi^-$ with one or both pions decaying to $\mu \nu$ must be eliminated. In its first run, a transition radiation detector and fine-grained dimuon trigger hodoscope were added to the E773 spectrometer to perform the $\pi^0 e^+ e^-$, $\pi^0 \mu^+ \mu^-$ search. Expected sensitivity for $\pi^0 e^+ e^-$ and $\pi^0 \mu^+ \mu^-$ decays is approximately 3×10^{-10} from the first run and 10^{-11} from the second. Analysis of the run's data is now in progress.

DEVELOPMENT WORK FOR TRIGGER PROCESSING FOR A HIGH SENSITIVITY SEARCH FOR DIRECT CP VIOLATION AT THE TEVATRON IN EXPERIMENTS 799II AND 832

(E. Collins, G. Gollin, M. Palmer, and M. Sendelbach)

Given the strength of our electronics development group, it is natural to design and build part of the trigger system for the new experiments here. We have been investigating the possibility of using Xilinx XC3000 field programmable gate array logic cells to build a processor which will count the number of "clusters" striking the gamma detector array in E799II/E832. The conceptual

design of the system's architecture is nearly complete; the circuit diagrams for part of the processor are being developed.

The E799/E832 hardware cluster finder will count the number of contiguous depositions of energy, or clusters, in the experiment's CsI array. This information will be made available to the Level 2 trigger less than 2 μ sec after the Level 1 trigger is generated. In addition, the HCF will provide the ADC system with a list of channels whose digitization is to be included in the experiment's data stream. We will discuss the following:

- a. Clustering algorithm and Monte Carlo simulation of its effectiveness
- b. Xilinx XC3000 logic cell arrays and hardware implementation of the clustering algorithm
- c. Sparsification scheme
- d. HCF II system architecture; communication with energy summing boards and ADC's

a. Clustering algorithm and Monte Carlo simulation of its effectiveness

We will define a cluster as a set of contiguous CsI crystals which produce signals above a certain threshold. The following are examples of single clusters:

Figure 3: single clusters

Depending on details of the shapes of showers, we might want to consider illuminated crystals which only touch corners (corner fusions) to be contiguous:

Figure 4: corner fusion clusters

The definition of a cluster as a set of contiguous crystals above threshold suggests one algorithm for counting clusters which begins by linking together all

lit crystals which share edges (or corners). This linking process might require several iterations to fuse blocks in a cluster like that shown in Figure 5:

Figure 5: complicated "glue'em" cluster

For convenience, we'll refer to this as the "glue 'em" algorithm. An advantage of the "glue 'em" algorithm is that clusters with holes can be recognized and counted properly.

Another possible algorithm involves counting the number of convex and concave segments encountered traveling around the perimeter of a cluster, as in Figure 6.

Fig. 6: counting concave and convex segments

There are five convex and four concave segments; the difference in the number of convex and concave segments found in the entire CsI array equals the number of clusters. This sort of algorithm can be implemented with logic cell array chips that scan 6-crystal sections of the array. The algorithm runs quickly, but cannot count clusters with holes.

A third algorithm makes use of the fact that a complete clockwise circuit around the perimeter of a cluster includes four more right turns than left turns, as illustrated below.

The neutral beams were produced at 5 milliradians by an 800 GeV primary proton beam. K mesons were generated using the Malensek energy spectrum (FNAL report FN-341, Oct. 1981), with an additional factor of $1/E$ included to account for the K_L decay probability. The beams diverged from the target, and were 10cm x 10cm wide at the calorimeter, with 10cm spacing between inner edges. Each beam hole was a square 15cm on a side, as shown in Figure 9 below.

Fig. 9: hole geometry in Monte Carlo

Kaon decays were generated flat in z inside the decay volume. The energy spectra of decaying kaons and produced photons are shown in Figure 10.

Figure 10: K meson and photon energy spectra

Of 10,000 generated Monte Carlo decays, 3301 had all four photons striking the CsI array. The energy and z spectra for these 3301 events are shown in Figure 11.

Figure 11: Accepted K meson energy and decay position spectra

Photon clusters were generated assuming that the energy per unit area is described by the function

$$E(r,\theta) = A e^{-r/b} + C e^{-(r/d)^2}$$

where A , b , C , and d are adjustable constants, and r is the distance from the photon's impact point. Values of the parameters are shown in Table 2. (A and C are rescaled to conserve energy.)

Table 2: Monte Carlo cluster shape parameters				
	A	b	C	d
"normal"	1	3 cm	1	3 cm
"fat"	1	6 cm	1	6 cm.

Energies deposited in cells on a 5 mm x 5 mm grid were summed and assigned to the appropriate CsI crystals in the array. To model gain imbalances

and noise, the total energy in each crystal was jittered randomly on an event-by-event basis by as much as $\pm 5\%$. The cluster finder received a map of the calorimeter with bits set for blocks with apparent signals greater than 500 MeV.

The number of clusters found by the "glue 'em" algorithm is almost always the same as the number found by the HCF algorithm, whether or not corner fusions take place. With "normal" clusters ($b, d = 3$ cm), most photons are resolved into individual clusters by the "glue 'em" algorithm as shown in the following table.

Table 3: clusters vs. photons					
"glue 'em" clusters (3cm)	photons in the CsI array				
	0	1	2	3	4
4					2201
3				3450	896
2			1834	809	182
1		331	193	61	22
0	8	10	3	0	0

The HCF algorithm usually agrees with the "glue 'em" algorithm:

Table 4: HCF vs "glue 'em" clusters					
HCF clusters (3cm)	"glue 'em" clusters				
	0	1	2	3	4
4					2201
3				4346	0
2			2821	0	0
1		602	4	0	0
0	21	5	0	0	0

All events with disagreement between the two algorithms had several photons fusing near a beam hole. Even when "fat" clusters are generated, the agreement between the HCF and "glue 'em" algorithms is very good, as shown in Tables 5 and 6.

Table 5: clusters vs. photons					
"glue 'em" clusters (6cm)	photons in CsI array				
	0	1	2	3	4
4					939
3				1855	1357
2			1277	2027	821
1		279	665	425	184
0	8	62	88	13	0

Table 6: HCF vs. "glue 'em" clusters					
HCF clusters (6cm)	"glue 'em" clusters				
	0	1	2	3	4
4					939
3				3205	0
2			4047	7	0
1		1429	78	0	0
0	171	124	0	0	0.

The number of blocks per cluster is a function of the cluster size parameters, b and d , as shown in Figure 12.

Figure 12: blocks per cluster with two different sets of shape parameters

In conclusion, the HCF algorithm almost always agrees with the “glue ‘em” algorithm when applied to $2\pi^0$ decays, and should work well as part of the level 2 trigger.

b. Xilinx XC3000 logic cell arrays and hardware implementation of the clustering algorithm

We will base the architecture of the HCF II around Xilinx CMOS XC3000 family logic cell arrays. Each XC3042 chip contains 96 I/O Blocks and 144 Configurable Logic Blocks (CLB's) in a 132-pin package. Nearly arbitrary interconnections between the chip's input/output pins and CLB's can be established by the I/O Blocks. In addition, interconnect resources on the chip allow complicated logic structures to be built from many CLB's. A schematic diagram of part of an XC3042 and a simplified diagram of a configurable logic block are shown in Figures 13 and 14.

Fig. 13: Xilinx logic cell array

Figure 14: CLB

Note that each CLB contains an arbitrary function generator which produces two output bits for patterns of five input bits.

The cluster counting algorithm can be implemented by calculating a "pattern weight" for overlapping groups of four blocks by presenting a raster scan of the CSI array to the HCF, as indicated in Figure 15.

Figure 15: cluster counting algorithm

The pattern weights associated with various combinations of "lit" and "unlit" blocks are indicated in Table 7.

Table 7: pattern weights	
pattern of struck blocks	pattern weight
0
1 (one right turn inside the cell)
0
-2 to fuse clusters which touch corners (two left turns inside the cell) +2 to separate clusters which touch corners (two right turns inside the cell)
-1 (one left turn inside the cell)
0

Because there are four possible pattern weights, the combinatorial function generator of a single CLB can generate the desired value. After each row is processed, the values are summed and the result is added to the sum from previous rows. By the time data from the entire CsI array is processed, the accumulated sum of pattern weights will equal four times the number of clusters. Two XC3042 chips can process an entire CsI row's worth of data simultaneously. Since the CsI information will be presented in a raster scan, a pair of chips could process the entire CsI array's data in 40 cycles. The HCF algorithm lends itself well to parallel generation of pattern weights, and we plan to build the processor so that it takes about 11 cycles to complete its task. Based on documentation from Xilinx, we estimate that one cycle will require 60nsec. Tests, to be conducted in the near future, will give us a more accurate picture of the XC3042's performance.

c. Sparsification scheme

The HCF will provide the ADC system with a bitmap indicating which CsI channels' digitizations are to be included in the experiment's data stream. Additional Xilinx chips will be used to set bits for one or two rings around blocks which are above threshold, as indicated in the figure below. All blocks in the rings or above threshold will be read out, as indicated in Figure 16.

Figure 16: sparsification via construction of perimeter rings

The algorithm for building a ring is best described graphically, as shown in Figure 17.

Figure 17: ring construction algorithm

As with the cluster counting algorithm, sparsification calculations can be done in parallel for different sections of the CsI array; construction of two rings around clusters will take about 14 cycles, each of 60nsec duration.

d. HCF II system architecture; communication with energy summing boards and ADC's

The HCF will consist of a router board, four processor boards, and an inverse router board. The router board will receive the bitmap of CsI blocks above

threshold and send parts of this bitmap to the processor boards. The processor boards will generate pattern sums for the cluster counting algorithm and sparsification bitmaps. The inverse router board will recombine the sparsification bitmaps from the processors and send the readout bitmap to the ADC system. A diagram of the HCF system's architecture follows, in Figure 18.

Figure 18: HCF II architecture

Communication between the HCF, the ADC's, and the summing circuits which produce the bitmap of blocks above threshold is shown in Figure 19. Signals are passed to the HCF on ribbon cables, carrying 160 bits per clock cycle. All data and control signals are differential ECL.

Figure 19: HCF - ADC communication

A timing diagram for some of the signals exchanged between the various section of the clustering and ADC systems is shown in Figure 20. It will take 600 nsec for the complete CsI bitmap to be delivered to the HCF; cluster counting can take place while data is being received. It is likely that the cluster counting and sparsification will be finished 1 μ sec after data begins to arrive at the HCF. It seems almost certain that no more than 2 μ sec will be needed to count clusters.

Figure 20: HCF system timing

PUBLICATIONS

V. Papadimitriou, A. Barker, R.A. Briere, L.K. Gibbons, G. Makoff, J.R. Patterson, S. Somalwar, Y.W. Wah, B. Winstein, R. Winston, M. Woods, H. Yamamoto, E.C. Swallow, G.J. Bock, R. Coleman, J. Enagonio, Y.B. Hsiung, K. Stanfield, R. Tschirhart, T. Yamanaka, G.D. Gollin, M. Karlsson, J.K. Okamitsu, P. Debu, B. Peyaud, R. Turley, and B. Vallage: A Measurement of the Branching Ratio of the Decay $K_L \rightarrow \pi^0 \gamma \gamma$, *Phys. Rev. D* **44**, 573 (1991).

S.V. Somalwar, A. Barker, R.A. Briere, L.K. Gibbons, G. Makoff, V. Papadimitriou, J.R. Patterson, Y.W. Wah, B. Winstein, R. Winston, H. Yamamoto, E.C. Swallow, G.J. Bock, R. Coleman, J. Enagonio, Y.B. Hsiung, E. Ramberg, K. Stanfield, R. Tschirhart, T. Yamanaka, G.D. Gollin, M. Karlsson, J.K. Okamitsu, P. Debu, B. Peyaud, R. Turley, and B. Vallage: A Measurement of the Quadratic Slope Parameter in the $K_L \rightarrow 3\pi^0$ Decay Dalitz Plot, *Phys. Rev. Lett.* **68**, 2580 (1992).

G.D. Gollin: CPT Tests With Kaons, proceedings of the Arthur Rich Memorial Symposium on Time Reversal Violation, Oct. 25-26, 1991, University of Michigan, P.H. Bucksbaum et al., eds., Ann Arbor, Michigan (1991); University of Illinois preprint UIUC-HEPG-92-1.

The HiRes Detector

Thomas A. O'Halloran, Jr.

Scientific and Professional Staff:

D. Bird, R. W. Downing, T. A. O'Halloran, Jr.
M. Kidd, V. J. Simaitis

OVERVIEW

HiRes is a detector located at Dugway Proving Grounds approximately 100 miles from Salt Lake City, Utah. It is being built by a collaboration consisting of Adelaide University, Columbia University, and the University of Utah. When completed, it will detect cosmic ray showers with improved resolution, an order of magnitude above current experiments. The experiment will offer a unique blend of astrophysics and particle physics. The higher energies attainable with this detector will allow us to address the question of galactic or extra-galactic origin of these particles and to measure the energy spectrum at energies for which theorists have predicted deviations from the power law exhibited at lower energies. The detector will also measure showers significantly higher than any energy attainable by terrestrial accelerators and we will search for deviations in shower development that were not seen at lower energies.

ACCOMPLISHMENTS IN FY1992

The University of Illinois participation in the construction of the prototype was severely limited by the funding available. While we had anticipated participating in a major way in the design of the electronics for the prototype, this had to be abandoned due to a lack of personnel. We have provided advice for the ordering of the electronic components for the Utah design of the basic electronics. We also have not been able to participate in the system design for the entire experiment. Both of these aspects would benefit from the experience of the Illinois group, but more funding is needed.

We have participated in the development of the on-line data acquisition and the on-line display. These programs have been used for the initial test of the prototype utilizing laser shots and have been quite successful. This work will continue.

It is obvious that a lot of the analysis that will be done for this experiment can be done utilizing the software packages available at Fermilab and CERN. We have begun to analyze the cosmic ray events utilizing the programs available from CERNLIB, for example, and we will introduce the rest of the cosmic ray group to

some of the techniques which are currently being used in the high energy physics program.

The most successful thing that we have proposed is to replace the existing buildings that house the mirror enclosures and the electronics with modified grain bins. The first modified bin has been assembled in Urbana and is now in the process of being shipped to Utah to be assembled on site. The modified bin will have an opening aperture that allows one design for all mirrors. Since it is still in the design stage, it is difficult to give a final number for a bin that has all the features necessary to protect the experimental apparatus, but some estimates indicate that the bins could be as much as \$750K cheaper than the current design. A second bin will be assembled at Urbana to work out some of the bugs we discovered during the initial construction, but it is then anticipated that we will have a final design.

It is obvious that there is a great need for the utilization of the engineering experience in electronics and in systems design that the Illinois group has acquired by participating in accelerator physics experiments at all of the various national laboratories. The present level of funding for this task prohibits the utilization of this experience. This is unfortunate.

FUTURE ACCOMPLISHMENTS.

DOE has indicated that the funding for this task will terminate at the end of October, 1992. We are in the process of preparing a proposal to DOE for funding. If this proposal is not approved, there will be no further participation by the Illinois group in this experiment.

PUBLICATIONS

L. Borodovsky, D. Bird, R. Downing, T. A. O'Halloran, V. Simaitis et al. The high resolution fly's eye (HiRes): Parameters and motivation. Proc. of the 22nd Intl. Cosmic Ray Conf. (Dublin, Ireland; 1991) (To appear).

W. Au, D. Bird, R. Downing, T. A. O'Halloran, V. Simaitis, M. Kidd et al. Description and status of the high resolution (HiRes) fly's eye experiment. Proc. of the 22nd Intl. Cosmic Ray Conf. (Dublin, Ireland; 1991) (To appear).

J. Borodovsky, D. Bird, R. Downing, T. A. O'Halloran, M. Kidd and V. Simaitis. Observation of real and simulated showers using the first two high resolution fly's eye (HiRes) mirrors. Proc. of the 22nd Intl. Cosmic Ray Conf. (Dublin, Ireland; 1991) (To appear).

Computational Facilities (Task Group F)

Jerald J. Wray

Scientific and Professional Staff:
Jerald J. Wray, David D. Lesny

OVERVIEW

Descriptions of the duties of Task Group F, the computer subgroup, the types of work we expect to be carried out on the High Energy Physics Group's computer facility and the plan guiding the direction of the facility's development were provided in the June 1991 proposal. They are summarized in the following two sections.

COMPUTER SUBGROUP SERVICES

Members of the computer subgroup operate and maintain the computer and network systems which support the High Energy Physics Group's (HEPG) research efforts. Part of their duties include helping other group members use the systems effectively. The subgroup members

- provide general system consulting,
- write and maintain "system level" routines,
- identify and evaluate potentially useful software packages,
- help users with special packages, as needed,
- arrange for appropriate hardware and software maintenance,
- install new releases of software,
- install software and set up the VAX Cluster machines to act as servers to other computers on the network,
- monitor system and network performance and initiate corrective actions when there are problems,
- coordinate with other groups as appropriate,
- reconfigure hardware on individual machines or the whole VAX cluster as needed.

They also do the long range planning for the computer facility after consulting with other group members, and they prepare budgets for standard operation and maintenance, as well as for system upgrades. They have no other duties at the University which require large blocks of time.

THE GENERAL SYSTEM CONCEPT

Most experiments the Group's physicists are involved in take so much data that the primary data reduction must be done on larger systems maintained for

that purpose, usually at the national labs where the experiment was run. The uses of Group computer system in Urbana are expected to be mainly program development, some design work, equipment testing, limited data reduction work (mostly for test purposes), and extensive Monte Carlo simulations, and physics analysis.

The Group facility is planned so it 1) can be expanded incrementally when needed, 2) is flexible, allowing a machine to be removed for lab work or returned for general use without causing major problems, 3) can be utilized with a minimum of information about the exact configuration, and 4) can be managed reasonably straightforwardly.

PROGRESS TO DATE IN 1992

In recent months the Computer subgroup has accomplished important parts of the upgrades which had been proposed, enhancing the productivity of the physicists using the system. Toward the end of the 1991 contract year we ordered a DECStation 5000/240, the RISC machine which was part of the special computer facility upgrade that was undertaken in 1991. We were also able to add several gigabytes of needed disk storage and four 5GB Exabyte tape drives at that time. This equipment has been installed since the beginning of the year.

We have installed additional Ethernet based X-windows type terminals, reducing the number of RS232 terminal lines needed. This and the return of a terminal server which had been in use at an experiment at Fermilab allowed us to replace our obsolete Gandalf port selector with faster servers, equipment for which we can reliably get spare parts. There are no free ports on the terminal servers so an additional server may be needed in the future.

Two Cluster VS3500s will be moved to laboratory test stands in the very near future - one replacing a MicroVAX II whose slowness was becoming a problem and the other as part of establishing a laboratory setup for a new faculty member. Two VS4000 Model 60s will replace them in the VAX Cluster. The VS3500s will continue to be available to cluster users when they are not in use as test stand controllers.

The faculty member whose laboratory will be using the VS3500 needed a relatively fast machine with a Q-bus -- requirements met by the VS3500. She is providing a VS4000/60 as a replacement for the HEPG cluster using funds from her new faculty start up monies. This has allowed us to add significantly to the power of the cluster and at the same time address some laboratory needs. These are examples of the flexibility and expandability of the cluster system.

Adding the above equipment has made it significantly easier to do physics analysis on this system. The additional disk space allowed one group to skim

selected events from several hundred data tapes (containing approximately 500 GBytes of data) in about a two week period, processing which would have taken at least two months without the disks. The space also allows groups to have much larger data samples available for multiple analysis passes, improving the timeliness and quality of the physics analysis.

Physicists have found that terminals with multi-windowing capabilities and reasonable graphics are valuable in their work. Complex combinations of tasks are frequently much more easily handled by having multiple windows, and the developing standards are making it easier to have active sessions on multiple machines, all controlled from one terminal.

The VS4000/60s, which are rated at approximately 12 SPEC marks, will provide higher capacity processors. Although our client/server software allows all the cluster machines to participate in processing of large data sets, it does require some effort to use effectively. There are some processing tasks which are not large enough to make using multiple processors practical but which require enough cpu time to make running on a faster processor highly desirable. Both types of jobs will benefit from these additions.

Since the first of the year we have installed new versions of of the operating systems for both the VMS and Ultrix machines. The new version of VMS supports version one of the Digital Equipment Corporation implementation of the Posix standard, an important step in making programs truly portable between different platforms. Other vendors have also announced that they will be supporting the Posix standard.) The new version of Ultrix makes it possible to use the newest DEC RISC platform and also improves other services on those machines. A move to an OSF/1 based operating system for these machines is expected in the future, and this should eventually lead to improved interoperability of many programs.

We have also installed software which allows the VAX Cluster to act as a file and print server for the Macintoshes used by some faculty members. This allows them to use the VAX laser printers and also provides larger disk spaces than most personal computers have. Using this network we provide them with the full file backup service of the Cluster.

There are certain classes of problems for which the RISC machines work quite well, and they are used extensively for them. Most users who do use them find that the ideal mode of operation is to use VMS for interactive work and the RISC machines running Ultrix for heavy data processing in a batch mode. Management problems are still complex because different platforms and operating systems require quite different knowledge and skills to make them function smoothly. Software evolution is heading in directions which will simplify these complex tasks, and we may see some significant progress in this area during the year. Standards for Remote Procedure Calls and for other

distributed services will make sharing loads with a variety of machines much easier.

During the remainder of this grant year we anticipate that we will add more disk storage, possibly expand the memory on some machines and install more X-terminals. More cpu power may be needed, but if it does not cause undue delays in the research of the group we will delay these acquisitions until the capabilities of the new generations of RISC based machines are better known, information which should be available by the end of the year.

Electronics Support

Robert R. Downing

Scientific and Professional Staff:

M. Haney, V. Simaitis, B. Whitten, L. Peek, H. Scott

FY92 ACCOMPLISHMENTS

The primary task of the engineering group is the support of experiments undertaken by other members of this contract. This support is in the design, construction, and testing of electronics and associated hardware for specific experiments.

The secondary task of this group is to acquire, develop, and employ general purpose CAE "tools" which can be used to support current and future needs of the researchers on this contract. This task, along with other SSC and related tasks, will be developing methods for high level simulation of physics data acquisition systems. We will be updating our old and acquiring new CAE tools on a regular basis. Analog and mixed analog/digital simulation will become a larger part of our efforts as higher speed technologies become viable. Analysis tools for transmission lines, thermal, mechanical, etc. will have to be added to the design software tool set.

We have obtained a programmer for PAL's, PLA's, FPGA's, etc. and CAE software which interfaces to it. We can simulate and then directly transmit the data to the programmer. Using FPGA's we can compact many chips of logic into one saving board space and increasing reliability.

We will continue to supply our internally developed simulation tools to others in the Physics community. FNAL, SLAC, Los Alamos, CERN/LEP and TRIUMF are using these tools to simulate FASTBUS modules. We regularly cooperate with standards groups and other general organizations which aid the entire physics community.

We have finished the Muon system upgrade at CDF. This consists of the Level 1 and the Level 2 trigger logic and associated electronics. We are beginning the design of the new muon electronics for the main injector/CDF upgrade. The higher luminosity will necessitate a different approach to the muon system. We are using some of the CAE tools development for SSC experiments by this contract and a TNRLC contract.

A further upgrade to E773 at FNAL is being designed. We are using the FPGA programming tools to develop a fast cluster finder. The hardware will be built in FASTBUS.

We have started work on electronics for the Fly's Eye cosmic ray experiment in Utah. We are consulting with LeCroy Electronics on a prototype high voltage monitoring and distribution system. By the end of this budget period, we will have finished a prototype design for a flash ADC board which may replace the current analog electronics. A final decision will be made after extensive field tests. A prototype mirror "house" has been constructed at Illinois. This building was tested and shipped to the Dugway site. A second house with some refinements has been built and its design will be the basis for a large contract to construct about 100 buildings in Utah.

We will also have to analyze the harsh environment impact on the electronics. The desert is very different from the relatively benign environment found in the typical high energy physics experiment. We are applying our large experiment knowledge to the site and looking at all aspects of the design and operation of the electronics. This has gone somewhat slowly due to a lack of funds.

**DATE
FILMED**

7/15/92