DOE/CE/15466--T7

**Coal Log Pipeline Research at the
University of Missouri**

DOE/CE/15466--T7

1st Quarterly Report for 1992

DE92 010809

Issued in March 1992

**Henry Liu
Professor and Director
Capsule Pipeline Research Center**

Project Sponsors:

**U.S. Department of Energy (Energy Related Inventions Program)
National Science Foundation (I/UCRC Program)
State of Missouri (Department of Economic Development)
Coal Log Pipeline Consortium:**

**Arch Mineral Corporation
ARCO Pipe Line Company
Associated Electric Coop.
Kansas City Power and Light
MAPCO Transportation, Inc.
Peabody Holding Company
Union Electric Company
Williams Pipe Line Company
Williams Technologies, Inc.**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Content

Page

(I)	Summary Report to DOE about the three Project Tasks	i
(II)	Individual Projects Progress Reports	
1.	Coal Log Fabrication (Marrero, Berg and Burkett)	1
2.	Compaction of Binderless Coal Logs (Gunnink and Liang)	5
3.	Water Absorbance and Permeability (Luecke)	15
4.	Coal Log Fabrication -- Design Fixture for Underwater Extrusion (Lin and Wang)	22
5.	Coal Slurry Capsule Pipeline System (Seaba)	26
6.	Coal Log Pipeline Activities at Rolla Campus (Wilson and Ding)	28
7.	Control of Small-Scale Coal Log Pipeline System (Nair et al.)	35
8.	Legal Aspects of Future Coal Log Pipeline Systems in the United States (Davis)	40
9.	Train Behavior Experiment in Coal Log Pipeline (Richards)	42
10.	Water Hammer in Hydraulic Capsule Pipeline (El-Bayya)	44
11.	Prediction and Control of Water Hammer in Pump Bypass (Phimjaichon)	46
12.	Revising Economic Report (Liu and Zuniga)	48a

DOE Project Quarterly Report

Prepared by Henry Liu, March 1992

Project Title: Coal-Log Pipeline System Development

Contract Number: DOE DEFG0190 CE 15466

DOE Program: Energy-Related Invention

DOE Technical Monitor
(Invention Coordinator): Glenn K. Ellis

Project Period: August 24, 1990 - June 30, 1992

Project Tasks:

1. Perform the necessary testing and development to demonstrate that the amount of binder in coal logs can be reduced to 8% or lower to produce logs with adequate strength to eliminate breakage during pipeline transportation, under conditions experienced in long distance pipeline systems. Prior to conducting any testing and demonstration, grantee shall perform an information search and make full determination of all previous attempts to extrude or briquette coal, upon which the testing and demonstration shall be based.
2. Perform the necessary development to demonstrate a small model of the most promising injection system for coal-logs, and test the logs produced from Task 1.
3. Conduct economic analysis of coal-log pipeline, based upon the work to date. Refine and complete the economic model.
4. Prepare a final report for DOE.

Quarterly Report No.: 6

Period Covered: November 26, 1991 - February 25, 1992

SUMMARY REPORT

Task 1

Work continued in coal log fabrication pertaining to both extrusion and compaction. We have been able to make coal logs by extrusion using as little as 4% binder (asphalt), and by compaction in a mold using no binders at all - binderless extrusion. However, the logs produced, when immersed in water under high pressure (500 psi), soaked 20 to 30% of water by weight which is excessive. Also, the logs are weakened after the water absorption test. Efforts have been initiated to test ways to eliminate or reduce water absorption of logs. These include improving coal particle size distribution to form logs with a higher density and less voids, applying a sealant to the log surface, manufacturing logs having an impermeable outer layer high in asphalt concentration, heat treatment of coal log surface to form an impermeable crust, use of a special binder that reportedly repels water (Macrotech process)¹, and the use of a special coal drying process (Rosebud process)² that reduces sulfur in coal and prevents moisture reabsorption. Details of our work in coal log fabrication are described in the attached reports submitted by Dr. Gunnink, Dr. Marrero, Dr. Luecke, and Mr. Burkett.

Task 2

The DOE contract requires us to build a small-scale demonstration model of a multi-branch coal log injection system controlled by computer. We have exceeded this goal by building a complete model of coal log pipeline including not only the injection system but also the pump bypass (booster station) and the coal log ejection systems, all controlled by a single personal computer.

The model has been completed, tested, improved, and demonstrated to the public during the Engineers' Week Laboratory Exhibition. It ran smoothly except for occasional clogging. Work is now underway to further improve the system so that it will never or rarely clog. Work is also underway to write a manual documenting the design and operational procedures. See attached report prepared by Professor Nair for details.

-
1. The Macrotech Corp. in Paris, Tennessee claims to have found a chemical that binds coal and repels water. We have sent coal to the company to make logs for testing in our laboratory.
 2. The Rosebud process, a DOE sponsored Clean Coal Demonstration Project, is under development by the Rosebud Syncoal Partnership at the Rosebud Mine in Montana. The company claims their treated coal does not reabsorb water. We are in the process of contacting the company for possible application to coal log pipeline.

Task 3:

Work is continuing in updating the economic report. The work will be completed by the end of the DOE project which is June 30, 1992. Three completed Appendices are attached.

Other Tasks:

Other tasks outside the scope of the DOE contract, supported by NSF, the State of Missouri, and the CLP Consortium, are briefly summarized as follows:

1. The underwater extrusion study has started. The test system has been designed, and materials for fabricating the system are being ordered. It is expected that the system can be fabricated by May 1, and then it will be used to test the concept of coal log extrusion directly into a pipe filled with water under pressure. It is anticipated that better logs can be made in this manner than direct extrusion into air. The attached report by Dr. Lin briefly discusses this work.
2. Due to savings in other areas, it was possible to initiate a new area of investigation consisting of using coal-water slurry (rather than water alone) as the medium for suspending and transporting coal logs. Since coal slurry has a density close to that of coal logs, it can suspend coal logs more easily than water can. This may result in less abrasion to the logs transported through pipelines, and will further increase the coal-to-water ratio in the pipe. It may be a practical alternative to using water alone as the medium for coal log transport. A laboratory set-up to test this new concept is being designed by Dr. Seaba. He will spend the next three months completing the design and fabricating the system, so that he will be able to test this new concept this Summer. See his report attached.
3. We have received an EPRI (Electric Power Research Institute) grant on the end-of-pipeline study and handling of coal logs at power plants. Most of the research is being done at the Rolla campus under the direction of Professor John Wilson, Chairman of Mining Engineering Department. Dr. Wilson's report is attached.
4. Professor Peter Davis of our Law School has been working on the legal aspects of coal log pipelines including the right of eminent domain, water rights and so forth. Preliminary finding of his study is described in the attached report written by him, and in more details in a paper submitted to an international conference for presentation in July.

5. As part of the required technology transfer program of the Capsule Pipeline Research Center, a short course on hydraulic transport of solids by pipeline has been organized. It will be offered in Kansas City, June 8-9, 1992. See tentative program attached.
6. The Capsule Pipeline Research Center has moved into a set of renovated offices, and a Coal Log Fabrication Laboratory has been established. The College of Engineering has given the Center \$59,600 to purchase several pieces of major equipment for the laboratory -- see Burkett's report under Marrero's report attached.
7. Other activities can be seen from the attached reports.

It should be apparent that the coal log pipeline research has entered into a new phase of extensive R&D designed for early commercialization of this emerging new technology.

INDIVIDUAL PROJECTS PROGRESS REPORTS

for period Nov. 26, 1991 - Feb. 25, 1992

Prepared in March 1992

Coal Log Fabrication

T.R. Marrero¹, D.M. Berg², and W.J. Burkett³

Department of Chemical Engineering

University of Missouri - Columbia

Introduction

Coal log fabrication efforts during the period of December 1, 1991 to February 29, 1992 are summarized as follows. The progress includes the preparation of three papers for publication, renovating new lab space, ordering new equipment, constructing a high pressure chamber, a grinding test, completing the extrusion experiments on a Powder River Basin coal (Hanna), and preparation of logs for end-of-pipe studies. Contacts with industry continue; this effort has been enhanced by the efforts of Dr. John Wilson. Water absorption tests of logs made without binder were conducted. One additional graduate student joined the project, a PhD candidate in chemical engineering; he will study the effects of temperature on coal particle agglomeration - a prelude to using heat to form an impermeable coal log surface.

During the next quarter, the lab arrangements should be established, major purchases received, another coal tested by extrusion, plus the log manufacture for the end-of-pipe study completed, and a paper and thesis for the PRB coal log extrusion study written. Direct travel to involve companies from Wyoming and Montana will be undertaken, if possible.

The Electric Power Research Institute (EPRI) project manager will visit in April to discuss the end-of-pipe study.

Publications

The papers prepared for publication are as follows:

1. "Extrusion of Coal Logs with Coal-Asphalt Mixtures," (Proceedings of the Institute of Briquetting and Agglomeration, 22nd Biennial Meeting, San Antonio, TX, November, 1992)
2. "Extruded Coal Log Performance Characteristics," (to be presented at the 17th International Conference on Coal & Slurry Technologies, Clearwater, Florida, April, 1992)

-
1. Associate Professor of Chemical Engineering and Associate Director, Capsule Pipeline Research Center.
 2. Research Associate, Capsule Pipeline Research Center
 3. Research Assistant, Capsule Pipeline Research Center

3. "Coal Log Fabrication by Extrusion,"
(submitted for presentation at the 7th International Symposium on Freight Pipelines, Wollongong, Australia, July, 1992)

In addition to these, short reviews of coal log pipeline technology have been sent to "Coal Voice" and the "Engineering and Mining Journal." These two write-ups are co-authored with John Wilson.

Lab Renovation (W.J. Burkett)

Preparation of space to consolidate experimental activities to support the development work was a major task. Space dedicated to the Capsule Pipeline Research Center became available at the end of the year upon the completion of the new addition to the Engineering Building. Refurbishing of the area was started in coordination with the relocation of the Civil Engineering Department's equipment. Requirements for the space were divided into the following areas:

- a) Main Experiments - coal log extrusion, water absorption (low and high pressure, cyclic), and binderless compaction. These experiments will generate little dust.
- b) Coal Mixtures Preparation - The following preparations will generate considerable dust: coal screening asphalt handling, and coal-asphalt mixing.
- c) Supporting Experiments - In a dust free area certain auxiliary experiments will be conducted. These tests include: coal-log/water corrosion, and coal-asphalt water permeability.
- d) Assigned Student Desk Area.

Space and utility needs for each area were defined and an overall laboratory layout finalized.

Three ventilation systems will be used. A high vacuum dust-filtration system will be connected to each high-dust operation. This will control major dust sources by keeping them to a limited area which is easily cleanable. A second ventilation system will continuously purge the high dust area. This will remove the fumes from the drying area and the asphalt heating and mixing operations. This air will be vented outside the building. A carbon monoxide analyzer and smoke detector are also installed in this area. The third system is an exhaust fan that will vent air from the major experimental area; this will be particularly helpful during the summer.

Utilities are being connected to all areas. The water absorption unit (6 cells) has been relocated and is in operation. The binderless compaction unit is also in operation. Two extruders will be relocated as soon as the dust filtration equipment is

delivered. The high pressure cyclic water absorption test chamber is awaiting equipment deliveries for final assembly. A hot water heater was installed, plus two sinks.

Lab Equipment (W.J. Burkett and T.R. Marrero)

The Center has received an allocation of equipment fund of \$59,600 from the College of Engineering. Equipment specifications have been written and forwarded to procurement. Some bids have already been received for evaluation. Equipment to be purchased includes the following:

A new large multi-screening unit to separate particle sizes from the raw coal samples will replace the unit borrowed from Civil Engineering.

Experience with extrusion tests has demonstrated the need for automatic data acquisition of ten variables. This acquisition system will be installed on the relocated extrusion line.

Moisture content of the coal is an important variable in both the binderless compression and coal-asphalt extrusion. A new moisture analyzer will allow more accurate, consistent, and faster results.

A compaction unit will allow small samples to be compacted under various conditions to help define the optimum extrusion and binderless conditions for the various coals. This unit will have the capability of producing 35 tons of force. It will also be automated to precisely determine the compression time.

A particle size analyzer will measure the particle size distribution for the various coals. This will allow size and area to be determined for extrusion and compaction experiments.

A small multi-sieve shaker will supply various particle distributions for small samples.

A constant coal-asphalt feeder for the extrusion line will eliminate variable screw loading due to bridging in the final hopper.

A variable speed belt conveyor will carry the coal-asphalt log as it is extruded.

The consolidation of the various experiments from four locations to this new single dedicated laboratory will be a key factor in allowing better use of the new equipment and enhance communication between various individuals working on coal log fabrication.

Extrusion Tests (D.M. Berg)

Extrusion trials of Hanna coal (Carbon County, Wyoming) were completed in addition to testing the coals for compressive strength and water absorption. These results are being evaluated and will be reported in detail during the next quarterly report. The minimum amount of binder used in this study (Asphalt Cement - 20) was 4 percent to produce logs; extrusion temperatures were about 75° C. The water absorption at 500 psi amounted to slightly more than 20%.

Logs for End-of-Pipe Tests (T.R. Marrero)

As part of the EPRI project, an initial 20 pound batch of eastern coal was extruded and the logs sent to Rolla for immersion in water and subsequent grinding tests by Dr. Wilson's group. Earlier attempts were made to extrude lignite but this type of coal behaved completely different than others. Lignite extrusion will be done last, after all the other coal types have been extruded.

Grinding Test (W.J. Burkett)

A mixture of 5% asphalt and coal which was typical feed to the extruder was sent to the T.J. Gundlach Company for grinding. This material was first sent through a 3/8" grinder which broke up large agglomerates to the 3/8" maximum size particle. The material from the grinder was then sent to a solid wheel grinder with 1/16" spacing between the wheels. Both grinders ran 300 lbs of material with very little indication of buildup on the wheels.

Although this was not an exhaustive quantitative test, it once again showed that grinding the coal asphalt log at the receiving end (power plant) was not likely to be a major problem.

COMPACTION OF BINDERLESS COAL LOGS FOR COAL PIPELINES

by
Brett Gunnink¹ and Zhouxiong Liang²

INTRODUCTION

Coal log pipelines transport compacted coal cylinders (logs) through a water filled pipeline. In order to fully develop this technology and make it ready for commercial use it is necessary to investigate means for fabricating coal logs. This paper describes one of the means for fabricating coal logs that is being investigated as part of the research and development program of the Capsule Pipeline Research Center at the University of Missouri-Columbia.

The production of coal compacts from loose coal particles is not new technology. There is considerable literature available on coal briquetting practices and graphite parts fabrication that contains information applicable to the fabrication of coal logs. Several parameters have a significant effect on the strength of binderless coal compacts. For a given coal these parameters include compaction temperature and moisture content, maximum compaction pressure and application duration, and coal particle size distribution. In addition, there is considerable evidence that performing the compaction process under vacuum allows compacts of comparable strength to be produced at much lower compaction pressures. This paper describes the experimental tests, and preliminary results, that are being conducted to investigate the significance of these variable compaction conditions and determine optimal compaction conditions.

COMPACTION PARAMETERS

There is much information in the literature concerning the fabrication of briquettes from brown coal and bituminous coal. The western subbituminous coals that are being tested in this study have characteristics somewhere between these two types of coal. Consequently, much valuable information can be gained concerning probable optimal conditions for the fabrication of coal logs from an examination of coal briquetting processes. The variables selected to be examined as part of this study were determined based on a review of coal briquetting processes.

It was concluded that the variables that have the greatest influence on the quality of the compacted coal logs include compaction moisture content, compaction temperature, maximum compaction pressure and duration, and maximum coal particle size and particle size distribution.

Most commercial processes begin by drying the coal to the desired moisture content at an elevated temperature (350 °F) and then allow the coal to cool to the desired compaction

¹Asst. Prof., Dept. of Civil Engr., Univer. of Missouri-Columbia, Columbia, MO 65211, (314) 882-3299

²Graduate Assistant at same address

temperature. The reported compaction pressures required to make briquettes vary from 1000 psi to 70,000 psi. At the high end of this range the compaction process is dynamic with compaction pressure being applied for only a split second. Further, with this sort of dynamic compaction the build up of air pressure within the compact causes the gross interparticle pressure to be only a fraction of the total applied pressure. Further, cracking of the compacts has been a problem with dynamic compaction operations. This results from the relative quick release of axial pressures and results in cracked compacts.

COMPACTION APPARATUS

An apparatus suitable for the compaction of 1.75 inch diameter by 3.5 inch long logs has been designed and constructed for use in this study. The compaction apparatus, shown schematically in Figure 1, consists of a cylinder and two pistons placed in a hydraulic testing machine. Compaction occurs when an axial load is applied to the pistons and both pistons move relative to the cylinder. The cylinder is not physically attached to the testing machine and is held in place by friction between the cylinder and the coal log. To provide uniform pressure through the length of the coal log, frictional forces between the log and the cylinder must be minimized. The use of a "floating" cylinder and a finely machined cylinder surface combine to minimize these frictional forces. The apparatus can be sealed for vacuum compaction. The pistons are vented to relieve some of the air pressure that builds up within a coal log during compaction. Resistive heaters surround the cylinder during the compaction process so that the cylinder temperature is constant. Further, the heaters keep the coal at the desired temperature during the compaction process. The ends of the cylinder are equipped with manifolds for applying and monitoring the evacuation of the cylinder if the log was compacted under vacuum. A temperature control system for the resistive heaters is used to set and control the temperature of the system.

During the compaction process, axial load and deformation data are collected. A computer based data acquisition system is used for the collection and processing of this data.

MATERIALS

The coal used for this study was a Powder River Basin coal from the subbituminous coal fields of Montana. The coal had a maximum particle size of 1/8 inch. Fifty percent, by weight, of the material was smaller 1/8" but larger than the ASTM No. 8 sieve. Twenty one percent was smaller than the No. 8 sieve but larger than the No. 16 sieve. Twelve percent was smaller than the No. 16 sieve but larger than the No. 30 sieve. Nine percent was smaller than the No. 30 sieve but larger than the No. 50 sieve. Five percent was smaller than the No. 50 but larger than the No. 100 and three percent was smaller than the No. 100 sieve.

TEST METHODS AND PROCEDURES

The process for fabricating a coal log begins by oven drying the various size fractions of coal in a 105 °C oven until the weight of the coal has stabilized. Hot water is then mixed with the hot coal and the mixture placed in the compaction apparatus which has been pre-heated to the desired compaction temperature. The temperature of the coal is then measured and the

COAL COMPACTION APPARATUS
MATL: TYPE 410 STAINLESS STEEL
QTY: 1

Figure 1 - Schematic of coal log compactor.

temperature of the system adjusted until the coal, water and compactor are all at the desired compaction temperature. The axial compressive force is then applied. When the compaction force has been removed, the residual radial stresses in the log are quite high. These high radial stresses create a large friction force on the cylinder wall and as a result it takes a considerable amount of force to eject the logs when these stresses are present. For example, if the maximum axial force was 50,000 lbs., the required ejection force may be as high as 10,000 lbs. or higher. If the log is ejected when the high residual stresses are present, considerable damage to the log occurs. Logs ejected in this manner have visible cracks and are weak. It has been found that the residual radial stress in the log can be significantly reduced in two ways. First, if the system is allowed to cool, the log can be ejected with much less force, less than 1000 lbs. This is because the coefficient of thermal expansion of the stainless steel compaction apparatus is less than that of the compacted coal log thus, the residual radial stress is reduced. However, allowing the system to cool is time consuming. With the second method, the compaction apparatus is rapidly heated, causing the compaction apparatus to expand at a higher rate than the coal log and again the log can be easily ejected. Logs for which data is presented in this paper were ejected using the second method. When ejected, the length and diameter of the logs are measured using a micrometer. The logs are weighed and then allowed to cool to ambient temperature prior to compressive strength testing. All data in this paper are from logs that were compacted at 90 °C and at an initial moisture content of 15%, with one exception which will be discussed later. Furthermore, all logs were compacted at a maximum axial stress of 20,000 psi.

RESULTS AND DISCUSSION

Table 1 contains data collected on coal logs. The study thus far has focused on the effects of loading time, unloading time and peak load application time. Each data set in this table is the average of three replicate logs. An examination of Table 1 indicates that log compressive strengths range from 62 psi to 517 psi, nearly an order of magnitude. Figure 2 contains a typical axial stress versus displacement plot for a relatively weak coal log. In contrast, Figure 3 contains a typical axial stress versus displacement plot for a relatively strong coal log. The significant parameters affecting log strength are discussed in the following paragraphs.

Figure 4 shows the relationship between compressive strength and unloading time when both the loading time and peak load application time are constant. It is apparent that the unloading rate has a significant impact on the strength of coal logs. Logs which were unloaded at a slow rate had higher strengths. Further, there appears to be a threshold, about 200 seconds, beyond which there is no additional strength gain. Similar observations can be made for the effect of loading rate on log strength. Figure 5 shows the observed relationship between compressive strength and loading time. As with unloading time, longer loading times result in a higher strength log. Again, there is a threshold, about 200 seconds, beyond which there is no additional strength gained from increasing the loading time. It appears that the two relationships are independent. In other words, one can not compensate for a quick unloading time by increasing the loading time.

Log Code	Loading Time (sec.)	Unloading Time (sec.)	Peak Load Time (sec.)	Recovery (inches)	Specific Gravity	Compressive Strength (psi)	Final Moisture Content (%)
A-even	120	27	0	0.294	1.16	186	
A-odd	127	233	0	0.207	1.22	423	
B-even	137	20	0	0.302	1.15	162	
B-odd	217	23	0	0.295	1.16	229	
C-even	143	403	0	0.197	1.19	431	
C-odd	167	423	217	0.167	1.2	517	
D-even	133	27	0	0.284	1.15	104	
D-odd	133	567	0	0.159	1.22	399	
E-even	123	33	0	0.304	1.14	134	
E-odd	550	33	0	0.258	1.17	227	
F-even	130	27	0	0.31	1.15	151	
F-odd	153	27	353	0.192	1.2	316	
G-no vac	150	25	0	0.277	1.17	181	8.8
G-vac	127	27	0	0.244	1.11	64	6.2
H-no vac	140	40	0	0.228	1.16	148	9.8
H-vac	137	37	0	0.194	1.11	62	9.4

Table 1 - Compilation of coal log test data.

Figure 2 - Typical axial stress versus axial displacement graph for a relatively weak coal log.

Figure 3 - Typical axial stress versus axial displacement graph for a relatively strong coal log.

Figure 4 - Log strength as a function of unloading time, with loading time and peak load application time constant.

Figure 5 - Log strength as a function of loading time, with unloading time and peak load application time constant.

The authors believe that there are at least three plausible explanations for this behavior: 1) a rheological model of the stress-strain behavior of the log is applicable, 2) air pressure develops in the log during compaction and its magnitude is rate and time dependent and 3) the strength of cohesive bonds which develop between coal particle is time dependent. For a simple rheological model consisting of a spring element and a dashpot element, under constant stress, strain will be time dependent (Bowles, 1984). If stress is not constant, strain will also be stress rate dependent. This is consistent with observed results. If one examines the data in Table 1 for log code F-even in contrast with that for F-odd, it can be observed that increasing the peak load application time from 0 to 353 seconds results in a increase in strength from 151 psi to 316 psi and an increase in log specific gravity from 1.15 to 1.2.

Figures 6 and 7 clearly illustrate the strain dependency of log strength. Figure 6 shows that compressive strength is directly related to log specific gravity. The higher specific gravity of high strength logs is not the result of greater axial displacement. The total axial displacement is highly dependent on the initial bulk specific gravity of the coal in its loose state and the elastic properties of the coal particles. It is independent of compaction loading parameters such as loading time. Recovery is defined as the difference between the axial displacement at peak load and the axial displacement immediately after unloading. The logs lengthen during unloading and continue to lengthen for a short time after the load has been removed. Figure 7 shows that compressive strength is inversely related to the amount of recovery. The amount of recovery is a function of the visco-elastic properties of the log and therefore dependent on loading time, unloading time and peak load application time.

In an effort to eliminate possible detrimental effects of entrapped air in the logs, some logs were compacted under vacuum. The data in Table 1 with the log code G-vac was obtained from logs made under a vacuum of approximately 25 mm of mercury. The logs compacted under vacuum had a much lower compressive strength, 64 versus 181 psi, and specific gravity, 1.11 versus 1.17, than the control group logs with the log code G-no vac. It was also observed that the final moisture content of the vacuum logs was lower, 6.2 versus 8.8 percent. The application of vacuum caused a loss of moisture in the logs. For the data in Table 1 with a log code of H-vac, the initial moisture content of the logs was increased to 18% to compensate for this moisture loss. Strength and specific gravity results remained unchanged. A comparison of the data for log codes H-no vac and H-vac show that log strength decreased from 148 psi to 62 psi and the specific gravity decreased from 1.16 to 1.11 due to the application of vacuum. However, the recovery of 0.194 inches for the vacuum logs was less than the recovery of 0.228 inches recorded for the control logs. The vapor pressure of water at the 90 °C compaction temperature is approximately 10 psi absolute. The authors believe that, inadvertently, a steam extraction system was created for the logs under vacuum and as a result, acidic functional groups, which have been recognized as contributing to bond strength of coal compacts (Ellison and Stanmore, 1981), were removed from the coal. In addition, the removal of this material fundamentally changed the mechanical characteristics of the coal particle. The resulting coal particles were stiffer, more elastic and less viscous in their response to the applied load. The results were logs with higher specific gravities, lower values of recovery, and lower compressive strengths. The authors are currently undertaking tests to validate this hypothesis. Further, the authors believe that the potential benefits of compaction under vacuum may be realized if the

Figure 6 - Illustration of the direct relationship between log strength and specific gravity.

Figure 7 - Illustration of the inverse relationship between log strength and recovery.

compaction occurs at a lower temperature and the applied vacuum is controlled so that the pressure in the system remains above the vapor pressure of water at that temperature.

SUMMARY OF CONCLUSIONS

At this stage of the research study the following conclusions can be drawn:

- 1) coal logs have been made with compressive strengths exceeding 500 psi;
- 2) the strength of coal logs is highly dependent on the loading time, peak load application time, and especially the unloading time;
- 3) coal log compressive strength is directly related to the specific gravity of the coal log;
- 4) it has been observed that if a vacuum is applied to aid in the compaction process and the air pressure within the coal log is reduced to a value below the vapor pressure of water at the compaction temperature, water is removed from the system and the strength of the coal log is greatly reduced; and
- 5) it has been hypothesized that if a vacuum is applied and the air pressure within the coal log remains above the vapor pressure of the water at the compaction temperature, the strength of the log will be improved.

ACKNOWLEDGEMENT

This research is sponsored by the Capsule Pipeline Research Center which is supported by the National Science Foundation (State/IUCR Program), Missouri Department of Economic Development, the University of Missouri, and the Coal Log Pipeline Consortium which consists of nine private companies.

REFERENCES

Bowles, J., Physical and Geotechnical Properties of Soils, 2nd Edition, McGraw-Hill, 351-355, 1984.

Ellison, G. and Stanmore, B.R., "High Strength Binderless Brown Coal Briquettes Part II. An Investigation Into Bonding", *Fuel Processing Technology*, 4, 291-304, 1981.

March 3, 1992

WATER ABSORBANCE AND PERMEABILITY

Richard H. Luecke
Professor of Chemical Engineering

As stated in the last report, the general objective of this work is to determine the water susceptibility of coal that has been coated with asphalt for use as a casing for coal-logs. The coated coal in the casing would prevent water infiltration into the log and may add other desirable properties such as strength, impact absorbance and abrasion resistance. We are primarily interested at this time in studying the water absorbance and water permeability.

The methods described here can also be used to evaluate other log construction designs to repel water infiltration, such as a solid coating of asphalt.

WATER ABSORBANCE:

Discussion:

The rate of drying provides information that will be useful in a variety of ways. Coal that has been compressed into solid disks or logs has three modes for the storage of moisture:

1. On the exterior surface;
2. In the interstices between particles;
3. In the interior of the individual coal particles.

The amounts of water in each these categories can be inferred from drying rate curves. This information can, in turn, be used to deduce other information such as how effectively individual particles are coated with binder.

We have developed a procedure to allow very rapid and simple characterization of the water susceptibility of coal. This procedure is based on analysis of the drying curve of coal samples that have been saturated with water. Ground coal is mixed with asphalt and compressed into small disks 1.25" diam x 1/8" thick. Each disk is soaked in water and hung by a string in a microbalance with a desiccant that maintains near-anhydrous air in the balance enclosure. The rate of drying is determined from a record of time vs. weight of the sample.

Drying of the coal disk proceeds in four distinct steps. Analysis of the drying rate curve allows us to identify the amount and location of absorbed water. By inference, this

information is indicative not only of the moisture distribution but also of other features such as completeness of particle coating, volume and connectivity of interparticle voids, etc.

Initially moisture is lost while the sample comes into thermodynamic balance between heat and mass transfer, i.e., the sample comes to the wet bulb temperature. A nearly constant drying rate period then ensues as long as a film of free moisture is present on the surface. This exterior water (Category 1. above) does not offer much useful information about the coal log structure. We dry the exterior of the samples as thoroughly as possible and do not use initial drying rate data in the analysis.

In the next stage, the drying rate decreases as moisture in the interstices between coal particles must be transported to the exterior surface for evaporation. Finally, a large decrease in drying rate signifies exhaustion of moisture on the coated surfaces of the packed particles. After this, the transport of moisture from internal pores in the coal particles occurs at a much lower rate than the surface processes.

Classic analysis of drying data (Geankopolis, "Transport Processes and Unit Operations", Wiley, 1983) divide the drying curve into periods of constant rate and decreasing rate. The decreasing rate is empirically assumed to be decreasing at a constant rate or at a rate proportional to the amount of moisture present. We found that the classic analysis did not fit much of our data well.

A modified drying rate analysis was developed that assumes that there are two drying rates of interest - a relatively fast rate for the moisture between the interstices of particles, and the slower rate from the particle interior:

Both drying rates occur simultaneously. After the surface moisture is gone the total drying rate is:

$$\frac{dw}{dt} = \frac{dw_1}{dt} + \frac{dw_2}{dt}$$

Solution to these equations leads to a second order exponential equation;

$$w = w_0 - \Delta w \left[1 - \frac{e^{-\frac{t}{\tau_1}} + r e^{-\frac{t}{\tau_2}}}{1 + r} \right]$$

where w is the sample weight,

Δw is total weight of moisture loss,

τ_1 is the time constant for the fast drying rate,

τ_2 is the time constant for the slow drying rate,

r is the ratio of water storage (fast/slow).

The drying time vs. weight data was regressed to obtain the drying rate time constants and the moisture storage ratio. The data fits are extremely close indicating that the model gives a valid representation of the drying mechanism. A typical drying curve is shown in Figure 1; Figure 2 is the same data shown in logarithmic coordinates to emphasize the goodness of fit. Figure 3 is a plot of the calculated moisture loss in terms of percent moisture of the original sample.

We have not yet completed analysis as a measure of the effectiveness or completeness of asphalt coating of the particles. These results also should be of use beyond the question of water absorption.

PERMEABILITY:

We have also built a simple apparatus for measurement of water permeability. The device consists of a tube (1.5" diam) with a lip to support a coal disk. The coal disk will be sealed to the ledge with gaskets and/or caulk. Water is added on the top of the disk and a container containing desiccant is sealed around the bottom. Periodic weighings of the desiccant (and container) will be used to compute the rate of water transport through the disk.

We are currently starting experiments with this device using solid blank discs to ensure that the sealing procedures are effective in preventing leakage of moisture from the outside.

SCHEDULE:

Analysis of drying rate vs. disk manufacturing procedures is just beginning. Some additional experiments may be required.

Current plans are to use the disks from the drying experiments for the permeability measurements. We do not yet know how much time is required for the permeability tests. It is anticipated that several permeability measurement devices will be used simultaneously if the current design is effective.

Figure 1. Correlation of drying data. 20% Binder. $\tau_1 = 221$, $\tau_2 = 2112$, water storage ratio = 0.522.

Figure 2. Correlation of drying data on logarithmic scale to demonstrate data fit.

Figure 3. Calculated water removal rate by two processes.

Coal Drying Data

D10

Coal Drying Data

Coal Drying Data D10

COAL LOG FABRICATION-- DESIGN FIXTURE FOR UNDERWATER EXTRUSION

Yuyi Lin
Assistant Professor
Liqing Wang
Research Assistant
Department of Mech. & Aero. Engineering
University of Missouri-Columbia

Introduction

We started working on the underwater fabrication of coal log since January 1992. It was proposed [Liu, 1991] that the center explore the possibility of making coal log directly into transportation pipe line filled with pressurized water. The coal log can be either extruded or compacted, with or without binder. After discussion with other members working on coal log fabrication, we decide to design a fixture that can be attached to one end of the die on the extruder. This fixture should be easy to manufacture. The following important concepts and experiments can be performed on this fixture:

1. With the water providing back pressure, can we extrude stronger log?
Currently it is impossible to maintain steady pressure higher than 220 psi at the exit of the die. Although the maximum available pressure from the extruder is estimated to be 6000 psi, working pressure goes up very rapidly beyond 220 psi. As a result, either the bolts holding the die would break, or the auger for the extruder would stop.
2. Would the water get into extruder? This should not happen if we can maintain a steady exit pressure of the log at >2000 psi which is the maximum water pressure we are going to use for the pipe line. If the water does get into the

extruder, how should we modify the extruder so that continuous extrusion can sustain.

3. With the die exposed and exchangeable, we can study how different restrictions on the dies can work best with different water pressure.

4. Coal log fabrication pressure inside the die could be measured by attaching strain gage to outer surface of die. Precise measurement of the pressure change could provide data for modification and design of the extruder, if such modification is necessary [Turk, 1990].

The Fixture Design

The assembly drawing of the under water extrusion fixture is shown in Fig.1. It has a transparent wall so that coal log extrusion process can be observed continuously. It has a plug on the die of the extruder, so that at the beginning the water can not get into the extruder before any coal log coming out of the extruder yet. The plug has a loose running fit so that the coal log does not have to overcome back pressure in addition to the water pressure. The plexiglass pipe is design to withstand 2000 psi water pressure. However, during the test, it is recommended the fixture be used first at 500 psi, then increase the pressure to 1000, 1500, and finally 2000 psi. Most metal parts are made from stainless steel, this is because the sulfuric content of some coal, and electrolytic effect can make aluminum and regular steel rustic quickly.

Plans for Next Three Months

Although it remains to be tested, we feel that the quality of extruded coal log at present stage may not be good enough to sustain soaking in high pressure water for days, being transported for long distance without breakage. One of the problem of extrusion using current extruder is that steady high pressure (>500 psi) can not be maintained right outside of extruder, at the location before or near the restriction of the die. We would like to study the pressure variation near the restriction inside the die, and find a way of controlling the extrusion pressure steadily at 2000--5000 psi.

Since the ultimate goal is commercial production of high quality coal log made into the pipe line directly, we would like to look into the feasibility of designing a semi-automatic coal log fabrication machine that would accept compacted or extruded coal logs, probably coat them with asphalt, and then put them into pressurized water filled pipe line. Also, other possibilities of making good quality coal log would be explored, such as using plunger type extruder to compact the coal log from both ends. In addition to the experimental data we are going to get from under water extrusion tests, data obtained by other members of the coal log fabrication group would be crucial for designing the automatic fabrication machine.

References

- Liu, H. and T. R. Marrero, 1990, "Proposal for Establishing an Industry/University Consortium (Center) to Develop the Coal Log Pipeline (CLP) for Transporting Coal."
- Turker, E. G. and S. Spector, 1987, "Coal and Refuse Agglomeration by Extrusion."

COAL SLURRY CAPSULE PIPELINE SYSTEM

James Seaba, Dept. of Mechanical and Aero. Engineering
and Gang Xu, Dept. of Mechanical and Aero. Engineering
University of Missouri-Columbia

INTRODUCTION

To facilitate more efficient transport of a coal-log in a pipeline, the effects of coal slurry instead of water will be investigated. The slurry consists of 50% coal and 50% water by weight. The improvements expected with the addition of slurry in the transportation process are first, lowering the lift-off velocity of the capsule, secondly, to reduce the water required to transport the coal-log, and third, possible reduction in log abrasion due to better suspension of logs in the pipe and due to reduced operation velocity. This project was recently initiated so only expected results, experimental considerations, and future work are presented.

EXPECTED RESULTS

The addition of slurry will raise the density of the transporting medium, thereby lowering the density ratio (S ; ratio of the density of the coal-log to that of the slurry) toward unity for the capsule. A reduction in the specific gravity toward unity results in a decrease in the lift-off velocity (V_l) of the coal-log. The correlation between the V_l and S is,

$$V_l \propto \sqrt{S-1},$$

as determined by Liu (1982). A decrease in the lift-off velocity corresponds to a decrease in the actual velocity of the logs in transit. Possible breakup or deterioration of the coal-log due to interactions with the inner wall of the pipe and other capsules will be reduced at lower velocities.

EXPERIMENTAL DESIGN CONSIDERATIONS

The slurry capsule system will be modeled with a 2 in. diameter pipeline. A closed loop will recirculate the slurry mixture and the capsule will be transported through part of the system, but taken out of the loop to avoid the slurry pump. Pressure measurements will be made along a horizontal straight section of pipe where the capsule has reached constant acceleration. The lift-off condition and coal-log behavior can be determined by using electromikes and a metallic capsule. Several design considerations are presently being investigated:

1. Friction or head loss due to the addition of the slurry,
2. proper instrumentation for a slurry environment,
3. loading and unloading system for capsule,
4. pump for slurries in closed loop configuration,
5. coal slurry composition,
6. data acquisition system,
7. instrumentation, and
8. fit into the hydraulics lab.

PRESENT AND FUTURE WORK

The current research effort is an in-depth literature search. The literature search will provide information about the design of a slurry capsule pipeline. Concurrently, from the literature search design criteria will be determined, i.e., pressure transducers, flow meters, and slurry pumps. Once the closed loop slurry system has been determined, construction of the test facility will begin. It is anticipated that the next three months will be spent in the design, construction, and testing of the slurry capsule pipeline.

REFERENCES

Liu, H. (1982). A theory on capsule lift-off in pipeline. J. Pipelines, Vol. 2, pp. 23-33.

COAL LOG PIPELINE ACTIVITIES REPORT

THE UNIVERSITY OF MISSOURI-ROLLA, MINING ENGINEERING

End Feb. 1992

John W. Wilson: Chairman, Professor, Mining Engineering
Yungchin Ding: Graduate Student, Mining Engineering

Introduction

Phases of the project being performed at the UMR campus include:

1. End of the pipeline studies on the use of coal logs at utility plants.
 - a. Bench scale tests on various coals.
 - b. Preparation of coal for Columbia tests.
 - c. Coal lab. analyses on binders for Columbia.
 - d. The study of utility facilities.
 - e. Study of water treatment at utility plants.
2. Marketing efforts to enhance the CLP project.
 - a. Obtain additional consortium members.
 - b. Assist in seeking technologies applicable to the rapid development of CLP technology.
 - c. Assist in finalization of EPRI project funding.
3. Preparation of technical papers.

Progress to Date on the Review of Coal Log Fuel Handling and Treatment at Power Plants

The Coal Log Pipeline uses a hydraulic method for transporting coal in the forms of logs through a water filled pipeline. It requires coal to be compressed into logs near the coal mining site and to transport these coal logs by pipeline, to the coal-burning utility plants. Other activities relate to the handling and utilization of coal logs at utility plants. The tests are designed to determine the effect that coal logs may have on the existing coal storage, handling and combustion methods at electric utility plants. Three types of furnaces; pulverized coal, cyclone, and fluidized bed furnaces, are commonly used for electrical

power generation and are referred to in this research as the "end use facility for coal log combustion". Sub-bituminous coal and Illinois coal, have been selected for coal log tests. Tests on the proximate analysis of selected coal samples, and asphalt/coal mixtures have been completed. According to the proximate analysis data, the use of asphalt as a binder for making coal logs has been found to have no significant influence on the properties of coal related to its combustion.

Proximate Analysis of Coal Samples

Two types of coal samples currently being tested include a Powder River Basin coal from Gillette, Wyoming and mid-western coal from Illinois. The rank, proximate analysis, sulfur content, and heating value of these two coals, as well as tests on a Texas lignite coal, are shown in Table I.

Table I shows that Wyoming coal has the highest moisture content, (up to 17.16%), while the Texas lignite and Illinois coal have moisture contents of 12.03% and 6.19% respectively. The lignite has an ash content of 14.71% (dry-basis) which is much higher than Wyoming coal (6.48%) and Illinois coal (12.40%). Sulfur analysis results show that the Illinois coal has the highest sulfur content (3.8%) when compared with the low sulfur Wyoming coal (0.294%). The heating value of the coal increases as the rank of coal increases, thus, the Illinois coal (high rank) has a heating value of 11,864 BTU/lb and the Texas lignite has only 9,223 BTU/lb (low rank), when compared on a dry basis.

Effect of Asphalt on Coal Properties

Asphalt has been used as a binder for making coal logs for pipeline transportation purposes. In these early tests, 2.5%, 5%, and 7.5% by weight of asphalt was mixed with crushed coal particles (-3/8") to test the "binding" capacity for making coal logs. The addition of asphalt was found to affect the properties of the coal as it related to its combustion, i.e., volatile matter, fixed carbon, sulfur content and heating value. Consequently, proximate analyses, sulfur analyses, and the heating value determinations of the asphalt/coal mix-

tures were also carried out to evaluate the influence of the asphalt on coal properties. These test results are shown in Table II.

The moisture content of the coal samples listed in Table II are very similar but show a decreasing amount for each increment of 2.5% added asphalt. This reduction in moisture could be attributed to the hydrophobic asphalt coating on the coal surface that tends to prevent the accumulation of water between coal particles. By evaluating the volatile matter data, the volatile matter increases about two to four percent for every 2.5% asphalt increment. According to the asphalt proximate analysis results, the asphalt has a volatile matter of 84.04%. Thus, the increase of volatile matter in coal samples is believed to be due to the high percentage of volatile matter content in the asphalt.

According to the test results mentioned above, there was no significant influence on the coal properties caused by the addition of asphalt as a binding medium. Future work will be carried out to investigate asphalt coal logs on the grinding and pulverizing operations. Three selected coal samples will be pulverized to a suitable size that meet the coal-burning furnace requirements. The particle size analysis will be carried out on these pulverized coal fines. For evaluating the effect of asphalt on coal pulverizing at the end-of-the-pipeline prior to combustion, particle size analysis will also be conducted on pulverized coal fines that have been previously mixed with different percentages of asphalt and pulverized by a laboratory scale hammer mill. By comparing the particle size analysis data between the original coal and asphalt/coal mixtures after the pulverizing process, the effect of asphalt on coal pulverizing and the degree of influence can then be determined.

Water Quality Study

A literature survey has been carried on the water treatment requirements required by the Federal Government and the respective States in the mid west, as they relate to power plants.

The federal and state (Missouri) water control regulations as they apply to both Steam Electric Power Generating and Coal Preparation Plant effluents,

specifies limitations that must be considered when testing coal log pipeline discharge water. These requirements are summarized as follows:

1. **BOD₅ (Biochemical Oxygen Demand):**
This is the quantity of oxygen used in the aerobic stabilization of waste water and polluted water. The BOD₅ in a period of 30 consecutive days is limited to 30mg/l.
2. **TSS (Total Suspended Solid):**
Refers to the nonfilterable residue after filtration operation. The maximum limit for TSS is 10.0mg/l
3. **pH:**
The pH of effluent water should be within 6.0 and 9.0 at all times.
4. **Dissolved Oxygen (DO):**
EPA criteria require a minimum of 5.0mg/l for fresh water aquatic life.
5. **Oil and Grease:**
The maximum oil and grease is 20.0mg/l.
6. **Metal Concentration:**
The maximum limit for metal concentrations are iron (1.0mg/l), manganese (4.0mg/l), copper (1.0mg/l), chromium (0.2mg/l), and zinc (1.0mg/l).
7. **Free Available Chlorine:**
The maximum limit for free available chlorine is 0.5mg/l.

Work in above areas will be accelerated with the assistance of a soon-to-graduate student to work on the CLP project as a graduate student in this department.

To obtain data on the effects of water pick-up in coal logs, we are awaiting the manufacture and water tests on coal logs from the Columbia Campus.

Marketing Efforts

A significant amount of the Principal Investigator's time has been taken up with writing to and visiting many large coal producers, utility companies and multi-disciplined energy companies. Dr. Marrero and Dr. Liu have records of all companies contacted in regard to possibly joining the Industrial consortium.

This work will be intensified over the next three months as we continue to seek at least two new consortium members that would qualify us to maximize the matching funds of NSF and the State of Missouri.

Technology transfer plans are in progress for showing the CLP concepts at the American Mining Congress MINEXPO to be held in Las Vegas-October 1992. This is one of the largest mining equipment/technology conferences in the world, that is held at four yearly intervals.

Technical papers have been prepared and submitted for presentation and publication to:

1. 4th International Conference on Bulk Material, July 1992, Australia.
2. 17th International Conference on Coal Utilization and Slurry Technologies, April 1992, Florida.

Short feature articles have been prepared with Dr. Marrero for publication in U.S. technical mining journals.

Several local press releases have been published at UMR and in Rolla on the aims of the CLP and UMR's contribution.

Future Work

Work over the next three months will include :

1. Complete tests on coals used to make coal logs by the Columbia team.

2. Continue to visit utility plants to ensure a complete understanding of present procedures in receiving, handling and burning of received coals.
3. Water treatment studies:
 - a. At existing utility plants.
 - b. Water pick-up in test logs.
 - c. Literature/data collection on standards imposed and possibly pending.
4. Provide ad hoc services to representatives of CLP team in Columbia

March 2, 1992

Table I
PROXIMATE ANALYSIS OF SOME COAL SAMPLES TESTED

Sources	Rank	Moisture %	Ash %	V.M. %	F.C. %	Sulfur %	Heat. V. BTU/lb
Wyoming	Sub-B	17.16	5.37	35.61	41.86	-	-
Dry-Basis		-	6.48	42.99	50.54	0.294	11,017
Illinois	Bitu.	6.19	11.64	34.10	48.07	-	-
Dry-Basis		-	12.40	36.35	51.24	3.80	11,864
Texas	Lignite	12.03	12.94	37.24	37.79	-	-
Dry-Basis		-	14.71	42.33	42.95	1.50	9,223

All analyses given on a Dry-Basis , that is, moisture free basis.

Sub-B : Sub-Bituminous Coal F.C. : Fixed Carbon
V.M. : Volatile Matter Heat V. : Heating Value

Table II
PROXIMATE ANALYSIS OF ASPHALT/COAL MIXTURES

% Asphalt	Moisture %	Ash %	V.M. %	F.C. %	Sulfur %	Heat V. BTU/lb
0%	2.22	7.89	32.48	57.42	-	-
Dry-Basis	-	8.06	33.20	58.74	0.345	11,564
2.5%	2.19	6.96	36.31	54.56	-	-
Dry-Basis	-	7.11	37.12	55.78	0.410	11,737
5.0%	1.97	6.44	39.88	51.72	-	-
Dry-Basis	-	6.57	40.68	52.76	0.499	11,914
7.5%	1.93	6.32	41.70	50.06	-	-
Dry-Basis	-	6.45	42.52	51.04	0.591	12,053
Asphalt	0	0.13	84.04	15.83	3.78	-

CONTROL OF THE SMALL-SCALE COAL LOG PIPELINE SYSTEM

S. S. Nair, Assistant Professor
S. Outangoun and C. Y. Shieh, Graduate Students
Department of Mechanical and Aerospace Engineering
J. Wu, Graduate Student
R. Oberto, Research Electronics Technician
Department of Civil Engineering
University of Missouri-Columbia

This report summarizes the control and modeling work pertaining to the demonstration coal log pipeline (CLP) unit for the period from 1 Dec '91 to 29 Feb '92. The basic design and construction details of this CLP demo system were described in [1,2] and the previous quarterly reports [3].

CONTROL IMPLEMENTATION RESULTS

The major mechanical subsystems were all successfully tested. Control implementation is performed using a 486 computer. The primary interface card is the Metrabyte PIO-96 which is a high density parallel digital I/O card with TTL/DTL compatible lines. At present, the control computer performs all the functions of data input and interpretation, decision making, and control output activation. Optical sensors are installed at the locations shown in Figures 1 and 2 for counting the passing capsules. The pressure of the water in the system is regulated by a valve at the outlet of the main pump located in the injection section.

A typical computer control cycle is as follows: the log trains are transferred to the four inlet launching tubes from the conveyor belts by using the auxiliary pump and the appropriate valves. This is done sequentially by monitoring the sensors at the inlet of the launching tubes. The computer then turns the main pump on and pumps the capsules ^{trains} out one by one, again by monitoring the sensors at the outlet of the launching tubes. Once all

the four trains are pumped out, the computer switches its attention to the by-pass section and monitors the sensor at the outlet of the divertor valve. After each count of ten the computer switches the divertor to the opposite position to fill up the opposite by-pass line. In the numbering sequence used, either the odd-numbered valves are all open at the same time or the even-numbered ones. This implies that when one line is being filled, the other one is being pumped out. This procedure is currently performed without turning off the by-pass pump. To prevent the possibility of this pump operating on a blocked head, all the four main by-pass valves, either odd or even numbered, are opened prior to switching to the opposite line. The train separator has not been activated since sufficient separation between the trains is achieved in the current implementation. The program automatically shuts down the system by switching the pumps off and then the valves, after the sensor count at the outlet conveyor reaches the total capsules injected.

This implementation has been successfully tested with a fast cycle time of approximately 90 seconds. The V-shaped joints at the inlet and by-pass sections have periodically caused jamming of the capsules. This has prompted redesign of the joints which is currently underway. Barring this problem, the system operated consistently in a reliable manner.

DYNAMIC MODELING STUDIES

The analytical model for unsteady flow in the CLP system without the capsules has been found to compare well with the predictions of the model proposed using the method of characteristics in [4]. The development of a model with the capsules is currently underway using Advanced Continuous Simulation Language (ACSL).

DISPLAY SOFTWARE

The display is currently intended to indicate the status of the system including valve positions, a count of the capsules, and pressure/velocity values at specific locations. It will incorporate the capability for multiple windows to display subsections of the larger system in greater detail. The program is being designed using the Borland C++ software

development package. Using the package, pull-down menus and dialog-boxes are being built according to system needs. At present, animation of the movements of capsules has been successfully done.

CURRENT EFFORTS

Analytical modeling studies are under way using a lumped parameter approach for the system with a single capsule. Later multiple capsules and other phenomena including the effect of closing of valves will be included to study the various dynamic interaction features. Decentralized control is also being investigated using several independent processors which should free the control computer for other tasks. Operations that can be performed in this fashion include counting the capsules at various locations, sequential switching of the pumps and valves, etc. Diagnostic, safety and data logging software modules are also being developed independent of the control software. These will finally be integrated with display and other functions using possibly a Local Area Network (LAN). For the mechanical system, the V-joints connecting the tube sections are being redesigned to prevent jamming of the capsules. This modification should also eliminate the leakage problem at the joints which seemingly causes air entrainment when the pressure in a line drops occasionally due to the combined operation of pumps and valves. Concurrent with these efforts, hardware and operational manuals documenting the system and software details are also being assembled.

REFERENCES

1. Baik, M.A., *Design and Construction of a 1.25-inch Coal Log Pipeline System*, First Quarterly Progress Report to DOE, November, 1990.
2. Liu, H., and Wu, J. P., *Coal Log Pipeline Intake and Booster Stations: Design and Operation Considerations*, 16th International Conference on Coal and Slurry Technologies, Clearwater, Florida, 1991.
3. Nair, S. S. et.al., NSF Quarterly Progress Reports , Aug '91 and Dec '91.
4. Paksanonda, P., Prediction of Headloss in Hydraulic Capsule Pipeline, MS Thesis, Department of Civil Engineering, University of Missouri-Columbia, 1991.

Top View

Side View

Fig. 1: Coal Log Injection & Ejection Systems of the Small Demo CLP

(S - optical sensor location)

Fig. 2: Pump Bypass & Coal Log Train Separator Systems of the Small Demo CLP

(S → sensor location)

LEGAL ASPECTS OF FUTURE COAL LOG PIPELINE SYSTEMS IN THE UNITED STATES

Peter N. Davis
Isidor Loeb Professor of Law
University of Missouri-Columbia
February 28, 1992

Quarterly Report: December 1991 - February 1992

Introduction:

Legal issues influencing future construction of coal log pipelines fall into four categories: (1) right-of-way acquisition, (2) water rights acquisition, (3) water pollution regulation, and (4) environmental assessment. A detailed discussion of those topics comprises my report of September 25, 1991. The first two topics primarily are matters of individual state laws. The latter two topics are predominantly involve federal law, although there is considerable supplemental state water pollution law. Those topics will be investigated over a four year period.

In this first year of our legal research, we are looking at the present statutory and case law in the areas of right-of-way and water rights acquisition. We are building on the published and unpublished research done in the late 1970s and 1980s in connection with coal slurry pipelines. On partial examination of that law shows that significant changes have occurred during the past 10 years in many states which improve the legal climate for coal log pipelines; nonetheless, significant legal obstacles remain in many other states.

Research:

During the fall semester 1991 and particularly in the December 1991 - February 1992 period, the statutes of 25 states was examined to determine (1) whether coal pipelines have been conferred the power to acquire rights-of-way by eminent domain, (2) whether water can be used for coal pipelines, (3) whether there are any restrictions on extra-watershed or interstate water diversions, and (4) whether coal pipelines can acquire water right by eminent domain. Also, the legal secondary literature was searched to determine the existence of information on two related legal questions: (1) whether a coal pipeline is considered to be a quasi-public use sufficient to support a conferral of eminent domain power, and (2) the law of overlapping right-of-way easements -- *e.g.*, can one railroad prevent a second railroad from crossing its line? This work was done jointly by me and my research assistant, Elizabeth Phillips.

Conference Paper:

In the same period, I prepared a 5000-word paper, *Legal Aspects of Future Coal Pipelines in the United States*, which I submitted to the 4th International Conference on Bulk Materials, Storage, Handling and Transportation, to be held in Wollongong NSW, Australia, on July 6-8, 1992. If accepted by the conference organizers, the paper will be published as part of the conference proceedings and I expect to go to Australia to present it.

The paper covers the legal topics discussed above, places the water law related topics in the context of American water use law (riparian rights, prior appropriation, groundwater doctrines), and states our preliminary findings.

Future Research:

During winter semester 1992 and particularly during the March - May 1992 quarter, we are investigating the same legal questions, discussed above, in the remaining 25 states. Also, we are looking at the 19th century railroad crossing cases and, if we can find any, more recent utility crossing cases to determine the current law of overlapping right-of-way easements. There appears to be no recent legal literature and very few recent cases on this topic. (This is curious because the railroads lost over 60 unreported cases in Oklahoma alone in the late 1970s when they tried to prevent the ETSI coal slurry pipeline from crossing under their tracks.) We expect to have this work done in time for presentation with my paper in July 1992.

Sources for Research:

We are using two major sources for our legal research, (1) the collection of law reports, statutes, legal treatises and other secondary legal materials, and many federal government documents in the Law Library of the University of Missouri-Columbia, and (2) the *Westlaw* and *Lexis* computerized legal database services to which our law library subscribes. These give us access to the entirety of law reports and statutes in the United States from the colonial period to yesterday.

References:

- (1) Davis, P.N., *Legal Aspects of Future Coal Log Pipeline Systems in the United States*, Project Description for CPRC Advisory Board, Sept. 25, 1991.
- (2) Davis, P.N., *Legal Aspects of Future Coal Pipelines in the United States*, paper submitted to 4th International Conference on Bulk Materials, Storage, Handling and Transportation, Jan. 22, 1992.

Train Behavior Experiments in the Coal Log Pipeline (CLP)

by James L. Richards, Research Assistant

February 26th, 1992

The problem with the computer model in the low velocity regime, reported in the last report, has been solved, thanks to a paper written by Dr. Henry Liu and Pituk Paksanonda. This paper, entitled "Pressure Variation along Stationary Capsule in Pipe," has provided the basis for accurate prediction of capsule headloss at low velocity with stationary capsules.

During this quarter, the pipeline loop has been modified with a transparent plexiglass test section with an inside diameter of 2.125 inches. This allows the motion of logs to be seen, as well as providing a smooth transition so the angle and gap data can be taken. Another modification to our test loop has been the inclusion of a transparent plexiglass bend so that the effects of capsules in a bend can be seen. The instrumentation of the previous test section has been installed in the pipe and has been recalibrated.

From previous experimental tests, after prolonged usage the coal logs were considerably damaged by the jet pumps. To eliminate log damage and to relieve the pumps from abrasion due to the coal particles in suspension, plexiglass logs were made. These capsules mimic the behavior of the coal logs except for the deterioration. The plexiglass capsules, which have a specific gravity similar to the coal logs, were made of two diameters. Each diameter of log had two sets of lengths made. With the smaller diameter logs, a new "dummy" capsule had to be devised to allow for the collection of data. These capsules were designed and constructed using the average values of the length, diameter, and specific gravity of the plexiglass logs.

With the loop and capsule ready, testing has begun. Data collected from this testing is capsule velocity, headloss, angle and gap information. This, as well as abrasion testing will be the final stages of this authors thesis. For the remainder of the semester, this author will continue writing (and finish) his thesis and finish the aforementioned experiments.

An interesting initial result in the low velocity testing was the observation of saltation of the logs in the pipe at very low velocity. This demonstrates that the logs were moving earlier (at a lower velocity) than previously thought (before the incipient velocity). One complication of this observation is the effect of the roughness between the capsules and the pipe wall.

March 1, 1992

Water Hammer in Hydraulic Capsule Pipeline

by: Majed M. El-Bayya (research assistant)

Achieved tasks:

Since the last report, the following tasks have been achieved:

1) Eliminating the numerical Instability:

Due to the use of large time step in the simulation of water hammer in Hydraulic Capsule Pipeline (HCP), a numerical instability was encountered in the solution. Two techniques have been used to eliminate this problem: a) by using smaller time step and b) by using implicit technique to estimate the capsule acceleration.

The first technique consumes more computer time and it is not practical. However, it has been used for comparison with the second technique. The result showed agreement between the techniques. The second technique use less computer time for the same accuracy and thus used in the solution.

2) Small spacing between capsules:

The analysis of the case where the spacing between the capsules in a train of capsules is smaller than some specific value of the capsule length has been done. An implicit technique was used in the solution for this case.

For a simple HCP system and at this stage, our computer program is capable of handling the following:

- 1) Single capsule moving concentrically in a horizontal pipe.
- 2) A train of capsules moving concentrically in a horizontal pipe with:
 - a) small spacing between the capsules and
 - b) wide spacing between the capsules.

Results:

Based on the results that we have from the mathematical model, we can say

that, in general, the maximum pressure in the system with a small spacing between capsules is larger than that with a large spacing.

Future tasks:

During the following three months, the following tasks will be performed:

- 1) Studying the effect of changing the boundary conditions, such as the closure time of the valve, on water hammer in the system.
- 2) Studying the effect of changing the capsule specification within the train of capsules.
- 3) Collecting information and establishing a technique to handle the impact of capsules in the system under water hammer action.

PREDICTION AND CONTROL OF WATERHAMMER IN PUMP BYPASS

PROGRESS REPORT

Rattanathip Phimjaichon
Research Assistant
Department of Civil Engineering

INTRODUCTION

One way to transport coal capsules in Hydraulic Capsule Pipeline (HCP) is to use ordinary water pumps which are required at selected intervals in order to maintain sufficient energy in flow carrying coal logs. An ordinary water pump such as a centrifugal pump can be used to drive capsule flow if the capsules can be made to bypass the pump. This is referred as the pump bypass scheme. One that appears to be most practical is shown on Figure 1 (Hogson and Charles, 1963). This pump bypass is a pipe network consisting eight valves and a pump. The valves are located one on each side of the two diamond configurations of bypass system. Three long pipes connect the diamonds at their junctions. The remaining two diamond vertices tie into the mainlines at the upstream and two downstream ends. The basic concept of the pump bypass involves housing the pump in the long middle pipe and diverting the capsules into the long outer pipes with a controlled sequence of valve switching.

Figure 1. Two Steps of HCP Bypass System

From Fig. 1, the operation of pump bypass involves two steps. The two sub-figures (a) and (b) identify the open valves and the closed valves during two steps. Each valve is designated a number in Fig. 1. During Step 1, the four odd numbered valves are closed, while the even numbered valves are open. Capsules from the upstream *Pipeline 1* pass through *Valve 4* and accumulate in *Pipeline 4*. Meanwhile, water and capsules leaving *Pipeline 2* to the downstream *Pipeline 5*, are being replaced by the water pumped

through *Valve 2*. This continues until *Pipeline 4* is filled to capacity with capsules and then Step 2 begins. During Step 2, the four even numbered valves are closed while the odd numbered valves are open. The capsules in *Pipeline 4* are driven through *Valve 7* into *Pipeline 5* by the pump discharge through *Valve 3*. The pump draws water from *Pipeline 5* through *Valve 5*. Meanwhile, capsules from *Pipeline 1* enter *Pipeline 2* through *Valve 1*. The system repeats periodically in this manner. Since the system requires alternate opening and closure of eight valves, waterhammer takes place.

The effect of waterhammer must be investigated in order to determine the conditions of operation favorable to attaining high linefill rates and mild pressure surges. Furthermore, undesirable pressure can be reduced or eliminated by introducing surge control devices into the system, such as surge tanks. Although this study is strongly analytical by computer simulation, it is important for successful operation of a coal log pipeline system.

METHODOLOGY

The following assumptions are employed to develop the hydraulic equations for pump bypass model:

1. No capsules are present in the flow. However, any pressure surge problems in the HCP bypass system identified without the presence of capsules can be expected to also occur with the capsule presence except for a difference in magnitude.
2. The system is horizontal.
3. The wave celerity is constant and much higher than the velocity of water.
4. The valve sections are short.
5. Cavitation and column separation do not occur.

The present model is an improvement of the study of Woodson (1988) in the following regards:

1. The upstream and downstream pipelines of the network are so long that waves propagating away from the bypass system are not reflected back.
2. Valve closure is considered in the term of τ (tau) which is a specified function of time based on the selected valves instead of using the valve loss coefficient K .

$$\tau = \sqrt{\frac{K_{open}}{K}}$$

in which K_{open} = The valve loss coefficient when valve is fully open, $K_{open} = 4.0$ is used in this study

3. The process of head loss consideration around a loop (diamond) is determined separately on each pipe instead of setting head loss around a loop being zero.
4. The pump is redesigned to optimize the pressure surge in pump bypass system. The head discharge relationship is given by

$$h_p = 6000.0 + 86.838Q - 48.903Q^2$$

in which h_p is the pump head in feet and Q is the pump discharge in cubic feet per second. At steady flow of the system, the pump head yields up to 4,350 feet at a constant 8 cubic feet per second of the pump discharge.

The method of characteristics, continuity equations, head loss equations, and numerical method are used to find the variations of discharges and pressures with time in the bypass system, at different locations.

RESULTS

The main studies had been done as follow:

1. Complete program in C LANGUAGE was written for determine the effect of waterhammer in the forms of the variation of discharges and pressures in pump bypass system.

2. The significance of time step using in the computer simulation was observed. The previous study was not concerned about the effect of time step, even though it affected the accuracy of the results significantly. The smaller the time step was, the more accurate the results were. It was found that for the same input data when the time step was less than 0.0041666 seconds, the results appeared constantly. Due to the power limitation of computer model, the time step used in this study was set to 0.004166 seconds for saving time consuming of program.

3. With the improvement of valve stroking strategies, the undesirable pressure surge were reduced in some cases. For example, the extensions of closure time of valves and the changes of linear function to piece wise function of valves caused the reductions of pressure surges to some extent.

The current study is aimed at the possibility of introducing a surge tank into a pump bypass system. The results of this study is expected to be accomplished by May.

FUTURE PLANS

To continue and complete the study, the following additional tasks are recommended:

1. Refinement of the present program.
2. The new strategies can be applied to modify the bypass model for combating the waterhammer problem. The improvement of surge control device strategies, valve stroking strategies ,and pump throttling strategies may reduce waterhammer in the system.
3. The effects of capsules on waterhammer problem must be thoroughly studied and included in the development of the bypass model.

REFERENCES

Hogson, G. W. and M. E. Charles, 1963, " Method and Apparatus for Transporting Package Material in a Pipeline", Canadian Patent No. 673,280, Canadian Patent Office, Ottawa, Ontario, Canada.

Woodson, R. J., 1988, Transient Control of Hydraulic Capsule Pipeline Bypass, M.S. Thesis, Department of Civil Engineering, University Of Missouri-Columbia, Columbia, Missouri.

Revising Economic Report

by Henry Liu and Robert Zuniga

Work has been initiated during the past three months to revise the 1990 report on coal log pipeline economics¹. Most of the time spent in this period is in collecting new data and revising old cost figures. Three major cost items have been revised: pipeline construction cost, pump cost and water cost. They are described in the attached three appendices to be used with the revised report.

Economic analysis will intensify in the next three months, and revision of the 1990 report will be completed by June 30, 1992, the expiration date of the DOE project.

-
1. Liu, H. and Wu, J.P., Economic Analysis of Coal Log Pipeline Transportation of Coal, UMC Civil Engineering Report, April 1990, 77 pages.

Appendix 1: Pipeline Costs

1. Cost Formula Used in Previous Report

Pipeline construction costs estimates given in the 1990 report on page 28, used pipeline cost information from the Office of Technology Assessment's 1978 report A Technology Assessment of Coal Slurry Pipeline. Basically, these costs were adjusted to reflect inflation between 1978 and 1990. The equation developed for pipeline costs (1990 values) as a function of pipe diameter is

$$C_{pc} = 118 D^{1.34} + 93 D^{0.87} + 22 D + 18 \quad (A1-1)^*$$

where C_{pc} is pipeline costs (\$1000/mile); and D is pipeline nominal diameter (ft). The cost includes steel pipe, construction (excavation, welding and insulation), coating, wrapping, valves and the right of way.

2. Oil and Gas Journal (OGJ) Average Pipeline Construction Cost (1990)

The 1990 Pipeline Economics Report of Oil and Gas Journal, December 1991, Vol. 89, No. 48, contains information on the projected costs for proposed pipeline projects based on annual reports filed with the U.S. Federal Energy Regulatory Commission (FERC).

Average construction costs for gas pipeline construction in the U.S. as a function of nominal pipe diameter for the range of 6" to 42" are given in Fig. 4 on page 48 of the Journal. These costs are determined from proposed pipeline construction projects and are listed in Table 2, pp. 46-47 (OGJ).

Current cost components include material, labor, miscellaneous, and right of way. Miscellaneous costs include surveying, engineering, supervision, contingencies, allowances for funds used during construction (Afudc), administration and overheads, and FERC filing fees (p.54 OGJ). Right of

*Same as Equation 96 of the previous report (Liu and Wu, 1990).

way includes the cost of obtaining the right-of-way and cost of any allowances for damages (p.54 OGJ).

The OGJ 1990 average construction costs (1990 dollars) is reproduced in Figure A1-1 and listed as the "Actual" curve. In this report two estimates are done using the data provided by this "Actual" curve. The first estimate, designated as "Small" in the figure, uses a subset (8 to 20 inches nominal diameter). The second estimate, designated as "Large", uses the full range (6 to 42 inches nominal diameter pipe diameter). Both estimates were obtained from a linear regression of the points and both are plotted in Fig. A1-1.

The estimate** for the subset of nominal pipe diameter 8 to 20 inches, designated as "Small", in 1992 dollars is

$$C_{pc1} = 153 D + 154 \quad (A1-2)$$

where C_{pc1} is pipeline costs (\$1000/mile); and D is pipeline nominal diameter (feet)

The estimate for the full range of nominal pipe diameter 6 to 42 inches, designated as "Large", in 1992 dollars, is

$$C_{pc2} = 298 D - 32.9 \quad (A1-3)$$

where C_{pc2} is pipeline costs (\$1000/mile); and D is pipeline nominal diameter (feet). For comparison purposes, Eq. A1-1 is also plotted in Figure A1-1 and is listed as "Liu and Wu".

**All equations are represented in 1992 dollars, based on United States Financial Data issued by the Federal Reserve Bank of St. Louis in January, 1992.

Fig. A1-1. OGJ 1990 Average Construction Costs (1990 dollars).

Fig. A1-2. OGJ Average Pipeline Construction Costs (1990 dollars) for years 1984 - 1990.

Fig. A1-3. OGJ Pipeline Construction Costs (1990 dollars): Comparison of Indexed Values Based on 1984-1990 Data.

3. OGJ Pipeline Construction Cost (1984-1991)

Since the average pipeline costs given in each yearly report includes pipeline construction in all regions of the United States and for a variety of pipeline lengths, another cost estimate criteria was used to constrain the yearly data to match the construction environment that the coal log pipeline would be built. The criteria included two general constraints, physical and geographical. The physical constraints are as follows: pipeline diameter range 8" - 20" and pipeline length greater than 50 miles. The geographic constraints include the following Midwestern states: Arizona, Colorado, Illinois (Northern, excluding Chicago), Iowa, Kansas, Montana, Nebraska, Nevada, New Mexico, North Dakota, South Dakota, Oklahoma, Texas, Utah, and Wyoming. Oil and Gas Journal (OGJ) Pipeline Economic Reports from 1984 to 1991 were then used to provide an estimate of pipeline construction costs (\$1000/mile) as a function of nominal pipe diameter (inches) for long pipelines in the Midwestern plain region. The result yields more meaningful cost figures for long pipelines in this region than using the full data set offered by the OGJ.

The cost data obtained by applying the above criteria were converted to 1990 dollars by the use of two different indices: the **Consumer Price Index (CPI)** and the **Chemical Engineering Plant Cost Index (CEPCI)**.

Consumer Price Index (CPI)

An inflation index obtained from Stocks, Bonds, Bills, and Inflation 1991 Yearbook by Ibbotson and Sinquefeld was used to represent all cost data in 1990 dollars. A linear regression analysis of the resulting data yielded the following estimation in 1992 dollars:

$$C_{pc3} = 220.9 D - 26.6 \quad (A1-4)$$

where C_{pc3} is pipeline costs (\$1000/mile); and D is pipeline nominal diameter (feet). Equation A1-4 is plotted in Fig. A1-2.

Chemical Engineering Plant Cost Index (CEPCI)

A plant cost index obtained from 1984 and 1990 Chemical Engineering was used to convert all cost data in 1990 dollars. This particular cost index was chosen since the pipeline cost data contained labor as a cost component. A linear regression analysis of the resulting data yielded the following estimation in 1992 dollars :

$$C_{pc4} = 215.6 D - 35.95 \quad (A1-5)$$

where C_{pc4} is pipeline costs (\$1000/mile); and D is pipeline diameter (feet). Equation A1-5 is also plotted in Figure A1-2.

4. Conclusion

To provide a comparison of the indexed pipeline construction cost estimations, Eqs. A1-1 (Liu and Wu), A1-4 (CPI), and A1-5 (CEPCI) are plotted in Figure A1-3. The indexed values of the pipeline construction cost estimates are relatively parallel over the nominal pipe diameter of 8 to 20 inches. Both indexed equations (CPI and CEPCI) are below the previous pipeline construction cost estimated. The effect of constraining the pipeline construction cost data available to meet the criteria of Midwestern plain regions and pipelines greater than 50 miles better approximates the conditions where the coal log pipeline will be constructed. However, to be conservative in cost estimate, Eq. A1-1(Liu and Wu, 1990) will be used in this report. When converted to 1992 dollars , Eq. A1-1 becomes

$$C_{pc5} = 129 D^{1.34} + 102 D^{0.87} + 24 D + 20 \quad (A1-6)$$

where C_{pc5} is pipeline costs (\$1000/mile); and D is pipeline diameter (feet).

Appendix 2: Pump Costs

The estimate of pump costs given on page 13 of the previous report (Liu and Wu, 1990) is

$$C_{u1} = 850(H_p)^{0.6} \quad (A2-1)^*$$

where C_{u1} is pump costs in 1990 dollars; and H_p is the horsepower of the pump. The estimate was based on centrifugal water pump costs. In places where water pumps are used, as at pipeline intakes, Eq. A2-1 is converted to

$$C_{uw1} = 930(H_p)^{0.6} \quad (A2-2)^{**}$$

where C_{uw1} is water pump costs in 1992 dollars; and H_p is the horsepower of the pump.

In the present revised study, it is assumed that the presence of coal particles in the water will require the use of slurry pumps at booster stations. Cost estimates for booster pumps are based on data for a selected number of slurry pumps obtained from Barrett, Haentjens & Co. located in Hazleton, Pennsylvania. Pump components and costs (1992 dollars) are summarized in Table A2.1 for three flow rates. A graph of pump costs as a function of horsepower is shown in Fig. A2-1. A regression analysis of the curve in Fig. A2-1 provides the following equation for cost estimate:

$$C_{us1} = 1122(H_p)^{0.805} \quad (A2-3)$$

where C_{us2} is slurry pump costs in 1992 dollars; and H_p is the horsepower of the pump.

*Same as Equation 21 of the previous report (Liu and Wu, 1990).

**1992 dollar conversion based on United States Financial Data issued by the Federal Reserve Bank of St. Louis in January, 1992 and Stocks, Bonds, Bills and Inflation 1991 Yearbook, 1991. Chicago, Illinois: Ibbotson Associates.

**Table A2.1 - Cost Data (1992) on Slurry Pumps Supplied by
Barrett, Haentjens & Co.**

1850 GPM System: \$ 414,920

7 pumps 300 feet total developed head each
1 variable pump for 150 to 300 feet total developed head
8 250 horsepower 1800 rpm motors
8 V-belt drives, 1770 rpm to 1550 rpm
1 variable frequency power supply
460 volt, 3-phase, 0-60 Hz output for 250 hp motor
8 bases total, one for each pump set, gear drive, and motor
2 extra sets of couplings

5550 GPM System: \$ 900,781

5 pumps 390 feet total developed head each
1 variable pump at 350 to 450 feet total developed head
6 880 horsepower, 1800 rpm motors
6 parallel shaft gear reducers
Input: 1770 rpm; Output: 1380 rpm
1 gear reducer, rated for 800 horsepower continuous operation
6 bases total, one for each pump set, gear drive, and motor
2 extra sets of couplings

6250 GPM System: \$ 1,134,548

5 pumps 400 feet total developed head each
1 variable pump at 300 to 355 feet total developed head
6 900 horsepower 1800 rpm motors
1 1000 horsepower ac motor
6 parallel shaft speed reducers
Input: 1770 rpm; Output: 1325 rpm
1 fluid coupling, 1770 rpm input speed, 100 hp continuous duty
6 bases total, one for each pump set, gear drive, and motor
2 extra sets of couplings

Fig. A2-1. Slurry Pump Costs as a Function of Horsepower.

Appendix 3: Water Costs

1. Introduction

The cost estimate for water listed on page 19 in the 1990 report (Liu & Wu) is \$0.40/100 ft³. As reported, this represents about one-half the cost of treated drinking water charged to large customers in Columbia, Missouri, 1989. This resulted in an annual water cost for the coal pipeline of

$$C_W' = 126 Q_W \quad (A3-1)^*$$

where C_W' is the annual cost (\$1000) in 1990 values; and Q_W is the discharge (volumetric flow rate) in cubic feet per second (cfs).

However, the availability of brackish water in dry, arid regions may provide the medium needed for coal log transport in pipelines without competing with regional water demands. Usually, brackish water is unsuitable for coal log transport unless the solids (salts) are removed. This calls for an evaluation of the technical and economic feasibility of desalination techniques for meeting the water requirements of a coal log pipeline.

2. Reverse Osmosis

Desalination techniques and their effectiveness in providing product water containing low levels of total dissolved solids (TDS) are dependent upon the initial TDS content of the raw water. The raw water is generally characterized by TDS content as **fresh water** (TDS < 500 ppm), **brackish water** (500ppm < TDS < 35,000ppm), and **saltwater** or **saline water** (TDS > 35,000ppm).

*Same as Equation 21 of the previous report (Liu and Wu, 1990).

At present, reverse osmosis is the most cost effective method to desalt water in large quantities. Simply stated, reverse osmosis is the process where a semipermeable membrane separates TDS from two solutions. Raw water, under pressure, passes across the membrane where a transfer of salts is impeded by the membrane, yielding a product water containing less TDS.

Membranes are an integral part of the reverse osmosis process. Membrane types currently used in industrial applications are hollow fiber (parallel bundled tubular membranes) and spiral wound (rolled long porous membrane sheets). Fluxes and salt rejection rates have increased over the last decade with the enhancement of membrane materials and design. Given a specific plant design, the raw water is usually pre-treated to meet membrane design criteria (pH, temperature, and pressure).

3. Reverse Osmosis Costs

TDS in brackish water range widely both regionally and locally. In order to approximate desalination costs, data was taken from [2,8,10,11,12]** where desalination costs was given for various reverse osmosis plants in operation within the continental United States. While costs vary between individual plants based on the local brackish water TDS, process rejection rates, and product water quality, general costs trends over the last two decades can be determined.

Costs of desalinating brackish water in million gallons per day (MGD) plant sizes was obtained from the sources listed above and converted to 1991 dollars by two indices [1,5]. Data for three plant sizes, 1 MGD, 5 MGD and 10 MGD, are plotted as a function of year in Figures A3-1, A3-2, and A3-3 respectively.

Figures A3-1, A3-2 and A3-3 indicate the cost reductions over the last two decades of desalinating brackish water due to the advancement in membrane technology and process design. A comprehensive report issued by the Office of Technology [12] in 1988 determined desalination costs for

**Numerals in [] correspond to reference numbers listed at the end of this Appendix.

brackish water to have decreased from \$5 per 1,000 gallons in 1963 to about \$1.50 to \$2.50 per 1,000 gallons (1985 dollars). The report also indicates that low pressure reverse osmosis membranes can further reduce desalination costs by \$0.50 per 1000 gallons (1985 dollars). This translates into \$2.01 to \$3.35 per 1,000 gallons with further costs reductions at low pressure of \$0.67 per 1,000 gallons (1992 dollars) [1,5].

4. CONCLUSION

The previous water costs estimate was based on one-half the cost of treated drinking water charged to large customers in Columbia, Missouri. Reflected in 1992 dollars and rounded to the nearest \$1,000, annual water cost were estimated to be

$$C_W' = 138 Q_W \quad (A3-2)$$

where C_W' is annual cost (\$1000) in 1992 values; and Q_W is discharge in cubic feet per second (cfs).

Costs for brackish water desalination by reverse osmosis in 1992 dollars are \$2.01 to \$3.35 per 1,000 gallons (\$1.50/100 ft³ - \$2.51/100 ft³). Using the average value of \$2.01 per 100 ft³, the following equation can be used to estimate the annual water cost for desalted water:

$$C_W' = 634 Q_W \quad (A3-3)$$

where C_W' is annual cost (\$1000) in 1992 values; and Q_W is water discharge in cfs.

Fig. A3-1. One Million Gallons per Day Plant Size
Desalination Costs (1992 dollars)

Fig. A3-2. Five Million Gallons per Day Plant Size.
Desalination Costs (1992 dollars).

Fig. A3-3. Ten Million Gallons per Day Plant Size.
Desalination Costs (1992 dollars).

References

1. Stocks, Bonds, Bills and Inflation 1991 Yearbook. 1991. Chicago, Illinois: Ibbotson Associates.
2. Channabasappa, K. C. 1975. "Status of Reverse Osmosis Desalination Technology." Desalination 17:31-67.
3. Czupryna, G., Gold, H. and Levy, R. 1986. Desulfication of Brackish Water by Ion Exchange for Calcium Sulfate Control. NTIS PB-87- 176236.
4. Dykes, G. M. 1983. "Desalting Water in Florida." J. Amer. Water Works Assoc. 75(3):104-107.
5. Federal Reserve Bank of St. Louis. January 16, 1992. United States Financial Data
6. Homer, W. A. 1968. "New Concepts for Desalting Brackish Water." J. Amer. Water Works Assoc. 60(8):869-881.
7. Hornburg, C. D., Morin, O. J. and Hart, G. K. 1975. Commercial Membrane Desalting Plants: Data and Analysis. NTIS PB-253-490: Office of Water Research and Technology.
8. Larson & Associates. 1979. A Study of the Energy Utilization in Operating Osmosis Systems. Oak Ridge National Laboratory for DOE: Oak Ridge, Tennessee. ORNL/TM-6735.
9. Melancon, S. M., Hess, B. C. and Thomas, R. W. 1979. Assessment of Energy Resource Development Impact on Water Quality: The Belle Fourche and Little Missouri River Basins. (Final Rept.). Interagency Energy - Environment Research and Development. U.S. Environmental Protection Agency. Las Vegas, Nevada.
10. Robinson, M. P., G. P. Westerhoff and T. M. Leahy. 1983. "Desalting - A Water Supply Alternative for Virginia Beach." J. Amer. Water Works Assoc. 75(3):109-117.
11. Streeter, R. L. 1973. The Potential of Desalting for Industrial Water Supplies in Northeastern Wyoming. NTIS: Office of Saline Water Report.
12. U.S. Congress Office of Technical Assessment. 1988. "Using Desalination Technologies of Water Treatment." OTA-BP-O-46 (Washington DC: U.S. Government Printing Office).
13. Yeatts, L. B., P. M. Lantz and W. L. Marshall. 1974. "Calcium Sulfate Solubility in Brackish Water Concentrates and Applications to Reverse Osmosis Processes; Polyphosphate Additives." Desalination 15:177-192.

END

**DATE
FILMED**

5 / 11 / 92