DOE/ER/13786--T3

DE92 016468

DE-FG-05-87-ER-13786

MECHANISMS OF FLOW THROUGH COMPRESSIBLE POROUS
BEDS IN SEDIMENTATION, FILTRATION, CENTRIFUGATION,
DELIQUORING, AND CERAMIC PROCESSING

FEBRUARY 1, 1991 / JANUARY 31, 1992

FRANK M. TILLER

UNIVERSITY OF HOUSTON
DEPARTMENT OF CHEMICAL ENGINEERING
HOUSTON, TEXAS 77204-4792

JUNE, 1992

REPORT SUBMITTED TO
OFFICE OF BASIC ENERGY—DIVISION OF CHEMICAL SCIENCES
THE U.S. DEPARTMENT OF ENERGY
UNDER GRANT NUMBER DE-FG05-87ER-13786

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

TABLE OF CONTENTS

Letter of Transmittal	
Introduction	1
Active Personnel	3
Summary of Research in Progress	4
Centrifugation	5
Cake Filtration	6
Sedimentation and Thickening	9
Capillary Suction Operations	12
Optimization Studies	14
Additional Investigation	15
Publications, 1990-92	17
Literature Cited	17

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

INTRODUCTION

Separation of particles from fluids is of fundamental importance in a vast array of industrial processes and human activity. In a general sense, particles consist of matter occupying a given volume in space and possessing a definite surface. Particles of interest in this research start with macromolecules and continue into the micron and millimeter ranges. They may take the form of precipitates, flocs, dust, foam, bubbles, mist, seeds, smoke, and droplets. Separation techniques are represented by many operations depending upon the size, shape, density, concentration, degree of aggregation, and interfacial characteristics of the particles in relation to the carrier fluid. The structural properties of the beds formed in the process of separation in response to stress are significant to the choice of a procedure for separation. Among separation operations will be found cake and deep-bed filtration, filtering and sedimenting centrifugation, sedimentation, thickening (gravitational, centrifugal, and cross-flow) coalescence, flotation, membranes, and cyclones. Separation of particles from fluids is an important element in many diverse fields including coal beneficiation, mining, oil field operation, environmental protection, flue gas desulfurization, pulp and paper, biotechnology, and the chemical process industry. Closely related to fluid/particle separation are slurry transport, mixing, and processing and storage of particles.

Growing international emphasis on protecting the environment will lead to potentially enormous investments by industry and government. Wastes must be recycled, landfilled, dumped into aqueous bodies, or burned to carbon dioxide and water vapor. Solution to the problems involving waste streams rests principally on fluid/solid processing and separation. Unfortunately, the U.S.A. lags Europe and Japan in providing educational opportunities for students of science and engineering in that area. In addition, disciplines involving the various separation techniques have grown independently with relatively little cross-over from closely allied fields such as filtration, thickening, and centrifugation. As design and operation of equipment has been empirical and based upon experience, interaction on an industry-to-industry basis has been limited. Experts in the various solid/liquid separation operations have seldom attempted to harmonize the common underlying principles. As a consequence, multi-authored textbooks generally consist of independent, unrelated sections on thickening, cake filtration, and centrifugal filtration—when, indeed, any theoretical treatment at all has been attempted.

The University of Houston research program is aimed at the specific area of solid/liquid separation including sedimentation, thickening, cake filtration, centrifugation, expression, washing, deep-bed filtration, screening, and membrane separation. Unification of the theoretical approaches to the various solid/liquid separation operations is the principle objective of the research. Exploring new aspects of basic separation mechanisms, verification of theory with experiment, development of laboratory procedures for obtaining data for design, optimizing operational methods, and transferring the results to industry are a part of the Houston program.

New methodology developed in our program now permits an engineer or scientist to handle thickening, cake filtration, centrifugal filtration, and expression in a unified manner. The same fundamental equations are simply adapted to the differing parameters and conditions related to the various modes of separation. As the system is flexible and adaptable to computational software, new developments can continually be added.

Discussions of the various research projects in this report have been kept to a minimum and are principally qualitative. The length of the report would be excessive if each topic were covered in depth. Although the number of research topics may appear larger than one would expect, many are closely interconnected and reflect our philosophy of working in apparently diverse fields such as ceramics, mining, wastewater, food, chemical processing, and oil well operations. They also represent the efforts of many years of activity.

We should like to take special note of our activity in using the CATSCAN for studying some of the troublesome problems underlying the settling of flocculated particles and flow through compactible cakes. New insights into the relative movement of particles and liquids in sedimentation and filtration operations were obtained from data taken with the Computerized Axial Tomographic Scanner (CATSCAN) located in the Enhanced Oil Recovery Laboratory two years ago. As a consequence, we were able to modify existing theory and point out serious deficiencies in analyzing and using laboratory data for design purposes. Unfortunately operation and maintenance of the CATSCAN is costly, and users must assume part of the financial liability. Funds requested for the CATSCAN were eliminated in the last two years of our program, and we were unable to continue with our research in that area. We are including \$8,000 for the CATSCAN in our annual budgets.

ACTIVE PERSONNEL

Principal Investigator

Frank M. Tiller, M.D. Anderson Professor of Chemical Engineering

Co-Investigator and Program Coordinator

N.B. Hsyung, Research Scientist

Visiting Researchers

Prof. D.Z. Cong, East China Institute of Chemical Technology, Shanghai, PRC

Dr. A.I. Yelshin, Novopolotsk Technical Institute, USSR

Dr. A.M. Kirby, CSIRO, Canberra, Australia

Prof. Avner Adin, Hebrew University, Israel

Mr. Y.L. Shen, East China Institute of Chemical Technology, Shanghai, PRC

Research Students

Graduate: S.L. Tarng, V. Thopay, F. Zhou, H. Makino

Undergraduate: Grace Tsai, Lee Coffelt

High School: N.F. Coffelt, Emanuel Garcia

Prof. D.Z. Cong is a well-known author of chemical engineering texts in China. He has been partially supported by the Chinese Government and funds from Dow Chemical Co.

Dr. A.I. Yelshin spent an academic year in Houston under the auspices of IREX as a Visiting Researcher. Solid/liquid separation is his specialty at the Novopolotsk Technical Institute which is located in Byelorussia. His support came from IREX.

Dr. A.M. Kirby of the Soils Division of the Commonwealth Scientific and Industrial Research Organization, Canberra, Australia spent one month in our Fluid/Particle Separation Laboratory. He analyzed data involving radial deposition of cakes. He was supported by funds arising from the M.D. Anderson Chair of the principal investigator.

Prof. Avner Adin of Hebrew University in Jerusalem, Israel spent an academic year as part of the team. He was partially supported by the DOE grant.

Mr. Y.L. Shen was a visiting scholar from the People's Republic of China. He was partially supported by the DOE grant and was principally involved in experimental aspects of the research.

SUMMARY OF RESEARCH IN PROGRESS

- 1. CENTRIFUGATION**
 - a. Centrifugal filtration theory
 - b. Centrifugal cake sedimentation theory
 - c. Comparison of cakes produced in filters and centrifuges
 - d. Dependence of rates on operation parameters
 - e. Centrifugal filtration experiments
- 2. CAKE FILTRATION**
 - a. Cake filtration combined with sedimentation
 - b. Radial filtration
 - c. Improved cake filtration theory
- 3. SEDIMENTATION AND THICKENING**
 - a. Theory of continuous thickening
 - b. Sedimentation studies with CATSCAN and gamma rays
 - c. Transient operation of thickeners
 - d. Fluidization of compressible sediments
- 4. CAPILLARY SUCTION OPERATIONS**
 - a. Slip casting of ceramics
 - b. Capillary suction apparatus
- 5. OPTIMIZATION STUDIES**
 - a. Optimizing tubular arrangements in candle filters
 - b. Maximizing filtration rates with filter aids.

1. CENTRIFUGATION

Centrifugal Filtration Theory. A series of studies have been carried out covering both sedimenting and filtering centrifuges. Centrifugation theory of concentrated suspensions (in the zone settling region) presently in the literature has been developed principally for incompressible beds. Inclusion of the effect of compressibility in our studies has led to improved understanding of the relative performance of filters and centrifuges (both sedimenting and filtering) with respect to average cake porosity.

Stresses in Filtering and Sedimenting Centrifuges. Compressive stresses are developed by centrifugal body forces and by frictional drag due to flow of liquid through the porous cake. In a sedimenting centrifuge, the solids flow toward the bowl; and the displaced liquid flows away from the bowl in the opposite direction. Consequently, the liquid flow *retards* consolidation. When the cake has reached an equilibrium state, there is no flow; and the final average porosity of the cake will depend entirely on the centrifugal body force. By contrast in a filtering centrifuge, the liquid flows through the cake in the same direction as the sedimenting solids. The frictional drag increases the compaction forces and is added to the centrifugal body force. Thus the centrifugal filter is more effective in both speed of cake deposit and reduction of the liquid content of the cake.

Specifications based on experience indicate that commercially available filtering centrifuges generally are designed with larger diameters and lower angular speeds in comparison with sedimenting centrifuges. Inclusion of the effect of compaction in the theory leads to predictions which confirm rotational speeds and diameters which have evolved through experience. The formulas also point to the theoretical superiority of centrifugal filters. Practical problems of clogging of the perforated bowl have prevented the filtering centrifuge from replacing decanters. However, lower speeds and larger diameters typical of centrifugal filters points to the possibility of reducing maintenance (proportional to the cube of the speed) and increasing throughput (Tiller and Hsyung, "Comparison of Compacted Cakes in Sedimenting and Filtering Centrifuges," 1990).

Comparison of Cakes in Filters and Centrifuges. Pressure filters, centrifugal filters, and sedimenting centrifuges (decanters) were compared with respect to the volume fraction of solids produced under equilibrium conditions. The behavior of three hypothetical materials were compared under a wide range of pressures and bowl speeds. Two highly flocculated examples with specific gravities of 1.1 and 4.0 were included along with a slightly compactible relatively easy to filter material. Compaction is effected by centrifugal forces in a decanter, frictionally generated drag due to liquid flow in vacuum and pressure filters, and both factors in centrifugal filters. The analysis applies to suspensions which are sufficiently concentrated to ensure zone settling.

Filters are ineffective in reducing the liquid content of highly compactible flocs unless expression techniques (not covered in this paper) are employed. At low centrifuge speeds and with thin cakes, frictional drag dominates compaction; and compared with decanters, filtering centrifuges theoretically provide products with smaller liquid content, particularly with low density solids. As centrifuge speed increases and centrifugal stresses grow, decanters begin to approach perforated bowl centrifuges in performance provided there is sufficient density difference between the solid and liquid. With neutrally buoyant materials, decanters are inoperative; and filtering centrifuges and filters are equally ineffective with super compactible cakes (Tiller and Hsyung, "Relative Performance of Filters and Centrifuges with Respect to Average Porosity," 1990).

1A. FUTURE WORK IN CENTRIFUGATION

Theoretical Investigation of Transients. Cake formation in both filtering and sedimenting centrifuges is accompanied by centrifugal sedimentation of the suspension. The flux at the cake surface is a function of the rate of sedimentation which varies with time. An unsolved problem concerning the flux involves solution of a first order hyperbolic differential equation. Characteristics (which arise in the solution of hyperbolic equations and are lines of constant concentration) arising from the bowl may lead to lower than presently predicted sedimentation rates. This topic is one which will be further investigated.

At some point in time, we plan to solve the partial differential equations governing centrifugal sedimentors. Solution of the hyperbolic equations involving sedimentation must be combined with the second order parabolic differential equations governing cake formation. Numerical solutions will be required.

We have documented the effect of the degree of cake compressibility and the effect of pump pressure on the flow rate and the average cake porosity in filters. For beds formed from highly compactible flocs, increasing pressure above a value in the neighborhood of one atmosphere in filters has little effect on either the rate or the average cake porosity. Our existing theoretical analysis of centrifugal filtration will now permit us to demonstrate the effect of bowl speed, bowl diameter, densities of solids and liquid, and parameters governing compactibility on rates of production and average cake porosity. We plan to produce charts for centrifugation which are similar to those we have published for filtration.

Experimental Work in Centrifugal Filtration. We have recently obtained a small basket centrifuge which is being modified so that cake thickness can be measured as a function of time. We hope to obtain data confirming our predictions concerning the effect of compactibility on flow rate and average porosity.

2. CAKE FILTRATION

Cake Filtration Combined with Sedimentation. Filtration is carried out industrially with the cake deposited (1) horizontally on a surface facing upward (horizontal leaf filter) (2) horizontally on a surface facing downward (drum filter rotating with a portion of the filter surface immersed in the slurry), or (3) vertically (vertical leaf, plate-and-frame, or disc filter). Laboratory filters are most frequently of the type in which cake is deposited on the top side of a horizontal medium as exemplified by a Buchner funnel filter. In all of these filters, gravitational sedimentation is of importance. The gravitational deposition of solids on cakes has been omitted from most theoretical developments.

CATSCAN studies enabled us to ascertain the precise effect of sedimentation and to demonstrate how it could be identified in an ordinary laboratory constant pressure filtration on a horizontal surface facing upward. After all of the solids had been deposited, the remaining liquid flowed at constant pressure through the cake which had a constant resistance. Consequently, the flow rate was constant; and the filtrate volume was linear in time. The linear portion of the filtrate curve is easy to identify and permits accurate calculation of average values of the permeability and specific resistance (Tiller et al., "CATSCAN Analysis of Sedimentation and Constant Pressure Filtration," 1990).

Radial Filtration. A new analysis of data previously taken in our laboratory with a filter equipped with a radial surface has been analyzed in connection with previously developed theory. The theory has been validated (Tiller, Kirby, and Nguyen, 1992).

Improved Cake Filtration Theory. A simple but fundamental contribution has been made to the analysis of experimental filtration data. Throughout the literature, variants of the following formula have been employed for data analysis and prediction of volume vs. time

$$q = \frac{dv}{dt} = \frac{p}{\mu(\alpha_{av}cv + R_m)} \quad (1)$$

where v = volume of filtrate per unit area, t = time, p = applied pressure, μ = viscosity, α_{av} = average specific resistance, c = mass of inert solids in cake per unit volume of filtrate, and R_m = resistance of the supporting medium. The value of c as derived from a material balance takes the value

$$c = \frac{\phi_s}{1 - \phi_s/\epsilon_{sav}} \quad (2)$$

where ϕ_s = volume fraction of solids in the slurry and ϵ_{sav} = average volume fraction of solids in the cake. Before Eq. 1 can be employed, ϵ_{sav} must be experimentally determined. Normally, the cake is analyzed at the end of an experiment, and the final value of ϵ_{sav} is then obtained. As the average solidsity varies during a filtration, there are theoretical objections to using the final value. In the new formulation, cake thickness is determined along with v . A simple material balance shows that

$$cv = \phi_s (v + L) \quad (3)$$

which then allows Eq. 1 to be re written as

$$R = \frac{pdt}{\mu dv} = \alpha_{av}\phi_s (L + v) + R_m \quad (4)$$

In this form, the resistance R can be plotted against $\phi_s (L + v)$; and α_{av} and R_m can then be obtained from an analysis of the plots. An equation for prediction of volume vs. time with requiring prior knowledge of the average cake solidsity has been derived in the form

$$\mu v \frac{dv}{dt} = \int_0^{\Delta p_c} \left(\frac{1}{\phi_s \alpha} - K \right) dp_s = \int_0^{\Delta p_c} \left(\frac{1}{\phi_s} - \frac{1}{\epsilon_s} \right) \frac{dp_s}{\alpha} \quad (5)$$

where α , K , ϵ_s are the respective local values of the specific resistance, permeability, and volume fraction of solids and Δp_c = pressure drop across the cake. The average solidsity can also be obtained as a function of time when both L and v are obtained as functions of t (Tiller, Cong, and Hsyung, 1992).

New Laboratory Filter. Prof. Cong with support from Dow Chemical Co. constructed a new rotating filter which permits simultaneous measurement of cake thickness and filtrate volume. The filter consists of a slowly rotating (variable speed) cylinder with a vertical filter surface at one end. The vertical surface avoids gravitational sedimentation inherent to horizontal filter surfaces, and the rotation maintains a uniform suspension concentration. This remarkable but simple device could easily become the standard for laboratory work. In addition to providing conditions compatible with theoretical assumptions underlying filtration theory, the filter serves as an instructional device in highlighting the dangers associated with horizontal filter surfaces. In addition to providing

theoretically correct average values of specific resistance (Eq. 3), permeability and solidosity can be obtained as a function of the pressure drop across the cake. Local values can then be estimated by manipulation of the data in accord with procedures developed at Houston many years ago.

The filter can also be used for obtaining data in the region of importance in continuous thickening. The use of low heads in the feed tank yields data in the low pressure region necessary for design purposes. This use of the filter is particularly useful as low pressure data for permeability and solidosity are virtually non existent.

Some improvements in the filter can provide even more idealized conditions. The medium resistance which usually assumed to be constant is necessary for calculation of the pressure drop across the cake. As the medium resistance is known to vary from our previous research (Tiller, Kirby, and Nguyen, 1992), its direct measurement would represent an improvement. It is planned to run a tube (rotating with the filter down the center of the cylinder containing a low pressure transducer or other device to measure the pressure at the medium. Then both the medium resistance and the pressure drop across the cake can be measured (Tiller, Cong, and Hsyung, 1992).

2A. FUTURE WORK IN FILTRATION

Migration of Fine Particles. Many filtrations involve slurries having particles ranging from the sub-micron to larger sizes. The fine particles can migrate through the pores of the bed, pass through the supporting medium, and appear in the filtrate. In previous studies of the filtration of liquefied coal, we showed that migration was a significant factor that required a major modification of the basic differential equations. The specific resistance was shown to be a function of deposition of migrating particles as well as the local effective stress. Empirical equations were used for data analysis.

An analysis of a simple system involving a slurry containing a bimodal mixture of fine and coarse particles has been initiated. The fine particles can undergo both deposition and removal (scouring) in the interstices of the cake which is assumed to be incompressible. After the analysis of the incompressible system is complete, more complex compactible cakes with particle migration will be studied.

Approximations Underlying Filtration Theory. Most simplified filtration theory is based upon Eq. 1 which rests on the assumption of a constant superficial flow rate q through the cake. Assumption of constant q leads to a pseudo steady-state model in which the variation of porosity throughout the cake is assumed to change very slowly with time. Where dilute suspensions are involved and the cake is moderately compactible, the pseudo steady-state model is thought to be correct within a few percent. However, for concentrated slurries forming highly compactible beds (waste water sludges, flocculated materials), the assumption of constant q is dubious.

There are two sources of error. One is associated with the numerical solutions of the basic mathematical equations and the second involves errors in the underlying scientific principles such as ignoring migration of particles and assuming that the permeability and specific resistance are unique functions of the effective stress. Each of these problems must be treated independently if a given theoretical foundation is to be appropriately tested. The first step in analysis of existing theory requires accurate numerical solutions of the full partial differential equations and comparison with the approximate pseudo steady-state models. A number of investigations in our laboratory have made cursory studies of the equations which have pointed to the need for more complete information. We propose solving the complete equations and determining the magnitude of the error involved in using existing approximate solutions. Guide lines can then be drawn up for defining ranges of parameters in which the approximate equations can be employed for design

purposes. In addition, more rigorous tests of experimental data can be undertaken to verify basic physical principles.

3. SEDIMENTATION AND THICKENING

Theory of continuous Thickening. A generalized graphical procedure was developed for determining the sediment height L of a continuous, flat-bottom thickener required to produce an underflow concentration ϵ_{su} at a given solid flux q_s . The method is based on an observation that plots of $\log L$ vs. $\log q_s$ at constant ϵ_{su} are approximately hyperbolic with asymptotes given by the minimum height L_{min} and the maximum flux q_{max} . An analytical equation for L_{min} as a function of q_{smax} provides an operating line on which a generalized relation of L/L_{min} vs. q_s/q_{max} is superimposed. The resulting curve permits calculation of L as a function of q_s for any system.

Although the method is based upon equations developed previously in our research, the procedure should prove to be adaptable to improved formulations or to direct use of laboratory or field data. Limitations and accuracy of the proposed method are undergoing further study (Tiller and Tarrg, 1992).

Sedimentation Studies With CATSCAN. A study of batch sedimentation of kaolin in the first year (1990) of the present research program revealed several surprises and tantalizing puzzles. Whereas the usual analysis of sedimentation phenomena assumes the existence of a sharp line of demarcation between the sediment and slurry, CATSCAN profiles indicated that what appeared to be the sediment surface extended far out into the suspension. With an *apparent* cake thickness of about 1-2 cm., a region of up to 5 cm. with concentrations close to the concentration at the presumed cake surface extended out into the suspension. It is thought that the upward flow of liquid from the compacting sediment may have been large enough to maintain the surface in a fluidized condition. If this presumption should prove to be valid, a number of anomalies in suspension behavior may be solved (Tiller, Hsyung, Shen, and Chen, 1990).

In another study involving simultaneous sedimentation and filtration, an apparent anomalous increase in concentration was observed in the slurry above the cake. In pure sedimentation, a first order hyperbolic differential equation (simpler than the corresponding equation in centrifugal sedimentation) controls the concentration vs. distance from the bottom of the container. Characteristic waves caused by the slowdown of particles deposited in the accumulating sediment move upward into the suspension and cause the settling rates to decrease. The velocity of the upward characteristic is less than the settling velocity for equal concentrations. When filtration takes place in addition to sedimentation, it has always been tacitly assumed that the filtrate velocity would be larger than the characteristic velocity and, therefore, that the characteristic wave would be "buried" in the cake. If the characteristic is buried, there would be no change in the suspension concentration above the cake. The appearance of a region of changed concentration in the CATSCAN studies indicates that some of the characteristics might not be "buried." Unfortunately, funding for the CATSCAN experiments was terminated with a budget cut, and we were advised to include note of the reduction in work plans so that interested parties would understand the abrupt cessation of activity. In this proposal, we are requesting funds to continue the studies.

Fluidization of Compressible Sediments. The theory of fluidization of large particles forming incompressible beds does not apply to compressible sediments and must be modified. The usual theory predicts the simultaneous fluidization of all particles and they maintenance of uniform concentration dependent upon the velocity of the fluid relative to the solid. A compressible bed fluidizes at the bottom, and the entire bed then rises as a rigid body. However, when the bed begins to rise, and unstable density condition exists;

and the cake begins to disintegrate. We use the term "lift-up" to emphasize the contrast with fluidization which leads to uniform expansion of the entire bed.

The lift-up velocity which is identified by the appearance of cracks at the bottom of the cake is determined by the permeability at the bottom of the cake. Thus determination of the lift-up velocity permits calculation of the corresponding permeability. The effective pressure at the bottom can be obtained from a knowledge of the unbuoyed weight of the sediment. Permeability can be obtained as a function of effective pressure in a range of interest in thickening by varying the height of the sediment (Thoppay, 1990).

3A. FUTURE WORK IN SEDIMENTATION AND THICKENING

Modifying Continuous Thickener Theory. Models for thickeners such as the Coe-Clevenger, Kynch, Fitch, and the one introduced in our research, are all based on a flat-bottomed tank. As practical thickeners are equipped with sloping bottoms, calculations based on existing models are inherently approximate. Further theoretical advances depend upon developing a more realistic model which includes the effect of the sloped bottom and, also of equal importance, the rheological properties of the sediment. Non-newtonian characteristics of the sediment, frictional effects of movement down the sloped bottom, and raking action will affect the final formulas.

As time becomes available, the present theory will be widened in scope starting with consideration of the flow of sediment along the sloped walls. The second stage of investigation will focus on the effect of the sediment rheology on flow patterns which are basic to any more realistic approach.

Free Settling Zone in Equilibrium with Compressed Sediment in Continuous Thickeners. Thickening can be effected in two distinct modes. In the first, particles settle freely (zone settling) and are not in direct contact. In the second mode, particles enter into contact and form a sediment (compression zone). In general in comparison to thickening where compressed sediments are encountered, free settling produces higher solid flux rates and lower underflow concentrations. However, under some circumstances, both forms of settling have been observed to occur simultaneously in commercial thickeners. It is not known whether a slow transient or a steady-state existed. The Coe and Clevenger (C-C) flux methods and its offshoots have been the principal methods used for predicting the behavior of steady-state, continuous thickeners. They are not applicable where compression zones exist. The C-C formulation and its offshoots depend upon existence of a unique relationship between the settling rate and suspension concentration. Restraints on the motion of particles forming sediments lead to a more complex situation in which the settling rate is no longer a unique function of concentration. The settling velocity in a sediment depends on the local permeability and the liquid pressure gradient in a Darcian-type equation. Depth is theoretically of no importance in free settling thickeners and does not enter into derivations. In contrast, depth is of fundamental significance in methods involving compressed sediments.

Although it appears that the two modes are incompatible, preliminary analyses indicate that under certain circumstances the convected flux (due to the underflow velocity) in thickeners with sediments may be large enough to offset the inherently higher relative flux of free settling. CATSCAN data have provide information on settling rates at different positions in cakes which support the possibility of an equilibrium relation existing between a free settling zone above a compressed sediment and a free settling zone above the sediment surface.

The theoretical side of this problem can be pursued without obtaining further experimental data. Reactivation of the CATSCAN program would provide important corroborative information. Solution of this problem important to an improved understanding of thickener operation.

CATSCAN and Gamma Ray Studies. A continuation of previous studies involving the CATSCAN laboratory is being proposed. As discussion of proposed work appears throughout this proposal, no further explanations will be undertaken at this point. The CATSCAN equipment which formerly was in a mode for receiving horizontal specimens (as in a hospital) is now re-oriented into a vertical position. The depth of sedimentation cells was limited to about 200 mm in the former configuration. In the new vertical mode, deeper cells can be used. In addition, the scans will provide substantially more information concerning uniformity of concentration. We anticipate making an in-depth study of phenomena related to the sediment-suspense interface.

Control Theory for Transient Operation of Thickeners. In an earlier phase of our research, methodology was developed for studying transients in continuous thickeners by solving the appropriate partial differential equations. A very slow settling material was originally investigated, and transients lasted from days to weeks. With highly flocculated slurries, rates are higher and detention times shorter. If time permits, the earlier studies will be repeated; and strategies for control of underflow concentrations will be investigated. Assuming that a feed change takes place, an operator could manipulate the underflow rate, addition of flocculants, and the sediment height to obtain desired results in minimum time. Methodology for calculating the time required to change from one steady-state to another will be developed when sufficient time is available.

Experimental Thickener. A small thickener is available for such time as manpower becomes available for operation.

Mathematical Study of Batch Sedimentation of Discrete Particles or Flocs. Numerous studies of sedimentation based on continuum mechanics have appeared in the literature. Difficulties involving boundary conditions at the interface between the suspension and the rising sediment represent a major problem in the mathematical procedures. In general, interior solutions close to the interface must be developed and matched to exterior solutions in the suspension in order to satisfy both boundary conditions and the differential equations..

In another procedure investigated by our group, a model consisting of discrete particles has been employed. In the simplest one dimensional model, particles are located in a vertical column and then allowed to settle subject to laws concerning mutual interaction and formation of cakes. The particles are treated by discrete mathematics and the fluid by continuum methods. Use of finite differences in handling the particles leads to a set of mixed differential-difference equations. In this procedure, no matching of interior and exterior solution is required. The model consists of a vertical column of N initially uniformly spaced particles. A set of N simultaneous difference equations of motion result. Matrix methods are then used for numerical solutions. Three types of forces are assumed to act on the particles in addition to gravitation which is the driving force in both the suspension and compactible sediment regions. In the suspension, two forces are involved. One predominating in the dilute range is of the Stokes type. In concentrated regions and close to the sediment surface, a more intense lubrication type of force is employed. In the sediment zone, the third force based upon the Darcian drag is introduced.

In a preliminary study, it was possible to imitate settling characteristics of a clay and a barite along with buildup of a sediment. The method offers an opportunity for modifying the initially uniformly spaced particles into various combinations including particles joined together in the form of flocs. Various generalizations could provide increasing sophistication while retaining the particulate nature of the model. Renewed efforts will be directed first toward the simple existing model in an attempt to relate required parameters to measurable laboratory quantities.

Sedimentation of Sub-micron Particles. Ponds for storage of wastes frequently contain sub-micron particles which settle very slowly. Phosphate and petrochemical slimes are typical of materials requiring sedimenting times which may require months or years for completion of the process. Preliminary CATSCAN studies of the settling of bentonite indicated that classical sedimentation theory in colloidal science may have to be modified because of sediment formation. Equations normally employed are based on mono-sized particles and do not take into account variable sedimentation velocities, differing Brownian diffusion coefficients, effect of zone settling, or the appearance of a sediment capable of sustaining a compressive load. The CATSCAN combined with particle size measurements made at different depths offers an opportunity for improving existing theory. We plan to investigate sedimentation of bentonite, kaolin, titanium dioxide, and aluminum hydroxide.

When time permits, centrifugation studies will also be undertaken.

4. CAPILLARY SUCTION OPERATIONS

Capillary suction phenomena are of importance in various solid/liquid separation operations. In drainage and blowing of cakes to remove liquid, the applied pressure drop (or gravitational force) must be large enough to overcome the capillary pressure if liquid is to be removed. In a recently marketed disc filter, the permeable disc was manufactured with small pore diameters which prevent the entrance of gas during drainage of liquid due to the high capillary suction. As gas cannot enter the disc which remains saturated with liquid, the load on the vacuum pump is substantially decreased.

Capillary suction is the driving force in slip casting of ceramics and operation of the capillary suction apparatus used for testing the effects of slurry pretreatment on cake resistance.

Slip Casting of Ceramics. The first article in a series on slip casting published in the *Journal of the American Ceramic Society* covered casting on a plane surface. When slips are placed in contact with plaster molds, the liquid is sucked out; and a compressed layer or cake, generally called a green body, is formed.

The theory was extended to cylindrical geometry with both external and internal deposition. Because of increased mathematical difficulties, the first portion of the investigation was restricted to incompressible cakes. Differences exist between interior and exterior deposition, and conclusions concerning the optimum mold pore size are more complex than in the case of plane surfaces. The optimum mold suction varies with both cake thickness and whether the cake is on the inside or outside. For thin cakes, the criterion developed for the plane surface applies approximately to the cylindrical case. A procedure for choosing a mold which yields the maximum deposition rate was developed (Tiller and Hsyung, "Theory of Filtration of Ceramics II," 1991).

Capillary Suction Apparatus. The CSA is widely used in the environmental field for rapidly determining the resistance of cakes. In commercial apparatus, slurry is poured into a small cylinder resting on filter paper. Liquid is sucked radially into the paper, and a cake forms in the cylinder. The capillary suction time (CST) which represents the time required for the liquid front in the paper to pass from one radius to another is used as a measure of the relative resistance of the cake. Many researchers and environmental engineers have used the CST to determine the effect of various pretreatment methods on the resistance of cakes.

A new CSA with a rectangular reservoir was developed to replace the cylindrical model. Narrow strips (with a width of about 2.0 cm.) of filter paper are glued to the rectangular cell. When slurry is poured into the reservoir, liquid is sucked out; and a thin

cake is formed. The distance traveled by the filtrate front in the paper is measured as a function of time. Theory developed in our research then permits calculation of the average specific resistance (Tiller, Adin, and Shen, 1990).

Our simple rectangular CSA can be duplicated quickly and economically. In order to run tests quickly and simultaneously, we maintain a minimum of ten units ready for use.

4A. FUTURE WORK IN CAPILLARY SUCTION

Slip Casting Theory of Compactible Cake Formation on Curved Surfaces. The Theory of deposition of incompressible ceramic cakes on curved surfaces will be extended to compressible cakes. In general, compressibility is a byproduct of particle aggregation. As the size of aggregates or flocs increases in suspension, initial cake porosity on deposition also increases leading to increased permeability. An improvement in deposition rates may result from flocculation. However, the resulting green body density is unfavorably decreased. Thus a trade-off emerges between production rate and density. Product specifications, the ultimate market, and the unit sales price all affect the compromise on the degree of flocculation and the choice of mold.

The question of production rate is also affected by the ratio of mold to cake permeability. As pore size is increased in molds, permeability increases; capillary suction decreases; and the rate of cake formation for a given slip may increase or decrease. There is a specific ratio of permeability the pressure drop across the cake and the production rate maximize. Thus increasing cake permeability by flocculation does not necessarily lead to improved processing rates. Knowledge of the relationship of the effect of flocculation on cake compactness and permeability is essential for solution of equations which yield production rates. Further investigations aimed at developing methodology for choosing desirable properties of molds will be undertaken.

Capillary Suction Apparatus. In the course of research on CSA characteristics, two important features have been identified. The capillary suction time (CST), defined as the difference in time required for the liquid front to pass between two fixed distances (radial or rectangular coordinates), is used to compare different slurries. The use of two fixed points in the CSA is equivalent to determining a tangent to a fuzzy curve, a notoriously inaccurate procedure. Combination of the theory developed in this research with multiple time readings has led to more precise evaluation of cake resistances

The second feature involves the problem of using paper whose resistance is large compared to the cake resistance. With large paper resistance, values of CST are obtained by subtraction of one large number from another of comparable size with resulting inaccuracy in the calculated value. Theory provided a means for alleviating the problem. The CST was found to be proportional to the square of the thickness of the paper. Thus by simply doubling or tripling the number of pieces of paper used in the CSA, the CST could be multiplied four or nine times thereby leading to more accurate results.

Capillary suction measurements are strongly affected by both cake and paper properties. Just as with slip casting, an optimum paper probably exists for each slurry being tested. we propose investigation of the capillary suction and permeability of available papers in relation to CST measurements.

Ceramic Molds for Capillary Suction Tests. The reservoir and the paper in the CSA present different areas for flow. The paper has a relatively small cross-section compared to the reservoir. In slip-casting experiments, the plaster mold and the cake formed from the slurry have the same area. Although based on the same basic principles, the equations for slip casting and capillary suction apparatus take on slightly different forms. Theory indicates that the pressure drop across the cake in a mold remains constant throughout the

filtration. Constancy of the pressure drop is a valuable attribute because the simple theory normally employed for data analysis is based upon maintenance of a constant pressure drop across the cake. The capillary pressure can exceed one atmosphere and is thus comparable to vacuum used in Buchner funnel tests.

Cake Compression in Relation to Capillary Forces.. Highly compactible cakes are formed from slurries containing large flocs. Contrary to reasonable expectations, increasing filtration pressure has little effect on either flow rate or solid content of such cakes. Squeezing operations resulting from pressure actuated diaphragms in filter presses, rolls, and pressbelt filters must be employed to reduce liquid content after filtration is completed. When slurry disappears in vacuum filtration, the cake surface comes into contact with the atmosphere. If the pores in the cake are large, air enters the cake resulting in displacement of the liquid. This phenomenon is common in rotary drum filtration. If the pores are small and the capillary suction of the cake is larger than atmospheric pressure, air cannot enter the cake. However, the atmosphere then acts like a piston and squeezes the cake.

Although Prof. Richard Dick of Cornell has published data demonstrating the compaction effect at the end of filtration, no theoretical studies have appeared. Methodology previously developed in our program to study expression operations at the termination of filtration will be employed in an investigation of atmospheric compression.

Fingering of gas can lead to breakthrough without the uniform displacement predicted by continuum methods based on Darcian flow. Consequently, theory based solely on displacement phenomena must be combined with other approaches which take two-phase flow into consideration. Among others, Wakeman of Exeter, Dodds of Nancy, and more recently (1992) Stahl and Wunsch of Karlsruhe have presented methods for calculating the saturation of cakes being drained (gravitationally or centrifugally) or blown by gas pressure. A probable combination of atmospheric compaction along with drainage is a line of thought which deserves attention. Ramifications of squeezing and displacement are significant from both practical and theoretical viewpoints.

The porosity (and consequently pore size) varies markedly with distance through highly compactible cakes. A dense skin (Tiller and Yeh, 1987) forms at the supporting medium while the cake remains essentially unconsolidated at the cake surface. Thus the capillary pressure will vary throughout the cake being highest at the medium. Yeh (1986) showed that air can penetrate a portion of a cake without necessarily breaking through entirely. Many possible combinations involving complete, partial, and no penetration of cake surfaces by gas are possible and will be investigated in relation to pressure difference and capillary pressure sometime in the future.

5. OPTIMIZATION STUDIES

The general question of optimization underlies most of our research. Although the basic thrust is theoretical in nature, the resulting analytical formulas or numerical solutions permit rational approaches to minimization (e.g., liquid content of cakes, filter aids, wash liquid) and maximization (rates) of operating quantities. Much of the information has been slow to penetrate into industrial circles, and we shall continue to devote a portion of our efforts to publishing in this area.

Optimizing Tubular Arrangements in Candle Filters. Three problems were addressed in this research (Tiller and Yelshin, 1990). The first related to determination of the best spacing of the cylindrical filter elements for a specific slurry given the slurry concentration and the permeability and porosity of the cake. The second problem involved finding the best operating procedure for an existing filter and a particular slurry. Given the tank diameter, pump characteristics, dead time when the filter is out of operation at the

end of a batch, and the requirements for washing, the operator can only manipulate the pump rate and the cake formation time. Methodology for determining the best operating conditions were developed.

The third problem concerned the use of an existing filter to accommodate a wide range of slurries and cakes. Although seldom mentioned in the literature, compromise design of filters aimed at providing nearly optimal results for materials having a wide range of permeabilities and compressibilities is of industrial significance and can be addressed by techniques developed in this investigation.

Cake thickness is the major element in determining the best spacing for tubular elements. In general, maximum production rates are obtained with thin cakes when the rate of cake formation is low. Thick cakes and wide spacing of tubes are indicated for slurries which produce rapid buildup. Low permeabilities and low concentrations result in low rates of cake formation with the reverse being true for high permeabilities and concentrations.

Due to the complexity of the problem, the study was restricted to incompressible cakes. We plan to continue the study using compactible cakes, adding filter aids, and employing various pumping techniques, i.e., constant pressure, constant rate, and variable pressure pumps.

Maximizing Filtration Rates with Filter Aids. Procedures for optimizing the quantity of filter aid used to clarify dilute suspensions in candle filters were developed (Tiller, Hsyung, and Shen, 1990). In contrast to the usual assumption that there is a fixed fraction of filter aid admix which yields the best results, we demonstrate that the optimum amount of filter aid varies with cake thickness, tube spacing, permeability, and dead time.

Filter aid decreases the permeability of the cake but at the same time adds to its bulk. After a sufficient quantity of filter aid has been added, the additional bulk offsets the decreased unit resistance; the total resistance rises; and the flow rate decreases after having passed through a maximum. In filters with fixed cake space, filter aid occupies part of the space originally allocated to the product solids. Additional cycles are required in order to process the original quantity of the product. Substantial improvement in cycle rates is necessary to offset the increased bulk due to the filter aid.

Software developed in tip part of the research program permits rapid determination of the effect of various operating strategies on cycle rates.

6. ADDITIONAL INVESTIGATIONS

Modification of Stress Balances for Flow Through Compactible Beds. Problems of flow through compactible matrices of particles using continuum techniques require the solution of two simultaneous differential equations (Tiller et al, 1987) which are:

1. Darcian equation involving the gradient of the liquid pressure.
2. Momentum balance which usually reduces to a stress balance and involves gradients of both liquid and effective (accumulated stress in particulate matrix) pressures.

For incompressible beds, the effective pressure does not change the particulate structure; and the permeability is constant or a function of position. As a consequence, the stress balance is immaterial; and Darcy's equation can be solved by itself. When compressible beds are involved, the particulate structure changes with the effective pressure. The changing bed structure requires the simultaneous solution of both the Darcy and the momentum equations.

In the classical approach introduced by Terzaghi in soil mechanics, an equilibrium relationship is assumed to exist between the effective pressure and the cake structure. Such an assumption requires that structural changes take place very slowly. Operations that are completed quickly, abrupt modifications of operating conditions, and rapid changes of momentum at interfaces may not conform to the Terzaghi equilibrium principle. Tsai (1986) showed that the equilibrium hypothesis leads to false results when applied to filtrations involving step changes in applied pressure.

The stress equations do not include interparticle dynamic friction. It is known (Tiller and Lu, 1972) that static friction is of great importance. As solid velocities are finite during compression, dynamic friction also requires consideration in the basic differential equation. The precise form in which friction should be incorporated will be considered in future investigations.

Particle Mechanics Applied to Cakes and Sediment. Cakes and sediments are simply beds of particles. At a scale comparable to particle or aggregate dimension, stress transmission takes place at points of contact. Continuum mechanics neglects particle-to-particle interaction and thereby results in loss of information. Yeh (1986) developed a particulate model of an incompressible bed and studied the patterns of stress distribution. His numerical solutions led to results which are at odds with continuum theory but can be harmonized with experiments carried out by Risbud (1974) on stress distribution in a compression-permeability cell.

Based on the results of these investigations, we believe that further theoretical and experimental research is justified. It is possible that substantial changes in basic theory would result. Design of experiments to prove or disprove the mathematical results obtained from particulate models is a crucial element of the research. When time permits, attention will be first directed primarily at the theoretical side of the investigation. However, in the future, we plan to construct a cell which will enable us to determine the distribution of stress at the cell boundaries.

PUBLICATIONS

1996

1. Tiller, F.M. and N.B. Hsyung, "Theory of Filtration of Ceramics: II Slip Casting on Radial Surfaces," in press, J. Amer. Ceram. Soc. (1990).
2. Tiller, F.M. and A. Yelshin, "Optimizing Candle Filters for Incompressible Cakes," *Filtration and Separation*, **26**, 436 (1990).
3. Tiller, F.M., Y.S. Shen, and A. Adin, "Capillary Suction Theory for Rectangular Cells," *J. WPCF*, **62**, 130 (1990).
4. Tiller, F.M. and C.S. Yeh, "Selecting the Right Centrifugal Pump for Pressure Filtration," *Filtration and Separation*, **27**, 48 (1990).
5. Tiller, F.M. and C.S. Yeh, "Relative Liquid Removal in Filtration and Expression," *Filtration and Separation*, **27**, 129 (1990).
6. Tiller, F.M., "Interpretation of Filtration Data, I," *Fluid/Particle Sep. J.*, **3**, 85 (1990).
7. Tiller, F.M., "Interpretation of Filtration Data, II, Pilot Plant Filtration of Cottonseed Oil," *Fluid/Particle Sep. J.*, **3**, 157 (1990).
8. Tiller, F.M., N.B. Hsyung, Y.L. Shen, and W. Chen, "CATSCAN Analysis of Sedimentation and Constant-Pressure Filtration," *Proc. Fifth World Filtration Congress, Vol. 2*, Societ Francaise de Filtration, p. 80 (1990).
9. Tiller, F.M., N.B. Hsyung and N.L. Coffelt, "CATSCAN Analyses of Sedimentation," *Advances in Filtration and Separation Technology*, Amer. Filtration Soc., **1**, 447 (1990).
10. Tiller, F.M., N.B. Hsyung, and Y.L. Shen, "Cycle Optimization Involving the Use of Filter Aids," *Advances in Fil. and Sep. Tech.*, **1**, 233 (1990).
11. Tiller, F.M., N.B. Hsyung, and G. Tsai, "Centrifugal Filtration of Compressible Cakes," *Advances in Fil. and Sep. Tech.*, Amer. Fil. Soc., **1**, 456 (1990).
12. Tiller, F.M. and N.B. Hsyung, "Comparison of Compacted Cakes in Sedimenting and Filtering Centrifuges," *Advances in Fil. and Sep. Tech.*, **2**, 242 (1990).
13. Tiller, F.M. and N.B. Hsyung, "Relative Performance of Filters and Centrifuges with Respect to Average Cake Porosity," *Advances in Fil. and Sep. Tech.*, **3** (1990).

GRADUATE STUDENT PUBLICATIONS

14. Tarng, David, "Methodology for Investigating Permeability and Porosity of Sediments Encountered in Thickening," *Advances in Fil. and Sep.*, **3** (1990).
15. Thoppay, V., "Fluidization of Compactible Beds," *Advances in Fil. and Sep. Tech.*, **3** (1990).

1991-92

16. Tiller, F.M., and N. B. Hsyung, "Transient Behavior in Filtering Centrifuges," *Advances in Fil. and Sep. Tech.*, **4**, 223 (1991).
17. Tiller, F.M., and N.B. Hsyung, "Compaction of Filter Cakes," *Advances in Fil. and Sep. Tech.*, in press, **5** (1992).
18. Tiller, F.M. "From Pipe to Porous Media Parameters," *Fluid/Particle Sep. J.*, **4**, 139 (1991).
19. Tiller, F.M., and W. Chen, "Analysis of Continuous Thickeners Based on Compression Zone Behavior," *Advances in Fil. and Sep. Tech.*, **4**, 97 (1991).
20. Tiller, F.M., Z.C. Cong, and N.B. Hsyung, "New Rotary Laboratory Filter," *adv. in Fil. and Sep. Tech.*, in press, **5** (1992).
21. Tiller, F.M., and David Tarng, "Generalized Approach to Design of Continuous Thickeners," *Advances in Fil. and Sep. Tech.*, in press, **5** (1992).
22. Tiller, F.M., J.M. Kirby, and H.L. Nguyen, "An Approximate Theory for Radial Filtration/Consolidation," submitted for publication to ASCE (1992).
23. Tiller, F.M. and N.B. Hsyung, "Unifying the Theory of Thickening, Filtration, and Centrifugation," in press, *IAWPRC* (1992).

LITERATURE CITED

24. Tiller, F.M., and W.M. Lu, "The Role of Porosity in Filtration VIII: Cake Non-Uniformity in Compression Permeability Cells," *AIChE Journal*, **8**, 569 (1972).
25. Tiller, F.M., C.S. Yeh, C.D. Tsai, and W. Chen, "Generalized Approach to Thickening, Filtration, and Centrifugation," *Filtration and Separation*, **23**, 121 (1987).
26. Tiller, F.M. and C.S. Yeh, "The Role of Porosity in Filtration Part XI: Filtration Followed by Expression," *AIChE Journal*, **33**, 1241 (1987).
27. Tsai, C.D., "The Compressibility of Cakes and Sediments," Ph.D. Dissertation, University of Houston, Houston, TX (1986).
28. Yeh, S.H., "Cake Deliquoring and Radial Filtration," Ph.D. Dissertation, University of Houston, Houston, TX (1985).

END

**DATE
FILMED
8 / 10 / 92**