AIM

Association for Information and Image Management

1100 Wayne Avenue, Suite 1100
Silver Spring, Maryland 20910
301/587-8202

Centimeter

Inches

MANUFACTURED TO AIM STANDARDS
BY APPLIED IMAGE, INC.

O

TECHNICAL REPORT

December 1, 1993 through February 28, 1994

Project Title: **DEVELOPMENT OF A USE FOR ILLINOIS COAL
CONCENTRATES FOR SLURRY FED GASIFIERS**

Doe Grant No: DE-FC22-92PC92521 (Year 2)
ICCI Project No: 93-1/1.1A-3M
Principal Investigator: Latif A Khan, ISGS
Other Investigators: John M. Lytle, Saleem Khan, and
Mahmoud At-Taras, ISGS and Henry P.
Ehrlinger III, Consultant
Project Manager: Daniel D. Banerjee, ICCI

ABSTRACT

The purpose of this project is to test concentrates made from preparation plant fines as to their amenability as feed for slurry fed, slagging, entrained-flow gasifiers. The high sulfur content and high BTU value of Illinois coals are advantageous in such gasifiers. Elemental sulfur is recovered as a revenue producing product in gasifier technologies, and the higher BTU Illinois coal concentrate requires less water to produce a pumpable slurry than western coal (30-35% vs 45%) thereby reducing the amount of heat lost in the vaporization of water. This means that 66 tons of Illinois coal concentrate, containing 13,000 BTU per pound, at 70% solids would provide as much net heat as 100 tons of 9500 BTU coal pumped at 54% solids.

During the current reporting period, waste slurry samples were obtained from the washing plants associated with surface mining, underground mining from which the fines are not treated, underground mining from which a flotation concentrate is made from the washer plant waste fines, and from a tailing pile associated with one of the washing plants which had been deposited for over five years. Column flotation testing was conducted on representative samples of several of these. Using a typical flotation reagent requirement of kerosene and MIBC several tests showed outstanding results when the feed rate was kept at the nominal rate of 10 pounds per hour as suggested by the Deister Concentrator Company. The most encouraging test was conducted on waste fines from the surface plant. While the ash content in the clean coal concentrate was higher than expected, the calorific content in the tailing was 422 BTU/pound, which was at least twice as low as any tailings produced either in the laboratory or in plants during the last ten years of coal flotation research. In this same test 96.9% of the BTU's were concentrated in the flotation product and 80.3% of the ash reported in the flotation tailing. Flotation results of the material which had been impounded for an extended period were encouraging as 67.7% of the BTU's were concentrated in a product which contained 12,762 BTU/ pound.

U.S. DOE patent clearance is not required prior to publication of this document.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

for MASTER

EXECUTIVE SUMMARY

The coal industry of Illinois discards a significant amount of coal as fines from washing plants. A small amount is recovered in three flotation plants and several fine-size gravity separation plants which treat washing plant waste. An estimate is that about 4,000,000 tons of recoverable coal is being impounded as waste per year from the thirty existing washing plants. This coal when concentrated by gravity and/or flotation approaches the size and chemical requirements for gasification.

The gasification of coal slurry is a technology which has been proven to be scientifically and environmentally effective. Integrated gasification -combined cycle (IGCC) plants have the capability to achieve heat rates as low as 8200 BTU/KWH (42% efficient). Additionally, IGCC plants are largely waste free. The products are medium BTU clean gas, steam, inert granulated slag, and elemental sulfur. The slag and sulfur are marketable, the slag has been examined by a number of State Highway Departments and found acceptable for highway base use, while the sulfur is sold for about \$67.00 per ton in the midwest, and up to \$115 per ton in the Florida market area. Illinois coal meets all of the desirable characteristics needed for gasification: first, it can be concentrated to a grade higher than 13,000 BTU/lb as compared to about 9500 BTU/lb for western coal; second, it can be densified to over 70% solids and remain pumpable as compared to about 55% for western coals; third, the sulfur is a marketable product in a gasifier rather than a penalty as when Illinois coal is utilized in conventional coal fired power generation, and fourth, it is partially ground to plant specifications when it is delivered to the IGCC plant.

With these opportunities and advantages Illinois coal has over western coal it was suggested that these opportunities be developed toward commercial usage. During the first, and this second reporting period samples have been obtained from the washing plant wastes from coal from underground mines, both No 5 and No. 6 seams, from a surface mine, and from an old tailings pond which had been in place for more than five years. Tests have been made on some of these, and without exception, concentrate grades in excess of 12,000 BTU/lb are the standard. On several occasions grades in excess of 13,000 BTU/lb have been made. The recovery of BTU's has varied from the mid 50% range to over 96%, and the rejection of ash has been in the mid to high 80% range.

Reported in this quarterly report are the results of typical tests made by the flotation of the fines from the waste streams from washing plants treating coal which was provided by surface mining and from the fine fraction of tailings which had been impounded for an extended period.

OBJECTIVES

The goals and objectives of this project are to have coal from Illinois washing plant waste streams used for gasifier feed for power generation. To do so, this project will utilize waste products from real plant waste streams from a variety of sources to develop a series of examples of concentrates which have low ash content, high BTU content, and sulfur which will be saleable when the coal is used for power generation using IGCC technology.

The coal industry of Illinois discards a significant amount of coal as fines from washing plants. A small amount is recovered in three flotation plants and several fine sized gravity separation plants which treat washing plant waste. An estimate is that about 4,000,000 tons of recoverable coal is being impounded as waste per year in Illinois. This coal when concentrated by gravity and/or flotation approaches the size and chemical requirements for slurry-fed, slagging, entrained-flow gasification. There are presently enough coal fines mined and discarded in Illinois annually to provide fuel for a 2400MW power plant. This is much larger than any existing power plant in the state.

Samples of coal concentrates generated from several different plant sources will be made and given a gasification amenability review to determine their acceptability as gasifier feed. In addition to current plant wastes, at least one sample of impounded waste will be examined under the same criteria.

Additionally, several of these concentrate samples will be tested for their potential as pumpable coal slurry. Earlier work indicated that existing pipeline technology had every reason to be a transportation method of choice.

This work at this time has a very important impact on the Illinois Coal Industry. Because of the recently legislated Clean Air Act, many of the markets for Illinois high-BTU, high-sulfur coal are in jeopardy. Three alternatives are available to users of coal to meet the mandated sulfur to energy ratios. First, substitute low BTU western coal for Illinois coal; this can be done either by total substitution, or by blending to a desired endpoint. Second, install scrubbers in any of their many forms, or lastly, adapt power plants to take advantage of the high BTU, high-sulfur feedstock available with Illinois coal. Illinois coal has ideal properties for integrated gasification combined cycle plants which produce power at about 25% higher efficiency than conventionally fired power plants, and produce no appreciable solid, liquid or gaseous pollutants.

INTRODUCTION AND BACKGROUND

The gasification of coal slurry is a technology which has been proven to be scientifically and environmentally effective. Integrated gasification combined cycle (IGCC) power plants have the capability to achieve heat rates as low as 8200 BTU/KWH (42% efficiency); this is compared to 10,300 BTU/KWH for conventional coal fired generation (33% efficiency).

Additionally, the IGCC plants are virtually waste free: the products are medium BTU clean gas, steam, inert granulated slag, and elemental sulfur. The slag and the sulfur are marketable, the sulfur at about \$115 per ton, and the granulated slag has been appraised by several different state Departments of Transportation and found to be acceptable road construction material. A pulverized coal plant generates steam, slag in some form and either SO_2 or NO_x gasses or scrubber sludge, neither of which is desirable. Destec Energy, Inc of Plaquemine, LA and Texaco's Cool Water plants have used several coals to prove their technologies, and both have used Illinois coals on controlled runs.

During the 1991-1992 contract year (with ICCI) the Illinois State Geological Survey contracted to study **Gasifier Feed, Tailor-made from Illinois Coal**. During the first two quarters products were made from Illinois coals in which the heat rate was reduced to 8490 BTU/KWH on real samples generated at Kerr-McGee's Galatia plant, a marked improvement when compared to either washed Illinois coal or western coal. The products from plant testing were submitted to Williams Technologies Slurry Pumping Test Facility in Flagstaff, AZ and found to be amenable to long distance pumping at high densities without additives.

EXPERIMENTAL PROCEDURES

Material for the testing program in this reporting period was obtained from two mines in Illinois. The first was a slurry of plant effluent from an operating plant which does not use any flotation process. The fines were collected in the field, returned to Champaign, screened on 65 mesh to remove the oversized material, then stored for use. The second sample was collected from an old tailings pond. The material had never been through a flotation circuit, thus had no flotation reagent associated with it. It is as near representative as the operators could suggest, and had been placed in the pond for longer than five years. This material was removed to Champaign, slurried and screened on the 65 mesh screen for oversize removal.

The procedure was to acquire representative samples of the slurries described above, transfer them to a mix tank, adjust the solids to a range of 6% to 8%, then set the flotation feed

rate in appropriate gallons per minute to deliver 10 pounds of dry solids per hour, the nominal feed rate for the Deister Laboratory Continuous Flow Flotation Column. The reagent feed rates to match the feed rate were calculated and started, then the feed was turned into the column. Every effort has been made on all tests to assure that steady state conditions were reached before any sampling was started. For the purpose of this work steady state has been reached when at least six volume changes of slurry have been fed into the column without a feed, tailing, air rate, or reagent rate change. This is normally a little over an hour.

MATERIAL BALANCES ON TYPICAL TESTS

Below we show material balances on several typical tests which were completed during this reporting period. These are three of quite a number of tests, but they represent a flavor for the grades and recoveries that were encountered while we were testing the waste streams from the washing plant fed by the coal from a surface mine, and from the long term tailings storage from an underground mine:

Test A

Source: Washing Plant Waste from Surface Mining

Prod	% Wt	A N A L Y S E S				DISTRIBUTION		
						Ash	T/S	BTU
T/S	BTU							
Feed	100.00	52.60	2.71	6373		100.0	100.0	100.0
Conct	53.28	19.71	2.84	11488		20.0	55.7	96.0
Tails	46.72	90.11	2.56	540		80.0	44.3	4.0

Conditions: Feed Rate, 10 pounds dry weight per hour
 Percent Solids: 7.1%, Kerosene 1.5#/ton, MIBC
 1.5#/ton
 pH 7.4

Test B

Source: Washing Plant Waste from Surface Mining

Prod	% Wt	A N A L Y S E S			DISTRIBUTION		
		Ash	T/S	BTU	Ash	T/S	BTU
Feed	100.00	52.65	2.56	6392	100.0	100.0	100.0
Conct	53.41	19.39	2.76	11599	19.7	57.4	96.9
Tails	46.59	90.76	2.33	422	80.3	42.6	3.1

Conditions: Feed rate, 10 pounds dry weight per hour
 Percent Solids: 6.9, Kerosene 1.5#/ton, MIBC
 1.5#/ton
 pH 7.45

Test C

Source: Washing plant waste from underground mine, from tailings pond

<u>Prod</u>	<u>% Wt</u>	<u>A N A L Y S E S</u>			<u>DISTRIBUTION</u>		
		Ash	T/S	BTU	Ash	T/S	BTU
Feed	100.00	37.50	3.22	8593	100.0	100.0	100.0
Conct	45.59	11.03	3.64	12762	13.4	51.6	67.7
Tails	54.41	59.56	2.87	5100	86.6	48.4	32.3

Conditions: Feed rate, 10 pounds dry weight per hour
Percent Solids: 6.3, Kerosene, 1.5#/ton; MIBC
1.5#/ton
pH 7.3

DISCUSSION

There were several unique features which are pointed out from the results above. From the material from the surface mine, the next test will utilize a dispersant, probably sodium silicate. This should let us maintain the same high recovery of energy matter(BTU's) yet lower the ash analyses of the concentrate. Nothing will be done to change the conditions which produced a tailing in the 500 BTU range. An analysis of this magnitude is lower than any reported work that has been conducted or reviewed be coal beneficiation practice. These tests should be completed in time for the May report.

The material from the tailing pond will be treated with both a dispersant and a higher quantity of collector. The surface of the coal particles in this feed product is apparently more oxidized than that from the recently mined material, thus a slower feed rate will be tested on this material to determine if a greater recovery can be made without sacrifice of grade in an effort to improve recovery of the BTU's.

Considering that the feeds to each of the flotation tests above was considered a waste product at the plant; we feel that we have made considerable strides in producing concentrates of value with low cost procedures. It is apparent that these early tests have not maximized the economic potential of these products, but have certainly shown that there is an opportunity to produce a valuable gasifier feed from Illinois Coal.

PROJECT MANAGEMENT REPORT
December 1, 1993 through February 28, 1994

Project Title: **DEVELOPMENT OF A USE FOR ILLINOIS COAL
CONCENTRATES FOR SLURRY FED GASIFIERS**

DOE Grant No: DE-FC22-92PC92521 (Year 2)
ICCI Project No: 93-1/1.1A-3M
Principal Investigator: Latif A. Khan, ISGS
Other Investigators: John M. Lytle, Saleem Khan, and
 Mahmood At-Taras, ISGS, and Henry P.
 Ehrlinger III, Consultant
Project Manager: Daniel D. Banerjee, ICCI

COMMENTS

Second Quarter costs are significantly below the original budget as a number of items are shown as obligation, but not as expended.

SCHEDULE OF PROJECT MILESTONES

Milestones:

- A. Testing using coal from waste streams (Task 1)
- B. Testing using coal from impounded waste (Task 2)
- C. Pumpability analyses of selected samples (Task 3)
- D. Combustion testing of selected products (Task 4)
- E. Select plant conditions (Task 5)
- F. Report at Annual Contractors Meeting
- G. Technical project management reports prepared and submitted

Financial Plan

A summary of total estimated project costs by major tasks is shown in the following table. Costs of safety, quality control, and report preparation are distributed into the research tables.

Tasks	ICDB Funding
1	31.235
2	31.235
3	9.187
4	5.000
5	19.265
Total	96.323

EXPENDITURES - EXHIBIT B

Projected and Estimated Actual Expenditures by Quarter

Quarter*	Types of Cost	Direct Labor	Materials and Supplies	Travel	Major Equipment	Other Direct Costs	Indirect Costs	Total
Sept. 1, 1993 to Nov. 30, 1993	Est. Actual	3,675	99	0	0	826	460	5,060
	Projected	6,746	750	1,326	0	12,598	2,142	23,562
Sept. 1, 1993 to Feb. 28, 1994	Est. Actual	7,995	1,417	1,581	0	10,362	2,134	23,489
	Projected	13,492	1,500	2,652	1,950	25,196	4,479	49,269
Sept. 1, 1993 to May 31, 1994	Est. Actual							
	Projected	20,238	2,250	3,798	1,950	37,794	6,603	72,633
Sept. 1, 1993 to Aug. 31, 1994	Est. Actual							
	Projected	26,984	3,000	5,304	1,950	50,392	8,763	96,393

* Cumulative by quarter

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

COSTS BY QUARTER - EXHIBIT C
DEVELOPMENT OF A USE FOR ILLINOIS COAL
CONCENTRATES FOR SLURRY FED GASIFIERS

○ Projected Expenditures
△ Actual Expenditures 23,489

Total ICCI Award \$96,393

DATE

FILMED

6/22/94

END