AIM

Association for Information and Image Management

1100 Wayne Avenue, Suite 1100
Silver Spring, Maryland 20910

301/587-8202

Centimeter

Inches

MANUFACTURED TO AIM STANDARDS
BY APPLIED IMAGE, INC.

1 of 1

HANFORD CODE C65

DOCUMENT NO.

REF-76942 RCD

SERIES AND COPY NO.

DATE

APR 14 1963

(CLASSIFICATION)

GENERAL ELECTRIC

DECLASSIFIED

HANFORD ATOMIC PRODUCTS OPERATION - RICHLAND, WASHINGTON

THIS DOCUMENT CONTAINS RESTRICTED DATA AS
DEFINED BY THE ATOMIC ENERGY ACT OF 1954
ITS SUBMITTAL FOR DISCLOSURE TO
OTHERS IN ANY MANNER THAN AUTHORIZED
HEREIN IS PROHIBITED.

TITLE

CFD'S POTENTIAL FOR PROCESSING THE NUMBER TRANSFORMANCE

OTHER OFFICIAL CLASSIFIED INFORMATION

THIS MATERIAL CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING OF THE ESPIONAGE LAWS, TITLE 18, U. S. C., SECS. 793 AND 794, THE TRANSMISSION OR REVELATION OF WHICH IN ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW.

AUTHOR

R. E. Fertilizer

CIRCULATING COPY
RECEIVED 300 AREA

MAR 14 1963

RETURN TO

TECHNICAL INFORMATION FILES

THIS DOCUMENT IS NOT TO BE LEFT ATTENDED WHERE ANY AUTHORITY OR PERSON MAY HAVE ACCESS TO IT. IT IS NOT TO BE STORED IN ANY PLACE WHERE IT MAY BE EXPOSED TO FIRE OR IN AN UNSECURED AREA. WHILE IT IS IN POSSESSION AND WHILE YOU ARE ESTABLISHING A SIGNATURE FOR IT, IT IS YOUR RESPONSIBILITY TO KEEP IT AND ITS CONTENTS WITHIN THE LIMITS OF THE SUBJECT MATTER FROM WHICH IT WAS REQUESTED. ANSWERS TO AND REAGERS OF YOUR PAGE OR RESPONSES TO WHICH IT IS NOT TO BE DUPLICATED IF ADDITIONAL REAGERS ARE NEEDED, OR FROM THE REAGERS' FILE. ALL PERSONS READING THIS DOCUMENT ARE REQUESTED TO SIGN THE SPACE PROVIDED BELOW.

ROUTE TO:

PAYROLL NO.

LOCATION

FILE	ROUTE	DATE
100-443888-100	100-443888-100	100-443888-100

SIGNATURE AND DATE

~~P.R. McHenry~~
~~B. J. Jackson~~
~~P.R. McHenry~~

979

202 A

3-14-63

~~10/11~~

(CLASSIFICATION)

DECLASSIFIED

HE-76942 RD

This document consists of
9 pages. No. 6 of
10 copies.

Distribution:

1. L. E. Butler
2. L. W. Long
3. J. H. Warren - V. R. Chapman
4. W. S. Frank
5. R. E. Tomlinson
6. P. R. McHurray - R. F. Jackson
7. H. E. Hanson - R. E. Imeson
8. K. G. Grim - J. E. McDonald
9. 300 Files
10. Record File

Classification Cancelled and Changed To

DECLASSIFIED

By Authority of DS Lewis

CG-PR-2, 3-18-94

By DK Hanson, 4-17-94

Verified By J. E. Savelly
4-18-94

CFD's POTENTIAL FOR PROCESSING
THE KLEIN TRANSDUCER

R. E. Tomlinson

Advanced Technical Planning
Research and Engineering Operations
Chemical Processing Department

March 14, 1963

HAMPDEN ATOMIC PRODUCTS OPERATION
RICHLAND, WASHINGTON

This document contains restricted information as defined in the Atomic Energy Act of 1954. Its transmission and disclosure of its contents in any manner to unauthorized persons is prohibited.

MASTER

DECLASSIFIED

875

**CFD's POTENTIAL FOR PROCESSING
THE HIGHLY TRANSURANIC**

1. Introduction

During the past several months, Linton Lang and others have been evaluating Hanford's potential for producing higher transuranic isotopes, particularly curium-242 and curium-244. This document outlines the concepts as currently visualized by Mr. Lang, and estimates the potential impact on CFD's development, construction, and production program.

As currently visualized, the irradiation program would proceed in three distinct steps, each of which is dependent on the availability of new fuel types, safety reviews, and other approvals. The timing indicated in the subsequent discussion assumes that all such approvals and technologies are available without delay. The E Reactor is not specifically included in this plan and is assumed to proceed as currently planned; however, it would appear that the New Production Reactor could easily participate in this program, particularly in Step 1. All reactors except E are assumed to continue the use of aluminum cladding on all fuels under this program.

2. Step 1

Fuel-grade plutonium (17 percent Pu-240) would be produced in addition to continued production of weapons-grade plutonium at about 75 percent of the current rates.

2.1 Irradiation Pattern - All reactors (except NWR) would be loaded in an E - B pattern. The E-metal (0.94 percent U-235) would be present in about four times the quantity of B-metal (about 0.23 percent U-235). The E-metal would be irradiated about three months to produce weapons-grade plutonium. The B-metal would be irradiated about three months to produce non-representative plutonium (about 8 percent Pu-240), or about ten months to produce fuel-grade plutonium (about 17 percent Pu-240).

2.2 Timing - Assuming all reviews and approvals are obtained without delay, the first reactor would be loaded in this pattern about January 1964; all reactors would be loaded in this pattern by January 1965.

DECLASSIFIED

-3-

2.3 Impact on CFB - During the one-year period starting July 1964, CFB's processing load would undergo a gradual transition from about 6000 tons of natural uranium plus 1800 tons of B-metal to no natural uranium, 6000 tons of B-metal, and 500 to 1500 tons of B-metal per year. If a large demand for non-representative plutonium (8 percent Pu-240) develops, the B-metal could be pushed after three months irradiation to meet this demand. In this case, up to 1500 tons of B-metal would be processed per year, and no higher isotopes would be produced to feed Steps 2 and 3. If no non-representative plutonium were produced, the B-metal would be irradiated about ten months. In this case, B-metal would be processed at about 500 tons per year to recover about 800 kgs of plutonium containing 17 percent Pu-240. In either case, the B-metal would produce weapons-grade plutonium at about 75 percent of current rates. The subsequent discussion assumes that all of the B-metal is exposed ten months to produce the 17 percent -240 material.

2.4 Changes Required in CFB - No new technology would be required. The Pusan Plant would have to be equipped with multipurpose dissolvers by the second quarter of FY 1965, at which time the total production load could probably be processed at Pusan (including projected RPH and PPH loads). The dissolver installation is not now budgeted to meet this schedule. On a normal schedule, the dissolvers would cost about \$1,500,000 and could be available by the last quarter of FY 1965. If the units are needed by the second quarter, additional costs of about \$100,000 would be incurred.

3. Step 2

The fuel-grade plutonium produced in Step 1 would be burned to the higher isotopes. The plutonium would be alloyed with aluminum and used in place of B-metal as the driver in one of the old reactors. The plutonium would be irradiated eighteen months at which time half the original plutonium would have been burned, and the residue would have an optimum content of Pu-241. At equilibrium, 400 kilograms of plutonium would be produced per year, having the composition

80 percent	Pu-239
50 "	Pu-240
20 "	Pu-241
2 "	Pu-242

The fuel types are under consideration and are discussed as alternatives.

3.1 The Separate Driver Fuel - A Pu-Al slug (P-metal) would be analogous to the U-Al J slug and would have dimensions similar to those of current fuels. The technology of fuel fabrication and the physics of irradiation are straightforward, but the safety aspects of reactor operation must be studied further.

DECLASSIFIED

An estimated one-half million dollars would be required for approved...
Capital requirements are estimated at one million dollars for a...
Aluminum, one-half million dollars for the design of aluminum...
existing and one hundred thousand dollars for a 1-year work.

With tests...
processing of 1-year in addition to the step 1 tests plus the...
Baker Plant. It is expected that the Baker Plant would accept the...
The plant could be located and constructed in the...
with the existing plant. Assuming adequate financing and energy...
plant, requiring 20,000 gallons of hot water and 100,000 gallons of...
About 100,000 gallons of the kind water would be generated per...
of depleted uranium solution to make it suitable for storage...
The aluminum solution would be mixed with about 20 ton equivalents...
1-year by an acid solution in a specially-made 10-ton aluminum...
1- and 2-year processing. The concept involves the elimination of...
been projected to handle the 1-year in a manner compatible with...
due to the technology of present technology, a process scheme has

and through the Baker Plant...
to the point that an entire year would be required to process the...
stringent critical mass requirements limit the aluminum throughput...
solid-state aluminum processing is essentially feasible; however...
production. A complete elimination followed by solid-state...
solution, cannot be used for highly irradiated alloys because of...
aluminum alloys, which is a necessary-irradiated alloy sold etc...
high burn up. The method presently used for this production...
to process the aluminum-alloys alloys because of the inability...
3.1.3 Aluminum Required in CPD - The technology would be required

800 lbs per year, as in Step 1...
cool, and fast-grade aluminum would be produced at rates up to...
grade aluminum to about 65 to 70 percent of current rates would...
aluminum in the 1-year stage. A decreased production of uranium...
1-year, and 400 lbs of aluminum associated with 17,000 lbs of...
lead would consist of 200 tons of 1-year, 1000 + 500 tons of...
CPD in CPD's processing lead would occur. At equilibrium, the...
3.1.2 Impact on CPD - As the 1-year becomes available, a slight

ready for processing in quantity around October 1966...
After six months cooling, the first irradiated fuel would be...
portion of uranium was found to have satisfactory incentive...
grade aluminum could be used in initial tests if early pro-...
increasing quantities, starting in July 1964, although uranium...
3.1.1 Timing - Fast-grade aluminum would be available in

-3-

Alternatively, the P-metal might be processed in the Strontium Separators after suitable modifications; the capital requirements would be about the same as for Redox, and the operating costs considerably less, but the operating reliability would be low because of its contact maintenance requirements.

3.2 The "Wrap-Around" Driver Fuel - A slug consisting of a Fe-Al alloy cylinder surrounding a depleted uranium core and clad in a conventional aluminum jacket might be used in the plutonium burner. The technology of fabrication and reprocessing would have to be developed. The irradiation characteristics of this slug design are advantageous enough to make it a strong candidate for the program.

3.2.1 Timing - The timing would be the same as discussed in 3.1.1; however, there is a greater chance of delay in the program for the "Wrap-Around" slug because of the development work required.

3.2.2 Impact on GFD - The processing load for GFD would be the same as discussed in 3.1.2, except for some decrease in the weight of aluminum in the alloy processed. The weight of aluminum associated with 400 kgs of plutonium per year would probably be about 10,000 kgs, but could approach the 17,000 kgs estimated for the alloy slugs, depending on the "Wrap-Around" slug design.

3.2.3 Changes Required in GFD - New technology would be required for processing the "Wrap-Around" P-metal slugs for the same reasons indicated for the separate driver slugs. However, a somewhat more complex processing scheme is required because of the presence of depleted uranium core. The jackets and Fe-Al alloy can be removed simultaneously but must be separated from the core to avoid mixing the 50 percent plutonium-240 in the alloy with fuel-grade plutonium in the core.

The processing scheme projected for the "Wrap-Around" slugs would use the currently available caustic dissolution - nitric acid acidification process developed at SEP. However, a continuous, critically-safe dissolver would be required in which the aluminum jackets and Fe-Al alloy could be removed continuously with caustic and the uranium cores could be recovered intact. The cores would then be dissolved with regular D-metal in the existing Redox or Parox dissolvers.

Approximately \$750,000 would be needed for a three-year development program on the rather complex continuous dissolver system and the demonstration of the flow sheet. Capital requirements are estimated at two million dollars for a dissolver-centrifuge complex; one-half million dollars for 50,000 gallons lag storage capacity; and one-hundred thousand dollars for a P-metal cask.

DECLASSIFIED

-7-

for a Ce-La separation facility would be about eight million dollars if the chloride solvent extraction process were to be used, or perhaps one to two million dollars if the ion-exchange process were successfully developed.

6. Alternative Production of Ce-244

An alternative plan to produce Ce-244 has been proposed and is being evaluated. Based on the preliminary information available, the potential impact on CSD is outlined below.

6.1 Irradiation Pattern - About 400 tons of depleted uranium would be clad as UO₂ in high-integrity jackets - perhaps zirconium. These elements would be irradiated in an E - D loading similar to that described in Step 1, section 2.1. The oxide elements would be irradiated two to three years.

6.2 Timing - The reactors might be loaded with the E - D oxide fuels during calendar year 1964. The entire depleted load might be discharged sometime during 1966 and would be available for processing about four months later.

6.3 Processing Pattern - The fuels could be processed in the Redox Plant - or Purex if the cladding were compatible with the dissolver equipment in place at that time. The plutonium, uranium, and neptunium could be recovered by the normal process. The uranium and neptunium could be reduced to oxides and decontaminated nitrate solution for dispatch by normal routes. The plutonium could be made available for exchange to the reactors to assist in the production of more curium-244.

The aqueous solvent extraction waste could be routed to B-Plant for extraction of the rare earths in the solvent extraction equipment. The separated rare earths (which should include the americium and curium) would be available for curium isolation and decontamination. The chromatographic ion-exchange process would be used to isolate curium if the process is successfully developed.

6.4 Estimated Costs - About \$750,000 is estimated to be required to develop the chromatographic (ion-exchange) ion-exchange process over a three-year period.

An estimated one to two million dollars would be required to install the chromatographic ion-exchange equipment, assuming the process is successfully developed. If current technology must be used, about eight million dollars would be required to construct the chloride solvent extraction facilities.

DECLASSIFIED

[REDACTED]

Step 1	Step 2	Step 3	Step 4
1 - 68	9 - 68	1 - 68	1 - 68
-	9 - 69	6 - 68	1 - 68
1 - 69	9 - 66	6 - 69	1 - 69
-	3 - 67	3 - 69	-
1 - 69	3 - 66	3 - 68	1 - 69
-	9 - 69	1 - 69	-
1 - 68	9 - 68	1 - 68	1 - 68

TABLE II

Step 1	Step 2	Step 3	Step 4	Step 5	Step 6
6000	1800	195	1000 ± 500	11.0 AT	0.1 IN
5400	1800	195	1000 ± 500	10.0 AT	0.1 IN
5400	1800	195	1000 ± 500	11.0 AT	0.1 IN

TABLE I

TABLE I

- 2 -

[REDACTED]

-9-

TABLE XII

ESTIMATED COSTS

	<u>Item</u>	<u>Capital \$ x 10⁻⁶</u>	<u>R & D</u>	
			<u>Years</u>	<u>\$ x 10⁻⁶</u>
Step 1	Perox Dissolvers	1.5	-	-
Step 2A	HFF Dissolver	1.0	2	0.5
	Log Storage	0.5	-	-
	Cask	1.0	-	-
Step 2B	Continuous Dissolver	2.0	2	0.75
	Log Storage	0.5	-	-
	Cask	0.1	-	-
Step 3	Pu Storage	0.4	-	-
	Au Isolation	-	2	0.25
	Au-Cu Separation	1 - 8	3	0.75

DECLASSIFIED

DATE
FILMED

8/2/94

END