BNL-47158
INFORMAL REPORT

HYDROPYROLYSIS OF BIOMASS

ATSUSHI KOBAYASHI AND MEYER STEINBERG

JANUARY 1992

DEPARTMENT OF APPLIED SCIENCE

BROOKHAVEN NATIONAL LABORATORY
UPTON, LONG ISLAND, NEW YORK 11753

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Department of Energy, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

HYDROLYSIS OF BIOMASS

Atsushi Kobayashi and Meyer Steinberg
Brookhaven National Laboratory
Upton, NY 11973

January 1992

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

UNDER CONTRACT TO THE U.S. ENVIRONMENTAL PROTECTION AGENCY
OFFICE OF RESEARCH AND DEVELOPMENT
RESEARCH TRIANGLE PARK, NC 27711

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

102

Hydropyrolysis of Biomass

by

Atsushi Kobayashi and Meyer Steinberg

Brookhaven National Laboratory

Upton, New York, 11973

Abstract

The pyrolysis and hydropyrolysis of biomass was investigated. Experimental runs using the biomass (Poplar wood sawdust) were performed using a tubular reactor of dimensions 1 inch inside diameter and 8 feet long heated at a temperature of 800 C and pressures between 450 and 750 psig. At low heat-up rate the reaction proceeds in two steps. First pyrolysis takes place at temperatures of 300 to 400 C and subsequent hydropyrolysis takes place at 700 C and above. This is also confirmed by pressurized thermogravimetric analysis (PTGA). Under conditions of rapid heat-up at higher temperatures and higher hydrogen pressure gasification and hydrogasification of biomass is especially effective in producing carbon monoxide and methane. An overall conversion of 88 to 90 wt% of biomass was obtained. This value is in agreement with the previous work of flash pyrolysis and hydropyrolysis of biomass for rapid heat-up and short residence time. Initial rates of biomass conversion indicate that the rate increases significantly with increase in hydrogen pressure. At 800 C and 755 psig the initial rate of biomass conversion to gases is 0.92 l/min.

1. Introduction

The Hydrocarb Process involves two main reactions; (1)hydrogasification of the carbaceous feedstock to produce methane-rich gas, and (2)the thermal decomposition of methane to produce hydrogen-rich gas, which is recycled to the hydrogasification section, and finally produces clean carbon black as product⁽¹⁾. A third step combines the CO formed from the hydrogasification section with hydrogen and produces methanol as co-product. The hydrogasification step is important in this process because the composition and the rate of formation of the methane-rich gas can determine the performance of the methane decomposition and methanol reactors as well as the overall performance of the cyclical Hydrocarb Process.

This work was performed in order to investigate both the rate and degree of conversion for the pyrolysis and hydropyrololysis of biomass using a tubular reactor at a temperature of 800 C and at pressures of 450 to 750 psig in a hydrogen atmosphere. Data at higher loading densities of biomass compared to previous experiments were also investigated. Previous experiments were performed under flash hydropyrolysis conditions in dilute phase at low CH₄, CO, and CO₂ in the gaseous phase^(2,3).

2. Experimental Description

2.1 Biomass preparation

The biomass, essentially Poplar wood sawdust, is ground and sieved to less than 150 micron diameter. This particle size was

chosen in order that the external heat and gaseous hydrogen in the reactor could penetrate through the biomass particles easily and the biomass could be smoothly fed into the tubular reactor from the feeder attached to the top of the reactor. The ground biomass is first dried in an oven, in which the temperature is kept constant at about 100 C until the moisture content of the biomass is reduced to less than 3 wt% so that the effect of water on the rate of the hydrolysis reaction is minimized. The dried biomass component was analyzed by standard analytical procedure and the elemental analysis is shown in Table 1.

Table 1 Biomass (poplar sawdust) composition

component	wt%
C	51.32
H	6.16
N	1.18
S	0.13
O	34.57
Ash	6.64
	<hr/>
	100 (total)

A very fine silica flour (Cab-O-Sil) was mixed with the ground biomass to prevent agglomeration and allow smooth flow of the sawdust from the feeder into the reactor. This process also prevented plugging inside the reactor. The weight content of silica flour was fixed at about 20 wt% as determined from past experience^(2,3).

2.2 Experimental Procedure

Figure 1 shows the schematic flow sheet of the experimental

equipment which consists of a biomass feeder, a tubular reactor, a carbon trap, and a gas-chromatograph.

Experiments were performed under two different modes; (1) In the first mode of operation, the biomass was loaded into the reactor on top of a 2 " height of packing consisting of 1/8 " alumina balls which rests on a perforated disk made of stainless steel positioned at the bottom of the reactor. After a helium purge, hydrogen was introduced into the system up to 755 psig and heated up from room temperature 800 C by the external electrical clamshell heaters. The pressure in the reactor was monitored by a pressure gauge and the concentrations of the effluent carbon containing gases, CH_4 , C_2H_4 , C_2H_6 , CO , and CO_2 , were analyzed with the thermal conductivity detector in the on-line gas-chromatograph; (2) In the second mode of operation, the reactor temperature was raised to 800 C and the reactor was pressurized with hydrogen over the range 455 to 755 psig, and the biomass was fed into the reactor at a rate between 10 and 20 grams/min. The pressure in the reactor was monitored and the effluent gases were analyzed in the same manner as mentioned method.

The reactor was a 1 " diameter Inconel 617 tube with 1/4 " wall thickness. The total tube height was 11 feet of which 8 feet is heated externally with electrical clamshell heaters. As described earlier, it had a disk of stainless steel positioned 2 feet up from the bottom of the heated zone to act as a hold-up platform for the biomass, and 1/8 " alumina balls about 2 inch in height is also set on the disk to assist in holding the biomass

sawdust. The sawdust bed height ranges from 5 to 6 feet in the heated zone.

4. Experimental Result and Discussion

Data Table 1 and Figure 2 show the results of the experimental Run No. 1154 for the conditions of biomass and hydrogen preloaded into the reactor, system purge and heated up from room temperature to 800 C at an initial pressure of 755 psig. The temperature and the concentrations of the gases generated are plotted as a function of the run time and are shown in Figure 2. At first, CO and CO₂ gases are generated before CH₄ is formed. The volume of CO₂ generated is much larger than CO at the beginning of the run. These gases begin to form around 470 C. CH₄ also begins to generate slowly around 470 C and it rapidly increases above 700 C. This phenomena appears to indicate that pyrolysis of biomass starts around 470 C and hydrolysis starts about 700 C.

A pressure calibration run is shown in Figure 3 which indicates the pressure change in the reactor with the temperature for the above mentioned conditions. The dotted line in the figure indicates the calibration line with hydrogen pressure as the reactor is heated up in the same manner as in the run when the biomass was present. This is compared with the pressure change for the Run No. 1154 when the biomass was present as shown by the solid line. At approximately 380 C, the pressure increases sharply compared with the calibration line. The difference between solid line and dotted line indicates that a reaction has occurred in the biomass itself

or between the heated biomass and the gaseous hydrogen. As indicated by the composition of the gases generated, CO, CO₂, CH₄, and others, as shown in Figure 2, the pyrolysis of the biomass begins around 380 C. Above 400 C, there appears to be almost no change in pressure shown in Figure 3. However taking into account the data shown in Figure 2, certainly some gases are generated in that temperature range. A zero pressure change in this region would mean that there is a balance between the gases generated and the hydrogen consumed by hydrolysis. Taking this effect into account, pyrolysis and hydrolysis of the biomass can be totally represented by following two steps;

First Step : Pyrolysis of $\xrightarrow{\text{heat}}$ CO + CO₂ + H₂O
 Biomass
 at temperatures of 300 - 400 C

Second Step : Hydrolysis of
 $\xrightarrow{\quad}$ CH₄ + other
 Biomass + H₂ CH₄ hydrocarbons
 C + H₂
 (remaining char or carbon)
 at temperature above 700 C

In the first step, at the lower temperatures of 300 through 400 C pyrolysis of the biomass occurs in the early stage of the reaction to produce mainly CO and CO₂. In the subsequent step, at higher temperatures above 700 C and at elevated hydrogen pressure, CH₄ and some higher hydrocarbons are generated by hydrolysis.

In connection with this work R. Khan⁽⁴⁾ performed two pressurized thermogravimetric analyses (PTGA) for us on Poplar and Fir wood. The PTGA data are shown in Figures 4 and 5 at 400 psig in

helium (solid line) and hydrogen (dotted line) atmospheres. The hydrogen line for weight loss in Figure 4 for Poplar wood shows 3 steps. The first weight loss of about 10 wt% takes place at the temperature of 150 to 300 C, which is probably due to water vaporization from the biomass. A large second weight loss of about 55 wt% starts at approximately 300 C and continues to about 450 C. Up to 450 C, both the helium and hydrogen curves are very similar. Thus in the low temperature regime, the pyrolysis reaction in the biomass occurs independent of the atmosphere present. On the other hand, beyond this temperature region, the hydrogen atmosphere data line decreases more than the helium data line which stops losing weight at about 600 C. The third weight loss of 10 to 15 wt% is probably due to the reaction of hydrogen with the remaining carbon to produce CH_4 and other hydrocarbons. Similar results are shown in Figure 5 for Fir wood. These PTGA results are in accord with our tubular reactor experimental results.

Data Tables 2 and 3 show the results of measurements that were obtained for conditions when the biomass is gradually fed into the reactor by the feeder. The reactor was heated up to 800 C before the start of the experimental run, and the system is filled with hydrogen to pressures of 455 and 755 psig respectively. Data Table 3 showing the results of Run No. 1152 gives the measurements obtained at 800 C and 755 psig initial pressure of hydrogen, whereas Data Table 2 of Run No. 1144 was obtained at 800 C and an initial pressure of 455 psig. Table 2 shows the initial conditions of the experiments for the two runs referred to in Data Tables 2

and 3, respectively.

Table 2 Initial Condition for the Experimental runs

Exp. No.	temperature C	initial pressure psig	biomass * feed rate grams/min.	biomass * quantity grams
Data Table 2 Run NO.1144	800	455	16.9	184
Data Table 3 Run No.1152	800	755	10.1	152

* the biomass used in both runs includes 20 wt% Silica

The biomass feeding times are 11 min. for Data Table 2 and 12 min. for Data Table 3.

The total conversion of biomass to generated gases in these two runs are 88.5 wt% and 89.6 wt% respectively, based on the remaining char in the reactor at the end of the runs. These results confirm the earlier dilute phase, short residence time flash hydrolysis^(2, 3) where over 90 % conversions were obtained at 800 to 1000 C and 500 psig pressure.

The change in the number of moles of gas in the reactor during the run has been calculated from the pressure change and is graphically given in Figure 7 and 9. The calculated data include the net molar change of both the generated gases, CO, CO₂, and CH₄ and the hydrogen gas consumed. These calculated data do not accurately indicate the change of the total moles in the gas phase, because water (H₂O) formed in the gases was not measured. However the data gives some indication of the rate of the reaction. The slope of the change in numbers of moles in the reactor shown in Figure 7, increases with time more slowly than that shown in Figure

9. The reaction appears to continue for 30 min. of residence time, which is almost 20 min. after all of the biomass was fed into the reactor. On the other hand, under the condition of 755 psig of initial hydrogen atmosphere in Figure 9, it appears to stop at around 15 min, only 3 min. after completion of feeding the biomass. These results indicate that the hydrogasification is favored by higher hydrogen pressure.

Table 3 below shows the initial rate of molar change. These data were calculated by taking into account the initial molar change data in each run and dividing by the feed rate of the biomass.

Table 3 Initial rate of molar change
in the hydrolysis of wood

Exp. No.	molar change rate mol/min./gram-biomass
Data Table 2 800 C 455 psig	0.012
Data Table 3 800 C 755 psig	0.036

The initial rate of molar numbers change of Data Table 3 is 3 times as large as that of Data Table 2, even though the biomass used was smaller than in Data Table 2. This result also implies that the total pressure of gaseous hydrogen strongly affects the rate of the reaction of biomass.

The gaseous concentrations shown in Data Table 3 are also higher than those of Data Table 2; CH₄ concentrations in Data 3 are in the range between 25 and 30 vol%, whereas those in Data 2 are 16 to 20 vol%. As indicated previously, the amount of biomass fed into

the reactor in Data Table 3 is smaller than in Data Table 2. These results indicate that the higher pressure is more effective in promoting gasification and hydrogasification of biomass.

In both Data Tables 2 and 3, the average ratio of the gases generated, CO , CO_2 , and CH_4 are approximately 3 : 1 : 3. Taking this ratio, and unreacted carbon of 10 to 15 wt%, into account and performing C, H and O mass balances, the following stoichiometric overall equation for hydropyrolysis of biomass at 800 C is derived.

This equation indicates that hydrogen is generated from the biomass. However, hydrogen is necessary to enhance the formation of CH_4 . Taking the sum of the molar number, 0.82 mol/ mol-biomass, of gas generated in this equation and the initial rate of molar change cited earlier into account, the initial rate of biomass conversion to gases is determined in Table 4.

Table 4 Initial rate of the biomass conversion

Exp. No.	initial rate of biomass to gas (1 / min.)
Data Table 2 800 C 455 psig	0.31
Data Table 3 800 C 755 psig	0.92

According to the result of the initial rate from Data Table 3 at 800 C and 755 psig, approximately 92 wt% of the biomass appears to be converted to gases in one minute. For the conditions of Data Table 2 at 800 C and 455 psig, a 31 % per min. conversion rate is

obtained. The fact that an increase in pressure by a factor of 2 results in an increase in rate by a factor of 3, indicates the very strong effect of pressure on the rate.

It should be noted that a number of additional runs were made during the course of this work, but the data could not be accurately presented because of operational leaks of gases from the system during the runs.

5. Conclusion

The following conclusions are derived from this work.

(1) Biomass hydrolysis conversion of 88 through 90 wt% can be obtained at temperature up to 800 C and initial hydrogen pressure of 455 and 755 psig respectively.

(2) The initial rate of biomass conversion of 0.31 l/min. is obtained at an initial pressure of 455 psi and 800 C, and a higher value of 0.92 l/min. is obtained at the higher pressure of 755 psig and 800 C. Hydrogen pressure has a significant enhancing effect on the rate of conversion of biomass to gases.

(3) Higher temperatures, above 700 C, and rapid heat-up rate is more effective in enhancing the conversion of biomass to CH_4 and CO .

(4) At low heat-up rate the reaction appears to proceed in two steps, first pyrolysis at 300 to 400 C followed by hydrolysis as a second step at temperatures up through and exceeding 700 C.

Work performed in-part by U.S. DOE

Reference

- (1) M. Steinberg, E. W. Grohse, and Y. Tung; "A Feasibility Study for the Corprocessing of Fossil Fuels with Biomass the Hydrocarb Process", BNL46058, Brookhaven National Laboratory, Upton, New York (April, 1991)
- (2) M. Steinberg and P. Fallon: "Flash pyrolysis and hydropyrolysis of biomass " BNL 30263, Brookhaven National Laboratory, Upton NY, (October 1981)
- (3) M. S. Sundram, M. Steinberg, and P. T. Fallon; "Characterization of the Products and Comparison of the Product Yields from the Flash Pyrolysis of Fir Wood in Hydrogen and Helium", Symposium paper of Energy from Biomass and Wastes 8th, pp 1395-1416 (1984)
- (4) R. Khan, Private Communication (August 19, 1991)

Data Table 1 Experimental Data for Hydropyrolysis of Biomass

Data Table 1			Experimental Data for Hydrolysis			
Hydropyrolysis of biomass			Run No. 1154			
November 26 1991			14: 30 - 17: 00			
Preloaded biomass is heated up in the closed system						
Wood 130 gram preloaded including SiO2 26 grams						
Alumina balls 50 grams						
Hydrogen feed rate 0 cf/min.						
temperature - 800 degree centigrade						
pressure 755 - psig						
time	press	reactor	concentrations			Vol%
min.	psig	temperature	of generated gases			
		C	CO	CO2	CH4	C2H6
0	755	35				
1	755	46				
6	757	118				
11	765	212				
16	772	305				
20	785	375				
21	804	383				
24	802	432				
26	803	452				
31	803	504				
33			5.2	8.9	0.4	
38	804	575				
41	804	595	9.7	21.3	0.9	
46	804	628	11.0	23.3	1.5	
51	804	652				
54			11.6	23.0	3.5	0.4
56	803	681				
61	804	718				
66	804	729				
71	803	750	7.8	21.7	12.1	1.8
76	803	768	7.0	24.3	18.8	2.8
81	803	783				
86	803	800				
91	803	813				
96	803	813				
101	802	814				
106	802	814	5.6	29.4	25.7	3.4
111	802	814				
123	800	813				
135	798	813				
residue in the reactor and char trap						
63 grams including 26 grams Silica						
some water (about 5 cc) remained in the char trap						
and inside reactor.						

Data Table 2 Experimental Data for the Hydrogasification in the rapid heating up of the Biomass.

at 800 degree centigrade and at 455 psig of initial hydrogen pressure

Run Number: 1144

October 2/11

Wood: 184.8 gm wood content: 80% SiO₂ content: 20%
147.8 36.96

Biomass Feed Rate: 16.9 grams/min.

800 cent: 460 psi

residue: 54 grams including SiO₂ Biomass Conversion: 88.5 wt%

time	CO Vol%	CO ₂ Vol%	CH ₄ Vol%	press. psig	press atm	change mol/number dn/dt	mol/change
0	0	0	0	455 n	31.952	0	0
1				462.5 ave	32.462	0.24479	0.24479
2	19.7	7.1	20.1	470 n	32.972	0.24479	0.48959
3				478 n	33.517	0.26111	0.75070
4				476.5 ave	33.414	-0.0489	0.70174
5	16.4	8.9	16.8	475 n	33.312	-0.0489	0.65278
6				478.5 ave	33.551	0.11423	0.76702
7				482 n	33.789	0.11423	0.88126
8				486 n	34.061	0.13055	1.01182
9				486 n	34.061	0	1.01182
10				488 ave	34.197	0.06527	1.07710
11	16	6	16	490 n	34.383	0.06527	1.14238
12				491 ave	34.401	0.03263	1.17502
13				492 n	34.469	0.03263	1.20765
14				497.5 ave	34.848	0.17951	1.38717
15	16.2	4.4	17.5	508 n	35.217	0.17951	1.56669
16				506 ave	35.421	0.09791	1.66461
17				509 ave	35.625	0.09791	1.76253
18	18.5	7.2	18.8	512 n	35.829	0.09791	1.86044
19				514 ave	35.965	0.06527	1.92572
20				516 n	36.102	0.06527	1.99100
21				519 ave	36.306	0.09791	2.08892
22				522 n	36.510	0.09791	2.18684
23				526 ave	36.782	0.13055	2.31740
24				530 n	37.054	0.13055	2.44795
25				532 ave	37.190	0.06527	2.51323
26				534 n	37.326	0.06527	2.57851
27				536 ave	37.462	0.06527	2.64379
28				538 ave	37.598	0.06527	2.70907
29				540 n	37.734	0.06527	2.77435
30				541 ave	37.802	0.03263	2.80699
31				542 n	37.870	0.03263	2.83963
32				542 ave	37.870	0	2.83963
33				542 n	37.870	0	2.83963
34				540 ave	37.734	-0.0652	2.77435
35	16.4	5.1	18.6	538 n	37.598	-0.0652	2.70907
36				536.5 ave	37.496	-0.0489	2.66011
37				535 ave	37.394	-0.0489	2.61115
38				533.5 ave	37.292	-0.0489	2.56219
39				532 n	37.190	-0.0489	2.51323
40				531.4 ave	37.149	-0.0195	2.49365
41				530.8 ave	37.108	-0.0195	2.47407
42				530.2 ave	37.068	-0.0195	2.45449
43				529.6 ave	37.027	-0.0195	2.43490
44				529 n	36.986	-0.0195	2.41531
45				528.2 ave	36.931	-0.0261	2.38920
46				527.4 ave	36.877	-0.0261	2.36309
47				526.6 ave	36.823	-0.0261	2.33698
48				525.8 ave	36.768	-0.0261	2.31087
49				525 n	36.714	-0.0261	2.28476
50				522.8 ave	36.566	-0.0707	2.21404
51				520.6 ave	36.419	-0.0707	2.14332
52				518.5 ave	36.272	-0.0707	2.07260
53				516.3 ave	36.124	-0.0707	2.00188
54				514.1 ave	35.977	-0.0707	1.93116
55				512 n	35.829	-0.0707	1.86044
56				500.6 ave	35.058	-0.3699	1.49053
57				499.3 ave	34.287	-0.3699	1.12062
58				478 n	33.517	-0.3699	0.75070

Data Table 3 Experimental Data for the Hydrogasification
in the rapid heating up of the Biomass.

at 800 degree centigrade and at 755 psig of
initial hydrogen pressure

Run number: 1152

November 18 12:30 - 13:10

Wood: 152 gm wood content 80% and SiO₂ 20%
121.6 gm 30.4 gm

Biomass Feed Rate: 10.1 grams/min.

Biomass Conversion: 89.6 wt%

800 cent 800 psi

residue char 43.1 grams including SiO₂

time	CO Vol%	CO ₂ Vol%	CH ₄ Vol%	correct press psig	correct press atm	change mol/number dn/dt	total mol/change
0	0	0	0	755	52.360	0	0
1				760	53.312	0.145597	0.145597
2				775	53.789	0.22848	0.68545
3				779	53.993	0.09792	0.78337
4				780	54.061	0.08264	0.81602
5				788	54.265	0.09792	0.91394
6				784	54.303	0.08264	0.94658
7				786	54.463	0.06528	1.01186
8				788	54.605	0.06528	1.07714
9				791	54.843	0.11424	1.19138
10				795	55.081	0.11424	1.30562
11				800	55.421	0.16320	1.46882
12				804	55.693	0.13056	1.5994
13				807	55.897	0.09792	1.69732
14				809	56.034	0.06528	1.76260
15				811	56.170	0.06528	1.82788
16				812	56.238	0.08264	1.86052
17				811	56.204	-0.0163	1.84420
18				811	56.170	-0.0163	1.82788
19				810	56.136	-0.0163	1.81156
20				810	56.102	-0.0163	1.79524
21				809	56.068	-0.0163	1.77892
22				809	56.034	-0.0163	1.76260
23				808	56	-0.0163	1.74628
24	33.4	14.7	29.5	808	55.965	-0.0163	1.72996
25				807	55.931	-0.0163	1.71364
26				807	55.897	-0.0163	1.69732
27				806	55.863	-0.0163	1.68100
28				806	55.829	-0.0163	1.66468
29				806	55.829	0	1.66468
30				806	55.829	0	1.66468
31				806	55.829	0	1.66468
32				806	55.829	0	1.66468
33				806	55.863	0.01632	1.68100
34	26	8.4	24.9	807	55.897	0.01632	1.69732
35				806	55.880	-0.0081	1.68916
36				806	55.863	-0.0081	1.68100
37				806	55.846	-0.0081	1.67284
38	25.7	8.1	23.6	806	55.829	-0.0081	1.66468
39				805	55.784	-0.0217	1.64292
40				804	55.739	-0.0217	1.62116
41				804	55.693	-0.0217	1.5994
42				804	55.710	0.00816	1.60756
43				804	55.727	0.00816	1.61572
44				804	55.744	0.00816	1.62388
45				805	55.761	0.00816	1.63204
46				805	55.761	0	1.63204
47				805	55.761	0	1.63204
48				805	55.761	0	1.63204
49				804	55.739	-0.0108	1.62116
50				804	55.716	-0.0108	1.61028
51				804	55.693	-0.0108	1.5994
52				804	55.727	0.01632	1.61572
53				805	55.761	0.01632	1.63204
54				804	55.748	-0.0065	1.62551
55				804	55.734	-0.0065	1.61898
56				804	55.721	-0.0065	1.61245
57				804	55.707	-0.0065	1.60592
58				804	55.693	-0.0065	1.5994

Figure 1 Schematic Flow Sheet of Tubular Reactor Equipment

Figure 2 Reactor Temperature, Generated Gases, vs. Lapse of Time at 755 psia, 100% hydrogen of the beginning pressure

Figure 4 Weight Losing Curve of Biomass (Poplar Wood) with Temperature using PtGA (Pressure Thermogravimetric Analyzer) at heat-up rate of 50 C/min. and 400 psig.

Figure 5 Weight Losing Curve of Biomass (Fir Wood) with Temperature using PTGA (Pressure Thermogravimetric Analyzer) at heat-up rate of 50 C/min. and 400 psig.

Figure 7 The change in number of moles in the reactor with time at 800 C and 455 psig of initial hydrogen pressure

Run No. 1144 - Data Table 2

Figure 8 The rate of molar change with time at 800 C and 455 psig of initial hydrogen pressure

Run No. 1144 - Data Table 2

Figure 9 The change in number of moles in the reactor with time at 800 C and 755 psig of initial hydrogen pressure

Run No. 1152 - Data Table 3

Figure 10 The rate of molar change with time at 800 C and 755 psig of initial hydrogen pressure

Run No. 1152 - Data Table 3

END

**DATE
FILMED
4 127 192**