AIM

Association for Information and Image Management

1100 Wayne Avenue, Suite 1100
Silver Spring, Maryland 20910
301/587-8202

Centimeter

Inches

MANUFACTURED TO AIM STANDARDS
BY APPLIED IMAGE, INC.

HANFORD CODE *C-65*

(CLASSIFICATION)

DOCUMENT NO.

HW-80864

SERIES AND COPY NO.

GENERAL ELECTRIC

DECLASSIFIED

HANFORD ATOMIC PRODUCTS OPERATION - RICHLAND, WASHINGTON

March 18, 1964

RESTRICTED DATA

THIS DOCUMENT CONTAINS RESTRICTED DATA AS DEFINED BY THE ATOMIC ENERGY ACT OF 1954. TRANSMITTAL OR DISCLOSURE OF CONTENTS IN ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED.

TITLE

FINAL REPORT
PT IP-603-I, EVALUATION OF ACCIDENTAL
FUEL FLUSHING POTENTIAL
D-DR REACTORS

OTHER OFFICIAL CLASSIFIED INFORMATION

THIS MATERIAL CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING OF THE ESPIONAGE LAWS, TITLE 18, U. S. C., SECS. 793 AND 794, THE TRANSMISSION OR REVELATION OF WHICH IN ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW.

AUTHOR

D. K. George
and
P. J. Hollifield

ISSUING FILE

THIS DOCUMENT MUST NOT BE LEFT UNATTENDED OR WHERE AN UNAUTHORIZED PERSON MAY HAVE ACCESS TO IT. WHEN NOT IN USE, IT MUST BE STORED IN AN APPROVED SECURED REPOSITORY. WHEN APPROVED FOR GUARDED AREA USE, IT IS YOUR RESPONSIBILITY UNTIL YOU HAVE OBTAINED A GUARDED RECEIPT FROM THE CLASSIFICATION OFFICE. IT IS YOUR RESPONSIBILITY TO KEEP IT AND ITS CONTENTS WITHIN THE LIMITS OF THE GUARDED AREA AND FROM ANY UNAUTHORIZED PERSON. ITS TRANSMISSION AND STORAGE OUTSIDE THE GUARDED AREA IS PROHIBITED. IT IS NOT TO BE DUPLICATED. ADDITIONAL COPIES ARE REQUIRED, OBTAIN THEM FROM THE ISSUING FILE. ALL PERSONS READING THIS DOCUMENT ARE REQUESTED TO SIGN IN THE SPACE PROVIDED BELOW.

ROUTE TO:

PAYROLL NO.

LOCATION

FILES ROUTE
DATE

SIGNATURE AND DATE

300 Files

REFERENCE COPY
RECEIVED 10 AREA
APR 1 1964
RETURN 10
TECHNICAL INFORMATION FILES

DECLASSIFIED

DECLASSIFIED

HANFORD CODE C-65

HW-80864

[REDACTED]
This document contains restricted information
deriving from Atomic Energy Commission Contract AT(45-1)-1350.
Its transmittal to other than the authorized recipient
is prohibited.

This document consists of
7 pages, [REDACTED]

This document classified by

MA Clinton

DISTRIBUTION

1. AEC-RLOO: PM Midkiff	16. PJ Hollifield
2. AEC-RLOO: RL Plum	17. HI Lewis
3. AEC-RLOO: CN Zangar	18. JE Morrissey
4. TW Ambrose	19. CA Munro
5. ER Astley	20. WH Radtke
6. JT Baker	21. RW Reid
7. RS Bell	22. OC Schroeder
8. JT Baker	23. HG Spencer
9. PA Carlson	24. RE Spicka
10. MA Clinton	25. RC Haynes
11. EJ Filip	26. SA Wood
12. DK George	27. PJ Zimmerman
13. OH Greager	28. 300 Files
14. CN Gross	29. Record Center
15. AK Hardin	

Classification Cancelled and Changed To

March 18, 1964

DECLASSIFIED

By Authority of RM J Ten
CG-PR-2, 4-6-94
by J-E Savely 4-17-94
Certified By Jessi Maley 4-18-94

HANFORD ATOMIC PRODUCTS OPERATION RICHLAND, WASHINGTON

NOTICE

This report was prepared for use within General Electric Company in the course of work under Atomic Energy Commission Contract AT(45-1)-1350, and any views or opinions expressed in the report are those of the author only. This report is subject to revision upon collection of additional data.

LEGAL NOTICE

This report was prepared as an account of Government sponsored work. Neither the United States, nor the Commission, nor any person acting on behalf of the Commission:

A. Makes any warranty or representation, expressed or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this report, or that the use of any information, apparatus, method, or process disclosed in this report may not infringe privately owned rights; or

B. Assumes any liabilities with respect to the use of, or for damages resulting from the use of any information, apparatus, method, or process disclosed in this report.

As used in the above, "person acting on behalf of the Commission" includes any employee or contractor of the Commission, or employee of such contractor, to the extent that such employee or contractor of the Commission, or employee of such contractor prepares, disseminates, or provides access to, any information pursuant to his employment or contract with the Commission, or his employment with such contractor.

MASTER DECLASSIFIED
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

FINAL REPORT
PT IP-603-I, EVALUATION OF ACCIDENTAL
FUEL FLUSHING POTENTIAL
D-DR REACTORS

INTRODUCTION

The purpose of Production Test IP-603-I was to obtain data to help determine if uranium I&E fuel can be flushed from tubes set up for discharge on a valved down crossheader by raising the front riser pressure. The two main reasons for obtaining this information are:

1. Process Standard H-020 limits the number of enriched fuel elements (E-metal) that may be discharged into the pickup chutes at any one time to guard against formation of a critical assembly. If it is possible to flush E-metal, then the number of tubes set up for discharge at any one time must be limited.
2. It has been recommended that the steam turbine pumps remain on automatic backup during reactor shutdown.² The flushing information obtained in this test will help determine if uranium fuel elements and irradiated dummies can be flushed by accidentally accelerating the steam turbine pumps during shutdown.

SUMMARY AND CONCLUSIONS

The test consisted of valving down one header at shutdown riser pressure, then increasing the riser pressure and recording the resulting front nozzle pressures on selected tubes uncapped on the rear.

The following conclusions were reached from the test results and a review of additional Thermal Hydraulics Lab. tests:

1. A standard length I&E uranium fuel column including the H reactor E-N charge will not be flushed from tubes set up for discharge on a valved down crossheader, provided the initial crossheader delta P is less than 225 inches at a top-of-riser pressure (TORP) of 75 psi or more. This is true for the B, D, DR, F, and H reactors, but not necessarily true for C and the K reactors.
2. A standard length fuel charge or the main section of the downstream dummy column will not flush by accelerating the 190 steam turbine pumps provided the conditions in 1 above are met.

Some of the end dummies may float out. During the test there was no tendency for the main sections of the dummy pattern to move.

3. It may be possible to flush an irradiated solid poison column such as is used at the small reactors for shield protection, with steam turbine pump pressures, depending on the number of pumps accelerated and the reactor valving configuration.

DECLASSIFIED

4. It is possible to flush a solid poison column such as is used at the small reactors for shield protection with normal operating pressure from the electric process pumps.

TEST RESULTS

The test results are shown graphically in Figure 1. The D reactor test was terminated at a top-of-riser pressure (TORP) of 500 psi because of crossheader vibration. The front-header pressure readings could not be obtained in the DR reactor test because of oscillation in the control room Heise gauge caused by leaks in the toggle valve O-rings on the other crossheader pressure sensing lines. The test header (number 6 at D reactor, number 5 at DR reactor) was throttled to a 225 inch differential pressure at a TORP of 75 psi. Tube numbers 0672 (34-piece OIIIEB charge) and 0772 (32-piece OIIINB charge) at D reactor and numbers 0579 (34-piece OIIIEB charge) and 0683 (32-piece OIIINB charge) at DR reactor were uncapped on the rear.

The front-nozzle pressures that resulted from raising the TORP were 53 psi at DR reactor (at a TORP of 540 psi), and 36 psi at D reactor (at a TORP of 500 psi), with no significant difference in the front-nozzle pressure readings between the natural and enriched charges.

The fuel column position from the end of the rear nozzle was measured before and after each test with no movement detected. The position of the main part of the downstream dummy column was also measured before and after each test. Although two or three of the end dummies did flush from each tube, no movement of the main section of the downstream dummy column was detected. Because the tubes could not be observed from the rear-face viewer, the pressure at which the end dummies flushed was not determined.

DISCUSSION

To find the required flushing pressure, Design Test #1185 was conducted. The Thermal Hydraulics Laboratory process tube mockup was charged with 33 OIII enriched bumper fuel pieces and one water mixer. The pressure was raised in steps until metal flushing occurred. The results indicated a front-nozzle pressure of about 80 psi was required to begin flushing an E-metal column, and about 90 psi was required to flush the whole column. The results also indicated the main section of the downstream dummy column did not flush until the front-nozzle pressure reached about 80 psi.³

The front-nozzle pressure that resulted from raising the TORP to the operating value was 53 psi at DR reactor. An extrapolation of the D reactor test data indicate a front-nozzle pressure of 43 psi would result from raising TORP to the operating value. These front-nozzle pressures are well below that required to flush E-metal found in Design Test #1185.

Additional Thermal Hydraulics Lab. reports were reviewed to obtain more flushing information:

DECLASSIFIED

In reference 4, a report on natural metal flushing, the following conclusions were reached:

1. A standard I&E natural metal column will flush at a front nozzle pressure of about 140 psi.
2. There is no tendency for the main section of the downstream dummy column to move until part of the metal charge flushes.
3. The front nozzle pressure required to flush metal will decrease as the process tube flow annulus area increases.

Although the I&E fuel element design has changed since reference 4 was issued, this change should not affect the natural metal flushing pressure by more than 20 psi.

In reference 5, a report on flushing pressures for OIIEB and lithium-aluminum elements, the following conclusions were reached.

1. A 40 OIIEB plus five 4" Li-Al I&E charge will start to flush at a front nozzle pressure of about 100 psi.
2. A 40-piece mint charge (6" Li-Al solid) will begin to flush at a front nozzle pressure of about 15.5 psi.
3. A 47-piece solid mint charge with a Pb-Cd anchor at each end will start to flush at a front nozzle pressure of about 17 psi.
4. There is no tendency for the dummy charge to be flushed before the fuel elements start to move.

The flushing pressure for the 40-piece OIIEB plus five 4" Li-Al charge should approximate the flushing pressure for the present H reactor E-N charge.

The flushing pressure for the 47-piece solid mint columns should approximate the flushing pressure for the mint charges used for shield protection at the old reactors. From these laboratory tests and this production test results, one can conclude (a) the 34-piece E-metal charge will flush at a lower pressure than a 32-piece natural fuel column or a longer enriched fuel column including the H reactor E-N charge, and (b) the upstream (irradiated) section of the downstream dummy column should not move before part of the fuel charge begins to flush.

The second purpose of this test was to obtain data to help determine the possibility of flushing irradiated fuel elements and dummies with steam turbine pump pressure. The maximum top-of-riser pressure available from the 190 steam turbine pumps, at the present speed setting, is about 180 psi at DR reactor and about 190 psi at D reactor (pump deadhead pressure minus elevation head to the top of the riser). In the actual case, the TORP resulting from steam pump acceleration will be less than this deadhead pressure depending on the number of pumps accelerated, whether the turbines are condensing or noncondensing, and

DECLASSIFIED

the reactor valving configuration. From this production test data, the maximum front-nozzle pressure that would result from steam pump acceleration on a header initially throttled to 225" ΔP would be 21 psi at DR reactor and 13 psi at D reactor. This nozzle pressure is far below the pressure required for flushing fuel elements and dummies; however, it may be possible to flush a solid poison column such as those used at the small reactors for shield protection (reference 5).

The results of this test are not applicable to C and the K reactors due to front hardware and tube flow annulus differences.

D. K. George

D. K. George, Engineer
Process Engineering Unit
Process Technology Subsection
Research and Engineering

P. J. Hollifield

P. J. Hollifield, Engineer
Process Engineering Unit
Process Technology Subsection
Research and Engineering

DKG:PJH:md

APPROVED:

M. A. Clinton

M. A. Clinton, Supervisor
Process Engineering Unit
Process Technology Subsection
Research and Engineering

DECLASSIFIED

REFERENCES

1. George, D.K., and P.J. Hollifield, Production Test IP-603-I, Evaluation of Accidental Fuel Flushing Potential, D-DR Reactors, July 30, 1963, HW-78452, (Secret).
2. Letter, R. W. Reid to R. S. Bell et al, Continuity of Reactor Shutdown Flow, dated June 26, 1963.
3. Lander, W.E.B., Final Report, E-Metal Flushing Flow for a BDF Process Tube, dated October 1, 1963, HW-79013, (Secret).
4. McCarthy, P.B., Nozzles Pressure Required to Flush Regular and I&E Out of BDF, C, and K Process Tubes, dated December 9, 1957, HW-54093, (Confidential-Undocumented).
5. Hammond, J.E., Flush-Discharging Pressures for OIII and Lithium-Aluminum Elements in a BDF Tube, dated August 31, 1961, HW-70908, (Confidential-Undocumented).

DECLASSIFIED

FIGURE 1. PT IP-603-I DATA
HEADER INITIALLY THROTTLED
TO 225" ΔP AT 75 psi TORP

DECLASSIFIED

DATE

FILMED

7/21/94

END