DOE/ER/60883--3

DE93 011615

SIMULATION OF LANDSCAPE DISTURBANCES
AND THE EFFECT OF CLIMATIC CHANGE

Final Report
for Period July 15, 1989 - July 14, 1990

William L. Baker

Department of Geography
University of Kansas
Lawrence, Kansas 66045

January 29, 1993

MASTER

Prepared for
THE U. S. DEPARTMENT OF ENERGY
AGREEMENT NO. DE-FGO2-89ER60883

ds
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the Department of Energy, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed or represents that its use would not infringe privately-owned rights.

TABLE OF CONTENTS

1. ABSTRACT	4
2. INTRODUCTION	5
3. RESEARCH CARRIED OUT DURING THE REPORTING PERIOD	5
3.1. Work completed through March 1, 1991	5
3.1.1. Analysis of Animas River Field Data	5
3.1.2. Version 2.0 of the Simulation Code	6
3.1.3. Flood-disturbance Model Concept	8
3.2. Work to be completed from March 1 to July 14, 1991	9
4. TIME ALLOCATION	9
5. BIBLIOGRAPHY	10
6. APPENDICES	11
A. Preprint - <u>Ecological Modelling</u> article	
C. Abstracts from papers presented at meetings	
1990 Ecological Society of America meetings	
1991 Association of American Geographers meetings	
1991 Ecological Society of America meetings	
1991 Intern. Assoc. Landsc. Ecol. World Congress	
D. SIMSCRIPT code for the non-climatic model	
E. Documentation for the GLE software	

*preprints +
abstracts
removed.
ok*

1. ABSTRACT

The purpose of this research is to understand how changes in climate may affect the structure of landscapes that are subject to periodic disturbances. A general model useful for examining the linkage between climatic change and landscape change has been developed. The model makes use of synoptic climatic data, a geographical information system (GRASS), field data on the location of disturbance patches, simulation code written in the SIMSCRIPT language, and a set of landscape structure analysis programs written specifically for this research project. A simplified version of the model, lacking the climatic driver, has been used to analyze how changes in disturbance regimes (in this case settlement and fire suppression) affect landscape change. Landscape change lagged in its response to changes in the disturbance regime, but the lags differed depending upon the character of the change and the particular measure considered. The model will now be modified for use in a specific setting to analyze the effects of changes in climate on the structure of flood-disturbed patches along the Animas River, Colorado.

2. INTRODUCTION

The research reported here represents the second year of a three year project begun at the University of Kansas and transferred at the beginning the second year to the University of Wyoming. It is Year 1 of the University of Wyoming research.

The purpose of this research is to understand how changes in climate may affect the structure of landscapes that are subject to periodic disturbances. The project involves the development of a general spatial computer simulation model, using the SIMSCRIPT simulation language and the GRASS GIS. The model will then be calibrated for a specific application, in modelling the effects of floods on vegetation patches along the Animas River in southwestern Colorado. Simulation experiments that will enable prediction of potential scenarios for future landscape structure will be completed during Year 3 of the project.

3. RESEARCH CARRIED OUT DURING THE REPORTING PERIOD

The proposed research tasks for the three year project were finalized in a memorandum dated April 20, 1989 from the PI to Walter H. Conley, then DOE Project Officer. This memorandum was an amendment to the original grant proposal. The primary research tasks for this year were to: (1) analyze Animas River field data, (2) complete Version 2.0 of the simulation code, (3) refine the simulation model for a flood-disturbed landscape, (4) conduct field research on the Animas River during the Summer of 1991, and (5) draft journal articles and present papers on the research.

3.1. Work Completed Through March 1, 1991:

3.1.1. Analysis of Animas River Field Data

During the Summer of 1990 we collected field data along the Animas River in preparation for the major field work to be completed during the Summer of 1991. We completed three tasks during this field work. First, we collected approximately 200 tree cores from sites along the river and from upland sites near the river. Ring widths and ages have subsequently been determined for about half the cores to date. We intend to use these tree-ring indices to reconstruct past flood events along the river. This flood history, if it can be successfully reconstructed, will provide an important capability to temporally extend the flood model that we are developing (section 3.1.3.). Second, we located, mapped, and photographed the study reach that will be extensively studied during the 1991 field season. Third, we refined our existing map of patch boundaries along the reach and identified locations that require additional work during the 1991 field season.

After the start of the 1990-91 academic year (in Oct. 1990), the PI and two new graduate students (Gillian Walford, Yunming Cai) returned to the Animas River to plan Ms. Walford's and Mr. Cai's master's thesis

research, both of which are part of this project.

3.1.2. Version 2.0 of the Simulation Code

We completed development of all parts of the general model including development of a software package for landscape structure analysis, and have a description of the general model in press (Appendix A). We have also been exploring the use of the model for analyzing non-climatic changes in landscapes, and have submitted a manuscript describing the results of an experiment with this approach. We will soon (section 3.2.) complete our first experiment with a simplified version of the climate-based model. Finally, we have conceptualized a specific application of the climate-based model to a flood environment (section 3.1.3.), but have not yet completed the coding for this application.

3.1.2.1. The general model

The general model is described in detail in an article in press with the journal Ecological Modelling, which is included in Appendix A, and will not be described further here. The code for the general model consists of approximately 1,800 lines written in SIMSCRIPT II.5, as well as the code for the GLE programs (section 3.1.2.2.).

3.1.2.2. The GLE programs for landscape structure analysis

An essential component of the general model is a suite of programs for analyzing landscape structure while the model runs. We reported last year that we had developed software called STRUCT for this purpose, but STRUCT was plagued by problems and had to be completely redone. The major problems with STRUCT were that: (1) it was very slow in operation, requiring several minutes to analyze a small landscape (e.g. 200 X 200 pixels), (2) it was prone to errors because it required conversion from raster to vector format prior to operation, and this conversion failed for complex landscape patterns, (3) we were never able to implement the moving-window version of the measures because they required repeated raster-to-vector conversions.

The STRUCT program was rewritten (and renamed the GLE programs) to use the raster format of the GRASS GIS exclusively. Version 2.0 of the GLE programs is almost complete and is described in detail in Appendix E. The code for the GLE software consists of about 10,000 lines written in the C language. Redevelopment of this software formed the master's thesis for Mr. Yunming Cai, who is scheduled to defend his thesis in early April. The GLE programs now run very quickly (in a few seconds, rather than a few minutes) and lack the errors that were a problem with STRUCT. Moreover, the programs contain several new measures that are useful for characterizing landscapes, including measures of texture and juxtaposition. The programs were designed to be used with the model, but can also be used as a standalone package for analyzing landscape

structure within the GRASS GIS. The first modelling experiment that uses the GLE programs has now been completed (Appendix B).

3.1.2.3. An application of a non-climatic version of the model

The climatic version of the model described in Appendix A requires field data that we will not have until after the field work in the Summer of 1991. We wanted to explore the use of the model prior to this time. In order to do so we developed a non-climatic version of the model that omits the effect of climatic change on the disturbance regime, but includes all the other features of the general model including the disturbance regime, the GIS representation of the landscape, and the GLE programs for landscape structure analysis. The code for this non-climatic version of the model is in Appendix D.

We used this non-climatic model to examine the potential influence of changes in the disturbance regime on landscape structure in the Boundary Waters Canoe Area (BWCA), Minnesota. The detailed results of this experiment are reported in an article just submitted to the journal Nature (see Appendix B). Changes in the disturbance regime in the BWCA were caused by a period of settlement followed by a period of fire suppression. The unexpected results of this experiment were that the landscape did not respond as quickly to the changes from suppression as it did to changes from the settlement period. Moreover, some measures of landscape structure (from the GLE programs) were more sensitive to change than were others. We believe that the results of this experiment are significant because the landscape appears to exhibit significant inertia to certain kinds of change, but less inertia to other kinds of change. Moreover, the results have implications for monitoring programs, such as the U.S. Environmental Protection Agency's EMAP program, that are aimed at detecting and characterizing landscape change.

3.1.2.4. A simplified version of the climate-based model

Based upon the unexpected results of this application of the non-climatic model (section 3.1.2.3.), we have decided to pursue a simpler version of the general model for exploring the potential effects of climatic change upon landscape structure.

The non-climatic version of the model contains a disturbance regime that can be simply changed manually at the end of a time period with a consistent disturbance regime, to explore the effects of a new disturbance regime. We now plan to modify this model so that the parameters of the disturbance regime can be made a direct function of temperature. We hope to then simulate the effects of historical changes in temperature upon landscape structure in the BWCA, using Fritts' temperature reconstruction for the BWCA area (Fritts, in press). If possible, we will also produce a prediction for landscape structure under a doubled CO₂ scenario. This approach is not the detailed and physically explicit approach we are using for the flood-based model (section 3.1.3.), but if successful it should provide a useful first approximation of a scenario for future landscape structure and an

assessment of the potential lags in response to climatic change.

3.1.3. Flood-disturbance Model Concept

The general model will be adapted for use in a specific setting—the effects of disturbance by floods along the Animas River, Colorado. This specific application will entail development and calibration (with field data) of a physically-based model of the climatic sources of floods and the effects of floods on patches in the riparian landscape. The model requires calibrating links between the occurrence of synoptic climatic types, the occurrence of streamflows of a particular magnitude and their associated unit stream power, the physical ability of unit stream power to produce disturbed patches along the reach, and the net effect of patch creation on landscape structure.

The climatic part of the model will be based upon the use of historical data on the occurrence of synoptic climatic types over the western United States (Barry et al. 1981). These data include an identification of the synoptic climatic type for each day since flood records began on the Animas River. These data will be used to determine the probability of occurrence of each synoptic climatic type by season for input to the model.

The climatic data are linked to the streamflow (disturbance) regime through determination of the probability of a certain percent change in discharge associated with each synoptic climatic type. We will use daily streamflow data for the Animas River obtained from the U.S. Geological Survey's WATSTORE data base system. Using these streamflow data, we will calculate, for each day of the record, the percent change in discharge and assign that change to the distribution of changes for the corresponding synoptic climatic type.

The streamflow regime must then be linked to the physical force exerted on the vegetation along the river and the capacity of that force to disturb the vegetation. To do this, we must calculate the unit stream power for the locations along the reach that have been disturbed during each day of the record when streamflow was sufficient to disturb the vegetation. The physical force that must be calculated is "unit stream power" which is dependent upon the specific weight of the water, the discharge, and the energy slope (Baker and Costa 1987). We will use the U.S. Army Corps of Engineers HEC-2 model (US Army Corps of Engin. 1982) to calculate, using stream channel cross-sections collected in the field, the depth of water during each past disturbance day. From the depth of water, estimates of Manning's n made in the field, and measurements of slope made in the field, we can calculate unit stream power for locations along the reach using the GRASS GIS. Unit stream power data can then be linked to the size of disturbances actually observed along the reach (reconstructed from field data).

We are optimistic that we can establish the link between weather conditions and the occurrence of disturbance patches along the reach, but this is completely new work. No one has studied this link previously and no one has attempted to measure the unit stream power that is required to disturb vegetation along a river. The outcome of the calibration is thus uncertain, but we expect that the model

formulation and modelling experiments will be interesting even if the calibration is not completely successful.

3.2. Work to be Completed from March 1 to July 14, 1991:

The primary tasks that remain to be completed during Year 2 include: (a) completion of the GLE programs, (2) a sensitivity analysis of the non-climatic model, (3) completion of the simplified climate model (section 3.1.2.4.), (4) completion of the Animas River field research, and (5) presentation of results at national meetings.

The GLE programs still need some debugging and final testing. This will be completed by the end of the academic year.

The core of the general model is contained in the simpler non-climatic model with which we now have direct experience. Prior to collecting field data on the Animas River, we need to know to which parameters the model is most sensitive, so that we can collect the required data with sufficient precision. We plan to complete a half fractional factorial sensitivity analysis (Swartzman and Kaluzny 1987) of the non-climatic model by the end of the academic year.

The simplified climate model will be developed and simulations with the model will be completed. This will require calibration of historical temperature changes with changes in the BWCA disturbance regime, followed by the simulation experiment, which will involve multiple runs and a statistical analysis of the results.

The field research on the Animas River will entail collection of three kinds of data: (1) mapped locations of all flood-disturbed patches, (2) dates when each patch was disturbed by flood, (3) stream cross-sections. Aerial photography will be used to map the locations of patches in the field. These locations will later be entered into the GRASS GIS. The time of disturbance will be determined using tree-ring analysis. Detailed measurements of stream cross-sections will be collected at 50-100 locations along the reach. These cross-sections are essential for use in the HEC-2 model (section 3.1.3.) in reconstructing streamflow characteristics at the time of each flood.

Presentations of the results of this year's work will be made at the Association of American Geographer's Annual Meetings in Miami, Florida (April 13-16, 1991). Presentations will also be made early in Year 3 at the Intern. Assoc. Landsc. Ecol. World Congress in Ottawa, Canada (July 22-25, 1991) and at the Ecological Society of America Annual Meetings in San Antonio, Texas (August 4-8, 1991).

4. TIME ALLOCATION

The PI has spent approximately 40% of his time on this project during the first part of Year 2, and will spend at least 40% of his time on the project during the remainder of Year 2. The PI has been intimately involved with all phases of the research. He wrote all the SIMSCRIPT code, supervised development of the GLE programs, completed all of the modelling experiment, and wrote both of the articles in the appendices.

5. BIBLIOGRAPHY

- Baker, V.R. and J.E. Costa. 1987. Flood power. p. 1-21 in L. Mayer and D. Nash (eds) Catastrophic flooding. Allen & Unwin, London.
- Barry, R.G., G. Kiladis, and R.S. Bradley. 1981. Synoptic climatology of the western United States in relation to climatic fluctuations during the Twentieth Century. J. Climatology 1:97-113.
- Fritts, H.C., in press. Reconstructing large scale climate patterns from tree-ring data: a diagnostic analysis. Univ. of Arizona Press, Tucson, in press.
- Swartzman, G.L. and S.P. Kaluzny. 1987. Ecological simulation primer. Macmillan, New York. 370 pp.
- U.S. Army Corps of Engineers. 1982. HEC-2 water surface profiles user's manual. Water Resources Support Center, The Hydrologic Engin. Support Center, Davis, California.

APPENDIX D. SIMSCRIPT Code for the Non-climatic Model

```

////////////////////////////////////
'' MODEL L A Y O U T ''
''
'' routine DISTINT selects a disturbance interval from a ''
'' distribution of disturbance intervals ''
'' routine DISTGEN selects a disturbance size from a ''
'' distribution of disturbance sizes ''
'' routine DISTPROB combines the layers in the GIS to create a ''
'' layer, DISTPROB_REAL, containing the probability of ''
'' being disturbed at each location in the landscape ''
'' routine DISTLOC checks for possible disturbance ''
'' locations, and places the disturbance into the landscape ''
'' routine DISTSPR moves the disturbance to adjoining ''
'' cells ''
'' routine SAMPINT selects a time interval to wait before ''
'' measuring landscape structure ''
////////////////////////////////////
''
''
////////////////////////////////////
'' MODEL I N S T A L L A T I O N / A D J U S T M E N T S ''
''
'' To change this program for another installation, you must correct ''
'' the following: ''
''
'' 1. Enter the correct directory path for the file ''
'' distprob.ascii which is read into the array ''
'' DISTRPROB_INT in routine DISTPROB, and the correct ''
'' recordsize ''
'' 2. Adjust the values used to reclass the raw age layer into ''
'' age classes for display by modifying file ''
'' reclass.txt currently in /home/grass3.1/sim ''
'' 3. Adjust the class intervals for the histograms of mean ''
'' disturbance size and interval by changing the values ''
'' in the TALLIES section of the preamble ''
'' 4. The number of class intervals is currently set at 15. If ''
'' you change this, you will need to change the format ''
'' for printing these out. See section #2 in the list ''
'' of operations completed each year in the MAIN section ''
////////////////////////////////////
''
''
////////////////////////////////////
'' MODEL S E T U P : N O N - H I S T O G R A M M O D E ''
''
'' The following must also be completed before the model is started: ''
''
'' 1. Start GRASS3, start the monitor by entering Dstart.mon ''
'' SUNVIEW, then Dselect.mon SUNVIEW, resize the window. ''
'' 2. Go to /home/grass3.1/sim and run Gle.setup to set up the ''
'' sampling method for analyzing landscape structure. ''
'' 3. Compile this code (simc -C model.sim) if not already done ''
'' 4. Compile the model_lib.c file by typing gcc ''
'' if not already done ''
'' 5. Return to /home/grass3.1/sim and type loadmodel, then ''
'' a.out to start the model ''
////////////////////////////////////
''
''
////////////////////////////////////
'' MODEL S E T U P : H I S T O G R A M D I S P L A Y M O D E ''

```

```

''
'' The following must also be completed before the model is started: ''
''
'' 1. Start GRASS3, start the monitor by entering Dstart.mon ''
''     SUNVIEW, then Dselect.mon SUNVIEW, resize the window. ''
'' 2. Go to /home/grass3.1/sim and run Gle.setup to set up the ''
''     sampling method for analyzing landscape structure. ''
'' 3. Remove the comment marks from the two sections with ''
''     comment marks followed by the number one ''
'' 4. Recompile this code (simc -C model.sim). ''
'' 5. Make sure the simgraphics icon files (*.grf) exist in the ''
''     /home/grass3.1/sim directory ''
'' 6. Compile the model_lib.c file by typing gcc ''
''     if not already done ''
'' 7. Return to /home/grass3.1/sim and type loadmodelg, then ''
''     a.out to start the model ''
''
''
''
preamble
''
''
''
''
'' ***** ''
'' * VARIABLE TYPES (E.G. REAL) MUST BE EXPLICITLY * ''
'' * DECLARED * ''
'' ***** ''
''
'' normally, mode is undefined
''
''
'' NONSIMSCRIPT ROUTINES
''
'' define annual_updt as a nonsimscript routine
''     which adds one to the AGE layer in grass
''     at the end of a year,
''
'' define initdistmap as a nonsimscript routine
''     which initializes the disturbance map prior
''     to starting the model
''
'' define initlayer as a nonsimscript routine
''     which copies a random cell layer into the
''     initial layer for the model to start with
''
'' define make_distprob as a nonsimscript routine
''     which makes DISTPROB using grass
''
'' define putnum as a nonsimscript routine
''     which calls fprintf to print out the
''     disturbance map (DISTMAP)
''
'' define reclass_map as a nonsimscript routine
''     which reclasses the current AGE map prior to display
''
'' define save_grass_layer as a nonsimscript routine
''     which saves a GRASS layer to a file for later analysis

```

```

''
    define show_map as a nonsimscript routine
''
    which displays the AGE map in a GRASS graphics window
''

    define sstruct as a nonsimscript routine
''
    which calls landscape measurement modules
''

    define update_map as a nonsimscript routine
''
    which updates the current AGE map
''

    define write_ascii as a nonsimscript routine
''
    which adds header information to DISTMAP
''
    so that it fits the GRASS format
''
''
''
''
    INTEGER VARIABLES
''

    define BUF as an integer variable
''
    used to hold temporary results
''

    define CURRENT_DISTURB_SIZE as an integer variable
''
    which contains the current disturbance size
''
    in pixels
''

    define DISTURB_INTERVAL as an integer variable
''
    which is the time in years between disturbances
''

    define DISTURB_INTERVAL_CHOICE as an integer variable
''
    which is 1 if the Weibull distribution of
''
    disturbance intervals is to be used, and is 2 if
''
    an empirical distribution of disturbance intervals
''
    is to be used.
''

    define DISTURB_YR as an integer variable
''
    which is the year in which a disturbance occurs
''

    define DONE as an integer variable
''
    which is 0 when routine DISTLOC option 3 is not
''
    done and is 1 when it is done
''

    define i, j as integer variables
''
    used to index arrays
''

    define LOC_OPTION as an integer variable
''
    which indicates which option is to be used for
''
    choosing where to start the disturbance
''

    define MAP_CHOICE as an integer variable
''
    which is 1 if map output is to be displayed
''
    during model run, and is 0 if not
''

    define MAX_LOC_ROW and MAX_LOC_COL as integer variables
''
    which contain the row and column locations for the
''
    maximum disturbance probability in DISTPROB_REAL
''

    define MAXR, MAXC as integer variables
''
    which are the row and col of the neighboring pixel
''
    that contains the maximum disturbance probability
''

    define NROW, NCOL as integer variables

```

```

''          which keep track of how many rows and columns
''          there are in the model area
''
define OVER as an integer variable
''          which is used in routine DISTSPR option 2
''          to determine whether a loop should be stopped
''
define PREVDIST_COL, PREVDIST_ROW as integer variables
''          which contain the location of the previous disturbed
''          cell
''
define R, C as integer variables
''          which contain the row and col location as the
''          disturbance spreads from pixel to pixel
''
define SAMP_INTERVAL as an integer variable
''          which is the current time to wait before
''          measuring landscape structure
''
define LAST_SAMP_YR as an integer variable
''          which is the year the landscape structure
''          is measured
''
define LAST_SAVE_YR as an integer variable
''          which is the year the map was last saved
''
define SAVE_GAP as an integer variable
''          which is the number of years to skip before saving
''          a new copy of the AGE layer in the GRASS GIS
''
define SIZE_EXPMEAN as an integer variable
''          which contains the mean of the exponential
''          distribution of potential disturbance sizes
''
define SPREAD_OPTION as an integer variable
''          which contains 1 for option 1 or 2 for option 2
''
define START.YR, STOP.YR as integer variables
''          which are the starting and stopping years for the
''          simulation run
''
define STM_SIZE, STM_DISTURB, STM_LOC, STM_SAMP
as integer variables
''          which specify the random number stream to use in
''          picking random numbers for disturbance size,
''          disturbance interval, disturbance location, and
''          sampling interval
''
define TEMP_YEAR as an integer variable
''          which holds the YEAR for display
''
define TIES as an integer variable
''          which is the size of arrays TIESROW and PROBTIESROW
''
define YEAR as an integer variable
''          which keeps track of the current year in the model
''          run
''
define ZEROTIES as an integer variable
''          which keeps track of the number of zeros

```

```

''          among the 8 neighbors during the spread process
''
''
REAL VARIABLES
''
''
''          define DISTMAX as a real variable
''          which indicates the maximum potential value
''          in the GRASS DISTPROB layer
''
''          define DISTPROB_SUM as a real variable
''          which contains the cumulative sum of the disturb-
''          ance probabilities in the DISTPROB_REAL layer
''
''          define DISTPROB_TOT as a real variable
''          which contains the cumulative sum of the disturb-
''          ance probabilities in the 8 neighbors-used in
''          routine DISTSPR option 2
''
''          define DISTURB_SIZE as a real variable
''          which contains the size of the disturbance
''
''          define MAX as a real variable
''          which contains the value of the maximum disturbance
''          probability in the 8 neighboring pixels
''
''          define MAX_DISTPROB as a real variable
''          which contains the maximum disturbance probability in
''          DISTPROB_REAL. Used to find the location for
''          initiating a disturbance.
''
''          define MINIMUMDIST as a real variable
''          which is the minimum probability that must occur in
''          order for a disturbance to be initiated. This
''          is used with option 2 in routine DISTLOC
''
''          define RAND_LOC_VAL as a real variable
''          which contains the random value selected from
''          the cumulative sum of disturbance probabilities
''          in routine DISTLOC option 3
''
''          define RAND_SPR_VAL as a real variable
''          which contains the random value selected from
''          the cumulative sum of disturbance probabilities
''          in the 8 neighbors in routine DISTSPR option 2
''
''          define SAMP_MEAN as a real variable
''          which contains the mean interval between
''          measurements of landscape structure
''
''          define SAMP_STDEV as a real variable
''          which contains the standard deviation of
''          the mean interval between measurements of
''          landscape structure
''
''          define TEMP_INTERVAL as a real variable
''          which temporarily holds MEAN.DISTURB_INTERVAL
''          for display
''
''          define TEMP_SIZE as a real variable
''          which temporarily holds MEAN.DISTURB_SIZE for
''          display

```



```

''
    define WEIBULL_SCALE as a real variable
''
    which contains the Weibull scale parameter value.
''
    This value is the value below which approximately
''
    63% of the values in the distribution will lie
''

    define WEIBULL_SHAPE as a real variable
''
    which contains the Weibull shape parameter value.
''
    This value ranges from 1.0 for an approximately
''
    negative exponential distribution to 3.6 for an
''
    approximately normal distribution to large values
''
    (e.g. 20.0) for a highly negatively skewed
''
    distribution
''

TEXT VARIABLES

''

    define DISTURB_OUT as a text variable
''
    which contains the name of the output file
''
    for the history of disturbances that occur
''
    during the model run
''

    define DISTURB_TEMP as a text variable
''
    which contains the word DISTURB, which is
''
    the prefix for all DISTURB_OUT files
''

    define FORMULA as a text variable
''
    which contains the formula for calculating
''
    disturbance probabilities
''

    define GLEDIST as a text variable
''
    which contains the Gle.dist landscape structure
''
    analysis command and its parameters
''

    define GLEPATCH as a text variable
''
    which contains the Gle.patch landscape structure
''
    analysis command and its parameters
''

    define GLETEX as a text variable
''
    which contains the Gle.dist landscape structure
''
    analysis command and its parameters
''

    define INIT_MAP as a text variable
''
    which contains the name of the starting map
''
    layer
''

    define PARAMS_FILE_NAME as a text variable
''
    which contains the name of the file containing
''
    the model input parameters
''

    define RUN as a text variable
''
    which contains the ID for the run
''

    define RUN_YR as a text variable
''
    which contains the concatenation of RUN and YEAR
''

    define YR_TXT1 as a text variable
''
    which is used temporarily during concatenation
''
    of RUN and YEAR
''

ARRAYS

```

```

"
define DISTMAP as an integer, 2-dimensional array
"    which is a map of the disturbance location
"
"
define DISTPROB_CUM as a real, 2-dimensional array
"    which is an array containing the cumulative sums
"    of disturbance probabilities in array DISTPROB_REAL
"
"
define DISTPROB_INT as an integer, 2-dimensional array
"    which is an array containing disturbance
"    probabilities
"
"
define DISTPROB_REAL as a real, 2-dimensional array
"    which is an array containing relativized disturbance
"    probabilities
"
"
define PROBTIESCOL as an integer, 1-dimensional array
"    which is the same as TIESCOL but used with option 2
"    in routine DISTLOC.
"
"
define PROBTIESROW as an integer, 1-dimensional array
"    which is the same as TIESROW but used with option 2
"    in routine DISTLOC.
"
"
define TIESCOL as an integer, 1-dimensional array
"    which holds column indices which are currently
"    tied as having the maximum probability of
"    disturbance. Used with option 1 in routine DISTLOC.
"
"
define TIESROW as an integer, 1-dimensional array
"    which holds row indices which are currently
"    tied as having the maximum probability of
"    disturbance. Used with option 1 in routine DISTLOC.
"
"
define ZEROTROW as an integer, 1-dimensional array
"    which holds row indices which are currently
"    tied as having a zero value in the disturbance
"    probability map.
"
"
define ZEROTCOL as an integer, 1-dimensional array
"    which holds column indices which are currently
"    tied as having a zero value in the disturbance
"    probability map.
"
"
RANDOM STEP VARIABLES
"
"
the system has an EMPIR_INTERVAL random step variable
"    define EMPIR_INTERVAL as an integer variable
"    which contains the empirical distribution of the
"    number of years between disturbances
"
"
FUNCTIONS
"
"
define CAN_CHECK as integer function
"    which keeps the disturbance from spreading off the map
"    or onto pixels that have already been disturbed
"
"

```

```

''      TALLIES
''
      tally FREQ.DISTURB_INTERVAL(0 to 30 by 2)
      as the dynamic histogram of DISTURB_INTERVAL
      tally FREQ.DISTURB_SIZE(0 to 15000 by 1000)
      as the dynamic histogram of DISTURB_SIZE
      tally MEAN.DISTURB_INTERVAL as the mean of DISTURB_INTERVAL
      tally MEAN.DISTURB_SIZE as the mean of DISTURB_SIZE
''
''
''      DISPLAY VARIABLES
''
''1      display variables include TEMP_YEAR, TEMP_SIZE,
''1      TEMP_INTERVAL
''
''
end
''
''
''
main
''
''
''
'' READ IN NAME OF PARAMETERS FILE ''
''
''      print 1 line thus
TYPE NAME OF PARAMETERS FILE:
      read PARAMS_FILE_NAME
''
''
''
'' READ IN PARAMETERS AND RESERVE SPACE ''
''
''      This section of the program reads in the model parameters
''      from the parameters file. These parameters are:
''
''      Line 1: XXXX XXXX      Starting year and stopping year
''                          for model run
''
''      Line 2: XXXX XXXX      Row and column dimensions (in
''                          pixels) of the model area
''
''      Line 3: XX XX XX XX    Random number streams for the:
''                          (1) size distribution
''                          (2) disturbance interval
''                          distribution
''                          (3) location algorithm DISTLOC
''                          (4) sampling interval distribution
''
''      Line 4: X..X(20 chars) Run identification
''
''      Line 5: X..X(20 chars) Name of starting map layer
''
''      Line 6: X              Display map output during the model
''                          run?
''                          1 - do display
''                          2 - don't display
''

```

```

Line 7: XXXX Mean for the exponential size
distribution

Line 8: XXX.X XXX.X Shape and scale parameters for
the Weibull interval distribution

Line 9: X Disturbance intervals?
1 - Weibull distribution
2 - empirical distribution

Line 10: XXXX XXXX XXXX (1) Number of years to skip before saving
a new copy of a particular layer in
the GRASS GIS for later display and
analysis
(2) Last year a new copy of a particular
layer was saved. Normally set equal
to the starting year for the model run
(3) Last year that landscape structure
was analyzed. Normally set equal to the
starting year for the model run

Line 11: XXX.XX XXX.XX Mean and standard deviation (real) for
normal distribution of time intervals
between measurements of landscape
structure. Set mean=0.0 if no
measurement is desired. Set standard
deviation =0.0 if fixed interval is
desired

Line 12: X..X(80 chars) Landscape structure distance measure
(Gle.dist) and parameters. Put 999 if
not used. Enclose whole expression in
single quotes ('').

Line 13: X..X(80 chars) Landscape structure patch measure
(Gle.patch) and parameters. Put 999 if
not used. Enclose whole expression in
single quotes ('').

Line 14: X..X(80 chars) Landscape structure texture measure
(Gle.tex) and parameters. Put cd 999 if
not used. Enclose whole expression in
single quotes ('').

Line 15: XXXXXXXX Maximum potential value that raw
disturbance probabilities will reach
during the model run

Line 16: XX.XX Minimum disturbance probability to be
used with option 2 for locating
disturbances

Line 17: X Option for locating disturbances:
1 - the disturbance is located
randomly among locations
that have tied disturbance
probabilities
2 - the disturbance is located
randomly among locations that
have a minimum probability of

```

```

//
//          being disturbed
//          3 - the disturbance is located
//              in a probabilistic manner
//              based on disturbance prob-
//              abilities
//
//
// Line 18: X          Option for spreading disturbances:
//                    1 - the disturbance is spread
//                        to the pixel, among the 8
//                        neighbors, that contains the
//                        highest disturbance
//                        probability.
//                    2 - the disturbance is spread
//                        probabilistically, according
//                        to the disturbance probabi-
//                        lities of the adjoining 8
//                        neighbors.
//
//
// Line 19: X..X (120char) Equation for calculating disturbance
//                    probabilities from the layers in the
//                    GRASS GIS. Used by routine DISTPROB.
//                    Put the right side of the equation
//                    only, and put in single quotes.
//
//
// Line 20+ X.XX XX ... Pairs of cumulative probability and
//                    sample values for the empirical
//                    disturbance interval distribution
//
//
//
//
//          *****
//          * OPEN PARAMETERS FILE FOR INPUT *
//          *****
//
//
// open unit 1 for input, recordsize is 132,
//   file name is PARAMS_FILE_NAME
// use unit 1 for input
// if ropenerr.v <> 0
//   print 1 line thus
//     Unable to open parameters file for input
//   close unit 1
// always
//
//
//          *****
//          * READ IN THE STARTING AND STOPPING YEARS FOR THE *
//          * SIMULATION FROM PARAMETERS FILE LINE 1. *
//          *****
//
//
// read START.YR, STOP.YR
//
//
//
//          *****
//          * READ IN THE ROW & COLUMN DIMENSIONS OF THE *
//          * MAP LAYERS, FROM PARAMETERS FILE LINE 2 *
//          *****
//
//
// read NROW, NCOL
//
//
//
//          *****

```

```

//      * READ IN THE RANDOM NUMBER STREAMS FROM PARAMETERS *
//      * FILE LINE 3 *
//      * * * * *
//
read STM_SIZE, STM_DISTURB, STM_LOC, STM_SAMP
//
//
//      * * * * *
//      * READ IN THE RUN IDENTIFICATION FROM PARAMETERS FILE *
//      * LINE 4 *
//      * * * * *
//
read RUN
//
//
//      * * * * *
//      * READ IN THE STARTING MAP LAYER NAME FROM PARAMETERS *
//      * FILE LINE 5 *
//      * * * * *
//
read INIT_MAP
//
//
//      * * * * *
//      * READ IN THE CHOICE OF WHETHER TO DISPLAY MAP *
//      * OUTPUT DURING THE MODEL RUN FROM PARAMETERS FILE *
//      * LINE 6 *
//      * * * * *
//
read MAP_CHOICE
//
//
//      * * * * *
//      * READ IN THE MEAN FOR THE EXPONENTIAL DISTRIBUTION *
//      * OF POTENTIAL DISTURBANCE SIZES AND THE RANDOM NUMBER*
//      * STREAM FROM PARAMETERS FILE LINE 7 *
//      * * * * *
//
read SIZE_EXPMEAN ,
//
//
//      * * * * *
//      * READ IN THE VALUE OF THE SHAPE AND SCALE PARAMETERS *
//      * FOR THE WEIBULL DISTRIBUTION OF DISTURBANCE *
//      * INTERVALS FROM PARAMETERS FILE LINE 8 *
//      * * * * *
//
read WEIBULL_SHAPE, WEIBULL_SCALE
//
//
//      * * * * *
//      * READ IN THE CHOICE BETWEEN USING A WEIBULL DISTRI- *
//      * BUTION (DISTURB_INTERVAL_CHOICE = 1) OR AN *
//      * EMPIRICAL DISTRIBUTION (DISTURB_INTERVAL_CHOICE = *
//      * 2) OF DISTURBANCE INTERVALS FROM PARAMETERS FILE *
//      * LINE 9 *
//      * * * * *
//
read DISTURB_INTERVAL_CHOICE
//

```

```

//
// *****
// * READ IN HOW MANY YEARS TO SKIP BEFORE SAVING *
// * A LAYER IN GRASS FROM PARAMETERS FILE LINE 10 *
// *****
//
read SAVE_GAP, LAST_SAVE_YR, LAST_SAMP_YR
//
// *****
// * READ IN THE MEAN AND STANDARD DEVIATION FOR A *
// * NORMAL DISTRIBUTION OF TIME INTERVALS BETWEEN *
// * MEASUREMENTS OF LANDSCAPE STRUCTURE FROM PARAMETERS *
// * FILE LINE 11 *
// *****
//
read SAMP_MEAN, SAMP_STDEV
//
// *****
// * READ IN THE LANDSCAPE STRUCTURE MEASURE GLE.DIST *
// * AND ITS PARAMETERS FROM PARAMETERS FILE LINE 12 *
// *****
//
read GLEDIST as T *
//
// *****
// * READ IN THE LANDSCAPE STRUCTURE MEASURE GLE.PATCH *
// * AND ITS PARAMETERS FROM PARAMETERS FILE LINE 13 *
// *****
//
read GLEPATCH as T *
//
// *****
// * READ IN THE LANDSCAPE STRUCTURE MEASURE GLE.TEX *
// * AND ITS PARAMETERS FROM PARAMETERS FILE LINE 14 *
// *****
//
read GLETEX as T *
//
// *****
// * READ IN THE MAXIMUM POTENTIAL VALUE FOR DISTPROB *
// * FROM PARAMETERS FILE LINE 15 *
// *****
//
read DISTMAX
//
// *****
// * READ IN THE MINIMUM DISTURBANCE PROBABILITY FROM *
// * PARAMETERS FILE LINE 16 *
// *****
//
read MINIMUMDIST
//
// *****

```

```

//      * READ IN THE OPTION FOR LOCATING DISTURBANCES FROM *
//      * PARAMETERS FILE LINE 17 *
//      * * * * *
//
read LOC_OPTION

//
//
//      * * * * *
//      * READ IN THE OPTION FOR SPREADING DISTURBANCES FROM *
//      * PARAMETERS FILE LINE 18 *
//      * * * * *
//
read SPREAD_OPTION

//
//
//      * * * * *
//      * READ IN THE FORMULA FOR CALCULATING DISTURBANCE *
//      * PROBABILITIES FROM PARAMETERS FILE LINE 19 *
//      * * * * *
//
read FORMULA

//
//
//      * * * * *
//      * READ IN THE EMPIRICAL PROBABILITY DISTRIBUTION FOR *
//      * DISTURBANCE INTERVALS FROM PARAMETERS FILE LINES *
//      * 20+. *
//      * * * * *
//
read EMPIR_INTERVAL
close unit 1

//
//
//
//      * * * * *
//      * OPEN UNIT 2 FOR OUTPUT OF DISTURBANCE INFO *
//      * * * * *
//
let DISTURB_TEMP = "disturb."
let DISTURB_OUT = concat.f(DISTURB_TEMP,RUN)
open unit 2 for output,
  file name is DISTURB_OUT
use unit 6 for output

//
//
//
//      * * * * *
//      * ALLOCATE MEMORY FOR ARRAYS *
//      * * * * *
//
reserve DISTPROB_CUM(*,*) as NROW by NCOL
reserve DISTPROB_INT(*,*) as NROW by NCOL
reserve DISTPROB_REAL(*,*) as NROW by NCOL
reserve DISTMAP(*,*) as NROW by NCOL
reserve PROBTIESROW(*) as (NROW * NCOL)
reserve PROBTIESCOL(*) as (NROW * NCOL)
reserve TIESROW(*) as 8
  reserve TIESCOL(*) as 8
reserve ZEROTROW(*) as 8
reserve ZEROTCOL(*) as 8

```



```
//
//
//
//
////////////////////////////////////////////////////////////////
'' MAIN PROGRAM
////////////////////////////////////////////////////////////////
//
//
// *****
// * INITIALIZE GRAPHICS ICONS TO DISPLAY HISTOGRAM
// * OUTPUT DURING THE MODEL RUN
// *****
//
//'1 display TEMP_YEAR with "Zyear.grf"
//'1 display TEMP_INTERVAL with "Zintmean.grf"
//'1 display TEMP_SIZE with "Zsizemean.grf"
//'1 show histogram FREQ.DISTURB_SIZE with "Zsizehist.grf"
//'1 show histogram FREQ.DISTURB_INTERVAL
//'1     with "Zinthist.grf"
//
//
// *****
// * INITIALIZE DISTURB_YR AND THE LAYER WITH WHICH THE
// * MODEL BEGINS, GET THE FIRST DISTURBANCE INTERVAL,
// * INITIALIZE THE DISTURBANCE MAP, MEASURE THE
// * LANDSCAPE STRUCTURE OF THE INITIAL MAP IF SAMPLING
// * WAS REQUESTED, AND GET THE FIRST SAMPLING INTERVAL
// *****
//
let DISTURB_YR = START.YR - 1
call initlayer given INIT_MAP
call DISTINCT
call initdistmap

let YR_TXT1 = ITOT.F(START.YR)
let RUN_YR = CONCAT.F(RUN,"_",YR_TXT1)

if LAST_SAMP_YR = START.YR
    call sstruct given RUN_YR, GLEDIST, GLEPATCH, GLETEx
always

if LAST_SAVE_YR = START.YR
    call save_grass_layer given RUN_YR
always

call SAMPINT

////////////////////////////////////////////////////////////////
//          START THE ANNUAL LOOP
//          ,
//
for YEAR = START.YR to STOP.YR
do

// *****
// * CONCATENATE THE RUN IDENTIFICATION AND YEAR TO USE
// * IN NAMING OUTPUT FILES
// *****
//
```

```

let YR_TXT1 = ITOT.F(YEAR)
let RUN_YR = CONCAT.F(RUN,"_",YR_TXT1)

//

let TEMP_YEAR = YEAR

//

//
*****
//
* PRINT INFORMATION ABOUT THE YEAR AND DISTURBANCES *
//
*****
//

print 2 lines with YEAR, DISTURB_YR, DISTURB_INTERVAL thus
*****
START OF YR ****, LAST DISTURB YR ****, DISTURB INTERV **** YEARS
//

//
*****
//
* IF THE REQUIRED DISTURBANCE INTERVAL HAS PASSED *
//
* THEN: *
//
* 1. GENERATE A DISTURBANCE AND RECORD THE YEAR *
//
* 2. PRINT THE DISTURBANCE INTERVAL AND SIZE *
//
* 3. WRITE OUT THE DISTURBANCE YEAR, SIZE, AND *
//
* INTERVAL *
//
* 4. INITIALIZE THE DISTURBANCE MAP *
//
* 5. CALCULATE THE DISTURBABILITY OF THE LANDSCAPE *
//
* 6. LOCATE THE DISTURBANCE IN THE LANDSCAPE *
//
* 7. SPREAD THE DISTURBANCE *
//
* 8. UPDATE THE AGE LAYER IN THE GIS *
//
* 9. DETERMINE THE NEXT DISTURBANCE INTERVAL *
//
* 10. END THE DISTURBANCE OPERATIONS *
//
*****
//

If ((YEAR - DISTURB_YR) = DISTURB_INTERVAL)

//

//
*****
//
* 1. Generate a disturbance and store the year, then *
//
* use a temporary variable to produce a display of *
//
* the cumulative mean disturbance size if the choice *
//
* was made to display graphic output during the model *
//
* run *
//
*****
//

Call DISTGEN
let DISTURB_YR = YEAR
let TEMP_SIZE = MEAN.DISTURB_SIZE

//

//
*****
//
* 2. Print the disturbance size *
//
*****
//

print 1 line with DISTURB_SIZE thus
DISTURB SIZE ****.* PIXELS
//

//
*****
//
* 3. Write the disturbance year, disturbance size, *
//
* and disturbance interval to a file *
//
*****
//

```

```

write YEAR, DISTURB_SIZE, DISTURB_INTERVAL as
I 4, S 2, D(8,1), S 2, I 4,/ using unit 2

**
**
**
**
*****
** * 4. Initialize the disturbance map *
*****
**
**
    let i = 0
    while i < NROW
    do
        let i = i + 1
        let j = 0
        while j < NCOL
        do
            let j = j + 1
            let DISTMAP (i, j) = 1
        loop
    loop

**
**
**
*****
** * 5. Calculate the disturbability of the landscape *
*****
**
**
    call DISTPROB

**
**
**
*****
** * 6. Locate the disturbance in the landscape. *
*****
**
**
    call DISTLOC

**
**
**
*****
** * 7. Check to see if DISTPROB contains only 0's. If *
** * so, do nothing. If DISTPROB contains disturbable *
** * pixels, then spread the disturbance *
*****
**
**
    if R = 0
        print 1 line thus
            DISTPROB ALL 0's-NO DISTURBANCE
    else
        call DISTSPR

**
**
**
*****
** * 8. Update the age layer in the GRASS GIS to reflect *
** * the effects of the disturbance. Use the following *
** * external routines to do this: *
** * a. call putnum writes distmap.ascii, an ASCII *
** * version of the DISTMAP array. *
** * b. call write_ascii reads in distmap.ascii, and *
** * writes out distmap whdr.ascii, which *

```

```

//      *      contains the header information needed      *
//      *      to read DISTMAP data into GRASS.            *
//      *      c. call update_map reads distmap_whdr.ascii into*
//      *      GRASS using the GRASS Mimportcell          *
//      *      command, and then uses the Gmapcalc        *
//      *      command to change all the disturbed       *
//      *      locations in the AGE map to AGE=0          *
//      *      *****
//
//
//      for i = 1 to NROW
//      do
//          for j = 1 to NCOL
//          do
//              call putnum (DISTMAP(i,j), NROW, j, i)
//          loop
//      loop
//      call write_ascii
//      call update_map
//      always
//
//
//
//      *****
//      * 9. Determine the next disturbance interval, then *
//      * use a temporary variable to produce the display of *
//      * cumulative mean disturbance interval if the choice *
//      * was made to display graphic output during the model *
//      * run                                                *
//      * *****
//
//
//      Call DISTINT
//      let TEMP_INTERVAL = MEAN.DISTURB_INTERVAL
//
//
//
//
//
//      *****
//      * 10. End the operations that were done only if the *
//      * disturbance interval had passed and a new disturb- *
//      * ance had occurred                                  *
//      * *****
//
//
//      always
//
//
//
//      *****
//      * BEGIN THE OPERATIONS THAT HAPPEN EVERY YEAR      *
//      * REGARDLESS OF DISTURBANCE. THESE INCLUDE:        *
//      * 1. DISPLAY THE LAST DISTURBANCE MAP AND THE      *
//      *   CURRENT MAP IF GRAPHIC OUTPUT WAS              *
//      *   REQUESTED DURING THE MODEL RUN                  *
//      * 2. SAVE THE MAP FOR LATER ANALYSIS, IF THE      *
//      *   INTERVAL TO SKIP BEFORE SAVING HAS PASSED     *
//      * 3. ADD A YEAR TO THE AGE OF EACH PIXEL IN THE    *
//      *   AGE LAYER OF THE GRASS GIS                      *
//      * 4. PRINT INFORMATION ABOUT SAMPLING              *
//      * 5. ANALYZE LANDSCAPE STRUCTURE IF IT'S TIME      *
//      * *****

```

```

//
//
// *****
// * 1. Display the last disturbance map and the current *
// * age map if graphic output was requested during the *
// * model run. Use external routines to do this *
// *****
//
//     if MAP_CHOICE = 1
//         call reclass_map
//         call show_map given RUN_YR
//     always
//
//
// *****
// * 2. Save a map for later analysis, if the time *
// * interval to skip before saving has passed. Use an *
// * external routine to save the map. *
// *****
//
//     if ((YEAR-LAST_SAVE_YR) = SAVE_GAP)
//         call save_grass_layer given RUN_YR
//         let LAST_SAVE_YR = YEAR
//     always
//
//
// *****
// * 3. Add a year to the age of each pixel in the age *
// * layer of the GRASS GIS. Use an external routine *
// * called annual_updt, which uses the GRASS Gmapcalc *
// * command to add 1 to every pixel in the AGE map *
// *****
//
//     call annual_updt
//
// *****
// * 4. Print information about sampling *
// *****
//
//     print 1 line with YEAR, LAST_SAMP_YR, SAMP_INTERVAL thus
// MIDDLE OF YR ****, LAST SAMPLING YR ****, SAMPLING INTERV **** YEARS
//
// *****
// * 5. Analyze landscape structure using the external *
// * routine sstruct if it's time to do so. *
// *****
//
//     if ((YEAR-LAST_SAMP_YR) = SAMP_INTERVAL)
//         call sstruct given RUN_YR, GLEDIST, GLEPATCH, GLETEX
//         let LAST_SAMP_YR = YEAR
//         call SAMPINT
//     always
//
//
// *****
// * END THE ANNUAL LOOP AND THE MAIN PROGRAM *
// *****
//

```

```

print 4 lines with YEAR thus
END OF YEAR ****
-----

      if YEAR = STOP.YR
        if LAST_SAVE_YR <> STOP.YR
          call save_grass_layer given RUN_YR
        always
        if LAST_SAMP_YR <> STOP.YR
          call sstruct given RUN_YR, GLEDIST, GLEPATCH, GLETENX
        always
      always
    loop
end
''
''
''
''
''
''
''
''
ROUTINES
''
routine DISTGEN
''
''
*****
* THIS ROUTINE SELECTS A DISTURBANCE SIZE FROM AN *
* EXPONENTIAL DISTRIBUTION OF DISTURBANCE SIZES WHOSE *
* MEAN IS SIZE_EXPMEAN *
*****
let DISTURB_SIZE = EXPONENTIAL.F(SIZE_EXPMEAN,STM_SIZE)
return
end
''
''
''
''
routine DISTINCT
''
''
*****
* THIS ROUTINE SELECTS A DISTURBANCE INTERVAL FROM A *
* WEIBULL DISTRIBUTION WHOSE PARAMETERS ARE *
* WEIBULL_SCALE AND WEIBULL_SHAPE (IF DISTURB_INTER- *
* VAL_CHOICE EQUALS 1), OR FROM AN EMPIRICAL *
* DISTRIBUTION (IF DISTURB_INTERVAL_CHOICE EQUALS 2) *
*****
if DISTURB_INTERVAL_CHOICE = 0
' print 1 line thus
No disturbance interval distribution selected!
always
if DISTURB_INTERVAL_CHOICE = 1
let DISTURB_INTERVAL =
TRUNC.F(WEIBULL.F(WEIBULL_SHAPE,WEIBULL_SCALE,STM_DISTURB))
always
if DISTURB_INTERVAL_CHOICE = 2
let DISTURB_INTERVAL = EMPIR_INTERVAL
```

```

        always
        return
end
//
//
//
routine DISTLOC
//
// *****
// * THIS ROUTINE INITIATES THE DISTURBANCE WITHIN A *
// * SINGLE CELL USING THREE OPTIONS: *
// * 1. THE DISTURBANCE IS INITIATED RANDOMLY *
// * AMONG TIED OCCURRENCES (IF THERE ARE ANY) OF *
// * MAXIMUM DISTURBANCE PROBABILITY. *
// * 2. THE DISTURBANCE IS INITIATED RANDOMLY *
// * AMONG THOSE CELLS THAT HAVE SOME MINIMUM *
// * PROBABILITY OF BEING DISTURBED. IF THERE ARE *
// * NO CELLS ABOVE THE MINIMUM VALUE, THEN NO *
// * DISTURBANCE OCCURS *
// * 3. THE DISTURBANCE IS INITIATED IN A PROB- *
// * ABILISTIC WAY. EACH CELL HAS A CHANCE OF *
// * BEING DISTURBED THAT IS PROPORTIONAL TO ITS *
// * DISTURBABILITY (DISTPROB) VALUE. *
// *****
//
//
// *****
// * Initialize PROBTIESROW, PROBTIESCOL, and TIES *
// *****
//
for i = 1 to (NROW * NCOL)
do
    let PROBTIESROW(i) = 0
    let PROBTIESCOL(i) = 0
loop
let TIES = 0
//
//
// *****
// * Option number 1 *
// *****
//
if LOC_OPTION = 1
//
//
// a. Initialize the variables
//
i = 0
let MAX_DISTPROB=0.0
let MAX_LOC_ROW=0
let MAX_LOC_COL=0
//
//
// b. Search the disturbance probability array for the maximum
// value
//
while i < NROW
do
    i = i + 1
    j = 0

```

```

while j < NCOL
do
  j = j + 1
  if DISTPROB_REAL(i, j) > MAX_DISTPROB
    let MAX_DISTPROB = DISTPROB_REAL (i, j)
    let MAX_LOC_ROW = i
    let MAX_LOC_COL = j
    let TIES = 1
    let PROBTIESROW(1) = i
    let PROBTIESCOL(1) = j
  else
    if DISTPROB_REAL(i, j) = MAX_DISTPROB
      let TIES = TIES + 1
      let PROBTIESROW(TIES) = i
      let PROBTIESCOL(TIES) = j
    always
  always
loop
loop

c. Then set that location in the disturbance map layer,
DISTMAP, equal to 0, unless there are ties. If so, then
use the random number generator to choose among the ties

  if TIES = 1
    let DISTMAP(MAX_LOC_ROW,MAX_LOC_COL)=0
    let R = MAX_LOC_ROW
    let C = MAX_LOC_COL
  else
    let MAXR = RANDI.F (1, TIES, STM_LOC)
    let R = PROBTIESROW (MAXR)
    let C = PROBTIESCOL (MAXR)
    let DISTMAP(R, C) = 0
  always

always

*****
* Option number 2
*****

if LOC_OPTION = 2

a. Initialize the variables

TIES = 0
i = 0

b. Search the disturbance probability array for all cells
that have a value above the minimum value for disturbance

while i < NROW
do
  i = i + 1
  j = 0
  while j < NCOL

```



```

do
  j = j + 1
  if DISTPROB_REAL(i, j) > MINIMUMDIST
    let TIES = TIES + 1
    let PROBTIESROW(TIES) = i
    let PROBTIESCOL(TIES) = j
  always
loop
loop
//
//
// c. If there are no ties, then no location is disturbable.
// Otherwise choose randomly among the tied locations.
//
//
if TIES = 0
  let R = 0
  let C = 0
else
  let MAXR = RANDI.F (1, TIES, STM_LOC)
  let R = PROBTIESROW (MAXR)
  let C = PROBTIESCOL (MAXR)
  let DISTMAP(R, C) = 0
always
//
always
//
//
// *****
// * Option number 3 *
// *****
//
//
if LOC_OPTION = 3
//
//
// a. initialize variables and arrays
//
//
let DISTPROB_SUM = 0.0
//
let i = 0
while i < NROW
do
  let i = i + 1
  let j = 0
  while j < NCOL
do
  let j = j + 1
  let DISTPROB_CUM(i, j) = 0.0
loop
loop
//
//
//
// b. sum up the disturbance probabilities in the
// DISTPROB_REAL layer, and make a new layer,
// DISTPROB_CUM, which contains cumulative sums of
// the values in DISTPROB_REAL
//
//
let i = 0
while i < NROW
do
  let i = i + 1
  let j = 0

```

```

        while j < NCOL
        do
            let j = j + 1
            let DISTPROB_SUM = DISTPROB_SUM + DISTPROB_REAL(i,j)
            let DISTPROB_CUM(i,j) = DISTPROB_SUM
        loop
    loop

    c. select a random number between 0 and the total of all
    the disturbance probabilities (DISTPROB_SUM), then find
    the cell in the DISTPROB_CUM layer that corresponds to
    that random number. This is the cell where the disturb-
    ance is initiated.

    let RAND_LOC_VAL = UNIFORM.F(0.0, DISTPROB_SUM, STM_LOC)

    let i = 0
    let DONE = 0
    while (i < NROW) AND (DONE = 0)
    do
        let i = i + 1
        let j = 0
        while (j < NCOL) AND (DONE = 0)
        do
            let j = j + 1
            if RAND_LOC_VAL <= DISTPROB_CUM(i,j)
            then
                let R = i
                let C = j
                let DISTMAP(R,C) = 0
                let DONE = 1
            always
        loop
    loop

    always
return

end

routine DISTPROB
**
** *****
** * THIS ROUTINE CALCULATES THE DISTURBABILITY OF THE *
** * LANDSCAPE BY CALLING EXTERNAL ROUTINES TO *
** * COMBINE THE GRASS LAYERS TO PRODUCE A MAP OF *
** * DISTURBANCE PROBABILITIES. *
** *****
**
**
** 1. Call the external routine make_distprob to read
** the equation for calculating disturbance prob-
** abilities, to use the GRASS Gmapcalc command to
** calculate disturbance probabilities, to create
** a new GRASS layer called DISTPROB, and to write it
** out as an ASCII file called distprob.ascii
**
** call make_distprob given FORMULA

```

```

//
//      2. Read in DISTPROB_INT from unit 10. Note that the
//      "recordsize" is the maximum length of what SIMSCRIPT
//      assumes are variable-length records. Make this
//      number more than three times the number of columns
//      in the model area
//

      open unit 10 for input, recordsize is 2000,
        file name is "/home/grass3.1/sim/distprob.ascii"
      use unit 10 for input
      if ropenerr.v <> 0
        print 1 line thus
          Unable to open distprob.ascii for input
        close unit 10
      always
      for i = 1 to NROW
      do
        for j = 1 to NCOL
        do
          read BUF using unit 10
          let DISTPROB_INT(i,j) = BUF
        loop
      loop
      close unit 10

//
//
//
//      3. Relativize raw DISTPROB_INT values using DISTMAX.
//      Put relativized values in DISTPROB_REAL.
//

      for i = 1 to NROW
      do
        for j = 1 to NCOL
        do
          if (DISTMAX = 0.0)
            print 1 line thus
              DISTMAX is 0.0 - Can't divide by it.
          else
            let DISTPROB_REAL(i,j) =
              REAL.F(DISTPROB_INT(i,j))/DISTMAX
          always
        loop
      loop

end
//
//
//
routine DISTSPR
//
//      * * * * *
//      * THIS ROUTINE USES A SPREAD ALGORITHM TO MOVE THE *
//      * DISTURBANCE TO ADJOINING CELLS, UNTIL THE DISTURB- *
//      * ANCE SIZE IS EQUAL TO THE POTENTIAL DISTURBANCE *
//      * SIZE. AT EACH LOCATION THE ALGORITHM LOOKS ONLY AT *
//      * THOSE NEIGHBORS THAT ARE NOT OFF THE EDGE OF THE *
//      * MAP AND ARE NOT ALREADY DISTURBED. THERE ARE TWO *
//      * OPTIONS: *
//      * 1. SPREAD THE DISTURBANCE TO THE PIXEL WITH THE *
//      * HIGHEST DISTURBANCE PROBABILITY. *
//      * 2. SPREAD THE DISTURBANCE PROBABILISTICALLY WITH *
//      * THE PROBABILITY OF SPREAD TO A PIXEL PROP- *

```

```

//      *      ORTIONAL TO ITS DISTURBANCE PROBABILITY      *
//      *      *      *      *      *      *      *      *      *
//
//
//      *      *      *      *      *      *      *      *      *
//      * Option number 1                                     *
//      *      *      *      *      *      *      *      *      *
//
//
//      if SPREAD_OPTION = 1
//
//
//      a. initialize variables
//
//      let CURRENT_DISTURB_SIZE = 1
//      let DISTPROB_REAL (R, C) = 0.0
//
//
//      b. check to see if disturbance has completed spreading
//
//      while (CURRENT_DISTURB_SIZE < trunc.f(DISTURB_SIZE))
//
//
//      c. enter the main 8 neighbor search loop
//
//      do
//
//      let TIES = 0
//      let MAX = 0.0
//      let ZEROTIES = 0
//
//
//      if CAN_CHECK (R + 1, C + 1) = 1
//      if (DISTMAP(R + 1, C + 1) = 0)
//      let ZEROTIES = ZEROTIES + 1
//      let ZEROTROW (ZEROTIES) = R + 1
//      let ZEROTCOL (ZEROTIES) = C + 1
//      let PREVDIST_ROW = R + 1
//      let PREVDIST_COL = C + 1
//      else
//      if DISTPROB_REAL (R + 1, C + 1) > MAX
//      let TIES = 1
//      let TIESROW (TIES) = R + 1
//      let TIESCOL (TIES) = C + 1
//      let MAX = DISTPROB_REAL (R + 1, C + 1)
//      else
//      if (DISTPROB_REAL(R + 1, C + 1) = MAX)
//      let TIES = TIES + 1
//      let TIESROW (TIES) = R + 1
//      let TIESCOL (TIES) = C + 1
//      always
//      always
//      always
//
//
//      if CAN_CHECK (R, C + 1) = 1
//      if (DISTMAP(R, C + 1) = 0)
//      let ZEROTIES = ZEROTIES + 1
//      let ZEROTROW (ZEROTIES) = R
//      let ZEROTCOL (ZEROTIES) = C + 1
//      let PREVDIST_ROW = R
//      let PREVDIST_COL = C + 1
//      else

```

```

if DISTPROB_REAL (R, C + 1) > MAX
    let TIES = 1
    let TIESROW (TIES) = R
    let TIESCOL (TIES) = C + 1
    let MAX = DISTPROB_REAL (R, C + 1)
else
    if (DISTPROB_REAL(R, C + 1) = MAX)
        let TIES = TIES + 1
        let TIESROW (TIES) = R
        let TIESCOL (TIES) = C + 1
    always
always
always
//

if CAN_CHECK (R - 1, C + 1) = 1
    if (DISTMAP(R - 1, C + 1) = 0)
        let ZEROTIES = ZEROTIES + 1
        let ZEROTROW (ZEROTIES) = R - 1
        let ZEROTCOL (ZEROTIES) = C + 1
        let PREVDIST_ROW = R - 1
        let PREVDIST_COL = C + 1
    else
        if DISTPROB_REAL (R - 1, C + 1) > MAX
            let TIES = 1
            let TIESROW (TIES) = R - 1
            let TIESCOL (TIES) = C + 1
            let MAX = DISTPROB_REAL (R - 1, C + 1)
        else
            if (DISTPROB_REAL(R - 1, C + 1) = MAX)
                let TIES = TIES + 1
                let TIESROW (TIES) = R - 1
                let TIESCOL (TIES) = C + 1
            always
        always
always
always
//

if CAN_CHECK (R + 1, C) = 1
    if (DISTMAP(R + 1, C) = 0)
        let ZEROTIES = ZEROTIES + 1
        let ZEROTROW (ZEROTIES) = R + 1
        let ZEROTCOL (ZEROTIES) = C
        let PREVDIST_ROW = R + 1
        let PREVDIST_COL = C
    else
        if DISTPROB_REAL (R + 1, C) > MAX
            let TIES = 1
            let TIESROW (TIES) = R + 1
            let TIESCOL (TIES) = C
            let MAX = DISTPROB_REAL (R + 1, C)
        else
            if (DISTPROB_REAL(R + 1, C) = MAX)
                let TIES = TIES + 1
                let TIESROW (TIES) = R + 1
                let TIESCOL (TIES) = C
            always
        always
always
always
always

```

```

if CAN_CHECK (R - 1, C) = 1
  if (DISTMAP(R - 1, C) = 0)
    let ZEROTIES = ZEROTIES + 1
    let ZEROTROW (ZEROTIES) = R - 1
    let ZEROTCOL (ZEROTIES) = C
    let PREVDIST_ROW = R - 1
    let PREVDIST_COL = C
  else
    if DISTPROB_REAL (R - 1, C) > MAX
      let TIES = 1
      let TIESROW (TIES) = R - 1
      let TIESCOL (TIES) = C
      let MAX = DISTPROB_REAL (R - 1, C)
    else
      if (DISTPROB_REAL(R - 1, C) = MAX)
        let TIES = TIES + 1
        let TIESROW (TIES) = R - 1
        let TIESCOL (TIES) = C
      always
    always
  always
always

if CAN_CHECK (R + 1, C - 1) = 1
  if (DISTMAP(R + 1, C - 1) = 0)
    let ZEROTIES = ZEROTIES + 1
    let ZEROTROW (ZEROTIES) = R + 1
    let ZEROTCOL (ZEROTIES) = C - 1
    let PREVDIST_ROW = R + 1
    let PREVDIST_COL = C - 1
  else
    if DISTPROB_REAL (R + 1, C - 1) > MAX
      let TIES = 1
      let TIESROW (TIES) = R + 1
      let TIESCOL (TIES) = C - 1
      let MAX = DISTPROB_REAL (R + 1, C - 1)
    else
      if (DISTPROB_REAL(R + 1, C - 1) = MAX)
        let TIES = TIES + 1
        let TIESROW (TIES) = R + 1
        let TIESCOL (TIES) = C - 1
      always
    always
  always
always

if CAN_CHECK (R, C - 1) = 1
  if (DISTMAP(R, C - 1) = 0)
    let ZEROTIES = ZEROTIES + 1
    let ZEROTROW (ZEROTIES) = R
    let ZEROTCOL (ZEROTIES) = C - 1
    let PREVDIST_ROW = R
    let PREVDIST_COL = C - 1
  else
    if DISTPROB_REAL (R, C - 1) > MAX
      let TIES = 1
      let TIESROW (TIES) = R
      let TIESCOL (TIES) = C - 1
      let MAX = DISTPROB_REAL (R, C - 1)

```

```

else
  if (DISTPROB_REAL(R, C - 1) = MAX)
    let TIES = TIES + 1
    let TIESROW (TIES) = R
    let TIESCOL (TIES) = C - 1
  always
always
always
//
if CAN_CHECK (R - 1, C - 1) = 1
  if (DISTMAP(R - 1, C - 1) = 0)
    let ZEROTIES = ZEROTIES + 1
    let ZEROTROW (ZEROTIES) = R - 1
    let ZEROTCOL (ZEROTIES) = C - 1
    let PREVDIST_ROW = R - 1
    let PREVDIST_COL = C - 1
  else
    if DISTPROB_REAL (R - 1, C - 1) > MAX
      let TIES = 1
      let TIESROW (TIES) = R - 1
      let TIESCOL (TIES) = C - 1
      let MAX = DISTPROB_REAL (R - 1, C - 1)
    else
      if (DISTPROB_REAL(R - 1, C - 1) = MAX)
        let TIES = TIES + 1
        let TIESROW (TIES) = R - 1
        let TIESCOL (TIES) = C - 1
      always
    always
  always
always
//
//
//
d. If at least one of the 8 neighbors has a disturbance
probability > 0.0
//
//
if MAX > 0.0
//
//
//
(1) If there is more than one neighboring pixel
already disturbed or the disturbance has
reached only 1 or 2 pixels, we're not on
a "peninsula" or the disturbance has just
started. Then find the maximum disturbance
probability by randomly choosing among tied
values. Disturb that pixel, move to it, and
add one to the count of disturbance size.
//
//
if (ZEROTIES > 1) OR (CURRENT_DISTURB_SIZE < 3)
  let MAXR = RANDI.F (1, TIES, 1)
  let R = TIESROW (MAXR)
  let C = TIESCOL (MAXR)
  let DISTMAP(R, C) = 0
  let DISTPROB_REAL(R, C) = 0.0
  let CURRENT_DISTURB_SIZE = CURRENT_DISTURB_SIZE + 1
//
//
//
(2) If there is only one neighboring pixel already
disturbed and if the disturbance has reached

```

```

    at least 3 pixels, then a "peninsula" could form.
    To stop this, move back to the already
    disturbed neighboring pixel and try to spread
    from there.

    else
        let R = PREVDIST_ROW
        let C = PREVDIST_COL
    always

e. If all the neighboring pixels have a disturbance
probability of 0.0, this means that they have all
been disturbed already or have no probability
of being disturbed. Then choose randomly among
the 8 neighbors and move to that pixel.

    else
        let MAXR = RANDI.F (1, ZEROTIES, 3)
        let R = ZEROTROW (MAXR)
        let C = ZEROTCOL (MAXR)
    always

loop

always

*****
* Option number 2 *
*****

if SPREAD_OPTION = 2

a. initialize variables

let CURRENT_DISTURB_SIZE = 1
let DISTPROB_REAL(R,C) = 0.0

b. check to see if disturbance has completed spreading

while (CURRENT_DISTURB_SIZE < trunc.f(DISTURB_SIZE))

c. total up the disturbance probabilities in the eight
neighbor cells. first checking to be sure the cell is
not off the map and has not already been disturbed.
Count up the number of 0.0 probabilities and keep
track of where previously disturbed cells are.

do
    let ZEROTIES = 0
    let PREVDIST_ROW = 0
    let PREVDIST_COL = 0
    let DISTPROB_TOT = 0.0

    if CAN_CHECK (R-1,C-1) = 1
        if (DISTMAP(R-1,C-1) = 1)

```



```

        let DISTPROB_TOT = DISTPROB_REAL(R-1,C-1) + DISTPROB_TOT
        let DISTPROB_CUM(R-1,C-1) = 0.0
        let DISTPROB_CUM(R-1,C-1) = DISTPROB_TOT
    else
        let DISTPROB_CUM(R-1,C-1) = 0.0
        let ZEROTIES = ZEROTIES + 1
        let ZEROTROW (ZEROTIES) = R - 1
        let ZEROTCOL (ZEROTIES) = C - 1
        let PREVDIST_ROW = R - 1
        let PREVDIST_COL = C - 1
    always
always
//

if CAN_CHECK (R-1,C) = 1
    if (DISTMAP(R-1,C) = 1)
        let DISTPROB_TOT = DISTPROB_REAL(R-1,C) + DISTPROB_TOT
        let DISTPROB_CUM(R-1,C) = 0.0
        let DISTPROB_CUM(R-1,C) = DISTPROB_TOT
    else
        let DISTPROB_CUM(R-1,C) = 0.0
        let ZEROTIES = ZEROTIES + 1
        let ZEROTROW (ZEROTIES) = R-1
        let ZEROTCOL (ZEROTIES) = C
        let PREVDIST_ROW = R-1
        let PREVDIST_COL = C
    always
always
//

if CAN_CHECK (R-1,C+1) = 1
    if (DISTMAP(R-1,C+1) = 1)
        let DISTPROB_TOT = DISTPROB_REAL(R-1,C+1) + DISTPROB_TOT
        let DISTPROB_CUM(R-1,C+1) = 0.0
        let DISTPROB_CUM(R-1,C+1) = DISTPROB_TOT
    else
        let DISTPROB_CUM(R-1,C+1) = 0.0
        let ZEROTIES = ZEROTIES + 1
        let ZEROTROW (ZEROTIES) = R-1
        let ZEROTCOL (ZEROTIES) = C+1
        let PREVDIST_ROW = R-1
        let PREVDIST_COL = C+1
    always
always
//

if CAN_CHECK (R,C-1) = 1
    if (DISTMAP(R,C-1) = 1)
        let DISTPROB_TOT = DISTPROB_REAL(R,C-1) + DISTPROB_TOT
        let DISTPROB_CUM(R,C-1) = 0.0
        let DISTPROB_CUM(R,C-1) = DISTPROB_TOT
    else
        let DISTPROB_CUM(R,C-1) = 0.0
        let ZEROTIES = ZEROTIES + 1
        let ZEROTROW (ZEROTIES) = R
        let ZEROTCOL (ZEROTIES) = C-1
        let PREVDIST_ROW = R
        let PREVDIST_COL = C-1
    always
always
//

if CAN_CHECK (R,C+1) = 1
    if (DISTMAP(R,C+1) = 1)

```

```

    let DISTPROB_TOT = DISTPROB_REAL(R,C+1) + DISTPROB_TOT
    let DISTPROB_CUM(R,C+1) = 0.0
    let DISTPROB_CUM(R,C+1) = DISTPROB_TOT
else
    let DISTPROB_CUM(R,C+1) = 0.0
    let ZEROTIES = ZEROTIES + 1
    let ZEROTROW (ZEROTIES) = R
    let ZEROTCOL (ZEROTIES) = C+1
    let PREVDIST_ROW = R
    let PREVDIST_COL = C+1
always
always
"

if CAN_CHECK (R+1,C-1) = 1
if (DISTMAP(R+1,C-1) = 1)
    let DISTPROB_TOT = DISTPROB_REAL(R+1,C-1) + DISTPROB_TOT
    let DISTPROB_CUM(R+1,C-1) = 0.0
    let DISTPROB_CUM(R+1,C-1) = DISTPROB_TOT
else
    let DISTPROB_CUM(R+1,C-1) = 0.0
    let ZEROTIES = ZEROTIES + 1
    let ZEROTROW (ZEROTIES) = R+1
    let ZEROTCOL (ZEROTIES) = C-1
    let PREVDIST_ROW = R+1
    let PREVDIST_COL = C-1
always
always
"

if CAN_CHECK (R+1,C) = 1
if (DISTMAP(R+1,C) = 1)
    let DISTPROB_TOT = DISTPROB_REAL(R+1,C) + DISTPROB_TOT
    let DISTPROB_CUM(R+1,C) = 0.0
    let DISTPROB_CUM(R+1,C) = DISTPROB_TOT
else
    let DISTPROB_CUM(R+1,C) = 0.0
    let ZEROTIES = ZEROTIES + 1
    let ZEROTROW (ZEROTIES) = R+1
    let ZEROTCOL (ZEROTIES) = C
    let PREVDIST_ROW = R+1
    let PREVDIST_COL = C
always
always
"

if CAN_CHECK (R+1,C+1) = 1
if (DISTMAP(R+1,C+1) = 1)
    let DISTPROB_TOT = DISTPROB_REAL(R+1,C+1) + DISTPROB_TOT
    let DISTPROB_CUM(R+1,C+1) = 0.0
    let DISTPROB_CUM(R+1,C+1) = DISTPROB_TOT
else
    let DISTPROB_CUM(R+1,C+1) = 0.0
    let ZEROTIES = ZEROTIES + 1
    let ZEROTROW (ZEROTIES) = R+1
    let ZEROTCOL (ZEROTIES) = C+1
    let PREVDIST_ROW = R+1
    let PREVDIST_COL = C+1
always
always
"

```

d. If at least one of the 8 neighbors has a disturbance

```

probability > 0.0
"
"
    if DISTPROB_TOT > 0.0
"
"
"
    (1) If there is more than one neighboring pixel
    already disturbed or the disturbance has
    reached only 1 or 2 pixels, we're not on
    a "peninsula" or the disturbance has just
    started. Then select a random number between 0.0
    and the total of the disturbance probabilities in
    the eight neighbor cells. Then find the cell
    among the eight neighbors whose cumulative
    probability corresponds to the value of the
    selected random number. Disturb that pixel,
    move to it, and add one to the count of
    disturbance size.
"
"
"
    if (ZEROTIES > 1) OR (CURRENT_DISTURB_SIZE < 3)
    let RAND_SPR_VAL = UNIFORM.F(0.0,DISTPROB_TOT,1)
    let OVER = 0
    if CAN_CHECK (R-1,C-1) = 1
    if (RAND_SPR_VAL<=DISTPROB_CUM(R-1,C-1)) AND (OVER=0)
    let OVER = 1
    let R = R-1
    let C = C-1
    always
    if CAN_CHECK (R-1,C) = 1
    if (RAND_SPR_VAL<=DISTPROB_CUM(R-1,C)) AND (OVER=0)
    let OVER = 1
    let R = R-1
    let C = C
    always
    if CAN_CHECK (R-1,C+1) = 1
    if (RAND_SPR_VAL<=DISTPROB_CUM(R-1,C+1)) AND (OVER=0)
    let OVER = 1
    let R = R-1
    let C = C+1
    always
    if CAN_CHECK (R,C-1) = 1
    if (RAND_SPR_VAL<=DISTPROB_CUM(R,C-1)) AND (OVER=0)
    let OVER = 1
    let R = R
    let C = C-1
    always
    if CAN_CHECK (R,C+1) = 1
    if (RAND_SPR_VAL<=DISTPROB_CUM(R,C+1)) AND (OVER=0)
    let OVER = 1
    let R = R
    let C = C+1
    always
    if CAN_CHECK (R+1,C-1) = 1
    if (RAND_SPR_VAL<=DISTPROB_CUM(R+1,C-1)) AND (OVER=0)
    let OVER = 1
    let R = R+1

```

```

        let C = C-1
      always
    always
    if CAN_CHECK (R+1,C) = 1
      if (RAND_SPR_VAL<=DISTPROB_CUM(R+1,C)) AND (OVER=0)
        let OVER = 1
        let R = R+1
        let C = C
      always
    always
    if CAN_CHECK (R+1,C+1) = 1
      if (RAND_SPR_VAL<=DISTPROB_CUM(R+1,C+1)) AND (OVER=0)
        let OVER = 1
        let R = R+1
        let C = C+1
      always
    always

  ''

  let DISTMAP(R, C) = 0
  let DISTPROB_REAL(R, C) = 0.0
  let CURRENT_DISTURB_SIZE = CURRENT_DISTURB_SIZE + 1

  ''

  ''
  (2) If there is only one neighboring pixel already
  ''
  disturbed and if the disturbance has reached
  ''
  at least 3 pixels, then a "peninsula" could form.
  ''
  To stop this, move back to the already
  ''
  disturbed neighboring pixel and try to spread
  ''
  from there.
  ''

  else
    let R = PREVDIST_ROW
    let C = PREVDIST_COL
  always

  ''

  ''
  e. If all the neighboring pixels have a disturbance
  ''
  probability of 0.0, this means that they have all
  ''
  been disturbed already or have no probability
  ''
  of being disturbed. Then choose randomly among
  ''
  the 8 neighbors and move to that pixel.
  ''

  else
    let MAXR = RANDI.F (1,ZEROTIES,1)
    let R = ZEROTROW (MAXR)
    let C = ZEROTCOL (MAXR)
  always

  ''

  loop
  always
  return

end
''
''
''
routine SAMPINT
''
''
  * * * * *
  ''
  * THIS ROUTINE SELECTS AN INTERVAL TO WAIT, BEFORE *
  ''
  * ANALYZING LANDSCAPE STRUCTURE, FROM A NORMAL *
  ''
  * DISTRIBUTION *
  ''
  * * * * *

```

```

//
    let SAMP_INTERVAL = 0
    if SAMP_STDEV = 0.0
        let SAMP_INTERVAL = TRUNC.F(SAMP_MEAN)
    else
        let SAMP_INTERVAL = 0
        while SAMP_INTERVAL < 1
            do
                let SAMP_INTERVAL =
                    TRUNC.F(NORMAL.F(SAMP_MEAN,SAMP_STDEV,STM_SAMP))
            loop
        always
    return
end
//
//
//
function CAN_CHECK (rowval, colval)
//
// *****
// * CAN_CHECK makes sure a disturbance doesn't spread *
// * off the map. It returns a 0 if rowval or colval *
// * are off the map. If not, it returns a 1 *
// *****
//
// Define rowval and colval as integer variables
//
    if (rowval > NROW) or (rowval < 1)
        return with 0
    else
        if (colval > NCOL) or (colval < 1)
            return with 0
        else
            return with 1
    //
end
//

```

APPENDIX E. Documentation for the GLE programs

GLE.SETUP, GLE.DIST, GLE.PATCH, GLE.TEX, AND GLE.NULL

A set of GRASS programs
for the quantitative analysis of landscape structure

Version 2.0
March 15, 1991

William L. Baker, Principal Investigator
and
Yunming Cai, Research Assistant

Department of Geography and Recreation
University of Wyoming
Laramie, Wyoming 82071

This set of programs was developed in its entirety with funds from U.S. Department of Energy Grant DE-FG02-89ER60883. This support does not constitute an endorsement by DOE of the views expressed in this document.

TABLE OF CONTENTS

1. INTRODUCTION	3
1.1. Purpose of the GLE programs	3
1.2. Relationship of the GLE programs and GRASS	3
1.3. Overview of the GLE programs	5
2. THE GLE PROGRAMS	5
2.1. Operation	5
2.2. Data input	10
2.3. Gle.setup	10
2.3.1. Sampling	11
2.3.2. Group/class limits	16
2.3.3. Color table	17
2.4. Syntax for the GLE analysis programs	18
2.5. Gle.dist	20
2.6. Gle.patch	21
2.6.1. Age/type measures	21
2.6.2. Size measures	23
2.6.3. Shape measures	24
2.6.4. Fractal dimension	26
2.6.5. Perimeter measures	26
2.7. Gle.tex	27
2.7.1. Diversity measures	28
2.7.2. Texture measures	28
2.7.3. Edge measures	31
2.8. Output from the GLE analysis programs	32
2.8.1. Output files and data formats	32
2.8.2. Data analysis with external statistical and graphics software	36
2.9. Gle.null	36
3. GLOSSARY	37
4. BIBLIOGRAPHY	38

1. INTRODUCTION

This manual provides an overview of how to use the set of GLE programs, including information about the logic of the programs and data input/output.

1.1. Purpose of the GLE programs

Since the 1970s, with the availability of satellite data, there has been an increasing interest in the structure of the earth on the scale of kilometers or hundreds of kilometers. Landscape ecology is a multi-disciplinary pursuit, involving geographers, biologists, sociologists, remote sensors, and many others. The focus of landscape ecology is on the dynamics and structure of the biosphere, including human activities, on the scale of kilometers (Risser et al. 1984; Forman and Godron 1986; Urban et al. 1987). The science of landscape ecology has expanded rapidly in the 1980s, and methods for the quantitative analysis of landscape structure are being developed (e.g. Mead et al. 1981; Gardner et al. 1987; Krummel et al. 1987; Milne 1988; Griffiths and Wooding 1988), yet there is no generally available software for this purpose.

The GLE programs have been designed to provide software for calculating a variety of common quantitative measures of landscape structure. The programs were specifically designed for analyzing the structure of landscapes output from a simulation model, but can be used to analyze the structure of nearly any landscape.

1.2. Relationship of the GLE programs and GRASS

The GLE programs are intended to be part of the Geographical Resources Analysis Support System (GRASS), a public-domain geographical information system (GIS), designed and developed through the Environmental Division of the U.S. Army Construction Engineering Research Laboratory in Champaign, Illinois (USA-CERL 1988) (Fig. 1). GRASS is a raster-based GIS, with some vector handling capabilities. GRASS requires the UNIX operating system, but can be used on a variety of workstations, as well as 80386-class personal computers.

The GLE programs directly use the GRASS database, GRASS libraries, and the GRASS data structure (Fig. 1) in the calculation of measures of landscape structure, and use GRASS for the entry of digitized data. GRASS also provides a number of separate image processing, data manipulation, and mapping programs which can be useful for preparing data for analysis with the GLE programs and for displaying output.

1.3. Overview of the GLE programs

The GLE programs are designed for analyzing landscapes composed of a mosaic of patches, but, more generally, these programs are capable of analyzing any two-dimensional array whose entries are integer values. The landscape can also be divided into regions, whose structure can then be analyzed separately.

The GLE programs have options for controlling the shape, size, number, and distribution of sampling units used to collect information about the landscape. Sampling unit shapes can be square, or rectangular with any length/width ratio. The size of sampling units can be changed, so that the landscape can be analyzed at a variety of spatial scales. Sampling units may be distributed across the landscape in a random, systematic, or stratified-random manner, or as a moving window.

The GLE programs can calculate a number of measures that produce single values as output (e.g. mean patch size in the sampling unit), as well as measures that produce a distribution of values as output (e.g. frequency distribution of patch sizes in the sampling unit) (Table 1). The programs include no options for graphing or statistically analyzing the results of the analyses. External software must be used.

The programs were developed on a SUN SPARCstation 1 workstation running the Sun OS 4.1 operating system and the Sunview windowing programs (Fig. 1). The code was written in the C programming language and makes use of functions provided in the GRASS programmers' library (Shapiro et al. 1989),

2. THE GLE PROGRAMS

2.1. Operation

To run the GLE programs, the user must first start the command-line version of GRASS (type "GRASS3") and set up the working environment in GRASS by specifying the GRASS location and map layers to be used. The sequence of operations usually is to first use Gle.setup to set up the sampling framework (e.g. regions, sampling unit size and shape, etc.) and then use the other GLE programs (e.g. Gle.tex, Gle.patch, Gle.dist) to make the desired measurements (Fig. 2). All of the GLE programs operate from the GRASS command prompt (>). The commands and their parameters are entered after the GRASS command prompt, and the programs then go through a sequence of operations to complete the set up and measurements (Fig. 3). Output from Gle.setup goes in the subdirectory "Gle_para" while output from the other GLE programs goes in the subdirectory "Gle_out". These subdirectories are created automatically when the programs are invoked, and are made subdirectories within the directory from which the programs are invoked.

TABLE 1. Measures that can be calculated by the GLE programs. All the measures can be calculated using the moving window method of sampling. With measures that produce a distribution as output only the first class of the distribution is used.

Gle.dist

Measures

Mean distance
Standard deviation distance
Number of patches in each distance class
Number of patches in each distance class by group

Method I

center to center
center to edge (boundary)
edge (boundary) to edge (boundary)

Method II

From every patch to all the adjacent patches
From every patch to the nearest patch of same age/type group
From every patch to the nearest patch of different age/type group
From every patch of one age/type group to every patch of a specific age/type group

Gle.patch

AGE/TYPE:

Mean patch age
Standard deviation patch age
Cover by age/type group
Density by age/type group

SIZE:

Mean patch size
Standard deviation size
Mean patch size by age/type group
Standard deviation size by age/type group
Number in each size class
Number in each size class by age/type group

SHAPE:

Indices: Corrected perimeter/area
Perimeter/area
Related circumscribing circle

Measures:

Mean patch shape
Standard deviation shape
Mean patch shape by age/type groups
Standard deviation shape by age/type group
Number in each shape class
Number in each shape class by age/type group

TABLE 1. Continued

FRACTAL DIMENSION

Perimeter-area fractal dimension

PERIMETER

Sum of total perimeters

Sum of total perimeters by age/type group

Mean perimeter length

Mean perimeter length by age/type group

Standard deviation perimeter length

Standard deviation perimeter length by age/type group

Gle.tex

DIVERSITY

Richness

Shannon

Dominance

Reciprocal Simpson's

TEXTURE

Measures

Contagion (C)

Angular second moment (ASM)

Inverse difference moment (IDM)

Entropy (ENT)

Contrast (CON)

Methods

2-neighbor: horizontal (2N-H)

2-neighbor: 45 degrees (2N-45)

2-neighbor: vertical (2N-V)

2-neighbor: 135 degrees (2N-135)

4-neighbor: horizontal/vertical (4N-HV)

4-neighbor: diagonal (4N-DIAG)

8-neighbor: (8N)

2.2. Data input

The GLE programs work directly with map layers that have been input and preprocessed in GRASS. Data from Landsat Multi-Spectral Scanner (MSS) or Thematic Mapper (TM) can be downloaded into GRASS using the image processing programs in GRASS. Data can also be input from a scanner. Vector information can be input using the GRASS digitizing programs. Vector information must be converted to raster data using the GRASS program "vect.to.cell" prior to using the GLE programs Gle.dist, Gle.patch, Gle.tex, and Gle.null. It is possible to input almost any kind of pixel-based (raster format) data, in nearly any format into GRASS. The user must, however, be able to write a formal description of the data format. Preprocessing capabilities of GRASS include programs to rectify imagery so that it matches a planimetric map and programs for classifying raw data into patch types.

The GLE programs were conceived for analyzing maps of patch types or patch ages, or both. A variety of landscape data can be considered "patch type" data. Patches may be disturbance patches, remnant patches, environmental resource patches, introduced patches, or simply patchy entities on a map (Forman and Godron 1986). Patch types may simply be landscape element types (Forman and Godron 1986), such as roads, dwellings, forest patches, grassland patches, hedgerows, or fields. Patch types could also be types of forest in a forested landscape (e.g. deciduous forest, recently-burned forest, conifer forest), or types of grassland in a prairie landscape. Patch types could also be the types identified by completing a classification of spectral data in a Landsat image, or in a scanned aerial photograph. In general, patch types are simply the result of grouping pieces of the landscape into units whose members share a common set of attributes.

It is also possible to analyze a map of patch ages. Patches of different age occur in landscapes subject to disturbances (e.g. fires, floods), where the age of the patch represents the time since it was last disturbed. This could also occur in other landscapes. For example, the program could be used to analyze the age structure of an urban landscape where the patches represent buildings that are replaced or destroyed over time.

2.3. Gle.setup

Gle.setup is used to set up the sampling and analysis framework that will be used by the other GLE programs. To run Gle.setup do the following:

1. After starting GRASS3 and setting up your location and mapset, start a GRASS display window. The procedure for this varies with the computer you are using. On the Sun:
 - Type "Dstart.mon SUNVIEW" and a carriage-return in a shell-command tool window
 - Type "Dselect.mon SUNVIEW" and a carriage-return

The screen will go black
 Move the cursor (you can't see it) to the edge of the screen, hold down the right mouse button and move down to "Resize." Release the right button.

Resize the display window by holding down the middle button while moving the window's boundary

2. Move the cursor back to the command window with the GRASS command prompt (>).
3. Type Gle.setup, a space, and the name of the GRASS cell file (see Glossary) you want to analyze.
4. The cell file will be displayed and you will see the main Gle.setup menu.

The first menu allows the user to select how sampling will be done (regions, sampling units, moving window), setup the limits for groups and classes, and change the color table.

2.3.1. Sampling

Information about the structure of the landscape is obtained by overlaying a set of sampling areas on top of a map layer, and then calculating specific structural measures for the part of the map layer that corresponds to the area in each sampling area.

A sampling area may be one of four things (Fig. 4). First, it is possible to treat the entire map layer as the one (and only) sampling area. Second, if the map layer can be divided into meaningful geographical regions, then it is possible to treat the regions themselves as sampling areas. The third option is that the sampling areas may be sampling units of fixed shape and size (also called scale) that are placed within the map layer as a whole. The fourth and final option is that the sampling area may be moved systematically across the map as a moving window. The following sections present additional details about these options for sampling areas.

2.3.1.1. Whole map layer

If the whole map layer is to be used as the one and only sampling area (Fig. 4), then Gle.setup does not need to be run. The user may complete an analysis by simply entering the GLE command (e.g. Gle.patch) followed by the name of the GRASS cell file to be analyzed.

2.3.1.2. Regions

If regions are to be used as the sampling areas (Fig. 4), then select "REGIONS" from the first Gle.setup menu, and the user is asked to do the following:

1. "ENTER THE NEW REGION FILE NAME:". Only a new file name is acceptable. The user can type LIST to find out the existing file names in this location and mapset.
2. "PLEASE OUTLINE REGION # 1". The user should move the mouse cursor into the graphic monitor window and use the mouse buttons as instructed:
 - Left button: where am I.
to display the current coordinates of the cursor in the cell array system.
 - Middle button: Mark a point.
to enter a vertex of the region boundary.
 - Right button: Mark LAST point.
to close the region boundary by settin the last vertex to be equal to the first one.
3. A "REGION OPTIONS:" menu is displayed and the user should use the mouse to select one of the options:
 - "DRAW MORE": repeat the above process and setup one more region.
 - "START OVER": abandon the previous setup and start all over again.
 - "DONE-SAVE": save the regions outlined so far and exit this procedure.
 - "QUIT-NO SAVE": quit the procedure without saving the regions.

Once the "DONE-SAVE" option is selected, the new cell file of the sampling regions is generated. It is displayed on the monitor window for a several seconds, the monitor window is refreshed, the main menu is displayed again and the program is ready for other setup work.

2.3.1.3. Sampling units

If sampling units are to be used as the sampling areas (Fig. 4), then choose "SAMP. UNITS" from the first Glé.setup menu. Then the

following choice is displayed followed by a series of other choices:

Define sampling units manually or graphically?

The next menu allows the user to choose to define the sampling units manually or graphically. When sampling units are defined manually, the user inputs the shape and size (scale) of the sampling units by specifying dimensions in pixels using the keyboard. When sampling units are defined graphically, the user uses the mouse to define the sampling units in the GRASS display window, and then actually places the sampling units for each scale onto the map. By placing the units graphically the user can directly determine the method of sampling unit distribution as well as the shape, size, and number of sampling units.

If the choice is made to define sampling units manually, the user next is prompted to use the mouse to outline the actual part (or whole) of the map that will be sampled, and the following series of questions must be answered.

How many different scales do you want?

Next the user is asked to specify the number of scales that will be used. The GLE programs allow the user to simultaneously sample the same map with the same measures at several scales. Currently there can be between 1 and 15 scales that can be sampled simultaneously. Substantial output can be produced if many scales are used.

Methods of sampling unit distribution

Sampling units must be placed spatially into the landscape. There are four options for doing this (Fig. 4):

1. Random nonoverlapping: Sampling units are placed in the landscape by randomly choosing numbers that specify the location of the upper left corner of each sampling unit, subject to the constraint that successive sampling units not overlap other sampling units or the edge of the landscape.
2. Systematic contiguous: Sampling units are placed side by side across the rows. If the placement of sampling units produces an imperfect fit (leftover area), then the leftover area is shifted to the upper left corner of the sampling area, and a randomly selected starting point is chosen within the leftover area.
3. Systematic noncontiguous: The user must specify the amount of spacing (in pixels) between sampling units. Horizontal and vertical spacing are identical. Leftover area is allocated

as it was with systematic contiguous sampling. Sampling units are again placed side by side (but spaced) across the rows. If the placement of sampling units produces an imperfect fit (leftover area), then the leftover area is shifted to the upper left corner of the sampling area, and a randomly selected starting point is chosen within the leftover area.

4. Stratified random: The user must specify the vertical and horizontal locations of strata, which partition the sampling area. The strata are rectangular areas within which single sampling units are randomly located.

The ratio for sampling unit of scale n ?

The user is next prompted to enter a ratio that defines the shape of the sampling units. Sampling units may have any rectangular shape, including square as a special case of rectangular. Rectangular shapes are specified by entering the ratio of columns/rows (horizontal dimension/vertical dimension) as a real number.

Maximum size is m . What size for each sampling unit of scale n ?

The user is then given the maximum possible size for a sampling unit (in pixels) and asked to input the size of sampling units at each scale. Sampling units can be of any size, but the maximum size is the size of the landscape as a whole. All the sampling units, that make up a single sampling scale, are the same size.

Maximum units in scale n is p . How many sampling units do you want?

The maximum number of units that can be placed over the map, given the shape and size of the units, is then given. The user can then choose the number of sampling units to be used in the map layer.

2.3.1.4. Moving window:

Using this procedure a rectangular "window" or single sampling unit is moved systematically across the map to produce a new map. This sampling procedure can only be used with the measures that produce a single value or with a single class of measures that produce distributions of values (Table 1). The first class specified when defining class limits (section 2.3.2.) is used if distributional measures are chosen with the moving window sampling method.

Sampling begins with the upper left corner of the window placed over the upper left corner of the map layer. The value of the chosen

measure is calculated for the window area. This value is assigned to the location on the new map layer corresponding to the center pixel in the window if the window has odd (e.g. 3 X 3) dimensions. The value is assigned to the location on the new map layer corresponding to the first pixel below and to the right of the center if the window has even dimensions (e.g. 6 X 10). The window is then moved to the right (across the row) by one pixel, and the process is repeated. At the end of the row, the window is moved down one pixel, and then back across the row.

This option produces a new map layer, whose dimensions are smaller by $(m-1)/2$ rows and columns, where m is the number of rows or columns in the window.

If the "MOVE-WINDOW" option in the main menu is selected, the user is prompted to do the following:

1. "Use the mouse to define the moving window?"
 - If yes, then the functions of the three mouse buttons are displayed: check size, move cursor, and define the move-window. The moving window is defined in the same way as the sampling unit. Once defined, it will be displayed wherever it is defined.
 - If no, then the prompt "Enter COLUMNS & ROWS of the window:" is displayed. Type in the number of rows and columns of the moving-window using the GRASS cell array coordinate system. Then the moving window will be displayed in the top-left corner of the current window of the monitor screen.
2. "Will the moving window search the whole map?"
 - If yes, the module saves the input and returns to the main menu.
 - If no, the button instruction is displayed and the user should use the mouse cursor to outline the area that the moving window will search through. This is done in the same way as above. After the area is defined and displayed wherever it is defined the user is asked "Is the search area ok?" If not, the process is repeated. Otherwise the area is displayed, with the moving window in a different color, at the top-left corner of the area. The picture is displayed for a few seconds and then it is refreshed. Then the main menu is redisplayed for next selection.

2.3.2. Group/class limits

The user can specify the limits for a number of groups and classes that are used in measurements and for reporting results. See the glossary for a definition of group and class. See the appropriate measurement options under Gle.dist and Gle.patch to determine whether you want to define class limits for these analyses.

The program is currently designed to allow no more than 25 age or type groups, 25 size classes, 25 shape index classes, and 25 distance index classes.

The user may also want to permanently group certain attributes prior to entering the GLE programs. For example, the user may want to group attributes 1-10, in a map whose attributes are ages, into a single attribute representing young patches. The user can do this using the GRASS Greclass and Gresample commands, which will create a new map layer that can then be analyzed with the GLE programs.

2.3.3. Color table

The user may want to change the color table for the map in the GRASS display window to make the sampling units, cursor, and rubber band more visible. There are several different color tables that can be tried until a suitable one is found. Note that if you choose one of the other color tables from the menu, the color table for that GRASS cell file gets changed. To change it back to what it was originally, select "SET-OLD" from the color table menu.

If the "Color Table" option in the main menu is selected, a menu titled "SEL. NEW COLOR TYPE" is displayed that has the following options:

- "ASPECT": generate a color table for aspect data.
- "GREY SCALE": generate a grey scale color table. Each color is a level of grey, increasing from black to white.
- "RAMPS": generate a color table with 3 sections: red only, green only, and blue only, each increasing from none to full intensity. This table is good for continuous data such as ages.
- "RAINBOW": generate a color table based on rainbow colors. the table generated here uses yellow, blue, indigo, violet, red. This table is good for continuous data such as ages.
- "RANDOM": generate random colors. Good as a first pass at a color table for nominal data. This option generates different color combinations for the color table each time. Therefore it can be used repeatedly until the satisfactory colors are displayed.
- "RED-YEL-GRN": generate a color table similar to that of "RAINBOW", except that the table starts at red, passes through yellow, and ends with green.
- "WAVE": generate a color table with 3 sections: red only, green only, and blue only, each increasing from none to full intensity and back down to none. This table is good for continuous data like ages.
- "SET OLD": assign the original color table to the input cell map if none of the above options improves the display during setup.

After one of these options is selected, the menu titled "WHAT'S NEXT" is displayed that has the following options:

- "START OVER": go back to the previous menu and reset the original color table.
- "MAIN MENU": exit from the color change module and go back to the main menu. The color table will be reset to that of the input file when the user leaves the Gle.setup program.
- "SAVE COLOR TAB.": exit from this module and permanently save the currently displayed color table.
- "QUIT SETUP": quit the Gle.setup program and don't save any changes.

2.4. Syntax for the GLE analysis programs

The GLE analysis programs include Gle.dist, Gle.patch, and Gle.tex. They are designed to do the landscape ecological analysis by computing the spatial measures selected from the measure list available with each program. Each program will be explained in the following sections. Gle.null, not a analysis program itself, is an accessory program for the landscape analysis which will be discussed in section 2.9.

All three GLE analysis programs are invoked at the GRASS prompt (>) using the command name and command-line parameters. Most of the command-line parameters are the same for all three programs.

Each legal command-line parameter is described briefly in help menus for each of the three GLE programs. Each program has a general help menu and a menu for the moving-window measures. Each help menu can be invoked in the same way: typing the Gle program name alone will invoke the general help, whereas typing the Gle program name plus "help" plus any extra character will invoke the moving-window menu. For example, "Gle.patch" will invoke the general help, while "Gle.patch help m" will invoke the moving window menu.

The general syntax of the GLE analysis programs is as following:

```
Program_name input_layer [samp] [back] [meas] [reg]
```

where:

Program_name is either Gle.patch, Gle.dist, or Gle.tex.,
Input_layer is the GRASS cell file to be analyzed. This cell file must be available in the user's working GRASS database (/location/mapset/).

Other parameters are optional, which means that if the parameter is omitted the program will use the default

value.

[samp] is the sampling method. The legal values are:

"W" - the whole map is the one and only sampling unit. This is the default value.

"R" - the regions in an existing GRASS cell file will be used as the sampling units. In this case, [reg] must be the file name of the region file which must be available in the user's working GRASS database. [reg] must be the last command-line parameter.

[back] is used with Gle.patch and Gle.tex to tell the program to run in the foreground or background. The legal values are:

"F" - the program will run in the foreground. This means the GRASS interface will be occupied by the GLE program until it's done. This is the default value.

"B" - the program will run in the background, so that the user can still access the GRASS interface.

[back/skip/NN] is used with Gle.dist to specify three parameters. The legal values are:

back is the same as above.

skip is to specify whether to skip some points when searching along the patch boundary. This is used to speed up the distance calculations.

skip $\leq$ 0 means don't skip;

skip $>$ 0 means:

if np $>$ skip + 50 - search every other boundary point;

if np $>$ skip + 200 - search every third boundary point;

if np $>$ skip + 500 - search every fourth boundary point;

if np $>$ skip + 2000 - search every fifth boundary point;

where np is the number of total boundary point of a patch. This is effective with the center-edge and edge-edge distance measures. The default value is skip = 1;

NN is the maximum number of candidate patches on the nearest-neighbor-list for searching the nearest neighbor patch. It means when searching the nearest patch of a particular patch, find NN "close" patches first using simple method, then find out the nearest patch from these NN candidate patches with point-by-point calculation. The legal range of NN is 1-30. If NN $<$ 1, NN = 1; if NN $>$ 30, NN = 30. The default value is NN = 5.

The "/" character is required for both "skip" and "NN"

with "skip" on the left of "NN" if "NN" is specified. Both "skip" and "NN" are used by the program to lighten the calculation, but both parameters may affect the precision of the analysis.

[meas] is the measure code and method code which are different for each program, and will be discussed in the sections for each particular program.

[reg] is the GRASS cell file containing the regions, which is needed only when "R" is specified as the sampling method (see [samp]).

For example,

Gle.patch test

analyzes the default patch measures using GRASS cell file "test" and the default parameters, which are: foreground, whole map.

Gle.dist test R B/O region

analyzes the default distance measures using GRASS cell file "test" with the GRASS cell file "region" as the sampling regions, and with the program run in the background. The program will check every boundary point when calculate center-edge or edge-edge distance measures.

2.5. Gle.dist

See section 2.4. for an explanation of how to start the Gle.dist program. Distance can be measured and summarized in a variety of ways, depending on whether distance is measured: (1) from every patch in the sampling unit or only from patches belonging to a particular age/type group, (2) to all adjacent neighboring patches or only to the single nearest neighbor patch, (3) regardless of the age/type group of the neighbor or only to patches belonging to a particular age/type group, and (4) from center to center, from center to edge, or from edge to edge. There are four combinations of the first three choices. These are numbered below in brackets:

From every patch in the sampling unit

To all the adjacent neighbors of the patch

[1] Distance to all adjacent neighbors is measured,
regardless of the age/type group of the adjacent neighbor
Distance is center-center
Distance is center-edge

To the single nearest neighbor of the patch

[2] Nearest neighbor must be of the same age/type group

Distance is center-center
 Distance is center-edge
 Distance is edge-edge
 [3] Nearest neighbor must be of a different age/type group
 Distance is center-center
 Distance is center-edge
 Distance is edge-edge
 From every patch in the sampling unit that belongs to a specific age/type group
 To the single nearest neighbor of the patch
 [4] Nearest neighbor belongs to a specific age/type group
 Distance is center-center
 Distance is center-edge
 Distance is edge-edge

These four methods are illustrated in Fig. 5. The number above each illustration corresponds to the number in brackets above. Only the center-center distance is illustrated. In [4] the "from" age/type group is 9 and the "to" age/type group is 4.

A polygon is considered to be adjacent to another polygon if it shares either an edge or a single vertex with the polygon. Distance from center to edge is measured from the center of one polygon to the closest point on the boundary of the other polygon. Distance from edge to edge is measured as the minimum distance between any points on the boundary of the two polygons.

Mean distance is simply the total of all the distances divided by the number of distances measured. Note that with measure [1] a very large number of distances are calculated, whereas with measures [2] and [3] the number of distances measured is the same as the number of patches in the sampling unit. With measure [4] the number of distances is the same as the number of patches in the sampling unit which belongs to the "from" age/type group. Note that the distance between polygons A and B may be used more than once with any of the measures, as this distance may be calculated once with polygon A as the "from" polygon and once with polygon B as the "from" polygon. The distance between polygons A and B is the same no matter which is the "from" polygon if center-center distance is calculated, but it is not the same if center-edge distance is calculated.

2.6. Gle.patch

See section 2.4. for an explanation of how to start the Gle.patch program. The measurement options of Gle.patch are described in detail below.

2.6.1. Age/type measures

These measurement options can be used on a map layer whose attributes are the ages of patches or the type of patches. Measures 1

and 2 are only appropriate if the attribute is age.

1. Mean patch age: This is the average age of all the pixels in the sampling unit. It can only be calculated if the map layer to be analyzed contains pixels whose value is age (in years). The area of a particular age is weighted by how many pixels it occupies. The weighted mean age, $\bar{x}$, is then:

$$\bar{x} = \frac{\sum_{i=1}^m (w_i * i)}{\text{size}}$$

where w_i is the number of pixels of age i , i is the actual age (in years) of these pixels, m is the number of attributes in the sampling unit, and size is the size of the sampling unit (in pixels).

2. Standard deviation of patch age: This is simply the standard deviation of the ages of the patches in the sampling unit. It can only be calculated if the map layer to be analyzed contains pixels whose value is age (in years). The standard deviation of patch age, s , is then:

$$s = \sqrt{\frac{\sum_{i=1}^N (x_i - \bar{x})^2}{N}}$$

where x_i is the age of patch i , $\bar{x}$ is the mean age of all the patches, and N is the number of patches.

3. Cover by age/type group: This is a measure of the amount of land area covered by each age or type group. Cover is expressed as the fraction of the sampling unit occupied by each age or type group.
4. Density by age/type group: This is a measure of the number of patches in each age/type group. It is expressed as first the fraction of the total number of patches that are in each age/type group, and second as the raw number of patches that are in each age/type group.

2.6.2. Size measures

1. Mean patch size: This measure, the mean size or area (in pixels) of the patches in the sampling unit, is calculated for all patches in the sampling unit, ignoring the age or

type group of each patch, by simply dividing the sampling unit size by the number of patches.

2. Standard deviation of patch size: This is the standard deviation of the sizes (in pixels) of all the patches in the sampling unit, ignoring the age or type group of each patch. The standard deviation of patch size, s , is then:

$$s = \sqrt{\frac{\sum_{i=1}^N (x_i - \bar{x})^2}{N}}$$

where x_i is the size of patch i , $\bar{x}$ is the mean size of all the patches, and N is the number of patches.

3. Mean patch size by age/type group: This is the mean patch size within the sampling unit, as in #1, but calculated separately for all the patches within each age/type group.
4. Standard deviation of patch size by age/type group: This is the standard deviation of the sizes (in pixels) of all the patches in the sampling unit, as in #2, but calculated separately for all the patches within each age/type group.
5. Number in each size class: This is a measure of the number of patches in the sampling unit that fall within each size class. This measure is calculated for all the patches in the sampling unit, ignoring the age or type group of each patch. The results can be reported for up to 25 size classes.
6. Number in each size class by age/type group: This is a measure of the number of patches in the sampling unit that fall within each size class. This measure is calculated separately for all the patches within each age or type group. The results can be reported for up to 25 size classes.

2.6.3. Shape measures

There are three possible indices of patch shape. These are only three of the simplest indices of two-dimensional shape (Austin 1984; MacEachren 1985):

1. Perimeter/area: The total length of the perimeter of each patch is divided by its area, and the mean of these values is then calculated. Where patches extend outside of the sampling unit,

the sampling unit edge is considered to be the edge of the patch. A problem with the ratio of perimeter/area as a shape index is that it varies with the size of the patch.

2. Corrected perimeter/area: The formula for this index for each patch is: $(.282 \times \text{perimeter})/(\text{area})^{1/2}$. The mean of these values for all the patches is then calculated. This index corrects for the size problem of index 1. The index varies from a value of 0.0 for a circle to infinity for an infinitely long and narrow shape. It is 1.1 for a square.

3. Related circumscribing circle: This index compares the area of the patch to the area of the smallest circle that can circumscribe the patch. The formula for each patch is:

$$RCC = \frac{2 * (\text{area}/\pi)^{1/2}}{\text{longest-axis}}$$

This index varies from 0.0 to 1.0 as the compactness of the shape approaches that of a circle. A square has the value 0.79789.

There are several possible measures of patch shape. Each of the measures is described below:

1. Mean patch shape: This measure is calculated for all patches in the sampling unit, ignoring the age or type group of each patch. The mean patch shape is simply the sum of the patch shape indices for every patch divided by the number of patches.
2. Standard deviation of patch shape: This is the standard deviation of the shapes of all the patches in the sampling unit, ignoring the age or type group of each patch. The standard deviation of patch shape, s , is then:

$$s = \sqrt{\left(\frac{\sum_{i=1}^N (x_i - \bar{x})^2}{N} \right)}$$

where x_i is the shape of patch i , $\bar{x}$ is the mean shape of all the patches, and N is the number of patches.

3. Mean patch shape by age/type group: This is the mean patch shape within the sampling unit, as in #1, but calculated separately for all the patches within each age/type group.
4. Standard deviation of patch shape by age/type group: This is the standard deviation of the shapes of all the patches in the sampling unit, as in #2, but calculated separately for all the patches within each age/type group.
5. Number in each shape index class: This is the number of patches, in the sampling unit, whose shape index value falls within each shape index class. This measure is calculated for all the patches in the sampling unit, ignoring the age or type group of each patch. The results can be reported for up to 25 shape index classes.
6. Number in each shape index class by age/type group: This is the number of patches, in the sampling unit, whose shape index value falls within each shape index class. This measure is calculated separately for all the patches in each age or type group. The results can be reported for up to 25 shape index classes.

2.6.4. Fractal dimension

The fractal dimension, D , for the patches in a sampling unit, is a measure of the complexity of the perimeter. The current version implements only the perimeter-area interpretation of fractal dimension (Krummel et al. 1987). The formula for fractal dimension, d , is:

$$d = 2 + s$$

where s is the slope of the regression of the log of the patch perimeter versus the log of the patch area.

2.6.5. Perimeter measures

The perimeter of a patch is the distance around the boundary, in pixels. The perimeter includes the edge of the sampling unit when the edge of the sampling unit intersects a patch. The perimeter is measured for each patch individually. Thus some boundaries between adjoining patches get measured twice. The edge measures (section 2.7.3) do not measure shared boundaries twice. There are several possible measures of perimeter:

1. Sum of the perimeters: This is the total of all the perimeters for all the patches in the sampling unit, ignoring the age/type group to which the patch belongs.
2. Mean perimeter length: This is the mean perimeter length for the patches in the sampling unit, ignoring the age/type group to which the patches belong. It is calculated by dividing the sum of the perimeters by the number of patches.
3. Sum of the perimeters by age/type group: This is the total of all the perimeters for all the patches in the sampling unit, as in #1, calculated separately for the patches belonging to each age/type group.
4. Mean perimeter length by age/type group: This is the mean perimeter length for the patches in the sampling unit, calculated separately for the patches belonging to each age/type group. It is calculated by dividing the sum of the perimeters by the number of patches within each age/type group.
5. Standard deviation of perimeter length: This is the standard deviation of perimeter length for all the patches in the sampling unit, ignoring the age/type group to which they belong. The standard deviation of perimeter length, s , is then:

$$s = \sqrt{\left(\frac{\sum_{i=1}^N (x_i - \bar{x})^2}{N} \right)}$$

where x_i is the perimeter length of patch i , $\bar{x}$ is the mean perimeter length of all the patches, and N is the number of patches.

6. Standard deviation of perimeter length by age/type group: This is the standard deviation of perimeter length for all the patches in the sampling unit, as in #5, but calculated separately for the patches belonging to each age/type group.

2.7. Gle.tex

See section 2.4. for an explanation of how to start the Gle.tex program. Gle.tex contains a set of measures of diversity, texture, and edge. The measurement options are described in detail below.

2.7.1. Diversity measures

These are measures of the diversity of patch types or patch ages within the sampling unit. The relative merits of the following indices have been evaluated by Peet (1974).

1. Richness: This is simply the number of different patch types or patch ages present in the sampling unit.
2. Shannon index (H'): This is an index that combines richness and evenness. Its formula is:

$$H' = -\sum_{i=1}^m p_i \ln(p_i)$$

where p_i is the fraction of the sampling unit occupied by age/type class i , and m is the number of ages or types in the sampling unit.

3. Dominance: This index is related to the Shannon index, but emphasizes the deviation from evenness. The formula for dominance, D , is:

$$D = 1/n^2 \sum_{i=1}^m p_i^2$$

where n is the number of ages or types in the sampling unit. This index was first proposed and used by O'Neill et al. (1988).

4. Reciprocal Simpson's index ($1/S$): This index also combines richness and evenness. Its formula is:

$$1/S = 1/\sum_{i=1}^m p_i^2$$

where p_i is the fraction of the sampling unit occupied by age/type class i , and m is the total number of age/type groups within the sampling unit.

2.7.2 Texture measures

Texture measures quantify the adjacency of similar ages or types. They are in a sense simply local (neighborhood) measures of diversity. Most of the measures have been reviewed by Haralick et al. (1973), Haralick (1975), and Musick and Glover (1990).

All of the measures require calculation of a grey-level co-occurrence matrix (GLCM), which is $m \times m$, where m is the number of ages

or types in the sampling unit. The GLCM matrix contains entries, P_{ij} , which are the total number of times that age/type i is adjacent to age/type j . The total number of adjacencies is calculated by moving through the sampling unit pixel-by-pixel. The adjacencies for each pixel are determined by examining neighbors using one of seven methods (Fig. 6). There are five measures of texture that can be calculated using the seven methods:

1. Contagion: This measure is a modification of the entropy measure (#4). The formula for contagion, C , is:

$$C = m \cdot \ln(m) - ENT$$

2. Angular second moment: This is a measure of the homogeneity of the landscape. Smaller values indicate more homogeneity. The formula for angular second moment, ASM , is:

$$ASM = \sum_{i=1}^m \sum_{j=1}^m (P_{ij})^2$$

3. Inverse difference moment: The formula for inverse difference moment, IDM , is:

$$IDM = \sum_{i=1}^m \sum_{j=1}^m \frac{1}{1+(i-j)^2} P_{ij}$$

4. Entropy: The formula for entropy, ENT , is:

$$ENT = - \sum_{i=1}^m \sum_{j=1}^m P_{ij} \cdot \ln(P_{ij})$$

5. Contrast: This is a measure of the contrast or amount of local variation present in the landscape. The formula for contrast, CON , is:

$$CON = \sum_{i=1}^m \sum_{j=1}^m [(i-j)^2 \cdot P_{ij}]$$

2.7.3. Edge measures

Edge is the amount of patch boundary, but in summing edge for all the patches in a sampling unit edges are counted only once when they are shared between two patches. There are three measures that are edge-related:

1. Mean juxtaposition: Juxtaposition is a measure of the weighted length of edges surrounding a center pixel. Mean juxtaposition for all the pixels in the sampling unit is calculated as follows:

- a. The program first calculates the juxtaposition for each pixel in the map layer by examining the attributes in the 8 neighboring cells. Weights are assigned by the user to different types of edges. A weighting matrix, which is $m \times m$, where m is the number of different attributes in the map layer, must be created by the user and stored in the directory from which the program is to be run. The weighting matrix contains real numbers, w_{ij} , explained below. Diagonal neighbors get a quantity ranking, q , of 1.0, while horizontal and vertical neighbors get a quantity ranking of 2.0. The juxtaposition for a center cell surrounded by eight neighbors is then given by:

$$J = \sum_{n=1}^8 \frac{q_n * w_n}{12}$$

- where q_n is 2.0 if cell n is horizontally or vertically adjacent and is 1.0 if cell n is diagonal, and w_{ij} is a number between -1.0 and +1.0 which indicate the relative "quality" or weight to be given to edges between attributes m_i and m_j .
- b. Then the program finds the mean juxtaposition of all the cells in the sampling area, by summing all the juxtaposition values and dividing by the number of cells.

Juxtaposition was described and used by Mead et al. (1981) and Henein and Cross (1983).

2. Standard deviation of juxtaposition: This is the standard deviation for all the pixels in the sampling

unit. The standard deviation, s , is given by:

$$s = \sqrt{\frac{\sum_{i=1}^N (x_i - \bar{x})^2}{N}}$$

where x_i is the juxtaposition for cell i , $\bar{x}$ is the mean juxtaposition of all the cells, and N is the number of cells.

3. Sum of the edges: This is the total length of all the edges, counted only once, of all the patches in the sampling unit. It differs from the total perimeter length which sums the length of each patch's total perimeter, effectively counting shared perimeters twice.

2.8. Output from the GLE analysis programs

2.8.1. Output files and data formats

Several output files are produced by the GLE programs. In our implementation on a Sun SPARCstation 1, output files are stored in the /gle_out subdirectory. The output files and their format are as follows. Abbreviations are used as follows:

- * = this line contains data which are saved in the file only if the measure is selected.
- C-C = center to center distance.
- C-E = center to edge (boundary) distance.
- E-E = edge (boundary) to edge (boundary) distance.

From GLE.dist:

1. DIST_ADJ (every patch to all the adjacent patches-method 1)
 - Mean distance Standard deviation distance
 - Number of patches in ea. distance class-all patches (C-C)
 - *Mean distance Standard deviation distance
 - *Number of patches in ea. distance class-all patches (C-E)
2. DIST_ADJ_COH (method 1)
 - *Number in ea. C-C index class-age/type group 1
 - *Number in ea. C-C index class-age/type group 2
 - ...
 - *Number in ea. C-C index class-age/type group n
 - *Number in ea. C-E index class-age/type group 1

- *Number in ea. C-E index class-age/type group 2
 -
 - *Number in ea. C-E index class-age/type group n
3. DIST_DF
(every patch to the nearest patch with a different age/type group-method 3)
- *Mean distance Standard deviation distance
 - *Number of patches in ea. distance-class-all patches (C-C)

 - *Mean distance Standard deviation distance
 - *Number of patches in ea. distance-class-all patches (C-E)
4. DIST_DF_COH (method 3)
- *Number in ea. C-C index class- age/type group 1
 - *Number in ea. C-C index class- age/type group 2
 -
 - *Number in ea. C-C index class- age/type group n

 - *Number in ea. C-E index class- age/type group 1
 - *Number in ea. C-E index class- age/type group 2
 -
 - *Number in ea. C-E index class- age/type group n
5. DIST_FT
(From every patch of one group To the nearest patch of a specific group - method 4)
- *Mean distance Standard deviation distance
 - *Number of patches in ea. distance-class-all patches (C-C)

 - *Mean distance Standard deviation distance
 - *Number of patches in ea. distance-class-all patches (C-E)

 - *Mean distance Standard deviation distance
 - *Number of patches in ea. distance-class-all patches (E-E)
6. DIST_FT_COH (method 4)
- *Number in ea. C-C index class- age/type group 1
 - *Number in ea. C-C index class- age/type group 2
 -
 - *Number in ea. C-C index class- age/type group n

 - *Number in ea. C-E index class- age/type group 1
 - *Number in ea. C-E index class- age/type group 2
 -
 - *Number in ea. C-E index class- age/type group n

 - *Number in ea. E-E index class- age/type group 1
 - *Number in ea. E-E index class- age/type group 2
 -

- *Number in ea. E-E index class- age/type group n
- 7. DIST_SM (every patch to the nearest patch of the same age/type group-method 2)
 - *Mean distance Standard deviation distance
 - *Number of patches in ea. distance-class-all patches (C-C)
 - *Mean distance Standard deviation distance
 - *Number of patches in ea. distance-class-all patches (C-E)
 - *Mean distance Standard deviation distance
 - *Number of patches in ea. distance-class-all patches (E-E)
- 8. DIST_SM_COH (method 2)
 - *Number in ea. C-C index class-age/type group 1
 - *Number in ea. C-C index class-age/type group 2
 -
 - *Number in ea. C-C index class-age/type group n
 - *Number in ea. C-E index class-age/type group 1
 - *Number in ea. C-E index class-age/type group 2
 -
 - *Number in ea. C-E index class-age/type group n
 - *Number in ea. E-E index class-age/type group 1
 - *Number in ea. E-E index class-age/type group 2
 -
 - *Number in ea. E-E index class-age/type group n

From Gle.patch:

- 1. AGE.OUT
 - Weighted mean age Mean age Standard deviation age
 - Cover by age/type-group as a fraction
 - Density by age/type-group-raw number
- 2. FRACT.OUT
 - Fractal dimension R2 SigB
- 3. PERIM.OUT
 - Sum of perim. Mean perim. Standard deviation perim.-all patches
 - Sum of perim.-by age/type groups
 - Mean perim.-by age/type groups
 - Standard deviation perim.-by age/type group
- 4. SHAPE.OUT
 - (Corr. Perim./Area)
 - Mean shape Standard deviation shape-all patches
 - Mean shape-by age/type group

Standard deviation shape-by age/type group
 Number in shape index class-all patches

(Perim./Area)

Mean shape Standard deviation shape-all patches
 Mean shape-by age/type group
 Standard deviation shape-by age/type group
 Number in ea. shape index class-all patches

(Rel. Circum. Circle)

Mean shape Standard deviation shape-all patches
 Mean shape-by age/type group
 Standard deviation shape-by age/type group
 Number in ea. shape index class-all patches

4. SHAPE_COH

*Number in ea. Corr. Perim./Area index class-age/type group 1
 *Number in ea. Corr. Perim./Area index class-age/type group 2
 ...
 *Number in ea. Corr. Perim./Area index class-age/type group n

 *Number in ea. Perim./Area index class-age/type group 1
 *Number in ea. Perim./Area index class-age/type group 2
 ...
 *Number in ea. Perim./Area index class-age/type group n

 *Number in ea. Rel. Circum. Circle index class-age/type group 1
 *Number in ea. Rel. Circum. Circle index class-age/type group 2
 ...
 *Number in ea. Rel. Circum. Circle index class-age/type group n

5. SIZE.OUT

Mean size-all patches Standard deviation size-all patches
 Mean size-by age/type group
 Standard deviation size by age/type group
 Number in ea. size class-all patches

7. SIZE_COH

Number in ea. size class-age/type 1
 Number in ea. size class-age/type 2
 ...
 Number in ea. size class-age/type n (number of groups)

From Gle.tex

1. TEXTURE

Richness Shannon Dominance 1/Simpson's
 *Contagion Ang. 2nd mom. Inv. diff. mom. Entropy Contrast
 *Mean juxta. Sum of edge Standard deviation juxta.

2.8.2. Data analysis with external statistical and graphics software

There are a number of more specialized measures of landscape structure which are not included in this program. Spatial autocorrelation analysis (Griffith 1987; Odland 1988), spatial spectral analysis (Ford and Renshaw 1984; Renshaw and Ford 1984), and geostatistics (Woodcock 1988; Mulla 1988; Oliver et al. 1989a, b) are all methods of spatial analysis that may provide useful quantitative information about landscape structure, but that also require specialized programming. Software for spatial autocorrelation analysis (Anselin 1989; Griffith 1989), spatial spectral analysis (Renshaw and Ford 1984), and geostatistical analysis (Robertson 1987) must be used separately from the GLE programs.

The data that are output by the GLE programs can be compared and analyzed graphically. There is currently no graphical display program built into the GLE programs, although maps and results from moving window analyses can be displayed using GRASS programs. GLE program output data must be examined graphically using external software.

2.9 Gle.null

Gle.null is designed to generate a neutral map layer based on the theory of Gardner et al. (1987). This map layer can be used as a "null hypothesis" layer for testing the statistical significance of landscape measures.

To start Gle.null type the program name followed by a carriage return at the GRASS prompt (>). The user will then be asked to input the name of the output neutral map name, the number of attributes, and the probability of each attribute. The user is prompted to repeatedly enter an attribute value followed by its probability, until all the attribute-probability pairs are input.

The total probability of all the attributes can be less than or greater than 100%. If less than 100%, the rest of the map is filled with zeroes. If greater than 100%, then the attributes after 100% is reached are ignored.

3. GLOSSARY

Age group: a grouping of similar ages into a group. For example all patches that have not been disturbed in 1, 5, 6, or 9 years might be grouped into a 0-10 year age group.

Attribute: One of several values that are possible for the cells in a GRASS cell file, or a polygon in a GRASS vector file.

Class: see "Index class"

Element type: a part (element) of the landscape that has been classified as belonging to a group of similar elements. For example, barns and houses are elements that might be classified as members of the "buildings" element type.

GRASS cell file: a two-dimensional raster array of integer values representing a geographic area. Cell files are normally stored in run-length encoded compressed format to save storage space, but they may also be uncompressed. A GRASS cell layer actually consists of the cell file itself plus several supporting files. Of these, the most important is the cell header file which contains information on the number of rows and columns in the cell file and the geographic area it covers. Other supporting files include the cell category file, the cell color table file, the cell history file, and the cell range file. These files are normally handled automatically in GRASS whenever a cell file is manipulated. (Refer to the GRASS User's Guide and the GRASS Programmer's Manual for further information.)

GRASS map layer: see map layer.

GRASS vector file: a polygonal representation of a geographic area, where the polygons are formed by points and line segments (also known as nodes and arcs). GRASS vector layers consist of an arc-node file (a "dig" file) and several supporting files. The arc-node file contains a header section, which includes the geographic location of the layer, and a list of arcs and their defining points and nodes. The vector index and pointer file ("dig_plus" file) contains the polygon topology, i.e., information on which arcs and nodes comprise which polygons. The vector category attribute file ("dig_att" file) lists the category, or attribute, for each polygon, while the vector category label file ("dig_cat" file) lists labels for the categories, if they have been supplied by the user. Although in most cases, the supporting files are handled automatically by GRASS, the user must in some cases deal with them separately. For example, when performing a raster to vector conversion, it is necessary to first create the arc-node file and then the topology file. (Refer to the GRASS User's Guide and the GRASS Programmer's Manual for further information.)

GRASS window: a data structure containing information on the geographical location (UTM coordinates) and resolution of each map layer.

Group: see "Age group" or "Type group"

Index class: the values of many of the indices may be reported in index classes in order to display the distribution of index values.

Map layer: a two-dimensional array of pixels, each corresponding to a location on a map, and each containing some information about that location. In typical applications of the GLE programs, the pixel values are either age (in years) or a number identifying a particular element type.

Moving window: a square sampling unit, with odd dimensions (e.g. 3 pixels wide by 3 pixels high), that is moved pixel-by-pixel across the rows in a map layer. At each location the center pixel is assigned the value for a particular structural measure calculated for the part of the map layer corresponding to the window area.

Sampling unit: a polygon, with a certain size and shape, that identifies the area on a map layer that is to be used in calculating the GLE measures.

Type group: The group to which a particular part (element) of the landscape belongs. See "Age group"

4. BIBLIOGRAPHY

- Anselin, L. 1989. Spatial regression analysis on the PC: spatial econometrics using GAUSS. Draft manual, Department of Geography and Department of Economics, University of California, Santa Barbara, Calif. 97 pp.
- Austin, R.F. 1984. Measuring and comparing two-dimensional shapes. p. 293-312 in Gaile, G.L. and C.J. Willmott (eds.) Spatial Statistics and Models. D. Reidel Publ. Co., Boston.
- Ford, E.D. and E. Renshaw. 1984. The interpretation of process from pattern using two-dimensional spectral analysis: modelling single species patterns in vegetation. *Vegetatio* 56:113-123.
- Forman, R.T.T. and M. Godron. 1986. Landscape Ecology. John Wiley and Sons, New York. 619 pp.
- Gardner, R.H., B.T. Milne, M.G. Turner, and R.V. O'Neill. 1987. Neutral models for the analysis of broad-scale landscape pattern. *Landscape Ecology* 1:19-28.
- Griffiths, D.A. 1987. Spatial Autocorrelation: A Primer. Resource Publications in Geography, Association of American Geographers, Washington, D.C. 86 pp.
- Griffiths, D.A. 1989. Spatial regression analysis on the PC. Institute of Mathematical Geography, Syracuse University, Discussion Paper No. 1. 84 pp.
- Griffiths, G.H. and M.G. Wooding. 1988. Pattern analysis and the ecological interpretation of satellite imagery. Proceedings of the IGARSS '88 Symposium [Edinburgh, Scotland-Sept. 13-16, 1988], p. 917-922.
- Haralick, R.M. 1975. Statistical and structural approaches to texture. *Proceedings of the IEEE* 67:786-804.
- Haralick, R.M., K. Shanmugam, and I. Dinstein. 1973. Textural features for image classification. *IEEE Transactions on Systems, Man, and Cybernetics* SMC-3:610-621.
- Heinen, J. and G.H. Cross. 1983. An approach to measure interspersion, juxtaposition, and spatial diversity from cover-type maps. *Wildlife Society Bulletin* 11:232-237.
- Kennedy, S.K. and W.-H. Lin. 1986. FRACT-a FORTRAN subroutine to calculate the variables necessary to determine the fractal dimension of closed forms. *Computers & Geosciences* 12:705-712.

- Krummel, J.R., R.H. Gardner, G. Sugihara, R.V. O'Neill, and P.R. Coleman. 1987. Landscape patterns in a disturbed environment. *Oikos* 48:321-324.
- MacEachren, A.M. 1985. Compactness of geographic shape: Comparison and evaluation of measures. *Geografiska Annaler* 67B:53-67.
- Mead, R.A., T.L. Sharik, S.P. Prisley, and J.T. Heinen. 1981. A computerized spatial analysis system for assessing wildlife habitat from vegetation maps. *Canadian Journal of Remote Sensing* 7:34-40.
- Milne, B.T. 1988. Measuring the fractal geometry of landscapes. *Applied Mathematics and Computation* 27:67-79.
- Mulla, D.J. 1988. Using geostatistics and spectral analysis to study spatial patterns in the topography of southeastern Washington state, U.S.A. *Earth Surface Processes and Landforms* 13:389-405.
- Musick, H.B. and H.D. Grover. 1990. Image textural measures as indices of landscape pattern. p. 77-103 in Turner, M.G. and R.H. Gardner (eds.) *Quantitative methods in landscape ecology*. Springer-Verlag, New York.
- Odlund, J. 1988. *Spatial Autocorrelation*. Sage Publications, Beverly Hills, California. 87 pp.
- Oliver, M., R. Webster, and J. Gerrard. 1989a. Geostatistics in physical geography. Part 1: theory. *Transactions of the Institute of British Geographers* 14:259-269.
- Oliver, M., R. Webster, and J. Gerrard. 1989b. Geostatistics in physical geography. Part 2: applications. *Transactions of the Institute of British Geographers* 14:270-286.
- O'Neill, R.V., J.R. Krummell, R.H. Gardner, G. Sugihara, B. Jackson, D.L. Angelis, B.T. Milne, M.G. Turner, B. Zygmunt, S.W. Christensen, V.H. Dale, and R.L. Graham. 1988. Indices of landscape pattern. *Landscape Ecology* 1:153-162.
- Peet, R.K. 1974. The measurement of species diversity. *Annual Review of Ecology and Systematics* 5:285-307.
- Renshaw, E. and E.D. Ford. 1984. The description of spatial pattern using two-dimensional spectral analysis. *Vegetatio* 56:75-85.
- Risser, P.G., J.R. Karr, and R.T.T. Forman. 1984. *Landscape ecology: directions and approaches*. Illinois Natural History Survey Special Publication No. 2, Champaign, Illinois. 18 pp.

- Robertson, G.P. 1987. Geostatistics in ecology: interpolating with known variance. *Ecology* 68:744-748.
- Shapiro, M., J. Westervelt, D. Gerdes, M. Higgins, and M. Larson. 1989. GRASS 3.0 Programmer's Manual. USA-CERL ADP Report N-89/14. US Army Corps of Engineers Construction Engineering Research Laboratory, Champaign, Illinois.
- Urban, D.L., R.V. O'Neill, and H.H. Shugart, Jr. 1987. Landscape ecology: a hierarchical perspective can help scientists understand spatial patterns. *BioScience* 37:119-127.
- USA-CERL. 1988. GRASS 3.0 User's Manual. United States Army Corps of Engineers Construction Engineering Research Laboratory, Champaign, Illinois.
- Woodcock, C.E., A.H. Strahler, and D.L.B. Jupp. 1988. The use of variograms in remote sensing: II. Real digital images. *Remote Sensing of Environment* 25:349-379.

Figure 1

GRASS and GLE PACKAGE

Figure 2

STRUCTURE OF GLE PROGRAMS

Figure 3

STRUCTURE OF GLE ANALYSIS PROGRAMS

Gle.tex - texture analysis
Gle.patch - patch analysis
Gle.dist - distance analysis

Figure 4

SAMPLING AREAS

WHOLE MAP LAYER

REGIONS

SAMPLING UNITS

Random
Nonoverlapping

Systematic
Contiguous

Systematic
Noncontiguous

Stratified
Random

MOVING WINDOW

Figure 5

figure 6

TEXTURE METHODS

**DATE
FILMED**

6 / 1 / 93