DOE/PC-9201471

PETC REVIEW

Issue 1 • March 1990

Received by OSTI
APR 13 1992

PITTSBURGH
ENERGY
TECHNOLOGY
CENTER

Office of Fossil Energy, U.S. Department of Energy

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Pittsburgh Energy Technology Center
Office of Fossil Energy

United States Department of Energy

The PETC Review is published three times a year by the Pittsburgh Energy Technology Center. Comments, suggestions, and topics for future issues are welcomed. Please send to the attention of Dr. Bernard Blaustein, PETC, PO Box 10940, Pittsburgh, PA 15236-0940. Phone 412-892-6163, FTS: 723-6163.

EDITOR-IN-CHIEF:

Bernard Blaustein

MANAGING EDITOR:

Jamey Reiss

SENIOR EDITOR/WRITER:

Gary Martin

COPY EDITORS:

Diane Hamner

Jean Mills

DESIGN, LAYOUT:

Gail Aull

Christie Flora

Larry Stephens

Mark Stoutt

COVER PHOTO:

David Luttrell

CONSULTANT:

Richard Voelker

PETC REVIEW EDITORIAL BOARD:

Thomas M. Torkos, Chairman

Bernard D. Blaustein

Fred R. Brown

Ralph A. Carabetta

Sun W. Chun

Hugh E. Cothran

Melvin C. Keller

Curtis McBride

Patrice L. Schlata

Joseph P. Strakey

DOE/PC--92011471

DE92 011471

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

PITTSBURGH
E N E R G Y
T E C H N O L O G Y
C E N T E R

MASTER

FROM THE DIRECTOR

Welcome to the inaugural issue of the PETC Review — a new journal designed to keep the U.S. coal community abreast of the latest and most significant developments in PETC's programs.

PETC, a world leader in coal science and technology for more than 40 years, is one of two Energy Technology Centers that spearhead DOE's efforts to develop a new generation of sophisticated technologies to expand world markets for coal. The advanced technologies we now have in the R&D pipeline will — when we succeed in bringing them to the marketplace — take us much closer to realizing the full potential of coal as a clean, economical, versatile, and secure source of energy.

We, at PETC, have a dedicated staff of 300 scientists, engineers, managers, and administrators who operate under a yearly budget of about \$150 million to advance the technology of coal. That dedication is reflected, in part, by the recognition our staff receives for its efforts. I am proud to report that two of our staff members recently received prestigious national awards for their contributions to coal research.

Albert W. Deurbrouck, PETC's recently retired Coal Preparation Division Director, earned the 1990 Percy W. Nicholls Award for "notable scientific or industrial achievement in the field of solid fuels." The award was presented in February by the American Institute of Mining, Metallurgical, and Petroleum Engineers.

(Continued)

Receiving the prestigious Storch Award in Fuel Chemistry in 1990 is Dr. Bradley C. Bockrath, a group leader in PETC's Direct Coal Conversion group. This annual award recognizes contributions to fundamental or engineering research on the chemistry and utilization of coal or related materials.

We are also enthusiastic about a number of current in-house R&D projects, particularly in the coal liquefaction area. Two bench-scale units will be built at PETC to process coal to liquid fuels. One unit, for direct liquefaction, will process 200 pounds of coal per day to produce coal liquids. The other unit, for indirect liquefaction, will convert a syngas of carbon monoxide and hydrogen into one barrel of liquid per day. In early summer, we expect to award a contract to construct the units.

PETC's Office of Project Management is responsible for implementing the Office of Fossil Energy's national R&D program in 12 areas, including coal preparation, flue gas cleanup, advanced combustion technology, coal liquefaction, alternative fuels, and magnetohydrodynamics. These technologies are of great interest to the nation's coal community and of paramount importance to the nation's energy future. A large and growing share of the coal community is becoming an active partner in the development of those technologies. A prime example of that partnership is the innovative Clean Coal Technology Program, a \$5 billion DOE program in which more than half of the funds will be provided by the private sector. The program has been cited by the President as a key element in this country's efforts to reduce acid rain. Our Office of Clean Coal Technology is managing seven projects from among those awarded in the first round, 12 projects that resulted from the second round of the program and 9 projects that were awarded in Round 3. In all, the Clean Coal Technology Program is expected to have five rounds.

We hope that the PETC Review will help to provide an awareness of developments and activities in the coal community. Each issue will include a list of recent RD&D awards, a calendar of upcoming events, and other information useful for those who want to bid on our solicitations, attend our conferences, or otherwise do business with PETC.

The current issue features several of PETC's most important technological efforts: advanced physical coal cleaning methods, together with a flue gas control technology called duct injection, offer relatively low-cost, near-term options for combating acid rain. The article on direct, two-stage liquefaction describes the progress of our efforts to convert coal into liquid fuels; since the early 1980s, we've cut the cost at which coal liquids could compete with oil from \$60 to \$70 a barrel to \$35 a barrel. The article on the Clean Coal Technology Program provides a description of the program and lists the status of selected projects.

We welcome any comments, criticisms, or suggestions you may have for making this new publication as interesting, informative, and useful as possible. To facilitate your response, we have included a reader information card in this inaugural issue.

SUN W. CHUN JOINED PETC IN 1975. AFTER SERVING AS DEPUTY DIRECTOR FOR SEVERAL YEARS, HE WAS NAMED DIRECTOR IN 1979. A PH.D. CHEMICAL ENGINEERING GRADUATE OF THE OHIO STATE UNIVERSITY, SUN ALSO SPENT ABOUT SEVEN YEARS EMPLOYED AT THE GULF RESEARCH AND DEVELOPMENT COMPANY IN A VARIETY OF PROCESS ENGINEERING RESEARCH ASSIGNMENTS INVOLVING COAL LIQUIDS, PROCESS TECHNOLOGY, HYDROCARBON PROCESSING, AND EXPLORATORY RESEARCH. AS DIRECTOR OF PETC, SUN ADMINISTERS BOTH IN-HOUSE AND NATIONAL R&D PROGRAMS IN COAL PREPARATION, COAL LIQUEFACTION, ALTERNATIVE FUELS AND ADVANCED COMBUSTION, MAGNETOHYDRODYNAMICS, FLUE GAS CLEANUP, COAL SCIENCE, SUPPORTING TECHNOLOGIES, AND CLEAN COAL DEMONSTRATION PROJECTS ASSOCIATED WITH PETC'S TECHNICAL EXPERTISE.

TABLE OF CONTENTS

SO₂ CONTROL AND DUCT INJECTION: A SOLUTION TO ACID RAIN	6
---	----------

ACID RAIN ABATEMENT AND ADVANCED COAL CLEANING: A PRECOMBUSTION OPTION	11
---	-----------

TWO-STAGE LIQUEFACTION OF COAL	17
---------------------------------------	-----------

CLEAN COAL TECHNOLOGY: ENERGY <u>AND</u> THE ENVIRONMENT	26
---	-----------

INSIDE REVIEW	5
FOCUS ON	34
CALENDAR OF UPCOMING EVENTS	36
RD & D AWARDS	37
RECENT PAPERS & PUBLICATIONS	41
PROJECT HIGHLIGHTS	43
AROUND THE CENTER	49

INSIDE REVIEW

SO₂ CONTROL AND DUCT INJECTION: A SOLUTION TO ACID RAIN

Concern about acid rain and the anticipation of legislation requiring emissions control threatens the use of coal by the electric power industry. To mitigate these concerns, PETC initiated research into the feasibility of duct injection as an alternative to conventional emissions control technology.

ACID RAIN ABATEMENT AND ADVANCED COAL CLEANING: A PRECOMBUSTION OPTION

Along with other technologies to reduce acid rain, PETC is leading the research and development efforts on two coal cleaning technologies: selective agglomeration and advanced froth flotation.

T W O - S T A G E LIQUEFACTION OF COAL

The oil embargo of the early 1970s provided incentive for the United States to consider other fuel sources as an alternative to oil. Although liquefaction of coal is an old technology, PETC researchers have made great advances in furthering the viability of this technology.

CLEAN COAL TECHNOLOGY: ENERGY AND THE ENVIRONMENT

Despite debate about whether the United States could produce energy economically and in sufficient quantity without damaging the environment, the Clean Coal Technology Program is demonstrating technologies that show coal can be both efficient and environmentally acceptable.

SO₂ CONTROL AND DUCT INJECTION: A SOLUTION TO ACID RAIN

Acid rain has become an important issue with the potential to threaten increased use of coal by the electrical power industry. Yet, with the continuing problem of fluctuating oil prices and supplies, and a dormant nuclear power industry, coal remains this country's most abundant, most affordable, and most reliable source of energy. Improving coal's environmental acceptability, by reducing its acid rain potential, has thus become one of the highest priority energy goals. PETC has been at the forefront of this effort.

As part of the Department of Energy's work on acid rain control technologies, PETC conducted an extensive analysis of electric utility company coal-fired boilers and sulfur dioxide (SO₂) emissions. An initial element of PETC's larger Acid Rain Control Initiative Study, this analysis discovered, contrary to conventional wisdom, that the principal sources of SO₂ emissions include not only the high-sulfur "dirty coals" but also the medium-sulfur coals as well. Thus, if the effort to eliminate acid rain targeted only the dirtiest of coals, then a significant part of the problem would remain unaddressed.

Lime hydrate silo at Dravo's Hydrate Addition at Low Temperature (HALT) process pilot plant, at Ohio Edison's Toronto (Ohio) Station.

Because of this finding, PETC put together a comprehensive program of coal-related acid rain research. One of the larger activity areas involved flue gas cleanup, with particular emphasis on the control of SO_2 .

INITIAL GOALS

According to Charles Drummond, PETC's Acting Division Director of the Flue Gas Cleanup Program, "The ultimate goal of this program is to promote a wider use of coal. So to achieve that goal, we have to develop the technologies needed to make the burning of coal economically and environmentally acceptable. We currently have research under way in a number of areas, but our biggest effort involves the development of low-cost SO_2 emissions control technologies that can be used to retrofit existing coal-fired power plants. If all goes well, we hope to have technology ready for commercialization by 1992."

To date, most of PETC's work has focused on being able to retrofit older power plants that pre-date the 1971 passage of the New Source Performance Standards (NSPS). These "nonregulated" utility boilers constitute the largest remaining source of uncontrolled SO_2 emissions in the United States, with approximately 200,000 MWe of generating capacity throughout the East and Midwest.

As initially defined, new, low-cost, readily installed emissions control technologies should be capable of removing at least 50% of the SO_2 content in flue gas, at a cost of less

than \$500 per ton of SO_2 removed. This is about one-half of the current baseline cost for removing the same amount of SO_2 using conventional wet scrubber technology. Because each power plant has its own unique set of physical characteristics and operating requirements, all new technology should, in addition, be flexible enough to permit application in a variety of limited space situations.

Candidate technologies fall into three categories, depending upon their point of application in the power plant: either before, during, or after combustion. Thus far, however, the principal focus of the Flue Gas Cleanup Program has been on capturing SO_2 after combustion, using in-duct injection of a calcium-based chemical reagent (see Figure 1). Such injection, made between the air preheater and the electrostatic precipitator, produces an environmentally safe, dry solid waste that can be disposed of with relative ease. Because capital investment costs are low, the economics of a duct injection system are quite favorable in comparison with conventional limestone wet slurry scrubbing systems.

As described by Drummond, "One of the main goals of our duct injection work is to develop a technology that can be used to retrofit older power plants economically. These boilers have limited service lives, and in many instances, they're used only as peaking units in a backup capacity for a utility's newer boilers. So, low capital costs are absolutely critical.

"Another critical concern involves ease of installation because utilities just can't afford extended periods of boiler down—time that require the purchase of replacement power. So, it was these types of very real savings that helped make duct injection technology the principal candidate for further development."

PROOF-OF-CONCEPT RESEARCH

Once it was decided to initiate duct injection research, PETC established four criteria for technology development: the

technology had to (1) achieve greater than 50% SO₂ removal; (2) obtain greater than 35% sorbent utilization; (3) result in an acceptable dry waste material; and (4) reduce the cost of emissions control to less than \$500 per ton of SO₂ removed. During 1985, three promising duct-injection processes were identified and funded for research at the proof-of-concept (POC) level: (1) Hydrate Addition at Low Temperature (HALT); (2) Confined Zone Dispersion (CZD); and (3) In-Duct Scrubbing (IDS). POC testing was done on actual slipstreams at operating coal-fired power plants. All POC work was completed in 1988.

Dravo Lime Company tested the HALT concept at a 5-MWe pilot unit at Ohio Edison's Toronto Power Station. Dry hydrated lime was injected into a duct containing humidified flue gas, both upstream and downstream from the point of humidification. Fifty percent of the sulfur was removed at a calcium-to-sulfur ratio of 1.9. Wall wetting and deposition problems were reported.

Bechtel National demonstrated the CZD process at the Campbell Power Station of Consumer Power Company at New Holland, Michigan. It used two nozzles to spray a pressure-hydrated dolomitic lime slurry into a flue gas slipstream with a gas flow equivalent of 5 MWe. Fifty percent of the sulfur was removed at a calcium-to-sulfur ratio of 1.5 to 1.8. As was true with the HALT process, Bechtel reported wall deposition.

General Electric Environmental Services demonstrated the IDS process at Ohio River Company's Muskingum River Power Plant in Beverly, Ohio. A rotary atomizer was used to spray a reactive slurry of hydrated lime and water into a flue gas duct with a slipstream equivalent of 12 MWe. Fifty percent sulfur removal was achieved at a calcium-to-sulfur ratio of 1.5. Again wall wetting and deposition were two of the problems encountered.

Although each of the three POC studies met DOE's four minimum criteria, they also showed the need for more scientific and engineering information to make this technology ready for commercial development. Specific areas for improvement include:

- Sorbent reactivity and behavior;
- Duct transport and chemical processes;
- System hydrodynamics;
- Nozzle design and operation;
- Humidification system design;
- Wall deposition of sorbent and fly ash;
- ESP performance; and
- Dry waste disposal.

A COMPREHENSIVE RESEARCH PROGRAM

"The proof-of-concept work that we initiated in 1985 accomplished what it was supposed to do," Drummond explained. "It showed us that the duct injection technology does have commercial promise."

But in order to make it more attractive to private developers, we needed much more information. So in 1987, we identified a 5-year, comprehensive research program to take this technology to a point of commercial readiness. We identified all the issues that need to be resolved and all the data needs.

"We're planning to end up at the completion of this program with a kind of 'generic' duct-injection technology," he said, "that will be applicable to all kinds of existing utility boiler situations. We'll also have published a design handbook that will give utilities all the engineering information and data they'll need to design environmentally acceptable retrofit systems for their own plants — sort of a do-it-yourself manual for the utility industry."

PETC's 5-year program has four types of tasks: (1) exploratory research and development; (2) engineering development; (3) systems integration; and (4) design basis validation. Its purpose is to develop an engineering design base that will: (1) be usable for retrofitting existing coal-fired utility boilers; (2) facilitate confident

predictions about scale-up operation; (3) be applicable to a range of boiler sizes, flue gas component concentrations, and duct configurations; and (4) provide a sound foundation for additional, non-Federal development of the technology. In addition to developing a design basis for duct-injection technology, this program will also

validate the design information by testing it on a full-scale operating plant.

In 1988, contracts for each of these efforts was let and work was begun. A Duct Configuration Survey has been completed by Burns & Roe Services Corporation, PETC's on-

site technical support contractor. In addition to the publication of a design handbook, this 5-year program will also result in the publication of 27 topical reports on various aspects of the research. Several of these reports have already been published.

"The country is seriously considering the acid rain problem," Drummond said, "and legislation requiring some type of emissions control system on all coal-fired boilers is currently being debated by Congress. We try to anticipate what these future requirements might be and develop technology accordingly.

"Of necessity, retrofitting existing plants with new emissions control technology requires a comprehensive, yet very flexible, approach. For small- and medium-sized plants that are burning low- and medium-sulfur coals, the use of duct injection methods seems to be the most effective way to go right now. However, for larger plants that are burning high-sulfur coals that require high-efficiency removal of sulfur oxides, a combined technology approach seems most feasible, using both duct injection and advanced coal cleaning methods.

"We're also working to develop other competitive technologies as well, particularly for use on larger existing boilers that are burning high-sulfur coals—the Tung flue gas desulfurization process, for instance. This is a uniquely simple,

" D U C T INJECTION TECHNOLOGY DOES HAVE COMMERCIAL PROMISE."

Figure 1.
Conceptual
duct sorbent
injection
process

liquid-liquid extraction and steam stripping process that is used to regenerate a sodium-based scrubbing liquor.

"This process was developed by retired MIT Professor Shao Tung, who has recently completed the development of the extraction step in laboratory studies. A pilot plant test unit is being planned for the Dunkirk Station of Niagara Mohawk. DOE is funding this research effort. It's a very promising concept that's being developed

DOE IS FUNDING A TUNG FLUE GAS DESULFURIZATION PILOT PLANT TEST UNIT FOR THE DUNKIRK STATION OF NIAGARA MOHAWK.

specifically to compete with lime/limestone scrubbers. It produces a salable by-product—sulfur—and there is no need for waste disposal.

"So even though our current emissions control work seems to be emphasizing duct-injection technology," Drummond concluded, "we're actually working on a broad assortment of technology options, to be used in a variety of ways, depending on the specific needs of a utility. Although we don't know what future regulations might require, by 1992 we want to have on hand an array of environmentally acceptable technologies that will enable the power industry to keep burning coal far into the future."

CHARLES J. DRUMMOND JOINED PETC

IN 1976, AFTER COMPLETING TWO YEARS OF PEACE CORPS SERVICE IN CASABLANCA, MOROCCO, AS AN ANALYTICAL CHEMIST IN THE MOROCCAN NATIONAL TESTING LABORATORY. AS PROGRAM COORDINATOR, CHARLIE IS RESPONSIBLE FOR THE MANAGEMENT OF DOE'S

FLUE GAS CLEANUP PROGRAM, INCLUDING PROJECTS WITH PRIVATE INDUSTRY, UNIVERSITIES, AND VARIOUS LABORATORIES THROUGHOUT THE COUNTRY. HE WAS PREVIOUSLY RESPONSIBLE FOR THE COORDINATION OF ALL IN-HOUSE FLUE GAS CLEANUP RESEARCH ACTIVITIES AND HAS WORKED ON THE DEVELOPMENT OF WASTEWATER TREATMENT TECHNOLOGY FOR COAL LIQUEFACTION AND GASIFICATION PROCESSES. CHARLIE IS A 1973 CHEMICAL ENGINEERING GRADUATE OF VILLANOVA UNIVERSITY AND HAS COMPLETED HIS COURSE WORK FOR A MASTER'S DEGREE IN CIVIL ENGINEERING FROM THE UNIVERSITY OF PITTSBURGH.

ACID RAIN ABATEMENT AND ADVANCED COAL CLEANING: A PRECOMBUSTION OPTION

Advanced coal cleaning is a second technological option in DOE's war against acid rain. Similar to the origin of the flue gas-duct injection research program, interest in advanced coal cleaning as a means of reducing the acid rain potential of coal-fired power plants began with PETC's Acid Rain Control Initiative Study.

In addition to showing that the combustion of both medium- and high-sulfur coals contributes significantly to boiler sulfur oxide emissions, this 1987 study also demonstrated that more than 60% of the sulfur in the coals studied was in a nonorganic, pyritic form. Unlike organic sulfur, which requires chemical processing to remove, most pyritic sulfur can be separated from coal using relatively simple grinding and cleaning procedures. Thus, the development of advanced coal cleaning technology has the promise of providing a low-cost, precombustion means to reduce sulfur oxide emissions. The Acid Rain Control Initiative Study preliminarily explored the feasibility of developing a number of advanced coal cleaning technologies.

PRELIMINARY FINDINGS

PETC investigators analyzed the data base developed during its 1985 national survey of 1166 coal-fired utility boilers to determine the amount, quality, and source of the coal burned in each boiler and the amounts of SO_2 emitted during combustion. On the basis of the moderate- and high-sulfur coals identified, four major seams/coals were chosen as being typical.

Each of these coals was then further investigated to determine: (1) the technical feasibility and (2) the associated capital, maintenance, and operating costs required to clean each using conventional and, where necessary, advanced cleaning methods to a level of 1.2, 1.8, 2.4, and 3.6 pounds of potential SO_2 emissions per million Btu. Many advanced cleaning methods were considered; however, two were identified as being most promising: selective agglomeration and advanced froth flotation. Additional analyses were then carried out.

It was concluded on the basis of these preliminary investigations that advanced cleaning alone can reduce SO_2 emissions from moderate-sulfur coals to below the original EPA New Source Performance Standards (NSPS) requirement of 1.2

pounds of SO_2 per million Btu. Where high-sulfur coals were used, however, advanced coal cleaning would have to be combined with some form of flue gas desulfurization in order to meet these same requirements.

TWO CANDIDATE TECHNOLOGIES

The investigators evaluated numerous physical coal cleaning technologies on the basis of performance, technical capabilities, and readiness for commercialization by 1992. The following were selected as having the best potential for separating pyritic sulfur from ultrafine coal:

Selective Agglomeration — An agglomerating liquid that is immiscible in water is added to an aqueous suspension of finely ground feed coal. When vigorously agitated, the hydrophobic coal particles cluster into large flocs in the nonaqueous fluid. The particles of mineral matter, still dispersed in the water, can then be separated from the coal by screening.

Using an X-ray photoelectron/scanning auger spectrometer to study the surface composition and structure of coal.

**Bechtel
microbubble
flotation
flowsheet**

Advanced Froth Flotation — A stream of finely dispersed air bubbles is passed through a slurry of coal and water. The air bubbles preferentially attach to the coal particles, removing them from the slurry as a froth. The mineral matter, having a low affinity for the air bubbles, remains in the water. Cleaning is, therefore, achieved by separating the froth from the mineral and water mixture. Advanced versions of this technology (see figure above for example), which attempt to separate ultrafine coal from pyrites, will use extremely fine bubbles, new flotation cell designs, and chemical reagents that can more specifically alter the behavior of pyrite.

According to Richard E. Hucko, Director of the PETC Coal Preparation and Solids Transport Division, "Both of these coal cleaning technologies should work adequately on medium-sulfur coals — each reducing sulfur emissions below the NSPS standard. And our preliminary findings also show that each should cost about half of what conventional flue gas scrubbing costs."

Based on the preliminary findings of the Acid Rain Control Initiative Study, the PETC investigators next designed a technology development program that is intended to have a technology and design base in place by 1992 for use on a prototype commercial facility. This program, named the Acid Rain Control Technology Initiative, has four requirements: (1) the advanced cleaning technologies must be broadly applicable to both high- and moderate-sulfur coals; (2) the technologies must reduce pyritic sulfur, thereby significantly reducing acidic emissions during combustion; (3) the cleaned coal products must be acceptable to utility operators; and (4) the total costs must be significantly less than those for alternative acid rain mitigating technologies. The implementation of this research program began in 1988.

ACID RAIN CONTROL TECHNOLOGY INITIATIVE: AN OVERVIEW

This program has three major elements and is concerned with major coal-producing regions in the United States (as

shown on the map). The first part involves getting a better understanding of the surface properties of finely ground coal and its associated mineral impurities, especially pyrite. The second part involves the engineering development and design of the individual advanced coal cleaning technologies. The third part of the program is concerned with the development of a comprehensive computer simulation model of the coal cleaning technologies.

As explained by Hucko, "In order to separate the pyritic sulfur from the surrounding coal, it must first be ground to a fine size so the individual particles of coal are as small as the grain size of the

**"T H E R E
R E A L L Y I S N ' T
A N Y T I M E T O
W A I T . . .
B E F O R E
S T A R T I N G T O
M O D E L T H E
P R O C E S S E S ."**

pyrite. At these fine grain sizes (about the consistency of talcum powder), particle surface properties become very important. The success we've obtained so far with these processes has been dependent on the differences in surface characteristics. So our technology development program logically begins with an integrated look at how

to control these properties during grinding. Coupling this surface behavior to process dynamics can then be better exploited as each technology progresses from bench-scale to proof-of-concept (POC) testing."

"The second part of the program," Hucko continued, "will establish an engineering design base to support process development, evaluation, and scaleup to a small commercial plant that is able to process 20 to 30 tons of coal per hour. We have two contractors working on this part of the program — one for each of the cleaning technologies.

"The third phase of the program is called Engineering Design and Analysis. The computer simulation model that will be developed in this part of the research will incorporate all the critical variables identified in the first two elements of the program. Even though detailed simulations will be contingent on the first two parts, work on generalized codes can begin

immediately. Since all three elements of work are scheduled for completion in 1992," Hucko added, "there really isn't any time to wait for actual experimental results before starting to model the processes."

PROGRAMS AND PLAYERS

PETC completed the procurement process for the initial phase (Coal Surface Control) of its Acid Rain Control Technology Initiative in September 1988 by awarding two contracts: one to the University of California at Berkeley and another to the University of Pittsburgh. Although both teams will investigate the general phenomenological aspects of coal surfaces, the work of each will be process-specific.

The University of California team includes the University of Utah, Columbia University of New York, and Praxis Engineers of California. This team will be concerned primarily with the methods and means to control or modify the coal surface characteristic impacts on the froth flotation process. It will also be responsible for conducting a 13-month coal weathering investigation on three different coals, of three different sizes, stored in three different environments.

The University of Pittsburgh team will be looking at the impact of similar coal surface phenomena on the selective agglomeration process. Westinghouse Electric, a team member, will be responsible for all quality assurance/quality control concerns.

"Neither of these surface control, 36-month contracts involves purely basic research — all the work, though fundamental, is very much application oriented. And most of it will be accomplished during the first 13 months, so it can feed, early on, into the engineering development work on these processes. Of particular importance in this regard will be the results of the coal weathering studies done by the University of California — how surface oxidation may or may not affect coal's hydrophobic characteristics and pyrite's behavior."

Two firms have also been selected for the engineering development work on the cleaning processes: Kaiser Engineers of Pittsburgh, Pennsylvania, and Southern Company Services of Birmingham, Alabama. Kaiser will work on froth flotation and Southern Company Services on selective agglomeration. Over a period of 42 months, the contractors will conduct bench-scale studies, which in turn will lead to POC testing of larger units. The POC results should suffice to prove the technical viability of each process and will also give industry adequate information to commercially develop each technology.

Kaiser, working with Babcock & Wilcox, Consolidation Coal, and others, is evaluating and testing all critical parameters in the froth flotation process, including coal grinding, flotation cell configuration, reagent type and dosages, fine coal handling, and drying. It is expected that POC tests will be conducted

at the Ohio Coal Development Office's new coal preparation test facility in Beverly, Ohio.

Southern Company Services is working with the Alberta Research Council of Canada and Praxis Engineers of California to develop a viable selective agglomeration technology. As with the other cleaning process, investigators will evaluate and test each critical step in the agglomeration process. A technical data base will also be compiled for design and scaleup to larger systems. Southern will design and build its POC module at Wilsonville, Alabama.

The Engineering Design and Analysis phase of the three-part Acid Rain Control Technology Initiative will be performed by Aspen Technology, Inc., of Cambridge, Massachusetts. Aspen Technology will work with Kaiser Engineers and the Electric Power Research Institute to apply a commercially available flexible process flowsheet simulator (ASPEN PLUS) as a

Key coal-producing regions of concern in the Acid Rain Control Technology Initiative.

framework for modeling the two advanced physical coal cleaning technologies being studied under this initiative. The simulator will then be used to (1) identify data and information gaps for the coal cleaning technologies, (2) determine areas for process improvements and opportunities for cost reduction, and (3) estimate the larger-scale technical and economic performance of the processes.

ECONOMICS ARE THE KEY

Asks about the anticipated reaction of the utility industry to the availability of advanced coal cleaning technology, Hucko was very positive. "I'd have to say I'm very optimistic about the industry's acceptance of any new technology that will enable it to reduce its SO₂ emissions economically," he said. "But the key here is the word 'economically'."

"If, as most people anticipate, some type of emissions control legislation is forthcoming, then utilities will be forced to

**"WE ARE
CONVINCED
THE SAVINGS
ARE THERE."**

comply. In this case, because everyone pays, the associated costs are less critical. However, since we started this program, it's been our goal to develop technology—whether for advanced cleaning or for flue gas cleanup—that costs less

per ton of SO₂ removed than does conventional wet scrubbers. Conventional lime/limestone scrubbing costs are currently averaging around \$1000 per ton of SO₂ removed. And our early projections for advanced coal cleaning costs are about 50% less than that, or about \$500 per ton. So it looks as though, at least at this early stage in our work, we're meeting this very critical cost criterion.

"Now if these projections hold and if advanced coal cleaning can reduce SO₂ emissions more economically than can (on a dollars per ton of SO₂ removed basis) conventional scrubbers, then it's quite reasonable to assume that utilities will adopt

this new technology. We've done extensive sensitivity analyses, including all the applicable variables—type of coal, sulfur content, age of plant, etc.—and this is what we're finding.

"Of course the costs will vary with each plant situation," Hucko explained, "but we're convinced the savings are there. And we think industry will be convinced as well, just as soon as our current research is completed and we have better numbers available. Advanced coal cleaning was always intended to be a technology option for both new plants and also for the retrofitting of existing plants. Everything we know right now about the economics involved says that it will meet both of these needs."

RICHARD E. HUCKO HEADS PETC'S

COAL PREPARATION AND SOLIDS TRANSPORT DIVISION AND IS CURRENTLY RESPONSIBLE FOR THE IMPLEMENTATION OF ALL COAL PREPARATION AND SOLIDS TRANSPORT RESEARCH ACTIVITIES.

A GRADUATE OF THE UNIVERSITY OF PITTSBURGH, RICH HAS AN M.S. DEGREE IN CIVIL ENGINEERING. INITIALLY EMPLOYED AT BRUCETON BY THE U.S. BUREAU OF MINES IN 1974, HE TRANSFERRED TO THE DOE IN 1977. FROM THE OUTSET, RICH HAS WORKED ALMOST EXCLUSIVELY IN THE AREA OF COAL BENEFICIATION RESEARCH, WITH INITIAL EMPHASIS ON SELECTIVE FLOCCULATION AND HIGH-GRADIENT MAGNETIC SEPARATION AND MOST RECENTLY IN THE DEVELOPMENT OF TECHNOLOGIES TO PRODUCE SUPERCLEAN COALS.

TWO-STAGE LIQUEFACTION OF COAL

The production of liquid fuel from coal using Two-Stage Liquefaction (TSL) has been under development in the United States since 1980. During this time, the process has been continuously improved to the point that it now produces the highest liquid yield and product quality of any liquefaction process worldwide. TSL can now be successfully applied to both bituminous and subbituminous coals, overcoming many of the problems associated with earlier processes. In addition, new information from laboratory studies is providing fundamental understanding of coal reactivity and hydrogen transfer that will lead to even more significant improvements in the future. PETC has been involved in coal liquefaction R&D since the early 1940s, when the Bureau of Mines initiated this effort as a part of its mission to advance coal as an alternative fuel source in the United States.

The purpose of the liquefaction program is to produce liquid fuel from coal — producing a high-grade refinery feedstock that can be made into gasoline, diesel fuel, or heating oil. During the last 10 years, the TSL process has become more commercially competitive with imported crude oil. The TSL product from the process development plant in Wilsonville, Alabama, is much better as a feedstock than is typical crude oil — it has a premium refinery value. That was not true a decade ago.

Integrated
Two-Stage
Liquefaction
Facility
Wilsonville,
Alabama

Early liquefaction processes used only one reactor. Today, the state-of-the-art is two reactors placed in series, resulting in a two-stage process that is continually evolving. For example, the two biggest improvements to the TSL process since the early 1980s have been better utilization of catalysts and the development of greatly improved recycle liquids. Because of these two improvements, both the quality and quantity of yield have increased. Ultimately, that translates to lower fuel costs.

SOME HISTORICAL BACKGROUND

Coal liquefaction technology began in 1869 when Bertholet treated coal with hydroiodic acid (518°F [270°C] for 24 hours) and obtained a liquid yield of about 60%. Similar liquefaction results were also obtained from dried wood and partially carbonized wood; however, coke and graphite could not be converted. In 1911, Bergius conducted the first coal hydrogenation (662°F [350°C] at 1500 to 3000 psig pressure) in the absence of a catalyst. In evaluating different coals, Bergius found that younger coals (e.g., lignite, brown coal, and bituminous coals) gave higher oil yields than did the older coals (e.g., anthracite). By 1927 Bergius had demonstrated the commercial operability of single-stage liquefaction. However, gasoline yield was small and was of a lower quality than gasoline from petroleum. In 1924 at BASF laboratories, Pier prepared sulfur-resistant catalysts from oxides of molybdenum, tungsten, iron, and other metals. This breakthrough led to the first production of white gasoline by reacting hydrogen and brown coal tar vapor with molybdenum and zinc oxide catalysts. Serious deactivation of the catalyst occurred, however.

The hydrogenation of tars from brown coal (with high concentrations of finely ground molybdenum suspensions in the feed stock) was found to be reasonable at 3000 psig and temperatures of less than 842°F (450°C). However, at more extreme conditions (e.g., higher coal tar flow,

temperature, or pressure), the slurry-phase reactor performance and catalyst activity deteriorated drastically. As a result, the search for better catalysts continued.

During this same period, coal liquefaction technologies were also being developed in Germany. The most notable of these was the Pott-Broche process,

C O A L LIQUEFACTION TECHNOLOGY BEGAN IN 1 8 6 9.

developed in 1927. This was a two-stage process in which the coal was initially liquefied at between 1450 and 2200 psi at a temperature between 780°F (415°C) and 806°F (430°C) and at a residence time of one hour. The filtered products were then further hydrogenated in the liquid phase using a supported metal catalyst. Difficulties in filtering and the poor quality of products, however, prevented the commercial development of this process.

EARLY COMMERCIALIZATION OF COAL LIQUEFACTION

The commercial liquefaction of coal began in 1927 in Germany. At the height of World War II, in 1943, there were 12 coal liquefaction plants producing over 12,000 tons/day of motor fuel. Concurrent with the developments in Germany, substantial coal and coal tar hydrogenation efforts were also proceeding in France, Great Britain, Japan, and the United States. However, the only commercial plant outside of Germany was in Billingham, Great Britain.

In the late 1940s, the number of new oil fields discovered in the United States decreased for the first time in this country's history. Therefore, a major emphasis began on the conversion of coal to liquid fuels. This effort was spearheaded by the Bureau of Mines in Pittsburgh. With the passage of the Synthetic Fuel laws in 1944 and 1948, the Bureau's program was expanded to include a semicommercial coal liquefaction plant producing 300 Bbl/day of gasoline. However, improvements in the technology were modest and extensive supplies of low-

cost oil became available from the Middle-East. Therefore, commercial interest in coal liquefaction dwindled. During the 1950s, both inside and outside of the United States, only laboratory and bench-scale work was performed.

Interest in coal liquefaction was renewed in 1962 with the establishment of the Office of Coal Research and the development of the Solvent-Refined Coal (SRC) process by the Spencer Chemical Co. Along with the non-catalytic SRC process, several catalytic processes were also being developed in the 1960s. Some of these processes had operational or other difficulties and were, therefore, abandoned. Others, (e.g., H-Coal, EDS, and the SRC-I and the SRC-II processes) continued to be developed throughout the 1970s.

SINGLE-STAGE PROCESSES

The TSL process has evolved from the 30 years of single-stage process development experience in direct liquefaction in the United States. The evolution of the TSL technology can be better understood through the contributions made by the major single-stage processes, including the following:

H-Coal: This is a direct catalytic coal hydroliquefaction process invented in 1963 by Hydrocarbon Research, Inc. (HRI). Development of the H-Coal process proceeded through conceptual stages to bench-scale and Process Development Unit (PDU) studies. This work culminated in the construction and operation of an H-Coal pilot plant, a 200- to 600-ton/day facility in Catlettsburg, Kentucky. The key component of the H-Coal process is its ebullated-bed reactor. Pulverized coal, recycle liquids, hydrogen, and a catalyst are brought together in the reactor to convert the coal into hydrocarbon liquids and gaseous products. This single step converts

coal slurry feed to distillate products in the Syncrude operating mode and to distillate products and low-sulfur deashed residuum in the Boiler Fuel mode. This process has several unique features and advantages:

Figure 1.
Hydrogen
consumption and
product yields for
single-stage
processes

- coal dissolution and upgrading to distillate products are accomplished in one reactor;
- products have a high H/C ratio and low heteroatom content as the result of catalytic hydrogenation;
- a high throughput of coal is achieved because of the rapid catalytic hydrogenation rates; and
- ash is removed by vacuum distillation, followed by gasification of the vacuum-tower bottoms to generate the hydrogen required by the process.

It also has several shortcomings:

- Its high reactor temperature results in excessive thermal cracking and, consequently, high hydrocarbon gas yields.

- The hydrogen consumption is high relative to the liquid yield.
- The product has considerable vacuum gas oil and is usable, therefore, only as a boiler fuel.

SRC-I: This is a thermal liquefaction process in which solvent, coal, and hydrogen are reacted in a "dissolver" reactor to produce a non-distillable resid (or extract) that is usable as a clean boiler fuel after deashing. Although reaction conditions are just slightly less severe than in the H-Coal process, the absence of a catalyst diminishes hydrogenation rates. This process also has technical and economic drawbacks, including:

- The all-distillate solvent is often of poor quality, causing caking or precipitation of heavy product, usually within the preheater, which is installed before the dissolver.
- The process requires a more expensive deashing system.

Ultimately, the low market value of the boiler fuel product rendered SRC-I economically unattractive when compared with other processes.

Exxon Donor Solvent (EDS):

The EDS process uses a non-catalytic hydroprocessing step to produce liquid hydrocarbons. Its important feature is the hydrogenation of the recycle solvent, which is used as a donor of hydrogen to the slurried coal in a high-pressure reactor. Reaction conditions are similar to those of the SRC-I and H-Coal processes. The product distribution is close to that of H-Coal, although product quality is poorer because of the absence of a hydrotreating catalyst. Several of the EDS features have been incorporated into TSL, including:

Figure 2.
Investment
costs for
single-stage
processes

- The donor solvent concept, which proved that a catalyst is not necessary for effective dissolution of coal.
- Bottoms recycle, which was shown to dramatically improve operability.
- Use of ashy recycle, which allows subbituminous coal to be effectively processed without a disposable catalyst.

SRC-II: The SRC-II process employs direct hydrogenation of coal in a reactor at high pressure and temperature to produce liquid hydrocarbon products, instead of the solid products of the SRC-I process. However, the SRC-II process is limited to coals that contain "catalytic" mineral matter, which excludes all lower-rank coals and some bituminous coals. In addition, the high temperature, thermal liquefaction reaction results in high yields of hydrocarbon gases and poor liquid product quality, relative to those produced by the H-Coal process.

The hydrogen consumption and product yields, using typical bituminous coals, for

all four processes are shown in Figure 1. The capital costs for each process are given in Figure 2.

THE NEXT STEP

By the late 1970s, it was apparent that the costs associated with single stage liquefaction processes could not be justified to produce boiler fuel. Coal liquefaction is better applied to making of higher value-added products like transportation fuels. This finding led to the Non-Integrated Two-Stage Liquefaction (NTSL) technology. However, NTSL was an inefficient process, even though a hydrotreating section had been added to maximize conversion of resid to distillates. Therefore, NTSL development was short-lived. It was replaced by a staged integrated approach, which has been the basis for all subsequent developments.

THERMAL INTEGRATED TWO-STAGE LIQUEFACTION

Studies done by Consol and Mobil, and at Wilsonville in the late 1970s, showed that with a well-hydrogenated solvent, the Short-Contact-Time (SCT) liquefaction process was a preferred thermal dissolution procedure because it eliminated the inefficient thermal hydrogenation inherent in the SRC-I process. Meanwhile, researchers at Cities Service Research and Development were successfully hydrocracking SRC-I resid, using LC-Fining at relatively low temperatures. It soon became apparent that a combination of these two reaction stages, wherein the second stage (i.e., the low-temperature, LC-Fining) provides the liquefaction solvent to SCT first stage, had the potential to liquefy coal more efficiently than any of the single-stage processes. This recognition led to

Figure 3.
Block flow
diagram of
integrated
two-stage
liquefaction

two ITSL processes—the Lummus ITSL and the Wilsonville ITSL.

Lummus ITSL: The Lummus ITSL process consists of an SCT coal dissolution first stage and an LC-Fining catalytic upgrading second stage (see Figure 3). Coal is first slurried with recycled solvent from LC-Fining and is then converted to a liquid in the SCT reactor. The resid fraction of this stream is then hydrogenated/hydrocracked to distillates in the LC-Fining stage, where recycle solvent is also generated. The ash is removed by the Lummus Antisolvent Deashing process. The recycling of the full-range bottoms, including resid, couples the two reaction stages and produces high yields of all distillate products. Several improvements over previous processes are as follows:

- The SCT coal dissolution reactor accomplished all that the SRC-I process did but much more efficiently and in a smaller volume reactor. Its hydrocarbon gas yields were reduced to about 1%, and heteroatom removal was comparable.
- ITSL showed that (1) ashy recycle is not detrimental to catalyst activity; (2) subbituminous coal is an attractive feed for direct liquefaction and actually has some advantages over bituminous coal; and (3) a lighter product can be made with little loss in hydrogen efficiency. This last point is extremely important for commercialization because lighter products have fewer environmental problems.

Figure 4.
HRI catalytic
two-stage
unit

■ Wilsonville ITSL: DOE's Wilsonville, Alabama, plant uses a Reconfigured Integrated Two-Stage Liquefaction (RITSL) process based on the Lummus process. Slurry preparation, thermal liquefaction, and fractionation steps are the same; however, the vacuum bottoms containing the thermal resid, unconverted coal, and ash are fed directly to the ebullated bed hydrotreater. Because the hydrotreater feed was not deashed, it contained all the coal ash along with unconverted coal and heavy organics that would normally be removed in the deashing step in the Lummus ITSL mode. The above changes in the ITSL process have resulted in conversions of over 95% with Wyodak subbituminous coal.

catalysts with a nickel-molybdenum catalyst that has a bimodal pore distribution and larger micropores. The latest reported results from this plant, using Illinois No. 6 coal, show a 78% distillate yield. Hydrogen efficiency is over 10 pounds of distillate per pound of hydrogen reacted. In addition, the two catalytic reaction stages produce a liquid with low heteroatom concentrations and a high hydrogen content, making this liquid's properties closer to petroleum than any coal liquids made by earlier processes.

**ALL STUDIES
SHOW THAT
THERE IS A
DEFINITE
TREND
TOWARD
LOWER COST
PER BARREL OF
LIQUID
PRODUCT.**

TODAY: CATALYTIC TWO-STAGE LIQUEFACTION (CTSL)

■ In 1982 HRI, a Lawrenceville, New Jersey research contractor to DOE for more than 15 years, initiated the development of a CTSL concept. In this new process, the first stage temperature was lowered to:

- (1) more closely balance hydrogenation and cracking rates and
- (2) allow the recycle solvent to be hydrogenated *in situ*, facilitating hydrogen transfer to coal dissolution.

The second stage was operated at higher temperatures to promote resid hydrocracking and to generate an aromatic solvent, which is then hydrogenated in the first stage (see Figure 4). CTSL development has also incorporated some new thinking about deashing.

The product from the second stage has undergone catalytic hydrogenation twice and is, therefore, a much lighter deasher feed than is the SRC-I resid, for which deashers were designed. Also, the CTSL replaced previous

■ Wilsonville CTSL: Wilsonville has made substantial modifications to process operating conditions with the most significant being the reactor temperatures. At Wilsonville, the first reactor is at the higher temperature, and the second reactor is kept at slightly lower temperatures. Distillate yields at this plant have also been up to 78%. However, Wilsonville has yet to test extinction recycle of distillates that boil at temperatures above 650° F.

TECHNOLOGY SUMMARY

After the oil embargo of the early 1970s, substantial improvement in liquefaction processes and the catalysts associated with these processes have been made. Liquid yields have increased, and simultaneously, the quality of liquids has also been improved substantially. Distillate yields have increased from 41% to 78%, resulting in equivalent liquid yields of about 5 barrels/ton of MAF bituminous coal (e.g., Illinois No. 6 and Ohio No. 6). Product quality is comparable to, or better than, No. 2 fuel oil; good hydrogen content and very

low heteroatom content are also common. Several studies have charted the economic progress of the TSL process and all show the same trend of reduced cost per barrel of liquid product (see Figure 5).

THE FUTURE OF DIRECT LIQUEFACTION

The TSL process is the process being used today. However, later this year, development will begin on an improved process. At this time, there is no indication of how this new process might be configured — whether it will be one, two, or maybe even three stages.

PETC has a number of lesser liquefaction research efforts that are ongoing. For instance, some PETC researchers are working on a simplified single-stage approach. Others have been working on a 'co-processing' technique in which a heavy, poor-quality petroleum resid is used to slurry the coal. Thus far, the economics of co-processing looks favorable, and a project is currently being proposed in PETC's Clean Coal Program to build a demonstration facility. Because this technology is a 'cousin' to the TSL process that PETC is currently working on, some technology transfer will result.

Even though the co-processing technology appears to have a better cost/benefit ratio at this time, direct liquefaction would be a better strategy in terms of reducing U.S. reliance on foreign oil. Co-processing uses only one-third coal and two-thirds petroleum; therefore, it is a transitional technology.

Because the price of oil is about \$17/barrel, no one in the private sector will build a coal liquefaction plant — there is no market incentive, which is the reason that DOE is funding most of the research and development cost.

Through the continuation of PETC's current research program, it has been estimated that by the late-1990s, the cost of a barrel of oil produced by coal liquefaction will approach \$25. By that time, market researchers predict that a barrel of imported crude will cost about the same

Figure 5.
Capital cost
and selling
price by
process

Dollars
(Capital costs in \$000/bbl/day;
selling price in \$/bbl)

amount of money. Therefore, commercial liquefaction may be a reality before the turn of the century.

To turn this expectation into a reality, cost-saving breakthroughs will be pursued in the following areas of near-term PETC research:

- **Deep Cleaning of Coal:** The quantity of resid rejected with the ash is a function of the amount of ash in the coal. Deep cleaning the coal to 5% ash could increase liquid yield by about 5% and will reduce corrosion and erosion of instruments and process components.
- **Testing Alternative Deashing Procedures:** Alternative procedures are being investigated to determine if energy rejection can be reduced below its current level of 8 to 16%.
- **Gas Oil Recycle to Extinction:** For both environmental and refining reasons, a lighter product is

desirable; and the market value of a lighter product is also substantially higher.

Co-Processing of Coal and Petroleum Resid: With co-processing, second stage reaction conditions are not determined by the need to make a good recycle solvent. This gives the process greater flexibility and should reduce liquefaction costs.

Solvent Quality: The ability of a solvent to liquefy coal is directly related to its quality. A better quality solvent, therefore, increases yields and decreases costs.

Catalyst Development: Finely dispersed catalysts with extremely high surface area and oil-soluble catalyst precursors provide the potential for much higher catalyst activity.

Preconversion Processing: Physical, chemical, or biological pretreatments could affect the chemistry of initial dissolution and reduce undesirable reactions, leading to easier liquefaction.

GILBERT V. McGURL JOINED PETC

IN 1981. AND IS NOW IN CHARGE OF THE LIQUID FUELS DIVISION. GIL IS RESPONSIBLE FOR ALL CONTRACT RESEARCH AND DEVELOPMENT WORK AIMED AT PRODUCING CLEAN

LIQUID FUELS FROM COAL. A PHD IN CHEMICAL ENGINEERING FROM THE UNIVERSITY OF MARYLAND, GIL IS A PROCESS DEVELOPMENT ENGINEER WHO HAS SPECIALIZED IN THE AREA OF SYNTHETIC FUELS. BEFORE COMING TO PETC, HE WORKED FOR ABOUT THREE YEARS ON COAL LIQUEFACTION AND GASIFICATION AT THE FOSSIL ENERGY HEADQUARTERS IN WASHINGTON, D.C. PRIOR TO DOE, GIL SPENT APPROXIMATELY EIGHT YEARS AT KOPPERS COMPANY AND TWO YEARS AT THE UNIVERSITY OF SOUTHWESTERN LOUISIANA TEACHING CHEMICAL ENGINEERING.

CLEAN COAL TECHNOLOGY: ENERGY AND THE ENVIRONMENT

Several advanced technologies for acid rain control have been described in the preceding articles in this issue. These technologies, along with others, are the basis for numerous Clean Coal Technology Program demonstration projects that are being put into place. These projects will, if successful, demonstrate that we can use coal as an energy source in an efficient and environmentally acceptable way. We'll be able to settle the debate over whether the United States can produce energy—economically and in sufficient quantity—without damaging the environment.

As Secretary of Energy James D. Watkins said at the press conference announcing the selection of Clean Coal Technology Program Round 3 projects, *"I believe many people see the linkage [the interdependency of energy to other elements of our society] as being energy or the environment—two aspects of our society often viewed as inherently and permanently pitted against each other."*

"It seems that those who support increased energy development are often portrayed as being on a collision course with those who advocate more aggressive environmental actions. That does not have to be the case."

"The projects we are announcing today represent concrete examples that environmental quality can be achieved concurrently with energy security—not instead of it. The technologies to be field tested by these flagship projects offer environmentally superior ways to use U.S. coal. They will demonstrate technologies that are significantly improved from the current means of burning coal. Most importantly, they demonstrate the confidence we have in America's ability to mobilize its technological prowess and apply it to achieving clean air. We can have clean air without diminishing our economy or our standard of living—and these projects, if they are successful, can give us the means to do it."

WHY BURN COAL?

Coal is the most plentiful form of fossil fuel in the United States. It is also the least expensive and is expected to remain so in comparison with oil and gas. Of the electricity generated in the United States, coal accounts for more than half. Coal reserves, at present consumption rates, are expected to last well into the 22nd century (see Figure 1).

THE PROBLEM

The problem, therefore, for the United States is to find environmentally acceptable ways to make the best use of the fossil energy resources it possesses. However, our scientists and engineers are not content with just making coal attractive environmentally. They also want to increase the efficiency with which we burn coal to make it more cost-effective than it already is. Today, coal-burning power plants attain efficiencies, on average, of about 35%. Even a 5% increase in average efficiency would boost a power plant's output very significantly.

Figure 1. U.S. proved reserves of coal compared to oil and gas

ONE SOLUTION — THE CLEAN COAL TECHNOLOGY PROGRAM

In December 1985, Congress enacted legislation appropriating \$400 million for projects in the first round of the Clean Coal Technology Program. The projects were to be at least 50% cost-shared by the private sector. At about the same time, a report was made by Special Envoys on Acid Rain from the United States and Canada that recommended that the United States implement a 5-year, \$5 billion program to demonstrate commercial applications of new technology to control emissions of sulfur dioxide (SO_2) and nitrogen oxides (NO_x).

In 1987, President Reagan initiated a major expansion of the Clean Coal Technology Program that included appropriating \$2.5 billion in funds as the government's share of the program. In his first State-of-the-Union message, President Bush endorsed the full implementation of the Program. The result of these efforts is that the ongoing Clean Coal Technology Program will bring to the commercial market viable alternatives to existing methods of burning coal and reducing SO_2 and NO_x emissions.

ACID RAIN

It is believed that acid rain results when SO_2 and NO_x are released into the atmosphere. As these compounds are transported through the atmosphere, over distances up to hundreds of miles, they are oxidized to sulfates and nitrates and form a dilute solution of sulfuric and nitric acid. Acid rain can be in the form of either wet deposition (rain or snow that carries the acidic compounds to the earth) or dry deposition (acidic gases adsorbed by particles or absorbed by leaves or other surfaces). These acids are thought to be damaging forests and aquatic life in headwater lakes and streams. In addition, they appear to cause some man-made

Figure 2. Pyritic and organic sulfur molecules

materials to deteriorate more quickly than normal. However, the types, causes, locations, and severity of the damage caused by acid rain are still uncertain.

Coal contains sulfur in either pyritic (physically distinct mineral particles) or organic (chemically bound to the coal) form (see Figure 2). When coal is burned, both forms of sulfur are released to the atmosphere as SO_2 . As with sulfur, nitrogen (chemically bound in molecules of the coal) is released to the atmosphere as NO_x when coal is burned.

In order to improve air quality, the Environmental Protection Agency (EPA) formulated New Source Performance Standards (NSPS) to control the amount of SO_2 and NO_x emitted by coal-fired power plants. New Clean Air legislation, proposed by President Bush and being considered by Congress, will call on utilities to make further reductions in these acid rain precursors.

In terms of SO_2 and NO_x emissions, clean coal technologies have the potential to make a coal-fired plant as clean as an oil-fired plant and, in some cases, as clean as a plant that burns natural gas—the cleanest of all fossil fuels.

Some clean coal technologies employ improved methods for coal combustion. Such technologies can improve the conversion efficiency of electricity and can also reduce emissions of acid rain precursors.

Clean coal technologies, if demonstrated to be economical at commercial scales, can result in a cleaner environment and lower power cost—an ideal combination for a nation determined to sustain economic growth and enhance its energy security while improving air quality.

To understand how clean coal technologies work, it helps to look at where they fit along coal's "fuel chain"—the path coal follows from a mine to a power plant or factory.

Clean coal technologies can be installed at any one of three stages (described below and keyed to the numbers shown in Figure 3) in the fuel chain, or in a fourth manner that departs from the traditional method of coal burning, namely, coal conversion:

1. **Precombustion.** Sulfur and other potential pollutants in coal are removed before they reach the boiler.
2. **Combustion.** Pollutants inside the combustor or boiler are removed while the coal burns.
3. **Post-combustion.** Flue gases released from coal boilers are cleaned in the ductwork leading to the smokestack or in advanced versions of today's scrubbers.
4. **Conversion.** Coal is changed into a gas or liquid that can be cleaned and used as a fuel.

THE NEW TECHNOLOGIES

Precombustion. In precombustion technology, the new thrust is in advanced physical cleaning techniques, which involve grinding the coal to much smaller sizes than is done today. New improved processes can then be used to separate most of the pyritic sulfur from the coal. For additional information, refer to the article entitled "Acid Rain Abatement and Advanced Coal Cleaning: A Precombustion Option" on pages 11 to 16 of this issue.

Combustion. Sulfur can also be removed from coal while it burns, which is advantageous because no additional removal equipment is required. This process uses fluidized bed combustors or advanced (slagging) combustors. In a fluidized bed combustor, crushed coal and limestone are mixed and float suspended on jets of air in the boiler. As the coal burns, sulfur is released and absorbed by the limestone, which forms a dry waste product that is captured and

removed from the boiler. The fluidized bed combustor is capable of removing as much as 90% of the sulfur in this way.

In addition, unlike traditional removal techniques, the fluidized bed combustor is capable of reducing nitrogen oxide emissions because the combustion temperature inside the boiler is low enough to reduce the formation of nitrogen oxide pollutants. Two types of fluidized bed combustors are being demonstrated in the Clean Coal Technology Program—an atmospheric fluidized bed combustor, which operates at normal atmospheric pressures, and a pressurized fluidized bed combustor, which operates at pressures between 6 to 16 times higher than normal atmospheric pressure.

Slagging coal combustors are also being investigated; most of them are based on the concept of a cyclone combustor, which burns pulverized coal in a chamber that is separate from and outside of the furnace cavity. This prevents ash from forming inside the furnace or boiler tubes, and this keeps boiler efficiency high. The name "slagging combustor" comes from the fact that the combustion temperature is so high that the mineral impurities in the coal melt and form a slag, which is forced to the outside wall of the combustor, where it is collected and removed. Also, by positioning air injection ports to burn

Figure 3. Stages in the coal fuel chain

the coal in stages, NO_x can be reduced by 50 to 70%; and SO_2 emissions can be reduced by 50 to 90% by injection of limestone in the combustor.

Post-Combustion. Post-combustion cleaning methods usually involve scrubbers that require large vessels, making the process a costly one. In a wet scrubber, a slurry of an

THE CLEAN COAL TECHNOLOGY PROGRAM IS PROVIDING SOLUTIONS TO CONVENTIONAL TECHNOLOGY PROBLEMS.

alkaline reagent (e.g., limestone) is sprayed into the flue gases from the burned coal. The reagent mixes with the flue gas to form calcium sulfite and calcium sulfate in the form of a wet sludge. Unfortunately, although these scrubbers can reduce SO_2 to below the NSPS limits, the waste product poses a

disposal problem. In addition, wet scrubbers require a large amount of water (between 500 to 2500 gallons per minute for a 500-megawatt electric plant); so, older scrubbers typically use 3 to 5% of the electric power produced by the plant. Newer scrubbers need to use only 1 to 2% parasitic power.

Another type of scrubber is a dry scrubber, which uses a finely atomized reagent slurry that evaporates in the hot gas from the flue. The dry residue contains the SO_2 from the flue gas. Although the dry residue is easier to dispose of and the dry scrubber doesn't require as much water to operate, it has not been demonstrated to be cost-effective for removing sulfur from high-sulfur coal.

The problems with conventional scrubber technology have been the cost, the waste product produced, and the inability to reduce NO_x emissions. The technologies being investigated in the Clean Coal Technology Program provide solutions to these problems. In fact, the products from the advanced technologies may even have commercial value. These advanced technologies range from completely new approaches for emissions control to advanced wet limestone scrubbers that are capable of significantly improved

performance over current technology.

One advanced technique is called in-duct sorbent injection, which sprays sorbent (e.g., lime) into the ductwork that leads from the boiler to the smokestack. This eliminates the need for the costly scrubber vessels. The lime can remove from 50 to 70% of the SO_2 and produces a dry powder that is collected and removed. SO_2 control and duct injection are discussed on pages 6 to 10 of this issue.

In other advanced flue gas cleaning technologies, new advantages include (1) regenerating the sulfur-absorbing chemical, which makes the system more cost-effective; (2) removing both SO_2 and NO_x ; and (3) producing an environmentally acceptable or salable dry waste product.

Conversion. There are new technologies being investigated that are different from conventional coal-firing techniques—they convert coal into another fuel form (usually solid, liquid, or gas) before combustion. These technologies include such processes as gasification combined cycle, underground gasification, coal liquefaction and coal-oil co-processing (see "Two-Stage Liquefaction of Coal" on pages 17 to 25 of this issue).

ADMINISTERING THE PROGRAM

The Clean Coal Technology Program is mandated by Public Law and is administered by the U.S. Department of Energy, Office of Fossil Energy. All of the projects selected in each round (there are plans to conduct a total of five rounds) of the program are technically overseen by either the Morgantown Energy Technology Center (METC) or PETC, depending on the technology under development. METC and PETC negotiate and award the cooperative agreements and provide oversight and technical expertise to the program participants during the conduct of the demonstration project. The third round of projects has been selected, and Congress has appropriated funds for rounds 4 and 5 (see Figure 4).

An important concept in many of the Clean Coal Technology projects is that of "retrofit technologies." Retrofit technologies generally are pollution control devices that can be installed on older power plants without making major changes in the plant design. Some retrofit concepts do not reduce sulfur emissions by the 90% required by the NSPS for new plants (unless possibly used in combination with each other) but offer a means of reducing sulfur emissions by 50 to 70% (called for in most new legislation to reduce acid rain) at far less cost than a conventional scrubber. Retrofit technologies include:

- Precombustion coal cleaning
- Limestone injection multistage burners (LIMB)
- In-duct sorbent injection
- Gas reburning
- Advanced slagging combustors
- Advanced scrubbers

One of the PETC-managed projects, Babcock and Wilcox's LIMB Demonstration Project Extension, was selected in Round 1 of the Clean Coal Technology Program and is already producing valuable results. This project involves testing two different concepts: (1) controlling SO₂ emissions by sorbent injection in the furnace and (2) using post-combustion control, specifically sorbent injection in the ductwork. Either of these technologies can reduce SO₂ emissions by at least 50%. Both employ injection of hydrated lime as the sorbent to capture SO₂ and then collect the used sorbent in an existing electrostatic precipitator on the power plant. When the project's tests are finished, the utility will have important information for deciding whether furnace injection or duct injection meets its specific requirements.

The first of these technologies being tested at the Edgewater Plant of Ohio Edison is the Coolside Process, which was developed by Consolidation Coal Company. In this process, hydrated lime is injected into the flue gas duct after the preheater (see Figure 1, page 9). A mixture of water and sodium sorbents is then injected into the flue gas, both to

	1986	1987	1988	1989	1990	1991	1992
Round #1	\$100		\$150				
Round #2			\$50	\$200	\$135	\$200	
Round #3					\$450	\$125	
Round #4						\$600	
Round #5							\$600

Figure 4. Clean Coal Technology appropriations (millions of \$)

humidify the gas stream and to promote the reactivity of the hydrated lime sorbent. The preliminary results from these tests are very encouraging.

The next phase of testing in this project will build on a previous EPA effort and will evaluate a number of sorbents for use in furnace injection. The Edgewater plant will also be operated on several different coals to determine what effect that will have on the efficiency of LIMB.

THE REST OF THE STORY

At this time, the rest of the story about the results from the Clean Coal Technology Program has yet to be written. However, preliminary results are coming in from some other Round 1 projects, and we will keep you informed in this publication as those results become available.

CLEAN COAL TECHNOLOGY PROJECTS MANAGED BY PETC

CCT-I			
PROPOSER	PROJECT	SITE	STATUS*
Babcock & Wilcox Company; Alliance, OH	Extended Tests of Limestone Injection Multistage Burner (LIMB) Plus Coolside Sorbent Duct Injection	Lorain, OH	Phase III
Coal Tech Corporation; Morion, PA	Advanced Cyclone Combustor with Integral Sulfur, Nitrogen, and Ash Control	Williamsport, PA	Phase III
Energy and Environmental Research Corp.; Irvine, CA	Enhancing the Use of Coal By Gas Reburning and Sorbent Injection	Springfield, IL, and Hennepin, IL	Phase II
Ohio Clean Fuels, Inc.; Warren, OH	Prototype Commercial Coal/Oil Co-Processing Plant	Warren, OH	Phase I
TRW, Inc.; Cleveland, OH	Advanced Slagging Combustion Utility Demonstration	Stony Point, NY, and Cleveland, OH	Phase I
Combustion Engineering, Inc.; Windsor, CT	Clean Coal Demonstration for the U.S. Electric Power Industry	Homer City, PA	Under Negotiation
Western Energy Company; Colstrip, MN	Advanced Coal Cleaning and Processing Facility	Colstrip, MN	Under Negotiation
CCT-II			
PROPOSER	PROJECT	SITE	STATUS
Southern Company Services, Inc.; Birmingham, AL	Demonstration of the Chiyoda Thoroughbred-121 Desulfurization Process	Plant Yates Newnan (near Atlanta), GA	Phase I
Southern Company Services, Inc.; Birmingham, AL	Advanced Wall-Fired Combustion Techniques for Reduction of Nitrogen Oxides	Plant Hammond Coosa (near Rome), GA	Phase I
Southern Company Services, Inc.; Birmingham, AL	Selective Catalytic Reduction Technology for Control of Nitrogen Oxides	Plant Crist Pensacola, Escambia County, FL	Under Negotiation
Southern Company Services, Inc.; Birmingham, AL	Advanced Tangentially Fired Combustion Techniques for Reduction of Nitrogen Oxide	Plant Smith Lynn Haven (near Panama City), FL	Under Negotiation

CCT-II (CONTINUED)

PROPOSER	PROJECT	SITE	STATUS
Combustion Engineering, Inc. & Snamprogetti USA, Inc.; Windsor, CT	WSA-SNOX Technology for Catalytically Reducing Sulfur Dioxide and Nitrogen Oxides from Flue Gas	Niles, OH	Phase I
The Babcock & Wilcox Company; Alliance, OH	Demonstration of SOX-NOX-ROX Box Post-Combustion Flue Gas Cleanup Process	Dillas Bottom, OH	Phase I
Passamaquoddy Tribe; Thomaston, ME	Innovative Sulfur Dioxide Scrubbing System for Coal-Burning Cement Kilns	Thomaston, ME	Phase II
Bethlehem Steel Corporation; Bethlehem, PA	Innovative Coke Oven Gas Cleaning	Baltimore County, MD	Phase II
The Babcock & Wilcox Company; Alliance, OH	Coal Reburning for Cyclone Boiler Nitrogen Oxide Control	Cassville, WI	Phase I
Pure Air; Allentown, PA	Advanced On-Site Flue Gas Desulfurization Process	Gary, IN	Phase I
TransAlta Resources Investment Corp.; Calgary, Alberta, Canada	Low Nitrogen Oxide/Sulfur Dioxide Burner Retrofit for Utility Cyclone Boilers	Marion, IL	Under Negotiation
Otisca Industries, Ltd.; Syracuse, NY	Production of Compliance OTISCA Fuel (Coal Water Slurry) and Combustion in Retrofitted Industrial Boilers	Syracuse, NY Jamesville, NY Oneida, NY	Under Negotiation

CCT-III

PROPOSER	PROJECT	SITE	STATUS
AirPol Inc.; Teterboro, NJ	Demonstration of Gas Suspension Absorption for Flue Gas Desulfurization	Paducah, KY	Under Negotiation
The Babcock & Wilcox Company; Alliance, OH	Full-Scale Demonstration of Low-NOx Cell Burner Retrofit	Aberdeen, OH	Under Negotiation
Bechtel Corp.; San Francisco, CA	Confined Zone Dispersion — Flue Gas Desulfurization Demonstration	Indiana County (near Seward), PA	Under Negotiation
Energy and Environmental Research Corp.; Irvine, CA	Evaluation of Gas Reburning and Low-NOx Burners on a Wall-Fired Boiler	Denver, CO	Under Negotiation
LIFAC N. America; Oakland, CA	Demonstration of LIFAC Flue Gas Desulfurization Technology	Richmond, IN	Under Negotiation
MK-Ferguson Co.; Cleveland, OH	Commercial Demonstration of the NOXSO SO2/NOx Removal Flue Gas Cleanup System	Niles, OH	Under Negotiation
Public Service Co. of Colorado; Denver, CO	Integrated Dry Sorbent Injection and NOx Control System	Denver, CO	Under Negotiation
Alaska Industrial Development & Export Authority; Anchorage, AK	Healy Co-Generation Project	Healy, AK	Under Negotiation
Air Products & Chemicals; Allentown, PA and Dakota Gasification Co.; Bismarck, ND	Commercial Scale Demonstration of the Liquid Phase Methanol Process	Bismarck, ND	Under Negotiation

- * Phase I: Design and Permitting
- Phase II: Construction and Start-up
- Phase III: Operation and Dismantlement

FOCUS ON

ALBERT W. DEURBROUCK

The previous director of PETC's Coal Preparation Division has been named the 1990 recipient of the Percy W. Nicholls Award. This is an Engineering Society Joint Award given annually, on an alternating basis, by the (1) Coal Division of the Society of Mining, Metallurgical, and Petroleum Engineers or (2) the Fuels Division of the American Society of Mechanical Engineers. The award will be presented to Mr. Deurbrouck at the AIME Annual Meeting in February 1990 in Salt Lake City, Utah.

This award was established and first given in 1942 "for notable scientific or industrial achievement in the field of solid fuels." Mr. Deurbrouck's "work in establishing the washing characteristics of the major commercial coal seams in the United States and his work as an international representative of the coal industry" were cited as significant factors in his selection. Past winners of this award include Richard C. Corey, former Director of the Bruceton Coal Research Center, and Dr. Homer H. Lowry, former Deputy Director of the Bruceton Research Center.

Mr. Deurbrouck is a mining engineering graduate from the University of Idaho whose principal areas of coal preparation research have included coal characterization, equipment performance evaluations, process development, dewatering, and fine-coal reconstitution. He is the author or co-author of more than 100 technical papers, and he holds three patents on coal preparation related technologies. Since 1977, Mr. Deurbrouck has been the U.S. representative on the Organizing Committee of the International Coal Preparation Congress. He is the western hemisphere editor of COAL PREPARATION: A Multinational Journal and is a contributing editor for The Journal of Coal Quality. He recently retired from PETC on December 29, 1989, after many years of service with DOE.

BRADLEY C. BOCKRATH

For the past 15 years, Dr. Bradley C. Bockrath has probed the complex reactions of coal liquefaction, applying the basic methods of physical organic chemistry to understanding the chemical mechanism of liquefaction at the molecular level. For his efforts, the American Chemical Society (ACS) has selected Dr. Bockrath for the distinguished Henry H. Storch Award in Fuel Chemistry for 1990. The national award is administered by the ACS and sponsored by the Exxon Research and Engineering Company.

Dr. Storch, the namesake of the award, is significant to PETC's history. Shortly after World War II when the present Center was constructed, he served as the Chief of the Research and Development Branch in the Office of Synthetic Liquid Fuels at the U.S. Bureau of Mines. Over the years, the Storch award has been awarded to a long list of scientists at the Center, including Irving Wender, Sol Weller, Robert A. Friedel, Heinz Sternberg, and Herbert L. Retcofsky.

The award, which has been granted annually since 1964, recognizes distinguished contributions to fundamental or engineering research on the chemistry and utilization of coal. Dr. Bockrath's focus has been on the mechanisms of coal liquefaction, particularly free radical chemistry, hydrogen transfer reactions, and the chemistry of liquefaction catalysts. Recently, Dr. Bockrath has concentrated on the chemistry of dispersed-phase catalysts in the first stage of liquefaction.

Before he began his work as a scientist at PETC in 1974, Dr. Bockrath, who is a group leader in the center's Direct Coal Conversion Division, spent three and one-half years at Ohio State University researching pulse-radiolysis. He has a B.S. in Chemistry from Union College and a Ph.D. in physical organic chemistry from the State University of New York at Albany.

In response to his recognition, Dr. Bockrath said: "PETC has always provided an atmosphere that fosters strong research in coal chemistry, and I expect that the award will return to the Center in the future."

Dr. Bockrath will receive the award at the national ACS meeting in April 1990.

CALENDAR OF UPCOMING EVENTS

- **MARCH 15-16**
UNIVERSITY COAL RESEARCH/HISTORICALLY BLACK COLLEGES AND UNIVERSITIES PEER REVIEW MEETING
 REVIEW, EVALUATE, AND RANK UCR/HBCU PROPOSALS.

- **APRIL 23-26**
14TH INTERNATIONAL CONFERENCE ON COAL AND SLURRY TECHNOLOGY (CONDUCTED BY THE COAL & SLURRY TECHNOLOGY ASSOCIATION IN COOPERATION WITH PETC)
 ADVANCE STATE-OF-THE-ART COAL AND SLURRY TECHNOLOGY BY PRESENTING DEVELOPMENTS IN THE PREPARATION, TRANSPORTATION, BENEFICIATION, AND COMBUSTION OF COAL AND SLURRY FUELS.

- **MAY 1-3**
FIRST INTERNATIONAL SYMPOSIUM ON THE BIOLOGICAL PROCESSING OF COAL (SPONSORED JOINTLY WITH THE ELECTRIC POWER RESEARCH INSTITUTE)
 FOSTER INCREASED ACTIVITY, IDENTIFY NEW BIOTECHNOLOGIES, AND PROMOTE TECHNOLOGY DEVELOPMENT AND IMPLEMENTATION IN THE BIOLOGICAL PROCESSING OF COAL.

- **JULY 16-19**
UNIVERSITY COAL RESEARCH/HISTORICALLY BLACK COLLEGES AND UNIVERSITIES CONTRACTORS' REVIEW MEETING
 REVIEW THE PROGRESS OF GRANTS UNDER THE UCR/HBCU PROGRAMS.

- **AUGUST 6-9**
SIXTH ANNUAL COAL PREPARATION, UTILIZATION, AND ENVIRONMENTAL CONTROL CONTRACTORS' CONFERENCE.
 REVIEW THE RESEARCH AND PROGRESS UNDER THESE PROGRAMS.

- **AUGUST 27-30**
USA/KOREA JOINT WORKSHOP ON COAL UTILIZATION TECHNOLOGY
 ENHANCE KOREA'S ACCESS TO A BROADER SPECTRUM OF U.S. COAL UTILIZATION TECHNOLOGIES AND ENCOURAGE INCREASED COAL IMPORTS FROM THE UNITED STATES.

- **SEPTEMBER 16-19**
AR&TD CONTRACTOR'S REVIEW MEETING (SPONSORED JOINTLY WITH METC)
 REVIEW THE RESEARCH AND PROGRESS UNDER THESE PROGRAMS.

- **SEPTEMBER 24-27**
DIRECT LIQUEFACTION CONTRACTORS' REVIEW MEETING
 REVIEW THE PROGRESS OF THE PROJECTS IN DIRECT COAL LIQUEFACTION.

FOR ADDITIONAL INFORMATION ABOUT ANY OF THESE MEETINGS, PLEASE CONTACT KAY DOWNEY, PETC, P.O. Box 10940, PITTSBURGH, PA 15236. PHONE: 412-892-6029, FTS: 723-6029

RD&D AWARDS

CONTRACT AWARD DATE	AWARDEE	PROGRAM/DESCRIPTION
CLEAN COAL		
11/14/89	Bathlehem Steel	Innovative coke oven gas cleaning system
BARTLESVILLE PROJECT OFFICE		
7/18/89	Improved Gravity Drainage Co.	Development of a novel subsurface oil production technology
8/01/89	Rougeot Oil & Gas Corp.	Enhanced oil recovery horizontal drilling project
9/05/89	University of Colorado	Chemically assisted in-situ recovery of oil shale
9/12/89	Interstate Oil Compact	Evaluation of the domestic oil resource and the economic recovery of mobile and immobile light oil
9/21/89	Penn State University	An experimental and theoretical study to relate uncommon rock fluid properties to oil recovery
9/21/89	University of Texas	Characterization of facies and permeability patterns in carbonate reservoirs based on outcrop analogs
9/22/89	University of California	Geophysical and transport properties of reservoir rocks
9/25/89	Colorado School of Mines	Lab modeling and field development of borehole seismic imaging techniques using seismic wave field measurements
9/26/89	Petrolphysics, Inc.	Innovative drilling completion system
9/26/89	University of Michigan	Characterization and modification of fluid conductivity in heterogeneous reservoirs to improve sweep efficiencies
9/27/89	Kawasaki Hormel Systems	Measuring wellbore heat losses in active steam injection well
9/27/89	Southwest Research Inst.	Demonstration of a high-resolution inverse vsp for reservoir characterization application
9/29/89	University of Alaska	Analysis of reservoir heterogeneities due to shallowing upward cycles in carbonate rocks
9/29/89	Johns Hopkins University	Statistically designed study of the variables and parameters of a CO ₂ equation of state
LIQUID FUELS		
8/09/89	Kentucky Research Foundation	Cooperative research in coal liquefaction
9/01/89	NASA Jet Propulsion Lab	Effects of surfactant in coal liquefaction
9/05/89	Advanced Fuel Research	Fundamental studies of water pretreatment of coal
9/08/89	Consolidation Coal Co.	Coal liquefaction process streams characterization and evaluation

CONTRACT AWARD DATE	AWARDEE	PROGRAM/DESCRIPTION
9/18/89	Viking Systems International	Design of slurry reactor for indirect liquefaction application
9/21/89	SRI International	Hydrothermal pretreatment of coal
9/21/89	University of Southern Cal.	High-temperature ceramic membrane reactors for coal liquid upgrading
9/22/89	Geo-Microbial Technology	Microbiological metal recovery from spent coal liquefaction catalysts
9/22/89	University of Arkansas	Biological production of ethanol from coal
9/27/89	Texas A&M Research	Development of improved Iron Fischer-Tropsch catalyst
9/27/89	Amoco Oil Co.	Direct conversion of light hydrocarbon gases to liquid fuels
9/27/89	Bechtel National, Inc.	Slurry reactor design studies
9/28/89	UOP, Inc.	Development of a stable cobalt ruthenium Fischer-Tropsch catalyst
COAL UTILIZATION		
7/21/89	University of Utah	Surface electrochemical control for fine coal and pyrite separation
8/15/89	Penn State University	Superclean coal-water slurry combustion testing in an oil-fired industrial boiler
9/22/89	United Technologies Corp.	Investigation of the rank dependence of tar evolution
9/27/89	Tecogen, Inc.	Storage, transportation, and atomization of CWF for residential applications
9/29/89	Westinghouse Electric	R&D for storage, transport, and handling of coal-based fuels
8/29/89	Lehigh University	Coal surface structure and thermodynamics
ADVANCED POWER 1 FUNDAMENTAL RESEARCH		
7/11/89	Louisville Research Found.	Mechanism of hydrodenitrogenation
7/31/89	Purdue Research Found.	Preconversion catalytic deoxygenation of phenolic functional groups
7/31/89	Yale University	Novel techniques for coal analysis and hydrogenation product analysis
8/01/89	Illinois Inst. of Tech.	Predictive models for circulating fluidized bed combustors

8/07/89	California Inst. of Tech.	Membranes of H ₂ separation in coal gas processing
8/07/89	Florida State University	Pulsed electron beam precharge
8/07/89	Texas A&M Research Found.	Novel reactor configuration for syngas conversion to alcohols
8/07/89	University of California	Pelletization of fine coals
8/07/89	University of Cincinnati	A novel coal feeder for production of low-sulfur fuel
8/11/89	University of Alabama	Permeability changes in coal resulting from gas desorption
8/15/89	Michigan State University	Enhanced coal hydrogasification via oxidative pretreatment
8/15/89	Texas Southern University	Transport of heavy metals in process wastewaters
8/18/89	North Carolina A&T	Thermodynamic model for calorimetric and phase co-existence properties of coal-derived fluids
8/18/89	University of Pittsburgh	A novel process for methanol synthesis
8/18/89	West Virginia University	Mineral transformations and fragmentation in coal combustion
8/21/89	University of Minnesota	Molten iron oxysulfide as a superior sulfur sorbent
8/24/89	Northeastern University combustion of coal water slurries	Effects of calcium magnesium acetate on the
8/24/89	University of Oklahoma	Selenium transformation in coal mine spoils
8/24/89	University of Minnesota temperature sulfur removal	Comparison of lime and iron oxide for high-
8/21/89	Grambling State University	NQR-NMR studies of higher alcohol synthesis Cu-Co catalysts
8/21/89	University of Washington	Chemistry of coal-related microparticles
8/21/89	University of Utah	Novel process for depolymerization of coal to C ₂ -C ₄ hydrocarbons
8/21/89	Virginia Polytechnic Inst.	Control of pyrite surface chemistry in physical coal cleaning
8/22/89	Lehigh University	Single electron chemistry of coals
8/23/89	Lehigh University	Binding and catalytic reductions of NO by transition metal aluminosilicates
8/23/89	Oregon State University synthetic liquids	Fundamental studies of catalytic processing of
8/24/89	Duke University	Basic properties of coals and other solids
8/29/89	Atlanta University	A novel approach to highly dispersed catalytic materials in coal for gasification

CONTRACT AWARD DATE	AWARDEE	PROGRAM/DESCRIPTION
8/29/89	Massachusetts Inst. Tech.	Coal plasticity at high heating rates and temperatures
8/29/89	Massachusetts Inst. Tech.	Effect of CO/CO ₂ on temperature and burning time for char combustion
8/30/89	Massachusetts Inst. Tech.	Control of catalytic hydrotreating selectivity with ammonia
9/21/89	Penn State University	Catalyst dispersion and activity under conditions of temperature-staged liquefaction
9/22/89	Boston University	Applications of micellar enzymology to clean coal technology
ENVIRONMENTAL CONTROL		
7/14/89	Battelle Memorial Inst.	Enhanced coal biodesulfurization through the genetic modification of bacterial strains
9/19/89	Cottrell Environmental	Evaluation of a pre-charging pulse jet filter for small combustor particulate control
9/20/89	Tecogen, Inc.	Integrated emissions control system for residential coal-water slurry furnace
9/20/89	UCC Research Corp.	Proof of concept and performance optimization of high-gravity, batch-type centrifuge for dewatering fine coal
9/22/89	Arthur D. Little, Inc.	Emissions control for small-scale combustors
9/22/89	Aspen Technology	Engineering design and analysis of advanced physical fine coal cleaning technologies
9/25/89	AVCO Everett Research	Confined vortex scrubber
9/28/89	Virginia Polytechnic Inst.	In-plant testing of the microbubble column flotation process
COAL PREPARATION/ SOLIDS TRANSPORT		
7/14/89	Battelle Memorial Inst.	Enhanced coal biodesulfurization through the genetic modification of bacterial strains
9/20/89	UCC Research Corp.	Proof of concept and performance optimization of high-gravity, batch-type centrifuge for dewatering fine coal
9/22/89	Aspen Technology	Engineering design and analysis of advanced physical fine coal cleaning technologies
9/28/89	Virginia Polytechnic Inst.	In-plant testing of the microbubble column flotation process

0001734VN-1330310-116

Smouse, S.M., McIlvried, T.S., and Avon, B.M., Fourteenth Int'l Conf. on Coal & Slurry Technology, April 24-27, 1989, Clearwater, FL.

Wildman, D.J., Ekmann, J.M., and Doohar, J., Fourteenth Int'l Conf. on Coal & Slurry Technology, April 24-27, 1989, Clearwater, FL.

Massoudi, M., Mathur, M., and Lee, K., Spring Technical Meeting, Central States Section, The Combustion Institute, April 30-May 2, 1989, Dearborn, MI.

ELECTRICAL FIELD EFFECTS IN COAL COMBUSTION,
Tumati, P., Brown, T.D., and Ekman, J.M., Twelfth Annual Energy-
Sources Technology Conf. and Exhibition, Jan. 22-25, 1989,
Houston, TX.

Hucko, R.E., and Smouse, S.M., Sixth Annual Int'l Pittsburgh Coal Conf., Sept. 25-29, 1989, Pittsburgh, PA.

Massoudi, M., and Ramezan, M., *Int'l Jour. Non-Linear Mechanics*, 24(3), 221-227, (1989).

NOVEL CATALYSTS FOR THE ACTIVATION OF METHANE,
Taylor, C.E., and Noceti, R.P., 11th North American Mtg. Catalysis
Soc., May 7-11, 1989, Dearborn, MI.

NOVEL CATALYSTS FOR THE CONVERSION OF METHANE,
Taylor, C.E., Noceti, R.P., and Snyder, T.W., Proc. 1989 Int'l Chem.
Congress of Pacific Basin Societies, Dec. 17-22, 1989, Honolulu,
Hawaii.

Baltrus, J.P., Diehl, J.R., McDonald, M.A., and Zaroachak, M.F., *Appl. Catalysis*, **48**, 199-213, (1989).

Mazumdar, M., and Irdi, G.A., *Fuel*, 68, 890-894, (July 1989)

Anderson, R.R., Gormley, R.J., and Rao, V.U.S., *Inst. Coal Chemistry, Academia Sinica, Taiyuan*, **16**(3), 284-288, (1988), Peoples Republic of China.

A PRELIMINARY INVESTIGATION OF FINE-COAL CLEANING VIA THE MICRO-MAG PROCESS,
Klima, M.S., Maronde, C.P., and Killmeyer, R.P., Coal Prep '89, May 2-4, 1989, Lexington, KY.

AN ELECTROCHEMICAL STUDY OF ADSORPTION OF SODIUM ETHYLXANTHATE ON COAL PYRITE AND MINERAL PYRITE,
Lai, R.W., Richardson, A.G., and Khan, S.U.M., Third Int. Conf. on Fundamentals of Adsorption (West Germany), May, 1989.

COMPARATIVE STUDY OF THE SURFACE PROPERTIES AND THE REACTIVITY OF COAL PYRITE AND MINERAL PYRITE,
Lai, R.W., Diehl, J.R., Hammack, R.W., and Khan, S.U.M., SME preprint No. 89-6, 118th AIME Meeting, Feb. 27-March 2, 1989, Las Vegas, NV.

SIZE REDUCTION AND SELECTIVE AGGLOMERATION OF COAL: TECHNICAL FEASIBILITY OF CLEANING PITTSBURGH SEAM COAL WITH ISOCTANE,
Lai, R.W., Gray, M.L., Richardson, A.G., and Chiang, S.H., Adv. in Coal and Mineral Processing Using Flotation, SME-AIME, 1989.

EFFECT OF HUMIC SUBSTANCES ON THE FLOTATION RESPONSE OF COAL,
Lai, R.W., and Wen, Wu-Wey, Coal Prep., 7, 69-83, (1989).

CATALYTIC DESULFURIZATION OF ORGANOSULFUR COMPOUNDS UNDER MCL CONDITIONS,
Nowak, M.W., and Fauth, D.J., Fifth Annual Coal Preparation, Utilization and Environmental Control Contractors' Conf., July 31-Aug. 3, 1989, USDOE, Pittsburgh, PA.

GAS SURFACE CHEMISTRY OF FLUE GAS SORBENTS,
Finseth, D., Hlivko, B., and Freeman, M., Proc. 1989 Int'l Conf. on Coal Science, Vol. II, pp. 1099-1102, Tokyo, Japan.

OVERVIEW OF DOE'S IN-HOUSE RESEARCH IN ADVANCED PHYSICAL COAL CLEANING,
Killmeyer, R.P., Sixth Annual Int'l Pittsburgh Coal Conf., Sept. 25-29, 1989, Pittsburgh, PA.

EVALUATION OF REVERSE COAL-PYRITE FLOTATION FOR A PROPOSED OHIO ADVANCED COAL-CLEANING TEST FACILITY,
Miller, K.J., USDOE/Pittsburgh Energy Technology Center, DOE/PETC/TR-89/8 (DE890164050), 14 pp., July 1989.

LIFE CYCLE TEST OF THE NOXSO PROCESS: SIMULTANEOUS REMOVAL OF NO_x AND SO₂ FROM FLUE GAS,
Haslbeck, J.L., Yeh, J.T., Ma, W.T., Solar, J.P., and Pennline, H.W., 82nd AWMA Annual Mtg., June 25-30, 1989, Anaheim, CA.

PERFORMANCE OF SODA ASH-LIME SORBENTS IN A SMALL-SCALE SPRAY DRYER,
Markussen, J.M., and Pennline, H.W., 82nd AWMA Annual Meeting, June 25-30, 1989, Anaheim, CA.

EVALUATION OF SODA ASH-LIME SORBENTS IN A SPRAY DRYER SYSTEM FOR SO₂/NO_x CONTROL,
Markussen, J.M., and Pennline, H.W., Paper No. U.S. 31, Proc. Sixth Annual Int'l Pittsburgh Coal Conf., Vol. 1, p. 299, Sept. 25-29, 1989, Pittsburgh, PA.

SOLID AND GASEOUS FUELS,
Schultz, H., Wells, A.W., Frommell, E.A., and Hough, M.R., Anal. Chem., 61, 84R-95R, (June 15, 1989).

STRUCTURAL DEFINITION OF SYNTHETIC FUELS--WILSONVILLE I,
Perry, M.B., Schmidt, C.E., and White, C.M., USDOE/Pittsburgh Energy Technology Center, DOE/PETC/TR-89/6 (DE89013627), 67 pp., May 1989.

CHARACTERIZATION OF COAL REACTION PRODUCTS USING PREPARATIVE-SCALE LIQUID CHROMATOGRAPHY AND AUTOMATED THIN-LAYER CHROMATOGRAPHY,
Perry, M.B., Cillo, D.L., and Barrage, T.C., Preprint, Am. Chem. Soc. Div. Pet. Chem., 1989, 34(2), 229-235.

SYMPOSIUM ON PYROLYSIS PRODUCTS DERIVED FROM COAL, OIL SHALE, TAR SANDS, BIOMASS, AND HEAVY OIL,
Perry, M.B., Pukanic, G.W., and Ruether, J.A., Preprint, Am. Chem. Soc. Div. Fuel Chem., 34(4), 1206-1217, (1989).

SIMPLIFIED WET SCRUBBING PROCESS FOR SO₂, NO_x, AND PARTICULATE REMOVAL FROM FLUE GAS,
Walker, R.J., and Perry, M.B., Paper No. 47e, 1989 Spring Nat'l Mtg. Amer. Inst. Chem. Eng., April 2-6, 1989, Houston, TX.

COAL/OIL COPROCESSING MECHANISM STUDIES,
Cugini, A.V., and Lett, R.G., Energy & Fuels, Vol. 3(2), 120-126, (1989).

INVESTIGATION OF LIQUEFACTION REACTIONS USING MOLECULAR PROBES,
Bockrath, B.C., Schroeder, K.T., and Smith, M.R., Proc. 1989 International Conference on Coal Science, Oct. 23-27, 1989, Tokyo, Japan.

FRACTIONATION OF HEAVY COAL LIQUEFACTION PRODUCTS BY SUPERCRITICAL FLUID DISTILLATION,
Warzinski, R.P., McKeegan, D.P., and Holder, G.D., Adv. in Thermodynamics, Vol. 1, New York: Taylor & Francis, 1989.

DISPERSED-PHASE CATALYST APPROACHES IN COAL LIQUEFACTION AND COPROCESSING,
Lett, R.G., Cugini, A.V., Utz, B.R., Krastman, D., Cillo, D.L., and Jin, G.T., Sixth Joint U.S.-Korea Workshop on Coal Utilization Technology, October 16-18, 1989, Seoul, Korea.

INTERLABORATORY COMPARISON OF ADVANCED FINE-COAL BENEFICIATION PROCESSES,
Jacobsen, P.S., Killmeyer, R.P., and Hucko, R.E., Third Int'l Conf. on Processing and Utilization of High-Sulfur Coals, November 14-17, 1989, Ames, IA.

THE U.S. DEPARTMENT OF ENERGY'S INITIATIVE IN ADVANCED COAL CLEANING FOR ACID RAIN CONTROL,
Feeley, T.J., Walsh, J.D., Gala, H.B., and Sniegocki, J.L., Third Int'l Conf. on Processing and Utilization of High-Sulfur Coals, November 14-17, 1989, Ames, IA.

PROJECT HIGHLIGHTS

MHD PROGRAM

Magnetohydrodynamics (MHD) is the study of the motion of an electrically conducting fluid in the presence of a magnetic field. Experiments conducted by Faraday in the 1830s demonstrated that a conductive wire may be replaced by a conducting fluid within a magnetic field for the generation of electrical power. In 1975, a number of MHD projects were initiated under the Energy Research and Development Administration (ERDA), which led to MHD becoming one of the major national technology programs in the Department of Energy (DOE) following the establishment of the Department in 1977.

Since about 1983, DOE-funded MHD research and development efforts have focused exclusively on coal-fired, MHD-steam, open-cycle electric power generation systems. MHD-steam, open-cycle systems comprise a "topping cycle" from which power is extracted directly by the process of MHD and a steam "bottoming cycle" in which power is produced by a conventional steam turbogenerator.

The present phase of the MHD Program was initiated in 1984 when DOE redirected the Program from one of component development to one of a multi-year effort to achieve integrated proof-of-concept (POC) testing of integrated subsystems. The POC activity will emphasize long-duration tests of prototypical hardware, designed to produce data required to predict or project MHD system reliability, availability, maintainability, and performance in a commercial application.

Prototypical components to be designed and fabricated and tested in an integrated topping cycle subsystem include a combustor, channel, diffuser, and power conditioning circuits. Contractors primarily responsible for this effort are TRW (combustor, systems integration), Avco (channel, diffuser, power conditioning), and Westinghouse Electric (power conditioning). Long-duration testing of the integrated, prototypical topping cycle subsystem will be conducted at a 50 MW(t) scale at the Component Development and Integration Facility (CDIF) in Butte, Montana.

Background research and development on these components has been completed, and the design process for the prototypical components has begun. Preliminary design documents for the combustor, channel, and diffuser have been submitted to DOE. These will be evaluated in detail by a committee consisting of technical personnel from both within and outside of DOE. The document review process was followed by meetings with personnel of TRW and Avco during January 1990 to resolve questions and issues raised by the reviewers. The review process for the power conditioning system being designed by Westinghouse Electric will be conducted later in FY 1990. Following completion of the preliminary design review process, the contractors will complete their design effort, which then will be subjected to a critical design review by DOE.

The scheduled activity for the remaining POC effort in the topping cycle area includes hardware fabrication from October 1990 to March 1992, installation and preliminary testing at the CDIF from April to September 1992, and long-duration testing at the CDIF from October 1992 through September 1993.

PACKED-BED FLOTATION COLUMN TO RECEIVE NOVEL COMMERCIAL APPLICATION

Stationary packed-bed column flotation, developed under PETC's Coal Preparation Program at Michigan Technological University (MTU), will be commercially deployed in a technology transfer application for the separation of fly ash into its carbon and ash constituents. The new flotation technology uses a controlled dispersion reagent scheme and a new type of flotation cell. This cell incorporates stacks of corrugated plates in a column to provide small passages for intimate bubble/particle contact. The stacked corrugated plates obviate the need for a sparger because they break any bubbles into small sizes. Capillary effects between the plates enable an almost unlimited height of froth to be supported. In the fly ash application, fly ash consisting of approximately 35% carbon and 65% ash will be processed by Carbovan, Inc., at McMurray, Alberta, Canada, with subsequent recovery of vanadium and other high-value products from the concentrated ash stream. Combining chemical dispersants

with the MTU packed column has allowed Carbovan to recover a high-grade (greater than 95%) carbon product and, at the same time, achieve high recoveries (greater than 98%) of the valuable metal-laden ash. The process is now being evaluated at the pilot scale, and Carbovan is committed to commercial implementation employing a 9-foot-diameter column to process over 100 metric tons of fly ash per day.

NEW PILOT-SCALE COMBUSTOR CONSTRUCTED AT PETC

Last year, PETC researchers completed the design and construction of a new pilot-scale combustion facility, the Fuels Evaluation Facility (FEF). This new combustor is being used as part of an ongoing multi-level Alternative Fuels Program project to assess the combustion performance of highly processed coal-based fuels.

Basic design criteria for the FEF, which is nominally rated at 500,000 Btu/hour (approximately 40 lb of coal/hour), were selected to achieve similarity with full-scale utility and industrial boilers. Pilot-scale combustors, such as the FEF, are used to assess fuel quality by comparing the combustion performance of a new fuel with that of reference fuels for which full-scale performance is known. The facility will be equipped to assess: small-scale storage, handling, and transport characteristics; fuel combustibility (flame stability and carbon conversion efficiency); ash deposition (slagging and fouling) propensity; fly ash erosion; and gaseous and particulate emissions. The facility is highly instrumented and equipped with a state-of-the-

art PC-based data acquisition and control system.

Approximately 900 hours of natural gas firing and 175 hours of coal firing were logged during shakedown and initial testing of the FEF. The first short-term tests in the new facility were completed while firing a highly beneficiated (2% ash) bituminous coal from the Upper Elkhorn No. 3 seam. Other deeply cleaned coals, which will be produced by advanced physical and chemical processes under development by PETC contractors, have been identified for formal testing this year. The FEF was designed to be highly flexible and will be used in other future applied and fundamental combustion projects. Through Cooperative Research and Development

Agreements (see Around the Center, Research and Development) with PETC, the facility can be made available for collaborative combustion research to private industry. A cooperative agreement is currently being negotiated to test a highly processed western subbituminous coal in the FEF.

GAS-TO-GASOLINE PROCESS

Conversion of light hydrocarbon gases to a product consisting largely of high octane alkylated aromatic hydrocarbons in the gasoline (C4-C10) boiling range is the result of a two-stage process developed at PETC.

In the first stage, methane, oxygen, and hydrogen chloride react over an oxyhydrochlorination (OHC)

New Pilot-Scale Combustor

Gas-to-Gasoline
Conversion Process

catalyst to produce, predominantly, chloromethanes and water. In a second stage, the chloromethanes are catalytically converted to higher hydrocarbons and hydrogen chloride by a shape-selective zeolite catalyst. The hydrogen chloride is recycled to the first stage reaction.

Both stages of the reaction sequence have been examined under a variety of operating conditions to optimize conversion of reactants and yields. The second-stage reaction has been carried out over a zeolite catalyst with feeds of chloromethane and of various mixtures characteristic of first-stage products (chloromethane, dichloromethane, and trichloromethane). The catalyst has shown no significant changes in conversions

or product distribution after multiple cycles of deactivation and oxidative regeneration.

Using open tubular gas chromatography combined with mass spectrometry and Fourier Transform Infrared Spectrometry, a typical product from the second stage has been separated into nearly 250 components, of which over 80 weight percent have been identified. Under the reaction condition studied, major constituents of the product are high-octane alkylated aromatics, the most abundant of which is 1,2,4-tri-methyl-benzene, accounting for 45 weight percent of the sample.

CLUBS AND ASSOCIATIONS ARE INVITED TO SUBMIT ARTICLES FOR CONSIDERATION.

Tecogen Completes Tests of Residential Furnace

Tecogen, Inc., of Waltham, Massachusetts, has completed testing of a coal-water fuel-fired residential warm-air heating system. The tests consisted of both life tests and cycle tests of the 100,000-Btu/hour system. The unique Tecogen-designed Inertial Reactor with Internal Separation (IRIS) combustor uses centrifugal forces to separate and detain larger coal-water fuel droplets in dual precombustion chambers to ensure high carbon burnout without the need for fine fuel atomization.

During life testing, 200 hours of firing were accumulated by 6- to 8-hour daily runs of the system. In this period, the furnace burned 1,758 pounds of coal-water fuel at daily average carbon conversion efficiencies ranging from 98.2 to 99.1%. The combustor operated on an average of 22% excess air and, at this level, yielded gaseous emissions of 0.5 lb/10⁶ Btu for both SO₂ and NO_x. SO₂ emissions were controlled by the use of cleaned coal. Although ash buildup was found in the system following the life testing period, the ash did not affect furnace operation or significantly reduce overall system efficiency.

Cycle tests of the system were also completed, simulating residential service. The cycle tests consisted of successive firing intervals of 20 minutes to 1 hour, interrupted by 10-minute cool-down periods. A total firing time of 54 hours was

accumulated during the cycle tests, accomplishing 74 firing cycles. Each cycle was initiated by a 3-minute firing of fuel oil to heat up the furnace prior to ignition of coal-water fuel. The cycle tests permitted fine-tuning of the system controls and operating procedure. Unlike the long-term life test results, in cyclic operation of the system, little ash built up in the furnace. Tecogen, together with its commercialization partner, Yukon Energy Corporation, is incorporating design improvements suggested by the test results into the design of a prototype residential furnace system. (See figure below)

COAL-WATER FUELS OFFER AN ALTERNATIVE TO OIL AND GAS

Coal-water fuel (CWF) mixtures, which typically contain 60 to 70% pulverized coal, 30 to 40% water, and less than 1% chemical additives,

have the potential for replacing fuel oil in commercial applications. Use of these coal-based fuels could lessen U.S. dependence on imported oil and reduce power generating costs. However, commercial development of CWF has been impeded by technical and economic uncertainties. The key technical question concerns the impact an ash-bearing CWF might have on furnaces originally designed for ash-free or very low-ash fuels. Economic feasibility will depend on the extent of boiler derating and equipment modification required. Resolution of these unanswered technical and economic questions is an essential prerequisite to the commercial development of CWFs as alternatives to fuel oil.

In response to this need, PETC initiated a comprehensive effort in 1982 to develop the necessary performance and cost data for assessing the commercial viability of CWFs, as applied to representative utility and industrial

units. Combustion Engineering, Inc. (C-E), was contracted to conduct a project composed of six tasks that began with coal resource evaluation and culminated in the assessment of the technical and economic consequences of switching representative commercial units from oil to state-of-the-art CWF firing. Extensive bench-, pilot-, and commercial-scale tests were performed by C-E to develop necessary CWF combustion and system operation data for the subsequent boiler performance analysis and retrofit cost estimates. Boiler performance models were then used with these data to establish specific load-limiting factors and to determine consequent equipment modification and retrofit costs. Finally, economic feasibilities, in terms of payback periods, were estimated for several boiler types based on fuel price differentials.

Within the limits of the fuel characteristics and commercial unit design conditions evaluated, the principal conclusions from this project were:

- CWFs prepared from judiciously selected and beneficiated feed coals can be efficiently burned under conditions typical of many oil-designed commercial units without severe slagging and fouling behavior.
- Both pilot-scale (4×10^6 Btu/hour) and commercial-scale (50×10^6 Btu/hour) combustion testing indicated that atomization quality in the combustion environment has a dominant effect on carbon conversion efficiency and fly ash characteristics. Reductions in spray droplet size distribution

Coal-Water Slurry
Residential Furnace

consistently resulted in improved combustion performance when considering a single fuel formulation.

- Preheating CWF prepared from a microfine coal to temperatures in excess of 220° F resulted in significant improvements in combustion and fly ash erosion performance.
- Costs associated with cleaning CWF feed coals to lower ash levels were generally justified by operational savings derived from improved performance characteristics.
- Economic analyses indicated that conversion to CWF firing generally becomes feasible when differential fuel costs are above \$1.00/10⁶ Btu.

Above all, this contract clearly demonstrated the improved system performance that results from using beneficiated feed coals, a topic that is now being addressed in a new contract with C-E initiated last year. This contract is examining the combustion characteristics of coal-based fuels in which the feed coal has had much of the mineral matter and sulfur removed by advanced coal cleaning processes.

COAL-FIRED GLASS MELTING SYSTEM COULD REVOLUTIONIZE THE GLASS INDUSTRY

Early in 1989, Vortec Corporation completed the assembly of its pilot-scale (5 million Btu/hour) coal-fired process heater for glass production. The installation is located at the University of Pittsburgh Applied Research Center (UPARC). Owing to its technology, which is

totally unique to the glass industry, this continuous process has the potential to achieve significantly lower capital and operating costs than the batch technologies employed currently to make glass products.

Vortec has made nine successful runs, beginning with natural gas fuel only, then progressing to co-firing coal and gas and to firing 100% coal. Molten glass has been produced from cullet, which is finely ground glass refuse. In two 4-hour duration runs, coal and gas were co-fired at a combined rate of 3 million Btu/hour, with a glass melting rate of 1100 lb/hour. The coal feed rate was varied from 30 to 90% of the total thermal input in these tests. The glass product was not discolored by coal rates up to 50%; beyond this level, an amber coloration was observed, which could be obviated by running the unit at lower load.

These results indicate that with the present system, high-quality glasses may be produced with 50% coal co-firing, and coal rates approaching 100% may be feasible for amber glass, insulation fiberglass, and mineral wool. Future work will emphasize improvements that have commercial application. Coal-fired pre-combustors will be added to increase the capacity with 100% coal input; and a melt reservoir will be incorporated to ensure a higher quality bubble-free glass product. Focus will also be placed on the production of glass from its raw material components (sand, limestone, and soda ash).

Complementary work is also being performed by Vortec on a Small Business Innovation Research (SBIR) project that will use the coal-fired

glass melting system to recycle fiberglass waste products. The production of insulation fiberglass results in over 100,000 tons per year of glass refuse that, in many states, must be disposed of in hazardous waste landfills. This can often cost a plant over \$1 million per year, which is then passed on to the consumer. The Vortec coal-fired combustion system will destroy the hazardous organic compounds in the fiberglass. The compounds are composed of phenolic glass binders and a tar or other adhesive for attaching the paper. At the same time, the system will produce a glass product suitable for direct recycling or, for rigid quality control, a cullet material that can be recycled to the fiberglass manufacturer's furnace as a cold feedstock.

MICRONIZED-MAGNETITE CYCLONING PERFORMANCE TESTS COMPLETED

PETC's in-house Coal Preparation Division completed a series of 45 closed-loop, 3-inch cyclone tests investigating the broad effects of five basic operating parameters as part of its novel Micro-Mag Process research. To extend the range of cleaning down to 400 mesh, this process uses much finer magnetite than does a conventional dense-medium cyclone process. PETC researchers studied magnetite particle size (20% minus-5-microns to 100% minus-5-microns); inlet pressure (5 psi to 40 psi); medium density (1.25 to 1.50); medium-to-coal ratio (5:1 to 15:1); and feed coal size range (100 x 200, 200 x 400, and 28 x 400 mesh). The resulting preliminary performance data from this series of tests indicate that the use of micronized magnetite in a cyclone allows for sharp separations down to 200 mesh. These

separations are much sharper than those possible in conventional cyclone systems, which are limited to a bottom size of 100 mesh. A complete report on the cyclone performance testing conducted last year will be published in early 1990.

GRAMBLING STATE UNIVERSITY (GSU) RECEIVES AWARDS

Since 1985, GSU has received four grants through the DOE University Coal Research Program to do research on magnetic characterization of Indirect Liquefaction Catalysts and preparation and characterization of Coal Water Slurries. Ten undergraduate Physics and Chemistry majors participated in the projects. Based on their work, they made presentations at six national conferences and co-authored three publications. Two students are currently pursuing Ph.D. programs at SUNY, Albany, and two have completed Master's degree programs at Texas A&M University.

The Department of Energy Fossil Energy research grants helped in not only establishing a strong undergraduate research program at GSU but also in paving the way for

procuring additional research grants from the Office of Naval Research (ONR) and the National Science Foundation (NSF). This year, GSU received a \$1.2 million dollar grant from ONR and a \$600,000 grant from NSF to establish additional undergraduate research projects in Physics, Chemistry, and Mathematics. Seven professors from these three departments have initiated research projects in materials preparation (catalysts, superconductors, and semiconductors) and characterization; 25 top-ranking undergraduate science majors are participating in the projects.

The GSU Science Research Institute will hold monthly seminars in which 25 area high school students participate in seminars where the Undergraduate Research Scholars make presentations on their research activities. The primary objective of these projects is to stimulate the interest of students and sustain their zeal to pursue graduate studies in the physical sciences. The institute also holds a summer program sponsored by ONR for high school students to train and motivate them to pursue careers in the physical sciences.

AROUND THE CENTER

CLEAN COAL TECHNOLOGY PROGRAM

J.P. STRAKEY

The Clean Coal Technology Demonstration projects differ in several important respects from those conducted under DOE's more traditional Fossil Energy R&D programs, which have centered on the long-range, high-risk, high-payoff research that industry is unlikely to undertake independently. Generally, DOE provides most or all of the funding for this type of research. By contrast, Clean Coal Technology projects seek to demonstrate the commercial feasibility of the best and most promising of the array of advanced clean coal concepts that have already reached the proof-of-concept stage. These projects are conducted under jointly funded cooperative agreements—not contracts—between government and industry. The industrial partner in each project contributes at least 50% of the total cost (in most cases, more) and owns all patent rights. The projects are selected from proposals submitted by industry in response to competitive solicitations issued by DOE. Thus, each project involves a technology that the industrial partner believes has very real commercial potential, and the partner has a very strong stake in bringing the technology to the marketplace.

The Clean Coal projects currently under way or under negotiation have

been selected by DOE through three such solicitations. Selections under the first—Clean Coal I—were announced on July 25, 1986; and under the second—Clean Coal II—on September 28, 1988. Clean Coal I covered the entire range of advanced clean coal technologies. Clean Coal II centers on technologies that will reduce acid rain precursors and especially on technologies that can be applied to existing facilities that use high-sulfur coal. A third solicitation—for Clean Coal III—was issued in May 1989, and 48 proposals were received and evaluated. Thirteen projects have been selected under Clean Coal III. Each is considered to be an advanced "showcase" venture that will contribute to the nation's efforts to combat acid rain and improve air quality. Monies have been appropriated for Clean Coal IV and V—\$600 million for each.

PETC has seven active projects under Clean Coal I, 12 under Clean Coal II, and 9 under Clean Coal III. Of the projects currently being managed at PETC, Coal Tech Corporation's Advanced Cyclone Combustor project (under Clean Coal I) will be completed in May 1990. Babcock & Wilcox's Limestone Injection Multistage Burner (LIMB) project began "Coolside" testing in August 1989, employing duct injection of hydrated lime. Extended LIMB testing will be carried out in early 1990. The projects under the Clean Coal program will provide a sound basis for commercializing clean coal technologies in the 1990s.

INTERNATIONAL

J.J. Lacey

PETC's role as the lead laboratory for DOE on a growing number of international agreements

strongly reflects a global cooperation in the coal arena. For example, an agreement signed by the United States and the Republic of Korea in 1982 established a cooperative laboratory relationship between the two countries that focuses on the exchange of coal-related technical information. As that relationship continued, both sides established a joint workshop to provide a forum for the exchange. At the workshop, Korea learns about U.S. coal technologies, while the U.S. coal community explores Korea's growing need for coal, equipment, and technology.

From October 17 to 18, 1989, the two countries discussed a range of topics at the Sixth Korea-U.S.A. Joint Workshop on Coal Utilization Technology in Seoul, Korea. During the coal policy session that kicked off the workshop, Korean official Jung-Gon Kim, Director for International Cooperation of the Ministry of Energy and Resources, stressed that Korea's energy resources are limited. He stated that his country relied on imports for 83% of its energy resources in 1988 and projected an increase to 90% in 2000. The absence of a bituminous coal resource base to fuel the utilities compounds the problem. Following Mr. Kim's statements, Joseph Yancik representing the U.S. Department of Commerce's International Trade Administration, emphasized that

the United States has more than 25% of the world's known coal reserves. For coal importing countries such as Korea, he added, the security of supply can provide the confidence to depend on coal as a primary energy fuel. More than 300 members of the U.S. and Korean coal communities gained information from 33 technical papers presented at the workshop. The papers covered coal combustion; coal mining, beneficiation, and coal-ash utilization; coal conversion; and pollution control.

Shortly after the Korean-U.S. Workshop, the United States and Japan collaborated on the sixth annual AIST-NEDO/DOE PETC Joint Technical Meeting on Coal Liquefaction. The participating parties included the Agency of Industrial Science and Technology of Japan and the New Energy Development Organization. The annual meeting, which was held from October 31 to November 1, 1989, in Tokyo, Japan, focuses on research and development activities that the two countries can share. Areas discussed by the U.S. delegation included liquefaction research and development, new directions in liquefaction research; bench-scale co-processing, bench-scale two-stage liquefaction, the advanced liquefaction program, and liquefaction and co-processing research at PETC. In turn, Japanese representatives presented an overview of their Sunshine Project, which attempts to develop energy sources to combat Japan's overdependence on overseas supplies and discussed their technologies for coal liquefaction.

During the Fourth U.S. DOE/Japan-AIST/ANRE Coordinating Meeting held on November 2, the participants signed the fiscal year 1990 implementation plans covering the areas of coal liquefaction, pollution control technology, fuel cells, surface coal

gasification, and materials for coal liquefaction.

PROJECT MANAGEMENT

R.A. Carabetta

The overall PETC R&D budget for this year is a bit higher than that for FY 1989, even after

implementation of the Gramm-Rudman-Hollings sequester—\$137 million vs \$125 million. Among PETC's areas of responsibility, the Flue Gas Cleanup, Coal Preparation, Liquefaction, and Advanced Combustion-Alternative Fuels Programs experienced the greatest funding increases.

Fiscal years 1988 and 1989 were busy ones for the Project Management's Coal Preparation and Environmental Control Divisions. A number of important contracts associated with the Acid Rain Control Initiative Study (see the articles in this issue) SO₂ Control and Duct Injection: A Solution to Acid Rain and the Acid Rain Abatement and Advanced Coal Cleaning: A Precombustion Option were implemented during these 2 years, and a major fraction of these Divisions' attention and funds is being directed to carry out the Study. Nevertheless, a number of procurements are contemplated for the fiscal year.

Several solicitations are being prepared by the Environmental Control Division staff for issuance in FY 1990. Technical areas of interest will include R&D on fine (less than 10 microns) particulate control; the development of chemical schemes that can, in a cost-effective way, convert streams of

concentrated pollutants produced by flue gas cleanup processes to useful by-products; and the development of advanced methods (such as membrane separators and electrochemical cells) for separating undesirable material from coal-derived flue gases. A modest project will also be initiated to gain basic information concerning the nature and quantities of toxic materials, such as heavy metals, present in the various streams of coal-fired power plants.

In the Coal Preparation Division, FY 1990 procurements are planned for R&D related to the deep beneficiation of coal via advance cycloning and the development of advanced physical fine coal cleaning methods. For the Solids Transport Program, a solicitation is planned for advanced research on granular flow.

Several major procurements are planned by the Liquid Fuels Division, our busiest group this year in terms of procurement activity. Currently under evaluation are proposals for the construction of bench-scale generic direct- and indirect-liquefaction units at PETC. Two solicitations for advanced direct coal liquefaction processes are in progress, as is a separate acquisition for advanced coal-oil co-processing development. To help optimize current direct coal liquefaction technology, competitive acquisitions of new R&D efforts for alternative bottoms processing and for preconversion processing are also planned.

A request for proposals to conduct baseline design and systems analyses for indirect coal liquefaction process plants will be issued in FY 1990. Requests for new starts in the indirect liquefaction area will also include work on Fischer-Tropsch catalyst research and the development of advanced processes leading to octane enhancers.

A competitive acquisition will be issued later this year for coal structure/reactivity, novel liquefaction concepts, and fine particles catalysis research as part of the Advanced Research/Coal Liquefaction Program.

In the Coal Utilization Division's Advanced Combustion/Alternative Fuels Programs, a solicitation for proof-of-concept testing of a fire-tube-boiler fueled by superclean coal-water mixtures is in preparation. A procurement document for the integrated testing of advanced industrial-scale combustion systems is being written. A similar solicitation for commercial-scale systems was issued early in FY 1989.

Staff in the Coal Utilization Division have also been busy evaluating state-of-the-art pulverized-coal-fired systems for electric power needs as we move into the next century. Possible new procurement? Stay tuned!

RESEARCH AND DEVELOPMENT

F.R. Brown

Each government-owned, government-operated facility like PETC is chartered to transfer Federal technology associated with

its mission areas to private industry, states, and localities. The Federal Technology Transfer Act of 1986, which is an amendment to the Stevenson-Wydler Technology Innovation Act of 1980, authorizes government-operated facilities to enter into cooperative research and development agreements (CRDAs)

with other Federal agencies, units of state or local government, industrial organizations (including universities), or other persons/entities to facilitate the transfer of technology or negotiate licensing agreements for government-owned inventions.

Unlike Federal procurements, CRDAs are not obtained through a competitive bid process, and the private-sector participants do not receive any financial remuneration for their efforts. Instead, the government provides any or all of the following: personnel, services, facilities, equipment, or other resources, with or without reimbursement. Private-sector participants may provide funds as well as any of the above-listed resources. The objective is to conduct specified research or development efforts consistent with the missions of the government-owned facility.

PETC is actively working or in negotiations on the following CRDAs:

- Commonwealth of Pennsylvania—research and development opportunities for anthracite coal
- Energy Brothers Corporation — K-fuel combustion characterization studies
- ASTM—coal grindability standards
- Benmol Corporation—flue gas cleanup sorbent characterization
- AMAX Coal Company—coal reconstitution
- Consolidation Coal Company —evaluation of reconstituted coal fuels

In addition to the 1986 Amendments to the Stevenson-Wydler Act, Congress passed another Amendment in November 1989 titled "National Competitiveness Technology Transfer Act of 1989," which will allow federal laboratories

to hold in confidence, for a period of 5 years, any data developed in cooperation with a private-sector person or business entity.

The new law is an exception to the long-standing policy of full disclosure of data if it was developed at public expense. This change is a move to encourage more realistic working relationships between the private sector and the federal laboratories. The new law does not alter the rules for contracts, grants, or cooperative agreements, which are awarded in the normal course of business under the authority of the Federal Grants and Cooperative Agreements Act.

The latest Stevenson-Wydler amendments extend coverage of the Act to the contractor-operated national laboratories. Government-owned and -operated laboratories have, for a number of years, been able to use the special provisions of the Stevenson-Wydler Act to quickly execute cooperative agreements with private parties concerning joint research. The existing Act allows the laboratory director to grant a patent license to private parties who are willing to negotiate royalty sharing agreements covering federal patents.

Congress has extended the trade secret protection to the data developed under the special CRDA, if the laboratory director agrees that the protection is warranted. This change modifies the Freedom of Information Act in terms of its basic policy and the rules as to disclosure of government records.

To qualify for a CRDA, interested organizations contact PETC's Technology Transfer Officer, Ms. Kay Downey. She will, in turn, contact the appropriate R&D technical staff. If a project is within the scope of PETC's mission, does not require resources excessive to the budget, and has a clearly

documented statement of work, the CRDA paperwork is completed and sent to PETC legal counsel for review. If it passes all necessary reviews, the CRDA is activated, and the technology transfer process begins. ■■■■■

ADMINISTRATION

M.C. Keller

PETC's Office of Administration handles what might be called the "nuts-and-bolts" of daily

operation—personnel, financial management, procurement, contracts, construction, maintenance, and health and safety. The latter component—health and safety—has become increasingly important, particularly as it affects the environment. The Administration Office takes the public's right to a healthy and safe environment very seriously.

Because nationwide DOE sites are involved in a variety of public activities that can be sensitive and potentially dangerous — such as waste disposal — absolute care must be taken to ensure that problems are dealt with in as effective and responsive a manner as possible.

To provide that assurance, Energy Secretary James D. Watkins instituted a 10-point initiative to strengthen the department's environmental, safety, and health protection and waste management activities. That initiative carries down to all DOE sites to assure complete compliance with federal and state environmental, safety, and health requirements.

The starting point of that initiative was a series of environmental surveys to identify concerns at each site. Technical teams sampled and analyzed each site having potential areas of concern (air, soil, water, etc.) After the results were published, follow-up analyses were conducted for each site.

Even when extreme care is taken regarding health and safety issues, problem areas can still arise at a site—and PETC is no exception. The survey, which was completed in August of 1988, revealed five areas of concern at PETC. By taking prompt and effective action, three of those five areas were corrected by the time the follow-up survey was conducted in June of 1989. PETC continues its work to eliminate the other two areas, which include the storage of drums on site and concerns that jointly involve PETC and the U.S. Bureau of Mines. As a result, PETC's cleanup effort was judged to be the best of all the surveyed DOE sites.

PETC's Administrative Office also intends to maintain that standard of compliance with all environmental, health, and safety regulations when the so-called DOE "tiger team," arrives to assess PETC. Assessments by the "tiger team," one of the ten points of the initiative mentioned earlier, will include thorough assessments of environment, safety, and health operations; documentation, agreements, and permits; and planning, resources management, and performance in meeting environment, safety, and health requirements and schedules. DOE plans to conduct assessments at 18 sites by June 30, 1990; and assessments at all of the department's 35 major sites will be completed by June of 1991. Compliance assessments for all other environmentally less demanding facilities will be scheduled for completion by December 1992.

The response to DOE's ten-point initiative is typical of PETC's Administrative Program Office. The office, which considers itself a service organization, exists to serve other PETC organizations and contractors by providing prompt, efficient responses to requests for assistance. ■■■■■

Reader Information Card

Please send me further information on

- SO₂ Control and Duct Injection: A Solution to Acid Rain
- Acid Rain Abatement and Advanced Coal Cleaning:
A Precombustion Option
- Two-Stage Liquefaction of Coal
- Clean Coal Technology: Energy and the Environment

As reported in Around the Center, send me further information on:

As shown in the Calendar of Upcoming Events, send me information on:

As printed in the RD & D Awards section, send me further information on:

Please send me further information on the following topic that was listed in the Project Highlights section:

As listed in Recent Papers and Publications section, please send me a copy of the following papers/publications:

Would reprints of the articles in this issue be useful to you? ☐ yes ☐ no. If yes, how many? _____

Your comments about the PETC Review will be greatly appreciated.

Please ☐ take my name off ☐ add the following people to your mailing list:

Name:

Address:

Please place this card in an envelope, and return it to:

Dr. Bernard Blaustein, PETC Review

P.O. Box 10940, Pittsburgh, PA 15236-0940

END

DATE
FILMED
6 105/92