AIIM

Association for Information and Image Management

1100 Wayne Avenue, Suite 1100
Silver Spring, Maryland 20910
301/587-8202

Centimeter

Inches

MANUFACTURED TO AIIM STANDARDS
BY APPLIED IMAGE, INC.

1 of 1

(CLASSIFICATION)

DOCUMENT NO.

BW-76316

SERIES AND COPY NO.

DATE _____

January 23, 1963

GENERAL ELECTRIC

HANFORD ATOMIC PRODUCTS OPERATION - RICHLAND, WASHINGTON

X

THIS DOCUMENT CONTAINS RESTRICTED DATA AS
DEFINED BY THE ATOMIC ENERGY ACT OF 1954
AND ITS REGULATIONS, TITLE 10, PART 301, OF THE
CODE OF FEDERAL REGULATIONS. IT IS THE POLICY
OF THE UNITED STATES GOVERNMENT TO PROMOTE
THE EXCHANGE OF INFORMATION AND KNOWLEDGE
AMONG PERSONS WHO ARE PROMOTING THE
PEACEFUL USES OF ATOMIC ENERGY AND TO
CONTROL THE RELEASE OF INFORMATION THAT
RELATES TO THE NATIONAL DEFENSE, THE
COMMON DEFENSE, OR THE COMMON INTERESTS
OF THE UNITED STATES.

TITLE

REPORT OF INVENTION

OTHER OFFICIAL CLASSIFIED INFORMATION

THIS MATERIAL CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING OF THE ESPIONAGE LAWS, TITLE 18, U.S.C., SECS. 793 AND 794, THE TRANSMISSION OR REVELATION OF WHICH IN ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW.

AUTHOR

L. W. Lang

PIEDMONT FILE

RECEIVED 11

JAN 19 1964

1.

TECHNICAL ...

THIS DOCUMENT MAY NOT BE DISTRIBUTED UNLESS WHERE AN AUTHORIZED PERSON MAY ACCESS TO IT. NO OTHER INFORMATION IS TO BE APPROVED OR DISAPPROVED WITHIN APPROVED AREAS WHILE YOU USE IT. YOU MUST NOT COPY IT OR REPRODUCE IT IN ANY MANNER. IT IS YOUR RESPONSIBILITY TO OBTAIN IT AND COMPLY WITH THE LIMITS OF APPROVED AND DISAPPROVED INFORMATION. IF YOU HAVE ANY QUESTIONS, PLEASE CONTACT THE PERSON WHO PROVIDED IT. IF ADDITIONAL COPIES ARE REQUIRED, OBTAIN THEM FROM THE SOURCE ISSUED FILE. IF PERSON READING THIS DOCUMENT ARE REQUESTED TO SIGN IN THE SPACE PROVIDED BELOW:

ROUTE TO:

PAYROLL NO.

LOCATION[illegible]

SIGNATURE AND DATE

Severe Handling This Document Authorization
Is Required From L. H. Long
Of The Ind. Sec. - I.R.D. Department

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DECLASSIFIED

84-3688-340 (3-57) ASS-GE RICHLAND, WYOM.

(CLASSIFICATION)

DECLASSIFIED

HW-76316
Page 1

DISTRIBUTION

- 1-6. R. Keith Sharp
7. A. B. Greninger
8. O. H. Greager
- 9-13. L. W. Lang
14. R. H. Meichle
15. R. Nilson
16. O. C. Schroeder
17. Records Center
18. 300 Files

Classification Cancelled and Changed To

DECLASSIFIED

By Authority of BM ITC

CG-PR-2 3-17-94

By DKHanson 4-17-94

Verified By JE Samely 4-18-94

This document contains restricted data as defined in the Atomic Energy Act of 1954. Its transmission or disclosure in any manner to unauthorized persons is prohibited.

This document consists of
3 pages. No. 9 of
18 copies.

January 23, 1963

REPORT OF INVENTION

SUMMARY

This invention discloses a method of making a synthetic nuclear fuel by mixing pure U-233 with U-238 fuels, such as depleted uranium, to produce a fuel that combines the most desirable nuclear properties of both the U-233 and U-238 fertile material. The process requires that U-233 be manufactured in such a manner as to be relatively uncontaminated from U-232.

DISCUSSION

The subject of this invention is a method of fuel handling that incorporates the desirable features of both U-233 and U-238. It is proposed that U-233 be formed by short-term irradiations of thorium that will minimize contamination by U-232. At the end of a short thorium irradiation the U-233 is removed and combined with U-238. This combination then makes a synthetic fuel that has all the advantages of each ingredient but does not run into significant U-232 contaminant problems. These advantages are:

1. The resonances and fast fission multiplication associated with U-238 fuels still contribute to conversion ratio.
2. Higher neutron production per neutron absorption is achieved by using U-233 as a fuel instead of U-235.

DECLASSIFIED

3. The U-233 does not become highly contaminated with U-232 and can be reprocessed without requiring shielded handling because of the radioactivity from the U-232.
4. The thorium ores do not become contaminated with thorium-228 and can be irradiated for an indefinite number of short term irradiations.
5. Depleted U-233 fuels would be enriched simply by adding additional material and would not involve the expenditure for gaseous diffusion separative duty inherent in the enrichment of U-235 fuels.
6. Numerous advantages might accrue to reactor design and operation, such as:
 - a. Reduced inventory of fissionable material.
 - b. Longer irradiations between fuel loads.
 - c. Reduction in reactor size and/or control requirements.

Two precautions must be observed to make pure U-233 at a reasonable unit cost. First, a thorium source must be used that has low Th-230 content. Thorium-230 and (n, α) product, protactinium-231, have relatively large thermal neutron cross-sections favoring the production of U-232. All thorium ores contain a small percentage of thorium-230. The thorium-230 is a decay product of U-234 and thus a product of the uranium fraction of mixed thorium-uranium deposits. The relatively pure thorium ores, such as the monazite sands of Brazil and India and thorium ores from the Lemhi Pass area of Idaho will have relatively low thorium-230. Thorium raw materials generally available in the United States are obtained as by-product from uranium refining. Canadian mills are the only North American source of thorium ores currently available. These ores have been reported as having 36 ppm thorium-230 by C. Rohrman⁽¹⁾. This amount of thorium-230 contributes the majority of U-232 end product during short irradiation periods. If ores containing 0.5 ppm thorium-230, such as the monazite sands, could be utilized for these short term irradiations, the U-232 content would be reduced by a factor of four or more.

The second precaution required for making pure U-233 is the minimization of neutrons of sufficient energy to cause $n, 2n$ nuclear events. The $n, 2n$ reaction of thorium-232 produces protactinium-231 that in turn captures a neutron to form U-232. Neutrons contributing to the $n, 2n$ reaction can be from the nuclear fuel used in the irradiation or from the fissioning of U-233. By removing the nuclear fuel from the vicinity of the thorium, the $n, 2n$ reaction can be reduced. The U-233 fissioning does not occur until appreciable quantities of U-233 have been built into the column. Thus, to minimize the buildup of U-232 from $n, 2n$ reactions, several steps may be taken. The nuclear fuel should be removed from the vicinity of the thorium. A "striped" loading of alternated fuel and target elements should not be considered. Secondly, the irradiation must be terminated before significant amounts of U-233 fissioning occurs. The thorium used for short-term irradiation can be recovered and re-irradiated indefinitely without becoming contaminated by thorium-228, the daughter of U-232, if these procedures are used.

(1) C. Rohrman - personal communication.

DECLASSIFIED

Blending of U-233 with U-238 could be accomplished in any of several chemical forms. Liquid blending could be performed as nitrate. Gaseous blending of the components as UF_6 would be possible, or dry blending as UF_4 might also be considered. Cascade depleted uranium would appear to be the most obvious source of U-238, although uranium of higher U-235 levels, such as natural uranium, could be used. The cross-sections of U-235 and U-233 are nearly equal and little selective burnout of one isotope over the other will occur in the reactor.

ORIGINAL SIGNED BY
L. W. LANG

Principal Engineer-Reactor Process
Manufacturing Section
IRRADIATION PROCESSING DEPARTMENT

LW Lang:ewm

DECLASSIFIED

DATE

FILMED

8/3 /94

END