Systematic Assessment of the State of Hazardous Waste Clean-up Technologies

**Quarterly Technical Progress Report
for Period October 1 through December 31, 1992**

Work Performed Under
Contract No.: DE-FC21-92MC29467

For
U.S. Department of Energy
Office of Fossil Energy
Morgantown Energy Technology Center
P. O. Box 880, Collins Ferry Road
Morgantown, West Virginia

By

Mitchell T. Berg, Department of Industrial Engineering
Brian E. Reed, Department of Civil Engineering
Mo Gabr, Department of Civil Engineering
William A. Sack, Department of Civil Engineering
West Virginia University
Morgantown, West Virginia 26506

January 1993

TABLE OF CONTENTS

1.0	EXECUTIVE SUMMARY	1
2.0	BACKGROUND	1
3.0	METHODOLOGY	2
4.0	RESULTS AND DISCUSSION	5
5.0	CONCLUSION	5

LIST OF FIGURES

<u>Figure No.</u>	<u>Page</u>
1.0 Division of Technologies	3
2.0 Conceptual View of Database Construction	4

1.0 EXECUTIVE SUMMARY

It is estimated that over 3700 hazardous waste sites are under the jurisdiction of the Department of Energy (DOE). Over the next 30 years, the Department of Energy (DOE) is committed to bringing all its facilities into compliance with applicable Federal, State, and local environmental laws and regulations. To perform this clean-up effort in the most efficient manner at each site will require that DOE managers have access to all available information on pertinent technologies; i.e., to aid in maximum technology transfer. The purpose of this effort is to systematically develop a database of those currently available and emerging clean-up technologies.

The development of a database of those currently available and emerging clean-up technologies is to be done in several phases: 1) A systems approach, 2) data collection, and 3) software development. Although the project officially started October 1, 1992, our award did not arrive until December, 1992. Thus, our main effort in this quarter was 1) the recruitment of graduate research assistants, 2) the organization of project responsibilities, and 3) the procurement of software. Currently, we are in the process of an initial screening of DOE hazardous waste sites. This task should be completed within the next several weeks.

2.0 BACKGROUND

It is estimated that over 3700 hazardous waste sites are under the jurisdiction of the Department of Energy (DOE). These sites were primarily generated from 45 years worth of environmental pollution from the design and manufacture of nuclear materials and weapons, and contain numerous types of wastes including: 1) volatile, low-volatile and nonvolatile organics, 2) radionuclides (e.g., uranium, plutonium and cesium), 3) nonradioactive heavy metals (e.g., chromium, nickel, and lead), and 4) toxic chemicals. These contaminants affect several media including soils (saturated and unsaturated), groundwater, vegetation, and air. Numerous and diverse DOE hazardous waste sites can be enumerated from soils contaminated by organics such as trichloroethylene (TCE) and perchloroethylene (PCE) at the Savannah River site to biota and vegetation contaminated by radionuclides such as radiocesium and radiostrontium at the Oak Ridge site.

Over the next 30 years, the Department of Energy (DOE) is committed to bringing all its facilities into compliance with applicable Federal, State, and local environmental laws and regulations. This clean-up task is quite complex involving numerous sites containing various radioactive, organic and inorganic contaminants. To perform this clean-up effort in the most efficient manner at each site will require that DOE managers have access to all available information on pertinent technologies; i.e., to aid in maximum technology transfer. The purpose of this effort is to systematically develop a database of those currently available and emerging clean-up technologies.

The construction of a database of clean-up technologies requires a systematic development

of those steps necessary to achieve clean-up objectives. These steps and associated technology groupings are given in Figure 1.

The initial step in assessing a potential hazardous waste site is the characterization and identification of the type and extent of the contamination. In this characterization step technologies are required both for in-situ and ex-situ assessment of contamination levels. Once site characterization is performed, the risks posed by the contamination must be assessed. This step necessitates the use of mathematical models to predict contaminant fate and subsequent impact on local populations. Assuming that a risk exists, technologies must then be examined (or developed) to either extract the contaminant from the fostering media for treatment and/or disposal, treat the contaminant in-situ, or directly dispose of the contaminant. Furthermore, at each step in the clean-up process decisions regarding technology choices must be made within the existing political, economic, and social climate.

Using the conceptual approach given in Figure 1, a systematic assessment of available and emerging technologies in each area will be developed. This will be accomplished for each area by the development of a database of both current and emerging technologies. An example to illustrate the concept of such a database is given in Figure 2. In this simple example, the user of the database may be interested in investigating the available technologies for cleaning up a soil contaminated by dioxin (TCDD). In this case, information regarding soil extraction and treatment procedures is organized such that the user can extract pertinent clean-up information.

It is envisioned in the initial phase of development that a DOE manager via a computer terminal will have access to information in the database via a query system. This system will allow the user to access the different available technologies for each step in the clean-up process, and extract pertinent information on how to proceed and obtain more detailed information. A natural result of such a systematic assessment is the discovery of where clean-up capabilities are lacking. Thus, as the process proceeds, a database will be compiled of those clean-up processes that are in need of further research.

3.0 METHODOLOGY

The development of a database of hazardous waste technologies will be carried out in several phases:

Phase I: A systems approach. This phase involves a systematic development of the components to be included in the database. The approach will drive the development of the computer database. The following sub-tasks are to be performed:

1. An initial screening of DOE hazardous waste sites;
2. The development of a conceptual model to classify DOE hazardous waste problems;
3. An initial formulation of the structure (or fields) of the database.

Figure 1. Division of technologies based on primary steps necessary for clean-up

Figure 2: Conceptual view of database construction in which the arrows indicate one path explored for the clean-up of 2,3,7,8 Tetrachlorodibenzo-p-dioxin (TCDD)

Phase II: Data collection. In this phase a complete review of the current clean-up technologies will be done. This review will be driven by the database structure developed in phase I (sub-task 3), and will be accomplished through a comprehensive literature review, discussions with clean-up experts, and possible hazardous waste site visitations.

Phase III: Software development. In parallel with the data collection phase of this work, a computer based database is to be developed. This includes a data storage/retrieval system along with user friendly access software. Several main sub-tasks are to be performed including:

1. Development of a user friendly front end (i.e., user interface);
2. Development of the structure of the database;
3. Input of the technologies collected in the data collection phase;
4. Software verification and testing.

4.0 RESULTS AND DISCUSSION

Although the project officially started October 1, 1992, our award did not arrive until December, 1992. Thus, our main effort in this quarter was 1) the recruitment of graduate research assistants, 2) the organization of project responsibilities, and 3) the procurement of software. As of January, 1992 we have recruited several graduate students who will function both to aid in the collection of data (phase II) and to work on software development. Graduate students involved directly in software development include Alok Bhatia and Gopi Sabnavis, both Master's students in the Department of Industrial Engineering. We have also organized project responsibilities toward the collection of data. All faculty will be responsible for the collection of data on characterization, extraction, treatment and disposal technologies in their field of expertise. Such data will be reported to the P.I. for integration into the database. We have also selected and ordered database software for the project. We have selected the relational database software FOX PRO 2.5 as our development package. This software will be run on an Intel 486 based computer.

Currently, we are in the process of an initial screening of DOE hazardous waste sites. This task should be completed within the next several weeks.

5.0 CONCLUSION

We are currently in the process of the initial phases of our study. To date, the resources necessary for the project have been assembled. In the next quarter, it is expected that a systematic assessment (i.e., phase I) will be near completion.

Site Remediation Technologies: Drain-Enhanced Soil Flushing for Organic Contaminants Removal

**Quarterly Technical Progress Report
for Period October 1 through December 31, 1992**

Work Performed Under
Contract No.: DE-FC21-92MC29467

For
U.S. Department of Energy
Office of Fossil Energy,
Morgantown Energy Technology Center
P. O. Box 880, Collins Ferry Road
Morgantown, West Virginia

By
M. A. Gabr, Department of Civil Engineering
J. J. Bowders, Department of Civil Engineering
B. E. Reed, Department of Civil Engineering
W. J. Sack, Department of Civil Engineering
M. T. Berg, Department of Industrial Engineering
West Virginia University
Morgantown, West Virginia 26506

January 1993

ABSTRACT

The effectiveness of the soil flushing process is limited by the extent with which the contaminant is extracted from the soil and solubilized in the flushing solution, and the ease with which the flushing solution moves through the contaminated soil. Generally, for fine grained soils, both the extraction of the contaminant from the soil and movement of flushing solution are less than that observed for large grained soils (i.e., sands). Thus, soil flushing is not always effective for remediating contaminated aquifers and the use of "pump and treat systems" on extremely long term basis is often required.

Prefabricated Vertical Drains (PVD) can be used to shorten the drainage path of the flow and therefore expedite the soil flushing process. Because the installation process is relatively simple and inexpensive, fluid extraction using this process can prove to be practical and cost-effective. Compared to conventional well fields and drains, the use of PV drains would expedite the contaminant recovery and reduce both labor and material costs.

Work to be conducted in this research investigates major parameters affecting the efficiency of contaminant extraction using PV drains. A single polycyclic aromatic hydrocarbon (PAH), in this case naphthalene ($C_{10}H_8$), is chosen as the study contaminant. Analysis to be conducted include naphthalene (by GC method 8100, USEPA, SW-846), and total organic carbon or chemical oxygen demand. The testing program include column and batch studies to estimate appropriate environmental and engineering parameters for the soils, contaminants, and surfactants under consideration. In addition, several pilot scale systems (Contaminant Recovery Cells, CRC) in which the recovery efficiency of the PV drains will be evaluated.

Preliminary laboratory work was conducted to evaluate the proper mix of the soil to be used in the testing program. Compaction tests according to ASTM 698D and permeability tests according to ASTM D5084 were conducted using blends of kaolinite and Ottawa sand. The blends consisted of 80/20 percent by dry weight sand to kaolinite. The average coefficient of permeability varied with the moisture content of the samples and was estimated to be on the order of 1×10^{-5} to 1×10^{-4} cm/sec. Based on the results of these experiments the blend to be used in the experiment will range from 80/20 to 70/30 sand to kaolinite.

In addition, acrylic material for construction of the column and the recovery cells has been ordered. Gas Chromograph (GC) for conducting analysis including naphthalene by GC method 8100, USEPA SW-846 has been ordered.

TABLE OF CONTENTS

Page No.

1.0 INTRODUCTION	1
2.0 BACKGROUND	2
2.1 Soil Flushing as a Remediation Technique	2
2.2 PV Drains and Subsurface Liquid Movement	3
2.3 Examples of PAHs Contaminated Sites	5
2.4 Use of Surfactants to Remove Soil-Bound Organics	6
2.5 PAH Adsorption and Desorption, Degradation, and Volatilization	7
2.5.1 Adsorption and Desorption	7
2.5.2 Biodegradation	8
2.5.3 Volatilization	8
3.0 METHODOLOGY	8
3.1 Laboratory Testing	8
3.1.1 Batch Isotherms	9
3.1.2 Column Studies	9
3.1.3 Contaminant Recovery Cells	9
4.0 RESULTS AND BENEFITS EXPECTED	10
5.0 CONCLUSIONS	10
6.0 REFERENCES	11
6.0 FIGURES	14

LIST OF TABLES

Table 1. Characteristics Affecting the Soil Flushing Process	3
Table 2. Surfactant Types	6
Table 2. Contaminant Recovery Cells and Operating Parameters	10

LIST OF FIGURES

Figure 1. Schematic of Conventional Soil Flushing Process	15
Figure 2. Field Installation Scheme of PVD System	16
Figure 3. Proposed Field Installation Scheme for Contaminant Recovery	16
Figure 4. Variation of Dry Unit Weight and Coefficient of Permeability as a Function of Moisture Content	17

1.0 INTRODUCTION

Recently, the United States Environmental Protection Agency (USEPA) evaluated the progress of 112 sites where groundwater extraction was an integral part of containment and/or restoration activities (USEPA 1989a,b,c). The majority of the 112 sites were contaminated with organic compounds. The type and concentration of these organic compounds were found to be extremely diverse. In general, chemicals such as TCE, creosote, and PCBs have been reported as contaminants of concern (USEPA 1989d). In addition to the variety of contaminants and concentrations that prevail at these sites, wide variations in soil type, geological formation, and hydrogeologic conditions exist. A "typical" contaminated soil is difficult to define and remediation measures are usually developed on a site-specific basis.

There are a number of approaches to remediation that are used at contaminated sites. Examples are in-situ bioremediation, vacuum or air stripping, immobilization, and soil washing/flushing. In the case of in-situ bioremediation, organic compound(s) are biochemically degraded within the contaminated subsurface. Air or steam stripping are feasible if the Henry's Law constant of the organic compound(s) is greater than 3×10^{-3} atm/m³ mol. In the case of immobilization techniques, contaminants are tightly bounded within a solid matrix that minimizes their migration. Solidification, stabilization, and vitrification are the principal immobilization techniques. Contrary to immobilization, the soil washing/flushing approach promotes contaminant solubilization and migration in the liquid phase so that the contaminants can be easily flushed from the soil matrix. Soil washing refers to ex-situ remediation of soils whereas soil flushing refers to in-situ extraction of contaminants (i.e., pump and treat technology). Considering all remediation approaches, only soil flushing and stripping remove contaminant(s) from the contaminated zone without excavating the soil. Of these two, soil flushing is the process of investigation in this research proposal.

The effectiveness of the soil flushing process is limited by the extent that the contaminant is extracted from the soil and solubilized in the flushing solution, and the ease with which the flushing solution moves through the contaminated soil. Generally, for fine grained soils, both the extraction of the contaminant from the soil and movement of flushing solution are less than that observed for large grained soils (i.e., sands). Thus, soil flushing is not always effective for remediating contaminated aquifers and the use of "pump and treat systems" on extremely long term basis is often required.

The improvement of flushing solution movement in low permeability soils (10^{-4} to 10^{-7} cm/s) is the subject of this research proposal. Specifically, the use of Prefabricated Vertical Drains (PVD), also referred to as wick drains, to decrease the flow path and travel time between flushing solution injection and extraction points will be investigated. The development of improved flushing agents (e.g., surfactants) is not within the scope of this proposal. Rather, several flushing agents will be selected based on literature and manufacturers' information and their effectiveness in extracting contaminants from soils will be evaluated in the laboratory. The most effective extracting agent(s) will then be employed to demonstrate the feasibility of using PV drains to improve the soil flushing process.

A cresote contaminated site has been selected as the object of remediation. The chemical composition of cresote is approximately 85 percent polycyclic aromatic hydrocarbons (PAHs), 10 percent phenolic compounds and 5 percent others (N, S, and O heterocyclic compounds). Thus, a single PAHs will be used as the study contaminant. Naphthalene will be used as the study contaminants.

In summary, the proposed research has as its objective the completion of the following three phases of study:

Phase 1: Quantifying the parameters that govern the release and transport of PAHs by and through the subsurface.

Phase 2: Development of a predictive mathematical model to simulate full-scale operation of PV drain-enhanced soil flushing systems.

Phase 3: Operation of a mesoscale pilot facility to investigate the performance of the PV drain-enhanced soil flushing technique and to calibrate the predictive model.

Specific tasks for each phase of the research program are discussed in the Investigative Approach section of this proposal.

2.0 BACKGROUND

In this section, background information on the conventional soil flushing system, the use of PV drains to improve liquid movement in the subsurface, and how PV drains will be used to improve the soil flushing system, will be presented. Because the focus of this research is on improving the movement and extraction of the flushing solution through the contaminated zone, the literature review will focus on liquid and mass transport in the subsurface. However, a brief discussion on PAHs contaminated sites, and the fate of PAHs in the subsurface (adsorption, desorption, biodegradation, and volatilization) is included.

2.1 Soil Flushing as a Remediation Technique

In soil washing/flushing water is the primary washing fluid; chemical additives are carried by the water to promote contaminant solubilization. Non-ionic and ionic surfactants, acids, and solvents are examples of chemical additives. While soil flushing is the focus of this research, much information can be gained by examining the effectiveness of chemical additives in extracting soil-bound contaminants in the soil washing process. Soil washing refers to the ex-situ remediation of soils, whereas soil flushing refers to the in-situ extraction of contaminants. Use of these two methods has been limited. However, of these two methods, there has been a greater amount of study conducted on soil washing systems, especially in Europe (USEPA, 1988a).

The conventional soil flushing process involves a number of steps. Each step must be considered separately when assessing the overall effectiveness. The four steps are:

- 1) contaminant solubilization by the wash fluid (surfactant),
- 2) extraction of the solubilized contaminants from the subsurface,
- 3) treatment of the spent flushing water, and,
- 4) disposal/reuse of the treatment residuals.

A general schematic of the first two steps, which defines the scope of this proposed investigation, is shown in Figure 1 (Holden et al. 1989). Conditions adversely affecting the success of soil flushing process are listed in Table 1. Hydrogeologic conditions of the contaminated area are extremely important to the success of the soil flushing process. USEPA (1988b) reported that soil flushing has been used at five Superfund sites for the removal of organics. The permeability of the soils at these sites was relatively high. Currently, the soil flushing option is difficult to implement at sites with low permeabilities.

Table 1. Characteristics Affecting the Soil Flushing Process

Characteristics	Reason for Potential Impact
Unfavorable Waste Characteristics Mixed waste types Variable Waste Composition	Washing solution difficult to formulate Frequent formulation of washing solution
Unfavorable Soil Characteristics Variable soil conditions Low permeability High soil humic content Soil-solvent interactions	Inconsistent flushing Movement of flushing solution hampered Desorption difficult Desorption inhibition
Unfavorable Flushing Solution Characteristics Difficult recovery of washing solution Poor treatability of washing solution Toxicity of washing solution Reduction of soil permeability	High costs Replacement of washing solution Health risks Flushing chemicals reduce porosity.

Source: Technology Screening Guide for Treatment of CERCLA Soils and Sludges, U.S. EPA, 1988.

2.2 PV Drains and Subsurface Liquid Movement

Prefabricated vertical (PV) drains, also referred to as wick or strip drains, were originally developed as a substitute for the commonly used sand drains. They have been used extensively in the past for the expedient drainage and consolidation of low permeability soils under surface

surcharge. The design of prefabricated vertical drains varies according to a specific application. Key parameters usually addressed in the design include:

1. Equivalent diameter of the drain which dictates the size of the inflow surface; and,
2. Discharge capacity of the drain .

As described by Anon (1988) PV drains consist of porous geotextiles wrapped around a plastic drainage core 3 to 4 inches wide and one quarter to 3/8 of an inch thick. PV drains are usually spaced in a manner to allow the dissipation of pore pressure generated due to the application of surcharge or hydraulic stresses on the system. They provide a conduit for flow under the induced hydraulic gradient. Typically they are arranged in a triangular or square grid pattern with 3 to 12 feet spacing. Installation rates reported in the literature are on the order of 1-3 feet per second excluding equipment mobilization and set-up time. Figure 2 illustrates the installation process of a typical PV drain configuration in a field situation.

The use of synthetic PV drains has evolved to many applications and several case studies were reported in literature. A theoretical study pertaining to the design and application of vertical drainage systems was conducted by Guido (1986). Recommendations for the selection of design spacing for band-shaped PV drains were examined. A comprehensive research program was carried out by New York State Department of Transportation (Suits et al 1986) to estimate the effectiveness of several types of PV drains. This research program included laboratory and field testing. Results indicated the suitability of using PV drains to accelerate the drainage of a given soil profile.

A successful implementation of PV drains was presented by Mattox (1987). In this project, construction of a 21.7 ft high embankment over weak marsh deposits in Mobile, Alabama, was accomplished through the use of geogrid reinforcing and PV drains. Installation of PV drains was necessary to reduce the time required for settlement of the embankment through accelerated drainage of the subsurface profile. Estimated savings due to the use of the innovative drainage technology was on the order of \$600,000. In another application, Thacker et al (1988) presented a case in which PV drains were used in the construction of a coal refuse impoundment to allow complete pore pressure dissipation. Field measurements with pneumatic piezometers indicated that the use of PV drains in the drainage scheme was successful. The coal refuse impoundment met prudent engineering criteria with regard to stability even though a large portion of the dam was being built over hydraulically filled fine coal refuse. In a similar application, Saye et al (1988) presented a case in which PV drains, installed at spacing ranging from 3 feet to 5.5 feet, were used in order to facilitate drainage and strength gain of soft highly plastic clay deposited in a cutoff oxbow of the Missouri River.

In general, research work conducted to quantify the performance of the PV drains is mostly directed toward the drainage potential to accelerate the consolidation process, or compression of a soil profile due to expulsion of water. No research specifically addressed the quantity of flow being collected using a PV drainage scheme. Furthermore, no research was conducted to

address the potential of using a PVD drainage scheme for the removal of pollutant substances from subsurface soils.

However, some research was conducted on the retrieval of tracers in agricultural applications through the use of subsurface drains. Everts and Kanwar (1990) presented the results of a study in which potassium bromide and calcium nitrate were used as tracers in sprinkler irrigation water. These tracers were applied to a field plot drained with a single subsurface drain line during two irrigations. Drain outflow was measured, and water samples were collected from drain discharge and analyzed for Nitrate (NO_3^-) and Bromide (Br^-) content. Results indicated that, transported on a mass basis, 24% and 12% of the bromide and 20% and 9% of the nitrate reach the drain, respectively, during the two sprinkler irrigations. Although not directly related to the scope of the proposed work, the results of this study indicates the promising potential of using subsurface drains for collecting subsurface pollutants.

In summary, PV drains shorten the drainage path of the flow and therefore would expedite the soil flushing process. Compared to conventional well fields and drains, the use of PV drains would reduce both labor and material costs. Because the installation process is relatively simple and inexpensive, fluid extraction using this process can prove to be practical and cost-effective. Figure 3 schematically shows a possible arrangement for the use of PVD system for recovery of subsurface pollutants in the field.

2.3 Examples of PAHs Contaminated Sites

There are over 2000 wood preserving sites in the United States requiring remediation with over 50 of these sites on the National Priority List (NPL), Stinson et al. (1991). The MacGillis and Gibbs Superfund site in New Brighton, Minnesota, is heavily contaminated with cresote, pentachlorophenol, and fuel oil. PAH concentrations as high as 407 mg/kg have been reported (Stinson et al. 1991). PAH concentrations of 2,800, 240, and 10 mg/kg for peat, soils, and sediments, respectively, have been reported at the Pine Street Canal Superfund site in Burlington, Vermont, (Weir and McLane 1991). Christiansen et al. (1991) reported PAH concentration exceeding 1900 mg/kg at an undisclosed Texas site. PAH concentrations exceeding 3,000 mg/kg and 20,000 mg/kg have been reported at the Bayou Bonfouca (Slidell, Louisiana) and the Jennison-Wright (Granite City, Illinois) sites, respectively, as stated by Halloran et al. 1991. In examining contaminated sites, a wide variety of PAHs (and other organic contaminants) are present in widely ranging concentrations. Thus, remediation research must address diverse conditions. However, because the main focus of this research project is the improvement of the liquid movement phenomenon of the soil flushing process, relatively simple PAHs (e.g., naphthalene) will be chosen as the study organics. It is tacitly assumed that the PV drain-enhanced soil flushing method will improve the efficiency of the pump and treat process regardless of the specific organic contaminant(s).

2.4 Use of Surfactants to Remove Soil-Bound Organics

Surfactant molecules have both a polar (hydrophilic) and nonpolar (hydrophobic) segment and thus they accumulate at polar-nonpolar interfaces. Above a certain concentration surfactants will form micelles (aggregates). The polar end of the molecule in the micelles is presented to the aqueous phase. The nonpolar end of the surfactant molecule faces inward, away from water molecules. The interior of the surfactant micelles is nonpolar and thus can solubilize nonpolar compounds that are sorbed onto soil particles. A large number of commercial surfactants that are environmentally safe and relatively inexpensive are available. Surfactant types can be categorized as ionic (anionic, cationic), nonionic, and amphoteric. Examples of surfactants and their characteristics are presented in Table 2 (USEPA 1985).

Table 2. Surfactant Types

Anionic	Cationic	Non-ionic	Amphoterics
Carboxylic acid salts	Long chain amines	Alcohol ethoxylates	pH sensitive
Sulfonic acid salts	Quaternary ammonium salts	Polyoxyethylenated alkylphenols	pH insensitive

The use of surfactants was first investigated by the Texas Research Institute (1979, 1985) as a method of recovering gasoline. Ellis et al. (1985) investigated the use of nonionic surfactants for removal of PCBs, chlorinated phenols, and petroleum hydrocarbons from soils. At surfactant concentrations of 1.5 percent (by volume) over 90 percent of the contaminants were removed from the soil. The use of surfactants increased removal by an order of magnitude over that observed for a water-only flush. A possible drawback to using nonionic surfactants in the soil flushing process is the difficulty encountered in separating the surfactant from the contaminated groundwater and subsequent surfactant reuse. Nash (1987) investigated surfactant enhanced soil flushing at the lab and field-scale using soil from the Volk Air National Guard Base, Wisconsin. Significant removal of organics in the lab-scale systems was reported. However, organic removal in the field-scale systems was less than that observed in the laboratory. The decrease in organic removal was attributed to the surfactant not penetrating the soil.

Liu et al. (1991) investigated the solubilization of several PAHs (anthracene, phenanthrene, and pyrene) by nonionic and anionic surfactants. Nonionic surfactants octyl- and nonyl-phenylethoxylates (9 to 12 ethoxylate units) were the most effective. A 1 percent (by volume) surfactant dosage was required to achieve 70-90 percent solubilization. Fountain and Hodge (1992) reported that several surfactants were able to increase the solubility of common chlorinated organics (e.g., perchloroethylene (PCE)) by several order of magnitudes. They also reported that, for PCE, several surfactants lowered interfacial tension between water and PCE to less than 1 dyne/cm causing downward vertical movement of the PCE. Thus, proper selection of surfactant mixtures is required if spreading of the contaminant downwards towards

uncontaminated soils is to be minimized.

Dworkin et al. (1988) and Kuhn and Piotek (1989) reported favorably on the use of soil flushing for wood preserving contaminated sites. The relationship between the amount of contaminant that is solubilized and the surfactant concentration is approximately linear provided that the surfactant concentration is above the "critical" micelle concentration (CMC) as described by Gannon et al. 1989. At surfactant concentrations below the CMC contaminant solubilization does not occur. Gannon et al. (1989) reported that the CMC may be substantially reduced by the presence of a hydrophobic contaminant. However, Liu et al. (1991) reported that the solubilization of several soil-bound PAHs occurred at surfactant concentrations that were larger than the "clean-water" CMC.

In summary, a great deal of research on the development and use of surfactants to remove organic compounds from soils has been conducted. Based on results from lab-scale studies as well as full scale remediation systems, the use of surfactants in the remediation of contaminated soils appears to be promising. As mentioned previously, the focus of this research is not the development of improved surfactants but rather the improvement of the movement of the flushing solution through the contaminated zone. Thus, surfactants, such as those presented in Table 2, will be selected based on literature and manufacturers' information. Their effectiveness in extracting contaminants from soils will be determined in the laboratory and the most effective and environmentally safe agents(s) will then be employed in the demonstration of the PV drains enhanced soil flushing process.

2.5 PAH Adsorption and Desorption, Degradation, and Volatilization

The fate of contaminants in the subsurface is influenced by the extent with which the contaminant adsorbs and desorbs, degrades, and volatilizes. Each of these topics will be discussed separately. The majority of the review focuses on adsorption and desorption because during the conduct of the proposed research, steps will be taken to minimize degradation and volatilization.

2.5.1 Adsorption and Desorption

PAHs, the study contaminant, readily accumulates on soil particles. The concentration of the soil-bound contaminant can be related to the solution concentration through a number of isotherms (Freundlich, Langmuir, and B.E.T). In this study it is assumed that the soil has been contaminated thus, adsorption of the PAH will not be examined to a large extent. However, the adsorption of the surfactant-PAH onto clean soil will be investigated. It is conceivable that the contaminated flushing solution will pass through areas of the subsurface that are not contaminated and thus, it is possible that readsorption can occur. Desorption or solubilization of the contaminant from the soil in the presence of surfactants will be studied.

2.5.2 Biodegradation

A large number of organic compounds are subject to biochemical degradation. Biological treatment of contaminated sites has been named as the remediation technique in about 15 percent of the Records of Decision (ROD) (Christiansen et al. 1991). Naphthalene, the simplest PAH, is considered relatively degradable with a BOD5/COD ratio of < 0.2 (USEPA 1985). Christiansen et al. (1991), reported that the half-lives of total and carcinogenic PAHs in a soil-sludge slurry reactor were between 16 and 88 days. Weir and McLane (1991) reported that PAHs of low molecular weight (e.g., naphthalene and 2-methylnaphthalene) were biodegradable in soils, but higher weight PAHs were not. Berg et al. (1991) demonstrated that the composting of PAH contaminated soils was a viable treatment alternative. Total PAH soil concentration was decreased from approximately 300 mg/kg to less than 50 mg/kg in 14 weeks. Thus, it is apparent that PAHs, especially those with lower molecular weights, are susceptible to biochemical degradation. Measures to deter or account for biodegradation in laboratory experiments will be implemented.

2.5.3 Volatilization

PAHs are classified as semivolatile and generally have a Henry's constant lower than 10^4 atm/m³ mol. Organic compounds having a Henry's constant greater than 3×10^3 atm/m³ mol are candidates for air stripping (Holden et al. 1989). While volatilization of PAHs is possible, transfer of the contaminant to the gas phase is not an efficient process. However, during the conduct of this research, the loss of PAHs from the soil via volatilization will be accounted for by using a controlled experiments environment.

3.0 METHODOLOGY

The proposed research plan is the first phase of five year plan during which the major parameters affecting the efficiency of contaminant extraction using PV drains will be quantified, pilot scale study is performed and the project can move to field implementation. The current phase program consists of column and batch studies to determine appropriate environmental and engineering parameters for the soils, contaminants, and surfactants under consideration. These experiments will be conducted during year one along with several pilot scale systems (Contaminant Recovery Cells, CRC) in which the recovery efficiency (hydraulic only) of the PV drains will be evaluated for uncontaminated soils.

3.1 Laboratory Testing

During the first year of the project, laboratory studies will be conducted to ascertain fundamental parameters of the soils, contaminant and surfactants. In addition, fundamental parameters of the recovery system will be evaluated. Preliminary laboratory work was conducted to evaluate the proper mix of the soil to be used in the testing program. Compaction tests according to ASTM 698D and permeability tests according to ASTM D5084 were conducted using blends of kaolinite and Ottawa sand to select the appropriate soil mix for use in the experiments.

3.1.1 Batch Isotherms

Batch isotherm studies will be performed in order to evaluate the effectiveness of surfactants for contaminant removal from soil surfaces. A suite of tests will be performed resulting in a matrix consisting of surfactant type and concentration, and soil contact time versus percent of contaminant removed from the soil. This information will lead to the selection of a surfactant for application in the column studies and in the contaminant recovery cells. Soils will be contaminated with Naphthalene by dissolving Naphthalene in Methanol, mixing the solution with soil, and allowing Methanol to evaporate. The initial soil/Naphthalene concentration will then be determined.

As previously mentioned, surfactants will be selected based on literature and manufacturer's data. Equilibrium isotherms will be estimated for the adsorption of Naphthalene on the three soils to be considered. Also, re-adsorption of Naphthalene, in the presence of the "short-listed" surfactant, by the clean soil will be assessed.

3.1.2 Column Studies

A series of column studies will be conducted, first on clean soil and then on contaminated soil. Clean soil studies will be used to obtain permeability characteristics of the soil types both for water and for surfactants as permeating liquids. The studies on contaminated soil columns will be used to ascertain the effectiveness of the surfactant in removing contaminants under a flow type situation and estimate the dispersion/advection characteristics of the system. Only the most promising surfactants according to the batch tests will be investigated.

3.1.3 Contaminant Recovery Cells

Three contaminant recovery cells (CRC's) will be constructed and used to assess the efficiency of the PV drain contaminant recovery system. The CRC's include a central section (0.67m X 0.67m X 1.0m - length/thickness/depth of soil) which will be filled with soil. An upstream reservoir will supply a base inflow into the soil while the downstream reservoir will collect the base outflow. The reservoirs will be used to pre-saturate the soil and to apply a constant base flow during water and contaminant recovery tests. For contaminant recovery purposes, PV drains will be installed into the soil. In order to quantify recovery efficiency, single and multiple drains will be used. Two systems of fluid recovery will be evaluated. These include applying a vacuum to the drains and applying a stress on the surface of the soil. Both systems provide a driving force for fluid transport from the soil.

A list of the CRC's and associated test parameters is given in Table 3. Drain efficiencies for the removal of fluids from the soils will be quantified. The time required for construction and preparation of the cells including saturation of the soils is expected to be on the order of two to three months. Contaminant recovery is expected to last for approximately two months for each recovery mode. Thus, CRC tests are expected to require 6 to 8 months to complete.

Table 3. Contaminant Recovery Cells and Operating Parameters

CELL No.	% SAND/ KAOLINITE	No. DRAINS	CONTAMINANT RECOVERY	
			VACUUM (psi)	APPLIED PRESSURE (psi)
			10	2 - 10
1	80/20 to 70/30	1	It is estimated that each recovery step will require 2-3 months	
2	80/20 to 70/30	2		
3	80/20 to 70/30	MULTIP		

4.0 RESULTS AND BENEFITS EXPECTED

The blends consisted of 80/20 percent by dry weight sand to kaolinite. The average coefficient of permeability varied with the moisture content of the samples and was estimated to be on the order of 1×10^5 to 1×10^{-4} cm/sec. Figure 4 shows the variation of the dry unit weight and coefficient of permeability with moisture content. Based on the results of these experiments the blend to be used in the experiment will range from 80/20 to 70/30 sand to kaolinite.

While major strides in the hazardous waste management field have been made in minimizing the risks associated with the disposal of wastes being generated, hundreds of inactive and/or abandoned hazardous waste sites exist that require remediation. The required remediation approach varies from site to site, depending on the hazardous constituents and site conditions present. The proposed study is an initial step in what will be a continuing effort to develop an in situ method, namely PV drain-enhanced soil flushing, to remove PAHs and other organic compounds from the contaminated subsurface. Because there is little or no experience with using PV drains as part of the soil flushing process, the proposed study will provide fundamental and basic information on performance characteristics of the DESF process as a mean of removing contaminants from sites containing fine grained soils.

5.0 CONCLUSIONS

In summary, the proposed work is progressing on budget and on time. More laboratory tests are planned to estimate the physical and engineering properties of the test soil including Atterberg Limits, grain size distribution and compressibility characteristics.

In parallel, supplies were ordered for the construction of the columns and the recovery cells. In addition, a HP Series II Gas Chromatograph with single flame ionization detector was ordered. A research team visited the Miles company for observing the performance of the EPA 8100 protocol. It is envisioned that this protocol with slight modification can be successfully adopted for this project.

6.0 REFERENCES

- Anon (1988) "Wick drains gain acceptance," TRNews (Transportation Research Board) No. 139 Nov-Dec 1988 pp 20-21.
- Bazaraa, M., and C.M Shetty (1979) "Non-linear Programming: Theory and Applications," Wiley & Sons, New York, NY.
- Berg, J.D., A.S. Eikum, T. Eggen, and H. Selfors (1991). "Cold-Climate Bioremediation: Composting and Groundwater Treatment Near the Artic Circle at a Coke Works", In Proceedings: Hazardous Materials Control/Superfund Conference, 321-325.
- Cameron, D.R., and A. Klute (1977) Convective-dispersive Solute Transport with a Combined Equilibrium and Kinetic Adsorption Model. Water Resources Research, Vol. 13, 183-188.
- Christiansen, J.A., C.R. Page, and J.P. Perez (1991) " Large-Scale Remediation Projects," In Proceedings: Hazardous Materials Control/Superfund Conference, pp. 127-130.
- Dworkin, D., D.J. Messinger, and R.M. Shapote (1988) "In-situ Flushing and Bio Reclamation Technologies at a Cresote-Based Wood Treatment Plant", In Proceedings, 5th National Conference on Hazardous Waste and Hazardous Materials, Las Vegas, Nevada.
- Ellis, W.E., J.R. Payne, and G.D. McNabb (1985) "Treatment of Contaminated Soils With Aqueous Surfactants," U.S. EPA Report No. EPA/600/2-85/129
- Everts, C. J., and R. S. Kanwar (1990)" Estimating preferential flow to a subsurface drain with tracers," Transactions of the American Society of Agricultural Engineering, Volume 33 No. 2, Mar-Apr, pp 451-457.
- Fountain J.C. and D.S. Hodge (1992). "Extraction of Organic Pollutants Using Enhanced Surfactant Flooding - Initial Field Test," New York State Center For Hazardous Waste Management.
- Gannon, O.K., P. Bibring, K. Raney, J.A. Ward, D.J. Wilson, J.L. Underwood, and K.A. Debelak (1989) "Soil Clean Up by In-Situ Surfactant Flushing. III. Laboratory Results", Separation Science Technology, Vol. 24, 1073.
- Guido, V. A., and N. M. Ludewig (1986)" Comparative Laboratory Evaluation of Band-Shaped Prefabricated Drains" ASTM Special Technical Publication 892, American Society for Testing Materials, Philadelphia, pp. 642-662.
- Halloran, A.R., R. Troast, and D.G. Gilroy (1991) "Solvent Extraction of PAH-Contaminated Soil," In Proceedings: Hazardous Materials Control/Superfund Conference, pp. 354-361.

Holden, T. J., P. Newton, P. Sylvestri, M. Diaz, C. Baker, J.G. Herrmann, and D. Guzman (1989) "How To Select Hazardous Waste Treatment Technologies For Soils and Sludges", Noyes Data Corporation, Park Ridge, New Jersey.

Kuhn, R.C. and K.R. Piotek (1989) "A Site-Specific In Situ Treatment Process Development Program for Wood Preserving Site", R.S. Kerr Technical Assistant Program-Oily Waste, Fate, Transport, Site Characterization, and Remediation, Denver Colorado.

Liu, Z., S. Laha, and R.G. Luthy (1991) "Surfactant Solubilization of Polycyclic Aromatic Hydrocarbons in Soil-Water Suspensions," Water Science Technology Vol. 23,475-485.

Mattox, R. M. (1987) "Geogrid Reinforcement for Cochrane Bridge Embankment" Geotextiles and Geomembranes VOL. 6, No. 1-3, pp. 225-232.

Nash, J.H. (1987) "Field Studies of I-Situ Soil Washing," U.S. EPA Report No.EPA/600/2-87/110.

Saye, S. R., C. N. Easton, W.D. Smith, K. H. Nass, and C. C. Ladd (1988) "Experience with Wick drains in highway construction over soft clay - Storz Expressway" Transportation Research Record No. 1159 1988 pp. 58-67, D.C.

Suits, L. D., R. L. Gemme, and J. J. Masi (1986) "Effectiveness of Prefabricated Drains on Laboratory Consolidation of Remolded Soils" Special Technical Publication 892. American Society for Testing Materials, Philadelphia, pp 663-683.

Stinson, M.K., H.S. Skovronek, and W.D. Ellis (1991) "U.S. EPA SITE Demonstration of Biotrol Soil Washing Process," In Proceedings: Hazardous Materials Control/Superfund Conference, 686-690.

Thacker, B. K., C. R. Ullrich, J. G. Athanasakes, and G. Smith (1988) "Evaluation of a coal refuse impoundment built by the upstream method" Hydraulic Fill Structures, Geotechnical Special Publication No. 21. Fort Collins, CO. pp. 730-749.

Texas Research Institute (1979) "Underground Movement of Gasoline on Groundwater and Enhanced recovery by Surfactants," American Petroleum Institute.

Texas Research Institute (1985) "Test Results of Enhanced Surfactant Gasoline Recovery in Large-Scale Model Aquifer," American Petroleum Institute.

USEPA. (1985). Remedial Action at Waste Disposal Sites, U.S. Environmental Protection Agency, Office of Research and Development, Research Information Center, Cincinnati, OH EPA 625/6-85/006).

USEPA. (1988a). Assessment of International Technologies for Superfund Applications: Technology Review and Trip Report Results. U.S. Environmental Protection Agency, Office

of Solid Waste and Emergency Response, Office of Emergency and Remedial Response, u40/2-88/003, Washington, D.C.

USEPA. (1988b). Technology Screening Guide for Treatment of CERCLA Soils and Sludges, U.S. Environmental Protection Agency, Office of Solid Waste and Emergency Response, Office of Emergency and Remedial Response, u40/2-88/004, Washington, D.C.

USEPA. (1989a). Evaluation of Groundwater Extraction Remedies, Volume 1 Summary Report, U.S. Environmental Protection Agency, Office of Emergency and Remedial Response, u40/2-89/054, Washington, D.C.

USEPA. (1989b). Evaluation of Groundwater Extraction Remedies, Volume 2 Case Studies 1-19, U.S. Environmental Protection Agency, Office of Emergency and Remedial Response, u40/2-89/054b, Washington, D.C.

USEPA. (1989c). Evaluation of Groundwater Extraction Remedies, Volume 3 General Site Data, Data Base Reports, U.S. Environmental Protection Agency, Office of Emergency and Remedial Response, u40/2-89/054c, Washington, D.C.

USEPA. (1989d). Forum on Innovative Hazardous Waste Treatment Technologies: Domestic and International, Atlanta, GA, U.S. Environmental Protection Agency, Office of Research and Development, u40/2-89/056, Cincinnati, OH.

Van Genuchten, M. Th. (1981) " Non-Equilibrium Transport Parameters from Miscible Displacement Experiments," US Department of Agriculture, Research Report No. 119, U.S. Salinity Laboratory, Riverside, CA.

Weir, B.A. and C.L. McLane (1991) "Treatment of Coal Tar-Contaminated Soils from a Superfund Site," In Proceedings: Hazardous Materials Control/Superfund Conference, pp. 309-314.

Wilson, D.J. (1989). Soil Clean Up by in-situ Surfactant Flushing. I. Mathematical Modeling. Separation Science and Technology, Vol. 24, No. 11, 863-892.

Wilson, D.J., and A. N. Clarke (1991) "Soil Clean Up by in-situ Surfactant Flushing. IV. A Two-Component Mathematical Model," Separation Science and Technology, Vol. 26, No. 9, 1177-1194.

Yeh, G. T., and D. S. Ward (1981) "FEMWASTE: A Finite Element Model for Waste Transport Through Saturated-Unsaturated Porous Media," ORNL-5601, Oak Ridge National Laboratory, TN.

FIGURES

Source: EPA/540/2-86/003(f)

Figure 1. Schematic of Conventional Soil Flushing Process

Figure 2. Field Installation Scheme of PVD System

Figure 3. Proposed Field Installation Scheme for Contaminant Recovery

Figure 4. Variation of Unit Weight and Coefficient of Permeability with Moisture Content

Site Remediation Technologies: In Situ Bio-remediation of Organic Contaminants

**Quarterly Technical Progress Report
for Period October 1 through December 31, 1992**

Work Performed Under
Contract No.: DE-FC21-92MC29467

For
U.S. Department of Energy
Office of Fossil Energy
Morgantown Energy Technology Center
P. O. Box 880, Collins Ferry Road
Morgantown, West Virginia

By
William A. Sack, Department of Civil Engineering
Kevin D. Jones, Department of Civil Engineering
Joan E. Cuddeback, Department of Civil Engineering
Andrew K. Shiemke, Department of Biochemistry
West Virginia University
Morgantown, West Virginia 26506

January 1993

ABSTRACT

In situ bioremediation offers a number of advantages over other processes for destruction of organics in groundwater. Advantages include the potential for complete or near complete destruction of contaminants in place, avoidance of transfer of the contaminants to another medium, less risk of health hazards due to human exposure and cost-effectiveness. The objective of this research is to evaluate and optimize the ability of methanogenic and other selected bacteria for biotransformation of TCE and other volatile organic compounds (VOC's) found at DOE sites. A five-phase workplan is presented which involves the systematic manipulation of environmental conditions to enhance the rate and extent of biodegradation of the candidate VOC's. Two graduate students have been recruited and the initial project tasks of performing the literature review and procurement of necessary supplies and equipment is well underway.

Table of Contents

Page No.

1.0 INTRODUCTION	1
2.0 PURPOSE	1
3.0 BACKGROUND	1
4.0 METHCDOLOGY	2
Phase 1: Literature Review	2
Phase 2: Batch Studies to Evaluate Optimum Concentration of Growth Enhancing Agents in Both Liquid and Soil Cultures	2
Phase 3: Column Studies to Evaluate the Rate and Extent of Degradation of Candidate VOC's.	3
Phase 4: Comparison of TCE Biotransformation by Particulate and Soluble Methane Monooxygenase	3
Phase 5: Investigation of the Utilization of the Symbiotic Relationship Between Methanogenic and Methanotrophic Bacteria for VOC Degradation Without Addition of Exogenous Methane	4
5.0 RESULTS AND DISCUSSION	4
6.0 CONCLUSION	4
7.0 REFERENCES	4

1.0 INTRODUCTION

A variety of toxic organic contaminants are found at DOE sites including fuel hydrocarbons, polychlorinated biphenyls (PCB's) and volatile organic solvents such as trichloroethylene (TCE), perchloroethylene, and carbon tetrachloride. These compounds may occur as single contaminants, but are often found in conjunction with heavy metals or in mixed wastes containing radioactive components.

In situ bioremediation has a number of advantages for destruction of organic contaminants in groundwater. Other processes such as sorption and volatilization do not destroy contaminants, but rather just concentrate them or transfer them to another medium. Abiotic (chemical) transformation is not normally cost-effective in groundwaters and may even result in production of more toxic chemical species.

Clean-up methods often involve soil flushing to mobilize the contaminants for transport to the surface for treatment. However, because many organic contaminants sorb to soils, they are not readily leached from the soils often leaving toxic residuals in place even after flushing. Furthermore, bringing the contaminants to the surface increases the risk of health hazards due to human exposure. There is increasing recognition that bacteria are present and active in the subsurface and that *in situ* biotransformation offers a potentially more effective and economical method of contaminant destruction.

2.0 PURPOSE

The purpose of the research is to evaluate and optimize the ability of methanotrophic and other selected bacteria for biotransformation of TCE and other volatile organic compounds (VOC's) found at DOE sites. The approach outlined involves the systematic manipulation of environmental conditions in the subsurface for the purpose of enhancing the rate and extent of biodegradation of candidate (VOC's). This approach takes advantage of the ubiquity of methanotrophic bacteria and introduction of non-native organisms should not be necessary. Also, only relatively benign enhancing compounds will be added in non-toxic concentrations. In addition, it is envisioned to take advantage of the natural symbiotic relationship between the methanogenic and methanotrophic bacteria to aid in biotransformation.

3.0 BACKGROUND

A number of exciting developments are occurring in the field of environmental biotechnology (engineering applications of microbial ecology). For example, while trace concentrations of some organic contaminants cannot support microbial growth as the sole electron

donor, they can still be biotransformed by engineering the system so that the microbial population obtains the majority of its energy and carbon from a different compound that serves as the primary substrate. This is sometimes referred to as *secondary utilization*. There are also many organic contaminants that are biotransformed in the environment for which no microorganisms have been found which are able to use them as sole carbon source. This is a special case of secondary metabolism often termed *cometabolism*. Cometabolism has been defined (Dalton, 1982) as the "transformation of a non-growth substrate in the obligate presence of a growth substrate or another transformable compound". As an example, halogenated methanes, ethanes, and ethylenes are poor growth substrates for bacterial growth but may be degraded by methanotrophs growing aerobically on methane (Henson et al., 1988).

4.0 METHODOLOGY

The principal focus of the investigation is to develop methods which will enhance bacterial metabolism of organic contaminants in sub-surface environments in order to increase the rate and extent of biodegradation. The methodology is presented in five phases below, however it is anticipated that modifications will be made to the workplan as the work progresses.

Phase 1: Literature Review

As noted above, it is planned that the work will focus on the use of methanotrophs for *in situ* VOC destruction. However, a complete review of the bioremediation literature will be carried out whether other classes of organisms also appear attractive and the research plan may be modified. The information gained from the literature review will be utilized both in this project and in the systematic study (METC/MC-1).

Phase 2: Batch Studies to Evaluate Optimum Concentration of Growth Enhancing Agents in Both Liquid and Soil Cultures

In order to enhance microbial activity, a variety of chemical compounds will be investigated for addition to areas of sub-surface VOC contamination. However, some of the compounds to be investigated are toxic in high concentrations (for example hydrogen peroxide). Thus, the maximum allowable and optimum concentrations of each of the candidate enhancing compounds will be evaluated. Several different methanotrophic species will be tested to determine if one is significantly more hardy than others. Liquid cultures of bacteria containing various concentrations of the test compound will be monitored for the rate of growth to determine the optimum concentration to promote growth and the concentration at which inhibition occurs.

These experiments will only offer a first approximation of the optimum concentrations because liquid cultures do not closely mimic

the conditions found in sub-surface soils. Thus, additional experiments will involve inoculating soil samples containing various concentrations of test compounds (peroxide, acetate, formate, EDTA, etc.). Several methods will be evaluated to monitor cell growth such as the rate of oxygen or methane uptake, measurement of CO₂ production, microscopic cell counting, or isolation and quantification of DNA. In this way, we will be able to determine the maximum non-toxic concentration of potential biodegradation enhancing compounds.

Phase 3: Column Studies to Evaluate the Rate and Extent of Degradation of Candidate VOC's.

At this stage, the work will begin to examine the effect of promising compounds on the actual rate and extent of degradation of TCE. This work will be performed using glass columns containing soil, TCE, and methanotrophic bacteria. The columns will be flushed with a slow stream of methane to provide a source of carbon. A control column using nitrogen gas will also be examined to insure that the gas is not volatilizing the TCE.

To test the ability of hydrogen peroxide to serve as a source of oxygen, the gas phase will contain little or no oxygen, and a dilute solution of hydrogen peroxide will be added, either as a steady stream or in periodic aliquots. At various times, samples will be taken and analyzed for TCE and bacterial growth. In this way, the relationship between rate of growth, and rate of TCE oxidation, as a function of peroxide concentration may be determined. Similar experiments will be performed for other compounds such as formate, formaldehyde, and EDTA.

Phase 4: Comparison of TCE Biotransformation by Particulate and Soluble Methane Monooxygenase

Some species of methanotrophic bacteria are able to express two distinct forms of methane monooxygenase: a soluble form (sMMO) located in the cytosol, or a particulate form (pMMO) located in the cell membrane. Only one of the two forms is expressed at any given time, with the amount of available copper serving as the metabolic switch controlling expression. The sMMO is expressed only when the amount of available copper is extremely low, and this is enhanced by excess iron, a necessary cofactor of sMMO. Thus it appears that in most subsurface environments, the membrane-bound form of MMO will be expressed. Indirect evidence suggests that sMMO is the more effective form for degradation of TCE and other VOC's. Thus, by reducing the amount of available copper in the environment, it may be possible to enhance expression of sMMO, and thereby increase the rate of contaminant degradation. Various metal chelators will be used to reduce the level of available copper to evaluate the potential benefit of sMMO expression.

Phase 5: Investigation of the Utilization of the Symbiotic Relationship Between Methanogenic and Methanotrophic Bacteria for VOC Degradation Without Addition of Exogenous Methane

In order to investigate the possibility of enhancing the symbiotic relationship between methanogenic and methanotrophic bacteria, a two-part column will be used. The lower section will contain acetate and an inoculum of methanotrophic bacteria; the upper portion will contain TCE and the methanotrophs. In this way, methane produced by methanogenesis will provide the carbon source for the methanotrophic bacteria. No exogenous methane will be added, with either peroxide or air serving as the source of oxygen. The amount of oxygen added will be critical, since the methanogens are strict anaerobes. Thus the goal will be determination of the amount of oxygen needed to optimize methanotroph growth and TCE degradation without inhibiting methanogenesis. This will closely mimic the actual sub-surface conditions, with both an anaerobic zone where methane can be generated, and an aerobic zone where it can be oxidized and support growth of methanotrophs.

5.0 RESULTS AND DISCUSSION

The work on this project began on December 16, 1992 with one graduate student (Kevin Jones). A second graduate student (Joan Cuddeback) will start on the project on January 1, 1993.

During the last half of December, the literature review was initiated. In addition, methods of analysis of TCE were reviewed and equipment and supplies orders were prepared.

6.0 CONCLUSION

The work began as of December 16, 1992 and is progressing according to the work schedule.

7. REFERENCES

Dalton, H., and D. E. Stirling (1982) "Cometabolism", Philos Trans R Soc Lond., 297: 481-96.

Henson, J. M., et al. (1988) "Microbial Removal of Halogenated Methanes, Ethanes, and Ethylenes in an Aerobic Soil Exposed to Methane" FEMS Microbiology Ecology, 53 (3/4) 193-201.

Excavation Systems for Hazardous Waste Sites: Dust Control Methods for In-situ Nuclear Waste Handling

**Quarterly Technical Progress Report
for Period October 1 through December 31, 1992**

Work Performed Under
Contract No.: DE-FC21-92MC29467

For
U.S. Department of Energy
Office of Fossil Energy
Morgantown Energy Technology Center
P. O. Box 880, Collins Ferry Road
Morgantown, West Virginia

By
Syd S. Peng, Department of Mining Engineering
Felicia F. Peng, Department of Mineral Processing Engineering
West Virginia University
Morgantown, West Virginia 26506

January 1993

TABLE OF CONTENTS

1.0 EXECUTIVE SUMMARY	1
---------------------------------	---

1.0 EXECUTIVE SUMMARY

For this reporting period, our major emphasis was on Task 2, i.e. a survey of existing material handling equipment and techniques used at nuclear waste sites. We have completed reviewing 14 reports dealing with nuclear waste sites, disposal techniques used in handling the various nuclear waste forms, the effect of nuclear waste, as well as the regulations and technology of nuclear waste disposal.

The literature search indicated that there appears to be no report of dust handling problems whatsoever associated with nuclear waste management.

As part of the Task 1 effort, we visited a strip coal mine in Pennsylvania. We noted that activity such as borehole drilling may not be applicable to nuclear waste disposal and thus its excavation-related dust problems may be different. We will therefore select strip mines without surfaces drilling or large construction sites for observation in the second quarter.

We also reviewed the hazardous site report prepared by the Corps of Engineers for the site located near Red House, WV.

Chemical Destruction of Polychlorinated Biphenyls

**Quarterly Technical Progress Report
for Period October 1 through December 31, 1992**

Work Performed Under
Contract No.: DE-FC21-92MC29467

For
U.S. Department of Energy
Office of Fossil Energy
Morgantown Energy Technology Center
P. O. Box 880, Collins Ferry Road
Morgantown, West Virginia

By
Kung K. Wang
Department of Chemistry
West Virginia University
Morgantown, West Virginia 26506

January 1993

ABSTRACT

The general objective of this research is to first evaluate the existing technologies for destruction of polychlorinated biphenyls (PCBs) by chemical methods. Development of new chemical treatment procedures for dechlorination of PCBs will also be a major focus of this research project. The detailed reaction pathway for the dechlorination process will be carefully probed so as to gain fundamental understanding of the reaction mechanism. Such information will be invaluable in providing guidelines for designing an efficient and economical system.

We have contacted two commercial vendors which are involved in chemical dechlorination of PCBs: (1) Chemical Waste Management, Inc. and (2) Trinity Environmental Technologies, Inc. Informations are being collected for technology assessments and economic feasibility studies. Additional commercial vendors will be contacted and various commercial processes will be compared to determine the advantages and disadvantages of these technologies.

A team of one postdoctoral research associate and one graduate student has been formed for this research project. A second graduate student will also join this research team in May of 1993. We are currently devoting our efforts to reviewing literatures, acquiring necessary chemicals and other supplies, and setting up experimental apparatus in the laboratory.

TABLE OF CONTENTS

Section No.	Page No.
1. EXECUTIVE SUMMARY	1

1. EXECUTIVE SUMMARY

It is the objective of this research to evaluate the existing technologies for destruction of polychlorinated biphenyls (PCBs) by chemical methods. We will also focus on establishing chemical treatment procedures for dechlorination of PCBs. We will probe into the detailed reaction mechanisms of various dechlorination processes so as to gain fundamental understanding of the reaction pathway. Such information will provide insight in designing an efficient and economical system.

We have contacted two commercial vendors which are involved in chemical dechlorination of PCBs: (1) Chemical Waste Management, Inc. and (2) Trinity Environmental Technologies, Inc. The Chemical Waste Management, Inc. utilizes a nucleophile-based process that enables the destruction of hazardous halogenated aromatic and/or aliphatic compounds through the successive replacement of one or more halogen atoms with 2-methoxyethoxy moieties. The Trinity Environmental Technology, Inc. utilizes sodium metal as well as ultrasonic irradiation to dechlorinate the PCBs to inert biphenyls and sodium chloride. Informations of these processes are being collected for technology assessments and economic feasibility studies. Additional vendors will be contacted and various commercial processes will be compared to determine the advantages and disadvantages of these technologies.

A team of one postdoctoral research associate and one graduate student has been formed for this research project. A second graduate student will also join this research team in May of 1993. We are currently devoting our efforts to reviewing literatures, acquiring necessary chemicals and other supplies, and setting up experimental apparatus in the laboratory.

**Development of Organic Sensors:
Monolayer and Multilayer Self-Assembled Films for Chemical Sensors**

**Quarterly Technical Progress Report
for Period October 1 through December 31, 1992**

Work Performed Under
Contract No.: DE-FC21-92MC29467

For
U.S. Department of Energy
Office of Fossil Energy
Morgantown Energy Technology Center
P. O. Box 880, Collins Ferry Road
Morgantown, West Virginia

By
Harry O. Finklea
Department of Chemistry
West Virginia University
Morgantown, West Virginia 26506

January 1993

TABLE OF CONTENTS

1.0 EXECUTIVE SUMMARY	1
---------------------------------	---

1.0 EXECUTIVE SUMMARY

Notification of the project was received in early December and as a consequence, efforts have only recently been initiated on the project. To this end, a Research Assistant is being sought to assist in the manpower efforts of the project. The investigator has initiated a literature review and is evaluating various pieces of capital equipment which must be procured to initiate some of the more complex laboratory work.

END

**DATE
FILMED**

5 / 4 / 93