NOTICE

**CERTAIN DATA
CONTAINED IN THIS
DOCUMENT MAY BE
DIFFICULT TO READ
IN MICROFICHE
PRODUCTS.**

DOE/PC/88937-T12(Vol.2)
(DE92014389)

**EXPERIMENTAL STUDIES ON THE GROUP IGNITION OF A CLOUD OF COAL
PARTICLES**

Volume II. Pyrolysis and Ignition Modeling

Final Report for the Period August 15, 1988–October 15, 1991

**By
Kalyan Annamalai
William Ryan**

January 1992

Work Performed Under Contract No. FG22-88PC88937

**For
U.S. Department of Energy
Pittsburgh Energy Technology Center
Pittsburgh, Pennsylvania**

**By
Texas A&M University
College Station, Texas**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615)576-8401, ~~1-800-553-6111~~.

Available to the public from the National Technical Information Service, U. S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

EXPERIMENTAL STUDIES ON THE GROUP IGNITION OF A CLOUD OF COAL PARTICLES

DOE/PC/88937--T12-Vol.2

DE92 014389

VOLUME II. PYROLYSIS AND IGNITION MODELING

by

Kalyan Annamalai
William Ryan

Final Report
(August 15, 1988 to October 15, 1991)
Grant No. DE-FG22-88PC88937

January 1992

Prepared for the
U.S. Department of Energy
Pittsburgh Energy Technology Center
P.O. Box 10940
Pittsburgh, PA 15236

ABSTRACT

Vol. I Experimental Results

A laminar flow reactor facility has been constructed, tested, and used to obtain a detailed set of data on ignition time and ignition temperature of streams of coal particles. Coal dusts of average particle diameters 39, 64 and 90 μm were fed into the reactor using a newly developed locally fluidized feeder (LFF) which is capable of delivering mass flow rates from 0.2 to 50 g/min.

Coal streams were injected into the vitiated ambience inside the reactor where the oxygen concentration was 10%. A zirconium dioxide oxygen analyzer was used to monitor the oxygen partial pressure. The vitiated gas temperatures ranged from 1023 to 1150 K. Coal mass flow rates were directly measured by weighing the hopper.

The location of the flame was observed and photographed through a pair of 38-cm (15-in) long, 19 mm (3/4 in) wide quartz windows located diametrically opposite of each other in the walls of the reactor unit. From the knowledge of the ignition distances and the velocity of the gases, ignition times were estimated.

Ignition temperatures were measured for flow rates ranging from dilute to rich coal streams (overall equivalence ratio of 0.1 to 2.5). The criterion used for the onset of ignition was the presence of smoke out of the exhaust duct of the reactor. The ignition temperature was defined as the minimum secondary stream temperature above which a specific coal stream ignited.

A brief summary of the results follows:

i) Ignition times show a minimum as the mass flow rate of coal was gradually increased from the dilute condition to dense flow condition. These findings qualitatively confirm the results from group ignition theory. The overall equivalence ratio at minimum ignition time was found to be less than 0.5 for all the cases studied. Ignition times ranged from 17 to 21 ms for particle sizes 39 and 64 μm and from 21 to 30 ms for the largest particle cloud.

ii) Ignition times decrease with increasing gas temperatures.

iii) Ignition times increase with particle size at the same mass flow rate.

iv) Ignition temperatures of very dilute streams were found to be higher than those for denser streams. Ignition was not possible for temperatures below 775 K for any coal mass flow rate.

v) Ignition temperatures are lower for larger particles for the dilute streams.

vi) The results on ignition are not very sensitive to the change in oxygen concentration.

vii) An optical technique has been developed to measure the transit times directly.

The results confirm the overall trends predicted by the group ignition theory of Ryan and Annamalai (1991).

ABSTRACT

Vol. II Pyrolysis and Ignition Modelling

Most of the fundamental pyrolysis, ignition and combustion experiments use either a batch or stream of coal parties and most practical uses of pulverized coal involve very dense clouds due to the good flame stability and high throughput. Despite this fact, most theoretical models used to interpret the experimental data have been based on the individual particle combustion model (IPC). As opposed to the IPC model, a group combustion theory (GC) is now emerging for the combustion modeling of a dense cloud of particles.

Group behavior implies the formation of a single flame around a large number of drops/particles rather than a flame around each individual drop/particle.

Earlier work has been done on the group combustion modeling of a cloud of drops and char particles. No such modeling has been conducted for a cloud of coal particles.

The primary objectives of this work are to formulate a model to simulate transient coal pyrolysis, ignition, and combustion of a cloud of coal particles and to compare results of the program with those reported in the literature elsewhere.

The present work is reported in the following order. An introduction to group combustion (GC) is given followed by a review of earlier works. Next, the relevance of the present work to practical application and spray combustion modeling is discussed. A group combustion model is then presented for a spherical cloud of coal particles along with a set of dimensional and nondimensional equations. Finally, nonsteady results are generated for pyrolysis, ignition, and combustion of a cloud of coal particles.

A brief summary of the results is as follows:

- (i.) Pyrolysis yields are lower for dense clouds (such as the clouds used in the ASTM test procedure) and higher for dilute clouds (such as those used in suspension experiments). The free stream temperature does not affect yields significantly for large particle sizes.
- (ii.) Small injector radii are desirable in most practical applications since this greatly reduces the mixing time resulting in high particle heating rates and thus, enhanced volatile yields and decreased char yields.
- (iii.) Refractory walls (i.e. high temperature, not water-cooled) provide a radiative environment which results in enhanced volatile yields.
- (iv.) Ignition is homogeneous for dense clouds and is heterogeneous for dilute clouds. Ignition time shows a minimum at a particular mass loading.
- (v.) Once the coal dust cloud is ignited, a detached flame due to volatiles oxidation is formed surrounding the cloud and the flame moves towards the cloud as the volatiles are depleted.

A two part comprehensive review paper has been written on the interactive processes in droplet and particle combustion.

TABLE OF CONTENTS

CHAPTER	Page
I . INTRODUCTION	1
1.1. Difference Between Coal and Droplet Combustion	1
1.2. Group Combustion	4
1.3. Scope of the Present Work	7
II . LITERATURE REVIEW	8
2.1. Group Combustion and Terminology	8
2.1.1. Individual Particle/Drop Combustion (IPC)	8
2.1.2. Incipient Group Combustion (IGC)	12
2.1.3. Partial Group Combustion (PGC)	12
2.1.4. Critical Group Combustion (CGC)	12
2.1.5. Total Group Combustion or Group Combustion (GC)	12
2.1.6. Sheath Combustion (SC)	12
2.2. Group Combustion of Liquid Drops	13
2.3. Pyrolysis of Coal Particles	19
2.4. Ignition of Coal Particles	23
2.5. Combustion of Coal Particles	25
2.6. Relevance	25
III . OBJECTIVES	32
IV . THE MODEL AND CONSERVATION EQUATIONS	33
4.1. Model for Transient Combustion	33
4.2. Assumptions	36
4.3. Dimensional Form of Conservation Equations	40

CHAPTER	Page
4.3.1. Gas phase conservation equations	40
4.3.1.1. Mass	40
4.3.1.2. Species	40
4.3.1.3. Energy	43
4.3.2. Solid Phase Equations	45
4.3.2.1. Mass	45
4.3.2.1.1. Mass loss rate due to pyrolysis	47
4.3.2.1.2. Mass loss rate due to heterogeneous reactions	50
4.3.2.2. Diameter of the particle (d_p)	52
4.3.2.3. Density of the particle (ρ_p)	53
4.3.2.4. Particle temperature (T_p)	53
4.3.2.5. Mass, species, and heat sources	56
4.3.2.5.1. Mass source ($\dot{w}_m'''$)	56
4.3.2.5.2. Species source ($\dot{w}_k'''$)	57
4.3.2.5.3. Heat source ($\dot{w}_h'''$)	58
4.3.3. Initial and boundary conditions	58
4.4. Nondimensional Form of Conservation Equations	60
4.4.1. Reference quantities	60
4.4.2. Nondimensional variables	60
4.4.3. Gas phase conservation equations	62
4.4.3.1. Mass	62
4.4.3.2. Species	63
4.4.3.3. Energy	63

CHAPTER	Page
4.4.4. Solid phase equations	63
4.4.4.1. Mass	63
4.4.4.2. Diameter	65
4.4.4.3. Density	65
4.4.4.4. Temperature	65
4.4.5. Initial and boundary conditions	65
4.4.5.1. Gas Phase	65
4.4.5.2. Particle	66
V . NUMERICAL METHOD FOR TRANSIENT COMBUSTION	67
5.1. Numerical Method	67
5.2. Numerical Scheme	68
5.3. Input Data	69
VI . RESULTS AND DISCUSSION	77
6.1. Group Combustion Number G	79
6.2. Pyrolysis of Coal Particles	82
6.2.1. No Radiation	83
6.2.1.1. Pyrolysis Results for an Initially Cold Cloud	83
6.2.1.2. Pyrolysis Results for an Initially Hot Cloud	89
6.2.2. Effects of Radiation	95
6.2.2.1. Initially Cold Cloud and Ambience	95
6.3. Ignition of Coal Particles	104
6.3.1. No Radiation	107
6.3.1.1. Ignition Results for an Initially Cold Cloud	107
6.3.1.2. Ignition Results for an Initially Hot Cloud	136

CHAPTER	Page
6.3.2. Effects of Radiation	137
6.4. Combustion	141
VII . SUMMARY OF RESULTS	147
REFERENCES.....	150
APPENDIX A. DESCRIPTION OF NUMERICAL SCHEME	157
APPENDIX B. NUMERICAL CODE	162

LIST OF FIGURES

Figure	Page
1.1. Difference between Oil and Coal Combustion	3
1.2. Individual Particle Combustion and Group Combustion	5
2.1. Group Combustion Studies	9
2.2. Group Combustion Modes and Terminology	10
2.3. Variation of Correction Factor with G-number	17
2.4. Illustration of Group Combustion for a Cloud of Char Particles	18
2.5. Schematic of a Wall Burner Using Pf Spray	26
2.6. Laminar Flow Reactor	28
2.7. Particle Source in Cell	30
4.1. Group Combustion Model for a Spherical Cloud of Coal Particles	34
4.2. Illustration of Point Source Assumption	37
4.3. Illustration of Energy Balance	44
4.4. Schematic of Transport Processes	46
6.1. Temperature and Volatile Concentration Profiles	78
6.2. Typical Temperature, Density and Volatile Profiles for Pyrolysis	85
6.3. Volatile Yield Time Histories	87
6.4. Pyrolysis Propagation Rate	88
6.5a. Effect of Cloud Radius on Volatile Yield	90
6.5b. Volatile Yield Time Histories for Various Cloud Radii ($G = 100$)	91
6.5c. Volatile Yield Time Histories for Various Cloud Radii ($G = 1$)	92
6.6. Effect of Particle Diameter on Volatile Yield	93
6.7. Effect of G-number on Volatile Yield for Various Free Stream Temperatures	94
6.8. Effect of Particle Diameter on Volatile Yield, Constant G-number	97

Figure	Page
6.9. Effect of Particle Diameter on Volatile Yield, Constant Fuel Volume Fraction	98
6.10. Effect of Particle Diameter on Volatile Yield, Constant Particle Surface Area	99
6.11. Effect of Particle Diameter on Volatile Yield, Cloud Radius Dependence	101
6.12. Effect of Radiative Temperature on Volatile Yield	102
6.13. Effect of Particle Diameter on Volatile Yield	103
6.14. Kobayashi's [1972] Experimental Data	105
6.15. Steady State Solutions for the Ignition of a Particle	109
6.16. Illustration of Ignition Criteria	111
6.17. Temperature Profiles for Ignition	112
6.18. Gas Phase Mass Fractions	113
6.19. Effect of G-number on Ignition for the Base Case	115
6.20a. Effect of G-number on Ignition Time for Various Ambient Temperatures	117
6.20b. Effect of Ambient Temperature on Ignition Time for Various G-numbers	118
6.20c. Variation of Ignition Time with Reciprocal Temperature	119
6.21. Effect of Proximate Volatile Matter on Ignition Time	122
6.22. Effect of Initial Cloud O ₂ Concentration on Ignition Time	123
6.23. Effect of Increased Pulverization on Ignition Time	124
6.24a. Effect of Particle Diameter on Ignition Time ($\sigma = 8.33 \times 10^{-6}$)	126
6.24b. Effect of Particle Diameter on Ignition Time ($\sigma = 8.33 \times 10^{-4}$)	127
6.25. Effect of Cloud Radius on Ignition Time	129
6.26. Relation Between Outer Particle Density and Ignition Mode	131
6.27. Effect of Altering Char Oxidation Kinetics on Ignition Time	132
6.28a. Effect of Altering Pyrolysis Kinetics on Ignition Time	134

Figure	Page
6.28b. Effect of Altering Gas Phase Kinetics on Ignition Time.....	135
6.29. Effect of G-number on Ignition Time (Hot Cloud).....	138
6.30. Comparison of Ignition Criteria	139
6.31. Effect of Radiative Temperature on Ignition Time	140
6.32. Flame Structure ($\xi_f \rightarrow \text{minimum}$).....	144
6.33. Flame Structure ($\xi_f = 1$).....	145
6.34. Flame Location Time History	146
A.1 Flow Chart	158

LIST OF TABLES

Table	Page
1.1 1986 Energy Demand and Supply.....	2
4.1 Time Scales for Group Combustion of Coal Particles.....	39
4.2 Conserved Quantity ψ for Various Conservation Equations.....	64
5.1 Input for Transient Results.....	73
6.1 G Number Definitions in Various Forms.....	80
A.1 Description of Subroutines.....	159

CHAPTER I

INTRODUCTION

Combustion of fossil fuels provides a large portion of the electric power generation in North America. Table 1.1 shows the 1986 energy demand and supply. Due to the desirable high intensity combustion characteristics and high throughput, most of the industrial oil spray burners and coal fired utility boilers use very dense clouds of drops/particles. Extensive experiments have been conducted in order to obtain the combustion characteristics coal/oil sprays. Invariably, these results have been interpreted using an Individual Particle Combustion (IPC) model. However, sprays consist of a large number of interacting drops/particles. Thus, the concept of Group Combustion (GC) or interactive combustion modeling is most useful in modeling liquid and coal spray combustion. In the present work, a group combustion model for pulverized coal has been proposed which accounts for particle interactions within the cloud. This is expected to lead to improvements in the understanding of the processes involved in pulverized coal combustion and the interpretation of experimental data.

1.1. Difference Between Coal and Droplet Combustion

It is important to realize the differences in the processes involved in the combustion of oil drops and the combustion of coal particles. An oil drop completely vaporizes on heating and the gasification is purely a physical process. The coal particle, on the other hand, *partially* pyrolyses (decomposes) on heating releasing gases and thus gasification is a chemical process. Considering a single oil drop placed in a hot furnace (Fig 1.1), the heat wave propagates to the

This document follows the style of the ASME Journal of Heat Transfer.

Table 1.1 1986 Energy Demand and Supply

Source GRI: Steve Friedman

<u>Supply (Quads)</u>		<u>Demand (Quads)</u>	
Petroleum		Petroleum	32
Domestic	22		
Imported	10		
Natural Gas		Natural Gas	17
Domestic	16		
Imported	1		
Coal		Coal	17
Domestic	19		
Exported	2		
Nuclear	5	Nuclear	5
Hydro	<u>6</u>	Hydro	<u>6</u>
	77		77

Energy Use

Residential	20
Commercial	6
Industrial	22
Transport	20
Losses	<u>19</u>
	77

1Quad = 10^{15} Btu (thousand trillion)

Oil Drop Combustion

Coal Particle Combustion

Figure 1.1. Difference between Oil and Coal Combustion

drop and heats up the oil drop. Vapors coming out of the oil drop start moving out into the surrounding atmosphere. They mix with oxygen in the atmosphere and establish a diffusion flame, away from the droplet surface. This flame is fed by the fuel vapors from the oil drop and oxygen from the ambience. In the case of a coal particle, the combustion process is different. When a coal particle is placed in a hot furnace, it undergoes pyrolysis and CO, CO₂, CH₄, C₂H₂, etc. are released. The volatiles diffuse into the surrounding atmosphere where they mix with oxygen to establish a flame. After the volatiles are exhausted, only char (carbon and hydrogen in small amounts) is left behind. The flame established by the volatiles extinguishes and oxygen diffuses to the char surface and reacts to form carbon monoxide and carbon dioxide. The CO₂ and CO formed diffuse out towards ambience. Due to the high temperatures prevailing in the gas phase near the char particle, the carbon monoxide reacts with the oxygen in the gas phase to produce a faint blue color flame. Individual particle ignition and combustion studies have been conducted by various workers. Theoretical results were obtained for the individual particle combustion rate ($\dot{m}_{s,\infty}$) and for the temperature required to ignite the particle. The results of these studies were correlated with experimental results obtained from individual particle experiments.

1.2. Group Combustion

Interpretation of experimental data using clouds of drops/particles and the modelling of most practical burner systems needs a better model than the individual particle combustion model. The basic elements of group combustion and its rise to importance can be easily explained with the help of Fig. 1.2. As shown in Fig. 1.2, a single oil droplet placed in a hot furnace is being considered. The drop gets heated and vapors come off the drop. These fuel vapors react with

Group Combustion

Oil Drop/Particle
($d_p \approx 50 \mu\text{m}$)

Individual Particle (drop)
Combustion, IPC

Burning Rate: $\dot{m}_{s,\infty}$

A Spherical Cloud

A Group of
Particles/Drops

Group Combustion, GC

$$\dot{m}_{s,c} = \frac{\dot{m}_{tot}}{\text{Total number of drops}}$$

Figure 1.2. Individual Particle Combustion and Group Combustion

oxygen in the atmosphere and establish a flame, provided the temperature of the furnace is hot enough. This flame stands outside the drop, fueled by vapors from the droplet surface and also by the oxygen from ambience. So we can see a single flame established around the drop and the burning rate of the drop can be calculated. Let this burning rate be $\dot{m}_{s,\infty}$. The subscript ' ∞ ' represents a particle in an infinite atmosphere.

On the other hand, consider a collection of drops contained in an imaginary spherical enclosure (Fig. 1.2). We can call this a cloud of drops. Introducing this cloud of drops into a hot furnace, we can see that the heat propagates into the cold cloud raising the temperatures of the gases and drops inside the cloud. When the temperature of the drops has reached the boiling point, vapors are released from the drop surface. These vapors tend to move towards ambience due to the density gradient of the fuel vapor concentration. The oxygen in the ambience, in turn, moves towards the cloud where the oxygen concentration is lower. The vapors coming out of the cloud react with oxygen in the ambient atmosphere. It is more likely that there exists a single flame around the whole cloud, instead of a flame being established around every drop in the cloud. This flame is fueled by the vapors released by each drop in the cloud and oxygen from the ambience. This process where the drops act as a group and sustain combustion is conventionally called group combustion. Previously, group combustion studies have been carried out on a cloud of liquid drops and char particles. However, there exists no model for a cloud of coal particles which deals with group pyrolysis, ignition, and combustion. Under such conditions, the average burning rate of a single in the cloud ($\dot{m}_{s,c}$) is lower than the burning rate of a similar isolated particle. A basic understanding of group combustion and the parameters which control group combustion is expected to result in the better

design of burners. Group combustion studies have been conducted for a cloud of liquid drops and char particles. However, there exists no prior literature on the group combustion of coal particles.

1.3. Scope of the Present Work

The present work deals with transient group combustion studies of a cloud of coal particles. The effects of group behavior on volatile yield, ignition, and combustion are presented. Relevance to spray combustion modeling, combustion in practical burners and laminar flow reactor experiments is also discussed.

CHAPTER II

LITERATURE REVIEW

This chapter includes definitions for various types of group combustion followed by a summary of the early literature on the group combustion of liquid drops. Following is a review of the experimental literature on the pyrolysis, ignition, and combustion of pulverized coal. Finally, the relevance of group combustion studies to practical systems is discussed.

2.1. Group Combustion and Terminology

Group combustion implies the formation of a common flame around a large number of drops/particles rather than a flame around each individual drop/particle. In broader terms, such a behavior could also be interpreted as the change in burning characteristics due to the collective behavior of a cloud of particles. Figure 2.1 illustrates the classification of group combustion studies. For simplicity most of these models involve the analyses on a spherically symmetric cloud of drops burning in quiescent air. Prior to detailed discussions of the literature review, a brief description of terminology is appropriate. For simplicity, this description refers to a cloud of drops rather than a cloud of coal particles.

2.1.1. Individual Particle/Drop Combustion (IPC)

In this mode all the drops in the cloud burn with an individual flame around each droplet (Figure 2.2a).

a.) Single Droplet

b.) Two Droplets

c.) Five Droplets

d.) Nine Droplets

e.) Monosized Stream

f.) A Cloud of Drops

Figure 2.1. Group Combustion Studies

a.) Individual
Particle
Combustion
(IPC)

b.) Incipient
Group
Combustion
(IGC)

c.) Partial
Group
Combustion
(PGC)

Figure 2.2. Group Combustion Modes and Terminology

d.) Critical
Group
Combustion
(CGC)

e.) Group
Combustion
(GC)

f.) Sheath
Combustion
(SC)

Figure 2.2 (Continued)

2.1.2. Incipient Group Combustion (IGC)

As the number of drops per unit volume (n) is increased, the outer drops burn in IPC mode consuming oxygen. The inner drops, surrounded with a lower oxygen concentration attain, large flame radii. A condition is reached at which the flame radii of the center drops just touch each other. Group combustion at this condition is called IGC (Figure 2.2b).

2.1.3. Partial Group Combustion (PGC)

As n is further increased, the outer drops consume all the oxygens and the inner drops, starved of oxygen, simply evaporate and the vapors from the inner drops diffuse outward and establish a group flame inside the cloud. While there is a group flame for the inner drops, the outer drops burn individually. Thus the cloud burns under PGC mode (Figure 2.2c).

2.1.4. Critical Group Combustion (CGC)

As n is further increased, the evaporation rate or the blowing rate of vapors is such that the oxygens can't penetrate into the cloud and the flame just stands at the cloud surface. The bulk gas temperature at the cloud surface (T_c) is exactly the same as the flame temperature (T_f) (Figure 2.2d).

2.1.5. Total Group Combustion or Group Combustion (GC)

If n is increased further, the blowing rate of vapors prevent the oxygens from penetrating into the cloud and a flame is established outside the cloud. The drops are at the wet bulb temperature* while T_c is between T_{wb} and T_f (Figure 2.2e).

* This term is commonly used in combustion literature to denote the saturation temperature at the partial pressure of vapors

2.1.6. Sheath Combustion (SC)

As n is increased to a large value the flame stands farther away from the cloud surface. Hence T_c decreases and eventually with a further increase in n a condition is reached where $T_c = T_{wb}$. The whole cloud behaves like an equivalent single drop of radius R_c with the equivalent drop density being equal to the cloud density. Combustion under this condition is called sheath combustion (Fig. 2.2f).

2.2. Group Combustion of Liquid Drops

The earliest work on group combustion was conducted by Suzuki and Chiu [1971]. They obtained group combustion results for a spherical cloud of liquid propellants. Later Labowsky and Rosner [1978] obtained a criteria for incipient group combustion in terms of Thiele Modulus (ψ_T) by using the analogy of a porous char combustion to the group combustion of a cloud of droplets. Chiu and Liu [1977] used a quasi-steady (QS) model for spherical, cylindrical, and planar clouds of droplets and a perturbation method to obtain a power series solution for the total group combustion rate and flame location.

The group combustion number, G , introduced by Chiu and Liu can be simply defined as,

$$G = 3 (\text{Fuel Volume Fraction}) \left(\frac{\text{Cloud Radius}}{\text{Droplet Radius}} \right)^2 \quad (2.1)$$

(The G number of Chiu and Liu is the same as the square of Thiele Modulus defined by Labowsky and Rosner). If the G number exceeds a critical value G_c at which there is critical group combustion, then the flame stands outside the cloud and if $G < G_c$, then there "may be" burning of individual droplets inside the cloud. McGrath and Chigier [1973] conducted different experimental studies on

liquid fuel sprays. The common observation among these experiments was the detection of a sheath flame around the outer periphery of the liquid spray which confirms the group combustion theory. Even combustion studies on a monosized stream of liquid drops reveal a sheath flame [Nuruzzaman et al., 1971]. Further, if the diameter of the droplet is very small, the establishment of the flame around a droplet may not be possible [Annamalai and Dubertaki, 1975], which may lead to group combustion.

Correa and Sichel [1982; 1983] used a matched asymptotic technique to get the propagation rate of a vaporization wave for a very dense cloud. Bellan et al. [1983] used the "bubble" model to investigate the evaporation of a cloud of drops enclosed in an adiabatic vessel. The drops are instantaneously injected into the adiabatic vessel filled with hot gases and evaporation continues until the vessel is saturated. These studies are essentially interaction studies. These studies are useful in interpreting the behavior of drops in the core of a spray.

Drop array studies have been conducted by Labowsky, [Evaporation: 1976; 1978; 1980 Combustion: 1980] Correction factors have been presented as a function of the number of drops, and the interdrop spacing. While array studies deal with a finite number of drops, group theory concerns itself with clouds whose particle number densities are on the order of 1.0×10^6 to 1.0×10^9 particlesperm³. Comparisons between the array studies and the group studies will be presented later.

Chiu and Kim [1983] published a model which was more or less a combination of the Chiu and Liu model [1977] and the Labowsky and Rosner [1978] model. They assumed partial group combustion with the drops in the outer layers burning individually, while the drops inside the cloud evaporate.

The QS formulation by Sichel and Palaniswamy [1984] for the ignition and extinction included a sheath combustion criteria in terms of vaporization wave

thickness ratio (ϵ), where $\epsilon \simeq \frac{1}{G}$. They provided explicit results for ignition, extinction, and cloud burning time evaluation, but there was no direct correlation with experimental data. Universal plots of the quasi-steady explicit results for evaporation, combustion, and flame structure were presented. Considering a cloud of dodecane drops, Annamalai et al. [1984] accounted for chemical reaction both in the cloud and outside the cloud and obtained numerical results for the ignition temperature of the cloud. The QS ignition analysis of a cloud of drops shows that the ignition temperature decreases with decreasing droplet size while a QS ignition analysis of a single droplet/particle shows an increase in ignition temperature with a decrease in droplet/particle size [Annamalai, 1979].

It is found from a group combustion analysis that the burning rate of a typical cloud of drops can be as low as 10% of the burning rate obtained with an individual droplet combustion model. Annamalai [1985c] compared the group burning rate to the sum of individual drop burning rate at various G-numbers and found that for $G < 0.3$, the results for the group burning rate are 90% of the rate predicted with the individual particle combustion model.

The term "Group Combustion" as defined so far implies the formation of a "group flame". More generally, group combustion is a result of drop interactions with or without the formation of a group flame. Annamalai [1984b] considered the group combustion of a cloud of drops as well as the group evaporation of a cloud of drops. As long as the mass fraction of O_2 is negligible at the cloud surface, the mass burning rate of a cloud with finite gas phase chemistry and infinite chemistry are identical. He has compared the results for $\dot{m}_{IPC}$ (the cloud burning rate assuming all particles in the cloud burn in the IPC mode), with the results for $\dot{m}_c$ (the cloud burning rate determined by the group combustion model) and defined the following correction factor.

$$CF = \frac{\dot{m}_{s,c}}{\dot{m}_{s,\infty}} = \frac{\text{average burning rate of a drop in the cloud}}{\text{burning rate of a single isolated drop}} \quad (2.2)$$

The results for CF have been obtained as a function of the G-number. Figure 2.3 shows the results for correction factor. The figure has been shown to be valid for the following conditions

- (i) Pure evaporation (without combustion)
- (ii) Combustion with finite chemistry as long as the oxygen mass fraction at each drop surface is negligible.
- (iii) Combustion with the thin flame model (i.e. a group flame outside the cloud).

As seen in figure 2.3, if the cloud is dilute ($G < 0.3$), the correction factor to the individual combustion model approaches 1.0. For a dense cloud ($G > 100$), the correction factor is less than 0.1. The review so far has concerned itself primarily with the group combustion studies based on liquid drops. The literature for the group combustion of coal particles is almost non-existent. Annamalai and Ramalingam [1987] formulated a QS group combustion model for a cloud of char particles. The group combustion of char particles can be illustrated with the aid of figure 2.4. Comparing figures 2.2 and 2.4, it is apparent that there is an analogy between group combustion of a cloud of char particles and a cloud of liquid drops. Thus figure 2.3 is also valid for cloud of char particles burning under the following conditions.

- (i) Combustion of char particles with a frozen gas phase chemistry.
- (ii) Combustion of char particles with finite gas phase chemistry as long as the O_2 and CO_2 mass fractions at each particle surface are negligible.
- (iii) Combustion of char particles with infinite gas phase chemistry.

While analytical studies on auto ignition of a dust cloud of char/carbon particles have been conducted by Rumanov and Khalkin [1969] and Krishna

Figure 2.3. Variation of Correction Factor with G-number

Figure 2.4. Illustration of Group Combustion for a Cloud of Char Particles

and Berlad [1980] using the steady state thermal theory of ignition and assuming uniform properties throughout the cloud, there is no prior literature on the group ignition and combustion of a cloud of coal particles. Ramalingam conducted preliminary group ignition studies for a cloud of char particles and found that ignition temperature is lower for a cloud than for a single char particle [1988]. As previously mentioned, the gasification of drops is total and is purely a physical process and ignition is homogeneous. On the other hand, the ignition of a cloud of char particles is heterogeneous. However, the ignition of a cloud of coal particles is somewhat complex in that the gasification of coal is partial and is a chemical decomposition process. Thus ignition can be due to heterogeneous reactions or due to homogeneous ignition of a mixture of volatiles and oxygen in the gas phase.

2.3. Pyrolysis of Coal Particles

Pyrolysis of coal refers to the evolution of gases from a particle upon heating. When pyrolysis is complete the change in mass divided by the original mass is termed the volatile yield of the particle. Traditionally, volatile yield has been determined by the ASTM method. This involves putting a 1 gm. sample in a platinum crucible and placing it in an oven for 7 minutes. The sample is then removed and weighed. The resulting volatile yield has been termed proximate volatile matter. The ratio of volatile yield to proximate volatile matter is termed Q and is in the range $1 < Q < 2$.

More recently researchers have found that high temperatures accompanied by high heating rates result in volatile yields greatly exceeding those obtained using the traditional ASTM-D3175 method. Although some of these studies are conducted in a oxidizing atmosphere, the majority are conducted in an inert atmosphere in order to avoid uncertainty resulting from the mass loss due to

pyrolysis and mass loss occurring due to heterogeneous reactions. Several different types of experimental apparatus are used to achieve the high temperatures and heating rates required to achieve enhanced volatile yield. These are

- (1.) Continuous Flow Reactors: In these experiments the particles are carried to the reactor in a cold primary gas flow. This flow is introduced into a hot secondary gas flow resulting in high heating rates. Thus the temperature history of the particles is highly dependent on the heat and mass transport characteristics of the entraining medium. Typical heating rates of 10^5 K/s are obtained. Laminar flow reactors fall into this category and since the flow is laminar these experiments most closely resemble a cylindrical cloud of coal particles introduced into a hot atmosphere [R. Eddinger et al., 1966; G. Kimber and M. Gray, 1967; S. Badzioch and G. Hawksley, 1970; D. Stickler et al., 1974; S. Ubhayakar et al., 1977; P. Solomon et al., 1982; C. Tsai and A. Scaroni, 1984; D. Maloney and R. Jenkins, 1984; A. Jamaluddin et al., 1986].

As opposed to continuous flow reactor studies, batch studies in which a small sample of coal is pulverized have also been conducted. These studies include the following

- (A.) Heated Grids: These experiments consist of layering a thin sample of pulverized coal on a screen which is then folded over and placed between two electrodes. Current is then passed through the screen and resistive heating is responsible for heating the particles. Typical heating rates of 10^4 K are obtained [D. Anthony et al., 1975; D. Anthony et al., 1976; E. Suuberg et al., 1978; P. Solomon, 1980; S. Niksa et al., 1984; A. Jamaluddin et al., 1986].
- (B.) Heating with Lasers: These experiments consist of sealing a small sample of coal in a glass container and irradiating the sample with a high energy

focused laser beam. Heating rates of up to 10^6 K can be obtained by such a procedure [N. Gat, et al., 1983].

- (C.) Explosion Chambers: In these experiments, a closed reactor is charged with a stoichiometric oxygen/hydrogen mixture. A batch of coal particles is then blown into the reactor. The oxygen/hydrogen mixture is then ignited and burnt filling the volume with high temperature gases. Thus, heating rates of the particles is extremely high. [D. Northam and C. von Rosenberg Jr., 1979].

A summary of the conclusions drawn from these studies is given below.

- i.) Generally volatile yields are greater for higher heating rates accompanied by higher temperatures [Kimber and Gray, 1967; Badzoich and Hawksley, 1970; Anthony et al., 1976; Niksa et al., 1984]
- ii.) When helium is used as the primary gas in laminar flow reactors, volatile yields increase due to the low heat capacity and high conductivity of helium [Eddinger et al., 1966; Maloney and Jenkins, 1984; Jamaluddin et al., 1986].
- iii.) In laminar flow reactors the heating rate of the particle is controlled by the heating rate of the carrier gas, thus decreasing the particle diameter does not result in an increase in volatile yield. However, in reactors where the mixing is enhanced, decreasing the particle diameter results in increased volatile yield [Anthony et al., 1976; Tsai and Scaroni, 1984].
- iv.) Even under the most rapid heating rates, significant devolatilization occurs during the heat-up period [Anthony et al., 1975; Maloney and Jenkins, 1984].
- v.) Values of Q vary between 1 (proximate yield) to 2 for extremely rapid pyrolysis of pulverized coal [Kimber and Gray, 1967; Badzoich and Hawksley, 1970].

- vi.) Pyrolysis seems to be solely a thermal process, since models developed based on an inert atmosphere are equally valid for an oxidizing environment [Stickler et al., 1974].
- vii.) Since the time to complete pyrolysis and burn released volatiles is short compared to the time required for char burnout in most practical systems, it is desirable to have rapid and extensive devolatilization in order to minimize char production and to decrease combustion time [Tsai and Scaroni, 1984].
- viii.) In the heated grid studies, it was found that volatile yield for bituminous coal increased with decreasing pressure. For lignites, volatile yield shows no pressure dependence. This will not be the case for laminar flow reactors since decreasing the pressure will severely hinder the heat transfer rate between the secondary and primary gas and between the primary gas and the particles [Anthony et al., 1975; Suuberg et al., 1978; Niksa et al., 1984].
- ix.) Devolatilizing in a hydrogen atmosphere results in increased volatile yields [Anthony et al., 1976].
- x.) Competing reaction and multiple parallel models have been shown to adequately describe devolatilization. According to the competing reaction model, two pyrolysis mechanisms seem to dominate pyrolysis. One which is dominant at low temperatures and one which becomes dominant at higher temperatures ($\approx 1300\text{K}$). The high temperature mechanism yields volatiles with a lower (H/C) ratio than the low temperature mechanism [Ubhayakar, 1977; Horton, 1978]. Thus
 - a.) Higher final temperatures result in increased yields. This results since the higher the temperature, the less residual volatile matter in the coal once pyrolysis is complete [Anthony and Howard, 1967].
 - b.) Higher heating rates result in increased yields. The higher the heating rate, the shorter the time to reach the high yield mechanism, thus

limiting the coal hydrogen and oxygen content depleted due to the low yield route.

The parallel reaction model assumes a large number of reactions having the same preexponential factor, and activation energies given by a Gaussian distribution function. As the name suggests the reactions proceed in parallel. The mass loss rate is given as

$$\frac{\dot{m}_v}{m_{c,0}} = V^{**} \left(\int_0^\infty \left[\exp \left(- \int_0^t k \, dt \right) \right] f(E) \, dE \right) \quad (2.3a)$$

where

$m_{c,0}$ is the initial mass of a coal particle,

$$f(E) = \left[\sigma (2\pi)^{1/2} \right]^{-1} \exp \left[- (E - E_0)^2 / 2\sigma_v^2 \right] \quad (2.3b)$$

, and

V^{**} is the ultimate volatile yield.

$$k = B_v \exp(-E/RT_p) \quad (2.3c)$$

The typical values of B , E_0 , and σ_v are $1.07 \times 10^{10} \, \text{s}^{-1}$, $230,000 \, \text{kJ/K mole}$, and $72,000 \, \text{kJ/K mole}$ for Pittsburgh seam coal [Anthony et al., 1976].

2.4. Ignition of Coal Particles

Once the volatiles are released they undergo gas phase oxidation. Ignition of a cloud of coal particles has been known to occur by two modes. The first mode, heterogeneous ignition, refers to ignition of the carbon and in-situ volatile matter at the surface of the coal particle. The other mode, homogeneous ignition, occurs when volatiles in the gas phase ignite. Single particle studies show that heterogeneous ignition normally occurs for smaller sized particles while homogeneous ignition occurs for larger sized particles. While single particle studies may be useful for the study of ignition and combustion of dilute

sprays, its application is limited since most industrial spray burners use very dense clouds. Furthermore, ignition occurs in the vicinity of the burner where the cloud is dense. Thus group ignition studies are more appropriate. Not only are ignition studies important in the design and understanding of the processes involved in practical burners, these studies are useful in the prevention of dust cloud explosions.

The experimental apparatus and conditions for conducting pulverized coal ignition studies are described briefly:

- (1.) Transport Reactors: In these experiments, coal is fed into an oxidizing atmosphere and the distance the coal travels in the reactor divided by the entrainment air velocity is defined as the ignition time [H. Cassel and I. Liebman, 1959; W. McLean, 1982; C. Tsai and A. Scaroni, 1984;].
- (2.) Drop Tube Furnaces: In these experiments, a small sample of coal is suspended in an oxidizing atmosphere and the temperature of the entraining air is varied until ignition occurs [K. Cashdollar and M. Hertzberg, 1983].
- (3.) Shock tubes: In these experiments, a small sample of coal is suspended in a shock tube. A shock wave is then passed over the coal particles which are then suspended in the hot shock treated air [W. Seeker et al., 1979].

The results of these studies are:

- i.) Minimum ignition temperatures for isolated particles increase as the particle radius is decreased. However, in large concentrations, ignition temperatures for small particle clouds are less than for relatively large particle clouds. Also, the ignition temperature of a cloud of particles may be less than that of the corresponding single particle due to particle interactions [Chen et al., 1984; Ramamlingam, 1988].
- ii.) Increasing particle diameter results in larger ignition times [Seeker et al., 1979].

- iii.) The use of helium as the primary entraining gas in transport reactors decreases ignition time due to the desirable heat transfer characteristics of helium [Maloney and Jenkins, 1984].

2.5. Combustion of Coal Particles

As mentioned previously, two types of ignition (heterogeneous and homogeneous) can occur. If heterogeneous ignition occurs, then combustion ensues and the carbon matter in the coal particles continue to burn along with the volatiles in-situ. The increased coal particle temperature then results in a rapid rise in the particle temperature which results in intensive pyrolysis. The blowing of pyrolysate reduces the oxygen concentration surrounding the coal particles thereby reducing the heterogeneous reaction rate and possibly resulting in the formation of a flame in the gas phase. Literature on the group combustion of a cloud of pulverized coal particles is nonexistent.

2.6. Relevance

The relevance of the present work is as follow:

- i) Boiler Burners/Spray Combustion: Figure 2.5 shows the schematic of a wall burner. The coal particles are transported to the burner in suspension in primary air which constitutes 10-20% of the total air. The remainder of the air is given a swirl motion. The swirling and the quarl create a hot recirculation zone. As the dense cloud of coal particles mix with the recirculation zone, the primary air surrounding the particles undergoes a transient heating processes which in turn heats up the particles leading to ignition and partial combustion. The partially combusted dense cloud of particles and products mix gradually with the secondary stream. The combustion of a dilute cloud is completed somewhere downstream of the recirculation zone.

As the figure shows, the cloud is very dense near the burner and hence group ignition occurs. Furthermore, one can expect sheath combustion to occur near the burner followed by group combustion when the particles are scattered in groups before they disperse downstream. Further downstream from the jet, the particles mix with the secondary air and disperse. An IPC model would suffice to predict the burning rate in this region.

- ii) **Laminar Flow Reactors:** Laminar flow reactors (Figure 2.6) use a densely loaded stream of coal particles injected into hot gas. The ignition data and the burning rate per particle has been normally interpreted using the IPC model. Reinterpretation using the group combustion theory may be necessary.
- iii) **The PCGC-2 (Pulverized Coal Gasification and Combustion-2 Dimensional)** is a model generated using a quasi-steady iterative approach to solve problems concerning the burning of a stream of particles [Smoot and Smith, 1987]. This model involves the PSI-cell (Particle Source in Cell) model. The PSI-cell method uses an Eulerian description for the gas phase and a Lagrangian frame for the particles (Fig. 2.7). The combustor geometry is divided into various cells and the gas phase conservation equations are solved with assumed source terms due to the particles in each cell. The properties like Y_{O_2} and T are assumed to remain constant throughout the cell. Since the cell contains a large number of particles, the group theory can describe the interactive behavior between the particles in the cell. Furthermore, the combined mass blowing rate may be high enough to prevent penetration of O_2 into the cell in which case the source terms are different. For the PSI-cell method, the problem appears to be quasi-steady (QS) combustion. However, the cloud of particles migrate into different cells at

Figure 2.6. Laminar Flow Reactor

various times. Thus the ignition and combustion processes are transient with respect to the particle dynamics.

- iv) **Combustion in a Diesel Engine:** As opposed to boiler burners, where the time averaged properties at a given location remains invariant with time (steady state), the combustion in engines are intermittent and hence the combustion is essentially non-steady. The PSI-cell model may involve space iterations at each time step. On the other hand, the adoption of packet combustion models (PACC) are less complex [Bell and Caton, 1986]. According to PACC model, the spray is divided into various packets which gradually entrain air. The entrainment rate for packets in the core of the spray is small, while the entrainment rate for a packet at the edge of the spray is large. The particle and gas histories are traced for each packet. Hence, the NS group combustion model is useful for both the PSI-cell and packet models as well as to interpret experimental data on the combustion of a cloud of particles.
- v) **Incipient and Developing Fires and Flame Propagation:** The problem of spontaneous combustion exists both in the seam and the dump of coal fields [Ghosh, 1986]. Experimental studies on the self-heating piles indicate an ignition temperature of 170K for the 4-7 μ m dust particles which increases monotonically with the particle size ($E \approx 72000\text{kJ/kmol}$) [Cashdollar and Hertzburg, 1983]. It should be mentioned that the QS IPC model will predict decreasing ignition temperature as particle diameter increases. Furthermore, the flame propagation models in ducts carrying coal dust/air mixtures invariably are based on individual coal particle ignition and combustion models [Pickles, 1982].

It is apparent from figure 2.5, that pyrolysis, ignition, and combustion occurs for a very dense cloud. Consider packet P (fig. 2.5). Since the particles

Figure 2.7. Particle Source in Cell

are small, the relative velocity between the surrounding gas and the particles is small. Thus, with respect to a coordinate axis attached to the particle, the particles appear to burn in a quiescent atmosphere. In real burners, the packet P moves through low temperature zones to zones of high temperature. Thus, the packet containing a fixed number of particles may expand. In order to understand the mechanisms governing dense cloud behavior and to extricate the basic parameters controlling group combustion, such a packet can be approximated as a spherical cloud of fixed radius burning in a quiescent atmosphere. Group combustion models have been formulated for a cloud of drops and char particles. There exists no theoretical model on the group combustion of coal particles to ascertain the interactive effects on the ignition and combustion characteristics of a cloud of coal particles. Although most of the interpretations of experimental burning rates for coal particle clouds/streams are based on the IPC model, a GC model would be more useful in reinterpreting the experimental data with due consideration to group effects.

CHAPTER III

OBJECTIVES

The primary objectives of this work are

- (1.) to improve the nonsteady code for group pyrolysis and ignition of a spherical cloud of coal particles,
- (2.) to formulate and include a thin flame combustion model to simulate combustion once the cloud has ignited,
- (3.) to include a simple radiation model, and
- (4.) to study the effect of ambient conditions and particle and cloud parameters on the pyrolysis, ignition, and combustion characteristics of a spherical cloud of pulverized coal particles with and without radiation.

In the following, a model is presented for the group behaviour of a cloud of coal particles which includes group pyrolysis, ignition, and combustion.

CHAPTER IV

THE MODEL AND CONSERVATION EQUATIONS

This chapter presents a detailed description of the model adopted. The assumptions used for the model are also listed along with used the various reactions used in the model. The conservation equations in the gas phase and solid phase for a cloud of monosized particles are presented. This is followed by the expressions for the source terms and the initial and boundary conditions for the set of differential equations (conservation equations). With the help of reference quantities, which are also presented in this chapter, the conservation equations are then made non-dimensional and finally the conventional form and the Shvab-Zeldovich transformation of the non-dimensional conservation equations are presented. The Shvab-Zeldovich transformations are useful in studying thin flame combustion.

4.1. Model for Transient Combustion

Consider a cloud of coal particles within a sphere of radius R_c (Figure 4.1). There is a thin film region around each coal particle (zone I) within which there is a property gradient. The region adjacent to the film zone is called the bulk gas zone (zone II) within which properties are almost uniform with respect to the " θ " and " ϕ " directions but vary with the " r " direction. The region outside the cloud is called the single phase zone (zone III). If a cloud of radius R_c containing coal particles of size " a " is placed in a hot furnace, then a thermal wave propagates from ambience into the cloud. The bulk gas temperature in zone II increases which in turn supplies heat to the particles. When the temperature of the particles reaches the pyrolysis level, thermal decomposition of

Figure 4.1. Group Combustion Model for a Spherical Cloud of Coal Particles

coal occurs releasing volatiles (V_I and V_{II}). The volatiles diffuse through the film zone into the bulk gas zone. The volatiles then diffuse towards both the center of the cloud as well as towards the ambience. Furthermore, volatiles undergo oxidation reactions in zones II and III. The volatiles diffusing towards the ambience can undergo rapid gas phase oxidation reactions resulting in gas phase ignition (homogeneous ignition) provided the ambient temperature is high. On the other hand, if pyrolysis is not intensive enough to prevent the penetration of O_2 into the cloud, then the coal particles inside the cloud can undergo heterogeneous oxidation reactions producing CO , H_2 , and CO_2 resulting in surface ignition (heterogeneous ignition). Thus the ignition mode may be either in the gas phase or on the particle surfaces. A single particle combustion model also reveals such a behavior [Annamalai and Durbetaki, 1977]. The CO produced during heterogeneous reactions undergoes further oxidation in both zones II and III.

Once the oxidation of volatiles and CO is rapid enough to effectively prevent oxygen from reaching the cloud, a spherical flame stands outside the cloud. The flame supplies heat to the cloud for the heat of pyrolysis of particles within the cloud and for heating CO and pyrolysate to the flame temperature (sensible enthalpy). Furthermore, it should be noted that the concentration of volatiles and temperature inside the cloud may be high enough for cracking reactions which can result in soot formation. The model accounts for:

1. Transient heating of a cloud of coal particles.
2. Pyrolysis of particles via competing reactions.
3. Heterogeneous reactions.

(Reaction - III)

4. Homogeneous gas phase reactions (until ignition)

(Reaction -IV)

(Reaction - Va)

(Reaction - Vb)

(Reaction-VI)

5. Thin Flame Model (after ignition)

4.2. Assumptions

- i.) Spherical symmetry exists and $\rho D = \text{constant}$.
- ii.) For zone I, there exists a property gradient. This property gradient is utilized in obtaining the relations for heat and mass transfer around each particle it is assumed that the relations obtained for a frozen film zone around the particle are valid.
- iii.) The coal particles are dry and ash free.
- iv.) The two phase cloud zone is treated as a single phase gas zone by assuming that the particles act as point heat and mass sources (i.e. the volume occupied by the particles is assumed to be small). Furthermore, in order to reduce the three-dimensionality of the problem to one dimension, the point sources are uniformly distributed at a given radius (i.e. volatiles are distributed at infinite speed between particles). This is illustrated in figure 4.2.
- v.) All gas phase chemical reactions for volatiles and CO occur by a single step.

Figure 4.2. Illustration of Point Source Assumption

- vi.) Pyrolysis occurs volumetrically with constant diameter while heterogeneous reactions occur at constant density and varying diameter. Hence during pyrolysis, the density decreases with constant diameter and for heterogeneous reactions, the particle shrinks at constant density [Stickler et al., 1979].
 - vii.) Gases are transparent to radiation at all wavelengths.
 - viii.) The ideal gas law is applicable.
 - ix.) The radiation heat loss from the particles is a function of the number of particles per unit volume in addition to its dependence on temperature. If the number density is high ($\approx 10^{11}$ particles/m³), then the interior particles may be radiatively shielded. If the cloud is dilute (in the radiative sense, 10^9 particles/m³), then the radiation loss is significant from each particle in the cloud.
 - x.) Particles are stationary in the cloud.
 - xi.) Volatile oxidation occurs by a two step reaction. One which proceeds relatively fast and results in the production of CO and the other which proceeds at a much slower rate and results in the production of CO₂. Thus the volatile oxidation kinetics are assumed to be the same as the CO oxidation kinetics.
- kinetics are assumed to be the same as char oxidation kinetics.

Additional assumptions will be stated later. The various time scales calculated for the cloud and the particles are indicated in Table 4.1. The thermal penetration time is longer than the heat up, pyrolysis, and burning times and as such the combustion process of a cloud of radius of R_c is essentially transient. Thus nonsteady conservation equation are used:

Table 4.1 Time Scales for Group Combustion of Coal Particles

$$R_c = 1 \times 10^{-2}$$

$$a = 50 \times 10^{-6}$$

Thermal Wave Penetration Time (αR_c^2):	1000 ms
Heat Diffusion Time to the Center of the Particle (αa^2):	25 ms
Heating Time for Particles (αa^2):	10 ms
Half Life Time for Pyrolysis (α_I/k_V):	
	at $T_p = 600, 700, 900, 1000K$
	$t_{1/2,p} = 5000, 600, 120, 12 \text{ ms}$
Char Particle Burnout Time:	
Kinetics Control (αa):	at $T_p = 700, 900, 1100, 1300, 1500K$
	$t_{b,k} = 122000, 9700, 1900, 600, 300 \text{ ms}$
Diffusion Control (αa^2):	152 ms
Half Life Time Scales for CO Oxidation (α_I/k_{CO}):	
	at $T_p = 800, 1000, 1500, 2000K$
	$t_{1/2,p} = 6800, 153, 1.0, 0.1 \text{ ms}$
Transport Time Scales Between the Particles:	
	for $n = 1.0 \times 10^7$ $t_T = 50 \text{ ms}$
	for $n = 1.0 \times 10^9$ $t_T = 2.5 \text{ ms}$

4.3. Dimensional Form of Conservation Equations

4.3.1. Gas phase conservation equations

4.3.1.1. Mass

$$4\pi r^2 \left(\frac{\partial \rho}{\partial t} \right) + \left(\frac{\partial \dot{m}}{\partial r} \right) = \dot{w}_m''' 4\pi r^2 \quad (4.1a)$$

$$\dot{w}_m''' = \begin{cases} \dot{m}_{pp}''' & r < R_c \\ 0 & r > R_c \end{cases} \quad (4.1b)$$

where

$\dot{w}_m'''$ is the mass production rate per unit volume of the gas phase,

$\dot{m}_{pp}'''$ is the mass added to the bulk gas phase (or mass produced) due to reactions at the particles per unit volume

ρ is the density of gas and

$\dot{m}$ is the mass flow rate at "r".

xii It is assumed that, the mass source per unit volume is only a function of r (i.e. all the point mass sources within "dr" are distributed uniformly throughout the volume $4\pi r^2 dr$ and as such $\dot{w}_m''' = n\dot{m}_{pp}'''$, where $\dot{m}_{pp}'''$ is the mass source per particle).

4.3.1.2. Species

$$4\pi r^2 \left[\frac{\partial(\rho Y_k)}{\partial t} \right] + \left[\frac{\partial(\dot{m} Y_k)}{\partial r} \right] - \left[\frac{\partial}{\partial r} \left(4\pi r^2 \rho D \left(\frac{\partial Y_k}{\partial r} \right) \right) \right] = \dot{w}_k''' 4\pi r^2 \quad (4.2a)$$

where

k represents the species O_2 , V (volatiles), CO, CO_2 , and H_2O

$\dot{w}_k'''$ is the production rate of species k per unit volume.

$$\dot{w}_k''' = (\dot{m}_{pp,k}''' + \dot{m}_{ch,k}'''), \quad \text{for } r < R_c \quad (4.2b)$$

$$\dot{w}_k''' = \dot{m}_{ch,k}''' \quad r > R_c$$

$\dot{m}_{pp,k}'''$ is the species k added (produced) to the bulk gas phase due to reactions at the particle per unit volume of the cloud,

$\dot{m}_{ch,k}'''$ is the species k added to the bulk gas phase due to chemical reactions in the gas phase,

Y_k is the mass fraction of species k , and

D is the diffusion coefficient

For $k = N_2$, $\dot{w}_k''' = 0$. It should be noted that if species are consumed at particle surfaces, then $\dot{m}_{pp,k}''' < 0$ and if produced $\dot{m}_{pp,k}''' > 0$. Consider the example,

For this reaction if $k=O_2$, the species O_2 is consumed and hence $\dot{m}_{pp,O_2}''' < 0$. The species CO is produced and hence $\dot{m}_{pp,CO}''' > 0$. Similarly, if species k is produced in the gas phase due to chemical reactions, $\dot{m}_{ch,k}''' > 0$ and if consumed, $\dot{m}_{ch,k}''' < 0$. Consider the example,

Here $\dot{m}_{ch,CO}''' < 0$ and $\dot{m}_{ch,CO_2}''' > 0$.

Using the mass conservation equation (4.1), equation (4.2a) can be rewritten as

$$\begin{aligned} 4\pi r^2 \rho \left(\frac{\partial Y_k}{\partial t} \right) + \dot{m} \left(\frac{\partial Y_k}{\partial r} \right) - \left[\frac{\partial}{\partial r} \left(4\pi r^2 \rho D \left(\frac{\partial Y_k}{\partial r} \right) \right) \right] \\ = (\dot{w}_k''' - \dot{w}_m''' Y_k) 4\pi r^2 \quad \tau < R_c \\ = \dot{w}_k''' \quad \tau > R_c \end{aligned} \quad (4.2c)$$

The physical meaning of the term on the right hand side of equation (4.2c) is as follows:

Suppose O_2 is consumed at the particle surface due to the reaction

of equation (4.2c) reduces to:

$$(\dot{w}_k''' - \dot{w}_m''' Y_k) 4\pi r^2 = [\dot{m}_{pT,O_2}''' - \dot{m}_{pp,O_2}'''] \quad (4.2d)$$

where $\dot{m}_{pp,O_2}''' < 0$ and $\dot{m}_{pp}''' > 0$. Hence the reduction of the O_2 mass fraction takes place due to the local consumption of O_2 (at the particle surface ($\dot{m}_{pp,O_2}'''$)) and due to the blowing rate ($\dot{m}_{pp}''' Y_{O_2}$) at r .

An interesting deduction can be made for the combustion of a cloud of char particles. Let us assume that CO oxidation is very rapid (Reaction IV) and O_2 is abundantly available in the gas phase. The source term in equation (4.2a) for $k = O_2$ is written as,

$$\dot{w}_{O_2}''' = \dot{m}_{pp,O_2}''' + \dot{m}_{ch,O_2}''' + \dot{m}_{pp,CO}''' \quad (4.3a)$$

Assuming CO oxidation is very rapid,

$$\dot{m}_{pp,O_2}''' = \dot{m}_{pp,I}''' \nu_I \quad (4.3b)$$

$$\dot{m}_{ch,O_2}''' = -\nu_{IV} \dot{m}_{pp,CO}''' \quad (4.3c)$$

Where

$$\dot{m}_{pp,CO}''' = \dot{m}_{pp,I}''' (1 + \nu_I) \dot{m}_{pp,III}''' (1 + \nu_{III}) \quad (4.3d)$$

Using (4.3b), (4.3c), and (4.3d) in (4.3a) yields

$$\dot{w}_{O_2}''' = -\dot{m}_{pp,I}''' [\nu_I + (1 + \nu_I) \nu_{IV}] - \dot{m}_{pp,III}''' (1 + \nu_{III}) \nu_{IV} \quad (4.3e)$$

Substituting the stoichiometric coefficients in terms of molecular weights into (4.3e),

$$\dot{w}_{O_2}''' = -(\dot{m}_{pp,I}''' + \dot{m}_{pp,III}''') (W_{O_2} / W_c) \quad (4.3f)$$

Equation (4.3f) is equivalent to the statement that oxygen is consumed for the direct production of CO_2 from the particles with the instantaneous production of CO_2 from carbon where the carbon loss rate is controlled by the reaction kinetics of I and III.

4.3.1.3. Energy

The energy conservation equation is obtained by considering a control volume bounded by surfaces of radii " r " and " $r + dr$ " and by the surfaces surrounding the particles within " r " and " $r + dr$ " (Figure 4.3).

$$4\pi r^2 [\partial(\rho h_T)/\partial t] + [\partial(\dot{m} h_T)/\partial r] - [\partial(4\pi r^2 \rho D(\partial h_T/\partial r))/\partial r] = \dot{w}_h''' 4\pi r^2 \quad (4.4a)$$

where

$$\dot{w}_h''' \text{ is the enthalpy production rate per unit volume of the bulk gas phase,} \\ \dot{w}_h''' = (\dot{q}_{conv}''' + \dot{q}_{ch}''') \quad r < R_c \quad (4b)$$

$$\dot{w}_h''' = \dot{q}_{ch}''' \quad r > R_c \quad (4c)$$

$\dot{q}_{conv}'''$ is the heat transferred by convection to the bulk gas phase from the solid particles per unit volume of the cloud,

h_T is the thermal enthalpy, $(\int_{T_w}^T c_p dT)$

$\dot{q}_{ch}'''$ is the heat added to the gas phase per unit volume due to chemical reactions in the gas phase.

If $T_p > T$ then $\dot{q}_{conv}''' > 0$. Such a situation occurs if surface oxidation reactions are dominant compared to the gas phase reactions. If $T_p < T$ then $\dot{q}_{conv}''' < 0$. Such a situation occurs during the pyrolysis and ignition process. Similarly, if the gas phase reaction is exothermic then $\dot{q}_{ch}''' > 0$ (eg. oxidation of volatiles). If the gas phase reaction is endothermic, then $\dot{q}_{ch}''' < 0$. Note that T_w may be a function of " r " for the nonsteady case. There is no quantitative difference between T_w and T_p except that T_w represents the gas temperature at the particle surface.

Using the mass conservation equation (4.1a), equation (4.4a) can be rewritten as,

$$4\pi r^2 \rho \left(\frac{\partial h_T}{\partial t} \right) + \dot{m} \left(\frac{\partial h_T}{\partial r} \right) - \left[\frac{\partial}{\partial r} \left(4\pi r^2 \rho D \left(\frac{\partial h_T}{\partial r} \right) \right) \right] = (\dot{w}_h''' - \dot{w}_m''' h_T) 4\pi r^2 \quad (4.4d)$$

Figure 4.3. Illustration of Energy Balance

The first term on the right hand side of eq. (4.4d) represents the rise in enthalpy due to heat addition to the gas phase arising from convection from the particles and the chemical heat liberation from the gas phase and the second term represents the enthalpy drop due to the blowing effect.

4.3.2. Solid Phase Equations

Figure 4.4 represents the processes occurring around the particles.

4.3.2.1. Mass

$$dm_p/dt = -\dot{m}_p \quad (4.5a)$$

where

dm_p/dt is the total rate of change of the particle mass due to pyrolysis and heterogeneous reactions,

$\dot{m}_p$ is the mass loss rate of a particle, and

m_p is the mass of a particle at any time t .

The mass loss rate ($\dot{m}_p$) is a sum of the volatiles liberation rate ($\dot{m}_V$) and carbon consumption rate ($\dot{m}_C$) due to heterogeneous reactions.

$$\dot{m}_p = \dot{m}_V + \dot{m}_C \quad (4.5b)$$

Further

$$(dm_p/dt)_V = -\dot{m}_V \quad (4.5c)$$

$$(dm_p/dt)_C = -\dot{m}_C \quad (4.5d)$$

where

$(dm_p/dt)_V$ is the rate of change of the mass of the particles due to pyrolysis

and

Figure 4.4. Schematic of Transport Processes

$(dm_p/dt)_C$ is the rate of change of the mass of the particles due to heterogeneous reactions and

$$(dm_p/dt) = (dm_p/dt)_V + (dm_p/dt)_C \quad (4.5e)$$

Using (4.5b) in (4.5a),

$$(dm_p)/dt = -\dot{m}_p = -(\dot{m}_V + \dot{m}_C) \quad (4.5f)$$

4.3.2.1.1. Mass loss rate due to pyrolysis

The kinetics of devolatilization is summarized by Anthony and Howard [1976]. Pyrolysis is normally assumed to be volumetric and hence proceeds with constant particle size and variable density (Figure 4.4a).

The mass loss rate of volatiles is evaluated essentially with the competing pyrolysis model. The description of this model is given by Kobayashi and Stickler et al. [1974]. According to the competing reaction model, there are two reactions (reaction I and reaction II) proceeding simultaneously and competing for hydrogen atoms.

Volatiles

Pyrolysis reaction I (low temperature)

$$\dot{m}_{V,I} = \alpha_I k_{V,I} m_{cu} \quad (4.6a)$$

where

α_I is the maximum possible volatile yield via pyrolysis reaction V_I ,

$k_{V,I}$ is the specific reaction rate constant for reaction I,

$$k_{V,I} = B_{V,I} \exp \left(\frac{-E_{V,I}}{(R_u T_p)} \right) \quad (4.6b)$$

$B_{V,I}$ is the preexponential factor for pyrolysis via pyrolysis reaction V_I

m_{cu} is the coal undegraded, and

$$m_{cu} = m_{p,0} - \int_0^t \left[\left(\frac{\dot{m}_{V,I}}{\alpha_I} \right) + \left(\frac{\dot{m}_{V,II}}{\alpha_{II}} \right) \right] dt \quad (4.6c)$$

Where

$m_{p,0}$ is the mass of the particle at time $t = 0$

$\dot{m}_{V,II}$ is the mass loss rate via pyrolysis reaction V_{II} .

Pyrolysis Reaction II (high temperature)

$$\dot{m}_{V,II} = \alpha_{II} k_{V,II} m_{cu} \quad (4.6d)$$

where α_{II} is the maximum possible yield via pyrolysis reaction (V_{II})

$$k_{V,II} = B_{V,II} \exp \left(\frac{-E_{V,II}}{R_u T_p} \right) \quad (4.6e)$$

Equations (4.6a) and (4.6c) can also be written as,

$$\left(\frac{\dot{m}_{V,I}}{m_{p,0}} \right) = \alpha_I k_{V,I} f_{cu}$$

$$\left(\frac{\dot{m}_{V,II}}{m_{p,0}} \right) = \alpha_{II} k_{V,II} f_{cu}$$

$$f_{cu} = \frac{m_{cu}}{m_{p,0}} = 1 - \int_0^t (k_{V,I} + k_{V,II}) f_{cu} dt$$

The total volatiles liberation rate due to both reactions (V_I) and (V_{II}) is given as

$$(\dot{m}_V) = (\dot{m}_{V,I}) + (\dot{m}_{V,II}) \quad (4.6f)$$

Using equation (4.6f) in (4.5c),

$$(dm_{p,i}/dt)_V = -\dot{m}_{V,i} = -(\dot{m}_{V,I} + \dot{m}_{V,II}) \quad (4.6g)$$

Pyrolysis with heterogeneous in-situ combustion of volatiles

If volatiles are consumed in-situ along with carbon, then eq. (4.6c) should be modified as,

$$m_{cu} = m_{p,0} - \int_0^t \left(\frac{\dot{m}_{V,I}}{\alpha_I} + \frac{\dot{m}_{V,II}}{\alpha_{II}} + \frac{\dot{m}_{V,S}}{VM} \right) dt \quad (4.7a)$$

where,

VM is the volatile fraction left in the coal at time t , and

$\dot{m}_{V,S}$ is the in-situ volatile combustion rate.

The Q factor

At any instant of time t

$$Q = \frac{\dot{m}_V \text{ for a given } m_{cu}}{\dot{m}'_{V,I} \text{ for the same } m_{cu}} \quad (4.7b)$$

where $(\dot{m}'_{V,I})$ is the volatile liberation rate when competing reaction V_{II} is absent.

Using (4.6a), (4.6c), (4.6d), and (4.6f) in (4.7b), Q becomes

$$Q = \left(1 + \frac{k_{V,II}\alpha_{II}}{k_{V,I}\alpha_I} \right) \quad (4.7c)$$

Note that if $k_{V,II} \rightarrow 0$, then $Q \rightarrow 1.0$ as expected.

Proximate Volatile Matter (PVM)

If the proximate volatile matter in coal is traced as a function of time, then

$$\frac{d((PVM)m_p)}{dt} = \left(-\frac{\dot{m}_V}{Q} - \dot{m}_{V,S} \right) \quad (4.7d)$$

Where

$$-\frac{dm_p}{dt} = (\dot{m}_V + \dot{m}_C + \dot{m}_{V,S}) \quad (4.7e)$$

$\dot{m}_v/Q$ is the proximate volatile loss rate and $\dot{m}_v$ is the actual volatile loss rate.

Using (4.7e) in (4.7d) gives

$$-\frac{d(PVM)}{dt} = \frac{\left(-\frac{\dot{m}_v}{Q} - \dot{m}_{v,s} + (PVM)\dot{m}\right)}{m_p} \quad (4.7f)$$

Equation (4.7f) is useful in tracking PVM as time varies. Suppose $\dot{m}_{v,s} = 0$, then for $Q = 1$, the proximate volatile matter decreases more slowly than for $Q = 2$.

4.3.2.1.2. Mass loss rate due to heterogeneous reactions

The following heterogeneous reactions proceed at the surface of the particles (see Figure 4.4).

The last reaction is neglected. The mass loss rate $\dot{m}_c$ due to heterogeneous char reactions is evaluated as follows. For heterogeneous reaction I

$$(\dot{m}_{C,I}) = \rho_w k_{C,I} Y_{O_2,w}^{n_{O_2,I}} \pi d_p^2 \quad (4.8a)$$

where

$n_{O_2,I}$ is the order of reaction I with respect to oxygen,

$Y_{O_2,w}$ is the concentration of oxygen at the wall of the particle,

$k_{C,I}$ is the specific reaction rate constant for reaction (I),

$B_{C,I}$ is the preexponential factor for reaction I,

$n_{O_2,I}$ is the order of reaction with respect to O_2 for reaction I

$\dot{m}_{C,I}$ is the carbon/char consumption due to reaction (I), and

$$k_{C,I} = B_{C,I} \exp\left(\frac{-E_{C,I}}{R_u T_p}\right) \quad (4.8b)$$

Similarly,

$$(\dot{m}_{C,II}) = \rho_w k_{C,II} Y_{O_2,w}^{n_{O_2,II}} \pi d_p^2 \quad (4.8c)$$

$$(\dot{m}_{C,III}) = \rho_w k_{C,III} Y_{O_2,w}^{n_{O_2,III}} \pi d_p^2 \quad (4.8d)$$

The specific reaction rate constant for other reactions are given as,

$$k_{C,II} = B_{C,II} \exp \left(\frac{-E_{C,II}}{R_u T_p} \right) \quad (4.8e)$$

$$k_{C,III} = B_{C,III} \exp \left(\frac{-E_{C,III}}{R_u T_p} \right) \quad (4.8f)$$

The total carbon consumption rate for a particle of size " d_p " is given as

$$(\dot{m}_C) = (\dot{m}_{C,I}) + (\dot{m}_{C,II}) + (\dot{m}_{C,III}) \quad (4.8g)$$

If T_p and d_p are known, then using equations (4.8), $\dot{m}_C$ can be evaluated.

Finally, assuming the in-situ combustion rate is proportional to the ratio of volatile matter to the fixed carbon in the coal.

$$\dot{m}_{V,S} = \dot{m}_C \left(\frac{VM}{(1 - VM)} \right) \quad (4.8h)$$

The species mass fractions at the wall ($Y_{k,w}$) of particle size i are calculated as follows.

With the assumption of a first order reaction at the particle surface, the analysis of the mass transfer across the frozen film yields the following expression for species fraction at the wall (Figure 4.4).

$$\left(\frac{Y_{k,w}}{Y_k} \right) = \left[\exp(X) - \sum_{l=1}^L \frac{\nu_{k,l} \rho k_{c,l} S n_l d_p (\exp(X) - 1)}{(X Sh \rho D)} \right]^{-1} \quad (4.8i)$$

where L is the total number of reactions involving species k

$$X = \dot{m}_p / (Sh \rho D \pi d_p) \quad (4.8j)$$

$$= h_m d_{p,i} / \rho D$$

$$Sh = 2 + 0.6 Re^{1/2} Sc^{1/3} \quad (4.8k)$$

$= 2$ for a quiescent atmosphere

$\nu_{k,l}$ is the stoichiometric mass of species k per unit mass of carbon in reaction "l,"

h_m is the mass transfer coefficient,

Sn_l equals +1 if species are produced for reaction l , and

Sn_l equals -1 if species are consumed for reaction l .

For example, if $k=O_2$, then there are two heterogeneous reactions (reactions r_I and r_{II}) which consume O_2 and hence $L = 2$. Since O_2 is consumed, the sign of Sn is negative for both the reactions (I) and (II). When carbon is oxidized heterogeneously, there may be in-situ combustion of volatiles. If in-situ volatiles combustion is included then $L=3$. Sn is negative and

$$k_{c,3} = (k_{c,I} + k_{c,II}) \left(\frac{VM}{FC} \right)$$

On the other hand if $k=CO_2$, then CO_2 is produced by reaction (II) and consumed by reaction (III). Hence $L = 2$ and $Sn_l = +1$ for reaction II and $Sn = -1$ for reaction III. For $k=CO$, CO is produced by reactions I and III. As such $L = 3$. Furthermore, $\nu_{CO,I} = 28/12$, $\nu_{CO,III} = 56/12$, and $Sn_l = +1$ for both the reactions.

4.3.2.2. Diameter of the particle (d_p)

Mass loss occurs due to consumption of carbon at constant density. Hence, as the diameter of the particle shrinks, the relation between $\dot{m}_c$ and d_p is given as

$$(1/2)\rho_p \pi d_p^2 (Dd_p/Dt) = -\dot{m}_C \quad (4.9)$$

4.3.2.3. Density of the particle (ρ_p)

The mass loss due to pyrolysis occurs volumetrically at constant particle size. Hence, the density decreases and

$$(\pi d_p^3)(D\rho_p/Dt) = -\dot{m}_V \quad (4.10)$$

4.3.2.4. Particle temperature (T_p)

From an energy balance around the individual particle,

$$m_p c_p (DT_p/Dt) = -(\dot{q}_{conv} + \dot{q}_{rad}) + \dot{q}_{ch,p} \quad (4.11a)$$

where

$\dot{q}_{conv}$ is the convective heat transfer between the bulk gas and particles of size " d_p ,"

$\dot{q}_{rad}$ is the radiative heat transfer between a particle of size " d_p " and ambience, and

$\dot{q}_{ch,p}$ is the chemical heat generation rate due to reactions at the particle surface.

Convection Term

Assuming quasi-steady behavior around the particle, the overall heat transfer rate between the particle and the gas is given as,

$$\dot{q}_{conv} = h^\circ (T_p - T) \pi d_p^2 F_k F_B \quad (4.11b)$$

where

F_k is the Knudson correction factor (only significant for small sized particles),

F_B is the blowing correction factor,

h_i° is the heat transfer coefficient for a particle of size d_p . In the absence of mass transfer, $h^\circ = Nu^\circ \lambda / d$.

$Nu^\circ = 2 + 0.6Re^{\frac{1}{2}}Pr^{\frac{1}{3}}$ (Ranz-Marshall correlation). $Nu^\circ = 2$ for burning in a quiescent atmosphere,

d_p is the particle diameter, and

$\dot{q}_{conv}$ is the convective heat transfer between the particle and the bulk gas adjacent to the particle.

The blowing correction factor to the heat transfer coefficient is given as

$$F_B = \left[\frac{[\dot{m}_p / 2\pi\rho D d_p]}{\left[\exp\left(\frac{\dot{m}_p}{2\pi\rho D d_p}\right) - 1 \right]} \right] \quad (4.11c)$$

The Knudson correction factor is given as

$$F_K = 1 - \left[\frac{(l_m / d_p)}{((l_m / d_p) + 0.17)} \right] \quad (4.11d)$$

where

l_m is the mean free path.

It is noted that the Knudson correction factor leads to 1.0 at $d_p \gg l_m$. Rewriting equation (4.11b) in terms of Nusselt number,

$$\dot{q}_{conv} = Nu^\circ \pi (T_p - T) \lambda d_p F_K F_B \quad (4.11e)$$

where $\lambda = Le\rho DC_p = \rho DC_p$ if $Le = 1.0$

Radiation Term

The particles transfer energy by radiation to the surroundings. The particles at the cloud periphery radiate to the ambience and hence the radiation loss is given as

$$\dot{q}_{rad} = \sigma_{SB} \epsilon (T_p^4 - T_{rad}^4) \pi d_p^2 \quad (4.11f)$$

where

ϵ is the emissivity,

σ_{SB} is the Stefan-Boltzmann constant, and T_{rad} is the radiative temperature surrounding the cloud. However for a dense cloud, the particles near the

center radiate to the hot glowing particles inside the cloud and only a fraction of the area may be available for radiation loss to the ambience. Thus, more generally, the radiation loss from the particles in the cloud can be written as,

$$\dot{q}_{rad} = F_R \sigma_{SB} \epsilon (T_p^4 - T_{rad}^4) \pi d_p^2 \quad (4.11g)$$

where

F_R is the radiation shape factor to account for the shielding effect. Thus $F_R \approx 1$ for particles near the cloud surface and $F_R \approx 0$ for particles near the center for a dense cloud. For a very dilute cloud, $F_R \approx 1$ for every particle inside the cloud.

In order to ascertain the effect of radiation loss on the results consider those particles at the center of a dilute cloud ($F_R = 1$). In eq. (4.11e) let $F_K = F_B = 1$; then for the particles at the periphery,

$$\frac{\dot{q}_{rad}}{\dot{q}_{conv}} = \left(\frac{(T_{rad}^4 - T_p^4) \sigma_{SB} \epsilon d_p}{Nu \lambda (T_g - T_p)} \right) \quad (4.11h)$$

If $T_p/T_{rad} \ll 1$ and assuming $T_g \approx T_{rad}$ for particles at the periphery,

$$\frac{\dot{q}_{rad}}{\dot{q}_{conv}} \approx \left(\frac{\sigma_{SB} \epsilon d_p T_{rad}^3}{Nu \lambda} \right) \quad (4.11i)$$

If $T_{rad} = 1000K$, $\sigma_{SB} \approx 5.67 \times 10^{-11} \text{ kW/m}^2\text{K}^4$, $d_p = 100 \times 10^6 \text{ m}$, $\epsilon = 1$, $Nu = 2$, $\lambda = 0.59 \times 10^{-4} \text{ kW/mK}$, then

$$\dot{q}_{rad}/\dot{q}_{conv} \approx 0.05$$

If $T_{rad} = 2000K$, then

$$\dot{q}_{rad}/\dot{q}_{conv} \approx 0.40$$

Once the particle heats up, the radiation term diminishes rapidly compared to the convective term and can be considered negligible in comparison.

For particles at the center of a dilute cloud $F_R = 1$, $\dot{q}_{conv} \approx 0$ since $T_g \approx T_p$ for the convective contribution in the initial period, while for the radiative contribution, $T_{rad} \approx T_\infty$ and hence $\dot{q}_{rad}/\dot{q}_{conv} \rightarrow \infty$.

The radiation view factor was assumed to be one for all clouds studied. More work is underway to determine an appropriate view factor for particles within the cloud.

The chemical source term

The heat liberation rate due to chemical reactions at the particles is given as

$$\dot{q}_{ch,p} = \dot{m}_{C,I} h_{C,I} + \dot{m}_{C,III} h_{C,III} + \dot{m}_{V,I} h_{P,I} + \dot{m}_{V,II} h_{P,II} \quad (4.11j)$$

where

$h_{C,I}$ is the heat released due to first heterogeneous reaction I,

$h_{C,III}$ is the heat released due to third heterogeneous reaction III,

$h_{P,I}$ is the heat released due to first pyrolysis reaction in the competing reaction model, and

$h_{P,II}$ is the heat released due to second pyrolysis reaction in the competing reaction model.

Note: $h_{C,I} > 0$ due to the oxidation reaction (I) and $h_{C,III} < 0$ due to the reduction reaction (III).

4.3.2.5. Mass, species, and heat sources

4.3.2.5.1. Mass source ($\dot{w}_m'''$)

The mass added to the unit volume of the bulk gas phase in the two phase cloud region (TPR) must be equal to the mass loss of solid particles per unit volume as long as the quasi-steady assumption is valid in the thin film region around each particle.

$$\dot{w}_m''' = \sum n \dot{m}_p \quad (4.12)$$

where n is the number of coal particles per unit volume of TPR.

The mass loss rate of the coal particles ($\dot{m}_p$) occurs due to pyrolysis and heterogeneous char reactions and the mass loss rate is given by equations (4.5).

4.3.2.5.2. Species source ($\dot{w}_k'''$)

Species k are produced/consumed at the particle due to heterogeneous and/or pyrolysis reactions and due to homogeneous gas phase reactions. Thus, for species k ,

$$\dot{w}_k''' = \dot{m}_{pp,k}''' + \dot{m}_{ch,k}''' \quad (4.13a)$$

Where

$\dot{m}_{pp,k}'''$ is species k produced at the particle surface and

$\dot{m}_{ch,k}'''$ is species k due to homogeneous reactions.

For example, $k = V$ (which maybe either V_I or V_{II}) then,

$$\dot{w}_V''' = n\dot{m}_V + \dot{m}_{ch,V} \quad (4.13b)$$

Where, for a global one step oxidation of volatiles assuming a first order reaction,

$$\dot{m}_{ch,V} = -A_V Y_V Y_{O_2} \rho^2 \exp\left(\frac{-E_V}{R_u T}\right) \quad (4.13c)$$

If $k = O_2$, then O_2 is consumed due to heterogeneous and homogeneous reactions. Thus,

$$\dot{w}_{O_2}''' = -n(\dot{m}_{c,I} \nu_I + \dot{m}_{c,II} \nu_{II} + \dot{m}_{V,s} \nu_{V,s}) - \dot{m}_{ch,O_2}''' \quad (4.13d)$$

Where

$$\dot{m}_{ch,O_2}''' = \dot{m}_{ch,V} \nu_V + \dot{m}_{ch,CO} \nu_{O_2,IV} \quad (4.13e)$$

and for the wet oxidation of CO [Howard et al., 1973]

$$\dot{m}_{ch,CO}''' = -A_{CO} \rho Y_{CO} Y_{O_2}^{0.5} Y_{H_2O}^{0.5} \exp\left(\frac{-E_{CO}}{R_u T}\right) \quad (4.13f)$$

Similarly for $k = CO$ and CO_2 , the source terms $\dot{w}_{CO}'''$ and $\dot{w}_{CO_2}'''$ can be calculated.

4.3.2.5.3. Heat source ($\dot{w}_h'''$)

The heat source in the gas phase is given as,

$$\dot{w}_h''' = \dot{q}_{conv}''' + \dot{q}_{ch}''' + \dot{q}_m''' \quad (4.14a)$$

where the convective heat transfer from the coal particles to the gas per unit volume within the cloud is given as

$$\dot{q}_{conv}''' = \sum n \dot{q}_{conv} \quad (4.14b)$$

and

$\dot{q}_{conv}$ is given by equation (4.10b).

$$\dot{q}_{ch}''' = |\dot{m}_{CO}'''| h_{c,CO} + |\dot{m}_{V,I}'''| h_{c,V,I} + |\dot{m}_{V,II}'''| h_{c,V,II} \quad (4.14c)$$

where

$h_{c,j}$ is the heat released per kg of CO burnt.

The heat added to the gas phase due to mass transport from the particle surface to the bulk gas phase is given as,

$$\dot{q}_m''' = \dot{m}_{pp}''' h_{T,w} \quad (4.14d)$$

$$h_{T,w} = \int_{T_{ref}}^{T_w} c_p dT \quad (4.14e)$$

While the first term $\dot{q}_{conv}'''$ in equation (4.14a) represents the heat sink or source in the gas phase due to the transient heating or cooling of coal particles, the second term, $\dot{q}_{ch}'''$, represents the heat generation per unit volume due to chemical reactions in the gas phase. The third term in eq. (4.14a) represents the heat added to the bulk gas from the particles due to mass transfer.

4.3.3. Initial and boundary conditions

At $t=0^+$,

Gas Phase

$$T = T_{\infty} \text{ or } h_T = h_{T,\infty} \quad R_c < r < \infty \quad (4.15a)$$

$$T = T_0 \text{ or } h_T = h_{T_0} \quad 0 < r < R_c$$

$$\rho = \rho_{\infty} \quad R_c < r < \infty \quad (4.15b)$$

$$\rho = \rho_0 \quad 0 < r < R_c$$

$$Y_k = Y_{k,\infty} \quad R_c < r < \infty \quad (4.15c)$$

$$Y_k = Y_{k,0} \quad 0 < r < R_c$$

Solid Phase

$$m_p = m_{p,0} \quad (4.15d)$$

$$d_p = d_{p,0} \quad (4.15e)$$

$$\rho_p = \rho_{p,0} \quad (4.15f)$$

$$T_p = T_{p,0} \quad (4.15g)$$

At any time t as $r \rightarrow \infty$

$$T = T_{\infty} \quad (4.16a)$$

$$\rho = \rho_{\infty} \quad (4.16b)$$

$$Y_k = Y_{k,\infty} \quad (4.16c)$$

And as $r \rightarrow 0$

$$\partial h_T / \partial r = \partial T / \partial r = 0 \quad (4.17a)$$

$$\partial \dot{m} / \partial r = 0 \quad (4.17b)$$

$$\partial Y_k / \partial r = 0 \quad (4.17c)$$

Cloud burning rate The cloud burning rate $\dot{m}_c$ at any time t is given by

$$\dot{m}_c = \int_0^{R_c} [(\dot{m}_p n)] 4\pi r^2 dr \quad (4.18)$$

where R_c is the cloud radius at any given time t .

4.4. Nondimensional Form of Conservation Equations

4.4.1. Reference quantities

$$\rho_{ref} = \frac{P}{RT_{ref}} \quad (4.19a)$$

where $R = R_u/W$ and W is the molecular weight

$$t_{ref} = \left(\frac{\rho_{ref} R_{c,0}^2}{\rho D} \right) \quad (4.19b)$$

$$\dot{m}_{ref,g}''' = \rho D / R_{c,0}^2 = \left(\frac{\rho_{ref}}{t_{ref}} \right) \quad (4.19c)$$

where ρ , is the density of the gas (determine ρ at $T = T_\infty$ and D at $T = T_\infty$).

$$\dot{m}_{ref,g} = 4\pi\rho D R_{c,0} \quad (4.19d)$$

$$h_{ref} = c_p T_{ref} \quad (4.19e)$$

$$\dot{m}_{ref,p} = \frac{\dot{m}_{p,0}}{t_{ref}} \quad (4.19f)$$

4.4.2. Nondimensional variables

$$\xi = \frac{R_{c,0}}{r} \quad (4.20a)$$

where $R_{c,0}$ is the cloud radius' at time $t = 0$

$$\tau = \frac{t}{t_{ref}} \quad (4.20b)$$

$$\rho^* = \frac{\rho}{\rho_{ref}} \quad (4.20c)$$

$$\alpha = \frac{\dot{m}}{\dot{m}_{ref,g}} \quad (4.20d)$$

$$G_0 = 4\pi n a_{ref} R_{c,0}^2 \quad (4.20e)$$

where $a_{ref} = a_0$

$$w_m = (\dot{w}_m''' / \dot{m}_{ref,g}''') \quad (4.20f)$$

$$w_k = (\dot{m}_{pp,k}''' + \dot{m}_{ch,k}''') / \dot{m}_{ref}''' \quad (4.20g)$$

$$w_h = (\dot{q}_{conv}''' + \dot{q}_{ch}''' + \dot{q}_m''') / (\dot{m}_{ref,g}''' h_{T,ref}) \quad (4.20h)$$

Equation (20h) can also be written as

$$w_h = q_{conv}'' [(nm_{p,o}) / \rho_{ref}] + [(\dot{q}_{ch}''' + \dot{q}_m''') / (\dot{m}_{ref,g}''' h_{ref})] \quad (4.20i)$$

$$h_T^* = h_T / h_{T,ref} \quad (4.20j)$$

If the cloud initially consists of mono-sized particles of radius (a_0) then

$$w_m = \frac{G_0 \dot{m}_{pp}}{(4\pi a_0 \rho D)} \quad (4.20k)$$

$$w_k = \frac{G_0 \dot{m}_{pp}}{(4\pi a_0 \rho D)} + \frac{\dot{m}_{ch,k}'''}{\dot{m}_{ref,g}'''} \quad (4.20l)$$

$$w_h = \frac{G_0 \dot{q}_{conv}}{(4\pi a_0 \rho D h_{T,ref})} + \frac{(\dot{q}_{ch}''' + \dot{q}_m''')}{(\dot{m}_{ref,g}''' h_{T,ref})} \quad (4.20m)$$

If c_p is constant, then

$$h_T^* = \frac{T}{T_{ref}} = \frac{1}{\rho^*} \quad (4.20n)$$

$$M = \dot{m}_c / 4\pi \rho D R_{c,o} \quad (4.21a)$$

With $\dot{w}_m''' = (\dot{m}_p n)$ in (4.18) and using (4.21a)

$$M = \int_1^\infty \dot{w}_m''' \left(\frac{d\xi}{\xi^4} \right) \quad (4.21b)$$

The solid phase non-dimensional quantities are defined as follows

$$m_p^* = \frac{m_p}{m_{p,o}} \quad (4.22a)$$

where $m_{p,o}$ is the mass of the particle at time $t = 0$.

$$d_p^* = \frac{d_p}{d_{p,o}} \quad (4.22b)$$

where $d_{p,o}$ is the diameter of the particle at time $t = 0$

$$D_V = \left[\frac{(B_{V,I} m_{p,o})}{(4\pi\rho D R_{c,o})} \right], \text{ Damkohler number for pyrolysis} \quad (4.22c)$$

$$E_V^* = \left(\frac{E_V / R_u}{T_{ref}} \right) \quad (4.22d)$$

$$D_C = \frac{B_C d_p^2 \rho_{ref}}{(4\pi\rho D R_{c,o})}, \text{ Damkohler number for carbon reactions} \quad (4.22e)$$

$$\theta_p = \frac{T_p}{T_{ref}} \quad (4.22f)$$

$$m_V^* = \frac{\dot{m}_V}{\dot{m}_{ref,p}} \quad (4.22g)$$

$$m_C^* = \frac{\dot{m}_C}{\dot{m}_{ref,p}} \quad (4.22h)$$

$$q_{conv}^* = \frac{\dot{q}_{conv} t_{ref}}{(h_{ref} m_{p,o})} \quad (4.22i)$$

$$q_{rad}^* = \frac{\dot{q}_{rad} t_{ref}}{(h_{ref} m_{p,o})} \quad (4.22j)$$

$$q_{ch,p}^* = \frac{\dot{q}_{ch,p} t_{ref}}{(h_{ref} m_{p,o})} \quad (4.22k)$$

4.4.3. Gas phase conservation equations

4.4.3.1. Mass

$$\left(\frac{\partial \rho^*}{\partial \tau} \right) - \xi^4 \frac{\partial \alpha}{\partial \xi} = W_m \quad (4.23a)$$

where

$$W_m = w_m \quad (4.23b)$$

4.4.3.2. Species

$$\rho^* \left(\frac{\partial Y_k}{\partial \tau} \right) - \alpha \xi^4 \left(\frac{\partial Y_k}{\partial \xi} \right) - \xi^4 \left(\frac{\partial^2 Y_k}{\partial \xi^2} \right) = W_k \quad (4.24a)$$

where

$$W_k = w_k - w_m Y_k \quad (4.24b)$$

4.4.3.3. Energy

$$\rho^* \left(\frac{\partial h_T^*}{\partial \tau} \right) - \alpha \xi^4 \left(\frac{\partial h_T^*}{\partial \xi} \right) - \xi^4 \left(\frac{\partial^2 h_T^*}{\partial \xi^2} \right) = W_h \quad (4.25a)$$

where

$$W_h = w_h - w_m h_T^* \quad (4.25b)$$

It should be recalled that for a cloud of monosized particles, w_m , w_k , and w_h are given in terms of the initial group combustion number, G_0 (eqns 4.19k-4.19m). Equations (4.22), (4.23) and (4.25) can be written in general form as follows:

$$A \left(\frac{\partial \psi}{\partial \tau} \right) - B \xi^4 \left(\frac{\partial \psi}{\partial \xi} \right) - C \xi^4 \left(\frac{\partial^2 \psi}{\partial \xi^2} \right) = D W_\psi \quad (4.25c)$$

where $W_\psi = W_m$, W_k and W_h .

The property ψ and the constants A, B, C and D for the conservation equations are tabulated in Table 4.2.

4.4.4. Solid phase equations

4.4.4.1. Mass

$$\frac{Dm_p^*}{D\tau} = -(m_V^* + m_C^*) \quad (4.26a)$$

Table 4.2. Conserved Quantity ψ for Various Conservation Equations

Constants for the Conservation Equations			
	Mass	Species	Energy
ψ	α	Y_k	h_T
A	0	1	1
B	1	α	α
C	0	1	1
D	1	1	1
W_ψ	$W_m - (\partial \rho^* / \partial \tau)$	W_k	W_h

4.4.4.2. Diameter

$$\rho_p^* \left(\frac{D(d_p^*)^3}{D\tau} \right) = -m_C^* \quad (4.26b)$$

4.4.4.3. Density

$$d_p^{*3} \left(\frac{D\rho_p^*}{D\tau} \right) = -m_V^* \quad (4.26c)$$

4.4.4.4. Temperature

$$m_p^* \left(\frac{D\theta_p}{D\tau} \right) = (q_{ch,p}^* - q_{conv}^* - q_{rad}^*) \quad (4.26d)$$

4.4.5. Initial and boundary conditions

4.4.5.1. Gas Phase

At time $\tau = 0$

$$\alpha = 0$$

$$\begin{aligned} \rho^* &= \rho_\infty^* = \frac{T_{ref}}{T_\infty} & 0 < \xi < \infty \\ \rho_0^* &= \frac{T_{ref}}{T_0} & 0 < \xi < 1 \\ \rho^* &= \frac{(\rho_0^* + \rho_\infty^*)}{2} & 1 < \xi < 0 \\ \rho^* &= \frac{(\rho_0^* + \rho_\infty^*)}{2} & \xi = 1 \end{aligned} \quad (4.27a)$$

$$Y_k = Y_{k,\infty} \quad 0 < \xi < 1 \quad (4.27b)$$

$$Y_k = Y_{k,0} \quad 1 < \xi < \infty \quad (4.27c)$$

$$Y_k = \frac{(Y_{k,\infty} + Y_{k,0})}{2} \quad \xi = 1 \quad (4.27d)$$

$$h_{T,\infty}^* = \frac{h_{T,\infty}}{h_{T,ref}} \quad 0 < \xi < 1$$

$$h_{T,0}^* = \frac{h_{T,0}}{h_{T,ref}} \quad 1 < \xi < \infty$$

$$h_T^* = \frac{(h_{T,\infty}^* + h_{T,0}^*)}{2} \quad \xi = 1$$

For time $\tau > 0$,

$$Y_k = Y_{k,\infty} \quad \xi \rightarrow 0 \quad (4.28a)$$

$$h_T^* = \frac{h_{T,\infty}}{h_{T,ref}} \quad \xi \rightarrow 0 \quad (4.28b)$$

$$\frac{\partial Y_k}{\partial \xi} \rightarrow 0 \quad \xi \rightarrow \infty \quad (4.28c)$$

$$\frac{\partial h_T^*}{\partial \xi} \rightarrow 0 \quad \xi \rightarrow \infty \quad (4.28d)$$

4.4.5.2. Particle

At time $\tau = 0$

$$m_p^* = 1 \quad (4.29a)$$

$$d_p^* = 1 \quad (4.29b)$$

$$\rho_p^* = 1 \quad (4.29c)$$

$$\theta_p = \left(\frac{T_{p,0}}{T_{ref}} \right) \quad (4.29d)$$

It should be noted that the gas phase conservation equations are first order with respect to nondimensional time, τ , and second order with respect to nondimensional radius, ξ , and as such, one needs two boundary conditions and one initial condition for each variable. The solid phase conservation equations are first order with respect to τ and hence one needs only the initial conditions.

CHAPTER V

NUMERICAL METHOD FOR TRANSIENT COMBUSTION

5.1. Numerical Method

It is convenient to use the dimensional form of the conservation equations to illustrate the numerical method. A brief description of the method used is given below:

(1.) Determine the source terms at $t = 0$

With the given initial conditions at $t = 0$ for $(T)_0$, $(Y_k)_0$, $(m_p)_0$, $(T_p)_0$, $(\rho_p)_0$, $(d_p)_0$, calculate the source terms $\dot{w}_k'''$, $\dot{w}_m'''$, $\dot{w}_h'''$ with $T_p = (T_p)_0$. (Note: the initial particle temperature may be different from the initial gas phase temperature in the cloud.)

Mass source ($\dot{w}_m'''$)

Use equations (4.6) for $\dot{m}_V$, equations (4.8) for $\dot{m}_C$, equation (4.5b) for $\dot{m}_p$ and equation (12) for $\dot{w}_m'''$.

Species source ($\dot{w}_k'''$)

Use equations (4.6) for $\dot{m}_{V,i}$, equation (4.8) for $\dot{m}_C$, (4.13a) for $\dot{m}_V'''$, equations (4.13d) for $\dot{w}_{O_2}'''$, etc.

Heat source ($\dot{w}_h'''$)

Use equations (4.11e) for $\dot{q}_{conv}$, equation (4.14b) for $\dot{q}_{conv}'''$, equation (4.14c) for $\dot{q}_{ch}'''$, and equation (4.14a) for $\dot{w}_h'''$.

(2.) Determine the properties at $t = \Delta t$ i) Gas phase properties (Y_k , T and ρ)

Using the source terms in equation (4.2c) and (4.4d) and the explicit method, determine Y_k and T for the next time step. With the ideal gas law find $\rho =$

(P/RT) at $t = \Delta t$. Since ρ at Δt is different from ρ at t , find $(\partial\rho/\partial t)$. Using the source term $\dot{w}_m'''$ and $(\partial\rho/\partial t)$, find $\dot{m}$ at $t = \Delta t$ using mass conservation equation (4.1a).

ii) Solid phase properties (T_p , ρ_p , and d_p)

With the estimated T in zone II at $t = \Delta t$, determine the amount of heat transferred via convection to or from the particles within Δt (See eq. 11b). Determine the chemical heat liberated due to reactions at the coal particles ($\dot{q}_{ch,p}$) using equation (4.111). Hence using equation (4.11a) find the particle temperature $(T_p)_{t=\Delta t}$ with $m_p = m_{p,0}$.

Determine the mass loss of volatiles within Δt from the knowledge of $\dot{m}_v$ at $t = 0$ (eqs. 4.6). Using equation (4.10) find ρ_p at $t = \Delta t$.

Determine the mass loss of carbon within Δt from the knowledge of $\dot{m}_{C,i}$ at $t = 0$ (eqs 4.8). Using equation (4.9) find d_p at $t = \Delta t$.

Using the estimated total mass loss rate $\dot{m}_p = (\dot{m}_v + \dot{m}_c)$ and equation (4.5a), determine m_p at $t = \Delta t$.

(3.) Properties at $t = 2\Delta t, 3\Delta t \dots etc$

With the knowledge of T_p at $t = \Delta t$, d_p at $t = \Delta t$, T at $t = \Delta t$, Y_k at $t = \Delta t$, $\dot{m}$ at $t = \Delta t$, etc, repeat steps 1 and 2 for gas phase and solid phase properties.

5.2. Numerical Scheme

An explicit upwind scheme is used for the first order derivative in equation 4.25c. Thus if mass is traveling outward over nodal point i ($\alpha_i > 0$) then

$$A \left(\frac{\psi_i^{k+1} - \psi_i^k}{\Delta\tau} \right) - B\xi^4 \left(\frac{\psi_{i+1}^k - \psi_i^k}{\Delta\xi} \right) - C\xi^4 \left(\frac{\psi_{i+1}^k + \psi_{i-1}^k - 2\psi_i^k}{\Delta\xi^2} \right) = DW_\psi \quad (5.1a)$$

and if mass is traveling inward over point i ($\alpha_i < 0$) then

$$A \left(\frac{\psi_i^{k+1} - \psi_i^k}{\Delta\tau} \right) - B\xi^4 \left(\frac{\psi_i^k - \psi_{i-1}^k}{\Delta\xi} \right) - C\xi^4 \left(\frac{\psi_{i+1}^k + \psi_{i-1}^k - 2\psi_i^k}{\Delta\xi^2} \right) = DW_\psi \quad (5.1b)$$

More details are given in Appendix B.

5.3. Input Data

The following section provides an alphabetical listing of the input data along with a brief description of each variable. Justification for the selected data are given in the M.S. Thesis by S. Ramalingam [1986]. The values assigned to each variable are then tabulated in table 5.1. Following table 5.1 is a discussion on the reasoning behind the selection of the values assigned to the input variables.

- ACO is the preexponential factor for the oxidation of carbon monoxide in the gas phase.
- AVG is the preexponential factor for the oxidation of volatiles in the gas phase.
- BV(1) is the preexponential factor for competing route 1.
- BV(2) is the preexponential factor for competing route 2.
- BC(1) is the preexponential factor for heterogeneous reaction 1.
- BC(2) is the preexponential factor for heterogeneous reaction 2.
- BC(3) is the preexponential factor for heterogeneous reaction 3.
- BC(4) is the preexponential factor for heterogeneous reaction 4.
- C is the carbon mass fraction in the coal.
- CP is the specific heat of the gas phase.
- DP is the initial particle diameter.
- DPO(I) is the diameter of the particles for size group I.
- DTEMPL stops calculation for the current time step if the difference between the particle and gas phase temperature is less than DTEMPL.

DTEMPL stops calculation for the current time step if the difference between the particle and gas phase temperature is less than DTEMPL.

DTGLMT recalculates the time step if the temperature rise of the gas phase or the particles is greater than DTGLMT.

DTSET is the time step used for the first iteration if JFLAG is equal to 1.

EC(1) is the activation energy for heterogeneous reaction 1.

EC(2) is the activation energy for heterogeneous reaction 2.

EC(3) is the activation energy for heterogeneous reaction 3.

EC(4) is the activation energy for heterogeneous reaction 4.

ECO is the activation energy for the oxidation of carbon monoxide in the gas phase.

EV(1) is the activation energy for competing route 1.

EV(2) is the activation energy for competing route 2.

EVG is the activation energy for the oxidation of volatiles in the gas phase.

FNXI is the number of space steps.

FREEL is the mean free length between molecules in the gas phase.

H is the hydrogen mass fraction in the coal.

HCOAL is the heating value of the coal.

HPYR(1) is the latent heat of reaction for pyrolysis route 1.

HPYR(2) is the latent heat of reaction for pyrolysis route 2.

ICHAR is a switch which determines whether coal or char combustion is simulated.

IMETHD allows one to use other numerical methods if desired (for upwind scheme IMETHD=1)

IOXDCO is the integer of OXDCO.

IOXDV is the integer of OXDSV.

ISOOT controls whether soot production is modelled or not.

ISTEDY controls whether steady state is to be modelled or not.

ISTEP is the number of time steps between print outs.

JFLAG determines whether DTSTEP is to be used as an initial time step or not.

IVOLS determines whether or not volatiles are consumed in-situ.

LAMBDA is the conductivity of the gas phase.

N is the nitrogen mass fraction in the coal.

NITERM is the maximum number of time steps allowed.

NCO is the order of reaction of carbon monoxide with respect to the oxidation of carbon monoxide in the gas phase.

NCO2 is the order of reaction of carbon dioxide with respect to reaction 3.

NO21 is the order of reaction of oxygen with respect to reaction 1.

NO22 is the order of reaction of oxygen with respect to reaction 2.

NO2CO is the is the order of reaction of oxygen with respect to the oxidation of carbon monoxide in the gas phase.

NO2V is the order of reaction for oxygen with respect to the oxidation of volatiles in the gas phase.

NH2O4 is the order of reaction of water with respect to reaction 4.

NH2OCO is the is the order of reaction of water with respect to the oxidation of carbon monoxide in the gas phase.

NPS(I) is the particle number density for size group I.

NSIZE is the number of size distributions of particles within the cloud.

NU is the Nusselt number.

NV is the order of reaction for volatiles with respect to the oxidation of volatiles in the gas phase.

O is the oxygen mass fraction in the coal.

OXDCO is a switch which can freeze the oxidation of carbon monoxide in the gas phase.

OXDSV is a switch which freezes the oxidation of volatiles.

PGSAT is the saturation pressure of water.

PRESS is the pressure.

RC is the initial cloud radius.

RHOD is the product of ρ and the diffusivity.

RHOPO is the initial coal density.

TO is the initial particle temperature.

TFLAME determines when to shift to the thin flame model.

TGCO is the initial temperature of the gas phase inside the cloud.

TINF is the ambient temperature of the surrounding the cloud.

TOUMAX is the maximum value allowed for τ .

TREF is the reference temperature.

TSUR is the temperature of the radiative surroundings.

VM(1) is the maximum yield allowed via competing reaction route 1.

VM(2) is the maximum yield allowed via competing reaction route 2.

XIMAX is the maximum value of ξ .

YCO2CO is the initial carbon dioxide mass fraction inside the cloud.

YCO2IN is the mass fraction of carbon dioxide in the ambience.

YCOCO is the initial carbon monoxide mass fraction inside the cloud.

YCOINF is the mass fraction of carbon monoxide in the ambience.

YO2CO is the initial oxygen mass fraction inside the cloud.

YO2INF is the mass fraction of oxygen in the ambience.

YVCO is the initial mass fraction of low temperature volatiles inside the cloud.

YVINF is the mass fraction of low temperature volatiles in the ambience.

YV2CO is the initial mass fraction of high temperature volatiles inside the cloud.

YV2INF is the mass fraction of high temperature volatiles in the ambience.

Table 5.1 Input for Transient Results

Computer Variable		Symbol	Units
AMBDATA (Ambient Data)			
TINF	= 1500.00	T_{∞}	K
YO2INF	= 0000.23	$Y_{O_2,\infty}$	
YCO2IN	= 0000.00	$Y_{CO_2,\infty}$	
YCOINF	= 0000.00	$Y_{CO,\infty}$	
YVIN	= 0000.00	$Y_{V,\infty}$	
YH2OIN	= 0000.00	$Y_{H_2O,\infty}$	
TO	= 300.00	T_0	K
TGCO	= 300.00	$T_{g,0}$	
YO2CO	= 0000.23	$Y_{O_2,0}$	
YCO2CO	= 0000.00	$Y_{CO_2,0}$	
YCOCO	= 0000.00	$Y_{CO,0}$	
YVCO	= 0000.00	$Y_{V,0}$	
YH2OIN	= 0000.00	Y_{H_2O}	
PRESS	= 0001.00	P	bars
PGSAT	= 0000.03	P_{H_2O}	bars
COALDATA (Coal Data)			
C	= 0.833		
H	= 0.056		
N	= 0.0		
O	= 0.111		
HCOAL	= 3.4×10^4		
SPRAYDATA (Spray Data)			
DP	= 100×10^{-6}	d_p	m
RC	= 1×10^{-2}	R_c	m
RHOPO	= 1.3×10^3	$\rho_{p,0}$	kg/m ³
INTEGDATA (Integer Data)			
NSIZE	= 1		
NITERN	= 90000		
ISTEP	= 1		
IMETHD	= 1		
SIZEDATA (Size Data)			
DPO(I)	= 0.1×10^{-3}		m
NPS(I)	= 0.16×10^{10}		particles/m ³
RHOPO(I)	= 0.13×10^4		kg/m ³

Table 5.1 (continued)

COMPRDATA (Competing Reactions Pyrolysis Data)

VM(1)	= 0.4	α_1	
VM(2)	= 0.8	α_2	
EV(1)	= 7.37×10^4	$E_{V,1}$	kJ/K mole
EV(2)	= 25.1×10^4	$E_{V,2}$	kJ/K mole
BV(1)	= 3.7×10^5	$B_{V,1}$	kJ/s
BV(2)	= 1.46×10^{13}	$B_{V,2}$	kJ/s
HPYR(1)	= -0.837×10^3	$h_{p,1}$	kJ/kg
HPYR(2)	= -1.67×10^3	$h_{p,2}$	kJ/kg

CHARDATA (Char Kinetics Data)

EC(1)	= 0.664×10^5	$E_{C,1}$	kJ/K kmole
EC(2)	= 0.0	$E_{C,2}$	kJ/K kmole
EC(3)	= 1.09×10^5	$E_{C,3}$	kJ/K kmole
EC(4)	= 0.0	$E_{C,4}$	kJ/K kmole
NO21	= 1.0	$n_{O_2,1}$	
NO22	= 1.0	$n_{O_2,2}$	
NCO2	= 1.0	n_{CO}	
NH2O4	= 1.0	n_{H_2O}	
EC(1)	= 0.45×10^3	$B_{C,1}$	m/s
EC(2)	= 0.0	$B_{C,2}$	m/s
EC(3)	= 0.39×10^3	$B_{C,3}$	m/s
EC(4)	= 0.0	$B_{C,4}$	m/s

NUMERDATA (Numerical Data)

XIMAX	= 3.0	ξ_{max}	
TOUMAX	= 3.0	τ_{max}	
FNXI	= 30	# of space steps	
DTEMPL	= 1.0		
DTGLMT	= 30.0		
DTSET	= 0.1×10^{-3}		

GASPRP (Free Stream Gas Properties)

RHOD	= 0.5×10^{-4}	ρD	kg/ms
CP	= 1.18	C_p	kJ, kgK
LAMBDA	= 0.59×10^{-4}	λ	kW/mK
NU	= 2.0	Nu	
FREEL	= 0.1×10^{-6}	l	m

Table 5.1 (continued)

COKINDATA (CO-Oxidation Kinetics Data)

ACO	$= 0.5 \times 10^{10}$	A_{CO}	m^3/kgs
ECO	$= 0.126 \times 10^6$	E_{CO}	$kJ/K \text{ mole}$
NCO	$= 1.0$	N_{CO}	
NO2CO	$= 0.5$	$N_{O_2,CO}$	
NH2OCO	$= 0.5$	$N_{H_2O,CO}$	

VOLKINDATA (Volatile Kinetics Data)

AVG	$= 0.5 \times 10^{10}$	$A_{V,g}$	m^3/kgs
EVG	$= 0.126 \times 10^6$	$E_{V,g}$	$kJ/K \text{ mole}$
NV	$= 1.0$	N_V	
NO2V	$= 1.0$	$N_{O_2,V}$	
OXDSV	$= 0.0$	On/Off switch for volatiles	

PROGCONTROLDATA (Program Control Data)

ICHAR	$= 0$	Coal is considered
IOXDV	$= 1$	Volatile oxidation is on
IOXDCC	$= 1$	CO oxidation is on
ISOOT	$= 0$	Soot formation is off
ISTEDY	$= 0$	Transient Problem
JFLAG	$= 0$	Initial time step is externally set
IVOLS	$= 0$	In-situ volatile oxidation is off

REFCON (Reference Conditions)

TREF	$= 300.0$	T_{ref}	K
------	-----------	-----------	---

The justification for the chosen values is as follows

The ambient temperature (T_{INF}) was selected as 1500 K since this is representative of typical boiler burner temperatures. 300 K was selected for the in cloud gas phase temperature (T_{GCO}) and for the particle temperature (T_0) since the cloud was assumed to be approximately at room temperature initially. 0.23 was selected for ambient oxygen mass fraction (Y_{O2INF}) and the cloud oxygen mass fraction (Y_{O2CO}) since this is the oxygen mass fraction of air. The pressure (P_{RESS}) was chosen to be atmospheric pressure. The coal mass fractions, (C, H, and O) coal density ($RHOP_0$), and coal heating value ($HCOAL$) were selected to represent a bituminous coal. $100\text{ }\mu\text{m}$ was chosen for the particle diameter (DP) since this is a typical pulverized coal particle diameter. 1 cm was used for the cloud radius (RC) since this is approximately the average diameter of the cylindrical cloud in laminar flow reactor studies. The particle number density (NPS) was selected in order to have the G-number equal 100 for the given particle diameter and cloud radius. Typical air properties were selected for the gas phase properties. The competing reaction pyrolysis kinetics were taken from Ubhayakar [1979]. The heterogeneous char oxidation kinetics were taken from Smith [1971]. The gas phase oxidation kinetics of CO was taken from Howard [1973]. The same oxidation kinetics are used for the volatile oxidation kinetics (see assumption (xi), chapter 4). Since our distance variable ξ is the reciprocal radius, we could not go to the center of the cloud since $\xi \rightarrow \infty$. The maximum value of xi used was 3. Thus the portion of the cloud within $r = R_c/3$ was neglected. However, this portion of the cloud is only 3% of the total cloud volume.

CHAPTER VI

RESULTS AND DISCUSSION

Prior to presenting the detailed results, the physical processes occurring during the heat up, ignition and combustion of a cloud of particles can be described. Consider a cold cloud ($T \approx 300\text{K}$) of coal particles. As soon as the cloud is placed in a hot furnace, a thermal wave propagates in side and heats up the gas in the cloud. The gas inturn heats up the particles. The particles release volatiles. Temperature and volatile concentration profiles are qualitatively similar to those shown in figure 6.1. If the local volatiles and oxygen concentrations and local temperature, at say $r = r_{ign}$, are such that a flammable mixture can be formed, then ignition occurs at $r = r_{ign}$.

Once ignited, the local temperature rises rapidly and subsequently a thin flame is formed outside the cloud as shown in figure 4.1. Combustion continues until all the volatiles are consumed, then char combustion occurs. If oxygen is absent in both the cloud and the ambience, then heat up and pyrolysis occur. Even though particles are present, they are assumed to point sources in that the temperature and volatile profiles in the cloud as shown in fig. 6.1 essentially refer to the gaseous region.

The results and discussion will be presented in the following order:

- 1.) Group combustion number definitions,
- 2.) Transient processes occuring during pulverized coal cloud combustion,
- 3.) Pyrolysis with and without radiation to/from the particles,
- 4.) Ignition with and without radiation to/from the particles, and
- 5.) Combustion.

Figure 6.1. Temperature and Volatile Concentration Profiles

6.1. Group Combustion Number G

The primary parameter used to correlate the QS cloud results is the group combustion number introduced by Chiu and Liu. The G-number definitions in various forms are summarized in Table 6.1. For a monosized cloud,

$$G_1 = G = 3 \times \frac{\text{fuel volume fraction} \times \text{cloud surface area}}{\text{particle surface area}} \quad (6.1b)$$

Writing the fuel volume fraction in terms of fuel particle size and number density,

$$G = 4\pi n a R_c^2 \quad (6.1a)$$

Alternatively the G-number can be interpreted as

$$G \approx \frac{\text{MTBP}}{\text{MTAC}} \quad (6.1a)$$

where

MTBP is the mass transfer between the bulk gas and all of the particles within the cloud and

MTAC is the mass transfer between the ambience and the cloud surface.

Subsequent results for steady stated combustion can be discussed with the interpretation of G-number either from equation (6.1a) or (6.1i). Equation (6.1i) is suitable for identifying the regimes of combustion under steady state conditions. If the rate of transport between the ambience and the cloud surface (MTAC) is very fast compared to the total transport rate between the bulk phase and all the particles in the cloud (MTBC, which depends on the total number of particles within the cloud), then the G-number is low, and the IPC model can be adopted (Figure 2.2a). If the transport rate between the ambience and the cloud surface is very slow compared to the total transport between the bulk phase and all the particles in the cloud, then the G-number is high and the SC model can be adopted (Figure 2.2f). A phenomenological approach can be applied to determine a criteria for group combustion. Consider the quasi-steady

Table 6.1. G Number Definitions in Various Forms

1. No of particles/m³

$$G = 4\pi n a R_c^2 \approx (\text{MTBP}/\text{MTAC}) \quad (6.1a)$$

2. Fuel volume fraction

$$G = 3\sigma (R_c^2/a^2) = 3 \times \frac{\text{fuel volume fraction} \times \text{cloud surface area}}{\text{particle surface area}} \quad (6.1b)$$

$$\sigma = [\text{fuel flow rate of fuel}/\rho_F] / [(\text{gas flow rate of gas}/\rho_g)] \quad (6.1c)$$

3. Total number of particles in the cloud (N) within a radius R_c

$$G = 3N(a/R_c) \quad (6.1d)$$

4. Total number of particles and interparticle separation distance [Ryan et al., 1986]

$$G \approx 6F_p^{1/3} N^{2/3} / (l/a) \quad (6.1e)$$

$$G \approx 24F_p (R_c/a)^2 / (l/a)^3 \quad (6.1f)$$

where F_p is the packing factor for spheres of diameter " l "

5. Total mass of the cloud

$$G = 9m_{\text{cloud}} / (4\pi a^2 \rho_p R_c) = 3(R_c/a)^2 (\rho_{cl}/\rho_p) \quad (6.1g)$$

where m_{cloud} is the total mass of the particles in the cloud.

6. Fuel particle loading

$$G = 3(Y_{p,c} \rho_g / \rho_p) (R_c^2/a^2) \quad (6.1h)$$

where $Y_{p,c}$ is the mass fraction of particles in the cloud.

7. Gas/Fuel Ratio in the Cloud

$$G = 3 \left[\frac{(\rho_g/\rho_p) (R_c^2/a^2)}{(m_g/m_{p,\text{cloud}})} \right] = 2.089 \left[\frac{(m_{\text{cloud}})^{2/3}}{a^2 (l/a) \rho_p^{2/3}} \right] \quad (6.1i)$$

8. G for Laminar Flow Reactors

$$G = 3 \left[\frac{\rho_g Y_{O_2} R_d^2}{(a^2 \rho_p (\dot{m}_{O_2}/\dot{m}_p))} \right] \quad (6.1j)$$

where R_d is the duct radius, Y_{O_2} is the oxygen mass fraction, and $\dot{m}_p$ is the particle mass flow rate.

combustion of a spherical cloud of coal particles. GC will exist if the velocity of the gases traveling out of the cloud is greater than the diffusion velocity of oxygen trying to enter the cloud. If each drop produces a mass flow rate of $\dot{m}_s$, then the total mass flow out of a cloud of radius R_c is given as $4/3\pi n R_c^3 \dot{m}_s$. Hence the net convective velocity is given as

$$v_c = \left(\frac{(4/3)\pi n R_c^3 \dot{m}_s}{4\pi R_c^2 \rho} \right) = \left(\frac{n R_c \dot{m}_s}{3\rho} \right) \quad (6.2)$$

The diffusion velocity of oxygen from outside of the cloud can be given as

$$v_d \approx \left(\frac{D}{R_c} \right) \quad (6.3)$$

If $v_c > v_d$, then the mass flow out of the cloud will prevent the diffusion of oxygen into the cloud. Thus for group combustion

$$v_c > v_d \quad (6.4)$$

Substituting eqs. (6.2) and (6.3) in eq. (6.4) and reducing yields

$$\frac{n R_c^2 \dot{m}_s}{\rho D} > 3 \quad (6.5)$$

Since $\dot{m}_s \approx 4\pi\rho Da$, eq. (6.5) becomes

$$4\pi n a R_c^2 > 3 \quad (6.6)$$

Note that the left hand side of eq. (6.6) is identical to eq. (6.1a) for G-number. Thus group combustion occurs if *

$$G > 3 \quad (6.7)$$

Even though G-number are used to correlate the QS results, they can still be used to interpret the non-steady (NS) results.

* Actually for liquid drops GC occurs if $G > 0.1$ and at $G > 1.0$ for char combustion, since the blowing will reduce the diffusion velocity v_d (eq. 6.3).

Transient Processes Occuring During P.C. Cloud Combustion

Once a cold cloud of particles is introduced into a hot oxidizing atmosphere, heat is transferred from the surroundings into the cloud and a "thermal wave" begins to penetrate in the cloud. As the thermal wave heats the gas phase surrounding the particles, the particles begin to heat. As the particles heat, volatiles are released in the bulk gas phase of the cloud, which then diffuse both toward the ambience and the center of the cloud. If the cloud is dense enough, the volatiles will ignite in the gas phase outside the cloud. Once ignition has taken place the volatiles oxide rapidly and the flame moves toward the cloud. Upon reaching the surface of the cloud, the coal (char, if completely devolitized) particles begin to burn in addition to the volatiles in the gas phase. Once all the volatiles in the gas phase complete burning, the remaining char particles burn heterogenously until extinction occurs.

6.2. Pyrolysis of Coal Particles

Pyrolysis was modelled using the competing reaction model (sec. 4.3.2.1.1). The ambient and cloud mass fractions of oxygen were set to zero so that the gas phase oxidation reactions can be frozen. The ambient temperature and the initial G-number (i.e. the number density of particles) were varied. The other data remains unchanged. Note that the G-number is not expected to vary during pyrolysis since the particle diameter and the number density remain constant.

Consider the ASTM test method for the proximate annalysis of coal (D3175). This method involves placing a covered platinum crucible containing 1 gm. of coal in an oven at 1200K for 7 minutes. For bituminous coals the ASTM method yields a value of approximately 40% volatile matter (termed proximate yield). The heating rate in such experiments is low due to the dense packing of the particles, resulting in low yields. Experiments in suspension mode (dilute cloud) indicate volatile yields exceeding 70% [Stickler et al., 1974].

For pure pyrolysis the time to complete devolatilization (pyrolysis time) can be expressed as

$$t_{pyr} = t_{th} + t_{h,p} + t_{cp} \quad (6.8)$$

where

t_{th} is the time required for heat to penetrate into the cloud,

$t_{h,p}$ is the time required for the particles to heat to the point where volatiles are liberated,

$t_{c,p}$ is the chemical time for pyrolysis.

6.2.1. No Radiation

The effect of particle diameter, cloud radius, particle number density, ambient temperature, and initial cloud gas phase temperature is presented in this section.

6.2.1.1. Pyrolysis Results for an Initially Cold Cloud

Figure 6.2 shows typical temperature, density, and volatile mass fraction profiles for a cloud of coal particles which is undergoing pyrolysis. The thermal wave has penetrated into the cloud and the particles at the outer edge of the cloud have completely pyrolysed while those in the center have just begun to pyrolyse.

Effect of Temperature and G-number

Results are presented for ambient temperatures of 1400K and 2800K for a dilute cloud ($G = 1$, $n = 1.6 \times 10^7$ particles/m³, $(l/a) \approx 90$, $R_c = 1.0 \times 10^{-2}$ m, $d_p = 100 \times 10^{-6}$ m) and a dense cloud ($G = 100$, $n = 1.6 \times 10^9$ particles/m³, $(l/a) \approx 20$, $R_c = 1.0 \times 10^{-2}$ m, $d_p = 100 \times 10^{-6}$ m). Initial gas and particle temperatures inside the cloud were set at 300K (Fig. 6.3). For $G = 1$, the cloud heats up rapidly and the time to complete the pyrolysis of all the particles in

Figure 6.2. Typical Temperature, Density and Volatile Profiles for Pyrolysis

Figure 6.3. Volatile Yield Time Histories

the cloud ranged from 0.28 s for an ambient temperature of 2800K to 0.50 s for an ambient temperature of 1400K. For $G = 100$, the cloud heats up slowly since the cloud is dense and the time to complete pyrolysis ranged from 0.52 s at an ambient temperature of 2800K to 0.91 s for an ambient temperature of 1400K. Thus it is apparent that the increased heat sink due to the increased particle number density ($G=100$) almost doubles the pyrolysis time scales. More importantly, the maximum volatile yield obtained was only 40.9% (only slightly greater than proximate yield). Thus the maximum value of the overall "Q" factor was 1.023. Results were also obtained for $G=1$ and $G=100$ for a particle diameter of $20\mu\text{m}$ (not shown). The ambient and cloud conditions were the same as for the previous case of $d_p = 100\mu\text{m}$. The maximum value of the "Q" factor obtained was only 1.025 which is only slightly greater than the maximum value previously obtained. This implies that the pyrolysis of a 1 cm. cold cloud of pulverized coal particles is controlled primarily by the thermal wave penetration time rather than the particle heatup time. Thus, by the time the particles reach a high enough temperature to release significant amounts of volatiles through the high yield route (V_{II} , section 4.3.2.1.1) the hydrogen and oxygen contents of the coal have been completely depleted via the low yield route (V_I). Thus it can be deduced that, for a cold 1 cm. cloud of coal particles introduced into a hot inert atmosphere the volatile yield is nearly independent of ambient temperature and G-number and volatile yields of approximately of 40% are to be expected.

For an ambient temperature of 2800K, the time to complete pyrolysis ranged from 0.24 s ($G=1$) to 0.25 s ($G=100$). Since $G = 3\sigma(R_c^2/a^2)$, decreasing the particle diameter by a factor of 5 while holding the G-number constant results in a decrease in the cloud fuel volume fraction by a factor of 25. Thus for a particle radius of $50\mu\text{m}$ the heat capacity of the particles within the cloud

is 25 times greater than that for a cloud of $20\mu\text{m}$ particles. Thus, while the $20\mu\text{m}$ particles do not have a significant effect on the thermal wave penetration time as G is varied from 1 to 100, the larger particles slow down the penetration rate since the heat capacity of the cloud containing larger particles is significant compared to the heat capacity of the gas phase in the cloud.

Pyrolysis Propagation Rate

The volatile yield time histories shown in figure 6.2 reveal the total time required to pyrolyse the entire cloud of particles. It provides no information of the volatile yield histories of particles in the cloud. Figure 6.4 shows the variation in particle density with time for various locations in the cloud.

This output was generated with the proximate volatile yield (α_1) set to 0.4 and the yield due to the secondary reaction (α_2) set to 0.0. This was done in order to determine the propagation rate of pyrolysis. As can be seen, the density of the particles in the cloud approaches 780 kg/m^3 as they should. Pyrolysis time is approximately 20 ms for particles at the periphery of the cloud and 200 ms for particles at the center of the cloud.

Results (not shown) were also generated assuming $\alpha_1 = 0$ and $\alpha_2 = 0.8$. These were similar, however they converged to 260 kg/m^3 (as they should).

Effect of Cloud Radius

The effect of cloud radius (injector radius in the laminar flow reactors) on volatile yield was studied. Ambient temperature was set at 2800K and the initial cloud temperature was 300K. For a dilute cloud ($G = 1$), volatile yield increases significantly with decreasing cloud radius (Figure 6.5a). This is due to the increase in the surface area to volume ratio resulting in higher heating rates for smaller clouds. The volatile yield is less dependent on the cloud radius for denser clouds ($G = 100$). This results since a higher G -number implies a greater

Figure 6.4. Pyrolysis Propagation Rate

heat sink per unit volume, thus the heating rate (and volatile yield) is reduced. Figures 6.5b and 6.5c show the time histories of volatile yield for various cloud radii.

6.2.1.2. Pyrolysis Results for an Initially Hot Cloud

In section 6.2.1.1, the heating rate and hence volatile yield was controlled by the thermal wave penetration time into the cloud. In order to determine the effect of particle heat up time on pyrolysis, results were generated with the initial cloud and ambient temperature being equal, while the initial particle temperature is set at 300K.

Effect of Particle Size

The initial cloud and ambient gas phase temperatures were set to 2800K. Results were generated for particle radii varying from 20 to 100 microns (Figure 6.6). The volatile yields obtained were 71.5% for the smaller sized particles (20 μm) and 49.2% for the larger sized particles (100 μm). This is significantly larger than the volatile yields previously obtained for an initially cold cloud ($\approx 40\%$).

Effect of Temperature

Next, the dependence of volatile yield on G-number was investigated for a number of ambient temperatures. The G-number was varied from 1 to 250, (by varying the fuel volume fraction) while the particle diameter and cloud radius were held constant at 20 microns and 1 cm, respectively. Volatile yield was relatively insensitive to G-number at high temperatures since the particles throughout the cloud are uniformly heated (Figure 6.7). At lower temperatures, volatile yields decrease significantly as the G-number increases. This is due to the increased coal loading cooling the cloud to a temperature at which the yield due to volatile reaction V_{II} is hindered.

Figure 6.5a. Effect of Cloud Radius on Volatile Yield

Figure 6.5b. Volatile Yield Time Histories for Various Cloud Radii ($G = 100$)

Figure 6.5c. Volatile Yield Time Histories for Various Cloud Radii ($G = 1$)

Figure 6.6. Effect of Particle Diameter on Volatile Yield

Figure 6.7. Effect of G-number on Volatile Yield for Various Free Stream Temperatures

6.2.2. Effects of Radiation

The emissivity of coal is close to unity and as such radiation effects may be significant in the heating of coal particles and thus ultimate volatile yield.

6.2.2.1. Initially Cold Cloud and Ambience

Runs were made for various radiative temperatures and cloud conditions while holding the initial cloud and ambient temperatures at 300K. This was done to simulate devolatilization of coal particles in an environment which does not promote cracking of released volatiles. In order to emphasize the second pyrolysis route (V_{II}) in the competing reaction model, a radiative temperature of 3000K was chosen as the base temperature for these plots. Results are also presented for a radiative temperature of 2000K (No runs were made below 1800K since the volatile yield is slightly in excess of proximate yield).

Consider an energy balance for an individual particle. This is expressed as

$$mC_p (\partial T / \partial t) = \epsilon \sigma A (T_{rad}^4 - T_p^4) - hA (T_p - T_g) \quad (6.9)$$

where T_p is the particle temperature,

T_g is the gas phase temperature surrounding the particle,

and T_{rad} is the temperature of the radiative surroundings.

Since $h \propto Nu/a$, eq. (6.9) can be rewritten as

$$k_1 a (\partial T / \partial t) = k_3 (T_{rad}^4 - T_p^4) - k_2 / a (T_g - T_p) \quad (6.10)$$

where a is the particle radius.

From eq. (6.10), it can be seen that the first term represents the heat capacity of the particle, the second term represents the heat gain/loss due to radiative heating, and the third term represents the heat loss/gain due to convective heating.

Figure 6.8 shows the effect of particle diameter on volatile yield in a radiative environment for G-numbers of 1 and 100. Since $G = 4\pi n a R_c^2$, these conditions imply increasing of the particle number density by a factor of k when the particle diameter is decreased by a factor of k (also a constant convective heat loss/gain for a given T_p and T_g). Under these conditions it is seen that particle diameter is the controlling factor in maximizing volatile yield since the maximum yield for both clouds is obtained for a particle diameter of approximately $40 \mu\text{m}$. Rewriting eq. (6.10) as

$$k_1 a^2 (\partial T / \partial t) = k_3 a (T_{rad}^4 - T_p^4) - k_2 (T_g - T_p) \quad (6.11)$$

we see that for small particle diameters the radiative heat gain term ($\propto a$) is small compared to the constant convective heat loss term. This results in slow heating of the particles and a relatively low yield. As the particle radius is increased, the radiative term increases in comparison to the convective term and the particles heat faster resulting in increased yields until an optimum particle diameter is reached ($d_p \approx 40 \mu\text{m}$). Beyond this particle diameter, the heat capacity of the particle ($\propto a^2$) becomes large and limits the heating rate of the particles and yields decrease again.

Referring to Figure 6.9, volatile yield has been plotted for various particle diameters while holding the fuel volume fraction constant ($\sigma = 5.3 \times 10^{-5}$, this corresponds to $R_c = 1 \text{ cm}$, $d_p = 40.0 \mu\text{m}$ and $G = 100$ of figure 6.8). In practical situations, this condition implies a constant coal mass flow rate or cloud heat capacity. These results suggest that for a process which has a constant rate of coal mass flow, increased pulverization is desired to maximize volatile yield for the range of diameters studied.

Figure 6.10 is a plot of the effect of particle diameter on volatile yield while the total particle surface area has been held constant (corresponding to $d_p =$

Figure 6.8. Effect of Particle Diameter on Volatile Yield, Constant G-number

Figure 6.9. Effect of Particle Diameter on Volatile Yield, Constant Fuel Volume Fraction

Figure 6.10. Effect of Particle Diameter on Volatile Yield, Constant Particle Surface Area

$40\ \mu\text{m}$, $R_c = 1\ \text{cm}$, and $G = 100^*$). This condition implies constant radiative heating for a given T_p and T_{rad} . Referring to eq. (6.10), for small particle diameters the convective term is large in comparison to the radiative term thus relatively low yields are obtained. As the particle diameter is increased, the convective term decreases and the heat capacity of the particle increases. Thus an optimum value of particle diameter exists below which convective heat loss slows the heating of the particle and above which the heat capacity of the particle limits the heating.

Next, Figure 6.11 shows the effect of cloud radius on volatile yield for two G -numbers and cloud radii. These conditions imply that for a given particle diameter, the particle number density is the same for both clouds. A slightly larger volatile yield is observed for the larger cloud (It is noticed that this is the opposite of the trends for an initially cold cloud) since the larger cloud has a smaller outer surface area to volume ratio. This lowers the heat loss to the ambience and effectively shields the inner particles from conduction but not radiation.

Figure 6.12 shows the dependency of volatile yield on the radiative temperature. The cloud conditions (i.e. $d_p = 40\ \mu\text{m}$, $G=100$, and $R_c = 1\ \text{cm}$) were chosen since they provided the maximum yield at $T_{\text{rad}} = 3000\text{K}$. At a temperature of 1800K , volatile yield is only 6% in excess of proximate volatile yield. Thus, no results were obtained for temperatures lower than 1800K .

Finally, figure 6.13 is a plot of shows the effect of particle diameter on volatile yield for a radiative temperature of 2000K and $G = 100$. We note that the optimum particle diameter has increased to $\approx 50\ \mu\text{m}$ (referring to figure 6.8

* This corresponds to the conditions which resulted in maximum volatile yield on figure 6.8

Figure 6.11. Effect of Particle Diameter on Volatile Yield, Cloud Radius Dependence

Figure 6.12. Effect of Radiative Temperature on Volatile Yield

Figure 6.13. Effect of Particle Diameter on Volatile Yield

the optimum particle diameter was approximately $40\text{ }\mu\text{m}$). Once again referring to eq. (6.11), we can see that such a result is due to a smaller radiative heat input, thus requiring a larger particle diameter for the radiative term to dominate the convective term.

Experimental Correlation

For an initially hot cloud, the difference between IPP (Individual Particle Pyrolysis) and GP (Group Pyrolysis) models is that there is a blowing effect in the latter model which prevents the penetration of heat from the surrounding ambience. Then as the particles pyrolyse the cloud model traces the reduction in the gas temperature surrounding the particles. Since the G-number is very low for Kobayashi's [1972] experiments, group effects are not expected to play a major role and as such pyrolysis is controlled by the IPP model. Figure 6.14 shows the comparison of the present results for volatile yield time histories for various ambient temperatures ($T_\infty = T_{g,c,0}$).

6.3. Ignition of Coal Particles

Introduction to the Problem

Ignition of a cloud of coal particles has been known to occur by two modes. The first mode, heterogeneous ignition, refers to ignition of the carbon and in-situ volatile matter. The other mode, homogeneous ignition, called the Faraday mechanism occurs when volatiles in the gas phase ignite. Single particle studies show that heterogeneous ignition normally occurs for larger sized particles [Annamalai and Durbetaki, 1977].

The processes occurring during the transient ignition of a cloud of coal particles can be visualized as a combination of the thermal wave penetration time (t_{th}), the particle heat-up time (t_h), flammable mixture formation time (t_f), and the induction time (t_i).

Figure 6.14. Kobayashi's [1972] Experimental Data

Thus ignition is homogeneous if

$$t_{th} + t_{h,p} + t_f + t_{i,g} < t_{th} + t_{h,s} + t_{i,s} \quad (6.12)$$

Ignition time can be expressed as

$$t_{ign} = t_{th} + t_{h,p} + t_f + t_{i,g} \quad (\text{homogeneous ignition}) \quad (6.12a)$$

$$t_{ign} = t_{th} + t_{h,s} + t_{i,g} \quad (\text{heterogeneous ignition}) \quad (6.12b)$$

Where

t_{th} is the time required for heat to penetrate into the cloud,

$t_{h,p}$ is the time required for the particles to heat to the point where volatiles are liberated,

$t_{h,s}$ is the time required to heat the particles to a point at which heterogeneous reactions (or surface reactions) become significant,

t_f is the time required for a flammable mixture to be formed in the gas phase once the particles begin to release volatiles,

$t_{i,g}$ is defined as the induction time in the gas phase (homogeneous ignition),

and

$t_{i,s}$ is defined as the induction time in the for heterogeneous (surface) reactions (heterogeneous ignition).

Although single particle studies may be useful for the study of ignition and combustion of dilute sprays, its application is limited since most industrial spray burners use very dense clouds and ignition occurs in the vicinity of the burner where the cloud is dense. The fundamental experiments on coal ignition and combustion involve

- i.) a single particle [Golovina, 1962; Kurylko and Essenhigh, 1973; Ragaland, 1985],

- ii.) a stream of particles as in laminar flow reactors [Hamor et al., 1973; Midkiff et al., 1986; Niksa et al. 1986], and
- iii.) a batch of coal/char particles introduced in furnaces [Chen et al. 1984] and in shock tubes [Seeker et al., 1979].

The ignition experiments conducted on a cloud of metal particles reveal lower ignition temperatures with increasing dust concentration and ignition temperatures of a dust cloud which are lower than those of isolated particles [Cassell and Liebman, 1959]. Recent experiments of Chen et al. [1984] on a cloud of char and coal particles reveal ignition temperatures of 620K to 700K while the single particle experiments yield values around 1050 to 1200K. The QS cloud ignition model of Krishna and Berlad [1980] for a cloud of char particles reveal a lower ignition temperature. The group combustion models, which have been proposed for obtaining the ignition and combustion characteristics of a cloud of liquid drops, reveal lower ignition temperatures (750K) compared to the ignition temperature of isolated drops [Annamalai et al., 1984]. The present section deals with the development of a group ignition model for a cloud of coal particles and presents the ignition results for both dilute and dense clouds. Qualitative comparisons of the results with experimental findings are given.

6.3.1. No Radiation

6.3.1.1. Ignition Results for an Initially Cold Cloud

Ignition Criteria

The classical Semenov's thermal theory of ignition involves i) the equality of the heat generation to the heat loss and ii) the equality of the rate of change of heat generation with temperature to the rate of change of heat loss with temperature. As such the theory provides the conventional S-type stationary solution

to the problem (Fig. 6.15). The steady state solution provides information on the minimum ignition temperature to ignite the particle irrespective of any time limitation. In practical systems, the residence time is limited. If a laminar flow reactor is used, the condition of no ignition within the fixed residence time is construed as the particle being unignitable at the given gas temperature (T_g). Even though the gas temperature may be higher than the required gas temperature at ignition ($T_{g,i}$) evaluated under steady state conditions, the particle was non-ignitable because of the limitations in residence time! Thus a transient analysis is more realistic than a steady state analysis since most combustion devices are time limited.

Single particle ignition studies on coal/char particles define the onset of ignition as a point at which the temperature rises rapidly with time. This implies that the heat generation rate is higher than the heat loss rate. One can apply a similar physical principle to the ignition of a coal dust cloud. The particle and gas phase temperatures are tracked as a function of time. Thus, if the particle temperature rises above its surrounding gas temperature (i.e. when the local heat generation rate is higher than the local heat loss rate from the particles), the cloud is said to have ignited heterogeneously (Heterogenous Ignition, HI). Similarly homogeneous ignition (Gas Ignition, GI) occurred when the gas phase temperature of a shell (a shell bounded by radii r and $r + \Delta r$) is greater than the temperature of both its adjacent shells (shells bounded by r and $r - \Delta r$, and $r + \Delta r$ and $r + 2\Delta r$) (i.e. when the local gas phase heat generation rate is higher than the heat loss by diffusion to the adjacent shells). Figure 6.16 illustrates the ignition criteria for the NS ignition of a cloud of coal particles. It is seen that the GI occurs at $t = 0.12$ s at $r = 1.111$ cm since the gas temperature jumps above the adjacent shells located at $r = 1$ and 1.25 cm. Furthermore,

Figure 6.15. Steady State Solutions for the Ignition of a Particle

homogeneous ignition occurs outside the cloud. The solid line, obtained with another set of conditions, illustrates the heterogeneous ignition criterion. At $t = 0.185$ s, the particle temperature rises above the gas temperature adjacent to the particle. Cloud ignition is termed heterogeneous if the time required for the particle temperature to rise above the local gas temperature is less than the time for a shell temperature to rise above the temperature of its adjacent shells and vice versa. Figure 6.17 is a plot of temperature profiles at various times up to ignition and figure 6.18 is a plot of gas phase component mass fractions at the time of ignition.

Effect of Coal Dust Concentration

Steady state group combustion analyses [Annamalai and Ramalingam 1987, Annamalai et al. 1988b] revealed that most of the results can be correlated with a dimensionless parameter G , called the group combustion number which is a measure of the denseness of the cloud. The dimensionless group obtained by Krishna and Berlad [1980] for the steady state ignition analysis of a uniform cloud is found to be equal to $G/3$. They obtained single char particle ignition when $G/3 \ll 1$ and cloud ignition of char particles when $G/3 \gg 1$.^{*} The G -number can be interpreted as the ratio of the mass transfer between the bulk gas and the particles within the cloud to the mass transfer between the cloud surface and ambience. In terms of cloud dimensions, such a ratio can be represented as,

$$G = 4\pi n a R_c^2 = \frac{9M_{p,c}}{(4\pi a^2 \rho_p R_c)} = 3\sigma \frac{R_c^2}{a^2} \quad (6.13)$$

^{*} The model is somewhat similar to Semenov's thermal theory of ignition. The whole cloud of radius R_c is treated like a single spherical particle of radius R_c with the density of the cloud being equal to the total mass of the particles within the cloud divided by the total volume of the cloud.

Figure 6.16. Illustration of Ignition Criteria

Figure 6.17. Temperature Profiles for Ignition

Figure 6.18. Gas Phase Mass Fractions

It should be noted that G-numbers change during combustion due to the reductions in a and R_c . However the change in G is expected to be negligible during the ignition process. As opposed to the steady state combustion/evaporation models, the non-steady results can't be correlated with a single dimensionless group, G (even though G may remain constant throughout ignition) because of the transient nature of ignition and the finite kinetics involved in the ignition process. However, it is useful in interpreting the results.

Figure 6.19 shows the effect of G-number (or coal dust concentration) on ignition time for the base case. It can be seen that for a cold cloud of 1 cm. radius suddenly introduced into a hot atmosphere, heterogeneous ignition occurs only for low G-numbers (G up to 3, IPI, Individual Particle Ignition mode). The ignition time increases weakly with G-number in this regime due to the increased coal loading slowing the heating of the cloud; this invariance of ignition time with dust concentration in this regime is indicative of heterogeneous ignition.

As the G-number increases (i.e. increasing the number of particles), there are two competing effects:

- i) the increased number of particles acts as a heat sink lowering the local gas temperature and slowing the propagation of the thermal wave and thereby causing fewer particles to participate in the pyrolysis and combustion process;
- ii) On the other hand, the increased number of particles provide more volatiles per unit volume which can rapidly form a flammable mixture resulting in decreased formation and induction times.

For low G-numbers, a flammable mixture can not be formed easily since the volatile concentration remains low due to the large volume of space fed by a small number of particles and due to diffusion away from the cloud pyrolysis

Figure 6.19. Effect of G-number on Ignition for the Base Case

zone. Thus, cloud ignition is essentially heterogeneous. For larger G-numbers ($G > 3$), the cloud ignites in the gas phase. For G-numbers up to about 50, the formation and induction times decrease more rapidly than the thermal wave penetration time increases, thereby causing the ignition time to decrease. For higher G-numbers, the thermal wave penetration time becomes dominant and the ignition time increases with an increase in dust concentration. Under this condition, one can visualize the cloud as a large single particle of radius equal to R_c and density equal to the cloud density with temperature gradients inside the particle (which is analogous to a large porous coal particle). The ignition time continues to increase as the number of particles is increased. The relation between these results and the ignition results for a laminar flow reactor type experiments can be now discussed. The laminar flow experiments involve a cylindrical stream of particles. For a fixed transport air flow rate, increased coal dust flow implies increased coal denseness and increased G-number. It has been shown that the QS combustion results for spherical and cylindrical clouds are similar; then if it is assumed that the NS results are similar for spherical or cylindrical clouds, then the ignition distance ($\propto$ ignition time for a fixed flow rate) with increasing mass flow of coal particles in a laminar flow reactor must increase weakly at first (dilute cloud, HI) then decrease (intermediate cloud, GI) and then increase again (very dense cloud, GI).

Effect of Ambient Temperature

Figure 6.20a shows that as the ambient temperature increases, the ignition time decreases since the thermal wave penetration time is greatly reduced. The size of the heterogeneous regime increases with increasing temperature. For example, at $G = 5$, ignition is heterogeneous if $T_\infty = 1100$ K. As the ambient temperature is increased, the thermal wave penetration depth may remain the same

Figure 6.20a. Effect of G-number on Ignition Time for Various Ambient Temperatures

Figure 6.20b. Effect of Ambient Temperature on Ignition Time for Various G-numbers

Figure 6.20c. Variation of Ignition Time with Reciprocal Temperature

within the time of ignition. However, the high ambient temperatures provide a high temperature environment around the reacting particles resulting in rapid char oxidation. At lower ambient temperatures, the char reactions slow down compared to the pyrolysis reactions. Thus, if pyrolysis is still significant at lower temperatures, the volatiles continue to accumulate to the flammability limit, resulting in homogeneous ignition. The G-number (or number of particles per m^3 or fuel volume fraction) corresponding to minimum ignition time also increases as temperature increases since the thermal wave penetration time becomes dominant at higher G-numbers for higher temperatures. It is also observed that the homogeneous ignition curve is flatter for higher ambient temperatures. At low temperatures ($T = 1100\text{K}$) and high G-numbers ($G > 100$), the heat capacity of the cold cloud lowers the temperature of the gas surrounding the cloud below that which significant volatile liberation can occur. The additional time required to "reheat" the surrounding gas results in rapidly increasing ignition time. For high ambient temperatures ($T = 1900\text{K}$), the temperature of the surrounding gas remains high enough to liberate volatiles and the ignition time increases only slightly. (Fig. 6.20b)

Figure 6.20c shows the variation of ignition time with reciprocal ambient temperature. Assuming that ignition time for a cloud of coal particles can be expressed by an Arrhenius type relation (i.e. $t_{\text{ign}} = k \exp(E/RT)$), one can determine apparent activation energies for dense and dilute clouds. From such an analysis, $E_{\text{dilute}} = 24,500 \text{ kJ/kmole}$ ($G=1$) and $E_{\text{dense}} = 34,000 \text{ kJ/kmole}$ ($G=100$). These activation energies are lower than the activation energies for heterogeneous reactions and gas phase volatile oxidation since the ignition time of a cloud of particles is controlled by the thermal wave penetration time.

Effect of Volatile Matter

Figure 6.21 shows the effect cloud denseness on ignition time for various proximate volatile mass fractions. The value of volatile matter used for the high temperature reaction (V_{II}) in the competing reaction model was assumed to be twice the low temperature values (V_I). For low G-numbers (dilute cloud, IPC regime), ignition time increases with increasing proximate volatile matter. This result is due to the increased heat loss resulting from the pyrolysis reactions causing the particles to heat slower. As proximate volatile matter decreases, the region of heterogeneous ignition increases as expected. At higher G-numbers, these results are the inverse of those in the heterogeneous regime. The increased proximate volatile matter results in decreased ignition time since the flammable mixture can be formed readily.

Effect of Oxygen Concentration in the Cloud

Figure 6.22 shows the effect of initial oxygen mass fraction on the dependency of ignition time with G-number. Ignition time increases with decreasing oxygen mass fraction as expected for both the heterogeneous and homogeneous regimes. This increase is greater for the heterogeneous region since oxygen is required to diffuse into the cloud for particle ignition while homogeneous ignition occurs outside the cloud where oxygen is readily available. This situation also results in a decrease in the size of the heterogeneous region.

Particle Diameter

The effect of particle diameter on ignition time was investigated in both the heterogeneous and homogeneous ignition regimes. Figure 6.23 shows the effect of fuel volume fraction at three particle diameters. Ignition time generally decreases with particle size. Also note that at $\sigma = 0.0015$, ignition switches from heterogeneous to homogeneous as the particle size increases from 50 to 100 μm .

Figure 6.21. Effect of Proximate Volatile Matter on Ignition Time

Figure 6.22. Effect of Initial Cloud O_2 Concentration on Ignition Time

Figure 6.23. Effect of Increased Pulverization on Ignition Time

Comparing the results in the heterogeneous region for the diameters studied, it can clearly be seen that the size of the heterogeneous region increases with decreasing particle size. This is due primarily to the fact that heterogeneous reactions are a surface phenomena and pyrolysis is a volumetric process. Thus, an increase in the surface area to volume ratio (i.e. decreasing particle diameter) results in a lower volatile release rate from each particle, which enhances the local oxygen concentration at the particle surface and thus results in a larger heterogeneous region. The fuel volume fraction was held constant while altering the particle diameter. It simulates the effect of pulverization on ignition characteristics for a constant mass flow rate. Under group ignition conditions, when the particle size was increased from 40 to 80 μm , ignition time increased only by 31% for the heterogeneous ignition regime (Figure 6.24a) and by 29% for the homogeneous ignition regime (Figure 6.24b). On the other hand, if the change in ignition temperature with a change in particle size is neglected for the isolated particle ignition case, then ignition time and hence the ignition distance should increase by four times when the particle diameter is doubled as if the IPC model is adopted. Thus, under group conditions and for a cold cloud, the thermal penetration time seems to dampen the sensitivity of the change in the ignition time with particle diameter.

Effect of Cloud Radius

The cloud radius is one of the significant parameters in reducing the ignition time since it reduces the thermal wave penetration time. Figure 6.25 shows the results. Reducing the cloud radius by a factor of 2, more than halves the ignition time. It has been shown in earlier works that QS results for spherical and cylindrical clouds reveal similar results for the variation of correction factor with G-number [Annamalai et al., 1988a]. Assuming that qualitatively the ignition

Figure 6.24a. Effect of Particle Diameter on Ignition Time ($\sigma = 8.33 \times 10^{-6}$)

Figure 6.24b. Effect of Particle Diameter on Ignition Time ($\sigma = 8.33 \times 10^{-4}$)

time results are applicable to a cylindrical stream of particles (as used in a laminar flow reactor), the reduction in cloud radius is equivalent to reducing the injector diameter or using multiple ports instead of a single port. Thus Figure 6.25 reveals the qualitative results when the injector diameter is altered. It is noted that the reduction in cloud radius at $n = 1.6 \times 10^7$ ($G=1$) results in the switching from HI to GI ignition modes since the heating rate is so rapid that the volatiles have little time to diffuse away resulting in the formation of a flammable mixture. Such an accumulation of volatiles leads to a reduction in the local oxygen mass fraction at the particle surface resulting in reduced surface reaction rates. Also, it can be seen that the size of the heterogeneous region decreases as the R_c is decreased. This result can be explained by considering a control volume outside of the cloud. For larger clouds in the heterogeneous region, the thermal wave penetration time is large enough that pyrolysis takes place slowly enough to allow any released volatiles to diffuse away from the cloud before a flammable mixture can be formed. However, for a smaller cloud with the same particle number density, the thermal wave penetration time is much smaller and thus pyrolysis is much more intensive and the volatiles are unable to diffuse away resulting in the rapid formation of a flammable mixture. In addition to this effect the volatiles are able to ignite closer to the cloud since the infinite gas surrounding the finite cloud is cooled less when a small cloud is introduced. These effects result in homogeneous ignition.

Relation between Ignition mode and Particle Density

Runs were made for a range of fuel volume fractions. This range corresponded to 100 micron particles with the G-number varying from 1 to 300. Ignition times and outer particle densities at the time of ignition were investigated. Figure 6.26 is a plot of the outer particle density at the time of ignition

Figure 6.25. Effect of Cloud Radius on Ignition Time

superimposed on a plot of ignition time as fuel volume fraction is varied for a 100 micron particle cloud. From this figure it can be seen that heterogeneous ignition occurred concurrently with the end of pyrolysis for all cases studied. Even though the pyrolysis occurs rapidly, the cloud is so dilute that a flammable mixture could not be formed in the gas phase. For very small G-numbers, ignition is able to occur slightly before the outer particles have completely devolatilized. This represents the point at which the endothermic heat of pyrolysis and the blockage due to the blowing of volatiles out of the cloud is overcome by the thermal wave propagating into the cloud. In addition to the decreased heat required for pyrolysis and blowing by the cloud, the particle density is at a minimum which also contributes to the rapid heating of the particle. The point at which the cloud number density is such that a flammable mixture could be formed in the gas phase corresponds to the point of minimum particle density at ignition. Beyond this point ignition is homogeneous and the cloud ignites before the outer particles have been able to completely devolatilize.

Effects of Kinetics of Reaction

The sensitivity of the results on the chemical kinetics was investigated by changing preexponential term in the Arrhenius equation for the char oxidation, pyrolysis, and gas phase oxidation kinetics.

Char Oxidation Kinetics The effect of char oxidation kinetics (heterogeneous reaction I) was investigated by dividing the preexponential factor by 10 and then multiplying by 10. Figure 6.27 shows the results when the char oxidation kinetics are altered. When the char reaction kinetics are suppressed ($B_C/10$), ignition is homogeneous for the entire range of G-numbers studied. Also ignition time increases slightly in the homogeneous range compared to base case. This is a result of the decreased reaction rate at the particle surface causing the particle to heat slower and thereby slowing pyrolysis.

Figure 6.26. Relation Between Outer Particle Density and Ignition Mode

Figure 6.27. Effect of Altering Char Oxidation Kinetics on Ignition Time

Enhancing the char oxidation kinetics by a factor of ten results in greatly decreased ignition times. Also ignition is heterogeneous for all but the most dense clouds.

Effect of Pyrolysis Kinetics Figure 6.28 shows the results when the pyrolysis kinetics are altered. When the pyrolysis kinetics are decreased by a factor of 10, the volatile liberation rate is slower. Hence the heat supplied for endothermic pyrolysis is less. Thus, the ignition time decreases in the heterogeneous region due to the decreased latent heat of pyrolysis allowing the particle to heat faster. Also the size of the heterogeneous region increases until a point is reached where the heat capacity of the cloud slows the heating of the particles thus allowing volatiles to pyrolyze and diffuse into the hot oxidizing surroundings where ignition then occurs.

When the pyrolysis kinetics are increased by a factor of ten, a surprising result occurs. It was found that the heterogeneous ignition time still decreases instead of increasing. This was due to the fact that i) the outer particles had completely pyrolyzed and, since the cloud is dilute, a flammable mixture could not form in the gas phase ii) and the char particles are less dense and heat up faster. Thus, ignition is expected to be heterogeneous as mentioned earlier. For higher G-numbers ignition time is decreased as expected since the flammable mixture formation time is greatly reduced.

Gas Phase Kinetics

Figure 6.28b shows the effect of altering the preexponential factor for the gas phase oxidation of volatiles ($A_{V,g}$) and CO (A_{CO}). Increased volatile oxidation kinetics results in decreased heterogeneous ignition times (at low G-numbers) since the gas phase in the cloud heats faster, thus causing the particles to completely devolatilize quicker and ignite heterogeneously. The suppression of the

Figure 6.28a. Effect of Altering Pyrolysis Kinetics on Ignition Time

Figure 6.28b. Effect of Altering Gas Phase Kinetics on Ignition Time

volatile oxidation kinetics results in an enlargement of the heterogeneous region since a large volatile mass fraction is required to form a flammable mixture. In the homogeneous region, the enhancement of the volatile oxidation kinetics results in a decrease in ignition time. Increasing the CO oxidation kinetics by a factor of ten lowers ignition time (Note that CO is produced by heterogeneous reactions. However, since CO is consumed so rapidly in the gas phase, it serves only as a heat source to enhance the liberation of volatiles from the particles resulting in the rapid formation of a flammable mixture in the gas phase). Suppressing the CO oxidation kinetics seems to have little effect. This result suggests that CO oxidation can be frozen for ignition studies of coal and is negligible in the base case.

The reported data reported in the literature list various values for A , B , and E . Although the preexponential factors and activation energies may be different by several orders of magnitude, the reaction rate ($k = A \exp(E/RT)$) are not significantly different within the temperature range of validity.

6.3.1.2. Ignition Results for an Initially Hot Cloud

Figure 6.29 shows the effect of cloud denseness on ignition time for an initially hot cloud of particles. The initial cloud temperature was set equal to the ambient temperature. For low G-numbers, ignition time shows little or no dependence on G-number. This is more pronounced for higher temperatures. In an initially hot cloud, if the interparticle separation is such that the diffusion transport time between particles is less than the ignition time then the particle ignites under IPI mode. Thus particles igniting under this condition would be expected to show little or no dependency on G-number. Since ignition time decreases as temperature increases, clouds with a small interparticle separation (higher particle loading or G-number) may experience IPI for high temperatures

while particle interactions may hinder ignition at lower temperatures. Thus the IPI region is larger for higher temperatures.

6.3.2. Effects of Radiation

If radiation is included, then new ignition criteria must be used. Since the particles now heat faster than the surrounding gas phase, the previous heterogeneous ignition criteria (i.e. particle temperature greater than the surrounding gas phase temperature) can not be used. Also it was found that for certain cases, the temperature of the outer shell in the cloud (i.e. $\xi = 1.0$) rose above the temperature of it's surrounding shells long before significant oxidation in the gas phase took place.

The new heterogeneous criteria stipulates that the mass loss rate per unit area of a particle must exceed a certain value. This value corresponds to the mass loss rate per unit area for $G=1$ using the previous criteria. The new homogeneous criterion stipulates that, in addition to the temperature of one shell being higher than the temperature of the two surrounding shells, the volatile oxidation rate be a local maximum. Figure 6.30 shows the effect of cloud denseness on ignition time for the base case using both the old and the new criteria.

Figure 6.31 shows the effect of surrounding radiative temperature for the base case. A high temperature radiative environment greatly reduces the ignition time. This reduction is much greater in the high G-number region, since the increased number of particles results in rapid heating of the interior of the cloud.

Experimental Review

The experimental data of Milne and Beachy [1977] shows a reduction in the primary reaction zone position with an increase in the coal dust concentration; their results suggest that 90 – 95% of the volatile matter is preferentially consumed within 1 cm indicating homogeneous ignition. The number of particles

Figure 6.29. Effect of G-number on Ignition Time (Hot Cloud)

Figure 6.30. Comparison of Ignition Criteria

Figure 6.31. Effect of Radiative Temperature on Ignition Time

per unit volume is comparable to the numbers corresponding to homogeneous ignition (about 3.8×10^8 particles per m^3 ; calculated from reported mass concentrations and assuming 100 micron particles). These results seem to confirm the results of fig. 6.19. Furthermore, Cashdollar and Hertzberg [1983] and Carpenter correlated the dense cloud flammability limits with VM which assuming homogeneous ignition.

6.4. Combustion

Once the volatiles are ignited, the gas temperature rises rapidly. The resulting gas phase reactions are so fast that the oxygen concentration reaches a negligible value. Subsequent combustion is assumed to be controlled by diffusion of oxygen from the ambience to the reaction zone. A thin flame model is then adopted for the combustion of volatiles.

The time for the cloud to completely burn can be expressed as

$$t_b = t_{th} + t_h + t_f + t_i + t_{pyr} + t_{c,ch} \quad (6.14)$$

where

$t_{c,ch}$ is the chemical time required for the char to completely burn once devolatilization is complete.

These times may overlap and will be different for different positions within the cloud, however they are very useful in describing the processes involved with transient group pyrolysis, ignition, and combustion.

Thin Flame Model

This method involves the use a Shvab-Zeldovich transformation and the assumption of a diffusionally controlled flame and volatiles are assumed to be generated via low temperature pyrolysis reaction I. The transformation variables used are given as follows

$$\beta_{VO_2} = Y_V - Y_{O_2}/\nu_{O_2,V}$$

$$\beta_{h_TV} = Y_V + h_T/h_{c,V}$$

where

β_{VO_2} is the Shvab Zeldovich variable for oxygen/volatiles

β_{h_TV} is the Shvab Zeldovich variable for volatile/enthalpy

Y_V is the mass fraction of volatiles

Y_{O_2} is the mass fraction of oxygen

$\nu_{O_2,V}$ is the stoichiometric coefficient for oxygen

h_T is the local thermal enthalpy and

$h_{c,V}$ is the heating value of the volatiles

The Shvab-Zeldovich transformation eliminates the gas phase chemical source terms. The variables β_{VO_2} and β_{h_TV} are traced as a function of time (Appendix C).

Once the following conditions involving β_{VO_2} and the temperature profile are met at any location (say ξ_f), the model switches from the thick flame model (the original model which assumes finite volatile oxidation kinetics) to the thin flame model at the same location (ξ_f). At the flame location,

- i) $\beta_{VO_2} = 0$ at $\xi = \xi_f$
- ii) $T > T_{limit}$ ($T_{limit} \approx 1800$ to $2000K$)

When these conditions have been met the flame is located at the position ($\xi = \xi_f$) where $\beta_{VO_2} = 0$ (Many time the location is the same as the ignition location. Volatile mass fractions are assumed to be zero for $r > r_f$ and oxygen mass fractions are set to zero if $r < r_f$. From the knowledge of β_{VO_2} and β_{h_TV} and the assumption of infinite gas phase kinetics, Y_V , T , and Y_{O_2} profiles can be obtained. Once β_{VO_2} has been determined volatile and oxygen mass fractions can be solved for and then gas phase enthalpy is found from the calculated values of β_{h_TV} and Y_{O_2} .

This method has proved more stable than the previous explicit method, but oscillates immediately after transition from thick to thin flame model. The reason is as follows:

When the cloud ignites homogeneously, there is still some oxygen left within the flame radius and volatiles remaining outside the flame radius. Once the thin flame model is adopted $Y_V = 0$ for $r > r_f$ and $Y_{O_2} = 0$ for $r < r_f$ which results in a rapid temperature rise within the cloud for $r < r_f$. The sudden jump in the temperature results in a rapid heating of the particles which act as heat sinks lowering the gas phase temperature subsequently.

Figure 6.32 gives the profiles of T , Y_V , Y_{O_2} , Y_{CO_2} , β_{VO_2} , and β_{hTV} shortly after the cloud has ignited and the flame is at a position farthest from the surface of the cloud. Prior to this point, the flame (maximum temperature location) was moving outward due to intensive pyrolysis until a point is reached at which oxygen diffusing to the surface of the flame overcomes the blowing due to pyrolysis and the flame begins to move back toward the cloud.

Figure 6.33 gives the profiles of T , Y_V , Y_{O_2} , Y_{CO} , Y_{CO_2} , β_{VO_2} , and β_{hTV} just as the flame has reached the cloud surface. Once this position is reached, the thin flame model is no longer valid since this formulation does not account for the presence of volatiles inside the cloud.

Figure 6.34 shows the flame radius time history for two volatile matter fractions. As expected, the flame reaches the cloud surface rapidly for the coal with a lower volatile mass fraction.

Figure 6.32. Flame Structure ($\xi_f \rightarrow \text{minimum}$)

Figure 6.33. Flame Structure ($\xi_f = 1$)

Figure 6.34. Flame Location Time History

CHAPTER VII

SUMMARY OF RESULTS

A group combustion model has been presented for the group pyrolysis, ignition, and combustion of a cloud of coal particles.

PyrolysisWithout RadiationCold Cloud

1. Volatile yields for an initially cold cloud ($R_c = 1$ cm) are slightly in excess of proximate yield since the thermal wave propagation time controls the heating rate of the particles within the cloud.
2. Small cloud radii are desirable to maximize volatile yield for an initially cold cloud since this decreases the thermal wave propagation time and thus speeds the heating of the particles.

Hot Cloud

3. Volatile yield was found to be a weak function of G-number for a particle size of $20\text{ }\mu\text{m}$ and high initial cloud temperatures. For lower temperatures, volatile yields in excess of proximate yield decrease significantly as G-number is increased due to the increased particle heat capacity lowering the initial cloud temperature below that which significant amounts of volatiles are released pyrolysis reaction II in the competing reaction pyrolysis scheme. For a particle size of $100\text{ }\mu\text{m}$ (diameter), there is no significant difference between the high and low G-number clouds because the particle heat up time is large (i.e. volatile yield $\approx$ proximate).
4. Small particle diameters are desired to maximize volatile yield since larger particles heat slower. Due to the slower heating, the majority of the initial

hydrogen and oxygen content of the coal to escape via pyrolysis reaction I before the particle temperature becomes hot enough to a pyrolysis via pyrolysis reaction II.

With Radiation

5. The results for radiation exhibit trends which are the opposite of those without radiation in that larger cloud radii and increased coal particle loading result in increased yields. Also extremely small particles result in decreased yields.

Ignition

Without Radiation

Cold Cloud

1. A group ignition model is presented for a cloud of coal particles which accounts for pyrolysis, and heterogeneous and homogeneous reactions. Criteria for heterogeneous and homogeneous ignition were established.
2. The results reveal heterogeneous ignition for dilute clouds and homogeneous ignition for dense clouds.
3. Ignition time increases as the number of particles per unit volume is increased from the dilute limit, then decreases and increases again revealing a minimum ignition time at a certain dust concentration.
4. The heterogeneous region increases in size as ambient temperature is increased. Also, the G-number corresponding to minimum ignition time increases with increasing temperature.
5. Decreasing the proximate volatile matter results in a decrease in ignition time in the heterogeneous region and an increase in the size of the heterogeneous region. In the homogeneous region, ignition time increases with decreasing proximate volatile matter as expected.

6. The parametric studies reveal that while heterogeneous ignition time decreases significantly with an increase in oxygen mass fraction, the decrease is not as significant for homogeneous ignition (gas ignition).

Hot Cloud

7. For an initially hot cloud, ignition time remains almost constant for relatively low G-numbers and then increases rapidly at high numbers.

With Radiation

8. High temperature radiative surfaces can greatly decrease ignition time especially for dense clouds.

Combustion of Coal

1. Once the cloud is ignited and is burning, a thin flame is formed outside the cloud. Thus, group combustion occurs for a cloud of coal particles.
2. The thin flame moves towards the cloud as the volatiles are consumed rapidly. A critical condition is reached at which the flame just anchors on the cloud surface. Correction factors under these conditions could not be estimated since the individual particle combustion rate can not be calculated with simple relations when volatiles are burning.

REFERENCES

- Annamalai, K., and Durbetaki, P., 1975, "Extinction of Spherical Diffusion Flames: Spalding's Approach," *Combustion and Flame*, Vol. 17, pp. 1416-1429.
- Annamalai, K., and Durbetaki, P., 1977, "A Theory on Transition of Ignition Phase of Coal Particles," *Combustion and Flame*, Vol. 29, pp. 193-208.
- Annamalai, K., J., 1979, "Critical Regimes of Coal Ignition," *Engineering for Power*, Vol. 101, No. 4, pp. 576-587.
- Annamalai, K., Madan, A., and Mortada, Y.I., 1984, "Ignition of a Cloud of Droplets," *ASME Winter Annual Meeting*, New Orleans, LA, Paper No. 84-WA/HT-18.
- Annamalai, K., 1985, "The Evaporation and Combustion of a Cloud of Droplets," *Heat Transfer in Fire and Combustion Systems*, (C.K. Law et al. ed.) ASME, New York, HTD, Vol. 45, pp. 27-35.
- Annamalai, K., and Ramalingam, S., 1987, "Distinctive Burning Characteristics of Carbon Particles," *Combustion and Flame*, Vol. 70 pp. 307-332.
- Annamalai, K., Ramalingam, S., Dahdah, T., and Chi, D., 1988a, "Group Combustion of a Cylindrical Cloud of Char Particles," *Journal of Heat Transfer*, Vol. 110, pp. 190-200.
- Annamalai, K., Ryan W.R., and Ramalingam, S.C., 1988b, "Group Combustion of Coal Particles, Final Report", PETC/DOE, Pittsburgh, PA.
- Anthony, D.B., and Howard, J.B., Hottel, H.C., and Meissner, H.P., 1975, "Rapid Devolatilization of Pulverized Coal," *15th Symposium (International) on Combustion*, The Combustion Institute, Pittsburgh, PA, pp. 1303-1317.
- Anthony, D.B., Howard, J.B., and Meissner, H.P., 1976, "Rapid Devolatilization and Hydrogasification of Bituminous Coal," *Fuel*, Vol. 55, pp. 121-128.

- Badzoich, S. and Hawksley, G.W., 1970, "Kinetics of Thermal Decomposition of Pulverized Coal Particles," *Industrial Engineering Chemical Progress, Design and Development*, Vol. 9, pp. 521-530.
- Baum, S.S., and Street, D.J., 1971, "Predicting the Combustion Behaviour of Coal Particles", *Combustion Science and Technology*, Vol. 3, pp. 231-243.
- Bell, R.S., and Caton, J.A., 1986, "Cycle Simulations of a Coal-Fueled, Reciprocating, Internal-Combustion Engine: the Role of Volatiles and Liquid Carriers," *Combustion Science and Technology*, Vol. 50, pp. 185-203.
- Bellan, J., and Cuffel, R., 1983, "A Theory of Nondilute Spray Evaporation Based upon Multiple Drop Interactions," *Combustion and Flame*, Vol. 51, pp. 55-67.
- Cashdollar, K.L., and Hertzberg, M., 1983, "Infrared Temperatures of Coal Dust Explosions," *Combustion Flame*, Vol. 57, pp. 23-35.
- Cassel, H.M., and Liebman, I., 1959, "The Cooperative Mechanisms in the Ignition of Dust Dispersions," *Combustion and Flame*, Vol. 3, pp. 467-475.
- Chen, M.R., Fan, L.S., and Essenhigh, R.H., 1984, "Prediction and Measurement of Ignition Temperature of Coal Particles," *Twentieth Symposium (International) on Combustion*, The Combustion Institute, Pittsburgh, PA, pp.1513-1519.
- Chiu, H.H., and Liu, F.M., 1977, "Group Combustion of Liquid Droplets," *Combustion Science Technology*, Vol. 17 pp. 127-142.
- Chiu, H.H., Kim, H.Y., and Croke, E.J., 1983, "Internal Group Combustion of Liquid Droplets," *Proc., 19th Symp. (International) on Combustion*, Combustion Institute, Pittsburgh, PA, pp. 991-980.
- Correa, S.M., and Sichel, M., 1982, "The Boundary Layer Structure of a Vaporizing Fuel Cloud," *Combustion Science and Technology*, Vol. 28, pp. 121-130.

- Correa, S.M., and Sichel, M., 1983, "The Group Combustion of a Spherical Cloud of comodisperse Fuel Droplets," *Proc. 19th Symposium (International) on Combustion*, Combustion Institute, Pittsburgh, PA, pp. 981-991.
- Eddinger, R.T., Friedman, L.D., and Rau, E., 1966, "Devolatization of Coal in a Transport Reactor," *Fuel*, Vol. 45, pp. 245-252.
- Gat, N., Cohen, L.M., Witte, A.B., and Denison, M.R., 1983, "Coal Pyrolysis Under Rapid Heating With a CW Laser," *Central States Section*, The Combustion Institute, Pittsburgh, PA, Paper #83-06.
- Golovina, E.S., and Khaustovich, G.P., 1962, "The Interaction of Carbon with Carbon Dioxide and Oxygen at Temperatures up to 3000 K," *8th Symposium (International) on Combustion*, The Combustion Institute, Pittsburgh, PA, pp. 784-792.
- Ghosh, R., 1986, "Spontaneous Combustion of Certain Indian Coals - Some Physio-chemical Considerations," *Fuel*, Vol. 65, pp.1042-1046.
- Hamor, R.J., Smith, I.W., and Taylor, R.J., 1973, "Kinetics of Combustion of Pulverized Brown Coal Char Between 630 and 2200 K," *Combustion and Flame*, Vol. 21, pp. 153-162.
- Horton, M.D., 1978, "Fast Pyrolysis," *Pulverized Coal Combustion and Gasification*, Plenum Press, London, pp.133-147.
- Howard, J.B., and Essenhigh, R.H., 1967, "Mechanism of Solid-Particle Combustion With Simultaneous Gas Phase Volatiles Combustion," *11th Symposium (International) on Combustion*, The Combustion Institute, Pittsburgh, PA, pp. 399-408.
- Howard, J.B., Williams, G.C., and Fine, D.H., 1973, "Kinetics of Carbon Monoxide Oxidation in Postflame Gases," *Proceedings 14th Symposium (International) on Combustion*, Combustion Institute, Pittsburg, PA, pp. 975-986.

- Jammaluddin, A.S., Truelove, J.S., and Wall T.F., 1986, "Devolatization of Bituminous Coals at Medium to High Heating Rates," *Combustion and Flame*, Vol. 63, pp.329-337.
- Kimber, G.M., and Gray, M.D., 1967, "Rapid Devolatization of Small Coal Particles," *Combustion and Flame*, pp. 360-362.
- Kobayashi, H., 1972, "Rapid Decomposition Mechanisms of Pulverized Coals," Ph.D. Thesis, Chemical Engineering, MIT, Cambridge Mass.
- Krishna, C.R., and Berlad, A.L., 1980, "A Model for Dust Cloud Autoignition," *Combustion and Flame*, Vol. 37, pp.207-210.
- Kurylko, L., and Essenhight, R.H., 1973, "Steady and Unsteady Combustion of Carbon," *Fourteenth Symposium (International) on Combustion*, The Combustion Institute, Pittsburgh, PA, pp. 1375-1386.
- Labowsky, M., 1976, "The Effects of Nearest Neighbor Interactions on the Evaporation Rate of a Cloud of Particles," *Chemical Engineering Science*, Vol. 31, pp. 801-803.
- Labowsky, M., 1978, "A Formalism for Calculating the Evaporation Rates of Rapidly Evaporating Interacting Particles," *Combustion Science and Technology*, Vol. 18, pp. 145-151.
- Labowsky, M., and Rosner, D.E., 1978, "Group Combustion of Droplets in Fuel Clouds, I. Quasi-Steady Predictions," *Evaporation - Combustion of Fuels*, Advances in Chemistry Series (J.T. Zung, Ed.), American Chemical Society, Washington, D.C., No. #166, pp. 63-79.
- Labowsky, M., 1980, "Calculation of the Burning Rates of Interacting Fuel Droplets," *Combustion Science and Technology*, Vol. 22, pp. 217-226.
- Maloney, D.J., and Jenkins, R.G., 1984, "Coupled Heat and Mass Transport and Chemical Kinetic Rate Limitations During Rapid Coal Pyrolysis," *Twenti-*

- eth Symposium (International) on Combustion*, The Combustion Institute, Pittsburgh, PA, pp. 1435-1433.
- McGrath, G.C., and Chigier, N.A., 1973, "Liquid Spray Burning in the Wake of a Stabilizer Dirk," *Proc. 14th Symposium (International) on Combustion*, The Combustion Institute, Pittsburgh, PA, pp. 1355-1363.
- Midkiff, K., Altenkirch, R., and Peck, R., 1986, "Stoichiometry and Coal Type Effects on Homogeneous vs. Heterogeneous Combustion in Pulverized Coal Flames," *Combustion and Flame*, Vol. 64, 253-267.
- Milne and Beachy, 1977, "The Microstructure of Pulverized Coal-Air Flames. II. Gaseous Species, Particulate, and Temperature Profiles," *Combustion Science and Technology*, Vol. 16, pp. 139-152.
- Niksa, S., Heyd L.E., Russel W.B., and Saville, D.A., 1984, "On the Role of Heating Rate in Rapid Coal Devolatilization," *Twentieth Symposium (International) on Combustion*, pp. 1445-1453.
- Niksa, S., Mitchell, R.E., Hencken, K.R., and Tichenor, D.A., 1986, "Optically Determined Temperatures, Sizes, and Velocities of Individual Carbon Particles under Typical Combustion Conditions," *Combustion and Flame*, Vol. 60, pp. 183-193.
- Northam, D.B. and Von Rosenberg, C.W., 1979, "Coal Gasification in Steam at Very High Temperatures," *Fuel*, Vol. 58, pp. 264-268.
- Nuruzzaman, A.S.M., Hedley, A.B., and Beer, J.M., 1970, "Combustion of Monosized Droplet Streams - Stationary Self-Supporting in Flames," *13th Symposium (International) on Combustion*, The Combustion Institute, Pittsburgh, PA, pp. 787-799.
- Pickles, J.H., 1982, "A Model for Coal Dust Explosions," *Combustion and Flame*, Vol. 44, pp. 153-168.

- Ragaland, K.W., and Yang, J.T., 1985, "Combustion of Millimeter Sized Coal Particles in Convective Flow," *Combustion and Flame*, Vol. 60, pp. 285-297.
- Ramalingam, S., 1988, "Group Ignition and Combustion of a Cloud of Char Particles Under Transient Conditions," MS Thesis, Mech. Engg. Texas A&M.
- Seeker, W.R., Wegenter, D.C., Lester, T.W., and Merklin, J.F., 1979, "Single Pulse Shock Tube Studies of Pulverized Coal Ignition," *Seventeenth Symposium (International) on Combustion*, The Combustion Institute, Pittsburgh, PA, pp.155-166.
- Sichel, M., and Palaniswamy, S., 1984, "Sheath Combustion of Sprays," *Proc. 20th Symposium (International) on Combustion*, Combustion Institute, Pittsburgh, PA, pp. 1789-1798.
- Smith, I.W., 1971, "Kinetics of Combustion of Size Graded Pulverized Fuels in the Temperature Range 1200-2270 K," *Combustion and Flame*, Vol. 17, pp. 303-314.
- Smoot, D. and Smith, D.J., 1987, "Comprehensive Modeling of Combustion Systems," Vol. 1, Proceedings of the 1987 ASME JSME Thermal Engineering Joint Conference, 137-149.
- Solomon, P.R., 1980, "The Characterization of Coals During Thermal Decomposition," *Fifth EPA Fundamental Combustion Research Workshop*, Newport Beach, CA.
- Solomom, P.R., Hamblen, D.G., Carangelo, R.M., and Krause, J.L., 1982, "Coal Thermal Decomposition in an Entrained Flow Reactor: Experiments and Theory," *Nineteenth Symposium (International) on Combustion*, Combustion Institute, Pittsburgh, PA, pp. 1139-1149.

- Stickler, D.B., Gannon, R.E., and Kobayashi, H., 1974, "Rapid Devolatilization Modeling of Coal," *Eastern States Section Meeting of the Combustion Institute*, Applied Physics Laboratory, Silver Springs, MD.
- Stickler, D.B., Becker, F.E., and Ubhayaker, S.K., 1979, "Combustion of Pulverized Coal in High Temperature Preheated Air," *Seventeenth Aerospace Sciences Meeting*, New Orleans, LA, (Private Collection-W. Ryan).
- Suuberg, E.M., Peters, W.A., and Howard, J.B., 1978, "Product Compositions and Formation in Rapid Pyrolysis of Pulverized Coal- Implications for Combustion," *Industrial Engineering Chemical Process Design and Development*, Vol. 17, pp.37-59.
- Suzuki, T., and Chiu, H.H., 1971, "Multidroplet Combustion of Liquid Propellants," *Proceedings of the 9th International Symposium on Space Technology and Science*, AGNE Publishing Co., Tokyo, Japan, pp. 145-154.
- Tsai, C. and Scaroni, A.W., 1984, "Pyrolysis During the Initial Stages of Pulverized Coal Combustion," *Twentieth Symposium (International) on Combustion*, Combustion Institute, Pittsburgh, PA, pp. 1455-1462.
- Ubhayakar, S.K., Stickler, D.B., Von Rosenberg, C.W., and Gannon, R.E., 1977, "Rapid Devolatilization of Pulverized Coal in Hot Combustion Gases," *Sixteenth Symposium (International) on Combustion*, Combustion Institute, Pittsburgh, PA, pp. 427-436.

APPENDIX A

DESCRIPTION OF NUMERICAL SCHEME

The main program reads in the input data from various input files. The input files and data are listed in Chapter 5, Table 11. The main program calls the necessary subroutines to calculate several parameters. An explicit method is used in the program. The flow chart is given in Figure A.1. Table A.1 presents the list of subroutines and their functions.

1. To determine the gas properties at $t = \Delta t$ with the given initial conditions at $t = 0$ (T_0 , $Y_{k,0}$, $m_{p,0}$, $T_{p,i,0}$, $\rho_{p,i,0}$, and $d_{p,i,0}$). The main program calls the subroutine source to calculate the source terms ($\dot{w}_k'''$, $\dot{w}_m'''$, and $\dot{w}_h'''$) with $T_{p,i,0}$. Since $\dot{w}_m'''$ is a sum of $\dot{m}_V'''$ and $\dot{m}_C'''$, the volatile liberation rate, $\dot{m}_{V,i}$, is found by subroutine VOLPRD with the help of subroutines, FCUTIL (fraction of coal utilized) and COMPR (competing pyrolysis reactions), and the heterogeneous production rate, $\dot{m}_C'''$, is found by subroutine HETPRD with the help of subroutines WALMSF (wall mass fraction of species) and SURFR (surface reactions). At the same time, the density of the particle is calculated by using subroutine RHOP, and the current diameter is established by using the subroutine DCUR. Further, the current mass of the particle, $m_{p,i}$, is found by using the subroutine MASSP. To compute $\dot{w}_k'''$, one has to find the mass production rate of species k in the gas phase due to pyrolysis and heterogeneous reactions at the particle surfaces and due to gas phase reactions. The subroutines VOLPRD and HETPRD provide the necessary outputs for the species generation due to pyrolysis and heterogeneous reactions ($\dot{w}_{k,p}'''$). The chemical production rate of species k due to gas phase reactions, $\dot{w}_{k,ch}'''$, is given by the subroutines COOXD (CO-oxidation reactions) and VOLOXD (volatile oxidation reactions).

The term $\dot{w}_h'''$, due to the gas phase oxidation is computed by using subroutines COOXD and VOLOXD. The subroutine SOURCE calls HTCONV to find the

Figure A.1 Flow Chart

Table A.1 Description of Subroutines

No.	Name	Output from program	Input to program
1.	SOURCE	$\dot{w}_m''', \dot{w}_h''', \dot{w}_k'''$	-
1.1	COOXD	$\dot{m}_{CO}, \dot{m}_{O_2}, \dot{m}_{CO_2},$ $\dot{q}_{ch,CO}'',$ due to CO oxidation	$T_g, Y_{O_2}, Y_{CO},$ $Y_{H_2O}, h_{c,CO}, A_{CO},$ $E_{CO}, N_{O_2}, N_{CO},$ N_{H_2O}
1.2	VOLOXD	$\dot{m}_V''', \dot{m}_{O_2}, \dot{m}_{CO_2}, \dot{m}_{H_2O}$ due to volatiles oxidation	$T_g, Y_{O_2}, Y_V, h_{c,V},$ $\nu_{O_2,V}, \nu_{CO_2,V},$ $\nu_{H_2O,V}, A_{V,g}, E_{V,g},$ N_v, N_{O_2}, W_v
1.3	VOLPRD	$\dot{m}_V''', \dot{q}_{pyr}'''$	$(\dot{m}_V, N, q_{pyr})_i$ of each size i
1.3.1	COMPR	$(\dot{m}_V, \dot{q}_{pyr}, f_{cu})_i$ of size i due to competing reactions	f_{cu}, E_V, B_V, T_p
1.3.2	FCUTIL	Δf_{cu}	$(f_{cu})_{previous},$
1.3.3	RHOP	ρ_p	$(\rho_p, \dot{m}_V, d_p)$ of the previous time step
1.4	HETPRD	$\dot{m}_{O_2}''', \dot{m}_{CO_2}''', \dot{m}_{H_2O}''', \dot{m}_{CO}''',$ $\dot{m}_c''', \dot{q}_h'''$ due to carbon gas reactions at the particle surface	n, T, d_p
1.4.1	SURFR	$(\dot{m}_C, \dot{m}_{O_2}, \dot{m}_{CO_2}, \dot{m}_{CO}, \dot{m}_{H_2O}, \dot{q})$ due to carbon gas reactions at particles of size i	$(T_p, Y_{k,w}, d_p, m_p)$ of previous time step
1.4.2	DCUR	d_p of current time step	$(\dot{d}_p, \dot{m}_C, \rho_p)$ of previous time step

Table A.1 (continued)

1.4.3	WALMSF	$Y_{k,w}$ at the wall for O_2 , CO_2 and H_2O	Y_k in the gas phase T_p, d_p, m_p
1.5	HTCONV	$\dot{q}_{conv}'''$	$\dot{q}_{conv,i}, n$
1.5.1	CONV	$\dot{q}_{conv,i}$	$(d_p, T_p, \dot{m}_p)$ of size i and T_g
1.5.1.1	FBLow	F_{blow}	$d_p, \dot{m}_p$
1.5.1.2	FKNUD	F_{knud}	d_p, l (mean free path)
2	EQUATION	ψ_L^{k+1} $\psi = h_T, Y_{V_I}, Y_{V_{II}},$ $Y_{O_2}, Y_{CO_2}, Y_{CO}, Y_{H_2O}$	$\psi_{L+1}^k, \psi_L^k, \psi_{L-1}^k$
3	MASSP	m_p at the current time step	$(\dot{m}_p, m_p)$ at previous time step
4	QRAD	$\dot{q}_{rad}$	$T_{surr}, T_p, \epsilon, F$
4.1	SHAPE	shape factor, F	
5	THETAP	θ_p at the current time step	$\dot{m}_p, \dot{q}_{pyr}, \dot{q}_h, \dot{q}_{conv}$ $q_{rad}, T_p)$ of previous time step
6	ALPA	$\alpha (= \dot{m}/\dot{m}_{ref,g})$	$(\rho_g)_i^{k+1}, (\rho_g)_i^k, w_m$
7	DELTOU	$\Delta\tau$ (minimum of $\Delta\tau_0, \Delta\tau_1, \Delta\tau_2$)	$\Delta\tau_0, \Delta\tau_1, \Delta\tau_2, \Delta\tau_{st}, JFLAG$ (a flag to determine if initial time step is externally fixed)

convective heat transfer from all the particles to the gas per unit volume of the cloud. The subroutine HTCONV calls CONV to find $\dot{q}_{conv,i}$ (convective heat transfer from particles of size i). The subroutine CONV calls FBLOW (which gives the blowing correction factor) and FKNUD (which gives the Knudson correction factor) in order to calculate $\dot{q}_{conv,i}$. The subroutines are called for every ξ and τ .

Then the main program calls subroutine EQUATION which is a common finite difference equation for all the variables of interest except for α . This subroutine computes Y_k and h_T at all time steps. Subroutine MASSP gives the temperature of the particle at every ξ and τ provided $\xi > 1$.

Finally, subroutine ALPA computes α , the dimensionless mass flow rate from the cloud at every time step.

2. Then the program determines the mass loss of volatiles within $\Delta\tau$ from the knowledge of $\dot{m}_{V,i}$ at $\tau = 0$ and the mass loss rate of carbon within $\Delta\tau$ from the knowledge of $\dot{m}_{C,i}$ at $\tau = 0$. From the total mass flow rate $\dot{m}_{p,i}$, $m_{p,i}$, $\rho_{p,i}$, and $d_{p,i}$ at $\tau = \Delta\tau$ are found.

3. Now the program repeats steps 1 and 2 for subsequent time steps.

APPENDIX B

NUMERICAL CODE

```
*****  
PROGRAM LISTING  
*****  
  
AUTHORS: Dr. Kalyan Annamalai, Suresh Ramalingham,  
and William Ryan  
*****  
  
C THIS PROGRAM READS IN THE INPUT DATA AND THEN CALLS VARIOUS SUBROUTINES  
C IN ORDER TO SIMULATE THE GROUP COMBUSTION OF A SPHERICAL CLOUD OF COAL  
C PARTICLES  
C  
C IMPLICIT DOUBLE PRECISION (A-H,O-Z)  
C REAL*8 IGNDIF,MVS,MCHS,MPS,MVSP,MCHSP,MPSP,N  
C REAL*8 NPS,MPO,NUI,NU2,NU3,NU4,NO21,NO22,NC023,NC04,NO24  
C REAL*8 LAMDA,NU,MPARTP,MCHPTP,MVPTP,MLOWP,MCHPTC,MVPTC  
C REAL*8 MLOWC,MPSFR,MELS,MPSC,MPART  
C REAL*8 NC0,NO2CO,NH2OCO,NV,NO2V,NH2O4  
C DIMENSION HTSP(5),YVF(5),PYH2O(5),YCOF(5),PYO2(5),PYCO2(5)  
C DIMENSION YV2P(5),VOLMAT(105,3),BHTVP(5),BVO2P(5)  
C  
C ----- GAS PHASE PROFILES -----  
C  
C COMMON/GASPRF/HTS(105,3),THETA(105,3),RHOGS(105,3),  
C 1 ALPHA(105,3),YV(105,3),YO2(105,3),YCO2(105,3),  
C 2 YCO(105,3),YH2O(105,3)  
C DIMENSION YVDP(105)  
C DIMENSION BHTV(105,3),BVO2(105,3)  
C  
C ----- MASS SOURCES IN THE GAS PHASE -----  
C  
C COMMON /SOURMS/W MSP(105)  
C  
C ----- CURRENT PARTICLE PROPERTIES -----  
C  
C COMMON/PARTS/THETP(105,5),MVS(105,5),MCHS(105,5),MPS(105,5),  
C 1 DPS(105,5),RHOPS(105,5),FCU(105,5),HPYRS(105,5),HHETS(105,5).  
C 2 CONVS(105,5)  
C  
C ----- PREVIOUS PARTICLE PROPERTIES -----  
C  
C COMMON/PARTSP/THETPP(105,5),MVSP(105,5),MCHSP(105,5),  
C 1 MPSP(105,5),DPSP(105,5),RHOPSP(105,5),FCUP(105,5),  
C 2 YO2W(105,5),YCO2W(105,5),YH2OW(105,5)  
C  
C ----- INITIAL PARTICLE PROPERTIES AND SIZE DISTRIBUTION -----  
C  
C COMMON/SIZEIN/NSIZE,NPS(5),DPO(5),RHOPO(5),MPO(5)  
C  
C ----- GAS PHASE TRANSPORT PROPERTIES -----  
C  
C COMMON/GASPRF/RHOD,CP,LAMDA,NU,FREEP  
C  
C ----- SPECIFIC HEAT OF THE PARTICLES -----  
C  
C COMMON/PARPRF/CPF  
C  
C ----- REFERENCE CONDITIONS -----  
C  
C COMMON/REFCON/TREF,TMREF,RCOROD,HREF  
C  
C ----- DATA FOR NUMERICAL METHOD -----  
C
```

```

COMMON/NUMER/XIMAX,TOUMAX,NXI,NTOU,DTOU,DXI
C ----- AMBIENT DATA -----
C
COMMON/AMBDAT/PRESS,TINF
C ----- INITIAL CLOUD RADIUS -----
C
COMMON/SPRAY/RCO
C ----- PROFILE OF VOLATILES RELEASED VIA ROUTE 2 -----
C
COMMON/V2PROF/YV2(105,3)
C ----- KEEPS TRACK OF THE LOCATION AND ITERATION STEP -----
C
COMMON/LOCATION/LL,KP
C ----- PYROLYSIS KINETICS DATA -----
C
COMMON/COMPRIN/BV(2),EV(2),VM(2),HPYR(2),HVV(2)
C ----- CO OXIDATION KINETICS DATA -----
C
COMMON/COKIN/ACO,ECO,NCO,NO2CO,NH2OCO
COMMON/VOLYLD/WPART,VOLFP
C ----- VOLATILE OXIDATION KINETICS -----
C
COMMON/VOLKIN/AVG,EVG,NV,NO2V
C ----- CHAR KINETICS DATA -----
C
COMMON/CHKIN/NU1,NU2,NU3,NU4,HC1,HC2,HC3,HC4,NO21,NO22
1 ,NCO23,NH2O4,BC(4),EC(4)
C ----- PREVIOUS GAS PHASE PROFILES -----
C
COMMON/GAS/TGAS,YO2P(5),YCO2P(5),YH2OP(5)
C ----- PREVIOUS PARTICLE SURFACE PROFILES -----
C
COMMON/WALP/YO2WP(105,5),YCO2WP(105,5),YH2OWP(105,5)
C ----- INITIAL HUMIDITY -----
C
COMMON/ATM/HUMIDY
COMMON/FCUT/FFCUT
C ----- GAS PHASE DENSITY -----
C
COMMON/DENS/RHOG
C ----- STORES THE INITIAL TIME STEP -----
C
COMMON/TIMEST/DTOUNW
COMMON/CLATOM/CAH,CAN,CAO
C ----- STORES TIME STEPS DETERMINED BY VARIOUS CRITERIA -----
C
COMMON/THETP/ADTOU,BDTOU,DTSET
COMMON/DTIME/DTTEMP
C ----- STORES VOLATILE PROPERTIES -----
C
COMMON/VOLPRP/WV1,WV2,VHA1,VNA1,VOA1,VHA2,VNA2,VOA2,HVV1,HVV2

```

```

COMMON/NUHER/XIMAX,TOUMAX,NXI,NTOU,DTOU,DXI
C
C ----- AMBIENT DATA -----
C
COMMON/AMBDAT/PRESS,TINF
C
C ----- INITIAL CLOUD RADIUS -----
C
COMMON/SPRAY/RCO
C
C ----- PROFILE OF VOLATILES RELEASED VIA ROUTE 2 -----
C
COMMON/V2PROP/YV2(105,3)
C
C ----- KEEPS TRACK OF THE LOCATION AND ITERATION STEP -----
C
COMMON/LOCATION/LL,KP
C
C ----- PYROLYSIS KINETICS DATA -----
C
COMMON/COMPRIN/BV(2),EV(2),VM(2),HPYR(2),HVV(2)
C
C ----- CO OXIDATION KINETICS DATA -----
C
COMMON/COKIN/ACO,ECO,NCO,NO2CO,NH2OCO
COMMON/VOLYLD/WPART,VOLFR
C
C ----- VOLATILE OXIDATION KINETICS -----
C
COMMON/VOLKIN/AVG,EVG,NV,NO2V
C
C ----- CHAR KINETICS DATA -----
C
1 COMMON/CHKIN/NU1,NU2,NU3,NU4,HC1,HC2,HC3,HC4,NO21,NO22
,NCO23,NH2O4,BC(4),EC(4)
C
C ----- PREVIOUS GAS PHASE PROFILES -----
C
COMMON/GAS/TGAS,YO2P(5),YCO2P(5),YH2OP(5)
C
C ----- PREVIOUS PARTICLE SURFACE PROFILES -----
C
COMMON/WALP/YO2WP(105,5),YCO2WP(105,5),YH2OWP(105,5)
C
C ----- INITIAL HUMIDITY -----
C
COMMON/ATM/HUMIDY
COMMON/FCUT/FFCUT
C
C ----- GAS PHASE DENSITY -----
C
COMMON/DENS/RHOG
C
C ----- STORES THE INITIAL TIME STEP -----
C
COMMON/TIMEST/DTOUNW
COMMON/CLATOM/CAH,CAN,CAO
C
C ----- STORES TIME STEPS DETERMINED BY VARIOUS CRITERIA -----
C
COMMON/THETP/ADTOU,BDTOU,DTSET
COMMON/DTIME/DTTEMP
C
C ----- STORES VOLATILE PROPERTIES -----
C
COMMON/VOLPRP/WV1,WV2,VHA1,VNA1,VOA1,VHA2,VNA2,VOA2,HVV1,HVV2

```

```

C
C ----- STOICHIOMETRIC COMBINATION COEFFICIENTS FOR VOLATILES -----
C
C      COMMON/STCV/SCCO21,SCCH2O1,SCO21,SCCO22,SCCH2O2,SCO22
C
C ----- TEMPERATURE RISE PER STEP LIMIT -----
C
C      COMMON/LIMIT/DTGLMT
C      COMMON/YVIMPLCT/V1CHV1,V1CHO2,V2CHV2,V2CHO2
C      COMMON/YCOIMPLCT/COCHCO,COCHO2
C      COMMON/METHOD/IMETH
C
C ----- READ AMBIENT DATA -----
C
C      OPEN(11,FILE='AMBDATA.DAT',STATUS='OLD')
C      READ(11,1001) TINF,YO2INF,YCO2IN,YCOINF,YVINP,YV2INF,YH2OIN
C      $      ,TO,TGC0,YO2C0,YCO2C0,YH2OC0,YCO0,YVC0,YV2C0,PRESS,PGSAT
C      $      ,TSUR
1001      FORMAT(10X,F7.2)
C      CLOSE(11)
C
C ----- READ COAL ANALYSIS DATA -----
C
C      OPEN(11,FILE='COALDATA.DAT',STATUS='OLD')
C      REWIND(11)
C      READ(11,1913) C,H,N,O,HCOAL
C      CLOSE(11)
1913      FORMAT(10X,E12.4)
C      ASH = 0.
C
C ----- READ CO KINETICS DATA -----
C
C      OPEN(11,FILE='COKINDATA.DAT',STATUS='OLD')
C      REWIND(11)
C      READ(11,1911) ACO,ECO,NCO,NO2CO,NH2OCO,OXDSCO
C      CLOSE(11)
1911      FORMAT(10X,E12.4)
C
C ----- READ VOLATILE KINETICS DATA -----
C
C      OPEN(11,FILE='VOLKINDATA.DAT',STATUS='OLD')
C      REWIND(11)
C      READ(11,1911) AVG,EVG,MV,NO2V,OXDSV
C      CLOSE(11)
C
C ----- READ SPRAY DATA -----
C
C      OPEN(11,FILE='SPRAYDATA.DAT',STATUS='OLD')
C      REWIND(11)
C      READ(11,1004) DP,RC,ROP0
C      CLOSE(11)
1004      FORMAT(10X,E11.3)
C
C ----- READ PYROLYSIS VIA COMPETING REACTION DATA -----
C
C      OPEN(11,FILE='COMPRDATA.DAT',STATUS='OLD')
C      REWIND(11)
C      READ(11,1004) VM(1),VM(2),EV(1),EV(2),BV(1),BV(2),
C      $      HPYR(1),HPYR(2)
C      CLOSE(11)
C      IF(VM(2).LT.1.0E-03) BV(2) = 1.0E-25
C
C ----- READ HETEROGENEOUS CHAR KINETICS DATA -----
C
C      OPEN(11,FILE='CHARDATA.DAT',STATUS='OLD')
C      REWIND(11)

```

```

601     FORMAT(15X,'@@@@@@@@TRANSIENT COMBUSTION OF COAL@@@@@@@@',/)
      END IF
      IF (ITYPE.EQ.2) THEN
        WRITE(93,602)
602     FORMAT(15X,'@@@@@@@@TRANSIENT IGNITION OF COAL@@@@@@@@',/)
      END IF
      IF (ITYPE.EQ.1) THEN
        WRITE(93,603)
603     FORMAT(15X,'@@@@@@@@TRANSIENT PYROLYSIS OF COAL@@@@@@@@',/)
      END IF
      END IF
      IF (IRAD.EQ.0) THEN
        WRITE(93,604)
604     FORMAT(15X,'@@@@@@@@RADIATION NOT INCLUDED@@@@@@@@',/)
      ELSE
        WRITE(93,605)
605     FORMAT(15X,'@@@@@@@@RADIATION INCLUDED@@@@@@@@',/)
      END IF
      IF (IOXDV.EQ.1) THEN
        WRITE(93,611)
611     FORMAT(15X,'+++++VOLATILES OXIDIZE+++++',/)
      ELSE
        WRITE(93,613)
613     FORMAT(15X,'.....FROZEN VOLATILES IN GAS PHASE.....',/)
      END IF
      IF (IOXDCO.EQ.1) THEN
        WRITE(93,617)
617     FORMAT(15X,'$$$$$$$$$ CO OXIDIZES $$$$$$$$$$',/)
      ELSE
        WRITE(93,619)
619     FORMAT(15X,'.....FROZEN CO IN GAS PHASE.....',/)
      END IF
      IF (ISOOT.EQ.1) THEN
        WRITE(93,621)
621     FORMAT(15X,'*****SOOT PRODUCTION SCHEME INCLUDED*****',/)
      ELSE
        WRITE(93,623)
623     FORMAT(15X,'*****SOOT PRODUCTION IS NOT INCLUDED*****',/)
      END IF
      IF (JFLAG.EQ.1) THEN
        WRITE(93,743)
743     FORMAT(15X,'INITIAL TIME STEP =MIN OF DTSET AND DTOU-STAB',/)
      ELSE
        WRITE(93,745)
745     FORMAT(15X,'*****INITIAL TIME STEP =DTSET*****',/)
      END IF

C ----- DETERMINE G-NUMBER AND INITIAL CLOUD MASS -----
C
      GRPNO=2.0*PI*DP*RC**2.0*NPS(1)
      AMASSO=ROPO*4.*PI*(RC**3.-(RC/XIMAX)**3.)/3.0

C ----- INITIALIZE VARIABLES FOR CHAR SIMULATION -----
C
      IF (ICHAR.EQ.1) THEN
        C = 1.-ASH
        H = 0.
        N = 0.
        O = 0.
        ROPO = (1.-0.46)*ROPO
        HCOAL = 32766.
        VM(1) = 1.E-07
        VM(2) = 1.E-07
        BV(1) = 1.0E-25
        BV(2) = 1.0E-25
        DO 606 I=1,NSIZE

```



```

      RHOP0(I) = (1.-0.46)*RHOP0(I)
606      CONTINUE
      END IF
C
C ----- INITIALIZE VARIABLES FOR COMBUSTION RUNS -----
C
      IF (ITYPE.EQ.3) THEN
        YO2C=0.0
        YV2INF=0.0
        YV2CO=0.0
        VM(2)=1.0E-07
        BV(2)=1.0E+03
      END IF
C
C ----- INITIALIZE THE PARTICLE EMISSIVITY -----
C
      IF (IRAD.EQ.0) THEN
        EMISS=0.0
      ELSE
        EMISS=1.0
      END IF
C
C ----- INITIALIZE REFERENCE CONDITIONS -----
C
      PREF = PRESS
      RHOREF = PRESS*28.97*100./(8.314*TREF)
      TMREF = RHOREF*RC**2/RHOD
C
C ----- INITIALIZE WATER VAPOR MASS FRACTIONS -----
C
      HUMIDY = PGSAT*18.02/(28.97*PRESS)
      YH2OIN = HUMIDY /(1.+HUMIDY)
      YH2OCO = YH2OIN
C
C ----- PRINT OUT INPUT DATA -----
C
      WRITE(93,761)TINF,YO2INF,YCO2IN,YCOINF,YVIN,YH2OIN,TSUR
761      FORMAT(/,'AMBIENT DATA',/,/,/,
1      ' TINF =',E12.4,' YO2INF=',E12.4,' YCO2INF=',E12.4,/,
2      ' YCOINF=',E12.4,' YVIN=',E12.4,' YH2OINF=',E12.4,/,
3      ' TSUR=',E12.4)
      WRITE(93,762)T0,TGC0,YO2CO,YH2OCO,YCO0,YVCO,PRESS,PGSAT
762      FORMAT(/,'CLOUD DATA',/,/,/,
1      ' TEMP PA=',E12.4,' TGC0=',E12.4,' YO2C =',E12.4,/,
2      ' YH2OCO =',E12.4,' YCO =',E12.4,' YVC =',E12.4,/,
3      ' PRESS =',E12.4,' HUMIDY=',E12.4)
      WRITE(93,763)C,H,N,O,HCOAL
763      FORMAT(/,'CCOAL DATA',/,/,/,
1      ' C=',E12.4,' H=',E12.4,' N=',E12.4,' O=',E12.4,/,
2      ' HEATING VALUE=',F8.1)
      WRITE(93,764)ACO,ECO,NCO,NO2CO,NH2OCO,OXDSO
764      FORMAT(/,'CCO OXIDATION KINETICS DATA',/,/,/,
1      ' ACO =',E12.4,' ECO =',E12.4,' NCO =',E12.4,/,
2      ' NO2 =',E12.4,' NH2O =',E12.4,' CO-ON/OFF',E12.4)
      WRITE(93,765)AVG,EVG,NV,NO2V,OXDSV
765      FORMAT(/,'VOLATILE OXIDATION KINETICS DATA',/,/,/,
1      ' AVG =',E12.4,' EVG =',E12.4,' NV =',E12.4,/,
2      ' NO2V =',E12.4,' V-ON/OFF',E12.4)
      WRITE(93,766)DP,RC,ROPO,EMISS
766      FORMAT(/,'SSPRAY DATA',/,/,/,
1      ' DP(M) =',E12.4,' RC(M) =',E12.4,' DENSITY=',E12.4,/,
2      ' EMISS =',E12.4)
      WRITE(93,767)VM(1),VM(2),EV(1),EV(2),BV(1),BV(2),
1      HPYR(1),HPYR(2)
767      FORMAT(/,'PPYROLYSIS KINETICS DATA',/,/,/,
1      ' VM1 =',E12.4,' VM2 =',E12.4,' EV1 =',E12.4,/,

```

```

2      ' EV2      =',E12.4,' BV1      =',E12.4,' BV2      =',E12.4,/,
3      ' HPYR1    =',E12.4,' HPYR2    =',E12.4)
      WRITE(93,768) EC(1),EC(2),EC(3),EC(4),NO21,NO22,NCO23,
      NH2O4,BC(1),BC(2),BC(3),BC(4)
768    $      FORMAT(/,'CCHAR KINETICS DATA',/,/,/,
1      ' EC1(CO) =',E12.4,' EC2      =',E12.4,' EC3      =',E12.4,/,
2      ' EC4      =',E12.4,' NO21     =',E12.4,' NO22     =',E12.4,/,
3      ' NCO23    =',E12.4,' NH2O4    =',E12.4,' BC1      =',E12.4,/,
4      ' BC2      =',E12.4,' BC3      =',E12.4,' BC4      =',E12.4)
      WRITE(93,769)XIMAX,TOUMAX,FNT,FNXI,DTEMP,DTGLMT,DTSET
1      ,NSIZE,NITER,ISTEP,IMETHD,ICHAR
769    $      FORMAT(/,'NUMERICAL ANALYSIS DATA',/,/,/,
1      ' XIMAX    =',E12.4,' TOUMAX =',E12.4,' TOUDIV =',E12.4,/,
2      ' XIDIV    =',E12.4,' TLMT C =',E12.4,' DTGLMT =',E12.4,/,
3      ' DTSET    =',E12.4,' NSIZE =',I12,' ITER NO =',I12,/,
4      ' ISTEP    =',I12,' IMETHD =',I12,' ICHAR =',I12)
      WRITE(93,770)TREF,TMREF
770    $      FORMAT(/,'REFERENCE CONDITIONS',/,/,/,
1      ' TREF     =',E12.4,' TMREF =',E12.4)
      WRITE(93,771)RHOD,CP,LAMDA,NU,FREEL
771    $      FORMAT(/,'GGAS PROPERTIES DATA',/,/,/,
1      ' RHOD     =',E12.4,' CP      =',E12.4,' LAMDA =',E12.4,/,
2      ' NU       =',E12.4,' FREEL   =',E12.4)
      FREEP = FREEL*TINF/(298.*PRESS)
      GRPNO = 2.0*PI*NPS(1)*DPO(1)*RC**2.0
      IOXDCO = INT(OXDSCO)
      IOXDV = INT(OXDVS)
      CPP = 1.18
      WPART = 12.01/C
      WCOAL = WPART

C
C ----- FIND HEATING VALUE OF VOLATILES -----
C
      CALL HVVOL(WCOAL,WCOAL)
      HVV1 = HVV(1)
      HVV2 = HVV(2)

C
C ----- DETERMINE MOLAR COAL COMPOSITION -----
C
      CALL CLCOMP(WCOAL,H,C,N,O,HAC,CCAN,OAC)
      CAH = HAC
      CAN = CCAN
      CAO = OAC

C
C ----- DETERMINE VOLATILE COMPOSITION FOR ROUTE 1 -----
C
      CALL VLCOMP(VM(1),HAC,CCAN,OAC,HAV1,VNV1,OAV1,WVOL1)

C
C ----- DETERMINE VOLATILE COMPOSITION FOR ROUTE 2 -----
C
      CALL VLCOMP(VM(2),HAC,CCAN,OAC,HAV2,VNV2,OAV2,WVOL2)
      WV1 = WVOL1
      WV2 = WVOL2
      VHA1 = HAV1
      VNA1 = VNV1
      VOA1 = OAV1
      VHA2 = HAV2
      VNA2 = VNV2
      VOA2 = OAV2

C
C ----- DETERMINE STOICHIOMETRIC COMBINATION COEFFICIENTS FOR PYROLYSIS -----
C ----- ROUTE 1 -----
C
      CALL STCVOL(HAV1,VNV1,OAV1,SCCO2,SCH2O,SCO2,WVOL1)
      SCCO21 = SCCO2
      SCH2O1 = SCH2O

```

```

      SCO21 = SCO2
C ----- DETERMINE STOICHIOMETRIC COMBINATION COEFFICIENTS FOR PYROLYSIS -----
C ----- ROUTE 2 -----
      CALL STCVOL(HAV2,VNV2,OAV2,SCCO2,SCH2O,SCO2,WVOL2)
      SCCO22 = SCCO2
      SCH2O2 = SCH2O
      SCO22 = SCO2
      WRITE(93,1953) GRPNO
1953      FORMAT(/' GROUP COMB.NO  0 = ',E12.4)
      RCO = RC
      NTOU = INT(FNT)
      NXI = INT(FNXI)
C ----- INITIALIZE PARTICLE PROPERTIES -----
      THETP0 = T0/TREF
      THETG0 = TGC0/TREF
      MPS0 = 1.
      DPS0 = 1.
      DO 50 I=1,NSIZE
        MP0(I) = PI*DPS0(I)**3*RHOP0(I)/6.
      CONTINUE
50
C ----- INITIALIZE TIME AND SPACE STEPS -----
      DTOU = DTSET
      DXI = XIMAX/FNXI
      ADTOU = 10.0D0
      DTTEMP = DTSET
      BDTOU = 10.0D00
      XIPENT = 1.
      IMETH = IT
C ----- DETERMINE INITIAL TIME STEP -----
      CALL DELTOU(XIPENT,JFLAG)
      GRADS = 0.
      RCO2OD = RCO**2.0/RHOD
      RHOP50 = 1.
      IT = 1
      NTOU1 = NTOU + 1
      NXI1 = NXI + 1
      TOU = 0.
      XIC = 0.999999
      XI = 0.
      XIPENT = 1.
      DTOU0 = DTOU
      ICLOUD = INT(1.0001/DXI)+1
      LCLOUD = ICLOUD
C ----- INITIALIZE CONDITIONS FOR PARTICLES OF ALL SIZES -----
      DO 52 L=1,NXI1
        DO 10 I=1,NSIZE
          THETP(L,I) = THETP0
          MPS(L,I) = MPS0
          DPS(L,I) = DPS0
          WMSP(L) = 0.
          CONVS(L,I) = 0.
          HPYRS(L,I) = 0.
          HHETS(L,I) = 0.
          RHOPS(L,I) = RHOP50
          MVS(L,I) = 0.
          MCHS(L,I) = 0.

```

```

      FCU(L,I) = 1.
      YO2W(L,I) = YO2C0
      YCO2W(L,I) = YCO2C0
      YH2OW(L,I) = YH2OC0
10    CONTINUE
52    CONTINUE
C
C ----- DETERMINE THE INITIAL CONDITIONS FOR GAS PROPERTIES -----
C
      HREF = CP*TREF
      HTC0 = CP*TGC0
      HTSC0 = HTC0/HREF
      HTCA0 = CP*TINF
      HTSCA0 = HTCA0/HREF
      THETC0 = TGC0/TREF
      THTCA0 = TINF/TREF
      ROGSC0 = TREF/T0
      YH2O0 = 0.
      ROGSA0 = TREF/TINF
      BVO2A0=YVINP-YO2INF/SCO21
      BHTVA0=YVINP+HTCA0/HVV1
      BVO2C0=YVC0-YO2C0/SCO21
      BHTVC0=YVC0+HTC0/HVV1
C
C ----- INITIALIZE THE GAS PHASE -----
C
      DO 40 K =1,3
      DO 30 L=1,NXIP1
        THETA(L,K) = THTCA0
        HTS(L,K) = HTSCA0
        RHOGS(L,K) = ROGSA0
        ALPHA(L,K) = 0.
        BVO2(L,K)=BVO2A0
        BHTV(L,K)=BHTVA0
        YV(L,K) = YVINP
        YV2(L,K) = YVINP
        YO2(L,K) = YO2INF
        YCO2(L,K) = YCO2IN
        YCO(L,K) = YCOINF
        YH2O(L,K) = YH2OIN
        IF(L.LE.ICLOUD) GO TO 30
        HTS(L,K) = HTSC0
        THETA(L,K) = THETC0
        RHOGS(L,K) = ROGSC0
        YV(L,K) = YVC0
        YV2(L,K) = YVC0
        YO2(L,K) = YO2C0
        YCO2(L,K) = YCO2C0
        YH2O(L,K) = YH2OC0
        BVO2(L,K)=BVO2C0
        BHTV(L,K)=BHTVC0
30      CONTINUE
40      CONTINUE
C
C ----- INITIALIZE CLOUD PROPERTIES AT THE CLOUD SURFACE -----
C
      HTS(ICLOUD,1) = (HTSC0+HTSCA0)*0.5
      YO2(ICLOUD,1) = (YO2C0+ YO2INF)*.5
      YCO2(ICLOUD,1) = (YCO2C0+YCO2IN) *.5
      YH2O(ICLOUD,1) = (YH2OC0 + YH2OIN) *.5
      BVO2(ICLOUD,1)=(BVO2A0+BVO2C0)*0.5
      BHTV(ICLOUD,1)=(BHTVA0+BHTVC0)*0.5
      RHOGS(ICLOUD,1) = TREF/(HTS(ICLOUD,1)*HREF/CP)
C
C ----- INTEGRATE THE GOVERNING EQUATIONS -----
C

```

```

      BINP = YCO2IN/3.6644 + YO2INF/1.3322
      SCBR = DLOG(1. + BINP)
C
C ----- INITIALIZE OTHER VARIABLES -----
C
      ITHIN=0
      ITHIN1=0
      IIGN=0
      DIFF=-100.0
      XITP=100.0
      XITPP=10.0
      ISKIP1=0
      IVOL=1
      DTGAS2=100.0
      TOU = 0.
      DTOUNW = DTOU
      V1CHV1 = 0.
      VOLPRD = 0.
      V2CHV2 = 0.
      V1CHO2 = 0.
      V2CHO2 = 0.
      COCHCO = 0.
      COCHO2 = 0.
      IFIXCO = 0
      DTOU00= DTOU
      DTOUP = DTOU0
      IFIXO2 = 0
      IFIXV1 = 0
      IFIXV2 = 0
      SOOTGN = 0.
      SUMKV2 = 0.
      CSOTNP = 0.
C
C ----- DO LOOP USED TO VARY TIME -----
C
      KKK=0
      DO 100 K=2,NITERN
      DTOUP = DTOU00
      TOU = TOU + DTOU
      KP = K-1
      TIME = THREF *TOU
      IF(MOD(K,ISTEP).EQ.0) THEN
      DTSTEP=TIME-PREVT
      WRITE(90,777) TIME,DTSTEP,DTOU
      WRITE(91,777) TIME,DTS'EP,DTOU
      WRITE(93,777) TIME,DTSTEP,DTOU
      777 1  FORMAT(/,' TIME=',E14.6,' DTSTEP=',E12.4,
      ' DTOU=',E13.5)
      PREVT=TIME
      END IF
C
C ----- REINITIALIZE VARIABLES AFTER EACH TIME STEP -----
C
      XI = 0.
      GCBR = 0.
      WYVPRP = 0.
      WYV2PP = 0.
      VOLGEN = 0.
      XIPR = XIC
      WMASPP = 0.
      CSOOTP = 0.
      WMASSP = 0.
      CSOTNT = 0.
      NCROSS=0
      TGASPR=TINF
      DTGAS=-100.0

```

```

C ----- DO LOOP USED TO VARY POSITION -----
C
C      DO 80 L=2,NXIP1
C        LL = L
C
C ----- STORE THE VALUES OF CURRENT PARTICLE PROPERTIES SO THAT -----
C ----- VALUES FOR K=2 CAN BE CALCULATED -----
C
      XI=XI+DXI
      RAD=RC0/XI
      IF(L.LT.LCLOUD) GO TO 75
      DO 70 I=1,NSIZE
        THETFP(L,I) = THETP(L,I)
        MVSP(L,I) = MVS(L,I)
        YO2WP(L,I) = YO2W(L,I)
        YCO2WP(L,I) = YCO2W(L,I)
        MCHSP(L,I) = MCHS(L,I)
        MPSP(L,I) = MPS(L,I)
        DPSP(L,I) = DPS(L,I)
        RHOPSP(L,I) = RHOPS(L,I)
        FCUP(L,I) = FCU(L,I)
        IF(DPS(L,I).LT.1.E-02) THEN
          LCLOUD = L
          XIC = DXI*REAL(L)
        END IF
      70 CONTINUE
      75 CONTINUE
C
C ----- STORE CURRENT PROPERTIES -----
C
      TGAS = HTS(L,1)*HREF/CP
      YO2P(1) = YO2(L-1,1)
      YO2P(2) = YO2(L,1)
      YO2P(3) = YO2(L+1,1)
      YCO2P(1) = YCO2(L-1,1)
      YCO2P(2) = YCO2(L,1)
      YCO2P(3) = YCO2(L+1,1)
      RHOG = RHOGS(L,1)*RHOREF
C
C ----- EVALUATE THE MASS SOURCE, ENTHALPY SOURCE, SPECIES V.O2, -----
C ----- CO2, CO, H2O SOURCE TERMS . SOME SOURCE TERMS WILL DIFFER -----
C ----- IF XI IS LESS THAN 1. (I.E. BETWEEN CLOUD AND AMBIENCE) -----
C
      CALL SOURCE (WMASPR, WHTSPR, WYVPR, WYV2PR, WYO2PR, WYCO2P,
1        WYH2OP, WBVO2P, WBHTVP,
2        WYCOPR, VVPRS1, VVPRS2, VCOPSS, VO2PSS, HREF, HVV1,
3        XI, XIC, IOXDCO, IOXDV, ITHIN)
      WMSP(L) = WMASPR
C
C ----- USE EQUATION SUBROUTINE TO SOLVE FOR NEW VALUES OF HTS, -----
C ----- YV, YV2, YCO, YCO2, YH2O, YO2, BVO2, AND BHTV. -----
C
      IF (ITHIN.EQ.1) THEN
C ----- SOLVE FOR BVO2 -----
C
        BVO2P(1)=BVO2(L-1,1)
        BVO2P(2)=BVO2(L,1)
        BVO2P(3)=BVO2(L+1,1)
        WBVO2=WBVO2P-WMASPR*BVO2(L,1)
        CALL EQUATION (BVO2C, WBVO2, BVO2P, XI, L, IT)
        BVO2(L,2)=BVO2C
        BVO2(L,3)=BVO2(L,1)
C
C ----- SOLVE FOR BHTV -----

```

```

C      BHTVP(1)=BHTV(L-1,1)
      BHTVP(2)=BHTV(L,1)
      BHTVP(3)=BHTV(L+1,1)
      WBHTV=WBHTVP-WMASPR*BHTV(L,1)
      CALL EQUATION (BHTVC,WBHTV,BHTVP,XI,L,IT)
      BHTV(L,2)=BHTVC
      BHTV(L,3)=BHTV(L,1)
      ELSE

```

```

C      C ----- SOLVE FOR HTS -----
C
      HTSP(1) = HTS(L-1,1)
      HTSP(2) = HTS(L,1)
      HTSP(3) = HTS(L+1,1)
      WHTSP = WHTSPR-WMASPR*HTSP(2)
      CALL EQUATION (HTSC,WHTSP,HTSP,XI,L,IT)
      HTS(L,2) = HTSC
      HTS(L,3) = HTS(L,1)

```

```

C      C ----- SOLVE FOR YV -----
C
      IF(VM(1).LT.1.0E-04) GO TO 421
      YVP(1) = YV(L-1,1)
      YVP(2) = YV(L,1)
      YVP(3) = YV(L+1,1)
      WYVP = WYVPR - WMASPR*YVP(2)
      CALL EQUATION(YVC,WYVP,YVP,XI,L,IT)
      IF(YVC.LT.1.0E-12) YVC=0.0
      YV(L,2) = YVC
      YV(L,3) = YV(L,1)
421    CONTINUE

```

```

C      C ----- SOLVE FOR YV2 -----
C
      YV2C = 0.D0
      IF(VM(2).LT.1.0E-04) GO TO 423
      YV2P(1) = YV2(L-1,1)
      YV2P(2) = YV2(L,1)
      YV2P(3) = YV2(L+1,1)
      WYV2P = WYV2PR - WMASPR*YV2P(2)
      CALL EQUATION(YV2C,WYV2P,YV2P,XI,L,IT)
      IF(YV2C.LT.1.E-12) YV2C=0.0
      YV2(L,2) = YV2C
      YV2(L,3) = YV2(L,1)
423    CONTINUE

```

```

C      C ----- SOLVE FOR YO2 -----
C
      YO2P(1) = YO2(L-1,1)
      YO2P(2) = YO2(L,1)
      YO2P(3) = YO2(L+1,1)
      WYO2P = WYO2PR - WMASPR*YO2P(2)
      CALL EQUATION(YO2C,WYO2P,YO2P,XI,L,IT)
      IF(YO2C.LT.1.0E-12) YO2C=0.0
      YO2(L,2) = YO2C
      YO2(L,3) = YO2(L,1)
      END IF

```

```

C      C ----- SOLVE FOR YCO2 -----
C
      YCO2P(1) = YCO2(L-1,1)
      YCO2P(2) = YCO2(L,1)
      YCO2P(3) = YCO2(L+1,1)
      WYCO2 = WYCO2P- WMASPR*YCO2P(2)
      CALL EQUATION (YCO2C,WYCO2,YCO2P,XI,L,IT)

```

```

IF(YCO2C,LT.1.E-12) YCO2C =0.0
YCO2(L,2) = YCO2C
YCO2(L,3) = YCO2(L,1)
C
C ----- SOLVE FOR YH2O -----
C
YH2OP(1) = YH2O(L-1,1)
YH2OP(2) = YH2O(L,1)
YH2OP(3) = YH2O(L+1,1)
WYH2O = WYH2OP - WMASPR * YH2OP(2)
CALL EQUATION (YH2OC,WYH2O,YH2OP,XI,L,IT)
IF(YH2OC,LT.0.0) YH2OC = 0.
YH2O(L,2) = YH2OC
YH2O(L,3) = YH2O(L,1)
C
C ----- SOLVE FOR YCO -----
C
YCOP(1) = YCO(L-1,1)
YCOP(2) = YCO(L,1)
YCOP(3) = YCO(L+1,1)
WYCOP = WYCOPR - WMASPR*YCOP(2)
CALL EQUATION (YCOC,WYCOP,YCOP,XI,L,IT)
IF(YCOC,LT.1.0E-12) YCOC=1.0E-12
YCO(L,2) = YCOC
YCO(L,3) = YCO(L,1)
C
C ----- DETERMINE YV AND YO2 FROM SHVAB ZELDOVICH VARIABLES IF THE -----
C ----- FLAME IS ESTABLISHED. DETERMINE GAS PHASE CURRENT AND -----
C ----- PREVIOUS GAS PHASE TEMPERATURE WHETHER FLAME IS ESTABLISHED -----
C ----- OR NOT. -----
C
IF (ITHIN.EQ.1) THEN
  IF (XI.GT.XITHIN) THEN
    YVC=BVO2C
    YV(L,2)=YVC
    YV(L,3)=YV(L,1)
    YO2C=0.0
    YO2(L,2)=0.0
    YO2(L,3)=YO2(L,1)
  ELSE
    YVC=0.0
    YV(L,2)=YVC
    YV(L,3)=YV(L,1)
    YO2C=-SCO21*BVO2(L,2)
    YO2(L,2)=YO2C
    YO2(L,3)=YO2(L,1)
  END IF
  TGP = (BHTVP(2)-YV(L,1))*HVV1/CP
  TGC = (BHTVC-YVC)*HVV1/CP
  ELSE
    BVO2(L,2)=YV(L,2)-YO2(L,2)/SCO21
    BHTV(L,2)=YV(L,2)+HTS(L,2)*HREF/HVV1
    TGP = HTSP(2)*HREF/CP
    TGC = HTSC*HREF/CP
  END IF
  RHOGS(L,2) = TREF/TGC
  TGAS = TGP
  HTC = TGC*CP
  TGDIF=ABS(TGC-TGP)
C
C ----- IF THE GAS PHASE TEMPERATURE RISE IS GREATER THAN THE -----
C ----- MAXIMUM ALLOWABLE TEMPERATURE RISE THEN A NEW TIME -----
C ----- STEP IS DETERMINED -----
C
IF(TGDIF.GT.DTGLMT) BDOU=ABS(DTGLMT*DOU/TGDIF)
DENGAS = TREF/TGC

```



```

      YVTC = YVC + YV2C
C ----- HERE THE CRITERIA FOR HOMOGENEOUS IGNITION ARE TESTED. -----
C ----- IF THESE CRITERIA ARE MET THEN IGNITION IS SIGNALLED. -----
C ----- FIRST THE CRITERIA WITHOUT RADIATION ARE PRESENTED AND -----
C ----- THEN THE CRITERIA WITH RADIATION. -----
      IF (ITHIN.EQ.0) THEN
        IF (ITYPE.NE.1) THEN
C ----- WITHOUT RADIATION -----
          IF (IRAD.EQ.0) THEN
            IF (L.GT.2) THEN
              TG1=HTS(L-2,I)*HREF/CP
              TG2=HTS(L-1,I)*HREF/CP
              TG3=HTS(L,I)*HREF/CP
            END IF
            IF ((TG2-IGNDIF).GT.TG1.AND.(TG2-IGNDIF).GT.TG3) THEN
              IF (ITYPE.EQ.3) THEN
                IF (TG2.GT.TFLAME) THEN
                  WRITE (90,2356) TIME
                  ITHIN1=1
                END IF
              ELSE
                WRITE (90,2356) TIME
                IIGN=1
              END IF
            END IF
          ELSE
            WRITE (90,2356) TIME
            IIGN=1
          END IF
        ELSE
          C ----- WITH RADIATION -----
          YVDOT = (YVC+YV2C-YV(L,1)-YV2(L,1))/DTOU
          DTGAS=TGAS-TGASPR
          IF (DTGAS.GT.IGNDIF) THEN
            IF (ITYPE.EQ.3) THEN
              IF (TGAS.GT.TFLAME) THEN
                WRITE (90,2356) TIME
                ITHIN1=1
              END IF
            ELSE
              IF (YVDOT.LT.0.0) THEN
                IF (YVDP(L).LT.YVDOT) THEN
                  WRITE (90,2356) TIME
                  IIGN=1
                END IF
              END IF
            END IF
          END IF
          YVDP(L)=YVDOT
          TGASPR=TGAS
        END IF
      END IF
2356      FORMAT (' HOMOGENEOUS IGNITION AT', 'E11.4'), 'SEC')
C ----- WRITE CONDITIONS OUTSIDE THE CLOUD -----
C
      IF (MOD(K,ISTEP).EQ.0) THEN
        IF (INT(XI*100.).LT.25) GO TO 3445
        IF (INT(XI*100.).GT.95) GO TO 3445
        IF (ITYPE.EQ.1) THEN
          WRITE (90,4857) XI,YVC,YV2C,RHOPTC
        END IF
        IF (ITYPE.EQ.2) THEN

```

```

WRITE (90,4857) XI,TGAS,YO2C,YVTC,YCO2C,YCOC,DFARTC,TPARTC
END IF
IF (ITYPE.EQ.3) THEN
  WRITE (90,4857) XI,TGAS,BHTV(L,2),BVO2(L,2),YVC,YO2C,YCO2C,
    YCOC
1
END IF
3445 CONTINUE
END IF
IF (DABS(TGC-T0).GT.DTEMPL) XIPENT = XI
IF (XIPENT.GT.XIMAX) XIPENT = XIMAX
TGAS1=TGAS

C ----- DETERMINE THE FLAME POSITION IF COMBUSTION HAS OCCURRED -----
C
IF (ITYPE.EQ.3) THEN
  AMULT=BVO2(L-1,2)*BVO2(L,2)
  IF (AMULT.LT.0.0) THEN
    NCROSS=NCROSS+1
    IF (NCROSS.EQ.1) THEN
      R2=1.0/(XI-DXI)
      R1=1.0/(XI)
      RR=R1-(R2-R1)*BVO2(L,2)/(BVO2(L-1,2)-BVO2(L,2))
      XITHIN=1.0/RR
    END IF
  END IF
END IF

C ----- TEST TO SEE IF THE PROGRAM SHOULD BE EXITED
C
IF (ITYPE.NE.3) THEN
  IF (TGC.GT.(3000.0)) GO TO 999
END IF
IF (TGC.LT.290.0) GO TO 999
IF (TIME.GE.5.0) GO TO 999
IF (XI.LT.XIC) GO TO 67

C ----- CALCULATE PARTICLE PROPERTIES -----
C
DO 66 I=1,NSIZE
  TPARTP = THETP(L,I)*TREF
  CALL QFACT(Q,TPARTP)
  QVALUE=Q
  MPARTP = MPSP(L,I)*MP
  DPARTP = DPSP(L,I)*DPO(I)
  RHOPTP = RHOPSP(L,I)*RHOP0(I)
  MCHPTP = MCHSP(L,I)*MPO(I)/TMREF
  MVPTP = MVSP(L,I)*MPO(I)/TMREF
  MBLOWP = (MCHSP(L,I)+MVSP(L,I))*MPO(I)/TMREF
  XMSREF = MPO(I)
  IF (DPS(L,I).LT.1.0E-02) GO TO 66
  DPARTC = DPS(L,I)*DPO(I)
  RHOPTC = RHOPS(L,I)*RHOP0(I)
  MCHPTC = MCHS(L,I)*MPO(I)/TMREF
  MVPTC = MVS(L,I)*MPO(I)/TMREF
  MBLOWC = (MCHS(L,I)+MVS(L,I))*MPO(I)/TMREF

C ----- DETERMINE THE MASS OF PARTICLE FOR THE CURRENT TIME STEP -----
C
MPSPR = MPS(L,I)
MBLS = MCHS(L,I) + MVS(L,I)
CALL MASSP(MPSPR,MBLS,MPSC)
MPS(L,I) = MPSC
CONVSP = CONV(S,L,I)
HPYRSP = HPYRS(L,I)
HHETSP = HHETS(L,I)
THTPR = THETPP(L,I)

```

```

      MPARTC = MPS(L,I)*MPO(I)
      ROPSPR = RHOPSP(L,I)
C
C
C ----- DETERMINE RADIATIVE HEAT TRANSFER BETWEEN THE PARTICLE AND -----
C ----- THE SURROUNDINGS -----
C
C      CALL RADN(TPARTP,TSUR,EMISS,XMSREF,DPARTP,GRADS)
C
C ----- DETERMINE CURRENT PARTICLE TEMPERATURE -----
C
C      CALL THETAP(THTPR,MPSPR,HFYRSP,HHETSP,CONVSP,GRADS,THTPSC)
C      THETP(L,I) = THTPSC
C      TPARTC = THTPSC*TMREF
C      VVV=MVS(L,I)
C      VOLSOL=0.0
C      VOLFRP=VOLMAT(L,I)
C
C ----- GIVES THE VOLATILE FRACTION LEFT IN THE COAL -----
C
C      CALL VOLFRAC(VVV,VOLSOL,MBLOWP,QVALUE,MPSC,VOLFRP,VOLFRAC)
C      VOLMAT(L,I)=VOLFRAC
C
C ----- HERE THE CRITERIA FOR HETEROGENEOUS IGNITION ARE TESTED. -----
C ----- IF THESE CRITERIA ARE MET THEN IGNITION IS SIGNALLED. -----
C ----- FIRST THE CRITERIA WITHOUT RADIATION ARE PRESENTED AND -----
C ----- THEN THE CRITERIA WITH RADIATION. -----
C
C      IF (ITYPE.EQ.2) THEN
C        IF (IRAD.EQ.0) THEN
C          DIFF=TPARTC-TGAS
C          IF (DIFF.GT.IGNDIF) THEN
C            WRITE (90,2355) TIME
C            GO TO 999
C          END IF
C        ELSE
C          AMMDOT = (DPARTP**3-DPARTC**3)*RHOPTC/(6.0*DPARTC**2*DTOU
1          *TMREF)
C          IF (AMMDOT.GT.1.05E-02) THEN
C            WRITE (90,2355) TIME
C            GO TO 999
C          END IF
C        END IF
C      END IF
2355      FORMAT (' HETEROGENEOUS IGNITION AT',E11.4,'SEC')
C
C ----- WRITE CONDITIONS INSIDE THE CLOUD -----
C
C      IF (MOD(K,ISTEP).EQ.0) THEN
C        IF (INT(XI*100.).LT.75) GO TO 345
C        IF (INT(XI*100.).GT.310) GO TO 345
C        IF (ITYPE.EQ.1) THEN
C          WRITE (90,4857) XI,YVC,YV2C,RHOPTC
C        END IF
C        IF (ITYPE.EQ.2) THEN
C          WRITE (90,4857) XI,TGAS,YO2C,YVTC,YCO2C,YCOC,DPARTC,TPARTC
C        END IF
C        IF (ITYPE.EQ.3) THEN
C          WRITE (90,4857) XI,TGAS,BHTV(L,2),BVO(L,2),YVC,YO2C,YCO2C,
1          YCOC
C        END IF
C      END IF
345      CONTINUE
C      END IF
66      CONTINUE
C
C ----- DETERMINE NEW TIME STEP FOR NEXT TIME STEP -----

```

```

C      CALL DELTOU(XIPENT,JFLAG)
      IF(L.EQ.LCLOUD) THEN
        WMASPR = 2.*WMASPR
        WYVPR = 2.*WYVPR
        WYV2PR = 2.*WYV2PR
      END IF
      IF(L.GT.LCLOUD) THEN
        DX = DXI
        Y1 = WMASPR
        Y2 = WMASPR
        CALL VOLINT(Y1,Y2,XI,DX,YDX)
        GCBR = GCBR + YDX
        Y1 = WYVPR + WYV2PR
        Y2 = WYVPR + WYV2PR
        CALL VOLINT(Y1,Y2,XI,DX,YDX)
        VOLGEN = VOLGEN + YDX
      END IF
      WMASPR = WMASPR
      WYVPR = WYVPR
      WYV2PR = WYV2PR
67      CONTINUE
      IF(ISOOT.EQ.1) THEN
        YVOL1 = YV(L,2)
        YOXY = YO2(L,2)
        YVOL2 = YV2(L,2)
        CALL SOOTPR(VM(1),VM(2),WV1,WV2,YVOL1,YVOL2,YOXY,CSOOT)
        Y1 = CSOOT
        Y2 = CSOOT
        CALL VOLINT(Y1,Y2,XI,DXI,YDX)
        CSOOTP = CSOOT
        CSOTNT = CSOTNT + YDX
      ELSE
        CSOTNT = 0.
      END IF
      PRNU=0.0
80      CONTINUE
96      CONTINUE
C      ----- DETERMINE INSTANTANEOUS VOLATILE YIELD FOR THE CLOUD -----
C
      IF (MOD(K,ISTEP).EQ.0) THEN
        AMASS=0.0
        AXI=1.0
        NN1=INT((1.0/DXI)+2.01)
        NN2=INT((XIMAX/DXI)+1.01)
        DO 1071 Y=NN1,NN2
          AXI=AXI+DXI
          R20=RC/AXI
          R10=RC/(AXI-DXI)
          S20=4.*PI*R20*R20
          S10=4.*PI*R10*R10
          RHO20=RHOPS(Y,1)*ROPO
          RHO10=RHOPS(Y-1,1)*ROPO
          RRHO=(S20*RHO20+S10*RHO10)/(S20+S10)
          VVOL=4./3.*PI*(R10*R10*R10-R20*R20*R20)
          AMASS=AMASS+RRHO*VVOL
1071      CONTINUE
          VLYD=1.0-AMASS/AMASS0
          VTEST=VLYD-VLPR
          VLPR=VLYD
          VDOT=VTEST/DTSTEP
        END IF
C
C      ----- PRINT THE FLAME LOCATION -----
C

```

```

      IF (ITYPE.EQ.3) THEN
      IF (MOD(K,ISTEP).EQ.0) WRITE (93,*) TIME,XITHIN
      END IF
C ----- EXIT IF THE PYROLYSIS IS COMPLETE, IGNITION IS REACHED, OR -----
C ----- THE THIN FLAME HAS REACHED THE CLOUD -----
C
      IF (ITYPE.EQ.1) THEN
      IF (MOD(K,ISTEP).EQ.0) THEN
      WRITE (93,*) TIME,VLYD
      IF (ABS(VDOT).LT.0.0001) THEN
      IF (VLYD.GE.VM(1)) THEN
      IF (VDDOT.LT.1.0E-06) THEN
      GO TO 999
      END IF
      END IF
      END IF
      END IF
      IF (ITYPE.EQ.2) THEN
      IF (IIGN.EQ.1) GO TO 999
      END IF
      IF (ITYPE.EQ.3) THEN
      IF (ITHIN.EQ.1.AND.XITHIN.GT.1.0) GO TO 999
      END IF
      IF (ITHIN1.EQ.1) THEN
      ITHIN=1
      END IF
      IF (MOD(K,ISTEP).EQ.0) THEN
      END IF
      CSOTNP = CSOTNT
      RMGCSC = GCBR/SCBR
      DBCBR = GCBR * 4.*3.1427*RHOD*RCO
      RGCIPC = RMGCSC*3./GRFNO
      SOOT = CSOTNT * (4.*3.1427*RCO*RHOD)
      VOLPRD = VOLGEN*DTOU + VOLPRD
      IF (VOLPRD.GT.0.0) SOOTFR = CSOTNT/VOLPRD
      IF (MOD(K,ISTEP).EQ.0) THEN
      WRITE (91,8490)
      FORMAT (/)
      END IF
      CALL ALPA
8490
C ----- RESET GAS PHASE DEPENDENT VARIABLES -----
C
      DO 88, L = 1,NXIP1
      HTS(L,1) = HTS(L,2)
      YV(L,1) = YV(L,2)
      YV2(L,1) = YV2(L,2)
      YH2O(L,1) = YH2O(L,2)
      YO2(L,1) = YO2(L,2)
      YCO2(L,1) = YCO2(L,2)
      YCO(L,1) = YCO(L,2)
      RHOGS(L,1) = RHOGS(L,2)
      ALPHA(L,1) = ALPHA(L,2)
      BVO2(L,1)=BVO2(L,2)
      BHTV(L,1)=BHTV(L,2)
88      CONTINUE
      JFLAG = 1
C ----- DETERMINE THE NEW TIME STEP -----
C
      CALL DELTOU(XIPENT,JFLAG)
200      CONTINUE
999      CONTINUE
19999     CONTINUE

```

```

20001  CONTINUE
      CLOSE(91)
      CLOSE(90)
      CLOSE(93)
      STOP
      END

C ----- THIS SUBROUTINE DETERMINES THE NON DIMENSIONAL MASS BLOWING RATE -----
C
      SUBROUTINE ALPA
      IMPLICIT DOUBLE PRECISION (A-H,O-Z)
      COMMON/GASPRF/HTS(105,3),THETA(105,3),RHOGS(105,3),
1     ALPHA(105,3),YV(105,3),YO2(105,3),YCO2(105,3),
2     YCO(105,3),YH2O(105,3)
      COMMON/SOURMS/WMSP(105)
      COMMON/NUMER/XIMAX,TOUMAX,NXI,NTOU,DTOU,DXI
      COMMON/LOCATION/LL,KP
      INTEGER I,K
      NXIP1 = NXI + 1
      XI = XIMAX
      ALPHA(NXIP1,2) = 0.
      ALPHA(NXI,2) = 0.
      NXIMIN = 2
      DO 10 L = NXI,NXIMIN, -1
      DRODTC = (RHOGS(L,2)-RHOGS(L,1))/DTOU
      DRODTP = (RHOGS(L+1,2)-RHOGS(L+1,1))/DTOU
      WMSPR = WMSP(L+1)
      WMSC = WMSP(L)
      XICUR = FLOAT(L-1)*DXI
      XIP = FLOAT(L)*DXI
      ALPHA(L,2) = ALPHA(L+1,2) + DXI*.5*((WMSPR-DRODTP)
1 /XIP**4 +(WMSC-DRODTC)/XICUR**4)
10     CONTINUE
      ALPHA(1,2) = ALPHA(2,2) + .5*(WMSC-DRODTC)/DXI**3
      RETURN
      END

C ----- THIS SUBROUTINE COMPUTES THE VARIABLE PSI -- WHETHER IT BE -----
C ----- ENTALPY OR SPECIES MASS FRACTION. IT USES THE UPWIND -----
C ----- SCHEME UNTIL THE LAST POINT AND THEN USES A FORWARD -----
C ----- DIFFERENCE SCHEME FOR THE LAST POINT. -----
C
      SUBROUTINE EQUATION (NEWPSI,WPSI,SPSI,XI,I,IT)
      IMPLICIT DOUBLE PRECISION(A-H,O-Z)
      COMMON/GASPRF/HTS(105,3),THETA(105,3),RHOGS(105,3),
$     ALPHA(105,3),YV(105,3),YO2(105,3),YCO2(105,3),
$     YCO(105,3),YH2O(105,3)
      COMMON/NUMER/XIMAX,TOUMAX,NXI,NTOU,DTOU,DXI
      DIMENSION SPSI(5)
      REAL*8 DXI,DT,NEWPSI,WPSI
      INTEGER I,K,NXI
      DATA A,B,C,D/1.0,1.0,1.0,1.0/
      SOURCE = D*WPSI
      IF (I.EQ. NXI+1) THEN
      DPDXI = 0.
      D2PD2X = 2.*(SPSI(1) - SPSI(2))/(DXI*DXI)
      ELSE
      IF (ALPHA(I,1).GE.0.0) THEN
      DPDXI = (SPSI(3) - SPSI(2))/(DXI)
      ELSE
      DPDXI = (SPSI(2) - SPSI(1))/(DXI)
      END IF
      D2PD2X = (SPSI(3) - 2.*SPSI(2) + SPSI(1))/(DXI*DXI)
      END IF
      ADVECT = B*(XI**4)*ALPHA(I,1) * DPDXI
      DIFFUS = C*(XI**4) * D2PD2X

```

```

NEWPSI = (DTOU/(A*RHOGS(I,1)))*(SOURCE+DIFFUS+ADVECT)
$      + SPSE(2)
      RETURN
      END

```

```

C ----- THIS SUBROUTINE PERFORMS VOLUME INTEGRATIONS -----
C

```

```

      SUBROUTINE VOLINT(Z1,Z2,X,DX,YDX)
      IMPLICIT DOUBLE PRECISION (A-H,O-Z)
      Y1 = Z1/X**4
      Y2 = 0.
      IF(DABS(X-DX).GT.1.0E-06) Y2 = Z2/(X-DX)**4
      YDX = (Y1+Y2)*.5*DX
      RETURN
      END

```

```

C ----- HERE THE CONVECTIVE HEAT TRANSFER BETWEEN THE PARTICLES -----
C ----- AND THE BULK GAS IS CALCULATED. -----
C

```

```

      SUBROUTINE CONV(QCONV,DP,TP,TGAS,M)
      IMPLICIT DOUBLE PRECISION (A-Z)
      COMMON/GASPRP/RHOD,CP,LAMDA,NU,FREFF
      CALL F3LOW(BLOWC,DP,M)
      CALL FKNUD(CKNUD,DP)
      QCONV = NU*LAMDA*(TP-TGAS)*3.14159*DP*CKNUD*BLOWC
      RETURN
      END

```

```

C ----- FINDS THE CONVECTIVE HEAT TRANSFER BETWEEN THE PARTICLES -----
C ----- AND BULK GAS PER UNIT VOLUME -----
C

```

```

      SUBROUTINE HTCONV(VCONVS)
      IMPLICIT DOUBLE PRECISION(A-H,O-Z)
      REAL*8 MCHSP,MVSP, MPSP,MVS,MCHS,MPS,MPO,MBLOW,NPS
      COMMON/PARTSP/THETPP(105,5),MVSP(105,5),MCHSP(105,5),
1      MPSP(105,5),DPSP(105,5),RHOPSP(105,5),FCUP(105,5),
2      YO2W(105,5),YCO2W(105,5),YH2OW(105,5)
      COMMON/SIZEIN/NSIZE,NPS(5),DPO(5),RHOP(5),MPO(5)
      COMMON/REFCON/TREF,TMREF,RCOROD,HREF
      COMMON/LOCATION/LL,KP
      COMMON/PARTS/THETP(105,5),MVS(105,5),MCHS(105,5),MPS(105,5),
1      DPS(105,5),RHOPS(105,5),FCU(105,5),HPYRS(105,5),HHETS(105,5),
2      CONVS(105,5)
      COMMON/GAS/TGAS,YO2P(5),YCO2P(5),YH2OP(5)
      CALCULATE THE HEAT TRANSFER FROM GAS TO PARTICLES/VOLUME
      VCONVS = 0.
      TEGAS = TGAS
      DO 10 I=1,NSIZE
      DPART = DPSP(LL,I)*DPO(I)
      TPART = THETPP(LL,I)*TREF
      MBLOW = (MCHSP(LL,I)+MVSP(LL,I))*MPO(I)*TMREF
      CALL CONV(QCONV,DPART,TPART,TEGAS,MBLOW)
      VCONVS = VCONVS + QCONV*NPS(I)*RCOROD/HREF
      CONVS(LL,I) = QCONV*TMREF/(MPO(I)*HREF)
10      CONTINUE
      RETURN
      END

```

```

C ----- FINDS THE HETEROGENEOUS REACTION RATES -----
C

```

```

      SUBROUTINE SURFR(MDHETT,TP,YO2W,YCO2W,YH2OW,DP,MDO2,MDCO2,
5      MDH2O,MDCO,MBLOW,HHETR)
      IMPLICIT DOUBLE PRECISION (A-H,O-Z)
      REAL*8 MDHET,MDHETT,MDO2,MDCO2,MDCO,MBLOW,NO21,NO22,NC023,
1      NCO4,NH2O4,MDH2O
      DIMENSION MDHET(4)

```

```

REAL*8 NU1,NU2,NU3,NU4
COMMON/CHKIN/NU1,NU2,NU3,NU4,HC1,HC2,HC3,HC4,NO21,NO22
1 ,NCO23,NH2O4,BC(4),EC(4)
COMMON/AMBDAT/PRESS,TINF
DATA NU1,NU2,NU3,NU4/1.332,2.664,3.664,1.500/
DATA HC1,HC2,HC3,HC4/9242,32806,14321,10932/
MDHETT = 0.
IF(DP.LT.0..OR.TP.LT.290.) THEN
105 WRITE(1,105) DP,TP
FORMAT(2X,'DP OR TP < 0. DP,TP ARE ',2(E12.4,2X))
END IF
AREA = 3.14159*DP**2
J =1
RU = 8.314
RHOW = PRESS*100.*30./(RU*TP)
FKFAC = BC(J)*DEXP(-EC(J)/(RU*TP))
MDHET(J) = FKFAC*YO2W**NO21*AREA*RHOW
MDHETT = MDHET(J) + MDHETT
J=2
FKFAC = BC(J)*DEXP(-EC(J)/(RU*TP))
MDHET(2) = FKFAC*YO2W**NO22*AREA*RHOW
MDO2 = - MDHET(1)*NU1 - MDHET(2) * NU2
MDHETT = MDHETT+MDHET(2)
J=3
FKFAC = BC(J)*DEXP(-EC(J)/(RU*TP))
MDHET(J) = FKFAC*YCO2W**NCO23*AREA*RHOW
MDHETT = MDHETT + MDHET(J)
J=4
FKFAC = BC(4)*DEXP(-EC(4)/(RU*TP))
MDHET(J) = FKFAC * YH2OW**NH2O4*AREA*RHOW
MDH2O = -MDHET(J)*NU4
MDCO2 = MDHET(2) * (1.+NU2) - MDHET(3) * NU3
MDCO = MDHET(1) * (1.+NU1) + MDHET(3) * (1.+NU3)
1 + MDHET(4)* (1. +NU4)
1 HHETR = MDHET(1) * HC1 + MDHET(2) * HC2 - MDHET(3) * HC3
- MDHET(4)*HC4
MDHETT = MDHETT + MDHET(J)
RETURN
END
C
C ----- USES THE COMPETING REACTION MODEL TO DETERMINE -----
C ----- PYROLYSIS RATES -----
C
SUBROUTINE COMPR(MDVOL,MDVOLT,FCU,TP,SUMFCU,THPYR)
IMPLICIT DOUBLE PRECISION (A-H,O-Z)
COMMON/COMPRIN/ BV(2),EV(2),VM(2),HPYR(2),HVV(2)
COMMON/VOLYLD/WPART,VOLFR
REAL*8 MDVOL,MDVOLT,HC0
DIMENSION MDVOL(2)
MDVOLT = 0.
NP =2
RU = 8.314
SUMFCU = 0.
THPYR = 0.0
DO 10 J=1,NP
MDVOL(J) = 0.
IF(VM(J).LT.1.E-05) GO TO 10
FKFAC = BV(J)*DEXP(-EV(J)/(RU*TP))
FCUFKF = FCU*FKFAC
MDVOL(J) = FCU*FKFAC*VM(J)
MDVOLT = MDVOLT + MDVOL(J)
SUMFCU = SUMFCU+ FCUFKF
THPYR = THPYR + HPYR(J) * MDVOL(J)
10 CONTINUE
Z = 0.
DO 17 J=1,NP

```



```

VO2PSS = VO2PSS + ( MDO2+OO2VOL) *NPS(I)*RCOROD
VCO2SS = VCO2SS + ( MDCO2+CCO2VO)*NPS(I)*RCOROD
VCOPSS = VCOPSS + MDCO*NPS(I)*RCOROD
VCPRSS = VCPRSS + MDHETT*NPS(I)*RCOROD
VHTMSH = VHTMSH + MDHETT*(1.+VOLHET)*NPS(I)*RCOROD*
1      CP*TPART/HREF
VHTRSS = VHTRSS + HHETRS
VH2OSS = VH2OPS+( MDH2O+HH2OVO)*NPS(I)*RCOROD
RHOPST = RHOPSP(LL,I)
MCHSC = MDHETT*TMREF/MP0(I)
MCHS(LL,I) = MCHSC
DPSPT = DPSP(LL,I)
CHSCM = MCHSC*(1.+VOLHET)
CALL DCUR (DPSPT,CHSCM,RHOPST,DPSC)
DPS(LL,I) = DPSC
HHETS(LL,I) = (HHETR+MDHETT*HVOLHT) * TMREF / (HREF * MP0(I))
BLOWM = (MCHS(LL,I)+VOLS(LL,I)+MVS(LL,I))*MP0(I)/TMREF
CALL WALMSF(YO2P(2),YCO2P(2),YH2OP(2),TPART,YO2WC,YCO2WC,
1      YH2OWC,DPART,BLOWM)
YO2W(LL,I) = YO2WC
YCO2W(LL,I) = YCO2WC
YH2OW(LL,I) = YH2OWC
10     CONTINUE
      RETURN
      END
C
C ----- THE MOLAR COMPOSITION OF THE COAL IS DETERMINED HERE -----
C
      SUBROUTINE CLCOMP(WCOAL,H,C,N,O,HAC,CCAN,OAC)
      IMPLICIT DOUBLE PRECISION(A-Z)
      CAT = C/12.01
      HAC = H/(1.01*CAT)
      CCAN = N/(14.01*CAT)
      OAC = O/(16.*CAT)
      WCOAL = 12.01+1.01*HAC+14.01*CCAN+16.*OAC
      WRITE(93,25)HAC,CCAN,OAC,WCOAL
25     1      FORMAT(/,'CCOAL ANALYSIS-ATOM BASIS',/,/,
1      'H =',E12.4,' N =',E12.4,' O =',E12.4,' MW =',E12.4)
C25    1      FORMAT(COAL ANALYSIS:MASS BASIS',/,/,2X,'H,C,N,O = ',
C      1      4(E12.4,2X),/,2X,' COAL ANALYSIS:ATOM BASIS',/,2X,
C      2      ' H = ',E12.4,' C = 1.0', ' N = ',E12.4,' O = ',E12.4,/,2X,
C      3      ' MOL.WT.OF COAL = ',E12.4,/)
      RETURN
      END
C
C ----- THE HEATING VALUE OF THE VOLATILES IS DETERMINED HERE -----
C
      SUBROUTINE HVVOL(HCOAL,WCOAL)
      IMPLICIT DOUBLE PRECISION(A-H,O-Z)
      COMMON/COMPRIN/BV(2),EV(2),VM(2),HPYR(2),HVV(2)
      WC = 12.01
      HFCO2 = -393520
      DO 10 J=1,2
      HVV(J) = 0.
      IF(VM(J).LT.1.E-04) GO TO 10
      HVV(J) = ((HCOAL-HPYR(J))+(1.-VM(J))*HFCO2/WC)/
1      (VM(J))
10     CONTINUE
      WRITE(93,15) HVV(1),HVV(2)
15     1      FORMAT(/,'HHEATING VALUES-VOL 1,VOL 2',/,/,
1      'H HVV1 =',E12.4,' HVV2 =',E12.4)
      RETURN
      END
C
C ----- THE STOICHIOMETRIC COMBINATION COEFFICIENTS FOR -----
C ----- VOLATILE OXIDATION ARE FOUND HERE -----

```

```

IF(VH(J).LT.1.E-05) GO TO 17
IF(MDVOLT.LT.1.E-35) GO TO 17
Z = Z+VH(J)-(MDVOL(J)/MDVOLT)/(WPART+(1.-VH(J))*12.01)
17 CONTINUE
VOLFR = Z*(WPART+12.01)/(1.+Z*12.01)
C WRITE(*,25) MDVOL(1),MDVOL(2),BV(1),BV(2),EV(1),EV(2)
C25 FORMAT(2X,'IN COMPR..MDVOL(J)',6(E12.4,2X))
C WRITE(1,35) FRFAC,FCU,SUMFCU,TP,HPYR(1),HPYR(2)
C35 FORMAT(2X,'IN COMPR.. FRFAC',6(E12.4,2X))
RETURN
END

C ----- FINDS THE RATE THAT O2, CO2, AND CO ARE PRODUCED/DESTROYED -----
C ----- DUE TO HETEROGENEOUS REACTIONS PER UNIT VOLUME -----
C
SUBROUTINE HETPRD(VO2PSS,VCO2SS,VH2OSS,VCOPSS,VCPRSS,VHTRSS,
1 VHTMSH)
IMPLICIT DOUBLE PRECISION (A-H,O-Z)
REAL*8 MVS,MVSP,MCHS,MCHSP,MPS,MPSP,MP0,LAMBDA,NU
REAL*8 MDHET,MDHETT,MLOW,MCHSC,MDO2,MDCO2,MDCO,NPS,MDH2O
COMMON/PARTSP/THETPP(105,5),MVSP(105,5),MCHSP(105,5),
1 MPSP(105,5),DPSP(105,5),RHOPSP(105,5),FCUP(105,5),
2 YO2W(105,5),YCO2W(105,5),YH2OW(105,5)
COMMON/PARTS/THETP(105,5),MVS(105,5),MCHS(105,5),MPS(105,5),
1 DPS(105,5),RHOPS(105,5),FCU(105,5),HPYRS(105,5),HHETS(105,5),
2 CONVS(105,5)
COMMON/REFCON/TREF,TMREF,RCOROD,HREF
COMMON/SIZEIN/NSIZE,NPS(5),DP0(5),RHOP0(5),MP0(5)
COMMON/GASPRP/RHOD,CP,LAMBDA,NU,FREEP
COMMON/AMBDAT/PRESS,TINF
COMMON/LOCATION/LL,KP
COMMON/GAS/TGAS,YO2P(5),YCO2P(5),YH2OP(5)
COMMON/WALP/YO2WP(105,5),YCO2WP(105,5),YH2OWP(105,5)
COMMON/VOLP/VOLMAT(105,5),VOLS(105,5)
COMMON/ICONTR/IVOLS
COMMON/VOLSUR/OO2VOL,CCO2VO,HH2OVO
VHTMSH = 0.
VO2PSS = 0.
VCO2SS = 0.
VCOPSS = 0.
VCPRSS = 0.
VH2OPS = 0.
VHTRSS = 0.
VOLHET = 0.
CO2VOL = 0.
H2OVOL = 0.
O2VOL = 0.
DO 10 I=1,NSIZE
VOLS(LL,I) = 0.
IF(IVOLS.EQ.1) THEN
VLMAT = VOLMAT(LL,I)
CALL HETVOL(VLMAT,VOLHET,HVOLHT,O2VOL,CO2VOL,H2OVOL)
VOLS(LL,I) = MCHSP(LL,I)*VOLHET
END IF
YO2WPP = YO2W(LL,I)
YCO2WW = YCO2W(LL,I)
YH2OWW = YH2OW(LL,I)
DPART = DPSP(LL,I)*DP0(I)
TPART = THETPP(LL,I)*TREF
MLOW = (MCHSP(LL,I)+VOLS(LL,I)+MVSP(LL,I))*MP0(I)/TMREF
CALL SURFR(MDHETT,TPART,YO2WPP,YCO2WW,YH2OWW,DPART,MDO2,MDCO2,
S MDH2O,MDCO,MLOW,HHETR)
OO2VOL = MDHETT*O2VOL
CCO2VO = MDHETT*CO2VOL
HH2OVO = MDHETT*H2OVOL
HHETRS = (HHETR+MDHETT*HVOLHT)*NPS(I)*RCOROD/HREF

```

```

C
SUBROUTINE STCVOL(HAV,NAV,OAV,SCCO2,SCH2O,SCO2,WVOL)
IMPLICIT DOUBLE PRECISION(A-Z)
  SCCO2 = 0.
  SCH2O = 0.
  SCO2 = 0.
  IF(WVOL.LT.1E-03) GO TO 30
  SCCO2 = 44.01/WVOL
  SCO2 = (1.+HAV*.25-OAV*.5)*32./WVOL
  SCH2O = HAV*0.5*18.02/WVOL
30  CONTINUE
  WRITE(93,25) SCO2,SCCO2,SCH2O
25  FORMAT(/,'SSTIOCH.COMB.COEFFICIENTS',/,/,
1    'O O2      =',E12.4,' CO2    =',E12.4,' H2O    =',E12.4)
  RETURN
END

C
C ----- THIS SUBROUTINE GIVES THE SOURCE TERM FOR MASS -----
C ----- SPECIES,ENERGY CONSERVATION EQUATIONS. -----
C
SUBROUTINE SOURCE(WMASPR,WHTSPR,WYVPR,WYV2PR,WYO2PR,WYCO2P,
1  WYH2OP,WBVO2P,WBHTVP,WYCOPR,VVPRS1,VVPRS2
2  ,VCOPSS,VO2PSS,HREF,HV1,XI,XIC,IOXDCO,IOXDV,ITHIN)
IMPLICIT DOUBLE PRECISION (A-H,O-Z)
COMMON/COMPKIN/BV(2),EV(2),VM(2),HPYR(2),HVV(2)
COMMON/STCV/SCCO21,SCH2O1,SCO21,SCCO22,SCH2O2,SCO22
SMCOCO = 0.
SMO2CO = 0.
SCO2CO = 0.
SH2OCO = 0.
SHCOCH = 0.
SMVCH1 = 0.
SMVCH2 = 0.
SMO2C1 = 0.
SMO2C2 = 0.
SHCOCH = 0.
SMCOC1 = 0.
SMCOC2 = 0.
SMCO21 = 0.
SMCO22 = 0.
SMH2O1 = 0.
SMH2O2 = 0.
SHVCH1 = 0.
SHVCH2 = 0.
VHTPRS = 0.
VHTMSH = 0.
VHTMSV = 0.
VHTMST = 0.
VO2PSS = 0.
VCO2SS = 0.
VCOPSS = 0.
VCONVS = 0.
VCPRSS = 0.
VHTRSS = 0.
VH2OSS = 0.
VVCH = 0.
IF (ITHIN.EQ.1) GO TO 50
IF (IOXDCO.NE.1) GO TO 568
CALL COOXD (SMCOCH,SMO2CO,SCO2CO,SH2OCO,SHCOCH)
568 CONTINUE
IF (IOXDV.EQ.0.OR.(VM(1).LT.1.E-04.AND.VM(2).LT.1.E-04))
1 GO TO 50
  I=1
  IF (VM(1).LT.1.E-04) GO TO 569
  CALL VOLOXD(SMVCH1,SMO2C1,SMCOC1,SMCO21,SMH2O1,SHVCH1,I)
569 CONTINUE

```

```

      I=2
      IF(VH(2).GT.1.E-04)
1 CALL VOLOXD(SMVCH2,SMO2C2,SMCOC2,SMCO22,SMH2O2,SHVCH2,I)
50 CONTINUE
      VVPRS1 = 0.
      VVPRS2 = 0.
      VHTPSS = 0.
      IF (XI.LT.XIC ) GO TO 10
      IF(VH(1).GT.1.E-04.OR.VH(2).GT.1.E-04)
1 CALL VOLPRD(VVPRS1,VVPRS2,VHTPSS,VHTMSV)
      CALL HETPRD(VO2PSS,VCO2SS,VH2OSS,VCOPSS,VCPRSS,VHTRSS,VHTMSH)
10 CONTINUE
      VO2PCH = SMO2C1 + SMO2C2 + SMO2CO
      VCO2CH = SMCO21 + SMCO22 + SCO2CO
      VVCH = SMVCH1 + SMVCH2
      VCOPCH = SMCOC1 + SMCOC2 + SMCOCO
      VVPRSS = VVPRS1 + VVPRS2
      VH2OCH = SMH2O1 + SMH2O2 + SH2OCO
      VHTPCH = SHVCH1 + SHVCH2 + SHCOCH
      WYO2PR = VO2PSS + VO2PCH
      WYCO2P = VCO2SS + VCO2CH
      WYVPR = VVPRS1 + SMVCH1
      WYV2PR = VVPRS2 + SMVCH2
      WBVO2P = VVPRS1 + VO2PSS/SCO21
      WYCOPR = VCOPSS + VCOPCH
      WHASPR = VCPRSS + VVPRSS
      WYH2OP = VH2OSS + VH2OCH
      VCONVS = 0.
      IF(XI.LT.XIC) GO TO 20
      CALL HTCONV(VCONVS)
20 CONTINUE
      WHTSPR = VCONVS + VHTPCH + VHTMSH + VHTMSV
      WBHTVP = VCONVS*HREF/HVV1
      IF(DABS(XI-XIC).GT.1.E-03) GO TO 60
      WHASPR = 0.5*(VCPRSS + VVPRSS)
      WHTSPR = (VCONVS+VHTMSH+VHTMSV)*0.5 + VHTPCH
      WYVPR = VVPRS1 *0.5 + SMVCH1
      WYV2PR = VVPRS2*0.5 + SMVCH2
      WYO2PR = VO2PSS *0.5 + VO2PCH
      WBVO2P = (VVPRS1-VO2PSS/SCO21)*0.5
      WBHTVP = VCONVS*0.5*HREF/HVV1
      WYCO2P = VCO2SS *0.5+VCO2CH
      WYH2OP = VH2OSS*0.5 + VH2OCH
      WYCOPR = VCOPSS * 0.5+VCOPCH
60 CONTINUE
      RETURN
      END

C ----- HERE THE MOLAR COMPOSITION OF THE VOLATILE IS DETERMINED -----
C
      SUBROUTINE VLCOMP(VOLFR,HAC,CCAN,OAC,HAV,NAV,OAV,WV)
      IMPLICIT DOUBLE PRECISION(A-Z)
      WCOAL = 12.01*1.+1.01*HAC+14.01*CCAN+16.*OAC
      VMATOM = 0.
      HAV = 0.
      NAV = 0.
      OAV = 0.
      IF(VOLFR.LT.1.E-04) GO TO 90
      VMATOM = 1.-(1.-VOLFR)*WCOAL/12.01
      HAV = HAC/VMATOM
      NAV = CCAN/VMATOM
      OAV = OAC/VMATOM
90 CONTINUE
      WV = 12.01+1.01*HAV+14.01*NAV+16.*OAV
      CAV = 1.
      WRITE(93,25) VOLFR,VMATOM,WV,HAV,CAV,NAV,OAV

```

```

25      FORMAT(/,'VOLATILE ANALYSIS-ATOM BASIS',/,/,
1      'V VOLFR =',E12.4,' VMATOM=',E12.4,' MW VOL =',E12.4
2      ,/,,'H H=',E12.4,' C=',E12.4,' N=',E12.4,' O=',E12.4)
      RETURN
      END
C
C ----- HERE THE VOLATILE PRODUCTION RATES ARE DETERMINED -----
C
      SUBROUTINE VOLFRD(VVPRS1,VVPRS2,VHTPSS,VHTMSV)
      IMPLICIT DOUBLE PRECISION (A-H,O-Z)
      REAL*8 MVS,MVSP,MCHS,MCHSP,MPS,MPSP,MP0
      REAL*8 MDVOL,MVOL,MDVOLT,NPS,NU,LAMDA
      REAL*8 MVOL3,MCO,MV,MVSC
      COMMON/SIZEIN/NSIZE,NPS(5),DP0(5),RHOP0(5),MP0(5)
      COMMON/PARTS/THETP(105,5),MVS(105,5),MCHS(105,5),MPS(105,5),
1      DPS(105,5),RHOPS(105,5),FCU(105,5),HPYRS(105,5),HNETS(105,5),
2      CONVS(105,5)
      COMMON/PARTSP/THETPP(105,5),MVSP(105,5),MCHSP(105,5),
1      MPSP(105,5),DPSP(105,5),RHOPSP(105,5),FCUP(105,5),
2      YO2W(105,5),YCO2W(105,5),YH2OW(105,5)
      COMMON/GASPRP/RHOD,CP,LAMDA,NU,FREF
      COMMON/REFCON/TREF,THREF,RCOROD,HREF
      COMMON/AMBDAT/PRESS,TINF
      COMMON/LOCATION/LL,KP
      COMMON/VOLF/VOLMAT(105,5),VOLS(105,5)
      COMMON/ICONTR/IVOLS
      DIMENSION MDVOL(2)
C      COMPUTE MASS OF VOLATILES PRODUCED PER VOLUME
C      FOR PARTICLES OF ALL SIZES
      VVPRS = 0.
      VHTMSV = 0.
      VVPRS1 = 0.
      VVPRS2 = 0.
      VHTPSS = 0.
      DO 10 I=1,NSIZE
      FCUT = FCUP(LL,I)
      TPART = THETPP(LL,I)*TREF
      CALL COMPR(MDVOL,MDVOLT,FCUT,TPART,SUMFU,THPYRS)
      SUMFUS = SUMFU*THREF
      HPYRS(LL,I) = THPYRS*THREF/HREF
      FCUTP = FCUT
      IF (IVOLS.EQ.1.AND.VOLMAT(LL,I).GT.1.E-02) THEN
      SUMFUS = SUMFUS + VOLS(LL,I)/VOLMAT(LL,I)
      END IF
      CALL FCUTIL(SUMFUS,FCUTP,FCUTC)
      FCU(LL,I) = FCUTC
      ROPSP = RHOPSP(LL,I)
      MVSC = MDVOLT*THREF
      DIASP = DPSP(LL,I)
      CALL REOP(ROPSP,MVSC,DIASP,ROPSC)
      MVS(LL,I) = MVSC
      RHOPS(LL,I) = ROPSC
      VVPRS1 = MDVOL(1)*NPS(I)*MP0(I)*RCOROD+ VVPRS1
      VVPRS2 = MDVOL(2)*NPS(I)*MP0(I)*RCOROD+ VVPRS2
      VHTPSS = THPYRS*MP0(I)*NPS(I)*RCOROD/HREF + VHTPSS
      VHTMSV = VHTMSV+MVS(LL,I)*CP*TPART*NPS(I)*MP0(I)*RCOROD/HREF
10      CONTINUE
      RETURN
      END
C
C ----- HERE THE CO OXIDATION RATE ARE FOUND -----
C
      SUBROUTINE COOXD(SMCOCH,SMO2CH,SMCO2C,SMH2OC,SHCOCH)
      IMPLICIT DOUBLE PRECISION(A-Z)
      INTEGER LL,KP
      COMMON/COKIN/ACO,ECO,NCO,NO2CO,NH2OCO

```

```

COMMON/GASPRF/HTS(105,3),THETA(105,3),RHOGS(105,3),
1 ALPHA(105,3),YV(105,3),YO2(105,3),YCO2(105,3),
2 YCO(105,3),YH2O(105,3)
COMMON/LOCATION/LL,KP
COMMON/REFCON/TREF,THREF,RCOROD,HREF
COMMON/DENS/RHOG
COMMON/GAS/TGAS,YO2P(5),YCO2P(5),YH2OP(5)
COMMON/ATM/HUMIDY
COMMON/YCOIMPLCT/COCHCO,COCHO2
RCO = 282990./28.01
NCOT = NCO + NO2CO + NH2OCO
YYCO = YCO(LL,1)
YYO2 = YO2(LL,1)
YYH2O = YH2O(LL,1)
IF(YYH2O.LT.1.E-06) YYH2O = HUMIDY
AA = -ACO*RHOG**(NCOT)*DEXP(-ECO/(8.314*TGAS))
MCOCH = -ACO*RHOG**(NCOT)*YYCO**NCO*YYO2**NO2CO*
1 YYH2O**NH2OCO*DEXP(-ECO/(8.314*TGAS))
MCO2CH = - MCOCH*44.01/28.01
HCOCH = DABS(MCOCH)*HCO
MO2CH = MCOCH*16./28.01
SMCOCH = MCOCH*RCOROD
SMCO2C = MCO2CH*RCOROD
SMO2CH = MO2CH*RCOROD
SHCOCH = HCOCH*RCOROD/HREF
SMH2OC = 0.
COCHCO = AA*YYO2**NO2CO*RCOROD
COCHO2 = AA*YYCO**NCO*RCOROD*16./28.01
RETURN
END

C ----- HERE THE VOLATILE OXIDATION RATES ARE FOUND -----
C
SUBROUTINE VOLOXD(SMVCH,SMO2CH,SMCOCH,SMCO2C,SMH2OC,SHVCH,I)
IMPLICIT DOUBLE PRECISION(A-Z)
INTEGER I
INTEGER LL,KP
COMMON/REFCON/TREF,THREF,RCOROD,HREF
COMMON/GAS/TGAS,YO2P(5),YCO2P(5),YH2OP(5)
COMMON/GASPRF/HTS(105,3),THETA(105,3),RHOGS(105,3),
1 ALPHA(105,3),YV(105,3),YO2(105,3),YCO2(105,3),
2 YCO(105,3),YH2O(105,3)
COMMON/V2PROF/YV2(105,3)
COMMON/VOLKIN/AVG,EVG,NV,NO2V
COMMON/DENS/RHOG
COMMON/VOLPRP/WV1,WV2,VHA1,VNA1,VOA1,VHA2,VNA2,VOA2,HVV1,HVV2
COMMON/STCV/SCCO21,SCH2O1,SCO21,SCCO22,SCH2O2,SCO22
COMMON/LOCATION/LL,KP
COMMON/YVIMPLCT/V1CHV1,V1CHO2,V2CHV2,V2CHO2
GO TO (20,40),I
20 CONTINUE
VY = YV(LL,1)
SCO2 = SCO21
SCCO2 = SCCO21
SCH2O = SCH2O1
HCVOL = HVV1
GO TO 50
40 CONTINUE
SCCO2 = SCCO22
SCH2O = SCH2O2
SCO2 = SCO22
HCVOL = HVV2
VY = YV2(LL,1)
50 CONTINUE
IF (VY.LT.0.0) VY=0.0
O2Y = YO2(LL,1)

```

```

AREA = 3.14159*DP**2.
RHOW = PRESS*100.*30./(RU*TP)
DAMO2 = RHOW*DP*DEXP(-EC(1)/(RU*TP))*BC(1)/RHOD
DAMCO2 = RHOW*DP*DEXP(-EC(3)/(RU*TP))*BC(3)/RHOD
DAMH2O = RHOW*DP*DEXP(-EC(4)/(RU*TP))*BC(4)/RHOD
XY = 1.
IF(PSIW.GT.0.01) THEN
  XY = (1.-X)/PSIW
  OO = OO2VOL/M
  CC = CC02VO/M
  HH = HH2OVO/M
ELSE
  XY = 1.
  OO = 0.
  CC = 0.
  HH = 0.
END IF
YO2W = (YO2BP*X+OO*(1.-X))/(1.+DAMO2*XY)
YCO2W = (YCO2BP*X+CC*(1.-X))/(1.+DAMCO2*XY)
YH2OW = (YH2OBP*X+HH*(1.-X))/(1.+DAMH2O*XY)

RETURN
END

C
C ----- HERE WE FIND THE FRACTION OF COAL UNUTILIZED -----
C
SUBROUTINE FCUTIL(SUMFUS,FCUTP,FCUTC)
IMPLICIT DOUBLE PRECISION(A-H,O-Z)
COMMON/NUMER/XIMAX,TOUMAX,NXI,NTOU,DTOU,DXI
COMMON/FCUT/FFCUT
FCUTC = FCUTP - SUMFUS*DTOU
FFCUT = FCUTC
RETURN
END

C
C ----- THIS SUBROUTINE FINDS THE PARTICLE DENSITY -----
C
SUBROUTINE RHOP (RHOPSP,MVS,DIASP,RHOCUR)
IMPLICIT DOUBLE PRECISION (A-H,O-Z)
REAL*8 MVS
COMMON/NUMER/XIMAX,TOUMAX,NXI,NTOU,DTOU,DXI
RHOCUR = RHOPSP-MVS*DTOU/DIASP**3
RETURN
END

C
C ----- THIS SUBROUTINE DETERMINES THE PARTICLE DIAMETER -----
C
SUBROUTINE DCUR (DPREV,MCHS,RHOPPR,DCR)
IMPLICIT DOUBLE PRECISION (A-H,O-Z)
COMMON/NUMER/XIMAX,TOUMAX,NXI,NTOU,DTOU,DXI
REAL*8 MCHS
DCR3=DPREV**3-MCHS*DTOU/RHOPPR
IF(DCR.LT.0.0) THEN
  DCR=DPREV
  ADDTM=DPREV**3*RHOPPR/MCHS
  WRITE(1,20) ADDTM
20  FORMAT(2X,'DP MAY BE<0 ,ADD BURN TIME 'TOU-',E12.4)
ELSE
  DCR=DCR3**.3333333333
END IF
RETURN
END

C
C ----- CALCULATE PARTICLE TEMPERATURE INPUT -----

```

```

C ----- PREVIOUS VALUE AND HEAT CONVECTED, HEAT LIBERATED -----
C ----- HEAT FOR PYROLYSIS AND HEAT RADIATED -----
C
SUBROUTINE THETAP(THTPR, MPSPR, HPYRSP, HHETSP, CONVSP, QRADE, THTPSC)
IMPLICIT DOUBLE PRECISION (A-H, O-Z)
REAL*8 MPSPR, LAMDA, NU
COMMON/NUMER/XIMAX, TOUMAX, NXI, NTOU, DTOU, DXI
COMMON/GASPRP/RHOD, CP, LAMDA, NU, FREEP
COMMON/FARPRP/CPF
COMMON/LOCATION/LL, KP
COMMON/THETP/ADTOU, BDTOU, DTSET
COMMON/REFCON/TREF, THREF, RCOROD, HREF
COMMON/LIMIT/DTGLMT
DTHETA = (HPYRSP+HHETSP-CONVSP-QRADE)*CP/(CPF*MPSPR)
THTPSC = THTPR + DTHETA*DTOU
DTPDIF = (THTPSC-THTPR) *TREF
IF (DABS(DTPDIF).GT.DTGLMT) ADTOU = DABS(DTGLMT)/(TREF*DTHETA)
IF (THTPSC.LT.0.0.OR.THTPSC.GT.20.0) THEN
10 WRITE(*,10) THTPSC, CONVSP, HPYRSP, HHETSP
   FORMAT(6X, ' THE TEMPERATURE OF THE PARTICLE GOES BELOW ZERO',
$      /, ' -- SOMETHING WRONG > THTPSC, CONVSP, HPYRSP, HHETSP > ', /,
$      4(E12.4))
   CALL EXIT
   ELSE
   RETURN
   END IF
   END

C
C ----- THIS SUBROUTINE FINDS THE MASS OF THE PARTICLES -----
C
SUBROUTINE MASSP(MPSPR, MBLS, MPSC)
IMPLICIT DOUBLE PRECISION (A-H, O-Z)
REAL*8 MPSPR, MBLS, MPSC
COMMON/NUMER/XIMAX, TOUMAX, NXI, NTU, DTOU, DXI
COMMON/LOCATION/LL, KP
IF (MPSPR.GT.MCLS*DTOU) THEN
   MPSC=MPSPR-MBLS*DTOU
   ELSE
   END IF
   RETURN
   END

C
C ----- HERE THE KNUDSON CORRECTION FACTOR IS FOUND -----
C
SUBROUTINE FKNUD(CKNUD, DP)
IMPLICIT DOUBLE PRECISION (A-Z)
COMMON/GASPRP/RHOD, CP, LAMDA, NU, FREEP
CKNUD=1.0-FREEP/(FREEP+0.17*DP)
RETURN
END

C
C ----- HERE THE BLOWING CORRECTION FACTOR IS DETERMINED -----
C
SUBROUTINE FBLOW(BLOWC, DP, M)
IMPLICIT DOUBLE PRECISION (A-Z)
COMMON/GASPRP/RHOD, CP, LAMDA, NU, FREEP
A = CP*M/(3.14159*LAMDA*NU*DP)
BLOWC = 1.0
IF (A .GT. 120.) GO TO 10
IF (A .GT. 0.01)
1 BLOWC = A/(DEXP(A)-1.)
RETURN
10 CONTINUE
WRITE(1,15) A

```



```

15      FORMAT(5X,'DIMENSIONLESS BURNING RATE > ',E12.6)
      END
C
C ----- THIS SUBROUTINE CALCULATES THE DTOU FOR THE NEXT TIME STEP -----
C
      SUBROUTINE DELTOU(XIPENT,JFLAG)
      IMPLICIT DOUBLE PRECISION (A-H,O-Z)
      COMMON/NUMER/XIMAX,TOUMAX,NXI,NTOU,DTOU,DXI
      COMMON/THETP/ADTOU,BDTOU,DTSET
      COMMON/DTIME/DTTEMP
      DTOU0=DTTEMP
      DTOU1 = DABS(ADTOU)
      DTOU2 = DABS(BDTOU)
      DTTEMP = MIN(DTOU1,DTOU2,DTOU0)
      IF(JFLAG.EQ.1) THEN
      DTOU3=DABS((0.295*DXI**2.0)/(XIPENT**4.0))
      DTOU = MIN(DTTEMP,DTOU3)
      END IF
      RETURN
      END
C
C ----- HERE THE AMOUNT OF VOLATILES BURNING IN-SITU IS ACCOUNTED FOR -----
C
      SUBROUTINE HETVOL(VLMAT,VOLHET,HVOLHT,O2VOL,CO2VOL,H2OVOL)
      IMPLICIT DOUBLE PRECISION(A-H,O-Z)
      COMMON/COMPRIN/BV(2),EV(2),VM(2),HPYR(.),HVV(2)
      COMMON/STCV/SCCO21,SCH2O1,SCO21,SCCO22,SCH2O2,SCO22
      VOLHET = VLMAT/(1.-VLMAT)
      HVOLHT = VOLHET*HVV(1)
      O2VOL = -VOLHET*SCCO21
      CO2VOL = VOLHET*SCCO21
      H2OVOL = VOLHET*SCH2O1
      RETURN
      END
C
C ----- HERE THE Q-FACTOR IS DETERMINED -----
C
      SUBROUTINE QFACT(Q,TP)
      IMPLICIT DOUBLE PRECISION(A-H,O-Z)
      COMMON/NUMER/XIMAX,TOUMAX,NXI,NTOU,DTOU,DXI
      COMMON/COMPRIN/BV(2),EV(2),VM(2),HPYR(2),HVV(2)
      COMMON/REFCON/TREF,THREF,RCOROD,HREF
      COMMON/LOCATION/LL,KF
      FKV2 = BV(2)*DEXP(-EV(2)/(8.314*TP))
      FKV1 = BV(1)*DEXP(-EV(1)/(8.314*TP))
      Q = 1.0+VM(2)*FKV2/(VM(1)*FKV1)
      RETURN
      END
C
C ----- DETERMINES THE FRACTION OF VOLATILES REMAINING IN THE COAL -----
C
      SUBROUTINE VOLFRAC(VOLRATE,VOLS,BLOW,Q,FRMASS,VOLFRP,VOLFRC)
      COMMON/NUMER/XIMAX,TOUMAX,NXI,NTOU,DTOU,DXI
      DPVM = -DTOU*(VOLRATE/Q + VOLS)/FRMASS
      VOLFRC = VOLFRP + DPVM
      IF(VOLFRC.LT.0.) VOLFRC = 0.
      RETURN
      END
C
C ----- HERE THE RADIATION TRANSFER IS CALCULATED -----
C
      SUBROUTINE RADN(TPART,TSUR,EMISS,XMSREF,DPART,QRADS)
      IMPLICIT DOUBLE PRECISION(A-H,O-Z)
      REAL*8 MPO,NPS
      COMMON/REFCON/TREF,THREF,RCOROD,HREF
      CALL FACTOR(F)

```

```

      SMVCH = 0.
      SMO2CH = 0.
      SMC0CH = 0.
      SMC02C = 0.
      SMH2OC = 0.
      SEVCH = 0.
      AA = -AVG*RHOG**(NV+NO2V)*DEXP(-EVG/(8.314*TGAS))
      MVCH = -AVG*RHOG**(NV+NO2V)*VY**NV*O2Y**NO2V*
1     DEXP(-EVG/(8.314*TGAS))
      HVCH = DABS(MVCH)*BCVOL
      MCO2CH = -MVCH*SCCO2
      MH2OCH = -MVCH*SCH2O
      MO2CH = MVCH*SCO2
      MCOCH = 0.
      SMVCH = MVCH*RCOROD
      SMC02C = MCO2CH*RCOROD
      SMH2OC = MH2OCH*RCOROD
      SMO2CH = MO2CH*RCOROD
      SMC0CH = MCOCH*RCOROD
      SEVCH = HVCH*RCOROD/HREF
      IF(I.EQ.1) THEN
        V1CHV1 = AA*O2Y**NO2V*RCOROD
        V1CHG2 = AA*VY**NV*SCO2*RCOROD
      ELSE
        V2CHG2 = AA*VY**NV**SCO2*RCOROD
        V2CHV2 = AA*O2Y**NO2V*RCOROD
      END IF
      RETURN
      END

C ----- HERE SOOT PRODUCTION IS MODELLED -----
C
C
      SUBROUTINE SOOTPR(VM1,VM2,WV1,WV2,YVOL1,YVOL2,YOXY,CSOOT)
      IMPLICIT DOUBLE PRECISION(A-Z)
      IF(VM1.GT.1.0E-06) THEN
      IF(VM2.GT.1.E-06) THEN
        CSOOT = (YVOL1/WV1+YVOL2/WV2-2.*YOXY/32.)*12.01
      ELSE
        CSOOT = (YVOL1/WV1-2.*YOXY/32.)*12.01
      END IF
      ELSE
        CONTINUE
      END IF
      IF(CSOOT.LT.0.D0) CSOOT = 0.
      RETURN
      END

C ----- HERE THE MASS FRACTIONS OF CO, O2, AND CO2 ARE -----
C ----- CALCULATED AT THE PARTICLE SURFACE -----
C
      SUBROUTINE WALMSF(YO2BP,YCO2BP,YH2OBP,TP,YO2W,YCO2W,YH2OW,DP,M)

      IMPLICIT DOUBLE PRECISION (A-H,O-Z)
      REAL*8 NU,NU1,NU2,NU3,NU4,NO21,NO22,NCO23,NH2O4,LAMDA
      REAL*8 M
      COMMON/GASPRP/RHOD,CP,LAMDA,NU,FRECP
      COMMON/AMBDAT/PRESS,TINF
      COMMON/CHKIN/NU1,NU2,NU3,NU4,HC1,HC2,HC3,HC4,NO21,NO22
1     ,NCO23,NH2O4,BC(4),EC(4)
      COMMON/GAS/TGAS,YO2P(5),YCO2P(5),YH2OP(5)
      COMMON/VOLSUR/OO2VOL,CCO2VO,HH2OVO
      PSIW = M/(4.*3.14159*RHOD*DP*0.5)
      RU = 8.314
      X = 0.
      IF(PSIW.LT.100.0) X= DEXP(-PSIW)

```

```

SYBOC = 5.67E-11
QRADN=F*EMISS*STBOC*(TPART**4-TSUR**4)*3.141627*DPART**2
QRADS=THREF*QRADN/(HREF*XHSREF)
RETURN
END

```

```

C ----- HERE THE VIEW FACTOR IS FOUND (ASSUMED TO BE 1) -----
C
C

```

```

SUBROUTINE FACTOR(F)
IMPLICIT DOUBLE PRECISION(A-H,O-Z)
F=1.0D+00
RETURN
END

```

END

**DATE
FILMED**

7 / 29 / 92