EGG-WTD-9520
September 1991

APR 27 1992

**Idaho
National
Engineering
Laboratory**

*Managed
by the U.S.
Department
of Energy*

INFORMAL REPORT

Test Plan for ISV Laboratory-Pyrolysis Testing

R. E. McAtee

*Work performed under
DOE Contract
No. DE-AC07-76ID01570*

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

This document contains new concepts or the author(s) interpretation of new calculations and/or measurements; accordingly, EG&G Idaho, Inc. is required by the United States Government to include the following disclaimer:

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights. References herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

EGG-WID--9520

DE92 012515

TEST PLAN
FOR ISV LABORATORY-PYROLYSIS TESTING

R. E. McAtee

Published September 1991

Idaho Engineering Laboratory
EG&G Idaho, Inc.
Idaho Falls, Idaho 83415

Prepared for the
U.S. Department of Energy
Idaho Operations Office
Under DOE Contract No. DE-AC07-76ID01570

RECEIVED

de
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

TEST PLAN FOR ISV LABORATORY PYROLYSIS TEST PLAN

REVISION 0

Prepared by	<u> </u>	<u>5/29/91</u>
	R. E. McAtee, ISV Program Test Manager	Date
Reviewed by	<u> </u>	<u>5/30/91</u>
	K. P. Lange, Program Manager	Date
	<u> </u>	<u>5/29/91</u>
	S. O. Bates, Project Manager	Date
	<u> </u>	<u>5/29/91</u>
	J. P. Shea, EIRC Chairman	Date

ABSTRACT

The objective of the laboratory-pyrolysis studies is to obtain information on the high temperature (< 1200 °C) degradation and alteration of organic chemicals and materials similar to those found in the Radioactive Waste Management Complex, Pit 9. This test plan describes experimental procedures, sampling and analysis strategy, sampling procedures, sample control, and document management. It addresses safety issues in the experimental apparatus and procedures, personal training, and hazardous waste disposal. Finally, it describes the data quality objectives using the EPA tiered approach to treatability studies to define where research/scoping tests fit into these studies and the EPA analytical levels required for the tests.

CONTENTS

ABSTRACT	iii
ACRONYMS	vii
1. INTRODUCTION	1
2. PROJECT DESCRIPTION	2
2.1 Background Information	2
2.2 Objective	5
2.3 Laboratory-Pyrolysis Support Studies for ISV	6
2.3.1 Laboratory-Pyrolysis Tests	6
2.3.2 Pyrolysis Tube Preparation	7
2.3.3 Sampling Objectives	9
2.3.4 Data Quality Objectives (DQOs)	9
3. PROJECT ORGANIZATION AND RESPONSIBILITIES	17
4. SAMPLING AND ANALYSIS STRATEGY	21
4.1 Identify and Quantify Degradation Products	21
4.1.1 Scrub Solution Analysis	21
4.1.2 Optional Analysis	21
5. SAMPLING PROCEDURES	22
5.1 Sample Collection	22
5.2 Decontamination Procedures	23
6. LABORATORY ANALYSIS	24
7. SAMPLE CONTROL AND DOCUMENT MANAGEMENT	25
7.1 Documentation	25
7.1.1 Sample Labels	25
7.1.2 Custody Seals	25
7.1.3 Unique Identifiers	26
7.1.4 Laboratory Logbooks	26
7.1.5 Chain of Custody Record	28
7.1.6 Sample Analysis Request	28
7.1.7 Sample Tracking	29

7.2	Sample Handling	30
8.	DATA REPORTING, REDUCTION, AND VALIDATION	31
8.1	Data Reporting and Reduction	31
8.2	Data Validation	31
8.3	List of Required Data	31
8.4	Uncertainty Analysis	33
9.	QUALITY ASSURANCE (QA)	34
9.1	Test Laboratory QA and QC	34
9.2	Laboratory QA and QC	35
9.2.1	General Laboratory Controls	35
9.2.2	Commercial Laboratory QA and QC (Wet Chemistry)	35
9.3	Laboratory Management Review	36
9.4	Audits	37
9.5	Corrective Action	37
10.	LABORATORY DATA	38
10.1	Laboratory	38
10.2	Analytical Laboratory Tests	38
11.	SAFETY AND TRAINING PROGRAMS	39
11.1	ISV Laboratory-Pyrolysis Tests, Experimental Description	39
11.2	Safety Training	40
11.3	Experimental and Operating Procedures	40
11.4	Hazardous Waste Disposal	42
11.5	Training Requirements and Documentation	42
12.	DATA MANAGEMENT	43
13.	REFERENCES	44

APPENDIX A--Sample Forms	A-1
APPENDIX B--Material Safety Data Sheets	B-1
APPENDIX C--Science & Technology Department Chemical Hygiene Plan	C-1

FIGURES

1. Chemical pyrolysis experimental apparatus	3
2. Vitrified soil-lined combustion tube	4
3. The role of treatability studies in the RI/FS and RD/RA process	11
4. Flow diagram of the tiered approach	12
5. Test plan logic diagram	13
6. Organizational chart for ISV laboratory pyrolysis tests	18
7. Sample naming system	27
8. ISV laboratory-pyrolysis test apparatus	41

TABLES

1. Pyrolysis test matrix	8
2. Field logbook requirements	26

ACRONYMS

ARDC	Administrative Record and Document Control
CERCLA	Comprehensive Environmental Response Compensation, and Liability Act
COC	chain of custody
DMS	Data Management System
DOE	Department of Energy
DOE-ID	Department of Energy-Idaho Operations Office
DOP	detailed operating procedure
DQO	data quality objective
DRR	Document Revision Request
EIRC	ERP Independent Review Committee
EPA	Environmental Protection Agency
ERIS	Environmental Restoration Information System
ERP	Environmental Restoration Program
GC/MS	gas chromatography/mass spectrometry
IC	ion chromatography
ICP	inductively coupled plasma-atomic emission spectroscopy
INEL	Idaho National Engineering Laboratory
IRC	Idaho Research Center
ISV	in situ vitrification
LPTM	Laboratory-Pyrolysis Test Manager
MSDS	Material Safety Data Sheet
ORNL	Oak Ridge National Laboratory
PARCC	Precision, accuracy, representativeness, comparability, completeness
PD	Program Directive
PNL	Pacific Northwest Laboratory
PQL	practical quantitation limit
QA	quality assurance
QC	quality control
RI/FS	remedial investigation/feasibility study
RPD	relative percent difference
RWMC	Radioactive Waste Management Complex
S&T	Science & Technology Department
SARA	Superfund Amendments and Reauthorization Act of 1986
SDA	Subsurface Disposal Area
SOP	standard operating procedure
SOW	Statement of Work

TBA Task Base Agreement
TP test plan
WTDD Waste Technology Development Department

TEST PLAN FOR ISV LABORATORY-PYROLYSIS TESTING

1. INTRODUCTION

The purposes of the laboratory-pyrolysis studies are to obtain data specific to the requirements of the in situ vitrification (ISV) modeling efforts and to increase the understanding of the chemical mechanisms of the ISV process effects on the Radioactive Waste Management Complex (RWMC) of Pit 9 waste materials. The program will include the study of flammable and combustible chemicals and materials found in Pit 9. Also laboratory pyrolysis tests are being run to provide a more controllable testing environment, and there will be faster data retrieval and evaluation to furnish engineering data to the larger laboratory tests.

The test plan (TP) has been prepared in accordance with the Environmental Restoration Program (ERP), Program Directive (PD) 5.2, and Appendix C¹ to define specific laboratory and quality assurance activities. This is necessary to generate data required to assist in the evaluation of ISV as a viable remedial technology for the Subsurface Disposal Area (SDA). This TP will consider the data requirements of ISV modeling, engineering support, (specifically in ISV off-gas monitoring and treatment systems), regulatory, and safety activities for the laboratory pyrolysis tests at the Idaho Research Center (IRC).

2. PROJECT DESCRIPTION

The laboratory-pyrolysis testing program is designed to furnish the basic data required for the ISV modeling program and engineering data to support the Idaho National Engineering Laboratory's (INEL's) ISV testing program, specifically in ISV off-gas monitoring and treatment systems. The study includes the pyrolysis of organic materials identified in RWMC Pit 9. The pyrolysis products will be quantitatively and qualitatively analyzed to determine the amounts and types of chemical species resulting from alteration and degradation of the pyrolyzed organic waste. Variation of pyrolysis temperature and time will determine temperature effects on the alteration of the organic materials and the degree of degradation.

The study will be conducted using high temperature furnaces instead of electrodes. Experiments will be designed to simulate ISV conditions as close as possible.

Figure 1 is schematic of the experimental apparatus to be used in the testing program. Variation to this test apparatus will include placing a crucible directly in the furnace with the least volatile waste simulates such as wood, paper, oils, etc.

The pyrolysis tubes used in the laboratory pyrolysis tests will be constructed from high temperature ceramic and graphite materials. To be more representative of the ISV melt environment in the laboratory tests, these tubes will be coated on the interior with non-contaminated soils from the RWMC area (see Figure 2).

2.1 Background Information

ISV is the process of joule heating (resistance heating) of soils to form a chemically inert glass or crystalline material. The purpose of the ISV process is to entrap the soil contaminants in the glass melt to form a stable, leach-resistant waste form. The organic contaminants are destroyed by high temperatures ranging from 1200-2000°C of the molten soil.

Figure 1. Chemical pyrolysis experimental apparatus.

Figure 2. Vitrified soil-lined combustion tube.

The ISV technology has been developed over the past 10 years at the Pacific Northwest Laboratory (PNL) and is patented by Battelle Memorial Institute (U.S. Patent No. 4, 376, 598-Brouns, Buel, and Bonner, 1983) for all applications except the ISV of radioactive waste. The program was sponsored by the Department of Energy (DOE) for remediation of their radioactive wastes. The ISV process is currently being developed at the INEL to determine its feasibility as a remediation process for the SDA. To be a successful candidate for this application, it would have to meet the criteria described in the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) as amended by Superfund Amendments and Reauthorization Act of 1986 (SARA). This will require complete accountability of the hazardous and toxic chemical waste at SDA. To meet these criteria will require the knowledge of the chemical mechanisms taking place throughout the ISV process. This will entail a comprehensive study of the effects of the molten soil on the flammable, combustible and explosive materials, and their influence on the transuranic and toxic metal waste at the SDA.

The INEL ISV program, sponsored by DOE, is being conducted by EG&G Idaho, Inc. The program is directed toward the remediation of low-level radioactive waste in landfill storage at the RWMC. The current studies are directed toward remediation of the RWMC Pit 9. The area has been characterized by reviewing the shipping and storage records.² The emphasis of the INEL study is to develop the ISV process for application to box and drummed hazardous and toxic waste and meet all safety and environmental requirements.

2.2 Objective

The objective of the ISV Laboratory Pyrolysis Tests are to determine chemical degradation and alteration of the RWMC Pit 9 organic wastes in a high temperature (1000-1400°C) environment. The data will be used to support the ISV modeling program and the engineering laboratory tests. Currently, data used for the ISV chemical model are the best available data from literature sources. Data quality information was not available. The tests will be of the quality (EPA analytical levels) described in Sections 2.3.4 and 9.

2.3 Laboratory-Pyrolysis Support Studies for ISV

2.3.1 Laboratory-Pyrolysis Tests

The laboratory-pyrolysis tests will be conducted in a high temperature tube furnace (maximum temperature 1700°C) shown in Figure 1. The organic materials will be vaporized through a ceramic or graphite tube enclosed in the furnace. A carrier gas, such as air or helium, will be used to assist the transport of the organic vapor through the furnace. By controlling the carrier gas flow and the vapor pressure of the organic material, the concentration of the organic material in the carrier gas can be determined and controlled. Materials having very low vapor pressures, such as cellulose materials (paper, cloth, and wood), will be placed in a crucible in the furnace and heated to the desired temperature.

After the organic vapor has passed through the furnace, the off-gas products will pass through a scrubbing solution to remove potential gaseous acids and other inorganic components. The scrubbed gas stream will be collected in either a cold trap, solvent trap or a carbon filter to remove the volatile organics. The type of trap or filter will be determined in the initial test development.

The organic chemicals and materials selected for this study are shown as the major waste components in the RWMC Pit 9 waste survey. They are as follows:

- Trichloroethane
- Trichloroethylene
- Carbon tetrachloride
- Ethylenediamine tetraacetic acid (EDTA)
- Regal oil (cutting oil)

- Isopropyl alcohol
- Acetic acid
- Polyvinyl chloride (PVC)
- Polyethylene
- Polystyrene
- Cellulose (wood, paper, cloth)

The tests will be conducted on each chemical or material in an oxidizing environment (air) and an inert environment (nitrogen). The combustion tube temperatures will be maintained at 1000-1400°C. See Figure 1 for a sketch of the experimental apparatus. The off-gas effluent from the tests will be collected and analyzed. The analysis data will be used to determine chemical species resulting from heat alteration of the starting materials and the degree of degradation. Upon completion of these single chemical or material tests, multiple component tests will be designed and conducted to determine effects of other chemicals on the degradation alteration processes. Table 1 shows the test matrix of the laboratory pyrolysis tests.

2.3.2 Pyrolysis Tube Preparation

To simulate the ISV melt environment, the pyrolysis tubes will be lined on the interior with non-contaminated soil from the RWMC area. The soil will be placed in a hammer mill and pulverized to a flour-like material. This material will be placed in the pyrolysis tubes (graphite and ceramic).

The tube will be turned and agitated to coat the interior with the soil material. The pyrolysis tube will then be placed in the tube furnace and heated to 1200°C where the soil will melt and form a glass-like coating on the tubes's interior surface. Figure 2 is a schematic drawing showing the soil-lined tube.

Table 1. Pyrolysis test matrix^a

<u>Chemical Compound</u>	<u>Carrier Gas</u>		<u>Temperatures</u>		
	<u>Oxidizing</u>	<u>Inert</u>	<u>1000°C</u>	<u>1200°C</u>	<u>1400°C</u>
Trichloroethylene	x	x		x	
Trichloroethane	x	x		x	
Carbontetrachloride	x	x		x	
Ethylenediamine-tetraacetic acid (EDTA)	x	x		x	
Regal oil (cutting oil)	x	x		x	
Isopropyl alcohol	x	x		x	
Acetic acid	x	x		x	
Polyvinyl chloride (PVC)	x	x		x	
Polyethylene	x	x		x	
Polystyrene	x	x		x	
Cellulose (paper and wood)	x	x		x	
*Pit 9 Composite ^b	x	x	x	x	x

a. The multiple component test will be patterned after the engineer scale test.

b. The composite of the major chemicals and materials in the RWMC Pit 9 source term.

2.3.3 Sampling Objectives

The sampling and analysis objectives for evaluating the laboratory pyrolysis tests are designed to provide data for:

- The ISV modeling program
- Determining if the alteration products from pyrolysis of the chemicals and materials selected for the study are hazardous. If hazardous materials are generated, the information will be used to determine the analysis criteria for the off-gas system of the engineering laboratory tests.

Conclusions obtained from evaluation of the data address concerns about the incomplete combustion of the organic materials during the ISV process. The data will be analyzed to assist in the engineering laboratory off-gas characterization.

2.3.4 Data Quality Objectives (DQOs)

Data quality objectives (DQO) have been established to ensure that the data collected as described in this scoping study are of adequate quantity and quality.

Laboratory screening is performed to determine the potential applicability of emerging or innovative technologies. Laboratory screening is also applied when performance data for a well-developed technology are inconclusive or questionable with respect to specific waste characteristics. For example, whereas soil washing has been well demonstrated on sandy soils, performance data for loamy or silty soils may be inconclusive or nonexistent. Also, where solidification or stabilization are known to be effective for treating metal-containing wastes, its effectiveness with respect to organic contaminants is still questionable and should be verified through laboratory screening.

The DQO established for laboratory screening are usually stated in qualitative terms. Laboratory screening evaluates primary waste variables

such as percent solids, total organic carbon, or pH. Therefore, analytical Levels I and II usually provide sufficient information for laboratory screening. Because laboratory screening does not directly support the remedy selection, it does not require a significant amount of replication in the samples and the analytical tests performed.

Confidence limits established for data derived from laboratory screening are typically wide, in keeping with the characteristics of this level of study (i.e., low cost, quick turnaround, and limited quality assurance (QA) and quality control (QC) level.³

The role of laboratory screening is shown in Figure 3. This decision tree illustrates when treatability studies are needed to support the evaluation of a technology.

Laboratory screening is the first step in the tiered approach and is designed to establish the validity of a process quickly and inexpensively. The tier of treatability testing is required for risk-management decisions. Figure 4 shows how screening tests fit in the tiered approach.³

Figure 5 is the test plan logic diagram. This shows the screening test process and the decision points within the process. Laboratory pyrolysis tests (screening tests) will require EPA Analytical Levels I and II for sample analysis. However, if a higher analytical level is required by the data users, this option is identified in the logic diagram. The impact of this decision on program cost and schedule would determine the level of approval (Laboratory Pyrolysis Test Manager, (LPTM) Program Manager, etc.) as described in Section 7.1.4.

The following is a list of criteria required to meet the DQOs.

1. Data Users--Are primarily the Technology Demonstration Group responsible for test or design of the ISV Engineering Laboratory

Figure 3. The role of treatability studies in the RI/FS and RD/RA process (Ref. 3).

Figure 4. Flow diagram of the tiered approach (Ref. 3).

Figure 5. Test plan logic diagram.

studies and the ISV computer modelling group. Their location on the Logic diagram (see Figure 5) places them at a decision point, to determine data quality requirements.

2. Available Information--Data from previous ISV test performed at PNL, Oak Ridge National Laboratory (ORNL), Geosafe Corporation, and INEL have been reviewed in developing the laboratory-pyrolysis tests.
3. Sampling Objectives--Objectives were discussed in Section 2.3.3. The test data will be used in evaluating chemical alteration of organic waste. This information will assist in the design of the sampling and monitoring of the off-gas effluent system of engineer-scale tests and the ISV modeling program.
4. Data Uses-Laboratory-pyrolysis tests data uses fall under two categories:
 - a. Experimental Design--The data collected will be used in the test design of the engineering laboratory tests. Specifically in the off-gas monitoring system.
 - b. Model Development--The data will support process- and health-based risk assessment modeling for the ISV program.
5. Evaluation of Sampling and Analysis Options--The sampling strategies included in this test plan were derived from the treatability study objective to determine whether ISV is an applicable remedial technology for SDA waste. The stated sampling and analysis procedures were determined to best meet the project objectives.
6. Precision, accuracy, representativeness, comparability and completeness (PARCC)--PARCC parameters will be determined for characterization of ISV products to aid in establishing PARCC goals for future tests. Methods to determine PARCC parameters will be described in turn.⁴

- a. Precision refers to the reproductiveness or degree of agreement among replicate measurements of the same quantity. The precision of an analytical method is the standard error of the estimates for the least square regression line of "measured" versus "target" concentrations. The primary role of this application is to characterize the precision of any analysis method used under specified conditions. This allows comparison of precision of different results under the same technique. Analytical precision will be expressed as a percentage of the difference between results of duplicate samples for a given analyte. Relative percent difference (RPD) is expressed as follows:

$$RPD = \frac{(C_1 - C_2)}{\frac{(C_1 + C_2)}{2}} \times 100\% \quad (1)$$

where

$$C_1 = (\text{analyte})_{\text{sample}}$$

$$C_2 = (\text{analyte})_{\text{replicate.}}$$

Test data precision will be checked by comparison of replicate measurements. Laboratory precision will be measured by the analysis of duplicate samples or measurements and laboratory splits.

- b. Accuracy is the degree of agreement of a measurement with reference to a true value. Accuracy determinations will provide a measure of the bias in the system and shall be expressed as the percent recovery of the measurement of a sample with known concentration of the analyte of interest. It is denoted as follows:

$$\text{Recovery} = \frac{(A_s - A_u)}{A_u} \times 100$$

$$A_{sa}$$

where

$$A_s = [\text{analyte}]_{\text{spiked}}$$

$$A_u = [\text{analyte}]_{\text{unspiked}}$$

$$A_{sa} = [\text{analytes spike}]_{\text{added}}. \quad (2)$$

- c. Representativeness expresses the degree to which data accurately and precisely represents an actual condition or characteristic of a population. Laboratory test sample locations and collection protocols have been selected regarding accuracy and precision so that results are representative of the phases analyzed.
- d. Comparability is an expression of the confidence with which one data set is compared with another. Laboratory procedures greatly affect comparability. To minimize procedural effects, only the specific methods and protocols that have been selected or specified will be used to collect and analyze samples. Data collected per the sampling plan will be reported in similar units for convenient comparison to historical data.
- e. Completeness is a measurement of the proportion of data specified in the test plan which is determined valid. Validated data must meet all acceptance criteria including PARCC and any other criteria specified by the analytical method used. In the case of failure of PARCC criteria for critical samples, samples should be recollected and reanalyzed or the same sample reanalyzed when required to meet the 90% completeness goal.

3. PROJECT ORGANIZATION AND RESPONSIBILITIES

The organizational responsibilities for ISV Program personnel are described in ERP Program Management Plan, EGG-WM-8219, and the Quality Program Plan for the Environmental Restoration Program, QPP-149.⁵ The project-specific responsibilities are described below, with the organizational structure depicted in Figure 6.

The ISV Program Manager, S. K. Merrill, is responsible for the ISV project and other treatability studies. Responsibilities include ensuring all appropriate Environmental Protection Agency (EPA), state, and Company regulations and requirements are met during the ISV activities. Specifically, the ISV Program Manager will manage the budget, review, and approve project documents, including the test plan, detailed operating procedures (DOPs), laboratory Statements of Work (SOWs), and procedures used to perform the work. In addition, the ISV Program Manager is responsible for reporting project status to the Technology Demonstration Group management and for arranging the necessary personnel and subcontracts to meet schedules and ensure required data quality is obtained.

The ERP QA Officer is responsible for reviewing the SOW, auditing the laboratory activities and reporting the results of the audits to the ISV program management. The QA Officer has the independence to report directly to the ISV Program Manager.

The LPTM, R. E. McAtee, acts as the data collection supervisor for sample collection activities. The data collection supervisor is responsible for ensuring that laboratory personnel have been properly trained and qualified in accordance with this plan. In addition, the data collection supervisor is also accountable as the sample custodian. Sample custodian responsibilities include: ensuring that samples are collected following the sampling procedures, chain of custody (COC) forms are completed, custody seals are used, and field logbooks are properly filled out. In addition, the data

Figure 6. Organizational Chart for ISV laboratory-pyrolysis tests.

collection supervisor will coordinate with the Laboratory Manager to obtain the results and correct any discrepancies noted in the data obtained.

The LPTM is responsible for the safe and successful completion of tasks necessary to complete ISV laboratory-pyrolysis tests described in Table 1 in accordance with this test plan. The LPTM will ensure that the DQOs are met and that the quality of the data is verified. Additionally, the LPTM will ensure that sampling activities are reviewed and assessed in accordance with the test plan requirements.

The ERP Independent Review Committee (EIRC) is responsible for reviewing and approving the test plan prior to testing and sample collection activities.

The Administrative Record and Document Control (ARDC) Officer is responsible for the storage and retrieval of the ISV logbooks, data, and other pertinent information collected during laboratory-pyrolysis tests. In addition, the ARDC is responsible for issuing the logbooks, custody seals, COC forms, and other controlled documents for the project.

The Laboratory Manager is responsible for laboratory technical quality, cost, control, laboratory personnel management, and adherence to schedules. Responsibilities include: preparing analytical reports and ensuring that analytical procedures are performed properly, that COC records are complete, and that all specified QA/QC procedures are implemented and recorded.

The Laboratory QA Manager is responsible for the development, implementation and continued operation of procedures that ensure the acceptability of all generated and produced data. The Laboratory QA Manager will also act as, or designate, a laboratory custodian. The laboratory custodian will inspect the sample and the sample seal condition of delivered samples, reconcile the information of the sample seal and label against the COC record, assign a laboratory number, log in the sample in the laboratory notebook, and store the samples until they are ready for analysis.

Health and Safety--The IRC Safety Review Committee will review the test plan for the laboratory pyrolysis tests to determine if the plan addresses

the health and safety requirements for the IRC. The IRC safety and industrial hygiene personnel will inspect the area where the tests are conducted to determine if the health and safety requirements for the IRC are being observed, as described in the test plan.

Data Types--The types of data include:

- Chemical characteristics (i.e., identification of a pyrolytical altered species of organic molecules degree of degradation of the pyrolyzed organic materials through mass balance determinations).

Data Quality Needs--Laboratory pyrolysis test data quality needs and laboratory analysis of inorganic and organic products of the test are shown in Figures 4 and 5. Figure 5 is the decision chart. The laboratory pyrolysis tests are screening or scoping tests for the larger laboratory tests. Laboratory analysis will be conducted at EPA Levels I and II. However, the option for data users (ISV modeling and bench-scale testing) to request higher quality data (EPA Levels III and V) with multiple tests and increased quality level of the sample analysis is shown in the decision chart. Figure 4 shows how the screening tests fit into EPA's tiered approach to treatability studies.

Data Quantity Needs--Review of scoping data collected from past ISV studies has provided the basis for the need to identify and describe ISV pyrolyzed organic materials present in SDA waste. Data quantity is based on the number of tests and sampling points.

4. SAMPLING AND ANALYSIS STRATEGY

The sampling and analysis strategy emphasizes collecting sufficient, representative data to meet the test plan objectives. The sampling strategy will be discussed for each experimental phase necessary to meet the test plan objectives.

4.1 Identify and Quantify Degradation Products

The first analysis will be the gas chromatography-mass spectrometry (GC/MS) analysis of the organic degradation products collected in the traps or charcoal filter in the off-gas stream. The identification and quantitation of the altered organic materials will be a major step in meeting the test plan objectives. Evaluation of the GC/MS analysis data will determine the alteration pathways of the pyrolyzed organic materials and their extent of partial or complete degradation.

4.1.1 Scrub Solution Analysis

Analysis of the scrub solution requires the solvent extraction of a known volume of the solution to remove any organic materials having limited solubility in water for GC/MS analysis. The scrub solution will be analyzed for anions such as NO_x , SO_x and HCL by ion chromatography (IC).

4.1.2 Optional Analysis

Other analytical analysis methods may be used where needed. This could include total organic analysis, atomic absorption spectrophotometry, and inductively coupled plasma-atomic emission spectroscopy (ICP).

5. SAMPLING PROCEDURES

Sampling procedures are listed for collecting all samples for the previously stated analyses. Procedures include equipment to obtain samples, protective clothing, and the required sample storage containers.,

Sample containers and collection equipment cleaning procedures are also included in the sampling procedures.

5.1 Sample Collection

Equipment

- Ten and 40 cc glass bottles (Teflon cap liner)
- Five and 10 cc auto-pipet
- Kimwipes
- Polyethylene seal-lock bags
- Ceramic crucibles and tubes (high temperature).

Protective Clothing--EPA Level D protection was selected because personnel will not be exposed to airborne hazardous pollutants during sampling activities. Protective clothing will consist of laboratory coats, leather shoes, safety glasses, rubber or plastic gloves, and a face shield (when required by EG&G Idaho and Science and Technology Department safety standard practices). Special protective equipment, when required, will be described in the test procedures.

Sampling Procedures--(a) samples will be taken from the scrubbing flask using the 5 ml auto-pipet and placed in a clean 10 cc glass bottle,
(b) charcoal filters will be placed in a polyethylene seal lock bag and kept

in a refrigerator at 4°C until analyzed, (c) sample tags, sample labels, and COC forms will be filled out as described in Section 7 of this plan.

5.2 Decontamination Procedures

Sample collection equipment will be cleaned or decontaminated as follows:

- Glass bottles will be washed in a glassware detergent, rinsed thoroughly in distilled or purified water (DI water polished by passing through a water purification system), acid washed (10% nitric acid), rinsed in distilled water, and dried in a drying oven. The cleaned bottles will be stored in a desiccator.
- Auto-pipet tips will be rinsed three times (outside) with distilled water and dried with a kimwipe before using. The tips will be disposed of after use.
- Ceramic tubes will be heated to 800°C and purged with nitrogen for one hour before use.

6. LABORATORY ANALYSIS

A task base agreement (TBA) will be produced for laboratory analysis support for ISV laboratory-pyrolysis tests. A TBA will help ensure adequate data reporting results, detection limits, and QC deliverables. The contracted laboratory must be approved and audited before sample analysis by the ERP Quality and Compliance Unit and QAO can begin. The laboratory must develop standard operating procedures (SOPs) for the proposed methods and submit the SOPs to the ISV LPTM.

7. SAMPLE CONTROL AND DOCUMENT MANAGEMENT

The collection of data for ISV laboratory-pyrolysis test activities will be fully documented in the appropriate logbooks, as shown in Table 2. All samples shipped for laboratory analysis will be labeled, tagged, accompanied by an ERP COC form and a sample analysis form. Procedures for proper documentation of data and sample collection, for control and tracking of samples, and for ensuring the integrity of the samples, are described in the following sections.

7.1 Documentation

Documentation of laboratory measurement and sampling activities will include the use of sample labels, sample tags, custody seals, and unique sample identifiers as specified in the ERP QPP-149.⁵ Necessary laboratory documentation is detailed below. Finally, a sample analysis form must accompany the samples shipped to the analytical laboratory. Documentation examples are included in Appendix A.

7.1.1 Sample Labels

All samples collected for laboratory analysis will be labeled. Gummed or taped labels will be affixed to the sample container and to any outer wrapping of the sample. Sample labels will include unique identifier, date and time of sample collection, requested analysis, preservative, and the name of collector.

7.1.2 Custody Seals

All samples collected for laboratory analysis will require a custody seal attached to the sample shipping container. Custody seals are used to detect sample tampering between the time the sample is collected and opened at the laboratory. Custody seal information includes the dates of sample collection and the collector(s) name.

Table 2. Field logbook requirements

<u>Logbook</u>	<u>Responsible Person</u>	<u>Remarks/Included Data</u>
Laboratory instrument calibration	Laboratory Manager or designate	One logbook required for each instrument. User name, date, time of calibration and maintenance.
Sample	Laboratory Manager or designate	Sample identification, sample date, time, sample matrix, sample location, narrative, map.
Sample shipping	Laboratory Manager or designate	Sample identification, date, time collected, laboratory or storage area shipped to, date shipped, COC number, classification, shipper, QA checked by.

7.1.3 Unique Identifiers

See Figure 7 for the sample naming system to be used.

7.1.4 Laboratory Logbooks

Logbooks will be used to document all aspects of the ISV laboratory-pyrolysis effort. Logbooks are consecutively numbered and bound. All entries will be made in permanent black ink, dated, and signed by the person making the entry. Logbooks are distributed and controlled by the ARDC field data coordinator. Table 2 lists the logs that will be maintained for the ISV sampling effort, the individual responsible for log maintenance, and the data required in each log. An example of the log forms are contained in Appendix A.

If an error is made in a logbook entry, the correction shall be made by drawing a single line through the error and entering the correct information.

Figure 7. Sample naming system.

All corrections will be initialed and dated by the individual making the correction. Logbook entries should be made with a waterproof, non-smear black pen. If laboratory change is necessary, the LPTM's (or designate's) approval is required before proceeding with the activity, and a document revision request must be written to change the test plan at the end of the laboratory activity.

If the change impacts the test plan (schedule, budget, milestones) a Document Revision Request (DRR) must be prepared when the change is identified and received. The same reviews and signatures as the original test plan are required.

7.1.5 Chain of Custody Record

COC records establish the documentation necessary to trace the sample possession from collection to analysis. COC forms are initiated by the laboratory sample team and accompany the samples to the analytical laboratory. COC forms are signed by the Laboratory Manager or designate and are returned to the Test Manager with the data package. All COC records are sent to the ERP ARDC for custody tracking.

7.1.6 Sample Analysis Request

The request for analysis form will be completed by sample team personnel and signed by the LPTM. The information provided on the form must be consistent with information on the COC record to ensure complete sample tracking. The laboratory portion of the form will be completed by the appropriate analytical laboratory. The sample analysis request form will accompany the COC record and the sample shipment. A copy of the form will be retained in the laboratory record. The form will include the following information:

- COC control number
- Project name and sample team leader's name
- Laboratory destination and contact

- Data package due date and designated recipients
- Unique sample identification number
- Sample matrix (solid, liquid, etc.)
- Preservative
- Requested analysis and special instructions
- Identification of possible hazards
- Sample disposal instructions.

7.1.7 Sample Tracking

The laboratory will have a QA and QC Program that, as a minimum, will accomplish the following: Upon sample receipt by the laboratory, the Laboratory Manager or designate will inspect the sample and sample seal condition, reconcile the information on the sample label and seal against that of the COC record, assign a laboratory number, log in the sample in the laboratory logbook, and store the sample in a sample storage room or cabinet until assigned to an analyst.

The Laboratory Manager or designate will inspect the sample for damage. Any discrepancies between the information on the sample label, seal, COC record, and the sample analysis request sheet will be resolved before the sample is assigned for analysis. This effort may require communications with the sample collector. Results of the inspection will be noted on the sample analysis request sheet and on the laboratory sample logbook. Incoming samples will carry the ISV sampling unique identifier. To further identify samples, the laboratory should assign its own identification numbers; each sample should be marked with the assigned laboratory number. This number is recorded in the laboratory sample logbook, along with information describing the sample. The sample information is copied from the sample analysis request sheet and cross referenced against the information on the sample label. In most cases, the Laboratory Manager

assigns the sample to an analyst. The manager shall review the information on the sample analysis request sheet, which includes inspection notes recorded by the laboratory. The analyst assigned to analyze the sample shall record the identifying information about the sample, the receipt date, the analysis date, and other pertinent information in the laboratory notebook. This notebook shall also include the subsequent raw analysis data and calculations.

Once the laboratory receives the sample, the Laboratory Manager or assignee is responsible for the sample care and custody. The Laboratory Manager or assignee should be prepared to testify that the sample was in his or her possession or secured in the laboratory at all times from receipt until the analysis was completed.

7.2 Sample Handling

To prevent contamination and to ensure sample representativeness, proper sample handling is required. Sample collection is described in Section 5.1. Sample handling in the analytical laboratory is described in their procedures.

8. DATA REPORTING, REDUCTION, AND VALIDATION

Data management for this task includes data reporting, reduction, and validation.

8.1 Data Reporting and Reduction

A specified data reporting format will be detailed in the request for analysis for analytical services. Data reduction methods for the reported data will place the data in an ERP standardized format for incorporation into the Environmental Restoration Information System (ERIS) when this system becomes available. International System of Units (SI) will be used for measurements. All formulas used to correct or convert units will be included in the data package.

8.2 Data Validation

The ISV LPTM or designate has the responsibility for having the reported data validated and qualified. Data will not be made available for decisions until it is validated by personnel of the Site Characterization Unit. The EIRC has the responsibility to verify the reported data and may call upon technical experts to assist in verification. Data will be validated by examining the required documentation and QC sample data, including duplicates and blind laboratory blanks (when applicable). Data will be qualified as per the requirements outlined in the *Buried Waste Program Data Qualification Manual* (EGG-WM-8488).⁶ All aspects of the sampling program will be subject to audit.

8.3 List of Required Data

The data qualification package shall include:

- Data quality objectives
- Sampling data
- Test plan reference

- DOP or SOP reference
 - Logbook reference or copies of applicable pages
 - Copies of calibration logs
 - Sample numbers
 - Sample location
 - Sample date and time
 - Duplicates (when applicable)
 - Blanks (when applicable)
 - Copies of QC reports (Laboratory Validation Process)
 - COC records
 - Storage and shipping requirements (when applicable)
- Contract requirements or reference
- Analytical information
 - Laboratory name
 - Date and time samples were analyzed
 - Analytical method or procedure referenced
 - Type of instrumentation used
- Cover letter
 - Listing of samples
 - Comments describing problems encountered in analysis
- Tabulated results
- QC samples
 - Initial calibration verification
 - Continuing calibration verification
 - Interference check sample analysis for ICP, GC-MS, IC, and GC
 - Preparation blank analysis
 - Matrix spike analysis (when applicable)
 - Duplicate sample analysis (when applicable)
 - Laboratory control sample analysis (when applicable)

- Raw data system printouts
 - Calibration standards
 - Calibration blanks
 - Preparation blanks
 - Samples and any atypical dilutions
 - Duplicates
 - Interference checks
 - Instrument adjustments
- Any media used to store the data, i.e., disks

8.4 Uncertainty Analysis

Uncertainty measurements will be determined for all analytical concentration data. The uncertainty measure will be determined as U, where B is the percent Recovery of Element - 100, and Science is the relative percent difference (RPD):

$$U = (B^2 + 4S^2)^{1/2} \quad (5)$$

The equation for RPD is shown in Section 2.3.4 Part 6.a.

9. QUALITY ASSURANCE (QA)

All sampling and analysis activities described in this plan will be performed in accordance with the QA and QC practices described in the ERP quality assurance plan, QPP-149.⁵ QPP-149 contains guidance for:

- Sampling and decontamination
- Sample custody
- Calibration procedures and frequency
- Analytical procedures
- Data reduction, validation, and reporting
- Internal quality control checks and frequency
- Performance and system audits
- Preventive maintenance
- Specific routine procedures used to assess data precision, accuracy and completeness
- Corrective actions
- Quality assurance reports to management.

This section summarizes QA and QC practices that will be followed during the execution of this plan.

9.1 Test Laboratory QA and QC

During all sampling operations, the laboratory QA Officer shall conduct periodic inspections as specified in QPP-149. The inspections specified in QPP-149 are sufficient to assure the quality of the data.

9.2 Laboratory QA and QC

9.2.1 General Laboratory Controls

In addition to instrument calibration and analysis of QC samples, the following controls will be implemented:

- Reagents and solvents will have certified compositions
- Reagent storage environment and duration will meet the manufacturer's guidelines
- Laboratory equipment will be calibrated and standardized following referenced procedures for the methods used and they shall be documented
- Volumetric measurements will be made with certified glassware
- Data reduction computations will be independently checked and
- Qualified personnel will be used for laboratory analyses.

9.2.2 Commercial Laboratory QA and QC (Wet Chemistry)

EPA Analytical Levels I and II are projected in this test plan for FY-91. However, the option for EPA Levels III and IV are stated and could be requested for special data needs. This request would require the following laboratory QA and QC methods.

Contracted laboratories shall run one duplicate sample as described in the analytical laboratory procedures for the method and a relative percent deviation, which will be calculated and recorded on the laboratory QC forms. If the results for the percent RPD are greater than $\pm 20\%$, the samples will be reanalyzed in the duplicate sample group.

One sample out of 10 to be analyzed by a particular technique will be spiked with a known concentration of an element to determine the accuracy as

percent recovery. The concentration of the spike should be five times the practical quantitation limits (PQL) (a similar concentration for an analyte concentration greater than five times the PQL) to accurately evaluate percent recovery. The percent recovery will be recorded on the analytical quality control forms. If the results fail, a 75-125% recovery criteria, a post-preparation spike should be analyzed to evaluate whether it is the sample preparation or the instrumentation that is not performing.

One reagent blank shall be carried through each applicable analytical procedure.

One check sample per waste form shall be run. The check sample shall contain a subset of the test analytes. The concentration of these analytes shall approach the estimated quantitation limit.

9.3 Laboratory Management Review

The Laboratory Manager or designate will review testing and analytical results prior to external distribution. The reviewer will:

- Compare analyses performed to the request for analysis forms
- Review results for reasonableness
- Review QC data results
- Verify that required checking was properly conducted
- Ensure that data are legible, complete, and meet all conditions of the SOW.

If the Laboratory Manager finds that the review indicates the data meet the project quality requirements, the data will be released as final information.

9.4 Audits

A systems audit will be conducted by the ERP QA Officer before or at the start of sampling for laboratory-pyrolysis test determinations. The objectives of these audits are detailed in the QPP-149 for the ERP.⁵ The systems audit will evaluate the sampling procedures described in the test plan for adequacy to ensure that procedures are being used.

An audit of the analytical procedures is scheduled for the laboratories conducting the analyses before or during the start of any sample analysis. This audit will be scheduled by the QA Officer, as well as the Project and Laboratory Managers.

9.5 Corrective Action

Following completion of the audits, any deficiencies will be discussed with responsible project staff and the corrective actions will be identified. *Company Policy Manual*, Section 9.7 defines this as nonconformity and describes the corrective action and tracking system to ensure compliance. Samples must be recollected and reanalyzed or the same sample reanalyzed. Significant problems will result in ceasing of both test laboratory and laboratory activities. Such a decision will only be made after discussion with the QA Officer, the LPTM, and the Program Manager.

The QA Officer will review results of all corrective actions after implementation to determine the effectiveness of the actions and will provide a written report of this review to the Program Manager.

10. LABORATORY DATA

10.1 Laboratory

Laboratory data includes all data recorded in laboratory logbooks during the sampling activities, including sample description and narratives. Laboratory sampling precision will be assessed by audits conducted to ensure the use of uniform sampling and measurement techniques. Laboratory completeness will be assessed by calculating the ratio of measurements recorded to the total number of measurements planned. The completeness goal for laboratory data is 90%.

10.2 Analytical Laboratory Tests

The quality assurance plan and SOPs of the laboratory will describe procedures to evaluate precision, accuracy, and completeness. This includes the preparation of blanks, replicates, and spikes. The accuracy, precision, and completeness of the data will be assessed for each sample lot using evaluation of QC samples.

Precision of laboratory data will be measured by the analysis of splits. Laboratory reagent blanks will be analyzed to monitor the introduction of artifacts into the process. The data obtained will be within the prescribed control limits.

Completeness of the laboratory data will be measured by the ratio of samples with results of acceptable accuracy and precision to the total number of samples analyzed. The completeness goal for laboratory data is 90%.

11. SAFETY AND TRAINING PROGRAMS

Training laboratory personnel for the ISV laboratory-pyrolysis test will be in accordance with the Laboratory Training Program. All personnel will acknowledge their understanding of the test plan training program with their signature on a training roster form.

Copies of the certification forms will be kept in the laboratory files and stored with the ARDC Officer after the task is completed.

11.1 ISV Laboratory-Pyrolysis Tests, Experimental Description

The pyrolysis tests will be conducted on organic materials simulating waste at the RWMC Pit 9. The following chemicals and materials will be used and are representative of the major components in Pit 9:

- Trichloroethane
- Trichloroethylene
- Carbon tetrachloride
- Ethylenediamine tetraacetic acid (EDTA)
- Petroleum oil
- Isopropyl alcohol
- Acetic acid
- Polyvinyl (rubber gloves)
- Polyethylene
- Polystyrene
- Cellulose (cloth and paper).

The experimental apparatus is shown in Figure 8. It is a self-contained experiment, where all chemicals resulting from the pyrolysis test should be trapped in the scrubbing solution and the charcoal filter (this may be changed to an organic solvent scrubber) except the carrier gas. A large charcoal filter will be used as a backup to the system. The test apparatus will be operated in a charcoal recirculating fume hood for additional protection to laboratory personnel.

In the pyrolysis tests less than 1 g quantities of the test chemicals and materials will be used. This quantity of material will generate gas volumes of about 100 to 200 cc. Degradation products could generate gas volumes of as much as 600 cc. However, by controlling the carrier gas flow and the vapor pressure of the test chemical, the increased flow rate above that of the carrier gas would range between 1 to 60 cc/min. The carrier gas will be regulated between 10 cc to 1 L/min. The ceramic or graphite tube will be about 1 in. i.d. (when crucibles are used, the tube size will be about 2.5 in. i.d.). The gas generated by the pyrolysis should not create excessive pressure in the experimental apparatus. As the chemicals used in the testing will be handled in the fume hood, exposure to the chemicals by laboratory personnel will be minimized.

11.2 Safety Training

Laboratory technicians involved in the testing program will be trained in the use of the equipment. They also will have hazard communication training and will review the Material Data Safety Sheets (MSDSs) for the chemicals used in this program. All laboratory workers will have had training in the Science & Technology Department Chemical Hygiene Plan (Appendix C). A training file will be kept in a file in the laboratory where the tests are performed for all program participants.

11.3 Experimental and Operating Procedures

Experimental procedures will be written for the laboratory pyrolysis tests by the LPTM. If during the laboratory testing, modifications are required in the procedures, the LPTM should approve the changes and modify the written procedures to address the change. All personnel involved in the

NOTE. EXPERIMENTAL APPARATUS WILL BE SET UP IN IRC LAB A-7

Figure 8. ISV laboratory-pyrolysis test apparatus.

laboratory tests will be trained in these procedures, and this training will be entered into their training record.

11.4 Hazardous Waste Disposal

All personnel participating in the ISV laboratory-pyrolysis test program will be trained in the hazardous waste disposal procedures required by the Science and Technology Department for their laboratories at the IRC. This training will be recorded on their training file.

11.5 Training Requirements and Documentation

Personnel working on the ISV laboratory-pyrolysis tests will meet the minimum training requirement described in WTDD-PD3.2, Appendix A.¹ In addition to this training requirement, they will participate in all training programs required by Science and Technology Department at the IRC to work in their laboratories. Personnel training requirements will be listed in the employee training checklist. A copy of their checklist will be kept in the ISV laboratory-pyrolysis test program file in the laboratory where the tests were performed.

12: DATA MANAGEMENT

All information, logbooks, analytical packages, project files, and laboratory records will be submitted to ARDC upon completion of ISV sampling activities. These records will be maintained under lock and key and access provided to EG&G Idaho and DOE-ID personnel following data validation.

The document checkout entails filling out a form identifying the document removed, date removed, and the person receiving the document. Upon return of the document, it will be placed under lock and key and the checkout form removed.

All validated data generated by this study will be included in the ISV Data Management System (DMS). The ISV DMS is presently under development and will be included in the ERIS. The inclusion of all ISV data within the ERIS will provide a centralized data repository and ensure security and integrity of the data.

13. REFERENCES

1. Environmental Restoration Program, Program Directives ERP-PD 5.2, Appendix C, July 7, 1991.
2. T. E. Wierman, Engineering Design File, BWP-ISV-024, March 20, 1989.
3. J. G. Herrmann, *Guide for Conducting Treatability Studies Under CERCLA*, EPA/540/2-89/058, December 1989.
4. *Data Quality Objectives for Remedial Response Activities: Development Process*, EPA/540/G-87/003, March 1987.
5. Quality Program Plan for the Environmental Restoration Program, ERP-QPP-149 Revisions, October 1990.
6. C. Casey, *BWP Data Qualification Manual*, EGG-WM-8488.
7. Waste Technology Department Directives, WTDD-PD 3.2, Appendix A, April 29, 1991.

APPENDIX A
SAMPLE FORMS

SAMPLE LOGBOOK

DATE (DD/MMM/YY): _ _ / _ _ / _ _ TIME: _ _ _ _ AM PM

LABORATORY FIELD MEMBERS:

NARRATIVE (description of sampling activities, location, description of sampling point, and samples collected):

RECORDED BY:	QA CHECKED BY:

SAMPLE LOGBOOK

DATE (DD/MMM/YY): _ _ / _ _ / _ _ TIME: _ _ _ _ AM PM

MAP OF SAMPLING LOCATION:

(Include location of sampling points and reference points)

RECORDED BY:

QA CHECKED BY:

EXAMPLE OF SAMPLE LABEL

ISV LABORATORY TEST SAMPLING		
LOCATION		
ANALYSIS	DATE (ddmmyy)	TIME
SAMPLE ID NO.		

SAMPLE LOGBOOK

DATE (DD/MMM/YY): / / TIME: AM PM
 SAMPLE TYPE: (0) Normal (1) Equip. Blank (PRIOR) (2) Trip Blank
 (3) Replicate (4) Split (5) Equip. Blank (POST) (6) Spike (7) Other

ID NO.	CODE	ID NO.	CODE	ID NO.	CODE

SPECIFIC SAMPLING POINT(S)/LOCATIONS

POINT (LOCATION)

DEPTH (IN)

FROM

TO

SAMPLE METHOD CODE:

--

(0) Grab (1) Spatial Composite (2) Time Composite (3) Other

SAMPLE DESCRIPTION: CODE:

--

SOIL/ROCK

- (00) Surface Soil
- (01) Subsurface Soil
- (02) Basalt
- (03) Sediment Interbed
- (04) Other

SEDIMENT/SLUDGE

- (05) Pond/Impoundment
- (06) Drum/Tank
- (07) Other

AIR/GAS

- (15) Soil Gas
- (16) Other

LIQUIDS

- (08) Pond/Impoundment
- (09) Drum/Tank
- (10) Plant Discharge
- (11) Spring/Seep
- (12) Perched Aquifer
- (13) Regional Aquifer
- (14) Other

FIELD MEASUREMENTS

MEASUREMENT	READING	UNITS	INST. MAKE/MODEL	INSTR. NO.

SAMPLING AND ANALYSIS PLAN FOLLOWED:

 NO YES

Explain Deviations:

RECORDED BY:

QA CHECKED BY:

APPENDIX A

WTDD EMPLOYEE TRAINING CHECKLIST

This checklist is a satisfactory auditable record to be maintained by the department Training Coordinator or designated alternate. A copy may be provided to the employee on request.

EMPLOYEE NAME: _____ HIRE DATE: _____

<u>Required Training</u>	<u>Initial</u>	<u>Annual</u>
1. Health and Safety Orientation for New Employee (TS-400)*	_____	
2a. Initial Comprehensive Security Briefing (ICSB)*	_____	
2b. Annual Security Refresher Briefing (ASR)		_____
3a. General HAZCOM Program Training (TS-100)*	_____	
3b. HAZCOM Annual Refresher Program (TS-100R)		_____
4. Non-radiation Worker Review (Blue Card, TS-509)*	_____	_____
5. Facility/area security orientation	_____	
6. Fire Prevention		_____
7. Off-the-Job Safety		_____
8. Office Safety		_____
9. Lock-out Tag-out		_____
10. Emergency Action Training		_____
11. DOE Order 5000.3A - Occurrence Reporting (WTD Department Requirement)	_____	
* Denotes training available at New Employee Orientation.		
12. Identify additional training required (if any) for employee to accomplish assigned tasks: i.e., Radiation Worker, Hazardous Waste Worker, Respirator, Additional 5500.3A training for Emergency Response Organization Members, Classified Document Handling, etc.		
_____	_____	_____
_____	_____	_____
_____	_____	_____

APPENDIX B
MATERIAL SAFETY DATA SHEETS

OCCUPATIONAL HEALTH SERVICES, INC.

FOR EMERGENCY SOURCE INFORMATION

11 WEST 42ND STREET, 12TH FLOOR

CONTACT: 1-615-366-2000

NEW YORK, NEW YORK 10036

1-800-445-MSDS (1-800-445-6737) OR 1-212-789-3535

SUBSTANCE IDENTIFICATION

CAS-NUMBER 71-55-6

RTEC-NUMBER KJ2975000

SUBSTANCE: ~~1,1,1-TRICHLOROETHANE~~, STABILIZED

TRADE NAMES/SYNONYMS:

~~1,1,1-TRICHLOROETHANE~~ ALPHA-TRICHLOROETHANE: AEROTHENE TT:
METHYLTRICHLOROMETHANE: METHYL CHLOROFORM: TRICHLOROMETHYLMETHANE:
~~TRICHLOROETHANE~~ ETHANE, 1,1,1-TRICHLORO-: CHLORTEN:
~~1,1,1-TRICHLOROETHANE~~ TRICHLOROETHANE 111 DEGREASE COLD/VAPOR (ASHLAND):
ST-1000A CLEANER (STRESSCOAT): BLACO-THANE (BARON-BLAKESLEE): PERM
ETHANE DG (DETREX CHEMICALS): SAFETY SOLVENT (LOCTITE CORPORATION):
ACTIVATOR 711, 702, 703 (LOCTITE CORPORATION): STCC 4941176: RCRA U226:
UN 2831: C2H3CL3: OHS14371

CHEMICAL FAMILY:

HALOGEN COMPOUND, ALIPHATIC

MOLECULAR FORMULA: C-H3-C-CL3

MOLECULAR WEIGHT: 133.40

CERCLA RATINGS (SCALE 0-3): HEALTH=2 FIRE=0 REACTIVITY=0 PERSISTENCE=3

NFPA RATINGS (SCALE 0-4): HEALTH=2 FIRE=0 REACTIVITY=0

COMPONENTS AND CONTAMINANTS

COMPONENT: 1,1,1-TRICHLOROETHANE CAS# 71-55-6 PERCENT: 94.0-98.0

COMPONENT: 1,4-DIOXANE CAS# 123-91-1 PERCENT: 0.0-4.0

OTHER CONTAMINANTS: NONE

EXPOSURE LIMIT:

METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE):

350 PPM (1900 MG/M3) OSHA TWA; 450 PPM (2450 MG/M3) OSHA STEL

350 PPM (1900 MG/M3) ACGIH TWA; 450 PPM (2450 MG/M3) ACGIH STEL

350 PPM NIOSH RECOMMENDED 15 MINUTE CEILING

1000 POUNDS CERCLA SECTION 103 REPORTABLE QUANTITY

SUBJECT TO SARA SECTION 313 ANNUAL TOXIC CHEMICAL RELEASE REPORTING

1,4-DIOXANE:

25 PPM (90 MG/M3) OSHA TWA (SKIN)

25 PPM (90 MG/M3) ACGIH TWA (SKIN)

1 PPM NIOSH RECOMMENDED 30 MINUTE CEILING

100 POUND CERCLA SECTION 103 REPORTABLE QUANTITY

SUBJECT TO SARA SECTION 313 ANNUAL TOXIC CHEMICAL RELEASE REPORTING

SUBJECT TO CALIFORNIA PROPOSITION 65 CANCER AND/OR REPRODUCTIVE TOXICITY

WARNING AND RELEASE REQUIREMENTS- (JANUARY 1, 1988)

PHYSICAL DATA

DESCRIPTION: CLEAR, COLORLESS LIQUID WITH A MILD CHLOROFORM-LIKE ODOR.
BOILING POINT: 160-190 F (71-88 C) MELTING POINT: -58 F (-50 C)
SPECIFIC GRAVITY: 1.29-1.33 EVAPORATION RATE: (BUTYL ACETATE=1)
6.0
VOLATILITY: 100% SOLUBILITY IN WATER: <5%
VAPOR DENSITY: 4.6 VAPOR PRESSURE: 134 MMHG @ 20 C
OTHER SOLVENTS (SOLVENT - SOLUBILITY):
SOLUBLE IN ACETONE, BENZENE, CHLOROFORM, METHANOL,
ETHANOL, CARBON DISULFIDE, ETHER, CARBON TETRACHLORIDE, N-HEPTANE.

FIRE AND EXPLOSION DATA

FIRE AND EXPLOSION HAZARD
NEGLECTIBLE FIRE HAZARD WHEN EXPOSED TO HEAT OR FLAME.

FLASH POINT: NOT AVAILABLE

FIREFIGHTING MEDIA:
DRY CHEMICAL OR CARBON DIOXIDE
(1990 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5).

FOR LARGER FIRES, USE WATER SPRAY, FOG OR REGULAR FOAM
(1990 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5).

FIREFIGHTING:
APPLY COOLING WATER TO SIDES OF CONTAINERS THAT ARE EXPOSED TO FLAMES UNTIL
WELL AFTER FIRE IS OUT. STAY AWAY FROM ENDS OF TANKS. ISOLATE FOR 1/2 MILE IN
ALL DIRECTIONS IF TANK, RAIL CAR OR TANK TRUCK IS INVOLVED IN FIRE (1990
EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5, GUIDE PAGE 74).

EXTINGUISH USING AGENTS FOR SURROUNDING FIRE. COOL FIRE-EXPOSED CONTAINERS
WITH FLOODING AMOUNTS OF WATER APPLIED FROM AS FAR A DISTANCE AS POSSIBLE.
DO NOT ALLOW RUN-OFF WATER INTO SEWERS AND WATER SOURCES. AVOID BREATHING
VAPORS.

TRANSPORTATION

DEPARTMENT OF TRANSPORTATION HAZARD CLASSIFICATION 49 CFR 172.101:
ORM-A

DEPARTMENT OF TRANSPORTATION LABELING REQUIREMENTS 49 CFR 172.101 AND
SUBPART E:
NONE

TOXICITY

METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE):

IRRITATION DATA: 450 PPM/8 HOURS EYE-MAN; 5 GM/12 DAYS INTERMITTENT

SKIN-RABBIT MILD; 20 MG/24 HOURS SKIN-RABBIT MODERATE;

100 MG EYE-RABBIT MILD; 2 MG/24 HOURS EYE-RABBIT SEVERE.

TOXICITY DATA: 27 GM/M3/10 MINUTES INHALATION-MAN LCLO;

350 PPM INHALATION-MAN TCLO; 200 PPM/4 HOURS INHALATION-MAN TCLO;

920 PPM/70 MINUTES INHALATION-HUMAN TCLO; 18000 PPM/4 HOURS INHALATION-RAT

LC50; 3911 PPM/2 HOURS INHALATION-MOUSE LC50; 24400 MG/M3 INHALATION-CAT

LC50; 15800 MG/KG SKIN-RABBIT LD50 (EPA-600/8-82-003F, 1984); 1 GM/KG

SKIN-RABBIT LDLO; 670 MG/KG ORAL-HUMAN TDLO; 10300 MG/KG ORAL-RAT LD50;

11240 MG/KG ORAL-MOUSE LD50; 5660 MG/KG ORAL-RABBIT LD50;

9470 MG/KG ORAL-GUINEA PIG LD50; 750 MG/KG ORAL-DOG LD50;

16 GM/KG SUBCUTANEOUS-MOUSE LD50; 500 MG/KG SUBCUTANEOUS-RABBIT LDLO;

95 MG/KG INTRAVENOUS-DOG LDLO; 3593 MG/KG INTRAPERITONEAL-RAT LD50;

3636 MG/KG INTRAPERITONEAL-MOUSE LD50; 3100 MG/KG INTRAPERITONEAL-DOG LD50;

MUTAGENIC DATA (RTECS); REPRODUCTIVE EFFECTS DATA (RTECS).

CARCINOGEN STATUS: ANIMAL INADEQUATE EVIDENCE (IARC GROUP-3).

LOCAL EFFECTS: IRRITANT- INHALATION, SKIN, EYE.

ACUTE TOXICITY LEVEL: SLIGHTLY TOXIC BY INHALATION, DERMAL ABSORPTION AND
INGESTION.

TARGET EFFECTS: CENTRAL NERVOUS SYSTEM DEPRESSANT. POISONING MAY ALSO AFFECT
THE HEART AND POSSIBLY LIVER AND KIDNEYS.

AT INCREASED RISK FROM EXPOSURE: PERSONS WITH PRE-EXISTING SKIN DISORDERS,
LIVER DISEASE OR CARDIOVASCULAR DISEASE.

ADDITIONAL DATA: ALCOHOL MAY POTENTIATE BOTH CARDIAC AND HEPATIC TOXICITY.

EPINEPHRINE OR OTHER STIMULANTS MAY INDUCE VENTRICULAR ARRHYTHMIAS.

1,4-DIOXANE:

IRRITATION DATA: 515 MG OPEN SKIN-RABBIT MILD; 300 PPM/15 MINUTES EYE-HUMAN;

21 MG EYE-RABBIT; 100 MG/24 HOURS EYE-RABBIT MODERATE; 10 UG EYE-GUINEA PIG
MODERATE.

TOXICITY DATA: 470 PPM INHALATION-HUMAN TCLO; 5500 PPM/1 MINUTE

INHALATION-HUMAN TCLO; 470 PPM/3 DAYS INHALATION-HUMAN LCLO; 46 GM/M3/2

HOURS INHALATION-RAT LC50; 37 GM/M3/2 HOURS INHALATION-MOUSE LC50; 44

GM/M3/7 HOURS INHALATION-CAT LCLO; 20500 MG/M3 INHALATION-MAMMAL LC50;

7600 MG/KG SKIN-RABBIT LD50; 2000 MG/KG ORAL-RABBIT LD50; 5700 MG/KG

ORAL-MOUSE LD50; 2000 MG/KG ORAL-CAT LD50; 3150 MG/KG ORAL-GUINEA PIG LD50;

1500 MG/KG INTRAVENOUS-RABBIT LDLO; 799 INTRAPERITONEAL-RAT LD50; MUTAGENIC

DATA (RTECS); REPRODUCTIVE EFFECTS DATA (RTECS); TUMORIGENIC DATA (RTECS).

CARCINOGEN STATUS: ANTICIPATED HUMAN CARCINOGEN (NTP); HUMAN INADEQUATE
EVIDENCE, ANIMAL SUFFICIENT EVIDENCE (IARC GROUP-2B). ORAL ADMINISTRATION
PRODUCED ADENOMAS AND CARCINOMAS IN THE LIVER AND CARCINOMAS OF THE NASAL
CAVITY IN RATS AND HEPATOMAS AND CARCINOMAS OF THE GALL BLADDER IN GUINEA
PIGS.

LOCAL EFFECTS: IRRITATION- INHALATION, SKIN, EYES.

ACUTE TOXICITY LEVEL: MODERATELY TOXIC BY INHALATION; SLIGHTLY TOXIC BY SKIN
CONTACT AND INGESTION.

TARGET EFFECTS: HEPATOTOXIN; CENTRAL NERVOUS SYSTEM DEPRESSANT; NEPHROTOXIN.
POISONING MAY AFFECT THE BRAIN.

AT INCREASED RISK FROM EXPOSURE: PERSONS WITH PRE-EXISTING LIVER, KIDNEY,
PULMONARY OR SKIN DISORDERS.

ADDITIONAL DATA: ALCOHOL MAY ENHANCE THE TOXIC EFFECTS.

HEALTH EFFECTS AND FIRST AID

INHALATION:

METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE):

IRRITANT/NARCOTIC. 1000 PPM IMMEDIATELY DANGEROUS TO LIFE OR HEALTH.

ACUTE EXPOSURE- EXPOSURE TO 500 PPM FOR 60 MINUTES SHOULD CAUSE NO EFFECT EXCEPT FOR A DISTINCTIVE ODOR WHILE 900-1000 PPM FOR 20 MINUTES MAY CAUSE MILD RESPIRATORY TRACT IRRITATION AND PROMPT BUT MINIMAL IMPAIRMENT OF EQUILIBRIUM WHICH MAY BE ACCOMPANIED BY HEADACHE, LASSITUDE AND ATAXIA. IMPAIRED PERFORMANCE OF BEHAVIORAL TESTS WAS ALSO REPORTED AT 1000 PPM. HIGHER LEVELS OF 2000-5000 PPM MAY CAUSE INCOORDINATION, ANESTHESIA, LOSS OF CONSCIOUSNESS, COMA AND DEATH. EXCESSIVE CONCENTRATIONS OF 10,000 PPM MAY CAUSE DEATH DUE TO RESPIRATORY OR CARDIAC FAILURE. CARDIAC SENSITIZATION MAY BE A CONTRIBUTING FACTOR. OTHER EFFECTS MAY INCLUDE NAUSEA, VOMITING, DROWSINESS, CONVULSIONS, FALL OF BLOOD PRESSURE LIVER AND KIDNEY DAMAGE, BRADYCARDIA AND BLOOD CLOTTING CHANGES.

CHRONIC EXPOSURE- NO ADVERSE EFFECTS RELATED TO EXPOSURE WERE REPORTED IN VOLUNTEERS EXPOSED TO 500 PPM FOR 7 HOURS A DAY FOR 5 DAYS, OR IN WORKERS EXPOSED TO 200 PPM FOR SEVERAL MONTHS TO 6 YEARS. EXPOSURE OF ANIMALS FOR 3 MONTHS AT CONCENTRATIONS FROM 1000 TO 10,000 PPM CAUSED SYMPTOMS OF CENTRAL NERVOUS SYSTEM DEPRESSION AND SOME PATHOLOGICAL CHANGES IN THE LIVERS AND LUNGS OF SOME SPECIES. REPRODUCTIVE EFFECTS HAVE BEEN REPORTED IN ANIMALS.

1,4-DIOXANE:

IRRITANT/NARCOTIC/HEPATOTOXIN/NEPHROTOXIN.

ACUTE EXPOSURE- MAY BE IRRITATING TO THE NOSE, THROAT AND RESPIRATORY TRACT AT 220 PPM. THIS COMPOUND HAS POOR WARNING PROPERTIES AND CAN BE INHALED IN AMOUNTS THAT MAY CAUSE SERIOUS SYSTEMIC INJURY. SYMPTOMS OF SYSTEMIC TOXICITY MAY INCLUDE HEADACHE, VERTIGO, DROWSINESS, DYSPNEA, NAUSEA, AND VOMITING. INHALATION CAUSED INCREASED SALIVATION, LACRIMATION, NARCOSIS, BEHAVIORAL CHANGES, AND DEATH IN ANIMALS. AUTOPSY REVEALED LUNG, LIVER AND KIDNEY DAMAGE, CONGESTION AND EDEMA OF THE LUNGS, AND INCREASED BLOOD COUNTS.

CHRONIC EXPOSURE- REPEATED EXPOSURE CAUSED MUCOUS MEMBRANE IRRITATION, DYSPNEA, HEADACHE, VERTIGO, LOSS OF APPETITE, NAUSEA AND VOMITING, PAIN AND TENDERNESS IN THE ABDOMEN AND LUMBAR REGION, DROWSINESS, MALAISE, LIVER ENLARGEMENT AND DAMAGE, OLIGURIA, ANURIA, UREMIA, COMA, AND DEATH FROM ACUTE RENAL FAILURE. AUTOPSIES REVEALED LUNG AND BRAIN CONGESTION, CENTRAL NERVOUS SYSTEM DAMAGE, LIVER NECROSIS, HEMORRHAGIC NEPHRITIS AND NECROSIS, LEUKOCYTOSIS, AND BRONCHOPNEUMONIA.

FIRST AID- REMOVE FROM EXPOSURE AREA TO FRESH AIR IMMEDIATELY. IF BREATHING HAS STOPPED, GIVE ARTIFICIAL RESPIRATION. MAINTAIN AIRWAY AND BLOOD PRESSURE AND ADMINISTER OXYGEN IF AVAILABLE. KEEP AFFECTED PERSON WARM AND AT REST. TREAT SYMPTOMATICALLY AND SUPPORTIVELY. ADMINISTRATION OF OXYGEN SHOULD BE PERFORMED BY QUALIFIED PERSONNEL. GET MEDICAL ATTENTION IMMEDIATELY.

SKIN CONTACT:

METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE):

IRRITANT.

ACUTE EXPOSURE- DIRECT CONTACT MAY CAUSE IRRITATION AND REDNESS. VAPORS ARE POORLY ABSORBED, BUT THE LIQUID, ESPECIALLY IF CONFINED UNDER AN IMPERMEABLE BARRIER MAY BE ABSORBED TO SOME EXTENT. THIS ALONE IS UNLIKELY

TO RESULT IN TOXIC EFFECTS, BUT MAY ADD TO THE EFFECTS OF INHALATION EXPOSURE.
CHRONIC EXPOSURE- REPEATED SKIN CONTACT MAY PRODUCE A DRY, SCALY, FISSURED DERMATITIS DUE TO THE DEFATTING PROPERTIES OF THE LIQUID, AND POSSIBLY BURNS.

1,4-DIOXANE:

IRRITANT/NARCOTIC/HEPATO TOXIN/NEPHROTOXIN.

ACUTE EXPOSURE- MAY CAUSE IRRITATION WITH REDNESS AND PAIN. ALLERGIC CONTACT DERMATITIS HAS BEEN REPORTED. SKIN ABSORPTION MAY OCCUR AND CAUSE HEADACHE, NAUSEA AND VOMITING. SKIN ABSORPTION PRODUCED SIGNS OF UNSTEADINESS, INCOORDINATION, NARCOSIS, ERYTHEMA, AND LIVER AND KIDNEY DAMAGE IN ANIMALS.

CHRONIC EXPOSURE- PROLONGED OR REPEATED CONTACT MAY CAUSE DRYING AND CRACKING OF THE SKIN, DERMATITIS, AND ECZEMA. SKIN ABSORPTION MAY HAVE CONTRIBUTED TO THE DEATH OF A WORKER FOLLOWING SKIN AND INHALATION EXPOSURE FOR ONE WEEK. ANIMAL STUDIES INDICATE REPEATED SKIN APPLICATION MAY RESULT IN LIVER AND KIDNEY DAMAGE. TUMOR PROMOTER ACTIVITY HAS BEEN REPORTED IN MICE.

FIRST AID- REMOVE CONTAMINATED CLOTHING AND SHOES IMMEDIATELY. WASH AFFECTED AREA WITH SOAP OR MILD DETERGENT AND LARGE AMOUNTS OF WATER UNTIL NO EVIDENCE OF CHEMICAL REMAINS (APPROXIMATELY 15-20 MINUTES). GET MEDICAL ATTENTION IMMEDIATELY.

EYE CONTACT:

METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE):

IRRITANT.

ACUTE EXPOSURE- EXPOSURE TO 500 PPM MAY CAUSE IRRITATION AND REDNESS.

DIRECT CONTACT WITH THE LIQUID MAY CAUSE TEMPORARY INJURY WITH COMPLETE RECOVERY EXPECTED IN 48 HOURS. DIRECT APPLICATION TO THE EYES OF RABBITS HAS CAUSED CONJUNCTIVAL IRRITATION, BUT NO CORNEAL DAMAGE.

CHRONIC EXPOSURE- REPEATED OR PROLONGED CONTACT MAY CAUSE CONJUNCTIVITIS.

1,4-DIOXANE:

IRRITANT.

ACUTE EXPOSURE- VAPORS MAY CAUSE IRRITATION AT CONCENTRATIONS ABOVE 220 PPM.

NO SERIOUS DISTURBANCES HAVE BEEN REPORTED BY EXTERNAL CONTACT. DIRECT APPLICATION TO RABBIT EYES CAUSED TRANSIENT CORNEAL INJURY.

CHRONIC EXPOSURE- REPEATED OR PROLONGED EXPOSURE MAY RESULT IN CONJUNCTIVITIS.

FIRST AID- WASH EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER OR NORMAL SALINE, OCCASIONALLY LIFTING UPPER AND LOWER LIDS, UNTIL NO EVIDENCE OF CHEMICAL REMAINS (APPROXIMATELY 15-20 MINUTES). GET MEDICAL ATTENTION IMMEDIATELY.

INGESTION:

METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE):

NARCOTIC.

ACUTE EXPOSURE- MAY CAUSE NAUSEA, VOMITING, DIARRHEA, GASTROINTESTINAL DISTURBANCES AND ABDOMINAL PAIN FOLLOWED BY CENTRAL NERVOUS SYSTEM DEPRESSION WITH HEADACHE, DIZZINESS, WEAKNESS, INCOORDINATION, MENTAL CONFUSION AND UNCONSCIOUSNESS. DEATH MAY OCCUR FROM CHRONIC RESPIRATORY FAILURE. OTHER SYMPTOMS AS DESCRIBED IN ACUTE INHALATION MAY ALSO OCCUR. MYOCARDIAL SENSITIZATION TO EPINEPHRINE AND SUBSEQUENT DEATH DUE TO CARDIAC ARREST MAY OCCUR. ASPIRATION MAY RESULT IN PULMONARY EDEMA OR CHEMICAL PNEUMONITIS.

CHRONIC EXPOSURE- REPRODUCTIVE EFFECTS HAVE BEEN REPORTED IN ANIMALS.

1,4-DIOXANE:

NARCOTIC/HEPATOTOXIN/NEPHROTOXIN/CARCINOGEN.

ACUTE EXPOSURE- MAY CAUSE LIGHT BURNING SENSATION ON CONTACT WITH ORAL MUCOUS MEMBRANES. LARGE DOSES RESULTED IN WEAKNESS, INCOORDINATION, DEPRESSION, COMA AND DEATH IN ANIMALS. AUTOPSY REVEALED HEMORRHAGIC AREAS IN THE PYLORIC REGION OF THE STOMACH, BLADDERS DISTENDED WITH URINE, SLIGHT PROTEINURIA AND ENLARGED KIDNEYS. ASPIRATION MAY RESULT IN PNEUMONIA.

CHRONIC EXPOSURE- IN ANIMAL FEEDING STUDIES, THIS COMPOUND PRODUCED LIVER AND KIDNEY DEGENERATION AND NECROSIS, ULCERATION OF THE STOMACH, HEPATOMAS, CARCINOMA OF THE NASAL CAVITY, CARCINOMA OF THE KIDNEY PELVIS, LEUKEMIA, LYMPHOSARCOMA, CHOLANGIOMAS, GALL BLADDER CARCINOMAS, AND TUMORS OF THE LUNG. REPRODUCTIVE EFFECTS HAVE BEEN REPORTED IN ANIMALS.

FIRST AID- TREAT SYMPTOMATICALLY AND SUPPORTIVELY. GET MEDICAL ATTENTION AND ADVICE ON WHETHER TO USE GASTRIC LAVAGE. EXTREME CARE MUST BE TAKEN TO PREVENT ASPIRATION. A CUFFED ENDOTRACHEAL TUBE USED BY QUALIFIED MEDICAL PERSONNEL MIGHT BE ADVISABLE. KEEP HEAD LOWER THAN HIPS TO PREVENT ASPIRATION SHOULD VOMITING OCCUR.

ANTIDOTE:

NO SPECIFIC ANTIDOTE. TREAT SYMPTOMATICALLY AND SUPPORTIVELY.

REACTIVITY SECTION

REACTIVITY:

SLOWLY DECOMPOSES OVER TIME YIELDING HYDROGEN CHLORIDE. AN INHIBITOR MAY BE ADDED TO SCAVENGE THE ACID THAT IS FORMED AND PREVENT CORROSION TO METALS. WATER MAY REACT WITH THE INHIBITOR AND ALLOW THE NATURAL DECOMPOSITION TO OCCUR.

INCOMPATIBILITIES:

METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE):

ACETONE: EXOTHERMIC REACTION.

ALKALI (STRONG): POSSIBLE VIOLENT REACTION.

ALUMINUM AND ALLOYS: MAY DECOMPOSE VIOLENTLY.

BARIUM: FIRE AND EXPLOSION HAZARD.

MAGNESIUM: VIOLENT DECOMPOSITION WITH EVOLUTION OF HYDROGEN CHLORIDE.

METALS (POWDERED): FIRE AND EXPLOSION HAZARD.

NITROGEN TETROXIDE: FORMS EXPLOSIVE MIXTURE.

OXIDIZERS (STRONG): POSSIBLE VIOLENT REACTION.

OXYGEN (GAS): POSSIBLE EXPLOSION WHEN HEATED @ 100 C.

OXYGEN (LIQUID): POSSIBLE VIOLENT EXPLOSION.

POTASH: FORMS FLAMMABLE OR EXPLOSIVE PRODUCT.

POTASSIUM AND ALLOYS: FORMS SHOCK-SENSITIVE MIXTURE.

POTASSIUM HYDROXIDE: FORMATION OF SPONTANEOUSLY FLAMMABLE PRODUCT.

RUBBER, PLASTICS, COATINGS: MAY BE ATTACKED.

SODIUM AND ALLOYS: FIRE AND EXPLOSION HAZARD.

SODIUM HYDROXIDE: FORMS SPONTANEOUSLY FLAMMABLE PRODUCT.

SODIUM-POTASSIUM ALLOY: POSSIBLE EXPLOSION.

TIN AND ALLOYS: INCOMPATIBLE.

ZINC AND ALLOYS: INCOMPATIBLE.

1,4-DIOXANE:

DECABORANE: FORMS SHOCK-SENSITIVE MIXTURE.

NICKEL (RANEY CATALYST): POSSIBLE EXPLOSIVE REACTION ABOVE 210 C.

NITRIC ACID + PERCHLORIC ACID: POSSIBLE EXPLOSIVE REACTION.
OXIDIZERS (STRONG): FIRE AND EXPLOSION HAZARD.
SILVER PERCHLORATE: MAY FORM EXPLOSIVE COMPOUND.
SULFUR TRIOXIDE: VIOLENT DECOMPOSITION ON STORAGE.
TRIETHYNYLALUMINUM: MAY EXPLODE WHEN HEATED.
SEE ALSO ETHERS.

DECOMPOSITION:

THERMAL DECOMPOSITION PRODUCTS MAY INCLUDE TOXIC AND CORROSIVE FUMES OF CHLORIDES, TOXIC FUMES OF PHOSGENE AND CHLOROACETYLENES, AND OXIDES OF CARBON.

POLYMERIZATION:

HAZARDOUS POLYMERIZATION HAS NOT BEEN REPORTED TO OCCUR UNDER NORMAL TEMPERATURES AND PRESSURES.

STORAGE-DISPOSAL

OBSERVE ALL FEDERAL, STATE AND LOCAL REGULATIONS WHEN STORING OR DISPOSING OF THIS SUBSTANCE. FOR ASSISTANCE, CONTACT THE DISTRICT DIRECTOR OF THE ENVIRONMENTAL PROTECTION AGENCY.

****STORAGE****

STORE IN A COOL, DRY, WELL-VENTILATED LOCATION, AWAY FROM ANY AREA WHERE THE FIRE HAZARD MAY BE ACUTE (NFPA 49, HAZARDOUS CHEMICALS DATA, 1975).

STORE AWAY FROM INCOMPATIBLE SUBSTANCES.

****DISPOSAL****

DISPOSAL MUST BE IN ACCORDANCE WITH STANDARDS APPLICABLE TO GENERATORS OF HAZARDOUS WASTE, 40CFR 262. EPA HAZARDOUS WASTE NUMBER U226.

CONDITIONS TO AVOID

MAY BURN BUT DOES NOT IGNITE READILY. CONTAINER MAY EXPLODE IN HEAT OF FIRE.

SPIILLS AND LEAKS

SOIL-RELEASE:

DIG A HOLDING AREA SUCH AS A PIT, POND OR LAGOON TO CONTAIN SPILL AND DIKE SURFACE FLOW USING BARRIER OF SOIL, SANDBAGS, FOAMED POLYURETHANE OR FOAMED CONCRETE. ABSORB LIQUID MASS WITH FLY ASH OR CEMENT POWDER.

WATER-SPILL:

LIMIT SPILL MOTION AND DISPERSION WITH NATURAL BARRIERS OR OIL SPILL CONTROL BOOMS.

TRAP SPILLED MATERIAL AT BOTTOM IN DEEP WATER POCKETS, EXCAVATED HOLDING AREAS

OR WITHIN SAND BAG BARRIERS.

USE SUCTION HOSES TO REMOVE TRAPPED SPILL MATERIAL.

THE CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986 (PROPOSITION 65) PROHIBITS CONTAMINATING ANY KNOWN SOURCE OF DRINKING WATER WITH SUBSTANCES KNOWN TO CAUSE CANCER AND/OR REPRODUCTIVE TOXICITY.

OCCUPATIONAL-SPILL:

SHUT OFF IGNITION SOURCES. STOP LEAK IF YOU CAN DO IT WITHOUT RISK. FOR SMALL LIQUID SPILLS, TAKE UP WITH SAND, EARTH OR OTHER ABSORBENT MATERIAL. FOR LARGER SPILLS, DIKE FAR AHEAD OF SPILL FOR LATER DISPOSAL. NO SMOKING, FLAMES OR FLARES IN HAZARD AREA! KEEP UNNECESSARY PEOPLE AWAY.

REPORTABLE QUANTITY (RQ): 1000 POUNDS

THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT (SARA) SECTION 304 REQUIRES THAT A RELEASE EQUAL TO OR GREATER THAN THE REPORTABLE QUANTITY FOR THIS SUBSTANCE BE IMMEDIATELY REPORTED TO THE LOCAL EMERGENCY PLANNING COMMITTEE AND THE STATE EMERGENCY RESPONSE COMMISSION (40 CFR 355.40). IF THE RELEASE OF THIS SUBSTANCE IS REPORTABLE UNDER CERCLA SECTION 103, THE NATIONAL RESPONSE CENTER MUST BE NOTIFIED IMMEDIATELY AT (800) 424-8802 OR (202) 426-2675 IN THE METROPOLITAN WASHINGTON, D.C. AREA (40 CFR 302.6).

PROTECTIVE EQUIPMENT SECTION

VENTILATION:

PROVIDE LOCAL EXHAUST OR PROCESS ENCLOSURE VENTILATION TO MEET PUBLISHED EXPOSURE LIMITS.

RESPIRATOR:

THE FOLLOWING RESPIRATORS AND MAXIMUM USE CONCENTRATIONS ARE RECOMMENDATIONS BY THE U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES, NIOSH POCKET GUIDE TO CHEMICAL HAZARDS; NIOSH CRITERIA DOCUMENTS OR BY THE U.S. DEPARTMENT OF LABOR, 29 CFR 1910 SUBPART Z.

THE SPECIFIC RESPIRATOR SELECTED MUST BE BASED ON CONTAMINATION LEVELS FOUND IN THE WORK PLACE, MUST NOT EXCEED THE WORKING LIMITS OF THE RESPIRATOR AND BE JOINTLY APPROVED BY THE NATIONAL INSTITUTE FOR OCCUPATIONAL SAFETY AND HEALTH AND THE MINE SAFETY AND HEALTH ADMINISTRATION (NIOSH-MSHA).

METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE):

1000 PPM- ANY SUPPLIED-AIR RESPIRATOR WITH FULL FACEPIECE.
ANY SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE.

ESCAPE- ANY AIR-PURIFYING FULL FACEPIECE RESPIRATOR (GAS MASK) WITH A CHIN-STYLE OR FRONT OR BACK-MOUNTED ORGANIC VAPOR CANISTER.
ANY APPROPRIATE ESCAPE-TYPE SELF-CONTAINED BREATHING APPARATUS.

FOR FIREFIGHTING AND OTHER IMMEDIATELY DANGEROUS TO LIFE OR HEALTH CONDITIONS:

SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.

SUPPLIED-AIR RESPIRATOR WITH FULL FACEPIECE AND OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE IN COMBINATION WITH AN AUXILIARY SELF-CONTAINED BREATHING APPARATUS OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.

CLOTHING:

EMPLOYEE MUST WEAR APPROPRIATE PROTECTIVE (IMPERVIOUS) CLOTHING AND EQUIPMENT TO PREVENT ANY POSSIBILITY OF SKIN CONTACT WITH THIS SUBSTANCE.

GLOVES:

EMPLOYEE MUST WEAR APPROPRIATE PROTECTIVE GLOVES TO PREVENT CONTACT WITH THIS SUBSTANCE.

EYE PROTECTION:

EMPLOYEE MUST WEAR SPLASH-PROOF OR DUST-RESISTANT SAFETY GOGGLES AND A FACESHIELD TO PREVENT CONTACT WITH THIS SUBSTANCE.

EMERGENCY WASH FACILITIES:

WHERE THERE IS ANY POSSIBILITY THAT AN EMPLOYEE'S EYES AND/OR SKIN MAY BE EXPOSED TO THIS SUBSTANCE, THE EMPLOYER SHOULD PROVIDE AN EYE WASH FOUNTAIN AND QUICK DRENCH SHOWER WITHIN THE IMMEDIATE WORK AREA FOR EMERGENCY USE.

AUTHORIZED BY- OCCUPATIONAL HEALTH SERVICES, INC.

CREATION DATE: 05/24/90

REVISION DATE: 10/10/90

MATERIAL SAFETY DATA SHEET

OHS23850

OCCUPATIONAL HEALTH SERVICES, INC.
11 WEST 42ND STREET, 12TH FLOOR
NEW YORK, NEW YORK 10036
1-800-445-MSDS (1-800-445-6737) OR 1-212-789-3535

FOR EMERGENCY SOURCE INFORMATION
CONTACT: 1-615-366-2000

SUBSTANCE IDENTIFICATION

CAS-NUMBER 79-01-6
RTEC-NUMBER KX4550000

SUBSTANCE: **TRICHLOROETHYLENE**

TRADE NAMES/SYNONYMS:

ACETYLENE TRICHLORIDE: ETHYLENE TRICHLORIDE: ALGYLEN:
1-CHLORO-2,2-DICHLOROETHYLENE: 1,1-DICHLORO-2-CHLOROETHYLENE: TCE:
ANAMENTH: ETHINYL TRICHLORIDE: TRICHLOROETHENE:
1,1,2-TRICHLOROETHYLENE: ETHYLENE, TRICHLORO-: CHLORYLEN:
1,1,2-TRICHLOROETHENE: ETHENE, TRICHLORO-: NEU-TRI (R) SOLVENT (DOW
CHEMICAL): BLACO-TRI (BARON-BLAKESLEE): UN 1710: RCRA U228: STCC
4941171: C2HCL3: OHS23850

CHEMICAL FAMILY:

HALOGEN COMPOUND, ALIPHATIC

MOLECULAR FORMULA: CL-C-H-C-CL2 MOLECULAR WEIGHT: 131.39

CERCLA RATINGS (SCALE 0-3): HEALTH=3 FIRE=1 REACTIVITY=0 PERSISTENCE=3
NFPA RATINGS (SCALE 0-4): HEALTH=2 FIRE=1 REACTIVITY=0

COMPONENTS AND CONTAMINANTS

COMPONENT: TRICHLOROETHYLENE CAS# 79-01-6 PERCENT: >99

OTHER CONTAMINANTS: TRACES OF AMINES OR EPOXIDES AS INHIBITORS.

EXPOSURE LIMIT:

TRICHLOROETHYLENE:

50 PPM (270 MG/M3) OSHA TWA; 200 PPM (1080 MG/M3) OSHA STEL
50 PPM (270 MG/M3) ACGIH TWA; 200 PPM (1080 MG/M3) ACGIH STEL
25 PPM NIOSH RECOMMENDED 10 HOUR TWA

100 POUNDS CERCLA SECTION 103 REPORTABLE QUANTITY
SUBJECT TO SARA SECTION 313 ANNUAL TOXIC CHEMICAL RELEASE REPORTING
SUBJECT TO CALIFORNIA PROPOSITION 65 CANCER AND/OR REPRODUCTIVE TOXICITY
WARNING AND RELEASE REQUIREMENTS- (APRIL 1, 1988)

PHYSICAL DATA

DESCRIPTION: COLORLESS LIQUID WITH A MILD CHLOROFORM-LIKE ODOR.

BOILING POINT: 189 F (87 C)

MELTING POINT: -99 F (-73 C)

SPECIFIC GRAVITY: 1.4642

EVAPORATION RATE: (CARBON
TETRACHLORIDE=1) 0.69

SOLUBILITY IN WATER: 0.1%

VAPOR DENSITY: 4.53

VAPOR PRESSURE: 58 MMHG @ 20 C

ODOR-THRESHOLD: 21 PPM

OTHER SOLVENTS (SOLVENT - SOLUBILITY):
SOLUBLE IN ALCOHOL, ETHER, ACETONE, CHLOROFORM,
BENZENE AND VEGETABLE OILS.

FIRE AND EXPLOSION DATA

FIRE AND EXPLOSION HAZARD
SLIGHT FIRE HAZARD WHEN EXPOSED TO HEAT OR FLAME.

UPPER EXPLOSION LIMIT: 52% @ 100 C LOWER EXPLOSION LIMIT: 7.8% @ 100 C

AUTOIGNITION TEMP.: 770 F (410 C)

FIREFIGHTING MEDIA:
DRY CHEMICAL OR CARBON DIOXIDE
(1990 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5).

FOR LARGER FIRES, USE WATER SPRAY, FOG OR REGULAR FOAM
(1990 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5).

FIREFIGHTING:
APPLY COOLING WATER TO SIDES OF CONTAINERS THAT ARE EXPOSED TO FLAMES UNTIL
WELL AFTER FIRE IS OUT. STAY AWAY FROM ENDS OF TANKS. ISOLATE FOR 1/2 MILE IN
ALL DIRECTIONS IF TANK, RAIL CAR OR TANK TRUCK IS INVOLVED IN FIRE (1990
EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5, GUIDE PAGE 74).

USE AGENT SUITABLE FOR TYPE OF FIRE. AVOID BREATHING TOXIC VAPORS, KEEP
UPWIND.

TRANSPORTATION

DEPARTMENT OF TRANSPORTATION HAZARD CLASSIFICATION 49 CFR 172.101:
ORM-A

DEPARTMENT OF TRANSPORTATION LABELING REQUIREMENTS 49 CFR 172.101 AND
SUBPART E:
NONE

DEPARTMENT OF TRANSPORTATION PACKAGING REQUIREMENTS: 49 CFR 173.605
EXCEPTIONS: 49 CFR 173.505

TOXICITY

TRICHLOROETHYLENE:
IRRITATION DATA: 2 MG/24 HOURS SKIN-RABBIT SEVERE; 20 MG/24 HOURS
EYE-RABBIT MODERATE.

TOXICITY DATA: 6900 MG/M3/10 MINUTES INHALATION-HUMAN TCLO; 160 PPM/83 MINUTES INHALATION-HUMAN TCLO; 812 MG/KG INHALATION-HUMAN TDLO; 110 PPM/8 HOURS INHALATION-HUMAN TCLO; 2900 PPM INHALATION-HUMAN LCLO; 8000 PPM/4 HOURS INHALATION-RAT LCLO; 8450 PPM/4 HOURS INHALATION-MOUSE LC50; 11,000 PPM INHALATION-RABBIT LCLO; 32,500 MG/M3/2 HOURS INHALATION-CAT LCLO; 37,200 PPM/40 MINUTES INHALATION-GUINEA PIG LCLO; 7 GM/KG ORAL-HUMAN LDLO; 2143 MG/KG ORAL-HUMAN TDLO; 2402 MG/KG ORAL-MOUSE LD50; 7330 MG/KG ORAL-RABBIT LDLO; 5864 MG/KG ORAL-CAT LDLO; 16 GM/KG SUBCUTANEOUS-MOUSE LD50; 1800 MG/KG SUBCUTANEOUS-RABBIT LDLO; 150 MG/KG SUBCUTANEOUS-DOG LDLO; 34 MG/KG INTRAVENOUS-MOUSE LD50; 150 MG/KG INTRAVENOUS-DOG LDLO; 1282 MG/KG INTRAPERITONEAL-RAT LD50; 1900 MG/KG INTRAPERITONEAL-DOG LD50; MUTAGENIC DATA (RTECS); REPRODUCTIVE EFFECTS DATA (RTECS); TUMORIGENIC DATA (RTECS).

CARCINOGEN STATUS: HUMAN INADEQUATE EVIDENCE, ANIMAL LIMITED EVIDENCE (IARC GROUP-3). ORAL ADMINISTRATION PRODUCED LIVER AND LUNG NEOPLASMS IN MICE; INHALATION WAS ASSOCIATED WITH AN INCREASED INCIDENCE OF LYMPHOMAS IN FEMALE MICE, BUT NOT IN RATS OR HAMSTERS.

LOCAL EFFECTS: IRRITANT-SKIN, EYE, INHALATION.

ACUTE TOXICITY LEVEL: MODERATELY TOXIC BY INHALATION AND INGESTION.

TARGET EFFECTS: CENTRAL NERVOUS SYSTEM DEPRESSANT. POISONING MAY AFFECT THE LIVER, KIDNEYS, LUNG AND HEART.

AT INCREASED RISK FROM EXPOSURE: PERSON WITH PRE-EXISTING HEART DISEASE.

ADDITIONAL DATA: THE PRESENCE OF TETRACHLOROETHANE AS AN IMPURITY, OR THE CONSUMPTION OF ALCOHOLIC BEVERAGES, CAFFEINE, OR OTHER DRUGS MAY ENHANCE THE SYSTEMIC TOXICITY. EPINEPHRINE OR OTHER STIMULANTS MAY INDUCE VENTRICULAR ARRHYTHMIAS. MAY CROSS THE PLACENTA. ONE STUDY SHOWS AN INCREASED RISK OF LEUKEMIA FOR CHILDREN WHOSE FATHERS HAD OCCUPATIONAL EXPOSURE TO CHLORINATED SOLVENTS AFTER THE BIRTH OF THE CHILD.

HEALTH EFFECTS AND FIRST AID

INHALATION:

TRICHLOROETHYLENE:

IRRITANT/NARCOTIC.

1000 PPM IMMEDIATELY DANGEROUS TO LIFE OR HEALTH.

ACUTE EXPOSURE- MAY CAUSE MILD IRRITATION OF THE RESPIRATORY TRACT. LEVELS OF 250-1000 PPM HAVE CAUSED IMPAIRED JUDGEMENT AND COORDINATION.

1000-5000 PPM HAS CAUSED EXCITATION FOLLOWED BY CENTRAL NERVOUS SYSTEM DEPRESSION WITH DROWSINESS, DIZZINESS, HEADACHE, NAUSEA, VOMITING, UNCONSCIOUSNESS AND COMA. IF CONSCIOUSNESS IS REGAINED, NAUSEA AND VOMITING MAY FOLLOW FOR SEVERAL HOURS. PSYCHOTIC EFFECTS MAY INCLUDE EUPHORIA, DISORIENTATION, VISUAL DISTURBANCES AND HALLUCINATIONS, AND DELUSIONS. OTHER EFFECTS MAY INCLUDE ABDOMINAL CRAMPS, PALLOR, HYPOTENSION, ANESTHESIA, TREMORS, PROFUSE PERSPIRATION, CYANOSIS, AND RARELY CONVULSIONS. DEATH MAY OCCUR FROM RESPIRATORY ARREST OR VENTRICULAR FIBRILLATION RESULTING IN PRIMARY CARDIAC FAILURE. LIVER AND KIDNEY DAMAGE MAY ALSO OCCUR. ANIMAL STUDIES HAVE ALSO SHOWN SPLEEN DAMAGE. TRIGEMINAL NERVE DAMAGE AND HEPATOTOXIC EFFECTS HAVE BEEN ATTRIBUTED TO EXPOSURE TO THE IMPURE SUBSTANCE OR TO THE DECOMPOSITION PRODUCTS.

CHRONIC EXPOSURE- REPEATED EXPOSURE TO LEVELS BELOW 300 PPM MAY CAUSE NAUSEA, VOMITING, HEADACHE, ABDOMINAL CRAMPS, SLEEPINESS, DRUNKENNESS, FLUSHING, ANOREXIA, SWELLING OF THE EYES, FACE AND HANDS, AND MILD CARDIAC ARRHYTHMIAS. OTHER SYMPTOMS MAY INCLUDE WHEEZING, JOINT AND MUSCLE PAIN, ANEMIA, AND RARELY JAUNDICE. INTOLERANCE TO ALCOHOL, TREMOR, GIDDINESS, ANXIETY AND CARDIAC ARRHYTHMIAS HAVE BEEN FOUND IN WORKERS CHRONICALLY EXPOSED TO 5-630 PPM. LIVER, KIDNEY AND BRAIN DAMAGE MAY ALSO OCCUR. REPRODUCTIVE EFFECTS HAVE BEEN REPORTED IN ANIMALS. ADMINISTRATION TO

FEMALE MICE WAS ASSOCIATED WITH AN INCREASED INCIDENCE OF LYMPHOMAS;
HOWEVER, NONE WERE FOUND IN RATS OR HAMSTERS.

FIRST AID- REMOVE FROM EXPOSURE AREA TO FRESH AIR IMMEDIATELY. IF BREATHING
HAS STOPPED, PERFORM ARTIFICIAL RESPIRATION. KEEP PERSON WARM AND AT REST.
TREAT SYMPTOMATICALLY AND SUPPORTIVELY. GET MEDICAL ATTENTION IMMEDIATELY.

SKIN CONTACT:

TRICHLOROETHYLENE:

IRRITANT/SENSITIZER.

ACUTE EXPOSURE- MAY CAUSE IRRITATION AND CONTACT DERMATITIS. MAY CAUSE
SENSITIZATION IN PREVIOUSLY EXPOSED INDIVIDUALS AND RESULT IN GENERALIZED
EXFOLIATIVE OR PAPULOVESICULAR DERMATITIS, AND ERYTHRODERMA. SKIN CONTACT
WITH SOAKED CLOTHING FOR A LONG PERIOD OF TIME MAY RESULT IN BLISTERING.
MAY BE ABSORBED THROUGH THE SKIN, HOWEVER, DERMAL ABSORPTION IS NOT LIKELY
TO BE OF TOXICOLOGICAL SIGNIFICANCE UNDER NORMAL USE.

CHRONIC EXPOSURE- MAY CAUSE A DEFATTING TYPE OF DERMATITIS RESULTING IN
ROUGHNESS, CHAPPING, VESICULATION AND SECONDARY INFECTION. REPEATED
CONTACT MAY RESULT IN PARALYSIS OF THE FINGERS. SENSITIZATION MAY OCCUR.
REPEATED LOW LEVEL EXPOSURE MAY CAUSE INEBRIATION, IRRITABILITY, AND
PERSONALITY CHANGES. CHRONIC ABSORPTION MAY ALSO PRODUCE WEIGHT LOSS,
NAUSEA, ANOREXIA, FATIGUE, VISUAL IMPAIRMENT, JOINT PAIN AND WHEEZING.
JAUNDICE IS RARE.

FIRST AID- REMOVE CONTAMINATED CLOTHING AND SHOES IMMEDIATELY. WASH AFFECTED
AREA WITH SOAP OR MILD DETERGENT AND LARGE AMOUNTS OF WATER UNTIL NO
EVIDENCE OF CHEMICAL REMAINS (APPROXIMATELY 15-20 MINUTES). GET MEDICAL
ATTENTION IMMEDIATELY.

EYE CONTACT:

TRICHLOROETHYLENE:

IRRITANT.

ACUTE EXPOSURE- DIRECT CONTACT WITH VAPOR OR LIQUID MAY CAUSE BURNS OF THE
LIDS, CONJUNCTIVA AND CORNEA WITH SYMPTOMS OF REDNESS, TEARING AND BLURRED
VISION. A SPLASH IN THE EYE MAY CAUSE SMARTING PAIN AND INJURY TO THE
CORNEAL EPITHELIUM WHICH MAY REGENERATE WITH COMPLETE RECOVERY.

CHRONIC EXPOSURE- REPEATED AND PROLONGED EXPOSURE MAY CAUSE CONJUNCTIVITIS,
CORNEAL INFLAMMATION, OPTIC NEURITIS, DOUBLE VISION, NYSTAGMUS, CHANGES IN
COLOR PERCEPTION AND BLINDNESS.

FIRST AID- WASH EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER OR NORMAL SALINE,
OCCASIONALLY LIFTING UPPER AND LOWER LIDS, UNTIL NO EVIDENCE OF CHEMICAL
REMAINS (APPROXIMATELY 15-20 MINUTES). GET MEDICAL ATTENTION IMMEDIATELY.

INGESTION:

TRICHLOROETHYLENE:

NARCOTIC/LIMITED ANIMAL CARCINOGEN.

ACUTE EXPOSURE- MAY CAUSE SEVERE BURNING SENSATION IN THE MOUTH, THROAT,
ESOPHAGUS, AND STOMACH, DIARRHEA, INEBRIATION, CONFUSION, TACHYCARDIA, AND
CENTRAL NERVOUS SYSTEM DEPRESSION WITH DIZZINESS, NAUSEA, VOMITING,
HEADACHE, COLLAPSE, CONVULSIONS, AND COMA FOLLOWED BY DEATH FROM
RESPIRATORY, CARDIAC OR HEPATORENAL FAILURE. LOW-LEVEL CONCENTRATIONS MAY
CAUSE HEADACHE, AMNESIA, NUMBNESS, WEAKNESS OF THE EXTREMITIES,
HEMIPARESIS AND PSYCHOSIS.

CHRONIC EXPOSURE- MAY CAUSE IRRITATION OF MUCOUS MEMBRANES, HEADACHE,
DROWSINESS, FATIGUE, GIDDINESS, EXCITABILITY, INDIGESTION, NAUSEA,
DISTURBANCES OF SENSATIONS IN THE EXTREMITIES AND OTHER SYMPTOMS NOTED IN

CHRONIC INHALATION. REPRODUCTIVE EFFECTS HAVE BEEN REPORTED IN ANIMALS. REPEATED ORAL ADMINISTRATION PRODUCED LIVER AND LUNG NEOPLASMS IN MICE.

FIRST AID- REMOVE BY GASTRIC LAVAGE OR EMESIS. MAINTAIN BLOOD PRESSURE AND AIRWAY. GIVE OXYGEN IF RESPIRATION IS DEPRESSED. DO NOT PERFORM GASTRIC LAVAGE OR EMESIS IF VICTIM IS UNCONSCIOUS. GET MEDICAL ATTENTION IMMEDIATELY (DREISBACH, HANDBOOK OF POISONING, 11TH ED.). ADMINISTRATION OF GASTRIC LAVAGE OR OXYGEN SHOULD BE PERFORMED BY QUALIFIED MEDICAL PERSONNEL.

ANTIDOTE:

NO SPECIFIC ANTIDOTE. TREAT SYMPTOMATICALLY AND SUPPORTIVELY.

REACTIVITY SECTION

REACTIVITY:

STABLE UNDER NORMAL TEMPERATURES AND PRESSURES IN A CLOSED CONTAINER. UNINHIBITED MATERIAL, ON HEATING OR EXPOSURE TO LIGHT, MAY DECOMPOSE OR POLYMERIZE, RELEASING HYDROGEN CHLORIDE.

INCOMPATIBILITIES:

TRICHLOROETHYLENE:

ALKALI: FORMS EXPLOSIVE MIXTURE.

ALUMINUM + DILUTE HYDROCHLORIC ACID: VIOLENT POLYMERIZATION.

ALUMINUM: VIOLENT DECOMPOSITION MAY OCCUR ON CONTACT WITH ALUMINUM POWDER OR FRESHLY FORMED SURFACES.

BARIUM: POSSIBLE DETONATION.

BERYLLIUM: FORMS IMPACT-SENSITIVE MIXTURE.

BORON: FORMS EXPLOSIVE OR IGNITABLE COMPOUND.

1-CHLORO-2,3-EPOXYPROPANE: FORMS EXPLOSIVE MIXTURE.

2,4-BIS(4(2',3'-EPOXYPROPOXY)PHENYL)PROPANE: FORMS EXPLOSIVE MIXTURE.

DI-2,3-EPOXYPROPYL ETHER OF 1,4-BUTANEDIOL: FORMS EXPLOSIVE MIXTURE.

EPOXIDES: POSSIBLE EXPLOSION.

LITHIUM: FORMS IMPACT-SENSITIVE MIXTURE.

MAGNESIUM: FORMS IMPACT-SENSITIVE MIXTURE.

METALS (POWDERED): FORMS EXPLOSIVE OR IGNITABLE COMPOUND.

MONO-2,3-EPOXYPROPYL ETHER OF 1,4-BUTANEDIOL: FORMS EXPLOSIVE MIXTURE.

NITROGEN TETRAOXIDE: FORMS EXPLOSIVE MIXTURE.

OXIDIZERS (STRONG): FIRE AND EXPLOSION HAZARD.

OXYGEN (LIQUID): EXPLODES WHEN INITIATED WITH A BLASTING CAP.

OXYGEN (GAS): EXPLODES UNDER PRESSURE AT ROOM TEMPERATURE.

PERCHLORIC ACID: VIOLENT REACTION.

POTASSIUM: FORMS EXPLOSIVE CHLOROACETYLENES.

POTASSIUM HYDROXIDE: FORMS EXPLOSIVE DICHLOROACETYLENE WHEN HEATED.

SODIUM: FORMS EXPLOSIVE CHLOROACETYLENES.

SODIUM HYDROXIDE: FORMS EXPLOSIVE CHLOROACETYLENES.

TITANIUM (POWDER): FORMS IMPACT-SENSITIVE MIXTURE.

DECOMPOSITION:

THERMAL DECOMPOSITION PRODUCTS MAY INCLUDE HIGHLY TOXIC FUMES OF PHOSGENE, TOXIC AND CORROSIVE FUMES OF CHLORIDES, AND OXIDES OF CARBON.

POLYMERIZATION:

MAY POLYMERIZE WHEN CATALYZED BY ALUMINUM CHLORIDE IN A SELF-SUSTAINING REACTION WHICH MAY DEVELOP TEMPERATURES UP TO 1350 C. A STABILIZER IS REQUIRED TO PREVENT POLYMERIZATION WHEN HEATED OR EXPOSED TO SUNLIGHT.

STORAGE-DISPOSAL

OBSERVE ALL FEDERAL, STATE AND LOCAL REGULATIONS WHEN STORING OR DISPOSING OF THIS SUBSTANCE. FOR ASSISTANCE, CONTACT THE DISTRICT DIRECTOR OF THE ENVIRONMENTAL PROTECTION AGENCY.

STORAGE

STORE IN A COOL, DRY, WELL-VENTILATED LOCATION, AWAY FROM ANY AREA WHERE THE FIRE HAZARD MAY BE ACUTE (NFPA 49, HAZARDOUS CHEMICALS DATA, 1975).

STORE AWAY FROM INCOMPATIBLE SUBSTANCES.

DISPOSAL

DISPOSAL MUST BE IN ACCORDANCE WITH STANDARDS APPLICABLE TO GENERATORS OF HAZARDOUS WASTE, 40CFR 262. EPA HAZARDOUS WASTE NUMBER U228.

TRICHLOROETHYLENE - REGULATORY LEVEL: 0.5 MG/L
MATERIALS WHICH CONTAIN THE ABOVE SUBSTANCE AT OR ABOVE THE REGULATORY LEVEL MEET THE EPA CHARACTERISTIC OF TOXICITY, AND MUST BE DISPOSED OF IN ACCORDANCE WITH 40 CFR PART 262. EPA HAZARDOUS WASTE NUMBER D040.

CONDITIONS TO AVOID

MAY BURN BUT DOES NOT IGNITE READILY. CONTAINER MAY EXPLODE IN HEAT OF FIRE.

SPILLS AND LEAKS

SOIL-RELEASE:

DIG A HOLDING AREA SUCH AS A PIT, POND OR LAGOON TO CONTAIN SPILL AND DIKE SURFACE FLOW USING BARRIER OF SOIL, SANDBAGS, FOAMED POLYURETHANE OR FOAMED CONCRETE. ABSORB LIQUID MASS WITH FLY ASH OR CEMENT POWDER.

AIR-RELEASE:

APPLY WATER SPRAY TO KNOCK DOWN AND REDUCE VAPORS. KNOCK-DOWN WATER IS CORROSIVE AND TOXIC AND SHOULD BE DIKED FOR CONTAINMENT.

WATER-SPILL:

USE ACTIVATED CARBON TO ABSORB SPILLED SUBSTANCE THAT IS DISSOLVED.

USE SUCTION HOSES TO REMOVE TRAPPED SPILL MATERIAL.

USE MECHANICAL DREDGES OR LIFTS TO EXTRACT IMMOBILIZED MASSES OF POLLUTION AND PRECIPITATES.

THE CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986 (PROPOSITION 65) PROHIBITS CONTAMINATING ANY KNOWN SOURCE OF DRINKING WATER WITH SUBSTANCES KNOWN TO CAUSE CANCER AND/OR REPRODUCTIVE TOXICITY.

OCCUPATIONAL-SPILL:

SHUT OFF IGNITION SOURCES. STOP LEAK IF YOU CAN DO IT WITHOUT RISK. FOR SMALL LIQUID SPILLS, TAKE UP WITH SAND, EARTH OR OTHER ABSORBENT MATERIAL. FOR LARGER SPILLS, DIKE FAR AHEAD OF SPILL FOR LATER DISPOSAL. NO SMOKING, FLAMES OR FLARES IN HAZARD AREA! KEEP UNNECESSARY PEOPLE AWAY.

REPORTABLE QUANTITY (RQ): 100 POUNDS

THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT (SARA) SECTION 304 REQUIRES THAT A RELEASE EQUAL TO OR GREATER THAN THE REPORTABLE QUANTITY FOR THIS SUBSTANCE BE IMMEDIATELY REPORTED TO THE LOCAL EMERGENCY PLANNING COMMITTEE AND THE STATE EMERGENCY RESPONSE COMMISSION (40 CFR 355.40). IF THE RELEASE OF THIS SUBSTANCE IS REPORTABLE UNDER CERCLA SECTION 103, THE NATIONAL RESPONSE CENTER MUST BE NOTIFIED IMMEDIATELY AT (800) 424-8802 OR (202) 426-2675 IN THE METROPOLITAN WASHINGTON, D.C. AREA (40 CFR 302.6).

PROTECTIVE EQUIPMENT SECTION

VENTILATION:

PROVIDE LOCAL EXHAUST OR PROCESS ENCLOSURE VENTILATION TO MEET PUBLISHED EXPOSURE LIMITS.

RESPIRATOR:

THE FOLLOWING RESPIRATORS AND MAXIMUM USE CONCENTRATIONS ARE RECOMMENDATIONS BY THE U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES, NIOSH POCKET GUIDE TO CHEMICAL HAZARDS; NIOSH CRITERIA DOCUMENTS OR BY THE U.S. DEPARTMENT OF LABOR, 29 CFR 1910 SUBPART Z.

THE SPECIFIC RESPIRATOR SELECTED MUST BE BASED ON CONTAMINATION LEVELS FOUND IN THE WORK PLACE, MUST NOT EXCEED THE WORKING LIMITS OF THE RESPIRATOR AND BE JOINTLY APPROVED BY THE NATIONAL INSTITUTE FOR OCCUPATIONAL SAFETY AND HEALTH AND THE MINE SAFETY AND HEALTH ADMINISTRATION (NIOSH-MSHA).

TRICHLOROETHYLENE:

AT ANY DETECTABLE CONCENTRATION:

ANY SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE AND OPERATED IN A PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.

ANY SUPPLIED-AIR RESPIRATOR WITH A FULLFACE-PIECE AND OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE IN COMBINATION WITH AN AUXILIARY SELF-CONTAINED BREATHING APPARATUS OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.

ESCAPE-ANY AIR-PURIFYING FULL FACEPIECE RESPIRATOR (GAS MASK) WITH A CHIN-STYLE OR FRONT- OR BACKMOUNTED ORGANIC VAPOR CANISTER.
ANY APPROPRIATE ESCAPE-TYPE SELF-CONTAINED BREATHING APPARATUS.

FOR FIREFIGHTING AND OTHER IMMEDIATELY DANGEROUS TO LIFE OR HEALTH CONDITIONS:

SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.

SUPPLIED-AIR RESPIRATOR WITH FULL FACEPIECE AND OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE IN COMBINATION WITH AN AUXILIARY SELF-CONTAINED BREATHING APPARATUS OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.

CLOTHING:

EMPLOYEE MUST WEAR APPROPRIATE PROTECTIVE (IMPERVIOUS) CLOTHING AND EQUIPMENT TO PREVENT REPEATED OR PROLONGED SKIN CONTACT WITH THIS SUBSTANCE.

GLOVES:

EMPLOYEE MUST WEAR APPROPRIATE PROTECTIVE GLOVES TO PREVENT CONTACT WITH THIS SUBSTANCE.

EYE PROTECTION:

EMPLOYEE MUST WEAR SPLASH-PROOF OR DUST-RESISTANT SAFETY GOGGLES TO PREVENT EYE CONTACT WITH THIS SUBSTANCE.

EMERGENCY EYE WASH: WHERE THERE IS ANY POSSIBILITY THAT AN EMPLOYEE'S EYES MAY BE EXPOSED TO THIS SUBSTANCE, THE EMPLOYER SHOULD PROVIDE AN EYE WASH FOUNTAIN WITHIN THE IMMEDIATE WORK AREA FOR EMERGENCY USE.

AUTHORIZED BY- OCCUPATIONAL HEALTH SERVICES, INC.

CREATION DATE: 10/24/84

REVISION DATE: 10/10/90

MATERIAL SAFETY DATA SHEET

OHS04310

OCCUPATIONAL HEALTH SERVICES, INC.
11 WEST 42ND STREET, 12TH FLOOR
NEW YORK, NEW YORK 10036
1-800-445-MSDS (1-800-445-6737) OR 1-212-789-3535

FOR EMERGENCY SOURCE INFORMATION
CONTACT: 1-615-366-2000

SUBSTANCE IDENTIFICATION

CAS-NUMBER 56-23-5
RTEC-NUMBER FG4900000

SUBSTANCE: **CARBON TETRACHLORIDE**

TRADE NAMES/SYNONYMS:

METHANE, TETRACHLORO-: CARBON CHLORIDE (CCL4): PERCHLOROMETHANE:
TETRACHLOROMETHANE: BENZINOFORM: NECATORINA: R 10: R 10
(REFRIGERANT): RCRA U211: UN 1846: STCC 4940320: CCL4: OHS04310

CHEMICAL FAMILY:

HALOGEN COMPOUND, ALIPHATIC

MOLECULAR FORMULA: C-CL4

MOLECULAR WEIGHT: 153.82

CERCLA RATINGS (SCALE 0-3): HEALTH=3 FIRE=0 REACTIVITY=0 PERSISTENCE=3
NFPA RATINGS (SCALE 0-4): HEALTH=3 FIRE=0 REACTIVITY=0

COMPONENTS AND CONTAMINANTS

COMPONENT: CARBON TETRACHLORIDE CAS# 56-23-5

PERCENT: 100.0

OTHER CONTAMINANTS: NONE

EXPOSURE LIMIT:

CARBON TETRACHLORIDE:

2 PPM (12.6 MG/M3) OSHA TWA

5 PPM (30 MG/M3) ACGIH TWA (SKIN)

ACGIH A2-SUSPECTED HUMAN CARCINOGEN.

2 PPM NIOSH RECOMMENDED 60 MINUTE CEILING (45 LITER SAMPLE)

10 POUNDS CERCLA SECTION 103 REPORTABLE QUANTITY

SUBJECT TO SARA SECTION 313 ANNUAL TOXIC CHEMICAL RELEASE REPORTING

SUBJECT TO CALIFORNIA PROPOSITION 65 CANCER AND/OR REPRODUCTIVE TOXICITY

WARNING AND RELEASE REQUIREMENTS- (OCTOBER 1, 1987)

PHYSICAL DATA

DESCRIPTION: CLEAR, COLORLESS, HEAVY LIQUID WITH CHARACTERISTIC ODOR.

BOILING POINT: 171 F (77 C)

MELTING POINT: -9 F (-23 C)

SPECIFIC GRAVITY: 1.5940

EVAPORATION RATE: (BUTYL ACETATE=1)
12.8

VOLATILITY: 100%

SOLUBILITY IN WATER: 0.08% @ 20 C

VAPOR DENSITY: 5.32

VAPOR PRESSURE: 91.3 MMHG @ 20 C

ODOR-THRESHOLD: 50 PPM

OTHER SOLVENTS (SOLVENT - SOLUBILITY):

SOLUBLE IN ALCOHOL, BENZENE, CHLOROFORM, ETHER, CARBON
DISULFIDE, PETROLEUM ETHER, SOLVENT NAPHTHA AND MOST FIXED, VOLATILE OILS AND
ACETONE.

FIRE AND EXPLOSION DATA

FIRE AND EXPLOSION HAZARD

NEGLIGIBLE FIRE HAZARD WHEN EXPOSED TO HEAT OR FLAME.

FLASH POINT: NONE

FIREFIGHTING MEDIA:

DRY CHEMICAL, WATER SPRAY OR REGULAR FOAM
(1990 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5).

FOR LARGER FIRES, USE WATER SPRAY, FOG OR REGULAR FOAM
(1990 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5).

FIREFIGHTING:

MOVE CONTAINER FROM FIRE AREA IF YOU CAN DO IT WITHOUT RISK. FIGHT FIRE FROM
MAXIMUM DISTANCE. STAY AWAY FROM ENDS OF TANKS. DIKE FIRE-CONTROL WATER FOR
LATER DISPOSAL; DO NOT SCATTER THE MATERIAL (1990 EMERGENCY RESPONSE
GUIDEBOOK, DOT P 5800.5, GUIDE PAGE 55).

USE SUITABLE AGENT FOR SURROUNDING FIRE. AVOID BREATHING VAPORS OR DUSTS,
KEEP UPWIND.

TRANSPORTATION

DEPARTMENT OF TRANSPORTATION HAZARD CLASSIFICATION 49 CFR 172.101:
ORM-A

DEPARTMENT OF TRANSPORTATION LABELING REQUIREMENTS 49 CFR 172.101 AND
SUBPART E:
NONE

DEPARTMENT OF TRANSPORTATION PACKAGING REQUIREMENTS: 49 CFR 173.620
EXCEPTIONS: 49 CFR 173.505

TOXICITY

CARBON TETRACHLORIDE:

IRRITATION DATA: 4 MG SKIN-RABBIT MILD; 500 MG/24 HOURS SKIN-RABBIT MILD;
2200 UG/30 SECONDS EYE-RABBIT MILD; 500 MG/24 HOURS EYE-RABBIT MILD.

TOXICITY DATA: 20 PPM INHALATION-HUMAN TCLO; 1000 PPM INHALATION-HUMAN LCLO;
45 PPM/3 DAYS INHALATION-HUMAN TCLO; 317 PPM/30 MINUTES INHALATION-HUMAN

TCLO; 5 PPH/5 MINUTES INHALATION-HUMAN LCLO; 8000 PPM/4 HOURS INHALATION-RAT LC50; 9526 PPM/8 HOURS INHALATION-MOUSE LC50; 20,000 PPM/2 HOURS INHALATION-GUINEA PIG LCLO; 38,110 PPM/2 HOURS INHALATION-CAT LCLO; 14,620 PPM/8 HOURS INHALATION-DOG LCLO; 34,500 MG/M3 INHALATION-MAMMAL LC50; 5070 MG/KG SKIN-RAT LD50; 1700 MG/KG ORAL-MAN TDLO; 1800 MG/KG ORAL-WOMAN TDLO; 2350 MG/KG ORAL-RAT LD50; 8263 MG/KG ORAL-MOUSE LD50; 5760 MG/KG MG/KG ORAL-RABBIT LD50; 5760 MG/KG ORAL-GUINEA PIG LD50; 1 GM/KG ORAL-DOG LDLO; 31 GM/KG SUBCUTANEOUS-MOUSE LD50; 3000 MG/KG SUBCUTANEOUS-RABBIT LDLO; 300 MG/KG SUBCUTANEOUS-CAT LDLO; 5840 MG/KG INTRAVENOUS-RABBIT LD50; 125 MG/KG INTRAVENOUS-DOG LDLO; 1500 MG/KG INTRAPERITONEAL-RAT LD50; 572 MG/KG INTRAPERITONEAL-MOUSE LD50; 478 MG/KG INTRAPERITONEAL-RABBIT LDLO; 1500 MG/KG INTRAPERITONEAL-DOG LD50; 93 MG/KG UNREPORTED-MAN LDLO; MUTAGENIC DATA (RTECS); REPRODUCTIVE EFFECTS DATA (RTECS); TUMORIGENIC DATA (RTECS).

CARCINOGEN STATUS: ANTICIPATED HUMAN CARCINOGEN (NTP); ANIMAL SUFFICIENT EVIDENCE, HUMAN INADEQUATE EVIDENCE (IARC GROUP-2B). CARBON TETRACHLORIDE WAS TESTED IN SEVERAL EXPERIMENTS IN MICE BY ORAL AND INTRARECTAL ADMINISTRATION AND IN RATS BY ORAL AND SUBCUTANEOUS ADMINISTRATION AND BY INHALATION EXPOSURE. IN VARIOUS STRAINS OF MICE, IT PRODUCED LIVER TUMORS, INCLUDING HEPATOCELLULAR CARCINOMAS. IN VARIOUS STRAINS OF RATS, IT PRODUCED BENIGN AND MALIGNANT LIVER TUMORS; AND IN ONE EXPERIMENT WITH SUBCUTANEOUS INJECTION, AN INCREASED INCIDENCE OF MAMMARY ADENOCARCINOMAS WAS OBSERVED.

ACUTE TOXICITY LEVEL: MODERATELY TOXIC BY INHALATION, INGESTION; SLIGHTLY TOXIC BY DERMAL ABSORPTION.

TARGET EFFECTS: CENTRAL NERVOUS SYSTEM DEPRESSANT; NEPHROTOXIN; HEPATOTOXIN. POISONING MAY ALSO AFFECT THE CARDIOVASCULAR SYSTEM.

AT INCREASED RISK FROM EXPOSURE: PERSONS WITH PRE-EXISTING LIVER AND/OR KIDNEY DAMAGE AND ALCOHOLICS.

ADDITIONAL DATA: MAY CROSS THE PLACENTA AND BE EXCRETED IN BREAST MILK.

ONE STUDY SHOWS AN INCREASED RISK OF LEUKEMIA FOR CHILDREN WHOSE FATHERS HAD OCCUPATIONAL EXPOSURE TO CHLORINATED SOLVENTS AFTER THE BIRTH OF THE CHILD. STIMULANTS SUCH AS EPINEPHRINE MAY INDUCE VENTRICULAR FIBRILLATION. ALCOHOLS, HALOALKANES, KETONES, BARBITURATES, PCB'S, PBB'S, AND DDT MAY ENHANCE THE TOXIC EFFECTS.

HEALTH EFFECTS AND FIRST AID

INHALATION:

CARBON TETRACHLORIDE:

NARCOTIC/NEPHROTOXIN/HEPATOTOXIN/CARCINOGEN.

ACUTE EXPOSURE- MAY CAUSE IRRITATION. EXPOSURE TO 25-117 PPM HAS CAUSED NAUSEA, HEADACHE, DIZZINESS, DEPRESSION, NARCOSIS, DYSPEPSIA, RESTRICTED VISION, AND LIVER DAMAGE. UNCONSCIOUSNESS, COMA AND DEATH MAY OCCUR AT 1000-2000 PPM/60-90 MINUTES. DEATH MAY BE DUE TO RESPIRATORY ARREST OR CIRCULATORY COLLAPSE, OR OCCASIONALLY, VENTRICULAR FIBRILLATION. OTHER EFFECTS MAY INCLUDE ABDOMINAL PAIN, DIARRHEA, VOMITING, HEMATEMESIS, MENTAL CONFUSION, HYPOTENSION, AND CONVULSIONS. IF DEATH IS NOT IMMEDIATE, AN ASYMPTOMATIC PERIOD OF SEVERAL DAYS MAY BE FOLLOWED BY KIDNEY NECROSIS WITH ALBUMINURIA, OLIGURIA OR ANURIA, EDEMA, PULMONARY EDEMA, AND UREMIA. HEPATIC NECROSIS WITH FATTY ACCUMULATION MAY OCCUR WITH SYMPTOMS OF NAUSEA, ANOREXIA, FLATULANCE, VOMITING, STOMACHACHE, JAUNDICE, AND AN ENLARGED AND TENDER LIVER. LIVER FAILURE MAY BE ACCOMPANIED BY ENCEPHALOPATHY. IN NON-FATAL CASES, KIDNEY AND LIVER FUNCTION MAY RETURN TO NORMAL. OTHER ORGANS THAT MAY BE AFFECTED INCLUDE PANCREAS, ADRENALS, TESTES, SPLEEN, PITUITARY, AND THYROID. HEPATIC NECROSIS, NEPHROSIS AND DEATH OCCURRED IN AN ALCOHOLIC EXPOSED TO 250 PPM/15 MINUTES; SLIGHT HEADACHE WAS REPORTED IN NON-ALCOHOLICS.

CHRONIC EXPOSURE- REPEATED OR PROLONGED EXPOSURE MAY CAUSE EFFECTS AS IN ACUTE INHALATION. OTHER EFFECTS MAY INCLUDE ANEMIA, AND VARIOUS VISUAL DISTURBANCES SUCH AS BLIND SPOTS, SPOTS BEFORE EYES, VISUAL HAZE, AND RESTRICTIONS OF COLOR FIELDS WHICH MAY INDICATE OPTIC NEURITIS OR ATROPHY. CASE REPORTS HAVE DESCRIBED LIVER TUMORS ASSOCIATED WITH CIRRHOSIS IN EXPOSED PERSONS. A MORTALITY STUDY OF LAUNDRY AND DRY CLEANING WORKERS EXPOSED TO CARBON TETRACHLORIDE AND A VARIETY OF OTHER SOLVENTS SUGGESTS AN EXCESS OF RESPIRATORY CANCERS, LIVER TUMORS, CERVICAL CANCERS, AND LEUKEMIA. IN RATS, CHRONIC INHALATION PRODUCED BENIGN AND MALIGNANT LIVER TUMORS. REPRODUCTIVE EFFECTS REPORTED IN ANIMALS INCLUDE A DECREASE IN FERTILITY, EMBRYOTOXICITY, FETOTOXICITY, AND A MODERATE TO MARKED DEGENERATION OF TESTICULAR GERMINAL EPITHELIUM.

FIRST AID- REMOVE FROM EXPOSURE AREA TO FRESH AIR IMMEDIATELY. IF BREATHING HAS STOPPED, PERFORM ARTIFICIAL RESPIRATION. KEEP PERSON WARM AND AT REST. TREAT SYMPTOMATICALLY AND SUPPORTIVELY. GET MEDICAL ATTENTION IMMEDIATELY.

SKIN CONTACT:

CARBON TETRACHLORIDE:

NARCOTIC/NEPHROTOXIN/HEPATOTOXIN.

ACUTE EXPOSURE- CONTACT WITH THE LIQUID MAY CAUSE DISTINCT PAIN WITH ERYTHEMA, HYPEREMIA, AND WHEEL FORMATION FOLLOWED BY VESICATION; SKIN ERUPTIONS ARE SOMETIMES SEEN. MAY BE ABSORBED THROUGH THE SKIN TO CAUSE EFFECTS AS DETAILED IN ACUTE INHALATION.

CHRONIC EXPOSURE- REPEATED OR PROLONGED CONTACT MAY RESULT IN IRRITATION AND DERMATITIS DUE TO THE DEFATTING ACTION ON THE SKIN. TOXIC AMOUNTS MAY BE ABSORBED THROUGH THE SKIN TO CAUSE EFFECTS AS DETAILED IN CHRONIC INHALATION.

FIRST AID- REMOVE CONTAMINATED CLOTHING AND SHOES IMMEDIATELY. WASH AFFECTED AREA WITH SOAP OR MILD DETERGENT AND LARGE AMOUNTS OF WATER UNTIL NO EVIDENCE OF CHEMICAL REMAINS (APPROXIMATELY 15-20 MINUTES). GET MEDICAL ATTENTION IMMEDIATELY.

EYE CONTACT:

CARBON TETRACHLORIDE:

ACUTE EXPOSURE- CONTACT WITH LIQUID OR VAPOR MAY CAUSE SLIGHT, TRANSIENT IRRITATION AND MINOR CONJUNCTIVAL INJURY.

CHRONIC EXPOSURE- NO DATA AVAILABLE.

FIRST AID- WASH EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER OR NORMAL SALINE, OCCASIONALLY LIFTING UPPER AND LOWER LIDS, UNTIL NO EVIDENCE OF CHEMICAL REMAINS (APPROXIMATELY 15-20 MINUTES). GET MEDICAL ATTENTION IMMEDIATELY.

INGESTION:

CARBON TETRACHLORIDE:

NARCOTIC/NEPHROTOXIN/HEPATOTOXIN/CARCINOGEN.

ACUTE EXPOSURE- MAY CAUSE EFFECTS AS IN ACUTE INHALATION. ASPIRATION MAY PRODUCE PRIMARY PULMONARY EDEMA. DOSES OF 40-48 MG/KG PRODUCED LIVER INJURY IN ANIMALS. INGESTION OF 1.5 ML HAS CAUSED DEATH.

CHRONIC EXPOSURE- REPEATED ADMINISTRATION TO ANIMALS HAS PRODUCED LIVER AND KIDNEY CHANGES. ADMINISTRATION TO ANIMALS PRODUCED LIVER TUMORS, INCLUDING HEPATOCELLULAR CARCINOMAS, IN VARIOUS STRAINS OF MICE; AND IN RATS CAUSED BENIGN AND MALIGNANT LIVER TUMORS. AS EVALUATED BY RTECS, ADMINISTRATION TO MICE RESULTED IN A STATISTICALLY SIGNIFICANT INCREASE IN THE INCIDENCE OF NEOPLASTIC TUMORS OF THE SKIN. ADMINISTRATION DURING GESTATION PRODUCED MARKED MATERNAL TOXICITY AND TOTAL RESORPTION OF FETUSES IN SOME ANIMALS, BUT NO TERATOGENICITY OR OTHER ADVERSE EFFECTS ON SURVIVORS.

FIRST AID- IF THE PERSON IS CONSCIOUS AND NOT CONVULSING, INDUCE EMESIS BY GIVING SYRUP OF IPECAC (KEEPING THE HEAD BELOW THE HIPS TO PREVENT ASPIRATION), FOLLOWED BY WATER. REPEAT IN 20 MINUTES IF NOT EFFECTIVE INITIALLY. IN PATIENTS WITH DEPRESSED RESPIRATION OR IF EMESIS IS NOT PRODUCED, PERFORM GASTRIC LAVAGE CAUTIOUSLY (DREISBACH, HANDBOOK OF POISONING, 12TH ED.). TREAT SYMPTOMATICALLY AND SUPPORTIVELY. GASTRIC LAVAGE SHOULD BE PERFORMED BY QUALIFIED MEDICAL PERSONNEL. GET MEDICAL ATTENTION IMMEDIATELY.

ANTIDOTE:

NO SPECIFIC ANTIDOTE. TREAT SYMPTOMATICALLY AND SUPPORTIVELY.

REACTIVITY SECTION

REACTIVITY:

STABLE UNDER NORMAL TEMPERATURES AND PRESSURES.

INCOMPATIBILITIES:

CARBON TETRACHLORIDE:

ALLYL ALCOHOL: FORMS EXPLOSIVE PRODUCTS.

ALUMINUM OXIDE AND COBALT/MOLYBDENUM: EXOTHERMIC REACTION IN PRESENCE OF AIR

ALUMINUM TRICHLORIDE: INCOMPATIBLE.

BENZOYL PEROXIDE: INCOMPATIBLE.

BENZOYL PEROXIDE AND ETHYLENE: VIOLENT EXPLOSION REACTION.

BORANES: POTENTIALLY EXPLOSIVE REACTION ON CONTACT.

BROMINE TRIFLUORIDE: EXOTHERMIC REACTION.

CALCIUM DISILIDE: POSSIBLE EXPLOSION ON IMPACT.

CALCIUM HYPOCHLORITE: EXPLOSIVE REACTION ON HEATING.

CHLORINE TRIFLUORIDE: FORMS EXPLOSIVE MIXTURE.

DIMETHYLACETAMIDE: EXOTHERMIC REACTION WITH INCREASE IN PRESSURE OR

VIGOROUS REACTION IN PRESENCE OF IRON.

DIMETHYLFORMAMIDE: VIOLENT REACTION IN PRESENCE OF IRON OR AT TEMPERATURES BELOW 100 C.

DINITROGEN TETRAOXIDE: FORMATION OF SHOCK-SENSITIVE MIXTURE.

ETHYLENE: MAY FORM EXPLOSIVE MIXTURE.

FLUORINE: VIOLENT REACTION OR POSSIBLE EXPLOSION.

HEXACHLOROCYCLOHEXANE: VIGOROUS REACTION.

METALS: POSSIBLE EXPLOSION ON HEATING OR IMPACT.

OXYGEN (LIQUID): VIGOROUS EXPLOSION REACTION.

PLASTICS, RUBBER AND COATINGS: MAY BE ATTACKED.

POTASSIUM TERT-BUTOXIDE: IGNITION REACTION.

SILANES (DI-, TRI-, TETRA-): EXOTHERMIC REACTION WITH POSSIBLE EXPLOSION.

SILVER PERCHLORATE AND HYDROGEN CHLORIDE: PRODUCES EXPLOSIVE MIXTURE.

TRIETHYLDIALUMINUM SESQUICHLORIDES: FORMATION OF HEAT-SENSITIVE PRODUCT.

TETRAETHYLENEPENTAMINE: POSSIBLE EXPLOSION REACTION.

WAX (BURNING): EXPLOSIVE REACTION.

DECOMPOSITION:

THERMAL DECOMPOSITION PRODUCTS MAY INCLUDE HIGHLY TOXIC FUMES OF PHOSGENE, TOXIC AND CORROSIVE FUMES OF CHLORIDES, AND OXIDES OF CARBON.

POLYMERIZATION:

HAZARDOUS POLYMERIZATION HAS NOT BEEN REPORTED TO OCCUR UNDER NORMAL TEMPERATURES AND PRESSURES.

STORAGE-DISPOSAL

OBSERVE ALL FEDERAL, STATE AND LOCAL REGULATIONS WHEN STORING OR DISPOSING OF THIS SUBSTANCE. FOR ASSISTANCE, CONTACT THE DISTRICT DIRECTOR OF THE ENVIRONMENTAL PROTECTION AGENCY.

STORAGE

STORE AWAY FROM INCOMPATIBLE SUBSTANCES.

PROTECT AGAINST PHYSICAL DAMAGE. STORE IN A COOL, DRY WELL VENTILATED LOCATION, AWAY FROM ANY AREA WHERE THE FIRE HAZARD MAY BE ACUTE (NFPA 49, HAZARDOUS CHEMICALS DATA, 1975).

DISPOSAL

DISPOSAL MUST BE IN ACCORDANCE WITH STANDARDS APPLICABLE TO GENERATORS OF HAZARDOUS WASTE, 40CFR 262. EPA HAZARDOUS WASTE NUMBER U211.

CARBON TETRACHLORIDE - REGULATORY LEVEL: 0.5 MG/L
MATERIALS WHICH CONTAIN THE ABOVE SUBSTANCE AT OR ABOVE THE REGULATORY LEVEL MEET THE EPA CHARACTERISTIC OF TOXICITY, AND MUST BE DISPOSED OF IN ACCORDANCE WITH 40 CFR PART 262. EPA HAZARDOUS WASTE NUMBER D019.

CONDITIONS TO AVOID

MAY BURN BUT DOES NOT IGNITE READILY. CONTAINERS MAY EXPLODE IN HEAT OF FIRE.

SPILLS AND LEAKS

SOIL-RELEASE:

DIG A HOLDING AREA SUCH AS A PIT, POND OR LAGOON TO CONTAIN SPILL AND DIKE SURFACE FLOW USING BARRIER OF SOIL, SANDBAGS, FOAMED POLYURETHANE OR FOAMED CONCRETE. ABSORB LIQUID MASS WITH FLY ASH OR CEMENT POWDER.

IMMOBILIZE SPILL WITH UNIVERSAL GELLING AGENT.

AIR-RELEASE:

KNOCK DOWN VAPORS WITH WATER SPRAY. KEEP UPWIND.

COMBUSTION PRODUCTS INCLUDE CORROSIVE OR TOXIC VAPORS.

WATER-SPILL:

TRAP SPILLED MATERIAL AT BOTTOM IN DEEP WATER POCKETS, EXCAVATED HOLDING AREAS OR WITHIN SAND BAG BARRIERS.

USE SUCTION HOSES TO REMOVE TRAPPED SPILL MATERIAL.

USE ACTIVATED CARBON TO ABSORB SPILLED SUBSTANCE THAT IS DISSOLVED.

USE MECHANICAL DREDGES OR LIFTS TO EXTRACT IMMOBILIZED MASSES OF POLLUTION AND PRECIPITATES.

THE CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986 (PROPOSITION 65) PROHIBITS CONTAMINATING ANY KNOWN SOURCE OF DRINKING WATER WITH SUBSTANCES KNOWN TO CAUSE CANCER AND/OR REPRODUCTIVE TOXICITY.

OCCUPATIONAL-SPILL:

DO NOT TOUCH SPILLED MATERIAL. STOP LEAK IF YOU CAN DO IT WITHOUT RISK. USE WATER SPRAY TO REDUCE VAPORS. FOR SMALL SPILLS, TAKE UP WITH SAND OR OTHER ABSORBENT MATERIAL AND PLACE INTO CONTAINERS FOR LATER DISPOSAL. FOR SMALL DRY SPILLS, WITH A CLEAN SHOVEL PLACE MATERIAL INTO CLEAN, DRY CONTAINERS AND COVER. MOVE CONTAINERS FROM SPILL AREA. FOR LARGER SPILLS, DIKE FAR AHEAD OF SPILL FOR LATER DISPOSAL. KEEP UNNECESSARY PEOPLE AWAY. ISOLATE HAZARD AREA AND DENY ENTRY. VENTILATE CLOSED SPACES BEFORE ENTERING.

REPORTABLE QUANTITY (RQ): 5000 POUNDS

THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT (SARA) SECTION 304 REQUIRES THAT A RELEASE EQUAL TO OR GREATER THAN THE REPORTABLE QUANTITY FOR THIS SUBSTANCE BE IMMEDIATELY REPORTED TO THE LOCAL EMERGENCY PLANNING COMMITTEE AND THE STATE EMERGENCY RESPONSE COMMISSION (40 CFR 355.40). IF THE RELEASE OF THIS SUBSTANCE IS REPORTABLE UNDER CERCLA SECTION 103, THE NATIONAL RESPONSE CENTER MUST BE NOTIFIED IMMEDIATELY AT (800) 424-8802 OR (202) 426-2675 IN THE METROPOLITAN WASHINGTON, D.C. AREA (40 CFR 302.6).

PROTECTIVE EQUIPMENT SECTION

VENTILATION:

PROVIDE LOCAL EXHAUST OR PROCESS ENCLOSURE VENTILATION TO MEET PUBLISHED EXPOSURE LIMITS.

RESPIRATOR:

THE FOLLOWING RESPIRATORS AND MAXIMUM USE CONCENTRATIONS ARE RECOMMENDATIONS BY THE U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES, NIOSH POCKET GUIDE TO CHEMICAL HAZARDS; NIOSH CRITERIA DOCUMENTS OR BY THE U.S. DEPARTMENT OF LABOR, 29 CFR 1910 SUBPART Z.

THE SPECIFIC RESPIRATOR SELECTED MUST BE BASED ON CONTAMINATION LEVELS FOUND IN THE WORK PLACE, MUST NOT EXCEED THE WORKING LIMITS OF THE RESPIRATOR AND BE JOINTLY APPROVED BY THE NATIONAL INSTITUTE FOR OCCUPATIONAL SAFETY AND HEALTH AND THE MINE SAFETY AND HEALTH ADMINISTRATION (NIOSH-MSHA).

CARBON TETRACHLORIDE:

AT ANY DETECTABLE CONCENTRATION:

ANY SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE AND OPERATED IN A PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.
ANY SUPPLIED-AIR RESPIRATOR WITH A FULL FACEPIECE AND OPERATED IN A PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE IN COMBINATION WITH AN AUXILIARY SELF-CONTAINED BREATHING APPARATUS OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.

ESCAPE- ANY AIR-PURIFYING FULL FACEPIECE RESPIRATOR (GAS MASK) WITH A CHIN-STYLE OR FRONT- OR BACK-MOUNTED ORGANIC VAPOR CANISTER.
ANY APPROPRIATE ESCAPE-TYPE SELF-CONTAINED BREATHING APPARATUS.

FOR FIREFIGHTING AND OTHER IMMEDIATELY DANGEROUS TO LIFE OR HEALTH CONDITIONS:

SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN
PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.

SUPPLIED-AIR RESPIRATOR WITH FULL FACEPIECE AND OPERATED IN PRESSURE-DEMAND
OR OTHER POSITIVE PRESSURE MODE IN COMBINATION WITH AN AUXILIARY
SELF-CONTAINED BREATHING APPARATUS OPERATED IN PRESSURE-DEMAND OR OTHER
POSITIVE PRESSURE MODE.

CLOTHING:

EMPLOYEE MUST WEAR APPROPRIATE PROTECTIVE (IMPERVIOUS) CLOTHING AND EQUIPMENT
TO PREVENT REPEATED OR PROLONGED SKIN CONTACT WITH THIS SUBSTANCE.

GLOVES:

EMPLOYEE MUST WEAR APPROPRIATE PROTECTIVE GLOVES TO PREVENT CONTACT WITH THIS
SUBSTANCE.

EYE PROTECTION:

EMPLOYEE MUST WEAR SPLASH-PROOF OR DUST-RESISTANT SAFETY GOGGLES TO PREVENT
EYE CONTACT WITH THIS SUBSTANCE.

EMERGENCY EYE WASH: WHERE THERE IS ANY POSSIBILITY THAT AN EMPLOYEE'S EYES MAY
BE EXPOSED TO THIS SUBSTANCE, THE EMPLOYER SHOULD PROVIDE AN EYE WASH
FOUNTAIN WITHIN THE IMMEDIATE WORK AREA FOR EMERGENCY USE.

AUTHORIZED BY- OCCUPATIONAL HEALTH SERVICES, INC.

CREATION DATE: 10/24/84

REVISION DATE: 10/10/90

OCCUPATIONAL HEALTH SERVICES, INC.
11 WEST 42ND STREET, 12TH FLOOR
NEW YORK, NEW YORK 10036
1-800-445-MSDS (1-800-445-6737) OR 1-212-789-3535

FOR EMERGENCY SOURCE INFORMATION
CONTACT: 1-615-366-2000

SUBSTANCE IDENTIFICATION

CAS-NUMBER 60-00-4
RTEC-NUMBER AH4025000

SUBSTANCE: **ETHYLENEDIAMINETETRAACETIC ACID**

TRADE NAMES/SYNONYMS:

GLYCINE, N,N'-1,2-ETHANEDIYLBIS(N-(CARBOXYMETHYL))-:
N,N'-1,2-ETHANEDIYLBIS(N-(CARBOXYMETHYL)GLYCINE: ACETIC ACID,
(ETHYLENEDINITRIL)OTETRA-: (ETHYLENEDINITRIL)OTETRAACETIC ACID: EDETIC
ACID: ~~EDTA~~ EDTA (CHELATING AGENT): ETHYLENEDINITRILOTETRAACETIC
ACID: VERSENE ACID: CHEELOX: HAVIDOTE: VERSENIC ACID: STCC
4966910: C10H16N2O8: OHS09570

CHEMICAL FAMILY:

AMINE, ALIPHATIC: CARBOXYLIC ACID

MOLECULAR FORMULA: (H-O2-C-C-H2)2-(N-C-H2)2-(C-H2-O2-H)2 MOLECULAR WEIGHT:
292.25

CERCLA RATINGS (SCALE 0-3): HEALTH=3 FIRE=1 REACTIVITY=0 PERSISTENCE=1

NFPA RATINGS (SCALE 0-4): HEALTH=U FIRE=1 REACTIVITY=0

COMPONENTS AND CONTAMINANTS

COMPONENT: ETHYLENEDIAMINETETRAACETIC ACID CAS# 60-00-4

PERCENT: 100.0

OTHER CONTAMINANTS: NONE

EXPOSURE LIMIT:

NO OCCUPATIONAL EXPOSURE LIMITS ESTABLISHED BY OSHA, ACGIH, OR NIOSH.

ETHYLENEDIAMINETETRAACETIC ACID:

5000 POUNDS CERCLA SECTION 103 REPORTABLE QUANTITY

PHYSICAL DATA

DESCRIPTION: ODORLESS, COLORLESS OR WHITE CRYSTALLINE SOLID.

MELTING POINT: 473 F (245 C)
(DECOMPOSES)

SPECIFIC GRAVITY: 0.86 @ 20 C

SOLUBILITY IN WATER: 0.05% @ 25 C

OTHER SOLVENTS (SOLVENT - SOLUBILITY):

SOLUBLE IN ALKALI HYDROXIDE SOLUTIONS; INSOLUBLE IN
COMMON ORGANIC SOLVENTS.

FIRE AND EXPLOSION DATA

FIRE AND EXPLOSION HAZARD
SLIGHT FIRE HAZARD WHEN EXPOSED TO HEAT OR FLAME.

DUST-AIR MIXTURES MAY IGNITE OR EXPLODE.

FIREFIGHTING MEDIA:

DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY OR REGULAR FOAM
(1990 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5).

FOR LARGER FIRES, USE WATER SPRAY, FOG OR REGULAR FOAM
(1990 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5).

FIREFIGHTING:

MOVE CONTAINER FROM FIRE AREA IF YOU CAN DO IT WITHOUT RISK. DO NOT SCATTER
SPILLED MATERIAL WITH HIGH-PRESSURE WATER STREAMS. DIKE FIRE-CONTROL WATER FOR
LATER DISPOSAL (1990 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5, GUIDE
PAGE 31).

USE AGENTS SUITABLE FOR TYPE OF SURROUNDING FIRE. AVOID BREATHING CORROSIVE
DUSTS OR VAPORS, KEEP UPWIND.

TOXICITY

ETHYLENEDIAMINETETRAACETIC ACID:

TOXICITY DATA: 2000 MG/KG ORAL-RAT LD50 (DPIRDU); 397 MG/KG
INTRAPERITONEAL-RAT LD50; 250 MG/KG INTRAPERITONEAL-MOUSE LD50;
MUTAGENIC DATA (RTECS); REPRODUCTIVE EFFECTS DATA (RTECS).

CARCINOGEN STATUS: NONE.

LOCAL EFFECTS: IRRITANT- INHALATION, SKIN, EYES.

ACUTE TOXICITY LEVEL: MODERATELY TOXIC BY INGESTION.

TARGET EFFECTS: POISONING MAY AFFECT THE KIDNEYS.

AT INCREASED RISK FROM EXPOSURE: PERSONS WITH RENAL OR HEART DISEASE;
A HISTORY OF SEIZURES OR INTRACRANIAL LESIONS; POTASSIUM DEFICIENCY;
OR INSULIN-DEPENDENT DIABETES.

ADDITIONAL DATA: PARENTERAL ADMINISTRATION OF EDTA OR ITS SALTS IN HIGH
DOSES MAY CAUSE SEVERE RENAL LESIONS AND TUBULAR NECROSIS, INTERNAL
HEMORRHAGE, LIFE-THREATENING HYPOCALCEMIA, AND DEATH. PROLONGED
PARENTERAL ADMINISTRATION MAY LEAD TO ELECTROLYTE IMBALANCE AND
CARDIAC ARRHYTHMIAS.

HEALTH EFFECTS AND FIRST AID

INHALATION:

ETHYLENEDIAMINETETRAACETIC ACID:
IRRITANT.

ACUTE EXPOSURE- INHALATION MAY CAUSE MUCOUS MEMBRANE IRRITATION WITH
SORE THROAT AND COUGHING.

CHRONIC EXPOSURE- NO DATA AVAILABLE.

FIRST AID- REMOVE FROM EXPOSURE AREA TO FRESH AIR IMMEDIATELY. IF BREATHING HAS STOPPED, PERFORM ARTIFICIAL RESPIRATION. KEEP PERSON WARM AND AT REST. TREAT SYMPTOMATICALLY AND SUPPORTIVELY. GET MEDICAL ATTENTION IMMEDIATELY.

SKIN CONTACT:

ETHYLENEDIAMINETETRAACETIC ACID:

IRRITANT.

ACUTE EXPOSURE- CONTACT MAY CAUSE IRRITATION WITH REDNESS AND PAIN.

CHRONIC EXPOSURE- REPEATED OR PROLONGED CONTACT WITH MOIST SKIN MAY CAUSE MODERATE IRRITATION AND POSSIBLY A MILD BURN.

FIRST AID- REMOVE CONTAMINATED CLOTHING AND SHOES IMMEDIATELY. WASH AFFECTED AREA WITH SOAP OR MILD DETERGENT AND LARGE AMOUNTS OF WATER UNTIL NO EVIDENCE OF CHEMICAL REMAINS (APPROXIMATELY 15-20 MINUTES). GET MEDICAL ATTENTION IMMEDIATELY.

EYE CONTACT:

ETHYLENEDIAMINETETRAACETIC ACID:

IRRITANT.

ACUTE EXPOSURE- CONTACT MAY CAUSE IRRITATION WITH REDNESS AND PAIN.

MAY CAUSE SOME TRANSIENT CORNEAL INJURY OR BURNS.

CHRONIC EXPOSURE- REPEATED OR PROLONGED CONTACT WITH IRRITANTS MAY CAUSE CONJUNCTIVITIS.

FIRST AID- WASH EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER OR NORMAL SALINE, OCCASIONALLY LIFTING UPPER AND LOWER LIDS, UNTIL NO EVIDENCE OF CHEMICAL REMAINS (APPROXIMATELY 15-20 MINUTES). GET MEDICAL ATTENTION IMMEDIATELY.

INGESTION:

ETHYLENEDIAMINETETRAACETIC ACID:

ACUTE EXPOSURE- ALTHOUGH POORLY ABSORBED FROM THE GASTROINTESTINAL TRACT, IF SUFFICIENT AMOUNTS ARE INGESTED SYSTEMIC TOXICITY MAY RESULT.

MAY CHELATE LEAD, MAGNESIUM, ZINC OR TRACE METALS IF THEY ARE

PRESENT IN THE INTESTINE, POSSIBLY CAUSING THEIR INCREASED

ABSORPTION AND THEREBY INCREASING TOTAL BODY STORES OF THESE METALS.

CHRONIC EXPOSURE- REPRODUCTIVE EFFECTS HAVE BEEN REPORTED IN ANIMAL STUDIES.

FIRST AID- TREAT SYMPTOMATICALLY AND SUPPORTIVELY. GET MEDICAL ATTENTION IMMEDIATELY. IF VOMITING OCCURS, KEEP HEAD LOWER THAN HIPS TO PREVENT ASPIRATION.

ANTIDOTE:

NO SPECIFIC ANTIDOTE. TREAT SYMPTOMATICALLY AND SUPPORTIVELY.

REACTIVITY SECTION

REACTIVITY:

STABLE UNDER NORMAL TEMPERATURES AND PRESSURES.

INCOMPATIBILITIES:

ETHYLENEDIAMINETETRAACETIC ACID:

ALUMINUM: LIBERATES FLAMMABLE HYDROGEN GAS.

COPPER AND ALLOYS: MAY CORRODE.

NICKEL: MAY CORRODE.

OXIDIZERS (STRONG): FIRE AND EXPLOSION HAZARD.

DECOMPOSITION:
THERMAL DECOMPOSITION PRODUCTS MAY INCLUDE TOXIC OXIDES OF CARBON AND NITROGEN.

POLYMERIZATION:
HAZARDOUS POLYMERIZATION HAS NOT BEEN REPORTED TO OCCUR UNDER NORMAL TEMPERATURES AND PRESSURES.

STORAGE-DISPOSAL

OBSERVE ALL FEDERAL, STATE AND LOCAL REGULATIONS WHEN STORING OR DISPOSING OF THIS SUBSTANCE. FOR ASSISTANCE, CONTACT THE DISTRICT DIRECTOR OF THE ENVIRONMENTAL PROTECTION AGENCY.

STORAGE

STORE AWAY FROM INCOMPATIBLE SUBSTANCES.

STORE IN A COOL, DRY PLACE; KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE.

CONDITIONS TO AVOID

MAY BURN BUT DOES NOT IGNITE READILY. AVOID CONTACT WITH STRONG OXIDIZERS, EXCESSIVE HEAT, SPARKS, OR OPEN FLAME.

SPILLS AND LEAKS

SOIL-RELEASE:
DIG A PIT, POND, LAGOON OR HOLDING AREA TO CONTAIN LIQUID OR SOLID MATERIAL. COVER SOLIDS WITH A PLASTIC SHEET TO PREVENT DISSOLVING IN RAIN OR FIREFIGHTING WATER.

WATER-SPILL:
NEUTRALIZE WITH CAUSTIC SODA.

ADD SUITABLE AGENT TO NEUTRALIZE SPILLED MATERIAL TO PH-7.

USE MECHANICAL DREDGES OR LIFTS TO EXTRACT IMMOBILIZED MASSES OF POLLUTION AND PRECIPITATES.

OCCUPATIONAL-SPILL:
SWEEP UP AND PLACE IN SUITABLE CLEAN, DRY CONTAINERS FOR RECLAMATION OR LATER DISPOSAL. DO NOT FLUSH SPILLED MATERIAL INTO SEWER. KEEP UNNECESSARY PEOPLE AWAY.

REPORTABLE QUANTITY (RQ): 5000 POUNDS
THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT (SARA) SECTION 304 REQUIRES THAT A RELEASE EQUAL TO OR GREATER THAN THE REPORTABLE QUANTITY FOR THIS

SUBSTANCE BE IMMEDIATELY REPORTED TO THE LOCAL EMERGENCY PLANNING COMMITTEE AND THE STATE EMERGENCY RESPONSE COMMISSION (40 CFR 355.40). IF THE RELEASE OF THIS SUBSTANCE IS REPORTABLE UNDER CERCLA SECTION 103, THE NATIONAL RESPONSE CENTER MUST BE NOTIFIED IMMEDIATELY AT (800) 424-8802 OR (202) 426-2675 IN THE METROPOLITAN WASHINGTON, D.C. AREA (40 CFR 302.6).

PROTECTIVE EQUIPMENT SECTION

VENTILATION:

PROVIDE LOCAL EXHAUST OR GENERAL DILUTION VENTILATION SYSTEM.

RESPIRATOR:

THE FOLLOWING RESPIRATORS ARE RECOMMENDED BASED ON INFORMATION FOUND IN THE PHYSICAL DATA, TOXICITY AND HEALTH EFFECTS SECTIONS. THEY ARE RANKED IN ORDER FROM MINIMUM TO MAXIMUM RESPIRATORY PROTECTION.

THE SPECIFIC RESPIRATOR SELECTED MUST BE BASED ON CONTAMINATION LEVELS FOUND IN THE WORK PLACE, MUST NOT EXCEED THE WORKING LIMITS OF THE RESPIRATOR AND BE JOINTLY APPROVED BY THE NATIONAL INSTITUTE FOR OCCUPATIONAL SAFETY AND HEALTH AND THE MINE SAFETY AND HEALTH ADMINISTRATION (NIOSH-MSHA).

CHEMICAL CARTRIDGE RESPIRATOR WITH FULL FACEPIECE AND ORGANIC VAPOR CARTRIDGE(S) IN COMBINATION WITH A DUST AND MIST FILTER.

CHEMICAL CARTRIDGE RESPIRATOR WITH FULL FACEPIECE AND ORGANIC VAPOR CARTRIDGE(S) IN COMBINATION WITH A HIGH-EFFICIENCY PARTICULATE FILTER.

GAS MASK WITH ORGANIC VAPOR CANISTER (CHIN-STYLE OR FRONT- OR BACK-MOUNTED CANISTER) WITH A FULL FACEPIECE AND A HIGH-EFFICIENCY PARTICULATE FILTER.

POWERED AIR-PURIFYING RESPIRATOR WITH TIGHT-FITTING FACEPIECE AND ORGANIC VAPOR CARTRIDGE(S) IN COMBINATION WITH A HIGH-EFFICIENCY PARTICULATE FILTER.

TYPE 'C' SUPPLIED-AIR RESPIRATOR WITH A FULL FACEPIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE OR WITH A FULL FACEPIECE, HELMET OR HOOD OPERATED IN CONTINUOUS-FLOW MODE.

SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.

FOR FIREFIGHTING AND OTHER IMMEDIATELY DANGEROUS TO LIFE OR HEALTH CONDITIONS:

SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.

SUPPLIED-AIR RESPIRATOR WITH FULL FACEPIECE AND OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE IN COMBINATION WITH AN AUXILIARY SELF-CONTAINED BREATHING APPARATUS OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.

CLOTHING:

EMPLOYEE MUST WEAR APPROPRIATE PROTECTIVE (IMPERVIOUS) CLOTHING AND EQUIPMENT TO PREVENT REPEATED OR PROLONGED SKIN CONTACT WITH THIS SUBSTANCE.

GLOVES:

EMPLOYEE MUST WEAR APPROPRIATE PROTECTIVE GLOVES TO PREVENT CONTACT WITH THIS

SUBSTANCE.

EYE PROTECTION:

EMPLOYEE MUST WEAR SPLASH-PROOF OR DUST-RESISTANT SAFETY GOGGLES TO PREVENT EYE CONTACT WITH THIS SUBSTANCE.

EMERGENCY EYE WASH: WHERE THERE IS ANY POSSIBILITY THAT AN EMPLOYEE'S EYES MAY BE EXPOSED TO THIS SUBSTANCE, THE EMPLOYER SHOULD PROVIDE AN EYE WASH FOUNTAIN WITHIN THE IMMEDIATE WORK AREA FOR EMERGENCY USE.

AUTHORIZED BY- OCCUPATIONAL HEALTH SERVICES, INC.

CREATION DATE: 01/23/85

REVISION DATE: 10/09/90

MATERIAL SAFETY DATA SHEET

OHS12090

OCCUPATIONAL HEALTH SERVICES, INC.

11 WEST 42ND STREET, 12TH FLOOR

NEW YORK, NEW YORK 10036

1-800-445-MSDS (1-800-445-6737) OR 1-212-789-3535

FOR EMERGENCY SOURCE INFORMATION

CONTACT: 1-615-366-2000

SUBSTANCE IDENTIFICATION

CAS-NUMBER 67-63-0

RTEC-NUMBER NT8050000

SUBSTANCE: ISOPROPYL ALCOHOL

TRADE NAMES/SYNONYMS:

ISOPROPANOL; ETHYL CARBINOL; DIMETHYLCARBINOL; 2-PROPANOL; ISOHOL;
SEC-PROPYL ALCOHOL; PROPYL ALCOHOL; XEROX FILM REMOVER (UNION CARBIDE);
CTL R-53 REDUCER (CHEMICAL TECHNOLOGY LABS., INC.); TEXPADS (THE TEXWIPE
COMPANY); CORONA WIRE CLEANER (CANON BUSINESS MACHINES); DISK DRIVE
HEAD CLEANING KIT (DIGITAL EQUIPMENT CORPORATION); LENS CLENS #3 (GENERAL
PRODUCTION SERVICES INC.); REDUCER (SHERWIN-WILLIAMS); ISOPROPYL ALC
SEMI GO 4X1GPOLY (ASHLAND CHEMICAL COMPANY); ADPRO-MULTISURF
(MALLINCKRODT); 108 THINNER (KESTER SOLDER COMPANY); STCC 4904205; UN
1219; C3H8O; OHS12090

CHEMICAL FAMILY:

ALCOHOL, ALIPHATIC

MOLECULAR FORMULA: C-H3-C-H-(O-H)-C-H3 MOLECULAR WEIGHT: 60.10

CERCLA RATINGS (SCALE 0-3): HEALTH=2 FIRE=3 REACTIVITY=0 PERSISTENCE=0

NFPA RATINGS (SCALE 0-4): HEALTH=1 FIRE=3 REACTIVITY=0

COMPONENTS AND CONTAMINANTS

COMPONENT: ISOPROPYL ALCOHOL (ISOPROPANOL) CAS# 67-63-0

PERCENT: 100.0

OTHER CONTAMINANTS: NONE

EXPOSURE LIMIT:

ISOPROPYL ALCOHOL (ISOPROPANOL; 2-PROPANOL):

400 PPM (980 MG/M3) OSHA TWA; 500 PPM (1225 MG/M3) OSHA STEL

400 PPM (980 MG/M3) ACGIH TWA; 500 PPM (1225 MG/M3) ACGIH STEL

400 PPM NIOSH RECOMMENDED 10 HOUR TWA;

800 PPM NIOSH RECOMMENDED 15 MINUTE CEILING

SUBJECT TO SARA SECTION 313 ANNUAL TOXIC CHEMICAL RELEASE REPORTING

PHYSICAL DATA

DESCRIPTION: COLORLESS LIQUID WITH AN ODOR OF ALCOHOL.

BOILING POINT: 180 F (82 C)

MELTING POINT: -129 F (-89 C)

SPECIFIC GRAVITY: 0.7855

EVAPORATION RATE: (BUTYL ACETATE=1)

VOLATILITY: 100%

SOLUBILITY IN WATER: SOLUBLE

VAPOR DENSITY: 2.1

VAPOR PRESSURE: 40 MMHG @ 24 C

ODOR-THRESHOLD: 40-45 PPM

OTHER SOLVENTS (SOLVENT - SOLUBILITY):
SOLUBLE IN ALCOHOL, ETHER, CHLOROFORM, ACETONE,
BENZENE; INSOLUBLE IN SALT SOLUTIONS.

OTHER PHYSICAL DATA

VISCOSITY: 2.1 CPS @ 25 C

FIRE AND EXPLOSION DATA

FIRE AND EXPLOSION HAZARD

DANGEROUS FIRE HAZARD WHEN EXPOSED TO HEAT OR FLAME.

VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL A CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK.

VAPOR-AIR MIXTURES ARE EXPLOSIVE.

FLASH POINT: 53 F (12 C) (CC)

UPPER EXPLOSION LIMIT: 12.7% @ 93 C

LOWER EXPLOSION LIMIT: 2.0%

AUTOIGNITION TEMP.: 750 F (399 C)

FLAMMABILITY CLASS (OSHA): IB

FIREFIGHTING MEDIA:

DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY OR ALCOHOL-RESISTANT FOAM
(1990 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5).FOR LARGER FIRES, USE WATER SPRAY, FOG OR ALCOHOL-RESISTANT FOAM
(1990 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5).

ALCOHOL FOAM

(NFPA 325M, FIRE HAZARD PROPERTIES OF FLAMMABLE LIQUIDS, GASES, AND VOLATILE SOLIDS, 1984).

FIREFIGHTING:

MOVE CONTAINER FROM FIRE AREA IF YOU CAN DO IT WITHOUT RISK. APPLY COOLING WATER TO SIDES OF CONTAINERS THAT ARE EXPOSED TO FLAMES UNTIL WELL AFTER FIRE IS OUT. STAY AWAY FROM ENDS OF TANKS. FOR MASSIVE FIRE IN CARGO AREA, USE UNMANNED HOSE HOLDER OR MONITOR NOZZLES; IF THIS IS IMPOSSIBLE, WITHDRAW FROM AREA AND LET FIRE BURN. WITHDRAW IMMEDIATELY IN CASE OF RISING SOUND FROM VENTING SAFETY DEVICE OR ANY DISCOLORATION OF TANK DUE TO FIRE. ISOLATE FOR 1/2 MILE IN ALL DIRECTIONS IF TANK, RAIL CAR OR TANK TRUCK IS INVOLVED IN FIRE (1990 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5, GUIDE PAGE 26).

EXTINGUISH ONLY IF FLOW CAN BE STOPPED; USE WATER IN FLOODING AMOUNTS AS FOG, SOLID STREAMS MAY NOT BE EFFECTIVE. COOL CONTAINERS WITH FLOODING AMOUNTS OF WATER, APPLY FROM AS FAR A DISTANCE AS POSSIBLE. AVOID BREATHING VAPORS, KEEP UPWIND.

WATER MAY BE INEFFECTIVE (NFPA 325M, FIRE HAZARD PROPERTIES OF FLAMMABLE LIQUIDS, GASES, AND VOLATILE SOLIDS, 1984)

TRANSPORTATION

DEPARTMENT OF TRANSPORTATION HAZARD CLASSIFICATION 49 CFR 172.101:
FLAMMABLE LIQUID

DEPARTMENT OF TRANSPORTATION LABELING REQUIREMENTS 49 CFR 172.101 AND
SUBPART E:
FLAMMABLE LIQUID

DEPARTMENT OF TRANSPORTATION PACKAGING REQUIREMENTS: 49 CFR 173.125
EXCEPTIONS: 49 CFR 173.118

TOXICITY

ISOPROPYL ALCOHOL (ISOPROPANOL; 2-PROPANOL):
IRRITATION DATA: 500 MG SKIN-RABBIT MILD; 16 MG EYE-RABBIT; 10 MG
EYE-RABBIT MODERATE; 100 MG/24 HOURS EYE-RABBIT MODERATE.
TOXICITY DATA: 12,800 PPM/3 HOURS INHALATION-MOUSE LCLO; 16,000 PPM/4 HOURS
INHALATION-RAT LCLO; 12,800 MG/KG SKIN-RABBIT LD50; 5272 MG/KG ORAL-MAN
LDLO; 14,432 MG/KG ORAL-MAN TDLO; 3570 MG/KG ORAL-HUMAN LDLO; 223 MG/KG
ORAL-HUMAN TDLO; 5045 MG/KG ORAL-RAT LD50; 3600 MG/KG ORAL-MOUSE LD50;
6410 MG/KG ORAL-RABBIT LD50; 4797 MG/KG ORAL-DOG LD50;
5000 MG/KG SUBCUTANEOUS-MOUSE LDLO; 6 MG/KG SUBCUTANEOUS-MAMMAL LDLO;
1088 MG/KG INTRAVENOUS-RAT LD50; 1509 MG/KG INTRAVENOUS-MOUSE LD50;
1184 MG/KG INTRAVENOUS-RABBIT LD50; 1963 MG/KG INTRAVENOUS-CAT LDLO;
5120 MG/KG INTRAVENOUS-DOG LDLO; 2735 MG/KG INTRAPERITONEAL-RAT LD50;
4477 MG/KG INTRAPERITONEAL-MOUSE LD50; 667 MG/KG INTRAPERITONEAL-RABBIT
LD50; MUTAGENIC DATA (RTECS); REPRODUCTIVE EFFECTS DATA (RTECS).
CARCINOGEN STATUS: HUMAN INADEQUATE EVIDENCE, ANIMAL INADEQUATE EVIDENCE
(IARC GROUP-3). STRONG ACID MANUFACTURING PROCESS: KNOWN HUMAN CARCINOGEN
(NTP); HUMAN SUFFICIENT EVIDENCE (IARC GROUP-1). WORKERS INVOLVED IN THE
MANUFACTURE OF ISOPROPYL ALCOHOL BY THE STRONG-ACID PROCESS, INVOLVING THE
FORMATION OF ISOPROPYL OILS, SHOWED AN INCREASE IN PARANASAL AND LARYNGEAL
CANCERS.
LOCAL EFFECTS: IRRITANT- INHALATION, EYE.
ACUTE TOXICITY LEVEL: SLIGHTLY TOXIC BY INGESTION, DERMAL ABSORPTION.
TARGET EFFECTS: CENTRAL NERVOUS SYSTEM DEPRESSANT.
AT INCREASED RISK FROM EXPOSURE: PERSONS WITH PRE-EXISTING SKIN DISORDERS;
IMPAIRED LIVER, RENAL AND/OR PULMONARY FUNCTION.
ADDITIONAL INFORMATION: POTENTIATES THE EFFECT OF CARBON TETRACHLORIDE AND
OTHER HEPATOTOXIC CHLORINATED ALIPHATIC HYDROCARBONS.

HEALTH EFFECTS AND FIRST AID

INHALATION:
ISOPROPYL ALCOHOL (ISOPROPANOL; 2-PROPANOL):
IRRITANT/NARCOTIC. 12,000 PPM IMMEDIATELY DANGEROUS TO LIFE OR HEALTH.

ACUTE EXPOSURE- HUMAN SUBJECTS EXPOSED TO 400 PPM FOR 3-5 MINUTES HAD MILD IRRITATION OF THE NOSE AND THROAT. AT 800 PPM THE IRRITATION WAS NOT SEVERE BUT UNCOMFORTABLE. HIGHER CONCENTRATIONS MAY CAUSE EFFECTS AS DETAILED IN ACUTE INGESTION. THE LENGTH OF TIME REQUIRED TO PRODUCE DEEP NARCOSIS IN ANIMALS WAS INVERSELY PROPORTIONAL TO THE CONCENTRATION: THE ONSET OF DEEP NARCOSIS RANGED FROM 460 MINUTES AT 3250 PPM TO 100 MINUTES AT 24,500 PPM.

CHRONIC EXPOSURE- MICE SUBJECTED TO 10900 PPM ISOPROPYL ALCOHOL IN AIR FOR ABOUT 4 HOURS/DAY UNTIL THEY HAD ACCUMULATED 123 HOURS OF EXPOSURE WERE NARCOTIZED BUT SURVIVED. REVERSIBLE FATTY CHANGES WERE OBSERVED IN THE LIVER. MALE MICE EXPOSED TO EITHER 1000 OR 5000 PPM OF ISOPROPYL ALCOHOL VAPOR FOR 6 HOURS A DAY FOR 9 EXPOSURES EXHIBITED HYALINE DROPLET NEPHROPATHY. REPRODUCTIVE EFFECTS HAVE BEEN REPORTED IN ANIMALS. THERE HAS BEEN AN INCREASED INCIDENCE OF CANCER OF THE PARANASAL SINUSES, AND POSSIBLY OF THE LARYNX, IN THE MANUFACTURE OF ISOPROPYL ALCOHOL BY THE STRONG ACID PROCESS, INVOLVING THE FORMATION OF ISOPROPYL OILS. IT IS NOT CLEAR WHICH SUBSTANCES ARE RESPONSIBLE.

FIRST AID- REMOVE FROM EXPOSURE AREA TO FRESH AIR IMMEDIATELY. IF BREATHING HAS STOPPED, PERFORM ARTIFICIAL RESPIRATION. KEEP PERSON WARM AND AT REST. TREAT SYMPTOMATICALLY AND SUPPORTIVELY. GET MEDICAL ATTENTION IMMEDIATELY.

SKIN CONTACT:

ISOPROPYL ALCOHOL (ISOPROPANOL; 2-PROPANOL):
NARCOTIC.

ACUTE EXPOSURE- CONTACT WITH THE SKIN MAY CAUSE SLIGHT IRRITATION. CONTACT DERMATITIS HAS BEEN REPORTED IN A FEW SENSITIVE INDIVIDUALS. SUBSTANCE MAY BE DERMALLY ABSORBED RESULTING IN SYSTEMIC TOXICITY AS DETAILED IN ACUTE INGESTION. TOXIC EFFECTS MAY BECOME MORE MARKED IF ABSORPTION AND INHALATION OCCUR CONCURRENTLY.

CHRONIC EXPOSURE- REPEATED OR PROLONGED EXPOSURE MAY CAUSE DERMATITIS DUE TO THE DEFATTING ACTION ON THE SKIN. REPEATED AND PROLONGED EXPOSURE TO THE SKIN OF RABBITS CAUSED SLIGHT ERYTHEMA, DRYING, AND SUPERFICIAL DESQUAMATION.

FIRST AID- REMOVE CONTAMINATED CLOTHING AND SHOES IMMEDIATELY. WASH AFFECTED AREA WITH SOAP OR MILD DETERGENT AND LARGE AMOUNTS OF WATER UNTIL NO EVIDENCE OF CHEMICAL REMAINS (APPROXIMATELY 15-20 MINUTES). GET MEDICAL ATTENTION IMMEDIATELY.

EYE CONTACT:

ISOPROPYL ALCOHOL (ISOPROPANOL; 2-PROPANOL):
IRRITANT.

ACUTE EXPOSURE- 400-800 PPM MAY CAUSE IRRITATION. IN RABBIT EYES, A DROP CAUSED MILD TRANSITORY INJURY AND A 50% AQUEOUS SOLUTION AFTER 3 MINUTES CAUSED MODERATE IRRITATION. CONTACT WITH A 70% SOLUTION CAUSED CONJUNCTIVITIS, IRITIS, AND CORNEAL OPACITY.

CHRONIC EXPOSURE- PROLONGED OR REPEATED EXPOSURE TO VAPORS MAY CAUSE CONJUNCTIVITIS.

FIRST AID- WASH EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER OR NORMAL SALINE, OCCASIONALLY LIFTING UPPER AND LOWER LIDS, UNTIL NO EVIDENCE OF CHEMICAL REMAINS (APPROXIMATELY 15-20 MINUTES). GET MEDICAL ATTENTION IMMEDIATELY.

INGESTION:

ISOPROPYL ALCOHOL (ISOPROPANOL; 2-PROPANOL):
NARCOTIC.

ACUTE EXPOSURE- INGESTION MAY CAUSE ABDOMINAL PAIN, HEMATEMESIS, NAUSEA, VOMITING, AND HEMORRHAGE. CENTRAL NERVOUS SYSTEM DEPRESSION MAY OCCUR WITH

HEADACHE, DIZZINESS, FLUSHING, INCOORDINATION, STUPOR, CONFUSION, HYPOTENSION, AREFLEXIA, AND REFRACTORY NARCOSIS. OLIGURIA FOLLOWED BY DIURESIS AND COMA MAY ALSO OCCUR. OTHER SYMPTOMS MAY INCLUDE HYPOGLYCEMIA, TENDERNESS AND EDEMA OF MUSCLES, AND ARRHYTHMIAS. VOMITING WITH ASPIRATION MAY CAUSE ASPIRATION PNEUMONIA. DEPRESSED RESPIRATION AND DEATH DUE TO RESPIRATORY PARALYSIS MAY OCCUR IN A FEW HOURS AFTER EXPOSURE. SEVERE AND PROLONGED SHOCK MAY LEAD TO SERIOUS OR FATAL RENAL DAMAGE AFTER SEVERAL DAYS. PATHOLOGIC FINDINGS HAVE INCLUDED EXTENSIVE HEMORRHAGIC TRACHEOBRONCHITIS, BRONCHOPNEUMONIA AND HEMORRHAGIC PULMONARY EDEMA.

CHRONIC EXPOSURE- NO ADVERSE EFFECTS RESULTED IN HUMANS FOLLOWING DAILY INGESTION OF 2.6 AND 6.4 MG/KG FOR 6 WEEKS. RATS THAT INGESTED 0.5 TO 10.0% ISOPROPYL ALCOHOL IN DRINKING WATER FOR 27 WEEKS SHOWED DECREASED BODY WEIGHT. PROLONGED ORAL ADMINISTRATION IN RABBITS PRODUCED ANESTHESIA AND DEATH. REPRODUCTIVE EFFECTS HAVE BEEN REPORTED IN ANIMALS.

FIRST AID- IN RESPIRATORY DEPRESSION, GIVE OXYGEN BY ARTIFICIAL RESPIRATION. GIVE ACTIVATED CHARCOAL. GASTRIC LAVAGE WITH PROTECTED AIRWAY IS USEFUL EVEN IF DELAYED. DO NOT ATTEMPT EMESIS IF RESPIRATION IS DEPRESSED. MAINTAIN BLOOD PRESSURE. TREATMENT SHOULD BE ADMINISTERED BY QUALIFIED MEDICAL PERSONNEL. (DREISBACH, HANDBOOK OF POISONING, 12TH ED.) GET MEDICAL ATTENTION.

ANTIDOTE:

NO SPECIFIC ANTIDOTE. TREAT SYMPTOMATICALLY AND SUPPORTIVELY.

REACTIVITY SECTION

REACTIVITY:

ISOPROPYL ALCOHOL (ISOPROPANOL; 2-PROPANOL):

STABLE UNDER NORMAL TEMPERATURES AND PRESSURES. MAY SLOWLY PEROXIDISE ON EXPOSURE TO AIR UNDER NORMAL STORAGE CONDITIONS. AN EXPLOSION HAZARD MAY EXIST IF THE SUBSTANCE IS DISTILLED OR ALLOWED TO EVAPORATE TO DRYNESS.

INCOMPATIBILITIES:

ISOPROPYL ALCOHOL (ISOPROPANOL; 2-PROPANOL):

ALUMINUM: DISSOLUTION IS EXOTHERMIC.

BARIUM PERCHLORATE: FORMATION OF EXPLOSIVE COMPOUND.

2-BUTANONE (METHYL ETHYL KETONE): ACCELERATES THE PEROXIDATION OF THE ALCOHOL.

CHROMIUM TRIOXIDE (GRANULAR): IGNITION.

COATINGS: MAY BE ATTACKED.

DIOXYGENYL TETRAFLUOROBORATE: IGNITION AT AMBIENT TEMPERATURES.

HYDROGEN + PALLADIUM (PARTICLES): IGNITION ON EXPOSURE TO AIR.

HYDROGEN PEROXIDE: FORMATION OF EXPLOSIVE COMPOUND.

KETONES: MARKEDLY INCREASES THE POSSIBILITY OF PEROXIDATION.

NITROFORM (TRINITROMETHANE): DISSOLVES LIBERATING HEAT AND POSSIBLY EXPLODING.

OLEUM: TEMPERATURE AND PRESSURE INCREASE IN CLOSED CONTAINER.

OXIDIZERS (STRONG): FIRE AND EXPLOSION HAZARD.

OXYGEN (GAS): AUTOXIDATION, ON EXPOSURE TO LIGHT, RESULTS IN FORMATION OF KETONES AND POTENTIALLY EXPLOSIVE HYDROGEN PEROXIDE.

PHOSGENE: IN THE PRESENCE OF IRON SALTS, MAY EXPLODE.

PLASTICS: MAY BE ATTACKED.

POTASSIUM TERT-BUTOXIDE: IGNITION.

RUBBER: MAY BE ATTACKED.

SODIUM DICHROMATE + SULFURIC ACID: EXOTHERMIC REACTION WITH POSSIBLE

INCANDESCENCE.
SEE ALSO ALCOHOLS.

ALCOHOLS:

ACETALDEHYDE: VIOLENT CONDENSATION REACTION.
BARIUM PERCHLORATE: FORMATION OF HIGHLY EXPLOSIVE PERCHLORIC ESTER ON REFLUXING.
CHLORINE: FORMATION OF HIGHLY EXPLOSIVE ALKYL HYPOCHLORITES.
DIETHYL ALUMINUM BROMIDE: SPONTANEOUS IGNITION.
ETHYLENE OXIDE: POSSIBLE EXPLOSION.
HEXAMETHYLENE DIISOCYANATE: POSSIBLE EXPLOSION IN ABSENCE OF SOLVENT.
HYDROGEN PEROXIDE + SULFURIC ACID: POSSIBLE EXPLOSION.
HYPOCHLOROUS ACID: FORMATION OF HIGHLY EXPLOSIVE ALKYL HYPOCHLORITES.
ISOCYANATES: POSSIBLE EXPLOSION IN ABSENCE OF SOLVENT.
LITHIUM ALUMINUM HYDRIDE: VIGOROUS REACTION.
NITROGEN TETROXIDE: POSSIBLE EXPLOSION.
PERCHLORIC ACID (HOT): DANGEROUS INTERACTION.
PERMONOSULFURIC ACID: POSSIBLE EXPLOSION ON CONTACT WITH PRIMARY OR SECONDARY ALCOHOLS.
TRI-ISO-BUTYL ALUMINUM: VIOLENT REACTION.

DECOMPOSITION:

THERMAL DECOMPOSITION PRODUCTS MAY INCLUDE TOXIC OXIDES OF CARBON.

POLYMERIZATION:

HAZARDOUS POLYMERIZATION HAS NOT BEEN REPORTED TO OCCUR UNDER NORMAL TEMPERATURES AND PRESSURES.

STORAGE-DISPOSAL

OBSERVE ALL FEDERAL, STATE AND LOCAL REGULATIONS WHEN STORING OR DISPOSING OF THIS SUBSTANCE. FOR ASSISTANCE, CONTACT THE DISTRICT DIRECTOR OF THE ENVIRONMENTAL PROTECTION AGENCY.

****STORAGE****

STORE IN ACCORDANCE WITH 29 CFR 1910.106.

BONDING AND GROUNDING: SUBSTANCES WITH LOW ELECTROCONDUCTIVITY, WHICH MAY BE IGNITED BY ELECTROSTATIC SPARKS, SHOULD BE STORED IN CONTAINERS WHICH MEET THE BONDING AND GROUNDING GUIDELINES SPECIFIED IN NFPA 77-1983, RECOMMENDED PRACTICE ON STATIC ELECTRICITY.

STORE AWAY FROM INCOMPATIBLE SUBSTANCES.

****DISPOSAL****

DISPOSAL MUST BE IN ACCORDANCE WITH STANDARDS APPLICABLE TO GENERATORS OF HAZARDOUS WASTE, 40 CFR 262. EPA HAZARDOUS WASTE NUMBER D001.
100 POUND CERCLA SECTION 103 REPORTABLE QUANTITY.

CONDITIONS TO AVOID

AVOID CONTACT WITH HEAT, SPARKS, FLAMES, OR OTHER SOURCES OF IGNITION. VAPORS MAY BE EXPLOSIVE AND POISONOUS; DO NOT ALLOW UNNECESSARY PERSONNEL IN AREA. DO NOT OVERHEAT CONTAINERS; CONTAINERS MAY VIOLENTLY RUPTURE AND TRAVEL A CONSIDERABLE DISTANCE IN HEAT OF FIRE.

SPILLS AND LEAKS

OCCUPATIONAL-SPILL:

SHUT OFF IGNITION SOURCES. STOP LEAK IF YOU CAN DO IT WITHOUT RISK. USE WATER SPRAY TO REDUCE VAPORS. FOR SMALL SPILLS, TAKE UP WITH SAND OR OTHER ABSORBENT MATERIAL AND PLACE INTO CONTAINERS FOR LATER DISPOSAL. FOR LARGER SPILLS, DIKE FAR AHEAD OF SPILL FOR LATER DISPOSAL. NO SMOKING, FLAMES OR FLARES IN HAZARD AREA. KEEP UNNECESSARY PEOPLE AWAY; ISOLATE HAZARD AREA AND DENY ENTRY.

PROTECTIVE EQUIPMENT SECTION

VENTILATION:

PROVIDE LOCAL EXHAUST OR GENERAL DILUTION VENTILATION TO MEET PUBLISHED EXPOSURE LIMITS. VENTILATION EQUIPMENT MUST BE EXPLOSION-PROOF.

RESPIRATOR:

THE FOLLOWING RESPIRATORS AND MAXIMUM USE CONCENTRATIONS ARE RECOMMENDATIONS BY THE U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES, NIOSH POCKET GUIDE TO CHEMICAL HAZARDS; NIOSH CRITERIA DOCUMENTS OR BY THE U.S. DEPARTMENT OF LABOR, 29 CFR 1910 SUBPART Z.

THE SPECIFIC RESPIRATOR SELECTED MUST BE BASED ON CONTAMINATION LEVELS FOUND IN THE WORK PLACE, MUST NOT EXCEED THE WORKING LIMITS OF THE RESPIRATOR AND BE JOINTLY APPROVED BY THE NATIONAL INSTITUTE FOR OCCUPATIONAL SAFETY AND HEALTH AND THE MINE SAFETY AND HEALTH ADMINISTRATION (NIOSH-MSHA).

ISOPROPYL ALCOHOL:

1000 PPM- ANY POWERED AIR-PURIFYING RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE(S).

ANY CHEMICAL CARTRIDGE RESPIRATOR WITH A FULL FACEPIECE AND ORGANIC VAPOR CARTRIDGE(S).

10,000 PPM- ANY SUPPLIED-AIR RESPIRATOR OPERATED IN A CONTINUOUS FLOW MODE.

12,000 PPM- ANY AIR-PURIFYING FULL FACEPIECE RESPIRATOR (GAS MASK) WITH A CHIN-STYLE OR FRONT- OR BACK-MOUNTED ORGANIC VAPOR CANISTER.
ANY SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE.
ANY SUPPLIED-AIR RESPIRATOR WITH A FULL FACEPIECE.

ESCAPE- ANY AIR-PURIFYING FULL FACEPIECE RESPIRATOR (GAS MASK) WITH A CHIN-STYLE OR FRONT- OR BACK-MOUNTED ORGANIC VAPOR CANISTER.
ANY APPROPRIATE ESCAPE-TYPE SELF-CONTAINED BREATHING APPARATUS.

FOR FIREFIGHTING AND OTHER IMMEDIATELY DANGEROUS TO LIFE OR HEALTH CONDITIONS:

SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN

PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.

SUPPLIED-AIR RESPIRATOR WITH FULL FACEPIECE AND OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE IN COMBINATION WITH AN AUXILIARY SELF-CONTAINED BREATHING APPARATUS OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.

CLOTHING:

EMPLOYEE MUST WEAR APPROPRIATE PROTECTIVE (IMPERVIOUS) CLOTHING AND EQUIPMENT TO PREVENT REPEATED OR PROLONGED SKIN CONTACT WITH THIS SUBSTANCE.

GLOVES:

EMPLOYEE MUST WEAR APPROPRIATE PROTECTIVE GLOVES TO PREVENT CONTACT WITH THIS SUBSTANCE.

EYE PROTECTION:

EMPLOYEE MUST WEAR SPLASH-PROOF OR DUST-RESISTANT SAFETY GOGGLES TO PREVENT EYE CONTACT WITH THIS SUBSTANCE.

EMERGENCY EYE WASH: WHERE THERE IS ANY POSSIBILITY THAT AN EMPLOYEE'S EYES MAY BE EXPOSED TO THIS SUBSTANCE, THE EMPLOYER SHOULD PROVIDE AN EYE WASH FOUNTAIN WITHIN THE IMMEDIATE WORK AREA FOR EMERGENCY USE.

AUTHORIZED BY- OCCUPATIONAL HEALTH SERVICES, INC.

CREATION DATE: 02/26/85

REVISION DATE: 10/09/90

MATERIAL SAFETY DATA SHEET

OHS00120

OCCUPATIONAL HEALTH SERVICES, INC.
11 WEST 42ND STREET, 12TH FLOOR
NEW YORK, NEW YORK 10036
1-800-445-MSDS (1-800-445-6737) OR 1-212-789-3535

FOR EMERGENCY SOURCE INFORMATION
CONTACT: 1-615-366-2000

SUBSTANCE IDENTIFICATION

SUBSTANCE: **ACETIC ACID** GLACIAL

CAS-NUMBER 64-19-7
RTEC-NUMBER AF1340000

TRADE NAMES/SYNONYMS:

ACETIC ACID GLACIAL ACETIC ACID: ETHANOIC ACID: VINEGAR ACID:
ETHYLIC ACID: PYROLIGNEOUS ACID: METHANECARBOXYLIC ACID: STCC 4931303:
UN 2789: C2H4O2: OHS00120

CHEMICAL FAMILY:

CARBOXYLIC ACID, ALIPHATIC

MOLECULAR FORMULA: C-H3-C-O2-H MOLECULAR WEIGHT: 60.05

CERCLA RATINGS (SCALE 0-3): HEALTH=2 FIRE=2 REACTIVITY=1 PERSISTENCE=0
NFPA RATINGS (SCALE 0-4): HEALTH=2 FIRE=2 REACTIVITY=1

COMPONENTS AND CONTAMINANTS

COMPONENT: ACETIC ACID, GLACIAL CAS# 64-19-7

PERCENT: 100

OTHER CONTAMINANTS: NONE

EXPOSURE LIMIT:

ACETIC ACID, GLACIAL:

10 PPM (25 MG/M3) OSHA TWA

10 PPM (25 MG/M3) ACGIH TWA; 15 PPM (37 MG/M3) ACGIH STEL

5000 POUNDS CERCLA SECTION 103 REPORTABLE QUANTITY

PHYSICAL DATA

DESCRIPTION: CLEAR, COLORLESS LIQUID WITH A STRONG, PUNGENT, CHARACTERISTIC
ODOR OF VINEGAR AND WHEN WELL DILUTED WITH WATER, AN ACID TASTE.

BOILING POINT: 244 F (118 C)

MELTING POINT: 62 F (17 C)

SPECIFIC GRAVITY: 1.0492

EVAPORATION RATE: (BUTYL ACETATE=1)
0.97

VISCOSITY: 1.22 CPS @ 20 C

SOLUBILITY IN WATER: VERY SOLUBLE

VAPOR DENSITY: 2.07

VAPOR PRESSURE: 11.8 MMHG @ 20 C

PH: 2.4 (1.0 M SOL.)

ODOR-THRESHOLD: 1.0 PPM

OTHER SOLVENTS (SOLVENT - SOLUBILITY):
SOLUBLE IN ETHANOL, GLYCEROL, ETHER, ACETONE, BENZENE,
CARBON TETRACHLORIDE; INSOLUBLE IN CARBON DISULFIDE, CHLOROFORM, DIMETHYL
SULFOXIDE

FIRE AND EXPLOSION DATA

FIRE AND EXPLOSION HAZARD
MODERATE FIRE HAZARD WHEN EXPOSED TO HEAT OR FLAME.

VAPOR-AIR MIXTURES ARE EXPLOSIVE ABOVE FLASH POINT.

VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL A CONSIDERABLE DISTANCE TO A SOURCE
OF IGNITION AND FLASH BACK.

FLASH POINT: 103 F (39 C) (CC) UPPER EXPLOSION LIMIT: 19.9% @ 200 F

LOWER EXPLOSION LIMIT: 4.0% AUTOIGNITION TEMP.: 867 F (464 C)

FLAMMABILITY CLASS (OSHA): II

FIREFIGHTING MEDIA:
DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY OR REGULAR FOAM
(1990 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5).

FOR LARGER FIRES, USE WATER SPRAY, FOG OR REGULAR FOAM
(1990 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5).

ALCOHOL FOAM
(NFPA 325M, FIRE HAZARD PROPERTIES OF FLAMMABLE LIQUIDS, GASES, AND VOLATILE
SOLIDS, 1984).

FIREFIGHTING:
MOVE CONTAINER FROM FIRE AREA IF YOU CAN DO IT WITHOUT RISK. DO NOT GET WATER
INSIDE CONTAINER. APPLY COOLING WATER TO SIDES OF CONTAINERS THAT ARE EXPOSED
TO FLAMES UNTIL WELL AFTER FIRE IS OUT. STAY AWAY FROM ENDS OF TANKS. WITHDRAW
IMMEDIATELY IN CASE OF RISING SOUND FROM VENTING SAFETY DEVICE OR ANY
DISCOLORATION OF TANK DUE TO FIRE. ISOLATE FOR 1/2 MILE IN ALL DIRECTIONS IF
TANK, RAIL CAR OR TANK TRUCK IS INVOLVED IN FIRE (1990 EMERGENCY RESPONSE
GUIDEBOOK, DOT P 5800.5, GUIDE PAGE 29).

USE FLOODING AMOUNTS OF WATER AS A FOG; SOLID STREAMS MAY BE INEFFECTIVE.
COOL CONTAINERS WITH FLOODING AMOUNTS OF WATER FROM AS FAR A DISTANCE AS
POSSIBLE. USE WATER SPRAY TO ABSORB CORROSIVE VAPORS. AVOID BREATHING
CORROSIVE VAPORS; KEEP UPWIND.

FIRE FIGHTING PHASES: USE WATER SPRAY, DRY CHEMICAL, ALCOHOL FOAM, OR CARBON
DIOXIDE. USE WATER TO KEEP FIRE-EXPOSED CONTAINERS COOL. IF A LEAK OR SPILL
HAS NOT IGNITED, USE WATER SPRAY TO DISPERSE THE VAPORS AND TO PROTECT THE MEN
ATTEMPTING TO STOP A LEAK. WATER SPRAY MAY BE USED TO FLUSH SPILLS AWAY FROM
EXPOSURES AND TO DILUTE SPILLS TO NONFLAMMABLE MIXTURES (NFPA 49, HAZARDOUS
CHEMICALS DATA, 1975).

TRANSPORTATION

DEPARTMENT OF TRANSPORTATION HAZARD CLASSIFICATION 49 CFR 172.101:
CORROSIVE MATERIAL

DEPARTMENT OF TRANSPORTATION LABELING REQUIREMENTS 49 CFR 172.101 AND
SUBPART E:
CORROSIVE

DEPARTMENT OF TRANSPORTATION PACKAGING REQUIREMENTS: 49 CFR 173.245
EXCEPTIONS: 49 CFR 173.244

TOXICITY

ACETIC ACID, GLACIAL:

IRRITATION DATA: 50 MG/24 HOURS SKIN-HUMAN MILD; 525 MG OPEN SKIN-RABBIT SEVERE; 50 MG/24 HOURS SKIN-RABBIT MILD; 20 MG/24 HOURS SKIN-RABBIT MODERATE; 50 UG OPEN EYE-RABBIT SEVERE; 5 MG/30 SECONDS RINSED EYE-RABBIT MILD.

TOXICITY DATA: 816 PPM/3 MINUTES INHALATION-HUMAN TCLO; 16,000 PPM/4 HOURS INHALATION-RAT LCLO; 5620 PPM/1 HOUR INHALATION-MOUSE LC50; 1060 MG/KG SKIN-RABBIT LD50; 1470 UG/KG ORAL-HUMAN TDLO; 3310 MG/KG ORAL-RAT LD50; 1200 MG/KG ORAL-RABBIT LDLO; 1200 MG/KG SUBCUTANEOUS-RABBIT LDLO; 525 MG/KG INTRAVENOUS-MOUSE LD50; 1200 MG/KG RECTAL-RABBIT LDLO; 308 MG/KG UNREPORTED-MAN LDLO; MUTAGENIC DATA (RTECS); REPRODUCTIVE EFFECTS DATA (RTECS).

CARCINOGEN STATUS: NONE.

LOCAL EFFECTS: CORROSIVE- EYE, SKIN, MUCOUS MEMBRANES.

ACUTE TOXICITY LEVEL: MODERATELY TOXIC BY INHALATION, DERMAL ABSORPTION, INGESTION.

TARGET EFFECTS: POISONING MAY AFFECT THE LIVER, KIDNEYS, AND CARDIOVASCULAR SYSTEM.

AT INCREASED RISK: PERSONS WITH A HISTORY OF RESPIRATORY, SKIN OR EYE DISEASE.

HEALTH EFFECTS AND FIRST AID

INHALATION:

ACETIC ACID, GLACIAL:

CORROSIVE. 1000 PPM IMMEDIATELY DANGEROUS TO LIFE OR HEALTH.

ACUTE EXPOSURE- MAY CAUSE SEVERE IRRITATION OF THE RESPIRATORY TRACT. 50 PPM OR MORE IS INTOLERABLE TO MOST PERSONS AND RESULTS IN PHARYNGEAL EDEMA AND CHRONIC BRONCHITIS. OTHER SYMPTOMS MAY INCLUDE COUGHING, DYSPNEA, SHORTNESS OF BREATH, LARYNGITIS, PULMONARY EDEMA, BRONCHOPNEUMONIA AND HYPOTENSION.

CHRONIC EXPOSURE- WORKERS REPEATEDLY EXPOSED TO CONCENTRATIONS UP TO 200 PPM HAVE BEEN FOUND TO SUFFER FROM PALPEBRAL EDEMA WITH HYPERTROPHY OF THE LYMPH NODES, CHRONIC PHARYNGITIS, CHRONIC BRONCHITIS AND IN SOME CASES, ASTHMATIC BRONCHITIS AND TRACES OF EROSION OF THE TEETH. COMPLAINTS OF DIGESTIVE DISORDERS WITH PYROSIS AND CONSTIPATION HAVE ALSO BEEN REPORTED.

FIRST AID- REMOVE FROM EXPOSURE AREA TO FRESH AIR IMMEDIATELY. IF BREATHING HAS STOPPED, GIVE ARTIFICIAL RESPIRATION. MAINTAIN AIRWAY AND BLOOD PRESSURE AND ADMINISTER OXYGEN IF AVAILABLE. KEEP AFFECTED PERSON WARM AND AT REST. TREAT SYMPTOMATICALLY AND SUPPORTIVELY. ADMINISTRATION OF OXYGEN

SHOULD BE PERFORMED BY QUALIFIED PERSONNEL. GET MEDICAL ATTENTION IMMEDIATELY.

SKIN CONTACT:

ACETIC ACID, GLACIAL:
CORROSIVE.

ACUTE EXPOSURE- DIRECT CONTACT MAY CAUSE SEVERE IRRITATION WITH PAIN, ERYTHEMA, BLISTERS, BURNS AND SUPERFICIAL DESTRUCTION OF THE SKIN WITH SLOW HEALING. THE SKIN MAY BECOME BLACKENED, HYPERKERATOTIC AND FISSURED. CHRONIC EXPOSURE- REPEATED AND PROLONGED CONTACT MAY CAUSE DARKENING OF THE SKIN, IRRITATION AND DERMATITIS.

FIRST AID- REMOVE CONTAMINATED CLOTHING AND SHOES IMMEDIATELY. WASH AFFECTED AREA WITH SOAP OR MILD DETERGENT AND LARGE AMOUNTS OF WATER UNTIL NO EVIDENCE OF CHEMICAL REMAINS (AT LEAST 15-20 MINUTES). IN CASE OF CHEMICAL BURNS, COVER AREA WITH STERILE, DRY DRESSING. BANDAGE SECURELY, BUT NOT TOO TIGHTLY. GET MEDICAL ATTENTION IMMEDIATELY.

EYE CONTACT:

ACETIC ACID, GLACIAL:
CORROSIVE.

ACUTE EXPOSURE- DIRECT CONTACT CAUSES SEVERE IRRITATION, LACRIMATION, CORNEAL EROSION, OPACIFICATION, IRITIS AND POSSIBLY LOSS OF SIGHT IN HUMANS. REGENERATION OF THE EPITHELIUM MAY TAKE MANY MONTHS, BUT CORNEAL ANESTHESIA AND OPACITY WILL USUALLY BE PERMANENT. IN LESS SEVERE CASES, CONJUNCTIVITIS, PHOTOPHOBIA AND HYPEREMIA OF THE CONJUNCTIVA OCCURRED. THE VAPOR AND DILUTE SOLUTIONS MAY CAUSE CONJUNCTIVAL HYPEREMIA AND SOMETIMES INJURY TO THE CORNEAL EPITHELIUM.

CHRONIC EXPOSURE- DEPENDING ON THE CONCENTRATION AND DURATION OF EXPOSURE, EFFECTS SIMILAR TO ACUTE EXPOSURE MAY OCCUR.

FIRST AID- WASH EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER, OCCASIONALLY LIFTING UPPER AND LOWER LIDS, UNTIL NO EVIDENCE OF CHEMICAL REMAINS (AT LEAST 15-20 MINUTES). CONTINUE IRRIGATING WITH NORMAL SALINE UNTIL THE PH HAS RETURNED TO NORMAL (30-60 MINUTES). COVER WITH STERILE BANDAGES. GET MEDICAL ATTENTION IMMEDIATELY.

INGESTION:

ACETIC ACID, GLACIAL:
CORROSIVE.

ACUTE EXPOSURE- IN CASES OF ACCIDENTAL INGESTION, SEVERE ULCERONECROTIC LESIONS OF THE UPPER DIGESTIVE TRACT, STRICTURE OF THE ESOPHAGUS, AND PERFORATION OF THE ESOPHAGUS AND PYLORUS HAVE BEEN OBSERVED WITH HEMATEMESIS, DIARRHEA, SHOCK, HEMOGLOBINURIA FOLLOWED BY ANURIA AND UREMIA. OTHER SYMPTOMS MAY INCLUDE VOMITING, ABDOMINAL SPASMS, THIRST, DIFFICULTY IN SWALLOWING, HYPOTHERMIA, RAPID AND WEAK PULSE, SLOW AND SHALLOW BREATHING, LARYNGITIS, BRONCHITIS, PULMONARY EDEMA, PNEUMONIA, HEMOLYSIS, ALBUMINURIA, HEMATURIA, TWITCHING, CONVULSIONS, CARDIOVASCULAR COLLAPSE, SHOCK AND DEATH. EFFECTS ON THE NEWBORN HAVE BEEN REPORTED IN RATS FROM 700 MG/KG, ADMINISTERED 18 DAYS AFTER GESTATION.

CHRONIC EXPOSURE- NO DATA AVAILABLE.

FIRST AID- DO NOT USE GASTRIC LAVAGE OR EMESIS. DILUTE THE ACID IMMEDIATELY BY DRINKING LARGE QUANTITIES OF WATER OR MILK. IF VOMITING PERSISTS, ADMINISTER FLUIDS REPEATEDLY. INGESTED ACID MUST BE DILUTED APPROXIMATELY 100 FOLD TO RENDER IT HARMLESS TO TISSUES. MAINTAIN AIRWAY AND TREAT SHOCK (DREISBACH, HANDBOOK OF POISONING, 12TH ED.). GET MEDICAL ATTENTION IMMEDIATELY. IF VOMITING OCCURS, KEEP HEAD BELOW HIPS TO HELP PREVENT ASPIRATION.

ANTIDOTE:
NO SPECIFIC ANTIDOTE. TREAT SYMPTOMATICALLY AND SUPPORTIVELY.

REACTIVITY SECTION

REACTIVITY:
REACTS EXOTHERMICALLY WITH WATER.

INCOMPATIBILITIES:

ACETIC ACID, GLACIAL:

ACETALDEHYDE: VIOLENT, EXOTHERMIC POLYMERIZATION REACTION.

ACETIC ANHYDRIDE + WATER: VIOLENT, EXOTHERMIC REACTION.

2-AMINOETHANOL: TEMPERATURE AND PRESSURE INCREASE IN CLOSED CONTAINER.

AMMONIUM NITRATE: IGNITES ON WARMING, ESPECIALLY IF CONCENTRATED.

5-AZIDOTETRAZOLE: POSSIBLE EXPLOSIVE REACTION.

BASES: EXOTHERMIC REACTION.

BROMINE PENTAFLUORIDE: FIRE AND EXPLOSION HAZARD.

CARBONATES: INCOMPATIBLE.

CHLORINE TRIFLUORIDE: VIOLENT, POSSIBLY EXPLOSIVE REACTION.

CHLOROSULFONIC ACID: TEMPERATURE AND PRESSURE INCREASE IN CLOSED CONTAINER.

CHROMIC ACID: EXPLOSIVE REACTION IF NOT KEPT COLD.

CHROMIUM TRIOXIDE: POSSIBLE FIRE AND EXPLOSION HAZARD.

DIALLYL METHYL CARBINOL AND UZONE: EXPLOSIVE REACTION.

ETHYLENE DIAMINE: TEMPERATURE AND PRESSURE INCREASE IN CLOSED CONTAINER.

ETHYLENEIMINE: TEMPERATURE AND PRESSURE INCREASE IN CLOSED CONTAINER.

HYDROGEN PEROXIDE: EXOTHERMIC REACTION ON HEATING WITH THE PRODUCTION OF
PERACETIC ACID WHICH WILL EXPLODE AT 110 C.

HYDROXIDES: INCOMPATIBLE.

LEAD: CORRODES.

METALS: ATTACKS MOST METALS, INCLUDING ZINC.

NITRIC ACID: EXPLOSIVE REACTION IF NOT KEPT COLD.

NITRIC ACID AND ACETONE: EXPLOSIVE REACTION (DELAYED) IN CLOSED CONTAINER.

OLEUM: TEMPERATURE AND PRESSURE INCREASE IN CLOSED CONTAINER.

OXIDIZERS: FIRE AND EXPLOSION HAZARD.

PERCHLORIC ACID: EXPLOSIVE REACTION.

PERMANGANATES: EXPLOSIVE REACTION IF NOT KEPT COLD.

PHOSPHATES: INCOMPATIBLE.

PHOSPHORUS ISOCYANATE: VIOLENT REACTION.

PHOSPHORUS TRICHLORIDE: EXPLOSIVE REACTION.

POTASSIUM HYDROXIDE: VIOLENT REACTION.

POTASSIUM PERMANGANATE: POSSIBLE EXPLOSION IF INADEQUATELY COOLED.

POTASSIUM TERT-BUTOXIDE: IGNITION REACTION.

SODIUM HYDROXIDE: TEMPERATURE AND PRESSURE INCREASE IN CLOSED CONTAINER.

SODIUM PEROXIDE: EXPLOSIVE REACTION IF NOT KEPT COLD.

XYLENE: MAY FORM DETONABLE MIXTURES DURING TERPHTHALIC ACID PRODUCTION, THE
PRESENCE OF WATER MAY DECREASE THE HAZARD.

DECOMPOSITION:

THERMAL DECOMPOSITION PRODUCTS MAY INCLUDE TOXIC OXIDES OF CARBON.

POLYMERIZATION:

HAZARDOUS POLYMERIZATION HAS NOT BEEN REPORTED TO OCCUR UNDER NORMAL
TEMPERATURES AND PRESSURES.

STORAGE-DISPOSAL

OBSERVE ALL FEDERAL, STATE AND LOCAL REGULATIONS WHEN STORING OR DISPOSING OF THIS SUBSTANCE. FOR ASSISTANCE, CONTACT THE DISTRICT DIRECTOR OF THE ENVIRONMENTAL PROTECTION AGENCY.

STORAGE

PROTECT AGAINST PHYSICAL DAMAGE. DETACHED STORAGE IS PREFERRED. SEPARATE FROM OXIDIZING MATERIALS AND AVOID STORAGE NEAR COMBUSTIBLE MATERIALS. KEEP ABOVE ITS FREEZING POINT (62 F) TO AVOID RUPTURE OF CARBOYS AND GLASS CONTAINERS (NFPA 49, HAZARDOUS CHEMICALS DATA, 1975).

BONDING AND GROUNDING: SUBSTANCES WITH LOW ELECTROCONDUCTIVITY, WHICH MAY BE IGNITED BY ELECTROSTATIC SPARKS, SHOULD BE STORED IN CONTAINERS WHICH MEET THE BONDING AND GROUNDING GUIDELINES SPECIFIED IN NFPA 77-1983, RECOMMENDED PRACTICE ON STATIC ELECTRICITY.

STORE AWAY FROM INCOMPATIBLE SUBSTANCES.

DISPOSAL

DISPOSAL MUST BE IN ACCORDANCE WITH STANDARDS APPLICABLE TO GENERATORS OF HAZARDOUS WASTE, 40 CFR 262. EPA HAZARDOUS WASTE NUMBER D002.
100 POUND CERCLA SECTION 103 REPORTABLE QUANTITY.

CONDITIONS TO AVOID

AVOID CONTACT WITH HEAT, SPARKS, FLAMES OR OTHER IGNITION SOURCES. VAPORS MAY BE EXPLOSIVE. MATERIAL IS CORROSIVE; AVOID CONTACT WITH SKIN OR EYES. DO NOT ALLOW CONTAMINATION OF WATER SOURCES.

USUAL SHIPPING CONTAINERS:

GLASS AND POLYETHYLENE CARBOYS AND POLYETHYLENE-LINED DRUMS, TANK BARGES (NFPA 49, HAZARDOUS CHEMICALS DATA, 1975).

SPILLS AND LEAKS

SOIL-RELEASE:

DIG A HOLDING AREA SUCH AS A PIT, POND OR LAGOON TO CONTAIN SPILL AND DIKE SURFACE FLOW USING BARRIER OF SOIL, SANDBAGS, FOAMED POLYURETHANE OR FOAMED CONCRETE. ABSORB LIQUID MASS WITH FLY ASH OR CEMENT POWDER.

NEUTRALIZE WITH CAUSTIC SODA (NAOH) OR SODA ASH (NA₂CO₃)

AIR-RELEASE:

KNOCK DOWN VAPORS WITH WATER SPRAY. KEEP UPWIND.

WATER USED TO KNOCK DOWN VAPORS MAY BECOME CORROSIVE OR TOXIC AND SHOULD BE CONTAINED PROPERLY FOR LATER DISPOSAL.

WATER-SPILL:
NEUTRALIZE WITH CAUSTIC SODA.

OCCUPATIONAL-SPILL:
SHUT OFF IGNITION SOURCES. DO NOT TOUCH SPILLED MATERIAL. STOP LEAK IF YOU CAN DO IT WITHOUT RISK. USE WATER SPRAY TO REDUCE VAPORS. DO NOT GET WATER INSIDE CONTAINER. FOR SMALL SPILLS, TAKE UP WITH SAND OR OTHER ABSORBENT MATERIAL AND PLACE INTO CONTAINERS FOR LATER DISPOSAL. FOR LARGER SPILLS, DIKE FAR AHEAD OF SPILL FOR LATER DISPOSAL. NO SMOKING, FLAMES OR FLARES IN HAZARD AREA. KEEP UNNECESSARY PEOPLE AWAY; ISOLATE HAZARD AREA AND DENY ENTRY.

REPORTABLE QUANTITY (RQ): 5000 POUNDS
THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT (SARA) SECTION 304 REQUIRES THAT A RELEASE EQUAL TO OR GREATER THAN THE REPORTABLE QUANTITY FOR THIS SUBSTANCE BE IMMEDIATELY REPORTED TO THE LOCAL EMERGENCY PLANNING COMMITTEE AND THE STATE EMERGENCY RESPONSE COMMISSION (40 CFR 355.40). IF THE RELEASE OF THIS SUBSTANCE IS REPORTABLE UNDER CERCLA SECTION 103, THE NATIONAL RESPONSE CENTER MUST BE NOTIFIED IMMEDIATELY AT (800) 424-8802 OR (202) 426-2675 IN THE METROPOLITAN WASHINGTON, D.C. AREA (40 CFR 302.6).

PROTECTIVE EQUIPMENT SECTION

VENTILATION:
PROVIDE LOCAL EXHAUST VENTILATION SYSTEM TO MEET PUBLISHED EXPOSURE LIMITS.

RESPIRATOR:
THE FOLLOWING RESPIRATORS AND MAXIMUM USE CONCENTRATIONS ARE RECOMMENDATIONS BY THE U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES, NIOSH POCKET GUIDE TO CHEMICAL HAZARDS; NIOSH CRITERIA DOCUMENTS OR BY THE U.S. DEPARTMENT OF LABOR, 29 CFR 1910 SUBPART Z.
THE SPECIFIC RESPIRATOR SELECTED MUST BE BASED ON CONTAMINATION LEVELS FOUND IN THE WORK PLACE, MUST NOT EXCEED THE WORKING LIMITS OF THE RESPIRATOR AND BE JOINTLY APPROVED BY THE NATIONAL INSTITUTE FOR OCCUPATIONAL SAFETY AND HEALTH AND THE MINE SAFETY AND HEALTH ADMINISTRATION (NIOSH-MSHA).

ACETIC ACID, GLACIAL:

250 PPM- SUPPLIED-AIR RESPIRATOR OPERATED IN CONTINUOUS FLOW MODE.
POWERED AIR-PURIFYING RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE(S).

500 PPM- CHEMICAL CARTRIDGE RESPIRATOR WITH FULL FACEPIECE AND ORGANIC VAPOR CARTRIDGE(S).
SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE.
SUPPLIED-AIR RESPIRATOR WITH FULL FACEPIECE.
AIR-PURIFYING FULL FACEPIECE RESPIRATOR (GAS MASK) WITH CHIN-STYLE OR FRONT- OR BACK-MOUNTED ORGANIC VAPOR CANISTER.
POWERED AIR-PURIFYING RESPIRATOR WITH TIGHT-FITTING FACEPIECE AND ORGANIC VAPOR CARTRIDGE(S).

1000 PPM- SUPPLIED-AIR RESPIRATOR WITH FULL FACEPIECE AND OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.

ESCAPE- AIR-PURIFYING FULL FACEPIECE RESPIRATOR (GAS MASK) WITH CHIN-STYLE OR FRONT- OR BACK-MOUNTED ORGANIC VAPOR CANISTER.
ESCAPE-TYPE SELF-CONTAINED BREATHING APPARATUS.

FOR FIREFIGHTING AND OTHER IMMEDIATELY DANGEROUS TO LIFE OR HEALTH CONDITIONS:

SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN
PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.

SUPPLIED-AIR RESPIRATOR WITH FULL FACEPIECE AND OPERATED IN PRESSURE-DEMAND
OR OTHER POSITIVE PRESSURE MODE IN COMBINATION WITH AN AUXILIARY
SELF-CONTAINED BREATHING APPARATUS OPERATED IN PRESSURE-DEMAND OR OTHER
POSITIVE PRESSURE MODE.

CLOTHING:

EMPLOYEE MUST WEAR APPROPRIATE PROTECTIVE (IMPERVIOUS) CLOTHING AND EQUIPMENT
TO PREVENT ANY POSSIBILITY OF SKIN CONTACT WITH THIS SUBSTANCE.

GLOVES:

EMPLOYEE MUST WEAR APPROPRIATE PROTECTIVE GLOVES TO PREVENT CONTACT WITH THIS
SUBSTANCE.

EYE PROTECTION:

EMPLOYEE MUST WEAR SPLASH-PROOF OR DUST-RESISTANT SAFETY GOGGLES AND A
FACESHIELD TO PREVENT CONTACT WITH THIS SUBSTANCE.

EMERGENCY WASH FACILITIES:

WHERE THERE IS ANY POSSIBILITY THAT AN EMPLOYEE'S EYES AND/OR SKIN MAY BE
EXPOSED TO THIS SUBSTANCE, THE EMPLOYER SHOULD PROVIDE AN EYE WASH FOUNTAIN
AND QUICK DRENCH SHOWER WITHIN THE IMMEDIATE WORK AREA FOR EMERGENCY USE.

AUTHORIZED BY- OCCUPATIONAL HEALTH SERVICES, INC.

CREATION DATE: 09/06/84

REVISION DATE: 10/09/90

OCCUPATIONAL HEALTH SERVICES, INC.
11 WEST 42ND STREET, 12TH FLOOR
NEW YORK, NEW YORK 10036
1-800-445-MSDS (1-800-445-6737) OR 1-212-789-3535

FOR EMERGENCY SOURCE INFORMATION
CONTACT: 1-615-366-2000

SUBSTANCE IDENTIFICATION

CAS-NUMBER 9002-86-2
RTEC-NUMBER KV0350000

SUBSTANCE: **POLYVINYL CHLORIDE**

TRADE NAMES/SYNONYMS:

CHLOROETHENE, HOMOPOLYMER: CHLOROETHYLENE, POLYMER:
POLY(CHLOROETHYLENE): POLY(CHLOROVINYL): POLY(VINYL CHLORIDE): VINYL
CHLORIDE POLYMER: VINYL CHLORIDE RESIN: PVC: OHS19162

CHEMICAL FAMILY:

POLYMER: HALOGEN

MOLECULAR FORMULA: (C2-H3-CL)X

MOLECULAR WEIGHT: 60,000-150,000 (AVE)

CERCLA RATINGS (SCALE 0-3): HEALTH=U FIRE=1 REACTIVITY=0 PERSISTENCE=3

NFPA RATINGS (SCALE 0-4): HEALTH=U FIRE=1 REACTIVITY=0

COMPONENTS AND CONTAMINANTS

COMPONENT: POLYVINYL CHLORIDE CAS# 9002-86-2

PERCENT: 100.0

OTHER CONTAMINANTS: MAY CONTAIN TRACES OF VINYL CHLORIDE MONOMER.

EXPOSURE LIMIT:

POLYVINYL CHLORIDE:

AS PER 29CFR 1910.1017, IF EXPOSURE TO VINYL CHLORIDE MONOMER SHOULD OCCUR,
THE EXPOSURE LIMITS FOR THE MONOMER APPLY TO THE MANUFACTURE, REACTION,
PACKAGING, REPACKAGING, STORAGE, HANDLING OR USE OF POLYVINYL CHLORIDE,
BUT NOT FOR FABRICATED PRODUCTS MADE OF POLYVINYL CHLORIDE.

VINYL CHLORIDE:

1.0 PPM OSHA TWA; 5 PPM OSHA 15 MINUTE CEILING;

0.5 PPM OSHA ACTION LEVEL AS AN 8 HOUR TWA

5 PPM ACGIH TWA

ACGIH A1-CONFIRMED HUMAN CARCINOGEN.

LOWEST FEASIBLE LIMIT NIOSH RECOMMENDED EXPOSURE CRITERIA

1 POUND CERCLA SECTION 103 REPORTABLE QUANTITY

SUBJECT TO SARA SECTION 313 ANNUAL TOXIC CHEMICAL RELEASE REPORTING

SUBJECT TO CALIFORNIA PROPOSITION 65 CANCER AND/OR REPRODUCTIVE TOXICITY

WARNING AND RELEASE REQUIREMENTS- (FEBRUARY 27, 1987)

PHYSICAL DATA

DESCRIPTION: WHITE POWDER OR COLORLESS GRANULES WHICH MAY DISCOLOR ON
EXPOSURE TO HEAT OR LIGHT IN THE ABSENCE OF STABILIZERS

MELTING POINT: NOT AVAILABLE

SPECIFIC GRAVITY: 1.30-1.58

SOLUBILITY IN WATER: INSOLUBLE

OTHER SOLVENTS (SOLVENT - SOLUBILITY):

CYCLOHEXANONE, METHYL CYCLOHEXANONE, NITROBENZENE,
DIMETHYL FORMAMIDE, TETRAHYDROFURAN, ISOPHORONE, MESITYL OXIDE, DIPROPYL
KETONE, METHYL AMYL KETONE, METHYL ISOBUTYL KETONE, ACETONYLACETONE, DIOXANE

OTHER PHYSICAL DATA

GLASS TRANSITION TEMPERATURE: APPROX. 178 F (81 C)

FIRE AND EXPLOSION DATA

FIRE AND EXPLOSION HAZARD

SLIGHT FIRE HAZARD WHEN EXPOSED TO HEAT OR FLAME.

FLASH POINT: 736 F (391 C)

AUTOIGNITION TEMP.: 849 F (454 C)

FIREFIGHTING MEDIA:

DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY OR REGULAR FOAM
(1990 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5).

FOR LARGER FIRES, USE WATER SPRAY, FOG OR REGULAR FOAM
(1990 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5).

FIREFIGHTING:

MOVE CONTAINER FROM FIRE AREA IF YOU CAN DO IT WITHOUT RISK. DO NOT SCATTER
SPILLED MATERIAL WITH HIGH-PRESSURE WATER STREAMS. DIKE FIRE-CONTROL WATER FOR
LATER DISPOSAL (1990 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5, GUIDE
PAGE 31).

USE AGENTS SUITABLE FOR TYPE OF SURROUNDING FIRE. AVOID BREATHING HAZARDOUS
VAPORS, KEEP UPWIND.

TOXICITY

POLYVINYL CHLORIDE:

TOXICITY DATA: 5000 MG/KG ORAL-RAT LDO (85GMAT); 300-400 MG/M3 INHALATION-RAT
LDO (85GMAT); 50 MG/KG INTRATRACHEAL-RAT LDO (85GMAT); TUMORIGENIC DATA
(RTECS).

CARCINOGEN STATUS: HUMAN INADEQUATE EVIDENCE, ANIMAL INADEQUATE EVIDENCE
(IARC GROUP-3).

ACUTE TOXICITY LEVEL: INSUFFICIENT DATA.

TARGET EFFECTS: CHRONIC INHALATION MAY AFFECT THE LUNGS.

HEALTH EFFECTS AND FIRST AID

INHALATION:

POLYVINYL CHLORIDE:

ACUTE EXPOSURE- A 4-HOUR EXPOSURE OF 300-400 MG/M3 WAS NOT FATAL TO RATS. EXCESSIVE LEVELS OF DUST MAY BE IRRITATING.

CHRONIC EXPOSURE- CHRONIC INHALATION OF POLYVINYL CHLORIDE DUST HAS BEEN ASSOCIATED WITH IMPAIRMENT OF RESPIRATORY FUNCTION, PNEUMOCONIOSIS AND FIBROSIS IN HUMANS AND ANIMALS.

FIRST AID- REMOVE FROM EXPOSURE AREA TO FRESH AIR IMMEDIATELY. IF BREATHING HAS STOPPED, PERFORM ARTIFICIAL RESPIRATION. KEEP PERSON WARM AND AT REST. TREAT SYMPTOMATICALLY AND SUPPORTIVELY. GET MEDICAL ATTENTION IMMEDIATELY.

SKIN CONTACT:

POLYVINYL CHLORIDE:

ACUTE EXPOSURE- NO DATA AVAILABLE.

CHRONIC EXPOSURE- A CONDITION KNOWN AS ACRO-OSTEOLYSIS HAS BEEN REPORTED IN WORKERS WHO HAND SCRAPE POLYVINYL CHLORIDE REACTION VESSELS WHICH, BESIDES POLYVINYL CHLORIDE, MAY ALSO HAVE CONTAINED VARIOUS OTHER SUBSTANCES, INCLUDING VINYL CHLORIDE MONOMER. THE CONDITION, WHICH USUALLY OCCURS AFTER 12 MONTHS OF EXPOSURE, IS CHARACTERIZED BY TEGMENTAL THICKENING AND LOCALIZED NODULES FORMING ON THE DORSAL SURFACES OF HANDS AND FOREARMS AND X-RAY EVIDENCE OF BONE DESTRUCTION OF THE DISTAL PHALANGES OF THE HANDS. IT IS ACCOMPANIED BY RAYNAUD'S PHENOMENON WITH DISCOMFORT AND BLANCHING OF THE FINGERS AND TOES ON EXPOSURE TO COLD OR EMOTIONAL DISTURBANCE. THE INTERMITTENT ATTACKS MAY INCLUDE OR BE PRECEDED BY NUMBNESS, TINGLING AND BURNING. ARTHRITIC LESIONS, DECALCIFICATIONS OF THE PATELLA AND CYSTIC LESIONS OF THE SACROILIAC JOINTS HAVE ALSO BEEN REPORTED.

FIRST AID- REMOVE CONTAMINATED CLOTHING AND SHOES IMMEDIATELY. WASH AFFECTED AREA WITH SOAP OR MILD DETERGENT AND LARGE AMOUNTS OF WATER UNTIL NO EVIDENCE OF CHEMICAL REMAINS (APPROXIMATELY 15-20 MINUTES). GET MEDICAL ATTENTION IMMEDIATELY.

EYE CONTACT:

POLYVINYL CHLORIDE:

ACUTE EXPOSURE- NO DATA AVAILABLE. DUSTS MAY IRRITATE THE EYES DUE TO MECHANICAL FRICTION.

CHRONIC EXPOSURE- NO DATA AVAILABLE.

FIRST AID- WASH EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER OR NORMAL SALINE, OCCASIONALLY LIFTING UPPER AND LOWER LIDS, UNTIL NO EVIDENCE OF CHEMICAL REMAINS (APPROXIMATELY 15-20 MINUTES). GET MEDICAL ATTENTION IMMEDIATELY.

INGESTION:

POLYVINYL CHLORIDE:

ACUTE EXPOSURE- A DOSE OF 5000 MG/KG WAS NOT FATAL TO RATS. MOST HIGH POLYMERS ARE BIOLOGICALLY INERT.

CHRONIC EXPOSURE- ONE CASE HAS REPORTED THE DEVELOPMENT OF A SQUAMOUS CELL CARCINOMA OF THE BUCCAL MUCOSA IN A PERSON WHO CHEWED POLYVINYL CHLORIDE CONTAINING PLASTICS. THE EXACT COMPOSITION OF THE PLASTICS WAS NOT KNOWN. DOGS WHICH WERE FED 250 MG/KG/DAY FOR 5 DAYS DID NOT EXHIBIT ANY ADVERSE EFFECTS.

FIRST AID- TREAT SYMPTOMATICALLY AND SUPPORTIVELY. GET MEDICAL ATTENTION IMMEDIATELY. IF VOMITING OCCURS, KEEP HEAD LOWER THAN HIPS TO PREVENT ASPIRATION.

ANTIDOTE:

NO SPECIFIC ANTIDOTE. TREAT SYMPTOMATICALLY AND SUPPORTIVELY.

REACTIVITY SECTION

REACTIVITY:
STABLE UNDER NORMAL TEMPERATURES AND PRESSURES.

INCOMPATIBILITIES:

POLYVINYL CHLORIDE:

AMMONIA: PROLONGED CONTACT WILL DECOMPOSE POLYVINYL CHLORIDE.

CHLORINE: BREAKS DOWN POLYVINYL CHLORIDE.

COPPER: CATALYZES DECOMPOSITION OF POLYVINYL CHLORIDE.

IRON: CATALYZES DECOMPOSITION OF POLYVINYL CHLORIDE.

DECOMPOSITION:

BEGINS TO DECOMPOSE ABOVE 148 C WITH THE EVOLUTION OF CORROSIVE HYDROGEN CHLORIDE GAS. AT ELEVATED TEMPERATURES, THERMAL DECOMPOSITION MAY YIELD FUMES OF ETHYL CHLORIDE, PHOSGENE, VINYL CHLORIDE MONOMER, AND TOXIC OXIDES OF CARBON.

POLYMERIZATION:

HAZARDOUS POLYMERIZATION HAS NOT BEEN REPORTED TO OCCUR UNDER NORMAL TEMPERATURES AND PRESSURES.

STORAGE-DISPOSAL

OBSERVE ALL FEDERAL, STATE AND LOCAL REGULATIONS WHEN STORING OR DISPOSING OF THIS SUBSTANCE. FOR ASSISTANCE, CONTACT THE DISTRICT DIRECTOR OF THE ENVIRONMENTAL PROTECTION AGENCY.

****STORAGE****

STORE AWAY FROM INCOMPATIBLE SUBSTANCES.

****DISPOSAL****

VINYL CHLORIDE - REGULATORY LEVEL: 0.2 MG/L

MATERIALS WHICH CONTAIN THE ABOVE SUBSTANCE AT OR ABOVE THE REGULATORY LEVEL MEET THE EPA CHARACTERISTIC OF TOXICITY, AND MUST BE DISPOSED OF IN ACCORDANCE WITH 40 CFR PART 262. EPA HAZARDOUS WASTE NUMBER D043.

CONDITIONS TO AVOID

MAY BURN BUT DOES NOT IGNITE READILY. AVOID CONTACT WITH STRONG OXIDIZERS, EXCESSIVE HEAT, SPARKS, OR OPEN FLAME.

SPILLS AND LEAKS

OCCUPATIONAL-SPILL:

SWEEP UP AND PLACE IN SUITABLE CLEAN, DRY CONTAINERS FOR RECLAMATION OR LATER DISPOSAL. DO NOT FLUSH SPILLED MATERIAL INTO SEWER. KEEP UNNECESSARY PEOPLE AWAY.

PROTECTIVE EQUIPMENT SECTION

VENTILATION:

PROVIDE LOCAL EXHAUST VENTILATION SYSTEM TO MEET PUBLISHED EXPOSURE LIMITS.

RESPIRATOR:

THE FOLLOWING RESPIRATORS ARE RECOMMENDED BASED ON INFORMATION FOUND IN THE PHYSICAL DATA, TOXICITY AND HEALTH EFFECTS SECTIONS. THEY ARE RANKED IN ORDER FROM MINIMUM TO MAXIMUM RESPIRATORY PROTECTION.

THE SPECIFIC RESPIRATOR SELECTED MUST BE BASED ON CONTAMINATION LEVELS FOUND IN THE WORK PLACE, MUST NOT EXCEED THE WORKING LIMITS OF THE RESPIRATOR AND BE JOINTLY APPROVED BY THE NATIONAL INSTITUTE FOR OCCUPATIONAL SAFETY AND HEALTH AND THE MINE SAFETY AND HEALTH ADMINISTRATION (NIOSH-MSHA).

DUST AND MIST RESPIRATOR WITH A FULL FACEPIECE.

AIR-PURIFYING FULL FACEPIECE RESPIRATOR WITH A HIGH-EFFICIENCY PARTICULATE FILTER.

POWERED AIR-PURIFYING RESPIRATOR WITH A TIGHT-FITTING FACEPIECE AND HIGH-EFFICIENCY PARTICULATE FILTER.

TYPE 'C' SUPPLIED-AIR RESPIRATOR WITH A FULL FACEPIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE OR WITH A FULL FACEPIECE, HELMET OR HOOD OPERATED IN CONTINUOUS-FLOW MODE.

SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.

FOR FIREFIGHTING AND OTHER IMMEDIATELY DANGEROUS TO LIFE OR HEALTH CONDITIONS:

SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.

SUPPLIED-AIR RESPIRATOR WITH FULL FACEPIECE AND OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE IN COMBINATION WITH AN AUXILIARY SELF-CONTAINED BREATHING APPARATUS OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.

AS PER 29CFR 1910.1017, IF EXPOSURE TO VINYL CHLORIDE MONOMER SHOULD OCCUR, THE REQUIRED RESPIRATORS FOR THE MONOMER APPLY TO THE MANUFACTURE, REACTION, PACKAGING, REPACKAGING, STORAGE, HANDLING OR USE OF POLYVINYL CHLORIDE, BUT NOT FOR FABRICATED PRODUCTS MADE OF POLYVINYL CHLORIDE.

THE FOLLOWING RESPIRATORS ARE THE MINIMUM LEGAL REQUIREMENTS AS SET FORTH BY THE OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION FOUND IN 29 CFR 1910, SUBPART Z.

REQUIRED RESPIRATORS FOR VINYL CHLORIDE

ATMOSPHERIC CONCENTRATIONS OF VINYL

REQUIRED APPARATUS

CHLORIDE

UNKNOWN OR ABOVE 3600 PPM

OPEN-CIRCUIT, SELF CONTAINED
BREATHING APPARATUS, PRESSURE
DEMAND TYPE, WITH FULL FACEPIECE

NOT OVER 3600 PPM

COMBINATION TYPE 'C' SUPPLIED AIR
RESPIRATOR, PRESSURE DEMAND TYPE,
WITH A FULL OR HALF FACEPIECE AND
AUXILIARY SELF-CONTAINED AIR
SUPPLY;

OR

COMBINATION TYPE SUPPLIED AIR
RESPIRATOR, CONTINUOUS FLOW TYPE,
WITH A FULL OR HALF FACEPIECE,
AND AUXILIARY SELF-CONTAINED AIR
SUPPLY.

NOT OVER 1000 PPM

TYPE 'C' SUPPLIED AIR RESPIRATOR,
CONTINUOUS FLOW TYPE, WITH A FULL
OR HALF FACEPIECE, HELMET OR
HOOD.

NOT OVER 100 PPM

COMBINATION TYPE 'C' SUPPLIED AIR
RESPIRATOR, DEMAND TYPE, WITH A
FULL FACEPIECE, AND AUXILIARY
SELF-CONTAINED AIR SUPPLY;

OR

OPEN-CIRCUIT SELF-CONTAINED
BREATHING APPARATUS WITH A FULL
FACEPIECE, IN DEMAND MODE;

OR

TYPE 'C' SUPPLIED AIR RESPIRATOR,
DEMAND TYPE, WITH FULL FACEPIECE.

NOT OVER 25 PPM

A POWERED AIR PURIFYING
RESPIRATOR WITH HOOD, HELMET,
FULL OR HALF FACEPIECE, AND A
CANISTER WHICH PROVIDES A SERVICE
LIFE OF AT LEAST 4 HOURS FOR
CONCENTRATIONS OF VINYL CHLORIDE
UP TO 25 PPM;

OR

GAS MASK, FRONT- OR BACK-MOUNTED
CANISTER WHICH PROVIDES A SERVICE
LIFE OF AT LEAST 4 HOURS FOR
CONCENTRATIONS OF VINYL CHLORIDE
UP TO 25 PPM.

NOT OVER 10 PPM

COMBINATION TYPE 'C' SUPPLIED AIR
RESPIRATOR, WITH A HALF FACEPIECE
AND AUXILIARY SELF-CONTAINED AIR
SUPPLY;

OR

TYPE 'C' SUPPLIED-AIR RESPIRATOR,
DEMAND TYPE, WITH A HALF
FACEPIECE;

OR

ANY CHEMICAL CARTRIDGE RESPIRATOR
WITH AN ORGANIC VAPOR CARTRIDGE

WHICH PROVIDES A SERVICE LIFE OF
AT LEAST 1 HOUR FOR
CONCENTRATIONS OF VINYL CHLORIDE
UP TO 10 PPM.

ENTRY INTO UNKNOWN CONCENTRATIONS OR CONCENTRATIONS GREATER THAN 36,000 PPM
(LOWER EXPLOSION LIMIT) MAY BE MADE ONLY FOR THE PURPOSES OF LIFE RESCUE;
AND

ENTRY INTO CONCENTRATIONS OF LESS THAN 36,000 PPM, BUT GREATER THAN 3600 PPM
MAY BE MADE ONLY FOR THE PURPOSES OF LIFE RESCUE, FIREFIGHTING OR SECURING
EQUIPMENT SO AS TO PREVENT A GREATER HAZARD OF RELEASE OF VINYL CHLORIDE.

CLOTHING:

EMPLOYEE MUST WEAR APPROPRIATE PROTECTIVE (IMPERVIOUS) CLOTHING AND EQUIPMENT
TO PREVENT REPEATED OR PROLONGED SKIN CONTACT WITH THIS SUBSTANCE.

GLOVES:

EMPLOYEE MUST WEAR APPROPRIATE PROTECTIVE GLOVES TO PREVENT CONTACT WITH THIS
SUBSTANCE.

EYE PROTECTION:

EMPLOYEE MUST WEAR SPLASH-PROOF OR DUST-RESISTANT SAFETY GOGGLES TO PREVENT
EYE CONTACT WITH THIS SUBSTANCE.

EMERGENCY EYE WASH: WHERE THERE IS ANY POSSIBILITY THAT AN EMPLOYEE'S EYES MAY
BE EXPOSED TO THIS SUBSTANCE, THE EMPLOYER SHOULD PROVIDE AN EYE WASH
FOUNTAIN WITHIN THE IMMEDIATE WORK AREA FOR EMERGENCY USE.

AUTHORIZED BY- OCCUPATIONAL HEALTH SERVICES, INC.

CREATION DATE: 07/30/87

REVISION DATE: 10/09/90

MATERIAL SAFETY DATA SHEET

OHS19119

OCCUPATIONAL HEALTH SERVICES, INC.
11 WEST 42ND STREET, 12TH FLOOR
NEW YORK, NEW YORK 10036
1-800-445-MSDS (1-800-445-6737) OR 1-212-789-3535

FOR EMERGENCY SOURCE INFORMATION
CONTACT: 1-615-366-2000

SUBSTANCE IDENTIFICATION

CAS-NUMBER 9002-88-4
RTEC-NUMBER TQ3325000

SUBSTANCE: ~~POLYETHYLENE~~

TRADE NAMES/SYNONYMS:

ETHENE, HOMOPOLYMER: ETHYLENE, POLYMERS: POLYETHENE: OHS19119

CHEMICAL FAMILY:

POLYMER: HYDROCARBON, ALIPHATIC

MOLECULAR FORMULA: (C₂H₄)_x

MOLECULAR WEIGHT: (26.02)_x

CERCLA RATINGS (SCALE 0-3): HEALTH=3 FIRE=1 REACTIVITY=0 PERSISTENCE=3
NFPA RATINGS (SCALE 0-4): HEALTH=U FIRE=1 REACTIVITY=0

COMPONENTS AND CONTAMINANTS

COMPONENT: POLYETHYLENE CAS# 9002-88-4

PERCENT: 100.0

OTHER CONTAMINANTS: NONE

EXPOSURE LIMIT:

NO OCCUPATIONAL EXPOSURE LIMITS ESTABLISHED BY OSHA, ACGIH, OR NIOSH.

PHYSICAL DATA

DESCRIPTION: WHITE, PLASTIC SOLID WITH A MILKY TRANSPARENCY. DARKENS ON
EXPOSURE TO LIGHT.

MELTING POINT: 185-230 F (85-110 C) SPECIFIC GRAVITY: 0.91-0.96

SOLUBILITY IN WATER: INSOLUBLE

OTHER SOLVENTS (SOLVENT - SOLUBILITY):

SOLUBLE IN TURPENTINE, PETROLEUM NAPHTHA, XYLENE, AND
TOLUENE, HOT TRICHLOROETHYLENE, AND HOT MINERAL OILS; SLIGHTLY SOLUBLE IN
METHYL ACETATE AND ACETONE.

FIRE AND EXPLOSION DATA

FIRE AND EXPLOSION HAZARD

SLIGHT FIRE HAZARD WHEN EXPOSED TO HEAT OR FLAME.

AUTOIGNITION TEMP.: 660 F (349 C)

FIREFIGHTING MEDIA:
DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY OR REGULAR FOAM
(1990 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5).

FOR LARGER FIRES, USE WATER SPRAY, FOG OR REGULAR FOAM
(1990 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5).

FIREFIGHTING:
MOVE CONTAINER FROM FIRE AREA IF YOU CAN DO IT WITHOUT RISK. DO NOT SCATTER
SPILLED MATERIAL WITH HIGH-PRESSURE WATER STREAMS. DIKE FIRE-CONTROL WATER FOR
LATER DISPOSAL (1990 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5, GUIDE
PAGE 31).

USE AGENTS SUITABLE FOR TYPE OF SURROUNDING FIRE. AVOID BREATHING HAZARDOUS
VAPORS, KEEP UPWIND.

TOXICITY

POLYETHYLENE:
TOXICITY DATA: TUMORIGENIC DATA (RTECS).
CARCINOGEN STATUS: ANIMAL INADEQUATE EVIDENCE (IARC GROUP-3).
ACUTE TOXICITY LEVEL: NO DATA AVAILABLE.
TARGET EFFECTS: NO DATA AVAILABLE.

HEALTH EFFECTS AND FIRST AID

INHALATION:
POLYETHYLENE:
ACUTE EXPOSURE- NO EVIDENCE HAS BEEN FOUND TO SHOW THAT POLYETHYLENE
PRODUCES TOXIC SYMPTOMS WHEN INHALED.
CHRONIC EXPOSURE- NO DATA AVAILABLE.

FIRST AID- REMOVE FROM EXPOSURE AREA TO FRESH AIR IMMEDIATELY. IF BREATHING
HAS STOPPED, PERFORM ARTIFICIAL RESPIRATION. KEEP PERSON WARM AND AT REST.
TREAT SYMPTOMATICALLY AND SUPPORTIVELY. GET MEDICAL ATTENTION IMMEDIATELY.

SKIN CONTACT:
POLYETHYLENE:
ACUTE EXPOSURE- POLYETHYLENES ARE NEITHER IRRITANTS OR SENSITIZERS TO THE
SKIN. DERMATITIS RESULTING FROM HEAT-SEALING OF POLYETHYLENE BAGS WAS
ATTRIBUTED TO THERMAL DECOMPOSITION PRODUCTS, FORMALDEHYDE AND ACROLEIN.
CHRONIC EXPOSURE- NO DATA AVAILABLE.

FIRST AID- REMOVE CONTAMINATED CLOTHING AND SHOES IMMEDIATELY. WASH AFFECTED
AREA WITH SOAP OR MILD DETERGENT AND LARGE AMOUNTS OF WATER UNTIL NO
EVIDENCE OF CHEMICAL REMAINS (APPROXIMATELY 15-20 MINUTES). GET MEDICAL
ATTENTION IMMEDIATELY.

EYE CONTACT:
POLYETHYLENE:
ACUTE EXPOSURE- NO DATA AVAILABLE.

CHRONIC EXPOSURE- NO DATA AVAILABLE.

FIRST AID- WASH EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER OR NORMAL SALINE, OCCASIONALLY LIFTING UPPER AND LOWER LIDS, UNTIL NO EVIDENCE OF CHEMICAL REMAINS (APPROXIMATELY 15-20 MINUTES). GET MEDICAL ATTENTION IMMEDIATELY.

INGESTION:

POLYETHYLENE:

ACUTE EXPOSURE- NO EVIDENCE HAS BEEN FOUND TO SHOW THAT POLYETHYLENE PRODUCES TOXIC SYMPTOMS WHEN INGESTED. A DOSE OF 7000 MG/KG WAS NOT LETHAL TO MICE.

CHRONIC EXPOSURE- RATS FED 8 GM/KG DAILY SHOWED NO TOXIC REACTIONS AND GAINED WEIGHT NORMALLY.

FIRST AID- TREAT SYMPTOMATICALLY AND SUPPORTIVELY. GET MEDICAL ATTENTION IMMEDIATELY. IF VOMITING OCCURS, KEEP HEAD LOWER THAN HIPS TO PREVENT ASPIRATION.

ANTIDOTE:

NO SPECIFIC ANTIDOTE. TREAT SYMPTOMATICALLY AND SUPPORTIVELY.

REACTIVITY SECTION

REACTIVITY:

STABLE UNDER NORMAL TEMPERATURES AND PRESSURES.

INCOMPATIBILITIES:

POLYETHYLENE:

AROMATIC HYDROCARBONS: MAY ATTACK POLYMER.

BENZENE: MAY ATTACK POLYMER.

CHLORINATED HYDROCARBONS: MAY ATTACK POLYMER.

FLUORINE: REACTS VIOLENTLY.

FREE HALOGENS: MAY ATTACK POLYMER.

GASOLINE: MAY ATTACK POLYMER.

LUBRICATING OILS: MAY ATTACK POLYMER.

NITRIC ACID: MAY ATTACK POLYMER.

OXIDIZING AGENTS: MAY SLOWLY ATTACK POLYMER.

PERCHLORIC ACID: MAY ATTACK POLYMER.

PETROLEUM ETHER: MAY ATTACK POLYMER.

GASEOUS OR LIQUID FLUORINE-OXYGEN: VIOLENT REACTION.

SULFURIC ACID (FUMING): MAY SLOWLY ATTACK POLYMER.

DECOMPOSITION:

THERMAL DECOMPOSITION PRODUCTS MAY INCLUDE TOXIC AND HAZARDOUS ACROLEIN AND FORMALDEHYDE AND OXIDES OF CARBON.

POLYMERIZATION:

HAZARDOUS POLYMERIZATION HAS NOT BEEN REPORTED TO OCCUR UNDER NORMAL TEMPERATURES AND PRESSURES.

STORAGE-DISPOSAL

OBSERVE ALL FEDERAL, STATE AND LOCAL REGULATIONS WHEN STORING OR DISPOSING OF THIS SUBSTANCE. FOR ASSISTANCE, CONTACT THE DISTRICT DIRECTOR OF THE

CONDITIONS TO AVOID

MAY BURN BUT DOES NOT IGNITE READILY. AVOID CONTACT WITH STRONG OXIDIZERS, EXCESSIVE HEAT, SPARKS, OR OPEN FLAME.

SPILLS AND LEAKS

OCCUPATIONAL-SPILL:
SWEEP UP AND PLACE IN SUITABLE CLEAN, DRY CONTAINERS FOR RECLAMATION OR LATER DISPOSAL. DO NOT FLUSH SPILLED MATERIAL INTO SEWER. KEEP UNNECESSARY PEOPLE AWAY.

PROTECTIVE EQUIPMENT SECTION

VENTILATION:
PROVIDE LOCAL EXHAUST OR GENERAL DILUTION VENTILATION SYSTEM.

RESPIRATOR:
THE FOLLOWING RESPIRATORS ARE RECOMMENDED BASED ON INFORMATION FOUND IN THE PHYSICAL DATA, TOXICITY AND HEALTH EFFECTS SECTIONS. THEY ARE RANKED IN ORDER FROM MINIMUM TO MAXIMUM RESPIRATORY PROTECTION.
THE SPECIFIC RESPIRATOR SELECTED MUST BE BASED ON CONTAMINATION LEVELS FOUND IN THE WORK PLACE, MUST NOT EXCEED THE WORKING LIMITS OF THE RESPIRATOR AND BE JOINTLY APPROVED BY THE NATIONAL INSTITUTE FOR OCCUPATIONAL SAFETY AND HEALTH AND THE MINE SAFETY AND HEALTH ADMINISTRATION (NIOSH-MSHA).

DUST AND MIST RESPIRATOR.

AIR-PURIFYING RESPIRATOR WITH A HIGH-EFFICIENCY PARTICULATE FILTER.

POWERED AIR-PURIFYING RESPIRATOR WITH A DUST AND MIST FILTER.

POWERED AIR-PURIFYING RESPIRATOR WITH A HIGH-EFFICIENCY PARTICULATE FILTER.

TYPE 'C' SUPPLIED-AIR RESPIRATOR OPERATED IN THE PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE OR CONTINUOUS-FLOW MODE.

SELF-CONTAINED BREATHING APPARATUS.

FOR FIREFIGHTING AND OTHER IMMEDIATELY DANGEROUS TO LIFE OR HEALTH CONDITIONS:

SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.

SUPPLIED-AIR RESPIRATOR WITH FULL FACEPIECE AND OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE IN COMBINATION WITH AN AUXILIARY SELF-CONTAINED BREATHING APPARATUS OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.

CLOTHING:
PROTECTIVE CLOTHING NOT REQUIRED. AVOID REPEATED OR PROLONGED CONTACT WITH
THIS SUBSTANCE.

GLOVES:
PROTECTIVE GLOVES ARE NOT REQUIRED BUT RECOMMENDED.

EYE PROTECTION:
EYE PROTECTION NOT REQUIRED, BUT ADVISABLE.

AUTHORIZED BY- OCCUPATIONAL HEALTH SERVICES, INC.

CREATION DATE: 11/03/86

REVISION DATE: 10/09/90

MATERIAL SAFETY DATA SHEET

OHS19150

OCCUPATIONAL HEALTH SERVICES, INC.
11 WEST 42ND STREET, 12TH FLOOR
NEW YORK, NEW YORK 10036
1-800-445-MSDS (1-800-445-6737) OR 1-212-789-3535

FOR EMERGENCY SOURCE INFORMATION
CONTACT: 1-615-366-2000

SUBSTANCE IDENTIFICATION

SUBSTANCE: **POLYSTYRENE**

CAS-NUMBER 9003-53-6
RTEC-NUMBER WL6475000

TRADE NAMES/SYNONYMS:

BENZENE, ETHENYL-, HOMOPOLYMER: ETHENYLBENZENE HOMOPOLYMER: DYLENE:
HOMOPOLYSTYRENE: STYRENE HOMOPOLYMER: VINYLBENZENE POLYMER: STYRENE
POLYMER: PS: OHS19150

CHEMICAL FAMILY:

STYRENE: POLYMER

MOLECULAR FORMULA: $(-C-H-(C_6-H_5)-C-H_2-)_X$

CERCLA RATINGS (SCALE 0-3): HEALTH=2 FIRE=1 REACTIVITY=0 PERSISTENCE=3

NFPA RATINGS (SCALE 0-4): HEALTH=U FIRE=1 REACTIVITY=0

COMPONENTS AND CONTAMINANTS

COMPONENT: POLYSTYRENE CAS# 9003-53-6

PERCENT: 100.0

OTHER CONTAMINANTS: NONE

EXPOSURE LIMIT:

NO OCCUPATIONAL EXPOSURE LIMITS ESTABLISHED BY OSHA, ACGIH, OR NIOSH.

PHYSICAL DATA

DESCRIPTION: ODORLESS, COLORLESS, CLEAR BRITTLE SOLID OR SOFT FOAM; YELLOWS
ON EXPOSURE TO LIGHT.

MELTING POINT: 464 F (240 C)

SPECIFIC GRAVITY: 1.04-1.13

SOLUBILITY IN WATER: INSOLUBLE

OTHER SOLVENTS (SOLVENT - SOLUBILITY):

SOLUBLE IN ETHYL BENZENE, METHYL ISOBUTYL KETONE,
TETRAHYDROFURAN, BENZENE, TOLUENE, METHYLENE CHLORIDE, PYRIDINE; INSOLUBLE IN
ALCOHOLS, ORGANIC ACIDS.

FIRE AND EXPLOSION DATA

FIRE AND EXPLOSION HAZARD

SLIGHT FIRE HAZARD WHEN EXPOSED TO HEAT OR FLAME.

DUST-AIR MIXTURES MAY IGNITE OR EXPLODE.

FLASH POINT: 653-680 F (345-360 C) AUTOIGNITION TEMP.: 800 F (427 C)

FIREFIGHTING MEDIA:

DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY OR REGULAR FOAM
(1990 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5).

FOR LARGER FIRES, USE WATER SPRAY, FOG OR REGULAR FOAM
(1990 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5).

FIREFIGHTING:

MOVE CONTAINER FROM FIRE AREA IF YOU CAN DO IT WITHOUT RISK. DO NOT SCATTER
SPILLED MATERIAL WITH HIGH-PRESSURE WATER STREAMS. DIKE FIRE-CONTROL WATER FOR
LATER DISPOSAL (1990 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5, GUIDE
PAGE 31).

USE AGENTS SUITABLE FOR TYPE OF SURROUNDING FIRE. AVOID BREATHING HAZARDOUS
VAPORS, KEEP UPWIND.

TOXICITY

POLYSTYRENE:

TOXICITY DATA: TUMORIGENIC DATA (RTECS).

CARCINOGEN STATUS: ANIMAL INADEQUATE EVIDENCE (IARC GROUP-3).

ACUTE TOXICITY LEVEL: NO DATA AVAILABLE.

TARGET EFFECTS: NO DATA AVAILABLE.

HEALTH EFFECTS AND FIRST AID

INHALATION:

POLYSTYRENE:

ACUTE EXPOSURE- MAY CAUSE TEMPORARY IRRITATION OF THE RESPIRATORY TRACT AND
COUGHING.

CHRONIC EXPOSURE- WORKERS EXPOSED TO POLYSTYRENE CONVERTING PROCESSES HAVE
SHOWN DISORDERS OF THE NERVOUS SYSTEM, LIVER AND OTHER ORGANS, BLOOD, AND
MUCOUS MEMBRANES OF THE UPPER RESPIRATORY TRACT. EEG CHANGES, SIGNS OF
MUTAGENESIS, SLIGHT CARCINOGENIC EFFECTS, DISTURBED ACID-BASE BALANCE,
CHANGES IN PROTEIN AND ELECTROLYTE METABOLISM, DISTURBED MENSTRUAL CYCLE,
COMPLICATIONS DURING PREGNANCY AND CHILD BIRTH, TOXICOSES, DISTURBED
SEXUAL ACTIVITY AND MORPHOLOGICAL CHANGES IN THE PLACENTA HAVE BEEN
REPORTED IN POLYSTYRENE PRODUCTION WORKERS. IN ADDITION, POLYSTYRENE
DUST HAS CAUSED RETARDATION OF WEIGHT GAIN, CHANGES IN RED AND WHITE
BLOOD CELLS, HEPATIC HYPERTROPHY AND A MILD PNEUMOCONIOSIS IN EXPERIMENTAL
ANIMALS.

FIRST AID- REMOVE FROM EXPOSURE AREA TO FRESH AIR IMMEDIATELY. IF BREATHING
HAS STOPPED, PERFORM ARTIFICIAL RESPIRATION. KEEP PERSON WARM AND AT REST.
TREAT SYMPTOMATICALLY AND SUPPORTIVELY. GET MEDICAL ATTENTION IMMEDIATELY.

SKIN CONTACT:

POLYSTYRENE:

ACUTE EXPOSURE- NO DATA AVAILABLE.

CHRONIC EXPOSURE- NO DATA AVAILABLE.

FIRST AID- REMOVE CONTAMINATED CLOTHING AND SHOES IMMEDIATELY. WASH AFFECTED AREA WITH SOAP OR MILD DETERGENT AND LARGE AMOUNTS OF WATER UNTIL NO EVIDENCE OF CHEMICAL REMAINS (APPROXIMATELY 15-20 MINUTES). GET MEDICAL ATTENTION IMMEDIATELY.

EYE CONTACT:

POLYSTYRENE:

ACUTE EXPOSURE- DUSTS MAY CAUSE MILD IRRITATION. FUMES MAY CAUSE IRRITATION AND TEARING.

CHRONIC EXPOSURE- NO DATA AVAILABLE.

FIRST AID- WASH EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER OR NORMAL SALINE, OCCASIONALLY LIFTING UPPER AND LOWER LIDS, UNTIL NO EVIDENCE OF CHEMICAL REMAINS (APPROXIMATELY 15-20 MINUTES). GET MEDICAL ATTENTION IMMEDIATELY.

INGESTION:

POLYSTYRENE:

ACUTE EXPOSURE- MAY CAUSE IRRITATION.

CHRONIC EXPOSURE- VARIOUS FEEDING STUDIES OF ANIMALS OF LEVELS UP TO 5% IN THE DIET HAVE FAILED TO INDICATE ANY ADVERSE EFFECTS. AN 11 MONTH STUDY IN WHICH RATS WERE GIVEN 99.54% POLYSTYRENE (0.15% MONOMER) IN WATER SHOWED NO SIGNIFICANT CHANGE IN BEHAVIOR OR GENERAL CONDITION. THE SPLEEN, HOWEVER, CONTAINED A CONSIDERABLE AMOUNT OF IRON AND HEMOSIDERIN AND THE LIVER, KIDNEYS AND STOMACH SHOWED A REACTIVE PROLIFERATION OF CONNECTIVE TISSUE.

FIRST AID- TREAT SYMPTOMATICALLY AND SUPPORTIVELY. GET MEDICAL ATTENTION IMMEDIATELY. IF VOMITING OCCURS, KEEP HEAD LOWER THAN HIPS TO PREVENT ASPIRATION.

ANTIDOTE:

NO SPECIFIC ANTIDOTE. TREAT SYMPTOMATICALLY AND SUPPORTIVELY.

REACTIVITY SECTION

REACTIVITY:

STABLE UNDER NORMAL TEMPERATURES AND PRESSURES.

MAY DETERIORATE FROM PROLONGED EXPOSURE TO LIGHT.

INCOMPATIBILITIES:

POLYSTYRENE:

HYDROCARBON SOLVENTS: MAY DISSOLVE.

OXIDIZERS (STRONG): FIRE AND EXPLOSION HAZARD.

DECOMPOSITION:

THERMAL DECOMPOSITION MAY RELEASE ACRID SMOKE AND IRRITATING FUMES.

THERMAL DECOMPOSITION PRODUCTS MAY INCLUDE TOXIC OXIDES OF CARBON.

POLYMERIZATION:

HAZARDOUS POLYMERIZATION HAS NOT BEEN REPORTED TO OCCUR UNDER NORMAL TEMPERATURES AND PRESSURES.

STORAGE-DISPOSAL

OBSERVE ALL FEDERAL, STATE AND LOCAL REGULATIONS WHEN STORING OR DISPOSING OF THIS SUBSTANCE. FOR ASSISTANCE, CONTACT THE DISTRICT DIRECTOR OF THE ENVIRONMENTAL PROTECTION AGENCY.

STORAGE

STORE AWAY FROM INCOMPATIBLE SUBSTANCES.

KEEP IN A TIGHTLY CLOSED CONTAINER. STORE IN A COOL, DRY, VENTILATED AREA.

CONDITIONS TO AVOID

MAY BURN BUT DOES NOT IGNITE READILY. AVOID CONTACT WITH STRONG OXIDIZERS, EXCESSIVE HEAT, SPARKS, OR OPEN FLAME.

SPILLS AND LEAKS

OCCUPATIONAL-SPILL:
SWEEP UP AND PLACE IN SUITABLE CLEAN, DRY CONTAINERS FOR RECLAMATION OR LATER DISPOSAL. DO NOT FLUSH SPILLED MATERIAL INTO SEWER. KEEP UNNECESSARY PEOPLE AWAY.

PROTECTIVE EQUIPMENT SECTION

VENTILATION:
PROVIDE LOCAL EXHAUST OR PROCESS ENCLOSURE VENTILATION SYSTEM.

RESPIRATOR:
THE FOLLOWING RESPIRATORS ARE RECOMMENDED BASED ON INFORMATION FOUND IN THE PHYSICAL DATA, TOXICITY AND HEALTH EFFECTS SECTIONS. THEY ARE RANKED IN ORDER FROM MINIMUM TO MAXIMUM RESPIRATORY PROTECTION.
THE SPECIFIC RESPIRATOR SELECTED MUST BE BASED ON CONTAMINATION LEVELS FOUND IN THE WORK PLACE, MUST NOT EXCEED THE WORKING LIMITS OF THE RESPIRATOR AND BE JOINTLY APPROVED BY THE NATIONAL INSTITUTE FOR OCCUPATIONAL SAFETY AND HEALTH AND THE MINE SAFETY AND HEALTH ADMINISTRATION (NIOSH-MSHA).

DUST AND MIST RESPIRATOR WITH A FULL FACEPIECE.

AIR-PURIFYING FULL FACEPIECE RESPIRATOR WITH A HIGH-EFFICIENCY PARTICULATE FILTER.

POWERED AIR-PURIFYING RESPIRATOR WITH A TIGHT-FITTING FACEPIECE AND HIGH-EFFICIENCY PARTICULATE FILTER.

TYPE 'C' SUPPLIED-AIR RESPIRATOR WITH A FULL FACEPIECE OPERATED IN
PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE OR WITH A FULL FACEPIECE,
HELMET OR HOOD OPERATED IN CONTINUOUS-FLOW MODE.

SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN
PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.

FOR FIREFIGHTING AND OTHER IMMEDIATELY DANGEROUS TO LIFE OR HEALTH CONDITIONS:

SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN
PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.

SUPPLIED-AIR RESPIRATOR WITH FULL FACEPIECE AND OPERATED IN PRESSURE-DEMAND
OR OTHER POSITIVE PRESSURE MODE IN COMBINATION WITH AN AUXILIARY
SELF-CONTAINED BREATHING APPARATUS OPERATED IN PRESSURE-DEMAND OR OTHER
POSITIVE PRESSURE MODE.

CLOTHING:

EMPLOYEE MUST WEAR APPROPRIATE PROTECTIVE (IMPERVIOUS) CLOTHING AND EQUIPMENT
TO PREVENT REPEATED OR PROLONGED SKIN CONTACT WITH THIS SUBSTANCE.

GLOVES:

EMPLOYEE MUST WEAR APPROPRIATE PROTECTIVE GLOVES TO PREVENT CONTACT WITH THIS
SUBSTANCE.

EYE PROTECTION:

EMPLOYEE MUST WEAR SPLASH-PROOF OR DUST-RESISTANT SAFETY GOGGLES TO PREVENT
EYE CONTACT WITH THIS SUBSTANCE.

EMERGENCY EYE WASH: WHERE THERE IS ANY POSSIBILITY THAT AN EMPLOYEE'S EYES MAY
BE EXPOSED TO THIS SUBSTANCE, THE EMPLOYER SHOULD PROVIDE AN EYE WASH
FOUNTAIN WITHIN THE IMMEDIATE WORK AREA FOR EMERGENCY USE.

AUTHORIZED BY- OCCUPATIONAL HEALTH SERVICES, INC.

CREATION DATE: 10/11/90

REVISION DATE: 10/11/90

MATERIAL SAFETY DATA SHEET

OHS04371

OCCUPATIONAL HEALTH SERVICES, INC.
11 WEST 42ND STREET, 12TH FLOOR
NEW YORK, NEW YORK 10036
1-800-445-MSDS (1-800-445-6737) OR 1-212-789-3535

FOR EMERGENCY SOURCE INFORMATION
CONTACT: 1-615-366-2000

SUBSTANCE IDENTIFICATION

SUBSTANCE: **CELLULOSE**

CAS-NUMBER 9004-34-6
RTEC-NUMBER FJ5691460

TRADE NAMES/SYNONYMS:

BETA-AMYLOSE: ALPHA-CELLULOSE: CRYSTALLINE CELLULOSE:
MICROCRYSTALLINE CELLULOSE: OHS04371

CHEMICAL FAMILY:
POLYSACCHARIDE

MOLECULAR FORMULA: (C₆-H₁₀-O₅)X MOLECULAR WEIGHT: (162.14)X

CERCLA RATINGS (SCALE 0-3): HEALTH=U FIRE=1 REACTIVITY=0 PERSISTENCE=0
NFPA RATINGS (SCALE 0-4): HEALTH=U FIRE=1 REACTIVITY=0

COMPONENTS AND CONTAMINANTS

COMPONENT: CELLULOSE CAS# 9004-34-6

PERCENT: 100.0

OTHER CONTAMINANTS: NONE

EXPOSURE LIMIT:

NUISANCE PARTICULATES (NUISANCE DUST):

5 MG/M³ OSHA TWA (RESPIRABLE DUST); 15 MG/M³ OSHA TWA (TOTAL DUST)10 MG/M³ ACGIH TWA (TOTAL DUST) (NO ASBESTOS AND < 1% CRYSTALLINE SILICA)

PHYSICAL DATA

DESCRIPTION: WHITE POWDER.

MELTING POINT: 500-518 F (260-270 C)

DECOMPOSES

SPECIFIC GRAVITY: 1.27-1.60

SOLUBILITY IN WATER: INSOLUBLE

OTHER SOLVENTS (SOLVENT - SOLUBILITY):

SOLUBLE IN SCHWEITZER'S REAGENT, CONCENTRATED SOLUTIONS
OF ZINC CHLORIDE, AMMONIACAL COPPER HYDROXIDE SOLUTIONS, AND CAUSTIC ALKALI
WITH CARBON DISULFIDE; INSOLUBLE IN DILUTE ACIDS AND ORGANIC ACIDS.

FIRE AND EXPLOSION DATA

FIRE AND EXPLOSION HAZARD

SLIGHT FIRE HAZARD WHEN EXPOSED TO HEAT OR FLAME.

DUST-AIR MIXTURES MAY IGNITE OR EXPLODE.

FIREFIGHTING MEDIA:

DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY OR REGULAR FOAM
(1990 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5).

FOR LARGER FIRES, USE WATER SPRAY, FOG OR REGULAR FOAM
(1990 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5).

FIREFIGHTING:

MOVE CONTAINER FROM FIRE AREA IF YOU CAN DO IT WITHOUT RISK. DO NOT SCATTER
SPILLED MATERIAL WITH HIGH-PRESSURE WATER STREAMS. DIKE FIRE-CONTROL WATER FOR
LATER DISPOSAL (1990 EMERGENCY RESPONSE GUIDEBOOK, DOT P 5800.5, GUIDE
PAGE 31).

USE AGENTS SUITABLE FOR TYPE OF SURROUNDING FIRE. AVOID BREATHING HAZARDOUS
VAPORS, KEEP UPWIND.

TOXICITY

CELLULOSE:

TOXICITY DATA: >2 GM/KG SKIN-RAT LD50 (FMC MSDS); >5 GM/KG ORAL-RAT LD50
(FMC MSDS).

CARCINOGEN STATUS: NONE.

ACUTE TOXICITY LEVEL: SLIGHTLY TOXIC BY DERMAL ABSORPTION, INGESTION.

TARGET EFFECTS: NUISANCE DUST.

HEALTH EFFECTS AND FIRST AID

INHALATION:

CELLULOSE:

NUISANCE DUST.

ACUTE EXPOSURE- AIRBORNE CELLULOSE DUST IS REPORTED TO BE NONIRRITATING
AND NON-TOXIC. NO MORTALITY OCCURRED IN RATS AT THE MAXIMUM ATTAINABLE
CONCENTRATION.

CHRONIC EXPOSURE- REPEATED INTRATRACHEAL INSTILLATION RESULTED IN
PHYSIOLOGIC, HISTOLOGIC, AND MORPHOMETRIC EVIDENCE OF PULMONARY FIBROSIS
IN HAMSTER LUNGS.

FIRST AID- IT IS UNLIKELY THAT EMERGENCY TREATMENT WILL BE REQUIRED. IF
ADVERSE EFFECTS OCCUR, REMOVE FROM EXPOSURE, TREAT SYMPTOMATICALLY AND
SUPPORTIVELY, AND GET MEDICAL ATTENTION.

SKIN CONTACT:

CELLULOSE:

ACUTE EXPOSURE- STUDIES IN RABBITS INDICATE NO IRRITATION FOLLOWING
CONTACT. THE REPORTED LD50 WAS >2 GM/KG.

CHRONIC EXPOSURE- NO DATA AVAILABLE.

FIRST AID- IT IS UNLIKELY THAT EMERGENCY TREATMENT WILL BE REQUIRED.

IF ADVERSE EFFECTS OCCUR, WASH WITH LARGE AMOUNTS OF WATER AND SOAP AND GET MEDICAL ATTENTION.

EYE CONTACT:

CELLULOSE:

ACUTE EXPOSURE- STUDIES IN RABBITS INDICATE MINIMAL IRRITATION FOLLOWING CONTACT.

CHRONIC EXPOSURE- NO DATA AVAILABLE.

FIRST AID- WASH EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER OR NORMAL SALINE, OCCASIONALLY LIFTING UPPER AND LOWER LIDS, UNTIL NO EVIDENCE OF CHEMICAL REMAINS (APPROXIMATELY 15-20 MINUTES). GET MEDICAL ATTENTION IMMEDIATELY.

INGESTION:

CELLULOSE:

ACUTE EXPOSURE- THE REPORTED LD50 WAS >5 GM/KG.

CHRONIC EXPOSURE- HUMAN STUDIES INDICATE THAT UP TO 30 GM/DAY CAN BE TOLERATED AS A BULK LAXATIVE.

FIRST AID- IT IS UNLIKELY THAT EMERGENCY TREATMENT WILL BE REQUIRED.
IF ADVERSE EFFECTS OCCUR, TREAT SYMPTOMATICALLY AND SUPPORTIVELY AND GET MEDICAL ATTENTION.

ANTIDOTE:

NO SPECIFIC ANTIDOTE. TREAT SYMPTOMATICALLY AND SUPPORTIVELY.

REACTIVITY SECTION

REACTIVITY:

STABLE UNDER NORMAL TEMPERATURES AND PRESSURES.

INCOMPATIBILITIES:

CELLULOSE:

BROMINE PENTAFLUORIDE: FIRE AND EXPLOSION HAZARD.

FLUORINE: VIOLENT EXPLOSION.

HYDROGEN PEROXIDE: IGNITES SPONTANEOUSLY.

SODIUM HYPOCHLORITE: POSSIBLE EXPLOSION HAZARD.

SODIUM NITRATE: VIOLENT REACTION AT ELEVATED TEMPERATURES.

DECOMPOSITION:

THERMAL DECOMPOSITION PRODUCTS MAY INCLUDE TOXIC OXIDES OF CARBON.

POLYMERIZATION:

HAZARDOUS POLYMERIZATION HAS NOT BEEN REPORTED TO OCCUR UNDER NORMAL TEMPERATURES AND PRESSURES.

CONDITIONS TO AVOID

MAY BURN BUT DOES NOT IGNITE READILY. AVOID CONTACT WITH STRONG OXIDIZERS, EXCESSIVE HEAT, SPARKS, OR OPEN FLAME.

SPILLS AND LEAKS

OCCUPATIONAL-SPILL:

SWEEP UP AND PLACE IN SUITABLE CLEAN, DRY CONTAINERS FOR RECLAMATION OR LATER DISPOSAL. DO NOT FLUSH SPILLED MATERIAL INTO SEWER. KEEP UNNECESSARY PEOPLE AWAY.

PROTECTIVE EQUIPMENT SECTION

VENTILATION:

PROVIDE LOCAL EXHAUST VENTILATION AND/OR GENERAL DILUTION VENTILATION TO MEET PUBLISHED EXPOSURE LIMITS.

RESPIRATOR:

THE FOLLOWING RESPIRATORS ARE RECOMMENDED BASED ON INFORMATION FOUND IN THE PHYSICAL DATA, TOXICITY AND HEALTH EFFECTS SECTIONS. THEY ARE RANKED IN ORDER FROM MINIMUM TO MAXIMUM RESPIRATORY PROTECTION. THE SPECIFIC RESPIRATOR SELECTED MUST BE BASED ON CONTAMINATION LEVELS FOUND IN THE WORK PLACE, MUST NOT EXCEED THE WORKING LIMITS OF THE RESPIRATOR AND BE JOINTLY APPROVED BY THE NATIONAL INSTITUTE FOR OCCUPATIONAL SAFETY AND HEALTH AND THE MINE SAFETY AND HEALTH ADMINISTRATION (NIOSH-MSHA).

DUST AND MIST RESPIRATOR.

AIR-PURIFYING RESPIRATOR WITH A HIGH-EFFICIENCY PARTICULATE FILTER.

POWERED AIR-PURIFYING RESPIRATOR WITH A DUST AND MIST FILTER.

POWERED AIR-PURIFYING RESPIRATOR WITH A HIGH-EFFICIENCY PARTICULATE FILTER.

TYPE 'C' SUPPLIED-AIR RESPIRATOR OPERATED IN THE PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE OR CONTINUOUS-FLOW MODE.

SELF-CONTAINED BREATHING APPARATUS.

FOR FIREFIGHTING AND OTHER IMMEDIATELY DANGEROUS TO LIFE OR HEALTH CONDITIONS:

SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.

SUPPLIED-AIR RESPIRATOR WITH FULL FACEPIECE AND OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE IN COMBINATION WITH AN AUXILIARY SELF-CONTAINED BREATHING APPARATUS OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.

CLOTHING:

PROTECTIVE CLOTHING NOT REQUIRED. AVOID REPEATED OR PROLONGED CONTACT WITH THIS SUBSTANCE.

GLOVES:

PROTECTIVE GLOVES ARE NOT REQUIRED BUT RECOMMENDED.

EYE PROTECTION:

EMPLOYEE MUST WEAR SPLASH-PROOF OR DUST-RESISTANT SAFETY GOGGLES TO PREVENT EYE CONTACT WITH THIS SUBSTANCE.

EMERGENCY EYE WASH: WHERE THERE IS ANY POSSIBILITY THAT AN EMPLOYEE'S EYES MAY
BE EXPOSED TO THIS SUBSTANCE, THE EMPLOYER SHOULD PROVIDE AN EYE WASH
FOUNTAIN WITHIN THE IMMEDIATE WORK AREA FOR EMERGENCY USE.

AUTHORIZED BY- OCCUPATIONAL HEALTH SERVICES, INC.

CREATION DATE: 05/25/89

REVISION DATE: 10/09/90

TEXACO INC.

INDUSTRIAL HYGIENE, TOXICOLOGY, AND MATERIAL
SAFETY DATA SHEET

NOTE: NO REPRESENTATION IS MADE AS TO THE ACCURACY OF THE INFORMATION
HEREIN. SEE PAGE 7 FOR CONDITIONS UNDER WHICH DATA ARE FURNISHED.

Trade Name and Synonyms 00701 REGAL OIL R&O 46 Regal B	
Manufacturer's Name Texaco Inc.	Emergency Telephone No. (914) 831-3400 ext. 204
Address P.O. Box 509 Beacon, NY 12508	
Chemical Name and/or Family or Description Turbine Oils	
THIS PRODUCT IS CLASSIFIED AS: <u> X </u> NOT HAZARDOUS: <u> </u> HAZARDOUS BY DEFINITION NO.1: <u> </u> ON ATTACHED EXPLANATION SHEETS	
WARNING STATEMENT: NONE CONSIDERED NECESSARY	
OCCUPATIONAL CONTROL PROCEDURES	
Protective Equipment (Type)	
Eyes:	Chemical type goggles or face shield optional.
Skin:	Exposed employees should exercise reasonable personal cleanliness; this includes cleansing exposed skin areas several times daily with soap and water, and laundering or dry cleaning soiled work clothing at least weekly.
Inhalation:	None required if exposures are within permissible concentrations; see below.
Ventilation:	Adequate to meet component permissible concentrations.
Permissible Concentrations:	
Air:	None established for product; refer to page 4 for component permissible concentrations.
EMERGENCY AND FIRST AID PROCEDURES	
First Aid	
Eyes:	As with most foreign materials, should eye contact occur, flush eyes with plenty of water.
Skin:	Wash exposed areas with soap and water
Ingestion:	None considered necessary.
Inhalation:	None considered necessary.
Other instructions:	None.

B-72

PHYSIOLOGICAL EFFECTS:

Grade: 00701

Effects of Exposure

Acute:

Eyes: Causes minimal eye irritation. Transient minor irritation may be noted following initial contact.

Skin: Effects of dermal contact slight, if any.

Respiratory System: Believed to be minimally irritating if not in excess of permissible concentrations; see page 1.

Chronic: N.D.

Other: -

Sensitization Properties:

Skin: Yes — No — Unknown X

Respiratory: Yes — No — Unknown X

Median Lethal Dose (LD₅₀) (Species)

Oral: Believed to be >10 g/kg (rat); practically non-toxic

Inhalation: N.D.

Dermal: Believed to be >8 g/kg (rabbit); practically non-toxic

Other: N. D.

Irritation Index, Estimation of Irritation (Species)

Skin: Believed to be 0.13/8.0 (rabbit); minimally irritating

Eyes: Believed to be 2.33/110 (rabbit); slightly irritating

Symptoms of Exposure: See above

FIRE PROTECTION INFORMATION

Ignition Temp. °F: N.D.

Flash Point °F (Method): 400°F (COC)

Flammable Limits (%): Lower N.D.

Upper N.D.

Products Evolved When Subjected to Heat or Combustion:

Carbon monoxide, carbon dioxide, aldehydes and ketones, combustion products of nitrogen and sulfur.

Recommended Fire Extinguishing Agents And Special Procedures:

According to the National Fire Protection Association Guide, use water spray, dry chemical, foam, or carbon dioxide. Water or foam may cause frothing. Use water to cool fire-exposed containers. If a leak or spill has not ignited, use water spray to disperse the vapors and to provide protection for persons attempting to stop the leak.

Unusual or Explosive Hazards:

None.

ENVIRONMENTAL PROTECTION

Code
No. 00701

Waste Disposal Method:

Under RCRA, it is the responsibility of the user of products to determine, at the time of disposal, whether product meets RCRA criteria for hazardous waste. This is because product uses, transformations, mixture, processes, etc. may render the resulting material hazardous. (See Remarks for Waste Classification.)

Procedures in Case of Breakage or Leakage:

(Transportation Spills Call CHEMTREC (800) 424-9300)
Contain spill if possible. Wipe up or absorb on suitable material and shovel up.

Remarks:

Waste Classification: Product has been evaluated for RCRA characteristics and does not meet criteria of a hazardous waste if discarded in its purchased form.

PRECAUTIONS

NONE CONSIDERED NECESSARY

Requirements for Transportation, Handling and Storage:

Minimum feasible handling temperatures should be maintained. Periods of exposure to high temperatures should be minimized. Water contamination should be avoided.

DOT Proper Shipping Name: N.A.

DOT Hazard Class (if applicable): N.A.

CHEMICAL AND PHYSICAL PROPERTIES

Boiling Point (°F) N.D. Vapor Pressure N.D. (mmHg)

Specific Gravity .8735 (H₂O=1) Vapor Density N.D. (Air=1)

Appearance and Odor light pale

pH of undiluted product N.A.

Solubility N.D.

Percent Volatile by Volume N.D.

Evaporation N.D.

Viscosity 44.3 cSt @ 40 °C

Other -

Hazardous Polymerizations - Occur X Do not occur

The Material Reacts Violently With: (If others is checked below, see additional comments on page 6 for further details)

Air - Water - Heat - Strong Oxidizers X Others - None of These

COMPOSITION Code No. 00701

Chemical/Common Name	CAS No.	Exposure Limit	Range in %
Solvent-dewaxed heavy paraffinic petroleum distillates	64742650	5mg/m3 ACGIH (MIST) 5mg/m3 OSHA (MIST) 10mg/m3 STEL (MIST)	95.00 - 99.99

To the best of our knowledge, none of the above listed components is hazardous according to OSHA (1910.1200) or one or more state Right To Know lists.

PRODUCT SHIPPING LABEL

Code
No. 00701

00701 REGAL OIL R&O 46

NONE CONSIDERED NECESSARY

Chemical/Common Name	CAS No.	Range in %
Solvent-dewaxed heavy paraffinic petroleum distillates	64742650	95.00 - 99.99

To the best of our knowledge, none of the above listed components is hazardous according to OSHA (1910.1200) or one or more state Right-To-Know lists.

HMIS
Health : 0 Reactivity : 0
Flammability: 1 'Special : -

CAUTION: Misuse of empty containers can be hazardous. Empty containers can be hazardous if used to store toxic, flammable or reactive materials. Cutting or welding of empty containers might cause fire, explosion or toxic fumes from residues. Do not pressurize or expose to open flame or heat. Keep container closed and drum bungs in place.

HEALTH EMERGENCY TELEPHONE: (914) 831-3400 (EXT. 204)

Texaco Inc.
2000 Westchester Avenue
White Plains, New York 10650

B-76

For Additional Information Concerning:

Fuels/Lubricants/Antifreezes
call (914) 831-3400 (EXT. 204)
Chemicals
call (512) 459-8543
Transportation Spills
call CHEMTREC (800) 424-9300

ADDITIONAL COMMENTS

Code
No. 00701

TEXACO INTENDS TO COMPLY FULLY WITH PROVISIONS OF THE TOXIC SUBSTANCES CONTROL ACT
STATE OF MICHIGAN CRITICAL MATERIALS ACT (REVISED 1987)
No critical materials present.

To determine applicability or effect of any law or regulation with respect to the product, users should consult his legal advisor or the appropriate government agency. TEXACO DOES NOT UNDERTAKE TO FURNISH ADVICE ON SUCH MATTERS.

By R. T. Richards Title Mgr. Env. Conservation & Toxicology
Date 03-14-88 ☐ New ☒ Revised, Supersedes 11-27-85

INDUSTRIAL HYGIENE, TOXICOLOGY, AND MATERIAL SAFETY DATA SHEET

Q 3-23-90

DISCONTINUED

NOTE: NO REPRESENTATION IS MADE AS TO THE ACCURACY OF THE INFORMATION HEREIN. SEE PAGE 5 FOR CONDITIONS UNDER WHICH DATA ARE FURNISHED.

Trade Name and Synonyms 00547 REGAL OIL 78	
Manufacturer's Name Texaco Inc	Emergency Telephone No. (914) 831-3400 ext. 406
Address P.O. Box 509 Beacon, NY 12508	
Chemical Name and/or Family or Description Paraffinic Mineral Oil	
THIS PRODUCT IS CLASSIFIED AS: <u> X </u> NOT HAZARDOUS: <u> </u> HAZARDOUS BY DEFINITION NO.(S) <u> </u> ON ATTACHED EXPLANATION SHEET 4	
WARNING STATEMENT: NONE CONSIDERED NECESSARY.	
OCCUPATIONAL CONTROL PROCEDURES	
Protective Equipment (Type) Eyes: Chemical type goggles or face shield optional. Skin: Exposed employees should exercise reasonable personal cleanliness; this includes cleansing exposed skin areas several times daily with soap and water, and laundering or dry cleaning soiled work clothing at least weekly. Inhalation: None required if exposures are within permissible concentrations; see below. Ventilation Required: Normal	
Permissible Concentrations: Air: 5 mg/cubic meter of air for mineral oil mist averaged over an 8 hour daily exposure (ACGIH 1982).	
EMERGENCY AND FIRST AID PROCEDURES	
First Aid Eyes: As with most foreign materials, should eye contact occur, flush eyes with plenty of water. Skin: None considered necessary. Ingestion: None considered necessary. Inhalation: None considered necessary. Other Instructions: None.	

DISCONTINUED

ENVIRONMENTAL PROTECTION

Code
No. 00547

Waste Disposal Method:

Under RCRA, it is the responsibility of the user of products to determine, at the time of disposal, whether product meets RCRA criteria for hazardous waste. This is because product uses, transformations, mixture, processes, etc. may render the resulting material hazardous. (See Remarks for Waste Classification)

Procedures in Case of Breakage or Leakage:

Contain spill if possible. Wipe up or absorb on suitable material and shovel up.

Remarks:

Waste Classification: Product has been evaluated for RCRA characteristics and does not meet criteria of a hazardous waste if discarded in its purchased form.

PRECAUTIONARY LABEL

NONE CONSIDERED NECESSARY.

Requirements for Transportation, Handling and Storage:

Minimum feasible handling temperatures should be maintained. Periods of exposure to high temperatures should be minimized. Water contamination should be avoided.

DOT Proper Shipping Name: N.A.

DOT Hazard Class (if applicable): N.A.

CHEMICAL AND PHYSICAL PROPERTIES

Boiling Point (°F) N.D.Vapor Pressure N.D. (mmHg)Specific Gravity N.D. (H₂O=1)Vapor Density N.D. (Air=1)Appearance and Odor N.D.pH of undiluted product N.A.Solubility N.D.Percent Volatile by Volume N.D.Evaporation N.D. ()=1Viscosity N.D.Other -Hazardous Polymerizations Occur X Do not occur

The Material Reacts Violently With: (If Others is checked below, see Additional Comments on Page 4 for further details)

Air Water Heat Strong Oxidizers Others None of These

B-79

X

N.D. - Not Determined N.A. - Not Applicable
< Less Than > Greater Than

MATERIAL SAFETY DATA SHEET

Honeywell

Page 1 of 3

CORP ID #

DIV. ID # B-553

I. MATERIAL IDENTIFICATION:

TRADE NAME:

Lubricating Oil: #79329, #15261, #71042, #4020

MANUFACTURER:

Honeywell Inc., 1100 Virginia Drive, Ft. Washington, PA 19034

TELEPHONE NUMBER

(215) 641-4328

SYNONYMS:

Petroleum Oil

MATERIAL USE:

Lubricating Oil

APPEARANCE AND ODOR

Light colored mineral oil, bland odor.

II. HAZARDOUS INGREDIENTS

MATERIAL	%	TLV (UNITS)
Material		TLV: 5 Mg./Cu.M PEL: 5 Mg./Cu.M STEL: 10 Mg./Cu.M (As oil mist)
Mineral Oil	64742-65-0	> 60
Lubricant Additive Mixture:	Composition claimed proprietary by supplier	1 - 10

NOTE: See attachment on Carcinogenicity

III. HEALTH HAZARD INFORMATION

EFFECTS OF EXCESSIVE EXPOSURE	<p>Threshold limit values: See Section II</p> <p><u>Acute:</u> Inhalation - Avoid breathing product mist. Breathing mist in excess of the TLV may cause irritation of upper respiratory tract. Persons with chronic respiratory disease may show increased symptoms due to irritation.</p> <p><u>Skin:</u> Slight irritant to those persons with sensitive skin on prolonged contact.</p> <p><u>Eye:</u> Mild irritant. <u>Ingestion:</u> No significant effects known.</p> <p><u>Chronic:</u> Unknown for this product.</p>
EMERGENCY AND FIRST AID PROCEDURES	<p><u>EYE CONTACT:</u> Flush with water 15 minutes; consult a physician if irritation persists.</p> <p><u>SKIN CONTACT:</u> Wash with soap and water; consult a physician if irritation persists.</p> <p><u>INHALATION:</u> Remove to source of fresh air.</p> <p><u>INGESTION:</u> DO NOT INDUCE VOMITING; give liquids, consult physician. Product is mainly mineral oil.</p>

IV. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION	Required only if TLV for oil mist is exceeded.
PROTECTIVE GLOVES	Not normally needed. Rubber if skin is sensitive.
OTHER PROTECTIVE EQUIPMENT	Goggles if splashing.

B-80

N.D. - NOT DETERMINED

N.A. - NOT APPLICABLE

Honeywell

SPECIAL PROTECTION INFORMATION (CONT.)

ACTION

Exhaust if misting; otherwise general type is satisfactory.

SPECIAL PRECAUTIONS

HANDLING AND STORAGE PRECAUTIONS

Avoid contact with strong oxidizers.

D.O.T. CLASS

N/A

SPILL, LEAK, AND DISPOSAL PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED

Clean up with dry oil absorbant material. Product is mainly mineral oil and is easily separated from water. Keep out of sewers and streams. Not considered a pollutant if effective waste disposal methods are utilized.

WASTE DISPOSAL METHOD

Follow regulations for disposal of waste petroleum oil. May be incinerated under controlled conditions.

REACTIVITY DATA

STABILITY

UNSTABLE

STABLE

CONDITIONS TO AVOID

Strong oxidizers.

INCOMPATIBILITY (MATERIALS TO AVOID)

Strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS

Thermal oxides of carbon.

FIRE AND EXPLOSION DATA

FIRE AND EXPLOSION HAZARDS

Flash point deg. F (method used): 420 C.O.C.

PRECAUTIONS

None

SPECIAL FIRE FIGHTING PROCEDURES

None--treat as oil fire.

EXTINGUISHING MEDIA

Carbon Dioxide, foam, dry chemical.

NFPA RATING

FLAMMABLE LIMITS/% IN AIR

H - 0

F - 1

R - 0

LEL: N/D

UEL: N/D

PHYSICAL DATA

BOILING POINT

760mm Hg: High wide range

SOLUBILITY IN WATER

Insoluble

VAPOR PRESSURE

<.0001

mm Hg

VOLATILES:

Nil

% BY VOLUME

SPECIFIC GRAVITY

(H₂O = 1): 0.88

EVAPORATION RATE

Nil

VAPOR DENSITY

(AIR = 1): 12+

FLASH POINT

420 C.O.C.

INFORMATION SOURCES

The information contained herein is based upon current available scientific information and manufacturers data. The data and conclusions contained herein represent the majority of uses for this product. Abuse or unforeseen circumstances are not addressed. Information may be developed from time to time which may render the conclusions of this report obsolete. Honeywell makes no warranties to its customers, agents, employees, or contractors as to the applicability of this information to the users intended purpose or for the consequences for its use or misuse.

☐ NEW☒ REVISION

B-81

APPROVED BY
M. E. Nicholson
Industrial Hygienist

DATE
5-19-89

H O N E Y W E L L

Page 3 of 3

ATTACHMENT

MSDS

CARCINOGENICITY

NTP, IARC, or
OSHA listed

This oil does not appear on lists
published by: the National Toxicology
Program (NTP), the International Agency
for Research on Cancer (IARC) or OSHA
regulation as a cancer causing agent.

APPENDIX C
S&T CHEMICAL HYGIENE PLAN

S&TD CHEMICAL HYGIENE PLAN GENERAL TRAINING AND INFORMATION

1.0. General Information

OSHA has promulgated a final standard (29 CFR 1910.1450) covering occupational exposures to hazardous chemicals in laboratories. The standard basically applies to all laboratories that use hazardous chemicals in accordance with the definition of laboratory use and laboratory scale provided in the standard. It has been determined that the operations you perform as part of your normal work activities are covered by OSHA's Laboratory standard.

The new standard became effective on May 1, 1990 and requires employers covered by the standard to have completed an appropriate Chemical Hygiene Plan and commenced carrying out its provisions by January 31, 1991. OSHA has recognized that laboratories typically differ from industrial operations in their use and handling of hazardous chemicals and that a different approach than that found in substance-specific health standards, including OSHA's Hazard Communication Standard, is warranted to protect workers. Although many of the requirements of OSHA's Hazard Communication Standard and OSHA's standard covering Occupational Exposures to Hazardous Chemicals in Laboratories are similar, OSHA's new laboratory standard allows employers greater flexibility in the methods used to maintain employee exposures to hazardous chemicals below Permissible Exposure Limits specified in OSHA's substance-specific standards.

2.0. Contents of OSHA's Laboratory Standard and the S&TD Chemical Hygiene Plan

Where OSHA's standard covering Occupational Exposures to Hazardous Chemicals in Laboratories applies, the requirements of all other OSHA health standards in 29 CFR 1910, subpart Z are superseded, with the following exceptions:

The requirement for limiting employee exposures to specific Permissible Exposure Limits (PELs) still applies.

Prohibition of skin and eye contact where specified by any OSHA health standard still applies.

Where the action level (normally 1/2 the PEL) or PEL is routinely exceeded for an OSHA regulated substance, exposure monitoring and medical surveillance requirements of the OSHA substance-specific standard apply.

The employer is required to develop and implement a Chemical Hygiene Plan which is capable of (1) protecting employees from health hazards associated with hazardous chemicals in the laboratory and (2) maintaining employee exposures at or below applicable exposure limits. S&TD Standard Practice (SP) 2.1.2 implements S&TD's Chemical Hygiene Plan. You are encouraged to read and understand S&TD SP 2.1.2. If you are interested in reviewing OSHA's standard covering Occupational Exposures to Hazardous Chemicals in Laboratories, a copy of the standard and its appendices will be made available to you through your manager. If you are unsure how to access an S&TD Standard Practice Manual, contact your manager.

OSHA requires the Chemical Hygiene Plan to include the following elements:

Standard operating procedures relevant to safety and health considerations to be followed when laboratory work involves the use of hazardous chemicals.

Criteria the employer will use to determine and implement control measures to reduce employee exposure to hazardous chemicals, including engineering controls and the use of personal protective equipment and hygiene practices.

A requirement that fume hoods are operating properly and specific measures that will be taken to ensure proper and adequate performance of such equipment.

Provisions for employee information and training.

The circumstances under which a particular laboratory operation, procedure, or activity shall require prior approval from the employer before implementation.

Provisions for medical consultation and medical examinations as required by the standard.

Designation of personnel responsible for implementation of the Chemical Hygiene Plan, including the assignment of a Chemical Hygiene Officer.

Provisions for additional employee protection for work with particularly hazardous substances, including carcinogens, reproductive toxins, and highly toxic agents.

The Chemical Hygiene Plan must be reviewed at least annually and updated as necessary.

Employees covered by the laboratory standard must receive training and information to ensure they are apprised of the hazards of chemicals present in their work areas. This training is required to be provided at the time of an employee's initial assignment to a work area where hazardous chemicals are present and prior to assignments involving new exposure situations. Job-specific hazard communication training you have already received as part of your employment will be used to help fulfill the training requirements of OSHA's Laboratory standard.

Employees who work with hazardous chemicals must be provided with an opportunity to receive medical attention under the following conditions:

Whenever an employee develops signs or symptoms associated with a hazardous chemical to which the employee may have been exposed in the laboratory, the employee shall be provided with an opportunity to receive a medical examination.

Where exposure monitoring reveals an exposure level routinely above the

action level (or PEL when there is no action level), for an OSHA-regulated substance, medical surveillance shall be established as required by the particular standard.

Whenever an event takes place in the work area such as a spill, leak, explosion, or other occurrence resulting in the likelihood of a hazardous exposure, the employee shall be provided the opportunity for a medical consultation and medical evaluation if deemed necessary by the physician.

The following requirements related to hazard identification apply under OSHA's Laboratory standard:

Labels on incoming containers of hazardous chemicals shall not be removed or defaced.

MSDSs or other relevant health hazard information for hazardous chemicals used in the laboratory must be maintained in a manner that is readily accessible to laboratory employees.

If respirators are used to minimize exposure, a respiratory protection program consistent with EG&G Idaho Company Procedure 11.1 must be implemented.

3.0 Additional Requirements

In addition to the requirements of OSHA's standard covering Occupational Exposures to Hazardous Chemicals in Laboratories, EG&G Idaho laboratory workers are required to comply with supplemental requirements of DOE Headquarters, DOE-ID, EG&G Corporate, and EG&G Idaho. The requirements for secondary container labeling, maintenance of Hazardous Agent Inventories, and procurement of hazardous chemicals found in EG&G Idaho's Hazard Communication Program (Company Procedure 11.2) must be met. A summary of these additional requirements is outlined below. For details on the additional requirements, refer to CP 11.2 or contact your supervisor.

A current inventory of all hazardous chemical, physical, and biological agents present in the work area must be maintained in a manner that is readily accessible to employees. EG&G Idaho utilizes a computerized inventory tracking system. Managers are required to maintain current hardcopies of the computerized inventories in the work areas.

A qualified industrial hygienist must review and approve the purchase of any new hazardous chemicals an organization wishes to purchase. A Material Safety Data Sheet (MSDS) or equivalent reference materials must be obtained prior to the purchase of any new hazardous chemical so a adequate evaluation of potential risk associated with its use and recommendations for protective measures needed to minimize the risk can be made.

Procurement and Materials Services will not process requisitions for hazardous chemicals unless the material is listed on an organization's current Hazardous Agent Inventory or a qualified industrial hygienist has

signed the requisition approving purchase of the material.

Employees covered by OSHA's standard on Occupational Exposures to Hazardous Chemicals in Laboratories must receive refresher training annually.

Secondary containers in laboratories, including glassware, must be marked to show the contents of the container unless ALL of the following conditions are met:

The original container label shows the name of the material, the name and address of the manufacturer, and appropriate hazard warnings.

The material in the secondary container will not be used by or result in exposure to anyone other than the employee who performed the transfer.

The entire contents of the secondary container are used or returned to the original container or other properly labeled container during the same work shift the transfer occurred.

4.0 Exposure Limits for Hazardous Chemicals

Many hazardous chemicals have been assigned exposure limits at which it is believed nearly all workers may be repeatedly exposed day after day without adverse effects. OSHA calls their exposure limits PELs, or Permissible Exposure Limits. Another agency, the American Conference of Governmental Industrial Hygienists, calls their exposure limits TLVs, or Threshold Limit Values. Some chemical manufacturers also have recommended maximum exposure limits for chemicals they produce. Where exposure limits have been developed for hazardous chemicals, they are required to be entered on the MSDS for the substance. You are encouraged to reference the appropriate MSDS (or other reference materials if an MSDS is not available) if you have any question regarding the exposure limit or any other health hazard information for the chemicals you work with.

----- END OF FORMAL TRAINING OUTLINE -----

5.0 Applicable Details of S&TD's Chemical Hygiene Plan

FURTHER INSTRUCTIONS FOR PERSON PERFORMING THE TRAINING:

A copy of S&TD's Chemical Hygiene Plan is included with this training outline. All employees covered by OSHA's laboratory standard are required to be trained on applicable details of the written Chemical Hygiene Plan. S&TD's Chemical Hygiene Plan references several existing S&TD Standard Practices which laboratory workers should already be knowledgeable of; therefore, the amount of detail you go into on the Chemical Hygiene Plan will depend on your employee's current knowledge of the standard practices referenced in the Chemical Hygiene Plan.

At this point in the training, inform employees of the applicable details of S&TD's Chemical Hygiene Plan (S&TD SP 2.1.2).

EG&G IDAHO, INC. STANDARD PRACTICE SCIENCE & TECHNOLOGY	TITLE: CHEMICAL HYGIENE
	DATE: _____ No.: SP 2.1.2
	LEGEND: * (REV) - } (ADD)

REVISIONS SHOWN BY BAR BELOW

APPROVED: _____ S&T DEPARTMENT MANAGER
REVIEWED BY: _____ LAB OPERATIONS MGR. SAFETY ISRG CHAIRMAN

1.0 PURPOSE AND SCOPE

The chemical hygiene plan applies to all S&TD organizations engaged in the laboratory use of hazardous chemicals as defined by 29CFR1910.1450. S&TD operations which do not meet the definition of laboratory use of hazardous chemicals are exempted from this plan and must meet all requirements of EG&G Idaho's Hazard Communication Program (Company Procedure 11.2). Questions regarding which requirements a particular operation falls under should be directed to the S&TD Chemical Hygiene Officer.

Proper implementation of the chemical hygiene plan will assure S&TD employees are protected from health hazards associated with hazardous chemicals in the laboratory and maintain employees exposures to hazardous chemicals below established maximum safe levels, including ACGIH Threshold Limit Values and OSHA Permissible Exposure Limits.

2.0 RESPONSIBILITIES

Responsibilities for implementation of the Science and Technology Department's Chemical Hygiene Plan are listed as follows:

2.1 The S&T Department Manager Shall:

- 2.1.1 Assume ultimate responsibility for chemical hygiene and implementation of this chemical hygiene plan within the Science and Technology Department.

EG&G IDAHO, INC. STANDARD PRACTICE SCIENCE & TECHNOLOGY	TITLE: CHEMICAL HYGIENE
	DATE: _____ No.: SP 2.1.2
	LEGEND: * (REV) - } (ADD)

2.2 S&TD Group/Unit Managers shall:

- 2.2.1 Assume responsibility for implementing the requirements of this plan and all SPs referenced in this plan.
- 2.2.2 Ensure laboratory workers know and follow all requirements of this plan, appropriate protective equipment is available and in working order, and laboratory workers have received the training described in section VI of this plan.
- 2.2.3 Provide regular audits and appraisals of their laboratories to ensure Chemical Hygiene requirements are met.
- 2.2.4 Know and understand the current legal requirements concerning regulated substances in their laboratories.
- 2.2.5 Determine the required amounts and level of protective equipment required for their laboratories.

2.3 S&TD Laboratory workers shall:

- 2.3.1 Plan and conduct each operation in accordance with established procedures.
- 2.3.2 Develop good personal chemical hygiene habits.

2.4 S&TD Chemical Hygiene Officer shall:

- 2.4.1 Be appointed by the S&TD Laboratory Operations Manager. This position shall be held by the most senior level industrial hygienist within the S&TD Safety and Environment Unit.

EG&G IDAHO, INC. STANDARD PRACTICE SCIENCE & TECHNOLOGY	TITLE: CHEMICAL HYGIENE
	DATE: _____ No.: SP 2.1.2
	LEGEND: * (REV) - } (ADD)

- 2.4.2 Work with S&TD managers and laboratory workers to develop and implement appropriate chemical hygiene policies and practices.
- 2.4.3 Serve as a technical resource to assist managers and employees within the S&TD carry out their responsibilities of this plan.
- 2.4.4 Assist S&TD managers conduct audits and appraisals of their laboratories as requested.
- 2.4.5 Serve as a member of the Independent Safety Review Group as deemed necessary by the ISRG Chairman.
- 2.4.6 Know the current legal requirements concerning regulated substances.
- 2.4.7 Annually (or more often if deemed necessary) review and update, if needed, this chemical hygiene plan.

3.0 STANDARD OPERATING PROCEDURES

3.1 Standard operating procedures relevant to safety and health consideration to be followed when laboratory work involves the use of hazardous chemicals are described in the Science and Technology Standard Practices (SP) Manual. Specific SPs relevant to this chemical hygiene plan include:

- 3.1.1 SP 1.4.4 - Housekeeping Standard
- 3.1.2 SP 1.4.9 - Safety Practices for Welding and Allied Processes
- 3.1.3 SP 2.1.1 - Non-Radioactive Chemical Waste Disposal
- 3.1.4 SP 2.1.5 - Eye Protection and Protective Clothing
- 3.1.5 SP 2.1.6 - Laboratory Safety
- 3.1.6 SP 2.1.7 - Perchloric Acid Use
- 3.1.7 SP 2.1.8 - Laboratory Hood Use
- 3.1.8 SP 2.1.10 - Hydrofluoric Acid Use

4.0 CRITERIA FOR DETERMINING AND IMPLEMENTING CONTROL MEASURES TO REDUCE EXPOSURES TO HAZARDOUS CHEMICALS

4.1 Any one, or a combination of, the following methods shall be used to identify and evaluate potential exposures to hazardous chemicals during laboratory operations and implement control measures to reduce employee exposure:

EG&G IDAHO, INC. STANDARD PRACTICE SCIENCE & TECHNOLOGY	TITLE: CHEMICAL HYGIENE
	DATE: _____ No.: SP 2.1.2
	LEGEND: * (REV) - } (ADD)

- 4.1.1 Adherence to standard operating procedures listed in section III of this chemical hygiene plan.
- 4.1.2 Review of new or revised experiments by the S&TD Independent Safety Review Group as described in SP 1.4.3.
- 4.1.3 Completion of Job Hazard Analysis Forms by S&TD Industrial Hygiene Personnel as described in EG&G Company Procedure 11.9.
- 4.1.4 Previous or on-going air monitoring results obtained during the same or similar operations.
- 4.1.5 Formal and informal audits, appraisals and walkthrough surveys conducted by S&TD management, employees, industrial hygiene, safety, and waste coordinator personnel.

5.0 LABORATORY HOODS AND OTHER PROTECTIVE EQUIPMENT

- 5.1 Requirements for the use of laboratory hoods and other protective equipment, as well as specific measures that must be taken to ensure proper and adequate performance of such equipment, may be found in the following SPs:

- 5.1.1 SP 1.4.9 - Safety Practices for Welding and Allied Processes
- 5.1.2 SP 2.1.4 - Chemical Spill Control
- 5.1.3 SP 2.1.5 - Eye Protection and Protective Clothing
- 5.1.4 SP 2.1.6 - Laboratory Safety
- 5.1.5 SP 2.1.7 - Perchloric Acid Use
- 5.1.6 SP 2.1.8 - Laboratory Hood Use
- 5.1.7 SP 2.1.10 - Hydrofluoric Acid Use

6.0 EMPLOYEE INFORMATION AND TRAINING

All S&TD employees covered by this chemical hygiene plan shall receive the training outlined below at the time of initial assignment and prior to assignments involving new exposure situations.

EG&G IDAHO, INC. STANDARD PRACTICE SCIENCE & TECHNOLOGY	TITLE: CHEMICAL HYGIENE
	DATE: _____ No.: SP 2.1.2
	LEGEND: * (REV) - } (ADD)

6.1 S&TD Unit Managers, in conjunction with the Training Coordinator, and Chemical Hygiene officer shall develop and provide the following general training and information sessions:

6.1.1 The contents of 29CFR1910.1450 (Occupation Exposure to Hazardous Chemicals in Laboratories) and its appendices.

6.1.2 The location and availability of this chemical hygiene plan, and how employees covered by this plan can access it.

6.1.3 The OSHA Permissible Exposure Limits, ACGIH TLV's, or other recommended exposure limits for hazardous chemicals.

6.1.4 The contents and applicable details of this chemical hygiene plan.

6.2 S&TD Unit Managers, in conjunction with the S&TD Training Coordinator and Chemical Hygiene Officer shall develop and provide the following specific training and information sessions:

6.2.1 Signs and symptoms associated with exposure to hazardous chemicals used in their laboratories.

6.2.2 Methods and observations that may be used to detect the presence or release of a hazardous chemical. This will include, as applicable, past and present air monitoring conducted in the lab(s), the use of continuous monitoring devices, and visual appearance or odor of hazardous chemicals when being released.

6.2.3 The physical and health hazards of chemicals in the lab(s).

6.2.4 Procedures listed in section III of this chemical hygiene plan that are applicable to the unit manager's operations.

6.2.5 The location and availability of material safety data sheets or other reference materials containing information on the hazards, safe handling, storage, and disposal of hazardous chemicals in the lab(s).

EG&G IDAHO, INC. STANDARD PRACTICE SCIENCE & TECHNOLOGY	TITLE: CHEMICAL HYGIENE
	DATE: _____ No.: SP 2.1.2
	LEGEND: * (REV) - } (ADD)

7.0 PRIOR APPROVAL REQUIREMENTS FOR CERTAIN LABORATORY OPERATIONS

- 7.1 All new or revised experiments conducted in laboratories within the Science and Technology Department shall be submitted to the Independent Safety Review Group for review and approval prior to initiation as specified in SP 1.4.3.

8.0 MEDICAL CONSULTATIONS AND EXAMINATIONS

- 8.1 Requirements for reporting occurrences including actual or suspected exposures to hazardous chemicals, are described in SP 1.4.2 and EG&G Idaho Safety Manual, Section 3. In addition, employees covered under this plan shall be given the opportunity to receive medical attention, including any follow-up examinations which the examining physician deems necessary, under the following conditions:

8.1.1 Whenever an employee develops signs or symptoms associated with a hazardous chemical to which the employee may have been exposed in the laboratory, the employee shall be provided with the opportunity to receive an examination as deemed appropriate by a physician within the INEL Occupational Medical Program (OMP).

8.1.2 Whenever an event takes place in the work area such as a spill, leak, explosion, or other occurrence resulting in the likelihood of a hazardous exposure, the affected employee(s) shall be provided an opportunity for a medical consultation to determine the need for a medical examination.

8.1.3 Where exposure monitoring reveals an exposure level routinely above the action level or, in the absence of an action level, the PEL for an OSHA-regulated substance for which there are exposure monitoring and medical surveillance requirements, medical surveillance shall be established as required by the particular standard.

- 8.2 Unit managers are responsible for providing INEL OMP personnel with the following information (as applicable) in all cases when medical consultations and/or examinations are provided as required by this chemical hygiene plan:

EG&G IDAHO, INC. STANDARD PRACTICE SCIENCE & TECHNOLOGY	TITLE: CHEMICAL HYGIENE DATE: _____ No.: SP 2.1.2 LEGEND: * (REV) - } (ADD)
---	---

- 8.2.1 Name, job title, work location, supervisor's name, and work phone number
- 8.2.2 Substances/physical agents (e.g., noise) that are involved
- 8.2.3 When the employee was first exposed
- 8.2.4 The personal protective equipment to be used, (make and model), and when the employee was trained in its use
- 8.2.5 If exposed over action limits, submit the actual monitoring data
- 8.2.6 How many days per month the employee is expected to require personal protective equipment in the coming year
- 8.2.7 How much longer this employee will be exposed to this substance(s)
- 8.2.8 A description of the signs and symptoms of exposure that the employee is experiencing

8.3 The S&T Chemical Hygiene Officer shall assist the unit manager in gathering this information, as requested.

9.0 WORK INVOLVING PARTICULARLY HAZARDOUS SUBSTANCES

- 9.1 A Job Hazard Analysis (JHA) Form, as described in EG&G Idaho Company Procedure 11.9, shall be completed for all S&T operations involving the use of a particularly hazardous substance. Particularly hazardous substances include all chemicals meeting the definition of a carcinogen, reproductive toxin, or highly toxic material per OSHA's Hazard Communication Standard (29CFR1910.1200). Unit managers are responsible for contacting an industrial hygienist within the S&T Department to have a JHA form completed. The industrial hygienist shall review the proposed use of the material, complete a JHA form, and recommend any additional monitoring or control measures needed as described in CP 11.9. If the work involves the use of a carcinogen, where the industrial hygienist has determined the potential for significant employee exposure exists, a carcinogen control program as described in CP 11.6 shall be implemented to control exposures.

EG&G IDAHO, INC. STANDARD PRACTICE SCIENCE & TECHNOLOGY	TITLE: CHEMICAL HYGIENE
	DATE: _____ No.: SP 2.1.2
	LEGEND: * (REV) - } (ADD)

10.0 REFERENCES

- 10.1 Prudent Practices for Handling Hazardous Chemicals in Laboratories, National Research Council, 1981
- 10.2 29 CFR 1910, 1450, Occupational Exposure to Hazardous Chemicals in Laboratories
- 10.3 EG&G Idaho Company Procedures Manual, Sections 11.2, 11.6, 11.9
- 10.4 29 CFR 1910.1200, Hazard Communication
- 10.5 Science and Technology Department Standard Practice Manual
- 10.6 EG&G Idaho Resource Manual

END

**DATE
FILMED**

6 / 4 / 92