**Idaho
National
Engineering
Laboratory**

*Managed
by the U.S.
Department
of Energy*

EGG-WTD-9432 Vol 1
Revision 1
November 1991

APR 27 1992

INFORMAL REPORT

Use of Noninvasive Geophysical Techniques for the In Situ Vitrification Program

Volume 1: Literature Review

**Nicholas E. Josten
Steven T. Marts
Glen S. Carpenter**

*Work performed under
DOE Contract
No. DE-AC07-76ID01570*

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

This document contains new concepts or the author(s) interpretation of new calculations and/or measurements; accordingly, EG&G Idaho, Inc. is required by the United States Government to include the following disclaimer:

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights. References herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

EGG-WID---9432-Vol.1-Rev.1

DE92 012568

USE OF NONINVASIVE GEOPHYSICAL TECHNIQUES
FOR THE
IN SITU VITRIFICATION PROGRAM
VOLUME 1: LITERATURE REVIEW

Nicholas E. Josten
Steven T. Marts
Glen S. Carpenter

Published November 1991

Idaho National Engineering Laboratory
EG&G Idaho, Inc.
Idaho Falls, Idaho 83415

Prepared for the
U. S. Department of Energy
Office of Environmental Restoration and Waste Management
Under DOE Field Office, Idaho
Contract DE-AC07-76ID01570

MISSILE

als
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

USE OF NONINVASIVE GEOPHYSICAL TECHNIQUES
FOR THE
IN SITU VITRIFICATION PROGRAM
VOLUME 1: LITERATURE REVIEW

Approved By: W. E. Harrison Date: 11/4/91
W. E. Harrison, Manager
Geosciences Group

Prepared By: N. E. Josten Date: 10/30/91
N. E. Josten

Reviewed By: T. R. Wood Date: 10/31/91
T. R. Wood
Technical Reviewer

ABSTRACT

In situ vitrification (ISV) is a waste pit remediation technology that can potentially eliminate the need for pit excavation. The ISV program at the Idaho National Engineering Laboratory (INEL) funded this study to evaluate geophysical techniques that might be useful for performing detailed screening of the materials, soil conditions, and local geology of waste pits targeted for remediation. The evaluation focusses on a specific set of characterization objectives developed by ISV engineers. The objectives are based on their assessment of safety, environmental, and cost efficiency issues associated with the ISV process. A literature review of geophysical case histories was conducted and a geophysical survey was performed at the INEL simulated waste pit so that the evaluation could be based on demonstrable results. The literature review shows that all the ISV objectives are theoretically achievable because they involve physical properties (such as electrical conductivity, density, or magnetization) that can be sensed by geophysical instruments. However, most of the ISV objectives require substantially higher resolution than is achieved in typical waste site investigations, or than has been demonstrated by researchers using state-of-the-art techniques. The survey at the INEL simulated waste pit yielded useful, qualitative information on subsurface materials and boundaries; but quantitative information, such as depth, size, or composition of buried materials, was subject to significant uncertainty. For ISV, the usefulness of geophysical characterization depends both on the capabilities of geophysical methods and on an assessment of the amount of uncertainty that is acceptable. Based on a preliminary assessment of these factors, the location of trench boundaries and detection of massive metallic objects are the important achievable objectives using current technology. Other ISV objectives are either not routinely achievable, or cannot be achieved with satisfactory confidence levels. A peer review of this report substantiated these conclusions but stressed that conventional geophysical methods are not designed for the high level of characterization sought by ISV and that continued research is needed.

Document	<u>EGG-WTD-9432 Vol 1</u>
Revision No.	<u>1</u>
Date	<u>November 1991</u>
Page No.	<u>iv</u>

EXECUTIVE SUMMARY

This three-volume report documents the efforts and results of a one-year study of the capabilities and limitations of geophysics for characterization of buried heterogenous waste. The study was funded by the In Situ Vitrification (ISV) Program at the Idaho National Engineering Laboratory (INEL). The ISV Program recognizes the need to obtain information on soil conditions and buried materials prior to remediation. This information is useful for developing system design criteria to optimize the safety and efficiency of ISV remediation for particular applications.

ISV engineers generated a list of waste characterization objectives based on their assessment of (a) the potential environmental impacts of ISV and (b) the subsurface conditions that could adversely affect ISV operations or equipment. These objectives describe specific quantitative information needed to characterize the soils, waste materials, and local environment of a waste site targeted for remediation. The general capabilities of geophysical methods for obtaining this information are discussed in Volumes 1 and 2 of this report, based on a literature review and on testing selected standard methods at the INEL simulated waste pit. Volume 3 summarizes the capabilities and limitations of geophysics in the specific context of the ISV objectives.

The results of the literature review indicate that many of the ISV objectives for waste characterization are unprecedented. All of the objectives are theoretically achievable because they involve physical properties (such as electrical conductivity, density, or magnetization) that can be sensed by geophysical techniques. However, the ISV objectives require substantially higher resolution than is achieved in typical waste site geophysical investigations, or than is demonstrated by researchers using state-of-the-art techniques. The potential field geophysical methods (electrical, electromagnetic, and magnetic methods) are typically used qualitatively or semi-quantitatively and cannot provide information on size, location, composition, etc. of materials to the level of precision that is needed by ISV engineers. For most of these methods, the detailed theoretical

framework for quantitative interpretation has not yet been fully developed for complex heterogenous waste pit applications. This is an area of steady research in geophysics; some success is being realized using numerical modelling approaches, particularly for simple, isolated waste targets. Quantitative interpretation of wave propagation geophysical methods [seismic and ground penetrating radar (GPR)] is more straightforward than for potential field methods. Seismic and GPR have been used routinely to determine accurate depths to large targets, such as water table or bedrock. Under ideal conditions GPR is capable of imaging buried waste objects with great precision. However, GPR and seismic results are highly site-specific. The geophysical literature contains very few examples of methods that might be applicable to time-sequential monitoring of the ISV melt progression. Although the approach to time sequential monitoring is slightly different than for object location, the same limitations of geophysical methods apply.

EM31 ground conductivity, magnetics, and GPR were tested at the INEL simulated waste pit in an effort to evaluate the site- specific performance of these standard techniques. The results of this work substantiated the findings of the literature review. Pit boundaries, general locations of metallic waste, and bulk properties of waste could be approximately determined using the geophysical data. Very little quantitative information, such as depth, size, or specific composition of buried materials, could be confidently determined from the geophysical data using standard interpretation methods. GPR had extremely limited exploration depth and was of little value at the simulated waste pit due to nonoptimal soil conditions. The work at the simulated waste pit demonstrated the importance of integrating multiple geophysical data sets to perform qualitative evaluation of buried materials. However, this work also demonstrated the imprecise nature of standard geophysical data for detailed, quantitative evaluation of heterogeneous waste pits. Note that the simulated waste pit survey utilized standard sensors and interpretation techniques. There was no attempt to further evaluate state-of-the-art sensors or advanced analysis techniques, such as numerical modelling or other procedures, discussed in the literature review.

The literature review and the simulated waste pit survey showed that geophysical methods can be used to obtain information that is relevant to ISV characterization objectives, but this information is typically low resolution and is subject to varying amounts of uncertainty. For ISV, the usefulness of geophysically-derived information depends on an assessment of the amount of uncertainty that is acceptable. Based on an initial assessment of these factors, it is concluded that geophysics can be very effective for (a) locating horizontal and vertical trench boundaries and (b) detecting massive metallic objects. To a lesser extent, geophysics can be effective for (a) detecting large void spaces, (b) estimating waste overburden thickness, (c) estimating soil properties, and (d) melt monitoring and evaluation of the post-melt vitrified mass. It is doubtful that geophysics can be effective for (a) determining waste type within containers and (b) evaluating container integrity. These conclusions are somewhat specific to conditions at the INEL, and might be modified slightly in areas where GPR is highly effective.

Recommendations for research that might increase the effectiveness of geophysics include (a) developing better GPR antennas that are capable of imaging objects in nonoptimal soil conditions, (b) developing realistic numerical modelling capabilities for electrical, electromagnetic, and magnetic methods that can be used for quantitative interpretation of the complex data sets encountered at heterogeneous waste pits, (c) improving acoustic tomography for monitoring the active ISV melt, (d) studying the feasibility of mounting sensors on the advancing ISV electrodes to provide early warning when the melt approaches certain types of waste materials, and (e) evaluating the advantages and disadvantages of borehole geophysics. Research is ongoing for most of these topics.

A peer review of this report was undertaken to validate and expand the observations presented. Five reviewers from major U.S. and Canadian universities with respected geophysical programs submitted comments. The reviews presented an interesting range of views on the potential role of geophysics for hazardous waste site investigations, but uniformly substantiated the conclusion that geophysics cannot currently provide the

detailed characterization desired for ISV. Specifically, the reviewers felt that this report accurately assessed the state-of-practice in geophysics, but did not thoroughly document the state-of-the-art. The reviewers also stressed that higher resolution geophysical techniques will depend on higher quality, higher density data sets than are used for conventional work. With regard to future work, the reviewers strongly supported development of numerical modelling techniques. In addition, DC resistivity was recommended for further consideration, because the theoretical framework for interpreting DC resistivity data is more straightforward than for other electrical methods.

The major conclusions from this study are:

- All of the ISV objectives for waste sites screening are theoretically achievable because they involve physical properties (such as electrical conductivity, density, or magnetization) that can be sensed by geophysical techniques. However, most of the ISV objectives require substantially higher resolution than is achieved in typical waste site geophysical investigations, or than has been demonstrated by researchers using state-of-the-art techniques.
- A conventional geophysical survey of the INEL simulated waste pit demonstrated that useful, qualitative information on subsurface materials and boundaries can be obtained from the interpretation of complementary geophysical data sets. Quantitative information, such as depth, size, or composition of buried materials, can be estimated, but is subject to significant uncertainty.
- For ISV, the usefulness of geophysically-derived information requires an assessment of the amount of uncertainty that is acceptable.
- Based on an assessment of uncertainty requirements and the capabilities of geophysical techniques, two specific ISV

objectives are considered to be addressable with conventional technology: location of trench boundaries and detection of massive metallic objects.

- A peer review of this report uniformly substantiated the conclusion that conventional geophysics cannot currently provide the detailed characterization desired for ISV site screening. The reviewers also stressed that conventional methods were not designed for this level of characterization and that continued research was needed.

Document EGG-WTD-9432 Vol 1
Revision No. 1
Date November 1991
Page No. x

CONTENTS

VOLUME 1--LITERATURE REVIEW

ABSTRACT	iii
EXECUTIVE SUMMARY	v
INTRODUCTION	1
DESCRIPTION OF GEOPHYSICAL METHODS	3
Electromagnetic Induction	3
Magnetics	3
Ground Penetrating Radar	4
Resistivity	4
Seismic Refraction	5
Gravity	5
GEOPHYSICAL APPLICATIONS	6
Waste Material Characterization	6
Electromagnetic and Magnetic Methods	6
Radar Methods	8
Resistivity Methods	9
Seismic Methods	9
Gravity Methods	9
Waste Site Characterization	10
Electromagnetic and Magnetic Methods	10
Radar Methods	11
Resistivity Methods	12
Seismic Methods	12
Gravity Methods	13
Melt Monitoring and Postmelt Characterization	13
CONCLUSIONS	15
REFERENCES	17
APPENDIX A--ISV CHARACTERIZATION DATA NEEDS	A-1

CONTENTS

VOLUME 2--DEMONSTRATION AT THE SIMULATED WASTE PIT

ABSTRACT	iii
INTRODUCTION	1
SIMULATED WASTE PIT	3
FIELD METHODS	7
Magnetic Method	7
Electromagnetic Induction Method	8
Ground Penetrating Radar	9
RESULTS AND DISCUSSION	11
Mapping Buried Waste with the Magnetic Method	11
Mapping Buried Waste with the Electromagnetic Induction Method	12
Mapping Buried Waste Using Ground Penetrating Radar	18
Estimating Pit Boundaries, Cover Thickness, and Depth to Basalt	20
Identifying the Type of Materials Inside the Waste Pit	27
Evaluation of Electromagnetic Induction and Magnetic Methods	32
CONCLUSIONS	34
REFERENCES	36
APPENDIX A ELECTROMAGNETIC AND MAGNETIC DATA	A-1

FIGURES

1. Location of simulated waste pit	4
2. Arrangement of objects inside the simulated waste pit relative to data coordinate system	6
3. Vertical magnetic gradient map of the large object zone showing both historical and interpreted boundaries (units in gammas/meter). Shading indicates interpreted object boundaries	13

4. Vertical magnetic gradient profile along 8N showing the locations of simulated waste objects	14
5. Inphase electromagnetic data profile along 8E showing the locations of simulated waste objects	16
6. Inphase electromagnetic data map of the large object zone showing both historical and interpreted boundaries (values are unitless). Shading indicates interpreted object boundaries	17
7. Ground penetrating radar (300 Mhz) along line 13N showing reflection from pyramid stack of drums	21
8. Ground penetrating radar (300 Mhz) along line 7N showing historical and interpreted locations of steel casing	22
9. Ground penetrating radar (300 Mhz) along line 9N showing historical and interpreted locations of steel casing	23
10. Inphase electromagnetic data map of simulated waste pit showing both historical and interpreted boundaries (values are unitless). Shading indicates interpreted pit boundaries	24
11. Vertical magnetic gradient map of simulated waste pit showing both historical and interpreted boundaries (units in gammas/meter). Shading indicates interpreted pit boundaries	25
12. Quadrature phase electromagnetic data map of simulated waste pit showing historical boundaries (units in millimhos/meter)	28
13. Total magnetic field map of simulated waste pit showing historical boundaries (units in gammas).	31

TABLES

1. Description of zones in simulated waste pit	5
2. Depth estimates interpreted from total magnetic field data	27

CONTENTS

VOLUME 3--DISCUSSION AND RECOMMENDATIONS

ABSTRACT	iii
INTRODUCTION	1
BACKGROUND	2
EVOLUTION OF ISV OBJECTIVES FOR GEOPHYSICS	3
SAFETY AND EFFICIENCY ISSUES FOR ISV	4
GEOPHYSICS AND ISV	6
Uncertainty Factors for Potential Field Methods	7
Uncertainty Factors for Propagation Methods	8
CAPABILITIES AND LIMITATIONS OF GEOPHYSICS FOR ISV NEEDS	11
Trench Boundaries	11
Detection of Massive Metallic Objects	12
Void Spaces	13
Waste Type Within Containers	14
Overburden Thickness	15
Soil Density/Perosity	15
Post-Melt Evaluation	15
RECOMMENDED GEOPHYSICAL PROGRAM FOR SCREENING ISV SITES	17
RECOMMENDED RESEARCH DIRECTIONS	19
Improved Radar Antennas	19
Geophysical Modeling	19
Improved Tomographic Imaging	20
Electrode Mounted Sensors	20
Evaluation of Borehole Geophysical Methods	21

CONCLUSIONS	22
REFERENCES	23

Document EGG-WTD-9432 Vol 1
Revision No. 1
Date November 1991
Page No. xvi

USE OF NONINVASIVE GEOPHYSICAL TECHNIQUES FOR THE
IN SITU VITRIFICATION PROGRAM
VOLUME 1: LITERATURE REVIEW

INTRODUCTION

This document is the first volume of a three volume report to evaluate geophysical methods for use in the detailed characterization of waste pits. The study was funded by the In Situ Vitrification (ISV) Program to support the ISV waste pit remediation technology being developed at the Idaho National Engineering Laboratory (INEL). Geophysical waste characterization is being considered as a means to enhance the efficiency and cost effectiveness of the ISV process. Volume 1 documents the results of a broad-based literature review conducted to assess the capabilities and limitations of geophysical methods in common use and to identify promising new technologies. Volume 2 contains the results of geophysical surveys conducted at a simulated waste pit, and Volume 3 presents recommendations for the effective use of geophysical methods to support ISV.

The ISV process utilizes electrical currents to vitrify waste material in place, thus, eliminating the need for excavation and handling of potentially hazardous materials. For a particular application, ISV system design and process control depend on the type and arrangement of soils and waste materials within the targeted pit. A preliminary list of ISV waste characterization objectives is included in Appendix A of this volume. These objectives fall into three categories: (1) waste material characterization, to locate and identify individual waste forms within the waste pit; (2) waste site characterization, to delineate pit boundaries, soil layering, and bulk properties of pit soils; and (3) melt monitoring and postmelt characterization, to monitor the melt progress and determine physical properties of the vitrified waste.

Only noninvasive geophysical methods are discussed in this report. A number of borehole technologies may be applicable to waste pit characterization but would require drilling close to or into the waste pit, creating undesirable safety hazards. This review was also limited primarily to geophysical methods that could be available to support ISV tests planned for 1992. Developing technologies and several methods from other disciplines that could be adapted for ISV are mentioned as possible research directions, but they are not discussed in depth.

A brief description of the geophysical methods reviewed is given below. These methods are then discussed in three sections that correspond to the three categories of waste characterization listed in Appendix A.

DESCRIPTION OF GEOPHYSICAL METHODS

The geophysical methods reviewed for this report are limited to those in common use and for which equipment and procedures have been developed and are commercially available. The following is a brief overview of these methods aimed at providing the reader with an understanding of the basic sensitivities of these geophysical tools and the types of applications for which they are suited. For a more detailed overview the reader is referred to Benson et al. (1988) or EPA (1987).

Electromagnetic Induction

Electromagnetic induction methods provide a means to measure the electrical conductivity of soil or rock and to detect the presence of buried conductors such as metallic waste. In this method, a radiated electromagnetic field induces eddy currents in the earth. These eddy currents generate a secondary magnetic field which is detected as an output voltage by the electromagnetic instrument. The output voltage is a cumulative response to subsurface conductivities between the surface and the depth of investigation. In approximate order of importance, measured conductivities usually reflect the presence of metallic masses, amount and type of pore fluids, and the rock or soil composition.

Magnetics

Magnetometers measure the intensity of the earth's magnetic field. Variations of this field are produced by the distribution of naturally occurring iron minerals in soil or rock or by the presence of ferrous metal objects. The response of the magnetometer is proportional to the mass of ferrous material. Amounts of naturally occurring iron minerals in rocks and soils are normally very low compared with the mass of ferrous material contained in iron or steel objects. As a result, magnetic responses from ferrous metal objects are easy to identify in most survey situations. The

magnetometer does not respond to nonferrous metals such as lead, copper, brass and some types of stainless steel.

Ground Penetrating Radar

Ground penetrating radar uses radio waves to acquire subsurface information. An antenna radiates electromagnetic pulses downward into the ground. The pulses are reflected back from any natural or manmade material that creates a contrast in electrical permittivity. The time that the electromagnetic pulse takes to travel to the reflector and back is proportional to the depth of the reflector. Reflections are recorded continuously as the antenna is moved over the ground surface allowing subsurface objects and layers to be imaged in a form similar to a geologic cross section. Metallic objects, containers filled with water or air, and soil layers with high moisture contents are typically good radar reflectors. The depth of investigation for ground penetrating radar is a function of the frequency of the transmitted pulses and the conductivity of the earth materials; it is highly site specific.

Resistivity

The resistivity method is used to (a) measure the electrical resistivity of subsurface soil, rock, and ground water and (b) detect the presence of buried waste. An electric current is injected into the ground by a pair of electrodes, and the resulting voltage is measured using a second pair of electrodes. Electrical resistivity is the reciprocal of conductivity. Resistivity and electromagnetic methods are therefore quite similar in terms of the materials which they are sensitive to. The spacing of the electrodes may be changed to vary the depth of investigation.

Seismic Refraction

Seismic refraction is used to map depths to specific geologic horizons such as bedrock or the water table. Seismic waves are transmitted into the subsurface where they travel at different velocities depending on the type of soil or rock. The waves are refracted at interfaces between layers of different velocity, changing the wave travel path. The refracted waves are detected by geophones spaced along a line at the surface, and the travel time is recorded. Differences in travel time can be used to determine the depth and thickness of earth layers having different velocities. Velocity is very dependent on density, which in turn is dependent on porosity, fluid saturation, presence of fractures, and mineral composition.

Gravity

The gravity method is used to detect variations in the earth's gravity field. Gravity variations are caused by lateral changes in subsurface density and are proportional to the total volume of anomalously dense material. Because of this volume dependency and the relatively small range of naturally occurring densities, detectable gravity anomalies normally are associated with major discontinuities such as faults. Detection of small density changes, such as voids, requires exacting field procedures.

GEOPHYSICAL APPLICATIONS

Waste Material Characterization

This section addresses geophysical techniques used to detect and identify common waste materials buried in disposal pits. As outlined in Appendix A, the ISV information requirements for waste material characterization include estimates of the amount of buried metal, the type and arrangement of waste containers, and the contents of waste containers.

Qualitative geophysics (i.e., techniques for detecting and approximately locating waste objects) is routinely successful for detecting waste that possesses a material property that contrasts sharply with the pit soil. This condition is most often met by metallic objects that have conductivities and magnetic susceptibilities that are many orders of magnitude higher than common soils. Quantitative geophysics (i.e., techniques for determining parameters such as size, depth, volume, or spatial arrangement of waste objects) is significantly more challenging. Little progress has been documented on the use of quantitative techniques in the geophysical literature.

The following discussion focuses on the efforts and problems in quantitative interpretation because many of the ISV information requirements for waste material characterization are quantitative.

Electromagnetic and Magnetic Methods

Electromagnetic and magnetic methods are very effective for metal detection and have been widely used to locate buried metal objects in waste pits (Tyagi and Lord, 1983; Breiner, 1973; Benson et al., 1988; Annan et al., 1990; Walsh, 1989; Lord and Koerner, 1987). Advancements in quantitative interpretation techniques have come from researchers involved in detecting unexploded ordnance for the U. S. Department of Defense (Das et al., 1984; Das et al., 1990; McFee et al., 1990; Joma et al., 1987). These techniques,

for both magnetic and electromagnetic data, are based on mathematical simulation of the electric and magnetic fields created by simple metallic bodies. Field data from magnetometer or electromagnetic surveys over unknown buried objects are compared with simulated responses calculated for a variety of simple objects. The goal is to find a match between the field and simulated data. When this match is found, the depth, size, and orientation of the unknown buried object can be estimated by the corresponding properties of the simulated object.

The mathematical simulation or modeling approach to quantitative interpretation may be readily adapted for buried metallic wastes that have simple, symmetric forms such as isolated steel drums (Gilkeson et al., 1986; Barrows and Rocchio, 1990). However, for irregular objects like crushed drums, scrap metal, or buried vehicles, the theoretical calculations are difficult to apply. Also, the calculations do not account for interference effects resulting from multiple objects in close proximity. Interference effects may range from simple superposition of responses to complex interactions between adjacent objects. Because irregular and closely spaced metallic objects are commonplace in waste pits, a means for simulating these waste configurations must be developed before modeling techniques can be widely applied.

Two additional phenomena will be important in developing modeling methods for magnetic data: remanent magnetization and demagnetization. Strong remanent magnetization has been documented in metal drums (Barrows and Rocchio, 1990). The magnitude and direction of this magnetization is unpredictable. Remanent magnetization, therefore, constitutes an additional unknown in magnetic modeling. Demagnetization, a phenomenon that reduces the ability of objects to become magnetized once a certain metal concentration is reached, is a predictable factor but will further complicate simulation algorithms (Grant and West, 1965).

Radar Methods

Ground penetrating radar systems may provide the best opportunity for imaging subsurface waste forms with the resolution necessary for ISV remediation (Lord and Koerner, 1987). Most of the current development work in radar imaging deals with (a) advancing the theory for electromagnetic wave behavior in earth materials (Chang and Mei, 1985; Hill, 1988; Hill, 1989; Smith and Scott, 1989; Low and Greenfield, 1990); (b) designing signal antennas that balance resolution and depth penetration requirements (Blom et al., 1987; Michiguchi et al., 1988); and (c) postprocessing algorithms to improve the ability to interpret recorded reflections (Michiguchi et al. 1987; Raju and Moore, 1990).

Because of a number of absorption phenomena, the penetration of radar waves into a waste pit is limited by the electrical properties of the overburden (Oldhoeft, 1984). A high percentage of clay minerals in the soil, which is common at the INEL, causes rapid attenuation of radar waves. The result is a low signal to noise ratio and poor target imaging.

Two approaches are available to improve imaging of objects buried in highly absorptive soils: antenna design and data processing. Most of the controllable parameters that affect attenuation are antenna variables. Antenna choice will be a critical factor in determining the usefulness of radar data at INEL waste pits. In the reviewed case histories, trial and error was the most commonly used method for selecting antennas (Daniels, 1989; Benson et al., 1988).

A great deal of development effort is being concentrated on postprocessing of radar data. Much of the basic theory is borrowed from the petroleum industry, which has developed sophisticated techniques for extracting meaningful signals from reflection seismic data. Because of the high clay content typical of the INEL, processing methods that separate signal from noise are especially important. This separation is made based on

differentiating between the distinct patterns that characterize various types of signal and noise (Raju and Moore, 1990; Michiguchi et al., 1988). The best postprocessing results are achieved when noise problems are anticipated and acquisition parameters are chosen to both minimize noise and maximize the effectiveness of postprocessing schemes (Daniels, 1989).

Resistivity Methods

Resistivity methods are not commonly used for detecting or identifying buried metal objects primarily because these methods are more difficult to implement than electromagnetic methods (McNeil, 1980; Sweeney, 1984). Spontaneous potential and complex resistivity are variations of the resistivity method that have been used to detect the presence of electrochemical reactions (Oldhoeft, 1986; Ward, 1990). The presence of such reactions may be indicative of certain chemical processes such as active corrosion. However, these reactions are difficult to detect when superimposed on the response of buried conductive material.

Seismic Methods

Successful applications of surface seismic methods to waste material characterization were not found in the literature.

Gravity Methods

Gravity methods have received limited treatment in the literature on waste material characterization. The reported work has dealt mainly with the problem of void detection (Butler, 1984; Adams, 1984). This work has been quite successful for large voids such as mine tunnels.

Waste Site Characterization

This section addresses geophysical techniques used to investigate the waste pit environment. As outlined in Appendix A, ISV information requirements for waste site characterization include locating pit boundaries, estimating thickness of overburden and depth to bedrock, and determining bulk properties of pit soils.

Geophysical methods have been widely applied to characterize waste pit environments. While waste material characterization depends on material contrasts on a small scale, waste site characterization involves contrasts on a much larger scale. The waste pit environment is typically treated as a layered media: an upper layer of soil overburden, a layer corresponding to the bulk waste mass, a second layer of soil underburden, and bedrock. If contrasts in metal content, fluid content, porosity, and density between successive layers occur over a large area, geophysical responses can usually be observed with enough redundancy to allow mapping of the layers.

Bulk soil parameters that affect geophysical responses (i.e., conductivity, permittivity, and density) are related to fundamental soil parameters such as mineralogy, porosity, and fluid content. An integrated geophysical approach may be effective for determining these fundamental parameters. However, the geophysical literature contains few examples of this integrated approach.

The following discussion focuses on the basis for geophysical characterization of waste sites and the factors that determine the applicability of specific geophysical methods.

Electromagnetic and Magnetic Methods

Waste pit excavation will not normally create a soil property contrast that renders the excavation boundary detectable by magnetic or electromagnetic

methods. However, pit boundaries have been inferred based on patterns of electromagnetic or magnetic anomalies (Benson et al., 1988). The anomalies reflect the location of buried metal within the pit rather than the excavation boundaries. In many cases, these are coincident. Rules of thumb based on theoretical models of sharp vertical boundaries are used to locate the pit boundary with respect to the observed anomaly (Dobrin, 1976; Breiner, 1973). Boundaries located in this way are approximate because actual pit boundaries are rarely sharp, vertical contacts.

Electromagnetic methods can also be used to produce an estimate for bulk soil conductivity or electrical permittivity (Benson et al., 1988; Stewart et al., 1990). Soil geoelectric properties such as conductivity and permittivity are dependent on soil properties such as porosity, moisture content, and presence of contaminants (Oldhoeft, 1980; Hipp, 1974; McNeil, 1980).

Radar Methods

Pit boundaries can be imaged directly with radar data if pit excavation has resulted in the truncation of natural, horizontal soil horizons. When the soil horizons are good electromagnetic wave reflectors, boundaries can be located very precisely (Merin, 1990).

Radar methods have been successfully used for detailed mapping of bedrock beneath soil layers (Kidd et al., 1990).^a These interfaces can be strong reflectors. In some cases these interfaces are gradational and the bedrock reflection can be obscured. Bedrock reflections from beneath waste pits can be difficult to obtain because the presence of concentrated metal or large voids will limit the penetration of radar waves.^a Absorptive soils, especially soils with high clay content, can also limit the penetration of radar waves (Oldhoeft, 1984).

a. Additional information provided to EG&G Idaho, Inc. by ICF Technology Incorporated, Fairfax, Virginia.

Radar data can be used to determine bulk geoelectric properties of soils. The literature outlines several methods for computing soil parameters such as permittivity and conductivity from wave attenuation and delay data in layered media (Michiguchi, 1988; Daniels, 1989; Benson et al., 1988). Under controlled conditions, conductivity and permittivity data have been used to estimate porosity and water saturation (Michiguchi, 1988). Permittivity data can also be used to generate velocity-depth functions for layered media. A velocity-depth function is required to determine depths to reflectors such as drums or bedrock from radar data.

Depth of penetration is the primary concern in choosing antennas for mapping horizontal interfaces. Many of the recent developments in data processing for radar signal enhancement are designed for layered reflectors (Daniels, 1989). Enhancement of layered reflectors is often achieved at the expense of point reflectors. Again, it is important to have clear objectives and to anticipate noise sources when designing the radar survey.

Resistivity Methods

Resistivity methods have been used to determine thickness of cover and the vertical extent of waste in landfills (Ward, 1990). Resistivity surveys can estimate cover thickness and extent of waste to within 10% of their depth (Ross et al., 1990; Carpenter et al., 1990). Asch and Morrison (1989) and Barker (1990) present electrode configurations designed to reduce errors caused by near-surface lateral variations. Improved interpretation schemes may also improve the resolution (Sandberg, 1990).

Seismic Methods

Seismic refraction is particularly well suited for defining the shallow geologic environment of a waste pit. Abundant examples of bedrock mapping are

found in the literature.^a Recent advances in field techniques and interpretation methods, including the generalized reciprocal method, have made it possible to interpret data from rapidly varying interfaces such as the top of the basalt layer (Lankston, 1990; Palmer, 1980; Telford et al., 1976).

Gravity Methods

Pit boundaries may be defined using gravity methods in cases where pit excavation or the presence of voids within waste materials produces decreased bulk density within the pit. Gravity has also been used successfully to estimate the bulk density of waste mass within landfills and to map depth to bedrock beneath landfills (Roberts et al., 1989; Kick, 1989). These applications use theoretical modeling to derive quantitative results from the observed gravity anomalies.

Melt Monitoring and Postmelt Characterization

This section addresses geophysical methods for evaluating the active ISV process and the properties of the postmelt mass as outlined in Appendix A. Because ISV is an experimental technology, applications of geophysical techniques for this purpose were not found in the literature. Borehole geophysical methods may be the most promising approach to this problem; however, they are not considered in this report because they are intrusive techniques.

Because there is only a localized disturbance of the subsurface during ISV, noninvasive geophysical methods may be effective for melt monitoring and postmelt characterization using controlled, time sequential surveys. Geophysical methods that are sensitive to large subsurface volumes (e.g.,

a. Information provided to EG&G Idaho, Inc. by EBASCO Services Incorporated, Bellevue, Washington.

magnetic, electromagnetic, and gravity methods) are applied before, during, and after the ISV process. Because the bulk of the subsurface environment remains unchanged during and following the ISV melt, changes in geophysical responses can be attributed directly to the melt process. It may be possible to derive valuable information in this way even if the total response from the individual surveys is complex and poorly understood.

CONCLUSIONS

Following a broad-based literature review to assess the capabilities and limitations of geophysical methods to support waste characterization for the ISV Program, the following conclusions were made:

- Many of the ISV waste material characterization information needs are unprecedented in the geophysical literature.
- Under ideal soil conditions, radar methods can image individual objects within a pit. However, electrically conductive clayey soils can limit the effectiveness of radar for imaging waste materials.
- Commonly used electrical and magnetic techniques for investigating waste pits are qualitative or semiquantitative. These geophysical methods are effective for detecting and approximately locating metallic waste.
- Progress in quantitative interpretation of electrical and magnetic data is being achieved through the use of simulation or modeling techniques. By this method, theoretical responses are calculated for a variety of waste objects in an attempt to match responses recorded in field data. This is a promising direction of research. However, the algorithms in current use do not handle irregularly shaped objects or superposition effects caused by multiple objects in close proximity.
- Pit boundaries, overburden, underburden, and depth to bedrock can be quantitatively determined using radar and seismic methods. There are many documented examples using these geophysical methods. Accuracy is limited by uncertainties in electromagnetic and acoustic wave velocities for soils.

- Waste pit soil properties such as density, porosity, electrical conductivity, and fluid content are all interrelated and an integrated geophysical approach would be ideally suited for soil studies. However, examples of geophysical studies that attempt to quantify bulk soil properties are limited in number and narrow in scope.
- Examples of real-time monitoring of the vitrification process or postmelt characterization are absent from the literature.

REFERENCES

- Adams, W. M., 1984, "Gravimetric Detection and Mapping of Tunnels in Coral Reef Structure," Proceedings of the Second Technical Symposium on Tunnel Detection, Colorado School of Mines and U. S. Army, Golden, Colorado.
- Annan, A. P., J. E. Scaife, P. Giamou, 1990, "Mapping Buried Barrels with Magnetics and Ground Penetrating Radar," Expanded Abstracts, Vol. 1, Society of Exploration Geophysicists 16th Annual Meeting and Exposition, San Francisco, California, September 23-27, pp. 422-423.
- Asch, T. and H. F. Morrison, 1989, "Mapping and Monitoring Electrical Resistivity with Surface and Subsurface Electrode Arrays," Geophysics, 54, 2, 1989, pp. 235-243.
- Barker, R. D., 1990, "Improving the Quality of Resistivity Sounding Data in Landfill Studies," Geotechnical and Environmental Geophysics, Vol 2, Environmental and Groundwater, Society of Exploration Geophysicists.
- Barrows, L. and J. E. Rocchio, 1990, "Magnetic Surveying for Buried Metallic Objects," Ground Water Monitoring Review, 10, 3, pp. 204-211.
- Benson, R., R. A. Glaccum, M. R. Noel, 1988, Geophysical Techniques for Sensing Buried Wastes and Waste Migration, Dublin, Ohio: National Water Well Association.
- Blom, R. G., L. R. Schenck, R. E. Alley, 1987, "What Are the Best Wavelengths, Incidence Angles and Polarizations for Discrimination Among Lava Flows and Sedimentary Rocks: A Statistical Approach," IEEE Transactions on Geoscience and Remote Sensing, GE-25, 2, pp. 208-213.
- Breiner, S., 1973, Applications Manual for Portable Magnetometers, Sunnyvale, California: GeoMetrics.
- Butler, D. K., 1984, "Microgravimetric and Gravity Gradient Techniques for Detection of Subsurface Cavities," Geophysics, 49, pp. 1084-1096.
- Carpenter, P.J., R.S. Kaufmann, B. Price, 1990, "Use of Resistivity Soundings to Determine Landfill Structure," Ground Water, 28, 4, pp. 569-575.
- Chang, H. S. and K. K. Mei, 1985, "Scattering of Electromagnetic Waves by Buried and Partly Buried Bodies of Revolution," IEEE Transactions on Geoscience and Remote Sensing, GE-23, 4, pp. 596-605.
- Daniels, J. J., 1989, "Fundamentals of Ground Penetrating Radar," Proceedings of the Symposium on the Application of Geophysics to Engineering and Environmental Problems, Golden, Colorado, March 13-16, pp. 62-142.

- Das, Y., J. E. McFee, R. H. Chesney, 1984, "Determination of Depth of Shallowly Buried Objects by Electromagnetic Induction," IEEE Transactions on Geoscience and Remote Sensing, GE-23, 1, pp. 60-66.
- Das, Y., J. E. McFee, J. Toews, G. C. Stuart, 1990, "Analysis of an Electromagnetic Induction Detector for Real-Time Location of Buried Objects," IEEE Transactions on Geoscience and Remote Sensing, 28, 3, pp. 278-288.
- Dobrin, M. B., 1976, Introduction to Geophysical Prospecting, New York: McGraw-Hill, Inc.
- EPA (U. S. Environmental Protection Agency), 1987, A Compendium of Superfund Field Operations Methods, U. S. Environmental Protection Agency Document PB88-181557.
- Gilkeson, R. H., P. C. Heigold, D. E. Laymon, 1986, "Practical Application of Theoretical Models to Magnetometer Surveys on Hazardous Waste Disposal Sites--A Case History," Ground Water Monitoring Review, 6, 1, pp. 54-61.
- Grant, F. S. and G. F. West, 1965, Interpretation Theory in Applied Geophysics, New York: McGraw-Hill, pp. 306-381.
- Hill, D. A., 1988, "Electromagnetic Scattering by Buried Objects of Low Contrast," IEEE Transactions on Geoscience and Remote Sensing, 26, 2, pp. 195-203.
- Hill, D. A., 1989, "Near-Field Detection of Buried Dielectric Objects," IEEE Transactions on Geoscience and Remote Sensing, 27, 4, pp. 364-368.
- Hipp, J. E., 1974, "Soil Electromagnetic Parameters as Functions of Frequency, Soil Density, and Soil Moisture," Proceedings of the IEEE, 62, 1, pp. 98-103.
- Joma, H., J. Wadi, H. Tarish, 1987, "A New Technique for Detection and Height Estimation of Buried Metal Objects," Proceedings of IGARSS '87 Symposium, Ann Arbor, Michigan, May 18-21, pp. 435-437.
- Kick, J. F., 1989, "Landfill Investigations in New England Using Gravity Methods," Proceedings of the Symposium on the Application of Geophysics to Engineering and Environmental Problems, Golden, Colorado, March 12-15, pp. 339-353.
- Kidd, D. F., J. A. Kruppenbach, B. Ricketts, 1990, "Multidiscipline Approach to Very Shallow Exploration Targets," Expanded Abstracts, Vol. 1, Society of Exploration Geophysicists 16th Annual Meeting and Exposition, San Francisco, California, September 23-27, pp. 460-463.

- Lankston, R. W., 1990, "High Resolution Refraction Seismic Data Acquisition and Interpretation," Geotechnical and Environmental Geophysics, Vol. 1, S. H. Ward (ed.), Tulsa, Oklahoma: Society of Exploration Geophysicists, pp. 45-74.
- Lord, A. F. and R. M. Koerner, 1987, Nondestructive Testing (NDT) Techniques to Detect Contained Subsurface Hazardous Waste, Office of Research and Development, U. S. Environmental Protection Agency Report EPA/600/2-87/078.
- Low, S. R. and R. J. Greenfield, 1990, "Response of a Cylindrical Target: Implications for Ground Penetrating Radar," Expanded Abstracts, Vol. 1, Society of Exploration Geophysicists 16th Annual Meeting and Exposition, San Francisco, California, September 23-27, pp. 424-427.
- McFee, J. E., Y. Das, R. O. Ellingson, 1990, "Locating and Identifying Compact Ferrous Objects," IEEE Transactions on Geoscience and Remote Sensing, 28, 2, pp. 182-193.
- McNeil, J. D., 1980, Electromagnetic Terrain Conductivity Measurement at Low Induction Numbers, Geonics Limited, Mississauga, Ontario, Technical Note 6.
- Merin, I. S., 1990, "Identification of Previously Unrecognized Waste Pits Using Ground Penetrating Radar and Historical Aerial Photographs," National Water Well Association 4th Outdoor Action Conference, Las Vegas, Nevada, May 13-17.
- Michiguchi, Y. et al., 1987, "Development of Signal Processing Methods for Imaging Buried Pipes," IEEE Transactions on Geoscience and Remote Sensing, GE-25, 1, pp. 11-15.
- Michiguchi, Y. et al., 1988, "Advanced Subsurface Radar System for Imaging Buried Pipes," IEEE Transactions on Geoscience and Remote Sensing, 26, 6, pp. 733-740.
- Oldhoeft, G. R., 1980, "Electrical Properties of Rocks," in Physical Properties of Rocks and Minerals, by Y. S. Touloukian, W. R. Judd, R. F. Roy (eds.), New York: McGraw-Hill, pp. 257-330.
- Oldhoeft, G. R., 1984, "Application and Limitations of Ground Penetrating Radar," Expanded Abstracts, 54th Annual International Meeting and Exposition of the Society of Exploration Geophysicists, Atlanta, Georgia, December 2-6, pp. 147-148.
- Oldhoeft, G. R., 1986, "Direct Detection of Hydrocarbons and Organic Chemicals with Ground Penetrating Radar and Complex Resistivity," Proceedings of the NWWA Conference on Petroleum Hydrocarbons and Organic Chemicals in Ground Water Prevention, Detection, and Restoration, Dublin, Ohio, April 16-18.
- Palmer, D., 1980, The Generalized Reciprocal Method of Seismic Refraction Interpretation, Tulsa, Oklahoma: Society of Exploration Geophysicists.

- Raju, G. and R. K. Moore, 1990, "A Matched-Filter Technique for Removing Hyperbolic Effects Due to Point Scatterers: Simulation and Application on Antarctic Radar Data," IEEE Transactions on Geoscience and Remote Sensing, 28, 4, pp. 726-729.
- Roberts, R. L., W. J. Hinze, D. I. Leap, 1989, "A Multi-Technique Geophysical Approach to Landfill Investigations," Proceedings of the Third National Outdoor Action Conference, Orlando, Florida, pp. 797-811.
- Ross, H. P., C. E. Mackelprang, P. M. Wright, 1990, "Dipole-Dipole Electrical Resistivity Surveys at Waste Disposal Sites in Northern Utah," Geotechnical and Environmental Geophysics, Vol. 2, Environmental and Groundwater, S. H. Ward (ed.), Tulsa, Oklahoma: Society of Exploration Geophysicists.
- Sandberg, S. K., 1990, "Resolution Improvement in Geoelectric Soundings Applied to Groundwater Investigations," Society of Exploration Geophysicists 16th Annual International Meeting and Exposition, San Francisco, California, September 23-27.
- Smith, G. S. and W. R. Scott, 1989, "A Scale Model for Studying Ground Penetrating Radars," IEEE Transactions on Geoscience and Remote Sensing, 27, 4, pp. 358-363.
- Stewart, D., W. L. Anderson, T. P. Grover, V. F. Labson, 1990, "New Instrument and Inversion Program for Near-Surface Mapping: High Frequency EM Sounding in the Frequency Range 300 kHz to 30 MHz," Expanded Abstracts, Vol. 1, Society of Exploration Geophysicists 16th Annual Meeting and Exposition, San Francisco, California, pp. 410-412.
- Sweeney, J. J., 1984, "Comparison of Electrical Resistivity Methods for Investigation of Ground Water Conditions at a Landfill Site," Ground Water Monitoring Review, 4, 1, pp. 52-59.
- Telford, W. M., L. P. Geldart, R. E. Sheriff, D. A. Keys, 1976, Applied Geophysics, New York: Cambridge University Press.
- Tyagi, S. and A. E. Lord, Jr., 1983, "Use of a Proton Precession Magnetometer to Detect Buried Drums in Sandy Soil," Journal of Hazardous Materials, 8, pp. 11-23.
- Walsh, D. C., 1989, "Surface Geophysical Exploration for Buried Drums in Urban Environments: Applications in New York," Proceedings of the Third National Outdoor Action Conference, Orlando, Florida, pp. 935-949.
- Ward, S. H. (ed.), 1990, "The Resistivity and Induced Polarization Methods," Geotechnical and Environmental Geophysics, Vol. 1, Review and Tutorial, Society of Exploration Geophysicists, 1990.

APPENDIX A
ISV CHARACTERIZATION DATA NEEDS

Appendix A contains a preliminary list of in situ vitrification (ISV) characterization needs. This list was compiled by ISV researchers to serve as a starting point for a quality improvement process aimed at refining these needs.

Table A-1. ISV data needs potentially met through use of geophysical methods

<u>Type of Information</u>	<u>Why Needed^a</u>	
Waste Material Characterization		
Amount of metal		
Per unit volume	PC,M/EA	Predict/control of melting - shorting and melt geometry issues
	PE,PC,M/EA	Predict/control metals pooling, concentration of fissile materials
Size of metal objects larger than drum	PC,M/EA	Predict/control of melting - shorting, melt geometry, and melt channeling issues. Also product quality (degree of incorporation), equipment placement.
Electrical conductivity	PC,M/EA	Predict/control of melting - shorting, melt geometry, and melt channeling issues
Spatial arrangement and location of waste containers and metal objects		
Orientation	PC,M/EA	Predict/control off-gas release Predict/control of melting - shorting, melt geometry, and melt channeling issues
Interrelationship/density (within container type)		
Stacked/random	PC,M/EA	Predict/control off-gas release Predict/control of melting - shorting, melt geometry, melt channeling issues

Table A-1. (continued)

<u>Type of Information</u>	<u>Why Needed^a</u>	
Distance separating		
Horizontal	PC,M/EA	Predict/control off-gas release Predict/control of melting - shorting, melt geometry, melt channeling issues
Vertical	PC,M/EA	Predict/control off-gas release Predict/control of melting - shorting, melt geometry, melt channeling issues
Distribution of container types		
Horizontal	PC,M/EA	Predict/control off-gas release Predict/control of melting - shorting, melt geometry, melt channeling issues
Vertical	PC,M/EA	Predict/control off-gas release Predict/control of melting - shorting, melt geometry, melt channeling issues
Locations (horizontal, vertical planes)		
Metal objects larger than drum	PC,M/EA	Predict/control off-gas release Predict/control of melting - shorting, melt geometry, melt channeling issues
Waste containers	PC,M/EA	Predict/control off-gas release Predict/control of melting - shorting, melt geometry, melt channeling issues

Table A-1. (continued)

<u>Type of Information</u>	<u>Why Needed*</u>	
Density/voids		
Soil/waste ratio with depth	PC, M/EA	Predict/control of melting - shorting, melt geometry, melt channeling issues. Also sidewall collapse/exposed waste, subsidence, surface settlement, and product quality issues.
Void space		
Size	PC, M/EA	Predict/control of melt geometry and channeling issues. Also sidewall collapse/exposed waste, subsidence, and surface settlement.
Density per unit volume	PC, M/EA	Predict/control of melt geometry and channeling issues. Also sidewall collapse/exposed waste, subsidence, and surface settlement.
Location	PC, M/EA	Predict/control of melt geometry and channeling issues. Also sidewall collapse/exposed waste, subsidence, and surface settlement.
Within containers	PC, M/EA	Predict/control of melt geometry and channeling issues. Also sidewall collapse/exposed waste, subsidence, and surface settlement. Predict/control off-gas release. Predict/control migration of contaminants.

Table A-1. (continued)

<u>Type of Information</u>	<u>Why Needed^a</u>	
Waste type within containers		
Liquid	PC, M/EA	Predict/control off-gas release. Predict/control migration of contaminants, contaminant retention.
Concrete	PC, M/EA	Predict/control off-gas release. Predict/control migration of contaminants, contaminant retention.
Ceramic	PC, M/EA	Predict/control off-gas release. Predict/control migration of contaminants, contaminant retention.
Sludge	PC, M/EA	Predict/control off-gas release. Predict/control migration of contaminants, contaminant retention.
Metal scrap	PC, M/EA	Predict/control of melting - shorting, melt geometry, and melt channeling issues. Predict/control migration of contaminants, contaminant retention.
Empty	PC, M/EA	Predict/control melt geometry, channeling. Also sidewall collapse/exposed waste, subsidence, and surface settlement. Predict/control migration of contaminants.

Table A-1. (continued)

<u>Type of Information</u>	<u>Why Needed^a</u>	
Combustibles	PC, M/EA	Predict/control off-gas release. Predict/control migration of contaminants, contaminant retention.
Special case (reactor shielding, dog paws, etc.)	PC, M/EA	Predict/control off-gas release. Predict/control of melting - shorting, melt geometry, and melt channeling issues. Predict/control migration of contaminants.
Mixtures	PC, M/EA	
Waste container type		
Drum	PC, M/EA	Predict/control of melting - shorting, melt geometry, and melt channeling issues.
Wooden box	PC, M/EA	Predict/control off-gas release. Predict/control melt geometry, channeling.
Large metal objects (tanks, engines, trucks, etc.)	PC, M/EA	Predict/control of melting - shorting, melt geometry, and melt channeling issues.
Other	PC, M/EA	
Waste container integrity		
Degree of corrosion	PC, M/EA	Predict/control off-gas release. Predict/control migration of contaminants.

Table A-1. (continued)

<u>Type of Information</u>	<u>Why Needed^a</u>	
Degree of compression - see void space		
Leakage	PC, M/EA	Predict/control off-gas release. Predict/control migration of contaminants.
Waste Site Characterization		
Local geology		
Depth to basalt	PC, M/EA	Predict/control melt growth/extent. Predict/control migration of contaminants.
Overburden depth	PC, M/EA	Predict/control melt growth/extent. Predict/control migration of contaminants, contaminant retention.
Underburden depth	PC, M/EA	Predict/control melt growth/extent. Predict/control migration of contaminants.
Soil properties (within pit/trench)^b		
Electrical conductivity	PC, M/EA	Predict/control melt growth/extent.
Density	M/EA	Predict/control melt growth/extent. Predict/control migration of contaminants.
Porosity	M/EA	Predict/control melt growth/extent. Predict/control migration of contaminants.

Table A-1. (continued)

<u>Type of Information</u>	<u>Why Needed^a</u>	
Pit/trench boundaries		
Depth	PC, M/EA	Predict/control melt growth/extent. Predict/control migration of contaminants.
Horizontal	PC, M/EA	Predict/control melt growth/extent. Predict/control migration of contaminants.
Water content		
Overburden	PC, M/EA	Predict/control off-gas release, melt rate. Predict/control migration of contaminants, contaminant retention.
Waste zone	PC, M/EA	Predict/control off-gas release, melt rate. Predict/control migration of contaminants, contaminant retention.
Underburden	PC, M/EA	Predict/control off-gas release. Predict/control migration of contaminants.
Real-time Monitoring of Vitrification Process		
Extent of melt	PC, M/EA	Predict/control melt geometry, melt channeling, melt extent, and degree of continuity with previous melts. Also can guide process control of subsidence issue.
Degree of incorporation of waste forms in melt	PC	Product quality

Table A-1. (continued)

<u>Type of Information</u>	<u>Why Needed^a</u>
Post-melt Characterization^c	
Physical properties of vitrified waste	
Phases (glass phases, residual waste phases)	
Spatial distribution	
Density	PE
Location	PE
	PE
Product quality	Product quality
	Product quality
	Product quality
Fractures	
Size	PE
Extent	PE
Location	PE
	Product quality - mechanical durability
	Product quality - mechanical durability
	Product quality - mechanical durability
Extent of melt	
Relative to waste	PE, PC ^d , M/EA
Relative to basalt	PE, PC ^d , M/EA
Absolute	PE, PC ^d , M/EA
Product quality - extent of treatment	
Product quality - extent of treatment	
Product quality - extent of treatment	

a. PC = process control
M/EA = modeling/engineering analysis
PE = product evaluation

Table A-1. (continued)

b. Information on soil properties for overburden and underburden may also be needed.
c. Routine characterization requirements are yet to be defined. Currently, it is believed that phase change information has a low priority while fracture data, which is related to mechanical durability assessments(s), has a higher priority. Importance of mechanical durability increases if product is to be removed for disposal. Extent of melt has a high priority. Information on chemical durability could be obtained from core drilling.
d. Contiguous melt issue

END

DATE
FILMED

6 104192