RECEIVED
APR 12 1993
OSTI

NEURAL NETWORK APPROACHES TO TRACER
IDENTIFICATION AS RELATED TO PIV RESEARCH

A Thesis

by

CHARLES HENRY SEELEY JR.

Submitted to the Office of Graduate Studies of
Texas A&M University
in partial fulfillment of the requirements for the degree of
MASTER OF SCIENCE

December 1992

Major Subject: Nuclear Engineering

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

FG02-88ER12813

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

ABSTRACT

Neural Network Approaches to Tracer Identification

as Related to PIV Research. (December 1992)

Charles Henry Seeley Jr., B.S., Texas A&M University

Chair of Advisory Committee: Dr. Yassin Hassan

Neural networks have become very powerful tools in many fields of interest. This thesis examines the application of neural networks to another rapidly growing field, flow visualization.

Flow visualization research is used to experimentally determine how fluids behave and to verify computational results obtained analytically. A form of flow visualization, particle image velocimetry (PIV), determines the flow movement by tracking neutrally buoyant particles suspended in the fluid. PIV research has begun to improve rapidly with the advent of digital imagers, which can quickly digitize an image into arrays of grey levels. These grey level arrays are analyzed to determine the location of the tracer particles. Once the particles positions have been determined across multiple image frames, it is possible to track their movements, and hence, the flow of the fluid.

This thesis explores the potential of several different neural networks to identify the positions of the tracer particles. Among these networks are Backpropagation, Kohonen (counter-propagation), and Cellular. Each of these algorithms were employed in their basic form, and training and testing were performed on a synthetic grey level array. Modifications were then made to them in attempts to improve the results.

The backpropagation learning algorithm used on multi-layer Perceptrons proved capable of identifying different sizes of particles. Unfortunately, when applied to an entire image array, with many particles scattered in it, it could not identify the centroids.

A form of counter-propagation was employed in which a competition, or Kohonen, layer was used to classify the grey level spots, and an upper backpropagation layer was used to identify which class corresponded to which size of particle. Many variations were tested. One of these competition networks performed well at recognizing individual spots. When applied to a synthetic image array with multiple spots it did not function as well. However, it did classify the output in such a way that a conventional fortran code was capable of extracting the centroids of all of the synthetic spots. This network was then applied to an image taken from a previous experiment. It performed as well as a global thresholding algorithm.

The cellular network was the least successful of the three examined. It requires a lot of working memory, and the training used, annealing, required inordinate amounts of time. Due to the training limitations, it was not fully tested.

All of these networks require further study. It was found during this thesis work that subtle changes in the design or parameters could produce profound changes in the results. It is believed that all of these networks have potential and could produce accurate results if the right modifications were made. However, at this point the competition networks performed the best at identifying the particles from grey level data.

TABLE OF CONTENTS

CHAPTER	Page
I INTRODUCTION	1
I.1 History of Neural Networks	1
I.2 History of Flow Visualization	4
I.3 Merging Two Fields	11
II PARTICLE IMAGE VELOCIMETRY	14
II.1 Overview	14
II.2 Experimental Setup	15
II.3 Standard Methods for Tracer Seed Identification	20
II.4 Thresholding Bubble Coronas	26
II.5 Tracking Methods	30
III THE BASIC NEURON	32
III.1 The Biological Neuron	32
III.2 The Artificial Neuron	36
IV BACKPROPAGATION	41
IV.1 Background	41
IV.2 Architecture	42
IV.3 Training	44
IV.4 Testing	48
IV.5 Adjusted Input Vector and a Second Hidden Layer	50
V KOHONEN SELF-ORGANIZING MAPS AND COUNTERPROPAGATION	57
V.1 Background	57
V.2 Traveling Salesman Problem	58
V.3 Architecture for Counterpropagation	61
V.4 Testing	63
VI CELLULAR NETWORKS	73
VI.1 Background	73
VI.2 Annealing	74
VI.3 Cellular Architecture	75

CHAPTER	Page
VI.4 Testing of Cellular	77
VII CONCLUSIONS	83
VII.1 Particle Image Velocimetry	83
VII.2 Backpropagation	84
VII.3 Kohonen Networks	85
VII.4 Cellular Networks	86
REFERENCES	87
VITA	95

LIST OF FIGURES

Figure	Page
1 Step Flow Setup	17
2 Air-Water Interface Setup	18
3 Rising Bubble Experiment	19
4 Step Flow Image (grey levels multiplied by 4)	21
5 Channel Flow Image	22
6 Bubbly Flow Image	23
7 Example of Global Thresholding	24
8 Example of Connectivity	24
9 Example of Smoothing	25
10 Grey levels along a line at $y = 824$ and a global threshold of 10	27
11 Binary Image Produced by Using a Global Threshold of 10	28
12 $\frac{1}{\sqrt{2}}$ Functions Applied to Figure 10.	29
13 Binary Image Produced Using a Global Threshold of 10 and Radial $\frac{1}{\sqrt{2}}$ Functions	30
14 Biological Neuron	33
15 Biological Neuron Potentials	34
16 Artificial Neuron Model	37
17 Transfer Functions	39
18 Multi-layer Perceptron Network	43
19 First Training Set Applied to Backpropagation Network	46
20 Example of Spot Consolidation	49

Figure	Page
21 Test Image	50
22 Output After First Training	51
23 Vectorizing the Input Matrix	52
24 <i>rms</i> Value Produced for an η Value of 0.87	54
25 Results Produced During Training Altered Architecture	55
26 Output from Second Architecture	56
27 Affect of Learning Parameter α	59
28 Output of Traveling Student Problem	62
29 Counterpropagation Network	63
30 Output from Competition Network, before Spot Consolidation	66
31 Output from Competition Network, after Spot Consolidation	67
32 Step Flow Image: Centroids Found by Conventional Methods	68
33 Step Flow Image: Centroids Found using Competition Network	69
34 Step Flow Image: Centroids Found using Competition Network, Trained on Faint Spots	70
35 Step Flow Image (100 x 100): Comparison of Methods	71
36 Example of Annealing	76
37 Dynamic Model Neuron	77
38 Cellular Network	78
39 Symmetrically Applied Weights	79
40 Annealing of the Cellular Network	82

CHAPTER I

INTRODUCTION

I.1 History of Neural Networks

This research brings together two entirely different fields of study, Neural Networks and Flow Visualization. Although both fields have seen significant expansion in the 1980's, their foundations have been around since the 1800's (Rogers and Kabrisky, 1991; Merzkirch, 1987).

Neural Networks began as a study into the functioning of biological neurons. In the eighteenth century, Galvani and Volta reported a connection between electricity and the central nervous system. Further research demonstrated that an electric current was conducted down the nerve fibers. In 1843, Emil Du Bois-Reymond measured the electric current in a carefully set up experiment using an early galvanometer.

The brain consists of hundreds of billions of neurons connected to hundreds of thousands of others (Wasserman, 1989). The problem with early neuron research had been that the neurons were packed together so tightly that an individual neuron could not be identified. In 1906, Golgi and Cajal won the Nobel prize for physiology and medicine when they discovered that silver nitrate applied to a sample slide of the cerebral cortex would stain individual neurons. With their discovery, individually stained neurons were now recognizable because the silver nitrate was absorbed by

This thesis follows a style based on Machine Vision and Applications

only a small percentage of the neurons. This led to the mapping of the cerebral cortex in 1943 by R. Lorente de Nó, one of Cajal's students. He reported that the neurons could be differentiated into 32 to 34 different types.

It was at this point that efforts to model the brain with computers began. Artificial neural networks were designed based on simplified biological neurons. Work in 1943 demonstrated that a two-state logical decision element could compute Boolean functions.

In 1944, Hodgkin and Huxley studied the threshold, inhibition, and excitation of large neurons in the giant squid (Hodgkin and Huxley, 1952). This work not only earned the two researchers a Nobel prize, but provided a basis for many artificial network models.

Hebb's learning laws were published in 1949. These laws provided algorithms for making an artificial network learn. Learning in this case involves altering connection weights between the neurons and, thus, altering the output from the network. Rosenblatt developed the perceptron in 1957 (Rosenblatt, 1958). This simple neural network model could perform many useful processes and elicited a great deal of interest in neural networks. Widrow and Hoff, in 1960, published their work on the ADaptive LINear Element (ADALINE), and on the Many ADaptive Linear Elements (MADALINE) (Widrow and Hoff, 1960). These networks were the first commercial neural networks. During this time, Steinbuch developed his Learning Matrix (Steinbuch and Piske, 1963), which was a pattern recognition machine based upon linear discriminant functions. The first competitive learning algorithms also began to appear during this time (Rosenblatt, 1958; Stark et al., 1962). In 1964, Kabrisky suggested that visual

discrimination could be related to low-frequency Fourier spectra of the input patterns. Neural networks were being improved constantly during these years, and enthusiasm for them was never higher.

Unfortunately, around 1969, a proof was published by Minsky and Pappert which demonstrated that a single-layer perceptron architecture could not do an exclusive-or problem. Due to the prestige of Minsky and a reduction in government funding, research in neural networks began to decline. However, the proof given by Minsky was only for single-layer perceptrons, and did not apply to multi-layer networks.

Several researchers, among whom were Kohonen, Grossberg, Anderson, and Hopfield, maintained their enthusiasm for artificial neural networks (Wasserman, 1989). Kohonen developed the self-organizing layer (Kohonen, 1982). Anderson developed the Brain-State-in-a-Box algorithm (Anderson, 1968). Grossberg assisted Kohonen in coupling a hybrid Kohonen system with a supervised perceptron layer. He also produced the Adaptive Resonance Theory (ART). Grossberg and Von der Malsburg continued working with competitive learning throughout the 1970's (Von der Malsburg, 1973; Grossberg, 1976a). The most outspoken of these researchers was Hopfield. It was largely due to his efforts that neural networks began to make a comeback. Among his work was a network that could solve the traveling salesman problem.

Backpropagation, the most popular training algorithm still used significantly today, was proposed in this time frame. Backpropagation was developed to overcome the problem of training a multi-layer network. Widrow used the new backpropagation learning rule as a guide for improving the Madaline learning. The results were

Madaline Rule II and Madaline Rule III. Other new networks were developed as understanding improved. It was in the late 1970's that Fukushima proposed the new Cognitron and Neocognitron models (Fukushima, 1975; Fukushima, 1980). During the 1980's, Kosko developed his Bidirectional Associative Memory (BAM) (Kosko, 1987). Currently, there are efforts at implementing neural networks in hardware. Analog VLSI technology is being applied to several networks. Mead, at Cal Tech, has developed a 48 x 48 pixel retina that can perform spatial and temporal differentiation.

Today, neural networks are applied to projects in nearly every subject. They are used in everything from speech synthesis to predicting the stock market. They are helping people make decisions in medical diagnoses. The growing allure of neural networks is due to the fact that large amounts of processing may be done by large numbers of simple processing elements operating in parallel (Lippmann, 1987).

The field of neural networks is becoming so diverse that it would be impossible to relate all of the important work being performed. This thesis examines the use of neural networks in another quickly growing field, flow visualization. The networks presented will be those which were applied toward this endeavor.

1.2 History of Flow Visualization

Flow visualization came about as a natural consequence of the work performed in fluid mechanics during the 1800's. Researchers such as Reynolds and Prandtl needed a means for both visually understanding their equations and proving their validity, so they devised simple flow visualization experiments that would demonstrate their work (Merzkirch, 1987). Their experiments were generally free surface liquid studies,

in which particles or dye float on the surface of a liquid and are used to follow the flow at the free surface. It was during this early work that Prandtl and Tietjens noticed the wall boundary layer and formation of vortices behind obstacles.

Advances in flow visualization have often followed advances in photography. The introduction of high-speed photography was seen as a means of slowing fluid phenomena, so that the fluid could be more easily studied. In addition, advances in schlieren and interferometry techniques improved flow visualization during this time.

The father of flow visualization is undoubtedly Ernst Mach. His experiments studied the shock wave formed by a flying bullet. Mach described his views in 1943: (Mach, 1943) "Modern science strives to construct its picture of the world not from speculation but so far as possible from facts. It verifies its constructs by recourse to observation." Cohen further described Mach: "Mach wished science to assert only that for which there can be evidence. Sensed data are the common shared mode of evidence for every observers. Mach took it for granted that knowledge was sensational" (Cohen, 1970; Merzkirch, 1987). Some of Mach's work was continued by his son Ludwig Mach, who in the late 1800's used smoke to visualize air flow, 'smoke visualization'.

The early 1950's produced technologies which drastically improved air flow visualization. The development of wind tunnels allowed researchers to build tuft screens which are made of wire grids spread along the axis of interest. Each grid point has a piece of string attached to it. As the air moves, the strings stretch out in the direction of the air flow. A picture is taken and the direction of air flow is determined by measuring the length of the string showing in the picture. The largest problem with this technique is that the camera is at different angles for different grid points. Hence,

a correction must be made before determining the actual flow direction. Further use of the wind tunnel technologies included the controlled release of smoke for use with smoke visualization, which by the end of the decade could be used in air flows at supersonic speeds.

By 1960, experimenters were using neutrally buoyant dyes to study liquid flows. Common dyes of the time included milk and food coloring. Later improvements included the use of fluorescent dyes, enhancing photographic reproduction of the flow. One such dye, Rhodamine, was used in 1963 to study the flow of water in a lake.

Small tracer particles were also being introduced into liquid. By applying a thin sheet of light across the plane of interest, a photograph would record only those particles in the plane. The results were streak lines, which are formed when the particle is moving much faster than the shutter speed of the camera. The length of the streak is the distance that the particle moved while the shutter was open. Velocity data can be extrapolated from the photograph by dividing the streak length by the shutter speed. During the early 1960's, experimenters had developed clever techniques to derive even more data from streak lines. Three-dimensional data was obtained by using several parallel sheets of light, each with a different color. The third dimensional data could then be determined by using the colors of the streaks. Some researchers developed techniques of moving the camera with the flow, effectively producing a Lagrangian point of view.

The use of tracer particles was examined closely during this time. In 1963, shock tubes were developed for air flow visualization. All of the tracer particles produced

for air were more dense and, thus, heavier than air. However, by producing small enough particles, they could be suspended in the air, like dust. Shock tubes start the air flow quickly, after the large particles have settled to the bottom but before the smaller particles settle.

In 1964, it was noticed that particles had a relaxation time when they crossed supersonic gas flows. This relaxation time was a result of the particle needing time to achieve the same velocity as the flow. By 1965, two sources of error in using tracer particles were discussed. These were the particles' inertia and Saffman's lift force. Saffman's lift force is due to a velocity gradient in the flow across the diameter of the particle. Due to these forces, a particle can not adjust to a changing flow instantaneously. Further research to explore these limitations resulted in the particle limiting frequency. The particle limiting frequency in turbulence describes the maximum velocity change that a particle can make in a flow. Later research revealed another source of error due to velocity gradients which cause particles to drift toward the center of vortices.

Laser Doppler Anemometry (LDA) was also established in 1964. LDA consists of optical probes which measure the Doppler effect of the scattered light from the particles. In 1967, the buoyancy problem for liquid seeds was partially resolved using hollow glass spheres as the tracer particles in water.

Other achievements include the production of multiple exposures on a single image by using a 15 pulse stroboscope. This eliminated the streak lines that had formerly been seen and caused discrete particle images, or spots, to be produced. The distances between these spots could be measured and the velocity of the particle calculated over

each time interval. Unfortunately, the multiple-exposed images caused a directional ambiguity. Without prior knowledge, it was impossible to tell the direction of travel (i.e. from right to left or from left to right).

By 1969, attempts were being made to produce three dimensional (3D) velocity measurements of two phase flows using a technique known as holography. Within a short time, double-exposed holograms were producing a series of interference patterns that could be used to determine the particles movements.

In the early 1970's, further problems with using particle tracers were being discovered, such as the particle-free region in boundary layers. However, this did not stop researchers from applying new techniques. In 1973, tomography was used to produce 3D data by directing light from multiple directions.

Smoke visualization was also advancing in the 1970's. New forms of smoke included steam (fog) and $TiCl_4$, which produces a white stream of smoke when in contact with moisture in the air. $TiCl_4$ has been used in studies involving atmospheric wind patterns. In 1973, an aerosol generator was produced that made particles with diameters of $0.7\mu m$ using di(2-ethylhexyl)-phthalate (DOP).

Improvements in the use of wind tunnels also continued. It was determined that smoke could be released at any time and from any position without significantly disturbing the flow. This was achieved by using evaporating oil from an electrically heated wire. Some researchers combined the growing tracer particle studies, which produced quantitative results, with smoke visualization by producing puffs of smoke.

The use of dyes in fluids also continued. In 1974, Pitot probes were used as dye injectors, and fluorometers were used to measure the concentrations of a fluorescent dye in a flow.

In 1975, the Basset-Boussinesq-Oseen equation (BBO), a form of the equation of motion, was applied to particle tracers and turbulent flows. By 1977, particle tracking had advanced again, in the form of Laser Speckle Photography. This method was used to determine the distance between particle spots of a double-exposure image by implementing a technique known as Young's fringe pattern analysis. After taking the double exposure, a small laser light is passed through the photograph. Interference patterns form behind the photograph caused by the slight displacement of the particle spot. The interference patterns, or fringes, will be off set in the same direction as the spot movement, and the distance between fringes will be proportional to the movement of the spot.

Other forms of light scattering were also becoming useful. Raman scattering happens when light is inelastically scattered from molecules. The molecules gain energy and the scattered light has a different frequency from the incident light. Raman scattering was used in 1977 to study processes involving flames and combustion.

Lasers were being applied to virtually every aspect of flow visualization by the late 1970's. An example of this was the production of a laser sheet ($< 1\text{mm}$ thick) to illuminate smoke. However, some researchers were still using stroboscopes. In 1979, a stroboscope apparatus was used to solve the direction ambiguity for multiple-exposure images. The stroboscope would produce 5 long pulses followed by 5 short pulses. This

allowed the direction to be determined by the varying streak widths. Although streaks were produced, they were very short and may be treated as individual spots.

The particle diameter was important to many aspects of flow visualization. The size would affect how it scattered light, how well it traveled with the fluid, and how gradients would affect it. It was important for researchers to produce small particles and to determine their exact diameter. Diffraction theory was applied in 1979 to determine the particle diameter. However, even with the advancements in the field of particle image velocimetry (PIV), the fundamental problems involved with using tracer particles were still not answered. In fact, new problems were being demonstrated frequently. In 1982, it was suggested that a thermophoretic force was acting on the particles and would produce a particle-free region near a hot body.

By 1980, computers began to alter the techniques applied to flow visualization, much as the laser had done before it (Settles, 1986). Whole images could now be digitized into grey levels. The grey levels could record the brightness of individual regions, and allowed the computers to begin processing the information. Streak photographs could now be processed by the growing field of image processing.

The problems involved in using several cameras to develop a 3D image were solved by applying an optical grid to help focus and correct for the camera angles. In 1982, 3D photography was applied to multi-frame particle tracking. Further work with Young's fringes produced the technique of 'spatial filtering' which would produce equivelocity fringes.

The field of flow visualization continues to develop new branches. One of these is X-ray visualization and neutron radiography (Cimbala and Sathianathan, 1988).

This technique allows visualization through opaque materials such as steel, which could not be imaged using light.

Also in 1982, computers began performing automatic image analyses of Young's fringes. By 1984, computers were doing image processing of tracer particles, and they were recalculating the reference movement for the Lagrangian system after the image was taken. Computers were capable of determining large scale flow structures from the mixture of small scale turbulence using match filters and, by 1985, image processing had been performed on hydrogen-bubble time lines.

1.3 Merging Two Fields

This project will discuss applications of neural networks to a branch PIV known as Pulsed Laser Velocimetry (PLV). This method uses a laser to produce pulses of light, much as a stroboscope. However, lasers can provide quicker pulses with shorter pulse widths. The light from the laser is shaped into a thin sheet. The light is scattered from tracer seeds in the flow, and the images are captured by digital cameras. These cameras store the images into arrays of grey levels. Each image contains the instantaneous positions of the tracer seeds. Using identification and tracking algorithms, these images can be used to produce full field vector representations of the flow.

The two major steps after acquisition of data are identification and tracking. Identification refers to the determination of the tracer seed (or spot) data. This consists of the location of the centroid and the area covered by the spot. Spots appear as bright regions on a dark background. Current methods used to gather this information are

thresholding and connectivity algorithms. Applying a threshold to a grey level image results in a binary image, where any pixel with a grey level above the threshold value is considered to be part of a spot (value = 1), and all others are not (value = 0). Connectivity routines search the image for pixels with a value of 1 and connect them together into spots. After the spots are connected, the centroids and area of each spot are stored. Tracking algorithms are then applied to match the spots from frame to frame, and derive their velocity data. This report concentrates on the process of tracer seed identification.

This process is similar to research in pattern recognition by neural networks. A major problem in pattern recognition is the rotational dependence of the object (Reber and Lyman, 1987). However, rotational dependence is not a problem with PLV data, because spots are roughly circular. The following is a review of current work in pattern recognition using neural networks.

Many of the common architectures have been adapted for pattern recognition. Some of these include the Adaptive Resonance Theory, Backpropagation, Cellular Cognitron and Neocognitron, Counterpropagation, Hopfield, and Perceptron networks (Fukushima, 1975; Fukushima, 1980; Carpenter and Grossberg, 1987b; Fuchs and Haken, 1987; Hecht-Nielsen, 1987b; Yang and Guest, 1987; Chua and Yang, 1988a; Pawlicki, 1988; Karbacher, 1990; Ruck et al., 1990). Backpropagation has been successfully used to visually check welding during non-destructive testing (Philips and Steele, 1989), and cellular networks have been used for character recognition (Matsumoto et al., 1990a). Fourier Pattern Analysis has been performed by some of the networks (Graham, 1981).

There have also been many hybrid architectures developed for pattern recognition. One such is a cellular network connected with competition regions (Tenorio and Hughes, 1987). This architecture shows similarity to the cognitron, cellular, and kohonen networks.

A great deal of study has been performed by Grossberg including work in binocular vision, edge detection, and the effects of luminescence (Carpenter and Grossberg, 1987a; Grossberg and Marshall, 1987; Grossberg and Mingolla, 1987; Grossberg and Todorović, 1987).

Most of these networks have been successful to some degree in pattern recognition. However, none of them have proven to be successful under all of the conditions needed for tracer particle identification. This research studied and developed several architectures that achieved some moderate success.

Although not discussed in detail here, researchers are beginning to develop networks which can track particles (Cenedese et al., 1992).

Currently, researchers do not immediately know how well their experiment has performed. It may take hours to perform the experiment and finish the analysis. If a lot of data is taken, this time lag could be days. Unfortunately, the experiments do not always produce the desired flows. Further, there could be problems with the tracer particle distribution. If this occurs, the researcher must modify the experimental set up. After the development of fast and accurate neural networks for both particle identification and tracking, researchers will be able to quantify the flow in real time. This will allow the researchers to modify their flows quickly, adjusting for any problems that have been noticed.

CHAPTER II

PARTICLE IMAGE VELOCIMETRY

II.1 Overview

This chapter is devoted to explaining the Particle Image Velocimetry (PIV) methods used in this research. It explains how the neural networks can fit together with PIV.

There are three major steps in a PIV experiment. setup and acquisition, seed identification, and tracking. The first major step is the experimental setup. This requires an understanding of fluid interactions. If the experiment is not to be taken in three dimensions (3D), then care must be exercised in maintaining a two dimensional (2D) fluid flow. This requires examining a slice of a steady state fluid far from boundary affects. For other experiments which are 3D (eg. bubbles in a flow and turbulent flows), any 2D measurements taken are only a small part of the whole picture. In this first step the laser sheet must be properly aligned, the laser pulse settings must be determined, and the camera angles and focus depths must be set.

The second major step is to convert the grey level images into useful data for tracking purposes. The standard methods for doing this include using grey level threshold values to produce a binary image. The threshold value is used to define every pixel in the image with grey levels greater than the threshold to correspond to a tracer seed (1), and any with lower grey levels to belong to background (0).

Connectivity routines are used to connect the 1's in the binary image into spots. This is performed for all of the sequential time frames taken in the experiment. It is in this step that the networks proposed in this project are applied.

The third major step is to track the movement of spots through time. Tracking algorithms compare the spots in sequential time frames and determine the likelihood of correspondence between these spots. Many algorithms are available, some correlate geometric patterns of spots, and others compare the consistency of constant curvature lines through several frames of data. The most likely vectors are produced and used to piece together a full field flow. This information can then be used for secondary purposes, such as vorticities, streamlines, and shear analysis.

II.2 Experimental Setup

There are an endless number of studies which can be performed using PIV. However, care must be taken to ensure that an experiment accurately demonstrates the problem to be studied. A short list of experiments which can be performed include turbulence, multiphase flows, fuel sprays, air in wind tunnels, neutron radiography, and convection flows (Meynart, 1983a; Adrian and Yao, 1984; Adrian and Yao, 1985; Bertollini et al., 1985; Kobayashi et al., 1985; Melton et al., 1986; Meynart et al., 1987; Cimbala and Sathianathan, 1988; Braun et al., 1990).

A major problem in many experiments is that the images are taken in 2D even though many flows are clearly 3D. Many people, at first glance, say that the best way to keep a flow 2D is to use narrow flow channels. This is an error. Using a narrow channel causes boundary layer problems and, thus, the fluid will act substantially

different at different planes in the flow. The method used to limit the amount of 3D captured on film is to use a very thin laser sheet, less than 1mm thick. Even if the fluid is 3D, only tracer seeds which remain in this sheet for consecutive frames can be tracked. Obviously, the best way to solve the 2D problem is to take the data in 3D. Methods vary on how to take 3D data. Some researchers use multiple colored light sheets, others use multiple cameras (stereoscopes), and others use holography to acquire 3D data. This project only deals with identification of tracer seeds using 2D data.

This project will use data taken from a few experiments which have previously been performed. The first of these was a single phase experiment, in which seeded water was forced into a tank. This produced a step flow and produced some recirculation regions. Figure 1 (Hassan and Blanchat, 1991).

Another set of data was taken from an experiment in which the air-water interfacial shear was studied. In this experiment air was passed over slow moving water. Figure 2 (Blanchat, 1991). This experiment produced data in which there are two distinct regions, the air and water. The tracer seeds and background levels were different for each region. This will help the testing and training of the networks.

The final test of the network was made from data taken from a bubble experiment. In this experiment, bubbles were rising in a tank of water, Figure 3 (Hassan et al., 1992a). This experiment is proposed to be the most difficult test of the network, because the network would have to distinguish between the bubbles and the tracer seeds.

Figure 1. Step Flow Setup

Figure 2. Air-Water Interface Setup

Figure 3. Rising Bubble Experiment

In these three experiments the data was captured by using digital imagers to store the light reflected from the tracer seeds and bubbles. A Nd:YAG laser was the source of the laser sheet. The data produced from these experiments was used in the testing and training for this project.

II.3 Standard Methods for Tracer Seed Identification

Light is scattered from the tracer seeds, or bubbles, in the fluid and, digital imagers store this information in the form of grey levels ranging from 0 to 256. In this project the digital imagers store the images in 1024 x 1024 arrays of grey levels. Figures 4, 5, and 6 show the grey level images produced from the three above experiments. Notice that the seeds and bubbles appear as bright spots.

These images also show the effect of noise. Some of the tracer seeds are barely visible in the bright background. The source of the noise in these experiments varied for each experiment. The imager used in the step flow was old and produced large grey levels near the edges of the lens. The channel flow had reflections from the air and water interfaces. The bubble flow produced a corona of reflected light around the bubbles. Every experiment produces unique noise patterns, so it is difficult to create a standard identification routine. Also, as can be seen in Figure 5, the seeds can be very faint within certain regions (in this image the water seeds are faint and the air seeds are bright).

The current methods work fairly well on noise-free images. These methods include two basic steps to identify tracer seeds, thresholding and connection. Thresholding is used to discriminate between the seeds (bubbles) and background. The concept is

Figure 4. Step Flow Image (grey levels multiplied by 4)

simple. Assuming the background is dark (low grey levels) and the seeds are bright (high grey levels) a grey level threshold can be applied to produce a binary image. As an example, assume the background has an average grey level of 5, and the seeds have an average of 150. Applying a threshold of 10 would produce an array where every pixel with grey level greater than 10 would have a value of 1, and all others would have a value of 0. This is known as a global threshold (refer to figure 7). There are

Figure 5. Channel Flow Image

several problems with using a global threshold. The most obvious is in determining the value at which the threshold should be set. The background can fluctuate wildly over the entire image and the tracer seeds can be very faint in some regions. Other methods include using local thresholds, but even these can have problems in regions with a large grey level gradient in the background.

Figure 6. Bubbly Flow Image

After a binary image is produced, a connectivity routine is applied to determine which pixels belong to which spots. Connectivity routines give a spot identification number to each pixel with a value of 1. The algorithm then checks adjacent pixels. If they both have a spot identification number, then the two numbers are treated as belonging to the same spot, and are merged together and given a single identification number (refer to figure 8). After all of the pixels have been grouped into spots, other

32	48	49	26	17	0	0	0	0	0
55	123	205	97	33	0	1	1	1	0
37	240	255	195	53	0	1	1	1	0
43	38	213	75	50	0	0	1	1	0
33	25	47	31	57	0	0	0	0	0

Picture File
(array of grey levels)

Binary Image
(using a threshold of 60)

Figure 7. Example of Global Thresholding

1	1	1							
1	1	1	1					1	
1	1				1	1	1		
			1	1	1	1	1		
				1	1				

Pixels are checked row by row.
New numbers are assigned if
they are not adjacent to a pixel
already assigned a number.
Different numbers adjacent to
one another are given the same
number (i.e. 1=2 and 3=4=5)

1	1	2							
1	1	1	1					3	
1	1				4	3	3		
			5	4	3	3	3		
				3	3				

Figure 8. Example of Connectivity

0	0	0	0	0	0	0	0	0	0
0	1	1	1	0	0	1	1	1	0
0	1	0	1	0	0	1	1	1	0
0	1	1	1	1	0	1	1	1	0
0	0	0	0	0	0	0	0	0	0
After Thresholding					After Smoothing				

Figure 9. Example of Smoothing

values can be calculated. These values include average grey level, average diameter, centroid, and number of pixels in the spot. Connectivity is discussed in detail in the literature (Horn, 1986; Gonzalez and Wintz, 1987).

Smoothing routines are sometimes applied between the thresholding and connectivity steps. Smoothing routines can eliminate some of the noise. There are several different kinds of smoothing. A common method calculates (for each pixel) the sum of the binary values of the eight neighboring pixels. If the sum is greater than a set number then the pixel should have a value of 1, else it should have a value of 0. For example if the number is 5, then if 5 or more of the neighboring pixels have a value of 1, then the center pixel will be given a value of 1, refer to figure 9.

Seed identification is the part of PIV that was investigated in this project. Attempts were made to perform this sequence using neural networks.

II.4 Thresholding Bubble Coronas

This section is included to demonstrate some of the intricacies involved in determining the seed locations. This work was produced as a result of studying the effects of the bubble corona during the neural networks research.

A corona is produced by laser light scattering from the bubble surface. It causes distortion of the grey levels surrounding the bubble, and its effects must be minimized to acquire data near the bubble. The type of corona that was examined is exemplified in Figure 6. The best way to remove this corona is to lower the intensity of the laser light. However, this can cause many of the faint seeds to become undetectable.

The best way of demonstrating the effect of the bubble corona is to plot the grey levels along a line of the image. Figure 10 shows the grey levels along the horizontal line of $y = 824$. This line roughly crosses the center of the top bubble. Notice how the grey level is clipped at the bubble (grey level = 255) and declines to the background slowly. Also shown are several tracer seed spots as shown by the grey level spikes. The straight line demonstrates a global threshold at a grey level of 10. As explained earlier, everything above the line would be seen as spots and below the line as background. This approach would produce a large spot around the bubble thousands of pixels in area, as shown in Figure 11. This is a binary image with the black showing the pixels which have grey levels higher than that of the global threshold.

At this point it was deemed necessary to find a function which could filter the effects of the corona. Since it is impossible to derive information from the region

Figure 10. Grey levels along a line at $y = 824$ and a global threshold of 10

where the grey level is equal to 255, the function should begin thresholding from the first pixel not in this region and continue until the function threshold is equal to the background or global threshold. Several Gaussian functions were tested but the best fit was a $\frac{1}{x^2}$ function.

Figure 12 shows Figure 10 with some $\frac{1}{x^2}$ curve overlays. Notice how the curving threshold catches only the peaks that come out of the corona. These peaks are probably seeds which were near the bubble. An important concept which can be clearly demonstrated in this figure is that the corona is asymmetric. This can be caused

Figure 11. Binary Image Produced by Using a Global Threshold of 10

by many reasons, among which are that the laser light is entering unidirectionally, and the bubble is not a perfect sphere. Thus the constants in the $\frac{1}{r^2}$ function must have angular dependence to produce a threshold which will properly fit the corona. Figure 12 shows a different curve on each side of the bubble. The constants used to produce the curves are now chosen arbitrarily by the experimenter to enhance the image properly. However, there are some suggestions for automating this step. Further, because of the difficulty involved in correcting for the angular dependence of the corona, the function is left symmetric. The center of the symmetry should be placed at the center of the bubble. However, usually the image will become clearer if the symmetry is placed off center from the bubble. Figure 13 was produced using off center symmetric functions. The rings are presented to show where the thresholding function equals to 254 and 10. All of the black inside of the inner ring has a value

Figure 12. $\frac{1}{\sqrt{r}}$ Functions Applied to Figure 10

of 255 and contains the region of the bubble. The outer ring is where the function equals the global threshold value of 10. The threshold function is applied to the region between the two rings. In Figure 13, the function applied to the upper bubble was centered at $x=540$ and $y=803$, and the radius of the inner ring is 85. The function applied to the lower bubble was centered at $x=536$ and $y=258$ with an inner ring radius of 75.

The purpose of the $\frac{1}{\sqrt{r}}$ function is purely to assist in thresholding near the bubble. This can allow tracer seeds to be tracked closer to the bubble when there is a significant corona. This function does not determine the attributes of the bubble. The

Figure 13. Binary Image Produced Using a Global Threshold of 10 and Radial $\frac{1}{r^2}$ Functions

bubble center is somewhat arbitrarily chosen to be the center of the region with grey levels of 255. The edge of the bubble is in no way determined by this procedure. This procedure could occasionally produce a seed spot which is actually part of the bubble. However, such statistically random events would not be tracked from frame to frame by the tracking programs.

II.5 Tracking Methods

Tracking methods will only be briefly discussed in this section for the purpose of determining the form that the output of the neural network should take. If the reader wishes to further discussion of these methods, it is suggested that he read the literature (Hild, 1989; Hassan et al., 1990; Adrian, 1991; Blanchat, 1991; Hassan

and Blanchat, 1991; Hassan et al., 1992a; Hassan et al., 1992b). The two algorithms which are to be used to track the results of this research are a multi-frame technique and a cross-correlation technique.

The multi-frame technique tracks spots through at least four frames of data. The tracking technique searches sequential frames of data pairing spots in consecutive frames. It pairs them in such a way as to produce constant curvature movement between frames. The tracks are rated as to how constant their curvature remains through multiple frames. This rating is called the sigma value for the track. Sigma values equal to zero are considered as a high probability to be an accurate track. The input to this algorithm consists mainly of the spot centroids in each frame, and can be improved using the spot average grey levels and spot areas.

The cross-correlation technique tracks spots by matching local region geometric patterns of spots. This method requires only two frames of data. The local pattern of spots for every spot in the first frame is compared to the local pattern of spots for every spot in the second frame. The pairing of spots occurs for those patterns that most closely correlate. This method works if the flow is laminar, and can work for turbulent flows if the time interval between frames is short enough. The pairings are rated by correlation between the patterns and the number of other spots for which it was part of a successful pattern correlation. The input to this algorithm consists of the spot centroids and areas and can be improved using the spot average grey levels.

The output of the neural network should include the data used in these tracking algorithms. The key pieces of data for both of these algorithms are the spot centroids and areas. The neural network must accurately produce this data to be successful.

CHAPTER III

THE BASIC NEURON

III.1 The Biological Neuron

As the name implies, neural networks are models based on biological neurons. The brain is basically a biological information processing computer, with the neuron as its smallest processing element (Rogers and Kabrisky, 1991). The biological neuron can be divided into three major regions, the dendrites, the body, and the axon. Figure 14. In its simplest interpretation, each dendrite receives a stimulus from another neuron which is sent across a region known as the synapse. This stimulus is transmitted to the body, which sums all of the stimuli from the converging dendrites. If the sum from the dendrites is high enough, the neuron becomes excited and transmits stimulus down its axon to other neurons. Hundreds of neuron types have been identified, ranging from 5 to $100\mu m$ in size with each neuron type capable of performing a different function. The brain consists of roughly 10^{11} neurons with over 10^{15} interconnections. It is this extremely high connectivity that makes the brain a powerful processor, not the complexity of individual neurons (Wasserman, 1989).

Neurons very rarely actually connect physically with one another. Instead, the stimulus is transmitted across a narrow gap between the axons and dendrites known as the synaptic cleft. The stimulus is transmitted across the synaptic cleft by neurotransmitters, which are composed of over 30 known chemicals. Some of these chemicals can excite the dendrite and others can inhibit it. When the axon becomes excited,

Figure 14. Biological Neuron

it releases some of these neurotransmitters, which travel across the synaptic cleft and are then absorbed by the dendrites.

Axons range in length from 0.1mm to over 1m . The axon, as mentioned, terminates at the synapse. The pre-synaptic terminal end of the axon contains many small spherical structures known as synaptic vesicles. These vesicles contain the neurotransmitters which are released when the axon becomes excited, and activate/inhibit hundreds of thousands of other neuron dendrites. The length of the axon is sheathed by a substance known as myelin. Myelin is responsible for maintaining and speeding the weak electrochemical signal down the length of the axon. The myelin is interrupted periodically at points called the nodes of Ranvier. The action potential is regenerated only at these nodes, efficiently making use of the neurons energy.

Figure 15. Biological Neuron Potentials

There are two methods of communication within the neuron, chemical signals across the synapses, and electrical signals within the neuron. Both of these processes can be attributed to the complexities of the cell membrane. In the thin membrane there are five classes of proteins: pumps, channels, receptors, enzymes, and structural proteins. Pumps move ions across the cell membrane, maintaining the concentration gradients. Channels control the flow of selected ions across the membrane. The channels can be affected by the electrical potentials in the nerve which provides a quick response for control of ionic gradients. Receptors are proteins that combine with molecules from the cellular environment. The enzymes speed many of the chemical reactions, and the structural proteins maintain the cell structure.

The chemical balance inside of the neuron has a sodium concentration ten times lower and a potassium concentration ten times higher than its surrounding environment. The pumps maintain this differential, resulting in a resting neuron electric potential of -70mV relative to the surrounding environment, Figure 15. As the synaptic inputs (chemical) affect the neuron, this electric potential changes due to

the changing chemical signals given to the membrane's proteins. When the potential is increased to $-50mV$, the sodium and potassium ion flows across the membrane become uninhibited and within a millisecond the neuron has a potential of $-50mV$. This potential then propagates quickly down the neuron's axon to cause the release of the neurotransmitters. After this pulse, the cell will remain inactive for several milliseconds, during which time it returns to its resting potential by action of the pumps.

The dendrites are not effected by the electric potential, they are only effected by the chemical information being sent across the synapse. Some of the chemicals cause the cell membrane to allow more sodium to pass into the neuron, while others reduce the amount that is being passed. This causes the electric potential in the dendrites to change subtly. This small potential is propagated to the main cell body. The cell body sums all of these small potentials coming from all of its dendrites. It requires the cooperation of many dendrites to cause the neuron to pulse. Some of the dendrites will be sending inhibitory potentials, increasing the amount of positive potential required from other dendrites to cause the neuron to pulse. All of the neurons in the brain do not pulse at the same time, thus causing the dendrites to receive stimulation at different times. Over a very short period these stimuli are summed, however, at any given moment, the neurons may be receiving stimuli from many of its hundreds of thousands of dendrites, and barring the neural dead time, the stimuli may be considered continuous. The frequency of the pulses depends on the effect, excitatory or inhibitory, from all of the dendrites. If there is a lot of excitation being experienced, it will activate more quickly and have a high frequency.

Likewise, if the excitation is minimal, but enough to cause the neuron to pulse, the frequency will be low. Frequency modulation is used commonly to provide a means of eliminating noise, as for example, in FM radio. Here the neuron is using a similar technique.

New discoveries are being made about the neuron every day. Unfortunately, most of these only increase the complexity of the neuron model and make the neuron ever harder to understand.

III.2 The Artificial Neuron

The biological neurons are in fact so complex that it is unreasonable to make a model that accurately describes their every working facet. Models are designed either to help the understanding of the processes, or to perform some other useful function. The artificial neurons used in neural networks fall in to both of these categories.

A generic neuron model is shown in Figure 16. In this figure, i is used to denote previous neuron or input signals, j denotes this neuron, and (i, j) is interpreted as from neuron i to neuron j . An input vector, $X(i, j)$, is applied to a neuron. The values of the input are transformed according to the weight vector, $w(i, j)$. The weighted input is integrated, $S(j)$, and compared to a threshold value, $h(j)$. If the integral is greater than the threshold value, the difference, $S(j) - h(j)$, is passed through a transfer function, $T(j)$. The output from the transfer function, $Y(j)$, is then sent either as output from the network, as input to other neurons in the network, or feedback to itself (Wasserman, 1989).

Figure 16. Artificial Neuron Model

The input vector, $X(i,j)$, is often the output from other neurons in the network. It can also include feedback directly from the output of the neuron to which it is being applied, or it may be an initial input to the network. Sometimes the input needs to be preprocessed to put it in a form that can be readily used by the neurons, or for specific use in a particular network. Standard preprocessing involves normalizing the input or scaling it to within some workable range. The number of inputs is dependent on the network. Some networks require that every neuron receives input from every other neuron. Some require that a neuron receives input only from neighboring neurons. Still others have input received from random neurons.

The weight vector, $w(i,j)$, has the same size as the input vector. Every input has an associated weight. If the weight is positive, then the input will help to excite the

neuron, and if it is negative, the input will have an inhibitory affect. The weight vector also affects the relative importance of one input over another. If the weight value is high, even a small input could have a significant effect. The weight vector is one of the most important parts of the model. By changing the weight vector, the neuron can change its output. Many learning algorithms exist, and their use depends mainly on which type of network the neurons are forming.

For most networks, the integrator sums the weighted inputs as follows.

$$S(j) = \sum_i X(i, j)w(i, j) - h(j) \quad (1)$$

For many networks, if $S(j) > 0.0$ the neuron will become active. When a neuron is active it produces output, and when it is inactive it does not. Other networks do not use this approach. They pass the integrated information on whether it is positive or not. Some networks, such as the Kohonen, do not sum the weighted inputs at all. These networks sum the difference between the input vector and the weight vector.

$$S(j) = \sum_i |X(i, j) - w(i, j)| - h(j) \quad (2)$$

This difference is basically the Hamming distance between the input vector and the weight vector. The Hamming distance is a term used to describe the degree of difference between sets. In a Kohonen network, the neuron which has the most similar weight vector to the inputs, $S(j)$ closest to zero, will become the active neuron, and all the others will become inactive. There are many variations on this theme.

The transfer function, $T(j)$, transforms $S(j)$ into the output $Y(j)$. There are many common transfer functions. Most of these produce outputs in the range of

Figure 17. Transfer Functions

either $-1.0 \leq Y(j) \leq 1.0$ or $0.0 \leq Y(j) \leq 1.0$. The four most common transfer functions are listed below, and shown in Figure 17.

$$\text{Bipolar } Y(j) = \begin{cases} 1.0, & \text{if } S(j) \geq 0.0; \\ 0.0 \text{ or } -1.0, & \text{if } S(j) < 0.0. \end{cases} \quad (3)$$

$$\text{Linear } Y(j) = S(j) \quad (4)$$

$$\text{Hyperbolic Tangent } Y(j) = \tanh[S(j)] \quad (5)$$

$$\text{Sigmoidal } Y(j) = \frac{1}{1 + e^{-S(j)}} \quad (6)$$

There are many parameters that can be altered in the above equations to produce variations of the same type of transfer function. Another type of transfer function which can be used for neurons that have continuously applied input is one which

oscillates. The amplitude may be determined as for any of the other transfer functions, and the frequency can be set by how active the neuron is. The term 'how active' is used to describe the extent above the threshold value of the integration value. Other methods for setting the frequency may also be used. One method is to set the frequency by the number of inputs that had an excitatory affect. Oscillating the output can provide more information about the state of the neuron than simply using standard transfer function output.

The artificial neuron model is analogous to the biological neuron in several ways. The weights can represent the synaptic gap between the neurons. The integrator is equivalent to the main body of the neuron, where the stimuli from all of the dendrites is summed. The transfer function can simulate the stimulus down the axon towards other dendrites. Granted this is a much simplified model, but it does provide a starting point for the construction of networks that can perform many important functions.

CHAPTER IV

BACKPROPAGATION

IV.1 Background

Backpropagation was developed to overcome the problems inherent in training the multi-layer perceptron. Its development allowed multi-layer architectures to be trained. The multi-layer perceptrons were then capable of learning nonlinear patterns from input data.

Backpropagation was independently designed by three different groups at three separate times. Rumelhart, Hinton, and Williams presented the algorithm in 1986. Upon its announcement, Parker was shown to have described a similar architecture in 1982. And further, it was discovered that in 1974 Werbos had already described the method. One of the largest drawbacks of performing research into neural networks is that concurrent research is being performed across the scientific spectrum. It is impossible to find all of the relevant information stored in the countless journals and conferences. Perhaps information retrieval itself should be an emphasis of neural network research.

Today, backpropagation is the most widely used learning algorithm. It has been applied successfully to many problems involving pattern detection, and has been implemented as part of a network used to check spotwelds in nondestructive testing (Yang and Guest, 1987; Philips and Steele, 1989).

Due to its widespread use, there are many variations from the basic design and training methods. Only the methods used in this research will be discussed, other methods are shown in the literature (Lippmann, 1987; Wasserman, 1989; Ruck et al., 1990; Rogers and Kabrisky, 1991).

IV.2 Architecture

The neuron used is shown in Figure 16 using a sigmoidal transfer function. Instead of using a threshold function $h(j)$, a bias $I(j)$ is given as input to each neuron, and Equation 1 becomes:

$$S(j) = \sum_i X(i, j)w(i, j) + I(j) \quad (7)$$

For training purposes the bias can be treated as a weight connecting neuron j to a neuron with a constant output of 1. This form of the neuron, known as the perceptron, will always be active when given input.

Perceptron networks are connected as shown in Figure 18. This figure shows a multi-layer network consisting of 2 hidden layers and an output layer. Every neuron is connected to every neuron in the following layer. This is known as being fully connected. The first hidden layer receives its input vector from an array consisting of the grey levels of a region of an image. All of these connections have associated weights. The bias connected to each neuron is not shown in this figure, but each connection also has an associated weight.

Each neuron in the output layer will correspond to a different size spot, with one neuron corresponding to the lack of any size spot. For instance, if the input matrix is a spot of diameter 3, then the output neuron corresponding to spots with diameter

Figure 18. Multi-layer Perceptron Network

3 will produce an output value of 1, and all others neurons in the output layer will produce values of -1.

Competition networks are often connected to the output of the multi-layer perceptron network. These networks can interpret the results, and can also help in many other ways. There are many variations that can be attempted. Each variation will be

discussed during the training and testing sections. Further, the conclusions section will have some ideas which were not implemented in this research.

The current work was done on a network consisting of 1 output layer (6 neurons) and 1 hidden layer (or input layer with 6 neurons). Each of the hidden layers neurons is fully connected with the input matrix.

IV.3 Training

Backpropagation will be the learning algorithm used to train this network. The basics of backpropagation are simple. First, randomly assign each weight in the network a number between 0 and 1. Next, apply a training sample as the input and compare the output vector with the target vector for the sample. Calculate new weights by adjusting the old weight by some amount to improve the accuracy. Finally, apply the training sample again and repeat the process until the desired accuracy is achieved.

The most difficult part of this process is in calculating the new weights. The weights must be adjusted on the output layer and then on the preceding hidden layers. This algorithm was tested using only 1 hidden layer, so the discussion that follows will only deal with a 2 layer network. Neurons in the hidden layer will be denoted by i and neurons in the output layer will be denoted by j . The training matrix, $M(x, y)$, is applied to the network and the output, $Y(j)$, is compared to the target vector, $T(j)$.

Mathematically, begin with the transfer function. As stated, a sigmoidal transfer function was used (refer to Equation 6). This function produces output from 0 to 1. Adjusting this to produce output between -1 and 1 produces,

$$Y(j) = \frac{2}{1 + e^{-S(j)}} - 1 \quad (8)$$

and the derivative of this function is as follows.

$$\frac{dY(j)}{dS(j)} = (Y(j) - 1) \left(1 - \frac{1}{2}(Y(j) - 1)\right) \quad (9)$$

To calculate the new weights from the hidden layer to the output layer, $w(i, j)$, use the following equations.

$$\delta(j) = \frac{dY(j)}{dS(j)} (T(j) - Y(j)) \quad (10)$$

$$\Delta w(i, j) = \eta \delta(j) Y(j) \quad (11)$$

$$w_{n+1}(i, j) = w_n(i, j) + \Delta w(i, j) \quad (12)$$

where w_n is the old weight, and w_{n+1} is the new value. η is used to control the speed at which the weights adjust and ranges from 0 to 1. The bias is also adjusted in this fashion.

$$I_{n+1}(j) = I_n(j) + \Delta w(i, j) \quad (13)$$

The weights from the input matrix to the hidden layer are some what more complex. The weighted values of $\delta(j)$ from the output layer are summed and used in determining the new hidden layer weights, $w(x, y, i)$.

$$\delta(i) = \frac{dY(i)}{dS(i)} \sum_j \delta(j) w(i, j) \quad (14)$$

$$\Delta w(x, y, i) = \eta \delta(i) Y(i) \quad (15)$$

$$w_{n+1}(x, y, i) = w_n(x, y, i) + \Delta w(x, y, i) \quad (16)$$

$$I_{n+1}(i) = I_n(i) + \Delta w(x, y, i) \quad (17)$$

The initial training set was given to determine how effective this method would be at distinguishing between spots of different sizes. Determining the location of spots in

Figure 19. First Training Set Applied to Backpropagation Network

an entire field will be discussed later. The training set and its associated target vectors are shown in Figure 19. The matrices on the left represent the $M(x,y)$ data. The white spaces have a value of -1 and the black have a value of 1. The training vector, $T(j)$, gives the desired value of the neurons in the output layer. Each neuron would correspond to a different size spot and should have a value of 1 when that size spot is given as input, and a value of -1 otherwise. This figure also shows a representation of

the output produced by the network after training was performed. The entire training set was given to the network and the error, $T(j) - Y(j)$, was averaged before being backpropagated. This method performed better than backpropagating after each matrix and prevented the network from forgetting the early matrices as it learned the later ones, in a cyclical manner.

The output column of Figure 19 graphically demonstrates which output neuron produced the highest value for the input matrix. This figure demonstrates that the network is capable of distinguishing between certain size spots. However, the larger spots were all identified as being of the largest size. This may be because the network is generalizing. That is it recognizes the 5, 7, and 9 diameter spots as being large and hence clumps them into one category. The reason for this generalization may be that the difference between these spots is less recognizable than the difference between the smaller spots (i.e. the difference between no spot and one diameter spot is significant). This figure does not demonstrate the values of the output layer neurons and further assumes that a competition was set up to decide which size spot is the most likely (in this case the spot represented by the output neuron with the highest value).

A measure for how effectively this network is distinguishing between spot sizes is the *rms* value. This value is calculated as follows.

$$rms = \sqrt{\frac{\sum_k \sum_j (T_k(j) - Y_k(j))^2}{kj}} \quad (18)$$

$$0.0 \leq rms \leq 2.0 \quad (19)$$

where k is the number of matrices in the training set. The closer to 0 the *rms* is the better trained the network is. The final training value for the output shown in

Figure 19 was 0.754 after 46 iterations with a η value of 0.8. This is not a very good *rms* value, but the results are encouraging.

η is chosen experimentally. Different training runs are performed using different η values. η is chosen from the one which produced the quickest or best results. In this research a few η were tested. It was determined that changing this value had little affect on the final *rms* value achieved. It did allow the network to train in fewer iterations. However, the size of this network is so small that the training time was not very long regardless of the η value.

IV.4 Testing

Testing the network involves applying the network to a full image, not just a 9 x 9 square. The method used is a slow process, requiring the network to examine the full image pixel by pixel. A 9 x 9 square centered on the pixel being examined will provide the grey level input to the network. Any parts of the square outside of the image (for center pixels near the edges) were treated as having a grey level of 0. At this point the output layer neuron with the highest value will be recorded along with its value. For now, this will be done using conventional fortran code, however it can be performed using a competition layer. At this point, the purpose is to test whether backpropagation can discriminate well enough. The competition layer may be added later.

The output produced is an array of spot sizes. Most of these will contain 0's. Again using conventional fortran instead of a competition layer, the pixels with values other than 0 will be compared to determine where the spot centroids are located. This will

Figure 20. Example of Spot Consolidation

be done by checking a diameter equal to the spot size for each non-zero pixel. Any other non-zero pixels in this region will be compared and the pixel with the lower spot size will be changed to a zero. An example of this may be seen in Figure 20. The final output that would be produced from this image would be the value 9 located at the center of the large spot, and the value 3 located at the center of the smaller spot.

The test image will be a 100 x 100 grey level image, simulating actual data, refer to Figure 21. There are 20 spots randomly sized (diameter 1-7) and placed throughout the image. The grey levels of the spots are 255 and the background is 0. The first test does not have any noise and is a very clean image.

As can be seen in Figure 22, this first test was not entirely satisfactory. This figure shows the centroids of identified spots. It is not intended to show the size of the spots, only that spots have a centroid at the locations of the black squares. This

Figure 21. Test Image

figure shows that the network did not correctly identify the centroids of the twenty spots shown in Figure 21. It does show however that the network is sensitive to the proximity of spots.

IV.5 Adjusted Input Vector and a Second Hidden Layer

In an attempt to improve the network two features were adjusted. First, a second

Figure 22. Output After First Training

hidden layer was added, refer to Figure 18. This was added in the hope that an additional layer, would improve the recognition of different spot sizes.

The second adjustment was to change the input matrix. As stated before, the input matrix was a 9 x 9 grey level image that was fully connected to the first hidden layer. The adjustment is to convert the matrix into a vector consisting of values

Figure 23. Vectorizing the Input Matrix

produced by examining different portions of the matrix. The vector will contain 6 values produced by summing the grey levels in the matrix over regions associated with spots of different sizes. This process is demonstrated in Figure 23. This input vector is then fully connected with the first hidden layer.

Training was performed differently also. The network would now train for one iteration on the first input vector, and then train on the next input vector. The

process would be repeated for every input vector and then start over with the first until a reasonable *rms* value was achieved. This was not done earlier for fear that the network would forget its previous training.

The network did produce a cyclical *rms* value. That is it would train in favor of one vector and forget an earlier vector, only to then forget this vector as it trained in favor of another vector. After roughly 300 iterations, the network was producing an *rms* that fluctuated between 0.447 and 0.477, with an η of 0.8. This was an improvement over the earlier architecture.

At this point the significance of the η value was discovered, quite by accident. Different η values (i.e. such as 0.2, 0.8, and 0.9) had been evaluated to produce little affect on the networks ability to identify the spots, and so a value 0.8 was chosen somewhat arbitrarily. During one of the training runs a value of 0.87 was accidentally given as the η value. The *rms* value produced during this run is shown in Figure 24. As this figure shows, the *rms* value dropped to 0.056 after roughly 350 iterations. These weights were saved and Figure 25 shows the results produced.

Figure 26 is the results produced when the new architecture and weights were applied to Figure 21. Again this figure only shows where the network identified spot centroids, and again the results are poor. However, these results are more tightly packed around the actual centroids shown in Figure 21. In addition, it correctly identified the centroids of the spots with a diameter of 1.

These results are not sufficient to perform the desired task of identifying the centroids of actual spots. However, they are encouraging. The major problem is not

Training

Figure 24. *rms* Value Produced for an η Value of 0.87

in recognizing a lone spot centered on an image, but of identifying many spots at various locations on the image. This is where further work will be required. It may be possible to train a network on an image, such as the one shown in Figure 21. If this image was successfully trained, then the network should perform adequately to move on to the next step of applying it to an experimental image, such as shown in Figure 4

Figure 25. Results Produced During Training Altered Architecture

Figure 26. Output from Second Architecture

CHAPTER V

KOHONEN SELF-ORGANIZING MAPS AND COUNTERPROPAGATION

V.1 Background

Competitive networks were derived from work into unsupervised networks. An example of a supervised network was given in Chapter IV, the backpropagation network. In a supervised network sample inputs are given for the network to train. These inputs are associated with known outputs. Hence, the network is trained to produce these outputs when given the corresponding inputs. Networks using unsupervised learning are not given a target output. These networks adjust their weights according to the input only. This process is partially accomplished by connecting the neurons in competition layers. Thus, a neuron will become active when it is familiar with the input (Wasserman, 1989; Rogers and Kabrisky, 1991).

The Kohonen Self-Organizing Map is an unsupervised network which has been proven capable of pattern recognition, including such fields as linguistics (Kohonen, 1990).

Competitive networks are often coupled with other networks, commonly backpropagation. Counterpropagation is one such network. This network composes of a supervised input layer with a supervised output layer. Counterpropagation can be used to reproduce information given only partial data. Other hybrid networks have

been suggested for use with machine inspection (Villalobos and Gruber, 1990). This network uses a competitive layer to generalize the input into categories, and a back-propagation network to fine tune the classification within these categories.

Again, the literature contains many examples of different architectures (Hecht-Nielsen, 1987a; Hecht-Nielsen, 1987b; Lippmann, 1987; Oja and Kohonen, 1987). This chapter will discuss the Kohonen Self-Organizing Map as an example of unsupervised learning, and will apply a simple network to a traveling salesman problem. After this, a counterpropagation network will be explained in detail. This network and versions of it were tested extensively in relation to tracer seed identification.

V.2 Traveling Salesman Problem

The traveling salesman problem is to determine the shortest path which would include stops at several cities. Here it is changed to be a traveling student problem, in which a student must stop in several buildings around campus. A Kohonen map will be used to determine the shortest path.

Unlike the backpropagation network described in the previous chapter, Kohonen layer neurons compete with one another, and the winner of the competition will be active, while all others remain inactive. There are variations on this theme in which multiple neurons can be active, but this example will have only one active neuron at a time.

The competition is performed by comparing the input vector with the weight vector for each neuron. The neuron which has the closest weight vector to the input will be the winner. In this example, the input vector will consist of the coordinates, $M_i(x, y)$,

Figure 27. Affect of Learning Parameter α

of building i and the weights, $wt_{sj}(x, y)$, of neuron j will represent coordinates on the same map. The distance between the two, $dis_{i,j}$, is calculated as

$$dis_{i,j} = \sqrt{(M_{i,x} - wt_{sj,x})^2 + (M_{i,y} - wt_{sj,y})^2} \quad (20)$$

The neuron with the smallest $dis_{i,j}$ is the winner.

Another major distinction between this architecture and that used for backpropagation is in the learning method. This network will have unsupervised learning. The weights will adjust solely on the input, not on any target output vector. The winner will have its weights adjusted so that they become closer to the building coordinates.

$$wt_{sj,x,n+1} = wt_{sj,x,n} + \alpha * (M_{i,x} - wt_{sj,x,n}) \quad (21)$$

$$wt_{sj,y,n+1} = wt_{sj,y,n} + \alpha * (M_{i,y} - wt_{sj,y,n}) \quad (22)$$

α is a constant used to adjust the speed at which the weights adjust. This learning can be visualized by placing both the weights, w , and the input, I , on a circle, Figure 27 (Wasserman, 1989). α will move the weights toward the input vector.

Another subtlety in this network is the concept of neighboring neurons. Neighboring neurons are not connected together by means of their input or output. They are simply close to the others in a physical sense. To continue with the traveling student problem, there will be 10 locations for which the student must visit, and hence the network will require 10 neurons. Every neuron is adjacent to only two other neurons, forming a ring of neurons. A neighborhood of only 1 means that only the 2 adjacent neurons are neighbors. A neighborhood of 2 means that the closest 4 neurons adjacent to a neuron are neighbors, and so on. A neighborhood of 5 will include all of the neurons in the ring. All of the neurons within the neighborhood of the winning neuron also change according to equations 21 and 22, where i and α remain the same as for the winner.

Training is performed for the winner and its neighbors for each location. The neighborhood begins large (i.e. 5) and α also begins large (i.e. 0.7). After all of the locations have been input α is reduced, and the input set is fed to the network again. After α reaches a low value (i.e. 0.1), the neighborhood is reduced by 1 and α is reset to its high value. Training is completed when the neighborhood is reduced to 0.

After training, each neuron will represent a location and adjacent neurons will represent locations that are close together. The ring of neurons will represent the shortest distance between all of the locations.

There are a few additions which must be made to make the network perform properly. The most important of these is to prevent one neuron from being the winner for multiple locations. This would also lead to a neuron never being the winner. To correct for this, each time α is updated check to see if this has occurred. If it exists,

Table 1. Input Locations for Traveling Student Problem

name	x-coordinate	y-coordinate	note
Duncan	1.4	2.4	cafeteria
Zachry	5.3	1.5	engineering
Blocker	5.2	2.3	business
Evans Library	3.6	2.3	library
Sbisa	4.9	3.4	cafeteria
Duddley's Draw	5.5	4.0	bar
Memorial Student Center	2.3	3.9	cafeteria
Small Animal Clinic	5.4	6.9	veterinary
Kyle Field	2.3	4.1	football
Olsen Field	1.0	5.6	baseball

then set the weights of the neuron which never won equal to one of the inputs for a neuron which wins multiple times. In doing this the adjacency of the neurons in the ring must be corrected, by moving the neuron which never won next to the one which won multiple times.

This example uses as input 10 locations around the Texas A&M University, requiring the network to have 10 neurons. The locations of the buildings are given as map coordinates in Table 1. A graphical representation of the output is presented in Figure 28. In this example the student will walk approximately 2.5 miles.

V.3 Architecture for Counterpropagation

Counterpropagation consists of a Kohonen, competition layer, coupled with a upper Grossberg layers, as shown in Figure 29. The competition layer separates the input

Figure 28. Output of Traveling Student Problem

into classes and the upper layer determines what those classes are to be. For this work the upper layers will be trained using Backpropagation.

As discussed above the Kohonen layer compares the input matrix with each of the competing neurons weight matrix, with the closest neuron becoming active. A major difference between the counterpropagation network and the above network is that there is no neighborhood in counterpropagation. Each neuron is completely independent from the others. Also, the input is somewhat more complex than the above x and y data. Here, the input will be a 9×9 matrix such as the one used for the backpropagation network described in the previous chapter, and the learning, shown in Figure 27, would be performed on a hypersphere. Training on the Kohonen layer would remain unsupervised, and each neuron would become responsible for

Figure 29. Counterpropagation Network

recognizing a different size of spot. α can be reduced linearly as above or using some other function such as,

$$\alpha(t) = Ae^{-\frac{t}{T}} \quad (23)$$

(Nasrabadi and Feng, 1987). The upper layers would be trained using supervised training, discussed in the previous chapter. The weights would be adjusted by comparing a target vector with the output vector, and the adjustment would be propagated down to the weights between the competition layer and the upper layer.

V.4 Testing

The first tests were very basic. The competition layer was not allowed to train ($\alpha = 0.0$) and did not have a threshold ($h(j) = 0.0$ in Equation 2). The weights

for each neuron in this layer were set equal to the input matrix for which it was to correspond, refer to Figure 10. There will be only one upper layer, or backpropagation layer, consisting of 6 neurons. These would correspond to the 5 spot sizes and the absence of any spot. The weights between this layer and the winning competition neuron would be adjusted using backpropagation. The output of the upper layer neurons would range from 0 to 1. All of the neurons should have values of 0, except for the neuron corresponding to the correct spot size, which will have a value of 1. Again, for now, only the winning competition neuron would be active.

The first problem with this architecture was that the upper layer weights would not change at all, regardless of the η value chosen. This was solved by scaling the sigmoidal function in the upper layer neurons by s . This changed Equation 6 and its derivative into the following,

$$Y(j) = \frac{1}{1 + e^{-\frac{s(j)}{s}}} \quad (24)$$

$$\frac{dY(j)}{dS(j)} = \frac{Y(j)(1 - Y(j))}{s} \quad (25)$$

With $s = 10$ and $\eta = .8$, the network produced a *rms* value of 0.88. Not a very good start.

At this point it was realized that the output of the competition layer could be very large. Since the upper layer was set to deal with numbers ranging from 0 to 1, this was a problem. The maximum Hamming distance between the input and the competition layer was 20,655 (255 grey levels x 9 x 9 pixels = 20,655). Further adjustment was made to the output of the competition neurons, so that the winner (determined as the

neuron with the highest output) would correspond to the neuron which most closely match the input. This altered the output of the competition layer neurons as such,

$$S(j) = 1 - \frac{\sum_{x,y} |I(x,y) - w(x,y,j)|}{20655} \quad (26)$$

Testing the network with these modification improved the *rms* value to 0.085 with $\eta = .9$ and $s = 1$. This correction solved the scaling problem, and thus, s was set equal to 1. These results are equivalent to those shown in Figure 25.

Applying this network with these weights to a 100 x 100 binary test image, shown in Figure 21, produces Figure 30. This figure shows all of the pixels in which the network output was non-zero. This figure is shows the neccesity of spot consolidation, described in the Backpropagation chapter, refer to Figure 20. Figure 31 is the output after spot consolidation. 95lost was due to the nearness of other large spots. This figure is markedly better than Figure 26, and is good enough to allow testing on more complicated input images.

The next image used for testing was with 20 randomly placed spots of various sizes on a 100 x 100 image, similar to the previously used image, but now there are two complexities added. First, the spot grey levels will no longer be set equal to 255. They will be randomly determined to be between 50 and 255. And second, noise will be introduced to the image. This is accomplished by adding a random amount of grey level to every pixel in the image. The noise added will be between 0 and a noise value. The first run will be with a noise value equal to 10.

The network was applied to this image and the results were that only $\frac{14}{20}$ of the spots were identified. The error was due to the initial training. The grey level of the

Figure 30. Output from Competition Network, before Spot Consolidation

training spots was equal to 255. If a test spot had a grey level of less than 127.5, the Hamming distance between it and the correct neuron would be larger than between it and the 'no spot' neuron. The network was retrained with the grey level of the training spots equal to 50. Again, the network was applied to the image. This time $\frac{19}{20}$ of the spots were identified, and again the one spot not identified was a small spot

Figure 31. Output from Competition Network, after Spot Consolidation

in close proximity to a large spot. It should be noted that the network would still have problems identifying faint spots (grey level ≤ 25). This could be corrected by training on fainter spots, however lowering the grey levels on the training spots could cause the network to begin identifying noise as being spots.

There should also be a problem if the background is greater than 25. With a background this high it is likely that some of the background pixels will register as

Figure 32. Step Flow Image: Centroids Found by Conventional Methods

spots. A solution to this could be to subtract the lowest grey level present, in the 9×9 input matrix, from every grey level in the input. This perform as a local correction for the background.

Figure 4 was used as the first experimental data given to the network. This image contains many faint spots and large regions of noise. Figure 32 shows the centroids found using the conventional methods discussed in Chapter II. For this figure a global

Figure 33. Step Flow Image: Centroids Found using Competition Network

threshold was set at 25. Figure 33 shows the centroids found using the above network. For this figure the network was trained on spots with a grey level of 50. There are many difference between these two. Figure 32 has 142 spots and Figure 33 has 174 spots. It appears that both methods have found a large number of different spots not identified by the other. Some of this may be do to the thresholding, either directly, as with the global threshold, or indirectly through the training spots for the network.

Figure 34. Step Flow Image: Centroids Found using Competition Network. Trained on Faint Spots

The affect of setting the global threshold, on the conventional method, to 15 was similar to that shown in Figure 11. This was caused by the noise around the edges. Retraining the network on spots with a grey value of 30, produced Figure 34. This figure contains 622 spots. Many of these are induced by noise, noticeably around the edges. Some of these are caused by unusually shaped spots causing the network to

Figure 35. Step Flow Image (100 x 100): Comparison of Methods

register a centroid twice. It is difficult to determine the accuracy of either method from these figures.

Figure 35 can be used to more easily compare these results. This figure is a blow up of the 100 x 100 square in the top left of Figure 4. The network used weight trained on spots with grey levels of 30 and the conventional method used a threshold

of 15. This was done to put both methods on an equal footing over this region of the image. Figure 35 shows the positions and relative sizes produced by the network and conventional analysis. It also shows the 'correct' answer, the spots found by manually selecting spots from the raw data. It should be noted that there is an error associated with manual selection. It is sometimes difficult to determine what is and is not a spot. It is used here only as a comparison. If any computational method can identify spots as well as a human, then the method would be a success. Figure 35 shows several spots which all of the methods found without trouble. It also demonstrates that there are spots which the network can find and the conventional method can not, and vice versa. The conventional method didn't mistake any background as being a spot, whereas the network has. From this small sample it appears that the network performed comparably with the conventional method. Further analysis, over a larger sample, will be made later.

CHAPTER VI

CELLULAR NETWORKS

VI.1 Background

Cellular networks have received much attention because they can be understood easily in electronic terms. Much work has been performed in making electronic cellular networks. (Chua and Yang, 1988a). These networks operate continuously and in real time. The neurons in a cellular network continuously fire, not discretely as in the previous networks.

Cellular networks have many characteristics in common with Kohonen networks, they can be trained using unsupervised learning and grouped into neighborhoods. Cellular networks consist of an array of interconnected neurons, which may be grouped in neighborhoods of neurons.

The difference between these and the competition networks is that in cellular networks the neurons interact with one another. The connections may be either excitatory or inhibitory. As stated some cellular networks are connected into neighborhoods of adjacent neurons. Yet, others can be connected completely at random.

Cellular networks may use supervised learning. Because of the large number, and great complexity of connections, an optimization method is used for adjusting the weights. Annealing is a commonly used optimization method. (Wasserman, 1989).

This process randomly adjusts the weights in a manner which will allow optimization to occur.

Cellular networks have been used in edge detection, noise removal, and character recognition (Chua and Yang, 1988a; Chua and Yang, 1988b; Matsumoto et al., 1990a; Matsumoto et al., 1990b; Matsumoto et al., 1990c). Some researchers are using cellular networks to mimic biological activities. Work has been performed to model the orientation sensitivity of the visual cortex (Von der Malsburg, 1973).

The Cognitron and Neocognitron are presented in this chapter because of their similarity to cellular networks. These networks were developed to simulate the human image recognition processes (Fukushima, 1975; Fukushima, 1980).

VI.2 Annealing

Annealing will be described first, because it is used in later networks. This method, as the name implies, is similar to the annealing process for metals (Wasserman, 1989). Annealing of the form described here can only be used with supervised learning

First, the artificial temperature must be initially set large, $T_0 = .0202$. Next, apply an input to the network and calculate the output. Compare the network output to the target output and calculate the *rms* value. Change a weight, w , by a random amount. These random amounts can be determined by using Cauchy Training. Again, apply the input and recalculate the *rms*. If the *rms* was reduced, then keep the weight adjustment. If the *rms* was increased, then there is a probability of keeping the changed weight, $P(\Delta w)$. This probability is determined as follows,

$$P(\Delta w) = e^{\frac{-\Delta w}{kT(i)}} \quad (27)$$

k is a constant similar to the Boltzmann constant, $k = .714$. If the weight is not kept, it is reset to its old value. Then repeat the process for each weight in the network. Increment t after N passes through all of the weights in the network. Continue this until the system has 'cooled'.

Cauchy Training is used to determine the cooling rate and the probability of accepting a weight change. Temperature is adjusted as follows.

$$T(t) = \frac{T_0}{1 - t} \quad (28)$$

The probability of accepting a weight change which resulted in an increase in the *rms* value is given as,

$$P(\Delta w)_{keep} = \frac{T(t)}{T(t)^2 + \Delta w^2} \quad (29)$$

Annealing is a slow process, but produces results that tend toward a global minimum. Figure 36 shows what an annealing process can be expected to produce. This figure was taken from a network to test the annealing process. The *rms* value is used to show how close the network was to its target output, and can range from 0 to 2. Figure 36 shows that the *rms* tends towards a minimum, however it can fluctuate wildly during training.

VI.3 Cellular Architecture

Cellular networks are often designed with electronics in mind (Chua and Yang, 1988a). These networks use what is known as a dynamic model neuron. Dynamic neurons are continuously receiving input and producing continuous output. A dynamic neuron is presented in Figure 37.

Training Cellular Network

Figure 36. Example of Annealing

Figure 37 has been modified slightly, from that shown in Figure 16, so that the terminology of this chapter can be more easily understood. Figure 37 shows neuron i, j , receiving input from positions k, l . V_{xij} refers to the internal state of the neuron, and V_{yij} refers to the output from the neuron. V_{ykl} is the output from neurons at k, l . V_{ykl} is adjusted by the weights $A(i, j, k, l)$. A is known as the feedback control. V_{ukl} is the external input to the network, and is adjusted by $B(i, j, k, l)$, known as

Figure 37. Dynamic Model Neuron

the input control. C and R_x are parameters of the neuron. I can be thought of as a threshold or bias. In equation form Figure 37 translates into,

$$C \frac{dV_{xij}(t)}{dt} = -\frac{1}{R_x} V_{xij}(t) + \sum_{k,l} A(i,j,k,l) V_{ykl}(t) + \sum_{k,l} B(i,j,k,l) V_{ukl}(t) + I \quad (30)$$

$f(\cdot)$ is the transfer function used by the neuron. For this work the transfer function will be linear between -1 and 1, see Equation 4.

These neurons are placed in arrays and connected to other neurons within the neighborhood. Figure 38 shows a 4 x 4 cellular network connected using a neighborhood of 1. The lines represent two way connections.

If the input to the network is used only to start the network at $t = 0$, then $B = 0$ and $V_{ykl}(0)$ should equal the input.

VI.4 Testing of Cellular

The first attempt was to train a large network ($5 \times 100 \times 100$ neurons) connected with a neighborhood of size 4. Each of the 5 layers would be trained to determine the

Figure 38. Cellular Network

centroid of a different size spot. That at steady state the value of the neuron at the centroid of the spot would have a value of 1.0 and otherwise have a value of -1.0. It should be recognized that the value of the neurons would probably be in proportion to how close to the centroid they were located. Then, the neuron with the highest value would be considered to be at the the centroid. Every neuron would have the same weights as all others on its layer. This is done to make the network learn a general rule for determining a spot location and not to learn where the specific training spots are located. A neighborhood of size 4 would consist of 81 connections to other neurons, including a feed back loop to itself. Each of these connection would normally require its on weight. However, this network was setup with 15 independent weights, that

Figure 39. Symmetrically Applied Weights

would be symmetrically applied to the neighborhood Figure 39. This figure shows the relative position of the 15 weights. Spots are generally round, thus it was decided that a few symmetrically applied weights would suffice for spot identification. This can be perceived as changing $wts(r, \theta)$ to $wts(r)$. This change would have two effects. First, it would speed up the training time by reducing the number of independent weights from 81 to 15. Second, the value of neurons could be affected by the roundness of a spot, which if successful may be helpful as a new parameter used by the tracking routines. Further, all the neurons would be excitatory in nature with no threshold. Later work may test how these improve may affect the network.

It was quickly realized that training a large cellular network would be time consuming. There would be 5 layers each consisting of a 100 x 100 array of neurons, thus 50,000 neurons. Each neuron would be connected to other neurons (including a

feedback loop to itself) with 81 weights. Thus there would be over 4 million computations per pass. Further, the cellular network used here must come to a steady state condition, requiring an iteration scheme. A limit was set on how many iterations would be allowed for the network to converge. If the network had not converged by this limit, then the network was treated as if it were diverging and new weights would be determined. The limit initially used was 1,000 iterations and the convergence tolerance was set at 0.01. Thus, the network could make over 4 billion computations per pass. Add to this fact that annealing is a notoriously slow process, and it can be seen that even the fastest computer would not finish training in a reasonable time. It was started on a HP750 workstation dedicated to this task, and it was determined that the network would finish training in approximately 1300 years. When this determination was made, the program was terminated.

The network had to be modified to speed the training time. This required some modifications not only in the number of neurons but in what the output would represent. Above, each of 5 layers was to recognize the centroid of different sized spots. The first modification was to reduce the number of layers to only 1. This neurons in this layer would be trained to identify the centroid of any size spot. This would cause the loss of the roundness parameter mentioned above, but the neurons would retain enough information about the spots (i.e. size and centroid) for the tracking programs. The second modification was to reduce the training set size. Now, the input to the network would consist of the 9 x 9 matrices shown in Figures 19 and 23. Further, the layer would consist of only a 9 x 9 array of neurons. Each of the input matrices would be given to the network as an impulse. After the input was given, the

network would iterate to a steady state solution. Then the next input matrix would be given to the network, and so on. The *rms* would be calculated for the entire set of matrices. The *rms* will range from 0 (perfect) to 2 (very poor). Further, in an attempt to make the network emphasize on the centroids, the *rms* is weighted so that the network will learn what is a spot with equal force as what is not a spot. The third modification was to reduce the iteration limit from 1.000 to 100.

The network was run on a HP750 workstation and required roughly 5 days to complete. The results are shown in Figure 40. As can be easily seen, the annealing failed to reach a minimum. The long periods where the *rms* is flat can be explained by the iteration limit imposed when the network is attempting to converge. If the network reaches this limit, the new weight is replaced with the old weight, the *rms* is held constant, and the annealing process continues.

These results were not encouraging. A future attempt may be made at training this network without annealing. There are many methods for minimizing a function. Although, most of these methods present a greater danger that the network would obtain only a local minimum, they could be used to show how effective the network is at spot identification.

Training Cellular Network

Figure 40. Annealing of the Cellular Network

CHAPTER VII

CONCLUSIONS

VII.1 Particle Image Velocimetry

Advances in lasers, computers and cameras have steadily improved the results achieved through particle image velocimetry (PIV). In recent years advances in tracking algorithms have further increased the reliability and speed at which raw imager data can be made in vector fields. The step between taking a picture and tracking the seeds has also been improving. Currently, research is being done to use neural networks in this regard.

The need for a new method of identifying tracer seeds is impelling. Current methods work only in limited situations. No method had been proposed which will identify seeds under a wide range of imager data. The imager data can be very clean in one experiment or due to the object of interest very noisy.

Global thresholding can work in images where the noise is low and the tracers are sharp. If noise is high or the tracers faint this method can have serious trouble. Further, if the grey levels in the image are not steady throughout the image, this method will fail.

Local thresholding can work in many cases that Global thresholding will fail. It only requires that the seeds be noticeably brighter than the background. The problems arise with the setting of the threshold. What grey level differential should be used

to determine a seed? How large should the local area be set? These are examples of questions which must be answered through trial and error for each image. One set of parameters need not work for other images. Further, many seeds may not have a large grey level gradient, causing the algorithm to fail to identify them.

This report presented a $\frac{1}{\sqrt{2}}$ function for use in discriminating seeds from within bubble coronas. Its application was presented in Figures 12 and 13. These results demonstrated a significant improvement in the tracer identification. However, this function can only be used for a limited type of image. Further, it currently involves operator assistance in producing the parameters of the function. It is desirable to produce an identification method which would be able to identify tracer seeds through a large range of images without operator assistance. Future research could reduce the operator assistance required to adjust the $\frac{1}{\sqrt{2}}$ routine and improve its response to less than ideal coronas.

VII.2 Backpropagation

Backpropagation is a training algorithm used for multi-layer perceptrons. Architectures were tested which employed 9 x 9 neuron input layer connected fully to a 6 neuron output layer. Each of the output neurons was to represent a different size seed. This architecture was not capable of determining the seed centroids.

Different input was tested. A 9 x 9 matrix and a modified vector were applied as input. The vector was produced from the matrix and fed to a modified input layer consisting of 6 neurons. A six neuron hidden layer was also added. This architecture was capable of recognizing the seeds when shown individually to the network,

but when shown a synthetic 100 x 100 image of grey levels with seeds randomly distributed, it was only capable of determining the seeds approximate position, but was not able to discriminate the centroid as accurately as required.

The importance of the parameters involved in training with backpropagation was shown to be significant. Slight alterations in the the learning rate, η , produced profoundly different results.

With further research, this architecture may be able to produce the results necessary for the tracking algorithms.

VII.3 Kohonen Networks

Competition networks such as the Kohonen networks have demonstrated their ability to perform unsupervised learning. These networks are also capable of classifying inputs into categories.

Coupling competition networks with backpropagation networks have produce results which are capable of discriminating spots. Further work will be required before the centroids can be distinguished. At this point, the centroids can be found using conventional fortran routines that decipher the output from the network.

This network was applied to a 100 x 100 synthetic image and produced accurate results. It was then given to a 1024 x 1024 experimental image. The results were encouraging. In accuracy, it competes with the global thresholding method, refer to Figures 32 - 35.

This network showed the most positive results of all of the networks studied during this research. Suggestions which might improve it are to use different input sets for training, and possibly to train on a full experimental image.

VII.4 Cellular Networks

The research into the cellular networks was attempted. However, due to the extreme time involved in the training process chosen, annealing, there was little time for encouraging results.

Annealing is very time consuming. Future research should attempt training using a more conventional optimization routine. This should speed the testing of different architectures. The current results are not satisfactory in seed identification.

There are several types of cellular networks which should be studied (i.e. Cognitron and Neocognitron, networks with inhibitory neurons).

REFERENCES

- Adrian RJ, Yao C (1984) Development of Pulsed Laser Velocimetry (PLV) for Measurement of Turbulent Flow. Proceedings of the Symposium on Turbulence, Rolla: University, Missouri, pp 170-186
- Adrian RJ, Yao C (1985) Pulsed Laser Technique Application to Liquid and Gaseous Flows and the Scattering Power of Seed Materials. *Applied Optics* 24(1):44-52
- Adrian RJ (1991) Particle-Imaging Techniques for Experimental Fluid Mechanics. to be published in the Annual Review of Fluid Mechanics, vol 23
- Anderson JA (1968) A Memory Model Utilizing Spatial Correlation Functions. *Kybernetik* 5:113-119
- Bertollini B, Oberdier L, Lee Y (1985) Image Processing System to Analyze Droplet Distributions in Sprays. *Optical Engineering* 24(3):464-469
- Blanchat TK (1991) Development of Pulsed Laser Velocimetry Techniques for Measurement of Two-Phase Interfacial Drag in a Horizontal Stratified Flow. Dissertation, Texas A&M University
- Braun MJ, Canacci VA, Russell LM (1990) Non-Intrusive Laser Based Computer Aided High Speed Flow Visualization in an Air Tunnel. 5th International Symposium on Application of Laser Techniques to Fluid Mechanics, July 9-12, Lisbon, Portugal, pp 6.1
- Carpenter GA, Grossberg S (1987a) ART 2: Self-Organization of Stable Category Recognition Codes for Analog Output Patterns. *Applied Optics* 26(23):4919-4930
- Carpenter GA, Grossberg S (1987b) A Massively Parallel Architecture for a Self-Organization Neural Pattern Recognition Machine. *Computer Vision, Graphics, and Image Processing* 37:54-115
- Cenedese A, Romano GP, Paglialunga A, Terlizzi M (1992) Neural Net for Trajectories Recognition in a Flow. Sixth International Symposium on Applications of Laser Techniques to Fluid Mechanics, Lisbon, Portugal, July 20-23, pp 27.1.1-27.1.5.
- Chua LO, Yang L (1988a) Cellular Neural Networks: Theory. *IEEE Transactions on Circuits and Systems* 35(10):1257-1272
- Chua LO, Yang L (1988b) Cellular Neural Networks: Applications. *IEEE Transactions on Circuits and Systems* 35(10):1272-1290

- Cimbala JM, Sathianathan D (1988) Streakline Flow visualization with Neutron Radiography. *Experiments in Fluids* 6:547-552
- Cohen RS (1970) Ernst Mach: Physics, Perception, and the Philosophy of Science. In "Ernst Mach, Physicist and Philosopher". Boston Studies in the Philosophy of Science, Vol. VI Reidel, Dordrecht-Holland.
- Fuchs A, Haken H (1987) Pattern Recognition and Associative Memory as Dynamical Processes in Nonlinear Systems. In: Caudill M, Butler C (ed) *Proceedings of the IEEE First International Conference on Neural Networks* SOS Printing, San Diego, California I:217-224
- Fukushima K (1975) Cognitron: A Self-Organizing Multilayered Neural Network. *Biological Cybernetics* 20:121-136
- Fukushima K (1980) Neocognitron: A Self-Organizing Neural Network Model for a Mechanism of Pattern Recognition Unaffected by Shift in Position. *Biological Cybernetics* 36:193-202
- Gonzalez RC, Wintz P (1987) *Digital Image Processing, Second Edition*. Addison-Wesley, Reading, Massachusetts
- Graham N (1981) The Visual System Does a Crude Fourier Analysis of Patterns. In: Grossberg S (ed) *Mathematical Psychology and Psychophysiology*, SIAM-AMS proceedings, Symposium in Applied Mathematics, New York 13:1-16
- Grossberg S (1976a) Adaptive Pattern Classification and Universal Recording, I: Parallel Development and Coding of Neural Feature Detectors. *Biological Cybernetics* 23:121-134
- Grossberg S, Marshall J (1987) A Computational Model of How Cortical Complex Cells Multiplex Information About Position, Contrast, Orientation, Spatial Frequency, and Disparity. *IEEE First International Conference on Neural Networks*, San Diego, California, June 21-24 IV:203-213
- Grossberg S, Mingolla E (1987) A Neural Network Architecture for Preattentive Vision: Multiple Scale Segmentation and Regularization. *IEEE First International Conference on Neural Networks*, San Diego, California, June 21-24 IV:177-184
- Grossberg S, Todorović D (1987) A Neural Network Architecture for Brightness Perception Under Constant and Variable Illumination Conditions. *IEEE First International Conference on Neural Networks*, San Diego, California, June 21-24 IV:185-192

- Hassan Y, Blanchat T, Hild R (1990) Full-Field Velocity Imaging Technique Using High-Energy Pulsed Laser Velocimetry. Image Processing Algorithms and Techniques. Proceedings of the SPIE 1244:130-142
- Hassan Y, Blanchat T (1991) Flow Velocity Measurements using Digital Image Pulsed Laser Velocimetry. Optical Engineering 30(8):1220-1227
- Hassan YA, Blanchat TK, Seeley Jr. CH, Canaan RE (1992a) Simultaneous Velocity Measurements of Both Components of a Two Phase Flow Using Particle Image Velocimetry. International Journal of Multiphase Flow 18(3):371-395
- Hassan YA, Blanchat TK, Seeley Jr. CH (1992b) PIV Flow Visualization using Particle Tracking Techniques. Journal of Measurement Science and Technology 3:633-642
- Hecht-Nielsen R (1987a) Neurocomputer Applications. National Computer Conference. pp 240-244
- Hecht-Nielsen R (1987b) Counterpropagation Networks. Applied Optics 26(23):4979-4984
- Hild R (1989) Single Phase Flow Visualization Using Digital Pulsed Laser Velocimetry. Thesis. Texas A&M University
- Hodgkin, Huxley (1952) A Quantitative Description of Membrane Current and Its Applications to Conduction and Excitation in Nerve. Journal of Physiology 117:500-544
- Horn BKP (1986) Robot Vision. McGraw-Hill, New York
- Karbacher S (1990) Associative Object Recognition by Hierarchic Template Matching. Optical Engineering 29(12):1449-1457
- Kobayashi T, Yoshitake Y, Saga T, Segawa S (1985) An Image Processing Technique for Determining Two-Dimensional Flow Fields with Reverse Flow. The Joint ASCE/ASME Mechanics Conference, International Symposium on Physical and Numerical Flow Visualization, FED 22:39-46
- Kohonen T (1982) Self-Organized Formation of Topology Correct Feature Maps. Biological Cybernetics 43:59-69
- Kohonen T (1990) The Self-Organizing Map. Proceedings of the IEEE 78(9):1464-1480

- Kosko B (1987) Adaptive Bidirectional Associative Memories. *Applied Optics* 26(23):4947-4960
- Lippmann RP (1987) An Introduction to Computing with Neural Nets. *IEEE ASSP Magazine*, April, pp 4-22
- Mach E (1943) Popular Scientific Lectures. translation by TJ McCormock. 5th ed., Open Court, La Salle, Illinois.
- Von der Malsburg C (1973) Self-Organizing Orientation Sensitive Cells in the Striate Cortex. *Kybernetik* 14:85-100
- Matsumoto T, Chua LO, Suzuki H (1990a) CNN Cloning Template: Connected Component Detector. *IEEE Transactions on Circuits and Systems* 37(5):633-635
- Matsumoto T, Chua LO, Furukawa R (1990b) CNN Cloning Template: Hole-Filler. *IEEE Transactions on Circuits and Systems* 37(5):635-638
- Matsumoto T, Chua LO, Yokohama T (1990c) Image Thinning with a Cellular Neural Network. *IEEE Transactions on Circuits and Systems* 37(5):638-640
- Melton LA, Murray AM, Verdieck JF (1986) Laser fluorescence Measurements for Fuel Sprays. *Remote Sensing, SPIE* 644:40-47
- Merzkirch W (1987) Flow Visualization, second edition. Academic Press, Inc., Orlando, Florida
- Meynart R (1983) Instantaneous Velocity Field Measurements in Unsteady Gas Flow by Speckle Velocimetry. *Applied Optics* 22(4):535-540
- Meynart R, Simpkins PG, Dudderar TD (1987) Speckle Measurements of Convection in a Liquid Cooled from Above. *Journal of Fluid Mechanics*, 178:1-20
- Nasrabadi NM, Feng Y (1987) Vector Quantization of Images Based Upon the Kohonen Self-Organizing Feature Maps. *Proceedings of the IEEE First International Conference on Neural Networks, San Diego, California* 1:101-108
- Oja E, Kohonen T (1987) The Subspace Learning Algorithm as a Formalism for Pattern Recognition and Neural Networks. In: Cudill M, Butler C (ed) *Proceedings of the IEEE First International Conference on Neural Networks*. SOS Printing, San Diego, California 1:277-284
- Pawlicki T (1988) NORA: Neural-Network Object Recognition Architecture. *Proceedings of the 1988 Connectionist Models Summer School, San Mateo, California*, pp 444-451

- Philips ML, Steele NF (1989) Nondestructive Evaluation Using Neural Networks. In: Agnihotri NK (ed) Nuclear Plant Journal. Agnihotri NK, Glen Ellyn, Illinois, pp.444-451
- Reber WL, Lyman J (1987) An Artificial Neural System Design for Rotation and Scale Invariant Pattern Recognition. IEEE First International Conference on Neural Networks, San Diego, California, June 21-24 IV:277-283
- Rogers SK, Kabrisky M (1991) An Introduction to Biological and Artificial Neural Networks for Pattern Recognition. Tutorial Texts in Optical Engineering, Vol. TT4. SPIE—The International Society for Optical Engineering, Bellingham, Washington
- Rosenblatt F (1958) Two Theorems of Statistical Separability in the Perceptron. In: Mechanization of Thought Processes: Proceedings of a Symposium held at the National Physical Laboratory, November 1958. H M Stationary Office, London 1:421-456
- Ruck DW, Rogers SK, Kabrisky M (1990) Feature Selection Using a Multilayer Perceptron. Journal of Neural Network Computing, Fall, pp 40-48
- Settles GS (1986) Modern Developments in Flow Visualization. AIAA Journal, 24(8):1313-1323
- Stark L, Okajima M, Whipple GH (1962) Computer Pattern Recognition Techniques: Electrocardiographic Diagnosis. Comm. of the ACM, October 5:527-532
- Steinbuch K, Piske UAW (1963) Learning Matrices and Their Applications. IEEE Trans. on Elect. Computers, December, EC-12(5):846-862
- Tenorio MF, Hughes CS (1987) Real Time Noisy Image Segmentation Using an Artificial Neural Network Model. IEEE First International Conference on Neural Networks, San Diego, California, June 21-24 IV:357-363
- Villalobos L, Gruber S (1990) A System for Neural Network-Based Inspection of Machined Surfaces. Journal of Neural Network Computing, Fall, pp 18-30
- Wasserman PD (1989) Neural Computing—Theory and Practice. Van Nostrand Reinhold, New York
- Widrow B, Hoff ME (1960) Adaptive Switching Circuits. In IRE WESCON, August, pp 96-104

Yang H, Guest CC (1987) Performance of Backpropagation for Rotation Invariant Pattern Recognition. IEEE First International Conference on Neural Networks. San Diego, California, June 21-24 IV:365-370

Supplementary Sources Consulted

Adrian R (1984) Scattering Particle Characteristics and their Effect on Pulsed Laser Measurements of fluid Flow: Speckle Velocimetry vs Particle Image Velocimetry. Applied Optics 23(11):1690-1691

Adrian RJ (1986) Image Shifting Technique to Resolve Directional Ambiguity in Double-Pulsed Velocimetry. Applied Optics 25(21):3855-3858

Adrian RJ, Yao CS (1987) Power Spectra of Fluid Velocities Measured by Laser Doppler Velocimetry. Experiments in Fluids 5:17-28

Chen DJ, Chiang FP (1990) Digital Processing of Young's Fringe in Speckle Photography. Optical Engineering 29(11):1413-1420

Economikos L (1988) Image Processing and Analysis of Colored Particle Motions in Turbulent Flow. Dissertation, Ohio State University

Frison T W (1990) Predicting Nonlinear and Chaotic Systems Behavior Using Neural Networks. Journal of Neural Network Computing 2(2):31-39

Grossberg S (1969) Some Networks That Can Learn, Remember, and Reproduce Any Number of Complicated Space-Time Patterns. I. Journal of Mathematics and Mechanics 19(1):53-91

Grossberg S (1976b) Adaptive Pattern Classification and Universal Recording, II: Feedback, Expectations, Olfaction, and Illusions. Biological Cybernetics 23:187-202

Grossberg S, Levine D S (1987) Attentional Mechanisms in Neural Information Processing: Examples from Pavlovian Conditioning. IEEE First International Conference on Neural Networks, San Diego, California, June 21-24 IV:49-57

Kalman RE (1968) On the Mathematics of Model Building. In: Caianiello ER (ed) Neural Networks; Proceedings of the School on Neural Networks. June, Ravello, Italy, Springer-Verlag, pp 170-177

- Kansa EJ (1990a) Multiquadrics - A Scattered Data Approximation Scheme with Applications to Computational Fluid-Dynamic - I. Surface Approximations and Particle Derivative Estimates. *Computers Math. Applications* 19(8/9):127-145
- Kansa EJ (1990b) Multiquadrics - A Scattered Data Approximation Scheme with Application to Computational Fluid-Dynamic - II. Solutions to Parabolic, Hyperbolic and Elliptic Partial Differential Equations. *Computers Math. Applications* 19(8/9):147-161
- Kobayashi T, Saga T, Segawa S (1986) Some Considerations on Automated Image Processing of Pathline Photographs. *Proceedings of the Fourth International Symposium on Flow Visualization*, Paris, France pp 241
- Landreth CC, Adrian RJ (1988) Measurement of Refinement of Velocity Data Using High Image Density Analysis in Particle Image Velocimetry. *Applications of Laser Anemometry to Fluid Mechanics*, 4th International Symposium, Lisbon, Portugal, July 11-14, pp 484-497
- Levy JC (1968) Statistical Approach to the Study of Neural Networks. In: Caianiello ER (ed) *Neural Networks; Proceedings of the School on Neural Networks*, June, Ravello, Italy, Springer-Verlag, pp 170-177
- Lourenco L, Krothapalli A (1986) The Role of Photographic Parameters in Laser Speckle or Particle Image Displacement Velocimetry. *Experiments in Fluids* 5:29-32
- de Luca A, Ricciardi LM (1968) Probabilistic Description of Neurons. In: Caianiello ER (ed) *Neural Networks; Proceedings of the School on Neural Networks*, June, Ravello, Italy, Springer-Verlag, pp 170-177.
- Meynart R (1983) Speckle Velocimetry: An Application of Image Analysis Techniques to the Measurement of Instantaneous Velocity Fields in Unsteady Flow. *ICIASF'83 Record*, New York, IEEE pp 30-36
- Mead C (1989) *Analog VLSI and Neural Systems*. Addison-Wesley Publishing Company, Reading, Massachusetts
- Mueller P, Spiro P, Blackman D, Furman RE (1987) Neural Computation of Visual Images. *IEEE First International Conference on Neural Networks*, San Diego, California, June 21-24 IV:75-88
- Narcowich FJ, Ward JD (1990) Norms of Inverses and Condition Numbers for Matrices Associated with Scattered Data. *Journal of Approximation Theory* 64(1):69-94

- Prenel JP, Porcar R, El Rhassouli A (1989) Three-Dimensional Flow Analysis by Means of Sequential and Volumic Laser Sheet Illumination. *Experiments in Fluids* 7:133-137
- Racca RG, Dewey JM (1988) A Method for Automatic Particle Tracking in a Three-Dimensional Flow Field. *Experiments in Fluids* 6:25-32
- Rodríguez-Vázquez A, Domínguez-Castro R, Rueda A, Huertas JL, Sánchez-Sinocio E (1990) Nonlinear Switched-Capacitor Neural Networks for Optimization Problems. *IEEE Transactions on Circuits and Systems*, March 37(3):384-387
- Seeley Jr. CH, Blanchat TK, Hassan YA (1991) Analysis of Particle-Tracking Techniques for Particle Image Velocimetry. *ANS Transactions* 64:29-31
- Self K (1990) Designing with Fuzzy Logic. *IEEE Spectrum*, November, pp 42-44, 105.
- Sontag ED, Sussmann HJ (1991) Back Propagation Separates Where Perceptrons Do. *Neural Networks* 4:243-349
- Williams RJ (1987) On the Use of Backpropagation in Associative Reinforcement Learning. In: Caudill M, Butler C (ed) *Proceedings of the IEEE First International Conference on Neural Networks*. SOS Printing, San Diego, California 1:263-270
- Wang Y, Cruz Jr JB, Mulligan Jr JH (1990) Two Coding Strategies for Bidirectional Associative Memory. *IEEE Transactions on Neural Networks*, March, 1(1):81-92
- Xu X, Tsai WT (1991) Effective Neural Algorithms for the Traveling Salesman Problem. *Neural Networks*, 4:193-205

END

DATE
FILMED

6 / 25 / 93